

# [MS-OXPROPS]:

## Exchange Server Protocols Master Property List

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

**Support.** For questions and support, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

## Revision Summary

Date	Revision History	Revision Class	Comments
4/4/2008	0.1	New	Initial Availability.
4/25/2008	0.2	Minor	Revised and updated property names and other technical content.
6/27/2008	1.0	Major	Initial Release.
8/6/2008	1.01	Minor	Updated references to reflect date of initial release.
9/3/2008	1.02	Minor	Changed title of document.
10/1/2008	1.03	Minor	Revised and edited technical content.
12/3/2008	1.04	Minor	Revised and edited technical content.
2/4/2009	1.05	Minor	Revised and edited technical content.
3/4/2009	1.06	Minor	Revised and edited technical content.
4/10/2009	2.0	Major	Updated technical content and applicable product releases.
7/15/2009	3.0	Major	Revised and edited for technical content.
11/4/2009	4.0.0	Major	Updated and revised the technical content.
2/10/2010	5.0.0	Major	Updated and revised the technical content.
5/5/2010	6.0.0	Major	Updated and revised the technical content.
8/4/2010	7.0	Major	Significantly changed the technical content.
11/3/2010	8.0	Major	Significantly changed the technical content.
3/18/2011	9.0	Major	Significantly changed the technical content.
8/5/2011	10.0	Major	Significantly changed the technical content.
10/7/2011	11.0	Major	Significantly changed the technical content.
1/20/2012	12.0	Major	Significantly changed the technical content.
4/27/2012	13.0	Major	Significantly changed the technical content.
7/16/2012	13.1	Minor	Clarified the meaning of the technical content.
10/8/2012	14.0	Major	Significantly changed the technical content.
2/11/2013	15.0	Major	Significantly changed the technical content.
7/26/2013	16.0	Major	Significantly changed the technical content.
11/18/2013	16.0	None	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	16.0	None	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	16.1	Minor	Clarified the meaning of the technical content.
7/31/2014	16.2	Minor	Clarified the meaning of the technical content.

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
10/30/2014	16.3	Minor	Clarified the meaning of the technical content.
3/16/2015	17.0	Major	Significantly changed the technical content.
5/26/2015	17.1	Minor	Clarified the meaning of the technical content.
9/14/2015	18.0	Major	Significantly changed the technical content.
6/13/2016	19.0	Major	Significantly changed the technical content.
9/14/2016	19.0	None	No changes to the meaning, language, or formatting of the technical content.
10/13/2017	20.0	Major	Significantly changed the technical content.
12/12/2017	20.0	None	No changes to the meaning, language, or formatting of the technical content.
7/24/2018	21.0	Major	Significantly changed the technical content.
10/1/2018	22.0	Major	Significantly changed the technical content.
3/19/2019	23.0	Major	Significantly changed the technical content.
6/18/2019	24.0	Major	Significantly changed the technical content.
8/18/2020	25.0	Major	Significantly changed the technical content.
4/22/2021	26.0	Major	Significantly changed the technical content.
8/17/2021	27.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1</b>	<b>Introduction .....</b>	<b>24</b>
1.1	Glossary .....	24
1.2	References .....	32
1.2.1	Normative References .....	32
1.2.2	Informative References .....	34
1.3	Overview .....	34
1.3.1	Common Message Classes .....	36
1.3.2	Commonly Used Property Sets .....	37
1.3.3	Property ID Ranges.....	38
1.3.4	WebDAV Property Naming .....	39
1.3.4.1	http://schemas.microsoft.com/mapi/proptag Namespace.....	39
1.3.4.2	http://schemas.microsoft.com/mapi/id Namespace .....	39
1.3.4.3	http://schemas.microsoft.com/mapi/string Namespace .....	40
1.4	Relationship to Protocols and Other Structures .....	40
1.5	Applicability Statement .....	40
1.6	Versioning and Localization .....	40
1.7	Vendor-Extensible Fields .....	41
<b>2</b>	<b>Structures .....</b>	<b>42</b>
2.1	PidLidAddressBookProviderArrayType .....	42
2.2	PidLidAddressBookProviderEmailList .....	42
2.3	PidLidAddressCountryCode .....	42
2.4	PidLidAgingDontAgeMe .....	42
2.5	PidLidAllAttendeesString .....	43
2.6	PidLidAllowExternalCheck .....	43
2.7	PidLidAnniversaryEventEntryId .....	44
2.8	PidLidAppointmentAuxiliaryFlags .....	44
2.9	PidLidAppointmentColor .....	44
2.10	PidLidAppointmentCounterProposal .....	44
2.11	PidLidAppointmentDuration .....	45
2.12	PidLidAppointmentEndDate.....	45
2.13	PidLidAppointmentEndTime .....	45
2.14	PidLidAppointmentEndWhole .....	46
2.15	PidLidAppointmentLastSequence .....	46
2.16	PidLidAppointmentMessageClass .....	46
2.17	PidLidAppointmentNotAllowPropose .....	47
2.18	PidLidAppointmentProposalNumber .....	47
2.19	PidLidAppointmentProposedDuration .....	47
2.20	PidLidAppointmentProposedEndWhole.....	48
2.21	PidLidAppointmentProposedStartWhole .....	48
2.22	PidLidAppointmentRecur .....	48
2.23	PidLidAppointmentReplyName .....	49
2.24	PidLidAppointmentReplyTime.....	49
2.25	PidLidAppointmentSequence .....	50
2.26	PidLidAppointmentSequenceTime .....	50
2.27	PidLidAppointmentStartDate .....	50
2.28	PidLidAppointmentStartTime.....	51
2.29	PidLidAppointmentStartWhole.....	51
2.30	PidLidAppointmentStateFlags.....	51
2.31	PidLidAppointmentSubType .....	52
2.32	PidLidAppointmentTimeZoneDefinitionEndDisplay .....	52
2.33	PidLidAppointmentTimeZoneDefinitionRecur .....	52
2.34	PidLidAppointmentTimeZoneDefinitionStartDisplay .....	53
2.35	PidLidAppointmentUnsendableRecipients .....	53
2.36	PidLidAppointmentUpdateTime.....	53

2.37	PidLidAttendeeCriticalChange.....	54
2.38	PidLidAutoFillLocation .....	54
2.39	PidLidAutoLog .....	54
2.40	PidLidAutoProcessState .....	55
2.41	PidLidAutoStartCheck .....	55
2.42	PidLidBilling.....	55
2.43	PidLidBirthdayEventEntryId .....	56
2.44	PidLidBirthdayLocal .....	56
2.45	PidLidBusinessCardCardPicture .....	56
2.46	PidLidBusinessCardDisplayDefinition .....	56
2.47	PidLidBusyStatus .....	57
2.48	PidLidCalendarType .....	57
2.49	PidLidCategories .....	58
2.50	PidLidCcAttendeesString .....	58
2.51	PidLidChangeHighlight .....	58
2.52	PidLidClassification .....	58
2.53	PidLidClassificationDescription .....	59
2.54	PidLidClassificationGuid.....	59
2.55	PidLidClassificationKeep .....	59
2.56	PidLidClassified .....	60
2.57	PidLidCleanGlobalObjectId.....	60
2.58	PidLidClientIntent.....	60
2.59	PidLidClipEnd.....	61
2.60	PidLidClipStart .....	61
2.61	PidLidCollaborateDoc .....	61
2.62	PidLidCommonEnd .....	62
2.63	PidLidCommonStart.....	62
2.64	PidLidCompanies.....	62
2.65	PidLidConferencingCheck .....	63
2.66	PidLidConferencingType .....	63
2.67	PidLidContactCharacterSet .....	63
2.68	PidLidContactItemData .....	64
2.69	PidLidContactLinkedGlobalAddressListEntryId .....	64
2.70	PidLidContactLinkEntry .....	64
2.71	PidLidContactLinkGlobalAddressListLinkId .....	65
2.72	PidLidContactLinkGlobalAddressListLinkState .....	65
2.73	PidLidContactLinkLinkRejectHistory .....	65
2.74	PidLidContactLinkName.....	66
2.75	PidLidContactLinkSearchKey .....	66
2.76	PidLidContactLinkSMTPAddressCache.....	66
2.77	PidLidContacts .....	66
2.78	PidLidContactUserField1 .....	67
2.79	PidLidContactUserField2 .....	67
2.80	PidLidContactUserField3 .....	68
2.81	PidLidContactUserField4 .....	68
2.82	PidLidConversationActionLastAppliedTime .....	68
2.83	PidLidConversationActionMaxDeliveryTime .....	69
2.84	PidLidConversationActionMoveFolderEid .....	69
2.85	PidLidConversationActionMoveStoreEid .....	69
2.86	PidLidConversationActionVersion .....	70
2.87	PidLidConversationProcessed .....	70
2.88	PidLidCurrentVersion .....	70
2.89	PidLidCurrentVersionName .....	71
2.90	PidLidDayInterval .....	71
2.91	PidLidDayOfMonth .....	71
2.92	PidLidDelegateMail .....	72
2.93	PidLidDepartment.....	72
2.94	PidLidDirectory .....	72

2.95	PidLidDistributionListChecksum .....	72
2.96	PidLidDistributionListMembers .....	73
2.97	PidLidDistributionListName .....	73
2.98	PidLidDistributionListOneOffMembers .....	73
2.99	PidLidDistributionListStream .....	74
2.100	PidLidEmail1AddressType .....	74
2.101	PidLidEmail1DisplayName .....	74
2.102	PidLidEmail1EmailAddress .....	75
2.103	PidLidEmail1OriginalDisplayName .....	75
2.104	PidLidEmail1OriginalEntryId .....	75
2.105	PidLidEmail2AddressType .....	76
2.106	PidLidEmail2DisplayName .....	76
2.107	PidLidEmail2EmailAddress .....	76
2.108	PidLidEmail2OriginalDisplayName .....	77
2.109	PidLidEmail2OriginalEntryId .....	77
2.110	PidLidEmail3AddressType .....	77
2.111	PidLidEmail3DisplayName .....	78
2.112	PidLidEmail3EmailAddress .....	78
2.113	PidLidEmail3OriginalDisplayName .....	78
2.114	PidLidEmail3OriginalEntryId .....	79
2.115	PidLidEndRecurrenceDate .....	79
2.116	PidLidEndRecurrenceTime .....	79
2.117	PidLidExceptionReplaceTime .....	80
2.118	PidLidFax1AddressType .....	80
2.119	PidLidFax1EmailAddress .....	80
2.120	PidLidFax1OriginalDisplayName .....	80
2.121	PidLidFax1OriginalEntryId .....	81
2.122	PidLidFax2AddressType .....	81
2.123	PidLidFax2EmailAddress .....	81
2.124	PidLidFax2OriginalDisplayName .....	82
2.125	PidLidFax2OriginalEntryId .....	82
2.126	PidLidFax3AddressType .....	82
2.127	PidLidFax3EmailAddress .....	83
2.128	PidLidFax3OriginalDisplayName .....	83
2.129	PidLidFax3OriginalEntryId .....	83
2.130	PidLidFExceptionalAttendees .....	83
2.131	PidLidFExceptionalBody .....	84
2.132	PidLidFileUnder .....	84
2.133	PidLidFileUnderId .....	84
2.134	PidLidFileUnderList .....	85
2.135	PidLidFInvited .....	85
2.136	PidLidFlagRequest .....	85
2.137	PidLidFlagString .....	86
2.138	PidLidForwardInstance .....	86
2.139	PidLidForwardNotificationRecipients .....	86
2.140	PidLidFOthersAppointment .....	87
2.141	PidLidFreeBusyLocation .....	87
2.142	PidLidGlobalObjectId .....	87
2.143	PidLidHasPicture .....	88
2.144	PidLidHomeAddress .....	88
2.145	PidLidHomeAddressCountryCode .....	88
2.146	PidLidHtml .....	89
2.147	PidLidICalendarDayOfWeekMask .....	89
2.148	PidLidInboundICalStream .....	89
2.149	PidLidInfoPathFormName .....	90
2.150	PidLidInstantMessagingAddress .....	90
2.151	PidLidIntendedBusyStatus .....	90
2.152	PidLidInternetAccountName .....	91

2.153	PidLidInternetAccountStamp	91
2.154	PidLidIsContactLinked	91
2.155	PidLidIsException	92
2.156	PidLidIsRecurring	92
2.157	PidLidIsSilent	92
2.158	PidLidLinkedTaskItems	93
2.159	PidLidLocation	93
2.160	PidLidLogDocumentPosted	93
2.161	PidLidLogDocumentPrinted	94
2.162	PidLidLogDocumentRouted	94
2.163	PidLidLogDocumentSaved	94
2.164	PidLidLogDuration	95
2.165	PidLidLogEnd	95
2.166	PidLidLogFlags	95
2.167	PidLidLogStart	95
2.168	PidLidLogType	96
2.169	PidLidLogTypeDesc	96
2.170	PidLidMeetingType	96
2.171	PidLidMeetingWorkspaceUrl	97
2.172	PidLidMonthInterval	97
2.173	PidLidMonthOfYear	97
2.174	PidLidMonthOfYearMask	98
2.175	PidLidNetShowUrl	98
2.176	PidLidNoEndDateFlag	98
2.177	PidLidNonSendableBcc	99
2.178	PidLidNonSendableCc	99
2.179	PidLidNonSendableTo	99
2.180	PidLidNonSendBccTrackStatus	100
2.181	PidLidNonSendCcTrackStatus	100
2.182	PidLidNonSendToTrackStatus	100
2.183	PidLidNoteColor	101
2.184	PidLidNoteHeight	101
2.185	PidLidNoteWidth	101
2.186	PidLidNoteX	102
2.187	PidLidNoteY	102
2.188	PidLidOccurrences	102
2.189	PidLidOldLocation	103
2.190	PidLidOldRecurrenceType	103
2.191	PidLidOldWhenEndWhole	103
2.192	PidLidOldWhenStartWhole	103
2.193	PidLidOnlinePassword	104
2.194	PidLidOptionalAttendees	104
2.195	PidLidOrganizerAlias	104
2.196	PidLidOriginalStoreEntryId	105
2.197	PidLidOtherAddress	105
2.198	PidLidOtherAddressCountryCode	105
2.199	PidLidOwnerCriticalChange	106
2.200	PidLidOwnerName	106
2.201	PidLidPendingStateForSiteMailboxDocument	106
2.202	PidLidPercentComplete	107
2.203	PidLidPostalAddressId	107
2.204	PidLidPostRssChannel	107
2.205	PidLidPostRssChannelLink	108
2.206	PidLidPostRssItemGuid	108
2.207	PidLidPostRssItemHash	108
2.208	PidLidPostRssItemLink	109
2.209	PidLidPostRssItemXml	109
2.210	PidLidPostRssSubscription	109

2.211	PidLidPrivate.....	109
2.212	PidLidPromptSendUpdate .....	110
2.213	PidLidRecurrenceDuration .....	110
2.214	PidLidRecurrencePattern .....	110
2.215	PidLidRecurrenceType .....	111
2.216	PidLidRecurring .....	111
2.217	PidLidReferenceEntryId .....	111
2.218	PidLidReminderDelta .....	112
2.219	PidLidReminderFileParameter.....	112
2.220	PidLidReminderOverride .....	113
2.221	PidLidReminderPlaySound .....	113
2.222	PidLidReminderSet .....	113
2.223	PidLidReminderSignalTime .....	114
2.224	PidLidReminderTime .....	114
2.225	PidLidReminderTimeDate .....	114
2.226	PidLidReminderTimeTime .....	115
2.227	PidLidReminderType .....	115
2.228	PidLidRemoteStatus.....	115
2.229	PidLidRequiredAttendees.....	116
2.230	PidLidResourceAttendees .....	116
2.231	PidLidResponseStatus .....	116
2.232	PidLidServerProcessed .....	117
2.233	PidLidServerProcessingActions .....	117
2.234	PidLidSharingAnonymity .....	117
2.235	PidLidSharingBindingEntryId.....	118
2.236	PidLidSharingBrowseUrl .....	118
2.237	PidLidSharingCapabilities .....	118
2.238	PidLidSharingConfigurationUrl.....	119
2.239	PidLidSharingDataRangeEnd .....	119
2.240	PidLidSharingDataRangeStart .....	119
2.241	PidLidSharingDetail .....	120
2.242	PidLidSharingExtensionXml.....	120
2.243	PidLidSharingFilter .....	120
2.244	PidLidSharingFlags .....	120
2.245	PidLidSharingFlavor .....	121
2.246	PidLidSharingFolderEntryId .....	121
2.247	PidLidSharingIndexEntryId .....	121
2.248	PidLidSharingInitiatorEntryId .....	122
2.249	PidLidSharingInitiatorName .....	122
2.250	PidLidSharingInitiatorSmtip.....	122
2.251	PidLidSharingInstanceGuid .....	123
2.252	PidLidSharingLastAutoSyncTime.....	123
2.253	PidLidSharingLastSyncTime .....	123
2.254	PidLidSharingLocalComment.....	124
2.255	PidLidSharingLocalLastModificationTime .....	124
2.256	PidLidSharingLocalName .....	124
2.257	PidLidSharingLocalPath .....	125
2.258	PidLidSharingLocalStoreUid .....	125
2.259	PidLidSharingLocalType.....	125
2.260	PidLidSharingLocalUid .....	125
2.261	PidLidSharingOriginalMessageEntryId .....	126
2.262	PidLidSharingParentBindingEntryId.....	126
2.263	PidLidSharingParticipants .....	126
2.264	PidLidSharingPermissions .....	127
2.265	PidLidSharingProviderExtension .....	127
2.266	PidLidSharingProviderGuid.....	127
2.267	PidLidSharingProviderName.....	128
2.268	PidLidSharingProviderUrl .....	128



2.269	PidLidSharingRangeEnd .....	128
2.270	PidLidSharingRangeStart.....	129
2.271	PidLidSharingReciprocation.....	129
2.272	PidLidSharingRemoteByteSize.....	129
2.273	PidLidSharingRemoteComment .....	130
2.274	PidLidSharingRemoteCrc .....	130
2.275	PidLidSharingRemoteLastModificationTime .....	130
2.276	PidLidSharingRemoteMessageCount.....	130
2.277	PidLidSharingRemoteName.....	131
2.278	PidLidSharingRemotePass .....	131
2.279	PidLidSharingRemotePath.....	131
2.280	PidLidSharingRemoteStoreUid.....	132
2.281	PidLidSharingRemoteType .....	132
2.282	PidLidSharingRemoteUid .....	132
2.283	PidLidSharingRemoteUser .....	133
2.284	PidLidSharingRemoteVersion .....	133
2.285	PidLidSharingResponseTime .....	133
2.286	PidLidSharingResponseType .....	134
2.287	PidLidSharingRoamLog .....	134
2.288	PidLidSharingStart .....	134
2.289	PidLidSharingStatus .....	135
2.290	PidLidSharingStop .....	135
2.291	PidLidSharingSyncFlags .....	135
2.292	PidLidSharingSyncInterval.....	135
2.293	PidLidSharingTimeToLive.....	136
2.294	PidLidSharingTimeToLiveAuto .....	136
2.295	PidLidSharingWorkingHoursDays .....	136
2.296	PidLidSharingWorkingHoursEnd.....	137
2.297	PidLidSharingWorkingHoursStart.....	137
2.298	PidLidSharingWorkingHoursTimeZone .....	137
2.299	PidLidSideEffects.....	138
2.300	PidLidSingleBodyICal .....	138
2.301	PidLidSmartNoAttach .....	138
2.302	PidLidSpamOriginalFolder.....	139
2.303	PidLidStartRecurrenceDate .....	139
2.304	PidLidStartRecurrenceTime.....	139
2.305	PidLidTaskAcceptanceState.....	140
2.306	PidLidTaskAccepted .....	140
2.307	PidLidTaskActualEffort .....	140
2.308	PidLidTaskAssigner .....	141
2.309	PidLidTaskAssigners .....	141
2.310	PidLidTaskComplete.....	141
2.311	PidLidTaskCustomFlags .....	142
2.312	PidLidTaskDateCompleted .....	142
2.313	PidLidTaskDeadOccurrence.....	142
2.314	PidLidTaskDueDate.....	143
2.315	PidLidTaskEstimatedEffort .....	143
2.316	PidLidTaskFCreator.....	143
2.317	PidLidTaskFFixOffline .....	144
2.318	PidLidTaskFRecurring .....	144
2.319	PidLidTaskGlobalId .....	144
2.320	PidLidTaskHistory .....	145
2.321	PidLidTaskLastDelegate.....	145
2.322	PidLidTaskLastUpdate .....	145
2.323	PidLidTaskLastUser.....	145
2.324	PidLidTaskMode .....	146
2.325	PidLidTaskMultipleRecipients.....	146
2.326	PidLidTaskNoCompute .....	146

2.327	PidLidTaskOrdinal	147
2.328	PidLidTaskOwner	147
2.329	PidLidTaskOwnership	147
2.330	PidLidTaskRecurrence	148
2.331	PidLidTaskResetReminder	148
2.332	PidLidTaskRole	148
2.333	PidLidTaskStartDate	149
2.334	PidLidTaskState	149
2.335	PidLidTaskStatus	150
2.336	PidLidTaskStatusOnComplete	150
2.337	PidLidTaskUpdates	150
2.338	PidLidTaskVersion	151
2.339	PidLidTeamTask	151
2.340	PidLidTimeZone	151
2.341	PidLidTimeZoneDescription	152
2.342	PidLidTimeZoneStruct	152
2.343	PidLidToAttendeesString	152
2.344	PidLidToDoOrdinalDate	153
2.345	PidLidToDoSubOrdinal	153
2.346	PidLidToDoTitle	153
2.347	PidLidUseTnef	154
2.348	PidLidValidFlagStringProof	154
2.349	PidLidVerbResponse	154
2.350	PidLidVerbStream	155
2.351	PidLidWeddingAnniversaryLocal	155
2.352	PidLidWeekInterval	155
2.353	PidLidWhere	156
2.354	PidLidWorkAddress	156
2.355	PidLidWorkAddressCity	156
2.356	PidLidWorkAddressCountry	157
2.357	PidLidWorkAddressCountryCode	157
2.358	PidLidWorkAddressPostalCode	157
2.359	PidLidWorkAddressPostOfficeBox	158
2.360	PidLidWorkAddressState	158
2.361	PidLidWorkAddressStreet	158
2.362	PidLidYearInterval	159
2.363	PidLidYomiCompanyName	159
2.364	PidLidYomiFirstName	159
2.365	PidLidYomiLastName	160
2.366	PidNameAcceptLanguage	160
2.367	PidNameApplicationName	160
2.368	PidNameAttachmentMacContentType	160
2.369	PidNameAttachmentMacInfo	161
2.370	PidNameAttachmentOriginalPermissionType	161
2.371	PidNameAttachmentPermissionType	161
2.372	PidNameAttachmentProviderType	162
2.373	PidNameAudioNotes	162
2.374	PidNameAuthor	162
2.375	PidNameAutomaticSpeechRecognitionData	162
2.376	PidNameBirthdayContactAttributionDisplayName	163
2.377	PidNameBirthdayContactEntryId	163
2.378	PidNameBirthdayContactPersonGuid	163
2.379	PidNameByteCount	164
2.380	PidNameCalendarAttendeeRole	164
2.381	PidNameCalendarBusystatus	164
2.382	PidNameCalendarContact	164
2.383	PidNameCalendarContactUrl	165
2.384	PidNameCalendarCreated	165

2.385	PidNameCalendarDescriptionUrl .....	165
2.386	PidNameCalendarDuration .....	166
2.387	PidNameCalendarExceptionDate .....	166
2.388	PidNameCalendarExceptionRule .....	166
2.389	PidNameCalendarGeoLatitude .....	167
2.390	PidNameCalendarGeoLongitude .....	167
2.391	PidNameCalendarInstanceType .....	167
2.392	PidNameCalendarIsOrganizer .....	167
2.393	PidNameCalendarLastModified .....	168
2.394	PidNameCalendarLocationUrl .....	168
2.395	PidNameCalendarMeetingStatus .....	168
2.396	PidNameCalendarMethod .....	169
2.397	PidNameCalendarProductId .....	169
2.398	PidNameCalendarRecurrenceIdRange .....	169
2.399	PidNameCalendarReminderOffset .....	169
2.400	PidNameCalendarResources .....	170
2.401	PidNameCalendarRsvp .....	170
2.402	PidNameCalendarSequence .....	170
2.403	PidNameCalendarTimeZone .....	171
2.404	PidNameCalendarTimeZoneId .....	171
2.405	PidNameCalendarTransparent .....	171
2.406	PidNameCalendarUid .....	172
2.407	PidNameCalendarVersion .....	172
2.408	PidNameCategory .....	172
2.409	PidNameCharacterCount .....	172
2.410	PidNameComments .....	173
2.411	PidNameCompany .....	173
2.412	PidNameContentBase .....	173
2.413	PidNameContentClass .....	174
2.414	PidNameContentType .....	174
2.415	PidNameCreateDateTimeReadOnly .....	174
2.416	PidNameCrossReference .....	175
2.417	PidNameDavId .....	175
2.418	PidNameDavIsCollection .....	175
2.419	PidNameDavIsStructuredDocument .....	176
2.420	PidNameDavParentName .....	176
2.421	PidNameDavUid .....	176
2.422	PidNameDocumentParts .....	176
2.423	PidNameEditTime .....	177
2.424	PidNameExchangeIntendedBusyStatus .....	177
2.425	PidNameExchangeJunkEmailMoveStamp .....	177
2.426	PidNameExchangeModifyExceptionStructure .....	178
2.427	PidNameExchangeNoModifyExceptions .....	178
2.428	PidNameExchangePatternEnd .....	178
2.429	PidNameExchangePatternStart .....	179
2.430	PidNameExchangeReminderInterval .....	179
2.431	PidNameExchDatabaseSchema .....	179
2.432	PidNameExchDataExpectedContentClass .....	179
2.433	PidNameExchDataSchemaCollectionReference .....	180
2.434	PidNameExtractedAddresses .....	180
2.435	PidNameExtractedContacts .....	180
2.436	PidNameExtractedEmails .....	181
2.437	PidNameExtractedMeetings .....	181
2.438	PidNameExtractedPhones .....	181
2.439	PidNameExtractedTasks .....	182
2.440	PidNameExtractedUrls .....	182
2.441	PidNameFrom .....	182
2.442	PidNameHeadingPairs .....	182

2.443	PidNameHiddenCount .....	183
2.444	PidNameHttpmailCalendar .....	183
2.445	PidNameHttpmailHtmlDescription .....	183
2.446	PidNameHttpmailSendMessage .....	184
2.447	PidNameICalendarRecurrenceDate .....	184
2.448	PidNameICalendarRecurrenceRule .....	184
2.449	PidNameInternetSubject .....	184
2.450	PidNameIsBirthdayContactWritable .....	185
2.451	PidNameKeywords.....	185
2.452	PidNameLastAuthor .....	185
2.453	PidNameLastPrinted.....	186
2.454	PidNameLastSaveDateTime .....	186
2.455	PidNameLineCount .....	186
2.456	PidNameLinksDirty .....	187
2.457	PidNameLocationUrl.....	187
2.458	PidNameManager .....	187
2.459	PidNameMeetingDoNotForward .....	187
2.460	PidNameMSIPLabels .....	188
2.461	PidNameMultimediaClipCount .....	188
2.462	PidNameNoteCount .....	188
2.463	PidNameOMSAccountGuid .....	189
2.464	PidNameOMSMobileModel.....	189
2.465	PidNameOMSScheduleTime .....	189
2.466	PidNameOMSServiceType.....	189
2.467	PidNameOMSSourceType .....	190
2.468	PidNamePageCount .....	190
2.469	PidNameParagraphCount.....	190
2.470	PidNamePhishingStamp .....	190
2.471	PidNamePresentationFormat.....	191
2.472	PidNameQuarantineOriginalSender .....	191
2.473	PidNameRevisionNumber .....	191
2.474	PidNameRightsManagementLicense .....	192
2.475	PidNameScale.....	192
2.476	PidNameSecurity.....	192
2.477	PidNameSlideCount .....	192
2.478	PidNameSubject.....	193
2.479	PidNameTemplate .....	193
2.480	PidNameThumbnail.....	193
2.481	PidNameTitle .....	194
2.482	PidNameWordCount.....	194
2.483	PidNameXCallId .....	194
2.484	PidNameXFaxNumberOfPages .....	195
2.485	PidNameXRequireProtectedPlayOnPhone .....	195
2.486	PidNameXSenderTelephoneNumber .....	195
2.487	PidNameXSharingBrowseUrl .....	195
2.488	PidNameXSharingCapabilities .....	196
2.489	PidNameXSharingConfigUrl.....	196
2.490	PidNameXSharingExendedCaps .....	196
2.491	PidNameXSharingFlavor .....	197
2.492	PidNameXSharingInstanceGuid .....	197
2.493	PidNameXSharingLocalType.....	197
2.494	PidNameXSharingProviderGuid.....	197
2.495	PidNameXSharingProviderName .....	198
2.496	PidNameXSharingProviderUrl .....	198
2.497	PidNameXSharingRemoteName.....	198
2.498	PidNameXSharingRemotePath.....	198
2.499	PidNameXSharingRemoteStoreUid.....	199
2.500	PidNameXSharingRemoteType .....	199

2.501	PidNameXSharingRemoteUid .....	199
2.502	PidNameXVoiceMessageAttachmentOrder .....	200
2.503	PidNameXVoiceMessageDuration .....	200
2.504	PidNameXVoiceMessageSenderName .....	200
2.505	PidTagAccess .....	200
2.506	PidTagAccessControlListData .....	201
2.507	PidTagAccessLevel.....	201
2.508	PidTagAccount .....	201
2.509	PidTagAdditionalRenEntryIds .....	202
2.510	PidTagAdditionalRenEntryIdsEx .....	202
2.511	PidTagAddressBookAuthorizedSenders .....	202
2.512	PidTagAddressBookContainerId .....	203
2.513	PidTagAddressBookDeliveryContentLength .....	203
2.514	PidTagAddressBookDisplayNamePrintable.....	203
2.515	PidTagAddressBookDisplayTypeExtended .....	203
2.516	PidTagAddressBookDistributionListExternalMemberCount .....	204
2.517	PidTagAddressBookDistributionListMemberCount.....	204
2.518	PidTagAddressBookDistributionListMemberSubmitAccepted .....	204
2.519	PidTagAddressBookDistributionListMemberSubmitRejected .....	205
2.520	PidTagAddressBookDistributionListRejectMessagesFromDLMembers .....	205
2.521	PidTagAddressBookEntryId .....	205
2.522	PidTagAddressBookExtensionAttribute1.....	205
2.523	PidTagAddressBookExtensionAttribute10.....	206
2.524	PidTagAddressBookExtensionAttribute11.....	206
2.525	PidTagAddressBookExtensionAttribute12.....	206
2.526	PidTagAddressBookExtensionAttribute13.....	207
2.527	PidTagAddressBookExtensionAttribute14.....	207
2.528	PidTagAddressBookExtensionAttribute15.....	207
2.529	PidTagAddressBookExtensionAttribute2.....	208
2.530	PidTagAddressBookExtensionAttribute3.....	208
2.531	PidTagAddressBookExtensionAttribute4.....	208
2.532	PidTagAddressBookExtensionAttribute5.....	208
2.533	PidTagAddressBookExtensionAttribute6.....	209
2.534	PidTagAddressBookExtensionAttribute7.....	209
2.535	PidTagAddressBookExtensionAttribute8.....	209
2.536	PidTagAddressBookExtensionAttribute9.....	210
2.537	PidTagAddressBookFolderPathname.....	210
2.538	PidTagAddressBookHierarchicalChildDepartments.....	210
2.539	PidTagAddressBookHierarchicalDepartmentMembers .....	210
2.540	PidTagAddressBookHierarchicalIsHierarchicalGroup .....	211
2.541	PidTagAddressBookHierarchicalParentDepartment .....	211
2.542	PidTagAddressBookHierarchicalRootDepartment.....	211
2.543	PidTagAddressBookHierarchicalShowInDepartments .....	212
2.544	PidTagAddressBookHomeMessageDatabase .....	212
2.545	PidTagAddressBookIsMaster .....	212
2.546	PidTagAddressBookIsMemberOfDistributionList .....	213
2.547	PidTagAddressBookManageDistributionList .....	213
2.548	PidTagAddressBookManager .....	213
2.549	PidTagAddressBookManagerDistinguishedName .....	213
2.550	PidTagAddressBookMember .....	214
2.551	PidTagAddressBookMessageId .....	214
2.552	PidTagAddressBookModerationEnabled .....	214
2.553	PidTagAddressBookNetworkAddress .....	215
2.554	PidTagAddressBookObjectDistinguishedName .....	215
2.555	PidTagAddressBookObjectGuid.....	215
2.556	PidTagAddressBookOrganizationalUnitRootDistinguishedName .....	215
2.557	PidTagAddressBookOwner .....	216
2.558	PidTagAddressBookOwnerBackLink.....	216

2.559	PidTagAddressBookParentEntryId	216
2.560	PidTagAddressBookPhoneticCompanyName	217
2.561	PidTagAddressBookPhoneticDepartmentName	217
2.562	PidTagAddressBookPhoneticDisplayName	217
2.563	PidTagAddressBookPhoneticGivenName	218
2.564	PidTagAddressBookPhoneticSurname	218
2.565	PidTagAddressBookProxyAddresses	218
2.566	PidTagAddressBookPublicDelegates	219
2.567	PidTagAddressBookReports	219
2.568	PidTagAddressBookRoomCapacity	219
2.569	PidTagAddressBookRoomContainers	219
2.570	PidTagAddressBookRoomDescription	220
2.571	PidTagAddressBookSenderHintTranslations	220
2.572	PidTagAddressBookSeniorityIndex	220
2.573	PidTagAddressBookTargetAddress	221
2.574	PidTagAddressBookUnauthorizedSenders	221
2.575	PidTagAddressBookX509Certificate	221
2.576	PidTagAddressType	222
2.577	PidTagAlternateRecipientAllowed	222
2.578	PidTagAnr	222
2.579	PidTagArchiveDate	222
2.580	PidTagArchivePeriod	223
2.581	PidTagArchiveTag	223
2.582	PidTagAssistant	223
2.583	PidTagAssistantTelephoneNumber	224
2.584	PidTagAssociated	224
2.585	PidTagAttachAdditionalInformation	224
2.586	PidTagAttachContentBase	224
2.587	PidTagAttachContentId	225
2.588	PidTagAttachContentLocation	225
2.589	PidTagAttachDataBinary	225
2.590	PidTagAttachDataObject	226
2.591	PidTagAttachEncoding	226
2.592	PidTagAttachExtension	226
2.593	PidTagAttachFilename	227
2.594	PidTagAttachFlags	227
2.595	PidTagAttachLongFilename	227
2.596	PidTagAttachLongPathname	228
2.597	PidTagAttachmentContactPhoto	228
2.598	PidTagAttachmentFlags	228
2.599	PidTagAttachmentHidden	229
2.600	PidTagAttachmentLinkId	229
2.601	PidTagAttachMethod	229
2.602	PidTagAttachMimeType	229
2.603	PidTagAttachNumber	230
2.604	PidTagAttachPathname	230
2.605	PidTagAttachPayloadClass	230
2.606	PidTagAttachPayloadProviderGuidString	231
2.607	PidTagAttachRendering	231
2.608	PidTagAttachSize	231
2.609	PidTagAttachTag	232
2.610	PidTagAttachTransportName	232
2.611	PidTagAttributeHidden	232
2.612	PidTagAttributeReadOnly	233
2.613	PidTagAutoForwardComment	233
2.614	PidTagAutoForwarded	233
2.615	PidTagAutoResponseSuppress	233
2.616	PidTagBirthday	234

2.617	PidTagBlockStatus.....	234
2.618	PidTagBody .....	234
2.619	PidTagBodyContentId .....	235
2.620	PidTagBodyContentLocation.....	235
2.621	PidTagBodyHtml.....	235
2.622	PidTagBusiness2TelephoneNumber.....	236
2.623	PidTagBusiness2TelephoneNumbers .....	236
2.624	PidTagBusinessFaxNumber .....	236
2.625	PidTagBusinessHomePage .....	237
2.626	PidTagBusinessTelephoneNumber .....	237
2.627	PidTagCallbackTelephoneNumber .....	237
2.628	PidTagCallId .....	238
2.629	PidTagCarTelephoneNumber .....	238
2.630	PidTagCdoRecurrenceid.....	238
2.631	PidTagChangeKey .....	238
2.632	PidTagChangeNumber.....	239
2.633	PidTagChildrensNames.....	239
2.634	PidTagClientActions .....	239
2.635	PidTagClientSubmitTime .....	240
2.636	PidTagCodePageId .....	240
2.637	PidTagComment.....	240
2.638	PidTagCompanyMainTelephoneNumber .....	241
2.639	PidTagCompanyName .....	241
2.640	PidTagComputerNetworkName.....	241
2.641	PidTagConflictEntryId .....	242
2.642	PidTagContainerClass .....	242
2.643	PidTagContainerContents .....	242
2.644	PidTagContainerFlags .....	243
2.645	PidTagContainerHierarchy .....	243
2.646	PidTagContentCount.....	243
2.647	PidTagContentFilterSpamConfidenceLevel .....	243
2.648	PidTagContentUnreadCount.....	244
2.649	PidTagConversationId .....	244
2.650	PidTagConversationIndex .....	244
2.651	PidTagConversationIndexTracking .....	245
2.652	PidTagConversationTopic.....	245
2.653	PidTagCountry .....	245
2.654	PidTagCreationTime.....	246
2.655	PidTagCreatorEntryId .....	246
2.656	PidTagCreatorName.....	246
2.657	PidTagCustomerId.....	247
2.658	PidTagDamBackPatched .....	247
2.659	PidTagDamOriginalEntryId .....	247
2.660	PidTagDefaultPostMessageClass .....	247
2.661	PidTagDeferredActionMessageOriginalEntryId .....	248
2.662	PidTagDeferredDeliveryTime.....	248
2.663	PidTagDeferredSendNumber.....	248
2.664	PidTagDeferredSendTime .....	248
2.665	PidTagDeferredSendUnits.....	249
2.666	PidTagDelegatedByRule .....	249
2.667	PidTagDelegateFlags.....	249
2.668	PidTagDeleteAfterSubmit .....	250
2.669	PidTagDeletedCountTotal .....	250
2.670	PidTagDeletedOn .....	250
2.671	PidTagDeliverTime .....	250
2.672	PidTagDepartmentName .....	251
2.673	PidTagDepth.....	251
2.674	PidTagDisplayBcc .....	251

2.675	PidTagDisplayCc.....	252
2.676	PidTagDisplayName.....	252
2.677	PidTagDisplayNamePrefix.....	252
2.678	PidTagDisplayTo.....	253
2.679	PidTagDisplayType.....	253
2.680	PidTagDisplayTypeEx.....	253
2.681	PidTagEmailAddress.....	254
2.682	PidTagEndDate.....	254
2.683	PidTagEntryId.....	254
2.684	PidTagExceptionEndTime.....	255
2.685	PidTagExceptionReplaceTime.....	255
2.686	PidTagExceptionStartTime.....	255
2.687	PidTagExchangeNTSecurityDescriptor.....	256
2.688	PidTagExpiryNumber.....	256
2.689	PidTagExpiryTime.....	256
2.690	PidTagExpiryUnits.....	256
2.691	PidTagExtendedFolderFlags.....	257
2.692	PidTagExtendedRuleMessageActions.....	257
2.693	PidTagExtendedRuleMessageCondition.....	257
2.694	PidTagExtendedRuleSizeLimit.....	258
2.695	PidTagFaxNumberOfPages.....	258
2.696	PidTagFlagCompleteTime.....	258
2.697	PidTagFlagStatus.....	259
2.698	PidTagFlatUrlName.....	259
2.699	PidTagFolderAssociatedContents.....	259
2.700	PidTagFolderId.....	259
2.701	PidTagFolderFlags.....	260
2.702	PidTagFolderType.....	260
2.703	PidTagFollowupIcon.....	260
2.704	PidTagFreeBusyCountMonths.....	261
2.705	PidTagFreeBusyEntryIds.....	261
2.706	PidTagFreeBusyMessageEmailAddress.....	261
2.707	PidTagFreeBusyPublishEnd.....	262
2.708	PidTagFreeBusyPublishStart.....	262
2.709	PidTagFreeBusyRangeTimestamp.....	262
2.710	PidTagFtpSite.....	262
2.711	PidTagGatewayNeedsToRefresh.....	263
2.712	PidTagGender.....	263
2.713	PidTagGeneration.....	263
2.714	PidTagGivenName.....	263
2.715	PidTagGovernmentIdNumber.....	264
2.716	PidTagHasAttachments.....	264
2.717	PidTagHasDeferredActionMessages.....	264
2.718	PidTagHasNamedProperties.....	265
2.719	PidTagHasRules.....	265
2.720	PidTagHierarchyChangeNumber.....	265
2.721	PidTagHierRev.....	265
2.722	PidTagHobbies.....	266
2.723	PidTagHome2TelephoneNumber.....	266
2.724	PidTagHome2TelephoneNumbers.....	266
2.725	PidTagHomeAddressCity.....	267
2.726	PidTagHomeAddressCountry.....	267
2.727	PidTagHomeAddressPostalCode.....	267
2.728	PidTagHomeAddressPostOfficeBox.....	267
2.729	PidTagHomeAddressStateOrProvince.....	268
2.730	PidTagHomeAddressStreet.....	268
2.731	PidTagHomeFaxNumber.....	268
2.732	PidTagHomeTelephoneNumber.....	269



2.733	PidTagHtml	269
2.734	PidTagICalendarEndTime	269
2.735	PidTagICalendarReminderNextTime	270
2.736	PidTagICalendarStartTime	270
2.737	PidTagIconIndex	270
2.738	PidTagImportance	271
2.739	PidTagInConflict	271
2.740	PidTagInitialDetailsPane	271
2.741	PidTagInitials	271
2.742	PidTagInReplyToId	272
2.743	PidTagInstanceKey	272
2.744	PidTagInstanceNum	272
2.745	PidTagInstID	273
2.746	PidTagInternetCodepage	273
2.747	PidTagInternetMailOverrideFormat	273
2.748	PidTagInternetMessageId	274
2.749	PidTagInternetReferences	274
2.750	PidTagIpmAppointmentEntryId	274
2.751	PidTagIpmContactEntryId	274
2.752	PidTagIpmDraftsEntryId	275
2.753	PidTagIpmJournalEntryId	275
2.754	PidTagIpmNoteEntryId	275
2.755	PidTagIpmTaskEntryId	276
2.756	PidTagIsdnNumber	276
2.757	PidTagJunkAddRecipientsToSafeSendersList	276
2.758	PidTagJunkIncludeContacts	276
2.759	PidTagJunkPermanentlyDelete	277
2.760	PidTagJunkPhishingEnableLinks	277
2.761	PidTagJunkThreshold	277
2.762	PidTagKeyword	278
2.763	PidTagLanguage	278
2.764	PidTagLastModificationTime	278
2.765	PidTagLastModifierEntryId	279
2.766	PidTagLastModifierName	279
2.767	PidTagLastVerbExecuted	279
2.768	PidTagLastVerbExecutionTime	279
2.769	PidTagListHelp	280
2.770	PidTagListSubscribe	280
2.771	PidTagListUnsubscribe	280
2.772	PidTagLocalCommitTime	281
2.773	PidTagLocalCommitTimeMax	281
2.774	PidTagLocaleId	281
2.775	PidTagLocality	282
2.776	PidTagLocation	282
2.777	PidTagMailboxOwnerEntryId	282
2.778	PidTagMailboxOwnerName	283
2.779	PidTagManagerName	283
2.780	PidTagMappingSignature	283
2.781	PidTagMaximumSubmitMessageSize	283
2.782	PidTagMemberId	284
2.783	PidTagMemberName	284
2.784	PidTagMemberRights	284
2.785	PidTagMessageAttachments	285
2.786	PidTagMessageCcMe	285
2.787	PidTagMessageClass	285
2.788	PidTagMessageCodepage	286
2.789	PidTagMessageDeliveryTime	286
2.790	PidTagMessageEditorFormat	286

2.791	PidTagMessageFlags	287
2.792	PidTagMessageHandlingSystemCommonName	287
2.793	PidTagMessageLocaleId	287
2.794	PidTagMessageRecipientMe	288
2.795	PidTagMessageRecipients	288
2.796	PidTagMessageSize	288
2.797	PidTagMessageSizeExtended	288
2.798	PidTagMessageStatus	289
2.799	PidTagMessageSubmissionId	289
2.800	PidTagMessageToMe	289
2.801	PidTagMid	290
2.802	PidTagMiddleName	290
2.803	PidTagMimeSkeleton	290
2.804	PidTagMobileTelephoneNumber	291
2.805	PidTagNativeBody	291
2.806	PidTagNextSendAcct	291
2.807	PidTagNickname	292
2.808	PidTagNonDeliveryReportDiagCode	292
2.809	PidTagNonDeliveryReportReasonCode	292
2.810	PidTagNonDeliveryReportStatusCode	292
2.811	PidTagNonReceiptNotificationRequested	293
2.812	PidTagNormalizedSubject	293
2.813	PidTagObjectType	293
2.814	PidTagOfficeLocation	294
2.815	PidTagOfflineAddressBookContainerGuid	294
2.816	PidTagOfflineAddressBookDistinguishedName	294
2.817	PidTagOfflineAddressBookMessageClass	295
2.818	PidTagOfflineAddressBookName	295
2.819	PidTagOfflineAddressBookSequence	295
2.820	PidTagOfflineAddressBookTruncatedProperties	295
2.821	PidTagOrdinalMost	296
2.822	PidTagOrganizationalIdNumber	296
2.823	PidTagOriginalAuthorEntryId	296
2.824	PidTagOriginalAuthorName	296
2.825	PidTagOriginalDeliveryTime	297
2.826	PidTagOriginalDisplayBcc	297
2.827	PidTagOriginalDisplayCc	297
2.828	PidTagOriginalDisplayTo	298
2.829	PidTagOriginalEntryId	298
2.830	PidTagOriginalMessageClass	298
2.831	PidTagOriginalMessageId	299
2.832	PidTagOriginalSenderAddressType	299
2.833	PidTagOriginalSenderEmailAddress	299
2.834	PidTagOriginalSenderEntryId	299
2.835	PidTagOriginalSenderName	300
2.836	PidTagOriginalSenderSearchKey	300
2.837	PidTagOriginalSensitivity	300
2.838	PidTagOriginalSentRepresentingAddressType	301
2.839	PidTagOriginalSentRepresentingEmailAddress	301
2.840	PidTagOriginalSentRepresentingEntryId	301
2.841	PidTagOriginalSentRepresentingName	302
2.842	PidTagOriginalSentRepresentingSearchKey	302
2.843	PidTagOriginalSubject	302
2.844	PidTagOriginalSubmitTime	302
2.845	PidTagOriginatorDeliveryReportRequested	303
2.846	PidTagOriginatorNonDeliveryReportRequested	303
2.847	PidTagOscSyncEnabled	303
2.848	PidTagOtherAddressCity	304

2.849	PidTagOtherAddressCountry .....	304
2.850	PidTagOtherAddressPostalCode .....	304
2.851	PidTagOtherAddressPostOfficeBox .....	305
2.852	PidTagOtherAddressStateOrProvince .....	305
2.853	PidTagOtherAddressStreet .....	305
2.854	PidTagOtherTelephoneNumber .....	306
2.855	PidTagOutOfOfficeState .....	306
2.856	PidTagOwnerAppointmentId .....	306
2.857	PidTagPagerTelephoneNumber .....	306
2.858	PidTagParentEntryId .....	307
2.859	PidTagParentFolderId .....	307
2.860	PidTagParentKey .....	307
2.861	PidTagParentSourceKey .....	308
2.862	PidTagPersonalHomePage .....	308
2.863	PidTagPolicyTag .....	308
2.864	PidTagPostalAddress .....	309
2.865	PidTagPostalCode .....	309
2.866	PidTagPostOfficeBox .....	309
2.867	PidTagPredecessorChangeList .....	309
2.868	PidTagPrimaryFaxNumber .....	310
2.869	PidTagPrimarySendAccount .....	310
2.870	PidTagPrimaryTelephoneNumber .....	310
2.871	PidTagPriority .....	311
2.872	PidTagProcessed .....	311
2.873	PidTagProfession .....	311
2.874	PidTagProhibitReceiveQuota .....	312
2.875	PidTagProhibitSendQuota .....	312
2.876	PidTagPurportedSenderDomain .....	312
2.877	PidTagRadioTelephoneNumber .....	312
2.878	PidTagRead .....	313
2.879	PidTagReadReceiptAddressType .....	313
2.880	PidTagReadReceiptEmailAddress .....	313
2.881	PidTagReadReceiptEntryId .....	314
2.882	PidTagReadReceiptName .....	314
2.883	PidTagReadReceiptRequested .....	314
2.884	PidTagReadReceiptSearchKey .....	315
2.885	PidTagReadReceiptSmtpAddress .....	315
2.886	PidTagReceiptTime .....	315
2.887	PidTagReceivedByAddressType .....	315
2.888	PidTagReceivedByEmailAddress .....	316
2.889	PidTagReceivedByEntryId .....	316
2.890	PidTagReceivedByName .....	316
2.891	PidTagReceivedBySearchKey .....	316
2.892	PidTagReceivedBySmtpAddress .....	317
2.893	PidTagReceivedRepresentingAddressType .....	317
2.894	PidTagReceivedRepresentingEmailAddress .....	317
2.895	PidTagReceivedRepresentingEntryId .....	318
2.896	PidTagReceivedRepresentingName .....	318
2.897	PidTagReceivedRepresentingSearchKey .....	318
2.898	PidTagReceivedRepresentingSmtpAddress .....	319
2.899	PidTagRecipientDisplayName .....	319
2.900	PidTagRecipientEntryId .....	319
2.901	PidTagRecipientFlags .....	319
2.902	PidTagRecipientOrder .....	320
2.903	PidTagRecipientProposed .....	320
2.904	PidTagRecipientProposedEndTime .....	320
2.905	PidTagRecipientProposedStartTime .....	321
2.906	PidTagRecipientReassignmentProhibited .....	321

2.907	PidTagRecipientTrackStatus.....	321
2.908	PidTagRecipientTrackStatusTime .....	321
2.909	PidTagRecipientType.....	322
2.910	PidTagRecordKey .....	322
2.911	PidTagReferredByName.....	322
2.912	PidTagRemindersOnlineEntryId .....	323
2.913	PidTagRemoteMessageTransferAgent.....	323
2.914	PidTagRenderingPosition .....	323
2.915	PidTagReplyRecipientEntries .....	324
2.916	PidTagReplyRecipientNames .....	324
2.917	PidTagReplyRequested.....	324
2.918	PidTagReplyTemplateId.....	325
2.919	PidTagReplyTime.....	325
2.920	PidTagReportDisposition.....	325
2.921	PidTagReportDispositionMode .....	325
2.922	PidTagReportEntryId.....	326
2.923	PidTagReportingMessageTransferAgent.....	326
2.924	PidTagReportName.....	326
2.925	PidTagReportSearchKey .....	327
2.926	PidTagReportTag.....	327
2.927	PidTagReportText.....	327
2.928	PidTagReportTime .....	327
2.929	PidTagResolveMethod .....	328
2.930	PidTagResponseRequested .....	328
2.931	PidTagResponsibility .....	328
2.932	PidTagRetentionDate .....	329
2.933	PidTagRetentionFlags.....	329
2.934	PidTagRetentionPeriod .....	329
2.935	PidTagRights .....	329
2.936	PidTagRoamingDatatypes.....	330
2.937	PidTagRoamingDictionary .....	330
2.938	PidTagRoamingXmlStream .....	330
2.939	PidTagRowid.....	330
2.940	PidTagRowType .....	331
2.941	PidTagRtfCompressed .....	331
2.942	PidTagRtfInSync .....	331
2.943	PidTagRuleActionNumber .....	332
2.944	PidTagRuleActions .....	332
2.945	PidTagRuleActionType.....	332
2.946	PidTagRuleCondition .....	332
2.947	PidTagRuleError .....	333
2.948	PidTagRuleFolderEntryId .....	333
2.949	PidTagRuleId .....	333
2.950	PidTagRuleIds.....	334
2.951	PidTagRuleLevel.....	334
2.952	PidTagRuleMessageLevel.....	334
2.953	PidTagRuleMessageName .....	335
2.954	PidTagRuleMessageProvider.....	335
2.955	PidTagRuleMessageProviderData .....	335
2.956	PidTagRuleMessageSequence.....	335
2.957	PidTagRuleMessageState.....	336
2.958	PidTagRuleMessageUserFlags.....	336
2.959	PidTagRuleName .....	336
2.960	PidTagRuleProvider .....	337
2.961	PidTagRuleProviderData .....	337
2.962	PidTagRuleSequence .....	337
2.963	PidTagRuleState.....	337
2.964	PidTagRuleUserFlags .....	338

2.965	PidTagRwRulesStream .....	338
2.966	PidTagScheduleInfoAppointmentTombstone.....	338
2.967	PidTagScheduleInfoAutoAcceptAppointments.....	339
2.968	PidTagScheduleInfoDelegateEntryIds.....	339
2.969	PidTagScheduleInfoDelegateNames .....	339
2.970	PidTagScheduleInfoDelegateNamesW .....	339
2.971	PidTagScheduleInfoDelegatorWantsCopy.....	340
2.972	PidTagScheduleInfoDelegatorWantsInfo .....	340
2.973	PidTagScheduleInfoDisallowOverlappingAppts.....	340
2.974	PidTagScheduleInfoDisallowRecurringAppts .....	341
2.975	PidTagScheduleInfoDontMailDelegates .....	341
2.976	PidTagScheduleInfoFreeBusy .....	341
2.977	PidTagScheduleInfoFreeBusyAway.....	342
2.978	PidTagScheduleInfoFreeBusyBusy .....	342
2.979	PidTagScheduleInfoFreeBusyMerged.....	342
2.980	PidTagScheduleInfoFreeBusyTentative .....	342
2.981	PidTagScheduleInfoMonthsAway .....	343
2.982	PidTagScheduleInfoMonthsBusy .....	343
2.983	PidTagScheduleInfoMonthsMerged .....	343
2.984	PidTagScheduleInfoMonthsTentative.....	343
2.985	PidTagScheduleInfoResourceType .....	344
2.986	PidTagSchedulePlusFreeBusyEntryId.....	344
2.987	PidTagScriptData .....	344
2.988	PidTagSearchFolderDefinition.....	345
2.989	PidTagSearchFolderEfpFlags .....	345
2.990	PidTagSearchFolderExpiration .....	345
2.991	PidTagSearchFolderId .....	345
2.992	PidTagSearchFolderLastUsed .....	346
2.993	PidTagSearchFolderRecreateInfo .....	346
2.994	PidTagSearchFolderStorageType .....	346
2.995	PidTagSearchFolderTag.....	346
2.996	PidTagSearchFolderTemplateId .....	347
2.997	PidTagSearchKey .....	347
2.998	PidTagSecurityDescriptorAsXml.....	347
2.999	PidTagSelectable.....	348
2.1000	PidTagSenderAddressType .....	348
2.1001	PidTagSenderEmailAddress.....	348
2.1002	PidTagSenderEntryId .....	349
2.1003	PidTagSenderIdStatus .....	349
2.1004	PidTagSenderName .....	349
2.1005	PidTagSenderSearchKey .....	350
2.1006	PidTagSenderSmtpAddress.....	350
2.1007	PidTagSenderTelephoneNumber.....	350
2.1008	PidTagSendInternetEncoding .....	351
2.1009	PidTagSendRichInfo.....	351
2.1010	PidTagSensitivity.....	351
2.1011	PidTagSentMailSvrEID .....	352
2.1012	PidTagSentRepresentingAddressType.....	352
2.1013	PidTagSentRepresentingEmailAddress.....	352
2.1014	PidTagSentRepresentingEntryId .....	353
2.1015	PidTagSentRepresentingFlags .....	353
2.1016	PidTagSentRepresentingName .....	353
2.1017	PidTagSentRepresentingSearchKey.....	354
2.1018	PidTagSentRepresentingSmtpAddress .....	354
2.1019	PidTagSerializedReplidGuidMap .....	354
2.1020	PidTagSmtpAddress.....	354
2.1021	PidTagSortLocaleId.....	355
2.1022	PidTagSourceKey .....	355

2.1023	PidTagSpokenName.....	355
2.1024	PidTagSpouseName.....	356
2.1025	PidTagStartDate.....	356
2.1026	PidTagStartDateEtc.....	356
2.1027	PidTagStateOrProvince.....	357
2.1028	PidTagStoreEntryId.....	357
2.1029	PidTagStoreState.....	357
2.1030	PidTagStoreSupportMask.....	357
2.1031	PidTagStreetAddress.....	358
2.1032	PidTagSubfolders.....	358
2.1033	PidTagSubject.....	358
2.1034	PidTagSubjectPrefix.....	359
2.1035	PidTagSupplementaryInfo.....	359
2.1036	PidTagSurname.....	359
2.1037	PidTagSwappedToDoData.....	360
2.1038	PidTagSwappedToDoStore.....	360
2.1039	PidTagTargetEntryId.....	360
2.1040	PidTagTelecommunicationsDeviceForDeafTelephoneNumber.....	361
2.1041	PidTagTelexNumber.....	361
2.1042	PidTagTemplateData.....	361
2.1043	PidTagTemplateid.....	361
2.1044	PidTagTextAttachmentCharset.....	362
2.1045	PidTagThumbnailPhoto.....	362
2.1046	PidTagTitle.....	362
2.1047	PidTagTnefCorrelationKey.....	363
2.1048	PidTagToDoItemFlags.....	363
2.1049	PidTagTransmittableDisplayName.....	363
2.1050	PidTagTransportMessageHeaders.....	364
2.1051	PidTagTrustSender.....	364
2.1052	PidTagUserCertificate.....	364
2.1053	PidTagUserEntryId.....	365
2.1054	PidTagUserX509Certificate.....	365
2.1055	PidTagViewDescriptorBinary.....	365
2.1056	PidTagViewDescriptorName.....	365
2.1057	PidTagViewDescriptorStrings.....	366
2.1058	PidTagViewDescriptorVersion.....	366
2.1059	PidTagVoiceMessageAttachmentOrder.....	366
2.1060	PidTagVoiceMessageDuration.....	366
2.1061	PidTagVoiceMessageSenderName.....	367
2.1062	PidTagWeddingAnniversary.....	367
2.1063	PidTagWlinkAddressBookEID.....	367
2.1064	PidTagWlinkAddressBookStoreEID.....	368
2.1065	PidTagWlinkCalendarColor.....	368
2.1066	PidTagWlinkClientID.....	368
2.1067	PidTagWlinkEntryId.....	368
2.1068	PidTagWlinkFlags.....	369
2.1069	PidTagWlinkFolderType.....	369
2.1070	PidTagWlinkGroupClsid.....	369
2.1071	PidTagWlinkGroupHeaderID.....	370
2.1072	PidTagWlinkGroupName.....	370
2.1073	PidTagWlinkOrdinal.....	370
2.1074	PidTagWlinkRecordKey.....	370
2.1075	PidTagWlinkROGroupType.....	371
2.1076	PidTagWlinkSaveStamp.....	371
2.1077	PidTagWlinkSection.....	371
2.1078	PidTagWlinkStoreEntryId.....	371
2.1079	PidTagWlinkType.....	372

<b>3</b>	<b>Structure Examples .....</b>	<b>373</b>
<b>4</b>	<b>Security .....</b>	<b>374</b>
4.1	Security Considerations for Implementers .....	374
4.2	Index of Security Fields .....	374
<b>5</b>	<b>Appendix A: Product Behavior .....</b>	<b>375</b>
<b>6</b>	<b>Change Tracking.....</b>	<b>376</b>
<b>7</b>	<b>Index.....</b>	<b>377</b>

# 1 Introduction

The Exchange Server Protocols Master Property List provides implementers with a single source of information about all the properties that are described by the specifications that comprise the Exchange Server Protocols documentation. If a property is not described by the specifications included in the Exchange Server Protocols documentation, it is not included in this document.

The criteria for including a property in the Exchange Server Protocols documentation are that it is set by a client in order to affect server behavior, or that it is set by a server in order to affect client behavior. Properties that are merely stored by the server on behalf of the client, or generated by the server for its own use and ignored by the client, are not necessarily documented. As a result, the properties that are included in the Exchange Server Protocols documentation, and therefore this document, are the critical **Message object** properties used for communication between clients and servers.

This document provides implementers with a convenient catalog of all these critical properties, a source of navigation to the individual technical specifications that describe these properties in detail, and a resource for additional helpful property information that is unique to this document.

Sections 1.7 and 2 of this specification are normative. All other sections and examples in this specification are informative.

## 1.1 Glossary

This document uses the following terms:

**8.3 name:** A file name string restricted in length to 12 characters that includes a base name of up to eight characters, one character for a period, and up to three characters for a file name extension. For more information on 8.3 file names, see [\[MS-CIFS\]](#) section 2.2.1.1.1.

**action:** A discrete operation that is executed on an incoming **Message object** when all conditions in the same **rule** are TRUE. A rule contains one or more actions.

**address book container:** An **Address Book object** that describes an **address list**.

**Address Book object:** An entity in an address book that contains a set of attributes, each attribute with a set of associated values.

**address list:** A collection of distinct **Address Book objects**.

**address type:** An identifier for the type of email address, such as **SMTP** and EX.

**alias:** An alternate name that can be used to reference an object or element.

**ambiguous name resolution (ANR):** A search algorithm that permits a client to search multiple naming-related attributes on objects by way of a single clause of the form "(anr=value)" in a Lightweight Directory Access Protocol (LDAP) search filter. This permits a client to query for an object when the client possesses some identifying material related to the object but does not know which attribute of the object contains that identifying material.

**Appointment object:** A **Calendar object** that has an organizer but no attendees.

**archive tag:** An element that contains information about the archive policy of a **Message object** or folder.

**Attachment object:** A set of properties that represents a file, **Message object**, or structured storage that is attached to a Message object and is visible through the attachments table for a Message object.



**Augmented Backus-Naur Form (ABNF):** A modified version of Backus-Naur Form (BNF), commonly used by Internet specifications. ABNF notation balances compactness and simplicity with reasonable representational power. ABNF differs from standard BNF in its definitions and uses of naming rules, repetition, alternatives, order-independence, and value ranges. For more information, see [\[RFC5234\]](#).

**blind carbon copy (Bcc) recipient:** An addressee on a **Message object** that is not visible to recipients of the Message object.

**body part:** A part of an Internet message, as described in [\[RFC2045\]](#).

**calendar:** A date range that shows availability, **meetings**, and appointments for one or more users or **resources**. See also **Calendar object**.

**Calendar folder:** A **Folder object** that contains **Calendar objects**.

**Calendar object:** A **Message object** that represents an event, which can be a one-time event or a recurring event. The Calendar object includes properties that specify event details such as description, organizer, date and time, and status.

**carbon copy (Cc) recipient:** An address on a **Message object** that is visible to recipients of the Message object but is not necessarily expected to take any action.

**class:** User-defined binary data that is associated with a key.

**Classification, labeling, and protection:** Classification is determining that an email has sensitive or otherwise interesting content in it. Labeling is tagging the email with an administrator-defined sensitivity label that travels with the email. Protection is enforcing administrator-defined outcomes based on the sensitivity label.

**common name (CN):** A string attribute of a certificate that is one component of a **distinguished name (DN)**. In Microsoft Enterprise uses, a CN must be unique within the forest where it is defined and any forests that share trust with the defining forest. The website or email address of the certificate owner is often used as a common name. Client applications often refer to a certification authority (CA) by the CN of its signing certificate.

**contact:** A person, company, or other entity that is stored in a directory and is associated with one or more unique identifiers and attributes, such as an Internet message address or login name.

**contents table:** A Table object whose rows represent the **Message objects** that are contained in a **Folder object**.

**conversation:** A single representation of a send/response series of email messages. A conversation appears in the Inbox as one unit and allows the user to view and read the series of related email messages in a single effort.

**conversation action:** A limited set of actions that a user applies to all **Message objects** that have the same PidTagConversationId value. The action is applied to all Message objects that are currently in the store or are delivered in the future.

**Coordinated Universal Time (UTC):** A high-precision atomic time standard that approximately tracks Universal Time (UT). It is the basis for legal, civil time all over the Earth. Time zones around the world are expressed as positive and negative offsets from UTC. In this role, it is also referred to as Zulu time (Z) and Greenwich Mean Time (GMT). In these specifications, all references to UTC refer to the time at UTC-0 (or GMT).

**counter proposal:** A request that an attendee sends to an **organizer** when requesting a change to the date or time of a meeting.

**cyclic redundancy check (CRC):** An algorithm used to produce a checksum (a small, fixed number of bits) against a block of data, such as a packet of network traffic or a block of a

computer file. The CRC is a broad class of functions used to detect errors after transmission or storage. A CRC is designed to catch random errors, as opposed to intentional errors. If errors might be introduced by a motivated and intelligent adversary, a cryptographic hash function should be used instead.

**Deferred Action Message (DAM):** A hidden message indicating to a client that it needs to execute one or more **rules** on another user-visible message in the store.

**delegate:** A user or resource that has permissions to act on behalf of another user or resource.

**delivery receipt:** A report message that is generated and sent by a client or server to the sender of a message or another designated recipient when an email message is received by an intended recipient.

**Department object:** An **Address Book object** that describes a department within an organization.

**departmental group:** A **distribution list** that describes a department within an organization.

**display name:** A text string that is used to identify a principal or other object in the user interface. Also referred to as title.

**display template:** A template that describes how to display or allow a user to modify information about an **Address Book object**.

**distinguished name (DN):** A name that uniquely identifies an object by using the relative distinguished name (RDN) for the object, and the names of container objects and domains that contain the object. The distinguished name (DN) identifies the object and its location in a tree.

**distribution list:** A collection of users, computers, contacts, or other groups that is used only for email distribution, and addressed as a single recipient.

**Document object:** A **Message object** that represents a single file, such as a document generated by a word-processing application. The Message object contains the file as an **Attachment object** and includes additional properties to describe the file.

**domain:** A set of users and computers sharing a common namespace and management infrastructure. At least one computer member of the set must act as a domain controller (DC) and host a member list that identifies all members of the domain, as well as optionally hosting the Active Directory service. The domain controller provides authentication of members, creating a unit of trust for its members. Each domain has an identifier that is shared among its members. For more information, see [\[MS-AUTHSOD\]](#) section 1.1.1.5 and [\[MS-ADTS\]](#).

**double-byte character set (DBCS):** A character set that can use more than one byte to represent a single character. A DBCS includes some characters that consist of 1 byte and some characters that consist of 2 bytes. Languages such as Chinese, Japanese, and Korean use DBCS.

**Email object:** A **Message object** that represents an email message in a message store and adheres to the property descriptions that are described in in [\[MS-OXOMSG\]](#).

**entry ID:** See **EntryID**.

**EntryID:** A sequence of bytes that is used to identify and access an object.

**Exception Embedded Message object:** An Embedded Message object that contains the changes for an Exception object.

**Exception object:** An instance of a **recurring series** that differs from the rest of the recurring series, for example by start time.

**File Transfer Protocol (FTP):** A member of the TCP/IP suite of protocols that is used to copy files between two computers on the Internet if both computers support their respective FTP roles. One computer is an FTP client and the other is an FTP server.

**flags:** A set of values used to configure or report options or settings.

**folder associated information (FAI):** A collection of **Message objects** that are stored in a Folder object and are typically hidden from view by email applications. An FAI Message object is used to store a variety of settings and auxiliary data, including forms, views, calendar options, favorites, and category lists.

**Folder object:** A messaging construct that is typically used to organize data into a hierarchy of objects containing Message objects and **folder associated information (FAI)** Message objects.

**free/busy status:** A property of an appointment that indicates how an appointment on the **calendar** of an attendee or resource affects their availability.

**Global Address List (GAL):** An **address list** that conceptually represents the default address list for an address book.

**globally unique identifier (GUID):** A term used interchangeably with universally unique identifier (UUID) in Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the value. Specifically, the use of this term does not imply or require that the algorithms described in [\[RFC4122\]](#) or [\[C706\]](#) must be used for generating the **GUID**. See also universally unique identifier (UUID).

**group header:** A **navigation shortcut** that groups other navigation shortcuts.

**Hypertext Markup Language (HTML):** An application of the Standard Generalized Markup Language (SGML) that uses tags to mark elements in a document, as described in [\[HTML\]](#).

**Hypertext Transfer Protocol (HTTP):** An application-level protocol for distributed, collaborative, hypermedia information systems (text, graphic images, sound, video, and other multimedia files) on the World Wide Web.

**instance:** A unique publication of data for a category. It enables a publisher to publish data for the same category multiple times. An example is a publisher who uses two different endpoints to publish data. These endpoints can publish the same category. However, each endpoint requires a different instance number to be considered a distinct publication by the server. An instance number is provided by the publishing client.

**Integrated Services Digital Network (ISDN):** A high-speed digital technology that uses existing telephone lines to provide Internet access and digital network services.

**Journal object:** A **Message object** that represents an entry in a journal or log and adheres to the property descriptions that are described in [\[MS-OXOJRN\]](#).

**locale:** A collection of rules and data that are specific to a language and a geographical area. A locale can include information about sorting rules, date and time formatting, numeric and monetary conventions, and character classification.

**Logon object:** A **Server object** that provides access to a private **mailbox** or a **public folder**. A client obtains a Logon object by issuing a RopLogon remote operation (ROP) to a server.

**long ID (LID):** A 32-bit quantity that, in combination with a GUID, defines a **named property**.

**mail tip:** A note that is presented to the author of a message when the author is composing the message. A mail tip provides information about the recipients of a message and issues that might impact delivery of the message, such as moderation or delivery restrictions.

**mail user:** An **Address Book object** that represents a person or entity that can receive deliverable messages.

**mailbox:** A **message store** that contains email, calendar items, and other **Message objects** for a single recipient.

**meeting:** An event with attendees.

**Meeting object:** A **Calendar object** that has both an organizer and attendees.

**meeting request:** An instance of a **Meeting Request object**.

**Meeting Request object:** A **Message object** that represents an invitation from the meeting organizer to an attendee.

**Meeting Response object:** A **Message object** that represents an attendee's response to a meeting organizer's invitation. The response indicates whether the attendee accepted, tentatively accepted, or declined the meeting request. The response can include a proposed new date or time for the meeting.

**Meeting Update object:** A **Message object** that represents a meeting organizer's changes to a previously scheduled meeting. The update is categorized as either a full update or an informational update.

**Meeting Workspace:** A website that is created by using the Meetings Web Services protocol, as described in [\[MS-MEETS\]](#). It can host documents, discussions, and other information about a meeting.

**meeting-related object:** A **Message object** that represents a relay of information between a meeting organizer and an attendee. It can be any of the following: **Meeting Request object**, **Meeting Update object**, Meeting Cancellation object, or **Meeting Response object**.

**message body:** The main message text of an email message. A few properties of a **Message object** represent its message body, with one property containing the text itself and others defining its code page and its relationship to alternative body formats.

**message class:** A property that loosely defines the type of a message, contact, or other Personal Information Manager (PIM) object in a mailbox.

**Message object:** A set of properties that represents an email message, appointment, contact, or other type of personal-information-management object. In addition to its own properties, a Message object contains recipient properties that represent the addressees to which it is addressed, and an attachments table that represents any files and other Message objects that are attached to it.

**message store:** A unit of containment for a single hierarchy of Folder objects, such as a mailbox or public folders.

**Messaging Application Programming Interface (MAPI):** A messaging architecture that enables multiple applications to interact with multiple messaging systems across a variety of hardware platforms.

**messaging object:** An object that exists in a **mailbox**. It can be only a **Folder object** or a **Message object**.

**MIME message:** A message that is as described in [\[RFC2045\]](#), [\[RFC2046\]](#), and [\[RFC2047\]](#).

**MIME part:** A message part that is as described in [\[RFC2045\]](#), [\[RFC2046\]](#), and [\[RFC2047\]](#).

**Multipurpose Internet Mail Extensions (MIME):** A set of extensions that redefines and expands support for various types of content in email messages, as described in [RFC2045], [RFC2046], and [RFC2047].

**name service provider interface (NSPI):** A method of performing address-book-related operations on Active Directory.

**named property:** A property that is identified by both a GUID and either a string name or a 32-bit identifier.

**navigation shortcut:** An object that contains identifying information to locate a folder in a message database or an object that groups other navigation shortcuts.

**non-Unicode:** A character set that has a restricted set of glyphs, such as Shift\_JIS or ISO-2022-JP.

**Note object:** A **Message object** that represents a simple text note in a messaging store and that adheres to the property descriptions that are described in [\[MS-OXONOTE\]](#). A Note object functions as an electronic equivalent of a paper sticky note.

**offline address book (OAB):** A collection of **address lists** that are stored in a format that a client can save and use locally.

**optional attendee:** An attendee of an event whom the organizer lists as an optional participant.

**organizer:** The owner or creator of a **meeting** or appointment.

**orphan instance:** An instance of an event that is in a **recurring series** and is in a Calendar folder without the recurring series. For all practical purposes, this is a single instance.

**Out of Office (OOF):** One of the possible values for the **free/busy status** on an appointment. It indicates that the user will not be in the office during the appointment.

**Permanent Entry ID:** A property of an **Address Book object** that can be used to uniquely identify the object.

**permission:** A rule that is associated with an object and that regulates which users can gain access to the object and in what manner. See also rights.

**phishing:** The luring of sensitive information, such as passwords or other personal information, from a recipient by masquerading as someone who is trustworthy and has a real need for such information.

**plain text:** Text that does not have markup. See also plain text message body.

**primary recipient:** A person for whom a message is directly intended.

**property ID:** A 16-bit numeric identifier of a specific attribute. A property ID does not include any **property type** information.

**property name:** A string that, in combination with a **property set**, identifies a **named property**.

**property set:** A set of attributes, identified by a **GUID**. Granting access to a property set grants access to all the attributes in the set.

**property type:** A 16-bit quantity that specifies the data type of a property value.

**public folder:** A **Folder object** that is stored in a location that is publicly available.

**read receipt:** An email message that is sent to the sender of a message to indicate that a message recipient received the message.

**recipient:** An entity that is in an **address list**, can receive email messages, and contains a set of attributes. Each attribute has a set of associated values.

**recipient table:** The part of a **Message object** that represents users to whom a message is addressed. Each row of the table is a set of properties that represents one **recipient**.

**recurrence pattern:** Information for a repeating event, such as the start and end time, the number of occurrences, and how occurrences are spaced, such as daily, weekly, or monthly.

**Recurring Calendar object:** A **Calendar object** that describes an event that repeats according to a recurrence pattern.

**recurring series:** An event that repeats at specific intervals of time according to a recurrence pattern.

**recurring task:** A series of **Task objects** that are described by a recurrence pattern.

**reminder:** A generally user-visible notification that a specified time has been reached. A reminder is most commonly related to the beginning of a meeting or the due time of a task but it can be applied to any object type.

**replica GUID (REPLGUID):** A value that represents a namespace for identifiers. If a REPLGUID is combined with a GLOBSET, the result is a set of global identifiers. A REPLGUID value has an associated **replica ID (REPLID)** that is used in its place on disk and on the wire.

**replica ID (REPLID):** A value that is mapped to a **replica GUID (REPLGUID)** that identifies a namespace for IDs within a given logon. REPLIDs are used on disk and on the wire for compactness, and are replaced with the corresponding REPLGUID for external consumption.

**resource:** Any component that a computer can access that can read, write, and process data. This includes internal components (such as a disk drive), a service, or an application running on and managed by the cluster on a network that is used to access a file.

**Resource object:** An **Address Book object** that represents an asset that can be reserved, such as a room or equipment.

**retention tag:** An element that contains information about the retention policy of a **Message object** or folder.

**Rich Text Format (RTF):** Text with formatting as described in [\[MSFT-RTF\]](#).

**rights-managed email message:** An email message that specifies permissions that are designed to protect its content from inappropriate access, use, and distribution.

**root folder:** The folder at the top of a hierarchy of folders in a list.

**ROP buffer:** A structure containing an array of bytes that encode a remote operation (ROP). The first byte in the buffer identifies the ROP. This byte is followed by ROP-specific fields. Multiple ROP buffers can be packed into a single remote procedure call (RPC) request or response.

**rule:** An item that defines a condition and an action. The condition is evaluated for each **Message object** as it is delivered, and the action is executed if the new Message object matches the condition.

**Rule FAI message:** A **folder associated information (FAI)** message stored in the Inbox special folder where the client can store extra rule-related information that is opaque to the server.

**Sent Items folder:** A **special folder** that is the default location for storing copies of **Message objects** after they are submitted or sent.

**server object:** A class of object in the configuration naming context (config NC). A **server object** can have an nTDSDSA object as a child.

**Short Message Service (SMS):** A communications protocol that is designed for sending text messages between mobile phones.

**signal time:** The time at which a **reminder** has been specified to notify the user or an agent acting on behalf of the user. For example, the signal time for a meeting that starts at 11:00 A.M. can be 10:45 A.M., thus allowing the user 15 minutes to prepare for or travel to the meeting upon receiving the notification.

**Simple Mail Transfer Protocol (SMTP):** A member of the TCP/IP suite of protocols that is used to transport Internet messages, as described in [\[RFC5321\]](#).

**site mailbox:** A repository comprised of a mailbox and a web-based collaboration environment that is presented to users as a mailbox in an email client. A site mailbox uses team membership to determine which users have access to the repository.

**soft delete:** A process that removes an item from the system, but not permanently. If an item is soft deleted, a server retains a back-up copy of the item and a client can access, restore, or permanently delete the item. See also hard delete.

**spam:** An unsolicited email message.

**spam filter:** A filter that checks certain conditions in a message to determine a spam confidence level.

**special folder:** One of a default set of **Folder objects** that can be used by an implementation to store and retrieve user data objects.

**stream:** A flow of data from one host to another host, or the data that flows between two hosts.

**tagged property:** A property that is defined by a 16-bit property ID and a 16-bit property type. The property ID for a tagged property is in the range 0x001 – 0x7FFF. Property IDs in the range 0x8000 – 0x8FFF are reserved for assignment to **named properties**.

**Task object:** A **Message object** that represents an assignment to be completed.

**task request:** A **Message object** that is used to issue a task assignment.

**Transmission Control Protocol (TCP):** A protocol used with the Internet Protocol (IP) to send data in the form of message units between computers over the Internet. TCP handles keeping track of the individual units of data (called packets) that a message is divided into for efficient routing through the Internet.

**Transport Neutral Encapsulation Format (TNEF):** A binary type-length-value encoding that is used to encode properties for transport, as described in [\[MS-OXTNEF\]](#).

**Unicode:** A character encoding standard developed by the Unicode Consortium that represents almost all of the written languages of the world. The **Unicode** standard [\[UNICODE5.0.0/2007\]](#) provides three forms (UTF-8, UTF-16, and UTF-32) and seven schemes (UTF-8, UTF-16, UTF-16 BE, UTF-16 LE, UTF-32, UTF-32 LE, and UTF-32 BE).

**Uniform Resource Identifier (URI):** A string that identifies a resource. The URI is an addressing mechanism defined in Internet Engineering Task Force (IETF) Uniform Resource Identifier (URI): Generic Syntax [\[RFC3986\]](#).

**Uniform Resource Locator (URL):** A string of characters in a standardized format that identifies a document or resource on the World Wide Web. The format is as specified in [\[RFC1738\]](#).

**unsendable attendee:** An attendee to whom a **meeting request** or meeting update is not sent.

**Use License:** An XrML 1.2 license that authorizes a user to gain access to a protected content file and describes the applicable usage policies. Also referred to as "End-User License (EUL)."

**Web Distributed Authoring and Versioning Protocol (WebDAV):** The Web Distributed Authoring and Versioning Protocol, as described in [\[RFC2518\]](#) or [\[RFC4918\]](#).

**X500 DN:** A distinguished name (DN), in Teletex form, of an object that is in an address book. An X500 DN can be more limited in the size and number of relative distinguished names (RDNs) than a full DN.

**XML:** The Extensible Markup Language, as described in [\[XML1.0\]](#).

**XML document:** A document object that is well formed, as described in [\[XML10/5\]](#), and might be valid. An XML document has a logical structure that is composed of declarations, elements, comments, character references, and processing instructions. It also has a physical structure that is composed of entities, starting with the root, or document, entity.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[ISO/IEC8802-3] ISO/IEC, "Information technology -- Telecommunications and information exchange between systems -- Local and metropolitan area networks -- Specific requirements -- Part 3", Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications, ISO/IEC 8802-3:2000, [http://www.iso.org/iso/iso\\_catalogue/catalogue\\_tc/catalogue\\_detail.htm?csnumber=31002](http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=31002)

[MS-OXABREF] Microsoft Corporation, "[Address Book Name Service Provider Interface \(NSPI\) Referral Protocol](#)".

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Algorithm](#)".

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCEXT] Microsoft Corporation, "[Client Extension Message Object Protocol](#)".

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol](#)".

[MS-OXCXICS] Microsoft Corporation, "[Bulk Data Transfer Protocol](#)".

[MS-OXCICAL] Microsoft Corporation, "[iCalendar to Appointment Object Conversion Algorithm](#)".

[MS-OXCMAIL] Microsoft Corporation, "[RFC 2822 and MIME to Email Object Conversion Algorithm](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol](#)".

[MS-OXCPERM] Microsoft Corporation, "[Exchange Access and Operation Permissions Protocol](#)".



[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol](#)".

[MS-OXCRPC] Microsoft Corporation, "[Wire Format Protocol](#)".

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol](#)".

[MS-OXCSTOR] Microsoft Corporation, "[Store Object Protocol](#)".

[MS-OXCTABL] Microsoft Corporation, "[Table Object Protocol](#)".

[MS-OXLDAP] Microsoft Corporation, "[Lightweight Directory Access Protocol \(LDAP\) Version 3 Extensions](#)".

[MS-OXMSG] Microsoft Corporation, "[Outlook Item \(.msg\) File Format](#)".

[MS-OXNSPI] Microsoft Corporation, "[Exchange Server Name Service Provider Interface \(NSPI\) Protocol](#)".

[MS-OXOABKT] Microsoft Corporation, "[Address Book User Interface Templates Protocol](#)".

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol](#)".

[MS-OXOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) File Format and Schema](#)".

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol](#)".

[MS-OXOCFG] Microsoft Corporation, "[Configuration Information Protocol](#)".

[MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol](#)".

[MS-OXODLGT] Microsoft Corporation, "[Delegate Access Configuration Protocol](#)".

[MS-OXODOC] Microsoft Corporation, "[Document Object Protocol](#)".

[MS-OXOFLAG] Microsoft Corporation, "[Informational Flagging Protocol](#)".

[MS-OXOJRNL] Microsoft Corporation, "[Journal Object Protocol](#)".

[MS-OXOMSG] Microsoft Corporation, "[Email Object Protocol](#)".

[MS-OXONOTE] Microsoft Corporation, "[Note Object Protocol](#)".

[MS-OXOPFFB] Microsoft Corporation, "[Public Folder-Based Free/Busy Protocol](#)".

[MS-OXOPOST] Microsoft Corporation, "[Post Object Protocol](#)".

[MS-OXORMDR] Microsoft Corporation, "[Reminder Settings Protocol](#)".

[MS-OXORMMS] Microsoft Corporation, "[Rights-Managed Email Object Protocol](#)".

[MS-OXORSS] Microsoft Corporation, "[RSS Object Protocol](#)".

[MS-OXORULE] Microsoft Corporation, "[Email Rules Protocol](#)".

[MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol](#)".

[MS-OXOSMIME] Microsoft Corporation, "[S/MIME Email Object Algorithm](#)".

[MS-OXOSMMS] Microsoft Corporation, "[Short Message Service \(SMS\) and Multimedia Messaging Service \(MMS\) Object Protocol](#)".

[MS-OXOSRCH] Microsoft Corporation, "[Search Folder List Configuration Protocol](#)".

[MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol](#)".

[MS-OXOUM] Microsoft Corporation, "[Voice Mail and Fax Objects Protocol](#)".

[MS-OXPFOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) Public Folder Retrieval Protocol](#)".

[MS-OXPHISH] Microsoft Corporation, "[Phishing Warning Protocol](#)".

[MS-OXPSVAL] Microsoft Corporation, "[Email Postmark Validation Algorithm](#)".

[MS-OXRTFCP] Microsoft Corporation, "[Rich Text Format \(RTF\) Compression Algorithm](#)".

[MS-OXRTFEX] Microsoft Corporation, "[Rich Text Format \(RTF\) Extensions Algorithm](#)".

[MS-OXSHARE] Microsoft Corporation, "[Sharing Message Object Protocol](#)".

[MS-OXTNEF] Microsoft Corporation, "[Transport Neutral Encapsulation Format \(TNEF\) Data Algorithm](#)".

[MS-OXVCARD] Microsoft Corporation, "[vCard to Contact Object Conversion Algorithm](#)".

[MS-OXWAVLS] Microsoft Corporation, "[Availability Web Service Protocol](#)".

[MS-WMF] Microsoft Corporation, "[Windows Metafile Format](#)".

[MS-XWDCAL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Calendar Support](#)".

[MS-XWDVSEC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Protocol Security Descriptor Extensions](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC3464] Moore, K., and Vaudreuil, G., "An Extensible Message Format for Delivery Status Notifications", RFC 3464, January 2003, <http://www.rfc-editor.org/rfc/rfc3464.txt>

[RFC3798] Hansen, T., and Vaudreuil, G., Eds., "Message Disposition Notification", RFC 3798, May 2004, <http://www.rfc-editor.org/rfc/rfc3798.txt>

### 1.2.2 Informative References

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

### 1.3 Overview

Each property listing in this document contains a link to the section of the technical specification in the Exchange Server Protocols documentation that acts as the defining reference for the property. The defining reference for each property contains the semantic use and definition of the property, including the property data type. The property information that is included in the defining reference for each property is required to successfully parse property data. As such, this document provides

implementers with a single source of navigation to all of the critical property information that is included in the individual Exchange Server Protocols technical specifications.

This document also provides additional information about each property that is helpful to the implementer, such as the functional area where the property is used, a list of all the technical specifications that cite the property, and a list of alternate names by which the canonical property is known within the system. This information is not included in the technical specifications that describe each property, and is unique to this document. It is provided for informational purposes only.

A typical scenario for using this document is when an implementer encounters both **property IDs** and property values with no other identification coming across the wire. The property data type and the semantic definition of the property that are included in the defining reference for each property allow the implementer to correctly parse property values that show up in **ROP buffers**. The parsed values in the ROP buffers include lists of property IDs, which are typically lists of four hexadecimal characters. By searching the information in this document for those four hexadecimal characters, the implementer can quickly name the associated property and navigate to the definition of the individual property in its defining specification.

The following information is provided for each property, as appropriate.

**Alternate names:** Alternate names are implementation-specific names for properties that are used in source code and non-protocol-related documentation. Information about alternate names is useful when the implementer needs to refer to legacy documentation about a specific canonical property.

**Area:** The functional area where the property is used. Sections [1.3.1](#), [1.3.2](#), and [1.3.3](#) describe the general functional areas where properties are used. The listing for each property in section [2](#) describes the areas with more varied descriptions so as to provide more insight into property usage.

**Canonical name:** The name used to refer to the property in the Exchange Server Protocols documentation. The prefix of the canonical name identifies the basic characteristics of a property to the implementer.

The canonical naming structure uses three categories that are denoted by the following prefixes to the canonical **property name**:

- PidLid prefix: Properties identified by an unsigned 32-bit quantity along with a property set.
- PidName prefix: Properties identified by a string name along with a property set.
- PidTag prefix: Properties identified by an unsigned 16-bit quantity.

**Description:** A brief description of the contents of the property.

**Data type:** The property value type, as described in [\[MS-OXCADATA\]](#), that specifies the type of values allowed for the property.

**Property ID:** An unsigned 16-bit quantity that identifies a **tagged property**. Property IDs are not necessarily unique. With the exception of property IDs in the range from 0x6800 to 0x7BFF (see section 1.3.3), the combination of property ID and data type are unique. Property IDs in the range from 0x6800 to 0x7BFF are defined by the **message class**.

**Property long ID (LID):** An unsigned 32-bit quantity that, along with the **property set**, identifies a **named property**.

**Property name:** A string that, along with the property set, identifies a named property.

**Property set:** A **GUID** that identifies a group of properties with a similar purpose.

**Defining references:** One or more technical specifications that describe the semantics and allowed values for the property.

**Consuming references:** One or more technical specifications that refer to the property but do not describe semantics and allowed values.

### 1.3.1 Common Message Classes

Applications set certain required properties corresponding to the object's **message class**. The following table describes several common message classes, the functional area to which each one corresponds, and the specification that describes each one's required and optional properties.

In the following table, an asterisk "\*" denotes that any string can appear at that point.

Area name	PidTagMessageClass property values	Specification
Common	IPM.*	<a href="#">[MS-OXCMSG]</a>
Email	IPM.Note, REPORT.*	<a href="#">[MS-OXCMSG]</a>
Calendar	IPM.Appointment, IPM.Schedule.Meeting.Request, IPM.Schedule.Meeting.Resp.*, IPM.Schedule.Meeting.Canceled, IPM.Schedule.Meeting.Notification	<a href="#">[MS-OXOCAL]</a>
Contact	IPM.Contact, IPM DistList	<a href="#">[MS- OXOCNTC]</a>
Task	IPM.Task, IPM.TaskRequest.*	<a href="#">[MS- OXOTASK]</a>
Journal	IPM.Activity	<a href="#">[MS- OXOJRNL]</a>
Sticky Note	IPM.StickyNote	<a href="#">[MS- OXONOTE]</a>
Document	IPM.Document.*	<a href="#">[MS-OXODOC]</a>
Post	IPM.Post	<a href="#">[MS- OXOPOST]</a>
RSS Feed	IPM.Post.RSS	<a href="#">[MS-OXORSS]</a>
Rights-managed Email	IPM.Note with PidNameContentClass= rpmsg.message	<a href="#">[MS- OXORMMS]</a>
S/MIME Email	IPM.Note.SMIME, IPM.Note.SMIME.MultipartSigned	<a href="#">[MS- OXOSMIME]</a>
Short Message Service (SMS) / Multimedia Message Service (MMS) Message	IPM.Note.Mobile.SMS, IPM.Note.Mobile.MMS	<a href="#">[MS- OXOSMMS]</a>
Unified Messaging	IPM.Note.Microsoft.Voicemail, IPM.Note.Microsoft.Fax	<a href="#">[MS-OXOUM]</a>
Sharing	IPM.Sharing IPM.Sharing.*	<a href="#">[MS- OXSHARE]</a>

### 1.3.2 Commonly Used Property Sets

Each **named property** specified in the list in section 2 is listed with the **GUID** that describes its **property set**. Several of the more common property sets and their functional areas are described in the following table.

Area name	Property set name and GUID value
Common	PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}
Common	PSETID_Common {00062008-0000-0000-C000-000000000046}
Contact	PSETID_Address {00062004-0000-0000-C000-000000000046}
Email	PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}
Calendar	PSETID_Appointment {00062002-0000-0000-C000-000000000046}
Calendar	PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}
Journal	PSETID_Log {0006200A-0000-0000-C000-000000000046}
Messaging	PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B0BFF}
Sticky note	PSETID_Note {0006200E-0000-0000-C000-000000000046}
RSS feed	PSETID_PostRss {00062041-0000-0000-C000-000000000046}
Task	PSETID_Task {00062003-0000-0000-C000-000000000046}
Unified messaging	PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}
Common	PS_MAPI {00020328-0000-0000-C000-000000000046}
Sync	PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}
Sharing	PSETID_Sharing {00062040-0000-0000-C000-000000000046}
Extracted entities	PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}
Attachment	PSETID_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

### 1.3.3 Property ID Ranges

The 65,536 possible values of the **property ID** are divided into sub-ranges reserved for various purposes, as described in the following table.

In this context, the term "non-transmittable" refers specifically to transmission via an email transport protocol (such as **SMTP**), and not to any network transport protocol (such as **TCP**):

- Servers do not allow property IDs in ranges specified as non-transmittable to be submitted for transport to another server via an email transport protocol. Property IDs in ranges not specified as non-transmittable are submitted for transport to another server.
- Clients can use properties in ranges described as **message class**-defined for application-defined purposes. When doing so, applications specify a value for the **PidTagMessageClass** property (section [2.787](#)) that is distinct from any value listed in section [1.3.1](#).
- Clients can use any **named property** for application-defined purposes. No constraint is placed on the value of the **PidTagMessageClass** property in this case, but the property set of the named property is distinct from any value listed in section [1.3.2](#). Note that named properties are transmittable.
- Clients can use properties in ranges specified as transport-defined, but they cannot define new properties in those ranges.
- Clients can use and define properties in ranges specified as user-defined, but need to avoid conflicts with alternate definitions of the same property ID.

Range minimum	Range maximum	Description
0x0001	0x0BFF	<b>Message object</b> envelope property; reserved
0x0C00	0x0DFF	<b>Recipient</b> property; reserved
0x0E00	0x0FFF	Non-transmittable Message property; reserved
0x1000	0x2FFF	Message content property; reserved
0x3000	0x33FF	Multi-purpose property that can appear on all or most objects; reserved
0x3400	0x35FF	<b>Message store</b> property; reserved
0x3600	0x36FF	Folder and <b>address book container</b> property; reserved
0x3700	0x38FF	Attachment property; reserved
0x3900	0x39FF	<b>Address Book object</b> property; reserved
0x3A00	0x3BFF	<b>Mail user</b> object property; reserved
0x3C00	0x3CFF	<b>Distribution list</b> property; reserved
0x3D00	0x3DFF	Profile section property; reserved
0x3E00	0x3EFF	Status object property; reserved
0x4000	0x57FF	Transport-defined envelope property
0x5800	0x5FFF	Transport-defined recipient property

Range minimum	Range maximum	Description
0x6000	0x65FF	User-defined non-transmittable property
0x6600	0x67FF	Provider-defined internal non-transmittable property
0x6800	0x7BFF	Message class-defined content property
0x7C00	0x7FFF	Message class-defined non-transmittable property
0x8000	0xFFFF	Reserved for mapping to named properties. The exceptions to this rule are some of the address book tagged properties (those with names beginning with PIDTagAddressBook). Many are static property IDs but are in this range.

### 1.3.4 WebDAV Property Naming

The email server is natively a **Messaging Application Programming Interface (MAPI) message store** where the vast majority of properties in it are MAPI properties. The **WebDAV** implementation uses the **Augmented Backus-Naur Form (ABNF)** notation, as described in [\[RFC5234\]](#), as a way to name MAPI properties, allowing Web Distributed Authoring and Versioning Protocol (WebDAV) clients to work with these properties directly.

The `http://schemas.microsoft.com/mapi/` namespace is used to access MAPI properties directly on the server. The namespace consists of three sub namespaces: `proptag`, `id`, and `string`. The ABNF notation used to specify the format of these namespaces is described in this section.

#### 1.3.4.1 `http://schemas.microsoft.com/mapi/proptag` Namespace

The `http://schemas.microsoft.com/mapi/proptag` namespace is used to access properties on the server that are identified by a **property ID**. The implementer can access these properties through **WebDAV** by appending the hexadecimal property ID value and the hexadecimal **property type** value to the namespace prefix.

```
proptag-specifier = "http://schemas.microsoft.com/mapi/proptag/x" property-id property-type
property-id      = 4HEXDIG
property-type    = 4HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/proptag/x0037001f (PidTagSubject)
```

#### 1.3.4.2 `http://schemas.microsoft.com/mapi/id` Namespace

The `http://schemas.microsoft.com/mapi/id` namespace is used to access **named properties** on the server that are identified by a property **long ID (LID)**. The implementer can access these properties through WebDAV by appending the **property set** and the hexadecimal property long ID (LID) value to the namespace prefix.

```
id-specifier = "http://schemas.microsoft.com/mapi/id/" property-set "/" property-long-id
```

```
property-set = "{" 8HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 12HEXDIG "}"  
property-long-id = 8HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/id/{00062002-0000-0000-C000-000000000046}/x00008213  
(PidLidAppointmentDuration)
```

### 1.3.4.3 <http://schemas.microsoft.com/mapi/string> Namespace

The <http://schemas.microsoft.com/mapi/string> namespace is used to access **named properties** on the server that are identified by a **property name**. The implementer can access these properties through WebDAV by appending the **property set** and the property name to the namespace prefix.

```
string-specifier = "http://schemas.microsoft.com/mapi/string/" property-set "/" property-name  
property-set = "{" 8*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 12*HEXDIG "}"  
property-name = 1*CHAR
```

Example:

```
http://schemas.microsoft.com/mapi/string/{00020329-0000-0000-C000-000000000046}/Subject  
(PidNameSubject)
```

## 1.4 Relationship to Protocols and Other Structures

This document relies on property data type and error code definitions in [\[MS-OXCDATA\]](#). For tables and examples that describe property data types, and property and other error codes, see [\[MS-OXCDATA\]](#).

The list of properties and their descriptions included in this document provide context for many of the data structures described in [\[MS-OXCDATA\]](#).

The description of each property contained in this document relies on the technical specification that is cited as its defining reference.

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

## 1.5 Applicability Statement

This document provides numeric values used to encode **property names**, tags, and data types in **ROP buffers**. It also serves as a convenient index to the object type documents that define how each property is used.

## 1.6 Versioning and Localization

None.



## 1.7 Vendor-Extensible Fields

**Property ID** ranges, as described in section [1.3.3](#), describe how applications choose properties to create new **Message object** types or to add functionality to existing types.

## 2 Structures

### 2.1 PidLidAddressBookProviderArrayType

**Canonical name:** PidLidAddressBookProviderArrayType

**Description:** Specifies the state of the electronic addresses of the **contact** and represents a set of bit **flags**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008029

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.12

**Alternate names:** dispidABPArrayType

### 2.2 PidLidAddressBookProviderEmailList

**Canonical name:** PidLidAddressBookProviderEmailList

**Description:** Specifies which electronic address properties are set on the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008028

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.11

**Alternate names:** dispidABPEmailList

### 2.3 PidLidAddressCountryCode

**Canonical name:** PidLidAddressCountryCode

**Description:** Specifies the country code portion of the mailing address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DD

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidAddressCountryCode

## 2.4 PidLidAgingDontAgeMe

**Canonical name:** PidLidAgingDontAgeMe

**Description:** Specifies whether to automatically archive the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000850E

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.33

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidAgingDontAgeMe

## 2.5 PidLidAllAttendeesString

**Canonical name:** PidLidAllAttendeesString

**Description:** Specifies a list of all the attendees except for the **organizer**, including **resources** and **unsendable attendees**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008238

**WebDAV:** <http://schemas.microsoft.com/mapi/allattendeesstring>

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.16

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidAllAttendeesString

## 2.6 PidLidAllowExternalCheck

**Canonical name:** PidLidAllowExternalCheck

**Description:** This property is set to TRUE.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008246

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.56.5

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidAllowExternCheck

## 2.7 PidLidAnniversaryEventEntryId

**Canonical name:** PidLidAnniversaryEventEntryId

**Description:** Specifies the **EntryID** of the **Appointment object** that represents an anniversary of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804E

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.6

**Alternate names:** dispidAnniversaryEventEID

## 2.8 PidLidAppointmentAuxiliaryFlags

**Canonical name:** PidLidAppointmentAuxiliaryFlags

**Description:** Specifies a bit field that describes the auxiliary state of the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008207

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.3

**Alternate names:** dispidApptAuxFlags

## 2.9 PidLidAppointmentColor

**Canonical name:** PidLidAppointmentColor

**Description:** Specifies the color to be used when displaying the **Calendar object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008214

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.50

**Alternate names:** dispidApptColor

## 2.10 PidLidAppointmentCounterProposal

**Canonical name:** PidLidAppointmentCounterProposal

**Description:** Indicates whether a **Meeting Response object** is a **counter proposal**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008257

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.7

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptCounterProposal

## 2.11 PidLidAppointmentDuration

**Canonical name:** PidLidAppointmentDuration

**Description:** Specifies the length of the event, in minutes.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008213

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/apptduration

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptDuration

## 2.12 PidLidAppointmentEndDate

**Canonical name:** PidLidAppointmentEndDate

**Description:** Indicates the date that the appointment ends.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008211

**WebDAV:** http://schemas.microsoft.com/mapi/apptenddate

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.3

**Alternate names:** dispidApptEndDate

## 2.13 PidLidAppointmentEndTime

**Canonical name:** PidLidAppointmentEndTime

**Description:** Indicates the time that the appointment ends.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008210

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptendtime>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.4

**Alternate names:** dispidApptEndTime

## 2.14 PidLidAppointmentEndWhole

**Canonical name:** PidLidAppointmentEndWhole

**Description:** Specifies the end date and time for the event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820E

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptendwhole>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.6

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptEndWhole

## 2.15 PidLidAppointmentLastSequence

**Canonical name:** PidLidAppointmentLastSequence

**Description:** Indicates to the **organizer** the last sequence number that was sent to any attendee.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008203

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.2

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptLastSequence

## 2.16 PidLidAppointmentMessageClass

**Canonical name:** PidLidAppointmentMessageClass

**Description:** Indicates the **message class** of the **Meeting object** to be generated from the **Meeting Request object**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000024

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.6

**Alternate names:** dispidApptMessageClass

## 2.17 PidLidAppointmentNotAllowPropose

**Canonical name:** PidLidAppointmentNotAllowPropose

**Description:** Indicates whether attendees are not allowed to propose a new date and/or time for the **meeting**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.26

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptNotAllowPropose

## 2.18 PidLidAppointmentProposalNumber

**Canonical name:** PidLidAppointmentProposalNumber

**Description:** Specifies the number of attendees who have sent **counter proposals** that have not been accepted or rejected by the **organizer**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008259

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.6

**Alternate names:** dispidApptProposalNum

## 2.19 PidLidAppointmentProposedDuration

**Canonical name:** PidLidAppointmentProposedDuration

**Description:** Indicates the proposed value for the **PidLidAppointmentDuration** property (section [2.11](#)) for a **counter proposal**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008256

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.5

**Alternate names:** dispidApptProposedDuration

## 2.20 PidLidAppointmentProposedEndWhole

**Canonical name:** PidLidAppointmentProposedEndWhole

**Description:** Specifies the proposed value for the **PidLidAppointmentEndWhole** property (section [2.14](#)) for a **counter proposal**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008251

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.4

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposedEndWhole

## 2.21 PidLidAppointmentProposedStartWhole

**Canonical name:** PidLidAppointmentProposedStartWhole

**Description:** Specifies the proposed value for the **PidLidAppointmentStartWhole** property (section [2.29](#)) for a **counter proposal**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008250

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.3

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposedStartWhole

## 2.22 PidLidAppointmentRecur

**Canonical name:** PidLidAppointmentRecur



**Description:** Specifies the dates and times when a **recurring series** occurs.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008216

**Data type:** PtypBinary, 0x0102

**WebDAV:** http://schemas.microsoft.com/mapi/apptrecur

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.44

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptRecur

### 2.23 PidLidAppointmentReplyName

**Canonical name:** PidLidAppointmentReplyName

**Description:** Specifies the user who last replied to the **meeting request** or **meeting** update.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008230

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/apptreplyname

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.5

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptReplyName, http://schemas.microsoft.com/mapi/apptreplyname

### 2.24 PidLidAppointmentReplyTime

**Canonical name:** PidLidAppointmentReplyTime

**Description:** Specifies the date and time at which the attendee responded to a received **meeting request** or **Meeting Update object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008220

**Data type:** PtypTime, 0x0040

**WebDAV:** urn:schemas:calendar:replytime, http://schemas.microsoft.com/mapi/apptreplytime

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.3

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptReplyTime

## 2.25 PidLidAppointmentSequence

**Canonical name:** PidLidAppointmentSequence

**Description:** Specifies the sequence number of a **Meeting object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008201

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/apptsequence

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptSequence

## 2.26 PidLidAppointmentSequenceTime

**Canonical name:** PidLidAppointmentSequenceTime

**Description:** Indicates the date and time at which the **PidLidAppointmentSequence** property (section [2.25](#)) was last modified.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008202

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.1

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptSeqTime

## 2.27 PidLidAppointmentStartDate

**Canonical name:** PidLidAppointmentStartDate

**Description:** Identifies the date that the appointment starts.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008212

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptstartdate

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.10

**Alternate names:** dispidApptStartDate

## 2.28 PidLidAppointmentStartTime

**Canonical name:** PidLidAppointmentStartTime

**Description:** Identifies the time that the appointment starts.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820F

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptstarttime

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.11

**Alternate names:** dispidApptStartTime

## 2.29 PidLidAppointmentStartWhole

**Canonical name:** PidLidAppointmentStartWhole

**Description:** Specifies the start date and time of the appointment.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820D

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptstartwhole

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptStartWhole

## 2.30 PidLidAppointmentStateFlags

**Canonical name:** PidLidAppointmentStateFlags

**Description:** Specifies a bit field that describes the state of the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008217

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/apptstateflags

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.10

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptStateFlags

### 2.31 PidLidAppointmentSubType

**Canonical name:** PidLidAppointmentSubType

**Description:** Specifies whether the event is an all-day event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008215

**Data type:** PtypBoolean, 0x000B

**WebDAV:** urn:schemas:calendar:alldayevent, <http://schemas.microsoft.com/mapi/apptsubtype>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptSubType

### 2.32 PidLidAppointmentTimeZoneDefinitionEndDisplay

**Canonical name:** PidLidAppointmentTimeZoneDefinitionEndDisplay

**Description:** Specifies time zone information that indicates the time zone of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825F

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.43

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptTZDefEndDisplay

### 2.33 PidLidAppointmentTimeZoneDefinitionRecur

**Canonical name:** PidLidAppointmentTimeZoneDefinitionRecur

**Description:** Specifies time zone information that describes how to convert the **meeting** date and time on a **recurring series** to and from **UTC**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008260

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.41

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** dispidApptTZDefRecur

### 2.34 PidLidAppointmentTimeZoneDefinitionStartDisplay

**Canonical name:** PidLidAppointmentTimeZoneDefinitionStartDisplay

**Description:** Specifies time zone information that indicates the time zone of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825E

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.42

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptTZDefStartDisplay

### 2.35 PidLidAppointmentUnsendableRecipients

**Canonical name:** PidLidAppointmentUnsendableRecipients

**Description:** Contains a list of **unsendable attendees**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825D

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.25

**Alternate names:** dispidApptUnsendableRecips

### 2.36 PidLidAppointmentUpdateTime

**Canonical name:** PidLidAppointmentUpdateTime

**Description:** Indicates the time at which the appointment was last updated.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008226

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptupdatetime>

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.15

**Alternate names:** dispidApptUpdateTime

### 2.37 PidLidAttendeeCriticalChange

**Canonical name:** PidLidAttendeeCriticalChange

**Description:** Specifies the date and time at which the **meeting-related object** was sent.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000001

**Data type:** PtypTime, 0x0040

**WebDAV:** [http://schemas.microsoft.com/mapi/attendee\\_critical\\_change](http://schemas.microsoft.com/mapi/attendee_critical_change)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_ATTENDEE\_CRITICAL\_CHANGE

### 2.38 PidLidAutoFillLocation

**Canonical name:** PidLidAutoFillLocation

**Description:** Indicates whether the value of the **PidLidLocation** property (section [2.159](#)) is set to the **PidTagDisplayName** property (section [2.676](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.8

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidAutoFillLocation

### 2.39 PidLidAutoLog

**Canonical name:** PidLidAutoLog

**Description:** Specifies to the application whether to create a **Journal object** for each **action** associated with this Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008025

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.19

**Alternate names:** dispidAutoLog

## 2.40 PidLidAutoProcessState

**Canonical name:** PidLidAutoProcessState

**Description:** Specifies the options used in the automatic processing of email messages.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851A

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.73

**Alternate names:** dispidSniffState

## 2.41 PidLidAutoStartCheck

**Canonical name:** PidLidAutoStartCheck

**Description:** Specifies whether to automatically start the conferencing application when a **reminder** for the start of a **meeting** is executed.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008244

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.56.1

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidAutoStartCheck

## 2.42 PidLidBilling

**Canonical name:** PidLidBilling

**Description:** Specifies billing information for the **contact**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008535

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:billinginformation

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.24

**Alternate names:** dispidBilling

### 2.43 PidLidBirthdayEventEntryId

**Canonical name:** PidLidBirthdayEventEntryId

**Description:** Specifies the **EntryID** of an optional **Appointment object** that represents the birthday of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804D

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.3

**Alternate names:** dispidBirthdayEventEID

### 2.44 PidLidBirthdayLocal

**Canonical name:** PidLidBirthdayLocal

**Description:** Specifies the birthday of a **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DE

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.2

**Alternate names:** dispidApptBirthdayLocal

### 2.45 PidLidBusinessCardCardPicture

**Canonical name:** PidLidBusinessCardCardPicture

**Description:** Contains the image to be used on a business card.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008041

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.2

**Alternate names:** dispidBCCardPicture

### 2.46 PidLidBusinessCardDisplayDefinition

**Canonical name:** PidLidBusinessCardDisplayDefinition



**Description:** Contains user customization details for displaying a **contact** as a business card.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008040

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidBCDisplayDefinition

## 2.47 PidLidBusyStatus

**Canonical name:** PidLidBusyStatus

**Description:** Specifies the availability of a user for the event described by the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008205

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/busystatus>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidBusyStatus

## 2.48 PidLidCalendarType

**Canonical name:** PidLidCalendarType

**Description:** Contains the value of the **CalendarType** field from the **PidLidAppointmentRecur** property (section [2.22](#)).

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000001C

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/calendar\\_type](http://schemas.microsoft.com/mapi/calendar_type)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.11

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_CALENDAR\_TYPE

## 2.49 PidLidCategories

**Canonical name:** PidLidCategories

**Description:** Contains the array of text labels assigned to this **Message object**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00009000

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.22

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidCategories

## 2.50 PidLidCcAttendeesString

**Canonical name:** PidLidCcAttendeesString

**Description:** Contains a list of all the sendable attendees who are also **optional attendees**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823C

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.18

**Alternate names:** dispidCCAttendeesString

## 2.51 PidLidChangeHighlight

**Canonical name:** PidLidChangeHighlight

**Description:** Specifies a bit field that indicates how the **Meeting object** has changed.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008204

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.2

**Consuming reference:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidChangeHighlight

## 2.52 PidLidClassification

**Canonical name:** PidLidClassification

**Description:** Contains a list of the classification categories to which the associated **Message object** has been assigned.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B6

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.23

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassification

### 2.53 PidLidClassificationDescription

**Canonical name:** PidLidClassificationDescription

**Description:** Contains a human-readable summary of each of the classification categories included in the **PidLidClassification** property (section 2.53).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B7

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.24

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassDesc

### 2.54 PidLidClassificationGuid

**Canonical name:** PidLidClassificationGuid

**Description:** Contains the **GUID** that identifies the list of email classification categories used by a **Message object**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B8

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.1

**Alternate names:** dispidClassGuid

### 2.55 PidLidClassificationKeep

**Canonical name:** PidLidClassificationKeep

**Description:** Indicates whether the message uses any classification categories.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BA

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.2

**Alternate names:** dispidClassKeep

## 2.56 PidLidClassified

**Canonical name:** PidLidClassified

**Description:** Indicates whether the contents of this message are regarded as classified information.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B5

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.25

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassified

## 2.57 PidLidCleanGlobalObjectId

**Canonical name:** PidLidCleanGlobalObjectId

**Description:** Contains the value of the **PidLidGlobalObjectId** property (section [2.142](#)) for an object that represents an **Exception object** to a **recurring series**, where the Year, Month, and Day fields are all zero.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000023

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.28

**Consuming references:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidCleanGlobalObjId

## 2.58 PidLidClientIntent

**Canonical name:** PidLidClientIntent

**Description:** Indicates what **actions** the user has taken on this **Meeting object**.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x00000015

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.2.4

**Alternate names:** dispidClientIntent

## 2.59 PidLidClipEnd

**Canonical name:** PidLidClipEnd

**Description:** Specifies the end date and time of the event in **UTC**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008236

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.15

**Alternate names:** dispidClipEnd

## 2.60 PidLidClipStart

**Canonical name:** PidLidClipStart

**Description:** Specifies the start date and time of the event in **UTC**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008235

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.14

**Alternate names:** dispidClipStart

## 2.61 PidLidCollaborateDoc

**Canonical name:** PidLidCollaborateDoc

**Description:** Specifies the document to be launched when the user joins the **meeting**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008247

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.56.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidCollaborateDoc

## 2.62 PidLidCommonEnd

**Canonical name:** PidLidCommonEnd

**Description:** Indicates the end time for the **Message object**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008517

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.19

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidCommonEnd

## 2.63 PidLidCommonStart

**Canonical name:** PidLidCommonStart

**Description:** Indicates the start time for the **Message object**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008516

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.18

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidCommonStart

## 2.64 PidLidCompanies

**Canonical name:** PidLidCompanies

**Description:** Contains a list of company names, each of which is associated with a **contact** that is specified in the PidLidContacts property ([\[MS-OXCMSG\]](#) section 2.2.1.57.2).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008539

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.2.4

**Alternate names:** dispidCompanies, <http://schemas.microsoft.com/exchange/companies>

## 2.65 PidLidConferencingCheck

**Canonical name:** PidLidConferencingCheck

**Description:** When set to TRUE (0x00000001), the PidLidConferencingCheck property indicates that the associated **meeting** is one of the following types:

- "Windows Media Services"
- "Windows NetMeeting"
- "Exchange Conferencing"

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008240

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.56.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidConfCheck

## 2.66 PidLidConferencingType

**Canonical name:** PidLidConferencingType

**Description:** Specifies the type of the **meeting**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008241

**Data type:** PtypInteger32, 0x0003

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.56.3

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidConfType

## 2.67 PidLidContactCharacterSet

**Canonical name:** PidLidContactCharacterSet

**Description:** Specifies the character set used for a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008023

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.18

**Alternate names:** dispidContactCharSet

## 2.68 PidLidContactItemData

**Canonical name:** PidLidContactItemData

**Description:** Specifies the visible fields in the application's user interface that are used to help display the **contact** information.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008007

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.22

**Alternate names:** dispidContactItemData

## 2.69 PidLidContactLinkedGlobalAddressListEntryId

**Canonical name:** PidLidContactLinkedGlobalAddressListEntryId

**Description:** Specifies the **EntryID** of the **GAL contact** to which the duplicate contact is linked.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E2

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.1

**Alternate names:** dispidContactLinkedGAEntryID

## 2.70 PidLidContactLinkEntry

**Canonical name:** PidLidContactLinkEntry

**Description:** Contains the elements of the **PidLidContacts** property (section [2.77](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008585

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties



**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.1

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContactLinkEntry

### 2.71 PidLidContactLinkGlobalAddressListLinkId

**Canonical name:** PidLidContactLinkGlobalAddressListLinkId

**Description:** Specifies the **GUID** of the **GAL contact** to which the duplicate contact is linked.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E8

**Data type:** PtypGuid, 0x0048

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.2

**Alternate names:** dispidContactLinkGALLinkID

### 2.72 PidLidContactLinkGlobalAddressListLinkState

**Canonical name:** PidLidContactLinkGlobalAddressListLinkState

**Description:** Specifies the state of the linking between the **GAL contact** and the duplicate contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E6

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.3

**Alternate names:** dispidContactLinkGALLinkState

### 2.73 PidLidContactLinkLinkRejectHistory

**Canonical name:** PidLidContactLinkLinkRejectHistory

**Description:** Contains a list of **GAL contacts** that were previously rejected for linking with the duplicate contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E5

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.4

**Alternate names:** dispidContactLinkLinkRejectHistory

## 2.74 PidLidContactLinkName

**Canonical name:** PidLidContactLinkName

**Description:**

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008586

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.3

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContactLinkName

## 2.75 PidLidContactLinkSearchKey

**Canonical name:** PidLidContactLinkSearchKey

**Description:** Contains the list of SearchKeys for a Contact object linked to by the **Message object**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008584

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.4

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContactLinkSearchKey

## 2.76 PidLidContactLinkSMTPAddressCache

**Canonical name:** PidLidContactLinkSMTPAddressCache

**Description:** Contains a list of the **SMTP** addresses that are used by the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E3

**Data type:** PtypMultipleString, 0x101F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.5

**Alternate names:** dispidContactLinkSMTPAddressCache

## 2.77 PidLidContacts

**Canonical name:** PidLidContacts

**Description:** Contains the **PidTagDisplayName** property (section [2.676](#)) of each Address Book **EntryID** referenced in the value of the **PidLidContactLinkEntry** property (section [2.70](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000853A

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContacts

## 2.78 PidLidContactUserField1

**Canonical name:** PidLidContactUserField1

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804F

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute1

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField1

## 2.79 PidLidContactUserField2

**Canonical name:** PidLidContactUserField2

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008050

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute2

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField2

## 2.80 PidLidContactUserField3

**Canonical name:** PidLidContactUserField3

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008051

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute3

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField3

## 2.81 PidLidContactUserField4

**Canonical name:** PidLidContactUserField4

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008052

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute4

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField4

## 2.82 PidLidConversationActionLastAppliedTime

**Canonical name:** PidLidConversationActionLastAppliedTime

**Description:** Contains the time, in **UTC**, that an **Email object** was last received in the **conversation**, or the last time that the user modified the **conversation action**, whichever occurs later.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085CA

**Data type:** PtypTime, 0x0040

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.1

**Alternate names:** dispidConvActionLastAppliedTime

### 2.83 PidLidConversationActionMaxDeliveryTime

**Canonical name:** PidLidConversationActionMaxDeliveryTime

**Description:** Contains the maximum value of the **PidTagMessageDeliveryTime** property (section [2.789](#)) of all of the **Email objects** modified in response to the last time that the user changed a **conversation action** on the client.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C8

**Data type:** PtypTime, 0x0040

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.2

**Alternate names:** dispidConvActionMaxDeliveryTime

### 2.84 PidLidConversationActionMoveFolderEid

**Canonical name:** PidLidConversationActionMoveFolderEid

**Description:** Contains the **EntryID** for the destination folder.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C6

**Data type:** PtypBinary, 0x0102

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.3

**Alternate names:** dispidConvActionMoveFolderEid

### 2.85 PidLidConversationActionMoveStoreEid

**Canonical name:** PidLidConversationActionMoveStoreEid

**Description:** Contains the **EntryID** for a move to a folder in a different **message store**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C7

**Data type:** PtypBinary, 0x0102

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.4

**Alternate names:** dispidConvActionMoveStoreEid

## 2.86 PidLidConversationActionVersion

**Canonical name:** PidLidConversationActionVersion

**Description:** Contains the version of the **conversation action FAI** message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085CB

**Data type:** PtypInteger32, 0x0003

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.5

**Alternate names:** dispidConvActionVersion

## 2.87 PidLidConversationProcessed

**Canonical name:** PidLidConversationProcessed

**Description:** Specifies a sequential number to be used in the processing of a **conversation action**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C9

**Data type:** PtypInteger32, 0x0003

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.6

**Alternate names:** dispidConvExLegacyProcessedRand

## 2.88 PidLidCurrentVersion

**Canonical name:** PidLidCurrentVersion

**Description:** Specifies the build number of the client application that sent the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008552

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.34

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidCurrentVersion

## 2.89 PidLidCurrentVersionName

**Canonical name:** PidLidCurrentVersionName

**Description:** Specifies the name of the client application that sent the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008554

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.35

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidCurrentVersionName

## 2.90 PidLidDayInterval

**Canonical name:** PidLidDayInterval

**Description:** Identifies the day interval for the **recurrence pattern**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000011

**Data type:** PtypInteger16, 0x0002

**WebDAV:** [http://schemas.microsoft.com/mapi/day\\_interval](http://schemas.microsoft.com/mapi/day_interval)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.19

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_DAY\_INTERVAL

## 2.91 PidLidDayOfMonth

**Canonical name:** PidLidDayOfMonth

**Description:** Identifies the day of the month for the appointment or **meeting**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001000

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/dayofmonth>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.20

## 2.92 PidLidDelegateMail

**Canonical name:** PidLidDelegateMail

**Description:** Indicates whether a **delegate** responded to the **meeting request**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000009

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/delegate\_mail

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.21

**Alternate names:** LID\_DELEGATE\_MAIL

## 2.93 PidLidDepartment

**Canonical name:** PidLidDepartment

**Description:** This property is ignored by the server and is set to an empty string by the client.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008010

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.4

**Alternate names:** dispidDepartment

## 2.94 PidLidDirectory

**Canonical name:** PidLidDirectory

**Description:** Specifies the directory server to be used.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008242

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.56.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidDirectory

## 2.95 PidLidDistributionListChecksum

**Canonical name:** PidLidDistributionListChecksum



**Description:** Specifies the 32-bit **cyclic redundancy check (CRC)** polynomial checksum, as specified in [\[ISO/IEC8802-3\]](#), calculated on the value of the **PidLidDistributionListMembers** property (section [2.96](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804C

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.3

**Alternate names:** dispidDLChecksum

## 2.96 PidLidDistributionListMembers

**Canonical name:** PidLidDistributionListMembers

**Description:** Specifies the list of **EntryIDs** of the objects corresponding to the members of the personal **distribution list**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008055

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.1

**Alternate names:** dispidDLMembers

## 2.97 PidLidDistributionListName

**Canonical name:** PidLidDistributionListName

**Description:** Specifies the name of the personal **distribution list**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008053

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.1.2

**Alternate names:** dispidDLName

## 2.98 PidLidDistributionListOneOffMembers

**Canonical name:** PidLidDistributionListOneOffMembers

**Description:** Specifies the list of one-off **EntryIDs** corresponding to the members of the personal **distribution list**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008054

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.2

**Alternate names:** dispidDLOneOffMembers

## 2.99 PidLidDistributionListStream

**Canonical name:** PidLidDistributionListStream

**Description:** Specifies the list of **EntryIDs** and one-off EntryIDs corresponding to the members of the personal **distribution list**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008064

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.4

**Alternate names:** dispidDLStream

## 2.100 PidLidEmail1AddressType

**Canonical name:** PidLidEmail1AddressType

**Description:** Specifies the **address type** of an electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008082

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1AddrType

## 2.101 PidLidEmail1DisplayName

**Canonical name:** PidLidEmail1DisplayName

**Description:** Specifies the user-readable **display name** for the email address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008080

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1DisplayName

## 2.102 PidLidEmail1EmailAddress

**Canonical name:** PidLidEmail1EmailAddress

**Description:** Specifies the email address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008083

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1EmailAddress

## 2.103 PidLidEmail1OriginalDisplayName

**Canonical name:** PidLidEmail1OriginalDisplayName

**Description:** Specifies the **SMTP** email address that corresponds to the email address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008084

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

**Alternate names:** dispidEmail1OriginalDisplayName, Email1OriginalDisplayName, EXSCHEMA\_MAPI\_EMAIL1ORIGINALDISPLAYNAME

## 2.104 PidLidEmail1OriginalEntryId

**Canonical name:** PidLidEmail1OriginalEntryId

**Description:** Specifies the **EntryID** of the object corresponding to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008085

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

**Alternate names:** dispidEmail1OriginalEntryID

### 2.105 PidLidEmail2AddressType

**Canonical name:** PidLidEmail2AddressType

**Description:** Specifies the **address type** of the electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008092

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2AddrType

### 2.106 PidLidEmail2DisplayName

**Canonical name:** PidLidEmail2DisplayName

**Description:** Specifies the user-readable **display name** for the email address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008090

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2DisplayName

### 2.107 PidLidEmail2EmailAddress

**Canonical name:** PidLidEmail2EmailAddress

**Description:** Specifies the email address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008093

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2EmailAddress

### 2.108 PidLidEmail2OriginalDisplayName

**Canonical name:** PidLidEmail2OriginalDisplayName

**Description:** Specifies the **SMTP** email address that corresponds to the email address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008094

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

**Alternate names:** dispidEmail2OriginalDisplayName

### 2.109 PidLidEmail2OriginalEntryId

**Canonical name:** PidLidEmail2OriginalEntryId

**Description:** Specifies the **EntryID** of the object that corresponds to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008095

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

**Alternate names:** dispidEmail2OriginalEntryID

### 2.110 PidLidEmail3AddressType

**Canonical name:** PidLidEmail3AddressType

**Description:** Specifies the **address type** of the electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3AddrType

### 2.111 PidLidEmail3DisplayName

**Canonical name:** PidLidEmail3DisplayName

**Description:** Specifies the user-readable **display name** for the email address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A0

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3DisplayName

### 2.112 PidLidEmail3EmailAddress

**Canonical name:** PidLidEmail3EmailAddress

**Description:** Specifies the email address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3EmailAddress

### 2.113 PidLidEmail3OriginalDisplayName

**Canonical name:** PidLidEmail3OriginalDisplayName

**Description:** Specifies the **SMTP** email address that corresponds to the email address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

**Alternate names:** dispidEmail3OriginalDisplayName

### 2.114 PidLidEmail3OriginalEntryId

**Canonical name:** PidLidEmail3OriginalEntryId

**Description:** Specifies the **EntryID** of the object that corresponds to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

**Alternate names:** dispidEmail3OriginalEntryID

### 2.115 PidLidEndRecurrenceDate

**Canonical name:** PidLidEndRecurrenceDate

**Description:** Identifies the end date of the recurrence range.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000F

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/end\\_recur\\_date](http://schemas.microsoft.com/mapi/end_recur_date)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.22

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_END\_RECUR\_DATE

### 2.116 PidLidEndRecurrenceTime

**Canonical name:** PidLidEndRecurrenceTime

**Description:** Identifies the end time of the recurrence range.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000010

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/end\\_recur\\_time](http://schemas.microsoft.com/mapi/end_recur_time)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.23

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_END\_RECUR\_TIME

## 2.117 PidLidExceptionReplaceTime

**Canonical name:** PidLidExceptionReplaceTime

**Description:** Specifies the date and time, in **UTC**, within a **recurrence pattern** that an exception will replace.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008228

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.2.5

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidExceptionReplaceTime

## 2.118 PidLidFax1AddressType

**Canonical name:** PidLidFax1AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

**Alternate names:** dispidFax1AddrType

## 2.119 PidLidFax1EmailAddress

**Canonical name:** PidLidFax1EmailAddress

**Description:** Contains a user-readable **display name**, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

**Alternate names:** dispidFax1EmailAddress

## 2.120 PidLidFax1OriginalDisplayName

**Canonical name:** PidLidFax1OriginalDisplayName



**Description:** Contains the same value as the **PidTagNormalizedSubject** property (section [2.812](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

**Alternate names:** dispidFax1OriginalDisplayName

### 2.121 PidLidFax1OriginalEntryId

**Canonical name:** PidLidFax1OriginalEntryId

**Description:** Specifies a one-off **EntryID** that corresponds to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

**Alternate names:** dispidFax1OriginalEntryID

### 2.122 PidLidFax2AddressType

**Canonical name:** PidLidFax2AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

**Alternate names:** dispidFax2AddrType

### 2.123 PidLidFax2EmailAddress

**Canonical name:** PidLidFax2EmailAddress

**Description:** Contains a user-readable **display name**, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

**Alternate names:** dispidFax2EmailAddress

### 2.124 PidLidFax2OriginalDisplayName

**Canonical name:** PidLidFax2OriginalDisplayName

**Description:** Contains the same value as the **PidTagNormalizedSubject** property (section [2.812](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

**Alternate names:** dispidFax2OriginalDisplayName

### 2.125 PidLidFax2OriginalEntryId

**Canonical name:** PidLidFax2OriginalEntryId

**Description:** Specifies a one-off **EntryID** corresponding to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

**Alternate names:** dispidFax2OriginalEntryID

### 2.126 PidLidFax3AddressType

**Canonical name:** PidLidFax3AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

**Alternate names:** dispidFax3AddrType

## 2.127 PidLidFax3EmailAddress

**Canonical name:** PidLidFax3EmailAddress

**Description:** Contains a user-readable **display name**, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

**Alternate names:** dispidFax3EmailAddress

## 2.128 PidLidFax3OriginalDisplayName

**Canonical name:** PidLidFax3OriginalDisplayName

**Description:** Contains the same value as the **PidTagNormalizedSubject** property (section [2.812](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

**Alternate names:** dispidFax3OriginalDisplayName

## 2.129 PidLidFax3OriginalEntryId

**Canonical name:** PidLidFax3OriginalEntryId

**Description:** Specifies a one-off **EntryID** that corresponds to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

**Alternate names:** dispidFax3OriginalEntryID

## 2.130 PidLidFExceptionalAttendees

**Canonical name:** PidLidFExceptionalAttendees

**Description:** Indicates that the object is a **Recurring Calendar object** with one or more exceptions, and that at least one of the **Exception Embedded Message objects** has at least one **RecipientRow** structure, as described in [\[MS-OXCDATA\]](#) section 2.8.3.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822B

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.2.3

**Consuming reference:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidFExceptionalAttendees

### 2.131 PidLidFExceptionalBody

**Canonical name:** PidLidFExceptionalBody

**Description:** Indicates that the **Exception Embedded Message object** has a body that differs from the **Recurring Calendar object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008206

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.2.6

**Alternate names:** dispidFExceptionalBody

### 2.132 PidLidFileUnder

**Canonical name:** PidLidFileUnder

**Description:** Specifies the name under which to file a **contact** when displaying a list of contacts.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008005

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.11

**Alternate names:** dispidFileUnder

### 2.133 PidLidFileUnderId

**Canonical name:** PidLidFileUnderId

**Description:** Specifies how to generate and recompute the value of the **PidLidFileUnder** property (section [2.132](#)) when other **contact** name properties change.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008006

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.12

**Alternate names:** dispidFileUnderId

### 2.134 PidLidFileUnderList

**Canonical name:** PidLidFileUnderList

**Description:** Specifies a list of possible values for the **PidLidFileUnderId** property (section [2.133](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008026

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.13

**Alternate names:** dispidFileUnderList

### 2.135 PidLidFInvited

**Canonical name:** PidLidFInvited

**Description:** Indicates whether invitations have been sent for the **meeting** that this **Meeting object** represents.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008229

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/invited

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidFInvited

### 2.136 PidLidFlagRequest

**Canonical name:** PidLidFlagRequest

**Description:** Contains user-specifiable text to be associated with the flag.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008530

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:httpmail:messageflag, http://schemas.microsoft.com/mapi/request

**Area:** Flagging

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidRequest

### 2.137 PidLidFlagString

**Canonical name:** PidLidFlagString

**Description:** Contains an index identifying one of a set of pre-defined text strings to be associated with the flag.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C0

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.10

**Alternate names:** dispidFlagStringEnum

### 2.138 PidLidForwardInstance

**Canonical name:** PidLidForwardInstance

**Description:** Indicates whether the **Meeting Request object** represents an exception to a **recurring series**, and whether it was forwarded (even when forwarded by the **organizer**) rather than being an invitation sent by the organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.3

**Alternate names:** dispidFwrInstance

### 2.139 PidLidForwardNotificationRecipients

**Canonical name:** PidLidForwardNotificationRecipients

**Description:** Contains a list of **RecipientRow** structures, as described in [\[MS-OXCDATA\]](#) section 2.8.3, that indicate the **recipients** of a **meeting** forward.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008261

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.9.3

**Alternate names:** dispidForwardNotificationRecipients

## 2.140 PidLidFOthersAppointment

**Canonical name:** PidLidFOthersAppointment

**Description:** Indicates whether the **Calendar folder** from which the **meeting** was opened is another user's **calendar**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822F

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.26

**Alternate names:** dispidFOthersAppt, <http://schemas.microsoft.com/mapi/fothersappt>

## 2.141 PidLidFreeBusyLocation

**Canonical name:** PidLidFreeBusyLocation

**Description:** Specifies a **URL** path from which a client can retrieve **free/busy status** information for the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D8

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:calendar:fburl

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.10

**Consuming references:** [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidFreeBusyLocation

## 2.142 PidLidGlobalObjectId

**Canonical name:** PidLidGlobalObjectId

**Description:** Contains an ID for an object that represents an exception to a **recurring series**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000003

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.27

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXWAVLS\]](#)

**Alternate names:** LID\_GLOBAL\_OBJID

### 2.143 PidLidHasPicture

**Canonical name:** PidLidHasPicture

**Description:** Specifies whether the attachment has a picture.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008015

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.8.1

**Alternate names:** dispidHasPicture

### 2.144 PidLidHomeAddress

**Canonical name:** PidLidHomeAddress

**Description:** Specifies the complete address of the home address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801A

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:homepostaladdress

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** dispidHomeAddress

### 2.145 PidLidHomeAddressCountryCode

**Canonical name:** PidLidHomeAddressCountryCode

**Description:** Specifies the country code portion of the home address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}



**Property long ID (LID):** 0x000080DA

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidHomeAddressCountryCode

## 2.146 PidLidHtml

**Canonical name:** PidLidHtml

**Description:** Specifies the business webpage URL of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802B

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.12

**Alternate names:** dispidHTML

## 2.147 PidLidICalendarDayOfWeekMask

**Canonical name:** PidLidICalendarDayOfWeekMask

**Description:** Identifies the day of the week for the appointment or **meeting**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001001

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.27

**Alternate names:** http://schemas.microsoft.com/mapi/dayofweekmask

## 2.148 PidLidInboundICalStream

**Canonical name:** PidLidInboundICalStream

**Description:** Contains the contents of the iCalendar **MIME part** of the original **MIME message**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000827A

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXCICAL\]](#) section 2.1.3.4.1

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InboundICalStream, dispidInboundICalStream

### 2.149 PidLidInfoPathFormName

**Canonical name:** PidLidInfoPathFormName

**Description:** Contains the name of the form associated with this message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B1

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.27

**Consuming reference:** [\[MS-OXCMAIL\]](#)

### 2.150 PidLidInstantMessagingAddress

**Canonical name:** PidLidInstantMessagingAddress

**Description:** Specifies the instant messaging address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008062

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.6

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidInstMsg

### 2.151 PidLidIntendedBusyStatus

**Canonical name:** PidLidIntendedBusyStatus

**Description:** Contains the value of the **PidLidBusyStatus** property (section [2.47](#)) on the **Meeting object** in the **organizer's calendar** at the time that the **Meeting Request object** or **Meeting Update object** was sent.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008224

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/intendedbusystatus

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidIntendedBusyStatus

### 2.152 PidLidInternetAccountName

**Canonical name:** PidLidInternetAccountName

**Description:** Specifies the user-visible email account name through which the email message is sent.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008580

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.62

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidInetAcctName

### 2.153 PidLidInternetAccountStamp

**Canonical name:** PidLidInternetAccountStamp

**Description:** Specifies the email account ID through which the email message is sent.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008581

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.63

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidInetAcctStamp

### 2.154 PidLidIsContactLinked

**Canonical name:** PidLidIsContactLinked

**Description:** Specifies whether the **contact** is linked to other contacts.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E0

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.6

**Alternate names:** dispidIsContactLinked

## 2.155 PidLidIsException

**Canonical name:** PidLidIsException

**Description:** Indicates whether the object represents an exception (including an **orphan instance**).

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000A

**Data type:** PtypBoolean, 0x000B

**WebDAV:** [http://schemas.microsoft.com/mapi/is\\_exception](http://schemas.microsoft.com/mapi/is_exception)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.35

**Consuming references:** [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_EXCEPTION

## 2.156 PidLidIsRecurring

**Canonical name:** PidLidIsRecurring

**Description:** Specifies whether the object is associated with a **recurring series**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000005

**Data type:** PtypBoolean, 0x000B

**WebDAV:** [http://schemas.microsoft.com/mapi/is\\_recurring](http://schemas.microsoft.com/mapi/is_recurring)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.13

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_RECURREN

## 2.157 PidLidIsSilent

**Canonical name:** PidLidIsSilent

**Description:** Indicates whether the user did not include any text in the body of the **Meeting Response object**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000004

**Data type:** PtypBoolean, 0x000B

**WebDAV:** [http://schemas.microsoft.com/mapi/is\\_silent](http://schemas.microsoft.com/mapi/is_silent)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.7

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_SILENT

## 2.158 PidLidLinkedTaskItems

**Canonical name:** PidLidLinkedTaskItems

**Description:** Indicates whether the user did not include any text in the body of the **Meeting Response object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820C

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Tasks

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.47

**Alternate names:** dispidLinkedTaskItems

## 2.159 PidLidLocation

**Canonical name:** PidLidLocation

**Description:** Specifies the location of the event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008208

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:calendar:location

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidLocation

## 2.160 PidLidLogDocumentPosted

**Canonical name:** PidLidLogDocumentPosted

**Description:** Indicates whether the document was sent by email or posted to a server folder during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008711

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.10

**Alternate names:** dispidLogDocPosted

### 2.161 PidLidLogDocumentPrinted

**Canonical name:** PidLidLogDocumentPrinted

**Description:** Indicates whether the document was printed during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870E

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.7

**Alternate names:** dispidLogDocPrinted

### 2.162 PidLidLogDocumentRouted

**Canonical name:** PidLidLogDocumentRouted

**Description:** Indicates whether the document was sent to a routing **recipient** during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008710

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.9

**Alternate names:** dispidLogDocRouted

### 2.163 PidLidLogDocumentSaved

**Canonical name:** PidLidLogDocumentSaved

**Description:** Indicates whether the document was saved during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870F

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.8

**Alternate names:** dispidLogDocSaved

## 2.164 PidLidLogDuration

**Canonical name:** PidLidLogDuration

**Description:** Contains the duration, in minutes, of the activity.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008707

**Data type:** PtypInteger32, 0x0003

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.5

**Alternate names:** dispidLogDuration

## 2.165 PidLidLogEnd

**Canonical name:** PidLidLogEnd

**Description:** Contains the time, in **UTC**, at which the activity ended.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008708

**Data type:** PtypTime, 0x0040

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.4

**Alternate names:** dispidLogEnd

## 2.166 PidLidLogFlags

**Canonical name:** PidLidLogFlags

**Description:** Contains metadata about the **Journal object**.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870C

**Data type:** PtypInteger32, 0x0003

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.6

**Alternate names:** dispidLogFlags

## 2.167 PidLidLogStart

**Canonical name:** PidLidLogStart

**Description:** Contains the time, in **UTC**, at which the activity began.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008706

**Data type:** PtypTime, 0x0040

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.3

**Alternate names:** dispidLogStart

## 2.168 PidLidLogType

**Canonical name:** PidLidLogType

**Description:** Briefly describes the journal activity that is being recorded.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008700

**Data type:** PtypString, 0x001F

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.1

**Alternate names:** dispidLogType

## 2.169 PidLidLogTypeDesc

**Canonical name:** PidLidLogTypeDesc

**Description:** Contains an expanded description of the journal activity that is being recorded.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008712

**Data type:** PtypString, 0x001F

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.2

**Alternate names:** dispidLogTypeDesc

## 2.170 PidLidMeetingType

**Canonical name:** PidLidMeetingType

**Description:** Indicates the type of **Meeting Request object** or **Meeting Update object**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000026

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.5



**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidMeetingType

### 2.171 PidLidMeetingWorkspaceUrl

**Canonical name:** PidLidMeetingWorkspaceUrl

**Description:** Specifies the **URL** of the **Meeting Workspace** that is associated with a **Calendar object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008209

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/meetingworkspaceurl

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.48

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidMWSURL

### 2.172 PidLidMonthInterval

**Canonical name:** PidLidMonthInterval

**Description:** Indicates the monthly interval of the appointment or **meeting**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000013

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/month\_interval

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.33

**Alternate names:** LID\_MONTH\_INTERVAL

### 2.173 PidLidMonthOfYear

**Canonical name:** PidLidMonthOfYear

**Description:** Indicates the month of the year in which the appointment or **meeting** occurs.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001006

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/monthofyear

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.34

### 2.174 PidLidMonthOfYearMask

**Canonical name:** PidLidMonthOfYearMask

**Description:** Indicates the calculated month of the year in which the appointment or **meeting** occurs.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000017

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/moy\\_mask](http://schemas.microsoft.com/mapi/moy_mask)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.35

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_MOY\_MASK

### 2.175 PidLidNetShowUrl

**Canonical name:** PidLidNetShowUrl

**Description:** Specifies the **URL** to be launched when the user joins the **meeting**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008248

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.56.8

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidNetShowURL

### 2.176 PidLidNoEndDateFlag

**Canonical name:** PidLidNoEndDateFlag

**Description:** Indicates whether the **recurrence pattern** has an end date.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000100B

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.36

**Alternate names:** <http://schemas.microsoft.com/mapi/fnoenddate>

### 2.177 PidLidNonSendableBcc

**Canonical name:** PidLidNonSendableBcc

**Description:** Contains a list of all of the **unsendable attendees** who are also resources.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008538

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/nosendablebcc>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.21

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableBCC

### 2.178 PidLidNonSendableCc

**Canonical name:** PidLidNonSendableCc

**Description:** Contains a list of all of the **unsendable attendees** who are also **optional attendees**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008537

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/nosendablecc>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.20

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableCC

### 2.179 PidLidNonSendableTo

**Canonical name:** PidLidNonSendableTo

**Description:** Contains a list of all of the **unsendable attendees** who are also required attendees.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008536

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/nosendableto>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.19

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableTo

### 2.180 PidLidNonSendBccTrackStatus

**Canonical name:** PidLidNonSendBccTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008545

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** <http://schemas.microsoft.com/mapi/nonsendbcctrackstatus>

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.24

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendBccTrackStatus

### 2.181 PidLidNonSendCcTrackStatus

**Canonical name:** PidLidNonSendCcTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008544

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** <http://schemas.microsoft.com/mapi/nonsendcctrackstatus>

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.23

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendCcTrackStatus

### 2.182 PidLidNonSendToTrackStatus

**Canonical name:** PidLidNonSendToTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008543

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** <http://schemas.microsoft.com/mapi/nonsendtotrackstatus>

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.22

**Consuming references:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendToTrackStatus

### 2.183 PidLidNoteColor

**Canonical name:** PidLidNoteColor

**Description:** Specifies the suggested background color of the **Note object**.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B00

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.1

**Alternate names:** dispidNoteColor

### 2.184 PidLidNoteHeight

**Canonical name:** PidLidNoteHeight

**Description:** Specifies the height of the visible message window in pixels.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B03

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.3

**Alternate names:** dispidNoteHeight

### 2.185 PidLidNoteWidth

**Canonical name:** PidLidNoteWidth

**Description:** Specifies the width of the visible message window in pixels.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B02

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.2

**Alternate names:** dispidNoteWidth

## 2.186 PidLidNoteX

**Canonical name:** PidLidNoteX

**Description:** Specifies the distance, in pixels, from the left edge of the screen that a user interface displays a **Note object**.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B04

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.4

**Alternate names:** dispidNoteX

## 2.187 PidLidNoteY

**Canonical name:** PidLidNoteY

**Description:** Specifies the distance, in pixels, from the top edge of the screen that a user interface displays a **Note object**.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B05

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.5

**Alternate names:** dispidNoteY

## 2.188 PidLidOccurrences

**Canonical name:** PidLidOccurrences

**Description:** Indicates the number of occurrences in the recurring appointment or **meeting**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001005

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/occurrences>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.43

## 2.189 PidLidOldLocation

**Canonical name:** PidLidOldLocation

**Description:** Indicates the original value of the **PidLidLocation** property (section [2.159](#)) before a **meeting** update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000028

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.7

**Alternate names:** dispidOldLocation

## 2.190 PidLidOldRecurrenceType

**Canonical name:** PidLidOldRecurrenceType

**Description:** Indicates the **recurrence pattern** for the appointment or **meeting**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000018

**Data type:** PtypInteger16, 0x0002

**WebDAV:** [http://schemas.microsoft.com/mapi/recur\\_type](http://schemas.microsoft.com/mapi/recur_type)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.44

**Alternate names:** LID\_RECUR\_TYPE

## 2.191 PidLidOldWhenEndWhole

**Canonical name:** PidLidOldWhenEndWhole

**Description:** Indicates the original value of the **PidLidAppointmentEndWhole** property (section [2.14](#)) before a **meeting** update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000002A

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.9

**Alternate names:** dispidOldWhenEndWhole

## 2.192 PidLidOldWhenStartWhole

**Canonical name:** PidLidOldWhenStartWhole

**Description:** Indicates the original value of the **PidLidAppointmentStartWhole** property (section [2.29](#)) before a **meeting** update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000029

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.8

**Alternate names:** dispidOldWhenStartWhole

### 2.193 PidLidOnlinePassword

**Canonical name:** PidLidOnlinePassword

**Description:** Specifies the password for a **meeting** on which the **PidLidConferencingType** property (section [2.66](#)) has the value 0x00000002.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008249

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.56.9

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidOnlinePassword

### 2.194 PidLidOptionalAttendees

**Canonical name:** PidLidOptionalAttendees

**Description:** Specifies **optional attendees**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000007

**Data type:** PtypString, 0x001F

**WebDAV:** [http://schemas.microsoft.com/mapi/optional\\_attendees](http://schemas.microsoft.com/mapi/optional_attendees)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.45

**Alternate names:** LID\_OPTIONAL\_ATTENDEES

### 2.195 PidLidOrganizerAlias

**Canonical name:** PidLidOrganizerAlias

**Description:** Specifies the email address of the **organizer**.



**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008243

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.56.6

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidOrgAlias

## 2.196 PidLidOriginalStoreEntryId

**Canonical name:** PidLidOriginalStoreEntryId

**Description:** Specifies the **EntryID** of the delegator's **message store**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008237

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.9

**Alternate names:** dispidOrigStoreEid, <http://schemas.microsoft.com/mapi/origstoreid>

## 2.197 PidLidOtherAddress

**Canonical name:** PidLidOtherAddress

**Description:** Specifies the complete address of the other address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801C

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:otherpostaladdress

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** dispidOtherAddress

## 2.198 PidLidOtherAddressCountryCode

**Canonical name:** PidLidOtherAddressCountryCode

**Description:** Specifies the country code portion of the other address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DC

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidOtherAddressCountryCode

## 2.199 PidLidOwnerCriticalChange

**Canonical name:** PidLidOwnerCriticalChange

**Description:** Specifies the date and time at which a **Meeting Request object** was sent by the **organizer**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000001A

**Data type:** PtypTime, 0x0040

**WebDAV:** urn:schemas:calendar:dtstamp,  
http://schemas.microsoft.com/mapi/owner\_critical\_change

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.34

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_OWNER\_CRITICAL\_CHANGE

## 2.200 PidLidOwnerName

**Canonical name:** PidLidOwnerName

**Description:** Indicates the name of the owner of the **mailbox**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822E

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/ownername

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.47

**Alternate names:** dispidOwnerName

## 2.201 PidLidPendingStateForSiteMailboxDocument

**Canonical name:** PidLidPendingStateForSiteMailboxDocument

**Description:** Specifies the synchronization state of the **Document object** that is in the Document Libraries folder of the **site mailbox**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085E0

**Data type:** PtypInteger32, 0x0003

**Area:** Site Mailbox

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.34

**Alternate names:** dispidPendingStateforTMDocument

## 2.202 PidLidPercentComplete

**Canonical name:** PidLidPercentComplete

**Description:** Indicates whether a time-flagged **Message object** is complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008102

**Data type:** PtypFloating64, 0x0005

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.2.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidPercentComplete

## 2.203 PidLidPostalAddressId

**Canonical name:** PidLidPostalAddressId

**Description:** Specifies which physical address is the mailing address for this **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008022

**Data type:** PtypInteger32, 0x0003

**WebDAV:** urn:schemas:contacts:mailingaddressid

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.9

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidPostalAddressId

## 2.204 PidLidPostRssChannel

**Canonical name:** PidLidPostRssChannel

**Description:** Contains the contents of the title field from the **XML** of the Atom feed or RSS channel.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008904

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.5

**Alternate names:** dispidPostRssChannel

## 2.205 PidLidPostRssChannelLink

**Canonical name:** PidLidPostRssChannelLink

**Description:** Contains the **URL** of the RSS or Atom feed from which the XML file came.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008900

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.1

**Alternate names:** dispidPostRssChannelLink

## 2.206 PidLidPostRssItemGuid

**Canonical name:** PidLidPostRssItemGuid

**Description:** Contains a unique identifier for the RSS object.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008903

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.4

**Alternate names:** dispidPostRssItemGuid

## 2.207 PidLidPostRssItemHash

**Canonical name:** PidLidPostRssItemHash

**Description:** Contains a hash of the feed XML computed by using an implementation-dependent algorithm.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008902

**Data type:** PtypInteger32, 0x0003

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.3

**Alternate names:** dispidPostRssItemHash

## 2.208 PidLidPostRssItemLink

**Canonical name:** PidLidPostRssItemLink

**Description:** Contains the **URL** of the link from an RSS or Atom item.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008901

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.2

**Alternate names:** dispidPostRssItemLink

## 2.209 PidLidPostRssItemXml

**Canonical name:** PidLidPostRssItemXml

**Description:** Contains the item element and all of its sub-elements from an RSS feed, or the entry element and all of its sub-elements from an Atom feed.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008905

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.6

**Alternate names:** dispidPostRssItemXml

## 2.210 PidLidPostRssSubscription

**Canonical name:** PidLidPostRssSubscription

**Description:** Contains the user's preferred name for the RSS or Atom subscription.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008906

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.7

**Alternate names:** dispidPostRssSubscription

## 2.211 PidLidPrivate

**Canonical name:** PidLidPrivate

**Description:** Indicates whether the end user wishes for this **Message object** to be hidden from other users who have access to the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008506

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.15

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidPrivate

## 2.212 PidLidPromptSendUpdate

**Canonical name:** PidLidPromptSendUpdate

**Description:** Indicates that the **Meeting Response object** was out-of-date when it was received.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008045

**Data type:** PtypBoolean, 0x000B

**Area:** Meeting Response

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.8

**Alternate names:** dispidPromptSendUpdate

## 2.213 PidLidRecurrenceDuration

**Canonical name:** PidLidRecurrenceDuration

**Description:** Identifies the length, in minutes, of the appointment or **meeting**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000100D

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/recurduration

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.48

## 2.214 PidLidRecurrencePattern

**Canonical name:** PidLidRecurrencePattern

**Description:** Specifies a description of the **recurrence pattern** of the **Calendar object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008232

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/recurpattern

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.46

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurPattern

## 2.215 PidLidRecurrenceType

**Canonical name:** PidLidRecurrenceType

**Description:** Specifies the recurrence type of the **recurring series**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008231

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/recurtype

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.45

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurType

## 2.216 PidLidRecurring

**Canonical name:** PidLidRecurring

**Description:** Specifies whether the object represents a **recurring series**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008223

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/recurring

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurring

## 2.217 PidLidReferenceEntryId

**Canonical name:** PidLidReferenceEntryId

**Description:** Specifies the value of the **EntryID** of the Contact object unless the Contact object is a copy of an earlier original.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BD

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.1

**Alternate names:** dispidReferenceEID

## 2.218 PidLidReminderDelta

**Canonical name:** PidLidReminderDelta

**Description:** Specifies the interval, in minutes, between the time at which the **reminder** first becomes overdue and the start time of the **Calendar object**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008501

**Data type:** PtypInteger32, 0x0003

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidReminderDelta, <http://schemas.microsoft.com/mapi/reminderdelta>

## 2.219 PidLidReminderFileParameter

**Canonical name:** PidLidReminderFileParameter

**Description:** Specifies the filename of the sound that a client is to play when the **reminder** for that object becomes overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851F

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderfileparam>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.7

**Consuming reference:** [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidReminderFileParam



## 2.220 PidLidReminderOverride

**Canonical name:** PidLidReminderOverride

**Description:** Specifies whether the client is to respect the current values of the **PidLidReminderPlaySound** property (section [2.221](#)) and the **PidLidReminderFileParameter** property (section [2.219](#)), or use the default values for those properties.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851C

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderoverride>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.5

**Consuming reference:** [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidReminderOverride

## 2.221 PidLidReminderPlaySound

**Canonical name:** PidLidReminderPlaySound

**Description:** Specifies whether the client is to play a sound when the **reminder** becomes overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851E

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderplaysound>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.6

**Consuming reference:** [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidReminderPlaySound

## 2.222 PidLidReminderSet

**Canonical name:** PidLidReminderSet

**Description:** Specifies whether a **reminder** is set on the object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008503

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderset>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFCICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidReminderSet

### 2.223 PidLidReminderSignalTime

**Canonical name:** PidLidReminderSignalTime

**Description:** Specifies the point in time when a **reminder** transitions from pending to overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008560

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/remindernexttime>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidReminderNextTime

### 2.224 PidLidReminderTime

**Canonical name:** PidLidReminderTime

**Description:** Specifies the initial **signal time** for objects that are not **Calendar objects**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008502

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/remindertime>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderTime

### 2.225 PidLidReminderTimeDate

**Canonical name:** PidLidReminderTimeDate

**Description:** Indicates the time and date of the **reminder** for the appointment or **meeting**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008505

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/remindertimedate

**Area:** Reminders

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.59

**Alternate names:** dispidReminderTimeDate

## 2.226 PidLidReminderTimeTime

**Canonical name:** PidLidReminderTimeTime

**Description:** Indicates the time of the **reminder** for the appointment or **meeting**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008504

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/remindertimetime

**Area:** Reminders

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.60

**Consuming references:** [\[MS-OXONOTE\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidReminderTimeTime

## 2.227 PidLidReminderType

**Canonical name:** PidLidReminderType

**Description:** This property is not set and, if set, is ignored.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851D

**Data type:** PtypInteger32, 0x0003

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.9

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderType, http://schemas.microsoft.com/mapi/remindertype

## 2.228 PidLidRemoteStatus

**Canonical name:** PidLidRemoteStatus

**Description:** Indicates the remote status of the **calendar** item.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008511

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/remotestatus

**Area:** Run-time configuration

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.62

**Alternate names:** dispidRemoteStatus

## 2.229 PidLidRequiredAttendees

**Canonical name:** PidLidRequiredAttendees

**Description:** Identifies required attendees for the appointment or **meeting**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000006

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/required\_attendees

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.63

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_REQUIRED\_ATTENDEES

## 2.230 PidLidResourceAttendees

**Canonical name:** PidLidResourceAttendees

**Description:** Identifies resource attendees for the appointment or **meeting**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000008

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/resource\_attendees

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.64

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_RESOURCE\_ATTENDEES

## 2.231 PidLidResponseStatus

**Canonical name:** PidLidResponseStatus

**Description:** Specifies the response status of an attendee.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008218

**Data type:** PtypInteger32, 0x0003

**WebDAV:** urn:schemas:calendar:attendeestatus, http://schemas.microsoft.com/mapi/responsestatus

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidResponseStatus

## 2.232 PidLidServerProcessed

**Canonical name:** PidLidServerProcessed

**Description:** Indicates whether the **Meeting Request object** or **Meeting Update object** has been processed.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x000085CC

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.4

**Alternate names:** dispidExchangeProcessed

## 2.233 PidLidServerProcessingActions

**Canonical name:** PidLidServerProcessingActions

**Description:** Indicates what processing **actions** have been taken on this **Meeting Request object** or **Meeting Update object**.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x000085CD

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.5

**Alternate names:** dispidExchangeProcessingAction

## 2.234 PidLidSharingAnonymity

**Canonical name:** PidLidSharingAnonymity

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A19

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingAnonymity

### 2.235 PidLidSharingBindingEntryId

**Canonical name:** PidLidSharingBindingEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2D

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingBindingEid

### 2.236 PidLidSharingBrowseUrl

**Canonical name:** PidLidSharingBrowseUrl

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A51

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingBrowseUrl

### 2.237 PidLidSharingCapabilities

**Canonical name:** PidLidSharingCapabilities

**Description:** Indicates that the **Message object** relates to a **special folder**.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A17

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.1

**Alternate names:** dispidSharingCaps

### 2.238 PidLidSharingConfigurationUrl

**Canonical name:** PidLidSharingConfigurationUrl

**Description:** Contains a zero-length string.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A24

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.3

**Alternate names:** dispidSharingConfigUrl

### 2.239 PidLidSharingDataRangeEnd

**Canonical name:** PidLidSharingDataRangeEnd

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A45

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingDataRangeEnd

### 2.240 PidLidSharingDataRangeStart

**Canonical name:** PidLidSharingDataRangeStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A44

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingDataRangeStart

## 2.241 PidLidSharingDetail

**Canonical name:** PidLidSharingDetail

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingDetail

## 2.242 PidLidSharingExtensionXml

**Canonical name:** PidLidSharingExtensionXml

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A21

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingExtXml

## 2.243 PidLidSharingFilter

**Canonical name:** PidLidSharingFilter

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A13

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingFilter

## 2.244 PidLidSharingFlags

**Canonical name:** PidLidSharingFlags



**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingFlags

## 2.245 PidLidSharingFlavor

**Canonical name:** PidLidSharingFlavor

**Description:** Indicates the type of Sharing **Message object**.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A18

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.5

**Alternate names:** dispidSharingFlavor

## 2.246 PidLidSharingFolderEntryId

**Canonical name:** PidLidSharingFolderEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A15

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingFolderEid

## 2.247 PidLidSharingIndexEntryId

**Canonical name:** PidLidSharingIndexEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2E

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingIndexEid

## 2.248 PidLidSharingInitiatorEntryId

**Canonical name:** PidLidSharingInitiatorEntryId

**Description:** Contains the value of the **PidTagEntryId** property (section [2.683](#)) for the **Address Book object** of the currently logged-on user.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A09

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.7

**Alternate names:** dispidSharingInitiatorEid

## 2.249 PidLidSharingInitiatorName

**Canonical name:** PidLidSharingInitiatorName

**Description:** Contains the value of the **PidTagDisplayName** property (section [2.676](#)) from the **Address Book object** identified by the **PidLidSharingInitiatorEntryId** property (section [2.248](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A07

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.8

**Alternate names:** dispidSharingInitiatorName

## 2.250 PidLidSharingInitiatorSntp

**Canonical name:** PidLidSharingInitiatorSntp

**Description:** Contains the value of the **PidTagSntpAddress** property (section [2.1020](#)) from the **Address Book object** identified by the **PidLidSharingInitiatorEntryId** property (section [2.248](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A08

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.9

**Alternate names:** dispidSharingInitiatorSntp

### 2.251 PidLidSharingInstanceGuid

**Canonical name:** PidLidSharingInstanceGuid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1C

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingInstanceGuid

### 2.252 PidLidSharingLastAutoSyncTime

**Canonical name:** PidLidSharingLastAutoSyncTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A55

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLastAutoSync

### 2.253 PidLidSharingLastSyncTime

**Canonical name:** PidLidSharingLastSyncTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1F

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLastSync

## 2.254 PidLidSharingLocalComment

**Canonical name:** PidLidSharingLocalComment

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalComment

## 2.255 PidLidSharingLocalLastModificationTime

**Canonical name:** PidLidSharingLocalLastModificationTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A23

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalLastMod

## 2.256 PidLidSharingLocalName

**Canonical name:** PidLidSharingLocalName

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0F

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalName

## 2.257 PidLidSharingLocalPath

**Canonical name:** PidLidSharingLocalPath

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0E

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalPath

## 2.258 PidLidSharingLocalStoreUid

**Canonical name:** PidLidSharingLocalStoreUid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A49

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalStoreUid

## 2.259 PidLidSharingLocalType

**Canonical name:** PidLidSharingLocalType

**Description:** Contains the value of the **PidTagContainerClass** property (section [2.642](#)) of the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A14

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.10

**Alternate names:** dispidSharingLocalType

## 2.260 PidLidSharingLocalUid

**Canonical name:** PidLidSharingLocalUid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A10

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalUid

### 2.261 PidLidSharingOriginalMessageEntryId

**Canonical name:** PidLidSharingOriginalMessageEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A29

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingOriginalMessageEid

### 2.262 PidLidSharingParentBindingEntryId

**Canonical name:** PidLidSharingParentBindingEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A5C

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingParentBindingEid

### 2.263 PidLidSharingParticipants

**Canonical name:** PidLidSharingParticipants

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1E

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingParticipants

## 2.264 PidLidSharingPermissions

**Canonical name:** PidLidSharingPermissions

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingPermissions

## 2.265 PidLidSharingProviderExtension

**Canonical name:** PidLidSharingProviderExtension

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0B

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingProviderExtension

## 2.266 PidLidSharingProviderGuid

**Canonical name:** PidLidSharingProviderGuid

**Description:** Contains the value "%xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.46".

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A01

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.12

**Alternate names:** dispidSharingProviderGuid

## 2.267 PidLidSharingProviderName

**Canonical name:** PidLidSharingProviderName

**Description:** Contains a user-displayable name of the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.266](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A02

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.14

**Alternate names:** dispidSharingProviderName

## 2.268 PidLidSharingProviderUrl

**Canonical name:** PidLidSharingProviderUrl

**Description:** Contains a **URL** related to the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.266](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A03

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.16

**Alternate names:** dispidSharingProviderUrl

## 2.269 PidLidSharingRangeEnd

**Canonical name:** PidLidSharingRangeEnd

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A47

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6



**Alternate names:** dispidSharingRangeEnd

## 2.270 PidLidSharingRangeStart

**Canonical name:** PidLidSharingRangeStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A46

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRangeStart

## 2.271 PidLidSharingReciprocation

**Canonical name:** PidLidSharingReciprocation

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingReciprocation

## 2.272 PidLidSharingRemoteByteSize

**Canonical name:** PidLidSharingRemoteByteSize

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Consuming reference:** [MS-OXSHARE]

**Alternate names:** dispidSharingRemoteByteSize

## 2.273 PidLidSharingRemoteComment

**Canonical name:** PidLidSharingRemoteComment

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2F

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteComment

## 2.274 PidLidSharingRemoteCrc

**Canonical name:** PidLidSharingRemoteCrc

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4C

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteCrc

## 2.275 PidLidSharingRemoteLastModificationTime

**Canonical name:** PidLidSharingRemoteLastModificationTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A22

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteLastMod

## 2.276 PidLidSharingRemoteMessageCount

**Canonical name:** PidLidSharingRemoteMessageCount

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4F

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteMsgCount

### 2.277 PidLidSharingRemoteName

**Canonical name:** PidLidSharingRemoteName

**Description:** Contains the value of the **PidTagDisplayName** property (section [2.676](#)) on the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A05

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.1

**Alternate names:** dispidSharingRemoteName

### 2.278 PidLidSharingRemotePass

**Canonical name:** PidLidSharingRemotePass

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemotePass

### 2.279 PidLidSharingRemotePath

**Canonical name:** PidLidSharingRemotePath

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A04

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemotePath

## 2.280 PidLidSharingRemoteStoreUid

**Canonical name:** PidLidSharingRemoteStoreUid

**Description:** Contains a hexadecimal string representation of the value of the **PidTagStoreEntryId** property (section [2.1028](#)) on the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A48

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.3

**Alternate names:** dispidSharingRemoteStoreUid

## 2.281 PidLidSharingRemoteType

**Canonical name:** PidLidSharingRemoteType

**Description:** Contains the same value as the **PidLidSharingLocalType** property (section [2.259](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.5

**Alternate names:** dispidSharingRemoteType

## 2.282 PidLidSharingRemoteUid

**Canonical name:** PidLidSharingRemoteUid

**Description:** Contains the **EntryID** of the folder being shared.

**Property set:** PSTID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A06

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.7

**Alternate names:** dispidSharingRemoteUid

## 2.283 PidLidSharingRemoteUser

**Canonical name:** PidLidSharingRemoteUser

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0C

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteUser

## 2.284 PidLidSharingRemoteVersion

**Canonical name:** PidLidSharingRemoteVersion

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A5B

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteVersion

## 2.285 PidLidSharingResponseTime

**Canonical name:** PidLidSharingResponseTime

**Description:** Contains the time at which the **recipient** of the sharing request sent a sharing response.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A28

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.4.1

**Alternate names:** dispidSharingResponseTime

## 2.286 PidLidSharingResponseType

**Canonical name:** PidLidSharingResponseType

**Description:** Contains the type of response with which the **recipient** of the sharing request responded.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A27

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.4.2

**Alternate names:** dispidSharingResponseType

## 2.287 PidLidSharingRoamLog

**Canonical name:** PidLidSharingRoamLog

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4E

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRoamLog

## 2.288 PidLidSharingStart

**Canonical name:** PidLidSharingStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A25

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingStart

## 2.289 PidLidSharingStatus

**Canonical name:** PidLidSharingStatus

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A00

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingStatus

## 2.290 PidLidSharingStop

**Canonical name:** PidLidSharingStop

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A26

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingStop

## 2.291 PidLidSharingSyncFlags

**Canonical name:** PidLidSharingSyncFlags

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A60

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingSyncFlags

## 2.292 PidLidSharingSyncInterval

**Canonical name:** PidLidSharingSyncInterval

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingSyncInterval

### 2.293 PidLidSharingTimeToLive

**Canonical name:** PidLidSharingTimeToLive

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2C

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingTimeToLive

### 2.294 PidLidSharingTimeToLiveAuto

**Canonical name:** PidLidSharingTimeToLiveAuto

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A56

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingTimeToLiveAuto

### 2.295 PidLidSharingWorkingHoursDays

**Canonical name:** PidLidSharingWorkingHoursDays

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.



**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A42

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursDays

## 2.296 PidLidSharingWorkingHoursEnd

**Canonical name:** PidLidSharingWorkingHoursEnd

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A41

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursEnd

## 2.297 PidLidSharingWorkingHoursStart

**Canonical name:** PidLidSharingWorkingHoursStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A40

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursStart

## 2.298 PidLidSharingWorkingHoursTimeZone

**Canonical name:** PidLidSharingWorkingHoursTimeZone

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A43

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursTZ

## 2.299 PidLidSideEffects

**Canonical name:** PidLidSideEffects

**Description:** Specifies how a **Message object** is handled by the client in relation to certain user interface **actions** by the user, such as deleting a message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008510

**Data type:** PtypInteger32, 0x0003

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.16

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidSideEffects

## 2.300 PidLidSingleBodyICal

**Canonical name:** PidLidSingleBodyICal

**Description:** Indicates that the original MIME message contained a single **MIME** part.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000827B

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-OXCICAL\]](#) section 2.1.3.4.2

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** IsSingleBodyICal, dispidIsSingleBodyICal

## 2.301 PidLidSmartNoAttach

**Canonical name:** PidLidSmartNoAttach

**Description:** Indicates whether the **Message object** has no end-user visible attachments.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008514

**Data type:** PtypBoolean, 0x000B

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.14

**Alternate names:** dispidSmartNoAttach

### 2.302 PidLidSpamOriginalFolder

**Canonical name:** PidLidSpamOriginalFolder

**Description:** Specifies which folder a message was in before it was filtered into the Junk Email folder.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000859C

**Data type:** PtypBinary, 0x0102

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.1.1

**Alternate names:** dispidSpamOriginalFolder

### 2.303 PidLidStartRecurrenceDate

**Canonical name:** PidLidStartRecurrenceDate

**Description:** Identifies the start date of the **recurrence pattern**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000D

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/start\\_recur\\_date](http://schemas.microsoft.com/mapi/start_recur_date)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.66

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_START\_RECUR\_DATE

### 2.304 PidLidStartRecurrenceTime

**Canonical name:** PidLidStartRecurrenceTime

**Description:** Identifies the start time of the **recurrence pattern**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000E

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/start\\_recur\\_time](http://schemas.microsoft.com/mapi/start_recur_time)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.67

**Consuming references:** [\[MS-OXOCAL\]](#), [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_START\_RECUR\_TIME

### 2.305 PidLidTaskAcceptanceState

**Canonical name:** PidLidTaskAcceptanceState

**Description:** Indicates the acceptance state of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000812A

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.30

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidTaskDelegValue

### 2.306 PidLidTaskAccepted

**Canonical name:** PidLidTaskAccepted

**Description:** Indicates whether a task assignee has replied to a **task request** for this **Task object**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008108

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.7

**Consuming reference:** [\[MS-OXOSFLD\]](#)

**Alternate names:** dispidTaskAccepted

### 2.307 PidLidTaskActualEffort

**Canonical name:** PidLidTaskActualEffort

**Description:** Indicates the number of minutes that the user actually spent working on a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008110

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskActualEffort

### 2.308 PidLidTaskAssigner

**Canonical name:** PidLidTaskAssigner

**Description:** Specifies the name of the user that last assigned the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008121

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.24

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskDelegator

### 2.309 PidLidTaskAssigners

**Canonical name:** PidLidTaskAssigners

**Description:** Contains a stack of entries, each of which represents a task assigner.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008117

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.16

**Alternate names:** dispidTaskMyDelegators

### 2.310 PidLidTaskComplete

**Canonical name:** PidLidTaskComplete

**Description:** Indicates that the task is complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811C

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.20

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskComplete

### 2.311 PidLidTaskCustomFlags

**Canonical name:** PidLidTaskCustomFlags

**Description:** The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008139

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.33

**Alternate names:** dispidTaskCustomFlags

### 2.312 PidLidTaskDateCompleted

**Canonical name:** PidLidTaskDateCompleted

**Description:** Specifies the date when the user completed work on the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000810F

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.9

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#)

**Alternate names:** dispidTaskDateCompleted

### 2.313 PidLidTaskDeadOccurrence

**Canonical name:** PidLidTaskDeadOccurrence

**Description:** Indicates whether new occurrences remain to be generated.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008109

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.8

**Alternate names:** dispidTaskDeadOccur

### 2.314 PidLidTaskDueDate

**Canonical name:** PidLidTaskDueDate

**Description:** Specifies the date by which the user expects work on the task to be complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008105

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskDueDate

### 2.315 PidLidTaskEstimatedEffort

**Canonical name:** PidLidTaskEstimatedEffort

**Description:** Indicates the number of minutes that the user expects to work on a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008111

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidTaskEstimatedEffort

### 2.316 PidLidTaskFCreator

**Canonical name:** PidLidTaskFCreator

**Description:** Indicates that the **Task object** was originally created by the **action** of the current user or user agent instead of by the processing of a **task request**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811E

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.21

**Alternate names:** dispidTaskFCreator

### 2.317 PidLidTaskFFixOffline

**Canonical name:** PidLidTaskFFixOffline

**Description:** Indicates the accuracy of the **PidLidTaskOwner** property (section [2.328](#)).

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000812C

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.31

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskFFixOffline

### 2.318 PidLidTaskFRecurring

**Canonical name:** PidLidTaskFRecurring

**Description:** Indicates whether the task includes a **recurrence pattern**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008126

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.28

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskFRecur

### 2.319 PidLidTaskGlobalId

**Canonical name:** PidLidTaskGlobalId

**Description:** Contains a unique **GUID** for this task, which is used to locate an existing task upon receipt of a task response or task update.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008519

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.32

**Alternate names:** dispidTaskGlobalObjId



## 2.320 PidLidTaskHistory

**Canonical name:** PidLidTaskHistory

**Description:** Indicates the type of change that was last made to the **Task object**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811A

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.18

**Alternate names:** dispidTaskHistory

## 2.321 PidLidTaskLastDelegate

**Canonical name:** PidLidTaskLastDelegate

**Description:** Contains the name of the user who most recently assigned the task, or the user to whom it was most recently assigned.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008125

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.27

**Alternate names:** dispidTaskLastDelegate

## 2.322 PidLidTaskLastUpdate

**Canonical name:** PidLidTaskLastUpdate

**Description:** Contains the date and time of the most recent change made to the **Task object**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008115

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.10

**Alternate names:** dispidTaskLastUpdate

## 2.323 PidLidTaskLastUser

**Canonical name:** PidLidTaskLastUser

**Description:** Contains the name of the most recent user to have been the owner of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008122

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.25

**Alternate names:** dispidTaskLastUser

### 2.324 PidLidTaskMode

**Canonical name:** PidLidTaskMode

**Description:** Specifies the assignment status of the embedded **Task object**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008518

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.3.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** dispidTaskMode

### 2.325 PidLidTaskMultipleRecipients

**Canonical name:** PidLidTaskMultipleRecipients

**Description:** Provides optimization hints about the **recipients** of a **Task object**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008120

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.23

**Alternate names:** dispidTaskMultRecips

### 2.326 PidLidTaskNoCompute

**Canonical name:** PidLidTaskNoCompute

**Description:** Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008124

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.35

**Consuming reference:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskNoCompute

### 2.327 PidLidTaskOrdinal

**Canonical name:** PidLidTaskOrdinal

**Description:** Provides an aid to custom sorting of **Task objects**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008123

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.26

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskOrdinal

### 2.328 PidLidTaskOwner

**Canonical name:** PidLidTaskOwner

**Description:** Contains the name of the owner of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811F

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.22

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskOwner

### 2.329 PidLidTaskOwnership

**Canonical name:** PidLidTaskOwnership

**Description:** Indicates the role of the current user relative to the **Task object**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008129

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.29

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskOwnership

### 2.330 PidLidTaskRecurrence

**Canonical name:** PidLidTaskRecurrence

**Description:** Contains a **RecurrencePattern** structure that provides information about **recurring tasks**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008116

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.15

**Consuming references:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskRecur

### 2.331 PidLidTaskResetReminder

**Canonical name:** PidLidTaskResetReminder

**Description:** Indicates whether future **instances** of **recurring tasks** need **reminders**, even though the value of the **PidLidReminderSet** property (section [2.222](#)) is 0x00.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008107

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.6

**Consuming references:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskResetReminder

### 2.332 PidLidTaskRole

**Canonical name:** PidLidTaskRole

**Description:** Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008127

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.34

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskRole

### 2.333 PidLidTaskStartDate

**Canonical name:** PidLidTaskStartDate

**Description:** Specifies the date on which the user expects work on the task to begin.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008104

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.4

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskStartDate

### 2.334 PidLidTaskState

**Canonical name:** PidLidTaskState

**Description:** Indicates the current assignment state of the **Task object**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008113

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.14

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskState

### 2.335 PidLidTaskStatus

**Canonical name:** PidLidTaskStatus

**Description:** Specifies the status of a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008101

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidTaskStatus

### 2.336 PidLidTaskStatusOnComplete

**Canonical name:** PidLidTaskStatusOnComplete

**Description:** Indicates whether the task assignee has been requested to send an email message update upon completion of the assigned task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008119

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.17

**Alternate names:** dispidTaskSOC

### 2.337 PidLidTaskUpdates

**Canonical name:** PidLidTaskUpdates

**Description:** Indicates whether the task assignee has been requested to send a task update when the assigned **Task object** changes.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811B

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.19

**Alternate names:** dispidTaskUpdates

### 2.338 PidLidTaskVersion

**Canonical name:** PidLidTaskVersion

**Description:** Indicates which copy is the latest update of a **Task object**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008112

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.13

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskVersion

### 2.339 PidLidTeamTask

**Canonical name:** PidLidTeamTask

**Description:** This property is set by the client but is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008103

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.36

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTeamTask

### 2.340 PidLidTimeZone

**Canonical name:** PidLidTimeZone

**Description:** Specifies information about the time zone of a recurring **meeting**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000C

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/time\\_zone](http://schemas.microsoft.com/mapi/time_zone)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.6

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_TIME\_ZONE

### 2.341 PidLidTimeZoneDescription

**Canonical name:** PidLidTimeZoneDescription

**Description:** Specifies a human-readable description of the time zone that is represented by the data in the **PidLidTimeZoneStruct** property (section [2.342](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008234

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/timezonedesc

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.40

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidTimeZoneDesc

### 2.342 PidLidTimeZoneStruct

**Canonical name:** PidLidTimeZoneStruct

**Description:** Specifies time zone information for a recurring **meeting**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008233

**Data type:** PtypBinary, 0x0102

**WebDAV:** http://schemas.microsoft.com/mapi/timezonestruct

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.39

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidTimeZoneStruct

### 2.343 PidLidToAttendeesString

**Canonical name:** PidLidToAttendeesString

**Description:** Contains a list of all of the sendable attendees who are also required attendees.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823B

**Data type:** PtypString, 0x001F

**Area:** Meetings



**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.17

**Alternate names:** dispidToAttendeesString

### 2.344 PidLidToDoOrdinalDate

**Canonical name:** PidLidToDoOrdinalDate

**Description:** Contains the current time, in **UTC**, which is used to determine the sort order of objects in a consolidated to-do list.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A0

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.13

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidToDoOrdinalDate

### 2.345 PidLidToDoSubOrdinal

**Canonical name:** PidLidToDoSubOrdinal

**Description:** Contains the numerals 0 through 9 that are used to break a tie when the **PidLidToDoOrdinalDate** property (section [2.344](#)) is used to perform a sort of objects.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A1

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.14

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidToDoSubOrdinal

### 2.346 PidLidToDoTitle

**Canonical name:** PidLidToDoTitle

**Description:** Contains user-specifiable text to identify this **Message object** in a consolidated to-do list.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A4

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidToDoTitle

### 2.347 PidLidUseTnef

**Canonical name:** PidLidUseTnef

**Description:** Specifies whether **Transport Neutral Encapsulation Format (TNEF)** is to be included on a message when the message is converted from TNEF to **MIME** or **SMTP** format.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008582

**Data type:** PtypBoolean, 0x000B

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.66

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidUseTNEF

### 2.348 PidLidValidFlagStringProof

**Canonical name:** PidLidValidFlagStringProof

**Description:** Contains the value of the **PidTagMessageDeliveryTime** property (section [2.789](#)) when modifying the **PidLidFlagRequest** property (section [2.136](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BF

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidValidFlagStringProof

### 2.349 PidLidVerbResponse

**Canonical name:** PidLidVerbResponse

**Description:** Specifies the voting option that a respondent has selected.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008524

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.75

**Alternate names:** dispidVerbResponse

### 2.350 PidLidVerbStream

**Canonical name:** PidLidVerbStream

**Description:** Specifies what voting responses the user can make in response to the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008520

**Data type:** PtypBinary, 0x0102

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.74

**Alternate names:** dispidVerbStream

### 2.351 PidLidWeddingAnniversaryLocal

**Canonical name:** PidLidWeddingAnniversaryLocal

**Description:** Specifies the wedding anniversary of the **contact**, at midnight in the client's local time zone, and is saved without any time zone conversions.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DF

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.5

**Alternate names:** dispidApptAnniversaryLocal

### 2.352 PidLidWeekInterval

**Canonical name:** PidLidWeekInterval

**Description:** Identifies the number of weeks that occur between each **meeting**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000012

**Data type:** PtypInteger16, 0x0002

**WebDAV:** [http://schemas.microsoft.com/mapi/week\\_interval](http://schemas.microsoft.com/mapi/week_interval)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.71

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_WEEK\_INTERVAL

### 2.353 PidLidWhere

**Canonical name:** PidLidWhere

**Description:** Contains the value of the **PidLidLocation** property (section [2.159](#)) from the associated **Meeting object**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000002

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/where

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.3

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_WHERE

### 2.354 PidLidWorkAddress

**Canonical name:** PidLidWorkAddress

**Description:** Specifies the complete address of the work address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801B

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:workaddress

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** dispidWorkAddress

### 2.355 PidLidWorkAddressCity

**Canonical name:** PidLidWorkAddressCity

**Description:** Specifies the city or locality portion of the work address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008046

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:l

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

**Alternate names:** dispidWorkAddressCity

### 2.356 PidLidWorkAddressCountry

**Canonical name:** PidLidWorkAddressCountry

**Description:** Specifies the country or region portion of the work address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008049

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:co

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

**Alternate names:** dispidWorkAddressCountry

### 2.357 PidLidWorkAddressCountryCode

**Canonical name:** PidLidWorkAddressCountryCode

**Description:** Specifies the country code portion of the work address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DB

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidWorkAddressCountryCode

### 2.358 PidLidWorkAddressPostalCode

**Canonical name:** PidLidWorkAddressPostalCode

**Description:** Specifies the postal code (ZIP code) portion of the work address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008048

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:postalcode

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

**Alternate names:** dispidWorkAddressPostalCode

### 2.359 PidLidWorkAddressPostOfficeBox

**Canonical name:** PidLidWorkAddressPostOfficeBox

**Description:** Specifies the post office box portion of the work address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804A

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:postofficebox

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

**Alternate names:** dispidWorkAddressPostOfficeBox

### 2.360 PidLidWorkAddressState

**Canonical name:** PidLidWorkAddressState

**Description:** Specifies the state or province portion of the work address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008047

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:st

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

**Alternate names:** dispidWorkAddressState

### 2.361 PidLidWorkAddressStreet

**Canonical name:** PidLidWorkAddressStreet

**Description:** Specifies the street portion of the work address of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008045

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:street

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.1

**Alternate names:** dispidWorkAddressStreet

### 2.362 PidLidYearInterval

**Canonical name:** PidLidYearInterval

**Description:** Indicates the yearly interval of the appointment or **meeting**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000014

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/year\_interval

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.73

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_YEAR\_INTERVAL

### 2.363 PidLidYomiCompanyName

**Canonical name:** PidLidYomiCompanyName

**Description:** Specifies the phonetic pronunciation of the company name of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802E

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/yomiorganization

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.8

**Alternate names:** dispidYomiCompanyName

### 2.364 PidLidYomiFirstName

**Canonical name:** PidLidYomiFirstName

**Description:** Specifies the phonetic pronunciation of the given name of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802C

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/yomifirstname

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.9

**Alternate names:** dispidYomiFirstName

### 2.365 PidLidYomiLastName

**Canonical name:** PidLidYomiLastName

**Description:** Specifies the phonetic pronunciation of the surname of the **contact**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802D

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/yomilastname

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.10

**Alternate names:** dispidYomiLastName

### 2.366 PidNameAcceptLanguage

**Canonical name:** PidNameAcceptLanguage

**Description:** Contains the value of the **MIME** Accept-Language header.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Accept-Language

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.42

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** AcceptLanguage

### 2.367 PidNameApplicationName

**Canonical name:** PidNameApplicationName

**Description:** Specifies the application used to open the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** AppName

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.9

**Alternate names:** urn:schemas-microsoft-com:office:office#NameOfApplication

### 2.368 PidNameAttachmentMacContentType

**Canonical name:** PidNameAttachmentMacContentType



**Description:** Contains the Content-Type of the Mac attachment.

**Property set:** PSETID\_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

**Property name:** AttachmentMacContentType

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.29

**Consuming reference:** [\[MS-OXCMAIL\]](#)

### 2.369 PidNameAttachmentMacInfo

**Canonical name:** PidNameAttachmentMacInfo

**Description:** Contains the headers and resource fork data associated with the Mac attachment.

**Property set:** PSETID\_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

**Property name:** AttachmentMacInfo

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.29

**Consuming reference:** [\[MS-OXCMAIL\]](#)

### 2.370 PidNameAttachmentOriginalPermissionType

**Canonical name:** PidNameAttachmentOriginalPermissionType

**Description:** Contains the original permission type data associated with a web reference attachment.

**Property set:** PSETID\_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

**Property name:** AttachmentOriginalPermissionType

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.27

### 2.371 PidNameAttachmentPermissionType

**Canonical name:** PidNameAttachmentPermissionType

**Description:** Contains the permission type data associated with a web reference attachment.

**Property set:** PSETID\_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

**Property name:** AttachmentPermissionType

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.28

### 2.372 PidNameAttachmentProviderType

**Canonical name:** PidNameAttachmentProviderType

**Description:** Contains the provider type data associated with a web reference attachment.

**Property set:** PSETID\_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

**Property name:** AttachmentProviderType

**Data type:** PtypeString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

### 2.373 PidNameAudioNotes

**Canonical name:** PidNameAudioNotes

**Description:** Contains textual annotations to a voice message after it has been delivered to the user's **mailbox**.

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** UMAudioNotes

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.15

**Alternate names:** UMAudioNotes

### 2.374 PidNameAuthor

**Canonical name:** PidNameAuthor

**Description:** Specifies the author of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Author

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.3

**Alternate names:** urn:schemas-microsoft-com:office:office#Author

### 2.375 PidNameAutomaticSpeechRecognitionData

**Canonical name:** PidNameAutomaticSpeechRecognitionData

**Description:** Contains an unprotected voice message.

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** AsrData

**Data type:** PtypBinary, 0x0102

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.13

### 2.376 PidNameBirthdayContactAttributionDisplayName

**Canonical name:** PidNameBirthdayContactAttributionDisplayName

**Description:** Indicates the name of the **contact** associated with the birthday event.

**Property set:** PSETID\_Address{00062004-0000-0000-C000-000000000046}

**Property name:** BirthdayContactAttributionDisplayName

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.52

### 2.377 PidNameBirthdayContactEntryId

**Canonical name:** PidNameBirthdayContactEntryId

**Description:** Indicate the **EntryID** of the **contact** associated with the birthday event.

**Property set:** PSETID\_Address{00062004-0000-0000-C000-000000000046}

**Property name:** BirthdayContactEntryId

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.53

### 2.378 PidNameBirthdayContactPersonGuid

**Canonical name:** PidNameBirthdayContactPersonGuid

**Description:** Indicates the person ID's **GUID** of the **contact** associated with the birthday event.

**Property set:** PSETID\_Address{00062004-0000-0000-C000-000000000046}

**Property name:** BirthdayContactPersonGuid

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.54

### 2.379 PidNameByteCount

**Canonical name:** PidNameByteCount

**Description:** Specifies the size, in bytes, of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** ByteCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.22

**Alternate names:** urn:schemas-microsoft-com:office:office#Bytes

### 2.380 PidNameCalendarAttendeeRole

**Canonical name:** PidNameCalendarAttendeeRole

**Description:** Specifies the role of the attendee.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:attendeerole

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.7

**Alternate names:** urn:schemas:calendar:attendeerole

### 2.381 PidNameCalendarBusystatus

**Canonical name:** PidNameCalendarBusystatus

**Description:** Specifies whether the attendee is busy at the time of an appointment on their **calendar**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:busystatus

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.8

**Alternate names:** urn:schemas:calendar:busystatus

### 2.382 PidNameCalendarContact

**Canonical name:** PidNameCalendarContact

**Description:** Identifies the name of a **contact** who is an attendee of a **meeting**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:contact

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.9

**Alternate names:** urn:schemas:calendar:contact

### 2.383 PidNameCalendarContactUrl

**Canonical name:** PidNameCalendarContactUrl

**Description:** Identifies the **URL** where you can access **contact** information in **HTML** format.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:contacturl

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.10

**Alternate names:** urn:schemas:calendar:contacturl

### 2.384 PidNameCalendarCreated

**Canonical name:** PidNameCalendarCreated

**Description:** Identifies the date and time, in **UTC**, when the **organizer** created the appointment or **meeting**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:created

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.11

**Alternate names:** urn:schemas:calendar:created

### 2.385 PidNameCalendarDescriptionUrl

**Canonical name:** PidNameCalendarDescriptionUrl

**Description:** Specifies the **URL** of a resource that contains a description of an appointment or **meeting**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:descriptionurl

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.12

**Alternate names:** urn:schemas:calendar:descriptionurl

### 2.386 PidNameCalendarDuration

**Canonical name:** PidNameCalendarDuration

**Description:** Identifies the duration, in seconds, of an appointment or **meeting**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:duration

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.13

**Alternate names:** urn:schemas:calendar:duration

### 2.387 PidNameCalendarExceptionDate

**Canonical name:** PidNameCalendarExceptionDate

**Description:** Identifies a list of dates that are exceptions to a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:exdate

**Data type:** PtypMultipleTime, 0x1040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.14

**Alternate names:** urn:schemas:calendar:exdate

### 2.388 PidNameCalendarExceptionRule

**Canonical name:** PidNameCalendarExceptionRule

**Description:** Specifies an exception **rule** for a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:exrule

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.15

**Alternate names:** urn:schemas:calendar:exrule

### 2.389 PidNameCalendarGeoLatitude

**Canonical name:** PidNameCalendarGeoLatitude

**Description:** Specifies the geographical latitude of the location of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:geolatitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.16

**Alternate names:** urn:schemas:calendar:geolatitude

### 2.390 PidNameCalendarGeoLongitude

**Canonical name:** PidNameCalendarGeoLongitude

**Description:** Specifies the geographical longitude of the location of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:geolongitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.17

**Alternate names:** urn:schemas:calendar:geolongitude

### 2.391 PidNameCalendarInstanceType

**Canonical name:** PidNameCalendarInstanceType

**Description:** Specifies the type of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:instancetype

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.18

**Alternate names:** urn:schemas:calendar:instancetype

### 2.392 PidNameCalendarIsOrganizer

**Canonical name:** PidNameCalendarIsOrganizer

**Description:** Specifies whether an attendee is the **organizer** of an appointment or **meeting**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:isorganizer

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.19

**Alternate names:** urn:schemas:calendar:isorganizer

### 2.393 PidNameCalendarLastModified

**Canonical name:** PidNameCalendarLastModified

**Description:** Specifies the date and time, in **UTC**, when an appointment was last modified.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:lastmodified

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.20

**Alternate names:** urn:schemas:calendar:lastmodified

### 2.394 PidNameCalendarLocationUrl

**Canonical name:** PidNameCalendarLocationUrl

**Description:** Specifies a **URL** with location information in **HTML** format.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:locationurl

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.21

**Alternate names:** urn:schemas:calendar:locationurl

### 2.395 PidNameCalendarMeetingStatus

**Canonical name:** PidNameCalendarMeetingStatus

**Description:** Specifies the status of an appointment or **meeting**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:meetingstatus

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.22



**Alternate names:** urn:schemas:calendar:meetingstatus

### 2.396 PidNameCalendarMethod

**Canonical name:** PidNameCalendarMethod

**Description:** Specifies the **iCalendar** method that is associated with an **Appointment object**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:method

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.23

**Alternate names:** urn:schemas:calendar:method

### 2.397 PidNameCalendarProductId

**Canonical name:** PidNameCalendarProductId

**Description:** Identifies the product that created the iCalendar-formatted **stream**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:prodid

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.24

**Alternate names:** urn:schemas:calendar:prodid

### 2.398 PidNameCalendarRecurrenceIdRange

**Canonical name:** PidNameCalendarRecurrenceIdRange

**Description:** Specifies which instances of a recurring appointment are being referred to.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:recurrenceidrange

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.25

**Alternate names:** urn:schemas:calendar:recurrenceidrange

### 2.399 PidNameCalendarReminderOffset

**Canonical name:** PidNameCalendarReminderOffset

**Description:** Identifies the number of seconds before an appointment starts that a **reminder** is to be displayed.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:reminderoffset

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.26

**Alternate names:** urn:schemas:calendar:reminderoffset

## 2.400 PidNameCalendarResources

**Canonical name:** PidNameCalendarResources

**Description:** Identifies a list of resources, such as rooms and video equipment, that are available for an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:resources

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.27

**Alternate names:** urn:schemas:calendar:resources

## 2.401 PidNameCalendarRsvp

**Canonical name:** PidNameCalendarRsvp

**Description:** Specifies whether the **organizer** of an appointment or **meeting** requested a response.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rsvp

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.28

**Alternate names:** urn:schemas:calendar:rsvp

## 2.402 PidNameCalendarSequence

**Canonical name:** PidNameCalendarSequence

**Description:** Specifies the sequence number of a version of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:sequence

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.29

**Alternate names:** urn:schemas:calendar:sequence

### 2.403 PidNameCalendarTimeZone

**Canonical name:** PidNameCalendarTimeZone

**Description:** Specifies the time zone of an appointment or **meeting**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:timezone

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.30

**Alternate names:** urn:schemas:calendar:timezone

### 2.404 PidNameCalendarTimeZoneId

**Canonical name:** PidNameCalendarTimeZoneId

**Description:** Specifies the time zone identifier of an appointment or **meeting**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:timezoneid

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.31

**Alternate names:** urn:schemas:calendar:timezoneid

### 2.405 PidNameCalendarTransparent

**Canonical name:** PidNameCalendarTransparent

**Description:** Specifies whether an appointment or **meeting** is visible to busy time searches.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:transparent

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.32

**Alternate names:** urn:schemas:calendar:transparent

## 2.406 PidNameCalendarUid

**Canonical name:** PidNameCalendarUid

**Description:** Specifies the unique identifier of an appointment or **meeting**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:uid

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.33

**Alternate names:** urn:schemas:calendar:uid

## 2.407 PidNameCalendarVersion

**Canonical name:** PidNameCalendarVersion

**Description:** Identifies the version of the iCalendar specification, as specified in [\[MS-OXCICAL\]](#) section 2.1.3.1.1.3, that is required to correctly interpret an iCalendar object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:version

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.34

**Alternate names:** urn:schemas:calendar:version

## 2.408 PidNameCategory

**Canonical name:** PidNameCategory

**Description:** Specifies the category of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Category

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.18

**Alternate names:** urn:schemas-microsoft-com:office:office#Category

## 2.409 PidNameCharacterCount

**Canonical name:** PidNameCharacterCount

**Description:** Specifies the character count of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** CharCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.16

**Alternate names:** urn:schemas-microsoft-com:office:office#Characters

## 2.410 PidNameComments

**Canonical name:** PidNameComments

**Description:** Specifies the comments of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Comments

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.5

**Alternate names:** urn:schemas-microsoft-com:office:office#Comments

## 2.411 PidNameCompany

**Canonical name:** PidNameCompany

**Description:** Specifies the company for which the file was created.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Company

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.21

**Alternate names:** urn:schemas-microsoft-com:office:office#Company

## 2.412 PidNameContentBase

**Canonical name:** PidNameContentBase

**Description:** Specifies the value of the **MIME** Content-Base header, which defines the base **URI** for resolving relative URLs contained within the **message body**.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Base

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.41

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** BodyContentBase

### 2.413 PidNameContentClass

**Canonical name:** PidNameContentClass

**Description:** Contains a string that identifies the type of content of a **Message object**.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Class

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.48

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** DAV:contentclass, urn:schemas:mailheader:content-class

### 2.414 PidNameContentType

**Canonical name:** PidNameContentType

**Description:** Specifies the type of the **body part** content.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Type

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.50

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:content-type

### 2.415 PidNameCreateDateTimeReadOnly

**Canonical name:** PidNameCreateDateTimeReadOnly

**Description:** Specifies the time, in **UTC**, that the file was first created.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** CreateDtmRo

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.12

**Alternate names:** urn:schemas-microsoft-com:office:office#Created

## 2.416 PidNameCrossReference

**Canonical name:** PidNameCrossReference

**Description:** Contains the name of the host (with domains omitted) and a white-space-separated list of colon-separated pairs of newsgroup names and message numbers.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Xref

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.3

**Alternate names:** urn:schemas:mailheader:xref

## 2.417 PidNameDavId

**Canonical name:** PidNameDavId

**Description:** Specifies a unique ID for the **calendar** item.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:id

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.2

**Alternate names:** DAV:id

## 2.418 PidNameDavIsCollection

**Canonical name:** PidNameDavIsCollection

**Description:** Indicates whether a **Calendar object** is a collection.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:iscollection

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.3

**Alternate names:** DAV:iscollection

## 2.419 PidNameDavIsStructuredDocument

**Canonical name:** PidNameDavIsStructuredDocument

**Description:** Indicates whether a **Calendar object** is a structured document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:isstructureddocument

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.4

**Alternate names:** DAV:isstructureddocument

## 2.420 PidNameDavParentName

**Canonical name:** PidNameDavParentName

**Description:** Specifies the name of the **Folder object** that contains the **Calendar object**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:parentname

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.5

**Alternate names:** DAV:parentname

## 2.421 PidNameDavUid

**Canonical name:** PidNameDavUid

**Description:** Specifies the unique identifier for an item.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:uid

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.6

**Alternate names:** DAV:uid

## 2.422 PidNameDocumentParts

**Canonical name:** PidNameDocumentParts

**Description:** Specifies the title of each part of the document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}



**Property name:** DocParts

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.29

**Alternate names:** urn:schemas-microsoft-com:office:office#PartTitles

### 2.423 PidNameEditTime

**Canonical name:** PidNameEditTime

**Description:** Specifies the time that the file was last edited.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** EditTime

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.10

**Alternate names:** urn:schemas-microsoft-com:office:office#TotalTime

### 2.424 PidNameExchangeIntendedBusyStatus

**Canonical name:** PidNameExchangeIntendedBusyStatus

**Description:** Specifies the intended **free/busy status** of a **meeting** in a **Meeting request**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/intendedbusystatus

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.1

**Alternate names:** http://schemas.microsoft.com/exchange/intendedbusystatus

### 2.425 PidNameExchangeJunkEmailMoveStamp

**Canonical name:** PidNameExchangeJunkEmailMoveStamp

**Description:** Indicates that the message is not to be processed by a **spam filter**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/junkemailmovestamp

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.1.2

**Consuming reference:** [\[MS-OXORSS\]](#)

**Alternate names:** <http://schemas.microsoft.com/exchange/junkemailmovestamp>

## 2.426 PidNameExchangeModifyExceptionStructure

**Canonical name:** PidNameExchangeModifyExceptionStructure

**Description:** Specifies a structure that modifies an exception to the recurrence.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** <http://schemas.microsoft.com/exchange/modifyexceptionstruct>

**Data type:** PtypBinary, 0x0102

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.2

**Alternate names:** <http://schemas.microsoft.com/exchange/modifyexceptionstruct>

## 2.427 PidNameExchangeNoModifyExceptions

**Canonical name:** PidNameExchangeNoModifyExceptions

**Description:** Indicates whether exceptions to a recurring appointment can be modified.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** <http://schemas.microsoft.com/exchange/nomodifyexceptions>

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.3

**Alternate names:** <http://schemas.microsoft.com/exchange/nomodifyexceptions>

## 2.428 PidNameExchangePatternEnd

**Canonical name:** PidNameExchangePatternEnd

**Description:** Identifies the maximum time when an instance of a recurring appointment ends.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** <http://schemas.microsoft.com/exchange/patternend>

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.4

**Alternate names:** <http://schemas.microsoft.com/exchange/patternend>

## 2.429 PidNameExchangePatternStart

**Canonical name:** PidNameExchangePatternStart

**Description:** Identifies the absolute minimum time when an instance of a recurring appointment starts.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/patternstart

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.5

**Alternate names:** http://schemas.microsoft.com/exchange/patternstart

## 2.430 PidNameExchangeReminderInterval

**Canonical name:** PidNameExchangeReminderInterval

**Description:** Identifies the time, in seconds, between **reminders**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/reminderinterval

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.6

**Consuming reference:** [MS-XWDCAL]

**Alternate names:** http://schemas.microsoft.com/exchange/reminderinterval

## 2.431 PidNameExchDatabaseSchema

**Canonical name:** PidNameExchDatabaseSchema

**Description:** Specifies an array of URLs that identifies other folders within the same **message store** that contain schema definition items.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:baseschema

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.5.1

**Alternate names:** urn:schemas-microsoft-com:exch-data:baseschema

## 2.432 PidNameExchDataExpectedContentClass

**Canonical name:** PidNameExchDataExpectedContentClass

**Description:** Specifies an array of names that indicates the expected content **classes** of items within a folder.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:expected-content-class

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.5.2

**Alternate names:** urn:schemas-microsoft-com:exch-data:expected-content-class

### 2.433 PidNameExchDataSchemaCollectionReference

**Canonical name:** PidNameExchDataSchemaCollectionReference

**Description:** Specifies an array of names that indicates the expected content classes of items within a folder.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:schema-collection-ref

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.5.3

**Alternate names:** urn:schemas-microsoft-com:exch-data:schema-collection-ref

### 2.434 PidNameExtractedAddresses

**Canonical name:** PidNameExtractedAddresses

**Description:** Contains an **XML document** with a single **AddressSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedAddresses

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.1

**Alternate names:** dispidXmlExtractedAddresses

### 2.435 PidNameExtractedContacts

**Canonical name:** PidNameExtractedContacts

**Description:** Contains an **XML document** with a single **ContactSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedContacts

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.2

**Alternate names:** dispidXmlExtractedContacts

### 2.436 PidNameExtractedEmails

**Canonical name:** PidNameExtractedEmails

**Description:** Contains an **XML document** with a single **EmailSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedEmails

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.3

**Alternate names:** dispidXmlExtractedEmails

### 2.437 PidNameExtractedMeetings

**Canonical name:** PidNameExtractedMeetings

**Description:** Contains an **XML document** with a single **MeetingSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedMeetings

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.4

**Alternate names:** dispidXmlExtractedMeetings

### 2.438 PidNameExtractedPhones

**Canonical name:** PidNameExtractedPhones

**Description:** Contains an **XML document** with a single **PhoneSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedPhones

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.5

**Alternate names:** dispidXmlExtractedPhones

### 2.439 PidNameExtractedTasks

**Canonical name:** PidNameExtractedTasks

**Description:** Contains an **XML document** with a single **TaskSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedTasks

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.6

**Alternate names:** dispidXmlExtractedTasks

### 2.440 PidNameExtractedUrls

**Canonical name:** PidNameExtractedUrls

**Description:** Contains an **XML document** with a single **UrlSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedUrls

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.7

**Alternate names:** dispidXmlExtractedUrls

### 2.441 PidNameFrom

**Canonical name:** PidNameFrom

**Description:** Specifies the **SMTP** email **alias** of the **organizer** of an appointment or **meeting**.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** From

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.35

**Alternate names:** urn:schemas:calendar:organizer

### 2.442 PidNameHeadingPairs

**Canonical name:** PidNameHeadingPairs

**Description:** Specifies which group of headings are indented in the document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** HeadingPairs

**Data type:** PtypBinary, 0x0102

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.30

**Alternate names:** urn:schemas-microsoft-com:office:office#HeadingPairs

#### 2.443 PidNameHiddenCount

**Canonical name:** PidNameHiddenCount

**Description:** Specifies the hidden value of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** HiddenCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.27

**Alternate names:** urn:schemas-microsoft-com:office:office#HiddenSlides

#### 2.444 PidNameHttpmailCalendar

**Canonical name:** PidNameHttpmailCalendar

**Description:** Specifies the **URL** for the **Calendar folder** for a particular user.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:calendar

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.3.1

**Alternate names:** urn:schemas:httpmail:calendar

#### 2.445 PidNameHttpmailHtmlDescription

**Canonical name:** PidNameHttpmailHtmlDescription

**Description:** Specifies the **HTML** content of the message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:htmldescription

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.3.2

**Alternate names:** urn:schemas:httpmail:htmldescription

#### 2.446 PidNameHttpmailSendMessage

**Canonical name:** PidNameHttpmailSendMessage

**Description:** Specifies the email submission **URI** to which outgoing email is submitted.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:sendmsg

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.3.3

**Alternate names:** urn:schemas:httpmail:sendmsg

#### 2.447 PidNameICalendarRecurrenceDate

**Canonical name:** PidNameICalendarRecurrenceDate

**Description:** Identifies an array of instances of a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rdate

**Data type:** PtypMultipleTime, 0x1040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.36

**Alternate names:** urn:schemas:calendar:rdate

#### 2.448 PidNameICalendarRecurrenceRule

**Canonical name:** PidNameICalendarRecurrenceRule

**Description:** Specifies the **rule** for the pattern that defines a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rrule

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.37

**Alternate names:** urn:schemas:calendar:rrule

#### 2.449 PidNameInternetSubject

**Canonical name:** PidNameInternetSubject



**Description:** Specifies the subject of the message.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Subject

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.4.1

**Alternate names:** urn:schemas:mailheader:subject

## 2.450 PidNameIsBirthdayContactWritable

**Canonical name:** PidNameIsBirthdayContactWritable

**Description:** Indicates whether the **contact** associated with the birthday event is writable.

**Property set:** PSETID\_Address{00062004-0000-0000-C000-000000000046}

**Property name:** IsBirthdayContactWritable

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.55

## 2.451 PidNameKeywords

**Canonical name:** PidNameKeywords

**Description:** Contains keywords or categories for the **Message object**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Keywords

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.17

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXONOTE\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Keywords,  
<http://schemas.microsoft.com/exchange/keywords-utf8>

## 2.452 PidNameLastAuthor

**Canonical name:** PidNameLastAuthor

**Description:** Specifies the most recent author of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastAuthor

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.7

**Alternate names:** urn:schemas-microsoft-com:office:office#LastAuthor

### 2.453 PidNameLastPrinted

**Canonical name:** PidNameLastPrinted

**Description:** Specifies the time, in **UTC**, that the file was last printed.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastPrinted

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.11

**Alternate names:** urn:schemas-microsoft-com:office:office#LastPrinted

### 2.454 PidNameLastSaveDateTime

**Canonical name:** PidNameLastSaveDateTime

**Description:** Specifies the time, in **UTC**, that the file was last saved.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastSaveDtm

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.13

**Alternate names:** urn:schemas-microsoft-com:office:office#LastSaved

### 2.455 PidNameLineCount

**Canonical name:** PidNameLineCount

**Description:** Specifies the number of lines in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LineCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.23

**Alternate names:** urn:schemas-microsoft-com:office:office#Lines

## 2.456 PidNameLinksDirty

**Canonical name:** PidNameLinksDirty

**Description:** Indicates whether the links in the document are up-to-date.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LinksDirty

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.31

**Alternate names:** urn:schemas-microsoft-com:office:office#LinksUpToDate

## 2.457 PidNameLocationUrl

**Canonical name:** PidNameLocationUrl

**Description:**

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:locationurl

**Data type:** PtypString, 0x001F

**Area:** Calendar

**Defining reference:**

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** urn:schemas:calendar:locationurl, LocationUrl

## 2.458 PidNameManager

**Canonical name:** PidNameManager

**Description:** Specifies the manager of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Manager

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.20

**Alternate names:** urn:schemas-microsoft-com:office:office#Manager

## 2.459 PidNameMeetingDoNotForward

**Canonical name:** PidNameMeetingDoNotForward

**Description:** Specifies whether to allow the meeting to be forwarded.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DoNotForward

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51

## 2.460 PidNameMSIPLabels

**Canonical name:** PidNameMSIPLabels

**Description:** Contains the string that specifies the **CLP** label information.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** msip\_labels

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.59

## 2.461 PidNameMultimediaClipCount

**Canonical name:** PidNameMultimediaClipCount

**Description:** Specifies the number of multimedia clips in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** MMClipCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.28

**Alternate names:** urn:schemas-microsoft-com:office:office#MultimediaClips

## 2.462 PidNameNoteCount

**Canonical name:** PidNameNoteCount

**Description:** Specifies the number of notes in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** NoteCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.26

**Alternate names:** urn:schemas-microsoft-com:office:office#Notes

### 2.463 PidNameOMSAccountGuid

**Canonical name:** PidNameOMSAccountGuid

**Description:** Contains the **GUID** of the **SMS** account used to deliver the message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSAccountGuid

**Data type:** PtypString, 0x001F

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.1

### 2.464 PidNameOMSMobileModel

**Canonical name:** PidNameOMSMobileModel

**Description:** Indicates the model of the mobile device used to send the **SMS** or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSMobileModel

**Data type:** PtypString, 0x001F

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.6

### 2.465 PidNameOMSScheduleTime

**Canonical name:** PidNameOMSScheduleTime

**Description:** Contains the time, in **UTC**, at which the client requested that the service provider send the **SMS** or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSScheduleTime

**Data type:** PtypTime, 0x0040

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.2

### 2.466 PidNameOMSServiceType

**Canonical name:** PidNameOMSServiceType

**Description:** Contains the type of service used to send an **SMS** or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSServiceType

**Data type:** PtypInteger32, 0x0003

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.3

### 2.467 PidNameOMSSourceType

**Canonical name:** PidNameOMSSourceType

**Description:** Contains the source of an **SMS** or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSSourceType

**Data type:** PtypInteger32, 0x0003

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.4

### 2.468 PidNamePageCount

**Canonical name:** PidNamePageCount

**Description:** Specifies the page count of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** PageCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.14

**Alternate names:** urn:schemas-microsoft-com:office:office#Pages

### 2.469 PidNameParagraphCount

**Canonical name:** PidNameParagraphCount

**Description:** Specifies the number of paragraphs in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** ParCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.24

**Alternate names:** urn:schemas-microsoft-com:office:office#Paragraphs

### 2.470 PidNamePhishingStamp

**Canonical name:** PidNamePhishingStamp

**Description:** Indicates whether a message is likely to be **phishing**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/outlook/phishingstamp

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXPHISH\]](#) section 2.2.1.1

## 2.471 PidNamePresentationFormat

**Canonical name:** PidNamePresentationFormat

**Description:** Specifies the presentation format of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** PresFormat

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.19

**Alternate names:** urn:schemas-microsoft-com:office:office#PresentationFormat

## 2.472 PidNameQuarantineOriginalSender

**Canonical name:** PidNameQuarantineOriginalSender

**Description:** Specifies the original sender of a message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** quarantine-original-sender

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.4

## 2.473 PidNameRevisionNumber

**Canonical name:** PidNameRevisionNumber

**Description:** Specifies the revision number of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** RevNumber

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.8

**Alternate names:** urn:schemas-microsoft-com:office:office#Revision

## 2.474 PidNameRightsManagementLicense

**Canonical name:** PidNameRightsManagementLicense

**Description:** Specifies the value used to cache the **Use License** for the **rights-managed email message**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DRMLicense

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXORMMS\]](#) section 2.2.1.1

## 2.475 PidNameScale

**Canonical name:** PidNameScale

**Description:** Indicates whether the image is to be scaled or cropped.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Scale

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.32

**Alternate names:** urn:schemas-microsoft-com:office:office#ScaleCrop

## 2.476 PidNameSecurity

**Canonical name:** PidNameSecurity

**Description:** Specifies the security level of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Security

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.17

**Alternate names:** urn:schemas-microsoft-com:office:office#Security

## 2.477 PidNameSlideCount

**Canonical name:** PidNameSlideCount

**Description:** Specifies the number of slides in the file attached to the Document object.



**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** SlideCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.25

**Alternate names:** urn:schemas-microsoft-com:office:office#Slides

## 2.478 PidNameSubject

**Canonical name:** PidNameSubject

**Description:** Specifies the subject of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Subject

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.2

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Subject

## 2.479 PidNameTemplate

**Canonical name:** PidNameTemplate

**Description:** Specifies the template of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Template

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.6

**Alternate names:** urn:schemas-microsoft-com:office:office#Template

## 2.480 PidNameThumbnail

**Canonical name:** PidNameThumbnail

**Description:** Specifies the data representing the thumbnail image of the document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Thumbnail

**Data type:** PtypBinary, 0x0102

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.33

**Alternate names:** urn:schemas-microsoft-com:office:office#ThumbNail

## 2.481 PidNameTitle

**Canonical name:** PidNameTitle

**Description:** Specifies the title of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Title

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.1

**Alternate names:** urn:schemas-microsoft-com:office:office#Title

## 2.482 PidNameWordCount

**Canonical name:** PidNameWordCount

**Description:** Specifies the word count of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** WordCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.15

**Alternate names:** urn:schemas-microsoft-com:office:office#Words

## 2.483 PidNameXCallId

**Canonical name:** PidNameXCallId

**Description:** Contains a unique identifier associated with the phone call.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-CallID

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.12

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.484 PidNameXFaxNumberOfPages

**Canonical name:** PidNameXFaxNumberOfPages

**Description:** Specifies how many discrete pages are contained within an attachment representing a facsimile message.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-FaxNumberOfPages

**Data type:** PtypInteger16, 0x0002

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.8

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.485 PidNameXRequireProtectedPlayOnPhone

**Canonical name:** PidNameXRequireProtectedPlayOnPhone

**Description:** Indicates that the client only renders the message on a phone.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-RequireProtectedPlayOnPhone

**Data type:** PtypBoolean, 0x000B

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.14

## 2.486 PidNameXSenderTelephoneNumber

**Canonical name:** PidNameXSenderTelephoneNumber

**Description:** Contains the telephone number of the caller associated with a voice mail message.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-CallingTelephoneNumber

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.2

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.487 PidNameXSharingBrowseUrl

**Canonical name:** PidNameXSharingBrowseUrl

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Browse-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

## 2.488 PidNameXSharingCapabilities

**Canonical name:** PidNameXSharingCapabilities

**Description:** Contains a string representation of the value of the **PidLidSharingCapabilities** property (section [2.237](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Capabilities

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.2

## 2.489 PidNameXSharingConfigUrl

**Canonical name:** PidNameXSharingConfigUrl

**Description:** Contains the same value as the **PidLidSharingConfigurationUrl** property (section [2.238](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Config-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.4

## 2.490 PidNameXSharingExendedCaps

**Canonical name:** PidNameXSharingExendedCaps

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Exended-Caps

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

## 2.491 PidNameXSharingFlavor

**Canonical name:** PidNameXSharingFlavor

**Description:** Contains a hexadecimal string representation of the value of the **PidLidSharingFlavor** property (section [2.245](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Flavor

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.6

## 2.492 PidNameXSharingInstanceGuid

**Canonical name:** PidNameXSharingInstanceGuid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Instance-Guid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

## 2.493 PidNameXSharingLocalType

**Canonical name:** PidNameXSharingLocalType

**Description:** Contains the same value as the **PidLidSharingLocalType** property (section [2.259](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Local-Type

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.11

## 2.494 PidNameXSharingProviderGuid

**Canonical name:** PidNameXSharingProviderGuid

**Description:** Contains the hexadecimal string representation of the value of the **PidLidSharingProviderGuid** property (section [2.266](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Guid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.13

#### 2.495 PidNameXSharingProviderName

**Canonical name:** PidNameXSharingProviderName

**Description:** Contains the same value as the **PidLidSharingProviderName** property (section [2.267](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Name

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.15

#### 2.496 PidNameXSharingProviderUrl

**Canonical name:** PidNameXSharingProviderUrl

**Description:** Contains the same value as the **PidLidSharingProviderUrl** property (section [2.268](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.17

#### 2.497 PidNameXSharingRemoteName

**Canonical name:** PidNameXSharingRemoteName

**Description:** Contains the same value as the **PidLidSharingRemoteName** property (section [2.277](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Name

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.2

#### 2.498 PidNameXSharingRemotePath

**Canonical name:** PidNameXSharingRemotePath

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Path

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

## 2.499 PidNameXSharingRemoteStoreUid

**Canonical name:** PidNameXSharingRemoteStoreUid

**Description:** Contains the same value as the **PidLidSharingRemoteStoreUid** property (section [2.282](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Store-Uid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.4

## 2.500 PidNameXSharingRemoteType

**Canonical name:** PidNameXSharingRemoteType

**Description:** Contains the same value as the **PidLidSharingRemoteType** property (section [2.281](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Type

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.6

## 2.501 PidNameXSharingRemoteUid

**Canonical name:** PidNameXSharingRemoteUid

**Description:** Contains the same value as the **PidLidSharingRemoteUid** property (section [2.282](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Uid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.8

## 2.502 PidNameXVoiceMessageAttachmentOrder

**Canonical name:** PidNameXVoiceMessageAttachmentOrder

**Description:** Contains the list of names for the audio file attachments that are to be played as part of a message, in reverse order.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-AttachmentOrder

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.10

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.503 PidNameXVoiceMessageDuration

**Canonical name:** PidNameXVoiceMessageDuration

**Description:** Specifies the length of the attached audio message, in seconds.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-VoiceMessageDuration

**Data type:** PtypInteger16, 0x0002

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.4

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.504 PidNameXVoiceMessageSenderName

**Canonical name:** PidNameXVoiceMessageSenderName

**Description:** Contains the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-VoiceMessageSenderName

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.6

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.505 PidTagAccess

**Canonical name:** PidTagAccess

**Description:** Indicates the operations available to the client for the object.



**Property ID:** 0x0FF4

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** PR\_ACCESS, ptagAccess

## 2.506 PidTagAccessControlListData

**Canonical name:** PidTagAccessControlListData

**Description:** Contains a **permissions** list for a folder.

**Property ID:** 0x3FE0

**Data type:** PtypBinary, 0x0102

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.3

**Consuming references:** [\[MS-OXCFOLD\]](#)

**Alternate names:** PR\_ACL\_DATA, ptagACLData

## 2.507 PidTagAccessLevel

**Canonical name:** PidTagAccessLevel

**Description:** Indicates the client's access level to the object.

**Property ID:** 0x0FF7

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_ACCESS\_LEVEL, ptagAccessLevel

## 2.508 PidTagAccount

**Canonical name:** PidTagAccount

**Description:** Contains the **alias** of an **Address Book object**, which is an alternative name by which the object can be identified.

**Property ID:** 0x3A00

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ACCOUNT, PR\_ACCOUNT\_A, PR\_ACCOUNT\_W, urn:schemas:contacts:account

## 2.509 PidTagAdditionalRenEntryIds

**Canonical name:** PidTagAdditionalRenEntryIds

**Description:** Contains the indexed entry IDs for several **special folders** related to conflicts, sync issues, local failures, server failures, junk email and **spam**.

**Property ID:** 0x36D8

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Outlook Application

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.4

**Consuming references:** [\[MS-OXCSPAM\]](#), [\[MS-OXPHISH\]](#)

**Alternate names:** PR\_ADDITIONAL\_REN\_ENTRYIDS, ptagAdditionalRenEntryIds

## 2.510 PidTagAdditionalRenEntryIdsEx

**Canonical name:** PidTagAdditionalRenEntryIdsEx

**Description:** Contains an array of blocks that specify the **EntryIDs** of several special folders.

**Property ID:** 0x36D9

**Data type:** PtypBinary, 0x0102

**Area:** Outlook Application

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.5

**Alternate names:** PR\_ADDITIONAL\_REN\_ENTRYIDS\_EX, ptagAdditionalRenEntryIdsEx

## 2.511 PidTagAddressBookAuthorizedSenders

**Canonical name:** PidTagAddressBookAuthorizedSenders

**Description:** Indicates whether delivery restrictions exist for a **recipient**.

**Property ID:** 0x8CD8

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.42

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_AUTH\_ORIG

## 2.512 PidTagAddressBookContainerId

**Canonical name:** PidTagAddressBookContainerId

**Description:** Contains the ID of a container on an **NSPI** server.

**Property ID:** 0xFFFFD

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.3

**Consuming references:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_CONTAINERID

## 2.513 PidTagAddressBookDeliveryContentLength

**Canonical name:** PidTagAddressBookDeliveryContentLength

**Description:** Specifies the maximum size, in bytes, of a message that a **recipient** can receive.

**Property ID:** 0x806A

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.27

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DELIV\_CONT\_LENGTH

## 2.514 PidTagAddressBookDisplayNamePrintable

**Canonical name:** PidTagAddressBookDisplayNamePrintable

**Description:** Contains the printable string version of the **display name**.

**Property ID:** 0x39FF

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.7

**Consuming reference:** [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE, PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE\_A, PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE\_W, PR\_7BIT\_DISPLAY\_NAME, PR\_7BIT\_DISPLAY\_NAME\_A, PR\_7BIT\_DISPLAY\_NAME\_W, ptagSimpleDisplayName

## 2.515 PidTagAddressBookDisplayTypeExtended

**Canonical name:** PidTagAddressBookDisplayTypeExtended

**Description:** Contains a value that indicates how to display an **Address Book object** in a table or as a **recipient** on a message.

**Property ID:** 0x8C93

**Data type:** **PtypInteger32**, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.35

**Alternate names:** PR\_EMS\_AB\_DISPLAY\_TYPE\_EX

## 2.516 PidTagAddressBookDistributionListExternalMemberCount

**Canonical name:** PidTagAddressBookDistributionListExternalMemberCount

**Description:** Contains the number of external **recipients** in the **distribution list**.

**Property ID:** 0x8CE3

**Data type:** **PtypInteger32**, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.30

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_EXTERNAL\_MEMBER\_COUNT

## 2.517 PidTagAddressBookDistributionListMemberCount

**Canonical name:** PidTagAddressBookDistributionListMemberCount

**Description:** Contains the total number of **recipients** in the **distribution list**.

**Property ID:** 0x8CE2

**Data type:** **PtypInteger32**, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.29

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_TOTAL\_MEMBER\_COUNT

## 2.518 PidTagAddressBookDistributionListMemberSubmitAccepted

**Canonical name:** PidTagAddressBookDistributionListMemberSubmitAccepted

**Description:** Indicates that delivery restrictions exist for a **recipient**.

**Property ID:** 0x8073

**Data type:** **PtypObject**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.44

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_SUBMIT\_PERMS\_BL\_O

### **2.519 PidTagAddressBookDistributionListMemberSubmitRejected**

**Canonical name:** PidTagAddressBookDistributionListMemberSubmitRejected

**Description:** Indicates that delivery restrictions exist for a **recipient**.

**Property ID:** 0x8CDA

**Data type:** **PtypObject**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.45

**Consuming references:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_SUBMIT\_PERMS

### **2.520 PidTagAddressBookDistributionListRejectMessagesFromDLMembers**

**Canonical name:** PidTagAddressBookDistributionListRejectMessagesFromDLMembers

**Description:** Indicates that delivery restrictions exist for a **recipient**.

**Property ID:** 0x8CDB

**Data type:** **PtypObject**, 0x000D

**Area:** Address book

**Defining reference:** [\[MS-OXOAB\]](#) section 2.9.2.2

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_REJECT\_PERMS

### **2.521 PidTagAddressBookEntryId**

**Canonical name:** PidTagAddressBookEntryId

**Description:** Contains the name-service **EntryID** of a directory object that refers to a **public folder**.

**Property ID:** 0x663B

**Data type:** **PtypBinary**, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.4

**Alternate names:** PR\_ADDRESS\_BOOK\_ENTRYID, ptagAddressBookEntryId

### **2.522 PidTagAddressBookExtensionAttribute1**

**Canonical name:** PidTagAddressBookExtensionAttribute1

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x802D

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1\_W

### 2.523 PidTagAddressBookExtensionAttribute10

**Canonical name:** PidTagAddressBookExtensionAttribute10

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8036

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_10,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_10\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_10\_W

### 2.524 PidTagAddressBookExtensionAttribute11

**Canonical name:** PidTagAddressBookExtensionAttribute11

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8C57

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_11,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_11\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_11\_W

### 2.525 PidTagAddressBookExtensionAttribute12

**Canonical name:** PidTagAddressBookExtensionAttribute12

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8C58

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_12,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_12\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_12\_W

### **2.526 PidTagAddressBookExtensionAttribute13**

**Canonical name:** PidTagAddressBookExtensionAttribute13

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8C59

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_13,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_13\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_13\_W

### **2.527 PidTagAddressBookExtensionAttribute14**

**Canonical name:** PidTagAddressBookExtensionAttribute14

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8C60

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_14,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_14\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_14\_W

### **2.528 PidTagAddressBookExtensionAttribute15**

**Canonical name:** PidTagAddressBookExtensionAttribute15

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8C61

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15\_W

## 2.529 PidTagAddressBookExtensionAttribute2

**Canonical name:** PidTagAddressBookExtensionAttribute2

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x802E

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_2,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_2\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_2\_W

## 2.530 PidTagAddressBookExtensionAttribute3

**Canonical name:** PidTagAddressBookExtensionAttribute3

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x802F

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_3,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_3\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_3\_W

## 2.531 PidTagAddressBookExtensionAttribute4

**Canonical name:** PidTagAddressBookExtensionAttribute4

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8030

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_4,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_4\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_4\_W

## 2.532 PidTagAddressBookExtensionAttribute5

**Canonical name:** PidTagAddressBookExtensionAttribute5

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.



**Property ID:** 0x8031

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_5,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_5\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_5\_W

### 2.533 PidTagAddressBookExtensionAttribute6

**Canonical name:** PidTagAddressBookExtensionAttribute6

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8032

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_6,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_6\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_6\_W

### 2.534 PidTagAddressBookExtensionAttribute7

**Canonical name:** PidTagAddressBookExtensionAttribute7

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8033

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_7,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_7\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_7\_W

### 2.535 PidTagAddressBookExtensionAttribute8

**Canonical name:** PidTagAddressBookExtensionAttribute8

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8034

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_8,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_8\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_8\_W

### 2.536 PidTagAddressBookExtensionAttribute9

**Canonical name:** PidTagAddressBookExtensionAttribute9

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x8035

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_9,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_9\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_9\_W

### 2.537 PidTagAddressBookFolderPathname

**Canonical name:** PidTagAddressBookFolderPathname

**Description:** This property is deprecated and is to be ignored.

**Property ID:** 0x8004

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.4

**Alternate names:** PR\_EMS\_AB\_FOLDER\_PATHNAME, PR\_EMS\_AB\_FOLDER\_PATHNAME\_A,  
PR\_EMS\_AB\_FOLDER\_PATHNAME\_W

### 2.538 PidTagAddressBookHierarchicalChildDepartments

**Canonical name:** PidTagAddressBookHierarchicalChildDepartments

**Description:** Contains the child departments in a hierarchy of departments.

**Property ID:** 0x8C9A

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.8.1

**Alternate names:** PR\_EMS\_AB\_HAB\_CHILD\_DEPARTMENTS

### 2.539 PidTagAddressBookHierarchicalDepartmentMembers

**Canonical name:** PidTagAddressBookHierarchicalDepartmentMembers

**Description:** Contains all of the **mail users** that belong to this department.

**Property ID:** 0x8C97

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.8.3

**Alternate names:** PR\_EMS\_AB\_HAB\_DEPARTMENT\_MEMBERS

## 2.540 PidTagAddressBookHierarchicalIsHierarchicalGroup

**Canonical name:** PidTagAddressBookHierarchicalIsHierarchicalGroup

**Description:** Indicates whether the **distribution list** represents a **departmental group**.

**Property ID:** 0x8CDD

**Data type:** **PtypBoolean**, 0x000B

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.5

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_IS\_HIERARCHICAL\_GROUP, PR\_EMS\_AB\_IS\_ORGANIZATIONAL

## 2.541 PidTagAddressBookHierarchicalParentDepartment

**Canonical name:** PidTagAddressBookHierarchicalParentDepartment

**Description:** Contains all of the departments to which this department is a child.

**Property ID:** 0x8C99

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.8.2

**Alternate names:** PR\_EMS\_AB\_HAB\_PARENT\_DEPARTMENT

## 2.542 PidTagAddressBookHierarchicalRootDepartment

**Canonical name:** PidTagAddressBookHierarchicalRootDepartment

**Description:** Contains the **distinguished name (DN)** of either the root **Department object** or the root **departmental group** in the department hierarchy for the organization.

**Property ID:** 0x8C98

**Data type:** **PtypString8**, 0x001E

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.7.2

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_ROOT\_DEPARTMENT

### 2.543 PidTagAddressBookHierarchicalShowInDepartments

**Canonical name:** PidTagAddressBookHierarchicalShowInDepartments

**Description:** Lists all Department objects of which the **mail user** is a member.

**Property ID:** 0x8C94

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.6

**Alternate names:** PR\_EMS\_AB\_HAB\_SHOW\_IN\_DEPARTMENTS

### 2.544 PidTagAddressBookHomeMessageDatabase

**Canonical name:** PidTagAddressBookHomeMessageDatabase

**Description:** Contains the **DN** expressed in the **X500 DN** format. This property is returned from a **name service provider interface (NSPI)** server as a **PtypEmbeddedTable**. Otherwise, the data type is **PtypString8**.

**Property ID:** 0x8006

**Data type:** **PtypString8**, 0x001E**PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.37

**Consuming references:** [\[MS-OXABREF\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_HOME\_MDB, PR\_EMS\_AB\_HOME\_MDB\_A, PR\_EMS\_AB\_HOME\_MDB\_W

### 2.545 PidTagAddressBookIsMaster

**Canonical name:** PidTagAddressBookIsMaster

**Description:** Contains a Boolean value of TRUE if it is possible to create **Address Book objects** in that container, and FALSE otherwise.

**Property ID:** 0xFFFFB

**Data type:** **PtypBoolean**, 0x000B

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.4

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_IS\_MASTER

## 2.546 PidTagAddressBookIsMemberOfDistributionList

**Canonical name:** PidTagAddressBookIsMemberOfDistributionList

**Description:** Lists all of the **distribution lists** for which the object is a member. This property is returned from an **NSPI** server as a **PtypEmbeddedTable**. Otherwise, the data type is **PtypString8**.

**Property ID:** 0x8008

**Data type:** **PtypString8**, 0x001E; **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.3

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL, PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL\_A, PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL\_W

## 2.547 PidTagAddressBookManageDistributionList

**Canonical name:** PidTagAddressBookManageDistributionList

**Description:** Contains information for use in **display templates** for **distribution lists**.

**Property ID:** 0x6704

**Data type:** **PtypObject**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.10.2

**Consuming reference:** [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_EMS\_AB\_MANAGE\_DL

## 2.548 PidTagAddressBookManager

**Canonical name:** PidTagAddressBookManager

**Description:** Contains one row that references the **mail user's** manager.

**Property ID:** 0x8005

**Data type:** **PtypObject**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.1

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_MANAGER, PR\_EMS\_AB\_MANAGER\_A, PR\_EMS\_AB\_MANAGER\_W

## 2.549 PidTagAddressBookManagerDistinguishedName

**Canonical name:** PidTagAddressBookManagerDistinguishedName

**Description:** Contains the **DN** of the **mail user's** manager.

**Property ID:** 0x8005

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.9

**Alternate names:** PR\_EMS\_AB\_MANAGER\_T

## 2.550 PidTagAddressBookMember

**Canonical name:** PidTagAddressBookMember

**Description:** Contains the members of the **distribution list**.

**Property ID:** 0x8009

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.1

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_MEMBER, PR\_EMS\_AB\_MEMBER\_A, PR\_EMS\_AB\_MEMBER\_W

## 2.551 PidTagAddressBookMessageId

**Canonical name:** PidTagAddressBookMessageId

**Description:** Contains the Short-term Message ID (MID) ([\[MS-OXCDATA\]](#) section 2.2.1.2) of the first message in the local site's **offline address book public folder**.

**Property ID:** 0x674F

**Data type:** PtypInteger64, 0x0014

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.2.2

**Alternate names:** ptagAddrbookMID

## 2.552 PidTagAddressBookModerationEnabled

**Canonical name:** PidTagAddressBookModerationEnabled

**Description:** Indicates whether moderation is enabled for the **mail user** or **distribution list**.

**Property ID:** 0x8CB5

**Data type:** PtypBoolean, 0x000B

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.28

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_ENABLE\_MODERATION

## 2.553 PidTagAddressBookNetworkAddress

**Canonical name:** PidTagAddressBookNetworkAddress

**Description:** Contains a list of names by which a server is known to the various transports in use by the network.

**Property ID:** 0x8170

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.38

**Alternate names:** PR\_EMS\_AB\_NETWORK\_ADDRESS, PR\_EMS\_AB\_NETWORK\_ADDRESS\_A, PR\_EMS\_AB\_NETWORK\_ADDRESS\_W

## 2.554 PidTagAddressBookObjectDistinguishedName

**Canonical name:** PidTagAddressBookObjectDistinguishedName

**Description:** Contains the **DN** of the **Address Book object**.

**Property ID:** 0x803C

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.15

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_OBJ\_DIST\_NAME, PR\_EMS\_AB\_OBJ\_DIST\_NAME\_A, PR\_EMS\_AB\_OBJ\_DIST\_NAME\_W

## 2.555 PidTagAddressBookObjectGuid

**Canonical name:** PidTagAddressBookObjectGuid

**Description:** Contains a **GUID** that identifies an **Address Book object**.

**Property ID:** 0x8C6D

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.25

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_OBJECT\_GUID

## 2.556 PidTagAddressBookOrganizationalUnitRootDistinguishedName

**Canonical name:** PidTagAddressBookOrganizationalUnitRootDistinguishedName

**Description:** Contains the **DN** of the Organization object of the **mail user's** organization.

**Property ID:** 0x8CA8

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.39

**Alternate names:** PR\_EMS\_AB\_ORG\_UNIT\_ROOT\_DN, msExchOURoot

### 2.557 PidTagAddressBookOwner

**Canonical name:** PidTagAddressBookOwner

**Description:** Contains one row that references the **distribution list's** owner.

**Property ID:** 0x800C

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.2

**Alternate names:** PR\_EMS\_AB\_OWNER\_O

### 2.558 PidTagAddressBookOwnerBackLink

**Canonical name:** PidTagAddressBookOwnerBackLink

**Description:** Contains a list of the **distribution lists** owned by a **mail user**.

**Property ID:** 0x8024

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.4

**Alternate names:** PR\_EMS\_AB\_OWNER\_BL\_O

### 2.559 PidTagAddressBookParentEntryId

**Canonical name:** PidTagAddressBookParentEntryId

**Description:** Contains the **EntryID** of the parent container in a hierarchy of **address book containers**.

**Property ID:** 0xFFFC

**Data type:** **PtypBinary**, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.5

**Consuming reference:** [\[MS-OXNSPI\]](#)



**Alternate names:** PR\_EMS\_AB\_PARENT\_ENTRYID

## 2.560 PidTagAddressBookPhoneticCompanyName

**Canonical name:** PidTagAddressBookPhoneticCompanyName

**Description:** Contains the phonetic representation of the **PidTagCompanyName** property (section [2.639](#)).

**Property ID:** 0x8C91

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.12

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME, PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME\_W

## 2.561 PidTagAddressBookPhoneticDepartmentName

**Canonical name:** PidTagAddressBookPhoneticDepartmentName

**Description:** Contains the phonetic representation of the **PidTagDepartmentName** property (section [2.672](#)).

**Property ID:** 0x8C90

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.13

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME, PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME\_W

## 2.562 PidTagAddressBookPhoneticDisplayName

**Canonical name:** PidTagAddressBookPhoneticDisplayName

**Description:** Contains the phonetic representation of the **PidTagDisplayName** property (section [2.676](#)).

**Property ID:** 0x8C92

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.9

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME, PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME\_W

### 2.563 PidTagAddressBookPhoneticGivenName

**Canonical name:** PidTagAddressBookPhoneticGivenName

**Description:** Contains the phonetic representation of the **PidTagGivenName** property (section [2.714](#)).

**Property ID:** 0x8C8E

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.10

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME, PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME\_W

### 2.564 PidTagAddressBookPhoneticSurname

**Canonical name:** PidTagAddressBookPhoneticSurname

**Description:** Contains the phonetic representation of the **PidTagSurname** property (section [2.1036](#)).

**Property ID:** 0x8C8F

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.11

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_SURNAME, PR\_EMS\_AB\_PHONETIC\_SURNAME\_A, PR\_EMS\_AB\_PHONETIC\_SURNAME\_W

### 2.565 PidTagAddressBookProxyAddresses

**Canonical name:** PidTagAddressBookProxyAddresses

**Description:** Contains alternate email addresses for the **Address Book object**.

**Property ID:** 0x800F

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.23

**Consuming references:** [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_PROXY\_ADDRESSES, PR\_EMS\_AB\_PROXY\_ADDRESSES\_A, PR\_EMS\_AB\_PROXY\_ADDRESSES\_W

## 2.566 PidTagAddressBookPublicDelegates

**Canonical name:** PidTagAddressBookPublicDelegates

**Description:** Contains a list of **mail users** who are allowed to send email on behalf of the **mailbox** owner.

**Property ID:** 0x8015

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.5

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_PUBLIC\_DELEGATES, PR\_EMS\_AB\_PUBLIC\_DELEGATES\_A, PR\_EMS\_AB\_PUBLIC\_DELEGATES\_W

## 2.567 PidTagAddressBookReports

**Canonical name:** PidTagAddressBookReports

**Description:** Lists all of the **mail user**'s direct reports.

**Property ID:** 0x800E

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.2

**Alternate names:** PR\_EMS\_AB\_REPORTS, PR\_EMS\_AB\_REPORTS\_A, PR\_EMS\_AB\_REPORTS\_W

## 2.568 PidTagAddressBookRoomCapacity

**Canonical name:** PidTagAddressBookRoomCapacity

**Description:** Contains the maximum occupancy of the room.

**Property ID:** 0x0807

**Data type:** **PtypInteger32**, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.9.1

**Alternate names:** PR\_EMS\_AB\_ROOM\_CAPACITY

## 2.569 PidTagAddressBookRoomContainers

**Canonical name:** PidTagAddressBookRoomContainers

**Description:** Contains a list of **DNs** that represent the **address book containers** that hold **Resource objects**, such as conference rooms and equipment.

**Property ID:** 0x8C96

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.7.1

**Alternate names:** PR\_EMS\_AB\_ROOM\_CONTAINERS, PR\_EMS\_AB\_ROOM\_CONTAINERS\_A, PR\_EMS\_AB\_ROOM\_CONTAINERS\_W

## 2.570 PidTagAddressBookRoomDescription

**Canonical name:** PidTagAddressBookRoomDescription

**Description:** Contains a description of the **Resource object**.

**Property ID:** 0x0809

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.9.2

**Alternate names:** PR\_EMS\_AB\_ROOM\_DESCRIPTION, PR\_EMS\_AB\_ROOM\_DESCRIPTION\_A, PR\_EMS\_AB\_ROOM\_DESCRIPTION\_W

## 2.571 PidTagAddressBookSenderHintTranslations

**Canonical name:** PidTagAddressBookSenderHintTranslations

**Description:** Contains the **locale** ID and translations of the default **mail tip**.

**Property ID:** 0x8CAC

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.26

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_SENDER\_HINT\_TRANSLATIONS\_W

## 2.572 PidTagAddressBookSeniorityIndex

**Canonical name:** PidTagAddressBookSeniorityIndex

**Description:** Contains a signed integer that specifies the seniority order of **Address Book objects** that represent members of a department and are referenced by a Department object or **departmental group**, with larger values specifying members that are more senior.

**Property ID:** 0x8CA0

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.24

**Consuming reference:** [\[MS-OXOAB\]](#) **Alternate names:** PR\_EMS\_AB\_HAB\_SENIORITY\_INDEX, PR\_EMS\_AB\_SENIORITY\_INDEX

### 2.573 PidTagAddressBookTargetAddress

**Canonical name:** PidTagAddressBookTargetAddress

**Description:** Contains the foreign system email address of an **Address Book object**.

**Property ID:** 0x8011

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.22

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_TARGET\_ADDRESS, PR\_EMS\_AB\_TARGET\_ADDRESS\_A, PR\_EMS\_AB\_TARGET\_ADDRESS\_W

### 2.574 PidTagAddressBookUnauthorizedSenders

**Canonical name:** PidTagAddressBookUnauthorizedSenders

**Description:** Indicates whether delivery restrictions exist for a **recipient**.

**Property ID:** 0x8CD9

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.43

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_UNAUTH\_ORIG

### 2.575 PidTagAddressBookX509Certificate

**Canonical name:** PidTagAddressBookX509Certificate

**Description:** Contains the ASN\_1 DER encoded X.509 certificates for the **mail user**.

**Property ID:** 0x8C6A

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.35

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_X509\_CERT

## 2.576 PidTagAddressType

**Canonical name:** PidTagAddressType

**Description:** Contains the email **address type** of a **Message object**.

**Property ID:** 0x3002

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.13

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXPSVAL\]](#)

**Alternate names:** PR\_ADDRTYPE, PR\_ADDRTYPE\_A, ptagAddrType, PR\_ADDRTYPE\_W

## 2.577 PidTagAlternateRecipientAllowed

**Canonical name:** PidTagAlternateRecipientAllowed

**Description:** Specifies whether the sender permits the message to be auto-forwarded.

**Property ID:** 0x0002

**Data type:** PtypBoolean, 0x000B

**Area:** Address Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.36

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ALTERNATE\_RECIPIENT\_ALLOWED, ptagAlternateRecipientAllowed

## 2.578 PidTagAnr

**Canonical name:** PidTagAnr

**Description:** Contains a filter value used in **ambiguous name resolution**.

**Property ID:** 0x360C

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.10.1

**Alternate names:** PR\_ANR, PR\_ANR\_A, PR\_ANR\_W

## 2.579 PidTagArchiveDate

**Canonical name:** PidTagArchiveDate

**Description:** Specifies the date, in **UTC**, after which a **Message object** is archived by the server.

**Property ID:** 0x301F

**Data type:** PtypTime, 0x0040

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.8

**Alternate names:** PR\_ARCHIVE\_DATE, ptagArchiveDate

## 2.580 PidTagArchivePeriod

**Canonical name:** PidTagArchivePeriod

**Description:** Specifies the number of days that a **Message object** can remain unarchived.

**Property ID:** 0x301E

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.7

**Alternate names:** PR\_ARCHIVE\_PERIOD, ptagArchivePeriod

## 2.581 PidTagArchiveTag

**Canonical name:** PidTagArchiveTag

**Description:** Specifies the **GUID** of an **archive tag**.

**Property ID:** 0x3018

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.1

**Alternate names:** PR\_ARCHIVE\_TAG, ptagArchiveTag

## 2.582 PidTagAssistant

**Canonical name:** PidTagAssistant

**Description:** Contains the name of the **mail user's** administrative assistant.

**Property ID:** 0x3A30

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.8

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ASSISTANT, PR\_ASSISTANT\_A, PR\_ASSISTANT\_W,  
urn:schemas:contacts:secretarycn

## 2.583 PidTagAssistantTelephoneNumber

**Canonical name:** PidTagAssistantTelephoneNumber

**Description:** Contains the telephone number of the **mail user's** administrative assistant.

**Property ID:** 0x3A2E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.31

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ASSISTANT\_TELEPHONE\_NUMBER, PR\_ASSISTANT\_TELEPHONE\_NUMBER\_A, PR\_ASSISTANT\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:secretaryphone

## 2.584 PidTagAssociated

**Canonical name:** PidTagAssociated

**Description:** Specifies whether the message being synchronized is an **FAI** message.

**Property ID:** 0x67AA

**Data type:** PtypBoolean, 0x000B

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.5

**Alternate names:** ptagAssociated

## 2.585 PidTagAttachAdditionalInformation

**Canonical name:** PidTagAttachAdditionalInformation

**Description:** Contains attachment encoding information.

**Property ID:** 0x370F

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.21

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_ADDITIONAL\_INFO

## 2.586 PidTagAttachContentBase

**Canonical name:** PidTagAttachContentBase

**Description:** Contains the base of a relative **URI**.

**Property ID:** 0x3711



**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.29

**Consuming reference:** [\[MS-OXCMAIL\]](#) **Alternate names:** PR\_ATTACH\_CONTENT\_BASE, PR\_ATTACH\_CONTENT\_BASE\_A, PR\_ATTACH\_CONTENT\_BASE\_W

## 2.587 PidTagAttachContentId

**Canonical name:** PidTagAttachContentId

**Description:** Contains a content identifier unique to the **Message object** that matches a corresponding "cid:" **URI** schema reference in the **HTML** body of the Message object.

**Property ID:** 0x3712

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.29

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_ATTACH\_CONTENT\_ID, PR\_ATTACH\_CONTENT\_ID\_A, PR\_ATTACH\_CONTENT\_ID\_W

## 2.588 PidTagAttachContentLocation

**Canonical name:** PidTagAttachContentLocation

**Description:** Contains a relative or full **URI** that matches a corresponding reference in the **HTML** body of a **Message object**.

**Property ID:** 0x3713

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.29

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_CONTENT\_LOCATION, PR\_ATTACH\_CONTENT\_LOCATION\_A, PR\_ATTACH\_CONTENT\_LOCATION\_W

## 2.589 PidTagAttachDataBinary

**Canonical name:** PidTagAttachDataBinary

**Description:** Contains the contents of the file to be attached.

**Property ID:** 0x3701

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_DATA\_BIN, ptagAttachDataBin

## 2.590 PidTagAttachDataObject

**Canonical name:** PidTagAttachDataObject

**Description:** Contains the binary representation of the **Attachment object** in an application-specific format.

**Property ID:** 0x3701

**Data type:** PtypObject, 0x000D

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.8

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_ATTACH\_DATA\_OBJ, ptagAttachDataObj

## 2.591 PidTagAttachEncoding

**Canonical name:** PidTagAttachEncoding

**Description:** Contains encoding information about the **Attachment object**.

**Property ID:** 0x3702

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.20

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_ENCODING

## 2.592 PidTagAttachExtension

**Canonical name:** PidTagAttachExtension

**Description:** Contains a file name extension that indicates the document type of an attachment.

**Property ID:** 0x3703

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.12

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_EXTENSION, PR\_ATTACH\_EXTENSION\_A, PR\_ATTACH\_EXTENSION\_W

### 2.593 PidTagAttachFilename

**Canonical name:** PidTagAttachFilename

**Description:** Contains the **8.3 name** of the **PidTagAttachLongFilename** property (section [2.595](#)).

**Property ID:** 0x3704

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-XPFOAB\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_FILENAME, PR\_ATTACH\_FILENAME\_A, ptagAttachFilename, PR\_ATTACH\_FILENAME\_W

### 2.594 PidTagAttachFlags

**Canonical name:** PidTagAttachFlags

**Description:** Indicates which body formats might reference this attachment when rendering data.

**Property ID:** 0x3714

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.18

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACH\_FLAGS

### 2.595 PidTagAttachLongFilename

**Canonical name:** PidTagAttachLongFilename

**Description:** Contains the full filename and extension of the **Attachment object**.

**Property ID:** 0x3707

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.10

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOUM\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_LONG\_FILENAME, PR\_ATTACH\_LONG\_FILENAME\_A, PR\_ATTACH\_LONG\_FILENAME\_W, urn:schemas:httpmail:attachmentfilename

## 2.596 PidTagAttachLongPathname

**Canonical name:** PidTagAttachLongPathname

**Description:** Contains the fully-qualified path and file name with extension.

**Property ID:** 0x370D

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.13

**Consuming reference:** [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_LONG\_PATHNAME, PR\_ATTACH\_LONG\_PATHNAME\_A, ptagAttachLongPathname, PR\_ATTACH\_LONG\_PATHNAME\_W

## 2.597 PidTagAttachmentContactPhoto

**Canonical name:** PidTagAttachmentContactPhoto

**Description:** Indicates that a **contact** photo attachment is attached to a Contact object.

**Property ID:** 0x7FFF

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.8.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACHMENT\_CONTACTPHOTO

## 2.598 PidTagAttachmentFlags

**Canonical name:** PidTagAttachmentFlags

**Description:** Indicates special handling for an **Attachment object**.

**Property ID:** 0x7FFD

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.23

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRN\]](#)

**Alternate names:** PR\_ATTACHMENT\_FLAGS, ptagAttachmentFlags

## 2.599 PidTagAttachmentHidden

**Canonical name:** PidTagAttachmentHidden

**Description:** Indicates whether an **Attachment object** is hidden from the end user.

**Property ID:** 0x7FFE

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.24

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_ATTACHMENT\_HIDDEN

## 2.600 PidTagAttachmentLinkId

**Canonical name:** PidTagAttachmentLinkId

**Description:** Contains the type of **Message object** to which an attachment is linked.

**Property ID:** 0x7FFA

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.22

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACHMENT\_LINKID, ptagAttachmentLinkId

## 2.601 PidTagAttachMethod

**Canonical name:** PidTagAttachMethod

**Description:** Represents the way the contents of an attachment are accessed.

**Property ID:** 0x3705

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.9

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_METHOD, ptagAttachMethod

## 2.602 PidTagAttachMimeTag

**Canonical name:** PidTagAttachMimeTag

**Description:** Contains a content-type **MIME** header.

**Property ID:** 0x370E

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.29

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#)

**Alternate names:** PR\_ATTACH\_MIME\_TAG, PR\_ATTACH\_MIME\_TAG\_A, PR\_ATTACH\_MIME\_TAG\_W

### 2.603 PidTagAttachNumber

**Canonical name:** PidTagAttachNumber

**Description:** Identifies the **Attachment object** within its **Message object**.

**Property ID:** 0x0E21

**Data type:** **PtypInteger32**, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_ATTACH\_NUM, ptagAttachNum

### 2.604 PidTagAttachPathname

**Canonical name:** PidTagAttachPathname

**Description:** Contains the **8.3 name** of the **PidTagAttachLongPathname** property (section [2.596](#)).

**Property ID:** 0x3708

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.14

**Consuming reference:** [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_PATHNAME, PR\_ATTACH\_PATHNAME\_A, ptagAttachPathname, PR\_ATTACH\_PATHNAME\_W

### 2.605 PidTagAttachPayloadClass

**Canonical name:** PidTagAttachPayloadClass

**Description:** Contains the class name of an object that can display the contents of the message.

**Property ID:** 0x371A

**Data type:** **PtypString**, 0x001F

**Area:** Outlook Application

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.29

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_PAYLOAD\_CLASS, PR\_ATTACH\_PAYLOAD\_CLASS\_A, PR\_ATTACH\_PAYLOAD\_CLASS\_W, ptagAttachPayloadClass

## 2.606 PidTagAttachPayloadProviderGuidIdString

**Canonical name:** PidTagAttachPayloadProviderGuidIdString

**Description:** Contains the **GUID** of the software component that can display the contents of the message.

**Property ID:** 0x3719

**Data type:** PtypString, 0x001F

**Area:** Outlook Application

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.29

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR, PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR\_A, PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR\_W

## 2.607 PidTagAttachRendering

**Canonical name:** PidTagAttachRendering

**Description:** Contains a Windows Metafile, as specified in [\[MS-WMF\]](#), for the **Attachment object**.

**Property ID:** 0x3709

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.17

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_RENDERING, ptagAttachRendering

## 2.608 PidTagAttachSize

**Canonical name:** PidTagAttachSize

**Description:** Contains the size, in bytes, consumed by the **Attachment object** on the server.

**Property ID:** 0x0E20

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACH\_SIZE, ptagAttachSize

## 2.609 PidTagAttachTag

**Canonical name:** PidTagAttachTag

**Description:** Contains the identifier information for the application that supplied the **Attachment object** data.

**Property ID:** 0x370A

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.15

**Consuming references:** [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_TAG

## 2.610 PidTagAttachTransportName

**Canonical name:** PidTagAttachTransportName

**Description:** Contains the name of an attachment file, modified so that it can be correlated with **TNEF** messages.

**Property ID:** 0x370C

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.19

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_TRANSPORT\_NAME, PR\_ATTACH\_TRANSPORT\_NAME\_A, PR\_ATTACH\_TRANSPORT\_NAME\_W

## 2.611 PidTagAttributeHidden

**Canonical name:** PidTagAttributeHidden

**Description:** Specifies the hide or show status of a folder.

**Property ID:** 0x10F4

**Data type:** PtypBoolean, 0x000B

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.1

**Consuming references:** [\[MS-OXOSFLD\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_ATTR\_HIDDEN, ptagAttrHidden, DAV:ishidden



## 2.612 PidTagAttributeReadOnly

**Canonical name:** PidTagAttributeReadOnly

**Description:** Indicates whether an item can be modified or deleted.

**Property ID:** 0x10F6

**Data type:** PtypBoolean, 0x000B

**Area:** Access Control Properties

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTR\_READONLY, ptagAttrReadOnly, DAV:isreadonly

## 2.613 PidTagAutoForwardComment

**Canonical name:** PidTagAutoForwardComment

**Description:** Contains text included in an automatically-generated message.

**Property ID:** 0x0004

**Data type:** PtypString, 0x001F

**Area:** General Report Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.21

**Alternate names:** PR\_AUTO\_FORWARD\_COMMENT, PR\_AUTO\_FORWARD\_COMMENT\_A, PR\_AUTO\_FORWARD\_COMMENT\_W

## 2.614 PidTagAutoForwarded

**Canonical name:** PidTagAutoForwarded

**Description:** Indicates that a **Message object** has been automatically generated or automatically forwarded.

**Property ID:** 0x0005

**Data type:** PtypBoolean, 0x000B

**Area:** General Report Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.20

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_AUTO\_FORWARDED, ptagAutoForwarded

## 2.615 PidTagAutoResponseSuppress

**Canonical name:** PidTagAutoResponseSuppress

**Description:** Specifies whether a client or server application will forego sending automated replies in response to this message.

**Property ID:** 0x3FDF

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.77

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_AUTO\_RESPONSE\_SUPPRESS, ptagAutoResponseSuppress

## 2.616 PidTagBirthday

**Canonical name:** PidTagBirthday

**Description:** Contains the date of the **mail user's** birthday at midnight.

**Property ID:** 0x3A42

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.1

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BIRTHDAY, urn:schemas:contacts:bday

## 2.617 PidTagBlockStatus

**Canonical name:** PidTagBlockStatus

**Description:** Indicates the user's preference for viewing external content (such as links to images on an **HTTP** server) in the **message body**.

**Property ID:** 0x1096

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.1

**Alternate names:** PR\_BLOCK\_STATUS, ptagBlockStatus

## 2.618 PidTagBody

**Canonical name:** PidTagBody

**Description:** Contains **message body** text in **plain text** format.

**Property ID:** 0x1000

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BODY, PR\_BODY\_A, ptagBody, PR\_BODY\_W, urn:schemas:httpmail:textdescription

## 2.619 PidTagBodyContentId

**Canonical name:** PidTagBodyContentId

**Description:** Contains a **GUID** that corresponds to the current **message body**.

**Property ID:** 0x1015

**Data type:** PtypString, 0x001F

**Area:** Exchange

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.7

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_BODY\_CONTENT\_ID, PR\_BODY\_CONTENT\_ID\_A, PR\_BODY\_CONTENT\_ID\_W

## 2.620 PidTagBodyContentLocation

**Canonical name:** PidTagBodyContentLocation

**Description:** Contains a globally unique **Uniform Resource Identifier (URI)** that serves as a label for the current **message body**.

**Property ID:** 0x1014

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.8

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_BODY\_CONTENT\_LOCATION, PR\_BODY\_CONTENT\_LOCATION\_A, PR\_BODY\_CONTENT\_LOCATION\_W

## 2.621 PidTagBodyHtml

**Canonical name:** PidTagBodyHtml

**Description:** Contains the **HTML** body of the **Message object**.

**Property ID:** 0x1013

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_BODY\_HTML, PR\_BODY\_HTML\_A, ptagBodyHtml, PR\_BODY\_HTML\_W

## 2.622 PidTagBusiness2TelephoneNumber

**Canonical name:** PidTagBusiness2TelephoneNumber

**Description:** Contains a secondary telephone number at the **mail user's** place of business.

**Property ID:** 0x3A1B

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.23

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** "PR\_BUSINESS2\_TELEPHONE\_NUMBER, PR\_BUSINESS2\_TELEPHONE\_NUMBER\_A, PR\_BUSINESS2\_TELEPHONE\_NUMBER\_W, PR\_OFFICE2\_TELEPHONE\_NUMBER, urn:schemas:contacts:telephonenumber2

## 2.623 PidTagBusiness2TelephoneNumbers

**Canonical name:** PidTagBusiness2TelephoneNumbers

**Description:** Contains secondary telephone numbers at the **mail user's** place of business.

**Property ID:** 0x3A1B

**Data type:** PtypMultipleString, 0x101F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.24

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_BUSINESS2\_TELEPHONE\_NUMBER\_A\_MV

## 2.624 PidTagBusinessFaxNumber

**Canonical name:** PidTagBusinessFaxNumber

**Description:** Contains the telephone number of the **mail user's** business fax machine.

**Property ID:** 0x3A24

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.6

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BUSINESS\_FAX\_NUMBER, PR\_BUSINESS\_FAX\_NUMBER\_A, PR\_BUSINESS\_FAX\_NUMBER\_W, urn:schemas:contacts:facsimiletelephonenumber

## 2.625 PidTagBusinessHomePage

**Canonical name:** PidTagBusinessHomePage

**Description:** Contains the **URL** of the **mail user's** business home page.

**Property ID:** 0x3A51

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.14

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BUSINESS\_HOME\_PAGE, PR\_BUSINESS\_HOME\_PAGE\_A, PR\_BUSINESS\_HOME\_PAGE\_W, urn:schemas:contacts:businesshomepageurn:schemas:contacts:businesshomepage

## 2.626 PidTagBusinessTelephoneNumber

**Canonical name:** PidTagBusinessTelephoneNumber

**Description:** Contains the primary telephone number of the **mail user's** place of business.

**Property ID:** 0x3A08

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.21

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BUSINESS\_TELEPHONE\_NUMBER, PR\_BUSINESS\_TELEPHONE\_NUMBER\_A, PR\_BUSINESS\_TELEPHONE\_NUMBER\_W, PR\_OFFICE\_TELEPHONE\_NUMBER, urn:schemas:contacts:telephoneNumber

## 2.627 PidTagCallbackTelephoneNumber

**Canonical name:** PidTagCallbackTelephoneNumber

**Description:** Contains a telephone number to reach the **mail user**.

**Property ID:** 0x3A02

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CALLBACK\_TELEPHONE\_NUMBER, PR\_CALLBACK\_TELEPHONE\_NUMBER\_A, PR\_CALLBACK\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:callbackphone

## 2.628 PidTagCallId

**Canonical name:** PidTagCallId

**Description:** Contains a unique identifier associated with the phone call.

**Property ID:** 0x6806

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.11

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaCallID

## 2.629 PidTagCarTelephoneNumber

**Canonical name:** PidTagCarTelephoneNumber

**Description:** Contains the **mail user's** car telephone number.

**Property ID:** 0x3A1E

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.9

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CAR\_TELEPHONE\_NUMBER, PR\_CAR\_TELEPHONE\_NUMBER\_A, PR\_CAR\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:othermobile

## 2.630 PidTagCdoRecurrenceid

**Canonical name:** PidTagCdoRecurrenceid

**Description:** Identifies a specific instance of a recurring appointment.

**Property ID:** 0x10C5

**Data type:** PtypTime, 0x0040

**Area:** Exchange

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.38

**Alternate names:** PR\_CDO\_RECURRENCEID, urn:schemas:calendar:recurrenceid

## 2.631 PidTagChangeKey

**Canonical name:** PidTagChangeKey

**Description:** Contains a structure that identifies the last change to the object.

**Property ID:** 0x65E2

**Data type:** **PtypBinary**, 0x0102

**Area:** History Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.7

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#)

**Alternate names:** PR\_CHANGE\_KEY

## 2.632 PidTagChangeNumber

**Canonical name:** PidTagChangeNumber

**Description:** Contains a structure that identifies the last change to the message or folder that is currently being synchronized.

**Property ID:** 0x67A4

**Data type:** **PtypInteger64**, 0x0014

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXCSTOR\]](#)

**Alternate names:** ptagCn

## 2.633 PidTagChildrensNames

**Canonical name:** PidTagChildrensNames

**Description:** Specifies the names of the children of the **contact**.

**Property ID:** 0x3A58

**Data type:** **PtypMultipleString**, 0x101F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.17

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CHILDRENS\_NAMES, PR\_CHILDRENS\_NAMES\_A, PR\_CHILDRENS\_NAMES\_W, urn:schemas:contacts:childrensnames

## 2.634 PidTagClientActions

**Canonical name:** PidTagClientActions

**Description:** Specifies the **actions** the client is required to take on the message.

**Property ID:** 0x6645

**Data type:** **PtypBinary**, 0x0102

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.6

**Alternate names:** PR\_CLIENT\_ACTIONS, ptagClientActions

### 2.635 PidTagClientSubmitTime

**Canonical name:** PidTagClientSubmitTime

**Description:** Contains the current time, in **UTC**, when the email message is submitted.

**Property ID:** 0x0039

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CLIENT\_SUBMIT\_TIME, urn:schemas:httpmail:date, http://schemas.microsoft.com/exchange/date-iso

### 2.636 PidTagCodePageId

**Canonical name:** PidTagCodePageId

**Description:** Contains the identifier for the client code page used for **Unicode** to **double-byte character set (DBCS)** string conversion.

**Property ID:** 0x66C3

**Data type:** PtypInteger32, 0x0003

**Area:** Exchange Profile Configuration

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.15

**Alternate names:** PR\_CODE\_PAGE\_ID, ptagCodePageId

### 2.637 PidTagComment

**Canonical name:** PidTagComment

**Description:** Contains a comment about the purpose or content of the **Address Book object**.

**Property ID:** 0x3004

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.2

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-XWDCAL\]](#)



**Alternate names:** PR\_COMMENT, PR\_COMMENT\_A, ptagComment, PR\_COMMENT\_W, DAV:comment, <http://schemas.microsoft.com/exchange/summary-utf8>

## 2.638 PidTagCompanyMainTelephoneNumber

**Canonical name:** PidTagCompanyMainTelephoneNumber

**Description:** Contains the main telephone number of the **mail user's** company.

**Property ID:** 0x3A57

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.14

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_COMPANY\_MAIN\_PHONE\_NUMBER, PR\_COMPANY\_MAIN\_PHONE\_NUMBER\_A, PR\_COMPANY\_MAIN\_PHONE\_NUMBER\_W, urn:schemas:contacts:organizationmainphone

## 2.639 PidTagCompanyName

**Canonical name:** PidTagCompanyName

**Description:** Contains the **mail user's** company name.

**Property ID:** 0x3A16

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.7

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_COMPANY\_NAME, PR\_COMPANY\_NAME\_A, PR\_COMPANY\_NAME\_W, urn:schemas:contacts:o

## 2.640 PidTagComputerNetworkName

**Canonical name:** PidTagComputerNetworkName

**Description:** Contains the name of the **mail user's** computer network.

**Property ID:** 0x3A49

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.16

**Alternate names:** PR\_COMPUTER\_NETWORK\_NAME, PR\_COMPUTER\_NETWORK\_NAME\_A, PR\_COMPUTER\_NETWORK\_NAME\_W, urn:schemas:contacts:computernetworkname

## 2.641 PidTagConflictEntryId

**Canonical name:** PidTagConflictEntryId

**Description:** Contains the **EntryID** of the conflict resolve message.

**Property ID:** 0x3FF0

**Data type:** PtypBinary, 0x0102

**Area:** ICS

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.4.2

**Alternate names:** PR\_CONFLICT\_ENTRYID, ptagConflictEntryId

## 2.642 PidTagContainerClass

**Canonical name:** PidTagContainerClass

**Description:** Contains a string value that describes the type of **Message object** that a folder contains.

**Property ID:** 0x3613

**Data type:** PtypString, 0x001F

**Area:** Container Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.3

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXMSGI\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_CONTAINER\_CLASS, PR\_CONTAINER\_CLASS\_A, ptagContainerClass, PR\_CONTAINER\_CLASS\_W,  
<http://schemas.microsoft.com/exchange/outlookfolderclass>  
<http://schemas.microsoft.com/exchange/outlookfolderclass>

## 2.643 PidTagContainerContents

**Canonical name:** PidTagContainerContents

**Description:** Empty. An **NSPI** server defines this value for **distribution lists** and it is not present for other objects.

**Property ID:** 0x360F

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Container Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_CONTAINER\_CONTENTS, ptagContainerContents

## 2.644 PidTagContainerFlags

**Canonical name:** PidTagContainerFlags

**Description:** Contains a bitmask of **flags** that describe capabilities of an **address book container**.

**Property ID:** 0x3600

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.1

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_CONTAINER\_FLAGS

## 2.645 PidTagContainerHierarchy

**Canonical name:** PidTagContainerHierarchy

**Description:** Identifies all of the subfolders of the current folder.

**Property ID:** 0x360E

**Data type:** PtypObject, 0x000D

**Area:** Container Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.4

**Consuming references:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_CONTAINER\_HIERARCHY, ptagContainerHierarchy

## 2.646 PidTagContentCount

**Canonical name:** PidTagContentCount

**Description:** Specifies the number of rows under the header row.

**Property ID:** 0x3602

**Data type:** PtypInteger32, 0x0003

**Area:** Folder Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.1

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#)

**Alternate names:** PR\_CONTENT\_COUNT, ptagContentCount, DAV:visiblecount

## 2.647 PidTagContentFilterSpamConfidenceLevel

**Canonical name:** PidTagContentFilterSpamConfidenceLevel

**Description:** Indicates a confidence level that the message is **spam**.

**Property ID:** 0x4076

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CONTENT\_FILTER\_SCL, ptagContentFilterSCL

## 2.648 PidTagContentUnreadCount

**Canonical name:** PidTagContentUnreadCount

**Description:** Specifies the number of rows under the header row that have the **PidTagRead** property (section [2.878](#)) set to FALSE.

**Property ID:** 0x3603

**Data type:** PtypInteger32, 0x0003

**Area:** Folder Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.2

**Consuming references:** [\[MS-OXCTABL\]](#)

**Alternate names:** PR\_CONTENT\_UNREAD, ptagContentUnread, urn:schemas:httpmail:unreadcount

## 2.649 PidTagConversationId

**Canonical name:** PidTagConversationId

**Description:** Contains a computed value derived from other **conversation**-related properties.

**Property ID:** 0x3013

**Data type:** PtypBinary, 0x0102

**Area:** Conversations

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_CONVERSATION\_ID

## 2.650 PidTagConversationIndex

**Canonical name:** PidTagConversationIndex

**Description:** Indicates the relative position of this message within a **conversation** thread.

**Property ID:** 0x0071

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_CONVERSATION\_INDEX, ptagConversationIndex

## 2.651 PidTagConversationIndexTracking

**Canonical name:** PidTagConversationIndexTracking

**Description:** Indicates whether the **GUID** portion of the **PidTagConversationIndex** property (section [2.650](#)) is to be used to compute the **PidTagConversationId** property (section [2.649](#)).

**Property ID:** 0x3016

**Data type:** PtypBoolean, 0x000B

**Area:** Conversations

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.4

**Alternate names:** PR\_CONVERSATION\_INDEX\_TRACKING

## 2.652 PidTagConversationTopic

**Canonical name:** PidTagConversationTopic

**Description:** Contains an unchanging copy of the original subject.

**Property ID:** 0x0070

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CONVERSATION\_TOPIC, PR\_CONVERSATION\_TOPIC\_A, ptagConversationTopic, PR\_CONVERSATION\_TOPIC\_W, urn:schemas:httpmail:thread-topic

## 2.653 PidTagCountry

**Canonical name:** PidTagCountry

**Description:** Contains the name of the **mail user's** country/region.

**Property ID:** 0x3A26

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.19

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_COUNTRY, PR\_COUNTRY\_A, PR\_COUNTRY\_W, PR\_BUSINESS\_ADDRESS\_COUNTRY, PR\_BUSINESS\_ADDRESS\_COUNTRY\_A, PR\_BUSINESS\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:mailingcountry

## 2.654 PidTagCreationTime

**Canonical name:** PidTagCreationTime

**Description:** Contains the time, in **UTC**, that the object was created.

**Property ID:** 0x3007

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.3

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATION\_TIME, ptagCreationTime, DAV:creationdate

## 2.655 PidTagCreatorEntryId

**Canonical name:** PidTagCreatorEntryId

**Description:** Specifies the original author of the message according to their Address Book **EntryID**.

**Property ID:** 0x3FF9

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.31

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATOR\_ENTRYID, ptagCreatorEntryId

## 2.656 PidTagCreatorName

**Canonical name:** PidTagCreatorName

**Description:** Contains the name of the creator of a **Message object**.

**Property ID:** 0x3FF8

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.51

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATOR\_NAME, PR\_CREATOR\_NAME\_A, ptagCreatorName, PR\_CREATOR\_NAME\_W

## 2.657 PidTagCustomerId

**Canonical name:** PidTagCustomerId

**Description:** Contains the **mail user's** customer identification number.

**Property ID:** 0x3A4A

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.8

**Alternate names:** PR\_CUSTOMER\_ID, PR\_CUSTOMER\_ID\_A, PR\_CUSTOMER\_ID\_W, urn:schemas:contacts:customerid

## 2.658 PidTagDamBackPatched

**Canonical name:** PidTagDamBackPatched

**Description:** Indicates whether the **Deferred Action Message (DAM)** was updated by the server.

**Property ID:** 0x6647

**Data type:** PtypBoolean, 0x000B

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.2

**Alternate names:** PR\_DAM\_BACK\_PATCHED, ptagDamBackPatched

## 2.659 PidTagDamOriginalEntryId

**Canonical name:** PidTagDamOriginalEntryId

**Description:** Contains the **EntryID** of the delivered message that the client has to process.

**Property ID:** 0x6646

**Data type:** PtypBinary, 0x0102

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.3

**Alternate names:** PR\_DAM\_ORIGINAL\_ENTRYID

## 2.660 PidTagDefaultPostMessageClass

**Canonical name:** PidTagDefaultPostMessageClass

**Description:** Contains the **message class** of the object.

**Property ID:** 0x36E5

**Data type:** PtypString, 0x001F

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.11.2

**Alternate names:** PR\_DEF\_POST\_MSGCLASS

### 2.661 PidTagDeferredActionMessageOriginalEntryId

**Canonical name:** PidTagDeferredActionMessageOriginalEntryId

**Description:** Contains the server **EntryID** for the **DAM**.

**Property ID:** 0x6741

**Data type:** PtypServerId, 0x00FB

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.8

**Alternate names:** PR\_DAM\_ORIG\_MSG\_SVREID, ptagDamOrgMsgSvrEID

### 2.662 PidTagDeferredDeliveryTime

**Canonical name:** PidTagDeferredDeliveryTime

**Description:** Contains the date and time, in **UTC**, at which the sender prefers that the message be delivered.

**Property ID:** 0x000F

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.6

**Alternate names:** PR\_DEFERRED\_DELIVERY\_TIME, ptagDeferredDeliveryTime, <http://schemas.microsoft.com/exchange/deferred-delivery-iso>

### 2.663 PidTagDeferredSendNumber

**Canonical name:** PidTagDeferredSendNumber

**Description:** Contains a number used in the calculation of how long to defer sending a message.

**Property ID:** 0x3FEB

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.2

**Alternate names:** PR\_DEFERRED\_SEND\_NUMBER

### 2.664 PidTagDeferredSendTime

**Canonical name:** PidTagDeferredSendTime

**Description:** Contains the amount of time after which a client would like to defer sending the message.



**Property ID:** 0x3FEF

**Data type:** PtypTime, 0x0040

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.4

**Alternate names:** PR\_DEFERRED\_SEND\_TIME, ptagDeferredSendTime

## 2.665 PidTagDeferredSendUnits

**Canonical name:** PidTagDeferredSendUnits

**Description:** Specifies the unit of time used as a multiplier with the **PidTagDeferredSendNumber** property (section [2.663](#)) value.

**Property ID:** 0x3FEC

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.3

**Alternate names:** PR\_DEFERRED\_SEND\_UNITS

## 2.666 PidTagDelegatedByRule

**Canonical name:** PidTagDelegatedByRule

**Description:** Specifies whether the message was forwarded due to the triggering of a **delegate** forward **rule**.

**Property ID:** 0x3FE3

**Data type:** PtypBoolean, 0x000B

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.84

**Consuming references:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_DELEGATED\_BY\_RULE

## 2.667 PidTagDelegateFlags

**Canonical name:** PidTagDelegateFlags

**Description:** Indicates whether **delegates** can view **Message objects** that are marked as private.

**Property ID:** 0x686B

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.6

**Alternate names:** PR\_DELEGATE\_FLAGS, ptagDelegateFlags

## 2.668 PidTagDeleteAfterSubmit

**Canonical name:** PidTagDeleteAfterSubmit

**Description:** Indicates that the original message is to be deleted after it is sent.

**Property ID:** 0x0E01

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.8

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** PR\_DELETE\_AFTER\_SUBMIT, ptagDeleteAfterSubmit

## 2.669 PidTagDeletedCountTotal

**Canonical name:** PidTagDeletedCountTotal

**Description:** Contains the total count of messages that have been deleted from a folder, excluding messages deleted within subfolders.

**Property ID:** 0x670B

**Data type:** PtypInteger32, 0x0003

**Area:** Server

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.15

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_DELETED\_COUNT\_TOTAL, ptagDeleteCountTotal

## 2.670 PidTagDeletedOn

**Canonical name:** PidTagDeletedOn

**Description:** Specifies the time, in **UTC**, when the item or folder was **soft deleted**.

**Property ID:** 0x668F

**Data type:** PtypTime, 0x0040

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.3

**Alternate names:** PR\_DELETED\_ON, ptagDeletedOn, urn:schemas:httpmail:deletedon

## 2.671 PidTagDeliverTime

**Canonical name:** PidTagDeliverTime

**Description:** Contains the delivery time for a delivery status notification, as specified [\[RFC3464\]](#), or a message disposition notification, as specified in [\[RFC3798\]](#).

**Property ID:** 0x0010

**Data type:** PtypTime, 0x0040

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.29

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_DELIVER\_TIME, ptagDeliverTime

## 2.672 PidTagDepartmentName

**Canonical name:** PidTagDepartmentName

**Description:** Contains a name for the department in which the **mail user** works.

**Property ID:** 0x3A18

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.6

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_DEPARTMENT\_NAME, PR\_DEPARTMENT\_NAME\_A, PR\_DEPARTMENT\_NAME\_W, urn:schemas:contacts:department

## 2.673 PidTagDepth

**Canonical name:** PidTagDepth

**Description:** Specifies the number of nested categories in which a given row is contained.

**Property ID:** 0x3005

**Data type:** PtypInteger32, 0x0003

**Area:** MapiCommon

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_DEPTH, ptagDepth

## 2.674 PidTagDisplayBcc

**Canonical name:** PidTagDisplayBcc

**Description:** Contains a list of **blind carbon copy (Bcc) recipient display names**.

**Property ID:** 0x0E02

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.7

**Consuming reference:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_DISPLAY\_BCC, PR\_DISPLAY\_BCC\_A, ptagDisplayBcc, PR\_DISPLAY\_BCC\_W, urn:schemas:httpmail:displaybcc

## 2.675 PidTagDisplayCc

**Canonical name:** PidTagDisplayCc

**Description:** Contains a list of **carbon copy (Cc) recipient display names**.

**Property ID:** 0x0E03

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_DISPLAY\_CC, PR\_DISPLAY\_CC\_A, ptagDisplayCc, PR\_DISPLAY\_CC\_W, urn:schemas:httpmail:displaycc

## 2.676 PidTagDisplayName

**Canonical name:** PidTagDisplayName

**Description:** Contains the **display name** of the folder.

**Property ID:** 0x3001

**Data type:** PtypString, 0x001F

**Area:** MapiCommon

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.5

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDVSEC\]](#)

**Alternate names:** PR\_DISPLAY\_NAME, PR\_DISPLAY\_NAME\_A, ptagDisplayName, PR\_DISPLAY\_NAME\_W, urn:schemas:contacts:cn

## 2.677 PidTagDisplayNamePrefix

**Canonical name:** PidTagDisplayNamePrefix

**Description:** Contains the **mail user's** honorific title.

**Property ID:** 0x3A45

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_DISPLAY\_NAME\_PREFIX, PR\_DISPLAY\_NAME\_PREFIX\_A, PR\_DISPLAY\_NAME\_PREFIX\_W, urn:schemas:contacts:personaltitle

## 2.678 PidTagDisplayTo

**Canonical name:** PidTagDisplayTo

**Description:** Contains a list of the **primary recipient display names**, separated by semicolons, when an email message has primary recipients .

**Property ID:** 0x0E04

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_DISPLAY\_TO, PR\_DISPLAY\_TO\_A, ptagDisplayTo, PR\_DISPLAY\_TO\_W

## 2.679 PidTagDisplayType

**Canonical name:** PidTagDisplayType

**Description:** Contains an integer value that indicates how to display an **Address Book object** in a table or as an addressee on a message.

**Property ID:** 0x3900

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAddressBook

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_DISPLAY\_TYPE, ptagDisplayType

## 2.680 PidTagDisplayTypeEx

**Canonical name:** PidTagDisplayTypeEx

**Description:** Contains an integer value that indicates how to display an **Address Book object** in a table or as a **recipient** on a message.

**Property ID:** 0x3905

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAddressBook

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_DISPLAY\_TYPE\_EX

## 2.681 PidTagEmailAddress

**Canonical name:** PidTagEmailAddress

**Description:** Contains the email address of a **Message object**.

**Property ID:** 0x3003

**Data type:** PtypString, 0x001F

**Area:** MapiCommon

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.14

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXPSVAL\]](#)

**Alternate names:** PR\_EMAIL\_ADDRESS, PR\_EMAIL\_ADDRESS\_A, PR\_EMAIL\_ADDRESS\_W

## 2.682 PidTagEndDate

**Canonical name:** PidTagEndDate

**Description:** Contains the value of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

**Property ID:** 0x0061

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.31

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_END\_DATE, [http://schemas.microsoft.com/mapi/end\\_date](http://schemas.microsoft.com/mapi/end_date)

## 2.683 PidTagEntryId

**Canonical name:** PidTagEntryId

**Description:** Contains the information to identify many different types of **messaging objects**.

**Property ID:** 0x0FFF

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCPerm\]](#) section 2.2.4

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-](#)

[OXOCNTC](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXWAVLS\]](#)

**Alternate names:** PR\_ENTRYID, ptagEntryId

## 2.684 PidTagExceptionEndTime

**Canonical name:** PidTagExceptionEndTime

**Description:** Contains the end date and time of the exception in the local time zone of the computer when the exception is created.

**Property ID:** 0x7FFC

**Data type:** PtypTime, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.1.5

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_EXCEPTION\_ENDTIME, ptagExceptionEndTime

## 2.685 PidTagExceptionReplaceTime

**Canonical name:** PidTagExceptionReplaceTime

**Description:** Indicates the original date and time, in **UTC**, at which the instance in the **recurrence pattern** would have occurred if it were not an exception.

**Property ID:** 0x7FF9

**Data type:** PtypTime, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.1.6

**Alternate names:** PR\_EXCEPTION\_REPLACETIME

## 2.686 PidTagExceptionStartTime

**Canonical name:** PidTagExceptionStartTime

**Description:** Contains the start date and time of the exception in the local time zone of the computer when the exception is created.

**Property ID:** 0x7FFB

**Data type:** PtypTime, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.1.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_EXCEPTION\_STARTTIME, ptagExceptionStartTime

## 2.687 PidTagExchangeNTSecurityDescriptor

**Canonical name:** PidTagExchangeNTSecurityDescriptor

**Description:** Contains the calculated security descriptor for the item.

**Property ID:** 0x0E84

**Data type:** PtypBinary, 0x0102

**Area:** Calendar Document

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.8

**Alternate names:** <http://schemas.microsoft.com/exchange/ntsecuritydescriptor>,  
<http://schemas.microsoft.com/exchange/ntsecuritydescriptor>

## 2.688 PidTagExpiryNumber

**Canonical name:** PidTagExpiryNumber

**Description:** Contains an integer value that is used along with the **PidTagExpiryUnits** property (section [2.690](#)) to define the expiry send time.

**Property ID:** 0x3FED

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.5

**Alternate names:** PR\_EXPIRY\_NUMBER

## 2.689 PidTagExpiryTime

**Canonical name:** PidTagExpiryTime

**Description:** Contains the time, in **UTC**, after which a client wants to receive an expiry event if the message arrives late.

**Property ID:** 0x0015

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.7

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_EXPIRY\_TIME, ptagExpiryTime, urn:schemas:httpmail:expiry-date,  
<http://schemas.microsoft.com/exchange/expiry-date-iso>

## 2.690 PidTagExpiryUnits

**Canonical name:** PidTagExpiryUnits

**Description:** Contains the unit of time that the value of the **PidTagExpiryNumber** property (section [2.688](#)) multiplies.



**Property ID:** 0x3FEE

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.6

**Alternate names:** PR\_EXPIRY\_UNITS

## 2.691 PidTagExtendedFolderFlags

**Canonical name:** PidTagExtendedFolderFlags

**Description:** Contains encoded sub-properties for a folder.

**Property ID:** 0x36DA

**Data type:** PtypBinary, 0x0102

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_EXTENDED\_FOLDER\_FLAGS, ptagExtendedFolderFlags

## 2.692 PidTagExtendedRuleMessageActions

**Canonical name:** PidTagExtendedRuleMessageActions

**Description:** Contains **action** information about named properties used in the **rule**.

**Property ID:** 0x0E99

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.9

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_MSG\_ACTIONS

## 2.693 PidTagExtendedRuleMessageCondition

**Canonical name:** PidTagExtendedRuleMessageCondition

**Description:** Contains condition information about named properties used in the **rule**.

**Property ID:** 0x0E9A

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.10

**Consuming references:** [\[MS-OXCPRPT\]](#), [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_MSG\_CONDITION

## 2.694 PidTagExtendedRuleSizeLimit

**Canonical name:** PidTagExtendedRuleSizeLimit

**Description:** Contains the maximum size, in bytes, that the user is allowed to accumulate for a single extended **rule**.

**Property ID:** 0x0E9B

**Data type:** PtypInteger32, 0x0003

**Area:** Rules

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.1

**Consuming Reference:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_SIZE\_LIMIT

## 2.695 PidTagFaxNumberOfPages

**Canonical name:** PidTagFaxNumberOfPages

**Description:** Contains the number of pages in a Fax object.

**Property ID:** 0x6804

**Data type:** PtypInteger32, 0x0003

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.7

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaFaxNumberOfPages

## 2.696 PidTagFlagCompleteTime

**Canonical name:** PidTagFlagCompleteTime

**Description:** Specifies the date and time, in **UTC**, that the **Message object** was flagged as complete.

**Property ID:** 0x1091

**Data type:** PtypTime, 0x0040

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_FLAG\_COMPLETE\_TIME, ptagFlagCompleteTime, urn:schemas:httpmail:flagcompleted

## 2.697 PidTagFlagStatus

**Canonical name:** PidTagFlagStatus

**Description:** Specifies the flag state of the **Message object**.

**Property ID:** 0x1090

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_FLAG\_STATUS, ptagFlagStatus

## 2.698 PidTagFlatUrlName

**Canonical name:** PidTagFlatUrlName

**Description:** Contains a unique identifier for an item across the **message store**.

**Property ID:** 0x670E

**Data type:** PtypString, 0x001F

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.9

**Alternate names:** PR\_FLAT\_URL\_NAME, PR\_FLAT\_URL\_NAME\_A, PR\_FLAT\_URL\_NAME\_W, ptagFlatURLName, http://schemas.microsoft.com/exchange/permanenturl

## 2.699 PidTagFolderAssociatedContents

**Canonical name:** PidTagFolderAssociatedContents

**Description:** Identifies all **FAI** messages in the current folder.

**Property ID:** 0x3610

**Data type:** PtypObject, 0x000D

**Area:** MapiContainer

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.6

**Consuming references:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_FOLDER\_ASSOCIATED\_CONTENTS

## 2.700 PidTagFolderId

**Canonical name:** PidTagFolderId

**Description:** Contains the Folder ID (FID) ([\[MS-OXCDATA\]](#) section 2.2.1.1) of the folder.

**Property ID:** 0x6748

**Data type:** PtypInteger64, 0x0014

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** ptagFID

## 2.701 PidTagFolderFlags

**Canonical name:** PidTagFolderFlags

**Description:** Contains a computed value to specify the type or state of a folder.

**Property ID:** 0x66A8

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.5

**Alternate names:** PR\_FOLDER\_FLAGS

## 2.702 PidTagFolderType

**Canonical name:** PidTagFolderType

**Description:** Specifies the type of a folder that includes the **Root folder**, Generic folder, and Search folder.

**Property ID:** 0x3601

**Data type:** PtypInteger32, 0x0003

**Area:** MapiContainer

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_FOLDER\_TYPE, ptagFolderType

## 2.703 PidTagFollowupIcon

**Canonical name:** PidTagFollowupIcon

**Description:** Specifies the flag color of the **Message object**.

**Property ID:** 0x1095

**Data type:** PtypInteger32, 0x0003

**Area:** RenMessageFolder

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_FOLLOWUP\_ICON, ptagFollowupIcon

## 2.704 PidTagFreeBusyCountMonths

**Canonical name:** PidTagFreeBusyCountMonths

**Description:** Contains an integer value used to calculate the start and end dates of the range of free/busy data to be published to the **public folders**.

**Property ID:** 0x6869

**Data type:** PtypInteger32, 0x0003

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.1

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_FREEBUSY\_COUNT\_MONTHS

## 2.705 PidTagFreeBusyEntryIds

**Canonical name:** PidTagFreeBusyEntryIds

**Description:** Contains **EntryIDs** of the Delegate Information object, the free/busy message of the logged on user, and the folder with the **PidTagDisplayName** property (section [2.676](#)) value of "Freebusy Data".

**Property ID:** 0x36E4

**Data type:** PtypMultipleBinary, 0x1102

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.6

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_FREEBUSY\_ENTRYIDS, ptagFreeBusyEntryIds

## 2.706 PidTagFreeBusyMessageEmailAddress

**Canonical name:** PidTagFreeBusyMessageEmailAddress

**Description:** Specifies the email address of the user or resource to whom this free/busy message applies.

**Property ID:** 0x6849

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.12

**Alternate names:** PR\_FREEBUSY\_EMA

## 2.707 PidTagFreeBusyPublishEnd

**Canonical name:** PidTagFreeBusyPublishEnd

**Description:** Specifies the end time, in **UTC**, of the publishing range.

**Property ID:** 0x6848

**Data type:** PtypInteger32, 0x0003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.10

**Alternate names:** PR\_FREEBUSY\_PUBLISH\_END

## 2.708 PidTagFreeBusyPublishStart

**Canonical name:** PidTagFreeBusyPublishStart

**Description:** Specifies the start time, in **UTC**, of the publishing range.

**Property ID:** 0x6847

**Data type:** PtypInteger32, 0x0003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.9

**Alternate names:** PR\_FREEBUSY\_PUBLISH\_START

## 2.709 PidTagFreeBusyRangeTimestamp

**Canonical name:** PidTagFreeBusyRangeTimestamp

**Description:** Specifies the time, in **UTC**, that the data was published.

**Property ID:** 0x6868

**Data type:** PtypTime, 0x0040

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.11

**Alternate names:** PR\_FREEBUSY\_RANGE\_TIMESTAMP

## 2.710 PidTagFtpSite

**Canonical name:** PidTagFtpSite

**Description:** Contains the **File Transfer Protocol (FTP)** site address of the **mail user**.

**Property ID:** 0x3A4C

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.15

**Alternate names:** PR\_FTP\_SITE, PR\_FTP\_SITE\_A, PR\_FTP\_SITE\_W, urn:schemas:contacts:ftpsite

### 2.711 PidTagGatewayNeedsToRefresh

**Canonical name:** PidTagGatewayNeedsToRefresh

**Description:** This property is deprecated and SHOULD NOT be used.

**Property ID:** 0x6846

**Data type:** PtypBoolean, 0x000B

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.4.1

**Alternate names:** PR\_GATEWAY\_NEEDS\_TO\_REFRESH

### 2.712 PidTagGender

**Canonical name:** PidTagGender

**Description:** Contains a value that represents the **mail user's** gender.

**Property ID:** 0x3A4D

**Data type:** PtypInteger16, 0x0002

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.20

**Alternate names:** PR\_GENDER, urn:schemas:contacts:gender

### 2.713 PidTagGeneration

**Canonical name:** PidTagGeneration

**Description:** Contains a generational abbreviation that follows the full name of the **mail user**.

**Property ID:** 0x3A05

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_GENERATION, PR\_GENERATION\_A, PR\_GENERATION\_W, urn:schemas:contacts:namesuffix

### 2.714 PidTagGivenName

**Canonical name:** PidTagGivenName

**Description:** Contains the **mail user's** given name.

**Property ID:** 0x3A06

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.2

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_GIVEN\_NAME, PR\_GIVEN\_NAME\_A, PR\_GIVEN\_NAME\_W, urn:schemas:contacts:givenName

## 2.715 PidTagGovernmentIdNumber

**Canonical name:** PidTagGovernmentIdNumber

**Description:** Contains a government identifier for the **mail user**.

**Property ID:** 0x3A07

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.9

**Alternate names:** PR\_GOVERNMENT\_ID\_NUMBER, PR\_GOVERNMENT\_ID\_NUMBER\_A, PR\_GOVERNMENT\_ID\_NUMBER\_W, urn:schemas:contacts:governmentid

## 2.716 PidTagHasAttachments

**Canonical name:** PidTagHasAttachments

**Description:** Indicates whether the **Message object** contains at least one attachment.

**Property ID:** 0x0E1B

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties Property set

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_HASATTACH, ptagHasAttach, urn:schemas:httpmail:hasattachment

## 2.717 PidTagHasDeferredActionMessages

**Canonical name:** PidTagHasDeferredActionMessages

**Description:** Indicates whether a **Message object** has a deferred **action** message associated with it.

**Property ID:** 0x3FEA

**Data type:** PtypBoolean, 0x000B

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.9.1

**Alternate names:** PR\_HAS\_DAMS, ptagHasDAMs



## 2.718 PidTagHasNamedProperties

**Canonical name:** PidTagHasNamedProperties

**Description:** Indicates whether the **Message object** has a **named property**.

**Property ID:** 0x664A

**Data type:** PtypBoolean, 0x000B

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.39

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_HAS\_NAMED\_PROPERTIES, ptagHasNamedProperties

## 2.719 PidTagHasRules

**Canonical name:** PidTagHasRules

**Description:** Indicates whether a **Folder object** has **rules**.

**Property ID:** 0x663A

**Data type:** PtypBoolean, 0x000B

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.8.1

**Alternate names:** PR\_HAS\_RULES, ptagHasRules

## 2.720 PidTagHierarchyChangeNumber

**Canonical name:** PidTagHierarchyChangeNumber

**Description:** Contains a number that monotonically increases every time a subfolder is added to, or deleted from, this folder.

**Property ID:** 0x663E

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.8

**Alternate names:** PR\_HIERARCHY\_CHANGE\_NUM

## 2.721 PidTagHierRev

**Canonical name:** PidTagHierRev

**Description:** Specifies the time, in **UTC**, to trigger the client in cached mode to synchronize the folder hierarchy.

**Property ID:** 0x4082

**Data type:** PtypTime, 0x0040

**Area:** TransportEnvelope

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.9

**Alternate names:** PR\_HIER\_REV, ptagHierRev

## 2.722 PidTagHobbies

**Canonical name:** PidTagHobbies

**Description:** Contains the names of the **mail user's** hobbies.

**Property ID:** 0x3A43

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOBBIES, PR\_HOBBIES\_A, PR\_HOBBIES\_W, urn:schemas:contacts:hobbies

## 2.723 PidTagHome2TelephoneNumber

**Canonical name:** PidTagHome2TelephoneNumber

**Description:** Contains a secondary telephone number at the **mail user's** home.

**Property ID:** 0x3A2F

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.25

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME2\_TELEPHONE\_NUMBER, PR\_HOME2\_TELEPHONE\_NUMBER\_A, PR\_HOME2\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:homephone2

## 2.724 PidTagHome2TelephoneNumbers

**Canonical name:** PidTagHome2TelephoneNumbers

**Description:** Contains secondary telephone numbers at the **mail user's** home.

**Property ID:** 0x3A2F

**Data type:** PtypMultipleString, 0x101F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.26

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_HOME2\_TELEPHONE\_NUMBER\_A\_MV

## 2.725 PidTagHomeAddressCity

**Canonical name:** PidTagHomeAddressCity

**Description:** Contains the name of the **mail user's** home locality, such as the town or city.

**Property ID:** 0x3A59

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_CITY, PR\_HOME\_ADDRESS\_CITY\_A, PR\_HOME\_ADDRESS\_CITY\_W, urn:schemas:contacts:homeCity

## 2.726 PidTagHomeAddressCountry

**Canonical name:** PidTagHomeAddressCountry

**Description:** Contains the name of the **mail user's** home country/region.

**Property ID:** 0x3A5A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_COUNTRY, PR\_HOME\_ADDRESS\_COUNTRY\_A, PR\_HOME\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:homeCountry

## 2.727 PidTagHomeAddressPostalCode

**Canonical name:** PidTagHomeAddressPostalCode

**Description:** Contains the postal code for the **mail user's** home postal address.

**Property ID:** 0x3A5B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_POSTAL\_CODE, PR\_HOME\_ADDRESS\_POSTAL\_CODE\_A, PR\_HOME\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:homePostalCode

## 2.728 PidTagHomeAddressPostOfficeBox

**Canonical name:** PidTagHomeAddressPostOfficeBox

**Description:** Contains the number or identifier of the **mail user's** home post office box.

**Property ID:** 0x3A5E

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX, PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:homepostofficebox

## 2.729 PidTagHomeAddressStateOrProvince

**Canonical name:** PidTagHomeAddressStateOrProvince

**Description:** Contains the name of the **mail user's** home state or province.

**Property ID:** 0x3A5C

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:homeState

## 2.730 PidTagHomeAddressStreet

**Canonical name:** PidTagHomeAddressStreet

**Description:** Contains the **mail user's** home street address.

**Property ID:** 0x3A5D

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.20

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_STREET, PR\_HOME\_ADDRESS\_STREET\_A, PR\_HOME\_ADDRESS\_STREET\_W, urn:schemas:contacts:homeStreet

## 2.731 PidTagHomeFaxNumber

**Canonical name:** PidTagHomeFaxNumber

**Description:** Contains the telephone number of the **mail user's** home fax machine.

**Property ID:** 0x3A25

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.6

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_FAX\_NUMBER, PR\_HOME\_FAX\_NUMBER\_A, PR\_HOME\_FAX\_NUMBER\_W, urn:schemas:contacts:homefax

## 2.732 PidTagHomeTelephoneNumber

**Canonical name:** PidTagHomeTelephoneNumber

**Description:** Contains the primary telephone number of the **mail user's** home.

**Property ID:** 0x3A09

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.22

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_TELEPHONE\_NUMBER, PR\_HOME\_TELEPHONE\_NUMBER\_A, PR\_HOME\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:homePhone

## 2.733 PidTagHtml

**Canonical name:** PidTagHtml

**Description:** Contains **message body** text in **HTML** format.

**Property ID:** 0x1013

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.9

**Consuming references:** [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_HTML, ptagHtml

## 2.734 PidTagICalendarEndTime

**Canonical name:** PidTagICalendarEndTime

**Description:** Contains the date and time, in **UTC**, when an appointment or **meeting** ends.

**Property ID:** 0x10C4

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.39

**Alternate names:** urn:schemas:calendar:dtend

### 2.735 PidTagICalendarReminderNextTime

**Canonical name:** PidTagICalendarReminderNextTime

**Description:** Contains the date and time, in UTC, for the activation of the next **reminder**.

**Property ID:** 0x10CA

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.40

**Alternate names:** urn:schemas:calendar:remindernexttime

### 2.736 PidTagICalendarStartTime

**Canonical name:** PidTagICalendarStartTime

**Description:** Contains the date and time, in **UTC**, when the appointment or **meeting** starts.

**Property ID:** 0x10C3

**Data type:** PtypTime, 0x0040

**Area:** Calendar Property set

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.41

**Alternate names:** urn:schemas:calendar:dtstart

### 2.737 PidTagIconIndex

**Canonical name:** PidTagIconIndex

**Description:** Specifies which icon is to be used by a user interface when displaying a group of **Message objects**.

**Property ID:** 0x1080

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.10

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ICON\_INDEX, ptagIconIndex

## 2.738 PidTagImportance

**Canonical name:** PidTagImportance

**Description:** Indicates the level of importance assigned by the end user to the **Message object**.

**Property ID:** 0x0017

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_IMPORTANCE, ptagImportance, urn:schemas:httpmail:importance, http://schemas.microsoft.com/exchange/importance-long, http://schemas.microsoft.com/exchange/x-priority-long

## 2.739 PidTagInConflict

**Canonical name:** PidTagInConflict

**Description:** Specifies whether the attachment represents an alternate replica.

**Property ID:** 0x666C

**Data type:** PtypBoolean, 0x000B

**Area:** Conflict Note

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.4.3

**Alternate names:** PR\_IN\_CONFLICT, ptagInConflict

## 2.740 PidTagInitialDetailsPane

**Canonical name:** PidTagInitialDetailsPane

**Description:** Indicates which page of a **display template** to display first.

**Property ID:** 0x3F08

**Data type:** PtypInteger32, 0x0003

**Area:** MAPI Display Tables

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.33

**Consuming Reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_INITIAL\_DETAILS\_PANE

## 2.741 PidTagInitials

**Canonical name:** PidTagInitials

**Description:** Contains the initials for parts of the full name of the **mail user**.

**Property ID:** 0x3A0A

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.3

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_INITIALS, PR\_INITIALS\_A, PR\_INITIALS\_W, urn:schemas:contacts:initials

## 2.742 PidTagInReplyToId

**Canonical name:** PidTagInReplyToId

**Description:** Contains the value of the original message's **PidTagInternetMessageId** property (section [2.748](#)) value.

**Property ID:** 0x1042

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.13

**Consuming Reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_IN\_REPLY\_TO\_ID, PR\_IN\_REPLY\_TO\_ID\_A, PR\_IN\_REPLY\_TO\_ID\_W

## 2.743 PidTagInstanceKey

**Canonical name:** PidTagInstanceKey

**Description:** Contains an object on an **NSPI** server.

**Property ID:** 0x0FF6

**Data type:** PtypBinary, 0x0102

**Area:** Table Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_INSTANCE\_KEY, ptagInstanceKey

## 2.744 PidTagInstanceNum

**Canonical name:** PidTagInstanceNum

**Description:** Contains an identifier for a single instance of a row in the table.

**Property ID:** 0x674E

**Data type:** PtypInteger32, 0x0003

**Area:** ProviderDefinedNonTransmittable



**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.2

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** ptagInstanceNum

## 2.745 PidTagInstID

**Canonical name:** PidTagInstID

**Description:** Contains an identifier for all instances of a row in the table.

**Property ID:** 0x674D

**Data type:** **PtypInteger64**, 0x0014

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.1

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** ptagInstID

## 2.746 PidTagInternetCodepage

**Canonical name:** PidTagInternetCodepage

**Description:** Indicates the code page used for the **PidTagBody** property (section [2.618](#)) or the **PidTagBodyHtml** property (section [2.621](#)).

**Property ID:** 0x3FDE

**Data type:** **PtypInteger32**, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_INTERNET\_CPID, ptagInternetCpid

## 2.747 PidTagInternetMailOverrideFormat

**Canonical name:** PidTagInternetMailOverrideFormat

**Description:** Indicates the encoding method and **HTML** inclusion for attachments.

**Property ID:** 0x5902

**Data type:** **PtypInteger32**, 0x0003

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_INETMAIL\_OVERRIDE\_FORMAT, ptagInetMailOverrideFormat

## 2.748 PidTagInternetMessageId

**Canonical name:** PidTagInternetMessageId

**Description:** Corresponds to the **message-id** field.

**Property ID:** 0x1035

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_INTERNET\_MESSAGE\_ID, PR\_INTERNET\_MESSAGE\_ID\_A, PR\_INTERNET\_MESSAGE\_ID\_W

## 2.749 PidTagInternetReferences

**Canonical name:** PidTagInternetReferences

**Description:** Contains a list of message IDs that specify the messages to which this reply is related.

**Property ID:** 0x1039

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_INTERNET\_REFERENCES, PR\_INTERNET\_REFERENCES\_A, PR\_INTERNET\_REFERENCES\_W

## 2.750 PidTagIpmAppointmentEntryId

**Canonical name:** PidTagIpmAppointmentEntryId

**Description:** Contains the **EntryID** of the **Calendar folder**.

**Property ID:** 0x36D0

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_APPOINTMENT\_ENTRYID

## 2.751 PidTagIpmContactEntryId

**Canonical name:** PidTagIpmContactEntryId

**Description:** Contains the **EntryID** of the **Contacts folder**.

**Property ID:** 0x36D1

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_CONTACT\_ENTRYID

### 2.752 PidTagIpmDraftsEntryId

**Canonical name:** PidTagIpmDraftsEntryId

**Description:** Contains the **EntryID** of the Drafts folder.

**Property ID:** 0x36D7

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Alternate names:** PR\_IPM\_DRAFTS\_ENTRYID

### 2.753 PidTagIpmJournalEntryId

**Canonical name:** PidTagIpmJournalEntryId

**Description:** Contains the **EntryID** of the Journal folder.

**Property ID:** 0x36D2

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_JOURNAL\_ENTRYID

### 2.754 PidTagIpmNoteEntryId

**Canonical name:** PidTagIpmNoteEntryId

**Description:** Contains the **EntryID** of the Notes folder.

**Property ID:** 0x36D3

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_NOTE\_ENTRYID

## 2.755 PidTagIpmTaskEntryId

**Canonical name:** PidTagIpmTaskEntryId

**Description:** Contains the **EntryID** of the Tasks folder.

**Property ID:** 0x36D4

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_TASK\_ENTRYID

## 2.756 PidTagIsdnNumber

**Canonical name:** PidTagIsdnNumber

**Description:** Contains the **Integrated Services Digital Network (ISDN)** telephone number of the **mail user**.

**Property ID:** 0x3A2D

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.16

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ISDN\_NUMBER, PR\_ISDN\_NUMBER\_A, PR\_ISDN\_NUMBER\_W,  
urn:schemas:contacts:internationalisdnnumber

## 2.757 PidTagJunkAddRecipientsToSafeSendersList

**Canonical name:** PidTagJunkAddRecipientsToSafeSendersList

**Description:** Indicates whether email **recipients** are to be added to the safe senders list.

**Property ID:** 0x6103

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.1

**Alternate names:** PR\_JUNK\_ADD\_RECIPS\_TO\_SSL

## 2.758 PidTagJunkIncludeContacts

**Canonical name:** PidTagJunkIncludeContacts

**Description:** Indicates whether email addresses of the **contacts** in the Contacts folder are treated in a special way with respect to the **spam filter**.

**Property ID:** 0x6100

**Data type:** **PtypInteger32**, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.2

**Alternate names:** PR\_JUNK\_INCLUDE\_CONTACTS

## 2.759 PidTagJunkPermanentlyDelete

**Canonical name:** PidTagJunkPermanentlyDelete

**Description:** Indicates whether messages identified as **spam** can be permanently deleted.

**Property ID:** 0x6102

**Data type:** **PtypInteger32**, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.3

**Alternate names:** PR\_JUNK\_PERMANENTLY\_DELETE

## 2.760 PidTagJunkPhishingEnableLinks

**Canonical name:** PidTagJunkPhishingEnableLinks

**Description:** Indicated whether the **phishing** stamp on a message is to be ignored.

**Property ID:** 0x6107

**Data type:** **PtypBoolean**, 0x000B

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.4

**Consuming reference:** [\[MS-OXPHISH\]](#)

**Alternate names:** PR\_JUNK\_PHISHING\_ENABLE\_LINKS

## 2.761 PidTagJunkThreshold

**Canonical name:** PidTagJunkThreshold

**Description:** Indicates how aggressively incoming email is to be sent to the Junk Email folder.

**Property ID:** 0x6101

**Data type:** **PtypInteger32**, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.5

**Alternate names:** PR\_JUNK\_THRESHOLD

## 2.762 PidTagKeyword

**Canonical name:** PidTagKeyword

**Description:** Contains a keyword that identifies the **mail user** to the mail user's system administrator.

**Property ID:** 0x3A0B

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.32

**Alternate names:** PR\_KEYWORD, PR\_KEYWORD\_A, PR\_KEYWORD\_W

## 2.763 PidTagLanguage

**Canonical name:** PidTagLanguage

**Description:** Contains a value that indicates the language in which the messaging user is writing messages.

**Property ID:** 0x3A0C

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.4

**Alternate names:** PR\_LANGUAGE, PR\_LANGUAGE\_A, PR\_LANGUAGE\_W, urn:schemas:contacts:language

## 2.764 PidTagLastModificationTime

**Canonical name:** PidTagLastModificationTime

**Description:** Contains the time, in **UTC**, of the last modification to the object.

**Property ID:** 0x3008

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.2

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_LAST\_MODIFICATION\_TIME, ptagLastModificationTime, urn:schemas:calendar:lastmodifiedtime, DAV:getlastmodified

## 2.765 PidTagLastModifierEntryId

**Canonical name:** PidTagLastModifierEntryId

**Description:** Specifies the Address Book **EntryID** of the last user to modify the contents of the message.

**Property ID:** 0x3FFB

**Data type:** PtypBinary, 0x0102

**Area:** History Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.32

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_LAST\_MODIFIER\_ENTRYID, ptagLastModifierEntryId

## 2.766 PidTagLastModifierName

**Canonical name:** PidTagLastModifierName

**Description:** Contains the name of the last **mail user** to change the **Message object**.

**Property ID:** 0x3FFA

**Data type:** PtypString, 0x001F

**Area:** History Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_LAST\_MODIFIER\_NAME, PR\_LAST\_MODIFIER\_NAME\_A, ptagLastModifierName, PR\_LAST\_MODIFIER\_NAME\_W

## 2.767 PidTagLastVerbExecuted

**Canonical name:** PidTagLastVerbExecuted

**Description:** Specifies the last verb executed for the message item to which it is related.

**Property ID:** 0x1081

**Data type:** PtypInteger32, 0x0003

**Area:** History Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.14

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_LAST\_VERB\_EXECUTED, ptagLastVerbExecuted

## 2.768 PidTagLastVerbExecutionTime

**Canonical name:** PidTagLastVerbExecutionTime

**Description:** Contains the date and time, in **UTC**, during which the operation represented in the **PidTagLastVerbExecuted** property (section [2.767](#)) took place.

**Property ID:** 0x1082

**Data type:** **PtypTime**, 0x0040

**Area:** History Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.15

**Consuming Reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_LAST\_VERB\_EXECUTION\_TIME, ptagLastVerbExecutionTime

## 2.769 PidTagListHelp

**Canonical name:** PidTagListHelp

**Description:** Contains a **URI** that provides detailed help information for the mailing list from which an email message was sent.

**Property ID:** 0x1043

**Data type:** **PtypString**, 0x001F

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.81

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_HELP, PR\_LIST\_HELP\_A, PR\_LIST\_HELP\_W

## 2.770 PidTagListSubscribe

**Canonical name:** PidTagListSubscribe

**Description:** Contains the **URI** that subscribes a **recipient** to a message's associated mailing list.

**Property ID:** 0x1044

**Data type:** **PtypString**, 0x001F

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.82

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_SUBSCRIBE, PR\_LIST\_SUBSCRIBE\_A, PR\_LIST\_SUBSCRIBE\_W

## 2.771 PidTagListUnsubscribe

**Canonical name:** PidTagListUnsubscribe

**Description:** Contains the **URI** that unsubscribes a **recipient** from a message's associated mailing list.

**Property ID:** 0x1045



**Data type:** PtypString, 0x001F

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.83

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_UNSUBSCRIBE, PR\_LIST\_UNSUBSCRIBE\_A, PR\_LIST\_UNSUBSCRIBE\_W

## 2.772 PidTagLocalCommitTime

**Canonical name:** PidTagLocalCommitTime

**Description:** Specifies the time, in **UTC**, that a **Message object** or **Folder object** was last changed.

**Property ID:** 0x6709

**Data type:** PtypTime, 0x0040

**Area:** Server

**Defining references:** [\[MS-OXCMSG\]](#) section 2.2.1.49; [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.13

**Alternate names:** PR\_LOCAL\_COMMIT\_TIME, ptagLocalCommitTime

## 2.773 PidTagLocalCommitTimeMax

**Canonical name:** PidTagLocalCommitTimeMax

**Description:** Contains the time of the most recent message change within the folder container, excluding messages changed within subfolders.

**Property ID:** 0x670A

**Data type:** PtypTime, 0x0040

**Area:** Server

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.14

**Consuming Reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_LOCAL\_COMMIT\_TIME\_MAX, ptagLocalCommitTimeMax

## 2.774 PidTagLocaleId

**Canonical name:** PidTagLocaleId

**Description:** Contains the **Logon object** LocaleID.

**Property ID:** 0x66A1

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.12

**Consuming references:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_LOCALE\_ID, ptagLocaleId

## 2.775 PidTagLocality

**Canonical name:** PidTagLocality

**Description:** Contains the name of the **mail user's** locality, such as the town or city.

**Property ID:** 0x3A27

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.16

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_LOCALITY, PR\_LOCALITY\_A, PR\_LOCALITY\_W, PR\_BUSINESS\_ADDRESS\_LOCALITY, PR\_BUSINESS\_ADDRESS\_LOCALITY\_A, PR\_BUSINESS\_ADDRESS\_LOCALITY\_W, urn:schemas:contacts:mailingcity

## 2.776 PidTagLocation

**Canonical name:** PidTagLocation

**Description:** Contains the location of the **mail user**.

**Property ID:** 0x3A0D

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.5

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_LOCATION, PR\_LOCATION\_A, PR\_LOCATION\_W, urn:schemas:contacts:location

## 2.777 PidTagMailboxOwnerEntryId

**Canonical name:** PidTagMailboxOwnerEntryId

**Description:** Contains the **EntryID** in the **Global Address List (GAL)** of the owner of the **mailbox**.

**Property ID:** 0x661B

**Data type:** PtypBinary, 0x0102

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.7

**Consuming references:** [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_MAILBOX\_OWNER\_ENTRYID, ptagMailboxOwnerEntryId

## 2.778 PidTagMailboxOwnerName

**Canonical name:** PidTagMailboxOwnerName

**Description:** Contains the **display name** of the owner of the **mailbox**.

**Property ID:** 0x661C

**Data type:** PtypString, 0x001F

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.8

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_MAILBOX\_OWNER\_NAME, PR\_MAILBOX\_OWNER\_NAME\_A, ptagMailboxOwnerName, PR\_MAILBOX\_OWNER\_NAME\_W

## 2.779 PidTagManagerName

**Canonical name:** PidTagManagerName

**Description:** Contains the name of the **mail user's** manager.

**Property ID:** 0x3A4E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.6

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_MANAGER\_NAME, PR\_MANAGER\_NAME\_A, PR\_MANAGER\_NAME\_W, urn:schemas:contacts:manager

## 2.780 PidTagMappingSignature

**Canonical name:** PidTagMappingSignature

**Description:** A 16-byte constant that is present on all **Address Book objects**, but is not present on objects in an offline address book.

**Property ID:** 0x0FF8

**Data type:** PtypBinary, 0x0102

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.32

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_MAPPING\_SIGNATURE, ptagMappingSignature

## 2.781 PidTagMaximumSubmitMessageSize

**Canonical name:** PidTagMaximumSubmitMessageSize

**Description:** Maximum size, in kilobytes, of a message that a user is allowed to submit for transmission to another user.

**Property ID:** 0x666D

**Data type:** **PtypInteger32**, 0x0003

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.2

**Alternate names:** PR\_MAX\_SUBMIT\_MESSAGE\_SIZE

## 2.782 PidTagMemberId

**Canonical name:** PidTagMemberId

**Description:** Contains a unique identifier that the messaging server generates for each user.

**Property ID:** 0x6671

**Data type:** **PtypInteger64**, 0x0014

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.5

**Alternate names:** PR\_MEMBER\_ID, ptagMemberId

## 2.783 PidTagMemberName

**Canonical name:** PidTagMemberName

**Description:** Contains the user-readable name of the user.

**Property ID:** 0x6672

**Data type:** **PtypString**, 0x001F

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.6

**Alternate names:** PR\_MEMBER\_NAME, PR\_MEMBER\_NAME\_A, ptagMemberName, PR\_MEMBER\_NAME\_W

## 2.784 PidTagMemberRights

**Canonical name:** PidTagMemberRights

**Description:** Contains the **permissions** for the specified user.

**Property ID:** 0x6673

**Data type:** **PtypInteger32**, 0x0003

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.7

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_MEMBER\_RIGHTS, ptagMemberRights

## 2.785 PidTagMessageAttachments

**Canonical name:** PidTagMessageAttachments

**Description:** Identifies all attachments to the current message.

**Property ID:** 0x0E13

**Data type:** PtypObject, 0x000D

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.52

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFCICS\]](#)

**Alternate names:** PR\_MESSAGE\_ATTACHMENTS, ptagMessageAttachments

## 2.786 PidTagMessageCcMe

**Canonical name:** PidTagMessageCcMe

**Description:** Indicates that the receiving **mailbox** owner is a **carbon copy (Cc) recipient** of this email message.

**Property ID:** 0x0058

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.18

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_CC\_ME, ptagMessageCcMe

## 2.787 PidTagMessageClass

**Canonical name:** PidTagMessageClass

**Description:** Denotes the specific type of the **Message object**.

**Property ID:** 0x001A

**Data type:** PtypString, 0x001F

**Area:** Common Property set

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCFCOLD\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCFCICS\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_MESSAGE\_CLASS, PR\_MESSAGE\_CLASS\_A, ptagMessageClass, PR\_MESSAGE\_CLASS\_W, <http://schemas.microsoft.com/exchange/outlookmessageclass><http://schemas.microsoft.com/exchange/outlookmessageclass>

## 2.788 PidTagMessageCodepage

**Canonical name:** PidTagMessageCodepage

**Description:** Specifies the code page used to encode the **non-Unicode** string properties on this **Message object**.

**Property ID:** 0x3FFD

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXTNEF\]](#) [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OPFOAB\]](#)

**Alternate names:** PR\_MESSAGE\_CODEPAGE

## 2.789 PidTagMessageDeliveryTime

**Canonical name:** PidTagMessageDeliveryTime

**Description:** Specifies the time (in **UTC**) when the server received the message.

**Property ID:** 0x0E06

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.9

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORSS\]](#)

**Alternate names:** PR\_MESSAGE\_DELIVERY\_TIME, urn:schemas:httpmail:datereceived

## 2.790 PidTagMessageEditorFormat

**Canonical name:** PidTagMessageEditorFormat

**Description:** Specifies the format that an email editor can use for editing the **message body**.

**Property ID:** 0x5909

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.78

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MSG\_EDITOR\_FORMAT, ptagMsgEditorFormat

## 2.791 PidTagMessageFlags

**Canonical name:** PidTagMessageFlags

**Description:** Specifies the status of the **Message object**.

**Property ID:** 0x0E07

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.6

**Consuming references:** [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#) [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_MESSAGE\_FLAGS, ptagMessageFlags

## 2.792 PidTagMessageHandlingSystemCommonName

**Canonical name:** PidTagMessageHandlingSystemCommonName

**Description:** Contains the **common name** of a messaging user for use in a message header.

**Property ID:** 0x3A0F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.33

**Alternate names:** PR\_MHS\_COMMON\_NAME, PR\_MHS\_COMMON\_NAME\_A, PR\_MHS\_COMMON\_NAME\_W, urn:schemas:contacts:dn

## 2.793 PidTagMessageLocaleId

**Canonical name:** PidTagMessageLocaleId

**Description:** Contains the Windows Locale ID of the end-user who created this message.

**Property ID:** 0x3FF1

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_LOCALE\_ID

## 2.794 PidTagMessageRecipientMe

**Canonical name:** PidTagMessageRecipientMe

**Description:** Indicates that the receiving **mailbox** owner is a primary or a **carbon copy (Cc) recipient** of this email message.

**Property ID:** 0x0059

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.19

**Consuming Reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_RECIP\_ME, ptagMessageRecipMe

## 2.795 PidTagMessageRecipients

**Canonical name:** PidTagMessageRecipients

**Description:** Identifies all of the **recipients** of the current message.

**Property ID:** 0x0E12

**Data type:** PtypObject, 0x000D

**Area:** Address Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.47

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_RECIPIENTS, ptagMessageRecipients

## 2.796 PidTagMessageSize

**Canonical name:** PidTagMessageSize

**Description:** Contains the size, in bytes, consumed by the **Message object** on the server.

**Property ID:** 0x0E08

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.10

**Consuming references:** [\[MS-OXCSTOR\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-XPFOAB\]](#)

**Alternate names:** PR\_MESSAGE\_SIZE, ptagMessageSize

## 2.797 PidTagMessageSizeExtended

**Canonical name:** PidTagMessageSizeExtended

**Description:** Specifies the 64-bit version of the **PidTagMessageSize** property (section [2.796](#)).



**Property ID:** 0x0E08

**Data type:** PtypInteger64, 0x0014

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCFOOLD\]](#) section 2.2.2.2.1.11

**Consuming reference:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_MESSAGE\_SIZE\_EXTENDED, ptagMessageSizeExtended

## 2.798 PidTagMessageStatus

**Canonical name:** PidTagMessageStatus

**Description:** Specifies the status of a message in a **contents table**.

**Property ID:** 0x0E17

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_MSG\_STATUS, ptagMsgStatus

## 2.799 PidTagMessageSubmissionId

**Canonical name:** PidTagMessageSubmissionId

**Description:** Contains a message identifier assigned by a message transfer agent.

**Property ID:** 0x0047

**Data type:** PtypBinary, 0x0102

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.79

**Consuming references:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_SUBMISSION\_ID, ptagMessageSubmissionId

## 2.800 PidTagMessageToMe

**Canonical name:** PidTagMessageToMe

**Description:** Indicates that the receiving **mailbox** owner is one of the **primary recipients** of this email message.

**Property ID:** 0x0057

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.17

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_TO\_ME, ptagMessageToMe

## 2.801 PidTagMid

**Canonical name:** PidTagMid

**Description:** Contains a value that contains the MID of the message currently being synchronized.

**Property ID:** 0x674A

**Data type:** **PtypInteger64**, 0x0014

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.1

**Consuming references:** [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** ptagMID, <http://schemas.microsoft.com/exchange/mid>

## 2.802 PidTagMiddleName

**Canonical name:** PidTagMiddleName

**Description:** Specifies the middle name(s) of the **contact**.

**Property ID:** 0x3A44

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.5

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_MIDDLE\_NAME, PR\_MIDDLE\_NAME\_A, PR\_MIDDLE\_NAME\_W, <urn:schemas:contacts:middlename>

## 2.803 PidTagMimeSkeleton

**Canonical name:** PidTagMimeSkeleton

**Description:** Contains the top-level **MIME** message headers, all MIME message **body part** headers, and body part content that is not already converted to **Message object** properties, including attachments.

**Property ID:** 0x64F0

**Data type:** **PtypBinary**, 0x0102

**Area:** MIME properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.28

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagMimeSkeleton

## 2.804 PidTagMobileTelephoneNumber

**Canonical name:** PidTagMobileTelephoneNumber

**Description:** Contains the **mail user's** cellular telephone number.

**Property ID:** 0x3A1C

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.27

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_MOBILE\_TELEPHONE\_NUMBER, PR\_MOBILE\_TELEPHONE\_NUMBER\_A, PR\_MOBILE\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:mobile

## 2.805 PidTagNativeBody

**Canonical name:** PidTagNativeBody

**Description:** Indicates the best available format for storing the **message body**.

**Property ID:** 0x1016

**Data type:** PtypInteger32, 0x0003

**Area:** BestBody

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.2

**Consuming Reference:** [\[MS-OXBBODY\]](#)

**Alternate names:** PR\_NATIVE\_BODY\_INFO, ptagNativeBodyInfo

## 2.806 PidTagNextSendAcct

**Canonical name:** PidTagNextSendAcct

**Description:** Specifies the server that a client is currently attempting to use to send email.

**Property ID:** 0x0E29

**Data type:** PtypString, 0x001F

**Area:** Outlook Application

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.65

**Consuming Reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_NEXT\_SEND\_ACCT

## 2.807 PidTagNickname

**Canonical name:** PidTagNickname

**Description:** Contains the **mail user's** nickname.

**Property ID:** 0x3A4F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.1

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_NICKNAME, PR\_NICKNAME\_A, PR\_NICKNAME\_W,  
urn:schemas:contacts:nickname

## 2.808 PidTagNonDeliveryReportDiagCode

**Canonical name:** PidTagNonDeliveryReportDiagCode

**Description:** Contains the diagnostic code for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C05

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.30

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_NDR\_DIAG\_CODE, ptagNonDeliveryDiagCode

## 2.809 PidTagNonDeliveryReportReasonCode

**Canonical name:** PidTagNonDeliveryReportReasonCode

**Description:** Contains an integer value that indicates a reason for delivery failure.

**Property ID:** 0x0C04

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.31

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_NDR\_REASON\_CODE, ptagNDRReasonCode

## 2.810 PidTagNonDeliveryReportStatusCode

**Canonical name:** PidTagNonDeliveryReportStatusCode

**Description:** Contains the value of the Status field for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C20

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.32

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_NDR\_STATUS\_CODE, ptagNDRStatusCode

### 2.811 PidTagNonReceiptNotificationRequested

**Canonical Name:** PidTagNonReceiptNotificationRequested

**Description:** Specifies whether the client sends a non-read receipt.

**Property ID:** 0x0C06

**Data type:** PtypBoolean, 0x000B

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.31

**Alternate names:** PR\_NON\_RECEIPT\_NOTIFICATION\_REQUESTED

### 2.812 PidTagNormalizedSubject

**Canonical name:** PidTagNormalizedSubject

**Description:** Contains the normalized subject of the message.

**Property ID:** 0x0E1D

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.10

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_NORMALIZED\_SUBJECT, PR\_NORMALIZED\_SUBJECT\_A, ptagNormalizedSubject, PR\_NORMALIZED\_SUBJECT\_W, urn:schemas:httpmail:normalizedsubject

### 2.813 PidTagObjectType

**Canonical name:** PidTagObjectType

**Description:** Indicates the type of **Server object**.

**Property ID:** 0x0FFE

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.7

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_OBJECT\_TYPE, ptagObjectType

## 2.814 PidTagOfficeLocation

**Canonical name:** PidTagOfficeLocation

**Description:** Contains the **mail user's** office location.

**Property ID:** 0x3A19

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.5

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_OFFICE\_LOCATION, PR\_OFFICE\_LOCATION\_A, PR\_OFFICE\_LOCATION\_W, urn:schemas:contacts:roomnumber

## 2.815 PidTagOfflineAddressBookContainerGuid

**Canonical name:** PidTagOfflineAddressBookContainerGuid

**Description:** A string-formatted **GUID** that represents the **address list** container object.

**Property ID:** 0x6802

**Data type:** PtypString8, 0x001E

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.1

**Alternate names:** PR\_OAB\_CONTAINER\_GUID, PR\_OAB\_CONTAINER\_GUID\_W

## 2.816 PidTagOfflineAddressBookDistinguishedName

**Canonical name:** PidTagOfflineAddressBookDistinguishedName

**Description:** Contains the **DN** of the **address list** that is contained in the OAB message.

**Property ID:** 0x6804

**Data type:** PtypString8, 0x001E

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.2

**Alternate names:** PR\_OAB\_DN, PR\_OAB\_DN\_W

## 2.817 PidTagOfflineAddressBookMessageClass

**Canonical name:** PidTagOfflineAddressBookMessageClass

**Description:** Contains the **message class** for full OAB messages.

**Property ID:** 0x6803

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXPFOAB\]](#) section 2.2.2.1.1

**Alternate names:** PR\_OAB\_MESSAGE\_CLASS

## 2.818 PidTagOfflineAddressBookName

**Canonical name:** PidTagOfflineAddressBookName

**Description:** Contains the **display name** of the **address list**.

**Property ID:** 0x6800

**Data type:** PtypString, 0x001F

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.3

**Alternate names:** PR\_OAB\_NAME, PR\_OAB\_NAME\_W

## 2.819 PidTagOfflineAddressBookSequence

**Canonical name:** PidTagOfflineAddressBookSequence

**Description:** Contains the sequence number of the OAB.

**Property ID:** 0x6801

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.4

**Alternate names:** PR\_OAB\_SEQUENCE

## 2.820 PidTagOfflineAddressBookTruncatedProperties

**Canonical name:** PidTagOfflineAddressBookTruncatedProperties

**Description:** Contains a list of the property tags that have been truncated or limited by the server.

**Property ID:** 0x6805

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.9.2.2

**Alternate names:** PR\_OAB\_TRUNCATED\_PROPS

## 2.821 PidTagOrdinalMost

**Canonical name:** PidTagOrdinalMost

**Description:** Contains a positive number whose negative is less than or equal to the value of the **PidLidTaskOrdinal** property (section [2.327](#)) of all of the **Task objects** in the folder.

**Property ID:** 0x36E2

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.1.1

**Alternate names:** PR\_ORDINAL\_MOST

## 2.822 PidTagOrganizationalIdNumber

**Canonical name:** PidTagOrganizationalIdNumber

**Description:** Contains an identifier for the **mail user** used within the mail user's organization.

**Property ID:** 0x3A10

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.7

**Alternate names:** PR\_ORGANIZATIONAL\_ID\_NUMBER, PR\_ORGANIZATIONAL\_ID\_NUMBER\_A, PR\_ORGANIZATIONAL\_ID\_NUMBER\_W, urn:schemas:contacts:employeenumber

## 2.823 PidTagOriginalAuthorEntryId

**Canonical name:** PidTagOriginalAuthorEntryId

**Description:** Contains an address book **EntryID** structure ([\[MS-OXCDATA\]](#) section 2.2.5.2) and is defined in report messages to identify the user who sent the original message.

**Property ID:** 0x004C

**Data type:** PtypBinary, 0x0102

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.32

**Alternate names:** PR\_ORIGINAL\_AUTHOR\_ENTRYID

## 2.824 PidTagOriginalAuthorName

**Canonical name:** PidTagOriginalAuthorName

**Description:** Contains the display name of the sender of the original message referenced by a report message.



**Property ID:** 0x004D

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.33

**Alternate names:** PR\_ORIGINAL\_AUTHOR\_NAME\_W

## 2.825 PidTagOriginalDeliveryTime

**Canonical name:** PidTagOriginalDeliveryTime

**Description:** Contains the delivery time, in **UTC**, from the original message.

**Property ID:** 0x0055

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.2

**Alternate names:** PR\_ORIGINAL\_DELIVERY\_TIME, ptagOriginalDeliveryTime

## 2.826 PidTagOriginalDisplayBcc

**Canonical name:** PidTagOriginalDisplayBcc

**Description:** Contains the value of the **PidTagDisplayBcc** property (section [2.674](#)) from the original message.

**Property ID:** 0x0072

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.5

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_BCC, PR\_ORIGINAL\_DISPLAY\_BCC\_A, ptagOriginalDisplayBcc, PR\_ORIGINAL\_DISPLAY\_BCC\_W, <http://schemas.microsoft.com/exchange/originaldisplaybcc>

## 2.827 PidTagOriginalDisplayCc

**Canonical name:** PidTagOriginalDisplayCc

**Description:** Contains the value of the **PidTagDisplayCc** property (section [2.675](#)) from the original message.

**Property ID:** 0x0073

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.4

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_CC, PR\_ORIGINAL\_DISPLAY\_CC\_A, ptagOriginalDisplayCc, PR\_ORIGINAL\_DISPLAY\_CC\_W, <http://schemas.microsoft.com/exchange/originaldisplaycc>, [http://schemas.microsoft.com/mapi/original\\_display\\_cc](http://schemas.microsoft.com/mapi/original_display_cc)

## 2.828 PidTagOriginalDisplayTo

**Canonical name:** PidTagOriginalDisplayTo

**Description:** Contains the value of the **PidTagDisplayTo** property (section [2.678](#)) from the original message.

**Property ID:** 0x0074

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.3

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_TO, PR\_ORIGINAL\_DISPLAY\_TO\_A, ptagOriginalDisplayTo, PR\_ORIGINAL\_DISPLAY\_TO\_W, <http://schemas.microsoft.com/exchange/originaldisplayto>, [http://schemas.microsoft.com/mapi/original\\_display\\_to](http://schemas.microsoft.com/mapi/original_display_to)

## 2.829 PidTagOriginalEntryId

**Canonical name:** PidTagOriginalEntryId

**Description:** Contains the original **EntryID** of an object.

**Property ID:** 0x3A12

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.9

**Alternate names:** PR\_ORIGINAL\_ENTRYID, ptagOriginalEntryId

## 2.830 PidTagOriginalMessageClass

**Canonical name:** PidTagOriginalMessageClass

**Description:** Designates the **PidTagMessageClass** property ([\[MS-OXCMSG\]](#) section 2.2.1.3) from the original message.

**Property ID:** 0x004B

**Data type:** PtypString, 0x001F

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.86

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ORIG\_MESSAGE\_CLASS, PR\_ORIG\_MESSAGE\_CLASS\_A, PR\_ORIG\_MESSAGE\_CLASS\_W

## 2.831 PidTagOriginalMessageId

**Canonical name:** PidTagOriginalMessageId

**Description:** Contains the message ID of the original message included in replies or resent messages.

**Property ID:** 0x1046

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.85

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagOriginalInternetMessageID, OriginalMessageId

## 2.832 PidTagOriginalSenderAddressType

**Canonical name:** PidTagOriginalSenderAddressType

**Description:** Contains the value of the original message sender's **PidTagSenderAddressType** property (section [2.1000](#)).

**Property ID:** 0x0066

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.6

**Alternate names:** PR\_ORIGINAL\_SENDER\_ADDRTYPE, PR\_ORIGINAL\_SENDER\_ADDRTYPE\_A, ptagOriginalSenderAddrType, PR\_ORIGINAL\_SENDER\_ADDRTYPE\_W

## 2.833 PidTagOriginalSenderEmailAddress

**Canonical name:** PidTagOriginalSenderEmailAddress

**Description:** Contains the value of the original message sender's **PidTagSenderEmailAddress** property (section [2.1001](#)).

**Property ID:** 0x0067

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.7

**Alternate names:** PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS, PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS\_A, PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS\_W

## 2.834 PidTagOriginalSenderEntryId

**Canonical name:** PidTagOriginalSenderEntryId

**Description:** Contains an address book **EntryID** that is set on delivery report messages.

**Property ID:** 0x005B

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.8

**Alternate names:** PR\_ORIGINAL\_SENDER\_ENTRYID, ptagOriginalSenderId

## 2.835 PidTagOriginalSenderName

**Canonical name:** PidTagOriginalSenderName

**Description:** Contains the value of the original message sender's **PidTagSenderName** property (section [2.1004](#)), and is set on delivery report messages.

**Property ID:** 0x005A

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.9

**Alternate names:** PR\_ORIGINAL\_SENDER\_NAME, PR\_ORIGINAL\_SENDER\_NAME\_A, ptagOriginalSenderName, PR\_ORIGINAL\_SENDER\_NAME\_W, <http://schemas.microsoft.com/exchange/originalsendername>

## 2.836 PidTagOriginalSenderSearchKey

**Canonical name:** PidTagOriginalSenderSearchKey

**Description:** Contains an address book search key set on the original email message.

**Property ID:** 0x005C

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.10

**Alternate names:** PR\_ORIGINAL\_SENDER\_SEARCH\_KEY, ptagOriginalSenderSearchKey

## 2.837 PidTagOriginalSensitivity

**Canonical name:** PidTagOriginalSensitivity

**Description:** Contains the sensitivity value of the original email message.

**Property ID:** 0x002E

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.22

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_ORIGINAL\_SENSITIVITY, ptagOriginalSensitivity

### 2.838 PidTagOriginalSentRepresentingAddressType

**Canonical name:** PidTagOriginalSentRepresentingAddressType

**Description:** Contains the **address type** of the end user who is represented by the original email message sender.

**Property ID:** 0x0068

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.11

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE, PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE\_A, ptagOriginalSentRepresentingAddrType, PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE\_W

### 2.839 PidTagOriginalSentRepresentingEmailAddress

**Canonical name:** PidTagOriginalSentRepresentingEmailAddress

**Description:** Contains the email address of the end user who is represented by the original email message sender.

**Property ID:** 0x0069

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.12

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS, PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_W

### 2.840 PidTagOriginalSentRepresentingEntryId

**Canonical name:** PidTagOriginalSentRepresentingEntryId

**Description:** Identifies an address book **EntryID** that contains the entry identifier of the end user who is represented by the original message sender.

**Property ID:** 0x005E

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.13

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_ENTRYID, ptagOriginalSentRepresentingEntryId

## 2.841 PidTagOriginalSentRepresentingName

**Canonical name:** PidTagOriginalSentRepresentingName

**Description:** Contains the **display name** of the end user who is represented by the original email message sender.

**Property ID:** 0x005D

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.14

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME, PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME\_A, ptagOriginalSentRepresentingName, PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME\_W

## 2.842 PidTagOriginalSentRepresentingSearchKey

**Canonical name:** PidTagOriginalSentRepresentingSearchKey

**Description:** Identifies an address book search key that contains the SearchKey of the end user who is represented by the original message sender.

**Property ID:** 0x005F

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.15

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_SEARCH\_KEY, ptagOriginalSentRepresentingSearchKey

## 2.843 PidTagOriginalSubject

**Canonical name:** PidTagOriginalSubject

**Description:** Specifies the subject of the original message.

**Property ID:** 0x0049

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.16

**Alternate names:** PR\_ORIGINAL\_SUBJECT, PR\_ORIGINAL\_SUBJECT\_A, ptagOriginalSubject, PR\_ORIGINAL\_SUBJECT\_W, <http://schemas.microsoft.com/exchange/originalsubject>, [http://schemas.microsoft.com/mapi/original\\_subject](http://schemas.microsoft.com/mapi/original_subject)

## 2.844 PidTagOriginalSubmitTime

**Canonical name:** PidTagOriginalSubmitTime

**Description:** Specifies the original email message's submission date and time, in **UTC**.

**Property ID:** 0x004E

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.17

**Alternate names:** PR\_ORIGINAL\_SUBMIT\_TIME, ptagOriginalSubmitTime,  
<http://schemas.microsoft.com/exchange/originaldate>,  
[http://schemas.microsoft.com/mapi/original\\_submit\\_time](http://schemas.microsoft.com/mapi/original_submit_time)

## 2.845 PidTagOriginatorDeliveryReportRequested

**Canonical name:** PidTagOriginatorDeliveryReportRequested

**Description:** Indicates whether an email sender requests an email **delivery receipt** from the messaging system.

**Property ID:** 0x0023

**Data type:** PtypBoolean, 0x000B

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.20

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ORIGINATOR\_DELIVERY\_REPORT\_REQUESTED,  
<http://schemas.microsoft.com/exchange/deliveryreportrequested>

## 2.846 PidTagOriginatorNonDeliveryReportRequested

**Canonical name:** PidTagOriginatorNonDeliveryReportRequested

**Description:** Specifies whether an email sender requests suppression of nondelivery receipts.

**Property ID:** 0x0C08

**Data type:** PtypBoolean, 0x000B

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.21

**Alternate names:** PR\_ORIGINATOR\_NON\_DELIVERY\_REPORT\_REQUESTED

## 2.847 PidTagOscSyncEnabled

**Canonical name:** PidTagOscSyncEnabled

**Description:** Specifies whether **contact** synchronization with an external source is handled by the server.

**Property ID:** 0x7C24

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.7

**Alternate names:** PR\_OSC\_SYNC\_ENABLEDONSERVER

### 2.848 PidTagOtherAddressCity

**Canonical name:** PidTagOtherAddressCity

**Description:** Contains the name of the **mail user's** other locality, such as the town or city.

**Property ID:** 0x3A5F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_CITY, PR\_OTHER\_ADDRESS\_CITY\_A, PR\_OTHER\_ADDRESS\_CITY\_W, urn:schemas:contacts:othercity

### 2.849 PidTagOtherAddressCountry

**Canonical name:** PidTagOtherAddressCountry

**Description:** Contains the name of the **mail user's** other country/region.

**Property ID:** 0x3A60

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_COUNTRY, PR\_OTHER\_ADDRESS\_COUNTRY\_A, PR\_OTHER\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:othercountry

### 2.850 PidTagOtherAddressPostalCode

**Canonical name:** PidTagOtherAddressPostalCode

**Description:** Contains the postal code for the **mail user's** other postal address.

**Property ID:** 0x3A61

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

**Consuming references:** [\[MS-OXVCARD\]](#)



**Alternate names:** PR\_OTHER\_ADDRESS\_POSTAL\_CODE, PR\_OTHER\_ADDRESS\_POSTAL\_CODE\_A, PR\_OTHER\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:otherpostalcode

## 2.851 PidTagOtherAddressPostOfficeBox

**Canonical name:** PidTagOtherAddressPostOfficeBox

**Description:** Contains the number or identifier of the **mail user's** other post office box.

**Property ID:** 0x3A64

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX, PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:otherpostofficebox

## 2.852 PidTagOtherAddressStateOrProvince

**Canonical name:** PidTagOtherAddressStateOrProvince

**Description:** Contains the name of the **mail user's** other state or province.

**Property ID:** 0x3A62

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:otherstate

## 2.853 PidTagOtherAddressStreet

**Canonical name:** PidTagOtherAddressStreet

**Description:** Contains the **mail user's** other street address.

**Property ID:** 0x3A63

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.1

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_STREET, PR\_OTHER\_ADDRESS\_STREET\_A, PR\_OTHER\_ADDRESS\_STREET\_W, urn:schemas:contacts:otherstreet

## 2.854 PidTagOtherTelephoneNumber

**Canonical name:** PidTagOtherTelephoneNumber

**Description:** Contains an alternate telephone number for the **mail user**.

**Property ID:** 0x3A1F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.10

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_TELEPHONE\_NUMBER, PR\_OTHER\_TELEPHONE\_NUMBER\_A, PR\_OTHER\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:otherTelephone

## 2.855 PidTagOutOfOfficeState

**Canonical name:** PidTagOutOfOfficeState

**Description:** Indicates whether the user is **OOF**.

**Property ID:** 0x661D

**Data type:** PtypBoolean, 0x000B

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.2.4

**Alternate names:** PR\_OOF\_STATE, ptagOOFSate

## 2.856 PidTagOwnerAppointmentId

**Canonical name:** PidTagOwnerAppointmentId

**Description:** Specifies a quasi-unique value among all of the **Calendar objects** in a user's **mailbox**.

**Property ID:** 0x0062

**Data type:** PtypInteger32, 0x0003

**Area:** Appointment

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.29

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_OWNER\_APPT\_ID, http://schemas.microsoft.com/mapi/owner\_appt\_id

## 2.857 PidTagPagerTelephoneNumber

**Canonical name:** PidTagPagerTelephoneNumber

**Description:** Contains the **mail user's** pager telephone number.

**Property ID:** 0x3A21

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.28

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PAGER\_TELEPHONE\_NUMBER, PR\_PAGER\_TELEPHONE\_NUMBER\_A, PR\_PAGER\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:pager

## 2.858 PidTagParentEntryId

**Canonical name:** PidTagParentEntryId

**Description:** Contains the **EntryID** of the folder where messages or subfolders reside.

**Property ID:** 0x0E09

**Data type:** **PtypBinary**, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.7

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_PARENT\_ENTRYID, ptagParentEntryId

## 2.859 PidTagParentFolderId

**Canonical name:** PidTagParentFolderId

**Description:** Contains a value that contains the Folder ID (FID), as specified in [\[MS-OXCDATA\]](#) section 2.2.1.1, that identifies the parent folder of the **messaging object** being synchronized.

**Property ID:** 0x6749

**Data type:** **PtypInteger64**, 0x0014

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.4

**Alternate names:** ptagParentFID

## 2.860 PidTagParentKey

**Canonical name:** PidTagParentKey

**Description:** Contains the search key that is used to correlate the original message and the reports about the original message.

**Property ID:** 0x0025

**Data type:** **PtypBinary**, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.18

**Alternate names:** PR\_PARENT\_KEY, ptagParentKey

### 2.861 PidTagParentSourceKey

**Canonical name:** PidTagParentSourceKey

**Description:** Contains a value on a folder that contains the **PidTagSourceKey** property (section [2.1022](#)) of the parent folder.

**Property ID:** 0x65E1

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.6

**Alternate names:** PR\_PARENT\_SOURCE\_KEY

### 2.862 PidTagPersonalHomePage

**Canonical name:** PidTagPersonalHomePage

**Description:** Contains the **URL** of the **mail user's** personal home page.

**Property ID:** 0x3A50

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.13

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PERSONAL\_HOME\_PAGE, PR\_PERSONAL\_HOME\_PAGE\_A, PR\_PERSONAL\_HOME\_PAGE\_W, urn:schemas:contacts:personalHomePage

### 2.863 PidTagPolicyTag

**Canonical name:** PidTagPolicyTag

**Description:** Specifies the **GUID** of a **retention tag**.

**Property ID:** 0x3019

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.2

**Alternate names:** PR\_POLICY\_TAG, ptagPolicyTag

## 2.864 PidTagPostalAddress

**Canonical name:** PidTagPostalAddress

**Description:** Contains the **mail user's** postal address.

**Property ID:** 0x3A15

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** PR\_POSTAL\_ADDRESS, PR\_POSTAL\_ADDRESS\_A, PR\_POSTAL\_ADDRESS\_W, urn:schemas:contacts:mailingpostaladdress

## 2.865 PidTagPostalCode

**Canonical name:** PidTagPostalCode

**Description:** Contains the postal code for the **mail user's** postal address.

**Property ID:** 0x3A2A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.18

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_POSTAL\_CODE, PR\_POSTAL\_CODE\_A, PR\_POSTAL\_CODE\_W, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE\_A, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:mailingpostalcode

## 2.866 PidTagPostOfficeBox

**Canonical name:** PidTagPostOfficeBox

**Description:** Contains the number or identifier of the **mail user's** post office box.

**Property ID:** 0x3A2B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.15

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_POST\_OFFICE\_BOX, PR\_POST\_OFFICE\_BOX\_A, PR\_POST\_OFFICE\_BOX\_W, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:mailingpostofficebox

## 2.867 PidTagPredecessorChangeList

**Canonical name:** PidTagPredecessorChangeList

**Description:** Contains a value that contains a serialized representation of a **PredecessorChangeList** structure.

**Property ID:** 0x65E3

**Data type:** **PtypBinary**, 0x0102

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.8

**Alternate names:** PR\_PREDECESSOR\_CHANGE\_LIST

## 2.868 PidTagPrimaryFaxNumber

**Canonical name:** PidTagPrimaryFaxNumber

**Description:** Contains the telephone number of the **mail user's** primary fax machine.

**Property ID:** 0x3A23

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.29

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_PRIMARY\_FAX\_NUMBER, PR\_PRIMARY\_FAX\_NUMBER\_A, PR\_PRIMARY\_FAX\_NUMBER\_W, urn:schemas:contacts:otherfax

## 2.869 PidTagPrimarySendAccount

**Canonical name:** PidTagPrimarySendAccount

**Description:** Specifies the first server that a client is to use to send the email with.

**Property ID:** 0x0E28

**Data type:** **PtypString**, 0x001F

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.64

**Alternate names:** PR\_PRIMARY\_SEND\_ACCT

## 2.870 PidTagPrimaryTelephoneNumber

**Canonical name:** PidTagPrimaryTelephoneNumber

**Description:** Contains the **mail user's** primary telephone number.

**Property ID:** 0x3A1A

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.5

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PRIMARY\_TELEPHONE\_NUMBER, PR\_PRIMARY\_TELEPHONE\_NUMBER\_A, PR\_PRIMARY\_TELEPHONE\_NUMBER\_W

## 2.871 PidTagPriority

**Canonical name:** PidTagPriority

**Description:** Indicates the client's request for the priority with which the message is to be sent by the messaging system.

**Property ID:** 0x0026

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOJRNL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_PRIORITY, ptagPriority, urn:schemas:httpmail:priority, urn:schemas:httpmail:priority

## 2.872 PidTagProcessed

**Canonical name:** PidTagProcessed

**Description:** Indicates whether a client has already processed a received task communication.

**Property ID:** 0x7D01

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_PROCESSED

## 2.873 PidTagProfession

**Canonical name:** PidTagProfession

**Description:** Contains the name of the **mail user's** line of business.

**Property ID:** 0x3A46

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.9

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PROFESSION, PR\_PROFESSION\_A, PR\_PROFESSION\_W,  
urn:schemas:contacts:profession

## 2.874 PidTagProhibitReceiveQuota

**Canonical name:** PidTagProhibitReceiveQuota

**Description:** Maximum size, in kilobytes, that a user is allowed to accumulate in their **mailbox** before no further email will be delivered to their mailbox.

**Property ID:** 0x666A

**Data type:** PtypInteger32, 0x0003

**Area:** Exchange Administrative

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.3

**Alternate names:** PR\_PROHIBIT\_RECEIVE\_QUOTA, ptagProhibitReceiveQuota

## 2.875 PidTagProhibitSendQuota

**Canonical name:** PidTagProhibitSendQuota

**Description:** Maximum size, in kilobytes, that a user is allowed to accumulate in their **mailbox** before the user can no longer send any more email.

**Property ID:** 0x666E

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.4

**Alternate names:** PR\_PROHIBIT\_SEND\_QUOTA, ptagProhibitSendQuota

## 2.876 PidTagPurportedSenderDomain

**Canonical name:** PidTagPurportedSenderDomain

**Description:** Contains the **domain** responsible for transmitting the current message.

**Property ID:** 0x4083

**Data type:** PtypString, 0x001F

**Area:** TransportEnvelope

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.43

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_PURPORTED\_SENDER\_DOMAIN

## 2.877 PidTagRadioTelephoneNumber

**Canonical name:** PidTagRadioTelephoneNumber

**Description:** Contains the **mail user's** radio telephone number.



**Property ID:** 0x3A1D

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.8

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_RADIO\_TELEPHONE\_NUMBER, PR\_RADIO\_TELEPHONE\_NUMBER\_A, PR\_RADIO\_TELEPHONE\_NUMBER\_W

## 2.878 PidTagRead

**Canonical name:** PidTagRead

**Description:** Indicates whether a message has been read.

**Property ID:** 0x0E69

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable Property set

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.53

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_READ, ptagRead, urn:schemas:httpmail:read

## 2.879 PidTagReadReceiptAddressType

**Canonical name:** PidTagReadReceiptAddressType

**Description:** Contains the **address type** of the end user to whom a **read receipt** is directed.

**Property ID:** 0x4029

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.24

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptAddrType, ReadReceiptAddrType

## 2.880 PidTagReadReceiptEmailAddress

**Canonical name:** PidTagReadReceiptEmailAddress

**Description:** Contains the email address of the end user to whom a **read receipt** is directed.

**Property ID:** 0x402A

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.25

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptEmailAddr, ReadReceiptEmailAddress

### 2.881 PidTagReadReceiptEntryId

**Canonical name:** PidTagReadReceiptEntryId

**Description:** Contains an address book **EntryID**.

**Property ID:** 0x0046

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.26

**Alternate names:** PR\_READ\_RECEIPT\_ENTRYID, ptagReadReceiptEntryId

### 2.882 PidTagReadReceiptName

**Canonical name:** PidTagReadReceiptName

**Description:** Contains the **display name** for the end user to whom a **read receipt** is directed.

**Property ID:** 0x402B

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.27

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptDisplayName, ReadReceiptDisplayName

### 2.883 PidTagReadReceiptRequested

**Canonical name:** PidTagReadReceiptRequested

**Description:** Specifies whether the email sender requests a **read receipt** from all **recipients** when this email message is read or opened.

**Property ID:** 0x0029

**Data type:** PtypBoolean, 0x000B

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.29

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** PR\_READ\_RECEIPT\_REQUESTED, ptagReadReceiptRequested, <http://schemas.microsoft.com/exchange/readreceiptrequested>

## 2.884 PidTagReadReceiptSearchKey

**Canonical name:** PidTagReadReceiptSearchKey

**Description:** Contains an address book search key.

**Property ID:** 0x0053

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.28

**Alternate names:** PR\_READ\_RECEIPT\_SEARCH\_KEY, ptagReadReceiptSearchKey

## 2.885 PidTagReadReceiptSmtpAddress

**Canonical name:** PidTagReadReceiptSmtpAddress

**Description:** Contains the SMTP email address of the user to whom a read receipt is directed.

**Property ID:** 0x5D05

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.30

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientReadReceiptSmtpAddress

## 2.886 PidTagReceiptTime

**Canonical name:** PidTagReceiptTime

**Description:** Contains the sent time for a message disposition notification, as specified in [\[RFC3798\]](#).

**Property ID:** 0x002A

**Data type:** PtypTime, 0x0040

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.33

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_RECEIPT\_TIME, ptagReceiptTime

## 2.887 PidTagReceivedByAddressType

**Canonical name:** PidTagReceivedByAddressType

**Description:** Contains the email message receiver's email **address type**.

**Property ID:** 0x0075

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.36

**Alternate names:** PR\_RECEIVED\_BY\_ADDRTYPE, PR\_RECEIVED\_BY\_ADDRTYPE\_A, ptagReceivedByAddrType, PR\_RECEIVED\_BY\_ADDRTYPE\_W

## 2.888 PidTagReceivedByEmailAddress

**Canonical name:** PidTagReceivedByEmailAddress

**Description:** Contains the email message receiver's email address.

**Property ID:** 0x0076

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.37

**Alternate names:** PR\_RECEIVED\_BY\_EMAIL\_ADDRESS, PR\_RECEIVED\_BY\_EMAIL\_ADDRESS\_A, PR\_RECEIVED\_BY\_EMAIL\_ADDRESS\_W

## 2.889 PidTagReceivedByEntryId

**Canonical name:** PidTagReceivedByEntryId

**Description:** Contains the address book **EntryID** of the **mailbox** receiving the **Email object**.

**Property ID:** 0x003F

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.38

**Alternate names:** PR\_RECEIVED\_BY\_ENTRYID

## 2.890 PidTagReceivedByName

**Canonical name:** PidTagReceivedByName

**Description:** Contains the email message receiver's **display name**.

**Property ID:** 0x0040

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.39

**Alternate names:** PR\_RECEIVED\_BY\_NAME, PR\_RECEIVED\_BY\_NAME\_A, PR\_RECEIVED\_BY\_NAME\_W

## 2.891 PidTagReceivedBySearchKey

**Canonical name:** PidTagReceivedBySearchKey

**Description:** Identifies an address book search key that contains a binary-comparable key that is used to identify correlated objects for a search.

**Property ID:** 0x0051

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.40

**Alternate names:** PR\_RECEIVED\_BY\_SEARCH\_KEY

## 2.892 PidTagReceivedBySmtpAddress

**Canonical name:** PidTagReceivedBySmtpAddress

**Description:** Contains the email message receiver's SMTP email address.

**Property ID:** 0x5D07

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.41

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientRcvdBySmtpAddress

## 2.893 PidTagReceivedRepresentingAddressType

**Canonical name:** PidTagReceivedRepresentingAddressType

**Description:** Contains the email **address type** for the end user represented by the receiving **mailbox** owner.

**Property ID:** 0x0077

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.23

**Alternate names:** PR\_RCVD\_REPRESENTING\_ADDRTYPE, PR\_RCVD\_REPRESENTING\_ADDRTYPE\_A, ptagRcvdRepresentingAddrType, PR\_RCVD\_REPRESENTING\_ADDRTYPE\_W

## 2.894 PidTagReceivedRepresentingEmailAddress

**Canonical name:** PidTagReceivedRepresentingEmailAddress

**Description:** Contains the email address for the end user represented by the receiving **mailbox** owner.

**Property ID:** 0x0078

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.24

**Alternate names:** PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS, PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS\_W

## 2.895 PidTagReceivedRepresentingEntryId

**Canonical name:** PidTagReceivedRepresentingEntryId

**Description:** Contains an address book **EntryID** that identifies the end user represented by the receiving **mailbox** owner.

**Property ID:** 0x0043

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.25

**Alternate names:** PR\_RCVD\_REPRESENTING\_ENTRYID, ptagRcvdRepresentingEntryId

## 2.896 PidTagReceivedRepresentingName

**Canonical name:** PidTagReceivedRepresentingName

**Description:** Contains the **display name** for the end user represented by the receiving **mailbox** owner.

**Property ID:** 0x0044

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.26

**Alternate names:** PR\_RCVD\_REPRESENTING\_NAME, PR\_RCVD\_REPRESENTING\_NAME\_A, ptagRcvdRepresentingName, PR\_RCVD\_REPRESENTING\_NAME\_W

## 2.897 PidTagReceivedRepresentingSearchKey

**Canonical name:** PidTagReceivedRepresentingSearchKey

**Description:** Identifies an address book search key that contains a binary-comparable key of the end user represented by the receiving **mailbox** owner.

**Property ID:** 0x0052

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.27

**Alternate names:** PR\_RCVD\_REPRESENTING\_SEARCH\_KEY, ptagRcvdRepresentingSearchKey

## 2.898 PidTagReceivedRepresentingSmtpAddress

**Canonical name:** PidTagReceivedRepresentingSmtpAddress

**Description:** Contains the SMTP email address of the user represented by the receiving mailbox owner.

**Property ID:** 0x5D08

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.28

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientRcvdRepresentingSmtpAddress

## 2.899 PidTagRecipientDisplayName

**Canonical name:** PidTagRecipientDisplayName

**Description:** Specifies the display name of the **recipient**.

**Property ID:** 0x5FF6

**Data type:** PtypString, 0x001F

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.54

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_DISPLAY\_NAME, PR\_RECIPIENT\_DISPLAY\_NAME\_W

## 2.900 PidTagRecipientEntryId

**Canonical name:** PidTagRecipientEntryId

**Description:** Identifies an **Address Book object** that specifies the **recipient**.

**Property ID:** 0x5FF7

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.55

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_ENTRYID, ptagRecipientEntryId

## 2.901 PidTagRecipientFlags

**Canonical name:** PidTagRecipientFlags

**Description:** Specifies a bit field that describes the **recipient** status.

**Property ID:** 0x5FFD

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_FLAGS

## 2.902 PidTagRecipientOrder

**Canonical name:** PidTagRecipientOrder

**Description:** Specifies the location of the current **recipient** in the **recipient table**.

**Property ID:** 0x5FDF

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.40

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_ORDER, ptagRecipientOrder

## 2.903 PidTagRecipientProposed

**Canonical name:** PidTagRecipientProposed

**Description:** Indicates that the attendee proposed a new date and/or time.

**Property ID:** 0x5FE1

**Data type:** PtypBoolean, 0x000B

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.4

**Alternate names:** PR\_RECIPIENT\_PROPOSED, ptagRecipientProposed

## 2.904 PidTagRecipientProposedEndTime

**Canonical name:** PidTagRecipientProposedEndTime

**Description:** Indicates the **meeting** end time requested by the attendee in a **counter proposal**.

**Property ID:** 0x5FE4

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.6

**Alternate names:** PR\_RECIPIENT\_PROPOSEDENDTIME, ptagRecipientProposedEndTime



## 2.905 PidTagRecipientProposedStartTime

**Canonical name:** PidTagRecipientProposedStartTime

**Description:** Indicates the **meeting** start time requested by the attendee in a **counter proposal**.

**Property ID:** 0x5FE3

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.5

**Alternate names:** PR\_RECIPIENT\_PROPOSEDSTARTTIME, ptagRecipientProposedStartTime

## 2.906 PidTagRecipientReassignmentProhibited

**Canonical name:** PidTagRecipientReassignmentProhibited

**Description:** Specifies whether adding additional or different **recipients** is prohibited for the email message when forwarding the email message.

**Property ID:** 0x002B

**Data type:** PtypBoolean, 0x000B

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.42

**Alternate names:** PR\_RECIPIENT\_REASSIGNMENT\_PROHIBITED, ptagRecipientReassignmentProhibited

## 2.907 PidTagRecipientTrackStatus

**Canonical name:** PidTagRecipientTrackStatus

**Description:** Indicates the response status that is returned by the attendee.

**Property ID:** 0x5FFF

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_TRACKSTATUS, ptagRecipientTrackStatus

## 2.908 PidTagRecipientTrackStatusTime

**Canonical name:** PidTagRecipientTrackStatusTime

**Description:** Indicates the date and time at which the attendee responded.

**Property ID:** 0x5FFB

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.3

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_RECIPIENT\_TRACKSTATUS\_TIME, ptagRecipientTrackStatusTime

## 2.909 PidTagRecipientType

**Canonical name:** PidTagRecipientType

**Description:** Represents the recipient type of a **recipient** on the message.

**Property ID:** 0x0C15

**Data type:** PtypInteger32, 0x0003

**Area:** MapiRecipient

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_TYPE, ptagRecipientType

## 2.910 PidTagRecordKey

**Canonical name:** PidTagRecordKey

**Description:** Contains a unique binary-comparable identifier for a specific object.

**Property ID:** 0x0FF9

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCFCFG\]](#), [\[MS-OXCFCICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCFCFG\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_RECORD\_KEY, ptagRecordKey

## 2.911 PidTagReferredByName

**Canonical name:** PidTagReferredByName

**Description:** Contains the name of the **mail user's** referral.

**Property ID:** 0x3A47

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.21

**Alternate names:** PR\_REferred\_BY\_NAME, PR\_REferred\_BY\_NAME\_A, PR\_REferred\_BY\_NAME\_W

## 2.912 PidTagRemindersOnlineEntryId

**Canonical name:** PidTagRemindersOnlineEntryId

**Description:** Contains an **EntryID** for the Reminders folder.

**Property ID:** 0x36D5

**Data type:** PtypBinary, 0x0102

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Alternate names:** PR\_REM\_ONLINE\_ENTRYID, ptagRemOnlineEntryId

## 2.913 PidTagRemoteMessageTransferAgent

**Canonical name:** PidTagRemoteMessageTransferAgent

**Description:** Contains the value of the Remote-MTA field for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C21

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.34

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_DSN\_REMOTE\_MTA, ptagDsnRemoteMta

## 2.914 PidTagRenderingPosition

**Canonical name:** PidTagRenderingPosition

**Description:** Represents an offset, in rendered characters, to use when rendering an attachment within the main message text.

**Property ID:** 0x370B

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAttachment

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.16

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_RENDERING\_POSITION, ptagRenderingPosition

## 2.915 PidTagReplyRecipientEntries

**Canonical name:** PidTagReplyRecipientEntries

**Description:** Identifies a **FlatEntryList** structure ([\[MS-OXCDATA\]](#) section 2.3.3) of address book **EntryIDs** for **recipients** that are to receive a reply.

**Property ID:** 0x004F

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.43

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_REPLY\_RECIPIENT\_ENTRIES, ptagReplyRecipientEntries, <http://schemas.microsoft.com/exchange/reply-to-base64>

## 2.916 PidTagReplyRecipientNames

**Canonical name:** PidTagReplyRecipientNames

**Description:** Contains a list of **display names** for **recipients** that are to receive a reply.

**Property ID:** 0x0050

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.44

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_REPLY\_RECIPIENT\_NAMES, PR\_REPLY\_RECIPIENT\_NAMES\_A, ptagReplyRecipientNames, PR\_REPLY\_RECIPIENT\_NAMES\_W

## 2.917 PidTagReplyRequested

**Canonical name:** PidTagReplyRequested

**Description:** Indicates whether a reply is requested to a **Message object**.

**Property ID:** 0x0C17

**Data type:** PtypBoolean, 0x000B

**Area:** MapiRecipient

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.45

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_REPLY\_REQUESTED, ptagReplyRequested

## 2.918 PidTagReplyTemplateId

**Canonical name:** PidTagReplyTemplateId

**Description:** Contains the value of the **GUID** that points to a Reply template.

**Property ID:** 0x65C2

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.9.2

**Alternate names:** PR\_REPLY\_TEMPLATE\_ID, ptagReplyTemplateId

## 2.919 PidTagReplyTime

**Canonical name:** PidTagReplyTime

**Description:** Specifies the time, in **UTC**, that the sender has designated for an associated work item to be due.

**Property ID:** 0x0030

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.3.1

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_REPLY\_TIME, urn:schemas:httpmail:reply-by, <http://schemas.microsoft.com/exchange/reply-by-iso>

## 2.920 PidTagReportDisposition

**Canonical name:** PidTagReportDisposition

**Description:** Contains a string indicating whether the original message was displayed to the user or deleted (report messages only).

**Property ID:** 0x0080

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.34

**Alternate names:** PR\_REPORT\_DISPOSITION\_W

## 2.921 PidTagReportDispositionMode

**Canonical name:** PidTagReportDispositionMode

**Description:** Contains a description of the **action** that a client has performed on behalf of a user (report messages only).

**Property ID:** 0x0081

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.35

**Alternate names:** PR\_REPORT\_DISPOSITION\_MODE\_W

## 2.922 PidTagReportEntryId

**Canonical name:** PidTagReportEntryId

**Description:** Specifies an **entry ID** that identifies the application that generated a report message.

**Property ID:** 0x0045

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.45

**Alternate names:** PR\_REPORT\_ENTRYID, ptagReportEntryId

## 2.923 PidTagReportingMessageTransferAgent

**Canonical name:** PidTagReportingMessageTransferAgent

**Description:** Contains the value of the Reporting-MTA field for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x6820

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.35

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagDsnReportingMta

## 2.924 PidTagReportName

**Canonical name:** PidTagReportName

**Description:** Contains the **display name** for the entity (usually a server agent) that generated the report message.

**Property ID:** 0x003A

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.20

**Alternate names:** PR\_REPORT\_NAME, PR\_REPORT\_NAME\_A, PR\_REPORT\_NAME\_W

## 2.925 PidTagReportSearchKey

**Canonical name:** PidTagReportSearchKey

**Description:** Contains an address book search key representing the entity (usually a server agent) that generated the report message.

**Property ID:** 0x0054

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.21

**Alternate names:** PR\_REPORT\_SEARCH\_KEY, ptagReportSearchKey

## 2.926 PidTagReportTag

**Canonical name:** PidTagReportTag

**Description:** Contains the data that is used to correlate the report and the original message.

**Property ID:** 0x0031

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.22

**Alternate names:** PR\_REPORT\_TAG, ptagReportTag

## 2.927 PidTagReportText

**Canonical name:** PidTagReportText

**Description:** Contains the optional text for a report message.

**Property ID:** 0x1001

**Data type:** PtypString, 0x001F

**Area:** MapiMessage

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.23

**Alternate names:** PR\_REPORT\_TEXT, PR\_REPORT\_TEXT\_A, ptagReportText, PR\_REPORT\_TEXT\_W

## 2.928 PidTagReportTime

**Canonical name:** PidTagReportTime

**Description:** Indicates the last time that the contact list that is controlled by the **PidTagJunkIncludeContacts** property (section [2.758](#)) was updated.

**Property ID:** 0x0032

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.6

**Alternate names:** PR\_REPORT\_TIME, ptagReportTime,  
<http://schemas.microsoft.com/exchange/reporttime>

### 2.929 PidTagResolveMethod

**Canonical name:** PidTagResolveMethod

**Description:** Specifies how to resolve any conflicts with the message.

**Property ID:** 0x3FE7

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.4.1

**Alternate names:** PR\_RESOLVE\_METHOD, ptagResolveMethod

### 2.930 PidTagResponseRequested

**Canonical name:** PidTagResponseRequested

**Description:** Indicates whether a response is requested to a **Message object**.

**Property ID:** 0x0063

**Data type:** PtypBoolean, 0x000B

**Area:** MapiEnvelope Property set

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.46

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_RESPONSE\_REQUESTED, urn:schemas:calendar:responserequested,  
[http://schemas.microsoft.com/mapi/response\\_requested](http://schemas.microsoft.com/mapi/response_requested)

### 2.931 PidTagResponsibility

**Canonical name:** PidTagResponsibility

**Description:** Specifies whether another mail agent has ensured that the message will be delivered.

**Property ID:** 0x0E0F

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.37

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_RESPONSIBILITY, ptagResponsibility



## 2.932 PidTagRetentionDate

**Canonical name:** PidTagRetentionDate

**Description:** Specifies the date, in **UTC**, after which a **Message object** is expired by the server.

**Property ID:** 0x301C

**Data type:** PtypTime, 0x0040

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.5

**Alternate names:** PR\_RETENTION\_DATE, ptagRetentionDate

## 2.933 PidTagRetentionFlags

**Canonical name:** PidTagRetentionFlags

**Description:** Contains **flags** that specify the status or nature of an item's **retention tag** or archive tag.

**Property ID:** 0x301D

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.6

**Alternate names:** PR\_RETENTION\_FLAGS, ptagRetentionFlags

## 2.934 PidTagRetentionPeriod

**Canonical name:** PidTagRetentionPeriod

**Description:** Specifies the number of days that a **Message object** can remain unarchived.

**Property ID:** 0x301A

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.3

**Alternate names:** PR\_RETENTION\_PERIOD, ptagRetentionPeriod

## 2.935 PidTagRights

**Canonical name:** PidTagRights

**Description:** Specifies a user's folder **permissions**.

**Property ID:** 0x6639

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXCFOOLD\]](#) section 2.2.2.2.2.8

**Consuming reference:** [\[MS-OXCPERM\]](#)

**Alternate names:** PR\_RIGHTS, ptagRights

## 2.936 PidTagRoamingDatatypes

**Canonical name:** PidTagRoamingDatatypes

**Description:** Contains a bitmask that indicates which **stream** properties exist on the message.

**Property ID:** 0x7C06

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.2.1

**Alternate names:** PR\_ROAMING\_DATATYPES

## 2.937 PidTagRoamingDictionary

**Canonical name:** PidTagRoamingDictionary

**Description:** Contains a dictionary **stream**, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.1.

**Property ID:** 0x7C07

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.2.2

**Alternate names:** PR\_ROAMING\_DICTIONARY

## 2.938 PidTagRoamingXmlStream

**Canonical name:** PidTagRoamingXmlStream

**Description:** Contains an **XML stream**, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.2.

**Property ID:** 0x7C08

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.2.3

**Alternate names:** PR\_ROAMING\_XMLSTREAM

## 2.939 PidTagRowid

**Canonical name:** PidTagRowid

**Description:** Contains a unique identifier for a **recipient** in a message's **recipient table**.

**Property ID:** 0x3000

**Data type:** PtypInteger32, 0x0003

**Area:** MapiCommon

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.38

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_ROWID, ptagRowId

## 2.940 PidTagRowType

**Canonical name:** PidTagRowType

**Description:** Identifies the type of the row.

**Property ID:** 0x0FF5

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.3

**Alternate names:** PR\_ROW\_TYPE, ptagRowType

## 2.941 PidTagRtfCompressed

**Canonical name:** PidTagRtfCompressed

**Description:** Contains **message body** text in compressed **RTF** format.

**Property ID:** 0x1009

**Data type:** PtypBinary, 0x0102

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.4

**Consuming references:** [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTCI\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFCP\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RTF\_COMPRESSED, ptagRTFCompressed

## 2.942 PidTagRtfInSync

**Canonical name:** PidTagRtfInSync

**Description:** Indicates whether the **PidTagBody** property (section [2.618](#)) and the **PidTagRtfCompressed** property (section [2.941](#)) contain the same text (ignoring formatting).

**Property ID:** 0x0E1F

**Data type:** PtypBoolean, 0x000B

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.5

**Consuming references:** [\[MS-OXBBODY\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_RTF\_IN\_SYNC, ptagRTFInSync

### 2.943 PidTagRuleActionNumber

**Canonical name:** PidTagRuleActionNumber

**Description:** Contains the index of a **rule action** that failed.

**Property ID:** 0x6650

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.7.4

**Alternate names:** PR\_RULE\_ACTION\_NUMBER, ptagRuleActionNumber

### 2.944 PidTagRuleActions

**Canonical name:** PidTagRuleActions

**Description:** Contains the set of **actions** associated with the **rule**.

**Property ID:** 0x6680

**Data type:** PtypRuleAction, 0x00FE

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.10

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_ACTIONS, ptagRuleActions

### 2.945 PidTagRuleActionType

**Canonical name:** PidTagRuleActionType

**Description:** Contains the **ActionType** field ([\[MS-OXORULE\]](#) section 2.2.5.1) of a **rule** that failed.

**Property ID:** 0x6649

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.7.3

**Alternate names:** PR\_RULE\_ACTION\_TYPE, ptagRuleActionType

### 2.946 PidTagRuleCondition

**Canonical name:** PidTagRuleCondition

**Description:** Defines the conditions under which a **rule action** is to be executed.

**Property ID:** 0x6679

**Data type:** **PtypRestriction**, 0x00FD

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.9

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_CONDITION, ptagRuleCondition

## 2.947 PidTagRuleError

**Canonical name:** PidTagRuleError

**Description:** Contains the error code that indicates the cause of an error encountered during the execution of the **rule**.

**Property ID:** 0x6648

**Data type:** **PtypInteger32**, 0x0003

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.7.2

**Alternate names:** PR\_RULE\_ERROR, ptagRuleError

## 2.948 PidTagRuleFolderEntryId

**Canonical name:** PidTagRuleFolderEntryId

**Description:** Contains the **EntryID** of the folder where the **rule** that triggered the generation of a **DAM** is stored.

**Property ID:** 0x6651

**Data type:** **PtypBinary**, 0x0102

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.5

**Alternate names:** PR\_RULE\_FOLDER\_ENTRYID, ptagRuleFolderEntryId

## 2.949 PidTagRuleId

**Canonical name:** PidTagRuleId

**Description:** Specifies a unique identifier that is generated by the messaging server for each **rule** when the rule is first created.

**Property ID:** 0x6674

**Data type:** **PtypInteger64**, 0x0014

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.1

**Alternate names:** PR\_RULE\_ID, ptagRuleId

## 2.950 PidTagRuleIds

**Canonical name:** PidTagRuleIds

**Description:** Contains a buffer that is obtained by concatenating the **PidTagRuleId** property (section [2.949](#)) values from all of the **rules** contributing **actions** that are contained in the **PidTagClientActions** property (section [2.634](#)).

**Property ID:** 0x6675

**Data type:** **PtypBinary**, 0x0102

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.7

**Alternate names:** PR\_RULE\_IDS, ptagRuleIds

## 2.951 PidTagRuleLevel

**Canonical name:** PidTagRuleLevel

**Description:** Contains 0x00000000. This property is not used.

**Property ID:** 0x6683

**Data type:** **PtypInteger32**, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.6

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_LEVEL, ptagRuleLevel

## 2.952 PidTagRuleMessageLevel

**Canonical name:** PidTagRuleMessageLevel

**Description:** Contains 0x00000000. Set on the **FAI** message.

**Property ID:** 0x65ED

**Data type:** **PtypInteger32**, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.6

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_LEVEL, ptagRuleMsgLevel

## 2.953 PidTagRuleMessageName

**Canonical name:** PidTagRuleMessageName

**Description:** Specifies the name of the **rule**. Set on the **FAI** message.

**Property ID:** 0x65EC

**Data type:** PtypString, 0x001F

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.1

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** ptagRuleMsgName

## 2.954 PidTagRuleMessageProvider

**Canonical name:** PidTagRuleMessageProvider

**Description:** Identifies the client application that owns the **rule**. Set on the **FAI** message.

**Property ID:** 0x65EB

**Data type:** PtypString, 0x001F

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.7

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** ptagRuleMsgProvider

## 2.955 PidTagRuleMessageProviderData

**Canonical name:** PidTagRuleMessageProviderData

**Description:** Contains opaque data set by the client for the exclusive use of the client. Set on the **FAI** message.

**Property ID:** 0x65EE

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.8

**Alternate names:** PR\_RULE\_MSG\_PROVIDER\_DATA, ptagRuleMsgProviderData

## 2.956 PidTagRuleMessageSequence

**Canonical name:** PidTagRuleMessageSequence

**Description:** Contains a value used to determine the order in which **rules** are evaluated and executed. Set on the **FAI** message.

**Property ID:** 0x65F3

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.3

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_SEQUENCE, ptagRuleMsgSequence

## 2.957 PidTagRuleMessageState

**Canonical name:** PidTagRuleMessageState

**Description:** Contains **flags** that specify the state of the **rule**. Set on the **FAI** message.

**Property ID:** 0x65E9

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.4

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_STATE, ptagRuleMsgState

## 2.958 PidTagRuleMessageUserFlags

**Canonical name:** PidTagRuleMessageUserFlags

**Description:** Contains an opaque property that the client sets for the exclusive use of the client. Set on the **FAI** message.

**Property ID:** 0x65EA

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.5

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_USER\_FLAGS, ptagRuleMsgUserFlags

## 2.959 PidTagRuleName

**Canonical name:** PidTagRuleName

**Description:** Specifies the name of the **rule**.

**Property ID:** 0x6682

**Data type:** PtypString, 0x001F

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.4



**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_NAME, PR\_RULE\_NAME\_A, ptagRuleName, PR\_RULE\_NAME\_W

## 2.960 PidTagRuleProvider

**Canonical name:** PidTagRuleProvider

**Description:** A string identifying the client application that owns a **rule**.

**Property ID:** 0x6681

**Data type:** PtypString, 0x001F

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.5

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_PROVIDER, ptagRuleProvider, PR\_RULE\_PROVIDER\_W

## 2.961 PidTagRuleProviderData

**Canonical name:** PidTagRuleProviderData

**Description:** Contains opaque data set by the client for the exclusive use of the client.

**Property ID:** 0x6684

**Data type:** PtypBinary, 0x0102

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.8

**Alternate names:** PR\_RULE\_PROVIDER\_DATA, ptagRuleProviderData

## 2.962 PidTagRuleSequence

**Canonical name:** PidTagRuleSequence

**Description:** Contains a value used to determine the order in which **rules** are evaluated and executed.

**Property ID:** 0x6676

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.2

**Consuming references:** [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_SEQUENCE, ptagRuleSequence

## 2.963 PidTagRuleState

**Canonical name:** PidTagRuleState

**Description:** Contains **flags** that specify the state of the **rule**.

**Property ID:** 0x6677

**Data type:** **PtypInteger32**, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.3

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_STATE, ptagRuleState

## 2.964 PidTagRuleUserFlags

**Canonical name:** PidTagRuleUserFlags

**Description:** Contains an opaque property that the client sets for the exclusive use of the client.

**Property ID:** 0x6678

**Data type:** **PtypInteger32**, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.7

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_USER\_FLAGS, ptagRuleUserFlags

## 2.965 PidTagRwRulesStream

**Canonical name:** PidTagRwRulesStream

**Description:** Contains additional **rule** data about the **Rule FAI message**.

**Property ID:** 0x6802

**Data type:** **PtypBinary**, 0x0102

**Area:** Message Class Defined Transmittable

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.9.3

**Alternate names:** PR\_RW\_RULES\_STREAM

## 2.966 PidTagScheduleInfoAppointmentTombstone

**Canonical name:** PidTagScheduleInfoAppointmentTombstone

**Description:** Contains a list of tombstones, where each tombstone represents a **Meeting object** that has been declined.

**Property ID:** 0x686A

**Data type:** **PtypBinary**, 0x0102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.5

**Alternate names:** PR\_SCHDINFO\_APPT\_TOMBSTONE

## 2.967 PidTagScheduleInfoAutoAcceptAppointments

**Canonical name:** PidTagScheduleInfoAutoAcceptAppointments

**Description:** Indicates whether a client or server is to automatically respond to all **meeting requests** for the attendee or resource.

**Property ID:** 0x686D

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.2

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_AUTO\_ACCEPT\_APPTS

## 2.968 PidTagScheduleInfoDelegateEntryIds

**Canonical name:** PidTagScheduleInfoDelegateEntryIds

**Description:** Specifies the **EntryIDs** of the **delegates**.

**Property ID:** 0x6845

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.5

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_ENTRYIDS

## 2.969 PidTagScheduleInfoDelegateNames

**Canonical name:** PidTagScheduleInfoDelegateNames

**Description:** Specifies the names of the **delegates**.

**Property ID:** 0x6844

**Data type:** PtypMultipleString, 0x101F

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.3

**Consuming reference:** [\[MS-OXMSG\]](#)

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_NAMES

## 2.970 PidTagScheduleInfoDelegateNamesW

**Canonical name:** PidTagScheduleInfoDelegateNamesW

**Description:** Specifies the names of the **delegates** in Unicode.

**Property ID:** 0x684A

**Data type:** **PtypMultipleString**, 0x101F

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.4

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_NAMES\_W, ptagDelegateNames

### 2.971 PidTagScheduleInfoDelegatorWantsCopy

**Canonical name:** PidTagScheduleInfoDelegatorWantsCopy

**Description:** Indicates whether the delegator wants to receive copies of the meeting-related objects that are sent to the **delegate**.

**Property ID:** 0x6842

**Data type:** **PtypBoolean**, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.1

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_BOSS\_WANTS\_COPY

### 2.972 PidTagScheduleInfoDelegatorWantsInfo

**Canonical name:** PidTagScheduleInfoDelegatorWantsInfo

**Description:** Indicates whether the delegator wants to receive informational updates.

**Property ID:** 0x684B

**Data type:** **PtypBoolean**, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.2

**Consuming references:** [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_BOSS\_WANTS\_INFO

### 2.973 PidTagScheduleInfoDisallowOverlappingAppts

**Canonical name:** PidTagScheduleInfoDisallowOverlappingAppts

**Description:** Indicates whether a client or server, when automatically responding to **meeting requests**, is to decline **Meeting Request objects** that overlap with previously scheduled events.

**Property ID:** 0x686F

**Data type:** **PtypBoolean**, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.4

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DISALLOW\_OVERLAPPING\_APPTS

## 2.974 PidTagScheduleInfoDisallowRecurringAppts

**Canonical name:** PidTagScheduleInfoDisallowRecurringAppts

**Description:** Indicates whether a client or server, when automatically responding to **meeting requests**, is to decline **Meeting Request objects** that represent a **recurring series**.

**Property ID:** 0x686E

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.3

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DISALLOW\_RECURRING\_APPTS

## 2.975 PidTagScheduleInfoDontMailDelegates

**Canonical name:** PidTagScheduleInfoDontMailDelegates

**Description:** Contains a value set to TRUE by the client, regardless of user input.

**Property ID:** 0x6843

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.7

**Consuming references:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DONT\_MAIL\_DELEGATES

## 2.976 PidTagScheduleInfoFreeBusy

**Canonical name:** PidTagScheduleInfoFreeBusy

**Description:** This property is deprecated and is not to be used.

**Property ID:** 0x686C

**Data type:** PtypBinary, 0x0102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.4.3

**Alternate names:** PR\_SCHDINFO\_FREEBUSY

## 2.977 PidTagScheduleInfoFreeBusyAway

**Canonical name:** PidTagScheduleInfoFreeBusyAway

**Description:** Specifies the times for which the **free/busy status** is set a value of **OOF**.

**Property ID:** 0x6856

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.6

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_OOF

## 2.978 PidTagScheduleInfoFreeBusyBusy

**Canonical name:** PidTagScheduleInfoFreeBusyBusy

**Description:** Specifies the blocks of time for which the **free/busy status** is set to a value of **busy**.

**Property ID:** 0x6854

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.4

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_BUSY

## 2.979 PidTagScheduleInfoFreeBusyMerged

**Canonical name:** PidTagScheduleInfoFreeBusyMerged

**Description:** Specifies the blocks for which free/busy data of type **busy** or **OOF** is present in the free/busy message.

**Property ID:** 0x6850

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.8

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_MERGED

## 2.980 PidTagScheduleInfoFreeBusyTentative

**Canonical name:** PidTagScheduleInfoFreeBusyTentative

**Description:** Specifies the blocks of times for which the **free/busy status** is set to a value of **tentative**.

**Property ID:** 0x6852

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.2

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_TENTATIVE

### 2.981 PidTagScheduleInfoMonthsAway

**Canonical name:** PidTagScheduleInfoMonthsAway

**Description:** Specifies the months for which free/busy data of type **OOF** is present in the free/busy message.

**Property ID:** 0x6855

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.5

**Alternate names:** PR\_SCHDINFO\_MONTHS\_OOF

### 2.982 PidTagScheduleInfoMonthsBusy

**Canonical name:** PidTagScheduleInfoMonthsBusy

**Description:** Specifies the months for which free/busy data of type **busy** is present in the free/busy message.

**Property ID:** 0x6853

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXMSG\]](#)

**Alternate names:** PR\_SCHDINFO\_MONTHS\_BUSY

### 2.983 PidTagScheduleInfoMonthsMerged

**Canonical name:** PidTagScheduleInfoMonthsMerged

**Description:** Specifies the months for which free/busy data of type **busy** or **OOF** is present in the free/busy message.

**Property ID:** 0x684F

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.7

**Alternate names:** PR\_SCHDINFO\_MONTHS\_MERGED

### 2.984 PidTagScheduleInfoMonthsTentative

**Canonical name:** PidTagScheduleInfoMonthsTentative

**Description:** Specifies the months for which free/busy data of type **tentative** is present in the free/busy message.

**Property ID:** 0x6851

**Data type:** **PtypMultipleInteger32**, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.1

**Alternate names:** PR\_SCHDINFO\_MONTHS\_TENTATIVE

## 2.985 PidTagScheduleInfoResourceType

**Canonical name:** PidTagScheduleInfoResourceType

**Description:** Set to 0x00000000 when sending and is ignored on receipt.

**Property ID:** 0x6841

**Data type:** **PtypInteger32**, 0x0003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.4.2

**Alternate names:** PR\_SCHDINFO\_RESOURCE\_TYPE

## 2.986 PidTagSchedulePlusFreeBusyEntryId

**Canonical name:** PidTagSchedulePlusFreeBusyEntryId

**Description:** Contains the **EntryID** of the folder named "SCHEDULE+ FREE BUSY" under the non-IPM subtree of the **public folder message store**.

**Property ID:** 0x6622

**Data type:** **PtypBinary**, 0x0102

**Area:** ExchangeMessageStore

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.2.2

**Alternate names:** PR\_SPLUS\_FREE\_BUSY\_ENTRYID

## 2.987 PidTagScriptData

**Canonical name:** PidTagScriptData

**Description:** Contains a series of instructions that can be executed to format an address and the data that is needed to execute those instructions.

**Property ID:** 0x0004

**Data type:** **PtypBinary**, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABKT\]](#) section 2.2.2



**Alternate names:** PR\_EMS\_SCRIPT\_BLOB

## 2.988 PidTagSearchFolderDefinition

**Canonical name:** PidTagSearchFolderDefinition

**Description:** Specifies the search criteria and search options.

**Property ID:** 0x6845

**Data type:** PtypBinary, 0x0102

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.8

**Alternate names:** PR\_WB\_SF\_DEFINITION

## 2.989 PidTagSearchFolderEfpFlags

**Canonical name:** PidTagSearchFolderEfpFlags

**Description:** Specifies **flags** that control how a folder is displayed.

**Property ID:** 0x6848

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.7

**Alternate names:** PR\_WB\_SF\_EFP\_FLAGS

## 2.990 PidTagSearchFolderExpiration

**Canonical name:** PidTagSearchFolderExpiration

**Description:** Contains the time, in **UTC**, at which the search folder container will be stale and has to be updated or recreated.

**Property ID:** 0x683A

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.5

**Alternate names:** PR\_WB\_SF\_EXPIRATION

## 2.991 PidTagSearchFolderId

**Canonical name:** PidTagSearchFolderId

**Description:** Contains a **GUID** that identifies the search folder.

**Property ID:** 0x6842

**Data type:** PtypBinary, 0x0102

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WB\_SF\_ID

## 2.992 PidTagSearchFolderLastUsed

**Canonical name:** PidTagSearchFolderLastUsed

**Description:** Contains the last time, in **UTC**, that the folder was accessed.

**Property ID:** 0x6834

**Data type:** **PtypInteger32**, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.4

**Alternate names:** PR\_WB\_SF\_LAST\_USED

## 2.993 PidTagSearchFolderRecreateInfo

**Canonical name:** PidTagSearchFolderRecreateInfo

**Description:** This property is not to be used.

**Property ID:** 0x6844

**Data type:** **PtypBinary**, 0x0102

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.9

**Alternate names:** PR\_WB\_SF\_RECREATE\_INFO

## 2.994 PidTagSearchFolderStorageType

**Canonical name:** PidTagSearchFolderStorageType

**Description:** Contains **flags** that specify the binary large object (BLOB) data that appears in the **PidTagSearchFolderDefinition** (section [2.988](#)) property.

**Property ID:** 0x6846

**Data type:** **PtypInteger32**, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.6

**Alternate names:** PR\_WB\_SF\_STORAGE\_TYPE

## 2.995 PidTagSearchFolderTag

**Canonical name:** PidTagSearchFolderTag

**Description:** Contains the value of the **SearchFolderTag** sub-property of the **PidTagExtendedFolderFlags** (section [2.691](#)) property of the search folder container.

**Property ID:** 0x6847

**Data type:** **PtypInteger32**, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.3

**Alternate names:** PR\_WB\_SF\_TAG

## 2.996 PidTagSearchFolderTemplateId

**Canonical name:** PidTagSearchFolderTemplateId

**Description:** Contains the ID of the template that is being used for the search.

**Property ID:** 0x6841

**Data type:** **PtypInteger32**, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.2

**Alternate names:** PR\_WB\_SF\_TEMPLATE\_ID

## 2.997 PidTagSearchKey

**Canonical name:** PidTagSearchKey

**Description:** Contains a unique binary-comparable key that identifies an object for a search.

**Property ID:** 0x300B

**Data type:** **PtypBinary**, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SEARCH\_KEY, ptagSearchKey

## 2.998 PidTagSecurityDescriptorAsXml

**Canonical name:** PidTagSecurityDescriptorAsXml

**Description:** Contains security attributes in **XML**.

**Property ID:** 0x0E6A

**Data type:** **PtypString**, 0x001F

**Area:** Access Control Properties

**Defining reference:** [\[MS-XWDVSEC\]](#) section 2.2.2

**Consuming reference:** [\[MS-OXCPERM\]](#)

**Alternate names:** PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML, PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML\_A, PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML\_W, <http://schemas.microsoft.com/exchange/security/descriptor>

## 2.999 PidTagSelectable

**Canonical name:** PidTagSelectable

**Description:** This property is not set and, if set, is ignored.

**Property ID:** 0x3609

**Data type:** PtypBoolean, 0x000B

**Area:** AB Container

**Defining reference:** [\[MS-OXOABKT\]](#) section 2.2.1

**Alternate names:** PR\_SELECTABLE

## 2.1000 PidTagSenderAddressType

**Canonical name:** PidTagSenderAddressType

**Description:** Contains the email **address type** of the sending **mailbox** owner.

**Property ID:** 0x0C1E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.48

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** PR\_SENDER\_ADDRTYPE, PR\_SENDER\_ADDRTYPE\_A, ptagSenderAddrType, PR\_SENDER\_ADDRTYPE\_W

## 2.1001 PidTagSenderEmailAddress

**Canonical name:** PidTagSenderEmailAddress

**Description:** Contains the email address of the sending **mailbox** owner.

**Property ID:** 0x0C1F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.49

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_EMAIL\_ADDRESS, PR\_SENDER\_EMAIL\_ADDRESS\_A, PR\_SENDER\_EMAIL\_ADDRESS\_W

## 2.1002 PidTagSenderEntryId

**Canonical name:** PidTagSenderEntryId

**Description:** Identifies an address book **EntryID** that contains the address book EntryID of the sending **mailbox** owner.

**Property ID:** 0x0C19

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.50

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_ENTRYID, ptagSenderEntryId

## 2.1003 PidTagSenderIdStatus

**Canonical name:** PidTagSenderIdStatus

**Description:** Reports the results of a Sender-ID check.

**Property ID:** 0x4079

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.80

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_SENDER\_ID\_STATUS

## 2.1004 PidTagSenderName

**Canonical name:** PidTagSenderName

**Description:** Contains the **display name** of the sending **mailbox** owner.

**Property ID:** 0x0C1A

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.51

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_NAME, PR\_SENDER\_NAME\_A, ptagSenderName, PR\_SENDER\_NAME\_W, urn:schemas:httpmail:sendername, http://schemas.microsoft.com/exchange/sender-name-utf8

## 2.1005 PidTagSenderSearchKey

**Canonical name:** PidTagSenderSearchKey

**Description:** Identifies an address book search key.

**Property ID:** 0x0C1D

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.52

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** PR\_SENDER\_SEARCH\_KEY, ptagSenderSearchKey

## 2.1006 PidTagSenderSmtpAddress

**Canonical name:** PidTagSenderSmtpAddress

**Description:** Contains the **SMTP** email address format of the e-mail address of the sending **mailbox** owner.

**Property ID:** 0x5D01

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.55

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** SenderSmtpAddress, ptagSenderSmtpAddress

## 2.1007 PidTagSenderTelephoneNumber

**Canonical name:** PidTagSenderTelephoneNumber

**Description:** Contains the telephone number of the caller associated with a voice mail message.

**Property ID:** 0x6802

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.1

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaSenderTelephoneNumber

## 2.1008 PidTagSendInternetEncoding

**Canonical name:** PidTagSendInternetEncoding

**Description:** Contains a bitmask of message encoding preferences for email sent to an email-enabled entity that is represented by this **Address Book object**.

**Property ID:** 0x3A71

**Data type:** PtypInteger32, 0x0003

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.19

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_SEND\_INTERNET\_ENCODING, ptagSendInternetEncoding

## 2.1009 PidTagSendRichInfo

**Canonical name:** PidTagSendRichInfo

**Description:** Indicates whether the email-enabled entity represented by the **Address Book object** can receive all message content, including **Rich Text Format (RTF)** and other embedded objects.

**Property ID:** 0x3A40

**Data type:** PtypBoolean, 0x000B

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.18

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_SEND\_RICH\_INFO, ptagSendRichInfo

## 2.1010 PidTagSensitivity

**Canonical name:** PidTagSensitivity

**Description:** Indicates the sender's assessment of the sensitivity of the **Message object**.

**Property ID:** 0x0036

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.13

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXVCARD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_SENSITIVITY, ptagSensitivity,  
<http://schemas.microsoft.com/exchange/sensitivity-long>,  
<http://schemas.microsoft.com/exchange/sensitivity>

## 2.1011 PidTagSentMailSvrEID

**Canonical name:** PidTagSentMailSvrEID

**Description:** Contains an **EntryID** that represents the **Sent Items folder** for the message.

**Property ID:** 0x6740

**Data type:** PtypServerId, 0x00FB

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.10

**Consuming reference:** [\[MS-OXCSTOR\]](#)

**Alternate names:** ptagSentMailSvrEID

## 2.1012 PidTagSentRepresentingAddressType

**Canonical name:** PidTagSentRepresentingAddressType

**Description:** Contains an email **address type**.

**Property ID:** 0x0064

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.54

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_ADDRTYPE, PR\_SENT\_REPRESENTING\_ADDRTYPE\_A, ptagSentRepresentingAddrType, PR\_SENT\_REPRESENTING\_ADDRTYPE\_W

## 2.1013 PidTagSentRepresentingEmailAddress

**Canonical name:** PidTagSentRepresentingEmailAddress

**Description:** Contains an email address for the end user who is represented by the sending **mailbox** owner.

**Property ID:** 0x0065

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.55

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS, PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_W



## 2.1014 PidTagSentRepresentingEntryId

**Canonical name:** PidTagSentRepresentingEntryId

**Description:** Contains the identifier of the end user who is represented by the sending **mailbox** owner.

**Property ID:** 0x0041

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.56

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_ENTRYID, ptagSentRepresentingEntryId

## 2.1015 PidTagSentRepresentingFlags

**Canonical name:** PidTagSentRepresentingFlags

**Description:**

**Property ID:** 0x401A

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:**

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** ptagSentRepresentingFlags

## 2.1016 PidTagSentRepresentingName

**Canonical name:** PidTagSentRepresentingName

**Description:** Contains the **display name** for the end user who is represented by the sending **mailbox** owner.

**Property ID:** 0x0042

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.57

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_NAME, PR\_SENT\_REPRESENTING\_NAME\_A, ptagSentRepresentingName, PR\_SENT\_REPRESENTING\_NAME\_W, urn:schemas:httpmail:fromname, http://schemas.microsoft.com/exchange/from-name-utf8

## 2.1017 PidTagSentRepresentingSearchKey

**Canonical name:** PidTagSentRepresentingSearchKey

**Description:** Contains a binary-comparable key that represents the end user who is represented by the sending **mailbox** owner.

**Property ID:** 0x003B

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.58

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_SEARCH\_KEY, ptagSentRepresentingSearchKey

## 2.1018 PidTagSentRepresentingSmtpAddress

**Canonical name:** PidTagSentRepresentingSmtpAddress

**Description:** Contains the SMTP email address of the end user who is represented by the sending mailbox owner.

**Property ID:** 0x5D02

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.59

**Alternate names:** ptagRecipientSentRepresentingSMTPAddress, SentRepresentingSMTPAddressXSO, PR\_SENT\_REPRESENTING\_SMTP\_ADDRESS

## 2.1019 PidTagSerializedReplidGuidMap

**Canonical name:** PidTagSerializedReplidGuidMap

**Description:** Contains a serialized list of **REPLID** and **REPLGUID** pairs which represent all or part of the REPLID / REPLGUID mapping of the associated **Logon object**.

**Property ID:** 0x6638

**Data type:** PtypBinary, 0x0102

**Area:** Logon Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.13

**Alternate names:** ptagSerializedReplidGuidMap

## 2.1020 PidTagSmtpAddress

**Canonical name:** PidTagSmtpAddress

**Description:** Contains the **SMTP** address of the **Message object**.

**Property ID:** 0x39FE

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.21

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXSHARE\]](#)

**Alternate names:** PR\_SMTP\_ADDRESS, PR\_SMTP\_ADDRESS\_A, PR\_SMTP\_ADDRESS\_W

## 2.1021 PidTagSortLocaleId

**Canonical name:** PidTagSortLocaleId

**Description:** Contains the **locale** identifier.

**Property ID:** 0x6705

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.14

**Consuming reference:** [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_SORT\_LOCALE\_ID, ptagSortLocaleId

## 2.1022 PidTagSourceKey

**Canonical name:** PidTagSourceKey

**Description:** Contains a value that contains an internal global identifier (GID) for this folder or message.

**Property ID:** 0x65E0

**Data type:** PtypBinary, 0x0102

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.5

**Alternate names:** PR\_SOURCE\_KEY

## 2.1023 PidTagSpokenName

**Canonical name:** PidTagSpokenName

**Description:** Contains a recording of the **mail user's** name pronunciation.

**Property ID:** 0x8CC2

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.41

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_UM\_SPOKEN\_NAME

## 2.1024 PidTagSpouseName

**Canonical name:** PidTagSpouseName

**Description:** Contains the name of the **mail user's** spouse/partner.

**Property ID:** 0x3A48

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_SPOUSE\_NAME, PR\_SPOUSE\_NAME\_A, PR\_SPOUSE\_NAME\_W,  
urn:schemas:contacts:spousecn

## 2.1025 PidTagStartDate

**Canonical name:** PidTagStartDate

**Description:** Contains the value of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

**Property ID:** 0x0060

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.30

**Consuming references:** [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#),

**Alternate names:** PR\_START\_DATE, [http://schemas.microsoft.com/mapi/start\\_date](http://schemas.microsoft.com/mapi/start_date)

## 2.1026 PidTagStartDateEtc

**Canonical name:** PidTagStartDateEtc

**Description:** Contains the default retention period, and the start date from which the age of a **Message object** is calculated.

**Property ID:** 0x301B

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.4

**Alternate names:** PR\_START\_DATE\_ETC, ptagStartDateEtc

## 2.1027 PidTagStateOrProvince

**Canonical name:** PidTagStateOrProvince

**Description:** Contains the name of the **mail user's** state or province.

**Property ID:** 0x3A28

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.17

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_STATE\_OR\_PROVINCE, PR\_STATE\_OR\_PROVINCE\_A, PR\_STATE\_OR\_PROVINCE\_W, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:mailingstate

## 2.1028 PidTagStoreEntryId

**Canonical name:** PidTagStoreEntryId

**Description:** Contains the unique **EntryID** of the **message store** where an object resides.

**Property ID:** 0x0FFB

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.44

**Consuming references:** [\[MS-OXOFLAG\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_STORE\_ENTRYID, ptagStoreEntryId

## 2.1029 PidTagStoreState

**Canonical name:** PidTagStoreState

**Description:** Indicates whether a **mailbox** has any active Search folders.

**Property ID:** 0x340E

**Data type:** PtypInteger32, 0x0003

**Area:** MapiMessageStore

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Alternate names:** PR\_STORE\_STATE

## 2.1030 PidTagStoreSupportMask

**Canonical name:** PidTagStoreSupportMask

**Description:** Indicates whether string properties within the .msg file are Unicode-encoded.

**Property ID:** 0x340D

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXMSG\]](#) section 2.1.1.1

**Alternate names:** PR\_STORE\_SUPPORT\_MASK, ptagStoreSupportMask

## 2.1031 PidTagStreetAddress

**Canonical name:** PidTagStreetAddress

**Description:** Contains the **mail user's** street address.

**Property ID:** 0x3A29

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.14

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_STREET\_ADDRESS, PR\_STREET\_ADDRESS\_A, PR\_STREET\_ADDRESS\_W, PR\_BUSINESS\_ADDRESS\_STREET, PR\_BUSINESS\_ADDRESS\_STREET\_A, PR\_BUSINESS\_ADDRESS\_STREET\_W, urn:schemas:contacts:mailingstreet

## 2.1032 PidTagSubfolders

**Canonical name:** PidTagSubfolders

**Description:** Specifies whether a folder has subfolders.

**Property ID:** 0x360A

**Data type:** PtypBoolean, 0x000B

**Area:** MapiContainer

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.12

**Alternate names:** PR\_SUBFOLDERS, ptagSubFolders, DAV:hassubs

## 2.1033 PidTagSubject

**Canonical name:** PidTagSubject

**Description:** Contains the subject of the email message.

**Property ID:** 0x0037

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.46

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORULE\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_SUBJECT, PR\_SUBJECT\_A, ptagSubject, PR\_SUBJECT\_W, urn:schemas:httpmail:subject, http://schemas.microsoft.com/exchange/subject-utf8

## 2.1034 PidTagSubjectPrefix

**Canonical name:** PidTagSubjectPrefix

**Description:** Contains the prefix for the subject of the message.

**Property ID:** 0x003D

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SUBJECT\_PREFIX, PR\_SUBJECT\_PREFIX\_A, ptagSubjectPrefix, PR\_SUBJECT\_PREFIX\_W

## 2.1035 PidTagSupplementaryInfo

**Canonical name:** PidTagSupplementaryInfo

**Description:** Contains supplementary information about a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C1B

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.36

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_SUPPLEMENTARY\_INFO, ptagSupplementaryInfo

## 2.1036 PidTagSurname

**Canonical name:** PidTagSurname

**Description:** Contains the **mail user's** family name.

**Property ID:** 0x3A11

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.1

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_SURNAME, PR\_SURNAME\_A, PR\_SURNAME\_W, urn:schemas:contacts:sn

### 2.1037 PidTagSwappedToDoData

**Canonical name:** PidTagSwappedToDoData

**Description:** Contains a secondary storage location for **flags** when sender flags or sender **reminders** are supported.

**Property ID:** 0x0E2D

**Data type:** PtypBinary, 0x0102

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.7

**Consuming reference:** [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_SWAPPED\_TODO\_DATA, ptagSwappedToDoData

### 2.1038 PidTagSwappedToDoStore

**Canonical name:** PidTagSwappedToDoStore

**Description:** Contains the value of the **PidTagStoreEntryId** property (section [2.1028](#)) of the message when the value of the **PidTagSwappedToDoData** property (section [2.1037](#)) is set.

**Property ID:** 0x0E2C

**Data type:** PtypBinary, 0x0102

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.8

**Consuming reference:** [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_SWAPPED\_TODO\_STORE, ptagSwappedToDoStore

### 2.1039 PidTagTargetEntryId

**Canonical name:** PidTagTargetEntryId

**Description:** Contains the message ID of a **Message object** being submitted for optimization ([\[MS-OXOMSG\]](#) section 3.2.4.4).

**Property ID:** 0x3010

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [MS-OXOMSG] section 2.2.1.76

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCRPC\]](#)

**Alternate names:** PR\_TARGET\_ENTRYID, ptagTargetEntryId



## 2.1040 PidTagTelecommunicationsDeviceForDeafTelephoneNumber

**Canonical name:** PidTagTelecommunicationsDeviceForDeafTelephoneNumber

**Description:** Contains the **mail user's** telecommunication device for the deaf (TTY/TDD) telephone number.

**Property ID:** 0x3A4B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.13

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TTYTDD\_PHONE\_NUMBER, PR\_TTYTDD\_PHONE\_NUMBER\_A, PR\_TTYTDD\_PHONE\_NUMBER\_W, urn:schemas:contacts:ttytddphone

## 2.1041 PidTagTelexNumber

**Canonical name:** PidTagTelexNumber

**Description:** Contains the **mail user's** telex number. This property is returned from an **NSPI** server as a **PtypMultipleBinary**. Otherwise, the data type is **PtypString**.

**Property ID:** 0x3A2C

**Data type:** PtypString, 0x001F; PtypMultipleBinary, 0x1102

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.30

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TELEX\_NUMBER, PR\_TELEX\_NUMBER\_A, PR\_TELEX\_NUMBER\_W, urn:schemas:contacts:telexnumber

## 2.1042 PidTagTemplateData

**Canonical name:** PidTagTemplateData

**Description:** Describes the controls used in the template that is used to retrieve address book information.

**Property ID:** 0x0001

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABKT\]](#) section 2.2.2

**Alternate names:** PR\_EMS\_TEMPLATE\_BLOB

## 2.1043 PidTagTemplateid

**Canonical name:** PidTagTemplateid

**Description:** Contains the value of the **PidTagEntryId** property (section [2.683](#)), expressed as a **Permanent Entry ID** format.

**Property ID:** 0x3902

**Data type:** **PtypBinary**, 0x0102

**Area:** MapiAddressBook

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.3

**Alternate names:** PR\_TEMPLATEID

## 2.1044 **PidTagTextAttachmentCharset**

**Canonical name:** PidTagTextAttachmentCharset

**Description:** Specifies the character set of an attachment received via **MIME** with the content-type of text.

**Property ID:** 0x371B

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.25

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagTextAttachmentCharset

## 2.1045 **PidTagThumbnailPhoto**

**Canonical name:** PidTagThumbnailPhoto

**Description:** Contains the **mail user's** photo in .jpg format.

**Property ID:** 0x8C9E

**Data type:** **PtypBinary**, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.40

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_THUMBNAIL\_PHOTO

## 2.1046 **PidTagTitle**

**Canonical name:** PidTagTitle

**Description:** Contains the **mail user's** job title.

**Property ID:** 0x3A17

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.4

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TITLE, PR\_TITLE\_A, PR\_TITLE\_W, urn:schemas:contacts:title

## 2.1047 PidTagTnefCorrelationKey

**Canonical name:** PidTagTnefCorrelationKey

**Description:** Contains a value that correlates a **Transport Neutral Encapsulation Format (TNEF)** attachment with a message.

**Property ID:** 0x007F

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.29

**Consuming reference:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_TNEF\_CORRELATION\_KEY

## 2.1048 PidTagToDoItemFlags

**Canonical name:** PidTagToDoItemFlags

**Description:** Contains **flags** associated with objects.

**Property ID:** 0x0E2B

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_TODO\_ITEM\_FLAGS, ptagToDoItemFlags

## 2.1049 PidTagTransmittableDisplayName

**Canonical name:** PidTagTransmittableDisplayName

**Description:** Contains an **Address Book object's display name** that is transmitted with the message.

**Property ID:** 0x3A20

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.8

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_TRANSMITABLE\_DISPLAY\_NAME, PR\_TRANSMITABLE\_DISPLAY\_NAME\_A, ptagTransmittableDisplayName, PR\_TRANSMITABLE\_DISPLAY\_NAME\_W

## 2.1050 PidTagTransportMessageHeaders

**Canonical name:** PidTagTransportMessageHeaders

**Description:** Contains transport-specific message envelope information for email.

**Property ID:** 0x007D

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.61

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_TRANSPORT\_MESSAGE\_HEADERS, PR\_TRANSPORT\_MESSAGE\_HEADERS\_A, PR\_TRANSPORT\_MESSAGE\_HEADERS\_W

## 2.1051 PidTagTrustSender

**Canonical name:** PidTagTrustSender

**Description:** Specifies whether the associated message was delivered through a trusted transport channel.

**Property ID:** 0x0E79

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.45

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_TRUST\_SENDER, ptagTrustSender

## 2.1052 PidTagUserCertificate

**Canonical name:** PidTagUserCertificate

**Description:** Contains an ASN.1 authentication certificate for a messaging user.

**Property ID:** 0x3A22

**Data type:** PtypBinary, 0x0102

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.34

**Consuming references:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_USER\_CERTIFICATE, ptagUserCertificate, urn:schemas:contacts:usercertificate

## 2.1053 PidTagUserEntryId

**Canonical name:** PidTagUserEntryId

**Description:** Address book **EntryID** of the user logged on to the **public folders**.

**Property ID:** 0x6619

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeMessageStore

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Alternate names:** PR\_USER\_ENTRYID, ptagUserEntryId

## 2.1054 PidTagUserX509Certificate

**Canonical name:** PidTagUserX509Certificate

**Description:** Contains a list of certificates for the **mail user**.

**Property ID:** 0x3A70

**Data type:** PtypMultipleBinary, 0x1102

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.36

**Consuming references:** [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_USER\_X509\_CERTIFICATE

## 2.1055 PidTagViewDescriptorBinary

**Canonical name:** PidTagViewDescriptorBinary

**Description:** Contains view definitions.

**Property ID:** 0x7001

**Data type:** PtypBinary, 0x0102

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.6.1

**Alternate names:** PR\_VD\_BINARY

## 2.1056 PidTagViewDescriptorName

**Canonical name:** PidTagViewDescriptorName

**Description:** Contains the view descriptor name.

**Property ID:** 0x7006

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCFG\]](#) section [2.2.6.2](#)

**Alternate names:** PR\_VD\_NAME, PR\_VD\_NAME\_W

## **2.1057 PidTagViewDescriptorStrings**

**Canonical name:** PidTagViewDescriptorStrings

**Description:** Contains view definitions in string format.

**Property ID:** 0x7002

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCFG\]](#) section [2.2.6.3](#)

**Alternate names:** PR\_VD\_STRINGS, PR\_VD\_STRINGS\_W

## **2.1058 PidTagViewDescriptorVersion**

**Canonical name:** PidTagViewDescriptorVersion

**Description:** Contains the View Descriptor version.

**Property ID:** 0x7007

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOCFG\]](#) section [2.2.6.4](#)

**Alternate names:** PR\_VD\_VERSION

## **2.1059 PidTagVoiceMessageAttachmentOrder**

**Canonical name:** PidTagVoiceMessageAttachmentOrder

**Description:** Contains a list of file names for the audio file attachments that are to be played as part of a message.

**Property ID:** 0x6805

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.9

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageAttachmentOrder

## **2.1060 PidTagVoiceMessageDuration**

**Canonical name:** PidTagVoiceMessageDuration

**Description:** Specifies the length of the attached audio message, in seconds.

**Property ID:** 0x6801

**Data type:** PtypInteger32, 0x0003

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.3

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageDuration

## 2.1061 PidTagVoiceMessageSenderName

**Canonical name:** PidTagVoiceMessageSenderName

**Description:** Specifies the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

**Property ID:** 0x6803

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.5

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageSenderName

## 2.1062 PidTagWeddingAnniversary

**Canonical name:** PidTagWeddingAnniversary

**Description:** Contains the date of the **mail user's** wedding anniversary.

**Property ID:** 0x3A41

**Data type:** PtypTime, 0x0040

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.4

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_WEDDING\_ANNIVERSARY, urn:schemas:contacts:weddinganniversary

## 2.1063 PidTagWlinkAddressBookEID

**Canonical name:** PidTagWlinkAddressBookEID

**Description:** Specifies the value of the **PidTagEntryId** property (section [2.683](#)) of the user to whom the folder belongs.

**Property ID:** 0x6854

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.16

**Alternate names:** PR\_WLINK\_ABEID

## 2.1064 PidTagWlinkAddressBookStoreEID

**Canonical name:** PidTagWlinkAddressBookStoreEID

**Description:** Specifies the value of the **PidTagStoreEntryId** property (section [2.1028](#)) of the current user (not the owner of the folder).

**Property ID:** 0x6891

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.17

**Alternate names:** PR\_WLINK\_AB\_EXSTOREEID

## 2.1065 PidTagWlinkCalendarColor

**Canonical name:** PidTagWlinkCalendarColor

**Description:** Specifies the background color of the **calendar**.

**Property ID:** 0x6853

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.15

**Alternate names:** PR\_WLINK\_CALENDAR\_COLOR

## 2.1066 PidTagWlinkClientID

**Canonical name:** PidTagWlinkClientID

**Description:** Specifies the Client ID that allows the client to determine whether the shortcut was created on the current machine/user via an equality test.

**Property ID:** 0x6890

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.18

**Alternate names:** PR\_WLINK\_CLIENTID

## 2.1067 PidTagWlinkEntryId

**Canonical name:** PidTagWlinkEntryId

**Description:** Specifies the **EntryID** of the folder pointed to by the shortcut.



**Property ID:** 0x684C

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.8

**Alternate names:** PR\_WLINK\_ENTRYID

## 2.1068 PidTagWlinkFlags

**Canonical name:** PidTagWlinkFlags

**Description:** Specifies conditions associated with the shortcut.

**Property ID:** 0x684A

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.6

**Alternate names:** PR\_WLINK\_FLAGS

## 2.1069 PidTagWlinkFolderType

**Canonical name:** PidTagWlinkFolderType

**Description:** Specifies the type of folder pointed to by the shortcut.

**Property ID:** 0x684F

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.11

**Alternate names:** PR\_WLINK\_FOLDER\_TYPE

## 2.1070 PidTagWlinkGroupClsid

**Canonical name:** PidTagWlinkGroupClsid

**Description:** Specifies the value of the **PidTagWlinkGroupHeaderID** property (section 2.1070) of the **group header** associated with the shortcut.

**Property ID:** 0x6850

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.12

**Alternate names:** PR\_WLINK\_GROUP\_CLSID

## 2.1071 PidTagWlinkGroupHeaderID

**Canonical name:** PidTagWlinkGroupHeaderID

**Description:** Specifies the ID of the **navigation shortcut** that groups other navigation shortcuts.

**Property ID:** 0x6842

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.3

**Alternate names:**

## 2.1072 PidTagWlinkGroupName

**Canonical name:** PidTagWlinkGroupName

**Description:** Specifies the value of the **PidTagNormalizedSubject** (section [2.812](#)) of the **group header** associated with the shortcut.

**Property ID:** 0x6851

**Data type:** PtypString, 0x001F

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.13

**Alternate names:** PR\_WLINK\_GROUP\_NAME

## 2.1073 PidTagWlinkOrdinal

**Canonical name:** PidTagWlinkOrdinal

**Description:** Specifies a variable-length binary property to be used to sort shortcuts lexicographically.

**Property ID:** 0x684B

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.7

**Alternate names:** PR\_WLINK\_ORDINAL

## 2.1074 PidTagWlinkRecordKey

**Canonical name:** PidTagWlinkRecordKey

**Description:** Specifies the value of **PidTagRecordKey** property (section [2.910](#)) of the folder pointed to by the shortcut.

**Property ID:** 0x684D

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.9

**Alternate names:** PR\_WLINK\_RECKEY

## **2.1075      PidTagWlinkROGroupType**

**Canonical name:** PidTagWlinkROGroupType

**Description:** Specifies the type of **group header**.

**Property ID:** 0x6892

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.19

**Alternate names:** PR\_WLINK\_RO\_GROUP\_TYPE

## **2.1076      PidTagWlinkSaveStamp**

**Canonical name:** PidTagWlinkSaveStamp

**Description:** Specifies an integer that allows a client to identify with a high probability whether the **navigation shortcut** was saved by the current client session.

**Property ID:** 0x6847

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.4

**Alternate names:**

## **2.1077      PidTagWlinkSection**

**Canonical name:** PidTagWlinkSection

**Description:** Specifies the section where the shortcut will be grouped.

**Property ID:** 0x6852

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.14

**Alternate names:** PR\_WLINK\_SECTION

## **2.1078      PidTagWlinkStoreEntryId**

**Canonical name:** PidTagWlinkStoreEntryId

**Description:** Specifies the value of the **PidTagStoreEntryId** property (section [2.1028](#)) of the folder pointed to by the shortcut.

**Property ID:** 0x684E

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.10

**Alternate names:** PR\_WLINK\_STORE\_ENTRYID

## **2.1079      PidTagWlinkType**

**Canonical name:** PidTagWlinkType

**Description:** Specifies the type of **navigation shortcut**.

**Property ID:** 0x6849

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.5

**Alternate names:** PR\_WLINK\_TYPE

### 3 Structure Examples

None.

## **4 Security**

There are no security considerations unique to this specification.

### **4.1 Security Considerations for Implementers**

None.

### **4.2 Index of Security Fields**

None.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Microsoft Exchange Server 2003
- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Exchange Server 2016
- Microsoft Exchange Server 2019
- Microsoft Office Outlook 2003
- Microsoft Office Outlook 2007
- Microsoft Outlook 2010
- Microsoft Outlook 2013
- Microsoft Outlook 2016
- Microsoft Outlook 2019
- Microsoft Outlook 2021

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

## 6 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Description	Revision class
<a href="#">5</a> Appendix A: Product Behavior	Updated list of supported products.	major



## 7 Index

### A

[Applicability](#) 40

### C

[Change tracking](#) 376

### E

[Examples](#) 373

### F

[Fields - security index](#) 374

[Fields - vendor-extensible](#) 41

### G

[Glossary](#) 24

### I

[Implementer - security considerations](#) 374

[Index of security fields](#) 374

[Informative references](#) 34

[Introduction](#) 24

### L

[Localization](#) 40

### N

[Normative references](#) 32

### O

Overview

[common message classes](#) 36

[commonly used property sets](#) 37

[property ID ranges](#) 38

[WebDAV property naming](#) 39

[Overview \(synopsis\)](#) 34

### P

[Product behavior](#) 375

### R

[References](#) 32

[informative](#) 34

[normative](#) 32

[Relationship to protocols and other structures](#) 40

### S

Security

[field index](#) 374

[implementer considerations](#) 374

### T

[Tracking changes](#) 376

### V

[Vendor-extensible fields](#) 41

[Versioning](#) 40