

[MS-OXRTFEX]:

Rich Text Format (RTF) Extensions Algorithm

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. For questions and support, please contact dochelp@microsoft.com.

Preliminary Documentation. This particular Open Specifications document provides documentation for past and current releases and/or for the pre-release version of this technology. This document provides final documentation for past and current releases and preliminary documentation, as applicable and specifically noted in this document, for the pre-release version. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. Because this documentation might change between the pre-release version and the final

version of this technology, there are risks in relying on this preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Preliminary

Revision Summary

Date	Revision History	Revision Class	Comments
4/4/2008	0.1	New	Initial Availability.
4/25/2008	0.2	Minor	Revised and updated property names and other technical content.
6/27/2008	1.0	Major	Initial Release.
8/6/2008	1.01	Minor	Updated references to reflect date of initial release.
9/3/2008	1.02	Minor	Revised and edited technical content.
12/3/2008	1.03	Minor	Updated IP notice.
3/4/2009	1.04	Minor	Revised and edited technical content.
4/10/2009	2.0	Major	Updated technical content and applicable product releases.
7/15/2009	3.0	Major	Revised and edited for technical content.
11/4/2009	3.0.1	Editorial	Revised and edited the technical content.
2/10/2010	3.0.1	None	Version 3.0.1 release
5/5/2010	3.1	Minor	Updated the technical content.
8/4/2010	3.2	Minor	Clarified the meaning of the technical content.
11/3/2010	3.2	None	No changes to the meaning, language, or formatting of the technical content.
3/18/2011	3.2	None	No changes to the meaning, language, or formatting of the technical content.
8/5/2011	4.0	Major	Significantly changed the technical content.
10/7/2011	4.0	None	No changes to the meaning, language, or formatting of the technical content.
1/20/2012	5.0	Major	Significantly changed the technical content.
4/27/2012	6.0	Major	Significantly changed the technical content.
7/16/2012	6.0	None	No changes to the meaning, language, or formatting of the technical content.
10/8/2012	7.0	Major	Significantly changed the technical content.
2/11/2013	7.0	None	No changes to the meaning, language, or formatting of the technical content.
7/26/2013	7.0	None	No changes to the meaning, language, or formatting of the technical content.
11/18/2013	7.0	None	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	7.0	None	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	7.1	Minor	Clarified the meaning of the technical content.

Date	Revision History	Revision Class	Comments
7/31/2014	8.0	Major	Significantly changed the technical content.
10/30/2014	8.1	Minor	Clarified the meaning of the technical content.
3/16/2015	9.0	Major	Significantly changed the technical content.
5/26/2015	9.0	None	No changes to the meaning, language, or formatting of the technical content.
9/14/2015	9.0	None	No changes to the meaning, language, or formatting of the technical content.
6/13/2016	9.0	None	No changes to the meaning, language, or formatting of the technical content.
9/14/2016	9.0	None	No changes to the meaning, language, or formatting of the technical content.
7/24/2018	10.0	Major	Significantly changed the technical content.
10/1/2018	11.0	Major	Significantly changed the technical content.
4/22/2021	12.0	Major	Significantly changed the technical content.

Table of Contents

1	Introduction	6
1.1	Glossary	6
1.2	References	7
1.2.1	Normative References	7
1.2.2	Informative References	8
1.3	Overview	8
1.3.1	HTML/Plain Text Encapsulation	8
1.3.2	Attachment and RTF Integration	9
1.4	Relationship to Protocols and Other Algorithms	9
1.5	Applicability Statement	9
1.6	Standards Assignments	9
2	Algorithm Details	10
2.1	Encapsulating RTF Writer Algorithm Details	10
2.1.1	Abstract Data Model	10
2.1.2	Initialization	10
2.1.3	Processing Rules	10
2.1.3.1	HTML and Plain Text Specific Encapsulation Syntax	10
2.1.3.1.1	FROMTEXT Control Word	10
2.1.3.1.2	FROMHTML Control Word	10
2.1.3.1.3	HTMLRTF Toggle Control Word	11
2.1.3.1.4	HTMLTAG Destination Group	11
2.1.3.1.4.1	HTMLTagParameter HTML Fragment	12
2.1.3.1.4.2	CONTENT HTML Fragment	13
2.1.3.1.5	MHTMLTAG Destination Group	14
2.1.3.1.6	HTMLBASE Control Word	14
2.1.3.2	Encoding HTML into RTF	15
2.1.3.3	Encoding Plain Text into RTF	15
2.2	De-Encapsulating RTF Reader Algorithm Details	16
2.2.1	Abstract Data Model	16
2.2.2	Initialization	16
2.2.3	Processing Rules	16
2.2.3.1	Recognizing RTF Containing Encapsulation	16
2.2.3.2	Extracting Encapsulated HTML from RTF	17
2.2.3.3	Extracting Original Plain Text from RTF	18
2.2.3.4	Attachment and RTF Integration	18
3	Algorithm Examples	20
3.1	Encapsulating HTML into RTF	20
3.2	Integrating Sample Attachments and RTF	21
4	Security	30
4.1	Security Considerations for Implementers	30
4.2	Index of Security Parameters	30
5	Appendix A: Product Behavior	31
6	Change Tracking	33
7	Index	34

1 Introduction

The Rich Text Format (RTF) Extensions Algorithm is an extension to **RTF**, as described in [\[MSFT-RTF\]](#), that is used to encode meta information from (or about) the original format (**HTML** or **plain text**) within RTF.

Sections 1.6 and 2 of this specification are normative. All other sections and examples in this specification are informative.

1.1 Glossary

This document uses the following terms:

Attachment object: A set of properties that represents a file, **Message object**, or structured storage that is attached to a Message object and is visible through the **attachments table** for a Message object.

attachments table: A Table object whose rows represent the **Attachment objects** that are attached to a **Message object**.

Augmented Backus-Naur Form (ABNF): A modified version of Backus-Naur Form (BNF), commonly used by Internet specifications. ABNF notation balances compactness and simplicity with reasonable representational power. ABNF differs from standard BNF in its definitions and uses of naming rules, repetition, alternatives, order-independence, and value ranges. For more information, see [\[RFC5234\]](#).

character set: A mapping between the characters of a written language and the values that are used to represent those characters to a computer.

code page: An ordered set of characters of a specific script in which a numerical index (code-point value) is associated with each character. Code pages are a means of providing support for **character sets** and keyboard layouts used in different countries. Devices such as the display and keyboard can be configured to use a specific code page and to switch from one code page (such as the United States) to another (such as Portugal) at the user's request.

de-encapsulating RTF reader: A **Rich Text Format (RTF)** reader, as described in [\[MSFT-RTF\]](#), that recognizes if an input RTF document contains encapsulated HTML or plain text, and extracts and renders the original **HTML** or plain text instead of the encapsulating RTF content.

encapsulating RTF writer: A **Rich Text Format (RTF)** writer, as described in [\[MSFT-RTF\]](#), that produces an RTF document as a result of format conversion from other formats, such as plain text or HTML, and also stores the original document in a form that allows for subsequent retrieval.

encapsulation: A process of encoding one document in another document in a way that allows the first document to be re-created in a form that is nearly identical to its original form.

format conversion: A process that converts a text document from one text format, such as Rich Text Format (RTF), HTML, or plain text, to another text format. The result of text conversion is typically a new document that is an approximate rendering of the same information.

Hypertext Markup Language (HTML): An application of the Standard Generalized Markup Language (SGML) that uses tags to mark elements in a document, as described in [\[HTML\]](#).

message body: The main message text of an email message. A few properties of a **Message object** represent its message body, with one property containing the text itself and others defining its **code page** and its relationship to alternative body formats.

Message object: A set of properties that represents an email message, appointment, contact, or other type of personal-information-management object. In addition to its own properties, a Message object contains recipient properties that represent the addressees to which it is addressed, and an **attachments table** that represents any files and other Message objects that are attached to it.

MIME Encapsulation of Aggregate HTML Documents (MHTML): A MIME-encapsulated HTML document, as described in [\[RFC2557\]](#).

plain text: Text that does not have markup. See also plain text message body.

remote operation (ROP): An operation that is invoked against a server. Each ROP represents an action, such as delete, send, or query. A ROP is contained in a ROP buffer for transmission over the wire.

rendering position: A location in a **Rich Text Format (RTF)** document where an attachment is placed visually.

Rich Text Format (RTF): Text with formatting as described in [\[MSFT-RTF\]](#).

ROP request: See ROP request buffer.

Unicode: A character encoding standard developed by the Unicode Consortium that represents almost all of the written languages of the world. The **Unicode** standard [\[UNICODE5.0.0/2007\]](#) provides three forms (UTF-8, UTF-16, and UTF-32) and seven schemes (UTF-8, UTF-16, UTF-16 BE, UTF-16 LE, UTF-32, UTF-32 LE, and UTF-32 BE).

Uniform Resource Locator (URL): A string of characters in a standardized format that identifies a document or resource on the World Wide Web. The format is as specified in [\[RFC1738\]](#).

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[HTML] World Wide Web Consortium, "HTML 4.01 Specification", W3C Recommendation, December 1999, <http://www.w3.org/TR/html4/>

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)".

[MS-OXCMMSG] Microsoft Corporation, "[Message and Attachment Object Protocol](#)".

[MSFT-RTF] Microsoft Corporation, "Rich Text Format (RTF) Specification", version 1.9.1, March 2008, [https://interoperability.blob.core.windows.net/files/Archive_References/\[MSFT-RTF\].pdf](https://interoperability.blob.core.windows.net/files/Archive_References/[MSFT-RTF].pdf)

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

1.2.2 Informative References

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Algorithm](#)".

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol](#)".

[MS-OXCFXICS] Microsoft Corporation, "[Bulk Data Transfer Protocol](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[MS-OXRTFCP] Microsoft Corporation, "[Rich Text Format \(RTF\) Compression Algorithm](#)".

1.3 Overview

E-mail can transmit text in different text formats, including **Hypertext Markup Language (HTML)**, **RTF**, and **plain text**. Various software components can impose different text format requirements for content to be stored or displayed to the user, and text **format conversion** might be necessary to comply with these requirements. For example, an e-mail client might be configured to compose e-mail in HTML, RTF, or plain text, and support dynamically changing formats during composition.

General format conversion can introduce noticeable (and unwanted) changes in content formatting. Therefore, it is imperative not only to aim for high-fidelity conversions to RTF, but also to find a mechanism to recover the content in its original format. This algorithm is used to encode meta information from (or about) the original format (HTML or plain text) within RTF, so that if conversion back to the original form is necessary, it can be very close to the original content.

1.3.1 HTML/Plain Text Encapsulation

Encapsulation and de-encapsulation can introduce changes in the content of the original document, as long as such changes do not affect the rendering of the document in its original format. For example, it is allowable to introduce, remove, or change insignificant whitespace in **HTML** and/or to normalize text line endings to use carriage return/line feed pairs (CRLFs).

Two software roles can be identified in respect to this encapsulation format:

1. **Encapsulating RTF writer**: The **RTF** writer, as described in [\[MSFT-RTF\]](#), that converts content from HTML or **plain text** format to RTF and preserves the original form of the content in an RTF document by using the encapsulation format specified by this algorithm.
2. **De-encapsulating RTF reader**: The RTF reader, as described in [\[MSFT-RTF\]](#), that converts content from RTF back to HTML or plain text format, by recognizing that an RTF document contains encapsulated HTML or plain text content and extracting such content (instead of performing a general **format conversion** from RTF to HTML or plain text format).

This algorithm does not specify a general format conversion process between HTML (or plain text) and RTF. Such a conversion process can be a proprietary and often approximate mapping between RTF formatting features, as described in [\[MSFT-RTF\]](#), and HTML formatting features, as described in [\[HTML\]](#). For example, the HTML code fragment "test" could be converted to "{\b test}". The encapsulation of original content is orthogonal to a format conversion process and can be combined with any such format conversion.

An RTF reader can choose to ignore the encapsulation within an RTF document and treat such a document as a pure RTF document. Therefore, the RTF document that contains the encapsulated original content needs to also contain an adequate RTF rendering of the original HTML or plain text document. The implementer determines the richness of the conversion from the original content format to RTF.

1.3.2 Attachment and RTF Integration

E-mail clients that support **RTF** can support rendering attachments, images, and file attachment icons inline with **message body** text. This algorithm defines how to identify and specify which object to render at a given position within an RTF document. This algorithm does not specify how to generate the visual representation of an attachment.

If a client does not implement this portion of the algorithm, relationships between the attachment position and associated text within a document might be ambiguous. For example, if a document introduces an attachment with the text "the content in the following file:", the expectation is that the file attachment icon will appear adjacent to the introductory text. However, if this algorithm is not implemented, the file attachment icon might not appear near the associated text, making the association ambiguous if there are multiple attachments involved.

1.4 Relationship to Protocols and Other Algorithms

This is an extension to **RTF**, as described in [\[MSFT-RTF\]](#).

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

1.5 Applicability Statement

This algorithm is applicable to any client or server that supports **RTF**. A client can use this algorithm to store or retrieve **HTML** or **plain text** that is encapsulated in RTF. De-encapsulating the original HTML or plain text from the RTF document enables the client to render content with higher fidelity than might be achieved by converting the content from RTF back to HTML or plain text format.

Attachment and RTF integration, as described in section [2.1](#), is necessary to adequately render RTF message bodies. The reintegration is important to providing an accurate placement of inline images, attachment icons, and other objects.

1.6 Standards Assignments

None.

2 Algorithm Details

2.1 Encapsulating RTF Writer Algorithm Details

Encapsulation enables storage of the **HTML** or **plain text** content of a document in the body of another **RTF** document. [<1>](#) Encapsulation leverages native RTF such that an RTF reader can render the RTF representation of the document without any indication of embedded content and, when de-encapsulated, the HTML and plain text will differ only minimally from the original HTML or plain text content.

To encapsulate HTML or plain text document content inside an RTF document, the RTF writer uses two extensibility features of RTF, as described in [\[MSFT-RTF\]](#):

1. RTF control words unknown to an RTF reader have to be ignored by the RTF reader. The HTML/plain text encapsulation format specified by this algorithm defines new RTF control words, as specified in section [2.1.3.1](#). RTF control words are described in [\[MSFT-RTF\]](#).
2. Ignorable RTF destinations (that is, RTF groups that start with "{*\<destination-name>" and end with "}") have to be skipped (not rendered in any form) by any RTF reader that does not recognize the <destination-name>. The HTML/plain text encapsulation format specified by this algorithm defines new RTF destinations for encapsulating original or rewritten HTML markup, as specified in section 2.1.

An implementer of this algorithm has to have a good understanding of RTF, as specified in [\[MSFT-RTF\]](#), and HTML, as specified in [\[HTML\]](#), to create RTF content that sufficiently represents the original HTML or plain text content, and to encapsulate plain text or HTML in such RTF.

2.1.1 Abstract Data Model

None.

2.1.2 Initialization

None.

2.1.3 Processing Rules

2.1.3.1 HTML and Plain Text Specific Encapsulation Syntax

Encapsulation uses several control words to fully encapsulate **HTML** and **plain text** in **RTF**. This section specifies the **Augmented Backus-Naur Form (ABNF)** grammar format, as specified in [\[RFC5234\]](#), for those tokens and includes information about each token.

2.1.3.1.1 FROMTEXT Control Word

The FROMTEXT control word specifies that the **RTF** document was produced from **plain text**.

```
; \fromtext
FROMTEXT = %x5C.66.72.6F.6D.74.65.78.74
```

This control word **MUST** appear before the \fonttbl control word and after the \rtf1 control word, as specified in [\[MSFT-RTF\]](#). For additional restrictions regarding placement of this control word, see section [2.2.2](#).

2.1.3.1.2 FROMHTML Control Word

The FROMHTML control word specifies that the **RTF** document contains encapsulated **HTML** text. [<2>](#)

```
; \fromhtml1
FROMHTML = %x5C.66.72.6F.6D.68.74.6D.6C "1"
```

This control word **MUST** be `\fromhtml1`. Any other form, such as `\fromhtml` or `\fromhtml0`, will not be considered encapsulated.

This control word **MUST** appear before the `\fonttbl` control word and after the `\rtf1` control word, as specified in [\[MSFT-RTF\]](#). For additional restrictions regarding placement of this control word, see section [2.2.2](#).

2.1.3.1.3 HTMLRTF Toggle Control Word

The HTMLRTF control word identifies fragments of **RTF** that were not in the original **HTML** content. [<3>](#)

```
; \htmlrtf or \htmlrtf1 or \htmlrtf0
HTMLRTF = %x5C.68.74.6D.6C.72.74.66["0" / "1"]
```

This control word is used to mark regions of the RTF content that are the result of approximate **format conversion** and were not part of the original HTML content.

This control word complies with the semantics specified in [\[MSFT-RTF\]](#) regarding toggle control words. Therefore, `\htmlrtf` and `\htmlrtf1` both represent enabling the control word.

Control word	State	Description
<code>\htmlrtf</code> <code>\htmlrtf1</code>	BEGIN	The de-encapsulating RTF reader MUST NOT copy any subsequent text and control words in the RTF content until the state is disabled.
<code>\htmlrtf0</code>	END	This control word disables an earlier instance of <code>\htmlrtf</code> or <code>\htmlrtf1</code> , thereby allowing the de-encapsulating RTF reader to evaluate subsequent text and control words in the RTF content.

A de-encapsulating RTF reader **MUST** support the HTMLRTF control word within nested groups. The state of the HTMLRTF control word **MUST** transfer when entering groups and be restored when exiting groups, as specified in [\[MSFT-RTF\]](#).

This example shows how states are modified when nested via groups using bold, where `\b` enables bold and `\b0` disables bold:

```
"\b bold { bold \b0 non-bold } bold \b0 non-bold non-bold { non-bold \b bold } non-bold"
```

2.1.3.1.4 HTMLTAG Destination Group

The HTMLTAG destination group encapsulates **HTML** fragments that cannot be directly represented in **RTF**. [<4>](#)

```
; \* \htmltag[HTMLTagParameter][CONTENT]
HTMLTAG = %x5C.2A.5C.68.74.6D.6C.74.61.67 [HTMLTagParameter] [CONTENT]
HTMLTagParameter = *3DIGIT
```

```
; A space MUST be used to separate the CONTENT HTML fragment
```

```

; from the HTMLTagParameter HTML fragment if the text
; starts with a DIGIT, or if the HTMLTagParameter HTML fragment
; is omitted.

CONTENT = [SP] *VCHAR

```

For example, "" would be specified in the CONTENT HTML fragment as follows: "*\htmltag148 ".

2.1.3.1.4.1 HTMLTagParameter HTML Fragment

The HTMLTagParameter **HTML** fragment is a **WORD** ([MS-DTYP]) value comprised of the flags specified in this section: **Destination**, **TagType**, and other flags. This fragment SHOULD NOT <5> be emitted, except as specified in section 2.1.3.2. Although the HTMLTagParameter HTML fragment is defined in terms of bitmasks, it appears in this specification as a decimal value.

Destination Flag

The **Destination** flag defines where the HTML content was located relative to the <HTML>, <HEAD>, and <BODY> elements. The following table specifies the values for the **Destination** flag.

Name	Value	Description
INBODY	0x0000	The corresponding fragment of original HTML SHOULD appear inside of a <BODY> HTML element.
INHEAD	0x0001	The corresponding fragment of original HTML SHOULD appear inside of a <HEAD> HTML element.
INHTML	0x0002	The corresponding fragment of original HTML SHOULD appear inside of an <HTML> HTML element.
OUTHTML	0x0003	The corresponding fragment of original HTML SHOULD appear outside of an <HTML> HTML element.

TagType Flag

The **TagType** flag defines the type of HTML content that is stored in the CONTENT HTML fragment in an *\htmltag destination group. The following table specifies the values for the **TagType** flag.

Name	Value	Description
TEXT	0x0000	This group encapsulates a text fragment rather than any HTML tags.
HTML	0x0010	This group encapsulates the <HTML> HTML element.
HEAD	0x0020	This group encapsulates the <HEAD> HTML element.
BODY	0x0030	This group encapsulates the <BODY> HTML element.
P	0x0040	This group encapsulates the <P> HTML element.
STARTP	0x0050	This group encapsulates an HTML tag that starts a paragraph other than the <P> HTML element.
ENDP	0x0060	This group encapsulates an HTML tag that ends a paragraph other than the <P> HTML element.
BR	0x0070	This group encapsulates the HTML element.
PRE	0x0080	This group encapsulates the <PRE> HTML element.

Name	Value	Description
FONT	0x0090	This group encapsulates the HTML element.
HEADER	0x00A0	This group encapsulates heading HTML tags such as <H1>, <H2>, and so on.
TITLE	0x00B0	This group encapsulates the <TITLE> HTML element.
PLAIN	0x00C0	This group encapsulates the <PLAIN> HTML element.
RESERVED1	0x00D0	Reserved, MUST be ignored.
RESERVED2	0x00E0	Reserved, MUST be ignored.
UNK	0x00F0	This group encapsulates any other HTML tag.

The following table specifies the values for the **Other** flags field.

Name	Value	Description
INPAR	0x0004	The corresponding fragment of the original HTML SHOULD appear inside a paragraph HTML element.
CLOSE	0x0008	This is a closing tag.
MHTML	0x0100	This group encapsulates MIME Encapsulation of Aggregate HTML Documents (MHTML) ; that is, an HTML tag with a rewritable <i>URL</i> parameter. For more details about the MHTMLTAG destination group, see section 2.1.3.1.5 .

2.1.3.1.4.2 CONTENT HTML Fragment

The CONTENT **HTML** fragment in an HTMLTAG destination group contains parts of original HTML markup or other text that are not duplicated or significantly transformed in **RTF** content, such as HTML tags, text that might include HTML character references, and HTML comments. [<6>](#)

It is possible that some text in the CONTENT HTML fragment will need to be escaped or converted to RTF control words to produce proper RTF. The following table specifies valid RTF escape tokens and control words that can be used in the CONTENT HTML fragment. A de-encapsulating RTF reader [MAY<7>](#) fail to extract the original HTML when other RTF control words are included in the CONTENT HTML fragment.

RTF escape tokens and control words	Corresponding HTML text
\par	%x0D.0A (OCTET sequence CRLF)
\tab	%x09 (OCTET form for the horizontal tab character)
\{	%x7B (OCTET form for {)
\}	%x7D (OCTET form for })
\\	%x5C (OCTET form for reverse solidus '\')
\quote	"‘" (Unicode value U+2018)
\rquote	"’" (Unicode value U+2019)
\dblquote	"“" (Unicode value U+201C)

RTF escape tokens and control words	Corresponding HTML text
\rdblquote	"”" (Unicode value U+201D)
\bullet	"•" (Unicode value U+2022)
\endash	"–" (Unicode value U+2013)
\emdash	"—" (Unicode value U+2014)
\~	" " (non-breaking space)
_	"­" (­ soft hyphen)
\HH	%xHH (OCTET with the hexadecimal value of HH)
\u[-]NNNNN	"&#xHHHH;" where: <ul style="list-style-type: none"> ▪ NNNNN is a positive integer expressed in decimal digits ▪ -NNNNN is a negative integer expressed in decimal digits ▪ HHHH is the hexadecimal equivalent of NNNNN or -NNNNN
\uc	No visual representation in HTML.

2.1.3.1.5 MHTMLTAG Destination Group

The MHTMLTAG destination group is used to encapsulate an **HTML** tag with a rewritable *URL* parameter.

```
; \* \mhtmltag [HTMLTagParameter] [CONTENT]
MHTMLTAG = %x5C.2A.5C.6D.68.74.6D.6C.74.61.67 [HTMLTagParameter] [CONTENT]
```

This **RTF** destination MAY be used in RTF marked with the \fromhtml1 control word. <8> The MHTMLTAG destination group has an optional numeric HTMLTagParameter HTML fragment. The values and format of the numeric parameter are identical to the numeric parameter in the HTMLTAG destination group, as specified in section [2.1.3.1.4.1](#).

This RTF control word SHOULD be skipped on de-encapsulation and SHOULD NOT be written when encapsulating.

2.1.3.1.6 HTMLBASE Control Word

The HTMLBASE control word indicates a location of a rewritten **Uniform Resource Locator (URL)** inside a MHTMLTAG destination group.

```
; \htmlbase
HTMLBASE = %x5C.68.74.6D.6C.62.61.73.65
```

This **RTF** control word SHOULD be skipped on de-encapsulation and SHOULD NOT be written when encapsulating. This is because the HTMLBASE control word can appear only inside an MHTMLTAG destination group, which is to be ignored, as specified in section [2.1.3.1.5](#).

2.1.3.2 Encoding HTML into RTF

The translation between **HTML** and **RTF** is not specified by this algorithm and is implementation-dependent. To emit RTF-encapsulated HTML, implementers MAY [<9>](#) do the following:

- Produce a valid RTF document, as specified by [\[MSFT-RTF\]](#).
- Emit a FROMHTML control word in the RTF header after the \rtf1 control word to indicate that encapsulated HTML is included in the RTF document.
- Specify a default **code page** for text runs in RTF by using the \ansicpgN keyword, as specified in [\[MSFT-RTF\]](#).
- Emit a font table to define fonts used in RTF.
- Specify **character set** information for each font when necessary, as specified in [\[MSFT-RTF\]](#).
- Produce a single empty HTMLTAG destination group with the **Destination** flag set to INBODY and the **TagType** flag set to P ({*\htmltag64}) before any shared visible text in a generated RTF document (for example, immediately following the RTF header, as specified in [\[MSFT-RTF\]](#)). [<10>](#)
- Use an HTMLTAG destination group to preserve any content of the original HTML document that does not have direct representation in RTF (such as HTML tags, text with HTML character references, HTML comments, or insignificant whitespace).
- Produce an HTMLTagParameter HTML fragment in any HTMLTAG destination control word (except the {*\htmltag64} empty destination group). [<11>](#) Any text inside an HTMLTAG destination group can be encoded by a default RTF code page, as specified in [\[MSFT-RTF\]](#). Any text that cannot be represented by using a default RTF code page without data loss can be encoded by using \uN control words.
- Use HTMLRTF control words to suppress de-encapsulation of any RTF content that is not part of the original HTML content. In particular, any emitted RTF control words that change character-formatting properties, such as \f, \fs, \b, or \i, can [<12>](#) be explicitly suppressed by the HTMLRTF control word. Any corresponding original HTML content can be encapsulated in HTMLTAG destination groups, as specified in section [2.1.3.1.4](#).
- Produce text in a code page that corresponds to the current font for each text run, or in a default RTF code page if no current font is selected for a text run (outside of an HTMLTAG destination group, and when not suppressed by an HTMLRTF control word). Any characters that cannot be represented in a selected code page can be encoded by using the \uN control word.

2.1.3.3 Encoding Plain Text into RTF

The translation between **plain text** and **RTF** is not specified by this algorithm and is implementation dependent. Implementers MUST produce a valid RTF document, as specified by [\[MSFT-RTF\]](#). Implementers MUST emit a FROMTEXT control word in the RTF header, after the \rtf1 control word, to indicate that RTF was produced from plain text. Implementers SHOULD specify a default **code page** for text runs in RTF by using the \ansicpgN control word, as specified in [\[MSFT-RTF\]](#).

Implementers can emit a font table to define fonts used in RTF. Implementers SHOULD specify charset information for each font when necessary, as specified in [\[MSFT-RTF\]](#).

Implementers MUST NOT use HTMLTAG destination groups or the FROMHTML control word in RTF content marked with the FROMTEXT control word. All textual content MUST be represented directly in RTF. Implementers SHOULD produce text in a code page that corresponds to the current font for each text run, or in a default RTF code page if no current font is selected for a text run.

Any characters that cannot be represented in a selected code page SHOULD be encoded by using the \uN control word. Any resulting characters that are not allowed or have a special meaning in RTF

syntax MUST be escaped, as specified in [MSFT-RTF]. Any line-ending character sequence (such as CRLF, CR, or LF) MUST be converted to RTF as \par or \line RTF control words. Implementers can add other formatting RTF control words that do not have textual representation (for example, to improve the presentation quality of the resulting RTF).

2.2 De-Encapsulating RTF Reader Algorithm Details

De-encapsulation enables previously encapsulated **HTML** and **plain text** content to be extracted and rendered as HTML and plain text instead of the encapsulating **RTF** content. After de-encapsulation, the HTML and plain text differ only minimally from the original HTML or plain text content.

2.2.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this algorithm. The described organization is provided to facilitate the explanation of how the algorithm behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

To properly integrate attachments with the **RTF** body, a client requires:

- A list of attachments.
- A position array that stores the \objattph locations built from the RTF body. The \objattph control word is specified in [MSFT-RTF].

These structures are necessary to combine the attachments from the **Message object** with the RTF body.

2.2.2 Initialization

The list of attachments MUST be sorted by the value of the **PidTagRenderingPosition** property ([MS-OXCMSG] section 2.2.2.16), in ascending order. Sorting the list of attachments can be accomplished when querying the contents from the **attachments table**, or from an in-memory list of attachments at some later point.

The position array MUST be cleared, making the size of the array zero.

2.2.3 Processing Rules

2.2.3.1 Recognizing RTF Containing Encapsulation

Before the **de-encapsulating RTF reader** tries to recognize the **encapsulation**, the reader SHOULD <13> ensure that the document has a valid **RTF** document heading according to [MSFT-RTF] (that is, it starts with the character sequence "{\rtf1").

The de-encapsulating RTF reader SHOULD <14> inspect no more than the first 10 RTF tokens (that is, begin group marks and control words) in the input RTF document, in sequence, starting from the beginning of the RTF document. If one of the control words is the FROMHTML control word, the de-encapsulating RTF reader SHOULD conclude that the RTF document contains an encapsulated **HTML** document and stop further inspection. If one of the control words is the FROMTEXT control word, the de-encapsulating RTF reader SHOULD conclude that the RTF document was produced from a **plain text** document and stop further inspection.

During the inspection, the de-encapsulating RTF reader SHOULD conclude that there is no encapsulated content and that this is a normal (pure) RTF document if any of the following conditions are true:

- There are any RTF tokens besides the begin group mark "{" or a control word within the first 10 tokens.
- There is no FROMHTML or FROMTEXT control word within the first 10 tokens.

2.2.3.2 Extracting Encapsulated HTML from RTF

The **de-encapsulating RTF reader** MUST parse the **RTF** document as specified in [\[MSFT-RTF\]](#). Before attempting de-encapsulation, the reader MUST first recognize the encapsulated content, as specified in section [2.2.3.1](#).

To be able to correctly convert text inside RTF, the de-encapsulating RTF reader SHOULD process control words and other information in RTF that affect the interpretation of text runs in RTF and a **code page** of such text runs. For more details about control words and text runs, see [\[MSFT-RTF\]](#). In particular, the de-encapsulating RTF reader SHOULD use the default code page, as specified in the RTF header, and it SHOULD use the code page information, as specified for each font in a font table. It also SHOULD track changes to the current font and use the appropriate code page for the currently selected font. The de-encapsulating RTF reader MUST skip other parts of the RTF header, as specified in [\[MSFT-RTF\]](#).

If the de-encapsulating RTF reader encounters an HTMLTAG destination group, it SHOULD ignore any HTMLTagParameter **HTML** fragments in an HTMLTAG control word. Any CONTENT HTML fragments inside HTMLTAG destination groups MUST be copied to a destination HTML document, as follows:

- Any RTF escapes and RTF control words that represent **Unicode** characters, as specified in section [2.1.3.1.4.2](#), MUST be converted to appropriate text and such text MUST be copied to the target HTML document. RTF escapes SHOULD be unescaped and the resulting bytes interpreted in a default RTF code page, as specified in [\[MSFT-RTF\]](#). Unicode characters produced from Unicode escapes (`\uN` control word) and other control words SHOULD be interpreted as Unicode characters.
- Any other RTF control words within a CONTENT HTML fragment inside an HTMLTAG destination group SHOULD be ignored.

Any remaining text within a CONTENT HTML fragment inside an HTMLTAG destination group MUST be copied to the target HTML document. To interpret such text, the de-encapsulating RTF reader MUST use the default RTF code page, as specified in the RTF header. For more details about code page support, see [\[MSFT-RTF\]](#).

Outside of an HTMLTAG destination group, the de-encapsulating RTF reader MUST do the following:

- Ignore and skip any text and RTF control words that are suppressed by any HTMLRTF control word other than the `\fN` control word. The de-encapsulating RTF reader SHOULD track the current font even when the corresponding `\fN` control word is inside of a fragment that is disabled with an HTMLRTF control word.
- Ignore and skip any standard RTF destination groups that do not produce visible text (such as `\colortbl` groups), except for the `\fonttbl` group. The de-encapsulating RTF reader SHOULD process a font table group and at least remember the code page that corresponds to each font.
- Ignore any ignorable destination groups (that is, groups that start with `"*`") other than the HTMLTAG destination group.
- Copy the remaining content to the target HTML document as follows:
 - Any RTF escapes and RTF keywords that represent Unicode characters MUST be converted to appropriate text, and such text MUST be copied to the target HTML document. For a complete list and syntax of such escapes and control words, see [\[MSFT-RTF\]](#). RTF escapes SHOULD be unescaped and the resulting bytes interpreted in a code page that corresponds to the current

font. Unicode characters produced from Unicode escapes (\uN control word) and other control words SHOULD be interpreted as Unicode characters.

- Any \par and \line RTF control words MUST be converted to CRLF and such CRLF sequences MUST be copied to the target HTML document.
- Any \tab RTF control words MUST be converted to the horizontal tab (%x09) character, and such characters MUST be copied to the target HTML document.
- Any other RTF control words SHOULD be ignored.
- Any remaining text MUST be copied to the target HTML document. Text SHOULD be interpreted in a code page that corresponds to the currently selected font.

2.2.3.3 Extracting Original Plain Text from RTF

The **de-encapsulating RTF reader** MUST parse the **RTF** document as specified in [\[MSFT-RTF\]](#). Before trying de-encapsulation, it MUST first recognize the encapsulated content, as specified in section [2.2.3.1](#).

To be able to correctly convert text inside RTF, the de-encapsulating RTF reader SHOULD process control words and other information in RTF that affect the interpretation of text runs in RTF and a **code page** of such text runs. For more details about code page support, see [\[MSFT-RTF\]](#). In particular, the de-encapsulating RTF reader SHOULD use the default code page, as specified in the RTF header, and it SHOULD use the code page information, as specified for each font in a font table. It SHOULD also track changes of a current font by following RTF text, and use the appropriate code page for the currently selected font. The de-encapsulating RTF reader MUST skip other parts of the RTF header, as specified in [\[MSFT-RTF\]](#).

The de-encapsulating RTF reader MUST examine each control token, translate it to its textual equivalent, and emit it to the output stream. Any RTF formatting control words that do not have a textual representation MUST be ignored.

Individual textual characters can be escaped by RTF and these SHOULD be converted to their character equivalents and emitted to the output stream (for example: "\{", "\}", "\\", and "\'HH"). After unescaping, the resulting bytes SHOULD be interpreted in a code page that corresponds to the currently selected font. **Unicode** characters produced from Unicode escapes (\uN control word) and other control words SHOULD be interpreted as Unicode characters.

The \par and \line RTF control words SHOULD be translated to CRLF and emitted to the output stream.

The \tab control word SHOULD be translated to the horizontal tab (%x09) character, and such character SHOULD be emitted to the output stream.

Any remaining text MUST be copied to the target **plain text** document. Text SHOULD be interpreted in a code page that corresponds to the currently selected font.

2.2.3.4 Attachment and RTF Integration

To integrate **Attachment objects** into an **RTF** body, the list of Attachment objects to integrate MUST be retrieved from the **attachments table**, as specified in [\[MS-OXCMSG\]](#) section 3.1.4.17. The attachment list MUST only include those Attachment objects that have a **PidTagAttachmentHidden** property ([\[MS-OXCMSG\]](#) section 2.2.2.24) whose value is equal to FALSE (0x00) or non-existent, and a **PidTagRenderingPosition** property ([\[MS-OXCMSG\]](#) section 2.2.2.16) whose value is not equal to 0xFFFFFFFF.

When the RTF reader is parsing RTF and it encounters an \objattph control word, it SHOULD add a new instance to the position array. The position array stores the location in the data stream where the

object belongs. This location can be represented as the number of characters from the beginning of the rendered content.

After the RTF reader has finished parsing the entire RTF content and populating the position array, sufficient information is available to complete the integration process. The number of values in the position array SHOULD be compared to the number of values in the attachments list (retrieved from the attachments table). If the number of values does not match, the RTF reader ignores the locations specified in the position array and uses the data provided in the attachment list. This can be accomplished by emptying the position array. Any extra attachments SHOULD be inserted at the end of the rendered RTF, or MAY [<15>](#) be inserted using the **rendering position** stored in the **PidTagRenderingPosition** property ([MS-OXCMSG] section 2.2.2.16) of the attachment.

The attachment list and the position array SHOULD be enumerated in lock step. For each instance, if a value exists in the position array, the location specified in the position array SHOULD be used as the insert location.

The next step is to prepare the attachment for insertion. The preparations necessary for insertion of an object will vary depending on the RTF reader. For more information, an implementer should consult the documentation associated with their RTF reader.

After it is prepared, the location specified for the Attachment object SHOULD be selected. If the location in the position array is greater than the number of rendered characters in the body, the insert [<16>](#) location is set to the end of the rendered RTF body. That location is then replaced with the prepared Attachment object.

At this point, the insertion is complete, and the RTF reader moves to the next attachment in sequential order, and to the next entry in the position array.

As specified earlier in this section, if there are not sufficient instances in the position array, any remaining attachments in the attachments list SHOULD be appended to the end of the RTF body, or MAY [<17>](#) be inserted using the rendering position stored in the **PidTagRenderingPosition** property of the attachment. If there are extra values in the position array, RTF readers SHOULD simply ignore rendering them, as specified in [\[MSFT-RTF\]](#).

For an example of attachment integration, see section [3.2](#).

3 Algorithm Examples

3.1 Encapsulating HTML into RTF

Having the following source **HTML** content:

```
<HTML><head>
<style>
<!--
  /* Style Definitions */
  p.MsoNormal, li.MsoNormal {font-family:Arial;}
-->
</style>
<!-- This is a HTML comment.
There is a horizontal tab (%x09) character before the comment,
and some new lines inside the comment. -->
</head>
<body>
<p
class="MsoNormal">Note the line break inside a P tag. <b>This is bold text</b> </p>
<p class="MsoNormal">
This is a normal text with a character references: &nbsp; &lt; &uml;<br>
characters that have special meaning in RTF: {}<br>
</p>
<ol>
<li class="MsoNormal">This is a list item
</li>
</ol>
</body>
</HTML>
```

An **encapsulating RTF writer** can (by conforming to this algorithm) produce the following **RTF**:

```
{\rtf1\ANSI\ansicpg1251\fromhtml1 \def0
{\fonttbl {\f0\modern Courier New;}{\f1\fswiss Arial;}{\f2\fswiss\fcharset0 Arial;}}
{\colortbl\red0\green0\blue0;\red0\green0\blue255;}
{\*\htmltag64}
\uc1\pard\plain\deftab360 \f0\fs24
{\*\htmltag <HTML><head>\par
<style>\par
<!--\par
  /* Style Definitions */\par
  p.MsoNormal, li.MsoNormal {\font-family:Arial;}\par
-->\par
</style>\par
\tab <!-- This is a HTML comment.\par
There is a horizontal tab (%x09) character before the comment, \par
and some new lines inside the comment. -->\par
</head>\par
<body>\par
<p\par
class="MsoNormal">}
{\htmlrtf \f1 \htmlrtf0 Note the line break inside a P tag. {\*\htmltag <b>}{\htmlrtf \b
\htmlrtf0 This is a bold text{\*\htmltag </b>}} \htmlrtf\par\htmlrtf0}
\htmlrtf \par \htmlrtf0
{\*\htmltag </p>\par
<p class="MsoNormal">\par}
{\htmlrtf \f1 \htmlrtf0 This is a normal text with a character references:
{\*\htmltag &nbsp;}\htmlrtf \'a0\htmlrtf0 {\*\htmltag &lt;}\htmlrtf <\htmlrtf0 {\*\htmltag
&uml;}\htmlrtf {\f2\'a8}\htmlrtf0{\*\htmltag <br>\par}\htmlrtf\line\htmlrtf0
characters which have special meaning in RTF: {\}\{\*\htmltag
<br>\par}\htmlrtf\line\htmlrtf0\htmlrtf\par\htmlrtf0}
{\*\htmltag </p>\par
<ol>\par
```

```

<li class="MsoNormal">{\htmlrtf
{{\*\pn\pnlvlbody\pndec\pnstart1\pnindent360{\pntxta.}}\li360\fi-360{\pntext 1.\tab} \f1
\htmlrtf0 This is a list item}\htmlrtf\par\htmlrtf0}
{\*\htmltag \par
</ol>\par
</body>\par
</HTML>\par }}

```

A **de-encapsulating RTF reader** can recover the original HTML document from the RTF example in this section by conforming to this algorithm.

3.2 Integrating Sample Attachments and RTF

A user has just received a piece of e-mail that they would like to open and read. The following is a description of what a client might do to accomplish the user's intentions and the responses that a server might return.

The user opens the **Message object** by using the **RopOpenMessage remote operation (ROP)** ([MS-OXCROPS] section 2.2.6.1) for an e-mail message that just arrived. It was sent with the message ID and folder ID described in the following table.

Property name	Property ID	Data type	Data
PidTagFolderId ([MS-OXCFOLD] section 2.2.2.2.1.6)	0x6748	PtypInteger64 ([MS-OXCDATA] section 2.11.1)	0xBFE7F00000000001
PidTagMid ([MS-OXCFXICS] section 2.2.1.2.1)	0x674A	PtypInteger64	0x95D9690100000001

The body properties are retrieved to determine which body format is appropriate to load, as described in [MS-OXBBODY]. The client sends a **RopGetPropertiesSpecific ROP request** ([MS-OXCROPS] section 2.2.8.3) and the server responds with the information described in the following table.

Property name	Property ID	Data type	Data	Value
PidTagRtfInSync ([MS-OXCMSG] section 2.2.1.56.5)	0x00E01F	PtypBoolean ([MS-OXCDATA] section 2.11.1)	0x0001	True

Property name	Property ID	Data type	Data	Value
)		
PidTagBody ([MS - OXC MSG] section 2.2.1.56.1)	0x11000	PtyperCode ([MS-OXCDATA] section 2.1.1)	0x8007000e	NotEnoughMemory
PidTagBodyHtm ([MS - OXC MSG] section 2.2.1.56.3)	0x11013	PtyperCode	0x8004010f	NotFound
PidTagRtfCompound ([MS - OXC MSG] section 2.2.1.56.4)	0x11019	PtyBinary ([MS-OXCDATA] section 2.1.1)	261 By s 01 01 00 00 53 01 00 4C 5A 46 75 69 B3	{\rtf1\ANSI\ansicpg1252\deff0\deflang1033{\fonttbl{\f0\fswiss\charset0 Arial;}}<CR><LF>{*\generator<SP>Riched20<SP>5.50.99.2050;} \viewkind4\uc1\pard\fs20<SP>This<SP>is<SP>a<SP>test<SP>email. \par<CR><LF>\objattph\20\par<CR><LF>\par{*\optional<SP>with<SP>an<SP>optional<SP>line\par}<CR><LF>Lets<SP>have<SP>another<SP>attachment\par<CR><LF>\objattph\20\par<CR><LF>\par<CR><LF>Adding<SP>a<SP>picture\par<CR><LF>\objattph\20\par<CR><LF>}

Property name	Property ID	Data type	Data	Value
			B7	<div data-bbox="224 426 1367 1549" data-label="Text"> <p style="font-size: 48px; opacity: 0.3; transform: rotate(-30deg);">Preliminary</p> </div>
			69	
			03	
			00	
			0A	
			00	
			72	
			63	
			70	
			67	
			31	
			32	
			35	
			16	
			32	
			00	
			F8	
			0B	
			60	
			6E	
			0E	
			10	
			30	
			33	
			33	
			4F	
			01	
			F7	
			02	
			A4	
			03	
			E3	
			02	
			00	
			63	
			68	
			0A	
			C0	
			73	
			B0	
			65	
			74	
			30	
			20	
			07	
			13	
			02	
			80	
			7D	
			0A	
			80	
			9D	
			00	
			00	
			2A	

Property name	Property ID	Data type	Data	Value
			09	<div data-bbox="224 428 1367 1549" data-label="Text"> <p>Preliminary</p> </div>
			B0	
			09	
			F0	
			04	
			90	
			61	
			74	
			05	
			B1	
			1A	
			52	
			0D	
			E0	
			68	
			09	
			80	
			01	
			D0	
			20	
			35	
			2E	
			C0	
			35	
			30	
			2E	
			39	
			39	
			2E	
			01	
			D0	
			13	
			A0	
			49	
			02	
			80	
			5C	
			76	
			08	
			90	
			77	
			6B	
			0B	
			80	
			64	
			3A	
			34	
			0C	
			60	
			63	
			00	
			50	
			0B	
			03	
			0B	

Property name	Property ID	Data type	Data	Value
			B5	<div data-bbox="219 420 1372 1554" data-label="Text"> <p>Preliminary</p> </div>
			20	
			54	
			8A	
			68	
			04	
			00	
			20	
			16	
			41	
			61	
			20	
			74	
			07	
			90	
			6D	
			05	
			40	
			65	
			00	
			C0	
			03	
			10	
			2E	
			0A	
			A2	
			0A	
			81	
			6F	
			04	
			62	
			6A	
			12	
			A0	
			74	
			70	
			68	
			5C	
			27	
			AF	
			0C	
			01	
			17	
			84	
			0A	
			B1	
			12	
			12	
			6F	
			05	
			30	
			69	
			02	
			20	
			E5	

Property name	Property ID	Data type	Data	Value
			07	<div data-bbox="224 428 1367 1549" data-label="Text"> <p>Preliminary</p> </div>
			40	
			20	
			03	
			F0	
			74	
			68	
			16	
			90	
			03	
			A0	
			19	
			87	
			D	
			A	
			6C	
			0B	
			80	
			65	
			0A	
			A2	
			11	
			E1	
			4C	
			11	
			30	
			04	
			20	
			E9	
			10	
			F0	
			76	
			65	
			1A	
			51	
			6F	
			1A	
			30	
			04	
			90	
			16	
			90	
			FB	
			02	
			40	
			00	
			D0	
			68	
			07	
			80	
			02	
			30	
			17	
			7F	
			18	

Property name	Property ID	Data type	Data	Value
			8A 0A 80 A8 41 64 64 0B 80 67 16 91 70 0D E0 5E 74 08 70 1B 53 1D DF 20 A2 7D 22 20	

Based on the server responses, the proper body to load is the value of the **PidTagRtfCompressed** property.

The **PidTagRtfCompressed** property is stored in a packed format; by using the RTF Compression Algorithm, as described in [\[MS-OXRTFCPI\]](#), the content is decoded and the raw **RTF** is as follows:

```
{\rtf1\ANSI\ansicpg1252\deff0\deflang1033{\fonttbl{\f0\fswiss\fcharset0
Arial;}}<CR><LF>{\*\generator<SP>Riched20<SP>5.50.99.2050;}\viewkind4\ucl\pard\f0\fs20<SP>Thi
s<SP>is<SP>a<SP>test<SP>e-
mail.\par<CR><LF>\objattph\'20\par<CR><LF>\par{\*\optional<SP>with<SP>an<SP>optional<SP>line\
par}<CR><LF>Lets<SP>have<SP>another<SP>attachment\par<CR><LF>\objattph\'20\par<CR><LF>\par<CR
><LF>Adding<SP>a<SP>picture\par<CR><LF>\objattph\'20\par<CR><LF>}
```

This algorithm is then used to determine whether the RTF is encapsulated by examining the RTF tokens before the font table destination. Because the FROMHTML and FROMTEXT control words are not found in the RTF header, the contents are not encapsulated.

As the body is loaded and the RTF reader parses the RTF, the render position of each \objattph token is calculated and stored in an array similar to that which is described in the following table.

Position array
22
54
74

Note There is an optional destination (\optional) that is not understood by the RTF reader. This affects the rendered token locations, as the contents "with an optional line < CRLF >" are not rendered.

When the body parsing is complete and the existence of placeholder tokens is recorded, the attachments from the message are loaded.

The following ROP requests are transmitted to the server:

- The **RopGetAttachmentTable** ROP ([MS-OXCROPS] section 2.2.6.17).
- The **RopSetColumns** ROP ([MS-OXCROPS] section 2.2.5.1), which requests the **PidTagAttachNumber** ([MS-OXCMSG] section 2.2.2.6), **PidTagAttachMethod** ([MS-OXCMSG] section 2.2.2.9), **PidTagRenderingPosition** ([MS-OXCMSG] section 2.2.2.16), **PidTagAttachLongFilename** ([MS-OXCMSG] section 2.2.2.10), and **PidTagAttachmentHidden** ([MS-OXCMSG] section 2.2.2.24) properties.
- The **RopQueryRows** ROP ([MS-OXCROPS] section 2.2.5.4).

The response buffer from the **RopQueryRows** ROP contains three rows, as described in the following three tables.

Row 1

Property name	Property ID	Data type	Data	Value
PidTagAttachNumber	0x0E21	PtypInteger32 ([MS-OXCDATA] section 2.11.1)	0x00000000	0
PidTagAttachMethod	0x3705	PtypInteger32	0x00000001	afByValue
PidTagRenderingPosition	0x370B	PtypInteger32	0x00000016	22
PidTagAttachLongFilename	0x3707	PtypString ([MS-OXCDATA] section 2.11.1)	00 68 00 65 00 6C 00 6C 00 6F 00 77 00 6F 00 72 00 6C 00 64 00 2E 00 74 00 78 00 74 00 00 00 00	"helloworld.txt"
PidTagAttachmentHidden	0x7FFE	PtypBoolean	0x0000	FALSE

Row 2

Property name	Property ID	Data type	Data	Value
PidTagAttachNumber	0x0E21	PtypInteger32	0x00000001	0
PidTagAttachMethod	0x3705	PtypInteger32	0x00000001	afByValue
PidTagRenderingPosition	0x370B	PtypInteger32	0x00000036	76
PidTagAttachLongFilename	0x3707	PtypString	00 68 00 65 00 6C 00 6C 00 6F 00 77 00 6F 00 72 00 6C	"helloworld.doc"

Property name	Property ID	Data type	Data	Value
			00 64 00 2E 00 64 00 6F 00 63 00 00 00 00	
PidTagAttachmentHidden	0x7FFE	PtypBoolean	0x0000	FALSE

Row 3

Property name	Property ID	Data type	Data	Value
PidTagAttachNumber	0x0E21	PtypInteger32	0x00000002	0
PidTagAttachMethod	0x3705	PtypInteger32	0x00000006	afOle
PidTagRenderingPosition	0x370B	PtypInteger32	0x0000004A	100
PidTagAttachLongFilename	0x3707	PtypString	00 50 00 42 00 72 00 75 00 73 00 68 00 00 00 00	"PBrush"
PidTagAttachmentHidden	0x7FFE	PtypBoolean	0x0000	FALSE

Because the attachments are already ordered correctly by **rendering position**, they do not need to be reordered.

Because the attachment list is three entries long, and the previously constructed position array is also three entries long, the insertion positions come from the position array. This results in replacing the second and third attachments at different positions than those set in the value of the **PidTagRenderingPosition** property. Specifically, the second attachment ("helloworld.doc") will replace position 54, not 76, and the third attachment will replace position 74, not 100.

Looping over the stored objattph positions in the position array, each attachment is prepared for insertion.

The first attachment ("helloworld.txt") replaces rendered character position 22. The second attachment ("helloworld.doc") replaces the rendered character position 54. Finally, the last attachment ("PBrush") replaces the rendered character position 74.

Because there are no additional attachments, the integration is complete.

4 Security

4.1 Security Considerations for Implementers

Because the **encapsulation** algorithm involves parsing and evaluating content that is not created by the algorithm, there is an opportunity for non-valid or malicious content to be provided. Therefore, it is recommended that implementers take all necessary precautions to protect other systems. For example, a linked **HTML** stylesheet (which would create a better HTML rendering of the document) might not be loaded due to security concerns with accessing the network to retrieve non-local data. In this case, a default font face and size might be chosen during the conversion process.

The encapsulation process could encapsulate carefully crafted arbitrary binary content other than valid HTML or **plain text**. Ensuring that such content is not accidentally and automatically interpreted as executable code or script is imperative.

4.2 Index of Security Parameters

None.

5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Microsoft Exchange Server 2003
- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Exchange Server 2016
- Microsoft Exchange Server 2019
- Microsoft Office Outlook 2003
- Microsoft Office Outlook 2007
- Microsoft Outlook 2010
- Microsoft Outlook 2013
- Microsoft Outlook 2016
- Microsoft Outlook 2019
- Microsoft Outlook 2021

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

[<1> Section 2.1](#): Exchange 2013, Exchange 2016, and Exchange 2019 do not emit **RTF**-encapsulated **HTML**.

[<2> Section 2.1.3.1.2](#): Exchange 2013, Exchange 2016, and Exchange 2019 do not emit the FROMHTML control word because the RTF writer in those versions does not produce RTF-encapsulated HTML.

[<3> Section 2.1.3.1.3](#): Exchange 2013, Exchange 2016, and Exchange 2019 do not emit the HTMLRTF control word because the RTF writer in those versions does not produce RTF-encapsulated HTML.

[<4> Section 2.1.3.1.4](#): Exchange 2013, Exchange 2016, and Exchange 2019 do not emit the HTMLTAG destination group because the RTF writer in those versions does not produce RTF-encapsulated HTML.

[<5> Section 2.1.3.1.4.1](#): The HTMLTagParameter HTML fragment is emitted by Exchange 2003, Exchange 2007, Exchange 2010, Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Outlook 2016, and Outlook 2019.

<6> [Section 2.1.3.1.4.2](#): Exchange 2013, Exchange 2016, and Exchange 2019 do not emit the CONTENT HTML fragment because the RTF writer in those versions does not produce RTF-encapsulated HTML.

<7> [Section 2.1.3.1.4.2](#): Exchange 2003, Office Outlook 2003, Office Outlook 2007, Microsoft Outlook 2010, Outlook 2013, Outlook 2016, and Outlook 2019 fail to de-encapsulate the RTF document when \line, \-, and other arbitrary RTF tokens are included in the CONTENT HTML fragment.

<8> [Section 2.1.3.1.5](#): While an MHTMLTAG destination group can be produced by Exchange 2003, Exchange 2007, or Exchange 2010, it is to be ignored. Any content encapsulated in an MHTMLTAG destination group represents a rewritten version of content encapsulated (in its original format) in another HTMLTAG destination group; thus, an MHTMLTAG destination group can be safely ignored.

<9> [Section 2.1.3.2](#): Exchange 2003, Exchange 2007, Exchange 2010 support writing RTF-encapsulated HTML.

<10> [Section 2.1.3.2](#): This empty {*\htmltag64} destination group disables deprecated behavior in Exchange 2003, Exchange 2007, Exchange 2010, Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Outlook 2016, and Outlook 2019.

<11> [Section 2.1.3.2](#): It is possible that Exchange 2003, Exchange 2007, Exchange 2010, Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Outlook 2016, and Outlook 2019 will produce the HTMLTagParameter HTML fragment for legacy reasons.

<12> [Section 2.1.3.2](#): Exchange 2003, Exchange 2007, Exchange 2010, Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Outlook 2016, and Outlook 2019 can produce unexpected HTML tags that were not in the original HTML document in response to character formatting RTF control words that are not disabled with the HTMLRTF control word. To avoid this deprecated behavior, it is best to disable any control words that affect current character formatting in RTF by using HTMLRTF control word. For a list of all RTF control words that can affect character formatting, see [\[MSFT-RTF\]](#). If in doubt about any particular control word, disable it by wrapping it with HTMLRTF control words, as specified in section [2.1.3.1.3](#).

<13> [Section 2.2.3.1](#): Exchange 2003, Exchange 2007, Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Outlook 2016, and Outlook 2019 ignore the absence of the \rtf1 keyword at the beginning of the RTF encoded text and try to de-encapsulate the text anyway. Exchange 2010, Exchange 2013, Exchange 2016, and Exchange 2019 can ignore the absence of the \rtf1 keyword and tries to de-encapsulate the text in certain implementation-specific scenarios.

<14> [Section 2.2.3.1](#): Exchange 2003, Exchange 2007, Exchange 2010, Exchange 2013, Exchange 2016, Exchange 2019, Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013 (in some scenarios), Outlook 2016 (in some scenarios), and Outlook 2019 (in some scenarios) could be able to recognize encapsulation by looking beyond 10 tokens. In most cases, Exchange 2007, Exchange 2010, Exchange 2013, Exchange 2016, and Exchange 2019 limit inspection to the first 10 tokens; therefore, this is a recommendation. Exchange 2003, Exchange 2007, Exchange 2010, Exchange 2013, Exchange 2016, Exchange 2019, Office Outlook 2003, Office Outlook 2007, Outlook 2010, Outlook 2013, Outlook 2016, and Outlook 2019 do not produce the \fromhtml1 or \fromtext keywords outside of the first 10 tokens of RTF.

<15> [Section 2.2.3.4](#): Office Outlook 2003 uses the **rendering position** stored in the **PidTagRenderingPosition** property of the attachment for extra attachments.

<16> [Section 2.2.3.4](#): "Insertion" and "replacement" are used as general terms. Other RTF readers might use a different mechanism for which these terms might seem inappropriate.

<17> [Section 2.2.3.4](#): Office Outlook 2003 uses the rendering position stored in the **PidTagRenderingPosition** property of the attachment for extra attachments.

6 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Description	Revision class
5 Appendix A: Product Behavior	Updated list of supported products.	major

7 Index

A

[Applicability](#) 9

C

[Change tracking](#) 33

D

De-Encapsulating RTF Reader

abstract data model

Abstract Data Model

[De-Encapsulating RTF Reader](#) 16

initialization

Initialization

[De-Encapsulating RTF Reader](#) 16

[overview](#) 16

De-Encapsulating RTF Reader - processing rules

[attachment and RTF integration](#) 18

[extracting encapsulated HTML from RTF](#) 17

[extracting original plain text from RTF](#) 18

[recognizing RTF containing encapsulation](#) 16

E

[Encapsulating HTML into RTF example](#) 20

Encapsulating RTF Writer

[overview](#) 10

Encapsulating RTF Writer - processing rules

[encoding HTML into RTF](#) 15

[encoding plain text into RTF](#) 15

[HTML and plain text syntax](#) 10

Examples

[Encapsulating HTML into RTF](#) 20

[Integrating Sample Attachments and RTF](#) 21

G

[Glossary](#) 6

I

[Implementer - security considerations](#) 30

[Index of security parameters](#) 30

[Informative references](#) 8

[Integrating Sample Attachments and RTF example](#)
21

[Introduction](#) 6

N

[Normative references](#) 7

O

[Overview \(synopsis\)](#) 8

P

[Parameters - security index](#) 30

Processing rules - de-encapsulating RTF Reader

[attachment and RTF integration](#) 18

[extracting encapsulated HTML from RTF](#) 17

[extracting original plain text from RTF](#) 18

[recognizing RTF containing encapsulation](#) 16

Processing rules - encapsulating RTF Writer

[encoding HTML into RTF](#) 15

[encoding plain text into RTF](#) 15

[HTML and plain text syntax](#) 10

[Product behavior](#) 31

R

References

[informative](#) 8

[normative](#) 7

Relationship to

other protocols

Relationship to

[other algorithms](#) 9

S

Security

[implementer considerations](#) 30

[parameter index](#) 30

[Standards assignments](#) 9

T

[Tracking changes](#) 33