

# [MS-OXSHARE]: Sharing Message Object Protocol Specification

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

| Date       | Revision History | Revision Class | Comments  |
|------------|------------------|----------------|---|
| 04/04/2008 | 0.1              |                | Initial Availability.   |
| 04/25/2008 | 0.2              |                | Revised and updated property names and other technical content.               |
| 06/27/2008 | 1.0              |                | Initial Release.  |
| 08/06/2008 | 1.01             |                | Revised and edited technical content.   |
| 12/02/2009 | 1.02             |                | Updated references.   |
| 12/03/2008 | 1.03             |                | Updated IP notice.  |
| 04/10/2009 | 2.0              |                | Updated technical content and applicable product releases.                    |
| 07/15/2009 | 3.0              | Major          | Revised and edited for technical content.                                     |
| 11/04/2009 | 3.0.1            | Editorial      | Revised and edited the technical content.                                     |
| 02/10/2010 | 3.0.1            | None           | Version 3.0.1 release   |
| 05/05/2010 | 3.0.2            | Editorial      | Revised and edited the technical content.                                     |
| 08/04/2010 | 3.1              | Minor          | Clarified the meaning of the technical content.                               |
| 11/03/2010 | 4.0              | Major          | Significantly changed the technical content.                                  |
| 03/18/2011 | 4.0              | No change      | No changes to the meaning, language, and formatting of the technical content. |
| 08/05/2011 | 4.0              | No change      | No changes to the meaning, language, or formatting of the technical content.  |
| 10/07/2011 | 4.0              | No change      | No changes to the meaning, language, or formatting of the technical content.  |

# Table of Contents

|  |          |
|--|----------|
| <b>1 Introduction .....</b>                          | <b>5</b> |
| 1.1 Glossary .....                                   | 5        |
| 1.2 References .....                                 | 6        |
| 1.2.1 Normative References .....                     | 6        |
| 1.2.2 Informative References .....                   | 6        |
| 1.3 Overview .....                                   | 6        |
| 1.4 Relationship to Other Protocols .....            | 7        |
| 1.5 Prerequisites/Preconditions .....                | 7        |
| 1.6 Applicability Statement .....                    | 7        |
| 1.7 Versioning and Capability Negotiation .....      | 7        |
| 1.8 Vendor-Extensible Fields .....                   | 7        |
| 1.9 Standards Assignments .....                      | 7        |
| <b>2 Messages.....</b>                               | <b>8</b> |
| 2.1 Transport.....                                   | 8        |
| 2.2 Message Syntax .....                             | 8        |
| 2.2.1 Common Message Object Properties .....         | 8        |
| 2.2.1.1 PidTagNormalizedSubject Property .....       | 8        |
| 2.2.1.2 PidTagSubjectPrefix Property .....           | 9        |
| 2.2.2 Common Sharing Message Object Properties ..... | 9        |
| 2.2.2.1 PidLidSharingCapabilities Property .....     | 9        |
| 2.2.2.2 PidNameXSharingCapabilities Property .....   | 9        |
| 2.2.2.3 PidLidSharingConfigurationUrl Property ..... | 9        |
| 2.2.2.4 PidNameXSharingConfigUrl Property .....      | 9        |
| 2.2.2.5 PidLidSharingFlavor Property .....           | 9        |
| 2.2.2.6 PidNameXSharingFlavor Property .....         | 10       |
| 2.2.2.7 PidLidSharingInitiatorEntryId Property ..... | 10       |
| 2.2.2.8 PidLidSharingInitiatorName Property .....    | 10       |
| 2.2.2.9 PidLidSharingInitiatorSmtp Property .....    | 10       |
| 2.2.2.10 PidLidSharingLocalType Property .....       | 10       |
| 2.2.2.11 PidNameXSharingLocalType Property .....     | 11       |
| 2.2.2.12 PidLidSharingProviderGuid Property .....    | 11       |
| 2.2.2.13 PidNameXSharingProviderGuid Property .....  | 11       |
| 2.2.2.14 PidLidSharingProviderName Property .....    | 11       |
| 2.2.2.15 PidNameXSharingProviderName Property .....  | 11       |
| 2.2.2.16 PidLidSharingProviderUrl Property .....     | 11       |
| 2.2.2.17 PidNameXSharingProviderUrl Property .....   | 12       |
| 2.2.3 Sharing Request Properties .....               | 12       |
| 2.2.3.1 PidLidSharingResponseTime Property .....     | 12       |
| 2.2.3.2 PidLidSharingResponseType Property .....     | 12       |
| 2.2.4 Sharing Invitation Properties .....            | 12       |
| 2.2.4.1 PidLidSharingRemoteName Property .....       | 12       |
| 2.2.4.2 PidNameXSharingRemoteName Property .....     | 12       |
| 2.2.4.3 PidLidSharingRemoteStoreUid Property .....   | 13       |
| 2.2.4.4 PidNameXSharingRemoteStoreUid Property ..... | 13       |
| 2.2.4.5 PidLidSharingRemoteType Property .....       | 13       |
| 2.2.4.6 PidNameXSharingRemoteType Property .....     | 13       |
| 2.2.4.7 PidLidSharingRemoteUid Property .....        | 13       |
| 2.2.4.8 PidNameXSharingRemoteUid Property .....      | 13       |
| 2.2.5 Ignored Properties .....                       | 13       |

|          |   |           |
|----------|---|-----------|
| 2.2.6    | Additional Property Constraints .....               | 15        |
| 2.2.6.1  | PidNameContentClass Property.....                   | 15        |
| 2.2.6.2  | PidTagMessageClass Property.....                    | 15        |
| <b>3</b> | <b>Protocol Details .....</b>                       | <b>16</b> |
| 3.1      | Client Details.....                                 | 16        |
| 3.1.1    | Abstract Data Model .....                           | 16        |
| 3.1.2    | Timers .....  | 16        |
| 3.1.3    | Initialization .....                                | 16        |
| 3.1.4    | Higher-Layer Triggered Events .....                 | 16        |
| 3.1.4.1  | Creating a Sharing Invitation .....                 | 16        |
| 3.1.4.2  | Creating a Sharing Request.....                     | 18        |
| 3.1.4.3  | Creating a Sharing Response – Accept .....          | 19        |
| 3.1.4.4  | Creating a Sharing Response – Deny.....             | 21        |
| 3.1.5    | Message Processing Events and Sequencing Rules..... | 23        |
| 3.1.6    | Timer Events .....                                  | 23        |
| 3.1.7    | Other Local Events .....                            | 23        |
| <b>4</b> | <b>Protocol Examples.....</b>                       | <b>24</b> |
| 4.1      | Sending a Sharing Request .....                     | 26        |
| 4.2      | Denying a Sharing Request .....                     | 28        |
| 4.3      | Accepting a Sharing Request.....                    | 30        |
| <b>5</b> | <b>Security.....</b>                                | <b>34</b> |
| 5.1      | Security Considerations for Implementers.....       | 34        |
| 5.2      | Index of Security Parameters .....                  | 34        |
| <b>6</b> | <b>Appendix A: Product Behavior.....</b>            | <b>35</b> |
| <b>7</b> | <b>Change Tracking.....</b>                         | <b>37</b> |
| <b>8</b> | <b>Index .....</b>                                  | <b>38</b> |

# 1 Introduction

The Sharing Message Object Protocol specifies the format of messages that enable a user to communicate status about the sharing of folders.

This document specifies the following:

- The message format used to inform users that they have been granted access to another user's folder and provide the information necessary to locate that folder.
- The message format used to request access to a user's folder.
- The message format used to respond to requests for access to a folder.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**big-endian**  
**handle**

The following terms are defined in [\[MS-OXGLOS\]](#):

**Address Book object**  
**Message object**  
**named property**  
**property ID**  
**recipient**  
**remote operation (ROP)**  
**restriction**  
**special folder**  
**Uniform Resource Locator (URL)**

The following terms are specific to this document:

**sharing invitation:** A type of Sharing Message object that informs a user that the user was granted access to another user's folder and provides the information necessary to locate that folder.

**Sharing Message object:** A Message object that is used to inform a recipient that they were granted access to another user's folder, request access to a recipient's folder, or respond to a request for access to a folder.

**sharing provider:** A software agent that is responsible for properly generating and processing a predefined Sharing Message object format.

**sharing request:** A type of Sharing Message object that is used to request access to a user's folder.

**sharing response:** A type of Sharing Message object that is used to respond to a sharing request.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

- [MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".
  - [MS-OXCOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)".
  - [MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)".
  - [MS-OXCPERM] Microsoft Corporation, "[Exchange Access and Operation Permissions Protocol Specification](#)".
  - [MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)".
  - [MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol Specification](#)".
  - [MS-OXODLGT] Microsoft Corporation, "[Delegate Access Configuration Protocol Specification](#)".
  - [MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)".
  - [MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol Specification](#)".
  - [MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)".
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

### 1.2.2 Informative References

- [MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".
- [MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)".
- [MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

## 1.3 Overview

The Sharing Message Object Protocol allows for the representation of a communication related to sharing a folder. It extends the Message and Attachment Object Protocol in that it defines new properties and adds **restrictions** to the properties that are specified in [\[MS-OXCMSG\]](#).

The Sharing Message Object Protocol specifies the format and semantics of the **Sharing Message object**. The properties that are specific to a Sharing Message object facilitate communication about granting access to a folder, requesting access to a folder, or responding to a request for access to a folder

## **1.4 Relationship to Other Protocols**

This specification extends the Message and Attachment Object Protocol specified in [\[MS-OXCMSG\]](#) and relies on an understanding of how to work with properties, folders, and **special folders** which are specified in [\[MS-OXCPRT\]](#), [\[MS-OXCFOLD\]](#), and [\[MS-OXOSFLD\]](#). It also uses the E-mail Object Protocol specified in [\[MS-OXOMSG\]](#) for message submission and delivery.

## **1.5 Prerequisites/Preconditions**

The Sharing Message Object Protocol has the same prerequisites and preconditions as specified in [\[MS-OXCMSG\]](#) and [\[MS-OXOMSG\]](#).

## **1.6 Applicability Statement**

The Sharing Message Object Protocol can be used to notify another user that access has been granted to a folder. This protocol can also be used to request access to a folder and to respond to such requests.

The Sharing Message Object Protocol cannot be used to convey information about any type of object other than folders.

## **1.7 Versioning and Capability Negotiation**

None.

## **1.8 Vendor-Extensible Fields**

This protocol provides no vendor-extensibility beyond what is specified in [\[MS-OXCMSG\]](#).

## **1.9 Standards Assignments**

None.

## 2 Messages

### 2.1 Transport

The Sharing Message Object Protocol uses the protocols specified in [\[MS-OXCPRPT\]](#) and [\[MS-OXCMSG\]](#) as its primary transport mechanism.

### 2.2 Message Syntax

A Sharing Message object can be created and modified by clients and servers. Except where noted, this section defines constraints under which both clients and servers operate.

Clients operate on Sharing Message objects by using the E-mail Object Protocol specified in [\[MS-OXOMSG\]](#) and the Message and Attachment Object Protocol specified in [\[MS-OXCMSG\]](#). How a server operates on Sharing Message objects is implementation-dependent. The results of any such operation are exposed to clients in a manner that is consistent with the Sharing Object Protocol.

Unless otherwise specified, a Sharing Message object adheres to all property constraints specified in [\[MS-OXPROPS\]](#) and all property constraints specified in [\[MS-OXCMSG\]](#). A Sharing Message object can also contain other properties specified in [\[MS-OXPROPS\]](#), but these properties have no effect on the Sharing Message Object Protocol.

Where a string value is specified as a hexadecimal string representation of a binary value, the string value is a sequence of hexadecimal digits that reflect the byte sequence of the binary value. For example, the string "00000000DCA740C8" is the hexadecimal string representation of the following byte sequence:

```
0000 00 00 00 00 dc a7 40 c8
```

Where a string value is specified as a hexadecimal string representation of an integer value, the string value is a sequence of hexadecimal digits that reflect the integer value in **big-endian** format, without an "0x" prefix, and without leading "0" characters. For example, the hexadecimal string representation of the integer 0x0000010B would be "10B".

Sharing Message object properties can be of several different data types. The following data types used by Sharing Message object properties are specified in [\[MS-OXCDATA\]](#) section 2.11.1:

- PtypBinary
- PtypInteger32
- PtypString
- PtypTime

#### 2.2.1 Common Message Object Properties

The following properties are general properties used by Sharing Message objects. The constraints on these properties are specified in [\[MS-OXPROPS\]](#).

##### 2.2.1.1 PidTagNormalizedSubject Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagNormalizedSubject** property is specified in [\[MS-OXCMSG\]](#) section 2.2.1.10.

### 2.2.1.2 PidTagSubjectPrefix Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagSubjectPrefix** property is specified in [\[MS-OXCMSG\]](#) section 2.2.1.9.

## 2.2.2 Common Sharing Message Object Properties

The following properties are specific to Sharing Message objects.

### 2.2.2.1 PidLidSharingCapabilities Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingCapabilities** property ([\[MS-OXPROPS\]](#) section 2.231) MUST be one of the following values.

| Value      | Scenario   |
|------------|--|
| 0x00040290 | This Sharing Message object relates to a special folder.         |
| 0x000402B0 | This Sharing Message object does not relate to a special folder. |

### 2.2.2.2 PidNameXSharingCapabilities Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingCapabilities** property ([\[MS-OXPROPS\]](#) section 2.554) contains the hexadecimal string representation of the **PidLidSharingCapabilities** property (section [2.2.2.1](#)).

### 2.2.2.3 PidLidSharingConfigurationUrl Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingConfigurationUrl** property ([\[MS-OXPROPS\]](#) section 2.232) MUST be a zero-length string.

### 2.2.2.4 PidNameXSharingConfigUrl Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingConfigUrl** property ([\[MS-OXPROPS\]](#) section 2.255) MUST be set to the same value as **PidLidSharingConfigurationUrl** (section [2.2.2.3](#)).

### 2.2.2.5 PidLidSharingFlavor Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingFlavor** property ([\[MS-OXPROPS\]](#) section 2.239) MUST be one of the following values.

| Value      | Type of Sharing Message object                    |
|------------|---|
| 0x00020310 | A <b>sharing invitation</b> for a special folder. |

| Value      | Type of Sharing Message object   |
|------------|--|
| 0x00000310 | A sharing invitation for a folder that is not a special folder.  |
| 0x00020500 | A <b>sharing request</b> .   |
| 0x00020710 | Both a sharing invitation for a special folder and a sharing request for the <b>recipient's</b> equivalent special folder. |
| 0x00025100 | A <b>sharing response</b> denying a request.   |
| 0x00023310 | A sharing response accepting a request (also a type of sharing invitation).  |

## 2.2.2.6 PidNameXSharingFlavor Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingFlavor** property ([\[MS-OXPROPS\]](#) section 2.557) MUST be set to the hexadecimal string representation of the value of **PidLidSharingFlavor** (section [2.2.2.5](#)).

## 2.2.2.7 PidLidSharingInitiatorEntryId Property

Type: **PtypBinary** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingInitiatorEntryId** property ([\[MS-OXPROPS\]](#) section 2.242) MUST be set to the value of the **PidTagEntryId** property ([\[MS-OXCPERM\]](#) section 2.2.1.4) for the **Address Book object** of the currently logged on user (see [\[MS-OXOABK\]](#)).

## 2.2.2.8 PidLidSharingInitiatorName Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingInitiatorName** property ([\[MS-OXPROPS\]](#) section 2.243) MUST be set to the value of the **PidTagDisplayName** property ([\[MS-OXCFOLD\]](#) section 2.2.2.2.3) from the Address Book object identified by **PidLidSharingInitiatorEntryId** (section [2.2.2.7](#)) and SHOULD be ignored.[<1>](#)

## 2.2.2.9 PidLidSharingInitiatorSmtip Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingInitiatorSmtip** property ([\[MS-OXPROPS\]](#) section 2.244) MUST be set to the value of the **PidTagSmtipAddress** property ([\[MS-OXOABK\]](#) section 2.2.3.21) from the Address Book object identified by **PidLidSharingInitiatorEntryId** (section [2.2.2.7](#)) and SHOULD be ignored.[<2>](#)

## 2.2.2.10 PidLidSharingLocalType Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingLocalType** property ([\[MS-OXPROPS\]](#) section 2.253) MUST be set to the value of **PidTagContainerClass** ([\[MS-OXPROPS\]](#) section 2.701) of the folder being shared and MUST be one of the following values:

- "IPF.Appointment"

- "IPF.Contact"
- "IPF.Task"
- "IPF.StickyNote"
- "IPF.Journal"

### **2.2.2.11 PidNameXSharingLocalType Property**

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingLocalType** property ([\[MS-OXPROPS\]](#) section 2.559) MUST be set to the same value as the **PidLidSharingLocalType** property (section [2.2.2.10](#)).

### **2.2.2.12 PidLidSharingProviderGuid Property**

Type: **PtypBinary** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingProviderGuid** property ([\[MS-OXPROPS\]](#) section 2.260) MUST be set to %xAE.F0.06.00.00.00.00.C0.00.00.00.00.00.00.46.

### **2.2.2.13 PidNameXSharingProviderGuid Property**

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingProviderGuid** property ([\[MS-OXPROPS\]](#) section 2.560) MUST be set to the hexadecimal string representation of the value of the **PidLidSharingProviderGuid** property (section [2.2.2.12](#)). That is, "AEF0060000000000C000000000000046".

### **2.2.2.14 PidLidSharingProviderName Property**

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingProviderName** property ([\[MS-OXPROPS\]](#) section 2.261) is a user-displayable name of the **sharing provider** identified by the **PidLidSharingProviderGuid** property (section [2.2.2.12](#)). SHOULD be ignored.<3>

### **2.2.2.15 PidNameXSharingProviderName Property**

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingProviderName** property ([\[MS-OXPROPS\]](#) section 2.561) MUST be set to the same value as **PidLidSharingProviderName** (section [2.2.2.14](#)) and SHOULD be ignored.<4>

### **2.2.2.16 PidLidSharingProviderUrl Property**

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingProviderUrl** property ([\[MS-OXPROPS\]](#) section 2.262) is a **Uniform Resource Locator (URL)** related to the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.2.2.12](#)). Generally used to provide more information about the sharing provider. SHOULD be ignored.<5>

### 2.2.2.17 PidNameXSharingProviderUrl Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingProviderUrl** property ([\[MS-OXPROPS\]](#) section 2.562) MUST be set to the same value as **PidLidSharingProviderGuid** ([\[MS-OXPROPS\]](#) section 2.261) and SHOULD be ignored.[<6>](#)

## 2.2.3 Sharing Request Properties

The following property constraints are specific to sharing requests to which the user has responded, which are Sharing Message objects with a **PidLidSharingFlavor** (section [2.2.2.5](#)) value of 0x00020500 or 0x00020710. For all other types of Sharing Message objects, these properties MUST NOT be set.

### 2.2.3.1 PidLidSharingResponseTime Property

Type: **PtypTime** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingResponseTime** property ([\[MS-OXPROPS\]](#) section 2.279) contains the time at which the recipient of the sharing request sent a sharing response.

### 2.2.3.2 PidLidSharingResponseType Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingResponseType** property ([\[MS-OXPROPS\]](#) section 2.280) contains the type of response with which the recipient of the sharing request responded. MUST be one of the following values.

| Value      | Meaning  |
|------------|----------|
| 0x00000001 | Accepted |
| 0x00000002 | Denied   |

## 2.2.4 Sharing Invitation Properties

The following property constraints are specific to sharing invitations, which are Sharing Message objects with a **PidLidSharingFlavor** property (section [2.2.2.5](#)) value of 0x00020310, 0x00000310, 0x0020710, or 0x0023310. For all other types of Sharing Message objects, these properties SHOULD NOT be set and MUST be ignored.[<7>](#)

### 2.2.4.1 PidLidSharingRemoteName Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingRemoteName** property ([\[MS-OXPROPS\]](#) section 2.271) MUST be set to the value of the **PidTagDisplayName** property ([\[MS-OXCFOLD\]](#) section 2.2.2.2.2.3) on the folder being shared.

### 2.2.4.2 PidNameXSharingRemoteName Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingRemoteName** property ([\[MS-OXPROPS\]](#) section 2.563) MUST be set to the same value as the **PidLidSharingRemoteName** property (section [2.2.4.1](#)).

#### 2.2.4.3 PidLidSharingRemoteStoreUid Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingRemoteStoreUid** property ([\[MS-OXPROPS\]](#) section 2.276) MUST be set to a hexadecimal string representation of the value of **PidTagStoreEntryId** ([\[MS-OXPROPS\]](#) section 2.1080) on the folder being shared.

#### 2.2.4.4 PidNameXSharingRemoteStoreUid Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingRemoteStoreUid** property ([\[MS-OXPROPS\]](#) section 2.565) MUST be set to the same value as **PidLidSharingRemoteStoreUid** (section [2.2.4.3](#)).

#### 2.2.4.5 PidLidSharingRemoteType Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingRemoteType** property ([\[MS-OXPROPS\]](#) section 2.275) MUST be set to the same value as the **PidLidSharingLocalType** property (section [2.2.2.10](#)) and SHOULD be ignored.[<8>](#)

#### 2.2.4.6 PidNameXSharingRemoteType Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingRemoteType** property ([\[MS-OXPROPS\]](#) section 2.566) MUST be set to the same value as **PidLidSharingRemoteType** (section [2.2.4.5](#)) and SHOULD be ignored.[<9>](#)

#### 2.2.4.7 PidLidSharingRemoteUid Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSharingRemoteUid** property ([\[MS-OXPROPS\]](#) section 2.276) MUST be set to the hexadecimal string representation of the value of **PidTagEntryId** ([\[MS-OXCPERM\]](#) section 2.2.1.4) on the folder being shared.

#### 2.2.4.8 PidNameXSharingRemoteUid Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameXSharingRemoteUid** property ([\[MS-OXPROPS\]](#) section 2.567) MUST be set to the same value as **PidLidSharingRemoteUid** (section [2.2.4.7](#)).

### 2.2.5 Ignored Properties

The following properties SHOULD NOT be set and MUST be ignored:[<10>](#)

- **PidLidSharingAnonymity** ([\[MS-OXPROPS\]](#) section 2.228)
- **PidLidSharingBindingEntryId** ([\[MS-OXPROPS\]](#) section 2.229)
- **PidLidSharingBrowseUrl** ([\[MS-OXPROPS\]](#) section 2.230)

- **PidNameXSharingBrowseUrl** ([\[MS-OXPROPS\]](#) section 2.553)
- **PidLidSharingDataRangeEnd** ([\[MS-OXPROPS\]](#) section 2.233)
- **PidLidSharingDataRangeStart** ([\[MS-OXPROPS\]](#) section 2.234)
- **PidLidSharingDetail** ([\[MS-OXPROPS\]](#) section 2.235)
- **PidLidSharingExtensionXml** ([\[MS-OXPROPS\]](#) section 2.236)
- **PidNameXSharingExendedCaps** ([\[MS-OXPROPS\]](#) section 2.556)
- **PidLidSharingFilter** ([\[MS-OXPROPS\]](#) section 2.237)
- **PidLidSharingFlags** ([\[MS-OXPROPS\]](#) section 2.238)
- **PidLidSharingFolderEntryId** ([\[MS-OXPROPS\]](#) section 2.240)
- **PidLidSharingIndexEntryId** ([\[MS-OXPROPS\]](#) section 2.241)
- **PidLidSharingInstanceId** ([\[MS-OXPROPS\]](#) section 2.245)
- **PidNameXSharingInstanceId** ([\[MS-OXPROPS\]](#) section 2.558)
- **PidLidSharingLastAutoSyncTime** ([\[MS-OXPROPS\]](#) section 2.246)
- **PidLidSharingLastSyncTime** ([\[MS-OXPROPS\]](#) section 2.247)
- **PidLidSharingLocalComment** ([\[MS-OXPROPS\]](#) section 2.248)
- **PidLidSharingLocalLastModificationTime** ([\[MS-OXPROPS\]](#) section 2.249)
- **PidLidSharingLocalName** ([\[MS-OXPROPS\]](#) section 2.250)
- **PidLidSharingLocalPath** ([\[MS-OXPROPS\]](#) section 2.251)
- **PidLidSharingLocalStoreUid** ([\[MS-OXPROPS\]](#) section 2.252)
- **PidLidSharingLocalUid** ([\[MS-OXPROPS\]](#) section 2.254)
- **PidLidSharingOriginalMessageEntryId** ([\[MS-OXPROPS\]](#) section 2.255)
- **PidLidSharingParentBindingEntryId** ([\[MS-OXPROPS\]](#) section 2.256)
- **PidLidSharingParticipants** ([\[MS-OXPROPS\]](#) section 2.257)
- **PidLidSharingPermissions** ([\[MS-OXPROPS\]](#) section 2.258)
- **PidLidSharingProviderExtension** ([\[MS-OXPROPS\]](#) section 2.259)
- **PidLidSharingRangeEnd** ([\[MS-OXPROPS\]](#) section 2.263)
- **PidLidSharingRangeStart** ([\[MS-OXPROPS\]](#) section 2.264)
- **PidLidSharingReciprocation** ([\[MS-OXPROPS\]](#) section 2.265)
- **PidLidSharingRemoteByteSize** ([\[MS-OXPROPS\]](#) section 2.266)
- **PidLidSharingRemoteComment** ([\[MS-OXPROPS\]](#) section 2.267)

- **PidLidSharingRemoteCrc** ([\[MS-OXPROPS\]](#) section 2.268)
- **PidLidSharingRemoteLastModificationTime** ([\[MS-OXPROPS\]](#) section 2.269)
- **PidLidSharingRemoteMessageCount** ([\[MS-OXPROPS\]](#) section 2.269)
- **PidLidSharingRemotePass** ([\[MS-OXPROPS\]](#) section 2.272)
- **PidLidSharingRemotePath** ([\[MS-OXPROPS\]](#) section 2.273)
- **PidNameXSharingRemotePath** ([\[MS-OXPROPS\]](#) section 2.564)
- **PidLidSharingRemoteUser** ([\[MS-OXPROPS\]](#) section 2.277)
- **PidLidSharingRemoteVersion** ([\[MS-OXPROPS\]](#) section 2.278)
- **PidLidSharingRoamLog** ([\[MS-OXPROPS\]](#) section 2.281)
- **PidLidSharingStart** ([\[MS-OXPROPS\]](#) section 2.282)
- **PidLidSharingStatus** ([\[MS-OXPROPS\]](#) section 2.283)
- **PidLidSharingStop** ([\[MS-OXPROPS\]](#) section 2.284)
- **PidLidSharingSyncFlags** ([\[MS-OXPROPS\]](#) section 2.285)
- **PidLidSharingSyncInterval** ([\[MS-OXPROPS\]](#) section 2.286)
- **PidLidSharingTimeToLive** ([\[MS-OXPROPS\]](#) section 2.287)
- **PidLidSharingTimeToLiveAuto** ([\[MS-OXPROPS\]](#) section 2.288)
- **PidLidSharingWorkingHoursDays** ([\[MS-OXPROPS\]](#) section 2.289)
- **PidLidSharingWorkingHoursEnd** ([\[MS-OXPROPS\]](#) section 2.290)
- **PidLidSharingWorkingHoursStart** ([\[MS-OXPROPS\]](#) section 2.291)
- **PidLidSharingWorkingHoursTimeZone** ([\[MS-OXPROPS\]](#) section 2.292)

## 2.2.6 Additional Property Constraints

This document specifies additional constraints on the following properties beyond what is specified in [\[MS-OXCMSG\]](#).

### 2.2.6.1 PidNameContentClass Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameContentClass** property ([\[MS-OXPROPS\]](#) section 2.428) MUST be set to "Sharing".

### 2.2.6.2 PidTagMessageClass Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagMessageClass** property ([\[MS-OXCMSG\]](#) section 2.2.1.3) MUST be set to "IPM.Sharing" or a value that begins with "IPM.Sharing.".

### 3 Protocol Details

There is no server role beyond those specified in [\[MS-OXCMMSG\]](#) and [\[MS-OXOMSG\]](#).

#### 3.1 Client Details

The client role is to create and operate on Sharing Message objects and otherwise operate in the client role, as specified in [\[MS-OXCMMSG\]](#) and [\[MS-OXOMSG\].<11>](#)

##### 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This specification does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

A Sharing Message object extends the **Message object** and has an abstract data model that does not differ from that specified in [\[MS-OXCMMSG\]](#).

##### 3.1.2 Timers

None.

##### 3.1.3 Initialization

None.

##### 3.1.4 Higher-Layer Triggered Events

###### 3.1.4.1 Creating a Sharing Invitation

The following table lists the properties and the corresponding values that MUST be set, as specified in section [2.2](#), to create a sharing invitation.

| Property  | Valid Values   |
|---|--|
| <b>PidTagMessageClass</b> ( <a href="#">[MS-OXCMMSG]</a> section 2.2.1.3) | "IPM.Sharing" or a value that begins with "IPM.Sharing."   |
| <b>PidNameContentClass</b> (section <a href="#">2.2.6.1</a> )             | "Sharing"  |
| <b>PidLidSharingProviderGuid</b> (section <a href="#">2.2.2.12</a> )      | %xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.00.46  |
| <b>PidNameXSharingProviderGuid</b> (section <a href="#">2.2.2.13</a> )    | "AEF006000000000C00000000000046"   |
| <b>PidLidSharingProviderName</b> (section <a href="#">2.2.2.14</a> )      | A user-displayable name of the sharing provider identified by <b>PidLidSharingProviderGuid</b> . |
| <b>PidNameXSharingProviderName</b> (section <a href="#">2.2.2.15</a> )    | The same value as <b>PidLidSharingProviderName</b> .   |
| <b>PidLidSharingProviderUrl</b> (section                                  | A URL related to the sharing provider identified by  |

| <b>Property</b>   | <b>Valid Values</b>  |
|---|--|
| <b>PidNameXSharingProviderUrl</b> (section <a href="#">2.2.2.16</a> )   | <b>PidLidSharingProviderGuid.</b>  |
| <b>PidNameXSharingProviderUrl</b> (section <a href="#">2.2.2.17</a> )   | The same value as <b>PidLidSharingProviderUrl</b> .  |
| <b>PidLidSharingConfigurationUrl</b> (section <a href="#">2.2.2.3</a> ) | A zero-length string.  |
| <b>PidNameXSharingConfigUrl</b> (section <a href="#">2.2.2.4</a> )      | The same value as <b>PidLidSharingConfigurationUrl</b> .   |
| <b>PidLidSharingFlavor</b> (section <a href="#">2.2.2.5</a> )           | If the folder being shared is a special folder: 0x00020310.<br>If the folder being shared is not a special folder: 0x00000310.   |
| <b>PidNameXSharingFlavor</b> (section <a href="#">2.2.2.6</a> )         | If the folder being shared is a special folder: "20310".<br>If the folder being shared is not a special folder: "310".   |
| <b>PidLidSharingCapabilities</b> (section <a href="#">2.2.2.1</a> )     | If the folder being shared is a special folder: 0x00040290.<br>If the folder being shared is not a special folder: 0x000402B0.   |
| <b>PidNameXSharingCapabilities</b> (section <a href="#">2.2.2.2</a> )   | If the folder being shared is a special folder: "40290".<br>If the folder being shared is not a special folder: "402B0".   |
| <b>PidLidSharingInitiatorEntryId</b> (section <a href="#">2.2.2.7</a> ) | The value of <b>PidTagEntryId</b> ( <a href="#">[MS-OXCPERM]</a> section 2.2.1.4) for the Address Book object of the currently logged in user.                             |
| <b>PidLidSharingInitiatorName</b> (section <a href="#">2.2.2.8</a> )    | The value of <b>PidTagDisplayName</b> ( <a href="#">[MS-OXCOLD]</a> section 2.2.2.2.2.3) from the Address Book object identified by <b>PidLidSharingInitiatorEntryId</b> . |
| <b>PidLidSharingInitiatorSsmtp</b> (section <a href="#">2.2.2.9</a> )   | The value of <b>PidTagSmtpAddress</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.3.21) from the Address Book object identified by <b>PidLidSharingInitiatorEntryId</b> .    |
| <b>PidLidSharingRemoteName</b> (section <a href="#">2.2.4.1</a> )       | The value of <b>PidTagDisplayName</b> on the folder being shared.  |
| <b>PidNameXSharingRemoteName</b> (section <a href="#">2.2.4.2</a> )     | The same value as <b>PidLidSharingRemoteName</b> .   |
| <b>PidLidSharingRemoteUid</b> (section <a href="#">2.2.4.7</a> )        | A hexadecimal string representation of the value of <b>PidTagEntryId</b> on the folder being shared.   |
| <b>PidNameXSharingRemoteUid</b> (section <a href="#">2.2.4.8</a> )      | The value of <b>PidLidSharingRemoteUid</b> .   |
| <b>PidLidSharingRemoteStoreUid</b> (section <a href="#">2.2.4.3</a> )   | A hexadecimal string representation of the value of <b>PidTagStoreEntryId</b> () on the folder being shared.   |
| <b>PidNameXSharingRemoteStoreUid</b> (section <a href="#">2.2.4.4</a> ) | The value of <b>PidLidSharingRemoteStoreUid</b> .  |
| <b>PidLidSharingLocalType</b> (section <a href="#">2.2.2.10</a> )       | A value from table 1 according to the type of folder being shared.   |
| <b>PidNameXSharingLocalType</b> (section <a href="#">2.2.2.11</a> )     | The same value as <b>PidLidSharingLocalType</b> .  |

| Property  | Valid Values                                       |
|---|--|
| <b>PidLidSharingRemoteType</b> (section <a href="#">2.2.4.5</a> )   | The same value as <b>PidLidSharingLocalType</b> .  |
| <b>PidNameXSharingRemoteType</b> (section <a href="#">2.2.4.6</a> ) | The same value as <b>PidLidSharingRemoteType</b> . |

| Type of folder | Valid Value       |
|----------------|-------------------|
| Calendar       | "IPF.Appointment" |
| Contacts       | "IPF.Contact"     |
| Tasks          | "IPF.Task"        |
| Notes          | "IPF.StickyNote"  |
| Journal        | "IPF.Journal"     |

### 3.1.4.2 Creating a Sharing Request

The following table lists the properties and the corresponding values that MUST be set, as specified in section [2.2](#), to create a sharing request.

| Property  | Valid Values   |
|---|--|
| <b>PidTagMessageClass</b> ( <a href="#">[MS-OXCMMSG]</a> section 2.2.1.3) | "IPM.Sharing" or a value that begins with "IPM.Sharing."   |
| <b>PidNameContentClass</b> (section <a href="#">2.2.6.1</a> )             | "Sharing"  |
| <b>PidLidSharingProviderGuid</b> (section <a href="#">2.2.2.12</a> )      | %xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.00.46  |
| <b>PidNameXSharingProviderGuid</b> (section <a href="#">2.2.2.13</a> )    | "AEF0060000000000C000000000000046"   |
| <b>PidLidSharingProviderName</b> (section <a href="#">2.2.2.14</a> )      | A user-displayable name of the sharing provider identified by <b>PidLidSharingProviderGuid</b> . |
| <b>PidNameXSharingProviderName</b> (section <a href="#">2.2.2.15</a> )    | The same value as <b>PidLidSharingProviderName</b> .   |
| <b>PidLidSharingProviderUrl</b> (section <a href="#">2.2.2.16</a> )       | A URL related to the sharing provider identified by <b>PidLidSharingProviderGuid</b> .           |
| <b>PidNameXSharingProviderUrl</b> (section <a href="#">2.2.2.17</a> )     | The same value as <b>PidLidSharingProviderUrl</b> .  |
| <b>PidLidSharingConfigurationUrl</b> (section <a href="#">2.2.2.3</a> )   | A zero-length string.  |
| <b>PidNameXSharingConfigUrl</b> (section <a href="#">2.2.2.4</a> )        | The same value as <b>PidLidSharingConfigurationUrl</b> .   |

| <b>Property</b>   | <b>Valid Values</b>  |
|---|--|
| <b>PidLidSharingFlavor</b> (section <a href="#">2.2.2.5</a> )           | 0x00020500   |
| <b>PidNameXSharingFlavor</b> (section <a href="#">2.2.2.6</a> )         | "20500"  |
| <b>PidLidSharingCapabilities</b> (section <a href="#">2.2.2.1</a> )     | 0x00040290   |
| <b>PidNameXSharingCapabilities</b> (section <a href="#">2.2.2.2</a> )   | "40290"  |
| <b>PidLidSharingInitiatorEntryId</b> (section <a href="#">2.2.2.7</a> ) | The value of <b>PidTagEntryId</b> ( <a href="#">[MS-OXCPERM]</a> section 2.2.1.4) for the Address Book object of the currently logged on user.                             |
| <b>PidLidSharingInitiatorName</b> (section <a href="#">2.2.2.8</a> )    | The value of <b>PidTagDisplayName</b> ( <a href="#">[MS-OXCOLD]</a> section 2.2.2.2.2.3) from the Address Book object identified by <b>PidLidSharingInitiatorEntryId</b> . |
| <b>PidLidSharingInitiatorSntp</b> (section <a href="#">2.2.2.9</a> )    | The value of <b>PidTagSntpAddress</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.3.21) from the Address Book object identified by <b>PidLidSharingInitiatorEntryId</b> .    |
| <b>PidLidSharingLocalType</b> (section <a href="#">2.2.2.10</a> )       | A value from table 2 according to the special folder being requested.  |
| <b>PidNameXSharingLocalType</b> (section <a href="#">2.2.2.11</a> )     | The same value as <b>PidLidSharingLocalType</b> .  |

The following table lists the valid values for the **PidLidSharingLocalType** property.

Table 2: Valid Values for PidLidSharingLocalType on a Sharing Request

| <b>Special Folder (See [MS-OXOSFLD])</b> | <b>Valid value</b> |
|--|--------------------|
| Calendar                                 | "IPF.Appointment"  |
| Contacts                                 | "IPF.Contact"      |
| Tasks                                    | "IPF.Task"         |
| Notes                                    | "IPF.StickyNote"   |
| Journal                                  | "IPF.Journal"      |

### 3.1.4.3 Creating a Sharing Response – Accept

The client can determine the special folder being requested by the sharing request according to the following table:

| <b>Value of PidLidSharingLocalType on the Sharing Request</b> | <b>Special Folder being Requested (See [MS-OXOSFLD])</b> |
|---|--|
| "IPF.appointment"   | Calendar   |
| "IPF.contact"   | Contacts   |

| <b>Value of <b>PidLidSharingLocalType</b> on the Sharing Request</b> | <b>Special Folder being Requested (See [MS-OXOSFLD])</b> |
|--|--|
| "IPF.Task"   | Tasks  |
| "IPF.StickyNote"   | Notes  |
| "IPF.journal"  | Journal  |

The following table lists the properties and the corresponding values that MUST be set, as specified in section 2.2, to create a sharing response that indicates that a sharing request has been accepted and provides the information necessary to locate the special folder being requested.

| <b>Property</b>  | <b>Valid Values</b>  |
|--|--|
| <b>PidTagMessageClass</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.3) | "IPM.Sharing" or a value that begins with "IPM.Sharing."   |
| <b>PidNameContentClass</b> (section <a href="#">2.2.6.1</a> )            | "Sharing"  |
| <b>PidLidSharingProviderGuid</b> (section <a href="#">2.2.2.12</a> )     | %xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.00.46  |
| <b>PidNameXSharingProviderGuid</b> (section <a href="#">2.2.2.13</a> )   | "AEF006000000000C000000000000046"  |
| <b>PidLidSharingProviderName</b> (section <a href="#">2.2.2.14</a> )     | A user-displayable name of the sharing provider identified by <b>PidLidSharingProviderGuid</b> .   |
| <b>PidNameXSharingProviderName</b> (section <a href="#">2.2.2.15</a> )   | The same value as <b>PidLidSharingProviderName</b> .   |
| <b>PidLidSharingProviderUrl</b> (section <a href="#">2.2.2.16</a> )      | A URL related to the sharing provider identified by <b>PidLidSharingProviderGuid</b> .   |
| <b>PidNameXSharingProviderUrl</b> (section <a href="#">2.2.2.17</a> )    | The same value as <b>PidLidSharingProviderUrl</b> .  |
| <b>PidLidSharingConfigurationUrl</b> (section <a href="#">2.2.2.3</a> )  | A zero-length string.  |
| <b>PidNameXSharingConfigUrl</b> (section <a href="#">2.2.2.4</a> )       | The same value as <b>PidLidSharingConfigurationUrl</b> .   |
| <b>PidLidSharingFlavor</b> (section <a href="#">2.2.2.5</a> )            | 0x00023310   |
| <b>PidNameXSharingFlavor</b> (section <a href="#">2.2.2.6</a> )          | "23310"  |
| <b>PidLidSharingCapabilities</b> (section <a href="#">2.2.2.1</a> )      | 0x00040290   |
| <b>PidNameXSharingCapabilities</b> (section <a href="#">2.2.2.2</a> )    | "40290"  |
| <b>PidLidSharingInitiatorEntryId</b> (section <a href="#">2.2.2.7</a> )  | The value of <b>PidTagEntryId</b> ( <a href="#">[MS-OXCPERM]</a> section 2.2.1.4) for the Address Book object of the currently logged on user.     |
| <b>PidLidSharingInitiatorName</b> (section <a href="#">2.2.2.8</a> )     | The value of <b>PidTagDisplayName</b> ( <a href="#">[MS-OXCFOLD]</a> section 2.2.1.4) for the Address Book object of the currently logged on user. |

| Property  | Valid Values  |
|---|---|
| <a href="#">2.2.2.8</a> )   | 2.2.2.2.2.3) from the Address Book object identified by <b>PidLidSharingInitiatorEntryId</b> .  |
| <b>PidLidSharingInitiatorSmtp</b> (section <a href="#">2.2.2.9</a> )    | The value of <b>PidTagSmtpAddress</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.3.21) from the Address Book object identified by <b>PidLidSharingInitiatorEntryId</b> . |
| <b>PidLidSharingRemoteName</b> (section <a href="#">2.2.4.1</a> )       | The value of <b>PidTagDisplayName</b> on the special folder being requested.  |
| <b>PidNameXSharingRemoteName</b> (section <a href="#">2.2.4.2</a> )     | The same value as <b>PidLidSharingRemoteName</b> .  |
| <b>PidLidSharingRemoteUid</b> (section <a href="#">2.2.4.7</a> )        | The hexadecimal string representation of the value of <b>PidTagEntryId</b> on the special folder being requested.   |
| <b>PidNameXSharingRemoteUid</b> (section <a href="#">2.2.4.8</a> )      | The value of <b>PidLidSharingRemoteUid</b> .  |
| <b>PidLidSharingRemoteStoreUid</b> (section <a href="#">2.2.4.3</a> )   | The hexadecimal string representation of the value of <b>PidTagStoreEntryId</b> () on the special folder being requested.   |
| <b>PidNameXSharingRemoteStoreUid</b> (section <a href="#">2.2.4.4</a> ) | The value of <b>PidLidSharingRemoteStoreUid</b> .   |
| <b>PidLidSharingLocalType</b> (section <a href="#">2.2.2.10</a> )       | The value of <b>PidLidSharingLocalType</b> on the sharing request to which this message is responding.  |
| <b>PidNameXSharingLocalType</b> (section <a href="#">2.2.2.11</a> )     | The same value as <b>PidLidSharingLocalType</b> .   |
| <b>PidLidSharingRemoteType</b> (section <a href="#">2.2.4.5</a> )       | The same value as <b>PidLidSharingLocalType</b> .   |
| <b>PidNameXSharingRemoteType</b> (section <a href="#">2.2.4.6</a> )     | The same value as <b>PidLidSharingRemoteType</b> .  |

The following table lists the properties and the corresponding values that MUST be set, as specified in section [2.2](#), on the sharing request to which this sharing response is responding.

| Property  | Valid Values                                     |
|---|--|
| <b>PidLidSharingResponseType</b> (section <a href="#">2.2.3.2</a> ) | 0x00000001                                       |
| <b>PidLidSharingResponseTime</b> (section <a href="#">2.2.3.1</a> ) | The time at which the sharing response was sent. |

### 3.1.4.4 Creating a Sharing Response – Deny

The following table lists the properties and the corresponding values that MUST be set, as specified in section [2.2](#), to create a sharing response that indicates a sharing request has been denied.

| Property   | Valid Values   |
|--|--|
| <b>PidTagMessageClass</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.3) | "IPM.Sharing" or a value that begins with "IPM.Sharing." |

| <b>Property</b>   | <b>Valid Values</b>  |
|---|--|
| <b>PidNameContentClass</b> (section <a href="#">2.2.6.1</a> )           | "Sharing"  |
| <b>PidLidSharingProviderGuid</b> (section <a href="#">2.2.2.12</a> )    | %xAE.F0.06.00.00.00.00.C0.00.00.00.00.00.46  |
| <b>PidNameXSharingProviderGuid</b> (section <a href="#">2.2.2.13</a> )  | "AEF006000000000C000000000000046"  |
| <b>PidLidSharingProviderName</b> (section <a href="#">2.2.2.14</a> )    | A user-displayable name of the sharing provider identified by <b>PidLidSharingProviderGuid</b> .   |
| <b>PidNameXSharingProviderName</b> (section <a href="#">2.2.2.15</a> )  | The same value as <b>PidLidSharingProviderName</b> .   |
| <b>PidLidSharingProviderUrl</b> (section <a href="#">2.2.2.16</a> )     | A URL related to the sharing provider identified by <b>PidLidSharingProviderGuid</b> .   |
| <b>PidNameXSharingProviderUrl</b> (section <a href="#">2.2.2.17</a> )   | The same value as <b>PidLidSharingProviderUrl</b> .  |
| <b>PidLidSharingConfigurationUrl</b> (section <a href="#">2.2.2.3</a> ) | A zero-length string.  |
| <b>PidNameXSharingConfigUrl</b> (section <a href="#">2.2.2.4</a> )      | The same value as <b>PidLidSharingConfigurationUrl</b> .   |
| <b>PidLidSharingFlavor</b> (section <a href="#">2.2.2.5</a> )           | 0x00025100   |
| <b>PidNameXSharingFlavor</b> (section <a href="#">2.2.2.6</a> )         | "25100"  |
| <b>PidLidSharingCapabilities</b> (section <a href="#">2.2.2.1</a> )     | 0x00040290   |
| <b>PidNameXSharingCapabilities</b> (section <a href="#">2.2.2.2</a> )   | "40290"  |
| <b>PidLidSharingInitiatorEntryId</b> (section <a href="#">2.2.2.7</a> ) | The value of <b>PidTagEntryId</b> ( <a href="#">[MS-OXCPERM]</a> section 2.2.1.4) for the Address Book object of the currently logged on user.                             |
| <b>PidLidSharingInitiatorName</b> (section <a href="#">2.2.2.8</a> )    | The value of <b>PidTagDisplayName</b> ( <a href="#">[MS-OXCOLD]</a> section 2.2.2.2.2.3) from the Address Book object identified by <b>PidLidSharingInitiatorEntryId</b> . |
| <b>PidLidSharingInitiatorSmtip</b> (section <a href="#">2.2.2.9</a> )   | The value of <b>PidTagSmtpAddress</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.3.21) from the Address Book object identified by <b>PidLidSharingInitiatorEntryId</b> .    |
| <b>PidLidSharingLocalType</b> (section <a href="#">2.2.2.10</a> )       | The value of <b>PidLidSharingLocalType</b> on the sharing request to which this message is responding.   |
| <b>PidNameXSharingLocalType</b> (section <a href="#">2.2.2.11</a> )     | The same value as <b>PidLidSharingLocalType</b> .  |

The following table lists the properties and the corresponding values that MUST be set, as specified in section [2.2](#), on the sharing request to which this sharing response is responding.

| Property  | Valid Values                                     |
|---|--|
| <b>PidLidSharingResponseType</b> (section <a href="#">2.2.3.2</a> ) | 0x00000002                                       |
| <b>PidLidSharingResponseTime</b> (section <a href="#">2.2.3.1</a> ) | The time at which the sharing response was sent. |

### 3.1.5 Message Processing Events and Sequencing Rules

None.

### 3.1.6 Timer Events

None.

### 3.1.7 Other Local Events

None.

## 4 Protocol Examples

Kendall Keil wants to see Ryan Gregg's calendar special folder. Kendall sends a sharing request to Ryan and Ryan responds.

The following is a description of what a client might do to accomplish this scenario and the responses a server might return. See [\[MS-OXCPRPT\]](#) and [\[MS-OXCMSG\]](#) for details about **remote operations (ROPs)**.

Before manipulating Sharing Message objects, the client has to ask the server to perform a mapping from **named properties** to **property IDs**, using **RopGetPropertyIdsFromNames** ([\[MS-OXCROPS\]](#) section 2.2.8.1).

| Property  | Property set GUID                     | NameID                  |
|---|---------------------------------------|-------------------------|
| <b>PidNameContentClass</b> (section <a href="#">2.2.6.1</a> )           | {00020386-0000-0000-c000-00000000046} | Content-class           |
| <b>PidLidSharingProviderGuid</b> (section <a href="#">2.2.2.12</a> )    | {00062040-0000-0000-C000-00000000046} | 0x00008A01              |
| <b>PidNameXSharingProviderGuid</b> (section <a href="#">2.2.2.13</a> )  | {00020386-0000-0000-C000-00000000046} | X-Sharing-Provider-GUID |
| <b>PidLidSharingProviderName</b> (section <a href="#">2.2.2.14</a> )    | {00062040-0000-0000-C000-00000000046} | 0x00008A02              |
| <b>PidNameXSharingProviderName</b> (section <a href="#">2.2.2.15</a> )  | {00020386-0000-0000-C000-00000000046} | X-Sharing-Provider-Name |
| <b>PidLidSharingProviderUrl</b> (section <a href="#">2.2.2.16</a> )     | {00062040-0000-0000-C000-00000000046} | 0x00008A03              |
| <b>PidNameXSharingProviderUrl</b> (section <a href="#">2.2.2.17</a> )   | {00020386-0000-0000-C000-00000000046} | X-Sharing-Provider-URL  |
| <b>PidLidSharingConfigurationUrl</b> (section <a href="#">2.2.2.3</a> ) | {00062040-0000-0000-C000-00000000046} | 0x00008A24              |
| <b>PidNameXSharingConfigUrl</b> (section <a href="#">2.2.2.4</a> )      | {00020386-0000-0000-C000-00000000046} | X-Sharing-Config-URL    |
| <b>PidLidSharingFlavor</b> (section <a href="#">2.2.2.5</a> )           | {00062040-0000-0000-C000-00000000046} | 0x00008A18              |
| <b>PidNameXSharingFlavor</b> (section <a href="#">2.2.2.6</a> )         | {00020386-0000-0000-C000-00000000046} | X-Sharing-Flavor        |
| <b>PidLidSharingCapabilities</b> (section <a href="#">2.2.2.1</a> )     | {00062040-0000-0000-C000-00000000046} | 0x00008A17              |
| <b>PidNameXSharingCapabilities</b> (section <a href="#">2.2.2.2</a> )   | {00020386-0000-0000-C000-00000000046} | X-Sharing-Capabilities  |
| <b>PidLidSharingLocalType</b> (section <a href="#">2.2.2.10</a> )       | {00062040-0000-0000-C000-00000000046} | 0x00008A14              |
| <b>PidNameXSharingLocalType</b> (section <a href="#">2.2.2.11</a> )     | {00020386-0000-0000-C000-00000000046} | X-Sharing-Local-Type    |

| <b>Property</b>   | <b>Property set GUID</b>              | <b>NameID</b>              |
|---|---------------------------------------|----------------------------|
| <b>PidLidSharingInitiatorEntryId</b> (section <a href="#">2.2.2.7</a> ) | {00062040-0000-0000-C000-00000000046} | 0x00008A09                 |
| <b>PidLidSharingInitiatorName</b> (section <a href="#">2.2.2.8</a> )    | {00062040-0000-0000-C000-00000000046} | 0x00008A07                 |
| <b>PidLidSharingInitiatorSmtip</b> (section <a href="#">2.2.2.9</a> )   | {00062040-0000-0000-C000-00000000046} | 0x00008A08                 |
| <b>PidLidSharingRemoteName</b> (section <a href="#">2.2.4.1</a> )       | {00062040-0000-0000-C000-00000000046} | 0x00008A05                 |
| <b>PidNameXSharingRemoteName</b> (section <a href="#">2.2.4.2</a> )     | {00020386-0000-0000-C000-00000000046} | X-Sharing-Remote-Name      |
| <b>PidLidSharingRemoteType</b> (section <a href="#">2.2.4.5</a> )       | {00062040-0000-0000-C000-00000000046} | 0x00008A1D                 |
| <b>PidNameXSharingRemoteType</b> (section <a href="#">2.2.4.6</a> )     | {00020386-0000-0000-C000-00000000046} | X-Sharing-Remote-Type      |
| <b>PidLidSharingRemoteUid</b> (section <a href="#">2.2.4.7</a> )        | {00062040-0000-0000-C000-00000000046} | 0x00008A06                 |
| <b>PidNameXSharingRemoteUid</b> (section <a href="#">2.2.4.8</a> )      | {00020386-0000-0000-C000-00000000046} | X-Sharing-Remote-Uid       |
| <b>PidLidSharingRemoteStoreUid</b> (section <a href="#">2.2.4.3</a> )   | {00062040-0000-0000-C000-00000000046} | 0x00008A48                 |
| <b>PidNameXSharingRemoteStoreUid</b> (section <a href="#">2.2.4.4</a> ) | {00020386-0000-0000-C000-00000000046} | X-Sharing-Remote-Store-Uid |
| <b>PidLidSharingResponseType</b> (section <a href="#">2.2.3.2</a> )     | {00062040-0000-0000-C000-00000000046} | 0x00008A27                 |
| <b>PidLidSharingResponseTime</b> (section <a href="#">2.2.3.1</a> )     | {00062040-0000-0000-C000-00000000046} | 0x00008A28                 |

The server might respond with the following identifiers, which will be used in the examples that follow. (The actual identifiers are at the discretion of the server.)

| <b>Property</b>                    | <b>Property ID</b> |
|------------------------------------|--------------------|
| <b>PidNameContentClass</b>         | 0x806D             |
| <b>PidLidSharingProviderGuid</b>   | 0x8243             |
| <b>PidNameXSharingProviderGuid</b> | 0x836F             |
| <b>PidLidSharingProviderName</b>   | 0x8244             |
| <b>PidNameXSharingProviderName</b> | 0x8370             |
| <b>PidLidSharingProviderUrl</b>    | 0x8245             |
| <b>PidNameXSharingProviderUrl</b>  | 0x8371             |

| Property                             | Property ID |
|--------------------------------------|-------------|
| <b>PidLidSharingConfigurationUrl</b> | 0x83D0      |
| <b>PidNameXSharingConfigUrl</b>      | 0x8377      |
| <b>PidLidSharingFlavor</b>           | 0x823D      |
| <b>PidNameXSharingFlavor</b>         | 0x836D      |
| <b>PidLidSharingCapabilities</b>     | 0x823C      |
| <b>PidNameXSharingCapabilities</b>   | 0x836C      |
| <b>PidLidSharingLocalType</b>        | 0x824F      |
| <b>PidNameXSharingLocalType</b>      | 0x8379      |
| <b>PidLidSharingInitiatorEntryId</b> | 0x8249      |
| <b>PidLidSharingInitiatorName</b>    | 0x8029      |
| <b>PidLidSharingInitiatorSsmtp</b>   | 0x8248      |
| <b>PidLidSharingRemoteName</b>       | 0x8026      |
| <b>PidNameXSharingRemoteName</b>     | 0x8373      |
| <b>PidLidSharingRemoteType</b>       | 0x8247      |
| <b>PidNameXSharingRemoteType</b>     | 0x8376      |
| <b>PidLidSharingRemoteUid</b>        | 0x8246      |
| <b>PidNameXSharingRemoteUid</b>      | 0x8374      |
| <b>PidLidSharingRemoteStoreUid</b>   | 0x83E1      |
| <b>PidNameXSharingRemoteStoreUid</b> | 0x8375      |
| <b>PidLidSharingResponseType</b>     | 0x83E4      |
| <b>PidLidSharingResponseTime</b>     | 0x83E3      |

## 4.1 Sending a Sharing Request

Kendall's client creates a Message object, using **RopCreateMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.2). The server returns a success code and a **handle** to a Message object.

The client then uses **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) to set the following properties and corresponding values on the Message object to create a sharing request, as follows:

| Property  | Property ID | Data Type  | Value         |
|---|-------------|------------|---------------|
| <b>PidTagMessageClass</b> ( <a href="#">[MS-OXCMMSG]</a> section 2.2.1.3) | 0x001A      | PtypString | "IPM.Sharing" |
| <b>PidNameContentClass</b> (section                                       | 0x806D      | PtypString | "Sharing"     |

| <b>Property</b>  | <b>Property ID</b> | <b>Data Type</b> | <b>Value</b>                        |
|--|--------------------|------------------|-------------------------------------|
| <a href="#">2.2.6.1)</a>   |                    |                  |                                     |
| <b>PidTagNormalizedSubject</b> ( <a href="#">[MS-OXCMSP]</a> section 2.2.1.10) | 0x0E1D             | PtypString       | "Sharing request: calendar"         |
| <b>PidTagSubjectPrefix</b> ( <a href="#">[MS-OXCMSP]</a> section 2.2.1.9)      | 0x003D             | PtypString       | "" (a zero-length string)           |
| <b>PidLidSharingProviderGuid</b> (section <a href="#">2.2.2.12</a> )           | 0x8243             | PtypBinary       | (See Figure 1)                      |
| <b>PidNameXSharingProviderGuid</b> (section <a href="#">2.2.2.13</a> )         | 0x836F             | PtypString       | "AEF0060000000000C0000000000000046" |
| <b>PidLidSharingProviderName</b> (section <a href="#">2.2.2.14</a> )           | 0x8244             | PtypString       | "Microsoft Exchange"                |
| <b>PidNameXSharingProviderName</b> (section <a href="#">2.2.2.15</a> )         | 0x8370             | PtypString       | "Microsoft Exchange"                |
| <b>PidLidSharingProviderUrl</b> (section <a href="#">2.2.2.16</a> )            | 0x8245             | PtypString       | "HTTP://www.microsoft.com/exchange" |
| <b>PidNameXSharingProviderUrl</b> (section <a href="#">2.2.2.17</a> )          | 0x8371             | PtypString       | "HTTP://www.microsoft.com/exchange" |
| <b>PidLidSharingConfigurationUrl</b> (section <a href="#">2.2.2.3</a> )        | 0x83D0             | PtypString       | "" (a zero-length string)           |
| <b>PidNameXSharingConfigUrl</b> (section <a href="#">2.2.2.4</a> )             | 0x8377             | PtypString       | "" (a zero-length string)           |
| <b>PidLidSharingFlavor</b> (section <a href="#">2.2.2.5</a> )                  | 0x823D             | PtypInteger32    | 0x00020500                          |
| <b>PidNameXSharingFlavor</b> (section <a href="#">2.2.2.6</a> )                | 0x836D             | PtypString       | "20500"                             |
| <b>PidLidSharingCapabilities</b> (section <a href="#">2.2.2.1</a> )            | 0x823C             | PtypInteger32    | 0x00040290                          |
| <b>PidNameXSharingCapabilities</b> (section <a href="#">2.2.2.2</a> )          | 0x836C             | PtypString       | "40290"                             |
| <b>PidLidSharingLocalType</b> (section <a href="#">2.2.2.10</a> )              | 0x824F             | PtypString       | "IPF.Appointment"                   |
| <b>PidNameXSharingLocalType</b> (section <a href="#">2.2.2.11</a> )            | 0x8379             | PtypString       | "IPF.Appointment"                   |
| <b>PidLidSharingInitiatorEntryId</b> (section <a href="#">2.2.2.7</a> )        | 0x8249             | PtypBinary       | (See Figure 2)                      |
| <b>PidLidSharingInitiatorName</b> (section <a href="#">2.2.2.8</a> )           | 0x8029             | PtypString       | user12                              |
| <b>PidLidSharingInitiatorSmtpp</b> (section <a href="#">2.2.2.9</a> )          | 0x8248             | PtypString       | user12@fabrikam.com                 |

Figure 1 shows the value of the **PidLidSharingProviderGuid** property. The size of the value is 16 bytes.

```
0000: ae f0 06 00 00 00 00 c0 00 00 00 00 00 00 00 46 .....F
```

Figure 2 shows the value of the **PidLidSharingInitiatorEntryId** property. The size of the value is 125 bytes.

```
0000: 00 00 00 00 dc a7 40 c8 c0 42 10 1a b4 b9 08 00 .....@..B.....
0010: 2b 2f e1 82 01 00 00 00 00 00 00 00 2f 6f 3d 46 +/...../o=F
0020: 69 72 73 74 20 4f 72 67 61 6e 69 7a 61 74 69 6f irst Organizatio
0030: 6e 2f 6f 75 3d 45 78 63 68 61 6e 67 65 20 41 64 n/ou=Exchange Ad
0040: 6d 69 6e 69 73 74 72 61 74 69 76 65 20 47 72 6f ministerative Gro
0050: 75 70 20 28 46 59 44 49 42 4f 48 46 32 33 53 50 up (FYDIBOHF23SP
0060: 44 4c 54 29 2f 63 6e 3d 52 65 63 69 70 69 65 6e DLT)/cn=Recipien
0070: 74 73 2f 63 6e 3d 75 73 65 72 31 32 00 ts/cn=user12.
```

After addressing the message as specified in [\[MS-OXOMSG\]](#), the client uses **RopSubmitMessage** ([\[MS-OXCROPS\]](#) section 2.2.7.1) to send the message to Ryan and then uses **RopRelease** ([\[MS-OXCROPS\]](#) section 2.2.15.3) to release the Message object.

## 4.2 Denying a Sharing Request

Ryan wants to send a sharing response denying the sharing request described in section 4.1. The client uses **RopCreateMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.2) to create a new Message object. The server returns a success code and a handle to a Message object.

The client then uses **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) to set the sharing properties for a sharing response that indicates that the request was denied, as follows:

| Property   | Property ID | Property Type | Value                               |
|--|-------------|---------------|-------------------------------------|
| <b>PidTagMessageClass</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.3)       | 0x001A      | PtypString    | "IPM.Sharing"                       |
| <b>PidNameContentClass</b> (section 2.2.6.1)                                   | 0x806d      | PtypString    | "Sharing"                           |
| <b>PidTagNormalizedSubject</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.10) | 0x0E1D      | PtypString    | "Denied: sharing request: calendar" |
| <b>PidTagSubjectPrefix</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.9)      | 0x003D      | PtypString    | "" (a zero-length string)           |
| <b>PidLidSharingProviderGuid</b> (section 2.2.2.12)                            | 0x8243      | PtypBinary    | (See Figure 3)                      |
| <b>PidNameXSharingProviderGuid</b> (section 2.2.2.13)                          | 0x836F      | PtypString    | "AEF006000000000C000000000000046"   |
| <b>PidLidSharingProviderName</b> (section 2.2.2.14)                            | 0x8244      | PtypString    | "Microsoft Exchange"                |
| <b>PidNameXSharingProviderName</b> (section 2.2.2.15)                          | 0x8370      | PtypString    | "Microsoft Exchange"                |

| Property   | Property ID | Property Type | Value                               |
|--|-------------|---------------|-------------------------------------|
| <b>PidLidSharingProviderUrl</b><br>(section <a href="#">2.2.2.16</a> )     | 0x8245      | PtypString    | "HTTP://www.microsoft.com/exchange" |
| <b>PidNameXSharingProviderUrl</b><br>(section <a href="#">2.2.2.17</a> )   | 0x8371      | PtypString    | "HTTP://www.microsoft.com/exchange" |
| <b>PidLidSharingConfigurationUrl</b><br>(section <a href="#">2.2.2.3</a> ) | 0x83D0      | PtypString    | "" (a zero-length string)           |
| <b>PidNameXSharingConfigUrl</b><br>(section <a href="#">2.2.2.4</a> )      | 0x8377      | PtypString    | "" (a zero-length string)           |
| <b>PidLidSharingFlavor</b> (section <a href="#">2.2.2.5</a> )              | 0x823D      | PtypInteger32 | 0x00025100                          |
| <b>PidNameXSharingFlavor</b><br>(section <a href="#">2.2.2.6</a> )         | 0x836D      | PtypString    | "25100"                             |
| <b>PidLidSharingCapabilities</b><br>(section <a href="#">2.2.2.1</a> )     | 0x823C      | PtypInteger32 | 0x00040290                          |
| <b>PidNameXSharingCapabilities</b><br>(section <a href="#">2.2.2.2</a> )   | 0x836C      | PtypString    | "40290"                             |
| <b>PidLidSharingLocalType</b> (section <a href="#">2.2.2.10</a> )          | 0x824F      | PtypString    | "IPF.Appointment"                   |
| <b>PidNameXSharingLocalType</b><br>(section <a href="#">2.2.2.11</a> )     | 0x8379      | PtypString    | "IPF.Appointment"                   |
| <b>PidLidSharingInitiatorEntryId</b><br>(section <a href="#">2.2.2.7</a> ) | 0x8249      | PtypBinary    | (See Figure 4)                      |
| <b>PidLidSharingInitiatorName</b><br>(section <a href="#">2.2.2.8</a> )    | 0x8029      | PtypString    | user12                              |
| <b>PidLidSharingInitiatorSmtip</b><br>(section <a href="#">2.2.2.9</a> )   | 0x8248      | PtypString    | user12@fabrikam.com                 |

Figure 3 shows the value of the **PidLidSharingProviderGuid** property. The size of the value is 16 bytes.

```
0000: ae f0 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 .....F
```

Figure 4 shows the value of the **PidLidSharingInitiatorEntryId** property. The size of the value is 125 bytes.

```
0000: 00 00 00 00 dc a7 40 c8 c0 42 10 1a b4 b9 08 00 .....@..B.....
0010: 2b 2f e1 82 01 00 00 00 00 00 00 2f 6f 3d 46 +/...../o=F
0020: 69 72 73 74 20 4f 72 67 61 6e 69 7a 61 74 69 6f irst Organizatio
0030: 6e 2f 6f 75 3d 45 78 63 68 61 6e 67 65 20 41 64 n/ou=Exchange Ad
0040: 6d 69 6e 69 73 74 72 61 74 69 76 65 20 47 72 6f ministrative Gro
0050: 75 70 20 28 46 59 44 49 42 4f 48 46 32 33 53 50 up (FYDIBOHF23SP
0060: 44 4c 54 29 2f 63 6e 3d 52 65 63 69 70 69 65 6e DLT)/cn=Recipien
```

After addressing the message as specified in [\[MS-OXOMSG\]](#), the client uses **RopSubmitMessage** ([\[MS-OXCROPS\]](#) section 2.2.7.1) to send the message to Kendall and then uses **RopRelease** ([\[MS-OXCROPS\]](#) section 2.2.15.3) to release the Message object.

Then, the client uses **RopOpenMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.1) to open the sharing request. The server returns a success code and a handle to the Message object.

The client uses **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) to set the sharing properties on the sharing request to indicate that the client has sent a sharing response denying the request and the time at which it was sent, as follows:

| Property  | Property ID | Property type | Data                          | Value                      |
|---|-------------|---------------|-------------------------------|----------------------------|
| <b>PidLidSharingResponseType</b> (section <a href="#">2.2.3.2</a> ) | 0x83E4      | PtypInteger32 | 02 00 00 00                   | 0x00000002                 |
| <b>PidLidSharingResponseTime</b> (section <a href="#">2.2.3.1</a> ) | 0x83E3      | PtypTime      | 00 9A C2<br>CF E3 7F C8<br>01 | 2008/03/06<br>23:43:00.000 |

The client uses **RopSaveChangesMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.3) to save the changes and uses **RopRelease** ([\[MS-OXCROPS\]](#) section 2.2.15.3) to release the Message object.

### 4.3 Accepting a Sharing Request

Ryan wants to send a sharing response accepting the sharing request described in section [4.1](#). The client uses **RopCreateMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.2) to create a new Message object. The server returns a success code and a handle to a Message object.

The client uses **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) to set the sharing properties for a sharing response that indicates that the request was accepted and provides the information required to locate the requested folder, as follows:

| Property   | Property ID | Property type | Value                                |
|--|-------------|---------------|--------------------------------------|
| <b>PidTagMessageClass</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.3)       | 0x001A      | PtypString    | "IPM.Sharing"                        |
| <b>PidNameContentClass</b> (section <a href="#">2.2.6.1</a> )                  | 0x806d      | PtypString    | "Sharing"                            |
| <b>PidTagNormalizedSubject</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.10) | 0x0E1D      | PtypString    | "Allowed: sharing request: calendar" |
| <b>PidTagSubjectPrefix</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.9)      | 0x003D      | PtypString    | "" (a zero-length string)            |
| <b>PidLidSharingProviderGuid</b> (section <a href="#">2.2.2.12</a> )           | 0x8243      | PtypBinary    | (See Figure 5)                       |
| <b>PidNameXSharingProviderGuid</b> (section <a href="#">2.2.2.13</a> )         | 0x836F      | PtypString    | AEF0060000000000C0000000<br>00000046 |

| <b>Property</b>   | <b>Property ID</b> | <b>Property type</b> | <b>Value</b>                        |
|---|--------------------|----------------------|-------------------------------------|
| <b>PidLidSharingProviderName</b> (section <a href="#">2.2.2.14</a> )    | 0x8244             | PtypString           | "Microsoft Exchange"                |
| <b>PidNameXSharingProviderName</b> (section <a href="#">2.2.2.15</a> )  | 0x8370             | PtypString           | "Microsoft Exchange"                |
| <b>PidLidSharingProviderUrl</b> (section <a href="#">2.2.2.16</a> )     | 0x8245             | PtypString           | "HTTP://www.microsoft.com/exchange" |
| <b>PidNameXSharingProviderUrl</b> (section <a href="#">2.2.2.17</a> )   | 0x8371             | PtypString           | "HTTP://www.microsoft.com/exchange" |
| <b>PidLidSharingConfigurationUrl</b> (section <a href="#">2.2.2.3</a> ) | 0x83D0             | PtypString           | "" (a zero-length string)           |
| <b>PidNameXSharingConfigUrl</b> (section <a href="#">2.2.2.4</a> )      | 0x8377             | PtypString           | "" (a zero-length string)           |
| <b>PidLidSharingFlavor</b> (section <a href="#">2.2.2.5</a> )           | 0x823D             | PtypInteger32        | 0x00023310                          |
| <b>PidNameXSharingFlavor</b> (section <a href="#">2.2.2.6</a> )         | 0x836D             | PtypString           | "23310"                             |
| <b>PidLidSharingCapabilities</b> (section <a href="#">2.2.2.1</a> )     | 0x823C             | PtypInteger32        | 0x00040290                          |
| <b>PidNameXSharingCapabilities</b> (section <a href="#">2.2.2.2</a> )   | 0x836C             | PtypString           | "40290"                             |
| <b>PidLidSharingLocalType</b> (section <a href="#">2.2.2.10</a> )       | 0x824F             | PtypString           | "IPF.Appointment"                   |
| <b>PidNameXSharingLocalType</b> (section <a href="#">2.2.2.11</a> )     | 0x8379             | PtypString           | "IPF.Appointment"                   |
| <b>PidLidSharingInitiatorEntryId</b> (section <a href="#">2.2.2.7</a> ) | 0x8249             | PtypBinary           | (See Figure 6)                      |
| <b>PidLidSharingInitiatorName</b> (section <a href="#">2.2.2.8</a> )    | 0x8029             | PtypString           | user10                              |
| <b>PidLidSharingInitiatorSsmtp</b> (section <a href="#">2.2.2.9</a> )   | 0x8248             | PtypString           | user10@fabrikam.com                 |
| <b>PidLidSharingRemoteName</b> (section <a href="#">2.2.4.1</a> )       | 0x8026             | PtypString           | "Calendar"                          |
| <b>PidNameXSharingRemoteName</b> (section <a href="#">2.2.4.2</a> )     | 0x8373             | PtypString           | "Calendar"                          |
| <b>PidLidSharingRemoteType</b> (section <a href="#">2.2.4.5</a> )       | 0x8247             | PtypString           | "IPF.Appointment"                   |
| <b>PidNameXSharingRemoteType</b> (section <a href="#">2.2.4.6</a> )     | 0x8376             | PtypString           | "IPF.Appointment"                   |
| <b>PidLidSharingRemoteUid</b> (section                                  | 0x8246             | PtypString           | 00000000B0FCA4F63C21A642            |

| <b>Property</b>  | <b>Property ID</b> | <b>Property type</b> | <b>Value</b>  |
|--|--------------------|----------------------|---|
| <a href="#">2.2.4.7)</a>   |                    |                      | BD4B8F1BDBA04BC60100612A<br>7BAB49F64E4B9C52DBFB5A53<br>AA1C000000F04EEF0000  |
| <b>PidNameXSharingRemoteUid</b><br>(section <a href="#">2.2.4.8</a> )    | 0x8374             | PtypString           | 00000000B0FCA4F63C21A642B<br>D4B8F1BDBA04BC60100612A7<br>BAB49F64E4B9C52DBFB5A53A<br>A1C000000F04EEF0000  |
| <b>PidLidSharingRemoteStoreUid</b><br>(section <a href="#">2.2.4.3</a> ) | 0x83E1             | PtypString           | 000000038A1BB1005E5101A<br>A1BB08002B2A56C20000454D<br>534D44422E444C4C000000000<br>0000001B55FA20AA6611CD9<br>BC800AA002FC45A0C00000033<br>36353952392D413131002F6F3<br>D4669727374204F7267616E69<br>7A6174696F6E2F6F753D45786<br>368616E67652041646D696E69<br>73747261746976652047726F7<br>570202846594449424F484632<br>335350444C54292F636E3D526<br>563697069656E74732F636E3D<br>75736572313000  |
| <b>PidNameXSharingRemoteStoreUi d</b> (section <a href="#">2.2.4.4</a> ) | 0x8375             | PtypString           | 000000038A1BB1005E5101AA<br>1BB08002B2A56C20000454D5<br>34D44422E444C4C0000000000<br>0000001B55FA20AA6611CD9B<br>C800AA002FC45A0C000000333<br>6353952392D413131002F6F3D<br>4669727374204F7267616E697<br>A6174696F6E2F6F753D457863<br>68616E67652041646D696E697<br>3747261746976652047726F75<br>70202846594449424F4846323<br>35350444C54292F636E3D5265<br>63697069656E74732F636E3D7<br>5736572313000 |

Figure 5 shows the value of the **PidLidSharingProviderGuid** property. The size of the value is 16 bytes.

```
0000: ae f0 06 00 00 00 00 00 c0 00 00 00 00 00 00 00 46 .....F
```

Figure 6 shows the value of the **PidLidSharingInitiatorEntryId** property. The size of the value is 125 bytes.

```
0000: 00 00 00 00 dc a7 40 c8 c0 42 10 1a b4 b9 08 00 .....@...B.....  
0010: 2b 2f e1 82 01 00 00 00 00 00 00 2f 6f 3d 46 +/...../o=F  
0020: 69 72 73 74 20 4f 72 67 61 6e 69 7a 61 74 69 6f irst Organizatio  
0030: 6e 2f 6f 75 3d 45 78 63 68 61 6e 67 65 20 41 64 n/ou=Exchange Ad  
0040: 6d 69 6e 69 73 74 72 61 74 69 76 65 20 47 72 6f ministrative Gro  
0050: 75 70 20 28 46 59 44 49 42 4f 48 46 32 33 53 50 up (FYDIBOHF23SP  
0060: 44 4c 54 29 2f 63 6e 3d 52 65 63 69 70 69 65 6e DLT)/cn=Recipien
```

After properly addressing the message as specified in [\[MS-OXOMSG\]](#), the client uses **RopSubmitMessage** ([\[MS-OXCROPS\]](#) section 2.2.7.1) to send the message to Kendall and then uses **RopRelease** ([\[MS-OXCROPS\]](#) section 2.2.15.3) to release the Message object.

The client then grants Kendall permission to the folder as specified in [\[MS-OXODLGT\]](#).

Then the client uses **RopOpenMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.1) to open the sharing request. The server returns a success code and a handle to the Message object.

The client uses **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) to set the sharing properties on the sharing request to indicate that the client has sent a sharing response accepting the request and the time at which it was sent, as follows:

| <b>Property</b>  | <b>Property ID</b> | <b>Property type</b> | <b>Data</b>                   | <b>Value</b>               |
|--|--------------------|----------------------|-------------------------------|----------------------------|
| <b>PidLidSharingResponseType</b><br>(section <a href="#">2.2.3.2</a> ) | 0x83E4             | PtypInteger32        | 01 00 00 00                   | 0x00000001                 |
| <b>PidLidSharingResponseTime</b><br>(section <a href="#">2.2.3.1</a> ) | 0x83E3             | PtypTime             | 00 9A C2<br>CF E3 7F C8<br>01 | 2008/03/06<br>23:43:00.000 |

The client uses **RopSaveChangesMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.3) to save the changes and uses **RopRelease** ([\[MS-OXCROPS\]](#) section 2.2.15.3) to release the Message object.

## 5 Security

### 5.1 Security Considerations for Implementers

There are no special security considerations specific to the Sharing Message Object Protocol. General security considerations pertaining to the underlying transport apply, as specified in [\[MS-OXOMSG\]](#) and [\[MS-OXCMSG\]](#).

### 5.2 Index of Security Parameters

None.

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010
- Microsoft® Office Outlook® 2007
- Microsoft® Outlook® 2010

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2.2.8:](#) Office Outlook 2007 sets the value but, upon receipt, ignores the property and queries the address book for its value based on **PidLidSharingInitiatorEntryId** ([\[MS-OXPROPS\]](#) section 2.242).

[<2> Section 2.2.2.9:](#) Office Outlook 2007 sets the value but, upon receipt, ignores the property and queries the address book for its value based on **PidLidSharingInitiatorEntryId** ([\[MS-OXPROPS\]](#) section 2.242).

[<3> Section 2.2.2.14:](#) Office Outlook 2007 sets the value but, upon receipt, ignores the property and instead uses a custom value based on the **PidLidSharingProviderGuid** property (section [2.2.2.12](#)).

[<4> Section 2.2.2.15:](#) Office Outlook 2007 sets the value but, upon receipt, ignores the property and instead uses a custom value based on the **PidLidSharingProviderGuid** property (section [2.2.2.12](#)).

[<5> Section 2.2.2.16:](#) Office Outlook 2007 sets the value but, upon receipt, ignores the property and instead uses a custom value based on the **PidLidSharingProviderGuid** property (section [2.2.2.12](#)).

[<6> Section 2.2.2.17:](#) Office Outlook 2007 sets the value but, upon receipt, ignores the property and instead uses a custom value based on the **PidLidSharingProviderGuid** property (section [2.2.2.12](#))

[<7> Section 2.2.4:](#) Office Outlook 2007 sets these properties.

[<8> Section 2.2.4.5:](#) Office Outlook 2007 sets this property to the same value as the **PidLidSharingLocalType** property (section [2.2.2.10](#)) but uses only the **PidLidSharingLocalType** property to determine behavior.

[<9> Section 2.2.4.6:](#) Office Outlook 2007 sets this property to the same value as the **PidLidSharingLocalType** property (section [2.2.2.10](#)) but uses only the **PidLidSharingLocalType** property to determine behavior.

[<10> Section 2.2.5:](#) Office Outlook 2007 sets differing subsets of these properties in different scenarios but their values have no meaning in the context of this protocol.

[<11> Section 3.1:](#) Office Outlook 2007 only create and operate upon Sharing Message objects that are stored by Exchange 2007 and Exchange 2010.

## 7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 8 Index

### A

Abstract data model  
[client](#) 16  
[Additional Property Constraints message](#) 15  
[Applicability](#) 7

### C

[Capability negotiation](#) 7  
[Change tracking](#) 37  
Client  
[abstract data model](#) 16  
[initialization](#) 16  
[message processing](#) 23  
[other local events](#) 23  
[overview](#) 16  
[sequencing rules](#) 23  
[timer events](#) 23  
[timers](#) 16  
[Common Message Object Properties message](#) 8  
[Common Sharing Message Object Properties message](#) 9

### D

Data model - abstract  
[client](#) 16

### F

[Fields - vendor-extensible](#) 7

### G

[Glossary](#) 5

### I

[Ignored Properties message](#) 13  
[Implementer - security considerations](#) 34  
[Index of security parameters](#) 34  
[Informative references](#) 6  
Initialization  
[client](#) 16  
[Introduction](#) 5

### M

Message processing  
[client](#) 23  
Messages  
[Additional Property Constraints](#) 15  
[Common Message Object Properties](#) 8  
[Common Sharing Message Object Properties](#) 9  
[Ignored Properties](#) 13  
[Sharing Invitation Properties](#) 12  
[Sharing Request Properties](#) 12  
[transport](#) 8

### N

[Normative references](#) 6

### O

Other local events  
[client](#) 23  
[Overview \(synopsis\)](#) 6

### P

[Parameters - security index](#) 34  
[Preconditions](#) 7  
[Prerequisites](#) 7  
[Product behavior](#) 35

### R

References  
[informative](#) 6  
[normative](#) 6  
[Relationship to other protocols](#) 7

### S

Security  
[implementer considerations](#) 34  
[parameter index](#) 34  
Sequencing rules  
[client](#) 23  
[Sharing Invitation Properties message](#) 12  
[Sharing Request Properties message](#) 12  
[Standards assignments](#) 7

### T

Timer events  
[client](#) 23  
Timers  
[client](#) 16  
[Tracking changes](#) 37  
[Transport](#) 8

### V

[Vendor-extensible fields](#) 7  
[Versioning](#) 7