

[MS-OXSHRMSG]: Sharing Message Attachment Schema

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
11/04/2009	1.0.0	Major	Initial Availability
02/10/2010	1.1.0	Minor	Updated the technical content.

Table of Contents

1	Introduction	4
1.1	Glossary.....	4
1.2	References.....	4
1.2.1	Normative References	4
1.2.2	Informative References	5
1.3	Structure Overview	5
1.4	Relationship to Protocols and Other Structures	5
1.5	Applicability Statement.....	5
1.6	Versioning and Localization	5
1.7	Vendor-Extensible Fields	5
2	Structures.....	6
2.1	Sharing Message Attachment Namespace	6
2.2	Sharing Message Attachment Processing Instructions	6
2.3	Sharing Message Schema	6
2.3.1	DataTypeType Simple Type	6
2.3.2	InitiatorType Complex Type.....	7
2.3.3	InvitationType Complex Type	7
2.3.4	t:ProviderType Complex Type.....	8
2.3.5	t:Providers Complex Type.....	8
2.3.6	SharingMesasge Element.....	9
3	Structure Examples	10
4	Security Considerations	12
5	Appendix A: Product Behavior	13
6	Change Tracking	14
7	Index	16

1 Introduction

This document specifies the Sharing Message Attachment schema, which defines the schema for an **XML** document that is used to establish a sharing relationship between two servers on behalf of client applications. This document contains identification information and encrypted tokens that enable the two servers to authenticate and establish the sharing relationship.

1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

Augmented Backus-Naur Form (ABNF)
shared folder
XML
XML namespace
XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", June 2008.

[MS-OXWSMSHR] Microsoft Corporation, "[Folder Sharing Web Service Protocol Specification](#)", July 2009.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.

[RFC5234] Crocker, D. and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 5234, January 2008, <http://www.ietf.org/rfc/rfc5234.txt>.

[XML] Bray, T., et al., "Extensible Markup Language (XML) 1.0 (Fifth Edition)", November 2008, <http://www.w3.org/TR/REC-xml/>.

[XMLENC] Eastlake, D., Ed., Reagle, J., Ed., Immamura, T., Dillaway, B., Simon, E., "XML Encryption Syntax and Processing", W3C Recommendation, December 2002, <http://www.w3c.org/TR/2002/REC-xmlenc-core-20021210/>.

[XMLNS] World Wide Web Consortium, "Namespaces in XML 1.0 (Second Edition)", August 2006, <http://www.w3.org/TR/REC-xml-names/>.

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmllschema-1-20010502/>.

[XMLSCHEMA2] Biron, P.V., Ed., and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmllschema-2-20010502/>.

1.2.2 Informative References

None.

1.3 Structure Overview

The Sharing Message Attachment schema specifies the authentication and identification information that is required for two servers to set up a sharing relationship on behalf of client applications. The sharing message attachment is composed of three main elements: the type of invitation, the e-mail address and name of the initiator, and the sharing invitation.

1.4 Relationship to Protocols and Other Structures

The Sharing Message Attachment schema is used by the Folder Sharing Web Service protocol [\[MS-OXWSMSHR\]](#) to provide authentication and identification information when a **shared folder** relationship is established between two servers. The operations that provide the encrypted token and folder information that is required by the servers to establish the sharing relationship are defined in [\[MS-OXWSMSHR\]](#).

Encrypted data elements of the sharing message structure are defined in [\[MS-OXWSMSHR\]](#). The format of the encrypted data that are contained in the encrypted data elements is defined in [\[XMLENC\]](#).

1.5 Applicability Statement

The XML document that is defined by the Sharing Message Attachment schema enables servers to share information on behalf of client applications with less risk of exposing secrets to those client applications. The encrypted data section of the sharing message is passed between the client applications while the information within the sharing message is protected.

1.6 Versioning and Localization

This document covers versioning issues in the following areas:

- **Structure versions:** None.
- **Localization:** None.

1.7 Vendor-Extensible Fields

None.

2 Structures

2.1 Sharing Message Attachment Namespace

The elements of the sharing message attachment are defined in the following namespace:

<http://schemas.microsoft.com/exchange/sharing/2008/>

Sharing message attachments use encryption elements that are defined by [\[XMLENC\]](#):

<http://www.w3.org/2001/04/xmlenc>

Sharing message attachments use encryption data elements that are defined by [\[MS-OXWSMSHR\]](#):

<http://schemas.microsoft.com/exchange/services/2006/types>

2.2 Sharing Message Attachment Processing Instructions

The following XML processing instruction tag, as specified in [\[XML\]](#) section 2.6, MUST appear in the sharing message attachment file:

```
<?xml version="1.0"?>
```

A formal definition in **Augmented Backus-Naur Form (ABNF)**, as specified in [\[RFC5234\]](#), of the XML processing instructions is as follows:

```
UDC_PI = '<?MicrosoftWindowsSharePointServices ' CONTENT_ID_TYPE '?>' CRLF  
CONTENT_ID_TYPE = 'ContentTypeID="0x010100B4CBD48E029A4AD8B62CB0E41868F2B0"'
```

2.3 Sharing Message Schema

The following sections specify the elements and attributes of the sharing message attachment.

2.3.1 Data Type Type Simple Type

The **Data Type Type** simple type defines the valid sharing message attachment types.

```
<xs:simpleType name="t:DataTypeType">  
  <xs:restriction  
    base="xs:string"  
  >  
  <xs:enumeration  
    value="calendar"  
  />  
</xs:restriction>  
</xs:simpleType>
```

Enumeration

The following value is defined by the **t:DataTypeType** simple type:

Value	Description
calendar	The sharing message attachment is for a calendar.

2.3.2 InitiatorType Complex Type

The **InitiatorType** complex type specifies the name and e-mail address of the entity that initiates the sharing relationship.

```
<xs:complexType name="InitiatorType">
  <xs:sequence>
    <xs:element name="Name"
      type="xs:string"
    />
    <xs:element name="SmtpAddress"
      type="xs:string"
    />
  </xs:sequence>
</xs:complexType>
```

Child Elements

Element	Type	Description
Name	xs:string	The display name of the entity that initiates the sharing relationship.
SmtpAddress	xs:string	The e-mail address of the entity that initiates the sharing relationship.

2.3.3 InvitationType Complex Type

The **InvitationType** complex type contains a list of folders to share and the encrypted information that is required to set up the shared folders.

```
<xs:complexType name="InvitationType">
  <xs:sequence>
    <xs:element name="Providers"
      type="t:ProvidersType"
    />
  </xs:sequence>
</xs:complexType>
```

Child Elements

Element	Type	Description
Providers	t:ProvidersType	One or more folders to share and the encrypted information that is required to set up the shared folders.

2.3.4 t:ProviderType Complex Type

The **ProviderType** complex type specifies a shared folder name and the encrypted information required to set up the shared folder.

```
<xs:complexType name="ProviderType">
  <xs:sequence>
    <xs:element name="FolderId"
      type="xs:string"
    />
    <xs:element name="EncryptedSharedFolderDataCollection"
      type="t:ArrayOfEncryptedSharedFolderDataType"
    />
  </xs:sequence>
  <xs:attribute name="Type"
    type="xs:string"
  />
  <xs:attribute name="TargetRecipients"
    type="xs:string"
  />
</xs:complexType>
```

Child Elements

Element	Type	Description
FolderId	xs:string	The identifier for the shared folder.
EncryptedSharedFolderDataCollection	t:ArrayOfEncryptedSharedFolderDataType	The encrypted authentication token, as specified in [XMLENC] .

Attributes

Name	Type	Description
Type	xs:string	Specifies the sharing provider type. MUST be "ms-exchange-external".
TargetRecipients	xs:string	Specifies a semi-colon delimited list of e-mail addresses that this provider applies to.

2.3.5 t:Providers Complex Type

The **ProvidersType** complex type specifies one or more shared folders and the encrypted data that is required to share the folders.

```
<xs:complexType>
  <xs:sequence>
    <xs:element name="Provider"
      type="t:ProviderType"
      maxOccurs="unbounded"
    />
```

```
</xs:sequence>
</xs:complexType>
```

Child Elements

Element	Type	Description
Provider	t:ProviderType	One or more shared folder providers.

2.3.6 SharingMesasge Element

The <SharingMessage> element provides a container for the sharing message attachment elements.

```
<xs:element name="SharingMesasge">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="DataType"
        type="t:DataTypeType"
      />
      <xs:element name="Initiator"
        type="t:InitiatorType"
      />
      <xs:element name="Invitation"
        type="t:InvitationType"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

Child Elements

Element	Type	Description
DataType	t:DataTypeType	The type of the sharing message attachment.
Initiator	t:InitiatorType	The name and e-mail address of the sender of the sharing message attachment.
Invitation	t:InvitationType	The details of the sharing invitation.

3 Structure Examples

The following is the complete **XML schema** for the sharing message attachment XML document.

[XML Schema]

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/sharing/2008"
  xmlns:tns="http://schemas.microsoft.com/exchange/sharing/2008"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
  xmlns:enc="http://www.w3.org/2001/04/xmlenc#"
  xmlns:ews="http://schemas.microsoft.com/exchange/services/2006/types"
  targetNamespace="http://schemas.microsoft.com/exchange/sharing/2008"
  elementFormDefault="qualified" version="Exchange2010" id="types">

  <xs:import namespace="http://www.w3.org/2001/04/xmlenc#" />
  <xs:import namespace="http://schemas.microsoft.com/services/exchange/2006/types" />

  <xs:simpleType name="DataTypeType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="calendar"/>
    </xs:restriction>
  </xs:simpleType>

  <xs:complexType name="InitiatorType">
    <xs:sequence>
      <xs:element name="Name" type="xs:string"/>
      <xs:element name="SmtpAddress" type="xs:string" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="ProviderType">
    <xs:sequence>
      <xs:element name="FolderId" type="xs:string"/>
      <xs:element name="EncryptedSharedFolderDataCollection"
        type="ews:ArrayOfEncryptedSharedFolderDataType"/>
    </xs:sequence>
    <xs:attribute name="Type" type="xs:string"/>
    <xs:attribute name="TargetRecipients" type="xs:string" />
  </xs:complexType>

  <xs:complexType name="ProvidersType">
    <xs:sequence>
      <xs:element name="Provider" type="t:ProviderType" maxOccurs="unbounded" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="InvitationType">
    <xs:sequence>
      <xs:element name="Title" type="xs:string" minOccurs="0" />
      <xs:element name="Providers" type="t:ProvidersType"/>
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="RequestType">
```

```

<xs:sequence>
  <xs:element name="Providers" type="t:ProvidersType" />
</xs:sequence>
</xs:complexType>

<xs:complexType name="AcceptOfRequestType">
  <xs:sequence>
    <xs:element name="Title" type="xs:string" minOccurs="0" />
    <xs:element name="Providers" type="t:ProvidersType" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="DenyOfRequestType">
  <xs:sequence>
    <xs:element name="Providers" type="t:ProvidersType" />
  </xs:sequence>
</xs:complexType>

<xs:element name="SharingMessage">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="DataType" type="t:DataTypeType"/>
      <xs:element name="Initiator" type="t:InitiatorType"/>
      <xs:choice>
        <xs:element name="AcceptOfRequest" type="t:AcceptOfRequestType" />
        <xs:element name="DenyOfRequest" type="t:DenyOfRequestType" />
        <xs:sequence>
          <xs:element name="RequestType" type="t:RequestType" minOccurs="0" />
          <xs:element name="Invitation" type="t:InvitationType" minOccurs="0" />
        </xs:sequence>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:schema>

```

4 Security Considerations

None.

5 Appendix A: Product Behavior

The information in this specification is applicable to the following product versions. References to product versions include released service packs.

- Microsoft Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

6 Change Tracking

This section identifies changes made to [MS-OXSHRMSG] protocol documentation between November 2009 and February 2010 releases. Changes are classed as major, minor, or editorial.

Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- A protocol is deprecated.
- The removal of a document from the documentation set.
- Changes made for template compliance.

Minor changes do not affect protocol interoperability or implementation. Examples are updates to fix technical accuracy or ambiguity at the sentence, paragraph, or table level.

Editorial changes apply to grammatical, formatting, and style issues.

No changes means that the document is identical to its last release.

Major and minor changes can be described further using the following revision types:

- New content added.
- Content update.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.

- Content removed for template compliance.
- Obsolete document removed.

Editorial changes always have the revision type "Editorially updated."

Some important terms used in revision type descriptions are defined as follows:

Protocol syntax refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.

Protocol revision refers to changes made to a protocol that affect the bits that are sent over the wire.

Changes are listed in the following table. If you need further information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
1.1 Glossary	Added the terms "Augmented Backus-Naur Form (ABNF)" and "shared folder".	N	Content update.
1.2.1 Normative References	Added reference information for [RFC5234] and [XML].	N	Content update.
1.3 Structure Overview	54300 Removed "(Synopsis)" from section heading.	N	Content update.

7 Index

A

[Applicability](#) 5

C

[Change tracking](#) 14

E

[Example](#) 10

G

[Glossary](#) 4

I

[Introduction](#) 4

L

[Localization](#) 5

N

[Normative references](#) 4

O

[Overview](#) 5

P

[Product behavior](#) 13

R

References

[normative](#) 4

[Relationship to protocols and other structures](#) 5

T

[Tracking changes](#) 14

V

[Versioning and Localization](#) 5