

[MS-OXTNEF]: Transport Neutral Encapsulation Format (TNEF) Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here:
<http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.
- **Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and

network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary			
Author	Date	Version	Comments
Microsoft Corporation	April 4, 2008	0.1	Initial Availability.
Microsoft Corporation	April 25, 2008	0.2	Revised and updated property names and other technical content.
Microsoft Corporation	June 27, 2008	1.0	Initial Release.
Microsoft Corporation	August 6, 2008	1.01	Revised and edited technical content.
Microsoft Corporation	September 3, 2008	1.02	Revised and edited technical content.
Microsoft Corporation	December 3, 2008	1.03	Revised and edited technical content.
Microsoft Corporation	March 4, 2009	1.04	Revised and edited technical content.
Microsoft Corporation	April 10, 2009	2.0	Updated technical content and applicable product releases.

Table of Contents

1	<i>Introduction</i>	5
1.1	Glossary	5
1.2	References	6
1.2.1	Normative References	6
1.2.2	Informative References	7
1.3	Structure Overview	7
1.4	Relationship to Protocols and Other Structures	7
1.5	Applicability Statement	8
1.6	Versioning	8
2	<i>Structure</i>	8
2.1	Additional Terms Used in this Document	8
2.1.1	Address Representations	8
2.2	ABNF Description	9
2.3	Attributes	13
2.3.1	attTnefVersion	13
2.3.2	attOemCodepage	13
2.3.3	attFrom	13
2.3.4	Date Attributes	15
2.3.5	Message Class Attributes	15
2.3.6	Conversation-Tracking Attributes	16
2.3.7	attSubject	16
2.3.8	attMessageStatus	17
2.3.9	attBody	17
2.3.10	attPriority	17
2.3.11	attAttachData	17
2.3.12	attAttachTitle	18
2.3.13	attAttachMetaFile	18
2.3.14	attAttachTransportFilename	18
2.3.15	attAttachRendData	18
2.3.16	attOwner	19
2.3.17	attSentFor	20
2.3.18	attDelegate	20
2.3.19	attAidOwner	21
2.3.20	attRequestRes	21
2.3.21	attMsgProps	21
2.3.22	attRecipTable	21
2.3.23	attAttachment	21
2.4	Encapsulated Message Properties	21
3	<i>Structure Examples</i>	26
3.1	Sample Message	26
3.2	Sample Meeting Response	32
4	<i>Security Considerations</i>	33

4.1	attRecipTable, attFrom.....	33
5	<i>Other Compatibility Issues.....</i>	33
5.1	attOemCodepage Handling	33
5.1.1	Encoding by TNEF Writer.....	33
5.1.2	Decoding by TNEF Reader	34
5.2	TNEF Encapsulation vs. Outer Wrapper Attributes.....	34
5.2.1	attBody Handling	34
5.2.2	attRecipTable Handling	35
5.2.3	attFrom Handling	35
5.2.4	attSubject Handling	35
6	<i>Appendix A: Office/Exchange Behavior.....</i>	35
Index.....		37

1 Introduction

This document specifies an encoding method for transmitting rich properties of electronic mail messages over a serial data stream. The result might be transported as a stream, as a file attachment in an arbitrary transport, or as a **MIME** [RFC2045] entity body on an Internet transport.

1.1 Glossary

The following terms are defined in [MS-OXGLOS]:

Augmented Backus-Naur Form (ABNF)

binary large object (BLOB)

body part

character set

code page

EntryID

GUID

little-endian

message class

Message object

metafile

MIME

plain text

property

recipient

Transport Neutral Encapsulation Format (TNEF)

Unicode

UTF-16LE (Unicode Transformation Format, 16-bits, Little-Endian)

The following terms are specific to this document:

CLSID: A **GUID** that is associated with a COM class.

Interface Identifier (IID): A **GUID** that uniquely identifies a particular COM interface.

TNEF Reader: The entity that is decoding a **TNEF** structure after message reception, for the purpose of reconstructing the rich properties that are contained in the stream.

TNEF Writer: The entity that is encoding/building a **TNEF** structure for the purpose of transporting rich properties.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

[MS-DTYP] Microsoft Corporation, "Windows Data Types", March 2007,
<http://go.microsoft.com/fwlink/?LinkId=111558>.

[MS-OAUT] Microsoft Corporation, "OLE Automation Protocol Specification", March 2007,
<http://go.microsoft.com/fwlink/?LinkId=112419>.

[MS-OXCDATA] Microsoft Corporation, "Data Structures Protocol Specification", June 2008.

[MS-OXGLOS] Microsoft Corporation, "Exchange Server Protocols Master Glossary", June 2008.

[MS-OXOCAL] Microsoft Corporation, "Appointment and Meeting Object Protocol Specification", June 2008.

[MS-OXOMSG] Microsoft Corporation, "E-Mail Object Protocol Specification", June 2008.

[MS-OXPROPS] Microsoft Corporation, "Exchange Server Protocols Master Property List Specification", June 2008.

[RFC2045] Freed, N., et al., "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", RFC 2045, November 1996,
<http://www.ietf.org/rfc/rfc2045.txt>.

[RFC2046] Freed, N. and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", RFC 2046, November 1996, <http://www.ietf.org/rfc/rfc2046.txt>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.

[RFC4234] Crocker, D., Ed. and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 4234, October 2005, <http://www.ietf.org/rfc/rfc4234.txt>.

[UTR#17] Whistler, K., Davis, M., and Freytag, A., "Unicode Technical Report #17: Character Encoding Model", September 2004, <http://www.unicode.org/reports/tr17>.

1.2.2 Informative References

[MacBin] Apple Corporation, "Macintosh Binary Transfer Format ("MacBinary III") Standard Proposal", http://www.lazerware.com/macbinary/macbinary_iii.html.

[MS-WMF] Microsoft Corporation, "Windows Metafile Format Specification", June 2007, <http://go.microsoft.com/fwlink/?LinkId=112205>.

1.3 Structure Overview

Transport Neutral Encapsulation Format (TNEF) organizes a hierarchy of rich message **properties** into a flattened structure that can be represented as a serial data stream. The typical structure of a particular property within the stream is: identifier (which usually also includes type information), size (where not exactly determined by type), data. In some cases, as specified in this document, groups of properties or multiple-value properties include counts. Others might include "padding" to enforce a particular alignment of the data.

1.4 Relationship to Protocols and Other Structures

The structure is intended to permit the transmission of rich message **property** information over transports that have no mechanism for representing that information natively.

The structure can be included as a file attachment (winmail.dat), as a **MIME** [RFC2045] **body part** (using the "application/ms-tnef" media type), added to the transmitted **plain text** body using UUENCODE or a similar method, to be decoded at the **recipient** end, or transported from sender to recipient using whatever means are provided by the protocol employed in transmitting message information between them.

This document specifically covers the application of this structure for transmission of message data over **Simple Mail Transfer Protocol (SMTP)**, POP, IMAP, or other Internet protocols that incorporate MIME [RFC2045].

All numeric data types in the structure that are greater than one byte in size are **little-endian** and any handling of these values on platforms that are not little-endian are required to take this into account and perform the appropriate transformations to get correct numbers, counts, values, and so on.

Contents of string examples in this document will be shown in **Augmented Backus-Naur Form (ABNF)** [RFC4234] format. Where the string has a terminating zero character, this will also be in that format; for example, "user1@example.com" %x00. For the purpose of string examples, the different terminating zero character size in a **Unicode character set** will not be illustrated.

1.5 Applicability Statement

The original application of the structure was in the Microsoft Mail 3.0 Windows client, to permit the creation and representation of **message classes** other than simple e-mail messages, and some additional attributes that were not natively supported by the transport protocol.

This application was further extended to allow the transport of the rich set of properties required by applications such as Microsoft Office Outlook, including named properties [MS-OXPROPS]. For backward compatibility with the original implementation, a special attribute is used to encapsulate the new message properties, and those properties with analogues to the original implementation are usually represented using the original attribute syntax.

To avoid confusion, attributes using the original syntax will be referred to as "attributes" and the rich set of properties will be referred to as "properties" in this specification.

1.6 Versioning

None.

2 Structure

The TNEF stream starts with a signature and a legacy key value, an attribute containing a legacy version number, and an attribute containing the Windows **code page** used by the encoder for ANSI attributes and properties. After that, the stream is a series of attributes laid out, one after the other – message attributes followed by attachment attributes. Three special attributes contain the various message and attachment properties, two of which are counted lists; the third is a counted list of counted lists.

Each attribute is laid out as follows: ID, length (of the contained data), the data itself, and a simple 16-bit checksum of the bytes comprising the data.

Encapsulated properties SHOULD be encoded after the attributes. Values of encapsulated properties SHOULD be used instead of any conflicting mapped attribute values. Message attributes and properties SHOULD be encoded before attachment attributes and properties.

Each set of attachment attributes MUST begin with **attAttachRendData**, followed by any other attributes; attachment properties encoded in **attAttachment** SHOULD be last.

2.1 Additional Terms Used in this Document

2.1.1 Address Representations

Address elements other than **recipients**, such as From and Sender, are represented in a **Message object** by a group of four properties: display name, address type, e-mail address, **EntryID**. In subsequent sections these groups are referred to as described here.

PidTagReceivedRepresenting_XXX: Refers to **(PidTagReceivedRepresentingName, PidTagReceivedRepresentingAddressType, and PidTagReceivedRepresentingEmailAddress)**, or **PidTagReceivedRepresentingEntryId**, where either would suffice to fully represent the display name, e-mail transport type, and e-mail address of a particular recipient or person on behalf of whom a message was received. See [MS-OXPROPS] for details about the **PidTagReceivedRepresenting** message properties.

PidTagSender_XXX: Refers to **(PidTagSenderName, PidTagSenderAddressType, and PidTagSenderEmailAddress)**, or **PidTagSenderEntryId**, where either would suffice to fully represent the display name, e-mail transport type, and e-mail address of a sender or person on behalf of whom a message was sent. See [MS-OXPROPS] for more details the **PidTagSender** message properties.

PidTagSentRepresenting_XXX: Refers to **(PidTagSentRepresentingName, PidTagSentRepresentingAddressType, and PidTagSentRepresentingEmailAddress)**, or **PidTagSentRepresentingEntryId**, where either would suffice to fully represent the display name, e-mail transport type, and e-mail address of a sender or person on behalf of whom a message was sent. See [MS-OXPROPS] for more details about the **PidTagSentRepresenting** message properties.

2.2 ABNF Description

TNEFStream = TNEFHeader TNEFVersion OEMCodePage MessageData *AttachData

TNEFVersion = attrLevelMessage idTnefVersion Length TNEFVersionData Checksum

OEMCodePage = attrLevelMessage idOEMCodePage Length OEMCodePageData Checksum

MessageData = *MessageAttribute [MessageProps]

MessageAttribute = attrLevelMessage idMessageAttr Length Data Checksum

MessageProps = attrLevelMessage idMsgProps Length Data Checksum

; An attachment is determined/delimited by **attAttachRendData**, followed by
; other encoded attributes, if any, and ending with **attAttachment** if there are
; any encoded **properties**.

AttachData = AttachRendData [*AttachAttribute] [AttachProps]

AttachRendData = attrLevelAttachment idAttachRendData Length Data Checksum

AttachAttribute = attrLevelAttachment idAttachAttr Length Data Checksum

AttachProps = attrLevelAttachment idAttachment Length Data Checksum

```

; TNEF Version. TNEF Writers MUST use %x00.00.01.00
; TNEF Readers MUST reject other values
TNEFVersionData = 4*4OCTET

; This is the code page of attribute strings. MUST contain an 8-bit
; code page for compatibility with legacy applications that cannot handle
; "strings" with "embedded zero characters."
OEMCodePageData = PrimaryCodePage SecondaryCodePage
PrimaryCodePage=UINT32
; Secondary CodePage is unused. SHOULD contain zero.
SecondaryCodePage=%x00.00.00.00

TNEFHeader = TNEFSignature LegacyKey
TNEFSignature = %x78.9F.3E.22

; Any number will suffice here. This is now legacy.
LegacyKey = UINT16

; The length of the following data field in bytes. All attribute lengths are
; 32-bit integers, including any terminating null characters.

Length = INT32

; Data of the attribute itself, flattened out based on the particular attribute
; according to the rules that follow.

Data = 0*OCTET

; 16-bit unsigned integer that is the sum, modulo 65536, of the data bytes for
; the attribute value data, calculated over the entire length of the attribute data.
; In the case where the attribute contains enhanced properties with padding, the
; pad bytes MUST be included in the calculation.

Checksum = UINT16

; Level where attribute applies, either to the message itself or to
; an attachment.

attrLevelMessage = %x01
attrLevelAttachment = %x02

; Attribute ID Tags

; TNEF Version

```

idTnefVersion = %x06.90.08.00

; OEM Codepage. See **attOemCodepage** handling in section 5 and Appendix A.
idOemCodepage = %x07.90.06.00

; Message-level attributes. SHOULD all be at **attrLevelMessage**.
idMessageAttr = idMessageClass / idFrom / idSubject / idDateSent /
idDateRecd / idMessageStatus / idMessageID /
idConversationID / idBody / idPriority / idDateModified /
idRecipTable / idOriginalMessageClass / idOwner / idSentFor /
idDelegate / idDateStart / idDateEnd / idAidOwner / idRequestRes

; **PidTagMessageClass**
idMessageClass = %x08.80.07.00

; **PidTagSenderEntryId**
idFrom = %x00.80.00.00

; **PidTagSubject**
idSubject = %x04.80.01.00

; **PidTagClientSubmitTime**
idDateSent = %x05.80.03.00

; **PidTagMessageDeliveryTime**
idDateRecd = %x06.80.03.00

; **PidTagMessageFlags**
idMessageStatus = %x07.80.06.00

; **PidTagSearchKey**
idMessageID = %x09.80.01.00

; **PidTagConversationIndex**
idConversationID = %x0B.80.01.00

; **PidTagBody**
idBody = %x0C.80.02.00

; **PidTagImportance**
idPriority = %x0D.80.04.00

; **PidTagLastModificationTime** (message)
idDateModified = %x20.80.03.00

; Message Property Encapsulation
idMsgProps = %x03.90.06.00

; **PidTagMessageRecipients**. See **attRecipTable** handling
; in section 5.
idRecipTable = %x04.90.06.00

; **PidTagOriginalMessageClass**
idOriginalMessageClass = %x00.06.07.00

; **PidTagReceivedRepresentingEmailAddress** or **PidTagSentRepresentingEmailAddress**
idOwner = %x00.00.06.00

; **PidTagSentRepresentingEmailAddress**
idSentFor = %x01.00.06.00

; **PidTagReceivedRepresentingEmailAddress**
idDelegate = %x00.02.06.00

; **PidTagStartDate**
idDateStart = %x06.00.03.00

; **PidTagEndDate**
idDateEnd = %x07.00.03.00

; **PidTagOwnerAppointmentId**
idAidOwner = %x08.00.05.00

; **PidTagResponseRequested**
idRequestRes = %x09.00.04.00

; Attachment-level attributes. MUST all be at **attrLevelAttachment**.
idAttachAttr = idAttachData / idAttachTitle / idAttachMetaFile /
idAttachCreateDate / idAttachModifyDate / idAttachTransportFilename

; **PidTagAttachDataBinary** or **PidTagAttachDataObject**
idAttachData = %x0F.80.06.00

; **PidTagAttachFilename**
idAttachTitle = %x10.80.01.00

; **PidTagAttachRendering**
idAttachMetaFile = %x11.80.06.00

```

; PidTagCreationTime
idAttachCreateDate = %x12.80.03.00

; PidTagLastModificationTime (attachment)
idAttachModifyDate = %x13.80.03.00

; PidTagAttachTransportName
idAttachTransportFilename = %x01.90.06.00

; Attachment RendData
idAttachRendData = %x00.06.90.02

; Attachment table Row
idAttachment = %x05.90.06.00

```

2.3 Attributes

This section describes the attributes that appear in the **TNEF** stream, including the structure of the attributes, the message **properties** they map to, and any required conversions between them and message properties.

Each attribute is described by a level at which it applies (message or attachment), the attribute ID, the length of the attribute data, the attribute data, and a simple checksum. They are documented in the following sections in the form "**attXXXX**." For example, **attSubject** refers to the following:

*attrLevelMessage idSubject Length *VCHAR Checksum*

2.3.1 attTnefVersion

Originally meant to permit versioning of the structure, this attribute is now legacy. **TNEF Writers** MUST write it as %x00.00.01.00 and **TNEF Readers** MUST reject other content.

2.3.2 attOemCodepage

Contains the Windows Codepage used by the **TNEF Writer** for all attribute string values, and for any ANSI strings in the encapsulated message properties. See section 5.1 for information about **code page** handling.

2.3.3 attFrom

Level=Message. Maps to/from: **PidTagSender_XXX**

The data for this attribute encodes as follows:

TRP-structure = TRP-header sender-display-name sender-email

TRP-header = trpidOneOff structure-length sender-name-length sender-email-length

; Structure type

trpidOneOff = %x04.00

; The length of the entire structure. See the following description.

structure-length = UINT16

; Length of sender name string, including the terminating zero character.

sender-name-length = UINT16

; Length of sender e-mail string, including the terminating zero character.

sender-email-length = UINT16

sender-display-name = 1*OCTET %x00

sender-email = sender-email-type ":" sender-email-address %x00

sender-email-type = 1*CHAR

sender-email-address = 1*CHAR

The **structure-length** field is calculated as 8 (the size of TRP-header in OCTETs) plus the length of **sender-display-name** (including the terminating zero character), and the length of **sender-email** (including the terminating zero character).<1>

The **sender-name-length** field is the length of **sender-display-name** in OCTETs (including the terminating zero character).

The **sender-email-length** field is calculated as the length of **sender-email** (including the terminating zero character).

The **sender-email** string is composed of four parts, the address-type (for example, the literal sequence "SMTP" for Internet addresses), a literal colon (":"), the address itself, and a terminating zero character. For example, the string "SMTP:user2@example.com" %x00 is a legal **sender-email** value.

TNEF Writers can use the discrete **PidTagSender Name**, **AddressType**, and **Address** properties if present, or access their values using the **PidTagSenderEntryId** property; **TNEF Readers** MUST set the **PidTagSenderEntryId** property and SHOULD decode the **attOwner** attribute into the other **PidTagSender** properties. For details about the **EntryID** property structure, see [MS-OXCMSG].

2.3.4 Date Attributes

The data for these attributes encode into a Date Time Record structure, as follows:

DTR = wYear wMonth wDay wHour wMinute wSecond wDayOfWeek

wYear = UINT16
wMonth = UINT16
wDay = UINT16
wHour = UINT16
wMinute = UINT16
wSecond = UINT16
wDayOfWeek = UINT16

wYear contains the year (2008 would be %xD8.07); *wMonth* is 1 for January, and so on; *wDay* is 1 for the first day of the month; *wHour*, *wMinute*, and *wSecond* contain the time; *wDayOfWeek* is 1 for Monday.

Attribute (in TNEF)	Level	Message Property
attDateSent	Message	PidTagClientSubmitTime
attDateRecd	Message	PidTagMessageDeliveryTime
attAttachCreateDate	Attachment	PidTagCreationTime
attAttachModifyDate	Attachment	PidTagLastModificationTime
attDateModified	Message	PidTagLastModificationTime
attDateStart	Message	PidTagStartDate
attDateEnd	Message	PidTagEndDate

2.3.5 Message Class Attributes

The **message class** attribute value is stored as a zero-terminated string that usually will hold the name specified by the client.

- **TNEF Writers** can represent any message class whose value is shown in the Message Property Value column of Table 1, using the value in the Attribute Value column.
- **TNEF Readers** MUST do the appropriate reverse mapping: if **attMessageClass** contains a value that is shown in the Attribute Value column, the value that MUST be returned is that of the value in the Message Property Value column. If the **attMessageClass** value begins with the string "Microsoft Mail v3.0", the **TNEF**

- Reader** MUST ignore the prefix while checking for the specially mapped message class values.
- TNEF Readers SHOULD ignore the checksum value for message class attributes because some legacy TNEF Writers generated invalid checksum values.
 - Other values SHOULD be written and read in their original form.

Table 1: Attribute and Message Property Values

Attribute Value (in TNEF)	Message Property Value
IPM.Microsoft Mail.Note	IPM.Note
IPM.Microsoft Mail.Read Receipt	Report.IPM.Note.IPNRN
IPM.Microsoft Mail.Non-Delivery	Report.IPM.Note.NDR
IPM.Microsoft Schedule.MtgRespP	IPM.Schedule.Meeting.Resp.Pos
IPM.Microsoft Schedule.MtgRespN	IPM.Schedule.Meeting.Resp.Neg
IPM.Microsoft Schedule.MtgRespA	IPM.Schedule.Meeting.Resp.Tent
IPM.Microsoft Schedule.MtgReq	IPM.Schedule.Meeting.Request
IPM.Microsoft Schedule.MtgCncl	IPM.Schedule.Meeting.Canceled

Message class attributes in TNEF are as follows:

Attribute (in TNEF)	Level	Message Property
attMessageClass	Message	PidTagMessageClass
attOriginalMessageClass	Message	PidTagOriginalMessageClass

2.3.6 Conversation-Tracking Attributes

These are stored by clients using binary, and stored in the attribute in text format. For compatibility, when generating a TNEF structure, the **TNEF Writer** MUST translate the binary representation into a textual one by emitting the two CHAR hexadecimal equivalent per OCTET (i.e. %x01 becomes "01", %x2D becomes "2D", and so on). Likewise, when reading the attribute from TNEF, the **TNEF Reader** SHOULD attempt to decode the text format back into binary.

Attribute (in TNEF)	Level	Message Property
attMessageID	Message	PidTagSearchKey
attParentID	Message	PidTagParentKey
attConversationID	Message	PidTagConversationIndex

2.3.7 attSubject

Level=Message. Maps to/from: **PidTagSubject**.

The data for this attribute is stored as a string with a terminating zero character.

2.3.8 attMessageStatus

Level=Message. Maps to/from: **PidTagMessageFlags**.

The data for this attribute is stored as an unsigned 32-bit integer, with the appropriate bits set to indicate the message status. For compatibility, these MUST be mapped to/from the following values:

Status	Attribute Flag (in TNEF)	Bit Value	Message Property Flag	Bit Value
Read	fmsRead	0x20	MSGFLAG_READ	0x01
Unmodified	fmsModified	0x01	MSGFLAG_UNMODIFIED	0x02
Submitted	fmsSubmitted	0x04	MSGFLAG_SUBMIT	0x04
Unsent	fmsLocal	0x02	MSGFLAG_UNSENT	0x08
Has Attachments	fmsHasAttach	0x80	MSGFLAG_HASATTACH	0x10

The states of the bit values match except for the unmodified flag. The value of fmsModified equals the negative of MSGFLAG_UNMODIFIED.

2.3.9 attBody

Level=Message. Maps to/from: **PidTagBody**.

The data for this attribute is stored as a string with a terminating zero character.

2.3.10 attPriority

Level=Message. Maps to/from: **PidTagImportance**.

The data for this attribute is stored as an unsigned 16-bit integer. For compatibility, these MUST be mapped to/from the following values:

Priority	Value (in TNEF)	Message Property Value
Low	3	0
Normal	2	1
High	1	2

2.3.11 attAttachData

Level=Attachment. Maps to/from: **PidTagAttachDataBinary**.

The data for this attribute is stored as a binary stream.

TNEF Writers can use this attribute for the attachment data if **PidTagAttachMethod** of the original attachment contains the value 0x0001 (ATTACH_BY_VALUE). For other values, the data MUST be encoded in **attAttachment**.

TNEF Writers MAY choose to put alternate text (such as "This is an attached message") in **attAttachData** for other cases. **TNEF Readers** MAY take advantage of this text for lightweight message display, but SHOULD use the data from **attAttachment** when doing a full decode.

2.3.12 attAttachTitle

Level=Attachment. Maps to/from: **PidTagAttachFilename**.

The data for this attribute is stored as a string with a terminating zero character.

2.3.13 attAttachMetaFile

Level=Attachment. Maps to/from: **PidTagAttachRendering**.

The data for this attribute is stored as a binary stream. See [MS-WMF] for a description of the content.

2.3.14 attAttachTransportFilename

Level=Attachment. Maps to/from: **PidTagAttachTransportName**.

The data for this attribute is stored as a string with a terminating zero character.

2.3.15 attAttachRendData

This attachment-level attribute contains a structure that contains information that can be used for rendering the attachment in the body.

Each set of attachment attributes MUST begin with **attAttachRendData**, followed by any other attributes; attachment properties encoded in **attAttachment** SHOULD be last.

The structure is laid out as follows:

attAttachRendData = AttachType AttachPosition RenderWidth RenderHeight DataFlags

AttachType = AttachTypeNull / AttachTypeFile / AttachTypeOle / AttachTypePicture

AttachTypeFile=%x01.00

AttachTypeOle=%x02.00

AttachPosition= INT32

RenderWidth=INT16

RenderHeight=INT16

DataFlags = FileDataDefault / FileDataMacBinary

FileDataDefault=%*x00.00.00.00*
FileDataMacBinary=%*x01.00.00.00*

AttachType MUST BE set by the **TNEF Writer** to *AttachTypeFile* when **PidTagAttachMethod** for the attachment is **ATTACH_BY_VALUE** or **ATTACH_EMBEDDED_MSG**, and to *AttachTypeOle* when **PidTagAttachMethod** is **ATTACH_OLE**.

TNEF Readers SHOULD set **PidTagAttachTag** for the attachment to %*x2A.86.48.86.F7.14.03.0A.03.01.01* when *AttachTypeOle* is set.

AttachPosition maps to/from **PidTagRenderingPosition**.

RenderWidth and **RenderHeight** can be set by the TNEF Writer to the size of the system icons if the attachment is a simple file attachment, or {-1,-1}. The messaging client SHOULD use {-1,-1} as a signal to compute them if needed for inline display of the attachment.

FileDataMacBinary SHOULD be set by the TNEF Writer if **PidTagAttachEncoding** for the attachment consists of the following bytes: %*x2A.86.48.86.F7.14.03.0B.01*, and the TNEF Reader SHOULD set the value of the **PidTagAttachEncoding** property for the attachment to the same bytes if *DataFlags* contains *FileDataMacBinary*.

2.3.16 attOwner

Level=Message. Meeting attribute.

Maps to/from: **PidTagReceivedRepresenting_XXX** or **PidTagSentRepresenting_XXX**.

The **attOwner** attribute is encoded as counted strings laid end-to-end. The format for **attOwner** is as follows:

attOwner=display-name-length display-name address-length address

; Length of "display-name," including terminating zero character.

display-name-length=UINT16

display-name=*CHAR %*x00*

; Length of "address", including terminating zero character.

address-length=UINT16

address= 1*CHAR ":" 1*CHAR %*x00*

The display-name-length and address-length are unsigned 16-bit values, including the terminating zero characters for the strings. The type and address strings in the email-address entry are separated by a colon (:) character; for example, "SMTP:user1@example.com" %*x00*.

The mapping of message properties to the **attOwner** attribute is dependent on the **message class** of the message being encoded.

If the message is either a Meeting Request or Meeting Cancellation (from the organizer, who is creating or deleting a meeting), the **TNEF Writer** SHOULD encode the **PidTagSentRepresenting** properties in the **attOwner** attribute and the **TNEF Reader** SHOULD decode the **attOwner** attribute into the **PidTagSentRepresenting** properties.

If the message is a meeting response of any type (from attendee, accepting, declining, and so on), the **TNEF Writer** SHOULD encode the **PidTagReceivedRepresenting** properties in the **attOwner** attribute and the **TNEF Reader** SHOULD decode the **attOwner** attribute into the **PidTagReceivedRepresenting** properties. For details about how to construct the **EntryID property**, see [MS-OXCMSG].

TNEF Writers can use the discrete **PidTag{Sent | Rcvd}Representing Name, AddressType**, and **Address** properties if present, or access their values by using the **PidTag{Sent | Rcvd}EntryId** property; TNEF Readers MUST set the **PidTag{Sent | Rcvd} EntryId** property and SHOULD decode the **attOwner** attribute into the other **PidTag{Sent | Rcvd} Representing** properties.

2.3.17 attSentFor

Level=Message. Meeting attribute. Maps to/from: **PidTagSentRepresenting_XXX**.

The **TNEF Writer** SHOULD encode the **PidTagSentRepresenting** properties in the **attSentFor** attribute and the **TNEF Reader** SHOULD decode the **attSentFor** attribute into the **PidTagSentRepresenting** properties.

TNEF Writers can use the discrete **PidTagSentRepresenting Name, AddressType**, and **Address** properties if present, or access their values by using the **PidTagSentRepresentingEntryId** property; TNEF Readers SHOULD set the **PidTagSentRepresentingEntryId** property and SHOULD decode the **attOwner** attribute into the other **PidTagSentRepresenting** properties.

2.3.18 attDelegate

Level=Message. Meeting attribute. Maps to/from: **PidTagDelegation**.

The **TNEF Writer** SHOULD encode the **PidTagReceivedRepresenting** properties in the **attDelegate** attribute and the **TNEF Reader** SHOULD decode the **attDelegate** attribute into the **PidTagReceivedRepresenting** properties.

The content can be transported as a **binary large object (BLOB)**. See [MS-OXPROPS] for an explanation of the **PidTagDelegation** property.

2.3.19 attAidOwner

Level=Message. Meeting attribute. Maps to/from: **PidTagOwnerAppointmentId**.

The content can be transported as a **BLOB**. See [MS-OXOCAL] for an explanation of the **PidTagOwnerAppointmentId property**.

2.3.20 attRequestRes

Level=Message. Meeting attribute. Maps to/from: **PidTagResponseRequested**.

This is a Boolean; it SHOULD be transported as a 16-bit integer (the low order 16 bits of **PidTagResponseRequested**). See [MS-OXOCAL] for an explanation of the **PidTagResponseRequested property**.

2.3.21 attMsgProps

Level=Message. Maps to/from an arbitrary set of message properties.

TNEF Writers SHOULD write this attribute after all the other message attributes and immediately before all the attachment attributes. See section 2.4 for a description of the encoding for this attribute.

2.3.22 attRecipTable

Level=Message. Maps to/from: **PidTagMessageRecipients**

See section 2.4 for a description of the encoding for this attribute.

2.3.23 attAttachment

Level=Attachment. Maps to/from an arbitrary set of properties for a single attachment.

TNEF Writers SHOULD write this encapsulation after all the attributes for an attachment. See section 2.4 for a description of the encoding for this attribute.

2.4 Encapsulated Message Properties

The following attributes are special in that they are used to encode any message **property** that does not have a counterpart in the set of existing TNEF-defined attributes. The attribute data is a counted set of message properties laid end-to-end. The format of this encoding, which allows for any set of message properties, is as follows:

MsgPropertyList = 1*MsgPropertyCount *MsgPropertyValue
MsgPropertyCount = UINT32

MsgPropertyValue = MsgPropertyTag MsgPropertyContent
MsgPropertyTag = MsgPropertyType MsgPropertyId [NamedPropSpec]

; Only present when MsgPropertyId is >= 0x8000.
 NamedPropSpec = PropNameSpace PropIDType PropMap

; Contains a **GUID** to specify the namespace.
 PropNameSpace = GUID
 PropIDType = IDTypeNumber / IDTypeString
 PropMap = PropMapID / PropMapString

IDTypeNumber = %x00.00.00.00
 IDTypeString = %x01.00.00.00

; Used if **PropIDType** is **IDTypeNumber**. Contains a number
 ; that is used to identify the **property** within the namespace.
 PropMapID = UINT32

; Used if **PropIDType** is **IDTypeString**. Contains a length, then a
 ; **UTF-16LE** encoded **UNICODE** string.
 ; The length includes the terminating 2-byte zero character. Optional padding
 ; to UINT32 boundary.
 PropMapString = UINT32 *UINT16 %00.00 [PropMapPad]

; Padding for a UTF-16LE encoded UNICODE string to UINT32 size.
 ; Should be either 0 or 2 bytes.
 PropMapPad=*1UINT16

Msg.PropertyType = TypeUnspecified / TypeNull / TypeInt16 / TypeInt32 /
 TypeFlt32 / TypeFlt64 / TypeCurrency / TypeAppTime / TypeError /
 TypeBoolean / TypeObject / TypeInt64 / TypeString8 / TypeUnicode /
 TypeSystime / TypeCLSID / TypeBinary / TypeMVInt16 / TypeMVInt32 /
 TypeMVFlt32 / TypeMVFlt64 / TypeMVCurrency / TypeMVAppTime /
 TypeMVSystime / TypeMVString8 / TypeMVBinary / TypeMVUnicode /
 TypeMVCLSID / TypeMVInt64

Msg.PropertyID = UINT16

; This is used on a calling interface, MUST NOT be on a stored property.
 TypeUnspecified = %x00.00

; This is returned from a calling interface, MUST NOT be on a stored property.
 TypeNull = %x01.00

; Signed 16-bit value = INT16.
 TypeInt16 = %x02.00
 TypeMVInt16 = %x02.10

```

; Signed 32-bit value = INT32.
TypeInt32 = %x03.00
TypeMVInt32 = %x03.10

; Signed 32-bit floating point= FLOAT.
TypeFlt32 = %x04.00
TypeMVFlt32 = %x04.10

; 64-bit floating point= DOUBLE.
TypeFlt64 = %x05.00
TypeMVFlt64 = %x05.10

; Signed 64-bit int = OLE CURRENCY type.
TypeCurrency = %x06.00
TypeMVCurrency = %x06.10

; Application time= OLE DATE type.
TypeAppTime = %x07.00
TypeMVAppTime = %x07.10

; This is returned from a calling interface, MUST NOT be on a stored property.
TypeError = %x0A.00

; 16-bit Boolean (non-zero = TRUE)
TypeBoolean = %x0B.00

; Embedded object on a property.
TypeObject = %x0D.00

; 8-byte signed integer= INT64.
TypeInt64 = %x14.00
TypeMVInt64 = %x14.10

; 8-bit character string with terminating zero character.
; See section 5.1 for more
; information about encoding and decoding 8-bit strings in TNEF.
TypeString8 = %x1F.00
TypeMVString8 = %x1F.10

; UTF-16LE or variant character string with terminating 2-byte zero character.
TypeUnicode = %x1F.00
TypeMVUnicode = %x1F.10

```

```

; FILETIME
TypeSystime = %x40.00
TypeMVSystime = %x40.10

; OLE GUID
TypeCLSID = %x48.00
TypeMVCLSID = %x48.10

; Uninterpreted BLOB.
TypeBinary = %x02.01
TypeMVBinary = %x02.11

; MsgPropertyContent varies by property type.
MsgPropertyContent = PropertyScalarContent / PropertyMultiScalarContent /
                    PropertyMultiVariableContent

; Scalars – Types Int16, Int32, Flt32, Flt64, Currency, AppTime,
;           Bool, Int64, Systime, CLSID
; The data for the particular property is written to the stream and if necessary,
; padded with bytes (which SHOULD be zero) to achieve a multiple of 4-bytes in length.

PropertyScalarContent = MsgPropertyContent [PropertyPad]

; PropertyPad – between 0 and 3 zero-filled bytes, added to the streamed
; property values to achieve 4-byte boundary. Writers MUST use zero bytes
; and Readers MUST permit non-zero bytes. These pad bytes MUST be counted
; in the checksum of the containing attribute.

PropertyPad=*3ZERO
ZERO= %x00

; Multi-value Scalars – Types MVInt16, MVInt32, MVFlt32, MVFlt64, MVCurrency,
;           MVAppTime, MVBool, MVInt64, MVSystime, MVCLSID
; The number of values for the property is written to the stream as a 4-byte
; value, then the data for each value is written to the stream and if need
; be, padded with bytes (which SHOULD be zero) to achieve a multiple of 4 bytes in length.

PropertyMultiScalarContent = PropertyContentCount *PropertyScalarContent
PropertyContentCount = UINT32

; Variable-length – Types Unicode, String8, Object, Binary.
; These are handled as a special case of Multi-Variable-Length with the number of values=1.

; Multi-Variable-length – Types MVUnicode, MVString8, MVBinary

```

; The number of values for the property is written to the stream as a 4-byte value,
; then for each value, the size of the property is written to the stream as a 4-byte
; value, then the data for the property is written to the stream and if necessary,
; padded with zero bytes to achieve a multiple of 4-bytes in length. No padding is necessary
; because each value was itself padded to a 4-byte boundary.

PropertyMultiVariableContent = MsgPropertyCount 1*PropertyVariableContent
MsgPropertyCount = UINT32

; The size of the property is written to the stream as a 4-byte value, then the data
; for the property is written to the stream and if necessary, padded with zero bytes
; to achieve a multiple of 4 bytes in length. The size includes the interface
; identifier at the beginning of the value stream for an object but does not include
; the padding bytes.
;
; If the property is of type **PT_OBJECT**, the value-size is followed by the interface
; identifier of the object, then the serialized stream of the data of the object. Only the
; **interface identifiers** of the **OLE IStorage**, the **OLE IStream**, and the
; Outlook/Exchange **IMessage** objects are supported. The size of the interface
; identifier is included in the calculation of value-size.
;
; If the object is an attached message (that is, it has a **property** type of **PT_OBJECT**
; and an interface identifier %x07.03.02.00.00.00.00.C0.00.00.00.00.00.00.46,
; that of a **Message object**), the value data is encoded as an
; embedded TNEF stream.

PropertyVariableContent = MsgPropertySize MsgPropertyContent [PropertyPad]
MsgPropertySize = UINT32

; Attributes containing encapsulated properties:

; **attMsgProps** - Maps to/from an arbitrary set of message properties.
MsgPropsData = MsgPropertyList

; **attRecipTable** - Maps to/from **PidTagMessageRecipients**.
; Number of table rows followed by the rows.
RecipTableData = NumRows *RecipRow

NumRows = UINT32
RecipRow = MsgPropertyList

; **attAttachment** – Maps to/from an arbitrary set of properties for a single attachment.
AttachPropsData = MsgPropertyList

3 Structure Examples

3.1 Sample Message

This message was sent within a Microsoft Exchange organization.

Explanation of content	Byte stream
Tnef Signature , Value=0x223E9F78	78 9f 3e 22
Attach Key , Value=0x0001	01 00
Message attribute, attTnefVersion Length=4 bytes	01 06 90 08 00 04 00 00 00
Data=0x00000001	00 00 01 00
Checksum=0x0001	01 00
Message attribute, attOemCodepage Length=8 bytes	01 07 90 06 00 08 00 00 00
Data= (Primary=1252, Secondary=0)	e4 04 00 00 00 00 00 00
Checksum=0x00E8	e8 00
Message attribute, attMessageClass Length=24 bytes	01 08 80 07 00 18 00 00 00
Data= "IPM.Microsoft Mail.Note" %x00	49 50 4d 2e 4d 69 63 72 6f 73 6f 66 74 20 4d 61 69 6c 2e 4e 6f 74 65 00
Checksum=0x0831	31 08
Message attribute, attPriority Length=2 bytes	01 0d 80 04 00 02 00 00 00
Data=0x0002 (Normal Priority)	02 00
Checksum=0x0002	02 00
Message attribute, attSubject Length=15 bytes	01 04 80 01 00 0f 00 00 00
Data= "Simple subject" %x00	53 69 6d 70 6c 65 20 73 75 62 6a 65 63 74 00
Checksum=0x0831	31 08
Message attribute, attDateSent Length=14 bytes	01 05 80 03 00 0e 00 00 00
Data= Tuesday, 02/17/2004, 11:25:35	d4 07 02 00 11 00 0b 00 19 00 23 00 02 00
Checksum=0x0137	37 01
Message attribute, attDateModified Length=14 bytes	01 20 80 03 00 0e 00 00 00
Data= Tuesday, 02/17/2004, 12:26:09	D4 07 02 00 11 00 0C 00 -- 1A 00 09 00 02 00
Checksum=0x011F	1F 01
Message attribute, attMessageID Length=33 bytes	01 09 80 01 00 21 00 00 00
Data= "757BB19CDE936A4087D90BB784C58E3B"	37 35 37 42 42 31 39 43 44 45 39 33 36 41 34 30 38 37 44 39 30 42 42 37 38 34 43 35 38 45 33 42 00
Checksum=0x0751	51 07
Message attribute, Encapsulation, attMsgProps Length=2256 bytes Number of properties=69	01 03 90 06 00 d0 08 00 00 45 00 00 00
Message property, PidTagAlternateRecipientAllowed Value=1 (TRUE)	0b 00 02 00 01 00 00 00
Message property, PidTagPriority Value=0 (LOW)	03 00 26 00 00 00 00 00
Message property, PidTagSensitivity Value=0 (LOW)	03 00 36 00 00 00 00 00
Message property, PidTagClientSubmitTime Value=Tuesday, 02/17/2004, 19:25:35	40 00 39 00 AA D6 F3 D0 8B F5 C3 01
Message property, PidTagSubjectPrefix Number of property values=1 Size of first property=1	1e 00 3d 00 01 00 00 00 01 00 00 00
Value = %x00	00
Pad=3 bytes	00 00 00

Explanation of content	Byte stream
Message property, PidTagReceivedByEntryId Number of property values=1 Size of first property=107	02 01 3f 00 01 00 00 00 6b 00 00 00
	00 00 00 00 DC A7 40 C8 C0 42 10 1A B4 B9 08 00 2B 2F E1 82 01 00 00 00 00 00 00 00 00 2F 4F 3D 46 49 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 49 45 4E 54 53 2F 43 4E 3D 54 45 53 54 32 31 55 57 32 00
Pad=1 byte	00
Message property, PidTagReceivedByName Number of property values=1 Size of first property=10	1e 00 40 00 01 00 00 00 0a 00 00 00
Value="Test21uw2" %x00	54 65 73 74 32 31 75 77 32 00
Pad=2 bytes	00 00
Message property, PidTagReceivedRepresentingEntryId Number of property values=1 Size of first property=107	02 01 43 00 01 00 00 00 6b 00 00 00
	00 00 00 00 DC A7 40 C8 C0 42 10 1A B4 B9 08 00 2B 2F E1 82 01 00 00 00 00 00 00 00 00 2F 4F 3D 46 49 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 49 45 4E 54 53 2F 43 4E 3D 54 45 53 54 32 31 55 57 32 00
Pad=1 byte	00
Message property, PidTagReceivedRepresentingName Number of property values=1 Size of first property=10	1e 00 44 00 01 00 00 00 0a 00 00 00
Value="Test21uw2" %x00	54 65 73 74 32 31 75 77 32 00
Pad=2 bytes	00 00
Message property, PidTagMessageSubmissionId Number of property values=1 Size of first property=57	02 01 47 00 01 00 00 00 39 00 00 00
	63 3D 55 53 3B 61 3D 20 3B 70 3D 46 69 72 73 74 20 4F 72 67 61 6E 69 7A 61 74 69 3B 6C 3D 4A 45 53 45 4F 47 50 55 57 32 2D 30 34 30 32 31 37 31 39 32 35 33 35 5A 2D 32 00
Pad=3 bytes	00 00 00
Message property, PidTagReceivedBySearchKey Number of property values=1 Size of first property=82	02 01 51 00 01 00 00 00 52 00 00 00
	45 58 3A 2F 4F 3D 46 49 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 49 45 4E 54 53 2F 43 4E 3D 54 45 53 54 32 31 55 57 32 00
Pad=2 bytes	00 00
Message property, PidTagReceivedRepresentingSearchKey Number of property values=1 Size of first property=82	02 01 52 00 01 00 00 00 52 00 00 00
	45 58 3A 2F 4F 3D 46 49 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 49 45 4E 54 53 2F 43 4E 3D 54 45 53 54 32 31 55 57 32 00
Pad=2 bytes	00 00

Explanation of content	Byte stream
Message property, PidTagMessageToMe Value=1 (TRUE)	00 0b 00 57 00 01 00 00
Message property, PidTagMessageCcMe Value=0 (FALSE)	00 0b 00 58 00 00 00 00
Message property, PidTagMessageRecipientMe Value=1 (TRUE)	00 0b 00 59 00 01 00 00
Message property, PidTagConversationTopic Number of property values=1 Size of first property=15 Value="Simple subject" %x00 Pad=1 byte	1e 00 70 00 01 00 00 00 0f 00 00 00 53 69 6D 70 6C 65 20 73 75 62 6A 65 63 74 00 00
Message property, PidTagConversationIndex Number of property values=1 Size of first property=22 Pad=2 bytes	02 01 71 00 01 00 00 00 16 00 00 00 01 C3 F5 8B 07 63 76 8D 89 1B D0 79 47 C9 8F 66 4E 21 9A D2 4A F2 00 00
Message property, PidTagReceivedByAddressType Number of property values=1 Size of first property=5 Value="SMTP" %x00 Pad=3 bytes	1e 00 75 00 01 00 00 00 05 00 00 00 53 4d 54 50 00 00 00 00
Message property, PidTagReceivedByEmailAddress Number of property values=1 Size of first property=40 Value="Test21uw2@mydomuw2.extest.microsoft.com" %x00	1e 00 76 00 01 00 00 00 28 00 00 00 54 65 73 74 32 31 75 77 32 40 6D 79 64 6F 6D 75 77 32 2E 65 78 74 65 73 74 2E 6D 69 63 72 6F 73 6F 66 74 2E 63 6F 6D 00
Message property, PidTagReceivedRepresentingAddressType Number of property values=1 Size of first property=5 Value="SMTP" %x00 Pad=3 bytes	1e 00 77 00 01 00 00 00 05 00 00 00 53 4d 54 50 00 00 00 00
Message property, PidTagReceivedRepresentingEmailAddress Number of property values=1 Size of first property=40 Value="Test21uw2@mydomuw2.extest.microsoft.com" %x00	1e 00 78 00 01 00 00 00 28 00 00 00 54 65 73 74 32 31 75 77 32 40 6D 79 64 6F 6D 75 77 32 2E 65 78 74 65 73 74 2E 6D 69 63 72 6F 73 6F 66 74 2E 63 6F 6D 00
Message property, PidTagSenderName Number of property values=1 Size of first property=10 Value="Test21uw2" %x00 Pad=2 bytes	1e 00 1A 0C 01 00 00 00 0a 00 00 00 54 65 73 74 32 31 75 77 32 00 00 00
Message property, PidTagNormalizedSubject Number of property values=1 Size of first property=15 Value="Simple subject" %x00 Pad=1 byte	1e 00 1D 0E 01 00 00 00 0f 00 00 00 53 69 6D 70 6C 65 20 73 75 62 6A 65 63 74 00 00
Message property, PidTagRtfCompressed Number of property values=1 Size of first property=150	02 01 09 10 01 00 00 00 96 00 00 00

Explanation of content	Byte stream
	92 00 00 00 AB 00 00 00 4C 5A 46 75 A8 14 2F 17 03 00 0A 00 72 63 70 67 31 32 35 16 32 00 F8 0B 60 6E 0E 10 30 33 33 4F 01 F7 02 A4 03 E3 02 00 63 68 0A C0 73 B0 65 74 30 20 07 13 02 80 7D 0A 80 9D 00 00 2A 09 B0 09 F0 04 90 61 74 05 B1 1A 52 0D E0 68 09 80 01 D0 20 35 2E 30 35 30 2E 33 13 B0 01 D0 30 32 49 02 80 5C 76 08 90 77 6B 0B 80 64 FA 34 0C 60 63 00 50 0B 03 0B B5 06 00 07 70 C9 0B 50 65 20 07 81 73 61 12 50 0A A2 0B 0A 80 11 E1 00 17 A0
Pad=2 bytes	00 00
Message property, PidTagInternetMessageId Number of property values=1 Size of first property=80 Value=<2896107D7E52DF4DB5D10536D BFEFAD07E37@jeseogpuw2.mydomuw2. extest.microsoft.com>%x00	1e 00 35 10 01 00 00 00 50 00 00 00 3C 32 38 39 36 31 30 37 44 37 45 35 32 44 46 34 44 42 35 44 31 30 35 33 36 44 42 46 45 46 41 44 30 37 45 33 37 40 6A 65 73 65 6F 67 70 75 77 32 2E 6D 79 64 6F 6D 75 77 32 2E 65 78 74 65 73 74 2E 6D 69 63 72 6F 73 6F 66 74 2E 63 6F 6D 3E 00
Message property, PidTagIconIndex Value=0xFFFF	03 00 80 10 ff ff ff ff
Message property, PidTagImapCachedMsgsize Number of property values=1 Size of first property=40	02 01 f0 10 01 00 00 00 28 00 00 00 03 00 00 00 01 00 00 00 01 00 00 00 01 00 00 00 01 00 00 08 00 00 00 00 DB 11 00 00 49 53 4F 2D 38 38 35 39 2D 31 00 00
Message property, PidTagUrlCompName Number of property values=1 Size of first property=38 Value="Simple subject.EML" %x00.00 (UNICODE)	1f 00 f3 10 01 00 00 00 26 00 00 00 53 00 69 00 6D 00 70 00 6C 00 65 00 20 00 73 00 75 00 62 00 6A 00 65 00 63 00 74 00 2E 00 45 00 4D 00 4C 00 00 00
Pad=2 bytes	00 00
Message property, PidTagAttributeHidden Value=0 (FALSE)	0b 00 f4 10 00 00 00 00
Message property, PidTagAttributeSystem Value=0 (FALSE)	0b 00 f5 10 00 00 00 00
Message property, PidTagAttributeReadOnly Value=0 (FALSE)	0b 00 f6 10 00 00 00 00
Message property, PidTagCreationTime Value=Tuesday, 02/17/2004, 20:26:09	40 00 07 30 90 24 46 47 94 f5 c3 01
Message property, PidTagLastModificationTime Value=Tuesday, 02/17/2004, 20:26:09	40 00 08 30 90 24 46 47 94 f5 c3 01
Message property, PidTagInternetCodepage Value=(Primary=1252, Secondary=0)	03 00 de 3f e4 04 00 00
Message property, PidTagMessageLocaleId Value=(Primary=1033, Secondary=0)	03 00 f1 3f 09 04 00 00
Message property, PidTagCreatorName Number of property values=1 Size of first property=10 Value="TEST2IUW2" %x00	1e 00 f8 3f 01 00 00 00 0a 00 00 00 54 65 73 74 32 31 75 77 32 00
Pad=2 bytes	00 00
Message property, PidTagCreatorEntryId Number of property values=1 Size of first property=107	02 01 F9 3F 01 00 00 00 6b 00 00 00 00 00 00 00 DC A7 40 C8 C0 42 10 1A B4 B9 08 00 2B 2F E1 82 01 00 00 00 00 00 00 00 00 2F 4F 3D 46 49 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 49 45 4E 54 53 2F 43 4E 3D 54 45 53 54 32 31 55 57 32 00
Pad=1 byte	00

Explanation of content	Byte stream
Message property, PidTagLastModifierName Number of property values=1 Size of first property=10 Value="TEST21UW2" %x00 Pad=2 bytes	1e 00 fa 3f 01 00 00 00 0a 00 00 00 54 65 73 74 32 31 75 77 32 00 00 00
Message property, PidTagLastModifierEntryId Number of property values=1 Size of first property=107	02 01 FB 3F 01 00 00 00 6b 00 00 00 00 00 00 00 DC A7 40 C8 C0 42 10 1A B4 B9 08 00 2B 2F E1 82 01 00 00 00 00 00 00 00 2F 4F 3D 46 49 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 49 45 4E 54 53 2F 43 4E 3D 54 45 53 54 32 31 55 57 32 00
Pad=1 byte	00
Message property, PidTagMessageCodepage Value=(Primary=1252, Secondary=0)	03 00 fd 3f e4 04 00 00
Message property, PidTagSenderFlags Value=0	03 00 19 40 00 00 00 00
Message property, PidTagSentRepresentingFlags Value=0	03 00 1A 40 00 00 00 00
Message property, PidTagReceivedByFlags Value=0	03 00 1B 40 00 00 00 00
Message property, PidTagReceivedRepresentingFlags Value=0	03 00 1C 40 00 00 00 00
Message property, PidTagSenderSimpleDisplayName Number of property values=1 Size of first property=10 Value="TEST21UW2" %x00 Pad=2 bytes	1e 00 30 40 01 00 00 00 0a 00 00 00 54 65 73 74 32 31 75 77 32 00 00 00
Message property, PidTagSentRepresentingSimpleDisplayName Number of property values=1 Size of first property=10 Value="TEST21UW2" %x00 Pad=2 bytes	1e 00 31 40 01 00 00 00 0a 00 00 00 54 65 73 74 32 31 75 77 32 00 00 00
Message property, PidTagReceivedRepresentingSimpleName Number of property values=1 Size of first property=10 Value="TEST21UW2" %x00 Pad=2 bytes	1e 00 34 40 01 00 00 00 0a 00 00 00 54 65 73 74 32 31 75 77 32 00 00 00
Message property, PidTagReceivedRepresentingSimpleDisplayName Number of property values=1 Size of first property=10 Value="TEST21UW2" %x00 Pad=2 bytes	1e 00 35 40 01 00 00 00 0a 00 00 00 54 65 73 74 32 31 75 77 32 00 00 00
Message property, PidTagCreatorSimpleDisplayName Number of property values=1 Size of first property=10 Value="TEST21UW2" %x00 Pad=2 bytes	1e 00 38 40 01 00 00 00 0a 00 00 00 54 65 73 74 32 31 75 77 32 00 00 00
Message property, PidTagLastModifierSimpleDisplayName Number of property values=1 Size of first property=10	1e 00 39 40 01 00 00 00 0a 00 00 00 54 65 73 74 32 31 75 77 32 00

Explanation of content	Byte stream
Value="TEST21UW2" %x00	54 65 73 74 32 31 75 77 32 00
Pad=2 bytes	00 00
Message property, PidTagContentFilterSpamConfidenceLevel Value=0xFFFFFFFF	03 00 76 40 ff ff ff ff
Message property, PidTagMessageEditorFormat Value=0x00000003	03 00 09 59 03 00 00 00
Message property, PidTagTnefCorrelationKey Number of property values=1 Size of first property=12	02 01 7f 00 01 00 00 00 0c 00 00 00
	38 71 6b 6a 30 30 73 67 6d 34 66 00
Message Property, PidLidAgingDontAgeMe PSETID_Common, MNID_ID, Id=0x850E Value=0	0b 00 87 81 08 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 00 00 00 00 0e 85 00 00 00 00 00 00
Message Property, PidLidCurrentVersion PSETID_Common, MNID_ID, Id=0x8552 Value=115608	03 00 9f 81 08 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 00 00 00 00 52 85 00 00 98 c3 01 00
Message Property, PidLidCurrentVersionName PSETID_Common, MNID_ID, Id=0x8554 Number of property values=1 Size of first property=5 Value="11.0" %x00	1e 00 a0 81 08 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 00 00 00 00 54 85 00 00 01 00 00 00 05 00 00 00
Pad=3 bytes	31 31 2e 30 00 00 00 00
Message Property, PidLidReminderDelta PSETID_Common, MNID_ID, Id=0x8501 Value=0	03 00 eb 81 08 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 00 00 00 00 01 85 00 00 00 00 00 00
Message Property, PidLidReminderSet PSETID_Common, MNID_ID, Id=0x8503 Value=0 (FALSE)	0b 00 f0 81 08 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 00 00 00 00 03 85 00 00 00 00 00 00
Message Property, PidLidSideEffects PSETID_Common, MNID_ID, Id=0x8510 Value=0	03 00 fa 81 08 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 00 00 00 00 10 85 00 00 00 00 00 00
Message Property, PidLidTaskMode PSETID_Common, MNID_ID, Id=0x8518 Value=0	03 00 01 82 08 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 00 00 00 00 18 85 00 00 00 00 00 00
Message Property, PidLidPrivate PSETID_Common, MNID_ID, Id=0x8506 Value=0 (FALSE)	0b 00 43 82 08 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 00 00 00 00 06 85 00 00 00 00 00 00
Message Property, PidLidUseTnef PSETID_Common, MNID_ID, Id=0x8582 Value=0 (FALSE)	0b 00 44 82 08 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 46 00 00 00 00 82 85 00 00 00 00 00 00
Message property, PidTagReadReceiptRequested Value=0 (FALSE)	0b 00 29 00 00 00 00 00

Explanation of content	Byte stream
Message property, PidTagOriginatorDeliveryReportRequested Value=0 (FALSE)	0b 00 23 00 00 00 00 00
Message property, PidTagRtfSyncBodyCrc Value=0xF00D29FF	03 00 06 10 ff 29 0d f0
Message property, PidTagRtfSyncBodyCount Value=13	03 00 07 10 0d 00 00 00
Message property, PidTagRtfSyncPrefixCount Value=0	03 00 10 10 00 00 00 00
Message property, PidTagRtfSyncTrailingCount Value=0	03 00 11 10 00 00 00 00
Message property, PidTagRtfSyncBodyTag Number of property values=1 Size of first property=14 Value="SIMPLEMESSAGE" %x00 Pad=2 bytes	1e 00 08 10 01 00 00 00 0e 00 00 00 53 49 4d 50 4c 45 4d 45 53 53 41 47 45 00 00 00
Message property, PidTagTnefCorrelationKey Number of property values=1 Size of first property=56	02 01 7f 00 01 00 00 00 38 00 00 00 3C 32 38 39 36 31 30 37 44 37 45 35 32 44 46 34 44 42 35 44 31 30 35 33 36 44 42 46 45 46 41 44 30 37 45 33 37 40 75 73 65 72 2E 65 78 61 6D 70 6C 65 2E 63 6F 6D 3E 00
Checksum for AttMsgProps	45 C1

3.2 Sample Meeting Response

This example is particularly short, as it was sent by a mobile application.

Explanation of content	Byte stream
Tnef Signature , Value=0x223E9F78	78 9f 3e 22
Attach Key , Value=0x0001	01 00
Message attribute, attTnefVersion Length=4 bytes	01 06 90 08 00 04 00 00 00
Data=0x00000001	00 00 01 00
Checksum=0x0001	01 00
Message attribute, attOemCodepage Length=8 bytes	01 07 90 06 00 08 00 00 00
Data= (Primary=1252, Secondary=0)	e4 04 00 00 00 00 00 00
Checksum=0x00E8	e8 00
Message attribute, attMessageClass Length=32 bytes	01 08 80 07 00 20 00 00 00
Data=“IPM.Microsoft Schedule.MtgRespN” %x00	49 50 4d 2e 4d 69 63 72 6f 73 6f 66 74 20 53 63 68 65 64 75 6c 65 2e 4d 74 67 52 65 73 70 4e 00
Checksum=0xB55	55 0b
Message attribute, attPriority Length=2 bytes	01 0d 80 04 00 02 00 00 00
Data=0x0002 (Normal Priority)	02 00
Checksum=0x0002	02 00
Message attribute, attDateSent Length=14 bytes	01 05 80 03 00 0e 00 00 00
Data= Wednesday, 01/16/2008, 23:28:08	d8 07 01 00 10 00 17 00 1c 00 08 00 03 00
Checksum=0x012E	2e 01
Message attribute, attDateModified Length=14 bytes	01 20 80 03 00 0e 00 00 00
Data= Wednesday, 01/16/2008, 23:28:08	d8 07 01 00 10 00 17 00 1c 00 08 00 03 00
Checksum=0x012E	2e 01
Message attribute, Encapsulation, attMsgProps Length=136 bytes Number of properties=2	01 03 90 06 00 88 00 00 00 02 00 00 00

Explanation of content	Byte stream
Message property, PidTagTnefCorrelationKey Number of property values=1 Size of first property=12	02 01 7f 00 01 00 00 00 0c 00 00 00
	38 71 6b 6a 30 30 73 67 6d 34 66 00
Message property, PidTagRtfCompressed Number of property values=1 Size of first property=93	02 01 09 10 01 00 00 00 5d 00 00 00
	59 00 00 00 b3 00 00 00 4c 5a 46 75 a9 be bb ed 87 00 0a 01 0d 03 43 74 65 78 74 01 f7 ff 02 a4 03 e4 05 eb 02 83 00 50 02 f3 06 b4 02 83 26 32 03 c5 02 00 63 68 0a c0 73 65 d8 74 30 20 07 13 02 80 7d 0a 80 08 cf 3f 09 d9 02 80 0a 84 0b 37 12 c2 01 d0 20 46 10 59 49 00 7d 18 20
Pad=3 bytes	00 00 00
Checksum for attMsgProps	f7 21

4 Security Considerations

4.1 *attRecipTable, attFrom*

Extreme care is recommended in the use of these attributes, particularly by the **TNEF Reader**, to avoid address or identity spoofing. More information about this can be found in [MS-OXCMSG] and section 5.2 of this specification.

5 Other Compatibility Issues

The preceding sections addressed issues of compatibility between the original implementation of TNEF and the richer implementation that is now used. This section discusses some compatibility issues within the richer implementation.

5.1 *attOemCodepage Handling*

Attribute **attOemCodepage** has been handled inconsistently between multiple implementations of TNEF. This can be particularly troublesome when forwarding messages with attached messages between systems that have different default **code pages**. To minimize problems caused by this inconsistent behavior, the following sections describe the recommended way to handle string encoding<2>.

5.1.1 Encoding by TNEF Writer

The **TNEF Writer** writes all ANSI strings, both the attribute strings and the encapsulated message **property** strings, with a consistent Windows ANSI **code page** and put its value into **attOemCodepage**. Choose a code page that does not allow embedded zero bytes other than the zero terminator.

If **PidTagInternetCodepage** is being stored in the encapsulated properties, set it to a value that maps to the same language group or language as the code page chosen for

attOemCodepage. This code page also determines the **character set** used in **MIME** if this **TNEF** is transmitted as a **MIME** entity body.

Do not write to an attribute any string that would suffer data loss if written using the consistent code page. Write to encapsulated properties with a **Unicode** data type all strings that would suffer data loss when using the consistent code page.

For compatibility purposes, **attMessageClass** always writes using the consistent code page.

5.1.2 Decoding by TNEF Reader

For ANSI string decoding from the **TNEF** structure, the **TNEF Reader** uses the Windows **code page** determined from the best of the following sources, listed in decreasing order of trustworthiness:

1. Any non-US-ASCII **MIME character set**, if the structure was transmitted as a **MIME body part** and character set name is available in the **MIME**, mapped to the most appropriate Windows code page that does not allow embedded zero bytes other than a zero terminator.
2. **attOemCodepage**, if available and nonzero.
3. **PidTagInternetCodepage**, if available in the encapsulated properties, mapped to the most appropriate Windows code page that does not allow embedded zero bytes other than a zero terminator.
4. The most appropriate default code page for the processing environment.

5.2 TNEF Encapsulation vs. Outer Wrapper Attributes

It is possible to encapsulate properties in the **TNEF** structure that represents data that is already conveyed as part of an outer wrapper such as **MIME**. Because in many cases the outer wrapper properties are subject to substantial validation during transport (reverse DNS lookups and other validation), they are considered more trustworthy than information inside an attached file that otherwise could overwrite good information with bad.

As a general rule, **TNEF Writers** do not duplicate any data that is already being reliably transported outside the structure and **TNEF Readers** do not override data from outside the structure with data from inside the structure. The individual implementations will determine how this rule is applied. For more details, see [MS-OXCMAIL]. Some highlights of this behavior are described in the following sections.

5.2.1 attBody Handling

When **TNEF** is being sent as a **MIME body part**, the **attBody** attribute is not written to **TNEF** or read from **TNEF** either by the client or server. The **plain text** body is instead transmitted in a **MIME** body part. When **TNEF** is being used to encode an attached message, **attBody** can be written and read. See [MS-OXCMAIL] for a more detailed description.

5.2.2 attRecipTable Handling

When TNEF is being sent as a **MIME body part**, the **attRecipTable** attribute is not written to TNEF or read from TNEF either by the client or server, except when sending or receiving a legacy [non]delivery report message (**attMessageClass** beginning with "REPORT." and ending in ".DR" or ".NDR"). The requisite message **recipient** information is transmitted in the MIME structure instead.

When TNEF is being sent as a MIME body part, when sending or receiving a legacy [non]delivery report message (**attMessageClass** beginning with "REPORT." and ending in ".DR" or ".NDR"), recipient information from **attRecipTable** is used to populate the received message recipient table.

When TNEF is being used to encode an attached message, recipient information from **attRecipTable** is used to populate the received message recipient table.

5.2.3 attFrom Handling

The **attFrom** attribute is not written to TNEF or read from TNEF either by the client or the server for **MIME** messages. The requisite message **recipient** information is transmitted in the MIME structure instead. When TNEF is being used to encode an attached message, the sender information is carried in encapsulated message properties in **attMsgProps**.

5.2.4 attSubject Handling

The **attSubject** attribute is not written to TNEF by the client or server for **MIME** messages, as the requisite subject information is transmitted in the MIME structure. When TNEF is being used to encode an attached message, the message subject information is carried in encapsulated message properties in **attMsgProps**. When the TNEF structure is being decoded, and **attSubject** is present, it will be used for the message if there is no MIME structure, if a MIME subject is not available, or if an attached message is being decoded.

6 Appendix A: Office/Exchange Behavior

The information in this specification is applicable to the following versions of Office/Exchange:

- Microsoft Office Outlook 2003
- Microsoft Exchange Server 2003
- Microsoft Office Outlook 2007
- Microsoft Exchange Server 2007
- Microsoft Outlook 2010
- Microsoft Exchange Server 2010

Exceptions, if any, are noted below. Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies Office/Exchange behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies Office/Exchange does not follow the prescription.

As of this writing, Exchange 2003, Exchange 2007, and Exchange 2010 recognize any one of the values listed in the following table.

Code	Description	Code	Description
874	Thai	1253	Greek
932	Japanese Shift-JIS	1254	Turkish
936	Simplified Chinese	1255	Hebrew
949	Korean	1256	Arabic
950	Traditional Chinese	1257	Baltic
1251	Cyrillic	1258	Vietnamese
1252	Latin-1 (similar to ISO 8859-1)		

<1> Section 2.3.3: Outlook 2003 and Exchange 2003 allocate and zero-fill an extra 8-byte structure after the **sender-e-mail** field.

<2> Section 5.1: The Exchange 2003 implementation of **TNEF** would use the **MIME character set** to determine its mapping of strings in the attributes and of ANSI strings in the encapsulated properties, regardless of the value of **attOemCodePage**. This can cause some confusion, but if they follow the rules in section 5 for reading and writing TNEF, other implementations are not likely to have any significant interoperability issues.

Index

ABNF description, 9
Applicability statement, 8
Attributes, 13
Encapsulated message properties, 21
Glossary, 5
Informative references, 7
Introduction, 5
Normative references, 6
Office/Exchange behavior, 35
Other compatibility issues, 33
Overview, 7
References, 6

- Informative references, 7
- Normative references, 6

Relationship to protocols and other structures, 7
Security considerations, 33
Structure, 8

- ABNF description, 9
- Attributes, 13
- Encapsulated message properties, 21

Structure examples, 26
Versioning, 8