

[MS-OXTNEF]: Transport Neutral Encapsulation Format (TNEF) Data Structure

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

| Date | Revision History | Revision Class | Comments |
|------------|------------------|----------------|---|
| 04/04/2008 | 0.1 | | Initial Availability. |
| 04/25/2008 | 0.2 | | Revised and updated property names and other technical content. |
| 06/27/2008 | 1.0 | | Initial Release. |
| 08/06/2008 | 1.01 | | Revised and edited technical content. |
| 09/03/2008 | 1.02 | | Revised and edited technical content. |
| 12/03/2008 | 1.03 | | Revised and edited technical content. |
| 03/04/2009 | 1.04 | | Revised and edited technical content. |
| 04/10/2009 | 2.0 | | Updated technical content and applicable product releases. |
| 07/15/2009 | 3.0 | Major | Revised and edited for technical content. |
| 11/04/2009 | 3.1.0 | Minor | Updated the technical content. |
| 02/10/2010 | 4.0.0 | Major | Updated and revised the technical content. |
| 05/05/2010 | 5.0.0 | Major | Updated and revised the technical content. |
| 08/04/2010 | 5.1 | Minor | Clarified the meaning of the technical content. |
| 11/03/2010 | 5.2 | Minor | Clarified the meaning of the technical content. |

Contents

| | |
|--|-----------|
| 1 Introduction | 5 |
| 1.1 Glossary | 5 |
| 1.2 References | 5 |
| 1.2.1 Normative References | 5 |
| 1.2.2 Informative References | 6 |
| 1.3 Overview | 6 |
| 1.4 Relationship to Protocols and Other Structures | 6 |
| 1.5 Applicability Statement | 7 |
| 1.6 Versioning and Localization | 7 |
| 1.7 Vendor-Extensible Fields | 7 |
| 2 Structures | 8 |
| 2.1 Conventions | 8 |
| 2.1.1 Address Representations | 8 |
| 2.1.2 ABNF Rules | 9 |
| 2.2 ABNF Description | 9 |
| 2.3 Attributes | 12 |
| 2.3.1 attTnefVersion | 12 |
| 2.3.2 attOemCodepage | 12 |
| 2.3.3 attFrom | 12 |
| 2.3.4 Date Attributes | 13 |
| 2.3.5 Message Class Attributes | 14 |
| 2.3.6 Conversation-Tracking Attribute | 15 |
| 2.3.7 attSubject | 15 |
| 2.3.8 attMessageStatus | 15 |
| 2.3.9 attBody | 15 |
| 2.3.10 attPriority | 16 |
| 2.3.11 attAttachData | 16 |
| 2.3.12 attAttachTitle | 16 |
| 2.3.13 attAttachMetaFile | 16 |
| 2.3.14 attAttachTransportFilename | 16 |
| 2.3.15 attAttachRendData | 16 |
| 2.3.16 attOwner | 17 |
| 2.3.17 attSentFor | 18 |
| 2.3.18 attDelegate | 18 |
| 2.3.19 attAidOwner | 19 |
| 2.3.20 attRequestRes | 19 |
| 2.3.21 attMsgProps | 19 |
| 2.3.22 attRecipTable | 19 |
| 2.3.23 attAttachment | 19 |
| 2.4 Encapsulated Message and Attachment Properties | 19 |
| 3 Structure Examples | 24 |
| 3.1 Sample Message | 24 |
| 3.2 Sample Meeting Response | 35 |
| 4 Security | 38 |
| 4.1 Security Considerations for Implementers | 38 |
| 4.2 Index of Security Fields | 38 |
| 5 Other Compatibility Issues | 39 |

| | |
|---|-----------|
| 5.1 attOemCodepage Handling..... | 39 |
| 5.1.1 Encoding by TNEF Writer..... | 39 |
| 5.1.2 Decoding by TNEF Reader | 39 |
| 5.2 TNEF Encapsulation vs. Outer Wrapper Attributes | 39 |
| 5.2.1 attBody Handling..... | 40 |
| 5.2.2 attRecipTable Handling | 40 |
| 5.2.3 attFrom Handling | 40 |
| 5.2.4 attSubject Handling | 40 |
| 6 Appendix A: Product Behavior | 41 |
| 7 Change Tracking..... | 42 |
| 8 Index | 48 |

1 Introduction

This document specifies a data structure for transmitting rich **properties** of electronic mail messages over a serial data stream. The result might be transported as a stream, as a file attachment in an arbitrary transport, or as a **MIME** [\[RFC2045\]](#) entity body on an Internet transport.

1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

Augmented Backus-Naur Form (ABNF)
binary large object (BLOB)
body part
character set
code page (1)
EntryID
GUID
Internet Message Access Protocol (IMAP)
little-endian
message class
Message object
MIME
plain text
Post Office Protocol - Version 3 (POP3)
property (1)
recipient (1)
Simple Mail Transfer Protocol (SMTP)
Transport Neutral Encapsulation Format (TNEF)
Unicode
UTF-16LE (Unicode Transformation Format, 16 bits, Little-Endian)

The following terms are specific to this document:

CLSID: A **GUID** that is associated with an object class.

Interface Identifier (IID): A **GUID** that uniquely identifies a particular interface.

TNEF Reader: The entity that is decoding a **TNEF** structure after message reception, for the purpose of reconstructing the rich properties that are contained in the stream.

TNEF Writer: The entity that is encoding/building a **TNEF** structure for the purpose of transporting rich properties.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site,

<http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-DTYP] Microsoft Corporation, "Windows Data Types", March 2007, <http://msdn.microsoft.com/en-us/library/cc230273.aspx>

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)", April 2008.

[MS-OXCMAIL] Microsoft Corporation, "[RFC2822 and MIME to E-Mail Object Conversion Protocol Specification](#)", April 2008.

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)", April 2008.

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)", April 2008.

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol Specification](#)", April 2008.

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)", April 2008.

[MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)", April 2008.

[RFC2045] Freed, N., and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", RFC 2045, November 1996, <http://www.ietf.org/rfc/rfc2045.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.ietf.org/rfc/rfc5234.txt>

1.2.2 Informative References

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", April 2008.

[MS-WMF] Microsoft Corporation, "Windows Metafile Format Specification", June 2007, <http://msdn.microsoft.com/en-us/library/cc215212.aspx>

[MSDN-UAF] Microsoft Corporation, "UUENCODE Attachment Format", [http://msdn.microsoft.com/en-us/library/aa579638\(v=EXCHG.80\).aspx](http://msdn.microsoft.com/en-us/library/aa579638(v=EXCHG.80).aspx)

1.3 Overview

Transport Neutral Encapsulation Format (TNEF) organizes a hierarchy of rich message properties into a flattened structure that can be represented as a serial data stream. The typical structure of a particular property within the stream is: identifier (which usually also includes type information), size (where not exactly determined by type), data. In some cases, as specified in this document, groups of properties or multiple-value properties include counts. Others might include "padding" to enforce a particular alignment of the data.

1.4 Relationship to Protocols and Other Structures

The structure is intended to permit the transmission of rich Message property information over transports that have no mechanism for representing that information natively.

The structure can be included as a file attachment (winmail.dat), as a MIME [\[RFC2045\]](#) **body part** (using the "application/ms-TNEF" media type), added to the transmitted **plain text** body using UUENCODE, as described in [\[MSDN-UAF\]](#), or a similar method, to be decoded at the **recipient** end, or transported from sender to recipient using whatever means are provided by the protocol employed in transmitting Message information between them.

This document specifically covers the application of this structure for transmission of message data over **Simple Mail Transfer Protocol (SMTP)**, **Post Office Protocol – Version 3 (POP3)**, **Internet Message Access Protocol (IMAP)**, or other Internet protocols that incorporate MIME [\[RFC2045\]](#).

All numeric data types in the structure that are greater than one byte in size are **little-endian** and any handling of these values on platforms that are not little-endian are required to take this into account and perform the appropriate transformations to get correct numbers, counts, values, and so on.

Contents of string examples in this document will be shown in **Augmented Backus-Naur Form (ABNF)** [\[RFC5234\]](#) format. Where the string has a terminating zero character, this will also be in that format; for example, "user1@example.com" %x00. For the purpose of string examples, the different terminating zero character size in a **Unicode character set** will not be illustrated.

1.5 Applicability Statement

The original application of the structure was to permit the creation and representation of **message classes** other than simple e-mail messages, and some additional attributes that were not natively supported by the transport protocol.

This application was further extended to allow the transport of the rich set of properties required by more modern messaging clients, including named properties [\[MS-OXPROPS\]](#). For backward compatibility with the original implementation, a special attribute is used to encapsulate the new message properties, and those properties with analogues to the original implementation are usually represented using the original attribute syntax.

1.6 Versioning and Localization

None.

1.7 Vendor-Extensible Fields

None.

2 Structures

In this specification, attributes using the original syntax described in section [1.5](#) are referred to as "attributes" and the rich set of properties described in section [1.5](#) will be referred to as "properties".

The TNEF stream starts with a signature and a legacy key value, an attribute containing a legacy version number, and an attribute containing the **code page** used by the encoder for ANSI attributes and properties. After that, the stream is a series of attributes laid out, one after the other – Message attributes followed by attachment attributes. Three special attributes contain the various message and attachment properties, two of which are counted lists; the third is a counted list of counted lists.

Each attribute is laid out as follows: level at which it applies (message or attachment), ID, length (of the contained data), the data itself, and a simple 16-bit checksum of the bytes comprising the data.

The special attribute that contains the encapsulated message properties SHOULD be encoded after all other message attributes, and the special attribute that contains the encapsulated attachment properties SHOULD be encoded after all other attachment attributes. Values of encapsulated properties SHOULD be used instead of any conflicting mapped attribute values. Message attributes and properties SHOULD be encoded before attachment attributes and properties.

Each set of attachment attributes MUST begin with **attAttachRendData**, followed by any other attributes; attachment properties encoded in **attAttachment** SHOULD be last.

2.1 Conventions

This specification uses the following conventions and common definitions for address representations and ABNF rule definitions.

2.1.1 Address Representations

Address elements other than recipients, such as From and Sender, are represented in a **Message object** by a group of four properties: display name, address type, e-mail address, **EntryID**. In subsequent sections these groups are referred to as described here.

PidTagReceivedRepresenting_XXX: Refers to ([PidTagReceivedRepresentingName](#), [PidTagReceivedRepresentingAddressType](#), and [PidTagReceivedRepresentingEmailAddress](#)), or [PidTagReceivedRepresentingEntryId](#), where either would suffice to fully represent the display name, e-mail transport type, and e-mail address of a particular recipient or person on behalf of whom a message was received. See [\[MS-OXPROPS\]](#) for details about the **PidTagReceivedRepresenting** message properties.

PidTagSender_XXX: Refers to ([PidTagSenderName](#), [PidTagSenderAddressType](#), and [PidTagSenderEmailAddress](#)), or [PidTagSenderEntryId](#), where either would suffice to fully represent the **display name**, e-mail transport type, and e-mail address of a sender. See [\[MS-OXPROPS\]](#) for more details the **PidTagSender** message properties.

PidTagSentRepresenting_XXX: Refers to ([PidTagSentRepresentingName](#), [PidTagSentRepresentingAddressType](#), and [PidTagSentRepresentingEmailAddress](#)), or [PidTagSentRepresentingEntryId](#), where either would suffice to fully represent the display name, e-mail transport type, and e-mail address of a sender or person on behalf of whom a message was sent. See [\[MS-OXPROPS\]](#) for more details about the **PidTagSentRepresenting** message properties.

2.1.2 ABNF Rules

This section specifies ABNF rules for data types common throughout section 2. For more information about these data types, see [\[MS-DTYP\]](#).

| Data type | ABNF rules |
|-----------|-------------------------|
| INT16 | INT16 = ["-"] 1*5DIGIT |
| INT32 | INT32 = ["-"] 1*10DIGIT |
| INT64 | INT64 = ["-"] 1*19DIGIT |
| UINT16 | UINT16 = 1*5DIGIT |
| UINT32 | UINT32 = 1*10DIGIT |

2.2 ABNF Description

```
TNEFStream = TNEFHeader TNEFVersion OEMCodePage MessageData *AttachData

TNEFVersion = attrLevelMessage idTnefVersion Length TNEFVersionData Checksum

OEMCodePage = attrLevelMessage idOEMCodePage Length OEMCodePageData Checksum

MessageData = *MessageAttribute [MessageProps]
MessageAttribute = attrLevelMessage idMessageAttr Length Data Checksum
MessageProps = attrLevelMessage idMsgProps Length Data Checksum

; An attachment is determined/delimited by attAttachRendData, followed by
; other encoded attributes, if any, and ending with attAttachment if there are
; any encoded properties.

AttachData = AttachRendData [*AttachAttribute] [AttachProps]
AttachRendData = attrLevelAttachment idAttachRendData Length Data Checksum
AttachAttribute = attrLevelAttachment idAttachAttr Length Data Checksum
AttachProps = attrLevelAttachment idAttachment Length Data Checksum

; TNEF Version. TNEF writers MUST use %x00.00.01.00
; TNEF readers MUST reject other values
TNEFVersionData = 4*4OCTET

; This is the code page of attribute strings. MUST contain an 8-bit
; code page (that is, a code page in which all characters are 8 bits
; in length) for compatibility with legacy applications that cannot handle
; "strings" with "embedded zero characters."
OEMCodePageData = PrimaryCodePage SecondaryCodePage
PrimaryCodePage=UINT32
; Secondary CodePage is unused. SHOULD contain zero.
SecondaryCodePage=%x00.00.00.00

TNEFHeader = TNEFSignature LegacyKey
TNEFSignature = %x78.9F.3E.22

; Any number will suffice here. This is now legacy.
LegacyKey = UINT16

; The length of the following data field in bytes. All attribute lengths are
```

```

; 32-bit integers, including any terminating null characters.

Length = INT32

; Data of the attribute itself, flattened out based on the particular attribute
; according to the rules that follow.

Data = 0*OCTET

; 16-bit unsigned integer that is the sum, modulo 65536, of the data bytes for
; the attribute value data, calculated over the entire length of the attribute data.
; In the case where the attribute contains enhanced properties with padding, the
; pad bytes MUST be included in the calculation.

Checksum = UINT16

; Level where attribute applies, either to the message itself or to
; an attachment.

attrLevelMessage = %x01
attrLevelAttachment = %x02

; Attribute ID Tags

; TNEF Version
idTnefVersion = %x06.90.08.00

; OEM Codepage. See attOemCodepage handling in section 5 and Appendix A.
idOemCodepage = %x07.90.06.00

; Message-level attributes. SHOULD all be at attrLevelMessage.
idMessageAttr = idMessageClass / idFrom / idSubject / idDateSent /
idDateRecd / idMessageStatus / idMessageID /
idBody / idPriority / idDateModified /
idRecipTable / idOriginalMessageClass / idOwner / idSentFor /
idDelegate / idDateStart / idDateEnd / idAidOwner / idRequestRes

; PidTagMessageClass
idMessageClass = %x08.80.07.00

; PidTagSender_XXX
idFrom = %x00.80.00.00

; PidTagSubject
idSubject = %x04.80.01.00

; PidTagClientSubmitTime
idDateSent = %x05.80.03.00

; PidTagMessageDeliveryTime
idDateRecd = %x06.80.03.00

; PidTagMessageFlags
idMessageStatus = %x07.80.06.00

; PidTagSearchKey
idMessageID = %x09.80.01.00

; PidTagBody

```

```

idBody = %x0C.80.02.00

; PidTagImportance
idPriority = %x0D.80.04.00

; PidTagLastModificationTime (message)
idDateModified = %x20.80.03.00

; Message Property Encapsulation
idMsgProps = %x03.90.06.00

; PidTagMessageRecipients. See attRecipTable handling
; in section 5.
idRecipTable = %x04.90.06.00

; PidTagOriginalMessageClass
idOriginalMessageClass = %x00.06.07.00

; PidTagReceivedRepresenting_XXX or
PidTagSentRepresenting_XXX
idOwner = %x00.00.06.00

; PidTagSentRepresenting_XXX
idSentFor = %x01.00.06.00

; PidTagReceivedRepresentingEntryId
idDelegate = %x00.02.06.00

; PidTagStartDate
idDateStart = %x06.00.03.00

; PidTagEndDate
idDateEnd = %x07.00.03.00

; PidTagOwnerAppointmentId
idAidOwner = %x08.00.05.00

; PidTagResponseRequested
idRequestRes = %x09.00.04.00

; Attachment-level attributes. MUST all be at attrLevelAttachment.
idAttachAttr = idAttachData / idAttachTitle / idAttachMetaFile /
idAttachCreateDate / idAttachModifyDate / idAttachTransportFilename

; PidTagAttachDataBinary
idAttachData = %x0F.80.06.00

; PidTagAttachFilename
idAttachTitle = %x10.80.01.00

; PidTagAttachRendering
idAttachMetaFile = %x11.80.06.00

; PidTagCreationTime
idAttachCreateDate = %x12.80.03.00

; PidTagLastModificationTime (attachment)
idAttachModifyDate = %x13.80.03.00

```

```
; PidTagAttachTransportName
idAttachTransportFilename = %x01.90.06.00

; Attachment RendData (section 2.3.15)
idAttachRendData = %x02.90.06.00

; Attachment table row
idAttachment = %x05.90.06.00
```

2.3 Attributes

This section describes the attributes that appear in the TNEF stream, including the structure of the attributes, the message properties they map to, and any required conversions between them and message properties.

Each attribute is described by a level at which it applies (message or attachment), the attribute ID, the length of the attribute data, the attribute data, and a simple checksum. They are documented in the following sections in the form "**attXXXX**." For example, **attSubject** refers to the following:

attrLevelMessage idSubject Length *VCHAR Checksum

2.3.1 attTnefVersion

Originally meant to permit versioning of the structure, this attribute is now legacy. **TNEF Writers** MUST write it as %x00.00.01.00 and **TNEF Readers** MUST reject other content.

2.3.2 attOemCodepage

Contains the code page used by the TNEF Writer for all attribute string values, and for any ANSI strings in the encapsulated message properties. See section [5.1](#) for information about code page handling.

2.3.3 attFrom

This Message-level attribute maps to/from **PidTagSender_XXX**.

The data for this attribute encodes as follows:

TRP-structure = TRP-header sender-display-name sender-email

TRP-header = trpidOneOff structure-length sender-name-length sender-email-length

; Structure type

trpidOneOff = %x04.00

; The length of the entire structure. See the following description.

structure-length = UINT16

; Length of sender display name string, including the terminating zero character.

sender-name-length = UINT16

; Length of sender e-mail string, including the terminating zero character.

sender-email-length = UINT16

sender-display-name = 1*OCTET %x00

sender-email = sender-email-type ":" sender-email-address %x00

sender-email-type = 1*CHAR

sender-email-address = 1*CHAR

The structure-length field is calculated as 8 (the size of TRP-header in OCTETs) plus the length of sender-display-name (including the terminating zero character), and the length of sender-email (including the terminating zero character).<1>

The sender-name-length field is the length of sender-display-name in OCTETs (including the terminating zero character).

The sender-email-length field is calculated as the length of sender-email (including the terminating zero character).

The sender-email string is composed of four parts, the address-type (for example, the literal sequence "SMTP" for Internet addresses), a literal colon (":"), the address itself, and a terminating zero character. For example, the string "SMTP:user2@example.com" %x00 is a legal sender-email value.

TNEF Writers can use the discrete **PidTagSender Name**, **AddressType**, and **EmailAddress** properties if present, or access their values using the [PidTagSenderEntryId](#) property ([\[MS-OXOMSG\]](#) section 2.2.1.42); TNEF Readers MUST set the [PidTagSenderEntryId](#) property and SHOULD decode the **attOwner** attribute into the other **PidTagSender** properties.

2.3.4 Date Attributes

The data for these attributes encode into a Date Time Record structure, as follows:

DTR = wYear wMonth wDay wHour wMinute wSecond wDayOfWeek

wYear = UINT16

wMonth = UINT16

wDay = UINT16

wHour = UINT16

wMinute = UINT16

wSecond = UINT16

wDayOfWeek = UINT16

wYear contains the year (for example, 2008 is %xD8.07); wMonth is 1 for January, and so on; wDay is 1 for the first day of the month; wHour, wMinute, and wSecond contain the time; wDayOfWeek is 1 for Monday.

| Attribute (in TNEF) | Level | Message property |
|---------------------|---------|--|
| attDateSent | Message | PidTagClientSubmitTime |

| Attribute (in TNEF) | Level | Message property |
|----------------------------|------------|--|
| attDateRecd | Message | PidTagMessageDeliveryTime |
| attAttachCreateDate | Attachment | PidTagCreationTime |
| attAttachModifyDate | Attachment | PidTagLastModificationTime |
| attDateModified | Message | PidTagLastModificationTime |
| attDateStart | Message | PidTagStartDate |
| attDateEnd | Message | PidTagEndDate |

2.3.5 Message Class Attributes

The message class attribute value is stored as a zero-terminated string that usually will hold the name specified by the client.

- TNEF Writers can represent any message class whose value is shown in the Message Property Value column of table 1, using the value in the Attribute Value column.
- TNEF Readers MUST do the appropriate reverse mapping: if **attMessageClass** contains a value that is shown in the Attribute Value column, the value that MUST be returned is that of the value in the Message Property Value column. If the **attMessageClass** value begins with the string "Microsoft Mail v3.0", the TNEF Reader MUST ignore the "Microsoft Mail v3.0" prefix when attempting to match the **attMessageClass** value to a value in the Attribute Value column. For example, the TNEF Reader MUST consider the **attMessageClass** value Microsoft Mail v3.0 IPM.Microsoft.Mail.Note to be the same as the **attMessageClass** value IPM.Microsoft.Mail.Note – which corresponds to the Message Property Value IPM.Note.
- TNEF Readers SHOULD ignore the checksum value for message class attributes because some legacy TNEF Writers generated invalid checksum values.
- Other values SHOULD be written and read in their original form.

Table 1: Attribute and Message Property Values

| Attribute Value (in TNEF) | Message Property Value |
|---------------------------------|--------------------------------|
| IPM.Microsoft Mail.Note | IPM.Note |
| IPM.Microsoft Mail.read receipt | Report.IPM.Note.IPNRN |
| IPM.Microsoft Mail.Non-Delivery | Report.IPM.Note.NDR |
| IPM.Microsoft Schedule.MtgRespP | IPM.Schedule.Meeting.Resp.Pos |
| IPM.Microsoft Schedule.MtgRespN | IPM.Schedule.Meeting.Resp.Neg |
| IPM.Microsoft Schedule.MtgRespA | IPM.Schedule.Meeting.Resp.Tent |
| IPM.Microsoft Schedule.MtgReq | IPM.Schedule.Meeting.Request |
| IPM.Microsoft Schedule.MtgCncl | IPM.Schedule.Meeting.Canceled |

Message class attributes in TNEF are as follows:

| Attribute in TNEF | Level | Message Property |
|--------------------------------|---------|--|
| attMessageClass | Message | PidTagMessageClass |
| attOriginalMessageClass | Message | PidTagOriginalMessageClass |

2.3.6 Conversation-Tracking Attribute

The **PidTagSearchKey** property ([\[MS-OXCPRPT\]](#) section 2.2.1.9) that maps to this attribute is stored in binary, but the attribute is represented in text format. For compatibility, when generating a TNEF structure, the TNEF Writer MUST translate the binary representation into a textual one by emitting the two CHAR hexadecimal equivalent per OCTET (i.e. %x01 becomes "01", %x2D becomes "2D", and so on). Likewise, when reading the attribute from TNEF, the TNEF Reader SHOULD attempt to decode the text format back into binary.

| Attribute (in TNEF) | Level | Message Property |
|---------------------|---------|---------------------------------|
| attMessageID | Message | PidTagSearchKey |

2.3.7 attSubject

This Message-level attribute maps to/from [PidTagSubject](#).

The data for this attribute is stored as a string with a terminating zero character.

2.3.8 attMessageStatus

This Message-level attribute maps to/from [PidTagMessageFlags](#).

The data for this attribute is stored as an unsigned 32-bit integer, with the appropriate bits set to indicate the Message status. For compatibility, these MUST be mapped to/from the following values:

| Status | Attribute Flag (in TNEF) | Bit Value | Message Property Flag | Bit Value |
|-----------------|--------------------------|-----------|-----------------------|-----------|
| Read | fmsRead | 0x20 | MSGFLAG_READ | 0x01 |
| Unmodified | fmsModified | 0x01 | MSGFLAG_UNMODIFIED | 0x02 |
| Submitted | fmsSubmitted | 0x04 | MSGFLAG_SUBMIT | 0x04 |
| Unsent | fmsLocal | 0x02 | MSGFLAG_UNSENT | 0x08 |
| Has Attachments | fmsHasAttach | 0x80 | MSGFLAG_HASATTACH | 0x10 |

If the attribute flag fmsModified is set, then the corresponding message property flag (MSGFLAG_UNMODIFIED) is clear (that is, not set). If the attribute flag fmsModified is clear, then the corresponding message property flag (MSGFLAG_UNMODIFIED) is set. For all other flags, either both the attribute flag and corresponding message property flag are set or both the attribute flag and corresponding message property flag are clear.

2.3.9 attBody

This Message-level attribute maps to/from [PidTagBody](#).

The data for this attribute is stored as a string with a terminating zero character.

2.3.10 attPriority

This Message-level attribute maps to/from [PidTagImportance](#).

The data for this attribute is stored as an unsigned 16-bit integer. For compatibility, these MUST be mapped to/from the following values:

| Priority | Value (in TNEF) | Message Property Value |
|----------|-----------------|------------------------|
| Low | 3 | 0 |
| Normal | 2 | 1 |
| High | 1 | 2 |

2.3.11 attAttachData

This Attachment-level attribute maps to/from [PidTagAttachDataBinary](#).

The data for this attribute is stored as a binary stream.

TNEF Writers can use this attribute for the attachment data if the [PidTagAttachMethod](#) of the original attachment contains the value 0x0001 (ATTACH_BY_VALUE). If the [PidTagAttachMethod](#) of the original attachment contains the value 0x0005 (ATTACH_EMBEDDED_MSG) or the value 0x0006 (ATTACH_OLE), then TNEF Writers MUST encode the data in **attAttachment** (section 2.4), and TNEF Readers SHOULD ignore **attAttachData**.

2.3.12 attAttachTitle

This Attachment-level attribute maps to/from [PidTagAttachLongFilename](#).

The data for this attribute is stored as a string with a terminating zero character.

TNEF Writers obtain **attAttachTitle** from [PidTagAttachLongFilename](#) if it is available; otherwise, TNEF Writers obtain **attAttachTitle** from [PidTagAttachFilename](#). TNEF Readers always set [PidTagAttachLongFilename](#).

2.3.13 attAttachMetaFile

This Attachment-level attribute maps to/from [PidTagAttachRendering](#).

The data for this attribute is stored as a binary stream. See [\[MS-WMF\]](#) for a description of the content.

2.3.14 attAttachTransportFilename

This Attachment-level attribute maps to/from [PidTagAttachTransportName](#).

The data for this attribute is stored as a string with a terminating zero character.

2.3.15 attAttachRendData

This attachment-level attribute contains a structure that contains information that can be used for rendering the attachment in the body.

Each set of attachment attributes MUST begin with **attAttachRenderData**, followed by any other attributes; attachment properties encoded in **attAttachment** SHOULD be last.

The structure is laid out as follows:

attAttachRenderData = AttachType AttachPosition RenderWidth RenderHeight DataFlags

AttachType = AttachTypeFile / AttachTypeOle

AttachTypeFile=%x01.00

AttachTypeOle=%x02.00

AttachPosition= INT32

RenderWidth=INT16

RenderHeight=INT16

DataFlags = FileDataDefault / FileDataMacBinary

FileDataDefault= %x00.00.00.00

FileDataMacBinary=%x01.00.00.00

AttachType MUST be set by the TNEF Writer to AttachTypeFile when [PidTagAttachMethod](#) ([MS-OXPROPS] section 2.667) for the attachment is ATTACH_BY_VALUE or ATTACH_EMBEDDED_MSG, and to AttachTypeOle when [PidTagAttachMethod](#) ([MS-OXPROPS] section 2.667) is ATTACH_OLE.

TNEF Readers SHOULD set [PidTagAttachTag](#) ([MS-OXPROPS] section 2.675) for the attachment to %x2A.86.48.86.F7.14.03.0A.03.01.01 when AttachTypeOle is set. TNEF Readers SHOULD NOT set [PidTagAttachTag](#) ([MS-OXPROPS] section 2.675) for the attachment when AttachTypeFile is set.

AttachPosition maps to/from [PidTagRenderingPosition](#) ([MS-OXPROPS] section 2.1021).

RenderWidth and RenderHeight SHOULD be set by the TNEF Writer to the size of the system icons if the attachment is a simple file attachment, or to {-1,-1} if the attachment is not a simple file attachment.

If [PidTagAttachEncoding](#) ([MS-OXPROPS] section 2.657) for the attachment consists of bytes %x2A.86.48.86.F7.14.03.0B.01, then FileDataMacBinary SHOULD be set by the TNEF Writer; otherwise FileDataDefault SHOULD be set by the TNEF Writer. <2> The TNEF Reader SHOULD set the value of the [PidTagAttachEncoding](#) property ([MS-OXPROPS] section 2.657) for the attachment to the same bytes when **DataFlags** contains FileDataMacBinary. If **DataFlags** contains FileDataDefault, then the TNEF Reader SHOULD NOT set the value of the [PidTagAttachEncoding](#) property ([MS-OXPROPS] section 2.657) for the attachment.

2.3.16 attOwner

This Message-level attribute is a Meeting attribute that maps to/from **PidTagReceivedRepresenting_XXX** or **PidTagSentRepresenting_XXX**.

The **attOwner** attribute is encoded as counted strings laid end-to-end. The format for **attOwner** is as follows:

attOwner=display-name-length display-name address-length address

; Length of "display-name," including terminating zero character.

display-name-length=UINT16

display-name=*CHAR %x00

; Length of "address", including terminating zero character.

address-length=UINT16

address= 1*CHAR ":" 1*CHAR %x00

The display-name-length and address-length are unsigned 16-bit values, including the terminating zero characters for the strings. The type and address strings in the email-address entry are separated by a colon (:) character; for example, "SMTP:user1@example.com" %x00.

The mapping of message properties to the **attOwner** attribute is dependent on the message class of the message being encoded.

If the message is either a Meeting Request or Meeting Cancellation (from the organizer, who is creating or deleting a meeting), the TNEF Writer SHOULD encode the **PidTagSentRepresenting** properties in the **attOwner** attribute and the TNEF Reader SHOULD decode the **attOwner** attribute into the **PidTagSentRepresenting** properties.

If the message is a meeting response of any type (from attendee, accepting, declining, and so on), the TNEF Writer SHOULD encode the **PidTagReceivedRepresenting** properties in the **attOwner** attribute and the TNEF Reader SHOULD decode the **attOwner** attribute into the **PidTagReceivedRepresenting** properties. For details about how to construct the EntryId property, see [\[MS-OXOMSG\]](#) section 2.2.1.25.

TNEF Writers can use the discrete **PidTag{Sent | Rcvd}Representing Name, AddressType, and EmailAddress** properties if present, or access their values by using the **PidTag{Sent | Rcvd}EntryId** property; TNEF Readers MUST set the **PidTag{Sent | Rcvd} EntryId** property and SHOULD decode the **attOwner** attribute into the other **PidTag{Sent | Rcvd} Representing** properties.

2.3.17 attSentFor

This Message-level attribute is a Meeting attribute that maps to/from **PidTagSentRepresenting_XXX**.

The TNEF Writer SHOULD encode the **PidTagSentRepresenting** properties in the **attSentFor** attribute and the TNEF Reader SHOULD decode the **attSentFor** attribute into the **PidTagSentRepresenting** properties.

TNEF Writers can use the discrete **PidTagSentRepresenting Name, AddressType, and EmailAddress** properties if present, or access their values by using the [PidTagSentRepresentingEntryId](#) property ; TNEF Readers SHOULD set the [PidTagSentRepresentingEntryId](#) property and SHOULD decode the attOwner attribute into the other **PidTagSentRepresenting** properties.

2.3.18 attDelegate

This Message-level attribute is a Meeting attribute that maps to/from [PidTagReceivedRepresentingEntryId](#).

The TNEF Writer SHOULD encode the **PidTagReceivedRepresentingEntryId** properties in the **attDelegate** attribute and the TNEF Reader SHOULD decode the attDelegate attribute into the **PidTagReceivedRepresentingEntryId** properties. [<3>](#)

The content can be transported as a **binary large object (BLOB)**. See [\[MS-OXPROPS\]](#) for an explanation of the [PidTagReceivedRepresentingEntryId](#) property.

2.3.19 attAidOwner

This Message-level attribute is a Meeting attribute that maps to/from [PidTagOwnerAppointmentId](#).

The content can be transported as a BLOB. See [\[MS-OXOCAL\]](#) for an explanation of the [PidTagOwnerAppointmentId](#) property.

2.3.20 attRequestRes

This Message-level attribute is a Meeting attribute that maps to/from [PidTagResponseRequested](#).

This is a Boolean; it SHOULD be transported as a 16-bit integer (the low order 16 bits of [PidTagResponseRequested](#)). See [\[MS-OXOCAL\]](#) for an explanation of the [PidTagResponseRequested](#) property.

2.3.21 attMsgProps

This Message-level attribute maps to/from an arbitrary set of message properties.

TNEF Writers SHOULD write this attribute after all the other message attributes and immediately before all the attachment attributes. See section [2.4](#) for a description of the encoding for this attribute.

2.3.22 attRecipTable

This Message-level attribute maps to/from [PidTagMessageRecipients](#).

See section [2.4](#) for a description of the encoding for this attribute.

2.3.23 attAttachment

This Attachment-level attribute maps to/from an arbitrary set of properties for a single attachment.

TNEF Writers SHOULD write this encapsulation after all the attributes for an attachment. See section [2.4](#) for a description of the encoding for this attribute.

2.4 Encapsulated Message and Attachment Properties

The attributes **attMsgProps** (section [2.3.21](#)) and **attAttachment** (section [2.3.23](#)) are special in that they are used to encode any message or attachment property that does not have a counterpart in the set of existing TNEF-defined attributes. The attribute data is a counted set of message or attachment properties laid end-to-end. The format of this encoding, which allows for any set of message or attachment properties, is as follows.

```
MsgPropertyList = MsgPropertyCount *MsgPropertyValue
MsgPropertyCount = UINT32

MsgPropertyValue = MsgPropertyTag MsgPropertyData
MsgPropertyTag = MsgPropertyType MsgPropertyId [NamedPropSpec]

; MUST be present when MsgPropertyId is >= 0x8000 (the minimum value
; of property ID for named properties, as specified in [MS-OXPROPS]
; section 1.3.3).
```

```

NamedPropSpec = PropNameSpace PropIDType PropMap

; Contains a GUID (as specified in [MS-OXCADATA]) to specify the namespace.
; The Writer obtains this value by using RopGetNamesFromPropertyIDs
; (as specified in [MS-OXCROPS]).
PropNameSpace = GUID
PropIDType = IDTypeNumber / IDTypeString
PropMap = PropMapID / PropMapString

IDTypeNumber = %x00.00.00.00
IDTypeString = %x01.00.00.00

; Used if PropIDType is IDTypeNumber. Contains a number (as specified in
; [MS-OXPROPS]) that is used to identify the property within the namespace.
PropMapID = UINT32

; Used if PropIDType is IDTypeString. Contains a length, then a
; UTF-16LE encoded Unicode string.
; The length is the length of the UTF-16LE encoded Unicode string
; (including the terminating 2-byte zero character).
; Optional padding to UINT32 boundary.
; The Writer obtains this value by using RopGetNamesFromPropertyIds
; (as specified in [MS-OXCROPS]).
PropMapString = UINT32 *UINT16 %00.00 [PropMapPad]

; Padding for a UTF-16LE encoded Unicode string to achieve a
; multiple of 4 bytes in length.
; Writers MUST use zero bytes and Readers MUST permit non-zero bytes.
; Should be either 0 or 2 bytes.
PropMapPad=*1UINT16

MsgPropertyType = TypeUnspecified / TypeNull / TypeInt16 / TypeInt32 /
TypeFlt32 / TypeFlt64 / TypeCurrency / TypeAppTime / TypeError /
TypeBoolean / TypeObject / TypeInt64 / TypeString8 / TypeUnicode /
TypeSystemtime / TypeCLSID / TypeBinary / TypeMVarInt16 / TypeMVarInt32 /
TypeMVarFlt32 / TypeMVarFlt64 / TypeMVCurrency / TypeMVAppTime /
TypeMVSystemtime / TypeMVString8 / TypeMVBinary / TypeMVUnicode /
TypeMVCLSID / TypeMVInt64

; An arbitrary value that corresponds to the property, MUST be unique for
; each named property.
MsgPropertyID = UINT16

TypeUnspecified = %x00.00

TypeNull = %x01.00

; Signed 16-bit value = INT16.
TypeInt16 = %x02.00
TypeMVarInt16 = %x02.10

; Signed 32-bit value = INT32.
TypeInt32 = %x03.00
TypeMVarInt32 = %x03.10

; Signed 32-bit floating point= FLOAT.
TypeFlt32 = %x04.00
TypeMVarFlt32 = %x04.10

```

```

; 64-bit floating point= DOUBLE.
TypeFlt64 = %x05.00
TypeMVFlt64 = %x05.10

; Signed 64-bit int = OLE CURRENCY type.
TypeCurrency = %x06.00
TypeMVCurrency = %x06.10

; Application time= OLE DATE type.
TypeAppTime = %x07.00
TypeMVAppTime = %x07.10

TypeError = %x0A.00

; 16-bit Boolean (non-zero = TRUE)
TypeBoolean = %x0B.00

; Embedded object on a property.
TypeObject = %x0D.00

; 8-byte signed integer= INT64.
TypeInt64 = %x14.00
TypeMVInt64 = %x14.10

; 8-bit character string with terminating zero character.
; See section 5.1 for more
; information about encoding and decoding 8-bit strings in TNEF.
TypeString8 = %x1E.00
TypeMVString8 = %x1E.10

; UTF-16LE or variant character string with terminating 2-byte zero character.
TypeUnicode = %x1F.00
TypeMVUnicode = %x1F.10

; FILETIME (see PtypTime as specified in [MS-OXCADATA] section 2.12.1)
TypeSystemtime = %x40.00
TypeMVSystemtime = %x40.10

; OLE GUID
TypeCLSID = %x48.00
TypeMVCLSID = %x48.10

; Uninterpreted BLOB.
TypeBinary = %x02.01
TypeMVBinary = %x02.11

; MsgPropertyData varies by property type. Individual property values
; are formatted as specified in section 2.12 of [MS-OXCADATA], with
; padding as specified in this document.
MsgPropertyData = PropertyScalarContent / PropertyMultiScalarContent /
PropertyMultiVariableContent

; Scalars - Types Int16, Int32, Flt32, Flt64, Currency, AppTime,
; Bool, Int64, Systemtime, CLSID
; The data for the particular property is written to the stream and if necessary,
; padded with bytes (which SHOULD be zero) to achieve a multiple of 4-bytes in length.

PropertyScalarContent = MsgPropertyContent [PropertyPad]

```

```

; PropertyPad - between 0 and 3 zero-filled bytes, added to the streamed
; property values to achieve 4-byte boundary. Writers MUST use zero bytes
; and Readers MUST permit non-zero bytes. These pad bytes MUST be counted
; in the checksum of the containing attribute.

PropertyPad=*3ZERO
ZERO= %x00

; Multi-value Scalars - Types MVInt16, MVInt32, MVFlt32, MVFlt64, MVCurrency,
; MVAppTime, MVInt64, MVSystime, MVCLSID
; The number of values for the property is written to the stream as a 4-byte
; value, then the data for each value is written to the stream and if need
; be, padded with bytes (which SHOULD be zero) to achieve a multiple of 4 bytes in length.

PropertyMultiScalarContent = PropertyContentCount *PropertyScalarContent
PropertyContentCount = UINT32

; Variable-length - Types Unicode, String8, Object, Binary.
; These are handled as a special case of Multi-Variable-Length with the number of values=1.

; Multi-Variable-length - Types MVUnicode, MVString8, MVBinary
; The number of values for the property is written to the stream as a 4-byte value,
; then for each value, the size of the property is written to the stream as a 4-byte
; value, then the data for the property is written to the stream and if necessary,
; padded with zero bytes to achieve a multiple of 4-bytes in length. No padding is necessary
; because each value was itself padded to a 4-byte boundary.

PropertyMultiVariableContent = MsgPropertyCount 1*PropertyVariableContent
MsgPropertyCount = UINT32

; The size of the property is written to the stream as a 4-byte value, then the data
; for the property is written to the stream and if necessary, padded with zero bytes
; to achieve a multiple of 4 bytes in length. The size includes the Interface
; Identifier at the beginning of the value stream for an object but does not include
; the padding bytes.
;
; If the property is of type PtypObject (as specified in [MS-OXCDATA] section 2.12.1),
; the value-size is followed by the Interface Identifier of the object, then the serialized
; stream of the data of the object. Only the Interface Identifier values
; %x0B.00.00.00.00.00.00.00.C0.00.00.00.00.00.00.46,
; %x0C.00.00.00.00.00.00.00.C0.00.00.00.00.00.00.46, and the Interface Identifiers of
; Message objects are supported. The size of the Interface Identifier is
; included in the calculation of value-size.
;
; If the object is an attached message (that is, it has a property type of
; PtypObject (as specified in [MS-OXCDATA] section 2.12.1) and an
; Interface Identifier %x07.03.02.00.00.00.00.00.C0.00.00.00.00.00.00.46,
; (that of a Message object), the value data is encoded as an embedded TNEF
; stream (that is, a complete TNEF stream as defined by this specification).

PropertyVariableContent = MsgPropertySize MsgPropertyContent [PropertyPad]
MsgPropertySize = UINT32

; Attributes containing encapsulated properties:

; attMsgProps - Maps to/from an arbitrary set of message properties.
MsgPropsData = MsgPropertyList

; attRecipTable - Maps to/from PidTagMessageRecipients.

```

```
; Number of table rows followed by the rows.  
RecipTableData = NumRows *RecipRow  
  
NumRows = UINT32  
RecipRow = MsgPropertyList  
  
; attAttachment - Maps to/from an arbitrary set of properties for a single attachment.  
AttachPropsData = MsgPropertyList
```

3 Structure Examples

3.1 Sample Message

| Explanation of content | Byte Stream |
|--|---|
| TNEF Signature , Value=0x223E9F78 | 78 9f 3e 22 |
| Attach Key , Value=0x0001 | 01 00 |
| Message attribute, attTnefVersion Length=4 bytes | 01 06 90 08 00 04 00 00 00 |
| Data=0x00010000 | 00 00 01 00 |
| Checksum=0x0001 | 01 00 |
| Message attribute, attOemCodepage Length=8 bytes | 01 07 90 06 00 08 00 00 00 |
| Data= (Primary=1252, Secondary=0) | e4 04 00 00 00 00 00 00 |
| Checksum=0x00E8 | e8 00 |
| Message attribute, attMessageClass Length=24 bytes | 01 08 80 07 00 18 00 00 00 |
| Data="IPM.Microsoft Mail.Note" %x00 | 49 50 4d 2e 4d 69 63 72 6f 73 6f 66 74 20 4d 61 69 6c 2e 4e 6f 74 65 00 |
| Checksum=0x0831 | 31 08 |
| Message attribute, attPriority Length=2 bytes | 01 0d 80 04 00 02 00 00 00 |
| Data=0x0002 (Normal Priority) | 02 00 |
| Checksum=0x0002 | 02 00 |
| Message attribute, attSubject Length=15 bytes | 01 04 80 01 00 0f 00 00 00 |
| Data="Simple subject" %x00 | 53 69 6d 70 6c 65 20 73 75 62 6a 65 |

| Explanation of content | Byte Stream |
|--|---|
| | 63 74 00 |
| Checksum=0x057A | 7a 05 |
| Message attribute, attDateSent Length=14 bytes | 01 05 80 03 00 0e 00 00 00 |
| Data= Tuesday, 02/17/2004, 11:25:35 | d4 07 02 00 11 00 0b 00 19 00 23 00 02 00 |
| Checksum=0x0137 | 37 01 |
| Message attribute, attDateModified Length=14 bytes | 01 20 80 03 00 0e 00 00 00 |
| Data= Tuesday, 02/17/2004, 12:26:09 | D4 07 02 00 11 00 0c 00 -- 1A 00 09 00 02 00 |
| Checksum=0x011F | 1F 01 |
| Message attribute, attMessageID Length=33 bytes | 01 09 80 01 00 21 00 00 00 |
| Data= "757BB19CDE936A4087D90BB784C58E3B" | 37 35 37 42 42 31 39 43 44 45 39 33 36 41 34 30 38 37 44 39 30 42 42 37 38 34 43 35 38 45 33 42 00 |
| Checksum=0x0751 | 51 07 |
| Message attribute, Encapsulation, attMsgProps Length=2256 bytes Number of properties=70 | 01 03 90 06 00 d0 08 00 00 46 00 00 00 |
| Message property, PidTagAlternateRecipientAllowed Value=1 (TRUE) | 0b 00 02 00 01 00 00 00 |
| Message property, PidTagPriority Value=0 (LOW) | 03 00 26 00 00 00 00 00 |
| Message property, PidTagSensitivity Value=0 (LOW) | 03 00 36 00 00 00 00 00 |
| Message property, PidTagClientSubmitTime Value=Tuesday, 02/17/2004, 19:25:35 | 40 00 39 00 |

| Explanation of content | Byte Stream |
|---|--|
| | AA D6 F3 D0 8B F5 C3 01 |
| Message property, PidTagSubjectPrefix Number of property values=1 Size of first property=1 | 1e 00 3d 00 01 00 00 00 01 00 00 00 |
| Value = %x00 | 00 |
| Pad=3 bytes | 00 00 00 |
| Message property, PidTagReceivedByEntryId Number of property values=1 Size of first property=107 | 02 01 3f 00 01 00 00 00 6b 00 00 00 |
| | 00 00 00 00 DC A7 40 C8 C0 42 10 1A B4 B9 08 00 2B 2F E1 82 01 00 00 00 00 00 00 00 2F 4F 3D 46 49 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 49 45 4E 54 53 2F 43 4E 3D 54 45 53 54 32 31 55 57 32 00 |
| Pad=1 byte | 00 |
| Message property, PidTagReceivedByName Number of property values=1 Size of first property=10 | 1e 00 40 00 01 00 00 00 0a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagReceivedRepresentingEntryId Number of property values=1 Size of first property=107 | 02 01 43 00 01 00 00 00 6b 00 00 00 |
| | 00 00 00 00 DC A7 40 C8 C0 42 10 1A B4 B9 08 00 2B 2F E1 82 01 00 00 00 00 00 00 00 2F 4F 3D 46 49 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 49 |

| Explanation of content | Byte Stream |
|---|--|
| | 45 4E 54 53 2F 43 4E3D 54 45 53 54 32 31 55 57 32 00 |
| Pad=1 byte | 00 |
| Message property, PidTagReceivedRepresentingName Number of property values=1 Size of first property=10 | 1e 00 44 0001 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagMessageSubmissionId Number of property values=1 Size of first property=57 | 02 01 47 0001 00 00 0039 00 00 00 |
| | 63 3D 55 53 3B 61 3D 20 3B 70 3D 46 69 72 73 7420 4F 72 67 61 6E 69 7A 61 74 69 3B 6C 3D 4A 4553 45 4F 47 50 55 57 32 2D 30 34 30 32 31 37 3139 32 35 33 35 5A 2D 32 00 |
| Pad=3 bytes | 00 00 00 |
| Message property, PidTagReceivedBySearchKey Number of property values=1 Size of first property=82 | 02 01 51 0001 00 00 0052 00 00 00 |
| | 45 58 3A 2F 4F 3D 46 49 52 53 54 20 4F 52 47 414E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 5354 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 4520 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 4945 4E 54 53 2F 43 4E 3D 54 45 53 54 32 31 55 5732 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagReceivedRepresentingSearchKey Number of property values=1 Size of first property=82 | 02 01 52 0001 00 00 0052 00 00 00 |
| | 45 58 3A 2F 4F 3D 46 49 52 53 54 20 4F 52 47 414E 49 5A 41 54 49 4F 4E 2F 4F 55 3D 46 49 52 5354 20 41 44 4D 49 4E 49 53 54 52 41 54 49 56 4520 47 52 4F 55 50 2F 43 4E 3D 52 45 43 49 50 4945 4E 54 53 2F 43 4E 3D 54 45 53 54 |

| Explanation of content | Byte Stream |
|---|--|
| | 32 31 55 5732 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagMessageToMe Value=1 (TRUE) | 0b 00 00 57 01 00 00 00 |
| Message property, PidTagMessageCcMe Value=0 (FALSE) | 0b 00 00 58 00 00 00 00 |
| Message property, PidTagMessageRecipientMe Value=1 (TRUE) | 0b 00 00 59 01 00 00 00 |
| Message property, PidTagConversationTopic Number of property values=1 Size of first property=15 | 1e 00 70 0001 00 00 00 0f 00 00 00 |
| Value="Simple subject" %x00 | 53 69 6D 70 6C 65 20 73 75 62 6A 65 63 74 00 |
| Pad=1 byte | 00 |
| Message property, PidTagConversationIndex Number of property values=1 Size of first property=22 | 02 01 71 0001 00 00 0016 00 00 00 |
| | 01 C3 F5 8B 07 63 76 8D 89 1B D0 79 47 C9 8F 664E 21 9A D2 4A F2 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagReceivedByAddressType Number of property values=1 Size of first property=5 | 1e 00 75 0001 00 00 0005 00 00 00 |
| Value="SMTP" %x00 | 53 4d 54 50 00 |
| Pad=3 bytes | 00 00 00 |
| Message property, PidTagReceivedByEmailAddress Number of property values=1 Size of first property=40 | 1e 00 76 0001 00 00 0028 00 00 00 |
| Value="Test21uw2@mydomuw2.extest.microsoft.com" %x00 | 54 65 73 74 32 31 75 77 32 40 6D 79 64 6F 6D 7577 32 2E 65 78 74 65 73 74 2E 6D 69 63 72 6F 736F 66 74 2E 63 6F 6D 00 |

| Explanation of content | Byte Stream |
|--|---|
| Message property, PidTagReceivedRepresentingAddressType Number of property values=1 Size of first property=5 | 1e 00 77 0001 00 00 0005 00 00 00 |
| Value="SMTP" %x00 | 53 4d 54 50 00 |
| Pad=3 bytes | 00 00 00 |
| Message property, PidTagReceivedRepresentingEmailAddress Number of property values=1 Size of first property=40 | 1e 00 78 0001 00 00 0028 00 00 00 |
| Value="Test21uw2@mydomuw2.exetest.microsoft.com" %x00 | 54 65 73 74 32 31 75 77 32 40 6D 79 64 6F 6D 7577 32 2E 65 78 74 65 73 74 2E 6D 69 63 72 6F 736F 66 74 2E 63 6F 6D 00 |
| Message property, PidTagSenderName Number of property values=1 Size of first property=10 | 1e 00 1A 0C01 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagNormalizedSubject Number of property values=1 Size of first property=15 | 1e 00 1D 0E01 00 00 000f 00 00 00 |
| Value="Simple subject" %x00 | 53 69 6D 70 6C 65 20 73 75 62 6A 65 63 74 00 |
| Pad=1 byte | 00 |
| Message property, PidTagRtfCompressed Number of property values=1 Size of first property=150 | 02 01 09 1001 00 00 0096 00 00 00 |
| | 92 00 00 00 AB 00 00 00 4C 5A 46 75 A8 14 2F 1703 00 0A 00 72 63 70 67 31 32 35 16 32 00 F8 0B60 6E 0E 10 30 33 33 4F 01 F7 02 A4 03 E3 02 0063 68 0A C0 73 B0 65 74 30 20 07 13 02 80 7D 0A80 9D 00 00 2A 09 B0 09 F0 04 90 61 74 05 B1 1A52 0D E0 68 09 80 01 D0 20 35 2E 30 35 30 2E 3313 B0 01 D0 30 32 49 02 80 5C 76 08 90 77 6B 0B80 64 FA |

| Explanation of content | Byte Stream |
|--|---|
| | 34 0C 60 63 00 50 0B 03 0B B5 06 00 0770 C9 0B 50 65 20 07 81 73 61 12 50 0A A2 0B 0A80 11 E1 00 17 A0 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagInternetMessageId Number of property values=1 Size of first property=80 | 1e 00 35 1001 00 00 0050 00 00 00 |
| Value="<2896107D7E52DF4DB5D10536D BFEFAD07E37@jeseogpuw2.mydomuw2. extest.microsoft.com>" %x00 | 3C 32 38 39 36 31 30 37 44 37 45 35 32 44 46 3444 42 35 44 31 30 35 33 36 44 42 46 45 46 41 4430 37 45 33 37 40 6A 65 73 65 6F 67 70 75 77 322E 6D 79 64 6F 6D 75 77 32 2E 65 78 74 65 73 742E 6D 69 63 72 6F 73 6F 66 74 2E 63 6F 6D 3E 00 |
| Message property, PidTagIconIndex Value=0xFFFFFFFF | 03 00 80 10ff ff ff ff |
| Message property, PidTagImapCachedMsgsize Number of property values=1 Size of first property=40 | 02 01 f0 1001 00 00 0028 00 00 00 |
| | 03 00 00 00 01 00 00 00 01 00 00 00 01 00 00 0001 00 00 00 08 00 00 00 DB 11 00 00 49 53 4F 2D38 38 35 39 2D 31 00 00 |
| Message property, PidTagUrlCompName Number of property values=1 Size of first property=38 | 1f 00 f3 1001 00 00 0026 00 00 00 |
| Value="Simple subject.EML" %x00.00 (Unicode) | 53 00 69 00 6D 00 70 00 6C 00 65 00 20 00 73 0075 00 62 00 6A 00 65 00 63 00 74 00 2E 00 45 004D 00 4C 00 00 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagAttributeHidden Value=0 (FALSE) | 0b 00 f4 1000 00 00 00 |
| Message property, PidTagAttributeSystem Value=0 (FALSE) | 0b 00 f5 1000 00 00 00 |
| Message property, PidTagAttributeReadOnly Value=0 (FALSE) | 0b 00 f6 1000 00 00 00 |
| Message property, PidTagCreationTime Value=Tuesday, 02/17/2004, 20:26:09 | 40 00 07 3090 24 46 47 94 f5 c3 01 |

| Explanation of content | Byte Stream |
|---|--|
| Message property, PidTagLastModificationTime Value=Tuesday, 02/17/2004, 20:26:09 | 40 00 08 3090 24 46 47 94 f5 c3 01 |
| Message property, PidTagInternetCodepage Value=(Primary=1252, Secondary=0) | 03 00 de 3fe4 04 00 00 |
| Message property, PidTagMessageLocaleId Value=(Primary=1033, Secondary=0) | 03 00 f1 3f09 04 00 00 |
| Message property, PidTagCreatorName Number of property values=1 Size of first property=10 | 1e 00 f8 3f01 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagCreatorEntryId Number of property values=1 Size of first property=107 | 02 01 f9 3f01 00 00 006b 00 00 00 |
| | 00 00 00 00 DC A7 40 C8 C0 42 10 1A B4 B9 08 002B 2F E1 82 01 00 00 00 00 00 00 00 2F 4F 3D 4649 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 4E49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F43 4E 3D 52 45 43 49 50 49 45 4E 54 53 2F 43 4E3D 54 45 53 54 32 31 55 57 32 00 |
| Pad=1 byte | 00 |
| Message property, PidTagLastModifierName Number of property values=1 Size of first property=10 | 1e 00 fa 3f01 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagLastModifierEntryId Number of property values=1 Size of first property=107 | 02 01 FB 3f01 00 00 006b 00 00 00 |
| | 00 00 00 00 DC A7 40 C8 C0 42 10 1A B4 B9 08 002B 2F E1 82 01 00 00 00 00 00 00 00 2F 4F 3D 4649 52 53 54 20 4F 52 47 41 4E 49 5A 41 54 49 4F4E 2F 4F 55 3D 46 49 52 53 54 20 41 44 4D 49 |

| Explanation of content | Byte Stream |
|--|---|
| | 4E49 53 54 52 41 54 49 56 45 20 47 52 4F 55 50 2F43 4E 3D 52 45 43 49 50 49 45 4E 54 53 2F 43 4E3D 54 45 53 54 32 31 55 57 32 00 |
| Pad=1 byte | 00 |
| Message property, PidTagMessageCodepage Value=(Primary=1252, Secondary=0) | 03 00 fd 3fe4 04 00 00 |
| Message property, PidTagSenderFlags Value=0 | 03 00 19 4000 00 00 00 |
| Message property, PidTagSentRepresentingFlags Value=0 | 03 00 1A 4000 00 00 00 |
| Message property, PidTagReceivedByFlags Value=0 | 03 00 1B 4000 00 00 00 |
| Message property, PidTagReceivedRepresentingFlags Value=0 | 03 00 1C 4000 00 00 00 |
| Message property, PidTagSenderSimpleDisplayName Number of property values=1 Size of first property=10 | 1e 00 30 4001 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagSentRepresentingSimpleDisplayName Number of property values=1 Size of first property=10 | 1e 00 31 4001 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagReceivedRepresentingSimpleDisplayName Number of property values=1 Size of first property=10 | 1e 00 34 4001 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |

| Explanation of content | Byte Stream |
|---|---|
| Message property, PidTagReceivedRepresentingSimpleDisplayName Number of property values=1 Size of first property=10 | 1e 00 35 4001 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagCreatorSimpleDisplayName Number of property values=1 Size of first property=10 | 1e 00 38 4001 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagLastModifierSimpleDisplayName Number of property values=1 Size of first property=10 | 1e 00 39 4001 00 00 000a 00 00 00 |
| Value="Test21uw2" %x00 | 54 65 73 74 32 31 75 77 32 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagContentFilterSpamConfidenceLevel Value=0xFFFFFFFF | 03 00 76 40ff ff ff ff |
| Message property, PidTagMessageEditorFormat Value=0x00000003 | 03 00 09 5903 00 00 00 |
| Message property, PidTagTnefCorrelationKey Number of property values=1 Size of first property=12 | 02 01 7f 0001 00 00 000c 00 00 00 |
| | 38 71 6b 6a 30 30 73 67 6d 34 66 00 |
| Message property, PidLidAqingDontAgeMe PSETID_Common, MNID_ID, Id=0x850E Value=0 | 0b 00 87 8108 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 4600 00 00 000e 85 00 0000 00 00 00 |
| Message property, PidLidCurrentVersion PSETID_Common, MNID_ID, Id=0x8552 | 03 00 9f 8108 20 06 00 00 00 00 00 c0 00 00 00 00 00 00 4600 00 00 0052 85 00 0098 c3 01 00 |

| Explanation of content | Byte Stream |
|--|---|
| Value=115608 | |
| Message property, PidLidCurrentVersionName PSETID_Common, MNID_ID, Id=0x8554 Number of property values=1 Size of first property=5 | 1E 00 A0 8108 20 06 00 00 00 00 00 00 c0 00 00 00 00 00 00 4600 00 00 0054 85 00 0001 00 00 0005 00 00 00 |
| Value="11.0" %x00 | 31 31 2E 30 00 |
| Pad=3 bytes | 00 00 00 |
| Message property, PidLidReminderDelta PSETID_Common, MNID_ID, Id=0x8501 Value=0 | 03 00 eb 8108 20 06 00 00 00 00 00 00 c0 00 00 00 00 00 00 4600 00 00 0001 85 00 0000 00 00 00 |
| Message property, PidLidReminderSet PSETID_Common, MNID_ID, Id=0x8503 Value=0 (FALSE) | 0b 00 f0 8108 20 06 00 00 00 00 00 00 c0 00 00 00 00 00 00 4600 00 00 0003 85 00 0000 00 00 00 |
| Message property, PidLidSideEffects PSETID_Common, MNID_ID, Id=0x8510 Value=0 | 03 00 fa 8108 20 06 00 00 00 00 00 00 c0 00 00 00 00 00 00 4600 00 00 0010 85 00 0000 00 00 00 |
| Message property, PidLidTaskMode PSETID_Common, MNID_ID, Id=0x8518 Value=0 | 03 00 01 8208 20 06 00 00 00 00 00 00 c0 00 00 00 00 00 00 4600 00 00 0018 85 00 0000 00 00 00 |
| Message property, PidLidPrivate PSETID_Common, MNID_ID, Id=0x8506 Value=0 (FALSE) | 0b 00 43 8208 20 06 00 00 00 00 00 00 c0 00 00 00 00 00 00 4600 00 00 0006 85 00 0000 00 00 00 |
| Message property, PidLidUseTnef PSETID_Common, MNID_ID, Id=0x8582 Value=0 (FALSE) | 0b 00 44 8208 20 06 00 00 00 00 00 00 c0 00 00 00 00 00 00 4600 00 00 0082 85 00 0000 00 00 00 |
| Message property, PidTagReadReceiptRequested Value=0 (FALSE) | 0b 00 29 0000 00 00 00 |
| Message property, PidTagOriginatorDeliveryReportRequested Value=0 (FALSE) | 0b 00 23 0000 00 00 00 |

| Explanation of content | Byte Stream |
|---|--|
| Message property, PidTagRtfSyncBodyCrc Value=0xF00D29FF | 03 00 06 10ff 29 0d f0 |
| Message property, PidTagRtfSyncBodyCount Value=13 | 03 00 07 100d 00 00 00 |
| Message property, PidTagRtfSyncPrefixCount Value=0 | 03 00 10 1000 00 00 00 |
| Message property, PidTagRtfSyncTrailingCount Value=0 | 03 00 11 1000 00 00 00 |
| Message property, PidTagRtfSyncBodyTag Number of property values=1 Size of first property=14 | 1e 00 08 1001 00 00 000e 00 00 00 |
| Value="SIMPLEMESSAGE" %x00 | 53 49 4d 50 4c 45 4d 45 53 53 41 47 45 00 |
| Pad=2 bytes | 00 00 |
| Message property, PidTagTnefCorrelationKey Number of property values=1 Size of first property=56 | 02 01 7f 0001 00 00 0038 00 00 00 |
| | 3C 32 38 39 36 31 30 37 44 37 45 35 32 44 46 3444 42 35 44 31 30 35 33 36 44 42 46 45 46 41 4430 37 45 33 37 40 75 73 65 72 2E 65 78 61 6D 706C 65 2E 63 6F 6D 3E 00 |
| Checksum for AttMsgProps | 45 C1 |

3.2 Sample Meeting Response

This example is particularly short, as it was sent by a mobile application.

| Explanation of content | Byte stream |
|---|---------------------------|
| TNEF Signature , Value=0x223E9F78 | 78 9f 3e 22 |
| Attach Key , Value=0x0001 | 01 00 |
| Message attribute , attTnefVersion Length=4 bytes | 01 06 90 08 0004 00 00 00 |
| Data=0x00010000 | 00 00 01 00 |

| Explanation of content | Byte stream |
|---|---|
| Checksum=0x0001 | 01 00 |
| Message attribute, attOemCodepage Length=8 bytes | 01 07 90 06 0008 00 00 00 |
| Data= (Primary=1252, Secondary=0) | e4 04 00 00 00 00 00 00 |
| Checksum=0x00E8 | e8 00 |
| Message attribute, attMessageClass Length=32 bytes | 01 08 80 07 0020 00 00 00 |
| Data="IPM.Microsoft Schedule.MtgRespN" %x00 | 49 50 4d 2e 4d 69 63 72 6f 73 6f 66 74 20 53 6368 65 64 75 6c 65 2e 4d 74 67 52 65 73 70 4e 00 |
| Checksum=0x0B55 | 55 0b |
| Message attribute, attPriority Length=2 bytes | 01 0d 80 04 0002 00 00 00 |
| Data=0x0002 (Normal Priority) | 02 00 |
| Checksum=0x0002 | 02 00 |
| Message attribute, attDateSent Length=14 bytes | 01 05 80 03 000e 00 00 00 |
| Data= Wednesday, 01/16/2008, 23:28:08 | d8 07 01 00 10 00 17 00 1c 00 08 00 03 00 |
| Checksum=0x012E | 2e 01 |
| Message attribute, attDateModified Length=14 bytes | 01 20 80 03 000e 00 00 00 |
| Data= Wednesday, 01/16/2008, 23:28:08 | d8 07 01 00 10 00 17 00 1c 00 08 00 03 00 |
| Checksum=0x012E | 2e 01 |
| Message attribute Encapsulation, attMsgProps Length=136 bytes | 01 03 90 06 0088 00 00 0002 00 00 00 |

| Explanation of content | Byte stream |
|--|---|
| Number of properties=2 | |
| Message property, PidTagTnefCorrelationKey Number of property values=1 Size of first property=12 | 02 01 7f 0001 00 00 000c 00 00 00 |
| | 38 71 6b 6a 30 30 73 67 6d 34 66 00 |
| Message property, PidTagRtfCompressed Number of property values=1 Size of first property=93 | 02 01 09 1001 00 00 005d 00 00 00 |
| | 59 00 00 00 b3 00 00 00 4c 5a 46 75 a9 be bb ed87 00 0a 01 0d 03 43 74 65 78 74 01 f7 ff 02 a403 e4 05 eb 02 83 00 50 02 f3 06 b4 02 83 26 3203 c5 02 00 63 68 0a c0 73 65 d8 74 30 20 07 1302 80 7d 0a 80 08 cf 3f 09 d9 02 80 0a 84 0b 3712 c2 01 d0 20 46 10 59 49 00 7d 18 20 |
| Pad=3 bytes | 00 00 00 |
| Checksum for attMsgProps | f7 21 |

4 Security

4.1 Security Considerations for Implementers

Extreme care is recommended in the use of the **attRecipTable** attribute and the **attFrom** attribute, particularly by the TNEF Reader, to avoid address or identity spoofing. More information about this can be found in [\[MS-OXCMSG\]](#) and section [5.2](#) of this specification.

4.2 Index of Security Fields

None.

5 Other Compatibility Issues

The preceding sections addressed issues of compatibility between the original implementation of TNEF and the richer implementation that is now used. This section discusses some compatibility issues within the richer implementation.

5.1 attOemCodepage Handling

Attribute **attOemCodepage** has been handled inconsistently between multiple implementations of TNEF. This can be particularly troublesome when forwarding messages with attached messages between systems that have different default code pages. To minimize problems caused by this inconsistent behavior, the following sections describe the recommended way to handle string encoding. <4>

5.1.1 Encoding by TNEF Writer

The TNEF Writer writes all ANSI strings, both the attribute strings and the encapsulated message property strings, with a consistent ANSI code page and put its value into **attOemCodepage**. Choose a code page that does not allow embedded zero bytes other than the zero terminator.

If [PidTagInternetCodepage](#) is being stored in the encapsulated properties, set it to a value that maps to the same language group or language as the code page chosen for **attOemCodepage**. This code page also determines the character set used in MIME if this TNEF is transmitted as a MIME entity body.

Do not write to an attribute any string that would suffer data loss if written using the consistent code page. Write to encapsulated properties with a Unicode data type all strings that would suffer data loss when using the consistent code page.

For compatibility purposes, **attMessageClass** always writes using the consistent code page.

5.1.2 Decoding by TNEF Reader

For ANSI string decoding from the TNEF structure, the TNEF Reader uses the code page determined from the best of the following sources, listed in decreasing order of trustworthiness:

1. Any non-US-ASCII MIME character set, if the structure was transmitted as a MIME body part and character set name is available in the MIME, mapped to the most appropriate code page that does not allow embedded zero bytes other than a zero terminator.
2. **attOemCodepage**, if available and nonzero.
3. [PidTagInternetCodepage](#), if available in the encapsulated properties, mapped to the most appropriate code page that does not allow embedded zero bytes other than a zero terminator.
4. The most appropriate default code page for the processing environment.

5.2 TNEF Encapsulation vs. Outer Wrapper Attributes

It is possible to encapsulate properties in the TNEF structure that represents data that is already conveyed as part of an outer wrapper such as MIME. Because in many cases the outer wrapper properties are subject to substantial validation during transport (reverse DNS lookups and other validation), they are considered more trustworthy than information inside an attached file that otherwise could overwrite good information with bad.

As a general rule, TNEF Writers do not duplicate any data that is already being reliably transported outside the structure and TNEF Readers do not override data from outside the structure with data from inside the structure. The individual implementations will determine how this rule is applied. For more details, see [\[MS-OXCMAIL\]](#). Some highlights of this behavior are described in the following sections.

5.2.1 attBody Handling

When TNEF is being sent as a MIME body part, the **attBody** attribute is not written to TNEF or read from TNEF either by the client or server. The plain text body is instead transmitted in a MIME body part. When TNEF is being used to encode an attached message, **attBody** MAY [<5>](#) be written and read. See [\[MS-OXCMAIL\]](#) for a more detailed description.

5.2.2 attRecipTable Handling

When TNEF is being sent as a MIME body part, the **attRecipTable** attribute is not written to TNEF or read from TNEF either by the client or server, except when sending or receiving a legacy [non]delivery report message (**attMessageClass** beginning with "REPORT." and ending in ".DR" or ".NDR"). The requisite message recipient information is transmitted in the MIME structure instead.

When TNEF is being sent as a MIME body part, when sending or receiving a legacy [non]delivery report message (**attMessageClass** beginning with "REPORT." and ending in ".DR" or ".NDR"), recipient information from **attRecipTable** is used to populate the received message recipient table.

When TNEF is being used to encode an attached message, recipient information from **attRecipTable** is used to populate the received message recipient table.

5.2.3 attFrom Handling

The **attFrom** attribute is not written to TNEF or read from TNEF either by the client or the server for MIME messages. The requisite message recipient information is transmitted in the MIME structure instead. When TNEF is being used to encode an attached message, the sender information is carried in encapsulated message properties in **attMsgProps**.

5.2.4 attSubject Handling

The **attSubject** attribute, if present for a MIME message, is overwritten by the subject value in the MIME structure. When TNEF is being used to encode an attached message, the message subject information is carried in encapsulated message properties in **attMagProps**. When the TNEF structure is being decoded, and **attSubject** is present, it is used for the message if there is no MIME structure, if a MIME subject is not available, or if an attached message is being decoded.

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products:

- Microsoft® Office Outlook® 2003
- Microsoft® Exchange Server 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Exchange Server 2007
- Microsoft® Outlook® 2010
- Microsoft® Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

[<1> Section 2.3.3:](#) Office Outlook 2003 and Exchange 2003 allocate and zero-fill an extra 8-byte structure after the sender-e-mail field.

[<2> Section 2.3.15:](#) In Exchange 2007 and Exchange 2010, the **TNEF Writer** always sets the **DataFlags** field to FileDataDefault, regardless of the attachment's [PidTagAttachEncoding](#) ([\[MS-OXPROPS\]](#) section 2.657) value.

[<3> Section 2.3.18:](#) Exchange 2007 and Exchange 2010 do not support the use of attDelegate.

[<4> Section 5.1:](#) The Exchange 2003 implementation of TNEF would use the MIME character set to determine its mapping of strings in the attributes and of ANSI strings in the encapsulated properties, regardless of the value of **attOemCodePage**. This can cause some confusion, but if they follow the rules in section 5 for reading and writing TNEF, other implementations are not likely to have any significant interoperability issues.

[<5> Section 5.2.1:](#) In Exchange 2003, the TNEF Writer writes **attBody** when TNEF is used to encode an attached message. In Exchange 2007 and Exchange 2010, the TNEF Writer does not write **attBody** when TNEF is used to encode an attached message.

7 Change Tracking

This section identifies changes that were made to the [MS-OXTNEF] protocol document between the August 2010 and November 2010 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- Changes made for template compliance.
- Removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type "Editorially updated."

Some important terms used in revision type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

| Section | Tracking number (if applicable) and description | Major change (Y or N) | Change Type |
|--|--|-----------------------|--------------------|
| 1 Introduction | 57502 Revised to state that this document specifies a data structure. | N | Content updated. |
| 1.1 Glossary | 48227 Specified the numbered definition that corresponds to the terms "property" and "recipient". | N | Content updated. |
| 1.1 Glossary | 57519 Specified the numbered definition that corresponds to the term "code page". | N | Content updated. |
| 1.1 Glossary | 48510 Removed the term "metafile" from the list of terms that are defined in [MS-OXGLOS]. | N | Content updated. |
| 1.1 Glossary | 55511 Added the terms "Internet Message Access Protocol (IMAP)", "Post Office Protocol - Version 3 (POP3)", and "Simple Mail Transfer Protocol (SMTP)" to the list of terms defined in [MS-OXGLOS]. | N | New content added. |
| 1.1 Glossary | 48810 Updated the definition for terms "CLSID" and "Interface Identifier (IID)". | N | Content updated. |
| 1.2.1 Normative References | 48809 Removed [RFC4234] from and added [RFC5234] to list of references. | N | Content updated. |

| Section | Tracking number (if applicable) and description | Major change (Y or N) | Change Type |
|--|--|------------------------------|--------------------|
| 1.2.1 Normative References | 58904 Added references [MS-DTYP] and [MS-OXCPRPT]. | N | Content updated. |
| 1.2.2 Informative References | 48811 Added reference [MSDN-UAF]. | N | Content updated. |
| 1.4 Relationship to Protocols and Other Structures | 48809 Replaced [RFC4234] reference with [RFC5234] reference. | N | Content updated. |
| 1.4 Relationship to Protocols and Other Structures | 48811 Added reference to [MSDN-UAF]. | N | Content updated. |
| 1.5 Applicability Statement | 48812 Moved information about the meaning of "attributes" and "properties" to Structures section. | N | Content updated. |
| 1.7 Vendor-Extensible Fields | 48232 Added section. | N | New content added. |
| 2 Structures | 48790 Added information about how each attribute is laid out. | N | Content updated. |
| 2 Structures | 48812 Added information about the meaning of "attributes" and "properties". | N | Content updated. |
| 2 Structures | 57545 Clarified information about the sequencing of attributes. | N | Content updated. |
| 2.1 Conventions | 48240 Changed section title from "Additional Terms Used in This Document" to "Conventions" and added description of section contents. | N | Content updated. |
| 2.1.2 ABNF Rules | 48240 Added section. | N | New content added. |
| 2.2 ABNF Description | 48814 Added section reference to comments for idAttachRendData. | N | Content updated. |
| 2.2 ABNF Description | 57609 Changed "PidTagSentRepresentingEmailAddress" to "PidTagSentRepresenting_XXX" in the comment for idSentFor. | N | Content updated. |
| 2.2 | 57608 | N | Content |

| Section | Tracking number (if applicable) and description | Major change (Y or N) | Change Type |
|--|--|-----------------------|--------------------|
| ABNF Description | Changed "PidTagReceivedRepresentingEmailAddress or PidTagSentRepresentingEmailAddress" to "PidTagReceivedRepresenting_XXX or PidTagSentRepresenting_XXX" in the comment for idOwner. | | updated. |
| 2.2 ABNF Description | 57607 Changed "PidTagSenderEntryId" to "PidTagSender_XXX" in the comment for idFrom. | N | Content updated. |
| 2.2 ABNF Description | 57515 Changed "PidTagReceivedRepresentingEmailAddress" to "PidTagReceivedRepresentingEntryId" in the comment for idDelegate. | N | Content updated. |
| 2.2 ABNF Description | 57532 Specified the meaning of "8-bit code page" in the comment for OEMCodePageData. | N | Content updated. |
| 2.3.3 attFrom | 57492 Changed the description of the "sender-name-length" field. | N | Content updated. |
| 2.3.3 attFrom | 48794 Updated document reference for PidTagSenderEntryId. | N | Content updated. |
| 2.3.5 Message Class Attributes | 48819 Clarified how the TNEF Reader maps the attMessageClass value to a message property value. | N | Content updated. |
| 2.3.6 Conversation-Tracking Attribute | 48821 Clarified how the attribute is stored. | N | Content updated. |
| 2.3.8 attMessageStatus | 57533 Updated information about how the state of each attribute flag corresponds to the state of the related message property flag. | N | Content updated. |
| 2.3.15 attAttachRendData | 48820 Clarified how the TNEF Writer sets RenderWidth and RenderHeight. | N | New content added. |
| 2.4 Encapsulated Message and Attachment Properties | 57546 Added mention of attachment properties to the section title and introductory text. | N | Content updated. |
| 2.4 Encapsulated Message and Attachment Properties | 48797 Added normative language to comment for NamedPropSpec. | N | Content updated. |

| Section | Tracking number (if applicable) and description | Major change (Y or N) | Change Type |
|--|--|------------------------------|--------------------|
| 2.4 Encapsulated Message and Attachment Properties | 48801 Clarified the meaning of "embedded TNEF stream" in the comments. | N | Content updated. |
| 2.4 Encapsulated Message and Attachment Properties | 57610 Clarified the meaning of "length" in the comments about PropMapString. | N | Content updated. |
| 2.4 Encapsulated Message and Attachment Properties | 57547 Removed "1*" in value of MsgPropertyList. | N | Content updated. |
| 2.4 Encapsulated Message and Attachment Properties | 48825 Updated introductory text to list the attributes that are specified in this section. | N | Content updated. |
| 2.4 Encapsulated Message and Attachment Properties | 48798 Removed the comments for TypeUnspecified, TypeNull, and TypeError. | N | Content updated. |
| 2.4 Encapsulated Message and Attachment Properties | 48800 Updated the comments for PropertyVariableContent. | N | Content updated. |
| 3.1 Sample Message | 57530 Clarified explanation of content for byte stream "00 00 01 00". | N | Content updated. |
| 3.2 Sample Meeting Response | 57503 Clarified explanation of content for byte stream "00 00 01 00". | N | Content updated. |
| 4 Security | 57531 Changed the section title from "Security Considerations" to "Security". | N | Content updated. |
| 4.1 Security Considerations for Implementers | 57531 Updated section title and revised section contents to include explicit mention of the attRecipTable and attFrom attributes. | N | Content updated. |
| 4.2 Index of Security | 57531 | N | New content |

| Section | Tracking number (if applicable) and description | Major change (Y or N) | Change Type |
|------------------------|---|-----------------------|-------------|
| Fields | Added section. | | added. |

8 Index

A

[Vendor-extensible fields](#) 7

[Applicability](#) 7

C

[Change tracking](#) 42

[Common data types and fields](#) 8

D

[Data types and fields - common](#) 8

Details

[common data types and fields](#) 8

F

[Fields - vendor-extensible](#) 7

G

[Glossary](#) 5

I

[Informative references](#) 6

[Introduction](#) 5

N

[Normative references](#) 5

O

[Overview \(synopsis\)](#) 6

P

[Product behavior](#) 41

R

References

[informative](#) 6

[normative](#) 5

[Relationship to protocols and other structures](#) 6

S

Structures

[overview](#) 8

T

[Tracking changes](#) 42

V