

# [MS-OXTNEF]: Transport Neutral Encapsulation Format (TNEF) Data Algorithm

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

| Date       | Revision History | Revision Class | Comments  |
|------------|------------------|----------------|---|
| 04/04/2008 | 0.1              |                | Initial Availability.   |
| 04/25/2008 | 0.2              |                | Revised and updated property names and other technical content.               |
| 06/27/2008 | 1.0              |                | Initial Release.  |
| 08/06/2008 | 1.01             |                | Revised and edited technical content.   |
| 09/03/2008 | 1.02             |                | Revised and edited technical content.   |
| 12/03/2008 | 1.03             |                | Revised and edited technical content.   |
| 03/04/2009 | 1.04             |                | Revised and edited technical content.   |
| 04/10/2009 | 2.0              |                | Updated technical content and applicable product releases.                    |
| 07/15/2009 | 3.0              | Major          | Revised and edited for technical content.                                     |
| 11/04/2009 | 3.1.0            | Minor          | Updated the technical content.  |
| 02/10/2010 | 4.0.0            | Major          | Updated and revised the technical content.                                    |
| 05/05/2010 | 5.0.0            | Major          | Updated and revised the technical content.                                    |
| 08/04/2010 | 5.1              | Minor          | Clarified the meaning of the technical content.                               |
| 11/03/2010 | 5.2              | Minor          | Clarified the meaning of the technical content.                               |
| 03/18/2011 | 5.2              | No change      | No changes to the meaning, language, and formatting of the technical content. |
| 08/05/2011 | 5.2              | No change      | No changes to the meaning, language, or formatting of the technical content.  |
| 10/07/2011 | 6.0              | Major          | Significantly changed the technical content.                                  |
| 01/20/2012 | 7.0              | Major          | Significantly changed the technical content.                                  |
| 04/27/2012 | 7.1              | Minor          | Clarified the meaning of the technical content.                               |
| 07/16/2012 | 7.1              | No change      | No changes to the meaning, language, or formatting of the technical content.  |
| 10/08/2012 | 8.0              | Major          | Significantly changed the technical content.                                  |
| 02/11/2013 | 8.0              | No change      | No changes to the meaning, language, or formatting of the technical content.  |
| 07/26/2013 | 8.1              | Minor          | Clarified the meaning of the technical content.                               |

# Table of Contents

|  |          |
|--|----------|
| <b>1 Introduction</b>  | <b>5</b> |
| 1.1 Glossary   | 5        |
| 1.2 References   | 5        |
| 1.2.1 Normative References                                   | 6        |
| 1.2.2 Informative References                                 | 6        |
| 1.3 Overview   | 7        |
| 1.4 Relationship to Protocols and Other Algorithms           | 7        |
| 1.5 Applicability Statement                                  | 7        |
| 1.6 Standards Assignments                                    | 7        |
| <b>2 Algorithm Details</b>                                   | <b>8</b> |
| 2.1 Common Algorithm Details                                 | 8        |
| 2.1.1 Abstract Data Model                                    | 8        |
| 2.1.2 Initialization   | 8        |
| 2.1.3 Processing Rules                                       | 8        |
| 2.1.3.1 Conventions  | 9        |
| 2.1.3.1.1 Address Representations                            | 9        |
| 2.1.3.1.2 ABNF Rules   | 9        |
| 2.1.3.2 ABNF Description                                     | 9        |
| 2.1.3.3 Attributes   | 12       |
| 2.1.3.3.1 attTnefVersion Attribute                           | 12       |
| 2.1.3.3.2 attOemCodepage Attribute                           | 13       |
| 2.1.3.3.3 attFrom Attribute                                  | 13       |
| 2.1.3.3.4 Date Attributes                                    | 14       |
| 2.1.3.3.5 Message Class Attributes                           | 14       |
| 2.1.3.3.6 attMessageID Attribute                             | 14       |
| 2.1.3.3.7 attSubject Attribute                               | 15       |
| 2.1.3.3.8 attMessageStatus Attribute                         | 15       |
| 2.1.3.3.9 attBody Attribute                                  | 15       |
| 2.1.3.3.10 attPriority Attribute                             | 15       |
| 2.1.3.3.11 attAttachData Attribute                           | 16       |
| 2.1.3.3.12 attAttachTitle Attribute                          | 16       |
| 2.1.3.3.13 attAttachMetaFile Attribute                       | 16       |
| 2.1.3.3.14 attAttachTransportFilename Attribute              | 16       |
| 2.1.3.3.15 attAttachRendData Attribute                       | 16       |
| 2.1.3.3.16 attOwner Attribute                                | 17       |
| 2.1.3.3.17 attSentFor Attribute                              | 17       |
| 2.1.3.3.18 attDelegate Attribute                             | 17       |
| 2.1.3.3.19 attAidOwner Attribute                             | 18       |
| 2.1.3.3.20 attRequestRes Attribute                           | 18       |
| 2.1.3.3.21 attMsgProps Attribute                             | 18       |
| 2.1.3.3.22 attRecipTable Attribute                           | 18       |
| 2.1.3.3.23 attAttachment Attribute                           | 18       |
| 2.1.3.4 Encapsulated Message and Attachment Properties       | 18       |
| 2.1.3.5 Other Compatibility Issues                           | 22       |
| 2.1.3.5.1 attOemCodepage Attribute Handling                  | 22       |
| 2.1.3.5.2 TNEF Encapsulation Versus Outer Wrapper Attributes | 22       |
| 2.1.3.5.2.1 attBody Attribute Handling                       | 22       |
| 2.1.3.5.2.2 attRecipTable Attribute Handling                 | 23       |
| 2.1.3.5.2.3 attFrom Attribute Handling                       | 23       |

|             |   |           |
|-------------|---|-----------|
| 2.1.3.5.2.4 | attSubject Attribute Handling .....                           | 23        |
| 2.2         | TNEF Writer Algorithm Details .....                           | 23        |
| 2.2.1       | Abstract Data Model .....                                     | 23        |
| 2.2.2       | Initialization .....  | 23        |
| 2.2.3       | Processing Rules .....  | 23        |
| 2.2.3.1     | attTnefVersion Attribute Handling by the TNEF Writer.....     | 23        |
| 2.2.3.2     | attOemCodepage Attribute Handling by TNEF Writer .....        | 24        |
| 2.2.3.3     | attFrom Attribute Handling by the TNEF Writer .....           | 24        |
| 2.2.3.4     | Message Class Attribute Handling by the TNEF Writer.....      | 24        |
| 2.2.3.5     | attSubject Attribute Handling by the TNEF Writer .....        | 25        |
| 2.2.3.6     | attBody Attribute Handling by the TNEF Writer .....           | 25        |
| 2.2.3.7     | attMessageID Attribute Handling by the TNEF Writer.....       | 25        |
| 2.2.3.8     | attAttachData Attribute Handling by the TNEF Writer.....      | 25        |
| 2.2.3.9     | attAttachTitle Attribute Handling by the TNEF Writer .....    | 25        |
| 2.2.3.10    | attAttachRendData Attribute Handling by the TNEF Writer.....  | 25        |
| 2.2.3.11    | attOwner Attribute Handling by the TNEF Writer .....          | 26        |
| 2.2.3.12    | attSentFor Attribute Handling by the TNEF Writer .....        | 26        |
| 2.2.3.13    | attDelegate Attribute Handling by the TNEF Writer .....       | 26        |
| 2.2.3.14    | attMsgProps Attribute Handling by the TNEF Writer .....       | 26        |
| 2.2.3.15    | attAttachment Attribute Handling by the TNEF Writer .....     | 26        |
| 2.2.3.16    | attRecipTable Attribute Handling by the TNEF Writer .....     | 26        |
| 2.3         | TNEF Reader Algorithm Details .....                           | 26        |
| 2.3.1       | Abstract Data Model .....                                     | 27        |
| 2.3.2       | Initialization .....  | 27        |
| 2.3.3       | Processing Rules .....  | 27        |
| 2.3.3.1     | attTnefVersion Attribute Handling by the TNEF Reader .....    | 27        |
| 2.3.3.2     | attOemCodepage Attribute Handling by the TNEF Reader .....    | 27        |
| 2.3.3.3     | attFrom Attribute Handling by the TNEF Reader.....            | 27        |
| 2.3.3.4     | attMessageClass Attribute Handling by the TNEF Reader.....    | 27        |
| 2.3.3.5     | attMessageID Attribute Handling by the TNEF Reader.....       | 28        |
| 2.3.3.6     | attSubject Attribute Handling by the TNEF Reader .....        | 28        |
| 2.3.3.7     | attAttachData Attribute Handling by the TNEF Reader .....     | 28        |
| 2.3.3.8     | attAttachTitle Attribute Handling by the TNEF Reader .....    | 28        |
| 2.3.3.9     | attAttachRendData Attribute Handling by the TNEF Reader ..... | 28        |
| 2.3.3.10    | attOwner Attribute Handling by the TNEF Reader .....          | 29        |
| 2.3.3.11    | attSentFor Attribute Handling by the TNEF Reader .....        | 29        |
| 2.3.3.12    | attDelegate Attribute Handling by the TNEF Reader.....        | 29        |
| <b>3</b>    | <b>Algorithm Examples .....</b>                               | <b>30</b> |
| 3.1         | Sample Message.....   | 30        |
| 3.2         | Sample Meeting Response .....                                 | 42        |
| <b>4</b>    | <b>Security.....</b>  | <b>45</b> |
| 4.1         | Security Considerations for Implementers.....                 | 45        |
| 4.2         | Index of Security Parameters .....                            | 45        |
| <b>5</b>    | <b>Appendix A: Product Behavior .....</b>                     | <b>46</b> |
| <b>6</b>    | <b>Change Tracking.....</b>                                   | <b>47</b> |
| <b>7</b>    | <b>Index .....</b>  | <b>49</b> |

# 1 Introduction

The Transport Neutral Encapsulation Format (TNEF) Data Algorithm enables the encoding of rich properties in electronic mail messages over a serial data stream. The result can be transported as a stream, as a file attachment in an arbitrary transport, or as a **MIME** entity body on an Internet transport.

Section 2 of this specification is normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Section 1.6 is also normative but cannot contain those terms. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**Augmented Backus-Naur Form (ABNF)**  
**code page**  
**little-endian**  
**Unicode**

The following terms are defined in [\[MS-OXGLOS\]](#):

**binary large object (BLOB)**  
**body part**  
**character set**  
**display name**  
**EntryID**  
**Internet Message Access Protocol - Version 4 (IMAP4)**  
**message class**  
**Message object**  
**Multipurpose Internet Mail Extensions (MIME)**  
**named property**  
**non-delivery report**  
**plain text message body**  
**Post Office Protocol - Version 3 (POP3)**  
**recipient**  
**Simple Mail Transfer Protocol (SMTP)**  
**Transport Neutral Encapsulation Format (TNEF)**  
**Transport Neutral Encapsulation Format (TNEF) Reader**  
**Transport Neutral Encapsulation Format (TNEF) Writer**

The following terms are specific to this document:

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.

## 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)".

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCMAIL] Microsoft Corporation, "[RFC 2822 and MIME to Email Object Conversion Algorithm](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol](#)".

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol](#)".

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol](#)".

[MS-OXOMSG] Microsoft Corporation, "[Email Object Protocol](#)".

[MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

## 1.2.2 Informative References

[MSDN-UAF] Microsoft Corporation, "UUENCODE Attachment Format", [http://msdn.microsoft.com/en-us/library/aa579638\(v=EXCHG.80\).aspx](http://msdn.microsoft.com/en-us/library/aa579638(v=EXCHG.80).aspx)

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXCFCOLD] Microsoft Corporation, "[Folder Object Protocol](#)".

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXORMDR] Microsoft Corporation, "[Reminder Settings Protocol](#)".

[MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[MS-WMF] Microsoft Corporation, "[Windows Metafile Format](#)".

[RFC2045] Freed, N., and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", RFC 2045, November 1996, <http://ietf.org/rfc/rfc2045.txt>

### 1.3 Overview

This algorithm organizes a hierarchy of rich message properties into a flattened structure that can be represented as a serial data stream. The typical format of a particular property within the stream is: identifier (which usually also includes type information), size (where not exactly determined by type), and data. In some cases, as described in this document, groups of properties or multiple-value properties include counts. Others might include padding to enforce a particular alignment of the data.

A typical scenario for using this algorithm is as follows. A **TNEF Writer** encodes rich properties into a serial data stream in order to transmit the properties through a messaging system that does not support those properties directly. By encoding the properties in **TNEF**, the properties that do not have direct representations in the underlying messaging system can be encapsulated during transport and then decoded by a **TNEF Reader** in order to make all the properties included in the original message available to the client application.

### 1.4 Relationship to Protocols and Other Algorithms

This algorithm is intended to permit the transmission of rich message property information over transports that have no mechanism for representing that information natively.

The output of the algorithm can be included in any of the following:

- A file attachment (winmail.dat).
- A MIME **body part**, as described in [\[RFC2045\]](#), using the "application/ms-TNEF" media type.
- As an addition to the transmitted **plain text message body** using UUENCODE, as described in [\[MSDN-UAF\]](#), or a similar method to be decoded at the **recipient (1)** end.
- A transmission from the sender to the recipient (1) using whatever means are provided by the protocol employed in transmitting message information between them.

Specifically, this algorithm transmits message data over **Simple Mail Transfer Protocol (SMTP)**, **Post Office Protocol - Version 3 (POP3)**, **Internet Message Access Protocol - Version 4 (IMAP4)**, or other Internet protocols that incorporate MIME, as described in [\[RFC2045\]](#).

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

### 1.5 Applicability Statement

The original application of the algorithm was to permit the creation and representation of **message classes** other than simple e-mail messages, and some additional attributes that were not natively supported by the transport protocol.

This application was further extended to allow the transport of the rich set of properties required by more modern messaging clients, including **named properties**. For backward compatibility with the original implementation, a special attribute is used to encapsulate the new message properties, and those properties with analogues to the original implementation are usually represented using the original attribute syntax.

### 1.6 Standards Assignments

None.

## 2 Algorithm Details

### 2.1 Common Algorithm Details

This section specifies details that are common to both the TNEF Writer and TNEF Reader roles. For details specific to the TNEF Writer role, see section [2.2](#). For details specific to the TNEF Reader role, see section [2.3](#).

All numeric data types in this algorithm that are greater than one byte in size are little-endian, and any handling of these values on platforms that are not **little-endian** are required to take this into account and perform the appropriate transformations to get correct numbers, counts, values, and so on.

String examples in this document are shown in **Augmented Backus-Naur Form (ABNF)** format, as specified in [\[RFC5234\]](#). When the string has a terminating null character, the terminating null character is included as well; for example, "user1@example.com" %x00. For the purpose of string examples, the different terminating null character size in a **Unicode character set (1)** is not illustrated.

#### 2.1.1 Abstract Data Model

None.

#### 2.1.2 Initialization

None.

#### 2.1.3 Processing Rules

In this specification, attributes using the original syntax described in section [1.5](#) are referred to as "attributes" and the rich set of properties described in section [1.5](#) will be referred to as "properties".

The TNEF stream starts with a signature, a legacy key value, an attribute containing a legacy version number, and an attribute containing the **code page** used by the encoder for ANSI attributes and properties. After that, the stream is a series of attributes laid out, one after the other – message attributes followed by attachment attributes. The special attributes **attMsgProps**, **attRecipTable**, and **attAttachment** contain the various message and attachment properties. **attMsgProps** and **attAttachment** are counted lists; **attRecipTable** is a counted list of counted lists.

Each attribute is laid out as follows: the level at which it applies (message or attachment), ID, length of the contained data, the data itself, and a simple 16-bit checksum of the bytes comprising the data.

The **attMsgProps** attribute SHOULD be encoded after all other message attributes, and the **attAttachment** attribute SHOULD be encoded after all other attachment attributes. Values of encapsulated properties SHOULD be used instead of any conflicting mapped attribute values. Message attributes and properties SHOULD be encoded before attachment attributes and properties.

Each set of attachment attributes MUST begin with the **attAttachRendData** attribute, as specified in section [2.1.3.3.15](#), followed by any other attributes; attachment properties encoded in the **attAttachment** attribute, as specified in section [2.1.3.3.23](#), SHOULD be last.



### 2.1.3.1 Conventions

This algorithm uses the conventions and common definitions defined in this section for address representations and ABNF rule definitions.

#### 2.1.3.1.1 Address Representations

Address elements other than recipients (1), such as From and Sender, are represented in a **Message object** by a group of four properties: **display name**, address type, e-mail address, **EntryID**. In subsequent sections, these groups are referred to as described here.

**PidTagReceivedRepresenting\_XXX**: Refers to the **PidTagReceivedRepresentingName** ([MS-OXOMSG] section 2.2.1.26), **PidTagReceivedRepresentingAddressType** ([MS-OXOMSG] section 2.2.1.23), and **PidTagReceivedRepresentingEmailAddress** ([MS-OXOMSG] section 2.2.1.24), or **PidTagReceivedRepresentingEntryId** ([MS-OXOMSG] section 2.2.1.25) properties, where either would suffice to fully represent the display name, e-mail transport type, and e-mail address of a particular recipient (1) or person on behalf of whom a message was received.

**PidTagSender\_XXX**: Refers to **PidTagSenderName** ([MS-OXOMSG] section 2.2.1.51), **PidTagSenderAddressType** ([MS-OXOMSG] section 2.2.1.48), and **PidTagSenderEmailAddress** ([MS-OXOMSG] section 2.2.1.49), or **PidTagSenderEntryId** ([MS-OXOMSG] section 2.2.1.50) properties, where either would suffice to fully represent the display name, e-mail transport type, and e-mail address of a sender.

**PidTagSentRepresenting\_XXX**: Refers to **PidTagSentRepresentingName** ([MS-OXOMSG] section 2.2.1.57), **PidTagSentRepresentingAddressType** ([MS-OXOMSG] section 2.2.1.54), and **PidTagSentRepresentingEmailAddress** ([MS-OXOMSG] section 2.2.1.55), or **PidTagSentRepresentingEntryId** ([MS-OXOMSG] section 2.2.1.56) properties, where either would suffice to fully represent the display name, e-mail transport type, and e-mail address of a sender or person on behalf of whom a message was sent.

#### 2.1.3.1.2 ABNF Rules

This section specifies ABNF rules for data types common throughout section 2. For more details about these data types, see [MS-DTYP].

| Data type     | ABNF rules                     |
|---------------|--------------------------------|
| <b>INT16</b>  | <b>INT16</b> = ["-"] 1*5DIGIT  |
| <b>INT32</b>  | <b>INT32</b> = ["-"] 1*10DIGIT |
| <b>INT64</b>  | <b>INT64</b> = ["-"] 1*19DIGIT |
| <b>UINT16</b> | <b>UINT16</b> = 1*5DIGIT       |
| <b>UINT32</b> | <b>UINT32</b> = 1*10DIGIT      |

#### 2.1.3.2 ABNF Description

```
TNEFStream = TNEFHeader TNEFVersion OEMCodePage MessageData *AttachData
```

```
TNEFHeader = TNEFSignature LegacyKey
```

```
TNEFSignature = %x78.9F.3E.22
```

```
; Any number will suffice here. This is now legacy.
```

```

LegacyKey = UINT16

TNEFVersion = attrLevelMessage idTnefVersion Length TNEFVersionData Checksum

OEMCodePage = attrLevelMessage idOEMCodePage Length OEMCodePageData Checksum

MessageData = *MessageAttribute [MessageProps]
MessageAttribute = attrLevelMessage idMessageAttr Length Data Checksum
MessageProps = attrLevelMessage idMsgProps Length Data Checksum

; An attachment is determined/delimited by attAttachRendData, followed by
; other encoded attributes, if any, and ending with attAttachment if there are
; any encoded properties.
AttachData = AttachRendData [*AttachAttribute] [AttachProps]
AttachRendData = attrLevelAttachment idAttachRendData Length Data Checksum
AttachAttribute = attrLevelAttachment idAttachAttr Length Data Checksum
AttachProps = attrLevelAttachment idAttachment Length Data Checksum

; TNEF Version. Any number will suffice here. This is now legacy.
TNEFVersionData = 4*4OCTET

; This is the code page of attribute strings. The TNEF stream MUST contain a
; code page in which all characters are 8 bits
; in length, for compatibility with legacy applications that cannot handle
; strings with embedded zero characters.
OEMCodePageData = PrimaryCodePage SecondaryCodePage
PrimaryCodePage=UINT32

; Secondary CodePage is unused. It SHOULD contain zero.
SecondaryCodePage=%x00.00.00.00

; The length of the following data field in bytes. All attribute lengths are
; 32-bit integers, including any terminating null characters.
Length = INT32

; Data of the attribute itself, flattened out based on the particular attribute
; according to the rules that follow.
Data = 0*OCTET

; 16-bit unsigned integer that is the sum, modulo 65536, of the data bytes for
; the attribute value data, calculated over the entire length of the attribute data.
; In the case where the attribute contains enhanced properties with padding, the
; pad bytes MUST be included in the calculation.
Checksum = UINT16

; Level where attribute applies, either to the message itself or to
; an attachment.
attrLevelMessage = %x01
attrLevelAttachment = %x02

; Attribute ID Tags

; TNEF Version
idTnefVersion = %x06.90.08.00

; OEM Codepage. See attOemCodepage handling in section 5 and Appendix A.
idOemCodepage = %x07.90.06.00

; Message-level attributes. SHOULD all be at attrLevelMessage.

```

```

idMessageAttr = idMessageClass / idFrom / idSubject / idDateSent /
idDateRecd / idMessageStatus / idMessageID /
idBody / idPriority / idDateModified /
idRecipTable / idOriginalMessageClass / idOwner / idSentFor /
idDelegate / idDateStart / idDateEnd / idAidOwner / idRequestRes

; PidTagMessageClass property ([MS-OXOMSG] section 2.2.2.1)
idMessageClass = %x08.80.07.00

; PidTagSender_XXX properties, as specified in section 2.1.3.1.1
idFrom = %x00.80.00.00

; PidTagSubject property ([MS-OXCMSG] section 2.2.1.46)
idSubject = %x04.80.01.00

; PidTagClientSubmitTime property ([MS-OXOMSG] section 2.2.3.11)
idDateSent = %x05.80.03.00

; PidTagMessageDeliveryTime property ([MS-OXOMSG] section 2.2.3.9)
idDateRecd = %x06.80.03.00

; PidTagMessageFlags property ([MS-OXCMSG] section 2.2.1.6)
idMessageStatus = %x07.80.06.00

; PidTagSearchKey property ([MS-OXCPRPT] section 2.2.1.9)
idMessageID = %x09.80.01.00

; PidTagBody property ([MS-OXCMSG] section 2.2.1.48.1)
idBody = %x0C.80.02.00

; PidTagImportance property ([MS-OXCMSG] section 2.2.1.11)
idPriority = %x0D.80.04.00

; PidTagLastModificationTime property ([MS-OXCMSG] section 2.2.2.2)
; for the message
idDateModified = %x20.80.03.00

; Message Property Encapsulation
idMsgProps = %x03.90.06.00

; PidTagMessageRecipients property ([MS-OXCMSG] section 2.2.1.47).
; For more details, see section 2.1.3.5.2.2.
idRecipTable = %x04.90.06.00

; PidTagOriginalMessageClass property ([MS-OXPROPS] section 2.881)
idOriginalMessageClass = %x00.06.07.00

; PidTagReceivedRepresenting_XXX or
PidTagSentRepresenting_XXX properties, as specified in section 2.1.3.1.1
idOwner = %x00.00.06.00

; PidTagSentRepresenting_XXX properties, as specified in section 2.1.3.1.1
idSentFor = %x01.00.06.00

; PidTagReceivedRepresentingEntryId property ([MS-OXOMSG] section 2.2.1.25)
idDelegate = %x00.02.06.00

; PidTagStartDate property ([MS-OXOCAL] section 2.2.1.30)
idDateStart = %x06.00.03.00

```

```

; PidTagEndDate property ([MS-OXOCAL] section 2.2.1.31)
idDateEnd = %x07.00.03.00

; PidTagOwnerAppointmentId property ([MS-OXOCAL] section 2.2.1.29)
idAidOwner = %x08.00.05.00

; PidTagResponseRequested property ([MS-OXOCAL] section 2.2.1.36)
idRequestRes = %x09.00.04.00

; Attachment-level attributes. All MUST be at attrLevelAttachment.
idAttachAttr = idAttachData / idAttachTitle / idAttachMetaFile /
idAttachCreateDate / idAttachModifyDate / idAttachTransportFilename

; PidTagAttachDataBinary property ([MS-OXCMSG] section 2.2.2.7)
idAttachData = %x0F.80.06.00

; PidTagAttachFilename property ([MS-OXCMSG] section 2.2.2.11)
idAttachTitle = %x10.80.01.00

; PidTagAttachRendering property ([MS-OXCMSG] section 2.2.2.17)
idAttachMetaFile = %x11.80.06.00

; PidTagCreationTime property ([MS-OXCMSG] section 2.2.2.3)
idAttachCreateDate = %x12.80.03.00

; PidTagLastModificationTime property ([MS-OXCMSG] section 2.2.2.2)
; for the attachment.
idAttachModifyDate = %x13.80.03.00

; PidTagAttachTransportName property ([MS-OXCMSG] section 2.2.2.19)
idAttachTransportFilename = %x01.90.06.00

; Attachment RendData, as specified in section 2.1.3.3.15
idAttachRendData = %x02.90.06.00

; Attachment table row
idAttachment = %x05.90.06.00

```

### 2.1.3.3 Attributes

This section specifies the attributes that appear in the TNEF stream, including the structure of the attributes, the message properties they map to, and any required conversions between them and message properties.

Each attribute is described by a level at which it applies (message or attachment), the attribute ID, the length of the attribute data, the attribute data, and a simple checksum. They are documented in the following sections in the form "**attXXXX**". For example, **attSubject** refers to the following:

**attrLevelMessage** idSubject Length \*VCHAR Checksum

#### 2.1.3.3.1 attTnefVersion Attribute

For details about how the TNEF Writer handles this attribute, see section [2.2.3.1](#). For details about the TNEF Reader handles this attribute, see section [2.3.3.1](#).

### 2.1.3.3.2 attOemCodepage Attribute

The **attOemCodepage** attribute contains the code page used by the TNEF Writer for all attribute string values, and for any ANSI strings in the encapsulated message properties. For more information about code page handling, see section [2.1.3.5.1](#).

### 2.1.3.3.3 attFrom Attribute

The **attFrom** attribute is a message-level attribute that maps to and from the **PidTagSender\_XXX** properties, as specified in section [2.1.3.1.1](#).

The data for this attribute encodes as follows:

```
TRP-structure = TRP-header sender-display-name sender-email empty
TRP-header = trpidOneOff structure-length sender-name-length sender-email-length
; Structure type
trpidOneOff = %x04.00

; The length of the entire structure. See the following description.
structure-length = UINT16

; Length of sender display name string, including the terminating null character.
sender-name-length = UINT16

; Length of sender e-mail string, including the terminating null character.
sender-email-length = UINT16
sender-display-name = 1*OCTET %x00
sender-email = sender-email-type ":" sender-email-address %x00
sender-email-type = 1*CHAR
sender-email-address = 1*CHAR
; Empty 8-byte structure
empty = 8*%x00
```

The **structure-length** field is calculated as eight (the size of TRP-header in OCTETs) plus the length of sender-display-name (including the terminating null character), plus the length of sender-email (including the terminating null character), plus eight (the size of the empty eight bytes).

The **sender-name-length** field is the length of sender-display-name in OCTETs (including the terminating null character).

The **sender-email-length** field is calculated as the length of sender-email (including the terminating null character).

The **sender-email** field is composed of four parts, the address-type (for example, the literal sequence "SMTP" for Internet addresses), a literal colon (":"), the address itself, and a terminating null character. For example, the string "SMTP:user2@example.com" %x00 is a legal sender-email value.

The **empty** field is a zero-filled 8-byte structure.

For details about how the TNEF Writer handles the **sender-email** field, see section [2.2.3.3](#). For details about the TNEF Reader handles the **sender-email** field, see section [2.3.3.3](#).

#### 2.1.3.3.4 Date Attributes

The date attributes, which are of type **PtypTime** ([\[MS-OXCDATA\]](#) section 2.11.1), are encoded into a **Date Time Record** structure, as follows. The encoding process used is implementation-dependent.

```
DTR = wYear wMonth wDay wHour wMinute wSecond wDayOfWeek
wYear = UINT16
wMonth = UINT16
wDay = UINT16
wHour = UINT16
wMinute = UINT16
wSecond = UINT16
wDayOfWeek = UINT16
```

The **wYear** field contains the year (for example, 2008 is %xD8.07); the **wMonth** field is 1 for January, and so on; The **WDay** field is 1 for the first day of the month; the **wHour**, **wMinute**, and **wSecond** fields contain the time; the **wDayOfWeek** field is 1 for Monday.

| Attribute (in TNEF)        | Level      | Message property   |
|----------------------------|------------|--|
| <b>attDateSent</b>         | Message    | <b>PidTagClientSubmitTime</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.3.11)    |
| <b>attDateRecd</b>         | Message    | <b>PidTagMessageDeliveryTime</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.3.9)  |
| <b>attAttachCreateDate</b> | Attachment | <b>PidTagCreationTime</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.2.3)         |
| <b>attAttachModifyDate</b> | Attachment | <b>PidTagLastModificationTime</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.2.2) |
| <b>attDateModified</b>     | Message    | <b>PidTagLastModificationTime</b>  |
| <b>attDateStart</b>        | Message    | <b>PidTagStartDate</b> ( <a href="#">[MS-OXOCAL]</a> section 2.2.1.30)           |
| <b>attDateEnd</b>          | Message    | <b>PidTagEndDate</b> ( <a href="#">[MS-OXOCAL]</a> section 2.2.1.31)             |

#### 2.1.3.3.5 Message Class Attributes

The message class attribute value is stored as a zero-terminated string that holds the name specified by the client.

Message class attributes in TNEF are as follows:

| Attribute in TNEF              | Level   | Message Property  |
|--------------------------------|---------|---|
| <b>attMessageClass</b>         | Message | <b>PidTagMessageClass</b> ( <a href="#">[MS-OXPROPS]</a> section 2.886)         |
| <b>attOriginalMessageClass</b> | Message | <b>PidTagOriginalMessageClass</b> ( <a href="#">[MS-OXPROPS]</a> section 2.819) |

For details about how the TNEF Writer handles these attributes, see section [2.2.3.4](#). For details about the TNEF Reader handles this field, see section [2.3.3.4](#).

#### 2.1.3.3.6 attMessageID Attribute

The **attMessageID** attribute is a message-level attribute that maps to the **PidTagSearchKey** property ([\[MS-OXCPRPT\]](#) section 2.2.1.9). The **PidTagSearchKey** property that maps to this attribute is stored in binary, but the attribute is represented in text format.

For details about how the TNEF Writer handles this attribute, see section [2.2.3.7](#). For details about how the TNEF Reader handles this attribute, see section [2.3.3.5](#).

### 2.1.3.3.7 attSubject Attribute

The **attSubject** attribute is a message-level attribute that maps to and from the **PidTagSubject** property ([\[MS-OXCMSG\]](#) section 2.2.1.46).

The data for this attribute is stored as a string with a terminating null character.

### 2.1.3.3.8 attMessageStatus Attribute

The **attMessageStatus** attribute is a message-level attribute that maps to and from the **PidTagMessageFlags** property ([\[MS-OXCMSG\]](#) section 2.2.1.6).

The data for this attribute is stored as an unsigned 32-bit integer, with the appropriate bits set to indicate the message status. For compatibility, these MUST be mapped to and from the following values:

| Status          | Attribute Flag (in TNEF) | Bit Value | Message Property Flag     | Bit Value |
|-----------------|--------------------------|-----------|---------------------------|-----------|
| Read            | <b>fmsRead</b>           | 0x20      | <b>MSGFLAG_READ</b>       | 0x01      |
| Unmodified      | <b>fmsModified</b>       | 0x01      | <b>MSGFLAG_UNMODIFIED</b> | 0x02      |
| Submitted       | <b>fmsSubmitted</b>      | 0x04      | <b>MSGFLAG_SUBMIT</b>     | 0x04      |
| Unsent          | <b>fmsLocal</b>          | 0x02      | <b>MSGFLAG_UNSENT</b>     | 0x08      |
| Has Attachments | <b>fmsHasAttach</b>      | 0x80      | <b>MSGFLAG_HASATTACH</b>  | 0x10      |

If the **fmsModified** attribute flag is set, then the corresponding message property flag (**MSGFLAG\_UNMODIFIED**) is clear (that is, not set). If the **fmsModified** attribute flag is clear, then the corresponding message property flag (**MSGFLAG\_UNMODIFIED**) is set. For all other flags, either both the attribute flag and corresponding message property flag are set or both the attribute flag and corresponding message property flag are clear.

### 2.1.3.3.9 attBody Attribute

The **attBody** attribute MAY [<1>](#) be supported.

The **attBody** attribute is a message-level attribute that maps to and from the **PidTagBody** property ([\[MS-OXCMSG\]](#) section 2.2.1.56.1).

The data for this attribute is stored as a string with a terminating null character.

For more details about how the TNEF Writer handles this attribute, see section [2.2.3.6](#).

### 2.1.3.3.10 attPriority Attribute

The **attPriority** attribute is a message-level attribute that maps to and from the **PidTagImportance** property ([\[MS-OXCMSG\]](#) section 2.2.1.11).

The data for this attribute is stored as an unsigned 16-bit integer. For compatibility, these MUST be mapped to and from the following values:

| Priority | Value (in TNEF) | Message Property Value |
|----------|-----------------|------------------------|
| Low      | 3               | 0                      |
| Normal   | 2               | 1                      |
| High     | 1               | 2                      |

#### 2.1.3.3.11 attAttachData Attribute

The **attAttachData** attribute is an attachment-level attribute that maps to and from the **PidTagAttachDataBinary** property ([\[MS-OXCMSG\]](#) section 2.2.2.7).

The data for this attribute is stored as a binary stream.

For details about how the TNEF Writer handles this attribute, see section [2.2.3.8](#). For details about how the TNEF Reader handles this attribute, see section [2.3.3.7](#).

#### 2.1.3.3.12 attAttachTitle Attribute

The **attAttachTitle** attribute is an attachment-level attribute that maps to and from the **PidTagAttachLongFilename** property ([\[MS-OXCMSG\]](#) section 2.2.2.10).

The data for this attribute is stored as a string with a terminating null character.

For details about how the TNEF Writer handles this attribute, see section [2.2.3.9](#). For details about how the TNEF Reader handles this attribute, see section [2.3.3.8](#).

#### 2.1.3.3.13 attAttachMetaFile Attribute

The **attAttachMetaFile** attribute is an attachment-level attribute that maps to and from the **PidTagAttachRendering** property ([\[MS-OXCMSG\]](#) section 2.2.2.17).

The data for this attribute is stored as a binary stream. For a description of the content of the binary stream, see [\[MS-WMF\]](#).

#### 2.1.3.3.14 attAttachTransportFilename Attribute

The **attAttachTransportFilename** attribute is an attachment-level attribute that maps to and from the **PidTagAttachTransportName** property ([\[MS-OXCMSG\]](#) section 2.2.2.19).

The data for this attribute is stored as a string with a terminating null character.

#### 2.1.3.3.15 attAttachRendData Attribute

The **attAttachRendData** attribute is an attachment-level attribute that contains a structure of information that can be used for rendering the attachment in the body.

Each set of attachment attributes MUST begin with the **attAttachRendData** attribute, followed by any other attributes; attachment properties encoded in the **attAttachment** attribute SHOULD be last.

The structure is formatted as follows:

```
attAttachRendData = AttachType AttachPosition RenderWidth RenderHeight DataFlags
AttachType = AttachTypeFile / AttachTypeOle
```



```
AttachTypeFile=%x01.00
AttachTypeOle=%x02.00
AttachPosition= INT32
RenderWidth=INT16
RenderHeight=INT16
DataFlags = FileDataDefault / FileDataMacBinary
FileDataDefault= %x00.00.00.00
FileDataMacBinary=%x01.00.00.00
```

The **AttachPosition** field maps to and from the **PidTagRenderingPosition** property ([\[MS-OXCMSG\]](#) section 2.2.2.16).

For details about how the TNEF Writer handles this attribute, see section [2.2.3.10](#). For details about how the TNEF Reader handles this attribute, see section [2.3.3.9](#).

### 2.1.3.3.16 attOwner Attribute

The **attOwner** attribute is a message-level attribute that is also a meeting attribute that maps to and from the **PidTagReceivedRepresenting\_XXX** or **PidTagSentRepresenting\_XXX** properties, as specified in section [2.1.3.1.1](#).

The **attOwner** attribute is encoded as counted strings laid end-to-end. The format for **attOwner** attribute is as follows:

```
attOwner=display-name-length display-name address-length address

; Length of "display-name," including terminating null character.
display-name-length=UINT16
display-name=*CHAR %x00

; Length of "address", including terminating null character.
address-length=UINT16
address= 1*CHAR ":" 1*CHAR %x00
```

The display-name-length and address-length are unsigned 16-bit values, including the terminating null characters for the strings. The type and address strings in the email-address entry are separated by a colon (:) character; for example, "SMTP:user1@example.com" %x00.

The mapping of message properties to the **attOwner** attribute is dependent on the message class of the message being encoded.

For details about how the TNEF Writer handles this attribute, see section [2.2.3.11](#). For details about how the TNEF Reader handles this attribute, see section [2.3.3.10](#).

### 2.1.3.3.17 attSentFor Attribute

The **attSentFor** attribute is a message-level attribute that is also a meeting attribute that maps to and from the **PidTagSentRepresenting\_XXX** properties, as specified in section [2.1.3.1.1](#).

For details about how the TNEF Writer handles this attribute, see section [2.2.3.12](#). For details about how the TNEF Reader handles this attribute, see section [2.3.3.11](#).

### 2.1.3.3.18 attDelegate Attribute

The **attDelegate** attribute MAY [<2>](#) be supported.

The **attDelegate** attribute is a message-level attribute that is a meeting attribute that maps to and from **PidTagReceivedRepresentingEntryId** property ([\[MS-OXOMSG\]](#) section 2.2.1.25).

The content can be transported as a **binary large object (BLOB)**.

For details about how the TNEF Writer handles this attribute, see section [2.2.3.13](#). For details about how the TNEF Reader handles this attribute, see section [2.3.3.12](#).

#### 2.1.3.3.19 attAidOwner Attribute

The **attAidOwner** attribute is a message-level attribute that is a meeting attribute that maps to and from the **PidTagOwnerAppointmentId** property ([\[MS-OXOCAL\]](#) section 2.2.1.29).

The content can be transported as a BLOB.

#### 2.1.3.3.20 attRequestRes Attribute

The **attRequestRes** attribute is a message-level attribute that is a meeting attribute that maps to and from the **PidTagResponseRequested** property ([\[MS-OXOCAL\]](#) section 2.2.1.36).

The data type of this value is a **BOOLEAN** ([\[MS-DTYP\]](#)); however, it SHOULD be transported as an **INT16** value ([\[MS-DTYP\]](#)). The 2-byte **INT16** value contains a null byte as the high-order 8 bits and the value of the **PidTagResponseRequested** property as the low-order 8 bits.

#### 2.1.3.3.21 attMsgProps Attribute

The **attMsgProps** attribute is a message-level attribute that maps to and from an arbitrary set of message properties.

For a description of the encoding for this attribute, see section [2.1.3.4](#).

For details about how the TNEF Writer handles this attribute, see section [2.2.3.14](#).

#### 2.1.3.3.22 attRecipTable Attribute

The **attRecipTable** attribute is a message-level attribute that maps to and from the **PidTagMessageRecipients** property ([\[MS-OXCMSG\]](#) section 2.2.1.47).

For a description of the encoding for this attribute, see section [2.1.3.4](#).

#### 2.1.3.3.23 attAttachment Attribute

The **attAttachment** attribute is an attachment-level attribute that maps to and from an arbitrary set of properties for a single attachment.

For a description of the encoding for this attribute, see section [2.1.3.4](#).

For details about how the TNEF Writer handles this attribute, see section [2.2.3.15](#).

### 2.1.3.4 Encapsulated Message and Attachment Properties

The **attMsgProps** and **attAttachment** attributes, as specified in sections [2.1.3.3.21](#) and section [2.1.3.3.23](#) respectively, are special in that they are used to encode any message or attachment property that does not have a counterpart in the set of existing TNEF-defined attributes. The attribute data is a counted set of message or attachment properties laid end-to-end. The format of this encoding, which allows for any set of message or attachment properties, is as follows.

```

; Attributes containing encapsulated properties:

; attMsgProps - Maps to and from an arbitrary set of message properties.
MsgPropsData = MsgPropertyList

; attRecipTable - Maps to and from PidTagMessageRecipients,
; as specified in [MS-OXCMSG] section 2.2.1.47.
; Number of table rows followed by the rows.
RecipTableData = NumRows *RecipRow

NumRows = UINT32
RecipRow = MsgPropertyList

; attAttachment - Maps to/from an arbitrary set of properties for a single attachment.
AttachPropsData = MsgPropertyList

MsgPropertyList = MsgPropertyCount *MsgPropertyValue
MsgPropertyCount = UINT32

MsgPropertyValue = MsgPropertyTag MsgPropertyData
MsgPropertyTag = MsgPropertyType MsgPropertyId [NamedPropSpec]

; This property MUST be present when MsgPropertyId is >= 0x8000 (the minimum value
; of property ID for named properties, as specified in
; [MS-OXPROPS] section 1.3.3).
NamedPropSpec = PropNameSpace PropIDType PropMap

; Contains a GUID, as specified in [MS-OXCDATA], to specify the namespace.
; The TNEF Writer obtains this value by using the RopGetNamesFromPropertyIDs ROP,
; as specified in [MS-OXCROPS] section 2.2.8.2.
PropNameSpace = GUID
PropIDType = IDTypeNumber / IDTypeString
PropMap = PropMapID / PropMapString

IDTypeNumber = %x00.00.00.00
IDTypeString = %x01.00.00.00

; Used if PropIDType is IDTypeNumber. Contains a number, as specified in
; [MS-OXPROPS], that is used to identify the property within the namespace.
PropMapID = UINT32

; Used if PropIDType is IDTypeString. Contains a length, then a
; UTF-16LE encoded Unicode string.
; The length is the length of the UTF-16LE encoded Unicode string
; (including the terminating 2-byte null character).
; Optional padding to UINT32 boundary.
; The TNEF Writer obtains this value by using the RopGetNamesFromPropertyIDs
; ROP, as specified in [MS-OXCROPS] section 2.2.8.2.
PropMapString = UINT32 *UINT16 %x00.00 [PropMapPad]

; Padding for a UTF-16LE encoded Unicode string to achieve a
; multiple of 4 bytes in length.
; The TNEF Writer MUST use zero bytes and the TNEF Reader
; MUST permit non-zero bytes.
; SHOULD be either 0 or 2 bytes.
PropMapPad=*1UINT16

MsgPropertyType = TypeUnspecified / TypeNull / TypeInt16 / TypeInt32 /

```

```

TypeFlt32 / TypeFlt64 / TypeCurrency / TypeAppTime / TypeError /
TypeBoolean / TypeObject / TypeInt64 / TypeString8 / TypeUnicode /
TypeSystemtime / TypeCLSID / TypeBinary / TypeMVarInt16 / TypeMVarInt32 /
TypeMVarFlt32 / TypeMVarFlt64 / TypeMVCurrency / TypeMVAppTime /
TypeMVSystemtime / TypeMVString8 / TypeMVBinary / TypeMVUnicode /
TypeMVCLSID / TypeMVInt64

; An arbitrary value that corresponds to the property.

MsgPropertyID = UINT16

TypeUnspecified = %x00.00

TypeNull = %x01.00

; Signed 16-bit value = INT16.
TypeInt16 = %x02.00
TypeMVarInt16 = %x02.10

; Signed 32-bit value = INT32.
TypeInt32 = %x03.00
TypeMVarInt32 = %x03.10

; Signed 32-bit floating point= FLOAT.
TypeFlt32 = %x04.00
TypeMVarFlt32 = %x04.10

; 64-bit floating point= DOUBLE.
TypeFlt64 = %x05.00
TypeMVarFlt64 = %x05.10

; Signed 64-bit int = OLE CURRENCY type.
TypeCurrency = %x06.00
TypeMVCurrency = %x06.10

; Application time= OLE DATE type.
TypeAppTime = %x07.00
TypeMVarAppTime = %x07.10

TypeError = %x0A.00

; 16-bit Boolean (non-zero = TRUE)
TypeBoolean = %x0B.00

; Embedded object on a property.
TypeObject = %x0D.00

; 8-byte signed integer= INT64.
TypeInt64 = %x14.00
TypeMVarInt64 = %x14.10

; 8-bit character string with terminating null character.
TypeString8 = %x1E.00
TypeMVString8 = %x1E.10

; UTF-16LE or variant character string with terminating 2-byte null character.
TypeUnicode = %x1F.00
TypeMVUnicode = %x1F.10

```

```

; FILETIME (a PtypTime value, as specified in [MS-OXCADATA] section 2.11.1)
TypeSystime = %x40.00
TypeMVSystime = %x40.10

; OLE GUID
TypeCLSID = %x48.00
TypeMVCLSID = %x48.10

; Uninterpreted BLOB.
TypeBinary = %x02.01
TypeMVBinary = %x02.11

; MsgPropertyData varies by property type. Individual property values
; are formatted as specified in [MS-OXCADATA] section 2.11, with
; padding as specified in this document.
MsgPropertyData = PropertyScalarContent / PropertyMultiScalarContent /
PropertyMultiVariableContent

; Scalars - Types Int16, Int32, Flt32, Flt64, Currency, AppTime,
; Bool, Int64, Systime, CLSID
; The data for the particular property is written to the stream and if necessary,
; padded with bytes (which SHOULD be zero) to achieve a multiple of 4-bytes in length.
PropertyScalarContent = MsgPropertyContent [PropertyPad]

; PropertyPad - between 0 and 3 zero-filled bytes, added to the streamed
; property values to achieve 4-byte boundary. The TNEF Writer MUST use zero bytes
; and the TNEF Reader MUST permit non-zero bytes. These pad bytes MUST be counted
; in the checksum of the containing attribute.
PropertyPad=*3ZERO
ZERO= %x00

; Multi-value Scalars - Types MVInt16, MVInt32, MVFlt32, MVFlt64, MVCurrency,
; MVAppTime, MVInt64, MVSystime, MVCLSID
; The number of values for the property is written to the stream as a 4-byte
; value, then the data for each value is written to the stream and if need
; be, padded with bytes (which SHOULD be zero) to achieve a multiple of 4 bytes in length.
PropertyMultiScalarContent = PropertyContentCount *PropertyScalarContent
PropertyContentCount = UINT32

; Variable-length - Types Unicode, String8, Object, Binary.
; These are handled as a special case of Multi-Variable-Length with the number of values=1.

; Multi-Variable-length - Types MVUnicode, MVString8, MVBinary
; The number of values for the property is written to the stream as a 4-byte value. ; Then,
; for each value, the size of the property is written to the stream as a
; 4-byte value, then the data for the property is written to the stream and, if
; necessary, padded with zero bytes to achieve a multiple of 4 bytes in length.

PropertyMultiVariableContent = MsgPropertyCount 1*PropertyVariableContent
MsgPropertyCount = UINT32

; The size of the property is written to the stream as a 4-byte value, then the data
; for the property is written to the stream and if necessary, padded with zero bytes
; to achieve a multiple of 4 bytes in length. The size includes the Interface
; Identifier at the beginning of the value stream for an object but does not include
; the padding bytes.
;
; If the property is of type PtypObject, as specified in
; [MS-OXCADATA] section 2.11.1,

```

```

; the value-size is followed by the Interface Identifier of the object, then the serialized
; stream of the data of the object. Only the Interface Identifier values
; %x0B.00.00.00.00.00.00.00.C0.00.00.00.00.00.00.46,
; %x0C.00.00.00.00.00.00.00.C0.00.00.00.00.00.00.46, and the Interface Identifiers of
; Message objects are supported. The size of the Interface Identifier is
; included in the calculation of value-size.
;
; If the object is an attached message (that is, it has a property type of
; PtypObject (as specified in [MS-OXCDATA] section 2.12.1) and an
; Interface Identifier %x07.03.02.00.00.00.00.00.C0.00.00.00.00.00.00.46,
; (that of a Message object), the value data is encoded as an embedded TNEF
; stream (that is, a complete TNEF stream as defined by this specification).

PropertyVariableContent = MsgPropertySize MsgPropertyContent [PropertyPad]
MsgPropertySize = UINT32

```

### 2.1.3.5 Other Compatibility Issues

The preceding sections addressed issues of compatibility between the original implementation of TNEF and the richer implementation that is now used. This section discusses some compatibility issues within the richer implementation.

#### 2.1.3.5.1 attOemCodepage Attribute Handling

The **attOemCodepage** attribute, as specified in section [2.1.3.3.2](#), has been handled inconsistently between multiple implementations of TNEF. This can be particularly troublesome when forwarding messages with attached messages between systems that have different default code pages. To minimize problems caused by this inconsistent behavior, section [2.2.3.2](#) specifies the recommended way to handle string encoding and section [2.3.3.2](#) specifies the way to handle string decoding.

#### 2.1.3.5.2 TNEF Encapsulation Versus Outer Wrapper Attributes

It is possible to encapsulate properties in the TNEF stream that represents data that is already conveyed as part of an outer wrapper such as MIME. Because in many cases the outer wrapper properties are subject to substantial validation during transport (reverse DNS lookups and other validation), they are considered more trustworthy than information inside an attached file that otherwise could overwrite correct information with incorrect information.

As a general rule, the TNEF Writer does not duplicate any data that is already being reliably transported outside the stream and the TNEF Reader does not override data from outside the stream with data from inside the stream. Individual implementations determine how this rule is applied. For more details, see [\[MS-OXCMAIL\]](#). Some highlights of this behavior are specified in the following sections.

##### 2.1.3.5.2.1 attBody Attribute Handling

When TNEF is being sent as a MIME body part, the **attBody** attribute is not written to TNEF or read from TNEF either by the client or server. The plain text message body is instead transmitted in a MIME body part. For more details about **attBody** attribute handling by the TNEF Writer, see section [2.2.3.6](#). For more details about MIME body parts, see [\[MS-OXCMAIL\]](#).

### 2.1.3.5.2.2 attRecipTable Attribute Handling

When TNEF is being sent as a MIME body part, the **attRecipTable** attribute is not written to TNEF or read from TNEF either by the client or server, except when sending or receiving a legacy **non-delivery report** message (the value of the **attMessageClass** attribute begins with "REPORT." and ends in ".DR" or ".NDR"). The requisite message recipient (1) information is transmitted in the MIME structure instead.

When TNEF is being sent as a MIME body part, when sending or receiving a legacy non-delivery report message (the value of the **attMessageClass** attribute begins with "REPORT." and ends in ".DR" or ".NDR"), recipient (1) information from the **attRecipTable** attribute is used to populate the received message recipient (1) table.

For more details about **attRecipTable** attribute handling by the TNEF Writer, see section [2.2.3.16](#).

### 2.1.3.5.2.3 attFrom Attribute Handling

The **attFrom** attribute is not written to TNEF or read from TNEF either by the client or the server for MIME messages. The requisite message recipient (1) information is transmitted in the MIME stream instead. For more details about how the TNEF Writer encodes sender information, see section [2.2.3.3](#).

### 2.1.3.5.2.4 attSubject Attribute Handling

The **attSubject** attribute, if present for a MIME message, is overwritten by the subject value in the MIME stream. For details about how the TNEF Writer handles this attribute, see section [2.2.3.5](#). For details about how the TNEF Reader handles this attribute, see section [2.3.3.6](#).

## 2.2 TNEF Writer Algorithm Details

The TNEF Writer encodes or builds a TNEF stream for the purpose of transporting rich properties. This section specifies details specific to the TNEF Writer role.

For details common to both the TNEF Reader and TNEF Writer roles, see section [2.1](#).

### 2.2.1 Abstract Data Model

None.

### 2.2.2 Initialization

None.

### 2.2.3 Processing Rules

This section specifies the processing rules applied by the TNEF Writer to specific TNEF attributes. For processing rules common to the TNEF Writer and the TNEF Reader, see section [2.1.3.3](#).

#### 2.2.3.1 attTnefVersion Attribute Handling by the TNEF Writer

The **attTnefVersion** attribute, as specified in section [2.1.3.3.1](#) MUST be written as %x00.00.01.00 by the TNEF Writer.

### 2.2.3.2 attOemCodepage Attribute Handling by TNEF Writer

The TNEF Writer writes all ANSI strings, both the attribute strings and the encapsulated message property strings, with a consistent ANSI code page and puts its value into the **attOemCodepage** property, as specified in section [2.1.3.3.2](#). Choose a code page that does not allow embedded zero bytes other than the zero terminator.

If **PidTagInternetCodepage** ([\[MS-OXCMSG\]](#) section 2.2.1.56.6) is being stored in the encapsulated properties, set it to the same value as the **attOemCodepage** attribute. This code page also determines the character set (1) used in MIME if this TNEF is transmitted as a MIME entity body.

Do not write to an attribute any string that would suffer data loss if written using the consistent code page. Write to encapsulated properties with a Unicode data type all strings that would suffer data loss when using the consistent code page.

For compatibility purposes, the **attMessageClass** attribute always writes using the consistent code page.

### 2.2.3.3 attFrom Attribute Handling by the TNEF Writer

When encoding the **sender-email** field of the **attFrom** attribute, as specified in section [2.1.3.3.3](#), the TNEF Writer can use the **PidTagSenderName** ([\[MS-OXOMSG\]](#) section 2.2.1.51), **PidTagSenderAddressType** ([\[MS-OXOMSG\]](#) section 2.2.1.48), and **PidTagSenderEmailAddress** ([\[MS-OXOMSG\]](#) section 2.2.1.49) properties if present, or access their values using the **PidTagSenderEntryId** property ([\[MS-OXOMSG\]](#) section 2.2.1.50).

When TNEF is being used to encode an attached message, the sender information is carried in encapsulated message properties in the **attFrom** attribute.

### 2.2.3.4 Message Class Attribute Handling by the TNEF Writer

The TNEF Writer can represent any message class, as specified in section [2.1.3.3.5](#), whose value is shown in the Message Property Value column of the following table, using the value in the Attribute value column.

| Attribute value (in TNEF)       | Message property value         |
|---------------------------------|--------------------------------|
| IPM.Microsoft Mail.Note         | IPM.Note                       |
| IPM.Microsoft Mail.Read Receipt | Report.IPM.Note.IPNRN          |
| IPM.Microsoft Mail.Non-Delivery | Report.IPM.Note.NDR            |
| IPM.Microsoft Schedule.MtgRespP | IPM.Schedule.Meeting.Resp.Pos  |
| IPM.Microsoft Schedule.MtgRespN | IPM.Schedule.Meeting.Resp.Neg  |
| IPM.Microsoft Schedule.MtgRespA | IPM.Schedule.Meeting.Resp.Tent |
| IPM.Microsoft Schedule.MtgReq   | IPM.Schedule.Meeting.Request   |
| IPM.Microsoft Schedule.MtgCncl  | IPM.Schedule.Meeting.Canceled  |

Values not included in the table SHOULD be written in their original form.



### 2.2.3.5 attSubject Attribute Handling by the TNEF Writer

When TNEF is being used to encode an attached message, the message subject information is carried in encapsulated message properties in the **attMsgProps** attribute, not the **attSubject** attribute.

### 2.2.3.6 attBody Attribute Handling by the TNEF Writer

When TNEF is being used to encode an attached message, the **attBody** attribute, as specified in section [2.1.3.3.9](#), MAY **<3>** be written and read.

### 2.2.3.7 attMessageID Attribute Handling by the TNEF Writer

For compatibility, when generating a TNEF stream, the TNEF Writer MUST translate the binary representation of the **attMessageID** attribute, as specified in section [2.1.3.3.6](#), into a textual one by emitting the two CHAR hexadecimal equivalent per OCTET (i.e. %x01 becomes "01", %x2D becomes "2D", and so on).

### 2.2.3.8 attAttachData Attribute Handling by the TNEF Writer

The TNEF Writer can use the **attAttachData** attribute, as specified in section [2.1.3.3.11](#), for the attachment data if the **PidTagAttachMethod** property ([\[MS-OXCMSG\]](#) section 2.2.2.9) of the original attachment contains the value 0x0001 (ATTACH\_BY\_VALUE). If the **PidTagAttachMethod** of the original attachment contains the value 0x0005 (ATTACH\_EMBEDDED\_MSG) or the value 0x0006 (ATTACH\_OLE), then the TNEF Writer MUST encode the data in **attAttachment** (section [2.1.3.4](#)).

### 2.2.3.9 attAttachTitle Attribute Handling by the TNEF Writer

The TNEF Writer obtains the value of the **attAttachTitle** attribute, as specified in section [2.1.3.3.12](#), from the **PidTagAttachLongFilename** property ([\[MS-OXCMSG\]](#) section 2.2.2.10) if it is available; otherwise, the TNEF Writer obtains the value of the **attAttachTitle** attribute from the **PidTagAttachFilename** property.

### 2.2.3.10 attAttachRendData Attribute Handling by the TNEF Writer

The **AttachType** field of the **attAttachRendData** attribute, as specified in section [2.1.3.3.15](#), MUST be set by the TNEF Writer to the value of the **AttachTypeFile** attribute when the **PidTagAttachMethod** property ([\[MS-OXCMSG\]](#) section 2.2.2.9) for the attachment is set to ATTACH\_BY\_VALUE or ATTACH\_EMBEDDED\_MSG, and to the value of the **AttachTypeOle** attribute when the **PidTagAttachMethod** property is set to ATTACH\_OLE.

The **RenderWidth** and **RenderHeight** fields of the **attAttachRendData** attribute SHOULD be set by the TNEF Writer to the size of the system icons if the attachment is a simple file attachment, or to {-1,-1} if the attachment is not a simple file attachment.

The **DataFlags** field SHOULD **<4>** always be set to **FileDataDefault** (%x00.00.00.00), regardless of the attachment's **PidTagAttachEncoding** property ([\[MS-OXCMSG\]](#) section 2.2.2.20) value. However, if the **PidTagAttachEncoding** property ([\[MS-OXCMSG\]](#) section 2.2.2.20) for the attachment consists of bytes %x2A.86.48.86.F7.14.03.0B.01, then the **FileDataMacBinary** bit MAY **<5>** be set by the TNEF Writer; otherwise the **FileDataDefault** field SHOULD be set by the TNEF Writer.

### 2.2.3.11 attOwner Attribute Handling by the TNEF Writer

If the message is either a meeting request or meeting cancellation (from the organizer, who is creating or deleting a meeting), the TNEF Writer SHOULD encode the **PidTagSentRepresenting\_XXX** properties, as specified in section [2.1.3.1.1](#), in the **attOwner** attribute, as specified in section [2.1.3.3.16](#).

If the message is a meeting response of any type (from attendee, accepting, declining, and so on), the TNEF Writer SHOULD encode the **PidTagReceivedRepresenting\_XXX** properties, as specified in section [2.1.3.1.1](#), in the **attOwner** attribute. The encoding used is implementation-dependent. For details about how to construct the **EntryId** property, see [\[MS-OXOMSG\]](#) section 2.2.1.25.

The TNEF Writer can use the discrete **PidTag{Sent | Rcvd}Representing Name, AddressType,** and **EmailAddress** properties if present, or access their values by using the **PidTag{Sent | Rcvd}EntryId** property.

### 2.2.3.12 attSentFor Attribute Handling by the TNEF Writer

The TNEF Writer SHOULD encode the **PidTagSentRepresenting\_XXX** properties, as specified in section [2.1.3.1.1](#), in the **attSentFor** attribute, as specified in section [2.1.3.3.17](#).

The TNEF Writer can use the discrete **PidTagSentRepresentingName** ([\[MS-OXOMSG\]](#) section 2.2.1.57), **PidTagSentRepresentingAddressType** ([\[MS-OXOMSG\]](#) section 2.2.1.54), and **PidTagSentRepresentingEmailAddress** ([\[MS-OXOMSG\]](#) section 2.2.1.55) properties if present, or access their values by using the **PidTagSentRepresentingEntryId** property ([\[MS-OXOMSG\]](#) section 2.2.1.56).

### 2.2.3.13 attDelegate Attribute Handling by the TNEF Writer

The TNEF Writer SHOULD encode the **PidTagReceivedRepresentingEntryId** properties, as specified in [\[MS-OXOMSG\]](#) section 2.2.1.25, in the **attDelegate** attribute, as specified in section [2.1.3.3.18](#).

### 2.2.3.14 attMsgProps Attribute Handling by the TNEF Writer

The TNEF Writer SHOULD write the **attMsgProps** attribute, as specified in section [2.1.3.3.21](#), after all the other message attributes and immediately before all the attachment attributes. For a description of the encoding for this attribute, see section [2.1.3.4](#).

### 2.2.3.15 attAttachment Attribute Handling by the TNEF Writer

The TNEF Writer SHOULD write the encapsulated **attAttachment** attribute, as specified in section [2.1.3.3.23](#), after all the attributes for an attachment.

### 2.2.3.16 attRecipTable Attribute Handling by the TNEF Writer

When TNEF is being used to encode an attached message, recipient (1) information from the **attRecipTable** attribute, as specified in section [2.1.3.3.22](#), is used to populate the received message recipient (1) table.

## 2.3 TNEF Reader Algorithm Details

The TNEF Reader decodes a TNEF stream after receiving a message, for the purpose of reconstructing the rich properties that are contained in the stream. This section specifies details specific to the TNEF Reader role.

For details common to both the TNEF Reader and TNEF Writer roles, see section [2.1](#).

### 2.3.1 Abstract Data Model

None.

### 2.3.2 Initialization

None.

### 2.3.3 Processing Rules

This section specifies the processing rules applied by the TNEF Reader to specific TNEF attributes. For processing rules common to the TNEF Writer and the TNEF Reader, see section [2.1.3.3](#).

#### 2.3.3.1 attTnefVersion Attribute Handling by the TNEF Reader

The TNEF Reader MUST reject values other than %x00.00.01.00 for the **attTnefVersion** attribute, as specified in section [2.1.3.3.1](#).

#### 2.3.3.2 attOemCodepage Attribute Handling by the TNEF Reader

When performing ANSI string decoding from the TNEF stream, the TNEF Reader uses the first code page determined from the following sources:

1. Any non-US-ASCII MIME character set (2), if the stream was transmitted as a MIME body part and the character set (2) name is available in MIME, mapped to the most appropriate code page that does not allow embedded zero bytes other than a zero terminator.
2. The **attOemCodepage** attribute, as specified in section [2.1.3.3.2](#), if available and nonzero.
3. The **PidTagInternetCodepage** property ([\[MS-OXCMSG\]](#) section 2.2.1.56.6), if available in the encapsulated properties, mapped to the most appropriate code page that does not allow embedded zero bytes other than a null terminator.
4. The most appropriate default code page for the processing environment.

#### 2.3.3.3 attFrom Attribute Handling by the TNEF Reader

When reading the **sender-email** field of the **attFrom** attribute, as specified in section [2.1.3.3.3](#), the TNEF Reader MUST set the **PidTagSenderEntryId** property ([\[MS-OXOMSG\]](#) section 2.2.1.50) and SHOULD decode the **attFrom** attribute into the other **PidTagSender\_XXX** properties, as specified in section [2.1.3.1.1](#).

#### 2.3.3.4 attMessageClass Attribute Handling by the TNEF Reader

If the **attMessageClass** or **attOriginalMessageClass** attribute, as specified in section [2.1.3.3.5](#), contains a value that is shown in the Attribute value column of the following table, the value that MUST be returned is that of the value in the Message property value column.

| Attribute value (in TNEF)       | Message property value |
|---------------------------------|------------------------|
| IPM.Microsoft Mail.Note         | IPM.Note               |
| IPM.Microsoft Mail.Read Receipt | Report.IPM.Note.IPNRN  |

| Attribute value (in TNEF)       | Message property value         |
|---------------------------------|--------------------------------|
| IPM.Microsoft Mail.Non-Delivery | Report.IPM.Note.NDR            |
| IPM.Microsoft Schedule.MtgRespP | IPM.Schedule.Meeting.Resp.Pos  |
| IPM.Microsoft Schedule.MtgRespN | IPM.Schedule.Meeting.Resp.Neg  |
| IPM.Microsoft Schedule.MtgRespA | IPM.Schedule.Meeting.Resp.Tent |
| IPM.Microsoft Schedule.MtgReq   | IPM.Schedule.Meeting.Request   |
| IPM.Microsoft Schedule.MtgCncl  | IPM.Schedule.Meeting.Canceled  |

Values not included in the table SHOULD be read in their original form.

If the value of the **attMessageClass** or **attOriginalMessageClass** attribute begins with the string "Microsoft Mail v3.0 ", the TNEF Reader MUST ignore the "Microsoft Mail v3.0 " prefix when attempting to match the value of the **attMessageClass** or **attOriginalMessageClass** attribute to a value in the Attribute Value column. For example, the TNEF Reader considers the value of the **attMessageClass** or **attOriginalMessageClass** attribute Microsoft Mail v3.0 IPM.Microsoft.Mail.Note to be the same as IPM.Microsoft.Mail.Note, which corresponds to the Message Property Value IPM.Note.

The TNEF Reader SHOULD ignore the checksum value for message class attributes because some legacy TNEF Writers generated non-valid checksum values.

### 2.3.3.5 attMessageID Attribute Handling by the TNEF Reader

When reading the **attMessageID** attribute, as specified in section [2.1.3.3.6](#), from TNEF, the TNEF Reader SHOULD attempt to decode the text format back into binary format.

### 2.3.3.6 attSubject Attribute Handling by the TNEF Reader

When the TNEF stream is being decoded, if the **attSubject** attribute, as specified in section [2.1.3.3.7](#), is present, it is used for the message if there is no MIME structure, if a MIME subject is not available, or if an attached message is being decoded.

### 2.3.3.7 attAttachData Attribute Handling by the TNEF Reader

If the **PidTagAttachMethod** property ([\[MS-OXCMSG\]](#) section 2.2.2.9) of the original attachment contains the value 0x0005 (ATTACH\_EMBEDDED\_MSG) or the value 0x0006 (ATTACH\_OLE), then the TNEF Reader SHOULD ignore the **attAttachData** attribute, as specified in section [2.1.3.3.11](#).

### 2.3.3.8 attAttachTitle Attribute Handling by the TNEF Reader

The TNEF Reader always sets the value of the **PidTagAttachLongFilename** property ([\[MS-OXCMSG\]](#) section 2.2.2.10), which maps to the **attAttachTitle** attribute, as specified in section [2.1.3.3.12](#).

### 2.3.3.9 attAttachRendData Attribute Handling by the TNEF Reader

The TNEF Reader SHOULD set the **PidTagAttachTag** property ([\[MS-OXCMSG\]](#) section 2.2.2.15) for the attachment to %x2A.86.48.86.F7.14.03.0A.03.02.01 when the **AttachTypeOle** field of the **attAttachRendData** attribute, as specified in section [2.1.3.3.15](#), is set. The TNEF Reader SHOULD

NOT set the **PidTagAttachTag** property for the attachment when **AttachTypeFile** field of the **attAttachRendData** attribute is set.

The TNEF Reader SHOULD set the value of the **PidTagAttachEncoding** property ([\[MS-OXCMSG\]](#) section 2.2.2.20) for the attachment to the same bytes when the **DataFlags** field of the **attAttachRendData** attribute has the **FileDataMacBinary** bit set. If the **DataFlags** field contains the value of **FileDataDefault**, then the TNEF Reader SHOULD NOT set the value of the **PidTagAttachEncoding** property for the attachment.

### 2.3.3.10 attOwner Attribute Handling by the TNEF Reader

If the message is either a meeting request or meeting cancellation (from the organizer, who is creating or deleting a meeting), the TNEF Reader SHOULD decode the **attOwner** attribute, as specified in section [2.1.3.3.16](#), into the **PidTagSentRepresenting\_XXX** properties, as specified in section [2.1.3.1.1](#).

If the message is a meeting response of any type (from attendee, accepting, declining, and so on), the TNEF Reader SHOULD decode the **attOwner** attribute into the **PidTagReceivedRepresenting\_XXX** properties, as specified in section [2.1.3.1.1](#). The decoding process used is implementation-dependent, as long as the decoded property values match those that were originally encoded. For details about how to construct the **PidTagReceivedRepresentingEntryId** property, see [\[MS-OXOMSG\]](#) section 2.2.1.25.

The TNEF Reader MUST set the **PidTag{Sent | Rcvd} EntryId** property and SHOULD decode the **attOwner** attribute into the other **PidTag{Sent | Rcvd} Representing** properties.

### 2.3.3.11 attSentFor Attribute Handling by the TNEF Reader

The TNEF Reader SHOULD decode the **attSentFor** attribute, as specified in section [2.1.3.3.17](#), into the **PidTagSentRepresenting\_XXX** properties, as specified in section [2.1.3.1.1](#).

The TNEF Reader SHOULD set the **PidTagSentRepresentingEntryId** property ([\[MS-OXOMSG\]](#) section 2.2.1.56) and SHOULD decode the **attOwner** attribute, as specified in section [2.1.3.3.16](#), into the other **PidTagSentRepresenting\_XXX** properties.

### 2.3.3.12 attDelegate Attribute Handling by the TNEF Reader

The TNEF Reader SHOULD decode the **attDelegate** attribute, as specified in section [2.1.3.3.18](#), into the **PidTagReceivedRepresentingEntryId** properties ([\[MS-OXOMSG\]](#) section 2.2.1.25).

## 3 Algorithm Examples

### 3.1 Sample Message

| Explanation of content                                       | Byte stream   |
|--|---|
| TNEF Signature, Value=0x223E9F78                             | 78 9f 3e 22   |
| Attach Key, Value=0x0001                                     | 01 00   |
| Message attribute, <b>attTnefVersion</b><br>Length=4 bytes   | 01 06 90 08 00<br>04 00 00 00   |
| Data=0x00010000  | 00 00 01 00   |
| Checksum=0x0001  | 01 00   |
| Message attribute, <b>attOemCodepage</b><br>Length=8 bytes   | 01 07 90 06 00<br>08 00 00 00   |
| Data= (Primary=1252, Secondary=0)                            | e4 04 00 00 00 00 00 00   |
| Checksum=0x00E8  | e8 00   |
| Message attribute, <b>attMessageClass</b><br>Length=24 bytes | 01 08 80 07 00<br>18 00 00 00   |
| Data="IPM.Microsoft Mail.Note" %x00                          | 49 50 4d 2e 4d 69 63 72 6f 73<br>6f 66 74 20 4d 61 69 6c 2e 4e<br>6f 74 65 00 |
| Checksum=0x0831  | 31 08   |
| Message attribute, <b>attPriority</b><br>Length=2 bytes      | 01 0d 80 04 00<br>02 00 00 00   |
| Data=0x0002 (Normal Priority)                                | 02 00   |
| Checksum=0x0002  | 02 00   |
| Message attribute, <b>attSubject</b><br>Length=15 bytes      | 01 04 80 01 00<br>0f 00 00 00   |
| Data="Simple subject" %x00                                   | 53 69 6d 70 6c 65 20 73 75 62 6a 65<br>63 74 00                               |

| Explanation of content   | Byte stream   |
|--|---|
| Checksum=0x057A  | 7a 05   |
| Message attribute, <b>attDateSent</b><br>Length=14 bytes   | 01 05 80 03 00<br>0e 00 00 00   |
| Data= Tuesday, 02/17/2004, 11:25:35  | d4 07 02 00 11 00 0b 00 19 00 23 00<br>02 00  |
| Checksum=0x0137  | 37 01   |
| Message attribute, <b>attDateModified</b><br>Length=14 bytes   | 01 20 80 03 00<br>0e 00 00 00   |
| Data= Tuesday, 02/17/2004, 12:26:09  | D4 07 02 00 11 00 0c 00 -- 1a 00 09<br>00 02 00   |
| Checksum=0x011F  | 1f 01   |
| Message attribute, <b>attMessageID</b><br>Length=33 bytes  | 01 09 80 01 00<br>21 00 00 00   |
| Data= "757BB19CDE936A4087D90BB784C58E3B"   | 37 35 37 42 42 31 39 43 44 45<br>39 33 36 41 34 30 38 37 44 39<br>30 42 42 37 38 34 43 35 38 45<br>33 42 00 |
| Checksum=0x0751  | 51 07   |
| Message attribute, Encapsulation, <b>attMsgProps</b><br>Length=2256 bytes<br>Number of properties=70                                   | 01 03 90 06 00<br>d0 08 00 00<br>46 00 00 00  |
| Message property, <b>PidTagAlternateRecipientAllowed</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.36)<br>Value=1 (TRUE)             | 0b 00 02 00<br>01 00 00 00  |
| Message property, <b>PidTagPriority</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.12)<br>Value=0 (LOW)                               | 03 00 26 00<br>00 00 00 00  |
| Message property, <b>PidTagSensitivity</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.13)<br>Value=0 (LOW)                            | 03 00 36 00<br>00 00 00 00  |
| Message property, <b>PidTagClientSubmitTime</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.3.11)<br>Value=Tuesday, 02/17/2004, 19:25:35 | 40 00 39 00<br>AA D6 F3 D0 8B F5 C3 01  |

| Explanation of content   | Byte stream  |
|--|--|
| Message property, <b>PidTagSubjectPrefix</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.60)<br>Number of property values=1<br>Size of first property=1                    | 1e 00 3d 00<br>01 00 00 00<br>01 00 00 00  |
| Value = %x00   | 00   |
| Pad=3 bytes  | 00 00 00   |
| Message property, <b>PidTagReceivedByEntryId</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.38)<br>Number of property values=1<br>Size of first property=107              | 02 01 3f 00<br>01 00 00 00<br>6b 00 00 00  |
|  | 00 00 00 00 DC A7 40 C8 C0 42 10 1A<br>B4 B9 08 00<br>2B 2F E1 82 01 00 00 00 00 00 00 00<br>2F 4F 3D 46<br>49 52 53 54 20 4F 52 47 41 4E 49 5A<br>41 54 49 4F<br>4E 2F 4F 55 3D 46 49 52 53 54 20 41<br>44 4D 49 4E<br>49 53 54 52 41 54 49 56 45 20 47 52<br>4F 55 50 2F<br>43 4E 3D 52 45 43 49 50 49 45 4E 54<br>53 2F 43 4E<br>3D 54 45 53 54 32 31 55 57 32 00 |
| Pad=1 byte   | 00   |
| Message property, <b>PidTagReceivedByName</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.39)<br>Number of property values=1<br>Size of first property=10                  | 1e 00 40 00<br>01 00 00 00<br>0a 00 00 00  |
| Value="Test21uw2" %x00   | 54 65 73 74 32 31 75 77 32 00  |
| Pad=2 bytes  | 00 00  |
| Message property,<br><b>PidTagReceivedRepresentingEntryId</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.25)<br>Number of property values=1<br>Size of first property=107 | 02 01 43 00<br>01 00 00 00<br>6b 00 00 00  |
|  | 00 00 00 00 DC A7 40 C8 C0 42 10 1A<br>B4 B9 08 00 2B 2F E1 82 01 00 00 00<br>00 00 00 00 2F 4F 3D 46 49 52 53 54<br>20 4F 52 47 41 4E 49 5A 41 54 49 4F<br>4E 2F 4F 55 3D 46 49 52 53 54 20 41<br>44 4D 49 4E 49 53 54 52 41 54 49 56   |



| Explanation of content   | Byte stream   |
|--|---|
|  | 45 20 47 52 4F 55 50 2F 43 4E 3D 52<br>45 43 49 50 49 45 4E 54 53 2F 43 4E<br>3D 54 45 53 54 32 31 55 57 32 00  |
| Pad=1 byte   | 00  |
| Message property, <b>PidTagReceivedRepresentingName</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.26)<br>Number of property values=1<br>Size of first property=10      | 1e 00 44 00 01 00 00 00 0a 00 00 00   |
| Value="Test21uw2" %x00   | 54 65 73 74 32 31 75 77 32 00   |
| Pad=2 bytes  | 00 00   |
| Message property, <b>PidTagMessageSubmissionId</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.79)<br>Number of property values=1<br>Size of first property=57           | 02 01 47 00 01 00 00 00 39 00 00 00   |
|  | 63 3D 55 53 3B 61 3D 20 3B 70 3D 46<br>69 72 73 74 20 4F 72 67 61 6E 69 7A<br>61 74 69 3B 6C 3D 4A 45 53 45 4F 47<br>50 55 57 32 2D 30 34 30 32 31 37 31<br>39 32 35 33 35 5A 2D 32 00  |
| Pad=3 bytes  | 00 00 00  |
| Message property, <b>PidTagReceivedBySearchKey</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.40)<br>Number of property values=1<br>Size of first property=82           | 02 01 51 00 01 00 00 00 52 00 00 00   |
|  | 45 58 3A 2F 4F 3D 46 49 52 53 54 20<br>4F 52 47 41 4E 49 5A 41 54 49 4F 4E<br>2F 4F 55 3D 46 49 52 53 54 20 41 44<br>4D 49 4E 49 53 54 52 41 54 49 56 45<br>20 47 52 4F 55 50 2F 43 4E 3D 52 45<br>43 49 50 49 45 4E 54 53 2F 43 4E 3D<br>54 45 53 54 32 31 55 57 32 00 |
| Pad=2 bytes  | 00 00   |
| Message property, <b>PidTagReceivedRepresentingSearchKey</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.27)<br>Number of property values=1<br>Size of first property=82 | 02 01 52 00 01 00 00 00 52 00 00 00   |
|  | 45 58 3A 2F 4F 3D 46 49 52 53 54 20   |

| Explanation of content  | Byte stream  |
|---|--|
|   | 4F 52 47 41 4E 49 5A 41 54 49 4F 4E<br>2F 4F 55 3D 46 49 52 53 54 20 41 44<br>4D 49 4E 49 53 54 52 41 54 49 56 45<br>20 47 52 4F 55 50 2F 43 4E 3D 52 45<br>43 49 50 49 45 4E 54 53 2F 43 4E 3D<br>54 45 53 54 32 31 55 57 32 00 |
| Pad=2 bytes   | 00 00  |
| Message property, <b>PidTagMessageToMe</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.17)<br>Value=1 (TRUE)  | 0b 00 00 57 01 00 00 00  |
| Message property, <b>PidTagMessageCcMe</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.18)<br>Value=0 (FALSE)   | 0b 00 00 58 00 00 00 00  |
| Message property <b>PidTagMessageRecipientMe</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.19)<br>Value=1 (TRUE)  | 0b 00 00 59 01 00 00 00  |
| Message property, <b>PidTagConversationTopic</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.5)<br>Number of property values=1<br>Size of first property=15     | 1e 00 70 00 01 00 00 00 0f 00 00 00  |
| Value="Simple subject" %x00   | 53 69 6D 70 6C 65 20 73 75 62 6A 65<br>63 74 00  |
| Pad=1 byte  | 00   |
| Message property, <b>PidTagConversationIndex</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.3)<br>Number of property values=1<br>Size of first property=22     | 02 01 71 00 01 00 00 00 16 00 00 00  |
|   | 01 C3 F5 8B 07 63 76 8D 89 1B D0 79<br>47 C9 8F 66 4E 21 9A D2 4A F2   |
| Pad=2 bytes   | 00 00  |
| Message property, <b>PidTagReceivedByAddressType</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.36)<br>Number of property values=1<br>Size of first property=5 | 1e 00 75 00 01 00 00 00 05 00 00 00  |
| Value="SMTP" %x00   | 53 4d 54 50 00   |
| Pad=3 bytes   | 00 00 00   |

| Explanation of content  | Byte stream  |
|---|--|
| Message property, <b>PidTagReceivedByEmailAddress</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.37)<br>Number of property values=1<br>Size of first property=40           | 1e 00 76 00 01 00 00 00 28 00 00 00  |
| Value="Test21uw2@mydomuw2.extest.microsoft.com" %x00  | 54 65 73 74 32 31 75 77 32 40 6D 79<br>64 6F 6D 75 77 32 2E 65 78 74 65 73<br>74 2E 6D 69 63 72 6F 73 6F 66 74 2E<br>63 6F 6D 00 |
| Message property, <b>PidTagReceivedRepresentingAddressType</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.23)<br>Number of property values=1<br>Size of first property=5   | 1e 00 77 00 01 00 00 00 05 00 00 00  |
| Value="SMTP" %x00   | 53 4d 54 50 00   |
| Pad=3 bytes   | 00 00 00   |
| Message property, <b>PidTagReceivedRepresentingEmailAddress</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.24)<br>Number of property values=1<br>Size of first property=40 | 1e 00 78 00 01 00 00 00 28 00 00 00  |
| Value="Test21uw2@mydomuw2.extest.microsoft.com" %x00  | 54 65 73 74 32 31 75 77 32 40 6D 79<br>64 6F 6D 75 77 32 2E 65 78 74 65 73<br>74 2E 6D 69 63 72 6F 73 6F 66 74 2E<br>63 6F 6D 00 |
| Message property, <b>PidTagSenderName</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.51)<br>Number of property values=1<br>Size of first property=10                       | 1e 00 1A 0C 01 00 00 00 0a 00 00 00  |
| Value="Test21uw2" %x00  | 54 65 73 74 32 31 75 77 32 00  |
| Pad=2 bytes   | 00 00  |
| Message property, <b>PidTagNormalizedSubject</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.10)<br>Number of property values=1<br>Size of first property=15                | 1e 00 1D 0E 01 00 00 00 0f 00 00 00  |
| Value="Simple subject" %x00   | 53 69 6D 70 6C 65 20 73 75 62 6A 65<br>63 74 00  |
| Pad=1 byte  | 00   |

| Explanation of content   | Byte stream   |
|--|---|
| Message property, <b>PidTagRtfCompressed</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.56.4)<br>Number of property values=1<br>Size of first property=150  | 02 01 09 10 01 00 00 00 96 00 00 00   |
|  | 92 00 00 00 AB 00 00 00 4C 5A 46 75<br>A8 14 2F 17 03 00 0A 00 72 63 70 67<br>31 32 35 16 32 00 F8 0B 60 6E 0E 10<br>30 33 33 4F 01 F7 02 A4 03 E3 02 00<br>63 68 0A C0 73 B0 65 74 30 20 07 13<br>02 80 7D 0A 80 9D 00 00 2A 09 B0 09<br>F0 04 90 61 74 05 B1 1A 52 0D E0 68<br>09 80 01 D0 20 35 2E 30 35 30 2E 33<br>13 B0 01 D0 30 32 49 02 80 5C 76 08<br>90 77 6B 0B 80 64 FA 34 0C 60 63 00<br>50 0B 03 0B B5 06 00 07 70 C9 0B 50<br>65 20 07 81 73 61 12 50 0A A2 0B 0A<br>80 11 E1 00 17 A0 |
| Pad=2 bytes  | 00 00   |
| Message property, <b>PidTagInternetMessageId</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.12)<br>Number of property values=1<br>Size of first property=80 | 1e 00 35 10 01 00 00 00 50 00 00 00   |
| Value="<2896107D7E52DF4DB5D10536D<br>BFEFAD07E37@jeseogpuw2.mydomuw2.<br>extest.microsoft.com>" %x00   | 3C 32 38 39 36 31 30 37 44 37 45 35<br>32 44 46 34 44 42 35 44 31 30 35 33<br>36 44 42 46 45 46 41 44 30 37 45 33<br>37 40 6A 65 73 65 6F 67 70 75 77 32<br>2E 6D 79 64 6F 6D 75 77 32 2E 65 78<br>74 65 73 74 2E 6D 69 63 72 6F 73 6F<br>66 74 2E 63 6F 6D 3E 00   |
| Message property, <b>PidTagIconIndex</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.10)<br>Value=0xFFFFFFFF   | 03 00 80 10 ff ff ff ff   |
| Unspecified <b>PtypBinary</b> property<br>Number of property values=1<br>Size of first property=40   | 02 01 f0 10 01 00 00 00 28 00 00 00   |
|  | 03 00 00 00 01 00 00 00 01 00 00 00<br>01 00 00 00 01 00 00 00 08 00 00 00<br>DB 11 00 00 49 53 4F 2D 38 38 35 39<br>2D 31 00 00  |
| Unspecified property<br>Number of property values=1<br>Size of first property=38   | 1f 00 f3 10 01 00 00 00 26 00 00 00   |
| Value="Simple subject.EML" %x00.00 (Unicode)   | 53 00 69 00 6D 00 70 00 6C 00 65 00<br>20 00 73 00 75 00 62 00 6A 00 65 00<br>63 00 74 00 2E 00 45 00 4D 00 4C 00   |

| Explanation of content   | Byte stream   |
|--|---|
|  | 00 00   |
| Pad=2 bytes  | 00 00   |
| Message property, <b>PidTagAttributeHidden</b> ( <a href="#">[MS-OXCFOOLD]</a> section 2.2.2.2.2.1)<br>Value=0 (FALSE)                                     | 0b 00 f4 10 00 00 00 00   |
| Unspecified <b>PtypBoolean</b> ( <a href="#">[MS-OXCADATA]</a> section 2.11.1) property<br>Value=0 (FALSE)   | 0b 00 f5 10 00 00 00 00   |
| Message property, <b>PidTagAttributeReadOnly</b> ( <a href="#">[MS-OXPROPS]</a> section 2.603)<br>Value=0 (FALSE)  | 0b 00 f6 10 00 00 00 00   |
| Message property, <b>PidTagCreationTime</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.2.3)<br>Value=Tuesday, 02/17/2004, 20:26:09                          | 40 00 07 30 90 24 46 47 94 f5 c3 01   |
| Message property, <b>PidTagLastModificationTime</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.2.2)<br>Value=Tuesday, 02/17/2004, 20:26:09                  | 40 00 08 30 90 24 46 47 94 f5 c3 01   |
| Message property, <b>PidTagInternetCodepage</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.56.6)<br>Value=(Primary=1252, Secondary=0)                     | 03 00 de 3f e4 04 00 00   |
| Message property, <b>PidTagMessageLocaleId</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.5)<br>Value=(Primary=1033, Secondary=0)                         | 03 00 f1 3f 09 04 00 00   |
| Message property, <b>PidTagCreatorName</b> ( <a href="#">[MS-OXPROPS]</a> section 2.647)<br>Number of property values=1<br>Size of first property=10       | 1e 00 f8 3f 01 00 00 00 0a 00 00 00   |
| Value="Test21uw2" %x00   | 54 65 73 74 32 31 75 77 32 00   |
| Pad=2 bytes  | 00 00   |
| Message property, <b>PidTagCreatorEntryId</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.31)<br>Number of property values=1<br>Size of first property=107 | 02 01 F9 3F 01 00 00 00 6b 00 00 00   |
|  | 00 00 00 00 DC A7 40 C8 C0 42 10 1A<br>B4 B9 08 00 2B 2F E1 82 01 00 00 00<br>00 00 00 00 2F 4F 3D 46 49 52 53 54<br>20 4F 52 47 41 4E 49 5A 41 54 49 4F<br>4E 2F 4F 55 3D 46 49 52 53 54 20 41<br>44 4D 49 4E 49 53 54 52 41 54 49 56<br>45 20 47 52 4F 55 50 2F 43 4E 3D 52 |

| Explanation of content  | Byte stream  |
|---|--|
|   | 45 43 49 50 49 45 4E 54 53 2F 43 4E<br>3D 54 45 53 54 32 31 55 57 32 00  |
| Pad=1 byte  | 00   |
| Message property, <b>PidTagLastModifierName</b> ( <a href="#">[MS-OXCPRPT]</a> section 2.2.1.5)<br>Number of property values=1<br>Size of first property=10     | 1e 00 fa 3f 01 00 00 00 0a 00 00 00  |
| Value="Test21uw2" %x00  | 54 65 73 74 32 31 75 77 32 00  |
| Pad=2 bytes   | 00 00  |
| Message property, <b>PidTagLastModifierEntryId</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.32)<br>Number of property values=1<br>Size of first property=107 | 02 01 FB 3F 01 00 00 006b 00 00 00   |
|   | 00 00 00 00 DC A7 40 C8 C0 42 10 1A<br>B4 B9 08 00 2B 2F E1 82 01 00 00 00<br>00 00 00 00 2F 4F 3D 46 49 52 53 54<br>20 4F 52 47 41 4E 49 5A 41 54 49 4F<br>4E 2F 4F 55 3D 46 49 52 53 54 20 41<br>44 4D 49 4E 49 53 54 52 41 54 49 56<br>45 20 47 52 4F 55 50 2F 43 4E 3D 52<br>45 43 49 50 49 45 4E 54 53 2F 43 4E<br>3D 54 45 53 54 32 31 55 57 32 00 |
| Pad=1 byte  | 00   |
| Message property, <b>PidTagMessageCodepage</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.4)<br>Value=(Primary=1252, Secondary=0)                              | 03 00 fd 3f e4 04 00 00  |
| Unspecified message property<br>Value=0   | 03 00 19 40 00 00 00 00  |
| Message property, <b>PidTagSentRepresentingFlags</b> ( <a href="#">[MS-OXPROPS]</a> section 2.1004)<br>Value=0  | 03 00 1A 40 00 00 00 00  |
| Unspecified message property<br>Value=0   | 03 00 1B 40 00 00 00 00  |
| Unspecified message property,<br>Value=0  | 03 00 1C 40 00 00 00 00  |
| Unspecified <b>PtypString</b> ( <a href="#">[MS-OXCDATA]</a> section 2.11.1)<br>property<br>Number of property values=1   | 1e 00 30 40 01 00 00 00 0a 00 00 00  |

| Explanation of content   | Byte stream                         |
|--|-------------------------------------|
| Size of first property=10  |                                     |
| Value="Test21uw2" %x00   | 54 65 73 74 32 31 75 77 32 00       |
| Pad=2 bytes  | 00 00                               |
| Unspecified <b>PtypString</b> property<br>Number of property values=1<br>Size of first property=10 | 1e 00 31 40 01 00 00 00 0a 00 00 00 |
| Value="Test21uw2" %x00   | 54 65 73 74 32 31 75 77 32 00       |
| Pad=2 bytes  | 00 00                               |
| Unspecified <b>PtypString</b> property<br>Number of property values=1<br>Size of first property=10 | 1e 00 34 40 01 00 00 00 0a 00 00 00 |
| Value="Test21uw2" %x00   | 54 65 73 74 32 31 75 77 32 00       |
| Pad=2 bytes  | 00 00                               |
| Unspecified <b>PtypString</b> property<br>Number of property values=1<br>Size of first property=10 | 1e 00 35 40 01 00 00 00 0a 00 00 00 |
| Value="Test21uw2" %x00   | 54 65 73 74 32 31 75 77 32 00       |
| Pad=2 bytes  | 00 00                               |
| Unspecified <b>PtypString</b> property<br>Number of property values=1<br>Size of first property=10 | 1e 00 38 40 01 00 00 00 0a 00 00 00 |
| Value="Test21uw2" %x00   | 54 65 73 74 32 31 75 77 32 00       |
| Pad=2 bytes  | 00 00                               |
| Unspecified <b>PtypString</b> property<br>Number of property values=1<br>Size of first property=10 | 1e 00 39 40 01 00 00 00 0a 00 00 00 |
| Value="Test21uw2" %x00   | 54 65 73 74 32 31 75 77 32 00       |
| Pad=2 bytes  | 00 00                               |

| Explanation of content   | Byte stream   |
|--|---|
| Message property, <b>PidTagContentFilterSpamConfidenceLevel</b> ( <a href="#">[MS-OXCSPAM]</a> section 2.2.1.3)<br>Value=0xFFFFFFFF  | 03 00 76 40 ff ff ff ff   |
| Message property, <b>PidTagMessageEditorFormat</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.78)<br>Value=0x00000003   | 03 00 09 59 03 00 00 00   |
| Message property, <b>PidTagTnefCorrelationKey</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.29)<br>Number of property values=1<br>Size of first property=12  | 02 01 7f 00 01 00 00 00 0c 00 00 00   |
|  | 38 71 6b 6a 30 30 73 67 6d 34 66 00   |
| Message property, <b>PidLidAgingDontAgeMe</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.33)<br>PSETID_Common, MNID_ID,<br>Id=0x850E<br>Value=0   | 0b 00 87 81 08 20 06 00 00 00 00 00<br>c0 00 00 00 00 00 00 46 00 00 00 00<br>0e 85 00 00 00 00 00 00             |
| Message property, <b>PidLidCurrentVersion</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.34)<br>PSETID_Common, MNID_ID,<br>Id=0x8552<br>Value=115608  | 03 00 9f 81 08 20 06 00 00 00 00 00<br>c0 00 00 00 00 00 00 46 00 00 00 00<br>52 85 00 00 98 c3 01 00             |
| Message property, <b>PidLidCurrentVersionName</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.35)<br>PSETID_Common, MNID_ID,<br>Id=0x8554<br>Number of property values=1<br>Size of first property=5 | 1E 00 A0 81 08 20 06 00 00 00 00 00<br>c0 00 00 00 00 00 00 46 00 00 00 00<br>54 85 00 00 01 00 00 00 05 00 00 00 |
| Value="11.0" %x00  | 31 31 2E 30 00  |
| Pad=3 bytes  | 00 00 00  |
| Message property, <b>PidLidReminderDelta</b> ( <a href="#">[MS-OXORMDR]</a> section 2.2.1.3)<br>PSETID_Common, MNID_ID,<br>Id=0x8501<br>Value=0  | 03 00 eb 81 08 20 06 00 00 00 00 00<br>c0 00 00 00 00 00 00 46 00 00 00 00<br>01 85 00 00 00 00 00 00             |
| Message property, <b>PidLidReminderSet</b> ( <a href="#">[MS-OXORMDR]</a> section 2.2.1.1)<br>PSETID_Common, MNID_ID,<br>Id=0x8503<br>Value=0 (FALSE)  | 0b 00 f0 81 08 20 06 00 00 00 00 00<br>c0 00 00 00 00 00 00 46 00 00 00 00<br>03 85 00 00 00 00 00 00             |



| Explanation of content  | Byte stream   |
|---|---|
| Message property, <b>PidLidSideEffects</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.16)<br>PSETID_Common, MNID_ID,<br>Id=0x8510<br>Value=0     | 03 00 fa 81 08 20 06 00 00 00 00 00<br>c0 00 00 00 00 00 00 46 00 00 00 00<br>10 85 00 00 00 00 00 00 |
| Message property, <b>PidLidTaskMode</b> ( <a href="#">[MS-OXOTASK]</a> section 2.2.2.2.1)<br>PSETID_Common, MNID_ID,<br>Id=0x8518<br>Value=0      | 03 00 01 82 08 20 06 00 00 00 00 00<br>c0 00 00 00 00 00 00 46 00 00 00 00<br>18 85 00 00 00 00 00 00 |
| Message property, <b>PidLidPrivate</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.15)<br>PSETID_Common, MNID_ID,<br>Id=0x8506<br>Value=0 (FALSE) | 0b 00 43 82 08 20 06 00 00 00 00 00<br>c0 00 00 00 00 00 00 46 00 00 00 00<br>06 85 00 00 00 00 00 00 |
| Message property, <b>PidLidUseTnef</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.66)<br>PSETID_Common, MNID_ID,<br>Id=0x8582<br>Value=0 (FALSE) | 0b 00 44 82 08 20 06 00 00 00 00 00<br>c0 00 00 00 00 00 00 46 00 00 00 00<br>82 85 00 00 00 00 00 00 |
| Message property, <b>PidTagReadReceiptRequested</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.29)<br>Value=0 (FALSE)                            | 0b 00 29 00 00 00 00 00   |
| Message property, <b>PidTagOriginatorDeliveryReportRequested</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.20)<br>Value=0 (FALSE)               | 0b 00 23 00 00 00 00 00   |
| Unspecified <b>PtypInteger32</b> ( <a href="#">[MS-OXCDATA]</a> section 2.11.1) property<br>Value=0xF00D29FF                                      | 03 00 06 10 ff 29 0d f0   |
| Unspecified <b>PtypInteger32</b> property<br>Value=13   | 03 00 07 10 0d 00 00 00   |
| Unspecified <b>PtypInteger32</b> property<br>Value=0  | 03 00 10 10 00 00 00 00   |
| Unspecified <b>PtypInteger32</b> property<br>Value=0  | 03 00 11 10 00 00 00 00   |
| Unspecified <b>PtypString</b> property<br>Number of property values=1<br>Size of first property=14  | 1e 00 08 10 01 00 00 00 0e 00 00 00   |
| Value="SIMPLEMESSAGE" %x00  | 53 49 4d 50 4c 45 4d 45 53 53 41 47<br>45 00  |

| Explanation of content  | Byte stream   |
|---|---|
| Pad=2 bytes   | 00 00   |
| Message property, <b>PidTagTnefCorrelationKey</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.29)<br>Number of property values=1<br>Size of first property=56 | 02 01 7f 00 01 00 00 00 38 00 00 00   |
|   | 3C 32 38 39 36 31 30 37 44 37 45 35<br>32 44 46 34 44 42 35 44 31 30 35 33<br>36 44 42 46 45 46 41 44 30 37 45 33<br>37 40 75 73 65 72 2E 65 78 61 6D 70<br>6C 65 2E 63 6F 6D 3E 00 |
| Checksum for <b>AttMsgProps</b>   | 45 C1   |

### 3.2 Sample Meeting Response

This example is particularly short, as it was sent by a mobile application.

| Explanation of content                                       | Byte stream  |
|--|--|
| TNEF Signature, Value=0x223E9F78                             | 78 9f 3e 22  |
| Attach Key, Value=0x0001                                     | 01 00  |
| Message attribute, <b>attTnefVersion</b><br>Length=4 bytes   | 01 06 90 08 00 04 00 00 00   |
| Data=0x00010000  | 00 00 01 00  |
| Checksum=0x0001  | 01 00  |
| Message attribute, <b>attOemCodepage</b><br>Length=8 bytes   | 01 07 90 06 00 08 00 00 00   |
| Data= (Primary=1252, Secondary=0)                            | e4 04 00 00 00 00 00 00  |
| Checksum=0x00E8  | e8 00  |
| Message attribute, <b>attMessageClass</b><br>Length=32 bytes | 01 08 80 07 00 20 00 00 00   |
| Data="IPM.Microsoft<br>Schedule.MtgRespN" %x00               | 49 50 4d 2e 4d 69 63 72 6f 73 6f 66 74 20 53 63 68 65<br>64 75 6c 65 2e 4d 74 67 52 65 73 70 4e 00 |
| Checksum=0x0B55  | 55 0b  |

| Explanation of content   | Byte stream   |
|--|---|
| Message attribute, <b>attPriority</b><br>Length=2 bytes  | 01 0d 80 04 00 02 00 00 00  |
| Data=0x0002 (Normal Priority)  | 02 00   |
| Checksum=0x0002  | 02 00   |
| Message attribute, <b>attDateSent</b><br>Length=14 bytes   | 01 05 80 03 00 0e 00 00 00  |
| Data= Wednesday, 01/16/2008,<br>23:28:08   | d8 07 01 00 10 00 17 00 1c 00 08 00 03 00   |
| Checksum=0x012E  | 2e 01   |
| Message attribute, <b>attDateModified</b><br>Length=14 bytes   | 01 20 80 03 000e 00 00 00   |
| Data= Wednesday, 01/16/2008,<br>23:28:08   | d8 07 01 00 10 00 17 00 1c 00 08 00 03 00   |
| Checksum=0x012E  | 2e 01   |
| Message attribute Encapsulation,<br><b>attMsgProps</b><br>Length=136 bytes<br>Number of properties=2   | 01 03 90 06 00 88 00 00 00 02 00 00 00  |
| Message property,<br><b>PidTagTnefCorrelationKey</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.29)<br>Number of property values=1<br>Size of first property=12 | 02 01 7f 00 01 00 00 00 0c 00 00 00   |
|  | 38 71 6b 6a 30 30 73 67 6d 34 66 00   |
| Message property,<br><b>PidTagRtfCompressed</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.56.4)<br>Number of property values=1<br>Size of first property=93    | 02 01 09 10 01 00 00 00 5d 00 00 00   |
|  | 59 00 00 00 b3 00 00 00 4c 5a 46 75 a9 be bb ed 87 00<br>0a 01 0d 03 43 74 65 78 74 01 f7 ff 02 a4 03 e4 05 eb<br>02 83 00 50 02 f3 06 b4 02 83 26 32 03 c5 02 00 63 68<br>0a c0 73 65 d8 74 30 20 07 13 02 80 7d 0a 80 08 cf 3f<br>09 d9 02 80 0a 84 0b 37 12 c2 01 d0 20 46 10 59 49 00<br>7d 18 20 |
| Pad=3 bytes  | 00 00 00  |

| Explanation of content          | Byte stream |
|---------------------------------|-------------|
| Checksum for <b>attMsgProps</b> | f7 21       |

## 4 Security

### 4.1 Security Considerations for Implementers

Extreme care is recommended in the use of the **attRecipTable** attribute and the **attFrom** attribute, particularly by the TNEF Reader, to avoid address or identity spoofing. More information about this can be found in [\[MS-OXCMSG\]](#) and section [2.1.3.5.2](#) of this specification.

### 4.2 Index of Security Parameters

None.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Exchange Server 2003
- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Office Outlook 2003
- Microsoft Office Outlook 2007
- Microsoft Outlook 2010
- Microsoft Outlook 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.3.3.9:](#) Exchange 2003 supports the use of the **attBody** attribute.

[<2> Section 2.1.3.3.18:](#) Exchange 2003 supports the use of the **attDelegate** attribute.

[<3> Section 2.2.3.6:](#) In Exchange 2003, the TNEF Writer writes the **attBody** attribute when TNEF is used to encode an attached message.

[<4> Section 2.2.3.10:](#) In Exchange 2003, the TNEF Writer does not always set the **DataFlags** field to **FileDataDefault**.

[<5> Section 2.2.3.10:](#) In Exchange 2003, the TNEF Writer sets the **FileDataMacBinary** bit if the **PidTagAttachEncoding** property ([\[MS-OXCMSG\]](#) section 2.2.2.20) for the attachment consists of bytes %x2A.86.48.86.F7.14.03.0B.01.

## 6 Change Tracking

This section identifies changes that were made to the [MS-OXTNEF] protocol document between the February 2013 and July 2013 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [protocol@microsoft.com](mailto:protocol@microsoft.com).

| Section                            | Tracking number (if applicable) and description          | Major change (Y or N) | Change type      |
|------------------------------------|--|-----------------------|------------------|
| <a href="#">3.1 Sample Message</a> | Removed the PidTagUrlCompName property from the example. | N                     | Content updated. |



## 7 Index

### A

[Applicability](#) 7

### C

[Change tracking](#) 47

Common

[overview](#) 8

### E

Examples

[Sample Meeting Response](#) 42

[Sample Message](#) 30

### G

[Glossary](#) 5

### I

[Implementer - security considerations](#) 45

[Index of security parameters](#) 45

[Informative references](#) 6

[Introduction](#) 5

### N

[Normative references](#) 6

### O

[Overview \(synopsis\)](#) 7

### P

[Parameters - security index](#) 45

[Product behavior](#) 46

### R

References

[informative](#) 6

[normative](#) 6

### S

[Sample Meeting Response example](#) 42

[Sample Message example](#) 30

Security

[implementer considerations](#) 45

[parameter index](#) 45

[Standards assignments](#) 7

### T

[Tracking changes](#) 47