

# [MS-OXVCARD]: vCard to Contact Object Conversion Algorithm

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.msp>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

| Date       | Revision History | Revision Class | Comments   |
|------------|------------------|----------------|--|
| 04/10/2009 | .1               | Major          | Initial Availability.  |
| 07/15/2009 | 1.0              | Major          | Revised and edited for technical content.                                    |
| 11/04/2009 | 1.0.1            | Editorial      | Revised and edited the technical content.                                    |
| 02/10/2010 | 1.0.1            | None           | Version 1.0.1 release  |
| 05/05/2010 | 1.1.0            | Minor          | Updated the technical content.   |
| 08/04/2010 | 1.2              | Minor          | Clarified the meaning of the technical content.                              |
| 11/03/2010 | 1.3              | Minor          | Clarified the meaning of the technical content.                              |
| 03/18/2011 | 2.0              | Major          | Significantly changed the technical content.                                 |
| 08/05/2011 | 3.0              | Major          | Significantly changed the technical content.                                 |
| 10/07/2011 | 3.0              | No change      | No changes to the meaning, language, or formatting of the technical content. |

# Table of Contents

|  |          |
|--|----------|
| <b>1 Introduction</b>                              | <b>5</b> |
| 1.1 Glossary                                       | 5        |
| 1.2 References                                     | 5        |
| 1.2.1 Normative References                         | 5        |
| 1.2.2 Informative References                       | 6        |
| 1.3 Overview                                       | 6        |
| 1.4 Relationship to Protocols and Other Algorithms | 6        |
| 1.5 Applicability Statement                        | 6        |
| 1.6 Standards Assignments                          | 7        |
| <b>2 Algorithm Details</b>                         | <b>8</b> |
| 2.1 Common Algorithm Details                       | 8        |
| 2.1.1 Abstract Data Model                          | 8        |
| 2.1.2 Initialization                               | 8        |
| 2.1.3 Processing Rules                             | 8        |
| 2.1.3.1 General Types                              | 8        |
| 2.1.3.1.1 Profile: vCard                           | 8        |
| 2.1.3.2 Identification Types                       | 8        |
| 2.1.3.2.1 Type: FN                                 | 8        |
| 2.1.3.2.2 Type: N                                  | 9        |
| 2.1.3.2.3 Type: NICKNAME                           | 9        |
| 2.1.3.2.4 Type: PHOTO                              | 9        |
| 2.1.3.2.5 Type: BDAY                               | 10       |
| 2.1.3.3 Deliverable Addressing Types               | 10       |
| 2.1.3.3.1 Type: ADR                                | 10       |
| 2.1.3.3.2 Type: LABEL                              | 12       |
| 2.1.3.4 Telecommunications Addressing Types        | 13       |
| 2.1.3.4.1 Type: TEL                                | 13       |
| 2.1.3.4.2 Type: EMAIL                              | 14       |
| 2.1.3.4.3 Type: MAILER                             | 15       |
| 2.1.3.5 Geographical Types                         | 15       |
| 2.1.3.5.1 Type: TZ                                 | 15       |
| 2.1.3.5.2 Type: GEO                                | 16       |
| 2.1.3.6 Organizational Types                       | 16       |
| 2.1.3.6.1 Type: TITLE                              | 16       |
| 2.1.3.6.2 Type: ROLE                               | 16       |
| 2.1.3.6.3 Type: LOGO                               | 16       |
| 2.1.3.6.4 Type: AGENT                              | 17       |
| 2.1.3.6.5 Type: ORG                                | 17       |
| 2.1.3.7 Explanatory Types                          | 18       |
| 2.1.3.7.1 Type: CATEGORIES                         | 18       |
| 2.1.3.7.2 Type: NOTE                               | 18       |
| 2.1.3.7.3 Type: PRODIG                             | 18       |
| 2.1.3.7.4 Type: REV                                | 19       |
| 2.1.3.7.5 Type: SORT-STRING                        | 19       |
| 2.1.3.7.6 Type: SOUND                              | 19       |
| 2.1.3.7.7 Type: UID                                | 19       |
| 2.1.3.7.8 Type: URL                                | 20       |
| 2.1.3.7.9 Type: VERSION                            | 20       |
| 2.1.3.8 Security Types                             | 20       |

|            |   |           |
|------------|---|-----------|
| 2.1.3.8.1  | Type: CLASS .....                             | 20        |
| 2.1.3.8.2  | Type: KEY .....                               | 21        |
| 2.1.3.9    | Custom Types .....                            | 21        |
| 2.1.3.9.1  | EBC Design .....                              | 21        |
| 2.1.3.9.2  | Children .....                                | 21        |
| 2.1.3.9.3  | User Text .....                               | 22        |
| 2.1.3.9.4  | Instant Messaging Address .....               | 22        |
| 2.1.3.9.5  | Telephone Numbers.....                        | 22        |
| 2.1.3.9.6  | Anniversary .....                             | 23        |
| 2.1.3.9.7  | Spouse's Name .....                           | 23        |
| 2.1.3.9.8  | Manager's Name .....                          | 23        |
| 2.1.3.9.9  | Assistant's Name.....                         | 24        |
| 2.1.3.9.10 | Free/Busy URL .....                           | 24        |
| 2.1.3.9.11 | Interests .....                               | 24        |
| <b>3</b>   | <b>Algorithm Examples .....</b>               | <b>25</b> |
| 3.1        | Importing a vCard .....                       | 25        |
| 3.2        | Exporting a Contact object.....               | 26        |
| <b>4</b>   | <b>Security.....</b>                          | <b>28</b> |
| 4.1        | Security Considerations for Implementers..... | 28        |
| 4.2        | Index of Security Parameters .....            | 28        |
| <b>5</b>   | <b>Appendix A: Product Behavior .....</b>     | <b>29</b> |
| <b>6</b>   | <b>Change Tracking.....</b>                   | <b>30</b> |
| <b>7</b>   | <b>Index .....</b>                            | <b>31</b> |

# 1 Introduction

The vCard to Contact Object Conversion Algorithm converts vCard data that specifies a directory object for a person or resource that can represent and exchange information about an individual, such as formatted and structured name and delivery addresses, email addresses, multiple telephone numbers, photographs, and audio clips, among other such types of data. Applications can use this algorithm to create vCard data to communicate with other contact systems.

Section 2 of this specification is normative and contains RFC 2119 language. Section 1.6 is also normative but cannot contain RFC 2119 language. All other sections and examples in this specification are informative only.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**common name (CN)**

The following terms are defined in [\[MS-OXGLOS\]](#):

**Attachment object**

**Contact object**

**Message object**

**Multipurpose Internet Mail Extensions (MIME)**

**Uniform Resource Identifier (URI)**

The following terms are specific to this document:

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXCICAL] Microsoft Corporation, "[iCalendar to Appointment Object Conversion Algorithm](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)".

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol Specification](#)".

[MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol Specification](#)".

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)".

[RFC2045] Freed, N., and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", RFC 2045, November 1996, <http://ietf.org/rfc/rfc2045.txt>

[RFC2047] Moore, K., "MIME (Multipurpose Internet Mail Extensions) Part Three: Message Header Extensions for Non-ASCII Text", RFC 2047, November 1996, <http://ietf.org/rfc/rfc2047.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2426] Dawson, F., and Howes, T., "vCard MIME Directory Profile", RFC 2426, September 1998, <http://www.rfc-editor.org/rfc/rfc2426.txt>

[X520] ITU-T, "Information technology - Open Systems Interconnection - The Directory: Selected attribute types", ITU-T Recommendation X.520, August 2005, <http://www.itu.int/rec/T-REC-X.520/en>

## 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXCMAIL] Microsoft Corporation, "[RFC2822 and MIME to E-Mail Object Conversion Algorithm](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[RFC2425] Howes, T., Smith, M., and Dawson, F., "A MIME Content-Type for Directory Information", RFC 2425, September 1998, <http://www.rfc-editor.org/rfc/rfc2425.txt>

## 1.3 Overview

A **Contact object** application, as described in [\[MS-OXOCNTC\]](#), can use this algorithm to import vCard data, as described in [\[RFC2426\]](#), into Contact objects, and also to export Contact objects as vCard data to communicate with other contact applications over non-**Message object** transport methods.

## 1.4 Relationship to Protocols and Other Algorithms

This document specifies an algorithm that maps vCard data, as described in [\[RFC2426\]](#), and a Contact object, as described in [\[MS-OXOCNTC\]](#). This algorithm can be updated and sent by using the protocols described in [\[MS-OXCMSG\]](#) and [\[MS-OXOMSG\]](#).

When used as a contact, vCard data can be embedded as a **Multipurpose Internet Mail Extensions (MIME)** part in an email message, as described in [\[RFC2425\]](#) and [\[MS-OXCMAIL\]](#).

This document covers versioning issues in the following areas:

- **Structure version:** The vCard data format defines a **VERSION** type, as specified in section [2.1.3.7.9](#).
- **Localization:** The vCard data format defines a **SORT-STRING** type to define language-specific sorting rules, as specified in section [2.1.3.7.5](#).

## 1.5 Applicability Statement

This algorithm is applicable to scenarios in which Contact object data needs to be transported between a Contact object source and a non-Contact object or indeterminate destination.

This algorithm is best avoided if 100 percent fidelity is required when transporting contact data between a Contact object source and a Contact object destination.

Note that [\[RFC2426\]](#) section 3.8 permits the insertion of nonstandard private values by using the extension mechanism defined in [\[RFC2045\]](#). The primary requirement of these private values is that the name begins with "x-", and as such they are often termed x-components, x-props, and x-parameters. This document specifies several x-props that provide additional contact information.

## **1.6 Standards Assignments**

None.

## 2 Algorithm Details

### 2.1 Common Algorithm Details

#### 2.1.1 Abstract Data Model

None.

#### 2.1.2 Initialization

None.

#### 2.1.3 Processing Rules

This section specifies the transformations required for converting data from the vCard format to Contact objects.

##### 2.1.3.1 General Types

The type defined in this section signifies that the information is vCard data.

###### 2.1.3.1.1 Profile: vCard

RFC reference: [\[RFC2426\]](#) section 3.

Description: The vCard MIME Directory Profile Type contains directory information, typically about a single directory entry. The information is captured in an attribute schema that is designed for personal contact information.

##### 2.1.3.2 Identification Types

The identification types are used in the vCard profile to capture identification and name information about the person or resource identified by a particular vCard.

###### 2.1.3.2.1 Type: FN

RFC reference: [\[RFC2426\]](#) section 3.1.1.

vCard data format: Name of the vCard object in **common name (CN)** semantics as specified in [\[X520\]](#).

Brief description: Formatted text that corresponds to the name that the vCard represents.

#### Importing to Contact Objects

The **FN** type is imported to the **PidTagDisplayName** ([\[MS-OXOCNTC\]](#) section 2.2.1.1.8), the **PidTagNormalizedSubject** ([\[MS-OXOCNTC\]](#) section 2.2.1.10.1), and the **PidTagConversationTopic** ([\[MS-OXOMSG\]](#) section 2.2.1.5) properties.

#### Exporting from Contact Objects

The **FN** type is generated from either the **PidTagDisplayName** or **PidTagNormalizedSubject** property. If both of these properties are set, the **PidTagDisplayName** property is used.



### 2.1.3.2.2 Type: N

RFC reference: [\[RFC2426\]](#) section 3.1.2.

vCard data format: N:<Family Name>; <Given Name>; <Middle Name>; <Honorific Prefixes>; <Honorific Postfixes>

Brief description: Structured name of the object that the vCard represents.

#### Importing to Contact Objects

Individual text components are separated by the semicolon (;) character. Text components can contain multiple values that are separated by the comma (,) character. The entire text component should be assigned to the corresponding property, as shown in the following table.

| vCard text component | Contact object property | Reference                                      |
|----------------------|-------------------------|--|
| Family Name          | PidTagSurname           | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.1.4 |
| Given Name           | PidTagGivenName         | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.1.6 |
| Middle Name          | PidTagMiddleName        | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.1.5 |
| Honorific Prefixes   | PidTagDisplayNamePrefix | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.1.3 |
| Honorific Postfixes  | PidTagGeneration        | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.1.2 |

#### Exporting from Contact Objects

The **PidTagSurname**, **PidTagGivenName**, **PidTagMiddleName**, **PidTagDisplayNamePrefix**, and **PidTagGeneration** properties are exported as semicolon-delimited strings.

### 2.1.3.2.3 Type: NICKNAME

RFC reference: [\[RFC2426\]](#) section 3.1.3.

vCard data format: NICKNAME: <nickname>

Brief description: The nickname of the object that the vCard represents.

#### Importing to and Exporting from Contact Objects

The **NICKNAME** property is imported to and exported from the **PidTagNickname** ([\[MS-OXOCNTC\]](#) section 2.2.1.1.1) property.

### 2.1.3.2.4 Type: PHOTO

RFC reference: [\[RFC2426\]](#) section 3.1.4.

vCard data format: PHOTO; ENCODING=b; TYPE=<type>:<data>

Brief description: An image or photograph that illustrates some aspect of the object that the vCard represents.

#### Importing to Contact Objects

The binary data for the associated photo is stored as an attachment. For more details about Message object attachments, see [\[MS-OXCMSG\]](#) section 2.2.2. The properties listed in the following table MUST be set on the **Attachment object**, as specified in [\[MS-OXCMSG\]](#).

| Attachment object property          | Reference                                     | Value  |
|-------------------------------------|---|--|
| <b>PidTagAttachmentContactPhoto</b> | <a href="#">[MS-OXCNTC]</a> section 2.2.1.8.3 | TRUE.  |
| <b>PidTagAttachDataBinary</b>       | <a href="#">[MS-OXCMSG]</a> section 2.2.2.7   | Photo stream in binary format.   |
| <b>PidTagAttachExtension</b>        | <a href="#">[MS-OXCMSG]</a> section 2.2.2.12  | ".jpg", ".bmp", ".gif", or ".png", according to the <b>TYPE</b> parameter.     |
| <b>PidTagAttachFilename</b>         | <a href="#">[MS-OXCMSG]</a> section 2.2.2.11  | "ContactPhoto.<ext>". The extension is the value of the <b>TYPE</b> parameter. |

Only binary data types with the **ENCODING** parameter set to "b" are supported. The **TYPE** parameter MUST be one of the following image type values:

- .bmp
- .gif
- .jpeg
- .png

### Exporting from Contact Objects

The **PHOTO** type is exported from the Attachment object with the **ENCODING** parameter set to "b" and the **TYPE** parameter set to the image type (.bmp, .gif, .jpeg, or .png). The image is exported in binary format, as specified in [\[RFC2047\]](#).

#### 2.1.3.2.5 Type: BDAY

RFC reference: [\[RFC2426\]](#) section 3.1.5.

vCard data format: BDAY:<date or date-time value>

Brief description: The birth date of the object that the vCard represents.

### Importing to and Exporting from Contact Objects

The **BDAY** type is imported to and exported from the **PidTagBirthday** ([\[MS-OXCNTC\]](#) section 2.2.1.5.1) property. The time that is associated with the birthday event is 0:00 in the client's local time zone.

#### 2.1.3.3 Deliverable Addressing Types

The deliverable addressing types are used in the vCard profile to capture information that is related to the delivery addressing or label for the person or resource identified by the vCard.

##### 2.1.3.3.1 Type: ADR

RFC reference: [\[RFC2426\]](#) section 3.2.1.

vCard data format: ADR;TYPE=[Type]:[PO Box];[Extended Address];[Street Address];[Locality];[Region];[Postal Code];[Country Name]

Brief description: Physical addresses that are associated with the object that the vCard represents.

### Importing to Contact Objects

The Contact object provides built-in support for three physical addresses: Home Address, Work Address, and Other Address. The vCard **TYPE** parameter can be set to one or more of the following values:

- dom
- intl
- postal
- parcel
- home
- work
- pref

The default **TYPE** parameter value is "intl, postal, parcel, work".

Addresses in the vCard map to the Contact object addresses, as shown in the following table.

| ADR TYPE parameter value  | Contact object address |
|---------------------------|------------------------|
| work                      | Work Address           |
| home                      | Home Address           |
| postal, dom, intl, parcel | Other Address          |

If the **TYPE** parameter contains "pref", the **PidLidPostalAddressId** property ([\[MS-OXOCNTC\]](#) section 2.2.1.3.9) is set to indicate that that address is the contact's mailing address.

The fields in the vCard address are mapped to the fields of the Contact object, as shown in the following table.

| vCard property                          | Contact object properties   |
|---|---|
| <b>PO Box</b>                           | <b>PidTagPostOfficeBox</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.20)<br><b>PidTagHomeAddressPostOfficeBox</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.26)<br><b>PidTagOtherAddressPostOfficeBox</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.32) |
| <b>Extended Address, Street Address</b> | <b>PidTagStreetAddress</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.19)<br><b>PidTagHomeAddressStreet</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.25)<br><b>PidTagOtherAddressStreet</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.31)               |
| <b>Locality</b>                         | <b>PidTagLocality</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.21)<br><b>PidTagHomeAddressCity</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.27)   |

| vCard property      | Contact object properties   |
|---------------------|---|
|                     | <b>PidTagOtherAddressCity</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.33)   |
| <b>Region</b>       | <b>PidTagStateOrProvince</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.22)<br><b>PidTagHomeAddressStateOrProvince</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.28)<br><b>PidTagOtherAddressStateOrProvince</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.34) |
| <b>Postal Code</b>  | <b>PidTagPostalCode</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.23)<br><b>PidTagHomeAddressPostalCode</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.29)<br><b>PidTagOtherAddressPostalCode</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.35)                |
| <b>Country Name</b> | <b>PidTagCountry</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.24)<br><b>PidTagHomeAddressCountry</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.30)<br><b>PidTagOtherAddressCountry</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.36)                         |

### Exporting from Contact Objects

Each address is exported as a structured **ADR** type, with the **TYPE** parameter set to the values listed in the following table.

| TYPE parameter value | Contact object properties   |
|----------------------|---|
| work                 | <b>PidTagPostOfficeBox</b><br><b>PidTagStreetAddress</b><br><b>PidTagLocality</b><br><b>PidTagStateOrProvince</b><br><b>PidTagPostalCode</b><br><b>PidTagCountry</b>  |
| home                 | <b>PidTagHomeAddressPostOfficeBox</b><br><b>PidTagHomeAddressStreet</b><br><b>PidTagHomeAddressCity</b><br><b>PidTagHomeAddressStateOrProvince</b><br><b>PidTagHomeAddressPostalCode</b><br><b>PidTagHomeAddressCountry</b>       |
| postal               | <b>PidTagOtherAddressPostOfficeBox</b><br><b>PidTagOtherAddressStreet</b><br><b>PidTagOtherAddressCity</b><br><b>PidTagOtherAddressStateOrProvince</b><br><b>PidTagOtherAddressPostalCode</b><br><b>PidTagOtherAddressCountry</b> |

The address that is selected as the mailing address by the **PidLidPostalAddressId** property also gets the value "pref" assigned to the **TYPE** parameter.

#### 2.1.3.3.2 Type: LABEL

RFC reference: [\[RFC2426\]](#) section 3.2.2.

vCard data format: LABEL;TYPE=[Type]:[Formatted Address]

Brief description: Structured mailing label for the object that the vCard represents.

### Importing to Contact Objects

The **LABEL** type is ignored on import.

### Exporting from Contact Objects

The physical address objects are exported as a formatted string that represents a mailing label. Labels are constructed from the Contact object fields that are listed in the following table.

| Address label | Contact object properties   |
|---------------|---|
| Work          | <b>PidTagPostOfficeBox</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.20)<br><b>PidTagStreetAddress</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.19)<br><b>PidTagLocality</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.21)<br><b>PidTagStateOrProvince</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.22)<br><b>PidTagPostalCode</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.23)<br><b>PidTagCountry</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.24)  |
| Home          | <b>PidTagHomeAddressPostOfficeBox</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.26)<br><b>PidTagHomeAddressStreet</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.25)<br><b>PidTagHomeAddressCity</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.27)<br><b>PidTagHomeAddressStateOrProvince</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.28)<br><b>PidTagHomeAddressPostalCode</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.29)<br><b>PidTagHomeAddressCountry</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.30)       |
| Postal        | <b>PidTagOtherAddressPostOfficeBox</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.32)<br><b>PidTagOtherAddressStreet</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.31)<br><b>PidTagOtherAddressCity</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.33)<br><b>PidTagOtherAddressStateOrProvince</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.34)<br><b>PidTagOtherAddressPostalCode</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.35)<br><b>PidTagOtherAddressCountry</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.36) |

## 2.1.3.4 Telecommunications Addressing Types

The telecommunications addressing types are used in the vCard profile to capture telecommunications information, such as telephone numbers and email addresses for the person or resource identified by the vCard.

### 2.1.3.4.1 Type: TEL

RFC reference: [\[RFC2426\]](#) section 3.3.1.

vCard data format: TEL; TYPE=[Type]:[Phone Number]

Brief description: A telephone number that is associated with the object that the vCard represents.

### Importing to Contact Objects

Telephone numbers are imported to the Contact object based on the **TYPE** parameter, as shown in the following table. If the **TYPE** parameter is not specified in the vCard, the default value is "voice".

| TYPE parameter value | Contact object properties   |
|----------------------|---|
| home                 | <b>PidTagHomeTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.39)<br><b>PidTagHome2TelephoneNumber</b> ([MS-OXOABK] section 2.2.4.42)         |
| msg                  | <b>PidTagOtherTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.48)  |
| work                 | <b>PidTagBusinessTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.38)<br><b>PidTagBusiness2TelephoneNumber</b> ([MS-OXOABK] section 2.2.4.40) |
| voice                | <b>PidTagOtherTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.48)  |
| cell                 | <b>PidTagMobileTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.45)   |
| video                | <b>PidTagOtherTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.48)  |
| pager                | <b>PidTagPagerTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.49)  |
| bbs                  | <b>PidTagOtherTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.48)  |
| modem                | <b>PidTagOtherTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.48)  |
| car                  | <b>PidTagCarTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.47)  |
| isdn                 | <b>PidTagIsdnNumber</b> ([MS-OXOABK] section 2.2.4.56)  |
| home;fax             | <b>PidTagHomeFaxNumber</b> ([MS-OXOABK] section 2.2.4.52)   |
| work;fax             | <b>PidTagBusinessFaxNumber</b> ([MS-OXOABK] section 2.2.4.51)   |
| pcs                  | Dropped   |
| pref                 | <b>PidTagPrimaryTelephoneNumber</b> ([MS-OXOABK] section 2.2.4.37)  |

### Exporting from Contact Objects

Each telephone number is exported as a formatted **TEL** type.

#### 2.1.3.4.2 Type: EMAIL

RFC reference: [\[RFC2426\]](#) section 3.3.2.

vCard data format: EMAIL;TYPE=[Type]:[Email]

Brief description: Email address of the object described by this vCard in either SMTP or X.400 format.

### Importing to Contact Objects

The contents of one to three **EMAIL** types are imported into Contact object properties depending on the **TYPE** parameter that is specified. The **EMAIL** type is imported as shown in the following table.

| TYPE parameter value                                   | Contact object properties   |
|--|---|
| internet (or no <b>TYPE</b> parameter value specified) | <b>PidLidEmail1AddressType</b> <a href="#">[MS-OXOCNTC]</a> section 2.2.1.2.2<br><b>PidLidEmail1EmailAddress</b> <a href="#">[MS-OXOCNTC]</a> section 2.2.1.2.3<br><b>PidLidEmail2AddressType</b> |

| TYPE parameter value | Contact object properties  |
|----------------------|--|
|                      | <b>PidLidEmail2EmailAddress</b><br><b>PidLidEmail3AddressType</b><br><b>PidLidEmail3EmailAddress</b><br>Any additional <b>EMAIL</b> types are ignored. |
| im                   | <b>PidLidInstantMessagingAddress</b> <a href="#">[MS-OXOCNTC]</a> section 2.2.1.9.6<br>Exported as <b>X-MS-IMADDRESS</b> .                             |
| telex                | <b>PidTagTelexNumber</b> ( <a href="#">[MS-EXOABK]</a> section 2.2.4.55)<br>Exported as the <b>X-MS-TEL;TYPE=telex</b> type.                           |

If multiple **TYPE** parameter values are set on an **EMAIL** type, the first recognized **TYPE** parameter value is used. If no **TYPE** parameter value is recognized, "internet" is used.

### Exporting from Contact Objects

The **PidLidEmail1AddressType**, **PidLidEmail1EmailAddress**, **PidLidEmail2AddressType**, **PidLidEmail2EmailAddress**, **PidLidEmail3AddressType**, and **PidLidEmail3EmailAddress** properties are exported to the vCard. The **PidLidEmail1DisplayName**, **PidLidEmail2DisplayName**, and **PidLidEmail3DisplayName** properties ([\[MS-OXOCNTC\]](#) section 2.2.1.2.1) are not exported.

The **PidLidInstantMessagingAddress** property is exported as an **X-MS-IMADDRESS** type; the **PidTagTelexNumber** property is exported as an **X-MS-TEL;TYPE=telex** type.

#### 2.1.3.4.3 Type: MAILER

RFC reference: [\[RFC2426\]](#) section 3.3.3.

vCard data format: MAILER:[Mailer]

Brief description: The name of the program that generated the vCard.

#### Importing to Contact Objects

The **MAILER** type is not imported.

#### Exporting from Contact Objects

The **MAILER** type is set to "Microsoft Exchange".

#### 2.1.3.5 Geographical Types

The geographical types capture geographical locations that are associated with the object that the vCard represents.

##### 2.1.3.5.1 Type: TZ

RFC reference: [\[RFC2426\]](#) section 3.4.1.

vCard data format: TZ:[UTC-Offset]

Brief description: The time zone where the object that is represented by the vCard is located.

## Importing to and Exporting from Contact Objects

The **TZ** type is neither imported to the Contact object nor exported when a vCard is created.

### 2.1.3.5.2 Type: GEO

RFC reference: [\[RFC2426\]](#) section 3.4.2.

vCard data format: GEO:[Decimal latitude]; [Decimal longitude]

Brief description: The decimal latitude and longitude of the location of the object that the vCard represents.

## Importing to and Exporting from Contact Objects

The **GEO** type is neither imported to the Contact object nor exported when a vCard is created.

### 2.1.3.6 Organizational Types

These types capture information about the organization or organizational units of the object that the vCard represents.

#### 2.1.3.6.1 Type: TITLE

RFC reference: [\[RFC2426\]](#) section 3.5.1.

vCard data format: TITLE:[Formatted title]

Brief description: Job title, functional position, or function of the object that the vCard represents.

## Importing to and Exporting from Contact Objects

The **TITLE** type is imported to and exported from the **PidTagTitle** property ([\[MS-OXOABK\]](#) section 2.2.4.7).

#### 2.1.3.6.2 Type: ROLE

RFC reference: [\[RFC2426\]](#) section 3.5.2.

vCard data format: ROLE:[Formatted title]

Brief description: The role, occupation, or business category of the object that is represented by the vCard.

## Importing to and Exporting from Contact Objects

The **ROLE** type is imported to and exported from the **PidTagProfession** property ([\[MS-OXOABK\]](#) section 2.2.4.70).

#### 2.1.3.6.3 Type: LOGO

RFC reference: [\[RFC2426\]](#) section 3.5.3.

vCard data format:

LOGO;Encoding=b;TYPE=[Type]:[Data]



LOGO;VALUE=uri:[URI]

Brief description: A graphic image of a logo that is associated with the object that is represented by the vCard.

### Importing to and Exporting from Contact Objects

The **LOGO** type is neither imported to the Contact object nor exported when a vCard is created.

#### 2.1.3.6.4 Type: AGENT

RFC reference: [\[RFC2426\]](#) section 3.5.4.

vCard data format:

AGENT;VALUE=uri:[Unique identifier]

AGENT;BEGIN:VCARD\n[vCard data]\nEND:VCARD\n

Brief description: Information about another person who will act on behalf of the object that is represented by the vCard.

### Importing to Contact Objects

Only the second (vCard) form of the **AGENT** type is imported. All values in the **AGENT** type vCard are dropped except for the **FN** and **TEL** types. Contact object properties are assigned as shown in the following table.

| AGENT vCard type | Contact object property   |
|------------------|---|
| <b>FN</b>        | <b>PidTagAssistant</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.11)                |
| <b>TEL</b>       | <b>PidTagAssistantTelephoneNumber</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.57) |

The last **TEL** type in the **AGENT** type vCard is used as the assistant's telephone number.

### Exporting from Contact Objects

The **PidTagAssistant** and **PidTagAssistantTelephoneNumber** properties are exported as the **X-MS-ASSISTANT** and **X-MS-TEL;TYPE=ASSISTANT** types.

#### 2.1.3.6.5 Type: ORG

RFC reference: [\[RFC2426\]](#) section 3.5.5.

vCard data format: ORG:[Organization];[SubUnit1];[SubUnit2]; <repeats>

Brief description: The organizational name and units that are associated with the object that is represented by the vCard.

### Importing to and Exporting from Contact Objects

The fields of the **ORG** type are imported to and exported from Contact object properties as shown in the following table.

| ORG type field       | Contact object property   |
|----------------------|---|
| Organization         | PidTagCompanyName ( <a href="#">[MS-OXOABK]</a> section 2.2.4.10)   |
| SubUnit1<br>SubUnit2 | PidTagDepartmentName ( <a href="#">[MS-OXOABK]</a> section 2.2.4.9) |

### 2.1.3.7 Explanatory Types

The explanatory types capture additional information about the person or resource that is identified by the vCard.

#### 2.1.3.7.1 Type: CATEGORIES

RFC reference: [\[RFC2426\]](#) section 3.6.1.

vCard data format: CATEGORIES:[value1],[value2],<repeats>

Brief description: Comma-separated category information that is associated with the object that is represented by the vCard.

#### Importing to and Exporting from Contact Objects

The categories type is imported to and exported from the **PidLidCategories** property ([\[MS-OXCMSG\]](#) section 2.2.1.22).

#### 2.1.3.7.2 Type: NOTE

RFC reference: [\[RFC2426\]](#) section 3.6.2.

**Contact** object reference: N/A.

vCard data format: NOTE:[Note]

Brief description: Supplemental information or comment that is associated with the object that is represented by the vCard.

#### Importing to and Exporting from Contact Objects

The **NOTE** type is imported to and exported from the **PidTagBody** property ([\[MS-OXCMSG\]](#) section 2.2.1.48.1).

#### 2.1.3.7.3 Type: PRODIG

RFC reference: [\[RFC2426\]](#) section 3.6.3.

vCard data format: PRODIG:[Product]

Brief description: Identifier of the product that created the vCard.

#### Importing to Contact Objects

The **PRODIG** type is not imported.

#### Exporting from Contact Objects

The **PRODIG** type is set to "Microsoft Exchange" when the vCard is created.

#### 2.1.3.7.4 Type: REV

RFC reference: [\[RFC2426\]](#) section 3.6.4.

vCard data format: REV:[Revision]

Brief description: Distinguishes the current revision of the information in the vCard from other renditions of the information.

##### Importing to and Exporting from Contact Objects

The **REV** type is imported to and exported from the **PidTagLastModificationTime** property ([\[MS-OXCMSG\]](#) section 2.2.2.2).

#### 2.1.3.7.5 Type: SORT-STRING

RFC reference: [\[RFC2426\]](#) section 3.6.5.

vCard data format: SORT-STRING:[Sort text]

Brief description: Text to be used for national/regional-language-specific sorting of the **FN** and **N** types.

##### Importing to and Exporting from Contact Objects

The **SORT-STRING** type is neither imported from nor exported to the vCard.

#### 2.1.3.7.6 Type: SOUND

RFC reference: [\[RFC2426\]](#) section 3.6.6.

vCard data format:

SOUND;TYPE=[Format];VALUE=uri:cid:[Uri]

SOUND:TYPE=[Format];ENCODING=b:[data]

Brief description: Digital sound content associated with the object that is represented by the vCard.

##### Importing to and Exporting from Contact Objects

The **SOUND** type is neither imported to the Contact object nor exported from the vCard.

#### 2.1.3.7.7 Type: UID

RFC reference: [\[RFC2426\]](#) section 3.6.7.

vCard data format: UID:[Unique identifier]

Brief description: Globally unique identifier that corresponds to the object that is represented by the vCard.

##### Importing to and Exporting from Contact Objects

The **UID** type is neither imported to the Contact object nor exported from the vCard.

### 2.1.3.7.8 Type: URL

RFC reference: [\[RFC2426\]](#) section 3.6.8.

vCard data format: URL:[Uri]

Brief description: **Uniform Resource Identifier (URI)** that is associated with the object that is represented by the vCard.

#### Importing to Contact Objects

The **URL** type is imported to the Contact object based on the **TYPE** parameter.

| TYPE parameter value | Contact object property   |
|----------------------|---|
| home                 | <b>PidTagPersonalHomePage</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.77) |
| work                 | <b>PidTagBusinessHomePage</b> ( <a href="#">[MS-OXOABK]</a> section 2.2.4.78) |

If the **TYPE** parameter is not specified, the URL type is imported first to the **PidTagBusinessHomePage** property. One additional URL type is imported to the **PidTagPersonalHomePage** property; any other instances are ignored.

#### Exporting from Contact Objects

One URL type is exported from the **PidTagBusinessHomePage** property with the **TYPE** parameter set to "work", and another URL type is exported from the **PidTagPersonalHomePage** property with the **TYPE** parameter set to "home".

### 2.1.3.7.9 Type: VERSION

RFC reference: [\[RFC2426\]](#) section 3.6.9.

vCard data format: VERSION:[Version]

Brief description: The version of the vCard specification that is used to format the vCard.

#### Importing to Contact Objects

The **VERSION** type is not imported to the Contact object.

#### Exporting from Contact Objects

The **VERSION** type is set to 3.0.

### 2.1.3.8 Security Types

The security types capture security information for the vCard.

#### 2.1.3.8.1 Type: CLASS

RFC reference: [\[RFC2426\]](#) section 3.7.1.

vCard data format: CLASS:[Access classification]

Brief description: Specifies the access classification for a vCard.

## Importing to and Exporting from Contact Objects

The **CLASS** type is imported to and exported from the **PidTagSensitivity** property ([\[MS-OXCMSG\]](#) section 2.2.1.13), as shown in the following table.

| CLASS type value | PidTagSensitivity value |
|------------------|-------------------------|
| Public           | 0                       |
| Private          | 2                       |
| Confidential     | 3                       |

If the **CLASS** type value is not one of the values shown in the preceding table, the **PidTagSensitivity** value is not set.

### 2.1.3.8.2 Type: KEY

RFC reference: [\[RFC2426\]](#) section 3.7.2.

vCard data format: KEY;ENCODING=b:[data]

Brief description: A public key or authentication certificate that is associated with the object that the vCard represents.

## Importing to and Exporting from Contact Objects

If the **KEY** type represents an X.509 certificate, the **KEY** type is imported to and exported from the **PidTagUserX509Certificate** property ([\[MS-OXOABK\]](#) section 2.2.4.66). Other certificate types are not imported.

### 2.1.3.9 Custom Types

The following types are extended types that use the nonstandard mechanism that is defined in [\[RFC2045\]](#).

#### 2.1.3.9.1 EBC Design

vCard header: X-MS-OL-DESIGN:

vCard data format: X-MS-OL-DESIGN:[data]

Brief description: Electronic business card that is associated with the object that the vCard represents.

## Importing to and Exporting from Contact Objects

The **X-MS-OL-DESIGN** type is imported to and exported from the **PidLidBusinessCardDisplayDefinition** property ([\[MS-OXOCNTC\]](#) section 2.2.1.7.1).

#### 2.1.3.9.2 Children

vCard header: X-MS-CHILD:, X-CHILD:

vCard data format: X-MS-CHILD:[Children's names]

Brief description: The names of children who are associated with the object that the vCard represents.

### Importing to and Exporting from Contact Objects

The **X-MS-CHILD** and **X-CHILD** types are imported to and exported from the **PidTagChildrensNames** property ([\[MS-OXOCNTC\]](#) section 2.2.1.9.17).

#### 2.1.3.9.3 User Text

vCard header: X-MS-TEXT:, X-CUSTOM:

vCard data format: X-MS-TEXT:[Text]

Brief description: Custom text that is associated with the object that the vCard represents.

### Importing to Contact Objects

The **X-MS-TEXT** type is saved to the **PidLidContactUserField1**, **PidLidContactUserField2**, **PidLidContactUserField3**, and **PidLidContactUserField4** properties ([\[MS-OXOCNTC\]](#) section 2.2.1.7.3) in the order in which they are received. A maximum of four **X-MS-TEXT** types can be saved; additional instances are discarded.

### Exporting from Contact Objects

The contents of the **PidLidContactUserField1**, **PidLidContactUserField2**, **PidLidContactUserField3**, and **PidLidContactUserField4** properties are exported as **X-MS-TEXT** types.

#### 2.1.3.9.4 Instant Messaging Address

vCard header: X-MS-IMADDRESS:, X-MS-RM-IMACCOUNT:, EMAIL;IM:

vCard data format: X-MS-IMADDRESS:[IM Address]

Brief description: Instant messaging address that is associated with the object that the vCard represents.

### Importing to and Exporting from Contact Objects

The **X-MS-IMADDRESS** type is imported to and exported from the **PidLidInstantMessagingAddress** property ([\[MS-OXOCNTC\]](#) section 2.2.1.9.6). Any additional **X-MS-IMADDRESS** types are ignored.

#### 2.1.3.9.5 Telephone Numbers

vCard header: X-MS-TEL;TYPE=<telephone type>

Brief description: The telephone number properties listed in the following table are imported to and exported from properties as **X-MS-TEL** types.

| TYPE property  | Contact object property        | Reference                                       |
|----------------|--------------------------------|---|
| TYPE=ASSISTANT | PidTagAssistantTelephoneNumber | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.4.11 |

| TYPE property | Contact object property                              | Reference                                       |
|---------------|--|---|
| TYPE=CALLBACK | PidTagCallbackTelephoneNumber                        | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.4.2  |
| TYPE=COMPANY  | PidTagCompanyMainTelephoneNumber                     | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.4.14 |
| TYPE=RADIO    | PidTagRadioTelephoneNumber                           | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.4.8  |
| TYPE=TTY/TDD  | PidTagTelecommunicationsDeviceForDeafTelephoneNumber | <a href="#">[MS-OXOCNTC]</a> section 2.2.1.4.13 |

### 2.1.3.9.6 Anniversary

vCard header: X-MS-ANNIVERSARY:, X-ANNIVERSARY:

vCard data format: X-MS-ANNIVERSARY:[date or date/time value]

Required: No.

Brief description: The wedding anniversary that is associated with the object that is represented by the vCard.

#### Importing to and Exporting from Contact Objects

The **X-MS-ANNIVERSARY** type is imported to and exported from the **PidTagWeddingAnniversary** property ([\[MS-OXOABK\]](#) section 2.2.4.80).

### 2.1.3.9.7 Spouse's Name

vCard header: X-MS-SPOUSE;N:

vCard data format: X-MS-SPOUSE;N:[Formatted name]

Brief description: The name of the spouse that is associated with the object that is represented by the vCard.

#### Importing to and Exporting from Contact Objects

The **X-MS-SPOUSE;N** type is imported to and exported from the **PidTagSpouseName** property ([\[MS-OXOABK\]](#) section 2.2.4.72).

### 2.1.3.9.8 Manager's Name

vCard header: X-MS-MANAGER;N:

vCard data format: X-MS-MANAGER;N:[Formatted name]

Brief description: The name of the manager who is associated with the object that the vCard represents.

### Importing to and Exporting from Contact Objects

The **X-MS-MANAGER;N** type is imported to and exported from the **PidTagManagerName** property ([\[MS-OXOABK\]](#) section 2.2.4.12).

#### 2.1.3.9.9 Assistant's Name

vCard header: X-MS-ASSISTANT;N;, X-ASSISTANT

vCard data format: X-MS-ASSISTANT;N:[Formatted name]

Brief description: The name of a person who is authorized to act on behalf of the object that is represented by the vCard.

### Importing to and Exporting from Contact Objects

The **X-MS-ASSISTANT;N** type is imported to and exported from the **PidTagAssistant** property ([\[MS-OXOABK\]](#) section 2.2.4.11). The **X-MS-TEL;ASSISTANT** and **X-MS-ASSISTANT;N:** types are used instead of the vCard **AGENT** type.

#### 2.1.3.9.10 Free/Busy URL

vCard header: X-MS-FBURL

vCard data format: X-MS-FBURL:[Uri]

Brief description: A URI from which a client can retrieve free/busy information for the object that is represented by the vCard as an iCal file, as specified in [\[MS-OXCICAL\]](#).

### Importing to and Exporting from Contact Objects

The **X-MS-FBURL** type is imported to and exported from the **PidLidFreeBusyLocation** property ([\[MS-OXOCNTC\]](#) section 2.2.1.9.10).

#### 2.1.3.9.11 Interests

vCard header: X-MS-INTERESTS;, X-INTERESTS:

vCard data format: X-MS-INTERESTS:[List of interests]

Brief description: The hobbies or other interests that are associated with the object that is represented by the vCard.

### Importing to and Exporting from Contact Objects

The **X-MS-INTERESTS** type is imported to and exported from the **PidTagHobbies** property ([\[MS-OXOABK\]](#) section 2.2.4.69).



### 3 Algorithm Examples

The following examples show how a vCard is imported to and exported from a Contact object.

#### 3.1 Importing a vCard

The following is a text representation of a vCard.

```
BEGIN:vCard
VERSION:3.0
FN:Dan Fennell
ORG:Contoso, Ltd.
ADR;TYPE=WORK,POSTAL,PARCEL;;;7890 Elm Street;Boulder;CO;33041;U.S.
TEL;TYPE=VOICE,MSG,WORK:+1-206-555-0102
TEL;TYPE=FAX,WORK:+1-206-555-0162
EMAIL;TYPE=INTERNET,PREF:dan.fennell@contoso.com
EMAIL;TYPE=INTERNET:dfennell@fabrikam.com
URL:http://www.contoso.com/
END:vCard
```

The information in the vCard is imported to a Contact object, as shown in the following table.

| vCard type   | Contact object property   | Value           |
|--|---|-----------------|
| <b>FN:</b>   | <b>PidTagDisplayName</b>  | Dan Fennell     |
| <b>ORG:</b>  | <b>PidTagCompanyName</b>  | Contoso, Ltd.   |
| <b>ADR; TYPE=WORK, postal,parcel:</b>                    | <b>PidTagStreetAddress</b><br><b>PidTagOtherAddressStreet</b>             | 7890 Elm St.    |
| <b>ADR; TYPE=WORK, postal,parcel:</b>                    | <b>PidTagLocality</b><br><b>PidTagOtherAddressCity</b>                    | Boulder         |
| <b>ADR; TYPE=WORK, postal,parcel:</b>                    | <b>PidTagStateOrProvince</b><br><b>PidTagOtherAddressStateOrProvince</b>  | CO              |
| <b>ADR; TYPE=WORK, postal,parcel:</b>                    | <b>PidTagPostalCode</b><br><b>PidTagOtherAddressPostalCode</b>            | 33041           |
| <b>ADR; TYPE=WORK, postal,parcel:</b>                    | <b>PidTagCountry</b><br><b>PidTagOtherAddressCountry</b>                  | U.S.            |
| <b>TEL;TYPE=VOICE,MSG, WORK:+1-206-555-0102</b>          | <b>PidTagBusinessTelephoneNumber</b><br><b>PidTagOtherTelephoneNumber</b> |                 |
| <b>TEL;TYPE=FAX, WORK:+1-206-555-0162</b>                | <b>PidTagBusinessFaxNumber</b>  | +1-206-555-0162 |
| <b>EMAIL;TYPE=INTERNET, PREF:dan.fennell@contoso.com</b> | <b>PidLidEmail1EmailAddress</b>   |                 |
| <b>EMAIL;TYPE=INTERNET:dfennell@fabrikam.com</b>         | <b>PidLidEmail2EmailAddress</b>   |                 |

| vCard type                  | Contact object property | Value |
|-----------------------------|-------------------------|-------|
| URL:http://www.contoso.com/ | PidTagBusinessHomePage  |       |

### 3.2 Exporting a Contact object

The following table contains the values stored in a Contact object.

| Contact object property          | Value                   |
|----------------------------------|-------------------------|
| PidLidEmail1EmailAddress         | dan.fennell@contoso.com |
| PidLidEmail2EmailAddress         | dfennell@fabrikam.com   |
| PidTagAssistant                  | Jeff Price              |
| PidTagAssistantTelephoneNumber   | +1-206-555-0188         |
| PidTagBusinessTelephoneNumber    | +1-206-555-0102         |
| PidTagCompanyMainTelephoneNumber | +1-206-555-0100         |
| PidTagCompanyName                | Contoso, Ltd.           |
| PidTagCountry                    | USA                     |
| PidTagGivenName                  | Dan                     |
| PidTagHomeAddressCountry         | USA                     |
| PidTagHomeAddressCity            | Boulder                 |
| PidTagHomeAddressPostalCode      | 33041                   |
| PidTagHomeAddressStateOrProvince | CO                      |
| PidTagHomeAddressStreet          | 345 Aspen Street        |
| PidTagLocality                   | Boulder                 |
| PidTagMobileTelephoneNumber      | +1-425-555-0199         |
| PidTagPostalCode                 | 33041                   |
| PidTagStateOrProvince            | CO                      |
| PidTagStreetAddress              | 7890 Elm Street         |
| PidTagSurname                    | Fennell                 |

The following vCard is generated from the preceding table.

```

BEGIN:vCard
VERSION:3.0
PROID:Microsoft Exchange
FN:Dan Fennell
N:Fennell;Dan;;;
ORG:Contoso, Ltd
ADR;TYPE=work,pref:;;7890 Elm Street;Boulder;CO;33041;U.S.

```

ADR;TYPE=home;;;345 Aspen Street;Boulder;CO;33041;U.S.  
EMAIL:TYPE=internet,pref:dan.fennell@contoso.com  
EMAIL:TYPE=internet:dfennell@fabrikam.com  
TEL;TYPE=work,pref:+1-206-555-0102  
TEL;TYPE=cell:+1-425-555-0199  
X-MS-TEL;TYPE=COMPANY:+1-206-555-0100  
X-MS-ASSISTANT;TYPE=N: Julian Price  
X-MS-TEL;TYPE=ASSISTANT:+1-206-555-0188

## 4 Security

### 4.1 Security Considerations for Implementers

The vCard format can carry cryptographic keys or certificates, as specified in section [2.1.3.8.2](#).

Section [2.1.3.8.1](#) specifies a security classification policy for a vCard. Note that the security policy is not enforced in any way.

vCards have no inherent authentication or privacy features, but they can be sent by any security mechanism that transfers MIME objects with security or privacy. Where the threat exists of invalid vCard information, it is recommended that you send the vCard by such a mechanism.

The information contained in a vCard may become out of date. In cases where the data is important to the originator of the vCard, it is recommended that you specify the **URL** type specified in section [2.1.3.7.8](#). In addition, you can use the **REV** type specified in section [2.1.3.7.4](#) to indicate the last time that the vCard data was updated.

### 4.2 Index of Security Parameters

| Security parameter | Section                   |
|--------------------|---------------------------|
| <b>CLASS</b> type  | <a href="#">2.1.3.8.1</a> |
| <b>KEY</b> type    | <a href="#">2.1.3.8.2</a> |
| <b>REV</b> type    | <a href="#">2.1.3.7.4</a> |
| <b>URL</b> type    | <a href="#">2.1.3.7.8</a> |

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2010

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

## 6 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 7 Index

### A

[Applicability](#) 6

### C

[Change tracking](#) 30

### E

Examples

[Exporting a Contact object](#) 26

[Importing a vCard](#) 25

[overview](#) 25

[Exporting a Contact object example](#) 26

### G

[Glossary](#) 5

### I

[Implementer - security considerations](#) 28

[Importing a vCard example](#) 25

[Index of security parameters](#) 28

[Informative references](#) 6

[Introduction](#) 5

### N

[Normative references](#) 5

### O

[Overview \(synopsis\)](#) 6

### P

[Parameters - security index](#) 28

[Product behavior](#) 29

### R

References

[informative](#) 6

[normative](#) 5

### S

Security

[implementer considerations](#) 28

[parameter index](#) 28

[Standards assignments](#) 7

### T

[Tracking changes](#) 30