

# [MS-OXWOAB]: Offline Address Book (OAB) Retrieval File Format

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Revised and edited technical content.
09/03/2008	1.02		Revised and edited technical content.
12/03/2008	1.03		Updated IP notice.
03/04/2009	1.04		Revised and edited technical content.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	3.1.0	Minor	Updated the technical content.
02/10/2010	3.2.0	Minor	Updated the technical content.
05/05/2010	3.2.1	Editorial	Revised and edited the technical content.
08/04/2010	3.3	Minor	Clarified the meaning of the technical content.
11/03/2010	3.3	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	4.0	Major	Significantly changed the technical content.
08/05/2011	4.0	No change	No changes to the meaning, language, or formatting of the technical content.
10/07/2011	4.0	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	5.0	Major	Significantly changed the technical content.
04/27/2012	5.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	5.0	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	5.1	Minor	Clarified the meaning of the technical content.
02/11/2013	5.1	No change	No changes to the meaning, language, or formatting of the technical content.
07/26/2013	5.1	No change	No changes to the meaning, language, or formatting of the technical content.
11/18/2013	5.1	No change	No changes to the meaning, language, or formatting of

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
			the technical content.
02/10/2014	5.1	No change	No changes to the meaning, language, or formatting of the technical content.
04/30/2014	6.0	Major	Significantly changed the technical content.
07/31/2014	6.0	No change	No changes to the meaning, language, or formatting of the technical content.

# Table of Contents

<b>1 Introduction</b>	<b>5</b>
1.1 Glossary	5
1.2 References	6
1.2.1 Normative References	6
1.2.2 Informative References	6
1.3 Overview	6
1.4 Relationship to Other Protocols	6
1.5 Prerequisites/Preconditions	7
1.6 Applicability Statement	7
1.7 Versioning and Capability Negotiation	7
1.8 Vendor-Extensible Fields	7
1.9 Standards Assignments	7
<b>2 Messages</b>	<b>8</b>
2.1 Transport	8
2.2 Message Syntax	8
2.2.1 Message Structures	8
2.2.1.1 Manifest File Structure	8
<b>3 Protocol Details</b>	<b>12</b>
3.1 Server Details	12
3.1.1 Abstract Data Model	12
3.1.2 Timers	12
3.1.3 Initialization	12
3.1.4 Higher-Layer Triggered Events	12
3.1.5 Message Processing Events and Sequencing Rules	12
3.1.6 Timer Events	12
3.1.7 Other Local Events	12
<b>4 Protocol Examples</b>	<b>13</b>
<b>5 Security</b>	<b>14</b>
5.1 Security Considerations for Implementers	14
5.2 Index of Security Parameters	14
<b>6 Appendix A: Product Behavior</b>	<b>15</b>
<b>7 Change Tracking</b>	<b>16</b>
<b>8 Index</b>	<b>17</b>

# 1 Introduction

The Offline Address Book (OAB) Retrieval File Format enables a client to retrieve an address book from the server for local storage when the server is offline. A server can represent properties of known **recipients (2)** and make them available in an **address book** to its clients. When the client cannot reach the server because the server is offline or there is a high network cost to access it, the client can use the OAB retrieval file format to keep a local copy of the address book. The **offline address book (OAB)** version 4 Web-based retrieval mechanism is a way of delivering an offline address book from the server to the client.

As part of **OAB Web distribution**, the server publishes an **OAB manifest** document. The format of that manifest is detailed in this document.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in [\[RFC2119\]](#). Sections 1.5 and 1.9 are also normative but does not contain those terms. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**Augmented Backus-Naur Form (ABNF)**  
**distinguished name (DN)**  
**GUID**  
**Hypertext Transfer Protocol (HTTP)**  
**Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**  
**XML**

The following terms are defined in [\[MS-OXGLOS\]](#):

**address book**  
**address list**  
**OAL data sequence number**  
**offline address book (OAB)**  
**offline address book (OAB) data file**  
**offline address list (OAL)**  
**recipient**  
**Uniform Resource Identifier (URI)**  
**Web Distribution Point (WDP)**

The following terms are specific to this document:

**OAB manifest:** A file that contains information about data files in a version 4 OAB and has a fixed, well-known name "oab.xml". By discovering the Web Distribution Point (WDP) URI and downloading the manifest, a client application can receive all the information that is necessary to download any published data file in a specific WDP, as necessary.

**OAB web distribution:** A distribution mechanism that is specific to offline address book (OAB) version 4 and is used to publish OAB data files and an OAB manifest as a collection of files that a client application can download by using the HTTP/1.1 protocol, as described in [\[RFC2616\]](#).

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[FIPS180] FIPS PUBS, "Secure Hash Standard", FIPS PUB 180-1, April 1995, <http://www.itl.nist.gov/fipspubs/fip180-1.htm>

[MS-LCID] Microsoft Corporation, "[Windows Language Code Identifier \(LCID\) Reference](#)".

[MS-OXDCLI] Microsoft Corporation, "[Autodiscover Publishing and Lookup Protocol](#)".

[MS-OXOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) File Format and Schema](#)".

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol](#)".

[MS-OXOABKT] Microsoft Corporation, "[Address Book User Interface Templates Protocol](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

[XML10] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Third Edition)", February 2004, <http://www.w3.org/TR/2004/REC-xml-20040204/>

### 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

## 1.3 Overview

Clients use the OAB manifest to identify the current version of data published by the server and build the **URIs** of data files to download. The format of the OAB manifest is **XML**, and the manifest contains one entry for each data file in the OAB. The entries are organized hierarchically.

## 1.4 Relationship to Other Protocols

- Clients discover the URI of the **WDP** by using the Autodiscover Publishing and Lookup Protocol [[MS-OXDCLI](#)].

- From the WDP URI, clients construct the manifest URI and use the **HTTP** /1.1 protocol [[RFC2616](#)] to retrieve the manifest file.
- Based on data in the manifest, clients use the Offline Address Book (OAB) Retrieval File Format to retrieve and consume **OAB data files** that are generated as described in [[MS-OXOAB](#)].
- This file format relies on the HTTP 1.1 protocol, as described in [[RFC2616](#)], to deliver the manifest and data OAB files from the server to the client. It also relies on **HTTPS**, as described in [[RFC2818](#)], for data protection services.

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [[MS-OXPROTO](#)].

## 1.5 Prerequisites/Preconditions

None.

## 1.6 Applicability Statement

Before the OAB Web distribution mechanism specified in this document can be used, a set of OAB files has to be generated in the format specified in [[MS-OXOAB](#)], the files have to be published on an HTTP 1.1 server, and the URI of the WDP has to be published by means of the Autodiscover Publishing and Lookup Protocol, as specified in [[MS-OXDCLI](#)].

## 1.7 Versioning and Capability Negotiation

The Offline Address Book (OAB) Retrieval File Format has only one version.

## 1.8 Vendor-Extensible Fields

None.

## 1.9 Standards Assignments

None.

## 2 Messages

### 2.1 Transport

None.

### 2.2 Message Syntax

#### 2.2.1 Message Structures

The client uses the Autodiscover Publishing and Lookup Protocol, as specified in [\[MS-OXDSCLI\]](#), to discover the Web Distribution Point (WDP) URI, and then it constructs a manifest URI by appending the well-known name "oab.xml", as specified in the following **ABNF**:

```
manifestURI = wdpUri "/oab.xml"
```

The client then retrieves the manifest file by using the standard HTTP/1.1 protocol, as specified in [\[RFC2616\]](#). The manifest file contains information about the **OAL data sequence number** and the names of the data files that are published to a given WDP. The detailed structure of the manifest file is specified in the next section.

After the client retrieves and parses the manifest file, it ascertains what **OALs** are associated with this OAB. The client can retrieve each OAL in the OAB independently.

For each file that has to be retrieved, the client constructs the URI according to the following definition, and then it retrieves each of those URIs by using the HTTP/1.1 protocol [\[RFC2616\]](#), as follows:

```
dataFileURI = wdpUri "/" file
```

#### 2.2.1.1 Manifest File Structure

The manifest file structure is a well-formed XML document, as specified in [\[XML10\]](#), and has the following ABNF structure, as per the specification of Augmented Backus-Naur Form (ABNF) semantics [\[RFC5234\]](#).

```
manifestDocument = prolog oabElement
prolog           = "<?xml" VersionInfo UTF8EncodingDecl "?>" *S
VersionInfo     = S "version" Eq (XMLQUOTE VersionNum XMLQUOTE)
VersionNum      = "1.0"
Eq              = "="
UTF8EncodingDecl = S "encoding" Eq XMLQUOTE "UTF-8" XMLQUOTE
oabElement      = oabSTag oabContent oabETag
oabSTag         = "<OAB>" *S
oabETag         = "</OAB>" *S
oabContent      = 1* oalElement
oalElement      = oalSTag S oalAttributes *S ">" *S oalContent oalETag
oalSTag         = "<OAL"
oalETag         = "</OAL>" *S
oalAttributes   = idAttribute S dnAttribute S nameAttribute
idAttribute     = "id=" XMLQUOTE guidString XMLQUOTE
dnAttribute     = "dn=" XMLQUOTE addresslist-legacy-dn XMLQUOTE
nameAttribute   = "name=" XMLQUOTE nestedUnicodeRdn XMLQUOTE
```

```

guidString          = 8HEX "-" 4HEX "-"4HEX "-" 4HEX "-" 12HEX
nestedUnicodeRdn   = 1*16 ( "\" unicodeRdn )
; the total length is limited to
; 1024 characters
unicodeRdn         = 1*1023 (NON-ZERO-OCTET)
NON-ZERO-OCTET     = %x01-FF ; Any octet (8-bit data unit) except for 0
oalContent         = fullElement 1*templateElement *diffElement
fullElement        = "<Full" S seq S ver S size S uncompressedsize S SHA ">" *S      file
*S "</Full>"
templateElement    = "<Template" S seq S ver S size S uncompressedsize S SHA S
langid S type ">" *S file *S "</Template>"
diffElement        = "<Diff" S seq S ver S size S uncompressedsize S SHA ">" *S
file *S "</Diff>"
seq                = "seq=" XMLQUOTE 1*DIGIT XMLQUOTE
; limited to values from 0 to 2147483648
ver                = "ver=" XMLQUOTE 1*DIGIT XMLQUOTE
; limited to values from 0 to 2147483648
size               = "size=" XMLQUOTE 1*DIGIT XMLQUOTE
uncompressedsize   = "uncompressedsize=" XMLQUOTE 1*DIGIT XMLQUOTE
SHA                = "SHA=" XMLQUOTE 40HEX XMLQUOTE
langid             = "langid=" XMLQUOTE 1*HEX XMLQUOTE
type               = "type=" XMLQUOTE ("mac" / "windows") XMLQUOTE
file               = *( NONDOT / DOT) 1* NONDOT
compressedfile     = file ".lzx"
addresslist-legacy-dn = "/guid=" 32(HEX) / "/" / legacy-dn
legacy-dn         = org org-unit 1*13(container) object-rdn
; legacy-dns are limited to 16 levels
org                = "/o=" rdn
org-unit           = "/ou=" rdn
container          = "/cn=" rdn
object-rdn         = "/cn=" rdn
rdn                = ( non-space-teletex ) /
( non-space-teletex *62(teletex-char)
non-space-teletex )
; rdn values are limited to 64 characters and
; the number of rdns is limited to 16 but the
; total cumulative length of rdn characters in
; a legacy-dn is limited to 256.

teletex-char      = " " / non-space-teletex
non-space-teletex = "!" / XMLQUOTE / "%" / "&" / "\" / "(" / ")" /
"*" / "+" / "," / "-" / "." / "0" / "1" /
"2" / "3" / "4" / "5" / "6" / "7" / "8" /
"9" / ":" / "<" / "=" / ">" / "?" / "@" /
"A" / "B" / "C" / "D" / "E" / "F" / "G" /
"H" / "I" / "J" / "K" / "L" / "M" / "N" /
"O" / "P" / "Q" / "R" / "S" / "T" / "U" /
"V" / "W" / "X" / "Y" / "Z" / "[" / "]" /
"_" / "a" / "b" / "c" / "d" / "e" / "f" /
"g" / "h" / "i" / "j" / "k" / "l" / "m" /
"n" / "o" / "p" / "q" / "r" / "s" / "t" /
"u" / "v" / "w" / "x" / "y" / "z" / "|"

DIGIT              = %x30-39
HEX                = DIGIT
/ "A" / "B" / "C" / "D" / "E" / "F"
/ "a" / "b" / "c" / "d" / "e" / "f"
S                  = 1*(%x20 / %x09 / %x0D / %x0A)
ALPHA              = %x41-5A / %x61-7A ; A-Z / a-z

```

XMLQUOTE	=	DQUOTE / "'"
DOT	=	"."
NONDOT	=	DIGIT / ALPHA / "-"
DQUOTE	=	%x22
		; " (Double Quote)

**oabElement:** The **oabElement** element in the document structure represents a top-level container in the hierarchy of the XML document, and it MUST contain one or more **oalElement** entities. The **oabElement** element does not have any attributes.

**oalElement:** The **oalElement** element is a container in the hierarchy of the XML document that contains the XML child elements **fullElement**, **templateElement**, and **diffElement**, and it represents an OAL that is part of the OAB. For an example of the XML structure, see section 4. The **oalElement** MUST have the following attributes:

- **id** (as specified in the **idAttribute** element): A string representation of randomly chosen **GUIDs** that uniquely represents the current OAL. This **id** remains the same through all subsequent OAB generations.
- **Dn:** The **distinguished name (DN)** of the OAL.
- **Name:** The name of the **address list**, prepended with "\".

For details about address lists, see [\[MS-OXOABK\]](#).

**fullElement:** Each **oalElement** element MUST contain exactly one **fullElement** element. The **fullElement** element provides information about the compressed full details file, as specified in [\[MS-OXOAB\]](#) section 2.11. The following attributes MUST be specified:

- **seq** – The OAL data sequence number.
- **ver** – The version of the data file, as specified in [\[MS-OXOAB\]](#).
- **size** – The size (in bytes) of the data file on the WDP.
- **uncompressedsize** – The size (in bytes) of the data file after decompression.
- **SHA** – The SHA1 checksum of the compressed file, calculated as specified in [\[FIPS180\]](#).
- **file** – The name of the data file on WDP. Although this file is not actually an element, it can be found in the XML content within the <Full> and </Full> tags.

**templateElement:** Each **oalElement** element MUST contain at least one **templateElement** element. The **templateElement** element provides information about the uncompressed display template file, as specified in [\[MS-OXOAB\]](#) section 2.2. The following attributes MUST be specified:

- **seq** – The OAL data sequence number. This is kept in sync with the sequence number of the **fullElement** element.
- **ver** – The version of the data file, as specified in [\[MS-OXOAB\]](#).
- **size** – The size (in bytes) of the data file on WDP.
- **uncompressedsize** – The size (in bytes) of the data file after decompression.
- **SHA** – The SHA1 checksum of the compressed file, calculated as specified in [\[FIPS180\]](#).

- **langid** – The template language identifier, as specified in [\[MS-LCID\]](#).
- **type** – A string representing the client platform, which is currently "windows" or "mac", as specified in [\[MS-OXOABKT\]](#).
- **file** – The name of the data file on WDP. Although this file is not actually an element, it can be found in the XML content within the <Template> and </Template> tags.

**diffElement:** Each **oalElement** element MUST contain zero or more **diffElements** element. The **diffElement** element provides information about the OAB v4 differential patch file, as specified in [\[MS-OXOAB\]](#) section 2.10. The following attributes MUST be specified:

- **seq** – The OAL data sequence number.
- **ver** – The version of the resulting data file that will be produced by applying this differential file.
- **size** – The size (in bytes) of data file on WDP.
- **uncompressedsize** – The size (in bytes) of data file after decompression.
- **SHA** – The SHA1 checksum of the compressed file, calculated as specified in [\[FIPS180\]](#).
- **file** – The name of the data file on WDP. Although this file is not actually an element, it can be found in the XML content within the <Diff> and </Diff> tags.

**seq attribute:** Each **fullElement**, **templateElement**, and **diffElement** element contains a **seq** attribute, which enables the optimizations for the client that are described in this section.

The client can internally maintain an integer value to store the sequence number of the last successfully downloaded OAL data. This enables the client to determine whether the server has any data that is newer than the data that is available on the client side. This internal value is referred to as **clientSequenceNumber**. If the client implementation maintains the **clientSequenceNumber** value, the client also has to store the OAL **id** to identify the OAL in future versions of the manifest. Additionally, the client has to store the last downloaded full details file so that it can build a new version of the data file by applying differential files to the older file.

As a result of parsing the manifest, the client finds the sequence number of the full OAL data file that is available on the server. This value is referred to as **serverSequenceNumber**. If **serverSequenceNumber** >= 2, there are zero or more differential details files with sequential sequence numbers from M to **serverSequenceNumber**, where  $2 \leq M \leq \text{serverSequenceNumber}$ . The number of differential details files depends on the server implementation.

If, for a particular OAL, the client has a copy of the full details file with the data sequence number **clientSequenceNumber**, and the manifest has differential details files from **clientSequenceNumber** to **serverSequenceNumber**, the client can download the differential detail files from **clientSequenceNumber** + 1 to **serverSequenceNumber** and apply them to the previously downloaded full details file to get to the latest version. Otherwise, the client can download a single full details file **serverSequenceNumber** value to bring itself up to date.

## **3 Protocol Details**

### **3.1 Server Details**

#### **3.1.1 Abstract Data Model**

None.

#### **3.1.2 Timers**

None.

#### **3.1.3 Initialization**

None.

#### **3.1.4 Higher-Layer Triggered Events**

None.

#### **3.1.5 Message Processing Events and Sequencing Rules**

None.

#### **3.1.6 Timer Events**

None.

#### **3.1.7 Other Local Events**

None.

## 4 Protocol Examples

The following is an example of the manifest file and corresponding WDP content. The OAB contains two address lists: "Global Address List," represented by the second OAL element, and "All Rooms," represented by the first OAL element. Both address lists include two templates, both with the language **id** value set to "0409" (English) both in Microsoft Windows and on the Macintosh. Both OALs have a full details data file and a differential details files. Note that the first OAL has the data sequence number 2 and only one differential file, whereas the second OAL has data sequence number 4 and three differential files.

```
<?xml version="1.0" encoding="UTF-8"?>
<OAB>
  <OAL id='f867b9e0-d01e-43e3-8708-ba86a1c77dff'
dn='/guid=F8E7206B268E404B9519453F0F184D24' name='\All Rooms'>
  <Full seq='2' ver='32' size='554' uncompressedsize='1165'
SHA='d626d8d782332b7e8d689eea266ee315c31f19da'>
    f867b9e0-d01e-43e3-8708-ba86a1c77dff-data-2.lzx
  </Full>
  <Template seq='2' ver='7' size='5794' uncompressedsize='25620'
SHA='53fb16d6dcd1a559b8649e9b269eee84b85c91b' langid='0409' type='windows'>
    f867b9e0-d01e-43e3-8708-ba86a1c77dff-lng0409-2.lzx
  </Template>
  <Template seq='2' ver='7' size='5794' uncompressedsize='25620'
SHA='53fb16d6dcd1a559b8649e9b269eee84b85c91b' langid='0409' type='mac'>
    f867b9e0-d01e-43e3-8708-ba86a1c77dff-mac0409-2.lzx
  </Template>
  <Diff seq='2' ver='32' size='132' uncompressedsize='1165'
SHA='f53ec568b6fc3e4adce0e7d7dfd5lace604a9234'>
    f867b9e0-d01e-43e3-8708-ba86a1c77dff-binpatch-2.lzx
  </Diff>
</OAL>
  <OAL id='2e3eaccd-85a0-4abe-84f8-603a49801bb6' dn='/' name='\Global Address List'>
  <Full seq='4' ver='32' size='574' uncompressedsize='1872'
SHA='91c1d0fa378dc961f9e8aafb17a9569767e21c73'>
    2e3eaccd-85a0-4abe-84f8-603a49801bb6-data-4.lzx
  </Full>
  <Template seq='4' ver='7' size='5794' uncompressedsize='25620'
SHA='53fb16d6dcd1a559b8649e9b269eee84b85c91b' langid='0409' type='windows'>
    2e3eaccd-85a0-4abe-84f8-603a49801bb6-lng0409-4.lzx
  </Template>
  <Template seq='4' ver='7' size='5794' uncompressedsize='25620'
SHA='53fb16d6dcd1a559b8649e9b269eee84b85c91b' langid='0409' type='mac'>
    2e3eaccd-85a0-4abe-84f8-603a49801bb6-mac0409-4.lzx
  </Template>
  <Diff seq='4' ver='32' size='132' uncompressedsize='1872'
SHA='49d0d0c8185dd93ba7df0fbc6b532049ba5a29c5'>
    2e3eaccd-85a0-4abe-84f8-603a49801bb6-binpatch-4.lzx
  </Diff>
  <Diff seq='2' ver='32' size='136' uncompressedsize='1197'
SHA='7e391a3fd934310489f87576ad6b6e1fd6fc1590'>
    2e3eaccd-85a0-4abe-84f8-603a49801bb6-binpatch-2.lzx
  </Diff>
  <Diff seq='3' ver='32' size='138' uncompressedsize='1544'
SHA='3eb5108d87e366681eb27be395f3ef7d9525c63f'>
    2e3eaccd-85a0-4abe-84f8-603a49801bb6-binpatch-3.lzx
  </Diff>
</OAL>
</OAB>
```

## 5 Security

### 5.1 Security Considerations for Implementers

The manifest file contains the results of the SHA-1 hashing calculation. Note, however, that the SHA-1 hash value is used as an optional means of checksum verification of the downloaded file, and it should not be used as a security feature. In particular, it does not prevent deliberate data tampering.

### 5.2 Index of Security Parameters

None.

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Office Outlook 2007
- Microsoft Outlook 2010
- Microsoft Outlook 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

## 7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 8 Index

### A

Abstract data model  
[server](#) 12  
[Applicability](#) 7

### C

[Capability negotiation](#) 7  
[Change tracking](#) 16

### D

Data model - abstract  
[server](#) 12

### F

[Fields - vendor-extensible](#) 7

### G

[Glossary](#) 5

### H

Higher-layer triggered events  
[server](#) 12

### I

[Implementer - security considerations](#) 14  
[Index of security parameters](#) 14  
[Informative references](#) 6  
Initialization  
[server](#) 12  
[Introduction](#) 5

### M

Message processing  
[server](#) 12  
[Message Structures message](#) 8  
Messages  
[Message Structures](#) 8  
[transport](#) 8

### N

[Normative references](#) 6

### O

Other local events  
[server](#) 12  
[Overview \(synopsis\)](#) 6

### P

[Parameters - security index](#) 14  
[Preconditions](#) 7  
[Prerequisites](#) 7  
[Product behavior](#) 15

### R

[References](#) 6  
[informative](#) 6  
[normative](#) 6  
[Relationship to other protocols](#) 6

### S

Security  
[implementer considerations](#) 14  
[parameter index](#) 14  
Sequencing rules  
[server](#) 12  
Server  
[abstract data model](#) 12  
[higher-layer triggered events](#) 12  
[initialization](#) 12  
[message processing](#) 12  
[other local events](#) 12  
[sequencing rules](#) 12  
[timer events](#) 12  
[timers](#) 12  
[Standards assignments](#) 7

### T

Timer events  
[server](#) 12  
Timers  
[server](#) 12  
[Tracking changes](#) 16  
[Transport](#) 8  
Triggered events - higher-layer  
[server](#) 12

### V

[Vendor-extensible fields](#) 7  
[Versioning](#) 7