

[MS-OXWSATT]: Attachment Handling Web Service Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
07/15/2009	1.0	Major	Initial Availability.
11/04/2009	1.0.1	Editorial	Revised and edited the technical content.
02/10/2010	2.0.0	Major	Updated and revised the technical content.
05/05/2010	3.0.0	Major	Updated and revised the technical content.
08/04/2010	3.1	Minor	Clarified the meaning of the technical content.
11/03/2010	4.0	Major	Significantly changed the technical content.
03/18/2011	5.0	Major	Significantly changed the technical content.
08/05/2011	5.1	Minor	Clarified the meaning of the technical content.
10/07/2011	5.1	No change	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1 Introduction	5
1.1 Glossary	5
1.2 References	5
1.2.1 Normative References	5
1.2.2 Informative References	6
1.3 Overview	6
1.4 Relationship to Other Protocols	7
1.5 Prerequisites/Preconditions	7
1.6 Applicability Statement	7
1.7 Versioning and Capability Negotiation	7
1.8 Vendor Extensible Fields	8
1.9 Standards Assignments	8
2 Messages	9
2.1 Transport	9
2.2 Common Message Syntax	9
2.2.1 Namespaces	9
2.2.2 Messages	9
2.2.3 Elements	9
2.2.4 Complex Types	9
2.2.4.1 t:ArrayOfAttachmentsType Complex Type	10
2.2.4.2 t:AttachmentIdType Complex Type	10
2.2.4.3 m:AttachmentInfoResponseMessageType Complex Type	11
2.2.4.4 t:AttachmentType Complex Type	12
2.2.4.5 t:FileAttachmentType Complex Type	13
2.2.4.6 t:ItemAttachmentType Complex Type	14
2.2.4.7 t:NonEmptyArrayOfRequestAttachmentIdsType Complex Type	15
2.2.4.8 t:RequestAttachmentIdType Complex Type	16
2.2.4.9 t:RootItemIdType Complex Type	16
2.2.5 Simple Types	17
2.2.6 Attributes	17
2.2.7 Groups	17
2.2.8 Attribute Groups	17
3 Protocol Details	18
3.1 ExchangeServicePortType Server Details	18
3.1.1 Abstract Data Model	18
3.1.2 Timers	18
3.1.3 Initialization	18
3.1.4 Message Processing Events and Sequencing Rules	18
3.1.4.1 CreateAttachment Operation	18
3.1.4.1.1 Messages	19
3.1.4.1.1.1 tns:CreateAttachmentSoapIn Message	19
3.1.4.1.1.2 tns:CreateAttachmentSoapOut Message	20
3.1.4.1.2 Elements	21
3.1.4.1.2.1 CreateAttachment Element	21
3.1.4.1.2.2 CreateAttachmentResponse Element	21
3.1.4.1.3 Complex Types	21
3.1.4.1.3.1 m:CreateAttachmentResponseType Complex Type	21
3.1.4.1.3.2 m:CreateAttachmentType Complex Type	22

3.1.4.2	DeleteAttachment Operation	23
3.1.4.2.1	Messages	23
3.1.4.2.1.1	tns>DeleteAttachmentSoapIn Message	24
3.1.4.2.1.2	tns>DeleteAttachmentSoapOut Message	24
3.1.4.2.2	Elements	25
3.1.4.2.2.1	DeleteAttachment Element	25
3.1.4.2.2.2	DeleteAttachmentResponse Element	25
3.1.4.2.3	Complex Types	25
3.1.4.2.3.1	m>DeleteAttachmentResponseMessageType Complex Type	26
3.1.4.2.3.2	m>DeleteAttachmentResponseType Complex Type	26
3.1.4.2.3.3	m>DeleteAttachmentType Complex Type	27
3.1.4.3	GetAttachment Operation	27
3.1.4.3.1	Messages	28
3.1.4.3.1.1	tns:GetAttachmentSoapIn Message	28
3.1.4.3.1.2	tns:GetAttachmentSoapOut Message	29
3.1.4.3.2	Elements	29
3.1.4.3.2.1	GetAttachment Element	29
3.1.4.3.2.2	GetAttachmentResponse Element	30
3.1.4.3.3	Complex Types	30
3.1.4.3.3.1	m:GetAttachmentResponseType Complex Type	30
3.1.4.3.3.2	m:GetAttachmentType Complex Type	30
3.1.4.3.3.3	t:AttachmentResponseShapeType Complex Type	31
3.1.5	Timer Events	32
3.1.6	Other Local Events	32
4	Protocol Examples	33
4.1	CreateAttachment Example	33
4.2	DeleteAttachment Example	34
4.3	GetAttachment Example	35
5	Security	37
5.1	Security Considerations for Implementers	37
5.2	Index of Security Parameters	37
6	Appendix A: Full WSDL	38
7	Appendix B: Full XML Schema	41
7.1	Messages Schema	41
7.2	Types Schema	43
8	Appendix C: Product Behavior	46
9	Change Tracking	47
10	Index	48

1 Introduction

The Attachment and Handling Web Service Protocol is used to create, delete, and get attachments on items on the server.

Sections 1.8, 2, and 3 of this specification are normative and contain RFC 2119 language. Section 1.5 and 1.9 are also normative but cannot contain RFC 2119 language. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

base64
Hypertext Transfer Protocol (HTTP)
Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)
XML

The following terms are defined in [\[MS-OXGLOS\]](#):

Attachment object
endpoint
mailbox
Message object
Multipurpose Internet Mail Extensions (MIME)
Simple Object Access Protocol (SOAP)
SOAP body
SOAP header
SOAP message
Uniform Resource Identifier (URI)
Uniform Resource Locator (URL)
Web Services Description Language (WSDL)
WSDL message
WSDL port type
XML namespace
XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXDCLI] Microsoft Corporation, "[Autodiscover Publishing and Lookup Protocol Specification](#)".

[MS-OXWSADISC] Microsoft Corporation, "[Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol Specification](#)".

[MS-OXWSCDATA] Microsoft Corporation, "[Common Web Service Data Types](#)".

[MS-OXWSCONT] Microsoft Corporation, "[Contacts Web Service Protocol Specification](#)".

[MS-OXWSCORE] Microsoft Corporation, "[Core Items Web Service Protocol Specification](#)".

[MS-OXWSGTZ] Microsoft Corporation, "[Get Server Time Zone Web Service Protocol Specification](#)".

[MS-OXWSMSG] Microsoft Corporation, "[E-Mail Message Types Web Service Protocol Specification](#)".

[MS-OXWSMTGS] Microsoft Corporation, "[Calendaring Web Service Protocol Specification](#)".

[MS-OXWSPOST] Microsoft Corporation, "[Post Items Web Service Protocol Specification](#)".

[MS-OXWSTASK] Microsoft Corporation, "[Tasks Web Service Protocol Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

[RFC3066] Alvestrand, H., "Tags for the Identification of Language", RFC 3066, January 2001, <http://www.ietf.org/rfc/rfc3066.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

1.3 Overview

The Attachment Handling Web Service Protocol enables clients to attach objects to messages. Clients use **Attachment objects** to associate files, OLE objects, other messages, or binary data with a particular **Message object**. Because Attachment objects are created, maintained, and accessed only in the context of a message, they are considered to be subobjects.

1.4 Relationship to Other Protocols

A client that implements this protocol can use the Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol [\[MS-OXWSADISC\]](#) or the Autodiscover Publishing and Lookup Protocol [\[MS-OXDSCLI\]](#) to identify the target **endpoint (4)** to use for each operation.

This protocol uses the **SOAP** protocol as described in [\[SOAP1.1\]](#) to specify the structure information exchanged between the client and server. This protocol uses the **XML** protocol as described in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#) to describe the message content sent to and from the server.

This protocol uses SOAP over **HTTP** as described in [\[RFC2616\]](#), and SOAP over **HTTPS** as described in [\[RFC2818\]](#), as shown in the following figure.




Figure 1: This protocol in relation to other protocols

1.5 Prerequisites/Preconditions

The endpoint (4) **URL** that is returned by either the Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol, as described in [\[MS-OXWSADISC\]](#), or the Autodiscover Publishing and Lookup Protocol, as described in [\[MS-OXDSCLI\]](#), is required to form the HTTP request to the Web server that hosts this protocol. The operations that this protocol defines cannot be accessed unless the correct endpoint (4) is identified in the HTTP Web requests that target this protocol.

1.6 Applicability Statement

The protocol specified in this document is applicable to environments that attach items to messages. This Web service protocol is applicable to SOAP-based clients [\[SOAP1.1\]](#).

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Supported Transports:** This protocol uses multiple transports with SOAP 1.1, as specified in section [2.1](#).
- **Protocol Versions:** This protocol has only one **WSDL port type** version. The **WSDL** version of the request is identified using the **t:RequestServerVersion** element as described in [\[MS-OXWSCDATA\]](#) section 2.2.4.8, and the version of the server responding to the request is identified using the **t:ServerVersionInfo** element as described in [\[MS-OXWSCDATA\]](#) section 2.2.4.9
- **Security and Authentication Methods:** This protocol relies on the Web server that is hosting it to perform authentication.

- **Localization:** This protocol includes text strings in various messages. Localization considerations for such strings are specified in sections [2.2](#) and [3.1.4](#)
- **Capability Negotiation:** This protocol does not support version negotiation.

1.8 Vendor Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

The SOAP version supported is SOAP 1.1. For details, see [\[SOAP1.1\]](#).

This protocol relies on the Web server that hosts the application to perform authentication. The protocol SHOULD use secure communications via HTTPS, as defined in [\[RFC2818\]](#).

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and Web Services Description Language (WSDL), as defined in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** by using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
tns	http://schemas.microsoft.com/exchange/services/2006/messages	
s	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]
targetNamespace	http://schemas.microsoft.com/exchange/services/2006/messages	
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
t	http://schemas.microsoft.com/exchange/services/2006/types	

2.2.2 Messages

This specification does not define any common **WSDL message** definitions.

2.2.3 Elements

This specification does not define any common XML schema element definitions.

2.2.4 Complex Types

The following table summarizes the set of common XML schema complex type definitions that are defined by this specification. XML schema complex type definitions that are specific to a particular operation are described with the operation.

Complex type name	Description
ArrayOfAttachmentsType	Represents an array of types based on attachments to the item.

Complex type name	Description
AttachmentIdType	Represents the item identifier and new change key of an item after an attachment has been attached.
AttachmentInfoResponseMessageType	Contains status and response data for attachment.
AttachmentType	Represents an attachment.
FileAttachmentType	Represents a file that is attached to an item in the server store.
t:ItemAttachmentType	Represents an item that is attached to another item.
NonEmptyArrayOfRequestAttachmentIdsType	Represents an array of attachment identifiers.
RequestAttachmentIdType	Represents the identifier for an attachment.
RootItemIdType	Identifies the root item of a deleted attachment.

2.2.4.1 t:ArrayOfAttachmentsType Complex Type

The **ArrayOfAttachmentsType** complex type represents an array of types based on attachments to the item. The **ArrayOfAttachmentsType** complex type is used only in the response message.

```
<xs:complexType name="ArrayOfAttachmentsType">
  <xs:choice
    minOccurs="0"
    maxOccurs="unbounded"
  >
    <xs:element name="ItemAttachment"
      type="t:ItemAttachmentType"
    />
    <xs:element name="FileAttachment"
      type="t:FileAttachmentType"
    />
  </xs:choice>
</xs:complexType>
```

The following table lists the child elements of the **ArrayOfAttachmentsType** complex type.

Element name	Type	Description
ItemAttachment	t:ItemAttachmentType (section 2.2.4.6)	Specifies an item that is attached to another item.
FileAttachment	t:FileAttachmentType (section 2.2.4.5)	Specifies a file that is attached to another item.

2.2.4.2 t:AttachmentIdType Complex Type

The **AttachmentIdType** complex type represents the item identifier and new change key of an item after an attachment has been attached. The **AttachmentIdType** complex type extends the **RequestAttachmentIdType** complex type, as specified in section [2.2.4.8](#).

```

<xs:complexType name="AttachmentIdType">
  <xs:complexContent>
    <xs:extension
      base="t:RequestAttachmentIdType"
    >
      <xs:attribute name="RootItemId"
        type="xs:string"
        use="optional"
      />
      <xs:attribute name="RootItemChangeKey"
        type="xs:string"
        use="optional"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table summarizes the set of common XML schema attribute definitions defined by this specification.

Attribute name	Type	Description
RootItemId	xs:string (XMLSCHEMA21)	Represents the unique identifier of the root store item to which the attachment is attached. The maximum length is 512 bytes after base64 decoding.
RootItemChangeKey	xs:string	Represents the change key of the root store item to which the attachment is attached. The maximum length is 512 bytes after base64 decoding.

2.2.4.3 m:AttachmentInfoResponseType Complex Type

The **AttachmentInfoResponseType** complex type contains status and response data for attachments. The **AttachmentInfoResponseType** complex type extends the **ResponseType** complex type, ([IMS-OXWSCDATA](#) section 2.2.3.52).

```

<xs:complexType name="AttachmentInfoResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:ResponseType"
    >
      <xs:sequence>
        <xs:element name="Attachments"
          type="t:ArrayOfAttachmentsType"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table lists the child element of the **AttachmentInfoResponseType** complex type.

Element name	Type	Description
Attachments	t:ArrayOfAttachmentsType (section 2.2.4.1)	Represents an array of types based on attachments on the item. The ArrayOfAttachmentsType complex type is used only in the response message.

2.2.4.4 t:AttachmentType Complex Type

The **AttachmentType** complex type represents an attachment.

```

<xs:complexType name="AttachmentType">
  <xs:sequence>
    <xs:element name="AttachmentId"
      type="t:AttachmentIdType"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="Name"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="ContentType"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="ContentId"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="ContentLocation"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="Size"
      type="xs:int"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="LastModifiedTime"
      type="xs:dateTime"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="IsInline"
      type="xs:boolean"
      minOccurs="0"
      maxOccurs="1"
    />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **AttachmentType** complex type.

Element name	Type	Description
AttachmentId	t:AttachmentIdType (section 2.2.4.2)	Specifies the attachment identifier.
Name	xs:string ([XMLSCHEMA2])	Specifies the descriptive name of the attachment.
ContentType	xs:string	Specifies the MIME type of the attachment content. For example: "text/enriched", "text/html", "text/plain", "text/rfc822-headers", "text/richtext", or "text/sgml".
ContentId	xs:string	Specifies the unique object identifier for an attachment.
ContentLocation	xs:string	Specifies the URI that corresponds to the location of the content of the attachment. The ContentLocation element can be used to associate an attachment with a URL that defines its location on the Web.
Size	xs:int ([XMLSCHEMA2])	Specifies an estimate of the size, in bytes, of the item's complete body.
LastModifiedTime	xs:dateTime ([XMLSCHEMA2])	Specifies the day and time that this item was last changed.
IsInline	xs:Boolean ([XMLSCHEMA2])	A Boolean value that indicates whether the attachment is an inline attachment. The IsInline element is set to indicate that the attachment appears inline within an item.

The **AttachmentType** complex type is extended by the **ItemAttachmentType** complex type, as specified in section [2.2.4.6](#), and the **FileAttachmentType** complex type, as specified in section [2.2.4.5](#).

2.2.4.5 t:FileAttachmentType Complex Type

The **FileAttachmentType** complex type represents a file that is attached to an item in the server store. The **FileAttachmentType** complex type extends the **AttachmentType** complex type, as specified in section [2.2.4.4](#).

```
<xs:complexType name="FileAttachmentType">
  <xs:complexContent>
    <xs:extension name="FileAttachmentType"
      base="t:AttachmentType"
    >
      <xs:sequence>
        <xs:element name="IsContactPhoto"
          type="xs:boolean"
          minOccurs="0"
          maxOccurs="1"
        />
        <xs:element name="Content"
          type="xs:base64Binary"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

```

        maxOccurs="1"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **FileAttachmentType** complex type.

Element name	Type	Description
IsContactPhoto	xs:boolean (XMLSCHEMA2)	A value that indicates whether this attachment is a contact photo. A text value of "true" indicates that the attachment is a contact photo.
Content	xs:base64Binary (XMLSCHEMA2)	Represents the base64-encoded contents of the file attachment.

2.2.4.6 t:ItemAttachmentType Complex Type

The **ItemAttachmentType** complex type represents an item that is attached to another item in the server store. The **ItemAttachmentType** complex type extends the **AttachmentType** complex type as specified in section [2.2.4.4](#).

```

<xs:complexType name="ItemAttachmentType">
  <xs:complexContent>
    <xs:extension
      base="t:AttachmentType"
    >
      <xs:choice
        minOccurs="0"
        maxOccurs="1"
      >
        <xs:element name="Item"
          type="t:ItemType"
        />
        <xs:element name="Message"
          type="t:MessageType"
        />
        <xs:element name="CalendarItem"
          type="t:CalendarItemType"
        />
        <xs:element name="Contact"
          type="t:ContactItemType"
        />
        <xs:element name="MeetingMessage"
          type="t:MeetingMessageType"
        />
        <xs:element name="MeetingRequest"
          type="t:MeetingRequestMessageType"
        />
        <xs:element name="MeetingResponse"
          type="t:MeetingResponseMessageType"
        />
        <xs:element name="MeetingCancellation"

```

```

        type="t:MeetingCancellationMessageType"
      />
    <xs:element name="Task"
      type="t:TaskType"
    />
    <xs:element name="PostItem"
      type="t:PostItemType"
    />
  </xs:choice>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **ItemAttachmentType** complex type.

Element name	Type	Description
Item	t:ItemType ([MS-OXWSCORE] section 2.2.4.6)	Represents a generic item in the server store.
Message	t:MessageType ([MS-OXWSMSG] section 2.2.4.1)	Represents a server e-mail message.
CalendarItem	t:CalendarItemType ([MS-OXWSMTGS] section 2.2.4.4)	Represents a calendar item.
Contact	t:ContactItemType ([MS-OXWSCONT] section 2.2.4.1)	Represents a contact item.
MeetingMessage	t:MeetingMessageType ([MS-OXWSMTGS] section 2.2.4.11)	Represents a meeting message in the server store.
MeetingRequest	t:MeetingRequestMessageType ([MS-OXWSMTGS] section 2.2.4.12)	Represents a meeting request in the server store.
MeetingResponse	t:MeetingResponseMessageType ([MS-OXWSMTGS] section 2.2.4.13)	Represents a meeting response in the server store.
MeetingCancellation	t:MeetingCancellationMessageType ([MS-OXWSMTGS] section 2.2.4.10)	Represents a meeting cancellation in the server store.
Task	t:TaskType ([MS-OXWSTASK] section 2.2.4.3)	Represents a task in the server store.
PostItem	t:PostItemType ([MS-OXWSPOST] section 2.2.4.1)	Represents a post item in the server store.

2.2.4.7 t:NonEmptyArrayOfRequestAttachmentIdsType Complex Type

The **NonEmptyArrayOfRequestAttachmentIdsType** complex type represents an array that contains attachment identifiers.

```
<xs:complexType name="NonEmptyArrayOfRequestAttachmentIdsType">
```

```

<xs:choice
  minOccurs="1"
  maxOccurs="unbounded"
>
  <xs:element name="AttachmentId"
    type="t:RequestAttachmentIdType"
  />
</xs:choice>
</xs:complexType>

```

The following table lists the child element of the **NonEmptyArrayOfRequestAttachmentIdsType** complex type.

Element name	Type	Description
AttachmentId	t:RequestAttachmentIdType section 2.2.4.8)	Represents an identifier for an attachment.

2.2.4.8 t:RequestAttachmentIdType Complex Type

The **RequestAttachmentIdType** complex type represents an identifier for an attachment. The **RequestAttachmentIdType** complex type extends the **BaseItemIdType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.12).

```

<xs:complexType name="RequestAttachmentIdType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseItemIdType"
    >
      <xs:attribute name="Id"
        type="xs:string"
        use="required"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table summarizes the set of common XML schema attribute definitions defined by this specification.

Attribute name	Type	Description
Id	xs:string ([XMLSCHEMA2])	Provides an identifier for an attachment. The maximum length is 512 bytes after base64 decoding.

2.2.4.9 t:RootItemIdType Complex Type

The **RootItemIdType** complex type identifies the root item of a deleted attachment and the new change key to the parent item. The **RootItemIdType** complex type extends the **BaseItemIdType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.12.)


```

<xs:complexType name="RootItemIdType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseItemIdType"
    >
      <xs:attribute name="RootItemId"
        type="xs:string"
        use="required"
      />
      <xs:attribute name="RootItemChangeKey"
        type="xs:string"
        use="required"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table summarizes the set of common XML schema attribute definitions defined by this specification.

Attribute name	Type	Description
RootItemId	xs:string (XMLSCHEMA21)	Identifies the root item of an attachment. The maximum length is 512 bytes after base64 decoding.
RootItemChangeKey	xs:string	Identifies the new change key of the root item of an attachment. The maximum length is 512 bytes after base64 decoding.

2.2.5 Simple Types

This specification does not define any common XML schema simple type definitions.

2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

3 Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state are required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

3.1 ExchangeServicePortType Server Details

The Attachment Handling Web Service Protocol defines a single WSDL port type with three operations. The operations enable client implementations to create, delete, and get attachments.

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that specified in this document.

The Attachment Handling Web Service Protocol is used to create, delete, and get attachments on items on the account's **mailbox** on the server.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

The following table summarizes the list of WSDL operations as defined by this specification:

Operation name	Description
CreateAttachment	Creates either an item or file attachment and attaches it to the specified item.
DeleteAttachment	Deletes file and item attachments from an existing item in the server store.
GetAttachment	Retrieves existing attachments on items in the server store.

3.1.4.1 CreateAttachment Operation

The **CreateAttachment** operation creates an item or file attachment on an item in the server store.

The following is the WSDL port type specification of the **CreateAttachment** operation.

```
<wsdl:operation name="CreateAttachment">
  <wsdl:input message="tns:CreateAttachmentSoapIn" />
  <wsdl:output message="tns:CreateAttachmentSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification of the **CreateAttachment** operation.

```
<wsdl:operation name="CreateAttachment">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/CreateAttachment" />
  <wsdl:input>
    <soap:header message="tns:CreateAttachmentSoapIn" part="Impersonation"
      use="literal"/>
    <soap:header message="tns:CreateAttachmentSoapIn" part="MailboxCulture"
      use="literal"/>
    <soap:header message="tns:CreateAttachmentSoapIn" part="RequestVersion"
      use="literal"/>
    <soap:header message="tns:CreateAttachmentSoapIn" part="TimeZoneContext"
      use="literal"/>
    <soap:body parts="request" use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="CreateAttachmentResult" use="literal" />
    <soap:header message="tns:CreateAttachmentSoapOut" part="ServerVersion"
      use="literal"/>
  </wsdl:output>
</wsdl:operation>
```

The protocol client sends a **CreateAttachmentSoapIn** request WSDL message, and the protocol server responds with a **CreateAttachmentSoapOut** response WSDL message.

An item attachment does not exist as a store item. It only exists as an attachment to an item or another attachment. Item attachments can be retrieved only by using the **GetAttachment** operation request.

A successful **CreateAttachment** operation request returns a **CreateAttachmentResponse** element with the **ResponseClass** attribute of the **CreateAttachmentResponseMessage** element set to "Success". The **ResponseCode** element of the **CreateAttachmentResponse** element is set to "NoError".

3.1.4.1.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to the **CreateAttachment** operation.

Message name	Description
CreateAttachmentSoapIn	Specifies the SOAP message that creates an attachment.
CreateAttachmentSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.1.1.1 tns:CreateAttachmentSoapIn Message

The **CreateAttachmentSoapIn** WSDL message specifies the **CreateAttachment** operation request to create an attachment.

```
<wsdl:message name="CreateAttachmentSoapIn">
  <wsdl:part name="request" element="tns:CreateAttachment" />
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

```
<wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>
```

The **CreateAttachmentSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/CreateAttachment>.

The five parts of the **CreateAttachmentSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	tns:CreateAttachment (section 3.1.4.1.2.1)	Specifies the SOAP body of the request create an attachment.
Impersonation	t:ExchangeImpersonation ([MS-OXWSCDATA] section 2.2.3.27)	Specifies a SOAP header that identifies the user whom the client application is impersonating.
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.3.36)	Specifies a SOAP header that identifies the culture to use for accessing the mailbox. The cultures are defined by [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.8)	Specifies a SOAP header that identifies the schema version for the CreateAttachment operation request.
TimeZoneContext	t:TimeZoneContext ([MS-OXWSGTZ] section 2.2.3.4)	Specifies a time zone definition and enables associating SOAP attributes with the definition.

3.1.4.1.1.2 tns:CreateAttachmentSoapOut Message

The **CreateAttachmentSoapOut** WSDL message specifies the server response to the **CreateAttachment** operation request to create an attachment.

```
<wsdl:message name="CreateAttachmentSoapOut">
  <wsdl:part name="CreateAttachmentResult" element="tns:CreateAttachmentResponse" />
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **CreateAttachmentSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/CreateAttachment>.

The two parts of the **CreateAttachmentSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
CreateAttachmentResult	tns:CreateAttachmentResponse (section 3.1.4.1.2.2)	Specifies the SOAP body of the response to a CreateAttachment operation request.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the server version for

Part name	Element/type	Description
		the response.

3.1.4.1.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
CreateAttachment	Specifies a request to create an attachment.
CreateAttachmentResponse	Specifies the response body content from a request to create an attachment.

3.1.4.1.2.1 CreateAttachment Element

The **CreateAttachment** element specifies the request message for a **CreateAttachment** operation.

```
<xs:element name="CreateAttachment"
  type="m:CreateAttachmentType"
/>
```

3.1.4.1.2.2 CreateAttachmentResponse Element

The **CreateAttachmentResponse** element specifies the response message for a **GetAttachment** operation.

```
<xs:element name="CreateAttachmentResponse"
  type="m:CreateAttachmentResponseType"
/>
```

3.1.4.1.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type name	Description
CreateAttachmentResponseType	Specifies a response message for the CreateAttachment operation.
CreateAttachmentType	Specifies request message for the CreateAttachment operation.

3.1.4.1.3.1 m:CreateAttachmentResponseType Complex Type

The **CreateAttachmentResponseType** complex type specifies the response message that is returned by the **CreateAttachment** operation. The **CreateAttachmentResponseType** complex

type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```
<xs:complexType name="CreateAttachmentResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseResponseMessageType"
    />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.1.3.2 m:CreateAttachmentType Complex Type

The **CreateAttachmentType** complex type specifies a request message to attach an item or file to a specified item in the server database. The **CreateAttachmentType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.14).

```
<xs:complexType name="CreateAttachmentType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    >
    <xs:sequence>
      <xs:element name="ParentItemId"
        type="t:ItemIdType"
      />
      <xs:element name="Attachments"
        type="t:NonEmptyArrayOfAttachmentsType"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexType>
```

The following table lists the child elements of the **CreateAttachmentType** complex type.

Element name	Type	Description
ParentItemId	t:ItemIdType ([MS-OXWSCORE] section 2.2.4.13)	Identifies the parent item in the server store that contains the attachment. The ParentItemId element MUST provide the ID of a store item. The ParentItemId element can be retrieved by using the GetItem operation.
Attachments	t:NonEmptyArrayOfAttachmentsType ([MS-OXWSCDATA] section 2.2.3.39)	Contains the items or files that are attached to an item in the server store.

3.1.4.2 DeleteAttachment Operation

The **DeleteAttachment** operation deletes an attachment from an item in the server store.

The following is the WSDL port type specification of the operation.

```
<wsdl:operation name="DeleteAttachment">
  <wsdl:input message="tns:DeleteAttachmentSoapIn" />
  <wsdl:output message="tns:DeleteAttachmentSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification of the operation.

```
<wsdl:operation name="DeleteAttachment">
  <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/DeleteAttachment" />
  <wsdl:input>
    <soap:header message="tns:DeleteAttachmentSoapIn" part="Impersonation"
use="literal"/>
    <soap:header message="tns:DeleteAttachmentSoapIn" part="MailboxCulture"
use="literal"/>
    <soap:header message="tns:DeleteAttachmentSoapIn" part="RequestVersion"
use="literal"/>
    <soap:body parts="request" use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="DeleteAttachmentResult" use="literal" />
    <soap:header message="tns:DeleteAttachmentSoapOut" part="ServerVersion"
use="literal"/>
  </wsdl:output>
</wsdl:operation>
```

The protocol client sends a **DeleteAttachmentSoapIn** request WSDL message, and the protocol server responds with a **DeleteAttachmentSoapOut** response WSDL message.

An item attachment does not exist as a store item. It only exists as an attachment to an item or another attachment. Item attachments can be retrieved only by using the **GetAttachment** operation request. Before an attachment can be deleted, the item **MUST** be retrieved from the server.

A successful **DeleteAttachment** operation request returns a **DeleteAttachmentResponse** element with the **ResponseClass** attribute of the **DeleteAttachmentResponseMessage** element set to "Success". The **ResponseCode** element of the **DeleteAttachmentResponse** element is set to "NoError".

3.1.4.2.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
DeleteAttachmentSoapIn	Specifies the SOAP message that deletes an attachment.
DeleteAttachmentSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.2.1.1 tns:DeleteAttachmentSoapIn Message

The **DeleteAttachmentSoapIn** WSDL message specifies the **DeleteAttachment** operation request to delete an attachment.

```
<wsdl:message name="DeleteAttachmentSoapIn">
  <wsdl:part name="request" element="tns:DeleteAttachment" />
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

The **DeleteAttachmentSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/DeleteAttachment>.

The four parts of the **DeleteAttachmentSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	tns:DeleteAttachment (section 3.1.4.2.2.1)	Specifies the SOAP body of the request to delete an attachment.
Impersonation	t:ExchangeImpersonation ([MS-OXWSCDATA] section 2.2.3.27)	Specifies a SOAP header that identifies the user who the client application is impersonating .
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.3.36)	Specifies a SOAP header that identifies the culture to use for accessing the mailbox. The cultures are defined by [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.8)	Specifies a SOAP header that identifies the schema version for the DeleteAttachment operation request.

3.1.4.2.1.2 tns:DeleteAttachmentSoapOut Message

The **DeleteAttachmentSoapOut** WSDL message specifies the server response to the **DeleteAttachment** operation request to delete an attachment.

```
<wsdl:message name="DeleteAttachmentSoapOut">
  <wsdl:part name="DeleteAttachmentResult" element="tns:DeleteAttachmentResponse" />
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **DeleteAttachmentSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/DeleteAttachment>.

The two parts of the **DeleteAttachmentSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
DeleteAttachmentResult	tns:DeleteAttachmentResponse (section 3.1.4.2.2.2)	Specifies the SOAP body of the response to a

Part name	Element/type	Description
		DeleteAttachment operation request.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the server version for the response.

3.1.4.2.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
DeleteAttachment	Specifies a request to delete an attachment.
DeleteAttachmentResponse	Specifies the response body content from a request to delete an attachment.

3.1.4.2.2.1 DeleteAttachment Element

The **DeleteAttachment** element specifies the request message for a **DeleteAttachment** operation.

```
<xs:element name="DeleteAttachment"
  type="m:DeleteAttachmentType"
/>
```

3.1.4.2.2.2 DeleteAttachmentResponse Element

The **DeleteAttachmentResponse** element specifies the response message for a **DeleteAttachment** operation.

```
<xs:element name="DeleteAttachmentResponse"
  type="m:DeleteAttachmentResponseType"
/>
```

3.1.4.2.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type name	Description
DeleteAttachmentResponseMessageType	Specifies the parent item of a deleted attachment.
DeleteAttachmentResponseType	Specifies a response message for the DeleteAttachment operation.

Complex type name	Description
DeleteAttachmentType	Specifies a request message for the DeleteAttachment operation.

3.1.4.2.3.1 m:DeleteAttachmentResponseMessageType Complex Type

The **DeleteAttachmentResponseMessageType** complex type contains the status and result of a single **DeleteAttachment** operation. The **DeleteAttachmentResponseMessageType** complex type extends the **ResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.52).

```
<xs:complexType name="DeleteAttachmentResponseMessageType">
  <xs:complexContent>
    <xs:extension
      base="m:ResponseMessageType"
    >
      <xs:sequence>
        <xs:element name="RootItemId"
          type="t:RootItemIdType"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists the child element of the **DeleteAttachmentResponseMessageType** complex type.

Element name	Type	Description
RootItemId	t:RootItemIdType (section 2.2.4.9)	Specifies the parent item of a deleted attachment.

3.1.4.2.3.2 m:DeleteAttachmentResponseType Complex Type

The **DeleteAttachmentResponseType** complex type specifies the response message that is returned by the **DeleteAttachment** operation. The **DeleteAttachmentResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```
<xs:complexType name="DeleteAttachmentResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseResponseMessageType"
    />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.2.3.3 m:DeleteAttachmentType Complex Type

The **DeleteAttachmentType** complex type specifies a request message to delete an attachment on an item in the server database. The **DeleteAttachmentType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.14).

```
<xs:complexType name="DeleteAttachmentType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    >
      <xs:sequence>
        <xs:element name="AttachmentIds"
          type="t:NonEmptyArrayOfRequestAttachmentIdsType"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists the child element of the **DeleteAttachmentType** complex type.

Element name	Type	Description
AttachmentIds	t:NonEmptyArrayOfRequestAttachmentIdsType (section 2.2.4.7)	Contains the items or files that are attached to an item in the server store to be deleted.

3.1.4.3 GetAttachment Operation

The **GetAttachment** operation gets an attachment from an item in the server store.

The following is the WSDL port type specification of the operation.

```
<wsdl:operation name="GetAttachment">
  <wsdl:input message="tns:GetAttachmentSoapIn" />
  <wsdl:output message="tns:GetAttachmentSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification of the operation.

```
<wsdl:operation name="GetAttachment">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetAttachment" />
  <wsdl:input>
    <soap:header message="tns:GetAttachmentSoapIn" part="Impersonation" use="literal"/>
    <soap:header message="tns:GetAttachmentSoapIn" part="MailboxCulture" use="literal"/>
    <soap:header message="tns:GetAttachmentSoapIn" part="RequestVersion" use="literal"/>
    <soap:header message="tns:GetAttachmentSoapIn" part="TimeZoneContext" use="literal"/>
    <soap:body parts="request" use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="GetAttachmentResult" use="literal" />
  </wsdl:output>
</wsdl:operation>
```

```

        <soap:header message="tns:GetAttachmentSoapOut" part="ServerVersion" use="literal"/>
    </wsdl:output>
</wsdl:operation>

```

The protocol client sends a **GetAttachmentSoapIn** request WSDL message, and the protocol server responds with a **GetAttachmentSoapOut** response WSDL message.

A successful **GetAttachment** operation request returns a **GetAttachmentResponse** element with the **ResponseClass** attribute of the **GetAttachmentResponseMessage** element set to "Success". The **ResponseCode** element of the **GetAttachmentResponse** element is set to "NoError".

3.1.4.3.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
GetAttachmentSoapIn	Specifies the SOAP message that gets an attachment.
GetAttachmentSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.3.1.1 tns:GetAttachmentSoapIn Message

The **GetAttachmentSoapIn** WSDL message specifies the **GetAttachment** operation request to get an attachment.

```

<wsdl:message name="GetAttachmentSoapIn">
  <wsdl:part name="request" element="tns:GetAttachment" />
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>

```

The **GetAttachmentSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetAttachment>.

The five parts of the **GetAttachmentSoapIn** message are described in the following table.

Part name	Element/type	Description
request	tns:GetAttachment (section 3.1.4.3.2.1)	Specifies the SOAP body of the request to get an attachment.
Impersonation	t:ExchangeImpersonation ([MS-OXWSCDATA] section 2.2.3.27)	Specifies a SOAP header that identifies the user who the client application is impersonating.
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.3.36)	Specifies a SOAP header that identifies the culture to use for accessing the mailbox. The cultures are defined by [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.8)	Specifies a SOAP header that identifies the schema version for the GetAttachment

Part name	Element/type	Description
		operation request.
TimeZoneContext	t:TimeZoneContext ([MS-OXWSGTZ] section 2.2.3.4)	Specifies a time zone definition and enables associating SOAP attributes with the definition.

3.1.4.3.1.2 tns:GetAttachmentSoapOut Message

The **GetAttachmentSoapOut** WSDL message specifies the server response to the **GetAttachment** operation request to get an attachment.

```
<wsdl:message name="GetAttachmentSoapOut">
  <wsdl:part name="GetAttachmentResult" element="tns:GetAttachmentResponse" />
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **GetAttachmentSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetAttachment>.

The two parts of the **GetAttachmentSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
GetAttachmentResult	tns:GetAttachmentResponse (section 3.1.4.3.2.2)	Specifies the SOAP body of the response to a GetAttachment operation request.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the server version for the response.

3.1.4.3.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
GetAttachment	Specifies a request to get an attachment.
GetAttachmentResponse	Specifies the response body content from a request to get an attachment.

3.1.4.3.2.1 GetAttachment Element

The **GetAttachment** element specifies the request message for a **GetAttachment** operation.

```
<xs:element name="GetAttachment"
  type="m:GetAttachmentType"
/>
```

3.1.4.3.2 GetAttachmentResponse Element

The **GetAttachmentResponse** element specifies the response message to a **GetAttachment** operation.

```
<xs:element name="GetAttachmentResponse"
  type="m:GetAttachmentResponseType"
/>
```

3.1.4.3.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type name	Description
GetAttachmentResponseType	Specifies a response message for the GetAttachment operation.
GetAttachmentType	Specifies a request message for the GetAttachment operation.
AttachmentResponseShapeType	Specifies additional properties for the GetAttachment operation to return.

3.1.4.3.3.1 m:GetAttachmentResponseType Complex Type

The **GetAttachmentResponseType** complex type specifies the response message that is returned by the **GetAttachment** operation. The **GetAttachmentResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```
<xs:complexType name="GetAttachmentResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseResponseMessageType"
    />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.3.3.2 m:GetAttachmentType Complex Type

The **GetAttachmentType** complex type specifies a request message to get attached items and files on an item in the server database. The **GetAttachmentType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.14).

```
<xs:complexType name="GetAttachmentType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    >
    <xs:sequence>
      <xs:element name="AttachmentShape"
        type="t:AttachmentResponseShapeType"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexContent>
</xs:complexType>
```

```

    />
    <xs:element name="AttachmentIds"
      type="t:NonEmptyArrayOfRequestAttachmentIdsType"
    />
  </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **GetAttachmentType** complex type.

Element name	Type	Description
AttachmentShape	t:AttachmentResponseShapeType (section 3.1.4.3.3.3)	Contains additional properties to return for the attachments.
AttachmentIds	t:NonEmptyArrayOfRequestAttachmentIdsType (section 2.2.4.7)	Contains the identifiers of the attachments to return in the response.

3.1.4.3.3 t:AttachmentResponseShapeType Complex Type

The **AttachmentResponseShapeType** complex type identifies additional properties for the **GetAttachment** operation to return.

```

<xs:complexType name="AttachmentResponseShapeType">
  <xs:sequence>
    <xs:element name="IncludeMimeContent"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="BodyType"
      type="t:BodyTypeResponseType"
      minOccurs="0"
    />
    <xs:element name="FilterHtmlContent"
      type="xs:boolean"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="AdditionalProperties"
      type="t:NonEmptyArrayOfPathsToElementType"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **AttachmentResponseShapeType** complex type.

Element name	Type	Description
IncludeMimeContent	xs:boolean ([XMLSCHEMA2])	Indicates whether the MIME

Element name	Type	Description
		content of an item or attachment is returned in a response. A text value of "true" indicates that the attachment contains MIME content.
BodyType	t:BodyTypeResponseType ([MS-OXWSCDATA] section 2.2.2.1)	Represents the format of the body text in a response.
FilterHtmlContent	xs:boolean ([XMLSCHEMA2])	Indicates whether to filter potentially unsafe HTML content from message bodies. A text value of "true" indicates that potentially unsafe HTML content is to be filtered from the attachment.
AdditionalProperties	t:NonEmptyArrayOfPathsToElementType ([MS-OXWSCDATA] section 2.2.3.40)	Contains additional properties to return in a response.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

The following examples show the request and response XML for the Attachment Handling Web Service Protocol operations.

4.1 CreateAttachment Example

The following is an example of a **CreateAttachment** operation, which creates an attachment named Deleteme.txt on the specified message. The item that it is attached to, which is represented by the **ParentItemId** element, is created separately. The **Id** attribute of the **ParentItemId** element has been shortened to preserve readability.

The client constructs the request XML and sends it to the server.

```
<?xml version="1.0" encoding="utf-8" ?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2010" />
  </soap:Header>
  <soap:Body>
    <m:CreateAttachment>
      <m:ParentItemId Id="AAMkAGIwODEy" />
      <m:Attachments>
        <t:FileAttachment>
          <t:Name>Deleteme.txt</t:Name>
          <t:IsInline>>false</t:IsInline>
          <t:IsContactPhoto>>false</t:IsContactPhoto>
          <t:Content>UGxLYXNlIGRlbGV0ZSB0aGlzIGZpbGUu</t:Content>
        </t:FileAttachment>
      </m:Attachments>
    </m:CreateAttachment>
  </soap:Body>
</soap:Envelope>
```

The server constructs the response XML and sends it to the client. The **Id**, **RootItemId**, and **RootItemChangeKey** attributes of the **AttachmentId** element have been shortened to preserve readability.

```
<?xml version="1.0" encoding="utf-8" ?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="14"
      MinorVersion="1" MajorBuildNumber="63"
      MinorBuildNumber="0"
      Version="Exchange2010"
      xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xmlns:xsd="http://www.w3.org/2001/XMLSchema" />
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <m:CreateAttachmentResponse
```

```

    xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
    xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types">
  <m:ResponseMessages>
    <m:CreateAttachmentResponseMessage ResponseClass="Success">
      <m:ResponseCode>NoError</m:ResponseCode>
      <m:Attachments>
        <t:FileAttachment>
          <t:AttachmentId Id="AAMkAGIwODEyY" RootItemId="AAMkAGIwODEyY"
RootItemChangeKey="CQAAABYAAADL " />
        </t:FileAttachment>
      </m:Attachments>
    </m:CreateAttachmentResponseMessage>
  </m:ResponseMessages>
</m:CreateAttachmentResponse>
</s:Body>
</s:Envelope>

```

4.2 DeleteAttachment Example

The following is an example of a **DeleteAttachment** operation. This example deletes an attachment from an item.

The client has to have the identifier for the item that has the attachment. The client constructs the request XML and sends it to the server. The **Id** attribute of the **AttachmentId** element has been shortened to preserve readability.

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2010" />
  </soap:Header>
  <soap:Body>
    <m>DeleteAttachment>
      <m:AttachmentIds>
        <t:AttachmentId Id="AAMkAGY4YzQw" />
      </m:AttachmentIds>
    </m>DeleteAttachment>
  </soap:Body>
</soap:Envelope>

```

The server constructs the response XML and sends it to the client. The **RootItemId** and **RootItemChangeKey** attributes of the **RootItemId** element have been shortened to preserve readability.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="14"
      MinorVersion="1"
      MajorBuildNumber="63" MinorBuildNumber="0"
      Version="Exchange2010"
    xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
    xmlns="http://schemas.microsoft.com/exchange/services/2006/types">

```

```

        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" />
</s:Header>
<s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <m:DeleteAttachmentResponse
xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types">
    <m:ResponseMessages>
      <m:DeleteAttachmentResponseMessage xsi:type="m:DeleteAttachmentResponseMessageType"
ResponseClass="Success">
        <m:ResponseCode>NoError</m:ResponseCode>
        <m:RootItemId RootItemId="AAMkAGY4YzQw=" RootItemChangeKey="CQAAABYAAA" />
      </m:DeleteAttachmentResponseMessage>
    </m:ResponseMessages>
  </m:DeleteAttachmentResponse>
</s:Body>
</s:Envelope>

```

4.3 GetAttachment Example

The following is an example of a **GetAttachment** operation. This example gets an attachment from the server store.

The client constructs the request XML and sends it to the server. The **Id** attribute of the **AttachmentId** element has been shortened to preserve readability.

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2010" />
  </soap:Header>
  <soap:Body>
    <m:GetAttachment>
      <m:AttachmentIds>
        <t:AttachmentId Id="AAMkAGY4YzQw" />
      </m:AttachmentIds>
    </m:GetAttachment>
  </soap:Body>
</soap:Envelope>

```

The server constructs the response XML and sends it to the client. In this example, there is one attachment in the attachments collection. The **Id** attribute of the **AttachmentId** element has been shortened to preserve readability. Note that the content is base64.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="14"
MinorVersion="1"
MajorBuildNumber="63"
MinorBuildNumber="0"

```

```
    Version="Exchange2010"
xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" />
</s:Header>
<s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <m:GetAttachmentResponse
xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types">
    <m:ResponseMessages>
      <m:GetAttachmentResponseMessage ResponseClass="Success">
        <m:ResponseCode>NoError</m:ResponseCode>
        <m:Attachments>
          <t:FileAttachment>
            <t:AttachmentId Id="AAMkAGY4YzQw" />
            <t:Name>Deleteme.txt</t:Name>
            <t:Content>UGxlyXNlIGRlbGV0ZSB0aGlzIHRleHQw</t:Content>
          </t:FileAttachment>
        </m:Attachments>
      </m:GetAttachmentResponseMessage>
    </m:ResponseMessages>
  </m:GetAttachmentResponse>
</s:Body>
</s:Envelope>
```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

The following table lists the XML files that are required to implement the functionality that is specified in this document.

File name	Description	Section
MS-OXWSATT.wsdl	Contains the WSDL for the implementation of this protocol.	6
MS-OXWSATT-messages.xsd	Contains the XML schema message definitions that are used in this protocol.	7.1
MS-OXWSATT-types.xsd	Contains the XML schema type definitions that are used in this protocol.	7.2

These files have to be placed in a common folder in order for the WSDL to validate and operate. Also, any schema files that are included in or imported into the MS-OXWSATT-types.xsd schema or the MS-OXWSATT-messages.xsd schema have to be placed in the common folder with these files.

This section contains the contents of the MS-OXWSATT.wsdl file.

```
<?xml version="1.0" encoding="utf-8"?>
<wSDL:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:s="http://www.w3.org/2001/XMLSchema" xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages">
  <wSDL:types>
    <xs:schema id="messages" elementFormDefault="qualified" version="Exchange2010"
xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
      <xs:include schemaLocation="MS-OXWSATT-messages.xsd" />
    </xs:schema>
    <xs:schema id="types" elementFormDefault="qualified" version="Exchange2010"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
      <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
      <!-- Add global elements and types from types.xsd -->
    </xs:schema>
  </wSDL:types>
  <wSDL:portType name="ExchangeServicePortType">
    <wSDL:operation name="CreateAttachment"
xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/">
      <wSDL:input message="tns:CreateAttachmentSoapIn"/>
      <wSDL:output message="tns:CreateAttachmentSoapOut"/>
    </wSDL:operation>
    <wSDL:operation name="DeleteAttachment"
xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/">
      <wSDL:input message="tns>DeleteAttachmentSoapIn"/>
      <wSDL:output message="tns>DeleteAttachmentSoapOut"/>
    </wSDL:operation>
    <wSDL:operation name="GetAttachment" xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/">
```

```

        <wsdl:input message="tns:GetAttachmentSoapIn"/>
        <wsdl:output message="tns:GetAttachmentSoapOut"/>
    </wsdl:operation>
</wsdl:portType>
<wsdl:message name="CreateAttachmentSoapIn"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:part name="request" element="tns:CreateAttachment"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>
<wsdl:message name="CreateAttachmentSoapOut"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:part name="CreateAttachmentResult" element="tns:CreateAttachmentResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="DeleteAttachmentSoapIn"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:part name="request" element="tns>DeleteAttachment"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="DeleteAttachmentSoapOut"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:part name="DeleteAttachmentResult" element="tns>DeleteAttachmentResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="GetAttachmentSoapIn" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:part name="request" element="tns:GetAttachment"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>
<wsdl:message name="GetAttachmentSoapOut" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:part name="GetAttachmentResult" element="tns:GetAttachmentResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:binding name="ExchangeServiceBinding" type="tns:ExchangeServicePortType">
    <wsdl:documentation xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
        <wsi:Claim conformsTo="http://ws-i.org/profiles/basic/1.0"
xmlns:wsi="http://ws-i.org/schemas/conformanceClaim/">
        </wsi:claim>
    </wsdl:documentation>
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http" style="document"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    <wsdl:operation name="CreateAttachment"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
        <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/CreateAttachment"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
        <wsdl:input>
            <soap:header message="tns:CreateAttachmentSoapIn" part="Impersonation"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
            <soap:header message="tns:CreateAttachmentSoapIn" part="MailboxCulture"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
            <soap:header message="tns:CreateAttachmentSoapIn" part="RequestVersion"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">

```

```

        <soap:header message="tns:CreateAttachmentSoapIn" part="TimeZoneContext"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:body parts="request" use="literal"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    </wsdl:input>
    <wsdl:output>
        <soap:body parts="CreateAttachmentResult" use="literal"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:header message="tns:CreateAttachmentSoapOut" part="ServerVersion"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeleteAttachment"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/DeleteAttachment"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <wsdl:input>
        <soap:header message="tns>DeleteAttachmentSoapIn" part="Impersonation"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:header message="tns>DeleteAttachmentSoapIn" part="MailboxCulture"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:header message="tns>DeleteAttachmentSoapIn" part="RequestVersion"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:body parts="request" use="literal"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    </wsdl:input>
    <wsdl:output>
        <soap:body parts="DeleteAttachmentResult" use="literal"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:header message="tns>DeleteAttachmentSoapOut" part="ServerVersion"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAttachment" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetAttachment"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <wsdl:input>
        <soap:header message="tns:GetAttachmentSoapIn" part="Impersonation"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:header message="tns:GetAttachmentSoapIn" part="MailboxCulture"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:header message="tns:GetAttachmentSoapIn" part="RequestVersion"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:header message="tns:GetAttachmentSoapIn" part="TimeZoneContext"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:body parts="request" use="literal"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    </wsdl:input>
    <wsdl:output>
        <soap:body parts="GetAttachmentResult" use="literal"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
        <soap:header message="tns:GetAttachmentSoapOut" part="ServerVersion"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
</wsdl:definitions>

```


7 Appendix B: Full XML Schema

For ease of implementation, the following sections provide the full XML schema for this protocol.

Schema name	Prefix	Section
Messages schema	m:	7.1
Types schema	t:	7.2

These files have to be placed in a common folder in order for the WSDL to validate and operate. Also, any schema files that are included in or imported into the MS-OXWSATT-types.xsd or MS-OXWSATT-messages.xsd schemas have to be placed in the common folder along with the files listed in the table.

7.1 Messages Schema

This section contains the contents of the MS-OXWSATT-messages.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSATT-messages.xsd includes the file listed in the following table. For the schema file to operate correctly, this file has to be present in the folder that contains the WSDL, types schema, and messages schema files for this protocol.

File name	Defining specification
MS-OXWSCDATA-messages.xsd	[MS-OXWSCDATA] section 7.1

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:m=http://schemas.microsoft.com/exchange/services/2006/messages
  xmlns:tns=http://schemas.microsoft.com/exchange/services/2006/messages
  xmlns:t=http://schemas.microsoft.com/exchange/services/2006/types
  xmlns:xs=http://www.w3.org/2001/XMLSchema
  targetNamespace=http://schemas.microsoft.com/exchange/services/2006/messages
  elementFormDefault="qualified" version="Exchange2010" id="messages">
  <!--      CHANGE THE SCHEMA LOCATION TO REFLECT THE TYPES XSD ASSOCIATED WITH THIS
  DOCUMENT
  <xs:import namespace="http://schemas.microsoft.com/exchange/services/2006/types"
  schemaLocation="types.xsd"/>
  <xs:include/>
  -->
  <xs:include schemaLocation="MS-OXWSCDATA-messages.xsd"/>
  <xs:import namespace="http://schemas.microsoft.com/exchange/services/2006/types"
  schemaLocation="MS-OXWSATT-types.xsd"/>
  <xs:complexType name="AttachmentInfoResponseMessageType">
    <xs:complexContent>
      <xs:extension base="m:ResponseMessageType">
        <xs:sequence>
          <xs:element name="Attachments" type="t:ArrayOfAttachmentsType"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="CreateAttachment" type="m:CreateAttachmentType"/>
  <xs:element name="CreateAttachmentResponse" type="m:CreateAttachmentResponseType"/>
  <xs:complexType name="CreateAttachmentResponseType">
```

```

        <xs:complexContent>
            <xs:extension base="m:BaseResponseMessageType"/>
        </xs:complexContent>
    </xs:complexType>
    <xs:complexType name="CreateAttachmentType">
        <xs:complexContent>
            <xs:extension base="m:BaseRequestType">
                <xs:sequence>
                    <xs:element name="ParentItemId" type="t:ItemIdType"/>
                    <xs:element name="Attachments"
type="t:NonEmptyArrayOfAttachmentsType"/>
                </xs:sequence>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
    <xs:complexType name="DeleteAttachmentType">
        <xs:complexContent>
            <xs:extension base="m:BaseRequestType">
                <xs:sequence>
                    <xs:element name="AttachmentIds"
type="t:NonEmptyArrayOfRequestAttachmentIdsType"/>
                </xs:sequence>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="DeleteAttachment" type="m:DeleteAttachmentType"/>
    <xs:complexType name="DeleteAttachmentResponseType">
        <xs:complexContent>
            <xs:extension base="m:BaseResponseMessageType"/>
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="DeleteAttachmentResponse" type="m:DeleteAttachmentResponseType"/>
    <xs:complexType name="DeleteAttachmentResponseMessageType">
        <xs:complexContent>
            <xs:extension base="m:ResponseMessageType">
                <xs:sequence>
                    <xs:element name="RootItemId" type="t:RootItemIdType"
minOccurs="0"/>
                </xs:sequence>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
    <xs:complexType name="GetAttachmentType">
        <xs:complexContent>
            <xs:extension base="m:BaseRequestType">
                <xs:sequence>
                    <xs:element name="AttachmentShape"
type="t:AttachmentResponseShapeType" minOccurs="0"/>
                    <xs:element name="AttachmentIds"
type="t:NonEmptyArrayOfRequestAttachmentIdsType"/>
                </xs:sequence>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="GetAttachment" type="m:GetAttachmentType"/>
    <xs:complexType name="GetAttachmentResponseType">
        <xs:complexContent>
            <xs:extension base="m:BaseResponseMessageType"/>
        </xs:complexContent>

```

```

    </xs:complexType>
    <xs:element name="GetAttachmentResponse" type="m:GetAttachmentResponseType"/>
</xs:schema>

```

7.2 Types Schema

This section contains the contents of the MS-OXWSATT-types.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSATT-types.xsd includes the files listed in the following table. For the schema file to operate correctly, these files have to be present in the folder that contains the WSDL, types schema, and messages schema files for this protocol.

File name	Defining specification
MS-OXWSCONT-types.xsd	[MS-OXWSCONT] section 6.2
MS-OXWSMSG-types.xsd	[MS-OXWSMSG] section 7.1
MS-OXWSMTGS-types.xsd	[MS-OXWSMTGS] section 7.2
MS-OXWSPOST-types.xsd	[MS-OXWSPOST] section 6.2

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
  elementFormDefault="qualified" version="Exchange2010" id="types">
  <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
  <xs:include schemaLocation="MS-OXWSCONT-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSMSG-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSMTGS-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSPOST-types.xsd"/>
  <xs:complexType name="ArrayOfAttachmentsType">
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="ItemAttachment" type="t:ItemAttachmentType"/>
      <xs:element name="FileAttachment" type="t:FileAttachmentType"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="AttachmentIdType">
    <xs:complexContent>
      <xs:extension base="t:RequestAttachmentIdType">
        <xs:attribute name="RootItemId" type="xs:string" use="optional"/>
        <xs:attribute name="RootItemChangeKey" type="xs:string" use="optional"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="AttachmentResponseShapeType">
    <xs:sequence>
      <xs:element name="IncludeMimeContent" type="xs:boolean" minOccurs="0"/>
      <xs:element name="BodyType" type="t:BodyTypeResponseType" minOccurs="0"/>
      <xs:element name="FilterHtmlContent" type="xs:boolean" minOccurs="0"/>
      <xs:element name="AdditionalProperties"
        type="t:NonEmptyArrayOfPathsToElementType" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="AttachmentType">

```

```

    <xs:sequence>
      <xs:element name="AttachmentId" type="t:AttachmentIdType" minOccurs="0"/>
      <xs:element name="Name" type="xs:string" minOccurs="0"/>
      <xs:element name="ContentType" type="xs:string" minOccurs="0"/>
      <xs:element name="ContentId" type="xs:string" minOccurs="0"/>
      <xs:element name="ContentLocation" type="xs:string" minOccurs="0"/>
      <xs:element name="Size" type="xs:int" minOccurs="0"/>
      <xs:element name="LastModifiedTime" type="xs:dateTime" minOccurs="0"/>
      <xs:element name="IsInline" type="xs:boolean" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="FileAttachmentType">
    <xs:complexContent>
      <xs:extension base="t:AttachmentType">
        <xs:sequence>
          <xs:element name="IsContactPhoto" type="xs:boolean" minOccurs="0"/>
          <xs:element name="Content" type="xs:base64Binary" minOccurs="0"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="ItemAttachmentType">
    <xs:complexContent>
      <xs:extension base="t:AttachmentType">
        <xs:choice minOccurs="0">
          <xs:element name="Item" type="t:ItemType"/>
          <xs:element name="Message" type="t:MessageType"/>
          <xs:element name="CalendarItem" type="t:CalendarItemType"/>
          <xs:element name="Contact" type="t:ContactItemType"/>
          <xs:element name="MeetingMessage" type="t:MeetingMessageType"/>
          <xs:element name="MeetingRequest"
type="t:MeetingRequestMessageType"/>
          <xs:element name="MeetingResponse"
type="t:MeetingResponseMessageType"/>
          <xs:element name="MeetingCancellation"
type="t:MeetingCancellationMessageType"/>
          <xs:element name="Task" type="t:TaskType"/>
          <xs:element name="PostItem" type="t:PostItemType"/>
        </xs:choice>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="NonEmptyArrayOfRequestAttachmentIdsType">
    <xs:choice maxOccurs="unbounded">
      <xs:element name="AttachmentId" type="t:RequestAttachmentIdType"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="RequestAttachmentIdType">
    <xs:complexContent>
      <xs:extension base="t:BaseItemIdType">
        <xs:attribute name="Id" type="xs:string" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="RootItemIdType">
    <xs:complexContent>
      <xs:extension base="t:BaseItemIdType">
        <xs:attribute name="RootItemId" type="xs:string" use="required"/>
        <xs:attribute name="RootItemChangeKey" type="xs:string" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

```

```
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
</xs:schema>
```

8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

9 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

10 Index

A

Abstract data model
[server](#) 18
[Applicability](#) 7
[Attribute groups](#) 17
[Attributes](#) 17

C

[Capability negotiation](#) 7
[Change tracking](#) 47
[Complex types](#) 9
[m:AttachmentInfoResponseMessageType Complex Type](#) 11
[t:ArrayOfAttachmentsType Complex Type](#) 10
[t:AttachmentIdType Complex Type](#) 10
[t:AttachmentType Complex Type](#) 12
[t:FileAttachmentType Complex Type](#) 13
[t:ItemAttachmentType Complex Type](#) 14
[t:NonEmptyArrayOfRequestAttachmentIdsType Complex Type](#) 15
[t:RequestAttachmentIdType Complex Type](#) 16
[t:RootItemIdType Complex Type](#) 16

D

Data model - abstract
[server](#) 18

E

Events
[local - server](#) 32
[timer - server](#) 32

F

[Fields - vendor extensible](#) 8
[Full WSDL](#) 38

G

[Glossary](#) 5
[Groups](#) 17

I

[Implementer - security considerations](#) 37
[Index of security parameters](#) 37
[Informative references](#) 6
Initialization
[server](#) 18
[Introduction](#) 5

L

Local events
[server](#) 32

M

[m:AttachmentInfoResponseMessageType Complex Type complex type](#) 11
Message processing
[server](#) 18
Messages
[attribute groups](#) 17
[attributes](#) 17
[complex types](#) 9
[elements](#) 9
[enumerated](#) 9
[groups](#) 17
[m:AttachmentInfoResponseMessageType Complex Type complex type](#) 11
[namespaces](#) 9
[simple types](#) 17
[syntax](#) 9
[t:ArrayOfAttachmentsType Complex Type complex type](#) 10
[t:AttachmentIdType Complex Type complex type](#) 10
[t:AttachmentType Complex Type complex type](#) 12
[t:FileAttachmentType Complex Type complex type](#) 13
[t:ItemAttachmentType Complex Type complex type](#) 14
[t:NonEmptyArrayOfRequestAttachmentIdsType Complex Type complex type](#) 15
[t:RequestAttachmentIdType Complex Type complex type](#) 16
[t:RootItemIdType Complex Type complex type](#) 16
[transport](#) 9

N

[Namespaces](#) 9
[Normative references](#) 5

O

Operations
[CreateAttachment Operation](#) 18
[DeleteAttachment Operation](#) 23
[GetAttachment Operation](#) 27
[Overview \(synopsis\)](#) 6

P

[Parameters - security index](#) 37
[Preconditions](#) 7
[Prerequisites](#) 7
[Product behavior](#) 46

R

References

[informative](#) 6
[normative](#) 5
[Relationship to other protocols](#) 7

S

Security
[implementer considerations](#) 37
[parameter index](#) 37
Sequencing rules
[server](#) 18
Server
[abstract data model](#) 18
[CreateAttachment Operation operation](#) 18
[DeleteAttachment Operation operation](#) 23
[GetAttachment Operation operation](#) 27
[initialization](#) 18
[local events](#) 32
[message processing](#) 18
[sequencing rules](#) 18
[timer events](#) 32
[timers](#) 18
[Simple types](#) 17
[Standards assignments](#) 8
Syntax
[messages - overview](#) 9

T

[t:ArrayOfAttachmentsType Complex Type complex type](#) 10
[t:AttachmentIdType Complex Type complex type](#) 10
[t:AttachmentType Complex Type complex type](#) 12
[t:FileAttachmentType Complex Type complex type](#) 13
[t:ItemAttachmentType Complex Type complex type](#) 14
[t:NonEmptyArrayOfRequestAttachmentIdsType Complex Type complex type](#) 15
[t:RequestAttachmentIdType Complex Type complex type](#) 16
[t:RootItemIdType Complex Type complex type](#) 16
Timer events
[server](#) 32
Timers
[server](#) 18
[Tracking changes](#) 47
[Transport](#) 9
Types
[complex](#) 9
[simple](#) 17

V

[Vendor extensible fields](#) 8
[Versioning](#) 7

W

[WSDL](#) 38