

[MS-OXWSCDATA]: Common Web Service Data Types

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.msp>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
07/15/2009	1.0	Major	Initial Availability.
11/04/2009	2.0.0	Major	Updated and revised the technical content.
02/10/2010	2.1.0	Minor	Updated the technical content.
05/05/2010	3.0.0	Major	Updated and revised the technical content.
08/04/2010	4.0	Major	Significantly changed the technical content.
11/03/2010	4.1	Minor	Clarified the meaning of the technical content.
03/18/2011	5.0	Major	Significantly changed the technical content.
08/05/2011	6.0	Major	Significantly changed the technical content.

Table of Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	7
1.2.1 Normative References	7
1.2.2 Informative References	8
1.3 Overview	8
1.4 Relationship to Other Protocols	8
1.5 Prerequisites/Preconditions	8
1.6 Applicability Statement	8
1.7 Versioning and Capability Negotiation	8
1.8 Vendor-Extensible Fields	8
1.9 Standards Assignments	8
2 Messages	9
2.1 Transport	9
2.2 Common Message Syntax	9
2.2.1 Namespaces	9
2.2.2 Simple Types	9
2.2.2.1 t:BodyTypeResponseType Simple Type	9
2.2.2.2 t:BodyTypeType Simple Type	10
2.2.2.3 t:DayOfWeekIndexType Simple Type	10
2.2.2.4 t:DayOfWeekType Simple Type	11
2.2.2.5 t:DaysOfWeekType Simple Type	12
2.2.2.6 t:DefaultShapeNamesType Simple Type	13
2.2.2.7 t:DictionaryURIType Simple Type	13
2.2.2.8 t:DisposalType Simple Type	14
2.2.2.9 t:DistinguishedFolderIdNameType Simple Type	15
2.2.2.10 t:DistinguishedPropertySetType Simple Type	18
2.2.2.11 t:DistinguishedUserType Simple Type	19
2.2.2.12 t:ExceptionPropertyURIType Simple Type	19
2.2.2.13 t:ExchangeVersionType Simple Type	21
2.2.2.14 t:ExcludesAttributeType Simple Type	21
2.2.2.15 t:LegacyFreeBusyType Simple Type	22
2.2.2.16 t:MailboxTypeType Simple Type	23
2.2.2.17 t:MonthNamesType Simple Type	24
2.2.2.18 t:NonEmptyStringType Simple Type	25
2.2.2.19 t:ResponseClassType Simple Type	25
2.2.2.20 m:ResponseCodeType Simple Type	26
2.2.2.21 t:SensitivityChoicesType Simple Type	73
2.2.2.22 t:UnindexedFieldURIType Simple Type	73
2.2.3 Complex Types	91
2.2.3.1 t:AbsoluteMonthlyRecurrencePatternType Complex Type	91
2.2.3.2 t:AbsoluteYearlyRecurrencePatternType Complex Type	91
2.2.3.3 t:AcceptSharingInvitationType Complex Type	92
2.2.3.4 t:ArrayOfCalendarPermissionsType Complex Type	92
2.2.3.5 t:ArrayOfEmailAddressesType Complex Type	92
2.2.3.6 t:ArrayOfPermissionsType Complex Type	93
2.2.3.7 t:ArrayOfRealItemsType Complex Type	93
2.2.3.8 t:ArrayOfRecipientsType Complex Type	95
2.2.3.9 m:ArrayOfResponseMessagesType Complex Type	95

2.2.3.10	t:ArrayOfStringsType Complex Type	103
2.2.3.11	t:BaseEmailAddressType Complex Type	103
2.2.3.12	t:BaseItemIdType Complex Type	103
2.2.3.13	t:BasePathToElementType Complex Type	103
2.2.3.14	m:BaseRequestType Complex Type	104
2.2.3.15	m:BaseResponseMessageType Complex Type	104
2.2.3.16	t:BodyType Complex Type	104
2.2.3.17	t:ConnectingSIDType Complex Type	105
2.2.3.18	t:ConstantValueType Complex Type	105
2.2.3.19	t:DailyRecurrencePatternType Complex Type	106
2.2.3.20	t:DeletedOccurrenceInfoType Complex Type	106
2.2.3.21	t:DistinguishedFolderIdType Complex Type	106
2.2.3.22	t:Duration Complex Type	107
2.2.3.23	t:EffectiveRightsType Complex Type	108
2.2.3.24	t:EmailAddress	109
2.2.3.25	t:EmailAdressesType Complex Type	109
2.2.3.26	t:EndDateRecurrenceRangeType Complex Type	110
2.2.3.27	t:ExchangeImpersonationType Complex Type	111
2.2.3.28	t:FieldURIOrConstantType Complex Type	111
2.2.3.29	t:FolderIdType Complex Type	111
2.2.3.30	t:FolderResponseShapeType Complex Type	112
2.2.3.31	t:ForwardItemType Complex Type	113
2.2.3.32	t:InternetHeaderType Complex Type	113
2.2.3.33	t:IntervalRecurrencePatternBaseType Complex Type	113
2.2.3.34	m:ItemInfoResponseMessageType Complex Type	114
2.2.3.35	t:ItemResponseShapeType Complex Type	114
2.2.3.36	t:MailboxCultureType Complex Type	116
2.2.3.37	t:NoEndRecurrenceRangeType Complex Type	116
2.2.3.38	t:NonEmptyArrayOfAllItemsType Complex Type	117
2.2.3.39	t:NonEmptyArrayOfAttachmentsType Complex Type	119
2.2.3.40	t:NonEmptyArrayOfPathsToElementType Complex Type	120
2.2.3.41	t:NumberedRecurrenceRangeType Complex Type	120
2.2.3.42	t:PathToExceptionFieldType Complex Type	121
2.2.3.43	t:PathToIndexedFieldType Complex Type	121
2.2.3.44	t:PathToUnindexedFieldType Complex Type	122
2.2.3.45	t:RecurrencePatternBaseType Complex Type	122
2.2.3.46	t:RecurrenceRangeBaseType Complex Type	122
2.2.3.47	t:RelativeMonthlyRecurrencePatternType Complex Type	123
2.2.3.48	t:RelativeYearlyRecurrencePatternType Complex Type	123
2.2.3.49	t:ReplyAllToItemType Complex Type	124
2.2.3.50	t:ReplyBody	124
2.2.3.51	t:ReplyToItemType Complex Type	125
2.2.3.52	m:ResponseMessageType Complex Type	125
2.2.3.53	t:ResponseObjectCoreType Complex Type	126
2.2.3.54	t:ResponseObjectType Complex Type	127
2.2.3.55	t:SingleRecipientType Complex Type	127
2.2.3.56	t:SuppressReadReceiptType Complex Type	127
2.2.3.57	t:UserIdType Complex Type	128
2.2.3.58	t:Value Complex Type	129
2.2.3.59	t:WeeklyRecurrencePatternType Complex Type	129
2.2.3.60	t:WellKnownResponseObjectType Complex Type	130
2.2.4	Elements	132
2.2.4.1	t:DateTimePrecision Element	132

2.2.4.2	t:ExceptionFieldURI Element	132
2.2.4.3	t:ExchangeImpersonation Element	132
2.2.4.4	t:FieldURI Element.....	133
2.2.4.5	t:IndexedFieldURI Element	133
2.2.4.6	t:MailboxCulture Element	133
2.2.4.7	t:Path Element	133
2.2.4.8	t:RequestServerVersion Element	134
2.2.4.9	t:ServerVersionInfo Element	134
2.2.4.10	Value Element	135
2.2.5	Attributes.....	135
2.2.6	Groups.....	135
2.2.6.1	t:RecurrencePatternTypes Group	135
2.2.6.2	t:RecurrenceRangeTypes Group	136
2.2.6.3	t:TimeChangePatternTypes Group	137
2.2.7	Attribute Groups	137
2.2.7.1	t:FindResponsePagingAttributes Attribute Group.....	137
2.2.8	Messages	138
3	Protocol Details.....	139
3.1	Server Details	139
3.1.1	Abstract Data Model	139
3.1.2	Timers	139
3.1.3	Initialization	139
3.1.4	Message Processing Events and Sequencing Rules.....	139
3.1.5	Timer Events	139
3.1.6	Other Local Events	139
3.2	Client Details.....	139
3.2.1	Abstract Data Model	139
3.2.2	Timers	139
3.2.3	Initialization	139
3.2.4	Message Processing Events and Sequencing Rules.....	139
3.2.5	Timer Events	140
3.2.6	Other Local Events	140
4	Protocol Examples.....	141
5	Security.....	142
5.1	Security Considerations for Implementers.....	142
5.2	Index of Security Parameters	142
6	Appendix A: Full WSDL.....	143
7	Appendix B: Full XML Schema	144
7.1	Messages Schema.....	144
7.2	Types Schema.....	153
8	Appendix C: Product Behavior	170
9	Change Tracking.....	172
10	Index	174

1 Introduction

This document specifies the Web service data types that are common to more than one Web service protocol.

Sections 1.7 and 2 of this specification are normative and contain RFC 2119 language. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Coordinated Universal Time (UTC)

The following terms are defined in [\[MS-OXGLOS\]](#):

Calendar folder
delegate
Deleted Items folder
distribution list
Drafts folder
free/busy message
free/busy status
Hypertext Markup Language (HTML)
Inbox folder
Junk E-mail folder
mailbox
Multipurpose Internet Mail Extensions (MIME)
OOF message
Out of Office (OOF)
Outbox folder
plain text
public folder
Sent Items folder
Simple Mail Transfer Protocol (SMTP)
SOAP header
Uniform Resource Identifier (URI)
Web Services Description Language (WSDL)
XML namespace
XML schema

The following terms are specific to this document:

real item: An item that can be stored in a mail server database, such as a calendar item, task, or contact.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXWSADISC] Microsoft Corporation, "[Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol Specification](#)".

[MS-OXWSATT] Microsoft Corporation, "[Attachment Handling Web Service Protocol Specification](#)".

[MS-OXWSBTRF] Microsoft Corporation, "[Bulk Transfer Web Service Protocol Specification](#)".

[MS-OXWS CONV] Microsoft Corporation, "[Conversations Web Service Protocol Specification](#)".

[MS-OXWSCORE] Microsoft Corporation, "[Core Items Web Service Protocol Specification](#)".

[MS-OXWSCVTID] Microsoft Corporation, "[Convert Item Identifier Web Service Protocol Specification](#)".

[MS-OXWSDLIST] Microsoft Corporation, "[Distribution List Creation and Usage Web Service Protocol Specification](#)".

[MS-OXWSFOLD] Microsoft Corporation, "[Folders and Folder Permissions Web Service Protocol Specification](#)".

[MS-OXWSGTRM] Microsoft Corporation, "[Get Rooms List Web Service Protocol Specification](#)".

[MS-OXWSGTZ] Microsoft Corporation, "[Get Server Time Zone Web Service Protocol Specification](#)".

[MS-OXWSMSG] Microsoft Corporation, "[E-Mail Message Types Web Service Protocol Specification](#)".

[MS-OXWSMSHR] Microsoft Corporation, "[Folder Sharing Web Service Protocol Specification](#)".

[MS-OXWSMTRK] Microsoft Corporation, "[Message Tracking Web Service Protocol Specification](#)".

[MS-OXWSNTIF] Microsoft Corporation, "[Notifications Web Service Protocol Specification](#)".

[MS-OXWSPSNTIF] Microsoft Corporation, "[Push Notifications Web Service Protocol Specification](#)".

[MS-OXWSRSLNM] Microsoft Corporation, "[Resolve Recipient Names Web Service Protocol Specification](#)".

[MS-OXWSSRCH] Microsoft Corporation, "[Mailbox Search Web Service Protocol Specification](#)".

[MS-OXWSSYNC] Microsoft Corporation, "[Mailbox Contents Synchronization Web Service Protocol Specification](#)".

[MS-OXWSTASK] Microsoft Corporation, "[Tasks Web Service Protocol Specification](#)".

[MS-OXWSUSRCFG] Microsoft Corporation, "[User Configuration Web Service Protocol Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC3066] Alvestrand, H., "Tags for the Identification of Language", RFC 3066, January 2001, <http://www.ietf.org/rfc/rfc3066.txt>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA0] Fallside, D., Ed. and Walmsley, P., Ed., "XML Schema Part 0: Primer, Second Edition", W3C Recommendation, October 2004, <http://www.w3.org/TR/2004/REC-xmlschema-0-20041028/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

1.3 Overview

This specification defines the global elements, types, groups, and attribute groups that are common across the Web service protocols.

1.4 Relationship to Other Protocols

The information specified in this document applies to two or more Web service protocols.

1.5 Prerequisites/Preconditions

None.

1.6 Applicability Statement

The information in this specification applies to common Web service data types that are shared by two or more Web service protocols.

1.7 Versioning and Capability Negotiation

This specification does not cover versioning or capability negotiation.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

This document does not specify any transport-specific details.

2.2 Common Message Syntax

This section contains common definitions that are used by this specification. The syntax of the definitions uses **XML schema**, as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and **Web Services Description Language (WSDL)**, as defined in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** by using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
m	http://schemas.microsoft.com/exchange/services/2006/messages	
t	http://schemas.microsoft.com/exchange/services/2006/types	
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]
tns	http://schemas.microsoft.com/exchange/services/2006/messages	
targetNamespace	http://schemas.microsoft.com/exchange/services/2006/messages	

2.2.2 Simple Types

2.2.2.1 t:BodyTypeResponseType Simple Type

The **BodyTypeResponseType** simple type specifies the type of content that is returned for the body of an item.

```
<xs:simpleType name="BodyTypeResponseType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="Best"
    />
    <xs:enumeration
      value="HTML"
    />
    <xs:enumeration
      value="Text"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The values listed in the following table are defined by the **BodyTypeResponseType** simple type.

Value	Description
Best	Specifies that the response returns the richest available body content. This is useful if it is unknown whether the content is text or HTML .
HTML	Specifies that the response returns an item body as HTML.
Text	Specifies that the response returns an item body as plain text .

2.2.2.2 t:BodyTypeType Simple Type

The **BodyTypeType** simple type specifies the item body content type.

```
<xs:simpleType name="BodyTypeType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="HTML"
    />
    <xs:enumeration
      value="Text"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **BodyTypeType** simple type:

Value	Description
HTML	Specifies the item body as HTML content.
Text	Specifies the item body as text content.

2.2.2.3 t:DayOfWeekIndexType Simple Type

The **DayOfWeekIndexType** simple type specifies which week in a month is used in a relative recurrence pattern.

```
<xs:simpleType name="DayOfWeekIndexType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="First"
    />
    <xs:enumeration
      value="Fourth"
    />
  </xs:restriction>
</xs:simpleType>
```

```

    <xs:enumeration
      value="Last"
    />
    <xs:enumeration
      value="Second"
    />
    <xs:enumeration
      value="Third"
    />
  </xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **DayOfWeekIndexType** simple type:

Value	Description
First	Specifies that the first week in the month is used in the recurrence pattern.
Fourth	Specifies that the fourth week in the month is used in the recurrence pattern.
Last	Specifies that the last week in the month is used in the recurrence pattern.
Second	Specifies that the second week in the month is used in the recurrence pattern.
Third	Specifies that the third week in the month is used in the recurrence pattern.

2.2.2.4 t:DayOfWeekType Simple Type

The **DayOfWeekType** simple type specifies days of the week that are used in item recurrence patterns.

```

<xs:simpleType name="DayOfWeekType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="Day"
    />
    <xs:enumeration
      value="Friday"
    />
    <xs:enumeration
      value="Monday"
    />
    <xs:enumeration
      value="Saturday"
    />
    <xs:enumeration
      value="Sunday"
    />
    <xs:enumeration
      value="Thursday"
    />
    <xs:enumeration

```

```

        value="Tuesday"
      />
    <xs:enumeration
      value="Wednesday"
    />
    <xs:enumeration
      value="Weekday"
    />
    <xs:enumeration
      value="WeekendDay"
    />
  </xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **DayOfWeekType** simple type:

Value	Description
Day	Identifies every day as part of the recurrence pattern. This value MUST NOT be used in the t:RelativeYearlyRecurrencePatternType (section 2.2.3.48) and t:WeeklyRecurrencePatternType (section 2.2.3.59) complex types.
Friday	Identifies Fridays as part of the recurrence pattern.
Monday	Identifies Mondays as part of the recurrence pattern.
Saturday	Identifies Saturdays as part of the recurrence pattern.
Sunday	Identifies Sundays as part of the recurrence pattern.
Thursday	Identifies Thursdays as part of the recurrence pattern.
Tuesday	Identifies Tuesdays as part of the recurrence pattern.
Wednesday	Identifies Wednesdays as part of the recurrence pattern.
Weekday	Identifies weekdays as part of the recurrence pattern. This value MUST NOT be used in the t:RelativeYearlyRecurrencePatternType and t:WeeklyRecurrencePatternType types.
WeekendDay	Identifies weekend days as part of the recurrence pattern. This value MUST NOT be used in the t:RelativeYearlyRecurrencePatternType and t:WeeklyRecurrencePatternType types.

2.2.2.5 t:DaysOfWeekType Simple Type

The **DaysOfWeekType** simple type specifies days of the week that are used in item recurrence patterns.

```

<xs:simpleType name="DaysOfWeekType">
  <xs:list>
    <xs:itemType name="t:DayOfWeekType" />
  </xs:list>
</xs:simpleType>

```

The values for this type are defined in section [2.2.2.4](#).

The following is the syntax for this type.

```
<xs:simpleType name="DaysOfWeekType">
  <xs:list itemType="t:DayOfWeekType" />
</xs:simpleType>
```

2.2.2.6 t:DefaultShapeNamesType Simple Type

The **DefaultShapeNamesType** simple type specifies standard sets of properties to return in an item or folder response.

```
<xs:simpleType name="DefaultShapeNamesType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="AllProperties"
    />
    <xs:enumeration
      value="Default"
    />
    <xs:enumeration
      value="IdOnly"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **DefaultShapeNamesType** simple type:

Value	Description
AllProperties	Specifies all the properties that are defined for the AllProperties shape. This option does not specify all available properties for an item or folder.
Default	Specifies a set of properties that are defined as the default for the item or folder.
IdOnly	Specifies only the item or folder ID.

2.2.2.7 t:DictionaryURIType Simple Type

The **DictionaryURIType** simple type specifies frequently referenced dictionary properties by **URI**.

```
<xs:simpleType name="DictionaryURIType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
```

```

    value="contactsEmailAddress"
  />
<xs:enumeration
  value="contactsImAddress"
  />
<xs:enumeration
  value="contactsPhoneNumber"
  />
<xs:enumeration
  value="contactsPhysicalAddressCity"
  />
<xs:enumeration
  value="contactsPhysicalAddressCountryOrRegion"
  />
<xs:enumeration
  value="contactsPhysicalAddressPostalCode"
  />
<xs:enumeration
  value="contactsPhysicalAddressState"
  />
<xs:enumeration
  value="contactsPhysicalAddressStreet"
  />
<xs:enumeration
  value="itemInternetMessageHeader"
  />
</xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **DictionaryURIType** simple type:

Value	Description
contactsEmailAddress	Specifies the EmailAddresses property.
contactsImAddress	Specifies the ImAddresses property.
contactsPhoneNumber	Specifies the PhoneNumbers property.
contactsPhysicalAddressCity	Specifies the PhysicalAddressCity property.
contactsPhysicalAddressCountryOrRegion	Specifies the PhysicalAddressCountryOrRegion property.
contactsPhysicalAddressPostalCode	Specifies the PhysicalAddressPostalCode property.
contactsPhysicalAddressState	Specifies the PhysicalAddressState property.
contactsPhysicalAddressStreet	Specifies the PhysicalAddressStreet property.
itemInternetMessageHeader	Specifies the InternetMessageHeader property.

2.2.2.8 t:DisposalType Simple Type

The **DisposalType** simple type specifies how an item or folder is deleted.

```

<xs:simpleType name="DisposalType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="HardDelete"
    />
    <xs:enumeration
      value="MoveToDeletedItems"
    />
    <xs:enumeration
      value="SoftDelete"
    />
  </xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **DisposalType** simple type:

Value	Description
HardDelete	Specifies that an item or folder is permanently removed from the store.
MoveToDeletedItems	Specifies that an item or folder is moved to the Deleted Items folder .
SoftDelete	Specifies that an item or folder is moved to the dumpster if the dumpster is enabled.

The **m:DeleteFolderType** ([\[MS-OXWSFOLD\]](#) section 3.1.4.4.3.2) and **m:DeleteItemType** ([\[MS-OXWSCORE\]](#) section 3.1.4.3.1.2) complex types MUST specify a value for **DisposalType**.

2.2.2.9 t:DistinguishedFolderIdNameType Simple Type

The **DistinguishedFolderIdNameType** simple type specifies well-known folders that can be referenced by name. [<1>](#)

```

<xs:simpleType name="DistinguishedFolderIdNameType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="calendar"
    />
    <xs:enumeration
      value="contacts"
    />
    <xs:enumeration
      value="deleteditems"
    />
    <xs:enumeration
      value="drafts"
    />
    <xs:enumeration
      value="inbox"
    />
  </xs:restriction>
</xs:simpleType>

```

```
    />
  <xs:enumeration
    value="journal"
  />
  <xs:enumeration
    value="junkemail"
  />
  <xs:enumeration
    value="msgfolderroot"
  />
  <xs:enumeration
    value="notes"
  />
  <xs:enumeration
    value="outbox"
  />
  <xs:enumeration
    value="publicfoldersroot"
  />
  <xs:enumeration
    value="root"
  />
  <xs:enumeration
    value="searchfolders"
  />
  <xs:enumeration
    value="sentitems"
  />
  <xs:enumeration
    value="tasks"
  />
  <xs:enumeration
    value="voicemail"
  />
  <xs:enumeration
    value="recoverableitemsroot"
  />
  <xs:enumeration
    value="recoverableitemsdeletions"
  />
  <xs:enumeration
    value="recoverableitemsversions"
  />
  <xs:enumeration
    value="recoverableitemspurges"
  />
  <xs:enumeration
    value="archiveroot"
  />
  <xs:enumeration
    value="archivemsgfolderroot"
  />
  <xs:enumeration
    value="archiveddeleteditems"
  />
  <xs:enumeration
    value="archiverecoverableitemsroot"
  />
  <xs:enumeration
```



```

    value="archiverecoverableitemsdeletions"
  />
  <xs:enumeration
    value="archiverecoverableitemsversions"
  />
  <xs:enumeration
    value="archiverecoverableitemspurges"
  />
</xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **DistinguishedFolderIdNameType** simple type:

Value	Description
calendar	Specifies the default Calendar folder .
contacts	Specifies the default Contacts folder.
deleteditems	Specifies the Deleted Items folder.
drafts	Specifies the Drafts folder .
inbox	Specifies the Inbox folder .
journal	Specifies the Journal folder.
junkemail	Specifies the Junk E-mail folder .
msgfolderroot	Specifies the message folder root.
notes	Specifies the Notes folder.
outbox	Specifies the Outbox folder .
publicfoldersroot	Specifies the root public folder .
root	Specifies the root of the mailbox .
searchfolders	Specifies the Search Folders folder.
sentitems	Specifies the Sent Items folder .
tasks	Specifies the Tasks folder.
voicemail	Specifies the Voice Mail folder.
recoverableitemsroot	Specifies the dumpster root folder.
recoverableitemsdeletions	Specifies the dumpster deletions folder.
recoverableitemsversions	Specifies the dumpster versions folder.
recoverableitemspurges	Specifies the dumpster purges folder.
archiveroot	Specifies the root archive folder.

Value	Description
archivemsgfolderroot	Specifies the root archive message folder.
archivedeleteditems	Specifies the archive Deleted Items folder.
archiverecoverableitemsroot	Specifies the archive recoverable items root folder.
archiverecoverableitemsdeletions	Specifies the archive recoverable items deletions folder.
archiverecoverableitemsversions	Specifies the archive recoverable items versions folder.
archiverecoverableitemspurges	Specifies the archive recoverable items purges folder.

2.2.2.10 t:DistinguishedPropertySetType Simple Type

The **DistinguishedPropertySetType** simple type specifies the well-known property set IDs for extended properties.

```
<xs:simpleType name="DistinguishedPropertySetType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="Address"
    />
    <xs:enumeration
      value="Appointment"
    />
    <xs:enumeration
      value="CalendarAssistant"
    />
    <xs:enumeration
      value="Common"
    />
    <xs:enumeration
      value="InternetHeaders"
    />
    <xs:enumeration
      value="Meeting"
    />
    <xs:enumeration
      value="PublicStrings"
    />
    <xs:enumeration
      value="Task"
    />
    <xs:enumeration
      value="UnifiedMessaging"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **DistinguishedPropertySetType** simple type:

Value	Description
Address	Specifies the address property set ID by name.
Appointment	Specifies the appointment property set ID by name.
CalendarAssistant	Specifies the calendar assistant property set ID by name.
Common	Specifies the common property set ID by name.
InternetHeaders	Specifies the Internet headers property set ID by name.
Meeting	Specifies the meeting property set ID by name.
PublicStrings	Specifies the public strings property set ID by name.
Task	Specifies the task property set ID by name.
UnifiedMessaging	Specifies the Unified Messaging property set ID by name.

2.2.2.11 t:DistinguishedUserType Simple Type

The **DistinguishedUserType** simple type specifies distinguished user accounts.

```
<xs:simpleType name="DistinguishedUserType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="Default"
    />
    <xs:enumeration
      value="Anonymous"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **DistinguishedUserType** simple type:

Value	Description
Default	Specifies the default user account.
Anonymous	Specifies the anonymous user account.

2.2.2.12 t:ExceptionPropertyURIType Simple Type

The **ExceptionPropertyURIType** simple type specifies an offending property path in an error.

```
<xs:simpleType name="ExceptionPropertyURIType">
  <xs:restriction
    base="xs:string"
  >
```

```

<xs:enumeration
  value="attachmentContent"
/>
<xs:enumeration
  value="attachmentContentType"
/>
<xs:enumeration
  value="attachmentName"
/>
<xs:enumeration
  value="recurrenceDayOfMonth"
/>
<xs:enumeration
  value="recurrenceDayOfWeekIndex"
/>
<xs:enumeration
  value="recurrenceDaysOfWeek"
/>
<xs:enumeration
  value="recurrenceInterval"
/>
<xs:enumeration
  value="recurrenceMonth"
/>
<xs:enumeration
  value="recurrenceNumberOfOccurrences"
/>
<xs:enumeration
  value="timezoneOffset"
/>
</xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **ExceptionPropertyURIType** simple type:

Value	Description
attachmentContent	Specifies that the attachment Content property contains an error.
attachmentContentType	Specifies that the attachment ContentType property contains an error.
attachmentName	Specifies that the attachment Name property contains an error.
recurrenceDayOfMonth	Specifies that the recurrence DayOfMonth property contains an error.
recurrenceDayOfWeekIndex	Specifies that the recurrence DayOfWeekIndex property contains an error.
recurrenceDaysOfWeek	Specifies that the recurrence DaysOfWeek property contains an error.
recurrenceInterval	Specifies that the recurrence Interval property contains an error.
recurrenceMonth	Specifies that the recurrence Month property contains an error.

Value	Description
recurrenceNumberOfOccurrences	Specifies that the recurrence NumberOfOccurrences property contains an error.
timezoneOffset	Specifies that the time zone Offset property contains an error.

2.2.2.13 t:ExchangeVersionType Simple Type

The **ExchangeVersionType** simple type specifies the schema version to target for a request. [<2>](#)

```
<xs:simpleType name="ExchangeVersionType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="Exchange2007"
    />
    <xs:enumeration
      value="Exchange2007_SP1"
    />
    <xs:enumeration
      value="Exchange2010"
    />
    <xs:enumeration
      value="Exchange2010_SP1"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **ExchangeVersionType** simple type:

Value	Description
Exchange2007	Specifies the first version of the target Web service schema. <3>
Exchange2007_SP1	Specifies the second version of the target Web service schema. <4>
Exchange2010	Specifies the third version of the target Web service schema. <5>
Exchange2010_SP1	Specifies the fourth version of the target Web service schema. <6>

2.2.2.14 t:ExcludesAttributeType Simple Type

The **ExcludesAttributeType** simple type specifies a decimal or hexadecimal bitmask for an exclude restriction.

```
<xs:simpleType name="ExcludesAttributeType">
  <xs:restriction
    base="xs:string"
  >
    <xs:pattern
      value="( (0x|0X) [0-9A-Fa-f]* ) | ([0-9]* )"
    />
  </xs:restriction>
</xs:simpleType>
```

```

    />
  </xs:restriction>
</xs:simpleType>

```

Patterns

The following pattern is defined by the **ExcludesAttributeType** simple type:

```
((0x|0X)[0-9A-Fa-f]*)|([0-9]*)
```

2.2.2.15 t:LegacyFreeBusyType Simple Type

The **LegacyFreeBusyType** simple type specifies the **free/busy status** for calendar items and meeting requests.

```

<xs:simpleType name="LegacyFreeBusyType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="Busy"
    />
    <xs:enumeration
      value="Free"
    />
    <xs:enumeration
      value="NoData"
    />
    <xs:enumeration
      value="OOF"
    />
    <xs:enumeration
      value="Tentative"
    />
  </xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **LegacyFreeBusyType** simple type:

Value	Description
Busy	Specifies the status as busy.
Free	Specifies the status as free.
NoData	Specifies that there is no data for that recipient.
OOF	Specifies the status as Out of Office (OOF) .
Tentative	Specifies the status as tentative.

2.2.2.16 t:MailboxTypeType Simple Type

The **MailboxTypeType** simple type specifies the type of mailbox that is represented by an e-mail address.

```
<xs:simpleType name="MailboxTypeType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="Unknown"
    />
    <xs:enumeration
      value="OneOff"
    />
    <xs:enumeration
      value="Contact"
    />
    <xs:enumeration
      value="Mailbox"
    />
    <xs:enumeration
      value="PrivateDL"
    />
    <xs:enumeration
      value="PublicDL"
    />
    <xs:enumeration
      value="PublicFolder"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **MailboxTypeType** simple type:

Value	Description
Unknown	Specifies an unknown type of mailbox.
OneOff	Specifies a one-off member of a personal distribution list .
Contact	Specifies contact in a user's mailbox.
Mailbox	Specifies a mail-enabled directory service object.
PrivateDL	Specifies a private distribution list in a user's mailbox.
PublicDL	Specifies a public distribution list.
PublicFolder	Specifies a public folder.

MailboxTypeType is used in the **t:EmailAddressType** complex type (section [2.2.3.25](#)).

2.2.2.17 t:MonthNamesType Simple Type

The **MonthNamesType** simple type specifies the month in which a yearly recurring item occurs.

```
<xs:simpleType name="MonthNamesType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="January"
    />
    <xs:enumeration
      value="February"
    />
    <xs:enumeration
      value="March"
    />
    <xs:enumeration
      value="April"
    />
    <xs:enumeration
      value="May"
    />
    <xs:enumeration
      value="June"
    />
    <xs:enumeration
      value="July"
    />
    <xs:enumeration
      value="August"
    />
    <xs:enumeration
      value="September"
    />
    <xs:enumeration
      value="October"
    />
    <xs:enumeration
      value="November"
    />
    <xs:enumeration
      value="December"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **MonthNamesType** simple type:

Value	Description
January	Specifies that a yearly recurring item occurs in January.
February	Specifies that a yearly recurring item occurs in February.

Value	Description
March	Specifies that a yearly recurring item occurs in March.
April	Specifies that a yearly recurring item occurs in April.
May	Specifies that a yearly recurring item occurs in May.
June	Specifies that a yearly recurring item occurs in June.
July	Specifies that a yearly recurring item occurs in July.
August	Specifies that a yearly recurring item occurs in August.
September	Specifies that a yearly recurring item occurs in September.
October	Specifies that a yearly recurring item occurs in October.
November	Specifies that a yearly recurring item occurs in November.
December	Specifies that a yearly recurring item occurs in December.

2.2.2.18 t:NonEmptyStringType Simple Type

The **NonEmptyStringType** simple type specifies a string that **MUST** have a minimum of one character.

```
<xs:simpleType name="NonEmptyStringType">
  <xs:restriction
    base="xs:string"
  >
    <xs:minLength
      value="1"
    />
  </xs:restriction>
</xs:simpleType>
```

2.2.2.19 t:ResponseClassType Simple Type

The **ResponseClassType** simple type specifies the status states of a response.

```
<xs:simpleType name="ResponseClassType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="Error"
    />
    <xs:enumeration
      value="Success"
    />
    <xs:enumeration
      value="Warning"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **ResponseClassType** simple type:

Value	Description
Error	Specifies that the request could not be processed.
Success	Specifies that the request was successfully processed.
Warning	Specifies that an unusual situation was encountered during the processing of the request and the request was not processed successfully.

2.2.2.20 m:ResponseCodeType Simple Type

The **ResponseCodeType** simple type specifies status information for the request. [<7>](#)

```
<xs:simpleType name="ResponseCodeType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="NoError"
    />
    <xs:enumeration
      value="ErrorAccessDenied"
    />
    <xs:enumeration
      value="ErrorAccessModeSpecified"
    />
    <xs:enumeration
      value="ErrorAccountDisabled"
    />
    <xs:enumeration
      value="ErrorAddDelegatesFailed"
    />
    <xs:enumeration
      value="ErrorAddressSpaceNotFound"
    />
    <xs:enumeration
      value="ErrorADOperation"
    />
    <xs:enumeration
      value="ErrorADSessionFilter"
    />
    <xs:enumeration
      value="ErrorADUnavailable"
    />
    <xs:enumeration
      value="ErrorAffectedTaskOccurrencesRequired"
    />
    <xs:enumeration
      value="ErrorAttachmentSizeLimitExceeded"
    />
    <xs:enumeration
```

```
    value="ErrorBatchProcessingStopped"
  />
<xs:enumeration
  value="ErrorCalendarCannotMoveOrCopyOccurrence"
  />
<xs:enumeration
  value="ErrorCalendarCannotUpdateDeletedItem"
  />
<xs:enumeration
  value="ErrorCalendarCannotUseIdForOccurrenceId"
  />
<xs:enumeration
  value="ErrorCalendarCannotUseIdForRecurringMasterId"
  />
<xs:enumeration
  value="ErrorCalendarDurationIsTooLong"
  />
<xs:enumeration
  value="ErrorCalendarEndDateIsEarlierThanStartDate"
  />
<xs:enumeration
  value="ErrorCalendarFolderIsInvalidForCalendarView"
  />
<xs:enumeration
  value="ErrorCalendarInvalidAttributeValue"
  />
<xs:enumeration
  value="ErrorCalendarInvalidDayForTimeChangePattern"
  />
<xs:enumeration
  value="ErrorCalendarInvalidDayForWeeklyRecurrence"
  />
<xs:enumeration
  value="ErrorCalendarInvalidPropertyState"
  />
<xs:enumeration
  value="ErrorCalendarInvalidPropertyValue"
  />
<xs:enumeration
  value="ErrorCalendarInvalidRecurrence"
  />
<xs:enumeration
  value="ErrorCalendarInvalidTimeZone"
  />
<xs:enumeration
  value="ErrorCalendarIsCancelledForAccept"
  />
<xs:enumeration
  value="ErrorCalendarIsCancelledForDecline"
  />
<xs:enumeration
  value="ErrorCalendarIsCancelledForRemove"
  />
<xs:enumeration
  value="ErrorCalendarIsCancelledForTentative"
  />
<xs:enumeration
  value="ErrorCalendarIsDelegatedForAccept"
  />
```

```

<xs:enumeration
  value="ErrorCalendarIsDelegatedForDecline"
/>
<xs:enumeration
  value="ErrorCalendarIsDelegatedForRemove"
/>
<xs:enumeration
  value="ErrorCalendarIsDelegatedForTentative"
/>
<xs:enumeration
  value="ErrorCalendarIsNotOrganizer"
/>
<xs:enumeration
  value="ErrorCalendarIsOrganizerForAccept"
/>
<xs:enumeration
  value="ErrorCalendarIsOrganizerForDecline"
/>
<xs:enumeration
  value="ErrorCalendarIsOrganizerForRemove"
/>
<xs:enumeration
  value="ErrorCalendarIsOrganizerForTentative"
/>
<xs:enumeration
  value="ErrorCalendarOccurrenceIndexIsOutOfRecurrenceRange"
/>
<xs:enumeration
  value="ErrorCalendarOccurrenceIsDeletedFromRecurrence"
/>
<xs:enumeration
  value="ErrorCalendarOutOfRange"
/>
<xs:enumeration
  value="ErrorCalendarMeetingRequestIsOutOfDate"
/>
<xs:enumeration
  value="ErrorCalendarViewRangeTooBig"
/>
<xs:enumeration
  value="ErrorCallerIsInvalidADAccount"
/>
<xs:enumeration
  value="ErrorCannotCreateCalendarItemInNonCalendarFolder"
/>
<xs:enumeration
  value="ErrorCannotCreateContactInNonContactFolder"
/>
<xs:enumeration
  value="ErrorCannotCreatePostItemInNonMailFolder"
/>
<xs:enumeration
  value="ErrorCannotCreateTaskInNonTaskFolder"
/>
<xs:enumeration
  value="ErrorCannotDeleteObject"
/>
<xs:enumeration
  value="ErrorCannotOpenFileAttachment"

```

```
</>
<xs:enumeration
  value="ErrorCannotDeleteTaskOccurrence"
/>
<xs:enumeration
  value="ErrorCannotEmptyFolder"
/>
<xs:enumeration
  value="ErrorCannotSetCalendarPermissionOnNonCalendarFolder"
/>
<xs:enumeration
  value="ErrorCannotSetNonCalendarPermissionOnCalendarFolder"
/>
<xs:enumeration
  value="ErrorCannotSetPermissionUnknownEntries"
/>
<xs:enumeration
  value="ErrorCannotUseFolderIdForItemId"
/>
<xs:enumeration
  value="ErrorCannotUseItemIdForFolderId"
/>
<xs:enumeration
  value="ErrorChangeKeyRequired"
/>
<xs:enumeration
  value="ErrorChangeKeyRequiredForWriteOperations"
/>
<xs:enumeration
  value="ErrorClientDisconnected"
/>
<xs:enumeration
  value="ErrorConnectionFailed"
/>
<xs:enumeration
  value="ErrorContainsFilterWrongType"
/>
<xs:enumeration
  value="ErrorContentConversionFailed"
/>
<xs:enumeration
  value="ErrorCorruptData"
/>
<xs:enumeration
  value="ErrorCreateItemAccessDenied"
/>
<xs:enumeration
  value="ErrorCreateManagedFolderPartialCompletion"
/>
<xs:enumeration
  value="ErrorCreateSubfolderAccessDenied"
/>
<xs:enumeration
  value="ErrorCrossMailboxMoveCopy"
/>
<xs:enumeration
  value="ErrorCrossSiteRequest"
/>
<xs:enumeration
```

```
    value="ErrorDataSizeLimitExceeded"
  />
<xs:enumeration
  value="ErrorDataSourceOperation"
  />
<xs:enumeration
  value="ErrorDelegateAlreadyExists"
  />
<xs:enumeration
  value="ErrorDelegateCannotAddOwner"
  />
<xs:enumeration
  value="ErrorDelegateMissingConfiguration"
  />
<xs:enumeration
  value="ErrorDelegateNoUser"
  />
<xs:enumeration
  value="ErrorDelegateValidationFailed"
  />
<xs:enumeration
  value="ErrorDeleteDistinguishedFolder"
  />
<xs:enumeration
  value="ErrorDeleteItemsFailed"
  />
<xs:enumeration
  value="ErrorDistinguishedUserNotSupported"
  />
<xs:enumeration
  value="ErrorDistributionListMemberNotExist"
  />
<xs:enumeration
  value="ErrorDuplicateInputFolderNames"
  />
<xs:enumeration
  value="ErrorDuplicateUserIdsSpecified"
  />
<xs:enumeration
  value="ErrorEmailAddressMismatch"
  />
<xs:enumeration
  value="ErrorEventNotFound"
  />
<xs:enumeration
  value="ErrorExceededConnectionCount"
  />
<xs:enumeration
  value="ErrorExceededSubscriptionCount"
  />
<xs:enumeration
  value="ErrorExceededFindCountLimit"
  />
<xs:enumeration
  value="ErrorExpiredSubscription"
  />
<xs:enumeration
  value="ErrorExternalFacingCAS"
  />
```

```
<xs:enumeration
  value="ErrorFolderCorrupt"
/>
<xs:enumeration
  value="ErrorFolderNotFound"
/>
<xs:enumeration
  value="ErrorFolderPropertRequestFailed"
/>
<xs:enumeration
  value="ErrorFolderSave"
/>
<xs:enumeration
  value="ErrorFolderSaveFailed"
/>
<xs:enumeration
  value="ErrorFolderSavePropertyError"
/>
<xs:enumeration
  value="ErrorFolderExists"
/>
<xs:enumeration
  value="ErrorFreeBusyGenerationFailed"
/>
<xs:enumeration
  value="ErrorGetServerSecurityDescriptorFailed"
/>
<xs:enumeration
  value="ErrorImpersonateUserDenied"
/>
<xs:enumeration
  value="ErrorImpersonationDenied"
/>
<xs:enumeration
  value="ErrorImpersonationFailed"
/>
<xs:enumeration
  value="ErrorIncorrectSchemaVersion"
/>
<xs:enumeration
  value="ErrorIncorrectUpdatePropertyCount"
/>
<xs:enumeration
  value="ErrorIndividualMailboxLimitReached"
/>
<xs:enumeration
  value="ErrorInsufficientResources"
/>
<xs:enumeration
  value="ErrorInternalServerError"
/>
<xs:enumeration
  value="ErrorInternalServerErrorTransientError"
/>
<xs:enumeration
  value="ErrorInvalidAccessLevel"
/>
<xs:enumeration
  value="ErrorInvalidArgument"
```

```
    />
  <xs:enumeration
    value="ErrorInvalidAttachmentId"
  />
  <xs:enumeration
    value="ErrorInvalidAttachmentSubfilter"
  />
  <xs:enumeration
    value="ErrorInvalidAttachmentSubfilterTextFilter"
  />
  <xs:enumeration
    value="ErrorInvalidAuthorizationContext"
  />
  <xs:enumeration
    value="ErrorInvalidChangeKey"
  />
  <xs:enumeration
    value="ErrorInvalidClientSecurityContext"
  />
  <xs:enumeration
    value="ErrorInvalidCompleteDate"
  />
  <xs:enumeration
    value="ErrorInvalidContactEmailAddress"
  />
  <xs:enumeration
    value="ErrorInvalidContactEmailIndex"
  />
  <xs:enumeration
    value="ErrorInvalidCrossForestCredentials"
  />
  <xs:enumeration
    value="ErrorInvalidDelegatePermission"
  />
  <xs:enumeration
    value="ErrorInvalidDelegateUserId"
  />
  <xs:enumeration
    value="ErrorInvalidExcludesRestriction"
  />
  <xs:enumeration
    value="ErrorInvalidExpressionTypeForSubFilter"
  />
  <xs:enumeration
    value="ErrorInvalidExtendedProperty"
  />
  <xs:enumeration
    value="ErrorInvalidExtendedPropertyValue"
  />
  <xs:enumeration
    value="ErrorInvalidFolderId"
  />
  <xs:enumeration
    value="ErrorInvalidFolderTypeForOperation"
  />
  <xs:enumeration
    value="ErrorInvalidFractionalPagingParameters"
  />
  <xs:enumeration
```



```

    value="ErrorInvalidFreeBusyViewType"
  />
<xs:enumeration
  value="ErrorInvalidId"
  />
<xs:enumeration
  value="ErrorInvalidIdEmpty"
  />
<xs:enumeration
  value="ErrorInvalidIdMalformed"
  />
<xs:enumeration
  value="ErrorInvalidIdMalformedEwsLegacyIdFormat"
  />
<xs:enumeration
  value="ErrorInvalidIdMonikerTooLong"
  />
<xs:enumeration
  value="ErrorInvalidIdNotAnItemAttachmentId"
  />
<xs:enumeration
  value="ErrorInvalidIdReturnedByResolveNames"
  />
<xs:enumeration
  value="ErrorInvalidIdStoreObjectIdTooLong"
  />
<xs:enumeration
  value="ErrorInvalidIdTooManyAttachmentLevels"
  />
<xs:enumeration
  value="ErrorInvalidIdXml"
  />
<xs:enumeration
  value="ErrorInvalidIndexedPagingParameters"
  />
<xs:enumeration
  value="ErrorInvalidInternetHeaderChildNodes"
  />
<xs:enumeration
  value="ErrorInvalidItemForOperationCreateItemAttachment"
  />
<xs:enumeration
  value="ErrorInvalidItemForOperationCreateItem"
  />
<xs:enumeration
  value="ErrorInvalidItemForOperationAcceptItem"
  />
<xs:enumeration
  value="ErrorInvalidItemForOperationDeclineItem"
  />
<xs:enumeration
  value="ErrorInvalidItemForOperationCancelItem"
  />
<xs:enumeration
  value="ErrorInvalidItemForOperationExpandDL"
  />
<xs:enumeration
  value="ErrorInvalidItemForOperationRemoveItem"
  />

```

```
<xs:enumeration
  value="ErrorInvalidItemForOperationSendItem"
 />
<xs:enumeration
  value="ErrorInvalidItemForOperationTentative"
 />
<xs:enumeration
  value="ErrorInvalidLogonType"
 />
<xs:enumeration
  value="ErrorInvalidMailbox"
 />
<xs:enumeration
  value="ErrorInvalidManagedFolderProperty"
 />
<xs:enumeration
  value="ErrorInvalidManagedFolderQuota"
 />
<xs:enumeration
  value="ErrorInvalidManagedFolderSize"
 />
<xs:enumeration
  value="ErrorInvalidMergedFreeBusyInterval"
 />
<xs:enumeration
  value="ErrorInvalidNameForNameResolution"
 />
<xs:enumeration
  value="ErrorInvalidOperation"
 />
<xs:enumeration
  value="ErrorInvalidNetworkServiceContext"
 />
<xs:enumeration
  value="ErrorInvalidOofParameter"
 />
<xs:enumeration
  value="ErrorInvalidPagingMaxRows"
 />
<xs:enumeration
  value="ErrorInvalidParentFolder"
 />
<xs:enumeration
  value="ErrorInvalidPercentCompleteValue"
 />
<xs:enumeration
  value="ErrorInvalidPermissionSettings"
 />
<xs:enumeration
  value="ErrorInvalidPhoneCallId"
 />
<xs:enumeration
  value="ErrorInvalidPhoneNumber"
 />
<xs:enumeration
  value="ErrorInvalidUserInfo"
 />
<xs:enumeration
  value="ErrorInvalidPropertyAppend"
```

```
    />
  <xs:enumeration
    value="ErrorInvalidPropertyDelete"
  />
  <xs:enumeration
    value="ErrorInvalidPropertyForExists"
  />
  <xs:enumeration
    value="ErrorInvalidPropertyForOperation"
  />
  <xs:enumeration
    value="ErrorInvalidPropertyRequest"
  />
  <xs:enumeration
    value="ErrorInvalidPropertySet"
  />
  <xs:enumeration
    value="ErrorInvalidPropertyUpdateSendMessage"
  />
  <xs:enumeration
    value="ErrorInvalidProxySecurityContext"
  />
  <xs:enumeration
    value="ErrorInvalidPullSubscriptionId"
  />
  <xs:enumeration
    value="ErrorInvalidPushSubscriptionUrl"
  />
  <xs:enumeration
    value="ErrorInvalidRecipients"
  />
  <xs:enumeration
    value="ErrorInvalidRecipientSubfilter"
  />
  <xs:enumeration
    value="ErrorInvalidRecipientSubfilterComparison"
  />
  <xs:enumeration
    value="ErrorInvalidRecipientSubfilterOrder"
  />
  <xs:enumeration
    value="ErrorInvalidRecipientSubfilterTextFilter"
  />
  <xs:enumeration
    value="ErrorInvalidReferenceItem"
  />
  <xs:enumeration
    value="ErrorInvalidRequest"
  />
  <xs:enumeration
    value="ErrorInvalidRestriction"
  />
  <xs:enumeration
    value="ErrorInvalidRoutingType"
  />
  <xs:enumeration
    value="ErrorInvalidScheduledOutOfDuration"
  />
  <xs:enumeration
```

```

    value="ErrorInvalidSchemaVersionForMailboxVersion"
  />
<xs:enumeration
  value="ErrorInvalidSecurityDescriptor"
  />
<xs:enumeration
  value="ErrorInvalidSendItemSaveSettings"
  />
<xs:enumeration
  value="ErrorInvalidSerializedAccessToken"
  />
<xs:enumeration
  value="ErrorInvalidServerVersion"
  />
<xs:enumeration
  value="ErrorInvalidSid"
  />
<xs:enumeration
  value="ErrorInvalidSIPUri"
  />
<xs:enumeration
  value="ErrorInvalidSmtpAddress"
  />
<xs:enumeration
  value="ErrorInvalidSubfilterType"
  />
<xs:enumeration
  value="ErrorInvalidSubfilterTypeNotAttendeeType"
  />
<xs:enumeration
  value="ErrorInvalidSubfilterTypeNotRecipientType"
  />
<xs:enumeration
  value="ErrorInvalidSubscription"
  />
<xs:enumeration
  value="ErrorInvalidSubscriptionRequest"
  />
<xs:enumeration
  value="ErrorInvalidSyncStateData"
  />
<xs:enumeration
  value="ErrorInvalidTimeInterval"
  />
<xs:enumeration
  value="ErrorInvalidUserOutOfSettings"
  />
<xs:enumeration
  value="ErrorInvalidUserPrincipalName"
  />
<xs:enumeration
  value="ErrorInvalidUserSid"
  />
<xs:enumeration
  value="ErrorInvalidUserSidMissingUPN"
  />
<xs:enumeration
  value="ErrorInvalidValueForProperty"
  />

```

```
<xs:enumeration
  value="ErrorInvalidWatermark"
 />
<xs:enumeration
  value="ErrorIPGatewayNotFound"
 />
<xs:enumeration
  value="ErrorIrresolvableConflict"
 />
<xs:enumeration
  value="ErrorItemCorrupt"
 />
<xs:enumeration
  value="ErrorItemNotFound"
 />
<xs:enumeration
  value="ErrorItemPropertyRequestFailed"
 />
<xs:enumeration
  value="ErrorItemSave"
 />
<xs:enumeration
  value="ErrorItemSavePropertyError"
 />
<xs:enumeration
  value="ErrorLegacyMailboxFreeBusyViewTypeNotMerged"
 />
<xs:enumeration
  value="ErrorLocalServerObjectNotFound"
 />
<xs:enumeration
  value="ErrorLogonAsNetworkServiceFailed"
 />
<xs:enumeration
  value="ErrorMailboxConfiguration"
 />
<xs:enumeration
  value="ErrorMailboxDataArrayEmpty"
 />
<xs:enumeration
  value="ErrorMailboxDataArrayTooBig"
 />
<xs:enumeration
  value="ErrorMailboxLogonFailed"
 />
<xs:enumeration
  value="ErrorMailboxMoveInProgress"
 />
<xs:enumeration
  value="ErrorMailboxStoreUnavailable"
 />
<xs:enumeration
  value="ErrorMailRecipientNotFound"
 />
<xs:enumeration
  value="ErrorMailTipsDisabled"
 />
<xs:enumeration
  value="ErrorManagedFolderAlreadyExists"
```

```
</>
<xs:enumeration
  value="ErrorManagedFolderNotFound"
/>
<xs:enumeration
  value="ErrorManagedFoldersRootFailure"
/>
<xs:enumeration
  value="ErrorMeetingSuggestionGenerationFailed"
/>
<xs:enumeration
  value="ErrorMessageDispositionRequired"
/>
<xs:enumeration
  value="ErrorMessageSizeExceeded"
/>
<xs:enumeration
  value="ErrorMimeContentConversionFailed"
/>
<xs:enumeration
  value="ErrorMimeContentInvalid"
/>
<xs:enumeration
  value="ErrorMimeContentInvalidBase64String"
/>
<xs:enumeration
  value="ErrorMissingArgument"
/>
<xs:enumeration
  value="ErrorMissingEmailAddress"
/>
<xs:enumeration
  value="ErrorMissingEmailAddressForManagedFolder"
/>
<xs:enumeration
  value="ErrorMissingInformationEmailAddress"
/>
<xs:enumeration
  value="ErrorMissingInformationReferenceItemId"
/>
<xs:enumeration
  value="ErrorMissingItemForCreateItemAttachment"
/>
<xs:enumeration
  value="ErrorMissingManagedFolderId"
/>
<xs:enumeration
  value="ErrorMissingRecipients"
/>
<xs:enumeration
  value="ErrorMissingUserIdInformation"
/>
<xs:enumeration
  value="ErrorMoreThanOneAccessModeSpecified"
/>
<xs:enumeration
  value="ErrorMoveCopyFailed"
/>
<xs:enumeration
```

```

    value="ErrorMoveDistinguishedFolder"
  />
<xs:enumeration
  value="ErrorNameResolutionMultipleResults"
  />
<xs:enumeration
  value="ErrorNameResolutionNoMailbox"
  />
<xs:enumeration
  value="ErrorNameResolutionNoResults"
  />
<xs:enumeration
  value="ErrorNoApplicableProxyCASServersAvailable"
  />
<xs:enumeration
  value="ErrorNoCalendar"
  />
<xs:enumeration
  value="ErrorNoDestinationCASDueToKerberosRequirements"
  />
<xs:enumeration
  value="ErrorNoDestinationCASDueToSSLRequirements"
  />
<xs:enumeration
  value="ErrorNoDestinationCASDueToVersionMismatch"
  />
<xs:enumeration
  value="ErrorNoFolderClassOverride"
  />
<xs:enumeration
  value="ErrorNoFreeBusyAccess"
  />
<xs:enumeration
  value="ErrorNonExistentMailbox"
  />
<xs:enumeration
  value="ErrorNonPrimarySmtpAddress"
  />
<xs:enumeration
  value="ErrorNoPropertyTagForCustomProperties"
  />
<xs:enumeration
  value="ErrorNoPublicFolderReplicaAvailable"
  />
<xs:enumeration
  value="ErrorNoPublicFolderServerAvailable"
  />
<xs:enumeration
  value="ErrorNoRespondingCASInDestinationSite"
  />
<xs:enumeration
  value="ErrorNotDelegate"
  />
<xs:enumeration
  value="ErrorNotEnoughMemory"
  />
<xs:enumeration
  value="ErrorObjectTypeChanged"
  />

```

```
<xs:enumeration
  value="ErrorOccurrenceCrossingBoundary"
/>
<xs:enumeration
  value="ErrorOccurrenceTimeSpanTooBig"
/>
<xs:enumeration
  value="ErrorOperationNotAllowedWithPublicFolderRoot"
/>
<xs:enumeration
  value="ErrorParentFolderIdRequired"
/>
<xs:enumeration
  value="ErrorParentFolderNotFound"
/>
<xs:enumeration
  value="ErrorPasswordChangeRequired"
/>
<xs:enumeration
  value="ErrorPasswordExpired"
/>
<xs:enumeration
  value="ErrorPhoneNumberNotDialable"
/>
<xs:enumeration
  value="ErrorPropertyUpdate"
/>
<xs:enumeration
  value="ErrorPropertyValidationFailure"
/>
<xs:enumeration
  value="ErrorProxiedSubscriptionCallFailure"
/>
<xs:enumeration
  value="ErrorProxyCallFailed"
/>
<xs:enumeration
  value="ErrorProxyGroupSidLimitExceeded"
/>
<xs:enumeration
  value="ErrorProxyRequestNotAllowed"
/>
<xs:enumeration
  value="ErrorProxyRequestProcessingFailed"
/>
<xs:enumeration
  value="ErrorProxyServiceDiscoveryFailed"
/>
<xs:enumeration
  value="ErrorProxyTokenExpired"
/>
<xs:enumeration
  value="ErrorPublicFolderRequestProcessingFailed"
/>
<xs:enumeration
  value="ErrorPublicFolderServerNotFound"
/>
<xs:enumeration
  value="ErrorQueryFilterTooLong"
```



```

/>
<xs:enumeration
  value="ErrorQuotaExceeded"
/>
<xs:enumeration
  value="ErrorReadEventsFailed"
/>
<xs:enumeration
  value="ErrorReadReceiptNotPending"
/>
<xs:enumeration
  value="ErrorRecurrenceEndDateTooBig"
/>
<xs:enumeration
  value="ErrorRecurrenceHasNoOccurrence"
/>
<xs:enumeration
  value="ErrorRemoveDelegatesFailed"
/>
<xs:enumeration
  value="ErrorRequestAborted"
/>
<xs:enumeration
  value="ErrorRequestStreamTooBig"
/>
<xs:enumeration
  value="ErrorRequiredPropertyMissing"
/>
<xs:enumeration
  value="ErrorResolveNamesInvalidFolderType"
/>
<xs:enumeration
  value="ErrorResolveNamesOnlyOneContactsFolderAllowed"
/>
<xs:enumeration
  value="ErrorResponseSchemaValidation"
/>
<xs:enumeration
  value="ErrorRestrictionTooLong"
/>
<xs:enumeration
  value="ErrorRestrictionTooComplex"
/>
<xs:enumeration
  value="ErrorResultSetTooBig"
/>
<xs:enumeration
  value="ErrorInvalidExchangeImpersonationHeaderData"
/>
<xs:enumeration
  value="ErrorSavedItemFolderNotFound"
/>
<xs:enumeration
  value="ErrorSchemaValidation"
/>
<xs:enumeration
  value="ErrorSearchFolderNotInitialized"
/>
<xs:enumeration

```

```
    value="ErrorSendAsDenied"
  />
<xs:enumeration
  value="ErrorSendMeetingCancellationsRequired"
  />
<xs:enumeration
  value="ErrorSendMeetingInvitationsOrCancellationsRequired"
  />
<xs:enumeration
  value="ErrorSendMeetingInvitationsRequired"
  />
<xs:enumeration
  value="ErrorSentMeetingRequestUpdate"
  />
<xs:enumeration
  value="ErrorSentTaskRequestUpdate"
  />
<xs:enumeration
  value="ErrorServerBusy"
  />
<xs:enumeration
  value="ErrorServiceDiscoveryFailed"
  />
<xs:enumeration
  value="ErrorStaleObject"
  />
<xs:enumeration
  value="ErrorSubmissionQuotaExceeded"
  />
<xs:enumeration
  value="ErrorSubscriptionAccessDenied"
  />
<xs:enumeration
  value="ErrorSubscriptionDelegateAccessNotSupported"
  />
<xs:enumeration
  value="ErrorSubscriptionNotFound"
  />
<xs:enumeration
  value="ErrorSubscriptionUnsubscribed"
  />
<xs:enumeration
  value="ErrorSyncFolderNotFound"
  />
<xs:enumeration
  value="ErrorTimeIntervalTooBig"
  />
<xs:enumeration
  value="ErrorTimeoutExpired"
  />
<xs:enumeration
  value="ErrorTimeZone"
  />
<xs:enumeration
  value="ErrorToFolderNotFound"
  />
<xs:enumeration
  value="ErrorTokenSerializationDenied"
  />
```

```
<xs:enumeration
  value="ErrorUpdatePropertyMismatch"
/>
<xs:enumeration
  value="ErrorUnifiedMessagingDialPlanNotFound"
/>
<xs:enumeration
  value="ErrorUnifiedMessagingRequestFailed"
/>
<xs:enumeration
  value="ErrorUnifiedMessagingServerNotFound"
/>
<xs:enumeration
  value="ErrorUnableToGetUserOofSettings"
/>
<xs:enumeration
  value="ErrorUnsupportedSubFilter"
/>
<xs:enumeration
  value="ErrorUnsupportedCulture"
/>
<xs:enumeration
  value="ErrorUnsupportedMapiPropertyType"
/>
<xs:enumeration
  value="ErrorUnsupportedMimeConversion"
/>
<xs:enumeration
  value="ErrorUnsupportedPathForQuery"
/>
<xs:enumeration
  value="ErrorUnsupportedPathForSortGroup"
/>
<xs:enumeration
  value="ErrorUnsupportedPropertyDefinition"
/>
<xs:enumeration
  value="ErrorUnsupportedQueryFilter"
/>
<xs:enumeration
  value="ErrorUnsupportedRecurrence"
/>
<xs:enumeration
  value="ErrorUnsupportedTypeForConversion"
/>
<xs:enumeration
  value="ErrorUpdateDelegatesFailed"
/>
<xs:enumeration
  value="ErrorUserNotUnifiedMessagingEnabled"
/>
<xs:enumeration
  value="ErrorValueOutOfRange"
/>
<xs:enumeration
  value="ErrorVoiceMailNotImplemented"
/>
<xs:enumeration
  value="ErrorVirusDetected"
```

```

/>
<xs:enumeration
  value="ErrorVirusMessageDeleted"
/>
<xs:enumeration
  value="ErrorWebRequestInInvalidState"
/>
<xs:enumeration
  value="ErrorWin32InteropError"
/>
<xs:enumeration
  value="ErrorWorkingHoursSaveFailed"
/>
<xs:enumeration
  value="ErrorWorkingHoursXmlMalformed"
/>
<xs:enumeration
  value="ErrorWrongServerVersion"
/>
<xs:enumeration
  value="ErrorWrongServerVersionDelegate"
/>
<xs:enumeration
  value="ErrorMissingInformationSharingFolderId"
/>
<xs:enumeration
  value="ErrorDuplicateSOAPHeader"
/>
<xs:enumeration
  value="ErrorSharingSynchronizationFailed"
/>
<xs:enumeration
  value="ErrorSharingNoExternalEwsAvailable"
/>
<xs:enumeration
  value="ErrorFreeBusyDLLimitReached"
/>
<xs:enumeration
  value="ErrorInvalidGetSharingFolderRequest"
/>
<xs:enumeration
  value="ErrorNotAllowedExternalSharingByPolicy"
/>
<xs:enumeration
  value="ErrorUserNotAllowedByPolicy"
/>
<xs:enumeration
  value="ErrorPermissionNotAllowedByPolicy"
/>
<xs:enumeration
  value="ErrorOrganizationNotFederated"
/>
<xs:enumeration
  value="ErrorMailboxFailover"
/>
<xs:enumeration
  value="ErrorInvalidExternalSharingInitiator"
/>
<xs:enumeration

```

```

        value="ErrorMessageTrackingPermanentError"
    />
<xs:enumeration
    value="ErrorMessageTrackingTransientError"
    />
<xs:enumeration
    value="ErrorMessageTrackingNoSuchDomain"
    />
<xs:enumeration
    value="ErrorUserWithoutFederatedProxyAddress"
    />
<xs:enumeration
    value="ErrorInvalidOrganizationRelationshipForFreeBusy"
    />
<xs:enumeration
    value="ErrorInvalidFederatedOrganizationId"
    />
<xs:enumeration
    value="ErrorInvalidExternalSharingSubscriber"
    />
<xs:enumeration
    value="ErrorInvalidSharingData"
    />
<xs:enumeration
    value="ErrorInvalidSharingMessage"
    />
<xs:enumeration
    value="ErrorNotSupportedSharingMessage"
    />
<xs:enumeration
    value="ErrorApplyConversationActionFailed"
    />
<xs:enumeration
    value="ErrorInboxRulesValidationError"
    />
<xs:enumeration
    value="ErrorOutlookRuleBlobExists"
    />
<xs:enumeration
    value="ErrorRulesOverQuota"
    />
<xs:enumeration
    value="ErrorNewEventStreamConnectionOpened"
    />
<xs:enumeration
    value="ErrorMissedNotificationEvents"
    />
</xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **ResponseCodeType** simple type:

Value	Description
NoError	Specifies that no errors occurred.
ErrorAccessDenied	Specifies that the calling account does not have the rights to perform the action requested.
ErrorAccessModeSpecified	This error is for internal use only. This error is not returned.
ErrorAccountDisabled	Specifies that the account has been disabled.
ErrorAddDelegatesFailed	Occurs when a list with added delegates cannot be saved.
ErrorAddressSpaceNotFound	Specifies that the address space record, or Domain Name System (DNS) domain name, for cross-forest availability could not be found in the directory service.
ErrorADOperation	Specifies that the operation failed because of communication problems with the directory service.
ErrorADSessionFilter	Specifies that the ResolveNames operation ([MS-OXWSRSLNM] section 3.1.4.1) request specifies an invalid name.
ErrorADUnavailable	Specifies that the directory service is unavailable. Try your request again later.
ErrorAffectedTaskOccurrencesRequired	Specifies that the AffectedTaskOccurrences property value is missing. This value is required when you are deleting a task.
ErrorAttachmentSizeLimitExceeded	Specifies that the size of the attachment exceeds <code>Int32.MaxValue</code> , in bytes. This response code is applicable to the CreateAttachment and GetAttachment methods.
ErrorBatchProcessingStopped	Specifies that the previous item in the request failed in such a way that Exchange Web Services stopped processing the remaining items in the request. All remaining items are marked with the ErrorBatchProcessingStopped error.
ErrorCalendarCannotMoveOrCopyOccurrence	Specifies that an attempt was made to move or copy an occurrence of a recurring calendar item.
ErrorCalendarCannotUpdateDeletedItem	Specifies that an attempt was made to update a calendar item that is located in the Deleted Items folder, and the update in question would send out a meeting invite.
ErrorCalendarCannotUseIdForOccurrenceId	Specifies that the OccurrenceId does not correspond to a valid occurrence of the recurringMasterId .
ErrorCalendarCannotUseIdForRecurringMasterId	Specifies that the recurringMasterId does not correspond to a valid occurrence of the OccurrenceId .
ErrorCalendarDurationIsTooLong	Specifies that the item duration of a calendar item exceeds five years.
ErrorCalendarEndDateIsEarlierThanStartDate	Specifies that the end date/time must be changed so that it is greater than the start date/time.
ErrorCalendarFolderIsValidForCalendarView	Specifies that the find operation that is using the CalendarViewType object is not for a calendar folder.

Value	Description
ErrorCalendarInvalidAttributeValue	This response code is not used.
ErrorCalendarInvalidDayForTimeChangePattern	Specifies that invalid values of Day , WeekDay , and WeekendDay were used to define the time change pattern.
ErrorCalendarInvalidDayForWeeklyRecurrence	Specifies that invalid values of Day , WeekDay , and WeekendDay were used to specify the weekly recurrence.
ErrorCalendarInvalidPropertyState	Specifies that the state of the calendar item recurrence binary large object (BLOB) in the store is invalid.
ErrorCalendarInvalidPropertyValue	This response code is not used.
ErrorCalendarInvalidRecurrence	Specifies that the internal structure of the objects that represent the recurrence is invalid.
ErrorCalendarInvalidTimeZone	Specifies that an invalid time zone was encountered.
ErrorCalendarIsCancelledForAccept	Specifies that a calendar item has been cancelled. This error code MUST be returned when responding to a meeting request with an t:AcceptItemType (section) response object after a meeting has been cancelled.
ErrorCalendarIsCancelledForDecline	Specifies that a calendar item has been cancelled. This error code MUST be returned when responding to a meeting request with a t:DeclineItemType (section) response object after a meeting has been cancelled.
ErrorCalendarIsCancelledForRemove	Specifies that a calendar item has been cancelled. This error code MUST be returned when responding to a meeting request with a t:RemoveItemType (section) response object after a meeting has been cancelled.
ErrorCalendarIsCancelledForTentative	Specifies that a calendar item has been cancelled. This error code MUST be returned when responding to a meeting request with a t:TentativelyAcceptItemType (section) response object after a meeting has been cancelled.
ErrorCalendarIsDelegatedForAccept	Specifies that delegate access cannot be used to accept a meeting request.
ErrorCalendarIsDelegatedForDecline	Specifies that delegate access cannot be used to decline a meeting request.
ErrorCalendarIsDelegatedForRemove	Specifies that delegate access cannot be used to delete a meeting request.
ErrorCalendarIsDelegatedForTentative	Specifies that delegate access cannot be used to tentatively accept a meeting request.
ErrorCalendarIsNotOrganizer	Specifies that a meeting cannot be canceled by someone other than the organizer.
ErrorCalendarIsOrganizerForAccept	Specifies that the meeting organizer cannot accept the meeting. Only attendees can accept meeting requests.
ErrorCalendarIsOrganizerForDecline	Specifies that the meeting organizer cannot decline the meeting. Only attendees can decline meeting requests.

Value	Description
ErrorCalendarIsOrganizerForRemove	Specifies that the meeting organizer cannot remove a meeting from the calendar. The organizer can only remove the meeting by canceling the meeting. Only attendees can remove a calendar item.
ErrorCalendarIsOrganizerForTentative	Specifies that the meeting organizer cannot tentatively accept a meeting. Only attendees can tentatively accept meeting requests.
ErrorCalendarOccurrenceIndexIsOutOfRecurrenceRange	Occurs when the occurrence index that is specified in the OccurrenceId property does not correspond to a valid occurrence. (for example, if your recurrence pattern defines a set of three meeting occurrences and you try to access the fifth occurrence).
ErrorCalendarOccurrenceIsDeletedFromRecurrence	Occurs when the occurrence index that is specified in the OccurrenceId property corresponds to a deleted instance.
ErrorCalendarOutOfRange	Occurs when a recurrence pattern is defined that contains a value for a month, day, or week that is out of range, such as the seventh week of the month.
ErrorCalendarMeetingRequestIsOutOfDate	Specifies that the calendar item associated with the meeting request has been updated since the meeting request was sent.
ErrorCalendarViewRangeTooBig	Occurs when the range for calendar paging is larger than two years.
ErrorCallerIsInvalidADAccount	Specifies that the requesting account is not a valid account in the directory database.
ErrorCannotCreateCalendarItemInNonCalendarFolder	Occurs when you are creating a calendar item and the SavedItemFolderId property refers to a folder other than the Calendar folder.
ErrorCannotCreateContactInNonContactFolder	Specifies that an attempt was made to create a contact in a folder other than the Contacts folder.
ErrorCannotCreatePostItemInNonMailFolder	Specifies that a post item can be created only in a Mail folder.
ErrorCannotCreateTaskInNonTaskFolder	Occurs when you are creating a task and the SavedItemFolderId property refers to a folder other than the Tasks folder.
ErrorCannotDeleteObject	Specifies that the item or folder to be deleted cannot be deleted.
ErrorCannotOpenFileAttachment	Occurs when the attachment stream does not open.
ErrorCannotDeleteTaskOccurrence	Specifies that you cannot delete an occurrence of a nonrecurring task and you cannot delete the last occurrence of a recurring task.
ErrorCannotEmptyFolder	This error MUST be returned when the server cannot empty a folder.
ErrorCannotSetCalendarPermissionOnNonCalendarFolder	Specifies that the caller tried to set calendar permissions on a folder other than the Calendar folder.

Value	Description
ErrorCannotSetNonCalendarPermissionOnCalendarFolder	Specifies that the caller tried to set non-Calendar folder permissions on a Calendar folder.
ErrorCannotSetPermissionUnknownEntries	Specifies that you cannot set unknown permissions in a permissions set.
ErrorCannotUseFolderIdForItemId	Occurs when the ID that was passed represents a folder instead of an item.
ErrorCannotUseItemIdForFolderId	Occurs when the ID that was passed in represents an item instead of a folder.
ErrorChangeKeyRequired	This response code has been replaced by ErrorChangeKeyRequiredForWriteOperations.
ErrorChangeKeyRequiredForWriteOperations	Specifies that a valid change key must be provided when you are performing certain update operations.
ErrorClientDisconnected	Specifies that the client was disconnected.
ErrorConnectionFailed	Occurs when Exchange Web Services cannot connect to the mailbox.
ErrorContainsFilterWrongType	Specifies that the property inspected for a Contains filter is not a string type. This error code MUST be returned when a Contains filter is used with a property that is not a string type.
ErrorContentConversionFailed	Occurs when Exchange Web Services is unable to retrieve the Multipurpose Internet Mail Extensions (MIME) content for the item that was retrieved by the GetItem method, or it is unable to create the item from the CreateItem method.
ErrorCorruptData	Specifies that the data is corrupted and cannot be processed.
ErrorCreateItemAccessDenied	Specifies that the caller does not have the necessary permissions to create the item.
ErrorCreateManagedFolderPartialCompletion	Specifies that one or more of the managed folders that were passed to the CreateManagedFolder method failed to be created. Search for each folder to determine which folders were created and which ones do not exist.
ErrorCreateSubfolderAccessDenied	Specifies that the calling account does not have the proper permissions to create the subfolder.
ErrorCrossMailboxMoveCopy	Specifies that the item or folder cannot be moved from one mailbox to another.
ErrorCrossSiteRequest	Specifies that the request is not allowed because the server that services the request is in a different site than the requested resource.
ErrorDataSizeLimitExceeded	Specifies that either the data that you were trying to set exceeded the maximum size for the property, or the value is large enough to require streaming and the property does not support streaming, such as for folder properties.
ErrorDataSourceOperation	Occurs when the underlying data provider failed to complete

Value	Description
	the operation.
ErrorDelegateAlreadyExists	Occurs in an AddDelegate method call when the specified user already exists in the list of delegates.
ErrorDelegateCannotAddOwner	Occurs in an AddDelegate method call when the specified user to be added is the owner of the mailbox.
ErrorDelegateMissingConfiguration	Occurs in a GetDelegate method call when there is either no delegate information on a local free/busy message or no Active Directory directory service public delegate (no public delegate or no Send On Behalf entry in the directory service).
ErrorDelegateNoUser	Occurs when a specified user cannot be mapped to a user in the directory service.
ErrorDelegateValidationFailed	Occurs in an AddDelegate method call when an added delegate user is not valid.
ErrorDeleteDistinguishedFolder	Specifies that you cannot delete a distinguished folder.
ErrorDeleteItemsFailed	This response code is not used.
ErrorDistinguishedUserNotSupported	Specifies that a distinguished user ID is not valid for the operation. The DistinguishedUserType simple type should not be present in the request.
ErrorDistributionListMemberNotExist	Specifies that a particular request distribution list member does not exist in the distribution list.
ErrorDuplicateInputFolderNames	Occurs when there are duplicate folder names in the array that was passed to the CreateManagedFolder method.
ErrorDuplicateUserIdsSpecified	Specifies that a duplicate user ID has been found in a permission set, that either Default or Anonymous is set more than once, or that there are duplicate SIDs or recipients.
ErrorEmailAddressMismatch	Occurs when the e-mail address for the distinguished folder ID does not match the mailbox that you are operating on. For example, you cannot create a search folder that exists in one mailbox but considers distinguished folders from another mailbox in its search criteria.
ErrorEventNotFound	Specifies that the subscription that was created with a particular watermark is no longer valid.
ErrorExceededConnectionCount	Specifies that there are more concurrent requests against the server than are allowed by a user's policy. This error MUST be returned when that occurs.
ErrorExceededSubscriptionCount	Specifies that a user's throttling policy maximum subscription count has been exceeded. This error MUST be returned when that occurs. Active subscriptions MUST be deleted before additional subscriptions can be created if this error occurs.
ErrorExceededFindCountLimit	Specifies that a search operation call has exceeded the total number of items that can be returned.
ErrorExpiredSubscription	Specifies that the subscription that is referenced by the

Value	Description
	GetEvents method has expired.
ErrorExternalFacingCAS	Specifies that a user's mailbox resides in a different directory service site and that the site contains an external-facing server. This error code MUST be returned when that occurs. The user MUST use the Autodiscover Publishing and Lookup SOAP-Based Web Service protocol [MS-OXWSADISC] to look up the correct server to connect to a mailbox.
ErrorFolderCorrupt	Specifies that the folder is corrupted and cannot be saved.
ErrorFolderNotFound	Specifies that the folder ID that was passed in does not correspond to a valid folder, or that the delegate does not have permissions to access the folder.
ErrorFolderPropertRequestFailed	Specifies that the requested property could not be retrieved. This does not indicate that the property does not exist, but that the property was corrupted in some way so that the retrieval failed.
ErrorFolderSave	Specifies that the folder could not be created or saved because of an invalid state.
ErrorFolderSaveFailed	Specifies that the folder could not be created or saved because of an invalid state.
ErrorFolderSavePropertyError	Specifies that the folder could not be created or updated because of invalid property values. The response code lists the properties that caused the problem.
ErrorFolderExists	Specifies that a folder that has the specified name already exists. Duplicate folder names are not allowed within the same parent folder.
ErrorFreeBusyGenerationFailed	Occurs when free/busy information cannot be retrieved because of an intervening failure.
ErrorGetServerSecurityDescriptorFailed	This response code is not used.
ErrorImpersonateUserDenied	Specifies that the calling account does not have the ms-Exchange-IMP-IMP-IMP right on either the user or contact that it is trying to impersonate or the mailbox database that contains the user mailbox. This response code is returned within a SOAP fault.
ErrorImpersonationDenied	Specifies that the calling account does not have the ms-Exchange-IMP-IMP-IMP right on the Client Access server that it is calling. This response code is returned within a SOAP fault.
ErrorImpersonationFailed	Specifies that there was an unexpected error when an attempt was made to perform server-to-server authentication. This response code typically indicates either that the service account that is running the Exchange Web Services application pool is configured incorrectly, that Exchange Web Services cannot talk to the directory, or that a trust between forests is not correctly configured.
ErrorIncorrectSchemaVersion	Specifies that the request was valid for the current server version but was invalid for the request server version that

Value	Description
	was specified.
ErrorIncorrectUpdatePropertyCount	Specifies that each change description in an UpdateItem or UpdateFolder method call must list only one property to be updated.
ErrorIndividualMailboxLimitReached	Occurs when the request contains too many attendees to be resolved. By default, the maximum number of attendees to be resolved is 100.
ErrorInsufficientResources	Specifies that the mailbox server is overloaded. Try your request again later.
ErrorInternalServerError	Specifies that Exchange Web Services encountered an error that it could not recover from, and there is not a more specific response code associated with the error that occurred.
ErrorInternalServerErrorTransientError	Specifies that an internal server error occurred and that you should try your request again later.
ErrorInvalidAccessLevel	Specifies that the level of access that the caller has on the free/busy data is invalid.
ErrorInvalidArgument	Specifies an error caused by all invalid arguments passed to the GetMessageTrackingReport operation ([MS-OXWSMTRK] section 3.1.4.2). This error MUST be returned in the following scenarios: <ul style="list-style-type: none"> ▪ The user specified in the sending-as parameter does not exist in the directory. ▪ The user specified in the sending-as parameter is not unique in the directory. ▪ The sending-as address is empty. ▪ The sending-as address is not a valid e-mail address.
ErrorInvalidAttachmentId	Specifies that the attachment was not found within the attachments collection for the item. For example, you might receive this response code if you have an attachment ID and then the attachment is deleted and you try to call the GetAttachment method on the attachment ID.
ErrorInvalidAttachmentSubfilter	Occurs when you try to bind to an existing search folder by using a complex attachment table restriction. Exchange Web Services supports only simple contains filters against the attachment table. If you try to bind to an existing search folder that has a more complex attachment table restriction (a subfilter), Exchange Web Services cannot render the XML for that filter and returns this response code. Note that you can still call the GetFolder method on the folder, but do not request the SearchParameters property.
ErrorInvalidAttachmentSubfilterTextFilter	Occurs when you try to bind to an existing search folder by using a complex attachment table restriction. Exchange Web Services supports only simple contains filters against the attachment table. If you try to bind to an existing search

Value	Description
	folder that has a more complex attachment table restriction, Exchange Web Services cannot render the XML for that filter. In this case, the attachment subfilter contains a text filter, but it is not looking at the attachment display name. Note that you can still call the GetFolder method on the folder, but do not request the SearchParameters property.
ErrorInvalidAuthorizationContext	Specifies a failure to proxy an availability request to a more applicable server.
ErrorInvalidChangeKey	Specifies that an invalid change key was passed in. Note that many methods do not require a change key to be passed. However, if you do provide a change key, it must be valid, although it does not necessarily have to be up-to-date.
ErrorInvalidClientSecurityContext	Specifies that there was an internal error when an attempt was made to resolve the identity of the caller.
ErrorInvalidCompleteDate	Occurs when you try to set the CompleteDate of a task to a time in the future. When it is converted to the local time of the Client Access server, the CompleteDate cannot be set to a value that is later than the local time on the Client Access server.
ErrorInvalidContactEmailAddress	Specifies that an invalid e-mail address was provided for a contact.
ErrorInvalidContactEmailIndex	Specifies that an invalid e-mail index value was provided for an e-mail entry.
ErrorInvalidCrossForestCredentials	Occurs when an availability request is proxied to a Client Access server in another forest.
ErrorInvalidDelegatePermission	Specifies that the specified folder permissions are invalid.
ErrorInvalidDelegateUserId	Specifies that the specified delegate user ID is invalid.
ErrorInvalidExcludesRestriction	Specifies that the bitmask that was passed into the Excludes restriction could not be parsed.
ErrorInvalidExpressionTypeForSubFilter	This response code is not used.
ErrorInvalidExtendedProperty	Occurs when the combination of extended property values that was specified are invalid or they result in an invalid extended property Uniform Resource Identifier (URI).
ErrorInvalidExtendedPropertyValue	Specifies that the value that was offered for the extended property is inconsistent with the type that was specified in the associated extended field URI. For example, if the PropertyType property on the extended field URI is set to string , but you set the value of the extended property as an array of integers, you will encounter this response code.
ErrorInvalidFolderId	Occurs when the folder ID is corrupted.
ErrorInvalidFolderTypeForOperation	Specifies that the specified folder type is invalid for the current operation. For example, you cannot create a Search folder in a public folder.

Value	Description
ErrorInvalidFractionalPagingParameters	Occurs in fractional paging when the user has specified one of the following: a numerator that is greater than the denominator, a numerator that is less than 0 (zero), or a denominator that is less than or equal to 0 (zero).
ErrorInvalidFreeBusyViewType	Occurs if a FreeBusyViewType of None is requested.
ErrorInvalidId	Specifies that the structure of the ID and/or change key is internally inconsistent.
ErrorInvalidIdEmpty	Specifies that the caller specified an ID that is empty.
ErrorInvalidIdMalformed	Specifies that the structure of the ID is internally inconsistent.
ErrorInvalidIdMalformedEwsLegacyIdFormat	Specifies that a folder or item ID is using a server schema version format that is not supported by the server <8>. You must use the ConvertId method to convert them first.
ErrorInvalidIdMonikerTooLong	Specifies that the structure of the ID is internally inconsistent. The moniker is contained within the ID and indicates which mailbox the ID belongs to. This response code is returned if the length of the moniker is checked and the byte count is longer than expected.
ErrorInvalidIdNotAnItemAttachmentId	Occurs when the AttachmentId property does not refer to an item attachment.
ErrorInvalidIdReturnedByResolveNames	Specifies that a contact in your mailbox is corrupt.
ErrorInvalidIdStoreObjectIdTooLong	Occurs when the structure of the ID is internally inconsistent.
ErrorInvalidIdTooManyAttachmentLevels	Specifies that the attachment hierarchies exceed the maximum of 255 levels deep.
ErrorInvalidIdXml	This response code is not used.
ErrorInvalidIndexedPagingParameters	Occurs if the offset for indexed paging is less than 0 (zero).
ErrorInvalidInternetHeaderChildNodes	This response code is not used.
ErrorInvalidItemForOperationCreateItemAttachment	Specifies that you tried to create an item attachment by using an unsupported item type. Supported item types for item attachments include ItemType , MessageType , CalendarItemType , TaskType , and ContactItemType objects. For example, if you try to create a MeetingMessage attachment, you will encounter this response code.
ErrorInvalidItemForOperationCreateItem	Specifies that you tried to create an unsupported item. Supported items include ItemType , MessageType , CalendarItemType , TaskType , and ContactItemType objects. For example, you cannot create a DistributionList object by using the CreateItem method. In addition, certain types are created as a side effect of doing something else. MeetingMessages objects, for example, are created when you send a calendar item to attendees; they are not explicitly created.
ErrorInvalidItemForOperationAcceptItem	Occurs when an AcceptItemType object is created on

Value	Description
	something other than a meeting request or a calendar item, or when an attempt is made to accept a calendar item occurrence that is in the Deleted Items folder.
ErrorInvalidItemForOperationDeclineItem	Specifies that a DeclineItemType object was created on something other than a meeting request or a calendar item, or that you tried to decline a calendar item occurrence that is in the Deleted Items folder.
ErrorInvalidItemForOperationCancelItem	Occurs when a CancelCalendarItemType object is created for something other than a calendar item.
ErrorInvalidItemForOperationExpandDL	Occurs when the instance of the ExpandDLType class that was passed to the ExpandDL method does not represent a distribution list.
ErrorInvalidItemForOperationRemoveItem	Occurs when a RemoveItemType object is created for an item other than a meeting cancellation.
ErrorInvalidItemForOperationSendItem	Occurs if the SendItem method was attempted on an item other than a message item. Only items whose ItemClass property value begins with IPM.Note can be sent.
ErrorInvalidItemForOperationTentative	Occurs if a TentativelyAcceptItemType object was created on an item other than a calendar item or meeting request. Also occurs if the TentativelyAcceptItemType object was created for a calendar item occurrence that is in the Deleted Items folder.
ErrorInvalidLogonType	This error is for internal use only. This error is not returned.
ErrorInvalidMailbox	<p>Specifies that the CreateItem or UpdateItem operation failed while creating or updating a personal distribution list. This error MUST be returned under the following conditions:</p> <ul style="list-style-type: none"> A member is not accessible by using an item identifier to identify the member's mailbox. The following m:ResponseMessageType XML MUST be returned for this scenario: <pre><m:MessageText>Mailbox is invalid. Verify the specified Mailbox property.</m:MessageText> <m:ResponseCode>ErrorInvalidMailbox</m:ResponseCode> <m:MessageXml> <t:FieldURI FieldURI="distributionlist:Members"/> <t:Value Name="Inner.ResponseCode">ErrorNonExistentMailbox</t:Value> <t:Value Name="Inner.MessageText">No mailbox with such guid.</t:Value> </m:MessageXml></pre> The specified identifier is for a private distribution list but the MailboxTypeType simple type (section 2.2.2.16) is not set to PrivateDL. The MessageText element of the ResponseMessageType complex type (section 2.2.3.52) MUST contain the following text: MailboxType should be

Value	Description
	<p>PrivateDL or not specified.</p> <ul style="list-style-type: none"> The specified identifier is for a database contact item but the contact does not have an e-mail address. The specified member's e-mail address, routing type, or name does not match to the corresponding properties of any contact's e-mail addresses. The MessageText element of the ResponseMessageType complex type (section 2.2.3.52) MUST contain the following text: The contact address wasn't found. The specified identifier is for a folder instead of a contact or private distribution list store item identifier. The following ResponseMessageType complex type (section 2.2.3.52) XML MUST be returned for this scenario: <pre><m:MessageText>Mailbox is invalid. Verify the specified Mailbox property.</m:MessageText> <m:ResponseCode>ErrorInvalidMailbox</m:ResponseCode> <m:MessageXml> <t:FieldURI FieldURI="distributionlist:Members"/> <t:Value Name="Inner.ResponseCode">ErrorCannotUseFolderIdForItemId</t:Value> <t:Value Name="Inner.MessageText">Expected an item Id but received a folder Id.</t:Value> </m:MessageXml></pre> The specified identifier does not represent either a contact or private distribution list. The following m:ResponseMessageType XML MUST be returned for this scenario where MemberIndex represents the index of the identifier that caused the error: <pre><m:MessageText>The ID of this item can't be used for a recipient, attendee, or group member.</m:MessageText> <m:ResponseCode>ErrorInvalidMailbox</m:ResponseCode> <m:MessageXml> <t:FieldURI FieldURI="distributionlist:Members"/> <t:Value Name="MemberIndex">7</t:Value> </m:MessageXml></pre> The mailbox is not specified by either an EmailAddress or ItemId element in the Mailbox element of the EmailAddressType. The following m:ResponseMessageType XML MUST be returned for this scenario where MemberIndex represents the index of the identifier that caused the error: <pre><m:MessageText>EmailAddress or ItemId must be included in the request.</m:MessageText> <m:ResponseCode>ErrorInvalidMailbox</m:ResponseCode> <m:MessageXml> <t:FieldURI FieldURI="distributionlist:Members"/> <t:Value Name="MemberIndex">0</t:Value></pre>

Value	Description
	<p data-bbox="768 201 971 226"></m:MessageXml></p> <ul data-bbox="768 247 1414 380" style="list-style-type: none"> <li data-bbox="768 247 1414 380">The member with the specified email address does not exist in the directory. The following m:ResponseMessageType XML MUST be returned for this scenario where MemberIndex represents the index of the identifier that caused the error: <pre data-bbox="768 405 1414 646"> <m:MessageText>Recipient is not found in Active Directory. Change MailboxType to OneOff or remove it.</m:MessageText> <m:ResponseCode>ErrorInvalidMailbox</m:ResponseCode> <m:MessageXml> <t:FieldURI FieldURI="distributionlist:Members"/> <t:Value Name="MemberIndex">1</t:Value> </m:MessageXml> </pre> <ul data-bbox="768 674 1414 751" style="list-style-type: none"> <li data-bbox="768 674 1414 751">A user with the specified email address does exist in the AD, but the specified MailboxType does not match user type in the directory. <p data-bbox="768 779 1414 877">The MessageXML element of the m:ResponseMessageType as specified in section 2.2.3.52, MUST contain the following XML when a member cannot be created or updated.</p> <pre data-bbox="797 905 1317 1031"> <m:MessageXml> <t:FieldURI FieldURI="distributionlist:Members"/> <t:Value Name="MemberIndex">4</t:Value> </m:MessageXml> </pre> <p data-bbox="768 1087 1414 1165">The MemberIndex value MUST specify the failing member from the either an UpdateItem or CreateItem request. The MemberIndex is a 0-based index.</p>
ErrorInvalidManagedFolderProperty	Specifies that the structure of the managed folder is corrupted and cannot be rendered.
ErrorInvalidManagedFolderQuota	Specifies that the quota that is set on the managed folder is less than zero, which indicates a corrupted managed folder.
ErrorInvalidManagedFolderSize	Specifies that the size that is set on the managed folder is less than zero, which indicates a corrupted managed folder.
ErrorInvalidMergedFreeBusyInterval	Specifies that the supplied merged free/busy interval value is invalid. The default minimum value is 5 minutes. The default maximum value is 1440 minutes.
ErrorInvalidNameForNameResolution	Specifies that the name that was passed into the ResolveNames method was invalid. For example, a zero-length string, a single space, a comma, and a dash are all invalid names.
ErrorInvalidOperation	This is a general error that is used when the requested operation is invalid. For example, this error indicates any of the following:

Value	Description
ErrorInvalidNetworkServiceContext	Specifies an error in the Network Service account on the Client Access server.
ErrorInvalidOofParameter	This response code is not used.
ErrorInvalidPagingMaxRows	Specifies that zero rows or a negative value is specified as the maximum number of rows to be returned.
ErrorInvalidParentFolder	Specifies that you passed in an invalid parent folder for an operation, for example by creating a folder within a search folder.
ErrorInvalidPercentCompleteValue	Occurs if the percent complete property is set to a value that is not between 0 and 100 (inclusive).
ErrorInvalidPermissionSettings	Specifies that the permission level is inconsistent with the permission settings.
ErrorInvalidPhoneCallId	Specifies that the caller identifier is not valid.
ErrorInvalidPhoneNumber	Specifies that the phone number is not correct or does not fit the dial plan rules.
ErrorInvalidUserInfo	<p>Specifies that a client sent an invalid folder permission request. This error code MUST be returned under the following conditions:</p> <ul style="list-style-type: none"> ▪ A user specifies a DistinguishedUser element of type t:DistinguishedUserType set to anonymous or default but then also provide either a SID, primary SMTP address or display name. ▪ SID cannot be mapped to a user. ▪ Primary SMTP address cannot be mapped to a user. ▪ User specifies more than one mailbox by setting more than one of the following properties: SID, primary SMTP address, and display name. ▪ An invalid SMTP address was provided for an external user. ▪ The request doesn't specify a distinguished user, SID, primary SMTP address, display name, or external user. ▪ The request specifies an identity that does not map to a user, group, or contact in the directory. ▪ The provided user permission is a disabled user that had a SELF SID in the directory. ▪ The request attempt to set the anonymous or default user permissions but the attempted permissions are not available on the folder. <p>The MessageXML for an ErrorInvalidUserInfo response contains the SID and display name that MUST identify the user to be given permissions and the permission level that we attempted to be given to a user. The MessageXML can look</p>

Value	Description
	<p>like the following:</p> <pre data-bbox="797 254 1422 611"> <m:MessageXml> <t:InvalidPermission> <t:Permission> <t:UserId> <t:SID>S-1-5-21-797165400-4101840936-1213943508-1116</t:SID> <t:DisplayName>Christopher M. Simison</t:DisplayName> </t:UserId> <t:PermissionLevel>Owner</t:PermissionLevel> </t:Permission> </t:InvalidPermission> </m:MessageXml> </pre>
ErrorInvalidPropertyAppend	Occurs if the property that you are trying to append to does not support appending. The following are the only properties that support appending: Recipient collections (To, Cc, Bcc), Attendee collections (Required, Optional, Resources), Body property, and ReplyTo.
ErrorInvalidPropertyDelete	Specifies that the property that you are trying to delete does not support deleting. For example, you cannot delete the ItemId property of the ItemType object.
ErrorInvalidPropertyForExists	Occurs if you pass one of the flag properties to a RestrictionType filter of ExistsType. The following are the flag properties: IsDraft, IsSubmitted, IsUnmodified, IsResend, and IsFromMe.
ErrorInvalidPropertyForOperation	Specifies that the property that you are trying to manipulate does not support the operation that is being performed on it.
ErrorInvalidPropertyRequest	Occurs if the property that is specified in the request is not available for the item type. For example, this response code is returned if a property that is only available on calendar items is requested in a GetItem method call for a message or is updated in an UpdateItem method call for a message.
ErrorInvalidPropertySet	Specifies that the property you are trying to set is read-only.
ErrorInvalidPropertyUpdateSentMessage	Occurs during an UpdateItem method call when a client tries to update certain properties of a message that has already been sent. For example, the following properties cannot be updated on a sent message: IsReadReceiptRequested and IsDeliveryReceiptRequested
ErrorInvalidProxySecurityContext	This response code is not used.
ErrorInvalidPullSubscriptionId	Occurs if you called GetEvents or Unsubscribe on a push subscription ID. To unsubscribe from a push subscription, you must respond to a push request with an unsubscribe response, or disconnect your Web service and wait for the push notifications to time out.

Value	Description
ErrorInvalidPushSubscriptionUrl	Specifies that the URL that was provided as a callback for the Subscribe method has an invalid format. The following conditions must be met for Exchange Web Services to accept the URL: String length MUST be greater than 0 and less than 2083, protocol is http or https, and able to be parsed by the URI Microsoft .NET Framework class.
ErrorInvalidRecipients	Specifies that the recipient collection on your message or the attendee collection on your calendar item is invalid.
ErrorInvalidRecipientSubfilter	Specifies that the search folder has a recipient table filter that Exchange Web Services cannot represent. To fix the error, retrieve the folder without requesting the search parameters.
ErrorInvalidRecipientSubfilterComparison	Specifies that the search folder has a recipient table filter that Exchange Web Services cannot represent. To fix the error, retrieve the folder without requesting the search parameters.
ErrorInvalidRecipientSubfilterOrder	Specifies that the search folder has a recipient table filter that Exchange Web Services cannot represent. To fix the error, retrieve the folder without requesting the search parameters.
ErrorInvalidRecipientSubfilterTextFilter	Specifies that the search folder has a recipient table filter that Exchange Web Services cannot represent. To fix the error, retrieve the folder without requesting the search parameters.
ErrorInvalidReferenceItem	Occurs under the following circumstances: The referenced item identifier is not a MessageType or CalendarItemType object, or one of their descendants; the reference item identifier is for a CalendarItemType object and the organizer is trying to Reply or ReplyAll. Calendar items can only be forwarded by the organizer; the message is a draft and Reply or ReplyAll is selected, and the ResponseObjects is set to SuppressReadReceipt and the item is not a message.
ErrorInvalidRequest	Specifies that the SOAP request has a SOAP action header, but nothing in the SOAP body. Note that the SOAP action header is not required as Exchange Web Services can determine the method to call from the local name of the root element in the SOAP body.
ErrorInvalidRestriction	This response code is not used.
ErrorInvalidRoutingType	Specifies that the RoutingType property that was passed for an EmailAddressType is not a valid routing type. Typically, routing type is set to SMTP.
ErrorInvalidScheduledOofDuration	Occurs if the specified duration end time is not greater than the start time, or if the end time does not occur in the future.
ErrorInvalidSchemaVersionForMailboxVersion	Specifies that a proxy request sent to another server is not capable of servicing the request due to a versioning mismatch. This error MUST be returned when the RequestServerVersion element (section 2.2.4.8) specifies a server version that does not match the mailbox server for a proxy request.
ErrorInvalidSecurityDescriptor	Specifies that the security descriptor on the Calendar folder in the store is corrupted.

Value	Description
ErrorInvalidSendItemSaveSettings	Occurs during an attempt to send an item where the SaveItemFolderId is specified in the request but the SaveItemToFolder property is set to false.
ErrorInvalidSerializedAccessToken	Specifies that the token that was passed in the header is malformed, does not refer to a valid account in the directory, or is missing the primary group SID.
ErrorInvalidServerVersion	Specifies that an invalid request server version was specified in the request.
ErrorInvalidSid	Specifies that one or more of the SID properties within the passed token or Impersonation block have an invalid structure.
ErrorInvalidSIPUri	Specifies that the SIP name, dial plan, or the phone number are invalid SIP URI.
ErrorInvalidSmtpAddress	Specifies that the SMTP address cannot be parsed.
ErrorInvalidSubfilterType	This response code is not used.
ErrorInvalidSubfilterTypeNotAttendeeType	This response code is not used.
ErrorInvalidSubfilterTypeNotRecipientType	This response code is not used.
ErrorInvalidSubscription	Specifies that the subscription is no longer valid. This could be because the Client Access is restarting or because the subscription expired.
ErrorInvalidSubscriptionRequest	Specifies that the subscribe request included multiple public folder IDs. A subscription can include multiple folders from the same mailbox or one public folder ID.
ErrorInvalidSyncStateData	Specifies that the sync state data is corrupted. This is returned by the SyncFolderItems method or the SyncFolderHierarchy method if the SyncState property data is invalid. To fix this error, you must resynchronize without the sync state. Make sure that if you are persisting sync state blobs and that you are not accidentally truncating the BLOB.
ErrorInvalidTimeInterval	Specifies that the specified time interval is invalid. The start time must be greater than or equal to the end time.
ErrorInvalidUserOofSettings	Specifies that the user Out of Office (OOF) settings are invalid because of a missing internal or external reply.
ErrorInvalidUserPrincipalName	Specifies that the UPN that was passed in the Impersonation SOAP header did not map to a valid account.
ErrorInvalidUserSid	Specifies that the SID that was passed in the Impersonation SOAP header was either structurally invalid or did not map to a valid account.
ErrorInvalidUserSidMissingUPN	This response code is not used.
ErrorInvalidValueForProperty	Specifies that the comparison value in the restriction is invalid for the property you are comparing against. For example, the comparison value of DateTimeCreated > true

Value	Description
	would return this response code. This response code is also returned if you specify an enumeration property in the comparison, but the value that you are comparing against is not a valid value for that enumeration.
ErrorInvalidWatermark	Specifies that the watermark is invalid.
ErrorIPGatewayNotFound	Specifies that a valid VoIP gateway is not available.
ErrorIrresolvableConflict	Specifies that conflict resolution was unable to resolve changes for the properties. The items in the store may have been changed and have to be updated. Retrieve the updated change key and try again.
ErrorItemCorrupt	Specifies that the state of the object is corrupted and cannot be retrieved. When you are retrieving an item, only certain properties will be in this state, such as Body and MimeContent. Omit these properties and retry the operation.
ErrorItemNotFound	Specifies that the item was not found or you do not have rights to access the item.
ErrorItemPropertyRequestFailed	Occurs if a property request fails. The property may exist, but could not be retrieved.
ErrorItemSave	Occurs when attempts to save the item or folder fail.
ErrorItemSavePropertyError	Occurs when attempts to save the item or folder fail because of invalid property values. The response code includes the path of the invalid properties.
ErrorLegacyMailboxFreeBusyViewTypeNotMerged	This response code is not used.
ErrorLocalServerObjectNotFound	This response code is not used.
ErrorLogonAsNetworkServiceFailed	Specifies that the availability service was unable to log on as the network service in order to proxy requests to the appropriate sites or forests. This response typically indicates a configuration error.
ErrorMailboxConfiguration	Specifies that the mailbox information in Active Directory is configured incorrectly.
ErrorMailboxDataArrayEmpty	Specifies that the MailboxDataArray property in the request is empty. You must supply at least one mailbox identifier.
ErrorMailboxDataArrayTooBig	Occurs when more than 100 entries are supplied in a MailboxDataArray.
ErrorMailboxLogonFailed	Occurs when the connection to the mailbox to get the calendar view information failed.
ErrorMailboxMoveInProgress	Specifies that the mailbox is currently being moved. Try your request again after the move is complete.
ErrorMailboxStoreUnavailable	Specifies that the mailbox database is offline, corrupt, shutting down, or exhibiting other conditions that make the mailbox unavailable.

Value	Description
ErrorMailRecipientNotFound	Occurs if the MailboxData information cannot be mapped to a valid mailbox account.
ErrorMailTipsDisabled	Specifies that mail tips are disabled. This error code MUST be returned when mail tips are disabled.
ErrorManagedFolderAlreadyExists	Specifies that the managed folder that you are trying to create already exists in your mailbox.
ErrorManagedFolderNotFound	Occurs when the folder name that was specified in the request does not map to a managed folder definition in Active Directory. You can only create instances of managed folders for folders defined in Active Directory. Check the name and try again.
ErrorManagedFoldersRootFailure	Specifies that the managed folders root was deleted from the mailbox or that there is already a folder in the same parent folder that has the name of the managed folder root. This will also occur if the attempt to create the root managed folder fails.
ErrorMeetingSuggestionGenerationFailed	Specifies that the suggestions engine encountered a problem when it was trying to generate the suggestions.
ErrorMessageDispositionRequired	Occurs if the MessageDisposition property is not set. This property is required: 1) When the item that is being created or updated is a MessageType object. 2) For the CancelCalendarItemType, AcceptItemType, DeclineItemType, or TentativelyAcceptItemType response objects.
ErrorMessageSizeExceeded	Specifies that the message that you are trying to send exceeded the allowed limits.
ErrorMimeContentConversionFailed	Occurs when the MIME content is not a valid iCal for a CreateItem method. For a GetItem method, this response indicates that the MIME content could not be generated.
ErrorMimeContentInvalid	Occurs when the MIME content is invalid.
ErrorMimeContentInvalidBase64String	Occurs when the MIME content in the request is not a valid base64 string.
ErrorMissingArgument	Specifies that a required argument was missing from the request. The response message text indicates which argument to check.
ErrorMissingEmailAddress	Specifies that you specified a distinguished folder ID in the request, but the account that made the request does not have a mailbox on the system.
ErrorMissingEmailAddressForManagedFolder	Specifies that you specified a distinguished folder ID in the request, but the account that made the request does not have a mailbox on the system. This response is returned from the CreateManagedFolder method.
ErrorMissingInformationEmailAddress	Specifies that the attendee or recipient does not have the EmailAddress property set. The other two EmailAddressType properties, Name and RoutingType, are optional.

Value	Description
ErrorMissingInformationReferenceItemId	Occurs if the ReferenceItemId property value is missing from the response object.
ErrorMissingItemForCreateItemAttachment	Occurs when you are creating an item attachment if you do not indicate the item that you want to create.
ErrorMissingManagedFolderId	Occurs when the policy IDs property, property tag 0x6732, for the folder is missing. You should consider this a corrupted folder.
ErrorMissingRecipients	Specifies that you tried to send an item without including recipients. Note that if you call the CreateItem method with a message disposition that causes the message to be sent, you will get the following response code: ErrorInvalidRecipients.
ErrorMissingUserIdInformation	Specifies that a user ID has not been fully specified in a permissions set.
ErrorMoreThanOneAccessModeSpecified	Specifies that you have specified more than one ExchangeImpersonation or SerializedSecurityContext property value within a request.
ErrorMoveCopyFailed	Specifies that the move or copy operation failed. Moving occurs in the CreateItem method when you accept a meeting request that is in the Deleted Items folder. In addition, if you decline a meeting request, cancel a calendar item, or remove a meeting from your calendar, it is moved to the Deleted Items folder.
ErrorMoveDistinguishedFolder	Occurs if you try to move a distinguished folder.
ErrorNameResolutionMultipleResults	Specifies that the ResolveNames method returned more than one result or that the ambiguous name that you specified matched more than one object in the directory. The response code includes the matched names in the response data.
ErrorNameResolutionNoMailbox	Specifies that the caller does not have a mailbox on the system.
ErrorNameResolutionNoResults	Occurs if the ResolveNames method returns no results.
ErrorNoApplicableProxyCASServersAvailable	This error code MUST be returned when the Web service cannot find a server to handle the request.
ErrorNoCalendar	Occurs if there is no Calendar folder for the mailbox.
ErrorNoDestinationCASDueToKerberosRequirements	Specifies that the request referred to a mailbox in another Active Directory site, but no Client Access servers in the destination site were configured for win Authentication and therefore the request could not be proxied.
ErrorNoDestinationCASDueToSSLRequirements	Specifies that the request referred to a mailbox in another Active Directory site, but no Client Access servers in the destination site were configured for SSL connections and therefore the request could not be proxied.
ErrorNoDestinationCASDueToVersionMismatch	Specifies that the request referred to a mailbox in another Active Directory site, but no Client Access servers in the destination site were of an acceptable product version to

Value	Description
	receive the request and therefore the request could not be proxied.
ErrorNoFolderClassOverride	Occurs if you set the FolderClass property when you are creating an item other than a generic folder. For typed folders such as CalendarFolderType and TasksFolderType, the folder class is implied. Setting the folder class to a different folder type by using the UpdateFolder method results in the ErrorObjectTypeChanged response. Instead, use a generic folder type but set the folder class to the value that you require. Exchange Web Services will create the correct strongly typed folder.
ErrorNoFreeBusyAccess	Specifies that the caller does not have free/busy viewing rights on the Calendar folder in question.
ErrorNonExistentMailbox	Specifies one of the following: 1) The e-mail address is empty in the CreateManagedFolder method 2) the SMTP address does not map to a valid mailbox.
ErrorNonPrimarySmtpAddress	Occurs when a caller passes in a non-primary SMTP address. The response includes the correct SMTP address to use.
ErrorNoPropertyTagForCustomProperties	Specifies that MAPI properties in the custom range, 0x8000 and greater, cannot be referenced by property tags. You must use the PropertySetId property or the DistinguishedPropertySetId together with the PropertyName or PropertyId properties.
ErrorNoPublicFolderReplicaAvailable	This response code is not used.
ErrorNoPublicFolderServerAvailable	This error code MUST be returned if no public folder server is available or if the caller does not have a home public server.
ErrorNoRespondingCASInDestinationSite	Specifies that the request referred to a mailbox in another Active Directory site, but none of the Client Access servers in that site responded and therefore the request could not be proxied.
ErrorNotDelegate	Specifies that the user is not a delegate for the mailbox. This error is returned by GetDelegate, RemoveDelegate, and UpdateDelegate method calls when the specified delegate user is not found in the list of delegates.
ErrorNotEnoughMemory	Specifies that the operation could not be completed because of insufficient memory.
ErrorObjectTypeChanged	Specifies that the object type cannot be changed. For the CreateItem method, the ItemClass property must be consistent with the strongly typed item such as a Message or Contact.
ErrorOccurrenceCrossingBoundary	Specifies that the time allotment for a given occurrence overlaps with an earlier or later occurrence.
ErrorOccurrenceTimeSpanTooBig	Specifies that the time allotment for a given occurrence overlaps with another occurrence of the same recurring item. This response also occurs if the length in minutes of a given occurrence is larger than Int32.MaxValue.

Value	Description
ErrorOperationNotAllowedWithPublicFolderRoot	Specifies that the current operation is not valid to be performed on the public folder root.
ErrorParentFolderIdRequired	This response code is not used.
ErrorParentFolderNotFound	Occurs in the CreateFolder when the parent folder is not found.
ErrorPasswordChangeRequired	Specifies that you must change your password before you can access this mailbox. This occurs when a new account has been created and the administrator indicated that the user must change the password at first logon. You cannot update the password by using Exchange Web Services. You must use a tool such as Outlook Web Access to change your password.
ErrorPasswordExpired	Specifies that the password has expired. You cannot change the password by using Exchange Web Services. You must use a tool such as Outlook Web Access to change your password.
ErrorPhoneNumberNotDialable	Specifies that the phone number was not in the correct phone form.
ErrorPropertyUpdate	Specifies that the update failed because of invalid property values. The response message includes the invalid property paths.
ErrorPropertyValidationFailure	This response code is not used.
ErrorProxiedSubscriptionCallFailure	Specifies that the request referred to a subscription that exists on another Client Access server, but an attempt to proxy the request to that Client Access server failed.
ErrorProxyCallFailed	This response code is not used.
ErrorProxyGroupSidLimitExceeded	Specifies that the request referred to a mailbox in another Active Directory site, and the original caller is a member of more than 3000 groups.
ErrorProxyRequestNotAllowed	Specifies that the request that Exchange Web Services sent to another Client Access server when trying to fulfill a GetUserAvailability request was invalid. This response code likely indicates a configuration or rights error, or that someone is trying unsuccessfully to mimic an availability proxy request.
ErrorProxyRequestProcessingFailed	Specifies that Exchange Web Services tried to proxy an availability request to another Client Access server for fulfillment, but the request failed. This response can be caused by network connectivity issues or request time-out issues.
ErrorProxyServiceDiscoveryFailed	This error code MUST be returned if the Web service cannot determine whether the request is to run on the target server or will be proxied to another server.
ErrorProxyTokenExpired	This response code is not used.
ErrorPublicFolderRequestProcessingFailed	Occurs when the recipient passed to GetUserAvailability is located on a computer that is running a server version that is

Value	Description
	earlier than the 2007 server version and the request to retrieve free/busy information for the recipient from the public folder server failed.
ErrorPublicFolderServerNotFound	Occurs when the recipient passed to GetUserAvailability is located on a server that is running a server version that is earlier than the 2007 server version and the request to retrieve free/busy information for the recipient from the public folder server failed because the organizational unit did not have a public folder server associated with it.
ErrorQueryFilterTooLong	Specifies that the search folder restriction may be valid, but is not supported by Exchange Web Services. Exchange Web Services limits restrictions to contain a maximum of 255 filter expressions. If you try to bind to an existing search folder that exceeds 255, this response code is returned.
ErrorQuotaExceeded	Occurs when the mailbox quota is exceeded.
ErrorReadEventsFailed	Specifies that the process for reading events was aborted because of an internal failure. Re-create the event synchronization based on a last known watermark.
ErrorReadReceiptNotPending	Occurs when an attempt has been made to suppress a read receipt when the message sender did not request a read receipt on the message.
ErrorRecurrenceEndDateTooBig	Occurs when the end date for the recurrence is after 9/1/4500.
ErrorRecurrenceHasNoOccurrence	Specifies that the recurrence has no occurrence instances in the specified range.
ErrorRemoveDelegatesFailed	Specifies that the delegate list failed to be saved after delegates were removed.
ErrorRequestAborted	This response code is not used.
ErrorRequestStreamTooBig	Specifies that during availability proxying, the request was determined to be too large.
ErrorRequiredPropertyMissing	Specifies that one or more of the required properties is missing from a CreateAttachment call. The response indicates which property path was not set.
ErrorResolveNamesInvalidFolderType	Specifies that the caller has specified a folder that is not a Contacts folder to ResolveNames.
ErrorResolveNamesOnlyOneContactsFolderAllowed	Specifies that the caller has specified more than one Contacts folder to ResolveNames.
ErrorResponseSchemaValidation	This response code is not used.
ErrorRestrictionTooLong	Occurs when the restriction has more than 255 filters.
ErrorRestrictionTooComplex	Specifies that the restriction that was passed cannot be evaluated by Exchange Web Services.
ErrorResultSetTooBig	Specifies that the number of calendar entries for a given recipient exceeds the allowed limit of 1000. Reduce the

Value	Description
	window and try again.
ErrorInvalidExchangeImpersonationHeaderData	Specifies that the ExchangeImpersonation header is missing or empty. This error MUST be returned if an ExchangeImpersonation element (section 2.2.4.3) is empty.
ErrorSavedItemFolderNotFound	Specifies that the folder in which to save the item does not exist.
ErrorSchemaValidation	Occurs when the incoming request fails schema validation against types.xsd and messages.xsd. This response code is always returned within a SOAP fault.
ErrorSearchFolderNotInitialized	Specifies that the search folder was created, but the search criteria were never set on the folder. This only occurs when you access corrupted search folders that were created by using another API or client. To fix this error, call UpdateFolder and set the SearchParameters to include the restriction that should be on the folder.
ErrorSendAsDenied	Occurs when both of the following conditions occur:
ErrorSendMeetingCancellationsRequired	Occurs during a DeleteItem call, when the SendMeetingCancellations property is missing from the request and the item to delete is a calendar item. If you are using the proxy objects, make sure that the SendMeetingCancellationsSpecified property is set to true.
ErrorSendMeetingInvitationsOrCancellationsRequired	Occurs during an UpdateItem method call, when the SendMeetingInvitationsOrCancellations property is missing from the request and the item to update is a calendar item. If you are using the proxy objects, make sure that the SendMeetingInvitationsOrCancellationsSpecified property is set to true.
ErrorSendMeetingInvitationsRequired	Occurs during a CreateItem method call, when the SendMeetingInvitations property is missing from the request and the item to create is a calendar item. If you are using the proxy objects, make sure that the SendMeetingInvitationsSpecified property is set to true.
ErrorSentMeetingRequestUpdate	Specifies that after the organizer sends a meeting request, the request cannot be updated. To modify the meeting, modify the calendar item, not the meeting request.
ErrorSentTaskRequestUpdate	Specifies that after the task initiator sends a task request, that request cannot be updated.
ErrorServerBusy	Occurs when the server is busy.
ErrorServiceDiscoveryFailed	Specifies that Exchange Web Services tried to proxy a user availability request to the appropriate forest for the recipient, but it could not determine where to send the request because of a service discovery failure.
ErrorStaleObject	Occurs in an UpdateItem or SendItem method call when the change key is not up to date or was not supplied. Call GetItem to retrieve an updated change key and then try the

Value	Description
	operation again.
ErrorSubmissionQuotaExceeded	Specifies that a user cannot immediately send more request because the submission quota has been reached.
ErrorSubscriptionAccessDenied	Specifies that you tried to access a subscription by using an account that did not create that subscription. Each subscription can only be accessed by the creator of the subscription.
ErrorSubscriptionDelegateAccessNotSupported	Specifies that you cannot create a subscription if you are not the owner or do not have owner access to the mailbox.
ErrorSubscriptionNotFound	Specifies that the specified subscription does not exist. The subscription may have expired, the Exchange Web Services process may have been restarted, or an invalid subscription was passed in. If the subscription was valid, re-create the subscription with the latest watermark.
ErrorSubscriptionUnsubscribed	This error code MUST be returned when a request is made for a subscription that has been unsubscribed.
ErrorSyncFolderNotFound	Specifies that the folder ID that was specified in the SyncFolderItems method call does not exist.
ErrorTimeIntervalTooBig	Specifies that the time window that was specified is larger than the allowed limit. By default, the allowed limit is 42.
ErrorTimeoutExpired	Specifies that the proxied request timed out.
ErrorTimeZone	Specifies that there is a time zone error.
ErrorToFolderNotFound	Specifies that the destination folder does not exist.
ErrorTokenSerializationDenied	Occurs if the caller tries to perform a token serialization request but does not have ms-Exch-EPI-TokenSerialization rights on the Client Access server they are calling.
ErrorUpdatePropertyMismatch	Occurs when the single property path that is listed in a change description does not match the single property that is being set within the actual ItemType or FolderType object.
ErrorUnifiedMessagingDialPlanNotFound	Specifies that a user's dial plan is not available.
ErrorUnifiedMessagingRequestFailed	Specifies that the user could not be found.
ErrorUnifiedMessagingServerNotFound	Specifies that a valid server for the dial plan can be found to handle the request.
ErrorUnableToGetUserOofSettings	This response code is not used.
ErrorUnsupportedSubFilter	This response code is not used.
ErrorUnsupportedCulture	Occurs if you try to set the Culture property to a value that is not parsable by the System.Globalization.CultureInfo class.
ErrorUnsupportedMapiPropertyType	Occurs if a caller tries to use extended properties of types object, object array, error or null.

Value	Description
ErrorUnsupportedMimeConversion	Occurs when you are trying to retrieve or set MIME content for an item other than a PostItemType, MessageType, or CalendarItemType object.
ErrorUnsupportedPathForQuery	Specifies that the property path cannot be used within a restriction. This value MUST be returned if an Excludes restriction is performed on a non-integer property.
ErrorUnsupportedPathForSortGroup	Specifies that the property path cannot be used for sorting or grouping operations.
ErrorUnsupportedPropertyDefinition	This response code is not used.
ErrorUnsupportedQueryFilter	Specifies that the search folder restriction may be valid, but is not supported by Exchange Web Services. You can still call the FindItem method on the search folder restriction to retrieve the items in the search folder; however, you cannot get the actual restriction clause.
ErrorUnsupportedRecurrence	Specifies that the recurrence pattern that was supplied is not supported for tasks.
ErrorUnsupportedTypeForConversion	Specifies that Exchange Web Services found a property type in the store but cannot generate XML for the property type.
ErrorUpdateDelegatesFailed	Specifies that the delegate list failed to be saved after delegates were updated.
ErrorUserNotUnifiedMessagingEnabled	Specifies that the requestor is not enabled.
ErrorValueOutOfRange	Specifies that a calendar view start date or end date was set to 1/1/0001 12:00:00 AM or 12/31/9999 11:59:59 PM.
ErrorVoiceMailNotImplemented	Specifies that voice mail is not implemented.
ErrorVirusDetected	Specifies that the database detected a virus in the message.
ErrorVirusMessageDeleted	Specifies that the database detected a virus in the message and deleted it.
ErrorWebRequestInInvalidState	This response code is not used.
ErrorWin32InteropError	Specifies that there was an internal failure during communication with unmanaged code.
ErrorWorkingHoursSaveFailed	This response code is not used.
ErrorWorkingHoursXmlMalformed	This response code is not used.
ErrorWrongServerVersion	Specifies that a request can only be made to a server that is the same version as the mailbox server. This error MUST be returned if a request is made to a server that is not the same version as the mailbox server.
ErrorWrongServerVersionDelegate	Specifies that a request was made by a delegate that has a different server version than the principal's mailbox server. This error MUST be returned if a request was made by a delegate that has a different server version than the principal's mailbox server.

Value	Description
ErrorMissingInformationSharingFolderId	This error code is never returned.
ErrorDuplicateSOAPHeader	Specifies that there are duplicate SOAP headers.
ErrorSharingSynchronizationFailed	Specifies that an attempt at synchronizing a sharing folder failed. This error code MUST be returned when: <ul style="list-style-type: none"> ▪ The subscription for a sharing folder is not found. ▪ The sharing folder was not found. ▪ The corresponding directory user was not found. ▪ The user no longer exists. ▪ The appointment is invalid. ▪ The contact item is invalid. ▪ There was a communication failure with the remote server.
ErrorSharingNoExternalEwsAvailable	Specifies that the external URL property has not been set in the Active Directory database. This error code MUST be returned if the external URL property has not been set in the Active Directory database.
ErrorFreeBusyDLLimitReached	Specifies that the maximum group member count has been reached for obtaining free/busy information for a distribution list. This error MUST be returned when the maximum group member count has been reached for obtaining free/busy information for a distribution list.
ErrorInvalidGetSharingFolderRequest	Specifies that the DataType and ShareFolderId element are both present in a request. This error code MUST be returned if the DataType and ShareFolderId element are both present in a request.
ErrorNotAllowedExternalSharingByPolicy	Specifies that the caller attempted to grant permissions in its calendar or contacts folder to a user in another organization and the attempt failed. This error code MUST be returned when the sharing policy is disabled for the caller or when the sharing policy assigned to the caller disallows sharing for the requested level or the requested folder type.
ErrorUserNotAllowedByPolicy	Specifies that the requestor attempted to grant permissions in its calendar or contacts folder to an external user but the sharing policy assigned to the requestor specifies that the domain of the external user is not listed in the policy.
ErrorPermissionNotAllowedByPolicy	Specifies that the requestor attempted to grant permissions in its calendar or contacts folder to an external user but the sharing policy assigned to the requestor specifies that the requested permission level is higher than what the sharing policy allows.
ErrorOrganizationNotFederated	Specifies that the requestor's organization is not federated so the requestor cannot create sharing messages to send to an external user or cannot accept sharing messages received

Value	Description
	from an external user. This error code MUST be returned if the requestor's organization is not federated.
ErrorMailboxFailover	Specifies that an attempt to access a mailbox failed because the mailbox is in a failover process.
ErrorInvalidExternalSharingInitiator	Specifies that the sharing invitation sender did not create the sharing invitation metadata. This error code MUST be returned if the sharing invitation sender did not create the sharing invitation metadata.
ErrorMessageTrackingPermanentError	Specifies that the message tracking service cannot track the message.
ErrorMessageTrackingTransientError	Specifies that either the message tracking service is down or busy. This error code specifies a transient error. Clients can retry to connect to the server when this error is received.
ErrorMessageTrackingNoSuchDomain	Specifies that the given domain cannot be found.
ErrorUserWithoutFederatedProxyAddress	Specifies that the requestor's organization has a set of federated domains but the requestor's organization does not have any SMTP proxy addresses with one of the federated domains.
ErrorInvalidOrganizationRelationshipForFreeBusy	Specifies that a caller requested free/busy information for a user in another organization but the organizational relationship does not have free/busy enabled.
ErrorInvalidFederatedOrganizationId	Specifies that the requestor's organization federation objects are not properly configured.
ErrorInvalidExternalSharingSubscriber	Specifies that a sharing message is not intended for the caller.
ErrorInvalidSharingData	Specifies that the sharing metadata is not valid. This can be caused by invalid XML.
ErrorInvalidSharingMessage	Specifies that the sharing message is not valid. This can be caused by a missing property.
ErrorNotSupportedSharingMessage	Specifies that the sharing message is not supported.
ErrorApplyConversationActionFailed	This error MUST be returned if an action cannot be applied to one or more items in the conversation.
ErrorInboxRulesValidationError	This error MUST be returned if any rule does not validate.
ErrorOutlookRuleBlobExists	This error MUST be returned when an attempt to manage Inbox rules occurs after another client has accessed the Inbox rules.
ErrorRulesOverQuota	This error MUST be returned when a user's rule quota has been exceeded.
ErrorNewEventStreamConnectionOpened	This error MUST be returned to the first subscription connection if a second subscription connection is opened.
ErrorMissedNotificationEvents	This error MUST be returned when event notifications are

Value	Description
	missed.

2.2.2.21 t:SensitivityChoicesType Simple Type

The **SensitivityChoicesType** simple type specifies the sensitivity level types that are available for an item.

```
<xs:simpleType name="SensitivityChoicesType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="Confidential"
    />
    <xs:enumeration
      value="Normal"
    />
    <xs:enumeration
      value="Personal"
    />
    <xs:enumeration
      value="Private"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **SensitivityChoicesType** simple type:

Value	Description
Confidential	Specifies the item as confidential.
Normal	Specifies the item as normal.
Personal	Specifies the item as personal.
Private	Specifies the item as private.

2.2.2.22 t:UnindexedFieldURIType Simple Type

The **UnindexedFieldURIType** simple type specifies unindexed properties. [<9>](#)

```
<xs:simpleType name="UnindexedFieldURIType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="folder:FolderId"
    />
    <xs:enumeration
      value="folder:ParentFolderId"
    />
  </xs:restriction>
</xs:simpleType>
```

```

/>
<xs:enumeration
  value="folder:DisplayName"
/>
<xs:enumeration
  value="folder:UnreadCount"
/>
<xs:enumeration
  value="folder:TotalCount"
/>
<xs:enumeration
  value="folder:ChildFolderCount"
/>
<xs:enumeration
  value="folder:FolderClass"
/>
<xs:enumeration
  value="folder:SearchParameters"
/>
<xs:enumeration
  value="folder:ManagedFolderInformation"
/>
<xs:enumeration
  value="folder:PermissionSet"
/>
<xs:enumeration
  value="folder:EffectiveRights"
/>
<xs:enumeration
  value="folder:SharingEffectiveRights"
/>
<xs:enumeration
  value="item:ItemId"
/>
<xs:enumeration
  value="item:ParentFolderId"
/>
<xs:enumeration
  value="item:ItemClass"
/>
<xs:enumeration
  value="item:MimeContent"
/>
<xs:enumeration
  value="item:Attachments"
/>
<xs:enumeration
  value="item:Subject"
/>
<xs:enumeration
  value="item:DateTimeReceived"
/>
<xs:enumeration
  value="item:Size"
/>
<xs:enumeration
  value="item:Categories"
/>
<xs:enumeration

```

```
    value="item:HasAttachments"
  />
<xs:enumeration
  value="item:Importance"
  />
<xs:enumeration
  value="item:InReplyTo"
  />
<xs:enumeration
  value="item:InternetMessageHeaders"
  />
<xs:enumeration
  value="item:IsAssociated"
  />
<xs:enumeration
  value="item:IsDraft"
  />
<xs:enumeration
  value="item:IsFromMe"
  />
<xs:enumeration
  value="item:IsResend"
  />
<xs:enumeration
  value="item:IsSubmitted"
  />
<xs:enumeration
  value="item:IsUnmodified"
  />
<xs:enumeration
  value="item:DateTimeSent"
  />
<xs:enumeration
  value="item:DateTimeCreated"
  />
<xs:enumeration
  value="item:Body"
  />
<xs:enumeration
  value="item:ResponseObjects"
  />
<xs:enumeration
  value="item:Sensitivity"
  />
<xs:enumeration
  value="item:ReminderDueBy"
  />
<xs:enumeration
  value="item:ReminderIsSet"
  />
<xs:enumeration
  value="item:ReminderMinutesBeforeStart"
  />
<xs:enumeration
  value="item:DisplayTo"
  />
<xs:enumeration
  value="item:DisplayCc"
  />
```

```
<xs:enumeration
  value="item:Culture"
/>
<xs:enumeration
  value="item:EffectiveRights"
/>
<xs:enumeration
  value="item:LastModifiedName"
/>
<xs:enumeration
  value="item:LastModifiedTime"
/>
<xs:enumeration
  value="item:ConversationId"
/>
<xs:enumeration
  value="item:UniqueBody"
/>
<xs:enumeration
  value="item:WebClientReadFormQueryString"
/>
<xs:enumeration
  value="item:WebClientEditFormQueryString"
/>
<xs:enumeration
  value="message:ConversationIndex"
/>
<xs:enumeration
  value="message:ConversationTopic"
/>
<xs:enumeration
  value="message:InternetMessageId"
/>
<xs:enumeration
  value="message:IsRead"
/>
<xs:enumeration
  value="message:IsResponseRequested"
/>
<xs:enumeration
  value="message:IsReadReceiptRequested"
/>
<xs:enumeration
  value="message:IsDeliveryReceiptRequested"
/>
<xs:enumeration
  value="message:ReceivedBy"
/>
<xs:enumeration
  value="message:ReceivedRepresenting"
/>
<xs:enumeration
  value="message:References"
/>
<xs:enumeration
  value="message:ReplyTo"
/>
<xs:enumeration
  value="message:From"
```

```

/>
<xs:enumeration
  value="message:Sender"
/>
<xs:enumeration
  value="message:ToRecipients"
/>
<xs:enumeration
  value="message:CcRecipients"
/>
<xs:enumeration
  value="message:BccRecipients"
/>
<xs:enumeration
  value="meeting:AssociatedCalendarItemId"
/>
<xs:enumeration
  value="meeting:IsDelegated"
/>
<xs:enumeration
  value="meeting:IsOutOfDate"
/>
<xs:enumeration
  value="meeting:HasBeenProcessed"
/>
<xs:enumeration
  value="meeting:ResponseType"
/>
<xs:enumeration
  value="meetingRequest:MeetingRequestType"
/>
<xs:enumeration
  value="meetingRequest:IntendedFreeBusyStatus"
/>
<xs:enumeration
  value="calendar:Start"
/>
<xs:enumeration
  value="calendar:End"
/>
<xs:enumeration
  value="calendar:OriginalStart"
/>
<xs:enumeration
  value="calendar:IsAllDayEvent"
/>
<xs:enumeration
  value="calendar:LegacyFreeBusyStatus"
/>
<xs:enumeration
  value="calendar:Location"
/>
<xs:enumeration
  value="calendar:When"
/>
<xs:enumeration
  value="calendar:IsMeeting"
/>
<xs:enumeration

```

```

    value="calendar:IsCancelled"
  />
<xs:enumeration
  value="calendar:IsRecurring"
 />
<xs:enumeration
  value="calendar:MeetingRequestWasSent"
 />
<xs:enumeration
  value="calendar:IsResponseRequested"
 />
<xs:enumeration
  value="calendar:CalendarItemType"
 />
<xs:enumeration
  value="calendar:MyResponseType"
 />
<xs:enumeration
  value="calendar:Organizer"
 />
<xs:enumeration
  value="calendar:RequiredAttendees"
 />
<xs:enumeration
  value="calendar:OptionalAttendees"
 />
<xs:enumeration
  value="calendar:Resources"
 />
<xs:enumeration
  value="calendar:ConflictingMeetingCount"
 />
<xs:enumeration
  value="calendar:AdjacentMeetingCount"
 />
<xs:enumeration
  value="calendar:ConflictingMeetings"
 />
<xs:enumeration
  value="calendar:AdjacentMeetings"
 />
<xs:enumeration
  value="calendar:Duration"
 />
<xs:enumeration
  value="calendar:TimeZone"
 />
<xs:enumeration
  value="calendar:AppointmentReplyTime"
 />
<xs:enumeration
  value="calendar:AppointmentSequenceNumber"
 />
<xs:enumeration
  value="calendar:AppointmentState"
 />
<xs:enumeration
  value="calendar:Recurrence"
 />

```

```

<xs:enumeration
  value="calendar:FirstOccurrence"
/>
<xs:enumeration
  value="calendar>LastOccurrence"
/>
<xs:enumeration
  value="calendar:ModifiedOccurrences"
/>
<xs:enumeration
  value="calendar:DeletedOccurrences"
/>
<xs:enumeration
  value="calendar:MeetingTimeZone"
/>
<xs:enumeration
  value="calendar:ConferenceType"
/>
<xs:enumeration
  value="calendar:AllowNewTimeProposal"
/>
<xs:enumeration
  value="calendar:IsOnlineMeeting"
/>
<xs:enumeration
  value="calendar:MeetingWorkspaceUrl"
/>
<xs:enumeration
  value="calendar:NetShowUrl"
/>
<xs:enumeration
  value="calendar:UID"
/>
<xs:enumeration
  value="calendar:RecurrenceId"
/>
<xs:enumeration
  value="calendar:DateTimeStamp"
/>
<xs:enumeration
  value="calendar:StartTimeZone"
/>
<xs:enumeration
  value="calendar:EndTimeZone"
/>
<xs:enumeration
  value="task:ActualWork"
/>
<xs:enumeration
  value="task:AssignedTime"
/>
<xs:enumeration
  value="task:BillingInformation"
/>
<xs:enumeration
  value="task:ChangeCount"
/>
<xs:enumeration
  value="task:Companies"

```

```
    />
  <xs:enumeration
    value="task:CompleteDate"
  />
  <xs:enumeration
    value="task:Contacts"
  />
  <xs:enumeration
    value="task:DelegationState"
  />
  <xs:enumeration
    value="task:Delegator"
  />
  <xs:enumeration
    value="task:DueDate"
  />
  <xs:enumeration
    value="task:IsAssignmentEditable"
  />
  <xs:enumeration
    value="task:IsComplete"
  />
  <xs:enumeration
    value="task:IsRecurring"
  />
  <xs:enumeration
    value="task:IsTeamTask"
  />
  <xs:enumeration
    value="task:Mileage"
  />
  <xs:enumeration
    value="task:Owner"
  />
  <xs:enumeration
    value="task:PercentComplete"
  />
  <xs:enumeration
    value="task:Recurrence"
  />
  <xs:enumeration
    value="task:StartDate"
  />
  <xs:enumeration
    value="task:Status"
  />
  <xs:enumeration
    value="task:StatusDescription"
  />
  <xs:enumeration
    value="task:TotalWork"
  />
  <xs:enumeration
    value="contacts:AssistantName"
  />
  <xs:enumeration
    value="contacts:Birthday"
  />
  <xs:enumeration
```



```
    value="contacts:BusinessHomePage"
  />
<xs:enumeration
  value="contacts:Children"
 />
<xs:enumeration
  value="contacts:Companies"
 />
<xs:enumeration
  value="contacts:CompanyName"
 />
<xs:enumeration
  value="contacts:CompleteName"
 />
<xs:enumeration
  value="contacts>ContactSource"
 />
<xs:enumeration
  value="contacts:Culture"
 />
<xs:enumeration
  value="contacts:Department"
 />
<xs:enumeration
  value="contacts:DisplayName"
 />
<xs:enumeration
  value="contacts:EmailAddresses"
 />
<xs:enumeration
  value="contacts:FileAs"
 />
<xs:enumeration
  value="contacts:FileAsMapping"
 />
<xs:enumeration
  value="contacts:Generation"
 />
<xs:enumeration
  value="contacts:GivenName"
 />
<xs:enumeration
  value="contacts:ImAddresses"
 />
<xs:enumeration
  value="contacts:Initials"
 />
<xs:enumeration
  value="contacts:JobTitle"
 />
<xs:enumeration
  value="contacts:Manager"
 />
<xs:enumeration
  value="contacts:MiddleName"
 />
<xs:enumeration
  value="contacts:Mileage"
 />
```

```
<xs:enumeration
  value="contacts:Nickname"
/>
<xs:enumeration
  value="contacts:OfficeLocation"
/>
<xs:enumeration
  value="contacts:PhoneNumbers"
/>
<xs:enumeration
  value="contacts:PhysicalAddresses"
/>
<xs:enumeration
  value="contacts:PostalAddressIndex"
/>
<xs:enumeration
  value="contacts:Profession"
/>
<xs:enumeration
  value="contacts:SpouseName"
/>
<xs:enumeration
  value="contacts:Surname"
/>
<xs:enumeration
  value="contacts:WeddingAnniversary"
/>
<xs:enumeration
  value="contacts:HasPicture"
/>
<xs:enumeration
  value="distributionlist:Members"
/>
<xs:enumeration
  value="postitem:PostedTime"
/>
<xs:enumeration
  value="conversation:ConversationId"
/>
<xs:enumeration
  value="conversation:ConversationTopic"
/>
<xs:enumeration
  value="conversation:UniqueRecipients"
/>
<xs:enumeration
  value="conversation:GlobalUniqueRecipients"
/>
<xs:enumeration
  value="conversation:UniqueUnreadSenders"
/>
<xs:enumeration
  value="conversation:GlobalUniqueUnreadSenders"
/>
<xs:enumeration
  value="conversation:UniqueSenders"
/>
<xs:enumeration
  value="conversation:GlobalUniqueSenders"
```

```
</>
<xs:enumeration
  value="conversation:LastDeliveryTime"
/>
<xs:enumeration
  value="conversation:GlobalLastDeliveryTime"
/>
<xs:enumeration
  value="conversation:Categories"
/>
<xs:enumeration
  value="conversation:GlobalCategories"
/>
<xs:enumeration
  value="conversation:FlagStatus"
/>
<xs:enumeration
  value="conversation:GlobalFlagStatus"
/>
<xs:enumeration
  value="conversation:HasAttachments"
/>
<xs:enumeration
  value="conversation:GlobalHasAttachments"
/>
<xs:enumeration
  value="conversation:MessageCount"
/>
<xs:enumeration
  value="conversation:GlobalMessageCount"
/>
<xs:enumeration
  value="conversation:UnreadCount"
/>
<xs:enumeration
  value="conversation:GlobalUnreadCount"
/>
<xs:enumeration
  value="conversation:Size"
/>
<xs:enumeration
  value="conversation:GlobalSize"
/>
<xs:enumeration
  value="conversation:ItemClasses"
/>
<xs:enumeration
  value="conversation:GlobalItemClasses"
/>
<xs:enumeration
  value="conversation:Importance"
/>
<xs:enumeration
  value="conversation:GlobalImportance"
/>
<xs:enumeration
  value="conversation:ItemIds"
/>
<xs:enumeration
```

```

        value="conversation:GlobalItemIds"
    />
</xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **UnindexedFieldURIType** simple type:

Value	Description
folder:FolderId	Specifies the FolderId property.
folder:ParentFolderId	Specifies the ParentFolderId property.
folder:DisplayName	Specifies the DisplayName property.
folder:UnreadCount	Specifies the UnreadCount property.
folder:TotalCount	Specifies the TotalCount property.
folder:ChildFolderCount	Specifies the ChildFolderCount property.
folder:FolderClass	Specifies the FolderClass property.
folder:SearchParameters	Specifies the SearchParameters property.
folder:ManagedFolderInformation	Specifies the ManagedFolderInformation property.
folder:PermissionSet	Specifies the PermissionSet property.
folder:EffectiveRights	Specifies the EffectiveRights property.
folder:SharingEffectiveRights	Specifies the SharingEffectiveRights property.
item:ItemId	Specifies the ItemId property.
item:ParentFolderId	Specifies the ParentFolderId property.
item:ItemClass	Specifies the ItemClass property.
item:MimeContent	Specifies the MimeContent property.
item:Attachments	Specifies the Attachments property.
item:Subject	Specifies the Subject property.
item:DateTimeReceived	Specifies the DateTimeReceived property.
item:Size	Specifies the Size property.
item:Categories	Specifies the Categories property.
item:HasAttachments	Specifies the HasAttachments property.
item:Importance	Specifies the Importance property.
item:InReplyTo	Specifies the InReplyTo property.

Value	Description
item:InternetMessageHeaders	Specifies the InternetMessageHeaders property.
item:IsAssociated	Specifies the IsAssociated property.
item:IsDraft	Specifies the IsDraft property.
item:IsFromMe	Specifies the IsFromMe property.
item:IsResend	Specifies the IsResend property.
item:IsSubmitted	Specifies the IsSubmitted property.
item:IsUnmodified	Specifies the IsUnmodified property.
item:DateTimeSent	Specifies the DateTimeSent property.
item:DateTimeCreated	Specifies the DateTimeCreated property.
item:Body	Specifies the Body property.
item:ResponseObjects	Specifies the ResponseObjects property.
item:Sensitivity	Specifies the Sensitivity property.
item:ReminderDueBy	Specifies the ReminderDueBy property.
item:ReminderIsSet	Specifies the ReminderIsSet property.
item:ReminderMinutesBeforeStart	Specifies the ReminderMinutesBeforeStart property.
item:DisplayTo	Specifies the DisplayTo property.
item:DisplayCc	Specifies the DisplayCc property.
item:Culture	Specifies the Culture property.
item:EffectiveRights	Specifies the EffectiveRights property.
item:LastModifiedName	Specifies the LastModifiedName property.
item:LastModifiedTime	Specifies the LastModifiedTime property.
item:ConversationId	Specifies the ConversationId property.
item:UniqueBody	Specifies the UniqueBody property.
item:WebClientReadFormQueryString	Specifies the WebClientReadFormQueryString property.
item:WebClientEditFormQueryString	Specifies the WebClientEditFormQueryString property.
message:ConversationIndex	Specifies the ConversationIndex property. This property is also valid for postitem.
message:ConversationTopic	Specifies the ConversationTopic property. This property is also valid for postitem.
message:InternetMessageId	Specifies the InternetMessageId property. This property is also valid for postitem.

Value	Description
message:IsRead	Specifies the IsRead property.
message:IsResponseRequested	Specifies the IsResponseRequested property.
message:IsReadReceiptRequested	Specifies the IsReadReceiptRequested property.
message:IsDeliveryReceiptRequested	Specifies the IsDeliveryReceiptRequested property.
message:ReceivedBy	Specifies the ReceivedBy property.
message:ReceivedRepresenting	Specifies the ReceivedRepresenting property.
message:References	Specifies the References property. This property is also valid for postitem.
message:ReplyTo	Specifies the ReplyTo property.
message:From	Specifies the From property. This property is also valid for postitem.
message:Sender	Specifies the Sender property. This property is also valid for postitem.
message:ToRecipients	Specifies the ToRecipients property.
message:CcRecipients	Specifies the CcRecipients property.
message:BccRecipients	Specifies the BccRecipients property.
meeting:AssociatedCalendarItemId	Specifies the AssociatedCalendarItemId property.
meeting:IsDelegated	Specifies the IsDelegated property.
meeting:IsOutOfDate	Specifies the IsOutOfDate property.
meeting:HasBeenProcessed	Specifies the HasBeenProcessed property.
meeting:ResponseType	Specifies the ResponseType property.
meetingRequest:MeetingRequestType	Specifies the MeetingRequestType property.
meetingRequest:IntendedFreeBusyStatus	Specifies the IntendedFreeBusyStatus property.
calendar:Start	Specifies the Start property.
calendar:End	Specifies the End property.
calendar:OriginalStart	Specifies the OriginalStart property.
calendar:IsAllDayEvent	Specifies the IsAllDayEvent property.
calendar:LegacyFreeBusyStatus	Specifies the LegacyFreeBusyStatus property.
calendar:Location	Specifies the Location property.
calendar:When	Specifies the When property.
calendar:IsMeeting	Specifies the IsMeeting property.

Value	Description
calendar:IsCancelled	Specifies the IsCancelled property.
calendar:IsRecurring	Specifies the IsRecurring property.
calendar:MeetingRequestWasSent	Specifies the MeetingRequestWasSent property.
calendar:IsResponseRequested	Specifies the IsResponseRequested property.
calendar:CalendarItemType	Specifies the CalendarItemType property.
calendar:MyResponseType	Specifies the MyResponseType property.
calendar:Organizer	Specifies the Organizer property.
calendar:RequiredAttendees	Specifies the RequiredAttendees property.
calendar:OptionalAttendees	Specifies the OptionalAttendees property.
calendar:Resources	Specifies the Resources property.
calendar:ConflictingMeetingCount	Specifies the ConflictingMeetingCount property.
calendar:AdjacentMeetingCount	Specifies the AdjacentMeetingCount property.
calendar:ConflictingMeetings	Specifies the ConflictingMeetings property.
calendar:AdjacentMeetings	Specifies the AdjacentMeetings property.
calendar:Duration	Specifies the Duration property.
calendar:TimeZone	Specifies the TimeZone property.
calendar:AppointmentReplyTime	Specifies the AppointmentReplyTime property.
calendar:AppointmentSequenceNumber	Specifies the AppointmentSequenceNumber property.
calendar:AppointmentState	Specifies the AppointmentState property.
calendar:Recurrence	Specifies the Recurrence property.
calendar:FirstOccurrence	Specifies the FirstOccurrence property.
calendar>LastOccurrence	Specifies the LastOccurrence property.
calendar:ModifiedOccurrences	Specifies the ModifiedOccurrences property.
calendar:DeletedOccurrences	Specifies the DeletedOccurrences property.
calendar:MeetingTimeZone	Specifies the MeetingTimeZone property.
calendar:ConferenceType	Specifies the ConferenceType property.
calendar:AllowNewTimeProposal	Specifies the AllowNewTimeProposal property.
calendar:IsOnlineMeeting	Specifies the IsOnlineMeeting property.
calendar:MeetingWorkspaceUrl	Specifies the MeetingWorkspaceUrl property.
calendar:NetShowUrl	Specifies the NetShowUrl property.

Value	Description
calendar:UID	Specifies the UID property.
calendar:RecurrenceId	Specifies the RecurrenceId property.
calendar:DateTimeStamp	Specifies the DateTimeStamp property.
calendar:StartTimeZone	Specifies the StartTimeZone property.
calendar:EndTimeZone	Specifies the EndTimeZone property.
task:ActualWork	Specifies the ActualWork property.
task:AssignedTime	Specifies the AssignedTime property.
task:BillingInformation	Specifies the BillingInformation property.
task:ChangeCount	Specifies the ChangeCount property.
task:Companies	Specifies the Companies property.
task:CompleteDate	Specifies the CompleteDate property.
task:Contacts	Specifies the Contacts property.
task:DelegationState	Specifies the DelegationState property.
task:Delegator	Specifies the Delegator property.
task:DueDate	Specifies the DueDate property.
task:IsAssignmentEditable	Specifies the IsAssignmentEditable property.
task:IsComplete	Specifies the IsComplete property.
task:IsRecurring	Specifies the IsRecurring property.
task:IsTeamTask	Specifies the IsTeamTask property.
task:Mileage	Specifies the Mileage property.
task:Owner	Specifies the Owner property.
task:PercentComplete	Specifies the PercentComplete property.
task:Recurrence	Specifies the Recurrence property.
task:StartDate	Specifies the StartDate property.
task:Status	Specifies the Status property.
task:StatusDescription	Specifies the StatusDescription property.
task:TotalWork	Specifies the TotalWork property.
contacts:AssistantName	Specifies the AssistantName property.
contacts:Birthday	Specifies the Birthday property.
contacts:BusinessHomePage	Specifies the BusinessHomePage property.

Value	Description
contacts:Children	Specifies the Children property.
contacts:Companies	Specifies the Companies property.
contacts:CompanyName	Specifies the CompanyName property.
contacts:CompleteName	Specifies the CompleteName property.
contacts>ContactSource	Specifies the ContactSource property.
contacts:Culture	Specifies the Culture property.
contacts:Department	Specifies the Department property.
contacts:DisplayName	Specifies the DisplayName property.
contacts:EmailAddresses	Specifies the EmailAddresses property.
contacts:FileAs	Specifies the FileAs property.
contacts:FileAsMapping	Specifies the FileAsMapping property.
contacts:Generation	Specifies the Generation property.
contacts:GivenName	Specifies the GivenName property.
contacts:ImAddresses	Specifies the ImAddresses property.
contacts:Initials	Specifies the Initials property.
contacts:JobTitle	Specifies the JobTitle property.
contacts:Manager	Specifies the Manager property.
contacts:MiddleName	Specifies the MiddleName property.
contacts:Mileage	Specifies the Mileage property.
contacts:Nickname	Specifies the Nickname property.
contacts:OfficeLocation	Specifies the OfficeLocation property.
contacts:PhoneNumbers	Specifies the PhoneNumbers property.
contacts:PhysicalAddresses	Specifies the PhysicalAddresses property.
contacts:PostalAddressIndex	Specifies the PostalAddressIndex property.
contacts:Profession	Specifies the Profession property.
contacts:SpouseName	Specifies the SpouseName property.
contacts:Surname	Specifies the Surname property.
contacts:WeddingAnniversary	Specifies the WeddingAnniversary property.
contacts:HasPicture	Specifies whether a contact has a picture.
distributionlist:Members	Specifies the Members property.

Value	Description
postitem:PostedTime	Specifies the PostedTime property.
conversation:ConversationId	Specifies the ConversationId property.
conversation:ConversationTopic	Specifies the ConversationTopic property.
conversation:UniqueRecipients	Specifies the UniqueRecipients property.
conversation:GlobalUniqueRecipients	Specifies the GlobalUniqueRecipients property.
conversation:UniqueUnreadSenders	Specifies the UniqueUnreadSenders property.
conversation:GlobalUniqueUnreadSenders	Specifies the GlobalUniqueUnreadSenders property.
conversation:UniqueSenders	Specifies the UniqueSenders property.
conversation:GlobalUniqueSenders	Specifies the GlobalUniqueSenders property.
conversation:LastDeliveryTime	Specifies the LastDeliveryTime property.
conversation:GlobalLastDeliveryTime	Specifies the GlobalLastDeliveryTime property.
conversation:Categories	Specifies the Categories property.
conversation:GlobalCategories	Specifies the GlobalCategories property.
conversation:FlagStatus	Specifies the FlagStatus property.
conversation:GlobalFlagStatus	Specifies the GlobalFlagStatus property.
conversation:HasAttachments	Specifies the HasAttachments property.
conversation:GlobalHasAttachments	Specifies the GlobalHasAttachments property.
conversation:MessageCount	Specifies the MessageCount property.
conversation:GlobalMessageCount	Specifies the GlobalMessageCount property.
conversation:UnreadCount	Specifies the UnreadCount property.
conversation:GlobalUnreadCount	Specifies the GlobalUnreadCount property.
conversation:Size	Specifies the Size property.
conversation:GlobalSize	Specifies the GlobalSize property.
conversation:ItemClasses	Specifies the ItemClasses property.
conversation:GlobalItemClasses	Specifies the GlobalItemClasses property.
conversation:Importance	Specifies the Importance property.
conversation:GlobalImportance	Specifies the GlobalImportance property.
conversation:ItemIds	Specifies the ItemIds property.
conversation:GlobalItemIds	Specifies the GlobalItemIds property.

2.2.3 Complex Types

2.2.3.1 t:AbsoluteMonthlyRecurrencePatternType Complex Type

The **AbsoluteMonthlyRecurrencePatternType** complex type specifies a monthly recurrence pattern.

```
<xs:complexType name="AbsoluteMonthlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:IntervalRecurrencePatternBaseType"
    >
      <xs:sequence>
        <xs:element name="DayOfMonth"
          type="xs:int"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
DayOfMonth	xs:int	Specifies the day of the month on which a recurring item occurs. This property MUST be present.

2.2.3.2 t:AbsoluteYearlyRecurrencePatternType Complex Type

The **AbsoluteYearlyRecurrencePatternType** complex type specifies a yearly recurrence pattern.

```
<xs:complexType name="AbsoluteYearlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrencePatternBaseType"
    >
      <xs:sequence>
        <xs:element name="DayOfMonth"
          type="xs:int"
        />
        <xs:element name="Month"
          type="t:MonthNamesType"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
DayOfMonth	xs:int	Specifies the day of the month on which a yearly recurring item occurs. This property MUST be present.
Month	t:MonthNamesType	Specifies the month in which a yearly recurring item occurs. This property MUST be present.

2.2.3.3 t:AcceptSharingInvitationType Complex Type

The **AcceptSharingInvitationType** complex type specifies a response object that is used to respond to a sharing invitation request.

```
<xs:complexType name="AcceptSharingInvitationType">
  <xs:complexContent>
    <xs:extension
      base="t:ReferenceItemResponseType"
    />
  </xs:complexContent>
</xs:complexType>
```

2.2.3.4 t:ArrayOfCalendarPermissionsType Complex Type

The **ArrayOfCalendarPermissionsType** complex type specifies an array of calendar permissions for a folder.

```
<xs:complexType name="ArrayOfCalendarPermissionsType">
  <xs:choice
    maxOccurs="unbounded"
    minOccurs="0"
  >
    <xs:element name="CalendarPermission"
      type="t:CalendarPermissionType"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
CalendarPermission	t:CalendarPermissionType	Specifies the access that a delegate has to a calendar folder. This element MUST exist if calendar permissions are set on a calendar folder.

2.2.3.5 t:ArrayOfEmailAddressesType Complex Type

The **ArrayOfEmailAddressesType** complex type specifies a list of e-mail addresses in the **GetRoomLists** operation ([\[MS-OXWSGTRM\]](#) section 3.1.4.1) and **GetMessageTrackingReport** operation ([\[MS-OXWSMTRK\]](#) section 3.1.4.2) responses.

```

<xs:complexType name="ArrayOfEmailAddressesType">
  <xs:sequence>
    <xs:element name="Address"
      type="t:EmailAddressType"
      maxOccurs="unbounded"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
Address	t:EmailAddressType	Specifies a single e-mail address.

2.2.3.6 t:ArrayOfPermissionsType Complex Type

The **ArrayOfPermissionsType** complex type specifies a collection of permissions for a folder.

```

<xs:complexType name="ArrayOfPermissionsType">
  <xs:choice
    minOccurs="0"
    maxOccurs="unbounded"
  >
    <xs:element name="Permission"
      type="t:PermissionType"
    />
  </xs:choice>
</xs:complexType>

```

Child Elements

Element	Type	Description
Permission	t:PermissionType	Specifies a single access permission that a delegate has to a folder. This element can occur zero or more times.

2.2.3.7 t:ArrayOfRealItemsType Complex Type

The **ArrayOfRealItemsType** complex type specifies an array of items that are returned by search and item operations. This complex type can contain zero or more elements that represent items.

```

<xs:complexType name="ArrayOfRealItemsType">
  <xs:sequence>
    <xs:choice
      minOccurs="0"
      maxOccurs="unbounded"
    >
      <xs:element name="Item"
        type="t:ItemType"
      />
    </xs:choice>
  </xs:sequence>
</xs:complexType>

```

```

<xs:element name="Message"
  type="t:MessageType"
/>
<xs:element name="CalendarItem"
  type="t:CalendarItemType"
/>
<xs:element name="Contact"
  type="t:ContactItemType"
/>
<xs:element name="DistributionList"
  type="t:DistributionListType"
/>
<xs:element name="MeetingMessage"
  type="t:MeetingMessageType"
/>
<xs:element name="MeetingRequest"
  type="t:MeetingRequestMessageType"
/>
<xs:element name="MeetingResponse"
  type="t:MeetingResponseMessageType"
/>
<xs:element name="MeetingCancellation"
  type="t:MeetingCancellationMessageType"
/>
<xs:element name="Task"
  type="t:TaskType"
/>
<xs:element name="PostItem"
  type="t:PostItemType"
/>
</xs:choice>
</xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
Item	t:ItemType	This element MUST NOT be used in response messages. All items of type t:ItemType ([MS-OXWSCORE]) MUST be returned as a t:MessageType type ([MS-OXWSMSG]).
Message	t:MessageType	Specifies a message item or other item that is not represented by the CalendarItem , Contact , DistributionList , MeetingMessage , MeetingRequest , MeetingResponse , MeetingCancellation , Task , or PostItem element.
CalendarItem	t:CalendarItemType	Specifies a calendar item.
Contact	t:ContactItemType	Specifies a contact item.
DistributionList	t:DistributionListType	Specifies a distribution list item.

Element	Type	Description
MeetingMessage	t:MeetingMessageType	Specifies a meeting message item.
MeetingRequest	t:MeetingRequestMessageType	Specifies a meeting request message item.
MeetingResponse	t:MeetingResponseMessageType	Specifies a meeting response message item.
MeetingCancellation	t:MeetingCancellationMessageType	Specifies a meeting cancellation message item.
Task	t:TaskType	Specifies a task item.
PostItem	t:PostItemType	Specifies a post item.

2.2.3.8 t:ArrayOfRecipientsType Complex Type

The **ArrayOfRecipientsType** complex type specifies an array of recipients of an item.

```
<xs:complexType name="ArrayOfRecipientsType">
  <xs:choice
    maxOccurs="unbounded"
    minOccurs="0"
  >
    <xs:element name="Mailbox"
      type="t:EmailAddressType"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
Mailbox	t:EmailAddressType	Specifies a single item recipient by e-mail address.

2.2.3.9 m:ArrayOfResponseMessagesType Complex Type

The **ArrayOfResponseMessagesType** complex type specifies an array of response messages.

```
<xs:complexType name="ArrayOfResponseMessagesType">
  <xs:choice
    maxOccurs="unbounded"
  >
    <xs:element name="CreateItemResponseMessage"
      type="m:ItemInfoResponseMessageType"
    />
    <xs:element name="DeleteItemResponseMessage"
      type="m:ResponseMessageType"
    />
    <xs:element name="GetItemResponseMessage"
      type="m:ItemInfoResponseMessageType"
    />
    <xs:element name="UpdateItemResponseMessage"

```

```

    type="m:UpdateItemResponseType"
  />
<xs:element name="SendItemResponseMessage"
  type="m:ResponseType"
  />
<xs:element name="DeleteFolderResponseMessage"
  type="m:ResponseType"
  />
<xs:element name="EmptyFolderResponseMessage"
  type="m:ResponseType"
  />
<xs:element name="CreateFolderResponseMessage"
  type="m:FolderInfoResponseType"
  />
<xs:element name="GetFolderResponseMessage"
  type="m:FolderInfoResponseType"
  />
<xs:element name="FindFolderResponseMessage"
  type="m:FindFolderResponseType"
  />
<xs:element name="UpdateFolderResponseMessage"
  type="m:FolderInfoResponseType"
  />
<xs:element name="MoveFolderResponseMessage"
  type="m:FolderInfoResponseType"
  />
<xs:element name="CopyFolderResponseMessage"
  type="m:FolderInfoResponseType"
  />
<xs:element name="CreateAttachmentResponseMessage"
  type="m:AttachmentInfoResponseType"
  />
<xs:element name="DeleteAttachmentResponseMessage"
  type="m>DeleteAttachmentResponseType"
  />
<xs:element name="GetAttachmentResponseMessage"
  type="m:AttachmentInfoResponseType"
  />
<xs:element name="UploadItemsResponseMessage"
  type="m:UploadItemsResponseType"
  />
<xs:element name="ExportItemsResponseMessage"
  type="m:ExportItemsResponseType"
  />
<xs:element name="FindItemResponseMessage"
  type="m:FindItemResponseType"
  />
<xs:element name="MoveItemResponseMessage"
  type="m:ItemInfoResponseType"
  />
<xs:element name="CopyItemResponseMessage"
  type="m:ItemInfoResponseType"
  />
<xs:element name="ResolveNamesResponseMessage"
  type="m:ResolveNamesResponseType"
  />
<xs:element name="ExpandDLResponseMessage"
  type="m:ExpandDLResponseType"
  />

```



```

<xs:element name="GetServerTimeZonesResponseMessage"
  type="m:GetServerTimeZonesResponseMessageType"
  />
<xs:element name="GetEventsResponseMessage"
  type="m:GetEventsResponseMessageType"
  />
<xs:element name="GetStreamingEventsResponseMessage"
  type="m:GetStreamingEventsResponseMessageType"
  />
<xs:element name="SubscribeResponseMessage"
  type="m:SubscribeResponseMessageType"
  />
<xs:element name="UnsubscribeResponseMessage"
  type="m:ResponseMessageType"
  />
<xs:element name="SendNotificationResponseMessage"
  type="m:SendNotificationResponseMessageType"
  />
<xs:element name="SyncFolderHierarchyResponseMessage"
  type="m:SyncFolderHierarchyResponseMessageType"
  />
<xs:element name="SyncFolderItemsResponseMessage"
  type="m:SyncFolderItemsResponseMessageType"
  />
<xs:element name="CreateManagedFolderResponseMessage"
  type="m:FolderInfoResponseMessageType"
  />
<xs:element name="ConvertIdResponseMessage"
  type="m:ConvertIdResponseMessageType"
  />
<xs:element name="GetSharingMetadataResponseMessage"
  type="m:GetSharingMetadataResponseMessageType"
  />
<xs:element name="RefreshSharingFolderResponseMessage"
  type="m:RefreshSharingFolderResponseMessageType"
  />
<xs:element name="GetSharingFolderResponseMessage"
  type="m:GetSharingFolderResponseMessageType"
  />
<xs:element name="CreateUserConfigurationResponseMessage"
  type="m:ResponseMessageType"
  />
<xs:element name="DeleteUserConfigurationResponseMessage"
  type="m:ResponseMessageType"
  />
<xs:element name="GetUserConfigurationResponseMessage"
  type="m:GetUserConfigurationResponseMessageType"
  />
<xs:element name="UpdateUserConfigurationResponseMessage"
  type="m:ResponseMessageType"
  />
<xs:element name="GetRoomListsResponse"
  type="m:GetRoomListsResponseMessageType"
  />
<xs:element name="GetRoomsResponse"
  type="m:GetRoomsResponseMessageType"
  />
<xs:element name="ApplyConversationActionResponseMessage"
  type="m:ResponseMessageType"

```

```

    />
  </xs:choice>
</xs:complexType>

```

Child Elements

Element	Type	Description
CreateItemResponseMessage	m:ItemInfoResponseMessageType	Specifies the response message for the CreateItem operation ([MS-OXWSCORE] section 3.1.4.2).
DeleteItemResponseMessage	m:ResponseMessageType	Specifies the response message for the DeleteItem operation ([MS-OXWSCORE] section 3.1.4.3).
GetItemResponseMessage	m:ItemInfoResponseMessageType	Specifies the response message for the GetItem operation ([MS-OXWSCORE] section 3.1.4.4).
UpdateItemResponseMessage	m:UpdateItemResponseMessageType	Specifies the response message for the UpdateItem operation ([MS-OXWSCORE] section 3.1.4.7).
SendItemResponseMessage	m:ResponseMessageType	Specifies the response message for the SendItem operation ([MS-OXWSCORE] section 3.1.4.6).
DeleteFolderResponseMessage	m:ResponseMessageType	Specifies the response message for the DeleteFolder operation ([MS-OXWSFOLD] section 3.1.4.4).
EmptyFolderResponseMessage	m:ResponseMessageType	Specifies the response message for the EmptyFolder operation. <10>
CreateFolderResponseMessage	m:FolderInfoResponseMessageType	Specifies the response message for the CreateFolder operation ([MS-OXWSFOLD] section 3.1.4.2).

Element	Type	Description
GetFolderResponseMessage	m:FolderInfoResponseType	Specifies the response message for the GetFolder operation ([MS-OXWSFOLD] section 3.1.4.6).
FindFolderResponseMessage	m:FindFolderResponseType	Specifies the response message for the FindFolder operation ([MS-OXWSSRCH] section 3.1.4.1).
UpdateFolderResponseMessage	m:FolderInfoResponseType	Specifies the response message for the UpdateFolder operation ([MS-OXWSFOLD] section 3.1.4.8).
MoveFolderResponseMessage	m:FolderInfoResponseType	Specifies the response message for the MoveFolder operation ([MS-OXWSFOLD] section 3.1.4.7).
CopyFolderResponseMessage	m:FolderInfoResponseType	Specifies the response message for the CopyFolder operation ([MS-OXWSFOLD] section 3.1.4.1).
CreateAttachmentResponseMessage	m:AttachmentInfoResponseType	Specifies the response message for the CreateAttachment operation ([MS-OXWSATT] section 3.1.4.1).
DeleteAttachmentResponseMessage	m>DeleteAttachmentResponseType	Specifies the response message for the DeleteAttachment operation ([MS-OXWSATT] section 3.1.4.2).
GetAttachmentResponseMessage	m:AttachmentInfoResponseType	Specifies the response message for the GetAttachment operation ([MS-OXWSATT] section 3.1.4.3).
UploadItemsResponseMessage	m:UploadItemsResponseType	Specifies the response message for the UploadItems operation ([MS-OXWSBTRF] section 3.1.4.2).<11>

Element	Type	Description
ExportItemsResponseMessage	m:ExportItemsResponseMessageType	Specifies the response message for the ExportItems operation ([MS-OXWSBTRF] section 3.1.4.1).<12>
FindItemResponseMessage	m:FindItemResponseMessageType	Specifies the response message for the FindItem operation ([MS-OXWSSRCH] section 3.1.4.2).
MoveItemResponseMessage	m:ItemInfoResponseMessageType	Specifies the response message for the MoveItem operation ([MS-OXWSCORE] section 3.1.4.5).
CopyItemResponseMessage	m:ItemInfoResponseMessageType	Specifies the response message for the CopyItem operation ([MS-OXWSCORE] section 3.1.4.1).
ResolveNamesResponseMessage	m:ResolveNamesResponseMessageType	Specifies the response message for the ResolveNames operation ([MS-OXWSRSLNM] section 3.1.4.1).
ExpandDLResponseMessage	m:ExpandDLResponseMessageType	Specifies the response message for the ExpandDL operation ([MS-OXWSDLIST] section 3.1.4.1).
GetServerTimeZonesResponseMessage	m:GetServerTimeZonesResponseMessageType	Specifies the response message for the GetServerTimeZones operation ([MS-OXWSGTZ] section 3.1.4.1).
GetEventsResponseMessage	m:GetEventsResponseMessageType	Specifies the response message for the GetEvents operation ([MS-OXWSNTIF] section 3.1.4.1).
GetStreamingEventsResponseMessage	m:GetStreamingEventsResponseMessageType	Specifies the response message for the GetStreamingEvents operation ([MS-OXWSNTIF] section 3.1.4.2).<13>
SubscribeResponseMessage	m:SubscribeResponseMessageType	Specifies the response

Element	Type	Description
		message for the Subscribe operation ([MS-OXWSNTIF] section 3.1.4.3).
UnsubscribeResponseMessage	m:ResponseMessageType	Specifies the response message for the Unsubscribe operation ([MS-OXWSNTIF] section 3.1.4.4).
SendNotificationResponseMessage	m:SendNotificationResponseMessageType	Specifies the response message for the SendNotification operation ([MS-OXWSPSNTIF] section 3.1.4.1).
SyncFolderHierarchyResponseMessage	m:SyncFolderHierarchyResponseMessageType	Specifies the response message for the SyncFolderHierarchy operation ([MS-OXWSSYNC] section 3.1.4.1).
SyncFolderItemsResponseMessage	m:SyncFolderItemsResponseMessageType	Specifies the response message for the SyncFolderItems operation ([MS-OXWSSYNC] section 3.1.4.2).
CreateManagedFolderResponseMessage	m:FolderInfoResponseMessageType	Specifies the response message for the CreateManagedFolder operation ([MS-OXWSFOLD] section 3.1.4.3).
ConvertIdResponseMessage	m:ConvertIdResponseMessageType	Specifies the response message for the ConvertId operation ([MS-OXWSCVTID] section 3.1.4.1).
GetSharingMetadataResponseMessage	m:GetSharingMetadataResponseMessageType	Specifies the response message for the GetSharingMetadata operation ([MS-OXWSMSHR] section 3.1.4.4).
RefreshSharingFolderResponseMessage	m:RefreshSharingFolderResponseMessageType	Specifies the response message for the RefreshSharingFolder operation ([MS-OXWSMSHR] section 3.1.4.5).

Element	Type	Description
GetSharingFolderResponseMessage	m:GetSharingFolderResponseType	Specifies the response message for the GetSharingFolder operation ([MS-OXWSMSHR] section 3.1.4.3).
CreateUserConfigurationResponseMessage	m:ResponseType	Specifies the response message for the CreateUserConfiguration operation ([MS-OXWSUSRCFG] section 3.1.4.1).
DeleteUserConfigurationResponseMessage	m:ResponseType	Specifies the response message for the DeleteUserConfiguration operation ([MS-OXWSUSRCFG] section 3.1.4.2).
GetUserConfigurationResponseMessage	m:GetUserConfigurationResponseType	Specifies the response message for the GetUserConfiguration operation ([MS-OXWSUSRCFG] section 3.1.4.3).
UpdateUserConfigurationResponseMessage	m:ResponseType	Specifies the response message for the UpdateUserConfiguration operation ([MS-OXWSUSRCFG] section 3.1.4.4).
GetRoomListsResponse	m:GetRoomListsResponseType	Specifies the response message for the GetRoomLists operation ([MS-OXWSGTRM] section 3.1.4.1).
GetRoomsResponse	m:GetRoomsResponseType	Specifies the response message for the GetRooms operation ([MS-OXWSGTRM] section 3.1.4.2).
ApplyConversationActionResponseMessage	m:ResponseType	Specifies the response message for the ApplyConversationAction operation ([MS-OXWSCONV] section 3.1.4.2). <14>

2.2.3.10 t:ArrayOfStringsType Complex Type

The **ArrayOfStringsType** complex type specifies a data structure that can contain zero or more strings.

```
<xs:complexType name="ArrayOfStringsType">
  <xs:sequence>
    <xs:element name="String"
      type="xs:string"
      minOccurs="0"
      maxOccurs="unbounded"
    />
  </xs:sequence>
</xs:complexType>
```

Child Elements

Element	Type	Description
String	xs:string	Specifies a single string of data.

2.2.3.11 t:BaseEmailAddressType Complex Type

The **BaseEmailAddressType** complex type specifies the base type for the **t:EmailAddressType** type (section [2.2.3.25](#)).

```
<xs:complexType name="BaseEmailAddressType" />
```

2.2.3.12 t:BaseItemIdType Complex Type

The **BaseItemIdType** complex type specifies the base type for identifiers that represent items in a mailbox. The **BaseItemIdType** type MUST NOT be sent in a SOAP message because it is an abstract type.

```
<xs:complexType name="BaseItemIdType"
  abstract="true"
/>
```

2.2.3.13 t:BasePathToElementType Complex Type

The **BasePathToElementType** complex type specifies the base type to types that specify additional properties. The **BasePathToElementType** type MUST NOT be sent in a SOAP message because it is an abstract type.

```
<xs:complexType name="BasePathToElementType"
  abstract="true"
/>
```

2.2.3.14 m:BaseRequestType Complex Type

The **BaseRequestType** complex type specifies the base type for requests. The **BaseRequestType** type MUST NOT be sent in a SOAP message because it is an abstract type.

```
<xs:complexType name="BaseRequestType"
  abstract="true"
/>
```

2.2.3.15 m:BaseResponseMessageType Complex Type

The **BaseResponseMessageType** complex type specifies the base response message for responses. The **BaseResponseMessageType** complex type MUST NOT be sent in a SOAP message because it is an abstract type.

```
<xs:complexType name="BaseResponseMessageType">
  <xs:sequence>
    <xs:element name="ResponseMessages"
      type="m:ArrayOfResponseMessagesType"
    />
  </xs:sequence>
</xs:complexType>
```

Child Elements

Element	Type	Description
ResponseMessages	m:ArrayOfResponseMessagesType	Specifies an array of response messages. There MUST be only one ResponseMessages element in a response.

2.2.3.16 t:BodyType Complex Type

The **BodyType** complex type specifies the body content and body content format of an item.

```
<xs:complexType name="BodyType">
  <xs:simpleContent>
    <xs:extension
      base="xs:string"
    >
      <xs:attribute name="BodyType"
        type="t:BodyTypeType"
      />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```

Attributes

Name	Type	Description
BodyType	t:BodyTypeType	Specifies the body content and format of an item.

2.2.3.17 t:ConnectingSIDType Complex Type

The **ConnectingSIDType** complex type specifies the account to use for impersonation.

```
<xs:complexType name="ConnectingSIDType">
  <xs:choice>
    <xs:element name="PrincipalName"
      type="t:NonEmptyStringType"
    />
    <xs:element name="SID"
      type="t:NonEmptyStringType"
    />
    <xs:element name="PrimarySmtpAddress"
      type="t:NonEmptyStringType"
    />
    <xs:element name="SmtpAddress"
      type="t:NonEmptyStringType"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
PrincipalName	t:NonEmptyStringType	Specifies the user principal name (UPN) for the account to use for impersonation.
SID	t:NonEmptyStringType	Specifies the security descriptor definition language (SDDL) form of the security identifier (SID) for the account to be used for impersonation.
PrimarySmtpAddress	t:NonEmptyStringType	Specifies the primary SMTP address of the account to be used for impersonation.
SmtpAddress	t:NonEmptyStringType	Specifies an SMTP address of the account to be used for impersonation.

Only one of the elements specified in the **ConnectingSIDType** complex type MUST exist in an impersonation request.

2.2.3.18 t:ConstantValueType Complex Type

The **ConstantValueType** complex type specifies a constant value for a search restriction.

```
<xs:complexType name="ConstantValueType">
  <xs:attribute name="Value"
    type="xs:string"
    use="required"
  />
</xs:complexType>
```

Attributes

Name	Type	Description
Value	xs:string	Specifies the value to be compared in a restriction.

2.2.3.19 t:DailyRecurrencePatternType Complex Type

The **DailyRecurrencePatternType** complex type specifies the interval, in days, at which a calendar item or a task recurs.

```
<xs:complexType name="DailyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:IntervalRecurrencePatternBaseType"
    />
  </xs:complexContent>
</xs:complexType>
```

2.2.3.20 t:DeletedOccurrenceInfoType Complex Type

The **DeletedOccurrenceInfoType** complex type specifies a deleted occurrence of a recurring calendar item.

```
<xs:complexType name="DeletedOccurrenceInfoType">
  <xs:sequence>
    <xs:element name="Start"
      type="xs:dateTime"
    />
  </xs:sequence>
</xs:complexType>
```

Child Elements

Element	Type	Description
Start	xs:dateTime	Specifies the start time of a deleted occurrence of a recurring calendar item.

2.2.3.21 t:DistinguishedFolderIdType Complex Type

The **DistinguishedFolderIdType** complex type specifies a distinguished folder identified by name.

```
<xs:complexType name="DistinguishedFolderIdType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseFolderIdType"
    >
    <xs:sequence>
```

```

    <xs:element name="Mailbox"
      type="t:EmailAddressType"
      minOccurs="0"
    />
  </xs:sequence>
  <xs:attribute name="Id"
    type="t:DistinguishedFolderIdNameType"
    use="required"
  />
  <xs:attribute name="ChangeKey"
    type="xs:string"
    use="optional"
  />
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
Mailbox	t:EmailAddressType	Specifies the primary SMTP address of a principal for a delegate access scenario. This element MUST exist to initiate delegate access.

Attributes

Name	Type	Description
Id	t:DistinguishedFolderIdNameType	Specifies the identifier of a distinguished folder. This attribute MUST exist.
ChangeKey	xs:string	Specifies the change key of a distinguished folder.

2.2.3.22 t:Duration Complex Type

The **Duration** complex type specifies a time interval.

```

<xs:complexType name="Duration">
  <xs:sequence>
    <xs:element name="StartTime"
      type="xs:dateTime"
      minOccurs="1"
      maxOccurs="1"
    />
    <xs:element name="EndTime"
      type="xs:dateTime"
      minOccurs="1"
      maxOccurs="1"
    />
  </xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
StartTime	xs:dateTime	Specifies the start of a time period. This element MUST be present.
EndTime	xs:dateTime	Specifies the end of a time period. This element MUST be present.

Restriction: The value of the **EndTime** element MUST be greater than the value of the **StartTime** element. Also, the specified times MUST be in **Coordinated Universal Time (UTC)**.

2.2.3.23 t:EffectiveRightsType Complex Type

The **EffectiveRightsType** complex type specifies client rights based on the permission settings for an item or folder.

```
<xs:complexType name="EffectiveRightsType">
  <xs:sequence>
    <xs:element name="CreateAssociated"
      type="xs:boolean"
    />
    <xs:element name="CreateContents"
      type="xs:boolean"
    />
    <xs:element name="CreateHierarchy"
      type="xs:boolean"
    />
    <xs:element name="Delete"
      type="xs:boolean"
    />
    <xs:element name="Modify"
      type="xs:boolean"
    />
    <xs:element name="Read"
      type="xs:boolean"
    />
    <xs:element name="ViewPrivateItems"
      type="xs:boolean"
    />
  </xs:sequence>
</xs:complexType>
```

Child Elements

Element	Type	Description
CreateAssociated	xs:boolean	Specifies whether a client can create an associated contents table. The xs:boolean type is specified in [XMLSCHEMA2] .
CreateContents	xs:boolean	Specifies whether a client can create a contents table.
CreateHierarchy	xs:boolean	Specifies whether a client can create a hierarchy table.
Delete	xs:boolean	Specifies whether a client can delete a folder or item.
Modify	xs:boolean	Specifies whether a client can modify a folder or item.
Read	xs:boolean	Specifies whether a client can read a folder or item.

Element	Type	Description
ViewPrivateItems	xs:boolean	Specifies whether a client can read private items.<15>

2.2.3.24 t:EmailAddress

The **EmailAddress** complex type specifies the name and address of the user.

```
<xs:complexType name="EmailAddress">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="Address" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="RoutingType" type="xs:string" />
  </xs:sequence>
</xs:complexType>
```

Element	Type	Definition
Name	xs:string	Represents the name of the attendee. This element is optional.
Address	xs:string	Represents the e-mail address of the attendee. This element MUST be present and MUST be a Simple Mail Transfer Protocol (SMTP) address.
RoutingType	xs:string	Represents the routing protocol for the e-mail address. This element is optional.

2.2.3.25 t:EmailAddressType Complex Type

The **EmailAddressType** complex type specifies an e-mail address.

```
<xs:complexType name="EmailAddressType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseEmailAddressType"
    >
    <xs:sequence>
      <xs:element name="Name"
        type="xs:string"
        minOccurs="0"
      />
      <xs:element name="EmailAddress"
        type="t:NonEmptyStringType"
        minOccurs="0"
      />
      <xs:element name="RoutingType"
        type="t:NonEmptyStringType"
        minOccurs="0"
      />
      <xs:element name="MailboxType"
        type="t:MailboxTypeType"
        minOccurs="0"
      />
      <xs:element name="ItemId"
```

```

        type="t:ItemIdType"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
Name	xs:string	Specifies the name of the mailbox that is associated with the e-mail address that is specified in the EmailAddress element.
EmailAddress	t:NonEmptyStringType	Specifies an e-mail address.
RoutingType	t:NonEmptyStringType	Specifies the type of routing for the e-mail address that is specified in the EmailAddress element.
MailboxType	t:MailboxTypeType	Specifies the type of mailbox that is represented by the EmailAddressType complex type (section 2.2.3.25).
ItemId	t:ItemIdType	Specifies the item identifier for the e-mail address that is represented by the EmailAddressType complex type (section 2.2.3.25).

2.2.3.26 t:EndDateRecurrenceRangeType Complex Type

The **EndDateRecurrenceRangeType** complex type specifies the start date and end date of an item recurrence pattern.

```

<xs:complexType name="EndDateRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrenceRangeBaseType"
    >
      <xs:sequence>
        <xs:element name="EndDate"
          type="xs:date"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
EndDate	xs:date	Specifies the end date of a recurrence pattern.

2.2.3.27 t:ExchangeImpersonationType Complex Type

The **ExchangeImpersonationType** complex type specifies the user to be impersonated.

```
<xs:complexType name="ExchangeImpersonationType">
  <xs:sequence>
    <xs:element name="ConnectingSID"
      type="t:ConnectingSIDType"
    />
  </xs:sequence>
  <xs:anyAttribute
    namespace="http://schemas.xmlsoap.org/soap/envelope/"
  />
</xs:complexType>
```

Child Elements

Element	Type	Description
ConnectingSID	t:ConnectingSIDType	Specifies the account to be impersonated. This element MUST exist for impersonation.

2.2.3.28 t:FieldURIOrConstantType Complex Type

The **FieldURIOrConstantType** complex type specifies either a property or a constant value to be compared with another property.

```
<xs:complexType name="FieldURIOrConstantType">
  <xs:choice>
    <xs:element
      ref="t:Path"
    />
    <xs:element name="Constant"
      type="t:ConstantValueType"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
t:Path	t:Path	Specifies the property to be used in a two-operand search expression. The t:Path element (section 2.2.4.7) specifies a substitutionGroup attribute, as specified in [XMLSCHEMA0] . An element that is represented by the substitutionGroup attribute of the t:Path element MUST be present.
Constant	t:ConstantValueType	Specifies a constant to be used in a two-operand search expression.

2.2.3.29 t:FolderIdType Complex Type

The **FolderIdType** complex type specifies a folder identifier.

```

<xs:complexType name="FolderIdType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseFolderIdType"
    >
      <xs:attribute name="Id"
        type="xs:string"
        use="required"
      />
      <xs:attribute name="ChangeKey"
        type="xs:string"
        use="optional"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Attributes

Name	Type	Description
Id	xs:string	Specifies a folder identifier.
ChangeKey	xs:string	Specifies a change key.

2.2.3.30 t:FolderResponseShapeType Complex Type

The **FolderResponseShapeType** complex type specifies the properties that are returned in a response in a **SyncFolderHierarchy** operation ([\[MS-OXWSSYNC\]](#) section 3.1.4.1), **GetFolder** operation ([\[MS-OXWSFOLD\]](#) section 3.1.4.6), or **FindFolder** operation ([\[MS-OXWSSRCH\]](#) section 3.1.4.1).

```

<xs:complexType name="FolderResponseShapeType">
  <xs:sequence>
    <xs:element name="BaseShape"
      type="t:DefaultShapeNamesType"
    />
    <xs:element name="AdditionalProperties"
      type="t:NonEmptyArrayOfPathsToElementType"
    />
  </xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
BaseShape	t:DefaultShapeNamesType	Specifies the basic configuration of properties to be returned in a response.
AdditionalProperties	t:NonEmptyArrayOfPathsToElementType	Specifies the identity of additional properties to be

Element	Type	Description
		returned in a response.

2.2.3.31 t:ForwardItemType Complex Type

The **ForwardItemType** complex type specifies a response object for forwarding messages and meeting messages to other recipients.

```
<xs:complexType name="ForwardItemType">
  <xs:complexContent>
    <xs:extension
      base="t:SmartResponseType"
    />
  </xs:complexContent>
</xs:complexType>
```

2.2.3.32 t:InternetHeaderType Complex Type

The **InternetHeaderType** complex type specifies the Internet message header for a specified header within the headers collection.

```
<xs:complexType name="InternetHeaderType">
  <xs:simpleContent>
    <xs:extension
      base="xs:string"
    >
      <xs:attribute name="HeaderName"
        type="xs:string"
        use="required"
      />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```

Attributes

Name	Type	Description
HeaderName	xs:string	Specifies the name of the header.

2.2.3.33 t:IntervalRecurrencePatternBaseType Complex Type

The **IntervalRecurrencePatternBaseType** complex type specifies the base type for non-yearly recurrence patterns.

```
<xs:complexType name="IntervalRecurrencePatternBaseType"
  abstract="true"
>
  <xs:complexContent>
    <xs:extension
      base="t:RecurrencePatternBaseType"
    />
  </xs:complexContent>
</xs:complexType>
```

```

    >
    <xs:sequence>
      <xs:element name="Interval"
        type="xs:int"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
Interval	xs:int	Specifies the interval between two consecutive recurring items.

2.2.3.34 m:ItemInfoResponseMessageType Complex Type

The **ItemInfoResponseMessageType** complex type specifies the response message for operations that create, update, or delete items.

```

<xs:complexType name="ItemInfoResponseMessageType">
  <xs:complexContent>
    <xs:extension
      base="m:ResponseMessageType"
    >
      <xs:sequence>
        <xs:element name="Items"
          type="t:ArrayOfRealItemsType"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
Items	t:ArrayOfRealItemsType	Specifies an array of real items .

2.2.3.35 t:ItemResponseShapeType Complex Type

The **ItemResponseShapeType** complex type specifies a set of properties to return in a **GetItem** operation ([\[MS-OXWSCORE\]](#) section 3.1.4.4), **FindItem** operation ([\[MS-OXWSSRCH\]](#) section 3.1.4.2), or **SyncFolderItems** operation ([\[MS-OXWSSYNC\]](#) section 3.1.4.2) response.

```

<xs:complexType name="ItemResponseShapeType">
  <xs:sequence>
    <xs:element name="BaseShape"
      type="t:DefaultShapeNamesType"
    />
  </xs:sequence>
</xs:complexType>

```

```

<xs:element name="IncludeMimeContent"
  type="xs:boolean"
  minOccurs="0"
/>
<xs:element name="BodyType"
  type="t:BodyTypeResponseType"
  minOccurs="0"
/>
<xs:element name="FilterHtmlContent"
  type="xs:boolean"
  maxOccurs="1"
  minOccurs="0"
/>
<xs:element name="ConvertHtmlCodePageToUTF8"
  type="xs:boolean"
  minOccurs="0"
/>
<xs:element name="AdditionalProperties"
  type="t:NonEmptyArrayOfPathsToElementType"
  minOccurs="0"
/>
</xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
BaseShape	t:DefaultShapeNamesType	Specifies the requested base properties to return in a response. This element MUST be present. The DefaultShapeNamesType simple type is specified in section 2.2.2.6 .
IncludeMimeContent	xs:boolean	Specifies whether the MIME content of an item is returned in a response. The xs:boolean type is specified in [XMLSCHEMA2] .
BodyType	t:BodyTypeResponseType	Specifies the requested body text format for the Body property that is returned in a response. If this element is not present, the server MUST use the default value of "default". The BodyTypeResponseType simple type is specified in section 2.2.2.1 .
FilterHtmlContent	xs:boolean	Specifies whether HTML content filtering is enabled.

Element	Type	Description
		If this value is set to true , script blocks and Web beacons MUST be removed from message bodies that are returned in a response.
ConvertHtmlCodePageToUTF8	xs:boolean	Specifies whether the item HTML body is converted to UTF8. The value of this element MUST be set to true or the element MUST NOT be specified to indicate to the server to convert the HTML code page to UTF8. <16>
AdditionalProperties	t:NonEmptyArrayOfPathsToElementType	Specifies a set of requested additional properties to return in a response.

2.2.3.36 t:MailboxCultureType Complex Type

The **MailboxCultureType** complex type specifies the culture to be used when opening a mailbox.

```
<xs:complexType name="MailboxCultureType">
  <xs:simpleContent>
    <xs:extension
      base="xs:language"
    >
      <xs:anyAttribute
        namespace="http://schemas.xmlsoap.org/soap/envelope/"
      />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```

The text value indicates the language to be used. The possible values for this element are specified in [\[RFC3066\]](#).

2.2.3.37 t:NoEndRecurrenceRangeType Complex Type

The **NoEndRecurrenceRangeType** complex type specifies the start date of an item recurrence pattern that does not have a defined end date.

```
<xs:complexType name="NoEndRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrenceRangeBaseType"
    />
  </xs:complexContent>
</xs:complexType>
```

2.2.3.38 t:NonEmptyArrayOfAllItemsType Complex Type

The **NonEmptyArrayOfAllItemsType** complex type specifies an array of store items and response objects.

```
<xs:complexType name="NonEmptyArrayOfAllItemsType">
  <xs:sequence>
    <xs:choice
      minOccurs="1"
      maxOccurs="unbounded"
    >
      <xs:element name="Item"
        type="t:ItemType"
      />
      <xs:element name="Message"
        type="t:MessageType"
      />
      <xs:element name="CalendarItem"
        type="t:CalendarItemType"
      />
      <xs:element name="Contact"
        type="t:ContactItemType"
      />
      <xs:element name="DistributionList"
        type="t:DistributionListType"
      />
      <xs:element name="MeetingMessage"
        type="t:MeetingMessageType"
      />
      <xs:element name="MeetingRequest"
        type="t:MeetingRequestMessageType"
      />
      <xs:element name="MeetingResponse"
        type="t:MeetingResponseMessageType"
      />
      <xs:element name="MeetingCancellation"
        type="t:MeetingCancellationMessageType"
      />
      <xs:element name="Task"
        type="t:TaskType"
      />
      <xs:element name="PostItem"
        type="t:PostItemType"
      />
      <xs:element name="ReplyToItem"
        type="t:ReplyToItemType"
      />
      <xs:element name="ForwardItem"
        type="t:ForwardItemType"
      />
      <xs:element name="ReplyAllToItem"
        type="t:ReplyAllToItemType"
      />
      <xs:element name="AcceptItem"
        type="t:AcceptItemType"
      />
      <xs:element name="TentativelyAcceptItem"
        type="t:TentativelyAcceptItemType"
      />
    </xs:choice>
  </xs:sequence>
</xs:complexType>
```

```

<xs:element name="DeclineItem"
  type="t:DeclineItemType"
/>
<xs:element name="CancelCalendarItem"
  type="t:CancelCalendarItemType"
/>
<xs:element name="RemoveItem"
  type="t:RemoveItemType"
/>
<xs:element name="SuppressReadReceipt"
  type="t:SuppressReadReceiptType"
/>
<xs:element name="PostReplyItem"
  type="t:PostReplyItemType"
/>
<xs:element name="AcceptSharingInvitation"
  type="t:AcceptSharingInvitationType"
/>
</xs:choice>
</xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
Item	t:ItemType	Specifies an item.
Message	t:MessageType	Specifies a message item.
CalendarItem	t:CalendarItemType	Specifies a calendar item.
Contact	t:ContactItemType	Specifies a contact item.
DistributionList	t:DistributionListType	Specifies a distribution list item.
MeetingMessage	t:MeetingMessageType	Specifies a meeting message item.
MeetingRequest	t:MeetingRequestMessageType	Specifies a meeting request message item.
MeetingResponse	t:MeetingResponseMessageType	Specifies a meeting response message item.
MeetingCancellation	t:MeetingCancellationMessageType	Specifies a meeting cancellation message item.
Task	t:TaskType	Specifies a task item.
PostItem	t:PostItemType	Specifies a post item.
ReplyToItem	t:ReplyToItemType	Specifies a ReplyToItem response object.
ForwardItem	t:ForwardItemType	Specifies a ForwardItem response object.

Element	Type	Description
ReplyAllToItem	t:ReplyAllToItemType	Specifies a ReplyToAllItem response object.
AcceptItem	t:AcceptItemType	Specifies an AcceptItem response object.
TentativelyAcceptItem	t:TentativelyAcceptItemType	Specifies a TentativelyAcceptItem response object.
DeclineItem	t:DeclineItemType	Specifies a DeclineItem response object.
CancelCalendarItem	t:CancelCalendarItemType	Specifies a CancelCalendarItem response object.
RemoveItem	t:RemoveItemType	Specifies a RemoveItem response object.
SuppressReadReceipt	t:SuppressReadReceiptType	Specifies a SuppressReadReceipt response object.
PostReplyItem	t:PostReplyItemType	Specifies a PostReplyItem response object.
AcceptSharingInvitation	t:AcceptSharingInvitationType	Specifies an AcceptSharingInvitation response object.

2.2.3.39 t:NonEmptyArrayOfAttachmentsType Complex Type

The **NonEmptyArrayOfAttachmentsType** complex type specifies an array of items or files that are attached to an item.

```
<xs:complexType name="NonEmptyArrayOfAttachmentsType">
  <xs:choice
    minOccurs="1"
    maxOccurs="unbounded"
  >
    <xs:element name="ItemAttachment"
      type="t:ItemAttachmentType"
    />
    <xs:element name="FileAttachment"
      type="t:FileAttachmentType"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
ItemAttachment	t:ItemAttachmentType	Specifies an item attachment.

Element	Type	Description
FileAttachment	t:FileAttachmentType	Specifies a file attachment.

2.2.3.40 t:NonEmptyArrayOfPathsToElementType Complex Type

The **NonEmptyArrayOfPathsToElementType** complex type specifies additional properties to be returned in a response.

```
<xs:complexType name="NonEmptyArrayOfPathsToElementType">
  <xs:choice
    maxOccurs="unbounded"
  >
    <xs:element
      ref="t:Path"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
t:Path	t:Path	Specifies a property to be returned in a response.

2.2.3.41 t:NumberedRecurrenceRangeType Complex Type

The **NumberedRecurrenceRangeType** complex type specifies the start date and number of occurrences of a recurring item.

```
<xs:complexType name="NumberedRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrenceRangeBaseType"
    >
      <xs:sequence>
        <xs:element name="NumberOfOccurrences"
          type="xs:int"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
NumberOfOccurrences	xs:int	Specifies the number of occurrences of a recurring item.

2.2.3.42 t:PathToExceptionFieldType Complex Type

The **t:PathToExceptionFieldType** complex type specifies errors in a response.

```
<xs:complexType name="PathToExceptionFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:BasePathToElementType"
    >
      <xs:attribute name="FieldURI"
        type="t:ExceptionPropertyURIType"
        use="required"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Attributes

Name	Type
FieldURI	t:ExceptionPropertyURIType

2.2.3.43 t:PathToIndexedFieldType Complex Type

The **PathToIndexedFieldType** complex type specifies individual members of a dictionary property.

```
<xs:complexType name="PathToIndexedFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:BasePathToElementType"
    >
      <xs:attribute name="FieldURI"
        type="t:DictionaryURIType"
        use="required"
      />
      <xs:attribute name="FieldIndex"
        type="xs:string"
        use="required"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Attributes

Name	Type	Description
FieldURI	t:DictionaryURIType	Specifies the dictionary property. This attribute MUST be present.
FieldIndex	xs:string	Specifies the entry index in a dictionary. This attribute MUST be present.

2.2.3.44 t:PathToUnindexedFieldType Complex Type

The **PathToUnindexedFieldType** complex type specifies frequently referenced properties.

```
<xs:complexType name="PathToUnindexedFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:BasePathToElementType"
    >
      <xs:attribute name="FieldURI"
        type="t:UnindexedFieldURIType"
        use="required"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Attributes

Name	Type	Description
FieldURI	t:UnindexedFieldURIType	Specifies frequently referenced field URIs. This attribute MUST be present.

2.2.3.45 t:RecurrencePatternBaseType Complex Type

The **RecurrencePatternBaseType** complex type specifies the base type for recurrence patterns.

```
<xs:complexType name="RecurrencePatternBaseType"
  abstract="true"
/>
```

2.2.3.46 t:RecurrenceRangeBaseType Complex Type

The **RecurrenceRangeBaseType** complex type specifies the base type for all recurrence patterns that have a start date.

```
<xs:complexType name="RecurrenceRangeBaseType"
  abstract="true"
>
  <xs:sequence>
    <xs:element name="StartDate"
      type="xs:date"
    />
  </xs:sequence>
</xs:complexType>
```

Child Elements

Element	Type	Description
StartDate	xs:date	Specifies the start date of a recurrence range.

2.2.3.47 t:RelativeMonthlyRecurrencePatternType Complex Type

The **RelativeMonthlyRecurrencePatternType** complex type specifies a relative monthly recurrence pattern.

```
<xs:complexType name="RelativeMonthlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:IntervalRecurrencePatternBaseType"
    >
      <xs:sequence>
        <xs:element name="DaysOfWeek"
          type="t:DayOfWeekType"
        />
        <xs:element name="DayOfWeekIndex"
          type="t:DayOfWeekIndexType"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
DaysOfWeek	t:DayOfWeekType	Specifies the days of the week that are used in a relative monthly recurrence pattern.
DayOfWeekIndex	t:DayOfWeekIndexType	Specifies the week that is used in a relative monthly recurrence pattern.

2.2.3.48 t:RelativeYearlyRecurrencePatternType Complex Type

The **RelativeYearlyRecurrencePatternType** complex type specifies a relative yearly recurrence pattern.

```
<xs:complexType name="RelativeYearlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrencePatternBaseType"
    >
      <xs:sequence>
        <xs:element name="DaysOfWeek"
          type="t:DayOfWeekType"
        />
        <xs:element name="DayOfWeekIndex"
          type="t:DayOfWeekIndexType"
        />
        <xs:element name="Month"

```

```

        type="t:MonthNamesType"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
DaysOfWeek	t:DayOfWeekType	Specifies the days of the week that are used in a relative monthly recurrence pattern. This element MUST be present.
DayOfWeekIndex	t:DayOfWeekIndexType	Specifies the week that is used in a relative monthly recurrence pattern. This element MUST be present.
Month	t:MonthNamesType	Specifies the month when a yearly recurring item occurs. This element MUST be present.

2.2.3.49 t:ReplyAllToItemType Complex Type

The **ReplyAllToItemType** complex type specifies a response object that is used to reply to the sender and all recipients of an item.

```

<xs:complexType name="ReplyAllToItemType">
  <xs:complexContent>
    <xs:extension
      base="t:SmartResponseType"
    />
  </xs:complexContent>
</xs:complexType>

```

2.2.3.50 t:ReplyBody

The **ReplyBody** complex type specifies the body of the **OOF message** that is sent to users.

```

<xs:complexType name="ReplyBody">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Message" type="xs:string" />
  </xs:sequence>
  <xs:attribute ref="xml:lang" use="optional" />
</xs:complexType>

```

Element	Type	Definition
Message	xs:string	An HTML message that forms the body of the OOF message. This element is optional and SHOULD NOT exceed 128000 bytes.

Attribute	Definition
xml:lang	Specifies the language used in the OOF message. This attribute is optional. The possible values of this attribute are defined by RFC3066 .

2.2.3.51 t:ReplyToItemType Complex Type

The **ReplyToItemType** complex type specifies a reply response object that is used to reply to the sender of an item.

```
<xs:complexType name="ReplyToItemType">
  <xs:complexContent>
    <xs:extension
      base="t:SmartResponseType"
    />
  </xs:complexContent>
</xs:complexType>
```

2.2.3.52 m:ResponseMessageType Complex Type

The **ResponseMessageType** complex type specifies information about the response status for a single entity in a request.

```
<xs:complexType name="ResponseMessageType">
  <xs:sequence
    minOccurs="0"
  >
    <xs:element name="MessageText"
      type="xs:string"
      minOccurs="0"
    />
    <xs:element name="ResponseCode"
      type="m:ResponseCodeType"
      minOccurs="0"
    />
    <xs:element name="DescriptiveLinkKey"
      type="xs:int"
      minOccurs="0"
    />
    <xs:element name="MessageXml"
      minOccurs="0"
    >
      <xs:complexType>
        <xs:sequence>
          <xs:any
            process_contents="lax"
            minOccurs="0"
            maxOccurs="unbounded"
          />
        </xs:sequence>
        <xs:attribute name="ResponseClass"
          type="t:ResponseClassType"
          use="required"
        />
      </xs:complexType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
```

```

    </xs:element>
  </xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
MessageText	xs:string	Specifies a text description of the status of a response.
ResponseCode	m:ResponseCodeType	Specifies the error code that identifies the specific error that the request encountered, if any.
DescriptiveLinkKey	xs:int	This element is not used.
MessageXml	N/A	Specifies additional error response information.

Attributes

Name	Type	Description
ResponseClass	t:ResponseClassType	<p>Represents the status of the response. The following values are valid for this attribute:</p> <ul style="list-style-type: none"> ▪ Success ▪ Warning ▪ Error <p>This attribute MUST be present.</p>

2.2.3.53 t:ResponseObjectCoreType Complex Type

The **ResponseObjectCoreType** complex type specifies the base type for response objects.

```

<xs:complexType name="ResponseObjectCoreType"
  abstract="true"
>
  <xs:complexContent>
    <xs:extension
      base="t:MessageType"
    >
      <xs:sequence>
        <xs:element name="ReferenceItemId"
          type="t:ItemIdType"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
ReferenceItemId	t:ItemIdType	Specifies the item identifier that is related to a response object.

2.2.3.54 t:ResponseType Complex Type

The **ResponseType** complex type specifies the base type for response objects.

```
<xs:complexType name="ResponseType"
  abstract="true"
>
  <xs:complexContent>
    <xs:extension
      base="t:ResponseObjectCoreType"
    >
      <xs:attribute name="ObjectName"
        type="xs:string"
        use="optional"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Attributes

Name	Type	Description
ObjectName	xs:string	Specifies the name of the reply object class as an English-language string.

2.2.3.55 t:SingleRecipientType Complex Type

The **SingleRecipientType** complex type specifies the e-mail address information for a single message recipient.

```
<xs:complexType name="SingleRecipientType">
  <xs:choice>
    <xs:element name="Mailbox"
      type="t:EmailAddressType"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
Mailbox	t:EmailAddressType	Specifies the e-mail address of a recipient.

2.2.3.56 t:SuppressReadReceiptType Complex Type

The **SuppressReadReceiptType** complex type specifies the suppress read receipt response object.

```

<xs:complexType name="SuppressReadReceiptType">
  <xs:complexContent>
    <xs:extension
      base="t:ReferenceItemResponseType"
    />
  </xs:complexContent>
</xs:complexType>

```

2.2.3.57 t:UserIdType Complex Type

The **UserIdType** complex type specifies a user identifier.

```

<xs:complexType name="UserIdType">
  <xs:sequence>
    <xs:element name="SID"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="PrimarySmtpAddress"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="DisplayName"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="DistinguishedUser"
      type="t:DistinguishedUserType"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="ExternalUserIdentity"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
  </xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
SID	xs:string	Specifies the security descriptor definition language (SSDL) form of the security identifier (SID) for a user.
PrimarySmtpAddress	xs:string	Specifies the primary SMTP address of an account.
DisplayName	xs:string	Specifies the user name for display.

Element	Type	Description
DistinguishedUser	t:DistinguishedUserType	Specifies a value that identifies the Anonymous and Default user accounts for delegate access.
ExternalUserIdentity	xs:string	Specifies an external user identity.

2.2.3.58 t:Value Complex Type

The **Value** complex type specifies the name and value of a property that is returned in an error response.

```
<xs:complexType name="Value">
  <xs:simpleContent>
    <xs:extension
      base="xs:string"
    >
      <xs:attribute name="Name"
        type="xs:string"
        use="required"
      />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```

Attributes

Name	Type	Description
Name	xs:string	Specifies a property name.

2.2.3.59 t:WeeklyRecurrencePatternType Complex Type

The **WeeklyRecurrencePatternType** complex type specifies the interval, in weeks, at which an item recurs, and the days on which the item recurs.

```
<xs:complexType name="WeeklyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:IntervalRecurrencePatternBaseType"
    >
      <xs:sequence>
        <xs:element name="DaysOfWeek"
          type="t:DaysOfWeekType"
        />
        <xs:element name="FirstDayOfWeek"
          type="t:DayOfWeekType"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
DaysOfWeek	t:DaysOfWeekType	Specifies the days of the week that are in the weekly recurrence pattern.
FirstDayOfWeek	t:DayOfWeekType	Specifies the first day of the week. <17>

2.2.3.60 t:WellKnownResponseType Complex Type

The **WellKnownResponseType** complex type specifies the base type for calendar item related response objects.

```
<xs:complexType name="WellKnownResponseType">
  <xs:complexContent>
    <xs:restriction
      base="t:ResponseType"
    >
      <xs:sequence>
        <xs:element name="ItemClass"
          type="t:ItemClassType"
          minOccurs="0"
        />
        <xs:element name="Sensitivity"
          type="t:SensitivityChoicesType"
          minOccurs="0"
        />
        <xs:element name="Body"
          type="t:BodyType"
          minOccurs="0"
        />
        <xs:element name="Attachments"
          type="t:NonEmptyArrayOfAttachmentsType"
          minOccurs="0"
        />
        <xs:element name="InternetMessageHeaders"
          type="t:NonEmptyArrayOfInternetHeadersType"
          minOccurs="0"
        />
        <xs:element name="Sender"
          type="t:SingleRecipientType"
          minOccurs="0"
        />
        <xs:element name="ToRecipients"
          type="t:ArrayOfRecipientsType"
          minOccurs="0"
        />
        <xs:element name="CcRecipients"
          type="t:ArrayOfRecipientsType"
          minOccurs="0"
        />
        <xs:element name="BccRecipients"
          type="t:ArrayOfRecipientsType"
        />
      </xs:sequence>
    </xs:restriction>
  </xs:complexContent>
</xs:complexType>
```

```

        minOccurs="0"
      />
    <xs:element name="IsReadReceiptRequested"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="IsDeliveryReceiptRequested"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="From"
      type="t:SingleRecipientType"
      minOccurs="0"
    />
    <xs:element name="ReferenceItemId"
      type="t:ItemIdType"
      minOccurs="0"
    />
  </xs:sequence>
  <xs:attribute name="ObjectName"
    type="xs:string"
    use="prohibited"
  />
</xs:restriction>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
ItemClass	t:ItemClassType	Specifies the item class.
Sensitivity	t:SensitivityChoicesType	Specifies the item sensitivity level.
Body	t:BodyType	Specifies the body content.
Attachments	t:NonEmptyArrayOfAttachmentsType	Specifies the attachments on a response object.
InternetMessageHeaders	t:NonEmptyArrayOfInternetHeadersType	Specifies an array of type InternetHeaderType that represents the collection of all Internet message headers that are contained in an item.
Sender	t:SingleRecipientType	Specifies the sender of a message.
ToRecipients	t:ArrayOfRecipientsType	Specifies a collection of

Element	Type	Description
		recipients of an item.
CcRecipients	t:ArrayOfRecipientsType	Specifies a collection of carbon copy (Cc) recipients of an item.
BccRecipients	t:ArrayOfRecipientsType	Specifies a collection of blind carbon copy (Bcc) recipients of an item.
IsReadReceiptRequested	xs:boolean	Specifies whether a read receipt is requested.
IsDeliveryReceiptRequested	xs:boolean	Specifies whether a delivery receipt is requested.
From	t:SingleRecipientType	Specifies the addressee who sent a message.
ReferenceItemId	t:ItemIdType	Specifies the item identifier that is related to a response object.

Attributes

Name	Type	Description
ObjectName	xs:string	Specifies the name of the reply object class as an English-language string.

2.2.4 Elements

2.2.4.1 t:DateTimePrecision Element

2.2.4.2 t:ExceptionFieldURI Element

The **ExceptionFieldURI** element specifies particular errors in a request.

```
<xs:element name="t:ExceptionFieldURI"
  type="t:PathToExceptionFieldType"
/>
```

2.2.4.3 t:ExchangeImpersonation Element

The **ExchangeImpersonation** element is used in the **SOAP header** of a request. When the **ExchangeImpersonation** element is present, the caller is trying to impersonate the account that is specified by the **ConnectingSID** element in the **t:ExchangeImpersonationType** complex type as specified in section [2.2.3.27](#).

```
<xs:element name="t:ExchangeImpersonation"
  type="t:ExchangeImpersonationType"
```

```
/>
```

2.2.4.4 t:FieldURI Element

The **FieldURI** element specifies frequently referenced properties by URI.

```
<xs:element name="t:FieldURI"  
  type="t:PathToUnindexedFieldType"  
/>
```

The full syntax for this element is `<xs:element name="FieldURI" type="t:PathToUnindexedFieldType" substitutionGroup="t:Path"/>`

2.2.4.5 t:IndexedFieldURI Element

The **IndexedFieldURI** element specifies individual members of a dictionary.

```
<xs:element name="t:IndexedFieldURI"  
  type="t:PathToIndexedFieldType"  
/>
```

The syntax for this element is `<xs:element name="IndexedFieldURI" type="t:PathToIndexedFieldType" substitutionGroup="t:Path" />`.

2.2.4.6 t:MailboxCulture Element

The **MailboxCulture** element specifies the culture to be used when opening a mailbox. The **MailboxCulture** element occurs in the SOAP header.

```
<xs:element name="t:MailboxCulture"  
  type="t:MailboxCultureType"  
/>
```

2.2.4.7 t:Path Element

The **Path** element specifies the base schema type for all property identifiers. This type is abstract and will never occur directly within instance documents. This type defines a substitution group.

```
<xs:element name="t:Path"  
  type="t:BasePathToElementType"  
  abstract="true"  
/>
```

2.2.4.8 t:RequestServerVersion Element

The **RequestServerVersion** element specifies the versioning information that identifies the schema version to be targeted for a request. [<18>](#)

```
<xs:element name="t:RequestServerVersion">
  <xs:complexType>
    <xs:attribute name="Version"
      type="t:ExchangeVersionType"
      use="required"
      fixed="Exchange2010_SP1"
    />
    <xs:anyAttribute
      namespace="http://schemas.xmlsoap.org/soap/envelope/"
    />
  </xs:complexType>
</xs:element>
```

Attributes

Name	Type
Version	t:ExchangeVersionType

2.2.4.9 t:ServerVersionInfo Element

The **ServerVersionInfo** element specifies the version number of the server.

```
<xs:element name="t:ServerVersionInfo">
  <xs:complexType>
    <xs:attribute name="MajorVersion"
      type="xs:int"
      use="optional"
    />
    <xs:attribute name="MinorVersion"
      type="xs:int"
      use="optional"
    />
    <xs:attribute name="MajorBuildNumber"
      type="xs:int"
      use="optional"
    />
    <xs:attribute name="MinorBuildNumber"
      type="xs:int"
      use="optional"
    />
    <xs:attribute name="Version"
      type="xs:string"
      use="optional"
    />
  </xs:complexType>
</xs:element>
```

Attributes

Name	Type
MajorVersion	xs:int
MinorVersion	xs:int
MajorBuildNumber	xs:int
MinorBuildNumber	xs:int
Version	xs:string

2.2.4.10 Value Element

The **Value** element specifies the value of an extended property.

```
<xs:element name="Value"  
  type="t:Value"  
/>
```

2.2.5 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.6 Groups

2.2.6.1 t:RecurrencePatternTypes Group

The **RecurrencePatternTypes** group specifies the recurrence pattern for calendar items and meeting requests.

```
<xs:group name="t:RecurrencePatternTypes">  
  <xs:sequence>  
    <xs:choice>  
      <xs:element name="t:RelativeYearlyRecurrence"  
        type="t:RelativeYearlyRecurrencePatternType"  
      />  
      <xs:element name="AbsoluteYearlyRecurrence"  
        type="t:AbsoluteYearlyRecurrencePatternType"  
      />  
      <xs:element name="RelativeMonthlyRecurrence"  
        type="t:RelativeMonthlyRecurrencePatternType"  
      />  
      <xs:element name="AbsoluteMonthlyRecurrence"  
        type="t:AbsoluteMonthlyRecurrencePatternType"  
      />  
      <xs:element name="WeeklyRecurrence"  
        type="t:WeeklyRecurrencePatternType"  
      />  
      <xs:element name="DailyRecurrence"  
        type="t:DailyRecurrencePatternType"  
      />  
    </xs:choice>  
  </xs:sequence>  
</xs:group>
```

```

</xs:sequence>
</xs:group>

```

Child Elements

Element	Type	Description
t:RelativeYearlyRecurrence	t:RelativeYearlyRecurrencePatternType	Specifies a relative yearly recurrence pattern.
AbsoluteYearlyRecurrence	t:AbsoluteYearlyRecurrencePatternType	Specifies a yearly recurrence pattern.
RelativeMonthlyRecurrence	t:RelativeMonthlyRecurrencePatternType	Specifies a relative monthly recurrence pattern for a recurring calendar item.
AbsoluteMonthlyRecurrence	t:AbsoluteMonthlyRecurrencePatternType	Specifies a monthly recurrence pattern.
WeeklyRecurrence	t:WeeklyRecurrencePatternType	Specifies the interval, in weeks, at which a calendar item recurs, and the days of the week on which it occurs.
DailyRecurrence	t:DailyRecurrencePatternType	Specifies the interval, in days, at which a calendar item recurs.

2.2.6.2 t:RecurrenceRangeTypes Group

The **RecurrenceRangeTypes** group specifies recurrence patterns with numbered recurrences, non-ending recurrence patterns, and recurrence patterns with a set start and end date.

```

<xs:group name="t:RecurrenceRangeTypes">
  <xs:sequence>
    <xs:choice>
      <xs:element name="NoEndRecurrence"
        type="t:NoEndRecurrenceRangeType"
      />
      <xs:element name="EndDateRecurrence"
        type="t:EndDateRecurrenceRangeType"
      />
      <xs:element name="NumberedRecurrence"
        type="t:NumberedRecurrenceRangeType"
      />
    </xs:choice>
  </xs:sequence>
</xs:group>

```


Child Elements

Element	Type	Description
NoEndRecurrence	t:NoEndRecurrenceRangeType	Specifies a recurrence pattern that does not have a defined end date.
EndDateRecurrence	t:EndDateRecurrenceRangeType	Specifies the start date and the end date of an item recurrence pattern.
NumberedRecurrence	t:NumberedRecurrenceRangeType	Specifies the start date and the number of occurrences of a recurring item.

2.2.6.3 t:TimeChangePatternTypes Group

The **TimeChangePatternTypes** group specifies the date when the time changes from standard time or daylight saving time.

```
<xs:group name="t:TimeChangePatternTypes">
  <xs:sequence>
    <xs:choice>
      <xs:element name="RelativeYearlyRecurrence"
        type="t:RelativeYearlyRecurrencePatternType"
      />
      <xs:element name="AbsoluteDate"
        type="xs:date"
      />
    </xs:choice>
  </xs:sequence>
</xs:group>
```

Child Elements

Element	Type	Description
RelativeYearlyRecurrence	t:RelativeYearlyRecurrencePatternType	Specifies a relative yearly recurrence pattern for a time zone transition date.
AbsoluteDate	xs:date	Specifies the date when the time changes from standard time or daylight saving time.

2.2.7 Attribute Groups

2.2.7.1 t:FindResponsePagingAttributes Attribute Group

The **FindResponsePagingAttributes** attribute group specifies paging and count information for a result set.

```
<xs:attributeGroup name="t:FindResponsePagingAttributes">
  <xs:attribute name="IndexedPagingOffset"
```

```

    type="xs:int"
    use="optional"
  />
  <xs:attribute name="NumeratorOffset"
    type="xs:int"
    use="optional"
  />
  <xs:attribute name="AbsoluteDenominator"
    type="xs:int"
    use="optional"
  />
  <xs:attribute name="IncludesLastItemInRange"
    type="xs:int"
    use="optional"
  />
  <xs:attribute name="TotalItemsInView"
    type="xs:int"
    use="optional"
  />
</xs:attributeGroup>

```

Attributes

Name	Type	Description
IndexedPagingOffset	xs:int	Specifies the next index that should be used for the next request when using an indexed paging view.
NumeratorOffset	xs:int	Specifies the new numerator value to use for the next request when using fraction page views.
AbsoluteDenominator	xs:int	Specifies the next denominator to use for the next request when doing fractional paging.
IncludesLastItemInRange	xs:int	Specifies whether the current results contain the last item in the query, such that no further paging is required.
TotalItemsInView	xs:int	Specifies the total number of results.

2.2.8 Messages

This specification does not define any common WSDL message definitions.

3 Protocol Details

This document specifies common XML schema types and elements and does not have any protocol details.

3.1 Server Details

This document specifies common XML schema types and elements and does not have any server protocol details.

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

None.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

3.2 Client Details

This document specifies common XML schema types and elements and does not have any client protocol details.

3.2.1 Abstract Data Model

None.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Message Processing Events and Sequencing Rules

None.

3.2.5 Timer Events

None.

3.2.6 Other Local Events

None.

4 Protocol Examples

None.

5 Security

5.1 Security Considerations for Implementers

The Common Web Service Data Types do not involve any additional security mechanisms.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

The XML files that are listed in the following table are required in order to implement the functionality described in this document.

File name	Description	Section
MS-OXWSCDATA-messages.xsd	Contains the XML schema message definitions.	7.1
MS-OXWSCDATA-types.xsd	Contains the XML schema type definitions.	7.2

These files have to be placed in a common folder in order for any referencing WSDL to validate and operate. Also, any schema files that are included in or imported into the MS-OXWSCDATA-types.xsd or MS-OXWSCDATA-messages.xsd schemas have to be placed in the common folder along with the files listed in the table.

This protocol specification does not define a WSDL file.

7 Appendix B: Full XML Schema

For ease of implementation, the following sections provide the full XML schema for this protocol.

Schema name	Prefix	Section
Messages schema	m:	7.1
Types schema	t:	7.2

These files have to be placed in a common folder in order for any referencing WSDL to validate and operate. Also, any schema files that are included in or imported into the MS-OXWSCDATA-types.xsd or MS-OXWCDATA-messages.xsd schemas have to be placed in the common folder along with the files listed in the table.

7.1 Messages Schema

This section provides the contents of the MS-OXWSCDATA-messages.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSCDATA-messages.xsd includes or imports the files listed in the following table. To operate correctly, these files have to be present in the folder that contains the types and messages schema files.

File name	Defining specification/section
MS-OXWSCDATA-types.xsd	section 7.2
MS-OXWSCORE-messages.xsd	[MS-OXWSCORE] section 7.1
MS-OXWSFOLD-messages.xsd	[MS-OXWSFOLD] section 7.1
MS-OXWSSRCH-messages.xsd	[MS-OXWSSRCH] section 7.1
MS-OXWSATT-messages.xsd	[MS-OXWSATT] section 7.1
MS-OXWSRSLNM-messages.xsd	[MS-OXWSRSLNM] section 7.1
MS-OXWSDLIST-messages.xsd	[MS-OXWSDLIST] section 6.3
MS-OXWSGTZ-messages.xsd	[MS-OXWSGTZ] section 7.1
MS-OXWSNTIF-messages.xsd	[MS-OXWSNTIF] section 7.1
MS-OXWSPSNTIF-messages.xsd	[MS-OXWSPSNTIF] section 7.1
MS-OXWSSYNC-messages.xsd	[MS-OXWSSYNC] section 7.1
MS-OXWSCVTID-messages.xsd	[MS-OXWSCVTID] section 7.1
MS-OXWSMSHR-messages.xsd	[MS-OXWSMSHR] section 7.1
MS-OXWSGTRM-messages.xsd	[MS-OXWSGTRM] section 6.3
MS-OXWSBTRF-messages.xsd	[MS-OXWSBTRF] section 7.1

```
<?xml version="1.0" encoding="utf-8"?>
```



```

<xs:schema xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
elementFormDefault="qualified" version="Exchange2010_SP1" id="messages">
  <xs:import namespace="http://schemas.microsoft.com/exchange/services/2006/types"
schemaLocation="MS-OXWSCDATA-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSCORE-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSFOLD-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSSRCH-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSATT-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSRSLNM-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSDLIST-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSGTZ-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSNTIF-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSPSNTIF-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSSYNC-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSCVTID-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSMSHR-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSGTRM-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSBTRF-messages.xsd"/>
  <xs:complexType name="ArrayOfResponseMessageType">
    <xs:choice maxOccurs="unbounded">
      <xs:element name="CreateItemResponseMessage"
type="m:ItemInfoResponseMessageType"/>
      <xs:element name="DeleteItemResponseMessage" type="m:ResponseMessageType"/>
      <xs:element name="GetItemResponseMessage"
type="m:ItemInfoResponseMessageType"/>
      <xs:element name="UpdateItemResponseMessage"
type="m:UpdateItemResponseMessageType"/>
      <xs:element name="SendItemResponseMessage" type="m:ResponseMessageType"/>
      <xs:element name="DeleteFolderResponseMessage" type="m:ResponseMessageType"/>
      <xs:element name="EmptyFolderResponseMessage" type="m:ResponseMessageType"/>
      <xs:element name="CreateFolderResponseMessage"
type="m:FolderInfoResponseMessageType"/>
      <xs:element name="GetFolderResponseMessage"
type="m:FolderInfoResponseMessageType"/>
      <xs:element name="FindFolderResponseMessage"
type="m:FindFolderResponseMessageType"/>
      <xs:element name="UpdateFolderResponseMessage"
type="m:FolderInfoResponseMessageType"/>
      <xs:element name="MoveFolderResponseMessage"
type="m:FolderInfoResponseMessageType"/>
      <xs:element name="CopyFolderResponseMessage"
type="m:FolderInfoResponseMessageType"/>
      <xs:element name="CreateAttachmentResponseMessage"
type="m:AttachmentInfoResponseMessageType"/>
      <xs:element name="DeleteAttachmentResponseMessage"
type="m>DeleteAttachmentResponseMessageType"/>
      <xs:element name="GetAttachmentResponseMessage"
type="m:AttachmentInfoResponseMessageType"/>
      <xs:element name="UploadItemsResponseMessage"
type="m:UploadItemsResponseMessageType"/>
      <xs:element name="ExportItemsResponseMessage"
type="m:ExportItemsResponseMessageType"/>
      <xs:element name="FindItemResponseMessage"
type="m:FindItemResponseMessageType"/>
      <xs:element name="MoveItemResponseMessage"
type="m:ItemInfoResponseMessageType"/>
      <xs:element name="CopyItemResponseMessage"
type="m:ItemInfoResponseMessageType"/>
    </xs:choice>
  </xs:complexType>

```

```

        <xs:element name="ResolveNamesResponseMessage"
type="m:ResolveNamesResponseMessageType"/>
        <xs:element name="ExpandDLResponseMessage"
type="m:ExpandDLResponseMessageType"/>
        <xs:element name="GetServerTimeZonesResponseMessage"
type="m:GetServerTimeZonesResponseMessageType"/>
        <xs:element name="GetEventsResponseMessage"
type="m:GetEventsResponseMessageType"/>
        <xs:element name="GetStreamingEventsResponseMessage"
type="m:GetStreamingEventsResponseMessageType"/>
        <xs:element name="SubscribeResponseMessage"
type="m:SubscribeResponseMessageType"/>
        <xs:element name="UnsubscribeResponseMessage" type="m:ResponseMessageType"/>
        <xs:element name="SendNotificationResponseMessage"
type="m:SendNotificationResponseMessageType"/>
        <xs:element name="SyncFolderHierarchyResponseMessage"
type="m:SyncFolderHierarchyResponseMessageType"/>
        <xs:element name="SyncFolderItemsResponseMessage"
type="m:SyncFolderItemsResponseMessageType"/>
        <xs:element name="CreateManagedFolderResponseMessage"
type="m:FolderInfoResponseMessageType"/>
        <xs:element name="ConvertIdResponseMessage"
type="m:ConvertIdResponseMessageType"/>
        <xs:element name="GetSharingMetadataResponseMessage"
type="m:GetSharingMetadataResponseMessageType"/>
        <xs:element name="RefreshSharingFolderResponseMessage"
type="m:RefreshSharingFolderResponseMessageType"/>
        <xs:element name="GetSharingFolderResponseMessage"
type="m:GetSharingFolderResponseMessageType"/>
        <xs:element name="CreateUserConfigurationResponseMessage"
type="m:ResponseMessageType"/>
        <xs:element name="DeleteUserConfigurationResponseMessage"
type="m:ResponseMessageType"/>
        <xs:element name="UpdateUserConfigurationResponseMessage"
type="m:ResponseMessageType"/>
        <xs:element name="GetRoomListsResponse"
type="m:GetRoomListsResponseMessageType"/>
        <xs:element name="GetRoomsResponse" type="m:GetRoomsResponseMessageType"/>
        <xs:element name="ApplyConversationActionResponseMessage"
type="m:ResponseMessageType"/>
    </xs:choice>
</xs:complexType>
<xs:complexType name="BaseRequestType" abstract="true"/>
<xs:complexType name="BaseResponseMessageType">
    <xs:sequence>
        <xs:element name="ResponseMessages" type="m:ArrayOfResponseMessagesType"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ItemInfoResponseMessageType">
    <xs:complexContent>
        <xs:extension base="m:ResponseMessageType">
            <xs:sequence>
                <xs:element name="Items" type="t:ArrayOfRealItemsType"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ResponseMessageType">
    <xs:sequence minOccurs="0">
        <xs:element name="MessageText" type="xs:string" minOccurs="0"/>
        <xs:element name="ResponseCode" type="m:ResponseCodeType" minOccurs="0"/>
    </xs:sequence>

```

```

    <xs:element name="DescriptiveLinkKey" type="xs:int" minOccurs="0"/>
    <xs:element name="MessageXml" minOccurs="0">
      <xs:complexType>
        <xs:sequence>
          <xs:any processContents="lax" minOccurs="0"
maxOccurs="unbounded"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="ResponseClass" type="t:ResponseClassType" use="required"/>
</xs:complexType>
<xs:simpleType name="ResponseCodeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NoError"/>
    <xs:enumeration value="ErrorAccessDenied"/>
    <xs:enumeration value="ErrorAccessModeSpecified"/>
    <xs:enumeration value="ErrorAccountDisabled"/>
    <xs:enumeration value="ErrorAddDelegatesFailed"/>
    <xs:enumeration value="ErrorAddressSpaceNotFound"/>
    <xs:enumeration value="ErrorADOperation"/>
    <xs:enumeration value="ErrorADSessionFilter"/>
    <xs:enumeration value="ErrorADUnavailable"/>
    <xs:enumeration value="ErrorAutoDiscoverFailed"/>
    <xs:enumeration value="ErrorAffectedTaskOccurrencesRequired"/>
    <xs:enumeration value="ErrorAttachmentSizeLimitExceeded"/>
    <xs:enumeration value="ErrorAvailabilityConfigNotFound"/>
    <xs:enumeration value="ErrorBatchProcessingStopped"/>
    <xs:enumeration value="ErrorCalendarCannotMoveOrCopyOccurrence"/>
    <xs:enumeration value="ErrorCalendarCannotUpdateDeletedItem"/>
    <xs:enumeration value="ErrorCalendarCannotUseIdForOccurrenceId"/>
    <xs:enumeration value="ErrorCalendarCannotUseIdForRecurringMasterId"/>
    <xs:enumeration value="ErrorCalendarDurationIsTooLong"/>
    <xs:enumeration value="ErrorCalendarEndDateIsEarlierThanStartDate"/>
    <xs:enumeration value="ErrorCalendarFolderIsInvalidForCalendarView"/>
    <xs:enumeration value="ErrorCalendarInvalidAttributeValue"/>
    <xs:enumeration value="ErrorCalendarInvalidDayForTimeChangePattern"/>
    <xs:enumeration value="ErrorCalendarInvalidDayForWeeklyRecurrence"/>
    <xs:enumeration value="ErrorCalendarInvalidPropertyState"/>
    <xs:enumeration value="ErrorCalendarInvalidPropertyValue"/>
    <xs:enumeration value="ErrorCalendarInvalidRecurrence"/>
    <xs:enumeration value="ErrorCalendarInvalidTimeZone"/>
    <xs:enumeration value="ErrorCalendarIsCancelledForAccept"/>
    <xs:enumeration value="ErrorCalendarIsCancelledForDecline"/>
    <xs:enumeration value="ErrorCalendarIsCancelledForRemove"/>
    <xs:enumeration value="ErrorCalendarIsCancelledForTentative"/>
    <xs:enumeration value="ErrorCalendarIsDelegatedForAccept"/>
    <xs:enumeration value="ErrorCalendarIsDelegatedForDecline"/>
    <xs:enumeration value="ErrorCalendarIsDelegatedForRemove"/>
    <xs:enumeration value="ErrorCalendarIsDelegatedForTentative"/>
    <xs:enumeration value="ErrorCalendarIsNotOrganizer"/>
    <xs:enumeration value="ErrorCalendarIsOrganizerForAccept"/>
    <xs:enumeration value="ErrorCalendarIsOrganizerForDecline"/>
    <xs:enumeration value="ErrorCalendarIsOrganizerForRemove"/>
    <xs:enumeration value="ErrorCalendarIsOrganizerForTentative"/>
    <xs:enumeration value="ErrorCalendarOccurrenceIndexIsOutOfRecurrenceRange"/>
    <xs:enumeration value="ErrorCalendarOccurrenceIsDeletedFromRecurrence"/>
    <xs:enumeration value="ErrorCalendarOutOfRange"/>
    <xs:enumeration value="ErrorCalendarMeetingRequestIsOutOfDate"/>
  </xs:restriction>
</xs:simpleType>

```

```
<xs:enumeration value="ErrorCalendarViewRangeTooBig"/>
<xs:enumeration value="ErrorCallerIsInvalidADAccount"/>
<xs:enumeration value="ErrorCannotCreateCalendarItemInNonCalendarFolder"/>
<xs:enumeration value="ErrorCannotCreateContactInNonContactFolder"/>
<xs:enumeration value="ErrorCannotCreatePostItemInNonMailFolder"/>
<xs:enumeration value="ErrorCannotCreateTaskInNonTaskFolder"/>
<xs:enumeration value="ErrorCannotDeleteObject"/>
<xs:enumeration value="ErrorCannotOpenFileAttachment"/>
<xs:enumeration value="ErrorCannotDeleteTaskOccurrence"/>
<xs:enumeration value="ErrorCannotEmptyFolder"/>
<xs:enumeration value="ErrorCannotSetCalendarPermissionOnNonCalendarFolder"/>
<xs:enumeration value="ErrorCannotSetNonCalendarPermissionOnCalendarFolder"/>
<xs:enumeration value="ErrorCannotSetPermissionUnknownEntries"/>
<xs:enumeration value="ErrorCannotUseFolderIdForItemId"/>
<xs:enumeration value="ErrorCannotUseItemIdForFolderId"/>
<xs:enumeration value="ErrorChangeKeyRequired"/>
<xs:enumeration value="ErrorChangeKeyRequiredForWriteOperations"/>
<xs:enumeration value="ErrorClientDisconnected"/>
<xs:enumeration value="ErrorConnectionFailed"/>
<xs:enumeration value="ErrorContainsFilterWrongType"/>
<xs:enumeration value="ErrorContentConversionFailed"/>
<xs:enumeration value="ErrorCorruptData"/>
<xs:enumeration value="ErrorCreateItemAccessDenied"/>
<xs:enumeration value="ErrorCreateManagedFolderPartialCompletion"/>
<xs:enumeration value="ErrorCreateSubfolderAccessDenied"/>
<xs:enumeration value="ErrorCrossMailboxMoveCopy"/>
<xs:enumeration value="ErrorCrossSiteRequest"/>
<xs:enumeration value="ErrorDataSizeLimitExceeded"/>
<xs:enumeration value="ErrorDataSourceOperation"/>
<xs:enumeration value="ErrorDelegateAlreadyExists"/>
<xs:enumeration value="ErrorDelegateCannotAddOwner"/>
<xs:enumeration value="ErrorDelegateMissingConfiguration"/>
<xs:enumeration value="ErrorDelegateNoUser"/>
<xs:enumeration value="ErrorDelegateValidationFailed"/>
<xs:enumeration value="ErrorDeleteDistinguishedFolder"/>
<xs:enumeration value="ErrorDeleteItemsFailed"/>
<xs:enumeration value="ErrorDistinguishedUserNotSupported"/>
<xs:enumeration value="ErrorDistributionListMemberNotExist"/>
<xs:enumeration value="ErrorDuplicateInputFolderNames"/>
<xs:enumeration value="ErrorDuplicateUserIdsSpecified"/>
<xs:enumeration value="ErrorEmailAddressMismatch"/>
<xs:enumeration value="ErrorEventNotFound"/>
<xs:enumeration value="ErrorExceededConnectionCount"/>
<xs:enumeration value="ErrorExceededSubscriptionCount"/>
<xs:enumeration value="ErrorExceededFindCountLimit"/>
<xs:enumeration value="ErrorExpiredSubscription"/>
<xs:enumeration value="ErrorFolderCorrupt"/>
<xs:enumeration value="ErrorFolderNotFound"/>
<xs:enumeration value="ErrorFolderPropertyRequestFailed"/>
<xs:enumeration value="ErrorFolderSave"/>
<xs:enumeration value="ErrorFolderSaveFailed"/>
<xs:enumeration value="ErrorFolderSavePropertyError"/>
<xs:enumeration value="ErrorFolderExists"/>
<xs:enumeration value="ErrorFreeBusyGenerationFailed"/>
<xs:enumeration value="ErrorGetServerSecurityDescriptorFailed"/>
<xs:enumeration value="ErrorImpersonateUserDenied"/>
<xs:enumeration value="ErrorImpersonationDenied"/>
<xs:enumeration value="ErrorImpersonationFailed"/>
<xs:enumeration value="ErrorIncorrectSchemaVersion"/>
```

```
<xs:enumeration value="ErrorIncorrectUpdatePropertyCount"/>
<xs:enumeration value="ErrorIndividualMailboxLimitReached"/>
<xs:enumeration value="ErrorInsufficientResources"/>
<xs:enumeration value="ErrorInternalServerError"/>
<xs:enumeration value="ErrorInternalServerTransientError"/>
<xs:enumeration value="ErrorInvalidAccessLevel"/>
<xs:enumeration value="ErrorInvalidArgument"/>
<xs:enumeration value="ErrorInvalidAttachmentId"/>
<xs:enumeration value="ErrorInvalidAttachmentSubfilter"/>
<xs:enumeration value="ErrorInvalidAttachmentSubfilterTextFilter"/>
<xs:enumeration value="ErrorInvalidAuthorizationContext"/>
<xs:enumeration value="ErrorInvalidChangeKey"/>
<xs:enumeration value="ErrorInvalidClientSecurityContext"/>
<xs:enumeration value="ErrorInvalidCompleteDate"/>
<xs:enumeration value="ErrorInvalidContactEmailAddress"/>
<xs:enumeration value="ErrorInvalidContactEmailIndex"/>
<xs:enumeration value="ErrorInvalidCrossForestCredentials"/>
<xs:enumeration value="ErrorInvalidDelegatePermission"/>
<xs:enumeration value="ErrorInvalidDelegateUserId"/>
<xs:enumeration value="ErrorInvalidExcludesRestriction"/>
<xs:enumeration value="ErrorInvalidExpressionTypeForSubFilter"/>
<xs:enumeration value="ErrorInvalidExtendedProperty"/>
<xs:enumeration value="ErrorInvalidExtendedPropertyValue"/>
<xs:enumeration value="ErrorInvalidFolderId"/>
<xs:enumeration value="ErrorInvalidFolderTypeForOperation"/>
<xs:enumeration value="ErrorInvalidFractionalPagingParameters"/>
<xs:enumeration value="ErrorInvalidFreeBusyViewType"/>
<xs:enumeration value="ErrorInvalidId"/>
<xs:enumeration value="ErrorInvalidIdEmpty"/>
<xs:enumeration value="ErrorInvalidIdMalformed"/>
<xs:enumeration value="ErrorInvalidIdMalformedEwsLegacyIdFormat"/>
<xs:enumeration value="ErrorInvalidIdMonikerTooLong"/>
<xs:enumeration value="ErrorInvalidIdNotAnItemAttachmentId"/>
<xs:enumeration value="ErrorInvalidIdReturnedByResolveNames"/>
<xs:enumeration value="ErrorInvalidIdStoreObjectIdTooLong"/>
<xs:enumeration value="ErrorInvalidIdTooManyAttachmentLevels"/>
<xs:enumeration value="ErrorInvalidIdXml"/>
<xs:enumeration value="ErrorInvalidIndexedPagingParameters"/>
<xs:enumeration value="ErrorInvalidInternetHeaderChildNodes"/>
<xs:enumeration value="ErrorInvalidItemForOperationCreateItemAttachment"/>
<xs:enumeration value="ErrorInvalidItemForOperationCreateItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationAcceptItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationDeclineItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationCancelItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationExpandDL"/>
<xs:enumeration value="ErrorInvalidItemForOperationRemoveItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationSendItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationTentative"/>
<xs:enumeration value="ErrorInvalidLogonType"/>
<xs:enumeration value="ErrorInvalidMailbox"/>
<xs:enumeration value="ErrorInvalidManagedFolderProperty"/>
<xs:enumeration value="ErrorInvalidManagedFolderQuota"/>
<xs:enumeration value="ErrorInvalidManagedFolderSize"/>
<xs:enumeration value="ErrorInvalidMergedFreeBusyInterval"/>
<xs:enumeration value="ErrorInvalidNameForNameResolution"/>
<xs:enumeration value="ErrorInvalidOperation"/>
<xs:enumeration value="ErrorInvalidNetworkServiceContext"/>
<xs:enumeration value="ErrorInvalidOofParameter"/>
<xs:enumeration value="ErrorInvalidPagingMaxRows"/>
```

```

<xs:enumeration value="ErrorInvalidParentFolder"/>
<xs:enumeration value="ErrorInvalidPercentCompleteValue"/>
<xs:enumeration value="ErrorInvalidPermissionSettings"/>
<xs:enumeration value="ErrorInvalidPhoneCallId"/>
<xs:enumeration value="ErrorInvalidPhoneNumber"/>
<xs:enumeration value="ErrorInvalidUserInfo"/>
<xs:enumeration value="ErrorInvalidPropertyAppend"/>
<xs:enumeration value="ErrorInvalidPropertyDelete"/>
<xs:enumeration value="ErrorInvalidPropertyForExists"/>
<xs:enumeration value="ErrorInvalidPropertyForOperation"/>
<xs:enumeration value="ErrorInvalidPropertyRequest"/>
<xs:enumeration value="ErrorInvalidPropertySet"/>
<xs:enumeration value="ErrorInvalidPropertyUpdateSendMessage"/>
<xs:enumeration value="ErrorInvalidProxySecurityContext"/>
<xs:enumeration value="ErrorInvalidPullSubscriptionId"/>
<xs:enumeration value="ErrorInvalidPushSubscriptionUrl"/>
<xs:enumeration value="ErrorInvalidRecipients"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilter"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilterComparison"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilterOrder"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilterTextFilter"/>
<xs:enumeration value="ErrorInvalidReferenceItem"/>
<xs:enumeration value="ErrorInvalidRequest"/>
<xs:enumeration value="ErrorInvalidRestriction"/>
<xs:enumeration value="ErrorInvalidRoutingType"/>
<xs:enumeration value="ErrorInvalidScheduledOutOfDuration"/>
<xs:enumeration value="ErrorInvalidSchemaVersionForMailboxVersion"/>
<xs:enumeration value="ErrorInvalidSecurityDescriptor"/>
<xs:enumeration value="ErrorInvalidSendItemSaveSettings"/>
<xs:enumeration value="ErrorInvalidSerializedAccessToken"/>
<xs:enumeration value="ErrorInvalidServerVersion"/>
<xs:enumeration value="ErrorInvalidSid"/>
<xs:enumeration value="ErrorInvalidSIPUri"/>
<xs:enumeration value="ErrorInvalidSmtptAddress"/>
<xs:enumeration value="ErrorInvalidSubfilterType"/>
<xs:enumeration value="ErrorInvalidSubfilterTypeNotAttendeeType"/>
<xs:enumeration value="ErrorInvalidSubfilterTypeNotRecipientType"/>
<xs:enumeration value="ErrorInvalidSubscription"/>
<xs:enumeration value="ErrorInvalidSubscriptionRequest"/>
<xs:enumeration value="ErrorInvalidSyncStateData"/>
<xs:enumeration value="ErrorInvalidTimeInterval"/>
<xs:enumeration value="ErrorInvalidUserOutOfSettings"/>
<xs:enumeration value="ErrorInvalidUserPrincipalName"/>
<xs:enumeration value="ErrorInvalidUserSid"/>
<xs:enumeration value="ErrorInvalidUserSidMissingUPN"/>
<xs:enumeration value="ErrorInvalidValueForProperty"/>
<xs:enumeration value="ErrorInvalidWatermark"/>
<xs:enumeration value="ErrorIPGatewayNotFound"/>
<xs:enumeration value="ErrorIrresolvableConflict"/>
<xs:enumeration value="ErrorItemCorrupt"/>
<xs:enumeration value="ErrorItemNotFound"/>
<xs:enumeration value="ErrorItemPropertyRequestFailed"/>
<xs:enumeration value="ErrorItemSave"/>
<xs:enumeration value="ErrorItemSavePropertyError"/>
<xs:enumeration value="ErrorLegacyMailboxFreeBusyViewTypeNotMerged"/>
<xs:enumeration value="ErrorLocalServerObjectNotFound"/>
<xs:enumeration value="ErrorLogonAsNetworkServiceFailed"/>
<xs:enumeration value="ErrorMailboxConfiguration"/>
<xs:enumeration value="ErrorMailboxDataArrayEmpty"/>

```

```
<xs:enumeration value="ErrorMailboxDataArrayTooBig"/>
<xs:enumeration value="ErrorMailboxLogonFailed"/>
<xs:enumeration value="ErrorMailboxMoveInProgress"/>
<xs:enumeration value="ErrorMailboxStoreUnavailable"/>
<xs:enumeration value="ErrorMailRecipientNotFound"/>
<xs:enumeration value="ErrorMailTipsDisabled"/>
<xs:enumeration value="ErrorManagedFolderAlreadyExists"/>
<xs:enumeration value="ErrorManagedFolderNotFound"/>
<xs:enumeration value="ErrorManagedFoldersRootFailure"/>
<xs:enumeration value="ErrorMeetingSuggestionGenerationFailed"/>
<xs:enumeration value="ErrorMessageDispositionRequired"/>
<xs:enumeration value="ErrorMessageSizeExceeded"/>
<xs:enumeration value="ErrorMimeContentConversionFailed"/>
<xs:enumeration value="ErrorMimeContentInvalid"/>
<xs:enumeration value="ErrorMimeContentInvalidBase64String"/>
<xs:enumeration value="ErrorMissingArgument"/>
<xs:enumeration value="ErrorMissingEmailAddress"/>
<xs:enumeration value="ErrorMissingEmailAddressForManagedFolder"/>
<xs:enumeration value="ErrorMissingInformationEmailAddress"/>
<xs:enumeration value="ErrorMissingInformationReferenceItemId"/>
<xs:enumeration value="ErrorMissingItemForCreateItemAttachment"/>
<xs:enumeration value="ErrorMissingManagedFolderId"/>
<xs:enumeration value="ErrorMissingRecipients"/>
<xs:enumeration value="ErrorMissingUserIdInformation"/>
<xs:enumeration value="ErrorMoreThanOneAccessModeSpecified"/>
<xs:enumeration value="ErrorMoveCopyFailed"/>
<xs:enumeration value="ErrorMoveDistinguishedFolder"/>
<xs:enumeration value="ErrorNameResolutionMultipleResults"/>
<xs:enumeration value="ErrorNameResolutionNoMailbox"/>
<xs:enumeration value="ErrorNameResolutionNoResults"/>
<xs:enumeration value="ErrorNoApplicableProxyCASServersAvailable"/>
<xs:enumeration value="ErrorNoCalendar"/>
<xs:enumeration value="ErrorNoDestinationCASDueToKerberosRequirements"/>
<xs:enumeration value="ErrorNoDestinationCASDueToSSLRequirements"/>
<xs:enumeration value="ErrorNoDestinationCASDueToVersionMismatch"/>
<xs:enumeration value="ErrorNoFolderClassOverride"/>
<xs:enumeration value="ErrorNoFreeBusyAccess"/>
<xs:enumeration value="ErrorNonExistentMailbox"/>
<xs:enumeration value="ErrorNonPrimarySmtptAddress"/>
<xs:enumeration value="ErrorNoPropertyTagForCustomProperties"/>
<xs:enumeration value="ErrorNoPublicFolderReplicaAvailable"/>
<xs:enumeration value="ErrorNoPublicFolderServerAvailable"/>
<xs:enumeration value="ErrorNoRespondingCASInDestinationSite"/>
<xs:enumeration value="ErrorNotDelegate"/>
<xs:enumeration value="ErrorNotEnoughMemory"/>
<xs:enumeration value="ErrorObjectTypeChanged"/>
<xs:enumeration value="ErrorOccurrenceCrossingBoundary"/>
<xs:enumeration value="ErrorOccurrenceTimeSpanTooBig"/>
<xs:enumeration value="ErrorOperationNotAllowedWithPublicFolderRoot"/>
<xs:enumeration value="ErrorParentFolderIdRequired"/>
<xs:enumeration value="ErrorParentFolderNotFound"/>
<xs:enumeration value="ErrorPasswordChangeRequired"/>
<xs:enumeration value="ErrorPasswordExpired"/>
<xs:enumeration value="ErrorPhoneNumberNotDialable"/>
<xs:enumeration value="ErrorPropertyUpdate"/>
<xs:enumeration value="ErrorPropertyValidationFailure"/>
<xs:enumeration value="ErrorProxiedSubscriptionCallFailure"/>
<xs:enumeration value="ErrorProxyCallFailed"/>
<xs:enumeration value="ErrorProxyGroupSidLimitExceeded"/>
```

```
<xs:enumeration value="ErrorProxyRequestNotAllowed"/>
<xs:enumeration value="ErrorProxyRequestProcessingFailed"/>
<xs:enumeration value="ErrorProxyServiceDiscoveryFailed"/>
<xs:enumeration value="ErrorProxyTokenExpired"/>
<xs:enumeration value="ErrorPublicFolderRequestProcessingFailed"/>
<xs:enumeration value="ErrorPublicFolderServerNotFound"/>
<xs:enumeration value="ErrorQueryFilterTooLong"/>
<xs:enumeration value="ErrorQuotaExceeded"/>
<xs:enumeration value="ErrorReadEventsFailed"/>
<xs:enumeration value="ErrorReadReceiptNotPending"/>
<xs:enumeration value="ErrorRecurrenceEndDateTooBig"/>
<xs:enumeration value="ErrorRecurrenceHasNoOccurrence"/>
<xs:enumeration value="ErrorRemoveDelegatesFailed"/>
<xs:enumeration value="ErrorRequestAborted"/>
<xs:enumeration value="ErrorRequestStreamTooBig"/>
<xs:enumeration value="ErrorRequiredPropertyMissing"/>
<xs:enumeration value="ErrorResolveNamesInvalidFolderType"/>
<xs:enumeration value="ErrorResolveNamesOnlyOneContactsFolderAllowed"/>
<xs:enumeration value="ErrorResponseSchemaValidation"/>
<xs:enumeration value="ErrorRestrictionTooLong"/>
<xs:enumeration value="ErrorRestrictionTooComplex"/>
<xs:enumeration value="ErrorResultSetTooBig"/>
<xs:enumeration value="ErrorInvalidExchangeImpersonationHeaderData"/>
<xs:enumeration value="ErrorSavedItemFolderNotFound"/>
<xs:enumeration value="ErrorSchemaValidation"/>
<xs:enumeration value="ErrorSearchFolderNotInitialized"/>
<xs:enumeration value="ErrorSendAsDenied"/>
<xs:enumeration value="ErrorSendMeetingCancellationsRequired"/>
<xs:enumeration value="ErrorSendMeetingInvitationsOrCancellationsRequired"/>
<xs:enumeration value="ErrorSendMeetingInvitationsRequired"/>
<xs:enumeration value="ErrorSentMeetingRequestUpdate"/>
<xs:enumeration value="ErrorSentTaskRequestUpdate"/>
<xs:enumeration value="ErrorServerBusy"/>
<xs:enumeration value="ErrorServiceDiscoveryFailed"/>
<xs:enumeration value="ErrorStaleObject"/>
<xs:enumeration value="ErrorSubmissionQuotaExceeded"/>
<xs:enumeration value="ErrorSubscriptionAccessDenied"/>
<xs:enumeration value="ErrorSubscriptionDelegateAccessNotSupported"/>
<xs:enumeration value="ErrorSubscriptionNotFound"/>
<xs:enumeration value="ErrorSubscriptionUnsubscribed"/>
<xs:enumeration value="ErrorSyncFolderNotFound"/>
<xs:enumeration value="ErrorTimeIntervalTooBig"/>
<xs:enumeration value="ErrorTimeoutExpired"/>
<xs:enumeration value="ErrorTimeZone"/>
<xs:enumeration value="ErrorToFolderNotFound"/>
<xs:enumeration value="ErrorTokenSerializationDenied"/>
<xs:enumeration value="ErrorUpdatePropertyMismatch"/>
<xs:enumeration value="ErrorUnifiedMessagingDialPlanNotFound"/>
<xs:enumeration value="ErrorUnifiedMessagingRequestFailed"/>
<xs:enumeration value="ErrorUnifiedMessagingServerNotFound"/>
<xs:enumeration value="ErrorUnableToGetUserOutOfSettings"/>
<xs:enumeration value="ErrorUnsupportedSubFilter"/>
<xs:enumeration value="ErrorUnsupportedCulture"/>
<xs:enumeration value="ErrorUnsupportedMapiPropertyType"/>
<xs:enumeration value="ErrorUnsupportedMimeConversion"/>
<xs:enumeration value="ErrorUnsupportedPathForQuery"/>
<xs:enumeration value="ErrorUnsupportedPathForSortGroup"/>
<xs:enumeration value="ErrorUnsupportedPropertyDefinition"/>
<xs:enumeration value="ErrorUnsupportedQueryFilter"/>
```



```

<xs:enumeration value="ErrorUnsupportedRecurrence"/>
<xs:enumeration value="ErrorUnsupportedTypeForConversion"/>
<xs:enumeration value="ErrorUpdateDelegatesFailed"/>
<xs:enumeration value="ErrorUserNotUnifiedMessagingEnabled"/>
<xs:enumeration value="ErrorVoiceMailNotImplemented"/>
<xs:enumeration value="ErrorValueOutOfRange"/>
<xs:enumeration value="ErrorVirusDetected"/>
<xs:enumeration value="ErrorVirusMessageDeleted"/>
<xs:enumeration value="ErrorWebRequestInInvalidState"/>
<xs:enumeration value="ErrorWin32InteropError"/>
<xs:enumeration value="ErrorWorkingHoursSaveFailed"/>
<xs:enumeration value="ErrorWorkingHoursXmlMalformed"/>
<xs:enumeration value="ErrorWrongServerVersion"/>
<xs:enumeration value="ErrorWrongServerVersionDelegate"/>
<xs:enumeration value="ErrorMissingInformationSharingFolderId"/>
<xs:enumeration value="ErrorDuplicateSOAPHeader"/>
<xs:enumeration value="ErrorSharingSynchronizationFailed"/>
<xs:enumeration value="ErrorSharingNoExternalEwsAvailable"/>
<xs:enumeration value="ErrorFreeBusyDLLimitReached"/>
<xs:enumeration value="ErrorInvalidGetSharingFolderRequest"/>
<xs:enumeration value="ErrorNotAllowedExternalSharingByPolicy"/>
<xs:enumeration value="ErrorUserNotAllowedByPolicy"/>
<xs:enumeration value="ErrorPermissionNotAllowedByPolicy"/>
<xs:enumeration value="ErrorOrganizationNotFederated"/>
<xs:enumeration value="ErrorMailboxFailover"/>
<xs:enumeration value="ErrorInvalidExternalSharingInitiator"/>
<xs:enumeration value="ErrorMessageTrackingPermanentError"/>
<xs:enumeration value="ErrorMessageTrackingTransientError"/>
<xs:enumeration value="ErrorMessageTrackingNoSuchDomain"/>
<xs:enumeration value="ErrorUserWithoutFederatedProxyAddress"/>
<xs:enumeration value="ErrorInvalidOrganizationRelationshipForFreeBusy"/>
<xs:enumeration value="ErrorInvalidFederatedOrganizationId"/>
<xs:enumeration value="ErrorInvalidExternalSharingSubscriber"/>
<xs:enumeration value="ErrorInvalidSharingData"/>
<xs:enumeration value="ErrorInvalidSharingMessage"/>
<xs:enumeration value="ErrorNotSupportedSharingMessage"/>
<xs:enumeration value="ErrorApplyConversationActionFailed"/>
<xs:enumeration value="ErrorInboxRulesValidationError"/>
<xs:enumeration value="ErrorOutlookRuleBlobExists"/>
<xs:enumeration value="ErrorRulesOverQuota"/>
<xs:enumeration value="ErrorNewEventStreamConnectionOpened"/>
<xs:enumeration value="ErrorMissedNotificationEvents"/>
</xs:restriction>
</xs:simpleType>
</xs:schema>

```

7.2 Types Schema

This section provides the contents of the MS-OXWSCDATA-types.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSCDATA-types.xsd includes or imports the files listed in the following table. To operate correctly, these files have to be present in the folder that contains the types and messages schema files.

File name	Defining specification
MS-OXWSMSG-types.xsd	[MS-OXWSMSG] section 7.1
MS-OXWSFOLD-types.xsd	[MS-OXWSFOLD] section 7.2
MS-OXWSATT-types.xsd	[MS-OXWSATT] section 7.2.
MS-OXWSDLIST-types.xsd	[MS-OXWSDLIST] section 6.2.
MS-OXWSTASK-types.xsd	[MS-OXWSTASK] section 7.2.

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
           xmlns:xs="http://www.w3.org/2001/XMLSchema"

targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
           elementFormDefault="qualified"
           version="Exchange2010_SP1"
           id="types">
  <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
  <xs:include schemaLocation="MS-OXWSMSG-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSFOLD-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSATT-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSDLIST-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSTASK-types.xsd"/>
  <xs:complexType name="AbsoluteMonthlyRecurrencePatternType">
    <xs:complexContent>
      <xs:extension base="t:IntervalRecurrencePatternBaseType">
        <xs:sequence>
          <xs:element name="DayOfMonth" type="xs:int"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="AbsoluteYearlyRecurrencePatternType">
    <xs:complexContent>
      <xs:extension base="t:RecurrencePatternBaseType">
        <xs:sequence>
          <xs:element name="DayOfMonth" type="xs:int"/>
          <xs:element name="Month" type="t:MonthNamesType"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="AcceptSharingInvitationType">
    <xs:complexContent>
      <xs:extension base="t:ReferenceItemResponseType"/>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="ArrayOfCalendarPermissionsType">
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="CalendarPermission" type="t:CalendarPermissionType"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="ArrayOfEmailAddressesType">
    <xs:sequence>
      <xs:element name="Address" type="t:EmailAddressType" minOccurs="0"
maxOccurs="unbounded"/>
    </xs:sequence>

```

```

</xs:complexType>
<xs:complexType name="ArrayOfPermissionsType">
  <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element name="Permission" type="t:PermissionType"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="ArrayOfRealItemsType">
  <xs:sequence>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="Item" type="t:ItemType"/>
      <xs:element name="Message" type="t:MessageType"/>
      <xs:element name="CalendarItem" type="t:CalendarItemType"/>
      <xs:element name="Contact" type="t:ContactItemType"/>
      <xs:element name="DistributionList" type="t:DistributionListType"/>
      <xs:element name="MeetingMessage" type="t:MeetingMessageType"/>
      <xs:element name="MeetingRequest" type="t:MeetingRequestMessageType"/>
      <xs:element name="MeetingResponse" type="t:MeetingResponseMessageType"/>
      <xs:element name="MeetingCancellation" type="t:MeetingCancellationMessageType"/>
      <xs:element name="Task" type="t:TaskType"/>
      <xs:element name="PostItem" type="t:PostItemType"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfRecipientsType">
  <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element name="Mailbox" type="t:EmailAddressType"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="ArrayOfStringsType">
  <xs:sequence>
    <xs:element name="String" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="BaseEmailAddressType"/>
<xs:complexType name="BaseItemIdType" abstract="true"/>
<xs:complexType name="BasePathToElementType" abstract="true"/>
<xs:complexType name="BodyType">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="BodyType" type="t:BodyTypeType" use="required"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="BodyTypeResponseType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Best"/>
    <xs:enumeration value="HTML"/>
    <xs:enumeration value="Text"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="BodyTypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="HTML"/>
    <xs:enumeration value="Text"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="ConnectingSIDType">
  <xs:choice>
    <xs:element name="PrincipalName" type="t:NonEmptyStringType"/>
  </xs:choice>

```

```

    <xs:element name="SID" type="t:NonEmptyStringType"/>
    <xs:element name="PrimarySmtpAddress" type="t:NonEmptyStringType"/>
    <xs:element name="SmtpAddress" type="t:NonEmptyStringType"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="ConstantValueType">
  <xs:attribute name="Value" type="xs:string" use="required"/>
</xs:complexType>
<xs:complexType name="DailyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension base="t:IntervalRecurrencePatternBaseType"/>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="DayOfWeekIndexType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="First"/>
    <xs:enumeration value="Second"/>
    <xs:enumeration value="Third"/>
    <xs:enumeration value="Fourth"/>
    <xs:enumeration value="Last"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DayOfWeekType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Sunday"/>
    <xs:enumeration value="Monday"/>
    <xs:enumeration value="Tuesday"/>
    <xs:enumeration value="Wednesday"/>
    <xs:enumeration value="Thursday"/>
    <xs:enumeration value="Friday"/>
    <xs:enumeration value="Saturday"/>
    <xs:enumeration value="Day"/>
    <xs:enumeration value="Weekday"/>
    <xs:enumeration value="WeekendDay"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DaysOfWeekType">
  <xs:list itemType="t:DayOfWeekType"/>
</xs:simpleType>
<xs:simpleType name="DefaultShapeNamesType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="IdOnly"/>
    <xs:enumeration value="Default"/>
    <xs:enumeration value="AllProperties"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="DeletedOccurrenceInfoType">
  <xs:sequence>
    <xs:element name="Start" type="xs:dateTime"/>
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="DictionaryURIType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="item:InternetMessageHeader"/>
    <xs:enumeration value="contacts:ImAddress"/>
    <xs:enumeration value="contacts:PhysicalAddress:Street"/>
    <xs:enumeration value="contacts:PhysicalAddress:City"/>
    <xs:enumeration value="contacts:PhysicalAddress:State"/>
    <xs:enumeration value="contacts:PhysicalAddress:CountryOrRegion"/>
  </xs:restriction>
</xs:simpleType>

```

```

    <xs:enumeration value="contacts:PhysicalAddress:PostalCode"/>
    <xs:enumeration value="contacts:PhoneNumber"/>
    <xs:enumeration value="contacts:EmailAddress"/>
    <xs:enumeration value="distributionlist:Members:Member"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DisposalType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="HardDelete"/>
    <xs:enumeration value="SoftDelete"/>
    <xs:enumeration value="MoveToDeletedItems"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DistinguishedFolderIdNameType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="calendar"/>
    <xs:enumeration value="contacts"/>
    <xs:enumeration value="deleteditems"/>
    <xs:enumeration value="drafts"/>
    <xs:enumeration value="inbox"/>
    <xs:enumeration value="journal"/>
    <xs:enumeration value="notes"/>
    <xs:enumeration value="outbox"/>
    <xs:enumeration value="sentitems"/>
    <xs:enumeration value="tasks"/>
    <xs:enumeration value="msgfolderroot"/>
    <xs:enumeration value="publicfoldersroot"/>
    <xs:enumeration value="root"/>
    <xs:enumeration value="junkemail"/>
    <xs:enumeration value="searchfolders"/>
    <xs:enumeration value="voicemail"/>
    <xs:enumeration value="recoverableitemsroot" />
    <xs:enumeration value="recoverableitemsdeletions" />
    <xs:enumeration value="recoverableitemsversions" />
    <xs:enumeration value="recoverableitemspurges" />
    <xs:enumeration value="archiveroot" />
    <xs:enumeration value="archivemsgfolderroot" />
    <xs:enumeration value="archivedeleteditems" />
    <xs:enumeration value="archiverecoverableitemsroot" />
    <xs:enumeration value="archiverecoverableitemsdeletions" />
    <xs:enumeration value="archiverecoverableitemsversions" />
    <xs:enumeration value="archiverecoverableitemspurges" />
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="DistinguishedFolderIdType">
  <xs:complexContent>
    <xs:extension base="t:BaseFolderIdType">
      <xs:sequence>
        <xs:element name="Mailbox" type="t:EmailAddressType" minOccurs="0"/>
      </xs:sequence>
      <xs:attribute name="Id" type="t:DistinguishedFolderIdNameType" use="required"/>
      <xs:attribute name="ChangeKey" type="xs:string" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="DistinguishedPropertySetType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Meeting"/>
    <xs:enumeration value="Appointment"/>
  </xs:restriction>

```

```

    <xs:enumeration value="Common"/>
    <xs:enumeration value="PublicStrings"/>
    <xs:enumeration value="Address"/>
    <xs:enumeration value="InternetHeaders"/>
    <xs:enumeration value="CalendarAssistant"/>
    <xs:enumeration value="UnifiedMessaging"/>
    <xs:enumeration value="Task"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DistinguishedUserType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default"/>
    <xs:enumeration value="Anonymous"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="Duration">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="StartTime" type="xs:dateTime"/>
    <xs:element minOccurs="1" maxOccurs="1" name="EndTime" type="xs:dateTime"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="EffectiveRightsType">
  <xs:sequence>
    <xs:element name="CreateAssociated" type="xs:boolean"/>
    <xs:element name="CreateContents" type="xs:boolean"/>
    <xs:element name="CreateHierarchy" type="xs:boolean"/>
    <xs:element name="Delete" type="xs:boolean"/>
    <xs:element name="Modify" type="xs:boolean"/>
    <xs:element name="Read" type="xs:boolean"/>
    <xs:element name="ViewPrivateItems" type="xs:boolean" minOccurs="0" maxOccurs="1" />
  </xs:sequence>
</xs:complexType>
<xs:complexType name="EmailAddress">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Address" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="RoutingType" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="EmailAddressType">
  <xs:complexContent>
    <xs:extension base="t:BaseEmailAddressType">
      <xs:sequence>
        <xs:element name="Name" type="xs:string" minOccurs="0"/>
        <xs:element name="EmailAddress" type="t:NonEmptyStringType" minOccurs="0"/>
        <xs:element name="RoutingType" type="t:NonEmptyStringType" minOccurs="0"/>
        <xs:element name="MailboxType" type="t:MailboxTypeType" minOccurs="0"/>
        <xs:element name="ItemId" type="t:ItemIdType" minOccurs="0"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="EndDateRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension base="t:RecurrenceRangeBaseType">
      <xs:sequence>
        <xs:element name="EndDate" type="xs:date"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

```

    </xs:complexContent>
</xs:complexType>
<xs:element name="ExceptionFieldURI" type="t:PathToExceptionFieldType"/>
<xs:simpleType name="ExceptionPropertyURIType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="attachment:Name"/>
    <xs:enumeration value="attachment:ContentType"/>
    <xs:enumeration value="attachment:Content"/>
    <xs:enumeration value="recurrence:Month"/>
    <xs:enumeration value="recurrence:DayOfWeekIndex"/>
    <xs:enumeration value="recurrence:DaysOfWeek"/>
    <xs:enumeration value="recurrence:DayOfMonth"/>
    <xs:enumeration value="recurrence:Interval"/>
    <xs:enumeration value="recurrence:NumberOfOccurrences"/>
    <xs:enumeration value="timezone:Offset"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="ExchangeImpersonationType">
  <xs:sequence>
    <xs:element name="ConnectingSID" type="t:ConnectingSIDType"/>
  </xs:sequence>
  <xs:anyAttribute namespace="http://schemas.xmlsoap.org/soap/envelope/" />
</xs:complexType>
<xs:element name="ExchangeImpersonation" type="t:ExchangeImpersonationType"/>
<xs:simpleType name="ExchangeVersionType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Exchange2007"/>
    <xs:enumeration value="Exchange2007_SP1"/>
    <xs:enumeration value="Exchange2010"/>
    <xs:enumeration value="Exchange2010_SP1"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ExcludesAttributeType">
  <xs:restriction base="xs:string">
    <xs:pattern value="( (0x|0X) [0-9A-Fa-f] * ) | ( [0-9] * ) "/>
  </xs:restriction>
</xs:simpleType>
<xs:element name="FieldURI" type="t:PathToUnindexedFieldType" substitutionGroup="t:Path"/>
<xs:complexType name="FieldURIOrConstantType">
  <xs:choice>
    <xs:element ref="t:Path"/>
    <xs:element name="Constant" type="t:ConstantValueType"/>
  </xs:choice>
</xs:complexType>
<xs:attributeGroup name="FindResponsePagingAttributes">
  <xs:attribute name="IndexedPagingOffset" type="xs:int" use="optional"/>
  <xs:attribute name="NumeratorOffset" type="xs:int" use="optional"/>
  <xs:attribute name="AbsoluteDenominator" type="xs:int" use="optional"/>
  <xs:attribute name="IncludesLastItemInRange" type="xs:boolean" use="optional"/>
  <xs:attribute name="TotalItemsInView" type="xs:int" use="optional"/>
</xs:attributeGroup>
<xs:complexType name="FolderIdType">
  <xs:complexContent>
    <xs:extension base="t:BaseFolderIdType">
      <xs:attribute name="Id" type="xs:string" use="required"/>
      <xs:attribute name="ChangeKey" type="xs:string" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

```

<xs:complexType name="FolderResponseShapeType">
  <xs:sequence>
    <xs:element name="BaseShape" type="t:DefaultShapeNamesType"/>
    <xs:element name="AdditionalProperties" type="t:NonEmptyArrayOfPathsToElementType"
minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ForwardItemType">
  <xs:complexContent>
    <xs:extension base="t:SmartResponseType"/>
  </xs:complexContent>
</xs:complexType>
<xs:element name="IndexedFieldURI" type="t:PathToIndexedFieldType"
substitutionGroup="t:Path"/>
<xs:complexType name="InternetHeaderType">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="HeaderName" type="xs:string" use="required"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:complexType name="IntervalRecurrencePatternBaseType" abstract="true">
  <xs:complexContent>
    <xs:extension base="t:RecurrencePatternBaseType">
      <xs:sequence>
        <xs:element name="Interval" type="xs:int"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="ItemResponseShapeType">
  <xs:sequence>
    <xs:element name="BaseShape" type="t:DefaultShapeNamesType"/>
    <xs:element name="IncludeMimeContent" type="xs:boolean" minOccurs="0"/>
    <xs:element name="BodyType" type="t:BodyTypeResponseType" minOccurs="0"/>
    <xs:element name="FilterHtmlContent" type="xs:boolean" minOccurs="0"/>
    <xs:element name="ConvertHtmlCodePageToUTF8" type="xs:boolean" minOccurs="0"
maxOccurs="1"/>
    <xs:element name="AdditionalProperties" type="t:NonEmptyArrayOfPathsToElementType"
minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="LegacyFreeBusyType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Free"/>
    <xs:enumeration value="Tentative"/>
    <xs:enumeration value="Busy"/>
    <xs:enumeration value="OOO"/>
    <xs:enumeration value="NoData"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="MailboxCultureType">
  <xs:simpleContent>
    <xs:extension base="xs:language">
      <xs:anyAttribute namespace="http://schemas.xmlsoap.org/soap/envelope"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:element name="MailboxCulture" type="t:MailboxCultureType"/>

```



```

<xs:simpleType name="MailboxTypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown"/>
    <xs:enumeration value="OneOff"/>
    <xs:enumeration value="Mailbox"/>
    <xs:enumeration value="PublicDL"/>
    <xs:enumeration value="PrivateDL"/>
    <xs:enumeration value="Contact"/>
    <xs:enumeration value="PublicFolder"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="MonthNamesType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="January"/>
    <xs:enumeration value="February"/>
    <xs:enumeration value="March"/>
    <xs:enumeration value="April"/>
    <xs:enumeration value="May"/>
    <xs:enumeration value="June"/>
    <xs:enumeration value="July"/>
    <xs:enumeration value="August"/>
    <xs:enumeration value="September"/>
    <xs:enumeration value="October"/>
    <xs:enumeration value="November"/>
    <xs:enumeration value="December"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="NoEndRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension base="t:RecurrenceRangeBaseType"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfAllItemsType">
  <xs:sequence>
    <xs:choice maxOccurs="unbounded">
      <xs:element name="Item" type="t:ItemType"/>
      <xs:element name="Message" type="t:MessageType"/>
      <xs:element name="CalendarItem" type="t:CalendarItemType"/>
      <xs:element name="Contact" type="t:ContactItemType"/>
      <xs:element name="DistributionList" type="t:DistributionListType"/>
      <xs:element name="MeetingMessage" type="t:MeetingMessageType"/>
      <xs:element name="MeetingRequest" type="t:MeetingRequestMessageType"/>
      <xs:element name="MeetingResponse" type="t:MeetingResponseMessageType"/>
      <xs:element name="MeetingCancellation" type="t:MeetingCancellationMessageType"/>
      <xs:element name="Task" type="t:TaskType"/>
      <xs:element name="PostItem" type="t:PostItemType"/>
      <xs:element name="ReplyToItem" type="t:ReplyToItemType"/>
      <xs:element name="ForwardItem" type="t:ForwardItemType"/>
      <xs:element name="ReplyAllToItem" type="t:ReplyAllToItemType"/>
      <xs:element name="AcceptItem" type="t:AcceptItemType"/>
      <xs:element name="TentativelyAcceptItem" type="t:TentativelyAcceptItemType"/>
      <xs:element name="DeclineItem" type="t:DeclineItemType"/>
      <xs:element name="CancelCalendarItem" type="t:CancelCalendarItemType"/>
      <xs:element name="RemoveItem" type="t:RemoveItemType"/>
      <xs:element name="SuppressReadReceipt" type="t:SuppressReadReceiptType"/>
      <xs:element name="PostReplyItem" type="t:PostReplyItemType"/>
      <xs:element name="AcceptSharingInvitation" type="t:AcceptSharingInvitationType"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>

```

```

</xs:complexType>
<xs:complexType name="NonEmptyArrayOfAttachmentsType">
  <xs:choice maxOccurs="unbounded">
    <xs:element name="ItemAttachment" type="t:ItemAttachmentType"/>
    <xs:element name="FileAttachment" type="t:FileAttachmentType"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfPathsToElementType">
  <xs:choice maxOccurs="unbounded">
    <xs:element ref="t:Path"/>
  </xs:choice>
</xs:complexType>
<xs:simpleType name="NonEmptyStringType">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="NumberedRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension base="t:RecurrenceRangeBaseType">
      <xs:sequence>
        <xs:element name="NumberOfOccurrences" type="xs:int"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="Path" type="t:BasePathToElementType" abstract="true"/>
<xs:complexType name="PathToExceptionFieldType">
  <xs:complexContent>
    <xs:extension base="t:BasePathToElementType">
      <xs:attribute name="FieldURI" type="t:ExceptionPropertyURIType" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="PathToIndexedFieldType">
  <xs:complexContent>
    <xs:extension base="t:BasePathToElementType">
      <xs:attribute name="FieldURI" type="t:DictionaryURIType" use="required"/>
      <xs:attribute name="FieldIndex" type="xs:string" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="PathToUnindexedFieldType">
  <xs:complexContent>
    <xs:extension base="t:BasePathToElementType">
      <xs:attribute name="FieldURI" type="t:UnindexedFieldURIType" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="RecurrencePatternBaseType" abstract="true"/>
<xs:group name="RecurrencePatternTypes">
  <xs:sequence>
    <xs:choice>
      <xs:element name="RelativeYearlyRecurrence"
type="t:RelativeYearlyRecurrencePatternType"/>
      <xs:element name="AbsoluteYearlyRecurrence"
type="t:AbsoluteYearlyRecurrencePatternType"/>
      <xs:element name="RelativeMonthlyRecurrence"
type="t:RelativeMonthlyRecurrencePatternType"/>
    </xs:choice>
  </xs:sequence>
</xs:group>

```

```

        <xs:element name="AbsoluteMonthlyRecurrence"
type="t:AbsoluteMonthlyRecurrencePatternType"/>
        <xs:element name="WeeklyRecurrence" type="t:WeeklyRecurrencePatternType"/>
        <xs:element name="DailyRecurrence" type="t:DailyRecurrencePatternType"/>
    </xs:choice>
</xs:sequence>
</xs:group>
<xs:complexType name="RecurrenceRangeBaseType" abstract="true">
    <xs:sequence>
        <xs:element name="StartDate" type="xs:date"/>
    </xs:sequence>
</xs:complexType>
<xs:group name="RecurrenceRangeTypes">
    <xs:sequence>
        <xs:choice>
            <xs:element name="NoEndRecurrence" type="t:NoEndRecurrenceRangeType"/>
            <xs:element name="EndDateRecurrence" type="t:EndDateRecurrenceRangeType"/>
            <xs:element name="NumberedRecurrence" type="t:NumberedRecurrenceRangeType"/>
        </xs:choice>
    </xs:sequence>
</xs:group>
<xs:complexType name="RelativeMonthlyRecurrencePatternType">
    <xs:complexContent>
        <xs:extension base="t:IntervalRecurrencePatternBaseType">
            <xs:sequence>
                <xs:element name="DaysOfWeek" type="t:DayOfWeekType"/>
                <xs:element name="DayOfWeekIndex" type="t:DayOfWeekIndexType"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="RelativeYearlyRecurrencePatternType">
    <xs:complexContent>
        <xs:extension base="t:RecurrencePatternBaseType">
            <xs:sequence>
                <xs:element name="DaysOfWeek" type="t:DayOfWeekType"/>
                <xs:element name="DayOfWeekIndex" type="t:DayOfWeekIndexType"/>
                <xs:element name="Month" type="t:MonthNamesType"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ReplyAllToItemType">
    <xs:complexContent>
        <xs:extension base="t:SmartResponseType"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ReplyBody">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Message" type="xs:string"/>
    </xs:sequence>
    <xs:attribute ref="xml:lang" use="optional"/>
</xs:complexType>
<xs:complexType name="ReplyToItemType">
    <xs:complexContent>
        <xs:extension base="t:SmartResponseType"/>
    </xs:complexContent>
</xs:complexType>
<xs:element name="RequestServerVersion">

```

```

    <xs:complexType>
      <xs:attribute name="Version" type="t:ExchangeVersionType" use="required"
fixed="Exchange2010_SP1"/>
      <xs:anyAttribute namespace="http://schemas.xmlsoap.org/soap/envelope/" />
    </xs:complexType>
  </xs:element>
  <xs:simpleType name="ResponseClassType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Success"/>
      <xs:enumeration value="Warning"/>
      <xs:enumeration value="Error"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="ResponseObjectCoreType" abstract="true">
    <xs:complexContent>
      <xs:extension base="t:MessageType">
        <xs:sequence>
          <xs:element name="ReferenceItemId" type="t:ItemIdType" minOccurs="0"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="ResponseObjectType" abstract="true">
    <xs:complexContent>
      <xs:extension base="t:ResponseObjectCoreType">
        <xs:attribute name="ObjectName" type="xs:string" use="optional"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:simpleType name="SensitivityChoicesType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Normal"/>
      <xs:enumeration value="Personal"/>
      <xs:enumeration value="Private"/>
      <xs:enumeration value="Confidential"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="ServerVersionInfo">
    <xs:complexType>
      <xs:attribute name="MajorVersion" type="xs:int" use="optional"/>
      <xs:attribute name="MinorVersion" type="xs:int" use="optional"/>
      <xs:attribute name="MajorBuildNumber" type="xs:int" use="optional"/>
      <xs:attribute name="MinorBuildNumber" type="xs:int" use="optional"/>
      <xs:attribute name="Version" type="xs:string" use="optional"/>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="SingleRecipientType">
    <xs:choice>
      <xs:element name="Mailbox" type="t:EmailAddressType"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="SuppressReadReceiptType">
    <xs:complexContent>
      <xs:extension base="t:ReferenceItemResponseType"/>
    </xs:complexContent>
  </xs:complexType>
  <xs:group name="TaskRecurrencePatternTypes">
    <xs:sequence>
      <xs:choice>

```

```

        <xs:element name="RelativeYearlyRecurrence"
type="t:RelativeYearlyRecurrencePatternType"/>
        <xs:element name="AbsoluteYearlyRecurrence"
type="t:AbsoluteYearlyRecurrencePatternType"/>
        <xs:element name="RelativeMonthlyRecurrence"
type="t:RelativeMonthlyRecurrencePatternType"/>
        <xs:element name="AbsoluteMonthlyRecurrence"
type="t:AbsoluteMonthlyRecurrencePatternType"/>
        <xs:element name="WeeklyRecurrence" type="t:WeeklyRecurrencePatternType"/>
        <xs:element name="DailyRecurrence" type="t:DailyRecurrencePatternType"/>
        <xs:element name="DailyRegeneration" type="t:DailyRegeneratingPatternType"/>
        <xs:element name="WeeklyRegeneration" type="t:WeeklyRegeneratingPatternType"/>
        <xs:element name="MonthlyRegeneration" type="t:MonthlyRegeneratingPatternType"/>
        <xs:element name="YearlyRegeneration" type="t:YearlyRegeneratingPatternType"/>
    </xs:choice>
</xs:sequence>
</xs:group>
<xs:group name="TimeChangePatternTypes">
    <xs:sequence>
        <xs:choice>
            <xs:element name="RelativeYearlyRecurrence"
type="t:RelativeYearlyRecurrencePatternType"/>
            <xs:element name="AbsoluteDate" type="xs:date"/>
        </xs:choice>
    </xs:sequence>
</xs:group>
<xs:simpleType name="UnindexedFieldURIType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="folder:FolderId"/>
        <xs:enumeration value="folder:ParentFolderId"/>
        <xs:enumeration value="folder:DisplayName"/>
        <xs:enumeration value="folder:UnreadCount"/>
        <xs:enumeration value="folder:TotalCount"/>
        <xs:enumeration value="folder:ChildFolderCount"/>
        <xs:enumeration value="folder:FolderClass"/>
        <xs:enumeration value="folder:SearchParameters"/>
        <xs:enumeration value="folder:ManagedFolderInformation"/>
        <xs:enumeration value="folder:PermissionSet"/>
        <xs:enumeration value="folder:EffectiveRights"/>
        <xs:enumeration value="folder:SharingEffectiveRights"/>
        <xs:enumeration value="item:ItemId"/>
        <xs:enumeration value="item:ParentFolderId"/>
        <xs:enumeration value="item:ItemClass"/>
        <xs:enumeration value="item:MimeContent"/>
        <xs:enumeration value="item:Attachments"/>
        <xs:enumeration value="item:Subject"/>
        <xs:enumeration value="item:DateTimeReceived"/>
        <xs:enumeration value="item:Size"/>
        <xs:enumeration value="item:Categories"/>
        <xs:enumeration value="item:HasAttachments"/>
        <xs:enumeration value="item:Importance"/>
        <xs:enumeration value="item:InReplyTo"/>
        <xs:enumeration value="item:InternetMessageHeaders"/>
        <xs:enumeration value="item:IsAssociated"/>
        <xs:enumeration value="item:IsDraft"/>
        <xs:enumeration value="item:IsFromMe"/>
        <xs:enumeration value="item:IsResend"/>
        <xs:enumeration value="item:IsSubmitted"/>
        <xs:enumeration value="item:IsUnmodified"/>
    </xs:restriction>
</xs:simpleType>

```

```

<xs:enumeration value="item:DateTimeSent"/>
<xs:enumeration value="item:DateTimeCreated"/>
<xs:enumeration value="item:Body"/>
<xs:enumeration value="item:ResponseObjects"/>
<xs:enumeration value="item:Sensitivity"/>
<xs:enumeration value="item:ReminderDueBy"/>
<xs:enumeration value="item:ReminderIsSet"/>
<xs:enumeration value="item:ReminderMinutesBeforeStart"/>
<xs:enumeration value="item:DisplayTo"/>
<xs:enumeration value="item:DisplayCc"/>
<xs:enumeration value="item:Culture"/>
<xs:enumeration value="item:EffectiveRights"/>
<xs:enumeration value="item:LastModifiedName"/>
<xs:enumeration value="item:LastModifiedTime"/>
<xs:enumeration value="item:ConversationId"/>
<xs:enumeration value="item:UniqueBody"/>
<xs:enumeration value="item:WebClientReadFormQueryString"/>
<xs:enumeration value="item:WebClientEditFormQueryString"/>
<xs:enumeration value="message:ConversationIndex"/>
<xs:enumeration value="message:ConversationTopic"/>
<xs:enumeration value="message:InternetMessageId"/>
<xs:enumeration value="message:IsRead"/>
<xs:enumeration value="message:IsResponseRequested"/>
<xs:enumeration value="message:IsReadReceiptRequested"/>
<xs:enumeration value="message:IsDeliveryReceiptRequested"/>
<xs:enumeration value="message:ReceivedBy"/>
<xs:enumeration value="message:ReceivedRepresenting"/>
<xs:enumeration value="message:References"/>
<xs:enumeration value="message:ReplyTo"/>
<xs:enumeration value="message:From"/>
<xs:enumeration value="message:Sender"/>
<xs:enumeration value="message:ToRecipients"/>
<xs:enumeration value="message:CcRecipients"/>
<xs:enumeration value="message:BccRecipients"/>
<xs:enumeration value="meeting:AssociatedCalendarItemId"/>
<xs:enumeration value="meeting:IsDelegated"/>
<xs:enumeration value="meeting:IsOutOfDate"/>
<xs:enumeration value="meeting:HasBeenProcessed"/>
<xs:enumeration value="meeting:ResponseType"/>
<xs:enumeration value="meetingRequest:MeetingRequestType"/>
<xs:enumeration value="meetingRequest:IntendedFreeBusyStatus"/>
<xs:enumeration value="calendar:Start"/>
<xs:enumeration value="calendar:End"/>
<xs:enumeration value="calendar:OriginalStart"/>
<xs:enumeration value="calendar:IsAllDayEvent"/>
<xs:enumeration value="calendar:LegacyFreeBusyStatus"/>
<xs:enumeration value="calendar:Location"/>
<xs:enumeration value="calendar:When"/>
<xs:enumeration value="calendar:IsMeeting"/>
<xs:enumeration value="calendar:IsCancelled"/>
<xs:enumeration value="calendar:IsRecurring"/>
<xs:enumeration value="calendar:MeetingRequestWasSent"/>
<xs:enumeration value="calendar:IsResponseRequested"/>
<xs:enumeration value="calendar:CalendarItemType"/>
<xs:enumeration value="calendar:MyResponseType"/>
<xs:enumeration value="calendar:Organizer"/>
<xs:enumeration value="calendar:RequiredAttendees"/>
<xs:enumeration value="calendar:OptionalAttendees"/>
<xs:enumeration value="calendar:Resources"/>

```

```
<xs:enumeration value="calendar:ConflictingMeetingCount"/>
<xs:enumeration value="calendar:AdjacentMeetingCount"/>
<xs:enumeration value="calendar:ConflictingMeetings"/>
<xs:enumeration value="calendar:AdjacentMeetings"/>
<xs:enumeration value="calendar:Duration"/>
<xs:enumeration value="calendar:TimeZone"/>
<xs:enumeration value="calendar:AppointmentReplyTime"/>
<xs:enumeration value="calendar:AppointmentSequenceNumber"/>
<xs:enumeration value="calendar:AppointmentState"/>
<xs:enumeration value="calendar:Recurrence"/>
<xs:enumeration value="calendar:FirstOccurrence"/>
<xs:enumeration value="calendar>LastOccurrence"/>
<xs:enumeration value="calendar:ModifiedOccurrences"/>
<xs:enumeration value="calendar:DeletedOccurrences"/>
<xs:enumeration value="calendar:MeetingTimeZone"/>
<xs:enumeration value="calendar:ConferenceType"/>
<xs:enumeration value="calendar:AllowNewTimeProposal"/>
<xs:enumeration value="calendar:IsOnlineMeeting"/>
<xs:enumeration value="calendar:MeetingWorkspaceUrl"/>
<xs:enumeration value="calendar:NetShowUrl"/>
<xs:enumeration value="calendar:UID"/>
<xs:enumeration value="calendar:RecurrenceId"/>
<xs:enumeration value="calendar:DateTimeStamp"/>
<xs:enumeration value="calendar:StartTimeZone"/>
<xs:enumeration value="calendar:EndTimeZone"/>
<xs:enumeration value="task:ActualWork"/>
<xs:enumeration value="task:AssignedTime"/>
<xs:enumeration value="task:BillingInformation"/>
<xs:enumeration value="task:ChangeCount"/>
<xs:enumeration value="task:Companies"/>
<xs:enumeration value="task:CompleteDate"/>
<xs:enumeration value="task:Contacts"/>
<xs:enumeration value="task:DelegationState"/>
<xs:enumeration value="task:Delegator"/>
<xs:enumeration value="task:DueDate"/>
<xs:enumeration value="task:IsAssignmentEditable"/>
<xs:enumeration value="task:IsComplete"/>
<xs:enumeration value="task:IsRecurring"/>
<xs:enumeration value="task:IsTeamTask"/>
<xs:enumeration value="task:Mileage"/>
<xs:enumeration value="task:Owner"/>
<xs:enumeration value="task:PercentComplete"/>
<xs:enumeration value="task:Recurrence"/>
<xs:enumeration value="task:StartDate"/>
<xs:enumeration value="task:Status"/>
<xs:enumeration value="task:StatusDescription"/>
<xs:enumeration value="task:TotalWork"/>
<xs:enumeration value="contacts:AssistantName"/>
<xs:enumeration value="contacts:Birthday"/>
<xs:enumeration value="contacts:BusinessHomePage"/>
<xs:enumeration value="contacts:Children"/>
<xs:enumeration value="contacts:Companies"/>
<xs:enumeration value="contacts:CompanyName"/>
<xs:enumeration value="contacts:CompleteName"/>
<xs:enumeration value="contacts>ContactSource"/>
<xs:enumeration value="contacts:Culture"/>
<xs:enumeration value="contacts:Department"/>
<xs:enumeration value="contacts:DisplayName"/>
<xs:enumeration value="contacts:EmailAddresses"/>
```

```

<xs:enumeration value="contacts:FileAs"/>
<xs:enumeration value="contacts:FileAsMapping"/>
<xs:enumeration value="contacts:Generation"/>
<xs:enumeration value="contacts:GivenName"/>
<xs:enumeration value="contacts:ImAddresses"/>
<xs:enumeration value="contacts:Initials"/>
<xs:enumeration value="contacts:JobTitle"/>
<xs:enumeration value="contacts:Manager"/>
<xs:enumeration value="contacts:MiddleName"/>
<xs:enumeration value="contacts:Mileage"/>
<xs:enumeration value="contacts:Nickname"/>
<xs:enumeration value="contacts:OfficeLocation"/>
<xs:enumeration value="contacts:PhoneNumbers"/>
<xs:enumeration value="contacts:PhysicalAddresses"/>
<xs:enumeration value="contacts:PostalAddressIndex"/>
<xs:enumeration value="contacts:Profession"/>
<xs:enumeration value="contacts:SpouseName"/>
<xs:enumeration value="contacts:Surname"/>
<xs:enumeration value="contacts:WeddingAnniversary"/>
<xs:enumeration value="contacts:HasPicture"/>
<xs:enumeration value="distributionlist:Members"/>
<xs:enumeration value="postitem:PostedTime"/>
<xs:enumeration value="conversation:ConversationId" />
<xs:enumeration value="conversation:ConversationTopic" />
<xs:enumeration value="conversation:UniqueRecipients" />
<xs:enumeration value="conversation:GlobalUniqueRecipients" />
<xs:enumeration value="conversation:UniqueUnreadSenders" />
<xs:enumeration value="conversation:GlobalUniqueUnreadSenders" />
<xs:enumeration value="conversation:UniqueSenders" />
<xs:enumeration value="conversation:GlobalUniqueSenders" />
<xs:enumeration value="conversation:LastDeliveryTime" />
<xs:enumeration value="conversation:GlobalLastDeliveryTime" />
<xs:enumeration value="conversation:Categories" />
<xs:enumeration value="conversation:GlobalCategories" />
<xs:enumeration value="conversation:FlagStatus" />
<xs:enumeration value="conversation:GlobalFlagStatus" />
<xs:enumeration value="conversation:HasAttachments" />
<xs:enumeration value="conversation:GlobalHasAttachments" />
<xs:enumeration value="conversation:MessageCount" />
<xs:enumeration value="conversation:GlobalMessageCount" />
<xs:enumeration value="conversation:UnreadCount" />
<xs:enumeration value="conversation:GlobalUnreadCount" />
<xs:enumeration value="conversation:Size" />
<xs:enumeration value="conversation:GlobalSize" />
<xs:enumeration value="conversation:ItemClasses" />
<xs:enumeration value="conversation:GlobalItemClasses" />
<xs:enumeration value="conversation:Importance" />
<xs:enumeration value="conversation:GlobalImportance" />
<xs:enumeration value="conversation:ItemIds" />
<xs:enumeration value="conversation:GlobalItemIds" />
</xs:restriction>
</xs:simpleType>
<xs:complexType name="UserIdType">
  <xs:sequence>
    <xs:element name="SID" type="xs:string" minOccurs="0"/>
    <xs:element name="PrimarySmtpAddress" type="xs:string" minOccurs="0"/>
    <xs:element name="DisplayName" type="xs:string" minOccurs="0"/>
    <xs:element name="DistinguishedUser" type="t:DistinguishedUserType" minOccurs="0"/>
    <xs:element name="ExternalUserIdentity" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>

```



```

    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Value">
    <xs:simpleContent>
      <xs:extension base="xs:string">
        <xs:attribute name="Name" type="xs:string" use="required"/>
      </xs:extension>
    </xs:simpleContent>
  </xs:complexType>
  <xs:element name="Value" type="t:Value"/>
  <xs:complexType name="WeeklyRecurrencePatternType">
    <xs:complexContent>
      <xs:extension base="t:IntervalRecurrencePatternBaseType">
        <xs:sequence>
          <xs:element name="DaysOfWeek" type="t:DaysOfWeekType"/>
          <xs:element name="FirstDayOfWeek" type="t:DayOfWeekType" minOccurs="0"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="WellKnownResponseType">
    <xs:complexContent>
      <xs:restriction base="t:ResponseType">
        <xs:sequence>
          <xs:element name="ItemClass" type="t:ItemClassType" minOccurs="0"/>
          <xs:element name="Sensitivity" type="t:SensitivityChoicesType" minOccurs="0"/>
          <xs:element name="Body" type="t:BodyType" minOccurs="0"/>
          <xs:element name="Attachments" type="t:NonEmptyArrayOfAttachmentsType"
minOccurs="0"/>
          <xs:element name="InternetMessageHeaders"
type="t:NonEmptyArrayOfInternetHeadersType" minOccurs="0"/>
          <xs:element name="Sender" type="t:SingleRecipientType" minOccurs="0"/>
          <xs:element name="ToRecipients" type="t:ArrayOfRecipientsType" minOccurs="0"/>
          <xs:element name="CcRecipients" type="t:ArrayOfRecipientsType" minOccurs="0"/>
          <xs:element name="BccRecipients" type="t:ArrayOfRecipientsType" minOccurs="0"/>
          <xs:element name="IsReadReceiptRequested" type="xs:boolean" minOccurs="0"/>
          <xs:element name="IsDeliveryReceiptRequested" type="xs:boolean" minOccurs="0"/>
          <xs:element name="From" type="t:SingleRecipientType" minOccurs="0"/>
          <xs:element name="ReferenceItemId" type="t:ItemIdType" minOccurs="0"/>
        </xs:sequence>
        <xs:attribute name="ObjectName" type="xs:string" use="prohibited"/>
      </xs:restriction>
    </xs:complexContent>
  </xs:complexType>
</xs:schema>

```

8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2.2.9:](#) Exchange 2007 and Exchange 2010 do not include the following enumeration values: recoverableitemsroot, recoverableitemsdeletions, recoverableitemsversions, recoverableitemspurges, archiveroot, archivermsgfolderroot, archiveddeleteditems, archiverecoverableitemsroot, archiverecoverableitemsdeletions, archiverecoverableitemsversions, and archiverecoverableitemspurges.

[<2> Section 2.2.2.13:](#) Exchange 2007 does not include the **ExchangeVersionType** simple type.

[<3> Section 2.2.2.13:](#) Exchange 2007 includes only the target schema that is identified by the Exchange 2007 enumeration value.

[<4> Section 2.2.2.13:](#) Exchange 2007 does not include the target schema that is identified by the Exchange 2007 SP1 enumeration value.

[<5> Section 2.2.2.13:](#) Exchange 2007 and Exchange 2007 SP1 do not include the target schema that is identified by the Exchange 2010 enumeration value.

[<6> Section 2.2.2.13:](#) Exchange 2007, Exchange 2007 SP1, and Exchange 2010 do not include the target schema that is identified by the Exchange 2010 SP1 enumeration value.

[<7> Section 2.2.2.20:](#) Exchange 2007 and Exchange 2010 do not include the following response codes: ErrorAccessModeSpecified, ErrorCannotEmptyFolder, ErrorClientDisconnected, ErrorInvalidLogonType, ErrorNoApplicableProxyCASServersAvailable, ErrorNoPublicFolderServerAvailable, ErrorProxyServiceDiscoveryFailed, ErrorSubscriptionUnsubscribed, ErrorOutlookRuleBlobExists, ErrorRulesOverQuota, ErrorInboxRulesValidationError, ErrorNewEventStreamConnectionOpened, ErrorMissedNotificationEvents, and ErrorApplyConversationActionFailed.

[<8> Section 2.2.2.20:](#) IDs that are based on the Exchange 2007 server schema are not supported by Exchange 2007 SP1 or later.

[<9> Section 2.2.2.22:](#) Exchange 2007 and Exchange 2010 do not include the following enumeration values: conversation:ConversationId, conversation:ConversationTopic, conversation:UniqueRecipients, conversation:GlobalUniqueRecipients, conversation:UniqueUnreadSenders, conversation:GlobalUniqueUnreadSenders, conversation:UniqueSenders, conversation:GlobalUniqueSenders, conversation>LastDeliveryTime, conversation:GlobalLastDeliveryTime, conversation:Categories, conversation:GlobalCategories,

conversation:FlagStatus, conversation:GlobalFlagStatus, conversation:HasAttachments, conversation:GlobalHasAttachments, conversation:MessageCount, conversation:GlobalMessageCount, conversation:UnreadCount, conversation:GlobalUnreadCount, conversation:Size, conversation:GlobalSize, conversation:ItemClasses, conversation:GlobalItemClasses, conversation:Importance, conversation:GlobalImportance, conversation:ItemIds, and conversation:GlobalItemIds.

<10> [Section 2.2.3.9](#): Exchange 2007 and Exchange 2010 do not include the **EmptyFolderResponseMessage** element.

<11> [Section 2.2.3.9](#): Exchange 2007 and Exchange 2010 do not include the **UploadItemsResponseMessage** element.

<12> [Section 2.2.3.9](#): Exchange 2007 and Exchange 2010 do not include the **ExportItemsResponseMessage** element.

<13> [Section 2.2.3.9](#): Exchange 2007 and Exchange 2010 do not include the **GetStreamingEventsResponseMessage** element.

<14> [Section 2.2.3.9](#): Exchange 2007 and Exchange 2010 do not include the **ApplyConversationActionResponseMessage** element.

<15> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not include the **ViewPrivateItems** element.

<16> [Section 2.2.3.35](#): Exchange 2007 and Exchange 2010 do not include the **ConvertHtmlCodePageToUTF8** element.

<17> [Section 2.2.3.59](#): Exchange 2007 and Exchange 2010 do not include the **FirstDayOfWeek** element.

<18> [Section 2.2.4.8](#): Exchange 2007 does not include the **RequestServerVersion** element. Exchange 2007 SP1 includes a **fixed** attribute with a value equal to **Exchange2007_SP1**. Exchange 2010 includes a **fixed** attribute with a value equal to **Exchange2010**.

9 Change Tracking

This section identifies changes that were made to the [MS-OXWSCDATA] protocol document between the March 2011 and August 2011 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.2.2.20 m:ResponseCodeType Simple Type	Added behavior information for the ErrorInvalidIdMalformedEwsLegacyIdFormat enumeration.	N	New product behavior note added.
2.2.4.1 t:DateTimePrecision Element	Added the DateTimePrecision element section.	Y	New content added.
7.1 Messages Schema	Updated references to referenced schemas.	N	Content updated.
7.2 Types Schema	Updated references to referenced schemas.	N	Content updated.
8 Appendix C: Product Behavior	Removed Exchange Server 2007 Service Pack 1 and Exchange Server 2010 Service Pack 1 from the list of applicable products.	N	Content removed.

10 Index

A

Abstract data model
 [client](#) 139
 [server](#) 139
[Applicability](#) 8
Attribute groups
 [t:FindResponsePagingAttributes](#) [Attribute Group](#)
 137
[Attributes](#) 135

C

[Capability negotiation](#) 8
[Change tracking](#) 172
Client
 [abstract data model](#) 139
 [initialization](#) 139
 [local events](#) 140
 [message processing](#) 139
 [sequencing rules](#) 139
 [timer events](#) 140
 [timers](#) 139
Complex types
 [m:ArrayOfResponseMessagesType](#) [Complex Type](#)
 95
 [m:BaseRequestType](#) [Complex Type](#) 104
 [m:BaseResponseMessageType](#) [Complex Type](#) 104
 [m:ItemInfoResponseMessageType](#) [Complex Type](#)
 114
 [m:ResponseMessageType](#) [Complex Type](#) 125
 [t:AbsoluteMonthlyRecurrencePatternType](#)
 [Complex Type](#) 91
 [t:AbsoluteYearlyRecurrencePatternType](#) [Complex](#)
 [Type](#) 91
 [t:AcceptSharingInvitationType](#) [Complex Type](#) 92
 [t:ArrayOfCalendarPermissionsType](#) [Complex Type](#)
 92
 [t:ArrayOfEmailAddressesType](#) [Complex Type](#) 92
 [t:ArrayOfPermissionsType](#) [Complex Type](#) 93
 [t:ArrayOfRealItemsType](#) [Complex Type](#) 93
 [t:ArrayOfRecipientsType](#) [Complex Type](#) 95
 [t:ArrayOfStringsType](#) [Complex Type](#) 103
 [t:BaseEmailAddressType](#) [Complex Type](#) 103
 [t:BaseItemIdType](#) [Complex Type](#) 103
 [t:BasePathToElementType](#) [Complex Type](#) 103
 [t:BodyType](#) [Complex Type](#) 104
 [t:ConnectingSIDType](#) [Complex Type](#) 105
 [t:ConstantValueType](#) [Complex Type](#) 105
 [t:DailyRecurrencePatternType](#) [Complex Type](#) 106
 [t:DeletedOccurrenceInfoType](#) [Complex Type](#) 106
 [t:DistinguishedFolderIdType](#) [Complex Type](#) 106
 [t:Duration](#) [Complex Type](#) 107
 [t:EffectiveRightsType](#) [Complex Type](#) 108
 [t:EmailAddressType](#) [Complex Type](#) 109
 [t:EmailAddress](#) 109
 [t:EndDateRecurrenceRangeType](#) [Complex Type](#)
 110

[t:ExchangeImpersonationType](#) [Complex Type](#) 111
 [t:FieldURIOrConstantType](#) [Complex Type](#) 111
 [t:FolderIdType](#) [Complex Type](#) 111
 [t:FolderResponseShapeType](#) [Complex Type](#) 112
 [t:ForwardItemType](#) [Complex Type](#) 113
 [t:InternetHeaderType](#) [Complex Type](#) 113
 [t:IntervalRecurrencePatternBaseType](#) [Complex](#)
 [Type](#) 113
 [t:ItemResponseShapeType](#) [Complex Type](#) 114
 [t:MailboxCultureType](#) [Complex Type](#) 116
 [t:NoEndRecurrenceRangeType](#) [Complex Type](#) 116
 [t:NonEmptyArrayOfAllItemsType](#) [Complex Type](#)
 117
 [t:NonEmptyArrayOfAttachmentsType](#) [Complex](#)
 [Type](#) 119
 [t:NonEmptyArrayOfPathsToElementType](#) [Complex](#)
 [Type](#) 120
 [t:NumberedRecurrenceRangeType](#) [Complex Type](#)
 120
 [t:PathToExceptionFieldType](#) [Complex Type](#) 121
 [t:PathToIndexedFieldType](#) [Complex Type](#) 121
 [t:PathToUnindexedFieldType](#) [Complex Type](#) 122
 [t:RecurrencePatternBaseType](#) [Complex Type](#) 122
 [t:RecurrenceRangeBaseType](#) [Complex Type](#) 122
 [t:RelativeMonthlyRecurrencePatternType](#)
 [Complex Type](#) 123
 [t:RelativeYearlyRecurrencePatternType](#) [Complex](#)
 [Type](#) 123
 [t:ReplyAllToItemType](#) [Complex Type](#) 124
 [t:ReplyBody](#) 124
 [t:ReplyToItemType](#) [Complex Type](#) 125
 [t:ResponseObjectCoreType](#) [Complex Type](#) 126
 [t:ResponseObjectType](#) [Complex Type](#) 127
 [t:SingleRecipientType](#) [Complex Type](#) 127
 [t:SuppressReadReceiptType](#) [Complex Type](#) 127
 [t:UserIdType](#) [Complex Type](#) 128
 [t:Value](#) [Complex Type](#) 129
 [t:WeeklyRecurrencePatternType](#) [Complex Type](#)
 129
 [t:WellKnownResponseObjectType](#) [Complex Type](#)
 130

D

Data model - abstract
 [client](#) 139
 [server](#) 139

E

Elements
 [t:ExceptionFieldURI](#) [Element](#) 132
 [t:ExchangeImpersonation](#) [Element](#) 132
 [t:FieldURI](#) [Element](#) 133
 [t:IndexedFieldURI](#) [Element](#) 133
 [t:MailboxCulture](#) [Element](#) 133
 [t:Path](#) [Element](#) 133
 [t:RequestServerVersion](#) [Element](#) 134

[t:ServerVersionInfo Element](#) 134
[Value Element](#) 135
 Events
 [local - client](#) 140
 [local - server](#) 139
 [timer - client](#) 140
 [timer - server](#) 139

F

[Fields - vendor-extensible](#) 8
[Full WSDL](#) 143

G

[Glossary](#) 6
 Groups
 [t:RecurrencePatternTypes Group](#) 135
 [t:RecurrenceRangeTypes Group](#) 136
 [t:TimeChangePatternTypes Group](#) 137

I

[Implementer - security considerations](#) 142
[Index of security parameters](#) 142
[Informative references](#) 8
 Initialization
 [client](#) 139
 [server](#) 139
[Introduction](#) 6

L

Local events
 [client](#) 140
 [server](#) 139

M

[m:ArrayOfResponseMessagesType Complex Type complex type](#) 95
[m:BaseRequestType Complex Type complex type](#) 104
[m:BaseResponseMessageType Complex Type complex type](#) 104
[m:ItemInfoResponseMessageType Complex Type complex type](#) 114
[m:ResponseCodeType Simple Type simple type](#) 26
[m:ResponseMessageType Complex Type complex type](#) 125
 Message processing
 [client](#) 139
 [server](#) 139
 Messages
 [attributes](#) 135
 [enumerated](#) 138
 [m:ArrayOfResponseMessagesType Complex Type complex type](#) 95
 [m:BaseRequestType Complex Type complex type](#) 104
 [m:BaseResponseMessageType Complex Type complex type](#) 104
[m:ItemInfoResponseMessageType Complex Type complex type](#) 114
[m:ResponseCodeType Simple Type simple type](#) 26
[m:ResponseMessageType Complex Type complex type](#) 125
 [namespaces](#) 9
 [syntax](#) 9
 [t:AbsoluteMonthlyRecurrencePatternType Complex Type complex type](#) 91
 [t:AbsoluteYearlyRecurrencePatternType Complex Type complex type](#) 91
 [t:AcceptSharingInvitationType Complex Type complex type](#) 92
 [t:ArrayOfCalendarPermissionsType Complex Type complex type](#) 92
 [t:ArrayOfEmailAddressesType Complex Type complex type](#) 92
 [t:ArrayOfPermissionsType Complex Type complex type](#) 93
 [t:ArrayOfRealItemsType Complex Type complex type](#) 93
 [t:ArrayOfRecipientsType Complex Type complex type](#) 95
 [t:ArrayOfStringsType Complex Type complex type](#) 103
 [t:BaseEmailAddressType Complex Type complex type](#) 103
 [t:BaseItemIdType Complex Type complex type](#) 103
 [t:BasePathToElementType Complex Type complex type](#) 103
 [t:BodyType Complex Type complex type](#) 104
 [t:BodyTypeResponseType Simple Type simple type](#) 9
 [t:BodyTypeType Simple Type simple type](#) 10
 [t:ConnectingSIDType Complex Type complex type](#) 105
 [t:ConstantValueType Complex Type complex type](#) 105
 [t:DailyRecurrencePatternType Complex Type complex type](#) 106
 [t:DayOfWeekIndexType Simple Type simple type](#) 10
 [t:DayOfWeekType Simple Type simple type](#) 11
 [t:DaysOfWeekType Simple Type simple type](#) 12
 [t:DefaultShapeNamesType Simple Type simple type](#) 13
 [t:DeletedOccurrenceInfoType Complex Type complex type](#) 106
 [t:DictionaryURIType Simple Type simple type](#) 13
 [t:DisposalType Simple Type simple type](#) 14
 [t:DistinguishedFolderIdNameType Simple Type simple type](#) 15
 [t:DistinguishedFolderIdType Complex Type complex type](#) 106
 [t:DistinguishedPropertySetType Simple Type simple type](#) 18
 [t:DistinguishedUserType Simple Type simple type](#) 19
 [t:Duration Complex Type complex type](#) 107

[t:EffectiveRightsType Complex Type complex type](#) 108
[t:EmailAddressType Complex Type complex type](#) 109
[t:EmailAddress complex type](#) 109
[t:EndDateRecurrenceRangeType Complex Type complex type](#) 110
[t:ExceptionFieldURI Element element](#) 132
[t:ExceptionPropertyURIType Simple Type simple type](#) 19
[t:ExchangeImpersonation Element element](#) 132
[t:ExchangeImpersonationType Complex Type complex type](#) 111
[t:ExchangeVersionType Simple Type simple type](#) 21
[t:ExcludesAttributeType Simple Type simple type](#) 21
[t:FieldURI Element element](#) 133
[t:FieldURIOrConstantType Complex Type complex type](#) 111
[t:FindResponsePagingAttributes Attribute Group attribute group](#) 137
[t:FolderIdType Complex Type complex type](#) 111
[t:FolderResponseShapeType Complex Type complex type](#) 112
[t:ForwardItemType Complex Type complex type](#) 113
[t:IndexedFieldURI Element element](#) 133
[t:InternetHeaderType Complex Type complex type](#) 113
[t:IntervalRecurrencePatternBaseType Complex Type complex type](#) 113
[t:ItemResponseShapeType Complex Type complex type](#) 114
[t:LegacyFreeBusyType Simple Type simple type](#) 22
[t:MailboxCulture Element element](#) 133
[t:MailboxCultureType Complex Type complex type](#) 116
[t:MailboxTypeType Simple Type simple type](#) 23
[t:MonthNamesType Simple Type simple type](#) 24
[t:NoEndRecurrenceRangeType Complex Type complex type](#) 116
[t:NonEmptyArrayOfAllItemsType Complex Type complex type](#) 117
[t:NonEmptyArrayOfAttachmentsType Complex Type complex type](#) 119
[t:NonEmptyArrayOfPathsToElementType Complex Type complex type](#) 120
[t:NonEmptyStringType Simple Type simple type](#) 25
[t:NumberedRecurrenceRangeType Complex Type complex type](#) 120
[t:Path Element element](#) 133
[t:PathToExceptionFieldType Complex Type complex type](#) 121
[t:PathToIndexedFieldType Complex Type complex type](#) 121
[t:PathToUnindexedFieldType Complex Type complex type](#) 122
[t:RecurrencePatternBaseType Complex Type complex type](#) 122
[t:RecurrencePatternTypes Group group](#) 135
[t:RecurrenceRangeBaseType Complex Type complex type](#) 122
[t:RecurrenceRangeTypes Group group](#) 136
[t:RelativeMonthlyRecurrencePatternType Complex Type complex type](#) 123
[t:RelativeYearlyRecurrencePatternType Complex Type complex type](#) 123
[t:ReplyAllToItemType Complex Type complex type](#) 124
[t:ReplyBody complex type](#) 124
[t:ReplyToItemType Complex Type complex type](#) 125
[t:RequestServerVersion Element element](#) 134
[t:ResponseClassType Simple Type simple type](#) 25
[t:ResponseObjectCoreType Complex Type complex type](#) 126
[t:ResponseObjectType Complex Type complex type](#) 127
[t:SensitivityChoicesType Simple Type simple type](#) 73
[t:ServerVersionInfo Element element](#) 134
[t:SingleRecipientType Complex Type complex type](#) 127
[t:SuppressReadReceiptType Complex Type complex type](#) 127
[t:TimeChangePatternTypes Group group](#) 137
[t:UnindexedFieldURIType Simple Type simple type](#) 73
[t:UserIdType Complex Type complex type](#) 128
[t:Value Complex Type complex type](#) 129
[t:WeeklyRecurrencePatternType Complex Type complex type](#) 129
[t:WellKnownResponseType Complex Type complex type](#) 130
[transport](#) 9
[Value Element element](#) 135

N
[Namespaces](#) 9
[Normative references](#) 7

O
[Overview \(synopsis\)](#) 8

P
[Parameters - security index](#) 142
[Preconditions](#) 8
[Prerequisites](#) 8
[Product behavior](#) 170

R
[References](#)
[informative](#) 8
[normative](#) 7
[Relationship to other protocols](#) 8

S

Security

[implementer considerations](#) 142
[parameter index](#) 142

Sequencing rules

[client](#) 139
[server](#) 139

Server

[abstract data model](#) 139
[initialization](#) 139
[local events](#) 139
[message processing](#) 139
[sequencing rules](#) 139
[timer events](#) 139
[timers](#) 139

Simple types

[m:ResponseCodeType Simple Type](#) 26
[t:BodyTypeResponseType Simple Type](#) 9
[t:BodyTypeType Simple Type](#) 10
[t:DayOfWeekIndexType Simple Type](#) 10
[t:DayOfWeekType Simple Type](#) 11
[t:DaysOfWeekType Simple Type](#) 12
[t:DefaultShapeNamesType Simple Type](#) 13
[t:DictionaryURIType Simple Type](#) 13
[t:DisposalType Simple Type](#) 14
[t:DistinguishedFolderIdNameType Simple Type](#) 15
[t:DistinguishedPropertySetType Simple Type](#) 18
[t:DistinguishedUserType Simple Type](#) 19
[t:ExceptionPropertyURIType Simple Type](#) 19
[t:ExchangeVersionType Simple Type](#) 21
[t:ExcludesAttributeType Simple Type](#) 21
[t:LegacyFreeBusyType Simple Type](#) 22
[t:MailboxTypeType Simple Type](#) 23
[t:MonthNamesType Simple Type](#) 24
[t:NonEmptyStringType Simple Type](#) 25
[t:ResponseClassType Simple Type](#) 25
[t:SensitivityChoicesType Simple Type](#) 73
[t:UnindexedFieldURIType Simple Type](#) 73

Standards assignments

Syntax

[messages - overview](#) 9

T

[t:AbsoluteMonthlyRecurrencePatternType Complex Type complex type](#) 91
[t:AbsoluteYearlyRecurrencePatternType Complex Type complex type](#) 91
[t:AcceptSharingInvitationType Complex Type complex type](#) 92
[t:ArrayOfCalendarPermissionsType Complex Type complex type](#) 92
[t:ArrayOfEmailAddressesType Complex Type complex type](#) 92
[t:ArrayOfPermissionsType Complex Type complex type](#) 93
[t:ArrayOfRealItemsType Complex Type complex type](#) 93

[t:ArrayOfRecipientsType Complex Type complex type](#) 95
[t:ArrayOfStringsType Complex Type complex type](#) 103
[t:BaseEmailAddressType Complex Type complex type](#) 103
[t:BaseItemIdType Complex Type complex type](#) 103
[t:BasePathToElementType Complex Type complex type](#) 103
[t:BodyType Complex Type complex type](#) 104
[t:BodyTypeResponseType Simple Type simple type](#) 9
[t:BodyTypeType Simple Type simple type](#) 10
[t:ConnectingSIDType Complex Type complex type](#) 105
[t:ConstantValueType Complex Type complex type](#) 105
[t:DailyRecurrencePatternType Complex Type complex type](#) 106
[t:DayOfWeekIndexType Simple Type simple type](#) 10
[t:DayOfWeekType Simple Type simple type](#) 11
[t:DaysOfWeekType Simple Type simple type](#) 12
[t:DefaultShapeNamesType Simple Type simple type](#) 13
[t:DeletedOccurrenceInfoType Complex Type complex type](#) 106
[t:DictionaryURIType Simple Type simple type](#) 13
[t:DisposalType Simple Type simple type](#) 14
[t:DistinguishedFolderIdNameType Simple Type simple type](#) 15
[t:DistinguishedFolderIdType Complex Type complex type](#) 106
[t:DistinguishedPropertySetType Simple Type simple type](#) 18
[t:DistinguishedUserType Simple Type simple type](#) 19
[t:Duration Complex Type complex type](#) 107
[t:EffectiveRightsType Complex Type complex type](#) 108
[t:EmailAddressType Complex Type complex type](#) 109
[t:EmailAddress complex type](#) 109
[t:EndDateRecurrenceRangeType Complex Type complex type](#) 110
[t:ExceptionFieldURI Element element](#) 132
[t:ExceptionPropertyURIType Simple Type simple type](#) 19
[t:ExchangeImpersonation Element element](#) 132
[t:ExchangeImpersonationType Complex Type complex type](#) 111
[t:ExchangeVersionType Simple Type simple type](#) 21
[t:ExcludesAttributeType Simple Type simple type](#) 21
[t:FieldURI Element element](#) 133
[t:FieldURIOrConstantType Complex Type complex type](#) 111
[t:FindResponsePagingAttributes Attribute Group attribute group](#) 137
[t:FolderIdType Complex Type complex type](#) 111
[t:FolderResponseShapeType Complex Type complex type](#) 112

[t:ForwardItemType Complex Type complex type](#) 113
[t:IndexedFieldURI Element element](#) 133
[t:InternetHeaderType Complex Type complex type](#) 113
[t:IntervalRecurrencePatternBaseType Complex Type complex type](#) 113
[t:ItemResponseShapeType Complex Type complex type](#) 114
[t:LegacyFreeBusyType Simple Type simple type](#) 22
[t:MailboxCulture Element element](#) 133
[t:MailboxCultureType Complex Type complex type](#) 116
[t:MailboxTypeType Simple Type simple type](#) 23
[t:MonthNamesType Simple Type simple type](#) 24
[t:NoEndRecurrenceRangeType Complex Type complex type](#) 116
[t:NonEmptyArrayOfAllItemsType Complex Type complex type](#) 117
[t:NonEmptyArrayOfAttachmentsType Complex Type complex type](#) 119
[t:NonEmptyArrayOfPathsToElementType Complex Type complex type](#) 120
[t:NonEmptyStringType Simple Type simple type](#) 25
[t:NumberedRecurrenceRangeType Complex Type complex type](#) 120
[t:Path Element element](#) 133
[t:PathToExceptionFieldType Complex Type complex type](#) 121
[t:PathToIndexedFieldType Complex Type complex type](#) 121
[t:PathToUnindexedFieldType Complex Type complex type](#) 122
[t:RecurrencePatternBaseType Complex Type complex type](#) 122
[t:RecurrencePatternTypes Group group](#) 135
[t:RecurrenceRangeBaseType Complex Type complex type](#) 122
[t:RecurrenceRangeTypes Group group](#) 136
[t:RelativeMonthlyRecurrencePatternType Complex Type complex type](#) 123
[t:RelativeYearlyRecurrencePatternType Complex Type complex type](#) 123
[t:ReplyAllToItemType Complex Type complex type](#) 124
[t:ReplyBody complex type](#) 124
[t:ReplyToItemType Complex Type complex type](#) 125
[t:RequestServerVersion Element element](#) 134
[t:ResponseClassType Simple Type simple type](#) 25
[t:ResponseObjectCoreType Complex Type complex type](#) 126
[t:ResponseObjectType Complex Type complex type](#) 127
[t:SensitivityChoicesType Simple Type simple type](#) 73
[t:ServerVersionInfo Element element](#) 134
[t:SingleRecipientType Complex Type complex type](#) 127
[t:SuppressReadReceiptType Complex Type complex type](#) 127

[t:TimeChangePatternTypes Group group](#) 137
[t:UnindexedFieldURIType Simple Type simple type](#) 73
[t:UserIdType Complex Type complex type](#) 128
[t:Value Complex Type complex type](#) 129
[t:WeeklyRecurrencePatternType Complex Type complex type](#) 129
[t:WellKnownResponseObjectType Complex Type complex type](#) 130
Timer events
 [client](#) 140
 [server](#) 139
Timers
 [client](#) 139
 [server](#) 139
[Tracking changes](#) 172
[Transport](#) 9

V

[Value Element element](#) 135
[Vendor-extensible fields](#) 8
[Versioning](#) 8

W

[WSDL](#) 143