

# [MS-OXWSCDATA]: Common Web Service Data Types

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
07/15/2009	1.0	Major	Initial Availability.
11/04/2009	2.0.0	Major	Updated and revised the technical content.
02/10/2010	2.1.0	Minor	Updated the technical content.
05/05/2010	3.0.0	Major	Updated and revised the technical content.
08/04/2010	4.0	Major	Significantly changed the technical content.
11/03/2010	4.1	Minor	Clarified the meaning of the technical content.
03/18/2011	5.0	Major	Significantly changed the technical content.
08/05/2011	6.0	Major	Significantly changed the technical content.
10/07/2011	7.0	Major	Significantly changed the technical content.
01/20/2012	8.0	Major	Significantly changed the technical content.
04/27/2012	8.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	9.0	Major	Significantly changed the technical content.
10/08/2012	10.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1 Introduction</b> .....	<b>6</b>
1.1 Glossary .....	6
1.2 References.....	7
1.2.1 Normative References.....	7
1.2.2 Informative References .....	8
1.3 Overview .....	8
1.4 Relationship to Other Protocols.....	8
1.5 Prerequisites/Preconditions .....	9
1.6 Applicability Statement.....	9
1.7 Versioning and Capability Negotiation.....	9
1.8 Vendor-Extensible Fields.....	9
1.9 Standards Assignments .....	9
<b>2 Messages</b> .....	<b>10</b>
2.1 Transport.....	10
2.2 Common Message Syntax .....	10
2.2.1 Namespaces .....	10
2.2.2 Messages .....	10
2.2.3 Simple Types.....	10
2.2.3.1 t:BodyTypeResponseType Simple Type.....	11
2.2.3.2 t:BodyTypeType Simple Type.....	12
2.2.3.3 t:DateTimePrecisionType Simple Type.....	12
2.2.3.4 t:DayOfWeekIndexType Simple Type .....	13
2.2.3.5 t:DayOfWeekType Simple Type .....	13
2.2.3.6 t:DaysOfWeekType Simple Type.....	14
2.2.3.7 t:DefaultShapeNamesType Simple Type .....	15
2.2.3.8 t:DictionaryURIType Simple Type .....	15
2.2.3.9 t:DisposalType Simple Type .....	16
2.2.3.10 t:DistinguishedFolderIdNameType Simple Type .....	16
2.2.3.11 t:DistinguishedPropertySetType Simple Type.....	19
2.2.3.12 t:DistinguishedUserType Simple Type.....	19
2.2.3.13 t:ExceptionPropertyURIType Simple Type .....	20
2.2.3.14 t:ExchangeVersionType Simple Type .....	21
2.2.3.15 t:ExcludesAttributeType Simple Type .....	21
2.2.3.16 t:IconIndexType Simple Type.....	22
2.2.3.17 t:LegacyFreeBusyType Simple Type .....	24
2.2.3.18 t:MailboxTypeType Simple Type.....	24
2.2.3.19 t:MonthNamesType Simple Type.....	25
2.2.3.20 t:NonEmptyStringType Simple Type .....	26
2.2.3.21 PredictedMessageType.....	26
2.2.3.22 t:ResponseClassType Simple Type .....	27
2.2.3.23 m:ResponseCodeType Simple Type .....	27
2.2.3.24 t:SensitivityChoicesType Simple Type.....	66
2.2.3.25 t:UnindexedFieldURIType Simple Type .....	66
2.2.4 Complex Types .....	83
2.2.4.1 t:AbsoluteMonthlyRecurrencePatternType Complex Type .....	83
2.2.4.2 t:AbsoluteYearlyRecurrencePatternType Complex Type.....	84
2.2.4.3 t:AcceptSharingInvitationType Complex Type.....	85
2.2.4.4 t:ArrayOfCalendarPermissionsType Complex Type .....	85
2.2.4.5 t:ArrayOfEmailAddressesType Complex Type .....	85

2.2.4.6	t:ArrayOfHighlightTermsType	86
2.2.4.7	t:ArrayOfPermissionsType Complex Type	86
2.2.4.8	t:ArrayOfRealItemsType Complex Type	87
2.2.4.9	t:ArrayOfRecipientsType Complex Type	88
2.2.4.10	m:ArrayOfResponseMessagesType Complex Type	89
2.2.4.11	t:ArrayOfStringsType Complex Type	98
2.2.4.12	t:BaseEmailAddressType Complex Type	99
2.2.4.13	t:BaseItemIdType Complex Type	99
2.2.4.14	t:BasePathToElementType Complex Type	99
2.2.4.15	m:BaseRequestType Complex Type	99
2.2.4.16	m:BaseResponseMessageType Complex Type	99
2.2.4.17	t:BodyType Complex Type	100
2.2.4.18	t:ChangeHighlightsType	100
2.2.4.19	t:ConnectingSIDType Complex Type	101
2.2.4.20	t:ConstantValueType Complex Type	102
2.2.4.21	t:DailyRecurrencePatternType Complex Type	102
2.2.4.22	t:DeletedOccurrenceInfoType Complex Type	102
2.2.4.23	t:DistinguishedFolderIdType Complex Type	103
2.2.4.24	t:Duration Complex Type	104
2.2.4.25	t:EffectiveRightsType Complex Type	104
2.2.4.26	t:EmailAddress	105
2.2.4.27	t:EmailAdressesType Complex Type	106
2.2.4.28	t:EndDateRecurrenceRangeType Complex Type	107
2.2.4.29	t:ExchangeImpersonationType Complex Type	107
2.2.4.30	t:FieldURIOrConstantType Complex Type	108
2.2.4.31	t:FolderIdType Complex Type	108
2.2.4.32	t:FolderResponseShapeType Complex Type	109
2.2.4.33	t:ForwardItemType Complex Type	110
2.2.4.34	t:HighlightTermType	110
2.2.4.35	t:InternetHeaderType Complex Type	110
2.2.4.36	t:IntervalRecurrencePatternBaseType Complex Type	111
2.2.4.37	m:ItemInfoResponseMessageType Complex Type	111
2.2.4.38	t:ItemResponseShapeType Complex Type	112
2.2.4.39	t:MailboxCultureType Complex Type	113
2.2.4.40	t:ManagementRoleType Complex Type	114
2.2.4.41	t:NoEndRecurrenceRangeType Complex Type	114
2.2.4.42	t:NonEmptyArrayOfAllItemsType Complex Type	114
2.2.4.43	t:NonEmptyArrayOfAttachmentsType Complex Type	117
2.2.4.44	t:NonEmptyArrayOfPathsToElementType Complex Type	118
2.2.4.45	t:NonEmptyArrayOfRoleType Complex Type	118
2.2.4.46	t:NumberedRecurrenceRangeType Complex Type	118
2.2.4.47	t:PathToExceptionFieldType Complex Type	119
2.2.4.48	t:PathToIndexedFieldType Complex Type	119
2.2.4.49	t:PathToUnindexedFieldType Complex Type	120
2.2.4.50	t:RecurrencePatternBaseType Complex Type	120
2.2.4.51	t:RecurrenceRangeBaseType Complex Type	121
2.2.4.52	t:RelativeMonthlyRecurrencePatternType Complex Type	121
2.2.4.53	t:RelativeYearlyRecurrencePatternType Complex Type	122
2.2.4.54	t:ReplyAllToItemType Complex Type	122
2.2.4.55	t:ReplyBody	123
2.2.4.56	t:ReplyToItemType Complex Type	123
2.2.4.57	m:ResponseMessageType Complex Type	123
2.2.4.58	t:ResponseObjectCoreType Complex Type	125

2.2.4.59	t:ResponseType Complex Type .....	125
2.2.4.60	t:SingleRecipientType Complex Type .....	126
2.2.4.61	t:SuppressReadReceiptType Complex Type .....	126
2.2.4.62	t:UserIdType Complex Type .....	126
2.2.4.63	t:Value Complex Type .....	127
2.2.4.64	t:WeeklyRecurrencePatternType Complex Type .....	128
2.2.4.65	t:WellKnownResponseType Complex Type.....	128
2.2.5	Elements.....	131
2.2.5.1	t:DateTimePrecision Element .....	131
2.2.5.2	t:ExceptionFieldURI Element .....	131
2.2.5.3	t:ExchangeImpersonation Element .....	131
2.2.5.4	t:FieldURI Element.....	131
2.2.5.5	t:IndexedFieldURI Element .....	131
2.2.5.6	t:MailboxCulture Element .....	132
2.2.5.7	t:ManagementRole Element .....	132
2.2.5.8	t:Path Element .....	132
2.2.5.9	t:RequestServerVersion Element .....	132
2.2.5.10	t:ServerVersionInfo Element .....	133
2.2.5.11	Value Element .....	134
2.2.6	Attributes.....	134
2.2.7	Groups.....	134
2.2.7.1	t:RecurrencePatternTypes Group .....	134
2.2.7.2	t:RecurrenceRangeTypes Group .....	135
2.2.7.3	t:TimeChangePatternTypes Group .....	136
2.2.8	Attribute Groups .....	136
2.2.8.1	t:FindResponsePagingAttributes Attribute Group.....	136
<b>3</b>	<b>Protocol Details.....</b>	<b>138</b>
3.1	Server Details .....	138
3.1.1	Abstract Data Model .....	138
3.1.2	Timers .....	138
3.1.3	Initialization .....	138
3.1.4	Message Processing Events and Sequencing Rules.....	138
3.1.5	Timer Events .....	138
3.1.6	Other Local Events .....	138
<b>4</b>	<b>Protocol Examples.....</b>	<b>139</b>
<b>5</b>	<b>Security.....</b>	<b>140</b>
5.1	Security Considerations for Implementers.....	140
5.2	Index of Security Parameters .....	140
<b>6</b>	<b>Appendix A: Full WSDL.....</b>	<b>141</b>
<b>7</b>	<b>Appendix B: Full XML Schema .....</b>	<b>142</b>
7.1	Messages Schema.....	142
7.2	Types Schema.....	153
<b>8</b>	<b>Appendix C: Product Behavior .....</b>	<b>175</b>
<b>9</b>	<b>Change Tracking.....</b>	<b>190</b>
<b>10</b>	<b>Index .....</b>	<b>194</b>

# 1 Introduction

The Common Web Service Data Types are Web service data types that are common to more than one Web service protocol.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

### **Coordinated Universal Time (UTC)**

The following terms are defined in [\[MS-OXGLOS\]](#):

**Calendar folder**  
**delegate**  
**Deleted Items folder**  
**distribution list**  
**endpoint**  
**free/busy message**  
**free/busy status**  
**Hypertext Markup Language (HTML)**  
**Inbox folder**  
**Information Rights Management (IRM)**  
**Junk Email folder**  
**mailbox**  
**Multipurpose Internet Mail Extensions (MIME)**  
**OOF message**  
**Out of Office (OOF)**  
**Outbox folder**  
**plain text**  
**public folder**  
**recurring task**  
**S/MIME (Secure/Multipurpose Internet Mail Extensions)**  
**Sent Items folder**  
**Short Message Service (SMS)**  
**Simple Mail Transfer Protocol (SMTP)**  
**SOAP header**  
**Uniform Resource Identifier (URI)**  
**Uniform Resource Locator (URL)**  
**Web Services Description Language (WSDL)**  
**XML namespace**  
**XML schema**

The following terms are specific to this document:

**real item:** An item that can be stored in a mail server database, such as a calendar item, task, or contact.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXWSATT] Microsoft Corporation, "[Attachment Handling Web Service Protocol Specification](#)".

[MS-OXWSBTRF] Microsoft Corporation, "[Bulk Transfer Web Service Protocol Specification](#)".

[MS-OXWSCEXT] Microsoft Corporation, "[Client Extension Web Service Protocol Specification](#)".

[MS-OXWSCONT] Microsoft Corporation, "[Contacts Web Service Protocol Specification](#)".

[MS-OXWSCONV] Microsoft Corporation, "[Conversations Web Service Protocol Specification](#)".

[MS-OXWSCORE] Microsoft Corporation, "[Core Items Web Service Protocol Specification](#)".

[MS-OXWSCVTID] Microsoft Corporation, "[Convert Item Identifier Web Service Protocol Specification](#)".

[MS-OXWSDLIST] Microsoft Corporation, "[Distribution List Creation and Usage Web Service Protocol Specification](#)".

[MS-OXWSEDISC] Microsoft Corporation, "[Electronic Discovery \(eDiscovery\) Web Service Protocol Specification](#)".

[MS-OXWSFOLD] Microsoft Corporation, "[Folders and Folder Permissions Web Service Protocol Specification](#)".

[MS-OXWSGTRM] Microsoft Corporation, "[Get Rooms List Web Service Protocol Specification](#)".

[MS-OXWSGTZ] Microsoft Corporation, "[Get Server Time Zone Web Service Protocol Specification](#)".

[MS-OXWSMSG] Microsoft Corporation, "[E-Mail Message Types Web Service Protocol Specification](#)".

[MS-OXWSMSHR] Microsoft Corporation, "[Folder Sharing Web Service Protocol Specification](#)".

[MS-OXWSMTGS] Microsoft Corporation, "[Calendaring Web Service Protocol Specification](#)".

[MS-OXWSMTRK] Microsoft Corporation, "[Message Tracking Web Service Protocol Specification](#)".

[MS-OXWSNTIF] Microsoft Corporation, "[Notifications Web Service Protocol Specification](#)".

[MS-OXWSPED] Microsoft Corporation, "[Password Expiration Date Web Service Protocol Specification](#)".

[MS-OXWSPOST] Microsoft Corporation, "[Post Items Web Service Protocol Specification](#)".

[MS-OXWSPSNTIF] Microsoft Corporation, "[Push Notifications Web Service Protocol Specification](#)".

[MS-OXWSRSLNM] Microsoft Corporation, "[Resolve Recipient Names Web Service Protocol Specification](#)".

[MS-OXWSSRCH] Microsoft Corporation, "[Mailbox Search Web Service Protocol Specification](#)".

[MS-OXWSSYNC] Microsoft Corporation, "[Mailbox Contents Synchronization Web Service Protocol Specification](#)".

[MS-OXWSTASK] Microsoft Corporation, "[Tasks Web Service Protocol Specification](#)".

[MS-OXWSUSRCFG] Microsoft Corporation, "[User Configuration Web Service Protocol Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC3066] Alvestrand, H., "Tags for the Identification of Language", RFC 3066, January 2001, <http://www.ietf.org/rfc/rfc3066.txt>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA0] Fallside, D., Ed. and Walmsley, P., Ed., "XML Schema Part 0: Primer, Second Edition", W3C Recommendation, October 2004, <http://www.w3.org/TR/2004/REC-xmlschema-0-20041028/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

### 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

### 1.3 Overview

The common Web Service data types are the global elements, types, groups, and attribute groups that are common across the Web service protocols.

### 1.4 Relationship to Other Protocols

These data types are used by two or more Web service protocols.



For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

### **1.5 Prerequisites/Preconditions**

None.

### **1.6 Applicability Statement**

These data types are shared by two or more Web service protocols.

### **1.7 Versioning and Capability Negotiation**

None.

### **1.8 Vendor-Extensible Fields**

None.

### **1.9 Standards Assignments**

None.

## 2 Messages

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The **WSDL** in this specification provides a base description of the protocol. The schema in this specification provides a base description of the message syntax. The text that specifies the WSDL and schema might specify restrictions that reflect actual protocol behavior. For example, the schema definition might allow for an element to be **empty**, **null**, or **not present** but the behavior of the protocol as specified restricts the same elements to being **non-empty**, **not null**, or **present**.

### 2.1 Transport

None.

### 2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and Web Services Description Language (WSDL), as defined in [\[WSDL\]](#).

#### 2.2.1 Namespaces

This specification defines and references various **XML namespaces** by using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
<b>m</b>	<a href="http://schemas.microsoft.com/exchange/services/2006/messages">http://schemas.microsoft.com/exchange/services/2006/messages</a>	
<b>t</b>	<a href="http://schemas.microsoft.com/exchange/services/2006/types">http://schemas.microsoft.com/exchange/services/2006/types</a>	
<b>xs</b>	<a href="http://www.w3.org/2001/XMLSchema">http://www.w3.org/2001/XMLSchema</a>	<a href="#">[XMLSCHEMA1]</a>
<b>tns</b>	<a href="http://schemas.microsoft.com/exchange/services/2006/messages">http://schemas.microsoft.com/exchange/services/2006/messages</a>	
<b>targetNamespace</b>	<a href="http://schemas.microsoft.com/exchange/services/2006/messages">http://schemas.microsoft.com/exchange/services/2006/messages</a>	

#### 2.2.2 Messages

This specification does not define any common WSDL message definitions.

#### 2.2.3 Simple Types

Simple type	Description
<b>BodyTypeResponseType</b>	Specifies the type of content that is returned for the body of an item.
<b>BodyTypeType</b>	Specifies the item body content type.
<b>DateTimePrecisionType</b>	Specifies the precision for returned date/time values. <a href="#">&lt;1&gt;</a>
<b>DayOfWeekIndexType</b>	Specifies which week in a month is used in a relative recurrence pattern.

Simple type	Description
<b>DayOfWeekType</b>	Specifies days of the week that are used in item recurrence patterns.
<b>DaysOfWeekType</b>	Specifies days of the week that are used in item recurrence patterns.
<b>DefaultShapeNamesType</b>	Specifies standard sets of properties to return in an item or folder response.
<b>DictionaryURIType</b>	Specifies frequently referenced dictionary properties by <b>URI</b> .
<b>DisposalType</b>	Specifies how an item or folder is deleted.
<b>DistinguishedFolderIdNameType</b>	Specifies well-known folders that can be referenced by name. <2>
<b>DistinguishedPropertySetType</b>	Specifies the well-known property set IDs for extended properties.
<b>DistinguishedUserType</b>	Specifies distinguished user accounts.
<b>ExceptionPropertyURIType</b>	Specifies an offending property path in an error.
<b>ExchangeVersionType</b>	Specifies the schema version to target for a request. <3>
<b>ExcludesAttributeType</b>	Specifies a decimal or hexadecimal bitmask for an exclude restriction.
<b>IconIndexType</b>	Specifies the icons to display. <4>
<b>LegacyFreeBusyType</b>	Specifies the <b>free/busy status</b> for calendar items and meeting requests.
<b>MailboxTypeType</b>	Specifies the type of <b>mailbox</b> that is represented by an e-mail address.
<b>MonthNamesType</b>	Specifies the month in which a yearly recurring item occurs.
<b>NonEmptyStringType</b>	Specifies a string that MUST have a minimum of one character.
<b>PredictedMessageActionType</b>	Specifies the predicted next action to be taken. <5>
<b>ResponseClassType</b>	Specifies the status states of a response.
<b>ResponseCodeType</b>	Specifies status information for the request. <6>
<b>SensitivityChoicesType</b>	Specifies the sensitivity level types that are available for an item.
<b>UnindexedFieldURIType</b>	Specifies unindexed properties. <7>

### 2.2.3.1 t:BodyTypeResponseType Simple Type

The **BodyTypeResponseType** simple type specifies the type of content that is returned for the body of an item.

```
<xs:simpleType name="BodyTypeResponseType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Best"/>
    <xs:enumeration value="HTML"/>
    <xs:enumeration value="Text"/>
  </xs:restriction>
</xs:simpleType>
```

```

    </xs:restriction>
</xs:simpleType>

```

The values that are defined by the **BodyTypeResponseType** simple type are listed in the following table.

Value	Meaning
<b>Best</b>	Specifies that the response returns the richest available body content. This is useful if it is unknown whether the content is text or <b>HTML</b> .
<b>HTML</b>	Specifies that the response returns an item body as HTML.
<b>Text</b>	Specifies that the response returns an item body as <b>plain text</b> .

### 2.2.3.2 t:BodyTypeType Simple Type

The **BodyTypeType** simple type specifies the item body content type.

```

<xs:simpleType name="BodyTypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="HTML"/>
    <xs:enumeration value="Text"/>
  </xs:restriction>
</xs:simpleType>

```

The values that are defined by the **BodyTypeType** simple type are listed in the following table.

Value	Meaning
<b>HTML</b>	Specifies the item body as HTML content.
<b>Text</b>	Specifies the item body as text content.

### 2.2.3.3 t:DateTimePrecisionType Simple Type

The **DateTimePrecisionType** simple type specifies the precision for returned date/time values. [<8>](#)

```

<xs:simpleType name="DateTimePrecisionType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Seconds"/>
    <xs:enumeration value="Milliseconds"/>
  </xs:restriction>
</xs:simpleType>

```

The values that are defined by the **DateTimePrecisionType** simple type are listed in the following table.

Value	Meaning
<b>Seconds</b>	Specifies that the precision for date/time return values is seconds.
<b>Milliseconds</b>	Specifies that the precision for date/time return values is milliseconds.

### 2.2.3.4 t:DayOfWeekIndexType Simple Type

The **DayOfWeekIndexType** simple type specifies which week in a month is used in a relative recurrence pattern.

```
<xs:simpleType name="DayOfWeekIndexType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="First"/>
    <xs:enumeration value="Fourth"/>
    <xs:enumeration value="Last"/>
    <xs:enumeration value="Second"/>
    <xs:enumeration value="Third"/>
  </xs:restriction>
</xs:simpleType>
```

The values that are defined by the **DayOfWeekIndexType** simple type are listed in the following table.

Value	Meaning
<b>First</b>	Specifies that the first week in the month is used in the recurrence pattern.
<b>Fourth</b>	Specifies that the fourth week in the month is used in the recurrence pattern.
<b>Last</b>	Specifies that the last week in the month is used in the recurrence pattern.
<b>Second</b>	Specifies that the second week in the month is used in the recurrence pattern.
<b>Third</b>	Specifies that the third week in the month is used in the recurrence pattern.

### 2.2.3.5 t:DayOfWeekType Simple Type

The **DayOfWeekType** simple type specifies days of the week that are used in item recurrence patterns.

```
<xs:simpleType name="DayOfWeekType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Day"/>
    <xs:enumeration value="Friday"/>
    <xs:enumeration value="Monday"/>
    <xs:enumeration value="Saturday"/>
    <xs:enumeration value="Sunday"/>
    <xs:enumeration value="Thursday"/>
    <xs:enumeration value="Tuesday"/>
    <xs:enumeration value="Wednesday"/>
    <xs:enumeration value="Weekday"/>
    <xs:enumeration value="WeekendDay"/>
  </xs:restriction>
</xs:simpleType>
```

```
</xs:simpleType>
```

The values that are defined by the **DayOfWeekType** simple type are listed in the following table.

Value	Meaning
<b>Day</b>	Identifies every day as part of the recurrence pattern. This value MUST NOT be used in the <b>t:RelativeYearlyRecurrencePatternType</b> (section <a href="#">2.2.4.53</a> ) and <b>t:WeeklyRecurrencePatternType</b> (section <a href="#">2.2.4.64</a> ) complex types.
<b>Friday</b>	Identifies Fridays as part of the recurrence pattern.
<b>Monday</b>	Identifies Mondays as part of the recurrence pattern.
<b>Saturday</b>	Identifies Saturdays as part of the recurrence pattern.
<b>Sunday</b>	Identifies Sundays as part of the recurrence pattern.
<b>Thursday</b>	Identifies Thursdays as part of the recurrence pattern.
<b>Tuesday</b>	Identifies Tuesdays as part of the recurrence pattern.
<b>Wednesday</b>	Identifies Wednesdays as part of the recurrence pattern.
<b>Weekday</b>	Identifies weekdays as part of the recurrence pattern. This value MUST NOT be used in the <b>t:RelativeYearlyRecurrencePatternType</b> and <b>t:WeeklyRecurrencePatternType</b> complex types.
<b>WeekendDay</b>	Identifies weekend days as part of the recurrence pattern. This value MUST NOT be used in the <b>t:RelativeYearlyRecurrencePatternType</b> and <b>t:WeeklyRecurrencePatternType</b> complex types.

### 2.2.3.6 t:DaysOfWeekType Simple Type

The **DaysOfWeekType** simple type specifies days of the week that are used in item recurrence patterns.

```
<xs:simpleType name="DaysOfWeekType">  
  <xs:list>  
    <xs:itemType name="t:DayOfWeekType"/>  
  </xs:list>  
</xs:simpleType>
```

The values for this type are defined in section [2.2.3.5](#).

The following is the syntax for this type.

```
<xs:simpleType name="DaysOfWeekType">  
  <xs:list itemType="t:DayOfWeekType"/>  
</xs:simpleType>
```

### 2.2.3.7 t:DefaultShapeNamesType Simple Type

The **DefaultShapeNamesType** simple type specifies standard sets of properties to return in an item or folder response.

```
<xs:simpleType name="DefaultShapeNamesType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="AllProperties"/>
    <xs:enumeration value="Default"/>
    <xs:enumeration value="IdOnly"/>
  </xs:restriction>
</xs:simpleType>
```

The values that are defined by the **DefaultShapeNamesType** simple type are listed in the following table.

Value	Meaning
<b>AllProperties</b>	Specifies all the properties that are defined for the <b>AllProperties</b> shape. This option does not specify all available properties for an item or folder.
<b>Default</b>	Specifies a set of properties that are defined as the default for the item or folder.
<b>IdOnly</b>	Specifies only the item or folder ID.

### 2.2.3.8 t:DictionaryURIType Simple Type

The **DictionaryURIType** simple type specifies frequently referenced dictionary properties by URI.

```
<xs:simpleType name="DictionaryURIType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="contactsEmailAddress"/>
    <xs:enumeration value="contactsImAddress"/>
    <xs:enumeration value="contactsPhoneNumber"/>
    <xs:enumeration value="contactsPhysicalAddressCity"/>
    <xs:enumeration value="contactsPhysicalAddressCountryOrRegion"/>
    <xs:enumeration value="contactsPhysicalAddressPostalCode"/>
    <xs:enumeration value="contactsPhysicalAddressState"/>
    <xs:enumeration value="contactsPhysicalAddressStreet"/>
    <xs:enumeration value="itemInternetMessageHeader"/>
  </xs:restriction>
</xs:simpleType>
```

The values that are defined by the **DictionaryURIType** simple type are listed in the following table.

Value	Meaning
<b>contactsEmailAddress</b>	Specifies the <b>EmailAddresses</b> property.
<b>contactsImAddress</b>	Specifies the <b>ImAddresses</b> property.
<b>contactsPhoneNumber</b>	Specifies the <b>PhoneNumbers</b> property.

Value	Meaning
<b>contactsPhysicalAddressCity</b>	Specifies the <b>PhysicalAddressCity</b> property.
<b>contactsPhysicalAddressCountryOrRegion</b>	Specifies the <b>PhysicalAddressCountryOrRegion</b> property.
<b>contactsPhysicalAddressPostalCode</b>	Specifies the <b>PhysicalAddressPostalCode</b> property.
<b>contactsPhysicalAddressState</b>	Specifies the <b>PhysicalAddressState</b> property.
<b>contactsPhysicalAddressStreet</b>	Specifies the <b>PhysicalAddressStreet</b> property.
<b>itemInternetMessageHeader</b>	Specifies the <b>InternetMessageHeader</b> property.

### 2.2.3.9 t:DisposalType Simple Type

The **DisposalType** simple type specifies how an item or folder is deleted.

```
<xs:simpleType name="DisposalType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="HardDelete"/>
    <xs:enumeration value="MoveToDeletedItems"/>
    <xs:enumeration value="SoftDelete"/>
  </xs:restriction>
</xs:simpleType>
```

The values that are defined by the **DisposalType** simple type are listed in the following table.

Value	Meaning
<b>HardDelete</b>	Specifies that an item or folder is permanently removed from the store.
<b>MoveToDeletedItems</b>	Specifies that an item or folder is moved to the <b>Deleted Items folder</b> .
<b>SoftDelete</b>	Specifies that an item or folder is moved to the dumpster if the dumpster is enabled.

The **DeleteFolderType** complex type, as specified in [\[MS-OXWSFOLD\]](#) section 3.1.4.4.3.2, and **DeleteItemType** complex type, as specified in [\[MS-OXWSCORE\]](#) section 3.1.4.3.3.2, MUST specify a value for the **DisposalType** simple type.

### 2.2.3.10 t:DistinguishedFolderIdNameType Simple Type

The **DistinguishedFolderIdNameType** simple type specifies well-known folders that can be referenced by name. [<9>](#)

```
<xs:simpleType name="DistinguishedFolderIdNameType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="calendar"/>
    <xs:enumeration value="contacts"/>
    <xs:enumeration value="deleteditems"/>
    <xs:enumeration value="drafts"/>
    <xs:enumeration value="inbox"/>
    <xs:enumeration value="journal"/>
  </xs:restriction>
</xs:simpleType>
```



```

<xs:enumeration value="junkemail"/>
<xs:enumeration value="msgfolderroot"/>
<xs:enumeration value="notes"/>
<xs:enumeration value="outbox"/>
<xs:enumeration value="publicfoldersroot"/>
<xs:enumeration value="root"/>
<xs:enumeration value="searchfolders"/>
<xs:enumeration value="sentitems"/>
<xs:enumeration value="tasks"/>
<xs:enumeration value="voicemail"/>
<xs:enumeration value="recoverableitemsroot"/>
<xs:enumeration value="recoverableitemsdeletions"/>
<xs:enumeration value="recoverableitemsversions"/>
<xs:enumeration value="recoverableitemspurges"/>
<xs:enumeration value="archiveroot"/>
<xs:enumeration value="archivemsgfolderroot"/>
<xs:enumeration value="archiveddeleteditems"/>
<xs:enumeration value="archiverecoverableitemsroot"/>
<xs:enumeration value="archiverecoverableitemsdeletions"/>
<xs:enumeration value="archiverecoverableitemsversions"/>
<xs:enumeration value="archiverecoverableitemspurges"/>
<xs:enumeration value="syncissues"/>
<xs:enumeration value="conflicts"/>
<xs:enumeration value="localfailures"/>
<xs:enumeration value="serverfailures"/>
<xs:enumeration value="recipientcache"/>
<xs:enumeration value="quickcontacts"/>
<xs:enumeration value="conversationhistory"/>
<xs:enumeration value="adminauditlogs"/>
<xs:enumeration value="todosearch"/>
<xs:enumeration value="mycontacts"/>
<xs:enumeration value="directory" />
<xs:enumeration value="imcontactlist"/>
<xs:enumeration value="peopleconnect" />
</xs:restriction>
</xs:simpleType>

```

The following table lists the values that are defined by the **DistinguishedFolderIdNameType** simple type.

Value	Meaning
<b>calendar</b>	Specifies the default <b>Calendar folder</b> .
<b>contacts</b>	Specifies the default Contacts folder.
<b>deleteditems</b>	Specifies the Deleted Items folder.
<b>drafts</b>	Specifies the free/busy status.
<b>inbox</b>	Specifies the <b>Inbox folder</b> .
<b>journal</b>	Specifies the Journal folder.
<b>junkemail</b>	Specifies the <b>Junk E-mail folder</b> .
<b>msgfolderroot</b>	Specifies the message folder root.

Value	Meaning
<b>notes</b>	Specifies the Notes folder.
<b>outbox</b>	Specifies the <b>Outbox folder</b> .
<b>publicfoldersroot</b>	Specifies the root <b>public folder</b> .
<b>root</b>	Specifies the root of the mailbox.
<b>searchfolders</b>	Specifies the Search Folders folder.
<b>sentitems</b>	Specifies the <b>Sent Items folder</b> .
<b>tasks</b>	Specifies the Tasks folder.
<b>voicemail</b>	Specifies the Voice Mail folder.
<b>recoverableitemsroot</b>	Specifies the dumpster root folder.
<b>recoverableitemsdeletions</b>	Specifies the dumpster deletions folder.
<b>recoverableitemsversions</b>	Specifies the dumpster versions folder.
<b>recoverableitemspurges</b>	Specifies the dumpster purges folder.
<b>archiveroot</b>	Specifies the root archive folder.
<b>archivemsgfolderroot</b>	Specifies the root archive message folder.
<b>archivedeleteditems</b>	Specifies the archive Deleted Items folder.
<b>archiverecoverableitemsroot</b>	Specifies the archive recoverable items root folder.
<b>archiverecoverableitemsdeletions</b>	Specifies the archive recoverable items deletions folder.
<b>archiverecoverableitemsversions</b>	Specifies the archive recoverable items versions folder.
<b>archiverecoverableitemspurges</b>	Specifies the archive recoverable items purges folder.
<b>syncissues</b>	Specifies the sync issues folder. <a href="#">&lt;10&gt;</a>
<b>conflicts</b>	Specifies the conflicts folder.
<b>localfailures</b>	Specifies the local failures folder. <a href="#">&lt;11&gt;</a>
<b>serverfailures</b>	Specifies the server failures folder. <a href="#">&lt;12&gt;</a>
<b>recipientcache</b>	Specifies the recipient cache folder. <a href="#">&lt;13&gt;</a>
<b>quickcontacts</b>	Specifies the quick contacts folder. <a href="#">&lt;14&gt;</a>
<b>conversationhistory</b>	Specifies the conversation history folder. <a href="#">&lt;15&gt;</a>
<b>adminauditlogs</b>	Specifies the admin audit logs folder. <a href="#">&lt;16&gt;</a>
<b>todosearch</b>	Specifies the to do search folder. <a href="#">&lt;17&gt;</a>
<b>mycontacts</b>	Specifies the my contacts folder. <a href="#">&lt;18&gt;</a>
<b>directory</b>	Specifies a directory. <a href="#">&lt;19&gt;</a>

Value	Meaning
<b>imcontactlist</b>	Specifies the IM contact list folder.
<b>peopleconnect</b>	Specifies the folder that is used for social networks. <20>

### 2.2.3.11 t:DistinguishedPropertySetType Simple Type

The **DistinguishedPropertySetType** simple type specifies the well-known property set IDs for extended properties.

```
<xs:simpleType name="DistinguishedPropertySetType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Address"/>
    <xs:enumeration value="Appointment"/>
    <xs:enumeration value="CalendarAssistant"/>
    <xs:enumeration value="Common"/>
    <xs:enumeration value="InternetHeaders"/>
    <xs:enumeration value="Meeting"/>
    <xs:enumeration value="PublicStrings"/>
    <xs:enumeration value="UnifiedMessaging"/>
    <xs:enumeration value="Task"/>
    <xs:enumeration value="Sharing"/>
  </xs:restriction>
</xs:simpleType>
```

The values that are defined by the **DistinguishedPropertySetType** simple type are listed in the following table.

Value	Meaning
<b>Address</b>	Specifies the address property set ID by name.
<b>Appointment</b>	Specifies the appointment property set ID by name.
<b>CalendarAssistant</b>	Specifies the calendar assistant property set ID by name.
<b>Common</b>	Specifies the common property set ID by name.
<b>InternetHeaders</b>	Specifies the Internet headers property set ID by name.
<b>Meeting</b>	Specifies the meeting property set ID by name.
<b>PublicStrings</b>	Specifies the public strings property set ID by name.
<b>UnifiedMessaging</b>	Specifies the Unified Messaging property set ID by name.
<b>Task</b>	Specifies the task property set ID by name.
<b>Sharing</b>	Specifies the sharing property set ID by name. <21>

### 2.2.3.12 t:DistinguishedUserType Simple Type

The **DistinguishedUserType** simple type specifies distinguished user accounts.

```

<xs:simpleType name="DistinguishedUserType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default"/>
    <xs:enumeration value="Anonymous"/>
  </xs:restriction>
</xs:simpleType>

```

The values that are defined by the **DistinguishedUserType** simple type are listed in the following table.

Value	Meaning
<b>Default</b>	Specifies the default user account.
<b>Anonymous</b>	Specifies the anonymous user account.

### 2.2.3.13 t:ExceptionPropertyURIType Simple Type

The **ExceptionPropertyURIType** simple type specifies an offending property path in an error.

```

<xs:simpleType name="ExceptionPropertyURIType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="attachmentContent"/>
    <xs:enumeration value="attachmentContentType"/>
    <xs:enumeration value="attachmentName"/>
    <xs:enumeration value="recurrenceDayOfMonth"/>
    <xs:enumeration value="recurrenceDayOfWeekIndex"/>
    <xs:enumeration value="recurrenceDaysOfWeek"/>
    <xs:enumeration value="recurrenceInterval"/>
    <xs:enumeration value="recurrenceMonth"/>
    <xs:enumeration value="recurrenceNumberOfOccurrences"/>
    <xs:enumeration value="timezoneOffset"/>
  </xs:restriction>
</xs:simpleType>

```

The values that are defined by the **ExceptionPropertyURIType** simple type are listed in the following table.

Value	Meaning
<b>attachmentContent</b>	Specifies that the attachment <b>Content</b> property contains an error.
<b>attachmentContentType</b>	Specifies that the attachment <b>ContentType</b> property contains an error.
<b>attachmentName</b>	Specifies that the attachment <b>Name</b> property contains an error.
<b>recurrenceDayOfMonth</b>	Specifies that the recurrence <b>DayOfMonth</b> property contains an error.
<b>recurrenceDayOfWeekIndex</b>	Specifies that the recurrence <b>DayOfWeekIndex</b> property contains an error.

Value	Meeting
<b>recurrenceDaysOfWeek</b>	Specifies that the recurrence <b>DaysOfWeek</b> property contains an error.
<b>recurrenceInterval</b>	Specifies that the recurrence <b>Interval</b> property contains an error.
<b>recurrenceMonth</b>	Specifies that the recurrence <b>Month</b> property contains an error.
<b>recurrenceNumberOfOccurrences</b>	Specifies that the recurrence <b>NumberOfOccurrences</b> property contains an error.
<b>timezoneOffset</b>	Specifies that the time zone <b>Offset</b> property contains an error.

### 2.2.3.14 t:ExchangeVersionType Simple Type

The **ExchangeVersionType** simple type specifies the schema version to target for a request. [<22>](#)

```
<xs:simpleType name="ExchangeVersionType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Exchange2007"/>
    <xs:enumeration value="Exchange2007_SP1"/>
    <xs:enumeration value="Exchange2010"/>
    <xs:enumeration value="Exchange2010_SP1"/>
    <xs:enumeration value="Exchange2010_SP2"/>
    <xs:enumeration value="Exchange2013"/>
  </xs:restriction>
</xs:simpleType>
```

The values that are defined by the **ExchangeVersionType** simple type are listed in the following table.

Value	Meaning
<b>Exchange2007</b>	Specifies the first version of the target Web service schema. <a href="#">&lt;23&gt;</a>
<b>Exchange2007_SP1</b>	Specifies the second version of the target Web service schema. <a href="#">&lt;24&gt;</a>
<b>Exchange2010</b>	Specifies the third version of the target Web service schema. <a href="#">&lt;25&gt;</a>
<b>Exchange2010_SP1</b>	Specifies the fourth version of the target Web service schema. <a href="#">&lt;26&gt;</a>
<b>Exchange2010_SP2</b>	Specifies the fifth version of the target Web service schema. <a href="#">&lt;27&gt;</a>
<b>Exchange2013</b>	Specifies the sixth version of the target Web service schema. <a href="#">&lt;28&gt;</a>

### 2.2.3.15 t:ExcludesAttributeType Simple Type

The **ExcludesAttributeType** simple type specifies a decimal or hexadecimal bitmask for an exclude restriction.

```
<xs:simpleType name="ExcludesAttributeType">
  <xs:restriction base="xs:string">
    <xs:pattern value="((0x|0X)[0-9A-Fa-f]*)|([0-9]*)"/>
  </xs:restriction>
```

```
</xs:simpleType>
```

The following pattern is defined by the **ExcludesAttributeType** simple type.

```
((0x|0X) [0-9A-Fa-f]*) | ([0-9]*)
```

### 2.2.3.16 t:IconIndexType Simple Type

The **IconIndexType** simple type specifies the icons to display. [<29>](#)

```
<xs:simpleType name="IconIndexType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default"/>
    <xs:enumeration value="PostItem"/>
    <xs:enumeration value="MailRead"/>
    <xs:enumeration value="MailUnread"/>
    <xs:enumeration value="MailReplied"/>
    <xs:enumeration value="MailForwarded"/>
    <xs:enumeration value="MailEncrypted"/>
    <xs:enumeration value="MailSmimeSigned"/>
    <xs:enumeration value="MailEncryptedReplied"/>
    <xs:enumeration value="MailSmimeSignedReplied"/>
    <xs:enumeration value="MailEncryptedForwarded"/>
    <xs:enumeration value="MailSmimeSignedForwarded"/>
    <xs:enumeration value="MailEncryptedRead"/>
    <xs:enumeration value="MailSmimeSignedRead"/>
    <xs:enumeration value="MailIrm"/>
    <xs:enumeration value="MailIrmForwarded"/>
    <xs:enumeration value="MailIrmReplied"/>
    <xs:enumeration value="SmsSubmitted"/>
    <xs:enumeration value="SmsRoutedToDeliveryPoint"/>
    <xs:enumeration value="SmsRoutedToExternalMessagingSystem"/>
    <xs:enumeration value="SmsDelivered"/>
    <xs:enumeration value="OutlookDefaultForContacts"/>
    <xs:enumeration value="AppointmentItem"/>
    <xs:enumeration value="AppointmentRecur"/>
    <xs:enumeration value="AppointmentMeet"/>
    <xs:enumeration value="AppointmentMeetRecur"/>
    <xs:enumeration value="AppointmentMeetNY"/>
    <xs:enumeration value="AppointmentMeetYes"/>
    <xs:enumeration value="AppointmentMeetNo"/>
    <xs:enumeration value="AppointmentMeetMaybe"/>
    <xs:enumeration value="AppointmentMeetCancel"/>
    <xs:enumeration value="AppointmentMeetInfo"/>
    <xs:enumeration value="TaskItem"/>
    <xs:enumeration value="TaskRecur"/>
    <xs:enumeration value="TaskOwned"/>
    <xs:enumeration value="TaskDelegated"/>
  </xs:restriction>
</xs:simpleType>
```

The following table describes the values defined by the **IconIndexType** simple type.

Value	Meaning
Default	Specifies the default icon.
PostItem	Specifies the icon for a post item ( <a href="#">[MS-OXWSPOST]</a> section 2.2.4.1).
MailRead	Specifies the mail read icon.
MailUnread	Specifies the unread mail icon.
MailReplied	Specifies the replied to mail icon.
MailForwarded	Specifies the forwarded mail icon.
MailEncrypted	Specifies the encrypted mail icon.
MailSmimeSigned	Specifies the <b>S/MIME (Secure/Multipurpose Internet Mail Extensions)</b> signed mail icon.
MailEncryptedReplied	Specifies the encrypted replied to mail icon.
MailSmimeSignedReplied	Specifies the S/MIME signed replied to mail icon.
MailEncryptedForwarded	Specifies the encrypted forwarded mail icon.
MailSmimeSignedForwarded	Specifies the S/MIME signed forwarded mail icon.
MailEncryptedRead	Specifies the encrypted read mail icon.
MailSmimeSignedRead	Specifies the S/MIME signed read mail icon.
MailIrm	Specifies the <b>Information Rights Management (IRM)</b> -protected mail icon.
MailIrmForwarded	Specifies the IRM-protected forwarded mail icon.
MailIrmReplied	Specifies the IRM-protected replied to mail icon.
SmsSubmitted	Specifies the icon mail submitted for <b>Short Message Service (SMS)</b> routing.
SmsRoutedToDeliveryPoint	Specifies the icon for SMS routing to an external delivery point.
SmsRoutedToExternalMessagingSystem	Specifies the icon for SMS routing to an external messaging system.
SmsDelivered	Specifies the SMS delivered mail icon.
OutlookDefaultForContacts	Specifies the default icon for contacts.
AppointmentItem	Specifies the appointment item icon.
AppointmentRecur	Specifies the recurring appointment icon.
AppointmentMeet	Specifies the meeting icon.
AppointmentMeetRecur	Specifies the recurring meeting icon.
AppointmentMeetNY	Specifies the icon for a tentative response to the meeting .

Value	Meaning
AppointmentMeetYes	Specifies the meeting acceptance icon.
AppointmentMeetNo	Specifies the meeting declined icon.
AppointmentMeetMaybe	Specifies the icon for a maybe response to the meeting.
AppointmentMeetCancel	Specifies the meeting cancel icon.
AppointmentMeetInfo	Specifies the meeting information icon.
TaskItem	Specifies the task item icon.
TaskRecur	Specifies the <b>recurring task</b> icon.
TaskOwned	Specifies the task owned icon.
TaskDelegated	Specifies the task delegated icon.

### 2.2.3.17 t:LegacyFreeBusyType Simple Type

The **LegacyFreeBusyType** simple type specifies the free/busy status for calendar items and meeting requests.

```
<xs:simpleType name="LegacyFreeBusyType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Busy"/>
    <xs:enumeration value="Free"/>
    <xs:enumeration value="NoData"/>
    <xs:enumeration value="OOF"/>
    <xs:enumeration value="Tentative"/>
    <xs:enumeration value="WorkingElsewhere"/>
  </xs:restriction>
</xs:simpleType>
```

The values that are defined by the **LegacyFreeBusyType** simple type are listed in the following table.

Value	Meaning
<b>Busy</b>	Specifies the status as busy.
<b>Free</b>	Specifies the status as free.
<b>NoData</b>	Specifies that there is no data for that recipient.
<b>OOF</b>	Specifies the status as <b>Out of Office (OOF)</b> .
<b>Tentative</b>	Specifies the status as tentative.
<b>WorkingElsewhere</b>	Specifies the status as working outside the office. <30>

### 2.2.3.18 t:MailboxType Simple Type

The **MailboxType** simple type specifies the type of mailbox that is represented by an e-mail address.



```

<xs:simpleType name="MailboxTypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Unknown"/>
    <xs:enumeration value="OneOff"/>
    <xs:enumeration value="Contact"/>
    <xs:enumeration value="Mailbox"/>
    <xs:enumeration value="PrivateDL"/>
    <xs:enumeration value="PublicDL"/>
    <xs:enumeration value="PublicFolder"/>
  </xs:restriction>
</xs:simpleType>

```

The values that are defined by the **MailboxTypeType** simple type are listed in the following table.

Value	Meaning
<b>Unknown</b>	Specifies an unknown type of mailbox.
<b>OneOff</b>	Specifies a one-off member of a personal <b>distribution list</b> .
<b>Contact</b>	Specifies contact in a user's mailbox.
<b>Mailbox</b>	Specifies a mail-enabled directory service object.
<b>PrivateDL</b>	Specifies a private distribution list in a user's mailbox.
<b>PublicDL</b>	Specifies a public distribution list.
<b>PublicFolder</b>	Specifies a public folder.

The **MailboxTypeType** simple type is used in the **EmailAddressType** complex type, as specified in section [2.2.4.27](#).

### 2.2.3.19 t:MonthNamesType Simple Type

The **MonthNamesType** simple type specifies the month in which a yearly recurring item occurs.

```

<xs:simpleType name="MonthNamesType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="January"/>
    <xs:enumeration value="February"/>
    <xs:enumeration value="March"/>
    <xs:enumeration value="April"/>
    <xs:enumeration value="May"/>
    <xs:enumeration value="June"/>
    <xs:enumeration value="July"/>
    <xs:enumeration value="August"/>
    <xs:enumeration value="September"/>
    <xs:enumeration value="October"/>
    <xs:enumeration value="November"/>
    <xs:enumeration value="December"/>
  </xs:restriction>
</xs:simpleType>

```

The values that are defined by the **MonthNamesType** simple type are listed in the following table.

Value	Meaning
<b>January</b>	Specifies that a yearly recurring item occurs in January.
<b>February</b>	Specifies that a yearly recurring item occurs in February.
<b>March</b>	Specifies that a yearly recurring item occurs in March.
<b>April</b>	Specifies that a yearly recurring item occurs in April.
<b>May</b>	Specifies that a yearly recurring item occurs in May.
<b>June</b>	Specifies that a yearly recurring item occurs in June.
<b>July</b>	Specifies that a yearly recurring item occurs in July.
<b>August</b>	Specifies that a yearly recurring item occurs in August.
<b>September</b>	Specifies that a yearly recurring item occurs in September.
<b>October</b>	Specifies that a yearly recurring item occurs in October.
<b>November</b>	Specifies that a yearly recurring item occurs in November.
<b>December</b>	Specifies that a yearly recurring item occurs in December.

### 2.2.3.20 t:NonEmptyStringType Simple Type

The **NonEmptyStringType** simple type specifies a string that **MUST** have a minimum of one character.

```
<xs:simpleType name="NonEmptyStringType">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
  </xs:restriction>
</xs:simpleType>
```

### 2.2.3.21 PredictedMessageType

The **PredictedMessageType** simple type specifies the predicted next action to be taken. [<31>](#)

```
<xs:simpleType name="PredictedMessageType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None" />
    <xs:enumeration value="Respond" />
    <xs:enumeration value="FollowUp" />
    <xs:enumeration value="MoveToFolder" />
    <xs:enumeration value="Delete" />
    <xs:enumeration value="Read" />
    <xs:enumeration value="Ignore" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes possible values.

Value	Description
None	The item has no predicted next action.
Response	The predicted next action is a response.
FollowUp	The predicted next action is a followup.
MoveToFolder	The predicted next action is a move to a different folder.
Delete	The predicted next action is a deletion.
Read	The predicted next action is a read.
Ignore	The predicted next action is that the item will be ignored.

### 2.2.3.22 t:ResponseClassType Simple Type

The **ResponseClassType** simple type specifies the status states of a response.

```
<xs:simpleType name="ResponseClassType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Error"/>
    <xs:enumeration value="Success"/>
    <xs:enumeration value="Warning"/>
  </xs:restriction>
</xs:simpleType>
```

The values that are defined by the **ResponseClassType** simple type are listed in the following table.

Value	Meaning
<b>Error</b>	Specifies that the request could not be processed.
<b>Success</b>	Specifies that the request was successfully processed.
<b>Warning</b>	Specifies that an unusual situation was encountered during the processing of the request and the request was not processed successfully.

### 2.2.3.23 m:ResponseCodeType Simple Type

The **ResponseCodeType** simple type specifies status information for the request. [<32>](#)

```
<xs:simpleType name="ResponseCodeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NoError"/>
    <xs:enumeration value="ErrorAccessDenied"/>
    <xs:enumeration value="ErrorAccessModeSpecified"/>
    <xs:enumeration value="ErrorAccountDisabled"/>
    <xs:enumeration value="ErrorAddDelegatesFailed"/>
    <xs:enumeration value="ErrorAddressSpaceNotFound"/>
    <xs:enumeration value="ErrorADOperation"/>
  </xs:restriction>
</xs:simpleType>
```

```

<xs:enumeration value="ErrorADSessionFilter"/>
<xs:enumeration value="ErrorADUnavailable"/>
<xs:enumeration value="ErrorAffectedTaskOccurrencesRequired"/>
<xs:enumeration value="ErrorArchiveFolderPathCreation"/>
<xs:enumeration value="ErrorArchiveMailboxNotEnabled"/>
<xs:enumeration value="ErrorArchiveMailboxServiceDiscoveryFailed"/>
<xs:enumeration value="ErrorAvailabilityConfigNotFound"/>
<xs:enumeration value="ErrorBatchProcessingStopped"/>
<xs:enumeration value="ErrorCalendarCannotMoveOrCopyOccurrence"/>
<xs:enumeration value="ErrorCalendarCannotUpdateDeletedItem"/>
<xs:enumeration value="ErrorCalendarCannotUseIdForOccurrenceId"/>
<xs:enumeration value="ErrorCalendarCannotUseIdForRecurringMasterId"/>
<xs:enumeration value="ErrorCalendarDurationIsTooLong"/>
<xs:enumeration value="ErrorCalendarEndDateIsEarlierThanStartDate"/>
<xs:enumeration value="ErrorCalendarFolderIsInvalidForCalendarView"/>
<xs:enumeration value="ErrorCalendarInvalidAttributeValue"/>
<xs:enumeration value="ErrorCalendarInvalidDayForTimeChangePattern"/>
<xs:enumeration value="ErrorCalendarInvalidDayForWeeklyRecurrence"/>
<xs:enumeration value="ErrorCalendarInvalidPropertyState"/>
<xs:enumeration value="ErrorCalendarInvalidPropertyValue"/>
<xs:enumeration value="ErrorCalendarInvalidRecurrence"/>
<xs:enumeration value="ErrorCalendarInvalidTimeZone"/>
<xs:enumeration value="ErrorCalendarIsCancelledForAccept"/>
<xs:enumeration value="ErrorCalendarIsCancelledForDecline"/>
<xs:enumeration value="ErrorCalendarIsCancelledForRemove"/>
<xs:enumeration value="ErrorCalendarIsCancelledForTentative"/>
<xs:enumeration value="ErrorCalendarIsDelegatedForAccept"/>
<xs:enumeration value="ErrorCalendarIsDelegatedForDecline"/>
<xs:enumeration value="ErrorCalendarIsDelegatedForRemove"/>
<xs:enumeration value="ErrorCalendarIsDelegatedForTentative"/>
<xs:enumeration value="ErrorCalendarIsNotOrganizer"/>
<xs:enumeration value="ErrorCalendarIsOrganizerForAccept"/>
<xs:enumeration value="ErrorCalendarIsOrganizerForDecline"/>
<xs:enumeration value="ErrorCalendarIsOrganizerForRemove"/>
<xs:enumeration value="ErrorCalendarIsOrganizerForTentative"/>
<xs:enumeration
    value="ErrorCalendarOccurrenceIndexIsOutOfRecurrenceRange"/>
<xs:enumeration value="ErrorCalendarOccurrenceIsDeletedFromRecurrence"/>
<xs:enumeration value="ErrorCalendarOutOfRange"/>
<xs:enumeration value="ErrorCalendarMeetingRequestIsOutOfDate"/>
<xs:enumeration value="ErrorCalendarViewRangeTooBig"/>
<xs:enumeration value="ErrorCallerIsInvalidADAccount"/>
<xs:enumeration value="ErrorCannotArchiveCalendarContactTaskFolderException"/>
<xs:enumeration value="ErrorCannotArchiveItemsInPublicFolders"/>
<xs:enumeration value="ErrorCannotArchiveItemsInArchiveMailbo"/>
<xs:enumeration value="ErrorCannotCreateCalendarItemInNonCalendarFolder"/>
<xs:enumeration value="ErrorCannotCreateContactInNonContactFolder"/>
<xs:enumeration value="ErrorCannotCreatePostItemInNonMailFolder"/>
<xs:enumeration value="ErrorCannotCreateTaskInNonTaskFolder"/>
<xs:enumeration value="ErrorCannotDeleteObject"/>
<xs:enumeration value="ErrorCannotDisableMandatoryExtension"/>
<xs:enumeration value="ErrorCannotGetSourceFolderPath"/>
<xs:enumeration value="ErrorCannotGetExternalEcpUrl"/>
<xs:enumeration value="ErrorCannotOpenFileAttachment"/>
<xs:enumeration value="ErrorCannotDeleteTaskOccurrence"/>
<xs:enumeration value="ErrorCannotEmptyFolder"/>
<xs:enumeration
    value="ErrorCannotSetCalendarPermissionOnNonCalendarFolder"/>
<xs:enumeration

```

```

    value="ErrorCannotSetNonCalendarPermissionOnCalendarFolder"/>
<xs:enumeration value="ErrorCannotSetPermissionUnknownEntries"/>
<xs:enumeration value="ErrorCannotSpecifySearchFolderAsSourceFolder"/>
<xs:enumeration value="ErrorCannotUseFolderIdForItemId"/>
<xs:enumeration value="ErrorCannotUseItemIdForFolderId"/>
<xs:enumeration value="ErrorChangeKeyRequired"/>
<xs:enumeration value="ErrorChangeKeyRequiredForWriteOperations"/>
<xs:enumeration value="ErrorClientDisconnected"/>
<xs:enumeration value="ErrorClientIntentInvalidStateDefinition"/>
<xs:enumeration value="ErrorClientIntentNotFound"/>
<xs:enumeration value="ErrorConnectionFailed"/>
<xs:enumeration value="ErrorContainsFilterWrongType"/>
<xs:enumeration value="ErrorContentConversionFailed"/>
<xs:enumeration value="ErrorContentIndexingNotEnabled"/>
<xs:enumeration value="ErrorCorruptData"/>
<xs:enumeration value="ErrorCreateItemAccessDenied"/>
<xs:enumeration value="ErrorCreateManagedFolderPartialCompletion"/>
<xs:enumeration value="ErrorCreateSubfolderAccessDenied"/>
<xs:enumeration value="ErrorCrossMailboxMoveCopy"/>
<xs:enumeration value="ErrorCrossSiteRequest"/>
<xs:enumeration value="ErrorDataSizeLimitExceeded"/>
<xs:enumeration value="ErrorDataSourceOperation"/>
<xs:enumeration value="ErrorDelegateAlreadyExists"/>
<xs:enumeration value="ErrorDelegateCannotAddOwner"/>
<xs:enumeration value="ErrorDelegateMissingConfiguration"/>
<xs:enumeration value="ErrorDelegateNoUser"/>
<xs:enumeration value="ErrorDelegateValidationFailed"/>
<xs:enumeration value="ErrorDeleteDistinguishedFolder"/>
<xs:enumeration value="ErrorDeleteItemsFailed"/>
<xs:enumeration value="ErrorDeleteUnifiedMessagingPromptFailed"/>
<xs:enumeration value="ErrorDistinguishedUserNotSupported"/>
<xs:enumeration value="ErrorDistributionListMemberNotExist"/>
<xs:enumeration value="ErrorDuplicateInputFolderNames"/>
<xs:enumeration value="ErrorDuplicateUserIdsSpecified"/>
<xs:enumeration value="ErrorEmailAddressMismatch"/>
<xs:enumeration value="ErrorEventNotFound"/>
<xs:enumeration value="ErrorExceededConnectionCount"/>
<xs:enumeration value="ErrorExceededSubscriptionCount"/>
<xs:enumeration value="ErrorExceededFindCountLimit"/>
<xs:enumeration value="ErrorExpiredSubscription"/>
<xs:enumeration value="ErrorExtensionNotFound"/>
<xs:enumeration value="ErrorFolderCorrupt"/>
<xs:enumeration value="ErrorFolderNotFound"/>
<xs:enumeration value="ErrorFolderPropertRequestFailed"/>
<xs:enumeration value="ErrorFolderSave"/>
<xs:enumeration value="ErrorFolderSaveFailed"/>
<xs:enumeration value="ErrorFolderSavePropertyError"/>
<xs:enumeration value="ErrorFolderExists"/>
<xs:enumeration value="ErrorFreeBusyGenerationFailed"/>
<xs:enumeration value="ErrorGetServerSecurityDescriptorFailed"/>
<xs:enumeration value="ErrorImContactLimitReached"/>
<xs:enumeration value="ErrorImGroupDisplayNameAlreadyExists"/>
<xs:enumeration value="ErrorImGroupLimitReached"/>
<xs:enumeration value="ErrorImpersonateUserDenied"/>
<xs:enumeration value="ErrorImpersonationDenied"/>
<xs:enumeration value="ErrorImpersonationFailed"/>
<xs:enumeration value="ErrorIncorrectSchemaVersion"/>
<xs:enumeration value="ErrorIncorrectUpdatePropertyCount"/>
<xs:enumeration value="ErrorIndividualMailboxLimitReached"/>

```

```
<xs:enumeration value="ErrorInsufficientResources"/>
<xs:enumeration value="ErrorInternalServerError"/>
<xs:enumeration value="ErrorInternalServerErrorTransientError"/>
<xs:enumeration value="ErrorInvalidAccessLevel"/>
<xs:enumeration value="ErrorInvalidArgument"/>
<xs:enumeration value="ErrorInvalidAttachmentId"/>
<xs:enumeration value="ErrorInvalidAttachmentSubfilter"/>
<xs:enumeration value="ErrorInvalidAttachmentSubfilterTextFilter"/>
<xs:enumeration value="ErrorInvalidAuthorizationContext"/>
<xs:enumeration value="ErrorInvalidChangeKey"/>
<xs:enumeration value="ErrorInvalidClientSecurityContext"/>
<xs:enumeration value="ErrorInvalidCompleteDate"/>
<xs:enumeration value="ErrorInvalidContactEmailAddress"/>
<xs:enumeration value="ErrorInvalidContactEmailIndex"/>
<xs:enumeration value="ErrorInvalidCrossForestCredentials"/>
<xs:enumeration value="ErrorInvalidDelegatePermission"/>
<xs:enumeration value="ErrorInvalidDelegateUserId"/>
<xs:enumeration value="ErrorInvalidExcludesRestriction"/>
<xs:enumeration value="ErrorInvalidExpressionTypeForSubFilter"/>
<xs:enumeration value="ErrorInvalidExtendedProperty"/>
<xs:enumeration value="ErrorInvalidExtendedPropertyValue"/>
<xs:enumeration value="ErrorInvalidFolderId"/>
<xs:enumeration value="ErrorInvalidFolderTypeForOperation"/>
<xs:enumeration value="ErrorInvalidFractionalPagingParameters"/>
<xs:enumeration value="ErrorInvalidFreeBusyViewType"/>
<xs:enumeration value="ErrorInvalidId"/>
<xs:enumeration value="ErrorInvalidIdEmpty"/>
<xs:enumeration value="ErrorInvalidIdMalformed"/>
<xs:enumeration value="ErrorInvalidIdMalformedEwsLegacyIdFormat"/>
<xs:enumeration value="ErrorInvalidIdMonikerTooLong"/>
<xs:enumeration value="ErrorInvalidIdNotAnItemAttachmentId"/>
<xs:enumeration value="ErrorInvalidIdReturnedByResolveNames"/>
<xs:enumeration value="ErrorInvalidIdStoreObjectIdTooLong"/>
<xs:enumeration value="ErrorInvalidIdTooManyAttachmentLevels"/>
<xs:enumeration value="ErrorInvalidIdXml"/>
<xs:enumeration value="ErrorInvalidImContactId"/>
<xs:enumeration value="ErrorInvalidImDistributionGroupSmtppAddress"/>
<xs:enumeration value="ErrorInvalidImGroupId"/>
<xs:enumeration value="ErrorInvalidIndexedPagingParameters"/>
<xs:enumeration value="ErrorInvalidInternetHeaderChildNodes"/>
<xs:enumeration value="ErrorInvalidItemForOperationArchiveItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationCreateItemAttachment"/>
<xs:enumeration value="ErrorInvalidItemForOperationCreateItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationAcceptItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationDeclineItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationCancelItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationExpandDL"/>
<xs:enumeration value="ErrorInvalidItemForOperationRemoveItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationSendItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationTentative"/>
<xs:enumeration value="ErrorInvalidLogonType"/>
<xs:enumeration value="ErrorInvalidMailbox"/>
<xs:enumeration value="ErrorInvalidManagedFolderProperty"/>
<xs:enumeration value="ErrorInvalidManagedFolderQuota"/>
<xs:enumeration value="ErrorInvalidManagedFolderSize"/>
<xs:enumeration value="ErrorInvalidMergedFreeBusyInterval"/>
<xs:enumeration value="ErrorInvalidNameForNameResolution"/>
<xs:enumeration value="ErrorInvalidOperation"/>
<xs:enumeration value="ErrorInvalidNetworkServiceContext"/>
```

```
<xs:enumeration value="ErrorInvalidOofParameter"/>
<xs:enumeration value="ErrorInvalidPagingMaxRows"/>
<xs:enumeration value="ErrorInvalidParentFolder"/>
<xs:enumeration value="ErrorInvalidPercentCompleteValue"/>
<xs:enumeration value="ErrorInvalidPermissionSettings"/>
<xs:enumeration value="ErrorInvalidPhoneCallId"/>
<xs:enumeration value="ErrorInvalidPhoneNumber"/>
<xs:enumeration value="ErrorInvalidUserInfo"/>
<xs:enumeration value="ErrorInvalidPropertyAppend"/>
<xs:enumeration value="ErrorInvalidPropertyDelete"/>
<xs:enumeration value="ErrorInvalidPropertyForExists"/>
<xs:enumeration value="ErrorInvalidPropertyForOperation"/>
<xs:enumeration value="ErrorInvalidPropertyRequest"/>
<xs:enumeration value="ErrorInvalidPropertySet"/>
<xs:enumeration value="ErrorInvalidPropertyUpdateSentMessage"/>
<xs:enumeration value="ErrorInvalidProxySecurityContext"/>
<xs:enumeration value="ErrorInvalidPullSubscriptionId"/>
<xs:enumeration value="ErrorInvalidPushSubscriptionUrl"/>
<xs:enumeration value="ErrorInvalidRecipients"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilter"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilterComparison"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilterOrder"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilterTextFilter"/>
<xs:enumeration value="ErrorInvalidReferenceItem"/>
<xs:enumeration value="ErrorInvalidRequest"/>
<xs:enumeration value="ErrorInvalidRestriction"/>
<xs:enumeration value="ErrorInvalidRetentionTagTypeMismatch"/>
<xs:enumeration value="ErrorInvalidRetentionTagInvisible"/>
<xs:enumeration value="ErrorInvalidRetentionTagIdGuid"/>
<xs:enumeration value="ErrorInvalidRetentionTagInheritance"/>
<xs:enumeration value="ErrorInvalidRoutingType"/>
<xs:enumeration value="ErrorInvalidScheduledOofDuration"/>
<xs:enumeration value="ErrorInvalidSchemaVersionForMailboxVersion"/>
<xs:enumeration value="ErrorInvalidSecurityDescriptor"/>
<xs:enumeration value="ErrorInvalidSendItemSaveSettings"/>
<xs:enumeration value="ErrorInvalidSerializedAccessToken"/>
<xs:enumeration value="ErrorInvalidServerVersion"/>
<xs:enumeration value="ErrorInvalidSid"/>
<xs:enumeration value="ErrorInvalidSIPUri"/>
<xs:enumeration value="ErrorInvalidSmtAddress"/>
<xs:enumeration value="ErrorInvalidSubfilterType"/>
<xs:enumeration value="ErrorInvalidSubfilterTypeNotAttendeeType"/>
<xs:enumeration value="ErrorInvalidSubfilterTypeNotRecipientType"/>
<xs:enumeration value="ErrorInvalidSubscription"/>
<xs:enumeration value="ErrorInvalidSubscriptionRequest"/>
<xs:enumeration value="ErrorInvalidSyncStateData"/>
<xs:enumeration value="ErrorInvalidTimeInterval"/>
<xs:enumeration value="ErrorInvalidUserOofSettings"/>
<xs:enumeration value="ErrorInvalidUserPrincipalName"/>
<xs:enumeration value="ErrorInvalidUserSid"/>
<xs:enumeration value="ErrorInvalidUserSidMissingUPN"/>
<xs:enumeration value="ErrorInvalidValueForProperty"/>
<xs:enumeration value="ErrorInvalidWatermark"/>
<xs:enumeration value="ErrorIPGatewayNotFound"/>
<xs:enumeration value="ErrorIrresolvableConflict"/>
<xs:enumeration value="ErrorItemCorrupt"/>
<xs:enumeration value="ErrorItemNotFound"/>
<xs:enumeration value="ErrorItemPropertyRequestFailed"/>
<xs:enumeration value="ErrorItemSave"/>
```

```
<xs:enumeration value="ErrorItemSavePropertyError"/>
<xs:enumeration value="ErrorLegacyMailboxFreeBusyViewTypeNotMerged"/>
<xs:enumeration value="ErrorLocalServerObjectNotFound"/>
<xs:enumeration value="ErrorLogonAsNetworkServiceFailed"/>
<xs:enumeration value="ErrorMailboxConfiguration"/>
<xs:enumeration value="ErrorMailboxDataArrayEmpty"/>
<xs:enumeration value="ErrorMailboxDataArrayTooBig"/>
<xs:enumeration value="ErrorMailboxHoldNotFound"/>
<xs:enumeration value="ErrorMailboxLogonFailed"/>
<xs:enumeration value="ErrorMailboxMoveInProgress"/>
<xs:enumeration value="ErrorMailboxStoreUnavailable"/>
<xs:enumeration value="ErrorMailRecipientNotFound"/>
<xs:enumeration value="ErrorMailTipsDisabled"/>
<xs:enumeration value="ErrorManagedFolderAlreadyExists"/>
<xs:enumeration value="ErrorManagedFolderNotFound"/>
<xs:enumeration value="ErrorManagedFoldersRootFailure"/>
<xs:enumeration value="ErrorMeetingSuggestionGenerationFailed"/>
<xs:enumeration value="ErrorMessageDispositionRequired"/>
<xs:enumeration value="ErrorMessageSizeExceeded"/>
<xs:enumeration value="ErrorMimeContentConversionFailed"/>
<xs:enumeration value="ErrorMimeContentInvalid"/>
<xs:enumeration value="ErrorMimeContentInvalidBase64String"/>
<xs:enumeration value="ErrorMissingArgument"/>
<xs:enumeration value="ErrorMissingEmailAddress"/>
<xs:enumeration value="ErrorMissingEmailAddressForManagedFolder"/>
<xs:enumeration value="ErrorMissingInformationEmailAddress"/>
<xs:enumeration value="ErrorMissingInformationReferenceItemId"/>
<xs:enumeration value="ErrorMissingItemForCreateItemAttachment"/>
<xs:enumeration value="ErrorMissingManagedFolderId"/>
<xs:enumeration value="ErrorMissingRecipients"/>
<xs:enumeration value="ErrorMissingUserIdInformation"/>
<xs:enumeration value="ErrorMoreThanOneAccessModeSpecified"/>
<xs:enumeration value="ErrorMoveCopyFailed"/>
<xs:enumeration value="ErrorMoveDistinguishedFolder"/>
<xs:enumeration value="ErrorMultiLegacyMailboxAccess"/>
<xs:enumeration value="ErrorNameResolutionMultipleResults"/>
<xs:enumeration value="ErrorNameResolutionNoMailbox"/>
<xs:enumeration value="ErrorNameResolutionNoResults"/>
<xs:enumeration value="ErrorNoApplicableProxyCASServersAvailable"/>
<xs:enumeration value="ErrorNoCalendar"/>
<xs:enumeration value="ErrorNoDestinationCASDueToKerberosRequirements"/>
<xs:enumeration value="ErrorNoDestinationCASDueToSSLRequirements"/>
<xs:enumeration value="ErrorNoDestinationCASDueToVersionMismatch"/>
<xs:enumeration value="ErrorNoFolderClassOverride"/>
<xs:enumeration value="ErrorNoFreeBusyAccess"/>
<xs:enumeration value="ErrorNonExistentMailbox"/>
<xs:enumeration value="ErrorNonPrimarySmtPAddress"/>
<xs:enumeration value="ErrorNoPropertyTagForCustomProperties"/>
<xs:enumeration value="ErrorNoPublicFolderReplicaAvailable"/>
<xs:enumeration value="ErrorNoPublicFolderServerAvailable"/>
<xs:enumeration value="ErrorNoRespondingCASInDestinationSite"/>
<xs:enumeration value="ErrorNotDelegate"/>
<xs:enumeration value="ErrorNotEnoughMemory"/>
<xs:enumeration value="ErrorObjectTypeChanged"/>
<xs:enumeration value="ErrorOccurrenceCrossingBoundary"/>
<xs:enumeration value="ErrorOccurrenceTimeSpanTooBig"/>
<xs:enumeration value="ErrorOperationNotAllowedWithPublicFolderRoot"/>
<xs:enumeration value="ErrorParentFolderIdRequired"/>
<xs:enumeration value="ErrorParentFolderNotFound"/>
```



```

<xs:enumeration value="ErrorPasswordChangeRequired"/>
<xs:enumeration value="ErrorPasswordExpired"/>
<xs:enumeration value="ErrorPhoneNumberNotDialable"/>
<xs:enumeration value="ErrorPropertyUpdate"/>
<xs:enumeration value="ErrorPromptPublishingOperationFailed"/>
<xs:enumeration value="ErrorPropertyValidationFailure"/>
<xs:enumeration value="ErrorProxiedSubscriptionCallFailure"/>
<xs:enumeration value="ErrorProxyCallFailed"/>
<xs:enumeration value="ErrorProxyGroupSidLimitExceeded"/>
<xs:enumeration value="ErrorProxyRequestNotAllowed"/>
<xs:enumeration value="ErrorProxyRequestProcessingFailed"/>
<xs:enumeration value="ErrorProxyServiceDiscoveryFailed"/>
<xs:enumeration value="ErrorProxyTokenExpired"/>
<xs:enumeration value="ErrorPublicFolderMailboxDiscoveryFailed"/>
<xs:enumeration value="ErrorPublicFolderOperationFailed"/>
<xs:enumeration value="ErrorPublicFolderRequestProcessingFailed"/>
<xs:enumeration value="ErrorPublicFolderServerNotFound"/>
<xs:enumeration value="ErrorPublicFolderSyncException"/>
<xs:enumeration value="ErrorQueryFilterTooLong"/>
<xs:enumeration value="ErrorQuotaExceeded"/>
<xs:enumeration value="ErrorReadEventsFailed"/>
<xs:enumeration value="ErrorReadReceiptNotPending"/>
<xs:enumeration value="ErrorRecurrenceEndDateTooBig"/>
<xs:enumeration value="ErrorRecurrenceHasNoOccurrence"/>
<xs:enumeration value="ErrorRemoveDelegatesFailed"/>
<xs:enumeration value="ErrorRequestAborted"/>
<xs:enumeration value="ErrorRequestStreamTooBig"/>
<xs:enumeration value="ErrorRequiredPropertyMissing"/>
<xs:enumeration value="ErrorResolveNamesInvalidFolderType"/>
<xs:enumeration value="ErrorResolveNamesOnlyOneContactsFolderAllowed"/>
<xs:enumeration value="ErrorResponseSchemaValidation"/>
<xs:enumeration value="ErrorRestrictionTooLong"/>
<xs:enumeration value="ErrorRestrictionTooComplex"/>
<xs:enumeration value="ErrorResultSetTooBig"/>
<xs:enumeration value="ErrorInvalidExchangeImpersonationHeaderData"/>
<xs:enumeration value="ErrorSavedItemFolderNotFound"/>
<xs:enumeration value="ErrorSchemaValidation"/>
<xs:enumeration value="ErrorSearchFolderNotInitialized"/>
<xs:enumeration value="ErrorSendAsDenied"/>
<xs:enumeration value="ErrorSendMeetingCancellationsRequired"/>
<xs:enumeration
    value="ErrorSendMeetingInvitationsOrCancellationsRequired"/>
<xs:enumeration value="ErrorSendMeetingInvitationsRequired"/>
<xs:enumeration value="ErrorSentMeetingRequestUpdate"/>
<xs:enumeration value="ErrorSentTaskRequestUpdate"/>
<xs:enumeration value="ErrorServerBusy"/>
<xs:enumeration value="ErrorServiceDiscoveryFailed"/>
<xs:enumeration value="ErrorStaleObject"/>
<xs:enumeration value="ErrorSubmissionQuotaExceeded"/>
<xs:enumeration value="ErrorSubscriptionAccessDenied"/>
<xs:enumeration value="ErrorSubscriptionDelegateAccessNotSupported"/>
<xs:enumeration value="ErrorSubscriptionNotFound"/>
<xs:enumeration value="ErrorSubscriptionUnsubscribed"/>
<xs:enumeration value="ErrorSyncFolderNotFound"/>
<xs:enumeration value="ErrorTeamMailboxNotFound"/>
<xs:enumeration value="ErrorTeamMailboxNotLinkedToSharePoint"/>
<xs:enumeration value="ErrorTeamMailboxUrlValidationFailed"/>
<xs:enumeration value="ErrorTeamMailboxNotAuthorizedOwner"/>
<xs:enumeration value="ErrorTeamMailboxActiveToPendingDelete"/>

```

```
<xs:enumeration value="ErrorTeamMailboxFailedSendingNotifications"/>
<xs:enumeration value="ErrorTeamMailboxErrorUnknown"/>
<xs:enumeration value="ErrorTimeIntervalTooBig"/>
<xs:enumeration value="ErrorTimeoutExpired"/>
<xs:enumeration value="ErrorTimeZone"/>
<xs:enumeration value="ErrorToFolderNotFound"/>
<xs:enumeration value="ErrorTokenSerializationDenied"/>
<xs:enumeration value="ErrorUpdatePropertyMismatch"/>
<xs:enumeration value="ErrorUnifiedMessagingDialPlanNotFound"/>
<xs:enumeration value="ErrorUnifiedMessagingReportDataNotFound"/>
<xs:enumeration value="ErrorUnifiedMessagingPromptNotFound"/>
<xs:enumeration value="ErrorUnifiedMessagingRequestFailed"/>
<xs:enumeration value="ErrorUnifiedMessagingServerNotFound"/>
<xs:enumeration value="ErrorUnableToGetUserOutOfSettings"/>
<xs:enumeration value="ErrorUnableToRemoveImContactFromGroup"/>
<xs:enumeration value="ErrorUnsupportedSubFilter"/>
<xs:enumeration value="ErrorUnsupportedCulture"/>
<xs:enumeration value="ErrorUnsupportedMapiPropertyType"/>
<xs:enumeration value="ErrorUnsupportedMimeConversion"/>
<xs:enumeration value="ErrorUnsupportedPathForQuery"/>
<xs:enumeration value="ErrorUnsupportedPathForSortGroup"/>
<xs:enumeration value="ErrorUnsupportedPropertyDefinition"/>
<xs:enumeration value="ErrorUnsupportedQueryFilter"/>
<xs:enumeration value="ErrorUnsupportedRecurrence"/>
<xs:enumeration value="ErrorUnsupportedTypeForConversion"/>
<xs:enumeration value="ErrorUpdateDelegatesFailed"/>
<xs:enumeration value="ErrorUserNotUnifiedMessagingEnabled"/>
<xs:enumeration value="ErrorValueOutOfRange"/>
<xs:enumeration value="ErrorVoiceMailNotImplemented"/>
<xs:enumeration value="ErrorVirusDetected"/>
<xs:enumeration value="ErrorVirusMessageDeleted"/>
<xs:enumeration value="ErrorWebRequestInInvalidState"/>
<xs:enumeration value="ErrorWin32InteropError"/>
<xs:enumeration value="ErrorWorkingHoursSaveFailed"/>
<xs:enumeration value="ErrorWorkingHoursXmlMalformed"/>
<xs:enumeration value="ErrorWrongServerVersion"/>
<xs:enumeration value="ErrorWrongServerVersionDelegate"/>
<xs:enumeration value="ErrorMissingInformationSharingFolderId"/>
<xs:enumeration value="ErrorDuplicateSOAPHeader"/>
<xs:enumeration value="ErrorSharingSynchronizationFailed"/>
<xs:enumeration value="ErrorSharingNoExternalEwsAvailable"/>
<xs:enumeration value="ErrorFreeBusyDLLimitReached"/>
<xs:enumeration value="ErrorInvalidGetSharingFolderRequest"/>
<xs:enumeration value="ErrorNotAllowedExternalSharingByPolicy"/>
<xs:enumeration value="ErrorUserNotAllowedByPolicy"/>
<xs:enumeration value="ErrorPermissionNotAllowedByPolicy"/>
<xs:enumeration value="ErrorOrganizationNotFederated"/>
<xs:enumeration value="ErrorMailboxFailover"/>
<xs:enumeration value="ErrorInvalidExternalSharingInitiator"/>
<xs:enumeration value="ErrorMessageTrackingPermanentError"/>
<xs:enumeration value="ErrorMessageTrackingTransientError"/>
<xs:enumeration value="ErrorMessageTrackingNoSuchDomain"/>
<xs:enumeration value="ErrorUserWithoutFederatedProxyAddress"/>
<xs:enumeration value="ErrorInvalidOrganizationRelationshipForFreeBusy"/>
<xs:enumeration value="ErrorInvalidFederatedOrganizationId"/>
<xs:enumeration value="ErrorInvalidExternalSharingSubscriber"/>
<xs:enumeration value="ErrorInvalidSharingData"/>
<xs:enumeration value="ErrorInvalidSharingMessage"/>
<xs:enumeration value="ErrorNotSupportedSharingMessage"/>
```

```

<xs:enumeration value="ErrorApplyConversationActionFailed"/>
<xs:enumeration value="ErrorInboxRulesValidationErrors"/>
<xs:enumeration value="ErrorOutlookRuleBlobExists"/>
<xs:enumeration value="ErrorRulesOverQuota"/>
<xs:enumeration value="ErrorNewEventStreamConnectionOpened"/>
<xs:enumeration value="ErrorMissedNotificationEvents"/>
<xs:enumeration value="ErrorDuplicateLegacyDistinguishedName"/>
<xs:enumeration value="ErrorInvalidClientAccessTokenRequest"/>
<xs:enumeration value="ErrorNoSpeechDetected"/>
<xs:enumeration value="ErrorUMServerUnavailable"/>
<xs:enumeration value="ErrorRecipientNotFound"/>
<xs:enumeration value="ErrorRecognizerNotInstalled"/>
<xs:enumeration value="ErrorSpeechGrammarError"/>
<xs:enumeration value="ErrorInvalidManagementRoleHeader"/>
<xs:enumeration value="ErrorLocationServicesDisabled"/>
<xs:enumeration value="ErrorLocationServicesRequestTimedOut"/>
<xs:enumeration value="ErrorLocationServicesRequestFailed"/>
<xs:enumeration value="ErrorLocationServicesInvalidRequest"/>
<xs:enumeration value="ErrorMailboxScopeNotAllowedWithoutQueryString"/>
<xs:enumeration value="ErrorArchiveMailboxSearchFailed"/>
<xs:enumeration value="ErrorArchiveMailboxServiceDiscoveryFailed"/>
<xs:enumeration value="ErrorInvalidPhotoSize"/>
<xs:enumeration value="ErrorSearchQueryHasTooManyKeywords"/>
<xs:enumeration value="ErrorSearchTooManyMailboxes"/>
<xs:enumeration value="ErrorDiscoverySearchesDisabled"/>
</xs:restriction>
</xs:simpleType>

```

The values that are defined by the **ResponseCodeType** simple type are listed in the following table.

Value	Meaning
<b>NoError</b>	Specifies that no errors occurred.
<b>ErrorAccessDenied</b>	Specifies that the calling account does not have the rights to perform the action requested.
<b>ErrorAccessModeSpecified</b>	This error is for internal use only. This error is not returned.
<b>ErrorAccountDisabled</b>	Specifies that the account has been disabled.
<b>ErrorAddDelegatesFailed</b>	Occurs when a list with added <b>delegates</b> cannot be saved.
<b>ErrorAddressSpaceNotFound</b>	Specifies that the address space record, or Domain Name System (DNS) domain name, for cross-forest availability could not be found in the directory service.
<b>ErrorADOperation</b>	Specifies that the operation failed because of communication problems with the directory service.
<b>ErrorADSessionFilter</b>	Specifies that the <b>ResolveNames</b> operation request, as specified in <a href="#">[MS-OXWSRSLNM]</a> section 3.1.4.1, specifies an invalid name.

Value	Meaning
<b>ErrorADUnavailable</b>	Specifies that the directory service is unavailable. Try your request again later.
<b>ErrorAffectedTaskOccurrencesRequired</b>	Specifies that the <b>AffectedTaskOccurrences</b> property value is missing. This value is required when you are deleting a task.
<b>ErrorArchiveFolderPathCreation</b>	Specifies that there was in error in creating an archive folder path. <a href="#">&lt;33&gt;</a>
<b>ErrorArchiveMailboxNotEnabled</b>	Specifies that the archive mailbox is disabled. <a href="#">&lt;34&gt;</a>
<b>ErrorArchiveMailboxServiceDiscoveryFailed</b>	Specifies that the archive mailbox service failed to discover a mailbox. <a href="#">&lt;35&gt;</a>
<b>ErrorAvailabilityConfigNotFound</b>	Specifies that the availability configuration was not found. <a href="#">&lt;36&gt;</a>
<b>ErrorBatchProcessingStopped</b>	Specifies that the previous item in the request failed in such a way that Exchange Web Services stopped processing the remaining items in the request. All remaining items are marked with the <b>ErrorBatchProcessingStopped</b> error.
<b>ErrorCalendarCannotMoveOrCopyOccurrence</b>	Specifies that an attempt was made to move or copy an occurrence of a recurring calendar item.
<b>ErrorCalendarCannotUpdateDeletedItem</b>	Specifies that an attempt was made to update a calendar item that is located in the Deleted Items folder, and the update in question would send out a meeting invite.
<b>ErrorCalendarCannotUseIdForOccurrenceId</b>	Specifies that the <b>OccurrenceId</b> does not correspond to a valid occurrence of the <b>recurringMasterId</b> .
<b>ErrorCalendarCannotUseIdForRecurringMasterId</b>	Specifies that the <b>recurringMasterId</b> does not correspond to a valid occurrence of the <b>OccurrenceId</b> .
<b>ErrorCalendarDurationIsTooLong</b>	Specifies that the item duration of a calendar item exceeds five years.
<b>ErrorCalendarEndDateIsEarlierThanStartDate</b>	Specifies that the end date/time MUST be changed so that it is greater than the start date/time.
<b>ErrorCalendarFolderIsInvalidForCalendarView</b>	Specifies that the find operation that is using the <b>CalendarViewType</b> object is not for a calendar folder.
<b>ErrorCalendarInvalidAttributeValue</b>	This response code is not used.
<b>ErrorCalendarInvalidDayForTimeChangePattern</b>	Specifies that invalid values of <b>Day</b> , <b>WeekDay</b> , and <b>WeekendDay</b> were used to define the time change pattern.
<b>ErrorCalendarInvalidDayForWeeklyRecurrence</b>	Specifies that invalid values of <b>Day</b> , <b>WeekDay</b> , and <b>WeekendDay</b> were used to specify the weekly recurrence.
<b>ErrorCalendarInvalidPropertyState</b>	Specifies that the state of the calendar item recurrence binary large object (BLOB) in the store is invalid.

Value	Meaning
<b>ErrorCalendarInvalidPropertyValue</b>	This response code is not used.
<b>ErrorCalendarInvalidRecurrence</b>	Specifies that the internal structure of the objects that represent the recurrence is invalid.
<b>ErrorCalendarInvalidTimeZone</b>	Specifies that an invalid time zone was encountered.
<b>ErrorCalendarIsCancelledForAccept</b>	Specifies that a calendar item has been cancelled. This error code MUST be returned when responding to a meeting request with an <b>t:AcceptItemType</b> ([MS-OXWSMTGS] section 2.2.4.1) response object after a meeting has been cancelled.
<b>ErrorCalendarIsCancelledForDecline</b>	Specifies that a calendar item has been cancelled. This error code MUST be returned when responding to a meeting request with a <b>t:DeclineItemType</b> ([MS-OXWSMTGS] section 2.2.4.9) response object after a meeting has been cancelled.
<b>ErrorCalendarIsCancelledForRemove</b>	Specifies that a calendar item has been cancelled. This error code MUST be returned when responding to a meeting request with a <b>t:RemoveItemType</b> ([MS-OXWSMTGS] section 2.2.4.21) response object after a meeting has been cancelled.
<b>ErrorCalendarIsCancelledForTentative</b>	Specifies that a calendar item has been cancelled. This error code MUST be returned when responding to a meeting request with a <b>t:TentativelyAcceptItemType</b> ([MS-OXWSMTGS] section 2.2.4.22) response object after a meeting has been cancelled.
<b>ErrorCalendarIsDelegatedForAccept</b>	Specifies that delegate access cannot be used to accept a meeting request.
<b>ErrorCalendarIsDelegatedForDecline</b>	Specifies that delegate access cannot be used to decline a meeting request.
<b>ErrorCalendarIsDelegatedForRemove</b>	Specifies that delegate access cannot be used to delete a meeting request.
<b>ErrorCalendarIsDelegatedForTentative</b>	Specifies that delegate access cannot be used to tentatively accept a meeting request.
<b>ErrorCalendarIsNotOrganizer</b>	Specifies that a meeting cannot be canceled by someone other than the organizer.
<b>ErrorCalendarIsOrganizerForAccept</b>	Specifies that the meeting organizer cannot accept the meeting. Only attendees can accept meeting requests.
<b>ErrorCalendarIsOrganizerForDecline</b>	Specifies that the meeting organizer cannot decline the meeting. Only attendees can decline meeting requests.
<b>ErrorCalendarIsOrganizerForRemove</b>	Specifies that the meeting organizer cannot remove a meeting from the calendar. The organizer can only remove the meeting by canceling the meeting. Only attendees can remove a calendar item.
<b>ErrorCalendarIsOrganizerForTentative</b>	Specifies that the meeting organizer cannot tentatively accept a meeting. Only attendees can tentatively accept

Value	Meaning
	meeting requests.
<b>ErrorCalendarOccurrenceIndexIsOutOfRecurrenceRange</b>	Occurs when the occurrence index that is specified in the <b>OccurrenceId</b> property does not correspond to a valid occurrence. (for example, if your recurrence pattern defines a set of three meeting occurrences and you try to access the fifth occurrence).
<b>ErrorCalendarOccurrenceIsDeletedFromRecurrence</b>	Occurs when the occurrence index that is specified in the <b>OccurrenceId</b> property corresponds to a deleted instance.
<b>ErrorCalendarOutOfRange</b>	Occurs when a recurrence pattern is defined that contains a value for a month, day, or week that is out of range, such as the seventh week of the month.
<b>ErrorCalendarMeetingRequestIsOutOfDate</b>	Specifies that the calendar item associated with the meeting request has been updated since the meeting request was sent.
<b>ErrorCalendarViewRangeTooBig</b>	Occurs when the range for calendar paging is larger than two years.
<b>ErrorCallerIsInvalidADAccount</b>	Specifies that the requesting account is not a valid account in the directory database.
<b>ErrorCannotArchiveCalendarContactTaskFolderException</b>	Specifies that an attempt was made to archive a calendar contact task folder. <a href="#">&lt;37&gt;</a>
<b>ErrorCannotArchiveItemsInPublicFolders</b>	Specifies that an attempt was made to archive items in public folders. <a href="#">&lt;38&gt;</a>
<b>ErrorCannotArchiveItemsInArchiveMailbox</b>	Specifies that an attempt was made to archive items in the archive mailbox. <a href="#">&lt;39&gt;</a>
<b>ErrorCannotCreateCalendarItemInNonCalendarFolder</b>	Occurs when you are creating a calendar item and the <b>SavedItemFolderId</b> property refers to a folder other than the Calendar folder.
<b>ErrorCannotCreateContactInNonContactFolder</b>	Specifies that an attempt was made to create a contact in a folder other than the Contacts folder.
<b>ErrorCannotCreatePostItemInNonMailFolder</b>	Specifies that a post item can be created only in a Mail folder.
<b>ErrorCannotCreateTaskInNonTaskFolder</b>	Occurs when you are creating a task and the <b>SavedItemFolderId</b> property refers to a folder other than the Tasks folder.
<b>ErrorCannotDeleteObject</b>	Specifies that the item or folder to be deleted cannot be deleted.
<b>ErrorCannotDeleteTaskOccurrence</b>	Specifies that you cannot delete an occurrence of a nonrecurring task and you cannot delete the last occurrence of a recurring task.
<b>ErrorCannotDisableMandatoryExtension</b>	Specifies that an attempt was made to disable a required extension.

Value	Meaning
<b>ErrorCannotEmptyFolder</b>	This error MUST be returned when the server cannot empty a folder.
<b>ErrorCannotGetSourceFolderPath</b>	Specifies that the source folder path could not be retrieved. <a href="#">&lt;40&gt;</a>
<b>ErrorCannotGetExternalEcpUrl</b>	Specifies that the server could not retrieve the external URL for Outlook Web App Options. <a href="#">&lt;41&gt;</a>
<b>ErrorCannotOpenFileAttachment</b>	Occurs when the attachment stream does not open.
<b>ErrorCannotSetCalendarPermissionOnNonCalendarFolder</b>	Specifies that the caller tried to set calendar permissions on a folder other than the Calendar folder.
<b>ErrorCannotSetNonCalendarPermissionOnCalendarFolder</b>	Specifies that the caller tried to set non-Calendar folder permissions on a Calendar folder.
<b>ErrorCannotSetPermissionUnknownEntries</b>	Specifies that you cannot set unknown permissions in a permissions set.
<b>ErrorCannotSpecifySearchFolderAsSourceFolder</b>	Specifies that an attempt was made to set the search folder as source folder. <a href="#">&lt;42&gt;</a>
<b>ErrorCannotUseFolderIdForItemId</b>	Occurs when the ID that was passed represents a folder instead of an item.
<b>ErrorCannotUseItemIdForFolderId</b>	Occurs when the ID that was passed in represents an item instead of a folder.
<b>ErrorChangeKeyRequired</b>	This response code has been replaced by <b>ErrorChangeKeyRequiredForWriteOperations</b> .
<b>ErrorChangeKeyRequiredForWriteOperations</b>	Specifies that a valid change key MUST be provided when you are performing certain update operations.
<b>ErrorClientDisconnected</b>	Specifies that the client was disconnected.
<b>ErrorClientIntentInvalidStateDefinition</b>	Specifies that the state of a changed appointment is not valid. <a href="#">&lt;43&gt;</a>
<b>ErrorClientIntentNotFound</b>	Specifies that the reason for changing an appointment was not found. <a href="#">&lt;44&gt;</a>
<b>ErrorConnectionFailed</b>	Occurs when Exchange Web Services cannot connect to the mailbox.
<b>ErrorContainsFilterWrongType</b>	Specifies that the property inspected for a Contains filter is not a string type. This error code MUST be returned when a Contains filter is used with a property that is not a string type.
<b>ErrorContentConversionFailed</b>	Occurs when Exchange Web Services is unable to retrieve the <b>Multipurpose Internet Mail Extensions (MIME)</b> content for the item that was retrieved by the <b>GetItem</b> method, or it is unable to create the item from the <b>CreateItem</b> method.
<b>ErrorContentIndexingNotEnabled</b>	<a href="#">&lt;45&gt;</a>

Value	Meaning
<b>ErrorCorruptData</b>	Specifies that the data is corrupted and cannot be processed.
<b>ErrorCreateItemAccessDenied</b>	Specifies that the caller does not have the necessary permissions to create the item.
<b>ErrorCreateManagedFolderPartialCompletion</b>	Specifies that one or more of the managed folders that were passed to the <b>CreateManagedFolder</b> method failed to be created. Search for each folder to determine which folders were created and which ones do not exist.
<b>ErrorCreateSubfolderAccessDenied</b>	Specifies that the calling account does not have the proper permissions to create the subfolder.
<b>ErrorCrossMailboxMoveCopy</b>	Specifies that the item or folder cannot be moved from one mailbox to another.
<b>ErrorCrossSiteRequest</b>	Specifies that the request is not allowed because the server that services the request is in a different site than the requested resource.
<b>ErrorDataSizeLimitExceeded</b>	Specifies that either the data that you were trying to set exceeded the maximum size for the property, or the value is large enough to require streaming and the property does not support streaming, such as for folder properties.
<b>ErrorDataSourceOperation</b>	Occurs when the underlying data provider failed to complete the operation.
<b>ErrorDelegateAlreadyExists</b>	Occurs in an <b>AddDelegate</b> method call when the specified user already exists in the list of delegates.
<b>ErrorDelegateCannotAddOwner</b>	Occurs in an <b>AddDelegate</b> method call when the specified user to be added is the owner of the mailbox.
<b>ErrorDelegateMissingConfiguration</b>	Occurs in a <b>GetDelegate</b> method call when there is either no delegate information on a local <b>free/busy message</b> or no Active Directory directory service public delegate (no public delegate or no Send On Behalf entry in the directory service).
<b>ErrorDelegateNoUser</b>	Occurs when a specified user cannot be mapped to a user in the directory service.
<b>ErrorDelegateValidationFailed</b>	Occurs in an <b>AddDelegate</b> method call when an added delegate user is not valid.
<b>ErrorDeleteDistinguishedFolder</b>	Specifies that you cannot delete a distinguished folder.
<b>ErrorDeleteItemsFailed</b>	This response code is not used.
<b>ErrorDeleteUnifiedMessagingPromptFailed</b>	<46>
<b>ErrorDistinguishedUserNotSupported</b>	Specifies that a distinguished user ID is not valid for the operation. The <b>DistinguishedUserType</b> simple type SHOULD NOT be present in the request.
<b>ErrorDistributionListMemberNotExist</b>	Specifies that a particular request distribution list member does not exist in the distribution list.



Value	Meaning
<b>ErrorDuplicateInputFolderNames</b>	Occurs when there are duplicate folder names in the array that was passed to the <b>CreateManagedFolder</b> method.
<b>ErrorDuplicateUserIdsSpecified</b>	Specifies that a duplicate user ID has been found in a permission set, that either Default or Anonymous is set more than once, or that there are duplicate SIDs or recipients.
<b>ErrorEmailAddressMismatch</b>	Occurs when the e-mail address for the distinguished folder ID does not match the mailbox that you are operating on. For example, you cannot create a search folder that exists in one mailbox but considers distinguished folders from another mailbox in its search criteria.
<b>ErrorEventNotFound</b>	Specifies that the subscription that was created with a particular watermark is no longer valid.
<b>ErrorExceededConnectionCount</b>	Specifies that there are more concurrent requests against the server than are allowed by a user's policy. This error <b>MUST</b> be returned when that occurs.
<b>ErrorExceededSubscriptionCount</b>	Specifies that a user's throttling policy maximum subscription count has been exceeded. This error <b>MUST</b> be returned when that occurs. Active subscriptions <b>MUST</b> be deleted before additional subscriptions can be created if this error occurs.
<b>ErrorExceededFindCountLimit</b>	Specifies that a search operation call has exceeded the total number of items that can be returned.
<b>ErrorExpiredSubscription</b>	Specifies that the subscription that is referenced by the <b>GetEvents</b> method has expired.
<b>ErrorExtensionNotFound</b>	Specifies that the desired extension was not found. <a href="#">&lt;47&gt;</a>
<b>ErrorFolderCorrupt</b>	Specifies that the folder is corrupted and cannot be saved.
<b>ErrorFolderNotFound</b>	Specifies that the folder ID that was passed in does not correspond to a valid folder, or that the delegate does not have permissions to access the folder.
<b>ErrorFolderPropertRequestFailed</b>	Specifies that the requested property could not be retrieved. This does not indicate that the property does not exist, but that the property was corrupted in some way so that the retrieval failed.
<b>ErrorFolderSave</b>	Specifies that the folder could not be created or saved because of an invalid state.
<b>ErrorFolderSaveFailed</b>	Specifies that the folder could not be created or saved because of an invalid state.
<b>ErrorFolderSavePropertyError</b>	Specifies that the folder could not be created or updated because of invalid property values. The response code lists the properties that caused the problem.
<b>ErrorFolderExists</b>	Specifies that a folder that has the specified name already exists. Duplicate folder names are not allowed within the

Value	Meaning
	same parent folder.
<b>ErrorFreeBusyGenerationFailed</b>	Occurs when free/busy information cannot be retrieved because of an intervening failure.
<b>ErrorGetServerSecurityDescriptorFailed</b>	This response code is not used.
<b>ErrorImContactLimitReached</b>	<48>
<b>ErrorImGroupDisplayNameAlreadyExists</b>	<49>
<b>ErrorImGroupLimitReached</b>	<50>
<b>ErrorImpersonateUserDenied</b>	Specifies that the calling account does not have the ms-Exch-EPI-May-Impersonate right on either the user or contact that it is trying to impersonate or the mailbox database that contains the user mailbox. This response code is returned within a SOAP fault.
<b>ErrorImpersonationDenied</b>	Specifies that the calling account does not have the ms-Exch-EPI-Impersonation right on the Client Access server that it is calling. This response code is returned within a SOAP fault.
<b>ErrorImpersonationFailed</b>	Specifies that there was an unexpected error when an attempt was made to perform server-to-server authentication. This response code typically indicates either that the service account that is running the Exchange Web Services application pool is configured incorrectly, that Exchange Web Services cannot talk to the directory, or that a trust between forests is not correctly configured.
<b>ErrorIncorrectSchemaVersion</b>	Specifies that the request was valid for the current server version but was invalid for the request server version that was specified.
<b>ErrorIncorrectUpdatePropertyCount</b>	Specifies that each change description in an <b>UpdateItem</b> or <b>UpdateFolder</b> method call MUST list only one property to be updated.
<b>ErrorIndividualMailboxLimitReached</b>	Occurs when the request contains too many attendees to be resolved. By default, the maximum number of attendees to be resolved is 100.
<b>ErrorInsufficientResources</b>	Specifies that the mailbox server is overloaded. Try your request again later.
<b>ErrorInternalServerError</b>	Specifies that Exchange Web Services encountered an error that it could not recover from, and there is not a more specific response code associated with the error that occurred.
<b>ErrorInternalServerTransientError</b>	Specifies that an internal server error occurred and that you SHOULD try your request again later.
<b>ErrorInvalidAccessLevel</b>	Specifies that the level of access that the caller has on the free/busy data is invalid.

Value	Meaning
<b>ErrorInvalidArgument</b>	<p>Specifies an error caused by all invalid arguments passed to the <b>GetMessageTrackingReport</b> operation, as specified in <a href="#">[MS-OXWSMTRK]</a> section 3.1.4.2. This error MUST be returned in the following scenarios:</p> <ul style="list-style-type: none"> <li>▪ The user specified in the sending-as parameter does not exist in the directory.</li> <li>▪ The user specified in the sending-as parameter is not unique in the directory.</li> <li>▪ The sending-as address is empty.</li> <li>▪ The sending-as address is not a valid e-mail address.</li> </ul>
<b>ErrorInvalidAttachmentId</b>	<p>Specifies that the attachment was not found within the attachments collection for the item. For example, you might receive this response code if you have an attachment ID and then the attachment is deleted and you try to call the <b>GetAttachment</b> method on the attachment ID.</p>
<b>ErrorInvalidAttachmentSubfilter</b>	<p>Occurs when you try to bind to an existing search folder by using a complex attachment table restriction. Exchange Web Services supports only simple contains filters against the attachment table. If you try to bind to an existing search folder that has a more complex attachment table restriction (a subfilter), Exchange Web Services cannot render the XML for that filter and returns this response code. Note that you can still call the <b>GetFolder</b> method on the folder, but do not request the <b>SearchParameters</b> property.</p>
<b>ErrorInvalidAttachmentSubfilterTextFilter</b>	<p>Occurs when you try to bind to an existing search folder by using a complex attachment table restriction. Exchange Web Services supports only simple contains filters against the attachment table. If you try to bind to an existing search folder that has a more complex attachment table restriction, Exchange Web Services cannot render the XML for that filter. In this case, the attachment subfilter contains a text filter, but it is not looking at the attachment display name. Note that you can still call the <b>GetFolder</b> method on the folder, but do not request the <b>SearchParameters</b> property.</p>
<b>ErrorInvalidAuthorizationContext</b>	<p>Specifies a failure to proxy an availability request to a more applicable server.</p>
<b>ErrorInvalidChangeKey</b>	<p>Specifies that an invalid change key was passed in. Note that many methods do not require a change key to be passed. However, if you do provide a change key, it MUST be valid, although it does not necessarily have to be up-to-date.</p>
<b>ErrorInvalidClientSecurityContext</b>	<p>Specifies that there was an internal error when an attempt was made to resolve the identity of the caller.</p>
<b>ErrorInvalidCompleteDate</b>	<p>Occurs when you try to set the <b>CompleteDate</b> of a task to a time in the future. When it is converted to the local</p>

Value	Meaning
	time of the Client Access server, the <b>CompleteDate</b> cannot be set to a value that is later than the local time on the Client Access server.
<b>ErrorInvalidContactEmailAddress</b>	Specifies that an invalid e-mail address was provided for a contact.
<b>ErrorInvalidContactEmailIndex</b>	Specifies that an invalid e-mail index value was provided for an e-mail entry.
<b>ErrorInvalidCrossForestCredentials</b>	Occurs when an availability request is proxied to a Client Access server in another forest.
<b>ErrorInvalidDelegatePermission</b>	Specifies that the specified folder permissions are invalid.
<b>ErrorInvalidDelegateUserId</b>	Specifies that the specified delegate user ID is invalid.
<b>ErrorInvalidExcludesRestriction</b>	Specifies that the bitmask that was passed into the Excludes restriction could not be parsed.
<b>ErrorInvalidExpressionTypeForSubFilter</b>	This response code is not used.
<b>ErrorInvalidExtendedProperty</b>	Occurs when the combination of extended property values that was specified are invalid or they result in an invalid extended property Uniform Resource Identifier (URI).
<b>ErrorInvalidExtendedPropertyValue</b>	Specifies that the value that was offered for the extended property is inconsistent with the type that was specified in the associated extended field URI. For example, if the <b>PropertyType</b> property on the extended field URI is set to <b>string</b> , but you set the value of the extended property as an array of integers, you will encounter this response code.
<b>ErrorInvalidFolderId</b>	Occurs when the folder ID is corrupted.
<b>ErrorInvalidFolderTypeForOperation</b>	Specifies that the specified folder type is invalid for the current operation. For example, you cannot create a Search folder in a public folder.
<b>ErrorInvalidFractionalPagingParameters</b>	Occurs in fractional paging when the user has specified one of the following: a numerator that is greater than the denominator, a numerator that is less than 0 (zero), or a denominator that is less than or equal to 0 (zero).
<b>ErrorInvalidFreeBusyViewType</b>	Occurs if a <b>FreeBusyViewType</b> of <b>None</b> is requested.
<b>ErrorInvalidId</b>	Specifies that the structure of the ID and/or change key is internally inconsistent.
<b>ErrorInvalidIdEmpty</b>	Specifies that the caller specified an ID that is empty.
<b>ErrorInvalidIdMalformed</b>	Specifies that the structure of the ID is internally inconsistent.
<b>ErrorInvalidIdMalformedEwsLegacyIdFormat</b>	Specifies that a folder or item ID is using a server schema version format that is not supported by the server. <a href="#">&lt;51&gt;</a> You MUST use the <b>ConvertId</b> method to convert them first.

Value	Meaning
<b>ErrorInvalidIdMonikerTooLong</b>	Specifies that the structure of the ID is internally inconsistent. The moniker is contained within the ID and indicates which mailbox the ID belongs to. This response code is returned if the length of the moniker is checked and the byte count is longer than expected.
<b>ErrorInvalidIdNotAnItemAttachmentId</b>	Occurs when the <b>AttachmentId</b> property does not refer to an item attachment.
<b>ErrorInvalidIdReturnedByResolveNames</b>	Specifies that a contact in your mailbox is corrupt.
<b>ErrorInvalidIdStoreObjectIdTooLong</b>	Occurs when the structure of the ID is internally inconsistent.
<b>ErrorInvalidIdTooManyAttachmentLevels</b>	Specifies that the attachment hierarchies exceed the maximum of 255 levels deep.
<b>ErrorInvalidIdXml</b>	This response code is not used.
<b>ErrorInvalidImContactId</b>	<a href="#">&lt;52&gt;</a>
<b>ErrorInvalidImDistributionGroupSmtpAddress</b>	<a href="#">&lt;53&gt;</a>
<b>ErrorInvalidImGroupId</b>	<a href="#">&lt;54&gt;</a>
<b>ErrorInvalidIndexedPagingParameters</b>	Occurs if the offset for indexed paging is less than 0 (zero).
<b>ErrorInvalidInternetHeaderChildNodes</b>	This response code is not used.
<b>ErrorInvalidItemForOperationCreateItemAttachment</b>	Specifies that you tried to create an item attachment by using an unsupported item type. Supported item types for item attachments include <b>ItemType</b> , <b>MessageType</b> , <b>CalendarItemType</b> , <b>TaskType</b> , and <b>ContactItemType</b> objects. For example, if you try to create a <b>MeetingMessage</b> attachment, you will encounter this response code.
<b>ErrorInvalidItemForOperationArchiveItem</b>	Specifies that an attempt was made to archive an unsupported item. <a href="#">&lt;55&gt;</a>
<b>ErrorInvalidItemForOperationCreateItem</b>	Specifies that you tried to create an unsupported item. Supported items include <b>ItemType</b> , <b>MessageType</b> , <b>CalendarItemType</b> , <b>TaskType</b> , and <b>ContactItemType</b> objects. For example, you cannot create a <b>DistributionList</b> object by using the <b>CreateItem</b> method. In addition, certain types are created as a side effect of doing something else. <b>MeetingMessages</b> objects, for example, are created when you send a calendar item to attendees; they are not explicitly created.
<b>ErrorInvalidItemForOperationAcceptItem</b>	Occurs when an <b>AcceptItemType</b> object is created on something other than a meeting request or a calendar item, or when an attempt is made to accept a calendar item occurrence that is in the Deleted Items folder.
<b>ErrorInvalidItemForOperationDeclineItem</b>	Specifies that a <b>DeclineItemType</b> object was created on

Value	Meaning
	something other than a meeting request or a calendar item, or that you tried to decline a calendar item occurrence that is in the Deleted Items folder.
<b>ErrorInvalidItemForOperationCancelItem</b>	Occurs when a <b>CancelCalendarItemType</b> object is created for something other than a calendar item.
<b>ErrorInvalidItemForOperationExpandDL</b>	Occurs when the instance of the <b>ExpandDLType</b> class that was passed to the <b>ExpandDL</b> method does not represent a distribution list.
<b>ErrorInvalidItemForOperationRemoveItem</b>	Occurs when a <b>RemoveItemType</b> object is created for an item other than a meeting cancellation.
<b>ErrorInvalidItemForOperationSendItem</b>	Occurs if the <b>SendItem</b> method was attempted on an item other than a message item. Only items whose <b>ItemClass</b> property value begins with <b>IPM.Note</b> can be sent.
<b>ErrorInvalidItemForOperationTentative</b>	Occurs if a <b>TentativelyAcceptItemType</b> object was created on an item other than a calendar item or meeting request. Also occurs if the <b>TentativelyAcceptItemType</b> object was created for a calendar item occurrence that is in the Deleted Items folder.
<b>ErrorInvalidLogonType</b>	This error is for internal use only. This error is not returned.
<b>ErrorInvalidMailbox</b>	<p>Specifies that the <b>CreateItem</b> or <b>UpdateItem</b> operation failed while creating or updating a personal distribution list. This error MUST be returned under the following conditions:</p> <ul style="list-style-type: none"> <li>A member is not accessible by using an item identifier to identify the member's mailbox. The following <b>m:ResponseMessageType</b> XML MUST be returned for this scenario: <pre> &lt;m:MessageText&gt;Mailbox is invalid. Verify the specified Mailbox property.&lt;/m:MessageText&gt; &lt;m:ResponseCode&gt;ErrorInvalidMailbox&lt;/m:ResponseCode&gt; &lt;m:MessageXml&gt; &lt;t:FieldURI FieldURI="distributionlist:Members"/&gt; &lt;t:Value Name="Inner.ResponseCode"&gt;ErrorNonExistentMailbox&lt;/t:Value&gt; &lt;t:Value Name="Inner.MessageText"&gt;No mailbox with such guid.&lt;/t:Value&gt; &lt;/m:MessageXml&gt; </pre> </li> <li>The specified identifier is for a private distribution list but the <b>MailboxTypeType</b> simple type (section <a href="#">2.2.3.18</a>) is not set to <b>PrivateDL</b>. The <b>MessageText</b> element of the <b>ResponseMessageType</b> complex type (section <a href="#">2.2.4.57</a>) MUST contain the following text: <b>MailboxType</b> SHOULD be <b>PrivateDL</b> or not specified.</li> </ul>

Value	Meaning
	<ul style="list-style-type: none"> <li data-bbox="800 201 1432 407"> <p>▪ The specified identifier is for a database contact item but the contact does not have an e-mail address. The specified member's e-mail address, routing type, or name does not match to the corresponding properties of any contact's e-mail addresses. The <b>MessageText</b> element of the <b>ResponseMessageType</b> complex type (section <a href="#">2.2.4.57</a>) MUST contain the following text: The contact address wasn't found.</p> </li> <li data-bbox="800 432 1432 558"> <p>▪ The specified identifier is for a folder instead of a contact or private distribution list store item identifier. The following <b>ResponseMessageType</b> complex type (section <a href="#">2.2.4.57</a>) XML MUST be returned for this scenario:</p> <pre data-bbox="800 583 1432 940"> &lt;m:MessageText&gt;Mailbox is invalid. Verify the specified Mailbox property.&lt;/m:MessageText&gt; &lt;m:ResponseCode&gt;ErrorInvalidMailbox&lt;/m:ResponseCode&gt; &lt;m:MessageXml&gt; &lt;t:FieldURI FieldURI="distributionlist:Members"/&gt; &lt;t:Value Name="Inner.ResponseCode"&gt;ErrorCannotUseFolderIdForItemId&lt;/t:Value&gt;   &lt;t:Value Name="Inner.MessageText"&gt;Expected an item Id but received a folder Id.&lt;/t:Value&gt; &lt;/m:MessageXml&gt; </pre> </li> <li data-bbox="800 966 1432 1092"> <p>▪ The specified identifier does not represent either a contact or private distribution list. The following <b>m:ResponseMessageType</b> XML MUST be returned for this scenario where <b>MemberIndex</b> represents the index of the identifier that caused the error:</p> <pre data-bbox="800 1117 1432 1360"> &lt;m:MessageText&gt;The ID of this item can't be used for a recipient, attendee, or group member.&lt;/m:MessageText&gt; &lt;m:ResponseCode&gt;ErrorInvalidMailbox&lt;/m:ResponseCode&gt; &lt;m:MessageXml&gt; &lt;t:FieldURI FieldURI="distributionlist:Members"/&gt; &lt;t:Value Name="MemberIndex"&gt;7&lt;/t:Value&gt; &lt;/m:MessageXml&gt; </pre> </li> <li data-bbox="800 1386 1432 1512"> <p>▪ The mailbox is not specified by either an <b>EmailAddress</b> or <b>ItemId</b> element in the <b>Mailbox</b> element of the <b>EmailAddressType</b>. The following <b>m:ResponseMessageType</b> XML MUST be returned for this scenario where <b>MemberIndex</b> represents the index of the identifier that caused the error:</p> <pre data-bbox="800 1570 1432 1711"> &lt;m:MessageText&gt;EmailAddress or ItemId MUST be included in the request.&lt;/m:MessageText&gt; &lt;m:ResponseCode&gt;ErrorInvalidMailbox&lt;/m:ResponseCode&gt; &lt;m:MessageXml&gt; </pre> </li> </ul>

Value	Meaning
	<p>&lt;t:FieldURI FieldURI="distributionlist:Members"/&gt;            &lt;t:Value Name="MemberIndex"&gt;0&lt;/t:Value&gt;            &lt;/m:MessageXml&gt;</p> <ul style="list-style-type: none"> <li>The member with the specified email address does not exist in the directory. The following <b>m:ResponseMessageType</b> XML MUST be returned for this scenario where <b>MemberIndex</b> represents the index of the identifier that caused the error:</li> </ul> <pre>&lt;m:MessageText&gt;Recipient is not found in Active Directory. Change MailboxType to OneOff or remove it.&lt;/m:MessageText&gt; &lt;m:ResponseCode&gt;ErrorInvalidMailbox&lt;/m:ResponseCode&gt; &lt;m:MessageXml&gt; &lt;t:FieldURI FieldURI="distributionlist:Members"/&gt; &lt;t:Value Name="MemberIndex"&gt;1&lt;/t:Value&gt; &lt;/m:MessageXml&gt;</pre> <ul style="list-style-type: none"> <li>A user with the specified email address does exist in the AD, but the specified <b>MailboxType</b> does not match user type in the directory.</li> </ul> <p>The <b>MessageXML</b> element of the <b>m:ResponseMessageType</b> as specified in section <a href="#">2.2.4.57</a>, MUST contain the following XML when a member cannot be created or updated.</p> <pre>&lt;m:MessageXml&gt;   &lt;t:FieldURI     FieldURI="distributionlist:Members"/&gt;   &lt;t:Value Name="MemberIndex"&gt;4&lt;/t:Value&gt; &lt;/m:MessageXml&gt;</pre> <p>The <b>MemberIndex</b> value MUST specify the failing member from either an <b>UpdateItem</b> or <b>CreateItem</b> request. The <b>MemberIndex</b> is a 0-based index.</p>
<b>ErrorInvalidManagedFolderProperty</b>	Specifies that the structure of the managed folder is corrupted and cannot be rendered.
<b>ErrorInvalidManagedFolderQuota</b>	Specifies that the quota that is set on the managed folder is less than zero, which indicates a corrupted managed folder.
<b>ErrorInvalidManagedFolderSize</b>	Specifies that the size that is set on the managed folder is less than zero, which indicates a corrupted managed folder.
<b>ErrorInvalidMergedFreeBusyInterval</b>	Specifies that the supplied merged free/busy interval value is invalid. The default minimum value is 5 minutes. The default maximum value is 1440 minutes.
<b>ErrorInvalidNameForNameResolution</b>	Specifies that the name that was passed into the <b>ResolveNames</b> method was invalid. For example, a zero-



Value	Meaning
	length string, a single space, a comma, and a dash are all invalid names.
<b>ErrorInvalidOperation</b>	This is a general error that is used when the requested operation is invalid. For example, this error indicates any of the following:
<b>ErrorInvalidNetworkServiceContext</b>	Specifies an error in the Network Service account on the Client Access server.
<b>ErrorInvalidOofParameter</b>	This response code is not used.
<b>ErrorInvalidPagingMaxRows</b>	Specifies that zero rows or a negative value is specified as the maximum number of rows to be returned.
<b>ErrorInvalidParentFolder</b>	Specifies that you passed in an invalid parent folder for an operation, for example by creating a folder within a search folder.
<b>ErrorInvalidPercentCompleteValue</b>	Occurs if the percent complete property is set to a value that is not between 0 and 100 (inclusive).
<b>ErrorInvalidPermissionSettings</b>	Specifies that the permission level is inconsistent with the permission settings.
<b>ErrorInvalidPhoneCallId</b>	Specifies that the caller identifier is not valid.
<b>ErrorInvalidPhoneNumber</b>	Specifies that the phone number is not correct or does not fit the dial plan rules.
<b>ErrorInvalidUserInfo</b>	<p>Specifies that a client sent an invalid folder permission request. This error code MUST be returned under the following conditions:</p> <ul style="list-style-type: none"> <li>▪ A user specifies a <b>DistinguishedUser</b> element of type <b>t:DistinguishedUserType</b> set to anonymous or default but then also provide either a SID, primary SMTP address or display name.</li> <li>▪ SID cannot be mapped to a user.</li> <li>▪ Primary SMTP address cannot be mapped to a user.</li> <li>▪ User specifies more than one mailbox by setting more than one of the following properties: SID, primary SMTP address, and display name.</li> <li>▪ An invalid SMTP address was provided for an external user.</li> <li>▪ The request doesn't specify a distinguished user, SID, primary SMTP address, display name, or external user.</li> <li>▪ The request specifies an identity that does not map to a user, group, or contact in the directory.</li> <li>▪ The provided user permission is a disabled user that had a SELF SID in the directory.</li> <li>▪ The request attempt to set the anonymous or default</li> </ul>

Value	Meaning
	<p>user permissions but the attempted permissions are not available on the folder.</p> <p>The <b>MessageXML</b> for an <b>ErrorInvalidUserInfo</b> response contains the SID and display name that <b>MUST</b> identify the user to be given permissions and the permission level that we attempted to be given to a user. The <b>MessageXML</b> can look like the following:</p> <pre data-bbox="829 436 1393 793"> &lt;m:MessageXml&gt;   &lt;t:InvalidPermission&gt;     &lt;t:Permission&gt;       &lt;t:UserId&gt;         &lt;t:SID&gt;S-1-5-21-797165400-4101840936-1213943508-1116&lt;/t:SID&gt;         &lt;t:DisplayName&gt;Christopher M. Simison&lt;/t:DisplayName&gt;       &lt;/t:UserId&gt;        &lt;t:PermissionLevel&gt;Owner&lt;/t:PermissionLevel&gt;     &lt;/t:Permission&gt;   &lt;/t:InvalidPermission&gt; &lt;/m:MessageXml&gt; </pre>
<b>ErrorInvalidPropertyAppend</b>	Occurs if the property that you are trying to append to does not support appending. The following are the only properties that support appending: Recipient collections (To, Cc, Bcc), Attendee collections (Required, Optional, Resources), Body property, and ReplyTo.
<b>ErrorInvalidPropertyDelete</b>	Specifies that the property that you are trying to delete does not support deleting. For example, you cannot delete the <b>ItemId</b> property of the <b>ItemType</b> object.
<b>ErrorInvalidPropertyForExists</b>	Occurs if you pass one of the flag properties to a <b>RestrictionType</b> filter of <b>ExistsType</b> . The following are the flag properties: <b>IsDraft</b> , <b>IsSubmitted</b> , <b>IsUnmodified</b> , <b>IsResend</b> , and <b>IsFromMe</b> .
<b>ErrorInvalidPropertyForOperation</b>	Specifies that the property that you are trying to manipulate does not support the operation that is being performed on it.
<b>ErrorInvalidPropertyRequest</b>	Occurs if the property that is specified in the request is not available for the item type. For example, this response code is returned if a property that is only available on calendar items is requested in a <b>GetItem</b> method call for a message or is updated in an <b>UpdateItem</b> method call for a message.
<b>ErrorInvalidPropertySet</b>	Specifies that the property you are trying to set is read-only.
<b>ErrorInvalidPropertyUpdateSentMessage</b>	Occurs during an <b>UpdateItem</b> method call when a client tries to update certain properties of a message that has already been sent. For example, the following properties cannot be updated on a sent message:

Value	Meaning
	IsReadReceiptRequested and IsDeliveryReceiptRequested
<b>ErrorInvalidProxySecurityContext</b>	This response code is not used.
<b>ErrorInvalidPullSubscriptionId</b>	Occurs if you called GetEvents or Unsubscribe on a push subscription ID. To unsubscribe from a push subscription, you MUST respond to a push request with an unsubscribe response, or disconnect your Web service and wait for the push notifications to time out.
<b>ErrorInvalidPushSubscriptionUrl</b>	Specifies that the URL that was provided as a callback for the Subscribe method has an invalid format. The following conditions MUST be met for Exchange Web Services to accept the URL: String length MUST be greater than 0 and less than 2083, protocol is http or https, and able to be parsed by the URI Microsoft .NET Framework class.
<b>ErrorInvalidRecipients</b>	Specifies that the recipient collection on your message or the attendee collection on your calendar item is invalid.
<b>ErrorInvalidRecipientSubfilter</b>	Specifies that the search folder has a recipient table filter that Exchange Web Services cannot represent. To fix the error, retrieve the folder without requesting the search parameters.
<b>ErrorInvalidRecipientSubfilterComparison</b>	Specifies that the search folder has a recipient table filter that Exchange Web Services cannot represent. To fix the error, retrieve the folder without requesting the search parameters.
<b>ErrorInvalidRecipientSubfilterOrder</b>	Specifies that the search folder has a recipient table filter that Exchange Web Services cannot represent. To fix the error, retrieve the folder without requesting the search parameters.
<b>ErrorInvalidRecipientSubfilterTextFilter</b>	Specifies that the search folder has a recipient table filter that Exchange Web Services cannot represent. To fix the error, retrieve the folder without requesting the search parameters.
<b>ErrorInvalidReferenceItem</b>	Occurs under the following circumstances: The referenced item identifier is not a MessageType or CalendarItemType object, or one of their descendants; the reference item identifier is for a CalendarItemType object and the organizer is trying to Reply or ReplyAll. Calendar items can only be forwarded by the organizer; the message is a draft and Reply or ReplyAll is selected, and the ResponseObjects is set to SuppressReadReceipt and the item is not a message.
<b>ErrorInvalidRequest</b>	Specifies that the SOAP request has a SOAP action header, but nothing in the SOAP body. Note that the SOAP action header is not required as Exchange Web Services can determine the method to call from the local name of the root element in the SOAP body.
<b>ErrorInvalidRestriction</b>	This response code is not used.
<b>ErrorInvalidRetentionTagTypeMismatch</b>	Specifies that the retention tag type was not

Value	Meaning
	matched.<56>
<b>ErrorInvalidRetentionTagInvisible</b>	Specifies that the retention tag was not visible.<57>
<b>ErrorInvalidRetentionTagIdGuid</b>	Specifies that a retention tag had an invalid GUID.<58>
<b>ErrorInvalidRetentionTagInheritance</b>	Specifies that there was an error in retention tag inheritance.<59>
<b>ErrorInvalidRoutingType</b>	Specifies that the RoutingType property that was passed for an EmailAddressType is not a valid routing type. Typically, routing type is set to SMTP.
<b>ErrorInvalidScheduledOofDuration</b>	Occurs if the specified duration end time is not greater than the start time, or if the end time does not occur in the future.
<b>ErrorInvalidSchemaVersionForMailboxVersion</b>	Specifies that a proxy request sent to another server is not capable of servicing the request due to a versioning mismatch. This error MUST be returned when the <b>RequestServerVersion</b> element (section 2.2.5.9) specifies a server version that does not match the mailbox server for a proxy request.
<b>ErrorInvalidSecurityDescriptor</b>	Specifies that the security descriptor on the Calendar folder in the store is corrupted.
<b>ErrorInvalidSendItemSaveSettings</b>	Occurs during an attempt to send an item where the SaveItemFolderId is specified in the request but the SaveItemToFolder property is set to false.
<b>ErrorInvalidSerializedAccessToken</b>	Specifies that the token that was passed in the header is malformed, does not refer to a valid account in the directory, or is missing the primary group SID.
<b>ErrorInvalidServerVersion</b>	Specifies that an invalid request server version was specified in the request.
<b>ErrorInvalidSid</b>	Specifies that one or more of the SID properties within the passed token or Impersonation block have an invalid structure.
<b>ErrorInvalidSIPUri</b>	Specifies that the SIP name, dial plan, or the phone number are invalid SIP URI.
<b>ErrorInvalidSmtpAddress</b>	Specifies that the SMTP address cannot be parsed.
<b>ErrorInvalidSubfilterType</b>	This response code is not used.
<b>ErrorInvalidSubfilterTypeNotAttendeeType</b>	This response code is not used.
<b>ErrorInvalidSubfilterTypeNotRecipientType</b>	This response code is not used.
<b>ErrorInvalidSubscription</b>	Specifies that the subscription is no longer valid. This could be because the Client Access is restarting or because the subscription expired.
<b>ErrorInvalidSubscriptionRequest</b>	Specifies that the subscribe request included multiple public folder IDs. A subscription can include multiple

Value	Meaning
	folders from the same mailbox or one public folder ID.
<b>ErrorInvalidSyncStateData</b>	Specifies that the sync state data is corrupted. This is returned by the SyncFolderItems method or the SyncFolderHierarchy method if the SyncState property data is invalid. To fix this error, you MUST resynchronize without the sync state. Make sure that if you are persisting sync state blobs and that you are not accidentally truncating the BLOB.
<b>ErrorInvalidTimeInterval</b>	Specifies that the specified time interval is invalid. The start time MUST be greater than or equal to the end time.
<b>ErrorInvalidUserOofSettings</b>	Specifies that the user Out of Office (OOF) settings are invalid because of a missing internal or external reply.
<b>ErrorInvalidUserPrincipalName</b>	Specifies that the UPN that was passed in the Impersonation <b>SOAP header</b> did not map to a valid account.
<b>ErrorInvalidUserSid</b>	Specifies that the SID that was passed in the Impersonation SOAP header was either structurally invalid or did not map to a valid account.
<b>ErrorInvalidUserSidMissingUPN</b>	This response code is not used.
<b>ErrorInvalidValueForProperty</b>	Specifies that the comparison value in the restriction is invalid for the property you are comparing against. For example, the comparison value of DateTimeCreated > true would return this response code. This response code is also returned if you specify an enumeration property in the comparison, but the value that you are comparing against is not a valid value for that enumeration.
<b>ErrorInvalidWatermark</b>	Specifies that the watermark is invalid.
<b>ErrorIPGatewayNotFound</b>	Specifies that a valid VoIP gateway is not available.
<b>ErrorIrresolvableConflict</b>	Specifies that conflict resolution was unable to resolve changes for the properties. The items in the store might have been changed and have to be updated. Retrieve the updated change key and try again.
<b>ErrorItemCorrupt</b>	Specifies that the state of the object is corrupted and cannot be retrieved. When you are retrieving an item, only certain properties will be in this state, such as Body and MimeContent. Omit these properties and retry the operation.
<b>ErrorItemNotFound</b>	Specifies that the item was not found or you do not have rights to access the item.
<b>ErrorItemPropertyRequestFailed</b>	Occurs if a property request fails. The property might exist, but it could not be retrieved.
<b>ErrorItemSave</b>	Occurs when attempts to save the item or folder fail.
<b>ErrorItemSavePropertyError</b>	Occurs when attempts to save the item or folder fail because of invalid property values. The response code

Value	Meaning
	includes the path of the invalid properties.
<b>ErrorLegacyMailboxFreeBusyViewTypeNotMerged</b>	This response code is not used.
<b>ErrorLocalServerObjectNotFound</b>	This response code is not used.
<b>ErrorLogonAsNetworkServiceFailed</b>	Specifies that the availability service was unable to log on as the network service in order to proxy requests to the appropriate sites or forests. This response typically indicates a configuration error.
<b>ErrorMailboxConfiguration</b>	Specifies that the mailbox information in Active Directory is configured incorrectly.
<b>ErrorMailboxDataArrayEmpty</b>	Specifies that the MailboxDataArray property in the request is empty. You MUST supply at least one mailbox identifier.
<b>ErrorMailboxDataArrayTooBig</b>	Occurs when more than 100 entries are supplied in a MailboxDataArray.
<b>ErrorMailboxHoldNotFound</b>	Specifies that the mailbox hold was not found. <60>
<b>ErrorMailboxLogonFailed</b>	Occurs when the connection to the mailbox to get the calendar view information failed.
<b>ErrorMailboxMoveInProgress</b>	Specifies that the mailbox is currently being moved. Try your request again after the move is complete.
<b>ErrorMailboxStoreUnavailable</b>	Specifies that the mailbox database is offline, corrupt, shutting down, or exhibiting other conditions that make the mailbox unavailable.
<b>ErrorMailRecipientNotFound</b>	Occurs if the MailboxData information cannot be mapped to a valid mailbox account.
<b>ErrorMailTipsDisabled</b>	Specifies that mail tips are disabled. This error code MUST be returned when mail tips are disabled.
<b>ErrorManagedFolderAlreadyExists</b>	Specifies that the managed folder that you are trying to create already exists in your mailbox.
<b>ErrorManagedFolderNotFound</b>	Occurs when the folder name that was specified in the request does not map to a managed folder definition in Active Directory. You can only create instances of managed folders for folders defined in Active Directory. Check the name and try again.
<b>ErrorManagedFoldersRootFailure</b>	Specifies that the managed folders root was deleted from the mailbox or that there is already a folder in the same parent folder that has the name of the managed folder root. This will also occur if the attempt to create the root managed folder fails.
<b>ErrorMeetingSuggestionGenerationFailed</b>	Specifies that the suggestions engine encountered a problem when it was trying to generate the suggestions.
<b>ErrorMessageDispositionRequired</b>	Occurs if the MessageDisposition property is not set. This property is required (1) when the item that is being

Value	Meaning
	created or updated is a MessageType object and (2) for the CancelCalendarItemType, AcceptItemType, DeclineItemType, or TentativelyAcceptItemType response objects.
<b>ErrorMessageSizeExceeded</b>	Specifies that the message that you are trying to send exceeded the allowed limits.
<b>ErrorMimeContentConversionFailed</b>	Occurs when the MIME content is not a valid iCal for a CreateItem method. For a GetItem method, this response indicates that the MIME content could not be generated.
<b>ErrorMimeContentInvalid</b>	Occurs when the MIME content is invalid.
<b>ErrorMimeContentInvalidBase64String</b>	Occurs when the MIME content in the request is not a valid base64 string.
<b>ErrorMissingArgument</b>	Specifies that a required argument was missing from the request. The response message text indicates which argument to check.
<b>ErrorMissingEmailAddress</b>	Specifies that you specified a distinguished folder ID in the request, but the account that made the request does not have a mailbox on the system.
<b>ErrorMissingEmailAddressForManagedFolder</b>	Specifies that you specified a distinguished folder ID in the request, but the account that made the request does not have a mailbox on the system. This response is returned from the CreateManagedFolder method.
<b>ErrorMissingInformationEmailAddress</b>	Specifies that the attendee or recipient does not have the EmailAddress property set. The other two EmailAddressType properties, Name and RoutingType, are optional.
<b>ErrorMissingInformationReferenceItemId</b>	Occurs if the ReferenceItemId property value is missing from the response object.
<b>ErrorMissingItemForCreateItemAttachment</b>	Occurs when you are creating an item attachment if you do not indicate the item that you want to create.
<b>ErrorMissingManagedFolderId</b>	Occurs when the policy IDs property, property tag 0x6732, for the folder is missing. You SHOULD consider this a corrupted folder.
<b>ErrorMissingRecipients</b>	Specifies that you tried to send an item without including recipients. Note that if you call the CreateItem method with a message disposition that causes the message to be sent, you will get the following response code: ErrorInvalidRecipients.
<b>ErrorMissingUserIdInformation</b>	Specifies that a user ID has not been fully specified in a permissions set.
<b>ErrorMoreThanOneAccessModeSpecified</b>	Specifies that you have specified more than one ExchangeImpersonation or SerializedSecurityContext property value within a request.
<b>ErrorMoveCopyFailed</b>	Specifies that the move or copy operation failed. Moving occurs in the CreateItem method when you accept a

Value	Meaning
	meeting request that is in the Deleted Items folder. In addition, if you decline a meeting request, cancel a calendar item, or remove a meeting from your calendar, it is moved to the Deleted Items folder.
<b>ErrorMoveDistinguishedFolder</b>	Occurs if you try to move a distinguished folder.
<b>ErrorMultiLegacyMailboxAccess</b>	Specifies that the request tried to access multiple mailbox servers. <a href="#">61</a>
<b>ErrorNameResolutionMultipleResults</b>	Specifies that the ResolveNames method returned more than one result or that the ambiguous name that you specified matched more than one object in the directory. The response code includes the matched names in the response data.
<b>ErrorNameResolutionNoMailbox</b>	Specifies that the caller does not have a mailbox on the system.
<b>ErrorNameResolutionNoResults</b>	Occurs if the ResolveNames method returns no results.
<b>ErrorNoApplicableProxyCASServersAvailable</b>	This error code MUST be returned when the Web service cannot find a server to handle the request.
<b>ErrorNoCalendar</b>	Occurs if there is no Calendar folder for the mailbox.
<b>ErrorNoDestinationCASDueToKerberosRequirements</b>	Specifies that the request referred to a mailbox in another Active Directory site, but no Client Access servers in the destination site were configured for win Authentication and therefore the request could not be proxied.
<b>ErrorNoDestinationCASDueToSSLRequirements</b>	Specifies that the request referred to a mailbox in another Active Directory site, but no Client Access servers in the destination site were configured for SSL connections and therefore the request could not be proxied.
<b>ErrorNoDestinationCASDueToVersionMismatch</b>	Specifies that the request referred to a mailbox in another Active Directory site, but no Client Access servers in the destination site were of an acceptable product version to receive the request and therefore the request could not be proxied.
<b>ErrorNoFolderClassOverride</b>	Occurs if you set the FolderClass property when you are creating an item other than a generic folder. For typed folders such as CalendarFolderType and TasksFolderType, the folder class is implied. Setting the folder class to a different folder type by using the UpdateFolder method results in the ErrorObjectTypeChanged response. Instead, use a generic folder type but set the folder class to the value that you require. Exchange Web Services will create the correct strongly typed folder.
<b>ErrorNoFreeBusyAccess</b>	Specifies that the caller does not have free/busy viewing rights on the Calendar folder in question.
<b>ErrorNonExistentMailbox</b>	Specifies one of the following: (1) The e-mail address is empty in the CreateManagedFolder method or (2) the SMTP address does not map to a valid mailbox.



<b>Value</b>	<b>Meaning</b>
<b>ErrorNonPrimarySmtpAddress</b>	Occurs when a caller passes in a non-primary SMTP address. The response includes the correct SMTP address to use.
<b>ErrorNoPropertyTagForCustomProperties</b>	Specifies that MAPI properties in the custom range, 0x8000 and greater, cannot be referenced by property tags. You MUST use the PropertySetId property or the DistinguishedPropertySetId together with the PropertyName or PropertyId properties.
<b>ErrorNoPublicFolderReplicaAvailable</b>	This response code is not used.
<b>ErrorNoPublicFolderServerAvailable</b>	This error code MUST be returned if no public folder server is available or if the caller does not have a home public server.
<b>ErrorNoRespondingCASInDestinationSite</b>	Specifies that the request referred to a mailbox in another Active Directory site, but none of the Client Access servers in that site responded and therefore the request could not be proxied.
<b>ErrorNotDelegate</b>	Specifies that the user is not a delegate for the mailbox. This error is returned by GetDelegate, RemoveDelegate, and UpdateDelegate method calls when the specified delegate user is not found in the list of delegates.
<b>ErrorNotEnoughMemory</b>	Specifies that the operation could not be completed because of insufficient memory.
<b>ErrorObjectTypeChanged</b>	Specifies that the object type cannot be changed. For the CreateItem method, the ItemClass property MUST be consistent with the strongly typed item such as a Message or Contact.
<b>ErrorOccurrenceCrossingBoundary</b>	Specifies that the time allotment for a given occurrence overlaps with an earlier or later occurrence.
<b>ErrorOccurrenceTimeSpanTooBig</b>	Specifies that the time allotment for a given occurrence overlaps with another occurrence of the same recurring item. This response also occurs if the length in minutes of a given occurrence is larger than Int32.MaxValue.
<b>ErrorOperationNotAllowedWithPublicFolderRoot</b>	Specifies that the current operation is not valid to be performed on the public folder root.
<b>ErrorParentFolderIdRequired</b>	This response code is not used.
<b>ErrorParentFolderNotFound</b>	Occurs in the CreateFolder when the parent folder is not found.
<b>ErrorPasswordChangeRequired</b>	Specifies that you MUST change your password before you can access this mailbox. This occurs when a new account has been created and the administrator indicated that the user MUST change the password at first logon. You cannot update the password by using Exchange Web Services. You MUST use a tool such as Outlook Web Access to change your password.
<b>ErrorPasswordExpired</b>	Specifies that the password has expired. You cannot

Value	Meaning
	change the password by using Exchange Web Services. You MUST use a tool such as Outlook Web Access to change your password.
<b>ErrorPhoneNumberNotDialable</b>	Specifies that the phone number was not in the correct phone form.
<b>ErrorPropertyUpdate</b>	Specifies that the update failed because of invalid property values. The response message includes the invalid property paths.
<b>ErrorPromptPublishingOperationFailed</b>	<a href="#">&lt;62&gt;</a>
<b>ErrorPropertyValidationFailure</b>	This response code is not used.
<b>ErrorProxiedSubscriptionCallFailure</b>	Specifies that the request referred to a subscription that exists on another Client Access server, but an attempt to proxy the request to that Client Access server failed.
<b>ErrorProxyCallFailed</b>	This response code is not used.
<b>ErrorProxyGroupSidLimitExceeded</b>	Specifies that the request referred to a mailbox in another Active Directory site, and the original caller is a member of more than 3000 groups.
<b>ErrorProxyRequestNotAllowed</b>	Specifies that the request that Exchange Web Services sent to another Client Access server when trying to fulfill a GetUserAvailability request was invalid. This response code likely indicates a configuration or rights error, or that someone is trying unsuccessfully to mimic an availability proxy request.
<b>ErrorProxyRequestProcessingFailed</b>	Specifies that Exchange Web Services tried to proxy an availability request to another Client Access server for fulfillment, but the request failed. This response can be caused by network connectivity issues or request time-out issues.
<b>ErrorProxyServiceDiscoveryFailed</b>	This error code MUST be returned if the Web service cannot determine whether the request is to run on the target server or will be proxied to another server.
<b>ErrorProxyTokenExpired</b>	This response code is not used.
<b>ErrorPublicFolderMailboxDiscoveryFailed</b>	Occurs when the public folder mailbox <b>endpoint (4) URL</b> discovery fails. <a href="#">&lt;63&gt;</a>
<b>ErrorPublicFolderOperationFailed</b>	Specifies that the service binding failed. <a href="#">&lt;64&gt;</a>
<b>ErrorPublicFolderRequestProcessingFailed</b>	Occurs when the recipient passed to GetUserAvailability is located on a computer that is running a server version that is earlier than the 2007 server version and the request to retrieve free/busy information for the recipient from the public folder server failed.
<b>ErrorPublicFolderServerNotFound</b>	Occurs when the recipient passed to GetUserAvailability is located on a server that is running a server version that is earlier than the 2007 server version and the request to retrieve free/busy information for the recipient from the public folder server failed because the organizational unit

Value	Meaning
	did not have a public folder server associated with it.
<b>ErrorPublicFolderSyncException</b>	Specifies that folder synchronization failed. <a href="#">&lt;65&gt;</a>
<b>ErrorQueryFilterTooLong</b>	Specifies that the search folder restriction might be valid, but it is not supported by Exchange Web Services. Exchange Web Services limits restrictions to contain a maximum of 255 filter expressions. If you try to bind to an existing search folder that exceeds 255, this response code is returned.
<b>ErrorQuotaExceeded</b>	Occurs when the mailbox quota is exceeded.
<b>ErrorReadEventsFailed</b>	Specifies that the process for reading events was aborted because of an internal failure. Re-create the event synchronization based on a last known watermark.
<b>ErrorReadReceiptNotPending</b>	Occurs when an attempt has been made to suppress a read receipt when the message sender did not request a read receipt on the message.
<b>ErrorRecurrenceEndDateTooBig</b>	Occurs when the end date for the recurrence is after 9/1/4500.
<b>ErrorRecurrenceHasNoOccurrence</b>	Specifies that the recurrence has no occurrence instances in the specified range.
<b>ErrorRemoveDelegatesFailed</b>	Specifies that the delegate list failed to be saved after delegates were removed.
<b>ErrorRequestAborted</b>	This response code is not used.
<b>ErrorRequestStreamTooBig</b>	Specifies that during availability proxying, the request was determined to be too large.
<b>ErrorRequiredPropertyMissing</b>	Specifies that one or more of the required properties is missing from a CreateAttachment call. The response indicates which property path was not set.
<b>ErrorResolveNamesInvalidFolderType</b>	Specifies that the caller has specified a folder that is not a Contacts folder to ResolveNames.
<b>ErrorResolveNamesOnlyOneContactsFolder Allowed</b>	Specifies that the caller has specified more than one Contacts folder to ResolveNames.
<b>ErrorResponseSchemaValidation</b>	This response code is not used.
<b>ErrorRestrictionTooLong</b>	Occurs when the restriction has more than 255 filters.
<b>ErrorRestrictionTooComplex</b>	Specifies that the restriction that was passed cannot be evaluated by Exchange Web Services.
<b>ErrorResultSetTooBig</b>	Specifies that the number of calendar entries for a given recipient exceeds the allowed limit of 1000. Reduce the window and try again.
<b>ErrorInvalidExchangeImpersonationHeader Data</b>	Specifies that the ExchangeImpersonation header is missing or empty. This error MUST be returned if an <b>ExchangeImpersonation</b> element (section <a href="#">2.2.5.3</a> ) is

Value	Meaning
	empty.
<b>ErrorSavedItemFolderNotFound</b>	Specifies that the folder in which to save the item does not exist.
<b>ErrorSchemaValidation</b>	Occurs when the incoming request fails schema validation against types.xsd and messages.xsd. This response code is always returned within a SOAP fault.
<b>ErrorSearchFolderNotInitialized</b>	Specifies that the search folder was created, but the search criteria were never set on the folder. This only occurs when you access corrupted search folders that were created by using another API or client. To fix this error, call UpdateFolder and set the SearchParameters to include the restriction that SHOULD be on the folder.
<b>ErrorSendAsDenied</b>	Occurs when both of the following conditions occur:
<b>ErrorSendMeetingCancellationsRequired</b>	Occurs during a DeleteItem call, when the SendMeetingCancellations property is missing from the request and the item to delete is a calendar item. If you are using the proxy objects, make sure that the SendMeetingCancellationsSpecified property is set to true.
<b>ErrorSendMeetingInvitationsOrCancellation sRequired</b>	Occurs during an UpdateItem method call, when the SendMeetingInvitationsOrCancellations property is missing from the request and the item to update is a calendar item. If you are using the proxy objects, make sure that the SendMeetingInvitationsOrCancellationsSpecified property is set to true.
<b>ErrorSendMeetingInvitationsRequired</b>	Occurs during a CreateItem method call, when the SendMeetingInvitations property is missing from the request and the item to create is a calendar item. If you are using the proxy objects, make sure that the SendMeetingInvitationsSpecified property is set to true.
<b>ErrorSentMeetingRequestUpdate</b>	Specifies that after the organizer sends a meeting request, the request cannot be updated. To modify the meeting, modify the calendar item, not the meeting request.
<b>ErrorSentTaskRequestUpdate</b>	Specifies that after the task initiator sends a task request, that request cannot be updated.
<b>ErrorServerBusy</b>	Occurs when the server is busy.
<b>ErrorServiceDiscoveryFailed</b>	Specifies that Exchange Web Services tried to proxy a user availability request to the appropriate forest for the recipient, but it could not determine where to send the request because of a service discovery failure.
<b>ErrorStaleObject</b>	Occurs in an UpdateItem or SendItem method call when the change key is not up to date or was not supplied. Call GetItem to retrieve an updated change key and then try the operation again.
<b>ErrorSubmissionQuotaExceeded</b>	Specifies that a user cannot immediately send more request because the submission quota has been reached.

Value	Meaning
<b>ErrorSubscriptionAccessDenied</b>	Specifies that you tried to access a subscription by using an account that did not create that subscription. Each subscription can only be accessed by the creator of the subscription.
<b>ErrorSubscriptionDelegateAccessNotSupported</b>	Specifies that you cannot create a subscription if you are not the owner or do not have owner access to the mailbox.
<b>ErrorSubscriptionNotFound</b>	Specifies that the specified subscription does not exist. The subscription might have expired, the Exchange Web Services process might have been restarted, or an invalid subscription was passed in. If the subscription was valid, re-create the subscription with the latest watermark.
<b>ErrorSubscriptionUnsubscribed</b>	This error code MUST be returned when a request is made for a subscription that has been unsubscribed.
<b>ErrorSyncFolderNotFound</b>	Specifies that the folder ID that was specified in the SyncFolderItems method call does not exist.
<b>ErrorTeamMailboxNotFound</b>	<a href="#">&lt;66&gt;</a>
<b>ErrorTeamMailboxNotLinkedToSharePoint</b>	<a href="#">&lt;67&gt;</a>
<b>ErrorTeamMailboxUrlValidationFailed</b>	<a href="#">&lt;68&gt;</a>
<b>ErrorTeamMailboxNotAuthorizedOwner</b>	<a href="#">&lt;69&gt;</a>
<b>ErrorTeamMailboxActiveToPendingDelete</b>	<a href="#">&lt;70&gt;</a>
<b>ErrorTeamMailboxFailedSendingNotifications</b>	<a href="#">&lt;71&gt;</a>
<b>ErrorTeamMailboxErrorUnknown</b>	<a href="#">&lt;72&gt;</a>
<b>ErrorTimeIntervalTooBig</b>	Specifies that the time window that was specified is larger than the allowed limit. By default, the allowed limit is 42.
<b>ErrorTimeoutExpired</b>	Specifies that the proxied request timed out.
<b>ErrorTimeZone</b>	Specifies that there is a time zone error.
<b>ErrorToFolderNotFound</b>	Specifies that the destination folder does not exist.
<b>ErrorTokenSerializationDenied</b>	Occurs if the caller tries to perform a token serialization request but does not have ms-Exch-EPI-TokenSerialization rights on the Client Access server they are calling.
<b>ErrorUpdatePropertyMismatch</b>	Occurs when the single property path that is listed in a change description does not match the single property that is being set within the actual ItemType or FolderType object.
<b>ErrorUnifiedMessagingDialPlanNotFound</b>	Specifies that a user's dial plan is not available.
<b>ErrorUnifiedMessagingReportDataNotFound</b>	<a href="#">&lt;73&gt;</a>
<b>ErrorUnifiedMessagingPromptNotFound</b>	<a href="#">&lt;74&gt;</a>

Value	Meaning
<b>ErrorUnifiedMessagingRequestFailed</b>	Specifies that the user could not be found.
<b>ErrorUnifiedMessagingServerNotFound</b>	Specifies that a valid server for the dial plan can be found to handle the request.
<b>ErrorUnableToGetUserOofSettings</b>	This response code is not used.
<b>ErrorUnableToRemoveImContactFromGroup</b>	<75>
<b>ErrorUnsupportedSubFilter</b>	This response code is not used.
<b>ErrorUnsupportedCulture</b>	Occurs if you try to set the Culture property to a value that is not parsable by the System.Globalization.CultureInfo class.
<b>ErrorUnsupportedMapiPropertyType</b>	Occurs if a caller tries to use extended properties of types object, object array, error or null.
<b>ErrorUnsupportedMimeConversion</b>	Occurs when you are trying to retrieve or set MIME content for an item other than a PostItemType, MessageType, or CalendarItemType object.
<b>ErrorUnsupportedPathForQuery</b>	Specifies that the property path cannot be used within a restriction. This value MUST be returned if an Excludes restriction is performed on a non-integer property.
<b>ErrorUnsupportedPathForSortGroup</b>	Specifies that the property path cannot be used for sorting or grouping operations.
<b>ErrorUnsupportedPropertyDefinition</b>	This response code is not used.
<b>ErrorUnsupportedQueryFilter</b>	Specifies that the search folder restriction might be valid, but is not supported by Exchange Web Services. You can still call the FindItem method on the search folder restriction to retrieve the items in the search folder; however, you cannot get the actual restriction clause.
<b>ErrorUnsupportedRecurrence</b>	Specifies that the recurrence pattern that was supplied is not supported for tasks.
<b>ErrorUnsupportedTypeForConversion</b>	Specifies that Exchange Web Services found a property type in the store but cannot generate XML for the property type.
<b>ErrorUpdateDelegatesFailed</b>	Specifies that the delegate list failed to be saved after delegates were updated.
<b>ErrorUserNotUnifiedMessagingEnabled</b>	Specifies that the requestor is not enabled.
<b>ErrorValueOutOfRange</b>	Specifies that a calendar view start date or end date was set to 1/1/0001 12:00:00 AM or 12/31/9999 11:59:59 PM.
<b>ErrorVoiceMailNotImplemented</b>	Specifies that voice mail is not implemented.
<b>ErrorVirusDetected</b>	Specifies that the database detected a virus in the message.

<b>Value</b>	<b>Meaning</b>
<b>ErrorVirusMessageDeleted</b>	Specifies that the database detected a virus in the message and deleted it.
<b>ErrorWebRequestInInvalidState</b>	This response code is not used.
<b>ErrorWin32InteropError</b>	Specifies that there was an internal failure during communication with unmanaged code.
<b>ErrorWorkingHoursSaveFailed</b>	This response code is not used.
<b>ErrorWorkingHoursXmlMalformed</b>	This response code is not used.
<b>ErrorWrongServerVersion</b>	Specifies that a request can only be made to a server that is the same version as the mailbox server. This error MUST be returned if a request is made to a server that is not the same version as the mailbox server.
<b>ErrorWrongServerVersionDelegate</b>	Specifies that a request was made by a delegate that has a different server version than the principal's mailbox server. This error MUST be returned if a request was made by a delegate that has a different server version than the principal's mailbox server.
<b>ErrorMissingInformationSharingFolderId</b>	This error code is never returned.
<b>ErrorDuplicateSOAPHeader</b>	Specifies that there are duplicate SOAP headers.
<b>ErrorSharingSynchronizationFailed</b>	Specifies that an attempt at synchronizing a sharing folder failed. This error code MUST be returned when: <ul style="list-style-type: none"> <li>▪ The subscription for a sharing folder is not found.</li> <li>▪ The sharing folder was not found.</li> <li>▪ The corresponding directory user was not found.</li> <li>▪ The user no longer exists.</li> <li>▪ The appointment is invalid.</li> <li>▪ The contact item is invalid.</li> <li>▪ There was a communication failure with the remote server.</li> </ul>
<b>ErrorSharingNoExternalEwsAvailable</b>	Specifies that the external URL property has not been set in the Active Directory database. This error code MUST be returned if the external URL property has not been set in the Active Directory database.
<b>ErrorFreeBusyDLLimitReached</b>	Specifies that the maximum group member count has been reached for obtaining free/busy information for a distribution list. This error MUST be returned when the maximum group member count has been reached for obtaining free/busy information for a distribution list.
<b>ErrorInvalidGetSharingFolderRequest</b>	Specifies that the DataType and ShareFolderId element are both present in a request. This error code MUST be returned if the DataType and ShareFolderId element are

Value	Meaning
	both present in a request.
<b>ErrorNotAllowedExternalSharingByPolicy</b>	Specifies that the caller attempted to grant permissions in its calendar or contacts folder to a user in another organization and the attempt failed. This error code MUST be returned when the sharing policy is disabled for the caller or when the sharing policy assigned to the caller disallows sharing for the requested level or the requested folder type.
<b>ErrorUserNotAllowedByPolicy</b>	Specifies that the requestor attempted to grant permissions in its calendar or contacts folder to an external user but the sharing policy assigned to the requestor specifies that the domain of the external user is not listed in the policy.
<b>ErrorPermissionNotAllowedByPolicy</b>	Specifies that the requestor attempted to grant permissions in its calendar or contacts folder to an external user but the sharing policy assigned to the requestor specifies that the requested permission level is higher than what the sharing policy allows.
<b>ErrorOrganizationNotFederated</b>	Specifies that the requestor's organization is not federated so the requestor cannot create sharing messages to send to an external user or cannot accept sharing messages received from an external user. This error code MUST be returned if the requestor's organization is not federated.
<b>ErrorMailboxFailover</b>	Specifies that an attempt to access a mailbox failed because the mailbox is in a failover process.
<b>ErrorInvalidExternalSharingInitiator</b>	Specifies that the sharing invitation sender did not create the sharing invitation metadata. This error code MUST be returned if the sharing invitation sender did not create the sharing invitation metadata.
<b>ErrorMessageTrackingPermanentError</b>	Specifies that the message tracking service cannot track the message.
<b>ErrorMessageTrackingTransientError</b>	Specifies that either the message tracking service is down or busy. This error code specifies a transient error. Clients can retry to connect to the server when this error is received.
<b>ErrorMessageTrackingNoSuchDomain</b>	Specifies that the given domain cannot be found.
<b>ErrorUserWithoutFederatedProxyAddress</b>	Specifies that the requestor's organization has a set of federated domains but the requestor's organization does not have any SMTP proxy addresses with one of the federated domains.
<b>ErrorInvalidOrganizationRelationshipForFreeBusy</b>	Specifies that a caller requested free/busy information for a user in another organization but the organizational relationship does not have free/busy enabled.
<b>ErrorInvalidFederatedOrganizationId</b>	Specifies that the requestor's organization federation objects are not properly configured.
<b>ErrorInvalidExternalSharingSubscriber</b>	Specifies that a sharing message is not intended for the



Value	Meaning
	caller.
<b>ErrorInvalidSharingData</b>	Specifies that the sharing metadata is not valid. This can be caused by invalid XML.
<b>ErrorInvalidSharingMessage</b>	Specifies that the sharing message is not valid. This can be caused by a missing property.
<b>ErrorNotSupportedSharingMessage</b>	Specifies that the sharing message is not supported.
<b>ErrorApplyConversationActionFailed</b>	This error MUST be returned if an action cannot be applied to one or more items in the conversation.
<b>ErrorInboxRulesValidationError</b>	This error MUST be returned if any rule does not validate.
<b>ErrorOutlookRuleBlobExists</b>	This error MUST be returned when an attempt to manage Inbox rules occurs after another client has accessed the Inbox rules.
<b>ErrorRulesOverQuota</b>	This error MUST be returned when a user's rule quota has been exceeded.
<b>ErrorNewEventStreamConnectionOpened</b>	This error MUST be returned to the first subscription connection if a second subscription connection is opened.
<b>ErrorMissedNotificationEvents</b>	This error MUST be returned when event notifications are missed.
<b>ErrorDuplicateLegacyDistinguishedName</b>	<a href="#">&lt;76&gt;</a>
<b>ErrorInvalidClientAccessTokenRequest</b>	<a href="#">&lt;77&gt;</a>
<b>ErrorNoSpeechDetected</b>	<a href="#">&lt;78&gt;</a>
<b>ErrorUMServerUnavailable</b>	<a href="#">&lt;79&gt;</a>
<b>ErrorRecipientNotFound</b>	<a href="#">&lt;80&gt;</a>
<b>ErrorRecognizerNotInstalled</b>	<a href="#">&lt;81&gt;</a>
<b>ErrorSpeechGrammarError</b>	<a href="#">&lt;82&gt;</a>
<b>ErrorInvalidManagementRoleHeader</b>	<a href="#">&lt;83&gt;</a>
<b>ErrorLocationServicesDisabled</b>	<a href="#">&lt;84&gt;</a>
<b>ErrorLocationServicesRequestTimedOut</b>	<a href="#">&lt;85&gt;</a>
<b>ErrorLocationServicesRequestFailed</b>	<a href="#">&lt;86&gt;</a>
<b>ErrorLocationServicesInvalidRequest</b>	<a href="#">&lt;87&gt;</a>
<b>ErrorMailboxScopeNotAllowedWithoutQueryString</b>	<a href="#">&lt;88&gt;</a>
<b>ErrorArchiveMailboxSearchFailed</b>	<a href="#">&lt;89&gt;</a>
<b>ErrorArchiveMailboxServiceDiscoveryFailed</b>	<a href="#">&lt;90&gt;</a>
<b>ErrorInvalidPhotoSize</b>	Specifies that the photo size is not valid. <a href="#">&lt;91&gt;</a>

Value	Meaning
<b>ErrorSearchQueryHasTooManyKeywords</b>	Specifies that the search query has too many keywords. <a href="#">&lt;92&gt;</a>
<b>ErrorSearchTooManyMailboxes</b>	Specifies that too many mailboxes were included in the search. <a href="#">&lt;93&gt;</a>
<b>ErrorDiscoverySearchesDisabled</b>	Specifies that the discovery search is disabled. <a href="#">&lt;94&gt;</a>

### 2.2.3.24 t:SensitivityChoicesType Simple Type

The **SensitivityChoicesType** simple type specifies the sensitivity level types that are available for an item.

```
<xs:simpleType name="SensitivityChoicesType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Confidential"/>
    <xs:enumeration value="Normal"/>
    <xs:enumeration value="Personal"/>
    <xs:enumeration value="Private"/>
  </xs:restriction>
</xs:simpleType>
```

The values that are defined by the **SensitivityChoicesType** simple type are listed in the following table.

Value	Meaning
<b>Confidential</b>	Specifies the item as confidential.
<b>Normal</b>	Specifies the item as normal.
<b>Personal</b>	Specifies the item as personal.
<b>Private</b>	Specifies the item as private.

### 2.2.3.25 t:UnindexedFieldURIType Simple Type

The **UnindexedFieldURIType** simple type specifies unindexed properties. [<95>](#)

```
<xs:simpleType name="UnindexedFieldURIType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="folder:FolderId"/>
    <xs:enumeration value="folder:ParentFolderId"/>
    <xs:enumeration value="folder:DisplayName"/>
    <xs:enumeration value="folder:UnreadCount"/>
    <xs:enumeration value="folder:TotalCount"/>
    <xs:enumeration value="folder:ChildFolderCount"/>
    <xs:enumeration value="folder:FolderClass"/>
    <xs:enumeration value="folder:SearchParameters"/>
    <xs:enumeration value="folder:ManagedFolderInformation"/>
    <xs:enumeration value="folder:PermissionSet"/>
    <xs:enumeration value="folder:EffectiveRights"/>
    <xs:enumeration value="folder:SharingEffectiveRights"/>
  </xs:restriction>
</xs:simpleType>
```

```

<xs:enumeration value="folder:DistinguishedFolderId"/>
<xs:enumeration value="folder:PolicyTag"/>
<xs:enumeration value="folder:ArchiveTag"/>
<xs:enumeration value="item:ItemId"/>
<xs:enumeration value="item:ParentFolderId"/>
<xs:enumeration value="item:ItemClass"/>
<xs:enumeration value="item:MimeContent"/>
<xs:enumeration value="item:Attachments"/>
<xs:enumeration value="item:Subject"/>
<xs:enumeration value="item:DateTimeReceived"/>
<xs:enumeration value="item:Size"/>
<xs:enumeration value="item:Categories"/>
<xs:enumeration value="item:HasAttachments"/>
<xs:enumeration value="item:Importance"/>
<xs:enumeration value="item:InReplyTo"/>
<xs:enumeration value="item:InternetMessageHeaders"/>
<xs:enumeration value="item:IsAssociated"/>
<xs:enumeration value="item:IsDraft"/>
<xs:enumeration value="item:IsFromMe"/>
<xs:enumeration value="item:IsResend"/>
<xs:enumeration value="item:IsSubmitted"/>
<xs:enumeration value="item:IsUnmodified"/>
<xs:enumeration value="item:DateTimeSent"/>
<xs:enumeration value="item:DateTimeCreated"/>
<xs:enumeration value="item:Body"/>
<xs:enumeration value="item:ResponseObjects"/>
<xs:enumeration value="item:Sensitivity"/>
<xs:enumeration value="item:ReminderDueBy"/>
<xs:enumeration value="item:ReminderIsSet"/>
<xs:enumeration value="item:ReminderNextTime"/>
<xs:enumeration value="item:ReminderMinutesBeforeStart"/>
<xs:enumeration value="item:DisplayTo"/>
<xs:enumeration value="item:DisplayCc"/>
<xs:enumeration value="item:Culture"/>
<xs:enumeration value="item:EffectiveRights"/>
<xs:enumeration value="item:LastModifiedName"/>
<xs:enumeration value="item:LastModifiedTime"/>
<xs:enumeration value="item:ConversationId"/>
<xs:enumeration value="item:UniqueBody"/>
<xs:enumeration value="item:Flag"/>
<xs:enumeration value="item:StoreEntryId"/>
<xs:enumeration value="item:InstanceKey"/>
<xs:enumeration value="item:NormalizedBody"/>
<xs:enumeration value="item:EntityExtractionResult" />
<xs:enumeration value="item:PolicyTag"/>
<xs:enumeration value="item:ArchiveTag"/>
<xs:enumeration value="item:RetentionDate"/>
<xs:enumeration value="item:Preview"/>
<xs:enumeration value="item:NextPredictedAction" />
<xs:enumeration value="item:GroupingAction" />
<xs:enumeration value="item:RightsManagementLicenseData" />
<xs:enumeration value="item:BlockStatus" />
<xs:enumeration value="item:HasBlockedImages" />
<xs:enumeration value="item:WebClientReadFormQueryString"/>
<xs:enumeration value="item:WebClientEditFormQueryString"/>
<xs:enumeration value="item:TextBody"/>
  <xs:enumeration value="item:IconIndex"/>
<xs:enumeration value="message:ConversationIndex"/>
<xs:enumeration value="message:ConversationTopic"/>

```

```
<xs:enumeration value="message:InternetMessageId"/>
<xs:enumeration value="message:IsRead"/>
<xs:enumeration value="message:IsResponseRequested"/>
<xs:enumeration value="message:IsReadReceiptRequested"/>
<xs:enumeration value="message:IsDeliveryReceiptRequested"/>
<xs:enumeration value="message:ReceivedBy"/>
<xs:enumeration value="message:ReceivedRepresenting"/>
<xs:enumeration value="message:References"/>
<xs:enumeration value="message:ReplyTo"/>
<xs:enumeration value="message:From"/>
<xs:enumeration value="message:Sender"/>
<xs:enumeration value="message:ToRecipients"/>
<xs:enumeration value="message:CcRecipients"/>
<xs:enumeration value="message:BccRecipients"/>
<xs:enumeration value="meeting:AssociatedCalendarItemId"/>
<xs:enumeration value="meeting:IsDelegated"/>
<xs:enumeration value="meeting:IsOutOfDate"/>
<xs:enumeration value="meeting:HasBeenProcessed"/>
<xs:enumeration value="meeting:ResponseType"/>
<xs:enumeration value="meeting:ProposedStart"/>
<xs:enumeration value="meeting:ProposedEnd"/>
<xs:enumeration value="meetingRequest:MeetingRequestType"/>
<xs:enumeration value="meetingRequest:IntendedFreeBusyStatus"/>
<xs:enumeration value="meetingRequest:ChangeHighlights"/>
<xs:enumeration value="calendar:Start"/>
<xs:enumeration value="calendar:End"/>
<xs:enumeration value="calendar:OriginalStart"/>
<xs:enumeration value="calendar:StartWallClock"/>
<xs:enumeration value="calendar:EndWallClock"/>
<xs:enumeration value="calendar:StartTimeZoneId"/>
<xs:enumeration value="calendar:EndTimeZoneId"/>
<xs:enumeration value="calendar:IsAllDayEvent"/>
<xs:enumeration value="calendar:LegacyFreeBusyStatus"/>
<xs:enumeration value="calendar:Location"/>
<xs:enumeration value="calendar:EnhancedLocation"/>
<xs:enumeration value="calendar:When"/>
<xs:enumeration value="calendar:IsMeeting"/>
<xs:enumeration value="calendar:IsCancelled"/>
<xs:enumeration value="calendar:IsRecurring"/>
<xs:enumeration value="calendar:MeetingRequestWasSent"/>
<xs:enumeration value="calendar:IsResponseRequested"/>
<xs:enumeration value="calendar:CalendarItemType"/>
<xs:enumeration value="calendar:MyResponseType"/>
<xs:enumeration value="calendar:Organizer"/>
<xs:enumeration value="calendar:RequiredAttendees"/>
<xs:enumeration value="calendar:OptionalAttendees"/>
<xs:enumeration value="calendar:Resources"/>
<xs:enumeration value="calendar:ConflictingMeetingCount"/>
<xs:enumeration value="calendar:AdjacentMeetingCount"/>
<xs:enumeration value="calendar:ConflictingMeetings"/>
<xs:enumeration value="calendar:AdjacentMeetings"/>
<xs:enumeration value="calendar:Duration"/>
<xs:enumeration value="calendar:TimeZone"/>
<xs:enumeration value="calendar:AppointmentReplyTime"/>
<xs:enumeration value="calendar:AppointmentSequenceNumber"/>
<xs:enumeration value="calendar:AppointmentState"/>
<xs:enumeration value="calendar:Recurrence"/>
<xs:enumeration value="calendar:FirstOccurrence"/>
<xs:enumeration value="calendar>LastOccurrence"/>
```

```
<xs:enumeration value="calendar:ModifiedOccurrences"/>
<xs:enumeration value="calendar:DeletedOccurrences"/>
<xs:enumeration value="calendar:MeetingTimeZone"/>
<xs:enumeration value="calendar:ConferenceType"/>
<xs:enumeration value="calendar:AllowNewTimeProposal"/>
<xs:enumeration value="calendar:IsOnlineMeeting"/>
<xs:enumeration value="calendar:MeetingWorkspaceUrl"/>
<xs:enumeration value="calendar:NetShowUrl"/>
<xs:enumeration value="calendar:UID"/>
<xs:enumeration value="calendar:RecurrenceId"/>
<xs:enumeration value="calendar:DateTimeStamp"/>
<xs:enumeration value="calendar:StartTimeZone"/>
<xs:enumeration value="calendar:EndTimeZone"/>
<xs:enumeration value="calendar:JoinOnlineMeetingUrl"/>
<xs:enumeration value="calendar:OnlineMeetingSettings"/>
<xs:enumeration value="calendar:IsOrganizer"/>
<xs:enumeration value="task:ActualWork"/>
<xs:enumeration value="task:AssignedTime"/>
<xs:enumeration value="task:BillingInformation"/>
<xs:enumeration value="task:ChangeCount"/>
<xs:enumeration value="task:Companies"/>
<xs:enumeration value="task:CompleteDate"/>
<xs:enumeration value="task:Contacts"/>
<xs:enumeration value="task:DelegationState"/>
<xs:enumeration value="task:Delegator"/>
<xs:enumeration value="task:DueDate"/>
<xs:enumeration value="task:IsAssignmentEditable"/>
<xs:enumeration value="task:IsComplete"/>
<xs:enumeration value="task:IsRecurring"/>
<xs:enumeration value="task:IsTeamTask"/>
<xs:enumeration value="task:Mileage"/>
<xs:enumeration value="task:Owner"/>
<xs:enumeration value="task:PercentComplete"/>
<xs:enumeration value="task:Recurrence"/>
<xs:enumeration value="task:StartDate"/>
<xs:enumeration value="task:Status"/>
<xs:enumeration value="task:StatusDescription"/>
<xs:enumeration value="task:TotalWork"/>
<xs:enumeration value="contacts:Alias"/>
<xs:enumeration value="contacts:AssistantName"/>
<xs:enumeration value="contacts:Birthday"/>
<xs:enumeration value="contacts:BusinessHomePage"/>
<xs:enumeration value="contacts:Children"/>
<xs:enumeration value="contacts:Companies"/>
<xs:enumeration value="contacts:CompanyName"/>
<xs:enumeration value="contacts:CompleteName"/>
<xs:enumeration value="contacts>ContactSource"/>
<xs:enumeration value="contacts:Culture"/>
<xs:enumeration value="contacts:Department"/>
<xs:enumeration value="contacts:DisplayName"/>
<xs:enumeration value="contacts:DirectoryId"/>
<xs:enumeration value="contacts:DirectReports"/>
<xs:enumeration value="contacts:EmailAddresses"/>
<xs:enumeration value="contacts:FileAs"/>
<xs:enumeration value="contacts:FileAsMapping"/>
<xs:enumeration value="contacts:Generation"/>
<xs:enumeration value="contacts:GivenName"/>
<xs:enumeration value="contacts:ImAddresses"/>
<xs:enumeration value="contacts:Initials"/>
```

```
<xs:enumeration value="contacts:JobTitle"/>
<xs:enumeration value="contacts:Manager"/>
<xs:enumeration value="contacts:ManagerMailbox"/>
<xs:enumeration value="contacts:MiddleName"/>
<xs:enumeration value="contacts:Mileage"/>
<xs:enumeration value="contacts:MSExchangeCertificate"/>
<xs:enumeration value="contacts:Nickname"/>
<xs:enumeration value="contacts:Notes"/>
<xs:enumeration value="contacts:OfficeLocation"/>
<xs:enumeration value="contacts:PhoneNumbers"/>
<xs:enumeration value="contacts:PhoneticFullName"/>
<xs:enumeration value="contacts:PhoneticFirstName"/>
<xs:enumeration value="contacts:PhoneticLastName"/>
<xs:enumeration value="contacts:Photo"/>
<xs:enumeration value="contacts:PhysicalAddresses"/>
<xs:enumeration value="contacts:PostalAddressIndex"/>
<xs:enumeration value="contacts:Profession"/>
<xs:enumeration value="contacts:SpouseName"/>
<xs:enumeration value="contacts:Surname"/>
<xs:enumeration value="contacts:WeddingAnniversary"/>
<xs:enumeration value="contacts:UserSMIMECertificate"/>
<xs:enumeration value="contacts:HasPicture"/>
<xs:enumeration value="distributionlist:Members"/>
<xs:enumeration value="postitem:PostedTime"/>
<xs:enumeration value="conversation:ConversationId"/>
<xs:enumeration value="conversation:ConversationTopic"/>
<xs:enumeration value="conversation:UniqueRecipients"/>
<xs:enumeration value="conversation:GlobalUniqueRecipients"/>
<xs:enumeration value="conversation:UniqueUnreadSenders"/>
<xs:enumeration value="conversation:GlobalUniqueUnreadSenders"/>
<xs:enumeration value="conversation:UniqueSenders"/>
<xs:enumeration value="conversation:GlobalUniqueSenders"/>
<xs:enumeration value="conversation:LastDeliveryTime"/>
<xs:enumeration value="conversation:GlobalLastDeliveryTime"/>
<xs:enumeration value="conversation:Categories"/>
<xs:enumeration value="conversation:GlobalCategories"/>
<xs:enumeration value="conversation:FlagStatus"/>
<xs:enumeration value="conversation:GlobalFlagStatus"/>
<xs:enumeration value="conversation:HasAttachments"/>
<xs:enumeration value="conversation:GlobalHasAttachments"/>
<xs:enumeration value="conversation:MessageCount"/>
<xs:enumeration value="conversation:GlobalMessageCount"/>
<xs:enumeration value="conversation:UnreadCount"/>
<xs:enumeration value="conversation:GlobalUnreadCount"/>
<xs:enumeration value="conversation:Size"/>
<xs:enumeration value="conversation:GlobalSize"/>
<xs:enumeration value="conversation:ItemClasses"/>
<xs:enumeration value="conversation:GlobalItemClasses"/>
<xs:enumeration value="conversation:Importance"/>
<xs:enumeration value="conversation:GlobalImportance"/>
<xs:enumeration value="conversation:ItemIds"/>
<xs:enumeration value="conversation:GlobalItemIds"/>
<xs:enumeration value="conversation:LastModifiedTime"/>
<xs:enumeration value="conversation:InstanceKey"/>
<xs:enumeration value="conversation:Preview"/>
<xs:enumeration value="conversation:NextPredictedAction"/>
<xs:enumeration value="conversation:GroupingAction"/>
<xs:enumeration value="conversation:IconIndex"/>
<xs:enumeration value="conversation:GlobalIconIndex"/>
```

```
<xs:enumeration value="conversation:DraftItemIds"/>
<xs:enumeration value="persona:PersonaId" />
<xs:enumeration value="persona:PersonaType" />
<xs:enumeration value="persona:GivenName" />
<xs:enumeration value="persona:CompanyName" />
<xs:enumeration value="persona:Surname" />
<xs:enumeration value="persona:DisplayName" />
<xs:enumeration value="persona:EmailAddress" />
<xs:enumeration value="persona:FileAs" />
<xs:enumeration value="persona:HomeCity" />
<xs:enumeration value="persona:CreationTime" />
<xs:enumeration value="persona:RelevanceScore" />
<xs:enumeration value="persona:WorkCity" />
<xs:enumeration value="persona:PersonaObjectStatus" />
<xs:enumeration value="persona:FileAsId" />
<xs:enumeration value="persona:DisplayNamePrefix" />
<xs:enumeration value="persona:YomiCompanyName" />
<xs:enumeration value="persona:YomiFirstName" />
<xs:enumeration value="persona:YomiLastName" />
<xs:enumeration value="persona:Title" />
<xs:enumeration value="persona:EmailAddresses" />
<xs:enumeration value="persona:PhoneNumber" />
<xs:enumeration value="persona:ImAddress" />
<xs:enumeration value="persona:ImAddresses" />
<xs:enumeration value="persona:ImAddresses2" />
<xs:enumeration value="persona:ImAddresses3" />
<xs:enumeration value="persona:FolderIds" />
<xs:enumeration value="persona:Attributions" />
<xs:enumeration value="persona:DisplayNames" />
<xs:enumeration value="persona:Initials" />
<xs:enumeration value="persona:FileAses" />
<xs:enumeration value="persona:FileAsIds" />
<xs:enumeration value="persona:DisplayNamePrefixes" />
<xs:enumeration value="persona:GivenNames" />
<xs:enumeration value="persona:MiddleNames" />
<xs:enumeration value="persona:Surnames" />
<xs:enumeration value="persona:Generations" />
<xs:enumeration value="persona:Nicknames" />
<xs:enumeration value="persona:YomiCompanyNames" />
<xs:enumeration value="persona:YomiFirstNames" />
<xs:enumeration value="persona:YomiLastNames" />
<xs:enumeration value="persona:BusinessPhoneNumbers" />
<xs:enumeration value="persona:BusinessPhoneNumbers2" />
<xs:enumeration value="persona:HomePhones" />
<xs:enumeration value="persona:HomePhones2" />
<xs:enumeration value="persona:MobilePhones" />
<xs:enumeration value="persona:MobilePhones2" />
<xs:enumeration value="persona:AssistantPhoneNumbers" />
<xs:enumeration value="persona:CallbackPhones" />
<xs:enumeration value="persona:CarPhones" />
<xs:enumeration value="persona:HomeFaxes" />
<xs:enumeration value="persona:OrganizationMainPhones" />
<xs:enumeration value="persona:OtherFaxes" />
<xs:enumeration value="persona:OtherTelephones" />
<xs:enumeration value="persona:OtherPhones2" />
<xs:enumeration value="persona:Paggers" />
<xs:enumeration value="persona:RadioPhones" />
<xs:enumeration value="persona:TelexNumbers" />
<xs:enumeration value="persona:WorkFaxes" />
```

```

<xs:enumeration value ="persona:Emails1" />
<xs:enumeration value ="persona:Emails2" />
<xs:enumeration value ="persona:Emails3" />
<xs:enumeration value ="persona:BusinessHomePages" />
<xs:enumeration value ="persona:School" />
<xs:enumeration value ="persona:PersonalHomePages" />
<xs:enumeration value ="persona:OfficeLocations" />
<xs:enumeration value ="persona:BusinessAddresses" />
<xs:enumeration value ="persona:HomeAddresses" />
<xs:enumeration value ="persona:OtherAddresses" />
<xs:enumeration value ="persona:Titles" />
<xs:enumeration value ="persona:Departments" />
<xs:enumeration value ="persona:CompanyNames" />
<xs:enumeration value ="persona:Managers" />
<xs:enumeration value ="persona:AssistantNames" />
<xs:enumeration value ="persona:Professions" />
<xs:enumeration value ="persona:SpouseNames" />
<xs:enumeration value ="persona:Hobbies" />
<xs:enumeration value ="persona:WeddingAnniversaries" />
<xs:enumeration value ="persona:Birthdays" />
<xs:enumeration value ="persona:Children" />
<xs:enumeration value ="persona:Locations" />
<xs:enumeration value ="persona:ExtendedProperties" />
<xs:enumeration value ="persona:PostalAddress" />
<xs:enumeration value ="persona:Bodies" />
</xs:restriction>
</xs:simpleType>

```

The values that are defined by the **UnindexedFieldURIType** simple type are listed in the following table.

Value	Description
Folder:FolderId	Specifies the <b>FolderId</b> property.
Folder:ParentFolderId	Specifies the <b>ParentFolderId</b> property.
Folder:DisplayName	Specifies the <b>DisplayName</b> property.
Folder:UnreadCount	Specifies the <b>UnreadCount</b> property.
Folder:TotalCount	Specifies the <b>TotalCount</b> property.
Folder:ChildFolderCount	Specifies the <b>ChildFolderCount</b> property.
Folder:FolderClass	Specifies the <b>FolderClass</b> property.
Folder:SearchParameters	Specifies the <b>SearchParameters</b> property.
Folder:ManagedFolderInformation	Specifies the <b>ManagedFolderInformation</b> property.
Folder:PermissionSet	Specifies the <b>PermissionSet</b> property.
Folder:EffectiveRights	Specifies the <b>EffectiveRights</b> property.
Folder:SharingEffectiveRights	Specifies the <b>SharingEffectiveRights</b> property.



Value	Description
Folder:DistinguishedFolderId	Specifies the <b>DistinguishedFolderId</b> property. <a href="#">.&lt;96&gt;</a>
Folder:PolicyTag	Specifies the <b>PolicyTag</b> property. <a href="#">.&lt;97&gt;</a>
Folder:ArchiveTag	Specifies the <b>ArchiveTag</b> property. <a href="#">.&lt;98&gt;</a>
Item:ItemId	Specifies the <b>ItemId</b> property.
Item:ParentFolderId	Specifies the <b>ParentFolderId</b> property.
Item:ItemClass	Specifies the <b>ItemClass</b> property.
Item:MimeContent	Specifies the <b>MimeContent</b> property.
Item:Attachments	Specifies the <b>Attachments</b> property.
Item:Subject	Specifies the <b>Subject</b> property.
Item:DateTimeReceived	Specifies the <b>DateTimeReceived</b> property.
Item:Size	Specifies the <b>Size</b> property.
Item:Categories	Specifies the <b>Categories</b> property.
Item:HasAttachments	Specifies the <b>HasAttachments</b> property.
Item:Importance	Specifies the <b>Importance</b> property.
Item:InReplyTo	Specifies the <b>InReplyTo</b> property.
Item:InternetMessageHeaders	Specifies the <b>InternetMessageHeaders</b> property.
Item:IsAssociated	Specifies the <b>IsAssociated</b> property.
Item:IsDraft	Specifies the <b>IsDraft</b> property.
Item:IsFromMe	Specifies the <b>IsFromMe</b> property.
Item:IsResend	Specifies the <b>IsResend</b> property.
Item:IsSubmitted	Specifies the <b>IsSubmitted</b> property.
Item:IsUnmodified	Specifies the <b>IsUnmodified</b> property.
Item:DateTimeSent	Specifies the <b>DateTimeSent</b> property.
Item:DateTimeCreated	Specifies the <b>DateTimeCreated</b> property.
Item:Body	Specifies the <b>Body</b> property.
Item:ResponseObjects	Specifies the <b>ResponseObjects</b> property.
Item:Sensitivity	Specifies the <b>Sensitivity</b> property.
Item:ReminderDueBy	Specifies the <b>ReminderDueBy</b> property.
Item:ReminderIsSet	Specifies the <b>ReminderIsSet</b> property.
Item:ReminderNextTime	Specifies the <b>ReminderNextTime</b> property. <a href="#">.&lt;99&gt;</a>

Value	Description
Item:ReminderMinutesBeforeStart	Specifies the <b>ReminderMinutesBeforeStart</b> property.
Item:DisplayTo	Specifies the <b>DisplayTo</b> property.
Item:DisplayCc	Specifies the <b>DisplayCc</b> property.
Item:Culture	Specifies the <b>Culture</b> property.
Item:EffectiveRights	Specifies the <b>EffectiveRights</b> property.
Item:LastModifiedName	Specifies the <b>LastModifiedName</b> property.
Item:LastModifiedTime	Specifies the <b>LastModifiedTime</b> property.
Item:ConversationId	Specifies the <b>ConversationId</b> property.
Item:UniqueBody	Specifies the <b>UniqueBody</b> property.
Item:Flag	Specifies the <b>Flag</b> property. <100>
Item:StoreEntryId	Specifies the <b>StoreEntryId</b> property.
Item:InstanceKey	Specifies the <b>InstanceKey</b> property. <101>
Item:NormalizedBody	Specifies the <b>NormalizedBody</b> property. <102>
item:EntityExtractionResult	Specifies the <b>EntityExtractionResult</b> property. <103>
item:PolicyTag	Specifies the <b>PolicyTag</b> property. <104>
item:ArchiveTag	Specifies the <b>ArchiveTag</b> property. <105>
item:RetentionDate	Specifies the <b>RetentionDate</b> property. <106>
item:Preview	Specifies the <b>Preview</b> property. <107>
item:NextPredictedAction	Specifies the <b>NextPredictedAction</b> property. <108>
item:GroupingAction	Specifies the <b>GroupingAction</b> property. <109>
item:RightsManagementLicenseData	Specifies the <b>RightsManagementLicenseData</b> property. <110>
item:BlockStatus	Specifies the <b>BlockStatus</b> property. <111>
item:HasBlockedImages	Specifies whether external images were blocked.
item:WebClientReadFormQueryString	Specifies the <b>WebClientReadFormQueryString</b> property.
item:WebClientEditFormQueryString	Specifies the <b>WebClientEditFormQueryString</b> property.
item:TextBody	Specifies the <b>TextBody</b> property. <112>
item:IconIndex	Specifies the icon index property. <113>
message:ConversationIndex	Specifies the <b>ConversationIndex</b> property. This property is also valid for postitem.
message:ConversationTopic	Specifies the <b>ConversationTopic</b> property. This property is

Value	Description
	also valid for postitem.
message:InternetMessageId	Specifies the <b>InternetMessageId</b> property. This property is also valid for postitem.
message:IsRead	Specifies the <b>IsRead</b> property.
message:IsResponseRequested	Specifies the <b>IsResponseRequested</b> property.
message:IsReadReceiptRequested	Specifies the <b>IsReadReceiptRequested</b> property.
message:IsDeliveryReceiptRequested	Specifies the <b>IsDeliveryReceiptRequested</b> property.
message:ReceivedBy	Specifies the <b>ReceivedBy</b> property.
message:ReceivedRepresenting	Specifies the <b>ReceivedRepresenting</b> property.
message:References	Specifies the <b>References</b> property. This property is also valid for postitem.
message:ReplyTo	Specifies the <b>ReplyTo</b> property.
message:From	Specifies the <b>From</b> property. This property is also valid for postitem.
message:Sender	Specifies the <b>Sender</b> property. This property is also valid for postitem.
message:ToRecipients	Specifies the <b>ToRecipients</b> property.
message:CcRecipients	Specifies the <b>CcRecipients</b> property.
message:BccRecipients	Specifies the <b>BccRecipients</b> property.
meeting:AssociatedCalendarItemId	Specifies the <b>AssociatedCalendarItemId</b> property.
meeting:IsDelegated	Specifies the <b>IsDelegated</b> property.
meeting:IsOutOfDate	Specifies the <b>IsOutOfDate</b> property.
meeting:HasBeenProcessed	Specifies the <b>HasBeenProcessed</b> property.
meeting:ResponseType	Specifies the <b>ResponseType</b> property.
meeting:ProposedStart	Specifies the <b>ProposedStart</b> property. <a href="#">&lt;114&gt;</a>
meeting:ProposedEnd	Specifies the <b>ProposedEnd</b> property. <a href="#">&lt;115&gt;</a>
meetingRequest:MeetingRequestType	Specifies the <b>MeetingRequestType</b> property.
meetingRequest:IntendedFreeBusyStatus	Specifies the <b>IntendedFreeBusyStatus</b> property.
meetingRequest:ChangeHighlights	Specifies the <b>ChangeHighlight</b> property. <a href="#">&lt;116&gt;</a>
calendar:Start	Specifies the <b>Start</b> property.
calendar:End	Specifies the <b>End</b> property.
calendar:OriginalStart	Specifies the <b>OriginalStart</b> property.

Value	Description
calendar:StartWallClock	Specifies the <b>StartWallClock</b> property. <117>
calendar:EndWallClock	Specifies the <b>EndWallClock</b> property. <118>
calendar:StartTimeZoneId	Specifies the <b>StartTimeZone</b> property. <119>
calendar:EndTimeZoneId	Specifies the <b>EndTimeZone</b> property. <120>
calendar:IsAllDayEvent	Specifies the <b>IsAllDayEvent</b> property.
calendar:LegacyFreeBusyStatus	Specifies the <b>LegacyFreeBusyStatus</b> property.
calendar:Location	Specifies the <b>Location</b> property.
calendar:EnhancedLocation	Specifies the <b>EnhancedLocation</b> property. <121>
calendar:When	Specifies the <b>When</b> property.
calendar:IsMeeting	Specifies the <b>IsMeeting</b> property.
calendar:IsCancelled	Specifies the <b>IsCancelled</b> property.
calendar:IsRecurring	Specifies the <b>IsRecurring</b> property.
calendar:MeetingRequestWasSent	Specifies the <b>MeetingRequestWasSent</b> property.
calendar:IsResponseRequested	Specifies the <b>IsResponseRequested</b> property.
calendar:CalendarItemType	Specifies the <b>CalendarItemType</b> property.
calendar:MyResponseType	Specifies the <b>MyResponseType</b> property.
calendar:Organizer	Specifies the <b>Organizer</b> property.
calendar:RequiredAttendees	Specifies the <b>RequiredAttendees</b> property.
calendar:OptionalAttendees	Specifies the <b>OptionalAttendees</b> property.
calendar:Resources	Specifies the <b>Resources</b> property.
calendar:ConflictingMeetingCount	Specifies the <b>ConflictingMeetingCount</b> property.
calendar:AdjacentMeetingCount	Specifies the <b>AdjacentMeetingCount</b> property.
calendar:ConflictingMeetings	Specifies the <b>ConflictingMeetings</b> property.
calendar:AdjacentMeetings	Specifies the <b>AdjacentMeetings</b> property.
calendar:Duration	Specifies the <b>Duration</b> property.
calendar:TimeZone	Specifies the <b>TimeZone</b> property.
calendar:AppointmentReplyTime	Specifies the <b>AppointmentReplyTime</b> property.
calendar:AppointmentSequenceNumber	Specifies the <b>AppointmentSequenceNumber</b> property.
calendar:AppointmentState	Specifies the <b>AppointmentState</b> property.
calendar:Recurrence	Specifies the <b>Recurrence</b> property.

Value	Description
calendar:FirstOccurrence	Specifies the <b>FirstOccurrence</b> property.
calendar>LastOccurrence	Specifies the <b>LastOccurrence</b> property.
calendar:ModifiedOccurrences	Specifies the <b>ModifiedOccurrences</b> property.
calendar:DeletedOccurrences	Specifies the <b>DeletedOccurrences</b> property.
calendar:MeetingTimeZone	Specifies the <b>MeetingTimeZone</b> property.
calendar:ConferenceType	Specifies the <b>ConferenceType</b> property.
calendar:AllowNewTimeProposal	Specifies the <b>AllowNewTimeProposal</b> property.
calendar:IsOnlineMeeting	Specifies the <b>IsOnlineMeeting</b> property.
calendar:MeetingWorkspaceUrl	Specifies the <b>MeetingWorkspaceUrl</b> property.
calendar:NetShowUrl	Specifies the <b>NetShowUrl</b> property.
calendar:UID	Specifies the <b>UID</b> property.
calendar:RecurrenceId	Specifies the <b>RecurrenceId</b> property.
calendar:DateTimeStamp	Specifies the <b>DateTimeStamp</b> property.
calendar:StartTimeZone	Specifies the <b>StartTimeZone</b> property.
calendar:EndTimeZone	Specifies the <b>EndTimeZone</b> property.
calendar:JoinOnlineMeetingUrl	Specifies the <b>JoinOnlineMeetingUrl</b> property. <122>
calendar:OnlineMeetingSettings	Specifies the <b>OnlineMeetingSettings</b> property. <123>
calendar:IsOrganizer	Specifies the <b>IsOrganizer</b> property. <124>
task:ActualWork	Specifies the <b>ActualWork</b> property.
task:AssignedTime	Specifies the <b>AssignedTime</b> property.
task:BillingInformation	Specifies the <b>BillingInformation</b> property.
task:ChangeCount	Specifies the <b>ChangeCount</b> property.
task:Companies	Specifies the <b>Companies</b> property.
task:CompleteDate	Specifies the <b>CompleteDate</b> property.
task:Contacts	Specifies the <b>Contacts</b> property.
task:DelegationState	Specifies the <b>DelegationState</b> property.
task:Delegator	Specifies the <b>Delegator</b> property.
task:DueDate	Specifies the <b>DueDate</b> property.
task:IsAssignmentEditable	Specifies the <b>IsAssignmentEditable</b> property.
task:IsComplete	Specifies the <b>IsComplete</b> property.

<b>Value</b>	<b>Description</b>
task:IsRecurring	Specifies the <b>IsRecurring</b> property.
task:IsTeamTask	Specifies the <b>IsTeamTask</b> property.
task:Mileage	Specifies the <b>Mileage</b> property.
task:Owner	Specifies the <b>Owner</b> property.
task:PercentComplete	Specifies the <b>PercentComplete</b> property.
task:Recurrence	Specifies the <b>Recurrence</b> property.
task:StartDate	Specifies the <b>StartDate</b> property.
task>Status	Specifies the <b>Status</b> property.
task>StatusDescription	Specifies the <b>StatusDescription</b> property.
task:TotalWork	Specifies the <b>TotalWork</b> property.
contacts:Alias	Specifies the <b>Alias</b> property.
contacts:AssistantName	Specifies the <b>AssistantName</b> property.
contacts:Birthday	Specifies the <b>Birthday</b> property.
contacts:BusinessHomePage	Specifies the <b>BusinessHomePage</b> property.
contacts:Children	Specifies the <b>Children</b> property.
contacts:Companies	Specifies the <b>Companies</b> property.
contacts:CompanyName	Specifies the <b>CompanyName</b> property.
contacts:CompleteName	Specifies the <b>CompleteName</b> property.
contacts>ContactSource	Specifies the <b>ContactSource</b> property.
contacts:Culture	Specifies the <b>Culture</b> property.
contacts:Department	Specifies the <b>Department</b> property.
contacts:DisplayName	Specifies the <b>DisplayName</b> property.
contacts:DirectoryId	Specifies the <b>DirectoryId</b> property.
contacts:DirectReports	Specifies the <b>DirectReports</b> property.
contacts:EmailAddresses	Specifies the <b>EmailAddresses</b> property.
contacts:FileAs	Specifies the <b>FileAs</b> property.
contacts:FileAsMapping	Specifies the <b>FileAsMapping</b> property.
contacts:Generation	Specifies the <b>Generation</b> property.
contacts:GivenName	Specifies the <b>GivenName</b> property.
contacts:ImAddresses	Specifies the <b>ImAddresses</b> property.

<b>Value</b>	<b>Description</b>
contacts:Initials	Specifies the <b>Initials</b> property.
contacts:JobTitle	Specifies the <b>JobTitle</b> property.
contacts:Manager	Specifies the <b>Manager</b> property.
contacts:ManagerMailbox	Specifies the <b>ManagerMailbox</b> property.
contacts:MiddleName	Specifies the <b>MiddleName</b> property.
contacts:Mileage	Specifies the <b>Mileage</b> property.
contacts:MSExchangeCertificate	Specifies the <b>MSExchangeCertificate</b> property.
contacts:Nickname	Specifies the <b>Nickname</b> property.
contacts:Notes	Specifies the <b>Notes</b> property.
contacts:OfficeLocation	Specifies the <b>OfficeLocation</b> property.
contacts:PhoneNumbers	Specifies the <b>PhoneNumbers</b> property.
contacts:PhoneticFullName	Specifies the <b>PhoneticFullName</b> property.
contacts:PhoneticFirstName	Specifies the <b>PhoneticFirstName</b> property.
contacts:PhoneticLastName	Specifies the <b>PhoneticLastName</b> property.
contacts:Photo	Specifies the <b>Photo</b> property.
contacts:PhysicalAddresses	Specifies the <b>PhysicalAddresses</b> property.
contacts:PostalAddressIndex	Specifies the <b>PostalAddressIndex</b> property.
contacts:Profession	Specifies the <b>Profession</b> property.
contacts:SpouseName	Specifies the <b>SpouseName</b> property.
contacts:Surname	Specifies the <b>Surname</b> property.
contacts:WeddingAnniversary	Specifies the <b>WeddingAnniversary</b> property.
contacts:UserSMIMECertificate	Specifies the <b>UserSMIMECertificate</b> property.
contacts:HasPicture	Specifies whether a contact has a picture.
distributionlist:Members	Specifies the <b>Members</b> property.
postitem:PostedTime	Specifies the <b>PostedTime</b> property.
conversation:ConversationId	Specifies the <b>ConversationId</b> property.
conversation:ConversationTopic	Specifies the <b>ConversationTopic</b> property.
conversation:UniqueRecipients	Specifies the <b>UniqueRecipients</b> property.
conversation:GlobalUniqueRecipients	Specifies the <b>GlobalUniqueRecipients</b> property.
conversation:UniqueUnreadSenders	Specifies the <b>UniqueUnreadSenders</b> property.

Value	Description
conversation:GlobalUniqueUnreadSenders	Specifies the <b>GlobalUniqueUnreadSenders</b> property.
conversation:UniqueSenders	Specifies the <b>UniqueSenders</b> property.
conversation:GlobalUniqueSenders	Specifies the <b>GlobalUniqueSenders</b> property.
conversation:LastDeliveryTime	Specifies the <b>LastDeliveryTime</b> property.
conversation:GlobalLastDeliveryTime	Specifies the <b>GlobalLastDeliveryTime</b> property.
conversation:Categories	Specifies the <b>Categories</b> property.
conversation:GlobalCategories	Specifies the <b>GlobalCategories</b> property.
conversation:FlagStatus	Specifies the <b>FlagStatus</b> property.
conversation:GlobalFlagStatus	Specifies the <b>GlobalFlagStatus</b> property.
conversation:HasAttachments	Specifies the <b>HasAttachments</b> property.
conversation:GlobalHasAttachments	Specifies the <b>GlobalHasAttachments</b> property.
conversation:MessageCount	Specifies the <b>MessageCount</b> property.
conversation:GlobalMessageCount	Specifies the <b>GlobalMessageCount</b> property.
conversation:UnreadCount	Specifies the <b>UnreadCount</b> property.
conversation:GlobalUnreadCount	Specifies the <b>GlobalUnreadCount</b> property.
conversation:Size	Specifies the <b>Size</b> property.
conversation:GlobalSize	Specifies the <b>GlobalSize</b> property.
conversation:ItemClasses	Specifies the <b>ItemClasses</b> property.
conversation:GlobalItemClasses	Specifies the <b>GlobalItemClasses</b> property.
conversation:Importance	Specifies the <b>Importance</b> property.
conversation:GlobalImportance	Specifies the <b>GlobalImportance</b> property.
conversation:ItemIds	Specifies the <b>ItemIds</b> property.
conversation:GlobalItemIds	Specifies the <b>GlobalItemIds</b> property.
conversation:LastModifiedTime	Specifies the <b>LastModifiedTime</b> property. <125>
conversation:InstanceKey	Specifies the <b>InstanceKey</b> property. <126>
conversation:Preview	Specifies the <b>Preview</b> property. <127>
conversation:NextPredictedAction	Specifies the <b>NextPredictedAction</b> property. <128>
conversation:GroupingAction	Specifies the <b>GroupingAction</b> property. <129>
conversation:IconIndex	Specifies the <b>IconIndex</b> property. <130>
conversation:GlobalIconIndex	Specifies the <b>GlobalIconIndex</b> property. <131>



Value	Description
conversation:DraftItemIds	Specifies the <b>DraftItemIds</b> property. <132>
persona:PersonaType	Specifies the <b>PersonaType</b> property. <133>
persona:GivenName	Specifies the <b>GivenName</b> property. <134>
persona:CompanyName	Specifies the <b>CompanyName</b> property. <135>
persona:SurName	Specifies the <b>SurName</b> property. <136>
persona:PersonaId	Specifies the <b>DisplayName</b> property. <137>
persona:EmailAddress	Specifies the <b>EmailAddress</b> property. <138>
persona:FileAs	Specifies the <b>FileAs</b> property. <139>
persona:HomeCity	Specifies the <b>HomeCity</b> property. <140>
persona:CreationTime	Specifies the <b>CreationTime</b> property. <141>
persona:RelevanceScore	Specifies the <b>RelevanceScore</b> property. <142>
persona:WorkCity	Specifies the <b>WorkCity</b> property. <143>
persona:PersonaObjectStatus	Specifies the <b>PersonaObjectStatus</b> property. <144>
persona:FileAsId	Specifies the <b>FileAsId</b> property. <145>
persona:DisplayNamePrefix	Specifies the <b>DisplayNamePrefix</b> property. <146>
persona:YomiCompanyName	Specifies the <b>YomiCompanyName</b> property. <147>
persona:YomiFirstName	Specifies the <b>YomiFirstName</b> property. <148>
persona:YomiLastName	Specifies the <b>YomiLastName</b> property. <149>
persona:Title	Specifies the <b>Title</b> property. <150>
persona:EmailAddresses	Specifies the <b>EmailAddresses</b> property. <151>
persona:PhoneNumber	Specifies the <b>PhoneNumber</b> property. <152>
persona:ImAddress	Specifies the <b>ImAddress</b> property. <153>
persona:ImAddresses	Specifies the <b>ImAddresses</b> property. <154>
persona:ImAddresses2	Specifies the <b>ImAddresses2</b> property. <155>
persona:ImAddresses3	Specifies the <b>ImAddresses3</b> property. <156>
persona:FolderIds	Specifies the <b>FolderIds</b> property. <157>
persona:Attributions	Specifies the <b>Attributions</b> property. <158>
persona:DisplayNames	Specifies the <b>DisplayNames</b> property. <159>
persona:Initials	Specifies the <b>Initials</b> property. <160>
persona:FileAses	Specifies the <b>FileAses</b> property. <161>

Value	Description
persona:FileAsIds	Specifies the <b>FileAsIds</b> property. <a href="#">.&lt;162&gt;</a>
persona:DisplayNamePrefixes	Specifies the <b>DisplayNamePrefixes</b> property. <a href="#">.&lt;163&gt;</a>
persona:GivenNames	Specifies the <b>GivenNames</b> property. <a href="#">.&lt;164&gt;</a>
persona:MiddleNames	Specifies the <b>MiddleNames</b> property. <a href="#">.&lt;165&gt;</a>
persona:Surnames	Specifies the <b>Surnames</b> property. <a href="#">.&lt;166&gt;</a>
persona:Generations	Specifies the <b>Generations</b> property. <a href="#">.&lt;167&gt;</a>
persona:Nicknames	Specifies the <b>Nicknames</b> property. <a href="#">.&lt;168&gt;</a>
persona:YomiCompanyNames	Specifies the <b>YomiCompanyNames</b> property. <a href="#">.&lt;169&gt;</a>
persona:YomiFirstNames	Specifies the <b>YomiFirstNames</b> property. <a href="#">.&lt;170&gt;</a>
persona:YomiLastNames	Specifies the <b>YomiLastNames</b> property. <a href="#">.&lt;171&gt;</a>
persona:BusinessPhoneNumbers	Specifies the <b>BusinessPhoneNumbers</b> property. <a href="#">.&lt;172&gt;</a>
persona:BusinessPhoneNumbers2	Specifies the <b>BusinessPhoneNumbers2</b> property. <a href="#">.&lt;173&gt;</a>
persona:HomePhones	Specifies the <b>HomePhones</b> property. <a href="#">.&lt;174&gt;</a>
persona:HomePhones2	Specifies the <b>HomePhones2</b> property. <a href="#">.&lt;175&gt;</a>
persona:MobilePhones	Specifies the <b>MobilePhones</b> property. <a href="#">.&lt;176&gt;</a>
persona:MobilePhones2	Specifies the <b>MobilePhones2</b> property. <a href="#">.&lt;177&gt;</a>
persona:AssistantPhoneNumbers	Specifies the <b>AssistantPhoneNumbers</b> property. <a href="#">.&lt;178&gt;</a>
persona:CallbackPhones	Specifies the <b>CallbackPhones</b> property. <a href="#">.&lt;179&gt;</a>
persona:CarPhones	Specifies the <b>CarPhones</b> property. <a href="#">.&lt;180&gt;</a>
persona:HomeFaxes	Specifies the <b>HomeFaxes</b> property. <a href="#">.&lt;181&gt;</a>
persona:OrganizationMainPhones	Specifies the <b>OrganizationMainPhones</b> property. <a href="#">.&lt;182&gt;</a>
persona:OtherFaxes	Specifies the <b>OtherFaxes</b> property. <a href="#">.&lt;183&gt;</a>
persona:OtherTelephones	Specifies the <b>OtherTelephones</b> property. <a href="#">.&lt;184&gt;</a>
persona:OtherPhones2	Specifies the <b>OtherPhones2</b> property. <a href="#">.&lt;185&gt;</a>
persona:Paggers	Specifies the <b>Paggers</b> property. <a href="#">.&lt;186&gt;</a>
persona:RadioPhones	Specifies the <b>RadioPhones</b> property. <a href="#">.&lt;187&gt;</a>
persona:TelexNumbers	Specifies the <b>TelexNumbers</b> property. <a href="#">.&lt;188&gt;</a>
persona:WorkFaxes	Specifies the <b>WorkFaxes</b> property. <a href="#">.&lt;189&gt;</a>
persona:Emails1	Specifies the <b>Emails1</b> property. <a href="#">.&lt;190&gt;</a>
persona:Emails2	Specifies the <b>Emails2</b> property. <a href="#">.&lt;191&gt;</a>

Value	Description
persona:Emails3	Specifies the <b>Emails3</b> property. <a href="#">&lt;192&gt;</a>
persona:BusinessHomePages	Specifies the <b>BusinessHomePages</b> property. <a href="#">&lt;193&gt;</a>
persona:School	Specifies the <b>School</b> property. <a href="#">&lt;194&gt;</a>
persona:PersonalHomePages	Specifies the <b>PersonalHomePages</b> property. <a href="#">&lt;195&gt;</a>
persona:OfficeLocations	Specifies the <b>OfficeLocations</b> property. <a href="#">&lt;196&gt;</a>
persona:BusinessAddresses	Specifies the <b>BusinessAddresses</b> property. <a href="#">&lt;197&gt;</a>
persona:HomeAddresses	Specifies the <b>HomeAddresses</b> property. <a href="#">&lt;198&gt;</a>
persona:OtherAddresses	Specifies the <b>OtherAddresses</b> property. <a href="#">&lt;199&gt;</a>
persona:Titles	Specifies the <b>Titles</b> property. <a href="#">&lt;200&gt;</a>
persona:Departments	Specifies the <b>Departments</b> property. <a href="#">&lt;201&gt;</a>
persona:CompanyNames	Specifies the <b>CompanyNames</b> property. <a href="#">&lt;202&gt;</a>
persona:Managers	Specifies the <b>Managers</b> property. <a href="#">&lt;203&gt;</a>
persona:AssistantNames	Specifies the <b>AssistantNames</b> property. <a href="#">&lt;204&gt;</a>
persona:Professions	Specifies the <b>Professions</b> property. <a href="#">&lt;205&gt;</a>
persona:SpouseNames	Specifies the <b>SpouseNames</b> property. <a href="#">&lt;206&gt;</a>
persona:Hobbies	Specifies the <b>Hobbies</b> property. <a href="#">&lt;207&gt;</a>
persona:WeddingAnniversaries	Specifies the <b>WeddingAnniversaries</b> property. <a href="#">&lt;208&gt;</a>
persona:Birthdays	Specifies the <b>Birthdays</b> property. <a href="#">&lt;209&gt;</a>
persona:Children	Specifies the <b>Children</b> property. <a href="#">&lt;210&gt;</a>
persona:Locations	Specifies the <b>Locations</b> property. <a href="#">&lt;211&gt;</a>
persona:ExtendedProperties	Specifies the <b>ExtendedProperties</b> property. <a href="#">&lt;212&gt;</a>
persona:PostalAddress	Specifies the <b>PostalAddress</b> property. <a href="#">&lt;213&gt;</a>
persona:Bodies	Specifies the <b>Bodies</b> property. <a href="#">&lt;214&gt;</a>

## 2.2.4 Complex Types

### 2.2.4.1 t:AbsoluteMonthlyRecurrencePatternType Complex Type

The **AbsoluteMonthlyRecurrencePatternType** complex type specifies a monthly recurrence pattern.

```
<xs:complexType name="AbsoluteMonthlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:IntervalRecurrencePatternBaseType"
```

```

    >
    <xs:sequence>
      <xs:element name="DayOfMonth"
        type="xs:int"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **AbsoluteMonthlyRecurrencePatternType** complex type.

Element name	Type	Description
<b>DayOfMonth</b>	<b>xs:int</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the day of the month on which a recurring item occurs. This property <b>MUST</b> be present.

#### 2.2.4.2 t:AbsoluteYearlyRecurrencePatternType Complex Type

The **AbsoluteYearlyRecurrencePatternType** complex type specifies a yearly recurrence pattern.

```

<xs:complexType name="AbsoluteYearlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrencePatternBaseType"
    >
      <xs:sequence>
        <xs:element name="DayOfMonth"
          type="xs:int"
        />
        <xs:element name="Month"
          type="t:MonthNamesType"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **AbsoluteYearlyRecurrencePatternType** complex type.

Element name	Type	Description
<b>DayOfMonth</b>	<b>xs:int</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the day of the month on which a yearly recurring item occurs. This property <b>MUST</b> be present.
<b>Month</b>	<b>t:MonthNamesType</b> (section <a href="#">2.2.3.19</a> )	Specifies the month in which a yearly recurring item occurs. This property <b>MUST</b> be present.

### 2.2.4.3 t:AcceptSharingInvitationType Complex Type

The **AcceptSharingInvitationType** complex type specifies a response object that is used to respond to a sharing invitation request.

```
<xs:complexType name="AcceptSharingInvitationType">
  <xs:complexContent>
    <xs:extension
      base="t:ReferenceItemResponseType"
    />
  </xs:complexContent>
</xs:complexType>
```

### 2.2.4.4 t:ArrayOfCalendarPermissionsType Complex Type

The **ArrayOfCalendarPermissionsType** complex type specifies an array of calendar permissions for a folder.

```
<xs:complexType name="ArrayOfCalendarPermissionsType">
  <xs:choice
    maxOccurs="unbounded"
    minOccurs="0"
  >
    <xs:element name="CalendarPermission"
      type="t:CalendarPermissionType"
    />
  </xs:choice>
</xs:complexType>
```

The following table lists the child elements of the **ArrayOfCalendarPermissionsType** complex type.

Element name	Type	Description
<b>CalendarPermission</b>	<b>t:CalendarPermissionType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.6)	Specifies the access that a delegate has to a calendar folder. This element <b>MUST</b> exist if calendar permissions are set on a calendar folder.

### 2.2.4.5 t:ArrayOfEmailAddressesType Complex Type

The **ArrayOfEmailAddressesType** complex type specifies a list of email addresses in the **GetRoomLists** operation (as specified in [\[MS-OXWSGTRM\]](#) section 3.1.4.1) and **GetMessageTrackingReport** operation (as specified in [\[MS-OXWSMTRK\]](#) section 3.1.4.2) responses.

```
<xs:complexType name="ArrayOfEmailAddressesType">
  <xs:sequence>
    <xs:element name="Address"
      type="t:EmailAddressType"
      maxOccurs="unbounded"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>
```

```

    />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **ArrayOfEmailAddressesType** complex type.

Element name	Type	Description
<b>Address</b>	<b>t:EmailAddressType</b> (section <a href="#">2.2.4.27</a> )	Specifies a single email address.

#### 2.2.4.6 t:ArrayOfHighlightTermsType

The **ArrayOfHighlightTermsType** complex type specifies an array of highlight terms. [<215>](#)

```

<xs:complexType name="ArrayOfHighlightTermsType">
  <xs:sequence>
    <xs:element name="Term" type="t:HighlightTermType" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child element of the **ArrayOfHighlightTermsType** complex type.

Name	Type	Description
<b>Term</b>	▪ <b>t:HighlightTermType</b> (section <a href="#">2.2.4.34</a> )	Specifies a single highlighted term.

#### 2.2.4.7 t:ArrayOfPermissionsType Complex Type

The **ArrayOfPermissionsType** complex type specifies a collection of permissions for a folder.

```

<xs:complexType name="ArrayOfPermissionsType">
  <xs:choice
    minOccurs="0"
    maxOccurs="unbounded"
  >
    <xs:element name="Permission"
      type="t:PermissionType"
    />
  </xs:choice>
</xs:complexType>

```

The following table lists the child elements of the **ArrayOfPermissionsType** complex type.

Element name	Type	Description
<b>Permission</b>	<b>t:PermissionType</b> ( <a href="#">[MS-OXWSFOLD]</a> section 2.2.4.13)	Specifies a single access permission that a delegate has to a folder. This element can occur zero or more

Element name	Type	Description
		times.

#### 2.2.4.8 t:ArrayOfRealItemsType Complex Type

The **ArrayOfRealItemsType** complex type specifies an array of items that are returned by search and item operations. This complex type can contain zero or more elements that represent items.

```
<xs:complexType name="ArrayOfRealItemsType">
  <xs:sequence>
    <xs:choice
      minOccurs="0"
      maxOccurs="unbounded"
    >
      <xs:element name="Item"
        type="t:ItemType"
      />
      <xs:element name="Message"
        type="t:MessageType"
      />
      <xs:element name="CalendarItem"
        type="t:CalendarItemType"
      />
      <xs:element name="Contact"
        type="t:ContactItemType"
      />
      <xs:element name="DistributionList"
        type="t:DistributionListType"
      />
      <xs:element name="MeetingMessage"
        type="t:MeetingMessageType"
      />
      <xs:element name="MeetingRequest"
        type="t:MeetingRequestMessageType"
      />
      <xs:element name="MeetingResponse"
        type="t:MeetingResponseMessageType"
      />
      <xs:element name="MeetingCancellation"
        type="t:MeetingCancellationMessageType"
      />
      <xs:element name="Task"
        type="t:TaskType"
      />
      <xs:element name="PostItem"
        type="t:PostItemType"
      />
    </xs:choice>
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **ArrayOfRealItemsType** complex type.

Element name	Type	Description
<b>Item</b>	<b>t:ItemType</b> ([MS-OXWSCORE] section 2.2.4.8)	This element MUST NOT be used in response messages. All items of type <b>t:ItemType</b> MUST be returned as a <b>t:MessageType</b> type.
<b>Message</b>	<b>t:MessageType</b> ([MS-OXWSMSG] section 2.2.4.1)	Specifies a message item or other item that is not represented by the <b>CalendarItem</b> , <b>Contact</b> , <b>DistributionList</b> , <b>MeetingMessage</b> , <b>MeetingRequest</b> , <b>MeetingResponse</b> , <b>MeetingCancellation</b> , <b>Task</b> , or <b>PostItem</b> element.
<b>CalendarItem</b>	<b>t:CalendarItemType</b> ([MS-OXWSMTGS] section 2.2.4.4)	Specifies a calendar item.
<b>Contact</b>	<b>t:ContactItemType</b> ([MS-OXWSCONT] section 2.2.4.2)	Specifies a contact item.
<b>DistributionList</b>	<b>t:DistributionListType</b> ([MS-OXWSDLIST] section 2.2.4.3)	Specifies a distribution list item.
<b>MeetingMessage</b>	<b>t:MeetingMessageType</b> ([MS-OXWSMTGS] section 2.2.4.12)	Specifies a meeting message item.
<b>MeetingRequest</b>	<b>t:MeetingRequestMessageType</b> ([MS-OXWSMTGS] section 2.2.4.13)	Specifies a meeting request message item.
<b>MeetingResponse</b>	<b>t:MeetingResponseMessageType</b> ([MS-OXWSMTGS] section 2.2.4.14)	Specifies a meeting response message item.
<b>MeetingCancellation</b>	<b>t:MeetingCancellationMessageType</b> ([MS-OXWSMTGS] section 2.2.4.11)	Specifies a meeting cancellation message item.
<b>Task</b>	<b>t:TaskType</b> ([MS-OXWSTASK] section 2.2.4.3)	Specifies a task item.
<b>PostItem</b>	<b>t:PostItemType</b> ([MS-OXWSPOST] section 2.2.4.1)	Specifies a post item.

### 2.2.4.9 t:ArrayOfRecipientsType Complex Type

The **ArrayOfRecipientsType** complex type specifies an array of recipients of an item.

```
<xs:complexType name="ArrayOfRecipientsType">
  <xs:choice
    maxOccurs="unbounded"
    minOccurs="0"
  >
    <xs:element name="Mailbox"
      type="t:EmailAddressType"
    />
  </xs:choice>
</xs:complexType>
```



The following table lists the child elements of the **ArrayOfRecipientsType** complex type.

Element name	Type	Description
<b>Mailbox</b>	<b>t:EmailAddressType</b> (section <a href="#">2.2.4.27</a> )	Specifies a single item recipient by e-mail address.

### 2.2.4.10 m:ArrayOfResponseMessagesType Complex Type

The **ArrayOfResponseMessagesType** complex type specifies an array of response messages.

```
<xs:complexType name="ArrayOfResponseMessagesType">
  <xs:choice
    maxOccurs="unbounded"
  >
    <xs:element name="CreateItemResponseMessage"
      type="m:ItemInfoResponseMessageType"
    />
    <xs:element name="DeleteItemResponseMessage"
      type="m:ResponseMessageType"
    />
    <xs:element name="GetItemResponseMessage"
      type="m:ItemInfoResponseMessageType"
    />
    <xs:element name="UpdateItemResponseMessage"
      type="m:UpdateItemResponseMessageType"
    />
    <xs:element name="UpdateItemInRecoverableItemsResponseMessage"
      type="m:UpdateItemInRecoverableItemsResponseMessageType"/>
    <xs:element name="SendItemResponseMessage"
      type="m:ResponseMessageType"
    />
    <xs:element name="DeleteFolderResponseMessage"
      type="m:ResponseMessageType"
    />
    <xs:element name="EmptyFolderResponseMessage"
      type="m:ResponseMessageType"
    />
    <xs:element name="CreateFolderResponseMessage"
      type="m:FolderInfoResponseMessageType"
    />
    <xs:element name="GetFolderResponseMessage"
      type="m:FolderInfoResponseMessageType"
    />
    <xs:element name="FindFolderResponseMessage"
      type="m:FindFolderResponseMessageType"
    />
    <xs:element name="UpdateFolderResponseMessage"
      type="m:FolderInfoResponseMessageType"
    />
    <xs:element name="MoveFolderResponseMessage"
      type="m:FolderInfoResponseMessageType"
    />
    <xs:element name="CopyFolderResponseMessage"
      type="m:FolderInfoResponseMessageType"
    />
    <xs:element name="CreateFolderPathResponseMessage"
```

```

    type="m:FolderInfoResponseMessageType"
  />
<xs:element name="CreateAttachmentResponseMessage"
  type="m:AttachmentInfoResponseMessageType"
  />
<xs:element name="DeleteAttachmentResponseMessage"
  type="m>DeleteAttachmentResponseMessageType"
  />
<xs:element name="GetAttachmentResponseMessage"
  type="m:AttachmentInfoResponseMessageType"
  />
<xs:element name="UploadItemsResponseMessage"
  type="m:UploadItemsResponseMessageType"
  />
<xs:element name="ExportItemsResponseMessage"
  type="m:ExportItemsResponseMessageType"
  />
<xs:element name="MarkAllItemsAsReadResponseMessage"
  type="m:ResponseMessageType" />
<xs:element name="GetClientAccessTokenResponseMessage"
  type="m:GetClientAccessTokenResponseMessageType" />
<xs:element name="GetAppManifestsResponseMessage" type="m:ResponseMessageType" />
<xs:element name="GetClientExtensionResponseMessage"
  type="m:ResponseMessageType" />
<xs:element name="SetClientExtensionResponseMessage"
  type="m:ResponseMessageType" />

<xs:element name="FindItemResponseMessage"
  type="m:FindItemResponseMessageType"
  />
<xs:element name="MoveItemResponseMessage"
  type="m:ItemInfoResponseMessageType"
  />
<xs:element name="ArchiveItemResponseMessage" type="m:ItemInfoResponseMessageType" />
<xs:element name="CopyItemResponseMessage"
  type="m:ItemInfoResponseMessageType"
  />
<xs:element name="ResolveNamesResponseMessage"
  type="m:ResolveNamesResponseMessageType"
  />
<xs:element name="ExpandDLResponseMessage"
  type="m:ExpandDLResponseMessageType"
  />
<xs:element name="GetServerTimeZonesResponseMessage"
  type="m:GetServerTimeZonesResponseMessageType"
  />
<xs:element name="GetEventsResponseMessage"
  type="m:GetEventsResponseMessageType"
  />
<xs:element name="GetStreamingEventsResponseMessage"
  type="m:GetStreamingEventsResponseMessageType"
  />
<xs:element name="SubscribeResponseMessage"
  type="m:SubscribeResponseMessageType"
  />
<xs:element name="UnsubscribeResponseMessage"
  type="m:ResponseMessageType"
  />
<xs:element name="SendNotificationResponseMessage"

```

```

    type="m:SendNotificationResponseMessageType"
  />
<xs:element name="SyncFolderHierarchyResponseMessage"
  type="m:SyncFolderHierarchyResponseMessageType"
  />
<xs:element name="SyncFolderItemsResponseMessage"
  type="m:SyncFolderItemsResponseMessageType"
  />
<xs:element name="CreateManagedFolderResponseMessage"
  type="m:FolderInfoResponseMessageType"
  />
<xs:element name="ConvertIdResponseMessage"
  type="m:ConvertIdResponseMessageType"
  />
<xs:element name="GetSharingMetadataResponseMessage"
  type="m:GetSharingMetadataResponseMessageType"
  />
<xs:element name="RefreshSharingFolderResponseMessage"
  type="m:RefreshSharingFolderResponseMessageType"
  />
<xs:element name="GetSharingFolderResponseMessage"
  type="m:GetSharingFolderResponseMessageType"
  />
<xs:element name="CreateUserConfigurationResponseMessage"
  type="m:ResponseMessageType"
  />
<xs:element name="DeleteUserConfigurationResponseMessage"
  type="m:ResponseMessageType"
  />
<xs:element name="GetUserConfigurationResponseMessage"
  type="m:GetUserConfigurationResponseMessageType"
  />
<xs:element name="UpdateUserConfigurationResponseMessage"
  type="m:ResponseMessageType"
  />
<xs:element name="GetRoomListsResponse"
  type="m:GetRoomListsResponseMessageType"
  />
<xs:element name="GetRoomsResponse"
  type="m:GetRoomsResponseMessageType"
  />
  <xs:element name="GetRemindersResponse"
    type="m:GetRemindersResponseMessageType"/>
  <xs:element name="PerformReminderActionResponse"
    type="m:PerformReminderActionResponseMessageType"/>
<xs:element name="ApplyConversationActionResponseMessage"
  type="m:ResponseMessageType"
  />
  <xs:element name="FindMailboxStatisticsByKeywordsResponseMessage"
    type="m:FindMailboxStatisticsByKeywordsResponseMessageType"/>
  <xs:element name="GetSearchableMailboxesResponseMessage"
    type="m:GetSearchableMailboxesResponseMessageType"/>
  <xs:element name="SearchMailboxesResponseMessage"
    type="m:SearchMailboxesResponseMessageType"/>
  <xs:element name="GetDiscoverySearchConfigurationResponseMessage"
    type="m:GetDiscoverySearchConfigurationResponseMessageType"/>
  <xs:element name="GetHoldOnMailboxesResponseMessage"
    type="m:GetHoldOnMailboxesResponseMessageType"/>

```

```

    <xs:element name="SetHoldOnMailboxesResponseMessage"
type="m:SetHoldOnMailboxesResponseMessageType"/>
    <xs:element name="GetNonIndexableItemStatisticsResponseMessage"
type="m:GetNonIndexableItemStatisticsResponseMessageType"/>
    <!-- GetNonIndexableItemDetails response -->
    <xs:element name="GetNonIndexableItemDetailsResponseMessage"
type="m:GetNonIndexableItemDetailsResponseMessageType"/>
    <!-- GetUserHoldSettings response -->
    <xs:element name="FindPeopleResponseMessage" type="m:FindPeopleResponseMessageType"/>

    <xs:element name="GetPasswordExpirationDateResponse"
type="m:GetPasswordExpirationDateResponseMessageType"
/>
    <xs:element name="GetPersonaResponseMessage" type="m:GetPersonaResponseMessageType"/>
    <xs:element name="GetConversationItemsResponseMessage"
type="m:GetConversationItemsResponseMessageType"/>
    <xs:element name="GetUserRetentionPolicyTagsResponseMessage"
type="m:GetUserRetentionPolicyTagsResponseMessageType"/>
    <xs:element name="GetUserPhotoResponseMessage"
type="m:GetUserPhotoResponseMessageType"/>
    <xs:element name="MarkAsJunkResponseMessage" type="m:MarkAsJunkResponseMessageType"/>
</xs:choice>
</xs:complexType>

```

The following table lists the child elements of the **ArrayOfResponseMessagesType** complex type.

Element name	Type	Description
<b>CreateItemResponseMessage</b>	<b>m:ItemInfoResponseMessageType</b> (section <a href="#">2.2.4.37</a> )	Specifies the response message for the <b>CreateItem</b> operation ( <a href="#">[MS-OXWSCORE]</a> section 3.1.4.2).
<b>DeleteItemResponseMessage</b>	<b>m:ResponseMessageType</b> (section <a href="#">2.2.4.57</a> )	Specifies the response message for the <b>DeleteItem</b> operation ( <a href="#">[MS-OXWSCORE]</a> section 3.1.4.3).
<b>GetItemResponseMessage</b>	<b>m:ItemInfoResponseMessageType</b> (section <a href="#">2.2.4.37</a> )	Specifies the response message for the <b>GetItem</b> operation ( <a href="#">[MS-OXWSCORE]</a> section 3.1.4.4).
<b>UpdateItemResponseMessage</b>	<b>m:UpdateItemResponseMessageType</b> ( <a href="#">[MS-OXWSCORE]</a> section 2.2.4.6)	Specifies the response message for the <b>UpdateItem</b> operation ( <a href="#">[MS-OXWSCORE]</a> section 3.1.4.9).
<b>UpdateItemInRecoverableItemsResponseMessage</b>	<b>m:UpdateItemInRecoverableItemsResponseMessageType</b>	Specifies the response message for the <b>UpdateItemInRecoverableItems</b> operation. <a href="#">&lt;216&gt;</a>
<b>SendItemResponseMessage</b>	<b>m:ResponseMessageType</b> (section <a href="#">2.2.4.57</a> )	Specifies the response message for the <b>SendItem</b> operation ( <a href="#">[MS-OXWSCORE]</a> section 3.1.4.8).

Element name	Type	Description
<b>DeleteFolderResponseMessage</b>	<b>m:ResponseMessageType</b> (section <a href="#">2.2.4.57</a> )	Specifies the response message for the <b>DeleteFolder</b> operation ( <a href="#">[MS-OXWSFOLD]</a> section 3.1.4.4).
<b>EmptyFolderResponseMessage</b>	<b>m:ResponseMessageType</b> (section <a href="#">2.2.4.57</a> )	Specifies the response message for the <b>EmptyFolder</b> operation. <217>
<b>CreateFolderResponseMessage</b>	<b>m:FolderInfoResponseMessageType</b> ( <a href="#">[MS-OXWSFOLD]</a> section 2.2.4.9)	Specifies the response message for the <b>CreateFolder</b> operation ( <a href="#">[MS-OXWSFOLD]</a> section 3.1.4.2).
<b>GetFolderResponseMessage</b>	<b>m:FolderInfoResponseMessageType</b>	Specifies the response message for the <b>GetFolder</b> operation ( <a href="#">[MS-OXWSFOLD]</a> section 3.1.4.6).
<b>FindFolderResponseMessage</b>	<b>m:FindFolderResponseMessageType</b> ( <a href="#">[MS-OXWSSRCH]</a> section 2.2.4.1)	Specifies the response message for the <b>FindFolder</b> operation ( <a href="#">[MS-OXWSSRCH]</a> section 3.1.4.1).
<b>UpdateFolderResponseMessage</b>	<b>m:FolderInfoResponseMessageType</b>	Specifies the response message for the <b>UpdateFolder</b> operation ( <a href="#">[MS-OXWSFOLD]</a> section 3.1.4.8).
<b>MoveFolderResponseMessage</b>	<b>m:FolderInfoResponseMessageType</b>	Specifies the response message for the <b>MoveFolder</b> operation ( <a href="#">[MS-OXWSFOLD]</a> section 3.1.4.7).
<b>CopyFolderResponseMessage</b>	<b>m:FolderInfoResponseMessageType</b>	Specifies the response message for the <b>CopyFolder</b> operation ( <a href="#">[MS-OXWSFOLD]</a> section 3.1.4.1).
<b>CreateFolderPathResponseMessage</b>	<b>m:FolderInfoResponseMessageType</b>	Specifies the response message for the <b>CreateFolderPath</b> operation. <218>
<b>CreateAttachmentResponseMessage</b>	<b>m:AttachmentInfoResponseMessageType</b> ( <a href="#">[MS-OXWSATT]</a> section 2.2.4.3)	Specifies the response message for the <b>CreateAttachment</b> operation ( <a href="#">[MS-OXWSATT]</a> section 3.1.4.1).
<b>DeleteAttachmentResponseMessage</b>	<b>m&gt;DeleteAttachmentResponseMessageType</b> ( <a href="#">[MS-OXWSATT]</a> section 3.1.4.2.3.1)	Specifies the response message for the <b>DeleteAttachment</b> operation ( <a href="#">[MS-OXWSATT]</a> section 3.1.4.2).

Element name	Type	Description
<b>GetAttachmentResponseMessage</b>	<b>m:AttachmentInfoResponseMessageType</b>	Specifies the response message for the <b>GetAttachment</b> operation ([MS-OXWSATT] section 3.1.4.3).
<b>UploadItemsResponseMessage</b>	<b>m:UploadItemsResponseMessageType</b> ([MS-OXWSBTRF] section 3.1.4.2.3.2)	Specifies the response message for the <b>UploadItems</b> operation ([MS-OXWSBTRF] section 3.1.4.2). <219>
<b>ExportItemsResponseMessage</b>	<b>m:ExportItemsResponseMessageType</b> ([MS-OXWSBTRF] section 3.1.4.1.3.1)	Specifies the response message for the <b>ExportItems</b> operation ([MS-OXWSBTRF] section 3.1.4.1). <220>
<b>MarkAllItemsAsReadResponseMessage</b>	<b>m:ResponseMessageType</b>	Specifies the response message for the <b>MarkAllItemsAsRead</b> operation. <221>
<b>GetClientAccessTokenResponseMessage</b>	<b>m:GetClientAccessTokenResponseMessageType</b>	Specifies the response message for the <b>GetClientAccessToken</b> operation. <222>
<b>GetAppManifestsResponseMessage</b>	<b>m:ResponseMessageType</b> (section 2.2.4.57)	Specifies the response message for the <b>GetAppManifests</b> operation ([MS-OXWSCEXT] section 3.1.4.2)
<b>GetClientExtensionResponseMessage</b>	<b>m:ResponseMessageType</b>	Specifies the response message for the <b>GetClientExtension</b> operation. <223>
<b>FindItemResponseMessage</b>	<b>m:FindItemResponseMessageType</b> ([MS-OXWSSRCH] section 2.2.4.2)	Specifies the response message for the <b>FindItem</b> operation ([MS-OXWSSRCH] section 3.1.4.2).
<b>MoveItemResponseMessage</b>	<b>m:ItemInfoResponseMessageType</b> (section 2.2.4.37)	Specifies the response message for the <b>MoveItem</b> operation ([MS-OXWSCORE] section 3.1.4.7).
<b>ArchiveItemResponseMessage</b>	<b>m:ItemInfoResponseMessageType</b>	Specifies the response message for the <b>ArchiveItem</b> operation. <224>
<b>CopyItemResponseMessage</b>	<b>m:ItemInfoResponseMessageType</b>	Specifies the response message for the <b>CopyItem</b> operation ([MS-OXWSCORE] section 3.1.4.1).
<b>ResolveNamesResponseMessage</b>	<b>m:ResolveNamesResponseMessageType</b> ([MS-OXWSRSLNM] section)	Specifies the response message for the

Element name	Type	Description
	3.1.4.1.3.3)	<b>ResolveNames</b> operation ( <a href="#">[MS-OXWSRSLNM]</a> section 3.1.4.1).
<b>ExpandDLResponseMessage</b>	<b>m:ExpandDLResponseMessage</b> Type ( <a href="#">[MS-OXWSDLIST]</a> section 2.2.4.1)	Specifies the response message for the <b>ExpandDL</b> operation ( <a href="#">[MS-OXWSDLIST]</a> section 3.1.4.1).
<b>GetServerTimeZonesResponseMessage</b>	<b>m:GetServerTimeZonesResponseMessage</b> Type ( <a href="#">[MS-OXWSGTZ]</a> section 3.1.4.1.3.1)	Specifies the response message for the <b>GetServerTimeZones</b> operation ( <a href="#">[MS-OXWSGTZ]</a> section 3.1.4.1).
<b>GetEventsResponseMessage</b>	<b>m:GetEventsResponseMessage</b> Type ( <a href="#">[MS-OXWSNTIF]</a> section 2.2.4.1)	Specifies the response message for the <b>GetEvents</b> operation ( <a href="#">[MS-OXWSNTIF]</a> section 3.1.4.1).
<b>GetStreamingEventsResponseMessage</b>	<b>m:GetStreamingEventsResponseMessage</b> Type ( <a href="#">[MS-OXWSNTIF]</a> section 2.2.4.2)	Specifies the response message for the <b>GetStreamingEvents</b> operation ( <a href="#">[MS-OXWSNTIF]</a> section 3.1.4.2). <225>
<b>SubscribeResponseMessage</b>	<b>m:SubscribeResponseMessage</b> Type ( <a href="#">[MS-OXWSNTIF]</a> section 2.2.4.3)	Specifies the response message for the <b>Subscribe</b> operation ( <a href="#">[MS-OXWSNTIF]</a> section 3.1.4.3).
<b>UnsubscribeResponseMessage</b>	<b>m:ResponseMessageType</b>	Specifies the response message for the <b>Unsubscribe</b> operation ( <a href="#">[MS-OXWSNTIF]</a> section 3.1.4.4).
<b>SendNotificationResponseMessage</b>	<b>m:SendNotificationResponseMessage</b> Type ( <a href="#">[MS-OXWSPSNTIF]</a> section 3.1.4.1.3.1)	Specifies the response message for the <b>SendNotification</b> operation ( <a href="#">[MS-OXWSPSNTIF]</a> section 3.1.4.1).
<b>SyncFolderHierarchyResponseMessage</b>	<b>m:SyncFolderHierarchyResponseMessage</b> Type ( <a href="#">[MS-OXWSSYNC]</a> section 2.2.4.4)	Specifies the response message for the <b>SyncFolderHierarchy</b> operation ( <a href="#">[MS-OXWSSYNC]</a> section 3.1.4.1).
<b>SyncFolderItemsResponseMessage</b>	<b>m:SyncFolderItemsResponseMessage</b> Type ( <a href="#">[MS-OXWSSYNC]</a> section 2.2.4.9)	Specifies the response message for the <b>SyncFolderItems</b> operation ( <a href="#">[MS-OXWSSYNC]</a> section 3.1.4.2).
<b>CreateManagedFolderResponseMessage</b>	<b>m:FolderInfoResponseMessageType</b>	Specifies the response message for the <b>CreateManagedFolder</b> operation ( <a href="#">[MS-OXWSFOLD]</a> section 3.1.4.3).

Element name	Type	Description
<b>ConvertIdResponseMessage</b>	<b>m:ConvertIdResponseMessageType</b> ( <a href="#">[MS-OXWSCVTID]</a> section 3.1.4.1.3.1)	Specifies the response message for the <b>ConvertId</b> operation ( <a href="#">[MS-OXWSCVTID]</a> section 3.1.4.1).
<b>GetSharingMetadataResponseMessage</b>	<b>m:GetSharingMetadataResponseMessageType</b> ( <a href="#">[MS-OXWSMSHR]</a> section 2.2.4.2)	Specifies the response message for the <b>GetSharingMetadata</b> operation ( <a href="#">[MS-OXWSMSHR]</a> section 3.1.4.4).
<b>RefreshSharingFolderResponseMessage</b>	<b>m:RefreshSharingFolderResponseMessageType</b> ( <a href="#">[MS-OXWSMSHR]</a> section 2.2.4.3)	Specifies the response message for the <b>RefreshSharingFolder</b> operation ( <a href="#">[MS-OXWSMSHR]</a> section 3.1.4.5).
<b>GetSharingFolderResponseMessage</b>	<b>m:GetSharingFolderResponseMessageType</b> ( <a href="#">[MS-OXWSMSHR]</a> section 2.2.4.1)	Specifies the response message for the <b>GetSharingFolder</b> operation ( <a href="#">[MS-OXWSMSHR]</a> section 3.1.4.3).
<b>CreateUserConfigurationResponseMessage</b>	<b>m:ResponseMessageType</b>	Specifies the response message for the <b>CreateUserConfiguration</b> operation ( <a href="#">[MS-OXWSUSRCFG]</a> section 3.1.4.1).
<b>DeleteUserConfigurationResponseMessage</b>	<b>m:ResponseMessageType</b>	Specifies the response message for the <b>DeleteUserConfiguration</b> operation ( <a href="#">[MS-OXWSUSRCFG]</a> section 3.1.4.2).
<b>GetUserConfigurationResponseMessage</b>	<b>m:GetUserConfigurationResponseMessageType</b> ( <a href="#">[MS-OXWSUSRCFG]</a> section 3.1.4.3.3.1)	Specifies the response message for the <b>GetUserConfiguration</b> operation ( <a href="#">[MS-OXWSUSRCFG]</a> section 3.1.4.3).
<b>UpdateUserConfigurationResponseMessage</b>	<b>m:ResponseMessageType</b>	Specifies the response message for the <b>UpdateUserConfiguration</b> operation ( <a href="#">[MS-OXWSUSRCFG]</a> section 3.1.4.4).
<b>GetRoomListsResponse</b>	<b>m:GetRoomListsResponseMessageType</b> ( <a href="#">[MS-OXWSGTRM]</a> section 3.1.4.1.3.1)	Specifies the response message for the <b>GetRoomLists</b> operation ( <a href="#">[MS-OXWSGTRM]</a> section 3.1.4.1).
<b>GetRoomsResponse</b>	<b>m:GetRoomsResponseMessageType</b> ( <a href="#">[MS-OXWSGTRM]</a> section 3.1.4.1.3.1)	Specifies the response message for the <b>GetRooms</b> operation ( <a href="#">[MS-OXWSGTRM]</a> section 3.1.4.1).



Element name	Type	Description
	3.1.4.2.3.1)	operation ( <a href="#">[MS-OXWSGTRM]</a> section 3.1.4.2).
<b>GetRemindersResponse</b>	<b>m:GetRemindersResponseMessage Type</b>	Specifies the response message for the <b>GetReminders</b> operation. <a href="#">&lt;226&gt;</a>
<b>PerformReminderActionResponse</b>	<b>m:PerformReminderActionResponseMessage Type</b>	Specifies the response message for the <b>PerformReminderAction</b> operation. <a href="#">&lt;227&gt;</a>
<b>ApplyConversationActionResponseMessage</b>	<b>m:ResponseMessageType</b>	Specifies the response message for the <b>ApplyConversationAction</b> operation ( <a href="#">[MS-OXWSCONV]</a> section 3.1.4.3). <a href="#">&lt;228&gt;</a>
<b>FindMailboxStatisticsByKeywordsResponseMessage</b>	<b>m:FindMailboxStatisticsByKeywordsResponseMessageType</b>	Specifies the response message for the <b>FindMailboxStatisticsByKeywords</b> operation. <a href="#">&lt;229&gt;</a>
<b>GetSearchableMailboxesResponseMessage</b>	<b>m:GetSearchableMailboxesResponseMessageType</b>	Specifies the response message for the <b>GetSearchableMailboxes</b> operation. <a href="#">&lt;230&gt;</a>
<b>SearchMailboxesResponseMessage</b>	<b>m:SearchMailboxesResponseMessageType</b>	Specifies the response message for the <b>SearchMailboxes</b> operation. <a href="#">&lt;231&gt;</a>
<b>GetDiscoverySearchConfigurationResponseMessage</b>	<b>m:GetDiscoverySearchConfigurationResponseMessageType</b> ( <a href="#">[MS-OXWSEDISC]</a> section 3.1.4.1.3.2)	Specifies the response message for the <b>GetDiscoverySearchConfiguration</b> operation ( <a href="#">[MS-OXWSEDISC]</a> section 3.1.4.1.2.1). <a href="#">&lt;232&gt;</a>
<b>GetHoldOnMailboxesResponseMessage</b>	<b>m:GetHoldOnMailboxesResponseMessageType</b>	Specifies the response message for the <b>PerformReminderAction</b> operation. <a href="#">&lt;233&gt;</a>
<b>SetHoldOnMailboxesResponseMessage</b>	<b>m:SetHoldOnMailboxesResponseMessageType</b>	Specifies the response message for the <b>PerformReminderAction</b> operation. <a href="#">&lt;234&gt;</a>
<b>GetNonIndexableItemStatisticsResponseMessage</b>	<b>m:GetNonIndexableItemStatisticsResponseMessageType</b>	Specifies the response message for the <b>GetNonIndexableItemStatistics</b> operation. <a href="#">&lt;235&gt;</a>
<b>GetNonIndexableItemDetailsResponseMessage</b>	<b>m:GetNonIndexableItemDetailsResponseMessageType</b>	Specifies the response message for the <b>GetNonIndexableItemDetails</b>

Element name	Type	Description
		Is operation. <236>
<b>FindPeopleResponseMessage</b>	<b>m:FindPeopleResponseMessageTy pe</b>	Specifies the response message for the <b>PerformReminderAction</b> operation. <237>
<b>GetPasswordExpirationDateRe sponse</b>	<b>m:GetPasswordExpirationDateRes ponseMessageType</b> ([MS-OXWSPED] section 3.1.4.1.3.2)	Specifies the response message for the GetPasswordExpirationDate operation ([MS-OXWSPED] section 3.1.4.1). <238>
<b>GetPersonaResponseMessage</b>	<b>m:GetPersonaResponseMessageTy pe</b>	Specifies the response message for the <b>GetPersonaResponseMessa ge</b> operation. <239>
<b>GetConversationItemsRespon seMessage</b>	<b>m:GetConversationItemsResponse MessageType</b> ([MS-OXWSCONV] section 3.1.4.2.3.6)	Specifies the response message for the <b>GetConversationItemsResp onseMessage</b> operation. <240>
<b>GetUserRetentionPolicyTagsR esponseMessage</b>	<b>m:GetUserRetentionPolicyTagsRes ponseMessageType</b>	Specifies the response message for the <b>GetUserRetentionPolicyTag sResponseMessage</b> operation. <241>
<b>GetUserPhotoResponseMessa ge</b>	<b>m:GetUserPhotoResponseMessage Type</b>	Specifies the response message for the <b>GetUserPhotoResponseMes sage</b> operation. <242>
<b>MarkAsJunkResponseMessage</b>	<b>m:MarkAsJunkResponseMessageT ype</b> ([MS-OXWSCORE] section 3.1.4.6.3.3)	Specifies the response message for the <b>MarkAsJunk</b> operation ([MS-OXWSCORE] section 3.1.4.6).

#### 2.2.4.11 t:ArrayOfStringsType Complex Type

The **ArrayOfStringsType** complex type specifies a data structure that can contain zero or more strings.

```
<xs:complexType name="ArrayOfStringsType">
  <xs:sequence>
    <xs:element name="String"
      type="xs:string"
      minOccurs="0"
      maxOccurs="unbounded"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **ArrayOfStringsType** complex type.

Element name	Type	Description
String	xs:string ( <a href="#">[XMLSCHEMA2]</a> )	Specifies a single string of data.

#### 2.2.4.12 t:BaseEmailAddressType Complex Type

The **BaseEmailAddressType** complex type specifies the base type for the **t:EmailAddressType** type (section [2.2.4.27](#)).

```
<xs:complexType name="BaseEmailAddressType" />
```

#### 2.2.4.13 t:BaseItemIdType Complex Type

The **BaseItemIdType** complex type specifies the base type for identifiers that represent items in a mailbox. The **BaseItemIdType** type MUST NOT be sent in a SOAP message because it is an abstract type.

```
<xs:complexType name="BaseItemIdType"
  abstract="true"
/>
```

#### 2.2.4.14 t:BasePathToElementType Complex Type

The **BasePathToElementType** complex type specifies the base type to types that specify additional properties. The **BasePathToElementType** type MUST NOT be sent in a SOAP message because it is an abstract type.

```
<xs:complexType name="BasePathToElementType"
  abstract="true"
/>
```

#### 2.2.4.15 m:BaseRequestType Complex Type

The **BaseRequestType** complex type specifies the base type for requests. The **BaseRequestType** type MUST NOT be sent in a SOAP message because it is an abstract type.

```
<xs:complexType name="BaseRequestType"
  abstract="true"
/>
```

#### 2.2.4.16 m:BaseResponseMessageType Complex Type

The **BaseResponseMessageType** complex type specifies the base response message for responses. The **BaseResponseMessageType** complex type MUST NOT be sent in a SOAP message because it is an abstract type.

```

<xs:complexType name="BaseResponseMessageType">
  <xs:sequence>
    <xs:element name="ResponseMessages"
      type="m:ArrayOfResponseMessagesType"
    />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **BaseResponseMessageType** complex type.

Element name	Type	Description
<b>ResponseMessages</b>	<b>m:ArrayOfResponseMessagesType</b> (section <a href="#">2.2.4.10</a> )	Specifies an array of response messages. There <b>MUST</b> be only one <b>ResponseMessages</b> element in a response.

### 2.2.4.17 t:BodyType Complex Type

The **BodyType** complex type specifies the body content and body content format of an item.

```

<xs:complexType name="BodyType">
  <xs:simpleContent>
    <xs:extension
      base="xs:string"
    >
      <xs:attribute name="BodyType" type="t:BodyTypeType"/>
      <xs:attribute name="IsTruncated" type="xs:boolean" use="optional"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

```

#### Attributes

Name	Type	Description
<b>BodyType</b>	<b>t:BodyTypeType</b> (section <a href="#">2.2.3.2</a> )	Specifies the body content and format of an item.
<b>IsTruncated</b>	<b>xs:boolean</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies whether the body is truncated. <a href="#">&lt;243&gt;</a>

### 2.2.4.18 t:ChangeHighlightsType

The **ChangeHighlightsType** complex type specifies the changes made to a meeting when a meeting update occurs. [<244>](#)

```

<xs:complexType name="ChangeHighlightsType">
  <xs:sequence>
    <xs:element name="HasLocationChanged" type="xs:boolean" minOccurs="0" />
    <xs:element name="Location" type="xs:string" minOccurs="0" />
    <xs:element name="HasStartTimeChanged" type="xs:boolean" minOccurs="0" />
    <xs:element name="Start" type="xs:dateTime" minOccurs="0" />
    <xs:element name="HasEndTimeChanged" type="xs:boolean" minOccurs="0" />
  </xs:sequence>
</xs:complexType>

```

```

    <xs:element name="End" type="xs:dateTime" minOccurs="0" />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **ChangeHighlightsType** complex type.

Element name	Type	Description
<b>HasLocationChanged</b>	<b>xs:boolean</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies whether the meeting location has changed.
<b>Location</b>	<b>xs:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the meeting location.
<b>HasStartTimeChanged</b>	<b>xs:boolean</b>	Specifies whether the meeting start time has changed.
<b>Start</b>	<b>xs:dateTime</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the meeting start time.
<b>HasEndTimeChanged</b>	<b>xs:boolean</b>	Specifies whether the meeting end time has changed.
<b>End</b>	<b>xs:dateTime</b>	Specifies the meeting end time.

#### 2.2.4.19 t:ConnectingSIDType Complex Type

The **ConnectingSIDType** complex type specifies the account to use for impersonation.

```

<xs:complexType name="ConnectingSIDType">
  <xs:choice>
    <xs:element name="PrincipalName"
      type="t:NonEmptyStringType"
    />
    <xs:element name="SID"
      type="t:NonEmptyStringType"
    />
    <xs:element name="PrimarySmtpAddress"
      type="t:NonEmptyStringType"
    />
    <xs:element name="SmtpAddress"
      type="t:NonEmptyStringType"
    />
  </xs:choice>
</xs:complexType>

```

The following table lists the child elements of the **ConnectingSIDType** complex type.

Element name	Type	Description
<b>PrincipalName</b>	<b>t:NonEmptyStringType</b> (section <a href="#">2.2.3.20</a> )	Specifies the user principal name (UPN) for the account to use for impersonation.
<b>SID</b>	<b>t:NonEmptyStringType</b>	Specifies the security descriptor definition language (SDDL) form of the security identifier (SID) for the account to be used for

Element name	Type	Description
		impersonation.
<b>PrimarySmtpAddress</b>	<b>t:NonEmptyStringType</b>	Specifies the primary <b>SMTP</b> address of the account to be used for impersonation.
<b>SmtpAddress</b>	<b>t:NonEmptyStringType</b>	Specifies an SMTP address of the account to be used for impersonation.

Only one of the elements specified in the **ConnectingSIDType** complex type MUST exist in an impersonation request.

#### 2.2.4.20 t:ConstantValueType Complex Type

The **ConstantValueType** complex type specifies a constant value for a search restriction.

```
<xs:complexType name="ConstantValueType">
  <xs:attribute name="Value"
    type="xs:string"
    use="required"
  />
</xs:complexType>
```

Attributes

Name	Type	Description
Value	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the value to be compared in a restriction.

#### 2.2.4.21 t:DailyRecurrencePatternType Complex Type

The **DailyRecurrencePatternType** complex type specifies the interval, in days, at which a calendar item or a task recurs.

```
<xs:complexType name="DailyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:IntervalRecurrencePatternBaseType"
    />
  </xs:complexContent>
</xs:complexType>
```

#### 2.2.4.22 t:DeletedOccurrenceInfoType Complex Type

The **DeletedOccurrenceInfoType** complex type specifies a deleted occurrence of a recurring calendar item.

```
<xs:complexType name="DeletedOccurrenceInfoType">
  <xs:sequence>
    <xs:element name="Start"
      type="xs:dateTime"
    />
  </xs:sequence>
</xs:complexType>
```

```

    />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **DeletedOccurrenceInfoType** complex type.

Element name	Type	Description
<b>Start</b>	<b>xs:dateTime</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the start time of a deleted occurrence of a recurring calendar item.

### 2.2.4.23 t:DistinguishedFolderIdType Complex Type

The **DistinguishedFolderIdType** complex type specifies a distinguished folder identified by name.

```

<xs:complexType name="DistinguishedFolderIdType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseFolderIdType"
    >
      <xs:sequence>
        <xs:element name="Mailbox"
          type="t:EmailAddressType"
          minOccurs="0"
        />
      </xs:sequence>
      <xs:attribute name="Id"
        type="t:DistinguishedFolderIdNameType"
        use="required"
      />
      <xs:attribute name="ChangeKey"
        type="xs:string"
        use="optional"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **DistinguishedFolderIdType** complex type.

Element name	Type	Description
<b>Mailbox</b>	<b>t:EmailAddressType</b> (section <a href="#">2.2.4.27</a> )	Specifies the primary SMTP address of a principal for a delegate access scenario. This element <b>MUST</b> exist to initiate delegate access.

Attributes

Name	Type	Description
Id	<b>t:DistinguishedFolderIdNameType</b> (section <a href="#">2.2.3.10</a> )	Specifies the identifier of a distinguished folder. This attribute <b>MUST</b> exist.
ChangeKey	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the change key of a distinguished folder.

#### 2.2.4.24 t:Duration Complex Type

The **Duration** complex type specifies a time interval.

```
<xs:complexType name="Duration">
  <xs:sequence>
    <xs:element name="StartTime"
      type="xs:dateTime"
      maxOccurs="1"
      minOccurs="1"
    />
    <xs:element name="EndTime"
      type="xs:dateTime"
      maxOccurs="1"
      minOccurs="1"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **Duration** complex type.

Element name	Type	Description
<b>StartTime</b>	<b>xs:dateTime</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the start of a time period. This element <b>MUST</b> be present.
<b>EndTime</b>	<b>xs:dateTime</b>	Specifies the end of a time period. This element <b>MUST</b> be present.

Restriction: The value of the **EndTime** element **MUST** be greater than the value of the **StartTime** element. Also, the specified times **MUST** be in **Coordinated Universal Time (UTC)**.

#### 2.2.4.25 t:EffectiveRightsType Complex Type

The **EffectiveRightsType** complex type specifies client rights based on the permission settings for an item or folder.

```
<xs:complexType name="EffectiveRightsType">
  <xs:sequence>
    <xs:element name="CreateAssociated"
      type="xs:boolean"
    />
    <xs:element name="CreateContents"
      type="xs:boolean"
    />
  </xs:sequence>
</xs:complexType>
```



```

<xs:element name="CreateHierarchy"
  type="xs:boolean"
  />
<xs:element name="Delete"
  type="xs:boolean"
  />
<xs:element name="Modify"
  type="xs:boolean"
  />
<xs:element name="Read"
  type="xs:boolean"
  />
<xs:element name="ViewPrivateItems"
  type="xs:boolean"
  />
</xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **EffectiveRightsType** complex type.

Element name	Type	Description
<b>CreateAssociated</b>	<b>xs:boolean</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies whether a client can create an associated contents table.
<b>CreateContents</b>	<b>xs:boolean</b>	Specifies whether a client can create a contents table.
<b>CreateHierarchy</b>	<b>xs:boolean</b>	Specifies whether a client can create a hierarchy table.
<b>Delete</b>	<b>xs:boolean</b>	Specifies whether a client can delete a folder or item.
<b>Modify</b>	<b>xs:boolean</b>	Specifies whether a client can modify a folder or item.
<b>Read</b>	<b>xs:boolean</b>	Specifies whether a client can read a folder or item.
<b>ViewPrivateItems</b>	<b>xs:boolean</b>	Specifies whether a client can read private items. <a href="#">&lt;245&gt;</a>

#### 2.2.4.26 t:EmailAddress

The **EmailAddress** complex type specifies the name and address of the user.

```

<xs:complexType name="EmailAddress">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string" />
    <xs:element minOccurs="1" maxOccurs="1" name="Address" type="xs:string" />
    <xs:element minOccurs="0" maxOccurs="1" name="RoutingType" type="xs:string" />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **EmailAddress** complex type.

Element	Type	Definition
<b>Name</b>	<b>xs:string</b> ( <a href="#">XMLSCHEMA2</a> )	Represents the name of the attendee. This element is optional.
<b>Address</b>	<b>xs:string</b>	Represents the e-mail address of the attendee. This element <b>MUST</b> be present and <b>MUST</b> be a Simple Mail Transfer Protocol (SMTP) address.
<b>RoutingType</b>	<b>xs:string</b>	Represents the routing protocol for the e-mail address. This element is optional.

### 2.2.4.27 t:EmailAddressType Complex Type

The **EmailAddressType** complex type specifies an email address.

```
<xs:complexType name="EmailAddressType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseEmailAddressType"
    >
      <xs:sequence>
        <xs:element name="Name"
          type="xs:string"
          minOccurs="0"
        />
        <xs:element name="EmailAddress"
          type="t:NonEmptyStringType"
          minOccurs="0"
        />
        <xs:element name="RoutingType"
          type="t:NonEmptyStringType"
          minOccurs="0"
        />
        <xs:element name="MailboxType"
          type="t:MailboxTypeType"
          minOccurs="0"
        />
        <xs:element name="ItemId"
          type="t:ItemIdType"
          minOccurs="0"
        />
        <xs:element name="OriginalDisplayName"
          type="xs:string"
          minOccurs="0"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists the child elements of the **EmailAddressType** complex type.

Element name	Type	Description
<b>Name</b>	<b>xs:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the name of the mailbox that is

Element name	Type	Description
		associated with the e-mail address that is specified in the <b>EmailAddress</b> element.
<b>EmailAddress</b>	<b>t:NonEmptyStringType</b> (section <a href="#">2.2.3.20</a> )	Specifies an e-mail address.
<b>RoutingType</b>	<b>t:NonEmptyStringType</b>	Specifies the type of routing for the e-mail address that is specified in the <b>EmailAddress</b> element.
<b>MailboxType</b>	<b>t:MailboxTypeType</b> (section <a href="#">2.2.3.18</a> )	Specifies the type of mailbox that is represented by the <b>EmailAddressType</b> complex type (section <a href="#">2.2.4.27</a> ).
<b>ItemId</b>	<b>t:ItemIdType</b> ( <a href="#">[MS-OXWSCORE]</a> section 2.2.4.19)	Specifies the item identifier for the e-mail address that is represented by the <b>EmailAddressType</b> complex type.
<b>OriginalDisplayName</b>	<b>xs:string</b>	Specifies the original display name for this address.

### 2.2.4.28 t:EndDateRecurrenceRangeType Complex Type

The **EndDateRecurrenceRangeType** complex type specifies the start date and end date of an item recurrence pattern.

```
<xs:complexType name="EndDateRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrenceRangeBaseType"
    >
      <xs:sequence>
        <xs:element name="EndDate"
          type="xs:date"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists the child elements of the **EndDateRecurrenceRangeType** complex type.

Element name	Type	Description
<b>EndDate</b>	<b>xs:date</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the end date of a recurrence pattern.

### 2.2.4.29 t:ExchangeImpersonationType Complex Type

The **ExchangeImpersonationType** complex type specifies the user to be impersonated.

```
<xs:complexType name="ExchangeImpersonationType">
  <xs:sequence>
    <xs:element name="ConnectingSID"
    />
  </xs:sequence>
</xs:complexType>
```

```

        type="t:ConnectingSIDType"
      />
    </xs:sequence>
    <xs:anyAttribute
      namespace="http://schemas.xmlsoap.org/soap/envelope/"
    />
  </xs:complexType>

```

The following table lists the child elements of the **ExchangeImpersonationType** complex type.

Element name	Type	Description
<b>ConnectingSID</b>	<b>t:ConnectingSIDType</b> (section <a href="#">2.2.4.19</a> )	Specifies the account to be impersonated. This element MUST exist for impersonation.

### 2.2.4.30 t:FieldURIOrConstantType Complex Type

The **FieldURIOrConstantType** complex type specifies either a property or a constant value to be compared with another property.

```

<xs:complexType name="FieldURIOrConstantType">
  <xs:choice>
    <xs:element
      ref="t:Path"
    />
    <xs:element name="Constant"
      type="t:ConstantValueType"
    />
  </xs:choice>
</xs:complexType>

```

The following table lists the child elements of the **FieldURIOrConstantType** complex type.

Element name	Type	Description
<b>t:Path</b>	<b>t:Path</b>	Specifies the property to be used in a two-operand search expression. The <b>t:Path</b> element (section <a href="#">2.2.5.8</a> ) specifies a <b>substitutionGroup</b> attribute, as specified in <a href="#">[XMLSCHEMA0]</a> . An element that is represented by the <b>substitutionGroup</b> attribute of the <b>t:Path</b> element MUST be present.
<b>Constant</b>	<b>t:ConstantValueType</b> (section <a href="#">2.2.4.20</a> )	Specifies a constant to be used in a two-operand search expression.

### 2.2.4.31 t:FolderIdType Complex Type

The **FolderIdType** complex type specifies a folder identifier.

```

<xs:complexType name="FolderIdType">
  <xs:complexContent>
    <xs:extension

```

```

    base="t:BaseFolderIdType"
  >
    <xs:attribute name="Id"
      type="xs:string"
      use="required"
    />
    <xs:attribute name="ChangeKey"
      type="xs:string"
      use="optional"
    />
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

#### Attributes

Name	Type	Description
<b>Id</b>	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies a folder identifier.
<b>ChangeKey</b>	<b>xs:string</b>	Specifies a change key.

### 2.2.4.32 t:FolderResponseShapeType Complex Type

The **FolderResponseShapeType** complex type specifies the properties that are returned in a response in a **SyncFolderHierarchy** operation, as specified in [\[MS-OXWSSYNC\]](#) section 3.1.4.1, **GetFolder** operation, as specified in [\[MS-OXWSFOLD\]](#) section 3.1.4.6, or **FindFolder** operation as specified in [\[MS-OXWSSRCH\]](#) section 3.1.4.1.

```

<xs:complexType name="FolderResponseShapeType">
  <xs:sequence>
    <xs:element name="BaseShape"
      type="t:DefaultShapeNamesType"
    />
    <xs:element name="AdditionalProperties"
      type="t:NonEmptyArrayOfPathsToElementType"
    />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **FolderResponseShapeType** complex type.

Element name	Type	Description
<b>BaseShape</b>	<b>t:DefaultShapeNamesType</b> (section <a href="#">2.2.3.7</a> )	Specifies the basic configuration of properties to be returned in a response.
<b>AdditionalProperties</b>	<b>t:NonEmptyArrayOfPathsToElementType</b> (section <a href="#">2.2.4.44</a> )	Specifies the identity of additional properties to be returned in a response.

### 2.2.4.33 t:ForwardItemType Complex Type

The **ForwardItemType** complex type specifies a response object for forwarding messages and meeting messages to other recipients.

```
<xs:complexType name="ForwardItemType">
  <xs:complexContent>
    <xs:extension
      base="t:SmartResponseType"
    />
  </xs:complexContent>
</xs:complexType>
```

### 2.2.4.34 t:HighlightTermType

The **HighlightTermType** complex type specifies the terms that are highlighted when using AQS. [<246>](#)

```
<xs:complexType name="HighlightTermType">
  <xs:sequence>
    <xs:element name="Scope" type="xs:string" minOccurs="1" maxOccurs="1" />
    <xs:element name="Value" type="xs:string" minOccurs="1" maxOccurs="1"/>
  </xs:sequence>
</xs:complexType>
```

The following table lists the child element of the **HighlightTermType** complex type.

Element name	Type	Description
<b>Scope</b>	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the querystring token scope.
<b>Value</b>	<b>xs:string</b>	Specifies the querystring token value.

### 2.2.4.35 t:InternetHeaderType Complex Type

The **InternetHeaderType** complex type specifies the Internet message header for a specified header within the headers collection.

```
<xs:complexType name="InternetHeaderType">
  <xs:simpleContent>
    <xs:extension
      base="xs:string"
    >
      <xs:attribute name="HeaderName"
        type="xs:string"
        use="required"
      />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```

Attribute name	Type	Description
<b>HeaderName</b>	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the name of the header.

### 2.2.4.36 t:IntervalRecurrencePatternBaseType Complex Type

The **IntervalRecurrencePatternBaseType** complex type specifies the base type for non-yearly recurrence patterns.

```

<xs:complexType name="IntervalRecurrencePatternBaseType"
  abstract="true"
>
  <xs:complexContent>
    <xs:extension
      base="t:RecurrencePatternBaseType"
    >
      <xs:sequence>
        <xs:element name="Interval"
          type="xs:int"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **IntervalRecurrencePatternBaseType** complex type.

Element name	Type	Description
<b>Interval</b>	<b>xs:int</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the interval between two consecutive recurring items.

### 2.2.4.37 m:ItemInfoResponseMessageType Complex Type

The **ItemInfoResponseMessageType** complex type specifies the response message for operations that create, update, or delete items.

```

<xs:complexType name="ItemInfoResponseMessageType">
  <xs:complexContent>
    <xs:extension
      base="m:ResponseMessageType"
    >
      <xs:sequence>
        <xs:element name="Items"
          type="t:ArrayOfRealItemsType"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **ItemInfoResponseMessageType** complex type.

Element name	Type	Description
<b>Items</b>	<b>t:ArrayOfRealItemsType</b> (section <a href="#">2.2.4.8</a> )	Specifies an array of <b>real items</b> .

### 2.2.4.38 t:ItemResponseShapeType Complex Type

The **ItemResponseShapeType** complex type specifies a set of properties to return in a **GetItem** operation, as specified in [\[MS-OXWSCORE\]](#) section 3.1.4.4, **FindItem** operation, as specified in [\[MS-OXWSSRCH\]](#) section 3.1.4.2, or **SyncFolderItems** operation, as specified in [\[MS-OXWSSYNC\]](#) section 3.1.4.2, response.

```
<xs:complexType name="ItemResponseShapeType">
  <xs:sequence>
    <xs:element name="BaseShape" type="t:DefaultShapeNamesType"/>
    <xs:element name="IncludeMimeContent" type="xs:boolean" minOccurs="0"/>
    <xs:element name="BodyType" type="t:BodyTypeResponseType" minOccurs="0"/>
    <xs:element name="FilterHtmlContent" type="xs:boolean" minOccurs="0"/>
    <xs:element name="ConvertHtmlCodePageToUTF8" type="xs:boolean" minOccurs="0"
maxOccurs="1"/>
    <xs:element name="InlineImageUrlTemplate" type="xs:string" minOccurs="0" maxOccurs="1"/>
    <xs:element name="BlockExternalImages" type="xs:boolean" minOccurs="0"
maxOccurs="1"/>
    <xs:element name="AddBlankTargetToLinks" type="xs:boolean" minOccurs="0"
maxOccurs="1"/>
    <xs:element name="MaximumBodySize" type="xs:int" minOccurs="0" maxOccurs="1"/>
    <xs:element name="AdditionalProperties" type="t:NonEmptyArrayOfPathsToElementType"
minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **ItemResponseShapeType** complex type.

Element name	Type	Description
<b>BaseShape</b>	<b>t:DefaultShapeNamesType</b> (section <a href="#">2.2.3.7</a> )	Specifies the requested base properties to return in a response. This element <b>MUST</b> be present.
<b>IncludeMimeContent</b>	<b>xs:boolean</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies whether the MIME content of an item is returned in a response.
<b>BodyType</b>	<b>t:BodyTypeResponseType</b> (section <a href="#">2.2.3.1</a> )	Specifies the requested body text format for the <b>Body</b> property that is returned in a response. If this element is not present, the server



Element name	Type	Description
		MUST use the default value of "default".
<b>FilterHtmlContent</b>	<b>xs:boolean</b>	Specifies whether HTML content filtering is enabled. If this value is set to <b>true</b> , script blocks and Web beacons MUST be removed from message bodies that are returned in a response.
<b>ConvertHtmlCodePageToUTF8</b>	<b>xs:boolean</b>	Specifies whether the item HTML body is converted to UTF8. The value of this element MUST be set to <b>true</b> or the element MUST NOT be specified to indicate to the server to convert the HTML code page to UTF8. <a href="#">&lt;247&gt;</a>
<b>InlineImageUrlTemplate</b>	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the name of the template for the inline image URL. <a href="#">&lt;248&gt;</a>
<b>BlockExternalImages</b>	<b>xs:boolean</b>	Specifies whether external images are blocked. <a href="#">&lt;249&gt;</a>
<b>AddBlankTargetToLinks</b>	<b>xs:boolean</b>	Specifies whether the target attribute is set to a value of <b>blank</b> . <a href="#">&lt;250&gt;</a>
<b>MaximumBodySize</b>	<b>xs:int</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the maximum size of the body to return.
<b>AdditionalProperties</b>	<b>t:NonEmptyArrayOfPathsToElementType</b> (section <a href="#">2.2.4.44</a> )	Specifies a set of requested additional properties to return in a response.

### 2.2.4.39 t:MailboxCultureType Complex Type

The **MailboxCultureType** complex type specifies the culture to be used when opening a mailbox.

```
<xs:complexType name="MailboxCultureType">
  <xs:simpleContent>
    <xs:extension
      base="xs:language"
```

```

    >
    <xs:anyAttribute
      namespace="http://schemas.xmlsoap.org/soap/envelope/"
    />
  </xs:extension>
</xs:simpleContent>
</xs:complexType>

```

The text value indicates the language to be used. The possible values for this element are specified in [\[RFC3066\]](#).

#### 2.2.4.40 t:ManagementRoleType Complex Type

The **ManagementRoleType** complex type specifies an array of user and application roles. [<251>](#)

```

<xs:complexType name="ManagementRoleType">
  <xs:sequence>
    <xs:element name="UserRoles" type="t:NonEmptyArrayOfRoleType" minOccurs="0"
      maxOccurs="1"/>
    <xs:element name="ApplicationRoles" type="t:NonEmptyArrayOfRoleType" minOccurs="0"
      maxOccurs="1" />
  </xs:sequence>
</xs:complexType>

```

The following table lists and describes the child elements of the **ManagementRoleType** complex type.

Element name	Type	Description
<b>UserRoles</b>	<b>t:NonEmptyArrayOfRoleType</b> (section <a href="#">2.2.4.45</a> )	Specifies an array of user roles.
<b>ApplicationRoles</b>	<b>t:NonEmptyArrayOfRoleType</b>	Specifies an array of application roles.

#### 2.2.4.41 t:NoEndRecurrenceRangeType Complex Type

The **NoEndRecurrenceRangeType** complex type specifies the start date of an item recurrence pattern that does not have a defined end date.

```

<xs:complexType name="NoEndRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrenceRangeBaseType"
    />
  </xs:complexContent>
</xs:complexType>

```

#### 2.2.4.42 t:NonEmptyArrayOfAllItemsType Complex Type

The **NonEmptyArrayOfAllItemsType** complex type specifies an array of store items and response objects.

```

<xs:complexType name="NonEmptyArrayOfAllItemsType">
  <xs:sequence>
    <xs:choice
      minOccurs="1"
      maxOccurs="unbounded"
    >
      <xs:element name="Item"
        type="t:ItemType"
      />
      <xs:element name="Message"
        type="t:MessageType"
      />
      <xs:element name="CalendarItem"
        type="t:CalendarItemType"
      />
      <xs:element name="Contact"
        type="t:ContactItemType"
      />
      <xs:element name="DistributionList"
        type="t:DistributionListType"
      />
      <xs:element name="MeetingMessage"
        type="t:MeetingMessageType"
      />
      <xs:element name="MeetingRequest"
        type="t:MeetingRequestMessageType"
      />
      <xs:element name="MeetingResponse"
        type="t:MeetingResponseMessageType"
      />
      <xs:element name="MeetingCancellation"
        type="t:MeetingCancellationMessageType"
      />
      <xs:element name="Task"
        type="t:TaskType"
      />
      <xs:element name="PostItem"
        type="t:PostItemType"
      />
      <xs:element name="ReplyToItem"
        type="t:ReplyToItemType"
      />
      <xs:element name="ForwardItem"
        type="t:ForwardItemType"
      />
      <xs:element name="ReplyAllToItem"
        type="t:ReplyAllToItemType"
      />
      <xs:element name="AcceptItem"
        type="t:AcceptItemType"
      />
      <xs:element name="TentativelyAcceptItem"
        type="t:TentativelyAcceptItemType"
      />
      <xs:element name="DeclineItem"
        type="t:DeclineItemType"
      />
      <xs:element name="CancelCalendarItem"
        type="t:CancelCalendarItemType"
      />
    </xs:choice>
  </xs:sequence>
</xs:complexType>

```

```

/>
<xs:element name="RemoveItem"
  type="t:RemoveItemType"
/>
<xs:element name="SuppressReadReceipt"
  type="t:SuppressReadReceiptType"
/>
<xs:element name="PostReplyItem"
  type="t:PostReplyItemType"
/>
<xs:element name="AcceptSharingInvitation"
  type="t:AcceptSharingInvitationType"
/>
</xs:choice>
</xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **NonEmptyArrayOfAllItemsType** complex type.

Element name	Type	Description
<b>Item</b>	<b>t:ItemType</b> ( <a href="#">[MS-OXWSCORE]</a> section 2.2.4.8)	Specifies an item.
<b>Message</b>	<b>t:MessageType</b> ( <a href="#">[MS-OXWSMSG]</a> section 2.2.4.1)	Specifies a message item.
<b>CalendarItem</b>	<b>t:CalendarItemType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.4)	Specifies a calendar item.
<b>Contact</b>	<b>t:ContactItemType</b> ( <a href="#">[MS-OXWSCONT]</a> section 2.2.4.2)	Specifies a contact item.
<b>DistributionList</b>	<b>t:DistributionListType</b> ( <a href="#">[MS-OXWSDLIST]</a> section 2.2.4.3)	Specifies a distribution list item.
<b>MeetingMessage</b>	<b>t:MeetingMessageType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.12)	Specifies a meeting message item.
<b>MeetingRequest</b>	<b>t:MeetingRequestMessageType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.13)	Specifies a meeting request message item.
<b>MeetingResponse</b>	<b>t:MeetingResponseMessageType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.14)	Specifies a meeting response message item.
<b>MeetingCancellation</b>	<b>t:MeetingCancellationMessageType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.11)	Specifies a meeting cancellation message item.
<b>Task</b>	<b>t:TaskType</b> ( <a href="#">[MS-OXWSTASK]</a> section 2.2.4.3))	Specifies a task item.
<b>PostItem</b>	<b>t:PostItemType</b> ( <a href="#">[MS-OXWSPOST]</a> section 2.2.4.1)	Specifies a post item.
<b>ReplyToItem</b>	<b>t:ReplyToItemType</b> (section <a href="#">2.2.4.56</a> )	Specifies a <b>ReplyToItem</b> response object.
<b>ForwardItem</b>	<b>t:ForwardItemType</b> (section <a href="#">2.2.4.33</a> )	Specifies a <b>ForwardItem</b>

Element name	Type	Description
		response object.
<b>ReplyAllToItem</b>	<b>t:ReplyAllToItemType</b> (section <a href="#">2.2.4.54</a> )	Specifies a <b>ReplyToAllItem</b> response object.
<b>AcceptItem</b>	<b>t:AcceptItemType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.1)	Specifies an <b>AcceptItem</b> response object.
<b>TentativelyAcceptItem</b>	<b>t:TentativelyAcceptItemType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.22)	Specifies a <b>TentativelyAcceptItem</b> response object.
<b>DeclineItem</b>	<b>t:DeclineItemType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.9)	Specifies a <b>DeclineItem</b> response object.
<b>CancelCalendarItem</b>	<b>t:CancelCalendarItemType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.8)	Specifies a <b>CancelCalendarItem</b> response object.
<b>RemoveItem</b>	<b>t:RemoveItemType</b> ( <a href="#">[MS-OXWSMTGS]</a> section 2.2.4.21)	Specifies a <b>RemoveItem</b> response object.
<b>SuppressReadReceipt</b>	<b>t:SuppressReadReceiptType</b> (section <a href="#">2.2.4.61</a> )	Specifies a <b>SuppressReadReceipt</b> response object.
<b>PostReplyItem</b>	<b>t:PostReplyItemType</b> ( <a href="#">[MS-OXWSPOST]</a> section 2.2.4.3)	Specifies a <b>PostReplyItem</b> response object.
<b>AcceptSharingInvitation</b>	<b>t:AcceptSharingInvitationType</b> (section <a href="#">2.2.4.3</a> )	Specifies an <b>AcceptSharingInvitation</b> response object.

### 2.2.4.43 t:NonEmptyArrayOfAttachmentsType Complex Type

The **NonEmptyArrayOfAttachmentsType** complex type specifies an array of items or files that are attached to an item.

```
<xs:complexType name="NonEmptyArrayOfAttachmentsType">
  <xs:choice
    minOccurs="1"
    maxOccurs="unbounded"
  >
    <xs:element name="ItemAttachment"
      type="t:ItemAttachmentType"
    />
    <xs:element name="FileAttachment"
      type="t:FileAttachmentType"
    />
  </xs:choice>
</xs:complexType>
```

The following table lists the child elements of the **NonEmptyArrayOfAttachmentsType** complex type.

Element name	Type	Description
<b>ItemAttachment</b>	<b>t:ItemAttachmentType</b> ( <a href="#">[MS-OXWSATT]</a> section 2.2.4.6)	Specifies an item attachment.
<b>FileAttachment</b>	<b>t:FileAttachmentType</b> ( <a href="#">[MS-OXWSATT]</a> section 2.2.4.5)	Specifies a file attachment.

#### 2.2.4.44 t:NonEmptyArrayOfPathsToElementType Complex Type

The **NonEmptyArrayOfPathsToElementType** complex type specifies additional properties to be returned in a response.

```
<xs:complexType name="NonEmptyArrayOfPathsToElementType">
  <xs:choice
    maxOccurs="unbounded"
  >
    <xs:element
      ref="t:Path"
    />
  </xs:choice>
</xs:complexType>
```

The following table lists the child elements of the **NonEmptyArrayOfPathsToElementType** complex type.

Element name	Type	Description
<b>t:Path</b>	<b>t:Path</b>	Specifies a property to be returned in a response.

#### 2.2.4.45 t:NonEmptyArrayOfRoleType Complex Type

The **NonEmptyArrayOfRoleType** complex type specifies one or more roles used by the caller. [<252>](#)

```
<xs:complexType name="NonEmptyArrayOfRoleType">
  <xs:sequence>
    <xs:element name="Role" type="xs:string" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

The following table lists and describes the child elements of the **NonEmptyArrayOfRoleType** complex type.

Element name	Type	Description
<b>Role</b>	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies a role identifier used by the caller.

#### 2.2.4.46 t:NumberedRecurrenceRangeType Complex Type

The **NumberedRecurrenceRangeType** complex type specifies the start date and number of occurrences of a recurring item.

```

<xs:complexType name="NumberedRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrenceRangeBaseType"
    >
      <xs:sequence>
        <xs:element name="NumberOfOccurrences"
          type="xs:int"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **NumberedRecurrenceRangeType** complex type.

Element name	Type	Description
<b>NumberOfOccurrences</b>	<b>xs:int</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the number of occurrences of a recurring item.

#### 2.2.4.47 t:PathToExceptionFieldType Complex Type

The **t:PathToExceptionFieldType** complex type specifies errors in a response.

```

<xs:complexType name="PathToExceptionFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:BasePathToElementType"
    >
      <xs:attribute name="FieldURI"
        type="t:ExceptionPropertyURIType"
        use="required"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Attribute name	Type
<b>FieldURI</b>	<b>t:ExceptionPropertyURIType</b> (section <a href="#">2.2.3.13</a> )

#### 2.2.4.48 t:PathToIndexedFieldType Complex Type

The **PathToIndexedFieldType** complex type specifies individual members of a dictionary property.

```

<xs:complexType name="PathToIndexedFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:BasePathToElementType"
    >
      <xs:attribute name="FieldURI"

```

```

        type="t:DictionaryURIType"
        use="required"
    />
    <xs:attribute name="FieldIndex"
        type="xs:string"
        use="required"
    />
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

Attribute name	Type	Description
FieldURI	<b>t:DictionaryURIType</b> (section <a href="#">2.2.3.8</a> )	Specifies the dictionary property. This attribute MUST be present.
FieldIndex	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the entry index in a dictionary. This attribute MUST be present.

#### 2.2.4.49 t:PathToUnindexedFieldType Complex Type

The **PathToUnindexedFieldType** complex type specifies frequently referenced properties.

```

<xs:complexType name="PathToUnindexedFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:BasePathToElementType"
    >
      <xs:attribute name="FieldURI"
        type="t:UnindexedFieldURIType"
        use="required"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Attributes

Name	Type	Description
<b>FieldURI</b>	<b>t:UnindexedFieldURIType</b> (section <a href="#">2.2.3.25</a> )	Specifies frequently referenced field URIs. This attribute MUST be present.

#### 2.2.4.50 t:RecurrencePatternBaseType Complex Type

The **RecurrencePatternBaseType** complex type specifies the base type for recurrence patterns.

```

<xs:complexType name="RecurrencePatternBaseType"
  abstract="true"
/>

```



### 2.2.4.51 t:RecurrenceRangeBaseType Complex Type

The **RecurrenceRangeBaseType** complex type specifies the base type for all recurrence patterns that have a start date.

```
<xs:complexType name="RecurrenceRangeBaseType"
  abstract="true"
  >
  <xs:sequence>
    <xs:element name="StartDate"
      type="xs:date"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **RecurrenceRangeBaseType** complex type.

Element name	Type	Description
<b>StartDate</b>	<b>xs:date</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the start date of a recurrence range.

### 2.2.4.52 t:RelativeMonthlyRecurrencePatternType Complex Type

The **RelativeMonthlyRecurrencePatternType** complex type specifies a relative monthly recurrence pattern.

```
<xs:complexType name="RelativeMonthlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:IntervalRecurrencePatternBaseType"
    >
    <xs:sequence>
      <xs:element name="DaysOfWeek"
        type="t:DayOfWeekType"
      />
      <xs:element name="DayOfWeekIndex"
        type="t:DayOfWeekIndexType"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>
```

The following table lists the child elements of the **RelativeMonthlyRecurrencePatternType** complex type.

Element name	Type	Description
<b>DaysOfWeek</b>	<b>t:DayOfWeekType</b> (section <a href="#">2.2.3.5</a> )	Specifies the days of the week that are used in a relative monthly recurrence pattern.
<b>DayOfWeekIndex</b>	<b>t:DayOfWeekIndexType</b> (section <a href="#">2.2.3.4</a> )	Specifies the week that is used in a relative monthly recurrence pattern.

### 2.2.4.53 t:RelativeYearlyRecurrencePatternType Complex Type

The **RelativeYearlyRecurrencePatternType** complex type specifies a relative yearly recurrence pattern.

```
<xs:complexType name="RelativeYearlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:RecurrencePatternBaseType"
    >
    <xs:sequence>
      <xs:element name="DaysOfWeek"
        type="t:DayOfWeekType"
      />
      <xs:element name="DayOfWeekIndex"
        type="t:DayOfWeekIndexType"
      />
      <xs:element name="Month"
        type="t:MonthNamesType"
      />
    </xs:sequence>
  </xs:complexContent>
</xs:complexType>
```

The following table lists the child elements of the **RelativeYearlyRecurrencePatternType** complex type.

Element name	Type	Description
<b>DaysOfWeek</b>	<b>t:DayOfWeekType</b> (section <a href="#">2.2.3.5</a> )	Specifies the days of the week that are used in a relative monthly recurrence pattern. This element <b>MUST</b> be present.
<b>DayOfWeekIndex</b>	<b>t:DayOfWeekIndexType</b> (section <a href="#">2.2.3.4</a> )	Specifies the week that is used in a relative monthly recurrence pattern. This element <b>MUST</b> be present.
<b>Month</b>	<b>t:MonthNamesType</b> (section <a href="#">2.2.3.19</a> )	Specifies the month when a yearly recurring item occurs. This element <b>MUST</b> be present.

### 2.2.4.54 t:ReplyAllToItemType Complex Type

The **ReplyAllToItemType** complex type specifies a response object that is used to reply to the sender and all recipients of an item.

```
<xs:complexType name="ReplyAllToItemType">
  <xs:complexContent>
    <xs:extension
      base="t:SmartResponseType"
    />
  </xs:complexContent>
</xs:complexType>
```

### 2.2.4.55 t:ReplyBody

The **ReplyBody** complex type specifies the body of the **OOF message** that is sent to users.

```
<xs:complexType name="ReplyBody">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Message" type="xs:string" />
  </xs:sequence>
  <xs:attribute ref="xml:lang" use="optional" />
</xs:complexType>
```

Element name	Type	Definition
<b>Message</b>	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	An HTML message that forms the body of the OOF message. This element is optional and SHOULD NOT exceed 128000 bytes.

Attribute	Definition
<b>xml:lang</b>	Specifies the language used in the OOF message. This attribute is optional. The possible values of this attribute are defined by <a href="#">[RFC3066]</a> .

### 2.2.4.56 t:ReplyToItemType Complex Type

The **ReplyToItemType** complex type specifies a reply response object that is used to reply to the sender of an item.

```
<xs:complexType name="ReplyToItemType">
  <xs:complexContent>
    <xs:extension base="t:SmartResponseType" />
  </xs:complexContent>
</xs:complexType>
```

### 2.2.4.57 m:ResponseMessageType Complex Type

The **ResponseMessageType** complex type specifies information about the response status for a single entity in a request.

```
<xs:complexType name="ResponseMessageType">
  <xs:sequence
    minOccurs="0"
  >
    <xs:element name="MessageText"
      type="xs:string"
      minOccurs="0"
    />
    <xs:element name="ResponseCode"
```

```

        type="m:ResponseCodeType"
        minOccurs="0"
      />
      <xs:element name="DescriptiveLinkKey"
        type="xs:int"
        minOccurs="0"
      />
      <xs:element name="MessageXml"
        minOccurs="0"
      >
        <xs:complexType>
          <xs:sequence>
            <xs:any
              process_contents="lax"
              minOccurs="0"
              maxOccurs="unbounded"
            />
          </xs:sequence>
          <xs:attribute name="ResponseClass"
            type="t:ResponseClassType"
            use="required"
          />
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>

```

The following table lists the child elements of the **ResponseMessageType** complex type.

Element name	Type	Description
<b>MessageText</b>	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies a text description of the status of a response.
<b>ResponseCode</b>	<b>m:ResponseCodeType</b> (section <a href="#">2.2.3.23</a> )	Specifies the error code that identifies the specific error that the request encountered, if any.
<b>DescriptiveLinkKey</b>	<b>xs:int</b> ( <a href="#">[XMLSCHEMA2]</a> )	This element is not used.
<b>MessageXml</b>	N/A	Specifies additional error response information.

#### Attributes

Attribute name	Type	Description
ResponseClass	<b>t:ResponseClassType</b> (section <a href="#">2.2.3.22</a> )	Represents the status of the response. The following values are valid for this attribute: <ul style="list-style-type: none"> <li>▪ Success</li> <li>▪ Warning</li> <li>▪ Error</li> </ul>

Attribute name	Type	Description
		This attribute MUST be present.

### 2.2.4.58 t:ResponseObjectCoreType Complex Type

The **ResponseObjectCoreType** complex type specifies the base type for response objects.

```
<xs:complexType name="ResponseObjectCoreType"
  abstract="true"
>
  <xs:complexContent>
    <xs:extension
      base="t:MessageType"
    >
      <xs:sequence>
        <xs:element name="ReferenceItemId"
          type="t:ItemIdType"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists the child elements of the **ResponseObjectCoreType** complex type.

Element name	Type	Description
<b>ReferenceItemId</b>	<b>t:ItemIdType</b> ( <a href="#">[MS-OXWSCORE]</a> section 2.2.4.19)	Specifies the item identifier that is related to a response object.

### 2.2.4.59 t:ResponseType Complex Type

The **ResponseType** complex type specifies the base type for response objects.

```
<xs:complexType name="ResponseType"
  abstract="true"
>
  <xs:complexContent>
    <xs:extension
      base="t:ResponseObjectCoreType"
    >
      <xs:attribute name="ObjectName"
        type="xs:string"
        use="optional"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

#### Attributes

Name	Type	Description
<b>ObjectName</b>	<b>xs:string</b> ( <a href="#">XMLSCHEMA21</a> )	Specifies the name of the reply object class as an English-language string.

#### 2.2.4.60 t:SingleRecipientType Complex Type

The **SingleRecipientType** complex type specifies the e-mail address information for a single message recipient.

```
<xs:complexType name="SingleRecipientType">
  <xs:choice>
    <xs:element name="Mailbox"
      type="t:EmailAddressType"
    />
  </xs:choice>
</xs:complexType>
```

The following table lists the child elements of the **SingleRecipientType** complex type.

Element name	Type	Description
<b>Mailbox</b>	<b>t:EmailAddressType</b> (section <a href="#">2.2.4.27</a> )	Specifies the e-mail address of a recipient.

#### 2.2.4.61 t:SuppressReadReceiptType Complex Type

The **SuppressReadReceiptType** complex type specifies the suppress read receipt response object.

```
<xs:complexType name="SuppressReadReceiptType">
  <xs:complexContent>
    <xs:extension
      base="t:ReferenceItemResponseType"
    />
  </xs:complexContent>
</xs:complexType>
```

#### 2.2.4.62 t:UserIdType Complex Type

The **UserIdType** complex type specifies a user identifier.

```
<xs:complexType name="UserIdType">
  <xs:sequence>
    <xs:element name="SID"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="PrimarySmtpAddress"
      type="xs:string"
      minOccurs="0"
      maxOccurs="1"
    />
  </xs:sequence>
</xs:complexType>
```

```

/>
<xs:element name="DisplayName"
  type="xs:string"
  minOccurs="0"
  maxOccurs="1"
/>
<xs:element name="DistinguishedUser"
  type="t:DistinguishedUserType"
  minOccurs="0"
  maxOccurs="1"
/>
<xs:element name="ExternalUserIdentity"
  type="xs:string"
  minOccurs="0"
  maxOccurs="1"
/>
</xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **UserIdType** complex type.

Element name	Type	Description
<b>SID</b>	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the security descriptor definition language (SSDL) form of the security identifier (SID) for a user.
<b>PrimarySmtpAddress</b>	<b>xs:string</b>	Specifies the primary SMTP address of an account.
<b>DisplayName</b>	<b>xs:string</b>	Specifies the user name for display.
<b>DistinguishedUser</b>	<b>t:DistinguishedUserType</b> (section <a href="#">2.2.3.12</a> )	Specifies a value that identifies the Anonymous and Default user accounts for delegate access.
<b>ExternalUserIdentity</b>	<b>xs:string</b>	Specifies an external user identity.

### 2.2.4.63 t:Value Complex Type

The **Value** complex type specifies the name and value of a property that is returned in an error response.

```

<xs:complexType name="Value">
  <xs:simpleContent>
    <xs:extension
      base="xs:string"
    >
      <xs:attribute name="Name"
        type="xs:string"
        use="required"
      />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

```

## Attributes

Name	Type	Description
Name	xs:string ( <a href="#">[XMLSCHEMA2]</a> )	Specifies a property name.

### 2.2.4.64 t:WeeklyRecurrencePatternType Complex Type

The **WeeklyRecurrencePatternType** complex type specifies the interval, in weeks, at which an item recurs, and the days on which the item recurs.

```
<xs:complexType name="WeeklyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension
      base="t:IntervalRecurrencePatternBaseType"
    >
      <xs:sequence>
        <xs:element name="DaysOfWeek"
          type="t:DaysOfWeekType"
        />
        <xs:element name="FirstDayOfWeek"
          type="t:DayOfWeekType"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists the child elements of the **WeeklyRecurrencePatternType** complex type.

Element name	Type	Description
<b>DaysOfWeek</b>	<b>t:DaysOfWeekType</b> (section <a href="#">2.2.3.6</a> )	Specifies the days of the week that are in the weekly recurrence pattern.
<b>FirstDayOfWeek</b>	<b>t:DayOfWeekType</b> (section <a href="#">2.2.3.5</a> )	Specifies the first day of the week. <a href="#">&lt;253&gt;</a>

### 2.2.4.65 t:WellKnownResponseType Complex Type

The **WellKnownResponseType** complex type specifies the base type for calendar item related response objects.

```
<xs:complexType name="WellKnownResponseType">
  <xs:complexContent>
    <xs:restriction
      base="t:ResponseType"
    >
      <xs:sequence>
        <xs:element name="ItemClass"

```



```

        type="t:ItemClassType"
        minOccurs="0"
      />
    <xs:element name="Sensitivity"
      type="t:SensitivityChoicesType"
      minOccurs="0"
    />
    <xs:element name="Body"
      type="t:BodyType"
      minOccurs="0"
    />
    <xs:element name="Attachments"
      type="t:NonEmptyArrayOfAttachmentsType"
      minOccurs="0"
    />
    <xs:element name="InternetMessageHeaders"
      type="t:NonEmptyArrayOfInternetHeadersType"
      minOccurs="0"
    />
    <xs:element name="Sender"
      type="t:SingleRecipientType"
      minOccurs="0"
    />
    <xs:element name="ToRecipients"
      type="t:ArrayOfRecipientsType"
      minOccurs="0"
    />
    <xs:element name="CcRecipients"
      type="t:ArrayOfRecipientsType"
      minOccurs="0"
    />
    <xs:element name="BccRecipients"
      type="t:ArrayOfRecipientsType"
      minOccurs="0"
    />
    <xs:element name="IsReadReceiptRequested"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="IsDeliveryReceiptRequested"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="From"
      type="t:SingleRecipientType"
      minOccurs="0"
    />
    <xs:element name="ReferenceItemId"
      type="t:ItemIdType"
      minOccurs="0"
    />
  </xs:sequence>
  <xs:attribute name="ObjectName"
    type="xs:string"
    use="prohibited"
  />
</xs:restriction>
</xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **WellKnownResponseType** complex type.

Element name	Type	Description
<b>ItemClass</b>	<b>t:ItemClassType</b> ( <a href="#">[MS-OXWSCORE]</a> section 2.2.5.4)	Specifies the item class.
<b>Sensitivity</b>	<b>t:SensitivityChoicesType</b> (section <a href="#">2.2.3.24</a> )	Specifies the item sensitivity level.
<b>Body</b>	<b>t:BodyType</b> (section <a href="#">2.2.4.17</a> )	Specifies the body content.
<b>Attachments</b>	<b>t:NonEmptyArrayOfAttachmentsType</b> (section <a href="#">2.2.4.43</a> )	Specifies the attachments on a response object.
<b>InternetMessageHeaders</b>	<b>t:NonEmptyArrayOfInternetHeadersType</b> ( <a href="#">[MS-OXWSCORE]</a> section 2.2.4.12)	Specifies an array of type <b>InternetHeaderType</b> that represents the collection of all Internet message headers that are contained in an item.
<b>Sender</b>	<b>t:SingleRecipientType</b> (section <a href="#">2.2.4.60</a> )	Specifies the sender of a message.
<b>ToRecipients</b>	<b>t:ArrayOfRecipientsType</b> (section <a href="#">2.2.4.9</a> )	Specifies a collection of recipients of an item.
<b>CcRecipients</b>	<b>t:ArrayOfRecipientsType</b>	Specifies a collection of carbon copy (Cc) recipients of an item.
<b>BccRecipients</b>	<b>t:ArrayOfRecipientsType</b>	Specifies a collection of blind carbon copy (Bcc) recipients of an item.
<b>IsReadReceiptRequested</b>	<b>xs:boolean</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies whether a read receipt is requested.
<b>IsDeliveryReceiptRequested</b>	<b>xs:boolean</b>	Specifies whether a delivery receipt is requested.
<b>From</b>	<b>t:SingleRecipientType</b>	Specifies the addressee who sent a message.
<b>ReferenceItemId</b>	<b>t:ItemIdType</b> ( <a href="#">[MS-OXWSCORE]</a> section 2.2.4.19)	Specifies the item identifier that is related to a response object.

## Attributes

Name	Type	Description
<b>ObjectName</b>	<b>xs:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the name of the reply object class as an English-language string.

## 2.2.5 Elements

### 2.2.5.1 t:DateTimePrecision Element

The **DateTimePrecision** element specifies precision of **DateTime** values that are returned in responses. [<254>](#) This element is optional.

```
<xs:element name="DateTimePrecision" type="t:DateTimePrecisionType" />
```

### 2.2.5.2 t:ExceptionFieldURI Element

The **ExceptionFieldURI** element specifies particular errors in a request.

```
<xs:element name="t:ExceptionFieldURI"  
  type="t:PathToExceptionFieldType"  
/>
```

### 2.2.5.3 t:ExchangeImpersonation Element

The **ExchangeImpersonation** element is used in the SOAP header of a request. When the **ExchangeImpersonation** element is present, the caller is trying to impersonate the account that is specified by the **ConnectingSID** element in the **t:ExchangeImpersonationType** complex type as specified in section [2.2.4.29](#).

```
<xs:element name="t:ExchangeImpersonation"  
  type="t:ExchangeImpersonationType"  
/>
```

### 2.2.5.4 t:FieldURI Element

The **FieldURI** element specifies frequently referenced properties by URI.

```
<xs:element name="t:FieldURI"  
  type="t:PathToUnindexedFieldType"  
/>
```

The full syntax for this element is `<xs:element name="FieldURI" type="t:PathToUnindexedFieldType" substitutionGroup="t:Path"/>`

### 2.2.5.5 t:IndexedFieldURI Element

The **IndexedFieldURI** element specifies individual members of a dictionary.

```
<xs:element name="t:IndexedFieldURI"
  type="t:PathToIndexedFieldType"
 />
```

The syntax for this element is `<xs:element name="IndexedFieldURI" type="t:PathToIndexedFieldType" substitutionGroup="t:Path" />`.

### 2.2.5.6 t:MailboxCulture Element

The **MailboxCulture** element specifies the culture to be used when opening a mailbox. The **MailboxCulture** element occurs in the SOAP header.

```
<xs:element name="t:MailboxCulture"
  type="t:MailboxCultureType"
 />
```

### 2.2.5.7 t:ManagementRole Element

The **ManagementRole** element specifies a SOAP header that contains roles used by the calling account. [<255>](#)

```
<xs:element name="ManagementRole" type="t:ManagementRoleType" />
```

### 2.2.5.8 t:Path Element

The **Path** element specifies the base schema type for all property identifiers. This type is abstract and will never occur directly within instance documents. This type defines a substitution group.

```
<xs:element name="t:Path"
  type="t:BasePathToElementType"
  abstract="true"
 />
```

### 2.2.5.9 t:RequestServerVersion Element

The **RequestServerVersion** element specifies the versioning information that identifies the schema version to be targeted for a request. [<256>](#)

```
<xs:element name="t:RequestServerVersion">
  <xs:complexType>
    <xs:attribute name="Version"
      type="t:ExchangeVersionType"
      use="required"
      fixed="Exchange2013"
    />
    <xs:anyAttribute
      namespace="http://schemas.xmlsoap.org/soap/envelope/"
    />
  </xs:complexType>
```

```
</xs:element>
```

The following table lists the attributes of the **RequestServerVersion** element.

Attribute name	Type	Description
<b>Version</b>	<b>t:ExchangeVersionType</b>	Specifies the target schema version.

### 2.2.5.10 t:ServerVersionInfo Element

The **ServerVersionInfo** element specifies the version number of the server.

```
<xs:element name="t:ServerVersionInfo">
  <xs:complexType>
    <xs:attribute name="MajorVersion"
      type="xs:int"
      use="optional"
    />
    <xs:attribute name="MinorVersion"
      type="xs:int"
      use="optional"
    />
    <xs:attribute name="MajorBuildNumber"
      type="xs:int"
      use="optional"
    />
    <xs:attribute name="MinorBuildNumber"
      type="xs:int"
      use="optional"
    />
    <xs:attribute name="Version"
      type="xs:string"
      use="optional"
    />
  </xs:complexType>
</xs:element>
```

#### Attributes

Name	Type
<b>MajorVersion</b>	<b>xs:int</b> ( <a href="#">[XMLSCHEMA2]</a> )
<b>MinorVersion</b>	<b>xs:int</b>
<b>MajorBuildNumber</b>	<b>xs:int</b>
<b>MinorBuildNumber</b>	<b>xs:int</b>
<b>Version</b>	<b>xs:string</b> ( <a href="#">[XMLSCHEMA2]</a> )

### 2.2.5.11 Value Element

The **Value** element specifies the value of an extended property.

```
<xs:element name="Value"
  type="t:Value"
/>
```

### 2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

### 2.2.7 Groups

#### 2.2.7.1 t:RecurrencePatternTypes Group

The **RecurrencePatternTypes** group specifies the recurrence pattern for calendar items and meeting requests.

```
<xs:group name="t:RecurrencePatternTypes">
  <xs:sequence>
    <xs:choice>
      <xs:element name="t:RelativeYearlyRecurrence"
        type="t:RelativeYearlyRecurrencePatternType"
      />
      <xs:element name="AbsoluteYearlyRecurrence"
        type="t:AbsoluteYearlyRecurrencePatternType"
      />
      <xs:element name="RelativeMonthlyRecurrence"
        type="t:RelativeMonthlyRecurrencePatternType"
      />
      <xs:element name="AbsoluteMonthlyRecurrence"
        type="t:AbsoluteMonthlyRecurrencePatternType"
      />
      <xs:element name="WeeklyRecurrence"
        type="t:WeeklyRecurrencePatternType"
      />
      <xs:element name="DailyRecurrence"
        type="t:DailyRecurrencePatternType"
      />
    </xs:choice>
  </xs:sequence>
</xs:group>
```

The following table lists the child elements of the **RecurrencePatternTypes** complex type.

Element name	Type	Description
<b>t:RelativeYearlyRecurrence</b>	<b>t:RelativeYearlyRecurrencePatternType</b> (section <a href="#">2.2.4.53</a> )	Specifies a relative yearly recurrence pattern.
<b>AbsoluteYearlyRecurrence</b>	<b>t:AbsoluteYearlyRecurrencePatternType</b>	Specifies a yearly

Element name	Type	Description
	(section <a href="#">2.2.4.2</a> )	recurrence pattern.
<b>RelativeMonthlyRecurrence</b>	<b>t:RelativeMonthlyRecurrencePatternType</b> (section <a href="#">2.2.4.52</a> )	Specifies a relative monthly recurrence pattern for a recurring calendar item.
<b>AbsoluteMonthlyRecurrence</b>	<b>t:AbsoluteMonthlyRecurrencePatternType</b> (section <a href="#">2.2.4.1</a> )	Specifies a monthly recurrence pattern.
<b>WeeklyRecurrence</b>	<b>t:WeeklyRecurrencePatternType</b> (section <a href="#">2.2.4.64</a> )	Specifies the interval, in weeks, at which a calendar item recurs, and the days of the week on which it occurs.
<b>DailyRecurrence</b>	<b>t:DailyRecurrencePatternType</b> (section <a href="#">2.2.4.21</a> )	Specifies the interval, in days, at which a calendar item recurs.

### 2.2.7.2 t:RecurrenceRangeTypes Group

The **RecurrenceRangeTypes** group specifies recurrence patterns with numbered recurrences, non-ending recurrence patterns, and recurrence patterns with a set start and end date.

```
<xs:group name="t:RecurrenceRangeTypes">
  <xs:sequence>
    <xs:choice>
      <xs:element name="NoEndRecurrence"
        type="t:NoEndRecurrenceRangeType"
      />
      <xs:element name="EndDateRecurrence"
        type="t:EndDateRecurrenceRangeType"
      />
      <xs:element name="NumberedRecurrence"
        type="t:NumberedRecurrenceRangeType"
      />
    </xs:choice>
  </xs:sequence>
</xs:group>
```

The following table lists the child elements of the **RecurrenceRangeTypes** complex type.

Element name	Type	Description
<b>NoEndRecurrence</b>	<b>t:NoEndRecurrenceRangeType</b> (section <a href="#">2.2.4.41</a> )	Specifies a recurrence pattern that does not have a defined end date.
<b>EndDateRecurrence</b>	<b>t:EndDateRecurrenceRangeType</b> (section <a href="#">2.2.4.28</a> )	Specifies the start date and the end date of an item recurrence

Element name	Type	Description
		pattern.
<b>NumberedRecurrence</b>	<b>t:NumberedRecurrenceRangeType</b> (section <a href="#">2.2.4.46</a> )	Specifies the start date and the number of occurrences of a recurring item.

### 2.2.7.3 t:TimeChangePatternTypes Group

The **TimeChangePatternTypes** group specifies the date when the time changes from standard time or daylight saving time.

```
<xs:group name="t:TimeChangePatternTypes">
  <xs:sequence>
    <xs:choice>
      <xs:element name="RelativeYearlyRecurrence"
        type="t:RelativeYearlyRecurrencePatternType"
      />
      <xs:element name="AbsoluteDate"
        type="xs:date"
      />
    </xs:choice>
  </xs:sequence>
</xs:group>
```

The following table lists the child elements of the **TimeChangePatternTypes** complex type.

Element name	Type	Description
<b>RelativeYearlyRecurrence</b>	<b>t:RelativeYearlyRecurrencePatternType</b> (section <a href="#">2.2.4.53</a> )	Specifies a relative yearly recurrence pattern for a time zone transition date.
<b>AbsoluteDate</b>	<b>xs:date</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the date when the time changes from standard time or daylight saving time.

## 2.2.8 Attribute Groups

### 2.2.8.1 t:FindResponsePagingAttributes Attribute Group

The **FindResponsePagingAttributes** attribute group specifies paging and count information for a result set.

```
<xs:attributeGroup name="t:FindResponsePagingAttributes">
  <xs:attribute name="IndexedPagingOffset"
    type="xs:int"
    use="optional"
  />
  <xs:attribute name="NumeratorOffset"
    type="xs:int"
  />
</xs:attributeGroup>
```



```

        use="optional"
    />
    <xs:attribute name="AbsoluteDenominator"
        type="xs:int"
        use="optional"
    />
    <xs:attribute name="IncludesLastItemInRange"
        type="xs:int"
        use="optional"
    />
    <xs:attribute name="TotalItemsInView"
        type="xs:int"
        use="optional"
    />
</xs:attributeGroup>

```

## Attributes

Name	Type	Description
<b>IndexedPagingOffset</b>	<b>xs:int</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the next index that SHOULD be used for the next request when using an indexed paging view.
<b>NumeratorOffset</b>	<b>xs:int</b>	<b>Specifies the new numerator value to use for the next request when using fraction page views.</b>
<b>AbsoluteDenominator</b>	<b>xs:int</b>	<b>Specifies the next denominator to use for the next request when doing fractional paging.</b>
<b>IncludesLastItemInRange</b>	<b>xs:int</b>	<b>Specifies whether the current results contain the last item in the query, such that no further paging is required.</b>
<b>TotalItemsInView</b>	<b>xs:int</b>	<b>Specifies the total number of results.</b>

## **3 Protocol Details**

This document specifies common XML schema types and elements and does not have any protocol details.

### **3.1 Server Details**

This document specifies common XML schema types and elements and does not have any server protocol details.

#### **3.1.1 Abstract Data Model**

None.

#### **3.1.2 Timers**

None.

#### **3.1.3 Initialization**

None.

#### **3.1.4 Message Processing Events and Sequencing Rules**

None.

#### **3.1.5 Timer Events**

None.

#### **3.1.6 Other Local Events**

None.

## 4 Protocol Examples

None.

## **5 Security**

### **5.1 Security Considerations for Implementers**

None.

### **5.2 Index of Security Parameters**

None.

## 6 Appendix A: Full WSDL

The XML files that are listed in the following table are required in order to implement the functionality described in this document.

File name	Description	Section
MS-OXWSCDATA-messages.xsd	Contains the XML schema message definitions.	<a href="#">7.1</a>
MS-OXWSCDATA-types.xsd	Contains the XML schema type definitions.	<a href="#">7.2</a>

These files have to be placed in a common folder in order for any referencing WSDL to validate and operate. Also, any schema files that are included in or imported into the MS-OXWSCDATA-types.xsd or MS-OXWSCDATA-messages.xsd schemas have to be placed in the common folder along with the files listed in the table.

This protocol specification does not define a WSDL file.

## 7 Appendix B: Full XML Schema

For ease of implementation, the following sections provide the full XML schema for this protocol.

Schema name	Prefix	Section
Messages schema	m:	<a href="#">7.1</a>
Types schema	t:	<a href="#">7.2</a>

These files have to be placed in a common folder in order for any referencing WSDL to validate and operate. Also, any schema files that are included in or imported into the MS-OXWSCDATA-types.xsd or MS-OXWCDATA-messages.xsd schemas have to be placed in the common folder along with the files listed in the table.

### 7.1 Messages Schema

This section provides the contents of the MS-OXWSCDATA-messages.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSCDATA-messages.xsd includes or imports the files listed in the following table. To operate correctly, these files have to be present in the folder that contains the types and messages schema files.

File name	Defining specification/section
MS-OXWSCDATA-types.xsd	section <a href="#">7.2</a>
MS-OXWSCORE-messages.xsd	<a href="#">[MS-OXWSCORE]</a> section 7.1
MS-OXWSFOLD-messages.xsd	<a href="#">[MS-OXWSFOLD]</a> section 7.1
MS-OXWSSRCH-messages.xsd	<a href="#">[MS-OXWSSRCH]</a> section 7.1
MS-OXWSATT-messages.xsd	<a href="#">[MS-OXWSATT]</a> section 7.1
MS-OXWSRSLNM-messages.xsd	<a href="#">[MS-OXWSRSLNM]</a> section 7.1
MS-OXWSDLIST-messages.xsd	<a href="#">[MS-OXWSDLIST]</a> section 6.3
MS-OXWSGTZ-messages.xsd	<a href="#">[MS-OXWSGTZ]</a> section 7.1
MS-OXWSNTIF-messages.xsd	<a href="#">[MS-OXWSNTIF]</a> section 7.1
MS-OXWSPSNTIF-messages.xsd	<a href="#">[MS-OXWSPSNTIF]</a> section 7.1
MS-OXWSSYNC-messages.xsd	<a href="#">[MS-OXWSSYNC]</a> section 7.1
MS-OXWSCVTID-messages.xsd	<a href="#">[MS-OXWSCVTID]</a> section 7.1
MS-OXWSMSHR-messages.xsd	<a href="#">[MS-OXWSMSHR]</a> section 7.1
MS-OXWSGTRM-messages.xsd	<a href="#">[MS-OXWSGTRM]</a> section 7.1
MS-OXWSBTRF-messages.xsd	<a href="#">[MS-OXWSBTRF]</a> section 7.1
MS-OXWSPED-messages.xsd	<a href="#">[MS-OXWSPED]</a> section 7

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
elementFormDefault="qualified" version="Exchange2013" id="messages">
  <xs:import namespace="http://schemas.microsoft.com/exchange/services/2006/types"
schemaLocation="MS-OXWSCDATA-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSCORE-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSFOLD-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSSRCH-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSATT-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSRSLNM-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSDLIST-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSGTZ-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSNTIF-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSPSNTIF-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSSYNC-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSCVTID-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSMSHR-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSGTRM-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSBTRF-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSGPED-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSCEXT-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSEDISC-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSGNI-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSPERS-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSCONV-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSURPT-messages.xsd"/>
  <xs:complexType name="ArrayOfResponseMessagesType">
    <xs:choice maxOccurs="unbounded">
      <xs:element name="CreateItemResponseMessage" type="m:ItemInfoResponseMessageType"/>
      <xs:element name="DeleteItemResponseMessage" type="m:ResponseMessageType"/>
      <xs:element name="GetItemResponseMessage" type="m:ItemInfoResponseMessageType"/>
      <xs:element name="UpdateItemResponseMessage" type="m:UpdateItemResponseMessageType"/>
      <xs:element name="UpdateItemInRecoverableItemsResponseMessage"
type="m:UpdateItemInRecoverableItemsResponseMessageType"/>
      <xs:element name="SendItemResponseMessage" type="m:ResponseMessageType"/>
      <xs:element name="DeleteFolderResponseMessage" type="m:ResponseMessageType"/>
      <xs:element name="EmptyFolderResponseMessage" type="m:ResponseMessageType"/>
      <xs:element name="CreateFolderResponseMessage" type="m:FolderInfoResponseMessageType"/>
      <xs:element name="GetFolderResponseMessage" type="m:FolderInfoResponseMessageType"/>
      <xs:element name="FindFolderResponseMessage" type="m:FindFolderResponseMessageType"/>
      <xs:element name="UpdateFolderResponseMessage" type="m:FolderInfoResponseMessageType"/>
      <xs:element name="MoveFolderResponseMessage" type="m:FolderInfoResponseMessageType"/>
      <xs:element name="CopyFolderResponseMessage" type="m:FolderInfoResponseMessageType"/>
      <xs:element name="CreateFolderPathResponseMessage"
type="m:FolderInfoResponseMessageType"/>
      <xs:element name="CreateAttachmentResponseMessage"
type="m:AttachmentInfoResponseMessageType"/>
      <xs:element name="DeleteAttachmentResponseMessage"
type="m>DeleteAttachmentResponseMessageType"/>
      <xs:element name="GetAttachmentResponseMessage"
type="m:AttachmentInfoResponseMessageType"/>
      <xs:element name="UploadItemsResponseMessage" type="m:UploadItemsResponseMessageType"/>
      <xs:element name="ExportItemsResponseMessage" type="m:ExportItemsResponseMessageType"/>
      <xs:element name="MarkAllItemsAsReadResponseMessage" type="m:ResponseMessageType"/>
      <xs:element name="GetClientAccessTokenResponseMessage"
type="m:GetClientAccessTokenResponseMessageType"/>
      <xs:element name="GetAppManifestsResponseMessage" type="m:ResponseMessageType"/>
    </xs:choice>
  </xs:complexType>

```

```

    <xs:element name="GetClientExtensionResponseMessage" type="m:ResponseMessageType"/>
  <xs:element name="GetClientExtensionResponseMessage" type="m:ResponseMessageType"/>
  <xs:element name="FindItemResponseMessage" type="m:FindItemResponseMessageType"/>
  <xs:element name="MoveItemResponseMessage" type="m:ItemInfoResponseMessageType"/>
  <xs:element name="ArchiveItemResponseMessage" type="m:ItemInfoResponseMessageType"/>
  <xs:element name="CopyItemResponseMessage" type="m:ItemInfoResponseMessageType"/>
  <xs:element name="ResolveNamesResponseMessage"
type="m:ResolveNamesResponseMessageType"/>
  <xs:element name="ExpandDLResponseMessage" type="m:ExpandDLResponseMessageType"/>
  <xs:element name="GetServerTimeZonesResponseMessage"
type="m:GetServerTimeZonesResponseMessageType"/>
  <xs:element name="GetEventsResponseMessage" type="m:GetEventsResponseMessageType"/>
  <xs:element name="GetStreamingEventsResponseMessage"
type="m:GetStreamingEventsResponseMessageType"/>
  <xs:element name="SubscribeResponseMessage" type="m:SubscribeResponseMessageType"/>
  <xs:element name="UnsubscribeResponseMessage" type="m:ResponseMessageType"/>
  <xs:element name="SendNotificationResponseMessage"
type="m:SendNotificationResponseMessageType"/>
  <xs:element name="SyncFolderHierarchyResponseMessage"
type="m:SyncFolderHierarchyResponseMessageType"/>
  <xs:element name="SyncFolderItemsResponseMessage"
type="m:SyncFolderItemsResponseMessageType"/>
  <xs:element name="CreateManagedFolderResponseMessage"
type="m:FolderInfoResponseMessageType"/>
  <xs:element name="ConvertIdResponseMessage" type="m:ConvertIdResponseMessageType"/>
  <xs:element name="GetSharingMetadataResponseMessage"
type="m:GetSharingMetadataResponseMessageType"/>
  <xs:element name="RefreshSharingFolderResponseMessage"
type="m:RefreshSharingFolderResponseMessageType"/>
  <xs:element name="GetSharingFolderResponseMessage"
type="m:GetSharingFolderResponseMessageType"/>
  <xs:element name="CreateUserConfigurationResponseMessage"
type="m:ResponseMessageType"/>
  <xs:element name="DeleteUserConfigurationResponseMessage"
type="m:ResponseMessageType"/>
  <xs:element name="UpdateUserConfigurationResponseMessage"
type="m:ResponseMessageType"/>
  <xs:element name="GetRoomListsResponse" type="m:GetRoomListsResponseMessageType"/>
  <xs:element name="GetRoomsResponse" type="m:GetRoomsResponseMessageType"/>
  <xs:element name="ApplyConversationActionResponseMessage"
type="m:ResponseMessageType"/>
  <xs:element name="GetSearchableMailboxesResponseMessage"
type="m:GetSearchableMailboxesResponseMessageType"/>
  <xs:element name="SearchMailboxesResponseMessage"
type="m:SearchMailboxesResponseMessageType"/>
  <xs:element name="GetDiscoverySearchConfigurationResponseMessage"
type="m:GetDiscoverySearchConfigurationResponseMessageType"/>
  <xs:element name="GetHoldOnMailboxesResponseMessage"
type="m:GetHoldOnMailboxesResponseMessageType"/>
  <xs:element name="SetHoldOnMailboxesResponseMessage"
type="m:SetHoldOnMailboxesResponseMessageType"/>
  <xs:element name="GetNonIndexableItemStatisticsResponseMessage"
type="m:GetNonIndexableItemStatisticsResponseMessageType"/>
  <!-- GetNonIndexableItemDetails response -->
  <xs:element name="GetNonIndexableItemDetailsResponseMessage"
type="m:GetNonIndexableItemDetailsResponseMessageType"/>
  <xs:element name="FindPeopleResponseMessage" type="m:FindPeopleResponseMessageType"/>
  <xs:element name="GetPasswordExpirationDateResponse"
type="m:GetPasswordExpirationDateResponseMessageType"/>
  <xs:element name="GetPersonaResponseMessage" type="m:GetPersonaResponseMessageType"/>

```



```

    <xs:element name="GetConversationItemsResponseMessage"
type="m:GetConversationItemsResponseMessageType"/>
    <xs:element name="GetUserRetentionPolicyTagsResponseMessage"
type="m:GetUserRetentionPolicyTagsResponseMessageType"/>
    <xs:element name="GetUserPhotoResponseMessage"
type="m:GetUserPhotoResponseMessageType"/>
    <xs:element name="MarkAsJunkResponseMessage" type="m:MarkAsJunkResponseMessageType"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="BaseRequestType" abstract="true"/>
<xs:complexType name="BaseResponseMessageType">
  <xs:sequence>
    <xs:element name="ResponseMessages" type="m:ArrayOfResponseMessagesType"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ItemInfoResponseMessageType">
  <xs:complexContent>
    <xs:extension base="m:ResponseMessageType">
      <xs:sequence>
        <xs:element name="Items" type="t:ArrayOfRealItemsType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="ResponseMessageType">
  <xs:sequence minOccurs="0">
    <xs:element name="MessageText" type="xs:string" minOccurs="0"/>
    <xs:element name="ResponseCode" type="m:ResponseCodeType" minOccurs="0"/>
    <xs:element name="DescriptiveLinkKey" type="xs:int" minOccurs="0"/>
    <xs:element name="MessageXml" minOccurs="0">
      <xs:complexType>
        <xs:sequence>
          <xs:any processContents="lax" minOccurs="0" maxOccurs="unbounded"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="ResponseClass" type="t:ResponseClassType" use="required"/>
</xs:complexType>
<xs:simpleType name="ResponseCodeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NoError"/>
    <xs:enumeration value="ErrorAccessDenied"/>
    <xs:enumeration value="ErrorAccessModeSpecified"/>
    <xs:enumeration value="ErrorAccountDisabled"/>
    <xs:enumeration value="ErrorAddDelegatesFailed"/>
    <xs:enumeration value="ErrorAddressSpaceNotFound"/>
    <xs:enumeration value="ErrorADOperation"/>
    <xs:enumeration value="ErrorADSessionFilter"/>
    <xs:enumeration value="ErrorADUnavailable"/>
    <xs:enumeration value="ErrorAutoDiscoverFailed"/>
    <xs:enumeration value="ErrorAffectedTaskOccurrencesRequired"/>
    <xs:enumeration value="ErrorAttachmentNestLevelLimitExceeded"/>
    <xs:enumeration value="ErrorAttachmentSizeLimitExceeded"/>
    <xs:enumeration value="ErrorArchiveFolderPathCreation"/>
    <xs:enumeration value="ErrorArchiveMailboxNotEnabled"/>
    <xs:enumeration value="ErrorArchiveMailboxServiceDiscoveryFailed"/>
    <xs:enumeration value="ErrorAvailabilityConfigNotFound"/>
    <xs:enumeration value="ErrorBatchProcessingStopped"/>
  </xs:restriction>
</xs:simpleType>

```

```
<xs:enumeration value="ErrorCalendarCannotMoveOrCopyOccurrence"/>
<xs:enumeration value="ErrorCalendarCannotUpdateDeletedItem"/>
<xs:enumeration value="ErrorCalendarCannotUseIdForOccurrenceId"/>
<xs:enumeration value="ErrorCalendarCannotUseIdForRecurringMasterId"/>
<xs:enumeration value="ErrorCalendarDurationIsTooLong"/>
<xs:enumeration value="ErrorCalendarEndDateIsEarlierThanStartDate"/>
<xs:enumeration value="ErrorCalendarFolderIsInvalidForCalendarView"/>
<xs:enumeration value="ErrorCalendarInvalidAttributeValue"/>
<xs:enumeration value="ErrorCalendarInvalidDayForTimeChangePattern"/>
<xs:enumeration value="ErrorCalendarInvalidDayForWeeklyRecurrence"/>
<xs:enumeration value="ErrorCalendarInvalidPropertyState"/>
<xs:enumeration value="ErrorCalendarInvalidPropertyValue"/>
<xs:enumeration value="ErrorCalendarInvalidRecurrence"/>
<xs:enumeration value="ErrorCalendarInvalidTimeZone"/>
<xs:enumeration value="ErrorCalendarIsCancelledForAccept"/>
<xs:enumeration value="ErrorCalendarIsCancelledForDecline"/>
<xs:enumeration value="ErrorCalendarIsCancelledForRemove"/>
<xs:enumeration value="ErrorCalendarIsCancelledForTentative"/>
<xs:enumeration value="ErrorCalendarIsDelegatedForAccept"/>
<xs:enumeration value="ErrorCalendarIsDelegatedForDecline"/>
<xs:enumeration value="ErrorCalendarIsDelegatedForRemove"/>
<xs:enumeration value="ErrorCalendarIsDelegatedForTentative"/>
<xs:enumeration value="ErrorCalendarIsNotOrganizer"/>
<xs:enumeration value="ErrorCalendarIsOrganizerForAccept"/>
<xs:enumeration value="ErrorCalendarIsOrganizerForDecline"/>
<xs:enumeration value="ErrorCalendarIsOrganizerForRemove"/>
<xs:enumeration value="ErrorCalendarIsOrganizerForTentative"/>
<xs:enumeration value="ErrorCalendarOccurrenceIndexIsOutOfRecurrenceRange"/>
<xs:enumeration value="ErrorCalendarOccurrenceIsDeletedFromRecurrence"/>
<xs:enumeration value="ErrorCalendarOutOfRange"/>
<xs:enumeration value="ErrorCalendarMeetingRequestIsOutOfDate"/>
<xs:enumeration value="ErrorCalendarViewRangeTooBig"/>
<xs:enumeration value="ErrorCallerIsInvalidADAccount"/>
<xs:enumeration value="ErrorCannotArchiveCalendarContactTaskFolderException"/>
<xs:enumeration value="ErrorCannotArchiveItemsInPublicFolders"/>
<xs:enumeration value="ErrorCannotArchiveItemsInArchiveMailbox"/>
<xs:enumeration value="ErrorCannotCreateCalendarItemInNonCalendarFolder"/>
<xs:enumeration value="ErrorCannotCreateContactInNonContactFolder"/>
<xs:enumeration value="ErrorCannotCreatePostItemInNonMailFolder"/>
<xs:enumeration value="ErrorCannotCreateTaskInNonTaskFolder"/>
<xs:enumeration value="ErrorCannotDeleteObject"/>
<xs:enumeration value="ErrorCannotDisableMandatoryExtension"/>
<xs:enumeration value="ErrorCannotGetSourceFolderPath"/>
<xs:enumeration value="ErrorCannotGetExternalEcpUrl"/>
<xs:enumeration value="ErrorCannotOpenFileAttachment"/>
<xs:enumeration value="ErrorCannotDeleteTaskOccurrence"/>
<xs:enumeration value="ErrorCannotEmptyFolder"/>
<xs:enumeration value="ErrorCannotSetCalendarPermissionOnNonCalendarFolder"/>
<xs:enumeration value="ErrorCannotSetNonCalendarPermissionOnCalendarFolder"/>
<xs:enumeration value="ErrorCannotSetPermissionUnknownEntries"/>
<xs:enumeration value="ErrorCannotSpecifySearchFolderAsSourceFolder"/>
<xs:enumeration value="ErrorCannotUseFolderIdForItemId"/>
<xs:enumeration value="ErrorCannotUseItemIdForFolderId"/>
<xs:enumeration value="ErrorChangeKeyRequired"/>
<xs:enumeration value="ErrorChangeKeyRequiredForWriteOperations"/>
<xs:enumeration value="ErrorClientDisconnected"/>
<xs:enumeration value="ErrorClientIntentInvalidStateDefinition"/>
<xs:enumeration value="ErrorClientIntentNotFound"/>
<xs:enumeration value="ErrorConnectionFailed"/>
```

```

<xs:enumeration value="ErrorContainsFilterWrongType"/>
<xs:enumeration value="ErrorContentConversionFailed"/>
<xs:enumeration value="ErrorContentIndexingNotEnabled"/>
<xs:enumeration value="ErrorCorruptData"/>
<xs:enumeration value="ErrorCreateItemAccessDenied"/>
<xs:enumeration value="ErrorCreateManagedFolderPartialCompletion"/>
<xs:enumeration value="ErrorCreateSubfolderAccessDenied"/>
<xs:enumeration value="ErrorCrossMailboxMoveCopy"/>
<xs:enumeration value="ErrorCrossSiteRequest"/>
<xs:enumeration value="ErrorDataSizeLimitExceeded"/>
<xs:enumeration value="ErrorDataSourceOperation"/>
<xs:enumeration value="ErrorDelegateAlreadyExists"/>
<xs:enumeration value="ErrorDelegateCannotAddOwner"/>
<xs:enumeration value="ErrorDelegateMissingConfiguration"/>
<xs:enumeration value="ErrorDelegateNoUser"/>
<xs:enumeration value="ErrorDelegateValidationFailed"/>
<xs:enumeration value="ErrorDeleteDistinguishedFolder"/>
<xs:enumeration value="ErrorDeleteItemsFailed"/>
<xs:enumeration value="ErrorDeleteUnifiedMessagingPromptFailed"/>
<xs:enumeration value="ErrorDistinguishedUserNotSupported"/>
<xs:enumeration value="ErrorDistributionListMemberNotExist"/>
<xs:enumeration value="ErrorDuplicateInputFolderNames"/>
<xs:enumeration value="ErrorDuplicateUserIdsSpecified"/>
<xs:enumeration value="ErrorEmailAddressMismatch"/>
<xs:enumeration value="ErrorEventNotFound"/>
<xs:enumeration value="ErrorExceededConnectionCount"/>
<xs:enumeration value="ErrorExceededSubscriptionCount"/>
<xs:enumeration value="ErrorExceededFindCountLimit"/>
<xs:enumeration value="ErrorExpiredSubscription"/>
<xs:enumeration value="ErrorExtensionNotFound"/>
<xs:enumeration value="ErrorFolderCorrupt"/>
<xs:enumeration value="ErrorFolderNotFound"/>
<xs:enumeration value="ErrorFolderPropertyRequestFailed"/>
<xs:enumeration value="ErrorFolderSave"/>
<xs:enumeration value="ErrorFolderSaveFailed"/>
<xs:enumeration value="ErrorFolderSavePropertyError"/>
<xs:enumeration value="ErrorFolderExists"/>
<xs:enumeration value="ErrorFreeBusyGenerationFailed"/>
<xs:enumeration value="ErrorGetServerSecurityDescriptorFailed"/>
<xs:enumeration value="ErrorImContactLimitReached"/>
<xs:enumeration value="ErrorImGroupDisplayNameAlreadyExists"/>
<xs:enumeration value="ErrorImGroupLimitReached"/>
<xs:enumeration value="ErrorImpersonateUserDenied"/>
<xs:enumeration value="ErrorImpersonationDenied"/>
<xs:enumeration value="ErrorImpersonationFailed"/>
<xs:enumeration value="ErrorIncorrectSchemaVersion"/>
<xs:enumeration value="ErrorIncorrectUpdatePropertyCount"/>
<xs:enumeration value="ErrorIndividualMailboxLimitReached"/>
<xs:enumeration value="ErrorInsufficientResources"/>
<xs:enumeration value="ErrorInternalServerError"/>
<xs:enumeration value="ErrorInternalServerErrorTransientError"/>
<xs:enumeration value="ErrorInvalidAccessLevel"/>
<xs:enumeration value="ErrorInvalidArgument"/>
<xs:enumeration value="ErrorInvalidAttachmentId"/>
<xs:enumeration value="ErrorInvalidAttachmentSubfilter"/>
<xs:enumeration value="ErrorInvalidAttachmentSubfilterTextFilter"/>
<xs:enumeration value="ErrorInvalidAuthorizationContext"/>
<xs:enumeration value="ErrorInvalidChangeKey"/>
<xs:enumeration value="ErrorInvalidClientSecurityContext"/>

```

```

<xs:enumeration value="ErrorInvalidCompleteDate"/>
<xs:enumeration value="ErrorInvalidContactEmailAddress"/>
<xs:enumeration value="ErrorInvalidContactEmailIndex"/>
<xs:enumeration value="ErrorInvalidCrossForestCredentials"/>
<xs:enumeration value="ErrorInvalidDelegatePermission"/>
<xs:enumeration value="ErrorInvalidDelegateUserId"/>
<xs:enumeration value="ErrorInvalidExcludesRestriction"/>
<xs:enumeration value="ErrorInvalidExpressionTypeForSubFilter"/>
<xs:enumeration value="ErrorInvalidExtendedProperty"/>
<xs:enumeration value="ErrorInvalidExtendedPropertyValue"/>
<xs:enumeration value="ErrorInvalidFolderId"/>
<xs:enumeration value="ErrorInvalidFolderTypeForOperation"/>
<xs:enumeration value="ErrorInvalidFractionalPagingParameters"/>
<xs:enumeration value="ErrorInvalidFreeBusyViewType"/>
<xs:enumeration value="ErrorInvalidId"/>
<xs:enumeration value="ErrorInvalidIdEmpty"/>
<xs:enumeration value="ErrorInvalidIdMalformed"/>
<xs:enumeration value="ErrorInvalidIdMalformedEwsLegacyIdFormat"/>
<xs:enumeration value="ErrorInvalidIdMonikerTooLong"/>
<xs:enumeration value="ErrorInvalidIdNotAnItemAttachmentId"/>
<xs:enumeration value="ErrorInvalidIdReturnedByResolveNames"/>
<xs:enumeration value="ErrorInvalidIdStoreObjectIdTooLong"/>
<xs:enumeration value="ErrorInvalidIdTooManyAttachmentLevels"/>
<xs:enumeration value="ErrorInvalidIdXml"/>
<xs:enumeration value="ErrorInvalidImContactId"/>
<xs:enumeration value="ErrorInvalidImDistributionGroupSmtPAddress"/>
<xs:enumeration value="ErrorInvalidImGroupId"/>
<xs:enumeration value="ErrorInvalidIndexedPagingParameters"/>
<xs:enumeration value="ErrorInvalidInternetHeaderChildNodes"/>
<xs:enumeration value="ErrorInvalidItemForOperationArchiveItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationCreateItemAttachment"/>
<xs:enumeration value="ErrorInvalidItemForOperationCreateItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationAcceptItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationDeclineItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationCancelItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationExpandDL"/>
<xs:enumeration value="ErrorInvalidItemForOperationRemoveItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationSendItem"/>
<xs:enumeration value="ErrorInvalidItemForOperationTentative"/>
<xs:enumeration value="ErrorInvalidLogonType"/>
<xs:enumeration value="ErrorInvalidMailbox"/>
<xs:enumeration value="ErrorInvalidManagedFolderProperty"/>
<xs:enumeration value="ErrorInvalidManagedFolderQuota"/>
<xs:enumeration value="ErrorInvalidManagedFolderSize"/>
<xs:enumeration value="ErrorInvalidMergedFreeBusyInterval"/>
<xs:enumeration value="ErrorInvalidNameForNameResolution"/>
<xs:enumeration value="ErrorInvalidOperation"/>
<xs:enumeration value="ErrorInvalidNetworkServiceContext"/>
<xs:enumeration value="ErrorInvalidOofParameter"/>
<xs:enumeration value="ErrorInvalidPagingMaxRows"/>
<xs:enumeration value="ErrorInvalidParentFolder"/>
<xs:enumeration value="ErrorInvalidPercentCompleteValue"/>
<xs:enumeration value="ErrorInvalidPermissionSettings"/>
<xs:enumeration value="ErrorInvalidPhoneCallId"/>
<xs:enumeration value="ErrorInvalidPhoneNumber"/>
<xs:enumeration value="ErrorInvalidUserInfo"/>
<xs:enumeration value="ErrorInvalidPropertyAppend"/>
<xs:enumeration value="ErrorInvalidPropertyDelete"/>
<xs:enumeration value="ErrorInvalidPropertyForExists"/>

```

```

<xs:enumeration value="ErrorInvalidPropertyForOperation"/>
<xs:enumeration value="ErrorInvalidPropertyRequest"/>
<xs:enumeration value="ErrorInvalidPropertySet"/>
<xs:enumeration value="ErrorInvalidPropertyUpdateSentMessage"/>
<xs:enumeration value="ErrorInvalidProxySecurityContext"/>
<xs:enumeration value="ErrorInvalidPullSubscriptionId"/>
<xs:enumeration value="ErrorInvalidPushSubscriptionUrl"/>
<xs:enumeration value="ErrorInvalidRecipients"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilter"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilterComparison"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilterOrder"/>
<xs:enumeration value="ErrorInvalidRecipientSubfilterTextFilter"/>
<xs:enumeration value="ErrorInvalidReferenceItem"/>
<xs:enumeration value="ErrorInvalidRequest"/>
<xs:enumeration value="ErrorInvalidRestriction"/>
<xs:enumeration value="ErrorInvalidRetentionTagIdGuid"/>
<xs:enumeration value="ErrorInvalidRetentionTagTypeMismatch"/>
<xs:enumeration value="ErrorInvalidRetentionTagInvisible"/>
<xs:enumeration value="ErrorInvalidRetentionTagInheritance"/>
<xs:enumeration value="ErrorInvalidRoutingType"/>
<xs:enumeration value="ErrorInvalidScheduledOofDuration"/>
<xs:enumeration value="ErrorInvalidSchemaVersionForMailboxVersion"/>
<xs:enumeration value="ErrorInvalidSecurityDescriptor"/>
<xs:enumeration value="ErrorInvalidSendItemSaveSettings"/>
<xs:enumeration value="ErrorInvalidSerializedAccessToken"/>
<xs:enumeration value="ErrorInvalidServerVersion"/>
<xs:enumeration value="ErrorInvalidSid"/>
<xs:enumeration value="ErrorInvalidSIPUri"/>
<xs:enumeration value="ErrorInvalidSmtAddress"/>
<xs:enumeration value="ErrorInvalidSubfilterType"/>
<xs:enumeration value="ErrorInvalidSubfilterTypeNotAttendeeType"/>
<xs:enumeration value="ErrorInvalidSubfilterTypeNotRecipientType"/>
<xs:enumeration value="ErrorInvalidSubscription"/>
<xs:enumeration value="ErrorInvalidSubscriptionRequest"/>
<xs:enumeration value="ErrorInvalidSyncStateData"/>
<xs:enumeration value="ErrorInvalidTimeInterval"/>
<xs:enumeration value="ErrorInvalidUserOofSettings"/>
<xs:enumeration value="ErrorInvalidUserPrincipalName"/>
<xs:enumeration value="ErrorInvalidUserSid"/>
<xs:enumeration value="ErrorInvalidUserSidMissingUPN"/>
<xs:enumeration value="ErrorInvalidValueForProperty"/>
<xs:enumeration value="ErrorInvalidWatermark"/>
<xs:enumeration value="ErrorIPGatewayNotFound"/>
<xs:enumeration value="ErrorIrresolvableConflict"/>
<xs:enumeration value="ErrorItemCorrupt"/>
<xs:enumeration value="ErrorItemNotFound"/>
<xs:enumeration value="ErrorItemPropertyRequestFailed"/>
<xs:enumeration value="ErrorItemSave"/>
<xs:enumeration value="ErrorItemSavePropertyError"/>
<xs:enumeration value="ErrorLegacyMailboxFreeBusyViewTypeNotMerged"/>
<xs:enumeration value="ErrorLocalServerObjectNotFound"/>
<xs:enumeration value="ErrorLogonAsNetworkServiceFailed"/>
<xs:enumeration value="ErrorMailboxConfiguration"/>
<xs:enumeration value="ErrorMailboxDataArrayEmpty"/>
<xs:enumeration value="ErrorMailboxDataArrayTooBig"/>
<xs:enumeration value="ErrorMailboxHoldNotFound"/>
<xs:enumeration value="ErrorMailboxLogonFailed"/>
<xs:enumeration value="ErrorMailboxMoveInProgress"/>
<xs:enumeration value="ErrorMailboxStoreUnavailable"/>

```

```

<xs:enumeration value="ErrorMailRecipientNotFound"/>
<xs:enumeration value="ErrorMailTipsDisabled"/>
<xs:enumeration value="ErrorManagedFolderAlreadyExists"/>
<xs:enumeration value="ErrorManagedFolderNotFound"/>
<xs:enumeration value="ErrorManagedFoldersRootFailure"/>
<xs:enumeration value="ErrorMeetingSuggestionGenerationFailed"/>
<xs:enumeration value="ErrorMessageDispositionRequired"/>
<xs:enumeration value="ErrorMessageSizeExceeded"/>
<xs:enumeration value="ErrorMimeContentConversionFailed"/>
<xs:enumeration value="ErrorMimeContentInvalid"/>
<xs:enumeration value="ErrorMimeContentInvalidBase64String"/>
<xs:enumeration value="ErrorMissingArgument"/>
<xs:enumeration value="ErrorMissingEmailAddress"/>
<xs:enumeration value="ErrorMissingEmailAddressForManagedFolder"/>
<xs:enumeration value="ErrorMissingInformationEmailAddress"/>
<xs:enumeration value="ErrorMissingInformationReferenceItemId"/>
<xs:enumeration value="ErrorMissingItemForCreateItemAttachment"/>
<xs:enumeration value="ErrorMissingManagedFolderId"/>
<xs:enumeration value="ErrorMissingRecipients"/>
<xs:enumeration value="ErrorMissingUserIdInformation"/>
<xs:enumeration value="ErrorMoreThanOneAccessModeSpecified"/>
<xs:enumeration value="ErrorMoveCopyFailed"/>
<xs:enumeration value="ErrorMoveDistinguishedFolder"/>
<xs:enumeration value="ErrorMultiLegacyMailboxAccess"/>
<xs:enumeration value="ErrorNameResolutionMultipleResults"/>
<xs:enumeration value="ErrorNameResolutionNoMailbox"/>
<xs:enumeration value="ErrorNameResolutionNoResults"/>
<xs:enumeration value="ErrorNoApplicableProxyCASServersAvailable"/>
<xs:enumeration value="ErrorNoCalendar"/>
<xs:enumeration value="ErrorNoDestinationCASDueToKerberosRequirements"/>
<xs:enumeration value="ErrorNoDestinationCASDueToSSLRequirements"/>
<xs:enumeration value="ErrorNoDestinationCASDueToVersionMismatch"/>
<xs:enumeration value="ErrorNoFolderClassOverride"/>
<xs:enumeration value="ErrorNoFreeBusyAccess"/>
<xs:enumeration value="ErrorNonExistentMailbox"/>
<xs:enumeration value="ErrorNonPrimarySmtptAddress"/>
<xs:enumeration value="ErrorNoPropertyTagForCustomProperties"/>
<xs:enumeration value="ErrorNoPublicFolderReplicaAvailable"/>
<xs:enumeration value="ErrorNoPublicFolderServerAvailable"/>
<xs:enumeration value="ErrorNoRespondingCASInDestinationSite"/>
<xs:enumeration value="ErrorNotDelegate"/>
<xs:enumeration value="ErrorNotEnoughMemory"/>
<xs:enumeration value="ErrorObjectTypeChanged"/>
<xs:enumeration value="ErrorOccurrenceCrossingBoundary"/>
<xs:enumeration value="ErrorOccurrenceTimeSpanTooBig"/>
<xs:enumeration value="ErrorOperationNotAllowedWithPublicFolderRoot"/>
<xs:enumeration value="ErrorParentFolderIdRequired"/>
<xs:enumeration value="ErrorParentFolderNotFound"/>
<xs:enumeration value="ErrorPasswordChangeRequired"/>
<xs:enumeration value="ErrorPasswordExpired"/>
<xs:enumeration value="ErrorPhoneNumberNotDialable"/>
<xs:enumeration value="ErrorPropertyUpdate"/>
<xs:enumeration value="ErrorPromptPublishingOperationFailed"/>
<xs:enumeration value="ErrorPropertyValidationFailure"/>
<xs:enumeration value="ErrorProxiedSubscriptionCallFailure"/>
<xs:enumeration value="ErrorProxyCallFailed"/>
<xs:enumeration value="ErrorProxyGroupSidLimitExceeded"/>
<xs:enumeration value="ErrorProxyRequestNotAllowed"/>
<xs:enumeration value="ErrorProxyRequestProcessingFailed"/>

```

```
<xs:enumeration value="ErrorProxyServiceDiscoveryFailed"/>
<xs:enumeration value="ErrorProxyTokenExpired"/>
<xs:enumeration value="ErrorPublicFolderMailboxDiscoveryFailed"/>
<xs:enumeration value="ErrorPublicFolderOperationFailed"/>
<xs:enumeration value="ErrorPublicFolderRequestProcessingFailed"/>
<xs:enumeration value="ErrorPublicFolderServerNotFound"/>
<xs:enumeration value="ErrorPublicFolderSyncException"/>
<xs:enumeration value="ErrorQueryFilterTooLong"/>
<xs:enumeration value="ErrorQuotaExceeded"/>
<xs:enumeration value="ErrorReadEventsFailed"/>
<xs:enumeration value="ErrorReadReceiptNotPending"/>
<xs:enumeration value="ErrorRecurrenceEndDateTooBig"/>
<xs:enumeration value="ErrorRecurrenceHasNoOccurrence"/>
<xs:enumeration value="ErrorRemoveDelegatesFailed"/>
<xs:enumeration value="ErrorRequestAborted"/>
<xs:enumeration value="ErrorRequestStreamTooBig"/>
<xs:enumeration value="ErrorRequiredPropertyMissing"/>
<xs:enumeration value="ErrorResolveNamesInvalidFolderType"/>
<xs:enumeration value="ErrorResolveNamesOnlyOneContactsFolderAllowed"/>
<xs:enumeration value="ErrorResponseSchemaValidation"/>
<xs:enumeration value="ErrorRestrictionTooLong"/>
<xs:enumeration value="ErrorRestrictionTooComplex"/>
<xs:enumeration value="ErrorResultSetTooBig"/>
<xs:enumeration value="ErrorInvalidExchangeImpersonationHeaderData"/>
<xs:enumeration value="ErrorSavedItemFolderNotFound"/>
<xs:enumeration value="ErrorSchemaValidation"/>
<xs:enumeration value="ErrorSearchFolderNotInitialized"/>
<xs:enumeration value="ErrorSendAsDenied"/>
<xs:enumeration value="ErrorSendMeetingCancellationsRequired"/>
<xs:enumeration value="ErrorSendMeetingInvitationsOrCancellationsRequired"/>
<xs:enumeration value="ErrorSendMeetingInvitationsRequired"/>
<xs:enumeration value="ErrorSentMeetingRequestUpdate"/>
<xs:enumeration value="ErrorSentTaskRequestUpdate"/>
<xs:enumeration value="ErrorServerBusy"/>
<xs:enumeration value="ErrorServiceDiscoveryFailed"/>
<xs:enumeration value="ErrorStaleObject"/>
<xs:enumeration value="ErrorSubmissionQuotaExceeded"/>
<xs:enumeration value="ErrorSubscriptionAccessDenied"/>
<xs:enumeration value="ErrorSubscriptionDelegateAccessNotSupported"/>
<xs:enumeration value="ErrorSubscriptionNotFound"/>
<xs:enumeration value="ErrorSubscriptionUnsubscribed"/>
<xs:enumeration value="ErrorSyncFolderNotFound"/>
<xs:enumeration value="ErrorTeamMailboxNotFound"/>
<xs:enumeration value="ErrorTeamMailboxNotLinkedToSharePoint"/>
<xs:enumeration value="ErrorTeamMailboxUrlValidationFailed"/>
<xs:enumeration value="ErrorTeamMailboxNotAuthorizedOwner"/>
<xs:enumeration value="ErrorTeamMailboxActiveToPendingDelete"/>
<xs:enumeration value="ErrorTeamMailboxFailedSendingNotifications"/>
<xs:enumeration value="ErrorTeamMailboxErrorUnknown"/>
<xs:enumeration value="ErrorTimeIntervalTooBig"/>
<xs:enumeration value="ErrorTimeoutExpired"/>
<xs:enumeration value="ErrorTimeZone"/>
<xs:enumeration value="ErrorToFolderNotFound"/>
<xs:enumeration value="ErrorTokenSerializationDenied"/>
<xs:enumeration value="ErrorUpdatePropertyMismatch"/>
<xs:enumeration value="ErrorUnifiedMessagingDialPlanNotFound"/>
<xs:enumeration value="ErrorUnifiedMessagingReportDataNotFound"/>
<xs:enumeration value="ErrorUnifiedMessagingPromptNotFound"/>
<xs:enumeration value="ErrorUnifiedMessagingRequestFailed"/>
```

```
<xs:enumeration value="ErrorUnifiedMessagingServerNotFound"/>
<xs:enumeration value="ErrorUnableToGetUserOofSettings"/>
<xs:enumeration value="ErrorUnableToRemoveImContactFromGroup"/>
<xs:enumeration value="ErrorUnsupportedSubFilter"/>
<xs:enumeration value="ErrorUnsupportedCulture"/>
<xs:enumeration value="ErrorUnsupportedMapiPropertyType"/>
<xs:enumeration value="ErrorUnsupportedMimeConversion"/>
<xs:enumeration value="ErrorUnsupportedPathForQuery"/>
<xs:enumeration value="ErrorUnsupportedPathForSortGroup"/>
<xs:enumeration value="ErrorUnsupportedPropertyDefinition"/>
<xs:enumeration value="ErrorUnsupportedQueryFilter"/>
<xs:enumeration value="ErrorUnsupportedRecurrence"/>
<xs:enumeration value="ErrorUnsupportedTypeForConversion"/>
<xs:enumeration value="ErrorUpdateDelegatesFailed"/>
<xs:enumeration value="ErrorUserNotUnifiedMessagingEnabled"/>
<xs:enumeration value="ErrorVoiceMailNotImplemented"/>
<xs:enumeration value="ErrorValueOutOfRange"/>
<xs:enumeration value="ErrorVirusDetected"/>
<xs:enumeration value="ErrorVirusMessageDeleted"/>
<xs:enumeration value="ErrorWebRequestInInvalidState"/>
<xs:enumeration value="ErrorWin32InteropError"/>
<xs:enumeration value="ErrorWorkingHoursSaveFailed"/>
<xs:enumeration value="ErrorWorkingHoursXmlMalformed"/>
<xs:enumeration value="ErrorWrongServerVersion"/>
<xs:enumeration value="ErrorWrongServerVersionDelegate"/>
<xs:enumeration value="ErrorMissingInformationSharingFolderId"/>
<xs:enumeration value="ErrorDuplicateSOAPHeader"/>
<xs:enumeration value="ErrorSharingSynchronizationFailed"/>
<xs:enumeration value="ErrorSharingNoExternalEwsAvailable"/>
<xs:enumeration value="ErrorFreeBusyDLLimitReached"/>
<xs:enumeration value="ErrorInvalidGetSharingFolderRequest"/>
<xs:enumeration value="ErrorNotAllowedExternalSharingByPolicy"/>
<xs:enumeration value="ErrorUserNotAllowedByPolicy"/>
<xs:enumeration value="ErrorPermissionNotAllowedByPolicy"/>
<xs:enumeration value="ErrorOrganizationNotFederated"/>
<xs:enumeration value="ErrorMailboxFailover"/>
<xs:enumeration value="ErrorInvalidExternalSharingInitiator"/>
<xs:enumeration value="ErrorMessageTrackingPermanentError"/>
<xs:enumeration value="ErrorMessageTrackingTransientError"/>
<xs:enumeration value="ErrorMessageTrackingNoSuchDomain"/>
<xs:enumeration value="ErrorUserWithoutFederatedProxyAddress"/>
<xs:enumeration value="ErrorInvalidOrganizationRelationshipForFreeBusy"/>
<xs:enumeration value="ErrorInvalidFederatedOrganizationId"/>
<xs:enumeration value="ErrorInvalidExternalSharingSubscriber"/>
<xs:enumeration value="ErrorInvalidSharingData"/>
<xs:enumeration value="ErrorInvalidSharingMessage"/>
<xs:enumeration value="ErrorNotSupportedSharingMessage"/>
<xs:enumeration value="ErrorApplyConversationActionFailed"/>
<xs:enumeration value="ErrorInboxRulesValidationError"/>
<xs:enumeration value="ErrorOutlookRuleBlobExists"/>
<xs:enumeration value="ErrorRulesOverQuota"/>
<xs:enumeration value="ErrorNewEventStreamConnectionOpened"/>
<xs:enumeration value="ErrorMissedNotificationEvents"/>
<xs:enumeration value="ErrorDuplicateLegacyDistinguishedName"/>
<xs:enumeration value="ErrorInvalidClientAccessTokenRequest"/>
<xs:enumeration value="ErrorNoSpeechDetected"/>
<xs:enumeration value="ErrorUMServerUnavailable"/>
<xs:enumeration value="ErrorRecipientNotFound"/>
<xs:enumeration value="ErrorRecognizerNotInstalled"/>
```



```

<xs:enumeration value="ErrorSpeechGrammarError"/>
<xs:enumeration value="ErrorInvalidManagementRoleHeader"/>
<xs:enumeration value="ErrorLocationServicesDisabled"/>
<xs:enumeration value="ErrorLocationServicesRequestTimedOut"/>
<xs:enumeration value="ErrorLocationServicesRequestFailed"/>
<xs:enumeration value="ErrorLocationServicesInvalidRequest"/>
<xs:enumeration value="ErrorMailboxScopeNotAllowedWithoutQueryString"/>
<xs:enumeration value="ErrorArchiveMailboxSearchFailed"/>
<xs:enumeration value="ErrorInvalidPhotoSize"/>
<xs:enumeration value="ErrorSearchQueryHasTooManyKeywords"/>
<xs:enumeration value="ErrorSearchTooManyMailboxes"/>
<xs:enumeration value="ErrorDiscoverySearchesDisabled"/>
</xs:restriction>
</xs:simpleType>
</xs:schema>

```

## 7.2 Types Schema

This section provides the contents of the MS-OXWSCDATA-types.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSCDATA-types.xsd includes or imports the files listed in the following table. To operate correctly, these files have to be present in the folder that contains the types and messages schema files.

File name	Defining specification
MS-OXWSMSG-types.xsd	<a href="#">[MS-OXWSMSG]</a> section 7.1
MS-OXWSFOLD-types.xsd	<a href="#">[MS-OXWSFOLD]</a> section 7.2
MS-OXWSATT-types.xsd	<a href="#">[MS-OXWSATT]</a> section 7.2.
MS-OXWSDLIST-types.xsd	<a href="#">[MS-OXWSDLIST]</a> section 6.2.
MS-OXWSTASK-types.xsd	<a href="#">[MS-OXWSTASK]</a> section 7.2.

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
elementFormDefault="qualified" version="Exchange2013" id="types">
  <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
  <xs:include schemaLocation="MS-OXWSMSG-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSFOLD-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSATT-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSDLIST-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSTASK-types.xsd"/>
  <xs:complexType name="AbsoluteMonthlyRecurrencePatternType">
    <xs:complexContent>
      <xs:extension base="t:IntervalRecurrencePatternBaseType">
        <xs:sequence>
          <xs:element name="DayOfMonth" type="xs:int"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="AbsoluteYearlyRecurrencePatternType">

```

```

    <xs:complexContent>
      <xs:extension base="t:RecurrencePatternBaseType">
        <xs:sequence>
          <xs:element name="DayOfMonth" type="xs:int"/>
          <xs:element name="Month" type="t:MonthNamesType"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="AcceptSharingInvitationType">
    <xs:complexContent>
      <xs:extension base="t:ReferenceItemResponseType"/>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="ArrayOfCalendarPermissionsType">
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="CalendarPermission" type="t:CalendarPermissionType"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="ArrayOfEmailAddressesType">
    <xs:sequence>
      <xs:element name="Address" type="t:EmailAddressType" minOccurs="0"
maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfHighlightTermsType">
    <xs:sequence>
      <xs:element name="Term" type="t:HighlightTermType" minOccurs="0"
maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfPermissionsType">
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="Permission" type="t:PermissionType"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="ArrayOfRealItemsType">
    <xs:sequence>
      <xs:choice minOccurs="0" maxOccurs="unbounded">
        <xs:element name="Item" type="t:ItemType"/>
        <xs:element name="Message" type="t:MessageType"/>
        <xs:element name="CalendarItem" type="t:CalendarItemType"/>
        <xs:element name="Contact" type="t:ContactItemType"/>
        <xs:element name="DistributionList" type="t:DistributionListType"/>
        <xs:element name="MeetingMessage" type="t:MeetingMessageType"/>
        <xs:element name="MeetingRequest" type="t:MeetingRequestMessageType"/>
        <xs:element name="MeetingResponse" type="t:MeetingResponseMessageType"/>
        <xs:element name="MeetingCancellation"
type="t:MeetingCancellationMessageType"/>
        <xs:element name="Task" type="t:TaskType"/>
        <xs:element name="PostItem" type="t:PostItemType"/>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfRecipientsType">
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="Mailbox" type="t:EmailAddressType"/>
    </xs:choice>
  </xs:complexType>

```

```

<xs:complexType name="ArrayOfStringsType">
  <xs:sequence>
    <xs:element name="String" type="xs:string" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="BaseEmailAddressType"/>
<xs:complexType name="BaseItemIdType" abstract="true"/>
<xs:complexType name="BasePathToElementType" abstract="true"/>
<xs:complexType name="BodyType">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="BodyType" type="t:BodyTypeType" use="required"/>
      <xs:attribute name="IsTruncated" type="xs:boolean" use="optional"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="BodyTypeResponseType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Best"/>
    <xs:enumeration value="HTML"/>
    <xs:enumeration value="Text"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="BodyTypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="HTML"/>
    <xs:enumeration value="Text"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="ChangeHighlightsType">
  <xs:sequence>
    <xs:element name="HasLocationChanged" type="xs:boolean" minOccurs="0"/>
    <xs:element name="Location" type="xs:string" minOccurs="0"/>
    <xs:element name="HasStartTimeChanged" type="xs:boolean" minOccurs="0"/>
    <xs:element name="Start" type="xs:dateTime" minOccurs="0"/>
    <xs:element name="HasEndTimeChanged" type="xs:boolean" minOccurs="0"/>
    <xs:element name="End" type="xs:dateTime" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ConnectingSIDType">
  <xs:choice>
    <xs:element name="PrincipalName" type="t:NonEmptyStringType"/>
    <xs:element name="SID" type="t:NonEmptyStringType"/>
    <xs:element name="PrimarySmtpAddress" type="t:NonEmptyStringType"/>
    <xs:element name="SmtpAddress" type="t:NonEmptyStringType"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="ConstantValueType">
  <xs:attribute name="Value" type="xs:string" use="required"/>
</xs:complexType>
<xs:complexType name="DailyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension base="t:IntervalRecurrencePatternBaseType"/>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="DateTimePrecisionType">
  <xs:annotation>
    <xs:documentation>Precision for returned DateTime values</xs:documentation>
  </xs:annotation>

```

```

    <xs:restriction base="xs:string">
      <xs:enumeration value="Seconds"/>
      <xs:enumeration value="Milliseconds"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element name="DateTimePrecision" type="t:DateTimePrecisionType"/>
<xs:simpleType name="DayOfWeekIndexType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="First"/>
    <xs:enumeration value="Second"/>
    <xs:enumeration value="Third"/>
    <xs:enumeration value="Fourth"/>
    <xs:enumeration value="Last"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DayOfWeekType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Sunday"/>
    <xs:enumeration value="Monday"/>
    <xs:enumeration value="Tuesday"/>
    <xs:enumeration value="Wednesday"/>
    <xs:enumeration value="Thursday"/>
    <xs:enumeration value="Friday"/>
    <xs:enumeration value="Saturday"/>
    <xs:enumeration value="Day"/>
    <xs:enumeration value="Weekday"/>
    <xs:enumeration value="WeekendDay"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DaysOfWeekType">
  <xs:list itemType="t:DayOfWeekType"/>
</xs:simpleType>
<xs:simpleType name="DefaultShapeNamesType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="IdOnly"/>
    <xs:enumeration value="Default"/>
    <xs:enumeration value="AllProperties"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="DeletedOccurrenceInfoType">
  <xs:sequence>
    <xs:element name="Start" type="xs:dateTime"/>
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="DictionaryURIType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="item:InternetMessageHeader"/>
    <xs:enumeration value="contacts:ImAddress"/>
    <xs:enumeration value="contacts:PhysicalAddress:Street"/>
    <xs:enumeration value="contacts:PhysicalAddress:City"/>
    <xs:enumeration value="contacts:PhysicalAddress:State"/>
    <xs:enumeration value="contacts:PhysicalAddress:CountryOrRegion"/>
    <xs:enumeration value="contacts:PhysicalAddress:PostalCode"/>
    <xs:enumeration value="contacts:PhoneNumber"/>
    <xs:enumeration value="contacts:EmailAddress"/>
    <xs:enumeration value="distributionlist:Members:Member"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DisposalType">

```

```

    <xs:restriction base="xs:string">
      <xs:enumeration value="HardDelete"/>
      <xs:enumeration value="SoftDelete"/>
      <xs:enumeration value="MoveToDeletedItems"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="DistinguishedFolderIdNameType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="calendar"/>
      <xs:enumeration value="contacts"/>
      <xs:enumeration value="deleteditems"/>
      <xs:enumeration value="drafts"/>
      <xs:enumeration value="inbox"/>
      <xs:enumeration value="journal"/>
      <xs:enumeration value="notes"/>
      <xs:enumeration value="outbox"/>
      <xs:enumeration value="sentitems"/>
      <xs:enumeration value="tasks"/>
      <xs:enumeration value="msgfolderroot"/>
      <xs:enumeration value="publicfoldersroot"/>
      <xs:enumeration value="root"/>
      <xs:enumeration value="junkemail"/>
      <xs:enumeration value="searchfolders"/>
      <xs:enumeration value="voicemail"/>
      <xs:enumeration value="recoverableitemsroot"/>
      <xs:enumeration value="recoverableitemsdeletions"/>
      <xs:enumeration value="recoverableitemsversions"/>
      <xs:enumeration value="recoverableitemspurges"/>
      <xs:enumeration value="archiveroot"/>
      <xs:enumeration value="archivemsgfolderroot"/>
      <xs:enumeration value="archiveddeleteditems"/>
      <xs:enumeration value="archiverecoverableitemsroot"/>
      <xs:enumeration value="archiverecoverableitemsdeletions"/>
      <xs:enumeration value="archiverecoverableitemsversions"/>
      <xs:enumeration value="archiverecoverableitemspurges"/>
      <xs:enumeration value="syncissues"/>
      <xs:enumeration value="conflicts"/>
      <xs:enumeration value="localfailures"/>
      <xs:enumeration value="serverfailures"/>
      <xs:enumeration value="recipientcache"/>
      <xs:enumeration value="quickcontacts"/>
      <xs:enumeration value="conversationhistory"/>
      <xs:enumeration value="adminauditlogs"/>
      <xs:enumeration value="todosearch"/>
      <xs:enumeration value="mycontacts"/>
      <xs:enumeration value="directory"/>
      <xs:enumeration value="imcontactlist"/>
      <xs:enumeration value="peopleconnect" />
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="DistinguishedFolderIdType">
    <xs:complexContent>
      <xs:extension base="t:BaseFolderIdType">
        <xs:sequence>
          <xs:element name="Mailbox" type="t:EmailAddressType" minOccurs="0"/>
        </xs:sequence>
        <xs:attribute name="Id" type="t:DistinguishedFolderIdNameType"
use="required"/>
        <xs:attribute name="ChangeKey" type="xs:string" use="optional"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

```

```

        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:simpleType name="DistinguishedPropertySetType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Meeting"/>
        <xs:enumeration value="Appointment"/>
        <xs:enumeration value="Common"/>
        <xs:enumeration value="PublicStrings"/>
        <xs:enumeration value="Address"/>
        <xs:enumeration value="InternetHeaders"/>
        <xs:enumeration value="CalendarAssistant"/>
        <xs:enumeration value="UnifiedMessaging"/>
        <xs:enumeration value="Task"/>
        <xs:enumeration value="Sharing"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DistinguishedUserType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Default"/>
        <xs:enumeration value="Anonymous"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="Duration">
    <xs:sequence>
        <xs:element name="StartTime" type="xs:dateTime" minOccurs="1" maxOccurs="1"/>
        <xs:element name="EndTime" type="xs:dateTime" minOccurs="1" maxOccurs="1"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="EffectiveRightsType">
    <xs:sequence>
        <xs:element name="CreateAssociated" type="xs:boolean"/>
        <xs:element name="CreateContents" type="xs:boolean"/>
        <xs:element name="CreateHierarchy" type="xs:boolean"/>
        <xs:element name="Delete" type="xs:boolean"/>
        <xs:element name="Modify" type="xs:boolean"/>
        <xs:element name="Read" type="xs:boolean"/>
        <xs:element name="ViewPrivateItems" type="xs:boolean" minOccurs="0"
maxOccurs="1"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="EmailAddress">
    <xs:sequence>
        <xs:element name="Name" type="xs:string" minOccurs="0" maxOccurs="1"/>
        <xs:element name="Address" type="xs:string" minOccurs="1" maxOccurs="1"/>
        <xs:element name="RoutingType" type="xs:string" minOccurs="0" maxOccurs="1"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="EmailAddressType">
    <xs:complexContent>
        <xs:extension base="t:BaseEmailAddressType">
            <xs:sequence>
                <xs:element name="Name" type="xs:string" minOccurs="0"/>
                <xs:element name="EmailAddress" type="t:NonEmptyStringType"
minOccurs="0"/>
                <xs:element name="RoutingType" type="t:NonEmptyStringType"
minOccurs="0"/>
                <xs:element name="MailboxType" type="t:MailboxTypeType" minOccurs="0"/>
                <xs:element name="ItemId" type="t:ItemIdType" minOccurs="0"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

```

```

        <xs:element name="OriginalDisplayName" type="xs:string" minOccurs="0"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="EndDateRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension base="t:RecurrenceRangeBaseType">
      <xs:sequence>
        <xs:element name="EndDate" type="xs:date"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="ExceptionFieldURI" type="t:PathToExceptionFieldType"/>
<xs:simpleType name="ExceptionPropertyURIType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="attachment:Name"/>
    <xs:enumeration value="attachment:ContentType"/>
    <xs:enumeration value="attachment:Content"/>
    <xs:enumeration value="recurrence:Month"/>
    <xs:enumeration value="recurrence:DayOfWeekIndex"/>
    <xs:enumeration value="recurrence:DaysOfWeek"/>
    <xs:enumeration value="recurrence:DayOfMonth"/>
    <xs:enumeration value="recurrence:Interval"/>
    <xs:enumeration value="recurrence:NumberOfOccurrences"/>
    <xs:enumeration value="timezone:Offset"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="ExchangeImpersonationType">
  <xs:sequence>
    <xs:element name="ConnectingSID" type="t:ConnectingSIDType"/>
  </xs:sequence>
  <xs:anyAttribute namespace="http://schemas.xmlsoap.org/soap/envelope/" />
</xs:complexType>
<xs:element name="ExchangeImpersonation" type="t:ExchangeImpersonationType"/>
<xs:simpleType name="ExchangeVersionType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Exchange2007"/>
    <xs:enumeration value="Exchange2007_SP1"/>
    <xs:enumeration value="Exchange2010"/>
    <xs:enumeration value="Exchange2010_SP1"/>
    <xs:enumeration value="Exchange2010_SP2"/>
    <xs:enumeration value="Exchange2013"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ExcludesAttributeType">
  <xs:restriction base="xs:string">
    <xs:pattern value="( (0x|0X) [0-9A-Fa-f]*) | ([0-9]*) "/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="IconIndexType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default"/>
    <xs:enumeration value="PostItem"/>
    <xs:enumeration value="MailRead"/>
    <xs:enumeration value="MailUnread"/>
    <xs:enumeration value="MailReplied"/>
    <xs:enumeration value="MailForwarded"/>
  </xs:restriction>
</xs:simpleType>

```

```

<xs:enumeration value="MailEncrypted"/>
<xs:enumeration value="MailSmimeSigned"/>
<xs:enumeration value="MailEncryptedReplied"/>
<xs:enumeration value="MailSmimeSignedReplied"/>
<xs:enumeration value="MailEncryptedForwarded"/>
<xs:enumeration value="MailSmimeSignedForwarded"/>
<xs:enumeration value="MailEncryptedRead"/>
<xs:enumeration value="MailSmimeSignedRead"/>
<xs:enumeration value="MailIrm"/>
<xs:enumeration value="MailIrmForwarded"/>
<xs:enumeration value="MailIrmReplied"/>
<xs:enumeration value="SmsSubmitted"/>
<xs:enumeration value="SmsRoutedToDeliveryPoint"/>
<xs:enumeration value="SmsRoutedToExternalMessagingSystem"/>
<xs:enumeration value="SmsDelivered"/>
<xs:enumeration value="OutlookDefaultForContacts"/>
<xs:enumeration value="AppointmentItem"/>
<xs:enumeration value="AppointmentRecur"/>
<xs:enumeration value="AppointmentMeet"/>
<xs:enumeration value="AppointmentMeetRecur"/>
<xs:enumeration value="AppointmentMeetNY"/>
<xs:enumeration value="AppointmentMeetYes"/>
<xs:enumeration value="AppointmentMeetNo"/>
<xs:enumeration value="AppointmentMeetMaybe"/>
<xs:enumeration value="AppointmentMeetCancel"/>
<xs:enumeration value="AppointmentMeetInfo"/>
<xs:enumeration value="TaskItem"/>
<xs:enumeration value="TaskRecur"/>
<xs:enumeration value="TaskOwned"/>
<xs:enumeration value="TaskDelegated"/>
</xs:restriction>
</xs:simpleType>
<xs:element name="FieldURI" type="t:PathToUnindexedFieldType"
substitutionGroup="t:Path"/>
<xs:complexType name="FieldURIOrConstantType">
  <xs:choice>
    <xs:element ref="t:Path"/>
    <xs:element name="Constant" type="t:ConstantValueType"/>
  </xs:choice>
</xs:complexType>
<xs:simpleType name="FlagStatusType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NotFlagged"/>
    <xs:enumeration value="Flagged"/>
    <xs:enumeration value="Complete"/>
  </xs:restriction>
</xs:simpleType>
<xs:attributeGroup name="FindResponsePagingAttributes">
  <xs:attribute name="IndexedPagingOffset" type="xs:int" use="optional"/>
  <xs:attribute name="NumeratorOffset" type="xs:int" use="optional"/>
  <xs:attribute name="AbsoluteDenominator" type="xs:int" use="optional"/>
  <xs:attribute name="IncludesLastItemInRange" type="xs:boolean" use="optional"/>
  <xs:attribute name="TotalItemsInView" type="xs:int" use="optional"/>
</xs:attributeGroup>
<xs:complexType name="FolderIdType">
  <xs:complexContent>
    <xs:extension base="t:BaseFolderIdType">
      <xs:attribute name="Id" type="xs:string" use="required"/>
      <xs:attribute name="ChangeKey" type="xs:string" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```



```

        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="FolderResponseShapeType">
    <xs:sequence>
        <xs:element name="BaseShape" type="t:DefaultShapeNamesType"/>
        <xs:element name="AdditionalProperties"
type="t:NonEmptyArrayOfPathsToElementType" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ForwardItemType">
    <xs:complexContent>
        <xs:extension base="t:SmartResponseType"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="HighlightTermType">
    <xs:sequence>
        <xs:element name="Scope" type="xs:string" minOccurs="1" maxOccurs="1"/>
        <xs:element name="Value" type="xs:string" minOccurs="1" maxOccurs="1"/>
    </xs:sequence>
</xs:complexType>
<xs:element name="IndexedFieldURI" type="t:PathToIndexedFieldType"
substitutionGroup="t:Path"/>
<xs:simpleType name="InferredImportanceType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Unimportant"/>
        <xs:enumeration value="None"/>
        <xs:enumeration value="Important"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="InternetHeaderType">
    <xs:simpleContent>
        <xs:extension base="xs:string">
            <xs:attribute name="HeaderName" type="xs:string" use="required"/>
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:complexType name="IntervalRecurrencePatternBaseType" abstract="true">
    <xs:complexContent>
        <xs:extension base="t:RecurrencePatternBaseType">
            <xs:sequence>
                <xs:element name="Interval" type="xs:int"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ItemResponseShapeType">
    <xs:sequence>
        <xs:element name="BaseShape" type="t:DefaultShapeNamesType"/>
        <xs:element name="IncludeMimeContent" type="xs:boolean" minOccurs="0"/>
        <xs:element name="BodyType" type="t:BodyTypeResponseType" minOccurs="0"/>
        <xs:element name="FilterHtmlContent" type="xs:boolean" minOccurs="0"/>
        <xs:element name="ConvertHtmlCodePageToUTF8" type="xs:boolean" minOccurs="0"
maxOccurs="1"/>
        <xs:element name="InlineImageUrlTemplate" type="xs:string" minOccurs="0"
maxOccurs="1"/>
        <xs:element name="BlockExternalImages" type="xs:boolean" minOccurs="0"
maxOccurs="1"/>
    </xs:sequence>

```

```

        <xs:element name="AddBlankTargetToLinks" type="xs:boolean" minOccurs="0"
maxOccurs="1"/>
        <xs:element name="MaximumBodySize" type="xs:int" minOccurs="0" maxOccurs="1"/>
        <xs:element name="AdditionalProperties"
type="t:NonEmptyArrayOfPathsToElementType" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="LegacyFreeBusyType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Free"/>
        <xs:enumeration value="Tentative"/>
        <xs:enumeration value="Busy"/>
        <xs:enumeration value="OOO"/>
        <xs:enumeration value="WorkingElsewhere"/>
        <xs:enumeration value="NoData"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="MailboxCultureType">
    <xs:simpleContent>
        <xs:extension base="xs:language">
            <xs:anyAttribute namespace="http://schemas.xmlsoap.org/soap/envelope/">
        </xs:extension>
    </xs:simpleContent>
</xs:complexType>
<xs:element name="MailboxCulture" type="t:MailboxCultureType"/>
<xs:simpleType name="MailboxTypeType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Unknown"/>
        <xs:enumeration value="OneOff"/>
        <xs:enumeration value="Mailbox"/>
        <xs:enumeration value="PublicDL"/>
        <xs:enumeration value="PrivateDL"/>
        <xs:enumeration value="Contact"/>
        <xs:enumeration value="PublicFolder"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="ManagementRoleType">
    <xs:sequence>
        <xs:element name="UserRoles" type="t:NonEmptyArrayOfRoleType" minOccurs="0"
maxOccurs="1"/>
        <xs:element name="ApplicationRoles" type="t:NonEmptyArrayOfRoleType"
minOccurs="0" maxOccurs="1"/>
    </xs:sequence>
</xs:complexType>
<xs:element name="ManagementRole" type="t:ManagementRoleType"/>
<xs:simpleType name="MonthNamesType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="January"/>
        <xs:enumeration value="February"/>
        <xs:enumeration value="March"/>
        <xs:enumeration value="April"/>
        <xs:enumeration value="May"/>
        <xs:enumeration value="June"/>
        <xs:enumeration value="July"/>
        <xs:enumeration value="August"/>
        <xs:enumeration value="September"/>
        <xs:enumeration value="October"/>
        <xs:enumeration value="November"/>
        <xs:enumeration value="December"/>
    </xs:restriction>

```

```

    </xs:restriction>
</xs:simpleType>
<xs:complexType name="NoEndRecurrenceRangeType">
  <xs:complexContent>
    <xs:extension base="t:RecurrenceRangeBaseType"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfAllItemsType">
  <xs:sequence>
    <xs:choice maxOccurs="unbounded">
      <xs:element name="Item" type="t:ItemType"/>
      <xs:element name="Message" type="t:MessageType"/>
      <xs:element name="CalendarItem" type="t:CalendarItemType"/>
      <xs:element name="Contact" type="t:ContactItemType"/>
      <xs:element name="DistributionList" type="t:DistributionListType"/>
      <xs:element name="MeetingMessage" type="t:MeetingMessageType"/>
      <xs:element name="MeetingRequest" type="t:MeetingRequestMessageType"/>
      <xs:element name="MeetingResponse" type="t:MeetingResponseMessageType"/>
      <xs:element name="MeetingCancellation"
type="t:MeetingCancellationMessageType"/>
      <xs:element name="Task" type="t:TaskType"/>
      <xs:element name="PostItem" type="t:PostItemType"/>
      <xs:element name="ReplyToItem" type="t:ReplyToItemType"/>
      <xs:element name="ForwardItem" type="t:ForwardItemType"/>
      <xs:element name="ReplyAllToItem" type="t:ReplyAllToItemType"/>
      <xs:element name="AcceptItem" type="t:AcceptItemType"/>
      <xs:element name="TentativelyAcceptItem" type="t:TentativelyAcceptItemType"/>
      <xs:element name="DeclineItem" type="t:DeclineItemType"/>
      <xs:element name="CancelCalendarItem" type="t:CancelCalendarItemType"/>
      <xs:element name="RemoveItem" type="t:RemoveItemType"/>
      <xs:element name="SuppressReadReceipt" type="t:SuppressReadReceiptType"/>
      <xs:element name="PostReplyItem" type="t:PostReplyItemType"/>
      <xs:element name="AcceptSharingInvitation"
type="t:AcceptSharingInvitationType"/>
    </xs:choice>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfAttachmentsType">
  <xs:choice maxOccurs="unbounded">
    <xs:element name="ItemAttachment" type="t:ItemAttachmentType"/>
    <xs:element name="FileAttachment" type="t:FileAttachmentType"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfPathsToElementType">
  <xs:choice maxOccurs="unbounded">
    <xs:element ref="t:Path"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfRoleType">
  <xs:sequence>
    <xs:element name="Role" type="xs:string" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="NonEmptyStringType">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="NumberedRecurrenceRangeType">

```

```

    <xs:complexContent>
      <xs:extension base="t:RecurrenceRangeBaseType">
        <xs:sequence>
          <xs:element name="NumberOfOccurrences" type="xs:int"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="Path" type="t:BasePathToElementType" abstract="true"/>
  <xs:complexType name="PathToExceptionFieldType">
    <xs:complexContent>
      <xs:extension base="t:BasePathToElementType">
        <xs:attribute name="FieldURI" type="t:ExceptionPropertyURIType"
use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="PathToIndexedFieldType">
    <xs:complexContent>
      <xs:extension base="t:BasePathToElementType">
        <xs:attribute name="FieldURI" type="t:DictionaryURIType" use="required"/>
        <xs:attribute name="FieldIndex" type="xs:string" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="PathToUnindexedFieldType">
    <xs:complexContent>
      <xs:extension base="t:BasePathToElementType">
        <xs:attribute name="FieldURI" type="t:UnindexedFieldURIType" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:simpleType name="PredictedMessageActionType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="None" />
      <xs:enumeration value="Respond" />
      <xs:enumeration value="FollowUp" />
      <xs:enumeration value="MoveToFolder" />
      <xs:enumeration value="Delete" />
      <xs:enumeration value="Read" />
      <xs:enumeration value="Ignore" />
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="RecurrencePatternBaseType" abstract="true"/>
  <xs:group name="RecurrencePatternTypes">
    <xs:sequence>
      <xs:choice>
        <xs:element name="RelativeYearlyRecurrence"
type="t:RelativeYearlyRecurrencePatternType"/>
        <xs:element name="AbsoluteYearlyRecurrence"
type="t:AbsoluteYearlyRecurrencePatternType"/>
        <xs:element name="RelativeMonthlyRecurrence"
type="t:RelativeMonthlyRecurrencePatternType"/>
        <xs:element name="AbsoluteMonthlyRecurrence"
type="t:AbsoluteMonthlyRecurrencePatternType"/>
        <xs:element name="WeeklyRecurrence" type="t:WeeklyRecurrencePatternType"/>
        <xs:element name="DailyRecurrence" type="t:DailyRecurrencePatternType"/>
      </xs:choice>
    </xs:sequence>
  </xs:group>

```

```

</xs:group>
<xs:complexType name="RecurrenceRangeBaseType" abstract="true">
  <xs:sequence>
    <xs:element name="StartDate" type="xs:date"/>
  </xs:sequence>
</xs:complexType>
<xs:group name="RecurrenceRangeTypes">
  <xs:sequence>
    <xs:choice>
      <xs:element name="NoEndRecurrence" type="t:NoEndRecurrenceRangeType"/>
      <xs:element name="EndDateRecurrence" type="t:EndDateRecurrenceRangeType"/>
      <xs:element name="NumberedRecurrence" type="t:NumberedRecurrenceRangeType"/>
    </xs:choice>
  </xs:sequence>
</xs:group>
<xs:complexType name="RelativeMonthlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension base="t:IntervalRecurrencePatternBaseType">
      <xs:sequence>
        <xs:element name="DaysOfWeek" type="t:DayOfWeekType"/>
        <xs:element name="DayOfWeekIndex" type="t:DayOfWeekIndexType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="RelativeYearlyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension base="t:RecurrencePatternBaseType">
      <xs:sequence>
        <xs:element name="DaysOfWeek" type="t:DayOfWeekType"/>
        <xs:element name="DayOfWeekIndex" type="t:DayOfWeekIndexType"/>
        <xs:element name="Month" type="t:MonthNamesType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="ReplyAllToItemType">
  <xs:complexContent>
    <xs:extension base="t:SmartResponseType"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="ReplyBody">
  <xs:sequence>
    <xs:element name="Message" type="xs:string" minOccurs="0" maxOccurs="1"/>
  </xs:sequence>
  <xs:attribute ref="xml:lang" use="optional"/>
</xs:complexType>
<xs:complexType name="ReplyToItemType">
  <xs:complexContent>
    <xs:extension base="t:SmartResponseType"/>
  </xs:complexContent>
</xs:complexType>
<xs:element name="RequestServerVersion">
  <xs:complexType>
    <xs:attribute name="Version" type="t:ExchangeVersionType" use="required"
fixed="Exchange2013"/>
    <xs:anyAttribute namespace="http://schemas.xmlsoap.org/soap/envelope"/>
  </xs:complexType>
</xs:element>

```

```

<xs:simpleType name="ResponseClassType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Success"/>
    <xs:enumeration value="Warning"/>
    <xs:enumeration value="Error"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="ResponseObjectCoreType" abstract="true">
  <xs:complexContent>
    <xs:extension base="t:MessageType">
      <xs:sequence>
        <xs:element name="ReferenceItemId" type="t:ItemIdType" minOccurs="0"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="ResponseObjectType" abstract="true">
  <xs:complexContent>
    <xs:extension base="t:ResponseObjectCoreType">
      <xs:attribute name="ObjectName" type="xs:string" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="SensitivityChoicesType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Normal"/>
    <xs:enumeration value="Personal"/>
    <xs:enumeration value="Private"/>
    <xs:enumeration value="Confidential"/>
  </xs:restriction>
</xs:simpleType>
<xs:element name="ServerVersionInfo">
  <xs:complexType>
    <xs:attribute name="MajorVersion" type="xs:int" use="optional"/>
    <xs:attribute name="MinorVersion" type="xs:int" use="optional"/>
    <xs:attribute name="MajorBuildNumber" type="xs:int" use="optional"/>
    <xs:attribute name="MinorBuildNumber" type="xs:int" use="optional"/>
    <xs:attribute name="Version" type="xs:string" use="optional"/>
  </xs:complexType>
</xs:element>
<xs:complexType name="SingleRecipientType">
  <xs:choice>
    <xs:element name="Mailbox" type="t:EmailAddressType"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="SuppressReadReceiptType">
  <xs:complexContent>
    <xs:extension base="t:ReferenceItemResponseType"/>
  </xs:complexContent>
</xs:complexType>
<xs:group name="TaskRecurrencePatternTypes">
  <xs:sequence>
    <xs:choice>
      <xs:element name="RelativeYearlyRecurrence"
type="t:RelativeYearlyRecurrencePatternType"/>
      <xs:element name="AbsoluteYearlyRecurrence"
type="t:AbsoluteYearlyRecurrencePatternType"/>
      <xs:element name="RelativeMonthlyRecurrence"
type="t:RelativeMonthlyRecurrencePatternType"/>
    </xs:choice>
  </xs:sequence>
</xs:group>

```

```

        <xs:element name="AbsoluteMonthlyRecurrence"
type="t:AbsoluteMonthlyRecurrencePatternType"/>
        <xs:element name="WeeklyRecurrence" type="t:WeeklyRecurrencePatternType"/>
        <xs:element name="DailyRecurrence" type="t:DailyRecurrencePatternType"/>
        <xs:element name="DailyRegeneration" type="t:DailyRegeneratingPatternType"/>
        <xs:element name="WeeklyRegeneration"
type="t:WeeklyRegeneratingPatternType"/>
        <xs:element name="MonthlyRegeneration"
type="t:MonthlyRegeneratingPatternType"/>
        <xs:element name="YearlyRegeneration"
type="t:YearlyRegeneratingPatternType"/>
    </xs:choice>
</xs:sequence>
</xs:group>
<xs:group name="TimeChangePatternTypes">
    <xs:sequence>
        <xs:choice>
            <xs:element name="RelativeYearlyRecurrence"
type="t:RelativeYearlyRecurrencePatternType"/>
            <xs:element name="AbsoluteDate" type="xs:date"/>
        </xs:choice>
    </xs:sequence>
</xs:group>
<xs:simpleType name="UnindexedFieldURIType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="folder:FolderId"/>
        <xs:enumeration value="folder:ParentFolderId"/>
        <xs:enumeration value="folder:DisplayName"/>
        <xs:enumeration value="folder:UnreadCount"/>
        <xs:enumeration value="folder:TotalCount"/>
        <xs:enumeration value="folder:ChildFolderCount"/>
        <xs:enumeration value="folder:FolderClass"/>
        <xs:enumeration value="folder:SearchParameters"/>
        <xs:enumeration value="folder:ManagedFolderInformation"/>
        <xs:enumeration value="folder:PermissionSet"/>
        <xs:enumeration value="folder:EffectiveRights"/>
        <xs:enumeration value="folder:SharingEffectiveRights"/>
        <xs:enumeration value="folder:DistinguishedFolderId"/>
        <xs:enumeration value="folder:PolicyTag"/>
        <xs:enumeration value="folder:ArchiveTag"/>
        <xs:enumeration value="item:ItemId"/>
        <xs:enumeration value="item:ParentFolderId"/>
        <xs:enumeration value="item:ItemClass"/>
        <xs:enumeration value="item:MimeContent"/>
        <xs:enumeration value="item:Attachments"/>
        <xs:enumeration value="item:Subject"/>
        <xs:enumeration value="item:DateTimeReceived"/>
        <xs:enumeration value="item:Size"/>
        <xs:enumeration value="item:Categories"/>
        <xs:enumeration value="item:HasAttachments"/>
        <xs:enumeration value="item:Importance"/>
        <xs:enumeration value="item:InReplyTo"/>
        <xs:enumeration value="item:InternetMessageHeaders"/>
        <xs:enumeration value="item:IsAssociated"/>
        <xs:enumeration value="item:IsDraft"/>
        <xs:enumeration value="item:IsFromMe"/>
        <xs:enumeration value="item:IsResend"/>
        <xs:enumeration value="item:IsSubmitted"/>
        <xs:enumeration value="item:IsUnmodified"/>
    </xs:restriction>
</xs:simpleType>

```

```

<xs:enumeration value="item:DateTimeSent"/>
<xs:enumeration value="item:DateTimeCreated"/>
<xs:enumeration value="item:Body"/>
<xs:enumeration value="item:ResponseObjects"/>
<xs:enumeration value="item:Sensitivity"/>
<xs:enumeration value="item:ReminderDueBy"/>
<xs:enumeration value="item:ReminderIsSet"/>
<xs:enumeration value="item:ReminderNextTime"/>
<xs:enumeration value="item:ReminderMinutesBeforeStart"/>
<xs:enumeration value="item:DisplayTo"/>
<xs:enumeration value="item:DisplayCc"/>
<xs:enumeration value="item:Culture"/>
<xs:enumeration value="item:EffectiveRights"/>
<xs:enumeration value="item:LastModifiedName"/>
<xs:enumeration value="item:LastModifiedTime"/>
<xs:enumeration value="item:ConversationId"/>
<xs:enumeration value="item:UniqueBody"/>
<xs:enumeration value="item:Flag"/>
<xs:enumeration value="item:StoreEntryId"/>
<xs:enumeration value="item:InstanceKey"/>
<xs:enumeration value="item:NormalizedBody"/>
<xs:enumeration value="item:EntityExtractionResult" />
<xs:enumeration value="item:PolicyTag"/>
<xs:enumeration value="item:ArchiveTag"/>
<xs:enumeration value="item:RetentionDate"/>
<xs:enumeration value="item:Preview"/>
<xs:enumeration value="item:NextPredictedAction" />
<xs:enumeration value="item:GroupingAction"/>
<xs:enumeration value="item:RightsManagementLicenseData" />
<xs:enumeration value="item:BlockStatus" />
<xs:enumeration value="item:HasBlockedImages" />
<xs:enumeration value="item:WebClientReadFormQueryString"/>
<xs:enumeration value="item:WebClientEditFormQueryString"/>
<xs:enumeration value="item:TextBody"/>
<xs:enumeration value="item:IconIndex"/>
<xs:enumeration value="message:ConversationIndex"/>
<xs:enumeration value="message:ConversationTopic"/>
<xs:enumeration value="message:InternetMessageId"/>
<xs:enumeration value="message:IsRead"/>
<xs:enumeration value="message:IsResponseRequested"/>
<xs:enumeration value="message:IsReadReceiptRequested"/>
<xs:enumeration value="message:IsDeliveryReceiptRequested"/>
<xs:enumeration value="message:ReceivedBy"/>
<xs:enumeration value="message:ReceivedRepresenting"/>
<xs:enumeration value="message:References"/>
<xs:enumeration value="message:ReplyTo"/>
<xs:enumeration value="message:From"/>
<xs:enumeration value="message:Sender"/>
<xs:enumeration value="message:ToRecipients"/>
<xs:enumeration value="message:CcRecipients"/>
<xs:enumeration value="message:BccRecipients"/>
<xs:enumeration value="meeting:AssociatedCalendarItemId"/>
<xs:enumeration value="meeting:IsDelegated"/>
<xs:enumeration value="meeting:IsOutOfDate"/>
<xs:enumeration value="meeting:HasBeenProcessed"/>
<xs:enumeration value="meeting:ResponseType"/>
<xs:enumeration value="meeting:ProposedStart"/>
<xs:enumeration value="meeting:ProposedEnd"/>
<xs:enumeration value="meetingRequest:MeetingRequestType"/>

```



```

<xs:enumeration value="meetingRequest:IntendedFreeBusyStatus"/>
<xs:enumeration value="meetingRequest:ChangeHighlights"/>
<xs:enumeration value="calendar:Start"/>
<xs:enumeration value="calendar:End"/>
<xs:enumeration value="calendar:OriginalStart"/>
<xs:enumeration value="calendar:StartWallClock"/>
<xs:enumeration value="calendar:EndWallClock"/>
<xs:enumeration value="calendar:StartTimeZoneId"/>
<xs:enumeration value="calendar:EndTimeZoneId"/>
<xs:enumeration value="calendar:IsAllDayEvent"/>
<xs:enumeration value="calendar:LegacyFreeBusyStatus"/>
<xs:enumeration value="calendar:Location"/>
<xs:enumeration value="calendar:EnhancedLocation"/>

<xs:enumeration value="calendar:When"/>
<xs:enumeration value="calendar:IsMeeting"/>
<xs:enumeration value="calendar:IsCancelled"/>
<xs:enumeration value="calendar:IsRecurring"/>
<xs:enumeration value="calendar:MeetingRequestWasSent"/>
<xs:enumeration value="calendar:IsResponseRequested"/>
<xs:enumeration value="calendar:CalendarItemType"/>
<xs:enumeration value="calendar:MyResponseType"/>
<xs:enumeration value="calendar:Organizer"/>
<xs:enumeration value="calendar:RequiredAttendees"/>
<xs:enumeration value="calendar:OptionalAttendees"/>
<xs:enumeration value="calendar:Resources"/>
<xs:enumeration value="calendar:ConflictingMeetingCount"/>
<xs:enumeration value="calendar:AdjacentMeetingCount"/>
<xs:enumeration value="calendar:ConflictingMeetings"/>
<xs:enumeration value="calendar:AdjacentMeetings"/>
<xs:enumeration value="calendar:Duration"/>
<xs:enumeration value="calendar:TimeZone"/>
<xs:enumeration value="calendar:AppointmentReplyTime"/>
<xs:enumeration value="calendar:AppointmentSequenceNumber"/>
<xs:enumeration value="calendar:AppointmentState"/>
<xs:enumeration value="calendar:Recurrence"/>
<xs:enumeration value="calendar:FirstOccurrence"/>
<xs:enumeration value="calendar>LastOccurrence"/>
<xs:enumeration value="calendar:ModifiedOccurrences"/>
<xs:enumeration value="calendar:DeletedOccurrences"/>
<xs:enumeration value="calendar:MeetingTimeZone"/>
<xs:enumeration value="calendar:ConferenceType"/>
<xs:enumeration value="calendar:AllowNewTimeProposal"/>
<xs:enumeration value="calendar:IsOnlineMeeting"/>
<xs:enumeration value="calendar:MeetingWorkspaceUrl"/>
<xs:enumeration value="calendar:NetShowUrl"/>
<xs:enumeration value="calendar:UID"/>
<xs:enumeration value="calendar:RecurrenceId"/>
<xs:enumeration value="calendar:DateTimeStamp"/>
<xs:enumeration value="calendar:StartTimeZone"/>
<xs:enumeration value="calendar:EndTimeZone"/>
<xs:enumeration value="calendar:JoinOnlineMeetingUrl"/>
<xs:enumeration value="calendar:OnlineMeetingSettings"/>
<xs:enumeration value="calendar:IsOrganizer"/>
<xs:enumeration value="task:ActualWork"/>
<xs:enumeration value="task:AssignedTime"/>
<xs:enumeration value="task:BillingInformation"/>
<xs:enumeration value="task:ChangeCount"/>
<xs:enumeration value="task:Companies"/>

```

```
<xs:enumeration value="task:CompleteDate"/>
<xs:enumeration value="task:Contacts"/>
<xs:enumeration value="task:DelegationState"/>
<xs:enumeration value="task:Delegator"/>
<xs:enumeration value="task:DueDate"/>
<xs:enumeration value="task:IsAssignmentEditable"/>
<xs:enumeration value="task:IsComplete"/>
<xs:enumeration value="task:IsRecurring"/>
<xs:enumeration value="task:IsTeamTask"/>
<xs:enumeration value="task:Mileage"/>
<xs:enumeration value="task:Owner"/>
<xs:enumeration value="task:PercentComplete"/>
<xs:enumeration value="task:Recurrence"/>
<xs:enumeration value="task:StartDate"/>
<xs:enumeration value="task:Status"/>
<xs:enumeration value="task:StatusDescription"/>
<xs:enumeration value="task:TotalWork"/>
<xs:enumeration value="contacts:Alias"/>
<xs:enumeration value="contacts:AssistantName"/>
<xs:enumeration value="contacts:Birthday"/>
<xs:enumeration value="contacts:BusinessHomePage"/>
<xs:enumeration value="contacts:Children"/>
<xs:enumeration value="contacts:Companies"/>
<xs:enumeration value="contacts:CompanyName"/>
<xs:enumeration value="contacts:CompleteName"/>
<xs:enumeration value="contacts>ContactSource"/>
<xs:enumeration value="contacts:Culture"/>
<xs:enumeration value="contacts:Department"/>
<xs:enumeration value="contacts:DisplayName"/>
<xs:enumeration value="contacts:DirectoryId"/>
<xs:enumeration value="contacts:DirectReports"/>
<xs:enumeration value="contacts:EmailAddresses"/>
<xs:enumeration value="contacts:FileAs"/>
<xs:enumeration value="contacts:FileAsMapping"/>
<xs:enumeration value="contacts:Generation"/>
<xs:enumeration value="contacts:GivenName"/>
<xs:enumeration value="contacts:ImAddresses"/>
<xs:enumeration value="contacts:Initials"/>
<xs:enumeration value="contacts:JobTitle"/>
<xs:enumeration value="contacts:Manager"/>
<xs:enumeration value="contacts:ManagerMailbox"/>
<xs:enumeration value="contacts:MiddleName"/>
<xs:enumeration value="contacts:Mileage"/>
<xs:enumeration value="contacts:MSExchangeCertificate"/>
<xs:enumeration value="contacts:Nickname"/>
<xs:enumeration value="contacts:Notes"/>
<xs:enumeration value="contacts:OfficeLocation"/>
<xs:enumeration value="contacts:PhoneNumbers"/>
<xs:enumeration value="contacts:PhoneticFullName"/>
<xs:enumeration value="contacts:PhoneticFirstName"/>
<xs:enumeration value="contacts:PhoneticLastName"/>
<xs:enumeration value="contacts:Photo"/>
<xs:enumeration value="contacts:PhysicalAddresses"/>
<xs:enumeration value="contacts:PostalAddressIndex"/>
<xs:enumeration value="contacts:Profession"/>
<xs:enumeration value="contacts:SpouseName"/>
<xs:enumeration value="contacts:Surname"/>
<xs:enumeration value="contacts:WeddingAnniversary"/>
<xs:enumeration value="contacts:UserSMIMECertificate"/>
```

```

<xs:enumeration value="contacts:HasPicture"/>
<xs:enumeration value="distributionlist:Members"/>
<xs:enumeration value="postitem:PostedTime"/>
<xs:enumeration value="conversation:ConversationId"/>
<xs:enumeration value="conversation:ConversationTopic"/>
<xs:enumeration value="conversation:UniqueRecipients"/>
<xs:enumeration value="conversation:GlobalUniqueRecipients"/>
<xs:enumeration value="conversation:UniqueUnreadSenders"/>
<xs:enumeration value="conversation:GlobalUniqueUnreadSenders"/>
<xs:enumeration value="conversation:UniqueSenders"/>
<xs:enumeration value="conversation:GlobalUniqueSenders"/>
<xs:enumeration value="conversation:LastDeliveryTime"/>
<xs:enumeration value="conversation:GlobalLastDeliveryTime"/>
<xs:enumeration value="conversation:Categories"/>
<xs:enumeration value="conversation:GlobalCategories"/>
<xs:enumeration value="conversation:FlagStatus"/>
<xs:enumeration value="conversation:GlobalFlagStatus"/>
<xs:enumeration value="conversation:HasAttachments"/>
<xs:enumeration value="conversation:GlobalHasAttachments"/>
<xs:enumeration value="conversation:MessageCount"/>
<xs:enumeration value="conversation:GlobalMessageCount"/>
<xs:enumeration value="conversation:UnreadCount"/>
<xs:enumeration value="conversation:GlobalUnreadCount"/>
<xs:enumeration value="conversation:Size"/>
<xs:enumeration value="conversation:GlobalSize"/>
<xs:enumeration value="conversation:ItemClasses"/>
<xs:enumeration value="conversation:GlobalItemClasses"/>
<xs:enumeration value="conversation:Importance"/>
<xs:enumeration value="conversation:GlobalImportance"/>
<xs:enumeration value="conversation:ItemIds"/>
<xs:enumeration value="conversation:GlobalItemIds"/>
<xs:enumeration value="conversation:LastModifiedTime"/>
<xs:enumeration value="conversation:InstanceKey"/>
<xs:enumeration value="conversation:Preview"/>
<xs:enumeration value="conversation:NextPredictedAction"/>
<xs:enumeration value="conversation:GroupingAction"/>
<xs:enumeration value="conversation:IconIndex"/>
<xs:enumeration value="conversation:GlobalIconIndex"/>
<xs:enumeration value="conversation:DraftItemIds"/>
<xs:enumeration value="persona:PersonaId" />
<xs:enumeration value="persona:PersonaType" />
<xs:enumeration value="persona:GivenName" />
<xs:enumeration value="persona:CompanyName" />
<xs:enumeration value="persona:Surname" />
<xs:enumeration value="persona:DisplayName" />
<xs:enumeration value="persona:EmailAddress" />
<xs:enumeration value="persona:FileAs" />
<xs:enumeration value="persona:HomeCity" />
<xs:enumeration value="persona:CreationTime" />

<xs:enumeration value="persona:RelevanceScore" />
<xs:enumeration value="persona:WorkCity" />
<xs:enumeration value="persona:PersonaObjectStatus" />
<xs:enumeration value="persona:FileAsId" />
<xs:enumeration value="persona:DisplayNamePrefix" />
<xs:enumeration value="persona:YomiCompanyName" />
<xs:enumeration value="persona:YomiFirstName" />
<xs:enumeration value="persona:YomiLastName" />

```

```
<xs:enumeration value ="persona:Title" />
<xs:enumeration value ="persona:EmailAddresses" />
<xs:enumeration value ="persona:PhoneNumber" />
<xs:enumeration value ="persona:ImAddress" />
<xs:enumeration value ="persona:ImAddresses" />
<xs:enumeration value ="persona:ImAddresses2" />
<xs:enumeration value ="persona:ImAddresses3" />
<xs:enumeration value ="persona:FolderIds" />
<xs:enumeration value ="persona:Attributions" />
<xs:enumeration value ="persona:DisplayNames" />
<xs:enumeration value ="persona:Initials" />
<xs:enumeration value ="persona:FileAses" />
<xs:enumeration value ="persona:FileAsIds" />
<xs:enumeration value ="persona:DisplayNamePrefixes" />
<xs:enumeration value ="persona:GivenNames" />
<xs:enumeration value ="persona:MiddleNames" />
<xs:enumeration value ="persona:Surnames" />
<xs:enumeration value ="persona:Generations" />
<xs:enumeration value ="persona:Nicknames" />
<xs:enumeration value ="persona:YomiCompanyNames" />
<xs:enumeration value ="persona:YomiFirstNames" />
<xs:enumeration value ="persona:YomiLastNames" />
<xs:enumeration value ="persona:BusinessPhoneNumbers" />
<xs:enumeration value ="persona:BusinessPhoneNumbers2" />
<xs:enumeration value ="persona:HomePhones" />
<xs:enumeration value ="persona:HomePhones2" />
<xs:enumeration value ="persona:MobilePhones" />
<xs:enumeration value ="persona:MobilePhones2" />
<xs:enumeration value ="persona:AssistantPhoneNumbers" />
<xs:enumeration value ="persona:CallbackPhones" />
<xs:enumeration value ="persona:CarPhones" />
<xs:enumeration value ="persona:HomeFaxes" />
<xs:enumeration value ="persona:OrganizationMainPhones" />
<xs:enumeration value ="persona:OtherFaxes" />
<xs:enumeration value ="persona:OtherTelephones" />
<xs:enumeration value ="persona:OtherPhones2" />
<xs:enumeration value ="persona:Paggers" />
<xs:enumeration value ="persona:RadioPhones" />
<xs:enumeration value ="persona:TelexNumbers" />
<xs:enumeration value ="persona:WorkFaxes" />
<xs:enumeration value ="persona:Emails1" />
<xs:enumeration value ="persona:Emails2" />
<xs:enumeration value ="persona:Emails3" />
<xs:enumeration value ="persona:BusinessHomePages" />
<xs:enumeration value ="persona:School" />
<xs:enumeration value ="persona:PersonalHomePages" />
<xs:enumeration value ="persona:OfficeLocations" />
<xs:enumeration value ="persona:BusinessAddresses" />
<xs:enumeration value ="persona:HomeAddresses" />
<xs:enumeration value ="persona:OtherAddresses" />
<xs:enumeration value ="persona:Titles" />
<xs:enumeration value ="persona:Departments" />
<xs:enumeration value ="persona:CompanyNames" />
<xs:enumeration value ="persona:Managers" />
<xs:enumeration value ="persona:AssistantNames" />
<xs:enumeration value ="persona:Professions" />
<xs:enumeration value ="persona:SpouseNames" />
<xs:enumeration value ="persona:Hobbies" />
<xs:enumeration value ="persona:WeddingAnniversaries" />
```

```

<xs:enumeration value ="persona:Birthdays" />
<xs:enumeration value ="persona:Children" />
<xs:enumeration value ="persona:Locations" />
<xs:enumeration value ="persona:ExtendedProperties" />
<xs:enumeration value ="persona:PostalAddress" />
<xs:enumeration value ="persona:Bodies" />
</xs:restriction>
</xs:simpleType>
<xs:complexType name="UserIdType">
  <xs:sequence>
    <xs:element name="SID" type="xs:string" minOccurs="0"/>
    <xs:element name="PrimarySmtpAddress" type="xs:string" minOccurs="0"/>
    <xs:element name="DisplayName" type="xs:string" minOccurs="0"/>
    <xs:element name="DistinguishedUser" type="t:DistinguishedUserType"
minOccurs="0"/>
    <xs:element name="ExternalUserIdentity" type="xs:string" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Value">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="Name" type="xs:string" use="required"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:element name="Value" type="t:Value"/>
<xs:complexType name="WeeklyRecurrencePatternType">
  <xs:complexContent>
    <xs:extension base="t:IntervalRecurrencePatternBaseType">
      <xs:sequence>
        <xs:element name="DaysOfWeek" type="t:DaysOfWeekType"/>
        <xs:element name="FirstDayOfWeek" type="t:DayOfWeekType" minOccurs="0"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="WellKnownResponseObjectType">
  <xs:complexContent>
    <xs:restriction base="t:ResponseObjectType">
      <xs:sequence>
        <xs:element name="ItemClass" type="t:ItemClassType" minOccurs="0"/>
        <xs:element name="Sensitivity" type="t:SensitivityChoicesType"
minOccurs="0"/>
        <xs:element name="Body" type="t:BodyType" minOccurs="0"/>
        <xs:element name="Attachments" type="t:NonEmptyArrayOfAttachmentsType"
minOccurs="0"/>
        <xs:element name="InternetMessageHeaders"
type="t:NonEmptyArrayOfInternetHeadersType" minOccurs="0"/>
        <xs:element name="Sender" type="t:SingleRecipientType" minOccurs="0"/>
        <xs:element name="ToRecipients" type="t:ArrayOfRecipientsType"
minOccurs="0"/>
        <xs:element name="CcRecipients" type="t:ArrayOfRecipientsType"
minOccurs="0"/>
        <xs:element name="BccRecipients" type="t:ArrayOfRecipientsType"
minOccurs="0"/>
        <xs:element name="IsReadReceiptRequested" type="xs:boolean"
minOccurs="0"/>
        <xs:element name="IsDeliveryReceiptRequested" type="xs:boolean"
minOccurs="0"/>
        <xs:element name="From" type="t:SingleRecipientType" minOccurs="0"/>

```

```
        <xs:element name="ReferenceItemId" type="t:ItemIdType" minOccurs="0"/>
      </xs:sequence>
      <xs:attribute name="ObjectName" type="xs:string" use="prohibited"/>
    </xs:restriction>
  </xs:complexContent>
</xs:complexType>
</xs:schema>
```

## 8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010
- Microsoft® Exchange Server 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2.3:](#) Exchange 2007, Exchange 2010, and Exchange 2010 SP1 do not include the **DateTimePrecisionType** simple type. The **DateTimePrecisionType** simple type was introduced in Exchange 2010 SP2.

[<2> Section 2.2.3:](#) Exchange 2007 and the initial release version of Exchange 2010 do not include the following enumeration values: recoverableitemsroot, recoverableitemsdeletions, recoverableitemsversions, recoverableitemspurges, archiveroot, archivemsgfolderroot, archiveddeleteditems, archiverecoverableitemsroot, archiverecoverableitemsdeletions, archiverecoverableitemsversions, and archiverecoverableitemspurges.

[<3> Section 2.2.3:](#) Exchange 2007 and Exchange 2010 do not use the **ExchangeVersionType** simple type.

[<4> Section 2.2.3:](#) Exchange 2007 and Exchange 2010 do not use the **IconIndexType** simple type.

[<5> Section 2.2.3:](#) Exchange 2007 and Exchange 2010 do not use the **PredictedMessageType** simple type.

[<6> Section 2.2.3:](#) Exchange 2007 and the initial release version of Exchange 2010 do not include the following response codes: ErrorAccessModeSpecified, ErrorCannotEmptyFolder, ErrorClientDisconnected, ErrorInvalidLogonType, ErrorNoApplicableProxyCASServersAvailable, ErrorNoPublicFolderServerAvailable, ErrorProxyServiceDiscoveryFailed, ErrorSubscriptionUnsubscribed, ErrorOutlookRuleBlobExists, ErrorRulesOverQuota, ErrorInboxRulesValidation, ErrorNewEventStreamConnectionOpened, ErrorMissedNotificationEvents, and ErrorApplyConversationActionFailed. Exchange 2010 SP1 does not include the ErrorAttachmentNestLevelLimitExceeded response code.

[<7> Section 2.2.3:](#) Exchange 2007 and the initial release version of Exchange 2010 do not include the following enumeration values: conversation:ConversationId, conversation:ConversationTopic, conversation:UniqueRecipients, conversation:GlobalUniqueRecipients, conversation:UniqueUnreadSenders, conversation:GlobalUniqueUnreadSenders, conversation:UniqueSenders, conversation:GlobalUniqueSenders, conversation:LastDeliveryTime, conversation:GlobalLastDeliveryTime, conversation:Categories, conversation:GlobalCategories, conversation:FlagStatus, conversation:GlobalFlagStatus, conversation:HasAttachments,

conversation:GlobalHasAttachments, conversation:MessageCount, conversation:GlobalMessageCount, conversation:UnreadCount, conversation:GlobalUnreadCount, conversation:Size, conversation:GlobalSize, conversation:ItemClasses, conversation:GlobalItemClasses, conversation:Importance, conversation:GlobalImportance, conversation:ItemIds, and conversation:GlobalItemIds.

Exchange 2007, Exchange 2010, and Exchange 2010 SP1 do not include the following enumeration values: **StoreEntryId**, **Alias**, **DirectoryId**, **DirectReports**, **ManagerMailbox**, **MSExchangeCertificate**, **Notes**, **PhoneticFullName**, **PhoneticFirstName**, **PhoneticLastName**, **Photo**, and **UserSMIMECertificate**.

<8> [Section 2.2.3.3:](#) Exchange 2007, Exchange 2010, and Exchange 2010 SP1 do not include the **DateTimePrecisionType** simple type. The **DateTimePrecisionType** simple type was introduced in Exchange 2010 SP2.

<9> [Section 2.2.3.10:](#) Exchange 2007 and the initial release version of Exchange 2010 do not include the following enumeration values: recoverableitemsroot, recoverableitemsdeletions, recoverableitemsversions, recoverableitemspurges, archiveroot, archivermsgfolderroot, archiveddeleteditems, archiverecoverableitemsroot, archiverecoverableitemsdeletions, archiverecoverableitemsversions, and archiverecoverableitemspurges.

<10> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "syncissues" value.

<11> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "localfailures" value.

<12> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "serverfailures" value.

<13> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "recipientcache" value.

<14> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "quickcontacts" value.

<15> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "conversationhistory" value.

<16> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "adminauditlogs" value.

<17> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "todosearch" value.

<18> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "mycontacts" value.

<19> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "directory" value.

<20> [Section 2.2.3.10:](#) Exchange 2007 and Exchange 2010 do not use the "peopleconnect" value.

<21> [Section 2.2.3.11:](#) Exchange 2007 and Exchange 2010 do not use the "Sharing" value.

<22> [Section 2.2.3.14:](#) Exchange 2007 does not support the **ExchangeVersionType** simple type.

<23> [Section 2.2.3.14:](#) Exchange 2007 includes only the target schema that is identified by the **Exchange2007** enumeration value.

<24> [Section 2.2.3.14:](#) Exchange 2007 does not include the target schema that is identified by the **Exchange2007\_SP1** enumeration value.

<25> [Section 2.2.3.14:](#) Exchange 2007 and Exchange 2007 SP1 do not include the target schema that is identified by the **Exchange2010** enumeration value.



<26> [Section 2.2.3.14](#): Exchange 2007 and Exchange 2010 do not include the target schema that is identified by the **Exchange2010\_SP1** enumeration value.

<27> [Section 2.2.3.14](#): Exchange 2007 and Exchange 2010 do not include the target schema that is identified by the **Exchange2010\_SP2** enumeration value.

<28> [Section 2.2.3.14](#): Exchange 2007 and Exchange 2010 do not include the target schema that is identified by the **Exchange2013** enumeration value.

<29> [Section 2.2.3.16](#): Exchange 2007 and Exchange 2010 do not use the **IconIndexType** simple type.

<30> [Section 2.2.3.17](#): Exchange 2007 and Exchange 2010 do not use the **WorkingElsewhere** value.

<31> [Section 2.2.3.21](#): Exchange 2007 and Exchange 2010 do not use the **PredictedMessageActionType** simple type.

<32> [Section 2.2.3.23](#): Exchange 2007 and the initial release version of Exchange 2010 do not include the following response codes: ErrorAccessModeSpecified, ErrorCannotEmptyFolder, ErrorClientDisconnected, ErrorInvalidLogonType, ErrorNoApplicableProxyCASServersAvailable, ErrorNoPublicFolderServerAvailable, ErrorProxyServiceDiscoveryFailed, ErrorSubscriptionUnsubscribed, ErrorOutlookRuleBlobExists, ErrorRulesOverQuota, ErrorInboxRulesValidation, ErrorNewEventStreamConnectionOpened, ErrorMissedNotificationEvents, and ErrorApplyConversationActionFailed. Exchange 2010 SP1 does not include the ErrorAttachmentNestLevelLimitExceeded response code.

<33> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorArchiveFolderPathCreation error code.

<34> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorArchiveMailboxNotEnabled error code.

<35> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorArchiveMailboxServiceDiscoveryFailed error code.

<36> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorAvailabilityConfigNotFound error code.

<37> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorCannotArchiveCalendarContactTaskFolderException error code.

<38> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorCannotArchiveItemsInPublicFolders error code.

<39> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorCannotArchiveItemsInArchiveMailbo error code.

<40> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorCannotGetSourceFolderPath error code.

<41> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorCannotGetExternalEcpUrl error code.

<42> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorCannotSpecifySearchFolderAsSourceFolder error code.

<43> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorClientIntentInvalidStateDefinition error code.

<44> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorClientIntentNotFound error code.

<45> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorContentIndexingNotEnabled error code.

<46> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorDeleteUnifiedMessagingPromptFailed error code.

<47> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorExtensionNotFound error code.

<48> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorImContactLimitReached error code.

<49> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorImGroupDisplayNameAlreadyExists error code.

<50> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorImGroupLimitReached error code.

<51> [Section 2.2.3.23](#): IDs that are based on the Exchange 2007 server schema are not supported by Exchange 2007 SP1 or later.

<52> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidImContactId error code.

<53> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidImDistributionGroupSmtpAddress error code.

<54> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidImGroupId error code.

<55> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidItemForOperationArchiveItem error code.

<56> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidRetentionTagTypeMismatch error code.

<57> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidRetentionTagInvisible error code.

<58> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidRetentionTagIdGuid error code.

<59> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidRetentionTagInheritance error code.

<60> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorMailboxHoldNotFound error code.

<61> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorMultiLegacyMailboxAccess error code.

<62> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorPromptPublishingOperationFailed error code.

<63> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorPublicFolderMailboxDiscoveryFailed error code.

<64> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorPublicFolderOperationFailed error code.

<65> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorPublicFolderSyncException error code.

<66> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorTeamMailboxNotFound error code.

<67> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorTeamMailboxNotLinkedToSharePoint error code.

<68> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorTeamMailboxUrlValidationFailed error code.

<69> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorTeamMailboxNotAuthorizedOwner error code.

<70> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorTeamMailboxActiveToPendingDelete error code.

<71> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorTeamMailboxFailedSendingNotifications error code.

<72> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorTeamMailboxErrorUnknown error code.

<73> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorUnifiedMessagingReportDataNotFound error code.

<74> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorUnifiedMessagingPromptNotFound error code.

<75> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorUnableToRemoveImContactFromGroup error code.

<76> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorDuplicateLegacyDistinguishedName error code.

<77> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidClientAccessTokenRequest error code.

<78> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorNoSpeechDetected error code.

<79> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorUMServerUnavailable error code.

<80> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorRecipientNotFound error code.

<81> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorRecognizerNotInstalled error code.

<82> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorSpeechGrammarError error code.

<83> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidManagementRoleHeader error code.

<84> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorLocationServicesDisabled error code.

<85> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorLocationServicesRequestTimedOut error code.

<86> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorLocationServicesRequestFailed error code.

<87> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorLocationServicesInvalidRequest error code.

<88> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorMailboxScopeNotAllowedWithoutQueryString error code.

<89> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorArchiveMailboxSearchFailed error code.

<90> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorArchiveMailboxServiceDiscoveryFailed error code.

<91> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorInvalidPhotoSize error code.

<92> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorSearchQueryHasTooManyKeywords error code.

<93> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorSearchTooManyMailboxes error code.

<94> [Section 2.2.3.23](#): Exchange 2007 and Exchange 2010 do not use the ErrorDiscoverySearchesDisabled error code.

<95> [Section 2.2.3.25](#): Exchange 2007 and the initial release version of Exchange 2010 do not include the following enumeration values: conversation:ConversationId, conversation:ConversationTopic, conversation:UniqueRecipients, conversation:GlobalUniqueRecipients, conversation:UniqueUnreadSenders, conversation:GlobalUniqueUnreadSenders, conversation:UniqueSenders, conversation:GlobalUniqueSenders, conversation:LastDeliveryTime, conversation:GlobalLastDeliveryTime, conversation:Categories, conversation:GlobalCategories, conversation:FlagStatus, conversation:GlobalFlagStatus, conversation:HasAttachments, conversation:GlobalHasAttachments, conversation:MessageCount, conversation:GlobalMessageCount, conversation:UnreadCount, conversation:GlobalUnreadCount, conversation:Size, conversation:GlobalSize, conversation:ItemClasses, conversation:GlobalItemClasses, conversation:Importance, conversation:GlobalImportance, conversation:ItemIds, and conversation:GlobalItemIds.

Exchange 2007, Exchange 2010, and Exchange 2010 SP1 do not include the following enumeration values: **StoreEntryId**, **Alias**, **DirectoryId**, **DirectReports**, **ManagerMailbox**, **MSExchangeCertificate**, **Notes**, **PhoneticFullName**, **PhoneticFirstName**, **PhoneticLastName**, **Photo**, and **UserSMIMECertificate**.

[<96> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **folder:DistinguishedFolderId** value.

[<97> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **folder:PolicyTag** value.

[<98> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **folder:ArchiveTag** value.

[<99> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **ReminderNextTime** value.

[<100> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:flag** value.

[<101> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:InstanceKey** value.

[<102> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:NormalizedBody** value.

[<103> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:EntityExtractionResult** value.

[<104> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:PolicyTag** value.

[<105> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:ArchiveTag** values.

[<106> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:RetentionDate** values.

[<107> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:Preview** value.

[<108> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:NextPredictedAction** value.

[<109> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:GroupingAction** value.

[<110> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:RightsManagementLicenseData** value.

[<111> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:BlockStatus** value.

[<112> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:TextBody** value.

[<113> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **item:IconIndex** value.

<114> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **meeting:ProposedStart** value.

<115> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **meeting:ProposedEnd** value.

<116> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **meetingRequest:ChangeHighlights** value.

<117> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **calendar:StartWallClock** value.

<118> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **calendar:EndWallClock** value.

<119> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **calendar:StartTimeZoneId** value.

<120> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **calendar:EndTimeZoneId** value.

<121> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **calendar:EnhancedLocation** value.

<122> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **calendar:JoinOnlineMeetingUrl** value.

<123> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **calendar:OnlineMeetingSettings** value.

<124> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **calendar:IsOrganizer** value.

<125> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **conversation:LastModified** value.

<126> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **conversation:InstanceKey** value.

<127> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **conversation:Preview** value.

<128> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **conversation:NextPredictedAction** value.

<129> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **conversation:GroupingAction** value.

<130> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **conversation:IconIndex** value.

<131> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **conversation:GlobalIconIndex** value.

<132> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **conversation:DraftItemIds** value.

<133> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:PersonaType** value.

<134> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:GivenName** value.

<135> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:CompanyName** value.

<136> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:SurName** value.

<137> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:DisplayName** value.

<138> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:EmailAddress** value.

<139> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:FileAs** value.

<140> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:HomeCity** value.

<141> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:CreationTime** value.

<142> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:RelevanceScore** value.

<143> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:WorkCity** value.

<144> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:PersonaObjectStatus** value.

<145> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:FileAsId** value.

<146> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:DisplayNamePrefix** value.

<147> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:YomiCompanyName** value.

<148> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:YomiFirstName** value.

<149> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:YomiFirstLast** value.

<150> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Title** value.

<151> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:EmailAddresses** value.

<152> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:PhoneNumber** value.

[<153> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:ImAddress** value.

[<154> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:ImAddresses** value.

[<155> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:ImAddresses2** value.

[<156> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:ImAddresses3** value.

[<157> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:FolderIds** value.

[<158> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:Attributions** value.

[<159> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:DisplayNames** value.

[<160> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:Initials** value.

[<161> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:FileAses** value.

[<162> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:FileAsIds** value.

[<163> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:DisplayNamePrefixes** value.

[<164> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:GivenNames** value.

[<165> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:MiddleNames** value.

[<166> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:Surnames** value.

[<167> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:Generations** value.

[<168> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:Nicknames** value.

[<169> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:YomiCompanyNames** value.

[<170> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:YomiFirstNames** value.

[<171> Section 2.2.3.25:](#) Exchange 2007 and Exchange 2010 do not use the **persona:YomiLastNames** value.



<172> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:BusinessPhoneNumbers** value.

<173> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:BusinessPhoneNumbers2** value.

<174> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:HomePhones** value.

<175> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:HomePhones2** value.

<176> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:MobilePhones** value.

<177> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:MobilePhones2** value.

<178> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:AssistantPhoneNumbers** value.

<179> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:CallbackPhones** value.

<180> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:CarPhones** value.

<181> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:HomeFaxes** value.

<182> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:OrganizationMainPhones** value.

<183> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:OtherFaxes** value.

<184> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:OtherTelephones** value.

<185> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:OtherPhones2** value.

<186> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Pagers** value.

<187> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:RadioPhones** value.

<188> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:TelexNumbers** value.

<189> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:WorkFaxes** value.

<190> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Emails1** value.

<191> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Emails2** value.

<192> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Emails3** value.

<193> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:BusinessHomePages** value.

<194> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:School** value.

<195> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:PersonalHomePages** value.

<196> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:OfficeLocations** value.

<197> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:BusinessAddresses** value.

<198> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:HomeAddresses** value.

<199> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:OtherAddresses** value.

<200> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Titles** value.

<201> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Departments** value.

<202> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:CompanyNames** value.

<203> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Managers** value.

<204> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:AssistantNames** value.

<205> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Professions** value.

<206> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:SpouseNames** value.

<207> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Hobbies** value.

<208> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:WeddingAnniversaries** value.

<209> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Birthday** value.

<210> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Children** value.

<211> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Locations** value.

<212> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:ExtendedProperties** value.

<213> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:PostalAddress** value.

<214> [Section 2.2.3.25](#): Exchange 2007 and Exchange 2010 do not use the **persona:Bodies** value.

<215> [Section 2.2.4.6](#): Exchange 2007 and Exchange 2010 do not use the **ArrayOfHighlightTermsType** complex type.

<216> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **UpdateItemInRecoverableItemsResponseMessage** element.

<217> [Section 2.2.4.10](#): Exchange 2007 and the initial release version of Exchange 2010 do not include the **EmptyFolderResponseMessage** element.

<218> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **CreateFolderPathResponseMessage** element.

<219> [Section 2.2.4.10](#): Exchange 2007 and the initial release version of Exchange 2010 do not include the **UploadItemsResponseMessage** element.

<220> [Section 2.2.4.10](#): Exchange 2007 and the initial release version of Exchange 2010 do not include the **ExportItemsResponseMessage** element.

<221> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **MarkAllItemsAsReadResponseMessage** element.

<222> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetClientAccessTokenResponseMessage** element.

<223> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetClientExtensionResponseMessage**, element.

<224> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **ArchiveItemResponseMessage** element.

<225> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not include the **GetStreamingEventsResponseMessage** element.

<226> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetRemindersResponse** and **PerformReminderActionResponse** element.

<227> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetRemindersResponse** element.

<228> [Section 2.2.4.10](#): Exchange 2007 and the initial release version of Exchange 2010 do not include the **ApplyConversationActionResponseMessage** element.

<229> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **FindMailboxStatisticsByKeywordsResponseMessage** element.

<230> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetSearchableMailboxesResponseMessage** element.

<231> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **SearchMailboxesResponseMessage** element.

<232> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetDiscoverySearchConfigurationResponseMessage** element.

<233> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetHoldOnMailboxesResponseMessage** element.

<234> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **SetHoldOnMailboxesResponseMessage** element.

<235> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetNonIndexableItemStatisticsResponseMessage** element.

<236> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetNonIndexableItemDetailsResponseMessage** element.

<237> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **FindPeopleResponseMessage** element.

<238> [Section 2.2.4.10](#): Exchange 2007, the initial release version of Exchange 2010, and Exchange 2010 SP1 do not include the **GetPasswordExpirationDateResponse** element.

<239> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetPersonaResponseMessage** element.

<240> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetConversationItemsResponseMessage** element.

<241> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetUserRetentionPolicyTagsResponseMessage** element.

<242> [Section 2.2.4.10](#): Exchange 2007 and Exchange 2010 do not use the **GetUserPhotoResponseMessage** element.

<243> [Section 2.2.4.17](#): Exchange 2007 and Exchange 2010 do not use the **IsTruncated** value.

<244> [Section 2.2.4.18](#): Exchange 2007 and Exchange 2010 do not use the **ChangeHighlightsType** complex type.

<245> [Section 2.2.4.25](#): Exchange 2007 and Exchange 2010 do not include the **ViewPrivateItems** element.

<246> [Section 2.2.4.34](#): Exchange 2007 and Exchange 2010 do not use the **HighlightTermType** element.

<247> [Section 2.2.4.38](#): Exchange 2007 and Exchange 2010 do not include the **ConvertHtmlCodePageToUTF8** element.

<248> [Section 2.2.4.38](#): Exchange 2007 and Exchange 2010 do not use the **InlineImageUriTemplate** element.

<249> [Section 2.2.4.38](#): Exchange 2007 and Exchange 2010 do not use the **BlockExternalImages** element.

<250> [Section 2.2.4.38](#): Exchange 2007 and Exchange 2010 do not use the **AddBlankTargetToLinks** element.

<251> [Section 2.2.4.40](#): Exchange 2007 and Exchange 2010 do not use the **ManagementRoleType** complex type.

<252> [Section 2.2.4.45](#): Exchange 2007 and Exchange 2010 do not use the **NonEmptyArrayOfRoleType** complex type.

<253> [Section 2.2.4.64](#): Exchange 2007 and Exchange 2010 do not include the **FirstDayOfWeek** element.

<254> [Section 2.2.5.1](#): Exchange 2007, the initial release version of Exchange 2010, and Exchange 2010 SP1 do not include the **DateTimePrecision** element.

<255> [Section 2.2.5.7](#): Exchange 2007 and Exchange 2010 do not use the **ManagementRole** element.

<256> [Section 2.2.5.9](#): Exchange 2007 does not include the **RequestServerVersion** element. Exchange 2007 SP1 includes a **fixed** attribute with a value equal to Exchange2007\_SP1. The initial release version of Exchange 2010 includes a **fixed** attribute with a value equal to Exchange2010. Exchange 2010 SP1 includes a **fixed** attribute with a value equal to Exchange2010\_SP1. Exchange 2010 SP2 includes a fixed attribute with a value equal to Exchange2010\_SP2.

## 9 Change Tracking

This section identifies changes that were made to the [MS-OXWSCDATA] protocol document between the July 2012 and October 2012 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [protocol@microsoft.com](mailto:protocol@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">1.1 Glossary</a>	Added the terms Information Rights Management (IRM), recurring task, S/MIME (Secure/Multipurpose Internet Mail Extensions), and Short Message Service (SMS) to the list of terms defined in [MS-OXGLOS].	N	Content updated
<a href="#">1.2.2 Informative References</a>	Added the reference [MS-OXPROTO].	N	Content updated
<a href="#">1.4 Relationship to Other Protocols</a>	Added informative reference information for overview of relationships between this and other protocols.	N	Content updated
<a href="#">2.2.3 Simple Types</a>	Added the IconIndexType simple type to the table of simple types.	Y	Content updated
<a href="#">2.2.3.10 t:DistinguishedFolderIdNameType Simple Type</a>	Added the imcontactlist and peopleconnect enumeration values.	N	Content updated
<a href="#">2.2.3.11 t:DistinguishedPropertySetType Simple Type</a>	Added the Task and Sharing enumeration values.	N	Content updated
<a href="#">2.2.3.14 t:ExchangeVersionType Simple Type</a>	Changed "Exchange2012" enumeration value to "Exchange2013" enumeration value.	Y	Product behavior note

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
			updated .
<a href="#">2.2.3.14 t:ExchangeVersionType Simple Type</a>	Changed the "Exchange2012" enumeration value to "Exchange2013".	Y	Content updated .
<a href="#">2.2.3.16 t:IconIndexType Simple Type</a>	Added section to specify the IconIndexType simple type.	Y	New content added.
<a href="#">2.2.3.23 m:ResponseCodeType Simple Type</a>	Added the ErrorCannotGetExternalEcpUrl, ErrorClientIntentInvalidStateDefinition, ErrorClientIntentNotFound, and ErrorMultiLegacyMailboxAccess enumeration values.	N	Content updated .
<a href="#">2.2.3.23 m:ResponseCodeType Simple Type</a>	Added the ErrorPublicFolderMailboxDiscoveryFailed, ErrorPublicFolderOperationFailed, ErrorPublicFolderSyncException, and ErrorInvalidPhotoSize enumeration values.	N	Content updated .
<a href="#">2.2.3.23 m:ResponseCodeType Simple Type</a>	Added the ErrorSearchQueryHasTooManyKeywords, ErrorSearchTooManyMailboxes, and ErrorDiscoverySearchesDisabled enumeration values.	N	Content updated .
<a href="#">2.2.3.25 t:UnindexedFieldURIType Simple Type</a>	Added the item:IconIndex, conversation:IconIndex, conversation:GlobalIconIndex, and conversation:DraftItemIds enumeration values.	N	Content updated .
<a href="#">2.2.4.10 m:ArrayOfResponseMessagesType Complex Type</a>	Added the GetAppManifestsResponseMessage, GetDiscoverySearchConfigurationResponseMessage, and MarkAsJunkResponseMessage elements.	N	Content updated .
<a href="#">2.2.4.10 m:ArrayOfResponseMessagesType Complex Type</a>	Removed the GetClientExtensionManifestsResponseMessage, GetPopularClientExtensionsResponseMessage, and GetClientExtensionResponseMessage elements.	N	Content updated .
<a href="#">2.2.4.17 t:BodyType Complex Type</a>	Added the IsTruncated attribute.	N	Content updated .
<a href="#">2.2.4.27 t:EmailAddressType Complex Type</a>	Added the OriginalDisplayName element.	N	Content updated .
<a href="#">2.2.4.38 t:ItemResponseShapeType Complex Type</a>	Added the MaximumBodySize element.	N	Content updated .



Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">2.2.4.38 t:ItemResponseShapeType Complex Type</a>	Removed the ConvertInlineImagesToDataUrls element.	N	Content updated .
<a href="#">2.2.5.9 t:RequestServerVersion Element</a>	Updated fixed value of the Version attribute.	Y	Content updated .
<a href="#">7.1 Messages Schema</a>	Updated schema.	Y	Content updated .
<a href="#">7.2 Types Schema</a>	Updated schema.	Y	Content updated .

## 10 Index

### A

Abstract data model  
    [server](#) 138  
[Applicability](#) 9  
Attribute groups  
    [t:FindResponsePagingAttributes Attribute Group](#)  
        136  
[Attributes](#) 134

### C

[Capability negotiation](#) 9  
[Change tracking](#) 190  
Complex types  
    [m:ArrayOfResponseMessagesType Complex Type](#)  
        89  
    [m:BaseRequestType Complex Type](#) 99  
    [m:BaseResponseMessageType Complex Type](#) 99  
    [m:ItemInfoResponseMessageType Complex Type](#)  
        111  
    [m:ResponseMessageType Complex Type](#) 123  
    [t:AbsoluteMonthlyRecurrencePatternType](#)  
        Complex Type 83  
    [t:AbsoluteYearlyRecurrencePatternType Complex](#)  
        Type 84  
    [t:AcceptSharingInvitationType Complex Type](#) 85  
    [t:ArrayOfCalendarPermissionsType Complex Type](#)  
        85  
    [t:ArrayOfEmailAddressesType Complex Type](#) 85  
    [t:ArrayOfHighlightTermsType](#) 86  
    [t:ArrayOfPermissionsType Complex Type](#) 86  
    [t:ArrayOfRealItemsType Complex Type](#) 87  
    [t:ArrayOfRecipientsType Complex Type](#) 88  
    [t:ArrayOfStringsType Complex Type](#) 98  
    [t:BaseEmailAddressType Complex Type](#) 99  
    [t:BaseItemIdType Complex Type](#) 99  
    [t:BasePathToElementType Complex Type](#) 99  
    [t:BodyType Complex Type](#) 100  
    [t:ChangeHighlightsType](#) 100  
    [t:ConnectingSIDType Complex Type](#) 101  
    [t:ConstantValueType Complex Type](#) 102  
    [t:DailyRecurrencePatternType Complex Type](#) 102  
    [t:DeletedOccurrenceInfoType Complex Type](#) 102  
    [t:DistinguishedFolderIdType Complex Type](#) 103  
    [t:Duration Complex Type](#) 104  
    [t:EffectiveRightsType Complex Type](#) 104  
    [t:EmailAddressType Complex Type](#) 106  
    [t:EmailAddress](#) 105  
    [t:EndDateRecurrenceRangeType Complex Type](#)  
        107  
    [t:ExchangeImpersonationType Complex Type](#) 107  
    [t:FieldURIOrConstantType Complex Type](#) 108  
    [t:FolderIdType Complex Type](#) 108  
    [t:FolderResponseShapeType Complex Type](#) 109  
    [t:ForwardItemType Complex Type](#) 110  
    [t:HighlightTermType](#) 110  
    [t:InternetHeaderType Complex Type](#) 110

[t:IntervalRecurrencePatternBaseType Complex](#)  
        Type 111  
    [t:ItemResponseShapeType Complex Type](#) 112  
    [t:MailboxCultureType Complex Type](#) 113  
    [t:ManagementRoleType Complex Type](#) 114  
    [t:NoEndRecurrenceRangeType Complex Type](#) 114  
    [t:NonEmptyArrayOfAllItemsType Complex Type](#)  
        114  
    [t:NonEmptyArrayOfAttachmentsType Complex](#)  
        Type 117  
    [t:NonEmptyArrayOfPathsToElementType Complex](#)  
        Type 118  
    [t:NonEmptyArrayOfRoleType Complex Type](#) 118  
    [t:NumberedRecurrenceRangeType Complex Type](#)  
        118  
    [t:PathToExceptionFieldType Complex Type](#) 119  
    [t:PathToIndexedFieldType Complex Type](#) 119  
    [t:PathToUnindexedFieldType Complex Type](#) 120  
    [t:RecurrencePatternBaseType Complex Type](#) 120  
    [t:RecurrenceRangeBaseType Complex Type](#) 121  
    [t:RelativeMonthlyRecurrencePatternType](#)  
        Complex Type 121  
    [t:RelativeYearlyRecurrencePatternType Complex](#)  
        Type 122  
    [t:ReplyAllToItemType Complex Type](#) 122  
    [t:ReplyBody](#) 123  
    [t:ReplyToItemType Complex Type](#) 123  
    [t:ResponseObjectCoreType Complex Type](#) 125  
    [t:ResponseObjectType Complex Type](#) 125  
    [t:SingleRecipientType Complex Type](#) 126  
    [t:SuppressReadReceiptType Complex Type](#) 126  
    [t:UserIdType Complex Type](#) 126  
    [t:Value Complex Type](#) 127  
    [t:WeeklyRecurrencePatternType Complex Type](#)  
        128  
    [t:WellKnownResponseObjectType Complex Type](#)  
        128

### D

Data model - abstract  
    [server](#) 138

### E

Elements  
    [t:DateTimePrecision Element](#) 131  
    [t:ExceptionFieldURI Element](#) 131  
    [t:ExchangeImpersonation Element](#) 131  
    [t:FieldURI Element](#) 131  
    [t:IndexedFieldURI Element](#) 131  
    [t:MailboxCulture Element](#) 132  
    [t:ManagementRole Element](#) 132  
    [t:Path Element](#) 132  
    [t:RequestServerVersion Element](#) 132  
    [t:ServerVersionInfo Element](#) 133  
    [Value Element](#) 134  
Events

[local - server](#) 138  
[timer - server](#) 138

## F

[Fields - vendor-extensible](#) 9  
[Full WSDL](#) 141  
[Full XML Schema](#) 142  
[Messages Schema](#) 142  
[Types Schema](#) 153

## G

[Glossary](#) 6  
Groups  
[t:RecurrencePatternTypes Group](#) 134  
[t:RecurrenceRangeTypes Group](#) 135  
[t:TimeChangePatternTypes Group](#) 136

## I

[Implementer - security considerations](#) 140  
[Index of security parameters](#) 140  
[Informative references](#) 8  
Initialization  
[server](#) 138  
[Introduction](#) 6

## L

Local events  
[server](#) 138

## M

[m:ArrayOfResponseMessagesType Complex Type complex type](#) 89  
[m:BaseRequestType Complex Type complex type](#) 99  
[m:BaseResponseMessageType Complex Type complex type](#) 99  
[m:ItemInfoResponseMessageType Complex Type complex type](#) 111  
[m:ResponseCodeType Simple Type simple type](#) 27  
[m:ResponseMessageType Complex Type complex type](#) 123  
Message processing  
[server](#) 138  
Messages  
[attributes](#) 134  
[enumerated](#) 10  
[m:ArrayOfResponseMessagesType Complex Type complex type](#) 89  
[m:BaseRequestType Complex Type complex type](#) 99  
[m:BaseResponseMessageType Complex Type complex type](#) 99  
[m:ItemInfoResponseMessageType Complex Type complex type](#) 111  
[m:ResponseCodeType Simple Type simple type](#) 27

[m:ResponseMessageType Complex Type complex type](#) 123  
[namespaces](#) 10  
[PredictedMessageActionType simple type](#) 26  
[simple types](#) 10  
[syntax](#) 10  
[t:AbsoluteMonthlyRecurrencePatternType Complex Type complex type](#) 83  
[t:AbsoluteYearlyRecurrencePatternType Complex Type complex type](#) 84  
[t:AcceptSharingInvitationType Complex Type complex type](#) 85  
[t:ArrayOfCalendarPermissionsType Complex Type complex type](#) 85  
[t:ArrayOfEmailAddressesType Complex Type complex type](#) 85  
[t:ArrayOfHighlightTermsType complex type](#) 86  
[t:ArrayOfPermissionsType Complex Type complex type](#) 86  
[t:ArrayOfRealItemsType Complex Type complex type](#) 87  
[t:ArrayOfRecipientsType Complex Type complex type](#) 88  
[t:ArrayOfStringsType Complex Type complex type](#) 98  
[t:BaseEmailAddressType Complex Type complex type](#) 99  
[t:BaseItemIdType Complex Type complex type](#) 99  
[t:BasePathToElementType Complex Type complex type](#) 99  
[t:BodyType Complex Type complex type](#) 100  
[t:BodyTypeResponseType Simple Type simple type](#) 11  
[t:BodyTypeType Simple Type simple type](#) 12  
[t:ChangeHighlightsType complex type](#) 100  
[t:ConnectingSIDType Complex Type complex type](#) 101  
[t:ConstantValueType Complex Type complex type](#) 102  
[t:DailyRecurrencePatternType Complex Type complex type](#) 102  
[t:DateTimePrecision Element element](#) 131  
[t:DateTimePrecisionType Simple Type simple type](#) 12  
[t:DayOfWeekIndexType Simple Type simple type](#) 13  
[t:DayOfWeekType Simple Type simple type](#) 13  
[t:DaysOfWeekType Simple Type simple type](#) 14  
[t:DefaultShapeNamesType Simple Type simple type](#) 15  
[t:DeletedOccurrenceInfoType Complex Type complex type](#) 102  
[t:DictionaryURIType Simple Type simple type](#) 15  
[t:DisposalType Simple Type simple type](#) 16  
[t:DistinguishedFolderIdNameType Simple Type simple type](#) 16  
[t:DistinguishedFolderIdType Complex Type complex type](#) 103  
[t:DistinguishedPropertySetType Simple Type simple type](#) 19

[t:DistinguishedUserType Simple Type simple type](#) 19  
[t:Duration Complex Type complex type](#) 104  
[t:EffectiveRightsType Complex Type complex type](#) 104  
[t:EmailAddressType Complex Type complex type](#) 106  
[t:EmailAddress complex type](#) 105  
[t:EndDateRecurrenceRangeType Complex Type complex type](#) 107  
[t:ExceptionFieldURI Element element](#) 131  
[t:ExceptionPropertyURIType Simple Type simple type](#) 20  
[t:ExchangeImpersonation Element element](#) 131  
[t:ExchangeImpersonationType Complex Type complex type](#) 107  
[t:ExchangeVersionType Simple Type simple type](#) 21  
[t:ExcludesAttributeType Simple Type simple type](#) 21  
[t:FieldURI Element element](#) 131  
[t:FieldURIOrConstantType Complex Type complex type](#) 108  
[t:FindResponsePagingAttributes Attribute Group attribute group](#) 136  
[t:FolderIdType Complex Type complex type](#) 108  
[t:FolderResponseShapeType Complex Type complex type](#) 109  
[t:ForwardItemType Complex Type complex type](#) 110  
[t:HighlightTermType complex type](#) 110  
[t:IconIndexType Simple Type simple type](#) 22  
[t:IndexedFieldURI Element element](#) 131  
[t:InternetHeaderType Complex Type complex type](#) 110  
[t:IntervalRecurrencePatternBaseType Complex Type complex type](#) 111  
[t:ItemResponseShapeType Complex Type complex type](#) 112  
[t:LegacyFreeBusyType Simple Type simple type](#) 24  
[t:MailboxCulture Element element](#) 132  
[t:MailboxCultureType Complex Type complex type](#) 113  
[t:MailboxTypeType Simple Type simple type](#) 24  
[t:ManagementRole Element element](#) 132  
[t:ManagementRoleType Complex Type complex type](#) 114  
[t:MonthNamesType Simple Type simple type](#) 25  
[t:NoEndRecurrenceRangeType Complex Type complex type](#) 114  
[t:NonEmptyArrayOfAllItemsType Complex Type complex type](#) 114  
[t:NonEmptyArrayOfAttachmentsType Complex Type complex type](#) 117  
[t:NonEmptyArrayOfPathsToElementType Complex Type complex type](#) 118  
[t:NonEmptyArrayOfRoleType Complex Type complex type](#) 118  
[t:NonEmptyStringType Simple Type simple type](#) 26

[t:NumberedRecurrenceRangeType Complex Type complex type](#) 118  
[t:Path Element element](#) 132  
[t:PathToExceptionFieldType Complex Type complex type](#) 119  
[t:PathToIndexedFieldType Complex Type complex type](#) 119  
[t:PathToUnindexedFieldType Complex Type complex type](#) 120  
[t:RecurrencePatternBaseType Complex Type complex type](#) 120  
[t:RecurrencePatternTypes Group group](#) 134  
[t:RecurrenceRangeBaseType Complex Type complex type](#) 121  
[t:RecurrenceRangeTypes Group group](#) 135  
[t:RelativeMonthlyRecurrencePatternType Complex Type complex type](#) 121  
[t:RelativeYearlyRecurrencePatternType Complex Type complex type](#) 122  
[t:ReplyAllToItemType Complex Type complex type](#) 122  
[t:ReplyBody complex type](#) 123  
[t:ReplyToItemType Complex Type complex type](#) 123  
[t:RequestServerVersion Element element](#) 132  
[t:ResponseClassType Simple Type simple type](#) 27  
[t:ResponseObjectCoreType Complex Type complex type](#) 125  
[t:ResponseObjectType Complex Type complex type](#) 125  
[t:SensitivityChoicesType Simple Type simple type](#) 66  
[t:ServerVersionInfo Element element](#) 133  
[t:SingleRecipientType Complex Type complex type](#) 126  
[t:SuppressReadReceiptType Complex Type complex type](#) 126  
[t:TimeChangePatternTypes Group group](#) 136  
[t:UnindexedFieldURIType Simple Type simple type](#) 66  
[t:UserIdType Complex Type complex type](#) 126  
[t:Value Complex Type complex type](#) 127  
[t:WeeklyRecurrencePatternType Complex Type complex type](#) 128  
[t:WellKnownResponseType Complex Type complex type](#) 128  
[transport](#) 10  
[Value Element element](#) 134

## N

[Namespaces](#) 10  
[Normative references](#) 7

## O

[Overview \(synopsis\)](#) 8

## P

[Parameters - security index](#) 140  
[Preconditions](#) 9

[PredictedMessageActionType simple type](#) 26  
[Prerequisites](#) 9  
[Product behavior](#) 175

## R

[References](#) 7  
    [informative](#) 8  
    [normative](#) 7  
[Relationship to other protocols](#) 8

## S

Security  
    [implementer considerations](#) 140  
    [parameter index](#) 140  
Sequencing rules  
    [server](#) 138  
Server  
    [abstract data model](#) 138  
    [initialization](#) 138  
    [local events](#) 138  
    [message processing](#) 138  
    [sequencing rules](#) 138  
    [timer events](#) 138  
    [timers](#) 138  
Simple types 10  
    [m:ResponseCodeType Simple Type](#) 27  
    [PredictedMessageActionType](#) 26  
    [t:BodyTypeResponseType Simple Type](#) 11  
    [t:BodyTypeType Simple Type](#) 12  
    [t:DateTimePrecisionType Simple Type](#) 12  
    [t:DayOfWeekIndexType Simple Type](#) 13  
    [t:DayOfWeekType Simple Type](#) 13  
    [t:DaysOfWeekType Simple Type](#) 14  
    [t:DefaultShapeNamesType Simple Type](#) 15  
    [t:DictionaryURIType Simple Type](#) 15  
    [t:DisposalType Simple Type](#) 16  
    [t:DistinguishedFolderIdNameType Simple Type](#) 16  
    [t:DistinguishedPropertySetType Simple Type](#) 19  
    [t:DistinguishedUserType Simple Type](#) 19  
    [t:ExceptionPropertyURIType Simple Type](#) 20  
    [t:ExchangeVersionType Simple Type](#) 21  
    [t:ExcludesAttributeType Simple Type](#) 21  
    [t:IconIndexType Simple Type](#) 22  
    [t:LegacyFreeBusyType Simple Type](#) 24  
    [t:MailboxTypeType Simple Type](#) 24  
    [t:MonthNamesType Simple Type](#) 25  
    [t:NonEmptyStringType Simple Type](#) 26  
    [t:ResponseClassType Simple Type](#) 27  
    [t:SensitivityChoicesType Simple Type](#) 66  
    [t:UnindexedFieldURIType Simple Type](#) 66  
[Standards assignments](#) 9  
Syntax  
    [messages - overview](#) 10

## T

[t:AbsoluteMonthlyRecurrencePatternType Complex Type complex type](#) 83

[t:AbsoluteYearlyRecurrencePatternType Complex Type complex type](#) 84  
[t:AcceptSharingInvitationType Complex Type complex type](#) 85  
[t:ArrayOfCalendarPermissionsType Complex Type complex type](#) 85  
[t:ArrayOfEmailAddressesType Complex Type complex type](#) 85  
[t:ArrayOfHighlightTermsType complex type](#) 86  
[t:ArrayOfPermissionsType Complex Type complex type](#) 86  
[t:ArrayOfRealItemsType Complex Type complex type](#) 87  
[t:ArrayOfRecipientsType Complex Type complex type](#) 88  
[t:ArrayOfStringsType Complex Type complex type](#) 98  
[t:BaseEmailAddressType Complex Type complex type](#) 99  
[t:BaseItemIdType Complex Type complex type](#) 99  
[t:BasePathToElementType Complex Type complex type](#) 99  
[t:BodyType Complex Type complex type](#) 100  
[t:BodyTypeResponseType Simple Type simple type](#) 11  
[t:BodyTypeType Simple Type simple type](#) 12  
[t:ChangeHighlightsType complex type](#) 100  
[t:ConnectingSIDType Complex Type complex type](#) 101  
[t:ConstantValueType Complex Type complex type](#) 102  
[t:DailyRecurrencePatternType Complex Type complex type](#) 102  
[t:DateTimePrecision Element element](#) 131  
[t:DateTimePrecisionType Simple Type simple type](#) 12  
[t:DayOfWeekIndexType Simple Type simple type](#) 13  
[t:DayOfWeekType Simple Type simple type](#) 13  
[t:DaysOfWeekType Simple Type simple type](#) 14  
[t:DefaultShapeNamesType Simple Type simple type](#) 15  
[t:DeletedOccurrenceInfoType Complex Type complex type](#) 102  
[t:DictionaryURIType Simple Type simple type](#) 15  
[t:DisposalType Simple Type simple type](#) 16  
[t:DistinguishedFolderIdNameType Simple Type simple type](#) 16  
[t:DistinguishedFolderIdType Complex Type complex type](#) 103  
[t:DistinguishedPropertySetType Simple Type simple type](#) 19  
[t:DistinguishedUserType Simple Type simple type](#) 19  
[t:Duration Complex Type complex type](#) 104  
[t:EffectiveRightsType Complex Type complex type](#) 104  
[t:EmailAddressType Complex Type complex type](#) 106  
[t:EmailAddress complex type](#) 105  
[t:EndDateRecurrenceRangeType Complex Type complex type](#) 107

[t:ExceptionFieldURI Element element](#) 131  
[t:ExceptionPropertyURIType Simple Type simple type](#) 20  
[t:ExchangeImpersonation Element element](#) 131  
[t:ExchangeImpersonationType Complex Type complex type](#) 107  
[t:ExchangeVersionType Simple Type simple type](#) 21  
[t:ExcludesAttributeType Simple Type simple type](#) 21  
[t:FieldURI Element element](#) 131  
[t:FieldURIOrConstantType Complex Type complex type](#) 108  
[t:FindResponsePagingAttributes Attribute Group attribute group](#) 136  
[t:FolderIdType Complex Type complex type](#) 108  
[t:FolderResponseShapeType Complex Type complex type](#) 109  
[t:ForwardItemType Complex Type complex type](#) 110  
[t:HighlightTermType complex type](#) 110  
[t:IconIndexType Simple Type simple type](#) 22  
[t:IndexedFieldURI Element element](#) 131  
[t:InternetHeaderType Complex Type complex type](#) 110  
[t:IntervalRecurrencePatternBaseType Complex Type complex type](#) 111  
[t:ItemResponseShapeType Complex Type complex type](#) 112  
[t:LegacyFreeBusyType Simple Type simple type](#) 24  
[t:MailboxCulture Element element](#) 132  
[t:MailboxCultureType Complex Type complex type](#) 113  
[t:MailboxType Simple Type simple type](#) 24  
[t:ManagementRole Element element](#) 132  
[t:ManagementRoleType Complex Type complex type](#) 114  
[t:MonthNamesType Simple Type simple type](#) 25  
[t:NoEndRecurrenceRangeType Complex Type complex type](#) 114  
[t:NonEmptyArrayOfAllItemsType Complex Type complex type](#) 114  
[t:NonEmptyArrayOfAttachmentsType Complex Type complex type](#) 117  
[t:NonEmptyArrayOfPathsToElementType Complex Type complex type](#) 118  
[t:NonEmptyArrayOfRoleType Complex Type complex type](#) 118  
[t:NonEmptyStringType Simple Type simple type](#) 26  
[t:NumberedRecurrenceRangeType Complex Type complex type](#) 118  
[t:Path Element element](#) 132  
[t:PathToExceptionFieldType Complex Type complex type](#) 119  
[t:PathToIndexedFieldType Complex Type complex type](#) 119  
[t:PathToUnindexedFieldType Complex Type complex type](#) 120  
[t:RecurrencePatternBaseType Complex Type complex type](#) 120  
[t:RecurrencePatternTypes Group group](#) 134  
[t:RecurrenceRangeBaseType Complex Type complex type](#) 121  
[t:RecurrenceRangeTypes Group group](#) 135  
[t:RelativeMonthlyRecurrencePatternType Complex Type complex type](#) 121  
[t:RelativeYearlyRecurrencePatternType Complex Type complex type](#) 122  
[t:ReplyAllToItemType Complex Type complex type](#) 122  
[t:ReplyBody complex type](#) 123  
[t:ReplyToItemType Complex Type complex type](#) 123  
[t:RequestServerVersion Element element](#) 132  
[t:ResponseClassType Simple Type simple type](#) 27  
[t:ResponseObjectCoreType Complex Type complex type](#) 125  
[t:ResponseObjectType Complex Type complex type](#) 125  
[t:SensitivityChoicesType Simple Type simple type](#) 66  
[t:ServerVersionInfo Element element](#) 133  
[t:SingleRecipientType Complex Type complex type](#) 126  
[t:SuppressReadReceiptType Complex Type complex type](#) 126  
[t:TimeChangePatternTypes Group group](#) 136  
[t:UnindexedFieldURIType Simple Type simple type](#) 66  
[t:UserIdType Complex Type complex type](#) 126  
[t:Value Complex Type complex type](#) 127  
[t:WeeklyRecurrencePatternType Complex Type complex type](#) 128  
[t:WellKnownResponseObjectType Complex Type complex type](#) 128  
 Timer events  
   [server](#) 138  
 Timers  
   [server](#) 138  
[Tracking changes](#) 190  
[Transport](#) 10  
 Types  
   [simple](#) 10  
**V**  
[Value Element element](#) 134  
[Vendor-extensible fields](#) 9  
[Versioning](#) 9  
**W**  
[WSDL](#) 141  
**X**  
[XML Schema](#) 142  
   [Messages Schema](#) 142  
   [Types Schema](#) 153