

[MS-OXWSCEXT]: Client Extension Web Service Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

Date	Revision History	Revision Class	Comments
07/16/2012	0.1	New	Released new document.
10/08/2012	1.0	Major	Significantly changed the technical content.
02/11/2013	1.1	Minor	Clarified the meaning of the technical content.
07/26/2013	1.1	No change	No changes to the meaning, language, or formatting of the technical content.
11/18/2013	1.1	No change	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	6
1.2.1 Normative References	6
1.2.2 Informative References	7
1.3 Overview	7
1.4 Relationship to Other Protocols	8
1.5 Prerequisites/Preconditions	8
1.6 Applicability Statement	8
1.7 Versioning and Capability Negotiation	8
1.8 Vendor-Extensible Fields	9
1.9 Standards Assignments	9
2 Messages	10
2.1 Transport	10
2.2 Common Message Syntax	10
2.2.1 Namespaces	10
2.2.2 Messages	10
2.2.3 Elements	10
2.2.4 Complex Types	11
2.2.5 Simple Types	11
2.2.6 Attributes	11
2.2.7 Groups	11
2.2.8 Attribute Groups	11
3 Protocol Details	12
3.1 ExchangeServicePortType Server Details	12
3.1.1 Abstract Data Model	12
3.1.2 Timers	12
3.1.3 Initialization	12
3.1.4 Message Processing Events and Sequencing Rules	12
3.1.4.1 DisableApp	13
3.1.4.1.1 Messages	13
3.1.4.1.1.1 DisableAppSoapIn	13
3.1.4.1.1.2 DisableAppSoapOut	14
3.1.4.1.2 Elements	14
3.1.4.1.2.1 DisableApp	15
3.1.4.1.2.2 DisableAppResponse	15
3.1.4.1.3 Complex Types	15
3.1.4.1.3.1 DisableAppType	15
3.1.4.1.3.2 DisableAppResponseType	16
3.1.4.1.4 Simple Types	16
3.1.4.1.4.1 DisableReasonType	16
3.1.4.1.5 Attributes	17
3.1.4.1.6 Groups	17
3.1.4.1.7 Attribute Groups	17
3.1.4.2 GetAppManifests	17
3.1.4.2.1 Messages	17
3.1.4.2.1.1 GetAppManifestsSoapIn	18
3.1.4.2.1.2 GetAppManifestsSoapOut	18

3.1.4.2.2	Elements.....	19
3.1.4.2.2.1	GetAppManifests	19
3.1.4.2.2.2	GetAppManifestsResponse	19
3.1.4.2.3	Complex Types	19
3.1.4.2.3.1	GetAppManifestsType.....	19
3.1.4.2.3.2	GetAppManifestsResponseType	20
3.1.4.2.3.3	ArrayOfAppManifestsType	20
3.1.4.2.4	Simple Types.....	20
3.1.4.2.5	Attributes.....	20
3.1.4.2.6	Groups.....	21
3.1.4.2.7	Attribute Groups	21
3.1.4.3	GetAppMarketplaceUrl.....	21
3.1.4.3.1	Messages	21
3.1.4.3.1.1	GetAppMarketplaceUrlSoapIn	22
3.1.4.3.1.2	GetAppMarketplaceUrlSoapOut.....	22
3.1.4.3.2	Elements.....	23
3.1.4.3.2.1	GetAppMarketplaceUrl.....	23
3.1.4.3.2.2	GetAppMarketplaceUrlResponse	23
3.1.4.3.3	Complex Types	23
3.1.4.3.3.1	GetAppMarketplaceUrlType	24
3.1.4.3.3.2	GetAppMarketplaceUrlResponseMessageType.....	24
3.1.4.3.4	Simple Types.....	24
3.1.4.3.5	Attributes.....	24
3.1.4.3.6	Groups.....	24
3.1.4.3.7	Attribute Groups	25
3.1.4.4	GetClientAccessToken	25
3.1.4.4.1	Messages	25
3.1.4.4.1.1	GetClientAccessTokenSoapIn	25
3.1.4.4.1.2	GetClientAccessTokenSoapOut	26
3.1.4.4.2	Elements.....	27
3.1.4.4.2.1	GetClientAccessToken	27
3.1.4.4.2.2	GetClientAccessTokenResponse	27
3.1.4.4.3	Complex Types	27
3.1.4.4.3.1	GetClientAccessTokenType	28
3.1.4.4.3.2	NonEmptyArrayOfClientAccessTokenRequestsType	28
3.1.4.4.3.3	ClientAccessTokenRequestType	28
3.1.4.4.3.4	GetClientAccessTokenResponseMessageType	29
3.1.4.4.3.5	ClientAccessTokenType	29
3.1.4.4.3.6	GetClientAccessTokenResponseType	30
3.1.4.4.4	Simple Types.....	30
3.1.4.4.4.1	ClientAccessTokenTypeType.....	30
3.1.4.4.5	Attributes.....	31
3.1.4.4.6	Groups.....	31
3.1.4.4.7	Attribute Groups	31
3.1.4.5	InstallApp.....	31
3.1.4.5.1	Messages	31
3.1.4.5.1.1	InstallAppSoapIn.....	32
3.1.4.5.1.2	InstallAppSoapOut.....	32
3.1.4.5.2	Elements.....	33
3.1.4.5.2.1	InstallApp.....	33
3.1.4.5.2.2	InstallAppResponse.....	33
3.1.4.5.3	Complex Types	33
3.1.4.5.3.1	InstallAppType	33

3.1.4.5.3.2	InstallAppResponseType.....	34
3.1.4.5.4	Simple Types.....	34
3.1.4.5.5	Attributes.....	34
3.1.4.5.6	Groups.....	34
3.1.4.5.7	Attribute Groups	34
3.1.4.6	UninstallApp.....	34
3.1.4.6.1	Messages	35
3.1.4.6.1.1	UninstallAppSoapIn.....	35
3.1.4.6.1.2	UninstallAppSoapOut	36
3.1.4.6.2	Elements.....	36
3.1.4.6.2.1	UninstallApp	37
3.1.4.6.2.2	UninstallAppResponse	37
3.1.4.6.3	Complex Types	37
3.1.4.6.3.1	UninstallAppType.....	37
3.1.4.6.3.2	UninstallAppResponseType	37
3.1.4.6.4	Simple Types.....	38
3.1.4.6.5	Attributes.....	38
3.1.4.6.6	Groups.....	38
3.1.4.6.7	Attribute Groups	38
3.1.5	Timer Events	38
3.1.6	Other Local Events	38
4	Protocol Examples.....	39
4.1	Getting App Manifest Files.....	39
4.2	Getting a Client Access Token	40
4.3	Getting an App Marketplace URL.....	41
4.4	Installing a Mail App.....	42
4.5	Disabling a Mail App.....	43
4.6	Uninstalling a Mail App	43
5	Security.....	45
5.1	Security Considerations for Implementers.....	45
5.2	Index of Security Parameters	45
6	Appendix A: Full WSDL	46
7	Appendix B: Full XML Schema	49
7.1	http://schemas.microsoft.com/exchange/services/2006/messages Schema	49
7.2	http://schemas.microsoft.com/exchange/services/2006/types Schema	51
8	Appendix C: Product Behavior	53
9	Change Tracking.....	54
10	Index	55

1 Introduction

The Client Extension Web Service Protocol enables clients to use a **web service** to install, uninstall, and disable **mail apps**.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Hypertext Transfer Protocol (HTTP)
Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)
SOAP
SOAP action
SOAP body
SOAP header
XML
XML namespace

The following terms are defined in [\[MS-OXGLOS\]](#):

base64 encoding
endpoint
mail app
mailbox
Uniform Resource Locator (URL)
web service
Web Services Description Language (WSDL)
WSDL message
WSDL operation
WSDL port type
XML namespace prefix
XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site,

<http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXDCLI] Microsoft Corporation, "[Autodiscover Publishing and Lookup Protocol](#)".

[MS-OXWSADISC] Microsoft Corporation, "[Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol](#)".

[MS-OXWSCDATA] Microsoft Corporation, "[Common Web Service Data Types](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[WSIBASIC] Ballinger, K., Ehnebuske, D., Gudgin, M., et al., Eds., "Basic Profile Version 1.0", Final Material, April 2004, <http://www.ws-i.org/Profiles/BasicProfile-1.0-2004-04-16.html>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., Eds., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OWEMXML] Microsoft Corporation, "[Office Web Extensibility Manifest Format](#)".

[MS-OWEXML] Microsoft Corporation, "[Office Web Extensibility Extensions to Office Open XML Structure Specification](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

1.3 Overview

The Client Extension Web Service Protocol enables clients to use a web service to manage client apps. It provides operations to install, uninstall, and disable client apps. This protocol also provides operations to retrieve and manage the access token, the manifest file, and the landing page for a mail app.

1.4 Relationship to Other Protocols

This protocol is used by clients that implement support for Office Web Extensions, as described in [\[MS-OWEXML\]](#) and the Office Web Extensibility Manifest Format, as described in [\[MS-OWEMXML\]](#).

A client that implements this protocol can use the Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol, as described in [\[MS-OXWSADISC\]](#), or the Autodiscover Publishing and Lookup Protocol, as described in [\[MS-OXDCLI\]](#), to identify the target **endpoint (4)** to use for each operation.

This protocol uses **SOAP**, as described in [\[SOAP1.1\]](#), to specify the structure information that is exchanged between the client and the server. This protocol uses the **XML schema**, as described in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), to describe the message content that is sent to and from the server.

This protocol uses SOAP over **HTTP**, as described in [\[RFC2616\]](#), and SOAP over **HTTPS**, as described in [\[RFC2818\]](#), as shown in the following layering diagram.




Figure 1: This protocol in relation to other protocols

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

1.5 Prerequisites/Preconditions

The operations that this protocol defines cannot be accessed unless the correct endpoint (4) is identified in the HTTP web requests that target this protocol. This endpoint (4) **URL** is returned by either the Autodiscover Publishing Lookup SOAP-Based Web Service Protocol, as specified in [\[MS-OXWSADISC\]](#), or the Autodiscover Publishing and Lookup Protocol, as specified in [\[MS-OXDCLI\]](#).

1.6 Applicability Statement

This protocol is applicable to environments that use web services to implement client extensions for a user's **mailbox**. This protocol is applicable to all SOAP-based clients, as described in [\[SOAP1.1\]](#).

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Supported Transports:** This protocol uses SOAP 1.1, as described in section [2.1](#).
- **Protocol Versions:** This protocol describes only one **WSDL port type** version. The **RequestServerVersion** element, as described in [\[MS-OXWSCDATA\]](#) section 2.2.3.9, identifies the WSDL port type version of the request. The **ServerVersionInfo** element, as described in

[\[MS-OXWSCDATA\]](#) section 2.2.3.10 , identifies the version of the server responding to the request.

- **Security and Authentication Methods:** This protocol relies on the web server that is hosting it to perform authentication.
- **Capability Negotiation:** This protocol does not support version negotiation.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The **Web Services Description Language (WSDL)** in this specification provides a base description of the protocol. The schema in this specification provides a base description of the message syntax. The text that specifies the WSDL and schema might specify restrictions that reflect actual protocol behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the protocol as specified restricts the same elements to being non-empty, not null, or present.

2.1 Transport

This protocol uses SOAP 1.1, as specified in [\[SOAP1.1\]](#).

This protocol **MUST** support SOAP over HTTP, as specified in [\[RFC2616\]](#). The protocol **SHOULD** use secure communications by means of HTTPS, as specified in [\[RFC2818\]](#).

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses XML schema, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and Web Services Description Language (WSDL), as specified in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific **XML namespace prefix** for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
m	http://schemas.microsoft.com/exchange/services/2006/messages	
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
t	http://schemas.microsoft.com/exchange/services/2006/types	
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
wsi	http://ws-i.org/schemas/conformanceClaim/	[WSIBASIC]
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1] [XMLSCHEMA2]

2.2.2 Messages

This specification does not define any common **WSDL message** definitions.

2.2.3 Elements

This specification does not define any common XML schema element definitions.

2.2.4 Complex Types

This specification does not define any common XML schema complex type definitions.

2.2.5 Simple Types

This specification does not define any common XML schema simple type definitions.

2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

3 Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

In the following sections, the schema definition might be less restrictive than the processing rules imposed by the protocol. The WSDL in this specification matches the WSDL that shipped with the product and provides a base description of the schema. The text that introduces the WSDL specifies additional restrictions that reflect actual Microsoft product behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the protocol as specified restricts the same elements to being non-empty, not null and present.

3.1 ExchangeServicePortType Server Details

This protocol defines a single WSDL port type with operations that enable clients to install, uninstall, or disable client apps.

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

The following table summarizes the list of operations as defined by this specification.

Operation	Description
DisableApp	The DisableApp WSDL operation disables a mail app.
GetAppManifests	The GetAppManifests WSDL operation retrieves the manifest files for a mail app.
GetAppMarketplaceUrl	The GetAppMarketplaceUrl WSDL operation retrieves the URL of the marketplace landing page for the mail app. The following is the WSDL port type specification of the GetAppMarketplaceUrl WSDL operation.
GetClientAccessToken	The GetClientAccessToken WSDL operation retrieves a client access token.
InstallApp	The InstallApp WSDL operation installs a mail app.
UninstallApp	The UninstallApp WSDL operation uninstalls a mail app.

3.1.4.1 DisableApp

The **DisableApp** WSDL operation disables a mail app.

The following is the WSDL port type specification of the **DisableApp** WSDL operation.

```
<wsdl:operation name="DisableApp" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="m:DisableAppSoapIn"/>
  <wsdl:output message="m:DisableAppSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **DisableApp** WSDL operation.

```
<wsdl:operation name="DisableApp" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/DisableApp"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  <wsdl:input>
    <soap:header message="m:DisableAppSoapIn" part="RequestVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:body use="literal" parts="request"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" parts="DisableAppResult"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:header message="m:DisableAppSoapOut" part="ServerVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:output>
</wsdl:operation>
```

The protocol client sends a **DisableAppSoapIn** request WSDL message and the protocol server responds with a **DisableAppSoapOut** response WSDL message.

3.1.4.1.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DisableAppSoapIn	Specifies a request to disable a mail app.
DisableAppSoapOut	Specifies the response to the DisableAppSoapIn request WSDL message.

3.1.4.1.1.1 DisableAppSoapIn

The **DisableAppSoapIn** request WSDL message specifies a request to disable a mail app.

The following is the **DisableAppSoapIn** WSDL message specification.

```
<wsdl:message name="DisableAppSoapIn" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="m:DisableApp"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

</wsdl:message>

The **DisableAppSoapIn** WSDL message is the input message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/DisableApp>.

The parts of the **DisableAppSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	DisableApp	Specifies the SOAP body of the request to disable a mail app.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the DisableApp WSDL operation request.

3.1.4.1.1.2 DisableAppSoapOut

The **DisableAppSoapOut** WSDL message specifies the response to the **DisableApp** request WSDL message.

The following is the **DisableAppSoapOut** WSDL message specification.

```
<wsdl:message name="DisableAppSoapOut" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">  
  <wsdl:part name="DisableAppResult" element="m:DisableAppResponse"/>  
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>  
</wsdl:message>
```

The **DisableAppSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/DisableApp>.

The parts of the **DisableAppSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
DisableAppResult	DisableAppResponse	Specifies the SOAP body of the response.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **DisableApp** WSDL operation request returns a **DisableAppResponse** element with the **ResponseClass** attribute set to "Success". The **ResponseCode** element of the **DisableAppResponse** element is set to "NoError".

If the **DisableApp** WSDL operation is not successful, it returns a **DisableAppResponse** element with the **ResponseClass** attribute set to "Error". The **ResponseCode** element of the **DisableAppResponse** element is set to one of the common errors defined in [\[MS-OXWSCDATA\]](#) section 2.2.5.23.

3.1.4.1.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DisableApp	The input data for the DisableApp WSDL operation.
DisableAppResponse	The result data for the DisableApp WSDL operation.

3.1.4.1.2.1 DisableApp

The **DisableApp** element specifies the input data for the **DisableApp** WSDL operation.

```
<xs:element name="DisableApp" type="m:DisableAppType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.1.2.2 DisableAppResponse

The **DisableAppResponse** element specifies the result data for the **DisableApp** WSDL operation.

```
<xs:element name="DisableAppResponse" type="m:DisableAppResponseType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.1.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
DisableAppResponseType	Specifies the response to a DisableApp WSDL operation request.
DisableAppType	Specifies a request to disable a mail app.

3.1.4.1.3.1 DisableAppType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **DisableAppType** complex type specifies a request to disable a mail app. This type extends the **BaseRequestType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.15.

```
<xs:complexType name="DisableAppType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="ID" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="DisableReason"
type="t:DisableReasonType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

ID: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#), that identifies the mail app.

DisableReason: An element of type **DisableReasonType** that specifies the reason to disable the mail app.

3.1.4.1.3.2 DisableAppResponseType

Namespace: http://schemas.microsoft.com/exchange/services/2006/messages

The **DisableAppResponseType** complex type specifies the response to a **DisableApp** WSDL operation request. This type extends the **ResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.57.

```
<xs:complexType name="DisableAppResponseType" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexContent mixed="false">  
    <xs:extension base="m:ResponseMessageType"/>  
  </xs:complexContent>  
</xs:complexType>
```

3.1.4.1.4 Simple Types

The following table summarizes the XML schema simple type definitions that are specific to this operation.

Simple type	Description
DisableReasonType	Indicates the reason the mail app is being disabled.

3.1.4.1.4.1 DisableReasonType

Namespace: http://schemas.microsoft.com/exchange/services/2006/types

The **DisableReasonType** simple type indicates the reason the mail app is being disabled.

```
<xs:simpleType name="DisableReasonType" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:restriction base="xs:string">  
    <xs:enumeration value="NoReason"/>  
    <xs:enumeration value="OutlookClientPerformance"/>  
    <xs:enumeration value="OWAClientPerformance"/>  
    <xs:enumeration value="MobileClientPerformance"/>  
  </xs:restriction>  
</xs:simpleType>
```

The following table specifies the allowable values for the **DisableReasonType** simple type.

Value	Meaning
NoReason	No reason specified.
OutlookClientPerformance	The mail app is being disabled from the messaging client due to performance.
OWAClientPerformance	The mail app is being disabled from the web client due to performance.
MobileClientPerformance	The mail app is being disabled from the mobile client due to performance.

3.1.4.1.5 Attributes

None.

3.1.4.1.6 Groups

None.

3.1.4.1.7 Attribute Groups

None.

3.1.4.2 GetAppManifests

The **GetAppManifests** WSDL operation retrieves the manifest files for a mail app.

The following is the WSDL port type specification of the **GetAppManifests** WSDL operation.

```
<wsdl:operation name="GetAppManifests" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="m:GetAppManifestsSoapIn"/>
  <wsdl:output message="m:GetAppManifestsSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **GetAppManifests** WSDL operation.

```
<wsdl:operation name="GetAppManifests" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetAppManifests"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  <wsdl:input>
    <soap:header message="m:GetAppManifestsSoapIn" part="RequestVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:body use="literal" parts="request"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" parts="GetAppManifestsResult"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:header message="m:GetAppManifestsSoapOut" part="ServerVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:output>
</wsdl:operation>
```

3.1.4.2.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAppManifestsSoapIn	Specifies a request to retrieve mail app manifest files.
GetAppManifestsSoapOut	Specifies the response to the GetAppManifestsSoapIn request WSDL message.

3.1.4.2.1.1 GetAppManifestsSoapIn

The **GetAppManifestsSoapIn** WSDL message specifies a request to retrieve mail app manifest files.

The following is the **GetAppManifestsSoapIn** WSDL message specification.

```
<wsdl:message name="GetAppManifestsSoapIn" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="m:GetAppManifests"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

The **GetAppManifestsSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetAppManifests>.

The parts of the **GetAppManifestsSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	GetAppManifests	Specifies the SOAP body of the request to retrieve manifest files.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the GetAppManifests WSDL operation request.

3.1.4.2.1.2 GetAppManifestsSoapOut

The **GetAppManifestsSoapOut** WSDL message specifies the response to the **GetAppManifestsSoapIn** request WSDL message.

The following is the **GetAppManifestsSoapOut** WSDL message specification.

```
<wsdl:message name="GetAppManifestsSoapOut" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="GetAppManifestsResult" element="m:GetAppManifestsResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **GetAppManifestsSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetAppManifests>.

The parts of the **GetAppManifestsSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
GetAppManifestsResult	GetAppManifestsResponse	Specifies the SOAP body of the response.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **GetAppManifests** WSDL operation request returns a **GetAppManifestsResponse** element with the **ResponseClass** attribute set to "Success". The **ResponseCode** element of the **GetAppManifestsResponse** element is set to "NoError".

If the **GetAppManifests** WSDL operation is not successful, it returns a **GetAppManifestsResponse** element with the **ResponseClass** attribute set to "Error". The **ResponseCode** element of the **GetAppManifestsResponse** element is set to one of the common errors defined in [\[MS-OXWSCDATA\]](#) section 2.2.5.23.

3.1.4.2.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAppManifests	The input data for the GetAppManifests WSDL operation.
GetAppManifestsResponse	The result data for the GetAppManifests WSDL operation.

3.1.4.2.2.1 GetAppManifests

The **GetAppManifests** element specifies the input data for the **GetAppManifests** WSDL operation.

```
<xs:element name="GetAppManifests" type="m:GetAppManifestsType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.2.2.2 GetAppManifestsResponse

The **GetAppManifestsResponse** element specifies the result data for the **GetAppManifests** WSDL operation.

```
<xs:element name="GetAppManifestsResponse" type="m:GetAppManifestsResponseType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.2.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfAppManifestsType	Specifies an array of mail app manifest files.
GetAppManifestsResponseType	Specifies the response to a GetAppManifests WSDL operation request
GetAppManifestsType	Specifies a request to retrieve mail app manifest files.

3.1.4.2.3.1 GetAppManifestsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetAppManifestsType** complex type specifies a request to retrieve mail app manifest files. This type extends the **BaseRequestType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.15.

```
<xs:complexType name="GetAppManifestsType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType"/>
  </xs:complexContent>
</xs:complexType>
```

3.1.4.2.3.2 GetAppManifestsResponseType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetAppManifestsResponseType** complex type specifies the response to a **GetAppManifests** WSDL operation request. This type extends the **ResponseMessageType**, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.57.

```
<xs:complexType name="GetAppManifestsResponseType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType">
      <xs:sequence>
        <xs:element maxOccurs="1" name="Manifests" type="m:ArrayOfAppManifestsType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Manifests: An element of type **ArrayOfAppManifestsType** that represents an array of mail app manifest files encoded with **base64 encoding**.

3.1.4.2.3.3 ArrayOfAppManifestsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **ArrayOfAppManifestsType** complex type specifies an array of mail app manifest files.

```
<xs:complexType name="ArrayOfAppManifestsType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Manifest" type="xs:base64Binary"/>
  </xs:sequence>
</xs:complexType>
```

Manifest: An element of type **base64Binary**, as defined in [\[XMLSCHEMA2\]](#), that represents a mail app manifest file encoded with base64 encoding.

3.1.4.2.4 Simple Types

None.

3.1.4.2.5 Attributes

None.

3.1.4.2.6 Groups

None.

3.1.4.2.7 Attribute Groups

None.

3.1.4.3 GetAppMarketplaceUrl

The **GetAppMarketplaceUrl** WSDL operation retrieves the URL of the marketplace landing page for the mail app.

The following is the WSDL port type specification of the **GetAppMarketplaceUrl** WSDL operation.

The following is the WSDL port type specification of the **GetAppMarketplaceUrl** WSDL operation.

```
<wsdl:operation name="GetAppMarketplaceUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="m:GetAppMarketplaceUrlSoapIn"/>
  <wsdl:output message="m:GetAppMarketplaceUrlSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification for the **GetAppMarketplaceUrl** WSDL operation.

```
<wsdl:operation name="GetAppMarketplaceUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetAppMarketplaceUrl"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  <wsdl:input>
    <soap:header message="m:GetAppMarketplaceUrlSoapIn" part="RequestVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:body use="literal" parts="request"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" parts="GetAppMarketplaceUrlResult"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:header message="m:GetAppMarketplaceUrlSoapOut" part="ServerVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:output>
</wsdl:operation>
```

The protocol client sends a **GetAppMarketplaceUrlSoapIn** request WSDL message and the protocol server responds with a **GetAppMarketplaceUrlSoapOut** response WSDL message.

3.1.4.3.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAppMarketplaceUrlSoapIn	Specifies a request to retrieve the marketplace URL.
GetAppMarketplaceUrlSoapOut	Specifies the response to the GetAppMarketplaceUrlSoapIn

Message	Description
	request WSDL message.

3.1.4.3.1.1 GetAppMarketplaceUriSoapIn

The **GetAppMarketplaceUriSoapIn** WSDL message specifies a request to retrieve the marketplace URL.

The following is the **GetAppMarketplaceUriSoapIn** WSDL message specification.

```
<wsdl:message name="GetAppMarketplaceUriSoapIn"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="m:GetAppMarketplaceUri"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

The **GetAppMarketplaceUriSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetAppMarketplaceUri>.

The parts of the **GetAppMarketplaceUriSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	GetAppMarketplaceUri	Specifies the SOAP body of the request to retrieve the marketplace URL.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the GetAppMarketplaceUri WSDL operation request.

3.1.4.3.1.2 GetAppMarketplaceUriSoapOut

The **GetAppMarketplaceUriSoapOut** WSDL message specifies the response to a **GetAppMarketplaceUriSoapIn** request WSDL message.

The following is the **GetAppMarketplaceUriSoapOut** WSDL message specification.

```
<wsdl:message name="GetAppMarketplaceUriSoapOut"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="GetAppMarketplaceUriResult" element="m:GetAppMarketplaceUriResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **GetAppMarketplaceUriSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetAppMarketplaceUri>.

The parts of the **GetAppMarketplaceUriSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
GetAppMarketplaceUriResult	GetAppMarketplaceUriResponse	Specifies the SOAP body of the

Part name	Element/type	Description
		response.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **GetAppMarketplaceUrl** WSDL operation request returns a **GetAppMarketplaceUrlResponse** element with the **ResponseClass** attribute set to "Success". The **ResponseCode** element of the **GetAppMarketplaceUrlResponse** element is set to "NoError".

If the **GetAppMarketplaceUrl** WSDL operation is not successful, it returns a **GetAppMarketplaceUrlResponse** element with the **ResponseClass** attribute set to "Error". The **ResponseCode** element of the **GetAppMarketplaceUrlResponse** element is set to one of the common errors defined in [\[MS-OXWSCDATA\]](#) section 2.2.5.23.

3.1.4.3.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAppMarketplaceUrl	The input data for the GetAppMarketplaceUrl WSDL operation.
GetAppMarketplaceUrlResponse	The result data for the GetAppMarketplaceUrl WSDL operation.

3.1.4.3.2.1 GetAppMarketplaceUrl

The **GetAppMarketplaceUrl** element specifies the input data for the **GetAppMarketplaceUrl** WSDL operation.

```
<xs:element name="GetAppMarketplaceUrl" type="m:GetAppMarketplaceUrlType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.3.2.2 GetAppMarketplaceUrlResponse

The **GetAppMarketplaceUrlResponse** element specifies the result data for the **GetAppMarketplaceUrl** WSDL operation.

```
<xs:element name="GetAppMarketplaceUrlResponse"
type="m:GetAppMarketplaceUrlResponseMessageType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.3.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
GetAppMarketplaceUrlResponseMessageType	Specifies the response message for a

Complex type	Description
	GetAppMarketplaceUri WSDL operation request.
GetAppMarketplaceUriType	Specifies a request to retrieve the marketplace URL.

3.1.4.3.3.1 GetAppMarketplaceUriType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetAppMarketplaceUriType** complex type specifies a request to retrieve the marketplace URL for a mail app. This type extends the **BaseRequestType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.15.

```
<xs:complexType name="GetAppMarketplaceUriType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType"/>
  </xs:complexContent>
</xs:complexType>
```

3.1.4.3.3.2 GetAppMarketplaceUriResponseMessageType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetAppMarketplaceUriResponseMessageType** complex type specifies the response to a **GetAppMarketplaceUri** WSDL operation request. This type extends the **ResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.57.

```
<xs:complexType name="GetAppMarketplaceUriResponseMessageType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="AppMarketplaceUri" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

AppMarketplaceUri: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#), that specifies the URL for the mail app.

3.1.4.3.4 Simple Types

None.

3.1.4.3.5 Attributes

None.

3.1.4.3.6 Groups

None.

3.1.4.3.7 Attribute Groups

None.

3.1.4.4 GetClientAccessToken

The **GetClientAccessToken** WSDL operation retrieves a client access token.

The following is the WSDL port type specification of the **GetClientAccessToken** WSDL operation.

```
<wsdl:operation name="GetClientAccessToken" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="m:GetClientAccessTokenSoapIn"/>
  <wsdl:output message="m:GetClientAccessTokenSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **GetClientAccessToken** WSDL operation.

```
<wsdl:operation name="GetClientAccessToken" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetClientAccessToken"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  <wsdl:input>
    <soap:header message="m:GetClientAccessTokenSoapIn" part="RequestVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:body use="literal" parts="request"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" parts="GetClientAccessTokenResult"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:header message="m:GetClientAccessTokenSoapOut" part="ServerVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:output>
</wsdl:operation>
```

The protocol client sends a **GetClientAccessTokenSoapIn** request WSDL message and the protocol server responds with a **GetClientAccessTokenSoapOut** response WSDL message.

3.1.4.4.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetClientAccessTokenSoapIn	Specifies a request to retrieve a client access token.
GetClientAccessTokenSoapOut	Specifies the response to a GetClientAccessTokenSoapIn request WSDL message.

3.1.4.4.1.1 GetClientAccessTokenSoapIn

The **GetClientAccessTokenSoapIn** WSDL message specifies a request to retrieve a client access token.

The following is the **GetClientAccessTokenSoapIn** WSDL message specification.

```
<wsdl:message name="GetClientAccessTokenSoapIn"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="m:GetClientAccessToken"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

The **GetClientAccessTokenSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetClientAccessToken>.

The parts of the **GetClientAccessTokenSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	GetClientAccessToken	Specifies the SOAP body of the request to retrieve the client access token.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the GetClientAccessToken WSDL operation request.

3.1.4.4.1.2 GetClientAccessTokenSoapOut

The **GetClientAccessTokenSoapOut** WSDL message specifies the response to a **GetClientAccessToken** WSDL operation request.

The following is the **GetClientAccessTokenSoapOut** WSDL message specification.

```
<wsdl:message name="GetClientAccessTokenSoapOut"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="GetClientAccessTokenResult" element="m:GetClientAccessTokenResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **GetClientAccessTokenSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetClientAccessToken>.

The parts of the **GetClientAccessTokenSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
GetClientAccessTokenResult	GetClientAccessTokenResponse	Specifies the SOAP body of the response that contains the requested information.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **GetClientAccessToken** WSDL operation request returns a **GetClientAccessTokenResponse** element with the **ResponseClass** attribute set to "Success". The **ResponseCode** element of the **GetClientAccessTokenResponse** element is set to "NoError".

If the **GetClientAccessToken** WSDL operation is not successful, it returns a **GetClientAccessTokenResponse** element with the **ResponseClass** attribute set to "Error". The **ResponseCode** element of the **GetClientAccessTokenResponse** element is set to one of the common errors defined in [\[MS-OXWSCDATA\]](#) section 2.2.5.23.

3.1.4.4.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetClientAccessToken	The input data for the GetClientAccessToken WSDL operation.
GetClientAccessTokenResponse	The result data for the GetClientAccessToken WSDL operation.

3.1.4.4.2.1 GetClientAccessToken

The **GetClientAccessToken** element specifies the input data for the **GetClientAccessToken** WSDL operation.

```
<xs:element name="GetClientAccessToken" type="m:GetClientAccessTokenType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.4.2.2 GetClientAccessTokenResponse

The **GetClientAccessTokenResponse** element specifies the result data for the **GetClientAccessToken** WSDL operation.

```
<xs:element name="GetClientAccessTokenResponse" type="m:GetClientAccessTokenResponseType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.4.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
ClientAccessTokenRequestType	Identifies the request type for a client access token.
ClientAccessTokenType	Specifies a client access token.
GetClientAccessTokenResponseMessageType	Specifies a response message for a GetClientAccessToken WSDL operation request.
GetClientAccessTokenResponseType	Specifies the response to a GetClientAccessToken WSDL operation

Complex type	Description
	request.
GetClientAccessTokenType	Specifies a request to retrieve a client access token.
NonEmptyArrayOfClientAccessTokenRequestsType	Specifies an array of client access token requests.

3.1.4.4.3.1 GetClientAccessTokenType

Namespace: http://schemas.microsoft.com/exchange/services/2006/messages

The **GetClientAccessTokenType** complex type specifies a request to retrieve a client access token. This type extends the **BaseRequestType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.15.

```
<xs:complexType name="GetClientAccessTokenType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="TokenRequests"
          type="t:NonEmptyArrayOfClientAccessTokenRequestsType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

TokenRequests: An element of type **NonEmptyArrayOfClientAccessTokenRequestsType** that specifies an array of client access token requests.

3.1.4.4.3.2 NonEmptyArrayOfClientAccessTokenRequestsType

Namespace: http://schemas.microsoft.com/exchange/services/2006/types

The **NonEmptyArrayOfClientAccessTokenRequestsType** complex type specifies an array of client access token requests.

```
<xs:complexType name="NonEmptyArrayOfClientAccessTokenRequestsType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element maxOccurs="unbounded" name="TokenRequest"
      type="t:ClientAccessTokenRequestType"/>
  </xs:sequence>
</xs:complexType>
```

TokenRequest: An element of type **ClientAccessTokenRequestType** that represents a single token request.

3.1.4.4.3.3 ClientAccessTokenRequestType

Namespace: http://schemas.microsoft.com/exchange/services/2006/types

The **ClientAccessTokenRequestType** complex type identifies the request type for a client access token.

```
<xs:complexType name="ClientAccessTokenRequestType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element name="Id" type="xs:string"/>
    <xs:element name="TokenType" type="t:ClientAccessTokenType"/>
  </xs:sequence>
</xs:complexType>
```

Id: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#), that contains the identifier of the mail app.

TokenType: An element of type **ClientAccessTokenType** that identifies the type of token that will be returned in the response.

3.1.4.4.3.4 GetClientAccessTokenResponseMessageType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetClientAccessTokenResponseMessageType** complex type specifies a response message for a **GetClientAccessToken** WSDL operation request. This type extends the **ResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.57.

```
<xs:complexType name="GetClientAccessTokenResponseMessageType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType">
      <xs:sequence>
        <xs:element minOccurs="0" name="Token" type="t:ClientAccessTokenType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Token: An element of type **ClientAccessTokenType** that represents the client access token.

3.1.4.4.3.5 ClientAccessTokenType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ClientAccessTokenType** complex type specifies a client access token.

```
<xs:complexType name="ClientAccessTokenType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element name="Id" type="xs:string"/>
    <xs:element name="TokenType" type="t:ClientAccessTokenType"/>
    <xs:element name="TokenValue" type="xs:string"/>
    <xs:element name="TTL" type="xs:integer"/>
  </xs:sequence>
</xs:complexType>
```

Id: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#), that represents a client access token identifier.

TokenType: An element of type **ClientAccessTokenTypeType** that represents the type of the token.

TokenValue: An element of type **string** that represents the value of the token.

TTL: An element of type **integer**, as defined in [\[XMLSCHEMA2\]](#), that represents the time to live for the token.

3.1.4.4.3.6 GetClientAccessTokenResponseType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetClientAccessTokenResponseType** complex type specifies the response to a **GetClientAccessToken** WSDL operation request. This type extends the **BaseResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.16.

```
<xs:complexType name="GetClientAccessTokenResponseType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseResponseMessageType"/>
  </xs:complexContent>
</xs:complexType>
```

3.1.4.4.4 Simple Types

The following table summarizes the XML schema simple type definitions that are specific to this operation.

Simple type	Description
ClientAccessTokenTypeType	Specifies the type of a client access token.

3.1.4.4.4.1 ClientAccessTokenTypeType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ClientAccessTokenTypeType** simple type specifies the type of a client access token.

```
<xs:simpleType name="ClientAccessTokenTypeType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="CallerIdentity"/>
    <xs:enumeration value="ExtensionCallback"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **ClientAccessTokenTypeType** simple type.

Value	Meaning
CallerIdentity	Indicates a caller identity client access token.

Value	Meaning
ExtensionCallback	Indicates an extension callback client access token.

3.1.4.4.5 Attributes

None.

3.1.4.4.6 Groups

None.

3.1.4.4.7 Attribute Groups

None.

3.1.4.5 InstallApp

The **InstallApp** WSDL operation installs a mail app.

The following is the WSDL port type specification of the **InstallApp** WSDL operation.

```
<wsdl:operation name="InstallApp" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="m:InstallAppSoapIn"/>
  <wsdl:output message="m:InstallAppSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **InstallApp** WSDL operation.

```
<wsdl:operation name="InstallApp" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/InstallApp"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    <wsdl:input>
      <soap:header message="m:InstallAppSoapIn" part="RequestVersion" use="literal"
        xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      <soap:body use="literal" parts="request"
        xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal" parts="InstallAppResult"
          xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
        <soap:header message="m:InstallAppSoapOut" part="ServerVersion" use="literal"
          xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
        </wsdl:output>
      </wsdl:operation>
```

3.1.4.5.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
InstallAppSoapIn	Specifies a request to install an app.
InstallAppSoapOut	Specifies the response to the InstallAppSoapIn request WSDL message.

3.1.4.5.1.1 InstallAppSoapIn

The **InstallAppSoapIn** WSDL message specifies a request to install a mail app.

The following is the **InstallAppSoapIn** WSDL message specification.

```
<wsdl:message name="InstallAppSoapIn" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="m:InstallApp"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

The **InstallAppSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/InstallApp>.

The parts of the **InstallAppSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	InstallApp	Specifies the SOAP body of the request to install a mail app.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the InstallApp WSDL operation request.

3.1.4.5.1.2 InstallAppSoapOut

The **InstallAppSoapOut** WSDL message specifies the response to the **InstallAppSoapIn** request.

The following is the **InstallAppSoapOut** WSDL message specification.

```
<wsdl:message name="InstallAppSoapOut" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="InstallAppResult" element="m:InstallAppResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **InstallAppSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/InstallApp>.

The parts of the **InstallAppSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
InstallAppResult	InstallAppResponse	Specifies the SOAP body of the response.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section)	Specifies a SOAP header that identifies the server version for the response.

Part name	Element/type	Description
	2.2.3.10)	

A successful **InstallApp** WSDL operation request returns an **InstallAppResponse** element with the **ResponseClass** attribute set to "Success". The **ResponseCode** element of the **InstallAppResponse** element is set to "NoError".

If the **InstallApp** WSDL operation is not successful, it returns an **InstallAppResponse** element with the **ResponseClass** attribute set to "Error". The **ResponseCode** element of the **InstallAppResponse** element is set to one of the common errors defined in [\[MS-OXWSCDATA\]](#) section 2.2.5.23.

3.1.4.5.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
InstallApp	The input data for the InstallApp WSDL operation.
InstallAppResponse	The result data for the InstallApp WSDL operation.

3.1.4.5.2.1 InstallApp

The **InstallApp** element specifies the input data for the **InstallApp** WSDL operation.

```
<xs:element name="InstallApp" type="m:InstallAppType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.5.2.2 InstallAppResponse

The **InstallAppResponse** element specifies the result data for the **InstallApp** WSDL operation.

```
<xs:element name="InstallAppResponse" type="m:InstallAppResponseType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.5.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
InstallAppResponseType	Specifies the response to an InstallApp WSDL operation request.
InstallAppType	Specifies a request to install a mail app.

3.1.4.5.3.1 InstallAppType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **InstallAppType** complex type specifies a request to install a mail app. This type extends the **BaseRequestType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.15.

```
<xs:complexType name="InstallAppType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="Manifest" type="xs:base64Binary"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Manifest: An element of type **base64Binary**, as defined in [\[XMLSCHEMA2\]](#), that contains the mail app manifest file encoded with base64 encoding.

3.1.4.5.3.2 InstallAppResponseType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **InstallAppResponseType** complex type specifies the response to an **InstallApp** WSDL operation request. This type extends the **ResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.57.

```
<xs:complexType name="InstallAppResponseType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType"/>
  </xs:complexContent>
</xs:complexType>
```

3.1.4.5.4 Simple Types

None.

3.1.4.5.5 Attributes

None.

3.1.4.5.6 Groups

None.

3.1.4.5.7 Attribute Groups

None.

3.1.4.6 UninstallApp

The **UninstallApp** WSDL operation uninstalls a mail app.

The following is the WSDL port type specification of the **UninstallApp** WSDL operation.

```
<wsdl:operation name="UninstallApp" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="m:UninstallAppSoapIn"/>
</wsdl:operation>
```

```
<wsdl:output message="m:UninstallAppSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **UninstallApp** WSDL operation.

```
<wsdl:operation name="UninstallApp" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/Uninstall"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  <wsdl:input>
    <soap:header message="m:UninstallAppSoapIn" part="RequestVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:body use="literal" parts="request"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" parts="UninstallAppResult"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
    <soap:header message="m:UninstallAppSoapOut" part="ServerVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" />
  </wsdl:output>
</wsdl:operation>
```

The protocol client sends an **UninstallAppSoapIn** request WSDL message and the protocol server responds with an **UninstallAppSoapOut** response WSDL message.

3.1.4.6.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UninstallAppSoapIn	Specifies a request to uninstall a mail app.
UninstallAppSoapOut	Specifies the response to the UninstallAppSoapIn request WSDL message.

3.1.4.6.1.1 UninstallAppSoapIn

The **UninstallAppSoapIn** WSDL message specifies a request to uninstall a mail app.

The following is the **UninstallAppSoapIn** WSDL message specification.

```
<wsdl:message name="UninstallAppSoapIn" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="m:UninstallApp"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

The **UninstallAppSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/UninstallApp>.

The parts of the **UninstallAppSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	UninstallApp	Specifies the SOAP body of the request to uninstall a mail app.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the UninstallApp WSDL operation request.

3.1.4.6.1.2 UninstallAppSoapOut

The **UninstallAppSoapOut** WSDL message specifies the response to the **UninstallAppSoapIn** request WSDL message.

The following is the **UninstallAppSoapOut** WSDL message specification.

```
<wsdl:message name="UninstallAppSoapOut" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="UninstallAppResult" element="m:UninstallAppResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **UninstallAppSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/UninstallApp>.

The parts of the **UninstallAppSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
UninstallAppResult	UninstallAppResponse	Represents the result of the operation.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **UninstallApp** WSDL operation request returns an **UninstallAppResponse** element with the **ResponseClass** attribute set to "Success". The **ResponseCode** element of the **UninstallAppResponse** element is set to "NoError".

If the **UninstallApp** WSDL operation is not successful, it returns an **UninstallAppResponse** element with the **ResponseClass** attribute set to "Error". The **ResponseCode** element of the **UninstallAppResponse** element is set to one of the common errors defined in [\[MS-OXWSCDATA\]](#) section 2.2.5.23.

3.1.4.6.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UninstallApp	The input data for the UninstallApp WSDL operation.
UninstallAppResponse	The result data for the UninstallApp WSDL operation.

3.1.4.6.2.1 UninstallApp

The **UninstallApp** element specifies the input data for the **UninstallApp** WSDL operation.

```
<xs:element name="UninstallApp" type="m:UninstallAppType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.6.2.2 UninstallAppResponse

The **UninstallAppResponse** element specifies the result data for the **UninstallApp** WSDL operation.

```
<xs:element name="UninstallAppResponse" type="m:UninstallAppResponseType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.6.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
UninstallAppResponseType	Specifies the response to an UninstallApp WSDL operation request.
UninstallAppType	Specifies a request to uninstall a mail app.

3.1.4.6.3.1 UninstallAppType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **UninstallAppType** complex type specifies a request to uninstall a mail app. This type extends the **BaseRequestType**, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.15.

```
<xs:complexType name="UninstallAppType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="ID" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

ID: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#), that specifies the identifier of the mail app.

3.1.4.6.3.2 UninstallAppResponseType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **UninstallAppResponseType** complex type specifies the response to an **UninstallApp** WSDL operation request. This type extends the **ResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.57.

```
<xs:complexType name="UninstallAppResponseType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType"/>
  </xs:complexContent>
</xs:complexType>
```

3.1.4.6.4 Simple Types

None.

3.1.4.6.5 Attributes

None.

3.1.4.6.6 Groups

None.

3.1.4.6.7 Attribute Groups

None.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

4.1 Getting App Manifest Files

This example of the **GetAppManifests** operation, as defined in section [3.1.4.2](#), shows how a client can retrieve the manifest files for mail apps from the server. The client sends the following request.

```
<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2013" />
    <t:MailboxCulture>en-US</t:MailboxCulture>
    <t:TimeZoneContext>
      <t:TimeZoneDefinition Id="GMT Standard Time"/>
    </t:TimeZoneContext>
  </soap:Header>
  <soap:Body >
    <m:GetAppManifests/>
  </soap:Body>
</soap:Envelope>
```

The server sends the following successful response to the client. The response returns four manifest files. Each file is an **XML** file encoded with base64 encoding. The contents of the files have been abbreviated for readability.

```
<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="15"
      MinorVersion="0"
      MajorBuildNumber="556"
      MinorBuildNumber="14"
      Version="Exchange2013"
      xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xsd="http://www.w3.org/2001/XMLSchema"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <GetAppManifestsResponse ResponseClass="Success"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
      <ResponseCode>NoError</ResponseCode>
      <m:Manifests xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
        <Manifest>PE9mZmljZUFwcCB4bWxucz0iaH</Manifest>
        <Manifest>PE9mZmljZUFwcCB4bWxucz0iaH</Manifest>
        <Manifest>PE9mZmljZUFwcCB4bWxucz0iaH</Manifest>
        <Manifest>PE9mZmljZUFwcCB4bWxucz0iaH</Manifest>
      </m:Manifests>
    </GetAppManifestsResponse>
  </s:Body>
</s:Envelope>
```



```

        <t:TTL>479</t:TTL>
    </m:Token>
</m:GetClientAccessTokenResponseMessage>
</m:ResponseMessages>
</m:GetClientAccessTokenResponse>
</s:Body>
</s:Envelope>

```

4.3 Getting an App Marketplace URL

This example of the **GetAppMarketplaceUrl** operation, as defined in section [3.1.4.3](#), shows how the client can retrieve the URL of the marketplace landing page for the mail app.

```

<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
    xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
    xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
    <soap:Header>
        <t:RequestServerVersion Version="Exchange2013" />
        <t:MailboxCulture>en-US</t:MailboxCulture>
        <t:TimeZoneContext>
            <t:TimeZoneDefinition Id="GMT Standard Time"/>
        </t:TimeZoneContext>
    </soap:Header>
    <soap:Body >
        <m:GetAppMarketplaceUrl/>
    </soap:Body>
</soap:Envelope>

```

The server sends the following successful response to the client.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
    <s:Header>
        <h:ServerVersionInfo MajorVersion="15"
            MinorVersion="0"
            MajorBuildNumber="556"
            MinorBuildNumber="14"
            Version="Exchange2013"
            xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns:xsd="http://www.w3.org/2001/XMLSchema"
            xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
    </s:Header>
    <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xmlns:xsd="http://www.w3.org/2001/XMLSchema">
        <GetAppMarketplaceUrlResponse ResponseClass="Success"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
            <ResponseCode>NoError</ResponseCode>
            <AppMarketplaceUrl>http://o15.officeredir.microsoft.com/r/r1idMktplcExchRedirect?app=outlook.
            exe&amp;ver=15&amp;clid=1033&amp;p1=15d0d556d14&amp;p2=4&amp;p3=0&amp;p4=HP&amp;p5=0&amp;Scop
            e=1&amp;CallBackURL=https%3a%2f%2fch1pr03.outlook.com%2fecp%2fExtension%2finstallFromURL.slab
            %3fexsvurl%3d1%2526realm%3dmicrosoft.com</AppMarketplaceUrl>
        </GetAppMarketplaceUrlResponse>
    </s:Body>

```

```
</s:Envelope>
```

4.4 Installing a Mail App

This example of the **InstallApp** operation, as defined in section [3.1.4.5](#), shows how the client sends a request to the server to install a mail app. The manifest file of the mail app has been abbreviated for readability.

```
<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2013" />
    <t:MailboxCulture>en-US</t:MailboxCulture>
    <t:TimeZoneContext>
      <t:TimeZoneDefinition Id="GMT Standard Time"/>
    </t:TimeZoneContext>
  </soap:Header>
  <soap:Body >
    <m:InstallApp>
      <m:Manifest>PE9mZmljZUFwcCB4bWxucz0iaHR0cDovL3NjaG=</m:Manifest>
    </m:InstallApp>
  </soap:Body>
</soap:Envelope>
```

The server sends the following successful response to the client.

```
<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="15"
      MinorVersion="0"
      MajorBuildNumber="556"
      MinorBuildNumber="14"
      Version="Exchange2013"
      xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xsd="http://www.w3.org/2001/XMLSchema"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <InstallAppResponse ResponseClass="Success"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
      <ResponseCode>NoError</ResponseCode>
    </InstallAppResponse>
  </s:Body>
</s:Envelope>
```

4.5 Disabling a Mail App

This example of the **DisableApp** operation, as defined in section [3.1.4.1](#), shows how the client sends a request to the server to disable a mail app. The ID of the app is in the manifest file.

```
<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2013" />
    <t:MailboxCulture>en-US</t:MailboxCulture>
    <t:TimeZoneContext>
      <t:TimeZoneDefinition Id="GMT Standard Time"/>
    </t:TimeZoneContext>
  </soap:Header>
  <soap:Body >
    <m:DisableApp>
      <m:ID>1C50226D-04B5-4AB2-9FCD-42E236B59E4B</m:ID>
      <m:DisableReason>NoReason</m:DisableReason>
    </m:DisableApp>
  </soap:Body>
</soap:Envelope>
```

The server sends the following successful response to the client.

```
<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="15"
      MinorVersion="0"
      MajorBuildNumber="556"
      MinorBuildNumber="14"
      Version="Exchange2013"
      xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:s="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xsd="http://www.w3.org/2001/XMLSchema"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <DisableAppResponse ResponseClass="Success"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
      <ResponseCode>NoError</ResponseCode>
    </DisableAppResponse>
  </s:Body>
</s:Envelope>
```

4.6 Uninstalling a Mail App

This example of the **UninstallApp** operation, as defined in section [3.1.4.6](#), shows how the client sends a request to the server to uninstall a mail app. The ID of the app is in the manifest file.

```
<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
```

```

        xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
        xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
<soap:Header>
  <t:RequestServerVersion Version="Exchange2013" />
</soap:Header>
<soap:Body >
  <m:UninstallApp>
    <m:ID>1C50226D-04B5-4AB2-9FCD-42E236B59E4B</m:ID>
  </m:UninstallApp>
</soap:Body>
</soap:Envelope>

```

The server sends the following successful response to the client.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="15"
      MinorVersion="0"
      MajorBuildNumber="556"
      MinorBuildNumber="14"
      Version="Exchange2013"
      xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xsd="http://www.w3.org/2001/XMLSchema"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <UninstallAppResponse ResponseClass="Success"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
      <ResponseCode>NoError</ResponseCode>
    </UninstallAppResponse>
  </s:Body>
</s:Envelope>

```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

Preliminary

6 Appendix A: Full WSDL

For ease of implementation, the full WSDL is provided in this appendix.

```
<?xml version="1.0"?>
<wsdl:definitions xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <xs:schema elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
version="Exchange2013" id="messages" xmlns:xs="http://www.w3.org/2001/XMLSchema">
      <xs:include schemaLocation="MS-OXWSCEXT-messages.xsd"/>
    </xs:schema>
  </wsdl:types>
  <wsdl:portType name="ExchangeServicePortType">
    <wsdl:operation name="DisableApp">
      <wsdl:input message="m:DisableAppSoapIn"/>
      <wsdl:output message="m:DisableAppSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="GetAppManifests">
      <wsdl:input message="m:GetAppManifestsSoapIn"/>
      <wsdl:output message="m:GetAppManifestsSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="GetAppMarketplaceUrl">
      <wsdl:input message="m:GetAppMarketplaceUrlSoapIn"/>
      <wsdl:output message="m:GetAppMarketplaceUrlSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="GetClientAccessToken">
      <wsdl:input message="m:GetClientAccessTokenSoapIn"/>
      <wsdl:output message="m:GetClientAccessTokenSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="InstallApp">
      <wsdl:input message="m:InstallAppSoapIn"/>
      <wsdl:output message="m:InstallAppSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="UninstallApp">
      <wsdl:input message="m:UninstallAppSoapIn"/>
      <wsdl:output message="m:UninstallAppSoapOut"/>
    </wsdl:operation>
  </wsdl:portType>
  <wsdl:binding name="ExchangeServiceBinding" type="m:ExchangeServicePortType">
    <wsdl:documentation>
      <wsi:Claim conformsTo="http://ws-i.org/profiles/basic/1.0" xmlns:wsi="http://ws-
i.org/schemas/conformanceClaim/">
    </wsdl:documentation>
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="DisableApp">
      <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/DisableApp"/>
      <wsdl:input>
        <soap:header message="m:DisableAppSoapIn" part="RequestVersion" use="literal"/>
        <soap:body use="literal" parts="request"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal" parts="DisableAppResult"/>
        <soap:header message="m:DisableAppSoapOut" part="ServerVersion" use="literal"/>
      </wsdl:output>
    </wsdl:operation>
  </wsdl:binding>

```

```

        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetClientAccessToken">
        <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetClientAccessToken
"/>
        <wsdl:input>
            <soap:header message="m:GetClientAccessTokenSoapIn" part="RequestVersion"
use="literal"/>
            <soap:body use="literal" parts="request"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" parts="GetClientAccessTokenResult"/>
            <soap:header message="m:GetClientAccessTokenSoapOut" part="ServerVersion"
use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetAppManifests">
        <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetAppManifests"/>
        <wsdl:input>
            <soap:header message="m:GetAppManifestsSoapIn" part="RequestVersion" use="literal"/>
            <soap:body use="literal" parts="request"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" parts="GetAppManifestsResult"/>
            <soap:header message="m:GetAppManifestsSoapOut" part="ServerVersion" use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetAppMarketplaceUrl">
        <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetAppMarketplaceUrl
"/>
        <wsdl:input>
            <soap:header message="m:GetAppMarketplaceUrlSoapIn" part="RequestVersion"
use="literal"/>
            <soap:body use="literal" parts="request"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" parts="GetAppMarketplaceUrlResult"/>
            <soap:header message="m:GetAppMarketplaceUrlSoapOut" part="ServerVersion"
use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="InstallApp">
        <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/InstallApp"/>
        <wsdl:input>
            <soap:header message="m:InstallAppSoapIn" part="RequestVersion" use="literal"/>
            <soap:body use="literal" parts="request"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" parts="InstallAppResult"/>
            <soap:header message="m:InstallAppSoapOut" part="ServerVersion" use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UninstallApp">
        <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/Uninstall"/>
        <wsdl:input>

```

```

        <soap:header message="m:UninstallAppSoapIn" part="RequestVersion" use="literal"/>
        <soap:body use="literal" parts="request"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal" parts="UninstallAppResult"/>
        <soap:header message="m:UninstallAppSoapOut" part="ServerVersion" use="literal"/>
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:message name="DisableAppSoapIn">
    <wsdl:part name="request" element="m:DisableApp"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="DisableAppSoapOut">
    <wsdl:part name="DisableAppResult" element="m:DisableAppResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="GetAppManifestsSoapIn">
    <wsdl:part name="request" element="m:GetAppManifests"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="GetAppManifestsSoapOut">
    <wsdl:part name="GetAppManifestsResult" element="m:GetAppManifestsResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="GetAppMarketplaceUrlSoapIn">
    <wsdl:part name="request" element="m:GetAppMarketplaceUrl"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="GetAppMarketplaceUrlSoapOut">
    <wsdl:part name="GetAppMarketplaceUrlResult" element="m:GetAppMarketplaceUrlResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="GetClientAccessTokenSoapIn">
    <wsdl:part name="request" element="m:GetClientAccessToken"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="GetClientAccessTokenSoapOut">
    <wsdl:part name="GetClientAccessTokenResult" element="m:GetClientAccessTokenResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="InstallAppSoapIn">
    <wsdl:part name="request" element="m:InstallApp"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="InstallAppSoapOut">
    <wsdl:part name="InstallAppResult" element="m:InstallAppResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="UninstallAppSoapIn">
    <wsdl:part name="request" element="m:UninstallApp"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="UninstallAppSoapOut">
    <wsdl:part name="UninstallAppResult" element="m:UninstallAppResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
</wsdl:definitions>

```


7 Appendix B: Full XML Schema

Schema name	Prefix	Section
http://schemas.microsoft.com/exchange/services/2006/messages	m	7.1
http://schemas.microsoft.com/exchange/services/2006/types	t	7.2

For ease of implementation, the following sections provide the full XML schema for this protocol.

7.1 <http://schemas.microsoft.com/exchange/services/2006/messages> Schema

This section contains the contents of the MS-OXWSCEXT-messages.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSCEXT-messages.xsd includes the files listed in the following table. For the schema file to operate correctly, these files have to be in the folder that contains the WSDL, types schema, and messages schema files for this protocol.

File name	Defining specification
MS-OXWSCDATA-messages.xsd	[MS-OXWSCDATA] section 7.1
MS-OXWSCEXT-types.xsd	section 7.2

```
<?xml version="1.0"?>
<xs:schema xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  elementFormDefault="qualified"
  targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
  version="Exchange2013" id="messages" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:include schemaLocation="MS-OXWSCDATA-messages.xsd"/>
  <xs:include schemaLocation="MS-OXWSCEXT-messages.xsd"/>
  <xs:import schemaLocation="MS-OXWSCEXT-types.xsd"
  namespace="http://schemas.microsoft.com/exchange/services/2006/types"/>
  <xs:complexType name="ArrayOfAppManifestsType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="Manifest"
      type="xs:base64Binary"/>
    </xs:sequence>
  </xs:complexType>
  <xs:element name="GetClientAccessToken" type="m:GetClientAccessTokenType"/>
  <xs:complexType name="GetClientAccessTokenResponseMessageType">
    <xs:complexContent mixed="false">
      <xs:extension base="m:ResponseMessageType">
        <xs:sequence>
          <xs:element minOccurs="0" name="Token" type="t:ClientAccessTokenType"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="GetClientAccessTokenResponseType">
    <xs:complexContent mixed="false">
      <xs:extension base="m:BaseResponseMessageType"/>
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="GetClientAccessTokenResponse" type="m:GetClientAccessTokenResponseType"/>
</xs:schema>
```

```

<xs:complexType name="GetClientAccessTokenType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="TokenRequests"
type="t:NonEmptyArrayOfClientAccessTokenRequestsType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="GetAppManifestsResponse" type="m:GetAppManifestsResponseType"/>
<xs:complexType name="GetAppManifestsResponseType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType">
      <xs:sequence>
        <xs:element maxOccurs="1" name="Manifests" type="m:ArrayOfAppManifestsType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="GetAppManifests" type="m:GetAppManifestsType"/>
<xs:complexType name="GetAppManifestsType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="GetAppMarketplaceUrlType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType"/>
  </xs:complexContent>
</xs:complexType>
<xs:element name="GetAppMarketplaceUrl" type="m:GetAppMarketplaceUrlType"/>
<xs:element name="GetAppMarketplaceUrlResponse"
type="m:GetAppMarketplaceUrlResponseMessageType"/>
<xs:complexType name="GetAppMarketplaceUrlResponseMessageType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="AppMarketplaceUrl" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="InstallAppType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="Manifest" type="xs:base64Binary"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="InstallApp" type="m:InstallAppType"/>
<xs:complexType name="InstallAppResponseType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType"/>
  </xs:complexContent>
</xs:complexType>
<xs:element name="InstallAppResponse" type="m:InstallAppResponseType"/>

```

```

<xs:complexType name="UninstallAppType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="ID" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="UninstallApp" type="m:UninstallAppType"/>
<xs:complexType name="UninstallAppResponseType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType"/>
  </xs:complexContent>
</xs:complexType>
<xs:element name="UninstallAppResponse" type="m:UninstallAppResponseType"/>
<xs:complexType name="DisableAppType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="ID" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="DisableReason"
type="t:DisableReasonType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="DisableApp" type="m:DisableAppType"/>
<xs:complexType name="DisableAppResponseType">
  <xs:complexContent mixed="false">
    <xs:extension base="m:ResponseMessageType"/>
  </xs:complexContent>
</xs:complexType>
<xs:element name="DisableAppResponse" type="m:DisableAppResponseType"/>
</xs:schema>

```

7.2 <http://schemas.microsoft.com/exchange/services/2006/types> Schema

This section contains the contents of the MS-OXWSCEXT-types.xsd file.

```

<?xml version="1.0"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
version="Exchange2013" id="types" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
  <xs:complexType name="ClientAccessTokenRequestType">
    <xs:sequence>
      <xs:element name="Id" type="xs:string"/>
      <xs:element name="TokenType" type="t:ClientAccessTokenTypeType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ClientAccessTokenType">
    <xs:sequence>
      <xs:element name="Id" type="xs:string"/>
      <xs:element name="TokenType" type="t:ClientAccessTokenTypeType"/>
      <xs:element name="TokenValue" type="xs:string"/>
      <xs:element name="TTL" type="xs:integer"/>
    </xs:sequence>
  </xs:complexType>

```

```
</xs:sequence>
</xs:complexType>
<xs:simpleType name="ClientAccessTokenTypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="CallerIdentity"/>
    <xs:enumeration value="ExtensionCallback"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DisableReasonType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NoReason"/>
    <xs:enumeration value="OutlookClientPerformance"/>
    <xs:enumeration value="OWAClientPerformance"/>
    <xs:enumeration value="MobileClientPerformance"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="NonEmptyArrayOfClientAccessTokenRequestsType">
  <xs:sequence>
    <xs:element maxOccurs="unbounded" name="TokenRequest"
type="t:ClientAccessTokenRequestType"/>
  </xs:sequence>
</xs:complexType>
</xs:schema>
```

8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Exchange Server 2013
- Microsoft Outlook 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

9 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

Preliminary

10 Index

A

Abstract data model
 [server](#) 12
[Applicability](#) 8
[Attribute groups](#) 11
[Attributes](#) 11

C

[Capability negotiation](#) 8
[Change tracking](#) 54
[Complex types](#) 11

D

Data model - abstract
 [server](#) 12
[Disabling a mail app example](#) 43

E

Events
 [local - server](#) 38
 [timer - server](#) 38

Examples

[disabling a mail app](#) 43
[getting a client access token](#) 40
[getting an app Marketplace URL](#) 41
[getting app manifest files](#) 39
[installing a mail app](#) 42
[uninstalling a mail app](#) 43

F

[Fields - vendor-extensible](#) 9
[Full WSDL](#) 46
[Full XML Schema](#) 49
 <http://schemas.microsoft.com/exchange/services/2006/messages> Schema 49
 <http://schemas.microsoft.com/exchange/services/2006/types> Schema 51

G

[Getting a client access token example](#) 40
[Getting an app Marketplace URL example](#) 41
[Getting app manifest files example](#) 39
[Glossary](#) 6
[Groups](#) 11

I

[Implementer - security considerations](#) 45
[Index of security parameters](#) 45
[Informative references](#) 7
Initialization
 [server](#) 12
[Installing a mail app example](#) 42

[Introduction](#) 6

L

Local events
 [server](#) 38

M

Message processing
 [server](#) 12
Messages
 [attribute groups](#) 11
 [attributes](#) 11
 [complex types](#) 11
 [elements](#) 10
 [enumerated](#) 10
 [groups](#) 11
 [namespaces](#) 10
 [simple types](#) 11
 [syntax](#) 10
 [transport](#) 10

N

[Namespaces](#) 10
[Normative references](#) 6

O

Operations
 [DisableApp](#) 13
 [GetAppManifests](#) 17
 [GetAppMarketplaceUrl](#) 21
 [GetClientAccessToken](#) 25
 [InstallApp](#) 31
 [UninstallApp](#) 34
[Overview \(synopsis\)](#) 7

P

[Parameters - security index](#) 45
[Preconditions](#) 8
[Prerequisites](#) 8
[Product behavior](#) 53
Protocol Details
 [overview](#) 12

R

[References](#) 6
 [informative](#) 7
 [normative](#) 6
[Relationship to other protocols](#) 8

S

Security
 [implementer considerations](#) 45

[parameter index](#) 45
Sequencing rules
 [server](#) 12
Server
 [abstract data model](#) 12
 [DisableApp operation](#) 13
 [GetAppManifests operation](#) 17
 [GetAppMarketplaceUrl operation](#) 21
 [GetClientAccessToken operation](#) 25
 [initialization](#) 12
 [InstallApp operation](#) 31
 [local events](#) 38
 [message processing](#) 12
 [sequencing rules](#) 12
 [timer events](#) 38
 [timers](#) 12
 [UninstallApp operation](#) 34
[Simple types](#) 11
[Standards assignments](#) 9
Syntax
 [messages - overview](#) 10

T

Timer events
 [server](#) 38
Timers
 [server](#) 12
[Tracking changes](#) 54
[Transport](#) 10
Types
 [complex](#) 11
 [simple](#) 11

U

[Uninstalling a mail app example](#) 43

V

[Vendor-extensible fields](#) 9
[Versioning](#) 8

W

[WSDL](#) 46

X

[XML Schema](#) 49
 <http://schemas.microsoft.com/exchange/services/2006/messages> Schema 49
 <http://schemas.microsoft.com/exchange/services/2006/types> Schema 51