

[MS-OXWScore]: Core Items Web Service Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final

documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

Date	Revision History	Revision Class	Comments
07/15/2009	1.0	Major	Initial Availability.
11/04/2009	1.1.0	Minor	1.1.0
02/10/2010	1.1.0	None	Version 1.1.0 release
05/05/2010	1.1.1	Editorial	Revised and edited the technical content.
08/04/2010	2.0	Major	Significantly changed the technical content.
11/03/2010	3.0	Major	Significantly changed the technical content.
03/18/2011	4.0	Major	Significantly changed the technical content.
08/05/2011	4.1	Minor	Clarified the meaning of the technical content.
10/07/2011	5.0	Major	Significantly changed the technical content.
01/20/2012	6.0	Major	Significantly changed the technical content.

Table of Contents

1 Introduction	7
1.1 Glossary	7
1.2 References	7
1.2.1 Normative References	8
1.2.2 Informative References	8
1.3 Overview	9
1.4 Relationship to Other Protocols	9
1.5 Prerequisites/Preconditions	10
1.6 Applicability Statement	10
1.7 Versioning and Capability Negotiation	10
1.8 Vendor-Extensible Fields	10
1.9 Standards Assignments	10
2 Messages.....	11
2.1 Transport	11
2.2 Common Message Syntax	11
2.2.1 Namespaces	11
2.2.2 Messages	11
2.2.3 Elements	11
2.2.3.1 t:BaseItemId Element	12
2.2.3.2 t:ManagementRole Element	12
2.2.4 Complex Types	12
2.2.4.1 m:BaseMoveCopyItemType Complex Type	13
2.2.4.2 m:SendItemResponseType Complex Type	14
2.2.4.3 m:SendItemType Complex Type	14
2.2.4.4 m:UpdateItemResponseMessageType Complex Type	15
2.2.4.5 t:ConflictResultsType Complex Type	16
2.2.4.6 t:ItemType Complex Type	16
2.2.4.7 t:ManagementRoleType Complex Type	22
2.2.4.8 t:MimeContentType Complex Type	23
2.2.4.9 t:NonEmptyArrayOfBaseItemIdsType Complex Type	23
2.2.4.10 t:NonEmptyArrayOfInternetHeadersType Complex Type	24
2.2.4.11 t:NonEmptyArrayOfResponseObjectsType Complex Type	24
2.2.4.12 t:NonEmptyArrayOfRoleType Complex Type	26
2.2.4.13 t:OccurrenceItemIdType Complex Type	26
2.2.4.14 t:RecurringMasterItemIdType Complex Type	27
2.2.4.15 t:ItemIdType Complex Type	28
2.2.4.16 t:ReferenceItemResponseType Complex Type	28
2.2.4.17 t:SmartResponseBaseType Complex Type	29
2.2.4.18 t:SmartResponseType Complex Type	31
2.2.5 Simple Types	31
2.2.5.1 t:DerivedItemIdType Simple Type	32
2.2.5.2 t:ImportanceChoicesType Simple Type	32
2.2.5.3 t:ItemClassType Simple Type	33
2.2.5.4 t:ReminderMinutesBeforeStartType Simple Type	33
2.2.6 Attributes	33
2.2.7 Groups	34
2.2.8 Attribute Groups	34
2.2.9 Common Data Structures	34

3 Protocol Details	35
3.1 ExchangeServicePortType Server Details	35
3.1.1 Abstract Data Model	35
3.1.2 Timers	35
3.1.3 Initialization	35
3.1.4 Message Processing Events and Sequencing Rules	35
3.1.4.1 CopyItem Operation.....	35
3.1.4.1.1 Messages	36
3.1.4.1.1.1 tns:CopyItemSoapIn Message.....	36
3.1.4.1.1.2 tns:CopyItemSoapOut Message.....	37
3.1.4.1.2 Elements.....	37
3.1.4.1.2.1 CopyItem Element	37
3.1.4.1.2.2 CopyItemResponse Element.....	38
3.1.4.1.3 Complex Types	38
3.1.4.1.3.1 m:CopyItemResponseType Complex Type	38
3.1.4.1.3.2 m:CopyItemType Complex Type.....	38
3.1.4.2 CreateItem Operation	39
3.1.4.2.1 Messages	39
3.1.4.2.1.1 tns:CreateItemSoapIn Message.....	39
3.1.4.2.1.2 tns:CreateItemSoapOut Message.....	40
3.1.4.2.2 Elements.....	41
3.1.4.2.2.1 CreateItem Element.....	41
3.1.4.2.2.2 CreateItemResponse Element	41
3.1.4.2.3 Complex Types	41
3.1.4.2.3.1 m:CreateItemResponseType Complex Type	41
3.1.4.2.3.2 m:CreateItemType Complex Type	42
3.1.4.3 DeleteItem Operation.....	43
3.1.4.3.1 Messages	43
3.1.4.3.1.1 tns:DeleteItemSoapIn Message	43
3.1.4.3.1.2 tns:DeleteItemSoapOut Message	44
3.1.4.3.2 Elements.....	45
3.1.4.3.2.1 DeleteItem Element	45
3.1.4.3.2.2 DeleteItemResponse Element.....	45
3.1.4.3.3 Complex Types	45
3.1.4.3.3.1 m:DeleteItemResponseType Complex Type	45
3.1.4.3.3.2 m:DeleteItemType Complex Type	46
3.1.4.4 GetItem Operation	47
3.1.4.4.1 Messages	47
3.1.4.4.1.1 tns:GetItemSoapIn Message	48
3.1.4.4.1.2 tns:GetItemSoapOut Message	49
3.1.4.4.2 Elements.....	49
3.1.4.4.2.1 GetItem Element	49
3.1.4.4.2.2 GetItemResponse Element	49
3.1.4.4.3 Complex Types	50
3.1.4.4.3.1 m:GetItemResponseType Complex Type	50
3.1.4.4.3.2 m:GetItemType Complex Type	50
3.1.4.5 MarkAllItemsAsRead Operation.....	51
3.1.4.5.1 Messages	51
3.1.4.5.1.1 tns:MarkAllItemsAsReadSoapIn Message	52
3.1.4.5.1.2 tns:MarkAllItemsAsReadSoapOut Message	52
3.1.4.5.2 Elements.....	53
3.1.4.5.2.1 MarkAllItemsAsRead Element	53
3.1.4.5.2.2 MarkAllItemsAsReadResponse Element	53

3.1.4.5.3 Complex Types	54
3.1.4.5.3.1 m:MarkAllItemsAsReadType Complex Type.....	54
3.1.4.5.3.2 m:MarkAllItemsAsReadResponseType Complex Type	54
3.1.4.6 MoveItem Operation	55
3.1.4.6.1 Messages	55
3.1.4.6.1.1 tns:MoveItemSoapIn Message.....	55
3.1.4.6.1.2 tns:MoveItemSoapOut Message	56
3.1.4.6.2 Elements.....	56
3.1.4.6.2.1 MoveItem Element.....	56
3.1.4.6.2.2 MoveItemResponse Element	57
3.1.4.6.3 Complex Types	57
3.1.4.6.3.1 m:MoveItemResponseType Complex Type	57
3.1.4.6.3.2 m:MoveItemType Complex Type	57
3.1.4.7 SendItem Operation.....	58
3.1.4.7.1 Messages	58
3.1.4.7.1.1 tns:SendItemSoapIn Message.....	58
3.1.4.7.1.2 tns:SendItemSoapOut Message	59
3.1.4.7.2 Elements.....	59
3.1.4.7.2.1 SendItem Element.....	60
3.1.4.7.2.2 SendItemResponse Element.....	60
3.1.4.7.3 Complex Types	60
3.1.4.7.3.1 m:SendItemResponseType Complex Type	60
3.1.4.7.3.2 m:SendItemType Complex Type.....	60
3.1.4.8 UpdateItem Operation.....	61
3.1.4.8.1 Messages	62
3.1.4.8.1.1 tns:UpdateItemSoapIn Message.....	62
3.1.4.8.1.2 tns:UpdateItemSoapOut Message.....	63
3.1.4.8.2 Elements.....	63
3.1.4.8.2.1 UpdateItem Element.....	63
3.1.4.8.2.2 UpdateItemResponse Element.....	64
3.1.4.8.3 Complex Types	64
3.1.4.8.3.1 m:UpdateItemResponseType Complex Type	64
3.1.4.8.3.2 m:UpdateItemType Complex Type	65
3.1.4.8.3.3 t:AppendToItemType Complex Type	66
3.1.4.8.3.4 t:ChangeDescriptionType Complex Type.....	68
3.1.4.8.3.5 t:DeleteItemType Complex Type	68
3.1.4.8.3.6 t:ItemChangeDescriptionType Complex Type	68
3.1.4.8.3.7 t:ItemChangeType Complex Type	69
3.1.4.8.3.8 t:NonEmptyArrayOfItemChangeDescriptionsType Complex Type	70
3.1.4.8.3.9 t:NonEmptyArrayOfItemChangesType Complex Type	70
3.1.4.8.3.10 t:SetItemType Complex Type	71
3.1.4.8.4 Simple Types.....	72
3.1.4.8.4.1 t:ConflictResolutionType Simple Type.....	72
3.1.5 Timer Events	73
3.1.6 Other Local Events	73

4 Protocol Examples.....

74

5 Security.....

75

5.1 Security Considerations for Implementers.....	75
5.2 Index of Security Parameters	75

6 Appendix A: Full WSDL

76

7 Appendix B: Full XML Schema	82
7.1 Messages Schema.....	82
7.2 Types Schema.....	85
8 Appendix C: Product Behavior	92
9 Change Tracking.....	93
10 Index	97

Preliminary

1 Introduction

The Core Items Web Service Protocol enables clients to create, update, and delete items on the server.

Sections 1.8, 2, and 3 of this specification are normative and contain RFC 2119 language. Sections 1.5 and 1.9 are also normative but cannot contain RFC 2119 language. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Hypertext Transfer Protocol (HTTP)

Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)

The following terms are defined in [\[MS-OXGLOS\]](#):

base64 encoding

blind carbon copy (Bcc) recipient

carbon copy (Cc) recipient

delivery receipt

endpoint

mailbox

meeting

MIME message

Multipurpose Internet Mail Extensions (MIME)

Outbox folder

read receipt

recipient

SOAP action

SOAP body

SOAP header

SOAP message

To recipient

Uniform Resource Locator (URL)

Web Services Description Language (WSDL)

WSDL message

WSDL port type

XML namespace

XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXWSCDATA] Microsoft Corporation, "[Common Web Service Data Types](#)".

[MS-OXWSCONT] Microsoft Corporation, "[Contacts Web Service Protocol Specification](#)".

[MS-OXWSDLIST] Microsoft Corporation, "[Distribution List Creation and Usage Web Service Protocol Specification](#)".

[MS-OXWSFOLD] Microsoft Corporation, "[Folders and Folder Permissions Web Service Protocol Specification](#)".

[MS-OXWSGTZ] Microsoft Corporation, "[Get Server Time Zone Web Service Protocol Specification](#)".

[MS-OXWSMSG] Microsoft Corporation, "[E-Mail Message Types Web Service Protocol Specification](#)".

[MS-OXWSMTGS] Microsoft Corporation, "[Calendaring Web Service Protocol Specification](#)".

[MS-OXWSPOST] Microsoft Corporation, "[Post Items Web Service Protocol Specification](#)".

[MS-OXWSTASK] Microsoft Corporation, "[Tasks Web Service Protocol Specification](#)".

[MS-OXWSXPROP] Microsoft Corporation, "[Extended Properties Structure](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

[RFC3066] Alvestrand, H., "Tags for the Identification of Language", RFC 3066, January 2001, <http://www.ietf.org/rfc/rfc3066.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmleschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmleschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXWSCORE] — v20120122
Core Items Web Service Protocol Specification

Copyright © 2012 Microsoft Corporation.

Release: Sunday, January 22, 2012

[MS-OXDSCLI] Microsoft Corporation, "[Autodiscover Publishing and Lookup Protocol Specification](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXWSADISC] Microsoft Corporation, "[Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol Specification](#)".

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

1.3 Overview

The Core Items Web Service Protocol provides clients with the ability to create items such as messages, tasks, and **meetings**, or to get the properties of an existing item. Clients can also use this protocol to update, delete, move, or copy items on the server.

1.4 Relationship to Other Protocols

A client that implements this protocol can use the Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol, as described in [\[MS-OXWSADISC\]](#), or the Autodiscover Publishing and Lookup Protocol, as described in [\[MS-OXDSCLI\]](#), to identify the target **endpoint (4)** to use for each operation.

The Core Items Web Service Protocol uses the SOAP Protocol, as described in [\[SOAP1.1\]](#), to specify the structure information exchanged between the client and server. Additionally, this protocol uses the XML Protocol, as described in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), to describe the message content sent to and from the server.

This protocol uses SOAP over **HTTP**, as described in [\[RFC2616\]](#), and SOAP over **HTTPS**, as described in [\[RFC2818\]](#), as shown in the following layering diagram.




Figure 1: This protocol in relation to other protocols

The item information that is returned by the Core Items Web Service Protocol is used when requests are made by using the following protocols:

- Contacts Web Service Protocol, as described in [\[MS-OXWSCONT\]](#)
- Distribution List Creation and Usage Web Service Protocol, as described in [\[MS-OXWSDLIST\]](#)
- E-Mail Message Types Web Service Protocol, as described in [\[MS-OXWSMSG\]](#)
- Calendaring Web Service Protocol, as described in [\[MS-OXWSMTGS\]](#)
- Post Items Web Service Protocol, as described in [\[MS-OXWSPOST\]](#)

- Tasks Web Service Protocol, as described in [\[MS-OXWSTASK\]](#)

1.5 Prerequisites/Preconditions

The endpoint(4) **URL** that is returned by either the Autodiscover Publishing Lookup SOAP-Based Web Service Protocol, as described in [\[MS-OXWSADISC\]](#), or the Autodiscover Publishing and Lookup Protocol, as described in [\[MS-OXDSCLI\]](#), is required to form the HTTP request to the Web server that hosts this protocol. The operations that this protocol defines cannot be accessed unless the correct endpoint (4) is identified in the HTTP Web requests that target this protocol.

1.6 Applicability Statement

This protocol is applicable to environments that create, delete, get, copy, move, or update items by using the server's Web services.

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Supported Transports:** This protocol uses SOAP 1.1, as specified in section [2.1](#).
- **Protocol Versions:** This protocol has only one **WSDL port type** version. The **WSDL** version of the request is identified by using the **t:RequestServerVersion** element, as described in [\[MS-OXWSCDATA\]](#) section 2.2.4.9. The version of the server responding to the request is identified by using the **t:ServerVersionInfo** element, as described in [\[MS-OXWSCDATA\]](#) section 2.2.4.10.
- **Security and Authentication Methods:** This protocol relies on the Web server that is hosting it to perform authentication.
- **Localization:** This protocol includes text strings in various messages. Localization considerations for such strings are specified in sections [2.2](#) and [3.1.4](#).
- **Capability Negotiation:** None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The WSDL in this specification provides a base description of the protocol. The schema in this specification provides a base description of the message syntax. The text that specifies the WSDL and schema might specify restrictions that reflect actual protocol behavior. For example, the schema definition might allow for an element to be **empty**, **null**, or **not present** but the behavior of the protocol as specified restricts the same elements to being **non-empty**, **not null**, or **present**.

2.1 Transport

The SOAP version supported is SOAP 1.1. For details, see [\[SOAP1.1\]](#).

This protocol relies on the Web server that hosts the application to perform authentication. The protocol SHOULD use secure communications via HTTPS, as defined in [\[RFC2818\]](#).

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and Web Services Description Language (WSDL), as defined in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** by using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
tns	http://schemas.microsoft.com/exchange/services/2006/messages	
s	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]
targetNamespace	http://schemas.microsoft.com/exchange/services/2006/messages	
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
t	http://schemas.microsoft.com/exchange/services/2006/types	

2.2.2 Messages

This specification does not define any common **WSDL message** definitions.

2.2.3 Elements

Note Some of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure. For information about specific differences between versions, see the behavior notes that are provided in the Product Behavior appendix.

The following table lists the set of common XML schema element definitions that are defined by this specification. XML schema element definitions that are specific to a particular operation are defined with the operation.

Element name	Description
BaseItemId	Specifies the base class for IDs that represent items in a mailbox .
ManagementRole	Specifies the roles the user or application wants to use.

2.2.3.1 t:BaseItemId Element

The **BaseItemId** element specifies the base class for IDs that represent items in a mailbox.

```
<xss:element name="t:BaseItemId"
  type="t:BaseItemIdType"
  abstract="true"
/>
```

2.2.3.2 t:ManagementRole Element

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **ManagementRole** element specifies the roles the user or application wants to use.[<1>](#)

```
<xss:element name="MailboxCulture" type="t:MailboxCultureType"/>
```

2.2.4 Complex Types

Note Some of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure. For information about specific differences between versions, see the behavior notes that are provided in the Product Behavior appendix.

The following table lists the set of common XML schema complex type definitions that are defined by this specification. XML schema complex type definitions that are specific to a particular operation are defined with the operation.

Complex type name	Description
BaseMoveCopyItemType	Specifies the base type for the CopyItemType complex type (section 3.1.4.1.3.2) and the MoveItemType complex type (section 3.1.4.6.3.2).
SendItemResponseType	Specifies a response to a call to the SendItem operation ([MS-OXWSMSG] section 3.1.4.7).
SendItemType	Specifies a request to send a message.
UpdateItemResponseMessageType	Specifies the status and result of a single call to the UpdateItem operation (section 3.1.4.8).
ConflictResultsType	Specifies the number of conflicts in an UpdateItem operation response.

Complex type name	Description
ItemType	Specifies a generic item in the server data store.
ManagementRoleType	Specifies the roles that are associated with a user or application.
MimeContentType	Specifies the native MIME stream of an object that is represented in base64-encoded binary format.
NonEmptyArrayOfBaseItemIdsType	Specifies a collection of items.
NonEmptyArrayOfInternetHeadersType	Specifies the collection of all Internet message headers that are contained in an item.
NonEmptyArrayOfResponseObjectsType	Specifies an array of response objects.
NonEmptyArrayOfRoleType	Specifies an array of role types.
OccurrenceItemIdType	Specifies a single occurrence of a recurring item.
RecurringMasterItemIdType	Specifies a recurrence master item by identifying the identifiers of one of its related occurrence items.
ItemIdType	Specifies the item identifier (ID) of an item.
ReferenceItemResponseType	Specifies a referenced item for a response object.
SmartResponseBaseType	Specifies the base type for ReplyToItem , ReplyAllToItem , ForwardItem , and CancelCalendarItem operation response objects.
SmartResponseType	Specifies the base type for ReplyToItem , ReplyAllToItem , ForwardItem , and CancelCalendarItem operation response objects.

2.2.4.1 m:BaseMoveCopyItemType Complex Type

The **BaseMoveCopyItemType** complex type specifies the base type for the **CopyItemType** complex type, as specified in section [3.1.4.1.3.2](#), and the **MoveItemType** complex type, as specified in section [3.1.4.6.3.2](#). The **BaseMoveCopyItemType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```

<xs:complexType name="BaseMoveCopyItemType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    >
      <xs:sequence>
        <xs:element name="ToFolderId"
          type="t:TargetFolderIdType"
        />
        <xs:element name="ItemIds"
          type="t:NonEmptyArrayOfBaseItemIdsType"
        />
        <xs:element name="ReturnNewItemIds"
          type="xs:boolean"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

```

        </xs:sequence>
    </xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists and describes the child elements of the **BaseMoveCopyItemType** complex type.

Element name	Type	Description
ToFolderId	t:TargetFolderIdType ([MS-OXWSFOLD] section 2.2.4.14)	Specifies an instance of the TargetFolderIdType complex type that specifies the folder to which the items specified by the ItemIds property are to be moved or copied.
ItemIds	t:NonEmptyArrayOfBaseItemIdsType (section 2.2.4.9)	Specifies an array of elements of type BaseItemIdType that specifies a set of items to be moved or copied.
ReturnNewItemIds	xs:boolean ([XMLSCHEMA2])	Specifies a Boolean return value that indicates whether the ItemId element is to be returned for new items. This element SHOULD <code><?></code> be included.

2.2.4.2 m:SendItemResponseType Complex Type

The **SendItemResponseType** complex type specifies a response to a call to the **SendItem** operation, as specified in section [3.1.4.7](#). The **SendItemResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.16).

```

<xs:complexType name="SendItemResponseType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseResponseMessageType"
        />
    </xs:complexContent>
</xs:complexType>

```

2.2.4.3 m:SendItemType Complex Type

The **SendItemType** complex type specifies a request to send a message. The **SendItemType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```

<xs:complexType name="SendItemType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseRequestType"
        />
        <xs:sequence>

```

```

<xs:element name="ItemIds"
    type="t:NonEmptyArrayOfBaseItemIdsType"
/>
<xs:element name="SavedItemFolderId"
    type="t:TargetFolderIdType"
    minOccurs="0"
/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists and describes the child elements of the **SendItemType** complex type.

Element name	Type	Description
ItemIds	t:NonEmptyArrayOfBaseItemIdsType (section 2.2.4.9)	Specifies an array of item identifiers for the items to try to send.
SavedItemFolderId	t:TargetFolderIdType ([MS-OXWSFOLD] section 2.2.4.14)	Specifies the identity of the folder that contains a saved version of a sent item.

2.2.4.4 m:UpdateItemResponseMessageType Complex Type

The **UpdateItemResponseMessageType** complex type specifies the status and result of a single call to the **UpdateItem** operation, as specified in section [3.1.4.8](#). The **UpdateItemResponseMessageType** complex type extends the **ItemInfoResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.37).

```

<xs:complexType name="UpdateItemResponseMessageType">
<xs:complexContent>
<xs:extension
    base="m:ItemInfoResponseMessageType"
>
<xs:sequence>
<xs:element name="ConflictResults"
    type="t:ConflictResultsType"
    minOccurs="0"
/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists and describes the child elements of the **UpdateItemResponseMessageType** complex type.

Element name	Type	Description
ConflictResults	t:ConflictResultsType (section 2.2.4.5)	Specifies the number of conflicts in the result of a single call.

2.2.4.5 t:ConflictResultsType Complex Type

The **ConflictResultsType** complex type specifies the number of conflicts in an **UpdateItem** operation response, as specified in section [3.1.4.8](#).

```
<xs:complexType name="ConflictResultsType">
  <xs:sequence>
    <xs:element name="Count"
      type="xs:int"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists and describes the child elements of the **ConflictResultsType** complex type.

Element name	Type	Description
Count	xs:int [XMLSCHEMA2]	Specifies an integer value that indicates the number of conflicts in an UpdateItem operation response.

2.2.4.6 t:ItemType Complex Type

The **ItemType** complex type specifies a generic item on the server.

```
<xs:complexType name="ItemType">
  <xs:sequence>
    <xs:element name="MimeType"
      type="t:MimeTypeType"
      minOccurs="0"
    />
    <xs:element name="ItemId"
      type="t:ItemIdType"
      minOccurs="0"
    />
    <xs:element name="ParentFolderId"
      type="t:FolderIdType"
      minOccurs="0"
    />
    <xs:element name="ItemClass"
      type="t:ItemClassType"
      minOccurs="0"
    />
    <xs:element name="Subject"
      type="xs:string"
      minOccurs="0"
    />
    <xs:element name="Sensitivity"
      type="t:SensitivityChoicesType"
      minOccurs="0"
    />
    <xs:element name="Body"
      type="t:BodyType"
      minOccurs="0"
    />
```

```
<xs:element name="Attachments"
    type="t:NonEmptyArrayOfAttachmentsType"
    minOccurs="0"
/>
<xs:element name="DateTimeReceived"
    type="xs:dateTime"
    minOccurs="0"
/>
<xs:element name="Size"
    type="xs:int"
    minOccurs="0"
/>
<xs:element name="Categories"
    type="t:ArrayOfStringsType"
    minOccurs="0"
/>
<xs:element name="Importance"
    type="t:ImportanceChoicesType"
    minOccurs="0"
/>
<xs:element name="InReplyTo"
    type="xs:string"
    minOccurs="0"
/>
<xs:element name="IsSubmitted"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="IsDraft"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="IsFromMe"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="IsResend"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="IsUnmodified"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="InternetMessageHeaders"
    type="t:NonEmptyArrayOfInternetHeadersType"
    minOccurs="0"
/>
<xs:element name="DateTimeSent"
    type="xs:dateTime"
    minOccurs="0"
/>
<xs:element name="DateTimeCreated"
    type="xs:dateTime"
    minOccurs="0"
/>
<xs:element name="ResponseObjects"
    type="t:NonEmptyArrayOfResponseObjectsType"
    minOccurs="0"
/>
```

```
    />
<xs:element name="ReminderDueBy"
    type="xs:dateTime"
    minOccurs="0"
/>
<xs:element name="ReminderIsSet"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="ReminderMinutesBeforeStart"
    type="t:ReminderMinutesBeforeStartType"
    minOccurs="0"
/>
<xs:element name="DisplayCc"
    type="xs:string"
    minOccurs="0"
/>
<xs:element name="DisplayTo"
    type="xs:string"
    minOccurs="0"
/>
<xs:element name="HasAttachments"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="ExtendedProperty"
    type="t:ExtendedPropertyType"
    minOccurs="0"
    maxOccurs="unbounded"
/>
<xs:element name="Culture"
    type="xs:language"
    minOccurs="0"
/>
<xs:element name="EffectiveRights"
    type="t:EffectiveRightsType"
    minOccurs="0"
/>
<xs:element name="LastModifiedName"
    type="xs:string"
    minOccurs="0"
/>
<xs:element name="LastModifiedTime"
    type="xs:dateTime"
    minOccurs="0"
/>
<xs:element name="IsAssociated"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="WebClientReadFormQueryString"
    type="xs:string"
    minOccurs="0"
/>
<xs:element name="WebClientEditFormQueryString"
    type="xs:string"
    minOccurs="0"
/>
<xs:element name="ConversationId"
```

```

        type="t:ItemIdType"
        minOccurs="0"
    />
<xs:element name="UniqueBody"
    type="t:BodyType"
    minOccurs="0"
/>
<xs:element name="StoreEntryId"
    type="xs:base64Binary"
    minOccurs="0"
/>
</xs:sequence>
</xs:complexType>

```

The following table lists and describes the child elements of the **ItemType** complex type.

Element name	Type	Description
MimeContent	t:MimeContentType (section 2.2.4.8)	Specifies an instance of the MimeContentType class that contains the native MIME stream of an object that is represented in base64Binary format.
ItemId	t:ItemIdType (section 2.2.4.15)	Specifies an instance of the ItemIdType class that represents the unique identifier and change key of an item in the server data store.
ParentFolderId	t:FolderIdType ([MS-OXWSCDATA] section 2.2.3.31)	Specifies an instance of the FolderIdType class that represents the identifier of the parent folder that contains an item or folder.
ItemClass	t:ItemClassType (section 2.2.5.3)	Specifies a string value that indicates the message class of an item.
Subject	xs:string ([XMLSCHEMA2])	Specifies a string value that represents the subject property of items. This value is limited to 255 characters.
Sensitivity	t:SensitivityChoicesType ([MS-OXWSCDATA] section 2.2.2.22)	Specifies one of the valid SensitivityChoicesType simple type enumeration values that indicates the sensitivity level of an item.
Body	t:BodyType ([MS-OXWSCDATA] section 2.2.3.17)	Specifies the body content of an item.
Attachments	t:NonEmptyArrayOfAttachmentsType ([MS-OXWSCDATA] section 2.2.3.43)	Specifies an AttachmentType array that

Element name	Type	Description
		contains the items or files that are attached to an item.
DateTimeReceived	xs:dateTime [XMLSCHEMA2]	Specifies the date and time that an item was received in a mailbox.
Size	xs:int [XMLSCHEMA2]	Specifies an integer value that represents the size of an item, in bytes.
Categories	t:ArrayOfStringsType ([MS-OXWSCDATA] section 2.2.3.11)	Specifies a string array that identifies the categories to which an item in a mailbox belongs.
Importance	t:ImportanceChoicesType (section 2.2.5.2)	Specifies one of the valid ImportanceChoicesType values to indicate the importance of an item.
InReplyTo	xs:string	Specifies a string value that contains the identifier of the item to which this item is a reply.
IsSubmitted	xs:boolean [XMLSCHEMA2]	Specifies a Boolean value that indicates whether an item has been submitted to the Outbox folder .
IsDraft	xs:boolean	Specifies a Boolean value that indicates whether an item has been sent.
IsFromMe	xs:boolean	Specifies a Boolean value that indicates whether a user sent an item to himself or herself.
IsResend	xs:boolean	Specifies a Boolean value that indicates whether an item has previously been sent.
IsUnmodified	xs:boolean	Specifies a Boolean value that indicates whether an item has been modified.
InternetMessageHeaders	t:NonEmptyArrayOfInternetHeadersType (section 2.2.4.10)	Specifies an array of the type InternetHeaderType that represents the collection of all Internet message headers that are contained in an item in a mailbox.
DateTimeSent	xs:dateTime	Specifies the date and time when an item in a mailbox was sent.

Element name	Type	Description
DateTimeCreated	xs:dateTime	Specifies the date and time when an item in a mailbox was created.
ResponseObjects	t:NonEmptyArrayOfResponseObjects Type (section 2.2.4.11)	Specifies an array of type ResponseObjectType that contains a collection of all the response objects that are associated with an item.
ReminderDueBy	xs:dateTime	Specifies an instance of the DateTime structure that represents the date and time when an event is to occur. This is used by the ReminderMinutesBeforeStart element to determine when the reminder is displayed.
ReminderIsSet	xs:boolean	Specifies a Boolean value that indicates whether a reminder has been set for an item.
ReminderMinutesBeforeStart	t:ReminderMinutesBeforeStartType (section 2.2.5.4)	Specifies a string value that indicates the number of minutes before an event occurs when a reminder is displayed.
DisplayCc	xs:string	Specifies the display string that is used for the contents of the Cc box. This is the concatenated string of all Cc recipient display names.
DisplayTo	xs:string	Specifies the display string that is used for the contents of the To box. This is the concatenated string of all To recipient display names.
HasAttachments	xs:boolean	Specifies a Boolean value that indicates whether an item has at least one attachment.
ExtendedProperty	t:ExtendedPropertyType ([MS-OXWSXPROP] section 2.1.5)	Specifies an array of ExtendedPropertyType elements that identify extended MAPI properties.
Culture	xs:language [XMLSCHEMA2]	Specifies the culture for an item in a mailbox.
EffectiveRights	t:EffectiveRightsType ([MS-OXWSCDATA] section 2.2.3.25)	Specifies an EffectiveRightsType element that represents the

Element name	Type	Description
		client's rights based on the permission settings for an item or folder.
LastModifiedName	xs:string	Specifies a string value that contains the name of the user who last modified an item.
LastModifiedTime	xs:dateTime	Specifies an instance of the DateTime structure that represents the date and time when an item was last modified.
IsAssociated	xs:boolean	Specifies a value that indicates whether this is an associated item.
WebClientReadFormQueryString	xs:string	Specifies the query string that should be appended to the Web client URL to open an item by using the appropriate read form in a Web browser.
WebClientEditFormQueryString	xs:string	Specifies the query string that should be appended to the Web client URL to open an item by using the appropriate edit form in a Web browser.
ConversationId	t:ItemIdType	Specifies the ID of the conversation that an item is part of.
UniqueBody	t:BodyType ([MS-OXWSCDATA] section 2.2.3.17)	Specifies the body part that is unique to the conversation that an item is part of.
StoreEntryId	xs:base64Binary ([XMLSCHEMA2])	Specifies the entry ID of the store that hosts an item. This element SHOULD <code><3></code> be included.

2.2.4.7 t:ManagementRoleType Complex Type

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **ManagementRoleType** complex type specifies the roles that are associated with a user or application.[`<4>`](#)

```
<xs:complexType name="ManagementRoleType">
  <xs:sequence>
    <xs:element name="UserRoles" type="t:NonEmptyArrayOfRoleType" minOccurs="0"
maxOccurs="1"/>
```

```

<xs:element name="ApplicationRoles" type="t:NonEmptyArrayOfRoleType" minOccurs="0"
maxOccurs="1"/>
</xs:sequence>
</xs:complexType>

```

The following table lists and describes the elements of the **ManagementRoleType** complex type.

Element name	Type	Description
UserRoles	t:NonEmptyArrayOfRoleType (section 2.2.4.12)	Specifies an array of elements of type string that specifies a set of user roles.
ApplicationRoles	t:NonEmptyArrayOfRoleType (section 2.2.4.12)	Specifies an array of elements of type string that specifies a set of application roles.

2.2.4.8 t:MimeContentType Complex Type

The **MimeContentType** complex type specifies the native MIME stream of an object that is represented in **base64 encoding**.

```

<xs:complexType name="MimeContentType">
  <xs:simpleContent>
    <xs:extension
      base="xs:string"
    >
      <xs:attribute name="CharacterSet"
        type="xs:string"
        use="optional"
      />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

```

The following table lists and describes the attributes of the **MimeContentType** complex type.

Attribute name	Type	Description
CharacterSet	xs:string [XMLSCHEMA2]	Specifies the International Standards Organization (ISO) name of the character set that is used in a MIME message .

2.2.4.9 t:NonEmptyArrayOfBaseItemIdsType Complex Type

The **NonEmptyArrayOfBaseItemIdsType** complex type specifies a collection of items.

```

<xs:complexType name="NonEmptyArrayOfBaseItemIdsType">
  <xs:choice
    minOccurs="1"
    maxOccurs="unbounded"
  >
    <xs:element name="ItemId"
      type="t:ItemIdType"
    />

```

```

<xs:element name="OccurrenceItemId"
    type="t:OccurrenceItemIdType"
/>
<xs:element name="RecurringMasterItemId"
    type="t:RecurringMasterItemIdType"
/>
</xs:choice>
</xs:complexType>

```

The following table lists and describes the child elements of the **NonEmptyArrayOfBaseItemIdsType** complex type.

Element name	Type	Description
ItemId	t:ItemIdType (section 2.2.4.15)	Specifies the item identifier.
OccurrenceItemId	t:OccurrenceItemIdType (section 2.2.4.13)	Specifies a single occurrence of a recurring item.
RecurringMasterItemId	t:RecurringMasterItemIdType (section 2.2.4.14)	Specifies a recurrence master item by indicating the identifier of one of the master item's related occurrence items.

2.2.4.10 t:NonEmptyArrayOfInternetHeadersType Complex Type

The **NonEmptyArrayOfInternetHeadersType** complex type specifies the collection of all Internet message headers that are contained in an item.

```

<xs:complexType name="NonEmptyArrayOfInternetHeadersType">
    <xs:sequence>
        <xs:element name="InternetMessageHeader"
            type="t:InternetHeaderType"
            maxOccurs="unbounded"
        />
    </xs:sequence>
</xs:complexType>

```

The following table lists and describes the child elements of the **NonEmptyArrayOfInternetHeadersType** complex type.

Element name	Type	Description
InternetMessageHeader	t:InternetHeaderType (MS-OXWSCDATA section 2.2.3.35)	Specifies a single Internet message header.

2.2.4.11 t:NonEmptyArrayOfResponseObjectsType Complex Type

The **NonEmptyArrayOfResponseObjectsType** complex type specifies an array of response objects.

```
<xs:complexType name="NonEmptyArrayOfResponseObjectsType">
```

```

<xs:choice
  maxOccurs="unbounded"
  minOccurs="0"
>
  <xs:element name="AcceptItem"
    type="t:AcceptItemType"
  />
  <xs:element name="TentativelyAcceptItem"
    type="t:TentativelyAcceptItemType"
  />
  <xs:element name="DeclineItem"
    type="t:DeclineItemType"
  />
  <xs:element name="ReplyToItem"
    type="t:ReplyToItemType"
  />
  <xs:element name="ForwardItem"
    type="t:ForwardItemType"
  />
  <xs:element name="ReplyAllToItem"
    type="t:ReplyAllToItemType"
  />
  <xs:element name="CancelCalendarItem"
    type="t:CancelCalendarItemType"
  />
  <xs:element name="RemoveItem"
    type="t:RemoveItemType"
  />
  <xs:element name="SuppressReadReceipt"
    type="t:SuppressReadReceiptType"
  />
  <xs:element name="PostReplyItem"
    type="t:PostReplyItemType"
  />
  <xs:element name="AcceptSharingInvitation"
    type="t:AcceptSharingInvitationType"
  />
</xs:choice>
</xs:complexType>

```

The following table lists and describes the child elements of the **NonEmptyArrayOfResponseObjectsType** complex type.

Element name	Type	Description
AcceptItem	t:AcceptItemType ([MS-OXWSMTGS] section 2.2.4.1)	Specifies an Accept reply to a meeting request.
TentativelyAcceptItem	t:TentativelyAcceptItemType ([MS-OXWSMTGS] section 2.2.4.20)	Specifies a Tentative reply to a meeting request.
DeclineItem	t:DeclineItemType ([MS-OXWSMTGS] section 2.2.4.9)	Specifies a Decline reply to a meeting request.
ReplyToItem	t:ReplyToItemType ([MS-OXWSCDATA] section 2.2.3.56)	Specifies a reply to the sender of an item.

Element name	Type	Description
ForwardItem	t:ForwardItemType ([MS-OXWSCDATA] section 2.2.3.33)	Specifies a server store item to be forwarded to recipients .
ReplyAllToItem	t:ReplyAllToItemType ([MS-OXWSCDATA] section 2.2.3.54)	Specifies a reply to the sender and all identified recipients of an item in the server store.
CancelCalendarItem	t:CancelCalendarItemType ([MS-OXWSMTGS] section 2.2.4.8)	Specifies the response object that is used to cancel a meeting.
RemoveItem	t:RemoveItemType ([MS-OXWSMTGS] section 2.2.4.19)	Specifies a response object that is used to remove a meeting item when a MeetingCancellation message is received.
SkipReadReceipt	t:SkipReadReceiptType ([MS-OXWSCDATA] section 2.2.3.61)	Specifies that read receipts are to be suppressed.
PostReplyItem	t:PostReplyItemType ([MS-OXWSPOST] section 2.2.4.3)	Specifies a reply to a post item.
AcceptSharingInvitation	t:AcceptSharingInvitationType ([MS-OXWSCDATA] section 2.2.3.3)	Specifies that sharing invitations are to be accepted.

2.2.4.12 t:NonEmptyArrayOfRoleType Complex Type

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **NonEmptyArrayOfRoleType** complex type specifies an array of role types.[<5>](#)

```
<xsd:complexType name="NonEmptyArrayOfRoleType">
  <xsd:sequence>
    <xsd:element name="Role" type="xsd:string" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

The following table lists and describes the child elements of the **NonEmptyArrayOfRoleType** complex type.

Element name	Type	Description
Role	xsd:string ([XMLSCHEMA2])	Specifies the name of a role.

2.2.4.13 t:OccurrenceItemIdType Complex Type

The **OccurrenceItemIdType** complex type specifies a single occurrence of a recurring item. The **OccurrenceItemIdType** complex type extends the **BaseItemIdType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.13).

```
<xsd:complexType name="OccurrenceItemIdType">
```

```

<xs:complexContent>
  <xs:extension
    base="t:BaseItemIdType"
  >
    <xs:attribute name="RecurringMasterId"
      type="t:DerivedItemIdType"
      use="required"
    />
    <xs:attribute name="ChangeKey"
      type="xs:string"
      use="optional"
    />
    <xs:attribute name="InstanceIndex"
      type="xs:int"
      use="required"
    />
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists and describes the attributes of the **OccurrenceItemIdType** complex type.

Attribute name	Type	Description
RecurringMasterId	t:DerivedItemIdType (section 2.2.5.1)	Specifies the identifier of the recurring master of a recurring item.
ChangeKey	xs:string [XMLSCHEMA2]	Specifies a specific version of a single occurrence of a recurring master item.
InstanceIndex	xs:int [XMLSCHEMA2]	Specifies the index of an item occurrence.

2.2.4.14 t:RecurringMasterItemIdType Complex Type

The **RecurringMasterItemIdType** complex type specifies a recurrence master item by indicating the identifiers of one of the master item's related occurrence items. The **RecurringMasterItemIdType** complex type extends the **BaseItemIdType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.13).

```

<xs:complexType name="RecurringMasterItemIdType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseItemIdType"
    >
      <xs:attribute name="OccurrenceId"
        type="t:DerivedItemIdType"
        use="required"
      />
      <xs:attribute name="ChangeKey"
        type="xs:string"
        use="optional"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

The following table lists and describes the attributes of the **RecurringMasterItemIdType** complex type.

Attribute name	Type	Description
OccurrenceId	t:DerivedItemIdType (section 2.2.5.1)	Specifies a single occurrence of a recurring master item.
ChangeKey	xs:string [XMLSCHEMA2]	Specifies a specific version of a single occurrence of a recurring master item.

2.2.4.15 t:ItemIdType Complex Type

The **ItemIdType** complex type specifies an item identifier of an item. The **ItemIdType** complex type extends the **BaseItemIdType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.13).

```
<xs:complexType name="ItemIdType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseItemIdType"
    >
      <xs:attribute name="Id"
        type="xs:string"
        use="required"
      />
      <xs:attribute name="ChangeKey"
        type="xs:string"
        use="optional"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists and describes the attributes of the **ItemIdType** complex type.

Attribute name	Type	Description
Id	xs:string [XMLSCHEMA2]	Specifies an item identifier. The maximum size of this attribute is 512 bytes after base64 encoding.
ChangeKey	xs:string	Specifies a change key. The maximum size of this attribute is 512 bytes after base64 encoding.

2.2.4.16 t:ReferenceItemResponseType Complex Type

The **ReferenceItemResponseType** complex type specifies a referenced item for a response object. The **ReferenceItemResponseType** complex type extends the **ResponseObjectType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.59).

```
<xs:complexType name="ReferenceItemResponseType">
  <xs:complexContent>
    <xs:restriction
      base="t:ResponseObjectType"
```

```

>
<xs:sequence>
  <xs:element name="ReferenceItemId"
    type="t:ItemIdType"
    minOccurs="0"
  />
</xs:sequence>
<xs:attribute name="ObjectName"
  type="xs:string"
  use="prohibited"
/>
</xs:restriction>
</xs:complexContent>
</xs:complexType>

```

The following table lists and describes the child elements of the **ReferenceItemResponseType** complex type.

Element name	Type	Description
ReferenceItemId	t:ItemIdType (section 2.2.4.15)	Specifies the referenced item identifier.
ObjectName	xs:string [XMLSCHEMA2]	Specifies the name of the reply object class as a string.

2.2.4.17 t:SmartResponseBaseType Complex Type

The **SmartResponseBaseType** complex type specifies the base type for the **ReplyToItemType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.56), the **ReplyAllToItemType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.54), the **ForwardItemType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.33), and the **CancelCalendarItemType** complex type, as specified in [\[MS-OXWSMTGS\]](#) section 2.2.4.8. The **SmartResponseBaseType** complex type extends the **responseObject** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.59).

```

<xs:complexType name="SmartResponseBaseType">
  <xs:complexContent>
    <xs:restriction
      base="t:responseObject"
    >
      <xs:sequence>
        <xs:element name="Subject"
          type="xs:string"
          minOccurs="0"
        />
        <xs:element name="Body"
          type="t:BodyType"
          minOccurs="0"
        />
        <xs:element name="ToRecipients"
          type="t:ArrayOfRecipientsType"
          minOccurs="0"
        />
        <xs:element name="CcRecipients"
          type="t:ArrayOfRecipientsType"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:restriction>
  </xs:complexContent>
</xs:complexType>

```

```

    />
<xs:element name="BccRecipients"
    type="t:ArrayOfRecipientsType"
    minOccurs="0"
/>
<xs:element name="IsReadReceiptRequested"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="IsDeliveryReceiptRequested"
    type="xs:boolean"
    minOccurs="0"
/>
<xs:element name="From"
    type="t:SingleRecipientType"
    minOccurs="0"
/>
<xs:element name="ReferenceItemId"
    type="t:ItemIdType"
    minOccurs="0"
/>
</xs:sequence>
<xs:attribute name="ObjectName"
    type="xs:string"
    use="prohibited"
/>
</xs:restriction>
</xs:complexContent>
</xs:complexType>

```

The following table lists and describes the child elements of the **SmartResponseBaseType** complex type.

Element name	Type	Description
Subject	xs:string [XMLSCHEMA2]	Specifies the subject.
Body	t:BodyType ([MS-OXWSCDATA] section 2.2.3.17)	Specifies the body content of an item.
ToRecipients	t:ArrayOfRecipientsType ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a collection of recipients of an e-mail message. This property is required for sending a message.
CcRecipients	t:ArrayOfRecipientsType	Specifies a collection of carbon copy (Cc) recipients of an e-mail message.
BccRecipients	t:ArrayOfRecipientsType	Specifies a collection of blind carbon copy (Bcc) recipients of an e-mail message.
IsReadReceiptRequested	xs:boolean [XMLSCHEMA2]	Specifies whether a read receipt is requested.
IsDeliveryReceiptRequested	xs:boolean	Specifies whether a delivery receipt is requested.

Element name	Type	Description
From	t:SingleRecipientType ([MS-OXWSCDATA] section 2.2.3.60)	Specifies the addressee from whom a message was sent.
ReferenceItemId	t:ItemIdType (section 2.2.4.15)	Specifies the item identifier that is related to a response object.

The following table lists and describes the attributes of the **SmartResponseBaseType** complex type.

Attribute name	Type	Description
ObjectName	xs:string ([XMLSCHEMA2])	Specifies the name of the reply object class as an English-language string.

2.2.4.18 t:SmartResponseType Complex Type

The **SmartResponseType** complex type specifies the base type for the **ReplyToItemType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.56), the **ReplyAllToItemType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.54), the **ForwardItemType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.33), and the **CancelCalendarItemType** complex type, as specified in [\[MS-OXWSMTGS\]](#) section 2.2.4.8. The **SmartResponseType** complex type extends the **SmartResponseBaseType** complex type, as specified in section [2.2.4.17](#).

```
<xs:complexType name="SmartResponseType">
  <xs:complexContent>
    <xs:extension
      base="t:SmartResponseBaseType"
    >
      <xs:sequence>
        <xs:element name="NewBodyContent"
          type="t:BodyType"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists and describes the child elements of the **SmartResponseType** complex type.

Element name	Type	Description
NewBodyContent	t:BodyType ([MS-OXWSCDATA] section 2.2.3.17)	Specifies the new body content of a message response object.

2.2.5 Simple Types

The following table lists the set of common XML schema simple type definitions that are defined by this specification. XML schema simple type definitions that are specific to a particular operation are defined with the operation.

Simple type name	Description
DerivedItemIdType	Specifies the identifier of the recurring master of a recurring item.
ImportanceChoicesType	Specifies the levels of importance for an item.
ItemClassType	Specifies an item class.
ReminderMinutesBeforeStartType	Specifies the number of minutes before an event occurs when a reminder is displayed.

2.2.5.1 t:DerivedItemIdType Simple Type

The **DerivedItemIdType** simple type specifies the identifier of the recurring master of a recurring item.

```
<xs:simpleType name="DerivedItemIdType">
  <xs:restriction
    base="xs:string"
  />
</xs:simpleType>
```

2.2.5.2 t:ImportanceChoicesType Simple Type

The **ImportanceChoicesType** simple type specifies the levels of importance for an item.

```
<xs:simpleType name="ImportanceChoicesType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="High"
    />
    <xs:enumeration
      value="Low"
    />
    <xs:enumeration
      value="Normal"
    />
  </xs:restriction>
</xs:simpleType>
```

The following table lists the values that are defined by the **ImportanceChoicesType** simple type.

Value	Meaning
High	Specifies high importance.
Low	Specifies low importance.
Normal	Specifies normal importance.

2.2.5.3 t:ItemClassType Simple Type

The **ItemClassType** simple type specifies an item class.

```
<xs:simpleType name="ItemClassType">
  <xs:restriction
    base="xs:string"
  />
</xs:simpleType>
```

2.2.5.4 t:ReminderMinutesBeforeStartType Simple Type

The **ReminderMinutesBeforeStartType** simple type specifies the number of minutes before an event occurs when a reminder is displayed.

```
<xs:simpleType name="ReminderMinutesBeforeStartType">
  <xs:union>
    <xs:simpleType
      id="ReminderMinutesBeforeStartType"
    >
      <xs:restriction
        base="xs:int"
      >
        <xs:minInclusive
          value="0"
        />
        <xs:maxInclusive
          value="2629800"
        />
      </xs:restriction>
    </xs:simpleType>
    <xs:simpleType
      id="ReminderMinutesBeforeStartMarkerType"
    >
      <xs:restriction
        base="xs:int"
      >
        <xs:minInclusive
          value="1525252321"
        />
        <xs:maxInclusive
          value="1525252321"
        />
      </xs:restriction>
    </xs:simpleType>
  </xs:union>
</xs:simpleType>
```

2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

2.2.9 Common Data Structures

This specification does not define any common XML schema data structures.

3 Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results that are returned by the transport are passed directly back to the higher-layer protocol or application.

3.1 ExchangeServicePortType Server Details

The Core Items Web Service Protocol defines a single port type with six operations. Those operations enable client implementations to update, delete, move, or copy items on the server.

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

Note Some of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure. For information about specific differences between versions, see the behavior notes that are provided in the Product Behavior appendix.

The following table summarizes the WSDL operations as defined by this specification.

Operation name	Description
GetItem	Gets items on the server.
CreateItem	Creates items on the server.
DeleteItem	Deletes items on the server.
UpdateItem	Updates items on the server.
MoveItem	Moves items on the server.
CopyItem	Copies items on the server.
MarkAllItemsAsRead	Marks all the items in a folder as read.

3.1.4.1 CopyItem Operation

The CopyItem operation copies items on the server.

The following is the WSDL port type specification for the **CopyItem** operation.

```
<wsdl:operation name="CopyItem" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
```

```

<wsdl:input message="tns:CopyItemSoapIn" />
<wsdl:output message="tns:CopyItemSoapOut" />
</wsdl:operation>

```

The following is the WSDL binding specification for the **CopyItem** operation.

```

<wsdl:operation name="CopyItem">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/CopyItem"/>
  <wsdl:input>
    <soap:header message="tns:CopyItemSoapIn" part="Impersonation" use="literal"/>
    <soap:header message="tns:CopyItemSoapIn" part="MailboxCulture" use="literal"/>
    <soap:header message="tns:CopyItemSoapIn" part="RequestVersion" use="literal"/>
    <soap:body parts="request" use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="CopyItemResult" use="literal"/>
    <soap:header message="tns:CopyItemSoapOut" part="ServerVersion" use="literal"/>
  </wsdl:output>
</wsdl:operation>

```

3.1.4.1.1 Messages

The following table lists the WSDL message definitions that are specific to the **CopyItem** operation.

Message name	Description
CopyItemSoapIn	Specifies the SOAP message that requests to copy an item in a mailbox.
CopyItemSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.1.1.1 tns:CopyItemSoapIn Message

The **CopyItemSoapIn** WSDL message specifies the **CopyItem** operation request to copy an item on the server.

```

<wsdl:message name="CopyItemSoapIn">
  <wsdl:part name="request" element="tns:CopyItem"/>
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>--

```

The **CopyItemSoapIn** WSDL message is the input message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/CopyItem>.

The parts of the **CopyItemSoapIn** WSDL message are listed and described in the following table.

Part name	Element/type	Description
request	tns:CopyItem (section 3.1.4.1.2.1)	Specifies the SOAP body of a request.
Impersonation	t:ExchangeImpersonation (IMS-	Specifies a SOAP header that identifies the user whom the client application is

Part name	Element/type	Description
	[MS-OXWSCDATA] section 2.2.4.3)	impersonating.
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.4.6)	Specifies a SOAP header that identifies the culture to be used for accessing the mailbox. The cultures are defined in [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the schema version for a CopyItem operation request.

3.1.4.1.1.2 tns:CopyItemSoapOut Message

The **CopyItemSoapOut** WSDL message specifies the server response to the **CopyItem** operation request to copy an item on the server.

```
<wsdl:message name="CopyItemSoapOut">
    <wsdl:part name="CopyItemResult" element="tns:CopyItemResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **CopyItemSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/CopyItem>.

The parts of the **CopyItemSoapOut** WSDL message are listed and described in the following table.

Part name	Element/type	Description
CopyItemResult	tns:CopyItemResponse (section 3.1.4.1.2.2)	Specifies the SOAP body of a response message.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.10)	Specifies a SOAP header that identifies the server version for a response.

3.1.4.1.2 Elements

The following table lists the XML schema element definitions that are specific to the CopyItem operation.

Element name	Description
CopyItem	Specifies a request to copy an item in a mailbox.
CopyItemResponse	Specifies a response to a CopyItem operation request.

3.1.4.1.2.1 CopyItem Element

The **CopyItem** element specifies a request to copy an item in a mailbox.

```
<xss:element name="CopyItem"
    type="m:CopyItemType"
/>
```

3.1.4.1.2.2 CopyItemResponse Element

The **CopyItemResponse** element specifies a response to a **CopyItem** operation request.

```
<xs:element name="CopyItemResponse"
    type="m:CopyItemResponseType"
/>
```

3.1.4.1.3 Complex Types

The following table lists the XML schema complex type definitions that are specific to the CopyItem operation.

Complex type name	Description
CopyItemResponseType	Specifies the response that is returned by the CopyItem operation.
CopyItemType	Specifies an operation to copy items in a mailbox.

3.1.4.1.3.1 m:CopyItemResponseType Complex Type

The **CopyItemResponseType** complex type specifies the response that is returned by the **CopyItem** operation. The **CopyItemResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.16).

```
<xs:complexType name="CopyItemResponseType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseResponseMessageType"
        />
    </xs:complexContent>
</xs:complexType>
```

3.1.4.1.3.2 m:CopyItemType Complex Type

The **CopyItemType** complex type specifies an operation to copy items in a mailbox. The **CopyItemType** complex type extends the **BaseMoveCopyItemType** complex type, as specified in section [2.2.4.1](#).

```
<xs:complexType name="CopyItemType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseMoveCopyItemType"
        />
    </xs:complexContent>
</xs:complexType>
```

3.1.4.2 CreateItem Operation

The **CreateItem** operation creates items on the server.

The following is the WSDL port type specification for the **CreateItem** operation.

```
<wsdl:operation name="CreateItem" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:input message="tns:CreateItemSoapIn" />
    <wsdl:output message="tns:CreateItemSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification for the **CreateItem** operation.

```
<wsdl:operation name="CreateItem">
    <soap:operation
        soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/CreateItem"/>
    <wsdl:input>
        <soap:header message="tns:CreateItemSoapIn" part="Impersonation" use="literal"/>
        <soap:header message="tns:CreateItemSoapIn" part="MailboxCulture" use="literal"/>
        <soap:header message="tns:CreateItemSoapIn" part="RequestVersion" use="literal"/>
        <soap:header message="tns:CreateItemSoapIn" part="TimeZoneContext" use="literal"/>
        <soap:body parts="request" use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body parts="CreateItemResult" use="literal"/>
        <soap:header message="tns:CreateItemSoapOut" part="ServerVersion" use="literal"/>
    </wsdl:output>
</wsdl:operation>
```

3.1.4.2.1 Messages

The following table lists the WSDL message definitions that are specific to the **CreateItem** operation.

Message name	Description
CreateItemSoapIn	Specifies the SOAP message that requests to create an item.
CreateItemSoapOut	Specifies the SOAP message that is returned by the server in response to a CreateItemSoapIn operation request.

3.1.4.2.1.1 tns:CreateItemSoapIn Message

The **CreateItemSoapIn** WSDL message specifies the **CreateItem** operation request to create items on the server.

```
<wsdl:message name="CreateItemSoapIn">
    <wsdl:part name="request" element="tns:CreateItem"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>
```

The **CreateItemSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/CreateItem>.

The parts of the **CreateItemSoapIn** WSDL message are listed and described in the following table.

Part name	Element/type	Description
request	tns:CreateItem (section 3.1.4.2.3.2)	Specifies the SOAP body of a request.
Impersonation	t:ExchangeImpersonation ([MS-OXWSCDATA] section 2.2.4.3)	Specifies a SOAP header that identifies the user whom the client application is impersonating.
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.4.6)	Specifies a SOAP header that identifies the culture to be used for accessing a mailbox. The cultures are defined in [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the schema version for a CreateItem operation (section 3.1.4.2) request.
TimeZoneContext	t:TimeZoneContext ([MS-OXWSGTZ] section 2.2.4.11)	Specifies a SOAP header that identifies the time zone to be used for all responses from the server. All times that are returned from the server will be converted to the specified time zone.

3.1.4.2.1.2 tns:CreateItemSoapOut Message

The **CreateItemSoapOut** WSDL message specifies the server response to a **CreateItem** operation request to create items on the server.

```
<wsdl:message name="CreateItemSoapOut">
  <wsdl:part name="CreateItemResult" element="tns:CreateItemResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **CreateItemSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/CreateItem>.

The parts of the **CreateItemSoapOut** WSDL message are listed and described in the following table.

Part name	Element/type	Description
CreateItemResult	tns:CreateItemResponse (section 3.1.4.2.2.2)	Specifies the SOAP body of a response message.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.10)	Specifies a SOAP header that identifies the server version for the response to a CreateItem operation request.

3.1.4.2.2 Elements

The following table lists the XML schema element definitions that are specific to the **CreateItem** operation.

Element name	Description
CreateItem	Specifies a request to create an item.
CreateItemResponse	Specifies a response to a CreateItem operation request.

3.1.4.2.2.1 CreateItem Element

The **CreateItem** element specifies a request to create an item.

```
<xs:element name="CreateItem"
    type="m:CreateItemType"
/>
```

3.1.4.2.2.2 CreateItemResponse Element

The **CreateItemResponse** element specifies a response to a **CreateItem** operation request.

```
<xs:element name="CreateItemResponse"
    type="m:CreateItemResponseType"
/>
```

3.1.4.2.3 Complex Types

The following table lists the XML schema complex type definitions that are specific to the **CreateItem** operation.

Complex type name	Description
CreateItemResponseType	Specifies a response to a CreateItem operation request.
CreateItemType	Specifies a request to create an item or response object.

3.1.4.2.3.1 m:CreateItemResponseType Complex Type

The **CreateItemResponseType** complex type specifies a response to a **CreateItem** operation request. The **CreateItemResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.16).

```
<xs:complexType name="CreateItemResponseType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseResponseMessageType"
        />
    </xs:complexContent>
</xs:complexType>
```

3.1.4.2.3.2 m:CreateItemType Complex Type

The **CreateItemType** complex type specifies a request to create an item or response object. The **CreateItemTYpe** complex type extends the **BaseRequestType** complex type ([MS-OXWSCDATA] section 2.2.3.15).

```
<xs:complexType name="CreateItemType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    >
      <xs:sequence>
        <xs:element name="SavedItemId"
          type="t:TargetFolderIdType"
          minOccurs="0"
        />
        <xs:element name="Items"
          type="t:NonEmptyArrayOfAllItemsType"
        />
      </xs:sequence>
      <xs:attribute name="MessageDisposition"
        type="t:MessageDispositionType"
        use="optional"
      />
      <xs:attribute name="SendMeetingInvitations"
        type="t:CalendarItemCreateOrDeleteOperationType"
        use="optional"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists and describes the child elements of the **CreateItemType** complex type.

Element name	Type	Description
SavedItemId	t:TargetFolderIdType ([MS-OXWSFOLD] section 2.2.4.14)	Specifies the folder in which new items are saved.
Items	t:NonEmptyArrayOfAllItemsType ([MS-OXWSCDATA] section 2.2.3.42)	Specifies the collection of items to be created.

The following table lists and describes the attributes of the **CreateItemType** complex type.

Attribute name	Type	Description
MessageDisposition	t:MessageDispositionType ([MS-OXWSMSG] section 2.2.5.1)	Specifies an enumeration that describes how an item is handled after it is created.

Attribute name	Type	Description
SendMeetingInvitations	t:CalendarItemCreateOrDeleteOperationType ([MS-OXWSMTGS] section 2.2.5.1)	Specifies an enumeration that describes how meeting requests are handled after they are created.

3.1.4.3 DeleteItem Operation

The **DeleteItem** operation deletes items on the server.

The following is the WSDL port type specification for the **DeleteItem** operation.

```
<wsdl:operation name="DeleteItem">
  <wsdl:input message="tns:DeleteItemSoapIn"/>
  <wsdl:output message="tns:DeleteItemSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification for the **DeleteItem** operation.

```
<wsdl:operation name="DeleteItem">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/DeleteItem"/>
  <wsdl:input>
    <soap:header message="tns:DeleteItemSoapIn" part="Impersonation" use="literal"/>
    <soap:header message="tns:DeleteItemSoapIn" part="MailboxCulture" use="literal"/>
    <soap:header message="tns:DeleteItemSoapIn" part="RequestVersion" use="literal"/>
    <soap:body parts="request" use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="DeleteItemResult" use="literal"/>
    <soap:header message="tns:DeleteItemSoapOut" part="ServerVersion" use="literal"/>
  </wsdl:output>
</wsdl:operation>
```

3.1.4.3.1 Messages

The following table lists the WSDL message definitions that are specific to the **DeleteItem** operation.

Message name	Description
DeleteItemSoapIn	Specifies the SOAP message that requests an item be deleted from a mailbox.
DeleteItemSoapOut	Specifies the SOAP message that is returned by the server in response to a DeleteItemSoapIn operation request.

3.1.4.3.1.1 tns:DeleteItemSoapIn Message

The **DeleteItemSoapIn** WSDL message specifies the **DeleteItem** operation request to delete an item on the server.

```

<wsdl:message name="DeleteItemSoapIn">
  <wsdl:part name="request" element="tns:DeleteItem"/>
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>

```

The **DeleteItemSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/DeleteItem>.

The parts of the **DeleteItemSoapIn** WSDL message are listed and described in the following table.

Part name	Element/type	Description
request	tns:DeleteItem (section 3.1.4.3.2.1)	Specifies the SOAP body of a request.
Impersonation	t:ExchangeImpersonation ([MS-OXWSCDATA] section 2.2.4.3)	Specifies a SOAP header that identifies the user whom the client application is impersonating.
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.4.6)	Specifies a SOAP header that identifies the culture to be used for accessing a mailbox. The cultures are defined in [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the schema version for a DeleteItem operation request.

3.1.4.3.1.2 tns:DeleteItemSoapOut Message

The **DeleteItemSoapOut** WSDL message specifies the server response to the **DeleteItem** operation request to delete an item on the server.

```

<wsdl:message name="DeleteItemSoapOut">
  <wsdl:part name="DeleteItemResult" element="tns:DeleteItemResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>

```

The **DeleteItemSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/DeleteItem>.

The parts of the **DeleteItemSoapOut** WSDL message are listed and described in the following table.

Part name	Element/type	Description
DeleteItemResult	tns:DeleteItemResponse (section 3.1.4.3.2.2)	Specifies the SOAP body of a response message.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.10)	Specifies a SOAP header that identifies the server version for a response.

3.1.4.3.2 Elements

The following table lists the XML schema element definitions that are specific to the **DeleteItem** operation.

Element name	Description
DeleteItem	Specifies a request to delete an item from a mailbox.
DeleteItemResponse	Specifies a response to a single DeleteItem operation request.

3.1.4.3.2.1 DeleteItem Element

The **DeleteItem** element specifies a request to delete an item from a mailbox.

```
<xs:element name="DeleteItem"
    type="m:DeleteItemType"
/>
```

3.1.4.3.2.2 DeleteItemResponse Element

The **DeleteItemResponse** element specifies a response to a single **DeleteItem** operation request.

```
<xs:element name="DeleteItemResponse"
    type="m:DeleteItemResponseType"
/>
```

3.1.4.3.3 Complex Types

The following table lists the XML schema complex type definitions that are specific to the **DeleteItem** operation.

Complex type name	Description
DeleteItemResponseType	Specifies a response to a single DeleteItem operation request.
DeleteItemType	Specifies a request to delete items.

3.1.4.3.3.1 m:DeleteItemResponseType Complex Type

The **DeleteItemResponseType** complex type specifies a response to a single **DeleteItem** operation request. The **DeleteItemResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.16).

```
<xs:complexType name="DeleteItemResponseType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseResponseMessageType"
        />
    </xs:complexContent>
</xs:complexType>
```

3.1.4.3.3.2 m:DeleteItemType Complex Type

The **DeleteItemType** complex type specifies a request to delete items. The **DeleteItemType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```
<xs:complexType name="DeleteItemType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    >
      <xs:sequence>
        <xs:element name="ItemIds"
          type="t:NonEmptyArrayOfBaseItemIdsType"
        />
      </xs:sequence>
      <xs:attribute name="DeleteType"
        type="t:DisposalType"
        use="required"
      />
      <xs:attribute name="SendMeetingCancellations"
        type="t:CalendarItemCreateOrDeleteOperationType"
        use="optional"
      />
      <xs:attribute name="AffectedTaskOccurrences"
        type="t:AffectedTaskOccurrencesType"
        use="optional"
      />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists and describes the child elements of the **DeleteItemType** complex type.

Element name	Type	Description
ItemIds	t:NonEmptyArrayOfBaseItemIdsType (section 2.2.4.9)	Specifies the collection of items to be deleted.

The following table lists and describes the attributes of the **DeleteItemType** complex type.

Attribute name	Type	Description
DeleteType	t:DisposalType ([MS-OXWSCDATA] section 2.2.2.9)	Specifies an enumeration value that describes how an item is to be deleted.
SendMeetingCancellations	t:CalendarItemCreateOrDeleteOperationType ([MS-OXWSMTGS] section 2.2.5.1)	Specifies an enumeration that describes how

Attribute name	Type	Description
		cancellations are to be handled for deleted meetings.
AffectedTaskOccurrences	t:AffectedTaskOccurrencesType (IMS-OXWSTASK section 3.1.4.3.1.1)	Specifies an enumeration value that indicates whether a task instance or a task master is to be deleted.

3.1.4.4 GetItem Operation

Note Some of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure. For information about specific differences between versions, see the behavior notes that are provided in the Product Behavior appendix.

The **GetItem** operation gets items on the server.

The following is the WSDL port type specification for the **GetItem** operation.

```
<wsdl:operation name="GetItem">
  <wsdl:input message="tns:.GetItemSoapIn"/>
  <wsdl:output message="tns:.GetItemSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification for the **GetItem** operation.

```
<wsdl:operation name="GetItem">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetItem"/>
  <wsdl:input>
    <soap:header message="tns:FormItemSoapIn" part="Impersonation" use="literal"/>
    <soap:header message="tns:FormItemSoapIn" part="MailboxCulture" use="literal"/>
    <soap:header message="tns:FormItemSoapIn" part="RequestVersion" use="literal"/>
    <soap:header message="tns:FormItemSoapIn" part="TimeZoneContext" use="literal"/>
    <soap:header message="tns:FormItemSoapIn" part="DateTimePrecision" use="literal" />
    <soap:header message="tns:FormItemSoapIn" part="ManagementRole" use="literal" />
  <soap:body parts="request" use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="FormItemResult" use="literal"/>
    <soap:header message="tns:FormItemSoapOut" part="ServerVersion" use="literal"/>
  </wsdl:output>
</wsdl:operation>
```

3.1.4.4.1 Messages

The following table lists the WSDL message definitions that are specific to the **GetItem** operation.

Message name	Description
GetItemSoapIn	Specifies the SOAP message that requests to get an item from a mailbox.
GetItemSoapOut	Specifies the SOAP message that is returned by the server in response to a GetItem operation request.

3.1.4.4.1.1 tns:.GetItemSoapIn Message

Note Some of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure. For information about specific differences between versions, see the behavior notes that are provided in the Product Behavior appendix.

The **GetItemSoapIn** WSDL message specifies the **GetItem** operation request to get an item from the server.

```
<wsdl:message name="GetItemSoapIn">
  <wsdl:part name="request" element="tns:.GetItem"/>
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
  <wsdl:part name="DateTimePrecision" element="t:DateTimePrecision" />
  <wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
```

The **GetItemSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetItem>.

The parts of the **GetItemSoapIn** WSDL message are listed and described in the following table.

Part name	Element/type	Description
request	tns:.GetItem (section 3.1.4.4.2.1)	Specifies the SOAP body of a request.
Impersonation	t:ExchangeImpersonation ([MS-OXWSCDATA] section 2.2.4.3)	Specifies a SOAP header that identifies the user whom the client application is impersonating.
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.4.6)	Specifies a SOAP header that identifies the culture to be used for accessing a mailbox. The cultures are defined in [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the schema version for a GetItem operation request.
TimeZoneContext	t:TimeZoneContex ([MS-OXWSGTZ] section 2.2.4.11)	Specifies a SOAP header that identifies the time zone to be used for all responses from the server. All times that are returned from the server will be converted to the specified time zone.
DateTimePrecision	t:DateTimePrecision ([MS-OXWSCDATA] section 2.2.4.1)	Specifies a SOAP header that identifies the resolution of date/time values in responses from the server, either in seconds or in milliseconds. This header SHOULD <6> be

Part name	Element/type	Description
		included.
ManagementRole	t:ManagementRole (section 2.2.3.2)	Specifies the roles the user or application wants to use. (7)

3.1.4.4.1.2 tns:.GetItemSoapOut Message

The **GetItemSoapOut** WSDL message specifies the server response to the **GetItem** operation request to get an item from the server.

```
<wsdl:message name="GetItemSoapOut">
  <wsdl:part name="GetItemResult" element="tns:.GetItemResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **GetItemSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/GetItem>.

The parts of the **GetItemSoapOut** WSDL message are listed and described in the following table.

Part name	Element/type	Description
GetItemResult	tns:.GetItemResponse (section 3.1.4.4.2.2)	Specifies the SOAP body of a response message.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.10)	Specifies a SOAP header that identifies the server version for a response.

3.1.4.4.2 Elements

The following table lists the XML schema element definitions that are specific to the **GetItem** operation.

Element name	Description
GetItem	Specifies a request to get an item from a mailbox.
GetItemResponse	Specifies a response to a GetItem operation request.

3.1.4.4.2.1 GetItem Element

The **GetItem** element specifies a request to get an item from a mailbox.

```
<xss:element name="GetItem"
  type="m:GetItemType"
/>
```

3.1.4.4.2.2 GetItemResponse Element

The **GetItemResponse** element specifies a response to a **GetItem** operation request.

```

<xs:element name="GetItemResponse"
    type="m:GetItemResponseType"
/>

```

3.1.4.4.3 Complex Types

The following table lists the XML schema complex type definitions that are specific to the **GetItem** operation.

Complex type name	Description
GetItemResponseType	Specifies a response to a GetItem operation request.
GetItemType	Specifies a request to get items from a mailbox.

3.1.4.4.3.1 m:GetItemResponseType Complex Type

The **GetItemResponseType** complex type specifies a response to a **GetItem** operation request. The **GetItemResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.16).

```

<xs:complexType name="GetItemResponseType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseResponseMessageType"
        />
    </xs:complexContent>
</xs:complexType>

```

3.1.4.4.3.2 m:GetItemType Complex Type

The **GetItemType** complex type specifies a request to get items from a mailbox. The **GetItemType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```

<xs:complexType name="GetItemType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseRequestType"
        >
            <xs:sequence>
                <xs:element name="ItemShape"
                    type="t:ItemResponseShapeType"
                />
                <xs:element name="ItemIds"
                    type="t:NonEmptyArrayOfBaseItemIdsType"
                />
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

```

The following table lists and describes the child elements of the **GetItemType** complex type.

Element name	Type	Description
ItemShape	t:ItemResponseShapeType ([MS-OXWSCDATA] section 2.2.3.38)	Specifies the response shape of a GetItem operation response.
ItemIds	t:NonEmptyArrayOfBaseItemIdsType (section 2.2.4.9)	Specifies the collection of items that a GetItem operation is to get.

3.1.4.5 MarkAllItemsAsRead Operation

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **MarkAllItemsAsRead** operation marks all items in a folder as read.[<8>](#)

The following is the WSDL port type specification for the **MarkAllItemsAsRead** operation.

```
<wsdl:operation name="MarkAllItemsAsRead">
  <wsdl:input message="tns:MarkAllItemsAsReadSoapIn"/>
  <wsdl:output message="tns:MarkAllItemsAsReadSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification for the **MarkAllItemsAsRead** operation.

```
<wsdl:operation name="MarkAllItemsAsRead">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/MarkAllItemsAsRead"/>
  <wsdl:input>
    <soap:header message="tns:MarkAllItemsAsReadSoapIn" part="Impersonation" use="literal"/>
    <soap:header message="tns:MarkAllItemsAsReadSoapIn" part="MailboxCulture" use="literal"/>
    <soap:header message="tns:MarkAllItemsAsReadSoapIn" part="RequestVersion" use="literal"/>
    <soap:body parts="request" use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="MarkAllItemsAsReadResult" use="literal"/>
    <soap:header message="tns:MarkAllItemsAsReadSoapOut" part="ServerVersion" use="literal"/>
  </wsdl:output>
</wsdl:operation>
```

3.1.4.5.1 Messages

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The following table lists the WSDL message definitions that are specific to the **MarkAllItemsAsRead** operation.

Message name	Description
MarkAllItemsAsReadSoapIn	Specifies the SOAP message that requests to mark all items as read.
MarkAllItemsAsReadSoapOut	Specifies the SOAP message that is returned by the server in response to a MarkAllItemsAsRead operation request.

3.1.4.5.1.1 tns:MarkAllItemsAsReadSoapIn Message

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **MarkAllItemsAsReadSoapIn** WSDL message specifies the **MarkAllItemsAsRead** operation request to mark all items as read.

```
<wsdl:message name="MarkAllItemsAsReadSoapIn">
  <wsdl:part name="request" element="tns:MarkAllItemsAsRead"/>
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

The **MarkAllItemsAsReadSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/MarkAllItemsAsRead>.

The parts of the **MarkAllItemsAsReadSoapIn** WSDL message are listed and described in the following table.

Part name	Element/type	Description
request	tns:MarkAllItemsAsRead (section 3.1.4.5.2.1)	Specifies the SOAP body of a request.
Impersonation	t:ExchangeImpersonation ([MS-OXWSCDATA] section 2.2.4.3)	Specifies a SOAP header that identifies the user whom the client application is impersonating.
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.4.6)	Specifies a SOAP header that identifies the culture to be used for accessing a mailbox. The cultures are defined in [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the schema version for a MarkAllItemsAsRead operation request.

3.1.4.5.1.2 tns:MarkAllItemsAsReadSoapOut Message

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **MarkAllItemsAsReadSoapOut** WSDL message specifies the server response to the **MarkAllItemsAsRead** operation request to mark all items as read.

```
<wsdl:message name="MarkAllItemsAsReadSoapOut">
  <wsdl:part name="MarkAllItemsAsReadResult" element="tns:MarkAllItemsAsReadResponse"/>
```

```

<wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>

```

The **MarkAllItemsAsReadSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/MarkAllItemsAsRead>.

The parts of the **MarkAllItemsAsReadSoapOut** WSDL message are listed and described in the following table.

Part name	Element/type	Description
MarkAllItemsAsReadResult	tns:MarkAllItemsAsReadResponse (section 3.1.4.5.2.2)	Specifies the SOAP body of a response message.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.10)	Specifies a SOAP header that identifies the server version for the response to a MarkAllItemsAsRead operation request.

3.1.4.5.2 Elements

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The following table lists the XML schema element definitions that are specific to the **MarkAllItemsAsRead** operation.

Element name	Description
MarkAllItemsAsRead	Specifies a request to mark all items as read.
MarkAllItemsAsReadResponse	Specifies a response to a MarkAllItemsAsRead operation request.

3.1.4.5.2.1 MarkAllItemsAsRead Element

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **MarkAllItemsAsRead** element specifies a request to mark all items as read.

```
<xss:element name="MarkAllItemsAsRead" type="m:MarkAllItemsAsReadType"/>
```

3.1.4.5.2.2 MarkAllItemsAsReadResponse Element

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **MarkAllItemsAsReadResponse** element specifies a response to a **MarkAllItemsAsRead** operation request.

```
<xss:element name="MarkAllItemsAsReadResponse" type="m:MarkAllItemsAsReadResponseType"/>
```

3.1.4.5.3 Complex Types

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The following table lists the XML schema complex type definitions that are specific to the **MarkAllItemsAsRead** operation.

Complex type name	Description
MarkAllItemsAsReadResponseType	Specifies a response to a call to the MarkAllItemsAsRead operation.
MarkAllItemsAsReadType	Specifies an operation to mark all items as read.

3.1.4.5.3.1 m:MarkAllItemsAsReadType Complex Type

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **MarkAllItemsAsReadType** complex type specifies a request to mark all items as read. The **MarkAllItemsAsReadType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```
<xs:complexType name="MarkAllItemsAsReadType">
  <xs:complexContent>
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element name="ReadFlag" type="xs:boolean" minOccurs="1" maxOccurs="1"/>
        <xs:element name="SuppressReadReceipts" type="xs:boolean" minOccurs="1" maxOccurs="1"/>
        <xs:element name="FolderIds" type="t:NonEmptyArrayOfBaseFolderIdsType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

3.1.4.5.3.2 m:MarkAllItemsAsReadResponseType Complex Type

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

The **MarkAllItemsAsReadResponseType** complex type specifies a response to a call to the **MarkAllItemsAsRead** operation. The **MarkAllItemsAsReadResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.16).

```
<xs:complexType name="MarkAllItemsAsReadResponseType">
  <xs:complexContent>
    <xs:extension base="m:BaseResponseMessageType"/>
  </xs:complexContent>
</xs:complexType>
```

3.1.4.6 MoveItem Operation

The **MoveItem** operation moves items on the server.

The following is the WSDL port type specification for the **MoveItem** operation.

```
<wsdl:operation name="MoveItem">
  <wsdl:input message="tns:MoveItemSoapIn"/>
  <wsdl:output message="tns:MoveItemSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification for the **MoveItem** operation.

```
<wsdl:operation name="MoveItem">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/MoveItem"/>
  <wsdl:input>
    <soap:header message="tns:MoveItemSoapIn" part="Impersonation" use="literal"/>
    <soap:header message="tns:MoveItemSoapIn" part="MailboxCulture" use="literal"/>
    <soap:header message="tns:MoveItemSoapIn" part="RequestVersion" use="literal"/>
    <soap:body parts="request" use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="MoveItemResult" use="literal"/>
    <soap:header message="tns:MoveItemSoapOut" part="ServerVersion" use="literal"/>
  </wsdl:output>
</wsdl:operation>
```

3.1.4.6.1 Messages

The following table lists the WSDL message definitions that are specific to the **MoveItem** operation.

Message name	Description
MoveItemSoapIn	Specifies the SOAP message that requests to move an item in a mailbox.
MoveItemSoapOut	Specifies the SOAP message that is returned by the server in response to a MoveItem operation request.

3.1.4.6.1.1 tns:MoveItemSoapIn Message

The **MoveItemSoapIn** WSDL message specifies the **MoveItem** operation request to move an item on the server.

```
<wsdl:message name="MoveItemSoapIn">
  <wsdl:part name="request" element="tns:MoveItem"/>
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

The **MoveItemSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/MoveItem>.

The parts of the **MoveItemSoapIn** WSDL message are listed and described in the following table.

Part name	Element/type	Description
request	tns:MoveItem (section 3.1.4.6.2.1)	Specifies the SOAP body of a request.
Impersonation	t:ExchangeImpersonation ([MS-OXWSCDATA] section 2.2.4.3)	Specifies a SOAP header that identifies the user whom the client application is impersonating.
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.4.6)	Specifies a SOAP header that identifies the culture to be used for accessing a mailbox. The cultures are defined in [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the schema version for a MoveItem operation request.

3.1.4.6.1.2 tns:MoveItemSoapOut Message

The **MoveItemSoapOut** WSDL message specifies the server response to the **MoveItem** operation request to move an item on the server.

The **MoveItemSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/MoveItem>.

The parts of the **MoveItemSoapOut** WSDL message are listed and described in the following table.

Part name	Element/type	Description
MoveItemResult	tns:MoveItemResponse (section 3.1.4.6.2.2)	Specifies the SOAP body of a response message.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.10)	Specifies a SOAP header that identifies the server version for the response to a MoveItem operation request.

3.1.4.6.2 Elements

The following table lists the XML schema element definitions that are specific to the **MoveItem** operation.

Element name	Description
MoveItem	Specifies a request to move an item.
MoveItemResponse	Specifies a response to a MoveItem operation request.

3.1.4.6.2.1 MoveItem Element

The **MoveItem** element specifies a request to move an item.

```
<xs:element name="MoveItem"
    type="m:MoveItemType"
/>
```

3.1.4.6.2.2 MoveItemResponse Element

The **MoveItemResponse** element specifies a response to a **MoveItem** operation request.

```
<xs:element name="MoveItemResponse"
    type="m:MoveItemResponseType"
/>
```

3.1.4.6.3 Complex Types

The following table lists the XML schema complex type definitions that are specific to the **MoveItem** operation.

Complex type name	Description
MoveItemResponseType	Specifies a response to a call to the MoveItem operation.
MoveItemType	Specifies an operation to move items in a mailbox.

3.1.4.6.3.1 m:MoveItemResponseType Complex Type

The **MoveItemResponseType** complex type specifies a response to a call to the **MoveItem** operation. The **MoveItemResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.16).

```
<xs:complexType name="MoveItemResponseType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseResponseMessageType"
        />
    </xs:complexContent>
</xs:complexType>
```

3.1.4.6.3.2 m:MoveItemType Complex Type

The **MoveItemType** complex type specifies an operation to move items in a mailbox. The **MoveItemType** complex type extends the **BaseMoveCopyItemType** complex type, as specified in section [2.2.4.1](#).

```
<xs:complexType name="MoveItemType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseMoveCopyItemType"
        />
    </xs:complexContent>
</xs:complexType>
```

3.1.4.7 SendItem Operation

The **SendItem** operation sends messages and post items on the server.

The following is the WSDL port type specification for the **SendItem** operation.

```
<wsdl:operation name="SendItem">
  <wsdl:input message="tns:SendItemSoapIn" />
  <wsdl:output message="tns:SendItemSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification for the **SendItem** operation.

```
<wsdl:operation name="SendItem">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/SendItem" />
  <wsdl:input>
    <soap:header message="tns:SendItemSoapIn" part="Impersonation" use="literal"/>
    <soap:header message="tns:SendItemSoapIn" part="MailboxCulture" use="literal"/>
    <soap:header message="tns:SendItemSoapIn" part="RequestVersion" use="literal"/>
    <soap:body parts="request" use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="SendItemResult" use="literal" />
    <soap:header message="tns:SendItemSoapOut" part="ServerVersion" use="literal"/>
  </wsdl:output>
</wsdl:operation>
```

3.1.4.7.1 Messages

The following table lists the WSDL message definitions that are specific to the **SendItem** operation.

Message name	Description
SendItemSoapIn	Specifies the SOAP message that requests to send an item.
SendItemSoapOut	Specifies the SOAP message that is sent by the server in response to a SendItem operation request.

3.1.4.7.1.1 tns:SendItemSoapIn Message

The **SendItemSoapIn** WSDL message specifies the **SendItem** operation request to post items on the server.

```
<wsdl:message name="SendItemSoapIn">
  <wsdl:part name="request" element="tns:SendItem" />
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
```

The **SendItemSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/SendItem>.

The parts of the **SendItemSoapIn** WSDL message are listed and described in the following table.

Part name	Element/type	Description
request	tns:SendItem (section 3.1.4.7.2.1)	Specifies the SOAP body of a request.
Impersonation	t:ExchangeImpersonation (IMS-OXWSCDATA section 2.2.4.3)	Specifies a SOAP header that identifies the user whom the client application is impersonating.
MailboxCulture	t:MailboxCulture (IMS-OXWSCDATA section 2.2.4.6)	Specifies a SOAP header that identifies the culture to be used for accessing a mailbox. The cultures are defined in RFC3066 .
RequestVersion	t:RequestServerVersion (IMS-OXWSCDATA section 2.2.4.9)	Specifies a SOAP header that identifies the schema version for a SendItem operation request.

3.1.4.7.1.2 tns:SendItemSoapOut Message

The **SendItemSoapOut** WSDL message specifies the server response to a **SendItem** operation request to post items on the server.

```
<wsdl:message name="SendItemSoapOut">
  <wsdl:part name="SendItemResult" element="tns:SendItemResponse" />
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **SendItemSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/SendItem>.

The parts of the **SendItemSoapOut** WSDL message are listed and described in the following table.

Part name	Element/type	Description
SendItemResult	tns:SendItemResponse (section 3.1.4.7.2.2)	Specifies the SOAP body of a response message.
ServerVersion	t:ServerVersionInfo (IMS-OXWSCDATA section 2.2.4.10)	Specifies a SOAP header that identifies the server version for the response to a SendItem operation request.

3.1.4.7.2 Elements

The following table lists the XML schema element definitions that are specific to the **SendItem** operation.

Element name	Description
SendItem	Specifies a request to send an item.
SentItemResponse	Specifies a response to a SendItem operation request.

3.1.4.7.2.1 SendItem Element

The **SendItem** element specifies the root element in a request to send an item.

```
<xs:element name="SendItem"
    type="m:SendItemType"
/>
```

3.1.4.7.2.2 SendItemResponse Element

The **SendItemResponse** element specifies a response to a **SendItem** operation request.

```
<xs:element name="SendItemResponse"
    type="m:SendItemResponseType"
/>
```

3.1.4.7.3 Complex Types

The following table lists the XML schema complex type definitions that are specific to the **SendItem** operation.

Complex type name	Description
SendItemResponseType	Specifies a response to a SendItem operation request.
SendItemType	Specifies a request to send messages and post items on the server.

3.1.4.7.3.1 m:SendItemResponseType Complex Type

The **SendItemResponseType** complex type specifies a response to a **SendItem** operation request. The **SendItemResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.16).

```
<xs:complexType name="SendItemResponseType">
    <xs:complexContent>
        <xs:extension
            base="m:BaseResponseMessageType"
        />
    </xs:complexContent>
</xs:complexType>
```

3.1.4.7.3.2 m:SendItemType Complex Type

The **SendItemType** complex type specifies a request to send messages and post items on the server. The **SendItemType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```
<xs:complexType name="SendItemType">
    <xs:complexContent>
```

```

<xs:extension
  base="m:BaseRequestType"
>
  <xs:sequence>
    <xs:element name="ItemIds"
      type="t:NonEmptyArrayOfBaseItemIdsType"
    />
    <xs:element name="SavedItemFolderId"
      type="t:TargetFolderIdType"
      minOccurs="0"
    />
  </xs:sequence>
  <xs:attribute name="SaveItemToFolder"
    type="xs:boolean"
    use="required"
  />
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists and describes the child elements of the **SendItemType** complex type.

Element name	Type	Description
ItemIds	t:NonEmptyArrayOfBaseItemIdsType (section 2.2.4.9)	Specifies an array of item identifiers for the items to try to send.
SavedItemFolderId	t:TargetFolderIdType ([MS-OXWSFOLD] section 2.2.4.14)	Specifies the identity of the folder that contains a saved version of a sent item.

The following table lists and describes the attributes of the **SendItemType** complex type.

Attribute name	Type	Description
SaveItemToFolder	xs:boolean [XMLSCHEMA2]	Specifies a Boolean value that indicates whether a copy of a sent item is saved.

3.1.4.8 UpdateItem Operation

The **UpdateItem** operation updates items on the server.

The following is the WSDL port type specification for the **UpdateItem** operation.

```

<wsdl:operation name="UpdateItem">
  <wsdl:input message="tns:UpdateItemSoapIn"/>
  <wsdl:output message="tns:UpdateItemSoapOut"/>
</wsdl:operation>

```

The following is the WSDL binding specification for the **UpdateItem** operation.

```
<wsdl:operation name="UpdateItem">
```

```

<soap:operation
  soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/UpdateItem"/>
  <wsdl:input>
    <soap:header message="tns:UpdateItemSoapIn" part="Impersonation" use="literal"/>
    <soap:header message="tns:UpdateItemSoapIn" part="MailboxCulture" use="literal"/>
    <soap:header message="tns:UpdateItemSoapIn" part="RequestVersion" use="literal"/>
    <soap:header message="tns:UpdateItemSoapIn" part="TimeZoneContext" use="literal"/>
    <soap:body parts="request" use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body parts="UpdateItemResult" use="literal"/>
    <soap:header message="tns:UpdateItemSoapOut" part="ServerVersion" use="literal"/>
  </wsdl:output>
</wsdl:operation>

```

3.1.4.8.1 Messages

The following table lists the WSDL message definitions that are specific to the **UpdateItem** operation.

Message name	Description
UpdateItemSoapIn	Specifies the SOAP message that requests that an item be updated.
UpdateItemSoapOut	Specifies the SOAP message that is returned in response to an UpdateItem operation request.

3.1.4.8.1.1 tns:UpdateItemSoapIn Message

The **UpdateItemSoapIn** WSDL message specifies the **UpdateItem** operation request to update items on the server.

```

<wsdl:message name="UpdateItemSoapIn">
  <wsdl:part name="request" element="tns:UpdateItem"/>
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>

```

The **UpdateItemSoapIn** WSDL message is the input message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/UpdateItem>.

The parts of the **UpdateItemSoapIn** WSDL message are listed and described in the following table.

Part name	Element/type	Description
request	tns:UpdateItem (section 3.1.4.8.2.1)	Specifies the SOAP body of a request.
Impersonation	t:ExchangeImpersonation ([MS-OXWSCDATA] section 2.2.4.3)	Specifies a SOAP header that identifies the user whom the client application is impersonating.
MailboxCulture	t:MailboxCulture ([MS-OXWSCDATA] section 2.2.4.3)	Specifies a SOAP header that identifies the mailbox culture.

Part name	Element/type	Description
	[MS-OXWSCDATA] section 2.2.4.6)	culture to be used for accessing a mailbox. The cultures are defined in [RFC3066] .
RequestVersion	t:RequestServerVersion ([MS-OXWSCDATA] section 2.2.4.9)	Specifies a SOAP header that identifies the schema version for an UpdateItem operation request.
TimeZoneContext	t:TimeZoneContext ([MS-OXWSGTZ] section 2.2.4.11)	Specifies a SOAP header that identifies the time zone to be used for all responses from the server. All times that are returned from the server will be converted to the specified time zone.

3.1.4.8.1.2 tns:UpdateItemSoapOut Message

The **UpdateItemSoapOut** WSDL message specifies the server response to an **UpdateItem** operation request to update items on the server.

```
<wsdl:message name="UpdateItemSoapOut">
  <wsdl:part name="UpdateItemResult" element="tns:UpdateItemResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **UpdateItemSoapOut** WSDL message is the output message for the SOAP action <http://schemas.microsoft.com/exchange/services/2006/messages/UpdateItem>.

The parts of the **UpdateItemSoapOut** WSDL message are listed and described in the following table.

Part name	Element/type	Description
UpdateItemResult	tns:UpdateItemResponse (section 3.1.4.8.2.2)	Specifies the SOAP body of a response message.
ServerVersion	t:ServerVersionInfo ([MS-OXWSCDATA] section 2.2.4.10)	Specifies a SOAP header that identifies the server version for a response to an UpdateItem operation request.

3.1.4.8.2 Elements

The following table lists the XML schema element definitions that are specific to the **UpdateItem** operation.

Element name	Description
UpdateItem	Specifies a request to update an item in a mailbox.
UpdateItemResponse	Specifies a response to an UpdateItem operation request.

3.1.4.8.2.1 UpdateItem Element

The **UpdateItem** element specifies a request to update an item in a mailbox.

```
<xs:element name="UpdateItem"
    type="m:UpdateItemType"
/>
```

3.1.4.8.2.2 UpdateItemResponse Element

The **UpdateItemResponse** element specifies a response to an **UpdateItem** operation request.

```
<xs:element name="UpdateItemResponse"
    type="m:UpdateItemResponseType"
/>
```

3.1.4.8.3 Complex Types

The following table lists the XML schema complex type definitions that are specific to this operation.

Complex type name	Description
UpdateItemResponseType	Specifies the response to a call to the UpdateItem operation.
UpdateItemType	Specifies a request to update a set of items.
AppendToItemFieldType	Specifies data to append to a single property of an item during and UpdateItem operation.
ChangeDescriptionType	Specifies the base type that is used to describe changes in UpdateFolder operations, as specified in [MS-OXWSFOLD] section 3.1.4.8, and UpdateItem operations.
DeleteItemFieldType	Specifies a property to delete from an item.
ItemChangeDescriptionType	Specifies data that describes changes that are applied by using the UpdateItem operation.
ItemChangeType	Specifies an item identifier and the updates to apply to the item.
NonEmptyArrayOfItemChangeDescriptionsType	Specifies an array of items and their change types.
NonEmptyArrayOfItemChangesType	Specifies an array of items and their changes.
SetItemFieldType	Specifies an update to a single property of an item.

3.1.4.8.3.1 m:UpdateItemResponseType Complex Type

The **UpdateItemResponseType** complex type specifies the response to a call to the **UpdateItem** operation. The **UpdateItemResponseType** complex type extends the **BaseResponseMessageType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.16).

```
<xs:complexType name="UpdateItemResponseType">
```

```

<xs:complexContent>
  <xs:extension
    base="m:BaseResponseMessageType"
  />
</xs:complexContent>
</xs:complexType>

```

3.1.4.8.3.2 m:UpdateItemType Complex Type

The **UpdateItemType** complex type specifies a request to update a set of items. The **UpdateItemType** complex type extends the **BaseRequestType** complex type ([\[MS-OXWSCDATA\]](#) section 2.2.3.15).

```

<xs:complexType name="UpdateItemType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    />
    <xs:sequence>
      <xs:element name="SavedItemFolderId"
        type="t:TargetFolderIdType"
        minOccurs="0"
      />
      <xs:element name="ItemChanges"
        type="t:NonEmptyArrayOfItemChangesType"
      />
    </xs:sequence>
    <xs:attribute name="ConflictResolution"
      type="t:ConflictResolutionType"
      use="required"
    />
    <xs:attribute name="MessageDisposition"
      type="t:MessageDispositionType"
      use="optional"
    />
    <xs:attribute name="SendMeetingInvitationsOrCancellations"
      type="t:CalendarItemUpdateOperationType"
      use="optional"
    />
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **UpdateItemType** complex type.

Element name	Type	Description
SavedItemFolderId	t:TargetFolderIdType ([MS-OXWSFOLD] section 2.2.4.14)	Specifies the target folder for saved items.
ItemChanges	t:NonEmptyArrayOfItemChangesType (section 3.1.4.8.3.9)	Specifies an array of item changes.

The following table lists the attributes of the **UpdateItemType** complex type.

Attribute name	Type	Description
ConflictResolution	t:ConflictResolutionType (section 3.1.4.8.4.1)	Specifies an enumeration value that represents the type of conflict resolution that is performed during an update.
MessageDisposition	t:MessageDispositionType ([MS-OXWSMSG] section 2.2.5.1)	Specifies an enumeration value that describes how a message item is handled after it is updated.
SendMeetingInvitationsOrCancellations	t:CalendarItemUpdateOperationType ([MS-OXWSMTGS] section 2.2.5.3)	Specifies an enumeration value that describes how a calendar item is handled after it is updated.

3.1.4.8.3.3 t:AppendToItemType Complex Type

The **AppendToItemType** complex type specifies data to append to a single property of an item during an **UpdateItem** operation. The **AppendToItemType** complex type extends the **ItemChangeDescriptionType** complex type, as specified in section [3.1.4.8.3.6](#).

```

<xs:complexType name="AppendToItemType">
  <xs:complexContent>
    <xs:extension
      base="t:ItemChangeDescriptionType"
    >
      <xs:choice>
        <xs:element name="Item"
          type="t:ItemType"
        />
        <xs:element name="Message"
          type="t:MessageType"
        />
        <xs:element name="CalendarItem"
          type="t:CalendarItemType"
        />
        <xs:element name="Contact"
          type="t>ContactItemType"
        />
        <xs:element name="DistributionList"
          type="t:DistributionListType"
        />
      </xs:choice>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

```

<xs:element name="MeetingMessage"
    type="t:MeetingMessageType"
/>
<xs:element name="MeetingRequest"
    type="t:MeetingRequestMessageType"
/>
<xs:element name="MeetingResponse"
    type="t:MeetingResponseMessageType"
/>
<xs:element name="MeetingCancellation"
    type="t:MeetingCancellationMessageType"
/>
<xs:element name="Task"
    type="t:TaskType"
/>
<xs:element name="PostItem"
    type="t:PostItemType"
/>
</xs:choice>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table lists the child elements of the **AppendToItemFieldType** complex type.

Element name	Type	Description
Item	t:ItemType (section 2.2.4.6)	Specifies a generic item.
Message	t:MessageType ([MS-OXWSMSG] section 2.2.4.1)	Specifies an e-mail message or non-IPM.Note item.
CalendarItem	t:CalendarItemType ([MS-OXWSMTGS] section 2.2.4.4)	Specifies a calendar item.
Contact	t:ContactItemType ([MS-OXWSCONT] section 2.2.4.2)	Specifies a contact item.
DistributionList	t:DistributionListType ([MS-OXWSDLIST] section 2.2.4.3)	Specifies a distribution list.
MeetingMessage	t:MeetingMessageType ([MS-OXWSMTGS] section 2.2.4.11)	Specifies a meeting.
MeetingRequest	t:MeetingRequestMessageType ([MS-OXWSMTGS] section 2.2.4.12)	Specifies a meeting request.
MeetingResponse	t:MeetingResponseMessageType ([MS-OXWSMTGS] section 2.2.4.13)	Specifies a meeting response.
MeetingCancellation	t:MeetingCancellationMessageType ([MS-OXWSMTGS] section 2.2.4.10)	Specifies a meeting cancellation.
Task	t:TaskType ([MS-OXWSTASK] section 2.2.4.3)	Specifies a task.
PostItem	t:PostItemType ([MS-OXWSPOST] section 2.2.4.1)	Specifies a post item.

3.1.4.8.3.4 t:ChangeDescriptionType Complex Type

The **ChangeDescriptionType** complex type specifies the base type that is used to describe changes in **UpdateFolder** operation, as specified in [\[MS-OXWSFOLD\]](#) section 3.1.4.8 ,and **UpdateItem** operation, as specified in (section [3.1.4.8](#)).

```
<xs:complexType name="ChangeDescriptionType"
    abstract="true"
>
<xs:sequence>
    <xs:element
        ref="t:Path"
    />
</xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **ChangeDescriptionType** complex type.

Element	Type	Description
Path	t:Path ([MS-OXWSCDATA] section 2.2.4.8)	Specifies a substitution group that specifies the property to update.

3.1.4.8.3.5 t:DeleteItemFieldType Complex Type

The **DeleteItemFieldType** complex type specifies a property to delete from an item. The **DeleteItemFieldType** complex type extends the **ItemChangeDescriptionType** complex type, as specified in section [3.1.4.8.3.6](#).

```
<xs:complexType name="DeleteItemFieldType">
    <xs:complexContent>
        <xs:extension
            base="t:ItemChangeDescriptionType"
        >
            <xs:sequence />
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
```

3.1.4.8.3.6 t:ItemChangeDescriptionType Complex Type

The **ItemChangeDescriptionType** complex type specifies data that describes changes that are applied by using the **UpdateItem** operation. The **ItemChangeDescriptionType** complex type extends the **ChangeDescriptionType** complex type, as specified in section [3.1.4.8.3.4](#).

```
<xs:complexType name="ItemChangeDescriptionType">
    <xs:complexContent>
        <xs:extension
            base="t:ChangeDescriptionType"
        />
    </xs:complexContent>
</xs:complexType>
```

3.1.4.8.3.7 t:ItemChangeType Complex Type

The **ItemChangeType** complex type specifies an item identifier and the updates to apply to the item.

```
<xs:complexType name="ItemChangeType">
  <xs:sequence>
    <xs:choice>
      <xs:element name="ItemId"
        type="t:ItemIdType"
      />
      <xs:element name="OccurrenceItemId"
        type="t:OccurrenceItemIdType"
      />
      <xs:element name="RecurringMasterItemId"
        type="t:RecurringMasterItemIdType"
      />
    </xs:choice>
    <xs:element name="Updates"
      type="t:NonEmptyArrayOfItemChangeDescriptionsType"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **ItemChangeType** complex type.

Element name	Type	Description
ItemId	t:ItemIdType (section 2.2.4.15)	Specifies an item identifier of an item in a mailbox.
OccurrenceItemId	t:OccurrenceItemIdType (section 2.2.4.13)	Specifies a single occurrence of a recurring item.
RecurringMasterItemId	t:RecurringMasterItemIdType (section 2.2.4.14)	Specifies a recurrence master item by identifying the identifiers of one of its related occurrence items.
Updates	t:NonEmptyArrayOfItemChangeDescriptionsType (section 3.1.4.8.3.8)	Specifies an array that defines append, set, and delete changes to item properties.

3.1.4.8.3.8 t:NonEmptyArrayOfItemChangeDescriptionsType Complex Type

The **NonEmptyArrayOfItemChangeDescriptionsType** complex type specifies an array of items and their change types.

```
<xs:complexType name="NonEmptyArrayOfItemChangeDescriptionsType">
  <xs:choice
    maxOccurs="unbounded"
  >
    <xs:element name="AppendToItemField"
      type="t:AppendToItemFieldType"
    />
    <xs:element name="SetItemField"
      type="t:SetItemFieldType"
    />
    <xs:element name="DeleteItemField"
      type="t:DeleteItemFieldType"
    />
  </xs:choice>
</xs:complexType>
```

The following table lists the child elements of the **NonEmptyArrayOfItemChangeDescriptionsType** complex type.

Element name	Type	Description
AppendToItemField	t:AppendToItemFieldType (section 3.1.4.8.3.3)	Specifies data to append to a single property of an item during an UpdateItem operation.
SetItemField	t:SetItemFieldType (section 3.1.4.8.3.10)	Specifies an update to a single property of an item in an UpdateItem operation.
DeleteItemField	t:DeleteItemFieldType (section 3.1.4.8.3.5)	Specifies an operation to delete a given property from an item during an UpdateItem operation.

3.1.4.8.3.9 t:NonEmptyArrayOfItemChangesType Complex Type

The **NonEmptyArrayOfItemChangesType** complex type specifies an array of items and their changes.

```
<xs:complexType name="NonEmptyArrayOfItemChangesType">
  <xs:sequence>
    <xs:element name="ItemChange"
      type="t:ItemChangeType"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **NonEmptyArrayOfItemChangesType** complex type.

Element name	Type	Description
ItemChange	t:ItemChangeType (section 3.1.4.8.3.7)	Specifies an item identifier and the updates to apply to the item.

3.1.4.8.3.10 t:SetItemFieldType Complex Type

The **SetItemFieldType** complex type specifies an update to a single property of an item. The **SetItemFieldType** complex type extends the **ItemChangeDescription** complex type, as specified in section [3.1.4.8.3.6](#).

```

<xs:complexType name="SetItemFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:ItemChangeDescriptionType"
    >
      <xs:choice>
        <xs:element name="Item"
          type="t:ItemType"
        />
        <xs:element name="Message"
          type="t:MessageType"
        />
        <xs:element name="CalendarItem"
          type="t:CalendarItemType"
        />
        <xs:element name="Contact"
          type="t>ContactItemType"
        />
        <xs:element name="DistributionList"
          type="t:DistributionListType"
        />
        <xs:element name="MeetingMessage"
          type="t:MeetingMessageType"
        />
        <xs:element name="MeetingRequest"
          type="t:MeetingRequestMessageType"
        />
        <xs:element name="MeetingResponse"
          type="t:MeetingResponseMessageType"
        />
        <xs:element name="MeetingCancellation"
          type="t:MeetingCancellationMessageType"
        />
        <xs:element name="Task"
          type="t:TaskType"
        />
        <xs:element name="PostItem"
          type="t:PostItemType"
        />
      </xs:choice>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

The following table lists and describes the child elements of the **SetItemType** complex type.

Element name	Type	Description
Item	t:ItemType (section 2.2.4.6)	Specifies a generic item.
Message	t:MessageType ([MS-OXWSMSG] section 2.2.4.1)	Specifies an e-mail message or non-IPM.Note item.
CalendarItem	t:CalendarItemType ([MS-OXWSMTGS] section 2.2.4.4)	Specifies a calendar item.
Contact	t>ContactItemType ([MS-OXWSCONT] section 2.2.4.2)	Specifies a contact item.
DistributionList	t:DistributionListType ([MS-OXWSDLIST] section 2.2.4.3)	Specifies a distribution list.
MeetingMessage	t:MeetingMessageType ([MS-OXWSMTGS] section 2.2.4.11)	Specifies a meeting.
MeetingRequest	t:MeetingRequestMessageType ([MS-OXWSMTGS] section 2.2.4.12)	Specifies a meeting request.
MeetingResponse	t:MeetingResponseMessageType ([MS-OXWSMTGS] section 2.2.4.13)	Specifies meeting response.
MeetingCancellation	t:MeetingCancellationMessageType ([MS-OXWSMTGS] section 2.2.4.10)	Specifies meeting cancellation.
Task	t:TaskType ([MS-OXWSTASK] section 2.2.4.3)	Specifies a task.
PostItem	t:PostItemType ([MS-OXWSPOST] section 2.2.4.1)	Specifies a post item.

3.1.4.8.4 Simple Types

The following table lists the XML schema simple type definitions that are specific to the **UpdateItem** operation.

Simple type name	Description
ConflictResolutionType	Specifies how a conflict is to be handled during an UpdateItem operation.

3.1.4.8.4.1 t:ConflictResolutionType Simple Type

The **ConflictResolutionType** simple type specifies how a conflict is to be handled during an **UpdateItem** operation.

```
<xs:simpleType name="ConflictResolutionType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="AlwaysOverwrite"
    />
  <xs:enumeration
```

```

        value="AutoResolve"
    />
<xss:enumeration
    value="NeverOverwrite"
    />
</xss:restriction>
</xss:simpleType>

```

The following table lists the values that are defined by the **ConflictResolutionType** simple type.

Value	Meaning
AlwaysOverwrite	If there is a conflict, the UpdateItem operation will overwrite information.
AutoResolve	The UpdateItem operation automatically resolves any conflict. The "AutoResolve" option will in most cases overwrite the existing value for a property. In some cases, the new value is ignored and the original value is retained. For example, user A changes the value of the Sensitivity property from "Normal" to "Confidential", and then user B sets that value to "Public". In this example, the "Confidential" setting is retained and user B's update is ignored.
NeverOverwrite	If there is a conflict, the UpdateItem operation fails and an error is returned.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

This section provides a simplified example of a request-response sequence for the **CreateItem** operation, as specified in section [3.1.4.2](#).

The following example shows a **CreateItem** request to create a message, send it, and save a copy in the SentItems folder.

```
<?xml version="1.0" encoding="utf-8" ?>
<CreateItem xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
             xmlns:xsd="http://www.w3.org/2001/XMLSchema"
             MessageDisposition="SendAndSaveCopy">
  <SavedItemFolderId xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
    <DistinguishedFolderId Id="sentitems"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/types" />
  </SavedItemFolderId>
  <Items xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
    <Message xmlns="http://schemas.microsoft.com/exchange/services/2006/types">
      <ItemClass>IPM.Note</ItemClass>
      <Subject>Daily Report</Subject>
      <Body BodyType="Text">(1) Handled customer issues, (2) Saved the world.</Body>
      <Sender>
        <Mailbox>
          <EmailAddress>user1@example.com</EmailAddress>
        </Mailbox>
      </Sender>
      <ToRecipients>
        <Mailbox>
          <EmailAddress>user2@example.com</EmailAddress>
        </Mailbox>
      </ToRecipients>
    </Message>
  </Items>
</CreateItem>
```

The following example shows a **CreateItem** response to the request to create a message, send it, and save a copy in the SentItems folder.

```
<?xml version="1.0" encoding="utf-8" ?>
<CreateItemType xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
                 xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <ResponseMessages xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
    <CreateItemResponseMessage ResponseClass="Success">
      <ResponseCode>NoError</ResponseCode>
      <Items />
    </CreateItemResponseMessage>
  </ResponseMessages>
</CreateItemType>
```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

Note Some of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure. For information about specific differences between versions, see the behavior notes that are provided in the Product Behavior appendix.

Note Some of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure. For information about specific differences between versions, see the behavior notes that are provided in the Product Behavior appendix.

The XML files that are listed in the following table are required in order to implement the functionality described in this document.

File name	Description	Section
MS-OXWScore.wsdl	Contains the WSDL for the implementation of this protocol.	6
MS-OXWScore-messages.xsd	Contains the XML schema message definitions used in this protocol.	7.1
MS-OXWScore-types.xsd	Contains the XML schema type definitions used in this protocol.	7.2

These files have to be placed in a common folder for the WSDL to validate and operate. Also, any schema files that are included in or imported into the MS-OXWScore-types.xsd or MS-OXWScore-messages.xsd schemas have to be placed in the common folder with the files named in the table.

This section provides the contents of the MS-OXWScore.wsdl file.

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
    xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
    xmlns:ss="http://www.w3.org/2001/XMLSchema" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
    xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
    targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages">
    <wsdl:types>
        <xss:schema id="messages" elementFormDefault="qualified" version="Exchange2010"
            xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
            xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
            xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns:xs="http://www.w3.org/2001/XMLSchema"
            targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
            <xss:import namespace="http://schemas.microsoft.com/exchange/services/2006/types"
                schemaLocation="MS-OXWScore-types.xsd"/>
            <xss:include schemaLocation="MS-OXWScore-messages.xsd"/>
            <!-- Add global elements and types from messages.xsd -->
        </xss:schema>
        <xss:schema id="types" elementFormDefault="qualified" version="Exchange2010"
            xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
            targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns:xs="http://www.w3.org/2001/XMLSchema">
            <xss:import namespace="http://www.w3.org/XML/1998/namespaces"/>
            <!-- Add global elements and types from types.xsd -->
        </xss:schema>
    </wsdl:types>
    <wsdl:portType name="ExchangeServicePortType">
```

```

<wsdl:operation name="GetItem">
  <wsdl:input message="tns:GetItemSoapIn"/>
  <wsdl:output message="tns:GetItemSoapOut"/>
</wsdl:operation>
<wsdl:operation name="CreateItem">
  <wsdl:input message="tns:CreateItemSoapIn"/>
  <wsdl:output message="tns:CreateItemSoapOut"/>
</wsdl:operation>
<wsdl:operation name="DeleteItem">
  <wsdl:input message="tns:DeleteItemSoapIn"/>
  <wsdl:output message="tns:DeleteItemSoapOut"/>
</wsdl:operation>
<wsdl:operation name="UpdateItem">
  <wsdl:input message="tns:UpdateItemSoapIn"/>
  <wsdl:output message="tns:UpdateItemSoapOut"/>
</wsdl:operation>
<wsdl:operation name="UpdateItemInRecoverableItems">
  <wsdl:input message="tns:UpdateItemInRecoverableItemsSoapIn"/>
  <wsdl:output message="tns:UpdateItemInRecoverableItemsSoapOut"/>
</wsdl:operation>
<wsdl:operation name="MarkAllItemsAsRead">
  <wsdl:input message="tns:MarkAllItemsAsReadSoapIn"/>
  <wsdl:output message="tns:MarkAllItemsAsReadSoapOut"/>
</wsdl:operation>
<wsdl:operation name="MoveItem">
  <wsdl:input message="tns:MoveItemSoapIn"/>
  <wsdl:output message="tns:MoveItemSoapOut"/>
</wsdl:operation>
<wsdl:operation name="CopyItem">
  <wsdl:input message="tns:CopyItemSoapIn"/>
  <wsdl:output message="tns:CopyItemSoapOut"/>
</wsdl:operation>
<wsdl:operation name="SendItem">
  <wsdl:input message="tns:SendItemSoapIn"/>
  <wsdl:output message="tns:SendItemSoapOut"/>
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="ExchangeServiceBinding" type="tns:ExchangeServicePortType">
  <wsdl:documentation>
    <wsi:Claim conformsTo="http://ws-i.org/profiles/basic/1.0" xmlns:wsi="http://ws-i.org/schemas/conformanceClaim"/>
  </wsdl:documentation>
  <soap:binding style="document" transport="http://schemas.xmlsoap.org/soap/http"/>
  <wsdl:operation name="GetItem">
    <soap:operation
      soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetItem"/>
    <wsdl:input>
      <soap:header message="tns:GetItemSoapIn" part="Impersonation" use="literal"/>
      <soap:header message="tns:GetItemSoapIn" part="MailboxCulture" use="literal"/>
      <soap:header message="tns:GetItemSoapIn" part="RequestVersion" use="literal"/>
      <soap:header message="tns:GetItemSoapIn" part="TimeZoneContext" use="literal"/>
      <soap:header message="tns:GetItemSoapIn" part="DateTimePrecision" use="literal"/>
      <soap:header message="tns:GetItemSoapIn" part="ManagementRole" use="literal" />
      <soap:body parts="request" use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body parts="GetItemResult" use="literal"/>
      <soap:header message="tns:GetItemSoapOut" part="ServerVersion" use="literal"/>
    </wsdl:output>
  </wsdl:operation>
</wsdl:binding>

```

```

    </wsdl:operation>
    <wsdl:operation name="CreateItem">
        <soap:operation
            soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/CreateItem"/>
        <wsdl:input>
            <soap:header message="tns:CreateItemSoapIn" part="Impersonation" use="literal"/>
            <soap:header message="tns:CreateItemSoapIn" part="MailboxCulture" use="literal"/>
            <soap:header message="tns:CreateItemSoapIn" part="RequestVersion" use="literal"/>
            <soap:header message="tns:CreateItemSoapIn" part="TimeZoneContext" use="literal"/>
            <soap:body parts="request" use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body parts="CreateItemResult" use="literal"/>
            <soap:header message="tns:CreateItemSoapOut" part="ServerVersion" use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteItem">
        <soap:operation
            soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/DeleteItem"/>
        <wsdl:input>
            <soap:header message="tns>DeleteItemSoapIn" part="Impersonation" use="literal"/>
            <soap:header message="tns>DeleteItemSoapIn" part="MailboxCulture" use="literal"/>
            <soap:header message="tns>DeleteItemSoapIn" part="RequestVersion" use="literal"/>
            <soap:body parts="request" use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body parts="DeleteItemResult" use="literal"/>
            <soap:header message="tns>DeleteItemSoapOut" part="ServerVersion" use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateItem">
        <soap:operation
            soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/UpdateItem"/>
        <wsdl:input>
            <soap:header message="tns:UpdateItemSoapIn" part="Impersonation" use="literal"/>
            <soap:header message="tns:UpdateItemSoapIn" part="MailboxCulture" use="literal"/>
            <soap:header message="tns:UpdateItemSoapIn" part="RequestVersion" use="literal"/>
            <soap:header message="tns:UpdateItemSoapIn" part="TimeZoneContext" use="literal"/>
            <soap:body parts="request" use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body parts="UpdateItemResult" use="literal"/>
            <soap:header message="tns:UpdateItemSoapOut" part="ServerVersion" use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="MarkAllItemsAsRead">
        <soap:operation
            soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/MarkAllItemsAsRead"/>
        <wsdl:input>
            <soap:header message="tns:MarkAllItemsAsReadSoapIn" part="Impersonation" use="literal"/>
            <soap:header message="tns:MarkAllItemsAsReadSoapIn" part="MailboxCulture" use="literal"/>
            <soap:header message="tns:MarkAllItemsAsReadSoapIn" part="RequestVersion" use="literal"/>
            <soap:body parts="request" use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body parts="MarkAllItemsAsReadResult" use="literal"/>

```

```

<soap:header message="tns:MarkAllItemsAsReadSoapOut" part="ServerVersion"
use="literal"/>
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="MoveItem">
<soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/MoveItem"/>
<wsdl:input>
<soap:header message="tns:MoveItemSoapIn" part="Impersonation" use="literal"/>
<soap:header message="tns:MoveItemSoapIn" part="MailboxCulture" use="literal"/>
<soap:header message="tns:MoveItemSoapIn" part="RequestVersion" use="literal"/>
<soap:body parts="request" use="literal"/>
</wsdl:input>
<wsdl:output>
<soap:body parts="MoveItemResult" use="literal"/>
<soap:header message="tns:MoveItemSoapOut" part="ServerVersion" use="literal"/>
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="CopyItem">
<soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/CopyItem"/>
<wsdl:input>
<soap:header message="tns:CopyItemSoapIn" part="Impersonation" use="literal"/>
<soap:header message="tns:CopyItemSoapIn" part="MailboxCulture" use="literal"/>
<soap:header message="tns:CopyItemSoapIn" part="RequestVersion" use="literal"/>
<soap:body parts="request" use="literal"/>
</wsdl:input>
<wsdl:output>
<soap:body parts="CopyItemResult" use="literal"/>
<soap:header message="tns:CopyItemSoapOut" part="ServerVersion" use="literal"/>
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SendItem">
<soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/SendItem"/>
<wsdl:input>
<soap:header message="tns:SendItemSoapIn" part="Impersonation" use="literal"/>
<soap:header message="tns:SendItemSoapIn" part="MailboxCulture" use="literal"/>
<soap:header message="tns:SendItemSoapIn" part="RequestVersion" use="literal"/>
<soap:body parts="request" use="literal"/>
</wsdl:input>
<wsdl:output>
<soap:body parts="SendItemResult" use="literal"/>
<soap:header message="tns:SendItemSoapOut" part="ServerVersion" use="literal"/>
</wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:message name="GetItemSoapIn">
<wsdl:part name="request" element="tns:GetItem"/>
<wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
<wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
<wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
<wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
<wsdl:part name="DateTimePrecision" element="t:DateTimePrecision"/>
<wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
<wsdl:message name="GetItemSoapOut">
<wsdl:part name="GetItemResult" element="tns:GetItemResponse"/>
<wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>

```

```

    </wsdl:message>
<wsdl:message name="CreateItemSoapIn">
    <wsdl:part name="request" element="tns:CreateItem"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>
<wsdl:message name="CreateItemSoapOut">
    <wsdl:part name="CreateItemResult" element="tns:CreateItemResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="DeleteItemSoapIn">
    <wsdl:part name="request" element="tns:DeleteItem"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="DeleteItemSoapOut">
    <wsdl:part name="DeleteItemResult" element="tns:DeleteItemResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="UpdateItemSoapIn">
    <wsdl:part name="request" element="tns:UpdateItem"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>
<wsdl:message name="UpdateItemSoapOut">
    <wsdl:part name="UpdateItemResult" element="tns:UpdateItemResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="MarkAllItemsAsReadSoapIn">
    <wsdl:part name="request" element="tns:MarkAllItemsAsRead"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="MarkAllItemsAsReadSoapOut">
    <wsdl:part name="MarkAllItemsAsReadResult" element="tns:MarkAllItemsAsReadResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="MoveItemSoapIn">
    <wsdl:part name="request" element="tns:MoveItem"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="MoveItemSoapOut">
    <wsdl:part name="MoveItemResult" element="tns:MoveItemResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="CopyItemSoapIn">
    <wsdl:part name="request" element="tns:CopyItem"/>
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>

```

```
<wsdl:message name="CopyItemSoapOut">
  <wsdl:part name="CopyItemResult" element="tns:CopyItemResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="SendItemSoapIn">
  <wsdl:part name="request" element="tns:SendItem"/>
  <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
  <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="SendItemSoapOut">
  <wsdl:part name="SendItemResult" element="tns:SendItemResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
</wsdl:definitions>
```

7 Appendix B: Full XML Schema

For ease of implementation, the following sections provide the full XML schema for this protocol.

Schema name	Prefix	Section
Messages schema	m:	7.1
Types schema	t:	7.2

These files have to be placed in a common folder in order for the WSDL to validate and operate. Also, any schema files that are included in or imported into the MS-OXWSNTIF-types.xsd or MS-OXWSNTIF-messages.xsd schemas have to be placed in the common folder along with the files listed in the table.

7.1 Messages Schema

Note Some of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure. For information about specific differences between versions, see the behavior notes that are provided in the Product Behavior appendix.

This section provides the contents of the MS-OXWSCORE-messages.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSCORE-messages.xsd includes the files listed in the following table. To operate correctly, these files have to be present in the folder that contains the WSDL, types schema, and messages schema files for this protocol.

File name	Defining specification
MS-OXWSCDATA-messages.xsd	[MS-OXWSCDATA] section 7.1
MS-OXWSCDATA-types.xsd	[MS-OXWSCDATA] section 7.2
MS-OXWSMSG-types.xsd	[MS-OXWSMSG] section 7.1

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
  elementFormDefault="qualified" version="Exchange2010_SP2" id="messages">
  <!-- Import common types. -->
  <xs:import namespace="http://schemas.microsoft.com/exchange/services/2006/types"
    schemaLocation="MS-OXWSCDATA-types.xsd"/>
  <xs:import namespace="http://schemas.microsoft.com/exchange/services/2006/types"
    schemaLocation="MS-OXWSCORE-types.xsd"/>
  <xs:import namespace="http://schemas.microsoft.com/exchange/services/2006/types"
    schemaLocation="MS-OXWSMSG-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSCDATA-messages.xsd"/>
  <xs:complexType name="BaseMoveCopyItemType">
    <xs:complexContent>
      <xs:extension base="m:BaseRequestType">
        <xs:sequence>
          <xs:element name="ToFolderId" type="t:TargetFolderIdType"/>
```

```

<xs:element name="ItemIds" type="t:NonEmptyArrayOfBaseItemIdsType"/>
<xs:element name="ReturnNewItemIds" type="xs:boolean" minOccurs="0"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="CopyItem" type="m:CopyItemType"/>
<xs:complexType name="CopyItemType">
<xs:complexContent>
<xs:extension base="m:BaseMoveCopyItemType"/>
</xs:complexContent>
</xs:complexType>
<xs:element name="CopyItemResponse" type="m:CopyItemResponseType"/>
<xs:complexType name="CopyItemResponseType">
<xs:complexContent>
<xs:extension base="m:BaseResponseMessageType"/>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="CreateItemResponseType">
<xs:complexContent>
<xs:extension base="m:BaseResponseMessageType"/>
</xs:complexContent>
</xs:complexType>
<xs:element name="CreateItemResponse" type="m:CreateItemResponseType"/>
<xs:complexType name="CreateItemType">
<xs:complexContent>
<xs:extension base="m:BaseRequestType">
<xs:sequence>
<xs:element name="SavedItemFolderId" type="t:TargetFolderIdType" minOccurs="0"/>
<xs:element name="Items" type="t:NonEmptyArrayOfAllItemsType"/>
</xs:sequence>
<xs:attribute name="MessageDisposition" type="t:MessageDispositionType"
use="optional"/>
<xs:attribute name="SendMeetingInvitations"
type="t:CalendarItemCreateOrDeleteOperationType" use="optional"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="CreateItem" type="m:CreateItemType"/>
<xs:complexType name="DeleteItemType">
<xs:complexContent>
<xs:extension base="m:BaseRequestType">
<xs:sequence>
<xs:element name="ItemIds" type="t:NonEmptyArrayOfBaseItemIdsType"/>
</xs:sequence>
<xs:attribute name="DeleteType" type="t:DisposalType" use="required"/>
<xs:attribute name="SendMeetingCancellations"
type="t:CalendarItemCreateOrDeleteOperationType" use="optional"/>
<xs:attribute name="AffectedTaskOccurrences" type="t:AffectedTaskOccurrencesType"
use="optional"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="DeleteItem" type="m:DeleteItemType"/>
<xs:complexType name="DeleteItemResponseType">
<xs:complexContent>
<xs:extension base="m:BaseResponseMessageType"/>
</xs:complexContent>
</xs:complexType>

```

```

<xs:element name="DeleteItemResponse" type="m:DeleteItemType" />
<xs:complexType name="GetItemType">
  <xs:complexContent>
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element name="ItemShape" type="t:ItemResponseShapeType" />
        <xs:element name="ItemIds" type="t:NonEmptyArrayOfBaseItemIdsType" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="GetItem" type="m:ItemType" />
<xs:complexType name="GetItemResponseType">
  <xs:complexContent>
    <xs:extension base="m:BaseResponseMessageType" />
  </xs:complexContent>
</xs:complexType>
<xs:element name="GetItemResponse" type="m:ItemType" />
<xs:complexType name="MarkAllItemsAsReadType">
  <xs:complexContent>
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>
        <xs:element name="ReadFlag" type="xs:boolean" minOccurs="1" maxOccurs="1" />
        <xs:element name="SuppressReadReceipts" type="xs:boolean" minOccurs="1" maxOccurs="1" />
        <xs:element name="FolderIds" type="t:NonEmptyArrayOfBaseFolderIdsType" />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="MarkAllItemsAsRead" type="m:MarkAllItemsAsReadType" />
<xs:complexType name="MarkAllItemsAsReadResponseType">
  <xs:complexContent>
    <xs:extension base="m:BaseResponseMessageType" />
  </xs:complexContent>
</xs:complexType>
<xs:element name="MarkAllItemsAsReadResponse" type="m:MarkAllItemsAsReadResponseType" />
<xs:complexType name="MoveItemResponseType">
  <xs:complexContent>
    <xs:extension base="m:BaseResponseMessageType" />
  </xs:complexContent>
</xs:complexType>
<xs:element name="MoveItemResponse" type="m:MoveItemType" />
<xs:complexType name="MoveItemType">
  <xs:complexContent>
    <xs:extension base="m:BaseMoveCopyItemType" />
  </xs:complexContent>
</xs:complexType>
<xs:element name="MoveItem" type="m:MoveItemType" />
<xs:complexType name="SendItemResponseType">
  <xs:complexContent>
    <xs:extension base="m:BaseResponseMessageType" />
  </xs:complexContent>
</xs:complexType>
<xs:element name="SendItemResponse" type="m:SendItemType" />
<xs:complexType name="SendItemType">
  <xs:complexContent>
    <xs:extension base="m:BaseRequestType">
      <xs:sequence>

```

```

<xs:element name="ItemIds" type="t:NonEmptyArrayOfBaseItemIdsType"/>
<xs:element name="SavedItemId" type="t:TargetFolderIdType" minOccurs="0"/>
</xs:sequence>
<xs:attribute name="SaveItemToFolder" type="xs:boolean" use="required"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="SendItem" type="m:SendItemType"/>
<xs:complexType name="UpdateItemResponseType">
<xs:complexContent>
<xs:extension base="m:BaseResponseMessageType"/>
</xs:complexContent>
</xs:complexType>
<xs:element name="UpdateItemResponse" type="m:UpdateItemResponseType"/>
<xs:complexType name="UpdateItemType">
<xs:complexContent>
<xs:extension base="m:BaseRequestType">
<xs:sequence>
<xs:element name="SavedItemId" type="t:TargetFolderIdType" minOccurs="0"/>
<xs:element name="ItemChanges" type="t:NonEmptyArrayOfItemChangesType"/>
</xs:sequence>
<xs:attribute name="ConflictResolution" type="t:ConflictResolutionType"
use="required"/>
<xs:attribute name="MessageDisposition" type="t:MessageDispositionType"
use="optional"/>
<xs:attribute name="SendMeetingInvitationsOrCancellations"
type="t:CalendarItemUpdateOperationType" use="optional"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="UpdateItem" type="m:UpdateItemType"/>
<xs:complexType name="UpdateItemResponseMessageType">
<xs:complexContent>
<xs:extension base="m:ItemInfoResponseMessageType">
<xs:sequence>
<xs:element name="ConflictResults" type="t:ConflictResultsType" minOccurs="0"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
</xs:complexType>
</xs:schema>

```

7.2 Types Schema

Note Some of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure. For information about specific differences between versions, see the behavior notes that are provided in the Product Behavior appendix.

This section provides the contents of the MS-OXWScore-types.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWScore-types.xsd includes the following file. To operate correctly, this file has to be included in the folder that contains the WSDL, types, and messages schema files for this protocol.

File name	Defining specification
MS-OXWSCDATA-types.xsd	[MS-OXWSCDATA] section 7.2

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
elementFormDefault="qualified" version="Exchange2010_SP2" id="types">
    <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
    <xs:include schemaLocation="MS-OXWSCDATA-types.xsd"/>
    <xs:complexType name="AppendToItemFieldType">
        <xs:complexContent>
            <xs:extension base="t:ItemChangeDescriptionType">
                <xs:choice>
                    <xs:element name="Item" type="t:ItemType"/>
                    <xs:element name="Message" type="t:MessageType"/>
                    <xs:element name="CalendarItem" type="t:CalendarItemType"/>
                    <xs:element name="Contact" type="t>ContactItemType"/>
                    <xs:element name="DistributionList" type="t:DistributionListType"/>
                    <xs:element name="MeetingMessage" type="t:MeetingMessageType"/>
                    <xs:element name="MeetingRequest" type="t:MeetingRequestMessageType"/>
                    <xs:element name="MeetingResponse" type="t:MeetingResponseMessageType"/>
                    <xs:element name="MeetingCancellation" type="t:MeetingCancellationMessageType"/>
                    <xs:element name="Task" type="t:TaskType"/>
                    <xs:element name="PostItem" type="t:PostItemType"/>
                </xs:choice>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="BaseItemId" type="t:BaseItemIdType"/>
    <xs:complexType name="ChangeDescriptionType" abstract="true">
        <xs:sequence>
            <xs:element ref="t:Path"/>
        </xs:sequence>
    </xs:complexType>
    <xs:simpleType name="ConflictResolutionType">
        <xs:restriction base="xs:string">
            <xs:enumeration value="NeverOverwrite"/>
            <xs:enumeration value="AutoResolve"/>
            <xs:enumeration value="AlwaysOverwrite"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:complexType name="ConflictResultsType">
        <xs:sequence>
            <xs:element name="Count" type="xs:int"/>
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="DeleteItemFieldType">
        <xs:complexContent>
            <xs:extension base="t:ItemChangeDescriptionType">
                <xs:sequence/>
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
    <xs:simpleType name="DerivedItemIdType">
        <xs:restriction base="xs:string"/>
    </xs:simpleType>
    <xs:simpleType name="ImportanceChoicesType">
        <xs:restriction base="xs:string">
            <xs:enumeration value="Low"/>
            <xs:enumeration value="Normal"/>

```

```

        <xs:enumeration value="High"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="ItemChangeDescriptionType">
    <xs:complexContent>
        <xs:extension base="t:ChangeDescriptionType"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ItemChangeType">
    <xs:sequence>
        <xs:choice>
            <xs:element name="ItemId" type="t:ItemIdType"/>
            <xs:element name="OccurrenceItemId" type="t:OccurrenceItemIdType"/>
            <xs:element name="RecurringMasterItemId" type="t:RecurringMasterItemIdType"/>
        </xs:choice>
        <xs:element name="Updates" type="t:NonEmptyArrayOfItemChangeDescriptionsType"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="ItemClassType">
    <xs:restriction base="xs:string"/>
</xs:simpleType>
<xs:complexType name="ItemIdType">
    <xs:annotation>
        <xs:documentation>Identifier for a fully resolved item</xs:documentation>
    </xs:annotation>
    <xs:complexContent>
        <xs:extension base="t:BaseItemIdType">
            <xs:attribute name="Id" type="xs:string" use="required"/>
            <xs:attribute name="ChangeKey" type="xs:string" use="optional"/>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ItemType">
    <xs:sequence>
        <xs:element name="MimeType" type="t:MimeType" minOccurs="0"/>
        <xs:element name="ItemId" type="t:ItemIdType" minOccurs="0"/>
        <xs:element name="ParentFolderId" type="t:FolderIdType" minOccurs="0"/>
        <xs:element name="ItemClass" type="t:ItemClassType" minOccurs="0"/>
        <xs:element name="Subject" type="xs:string" minOccurs="0"/>
        <xs:element name="Sensitivity" type="t:SensitivityChoicesType" minOccurs="0"/>
        <xs:element name="Body" type="t:BodyType" minOccurs="0"/>
        <xs:element name="Attachments" type="t:NonEmptyArrayOfAttachmentsType" minOccurs="0"/>
        <xs:element name="DateTimeReceived" type="xs:dateTime" minOccurs="0"/>
        <xs:element name="Size" type="xs:int" minOccurs="0"/>
        <xs:element name="Categories" type="t:ArrayOfStringsType" minOccurs="0"/>
        <xs:element name="Importance" type="t:ImportanceChoicesType" minOccurs="0"/>
        <xs:element name="InReplyTo" type="xs:string" minOccurs="0"/>
        <xs:element name="IsSubmitted" type="xs:boolean" minOccurs="0"/>
        <xs:element name="IsDraft" type="xs:boolean" minOccurs="0"/>
        <xs:element name="IsFromMe" type="xs:boolean" minOccurs="0"/>
        <xs:element name="IsResend" type="xs:boolean" minOccurs="0"/>
        <xs:element name="IsUnmodified" type="xs:boolean" minOccurs="0"/>
        <xs:element name="InternetMessageHeaders" type="t:NonEmptyArrayOfInternetHeadersType"
minOccurs="0"/>
        <xs:element name="DateTimeSent" type="xs:dateTime" minOccurs="0"/>
        <xs:element name="DateTimeCreated" type="xs:dateTime" minOccurs="0"/>
        <xs:element name="ResponseObjects" type="t:NonEmptyArrayOfResponseObjectsType"
minOccurs="0"/>
        <xs:element name="ReminderDueBy" type="xs:dateTime" minOccurs="0"/>
    </xs:sequence>

```

```

<xs:element name="ReminderIsSet" type="xs:boolean" minOccurs="0"/>
<xs:element name="ReminderMinutesBeforeStart" type="t:ReminderMinutesBeforeStartType"
minOccurs="0"/>
<xs:element name="DisplayCc" type="xs:string" minOccurs="0"/>
<xs:element name="DisplayTo" type="xs:string" minOccurs="0"/>
<xs:element name="HasAttachments" type="xs:boolean" minOccurs="0"/>
<xs:element name="ExtendedProperty" type="t:ExtendedPropertyType" minOccurs="0"
maxOccurs="unbounded"/>
<xs:element name="Culture" type="xs:language" minOccurs="0"/>
<xs:element name="EffectiveRights" type="t:EffectiveRightsType" minOccurs="0"/>
<xs:element name="LastModifiedName" type="xs:string" minOccurs="0"/>
<xs:element name="LastModifiedTime" type="xs:dateTime" minOccurs="0"/>
<xs:element name="IsAssociated" type="xs:boolean" minOccurs="0"/>
<xs:element name="WebClientReadFormQueryString" type="xs:string" minOccurs="0"/>
<xs:element name="WebClientEditFormQueryString" type="xs:string" minOccurs="0"/>
<xs:element name="ConversationId" type="t:ItemIdType" minOccurs="0"/>
<xs:element name="UniqueBody" type="t:BodyType" minOccurs="0"/>
<xs:element name="StoreEntryId" type="xs:base64Binary" minOccurs="0"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="MimeTypeContent">
<xs:simpleContent>
<xs:extension base="xs:string">
<xs:attribute name="CharacterSet" type="xs:string" use="optional"/>
</xs:extension>
</xs:simpleContent>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfBaseItemIdsType">
<xs:choice maxOccurs="unbounded">
<xs:element name="ItemId" type="t:ItemIdType"/>
<xs:element name="OccurrenceItemId" type="t:OccurrenceItemIdType"/>
<xs:element name="RecurringMasterItemId" type="t:RecurringMasterItemIdType"/>
</xs:choice>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfInternetHeadersType">
<xs:sequence>
<xs:element name="InternetMessageHeader" type="t:InternetHeaderType"
maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfItemChangeDescriptionsType">
<xs:choice maxOccurs="unbounded">
<xs:element name="AppendToItemField" type="t:AppendToItemFieldType"/>
<xs:element name="SetItemField" type="t:SetItemFieldType"/>
<xs:element name="DeleteItemField" type="t:DeleteItemFieldType"/>
</xs:choice>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfItemChangesType">
<xs:sequence>
<xs:element name="ItemChange" type="t:ItemChangeType" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfResponseObjectsType">
<xs:choice minOccurs="0" maxOccurs="unbounded">
<xs:element name="AcceptItem" type="t:AcceptItemType"/>
<xs:element name="TentativelyAcceptItem" type="t:TentativelyAcceptItemType"/>
<xs:element name="DeclineItem" type="t:DeclineItemType"/>
<xs:element name="ReplyToItem" type="t:ReplyToItemType"/>
<xs:element name="ForwardItem" type="t:ForwardItemType"/>

```

```

<xs:element name="ReplyAllToItem" type="t:ReplyAllToItemType"/>
<xs:element name="CancelCalendarItem" type="t:CancelCalendarItemType"/>
<xs:element name="RemoveItem" type="t:RemoveItemType"/>
<xs:element name="SuppressReadReceipt" type="t:SuppressReadReceiptType"/>
<xs:element name="PostReplyItem" type="t:PostReplyItemType"/>
<xs:element name="AcceptSharingInvitation" type="t:AcceptSharingInvitationType"/>
</xs:choice>
</xs:complexType>
<xs:complexType name="OccurrenceItemIdType">
<xs:complexContent>
<xs:extension base="t:BaseItemIdType">
<xs:attribute name="RecurringMasterId" type="t:DerivedItemIdType" use="required"/>
<xs:attribute name="ChangeKey" type="xs:string" use="optional"/>
<xs:attribute name="InstanceIndex" type="xs:int" use="required"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="RecurringMasterItemIdType">
<xs:complexContent>
<xs:extension base="t:BaseItemIdType">
<xs:attribute name="OccurrenceId" type="t:DerivedItemIdType" use="required"/>
<xs:attribute name="ChangeKey" type="xs:string" use="optional"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="ReferenceItemResponseType">
<xs:complexContent>
<xs:restriction base="t:ResponseObjectType">
<xs:sequence>
<xs:element name="ReferenceItemId" type="t:ItemIdType" minOccurs="0"/>
</xs:sequence>
<xs:attribute name="ObjectName" type="xs:string" use="prohibited"/>
</xs:restriction>
</xs:complexContent>
</xs:complexType>
<xs:simpleType name="ReminderMinutesBeforeStartType">
<xs:union>
<xs:simpleType id="ReminderMinutesBeforeStartType">
<xs:restriction base="xs:int">
<xs:minInclusive value="0"/>
<xs:maxInclusive value="2629800"/>
</xs:restriction>
</xs:simpleType>
<xs:simpleType id="ReminderMinutesBeforeStartMarkerType">
<xs:restriction base="xs:int">
<xs:minInclusive value="1525252321"/>
<xs:maxInclusive value="1525252321"/>
</xs:restriction>
</xs:simpleType>
</xs:union>
</xs:simpleType>
<xs:complexType name="SetItemFieldType">
<xs:complexContent>
<xs:extension base="t:ItemChangeDescriptionType">
<xs:choice>
<xs:element name="Item" type="t:ItemType"/>
<xs:element name="Message" type="t:MessageType"/>
<xs:element name="CalendarItem" type="t:CalendarItemType"/>
<xs:element name="Contact" type="t:ContactItemType"/>

```

```

<xs:element name="DistributionList" type="t:DistributionListType"/>
<xs:element name="MeetingMessage" type="t:MeetingMessageType"/>
<xs:element name="MeetingRequest" type="t:MeetingRequestMessageType"/>
<xs:element name="MeetingResponse" type="t:MeetingResponseMessageType"/>
<xs:element name="MeetingCancellation" type="t:MeetingCancellationMessageType"/>
<xs:element name="Task" type="t:TaskType"/>
<xs:element name="PostItem" type="t:PostItemType"/>
</xs:choice>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="SmartResponseBaseType">
<xs:complexContent>
<xs:restriction base="t:ResponseObjectType">
<xs:sequence>
<xs:element name="Subject" type="xs:string" minOccurs="0"/>
<xs:element name="Body" type="t:BodyType" minOccurs="0"/>
<xs:element name="ToRecipients" type="t:ArrayOfRecipientsType" minOccurs="0"/>
<xs:element name="CcRecipients" type="t:ArrayOfRecipientsType" minOccurs="0"/>
<xs:element name="BccRecipients" type="t:ArrayOfRecipientsType" minOccurs="0"/>
<xs:element name="IsReadReceiptRequested" type="xs:boolean" minOccurs="0"/>
<xs:element name="IsDeliveryReceiptRequested" type="xs:boolean" minOccurs="0"/>
<xs:element name="From" type="t:SingleRecipientType" minOccurs="0"/>
<xs:element name="ReferenceItemId" type="t:ItemIdType" minOccurs="0"/>
</xs:sequence>
<xs:attribute name="ObjectName" type="xs:string" use="prohibited"/>
</xs:restriction>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="SmartResponseType">
<xs:complexContent>
<xs:extension base="t:SmartResponseBaseType">
<xs:sequence>
<xs:element name="NewBodyContent" type="t:BodyType" minOccurs="0"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

<xs:complexType name="NonEmptyArrayOfRoleType">
<xs:sequence>
<xs:element name="Role" type="xs:string" maxOccurs="unbounded"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="ManagementRoleType">
<xs:sequence>
<xs:element name="UserRoles" type="t:NonEmptyArrayOfRoleType" minOccurs="0"
maxOccurs="1"/>
<xs:element name="ApplicationRoles" type="t:NonEmptyArrayOfRoleType" minOccurs="0"
maxOccurs="1"/>

```

```
</xs:sequence>  
</xs:complexType>  
  
<xs:element name="ManagementRole" type="t:ManagementRoleType"/>  
</xs:schema>
```

Preliminary

8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010
- Microsoft® Exchange Server 15 Technical Preview

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2.3.2:](#) Exchange 2007 and Exchange 2010 do not support the **ManagementRole** element.

[<2> Section 2.2.4.1:](#) Exchange 2007, Exchange 2010, and Exchange 2010 SP1 do not include the **ReturnNewItemIds** element. The **ReturnNewItemIds** element was introduced in Exchange 2010 SP2.

[<3> Section 2.2.4.6:](#) Exchange 2007, Exchange 2010 and Exchange 2010 SP1 do not support the **StoreEntryId** element. The **StoreEntryId** element was introduced in Exchange 2010 SP2.

[<4> Section 2.2.4.7:](#) Exchange 2007 and Exchange 2010 do not support the **ManagementRoleType** complex type.

[<5> Section 2.2.4.12:](#) Exchange 2007 and Exchange 2010 do not support the **NonEmptyArrayOfRoleType** complex type.

[<6> Section 3.1.4.4.1.1:](#) Exchange 2007, Exchange 2010 and Exchange 2010 SP1 do not support the **DateTimePrecision** SOAP header. The **DateTimePrecision** SOAP header was introduced in Exchange 2010 SP2.

[<7> Section 3.1.4.4.1.1:](#) Exchange 2007 and Exchange 2010 do not support the **ManagementRole** SOAP header. The **ManagementRole** SOAP header was introduced in ex15.

[<8> Section 3.1.4.5:](#) Exchange 2007 and Exchange 2010 do not support the **MarkAllItemsAsRead** operation.

9 Change Tracking

This section identifies changes that were made to the [MS-OXWSOCE] protocol document between the October 2011 and January 2012 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.2.3 Elements	Added the ManagementRole element to the table.	Y	Content updated due to protocol revision.
2.2.3.2 t:ManagementRole Element	Added section.	Y	New content added due to protocol revision.
2.2.4 Complex Types	Added the ManagementRoleType and NonEmptyArrayOfRoleType complex types to the table.	Y	Content updated due to protocol revision.
2.2.4.7 t:ManagementRoleType Complex Type	Added section.	Y	New content added due to protocol revision.
2.2.4.12 t:NonEmptyArrayOfRoleType Complex Type	Added section.	Y	New content added due to protocol revision.
3.1.4 Message Processing Events and Sequencing Rules	Added the MarkAllItemsAsRead operation to the table.	Y	Content updated due to protocol revision.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<u>3.1.4.4 GetItem Operation</u>	Added the ManagementRole header to the WSDL binding syntax.	Y	Content updated due to protocol revision.
<u>3.1.4.4.1.1 tns:.GetItemSoapIn Message</u>	Added the ManagementRole header to the GetItemSoapIn message.	Y	Content updated due to protocol revision.
<u>3.1.4.5 MarkAllItemsAsRead Operation</u>	Added section.	Y	New content added due to protocol revision.
<u>3.1.4.5.1 Messages</u>	Added section.	Y	New content added due to protocol revision.
<u>3.1.4.5.1.1 tns:MarkAllItemsAsReadSoapIn Message</u>	Added section.	Y	New content added due to protocol revision.
<u>3.1.4.5.1.2 tns:MarkAllItemsAsReadSoapOut Message</u>	Added section.	Y	New content added due to protocol revision.
<u>3.1.4.5.2 Elements</u>	Added section.	Y	New content added due to protocol revision.
<u>3.1.4.5.2.1 MarkAllItemsAsRead Element</u>	Added section.	Y	New content added due to protocol revision.
<u>3.1.4.5.2.2 MarkAllItemsAsReadResponse Element</u>	Added section.	Y	New content added due to protocol revision.
<u>3.1.4.5.3 Complex Types</u>	Added section.	Y	New content added due to protocol revision.
<u>3.1.4.5.3.1 tns:MarkAllItemsAsReadType Complex Type</u>	Added section.	Y	New content added due to protocol revision.
<u>3.1.4.5.3.2</u>	Added section.	Y	New content

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
m:MarkAllItemsAsReadResponseType Complex Type			added due to protocol revision.
6 Appendix A: Full WSDL	Updated contents of the WSDL file.	Y	Content updated due to protocol revision.
7.1 Messages Schema	Updated the contents of the XML file.	Y	Content updated due to protocol revision.
7.2 Types Schema	Updated the contents of the XML file.	Y	Content updated due to protocol revision.
8 Appendix C: Product Behavior	Added Exchange 15 Technical Preview to the list of applicable product versions.	Y	Content updated.

10 Index

A

Abstract data model
[server](#) 35
[Applicability](#) 10
[Attribute groups](#) 34
[Attributes](#) 33

C

[Capability negotiation](#) 10
[Change tracking](#) 93
[Complex types](#) 12
[m:BaseMoveCopyItemType Complex Type](#) 13
[m:SendItemResponseType Complex Type](#) 14
[m:SendItemType Complex Type](#) 14
[m:UpdateItemResponseMessageType Complex Type](#) 15
[t:ConflictResultsType Complex Type](#) 16
[t:ItemIdType Complex Type](#) 28
[t:ItemType Complex Type](#) 16
[t:ManagementRoleType Complex Type](#) 22
[t:MimeContentType Complex Type](#) 23
[t:NonEmptyArrayOfBaseItemIdsType Complex Type](#) 23
[t:NonEmptyArrayOfInternetHeadersType Complex Type](#) 24
[t:NonEmptyArrayOfResponseObjectsType Complex Type](#) 24
[t:NonEmptyArrayOfRoleType Complex Type](#) 26
[t:OccurrenceItemIdType Complex Type](#) 26
[t:RecurringMasterItemIdType Complex Type](#) 27
[t:ReferenceItemResponseType Complex Type](#) 28
[t:SmartResponseBaseType Complex Type](#) 29
[t:SmartResponseType Complex Type](#) 31

D

Data model - abstract
[server](#) 35

E

Elements
[t:BaseItemId Element](#) 12
[t:ManagementRole Element](#) 12
Events
[local - server](#) 73
[timer - server](#) 73

F

[Fields - vendor-extensible](#) 10
[Full WSDL](#) 76

G

[Glossary](#) 7

[Groups](#) 34

I

[Implementer - security considerations](#) 75
[Index of security parameters](#) 75
[Informative references](#) 8
Initialization
[server](#) 35
[Introduction](#) 7

L

Local events
[server](#) 73

M

[m:BaseMoveCopyItemType Complex Type complex type](#) 13
[m:SendItemResponseType Complex Type complex type](#) 14
[m:SendItemType Complex Type complex type](#) 14
[m:UpdateItemResponseMessageType Complex Type complex type](#) 15
Message processing
[server](#) 35
Messages
[attribute groups](#) 34
[attributes](#) 33
[complex types](#) 12
[elements](#) 11
[enumerated](#) 11
[groups](#) 34
[m:BaseMoveCopyItemType Complex Type complex type](#) 13
[m:SendItemResponseType Complex Type complex type](#) 14
[m:SendItemType Complex Type complex type](#) 14
[m:UpdateItemResponseMessageType Complex Type complex type](#) 15
[namespaces](#) 11
[simple types](#) 31
[syntax](#) 11
[t:BaseItemId Element element](#) 12
[t:ConflictResultsType Complex Type complex type](#) 16
[t:DerivedItemIdType Simple Type simple type](#) 32
[t:ImportanceChoicesType Simple Type simple type](#) 32
[t:ItemClassType Simple Type simple type](#) 33
[t:ItemIdType Complex Type complex type](#) 28
[t:ItemType Complex Type complex type](#) 16
[t:ManagementRole Element element](#) 12
[t:ManagementRoleType Complex Type complex type](#) 22
[t:MimeContentType Complex Type complex type](#) 23

[t:NonEmptyArrayOfBaseItemIdsType Complex Type](#) complex type 23
[t:NonEmptyArrayOfInternetHeadersType Complex Type](#) complex type 24
[t:NonEmptyArrayOfResponseObjectsType Complex Type](#) complex type 24
[t:NonEmptyArrayOfRoleType Complex Type complex type](#) 26
[t:OccurrenceItemIdType Complex Type complex type](#) 26
[t:RecurringMasterItemIdType Complex Type complex type](#) 27
[t:ReferenceItemResponseType Complex Type complex type](#) 28
[t:ReminderMinutesBeforeStartType Simple Type simple type](#) 33
[t:SmartResponseBaseType Complex Type complex type](#) 29
[t:SmartResponseType Complex Type complex type](#) 31
[transport](#) 11

N

[Namespaces](#) 11
[Normative references](#) 8

O

Operations

- [CopyItem Operation](#) 35
- [CreateItem Operation](#) 39
- [DeleteItem Operation](#) 43
- [GetItem Operation](#) 47
- [MarkAllItemsAsRead Operation](#) 51
- [MoveItem Operation](#) 55
- [SendItem Operation](#) 58
- [UpdateItem Operation](#) 61
- [Overview \(synopsis\)](#) 9

P

[Parameters - security index](#) 75
[Product behavior](#) 92

R

[References](#) 7

- informative 8
- normative 8

[Relationship to other protocols](#) 9

S

Security

- [implementer considerations](#) 75
- [parameter index](#) 75

Sequencing rules

- [server](#) 35

Server

- [abstract data model](#) 35
- [CopyItem Operation operation](#) 35

[CreateItem Operation operation](#) 39
[DeleteItem Operation operation](#) 43
[GetItem Operation operation](#) 47
[initialization](#) 35
[local events](#) 73
[MarkAllItemsAsRead Operation operation](#) 51
[message processing](#) 35
[MoveItem Operation operation](#) 55
[SendItem Operation operation](#) 58
[sequencing rules](#) 35
[timer events](#) 73
[timers](#) 35
[UpdateItem Operation operation](#) 61
[Simple types](#) 31

[t:DerivedItemIdType Simple Type](#) 32
[t:ImportanceChoicesType Simple Type](#) 32
[t:ItemClassType Simple Type](#) 33
[t:ReminderMinutesBeforeStartType Simple Type](#) 33

T

[t:BaseItemId Element element](#) 12
[t:ConflictResultsType Complex Type complex type](#) 16
[t:DerivedItemIdType Simple Type simple type](#) 32
[t:ImportanceChoicesType Simple Type simple type](#) 32
[t:ItemClassType Simple Type simple type](#) 33
[t:ItemIdType Complex Type complex type](#) 28
[t:ItemType Complex Type complex type](#) 16
[t:ManagementRole Element element](#) 12
[t:ManagementRoleType Complex Type complex type](#) 22
[t:MimeType Complex Type complex type](#) 23
[t:NonEmptyArrayOfBaseItemIdsType Complex Type complex type](#) 23
[t:NonEmptyArrayOfInternetHeadersType Complex Type complex type](#) 24
[t:NonEmptyArrayOfResponseObjectsType Complex Type complex type](#) 24
[t:NonEmptyArrayOfRoleType Complex Type complex type](#) 26
[t:OccurrenceItemIdType Complex Type complex type](#) 26
[t:RecurringMasterItemIdType Complex Type complex type](#) 27
[t:ReferenceItemResponseType Complex Type complex type](#) 28
[t:ReminderMinutesBeforeStartType Simple Type simple type](#) 33
[t:SmartResponseBaseType Complex Type complex type](#) 29
[t:SmartResponseType Complex Type complex type](#) 31
[Timer events server](#) 73
[Timers server](#) 35

[Tracking changes](#) 93

[Transport](#) 11

Types

[complex](#) 12

[simple](#) 31

V

[Vendor-extensible fields](#) 10

[Versioning](#) 10

W

[WSDL](#) 76