

[MS-OXWSEDISC]:

Electronic Discovery (eDiscovery) Web Service Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation ("this documentation") for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. For questions and support, please contact dochelp@microsoft.com.

Revision Summary

Date	Revision History	Revision Class	Comments
7/16/2012	0.1	New	Released new document.
10/8/2012	1.0	Major	Significantly changed the technical content.
2/11/2013	2.0	Major	Significantly changed the technical content.
7/26/2013	2.0	None	No changes to the meaning, language, or formatting of the technical content.
11/18/2013	2.0	None	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	2.0	None	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	2.1	Minor	Clarified the meaning of the technical content.
7/31/2014	2.2	Minor	Clarified the meaning of the technical content.
10/30/2014	2.3	Minor	Clarified the meaning of the technical content.
5/26/2015	3.0	Major	Significantly changed the technical content.
9/14/2015	4.0	Major	Significantly changed the technical content.
6/13/2016	5.0	Major	Significantly changed the technical content.
9/14/2016	5.0	None	No changes to the meaning, language, or formatting of the technical content.
7/24/2018	6.0	Major	Significantly changed the technical content.
10/1/2018	7.0	Major	Significantly changed the technical content.
5/17/2022	8.0	Major	Significantly changed the technical content.
5/20/2025	9.0	Major	Significantly changed the technical content.

Table of Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	7
1.2.1 Normative References	8
1.2.2 Informative References	8
1.3 Overview	9
1.4 Relationship to Other Protocols	9
1.5 Prerequisites/Preconditions	9
1.6 Applicability Statement	9
1.7 Versioning and Capability Negotiation	10
1.8 Vendor-Extensible Fields	10
1.9 Standards Assignments.....	10
2 Messages.....	11
2.1 Transport	11
2.2 Common Message Syntax	11
2.2.1 Namespaces	11
2.2.2 Messages.....	11
2.2.3 Elements	11
2.2.4 Complex Types.....	12
2.2.4.1 ArrayOfFailedSearchMailboxesType	12
2.2.4.2 ArrayOfMailboxHoldStatusType	12
2.2.4.3 ArrayOfSearchableMailboxesType.....	13
2.2.4.4 FailedSearchMailboxType	13
2.2.4.5 MailboxHoldResultType	13
2.2.4.6 MailboxHoldStatusType.....	14
2.2.4.7 SearchableMailboxType.....	14
2.2.5 Simple Types	15
2.2.5.1 HoldStatusType	15
2.2.6 Attributes	16
2.2.7 Groups	16
2.2.8 Attribute Groups.....	16
3 Protocol Details	17
3.1 ExchangeServicePortType Server Details.....	17
3.1.1 Abstract Data Model.....	17
3.1.2 Timers	17
3.1.3 Initialization.....	17
3.1.4 Message Processing Events and Sequencing Rules	17
3.1.4.1 GetDiscoverySearchConfiguration	18
3.1.4.1.1 Messages	18
3.1.4.1.1.1 GetDiscoverySearchConfigurationSoapIn	18
3.1.4.1.1.2 GetDiscoverySearchConfigurationSoapOut	19
3.1.4.1.2 Elements.....	20
3.1.4.1.2.1 GetDiscoverySearchConfiguration	20
3.1.4.1.2.2 GetDiscoverySearchConfigurationResponse	20
3.1.4.1.3 Complex Types	21
3.1.4.1.3.1 GetDiscoverySearchConfigurationType.....	21
3.1.4.1.3.2 GetDiscoverySearchConfigurationResponseMessageType	21
3.1.4.1.3.3 ArrayOfDiscoverySearchConfigurationType.....	22
3.1.4.1.3.4 DiscoverySearchConfigurationType	22
3.1.4.1.4 Simple Types	23
3.1.4.1.5 Attributes	23
3.1.4.1.6 Groups.....	23
3.1.4.1.7 Attribute Groups.....	23

3.1.4.2	GetHoldOnMailboxes	23
3.1.4.2.1	Messages	24
3.1.4.2.1.1	GetHoldOnMailboxesSoapIn	24
3.1.4.2.1.2	GetHoldOnMailboxesSoapOut	25
3.1.4.2.2	Elements	25
3.1.4.2.2.1	GetHoldOnMailboxes	25
3.1.4.2.2.2	GetHoldOnMailboxesResponse	26
3.1.4.2.3	Complex Types	26
3.1.4.2.3.1	GetHoldOnMailboxesType	26
3.1.4.2.3.2	GetHoldOnMailboxesResponseMessageType	26
3.1.4.2.4	Simple Types	27
3.1.4.2.5	Attributes	27
3.1.4.2.6	Groups	27
3.1.4.2.7	Attribute Groups	27
3.1.4.3	GetSearchableMailboxes	27
3.1.4.3.1	Messages	28
3.1.4.3.1.1	GetSearchableMailboxesSoapIn	28
3.1.4.3.1.2	GetSearchableMailboxesSoapOut	29
3.1.4.3.2	Elements	29
3.1.4.3.2.1	GetSearchableMailboxes	30
3.1.4.3.2.2	GetSearchableMailboxesResponse	30
3.1.4.3.3	Complex Types	30
3.1.4.3.3.1	GetSearchableMailboxesType	30
3.1.4.3.3.2	GetSearchableMailboxesResponseMessageType	31
3.1.4.3.4	Simple Types	31
3.1.4.3.5	Attributes	31
3.1.4.3.6	Groups	31
3.1.4.3.7	Attribute Groups	31
3.1.4.4	SearchMailboxes	32
3.1.4.4.1	Messages	32
3.1.4.4.1.1	SearchMailboxesSoapIn	32
3.1.4.4.1.2	SearchMailboxesSoapOut	33
3.1.4.4.2	Elements	34
3.1.4.4.2.1	SearchMailboxes	34
3.1.4.4.2.2	SearchMailboxesResponse	34
3.1.4.4.3	Complex Types	34
3.1.4.4.3.1	SearchMailboxesType	35
3.1.4.4.3.2	NonEmptyArrayOfMailboxQueriesType	36
3.1.4.4.3.3	MailboxQueryType	36
3.1.4.4.3.4	NonEmptyArrayOfMailboxSearchScopesType	37
3.1.4.4.3.5	MailboxSearchScopeType	37
3.1.4.4.3.6	PreviewItemResponseShapeType	37
3.1.4.4.3.7	NonEmptyArrayOfExtendedFieldURIsType	38
3.1.4.4.3.8	SearchMailboxesResponseType	38
3.1.4.4.3.9	SearchMailboxesResponseMessageType	38
3.1.4.4.3.10	SearchMailboxesResultType	39
3.1.4.4.3.11	ArrayOfKeywordStatisticsSearchResultsType	40
3.1.4.4.3.12	KeywordStatisticsSearchResultType	40
3.1.4.4.3.13	ArrayOfSearchPreviewItemsType	40
3.1.4.4.3.14	SearchPreviewItemType	41
3.1.4.4.3.15	PreviewItemMailboxType	42
3.1.4.4.3.16	ArrayOfSearchRefinerItemsType	43
3.1.4.4.3.17	SearchRefinerItemType	43
3.1.4.4.3.18	ArrayOfMailboxStatisticsItemsType	43
3.1.4.4.3.19	MailboxStatisticsItemType	44
3.1.4.4.3.20	ArrayOfExtendedAttributesType	44
3.1.4.4.3.21	ExtendedAttributeType	44
3.1.4.4.4	Simple Types	45

3.1.4.4.4.1	MailboxSearchLocationType.....	45
3.1.4.4.4.2	SearchResultType	45
3.1.4.4.4.3	PreviewItemBaseShapeType.....	46
3.1.4.4.4.4	SearchPageDirectionType.....	46
3.1.4.4.5	Attributes	46
3.1.4.4.6	Groups.....	47
3.1.4.4.7	Attribute Groups.....	47
3.1.4.5	SetHoldOnMailboxes.....	47
3.1.4.5.1	Messages	47
3.1.4.5.1.1	SetHoldOnMailboxesSoapIn.....	48
3.1.4.5.1.2	SetHoldOnMailboxesSoapOut.....	48
3.1.4.5.2	Elements.....	49
3.1.4.5.2.1	SetHoldOnMailboxes.....	49
3.1.4.5.2.2	SetHoldOnMailboxesResponse	49
3.1.4.5.3	Complex Types	49
3.1.4.5.3.1	SetHoldOnMailboxesType	50
3.1.4.5.3.2	SetHoldOnMailboxesResponseMessageType.....	51
3.1.4.5.4	Simple Types	51
3.1.4.5.4.1	HoldActionType.....	51
3.1.4.5.5	Attributes	52
3.1.4.5.6	Groups.....	52
3.1.4.5.7	Attribute Groups.....	52
3.1.5	Timer Events.....	52
3.1.6	Other Local Events.....	52
4	Protocol Examples.....	53
4.1	Setting Holds On Mailboxes	53
4.2	Getting Mailboxes With Holds	54
4.3	Getting Searchable Mailboxes	55
4.4	Searching Mailboxes	57
5	Security	59
5.1	Security Considerations for Implementers	59
5.2	Index of Security Parameters	59
6	Appendix A: Full WSDL	60
7	Appendix B: Full XML Schema.....	63
7.1	http://schemas.microsoft.com/exchange/services/2006/messages Schema	63
7.2	http://schemas.microsoft.com/exchange/services/2006/types Schema.....	65
8	Appendix C: Product Behavior	71
9	Change Tracking.....	72
10	Index.....	73

1 Introduction

The Electronic Discovery (eDiscovery) Web Service Protocol enables clients to use a **web service** to implement legal compliance holds, get user hold settings, and search for **mailboxes**.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

1.1 Glossary

This document uses the following terms:

display name: A text string that is used to identify a principal or other object in the user interface. Also referred to as title.

distinguished name (DN): In the Active Directory directory service, the unique identifier of an object in Active Directory, as described in [\[MS-ADTS\]](#) and [\[RFC2251\]](#).

distribution list: A collection of users, computers, contacts, or other groups that is used only for email distribution, and addressed as a single recipient.

electronic discovery (eDiscovery): A type of legal discovery that focuses on electronic (computer) communications and files.

email address: A string that identifies a user and enables the user to receive Internet messages.

endpoint: A communication port that is exposed by an application server for a specific shared service and to which messages can be addressed.

globally unique identifier (GUID): A term used interchangeably with universally unique identifier (UUID) in Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the value. Specifically, the use of this term does not imply or require that the algorithms described in [\[RFC4122\]](#) or [\[C706\]](#) have to be used for generating the GUID. See also universally unique identifier (UUID).

Hypertext Transfer Protocol (HTTP): An application-level protocol for distributed, collaborative, hypermedia information systems (text, graphic images, sound, video, and other multimedia files) on the World Wide Web.

Hypertext Transfer Protocol Secure (HTTPS): An extension of HTTP that securely encrypts and decrypts web page requests. In some older protocols, "Hypertext Transfer Protocol over Secure Sockets Layer" is still used (Secure Sockets Layer has been deprecated). For more information, see [\[SSL3\]](#) and [\[RFC5246\]](#).

mailbox: A message store that contains email, calendar items, and other Message objects for a single recipient.

recipient: An entity that can receive email messages.

Simple Mail Transfer Protocol (SMTP): A member of the TCP/IP suite of protocols that is used to transport Internet messages, as described in [\[RFC5321\]](#).

SOAP: A lightweight protocol for exchanging structured information in a decentralized, distributed environment. **SOAP** uses XML technologies to define an extensible messaging framework, which provides a message construct that can be exchanged over a variety of underlying protocols. The framework has been designed to be independent of any particular programming model and other implementation-specific semantics. SOAP 1.2 supersedes SOAP 1.1. See [\[SOAP1.2-1/2003\]](#).

SOAP action: The HTTP request header field used to indicate the intent of the **SOAP** request, using a URI value. See [\[SOAP1.1\]](#) section 6.1.1 for more information.

SOAP body: A container for the payload data being delivered by a SOAP message to its recipient. See [\[SOAP1.2-1/2007\]](#) section 5.3 for more information.

SOAP header: A mechanism for implementing extensions to a SOAP message in a decentralized manner without prior agreement between the communicating parties. See [\[SOAP1.2-1/2007\]](#) section 5.2 for more information.

Uniform Resource Locator (URL): A string of characters in a standardized format that identifies a document or resource on the World Wide Web. The format is as specified in [\[RFC1738\]](#).

web server: A server computer that hosts websites and responds to requests from applications.

web service: A unit of application logic that provides data and services to other applications and can be called by using standard Internet transport protocols such as **HTTP**, **Simple Mail Transfer Protocol (SMTP)**, or File Transfer Protocol (FTP). Web services can perform functions that range from simple requests to complicated business processes.

Web Services Description Language (WSDL): An XML format for describing network services as a set of endpoints that operate on messages that contain either document-oriented or procedure-oriented information. The operations and messages are described abstractly and are bound to a concrete network protocol and message format in order to define an endpoint. Related concrete endpoints are combined into abstract endpoints, which describe a network service. WSDL is extensible, which allows the description of endpoints and their messages regardless of the message formats or network protocols that are used.

WSDL message: An abstract, typed definition of the data that is communicated during a **WSDL operation** [\[WSDL\]](#). Also, an element that describes the data being exchanged between web service providers and clients.

WSDL operation: A single action or function of a web service. The execution of a WSDL operation typically requires the exchange of messages between the service requestor and the service provider.

WSDL port type: A named set of logically-related, abstract **Web Services Description Language (WSDL)** operations and messages.

XML namespace: A collection of names that is used to identify elements, types, and attributes in XML documents identified in a URI reference [\[RFC3986\]](#). A combination of XML namespace and local name allows XML documents to use elements, types, and attributes that have the same names but come from different sources. For more information, see [\[XMLNS-2ED\]](#).

XML namespace prefix: An abbreviated form of an **XML namespace**, as described in [\[XML\]](#).

XML schema: A description of a type of XML document that is typically expressed in terms of constraints on the structure and content of documents of that type, in addition to the basic syntax constraints that are imposed by XML itself. An XML schema provides a view of a document type at a relatively high level of abstraction.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

- [MS-OXWSCDATA] Microsoft Corporation, "[Common Web Service Data Types](#)".
- [MS-OXWSCORE] Microsoft Corporation, "[Core Items Web Service Protocol](#)".
- [MS-OXWSMSHR] Microsoft Corporation, "[Folder Sharing Web Service Protocol](#)".
- [MS-OXWSSRCH] Microsoft Corporation, "[Mailbox Search Web Service Protocol](#)".
- [MS-OXWSXPROP] Microsoft Corporation, "[Extended Properties Structure](#)".
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <https://www.rfc-editor.org/info/rfc2119>
- [RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <https://www.rfc-editor.org/info/rfc2616>
- [RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <https://www.rfc-editor.org/info/rfc2818>
- [SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", W3C Note, May 2000, <https://www.w3.org/TR/2000/NOTE-SOAP-20000508/>
- [WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <https://www.w3.org/TR/2001/NOTE-wsdl-20010315>
- [WSIBASIC] Ballinger, K., Ehnebuske, D., Gudgin, M., et al., Eds., "Basic Profile Version 1.0", Final Material, April 2004, <http://www.ws-i.org/Profiles/BasicProfile-1.0-2004-04-16.html>
- [XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <https://www.w3.org/TR/2009/REC-xml-names-20091208/>
- [XMLSCHEMA1/2] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures Second Edition", W3C Recommendation, October 2004, <https://www.w3.org/TR/2004/REC-xmlschema-1-20041028/>
- [XMLSCHEMA1] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <https://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>
- [XMLSCHEMA2/2] Biron, P., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes Second Edition", W3C Recommendation, October 2004, <https://www.w3.org/TR/2004/REC-xmlschema-2-20041028/>
- [XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <https://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

- [MS-OXDSCLI] Microsoft Corporation, "[Autodiscover Publishing and Lookup Protocol](#)".
- [MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".
- [MS-OXWSADISC] Microsoft Corporation, "[Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol](#)".

1.3 Overview

The eDiscovery Web Service Protocol is a federated query **web service** that enables external applications to query **mailbox** data.

Discovery consists of several phases, including identifying and preserving key data, reducing the amount of data, reviewing the data, and producing data in court. **Electronic discovery (eDiscovery)** queries facilitate the discovery process by providing a single discovery workflow.

1.4 Relationship to Other Protocols

A client that implements this protocol can use the Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol, as described in [\[MS-OXWSADISC\]](#), or the Autodiscover Publishing and Lookup Protocol, as described in [\[MS-OXDSCLI\]](#), to identify the target **endpoint** to use for each operation.

This protocol uses **SOAP**, as described in [\[SOAP1.1\]](#), to specify the structure information that is exchanged between the client and the server. This protocol uses the **XML schema**, as described in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), to describe the message content that is sent to and from the server.

This protocol uses SOAP over **HTTP**, as described in [\[RFC2616\]](#), and SOAP over **HTTPS**, as described in [\[RFC2818\]](#), as shown in the following layering diagram.




Figure 1: This protocol in relation to other protocols

The Nonindexable Item Web Service Protocol, as described in [\[MS-OXWSGNI\]](#), uses the mailbox search and mailbox hold information provided by this protocol.

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

1.5 Prerequisites/Preconditions

The operations that this protocol defines cannot be accessed unless the correct **endpoint** is identified in the **HTTP** web requests that target this protocol. This endpoint **URL** is returned by either the Autodiscover Publishing Lookup SOAP-Based Web Service Protocol, as specified in [\[MS-OXWSADISC\]](#), or the Autodiscover Publishing and Lookup Protocol, as specified in [\[MS-OXDSCLI\]](#).

1.6 Applicability Statement

This protocol is applicable to environments that use **web services** to implement electronic discovery from a user's **mailbox**. This protocol is applicable to all **SOAP**-based clients, as described in [\[SOAP1.1\]](#).

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Supported Transports:** This protocol uses SOAP 1.1, as specified in section [2.1](#).
- **Protocol Versions:** This protocol specifies only one **WSDL port type** version. The **RequestServerVersion** element, as described in [\[MS-OXWSCDATA\]](#) section 2.2.3.9, identifies the **Web Services Description Language (WSDL)** version of the request. The **ServerVersionInfo** element, as described in [\[MS-OXWSCDATA\]](#) section 2.2.3.10, identifies the version of the server responding to the request.
- **Security and Authentication Methods:** This protocol relies on the **web server** that is hosting it to perform authentication.
- **Localization:** This protocol includes date and time formats in various elements, as specified in section [3.1.4](#).
- **Capability Negotiation:** This protocol does not support version negotiation.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The **WSDL** in this specification provides a base description of the protocol. The schema in this specification provides a base description of the message syntax. The text that specifies the WSDL and schema might specify restrictions that reflect actual protocol behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the protocol as specified restricts the same elements to being non-empty, not null, or present.

2.1 Transport

This protocol uses the Simple Object Access Protocol (SOAP) 1.1, as specified in [\[SOAP1.1\]](#).

This protocol MUST support **SOAP** over **HTTP**, as specified in [\[RFC2616\]](#). The protocol SHOULD use secure communications by means of **HTTPS**, as defined in [\[RFC2818\]](#).

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and **WSDL**, as defined in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific **XML namespace prefix** for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
t	http://schemas.microsoft.com/exchange/services/2006/types	
tns	http://schemas.microsoft.com/exchange/services/2006/messages	
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
wsi	http://ws-i.org/schemas/conformanceClaim/	[WSIBASIC]
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1/2] [XMLSCHEMA2/2]

2.2.2 Messages

This specification does not define any common **WSDL message** definitions.

2.2.3 Elements

This specification does not define any common **XML schema** element definitions.

2.2.4 Complex Types

The following table summarizes the set of common **XML schema** complex type definitions defined by this specification. XML schema complex type definitions that are specific to a particular operation are described with the operation.

Complex type	Description
ArrayOfFailedSearchMailboxesType	The ArrayOfFailedSearchMailboxesType complex type specifies an array of failed searches.
ArrayOfMailboxHoldStatusType	The ArrayOfMailboxHoldStatusType complex type specifies an array of mailbox hold statuses.
ArrayOfSearchableMailboxesType	The ArrayOfSearchableMailboxesType complex type specifies an array of mailbox entities returned from the GetSearchableMailboxes operation.
FailedSearchMailboxType	The FailedSearchMailboxType complex type represents a failed search of a mailbox.
MailboxHoldResultType	The MailboxHoldResultType complex type specifies the result of a mailbox hold.
MailboxHoldStatusType	The MailboxHoldStatusType complex type specifies the status of a mailbox hold.
SearchableMailboxType	The SearchableMailboxType complex type specifies the mailbox entity returned from the GetSearchableMailboxes operation specified in section 3.1.4.3 .

2.2.4.1 ArrayOfFailedSearchMailboxesType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfFailedSearchMailboxesType** complex type specifies an array of failed searches.

```
<xs:complexType name="ArrayOfFailedSearchMailboxesType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="FailedMailbox"
      type="t:FailedSearchMailboxType"/>
  </xs:sequence>
</xs:complexType>
```

FailedMailbox: An element of type **FailedSearchMailboxType**, as defined in section [2.2.4.4](#), that specifies a failed search.

2.2.4.2 ArrayOfMailboxHoldStatusType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfMailboxHoldStatusType** complex type specifies an array of **mailbox** hold statuses.

```
<xs:complexType name="ArrayOfMailboxHoldStatusType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
```

```

<xs:element minOccurs="0" maxOccurs="unbounded" name="MailboxHoldStatus"
type="t:MailboxHoldStatusType"/>
</xs:sequence>
</xs:complexType>

```

MailboxHoldStatus: An element of type **MailboxHoldStatusType**, as defined in section [2.2.4.6](#), that specifies the hold status of the mailbox.

2.2.4.3 ArrayOfSearchableMailboxesType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfSearchableMailboxesType** complex type specifies an array of **mailbox** entities returned from the **GetSearchableMailboxes** operation.

```

<xs:complexType name="ArrayOfSearchableMailboxesType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:sequence>
<xs:element minOccurs="0" maxOccurs="unbounded" name="SearchableMailbox"
type="t:SearchableMailboxType"/>
</xs:sequence>
</xs:complexType>

```

SearchableMailbox: An element of type **SearchableMailboxType**, as defined in section [2.2.4.7](#), that represents the **distribution list** or mailbox entity returned from the **GetSearchableMailboxes** operation.

2.2.4.4 FailedSearchMailboxType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **FailedSearchMailboxType** complex type represents a failed search of a **mailbox**.

```

<xs:complexType name="FailedSearchMailboxType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:sequence>
<xs:element minOccurs="1" maxOccurs="1" name="Mailbox" type="xs:string"/>
<xs:element minOccurs="1" maxOccurs="1" name="ErrorCode" type="xs:int"/>
<xs:element minOccurs="1" maxOccurs="1" name="ErrorMessage" type="xs:string"/>
<xs:element minOccurs="1" maxOccurs="1" name="IsArchive" type="xs:boolean"/>
</xs:sequence>
</xs:complexType>

```

Mailbox: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that contains an identifier for the mailbox.

ErrorCode: An element of type **int**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.17, that contains the error code of the failed search.[<1>](#)

ErrorMessage: An element of type **string** that contains the error message of the failed search.

IsArchive: An element of type **boolean**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.2, that indicates whether the mailbox is an archive mailbox.

2.2.4.5 MailboxHoldResultType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **MailboxHoldResultType** complex type specifies the result of a **mailbox** hold.

```
<xs:complexType name="MailboxHoldResultType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element name="HoldId" type="xs:string"/>
    <xs:element minOccurs="0" name="Query" type="xs:string"/>
    <xs:element name="MailboxHoldStatuses" type="t:ArrayOfMailboxHoldStatusType"/>
  </xs:sequence>
</xs:complexType>
```

HoldId: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) 3.2.1, that represents the hold identifier.

Query: An element of type **string** that represents a search query.

MailboxHoldStatuses: An element of type **ArrayOfMailboxHoldStatusType**, as defined in section [2.2.4.2](#), that contains an array of mailbox hold statuses.

2.2.4.6 MailboxHoldStatusType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **MailboxHoldStatusType** complex type specifies the status of a **mailbox** hold.

```
<xs:complexType name="MailboxHoldStatusType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Mailbox" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Status" type="t:HoldStatusType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="AdditionalInfo" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Mailbox: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1., that contains an identifier for the mailbox.

Status: An element of type **HoldStatusType**, as defined in section [2.2.5.1](#), that contains the hold status for a mailbox.

AdditionalInfo: An element of type **string** that represents additional information.

2.2.4.7 SearchableMailboxType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **SearchableMailboxType** complex type specifies the **mailbox** entity returned from the **GetSearchableMailboxes** operation specified in section [3.1.4.3](#).

```
<xs:complexType name="SearchableMailboxType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Guid" type="t:GuidType"/>
    <xs:element minOccurs="1" maxOccurs="1" name="PrimarySmtpAddress" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="IsExternalMailbox" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ExternalEmailAddress" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="DisplayName" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="IsMembershipGroup" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ReferenceId" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Guid: An element of type **GuidType**, as defined in [MS-OXWSXPROP] section 2.1.7, that contains the **GUID** of the mailbox.

PrimarySmtpAddress: An element of type **string**, as defined in [XMLSCHEMA2] section 3.2.1, that represents the primary **Simple Mail Transfer Protocol (SMTP)** address of the mailbox.

IsExternalMailbox: An element of type **boolean**, as defined in [XMLSCHEMA2] section 3.2.2, that indicates whether the mailbox is an external mailbox.

ExternalEmailAddress: An element of type **string** that contains the external **email address** of the mailbox.

DisplayName: An element of type **string** that specifies the name of the mailbox.

IsMembershipGroup: An element of type **boolean** that indicates whether the entity is a mailbox or a **distribution list**. True indicates a distribution list; otherwise, false.

ReferenceId: An element of type **string** that contains the reference identifier for the mailbox.

2.2.5 Simple Types

The following table summarizes the set of common **XML schema** simple type definitions defined by this specification. XML schema simple type definitions that are specific to a particular operation are described with the operation.

Simple type	Description
HoldStatusType	The HoldStatusType simple type specifies the hold status.

2.2.5.1 HoldStatusType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **HoldStatusType** simple type specifies the hold status.

```
<xs:simpleType name="HoldStatusType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NotOnHold"/>
    <xs:enumeration value="Pending"/>
    <xs:enumeration value="OnHold"/>
    <xs:enumeration value="PartialHold"/>
    <xs:enumeration value="Failed"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **HoldStatusType** simple type.

Value	Meaning
NotOnHold	The mailbox is not on hold.
Pending	Placing or releasing a hold is in progress.
OnHold	The hold was successfully applied to the mailbox.
PartialHold	The hold was successfully applied to some mailboxes but not to all mailboxes.

Value	Meaning
Failed	The hold failed to apply to the mailbox.

2.2.6 Attributes

This specification does not define any common **XML schema** attribute definitions.

2.2.7 Groups

This specification does not define any common **XML schema** group definitions.

2.2.8 Attribute Groups

This specification does not define any common **XML schema** attribute group definitions.

3 Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

In the following sections, the schema definition might be less restrictive than the processing rules imposed by the protocol. The **WSDL** in this specification matches the WSDL that shipped with the product and provides a base description of the schema. The text that introduces the WSDL specifies additional restrictions that reflect actual Microsoft product behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the protocol as specified restricts the same elements to being non-empty, not null and present.

3.1 ExchangeServicePortType Server Details

This protocol defines a single **WSDL port type**, the ExchangeServicePortType, and a set of operations that enable clients to perform **eDiscovery** searches of **mailboxes** and to get and set holds on mailboxes.

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

The following table summarizes the list of operations as defined by this specification.

Operation	Description
GetDiscoverySearchConfiguration	The GetDiscoverySearchConfiguration operation retrieves a search configuration for eDiscovery .
GetHoldOnMailboxes	The GetHoldOnMailboxes operation retrieves the status of a query-based hold, which is set by using the SetHoldOnMailboxes operation, as specified in section 3.1.4.5 . A query-based hold is used to preserve items based on specified query parameters.
GetSearchableMailboxes	The GetSearchableMailboxes operation retrieves a list of mailboxes on which the client has permission to search or to perform eDiscovery.
SearchMailboxes	The SearchMailboxes operation searches for items in the specified mailboxes that match query keywords.
SetHoldOnMailboxes	The SetHoldOnMailboxes operation sets a query-based hold on mailboxes.

3.1.4.1 GetDiscoverySearchConfiguration

The **GetDiscoverySearchConfiguration** operation retrieves a search configuration for **eDiscovery**.

The following is the **WSDL** port type specification of the **GetDiscoverySearchConfiguration WSDL operation**.

```
<wsdl:operation name="GetDiscoverySearchConfiguration"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetDiscoverySearchConfigurationSoapIn"/>
  <wsdl:output message="tns:GetDiscoverySearchConfigurationSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **GetDiscoverySearchConfiguration** operation.

```
<wsdl:operation name="GetDiscoverySearchConfiguration"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetDiscoverySearchCo
    nfiguration" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    <wsdl:input>
      <soap:header message="tns:GetDiscoverySearchConfigurationSoapIn" part="RequestVersion"
        use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
        <soap:header message="tns:GetDiscoverySearchConfigurationSoapIn" part="ManagementRole"
          use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
        <soap:body use="literal" parts="request"
          xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal" parts="GetDiscoverySearchConfigurationResult"
          xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
        <soap:header message="tns:GetDiscoverySearchConfigurationSoapOut" part="ServerVersion"
          use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      </wsdl:output>
    </wsdl:operation>
```

The client sends a **GetDiscoverySearchConfigurationSoapIn** request **WSDL message**, as specified in section [3.1.4.1.1.1](#), and the server responds with a **GetDiscoverySearchConfigurationSoapOut** response, as specified in section [3.1.4.1.1.2](#).

3.1.4.1.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message	Description
GetDiscoverySearchConfigurationSoapIn	Specifies the request to retrieve the search configuration.
GetDiscoverySearchConfigurationSoapOut	Specifies the response to the GetDiscoverySearchConfigurationSoapIn request message (section 3.1.4.1.1.1).

3.1.4.1.1.1 GetDiscoverySearchConfigurationSoapIn

The **GetDiscoverySearchConfigurationSoapIn WSDL message** specifies the request to retrieve the search configuration.

The following is the **GetDiscoverySearchConfigurationSoapIn** WSDL message specification.

```
<wsdl:message name="GetDiscoverySearchConfigurationSoapIn"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="tns:GetDiscoverySearchConfiguration"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
```

The **GetDiscoverySearchConfigurationSoapIn** WSDL message is the input message for the **SOAP action**

<http://schemas.microsoft.com/exchange/services/2006/messages/GetDiscoverySearchConfiguration>.

The parts of the **GetDiscoverySearchConfigurationSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	GetDiscoverySearchConfiguration	Specifies the SOAP body of the request for the search configuration.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the GetDiscoverySearchConfigurationSoapIn WSDL message.
ManagementRole	ManagementRole ([MS-OXWSCDATA] section 2.2.3.7)	Specifies a SOAP header that identifies a user or application role.

3.1.4.1.1.2 GetDiscoverySearchConfigurationSoapOut

The **GetDiscoverySearchConfigurationSoapOut WSDL message** specifies the response to the **GetDiscoverySearchConfigurationSoapIn** request message specified in section [3.1.4.1.1.1](#).

The following is the **GetDiscoverySearchConfigurationSoapOut** WSDL message specification.

```
<wsdl:message name="GetDiscoverySearchConfigurationSoapOut"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="GetDiscoverySearchConfigurationResult"
    element="tns:GetDiscoverySearchConfigurationResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **GetDiscoverySearchConfigurationSoapOut** WSDL message is the output message for the **SOAP action**

<http://schemas.microsoft.com/exchange/services/2006/messages/GetDiscoverySearchConfiguration>.

The parts of the **GetDiscoverySearchConfigurationSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
GetDiscoverySearchConfigurationResult	GetDiscoverySearchConfigurationResponse	Specifies the SOAP body of the response that contains

Part name	Element/type	Description
		the requested configuration.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **GetDiscoverySearchConfiguration** request, as specified in section [3.1.4.1.2.1](#) returns a **GetDiscoverySearchConfigurationResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA] section 2.2.4.65) attribute set to "Success". The **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **GetDiscoverySearchConfigurationResponse** element is set to "NoError".

If the **GetDiscoverySearchConfiguration** request is not successful, it returns a **GetDiscoverySearchConfigurationResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA] section 2.2.4.65) attribute set to "Error". The **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **GetDiscoverySearchConfigurationResponse** element is set to one of the common errors defined in [MS-OXWSCDATA] section 2.2.5.24.

3.1.4.1.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element	Description
GetDiscoverySearchConfiguration	The input data for the GetDiscoverySearchConfiguration WSDL operation .
GetDiscoverySearchConfigurationResponse	The result data for the GetDiscoverySearchConfiguration WSDL operation .

3.1.4.1.2.1 GetDiscoverySearchConfiguration

The **GetDiscoverySearchConfiguration** element specifies the input data for the **GetDiscoverySearchConfiguration WSDL operation**.

```
<xss:element name="GetDiscoverySearchConfiguration"
type="tns:GetDiscoverySearchConfigurationType" xmlns:xss="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.1.2.2 GetDiscoverySearchConfigurationResponse

The **GetDiscoverySearchConfigurationResponse** element specifies the result data for the **GetDiscoverySearchConfiguration WSDL operation**.

```
<xss:element name="GetDiscoverySearchConfigurationResponse"
type="tns:GetDiscoverySearchConfigurationResponseMessageType"
xmlns:xss="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.1.3 Complex Types

The following table summarizes the **XML schema** complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfDiscoverySearchConfigurationType	Specifies an array of DiscoverySearchConfigurationType complex types (section 3.1.4.1.3.4) returned from the GetDiscoverySearchConfiguration operation.
DiscoverySearchConfigurationType	Specifies the search configuration returned from the GetDiscoverySearchConfiguration operation.
GetDiscoverySearchConfigurationResponseMessageType	Specifies the response message for a GetDiscoverySearchConfiguration operation (section 3.1.4.1).
GetDiscoverySearchConfigurationType	Specifies a request to retrieve the search configuration.

3.1.4.1.3.1 GetDiscoverySearchConfigurationType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetDiscoverySearchConfigurationType** complex type specifies a request to retrieve the search configuration. This type extends the **BaseRequestType** complex type, as described in [\[MS-OXWSCDATA\]](#) section 2.2.4.17.

```
<xs:complexType name="GetDiscoverySearchConfigurationType">
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:BaseRequestType">
        <xs:sequence>
          <xs:element minOccurs="0" name="SearchId" type="xs:string"/>
          <xs:element minOccurs="0" name="ExpandGroupMembership" type="xs:boolean"/>
          <xs:element minOccurs="0" name="InPlaceHoldConfigurationOnly" type="xs:boolean"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
```

SearchId: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the identifier of the search.

ExpandGroupMembership: An element of type **boolean**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.2, that specifies whether to expand the group membership. The value "true" specifies extending the group membership.

InPlaceHoldConfigurationOnly: An element of type **boolean** that specifies whether to include the in-place hold configuration. An in-place hold preserves all mailbox content, including deleted items and original versions of modified items. The value "true" specifies that the in-place hold configuration is included.

3.1.4.1.3.2 GetDiscoverySearchConfigurationResponseMessageType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetDiscoverySearchConfigurationResponseMessageType** complex type specifies the response message for a **GetDiscoverySearchConfiguration** operation, as specified in section [3.1.4.1](#). This type extends the **ResponseType** complex type, as specified by [\[MS-OXWSCDATA\]](#) section 2.2.4.65.

```
<xs:complexType name="GetDiscoverySearchConfigurationResponseMessageType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:ResponseType">
      <xs:sequence>
        <xs:element name="DiscoverySearchConfigurations"
          type="t:ArrayOfDiscoverySearchConfigurationType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

DiscoverySearchConfigurations: An element of type **ArrayOfDiscoverySearchConfigurationType**, as defined in section [3.1.4.1.3.3](#), that contains an array of search configurations.

3.1.4.1.3.3 ArrayOfDiscoverySearchConfigurationType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfDiscoverySearchConfigurationType** complex type specifies an array of **DiscoverySearchConfigurationType** complex types, as specified in section [3.1.4.1.3.4](#), returned from the **GetDiscoverySearchConfiguration** operation specified in section [3.1.4.1](#).

```
<xs:complexType name="ArrayOfDiscoverySearchConfigurationType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DiscoverySearchConfiguration"
      type="t:DiscoverySearchConfigurationType"/>
  </xs:sequence>
</xs:complexType>
```

DiscoverySearchConfiguration: An element of type **DiscoverySearchConfigurationType**, as defined in section 3.1.4.1.3.4, that represents the search configuration returned from the **GetDiscoverySearchConfiguration** operation specified in section 3.1.4.1.

3.1.4.1.3.4 DiscoverySearchConfigurationType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **DiscoverySearchConfigurationType** complex type specifies the search configuration returned from the **GetDiscoverySearchConfiguration** operation specified in section [3.1.4.1](#).

```
<xs:complexType name="DiscoverySearchConfigurationType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="SearchId" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SearchQuery" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="SearchableMailboxes"
      type="t:ArrayOfSearchableMailboxesType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="InPlaceHoldIdentity" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ManagedByOrganization" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Language" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

```
</xs:complexType>
```

SearchId: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the search identifier.

SearchQuery: An element of type **string** that represents the search query.

SearchableMailboxes: An element of type **ArrayOfSearchableMailboxesType**, as defined in section [2.2.4.3](#), that specifies the list of searchable **mailboxes**.

InPlaceHoldIdentity: An element of type **string** that specifies the identity of the in-place hold.

ManagedByOrganization: An element of type **string** that specifies the managing organization.

Language: An element of type **string** that specifies the language of the search.

3.1.4.1.4 Simple Types

None.

3.1.4.1.5 Attributes

None.

3.1.4.1.6 Groups

None.

3.1.4.1.7 Attribute Groups

None.

3.1.4.2 GetHoldOnMailboxes

The **GetHoldOnMailboxes** operation retrieves the status of a query-based hold, which is set by using the **SetHoldOnMailboxes** operation, as specified in section [3.1.4.5](#). A query-based hold is used to preserve items based on specified query parameters.

The following is the **WSDL** port type specification of the **GetHoldOnMailboxes WSDL operation**.

```
<wsdl:operation name="GetHoldOnMailboxes" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetHoldOnMailboxesSoapIn"/>
  <wsdl:output message="tns:GetHoldOnMailboxesSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **GetHoldOnMailboxes** operation.

```
<wsdl:operation name="GetHoldOnMailboxes" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetHoldOnMailboxes"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
  <wsdl:input>
    <soap:header message="tns:GetHoldOnMailboxesSoapIn" part="RequestVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
    <soap:header message="tns:GetHoldOnMailboxesSoapIn" part="ManagementRole" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
    <soap:body use="literal" parts="request"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
  </wsdl:input>
</wsdl:operation>
```

```

</wsdl:input>
<wsdl:output>
  <soap:body use="literal" parts="GetHoldOnMailboxesResult"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    <soap:header message="tns:GetHoldOnMailboxesSoapOut" part="ServerVersion" use="literal"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
  </wsdl:output>
</wsdl:operation>

```

The client sends a **GetHoldOnMailboxesSoapIn** request **WSDL message**, as specified in section [3.1.4.2.1.1](#) and the server responds with a **GetHoldOnMailboxesSoapOut** response, as specified in section [3.1.4.2.1.2](#).

3.1.4.2.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message	Description
GetHoldOnMailboxesSoapIn	Specifies the request to retrieve the status of a query-based hold.
GetHoldOnMailboxesSoapOut	Specifies the response to the GetHoldOnMailboxesSoapIn request specified in section 3.1.4.2.1.1 .

3.1.4.2.1.1 GetHoldOnMailboxesSoapIn

The **GetHoldOnMailboxesSoapIn WSDL message** specifies the request to retrieve the status of a query-based hold.

The following is the **GetHoldOnMailboxesSoapIn** WSDL message specification.

```

<wsdl:message name="GetHoldOnMailboxesSoapIn" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="tns:GetHoldOnMailboxes"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>

```

The **GetHoldOnMailboxesSoapIn** WSDL message is the input message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/GetHoldOnMailboxes>.

The parts of the **GetHoldOnMailboxesSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	GetHoldOnMailboxes	Specifies the SOAP body of the request to get the status of a query-based hold.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the GetHoldOnMailboxesSoapIn WSDL message.
ManagementRole	ManagementRole ([MS-OXWSCDATA] section 2.2.3.7)	Specifies a SOAP header that identifies a user or application role.

3.1.4.2.1.2 GetHoldOnMailboxesSoapOut

The **GetHoldOnMailboxesSoapOut WSDL message** specifies the response to the **GetHoldOnMailboxesSoapIn** request specified in section [3.1.4.2.1.1](#).

The following is the **GetHoldOnMailboxesSoapOut** WSDL message specification.

```
<wsdl:message name="GetHoldOnMailboxesSoapOut" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="GetHoldOnMailboxesResult" element="tns:GetHoldOnMailboxesResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **GetHoldOnMailboxesSoapOut** WSDL message is the output message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/GetHoldOnMailboxes>.

The parts of the **GetHoldOnMailboxesSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
GetHoldOnMailboxesResult	GetHoldOnMailboxesResponse	Specifies the SOAP body of the response that contains the result of the request .
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **GetHoldOnMailboxes** request, as specified in section [3.1.4.2.2.1](#), returns a **GetHoldOnMailboxesResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA] section 2.2.4.65) attribute set to "Success". **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **GetHoldOnMailboxesResponse** element is set to "NoError".

If the **GetHoldOnMailboxes** request is not successful, it returns a **GetHoldOnMailboxesResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA] section 2.2.4.65) attribute set to "Error". The **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **GetHoldOnMailboxesResponse** element is set to one of the common errors defined in [MS-OXWSCDATA] section 2.2.5.24.

3.1.4.2.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element	Description
GetHoldOnMailboxes	The input data for the GetHoldOnMailboxes WSDL operation .
GetHoldOnMailboxesResponse	The result data for the GetHoldOnMailboxes WSDL operation.

3.1.4.2.2.1 GetHoldOnMailboxes

The **GetHoldOnMailboxes** element specifies the input data for the **GetHoldOnMailboxes WSDL operation**.

```
<xs:element name="GetHoldOnMailboxes" type="tns:GetHoldOnMailboxesType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.2.2.2 GetHoldOnMailboxesResponse

The **GetHoldOnMailboxesResponse** element specifies the result data for the **GetHoldOnMailboxes WSDL operation**.

```
<xs:element name="GetHoldOnMailboxesResponse"
  type="tns:GetHoldOnMailboxesResponseMessageType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.2.3 Complex Types

The following table summarizes the **XML schema** complex type definitions that are specific to this operation.

Complex type	Description
GetHoldOnMailboxesResponseMessageType	Specifies the response message for a GetHoldOnMailboxes operation, as specified in section 3.1.4.2 .
GetHoldOnMailboxesType	Specifies a request to retrieve the status of a query-based hold.

3.1.4.2.3.1 GetHoldOnMailboxesType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetHoldOnMailboxesType** complex type specifies a request to retrieve the status of query-based holds on **mailboxes**. The **GetHoldOnMailboxesType** complex type extends the **BaseRequestType** complex type, as described in [\[MS-OXWSCDATA\]](#) section 2.2.4.17.

```
<xs:complexType name="GetHoldOnMailboxesType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" name="HoldId" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

HoldId: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the identifier of the hold to be queried.

3.1.4.2.3.2 GetHoldOnMailboxesResponseMessageType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetHoldOnMailboxesResponseType** complex type specifies the response message for a **GetHoldOnMailboxes** operation, as specified in section [3.1.4.2](#). This type extends the **ResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.65.

```
<xs:complexType name="GetHoldOnMailboxesResponseType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:ResponseMessageType">
      <xs:sequence>
        <xs:element minOccurs="0" name="MailboxHoldResult" type="t:MailboxHoldResultType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

MailboxHoldResult: An element of type **MailboxHoldResultType**, as defined in section [2.2.4.5](#), that represents the object that contains the hold result information.

3.1.4.2.4 Simple Types

None.

3.1.4.2.5 Attributes

None.

3.1.4.2.6 Groups

None.

3.1.4.2.7 Attribute Groups

None.

3.1.4.3 GetSearchableMailboxes

The **GetSearchableMailboxes** operation retrieves a list of **mailboxes** on which the client has permission to search or to perform **eDiscovery**.

The following is the **WSDL** port type specification of the **GetSearchableMailboxes WSDL operation**.

```
<wsdl:operation name="GetSearchableMailboxes" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetSearchableMailboxesSoapIn"/>
  <wsdl:output message="tns:GetSearchableMailboxesSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **GetSearchableMailboxes** operation.

```
<wsdl:operation name="GetSearchableMailboxes" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetSearchableMailboxes" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
  <wsdl:input>
    <soap:header message="tns:GetSearchableMailboxesSoapIn" part="RequestVersion"
      use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    <soap:header message="tns:GetSearchableMailboxesSoapIn" part="ManagementRole"
      use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
```

```

<soap:body use="literal" parts="request"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
</wsdl:input>
<wsdl:output>
    <soap:body use="literal" parts="GetSearchableMailboxesResult"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
        <soap:header message="tns:GetSearchableMailboxesSoapOut" part="ServerVersion"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    </wsdl:output>
</wsdl:operation>

```

The client sends a **GetSearchableMailboxesSoapIn** request **WSDL message**, as specified in section [3.1.4.3.1.1](#), and the server responds with **GetSearchableMailboxesSoapOut** response, as specified in section [3.1.4.3.1.2](#).

3.1.4.3.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message	Description
GetSearchableMailboxesSoapIn	Specifies the request to retrieve searchable mailboxes .
GetSearchableMailboxesSoapOut	Specifies the response to the GetSearchableMailboxesSoapIn request.

3.1.4.3.1.1 GetSearchableMailboxesSoapIn

The **GetSearchableMailboxesSoapIn WSDL message** specifies the request to retrieve searchable **mailboxes**.

The following is the **GetSearchableMailboxesSoapIn** WSDL message specification.

```

<wsdl:message name="GetSearchableMailboxesSoapIn"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:part name="request" element="tns:GetSearchableMailboxes"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    <wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>

```

The **GetSearchableMailboxesSoapIn** WSDL message is the input message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/GetSearchableMailboxes>.

The parts of the **GetSearchableMailboxesSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	GetSearchableMailboxes	Specifies the SOAP body of the request to retrieve searchable mailboxes.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the GetSearchableMailboxesSoapIn WSDL message.
ManagementRole	ManagementRole	Specifies a SOAP header that identifies a user or

Part name	Element/type	Description
	([MS-OXWSCDATA] section 2.2.3.7)	application role.

3.1.4.3.1.2 GetSearchableMailboxesSoapOut

The **GetSearchableMailboxesSoapOut WSDL message** specifies the response to the **GetSearchableMailboxesSoapIn** request specified in section [3.1.4.3.1.1](#).

The following is the **GetSearchableMailboxesSoapOut** WSDL message specification.

```
<wsdl:message name="GetSearchableMailboxesSoapOut"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
    <wsdl:part name="GetSearchableMailboxesResult"
      element="tns:GetSearchableMailboxesResponse"/>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
  </wsdl:message>
```

The **GetSearchableMailboxesSoapOut** WSDL message is the output message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/GetSearchableMailboxes>.

The parts of the **GetSearchableMailboxesSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
GetSearchableMailboxesResult	GetSearchableMailboxesResponse	Specifies the SOAP body of the response that contains the requested information.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **GetSearchableMailboxes** request, as specified in section [3.1.4.3.2.1](#), returns a **GetSearchableMailboxesResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA] section 2.2.4.65) attribute set to "Success". The **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **GetSearchableMailboxesResponse** element is set to "NoError".

If the **GetSearchableMailboxes** request is not successful, it returns a **GetSearchableMailboxesResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA] section 2.2.4.65) attribute set to "Error". The **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **GetSearchableMailboxesResponse** element is set to one of the common errors defined in [MS-OXWSCDATA] section 2.2.5.24.

3.1.4.3.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element	Description
GetSearchableMailboxes	The input data for the GetSearchableMailboxes WSDL operation .
GetSearchableMailboxesResponse	The result data for the GetSearchableMailboxes WSDL operation.

3.1.4.3.2.1 GetSearchableMailboxes

The **GetSearchableMailboxes** element specifies the input data for the **GetSearchableMailboxes WSDL operation**.

```
<xs:element name="GetSearchableMailboxes" type="tns:GetSearchableMailboxesType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.3.2.2 GetSearchableMailboxesResponse

The **GetSearchableMailboxesResponse** element specifies the result data for the **GetSearchableMailboxes WSDL operation**.

```
<xs:element name="GetSearchableMailboxesResponse"
type="tns:GetSearchableMailboxesResponseMessageType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.3.3 Complex Types

The following table summarizes the **XML schema** complex type definitions that are specific to this operation.

Complex type	Description
GetSearchableMailboxesResponseMessageType	Specifies the response for a GetSearchableMailboxes operation, as specified in section 3.1.4.3 .
GetSearchableMailboxesType	Specifies a request to retrieve searchable mailboxes .

3.1.4.3.3.1 GetSearchableMailboxesType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetSearchableMailboxesType** complex type specifies a request to retrieve **mailboxes** that the client has permission to search or perform **eDiscovery** on.

```
<xs:complexType name="GetSearchableMailboxesType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="0" name="SearchFilter" type="xs:string"/>
        <xs:element minOccurs="0" name="ExpandGroupMembership" type="xs:boolean"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

SearchFilter: An element of type **string**, as defined in [XMLSCHEMA2] section 3.2.1, that represents a search filter. This element can be empty or contain a specific **email address**, **display name**, or other property of the mailbox.

ExpandGroupMembership: An element of type **boolean**, as defined in [XMLSCHEMA2] section 3.2.2, that indicates whether to expand the group membership if the instance is a **distribution list**. The value "true" specifies expanding the membership.

If the **SearchFilter** element is a distribution group and if the value of the **ExpandGroupMembership** element is "false", the search results will return the mailbox information for the distribution group. If the **SearchFilter** element is a distribution group and the value of the **ExpandGroupMembership** element is "true", then the search results will return the distribution group member information. The distribution group can also take the user name of a single user.

If the **GetSearchableMailboxes** element is empty, the response will contain all searchable mailboxes. This is the same as having an empty **SearchFilter** element and the **ExpandGroupMembership** element set to "false".

3.1.4.3.3.2 GetSearchableMailboxesResponseType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetSearchableMailboxesResponseType** complex type specifies the response for a **GetSearchableMailboxes** operation specified in section 3.1.4.3. This type extends the **ResponseMessageType** complex type, as specified in [MS-OXWSCDATA] section 2.2.4.65.

```
<xs:complexType name="GetSearchableMailboxesResponseMessageType">
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:ResponseMessageType">
        <xs:sequence>
          <xs:element name="SearchableMailboxes" type="t:ArrayOfSearchableMailboxesType"/>
          <xs:element minOccurs="0" name="FailedMailboxes"
            type="t:ArrayOfFailedSearchMailboxesType"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
```

SearchableMailboxes: An element of type **ArrayOfSearchableMailboxesType**, as defined in section 2.2.4.3, that represents the object that contains the **mailboxes** or **distribution list** that match the search filter.

FailedMailboxes: An element of type **ArrayOfFailedSearchMailboxesType**, as defined in section 2.2.4.1, that contains a list of mailboxes that failed the query.

3.1.4.3.4 Simple Types

None.

3.1.4.3.5 Attributes

None.

3.1.4.3.6 Groups

None.

3.1.4.3.7 Attribute Groups

None.

3.1.4.4 SearchMailboxes

The **SearchMailboxes** operation searches for items in the specified **mailboxes** that match query keywords.

The following is the **WSDL** port type specification of the **SearchMailboxes WSDL operation**.

```
<wsdl:operation name="SearchMailboxes" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:SearchMailboxesSoapIn"/>
  <wsdl:output message="tns:SearchMailboxesSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **SearchMailboxes** operation.

```
<wsdl:operation name="SearchMailboxes" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/SearchMailboxes"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    <wsdl:input>
      <soap:header message="tns:SearchMailboxesSoapIn" part="RequestVersion" use="literal"
        xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      <soap:header message="tns:SearchMailboxesSoapIn" part="ManagementRole" use="literal"
        xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      <soap:body use="literal" parts="request"
        xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" parts="SearchMailboxesResult"
        xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      <soap:header message="tns:SearchMailboxesSoapOut" part="ServerVersion" use="literal"
        xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    </wsdl:output>
  </wsdl:operation>
```

The client sends a **SearchMailboxesSoapIn** request **WSDL message**, as specified in section [3.1.4.4.1.1](#), and the server responds with a **SearchMailboxesSoapOut** response, as specified in section [3.1.4.4.1.2](#).

3.1.4.4.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message	Description
SearchMailboxesSoapIn	Specifies the request to search mailboxes .
SearchMailboxesSoapOut	Specifies the response to the SearchMailboxesSoapIn request.

3.1.4.4.1.1 SearchMailboxesSoapIn

The **SearchMailboxesSoapIn WSDL message** specifies the request to search **mailboxes**.

The following is the **SearchMailboxesSoapIn** WSDL message specification.

```

<wsdl:message name="SearchMailboxesSoapIn" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="tns:SearchMailboxes"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>

```

The **SearchMailboxesSoapIn** WSDL message is the input message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/SearchMailboxes>.

The parts of the **SearchMailboxesSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	SearchMailboxes	Specifies the SOAP body of the request to search mailboxes.
RequestVersion ([MS-OXWSCDATA] section 2.2.3.9)	RequestServerVersion	Specifies a SOAP header that identifies the schema version for the SearchMailboxesSoapIn WSDL message.
ManagementRole ([MS-OXWSCDATA] section 2.2.3.7)	ManagementRole	Specifies a SOAP header that identifies a user or application role.

3.1.4.4.1.2 SearchMailboxesSoapOut

The **SearchMailboxesSoapOut WSDL message** specifies the response to the **SearchMailboxesSoapIn** request specified in section [3.1.4.3.1.1](#).

The following is the **SearchMailboxesSoapOut** WSDL message specification.

```

<wsdl:message name="SearchMailboxesSoapOut" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="SearchMailboxesResult" element="tns:SearchMailboxesResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>

```

The **SearchMailboxesSoapOut** WSDL message is the output message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/SearchMailboxes>.

The parts of the **SearchMailboxesSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
SearchMailboxesResult	SearchMailboxesResponse	Specifies the SOAP body of the response that contains the requested search information.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **SearchMailboxes** request, as specified in section [3.1.4.4.2.1](#), returns a **SearchMailboxesResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA]

section 2.2.4.65) attribute set to "Success". The **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **SearchMailboxesResponse** element is set to "NoError".

If the **SearchMailboxes** request is not successful, it returns a **SearchMailboxesResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA] section 2.2.4.65) attribute set to "Error". The **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **SearchMailboxesResponse** element is set to one of the common errors defined in [MS-OXWSCDATA] section 2.2.5.24.

3.1.4.4.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element	Description
SearchMailboxes	The input data for the SearchMailboxes WSDL operation .
SearchMailboxesResponse	The result data for the SearchMailboxes WSDL operation.

3.1.4.4.2.1 SearchMailboxes

The **SearchMailboxes** element specifies the input data for the **SearchMailboxes WSDL operation**.

```
<xs:element name="SearchMailboxes" type="tns:SearchMailboxesType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.4.2.2 SearchMailboxesResponse

The **SearchMailboxesResponse** element specifies the result data for the **SearchMailboxes WSDL operation**.

```
<xs:element name="SearchMailboxesResponse" type="tns:SearchMailboxesResponseType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.4.3 Complex Types

The following table summarizes the **XML schema** complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfExtendedAttributesType	For internal use only.
ArrayOfKeywordStatisticsSearchResultsType	Specifies an array of keyword statistics in the search result.
ArrayOfMailboxStatisticsItemsType	Specifies an array of mailbox statistics.
ArrayOfSearchPreviewItemsType	Specifies an array of search preview items.
ArrayOfSearchRefinerItemsType	Specifies an array of search refiner items.
ExtendedAttributeType	For internal use only.
KeywordStatisticsSearchResultType	Specifies a keyword statistics search result.

Complex type	Description
MailboxQueryType	Specifies the type of the mailbox query.
MailboxSearchScopeType	Specifies a mailbox search scope.
MailboxStatisticsItemType	Specifies a mailbox statistic.
NonEmptyArrayOfExtendedFieldURIsType	Specifies an array of extended property names.
NonEmptyArrayOfMailboxQueriesType	Specifies an array of mailbox queries.
NonEmptyArrayOfMailboxSearchScopesType	Specifies an array of mailbox search scopes.
PreviewItemMailboxType	Specifies the mailbox information in a preview item.
PreviewItemResponseShapeType	Specifies the response format of a preview item, that is, the base shape plus properties.
SearchMailboxesResponseMessageType	Specifies a response message for the SearchMailboxes operation specified in section 3.1.4.4 .
SearchMailboxesResponseType	Specifies the response for a SearchMailboxes operation.
SearchMailboxesResultType	Specifies the result from the SearchMailboxes operation.
SearchMailboxesType	Specifies the format and content of the query response.
SearchPreviewItemType	Specifies a search preview item.
SearchRefinerItemType	Specifies a search refiner item.

3.1.4.4.3.1 SearchMailboxesType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **SearchMailboxesType** complex type specifies the content and format of the result. This type extends the **BaseRequestType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.17.

```

<xs:complexType name="SearchMailboxesType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" name="SearchQueries"
          type="t:NonEmptyArrayOfMailboxQueriesType"/>
        <xs:element minOccurs="1" name="ResultType" type="t:SearchResultType"/>
        <xs:element minOccurs="0" name="PreviewItemResponseShape"
          type="t:PreviewItemResponseShapeType"/>
        <xs:element minOccurs="0" name="SortBy" type="t:FieldOrderType"/>
        <xs:element minOccurs="0" name="Language" type="xs:string"/>
        <xs:element minOccurs="0" name="Deduplication" type="xs:boolean"/>
        <xs:element minOccurs="0" name="PageSize" type="xs:int"/>
        <xs:element minOccurs="0" name="PageItemReference" type="xs:string"/>
        <xs:element minOccurs="0" name="PageDirection" type="t:SearchPageDirectionType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

SearchQueries: An element of type **NonEmptyArrayOfMailboxQueriesType**, as defined in section [3.1.4.4.3.2](#), that represents a set of **mailbox** search scopes.

ResultType: An element of type **SearchResultType**, as defined in section [3.1.4.4.4.2](#), that represents an enumeration type to indicate the type of search result.

PreviewItemResponseShape: An element of type **PreviewItemResponseShapeType**, as defined in section [3.1.4.4.3.6](#), that represents what properties are returned for the preview search result.

SortBy: An element of type **FieldOrderType**, as defined in [\[MS-OXWSSRCH\]](#) section 3.1.4.2.3.6, that specifies a single field by which to sort results and specifies the direction of the sort.

Language: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the query language, for example, "en-us".

Deduplication: An element of type **boolean**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.2, that indicates whether to remove duplicates from the search result.

PageSize: An element of type **int**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.17, that represents the total number of items shown on a preview page.

PageItemReference: An element of type **string** that is used for paging implementation. For the first call, this element should be null. For subsequent calls, set this value to the **SortValue** of the last preview item in the response. **SortValue** is defined in section [3.1.4.4.3.14](#).

PageDirection: An element of type **SearchPageDirectionType**, as defined in section [3.1.4.4.4.4](#), that represents the paging direction; for example, "previous" or "next".

3.1.4.4.3.2 NonEmptyArrayOfMailboxQueriesType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **NonEmptyArrayOfMailboxQueriesType** complex type specifies an array of **mailbox** queries.

```
<xs:complexType name="NonEmptyArrayOfMailboxQueriesType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="unbounded" name="MailboxQuery"
      type="t:MailboxQueryType"/>
  </xs:sequence>
</xs:complexType>
```

MailboxQuery: An element of type **MailboxQueryType**, as defined in section [3.1.4.4.3.3](#), that represents a combination of a query and a list of search scopes.

3.1.4.4.3.3 MailboxQueryType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **MailboxQueryType** complex type specifies the type of the **mailbox** query.

```
<xs:complexType name="MailboxQueryType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Query" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="MailboxSearchScopes"
      type="t:NonEmptyArrayOfMailboxSearchScopesType"/>
  </xs:sequence>
</xs:complexType>
```

Query: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that identifies a search query.

MailboxSearchScopes: An element of type **NonEmptyArrayOfMailboxSearchScopesType**, as defined in section [3.1.4.4.3.4](#), that contains a list of one or more **MailboxSearchScopeType** complex types, as defined in section [3.1.4.4.3.5](#).

3.1.4.4.3.4 NonEmptyArrayOfMailboxSearchScopesType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **NonEmptyArrayOfMailboxSearchScopesType** complex type specifies an array of **mailbox** search scopes.

```
<xs:complexType name="NonEmptyArrayOfMailboxSearchScopesType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="unbounded" name="MailboxSearchScope"
      type="t:MailboxSearchScopeType"/>
  </xs:sequence>
</xs:complexType>
```

MailboxSearchScope: An element of type **MailboxSearchScopeType**, as defined in section [3.1.4.4.3.5](#), that represents a combination of a mailbox and a search scope.

3.1.4.4.3.5 MailboxSearchScopeType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **MailboxSearchScopeType** complex type specifies a query and a set of **mailboxes**.

```
<xs:complexType name="MailboxSearchScopeType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Mailbox" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SearchScope"
      type="t:MailboxSearchLocationType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ExtendedAttributes"
      type="t:ArrayOfExtendedAttributesType"/>
  </xs:sequence>
</xs:complexType>
```

Mailbox: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that contains an identifier for the mailbox.

SearchScope: An element of type **MailboxSearchLocationType**, as defined in section [3.1.4.4.4.1](#), that represents the search scope.

ExtendedAttributes: For internal use only. [<2>](#)

3.1.4.4.3.6 PreviewItemResponseShapeType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **PreviewItemResponseShapeType** complex type specifies the response format of a preview item; that is, the base shape plus properties.

```
<xs:complexType name="PreviewItemResponseShapeType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="BaseShape"
      type="t:PreviewItemBaseShapeType"/>
```

```

<xs:element minOccurs="0" maxOccurs="1" name="AdditionalProperties"
type="t:NonEmptyArrayOfExtendedFieldURIsType"/>
</xs:sequence>
</xs:complexType>

```

BaseShape: An element of type **PreviewItemBaseShapeType**, as defined in section [3.1.4.4.4.3](#), that represents either the default preview with all properties returned or a compact preview with fewer properties returned.

AdditionalProperties: An element of type **NonEmptyArrayOfExtendedFieldURIsType**, as defined in section [3.1.4.4.3.7](#), that represents additional item properties to be returned.

3.1.4.4.3.7 NonEmptyArrayOfExtendedFieldURIsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **NonEmptyArrayOfExtendedFieldURIsType** complex type specifies an array of extended property names.

```

<xs:complexType name="NonEmptyArrayOfExtendedFieldURIsType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:choice maxOccurs="unbounded">
<xs:element name="ExtendedFieldURI" type="t:PathToExtendedFieldType"/>
</xs:choice>
</xs:complexType>

```

ExtendedFieldURI: An element of type **PathToExtendedFieldType**, as defined in [\[MS-OXWSXPROP\]](#) section 2.1.6, that represents the extended property name.

3.1.4.4.3.8 SearchMailboxesResponseType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **SearchMailboxesResponseType** complex type specifies a response for a **SearchMailboxes** operation, as specified in section [3.1.4.4](#). This type extends the **BaseResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.18.

```

<xs:complexType name="SearchMailboxesResponseType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:complexContent mixed="false">
<xs:extension base="tns:BaseResponseMessageType"/>
</xs:complexContent>
</xs:complexType>

```

3.1.4.4.3.9 SearchMailboxesResponseMessageType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **SearchMailboxesResponseMessageType** complex type specifies a response message for the **SearchMailboxes** operation specified in section [3.1.4.4](#). This type extends the **ResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.65.

```

<xs:complexType name="SearchMailboxesResponseMessageType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:complexContent mixed="false">
<xs:extension base="tns:ResponseMessageType">
<xs:sequence>

```

```

<xs:element minOccurs="0" name="SearchMailboxesResult"
type="t:SearchMailboxesResultType"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

SearchMailboxesResult: An element of type **SearchMailboxesResultType**, as defined in section [3.1.4.4.3.10](#), that represents the result of a **SearchMailboxes** operation, as specified in section 3.1.4.4.

3.1.4.4.3.10 SearchMailboxesResultType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **SearchMailboxesResultType** complex type specifies the result from the **SearchMailboxes** operation specified in section [3.1.4.4](#).

```

<xs:complexType name="SearchMailboxesResultType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:sequence>
<xs:element minOccurs="1" name="SearchQueries"
type="t:NonEmptyArrayOfMailboxQueriesType">
<xs:element minOccurs="1" name="ResultType" type="t:SearchResultType"/>
<xs:element minOccurs="1" name="ItemCount" type="xs:long"/>
<xs:element minOccurs="1" name="Size" type="xs:long"/>
<xs:element minOccurs="1" name="PageItemCount" type="xs:int"/>
<xs:element minOccurs="1" name="PageItemSize" type="xs:long"/>
<xs:element minOccurs="0" name="KeywordStats"
type="t:ArrayOfKeywordStatisticsSearchResultsType"/>
<xs:element minOccurs="0" name="Items" type="t:ArrayOfSearchPreviewItemsType"/>
<xs:element minOccurs="0" name="FailedMailboxes"
type="t:ArrayOfFailedSearchMailboxesType"/>
<xs:element minOccurs="0" name="Refiners" type="t:ArrayOfSearchRefinerItemsType"/>
<xs:element minOccurs="0" name="MailboxStats"
type="t:ArrayOfMailboxStatisticsItemsType"/>
</xs:sequence>
</xs:complexType>

```

SearchQueries: An element of type **NonEmptyArrayOfMailboxQueriesType** complex, as defined in section [3.1.4.4.3.2](#), that contains a list of **mailboxes** plus the query to be searched.

ResultType: An element of type **SearchResultType**, as defined in section [3.1.4.4.4.2](#), that contains the type of search, either statistics only or preview only.

ItemCount: An element of type **long**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.16, that contains a value for the total number of items in a search result.

Size: An element of type **long** that contains the total size of the search result.

PageItemCount: An element of type **int**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.17, that contains the number of pages returned in a search result pagination.

PageItemSize: An element of type **long** that contains the number of items to return in a search result pagination.

KeywordStats: An element of type **ArrayOfKeywordStatisticsSearchResultsType**, as defined in section [3.1.4.4.3.11](#), that contains a list of one or more **KeywordStat** elements.

Items: An element of type **ArrayOfSearchPreviewItemsType**, as defined in section [3.1.4.4.3.13](#), that contains a list of items available for preview.

FailedMailboxes: An element of type **ArrayOfFailedSearchMailboxesType**, as defined in section [2.2.4.1](#), that contains a list of mailboxes that failed the search.

Refiners: An element of type **ArrayOfSearchRefinerItemsType**, as defined in section [3.1.4.4.3.16](#), that contains a list of one or more **Refiner** elements.

MailboxStats: An element of type **ArrayOfMailboxStatisticsItemsType**, as defined in section [3.1.4.4.3.18](#), that contains a list of one or more mailbox statistics.

3.1.4.4.3.11 ArrayOfKeywordStatisticsSearchResultsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfKeywordStatisticsSearchResultsType** complex type specifies an array of keyword statistics in the search result.

```
<xs:complexType name="ArrayOfKeywordStatisticsSearchResultsType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="KeywordStat"
      type="t:KeywordStatisticsSearchResultType"/>
  </xs:sequence>
</xs:complexType>
```

KeywordStat: An element of type **KeywordStatisticsSearchResultType**, as defined in section [3.1.4.4.3.12](#), that represents keyword statistics information.

3.1.4.4.3.12 KeywordStatisticsSearchResultType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **KeywordStatisticsSearchResultType** complex type specifies a keyword statistics search result.

```
<xs:complexType name="KeywordStatisticsSearchResultType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Keyword" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ItemHits" type="xs:int"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Size" type="xs:long"/>
  </xs:sequence>
</xs:complexType>
```

Keyword: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the word to be searched for.

ItemHits: An element of type **int**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.17, that represents the number of times that an item appears.

Size: An element of type **long**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.16, that represents the total number of items that have the keyword.

3.1.4.4.3.13 ArrayOfSearchPreviewItemsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfSearchPreviewItemsType** complex type specifies an array of search preview items.

```

<xs:complexType name="ArrayOfSearchPreviewItemsType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">

  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SearchPreviewItem"
      type="t:SearchPreviewItemType"/>
  </xs:sequence>
</xs:complexType>

```

SearchPreviewItem: An element of type **SearchPreviewItemType**, as defined in section [3.1.4.4.3.14](#), that represents a search preview item.

3.1.4.4.3.14 SearchPreviewItemType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **SearchPreviewItemType** complex type specifies a search preview item.

```

<xs:complexType name="SearchPreviewItemType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Id" type="t:ItemIdType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Mailbox" type="t:PreviewItemMailboxType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ParentId" type="t:ItemIdType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ItemClass" type="t:ItemClassType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="UniqueHash" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="SortValue" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="OwaLink" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Sender" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ToRecipients"
      type="t:ArrayOfSmtpAddressType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CcRecipients"
      type="t:ArrayOfSmtpAddressType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="BccRecipients"
      type="t:ArrayOfSmtpAddressType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CreatedTime" type="xs:dateTime"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ReceivedTime" type="xs:dateTime"/>
    <xs:element minOccurs="0" maxOccurs="1" name="SentTime" type="xs:dateTime"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Subject" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Size" type="xs:long"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Preview" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Importance"
      type="t:ImportanceChoicesType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Read" type="xs:boolean"/>
    <xs:element minOccurs="0" maxOccurs="1" name="HasAttachment" type="xs:boolean"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ExtendedProperties"
      type="t:NonEmptyArrayOfExtendedPropertyType"/>
  </xs:sequence>
</xs:complexType>

```

Id: An element of type **ItemIdType**, as defined in [\[MS-OXWScore\]](#) section 2.2.4.25, that represents the item identifier.

Mailbox: An element of the **PreviewItemMailboxType** complex type, as defined in section [3.1.4.4.3.15](#), that contains an identifier for the **mailbox**.

ParentId: An element of type **ItemIdType** that contains the identifier of the parent of the item.

ItemClass: An element of type **ItemClassType**, as defined in [\[MS-OXWScore\]](#) section 2.2.5.4, that contains the message class of the item.

UniqueHash: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that contains a unique hash value used to identify and eliminate duplicates.

SortValue: An element of type **string** that contains a value used for sorting. Preview items are returned ordered by this **SortValue**. To fetch the next page of results, a subsequent call should be made with the **SortValue** of the last item as the **PageItemReference** of the next request.

OwaLink: An element of type **string** that contains the link to preview the item.

Sender: An element of type **string** that contains the address of the person who sent the item.

ToRecipients: An element of type **ArrayOfSmtpAddressType**, as defined in [\[MS-OXWSMSHR\]](#) section 3.1.4.4.3.1, that contains a list of **recipients** to whom the item was sent.

CcRecipients: An element of type **ArrayOfSmtpAddressType** that contains a list of recipients who are carbon copied for the item.

BccRecipients: An element of type **ArrayOfSmtpAddressType** that contains a list of recipients who are blind carbon copied for the item.

CreatedTime: An element of type **dateTime**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.7, that contains the time at which the item was created.

ReceivedTime: An element of type **dateTime** that contains the time at which the item was received.

SentTime: An element of type **dateTime** that contains the time at which the item was sent.

Subject: An element of type **string** that contains the subject of a message item.

Size: An element of type **long**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.16, that contains the size of the item.

Preview: An element of type **string** that is not used and always returns an empty string.

Importance: An element of type **ImportanceChoicesType**, as defined in [\[MS-OXWSCORE\]](#) section 2.2.5.3, that indicates the urgency of the item. The possible values are "High", "Normal", and "Low".

Read: An element of type **boolean**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.2, that indicates whether an item has been read.

HasAttachment: An element of type **boolean** that indicates whether the item has attachments.

ExtendedProperties: A element of type **NonEmptyArrayOfTypeName**, as defined in [\[MS-OXWSXPROP\]](#) section 2.1.3, that contains an array of additional properties.

3.1.4.4.3.15 PreviewItemMailboxType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **PreviewItemMailboxType** complex type specifies the **mailbox** information in a preview item.

```
<xs:complexType name="PreviewItemMailboxType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="MailboxId" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="PrimarySmtpAddress" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

MailboxId: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that contains an identifier for the mailbox.

PrimarySmtpAddress: An element of type **string** that represents the primary **SMTP** address of the mailbox.

3.1.4.4.3.16 ArrayOfSearchRefinerItemsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfSearchRefinerItemsType** complex type specifies an array of search refiner items.

```
<xs:complexType name="ArrayOfSearchRefinerItemsType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Refiner"
      type="t:SearchRefinerItemType"/>
  </xs:sequence>
</xs:complexType>
```

Refiner: An element of the **SearchRefinerItemType** complex type, as defined in section [3.1.4.4.3.17](#), that represents a search refiner.

3.1.4.4.3.17 SearchRefinerItemType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **SearchRefinerItemType** complex type specifies a search refiner item.

```
<xs:complexType name="SearchRefinerItemType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Name" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Value" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Count" type="xs:long"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Token" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Name: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the name of the search refiner.

Value: An element of type **string** that represents the search refiner value.

Count: An element of type **long**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.16, that represents the item count in the search refiner.

Token: An element of type **string** that represents the search refiner token.

3.1.4.4.3.18 ArrayOfMailboxStatisticsItemsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfMailboxStatisticsItemsType** complex type specifies an array of **mailbox** statistics.

```
<xs:complexType name="ArrayOfMailboxStatisticsItemsType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="MailboxStat"
      type="t:MailboxStatisticsItemType"/>
  </xs:sequence>
</xs:complexType>
```

MailboxStat: A element of type **MailboxStatisticsItemType**, as defined in section [3.1.4.4.3.19](#), that contains a value for the mailbox statistic.

3.1.4.4.3.19 MailboxStatisticsItemType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **MailboxStatisticsItemType** complex type specifies a **mailbox** statistic.

```
<xs:complexType name="MailboxStatisticsItemType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="MailboxId" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="DisplayName" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ItemCount" type="xs:long"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Size" type="xs:long"/>
  </xs:sequence>
</xs:complexType>
```

MailboxId: An element of type **string**, as defined in [XMLSCHEMA2] section 3.2.1, that contains an identifier for the mailbox.

DisplayName: An element of type **string** that specifies the name of the mailbox.

ItemCount: An element of type **long**, as defined in [XMLSCHEMA2] section 3.3.16, that contains the total number of items in a search result.

Size: An element of type **long** that contains the size, in bytes, of the mailbox items returned from a search.

3.1.4.4.3.20 ArrayOfExtendedAttributesType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfExtendedAttributesType** complex type is intended for internal use only. [<3>](#)

```
<xs:complexType name="ArrayOfExtendedAttributesType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="ExtendedAttribute"
      type="t:ExtendedAttributeType"/>
  </xs:sequence>
</xs:complexType>
```

ExtendedAttribute: For internal use only.

3.1.4.4.3.21 ExtendedAttributeType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ExtendedAttributeType** complex type is intended for internal use only. [<4>](#)

```
<xs:complexType name="ExtendedAttributeType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Name" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Value" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Name: For internal use only.

Value: For internal use only.

3.1.4.4.4 Simple Types

The following table summarizes the **XML schema** simple type definitions that are specific to this operation.

Simple type	Description
MailboxSearchLocationType	Specifies the location to be searched.
PreviewItemBaseShapeType	Specifies whether an item is previewed with all its properties or it is compacted.
SearchPageDirectionType	Specifies the direction in which to search.
SearchResultType	Specifies a search result.

3.1.4.4.4.1 MailboxSearchLocationType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **MailboxSearchLocationType** simple type specifies the location to be searched.

```
<xs:simpleType name="MailboxSearchLocationType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="PrimaryOnly"/>
    <xs:enumeration value="ArchiveOnly"/>
    <xs:enumeration value="All"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **MailboxSearchLocationType** simple type.

Value	Meaning
PrimaryOnly	Search in primary mailbox only.
ArchiveOnly	Search in archive mailbox only.
All	Search in all mailboxes.

3.1.4.4.4.2 SearchResultType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **SearchResultType** simple type specifies a search result.

```
<xs:simpleType name="SearchResultType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="StatisticsOnly"/>
    <xs:enumeration value="PreviewOnly"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **SearchResultType** simple type.

Value	Meaning
StatisticsOnly	Perform statistics search only.
PreviewOnly	Perform preview search only.

3.1.4.4.4.3 PreviewItemBaseShapeType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **PreviewItemBaseShapeType** simple type specifies whether an item is previewed with all its properties or it is compacted.

```
<xs:simpleType name="PreviewItemBaseShapeType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default"/>
    <xs:enumeration value="Compact"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **PreviewItemBaseShapeType** simple type.

Value	Meaning
Default	Indicates the default view with all properties for the item preview.
Compact	Indicates a compact view with only a few properties for the item preview.

3.1.4.4.4.4 SearchPageDirectionType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **SearchPageDirectionType** simple type specifies the direction in which to search.

```
<xs:simpleType name="SearchPageDirectionType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Previous"/>
    <xs:enumeration value="Next"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **SearchPageDirectionType** simple type.

Value	Meaning
Previous	Navigate to the previous page.
Next	Navigate to the next page.

3.1.4.4.5 Attributes

None.

3.1.4.6 Groups

None.

3.1.4.7 Attribute Groups

None.

3.1.4.5 SetHoldOnMailboxes

The **SetHoldOnMailboxes** operation sets a query-based hold on **mailboxes**.

The following is the **WSDL** port type specification of the **SetHoldOnMailboxes WSDL operation**.

```
<wsdl:operation name="SetHoldOnMailboxes" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:SetHoldOnMailboxesSoapIn"/>
  <wsdl:output message="tns:SetHoldOnMailboxesSoapOut"/>
</wsdl:operation>
```

The following is the WSDL binding specification of the **SetHoldOnMailboxes** operation.

```
<wsdl:operation name="SetHoldOnMailboxes" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/SetHoldOnMailboxes"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
  <wsdl:input>
    <soap:header message="tns:SetHoldOnMailboxesSoapIn" part="RequestVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
    <soap:header message="tns:SetHoldOnMailboxesSoapIn" part="ManagementRole" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
    <soap:body use="literal" parts="request"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" parts="SetHoldOnMailboxesResult"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
    <soap:header message="tns:SetHoldOnMailboxesSoapOut" part="ServerVersion" use="literal"
      xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"/>
  </wsdl:output>
</wsdl:operation>
```

The client sends a **SetHoldOnMailboxesSoapIn** request **WSDL message**, as specified in section [3.1.4.5.1.1](#), and the server responds with a **SetHoldOnMailboxesSoapOut** response, as specified in section [3.1.4.5.1.2](#).

3.1.4.5.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message	Description
SetHoldOnMailboxesSoapIn	Specifies the request to set a query-based hold on mailboxes .
SetHoldOnMailboxesSoapOut	Specifies the response to the SetHoldOnMailboxesSoapIn request specified in section 3.1.4.5.1.1 .

3.1.4.5.1.1 SetHoldOnMailboxesSoapIn

The **SetHoldOnMailboxesSoapIn WSDL message** specifies the request to set a query-based hold on **mailboxes**.

The following is the **SetHoldOnMailboxesSoapIn** WSDL message specification.

```
<wsdl:message name="SetHoldOnMailboxesSoapIn" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="tns:SetHoldOnMailboxes"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
```

The **SetHoldOnMailboxesSoapIn** WSDL message is the input message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/SetHoldOnMailboxes>.

The parts of the **SetHoldOnMailboxesSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	SetHoldOnMailboxes	Specifies the SOAP body of the request to set a query-based hold on mailboxes.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the SetHoldOnMailboxesSoapIn WSDL message.
ManagementRole	ManagementRole ([MS-OXWSCDATA] section 2.2.3.7)	Specifies a SOAP header that identifies a user or application role.

3.1.4.5.1.2 SetHoldOnMailboxesSoapOut

The **SetHoldOnMailboxesSoapOut WSDL message** specifies the response to the **SetHoldOnMailboxesSoapIn** request specified in section [3.1.4.5.1.1](#).

The following is the **SetHoldOnMailboxesSoapOut** WSDL message specification.

```
<wsdl:message name="SetHoldOnMailboxesSoapOut" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="SetHoldOnMailboxesResult" element="tns:SetHoldOnMailboxesResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **SetHoldOnMailboxesSoapOut** WSDL message is the output message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/SetHoldOnMailboxes>.

The parts of the **SetHoldOnMailboxesSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
SetHoldOnMailboxesResult	SetHoldOnMailboxesResponse	Specifies the SOAP body of the response that contains the result of the request.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section	Specifies a SOAP header that identifies the server version for the response.

Part name	Element/type	Description
	2.2.3.10)	

A successful **SetHoldOnMailboxes** request, as specified in section [3.1.4.5.2.1](#), returns a **SetHoldOnMailboxesResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA] section 2.2.4.65) attribute set to "Success". The **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **SetHoldOnMailboxesResponse** element is set to "NoError".

If the **SetHoldOnMailboxes** request is not successful, it returns a **SetHoldOnMailboxesResponse** element with the **ResponseClass** (as specified in [MS-OXWSCDATA] section 2.2.4.65) attribute set to "Error". The **ResponseCode** (as specified in [MS-OXWSCDATA] section 2.2.4.65) element of the **SetHoldOnMailboxesResponse** element is set to one of the common errors defined in [MS-OXWSCDATA] section 2.2.5.24.

3.1.4.5.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element	Description
SetHoldOnMailboxes	The input data for the SetHoldOnMailboxes WSDL operation .
SetHoldOnMailboxesResponse	The result data for the SetHoldOnMailboxes WSDL operation.

3.1.4.5.2.1 SetHoldOnMailboxes

The **SetHoldOnMailboxes** element specifies the input data for the **SetHoldOnMailboxes WSDL operation**.

```
<xs:element name="SetHoldOnMailboxes" type="tns:SetHoldOnMailboxesType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.5.2.2 SetHoldOnMailboxesResponse

The **SetHoldOnMailboxesResponse** element specifies the result data for the **SetHoldOnMailboxes WSDL operation**.

```
<xs:element name="SetHoldOnMailboxesResponse"
  type="tns:SetHoldOnMailboxesResponseMessageType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.5.3 Complex Types

The following table summarizes the **XML schema** complex type definitions that are specific to this operation.

Complex type	Description
SetHoldOnMailboxesResponseMessageType	Specifies the response message for a SetHoldOnMailboxes

Complex type	Description
	operation, as specified in section 3.1.4.5.
SetHoldOnMailboxesType	Specifies a request to set a query-based hold on mailboxes .

3.1.4.5.3.1 SetHoldOnMailboxesType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **SetHoldOnMailboxesType** complex type specifies a request to set a query-based hold on **mailboxes**. This type extends the **BaseRequestType** complex type, as described in [\[MS-OXWSCDATA\]](#) section 2.2.4.17.

```
<xs:complexType name="SetHoldOnMailboxesType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" name="ActionType" type="t:HoldActionType"/>
        <xs:element minOccurs="1" name="HoldId" type="xs:string"/>
        <xs:element minOccurs="1" name="Query" type="xs:string"/>
        <xs:element minOccurs="0" name="Mailboxes" type="t:ArrayOfStringsType"/>
        <xs:element minOccurs="0" name="Language" type="xs:string"/>
        <xs:element minOccurs="0" name="IncludeNonIndexableItems" type="xs:boolean"/>
        <xs:element minOccurs="0" name="Deduplication" type="xs:boolean"/>
        <xs:element minOccurs="0" name="InPlaceHoldIdentity" type="xs:string"/>
        <xs:element minOccurs="0" name="ItemHoldPeriod" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

ActionType: An element of type **HoldActionType**, as defined in section [3.1.4.5.4.1](#) that represents the type of action.

HoldId: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the identifier of the hold.

Query: An element of type **string** that represents a query.

Mailboxes: An element of type **ArrayOfStringsType**, as defined in [\[MS-OXWSCDATA\]](#) section 2.2.4.13, contains a set of **distinguished names (DN)** that represent the mailboxes to which the query-based hold will apply.

Language: An element of type **string** that represents the language of the query, for example, "en-us".[<5>](#)

IncludeNonIndexableItems: An element of type **boolean**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.2, that indicates whether to include items that cannot be indexed.

Deduplication: An element of type **boolean** that indicates whether to remove duplicates from the search result.

InPlaceHoldIdentity: An element of type **string** that specifies the identity of a hold that preserves the mailbox items.

ItemHoldPeriod: An element of type **string** that specifies the time period for the hold.

3.1.4.5.3.2 SetHoldOnMailboxesResponseType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **SetHoldOnMailboxesResponseMessageType** complex type specifies the response message for a **SetHoldOnMailboxes** operation, as specified in section 3.1.4.5. This type extends the **ResponseMessageType** complex type, as described in [\[MS-OXWSCDATA\]](#) section 2.2.4.65.

```
<xs:complexType name="SetHoldOnMailboxesResponseMessageType"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:ResponseMessageType">
      <xs:sequence>
        <xs:element minOccurs="0" name="MailboxHoldResult" type="t:MailboxHoldResultType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

MailboxHoldResult: An element of type **MailboxHoldResultType** complex type, as defined in section 2.2.4.5, that represents the result of a **SetHoldOnMailboxes** operation, as specified in section 3.1.4.5.

3.1.4.5.4 Simple Types

The following table summarizes the **XML schema** simple type definitions that are specific to this operation.

Simple type	Description
Hold ActionType	Specifies a hold action.

3.1.4.5.4.1 Hold ActionType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **Hold ActionType** simple type specifies a hold action.

```
<xs:simpleType name="HoldActionType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Create"/>
    <xs:enumeration value="Update"/>
    <xs:enumeration value="Remove"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **Hold ActionType** simple type.

Value	Meaning
Create	The action is placing a hold.
Update	The action is updating a hold.
Remove	The action is releasing a hold.

3.1.4.5.5 Attributes

None.

3.1.4.5.6 Groups

None.

3.1.4.5.7 Attribute Groups

None.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

4.1 Setting Holds On Mailboxes

This example of the **SetHoldOnMailboxes** operation, as defined in section 3.1.4.5, shows how the client requests the server to set holds on mailboxes. In this example, the client requests holds on two mailboxes and assigns the hold ID "HoldId2".

```
<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
    xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
    xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
    <soap:Header>
        <t:RequestServerVersion Version="Exchange2013" />
    </soap:Header>
    <soap:Body>
        <m:SetHoldOnMailboxes>
            <m:ActionType>Create</m:ActionType>
            <m:HoldId>HoldId2</m:HoldId>
            <m:Query>test</m:Query>
            <m:Mailboxes>
                <t:String>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=1fa841ff5e4749ba93ecc0fd98c2cadf-Willi</t:String>
                <t:String>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=aed2146adaa24ffc9f0f279917e8de95-Micha</t:String>
            </m:Mailboxes>
            <m:Language>English</m:Language>
            <m:IncludeNonIndexableItems>false</m:IncludeNonIndexableItems>
            <m:Deduplication>true</m:Deduplication>
        </m:SetHoldOnMailboxes>
    </soap:Body>
</soap:Envelope>
```

The server returns the following successful response to the client.

```
<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
    <s:Header>
        <h:ServerVersionInfo MajorVersion="15"
            MinorVersion="0"
            MajorBuildNumber="526"
            MinorBuildNumber="0"
            Version="Exchange2013"
            xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns:xsd="http://www.w3.org/2001/XMLSchema"
            xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
    </s:Header>
    <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xmlns:xsd="http://www.w3.org/2001/XMLSchema">
        <SetHoldOnMailboxesResponse ResponseClass="Success"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
            <ResponseCode>NoError</ResponseCode>
            <MailboxHoldResult>
                <HoldId
                    xmlns="http://schemas.microsoft.com/exchange/services/2006/types">HoldId2</HoldId>
                <Query
                    xmlns="http://schemas.microsoft.com/exchange/services/2006/types">test</Query>
                <MailboxHoldStatuses
                    xmlns="http://schemas.microsoft.com/exchange/services/2006/types">
                    <MailboxHoldStatus>
                        <Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=1fa841ff5e4749ba93ecc0fd98c2cadf-Willi</Mailbox>
                        <Status>Pending</Status>
                        <AdditionalInfo/>
                    </MailboxHoldStatus>
                </MailboxHoldStatuses>
            </MailboxHoldResult>
        </SetHoldOnMailboxesResponse>
    </s:Body>
</s:Envelope>
```

```

        </MailboxHoldStatus>
    <MailboxHoldStatus>
        <Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=aed2146adaa24ffc9f0f279917e8de95-Micha</Mailbox>
        <Status>Pending</Status>
        <AdditionalInfo/>
    </MailboxHoldStatus>
    <MailboxHoldStatuses>
    </MailboxHoldResult>
</SetHoldOnMailboxesResponse>
</s:Body>
</s:Envelope>

```

4.2 Getting Mailboxes With Holds

This example of the **GetHoldOnMailboxes** operation, as defined in section [3.1.4.2](#), shows how the client sends a request to the server to get all **mailboxes** with hold ID "HoldId2".

```

<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
    <xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types">
    <xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
<soap:Header>
    <t:RequestServerVersion Version="Exchange2013" />
</soap:Header>
<soap:Body>
    <m:GetHoldOnMailboxes>
        <m:HoldId>HoldId2</m:HoldId>
    </m:GetHoldOnMailboxes>
</soap:Body>
</soap:Envelope>

```

The server sends the following successful response to the client. This response returns two mailboxes.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
    <s:Header>
        <h:ServerVersionInfo MajorVersion="15"
            MinorVersion="0"
            MajorBuildNumber="526"
            MinorBuildNumber="0"
            Version="Exchange2013"
            xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns:xsd="http://www.w3.org/2001/XMLSchema"
            xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
    </s:Header>
    <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xmlns:xsd="http://www.w3.org/2001/XMLSchema">
        <GetHoldOnMailboxesResponse ResponseClass="Success"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
            <ResponseCode>NoError</ResponseCode>
            <MailboxHoldResult>
                <HoldId
                    xmlns="http://schemas.microsoft.com/exchange/services/2006/types">HoldId2</HoldId>
                <Query
                    xmlns="http://schemas.microsoft.com/exchange/services/2006/types">test</Query>
                <MailboxHoldStatuses
                    xmlns="http://schemas.microsoft.com/exchange/services/2006/types">
                    <MailboxHoldStatus>
                        <Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=1fa841ff5e4749ba93ecc0fd98c2cadf-Willi</Mailbox>
                        <Status>OnHold</Status>
                        <AdditionalInfo/>

```

```

        </MailboxHoldStatus>
        <MailboxHoldStatus>
            <Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=aed2146adaa24ffc9f0f279917e8de95-Micha</Mailbox>
            <Status>OnHold</Status>
            <AdditionalInfo/>
        </MailboxHoldStatus>
        <MailboxHoldStatuses>
        </MailboxHoldResult>
    </GetHoldOnMailboxesResponse>
</s:Body>
</s:Envelope>

```

4.3 Getting Searchable Mailboxes

This example of the **GetSearchableMailboxes** operation, as defined in section [3.1.4.3](#), shows a request from the client to get searchable mailboxes.

```

<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
    xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
    xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
    <soap:Header>
        <t:RequestServerVersion Version="Exchange2013" />
    </soap:Header>
    <soap:Body>
        <m:GetSearchableMailboxes>
            <m:SearchFilter>lolgroupl</m:SearchFilter>
            <m:ExpandGroupMembership>true</m:ExpandGroupMembership>
        </m:GetSearchableMailboxes>
    </soap:Body>
</soap:Envelope>

```

This server sends the following successful response for an unexpanded distribution group.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
    <s:Header>
        <h:ServerVersionInfo MajorVersion="15"
            MinorVersion="0"
            MajorBuildNumber="526"
            MinorBuildNumber="0"
            Version="Exchange2013"
            xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns:xsd="http://www.w3.org/2001/XMLSchema"
            xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
    </s:Header>
    <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xmlns:xsd="http://www.w3.org/2001/XMLSchema">
        <GetSearchableMailboxesResponse ResponseClass="Success"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
            <ResponseCode>NoError</ResponseCode>
            <SearchableMailboxes>
                <SearchableMailbox xmlns="http://schemas.microsoft.com/exchange/services/2006/types">
                    <Guid>33a408fe-1574-4e3b-99f5-6e1e001f3035</Guid>
                    <PrimarySmtpAddress>LOLgroup@exhb-
93591dom.extest.microsoft.com</PrimarySmtpAddress>
                    <IsExternalMailbox>false</IsExternalMailbox>
                    <ExternalEmailAddress/>
                    <DisplayName>LOLgroup</DisplayName>
                    <IsMembershipGroup>true</IsMembershipGroup>
                    <ReferenceId>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=85793b958a0b4295b13b8f02b81bf9cc-LOLgroup</ReferenceId>

```

```

        </SearchableMailbox>
    </SearchableMailboxes>
</GetSearchableMailboxesResponse>
</s:Body>
</s:Envelope>

```

The server sends the following response for an expanded distribution group.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
    <s:Header>
        <h:ServerVersionInfo MajorVersion="15"
            MinorVersion="0"
            MajorBuildNumber="526"
            MinorBuildNumber="0"
            Version="Exchange2013"
            xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns:xsd="http://www.w3.org/2001/XMLSchema"
            xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
    </s:Header>
    <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xmlns:xsd="http://www.w3.org/2001/XMLSchema">
        <GetSearchableMailboxesResponse ResponseClass="Success"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
            <ResponseCode>NoError</ResponseCode>
            <SearchableMailboxes>
                <SearchableMailbox
                    xmlns="http://schemas.microsoft.com/exchange/services/2006/types">
                    <Guid>e5d42cdf-a027-4ec6-986b-6fa0ecadb9f5</Guid>
                    <PrimarySmtpAddress>JSmith@exhb-
                        93591dom.extest.microsoft.com</PrimarySmtpAddress>
                    <IsExternalMailbox>false</IsExternalMailbox>
                    <ExternalEmailAddress/>
                    <DisplayName>Julia Smith</DisplayName>
                    <IsMembershipGroup>false</IsMembershipGroup>
                    <ReferenceId>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=0a4fc86f888246159405d60956dd02d7-Julia</ReferenceId>
                </SearchableMailbox>
                <SearchableMailbox xmlns="http://schemas.microsoft.com/exchange/services/2006/types">
                    <Guid>45d0fffb-5013-459a-a34c-52453b30e9ca</Guid>
                    <PrimarySmtpAddress>LMoore@exhb-93591dom.extest.microsoft.com</PrimarySmtpAddress>
                    <IsExternalMailbox>false</IsExternalMailbox>
                    <ExternalEmailAddress/>
                    <DisplayName>Laura Moore</DisplayName>
                    <IsMembershipGroup>false</IsMembershipGroup>
                    <ReferenceId>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=2910d8f8222f4374bbf9338d8f9d714b-Laura</ReferenceId>
                </SearchableMailbox>
                <SearchableMailbox xmlns="http://schemas.microsoft.com/exchange/services/2006/types">
                    <Guid>3c620d04-8b33-435e-95be-5b9351599576</Guid>
                    <PrimarySmtpAddress>SBrown@exhb-93591dom.extest.microsoft.com</PrimarySmtpAddress>
                    <IsExternalMailbox>false</IsExternalMailbox>
                    <ExternalEmailAddress/>
                    <DisplayName>Steven Brown</DisplayName>
                    <IsMembershipGroup>false</IsMembershipGroup>
                    <ReferenceId>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=35181a742f0e47e392c8201a60d13ecf-Steve</ReferenceId>
                </SearchableMailbox>
            </SearchableMailboxes>
        </GetSearchableMailboxesResponse>
    </s:Body>
</s:Envelope> -->

```

4.4 Searching Mailboxes

This example of the **SearchMailboxes** operation, as defined in section [3.1.4.4](#), shows a request from the client to the server to search the specified **mailboxes**.

```
<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
    xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
    xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
        <soap:Header>
            <t:RequestServerVersion Version="Exchange2013" />
        </soap:Header>
        <soap:Body>
            <m:SearchMailboxes>
                <m:SearchQueries>
                    <t:MailboxQuery>
                        <t:Query>Test Item</t:Query>
                        <t:MailboxSearchScopes>
                            <t:MailboxSearchScope>
                                <t:Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=35181a742f0e47e392c8201a60d13ecf-Steve</t:Mailbox>
                                <t:SearchScope>All</t:SearchScope>
                            </t:MailboxSearchScope>
                            <t:MailboxSearchScope>
                                <t:Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=f00c9f70539844beb04001d8f40c572e-Antho</t:Mailbox>
                                <t:SearchScope>PrimaryOnly</t:SearchScope>
                            </t:MailboxSearchScope>
                        </t:MailboxSearchScopes>
                    </t:MailboxQuery>
                    <t:MailboxQuery>
                        <t:Query></t:Query>
                        <t:MailboxSearchScopes>
                            <t:MailboxSearchScope>
                                <t:Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=accba4fd5ddf4356b8a0e82ce1645f4e-Danie</t:Mailbox>
                                <t:SearchScope>ArchiveOnly</t:SearchScope>
                            </t:MailboxSearchScope>
                        </t:MailboxSearchScopes>
                    </t:MailboxQuery>
                </m:SearchQueries>
                <m:ResultType>StatisticsOnly</m:ResultType>
            </m:SearchMailboxes>
        </soap:Body>
    </soap:Envelope>
```

The server sends the following successful response to the client.

```
<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
    <s:Header>
        <h:ServerVersionInfo MajorVersion="15"
            MinorVersion="0"
            MajorBuildNumber="526"
            MinorBuildNumber="0"
            Version="Exchange2013"
            xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
            xmlns:xsd="http://www.w3.org/2001/XMLSchema"
            xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
    </s:Header>
    <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xmlns:xsd="http://www.w3.org/2001/XMLSchema">
        <m:SearchMailboxesResponse
            xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
```

```

xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types">
<m:ResponseMessages>
  <m:SearchMailboxesResponseMessage ResponseClass="Success">
    <m:ResponseCode>NoError</m:ResponseCode>
    <m:SearchMailboxesResult>
      <t:SearchQueries>
        <t:MailboxQuery>
          <t:Query>Test Item</t:Query>
          <t:MailboxSearchScopes>
            <t:MailboxSearchScope>
              <t:Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=35181a742f0e47e392c8201a60d13ecf-Steve</t:Mailbox>
              <t:SearchScope>All</t:SearchScope>

            </t:MailboxSearchScope>
            <t:MailboxSearchScope>
              <t:Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=f00c9f70539844beb04001d8f40c572e-Antho</t:Mailbox>
              <t:SearchScope>PrimaryOnly</t:SearchScope>
            </t:MailboxSearchScope>
          </t:MailboxSearchScopes>
        </t:MailboxQuery>
      </t:SearchQueries>
      <t:ResultType>StatisticsOnly</t:ResultType>
      <t:ItemCount>2</t:ItemCount>
      <t:Size>20206</t:Size>
      <t:PageItemCount>0</t:PageItemCount>
      <t:PageItemSize>0</t:PageItemSize>
      <t:KeywordStats>
        <t:KeywordStat>
          <t:Keyword>Test Item</t:Keyword>
          <t:ItemHits>2</t:ItemHits>
          <t:Size>20206</t:Size>
        </t:KeywordStat>
      </t:KeywordStats>
      <t:FailedMailboxes>
        <t:FailedMailbox>
          <t:Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=accba4fd5ddf4356b8a0e82ce1645f4e-Danie</t:Mailbox>
          <t:ErrorCode>0</t:ErrorCode>
          <t:ErrorMessage>The search query can't be empty.</t:ErrorMessage>
          <t:IsArchive>true</t:IsArchive>
        </t:FailedMailbox>
      </t:FailedMailboxes>
    </m:SearchMailboxesResult>
  </m:SearchMailboxesResponseMessage>
</m:ResponseMessages>
</m:SearchMailboxesResponse>
</s:Body>
</s:Envelope>

```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

For ease of implementation, the full WSDL is provided in this appendix.

```
<?xml version="1.0" encoding="UTF-8"?>
<wsdl:definitions xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
    xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
    xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
    targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
    xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:types>
        <xss:schema elementFormDefault="qualified"
            targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
            version="Exchange2016" id="messages" xmlns:xss="http://www.w3.org/2001/XMLSchema">
            <xss:include schemaLocation="MS-OXWSEDISC-messages.xsd"/>
        </xss:schema>
    </wsdl:types>
    <wsdl:portType name="ExchangeServicePortType">
        <wsdl:operation name="GetDiscoverySearchConfiguration">
            <wsdl:input message="tns:GetDiscoverySearchConfigurationSoapIn"/>
            <wsdl:output message="tns:GetDiscoverySearchConfigurationSoapOut"/>
        </wsdl:operation>
        <wsdl:operation name="GetHoldOnMailboxes">
            <wsdl:input message="tns:GetHoldOnMailboxesSoapIn"/>
            <wsdl:output message="tns:GetHoldOnMailboxesSoapOut"/>
        </wsdl:operation>
        <wsdl:operation name="GetSearchableMailboxes">
            <wsdl:input message="tns:GetSearchableMailboxesSoapIn"/>
            <wsdl:output message="tns:GetSearchableMailboxesSoapOut"/>
        </wsdl:operation>
        <wsdl:operation name="SearchMailboxes">
            <wsdl:input message="tns:SearchMailboxesSoapIn"/>
            <wsdl:output message="tns:SearchMailboxesSoapOut"/>
        </wsdl:operation>
        <wsdl:operation name="SetHoldOnMailboxes">
            <wsdl:input message="tns:SetHoldOnMailboxesSoapIn"/>
            <wsdl:output message="tns:SetHoldOnMailboxesSoapOut"/>
        </wsdl:operation>
    </wsdl:portType>
    <wsdl:binding name="ExchangeServiceBinding" type="tns:ExchangeServicePortType">
        <wsdl:documentation>
            <wsi:Claim conformsTo="http://ws-i.org/profiles/basic/1.0" xmlns:wsi="http://ws-i.org/schemas/conformanceClaim"/>
        </wsdl:documentation>
        <soap:binding transport="http://schemas.xmlsoap.org/soap/http"/>
        <wsdl:operation name="GetDiscoverySearchConfiguration">
            <soap:operation
                soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetDiscoverySearchCo
nfiguration"/>
            <wsdl:input>
                <soap:header message="tns:GetDiscoverySearchConfigurationSoapIn"
                    part="RequestVersion" use="literal"/>
                <soap:header message="tns:GetDiscoverySearchConfigurationSoapIn"
                    part="ManagementRole" use="literal"/>
                <soap:body use="literal" parts="request"/>
            </wsdl:input>
            <wsdl:output>
                <soap:body use="literal" parts="GetDiscoverySearchConfigurationResult"/>
                <soap:header message="tns:GetDiscoverySearchConfigurationSoapOut"
                    part="ServerVersion" use="literal"/>
            </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="GetHoldOnMailboxes">
            <soap:operation
                soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetHoldOnMailboxes"/>
            <wsdl:input>
```

```

<soap:header message="tns:GetHoldOnMailboxesSoapIn" part="RequestVersion"
use="literal"/>
<soap:header message="tns:GetHoldOnMailboxesSoapIn" part="ManagementRole"
use="literal"/>
<soap:body use="literal" parts="request"/>
</wsdl:input>
<wsdl:output>
<soap:body use="literal" parts="GetHoldOnMailboxesResult"/>
<soap:header message="tns:GetHoldOnMailboxesSoapOut" part="ServerVersion"
use="literal"/>
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetSearchableMailboxes">
<soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetSearchableMailbox
es"/>
<wsdl:input>
<soap:header message="tns:GetSearchableMailboxesSoapIn" part="RequestVersion"
use="literal"/>
<soap:header message="tns:GetSearchableMailboxesSoapIn" part="ManagementRole"
use="literal"/>
<soap:body use="literal" parts="request"/>
</wsdl:input>
<wsdl:output>
<soap:body use="literal" parts="GetSearchableMailboxesResult"/>
<soap:header message="tns:GetSearchableMailboxesSoapOut" part="ServerVersion"
use="literal"/>
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SearchMailboxes">
<soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/SearchMailboxes"/>
<wsdl:input>
<soap:header message="tns:SearchMailboxesSoapIn" part="RequestVersion"
use="literal"/>
<soap:header message="tns:SearchMailboxesSoapIn" part="ManagementRole"
use="literal"/>
<soap:body use="literal" parts="request"/>
</wsdl:input>
<wsdl:output>
<soap:body use="literal" parts="SearchMailboxesResult"/>
<soap:header message="tns:SearchMailboxesSoapOut" part="ServerVersion"
use="literal"/>
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="SetHoldOnMailboxes">
<soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/SetHoldOnMailboxes"/
>
<wsdl:input>
<soap:header message="tns:SetHoldOnMailboxesSoapIn" part="RequestVersion"
use="literal"/>
<soap:header message="tns:SetHoldOnMailboxesSoapIn" part="ManagementRole"
use="literal"/>
<soap:body use="literal" parts="request"/>
</wsdl:input>
<wsdl:output>
<soap:body use="literal" parts="SetHoldOnMailboxesResult"/>
<soap:header message="tns:SetHoldOnMailboxesSoapOut" part="ServerVersion"
use="literal"/>
</wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:message name="GetDiscoverySearchConfigurationSoapIn">
<wsdl:part name="request" element="tns:GetDiscoverySearchConfiguration"/>
<wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
<wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
<wsdl:message name="GetDiscoverySearchConfigurationSoapOut">

```

```

<wsdl:part name="GetDiscoverySearchConfigurationResult"
element="tns:GetDiscoverySearchConfigurationResponse"/>
<wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="GetHoldOnMailboxesSoapIn">
<wsdl:part name="request" element="tns:GetHoldOnMailboxes"/>
<wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
<wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
<wsdl:message name="GetHoldOnMailboxesSoapOut">
<wsdl:part name="GetHoldOnMailboxesResult" element="tns:GetHoldOnMailboxesResponse"/>
<wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="GetSearchableMailboxesSoapIn">
<wsdl:part name="request" element="tns:GetSearchableMailboxes"/>
<wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
<wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
<wsdl:message name="GetSearchableMailboxesSoapOut">
<wsdl:part name="GetSearchableMailboxesResult"
element="tns:GetSearchableMailboxesResponse"/>
<wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="SearchMailboxesSoapIn">
<wsdl:part name="request" element="tns:SearchMailboxes"/>
<wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
<wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
<wsdl:message name="SearchMailboxesSoapOut">
<wsdl:part name="SearchMailboxesResult" element="tns:SearchMailboxesResponse"/>
<wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="SetHoldOnMailboxesSoapIn">
<wsdl:part name="request" element="tns:SetHoldOnMailboxes"/>
<wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
<wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
<wsdl:message name="SetHoldOnMailboxesSoapOut">
<wsdl:part name="SetHoldOnMailboxesResult" element="tns:SetHoldOnMailboxesResponse"/>
<wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
</wsdl:definitions>

```

7 Appendix B: Full XML Schema

Schema name	Prefix	Section
http://schemas.microsoft.com/exchange/services/2006/types	t	7.2
http://schemas.microsoft.com/exchange/services/2006/messages	tns	7.1

For ease of implementation, the following sections provide the full XML schema for this protocol.

7.1 http://schemas.microsoft.com/exchange/services/2006/messages Schema

This section contains the contents of the MS-OXWSEDISC-messages.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSEDISC-messages.xsd includes the files listed in the following table. For the schema file to operate correctly, these files have to be present in the folder that contains the **WSDL**, types schema, and messages schema files for this protocol.

File name	Defining specification
MS-OXWSCDATA-messages.xsd	[MS-OXWSCDATA] section 7.1
MS-OXWSWDISC-types.xsd	7.2

```
<?xml version="1.0" encoding="UTF-8"?>
<xss:schema xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  elementFormDefault="qualified"
  targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
  version="Exchange2016" id="messages" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xss:import schemaLocation="MS-OXWSEDISC-types.xsd"
    namespace="http://schemas.microsoft.com/exchange/services/2006/types"/>
  <xss:include schemaLocation="MS-OXWSCDATA-messages.xsd"/>
  <xss:element name="GetHoldOnMailboxes" type="tns:GetHoldOnMailboxesType"/>
  <xss:element name="GetHoldOnMailboxesResponse"
    type="tns:GetHoldOnMailboxesResponseMessageType"/>
  <xss:complexType name="GetDiscoverySearchConfigurationType">
    <xss:complexContent mixed="false">
      <xss:extension base="tns:BaseRequestType">
        <xss:sequence>
          <xss:element minOccurs="0" name="SearchId" type="xs:string"/>
          <xss:element minOccurs="0" name="ExpandGroupMembership" type="xs:boolean"/>
          <xss:element minOccurs="0" name="InPlaceHoldConfigurationOnly" type="xs:boolean"/>
        </xss:sequence>
      </xss:extension>
    </xss:complexContent>
  </xss:complexType>
  <xss:element name="GetDiscoverySearchConfiguration"
    type="tns:GetDiscoverySearchConfigurationType"/>
  <xss:complexType name="GetDiscoverySearchConfigurationResponseMessageType">
    <xss:complexContent mixed="false">
      <xss:extension base="tns:ResponseMessageType">
        <xss:sequence>
          <xss:element name="DiscoverySearchConfigurations"
            type="t:ArrayOfDiscoverySearchConfigurationType"/>
        </xss:sequence>
      </xss:extension>
    </xss:complexContent>
  </xss:complexType>
</xss:schema>
```

```

</xs:complexType>
<xs:element name="GetDiscoverySearchConfigurationResponse"
type="tns:GetDiscoverySearchConfigurationResponseMessageType">
<xs:complexType name="GetHoldOnMailboxesResponseMessageType">
<xs:complexContent mixed="false">
<xs:extension base="tns:ResponseMessageType">
<xs:sequence>
<xs:element minOccurs="0" name="MailboxHoldResult" type="t:MailboxHoldResultType"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="GetHoldOnMailboxesType">
<xs:complexContent mixed="false">
<xs:extension base="tns:BaseRequestType">
<xs:sequence>
<xs:element minOccurs="1" name="HoldId" type="xs:string"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="GetSearchableMailboxesType">
<xs:complexContent mixed="false">
<xs:extension base="tns:BaseRequestType">
<xs:sequence>
<xs:element minOccurs="0" name="SearchFilter" type="xs:string"/>
<xs:element minOccurs="0" name="ExpandGroupMembership" type="xs:boolean"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="GetSearchableMailboxes" type="tns:GetSearchableMailboxesType"/>
<xs:complexType name="GetSearchableMailboxesResponseMessageType">
<xs:complexContent mixed="false">
<xs:extension base="tns:ResponseMessageType">
<xs:sequence>
<xs:element name="SearchableMailboxes" type="t:ArrayOfSearchableMailboxesType"/>
<xs:element minOccurs="0" name="FailedMailboxes"
type="t:ArrayOfFailedSearchMailboxesType"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="GetSearchableMailboxesResponse"
type="tns:GetSearchableMailboxesResponseMessageType"/>
<xs:complexType name="SearchMailboxesType">
<xs:complexContent mixed="false">
<xs:extension base="tns:BaseRequestType">
<xs:sequence>
<xs:element minOccurs="1" name="SearchQueries"
type="t:NonEmptyArrayOfMailboxQueriesType"/>
<xs:element minOccurs="1" name="ResultType" type="t:SearchResultType"/>
<xs:element minOccurs="0" name="PreviewItemResponseShape"
type="t:PreviewItemResponseType"/>
<xs:element minOccurs="0" name="SortBy" type="t:FieldOrderType"/>
<xs:element minOccurs="0" name="Language" type="xs:string"/>
<xs:element minOccurs="0" name="Deduplication" type="xs:boolean"/>
<xs:element minOccurs="0" name="PageSize" type="xs:int"/>
<xs:element minOccurs="0" name="PageItemReference" type="xs:string"/>
<xs:element minOccurs="0" name="PageDirection" type="t:SearchPageDirectionType"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="SearchMailboxes" type="tns:SearchMailboxesType"/>
<xs:complexType name="SearchMailboxesResponseType">
<xs:complexContent mixed="false">
<xs:extension base="tns:BaseResponseMessageType"/>
</xs:complexContent>

```

```

</xs:complexType>
<xs:element name="SearchMailboxesResponse" type="tns:SearchMailboxesResponseType"/>
<xs:complexType name="SearchMailboxesResponseMessageType">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:ResponseMessageType">
            <xs:sequence>
                <xs:element minOccurs="0" name="SearchMailboxesResult"
type="t:SearchMailboxesResultType"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="SetHoldOnMailboxesType">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:BaseRequestType">
            <xs:sequence>
                <xs:element minOccurs="1" name="ActionType" type="t:HoldActionType"/>
                <xs:element minOccurs="1" name="HoldId" type="xs:string"/>
                <xs:element minOccurs="1" name="Query" type="xs:string"/>
                <xs:element minOccurs="0" name="Mailboxes" type="t:ArrayOfStringsType"/>
                <xs:element minOccurs="0" name="Language" type="xs:string"/>
                <xs:element minOccurs="0" name="IncludeNonIndexableItems" type="xs:boolean"/>
                <xs:element minOccurs="0" name="Deduplication" type="xs:boolean"/>
                <xs:element minOccurs="0" name="InPlaceHoldIdentity" type="xs:string"/>
                <xs:element minOccurs="0" name="ItemHoldPeriod" type="xs:string"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="SetHoldOnMailboxes" type="tns:SetHoldOnMailboxesType"/>
<xs:complexType name="SetHoldOnMailboxesResponseMessageType">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:ResponseMessageType">
            <xs:sequence>
                <xs:element minOccurs="0" name="MailboxHoldResult" type="t:MailboxHoldResultType"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="SetHoldOnMailboxesResponse"
type="tns:SetHoldOnMailboxesResponseMessageType"/>
</xs:schema>

```

7.2 <http://schemas.microsoft.com/exchange/services/2006/types> Schema

This section contains the contents of the MS-OXWSEDISC-types.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSEDISC-types.xsd includes the files listed in the following table. For the schema file to operate correctly, these files have to be present in the folder that contains the **WSDL**, types schema, and messages schema files for this protocol.

File name	Defining specification
MS-OXWSXPROP-types.xsd	[MS-OXWSXPROP] section 2.1
MS-OXWSMSHR-types.xsd	[MS-OXWSMSHR] section 7.2

```

<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
elementFormDefault="qualified"

```

```

targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
version="Exchange2016" id="types" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
  <xs:include schemaLocation="MS-OXWSXPROP-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSMSHR-types.xsd"/>
  <xs:complexType name="ArrayOfDiscoverySearchConfigurationType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="DiscoverySearchConfiguration"
type="t:DiscoverySearchConfigurationType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfFailedSearchMailboxesType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="FailedMailbox"
type="t:FailedSearchMailboxType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfKeywordStatisticsSearchResultsType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="KeywordStat"
type="t:KeywordStatisticsSearchResultType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfMailboxHoldStatusType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="MailboxHoldStatus"
type="t:MailboxHoldStatusType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfMailboxStatisticsItemsType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="MailboxStat"
type="t:MailboxStatisticsItemType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfSearchableMailboxesType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="SearchableMailbox"
type="t:SearchableMailboxType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfSearchPreviewItemsType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="SearchPreviewItem"
type="t:SearchPreviewItemType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfSearchRefinerItemsType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="Refiner"
type="t:SearchRefinerItemType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="DiscoverySearchConfigurationType">
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="SearchId" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="SearchQuery" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="SearchableMailboxes"
type="t:ArrayOfSearchableMailboxesType"/>
      <xs:element minOccurs="0" maxOccurs="1" name="InPlaceHoldIdentity" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="ManagedByOrganization" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="Language" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="FailedSearchMailboxType">
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="Mailbox" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="ErrorCode" type="xs:int"/>
      <xs:element minOccurs="1" maxOccurs="1" name="ErrorMessage" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="IsArchive" type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>

```

```

        </xs:sequence>
    </xs:complexType>
    <xs:simpleType name="HoldActionType">
        <xs:restriction base="xs:string">
            <xs:enumeration value="Create"/>
            <xs:enumeration value="Update"/>
            <xs:enumeration value="Remove"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="HoldStatusType">
        <xs:restriction base="xs:string">
            <xs:enumeration value="NotOnHold"/>
            <xs:enumeration value="Pending"/>
            <xs:enumeration value="OnHold"/>
            <xs:enumeration value="PartialHold"/>
            <xs:enumeration value="Failed"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:complexType name="KeywordStatisticsSearchResultType">
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="Keyword" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="ItemHits" type="xs:int"/>
            <xs:element minOccurs="1" maxOccurs="1" name="Size" type="xs:long"/>
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="MailboxStatisticsSearchResultType">
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="UserMailbox" type="t:UserMailboxType"/>
            <xs:element minOccurs="0" maxOccurs="1" name="KeywordStatisticsSearchResult"
type="t:KeywordStatisticsSearchResultType"/>
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="MailboxHoldResultType">
        <xs:sequence>
            <xs:element name="HoldId" type="xs:string"/>
            <xs:element minOccurs="0" name="Query" type="xs:string"/>
            <xs:element name="MailboxHoldStatuses" type="t:ArrayOfMailboxHoldStatusType"/>
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="MailboxHoldStatusType">
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="Mailbox" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="Status" type="t:HoldStatusType"/>
            <xs:element minOccurs="0" maxOccurs="1" name="AdditionalInfo" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="MailboxQueryType">
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="Query" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="MailboxSearchScopes"
type="t:NonEmptyArrayOfMailboxSearchScopesType"/>
        </xs:sequence>
    </xs:complexType>
    <xs:simpleType name="MailboxSearchLocationType">
        <xs:restriction base="xs:string">
            <xs:enumeration value="PrimaryOnly"/>
            <xs:enumeration value="ArchiveOnly"/>
            <xs:enumeration value="All"/>
        </xs:restriction>
    </xs:simpleType>
    <xs:complexType name="ExtendedAttributeType">
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="Name" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="Value" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="ArrayOfExtendedAttributesType">
        <xs:sequence>

```

```

<xs:element minOccurs="0" maxOccurs="unbounded" name="ExtendedAttribute"
type="t:ExtendedAttributeType"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="MailboxSearchScopeType">
<xs:sequence>
<xs:element minOccurs="1" maxOccurs="1" name="Mailbox" type="xs:string"/>
<xs:element minOccurs="1" maxOccurs="1" name="SearchScope"
type="t:MailboxSearchLocationType"/>
<xs:element minOccurs="0" maxOccurs="1" name="ExtendedAttributes"
type="t:ArrayOfExtendedAttributesType"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="MailboxStatisticsItemType">
<xs:sequence>
<xs:element minOccurs="1" maxOccurs="1" name="MailboxId" type="xs:string"/>
<xs:element minOccurs="1" maxOccurs="1" name="DisplayName" type="xs:string"/>
<xs:element minOccurs="1" maxOccurs="1" name="ItemCount" type="xs:long"/>
<xs:element minOccurs="1" maxOccurs="1" name="Size" type="xs:long"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfExtendedFieldURIsType">
<xs:choice maxOccurs="unbounded">
<xs:element name="ExtendedFieldURI" type="t:PathToExtendedFieldType"/>
</xs:choice>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfMailboxSearchScopesType">
<xs:sequence>
<xs:element minOccurs="1" maxOccurs="unbounded" name="MailboxSearchScope"
type="t:MailboxSearchScopeType"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfMailboxQueriesType">
<xs:sequence>
<xs:element minOccurs="1" maxOccurs="unbounded" name="MailboxQuery"
type="t:MailboxQueryType"/>
</xs:sequence>
</xs:complexType>
<xs:simpleType name="PreviewItemBaseShapeType">
<xs:restriction base="xs:string">
<xs:enumeration value="Default"/>
<xs:enumeration value="Compact"/>
</xs:restriction>
</xs:simpleType>
<xs:complexType name="PreviewItemMailboxType">
<xs:sequence>
<xs:element minOccurs="1" maxOccurs="1" name="MailboxId" type="xs:string"/>
<xs:element minOccurs="1" maxOccurs="1" name="PrimarySmtpAddress" type="xs:string"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="PreviewItemResponseShapeType">
<xs:sequence>
<xs:element minOccurs="1" maxOccurs="1" name="BaseShape"
type="t:PreviewItemBaseShapeType"/>
<xs:element minOccurs="0" maxOccurs="1" name="AdditionalProperties"
type="t:NonEmptyArrayOfExtendedFieldURIsType"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="SearchableMailboxType">
<xs:sequence>
<xs:element minOccurs="1" maxOccurs="1" name="Guid" type="t:GuidType"/>
<xs:element minOccurs="1" maxOccurs="1" name="PrimarySmtpAddress" type="xs:string"/>
<xs:element minOccurs="1" maxOccurs="1" name="IsExternalMailbox" type="xs:boolean"/>
<xs:element minOccurs="1" maxOccurs="1" name="ExternalEmailAddress" type="xs:string"/>
<xs:element minOccurs="1" maxOccurs="1" name="DisplayName" type="xs:string"/>
<xs:element minOccurs="1" maxOccurs="1" name="IsMembershipGroup" type="xs:boolean"/>
<xs:element minOccurs="1" maxOccurs="1" name="ReferenceId" type="xs:string"/>
</xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="SearchMailboxesResultType">
  <xs:sequence>
    <xs:element minOccurs="1" name="SearchQueries"
      type="t:NonEmptyArrayOfMailboxQueriesType"/>
      <xs:element minOccurs="1" name="ResultType" type="t:SearchResultType"/>
      <xs:element minOccurs="1" name="ItemCount" type="xs:long"/>
      <xs:element minOccurs="1" name="Size" type="xs:long"/>
      <xs:element minOccurs="1" name="PageItemCount" type="xs:int"/>
      <xs:element minOccurs="1" name="PageItemSize" type="xs:long"/>
      <xs:element minOccurs="0" name="KeywordStats"
        type="t:ArrayOfKeywordStatisticsSearchResultsType"/>
        <xs:element minOccurs="0" name="Items" type="t:ArrayOfSearchPreviewItemsType"/>
        <xs:element minOccurs="0" name="FailedMailboxes"
          type="t:ArrayOfFailedSearchMailboxesType"/>
          <xs:element minOccurs="0" name="Refiners" type="t:ArrayOfSearchRefinerItemsType"/>
          <xs:element minOccurs="0" name="MailboxStats"
            type="t:ArrayOfMailboxStatisticsItemsType"/>
            </xs:sequence>
            </xs:complexType>
            <xs:simpleType name="SearchPageDirectionType">
              <xs:restriction base="xs:string">
                <xs:enumeration value="Previous"/>
                <xs:enumeration value="Next"/>
              </xs:restriction>
            </xs:simpleType>
            <xs:complexType name="SearchPreviewItemType">
              <xs:sequence>
                <xs:element minOccurs="1" maxOccurs="1" name="Id" type="t:ItemIdType"/>
                <xs:element minOccurs="0" maxOccurs="1" name="Mailbox"
                  type="t:PreviewItemMailboxType"/>
                  <xs:element minOccurs="0" maxOccurs="1" name="ParentId" type="t:ItemIdType"/>
                  <xs:element minOccurs="0" maxOccurs="1" name="ItemClass" type="t:ItemClassType"/>
                  <xs:element minOccurs="0" maxOccurs="1" name="UniqueHash" type="xs:string"/>
                  <xs:element minOccurs="0" maxOccurs="1" name="SortValue" type="xs:string"/>
                  <xs:element minOccurs="0" maxOccurs="1" name="OwaLink" type="xs:string"/>
                  <xs:element minOccurs="0" maxOccurs="1" name="Sender" type="xs:string"/>
                  <xs:element minOccurs="0" maxOccurs="1" name="ToRecipients"
                    type="t:ArrayOfSmtpAddressType"/>
                    <xs:element minOccurs="0" maxOccurs="1" name="CcRecipients"
                      type="t:ArrayOfSmtpAddressType"/>
                      <xs:element minOccurs="0" maxOccurs="1" name="BccRecipients"
                        type="t:ArrayOfSmtpAddressType"/>
                        <xs:element minOccurs="0" maxOccurs="1" name="CreatedTime" type="xs:dateTime"/>
                        <xs:element minOccurs="0" maxOccurs="1" name="ReceivedTime" type="xs:dateTime"/>
                        <xs:element minOccurs="0" maxOccurs="1" name="SentTime" type="xs:dateTime"/>
                        <xs:element minOccurs="0" maxOccurs="1" name="Subject" type="xs:string"/>
                        <xs:element minOccurs="0" maxOccurs="1" name="Size" type="xs:long"/>
                        <xs:element minOccurs="0" maxOccurs="1" name="Preview" type="xs:string"/>
                        <xs:element minOccurs="0" maxOccurs="1" name="Importance"
                          type="t:ImportanceChoicesType"/>
                          <xs:element minOccurs="0" maxOccurs="1" name="Read" type="xs:boolean"/>
                          <xs:element minOccurs="0" maxOccurs="1" name="HasAttachment" type="xs:boolean"/>
                          <xs:element minOccurs="0" maxOccurs="1" name="ExtendedProperties"
                            type="t:NonEmptyArrayOfExtendedPropertyType"/>
                            </xs:sequence>
                            </xs:complexType>
                            <xs:complexType name="SearchRefinerItemType">
                              <xs:sequence>
                                <xs:element minOccurs="1" maxOccurs="1" name="Name" type="xs:string"/>
                                <xs:element minOccurs="1" maxOccurs="1" name="Value" type="xs:string"/>
                                <xs:element minOccurs="1" maxOccurs="1" name="Count" type="xs:long"/>
                                <xs:element minOccurs="1" maxOccurs="1" name="Token" type="xs:string"/>
                              </xs:sequence>
                            </xs:complexType>
                            <xs:simpleType name="SearchResultType">
                              <xs:restriction base="xs:string">
                                <xs:enumeration value="StatisticsOnly"/>
                                <xs:enumeration value="PreviewOnly"/>
                              </xs:restriction>
                            </xs:simpleType>
                          </xs:complexType>
                        </xs:sequence>
                      </xs:complexType>
                    </xs:sequence>
                  </xs:complexType>
                </xs:sequence>
              </xs:complexType>
            </xs:complexType>
          </xs:sequence>
        </xs:complexType>
      </xs:complexType>
    </xs:sequence>
  </xs:complexType>

```

```
</xs:simpleType>
<xs:complexType name="UserMailboxType">
  <xs:attribute name="Id" type="xs:string" use="required"/>
  <xs:attribute name="IsArchive" type="xs:boolean" use="required"/>
</xs:complexType>
</xs:schema>
```

8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Microsoft Exchange Server 2013
- Microsoft SharePoint Server 2013
- Microsoft Exchange Server 2016
- Microsoft Exchange Server 2019
- Microsoft SharePoint Server 2016
- Microsoft Exchange Server Subscription Edition

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

[**<1> Section 2.2.4.4**](#): Exchange 2013, Exchange 2016, and Exchange 2019 do not use the **ErrorCode** element. This value is always 0.

[**<2> Section 3.1.4.4.3.5**](#): Microsoft Exchange Server 2007, Microsoft Exchange Server 2010, and the initial release of Exchange 2013 do not support the **ExtendedAttributes** element. This element was introduced in Microsoft Exchange Server 2013 Service Pack 1 (SP1).

[**<3> Section 3.1.4.4.3.20**](#): Exchange 2007, Exchange 2010, and the initial release of Exchange 2013 do not support the **ArrayOfExtendedAttributesType** complex type. This type was introduced in Exchange 2013 SP1.

[**<4> Section 3.1.4.4.3.21**](#): Exchange 2007, Exchange 2010, and the initial release Exchange 2013 do not support the **ExtendedAttributeType** complex type. This type was introduced in Exchange 2013 SP1.

[**<5> Section 3.1.4.5.3.1**](#): Exchange 2013, Exchange 2016, and Exchange 2019 do not use the **Language** element; it can be set to any value.

9 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Description	Revision class
8 Appendix C: Product Behavior	Updated list of supported products.	Major

10 Index

A

Abstract data model
 [server](#) 17
[Applicability](#) 9
[ArrayOfFailedSearchMailboxesType complex type](#) 12
[ArrayOfMailboxHoldStatusType complex type](#) 12
[ArrayOfSearchableMailboxesType complex type](#) 13
[Attribute groups](#) 16
[Attributes](#) 16

C

[Capability negotiation](#) 10
[Change tracking](#) 72
Client
 [overview](#) 17
[Complex types](#) 12
 [ArrayOfFailedSearchMailboxesType](#) 12
 [ArrayOfMailboxHoldStatusType](#) 12
 [ArrayOfSearchableMailboxesType](#) 13
 [FailedSearchMailboxType](#) 13
 [MailboxHoldResultType](#) 13
 [MailboxHoldStatusType](#) 14
 [SearchableMailboxType](#) 14

D

Data model - abstract
 [server](#) 17

E

Events
 [local - server](#) 52
 [timer - server](#) 52
Examples
 [getting mailboxes with holds](#) 54
 [getting searchable mailboxes](#) 55
 [searching mailboxes](#) 57
 [setting holds on mailboxes](#) 53
[ExchangeServicePortType port type](#) 17

F

[FailedSearchMailboxType complex type](#) 13
[Fields - vendor-extensible](#) 10
[Full WSDL](#) 60
[Full XML schema](#) 63
 <http://schemas.microsoft.com/exchange/service/s/2006/messages Schema> 63
 <http://schemas.microsoft.com/exchange/service/s/2006/types Schema> 65

G

[Getting mailboxes with holds example](#) 54
[Getting searchable mailboxes example](#) 55
[Glossary](#) 6

[Groups](#) 16

H

[HoldStatusType simple type](#) 15

I

[Implementer - security considerations](#) 59
[Index of security parameters](#) 59
[Informative references](#) 8

Initialization

[server](#) 17

[Introduction](#) 6

L

Local events
 [server](#) 52

M

[MailboxHoldResultType complex type](#) 13
[MailboxHoldStatusType complex type](#) 14
Message processing
 [server](#) 17
Messages
 [ArrayOfFailedSearchMailboxesType complex type](#)
 12
 [ArrayOfMailboxHoldStatusType complex type](#) 12
 [ArrayOfSearchableMailboxesType complex type](#) 13
 [attribute groups](#) 16
 [attributes](#) 16
 [complex types](#) 12
 [elements](#) 11
 [enumerated](#) 11
 [FailedSearchMailboxType complex type](#) 13
 [groups](#) 16
 [HoldStatusType simple type](#) 15
 [MailboxHoldResultType complex type](#) 13
 [MailboxHoldStatusType complex type](#) 14
 [namespaces](#) 11
 [SearchableMailboxType complex type](#) 14
 [simple types](#) 15
 [syntax](#) 11
 [transport](#) 11

N

[Namespaces](#) 11
[Normative references](#) 8

O

Operations
 [GetDiscoverySearchConfiguration](#) 18
 [GetHoldOnMailboxes](#) 23
 [GetSearchableMailboxes](#) 27
 [SearchMailboxes](#) 32
 [SetHoldOnMailboxes](#) 47
 [Overview \(synopsis\)](#) 9

P

[Parameters - security index](#) 59

Port types

[ExchangeServicePortType](#) 17

Preconditions 9

Prerequisites 9

[Product behavior](#) 71

Protocol Details

[overview](#) 17

R

[References](#) 7

informative 8

normative 8

[Relationship to other protocols](#) 9

S

[SearchableMailboxType complex type](#) 14

[Searching mailboxes example](#) 57

Security

[implementer considerations](#) 59

[parameter index](#) 59

Sequencing rules

[server](#) 17

Server

[abstract data model](#) 17

[ExchangeServicePortType port type](#) 17

[GetDiscoverySearchConfiguration operation](#) 18

[GetHoldOnMailboxes operation](#) 23

[GetSearchableMailboxes operation](#) 27

[initialization](#) 17

[local events](#) 52

[message processing](#) 17

[overview](#) 17

[SearchMailboxes operation](#) 32

[sequencing rules](#) 17

[SetHoldOnMailboxes operation](#) 47

[timer events](#) 52

[timers](#) 17

[Setting holds on mailboxes example](#) 53

Simple types 15

[HoldStatusType](#) 15

[Standards assignments](#) 10

Syntax

[messages - overview](#) 11

T

Timer events

[server](#) 52

Timers

[server](#) 17

[Tracking changes](#) 72

[Transport](#) 11

Types

[complex](#) 12

[simple](#) 15

V

[Vendor-extensible fields](#) 10

[Versioning](#) 10

W

[WSDL](#) 60

X

[XML schema](#) 63

<http://schemas.microsoft.com/exchange/service/s/2006/messages Schema> 63

<http://schemas.microsoft.com/exchange/service/s/2006/types Schema> 65