

[MS-OXWSFOLD]: Folders and Folder Permissions Web Service Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplq@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
07/15/2009	1.0	Major	Initial Availability.

PRELIMINARY

Table of Contents

1 Introduction	7
1.1 Glossary.....	7
1.2 References.....	7
1.2.1 Normative References	7
1.2.2 Informative References	8
1.3 Protocol Overview	8
1.4 Relationship to Other Protocols.....	8
1.5 Prerequisites/Preconditions.....	9
1.6 Applicability Statement.....	9
1.7 Versioning and Capability Negotiation.....	9
1.8 Vendor-Extensible Fields	9
1.9 Standards Assignments	9
2 Messages	10
2.1 Transport.....	10
2.2 Common Message Syntax.....	10
2.2.1 Namespaces.....	10
2.2.2 Simple Types	10
2.2.2.1 t:FolderClassType Simple Type.....	11
2.2.2.2 t:PermissionActionType Simple Type	11
2.2.2.3 t:PermissionLevelType Simple Type.....	11
2.2.2.4 t:PermissionReadAccessType Simple Type	13
2.2.3 Complex Types.....	13
2.2.3.1 t:ArrayOfFoldersType Complex Type.....	14
2.2.3.2 m:BaseMoveCopyFolderType Complex Type	15
2.2.3.3 t:BasePermissionType Complex Type.....	15
2.2.3.4 t:ArrayOfUnknownEntriesType Complex Type	17
2.2.3.5 t:BaseFolderIdType Complex Type.....	17
2.2.3.6 t:BaseFolderType Complex Type.....	17
2.2.3.7 t:FolderChangeDescriptionType Complex Type.....	19
2.2.3.8 t:FolderChangeType Complex Type.....	19
2.2.3.9 m:FolderInfoResponseMessageType Complex Type.....	20
2.2.3.10 t:FolderType Complex Type	21
2.2.3.11 t:ManagedFolderInformationType Complex Type.....	21
2.2.3.12 t:PermissionSetType Complex Type	23
2.2.3.13 t:PermissionType Complex Type	23
2.2.3.14 t:TargetFolderIdType Complex Type	24
2.2.4 Elements.....	24
2.2.5 Attributes.....	24
2.2.6 Groups.....	24
2.2.7 Attribute Groups	24
2.2.8 Message Syntax.....	24
3 Protocol Details	25
3.1 ExchangeServicePortType Server Detail.....	25
3.1.1 Abstract Data Model.....	25
3.1.2 Timers	25
3.1.3 Initialization	25
3.1.4 Message Processing Events and Sequencing	25
3.1.4.1 CopyFolder.....	26

3.1.4.1.1	CopyFolder Simple Types	26
3.1.4.1.2	CopyFolder Complex Types.....	26
3.1.4.1.2.1	m:CopyFolderResponseType Complex Type	26
3.1.4.1.2.2	m:CopyFolderType Complex Type.....	27
3.1.4.1.3	CopyFolder Elements.....	27
3.1.4.1.3.1	CopyFolder Element	27
3.1.4.1.3.2	CopyFolderResponse Element.....	27
3.1.4.1.4	CopyFolder Attributes.....	27
3.1.4.1.5	CopyFolder Groups.....	27
3.1.4.1.6	CopyFolder Attribute Groups.....	28
3.1.4.1.7	CopyFolder Messages	28
3.1.4.1.7.1	tns:CopyFolderSoapIn.....	28
3.1.4.1.7.2	tns:CopyFolderSoapOut.....	28
3.1.4.2	CreateFolder	28
3.1.4.2.1	CreateFolder Simple Types	29
3.1.4.2.2	CreateFolder Complex Types	29
3.1.4.2.2.1	t:CreateFolderResponseType Complex Type.....	29
3.1.4.2.2.2	m:CreateFolderType Complex Type	29
3.1.4.2.2.3	t:NonEmptyArrayOfFoldersType Complex Type	30
3.1.4.2.3	CreateFolder Elements	31
3.1.4.2.3.1	CreateFolder Element.....	31
3.1.4.2.3.2	CreateFolderResponse Element.....	31
3.1.4.2.4	CreateFolder Attributes	31
3.1.4.2.5	CreateFolder Groups	31
3.1.4.2.6	CreateFolder Attribute Groups	31
3.1.4.2.7	CreateFolder Messages.....	31
3.1.4.2.7.1	tns:CreateFolderSoapIn.....	32
3.1.4.2.7.2	tns:CreateFolderSoapOut	32
3.1.4.3	CreateManagedFolder.....	32
3.1.4.3.1	CreateManagedFolder Simple Types	32
3.1.4.3.2	CreateManagedFolder Complex Types.....	32
3.1.4.3.2.1	m:CreateManagedFolderRequestType Complex Type.....	33
3.1.4.3.2.2	m:CreateManagedFolderResponseType Complex Type	33
3.1.4.3.2.3	t:NonEmptyArrayOfFolderNamesType Complex Type	34
3.1.4.3.3	CreateManagedFolder Elements.....	34
3.1.4.3.3.1	CreateManagedFolder Element	34
3.1.4.3.3.2	CreateManagedFolderResponse Element	34
3.1.4.3.4	CreateManagedFolder Attributes	35
3.1.4.3.5	CreateManagedFolder Group	35
3.1.4.3.6	CreateManagedFolder Attribute Groups.....	35
3.1.4.3.7	CreateManagedFolder Messages	35
3.1.4.3.7.1	tns:CreateManagedFolderSoapIn	35
3.1.4.3.7.2	tns:CreateManagedFolderSoapOut.....	35
3.1.4.4	DeleteFolder.....	36
3.1.4.4.1	DeleteFolder Simple Types.....	36
3.1.4.4.2	DeleteFolder Complex Types.....	36
3.1.4.4.2.1	m>DeleteFolderResponseType Complex Type	36
3.1.4.4.2.2	m>DeleteFolderType Complex Type.....	36
3.1.4.4.3	DeleteFolder Elements.....	37
3.1.4.4.3.1	DeleteFolder Element.....	37
3.1.4.4.3.2	DeleteFolderResponse Element.....	37
3.1.4.4.4	DeleteFolder Attributes.....	38
3.1.4.4.5	DeleteFolder Groups.....	38

3.1.4.4.6	DeleteFolder Attribute Groups	38
3.1.4.4.7	DeleteFolder Messages	38
3.1.4.4.7.1	tns>DeleteFolderSoapIn	38
3.1.4.4.7.2	tns>DeleteFolderSoapOut	38
3.1.4.5	GetFolder	39
3.1.4.5.1	GetFolder Simple Types	39
3.1.4.5.2	GetFolder Complex Types	39
3.1.4.5.2.1	m:GetFolderResponseType Complex Type	39
3.1.4.5.2.2	m:GetFolderType Complex Type	39
3.1.4.5.2.3	t:NonEmptyArrayOfBaseFolderIdsType Complex Type	40
3.1.4.5.3	GetFolder Elements	40
3.1.4.5.3.1	GetFolder Element	41
3.1.4.5.3.2	GetFolderResponse Element	41
3.1.4.5.4	GetFolder Attributes	41
3.1.4.5.5	GetFolder Groups	41
3.1.4.5.6	GetFolder Attribute Groups	41
3.1.4.5.7	GetFolder Messages	41
3.1.4.5.7.1	tns:GetFolderSoapIn	41
3.1.4.5.7.2	tns:GetFolderSoapOut	42
3.1.4.6	MoveFolder	42
3.1.4.6.1	MoveFolder Simple Types	42
3.1.4.6.2	MoveFolder Complex Types	42
3.1.4.6.2.1	m:MoveFolderResponseType Complex Type	43
3.1.4.6.2.2	m:MoveFolderType Complex Type	43
3.1.4.6.3	MoveFolder Elements	43
3.1.4.6.3.1	MoveFolder Element	43
3.1.4.6.3.2	MoveFolderResponse Element	43
3.1.4.6.4	MoveFolder Attributes	44
3.1.4.6.5	MoveFolder Groups	44
3.1.4.6.6	MoveFolder Attribute Groups	44
3.1.4.6.7	MoveFolder Messages	44
3.1.4.6.7.1	tns:MoveFolderSoapIn	44
3.1.4.6.7.2	tns:MoveFolderSoapOut	44
3.1.4.7	UpdateFolder	45
3.1.4.7.1	UpdateFolder Simple Types	45
3.1.4.7.2	UpdateFolder Complex Types	45
3.1.4.7.2.1	m:UpdateFolderResponseType Complex Type	45
3.1.4.7.2.2	m:UpdateFolderType Complex Type	46
3.1.4.7.2.3	t:AppendToFolderFieldType Complex Type	46
3.1.4.7.2.4	t>DeleteFolderFieldType Complex Type	47
3.1.4.7.2.5	t:NonEmptyArrayOfFolderChangeDescriptionsType Complex Type	47
3.1.4.7.2.6	t:NonEmptyArrayOfFolderChangesType Complex Type	48
3.1.4.7.2.7	t:SetFolderFieldType Complex Type	48
3.1.4.7.3	UpdateFolder Elements	49
3.1.4.7.3.1	UpdateFolder Element	49
3.1.4.7.3.2	UpdateFolderResponse Element	50
3.1.4.7.4	UpdateFolder Attributes	50
3.1.4.7.5	UpdateFolder Groups	50
3.1.4.7.6	UpdateFolder Attribute Groups	50
3.1.4.7.7	UpdateFolder Messages	50
3.1.4.7.7.1	tns:UpdateFolderSoapIn	50
3.1.4.7.7.2	tns:UpdateFolderSoapOut	50
3.1.5	Server Timer Events	51

3.1.6	Server Other Local Events	51
3.2	Client Details.....	51
3.2.1	Abstract Data Model.....	51
3.2.2	Timers	51
3.2.3	Initialization	51
3.2.4	Message Processing Events and Sequencing	51
3.2.5	Timer Events.....	51
3.2.6	Other Local Events	51
4	Protocol Examples	52
5	Security.....	53
5.1	Security Considerations for Implementers.....	53
5.2	Index of Security Parameters	53
6	Appendix A: Full WSDL	54
6.1	Messages Schema	54
6.2	Types Schema.....	57
6.3	WSDL.....	61
7	Appendix B: Product Behavior	66
8	Change Tracking	67
9	Index.....	68

1 Introduction

This document specifies the Folders and Folder Permissions Web Service Protocol Specification, which is used by clients to manipulate and organize **folders**, and retrieve and set permissions on a **Folder object**.

1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

Active Directory
contact
folder
folder object
mailbox
message
search folder
SOAP body
SOAP fault
SOAP header
special folder
store
Web Services Description Language (WSDL)
WSDL message
WSDL port type
XML
XML namespace
XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", June 2008.

[MS-OXWSCDATA] Microsoft Corporation, "[Common Web Service Data Types Specification](#)", July 2009.

[MS-OXWSXPROP] Microsoft Corporation, "[Extended Exchange Server Web Service Properties Specification](#)", July 2009.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.

[RFC3066] Alvestrand, H., "Tags for the Identification of Languages", RFC 3066, January 2001, <http://www.ietf.org/rfc/rfc3066.txt>.

[SOAP1.1] Box, D., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>.

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315/>.

[XMLNS] World Wide Web Consortium, "Namespaces in XML 1.0 (Second Edition)", August 2006, <http://www.w3.org/TR/REC-xml-names/>.

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>.

[XMLSCHEMA2] Biron, P.V., Ed., and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>.

1.2.2 Informative References

None.

1.3 Protocol Overview

The Folders and Folder Permissions Web Service Protocol provides clients with the folder operations for retrieving folder permission lists that are stored on the server. The protocol specifies the elements and operations for creating and locating the **special folders** in a **mailbox**.

1.4 Relationship to Other Protocols

The Folders and Folder Permissions Web Service uses SOAP over HTTPS, as shown in the following figures.




Figure 1: Figure 1: SOAP over HTTP




Figure 2: Figure 2:SOAP over HTTPS

1.5 Prerequisites/Preconditions

None.

1.6 Applicability Statement

The specification is applicable to environments that copy, create, delete, get, move, or update folders, using Exchange Web Services.

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

Supported Transports: This protocol uses SOAP 1.1, as specified in section [2.1](#).

Protocol Versions: This protocol specifies only one **WSDL port type** version.

Security and Authentication Methods: This protocol relies on the Web server that is hosting it to perform authentication.

Localization: This protocol includes text strings in various **messages**. Localization considerations for such strings are specified in section [3.1.4](#).

Capability Negotiation: None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

The SOAP version supported is SOAP 1.1. For details, see [\[SOAP1.1\]](#).

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and **Web Services Description Language (WSDL)**, as defined in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
tns	http://schemas.microsoft.com/exchange/services/2006/messages	[MS-OXWSFOLD]
s	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]
targetNamespace	http://schemas.microsoft.com/exchange/services/2006/messages	[MS-OXWSFOLD]
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
t	http://schemas.microsoft.com/exchange/services/2006/types	[MS-OXWSFOLD]

2.2.2 Simple Types

The following table summarizes the set of common XML schema simple type definitions defined by this specification. XML schema simple type definitions that are specific to a particular operation are described with the operation.

Simple Type	Description
t:FolderClassType	A string representation of the folder.
t:PermissionActionType	The PermissionActionType enumeration defines which items in a folder a user has permission to edit or delete.
t:PermissionLevelType	The PermissionLevelType enumeration specifies the permission level that a user has on a folder.
t:PermissionReadAccessType	The PermissionReadAccessType enumeration specifies whether a user has permission to read items in a folder.

2.2.2.1 t:FolderClassType Simple Type

The **FolderClassType** simple type represents the folder.

```
<xs:simpleType name="FolderClassType">
  <xs:restriction
    base="xs:string"
  />
</xs:simpleType>
```

2.2.2.2 t:PermissionActionType Simple Type

The **PermissionActionType** simple type enumeration defines which items in a folder a user has permission to edit or delete.

```
<xs:simpleType name="PermissionActionType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="None"
    />
    <xs:enumeration
      value="Owned"
    />
    <xs:enumeration
      value="All"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **PermissionActionType** simple type:

Value	Description
None	Indicates that the user does not have permission to perform the action on any items in the folder.
Owned	Indicates that the user has permission to perform the action on the items in the folder that the user owns.
All	Indicates that the user has permission to perform the action on all items in the folder.

2.2.2.3 t:PermissionLevelType Simple Type

The **PermissionLevelType** simple type enumeration specifies the permission level that a user has on a folder.

```
<xs:simpleType name="PermissionLevelType">
  <xs:restriction
```

```

    base="xs:string"
  >
    <xs:enumeration
      value="None"
    />
    <xs:enumeration
      value="Owner"
    />
    <xs:enumeration
      value="PublishingEditor"
    />
    <xs:enumeration
      value="Editor"
    />
    <xs:enumeration
      value="PublishingAuthor"
    />
    <xs:enumeration
      value="Author"
    />
    <xs:enumeration
      value="NoneditingAuthor"
    />
    <xs:enumeration
      value="Reviewer"
    />
    <xs:enumeration
      value="Contributor"
    />
    <xs:enumeration
      value="Custom"
    />
  </xs:restriction>
</xs:simpleType>

```

Enumeration

The following values are defined by the **PermissionLevelType** simple type:

Value	Description
None	The user has no permissions on the folder.
Owner	The user can create, read, edit, and delete all items in the folder, and create subfolders. The user is both folder owner and folder contact.
PublishingEditor	The user can create, read, edit, and delete all items in the folder, and create subfolders.
Editor	The user can create, read, edit, and delete all items in the folder.
PublishingAuthor	The user can create and read all items in the folder, edit and delete only items that the user creates, and create subfolders.
Author	The user can create and read all items in the folder, and edit and delete only items that the user creates.

Value	Description
NoneditingAuthor	The user can create and read all items in the folder, and delete only items that the user creates.
Reviewer	The user can read all items in the folder.
Contributor	The user can create items in the folder. The contents of the folder do not appear.
Custom	The user has custom access permissions on the folder.

2.2.2.4 t:PermissionReadAccessType Simple Type

The **PermissionReadAccessType** simple type enumeration specifies whether a user has permission to read items in a folder.

```
<xs:simpleType name="PermissionReadAccessType">
  <xs:restriction
    base="xs:string"
  >
    <xs:enumeration
      value="None"
    />
    <xs:enumeration
      value="FullDetails"
    />
  </xs:restriction>
</xs:simpleType>
```

Enumeration

The following values are defined by the **PermissionReadAccessType** simple type:

Value	Description
None	The user does not have permission to read items in the folder.
FullDetails	The user has permission to read all items in the folder.

2.2.3 Complex Types

The following XML schema complex types are specific to this operation.

ComplexType	Description
ArrayOfFoldersType	An array of t:FolderTypes , which determines the type of folder.
BaseMoveCopyFolderType	Base type for the CopyFolderType and MoveFolderType types.
BasePermissionType	Base type that defines base permissions for items and folders.
ArrayOfUnknownEntriesType	An array of unknown permission entries that cannot be resolved against the Active Directory directory service.

ComplexType	Description
BaseFolderIdType	The base element for derived elements that represent a folder identifier.
BaseFolderType	The element class for derived elements that represent a folder.
FolderChangeDescriptionType	Describes a change to a single folder property .
FolderChangeType	Represents a collection of changes to be performed on a single folder.
FolderInfoResponseMessageType	Represents the response message.
FolderType	Represents a regular folder in the server database.
ManagedFolderInformationType	Contains information about a managed custom folder.
PermissionSetType	Contains all the permissions that are configured for a folder.
PermissionType	Specifies a permission on a folder.
TargetFolderIdType	Represents a target folder for operations that create, save, copy, move, or synchronize items or folder.

2.2.3.1 t:ArrayOfFoldersType Complex Type

The [ArrayOfFoldersType](#) complex type specifies an array of [FolderTypes](#), which determines the type of folder.

```
<xs:complexType name="ArrayOfFoldersType">
  <xs:choice
    minOccurs="0"
    maxOccurs="unbounded"
  >
    <xs:element name="Folder"
      type="t:FolderType"
    />
    <xs:element name="CalendarFolder"
      type="t:CalendarFolderType"
    />
    <xs:element name="ContactsFolder"
      type="t:ContactsFolderType"
    />
    <xs:element name="SearchFolder"
      type="t:SearchFolderType"
    />
    <xs:element name="TasksFolder"
      type="t:TasksFolderType"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
Folder	t:FolderType	Represents a regular folder in the server database.
CalendarFolder	t:CalendarFolderType	Represents a folder that primarily contains calendar items.
ContactsFolder	t:ContactsFolderType	Represents a Contacts folder in a mailbox.
SearchFolder	t:SearchFolderType	Represents a Search folder that is contained in a mailbox.
TasksFolder	t:TasksFolderType	Represents a Tasks folder that is contained in a mailbox.

2.2.3.2 m:BaseMoveCopyFolderType Complex Type

The [BaseMoveCopyFolderType](#) complex type is the base type for the [CopyFolderType](#) and [MoveFolderType](#) types.

```
<xs:complexType name="BaseMoveCopyFolderType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    >
      <xs:sequence>
        <xs:element name="ToFolderId"
          type="t:TargetFolderIdType"
        />
        <xs:element name="FolderIds"
          type="t:NonEmptyArrayOfBaseFolderIdsType"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
ToFolderId	t:TargetFolderIdType	Represents a target folder for operations that create, save, copy, move, or synchronize items or folders.
FolderIds	t:NonEmptyArrayOfBaseFolderIdsType	Specifies an array of one or more folders.

2.2.3.3 t:BasePermissionType Complex Type

The [BasePermissionType](#) complex type is an abstract type that defines base permissions for items and folders.

```
<xs:complexType name="BasePermissionType"
  abstract="true"
>
  <xs:sequence>
    <xs:element name="UserId"
  >
```

```

        type="t:UserIdType"
      />
    <xs:element name="CanCreateItems"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="CanCreateSubFolders"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="IsFolderOwner"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="IsFolderVisible"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="IsFolderContact"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="EditItems"
      type="t:PermissionActionType"
      minOccurs="0"
    />
    <xs:element name="DeleteItems"
      type="PermissionActionType"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
UserId	t:UserIdType	Specifies a user identifier.
CanCreateItems	xs:boolean	A value that specifies whether a client can create items in a folder.
CanCreateSubFolders	xs:boolean	A value that specifies whether the client can create subfolders.
IsFolderOwner	xs:boolean	A value that specifies whether the user is the owner of a folder.
IsFolderVisible	xs:boolean	A value that specifies whether a user can view a folder.
IsFolderContact	xs:boolean	A value that specifies whether a user is a contact for a folder.
EditItems	t:PermissionActionType	A value that specifies whether a client can edit items.

Element	Type	Description
DeleteItems	PermissionActionType	A value that specifies whether the client can delete items.

2.2.3.4 t:ArrayOfUnknownEntriesType Complex Type

The [ArrayOfUnknownEntriesType](#) complex type represents an array of unknown permission entries that cannot be resolved against the directory service. The text value represents a security identifier (SID).

```
<xs:complexType name="ArrayOfUnknownEntriesType">
  <xs:choice
    minOccurs="0"
    maxOccurs="unbounded"
  >
    <xs:element name="UnknownEntry"
      type="xs:string"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
UnknownEntry	xs:string	Represents an array of unknown permission entries that cannot be resolved against the directory service.

2.2.3.5 t:BaseFolderIdType Complex Type

The [BaseFolderIdType](#) complex type specifies the base element for derived elements that represent a folder identifier. The **BaseFolderIdType** type MUST NOT be sent in a SOAP message since it is an abstract type.

```
<xs:complexType name="BaseFolderIdType"
  abstract="true"
/>
```

2.2.3.6 t:BaseFolderType Complex Type

The [BaseFolderType](#) complex type specifies the base type for folders. The [BaseFolderIdType](#) type MUST NOT be sent in a SOAP message since it is an abstract type.

```
<xs:complexType name="BaseFolderType"
  abstract="true"
>
  <xs:sequence>
    <xs:element name="FolderId"
      type="FolderIdType"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>
```

```

/>
<xs:element name="ParentFolderId"
  type="FolderIdType"
  minOccurs="0"
/>
<xs:element name="FolderClass"
  type="xs:string"
  minOccurs="0"
/>
<xs:element name="DisplayName"
  type="xs:string"
  minOccurs="0"
/>
<xs:element name="TotalCount"
  type="xs:int"
  minOccurs="0"
/>
<xs:element name="ChildFolderCount"
  type="xs:int"
  minOccurs="0"
/>
<xs:element name="ExtendedProperty"
  type="t:ExtendedPropertyType"
  minOccurs="0"
  maxOccurs="unbounded"
/>
<xs:element name="ManagedFolderInformation"
  type="ManagedFolderInformationType"
  minOccurs="0"
/>
<xs:element name="EffectiveRights"
  type="EffectiveRightsType"
  minOccurs="0"
/>
</xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
FolderId	FolderIdType	Specifies the folder identifier and change key.
ParentFolderId	FolderIdType	Specifies the parent folder identifier.
FolderClass	xs:string	Specifies the folder class. This value MUST be "IPF.Appointment" for calendar folders, "IPF.Contact" for contact folders, "IPF.Journal" for journal folders, "IPF.Note" for mail folders, "IPF.StickyNote" for note folders, "IPF.Task" for task folders. The folders class can be a custom class. The following example specifies how to set a custom folder class. "IPF. <folderclass>", where

Element	Type	Description
		<folderclass> is the name of the custom class.
DisplayName	xs:string	Specifies the folders display name.
TotalCount	xs:int	Specifies the total number of items in a folder. This property MUST be read-only for a client and is only returned in a response.
ChildFolderCount	xs:int	Specifies the total number of child folders in a folder. This property MUST be read-only for a client and is only returned in a response.
ExtendedProperty	t:ExtendedPropertyType	Specifies the set of extended properties on a folder.
ManagedFolderInformation	ManagedFolderInformationType	Specifies metadata for a managed folder. This property MUST be read-only for a client and is only returned in a response. This complex type is specified in [MS-OXWSFOLD] section 2.2.3.11.
EffectiveRights	EffectiveRightsType	Specifies the operations that the current logon user can perform on the folder. This property MUST be read-only for a client and is only returned in a response.

2.2.3.7 t:FolderChangeDescriptionType Complex Type

The [FolderChangeDescriptionType](#) complex type specifies a change to a single folder property.

```
<xs:complexType name="FolderChangeDescriptionType">
  <xs:complexContent>
    <xs:extension
      base="ChangeDescriptionType"
      />
  </xs:complexContent>
</xs:complexType>
```

2.2.3.8 t:FolderChangeType Complex Type

The [FolderChangeType](#) complex type specifies a collection of changes to be performed on a single folder.

```
<xs:complexType name="FolderChangeType">
  <xs:sequence>
    <xs:choice>
      <xs:element name="FolderId"
        type="FolderIdType"
        />
    </xs:choice>
  </xs:sequence>
</xs:complexType>
```

```

    <xs:element name="DistinguishedFolderId"
      type="DistinguishedFolderIdType"
    />
  </xs:choice>
  <xs:element name="Updates"
    type="NonEmptyArrayOfFolderChangeDescriptionsType"
  />
</xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
FolderId	FolderIdType	Specifies an identifier for a fully resolved folder.
DistinguishedFolderId	DistinguishedFolderIdType	Specifies an identifier for a distinguished folder.
Updates	NonEmptyArrayOfFolderChangeDescriptionsType	Specifies a collection of changes to a folder.

2.2.3.9 m:FolderInfoResponseType Complex Type

The [FolderInfoResponseType](#) complex type represents the response message for the [CreateFolder](#), [GetFolder](#), [UpdateFolder](#), [MoveFolder](#), [CopyFolder](#), and [CreateManagedFolder](#) operations.

```

<xs:complexType name="FolderInfoResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:ResponseType"
    >
    <xs:sequence>
      <xs:element name="Folders"
        type="t:ArrayOfFoldersType"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
Folders	t:ArrayOfFoldersType	Represents the response message.

2.2.3.10 t:FolderType Complex Type

The [FolderType](#) complex type represents a regular folder in the server database.

```
<xs:complexType name="FolderType">
  <xs:complexContent>
    <xs:extension
      base="t:BaseFolderType"
    >
      <xs:sequence>
        <xs:element name="PermissionSet"
          type="t:PermissionSetType"
          minOccurs="0"
        />
        <xs:element name="UnreadCount"
          type="xs:int"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
PermissionSet	t:PermissionSetType	Specifies all permissions that are configured for a folder.
UnreadCount	xs:int	Specifies the number of unread items in a folder. This element MUST only exist in responses and MUST equal the sum of all MessageType and PostItemtype item types that have the IsRead property set to false .

2.2.3.11 t:ManagedFolderInformationType Complex Type

The [t:ManagedFolderInformationType](#) complex type contains information about a managed custom folder.

```
<xs:complexType name="ManagedFolderInformationType">
  <xs:sequence>
    <xs:element name="CanDelete"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="CanRenameOrMove"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="MustDisplayComment"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="HasQuota"
      type="xs:boolean"
    />
  </xs:sequence>
</xs:complexType>
```

```

        minOccurs="0"
      />
    <xs:element name="IsManagedFoldersRoot"
      type="xs:boolean"
      minOccurs="0"
    />
    <xs:element name="ManagedFolderId"
      type="xs:string"
      minOccurs="0"
    />
    <xs:element name="Comment"
      type="xs:string"
      minOccurs="0"
    />
    <xs:element name="StorageQuota"
      type="xs:int"
      minOccurs="0"
    />
    <xs:element name="FolderSize"
      type="xs:int"
      minOccurs="0"
    />
    <xs:element name="HomePage"
      type="xs:string"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
CanDelete	xs:boolean	A value that indicates whether a managed folder can be deleted by a client.
CanRenameOrMove	xs:boolean	A value that indicates whether a managed folder can be renamed or moved by a client.
MustDisplayComment	xs:boolean	A value that indicates whether the managed folder comment must be displayed.
HasQuota	xs:boolean	A value that indicates whether a managed folder has a quota.
IsManagedFoldersRoot	xs:boolean	A value that indicates whether the managed folder is the root managed folder.
ManagedFolderId	xs:string	The unique identifier of a managed folder.
Comment	xs:string	A comment that is associated with a managed folder.
StorageQuota	xs:int	The storage quota for a managed folder.
FolderSize	xs:int	A value that describes the total size of all the contents of a managed folder.
HomePage	xs:string	The URL that is the default home page for the managed folder.

2.2.3.12 t:PermissionSetType Complex Type

The [PermissionSetType](#) complex type contains all the permissions that are configured for a folder. This constitutes the set of permissions on a folder.

```
<xs:complexType name="PermissionSetType">
  <xs:sequence>
    <xs:element name="Permissions"
      type="t:ArrayOfPermissionsType"
    />
    <xs:element name="UnknownEntries"
      type="t:ArrayOfUnknownEntriesType"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>
```

Child Elements

Element	Type
Permissions	t:ArrayOfPermissionsType
UnknownEntries	t:ArrayOfUnknownEntriesType

2.2.3.13 t:PermissionType Complex Type

The [PermissionType](#) complex type specifies a permission on a folder.

```
<xs:complexType>
  <xs:complexContent>
    <xs:extension
      base="t:BasePermissionType"
    >
    <xs:sequence>
      <xs:element name="ReadItems"
        type="t:PermissionReadAccessType"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="PermissionLevel"
        type="t:PermissionLevelType"
        maxOccurs="1"
        minOccurs="1"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
ReadItems	t:PermissionReadAccessType	Specifies whether a user has permission to read items in a folder.
PermissionLevel	t:PermissionLevelType	Specifies the combination of permissions that a user has on a folder.

2.2.3.14 t:TargetFolderIdType Complex Type

The [TargetFolderIdType](#) complex type specifies a target folder for operations that create, save, copy, move, or synchronize items or folders.

```
<xs:complexType name="TargetFolderIdType">
  <xs:choice>
    <xs:element name="FolderId"
      type="t:FolderIdType"
    />
    <xs:element name="DistinguishedFolderId"
      type="t:DistinguishedFolderIdType"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
FolderId	t:FolderIdType	Specifies a folder identifier.
DistinguishedFolderId	t:DistinguishedFolderIdType	Specifies a distinguished folder identifier.

2.2.4 Elements

This specification does not define any common XML schema element definitions.

2.2.5 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.6 Groups

This specification does not define any common XML schema group definitions.

2.2.7 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

2.2.8 Message Syntax

This specification does not define any common XML schema message definitions.

3 Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

3.1 ExchangeServicePortType Server Detail

The Folders and Folder Permissions Web Service Protocol has seven operations to manipulate folders.

Operation	Description
CreateFolder	Creates folders, calendar folders, contacts folders, tasks folders, and search folder.
DeleteFolder	Deletes folders from a mailbox.
UpdateFolder	Modifies properties of an existing item in the server store.
MoveFolder	Moves folders from a specified folder and puts them in another folder.
CopyFolder	Copies identified folders and returns the Id and ChangeKey of the copied folders.
GetFolder	Gets folders from the server store .
CreateManagedFolder	Creates a managed folder in the server store.

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that specified in this document.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing

This protocol includes the operations listed in the following table.

Operation	Description
CreateFolder	Creates folders, calendar folders, contacts folders, tasks folders, and search folders.
DeleteFolder	Deletes folders from a mailbox.
UpdateFolder	Modifies properties of an existing item in the server store.

Operation	Description
MoveFolder	Moves folders from a specified folder and puts them in another folder.
CopyFolder	Copies identified folders and returns the Id and ChangeKey of the copied folders.
GetFolder	Gets folders from the server store.
CreateManagedFolder	Creates a managed folder in the server store.

3.1.4.1 CopyFolder

The [CopyFolder](#) operation copies identified folders and returns the Id and ChangeKey of the copied folders.

Request

Message Format	Description
tns:CopyFolderSoapIn	Specifies the SOAP message that copies the folders.

Response

Message Format	Description
tns:CopyFolderSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.1.1 CopyFolder Simple Types

This specification does not define any specific XML schema simple types for this operation.

3.1.4.1.2 CopyFolder Complex Types

The following XML schema complex types are specific to this operation.

Type	Description
m:CopyFolderResponseType	Represents a response to a CopyFolder operation.
m:CopyFolderType	Represents an operation to copy folders in a server database.

3.1.4.1.2.1 m:CopyFolderResponseType Complex Type

The [CopyFolderResponseType](#) complex type represents a response to a [CopyFolder](#) operation.

```
<xs:complexType name="CopyFolderResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseResponseMessageType"
    />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.1.2.2 m:CopyFolderType Complex Type

The [m:CopyFolderType](#) complex type represents an operation to copy folders in a server database.

```
<xs:complexType name="CopyFolderType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseMoveCopyFolderType"
    />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.1.3 CopyFolder Elements

The following XML schema element definitions are specific to this operation.

Operation	Description
tns:CopyFolder	Defines a request to copy folders in a mailbox in the server store.
tns:CopyFolderResponse	Defines a response to a CopyFolder request.

3.1.4.1.3.1 CopyFolder Element

The [CopyFolder](#) element defines a request to copy folders in a mailbox in the server store.

```
<xs:element name="CopyFolder"
  type="m:CopyFolderType"
/>
```

3.1.4.1.3.2 CopyFolderResponse Element

The [CopyFolderResponse](#) element defines a response to a [CopyFolder](#) operation.

```
<xs:element name="CopyFolderResponse"
  type="m:CopyFolderResponseType"
/>
```

3.1.4.1.4 CopyFolder Attributes

This specification does not define any specific XML schema attribute definitions for this operation.

3.1.4.1.5 CopyFolder Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.1.6 CopyFolder Attribute Groups

This specification does not define any specific XML schema attribute group definitions for this operation.

3.1.4.1.7 CopyFolder Messages

The following **WSDL message** definitions are specific to this operation.

Messages	Description
tns:CopyFolderSoapIn	The request that copies a folder.
tns:CopyFolderSoapOut	The response from a copy folder request.

3.1.4.1.7.1 tns:CopyFolderSoapIn

The [CopyFolderSoapIn](#) message contains four parts.

Part Name	Element/Type	Description
request	tns:CopyFolder	This part specifies the request.
Impersonation	t:ExchangeImpersonation	The identifier of the account to impersonate.
MailboxCulture	t:MailboxCulture	This part specifies the culture to use for accessing the server. The cultures are defined by [RFC3066] .
RequestVersion	t:RequestServerVersion	This part specifies the schema version for the CopyFolder request.

3.1.4.1.7.2 tns:CopyFolderSoapOut

The [CopyFolderSoapOut](#) message contains two parts.

Part Name	Element/Type	Description
CopyFolderResult	tns:CopyFolderResponse	This part specifies the response.
ServerVersion	t:ServerVersionInfo	This part specifies the server version for the response.

3.1.4.2 CreateFolder

The [CreateFolder](#) operation creates folders, calendar folders, contacts folders, tasks folders, and search folders.

Request

Message Format	Description
tns:CreateFolderSoapIn	Specifies the SOAP message that creates the folders.

Response

Message Format	Description
tns:CreateFolderSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.2.1 CreateFolder Simple Types

This specification does not define any specific XML schema simple types for this operation.

3.1.4.2.2 CreateFolder Complex Types

The following XML schema complex types are specific to this operation.

Type	Description
m:CreateFolderResponseType	Represents a response to a CreateFolder operation.
m:CreateFolderType	Represents an operation to create folders in a server database.
t:NonEmptyArrayOfFoldersType	An array of folders that has at least one member.

3.1.4.2.2.1 t:CreateFolderResponseType Complex Type

The [CreateFolderResponseType](#) complex type represents a response to a [CreateFolder](#) operation.

```
<xs:complexType name="CreateFolderResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseResponseMessageType"
      />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.2.2.2 m:CreateFolderType Complex Type

The [CreateFolderType](#) complex type represents a request to create a folder.

```
<xs:complexType name="CreateFolderType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
      >
      <xs:sequence>
        <xs:element name="ParentFolderId"
          type="t:TargetFolderIdType"
          />
        <xs:element name="Folders"
          type="t:NonEmptyArrayOfFoldersType"
          />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
ParentFolderId	t:TargetFolderIdType	The identifier of the folder that will contain the newly created folder.
Folders	t:NonEmptyArrayOfFoldersType	Represents a target folder for operations that create, save, copy, move, or synchronize items or folder.

3.1.4.2.2.3 t:NonEmptyArrayOfFoldersType Complex Type

The [NonEmptyArrayOfFoldersType](#) represents an array of folders that has at least one member.

```
<xs:complexType name="NonEmptyArrayOfFoldersType">
  <xs:choice
    maxOccurs="unbounded"
  >
    <xs:element name="Folder"
      type="t:FolderType"
    />
    <xs:element name="CalendarFolder"
      type="t:CalendarFolderType"
    />
    <xs:element name="ContactsFolder"
      type="t:ContactsFolderType"
    />
    <xs:element name="SearchFolder"
      type="t:SearchFolderType"
    />
    <xs:element name="TasksFolder"
      type="t:TasksFolderType"
    />
  </xs:choice>
</xs:complexType>
```

Child Elements

Element	Type	Description
Folder	t:FolderType	Represents a regular folder in the server database.
CalendarFolder	t:CalendarFolderType	Represents a folder that primarily contains calendar items.
ContactsFolder	t:ContactsFolderType	Represents a Contacts folder in a mailbox.
SearchFolder	t:SearchFolderType	Represents a search folder that is contained in a mailbox.
TasksFolder	t:TasksFolderType	Represents a Tasks folder that is contained in a mailbox.

3.1.4.2.3 CreateFolder Elements

The following XML schema element definitions are specific to this operation.

Operation	Description
tns:CreateFolder	Defines a request to create folders in a mailbox in the server store.
tns:CreateFolderResponse	Defines a response to a CreateFolder request.

3.1.4.2.3.1 CreateFolder Element

The [CreateFolder](#) element defines a request to create a folder in a mailbox in the server store.

```
<xs:element name="CreateFolder"
  type="m:CreateFolderType"
 />
```

3.1.4.2.3.2 CreateFolderResponse Element

The [CreateFolderResponse](#) element defines a response to a [CreateFolder](#) request.

```
<xs:element name="CreateFolderResponse"
  type="m:CreateFolderResponseType"
 />
```

3.1.4.2.4 CreateFolder Attributes

This specification does not define any specific XML schema attribute definitions for this operation.

3.1.4.2.5 CreateFolder Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.2.6 CreateFolder Attribute Groups

This specification does not define any specific XML schema attribute group definitions for this operation.

3.1.4.2.7 CreateFolder Messages

The following WSDL message definitions are specific to this operation.

Messages	Description
tns:CreateFolderSoapIn	The request that creates a folder.
tns:CreateFolderSoapOut	The response from a create folder request.

3.1.4.2.7.1 tns:CreateFolderSoapIn

The [CreateFolderSoapIn](#) message contains five parts.

Part Name	Element/Type	Description
request	tns:CreateFolder	This part specifies the request.
Impersonation	t:ExchangeImpersonation	The identifier of the account to impersonate.
MailboxCulture	t:MailboxCulture	This part specifies the culture to use for accessing the server. The cultures are defined by [RFC 3066] .
RequestVersion	t:RequestServerVersion	This part specifies the schema version for the CreateFolder request.
TimeZoneContext	t:TimeZoneContext	Specifies a time zone definition and enables associating SOAP attributes with the definition.

3.1.4.2.7.2 tns:CreateFolderSoapOut

The [CreateFolderSoapOut](#) message contains two parts.

Part Name	Element/Type	Description
CreateFolderResult	tns:CreateFolderResponse	This part specifies the response.
ServerVersion	t:ServerVersionInfo	This part specifies the server version for the response.

3.1.4.3 CreateManagedFolder

The [CreateManagedFolder](#) operation creates a managed folder in the server store.

Request

Message Format	Description
tns:CreateManagedFolderSoapIn	Specifies the SOAP message that creates the managed folder.

Response

Message Format	Description
tns:CreateManagedFolderSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.3.1 CreateFolder Simple Types

This specification does not define any specific XML schema simple types for this operation.

3.1.4.3.2 CreateManagedFolder Complex Types

The following XML schema complex types are specific to this operation.

Type	Description
m:CreateManagedFolderRequestType	Represents an operation to create a managed folder in a server database.
m:CreateManagedFolderResponseType	Represents a response to a CreateManagedFolder operation.
t:NonEmptyArrayOfFolderNamesType	An array of named managed folders in a mailbox that has at least one member.

3.1.4.3.2.1 m:CreateManagedFolderRequestType Complex Type

The [CreateManagedFolderRequestType](#) complex type represents an operation to create a managed folder in a server database.

```
<xs:complexType name="CreateManagedFolderRequestType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    >
      <xs:sequence>
        <xs:element name="FolderNames"
          type="t:NonEmptyArrayOfFolderNamesType"
        />
        <xs:element name="Mailbox"
          type="t:EmailAddressType"
          minOccurs="0"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Child Elements

Element	Type	Description
FolderNames	t:NonEmptyArrayOfFolderNamesType	An array of managed folders to add to a mailbox. This array has at least one member.
Mailbox	t:EmailAddressType	The e-mail address of the mailbox in which the managed folders are added.

3.1.4.3.2.2 m:CreateManagedFolderResponseType Complex Type

The [m:CreateManagedFolderResponseType](#) complex type represents a response to a [CreateManagedFolder](#) operation.

```
<xs:complexType name="CreateManagedFolderResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseResponseMessageType"
    />
  </xs:complexContent>
</xs:complexType>
```

```

</xs:complexContent>
</xs:complexType>

```

3.1.4.3.2.3 t:NonEmptyArrayOfFolderNamesType Complex Type

The [NonEmptyArrayOfFolderNamesType](#) complex type represents an array of named managed folders in a mailbox that has at least one member.

```

<xs:complexType name="NonEmptyArrayOfFolderNamesType">
  <xs:sequence>
    <xs:element name="FolderName"
      type="xs:string"
      maxOccurs="unbounded"
    />
  </xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type
FolderName	xs:string

3.1.4.3.3 CreateManagedFolder Elements

The following **XML Schema** element definitions are specific to this operation.

Operation	Description
tns:CreateManagedFolder	Defines a request to add a managed folder to a mailbox in the server store.
tns:CreateManagedFolderResponse	Defines a response to a CreateManagedFolder request.

3.1.4.3.3.1 CreateManagedFolder Element

The [CreateManagedFolder](#) element defines a request to create a managed folder in a mailbox in the server store.

```

<xs:element name="CreateManagedFolder"
  type="m:CreateManagedFolderRequestType"
/>

```

3.1.4.3.3.2 CreateManagedFolderResponse Element

The [CreateManagedFolderResponse](#) element defines a response to a [CreateManagedFolder](#) request.

```

<xs:element name="CreateManagedFolderResponse"

```

```

type="m:CreateManagedFolderResponseType"
/>

```

3.1.4.3.4 CreateManagedFolder Attributes

This specification does not define any specific XML schema attribute definitions for this operation.

3.1.4.3.5 CreateManagedFolder Group

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.3.6 CreateManagedFolder Attribute Groups

This specification does not define any specific XML schema attribute group definitions for this operation.

3.1.4.3.7 CreateManagedFolder Messages

The following **WSDL message** definitions are specific to this operation.

Messages	Description
tns:CreateManagedFolderSoapIn	The request that creates a managed folder.
tns:CreateManagedFolderSoapOut	The response from a create managed folder request.

3.1.4.3.7.1 tns:CreateManagedFolderSoapIn

The [CreateManagedFolderSoapIn](#) message contains four parts.

Part Name	Element/Type	Description
request	tns:CreateManagedFolder	This part specifies the request.
Impersonation	t:ExchangeImpersonation	The identifier of the account to impersonate.
MailboxCulture	t:MailboxCulture	This part specifies the culture to use for accessing the server. The cultures are defined by [RFC3066] .
RequestVersion	t:RequestServerVersion	This part specifies the schema version for the CreateManagedFolder request.

3.1.4.3.7.2 tns:CreateManagedFolderSoapOut

The [CreateManagedFolderSoapOut](#) message contains two parts.

Part Name	Element/Type	Description
CreateManagedFolderResult	tns:CreateManagedFolderResponse	This part specifies the response.
ServerVersion	t:ServerVersionInfo	This part specifies the server version for the response.

3.1.4.4 DeleteFolder

The [DeleteFolder](#) operation deletes folders from a mailbox. Use the **DeleteFolder** operation to delete unmanaged folders and managed folders. You cannot delete default folders, such as the Inbox or Deleted Items folders, by using this operation.

Request

Message Format	Description
tns:DeleteFolderSoapIn	Specifies the SOAP message that deletes a folder.

Response

Message Format	Description
tns:DeleteFolderSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.4.1 CreateManagedFolder Simple Types

This specification does not define any specific XML schema simple types for this operation.

3.1.4.4.2 DeleteFolder Complex Types

The following XML schema complex types are specific to this operation.

Type	Description
m:DeleteFolderResponseType	Represents an operation to delete a folder in a server database.
m:DeleteFolderType	Represents a response to a DeleteFolder operation.

3.1.4.4.2.1 m:DeleteFolderResponseType Complex Type

The [DeleteFolderResponseType](#) complex type represents a response to a [DeleteFolder](#) operation.

```
<xs:complexType name="DeleteFolderResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseResponseMessageType"
    />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.4.2.2 m:DeleteFolderType Complex Type

The [DeleteFolderType](#) complex type represents a request to delete folders from a mailbox.

```
<xs:complexType name="DeleteFolderType">
  <xs:complexContent>
    <xs:extension
```

```

    base="m:BaseRequestType"
  >
    <xs:sequence>
      <xs:element name="FolderIds"
        type="t:NonEmptyArrayOfBaseFolderIdsType"
      />
    </xs:sequence>
    <xs:attribute name="DeleteType"
      type="t:DisposalType"
      use="required"
    />
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type
FolderIds	t:NonEmptyArrayOfBaseFolderIdsType

Attributes

Name	Type
DeleteType	t:DisposalType

3.1.4.4.3 DeleteFolder Elements

The following XML schema element definitions are specific to this operation.

Operation	Description
tns:DeleteFolder	Defines a request to delete a folder from a mailbox in the server store.
tns:DeleteFolderResponse	Defines a response to a DeleteFolder request.

3.1.4.4.3.1 DeleteFolder Element

The [DeleteFolder](#) element defines a request to delete a folder from a mailbox in the server store.

```

<xs:element name="DeleteFolder"
  type="m:DeleteFolderType"
/>

```

3.1.4.4.3.2 DeleteFolderResponse Element

The [DeleteFolderResponse](#) element represents a response to a [DeleteFolder](#) operation.

```

<xs:element name="DeleteFolderResponse"
  type="m:DeleteFolderResponseType"

```

/>

3.1.4.4.4 DeleteFolder Attributes

This specification does not define any specific XML schema attribute definitions for this operation.

3.1.4.4.5 DeleteFolder Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.4.6 DeleteFolder Attribute Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.4.7 DeleteFolder Messages

The following WSDL message definitions are specific to this operation.

Messages	Description
tns:DeleteFolderSoapIn	The request that deletes a folder.
tns:DeleteFolderSoapOut	The response from a delete folder request.

3.1.4.4.7.1 tns:DeleteFolderSoapIn

The [DeleteFolderSoapIn](#) message contains four parts.

Part Name	Element/Type	Description
request	tns:DeleteFolder	This part specifies the request.
Impersonation	t:ExchangeImpersonation	The identifier of the account to impersonate.
MailboxCulture	t:MailboxCulture	This part specifies the culture to use for accessing the server. The cultures are defined by [RFC3066] .
RequestVersion	t:RequestServerVersion	This part specifies the schema version for the DeleteFolder request.

3.1.4.4.7.2 tns:DeleteFolderSoapOut

The [DeleteFolderSoapOut](#) message contains two parts.

Part Name	Element/Type	Description
DeleteFolderResult	tns:DeleteFolderResponse	This part specifies the response.
ServerVersion	t:ServerVersionInfo	This part specifies the server version for the response.

3.1.4.5 GetFolder

The [GetFolder](#) operation creates folders, calendar folders, contacts folders, tasks folders, and search folders.

Request

Message Format	Description
tns:GetFolderSoapIn	Specifies the SOAP message that gets folders from the server store.

Response

Message Format	Description
tns:GetFolderSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.5.1 GetFolder Simple Types

This specification does not define any specific XML schema simple types for this operation.

3.1.4.5.2 GetFolder Complex Types

The following XML schema complex types are specific to this operation.

Type	Description
m:GetFolderResponseType	Represents a response to a GetFolder operation.
m:GetFolderType	Represents an operation to get a folder in a server database.
t:NonEmptyArrayOfBaseFolderIdsType	Specifies an array of one or more folders.

3.1.4.5.2.1 m:GetFolderResponseType Complex Type

The [GetFolderResponseType](#) complex type represents a response to a [GetFolder](#) operation.

```
<xs:complexType name="GetFolderResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseResponseMessageType"
    />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.5.2.2 m:GetFolderType Complex Type

The [GetFolderType](#) complex type represents an operation to get a folder in a server database.

```
<xs:complexType name="GetFolderType">
  <xs:complexContent>
    <xs:extension
```

```

    base="m:BaseRequestType"
  >
    <xs:sequence>
      <xs:element name="FolderShape"
        type="t:FolderResponseShapeType"
      />
      <xs:element name="FolderIds"
        type="t:NonEmptyArrayOfBaseFolderIdsType"
      />
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type
FolderShape	t:FolderResponseShapeType
FolderIds	t:NonEmptyArrayOfBaseFolderIdsType

3.1.4.5.2.3 t:NonEmptyArrayOfBaseFolderIdsType Complex Type

The [NonEmptyArrayOfBaseFolderIdsType](#) complex type specifies an array of one or more folders.

```

<xs:complexType>
  <xs:choice
    maxOccurs="unbounded"
  >
    <xs:element name="FolderId"
      type="t:FolderIdType"
    />
    <xs:element name="DistinguishedFolderId"
      type="t:DistinguishedFolderIdType"
    />
  </xs:choice>
</xs:complexType>

```

Child Elements

Element	Type	Description
FolderId	t:FolderIdType	Identifies a folder.
DistinguishedFolderId	t:DistinguishedFolderIdType	Specifies a distinguished folder identifier.

3.1.4.5.3 GetFolder Elements

The following XML schema element definitions are specific to this operation.

Operation	Description
tns:GetFolder	Defines a request to get a folder from a mailbox in the server store.
tns:GetFolderResponse	Defines a response to a GetFolder request.

3.1.4.5.3.1 GetFolder Element

The [GetFolder](#) element defines a request to get a folder from a mailbox in the server store.

```
<xs:element name="GetFolder"
  type="m:GetFolderType"
 />
```

3.1.4.5.3.2 GetFolderResponse Element

The [GetFolderResponse](#) element represents a response to a [GetFolder](#) request.

```
<xs:element name="GetFolderResponse"
  type="m:GetFolderResponseType"
 />
```

3.1.4.5.4 GetFolder Attributes

This specification does not define any specific XML schema attribute definitions for this operation.

3.1.4.5.5 GetFolder Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.5.6 GetFolder Attribute Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.5.7 GetFolder Messages

The following WSDL message definitions are specific to this operation.

Messages	Description
tns:GetFolderSoapIn	The request that gets a folder.
tns:GetFolderSoapOut	The response from a get folder request.

3.1.4.5.7.1 tns:GetFolderSoapIn

The [GetFolderSoapIn](#) message contains five parts.

Part Name	Element/Type	Description
request	tns:GetFolder	This part specifies the request.
Impersonation	t:ExchangeImpersonation	The identifier of the account to impersonate.
MailboxCulture	t:MailboxCulture	This part specifies the culture to use for accessing the server. The cultures are defined by [RFC 3066] .
RequestVersion	t:RequestServerVersion	This part specifies the schema version for the GetFolder request.
TimeZoneContext	t:TimeZoneContext	Specifies a time zone definition and enables associating SOAP attributes with the definition.

3.1.4.5.7.2 tns:GetFolderSoapOut

The [tns:GetFolderSoapOut](#) message contains two parts.

Part Name	Element/Type	Description
GetFolderResult	tns:GetFolderResponse	This part specifies the response message.
ServerVersion	t:ServerVersionInfo	This part specifies the server version for the response.

3.1.4.6 MoveFolder

The [MoveFolder](#) operation moves folders from a specified folder and puts them in another folder.

Request

Message Format	Description
tns:MoveFolderSoapIn	Specifies the SOAP message that moves folders from a specified folder and puts them in another folder.

Response

Message Format	Description
tns:MoveFolderSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.6.1 MoveFolder Simple Types

This specification does not define any specific XML schema simple types for this operation.

3.1.4.6.2 MoveFolder Complex Types

The following XML schema complex types are specific to this operation.

Type	Description
m:MoveFolderResponseType	Represents a response to a MoveFolder operation.

Type	Description
m:MoveFolderType	Represents an operation to move a folder in a mailbox.

3.1.4.6.2.1 m:MoveFolderResponseType Complex Type

The [MoveFolderResponseType](#) complex type represents a response to a [MoveFolder](#) operation.

```
<xs:complexType name="MoveFolderResponseType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseResponseMessageType"
    />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.6.2.2 m:MoveFolderType Complex Type

The [MoveFolderType](#) complex type represents an operation to move folders in a mailbox.

```
<xs:complexType name="MoveFolderType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseMoveCopyFolderType"
    />
  </xs:complexContent>
</xs:complexType>
```

3.1.4.6.3 MoveFolder Elements

The following XML schema element definitions are specific to this operation.

Operation	Description
tns:MoveFolder	Defines a request to move a folder in the server store.
tns:MoveFolderResponse	Defines a response to a MoveFolder request.

3.1.4.6.3.1 MoveFolder Element

The [MoveFolder](#) element defines a request to move a folder in the server store.

```
<xs:element name="MoveFolder"
  type="m:MoveFolderType"
/>
```

3.1.4.6.3.2 MoveFolderResponse Element

The [MoveFolderResponse](#) element represents a response to a [MoveFolder](#) request.

```
<xs:element name="MoveFolderResponse"
  type="m:MoveFolderResponseType"
/>
```

3.1.4.6.4 MoveFolder Attributes

This specification does not define any specific XML schema attribute definitions for this operation.

3.1.4.6.5 MoveFolder Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.6.6 MoveFolder Attribute Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.6.7 MoveFolder Messages

The following WSDL message definitions are specific to this operation.

Messages	Description
tns:MoveFolderSoapIn	The request that moves a folder.
tns:MoveFolderSoapOut	The response from a move folder request.

3.1.4.6.7.1 tns:MoveFolderSoapIn

The [MoveFolderSoapIn](#) message contains four parts.

Part Name	Element/Type	Description
request	tns:MoveFolder	This part specifies the request.
Impersonation	t:ExchangeImpersonation	The identifier of the account to impersonate.
MailboxCulture	t:MailboxCulture	This part specifies the culture to use for accessing the server. The cultures are defined by [RFC3066] .
RequestVersion	t:RequestServerVersion	This part specifies the schema version for the MoveFolder request.

3.1.4.6.7.2 tns:MoveFolderSoapOut

The [MoveFolderSoapOut](#) message contains two parts.

Part Name	Element/Type	Description
MoveFolderResult	tns:MoveFolderResponse	This part specifies the response message.
ServerVersion	t:ServerVersionInfo	This part specifies the server version for the response.

3.1.4.7 UpdateFolder

The [UpdateFolder](#) operation modifies properties of an existing item in the server store.

Request

Message Format	Description
tns:UpdateFolderSoapIn	Specifies the SOAP message that requests the properties of an existing item in the server store.

Response

Message Format	Description
tns:UpdateFolderSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.7.1 UpdateFolder Simple Types

This specification does not define any specific XML schema simple types for this operation.

3.1.4.7.2 UpdateFolder Complex Types

The following XML schema complex types are specific to this operation.

Type	Description
m:UpdateFolderResponseType	Represents a response to an UpdateFolder operation.
m:UpdateFolderType	Represents a request to update folders in a mailbox.
t:AppendToFolderFieldType	Do not use. This complex type is not implemented.
t>DeleteFolderFieldType	Represents an UpdateFolder operation to delete a property from a folder.
t:NonEmptyArrayOfFolderChangeDescriptionsType	An array of t:ChangeDescriptionTypes that has at least one member.
t:NonEmptyArrayOfFolderChangesType	An array of t:FolderChangeTypes that has at least one member.
t:SetFolderFieldType	Represents an UpdateFolder operation to set a property on an existing folder.

3.1.4.7.2.1 m:UpdateFolderResponseType Complex Type

The [UpdateFolderResponseType](#) complex type represents a response to an [UpdateFolder](#) operation.

```
<xs:complexType name="UpdateFolderResponseType">
  <xs:complexContent>
```

```

    <xs:extension
      base="m:BaseResponseMessageType"
    />
  </xs:complexContent>
</xs:complexType>

```

3.1.4.7.2.2 m:UpdateFolderType Complex Type

The [m:UpdateFolderType](#) complex type represents an operation to update folders in a mailbox.

```

<xs:complexType name="UpdateFolderType">
  <xs:complexContent>
    <xs:extension
      base="m:BaseRequestType"
    >
      <xs:sequence>
        <xs:element name="FolderChanges"
          type="t:NonEmptyArrayOfFolderChangesType"
        />
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type
FolderChanges	t:NonEmptyArrayOfFolderChangesType

3.1.4.7.2.3 t:AppendToFolderFieldType Complex Type

The [AppendToFolderFieldType](#) complex type is not implemented. Any request that uses this complex type will always return an error response.

```

<xs:complexType name="AppendToFolderFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:FolderChangeDescriptionType"
    >
      <xs:sequence>
        <xs:choice>
          <xs:element name="Folder"
            type="t:FolderType"
          />
          <xs:element name="CalendarFolder"
            type="t:CalendarFolderType"
          />
          <xs:element name="ContactsFolder"
            type="t:ContactsFolderType"
          />
          <xs:element name="SearchFolder"
            type="t:SearchFolderType"
          />
        </xs:choice>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

```

        />
        <xs:element name="TasksFolder"
            type="t:TasksFolderType"
        />
    </xs:choice>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
Folder	t:FolderType	Represents a regular folder in the server database.
CalendarFolder	t:CalendarFolderType	Represents a folder that primarily contains calendar items.
ContactsFolder	t:ContactsFolderType	Represents a Contacts folder in a mailbox.
SearchFolder	t:SearchFolderType	Represents a search folder that is contained in a mailbox.
TasksFolder	t:TasksFolderType	Represents a Tasks folder that is contained in a mailbox.

3.1.4.7.2.4 t:DeleteFolderFieldType Complex Type

The [DeleteFolderFieldType](#) complex type represents an [UpdateFolder](#) operation to delete a property from a folder.

```

<xs:complexType name="DeleteFolderFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:FolderChangeDescriptionType"
    >
      <xs:sequence />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

3.1.4.7.2.5 t:NonEmptyArrayOfFolderChangeDescriptionsType Complex Type

The [NonEmptyArrayOfFolderChangeDescriptionsType](#) complex type is an array of [t:ChangeDescriptionTypes](#) that has at least one member. The [t:FolderChangeDescriptionType](#) members describe a change to a single folder property.

```

<xs:complexType name="NonEmptyArrayOfFolderChangeDescriptionsType">
  <xs:choice
    maxOccurs="unbounded"
  >
    <xs:element name="AppendToFolderField"
      type="t:AppendToFolderFieldType"
    />
    <xs:element name="SetFolderField"

```

```

        type="t:SetFolderFieldType"
      />
    <xs:element name="DeleteFolderField"
      type="t:DeleteFolderFieldType"
    />
  </xs:choice>
</xs:complexType>

```

Child Elements

Element	Type	Description
AppendToFolderField	t:AppendToFolderFieldType	Do not use. This complex type is not implemented.
SetFolderField	t:SetFolderFieldType	Represents an UpdateFolder operation to set a property on an existing folder.
DeleteFolderField	t>DeleteFolderFieldType	Represents an UpdateFolder operation to delete a property from a folder.

3.1.4.7.2.6 t:NonEmptyArrayOfFolderChangesType Complex Type

The [NonEmptyArrayOfFolderChangesType](#) complex type represents an array of [t:FolderChangeTypes](#) that has at least one member. The **t:FolderChangeType** type represents a collection of changes to be performed on a single folder.

```

<xs:complexType name="NonEmptyArrayOfFolderChangesType">
  <xs:sequence>
    <xs:element name="FolderChange"
      type="t:FolderChangeType"
      maxOccurs="unbounded"
    />
  </xs:sequence>
</xs:complexType>

```

Child Elements

Element	Type	Description
FolderChange	t:FolderChangeType	Represents a collection of changes to be performed on a single folder.

3.1.4.7.2.7 t:SetFolderFieldType Complex Type

The [t:SetFolderFieldType](#) complex type represents an [UpdateFolder](#) operation to set a property on an existing folder.

```

<xs:complexType name="SetFolderFieldType">
  <xs:complexContent>
    <xs:extension
      base="t:FolderChangeDescriptionType"
    />
  </xs:complexContent>
</xs:complexType>

```



```

>
  <xs:choice>
    <xs:element name="Folder"
      type="t:FolderType"
    />
    <xs:element name="CalendarFolder"
      type="t:CalendarFolderType"
    />
    <xs:element name="ContactsFolder"
      type="t:ContactsFolderType"
    />
    <xs:element name="SearchFolder"
      type="t:SearchFolderType"
    />
    <xs:element name="TasksFolder"
      type="t:TasksFolderType"
    />
  </xs:choice>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

Child Elements

Element	Type	Description
Folder	t:FolderType	Represents a regular folder in the server database.
CalendarFolder	t:CalendarFolderType	Represents a folder that primarily contains calendar items.
ContactsFolder	t:ContactsFolderType	Represents a Contacts folder in a mailbox.
SearchFolder	t:SearchFolderType	Represents a search folder that is contained in a mailbox.
TasksFolder	t:TasksFolderType	Represents a Tasks folder that is contained in a mailbox.

3.1.4.7.3 UpdateFolder Elements

The following XML schema element definitions are specific to this operation.

Operation	Description
tns:UpdateFolder	Defines a request to update a folder in the server store.
tns:UpdateFolderResponse	Defines a response to an UpdateFolder request.

3.1.4.7.3.1 UpdateFolder Element

The [UpdateFolder](#) element defines a request to update a folder in the server store.

```

<xs:element name="UpdateFolder"
  type="m:UpdateFolderType"
/>

```

3.1.4.7.3.2 UpdateFolderResponse Element

The [UpdateFolderResponse](#) element represents a response to an [UpdateFolder](#) request.

```
<xs:element name="UpdateFolderResponse"
  type="m:UpdateFolderResponseType"
/>
```

3.1.4.7.4 UpdateFolder Attributes

This specification does not define any specific XML schema attribute definitions for this operation.

3.1.4.7.5 UpdateFolder Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.7.6 UpdateFolder Attribute Groups

This specification does not define any specific XML schema group definitions for this operation.

3.1.4.7.7 UpdateFolder Messages

The following WSDL message definitions are specific to this operation.

Messages	Description
tns:UpdateFolderSoapIn	The request that updates a folder.
tns:UpdateFolderSoapOut	The response from an update folder request.

3.1.4.7.7.1 tns:UpdateFolderSoapIn

The [UpdateFolderSoapIn](#) message contains five parts.

Part Name	Element/Type	Description
request	tns:UpdateFolder	This part specifies the request.
Impersonation	t:ExchangeImpersonation	The identifier of the account to impersonate.
MailboxCulture	t:MailboxCulture	This part specifies the culture to use for accessing the server. The cultures are defined by [RFC 3066] .
RequestVersion	t:RequestServerVersion	This part specifies the schema version for the UpdateFolder request.
TimeZoneContext	t:TimeZoneContext	Specifies a time zone definition and enables associating SOAP attributes with the definition.

3.1.4.7.7.2 tns:UpdateFolderSoapOut

The [MoveFolderSoapOut](#) message contains two parts.

Part Name	Element/Type	Description
UpdateFolderResult	tns:UpdateFolderResponse	This part specifies the response message.
ServerVersion	t:ServerVersionInfo	This part specifies the server version for the response.

3.1.5 Server Timer Events

None.

3.1.6 Server Other Local Events

None.

3.2 Client Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results that are returned by the transport are passed directly back to the higher-layer protocol or application.

3.2.1 Abstract Data Model

None.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Message Processing Events and Sequencing

None.

3.2.5 Timer Events

None.

3.2.6 Other Local Events

None.

4 Protocol Examples

None.

PRELIMINARY

5 Security

5.1 Security Considerations for Implementers

The Folders and Folder Permissions Web service does not use additional security mechanisms.

5.2 Index of Security Parameters

None.

PRELIMINARY

6 Appendix A: Full WSDL

The following table lists the **XML** files that are required to implement the functionality that is specified in this document. The contents of each file are included in this section.

Section	File name	Description
WSDL	MS-OXWSFOLD.wsdl	Contains the WSDL for the implementation of this protocol.
Types Schema	MS-OXWSFOLD-types.xsd	Contains the XML schema type definitions that are used in this protocol.
Messages Schema	MS-OXWSFOLD-messages.xsd	Contains the XML schema message definitions that are used in this protocol.

These files need to be placed in a common folder for the WSDL to validate and operate. Also, any schema files that are included in or imported into the MS-OXWSFOLD-types.xsd or MS-OXWSFOLD-messages.xsd schemas need to be placed in the common folder with the files.

6.1 Messages Schema

This section contains the contents of the MS-OXWSFOLD-messages.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSFOLD-types.xsd includes the file listed in the following table. For the schema file to operate correctly, this file needs to be in the folder that contains the WSDL, types schema, and messages schema files for this protocol.

Defining specification	File name
[MS-OXWSCDATA] , section 6.2	MS-OXWSCDATA -messages.xsd

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
  elementFormDefault="qualified" version="Exchange2010" id="messages">
  <xs:import namespace="http://schemas.microsoft.com/exchange/services/2006/types"
    schemaLocation="MS-OXWSFOLD-TYPES.xsd" />
  <xs:include schemaLocation="MS-OXWSCDATA-messages.xsd" />
  <xs:complexType name="BaseMoveCopyFolderType">
    <xs:complexContent>
      <xs:extension base="m:BaseRequestType">
        <xs:sequence>
          <xs:element name="ToFolderId" type="t:TargetFolderIdType" />
          <xs:element name="FolderIds"
            type="t:NonEmptyArrayOfBaseFolderIdsType" />
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="CopyFolder" type="m:CopyFolderType" />
  <xs:complexType name="CopyFolderType">
    <xs:complexContent>
```

```

        <xs:extension base="m:BaseMoveCopyFolderType" />
    </xs:complexContent>
</xs:complexType>
<xs:element name="CopyFolderResponse" type="m:CopyFolderResponseType"/>
<xs:complexType name="CopyFolderResponseType">
    <xs:complexContent>
        <xs:extension base="m:BaseResponseMessageType" />
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="CreateFolderResponseType">
    <xs:complexContent>
        <xs:extension base="m:BaseResponseMessageType" />
    </xs:complexContent>
</xs:complexType>
<xs:element name="CreateFolderResponse" type="m:CreateFolderResponseType"/>
<xs:complexType name="CreateFolderType">
    <xs:complexContent>
        <xs:extension base="m:BaseRequestType">
            <xs:sequence>
                <xs:element name="ParentFolderId" type="t:TargetFolderIdType"/>
                <xs:element name="Folders" type="t:NonEmptyArrayOfFoldersType"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="CreateFolder" type="m:CreateFolderType"/>
<xs:complexType name="CreateManagedFolderRequestType">
    <xs:complexContent>
        <xs:extension base="m:BaseRequestType">
            <xs:sequence>
                <xs:element name="FolderNames"
type="t:NonEmptyArrayOfFolderNamesType"/>
                <xs:element name="Mailbox" type="t:EmailAddressType" minOccurs="0"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="CreateManagedFolder" type="m:CreateManagedFolderRequestType"/>
<xs:complexType name="CreateManagedFolderResponseType">
    <xs:complexContent>
        <xs:extension base="m:BaseResponseMessageType" />
    </xs:complexContent>
</xs:complexType>
<xs:element name="CreateManagedFolderResponse"
type="m:CreateManagedFolderResponseType"/>
<xs:complexType name="DeleteFolderType">
    <xs:complexContent>
        <xs:extension base="m:BaseRequestType">
            <xs:sequence>
                <xs:element name="FolderIds"
type="t:NonEmptyArrayOfBaseFolderIdsType"/>
            </xs:sequence>
            <xs:attribute name="DeleteType" type="t:DisposalType" use="required"/>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="DeleteFolder" type="m:DeleteFolderType"/>
<xs:complexType name="DeleteFolderResponseType">
    <xs:complexContent>

```

```

        <xs:extension base="m:BaseResponseMessageType"/>
    </xs:complexContent>
</xs:complexType>
<xs:element name="DeleteFolderResponse" type="m:DeleteFolderResponseType"/>
<xs:complexType name="FolderInfoResponseMessageType">
    <xs:complexContent>
        <xs:extension base="m:ResponseMessageType">
            <xs:sequence>
                <xs:element name="Folders" type="t:ArrayOfFoldersType"
minOccurs="0"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="GetFolderType">
    <xs:complexContent>
        <xs:extension base="m:BaseRequestType">
            <xs:sequence>
                <xs:element name="FolderShape" type="t:FolderResponseShapeType"/>
                <xs:element name="FolderIds"
type="t:NonEmptyArrayOfBaseFolderIdsType"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="GetFolder" type="m:GetFolderType"/>
<xs:complexType name="GetFolderResponseType">
    <xs:complexContent>
        <xs:extension base="m:BaseResponseMessageType"/>
    </xs:complexContent>
</xs:complexType>
<xs:element name="GetFolderResponse" type="m:GetFolderResponseType"/>
<xs:complexType name="MoveFolderResponseType">
    <xs:complexContent>
        <xs:extension base="m:BaseResponseMessageType"/>
    </xs:complexContent>
</xs:complexType>
<xs:element name="MoveFolderResponse" type="m:MoveFolderResponseType"/>
<xs:complexType name="MoveFolderType">
    <xs:complexContent>
        <xs:extension base="m:BaseMoveCopyFolderType"/>
    </xs:complexContent>
</xs:complexType>
<xs:element name="MoveFolder" type="m:MoveFolderType"/>
<xs:complexType name="UpdateFolderType">
    <xs:complexContent>
        <xs:extension base="m:BaseRequestType">
            <xs:sequence>
                <xs:element name="FolderChanges"
type="t:NonEmptyArrayOfFolderChangesType"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="UpdateFolder" type="m:UpdateFolderType"/>
<xs:complexType name="UpdateFolderResponseType">
    <xs:complexContent>
        <xs:extension base="m:BaseResponseMessageType"/>
    </xs:complexContent>

```



```

    </xs:complexType>
    <xs:element name="UpdateFolderResponse" type="m:UpdateFolderResponseType"/>
</xs:schema>

```

6.2 Types Schema

This section contains the contents of the MS-OXWSFOLD-types.xsd file and information about additional files that this schema file requires to operate correctly.

MS-OXWSFOLD-types.xsd includes the files listed in the following table. For the schema file to operate correctly, these files need to be present in the folder that contains the WSDL, types schema, and messages schema files for this protocol.

Defining specification	File name
[MS-OXWSCDATA] , section 6.2	MS-OXWSCDATA-types.xsd
[MS-OXWSXPROP] , section 6.1	MS-OXWSXPROP-types.xsd

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
  elementFormDefault="qualified" version="Exchange2010" id="types">
  <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
  <xs:include schemaLocation="MS-OXWSCDATA-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSXPROP-types.xsd"/>
  <xs:complexType name="AppendToFolderFieldType">
    <xs:complexContent>
      <xs:extension base="t:FolderChangeDescriptionType">
        <xs:sequence>
          <xs:choice>
            <xs:element name="Folder" type="t:FolderType"/>
            <xs:element name="CalendarFolder" type="t:CalendarFolderType"/>
            <xs:element name="ContactsFolder" type="t:ContactsFolderType"/>
            <xs:element name="SearchFolder" type="t:SearchFolderType"/>
            <xs:element name="TasksFolder" type="t:TasksFolderType"/>
          </xs:choice>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="ArrayOfFoldersType">
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="Folder" type="t:FolderType"/>
      <xs:element name="CalendarFolder" type="t:CalendarFolderType"/>
      <xs:element name="ContactsFolder" type="t:ContactsFolderType"/>
      <xs:element name="SearchFolder" type="t:SearchFolderType"/>
      <xs:element name="TasksFolder" type="t:TasksFolderType"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="ArrayOfUnknownEntriesType">
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="UnknownEntry" type="xs:string"/>
    </xs:choice>
  </xs:complexType>

```

```

</xs:complexType>
<xs:complexType name="BaseFolderIdType" abstract="true">
</xs:complexType>
<xs:complexType name="BaseFolderType" abstract="true">
  <xs:sequence>
    <xs:element name="FolderId" type="t:FolderIdType" minOccurs="0"/>
    <xs:element name="ParentFolderId" type="t:FolderIdType" minOccurs="0"/>
    <xs:element name="FolderClass" type="xs:string" minOccurs="0"/>
    <xs:element name="DisplayName" type="xs:string" minOccurs="0"/>
    <xs:element name="TotalCount" type="xs:int" minOccurs="0"/>
    <xs:element name="ChildFolderCount" type="xs:int" minOccurs="0"/>
    <xs:element name="ExtendedProperty" type="t:ExtendedPropertyType"
minOccurs="0" maxOccurs="unbounded"/>
    <xs:element name="ManagedFolderInformation"
type="t:ManagedFolderInformationType" minOccurs="0"/>
    <xs:element name="EffectiveRights" type="t:EffectiveRightsType"
minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="BasePermissionType" abstract="true">
  <xs:sequence>
    <xs:element name="UserId" type="t:UserIdType"/>
    <xs:element name="CanCreateItems" type="xs:boolean" minOccurs="0"/>
    <xs:element name="CanCreateSubFolders" type="xs:boolean" minOccurs="0"/>
    <xs:element name="IsFolderOwner" type="xs:boolean" minOccurs="0"/>
    <xs:element name="IsFolderVisible" type="xs:boolean" minOccurs="0"/>
    <xs:element name="IsFolderContact" type="xs:boolean" minOccurs="0"/>
    <xs:element name="EditItems" type="t:PermissionActionType" minOccurs="0"/>
    <xs:element name="DeleteItems" type="t:PermissionActionType" minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="DeleteFolderFieldType">
  <xs:complexContent>
    <xs:extension base="t:FolderChangeDescriptionType">
      <xs:sequence/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="FolderChangeDescriptionType">
  <xs:complexContent>
    <xs:extension base="t:ChangeDescriptionType"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="FolderChangeType">
  <xs:sequence>
    <xs:choice>
      <xs:element name="FolderId" type="t:FolderIdType"/>
      <xs:element name="DistinguishedFolderId"
type="t:DistinguishedFolderIdType"/>
    </xs:choice>
    <xs:element name="Updates"
type="t:NonEmptyArrayOfFolderChangeDescriptionsType"/>
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="FolderClassType">
  <xs:restriction base="xs:string"/>
</xs:simpleType>
<xs:complexType name="ManagedFolderInformationType">
  <xs:sequence>

```

```

        <xs:element name="CanDelete" type="xs:boolean" minOccurs="0"/>
        <xs:element name="CanRenameOrMove" type="xs:boolean" minOccurs="0"/>
        <xs:element name="MustDisplayComment" type="xs:boolean" minOccurs="0"/>
        <xs:element name="HasQuota" type="xs:boolean" minOccurs="0"/>
        <xs:element name="IsManagedFoldersRoot" type="xs:boolean" minOccurs="0"/>
        <xs:element name="ManagedFolderId" type="xs:string" minOccurs="0"/>
        <xs:element name="Comment" type="xs:string" minOccurs="0"/>
        <xs:element name="StorageQuota" type="xs:int" minOccurs="0"/>
        <xs:element name="FolderSize" type="xs:int" minOccurs="0"/>
        <xs:element name="HomePage" type="xs:string" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="FolderType">
    <xs:complexContent>
        <xs:extension base="t:BaseFolderType">
            <xs:sequence>
                <xs:element name="PermissionSet" type="t:PermissionSetType"
minOccurs="0"/>
                <xs:element name="UnreadCount" type="xs:int" minOccurs="0"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfBaseFolderIdsType">
    <xs:choice maxOccurs="unbounded">
        <xs:element name="FolderId" type="t:FolderIdType"/>
        <xs:element name="DistinguishedFolderId" type="t:DistinguishedFolderIdType"/>
    </xs:choice>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfFolderChangeDescriptionsType">
    <xs:choice maxOccurs="unbounded">
        <xs:element name="AppendToFolderField" type="t:AppendToFolderFieldType"/>
        <xs:element name="SetFolderField" type="t:SetFolderFieldType"/>
        <xs:element name="DeleteFolderField" type="t>DeleteFolderFieldType"/>
    </xs:choice>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfFolderChangesType">
    <xs:sequence>
        <xs:element name="FolderChange" type="t:FolderChangeType"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfFolderNamesType">
    <xs:sequence>
        <xs:element name="FolderName" type="xs:string" maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="NonEmptyArrayOfFoldersType">
    <xs:choice maxOccurs="unbounded">
        <xs:element name="Folder" type="t:FolderType"/>
        <xs:element name="CalendarFolder" type="t:CalendarFolderType"/>
        <xs:element name="ContactsFolder" type="t:ContactsFolderType"/>
        <xs:element name="SearchFolder" type="t:SearchFolderType"/>
        <xs:element name="TasksFolder" type="t:TasksFolderType"/>
    </xs:choice>
</xs:complexType>
<xs:simpleType name="PermissionActionType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
    </xs:restriction>
</xs:simpleType>

```

```

        <xs:enumeration value="Owned"/>
        <xs:enumeration value="All"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="PermissionLevelType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="Owner"/>
        <xs:enumeration value="PublishingEditor"/>
        <xs:enumeration value="Editor"/>
        <xs:enumeration value="PublishingAuthor"/>
        <xs:enumeration value="Author"/>
        <xs:enumeration value="NoneditingAuthor"/>
        <xs:enumeration value="Reviewer"/>
        <xs:enumeration value="Contributor"/>
        <xs:enumeration value="Custom"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="PermissionReadAccessType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="FullDetails"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="PermissionSetType">
    <xs:sequence>
        <xs:element name="Permissions" type="t:ArrayOfPermissionsType"/>
        <xs:element name="UnknownEntries" type="t:ArrayOfUnknownEntriesType"
minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="PermissionType">
    <xs:complexContent>
        <xs:extension base="t:BasePermissionType">
            <xs:sequence>
                <xs:element name="ReadItems" type="t:PermissionReadAccessType"
minOccurs="0"/>
                <xs:element name="PermissionLevel" type="t:PermissionLevelType"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="SetFolderFieldType">
    <xs:complexContent>
        <xs:extension base="t:FolderChangeDescriptionType">
            <xs:choice>
                <xs:element name="Folder" type="t:FolderType"/>
                <xs:element name="CalendarFolder" type="t:CalendarFolderType"/>
                <xs:element name="ContactsFolder" type="t:ContactsFolderType"/>
                <xs:element name="SearchFolder" type="t:SearchFolderType"/>
                <xs:element name="TasksFolder" type="t:TasksFolderType"/>
            </xs:choice>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="TargetFolderIdType">
    <xs:choice>
        <xs:element name="FolderId" type="t:FolderIdType"/>
        <xs:element name="DistinguishedFolderId" type="t:DistinguishedFolderIdType"/>
    </xs:choice>

```

```

    </xs:choice>
  </xs:complexType>
</xs:schema>

```

6.3 WSDL

This section contains the contents of the MS-OXWSFOLD.wsdl file.

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:s="http://www.w3.org/2001/XMLSchema"
xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages">
  <wsdl:types>
    <xs:schema id="messages"
      elementFormDefault="qualified"
      version="Exchange2010"
      xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
      xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
      xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xs="http://www.w3.org/2001/XMLSchema"
      targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
      <xs:include schemaLocation="MS-OXWSFOLD-messages.xsd"/>
      <!-- Add global elements and types from messages.xsd -->
    </xs:schema>
    <xs:schema id="types"
      elementFormDefault="qualified"
      version="Exchange2010"
      xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
      targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xs="http://www.w3.org/2001/XMLSchema">
      <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
    </xs:schema>
  </wsdl:types>
  <wsdl:portType name="ExchangeServicePortType">
    <wsdl:operation name="CreateFolder">
      <wsdl:input message="tns:CreateFolderSoapIn" />
      <wsdl:output message="tns:CreateFolderSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="DeleteFolder">
      <wsdl:input message="tns>DeleteFolderSoapIn" />
      <wsdl:output message="tns>DeleteFolderSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="UpdateFolder">
      <wsdl:input message="tns:UpdateFolderSoapIn" />
      <wsdl:output message="tns:UpdateFolderSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="MoveFolder">
      <wsdl:input message="tns:MoveFolderSoapIn" />
      <wsdl:output message="tns:MoveFolderSoapOut" />
    </wsdl:operation>
  </wsdl:portType>

```

```

</wsdl:operation>
<wsdl:operation name="CopyFolder">
  <wsdl:input message="tns:CopyFolderSoapIn" />
  <wsdl:output message="tns:CopyFolderSoapOut" />
</wsdl:operation>
  <wsdl:operation name="GetFolder">
    <wsdl:input message="tns:GetFolderSoapIn" />
    <wsdl:output message="tns:GetFolderSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="CreateManagedFolder">
    <wsdl:input message="tns:CreateManagedFolderSoapIn" />
    <wsdl:output message="tns:CreateManagedFolderSoapOut" />
  </wsdl:operation>

</wsdl:portType>
<wsdl:binding name="ExchangeServiceBinding" type="tns:ExchangeServicePortType">
  <wsdl:documentation>
    <wsi:Claim conformsTo="http://ws-i.org/profiles/basic/1.0"
xmlns:wsi="http://ws-i.org/schemas/conformanceClaim/" />
  </wsdl:documentation>
  <soap:binding style="document" transport="http://schemas.xmlsoap.org/soap/http"/>
  <wsdl:operation name="GetFolder">
    <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetFolder" />
    <wsdl:input>
      <soap:header message="tns:GetFolderSoapIn" part="Impersonation"
use="literal"/>
      <soap:header message="tns:GetFolderSoapIn" part="MailboxCulture"
use="literal"/>
      <soap:header message="tns:GetFolderSoapIn" part="RequestVersion"
use="literal"/>
      <soap:header message="tns:GetFolderSoapIn" part="TimeZoneContext"
use="literal"/>
      <soap:body parts="request" use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body parts="GetFolderResult" use="literal" />
      <soap:header message="tns:GetFolderSoapOut" part="ServerVersion"
use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="CreateFolder">
    <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/CreateFolder" />
    <wsdl:input>
      <soap:header message="tns:CreateFolderSoapIn" part="Impersonation"
use="literal"/>
      <soap:header message="tns:CreateFolderSoapIn" part="MailboxCulture"
use="literal"/>
      <soap:header message="tns:CreateFolderSoapIn" part="RequestVersion"
use="literal"/>
      <soap:header message="tns:CreateFolderSoapIn" part="TimeZoneContext"
use="literal"/>
      <soap:body parts="request" use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body parts="CreateFolderResult" use="literal" />
      <soap:header message="tns:CreateFolderSoapOut" part="ServerVersion"
use="literal"/>
    </wsdl:output>
  </wsdl:operation>

```

```

    </wsdl:operation>
    <wsdl:operation name="DeleteFolder">
      <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/DeleteFolder" />
      <wsdl:input>
        <soap:header message="tns:DeleteFolderSoapIn" part="Impersonation"
use="literal" />
        <soap:header message="tns:DeleteFolderSoapIn" part="MailboxCulture"
use="literal" />
        <soap:header message="tns:DeleteFolderSoapIn" part="RequestVersion"
use="literal" />
        <soap:body parts="request" use="literal" />
      </wsdl:input>
      <wsdl:output>
        <soap:body parts="DeleteFolderResult" use="literal" />
        <soap:header message="tns:DeleteFolderSoapOut" part="ServerVersion"
use="literal" />
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateFolder">
      <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/UpdateFolder" />
      <wsdl:input>
        <soap:header message="tns:UpdateFolderSoapIn" part="Impersonation"
use="literal" />
        <soap:header message="tns:UpdateFolderSoapIn" part="MailboxCulture"
use="literal" />
        <soap:header message="tns:UpdateFolderSoapIn" part="RequestVersion"
use="literal" />
        <soap:header message="tns:UpdateFolderSoapIn" part="TimeZoneContext"
use="literal" />
        <soap:body parts="request" use="literal" />
      </wsdl:input>
      <wsdl:output>
        <soap:body parts="UpdateFolderResult" use="literal" />
        <soap:header message="tns:UpdateFolderSoapOut" part="ServerVersion"
use="literal" />
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="MoveFolder">
      <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/MoveFolder" />
      <wsdl:input>
        <soap:header message="tns:MoveFolderSoapIn" part="Impersonation"
use="literal" />
        <soap:header message="tns:MoveFolderSoapIn" part="MailboxCulture"
use="literal" />
        <soap:header message="tns:MoveFolderSoapIn" part="RequestVersion"
use="literal" />
        <soap:body parts="request" use="literal" />
      </wsdl:input>
      <wsdl:output>
        <soap:body parts="MoveFolderResult" use="literal" />
        <soap:header message="tns:MoveFolderSoapOut" part="ServerVersion"
use="literal" />
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CopyFolder">
      <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/CopyFolder" />

```

```

        <wsdl:input>
            <soap:header message="tns:CopyFolderSoapIn" part="Impersonation"
use="literal"/>
            <soap:header message="tns:CopyFolderSoapIn" part="MailboxCulture"
use="literal"/>
            <soap:header message="tns:CopyFolderSoapIn" part="RequestVersion"
use="literal"/>
            <soap:body parts="request" use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body parts="CopyFolderResult" use="literal" />
            <soap:header message="tns:CopyFolderSoapOut" part="ServerVersion"
use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CreateManagedFolder">
        <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/CreateManagedFolder"
/>
        <wsdl:input>
            <soap:header message="tns:CreateManagedFolderSoapIn" part="Impersonation"
use="literal"/>
            <soap:header message="tns:CreateManagedFolderSoapIn" part="MailboxCulture"
use="literal"/>
            <soap:header message="tns:CreateManagedFolderSoapIn" part="RequestVersion"
use="literal"/>
            <soap:body parts="request" use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body parts="CreateManagedFolderResult" use="literal" />
            <soap:header message="tns:CreateManagedFolderSoapOut" part="ServerVersion"
use="literal"/>
        </wsdl:output>
    </wsdl:operation>

</wsdl:binding>
<wsdl:message name="GetFolderSoapIn">
    <wsdl:part name="request" element="tns:GetFolder" />
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>
<wsdl:message name="GetFolderSoapOut">
    <wsdl:part name="GetFolderResult" element="tns:GetFolderResponse" />
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="CreateFolderSoapIn">
    <wsdl:part name="request" element="tns:CreateFolder" />
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>
<wsdl:message name="CreateFolderSoapOut">
    <wsdl:part name="CreateFolderResult" element="tns:CreateFolderResponse" />
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="CreateManagedFolderSoapIn">

```



```

        <wsdl:part name="request" element="tns:CreateManagedFolder" />
        <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
        <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
        <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    </wsdl:message>
    <wsdl:message name="CreateManagedFolderSoapOut">
        <wsdl:part name="CreateManagedFolderResult" element="tns:CreateManagedFolderResponse" />
    </wsdl:message>
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:definitions>

    <wsdl:part name="request" element="tns>DeleteFolder" />
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="DeleteFolderSoapOut">
    <wsdl:part name="DeleteFolderResult" element="tns>DeleteFolderResponse" />
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="UpdateFolderSoapIn">
    <wsdl:part name="request" element="tns:UpdateFolder" />
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
    <wsdl:part name="TimeZoneContext" element="t:TimeZoneContext"/>
</wsdl:message>
<wsdl:message name="UpdateFolderSoapOut">
    <wsdl:part name="UpdateFolderResult" element="tns:UpdateFolderResponse" />
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="MoveFolderSoapIn">
    <wsdl:part name="request" element="tns:MoveFolder" />
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="MoveFolderSoapOut">
    <wsdl:part name="MoveFolderResult" element="tns:MoveFolderResponse" />
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="CopyFolderSoapIn">
    <wsdl:part name="request" element="tns:CopyFolder" />
    <wsdl:part name="Impersonation" element="t:ExchangeImpersonation"/>
    <wsdl:part name="MailboxCulture" element="t:MailboxCulture"/>
    <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
</wsdl:message>
<wsdl:message name="CopyFolderSoapOut">
    <wsdl:part name="CopyFolderResult" element="tns:CopyFolderResponse" />
    <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
</wsdl:definitions>

```

7 Appendix B: Product Behavior

The information in this specification is applicable to the following product versions:

- Microsoft Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

PRELIMINARY

8 Change Tracking

This section will report content and/or editorial changes, beginning with the next release.

PRELIMINARY

9 Index

A

[Applicability](#)

C

[Capability negotiation](#)

[Change tracking](#)

Client

[abstract data model](#)

[initialization](#)

[local events](#)

[message processing](#)

[overview](#)

[sequencing rules](#)

[timer events](#)

[timers](#)

F

[Full WSDL](#)

G

[Glossary](#)

I

[Introduction](#)

M

Messages

[overview](#)

[syntax](#)

[transport](#)

O

[Overview \(synopsis\)](#)

P

[Preconditions](#)

[Prerequisites](#)

[Product behavior](#)

R

[Relationship to other protocols](#)

S

Security

[implementer considerations](#)

[overview](#)

[parameter index](#)

Server

[abstract data model](#)

[initialization](#)

[local events](#)

[message processing](#)

[overview](#)

[sequencing rules](#)

[timer events](#)

[timers](#)

[Standards assignments](#)

T

[Tracking changes](#)

V

[Vendor-extensible fields](#)

[Versioning](#)