

[MS-OXWSLVID]: Federated Internet Authentication Web Service Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
11/04/2009	1.0.0	Major	Initial availability
02/10/2010	1.1.0	Minor	Updated the technical content.
05/05/2010	1.2.0	Minor	Updated the technical content.
08/04/2010	2.0	Major	Significantly changed the technical content.
11/03/2010	2.1	Minor	Clarified the meaning of the technical content.
03/18/2011	3.0	Major	Significantly changed the technical content.
08/05/2011	3.1	Minor	Clarified the meaning of the technical content.
10/07/2011	3.1	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	4.0	Major	Significantly changed the technical content.
04/27/2012	4.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	4.1	Minor	Clarified the meaning of the technical content.
10/08/2012	5.0	Major	Significantly changed the technical content.
02/11/2013	5.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/26/2013	6.0	Major	Significantly changed the technical content.
11/18/2013	6.0	No change	No changes to the meaning, language, or formatting of the technical content.
02/10/2014	6.0	No change	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1 Introduction	7
1.1 Glossary	7
1.2 References	7
1.2.1 Normative References	8
1.2.2 Informative References	9
1.3 Overview	9
1.4 Relationship to Other Protocols	9
1.5 Prerequisites/Preconditions	9
1.6 Applicability Statement	9
1.7 Versioning and Capability Negotiation	10
1.8 Vendor-Extensible Fields	10
1.9 Standards Assignments	10
2 Messages	11
2.1 Transport	11
2.2 Common Message Syntax	11
2.2.1 Namespaces	11
2.2.2 Messages	11
2.2.3 Elements	12
2.2.3.1 tns:DomainOwnershipProofHeader Element	12
2.2.3.2 s:Security Element	12
2.2.4 Complex Types	12
2.2.4.1 tns:ArrayOfProperty Complex Type	13
2.2.4.2 tns:DomainInfo Complex Type	13
2.2.4.3 tns:DomainOwnershipProofHeader Complex Type	14
2.2.4.4 tns:Property Complex Type	15
2.2.4.5 s1:WSSecurityHeader Complex Type	15
2.2.5 Simple Types	16
2.2.5.1 tns:DomainState Simple Type	16
2.2.6 Attributes	17
2.2.7 Groups	17
2.2.8 Attribute Groups	17
3 Protocol Details	18
3.1 ManageDelegationSoap Client Details	18
3.1.1 Abstract Data Model	18
3.1.2 Timers	19
3.1.3 Initialization	19
3.1.4 Message Processing Events and Sequencing Rules	19
3.1.4.1 AddUri Operation	19
3.1.4.1.1 Messages	20
3.1.4.1.1.1 tns:AddUriSoapIn Message	20
3.1.4.1.1.2 tns:AddUriSoapOut Message	20
3.1.4.1.2 Elements	21
3.1.4.1.2.1 tns:AddUri Element	21
3.1.4.1.2.2 tns:AddUriResponse Element	21
3.1.4.2 CreateAppId Operation	22
3.1.4.2.1 Messages	22
3.1.4.2.1.1 tns:CreateAppIdSoapIn Message	22
3.1.4.2.1.2 tns:CreateAppIdSoapOut Message	23

3.1.4.2.2	Elements.....	23
3.1.4.2.2.1	tns:CreateAppId Element	23
3.1.4.2.2.2	tns:CreateAppIdResponse Element	24
3.1.4.2.3	Complex Types	24
3.1.4.2.3.1	tns:AppIdInfo Complex Type.....	25
3.1.4.3	GetDomainInfo Operation	25
3.1.4.3.1	Messages	26
3.1.4.3.1.1	tns:GetDomainInfoSoapIn Message	26
3.1.4.3.1.2	tns:GetDomainInfoSoapOut Message	26
3.1.4.3.2	Elements.....	27
3.1.4.3.2.1	tns:GetDomainInfo Element.....	27
3.1.4.3.2.2	tns:GetDomainInfoResponse Element	27
3.1.4.4	ReleaseDomain Operation.....	28
3.1.4.4.1	Messages	28
3.1.4.4.1.1	tns:ReleaseDomainSoapIn Message	28
3.1.4.4.1.2	tns:ReleaseDomainSoapOut Message.....	29
3.1.4.4.2	Elements.....	29
3.1.4.4.2.1	tns:ReleaseDomain Element	29
3.1.4.4.2.2	tns:ReleaseDomainResponse Element	30
3.1.4.5	RemoveUri Operation	30
3.1.4.5.1	Messages	31
3.1.4.5.1.1	tns:RemoveUriSoapIn Message	31
3.1.4.5.1.2	tns:RemoveUriSoapOut Message	31
3.1.4.5.2	Elements.....	32
3.1.4.5.2.1	tns:RemoveUri Element.....	32
3.1.4.5.2.2	tns:RemoveUriResponse Element	32
3.1.4.6	ReserveDomain Operation	33
3.1.4.6.1	Messages	33
3.1.4.6.1.1	tns:ReserveDomainSoapIn Message.....	33
3.1.4.6.1.2	tns:ReserveDomainSoapOut Message	34
3.1.4.6.2	Elements.....	34
3.1.4.6.2.1	tns:ReserveDomain Element	34
3.1.4.6.2.2	tns:ReserveDomainResponse Element.....	35
3.1.4.7	UpdateAppIdCertificate Operation.....	35
3.1.4.7.1	Messages	36
3.1.4.7.1.1	tns:UpdateAppIdCertificateSoapIn Message	36
3.1.4.7.1.2	tns:UpdateAppIdCertificateSoapOut Message	36
3.1.4.7.2	Elements.....	37
3.1.4.7.2.1	tns:UpdateAppIdCertificate Element.....	37
3.1.4.7.2.2	tns:UpdateAppIdCertificateResponse Element	38
3.1.4.8	UpdateAppIdProperties Operation	38
3.1.4.8.1	Messages	38
3.1.4.8.1.1	tns:UpdateAppIdPropertiesSoapIn Message	39
3.1.4.8.1.2	tns:UpdateAppIdPropertiesSoapOut Message	39
3.1.4.8.2	Elements.....	39
3.1.4.8.2.1	tns:UpdateAppIdProperties Element.....	40
3.1.4.8.2.2	tns:UpdateAppIdPropertiesResponse Element	40
3.1.5	Timer Events	41
3.1.6	Other Local Events	41
3.2	ManageDelegation2Soap Client Details	41
3.2.1	Abstract Data Model	41
3.2.2	Timers	42
3.2.3	Initialization	42

3.2.4	Message Processing Events and Sequencing Rules	42
3.2.4.1	AddUri Operation	42
3.2.4.1.1	Messages	43
3.2.4.1.1.1	tns:AddUriDomainOwnershipProofHeader Message	43
3.2.4.1.1.2	tns:AddUriSecurity Message.....	44
3.2.4.1.1.3	tns:AddUriSoapIn Message	44
3.2.4.1.1.4	tns:AddUriSoapOut Message	44
3.2.4.1.2	Elements.....	45
3.2.4.1.2.1	tns:AddUri Element.....	45
3.2.4.1.2.2	tns:AddUriResponse Element	45
3.2.4.2	CreateAppId Operation.....	46
3.2.4.2.1	Messages	46
3.2.4.2.1.1	tns:CreateAppIdDomainOwnershipProofHeader Message	47
3.2.4.2.1.2	tns:CreateAppIdSecurity Message	47
3.2.4.2.1.3	tns:CreateAppIdSoapIn Message	47
3.2.4.2.1.4	tns:CreateAppIdSoapOut Message	48
3.2.4.2.2	Elements.....	48
3.2.4.2.2.1	tns:CreateAppId Element	48
3.2.4.2.2.2	tns:CreateAppIdResponse Element	49
3.2.4.2.3	Complex Types	49
3.2.4.2.3.1	t:AppIdInfo Complex Type.....	50
3.2.4.3	GetDomainInfo Operation	50
3.2.4.3.1	Messages	51
3.2.4.3.1.1	tns:GetDomainInfoSecurity Message.....	51
3.2.4.3.1.2	tns:GetDomainInfoSoapIn Message	51
3.2.4.3.1.3	tns:GetDomainInfoSoapOut Message	51
3.2.4.3.2	Elements.....	52
3.2.4.3.2.1	tns:GetDomainInfo Element.....	52
3.2.4.3.2.2	tns:GetDomainInfoResponse Element	53
3.2.4.4	ReleaseDomain Operation.....	53
3.2.4.4.1	Messages	54
3.2.4.4.1.1	tns:ReleaseDomainSecurity Message	54
3.2.4.4.1.2	tns:ReleaseDomainSoapIn Message	54
3.2.4.4.1.3	tns:ReleaseDomainSoapOut Message.....	55
3.2.4.4.2	Elements.....	55
3.2.4.4.2.1	tns:ReleaseDomain Element	55
3.2.4.4.2.2	tns:ReleaseDomainResponse Element	56
3.2.4.5	RemoveUri Operation	56
3.2.4.5.1	Messages	57
3.2.4.5.1.1	tns:RemoveUriSecurity Message.....	57
3.2.4.5.1.2	tns:RemoveUriSoapIn Message	57
3.2.4.5.1.3	tns:RemoveUriSoapOut Message	58
3.2.4.5.2	Elements.....	58
3.2.4.5.2.1	tns:RemoveUri Element.....	58
3.2.4.5.2.2	tns:RemoveUriResponse Element	59
3.2.4.6	ReserveDomain Operation	59
3.2.4.6.1	Messages	60
3.2.4.6.1.1	tns:ReserveDomainDomainOwnershipProofHeader Message.....	60
3.2.4.6.1.2	tns:ReserveDomainSecurity Message	60
3.2.4.6.1.3	tns:ReserveDomainSoapIn Message.....	61
3.2.4.6.1.4	tns:ReserveDomainSoapOut Message	61
3.2.4.6.2	Elements.....	61
3.2.4.6.2.1	tns:ReserveDomain Element	62

3.2.4.6.2.2	tns:ReserveDomainResponse Element	62
3.2.4.7	UpdateAppIdCertificate Operation	63
3.2.4.7.1	Messages	63
3.2.4.7.1.1	tns:UpdateAppIdCertificateSecurity Message	63
3.2.4.7.1.2	tns:UpdateAppIdCertificateSoapIn Message	64
3.2.4.7.1.3	tns:UpdateAppIdCertificateSoapOut Message	64
3.2.4.7.2	Elements	65
3.2.4.7.2.1	tns:UpdateAppIdCertificate Element	65
3.2.4.7.2.2	tns:UpdateAppIdCertificateResponse Element	65
3.2.4.8	UpdateAppIdProperties Operation	66
3.2.4.8.1	Messages	66
3.2.4.8.1.1	tns:UpdateAppIdPropertiesSecurity Message	66
3.2.4.8.1.2	tns:UpdateAppIdPropertiesSoapIn Message	67
3.2.4.8.1.3	tns:UpdateAppIdPropertiesSoapOut Message	67
3.2.4.8.2	Elements	68
3.2.4.8.2.1	tns:UpdateAppIdProperties Element	68
3.2.4.8.2.2	tns:UpdateAppIdPropertiesResponse Element	68
3.2.5	Timer Events	69
3.2.6	Other Local Events	69
3.3	Federation Metadata Client Details	69
3.3.1	Abstract Data Model	69
3.3.2	Timers	70
3.3.3	Initialization	70
3.3.4	Message Processing Events and Sequencing	70
3.3.4.1	Requesting the Service Issue a Token	70
3.3.4.1.1	Token Request	70
3.3.4.1.2	Token Response	75
3.3.4.1.3	Encrypted and Unencrypted Tokens	77
3.3.5	Timer Events	81
3.3.6	Other Local Events	81
4	Protocol Examples	82
4.1	Registering with a Security Token Service	82
4.1.1	Creating an Application Identifier	82
4.1.2	Reserving a Federated Organization Domain	83
4.1.3	Retrieving Domain Information	84
4.1.4	Registering a Domain Name	85
4.1.5	Removing a Registered Domain Name	86
4.1.6	Updating a Certificate	86
5	Security	88
5.1	Security Considerations for Implementers	88
5.2	Index of Security Parameters	88
6	Appendix A: Full WSDL	89
6.1	ManageDelegationSoap WSDL	89
6.2	ManageDelegation2Soap WSDL	96
7	Appendix B: Product Behavior	107
8	Change Tracking	109
9	Index	110

1 Introduction

The Federated Internet Authentication Web Service Protocol defines the interaction between the server and standard Internet authentication protocols. The server uses this protocol to call external Web services to obtain security tokens that are then used by other Web service protocols to authenticate a transaction.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

- certificate**
- Coordinated Universal Time (UTC)**
- domain**
- domain name**
- Domain Name System (DNS)**
- Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**
- private key**
- public key**
- SOAP action**
- SOAP body**
- SOAP header**
- SOAP message**
- user principal name (UPN)**
- X.509**
- XML**
- XML namespace**

The following terms are defined in [\[MS-OXGLOS\]](#):

- base64 encoding**
- security token service (STS)**
- Uniform Resource Identifier (URI)**
- Uniform Resource Locator (URL)**
- Web Services Description Language (WSDL)**
- WSDL message**
- WSDL port type**
- XML schema**

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[SAML] OASIS, "Web Services Security: SAML Token Profile", Oasis Standard, December 2004, <http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.0.pdf>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP1.2/1] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>

[WSADDRBIND] Gudgin, M., Hadley, M., and Rogers, T., Eds., "Web Services Addressing 1.0 – SOAP Binding", W3C Recommendation, May 2006, <http://www.w3.org/TR/2006/REC-ws-addr-soap-20060509/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[WSDLSOAP] Angelov, D., Ballinger, K., Butek, R., et al., "WSDL 1.1 Binding Extension for SOAP 1.2", W3c Member Submission, April 2006, <http://www.w3.org/Submission/wsdl11soap12/>

[WSFederation] Kaler, C., Nadalin, A., Bajaj, S., et al., "Web Services Federation Language (WS-Federation)", Version 1.1, December 2006, <http://specs.xmlsoap.org/ws/2006/12/federation/ws-federation.pdf>

[WSS] OASIS, "Web Services Security: SOAP Message Security 1.1 (WS-Security 2004)", February 2006, <http://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf>

[WSTrust1.4] OASIS Standard, "WS-Trust 1.4", February 2009, <http://docs.oasis-open.org/ws-sx/ws-trust/v1.4/os/ws-trust-1.4-spec-os.doc>

[XMLDSig2] Bartel, M., Boyer, J., Fox, B., et al., "XML Signature Syntax and Processing (Second Edition)", W3C Recommendation, June 2008, <http://www.w3.org/TR/2008/REC-xmlsig-core-20080610/>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

[XPath] Clark, J. and DeRose, S., "XML Path Language (XPath), Version 1.0", W3C Recommendation, November 1999, <http://www.w3.org/TR/xpath>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[MS-OXWSMSHR] Microsoft Corporation, "[Folder Sharing Web Service Protocol](#)".

1.3 Overview

The Federated Internet Authentication Web Service Protocol defines the interactions between the server and standard Internet authentication protocols to provide authentication information to other services on the server. This protocol uses the following:

- The Managed Delegation Web service, to establish a relationship with a **security token service (STS)**. The operations that are exposed by the Managed Delegation Web service are described in section [3.1](#) and section [3.2](#).
- The **Federation** element, as described in [\[WSFederation\]](#), to provide the security tokens and endpoints that are used to create authentication tokens that can be used to authenticate users and services with other organizations.
- The authentication token that is returned by an STS, as described in [\[WSTrust1.4\]](#).

1.4 Relationship to Other Protocols

The Federated Internet Authentication Web Service Protocol uses the standard Web Service Federation Language Protocol, as described in [\[WSFederation\]](#), and the WS-Trust 1.4 Protocol, as described in [\[WSTrust1.4\]](#), to provide authentication services for a server. The Folder Sharing Web Service Protocol, as described in [\[MS-OXWSMSHR\]](#), uses this protocol for authentication services.

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

1.5 Prerequisites/Preconditions

The Federated Internet Authentication Web Service Protocol uses services that are provided by external Web services to establish federated relationships between organizations. In order to operate, the protocol requires that the service provide the following:

- The **URL** of a service that provides a Federation Metadata Document, as described in [\[WSFederation\]](#) section 3.1, with the fields and values as described in section [3.3.1](#).
- The URL of a delegation management service that provides services, as described in section [3.1](#) or section [3.2](#).

1.6 Applicability Statement

This protocol is applicable to applications that request federated authentication information on behalf of a client, and applications that expose Web services that provide federated authentication information to servers.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The **WSDL** in this specification provides a base description of the protocol. The schema in this specification provides a base description of the message syntax. The text that specifies the WSDL and schema might specify restrictions that reflect actual protocol behavior. For example, the schema definition might allow for an element to be **empty**, **null**, or **not present** but the behavior of the protocol as specified restricts the same elements to being **non-empty**, **not null**, or **present**.

2.1 Transport

Protocol servers support SOAP over **HTTPS**. Protocol messages are formatted as specified in [\[SOAP1.1\]](#) or in [\[SOAP1.2/1\]](#). Security tokens are used as specified in [\[WSS\]](#). Security tokens are exchanged as specified in [\[WSTrust1.4\]](#). Web service addresses are bound as specified in [\[WSADDRBIND\]](#).

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and Web Services Description Language (WSDL), as defined in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** by using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
s	http://www.w3.org/2001/XMLSchema	[XMLNS]
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
soap12	http://schemas.xmlsoap.org/wsdl/soap12/	[WSDLSOAP]
s1	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd	[WSS]
s2	http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd	[WSS]
s3	http://www.w3.org/2000/09/xmldsig#	[XMLDSig2]
tns	http://domains.live.com/Service/ManageDelegation2/V1.0	
wsdl	http://schemas.xmlsoap.org/WSDL/	[WSDL]

2.2.2 Messages

This specification does not define any common **WSDL message** definitions.

2.2.3 Elements

The following table summarizes the set of common XML schema element definitions that are defined by this specification. XML schema element definitions that are specific to a particular operation are described with the operation.

Element name	Description
DomainOwnershipProofHeader	Specifies the security credentials that identify the owner of a domain that is participating in the federation management service.
Security	Specifies the elements of the WSSecurityHeader element that are used by the Federated Internet Authentication Web Service Protocol.

2.2.3.1 tns:DomainOwnershipProofHeader Element

The **DomainOwnershipProofHeader** element defines the credentials that are required to prove ownership of a domain that is participating in a federation management service.

```
<xs:element name="tns:DomainOwnershipProofHeader"
  type="tns:DomainOwnershipProofHeader"
/>
```

2.2.3.2 s:Security Element

The **Security** element specifies the elements of the **WSSecurityHeader** element that are used by the Federated Internet Authentication Web Service Protocol. These elements are **Timestamp**, as specified in [\[WSS\]](#) Appendix A, and **Signature**, as specified in [\[XMLDSig2\]](#).

```
<xs:element name="s:Security"
  type="s1:WSSecurityHeader"
/>
```

2.2.4 Complex Types

The following table summarizes the set of common XML schema complex types that are defined by this specification. XML schema complex type definitions that are specific to a particular operation are defined with the operation.

Complex type name	Description
ArrayOfProperty	Specifies an array of property name/value pairs for a managed delegate relationship.
DomainInfo	Specifies the domain information that is returned by the GetDomainInfo operation.
DomainOwnershipProofHeader	Specifies the credentials that are required to prove ownership of a domain.
Property	Specifies a name/value pair for a managed delegate relationship.

Complex type name	Description
WSSecurityHeader	Specifies the elements of the standard WSSecurityHeader element that are used by the Federated Internet Authentication Web Service Protocol.

2.2.4.1 tns:ArrayOfProperty Complex Type

The **ArrayOfProperty** complex type specifies one or more **Property** complex type name/value pairs, as specified in section [2.2.4.4](#).

```
<xs:complexType name="ArrayOfProperty">
  <xs:sequence>
    <xs:element name="Property"
      type="tns:Property"
      minOccurs="0"
      maxOccurs="unbounded"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **ArrayOfProperty** complex type.

Element name	Type	Description
Property	tns:Property (section 2.2.4.4)	A name/value pair that describes a managed delegation relationship property.

2.2.4.2 tns:DomainInfo Complex Type

The **DomainInfo** complex type defines the domain information that is returned by the **GetDomainInfo** operation, as specified in section [3.1.4.3](#).

```
<xs:complexType name="DomainInfo">
  <xs:sequence>
    <xs:element name="DomainName"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="AppId"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="DomainState"
      type="tns:DomainState"
      maxOccurs="1"
      minOccurs="1"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **DomainInfo** complex type.

Element name	Type	Description
DomainName	s:string ([XMLSCHEMA2])	Specifies the registered name of the domain.
AppId	s:string	Specifies the application identifier that is associated with the domain.
DomainState	tns:DomainState (section 2.2.5.1)	Specifies the current state of the domain. MUST be present.

2.2.4.3 tns:DomainOwnershipProofHeader Complex Type

The **DomainOwnershipProofHeader** complex type specifies the credentials that are required to prove ownership of a domain that is participating in a federation management service.

```
<xs:complexType name="DomainOwnershipProofHeader">
  <xs:sequence>
    <xs:element name="Domain"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="HashAlgorithm"
      type="s:string"
    />
    <xs:element name="Signature"
      type="s:string"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **DomainOwnershipProofHeader** complex type.

Element name	Type	Description
Domain	s:string ([XMLSCHEMA2])	Specifies the name of the domain that is participating in the federation management service.
HashAlgorithm	s:string	Specifies the hash algorithm that is used to create the signature.
Signature	s:string	Specifies the signature of the domain owner.

Create the **Signature** element by performing the following algorithm:

- Sign the **Domain** element with the private key from the certificate used to authenticate the domain with the STS.
- Hash the certificate signature with the SHA-512 hash algorithm.

- Encode the hashed value of the signature with **base64 encoding**.

The server compares the value of the **Signature** element with the contents of a TXT record on the **Domain Name System (DNS)** server for the domain specified in the **Domain** element to determine whether the application is authorized to make Web service calls for the domain.

2.2.4.4 tns:Property Complex Type

The **Property** complex type specifies a managed delegation property as a name/value pair.

```
<xs:complexType name="Property">
  <xs:sequence>
    <xs:element name="Name"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="Value"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **Property** complex type.

Element name	Type	Description
Name	s:string ([XMLSCHEMA2])	Specifies the name of the property.
Value	s:string	Specifies the value of the property expressed as a string.

2.2.4.5 s1:WSSecurityHeader Complex Type

The **WSSecurityHeader** complex type specifies the elements of the **WSSecurityHeader** element that are used by the Federated Internet Authentication Web Service Protocol.

```
<xs:complexType name="WSSecurityHeader">
  <xs:sequence>
    <xs:element
      minOccurs="0"
      maxOccurs="1"
      ref="s2:Timestamp"
    />
    <xs:element
      minOccurs="0"
      maxOccurs="1"
      ref="s3:Signature"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **WSSecurityHeader** complex type.

Element name	Type	Description
Timestamp	s2:Timestamp [WSS] Appendix A	Specifies the date and time that the request was created. The Timestamp element MUST contain a Created and an Expired element.
Signature	s3:Signature [XMLDSig2]	Specifies the signature for the request. The signature is created by signing the Timestamp element with the X.509 certificate (2) private key that is associated with the domain owner. The Signature element MUST contain the signature method and the X.509 certificate (2) public key .

2.2.5 Simple Types

The following table summarizes the set of common XML schema simple types that are defined by this specification. XML schema simple type definitions that are specific to a particular operation are defined with the operation.

Simple type name	Description
DomainState	Specifies the possible states that can be returned by the GetDomainInfo operation.

2.2.5.1 tns:DomainState Simple Type

The **DomainState** simple type specifies the possible states that can be returned by the **GetDomainInfo** operation, as specified in sections [3.1.4.3](#) and [3.2.4.3](#).

```
<xs:simpleType name="DomainState">
  <xs:restriction
    base="s:string"
  >
    <xs:enumeration
      value="PendingActivation"
    />
    <xs:enumeration
      value="Active"
    />
    <xs:enumeration
      value="PendingRelease"
    />
  </xs:restriction>
</xs:simpleType>
```

The following table lists the values that are defined by the **DomainState** simple type.

Value	Meaning
PendingActivation	The request to create a domain has been received but it is not yet active.

Value	Meaning
Active	The domain is active.
PendingRelease	The request to release a domain has been received, but the domain has not yet been released.

2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

3 Protocol Details

The Federated Internet Authentication Web Service Protocol does not act as a server, and does not expose any services to outside callers. This specification describes the server's interactions as a client to external services.

3.1 ManageDelegationSoap Client Details

This client protocol is used by client applications to identify server applications and authenticate those server applications.

3.1.1 Abstract Data Model

This section contains a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that specified in this document.

This protocol is used by client applications to identify server applications and authenticate those server applications. It uses the standard Internet authentication techniques specified in [\[SAML\]](#), [\[WSFederation\]](#), [\[WSS\]](#), [\[WSTrust1.4\]](#), and [\[XMLDSig2\]](#) for that identification and authentication.

Clients that implement this protocol take the following steps to establish a relationship with the federation management service:

1. Create an application identifier by using the **CreateAppId** operation, as specified in section [3.1.4.2](#).
2. Place the application identifier on the domain's DNS server as a TXT record.
3. Reserve a **domain name** with the federation management service by using the **ReserveDomain** operation, as specified in section [3.1.4.6](#).
4. Register the **URI** that is associated with the domain with the federation management service by using the **AddUri** operation, as specified in section [3.1.4.1](#).

Clients can request and modify information stored with the federation management service by doing the following:

- Using the **GetDomainInfo** operation, as specified in section [3.1.4.3](#), to retrieve domain information from the federation management service.
- Modifying the information stored with the federation management service by using the **UpdateAppIdCertificate** operation, as specified in section [3.1.4.7](#), and the **UpdateAppIdProperties** operation, as specified in section [3.1.4.8](#).

Clients can end participation with the federation management service by doing the following:

- Using the **RemoveUri** operation, as specified in section [3.1.4.5](#), to remove a URI registered to the domain.
- Using the **ReleaseDomain** operation, as specified in section [3.1.4.4](#), to remove a registered domain from the federation management service.

3.1.2 Timers

None.

3.1.3 Initialization

Before calling this protocol, the client application requires the following:

- The URL of a service that provides a Federation Metadata Document, as specified in [\[WSFederation\]](#) section 3.1, with the fields and values as specified in section [3.3.<1>](#)
- The URL of a delegation management service that provides services as described in section [3.1.<2>](#)
- A DNS TXT record containing the client's application ID on the DNS server for the domain.

3.1.4 Message Processing Events and Sequencing Rules

This protocol uses the operations that are listed in the following table.

Operation name	Description
AddUri	Registers a URI with the federation management service.
CreateAppId	Creates an application identifier for an organization with the federation management service.
GetDomainInfo	Gets domain status information from the federation management service.
ReleaseDomain	Removes a domain from the federation management service.
RemoveUri	Removes a registered URI from the federation management service.
ReserveDomain	Verifies that a domain has to be managed by the specified application identifier.
UpdateAppIdCertificate	Updates the security certificate that is associated with an application identifier.
UpdateAppIdProperties	Updates the organizational information that is associated with an application identifier.

3.1.4.1 AddUri Operation

The **AddUri** operation registers the URL of an organization that is participating in the federation management service.

The following is the **WSDL port type** specification for this operation.

```
<wsdl:operation name="AddUri">
  <wsdl:input message="tns:AddUriSoapIn" />
  <wsdl:output message="tns:AddUriSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification for this operation.

```

<wsdl:operation name="AddUri">
  <soap:operation soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/AddUri"
style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>

```

3.1.4.1.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
AddUriSoapIn	Specifies the SOAP message that requests the application identifier.
AddUriSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.1.1.1 tns:AddUriSoapIn Message

The **AddUriSoapIn** WSDL message specifies a request to register a URI with the federation management service.

```

<wsdl:message name="AddUriSoapIn">
  <wsdl:part name="parameters" element="tns:AddUri" />
</wsdl:message>

```

The **AddUriSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/AddUri>.

The part of the **AddUriSoapIn** WSDL message is described in the following table.

Part Name	Element/type	Description
parameters	tns:AddUri (section 3.2.4.1.2.1)	Specifies the SOAP body of the request to register a URI with the federation management service.

3.1.4.1.1.2 tns:AddUriSoapOut Message

The **AddUriSoapOut** WSDL message specifies the response to a request to register a URI with the federation management server.

```

<wsdl:message name="AddUriSoapOut">
  <wsdl:part name="parameters" element="tns:AddUriResponse" />
</wsdl:message>

```

The **AddUriSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/AddUri>.

The part of the **AddUriSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:AddUriResponse (section 3.2.4.1.2.2)	Specifies the SOAP body of the response.

3.1.4.1.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
AddUri	Specifies the URI that is to be added to the federation management service.
AddUriResponse	Specifies the response from the AddUri operation.

3.1.4.1.2.1 tns:AddUri Element

The **AddUri** element specifies the URI that is to be added to the federation management service by the **AddUri** operation.

```
<xs:element name="AddUri">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
      <xs:element name="uri"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **AddUri** element.

Element name	Type	Description
ownerAppId	s:string (XMLSCHEMA2)	Specifies the application identifier that is assigned to the entity that is requesting that the URI be registered with a federation management service.
uri	s:string	Specifies the URI to register with the federation management service.

3.1.4.1.2.2 tns:AddUriResponse Element

The **AddUriResponse** element specifies the response from the **AddUri** operation (section [3.1.4.1](#)).

```
<xs:element name="AddUriResponse">
  <xs:complexType />
</xs:element>
```

3.1.4.2 CreateAppId Operation

The **CreateAppId** operation creates an identifier for an organization that participates in a federation management service. The identifier that is returned by the **CreateAppId** operation is used when calling operations on the federation management server to identify the organization that is making the request.

The following is the WSDL port type specification for this operation.

```
<wsdl:operation name="CreateAppId">
  <wsdl:input message="tns:CreateAppIdSoapIn" />
  <wsdl:output message="tns:CreateAppIdSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification for this operation.

```
<wsdl:operation name="CreateAppId">
  <soap:operation
  soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId"
  style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **CreateAppId** operation requires that the certificate specified in the input message be attached as a **SOAP header** to the request.

3.1.4.2.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
CreateAppIdSoapIn	Specifies the SOAP message that requests the application identifier.
CreateAppIdSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.2.1.1 tns:CreateAppIdSoapIn Message

The **CreateAppIdSoapIn** WSDL message specifies the request to create an application identifier.

```
<wsdl:message name="CreateAppIdSoapIn">
  <wsdl:part name="parameters" element="tns:CreateAppId" />
</wsdl:message>
```

```
</wsdl:message>
```

The **CreateAppIdSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId>.

The parts of the **CreateAppIdSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:CreateAppId (section 3.2.4.2.2.1)	Contains the SOAP body of the request to create an application identifier.

3.1.4.2.1.2 tns:CreateAppIdSoapOut Message

The **CreateAppIdSoapOut** WSDL message specifies the response to a request to create an application identifier.

```
<wsdl:message name="CreateAppIdSoapOut">  
  <wsdl:part name="parameters" element="tns:CreateAppIdResponse" />  
</wsdl:message>
```

The **CreateAppIdSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId>.

The part of the **CreateAppIdSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:CreateAppIdResponse (section 3.2.4.2.2.2)	Specifies the SOAP body of the response that contains the application identifier and administrative key.

3.1.4.2.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
CreateAppId	Specifies the information that is required to establish a relationship with a federation management service.
CreateAppIdResponse	Specifies the response from the CreateAppId operation that contains an application identifier.

3.1.4.2.2.1 tns:CreateAppId Element

The **CreateAppId** element specifies the information that is required to establish a relationship with a federation management service.

```
<xs:element name="CreateAppId">  
  <xs:complexType>  
    <xs:sequence>
```

```

<xs:element name="cerfiticatate"
  type="s:string"
  minOccurs="0"
  maxOccurs="1"
/>
<xs:element name="properties"
  type="tns:ArrayOfProperty"
/>
</xs:sequence>
</xs:complexType>
</xs:element>

```

The following table lists the child elements of the **CreateAppId** element.

Element name	Type	Description
certificate	s:string ([XMLSCHEMA2])	Specifies the certificate that will be used for application identifier management and for encryption of the delegation ticket for this domain. MUST be a string encoded with base64 encoding.
properties	tns:ArrayOfProperty (section 2.2.4.1)	Specifies additional information about the organization. Can be present.

3.1.4.2.2.2 tns:CreateAppIdResponse Element

The **CreateAppIdResponse** element specifies the response from the **CreateAppId** operation, as specified in section [3.1.4.2](#), that contains an application identifier and administrative key.

```

<xs:element name="CreateAppIdResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="CreateAppIdResult"
        type="tns:AppIdInfo"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

The following table lists the child elements of the **CreateAppIdResponse** element.

Element name	Type	Description
CreateAppIdResult	tns:AppIdInfo (section 3.1.4.2.3.1)	Specifies an application identifier and the associated administrative key.

3.1.4.2.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
AppIdInfo	Specifies an application identifier and administrative key.

3.1.4.2.3.1 tns:AppIdInfo Complex Type

The **AppIdInfo** complex type specifies an application identifier and the associated administrative key.

```
<xs:complexType name="AppIdInfo">
  <xs:sequence>
    <xs:element name="AppId"
      type="s:string"
    />
    <xs:element name="AdminKey"
      type="s:string"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **AppIdInfo** complex type.

Element name	Type	Description
AppId	s:string (XMLSCHEMA21)	Specifies an application identifier.
AdminKey	s:string	Specifies the administrative key that is associated with the application identifier.

3.1.4.3 GetDomainInfo Operation

The **GetDomainInfo** operation retrieves federation status information for a domain.

The following is the WSDL port type specification for this operation.

```
<wsdl:operation name="GetDomainInfo">
  <wsdl:input message="tns:GetDomainInfoSoapIn" />
  <wsdl:output message="tns:GetDomainInfoSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification for this operation.

```
<wsdl:operation name="GetDomainInfo">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

```

    </wsdl:output>
</wsdl:operation>

```

3.1.4.3.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
GetDomainInfoSoapIn	Specifies the SOAP message that requests the domain information.
GetDomainInfoSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.3.1.1 tns:GetDomainInfoSoapIn Message

The **GetDomainInfoSoapIn** WSDL message specifies a request to return domain information.

```

<wsdl:message name="GetDomainInfoSoapIn">
  <wsdl:part name="parameters" element="tns:GetDomainInfo" />
</wsdl:message>

```

The **GetDomainInfoSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo>.

The part of the **GetDomainInfoSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:GetDomainInfo (section 3.1.4.3.2.1)	Specifies the SOAP body of the request to return domain information.

3.1.4.3.1.2 tns:GetDomainInfoSoapOut Message

The **GetDomainInfoSoapOut** WSDL message specifies the response to a request for domain information.

```

<wsdl:message name="GetDomainInfoSoapOut">
  <wsdl:part name="parameters" element="tns:GetDomainInfoResponse" />
</wsdl:message>

```

The **GetDomainInfoSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo>.

The part of the **GetDomainInfoSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:GetDomainInfoResponse (section 3.1.4.3.2.2)	Specifies the SOAP body of the response containing information about the requested domain.

3.1.4.3.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
GetDomainInfo	Specifies the information that is required to request domain information from a federation management service.
GetDomainInfoResponse	Specifies the response from the GetDomainInfo operation.

3.1.4.3.2.1 tns:GetDomainInfo Element

The **GetDomainInfo** element specifies the information that is needed to request the current status of a domain.

```
<xs:element name="GetDomainInfo">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
      />
      <xs:element name="domainName"
        type="s:string"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **GetDomainInfo** element.

Element name	Type	Description
ownerAppId	s:string (XMLSCHEMA2)	Specifies the application identifier of the domain owner.
domainName	s:string	Specifies the domain for which information is to be returned.

3.1.4.3.2.2 tns:GetDomainInfoResponse Element

The **GetDomainInfoResponse** element specifies the response from a **GetDomainInfo** operation request.

```
<xs:element name="GetDomainInfoResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="GetDomainInfoResult"
        type="tns:DomainState"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

    </xs:sequence>
  </xs:complexType>
</xs:element>

```

The following table lists the child elements of the **GetDomainInfoResponse** element.

Element name	Type	Description
GetDomainInfoResult	tns:DomainState (section 2.2.5.1)	Specifies the domain status information.

3.1.4.4 ReleaseDomain Operation

The **ReleaseDomain** operation releases the specified domain from federation management services.

The following is the WSDL port type specification for this operation.

```

<wsdl:operation name="ReleaseDomain">
  <wsdl:input message="tns:ReleaseDomainSoapIn" />
  <wsdl:output message="tns:ReleaseDomainSoapOut" />
</wsdl:operation>

```

The following is the WSDL binding specification for this operation.

```

<wsdl:operation name="ReleaseDomain">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>

```

3.1.4.4.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
ReleaseDomainSoapIn	Specifies the SOAP message that requests that the domain be released from the federation management service.
ReleaseDomainSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.4.1.1 tns:ReleaseDomainSoapIn Message

The **ReleaseDomainSoapIn** WSDL message specifies the domain to release from the federation management service.

```
<wsdl:message name="ReleaseDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReleaseDomain" />
</wsdl:message>
```

The **ReleaseDomainSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain>.

The part of the **ReleaseDomainSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:ReleaseDomain (section 3.1.4.4.2.1)	Specifies the SOAP body of the request to release a domain.

3.1.4.4.1.2 tns:ReleaseDomainSoapOut Message

The **ReleaseDomainSoapOut** WSDL message specifies the response from a request to release a domain from the federation management service.

```
<wsdl:message name="ReleaseDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReleaseDomainResponse" />
</wsdl:message>
```

The **ReleaseDomainSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain>.

The part of the **ReleaseDomainSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:ReleaseDomainResponse (section 3.1.4.4.2.2)	Defines the SOAP body of the response from the request to release a domain from the federation management service.

3.1.4.4.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
ReleaseDomain	Specifies the information that is required to release a domain from the federation management service.
ReleaseDomainResponse	Specifies the response from the ReleaseDomain operation.

3.1.4.4.2.1 tns:ReleaseDomain Element

The **ReleaseDomain** element specifies the information that is required for the **ReleaseDomain** operation.

```
<xs:element name="ReleaseDomain">
  <xs:complexType>
```

```

<xs:sequence>
  <xs:element name="ownerAppId"
    type="s:string"
    />
  <xs:element name="domainName"
    type="s:string"
    />
</xs:sequence>
</xs:complexType>
</xs:element>

```

The following table lists the child elements of the **ReleaseDomain** element.

Element name	Type	Description
ownerAppId	s:string (XMLSCHEMA2)	Specifies the application identifier assigned to the domain manager when the domain was registered with the federation management service.
domainName	s:string	Specifies the domain to release.

3.1.4.4.2 tns:ReleaseDomainResponse Element

The **ReleaseDomainResponse** element specifies the response from the **ReleaseDomain** operation.

```

<xs:element name="ReleaseDomainResponse">
  <xs:complexType />
</xs:element>

```

3.1.4.5 RemoveUri Operation

The **RemoveUri** operation removes a previously registered URI from the federation management service.

The following is the WSDL port type specification for the operation.

```

<wsdl:operation name="RemoveUri">
  <wsdl:input message="tns:RemoveUriSoapIn" />
  <wsdl:output message="tns:RemoveUriSoapOut" />
</wsdl:operation>

```

The following is the WSDL binding specification for the operation.

```

<wsdl:operation name="RemoveUri">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri" style="document"
  />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>

```

```

<wsdl:output>
  <soap:body use="literal" />
</wsdl:output>
</wsdl:operation>

```

3.1.4.5.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
RemoveUriSoapIn	Specifies the SOAP message that requests the URI be removed.
RemoveUriSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.5.1.1 tns:RemoveUriSoapIn Message

The **RemoveUriSoapIn** WSDL message defines one part that specifies a request to remove a URI from the federation management server.

```

<wsdl:message name="RemoveUriSoapIn">
  <wsdl:part name="parameters" element="tns:RemoveUri" />
</wsdl:message>

```

The **RemoveUriSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri>.

The part of the **RemoveUriSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:RemoveUri (section 3.1.4.5.2.1)	Specifies the SOAP body of the request that provides the application identifier of the URI owner and the URI to remove from the federation management server.

3.1.4.5.1.2 tns:RemoveUriSoapOut Message

The **RemoveUriSoapOut** WSDL message specifies the response to a request to remove a URI from the federation management server.

```

<wsdl:message name="RemoveUriSoapOut">
  <wsdl:part name="parameters" element="tns:RemoveUriResponse" />
</wsdl:message>

```

The **RemoveUriSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri>.

The part of the **RemoveUriSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:RemoveUriResponse (section 3.1.4.5.2.2)	Specifies the SOAP body of the response from the operation.

3.1.4.5.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
RemoveUri	Specifies the information that is required to remove a URI from the federation management service.
RemoveUriResponse	Specifies the response from the RemoveUri operation.

3.1.4.5.2.1 tns:RemoveUri Element

The **RemoveUri** element specifies the application identifier and URI to remove.

```
<xs:element name="RemoveUri">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
      <xs:element name="uri"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **RemoveUri** element.

Element name	Type	Description
ownerAppId	s:string (XMLSCHEMA2)	Specifies the application identifier of the organization that is removing the URI.
uri	s:string	Specifies the URI to remove.

3.1.4.5.2.2 tns:RemoveUriResponse Element

The **RemoveUriResponse** element specifies the response from the **RemoveUri** operation.

```
<xs:element name="RemoveUriResponse">
```



```
<xs:complexType />
</xs:element>
```

3.1.4.6 ReserveDomain Operation

The **ReserveDomain** operation verifies that a specified domain is to be associated with an application identifier.

The following is the WSDL port type specification for the operation.

```
<wsdl:operation name="ReserveDomain">
  <wsdl:input message="tns:ReserveDomainSoapIn" />
  <wsdl:output message="tns:ReserveDomainSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification for the operation.

```
<wsdl:operation name="ReserveDomain">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

3.1.4.6.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
ReserveDomainSoapIn	Specifies the SOAP message that requests that the domain be reserved.
ReserveDomainSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.6.1.1 tns:ReserveDomainSoapIn Message

The **ReserveDomainSoapIn** WSDL message specifies a request to reserve a domain with the federation management service.

```
<wsdl:message name="ReserveDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReserveDomain" />
</wsdl:message>
```

The **ReserveDomainSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain>.

The part of the **ReserveDomainSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:ReserveDomain (section 3.1.4.6.2.1)	Specifies the SOAP body of the request to reserve a domain.

3.1.4.6.1.2 tns:ReserveDomainSoapOut Message

The **ReserveDomainSoapOut** WSDL message specifies the response from a request to reserve a domain with the federation management server.

```
<wsdl:message name="ReserveDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReserveDomainResponse" />
</wsdl:message>
```

The **ReserveDomainSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain>.

The part of the **ReserveDomainSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:ReserveDomainResponse (section 3.1.4.6.2.2)	Specifies the SOAP body of the response from the operation.

3.1.4.6.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
ReserveDomain	Specifies the information that is required to register a domain with a federation management service.
ReserveDomainResponse	Specifies the response from the ReserveDomain operation.

3.1.4.6.2.1 tns:ReserveDomain Element

The **ReserveDomain** element specifies the information that is required to reserve a domain for federation management by using the **ReserveDomain** operation.

```
<xs:element name="ReserveDomain">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="domainName"
        type="s:string"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

        minOccurs="0"
      />
      <xs:element name="programId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

The following table lists the child elements of the **ReserveDomain** element.

Element name	Type	Description
ownerAppId	s:string ([XMLSCHEMA2])	Specifies the application identifier of the organization that wants to reserve the domain.
domainName	s:string	Specifies the domain name of the domain to reserve for federation management.
programId	s:string	Reserved for future use. <3>

3.1.4.6.2.2 tns:ReserveDomainResponse Element

The **ReserveDomainResponse** element specifies the response from the **ReserveDomain** operation.

```

<xs:element name="ReserveDomainResponse">
  <xs:complexType />
</xs:element>

```

3.1.4.7 UpdateAppIdCertificate Operation

The **UpdateAppIdCertificate** operation updates the security certificate that is associated with an application identifier. After the certificate is updated, all subsequent calls to federation management operations use the new certificate for identification and encryption.

The following is the WSDL port type specification for the operation.

```

<wsdl:operation name="UpdateAppIdCertificate">
  <wsdl:input message="tns:UpdateAppIdCertificateSoapIn" />
  <wsdl:output message="tns:UpdateAppIdCertificateSoapOut" />
</wsdl:operation>

```

The following is the WSDL binding specification for the operation.

```

<wsdl:operation name="UpdateAppIdCertificate">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate"
    style="document" />

```

```

    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>

```

3.1.4.7.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
UpdateAppIdCertificateSoapIn	Specifies the SOAP message that requests that the security certificate be updated.
UpdateAppIdCertificateSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.7.1.1 tns:UpdateAppIdCertificateSoapIn Message

The **UpdateAppIdCertificateSoapIn** WSDL message specifies a request to update the security certificate that is associated with an application identifier.

```

<wsdl:message name="UpdateAppIdCertificateSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificate" />
</wsdl:message>

```

The **UpdateAppIdCertificateSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate>.

The part of the **UpdateAppIdCertificateSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:UpdateAppIdCertificate (section 3.1.4.7.2.1)	Specifies the SOAP body of a request to update the security certificate that is associated with an application identifier.

3.1.4.7.1.2 tns:UpdateAppIdCertificateSoapOut Message

The **UpdateAppIdCertificateSoapOut** WSDL message specifies the response from a request to update the security certificate associated with an application identifier.

```

<wsdl:message name="UpdateAppIdCertificateSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificateResponse" />
</wsdl:message>

```

The **UpdateAppIdCertificateSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate>.

The part of the **UpdateAppIdCertificateSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:UpdateAppIdCertificateResponse (section 3.1.4.7.2.2)	Specifies the SOAP body of the response from the server.

3.1.4.7.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
UpdateAppIdCertificate	Specifies the information that is required to update the security certificate with a federation management service.
UpdateAppIdCertificateResponse	Specifies the response from the UpdateAppIdCertificate operation.

3.1.4.7.2.1 tns:UpdateAppIdCertificate Element

The **UpdateAppIdCertificate** element specifies the authentication information and new certificate to replace the existing certificate for the **UpdateAppIdCertificate** operation.

```
<xs:element name="UpdateAppIdCertificate"
  maxOccurs="1"
  minOccurs="0"
  >
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
        />
      <xs:element name="appIdAdminKey"
        type="s:string"
        />
      <xs:element name="newCertificate"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
        />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **UpdateAppIdCertificate** element.

Element name	Type	Description
appId	s:string	Specifies the application identifier for the organization that is

Element name	Type	Description
	([XMLSCHEMA2])	changing the security certificate that is associated with the application identifier.
appIdAdminKey	s:string	Specifies the administrative key that was associated with the application identifier when the application identifier was created.
newCertificate	s:string	Specifies the new security certificate as a string encoded with base64 encoding.

3.1.4.7.2.2 tns:UpdateAppIdCertificateResponse Element

The **UpdateAppIdCertificateResponse** element specifies the response from the **UpdateAppIdCertificate** operation.

```
<xs:element name="UpdateAppIdCertificateResponse">
  <xs:complexType />
</xs:element>
```

3.1.4.8 UpdateAppIdProperties Operation

The **UpdateAppIdProperties** operation updates the additional information about an organization that is stored with the federation management service.

The following is the WSDL port type specification for the operation.

```
<wsdl:operation name="UpdateAppIdProperties">
  <wsdl:input message="tns:UpdateAppIdPropertiesSoapIn" />
  <wsdl:output message="tns:UpdateAppIdPropertiesSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification for the operation.

```
<wsdl:operation name="UpdateAppIdProperties">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

3.1.4.8.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
UpdateAppIdPropertiesSoapIn	Specifies the SOAP message that requests that the properties be updated.
UpdateAppIdPropertiesSoapOut	Specifies the SOAP message that is returned by the server in response.

3.1.4.8.1.1 tns:UpdateAppIdPropertiesSoapIn Message

The **UpdateAppIdPropertiesSoapIn** WSDL message identifies the application properties to update.

```
<wsdl:message name="UpdateAppIdPropertiesSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdProperties" />
</wsdl:message>
```

The **UpdateAppIdPropertiesSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties>.

The part of the **UpdateAppIdPropertiesSoapIn** WSDL message is described the following table.

Part name	Element/type	Description
parameters	tns:UpdateAppIdProperties (section 3.1.4.8.2.1)	Specifies the SOAP body that identifies the properties to modify.

3.1.4.8.1.2 tns:UpdateAppIdPropertiesSoapOut Message

The **UpdateAppIdPropertiesSoapOut** WSDL message specifies the response from a request to update application properties.

```
<wsdl:message name="UpdateAppIdPropertiesSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdPropertiesResponse" />
</wsdl:message>
```

The **UpdateAppIdPropertiesSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties>.

The part of the **UpdateAppIdPropertiesSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:UpdateAppIdPropertiesResponse (section 3.1.4.8.2.2)	Defines the SOAP body of the response.

3.1.4.8.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
UpdateAppIdProperties	Specifies the information that is required to update the properties that are stored with a federation management service.
UpdateAppIdPropertiesResponse	Specifies the response from the UpdateAppIdProperties operation.

3.1.4.8.2.1 tns:UpdateAppIdProperties Element

The **UpdateAppIdProperties** element specifies the organization properties to modify with the **UpdateAppIdProperties** operation.

```
<xs:element name="UpdateAppIdProperties">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
      <xs:element name="properties"
        type="tns:ArrayOfProperty"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the UpdateAppIdProperties element.

Element name	Type	Description
ownerAppId	s:string ([XMLSCHEMA2])	Specifies the application identifier of the organization that is changing properties.
properties	tns:ArrayOfProperty (section 2.2.4.1)	Specifies one or more properties to modify.

3.1.4.8.2.2 tns:UpdateAppIdPropertiesResponse Element

The **UpdateAppIdPropertiesResponse** element specifies the response from the **UpdateAppIdProperties** operation.

```
<xs:element name="UpdateAppIdPropertiesResponse">
  <xs:complexType />
</xs:element>
```


3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

3.2 ManageDelegation2Soap Client Details

This client protocol is used by client applications to identify server applications and authenticate those server applications.

3.2.1 Abstract Data Model

This section contains a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that specified in this document.

This protocol is used by client applications to identify server applications and authenticate those server applications. It uses the standard Internet authentication techniques specified in [\[SAML\]](#), [\[WSFederation\]](#), [\[WSS\]](#), [\[WSTrust1.4\]](#), and [\[XMLDSig2\]](#) for that identification and authentication.

Clients that implement this protocol take the following steps to establish a relationship with the federation management service:

1. Create an application identifier by using the **CreateAppId** operation, as specified in section [3.2.4.2](#).
2. Create a domain identifier by hashing the URI of the domain and place the domain identifier on the domain's DNS server as a TXT record.
3. Reserve a domain name with the federation management service by using the **ReserveDomain** operation, as specified in section [3.2.4.6](#).
4. Register the URI that is associated with the domain with the federation management service by using the **AddUri** operation, as specified in section [3.2.4.1](#).

Clients can request and modify information stored with the federation management service by doing the following:

- Using the **GetDomainInfo** operation, as specified in section [3.2.4.3](#), to retrieve domain information from the federation management service.
- Modifying the information stored with the federation management service by using the **UpdateAppIdCertificate** operation, as specified in section [3.2.4.7](#), and the **UpdateAppIdProperties** operation, as specified in section [3.2.4.8](#).

Clients can end participation with the federation management service by doing the following:

- Using the **RemoveUri** operation, as specified in section [3.2.4.5](#), to remove a URI registered to the domain.
- Using the **ReleaseDomain** operation, as specified in section [3.2.4.4](#), to remove a registered domain from the federation management service.

3.2.2 Timers

None.

3.2.3 Initialization

Before calling this protocol, the client application requires the following:

- The URL of a service that provides a Federation Metadata Document, as specified in [\[WSFederation\]](#) section 3.1, with the fields and values as specified in section [3.3.<4>](#)
- The URL of a delegation management service that provides services as specified in section [3.2.4.<5>](#)
- A DNS TXT record containing a domain proof string, as specified in section [2.2.4.3](#), on the DNS server for the domain.

3.2.4 Message Processing Events and Sequencing Rules

This protocol uses the operations that are listed in the following table.

Operation name	Description
AddUri	Registers a URI with the federation management service.
CreateAppId	Creates an application identifier for an organization with the federation management service.
GetDomainInfo	Gets domain status information from the federation management service.
ReleaseDomain	Removes a domain from the federation management service.
RemoveUri	Removes a registered URI from the federation management service.
ReserveDomain	Verifies that a domain is managed by the specified application identifier.
UpdateAppIdCertificate	Updates the security certificate associated with an application identifier.
UpdateAppIdProperties	Updates the organizational information associated with an application identifier.

3.2.4.1 AddUri Operation

The **AddUri** operation registers the URI of an organization that participates in the federation management service.

The following is the WSDL port type specification of the operation.

```
<wsdl:operation name="AddUri">
  <wsdl:input message="tns:AddUriSoapIn" />
  <wsdl:output message="tns:AddUriSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification of the operation.

```
<wsdl:operation name="AddUri">
```

```

    <soap12:operation
      soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/AddUri" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>

```

The **AddUriDomainOwnershipProofHeader** message, as specified in section [3.2.4.1.1.1](#), and **AddUriSecurity** message, as specified in section [3.2.4.1.1.2](#), MUST be attached as SOAP headers to **AddUri** operation requests.

3.2.4.1.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
AddUriDomainOwnershipProofHeader	Specifies a SOAP header that authenticates domain ownership.
AddUriSecurity	Specifies a SOAP header that authenticates the request.
AddUriSoapIn	Specifies the SOAP message that requests the application identifier.
AddUriSoapOut	Specifies the SOAP message that is returned by the server in response.

3.2.4.1.1.1 tns:AddUriDomainOwnershipProofHeader Message

The **AddUriDomainOwnershipProofHeader** WSDL message specifies the SOAP header that identifies the requester as the owner of a domain.

```

<wsdl:message name="AddUriDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader" element="tns:DomainOwnershipProofHeader" />
</wsdl:message>

```

The part of the **AddUriDomainOwnershipProofHeader** WSDL message is described in the following table.

Part name	Element/type	Description
DomainOwnershipProofHeader	tns:DomainOwnershipProofHeader (section 2.2.3.1)	Specifies the credentials that are required to prove ownership of a domain that is participating in a federation management service.

3.2.4.1.1.2 tns:AddUriSecurity Message

The **AddUriSecurity** WSDL message specifies the SOAP header that authenticates a request to register a URI with the federation management service.

```
<wsdl:message name="AddUriSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **AddUriSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
Security	s:Security (section 2.2.3.2)	Specifies the SOAP header that contains the security elements needed to authenticate the request.

3.2.4.1.1.3 tns:AddUriSoapIn Message

The **AddUriSoapIn** WSDL message specifies the SOAP message that represents a request to register a URI with the federation management service.

```
<wsdl:message name="AddUriSoapIn">
  <wsdl:part name="parameters" element="tns:AddUri" />
</wsdl:message>
```

The **AddUriSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/AddUri>.

The part of the **AddUriSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:AddUri (section 3.2.4.1.2.1)	Specifies the SOAP body of the request to register a URI with the federation management service.

3.2.4.1.1.4 tns:AddUriSoapOut Message

The **AddUriSoapOut** WSDL message specifies the SOAP message that represents a response from a request to register a URI with the federation management service.

```
<wsdl:message name="AddUriSoapOut">
  <wsdl:part name="parameters" element="tns:AddUriResponse" />
</wsdl:message>
```

The **AddUriSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/AddUri>.

The part of the **AddUriSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:AddUriResponse (section 3.2.4.1.2.2)	Specifies the SOAP body of the response.

3.2.4.1.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
AddUri	Specifies the URI that is to be added to the federation management service.
AddUriResponse	Specifies the response from AddUri operation.

3.2.4.1.2.1 tns:AddUri Element

The **AddUri** element specifies the URI that is to be added to the federation management service by the **AddUri** operation.

```
<xs:element name="AddUri">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="uri"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **AddUri** element.

Element name	Type	Description
appId	s:string ([XMLSCHEMA2])	Specifies the application identifier that is assigned to the entity requesting that the URI be registered with a federation management service.
uri	s:string	Specifies the URI to register with the federation management service.

3.2.4.1.2.2 tns:AddUriResponse Element

The **AddUriResponse** element specifies the response from the **AddUri** operation.

```

<xs:element name="AddUriResponse">
  <xs:complexType />
</xs:element>

```

3.2.4.2 CreateAppId Operation

The **CreateAppId** operation creates an identifier for an organization that participates in a federation management service. The identifier that is returned by the **CreateAppId** operation is used when calling operations on the federation management server to identify the organization that is making the request.

The following is the WSDL port type specification for the operation.

```

<wsdl:operation name="CreateAppId">
  <wsdl:input message="tns:CreateAppIdSoapIn" />
  <wsdl:output message="tns:CreateAppIdSoapOut" />
</wsdl:operation>

```

The following is the WSDL binding specification for the operation.

```

<wsdl:operation name="CreateAppId">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>

```

The **CreateAppIdDomainOwnershipProofHeader** message, as specified in section [3.2.4.2.1.1](#), and **CreateAppIdSecurity** message, as specified in section [3.2.4.2.1.2](#), MUST be attached as SOAP headers to **CreateAppId** operation requests.

3.2.4.2.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CreateAppIdDomainOwnershipProofHeader	Specifies a SOAP header that authenticates domain ownership.
CreateAppIdSecurity	Specifies a SOAP header that authenticates the request.
CreateAppIdSoapIn	Specifies the SOAP message that requests the application identifier.
CreateAppIdSoapOut	Specifies the SOAP message that is returned by the

Message	Description
	server in response.

3.2.4.2.1.1 tns:CreateAppIdDomainOwnershipProofHeader Message

The **CreateAppIdDomainOwnershipProofHeader** WSDL message specifies the SOAP header that identifies the requester as the owner of a domain.

```
<wsdl:message name="CreateAppIdDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader" element="DomainOwnershipProofHeader" />
</wsdl:message>
```

The part of the **CreateAppIdDomainOwnershipProofHeader** WSDL message is described in the following table.

Part name	Element/type	Description
DomainOwnershipProofHeader	tns:DomainOwnershipProofHeader (section 2.2.4.3)	Specifies the SOAP header that contains the credentials that are required to prove ownership of a domain that is participating in a federation management service.

3.2.4.2.1.2 tns:CreateAppIdSecurity Message

The **CreateAppIdSecurity** WSDL message specifies the SOAP header that authenticates a request to create an application identifier with the federation management service.

```
<wsdl:message name="CreateAppIdSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **CreateAppIdSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
Security	s:Security (section 2.2.3.2)	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

3.2.4.2.1.3 tns:CreateAppIdSoapIn Message

The **CreateAppIdSoapIn** WSDL message specifies the SOAP message that represents a request to create an application identifier with the federation management service.

```
<wsdl:message name="CreateAppIdSoapIn">
  <wsdl:part name="parameters" element="tns:CreateAppId" />
</wsdl:message>
```

The **CreateAppIdSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId>.

The part of the **CreateAppIdSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:CreateAppId (section 3.2.4.2.2.1)	Specifies the SOAP body of the request to create an application identifier.

3.2.4.2.1.4 tns:CreateAppIdSoapOut Message

The **CreateAppIdSoapOut** WSDL message specifies the SOAP message that represents a response to a request to create an identifier for an organization that participates in a federation management service.

```
<wsdl:message name="CreateAppIdSoapOut">
  <wsdl:part name="parameters" element="tns:CreateAppIdResponse" />
</wsdl:message>
```

The **CreateAppIdSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId>.

The part of the **CreateAppIdSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:CreateAppIdResponse (section 3.2.4.2.2.2)	Specifies the SOAP body of the response.

3.2.4.2.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
CreateAppId	Specifies the information that is required to establish a relationship with a federation management service.
CreateAppIdResponse	Specifies the response from the CreateAppId operation that contains an application identifier.

3.2.4.2.2.1 tns:CreateAppId Element

The **CreateAppId** element specifies the information that is required to establish a relationship with a federation management service.

```
<xs:element name="CreateAppId">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="uri"
        type="s:string"
        minOccurs="0"/>
```



```

        maxOccurs="1"
      />
      <xs:element name="properties"
        type="tns:ArrayOfProperty"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

The following table lists the child elements of the **CreateAppId** element.

Element name	Type	Description
uri	s:string ([XMLSCHEMA2])	Specifies the URI that identifies the entity requesting an application identifier.
properties	tns:ArrayOfProperty (section 2.2.4.1)	Specifies additional information about the organization. Can be present.

3.2.4.2.2 tns:CreateAppIdResponse Element

The **CreateAppIdResponse** element specifies the response from the **CreateAppId** operation that contains the application identifier.

```

<xs:element name="CreateAppIdResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="CreateAppIdResult"
        type="tns:AppIdInfo"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

The following table lists the child elements of the **CreateAppIdResponse** element.

Element name	Type	Description
CreateAppIdResult	tns:AppIdInfo (section 3.2.4.2.3.1)	Specifies the application identifier. Can be present.

3.2.4.2.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex Type name	Description
AppIdInfo	Specifies an application identifier.

3.2.4.2.3.1 t:AppIdInfo Complex Type

The **AppIdInfo** complex type specifies an application identifier.

```
<xs:complexType name="AppIdInfo">
  <xs:sequence>
    <xs:element name="AppId"
      type="s:string"
      minOccurs="0"
      maxOccurs="1"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **AppIdInfo** complex type.

Element name	Type	Description
AppId	s:string [XMLSCHEMA2]	Specifies an application identifier. Can be present.

3.2.4.3 GetDomainInfo Operation

The **GetDomainInfo** operation retrieves federation status information for a domain.

The following is the WSDL port type specification for the operation.

```
<wsdl:operation name="GetDomainInfo">
  <wsdl:input message="tns:GetDomainInfoSoapIn" />
  <wsdl:output message="tns:GetDomainInfoSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification for the operation.

```
<wsdl:operation name="GetDomainInfo">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **GetDomainInfoSecurity** message, as specified in section [3.2.4.3.1.1](#), MUST be attached as a SOAP header to **GetDomainInfo** operation requests.

3.2.4.3.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
GetDomainInfoSecurity	Specifies a SOAP header that authenticates the request.
GetDomainInfoSoapIn	Specifies the SOAP message that requests the domain information.
GetDomainInfoSoapOut	Specifies the SOAP message that is returned by the server in response.

3.2.4.3.1.1 tns:GetDomainInfoSecurity Message

The **GetDomainSecurity** WSDL message specifies the SOAP header that authenticates a request for domain information from the federation management service.

```
<wsdl:message name="GetDomainInfoSecurity">  
  <wsdl:part name="Security" element="s:Security" />  
</wsdl:message>
```

The part of the **GetDomainSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
Security	s:Security (section 2.2.3.2)	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

3.2.4.3.1.2 tns:GetDomainInfoSoapIn Message

The **GetDomainSoapIn** WSDL message specifies the SOAP message that represents a request for domain information from the federation management service.

```
<wsdl:message name="GetDomainInfoSoapIn">  
  <wsdl:part name="parameters" element="tns:GetDomainInfo" />  
</wsdl:message>
```

The **GetDomainInfoSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo>.

The part of the **GetDomainInfoSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:GetDomainInfo (section 3.2.4.3.2.1)	Specifies the SOAP body of the request for domain information.

3.2.4.3.1.3 tns:GetDomainInfoSoapOut Message

The **GetDomainInfoSoapOut** WSDL message specifies the SOAP message that represents a response to a request for domain information from a federation management service.

```

<wsdl:message name="GetDomainInfoSoapOut">
  <wsdl:part name="parameters" element="tns:GetDomainInfoResponse" />
</wsdl:message>

```

The **GetDomainInfoSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo>.

The part of the **GetDomainInfoSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:GetDomainInfoResponse (section 3.2.4.3.2.2)	Specifies the SOAP body of the response from the server.

3.2.4.3.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
GetDomainInfo	Specifies the information that is required to request domain information from federation management service.
GetDomainInfoResponse	Specifies the response from the GetDomainInfo operation.

3.2.4.3.2.1 tns:GetDomainInfo Element

The **GetDomainInfo** element specifies the information that is required to request domain information from a federation management service.

```

<xs:element name="GetDomainInfo">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="domainName"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

The following table lists the child elements of the **GetDomainInfo** element.

Element name	Type	Description
appId	s:string (XMLSCHEMA21)	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
domainName	s:string	Specifies the domain for which information is requested. Can be present.

3.2.4.3.2.2 tns:GetDomainInfoResponse Element

The **GetDomainInfoResponse** element specifies the response from the **GetDomainInfo** operation that contains the application identifier.

```
<xs:element name="GetDomainInfoResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="GetDomainInfoResult"
        type="tns:DomainInfo"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **GetDomainInfoResponse** element.

Element name	Type	Description
GetDomainInfoResult	tns:DomainInfo (section 2.2.4.2)	Specifies the domain status information. Can be present.

3.2.4.4 ReleaseDomain Operation

The **ReleaseDomain** operation releases the specified domain from federation management services.

The following is WSDL port type specification for the operation.

```
<wsdl:operation name="ReleaseDomain">
  <wsdl:input message="tns:ReleaseDomainSoapIn" />
  <wsdl:output message="tns:ReleaseDomainSoapOut" />
</wsdl:operation>
```

The following is the WSDL binding specification for the operation.

```
<wsdl:operation name="ReleaseDomain">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain"
    style="document" />
</wsdl:operation>
```

```

    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>

```

The **ReleaseDomainSecurity** message, as specified in section [3.2.4.4.1.1](#), MUST be attached as a SOAP header to **ReleaseDomain** operation requests.

3.2.4.4.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
ReleaseDomainSecurity	Specifies a SOAP header that authenticates the request.
ReleaseDomainSoapIn	Specifies the SOAP message that requests the domain information.
ReleaseDomainSoapOut	Specifies the SOAP message that is returned by the server in response.

3.2.4.4.1.1 tns:ReleaseDomainSecurity Message

The **ReleaseDomainSecurity** WSDL message specifies the SOAP header that authenticates a request to release a domain from the federation management service.

```

<wsdl:message name="ReleaseDomainSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>

```

The part of the **ReleaseDomainSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
Security	s:Security (section 2.2.3.2)	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

3.2.4.4.1.2 tns:ReleaseDomainSoapIn Message

The **ReleaseDomainSoapIn** WSDL message specifies the SOAP message that represents a request to release a domain from the federation management service.

```

<wsdl:message name="ReleaseDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReleaseDomain" />
</wsdl:message>

```

The **ReleaseDomainSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain>.

The part of the **ReleaseDomainSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:ReleaseDomain (section 3.2.4.4.2.1)	Specifies the SOAP body the request to release a domain from the federation management service.

3.2.4.4.1.3 tns:ReleaseDomainSoapOut Message

The **ReleaseDomainSoapOut** WSDL message specifies the SOAP message that represents a response to a request to release a domain from federation management service.

```
<wsdl:message name="ReleaseDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReleaseDomainResponse" />
</wsdl:message>
```

The **ReleaseDomainSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain>.

The part of the **ReleaseDomainSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:ReleaseDomainResponse (section 3.2.4.4.2.2)	Specifies the SOAP body of the response from the server.

3.2.4.4.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
ReleaseDomain	Specifies the information that is required to release a domain from federation management service.
ReleaseDomainResponse	Specifies the response from the ReleaseDomain operation.

3.2.4.4.2.1 tns:ReleaseDomain Element

The **ReleaseDomain** element specifies the information that is required to release a domain from federation management service.

```
<xs:element name="ReleaseDomain">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="domainName"
        type="s:string"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

        maxOccurs="1"
    />
</xs:sequence>
</xs:complexType>
</xs:element>

```

The following table lists the child elements of the **ReleaseDomain** element.

Element name	Type	Description
appId	s:string (XMLSCHEMA2)	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
domainName	s:string	Specifies the domain to be released. Can be present.

3.2.4.4.2 tns:ReleaseDomainResponse Element

The **ReleaseDomainResponse** element specifies the response from the **ReleaseDomain** operation.

```

<xs:element name="ReleaseDomainResponse">
  <xs:complexType />
</xs:element>

```

3.2.4.5 RemoveUri Operation

The **RemoveUri** operation removes a previously registered URI from the federation management service.

The following is the WSDL port type specification for the operation.

```

<wsdl:operation name="RemoveUri">
  <wsdl:input message="tns:RemoveUriSoapIn" />
  <wsdl:output message="tns:RemoveUriSoapOut" />
</wsdl:operation>

```

The following is the WSDL binding specification for the operation.

```

<wsdl:operation name="RemoveUri">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri" style="document"
  />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>

```



```
</wsdl:operation>
```

The **RemoveUriSecurity** message, as specified in section [3.2.4.5.1.1](#), MUST be attached as a SOAP header to **RemoveUri** operation requests.

3.2.4.5.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
RemoveUriSecurity	Specifies a SOAP header that authenticates the request.
RemoveUriSoapIn	Specifies the SOAP message that requests the URI be removed.
RemoveUriSoapOut	Specifies the SOAP message that is returned by the server in response.

3.2.4.5.1.1 tns:RemoveUriSecurity Message

The **RemoveUriSecurity** WSDL message specifies the SOAP header that authenticates a request to remove a URI from the federation management service.

```
<wsdl:message name="RemoveUriSecurity">  
  <wsdl:part name="Security" element="s:Security" />  
</wsdl:message>
```

The part of the **RemoveUriSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
Security	s:Security (section 2.2.3.2)	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

3.2.4.5.1.2 tns:RemoveUriSoapIn Message

The **RemoveUriSoapIn** WSDL message specifies the SOAP message that represents a request to remove a URI from the federation management service.

```
<wsdl:message name="RemoveUriSoapIn">  
  <wsdl:part name="parameters" element="tns:RemoveUri" />  
</wsdl:message>
```

The **RemoveUriSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri>.

The part of the **RemoveUriSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:RemoveUri (section 3.2.4.5.1.2)	Specifies the SOAP body of the request to remove the URI

Part name	Element/type	Description
	3.2.4.5.2.1)	from the federation management service.

3.2.4.5.1.3 tns:RemoveUriSoapOut Message

The **RemoveUriSoapOut** WSDL message specifies the SOAP message that represents a response to a request to remove a URI from federation management service.

```
<wsdl:message name="RemoveUriSoapOut">
  <wsdl:part name="parameters" element="tns:RemoveUriResponse" />
</wsdl:message>
```

The **RemoveUriSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri>.

The part of the **RemoveUriSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:RemoveUriResponse (section 3.2.4.5.2.2)	Specifies the SOAP body of the response from the server.

3.2.4.5.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
RemoveUri	Specifies the information that is required to remove a URI from federation management service.
RemoveUriResponse	Specifies the response from the RemoveUri operation.

3.2.4.5.2.1 tns:RemoveUri Element

The **RemoveUri** element specifies the information that is required to remove a URI from federation management service.

```
<xs:element name="RemoveUri">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="uri"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

    </xs:complexType>
</xs:element>

```

The following table lists the child elements of the **RemoveUri** element.

Element name	Type	Description
appId	s:string (XMLSCHEMA21)	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
uri	s:string	Specifies the URI to be removed. Can be present.

3.2.4.5.2.2 tns:RemoveUriResponse Element

The **RemoveUriResponse** element specifies the response from the **RemoveUri** operation.

```

<xs:element name="RemoveUriResponse">
  <xs:complexType />
</xs:element>

```

3.2.4.6 ReserveDomain Operation

The **ReserveDomain** operation verifies that a specified domain is to be associated with an application identifier.

The following is the WSDL port type specification for the operation.

```

<wsdl:operation name="ReserveDomain">
  <wsdl:input message="tns:ReserveDomainSoapIn" />
  <wsdl:output message="tns:ReserveDomainSoapOut" />
</wsdl:operation>

```

The following is the WSDL binding specification for the operation.

```

<wsdl:operation name="ReserveDomain">
  <soap12:operation
soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain"
style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>

```

The **ReserveDomainDomainOwnershipProofHeader** message, as specified in section [3.2.4.6.1.1](#), and the **ReserveDomainSecurity** message, as specified in section [3.2.4.6.1.2](#), MUST be attached as SOAP headers to **ReserveDomain** operation requests.

3.2.4.6.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
ReserveDomainDomainOwnershipProofHeader	Specifies a SOAP header that authenticates domain ownership.
ReserveDomainSecurity	Specifies a SOAP header that authenticates the request.
ReserveDomainSoapIn	Specifies the SOAP message that requests the domain be reserved.
ReserveDomainSoapOut	Specifies the SOAP message that is returned by the server in response.

3.2.4.6.1.1 tns:ReserveDomainDomainOwnershipProofHeader Message

The **ReserveDomainDomainOwnershipProofHeader** WSDL message specifies the SOAP header that identifies the requester as the owner of a domain.

```
<wsdl:message name="ReserveDomainDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader" element="tns:DomainOwnershipProofHeader" />
</wsdl:message>
```

The part of the **ReserveDomainDomainOwnershipProofHeader** WSDL message is described in the following table.

Part name	Element/type	Description
DomainOwnershipProofHeader	tns:DomainOwnershipProofHeader (section 2.2.3.1)	Specifies the SOAP header that contains the credentials that are required to prove ownership of a domain that is participating in a federation management service.

3.2.4.6.1.2 tns:ReserveDomainSecurity Message

The **ReserveDomainSecurity** WSDL message specifies the SOAP header that authenticates a request to reserve a domain with the federation management service.

```
<wsdl:message name="ReserveSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **ReserveSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
Security	s:Security (section 2.2.3.2)	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

3.2.4.6.1.3 tns:ReserveDomainSoapIn Message

The **ReserveDomainSoapIn** WSDL message specifies the SOAP message that represents a request to register a domain with the federation management service.

```
<wsdl:message name="ReserveDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReserveDomain" />
</wsdl:message>
```

The **ReserveDomainSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain>.

The part of the **ReserveDomainSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:ReserveDomain (section 3.2.4.6.2.1)	Specifies the SOAP body of the request to register a domain with the federation management service.

3.2.4.6.1.4 tns:ReserveDomainSoapOut Message

The **ReserveDomainSoapOut** WSDL message specifies the SOAP message that represents a response to a request to register a domain with the federation management service.

```
<wsdl:message name="ReserveDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReserveDomainResponse" />
</wsdl:message>
```

The **ReserveDomainSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain>.

The part of the **ReserveDomainSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:ReserveDomainResponse (section 3.2.4.6.2.2)	Specifies the SOAP body of the response from the server.

3.2.4.6.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
ReserveDomain	Specifies the information that is required to register a domain with a federation management service.
ReserveDomainResponse	Specifies the response from the ReserveDomain operation.

3.2.4.6.2.1 tns:ReserveDomain Element

The **ReserveDomain** element specifies the information that is required to reserve a domain with a federation management service.

```
<xs:element name="ReserveDomain">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="domainName"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="programId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **ReserveDomain** element.

Element name	Type	Description
appId	s:string (XMLSCHEMA2)	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
domainName	s:string	Specifies the domain that is to be registered. Can be present.
programId	s:string	Reserved for future use. <6> Can be present.

3.2.4.6.2.2 tns:ReserveDomainResponse Element

The **ReserveDomainResponse** element specifies the response from the **ReserveDomain** operation.

```

<xs:element name="ReserveDomainResponse">
  <xs:complexType />
</xs:element>

```

3.2.4.7 UpdateAppIdCertificate Operation

The **UpdateAppIdCertificate** operation updates the security certificate that is associated with an application identifier. After the certificate is updated, all subsequent calls to federation management operations use the new certificate for identification and encryption.

The following is the WSDL port type specification for the operation.

```

<wsdl:operation name="UpdateAppIdCertificate">
  <wsdl:input message="tns:UpdateAppIdCertificate SoapIn" />
  <wsdl:output message="tns:UpdateAppIdCertificate SoapOut" />
</wsdl:operation>

```

The following is the WSDL binding specification for the operation.

```

<wsdl:operation name="UpdateAppIdCertificate">
  <soap12:operation
  soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate"
  style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>

```

The **UpdateAppIdCertificateSecurity** message, as specified in section [3.2.4.7.1.1](#), MUST be attached as a SOAP header to **UpdateAppIdCertificate** operation requests.

3.2.4.7.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
UpdateAppIdCertificateSecurity	Specifies a SOAP header that authenticates the request.
UpdateAppIdCertificateSoapIn	Specifies the SOAP message that requests the security certificate be updated.
UpdateAppIdCertificateSoapOut	Specifies the SOAP message that is returned by the server in response.

3.2.4.7.1.1 tns:UpdateAppIdCertificateSecurity Message

The **UpdateAppIdCertificateSecurity** WSDL message specifies the SOAP header that authenticates a request to update the security certificate of the federation management service.

```
<wsdl:message name="UpdateAppIdCertificateSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **UpdateAppIdCertificateSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
Security	s:Security (section 2.2.3.2)	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

3.2.4.7.1.2 tns:UpdateAppIdCertificateSoapIn Message

The **UpdateAppIdCertificateSoapIn** WSDL message specifies the SOAP message that represents a request to update the security certificate with the federation management service.

```
<wsdl:message name="UpdateAppIdCertificateSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificate" />
</wsdl:message>
```

The **UpdateAppIdCertificateSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate>.

The part of the **UpdateAppIdCertificateSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:UpdateAppIdCertificate (section 3.2.4.7.2.1).	Specifies the SOAP body of the request to update the security certificate with the federation management service.

3.2.4.7.1.3 tns:UpdateAppIdCertificateSoapOut Message

The **UpdateAppIdCertificateSoapOut** WSDL message specifies the SOAP message that represents a response to a request to remove a URI from federation management service.

```
<wsdl:message name="UpdateAppIdCertificateSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificateResponse" />
</wsdl:message>
```

The **UpdateAppIdCertificateSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate>.

The **UpdateAppIdCertificateSoapOut** WSDL message specifies one part, as described in the following table.

Part name	Element/type	Description
parameters	tns:UpdateAppIdCertificateResponse (section 3.2.4.7.2.2).	Specifies SOAP body of the response from the server.

3.2.4.7.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
UpdateAppIdCertificate	Specifies the information that is required to update the security certificate with a federation management service.
UpdateAppIdCertificateResponse	Specifies the response from the UpdateAppIdCertificate operation (section 3.2.4.7).

3.2.4.7.2.1 tns:UpdateAppIdCertificate Element

The **UpdateAppIdCertificate** element specifies the information that is required update a security certificate with a federation management service.

```
<xs:element name="UpdateAppIdCertificate">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="newCertificate"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **UpdateAppIdCertificate** element.

Element name	Type	Description
appId	s:string (XMLSCHEMA2)	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
newCertificate	s:string	Specifies the new security certificate as a string encoded with base64 encoding. Can be present.

3.2.4.7.2.2 tns:UpdateAppIdCertificateResponse Element

The **UpdateAppIdCertificateResponse** element specifies the response from the **UpdateAppIdCertificate** operation.

```
<xs:element name="UpdateAppIdCertificateResponse">
  <xs:complexType />
</xs:element>
```

```
</xs:element>
```

3.2.4.8 UpdateAppIdProperties Operation

The **UpdateAppIdProperties** operation updates the additional information about an organization that is stored with the federation management service.

The following is the WSDL port type specification for the operation.

```
<wsdl:operation name="UpdateAppIdProperties">  
  <wsdl:input message="tns:UpdateAppIdPropertiesSoapIn" />  
  <wsdl:output message="tns:UpdateAppIdPropertiesSoapOut" />  
</wsdl:operation>
```

The following is the WSDL binding specification for the operation.

```
<wsdl:operation name="UpdateAppIdProperties">  
  <soap12:operation  
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties"  
    style="document" />  
  <wsdl:input>  
    <soap12:body use="literal" />  
  </wsdl:input>  
  <wsdl:output>  
    <soap12:body use="literal" />  
  </wsdl:output>  
</wsdl:operation>
```

The **UpdateAppIdPropertiesSecurity** message, as specified in section [3.2.4.8.1.1](#), MUST be attached as a SOAP header to **UpdateAppIdProperties** operation requests.

3.2.4.8.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message name	Description
UpdateAppIdPropertiesSecurity	Specifies a SOAP header that authenticates the request.
UpdateAppIdPropertiesSoapIn	Specifies the SOAP message that requests the properties be updated.
UpdateAppIdPropertiesSoapOut	Specifies the SOAP message that is returned by the server in response.

3.2.4.8.1.1 tns:UpdateAppIdPropertiesSecurity Message

The **UpdateAppIdPropertiesSecurity** WSDL message specifies the SOAP header that authenticates a request to update the security certificate of the federation management service.

```
<wsdl:message name="UpdateAppIdPropertiesSecurity">
```

```
<wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **UpdateAppIdPropertiesSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
Security	s:Security (section 2.2.3.2)	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

3.2.4.8.1.2 tns:UpdateAppIdPropertiesSoapIn Message

The **UpdateAppIdPropertiesSoapIn** WSDL message specifies the SOAP message that represents a request to register a domain with the federation management service.

```
<wsdl:message name="UpdateAppIdPropertiesSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdProperties" />
</wsdl:message>
```

The **UpdateAppIdPropertiesSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties>.

The part of the **UpdateAppIdPropertiesSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	tns:UpdateAppIdProperties (section 3.2.4.8.2.1)	Specifies the SOAP body of the request containing the properties to modify.

3.2.4.8.1.3 tns:UpdateAppIdPropertiesSoapOut Message

The **UpdateAppIdPropertiesSoapOut** WSDL message specifies the SOAP message that represents a response to a request to remove a URI from federation management service.

```
<wsdl:message name="UpdateAppIdPropertiesSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdPropertiesResponse" />
</wsdl:message>
```

The **UpdateAppIdPropertiesSoapOut** WSDL message is the output message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties>.

The **UpdateAppIdPropertiesSoapOut** WSDL message specifies one part, as described in the following table.

Part name	Element/type	Description
parameters	tns:UpdateAppIdPropertiesResponse (section 3.2.4.8.2.2)	Specifies the SOAP body of the response from the server.

3.2.4.8.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element name	Description
UpdateAppIdProperties	Specifies the information that is required to update the properties stored with a federation management service.
UpdateAppIdPropertiesResponse	Specifies the response from the UpdateAppIdProperties operation.

3.2.4.8.2.1 tns:UpdateAppIdProperties Element

The **UpdateAppIdProperties** element specifies organization properties to modify with a federation management service.

```
<xs:element name="UpdateAppIdProperties">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="properties"
        type="tns:ArrayOfProperty"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **UpdateAppIdProperties** element.

Element name	Type	Description
appId	s:string ([XMLSCHEMA2])	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
properties	tns:ArrayOfProperty (section 2.2.4.1)	Specifies one or more properties to modify. Can be present.

3.2.4.8.2.2 tns:UpdateAppIdPropertiesResponse Element

The **UpdateAppIdPropertiesResponse** element specifies the response from the **UpdateAppIdProperties** operation.

```
<xs:element name="UpdateAppIdPropertiesResponse">
  <xs:complexType />
```

</xs:element>

3.2.5 Timer Events

None.

3.2.6 Other Local Events

None.

3.3 Federation Metadata Client Details

The Federated Internet Authentication Web Service Protocol uses elements from the Federation Metadata XML Document, as specified in [\[WSFederation\]](#).

The following table lists the **XML** elements and element values that the protocol uses from the Federation Metadata Document.

Element name	Description
FederationMetadata	MUST be present. MUST contain at least one Federation element.
Federation	MUST be present. MUST contain at least one of each of the following elements: <ul style="list-style-type: none">▪ TokenSigningKeyInfo▪ IssuerNamesOffered▪ TargetServiceEndpoints▪ WebRequestorRedirectEndpoints
TokenSigningKeyInfo	At least one instance MUST be present. MUST contain at least one X509Certificate element. The first instance MUST contain the Id attribute with the value "stscer". The second instance, if any, MUST contain the Id attribute with the value "stsbcer".
X509Certificate	MUST be present.
IssuerNamesOffered	MUST be present. MUST contain the uri attribute with the value "uri:WindowsLiveId".
TargetServiceEndpoints	MUST be present. MUST contain at least one Address element which MUST contain a valid absolute path URI.
WebRequestorRedirectEndpoints	MUST be present. MUST contain at least one Address element which MUST contain a valid absolute path URI.

3.3.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations

adhere to this model as long as their external behavior is consistent with that described in this document.

The Federation Metadata Document, as specified in [\[WSFederation\]](#), is stateless; however, the server can cache certain values that are contained in the Federation Metadata Document to improve performance.

3.3.2 Timers

None.

3.3.3 Initialization

None.

3.3.4 Message Processing Events and Sequencing

None.

3.3.4.1 Requesting the Service Issue a Token

This section specifies the required elements and values that the request and response from the STS contain, and the required elements and values of the encrypted and unencrypted tokens.

3.3.4.1.1 Token Request

The following is a token request that is sent to an STS. The required elements and values are specified after the token request.

```
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope"
xmlns:a="http://www.w3.org/2005/08/addressing" xmlns:u="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" xmlns:o="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:t="http://schemas.xmlsoap.org/ws/2005/02/trust"
xmlns:auth="http://schemas.xmlsoap.org/ws/2006/12/authorization"
xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy">
  <s:Header>
    <a:To s:mustUnderstand="1" u:Id="_1">https://login.live-
int.com:44329/liveidSTS.srf</a:To>
    <a:Action
s:mustUnderstand="1">http://schemas.xmlsoap.org/ws/2005/02/trust/RST/Issue</a:Action>
    <a:MessageID>urn:uuid:64f95d31-e078-4f2e-8bb2-d8e6e183a1f0</a:MessageID>
    <a:ReplyTo>
      <a:Address>http://www.w3.org/2005/08/addressing/anonymous</a:Address>
    </a:ReplyTo>
    <o:Security s:mustUnderstand="1">
      <u:Timestamp u:Id="_0">
        <u:Created>2009-09-24T17:34:08Z</u:Created>
        <u:Expires>2009-09-24T17:39:08Z</u:Expires>
      </u:Timestamp>
      <Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
        <SignedInfo>
          <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
          <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
          <Reference URI="#_1">
            <Transforms>
              <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />

```

```

    </Transforms>
    <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
    <DigestValue>Y6HYkPrH5NqSrdcLg8AYXDphZ74=</DigestValue>
  </Reference>
  <Reference URI="#_0">
    <Transforms>
      <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </Transforms>
    <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
    <DigestValue>1Taikh1jTPazJ2KnVddUmByNd/s=</DigestValue>
  </Reference>
</SignedInfo>
<SignatureValue>dbpePnJ3w7i6Ro09jhxzd60HKt3ssZPuSWVk ... ==</SignatureValue>
<KeyInfo>
  <o:SecurityTokenReference>
    <o:KeyIdentifier Value="http://docs.oasis-open.org/wss/2004/01/oasis-200401-
wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</o:KeyIdentifier>
  </o:SecurityTokenReference>
</KeyInfo>
</Signature>
</o:Security>
</s:Header>
<s:Body>
  <t:RequestSecurityToken Id="uuid-e067aa03-623a-4120-b8d9-64b60e8f1104">
    <t:RequestType>http://schemas.xmlsoap.org/ws/2005/02/trust/Issue</t:RequestType>
    <t:TokenType>http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-
1.1#SAMLV1.1</t:TokenType>
    <t:KeyType>http://schemas.xmlsoap.org/ws/2005/02/trust/SymmetricKey</t:KeyType>
    <t:KeySize>256</t:KeySize>
    <t:CanonicalizationAlgorithm>http://www.w3.org/2001/10/xml-exc-
c14n#</t:CanonicalizationAlgorithm>
    <t:EncryptionAlgorithm>http://www.w3.org/2001/04/xmlenc#aes256-
cbc</t:EncryptionAlgorithm>
    <t:EncryptWith>http://www.w3.org/2001/04/xmlenc#aes256-cbc</t:EncryptWith>
    <t:SignWith>http://www.w3.org/2000/09/xmldsig#hmac-sha1</t:SignWith>

    <t:ComputedKeyAlgorithm>http://schemas.xmlsoap.org/ws/2005/02/trust/CK/PSHA1</t:ComputedKeyAl
gorithm>
    <wsp:AppliesTo>
      <a:EndpointReference>
        <a:Address>http://fabrikam.com</a:Address>
      </a:EndpointReference>
    </wsp:AppliesTo>
    <t:OnBehalfOf>
      <saml:Assertion MajorVersion="1" MinorVersion="1" AssertionID="saml-6c5a4142-8257-
4efa-8b45-491feee53159" Issuer="contoso.com" IssueInstant="2009-09-24T17:34:09.095Z"
xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion">
        <saml:Conditions NotBefore="2009-09-24T17:34:09.079Z" NotOnOrAfter="2009-09-
24T17:39:09.079Z">
          <saml:AudienceRestrictionCondition>
            <saml:Audience>uri:WindowsLiveID</saml:Audience>
          </saml:AudienceRestrictionCondition>
        </saml:Conditions>
        <saml:AttributeStatement>
          <saml:Subject>
            <saml:NameIdentifier
Format="http://schemas.microsoft.com/LiveID/Federation/2008/05/ImmutableID">A0/HqOjr7EOU8HUUv
2Tgfg==@contoso.com</saml:NameIdentifier>
          <saml:SubjectConfirmation>

```

```

        <saml:ConfirmationMethod>urn:oasis:names:tc:SAML:1.0:cm:sender-
vouches</saml:ConfirmationMethod>
    </saml:SubjectConfirmation>
</saml:Subject>
    <saml:Attribute AttributeName="EmailAddress"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims">
    <saml:AttributeValue>joe@contoso.com</saml:AttributeValue>
    </saml:Attribute>
</saml:AttributeStatement>
    <saml:AuthenticationStatement
AuthenticationMethod="urn:oasis:names:tc:SAML:1.0:am:password" AuthenticationInstant="2009-
09-24T17:34:09.095Z">
    <saml:Subject>
    <saml:NameIdentifier
Format="http://schemas.microsoft.com/LiveID/Federation/2008/05/ImmutableID">A0/HqOjr7EOU8HUUv
2Tgfg==@contoso.com</saml:NameIdentifier>
    <saml:SubjectConfirmation>
    <saml:ConfirmationMethod>urn:oasis:names:tc:SAML:1.0:cm:sender-
vouches</saml:ConfirmationMethod>
    </saml:SubjectConfirmation>
</saml:Subject>
</saml:AuthenticationStatement>
    <Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
    <SignedInfo>
    <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
    <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
    <Reference URI="#saml-6c5a4142-8257-4efa-8b45-491feee53159">
    <Transforms>
    <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-
signature" />
    <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </Transforms>
    <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
    <DigestValue>2fQF5XM8cqkXR/DOd/TigD3c6YM=</DigestValue>
    </Reference>
    </SignedInfo>
    <SignatureValue>b+MQeAJwIKGjoWgkE1+ookJ626nZ5 ... ==</SignatureValue>
    <KeyInfo>
    <o:SecurityTokenReference xmlns:o="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd">
    <o:KeyIdentifier ValueType="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</o:KeyIdentifier>
    </o:SecurityTokenReference>
    </KeyInfo>
    </Signature>
</saml:Assertion>
</t:OnBehalfOf>
    <auth:AdditionalContext>
    <auth:ContextItem
Scope="http://schemas.xmlsoap.org/ws/2006/12/authorization/ctx/requestor"
Name="http://schemas.microsoft.com/wlid/requestor">
    <auth:Value>contoso.com</auth:Value>
    </auth:ContextItem>
</auth:AdditionalContext>
    <t:Claims Dialect="http://schemas.xmlsoap.org/ws/2006/12/authorization/authclaims">
    <auth:ClaimType
Uri="http://schemas.xmlsoap.org/ws/2006/12/authorization/claims/action">
    <auth:Value>MSExchange.SharingCalendarFreeBusy</auth:Value>
    </auth:ClaimType>

```



```

    </t:Claims>
    <wsp:PolicyReference URI="EX_MBI_FED_SSL"></wsp:PolicyReference>
  </t:RequestSecurityToken>
</s:Body>
</s:Envelope>

```

The following attributes and elements are required.

- **/s:Envelope/s:Header/a:To** The URI in this element is taken from the **/Federation Metadata/Federation/TargetServiceEndpoint** element of the federation metadata document provided by the STS.
- **/s:Envelope/s:Header/o:Security/u:Timestamp/u:Created** The **Coordinated Universal Time (UTC)** time at which the request is made.
- **/s:Envelope/s:Header/o:Security/u:Timestamp/u:Expires** The **UTC** time at which the offer for the authentication token expires. This is the create time plus a duration. [<7>](#)
- **/s:Envelope/s:Header/o:Security/Signature** The standard signature of the **To** and **Timestamp** headers, as specified in [\[XMLDSig2\]](#).
- **/s:Envelope/s:Header/o:Security/Signature/Reference/DigestValue** The digest value that is returned by the specified digest method of the previous **To** and **Timestamp** headers, as specified in [\[XMLDSig2\]](#).
- **/s:Envelope/s:Header/o:Security/Signature/SignatureValue** The signature of the **To** and **Timestamp** headers, as specified in [\[XMLDSig2\]](#).
- **/s:Envelope/s:Header/o:Security/Signature/KeyInfo/o:SecurityTokenReference/o:KeyIdentifier** The **SubjectKeyIdentifier** value of the X509 certificate that is associated with the organization and sent to the STS by using the **CreateAppId** operation, as specified in section [3.2.4.2](#), or **UpdateAppIdCertificate** operation, as specified in section [3.2.4.7](#).
- **/s:Envelope/s:Body/s:RequestSecurityToken/wsp:AppliesTo/a:EndpointReference/a:Address** The URI of the organization to which the token will be sent.
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Assertion** Attributes of the **saml:Assertion** element, as shown in the following table.

Attribute	Value
AssertionId	A unique identifier that identifies this specific token request.
Issuer	The URI of the organization that is requesting the token. This URI is the same as the value that is sent to the STS with the AddUri operation, <8> as specified in section 3.2.4.1 .
IssueInstant	The UTC date and time that the request is made.

- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Conditions** Attributes of the **saml:Conditions** element, as shown in the following table.

Attribute	Value
NotBefore	The UTC date and time that the request is made.

Attribute	Value
NoOnOrAfter	The UTC date and time that the offer expires.

- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Conditions/saml:AudienceRestrictionCondition/saml:Audience** MUST be set to the URI of the STS. <9>
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AttributeStatement/saml:Subject/saml:NameIdentifier** The **Format** attribute of the **saml:NameIdentifier** element MUST be set to an identifier of the user for whom the token is requested. <10>
- **s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AttributeStatement/saml:Attribute** An attribute MUST be set to the e-mail address of the user for whom the token is requested. The **AttributeName** MUST be "EmailAddress".
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AttributeStatement/saml:Attribute/saml:AttributeValue** The e-mail address of the user for whom the token is requested. The domain part of the e-mail address MUST be one of the URI values previously registered with the **AddUri** operation, as specified in section 3.2.4.1.
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AuthenticationStatement/saml:Subject/saml:NameIdentifier** The **Format** attribute of the **saml:NameIdentifier** element MUST be set to an identifier of the user for whom the token is requested. The identifier MUST be the same as the **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AttributeStatement/saml:subject/saml:NameIdentifier** element value. <11>
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AuthenticationStatement/saml:Signature** The **Signature** element is set to the standard XML signature of the **OnBehalfOf** element, as specified in [XMLDSig2]. Expected values for elements of the **Signature** element are as follows:
 - **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AuthenticationStatement/saml:Signature/KeyInfo/o:KeyIdentifier** MUST be the **SubjectKeyIdentifier** element of the X509 certificate that is used when calling the **CreateAppId** operation, as specified as in section 3.2.4.2.
- **/s:Envelope/s:Body/t:RequestSecurityToken/auth:AdditionalContext/auth:ContextItem** A **ContextItem** element with the **Scope** attribute set to "**http://schemas.xmlsoap.org/ws/2006/12/authorization/ctx/requestor**" and the **name** element set to "**http://schemas.microsoft.com/wild/requestor**" MUST be present.
- **/s:Envelope/s:Body/t:RequestSecurityToken/auth:AdditionalContext/auth:ContextItem/auth:Value** MUST be set to the same URI as the value used for the **Issuer** attribute of the **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Assertion** element.
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:Claims** The request MUST contain a **t:Claims** element with the **Dialect** attribute value set to "**http://schemas.xmlsoap.org/ws/2006/12/authorization/authclaims**" and containing at least one **auth:ClaimType** element.
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:Claims/auth:ClaimType** The request MUST contain an **auth:ClaimType** element with the **Uri** attribute value set to

"http://schemas.xmlsoap.org/ws/2006/12/authorization/claims/action" and containing at least one **auth:Value** element.

- **/s:Envelope/s:Body/t:RequestSecurityToken/t:Claims/auth:ClaimType/auth:Value** MUST be set to the name of the token requested. Can be any one of the following names.
 - **MSEExchange.SharingInviteMessage**
 - **MSEExchange.SharingCalendarFreeBusy**
 - **MSEExchange.SharingRead**
 - **MSEExchange.DeliveryExternalSubmit**
 - **MSEExchange.DeliveryInternalSubmit**
 - **MSEExchange.MailboxMove**
 - **MSEExchange.Autodiscover**
 - **MSEExchange.CertificationWS**
 - **MSEExchange.LicensingWS**
- **/s:Envelope/s:Body/t:RequestSecurityToken/wsp:PolicyReference** The request MUST contain one **wsp:Policy** element with the URI attribute value set to the token policy to use. [<12>](#)

3.3.4.1.2 Token Response

The following is a token response that is sent from an STS. The required elements and values are specified after the token response.

```
<S:Envelope xmlns:S="http://www.w3.org/2003/05/soap-envelope" xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" xmlns:wsa="http://www.w3.org/2005/08/addressing">
  <S:Header>
    <wsa:Action xmlns:S="http://www.w3.org/2003/05/soap-envelope"
xmlns:wsa="http://www.w3.org/2005/08/addressing" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" wsu:Id="Action"
S:mustUnderstand="1">http://schemas.xmlsoap.org/ws/2005/02/trust/RSTR/Issue</wsa:Action>
    <wsa:To xmlns:S="http://www.w3.org/2003/05/soap-envelope"
xmlns:wsa="http://www.w3.org/2005/08/addressing" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" wsu:Id="To"
S:mustUnderstand="1">http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:To>
    <wsse:Security S:mustUnderstand="1">
      <wsu:Timestamp xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" wsu:Id="TS">
        <wsu:Created>2009-09-24T17:34:01Z</wsu:Created>
        <wsu:Expires>2009-09-24T17:39:01Z</wsu:Expires>
      </wsu:Timestamp>
    </wsse:Security>
  </S:Header>
  <S:Body>
    <wst:RequestSecurityTokenResponse xmlns:S="http://www.w3.org/2003/05/soap-envelope"
xmlns:wst="http://schemas.xmlsoap.org/ws/2005/02/trust" xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
```

```

xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:psf="http://schemas.microsoft.com/Passport/SoapServices/SOAPFault">
  <wst:TokenType>urn:oasis:names:tc:SAML:1.0</wst:TokenType>
  <wsp:AppliesTo xmlns:wsa="http://www.w3.org/2005/08/addressing">
    <wsa:EndpointReference>
      <wsa:Address>http://fabrikam.com</wsa:Address>
    </wsa:EndpointReference>
  </wsp:AppliesTo>
  <wst:Lifetime>
    <wsu:Created>2009-09-24T17:34:01Z</wsu:Created>
    <wsu:Expires>2009-10-09T17:34:01Z</wsu:Expires>
  </wst:Lifetime>
  <wst:RequestedSecurityToken>
    <EncryptedData xmlns="http://www.w3.org/2001/04/xmlenc#" Id="Assertion0"
Type="http://www.w3.org/2001/04/xmlenc#Element">
      <EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#tripleDES-
cbc"></EncryptionMethod>
      <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <EncryptedKey>
          <EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#rsa-oaep-
mgflp"></EncryptionMethod>
          <ds:KeyInfo Id="keyinfo">
            <wsse:SecurityTokenReference>
              <wsse:KeyIdentifier EncodingType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0#Base64Binary"
ValueType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</wsse:KeyIdentifier>
            </wsse:SecurityTokenReference>
          </ds:KeyInfo>
          <CipherData>
            <CipherValue>mfYn2OYAGs6YaXw5P8L79mmHvHbd3+Of1QWprAmRww/Finek03IEa/r7LlxxGfb7FAA+ScthkQA...
==</CipherValue>
          </CipherData>
        </EncryptedKey>
      </ds:KeyInfo>
      <CipherData>
        <CipherValue>B5B4B/PrdcBj9s8CQxBs6pNNLFlA9VeA4Y5ZIM6VBkDYwX6zmnCmBkOghx9pPrSGxmp2KChWU5QAKHsJ
...==</CipherValue>
      </CipherData>
    </EncryptedData>
  </wst:RequestedSecurityToken>
  <wst:RequestedAttachedReference>
    <wsse:SecurityTokenReference>
      <wsse:KeyIdentifier ValueType="http://docs.oasis-open.org/wss/oasis-wss-saml-token-
profile-1.0#SAMLAssertionID">uuid-c3a658d0-d832-43dc-bf57-2bfba93c13e5</wsse:KeyIdentifier>
    </wsse:SecurityTokenReference>
  </wst:RequestedAttachedReference>
  <wst:RequestedUnattachedReference>
    <wsse:SecurityTokenReference>
      <wsse:KeyIdentifier ValueType="http://docs.oasis-open.org/wss/oasis-wss-saml-token-
profile-1.0#SAMLAssertionID">uuid-c3a658d0-d832-43dc-bf57-2bfba93c13e5</wsse:KeyIdentifier>
    </wsse:SecurityTokenReference>
  </wst:RequestedUnattachedReference>
  <wst:RequestedProofToken>
    <wst:BinarySecret>TfKqVImHiUlePfaBrAE6P6Jevxwl/XF8</wst:BinarySecret>
  </wst:RequestedProofToken>
</wst:RequestSecurityTokenResponse>
</S:Body>

```

</S:Envelope>

The following attributes and elements are required.

- **/s:body/wst:RequestSecurityTokenResponse** The response from the server MUST contain at least one **wst:RequestSecurityTokenResponse** element, as specified in [\[WSTrust1.4\]](#), with child elements as follows.
- **/s:body/wst:RequestSecurityTokenResponse/wsp:AppliesTo** The response MUST contain the **wsp:AppliesTo** element with at least one child **wsa:EndpointReference** element.
- **/s:body/wst:RequestSecurityTokenResponse/wsp:AppliesTo/wsa:EndpointReference/wsa:Address** The **wsa:Address** element MUST contain the same value as the **/s:Envelope/s:Body/t:RequestSecurityToken/wsp:AppliesTo/a:EndpointReference/a:Address** element specified in the token request.
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedSecurityToken** The response MUST contain at most one **wst:RequestedSecurityToken** element that MUST contain one and only one **EncryptedData** child element that contains the encrypted token that will be sent to another service for authentication. The required elements of the token are specified in section [3.3.4.1.3](#).
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference** The response MUST contain at least one **wst:RequestedAttachedReference** element that contains at least one child **wsse:SecurityTokenReference** element.
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference/wsse:SecurityTokenReference** The response MUST contain at least one **wsse:SecurityTokenReference** element that contains at least one child **wsse:KeyIdentifier** element.
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference/wsse:SecurityTokenReference/wsse:KeyIdentifier** The response MUST contain at least one **wsse:KeyIdentifier** element that contains the identifier of the SAML assertion encrypted within the **RequestedSecurityToken** element.
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedProofToken** The response MUST contain at least one **wst:RequestedProofToken** element that contains at least one child **wst:BinarySecret** element.
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference/wst:RequestedProofToken/wst:BinarySecret** The response MUST contain a **BinarySecret** element with the value set to the symmetric key that is encrypted in the **RequestedSecurityToken** element.

3.3.4.1.3 Encrypted and Unencrypted Tokens

This section shows the required attributes and elements of the encrypted and unencrypted tokens that are received from the STS.

The following is an encrypted token from an STS. The required elements and values are specified after the encrypted and unencrypted tokens.

```
<EncryptedData xmlns="http://www.w3.org/2001/04/xmlenc#" Id="Assertion0"
Type="http://www.w3.org/2001/04/xmlenc#Element">
```

```

    <EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#tripleDES-
cbc"></EncryptionMethod>
    <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
      <EncryptedKey>
        <EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#rsa-
oap-mgflp"></EncryptionMethod>
        <ds:KeyInfo Id="keyinfo">
          <wsse:SecurityTokenReference>
            <wsse:KeyIdentifier EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-
soap-message-security-1.0#Base64Binary" ValueType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</wsse:KeyIdentifier>
          </wsse:SecurityTokenReference>
        </ds:KeyInfo>
      <CipherData>
        <CipherValue>mfYn2OYAGs6YaXw5P8L79mmHvHbd3+Of1QWprAmRww/Finek03IEa/r7LlxxGfb7FAA+ScthkQA...
        ==</CipherValue>
      </CipherData>
    </EncryptedKey>
  </ds:KeyInfo>
</CipherData>
<CipherValue>B5B4B/PrdcBj9s8CQxBs6pNNLF1A9VeA4Y5ZIM6VBkDYwX6zmnCmBkOghx9pPrSGxmp2KChWU5QAKHsJ
...==</CipherValue>
</CipherData>
</EncryptedData>

```

The following is an encrypted token from an STS. The required elements and values are specified after the token.

```

<saml:Assertion xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion" AssertionID="uuid-
c3a658d0-d832-43dc-bf57-2bfb93c13e5" IssueInstant="2009-09-24T17:34:01Z"
Issuer="uri:WindowsLiveID" MajorVersion="1" MinorVersion="1">
  <saml:Conditions NotBefore="2009-09-24T17:34:01Z" NotOnOrAfter="2009-10-09T17:34:01Z">
    <saml:AudienceRestrictionCondition>
      <saml:Audience>http://fabrikam.com</samlAudience >
    </saml:AudienceRestrictionCondition>
  </saml:Conditions>
  <saml:AuthenticationStatement AuthenticationInstant="2009-09-24T17:34:01Z"
AuthenticationMethod="urn:oasis:names:tc:SAML:1.0:am:password">
    <saml:Subject>
      <saml:NameIdentifier
Format="http://schemas.xmlsoap.org/claims/UPN">a744b0351351444d3087ca806986b9a0@Live.com</sam
l:NameIdentifier>
      <saml:SubjectConfirmation>
        <saml:ConfirmationMethod>urn:oasis:names:tc:saml:1.0:cm:holder-of-
key</saml:ConfirmationMethod>
        <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
          <e:EncryptedKey xmlns:e="http://www.w3.org/2001/04/xmlenc#">
            <e:EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#rsa-
oap-mgflp"></e:EncryptionMethod>
            <ds:KeyInfo Id="keyinfo">
              <wsse:SecurityTokenReference xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd">
                <wsse:KeyIdentifier EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-soap-message-security-1.0#Base64Binary" ValueType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</wsse:KeyIdentifier>
              </ds:KeyInfo>
            </e:EncryptedKey>
          </ds:KeyInfo>
        </saml:SubjectConfirmation>
      </saml:Subject>
    </saml:AuthenticationStatement>
  </saml:Assertion>

```

```

    </wsse:SecurityTokenReference>
  </ds:KeyInfo>
  <e:CipherData>
    <e:CipherValue>lRRb1PaUiQrsdA0me/Q4Gt6RVHkDm5ehPNZaDoiQ ... ==</e:CipherValue>
  </e:CipherData>
</e:EncryptedKey>
  </ds:KeyInfo>
  </saml:SubjectConfirmation>
</saml:Subject>
</saml:AuthenticationStatement>
<saml:AttributeStatement>
  <saml:Subject>
    <saml:NameIdentifier
Format="http://schemas.xmlsoap.org/claims/UPN">a744b0351351444d3087ca806986b9a0@Live.com</sam
l:NameIdentifier>
    </saml:Subject>
    <saml:Attribute AttributeName="RequestorDomain"
AttributeNameNamespace="http://schemas.microsoft.com/ws/2006/04/identity/claims">
      <saml:AttributeValue>contoso.com</saml:AttributeValue>
    </saml:Attribute>
    <saml:Attribute AttributeName="EmailAddress"
AttributeNameNamespace="http://schemas.xmlsoap.org/claims">
      <saml:AttributeValue>joe@contoso.com</saml:AttributeValue>
    </saml:Attribute>
    <saml:Attribute AttributeName="action"
AttributeNameNamespace="http://schemas.xmlsoap.org/ws/2006/12/authorization/claims">
      <saml:AttributeValue>MSExchange.SharingCalendarFreeBusy</saml:AttributeValue>
    </saml:Attribute>
    <saml:Attribute AttributeName="ThirdPartyRequested"
AttributeNameNamespace="http://schemas.microsoft.com/ws/2006/04/identity/claims">
      <saml:AttributeValue></saml:AttributeValue>
    </saml:Attribute>
    <saml:Attribute AttributeName="AuthenticatingAuthority"
AttributeNameNamespace="http://schemas.microsoft.com/ws/2008/06/identity">
      <saml:AttributeValue>http://contoso.com</saml:AttributeValue>
    </saml:Attribute>
  </saml:AttributeStatement>
  <Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
    <SignedInfo>
      <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-
c14n#"></CanonicalizationMethod>
      <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-
sha1"></SignatureMethod>
      <Reference URI="#uuid-c3a658d0-d832-43dc-bf57-2bfba93c13e5">
        <Transforms>
          <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature"></Transform>
          <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#"></Transform>
        </Transforms>
        <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1"></DigestMethod>
        <DigestValue>DP2Bg6+h59Uw4zc8DjRNJ4UQAlw=</DigestValue>
      </Reference>
    </SignedInfo>
    <SignatureValue>
      baY0k5dLPuPHKcWTgMATaXKEJL4vX8GeWvaQgCeZchNUbXij1BmPH/Lqu/1HtFavGpLDJ+ukbGeV
      vKWveIGCnre8SCYBUBHlwi0FSw+p+pmFG1RytRG4mkAzEI9dskGnW0RlhFfSVDzvnSBGwrNzSH5o
      Y9hKDVT5emRGeYpDQYc=
    </SignatureValue>
    <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#" Id="keyinfo">
      <wsse:SecurityTokenReference xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-
      200401-wss-wssecurity-secext-1.0.xsd">

```

```

    <wsse:KeyIdentifier EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-soap-message-security-1.0#Base64Binary" ValueType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">VbJyIcGL0AjB4/Wm4DgUZux6uUk=</wsse:KeyIdentifier>
    </wsse:SecurityTokenReference>
  </ds:KeyInfo>
</Signature>
</saml:Assertion>

```

The following elements and attributes are required.

- **/saml:Assertion** The **AssertionID** attribute MUST match the **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference/wsse:SecurityTokenReference/wsse:KeyIdentifier** element in the response from the STS.
- **/saml:Assertion/saml:Conditions/saml:AudienceRestrictionCondition/saml:Audience** The **saml:Audience** element MUST contain the same value as the **/s:Envelope/s:Body/t:RequestSecurityToken/wsp:AppliesTo/a:EndpointReference/a:Address** element in the request.
- **/saml:Assertion/saml:AuthenticationStatement/saml:Subject/saml:NameIdentifier** The **saml:NameIdentifier** element MUST be present and MUST be in **UPN** syntax, but can be any value that the STS wants; however it is always the same for each **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AuthenticationStatement/saml:Subject/saml:NameIdentifier** element in the request.
- **/saml:Assertion/saml:AuthenticationStatement/saml:Subject/saml:SubjectConfirmation** The **saml:SubjectConfirmation** element MUST be present and MUST be in the format specified in [\[SAML\]](#).
- **/saml:Assertion/saml:AttributeStatement/saml:Subject/saml:NameIdentifier** The value of the **saml:NameIdentifier** element MUST be the same as the **/saml:Assertion/saml:AuthenticationStatement/saml:Subject/saml:NameIdentifier** element.
- **/saml:Assertion/saml:AttributeStatement/saml:Attribute** The **saml:Attribute** element MUST contain the attributes of the **AttributeValue** child element of the **Attribute** element that are listed in the following table.

Attribute name	AttributeValue element
RequestorDomain	MUST be the same as the /s:Envelope/s:Body/s:RequestSecurityToken/auth:AdditionalContext/auth:ContextItem/auth:Value element in the token request.
EmailAddresses	MUST be the same as the /s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Assertion/saml:AttributeStatement/saml:Attribute@[EmailAddress]\AttributeValue element in the token request.
action	MUST be the same as the /s:Envelope/s:Body/t:RequestSecurityToken/t:Claims\auth:ClaimType@[.../Action]\auth:Value element in the token request.
ThirdPartyRe	MUST NOT contain a value.

Attribute name	AttributeValue element
quested	
AuthenticatingAuthority	MUST contain a domain name previously registered with the AddUri operation, as specified in section 3.2.4.1 .

- **/saml:Assertion/Signature** The **Signature** element MUST be a standard signature, as specified in [\[XMLDSig2\]](#), and MUST sign the entire **Assertion** element.

3.3.5 Timer Events

None.

3.3.6 Other Local Events

None.

4 Protocol Examples

The following examples show the XML messages that are used by the Federated Internet Authentication Web Service Protocol. Where the Federated Internet Authentication Web Service Protocol requires specific values in an element of the XML document, the element node is described by using the syntax described in [\[XPATH\]](#).

4.1 Registering with a Security Token Service

The following examples show the XML messages that are used by the Federated Internet Authentication Web Service Protocol to communicate with the Managed Delegation Web service that is exposed by an STS. Where the Federated Internet Authentication Web Service Protocol requires specific values in an element of the XML document, the element node is described by using the syntax described in [\[XPATH\]](#).

4.1.1 Creating an Application Identifier

This example shows the request and response messages that are sent to and received from the **CreateAppId** operation.

The following is an example of the request that was sent to the **CreateAppId** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CreateAppId xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <certificate>MIIFCjCCBLsGAWIBAgIKFZsHigAGA...</certificate>
    </CreateAppId>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/CreateAppId/certificate:** The certificate in base64 encoding that will be used to identify requests from the organization and to encrypt information sent to the organization.

The following is an example of the response that is returned by the **CreateAppId** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CreateAppIdResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <CreateAppIdResult>
        <AppId>0000000060000EB9</AppId>
        <AdminKey>6MoW1lqVuL/sYZFCNPcGRhn+dyVX4TR4J9xFZsB7jKU</AdminKey>
      </CreateAppIdResult>
    </CreateAppIdResponse>
  </soap:Body>
```

```
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/CreateAppIdResponse/CreateAppIdResult/AppId:** The application identifier that is assigned to the organization by the STS. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/CreateAppIdResponse/CreateAppIdResult/AdminKey:** The administrative key that is assigned to the organization by the STS. This key is used to identify the organization when changing administrative information that is maintained by the STS. The administrative key can be any combination of letters and numbers.

4.1.2 Reserving a Federated Organization Domain

This example shows the request and response messages that are sent to and received from the **ReserveDomain** operation.

The following is an example of the request that is sent to the **ReserveDomain** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <ReserveDomain xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <ownerAppId>0000000060000EB9</ownerAppId>
      <domainName>contoso.com</domainName>
      <programId></programId>
    </ReserveDomain>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements used in the example:

- **/soap:Envelope/soap:Body/ReserveDomain/ownerAppId:** The application identifier that is assigned to the organization by the STS. This value is returned in response to the **CreateAppId** operation.
- **/soap:Envelope/soap:Body/ReserveDomain/domainName:** The domain name of the organization.
- **/soap:Envelope/soap:Body/ReserveDomain/programId:** This element is reserved for future use.

The following is an example of the response that is returned by the **ReserveDomain** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <ReserveDomainResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0" />
  </soap:Body>
</soap:Envelope>
```

```
</soap:Body>
</soap:Envelope>
```

4.1.3 Retrieving Domain Information

This example shows the request and response messages that are sent to and received from the **GetDomainInfo** operation.

The following is an example of the request that is sent to the **GetDomainInfo** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetDomainInfo xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <ownerAppId>0000000060000EB9</ownerAppId>
      <domainName>contoso.com</domainName>
    </GetDomainInfo>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/GetDomainInfo/ownerAppId:** The application identifier that is assigned to the organization by the STS. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/GetDomainInfo/domainName:** The domain name of the organization.

The following is an example of the response that is returned by the **GetDomainInfo** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetDomainInfoResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <GetDomainInfoResult>
        <DomainName>vyotqn-dom.extest.microsoft.com</DomainName>
        <AppId>0000000060000EB9</AppId>
        <DomainState>Active</DomainState>
      </GetDomainInfoResult>
    </GetDomainInfoResponse>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used the example:

- **/soap:Envelope/soap:Body/GetDomainInfoResponse/GetDomainInfoResult/DomainName:** The domain registered by the organization with the STS.
- **/soap:Envelope/soap:Body/GetDomainInfoResponse/GetDomainInfoResult/AppId:** The application identifier that is assigned to the organization by the STS. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/GetDomainInfoResponse/GetDomainInfoResult/DomainState:** The current state of the domain. The possible states are described by the **DomainState** simple type, as described in section [2.2.5.1](#).

4.1.4 Registering a Domain Name

This example shows the request and response messages that are sent to and received from the **AddUri** operation.

The following is an example of the request that is sent to the **AddUri** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <AddUri xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <ownerAppId>0000000060000EB9</ownerAppId>
      <uri>VYOTQN-DOM.EXTEST.MICROSOFT.COM</uri>
    </AddUri>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/AddUri/ownerAppId:** The application identifier that is assigned to the organization by the STS. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/AddUri/uri:** The domain name of the organization.

The following is an example of the response that is returned by the **AddUri** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <AddUriResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0" />
  </soap:Body>
</soap:Envelope>
```

4.1.5 Removing a Registered Domain Name

This example shows the request and response messages that are sent to and received from the **RemoveUri** operation.

The following is an example of the request that is sent to the **RemoveUri** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <RemoveUri xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <ownerAppId>0000000060000EB9</ownerAppId>
      <uri>contoso.com</uri>
    </RemoveUri>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/RemoveUri/ownerAppId:** The application identifier that is assigned to the organization by the STS. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/RemoveUri/uri:** The organization domain name to remove.

The following is an example of the response that is returned by the **RemoveUri** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <RemoveUriResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0" />
  </soap:Body>
</soap:Envelope>
```

4.1.6 Updating a Certificate

This example shows the request and response messages that are sent to and received from the **UpdateAppIdCertificate** operation.

The following is an example of the request that is sent to the **UpdateAppIdCertificate** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
```

```

    <UpdateAppIdCertificate xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <appId>0000000060000EB9</appId>
      <appIdAdminKey>6MoWllqVuL/sYZFCNPcGRhn+dyVX4TR4J9xFZsB7jKU=</appIdAdminKey>
      <newCertificate>MIIFTTCBPegAwIBAgIKIl... </newCertificate>
    </UpdateAppIdCertificate>
  </soap:Body>
</soap:Envelope>

```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/UpdateAppIdCertificate/appId:** The application identifier that is assigned to the organization by the STS. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/UpdateAppIdCertificate/apIdAdminKey:** The administrative key that is assigned to the organization by the STS.
- **/soap:Envelope/soap:Body/UpdateAppIdCertificate/newCertificate:** The new certificate in base64 encoding that will be used to identify requests from the organization and to encrypt information that is sent to the organization.

The following is an example of the response that is returned by the **UpdateAppIdCertificate** operation.

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <UpdateAppIdCertificateResponse
      xmlns="http://domains.live.com/Service/ManageDelegation/V1.0" />
    </soap:Body>
  </soap:Envelope>

```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

The XML files that are listed in the following table are required in order to implement the functionality specified in this document.

File name	Description	Section
ManageLiveFederation.wsdl	Defines the ManageDelegationSoap client protocol.	6.1
ManageDelegation2.wsdl	Defines the ManageDelegation2Soap client protocol.	6.2

For ease of implementation, the full WSDL files are provided in the following sections.

6.1 ManageDelegationSoap WSDL

This section contains the WSDL that defines the operations, messages, types, and elements used by the **ManageDelegationSoap** client protocol described in section [3.1](#).

```
<?xml version="1.0" encoding="us-ascii"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:tns="http://domains.live.com/Service/ManageDelegation/V1.0"
  xmlns:s="http://www.w3.org/2001/XMLSchema"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
  xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
  targetNamespace="http://domains.live.com/Service/ManageDelegation/V1.0"
  xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <s:schema elementFormDefault="qualified"
      targetNamespace="http://domains.live.com/Service/ManageDelegation/V1.0">
      <s:element name="CreateAppId">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="certificate"
              type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="properties"
              type="tns:ArrayOfProperty" />
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:complexType name="ArrayOfProperty">
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="unbounded" name="Property" nillable="true"
            type="tns:Property" />
        </s:sequence>
      </s:complexType>
      <s:complexType name="Property">
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="1" name="Name" type="s:string" />
          <s:element minOccurs="0" maxOccurs="1" name="Value" type="s:string" />
        </s:sequence>
      </s:complexType>
      <s:element name="CreateAppIdResponse">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="CreateAppIdResult"
              type="tns:AppIdInfo" />
          </s:sequence>
        </s:complexType>
      </s:element>
    </s:schema>
  </wsdl:types>

```

```

    </s:complexType>
  </s:element>
  <s:complexType name="AppIdInfo">
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="AppId" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="AdminKey" type="s:string" />
    </s:sequence>
  </s:complexType>
  <s:element name="UpdateAppIdCertificate">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="appIdAdminKey"
          type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="newCertificate"
          type="s:string" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:element name="UpdateAppIdCertificateResponse">
    <s:complexType />
  </s:element>
  <s:element name="UpdateAppIdProperties">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="properties"
          type="tns:ArrayOfProperty" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:element name="UpdateAppIdPropertiesResponse">
    <s:complexType />
  </s:element>
  <s:element name="AddUri">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
          type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:element name="AddUriResponse">
    <s:complexType />
  </s:element>
  <s:element name="RemoveUri">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
          type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:element name="RemoveUriResponse">
    <s:complexType />
  </s:element>
  <s:element name="ReserveDomain">

```

```

<s:complexType>
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
      type="s:string" />
    <s:element minOccurs="0" maxOccurs="1" name="domainName"
      type="s:string" />
    <s:element minOccurs="0" maxOccurs="1" name="programId"
      type="s:string" />
  </s:sequence>
</s:complexType>
</s:element>
<s:element name="ReserveDomainResponse">
  <s:complexType />
</s:element>
<s:element name="ReleaseDomain">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="domainName"
        type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="ReleaseDomainResponse">
  <s:complexType />
</s:element>
<s:element name="GetDomainInfo">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="domainName"
        type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="GetDomainInfoResponse">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="GetDomainInfoResult"
        type="tns:DomainInfo" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:complexType name="DomainInfo">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="1" name="DomainName"
      type="s:string" />
    <s:element minOccurs="0" maxOccurs="1" name="AppId" type="s:string" />
    <s:element minOccurs="1" maxOccurs="1" name="DomainState"
      type="tns:DomainState" />
  </s:sequence>
</s:complexType>
<s:simpleType name="DomainState">
  <s:restriction base="s:string">
    <s:enumeration value="PendingActivation" />
    <s:enumeration value="Active" />
    <s:enumeration value="PendingRelease" />
  </s:restriction>
</s:simpleType>

```

```

        </s:restriction>
    </s:simpleType>
</s:schema>
</wsdl:types>
<wsdl:message name="CreateAppIdSoapIn">
    <wsdl:part name="parameters" element="tns:CreateAppId" />
</wsdl:message>
<wsdl:message name="CreateAppIdSoapOut">
    <wsdl:part name="parameters" element="tns:CreateAppIdResponse" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSoapIn">
    <wsdl:part name="parameters" element="tns:UpdateAppIdCertificate" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSoapOut">
    <wsdl:part name="parameters" element="tns:UpdateAppIdCertificateResponse" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSoapIn">
    <wsdl:part name="parameters" element="tns:UpdateAppIdProperties" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSoapOut">
    <wsdl:part name="parameters" element="tns:UpdateAppIdPropertiesResponse" />
</wsdl:message>
<wsdl:message name="AddUriSoapIn">
    <wsdl:part name="parameters" element="tns:AddUri" />
</wsdl:message>
<wsdl:message name="AddUriSoapOut">
    <wsdl:part name="parameters" element="tns:AddUriResponse" />
</wsdl:message>
<wsdl:message name="RemoveUriSoapIn">
    <wsdl:part name="parameters" element="tns:RemoveUri" />
</wsdl:message>
<wsdl:message name="RemoveUriSoapOut">
    <wsdl:part name="parameters" element="tns:RemoveUriResponse" />
</wsdl:message>
<wsdl:message name="ReserveDomainSoapIn">
    <wsdl:part name="parameters" element="tns:ReserveDomain" />
</wsdl:message>
<wsdl:message name="ReserveDomainSoapOut">
    <wsdl:part name="parameters" element="tns:ReserveDomainResponse" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSoapIn">
    <wsdl:part name="parameters" element="tns:ReleaseDomain" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSoapOut">
    <wsdl:part name="parameters" element="tns:ReleaseDomainResponse" />
</wsdl:message>
<wsdl:message name="GetDomainInfoSoapIn">
    <wsdl:part name="parameters" element="tns:GetDomainInfo" />
</wsdl:message>
<wsdl:message name="GetDomainInfoSoapOut">
    <wsdl:part name="parameters" element="tns:GetDomainInfoResponse" />
</wsdl:message>
<wsdl:portType name="ManageDelegationSoap">
    <wsdl:operation name="CreateAppId">
        <wsdl:input message="tns:CreateAppIdSoapIn" />
        <wsdl:output message="tns:CreateAppIdSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="UpdateAppIdCertificate">
        <wsdl:input message="tns:UpdateAppIdCertificateSoapIn" />

```

```

    <wsdl:output message="tns:UpdateAppIdCertificateSoapOut" />
</wsdl:operation>
<wsdl:operation name="UpdateAppIdProperties">
    <wsdl:input message="tns:UpdateAppIdPropertiesSoapIn" />
    <wsdl:output message="tns:UpdateAppIdPropertiesSoapOut" />
</wsdl:operation>
<wsdl:operation name="AddUri">
    <wsdl:input message="tns:AddUriSoapIn" />
    <wsdl:output message="tns:AddUriSoapOut" />
</wsdl:operation>
<wsdl:operation name="RemoveUri">
    <wsdl:input message="tns:RemoveUriSoapIn" />
    <wsdl:output message="tns:RemoveUriSoapOut" />
</wsdl:operation>
<wsdl:operation name="ReserveDomain">
    <wsdl:input message="tns:ReserveDomainSoapIn" />
    <wsdl:output message="tns:ReserveDomainSoapOut" />
</wsdl:operation>
<wsdl:operation name="ReleaseDomain">
    <wsdl:input message="tns:ReleaseDomainSoapIn" />
    <wsdl:output message="tns:ReleaseDomainSoapOut" />
</wsdl:operation>
<wsdl:operation name="GetDomainInfo">
    <wsdl:input message="tns:GetDomainInfoSoapIn" />
    <wsdl:output message="tns:GetDomainInfoSoapOut" />
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="ManageDelegationSoap" type="tns:ManageDelegationSoap">
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
    <wsdl:operation name="CreateAppId">
        <soap:operation
            soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
                CreateAppId" style="document" />
        <wsdl:input>
            <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateAppIdCertificate">
        <soap:operation
            soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
                UpdateAppIdCertificate" style="document" />
        <wsdl:input>
            <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateAppIdProperties">
        <soap:operation
            soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
                UpdateAppIdProperties" style="document" />
        <wsdl:input>
            <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>

```

```

        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="AddUri">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        AddUri" style="document" />
    <wsdl:input>
        <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RemoveUri">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        /RemoveUri" style="document" />
    <wsdl:input>
        <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReserveDomain">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        ReserveDomain" style="document" />
    <wsdl:input>
        <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReleaseDomain">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        ReleaseDomain" style="document" />
    <wsdl:input>
        <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDomainInfo">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        GetDomainInfo" style="document" />
    <wsdl:input>
        <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>

```

```

<wsdl:binding name="ManageDelegationSoap12" type="tns:ManageDelegationSoap">
  <soap12:binding transport="http://schemas.xmlsoap.org/soap/http" />
  <wsdl:operation name="CreateAppId">
    <soap12:operation
      soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        CreateAppId" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdCertificate">
    <soap12:operation
      soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        UpdateAppIdCertificate" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdProperties">
    <soap12:operation
      soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        UpdateAppIdProperties" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="AddUri">
    <soap12:operation
      soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        AddUri" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="RemoveUri">
    <soap12:operation
      soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        RemoveUri" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="ReserveDomain">
    <soap12:operation

```

```

        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        ReserveDomain" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReleaseDomain">
    <soap12:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        ReleaseDomain" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDomainInfo">
    <soap12:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/
        GetDomainInfo" style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="ManageDelegation">
    <wsdl:port name="ManageDelegationSoap" binding="tns:ManageDelegationSoap">
        <soap:address location="https://domains-tst.live-int.com/service/
        managedelegation.asmx" />
    </wsdl:port>
    <wsdl:port name="ManageDelegationSoap12" binding="tns:ManageDelegationSoap12">
        <soap12:address location="https://domains-tst.live-int.com/service/
        managedelegation.asmx" />
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>

```

6.2 ManageDelegation2Soap WSDL

This section contains the WSDL that defines the operations, messages, types, and elements used by the **ManageDelegation2Soap** client protocol described in section [3.2](#).

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
    xmlns:s3="http://www.w3.org/2000/09/xmldsig#"
    xmlns:tns="http://domains.live.com/Service/ManageDelegation2/V1.0"
    xmlns:s1="http://docs.oasis-open.org/wss/2004/01/
    oasis-200401-wss-wssecurity-secext-1.0.xsd"
    xmlns:s="http://www.w3.org/2001/XMLSchema"
    xmlns:s2="http://docs.oasis-open.org/

```



```

    wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
targetNamespace="http://domains.live.com/Service/ManageDelegation2/V1.0"
xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/">
<wsdl:types>
  <s:schema elementFormDefault="qualified"
    targetNamespace="http://domains.live.com/Service/ManageDelegation2/V1.0">
    <s:element name="CreateAppId">
      <s:complexType>
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
          <s:element minOccurs="0" maxOccurs="1" name="properties"
            type="tns:ArrayOfProperty" />
        </s:sequence>
      </s:complexType>
    </s:element>
    <s:complexType name="ArrayOfProperty">
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="unbounded" name="Property"
          type="tns:Property" />
      </s:sequence>
    </s:complexType>
    <s:complexType name="Property">
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="Name" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="Value" type="s:string" />
      </s:sequence>
    </s:complexType>
    <s:element name="CreateAppIdResponse">
      <s:complexType>
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="1" name="CreateAppIdResult"
            type="tns:AppIdInfo" />
        </s:sequence>
      </s:complexType>
    </s:element>
    <s:complexType name="AppIdInfo">
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="AppId" type="s:string" />
      </s:sequence>
    </s:complexType>
    <s:element name="DomainOwnershipProofHeader" type="tns:DomainOwnershipProofHeader" />
    <s:complexType name="DomainOwnershipProofHeader">
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="Domain" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="HashAlgorithm"
          type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="Signature"
          type="s:string" />
      </s:sequence>
      <s:anyAttribute />
    </s:complexType>
    <s:element name="UpdateAppIdCertificate">
      <s:complexType>
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
          <s:element minOccurs="0" maxOccurs="1" name="newCertificate"
            type="s:string" />
        </s:sequence>
      </s:complexType>
    </s:element>
  </s:schema>
</wsdl:types>

```

```

    </s:complexType>
  </s:element>
  <s:element name="UpdateAppIdCertificateResponse">
    <s:complexType />
  </s:element>
  <s:element name="UpdateAppIdProperties">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="properties"
          type="tns:ArrayOfProperty" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:element name="UpdateAppIdPropertiesResponse">
    <s:complexType />
  </s:element>
  <s:element name="AddUri">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:element name="AddUriResponse">
    <s:complexType />
  </s:element>
  <s:element name="RemoveUri">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:element name="RemoveUriResponse">
    <s:complexType />
  </s:element>
  <s:element name="ReserveDomain">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="domainName"
          type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="programId" type="s:string" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:element name="ReserveDomainResponse">
    <s:complexType />
  </s:element>
  <s:element name="ReleaseDomain">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="domainName"
          type="s:string" />
      </s:sequence>
    </s:complexType>
  </s:element>

```

```

    </s:complexType>
  </s:element>
  <s:element name="ReleaseDomainResponse">
    <s:complexType />
  </s:element>
  <s:element name="GetDomainInfo">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="domainName"
          type="s:string" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:element name="GetDomainInfoResponse">
    <s:complexType>
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="GetDomainInfoResult"
          type="tns:DomainInfo" />
      </s:sequence>
    </s:complexType>
  </s:element>
  <s:complexType name="DomainInfo">
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="DomainName"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="AppId" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="DomainState"
        type="tns:DomainState" />
    </s:sequence>
  </s:complexType>
  <s:simpleType name="DomainState">
    <s:restriction base="s:string">
      <s:enumeration value="PendingActivation" />
      <s:enumeration value="Active" />
      <s:enumeration value="PendingRelease" />
    </s:restriction>
  </s:simpleType>
</s:schema>
<s:schema elementFormDefault="qualified"
  targetNamespace="http://docs.oasis-open.org/wss/2004/01/
  oasis-200401-wss-wssecurity-secext-1.0.xsd">
  <s:import
    namespace="http://docs.oasis-open.org/wss/2004/01/
    oasis-200401-wss-wssecurity-utility-1.0.xsd" />
  <s:import namespace="http://www.w3.org/2000/09/xmldsig#" />
  <s:element name="Security" type="s1:WSSecurityHeader" />
  <s:complexType name="WSSecurityHeader">
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" ref="s2:Timestamp" />
      <s:element minOccurs="0" maxOccurs="1" ref="s3:Signature" />
    </s:sequence>
    <s:anyAttribute />
  </s:complexType>
</s:schema>
<s:schema elementFormDefault="qualified"
  targetNamespace="http://docs.oasis-open.org/wss/2004/01/
  oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <s:element name="Timestamp">

```

```

    <s:complexType mixed="true">
      <s:sequence>
        <s:any maxOccurs="unbounded" />
      </s:sequence>
      <s:anyAttribute />
    </s:complexType>
  </s:element>
</s:schema>
<s:schema elementFormDefault="qualified"
  targetNamespace="http://www.w3.org/2000/09/xmldsig#">
  <s:element name="Signature">
    <s:complexType mixed="true">
      <s:sequence>
        <s:any maxOccurs="unbounded" />
      </s:sequence>
      <s:anyAttribute />
    </s:complexType>
  </s:element>
</s:schema>
</wsdl:types>
<wsdl:message name="CreateAppIdSoapIn">
  <wsdl:part name="parameters" element="tns:CreateAppId" />
</wsdl:message>
<wsdl:message name="CreateAppIdSoapOut">
  <wsdl:part name="parameters" element="tns:CreateAppIdResponse" />
</wsdl:message>
<wsdl:message name="CreateAppIdSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="CreateAppIdDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader"
    element="tns:DomainOwnershipProofHeader" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificate" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificateResponse" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdProperties" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdPropertiesResponse" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="AddUriSoapIn">
  <wsdl:part name="parameters" element="tns:AddUri" />
</wsdl:message>
<wsdl:message name="AddUriSoapOut">
  <wsdl:part name="parameters" element="tns:AddUriResponse" />
</wsdl:message>
<wsdl:message name="AddUriSecurity">
  <wsdl:part name="Security" element="s1:Security" />

```

```

</wsdl:message>
<wsdl:message name="AddUriDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader"
    element="tns:DomainOwnershipProofHeader" />
</wsdl:message>
<wsdl:message name="RemoveUriSoapIn">
  <wsdl:part name="parameters" element="tns:RemoveUri" />
</wsdl:message>
<wsdl:message name="RemoveUriSoapOut">
  <wsdl:part name="parameters" element="tns:RemoveUriResponse" />
</wsdl:message>
<wsdl:message name="RemoveUriSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="ReserveDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReserveDomain" />
</wsdl:message>
<wsdl:message name="ReserveDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReserveDomainResponse" />
</wsdl:message>
<wsdl:message name="ReserveDomainSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="ReserveDomainDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader"
    element="tns:DomainOwnershipProofHeader" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReleaseDomain" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReleaseDomainResponse" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="GetDomainInfoSoapIn">
  <wsdl:part name="parameters" element="tns:GetDomainInfo" />
</wsdl:message>
<wsdl:message name="GetDomainInfoSoapOut">
  <wsdl:part name="parameters" element="tns:GetDomainInfoResponse" />
</wsdl:message>
<wsdl:message name="GetDomainInfoSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:portType name="ManageDelegation2Soap">
  <wsdl:operation name="CreateAppId">
    <wsdl:input message="tns:CreateAppIdSoapIn" />
    <wsdl:output message="tns:CreateAppIdSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdCertificate">
    <wsdl:input message="tns:UpdateAppIdCertificateSoapIn" />
    <wsdl:output message="tns:UpdateAppIdCertificateSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdProperties">
    <wsdl:input message="tns:UpdateAppIdPropertiesSoapIn" />
    <wsdl:output message="tns:UpdateAppIdPropertiesSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="AddUri">

```

```

    <wsdl:input message="tns:AddUriSoapIn" />
    <wsdl:output message="tns:AddUriSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="RemoveUri">
    <wsdl:input message="tns:RemoveUriSoapIn" />
    <wsdl:output message="tns:RemoveUriSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="ReserveDomain">
    <wsdl:input message="tns:ReserveDomainSoapIn" />
    <wsdl:output message="tns:ReserveDomainSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="ReleaseDomain">
    <wsdl:input message="tns:ReleaseDomainSoapIn" />
    <wsdl:output message="tns:ReleaseDomainSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="GetDomainInfo">
    <wsdl:input message="tns:GetDomainInfoSoapIn" />
    <wsdl:output message="tns:GetDomainInfoSoapOut" />
  </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="ManageDelegation2Soap" type="tns:ManageDelegation2Soap">
  <soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
  <wsdl:operation name="CreateAppId">
    <soap:operation
      soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
        CreateAppId" style="document" />
    <wsdl:input>
      <soap:body use="literal" />
      <soap:header message="tns:CreateAppIdSecurity" part="Security"
        use="literal" />
      <soap:header message="tns:CreateAppIdDomainOwnershipProofHeader"
        part="DomainOwnershipProofHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdCertificate">
    <soap:operation
      soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
        UpdateAppIdCertificate" style="document" />
    <wsdl:input>
      <soap:body use="literal" />
      <soap:header message="tns:UpdateAppIdCertificateSecurity"
        part="Security" use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdProperties">
    <soap:operation
      soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
        UpdateAppIdProperties" style="document" />
    <wsdl:input>
      <soap:body use="literal" />
      <soap:header message="tns:UpdateAppIdPropertiesSecurity" part="Security"
        use="literal" />
    </wsdl:input>
  </wsdl:operation>

```

```

<wsdl:output>
  <soap:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="AddUri">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
    AddUri" style="document" />
  <wsdl:input>
    <soap:body use="literal" />
    <soap:header message="tns:AddUriSecurity" part="Security" use="literal" />
    <soap:header message="tns:AddUriDomainOwnershipProofHeader"
      part="DomainOwnershipProofHeader" use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RemoveUri">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
    RemoveUri" style="document" />
  <wsdl:input>
    <soap:body use="literal" />
    <soap:header message="tns:RemoveUriSecurity" part="Security"
      use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReserveDomain">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
    ReserveDomain" style="document" />
  <wsdl:input>
    <soap:body use="literal" />
    <soap:header message="tns:ReserveDomainSecurity" part="Security"
      use="literal" />
    <soap:header message="tns:ReserveDomainDomainOwnershipProofHeader"
      part="DomainOwnershipProofHeader" use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReleaseDomain">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
    ReleaseDomain" style="document" />
  <wsdl:input>
    <soap:body use="literal" />
    <soap:header message="tns:ReleaseDomainSecurity" part="Security"
      use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>

```

```

<wsdl:operation name="GetDomainInfo">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
    GetDomainInfo" style="document" />
  <wsdl:input>
    <soap:body use="literal" />
    <soap:header message="tns:GetDomainInfoSecurity" part="Security"
      use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:binding name="ManageDelegation2Soap12" type="tns:ManageDelegation2Soap">
  <soap12:binding transport="http://schemas.xmlsoap.org/soap/http" />
  <wsdl:operation name="CreateAppId">
    <soap12:operation
      soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
      CreateAppId" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
      <soap12:header message="tns:CreateAppIdSecurity" part="Security"
        use="literal" />
      <soap12:header message="tns:CreateAppIdDomainOwnershipProofHeader"
        part="DomainOwnershipProofHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdCertificate">
    <soap12:operation
      soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
      UpdateAppIdCertificate" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
      <soap12:header message="tns:UpdateAppIdCertificateSecurity" part="Security"
        use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdProperties">
    <soap12:operation
      soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
      UpdateAppIdProperties" style="document" />
    <wsdl:input>
      <soap12:body use="literal" />
      <soap12:header message="tns:UpdateAppIdPropertiesSecurity" part="Security"
        use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="AddUri">
    <soap12:operation

```



```

        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
        AddUri" style="document" />
<wsdl:input>
  <soap12:body use="literal" />
  <soap12:header message="tns:AddUriSecurity" part="Security" use="literal" />
  <soap12:header message="tns:AddUriDomainOwnershipProofHeader"
    part="DomainOwnershipProofHeader" use="literal" />
</wsdl:input>
<wsdl:output>
  <soap12:body use="literal" />
</wsdl:output>
</wsdl:operation>
<wsdl:operation name="RemoveUri">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
    RemoveUri" style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:RemoveUriSecurity" part="Security"
      use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReserveDomain">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
    ReserveDomain" style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:ReserveDomainSecurity" part="Security"
      use="literal" />
    <soap12:header message="tns:ReserveDomainDomainOwnershipProofHeader"
      part="DomainOwnershipProofHeader" use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReleaseDomain">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
    ReleaseDomain" style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
    <soap12:header message="tns:ReleaseDomainSecurity" part="Security"
      use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDomainInfo">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/
    GetDomainInfo" style="document" />
  <wsdl:input>
    <soap12:body use="literal" />

```

```
        <soap12:header message="tns:GetDomainInfoSecurity" part="Security"
            use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="ManageDelegation2">
    <wsdl:port name="ManageDelegation2Soap" binding="tns:ManageDelegation2Soap">
        <soap:address
            location="https://domains-dev.live-int.com/
            service/ManageDelegation2.asmx" />
    </wsdl:port>
    <wsdl:port name="ManageDelegation2Soap12"
        binding="tns:ManageDelegation2Soap12">
        <soap12:address
            location="https://domains-dev.live-int.com/
            service/ManageDelegation2.asmx" />
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>
```

7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 3.1.3:](#) By default, Exchange 2010 and Exchange 2013 get the Federation Metadata Document from the URL <http://nexus.passport.com/FederationMetadata/2006-12/FederationMetadata.xml>. This URL can be modified when establishing the federated domain.

[<2> Section 3.1.3:](#) Exchange 2010 and Exchange 2013 store the URL of the delegation management service in Active Directory when the server is loaded. The URL is stored in the **serviceBindingInformation** property of the Active Directory object `CN=DomainPartnerManageDelegation,CN=ServiceEndpoints,CN=FirstOrganization,CN=MicrosoftExchange,CN=Services,CN=Configuration,DC=`

When the server calls the delegation management service, this object is read to obtain the URL of the service.

[<3> Section 3.1.4.6.2.1:](#) Exchange 2010 and Exchange 2013 set this element to the string "ExchangeConnector".

[<4> Section 3.2.3:](#) By default, Exchange 2010 and Exchange 2013 get the Federation Metadata Document from the URL <http://nexus.passport.com/FederationMetadata/2006-12/FederationMetadata.xml>. This URL can be modified when establishing the federated domain.

[<5> Section 3.2.3:](#) Exchange 2010 and Exchange 2013 store the URL of the delegation management service in Active Directory when the server is loaded. The URL is stored in the **serviceBindingInformation** property of the Active Directory object `CN=DomainPartnerManageDelegation,CN=ServiceEndpoints,CN=FirstOrganization,CN=MicrosoftExchange,CN=Services,CN=Configuration,DC=`

When the server calls the delegation management service, this object is read to obtain the URL of the service.

[<6> Section 3.2.4.6.2.1:](#) Exchange 2010 and Exchange 2013 set this element to the string "ExchangeConnector".

[<7> Section 3.3.4.1.1:](#) The duration of the offer depends on the type of offer made. Exchange 2010 and Exchange 2013 create an offer with the duration set to the following values.

Offer type	Default duration
MSExchange.SharingInviteMessage	15 days
MSExchange.SharingCalendarFreeBusy	5 minutes
MSExchange.SharingRead	60 minutes
MSExchange.DeliveryExternalSubmit	48 hours
MSExchange.DeliveryInternalSubmit	48 hours
MSExchange.MailboxMove	60 minutes
MSExchange.Autodiscover	5 minutes

<8> [Section 3.3.4.1.1:](#) Exchange 2010 stores this value in the directory service property **msExchFedApplicationURI** of the **msExchFedTrust** object.

<9> [Section 3.3.4.1.1:](#) Exchange 2010 stores this value in the directory service property **msExchFedTokenIssuerURI** of the **msExchFedTrust** object. Exchange 2010 always uses the value "uri:WindowsLiveID".

<10> [Section 3.3.4.1.1:](#) Exchange 2010 obtains the value of the **saml:NameIdentifier** element from the **user** object in the directory service of the user for whom the token is requested. If the directory service **user** object has the **msExchImmutable** property set, that value is used; otherwise, Exchange 2010 uses the **objectGuid** property of the **user** object, which is encoded using base64 encoding, concatenated with the **msExchFedAccountNamespace** property of the **msExchFedOrgId** object.

<11> [Section 3.3.4.1.1:](#) Exchange 2010 obtains the value of the **saml:NameIdentifier** element from the **user** object in the directory service of the user for whom the token is requested. If the directory service **user** object has the **msExchImmutable** property set, that value is used; otherwise, Exchange 2010 uses the **objectGuid** property of the **user** object, which is encoded using base64 encoding, concatenated with the **msExchFedAccountNamespace** property of the **msExchFedOrgId** object.

<12> [Section 3.3.4.1.1:](#) Exchange 2010 sets the URI to the attribute value found in the directory service property **msExchFedPolicyReferenceURI** of the **msExchFedTrust** object. The default value is "EX_MBI_FED_SSL".

8 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

9 Index

A

Abstract data model
client ([section 3.1.1](#) 18, [section 3.2.1](#) 41, [section 3.3.1](#) 69)
[Applicability](#) 9
[Attribute groups](#) 17
[Attributes](#) 17

C

[Capability negotiation](#) 10
[Change tracking](#) 109
Client
abstract data model ([section 3.1.1](#) 18, [section 3.2.1](#) 41, [section 3.3.1](#) 69)
initialization ([section 3.1.3](#) 19, [section 3.2.3](#) 42, [section 3.3.3](#) 70)
local events ([section 3.1.6](#) 41, [section 3.2.6](#) 69, [section 3.3.6](#) 81)
message processing ([section 3.1.4](#) 19, [section 3.2.4](#) 42)
sequencing rules ([section 3.1.4](#) 19, [section 3.2.4](#) 42)
timer events ([section 3.1.5](#) 41, [section 3.2.5](#) 69, [section 3.3.5](#) 81)
timers ([section 3.1.2](#) 19, [section 3.2.2](#) 42, [section 3.3.2](#) 70)
[Complex types](#) 12
[s1:WSSecurityHeader Complex Type](#) 15
[tns:ArrayOfProperty Complex Type](#) 13
[tns:DomainInfo Complex Type](#) 13
[tns:DomainOwnershipProofHeader Complex Type](#) 14
[tns:Property Complex Type](#) 15

D

Data model - abstract
client ([section 3.1.1](#) 18, [section 3.2.1](#) 41, [section 3.3.1](#) 69)

E

Elements
[s:Security Element](#) 12
[tns:DomainOwnershipProofHeader Element](#) 12
Events
local - client ([section 3.1.6](#) 41, [section 3.2.6](#) 69, [section 3.3.6](#) 81)
timer - client ([section 3.1.5](#) 41, [section 3.2.5](#) 69, [section 3.3.5](#) 81)

F

[Fields - vendor-extensible](#) 10
[Full WSDL](#) 89
[ManageDelegation2Soap WSDL](#) 96
[ManageDelegationSoap WSDL](#) 89

G

[Glossary](#) 7
[Groups](#) 17

I

[Implementer - security considerations](#) 88
[Index of security parameters](#) 88
[Informative references](#) 9
Initialization
client ([section 3.1.3](#) 19, [section 3.2.3](#) 42, [section 3.3.3](#) 70)
[Introduction](#) 7

L

Local events
client ([section 3.1.6](#) 41, [section 3.2.6](#) 69, [section 3.3.6](#) 81)

M

Message processing
client ([section 3.1.4](#) 19, [section 3.2.4](#) 42)
Messages
[attribute groups](#) 17
[attributes](#) 17
[complex types](#) 12
[elements](#) 12
[enumerated](#) 11
[groups](#) 17
[namespaces](#) 11
[s:Security Elementelement](#) 12
[s1:WSSecurityHeader Complex Typecomplex type](#) 15
[simple types](#) 16
[syntax](#) 11
[tns:ArrayOfProperty Complex Typecomplex type](#) 13
[tns:DomainInfo Complex Typecomplex type](#) 13
[tns:DomainOwnershipProofHeader Complex Typecomplex type](#) 14
[tns:DomainOwnershipProofHeader Elementelement](#) 12
[tns:DomainState Simple Typesimple type](#) 16
[tns:Property Complex Typecomplex type](#) 15
[transport](#) 11

N

[Namespaces](#) 11
[Normative references](#) 8

O

[Overview \(synopsis\)](#) 9

P

[Parameters - security index](#) 88
[Preconditions](#) 9
[Prerequisites](#) 9
[Product behavior](#) 107
Protocol Details
 [overview](#) 18

[ManageDelegation2Soap WSDL](#) 96
[ManageDelegationSoap WSDL](#) 89

R

[References](#) 7
 [informative](#) 9
 [normative](#) 8
[Relationship to other protocols](#) 9

S

[s:Security Elementelement](#) 12
[s1:WSSecurityHeader Complex Typecomplex type](#)
 15
Security
 [implementer considerations](#) 88
 [parameter index](#) 88
Sequencing rules
 client ([section 3.1.4](#) 19, [section 3.2.4](#) 42)
[Simple types](#) 16
 [tns:DomainState Simple Type](#) 16
[Standards assignments](#) 10
Syntax
 [messages - overview](#) 11

T

Timer events
 client ([section 3.1.5](#) 41, [section 3.2.5](#) 69, [section 3.3.5](#) 81)
Timers
 client ([section 3.1.2](#) 19, [section 3.2.2](#) 42, [section 3.3.2](#) 70)
[tns:ArrayOfProperty Complex Typecomplex type](#) 13
[tns:DomainInfo Complex Typecomplex type](#) 13
[tns:DomainOwnershipProofHeader Complex Typecomplex type](#) 14
[tns:DomainOwnershipProofHeader Elementelement](#)
 12
[tns:DomainState Simple Typesimple type](#) 16
[tns:Property Complex Typecomplex type](#) 15
[Tracking changes](#) 109
[Transport](#) 11
Types
 [complex](#) 12
 [simple](#) 16

V

[Vendor-extensible fields](#) 10
[Versioning](#) 10

W

[WSDL](#) 89