

[MS-OXWSXPROP]: Extended Properties Structure

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

| Date | Revision History | Revision Class | Comments |
|------------|------------------|----------------|--|
| 07/15/2009 | 1.0 | Major | Initial Availability. |
| 11/04/2009 | 1.1.0 | Minor | Updated the technical content. |
| 02/10/2010 | 2.0.0 | Major | Updated and revised the technical content. |
| 05/05/2010 | 2.0.1 | Editorial | Revised and edited the technical content. |
| 08/04/2010 | 3.0 | Major | Significantly changed the technical content. |
| 11/03/2010 | 4.0 | Major | Significantly changed the technical content. |
| 03/18/2011 | 5.0 | Major | Significantly changed the technical content. |
| 08/05/2011 | 6.0 | Major | Significantly changed the technical content. |
| 10/07/2011 | 6.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 01/20/2012 | 7.0 | Major | Significantly changed the technical content. |
| 04/27/2012 | 7.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 07/16/2012 | 7.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 10/08/2012 | 8.0 | Major | Significantly changed the technical content. |
| 02/11/2013 | 8.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 07/26/2013 | 8.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 11/18/2013 | 8.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 02/10/2014 | 8.0 | No change | No changes to the meaning, language, or formatting of the technical content. |

Table of Contents

| | |
|--|-----------|
| 1 Introduction | 4 |
| 1.1 Glossary | 4 |
| 1.2 References | 4 |
| 1.2.1 Normative References | 4 |
| 1.2.2 Informative References | 5 |
| 1.3 Overview | 5 |
| 1.4 Relationship to Protocols and Other Structures | 5 |
| 1.5 Applicability Statement | 5 |
| 1.6 Versioning and Localization | 5 |
| 1.7 Vendor-Extensible Fields | 6 |
| 2 Structures | 7 |
| 2.1 Extended Properties Schema | 7 |
| 2.1.1 Extended Properties Namespaces | 8 |
| 2.1.2 ExtendedFieldURI Element | 9 |
| 2.1.3 NonEmptyArrayOfExtendedPropertyType Complex Type | 9 |
| 2.1.4 t:NonEmptyArrayOfPropertyValuesType Complex Type | 9 |
| 2.1.5 t:ExtendedPropertyType Complex Type | 10 |
| 2.1.6 t:PathToExtendedFieldType Complex Type | 10 |
| 2.1.7 t:GuidType Simple Type | 12 |
| 2.1.8 t:MapiPropertyTypeType Simple Type | 12 |
| 2.1.9 t:PropertyTagType Simple Type | 15 |
| 3 Structure Examples | 17 |
| 3.1 Creating Extended Properties | 17 |
| 3.2 Retrieving Extended Properties | 18 |
| 4 Security | 21 |
| 4.1 Security Considerations for Implementers | 21 |
| 4.2 Index of Security Parameters | 21 |
| 5 Appendix A: Product Behavior | 22 |
| 6 Change Tracking | 23 |
| 7 Index | 24 |

1 Introduction

The Extended Properties Structure is used by clients to manipulate extended properties on various types of objects. Extended properties are custom properties that users set on items and folders in a server's mailbox.

Sections 1.7 and 2 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

GUID
XML
XML namespace

The following terms are defined in [\[MS-OXGLOS\]](#):

XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[MS-OXWSCDATA] Microsoft Corporation, "[Common Web Service Data Types](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[MS-OXWSCORE] Microsoft Corporation, "[Core Items Web Service Protocol](#)".

[MS-OXWSFOLD] Microsoft Corporation, "[Folders and Folder Permissions Web Service Protocol](#)".

1.3 Overview

The Extended Properties Structure is used by protocols that handle items and folders.

1.4 Relationship to Protocols and Other Structures

This structure is used by operations that are part of the Core Items Web Service Protocol, as described in [\[MS-OXWSCORE\]](#), and the Folder and Folder Permissions Web Service Protocol, as described in [\[MS-OXWSFOLD\]](#).

Extended properties can be added or updated by using the following operations:

- The **CreateItem** operation, as described in [\[MS-OXWSCORE\]](#) section 3.1.4.2. The **CreateItem** operation creates items on the server.
- The **UpdateItem** operation, as described in [\[MS-OXWSCORE\]](#) section 3.1.4.9. The **UpdateItem** operation updates items on the server.
- The **CreateFolder** operation, as described in [\[MS-OXWSFOLD\]](#) section 3.1.4.2. The **CreateFolder** operation creates folders on the server.
- The **UpdateFolder** operation, as described in [\[MS-OXWSFOLD\]](#) section 3.1.4.8. The **UpdateFolder** operation modifies properties of a folder on the server.

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

1.5 Applicability Statement

The information provided in this document applies to protocols that use extended properties.

1.6 Versioning and Localization

This document covers versioning issues in the following areas:

- **Structure Versions:** This document specifies the only version of the Extended Properties Structure.

- **Localization:** This structure does not include any locale-specific processes or data.

1.7 Vendor-Extensible Fields

None.

2 Structures

2.1 Extended Properties Schema

The following sections specify the namespaces, elements, complex types, and simple types of the Extended Properties Structure. The elements and types use type definitions that are specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

MS-OXWSXPROP-types.xsd includes the file listed in the following table. To operate correctly, this file has to be present in the folder that contains the types schema for this structure.

| File name | Defining specification |
|------------------------|--|
| MS-OXWSCDATA-types.xsd | [MS-OXWSCDATA] section 7.2 |

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
elementFormDefault="qualified" version="Exchange2013" id="types">
  <xs:include schemaLocation="MS-OXWSCDATA-types.xsd"/>
  <xs:element name="ExtendedFieldURI" type="t:PathToExtendedFieldType"
substitutionGroup="t:Path"/>
  <xs:complexType name="ExtendedPropertyType">
    <xs:sequence>
      <xs:element name="ExtendedFieldURI" type="t:PathToExtendedFieldType"/>
      <xs:choice>
        <xs:element name="Value" type="xs:string"/>
        <xs:element name="Values" type="t:NonEmptyArrayOfPropertyValuesType"/>
      </xs:choice>
    </xs:sequence>
  </xs:complexType>
  <xs:simpleType name="GuidType">
    <xs:restriction base="xs:string">
      <xs:pattern value="[0-9A-Fa-f]{8}-[0-9A-Fa-f]{4}-[0-9A-Fa-f]{4}-[0-9A-Fa-f]{4}-[0-9A-
Fa-f]{12}"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="MapiPropertyTypeType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="ApplicationTime"/>
      <xs:enumeration value="ApplicationTimeArray"/>
      <xs:enumeration value="Binary"/>
      <xs:enumeration value="BinaryArray"/>
      <xs:enumeration value="Boolean"/>
      <xs:enumeration value="CLSID"/>
      <xs:enumeration value="CLSIDArray"/>
      <xs:enumeration value="Currency"/>
      <xs:enumeration value="CurrencyArray"/>
      <xs:enumeration value="Double"/>
      <xs:enumeration value="DoubleArray"/>
      <xs:enumeration value="Error"/>
      <xs:enumeration value="Float"/>
      <xs:enumeration value="FloatArray"/>
      <xs:enumeration value="Integer"/>
      <xs:enumeration value="IntegerArray"/>
      <xs:enumeration value="Long"/>
      <xs:enumeration value="LongArray"/>
    </xs:restriction>
  </xs:simpleType>

```

```

    <xs:enumeration value="Null"/>
    <xs:enumeration value="Object"/>
    <xs:enumeration value="ObjectArray"/>
    <xs:enumeration value="Short"/>
    <xs:enumeration value="ShortArray"/>
    <xs:enumeration value="SystemTime"/>
    <xs:enumeration value="SystemTimeArray"/>
    <xs:enumeration value="String"/>
    <xs:enumeration value="StringArray"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="NonEmptyArrayOfPropertyValuesType">
  <xs:choice>
    <xs:element name="Value" type="xs:string" maxOccurs="unbounded"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="PathToExtendedFieldType">
  <xs:complexContent>
    <xs:extension base="t:BasePathToElementType">
      <xs:attribute name="DistinguishedPropertySetId" type="t:DistinguishedPropertySetType"
use="optional"/>
      <xs:attribute name="PropertySetId" type="t:GuidType" use="optional"/>
      <xs:attribute name="PropertyTag" type="t:PropertyTagType" use="optional"/>
      <xs:attribute name="PropertyName" type="xs:string" use="optional"/>
      <xs:attribute name="PropertyId" type="xs:int" use="optional"/>
      <xs:attribute name="PropertyType" type="t:MapiPropertyTypeType" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="PropertyTagType">
  <xs:union memberTypes="xs:unsignedShort">
    <xs:simpleType id="HexPropertyTagType">
      <xs:restriction base="xs:string">
        <xs:pattern value="(0x|0X) [0-9A-Fa-f]{1,4}"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:union>
</xs:simpleType>
</xs:schema>

```

2.1.1 Extended Properties Namespaces

This specification defines and references various **XML namespaces** by using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

| Prefix | Namespace URI | Reference |
|-----------------|--|------------------------------|
| soap | http://schemas.xmlsoap.org/wsdl/soap/ | [SOAP1.1] |
| tns | http://schemas.microsoft.com/exchange/services/2006/messages | |
| s | http://www.w3.org/2001/XMLSchema | [XMLSCHEMA1] |
| targetNamespace | http://schemas.microsoft.com/exchange/services/2006/messages | |

| Prefix | Namespace URI | Reference |
|--------|---|------------------------|
| wSDL | http://schemas.xmlsoap.org/wSDL/ | [WSDL] |
| t | http://schemas.microsoft.com/exchange/services/2006/types | |

2.1.2 ExtendedFieldURI Element

The **ExtendedFieldURI** element specifies an extended MAPI property.

```
<xs:element name="ExtendedFieldURI"
  type="t:PathToExtendedFieldType"
  substitutionGroup="t:Path"
/>
```

This element allows substitution of the **Path** element, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.3.8, for the **PathToExtendedFieldType** element, as specified in section [2.1.6](#).

2.1.3 NonEmptyArrayOfExtendedPropertyType Complex Type

The **NonEmptyArrayOfExtendedPropertyType** complex type represents an extended property. This array has at least one member. [<1>](#)

```
<xs:complexType name="NonEmptyArrayOfExtendedPropertyType">
  <xs:choice>
    <xs:element name="ExtendedProperty" type="t:ExtendedPropertyType" maxOccurs="unbounded"/>
  </xs:choice>
</xs:complexType>
```

The following table lists the child element of the **NonEmptyArrayOfExtendedPropertyType** complex type.

| Element name | Type | Description |
|-------------------------|---|---|
| ExtendedProperty | ExtendedPropertyType (section 2.1.5) | Specifies an extended property instance, including both its path identifier and its associated value. |

2.1.4 t:NonEmptyArrayOfPropertyValuesType Complex Type

The **NonEmptyArrayOfPropertyValuesType** complex type represents a collection of values for an extended property. This array has at least one member.

```
<xs:complexType name="NonEmptyArrayOfPropertyValuesType">
  <xs:choice>
    <xs:element name="Value"
      type="xs:string"
      maxOccurs="unbounded"
    />
  </xs:choice>
</xs:complexType>
```

The following table lists the child element of the **NonEmptyArrayOfPropertyValuesType** complex type.

| Element name | Type | Description |
|--------------|---|---|
| Value | xs:string ([XMLSCHEMA2]) | Specifies a value for an extended property. |

2.1.5 t:ExtendedPropertyType Complex Type

The **ExtendedPropertyType** complex type specifies extended properties on folders and items. This complex type represents an extended property instance, including both its path identifier and its associated value.

```
<xs:complexType name="ExtendedPropertyType">
  <xs:sequence>
    <xs:element name="ExtendedFieldURI"
      type="t:PathToExtendedFieldType"
    />
    <xs:choice>
      <xs:element name="Value"
        type="xs:string"
      />
      <xs:element name="Values"
        type="t:NonEmptyArrayOfPropertyValuesType"
      />
    </xs:choice>
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **ExtendedPropertyType** complex type.

| Element name | Type | Description |
|-------------------------|---|--|
| ExtendedFieldURI | t:PathToExtendedFieldType (section 2.1.6) | Specifies the path to the extended property. |
| Value | xs:string ([XMLSCHEMA2]) | Specifies a single value for the property specified by the ExtendedFieldURI element (section 2.1.2). |
| Values | t:NonEmptyArrayOfPropertyValuesType (section 2.1.4) | Specifies two or more values for the property specified by the ExtendedFieldURI element (section 2.1.2). |

2.1.6 t:PathToExtendedFieldType Complex Type

The **PathToExtendedFieldType** complex type specifies an extended property. The **PathToExtendedFieldType** complex type extends the **BasePathToElementType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.14.

```
<xs:complexType name="PathToExtendedFieldType">
  <xs:complexContent>
```

```

<xs:extension
  base="t:BasePathToElementType"
  >
  <xs:attribute name="DistinguishedPropertySetId"
    type="t:DistinguishedPropertySetType"
    use="optional"
  />
  <xs:attribute name="PropertySetId"
    type="t:GuidType"
    use="optional"
  />
  <xs:attribute name="PropertyTag"
    type="t:PropertyTagType"
    use="optional"
  />
  <xs:attribute name="PropertyName"
    type="xs:string"
    use="optional"
  />
  <xs:attribute name="PropertyId"
    type="xs:int"
    use="optional"
  />
  <xs:attribute name="PropertyType"
    type="t:MapiPropertyTypeType"
    use="required"
  />
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

The following table summarizes the set of common **XML schema** attribute definitions defined by this specification.

| Attribute name | Type | Description |
|-----------------------------------|--|---|
| DistinguishedPropertySetId | t:DistinguishedPropertySetType ([MS-OXWSCDATA] section 2.2.5.11) | Specifies well-known property set IDs for extended properties. If this attribute is used, the PropertySetId and PropertyTag attributes cannot be used. This attribute MUST be used with the PropertyType attribute and either the PropertyId or PropertyName attribute. |
| PropertySetId | t:GuidType (section 2.1.7) | Specifies an extended property set or namespace by its identifying GUID . If this attribute is used, the DistinguishedPropertySetId and PropertyTag attributes cannot be used. This attribute MUST be used with the PropertyType attribute and either the PropertyId or |

| Attribute name | Type | Description |
|---------------------|--|--|
| | | PropertyName attribute. |
| PropertyTag | t:PropertyTagType (section 2.1.9) | Specifies the property tag. The PropertyTag attribute can be represented as either a hexadecimal value or a short integer. If the PropertyTag attribute is used, the DistinguishedPropertySetId , PropertySetId , PropertyName , and PropertyId attributes MUST NOT be used. |
| PropertyName | xs:string ([XMLSCHEMA2]) | Specifies an extended property by its name. This property MUST be coupled with either the DistinguishedPropertySetId or PropertySetId attribute. |
| PropertyId | xs:int ([XMLSCHEMA2]) | Specifies an extended property by its dispatch ID. This property MUST be coupled with either the DistinguishedPropertySetId or PropertySetId attribute. |
| PropertyType | t:MapiPropertyTypeType (section 2.1.8) | Specifies the property type of an extended property. |

2.1.7 t:GuidType Simple Type

The **GuidType** simple type specifies an extended property set or namespace by its identifying GUID.

```
<xs:simpleType name="GuidType">
  <xs:restriction
    base="xs:string"
  >
    <xs:pattern
      value="[0-9A-Fa-f]{8}-[0-9A-Fa-f]{4}-[0-9A-Fa-f]{4}-[0-9A-Fa-f]{4}-[0-9A-Fa-f]{12}"
    />
  </xs:restriction>
</xs:simpleType>
```

The following pattern is defined by the **GuidType** simple type.

```
[0-9A-Fa-f]{8}-[0-9A-Fa-f]{4}-[0-9A-Fa-f]{4}-[0-9A-Fa-f]{4}-[0-9A-Fa-f]{12}
```

2.1.8 t:MapiPropertyTypeType Simple Type

The **MapiPropertyTypeType** simple type specifies the property type.

```
<xs:simpleType name="MapiPropertyTypeType">
  <xs:restriction
```

```
base="xs:string"
>
<xs:enumeration
  value="ApplicationTime"
/>
<xs:enumeration
  value="ApplicationTimeArray"
/>
<xs:enumeration
  value="Binary"
/>
<xs:enumeration
  value="BinaryArray"
/>
<xs:enumeration
  value="Boolean"
/>
<xs:enumeration
  value="CLSID"
/>
<xs:enumeration
  value="CLSIDArray"
/>
<xs:enumeration
  value="Currency"
/>
<xs:enumeration
  value="CurrencyArray"
/>
<xs:enumeration
  value="Double"
/>
<xs:enumeration
  value="DoubleArray"
/>
<xs:enumeration
  value="Error"
/>
<xs:enumeration
  value="Float"
/>
<xs:enumeration
  value="FloatArray"
/>
<xs:enumeration
  value="Integer"
/>
<xs:enumeration
  value="IntegerArray"
/>
<xs:enumeration
  value="Long"
/>
<xs:enumeration
  value="LongArray"
/>
<xs:enumeration
  value="Null"
/>
```

```

<xs:enumeration
  value="Object"
/>
<xs:enumeration
  value="ObjectArray"
/>
<xs:enumeration
  value="Short"
/>
<xs:enumeration
  value="ShortArray"
/>
<xs:enumeration
  value="SystemTime"
/>
<xs:enumeration
  value="SystemTimeArray"
/>
<xs:enumeration
  value="String"
/>
<xs:enumeration
  value="StringArray"
/>
</xs:restriction>
</xs:simpleType>

```

The following table lists the values that are defined by the **MapiPropertyTypeType** simple type.

| Value | Description |
|----------------------|--|
| ApplicationTime | Specifies a double value that is interpreted as a date and time. The integer part is the date, and the fraction part is the time. |
| ApplicationTimeArray | Specifies an array of double values that are interpreted as a date and time. |
| Binary | Specifies a base64-encoded binary value. |
| BinaryArray | Specifies an array of base64-encoded binary values. |
| Boolean | Specifies a Boolean "true" or "false" value. |
| CLSID | Specifies a GUID string. |
| CLSIDArray | Specifies an array of GUID strings. |
| Currency | Specifies a 64-bit integer that is interpreted as the number of cents. |
| CurrencyArray | Specifies an array of 64-bit integers that are interpreted as the number of cents. |
| Double | Specifies a 64-bit floating-point value. |
| DoubleArray | Specifies an array of 64-bit floating-point values. |
| Error | Specifies an SCODE value; this is a 32-bit unsigned integer. This value is not used for restrictions or for getting or setting values. This value exists only for reporting. |
| Float | Specifies a 32-bit floating-point value. |

| Value | Description |
|-----------------|---|
| FloatArray | Specifies an array of 32-bit floating-point values. |
| Integer | Specifies a signed 32-bit (Int32) integer. |
| IntegerArray | Specifies an array of signed 32-bit (Int32) integers. |
| Long | Specifies a signed or unsigned 64-bit (Int64) integer. |
| LongArray | Specifies an array of signed or unsigned 64-bit (Int64) integers. |
| Null | Indicates no property value. This value is not used for restrictions or for getting or setting values. This value exists only for reporting. |
| Object | Specifies a pointer to an object that implements the IUnknown interface. This value is not used for restrictions or for getting or setting values. This value exists only for reporting. |
| ObjectArray | Specifies an array of pointers to objects that implement the IUnknown interface. This value is not used for restrictions or for getting or setting values. This value exists only for reporting. |
| Short | Specifies a signed 16-bit integer. |
| ShortArray | Specifies an array of signed 16-bit integers. |
| SystemTime | Specifies a 64-bit integer date and time value in the form of a FILETIME structure. |
| SystemTimeArray | Specifies an array of 64-bit integer date and time values in the form of a FILETIME structure. |
| String | Specifies a Unicode string. |
| StringArray | Specifies an array of Unicode strings. |

2.1.9 t:PropertyTagType Simple Type

The **PropertyTagType** simple type specifies the property tag.

```
<xs:simpleType name="PropertyTagType">
  <xs:union
    memberTypes="xs:unsignedShort"
  >
    <xs:simpleType
      id="HexPropertyTagType"
    >
      <xs:restriction
        base="xs:string"
      >
        <xs:pattern
          value="(0x|0X)[0-9A-Fa-f]{1,4}"
        />
      </xs:restriction>
    </xs:simpleType>
  </xs:union>
</xs:simpleType>
```

The following pattern is defined by the **PropertyTagType** simple type.

```
(0x|0X) [0-9A-Fa-f] {1,4}
```

Note that the property tag can be represented in either hexadecimal or decimal form.

3 Structure Examples

The following examples show how extended properties are created and retrieved.

3.1 Creating Extended Properties

The following example creates and sends mail with three extended properties.

The client constructs the request **XML** and sends the newly created message to the server. The message has three custom properties. The first custom property is named **Expiration Date** and has a string value set to a time of "12/25/2009 3:25:15 PM". The second custom property is named **Employee Type** and has a string value set to "Part Time". The third custom property is named **MyFlag** and has an integer value set to "4". Each of these extended properties becomes part of the message. The **PropertySetId** attribute values are GUIDs, and are shown in the following examples.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2013" />
  </soap:Header>
  <soap:Body>
    <m:CreateItem MessageDisposition="SendAndSaveCopy">
      <m:SavedItemFolderId>
        <t:DistinguishedFolderId Id="sentitems" />
      </m:SavedItemFolderId>
      <m:Items>
        <t:Message>
          <t:Subject>Interesting</t:Subject>
          <t:Body BodyType="HTML">The merger is finalized.</t:Body>
          <t:ExtendedProperty>
            <t:ExtendedFieldURI PropertySetId="c11ff724-aa03-4555-9952-8fa248a11c3e"
              PropertyName="Expiration Date" PropertyType="String" />
            <t:Value>12/25/2009 3:25:15 PM</t:Value>
          </t:ExtendedProperty>
          <t:ExtendedProperty>
            <t:ExtendedFieldURI PropertySetId="24a3075f-a8b7-4181-a9ed-708a947b8765"
              PropertyName="Employee Type" PropertyType="String" />
            <t:Value>Part Time</t:Value>
          </t:ExtendedProperty>
          <t:ExtendedProperty>
            <t:ExtendedFieldURI PropertySetId="75a5486f-9267-49ca-9b4e-3d04ca9ec179"
              PropertyName="MyFlag" PropertyType="Integer" />
            <t:Value>4</t:Value>
          </t:ExtendedProperty>
          <t:ToRecipients>
            <t:Mailbox>
              <t:EmailAddress>User1@Contoso.com</t:EmailAddress>
            </t:Mailbox>
            <t:Mailbox>
              <t:EmailAddress>User2@Contoso.com</t:EmailAddress>
            </t:Mailbox>
          </t:ToRecipients>
        </t:Message>
      </m:Items>
    </m:CreateItem>
  </soap:Body>
</soap:Envelope>
```

```

    </m:CreateItem>
  </soap:Body>
</soap:Envelope>

```

The server constructs the response XML and sends it to the client, as shown in the following example.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="14"
      MinorVersion="1"
      MajorBuildNumber="63"
      MinorBuildNumber="0"
      Version="Exchange2013"
      xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xmlns:xsd="http://www.w3.org/2001/XMLSchema" />
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <m:CreateItemResponse
      xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
      xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types">
      <m:ResponseMessages>
        <m:CreateItemResponseMessage ResponseClass="Success">
          <m:ResponseCode>NoError</m:ResponseCode>
          <m:Items />
        </m:CreateItemResponseMessage>
      </m:ResponseMessages>
    </m:CreateItemResponse>
  </s:Body>
</s:Envelope>

```

3.2 Retrieving Extended Properties

The following example gets a message and retrieves the three specified extended properties.

The client constructs the request XML and sends it to the server. The client is requesting the specified message with the three named extended properties — **Expiration Date**, **Employee Type**, and **MyFlag**. The **PropertySetId** attribute values are GUIDs, and are shown in the following examples. Note that the **ItemId** and **ChangeKey** attributes have been shortened to preserve readability.

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2013" />
  </soap:Header>
  <soap:Body>
    <m:GetItem>
      <m:ItemShape>

```

```

    <t:BaseShape>IdOnly</t:BaseShape>
    <t:AdditionalProperties>
      <t:ExtendedFieldURI PropertySetId="c11ff724-aa03-4555-9952-8fa248a11c3e"
PropertyName="Expiration Date" PropertyType="String" />
      <t:ExtendedFieldURI PropertySetId="24a3075f-a8b7-4181-a9ed-708a947b8765"
PropertyName="Employee Type" PropertyType="String" />
      <t:ExtendedFieldURI PropertySetId="75a5486f-9267-49ca-9b4e-3d04ca9ec179"
PropertyName="MyFlag" PropertyType="Integer" />
    </t:AdditionalProperties>
  </m:ItemShape>
  <m:ItemIds>
    <t:ItemId Id="AAMkAGIwODEy" ChangeKey="CQAAABYAAA" />
  </m:ItemIds>
</m:GetItem>
</soap:Body>
</soap:Envelope>

```

The server constructs the response XML and sends it to the client. In this example, three extended properties are returned; these are the custom properties that were generated when the message was created. The **PropertySetId**, **PropertyName**, and **PropertyType** attributes are included in the response.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="14" MinorVersion="1" MajorBuildNumber="63"
MinorBuildNumber="0"
      Version="Exchange2013"
xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" />
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <m:GetItemResponse
xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types">
      <m:ResponseMessages>
        <m:GetItemResponseMessage ResponseClass="Success">
          <m:ResponseCode>NoError</m:ResponseCode>
          <m:Items>
            <t:Message>
              <t:ItemId Id="AAMkAGIwODEy" ChangeKey="CQAAABYAAA" />
              <t:ExtendedProperty>
                <t:ExtendedFieldURI PropertySetId="c11ff724-aa03-4555-9952-8fa248a11c3e"
PropertyName="Expiration Date" PropertyType="String" />
                <t:Value>12/25/2009 3:25:15 PM </t:Value>
              </t:ExtendedProperty>
              <t:ExtendedProperty>
                <t:ExtendedFieldURI PropertySetId="24a3075f-a8b7-4181-a9ed-708a947b8765"
PropertyName="Employee Type" PropertyType="String" />
                <t:Value>Part Time</t:Value>
              </t:ExtendedProperty>
              <t:ExtendedProperty>
                <t:ExtendedFieldURI PropertySetId="75a5486f-9267-49ca-9b4e-3d04ca9ec179"
PropertyName="MyFlag" PropertyType="Integer" />
                <t:Value>4</t:Value>
            </t:Message>
          </m:Items>
        </m:GetItemResponseMessage>
      </m:ResponseMessages>
    </m:GetItemResponse>
  </s:Body>
</Envelope>

```

```
        </t:ExtendedProperty>
      </t:Message>
    </m:Items>
  </m:GetItemResponseMessage>
</m:ResponseMessages>
</m:GetItemResponse>
</s:Body>
</s:Envelope>
```

4 Security

4.1 Security Considerations for Implementers

None.

4.2 Index of Security Parameters

None.

5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.3:](#) Exchange 2007 and Exchange 2010 do not use the **NonEmptyArrayOfExtendedPropertyType** complex type.

6 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

7 Index

A

[Applicability](#) 5

C

[Change tracking](#) 23

[Creating Extended Properties example](#) 17

E

[Examples](#) 17

[Creating Extended Properties](#) 17

[Retrieving Extended Properties](#) 18

F

[Fields - vendor-extensible](#) 6

G

[Glossary](#) 4

I

[Implementer - security considerations](#) 21

[Index of security parameters](#) 21

[Informative references](#) 5

[Introduction](#) 4

L

[Localization](#) 5

N

[Normative references](#) 4

O

[Overview \(synopsis\)](#) 5

P

[Parameters - security index](#) 21

[Product behavior](#) 22

R

[References](#) 4

[informative](#) 5

[normative](#) 4

[Relationship to protocols and other structures](#) 5

[Retrieving Extended Properties example](#) 18

S

Security

[implementer considerations](#) 21

[parameter index](#) 21

T

[Tracking changes](#) 23

V

[Vendor-extensible fields](#) 6

[Versioning](#) 5