

[MS-PERMS]:

Permissions Web Service Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
4/4/2008	0.1	New	Initial Availability
6/27/2008	1.0	Major	Revised and edited the technical content
12/12/2008	1.01	Editorial	Revised and edited the technical content
7/13/2009	1.02	Major	Revised and edited the technical content
8/28/2009	1.03	Editorial	Revised and edited the technical content
11/6/2009	1.04	Editorial	Revised and edited the technical content
2/19/2010	2.0	Minor	Updated the technical content
3/31/2010	2.01	Editorial	Revised and edited the technical content
4/30/2010	2.02	Editorial	Revised and edited the technical content
6/7/2010	2.03	Editorial	Revised and edited the technical content
6/29/2010	2.04	Editorial	Changed language and formatting in the technical content.
7/23/2010	2.04	None	No changes to the meaning, language, or formatting of the technical content.
9/27/2010	2.04	None	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	2.04	None	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	2.04	None	No changes to the meaning, language, or formatting of the technical content.
3/18/2011	2.04	None	No changes to the meaning, language, or formatting of the technical content.
6/10/2011	2.04	None	No changes to the meaning, language, or formatting of the technical content.
1/20/2012	3.0	Major	Significantly changed the technical content.
4/11/2012	3.0	None	No changes to the meaning, language, or formatting of the technical content.
7/16/2012	3.0	None	No changes to the meaning, language, or formatting of the technical content.
9/12/2012	3.0	None	No changes to the meaning, language, or formatting of the technical content.
10/8/2012	3.1	Minor	Clarified the meaning of the technical content.
2/11/2013	3.2	Minor	Clarified the meaning of the technical content.
7/30/2013	3.3	Minor	Clarified the meaning of the technical content.
11/18/2013	3.3	None	No changes to the meaning, language, or formatting of the technical content.

Date	Revision History	Revision Class	Comments
2/10/2014	3.3	None	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	3.4	Minor	Clarified the meaning of the technical content.
7/31/2014	3.5	Minor	Clarified the meaning of the technical content.
10/30/2014	3.5	None	No changes to the meaning, language, or formatting of the technical content.
3/16/2015	4.0	Major	Significantly changed the technical content.
2/26/2016	5.0	Major	Significantly changed the technical content.
7/15/2016	5.0	None	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1	Introduction	7
1.1	Glossary	7
1.2	References	8
1.2.1	Normative References	8
1.2.2	Informative References	9
1.3	Overview	9
1.4	Relationship to Other Protocols	9
1.5	Prerequisites/Preconditions	10
1.6	Applicability Statement	10
1.7	Versioning and Capability Negotiation	10
1.8	Vendor-Extensible Fields	10
1.9	Standards Assignments.....	10
2	Messages.....	11
2.1	Transport	11
2.2	Common Message Syntax	11
2.2.1	Namespaces	11
2.2.2	Messages.....	11
2.2.3	Elements	11
2.2.4	Complex Types.....	11
2.2.5	Simple Types	12
2.2.6	Attributes	12
2.2.7	Groups	12
2.2.8	Attribute Groups.....	12
3	Protocol Details	13
3.1	Permissions Soap Server Details	13
3.1.1	Abstract Data Model.....	13
3.1.2	Timers	13
3.1.3	Initialization.....	13
3.1.4	Message Processing Events and Sequencing Rules	13
3.1.4.1	AddPermission	14
3.1.4.1.1	Messages	14
3.1.4.1.1.1	AddPermissionSoapIn	14
3.1.4.1.1.2	AddPermissionSoapOut.....	14
3.1.4.1.2	Elements	14
3.1.4.1.2.1	AddPermission.....	15
3.1.4.1.2.2	AddPermissionResponse	15
3.1.4.1.3	Complex Types	16
3.1.4.1.4	Simple Types	16
3.1.4.1.5	Attributes	16
3.1.4.1.6	Groups.....	16
3.1.4.1.7	Attribute Groups.....	16
3.1.4.2	AddPermissionCollection	16
3.1.4.2.1	Messages	16
3.1.4.2.1.1	AddPermissionCollectionSoapIn	17
3.1.4.2.1.2	AddPermissionCollectionSoapOut	17
3.1.4.2.2	Elements.....	17
3.1.4.2.2.1	AddPermissionCollection	17
3.1.4.2.2.2	AddPermissionCollectionResponse	19
3.1.4.2.3	Complex Types	19
3.1.4.2.4	Simple Types	19
3.1.4.2.5	Attributes	19
3.1.4.2.6	Groups.....	19
3.1.4.2.7	Attribute Groups.....	19

3.1.4.3	GetPermissionCollection	19
3.1.4.3.1	Messages	20
3.1.4.3.1.1	GetPermissionCollectionSoapIn	20
3.1.4.3.1.2	GetPermissionCollectionSoapOut	20
3.1.4.3.2	Elements	20
3.1.4.3.2.1	GetPermissionCollection	20
3.1.4.3.2.2	GetPermissionCollectionResponse	21
3.1.4.3.3	Complex Types	22
3.1.4.3.4	Simple Types	22
3.1.4.3.5	Attributes	22
3.1.4.3.6	Groups	22
3.1.4.3.7	Attribute Groups	22
3.1.4.4	RemovePermission	22
3.1.4.4.1	Messages	22
3.1.4.4.1.1	RemovePermissionSoapIn	23
3.1.4.4.1.2	RemovePermissionSoapOut	23
3.1.4.4.2	Elements	23
3.1.4.4.2.1	RemovePermission	23
3.1.4.4.2.2	RemovePermissionResponse	24
3.1.4.4.3	Complex Types	24
3.1.4.4.4	Simple Types	24
3.1.4.4.5	Attributes	24
3.1.4.4.6	Groups	24
3.1.4.4.7	Attribute Groups	24
3.1.4.5	RemovePermissionCollection	24
3.1.4.5.1	Messages	25
3.1.4.5.1.1	RemovePermissionCollectionSoapIn	25
3.1.4.5.1.2	RemovePermissionCollectionSoapOut	25
3.1.4.5.2	Elements	25
3.1.4.5.2.1	RemovePermissionCollection	26
3.1.4.5.2.2	RemovePermissionCollectionResponse	26
3.1.4.5.3	Complex Types	26
3.1.4.5.4	Simple Types	27
3.1.4.5.5	Attributes	27
3.1.4.5.6	Groups	27
3.1.4.5.7	Attribute Groups	27
3.1.4.6	UpdatePermission	27
3.1.4.6.1	Messages	27
3.1.4.6.1.1	UpdatePermissionSoapIn	27
3.1.4.6.1.2	UpdatePermissionSoapOut	28
3.1.4.6.2	Elements	28
3.1.4.6.2.1	UpdatePermission	28
3.1.4.6.2.2	UpdatePermissionResponse	29
3.1.4.6.3	Complex Types	29
3.1.4.6.4	Simple Types	29
3.1.4.6.5	Attributes	29
3.1.4.6.6	Groups	29
3.1.4.6.7	Attribute Groups	29
3.1.5	Timer Events	29
3.1.6	Other Local Events	29
4	Protocol Examples	30
5	Security	33
5.1	Security Considerations for Implementers	33
5.2	Index of Security Parameters	33
6	Appendix A: Full WSDL	34
7	Appendix B: Product Behavior	40

8	Change Tracking	41
9	Index	42

1 Introduction

The Permissions Web Service Protocol enables protocol clients to manage permissions to items on the protocol server.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

1.1 Glossary

This document uses the following terms:

Hypertext Transfer Protocol (HTTP): An application-level protocol for distributed, collaborative, hypermedia information systems (text, graphic images, sound, video, and other multimedia files) on the World Wide Web.

Hypertext Transfer Protocol Secure (HTTPS): An extension of HTTP that securely encrypts and decrypts web page requests. In some older protocols, "Hypertext Transfer Protocol over Secure Sockets Layer" is still used (Secure Sockets Layer has been deprecated). For more information, see [\[SSL3\]](#) and [\[RFC5246\]](#).

list: A container within a SharePoint site that stores list items. A list has a customizable schema that is composed of one or more fields.

role: A symbolic name that defines a class of users for a set of components. A role defines which users can call interfaces on a component.

security principal: An identity that can be used to regulate access to resources. A security principal can be a user, a computer, or a group that represents a set of users.

security principal name (SPN): The name that identifies a security principal (for example, machinename\$@domainname for a machine joined to a domain or username@domainname for a user). Domainname is resolved using the Domain Name System (DNS).

site: A group of related pages and data within a SharePoint site collection. The structure and content of a site is based on a site definition. Also referred to as SharePoint site and web site.

SOAP: A lightweight protocol for exchanging structured information in a decentralized, distributed environment. **SOAP** uses **XML** technologies to define an extensible messaging framework, which provides a message construct that can be exchanged over a variety of underlying protocols. The framework has been designed to be independent of any particular programming model and other implementation-specific semantics. SOAP 1.2 supersedes SOAP 1.1. See [\[SOAP1.2-1/2003\]](#).

SOAP action: The HTTP request header field used to indicate the intent of the **SOAP** request, using a URI value. See [\[SOAP1.1\]](#) section 6.1.1 for more information.

SOAP body: A container for the payload data being delivered by a **SOAP message** to its recipient. See [\[SOAP1.2-1/2007\]](#) section 5.3 for more information.

SOAP fault: A container for error and status information within a **SOAP message**. See [\[SOAP1.2-1/2007\]](#) section 5.4 for more information.

SOAP message: An **XML** document consisting of a mandatory SOAP envelope, an optional SOAP header, and a mandatory **SOAP body**. See [\[SOAP1.2-1/2007\]](#) section 5 for more information.

Uniform Resource Locator (URL): A string of characters in a standardized format that identifies a document or resource on the World Wide Web. The format is as specified in [\[RFC1738\]](#).

web service: A unit of application logic that provides data and services to other applications and can be called by using standard Internet transport protocols such as **HTTP**, Simple Mail Transfer Protocol (SMTP), or File Transfer Protocol (FTP). Web services can perform functions that range from simple requests to complicated business processes.

Web Services Description Language (WSDL): An XML format for describing network services as a set of endpoints that operate on messages that contain either document-oriented or procedure-oriented information. The operations and messages are described abstractly and are bound to a concrete network protocol and message format in order to define an endpoint. Related concrete endpoints are combined into abstract endpoints, which describe a network service. WSDL is extensible, which allows the description of endpoints and their messages regardless of the message formats or network protocols that are used.

XML: The Extensible Markup Language, as described in [\[XML1.0\]](#).

XML namespace: A collection of names that is used to identify elements, types, and attributes in XML documents identified in a URI reference [\[RFC3986\]](#). A combination of XML namespace and local name allows XML documents to use elements, types, and attributes that have the same names but come from different sources. For more information, see [\[XMLNS-2ED\]](#).

XML schema: A description of a type of XML document that is typically expressed in terms of constraints on the structure and content of documents of that type, in addition to the basic syntax constraints that are imposed by **XML** itself. An XML schema provides a view of a document type at a relatively high level of abstraction.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[MS-WSSFO3] Microsoft Corporation, "[Windows SharePoint Services \(WSS\): File Operations Database Communications Version 3 Protocol](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.rfc-editor.org/rfc/rfc2616.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP1.2/1] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>

[SOAP1.2/2] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 2: Adjuncts", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part2-20030624>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

None.

1.3 Overview

This protocol enables protocol clients to manage permissions to content on a protocol server. The content can be stored as **sites** or **lists**, and the protocol is to be used through a **Web service**. It defines messages to add, modify, get and remove permissions.

This protocol only manages the permissions. The protocol server implementation is expected to store and enforce them.

1.4 Relationship to Other Protocols

This protocol uses the **SOAP** message protocol for formatting request and response messages, as described in [\[SOAP1.1\]](#), [\[SOAP1.2/1\]](#) and [\[SOAP1.2/2\]](#). It transmits those messages by using **HTTP**, as described in [\[RFC2616\]](#), or **Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**, as described in [\[RFC2818\]](#).

The following diagram shows the underlying messaging and transport stack used by the protocol:




Figure 1: This protocol in relation to other protocols

1.5 Prerequisites/Preconditions

This protocol operates against a site that is identified by a **URL** that is known by protocol clients. The protocol server endpoint is formed by appending "_vti_bin/permissions.asmx" to the URL of the site, for example http://www.example.com/Repository/_vti_bin/permissions.asmx.

This protocol assumes that authentication has been performed by the underlying protocols.

1.6 Applicability Statement

This protocol provides operations for a protocol client to add, modify, get, and remove permissions from a site or a list. This protocol is not intended to be used to add new **roles**.

1.7 Versioning and Capability Negotiation

This protocol uses multiple transports with SOAP as specified in section [2.1](#).

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

Protocol servers MUST support SOAP over HTTP. Protocol servers SHOULD additionally support SOAP over HTTPS for securing communication with protocol clients.

Protocol messages MUST be formatted as specified either in [\[SOAP1.1\]](#) section 4 or in [\[SOAP1.2/1\]](#) section 5. Protocol server faults MUST be returned either by using HTTP Status Codes as specified in [\[RFC2616\]](#) section 10 or by using **SOAP faults** as specified either in [\[SOAP1.1\]](#) section 4.4 or in [\[SOAP1.2/1\]](#) section 5.4.

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and **Web Services Description Language (WSDL)**, as specified in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
tns	http://schemas.microsoft.com/sharepoint/soap/directory/	
s	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]
soap12	http://schemas.xmlsoap.org/wsdl/soap12/	[SOAP1.2/1] [SOAP1.2/2]
(none)	http://schemas.microsoft.com/sharepoint/soap/directory/	
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]

2.2.2 Messages

This specification does not define any common WSDL message definitions.

2.2.3 Elements

This specification does not define any common XML schema element definitions.

2.2.4 Complex Types

This specification does not define any common XML schema complex type definitions.

2.2.5 Simple Types

This specification does not define any common XML schema simple type definitions.

2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

3 Protocol Details

Except where specified, protocol clients SHOULD interpret HTTP Status Codes returned by the protocol server as specified in [\[RFC2616\]](#) section 10.

This protocol allows protocol servers to notify protocol clients of application-level faults by using SOAP faults. Except where specified, these SOAP faults are not significant for interoperability, and protocol clients can interpret them in an implementation-specific manner.

This protocol allows protocol servers to perform implementation-specific authorization checks and notify protocol clients of authorization faults either by using HTTP Status Codes or by using SOAP faults as specified previously in this section.

3.1 Permissions Soap Server Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

A server implementation of this protocol MUST maintain a list of permissions for each list or site that it contains. Such permissions MUST be accessible by the name of the list or site that it relates to.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

The following table summarizes the list of WSDL operations as defined by this specification:

Operation	Description
AddPermission	Used to add permissions on a site or a list.
AddPermissionCollection	Used to add a collection of permissions on a site or a list.
GetPermissionCollection	Used to get the permission collection for a site or a list.
RemovePermission	Used to remove a specified permission from a list or a site.
RemovePermissionCollection	Used to remove permissions from a list or a site for the specified security principal collection.
UpdatePermission	Used to modify permissions of a list or site for the specified security principal or security group.

3.1.4.1 AddPermission

This operation is used to add site permissions for the specified security principal or security group that exists on the site, or to add permissions to the specified list for the specified security principal (2) or security group that exists on the site.

```
<wsdl:operation name="AddPermission">
  <wsdl:input message="tns:AddPermissionSoapIn" />
  <wsdl:output message="tns:AddPermissionSoapOut" />
</wsdl:operation>
```

The protocol client sends an **AddPermissionSoapIn** request message and the protocol server responds with an **AddPermissionSoapOut** response message, as follows:

- If the value specified in **objectType** is "list" and no list with the name specified in **objectName** exists, the server MUST return a SOAP fault with error code 0x82000006.
- If the value specified in **objectType** is not "list" or "web", the server MUST return a SOAP fault with error code 0x80131600.
- If the value specified in **permissionType** is not "user", "group", or "role", the server MUST return a SOAP fault with error code 0x80131600.
- If the security principal or the security group specified in **permissionIdentifier** does not exist, the server MUST return a SOAP fault with error code 0x80131600.

3.1.4.1.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
AddPermissionSoapIn	A request to initiate a AddPermission operation on the protocol server.
AddPermissionSoapOut	A response from the protocol server at completion of the AddPermission operation.

3.1.4.1.1.1 AddPermissionSoapIn

The request message for an **AddPermission** operation.

The **SOAP action** value of the message is defined as:

```
http://schemas.microsoft.com/sharepoint/soap/directory/AddPermission
```

The **SOAP body** contains an **AddPermission** element.

3.1.4.1.1.2 AddPermissionSoapOut

The response message of an **AddPermission** operation.

The SOAP body contains an **AddPermissionResponse** element.

3.1.4.1.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
AddPermission	The input data of an AddPermission operation.
AddPermissionResponse	The output data of an AddPermission operation.

3.1.4.1.2.1 AddPermission

The input data of an **AddPermission** operation. The definition of the **AddPermission** element is as follows:

```
<s:element name="AddPermission">
  <s:complexType>
    <s:sequence>
      <s:element name="objectName" type="s:string" minOccurs="1" maxOccurs="1"/>
      <s:element name="objectType" type="s:string" minOccurs="1" maxOccurs="1"/>
      <s:element name="permissionIdentifier" type="s:string" minOccurs="1" maxOccurs="1"/>
      <s:element name="permissionType" type="s:string" minOccurs="1" maxOccurs="1"/>
      <s:element name="permissionMask" type="s:int" minOccurs="1" maxOccurs="1"/>
    </s:sequence>
  </s:complexType>
</s:element>
```

objectName: A string that contains the name of a list or a site. The specified list (1) or site (2) specified in this parameter **MUST** exist on the protocol server.

objectType: A string that specifies whether permission is to be added to a list (1) or a site (2). The value **MUST** be "list" for a list (1) or "web" for a site (2).

permissionIdentifier: A string that contains the name of the security group or the **security principal name (SPN)** of the security principal to whom the permission applies. The security principal or security group **MUST** already exist on the site on the protocol server.

permissionType: A string that specifies whether permission applies to a security principal or to a security group. The value **MUST** be "user" for security principal, "group" for security group, or "role". If **permissionType** equals "role" and **objectType** equals "web", permissions for the role will not be updated. If **permissionType** equals "role" and **objectType** equals "list", permissions for all security principals assigned to the role will be updated. [<1>](#)

permissionMask: A Rights Mask that is lower 32 bits of the WSS Rights Mask that is specified in [\[MS-WSSFO3\]](#) section 2.2.2.15.

3.1.4.1.2.2 AddPermissionResponse

The output data of an **AddPermission** operation. If the operation succeeds, an **AddPermissionResponse** **MUST** be returned by the protocol server.

The definition of the **AddPermissionResponse** element is as follows:

```
<s:element name="AddPermissionResponse">
  <s:complexType/>
</s:element>
```

3.1.4.1.3 Complex Types

None.

3.1.4.1.4 Simple Types

None.

3.1.4.1.5 Attributes

None.

3.1.4.1.6 Groups

None.

3.1.4.1.7 Attribute Groups

None.

3.1.4.2 AddPermissionCollection

This operation is used to add site permissions for the specified collection of security principals or security groups, or to add permissions to a list for the specified collection of security principals or security groups that exist on the protocol server.

```
<wsdl:operation name="AddPermissionCollection">
  <wsdl:input message="tns:AddPermissionCollectionSoapIn" />
  <wsdl:output message="tns:AddPermissionCollectionSoapOut" />
</wsdl:operation>
```

The protocol client sends an **AddPermissionCollectionSoapIn** request message and the protocol server responds with an **AddPermissionCollectionSoapOut** response message, as follows:

- If the value specified in **objectType** is "list" and no list with the name specified in **objectName** exists, the server MUST return a SOAP fault with error code 0x82000006.
- If the value specified in **objectType** is not "list" or "web", the server MUST return a SOAP fault with error code 0x80131600.
- If the value specified in **permissionsInfoXml** is an invalid **XML**, the server returns a SOAP fault without an error code.

3.1.4.2.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
AddPermissionCollectionSoapIn	A request to initiate a AddPermissionCollection operation on the protocol server.
AddPermissionCollectionSoapOut	A response from the protocol server at completion of the AddPermissionCollection operation.

3.1.4.2.1.1 AddPermissionCollectionSoapIn

The request message for an **AddPermissionCollection** operation.

The SOAP action value of the message is defined as:

```
http://schemas.microsoft.com/sharepoint/soap/directory/AddPermissionCollection
```

The SOAP body contains an **AddPermissionCollection** element.

3.1.4.2.1.2 AddPermissionCollectionSoapOut

The response message of an **AddPermissionCollection** operation.

The SOAP body contains an **AddPermissionCollectionResponse** element.

3.1.4.2.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
AddPermissionCollection	The input data of an AddPermissionCollection operation.
AddPermissionCollectionResponse	The output data of an AddPermissionCollection operation.

3.1.4.2.2.1 AddPermissionCollection

The input data of an **AddPermissionCollection** operation. The definition of the **AddPermissionCollection** element is as follows:

```
<s:element name="AddPermissionCollection">
  <s:complexType>
    <s:sequence>
      <s:element name="objectName" type="s:string" minOccurs="1"/>
      <s:element name="objectType" type="s:string" minOccurs="1"/>
      <s:element name="permissionsInfoXml" minOccurs="1">
        <s:complexType>
          <s:sequence>
            <s:element name="Permissions">
              <s:complexType>
                <s:sequence>
                  <s:element name="Users" minOccurs="0" maxOccurs="1">
                    <s:complexType>
                      <s:sequence>
                        <s:element minOccurs="0" maxOccurs="100" name="User">
                          <s:complexType>
                            <s:attribute name="LoginName" type="s:string" use="required" />
                            <s:attribute name="Email" type="s:string" use="optional" />
                            <s:attribute name="Name" type="s:string" use="optional" />
                            <s:attribute name="Notes" type="s:string" use="optional" />
                            <s:attribute name="PermissionMask" type="s:int" use="required" />
                          </s:complexType>
                        </s:element>
                      </s:sequence>
                    </s:complexType>
                  </s:element>
                </s:sequence>
              </s:complexType>
            </s:element>
          </s:sequence>
        </s:complexType>
      </s:element>
    </s:sequence>
  </s:complexType>
</s:element>
```

```

</s:element>
<s:element name="Groups" minOccurs="0" maxOccurs="1">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="100" name="Group">
        <s:complexType>
          <s:attribute name="GroupName" type="s:string" use="required" />
          <s:attribute name="PermissionMask" type="s:int" use="required" />
        </s:complexType>
      </s:element>
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="Roles" minOccurs="0" maxOccurs="1">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="100" name="Role">
        <s:complexType>
          <s:attribute name="RoleName" type="s:string" use="required" />
          <s:attribute name="PermissionMask" type="s:int" use="required" />
        </s:complexType>
      </s:element>
    </s:sequence>
  </s:complexType>
</s:element>
</s:sequence>
</s:complexType>
</s:element>
</s:sequence>
</s:complexType>
</s:element>
</s:sequence>
</s:complexType>
</s:element>

```

objectName: A string that contains the name of a list or a site. The list (1) or site (2) specified in this parameter **MUST** exist on the protocol server.

objectType: A string that specifies whether permissions are to be added to a list (1) or a site (2). The value **MUST** be "list" for a list (1) or "web" for a site (2).

permissionsInfoXml: An XML fragment that contains the permissions to add. The XML fragment **MUST** adhere to the schema specified previously in this section.

Permissions: A complex type that represents the permissions to add.

Users: A complex type that represents a collection of existing users with specified permissions.

User: A complex type that represents an existing user with specified permissions.

User.LoginName: A string that specifies the user identifier (login).

User.Email: A string that specifies the user email.

User.Name: A string that specifies the user name.

User.Notes: A string that specifies the user notes.

User.PermissionMask: A Rights Mask that represents the lower 32 bits of the WSS Rights Mask that is specified in [\[MS-WSSFO3\]](#) section [2.2.2.15](#).

Groups: A complex type that represents a collection of existing cross-site groups with specified permissions.

Group: A complex type that represents an existing cross-site group with specified permissions.

Group.GroupName: A string that specifies the cross-site group name.

Group.PermissionMask: A Rights Mask that represents the lower 32 bits of the WSS Rights Mask that is specified in [MS-WSSFO3] section [2.2.2.15](#).

Roles: A complex type that represents a collection of existing roles with specified permissions.

Role: A complex type that represents an existing role definition for a user, group, or Web site.

Role.RoleName: A string that specifies the role name.

Role.PermissionMask: A Rights Mask that represents the lower 32 bits of the WSS Rights Mask that is specified in [MS-WSSFO3] section [2.2.2.15](#).

3.1.4.2.2 AddPermissionCollectionResponse

The output data of an **AddPermissionCollection** operation. If the operation succeeds, an **AddPermissionCollectionResponse** MUST be returned by the protocol server.

The definition of the **AddPermissionCollectionResponse** element is as follows:

```
<s:element name="AddPermissionCollectionResponse">
  <s:complexType/>
</s:element>
```

3.1.4.2.3 Complex Types

None.

3.1.4.2.4 Simple Types

None.

3.1.4.2.5 Attributes

None.

3.1.4.2.6 Groups

None.

3.1.4.2.7 Attribute Groups

None.

3.1.4.3 GetPermissionCollection

This operation is used to retrieve the permission collection for a site or a list from a protocol server.

```
<wsdl:operation name="GetPermissionCollection">
  <wsdl:input message="tns:GetPermissionCollectionSoapIn" />
  <wsdl:output message="tns:GetPermissionCollectionSoapOut" />
</wsdl:operation>
```

The protocol client sends a **GetPermissionCollectionSoapIn** request message and the protocol server responds with a **GetPermissionCollectionSoapOut** response message, as follows:

- If the value specified in **objectType** is "list" and no list with the name specified in **objectName** exists, the server MUST return a SOAP fault with error code 0x82000006.
- If the value specified in **objectType** is not "list" or "web", the server MUST return a SOAP fault with error code 0x80131600.

3.1.4.3.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetPermissionCollectionSoapIn	A request to initiate a GetPermissionCollection operation on the protocol server.
GetPermissionCollectionSoapOut	A response from the protocol server at completion of the GetPermissionCollection operation.

3.1.4.3.1.1 GetPermissionCollectionSoapIn

The request message for a **GetPermissionCollection** operation.

The SOAP action value of the message is defined as:

```
http://schemas.microsoft.com/sharepoint/soap/directory/GetPermissionCollection
```

The SOAP body contains a **GetPermissionCollection** element.

3.1.4.3.1.2 GetPermissionCollectionSoapOut

The response message of a **GetPermissionCollection** operation.

The SOAP body contains a **GetPermissionCollectionResponse** element.

3.1.4.3.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetPermissionCollection	The input data for a GetPermissionCollection operation.
GetPermissionCollectionResponse	The output data of a GetPermissionCollection operation.

3.1.4.3.2.1 GetPermissionCollection

The input data for a **GetPermissionCollection** operation. The definition of the **GetPermissionCollection** element is as follows:

```
<s:element name="GetPermissionCollection">
  <s:complexType>
    <s:sequence>
      <s:element name="objectName" type="s:string" minOccurs="1" maxOccurs="1"/>
      <s:element name="objectType" type="s:string" minOccurs="1" maxOccurs="1"/>
    </s:sequence>
  </s:complexType>
</s:element>
```

objectName: A string that contains the name of a list or a site. The list (1) or site (2) specified in this parameter **MUST** exist on the protocol server.

objectType: A string that specifies whether permissions are to be retrieved for a list (1) or a site (2). The value **MUST** be "list" for a list (1) or "web" for a site (2).

3.1.4.3.2.2 GetPermissionCollectionResponse

The output data of a **GetPermissionCollection** operation. If the operation succeeds, a **GetPermissionCollectionResponse** **MUST** be returned by the protocol server.

```
<s:element name="GetPermissionCollectionResponse">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="GetPermissionCollectionResult">
        <s:complexType>
          <s:sequence>
            <s:element name="GetPermissionCollection">
              <s:complexType>
                <s:sequence>
                  <s:element maxOccurs="unbounded" name="Permission">
                    <s:complexType>
                      <s:attribute name="MemberID" type="s:int" use="required" />
                      <s:attribute name="Mask" type="s:int" use="required" />
                      <s:attribute name="MemberIsUser" type="s:string" use="required" />
                      <s:attribute name="MemberGlobal" type="s:string" use="required" />
                      <s:attribute name="UserLogin" type="s:string" use="optional" />
                      <s:attribute name="GroupName" type="s:string" use="optional" />
                    </s:complexType>
                  </s:element>
                </s:sequence>
              </s:complexType>
            </s:element>
          </s:sequence>
        </s:complexType>
      </s:element>
    </s:sequence>
  </s:complexType>
</s:element>
```

GetPermissionCollectionResult: An XML fragment that contains the permissions for the specified site or list. The XML fragment **MUST** adhere to the preceding schema.

Permission: A complex type that represents the permissions for the specified site or list.

Permission.MemberID: A unique 32-bit integer that specifies the **MemberID** of the user or group for the permission.

Permission.Mask: A Rights Mask that represents the lower 32 bits of the WSS Rights Mask specified in [\[MS-WSSFO3\]](#) section [2.2.2.15](#).

Permission.MemberIsUser: A string that specifies whether the related member is user.

Permission.MemberGlobal: A string that specifies whether the related member is global.

Permission.UserLogin: A string that specifies the related user identifier (login).

Permission.GroupName: A string that specifies the related cross-site group name.

3.1.4.3.3 Complex Types

None.

3.1.4.3.4 Simple Types

None.

3.1.4.3.5 Attributes

None.

3.1.4.3.6 Groups

None.

3.1.4.3.7 Attribute Groups

None.

3.1.4.4 RemovePermission

This operation is used to remove a specified permission from a list or a site.

```
<wsdl:operation name="RemovePermission">
  <wsdl:input message="tns:RemovePermissionSoapIn" />
  <wsdl:output message="tns:RemovePermissionSoapOut" />
</wsdl:operation>
```

The protocol client sends a **RemovePermissionSoapIn** request message and the protocol server responds with a **RemovePermissionSoapOut** response message, as follows:

- If the value specified in **objectType** is "list" and no list with the name specified in **objectName** exists, the server MUST return a SOAP fault with error code 0x82000006.
- If the value specified in **objectType** is not "list" or "web", the server MUST return a SOAP fault with error code 0x80131600.
- If the value specified in **permissionType** is not "user" or "group", the server MUST return a SOAP fault with error code 0x80131600.
- If the security principal (2) or the security group specified in **permissionIdentifier** does not exist, the server MUST return a SOAP fault with error code 0x80131600.

3.1.4.4.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
RemovePermissionSoapIn	A request to initiate a RemovePermission operation on the protocol server.
RemovePermissionSoapOut	A response from the protocol server at completion of the RemovePermission operation.

3.1.4.4.1.1 RemovePermissionSoapIn

The request message for a **RemovePermission** operation.

The SOAP action value of the message is defined as:

```
http://schemas.microsoft.com/sharepoint/soap/directory/RemovePermission
```

The SOAP body contains a **RemovePermission** element.

3.1.4.4.1.2 RemovePermissionSoapOut

The response message of a **RemovePermission** operation.

The SOAP body contains a **RemovePermissionResponse** element.

3.1.4.4.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
RemovePermission	The input data for a RemovePermission operation.
RemovePermissionResponse	The output data of a RemovePermission operation.

3.1.4.4.2.1 RemovePermission

The input data for a **RemovePermission** operation. The definition of the **RemovePermission** element is as follows:

```
<s:element name="RemovePermission">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="1" maxOccurs="1" name="objectName" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="objectType" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="permissionIdentifier" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="permissionType" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
```

objectName: A string that contains the name of a list or a site. The specified list (1) or site (2) specified in this parameter MUST exist on the protocol server.

objectType: A string that specifies whether permission is to be removed for a list or a site. The value MUST be "list" for a list or "web" for a site.

permissionIdentifier: A string that contains the name of the security group or the name of the security principal (2) whose permission is to be removed. The specified security principal (2) or security group MUST already exist on the site.

permissionType: A string that specifies whether permission is to be removed for the security principal (2) or security group. The value MUST be "user" for security principal (2), "group" for security group, or "role". If **permissionType** equals "role" and **objectType** equals "web", permissions for the role will not be removed. If **permissionType** equals "role" and **objectType** equals "list", permissions for all security principals (2) assigned to the role will remain unchanged. [<2>](#)

3.1.4.4.2 RemovePermissionResponse

The output data of a **RemovePermission** operation. If the operation succeeds, a **RemovePermissionResponse** MUST be returned by the protocol server.

```
<s:element name="RemovePermissionResponse">
  <s:complexType/>
</s:element>
```

3.1.4.4.3 Complex Types

None.

3.1.4.4.4 Simple Types

None.

3.1.4.4.5 Attributes

None.

3.1.4.4.6 Groups

None.

3.1.4.4.7 Attribute Groups

None.

3.1.4.5 RemovePermissionCollection

This operation is used to remove permissions from a list or a site for the specified security principals (2).

```
<wsdl:operation name="RemovePermissionCollection">
  <wsdl:input message="tns:RemovePermissionCollectionSoapIn" />
  <wsdl:output message="tns:RemovePermissionCollectionSoapOut" />
</wsdl:operation>
```


The protocol client sends a **RemovePermissionCollectionSoapIn** request message and the protocol server responds with a **RemovePermissionCollectionSoapOut** response message, as follows:

- If the value specified in **objectType** is "list" and no list with the name specified in **objectName** exists, the server MUST return a SOAP fault with error code 0x82000006.
- If the value specified in **objectType** is not "list" or "web", the server MUST return a SOAP fault with error code 0x80131600.
- If the value specified in **memberIdsXml** is an invalid XML, the server returns a SOAP fault without an error code.

3.1.4.5.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
RemovePermissionCollectionSoapIn	A request to initiate a RemovePermissionCollection operation on the protocol server.
RemovePermissionCollectionSoapOut	A response from the protocol server at completion of the RemovePermissionCollection operation.

3.1.4.5.1.1 RemovePermissionCollectionSoapIn

The request message for a **RemovePermissionCollection** operation.

The SOAP action value of the message is defined as:

`http://schemas.microsoft.com/sharepoint/soap/directory/RemovePermissionCollection`

The SOAP body contains a **RemovePermissionCollection** element.

3.1.4.5.1.2 RemovePermissionCollectionSoapOut

The response message of a **RemovePermissionCollection** operation.

The SOAP body contains a **RemovePermissionCollectionResponse** element.

3.1.4.5.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
RemovePermissionCollection	The input data for a RemovePermissionCollection operation.
RemovePermissionCollectionResponse	The output data of a RemovePermissionCollection operation.

3.1.4.5.2.1 RemovePermissionCollection

The input data for a **RemovePermissionCollection** operation. The definition of the **RemovePermissionCollection** element is as follows:

```
<s:element name="RemovePermissionCollection">
  <s:complexType>
    <s:sequence>
      <s:element name="objectName" type="s:string" minOccurs="1"/>
      <s:element name="objectType" type="s:string" minOccurs="1"/>
      <s:element name="memberIdsXml" minOccurs="1">
        <s:complexType>
          <s:sequence>
            <s:element name="Members">
              <s:complexType>
                <s:sequence>
                  <s:element maxOccurs="unbounded" name="Member">
                    <s:complexType>
                      <s:attribute name="ID" type="s:int" use="required" />
                    </s:complexType>
                  </s:element>
                </s:sequence>
              </s:complexType>
            </s:element>
          </s:sequence>
        </s:complexType>
      </s:element>
    </s:sequence>
  </s:complexType>
</s:element>
```

objectName: A string that contains the name of a list or a site. The list (1) or site (2) specified in this parameter MUST exist on the protocol server.

objectType: A string that specifies whether permissions are to be removed for a list or a site. The value MUST be "list" for a list or "web" for a site.

memberIdsXml: An XML fragment that contains the permissions to be removed from the specified list. The XML fragment MUST adhere to the schema specified previously in this section.

Members: A complex type that represents a collection of members associated with permissions that are to be removed.

Member: A complex type that represents a user or group associated with a permission that are to be removed.

Member.ID: A 32-bit integer that specifies a unique member associated with a permission.

3.1.4.5.2.2 RemovePermissionCollectionResponse

The output data of a **RemovePermissionCollection** operation. If the operation succeeds, a **RemovePermissionCollectionResponse** MUST be returned by the protocol server.

```
<s:element name="RemovePermissionCollectionResponse">
  <s:complexType/>
</s:element>
```

3.1.4.5.3 Complex Types

None.

3.1.4.5.4 Simple Types

None.

3.1.4.5.5 Attributes

None.

3.1.4.5.6 Groups

None.

3.1.4.5.7 Attribute Groups

None.

3.1.4.6 UpdatePermission

This operation is used to modify site permissions for the specified security principal (2) or security group, or to modify permissions of a list for the specified security principal (2) or security group.

```
<wsdl:operation name="UpdatePermission">
  <wsdl:input message="tns:UpdatePermissionSoapIn" />
  <wsdl:output message="tns:UpdatePermissionSoapOut" />
</wsdl:operation>
```

The protocol client sends an **UpdatePermissionSoapIn** request message and the protocol server responds with an **UpdatePermissionSoapOut** response message, as follows:

- If the value specified in **objectType** is "list" and no list with the name specified in **objectName** exists, the server MUST return a SOAP fault with error code 0x82000006.
- If the value specified in **objectType** is not "list" or "web", the server MUST return a SOAP fault with error code 0x80131600.
- If the value specified in **permissionType** is not "user" or "group", the server MUST return a SOAP fault with error code 0x80131600.
- If the security principal (2) or the security group specified in **permissionIdentifier** does not exist, the server MUST return a SOAP fault with error code 0x80131600.

3.1.4.6.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdatePermissionSoapIn	A request to initiate a UpdatePermission operation on the protocol server.
UpdatePermissionSoapOut	A response from the protocol server at completion of the UpdatePermission operation.

3.1.4.6.1.1 UpdatePermissionSoapIn

The request message for an **UpdatePermission** operation.

The SOAP action value of the message is defined as:

```
http://schemas.microsoft.com/sharepoint/soap/directory/UpdatePermission
```

The SOAP body contains an **UpdatePermission** element.

3.1.4.6.1.2 UpdatePermissionSoapOut

The response message of an **UpdatePermission** operation.

The SOAP body contains an UpdatePermissionResponse element.

3.1.4.6.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdatePermission	The input data of an UpdatePermission operation.
UpdatePermissionResponse	The output data for an UpdatePermission operation.

3.1.4.6.2.1 UpdatePermission

The input data of an **UpdatePermission** operation. The definition of the **UpdatePermission** element is as follows:

```
<s:element name="UpdatePermission">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="1" maxOccurs="1" name="objectName" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="objectType" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="permissionIdentifier" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="permissionType" type="s:string" />
      <s:element minOccurs="1" maxOccurs="1" name="permissionMask" type="s:int" />
    </s:sequence>
  </s:complexType>
</s:element>
```

objectName: A string that contains the name of a list or a site. The list (1) or site (2) specified in this parameter **MUST** exist on the protocol server.

objectType: A string that specifies whether permission is to be updated for a list or a site. The value **MUST** be "list" for a list or "web" for a site.

permissionIdentifier: A string that contains the name of the security group or the name of the security principal (2) to whom the permission applies. The security principal (2) or security group **MUST** already exist on the site (2) on the protocol server.

permissionType: A string that specifies whether permission applies to the security principal (2) or to the security group. The value **MUST** be "user" for security principal (2), "group" for security group, or

"role". If **permissionType** equals "role" and **objectType** equals "web", the server MUST return a SOAP fault with error code 0x80131600. If **permissionType** equals "role" and **objectType** equals "list", the server MUST return a SOAP fault with error code 0x80131600. <3>

permissionMask: A Rights Mask that is lower 32 bits of the WSS Rights Mask which is specified in [\[MS-WSSFO3\]](#) section 2.2.2.15.

3.1.4.6.2.2 UpdatePermissionResponse

The output data for an **UpdatePermission** operation. If the operation succeeds, an **UpdatePermissionResponse** MUST be returned by the protocol server.

```
<s:element name="UpdatePermissionResponse">
  <s:complexType/>
</s:element>
```

3.1.4.6.3 Complex Types

None.

3.1.4.6.4 Simple Types

None.

3.1.4.6.5 Attributes

None.

3.1.4.6.6 Groups

None.

3.1.4.6.7 Attribute Groups

None.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

In this scenario, a protocol client first adds a permission to a list and then gets the collection of permissions for that list. The protocol client then updates the recently added permission and gets the collection of permissions again to see the updated collection.

A protocol client first constructs the following **SOAP message** to add a permission to a list. The protocol client sends the SOAP message to the protocol server:

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <AddPermission xmlns="http://schemas.microsoft.com/sharepoint/soap/directory/">
      <objectName>
        Announcements
      </objectName>
      <objectType>
        list
      </objectType>
      <permissionIdentifier>
        HelpGroup
      </permissionIdentifier>
      <permissionType>
        group
      </permissionType>
      <permissionMask>
        -1
      </permissionMask>
    </AddPermission>
  </soap:Body>
</soap:Envelope>
```

The protocol server then responds with the following:

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <AddPermissionResponse xmlns="http://schemas.microsoft.com/sharepoint/soap/directory/" />
  </soap:Body>
</soap:Envelope>
```

To get the collection of permissions from a list, the protocol client next constructs the following SOAP message. The protocol client sends the SOAP message to the protocol server:

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetPermissionCollection xmlns="http://schemas.microsoft.com/sharepoint/soap/directory/">
      <objectName>
        Announcements
      </objectName>
      <objectType>
        list
      </objectType>
    </GetPermissionCollection>
  </soap:Body>
</soap:Envelope>
```

The protocol server then responds with the following:

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetPermissionCollectionResponse
xmlns="http://schemas.microsoft.com/sharepoint/soap/directory/">
      <GetPermissionCollectionResult>
        <GetPermissionCollection>
          <Permissions>
            <Permission MemberID="1" Mask="-1" MemberIsUser="True" MemberGlobal="False"
UserLogin="MYDOMAIN\user1" />
            <Permission MemberID="3" Mask="-1" MemberIsUser="False" MemberGlobal="True"
GroupName="Farm Administrators" />
            <Permission MemberID="5" Mask="-1" MemberIsUser="False" MemberGlobal="True"
GroupName="HelpGroup" />
          </Permissions>
        </GetPermissionCollection>
      </GetPermissionCollectionResult>
    </GetPermissionCollectionResponse>
  </soap:Body>
</soap:Envelope>
```

To update the permissions for a group to a list, the protocol client constructs the following SOAP message and sends it to the protocol server:

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <UpdatePermission xmlns="http://schemas.microsoft.com/sharepoint/soap/directory/">
      <objectName>
        Announcements
      </objectName>
      <objectType>
        list
      </objectType>
      <permissionIdentifier>
        HelpGroup
      </permissionIdentifier>
      <permissionType>
        group
      </permissionType>
      <permissionMask>
        138612833
      </permissionMask>
    </UpdatePermission>
  </soap:Body>
</soap:Envelope>
```

The protocol server then responds with the following:

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <UpdatePermissionResponse xmlns="http://schemas.microsoft.com/sharepoint/soap/directory/"
/>
  </soap:Body>
</soap:Envelope>
```

To get the collection of permissions from a list, the protocol client then constructs the following SOAP message and sends it to the protocol server:

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetPermissionCollection xmlns="http://schemas.microsoft.com/sharepoint/soap/directory/">
      <objectName>
        Announcements
      </objectName>
      <objectType>
        list
      </objectType>
    </GetPermissionCollection>
  </soap:Body>
</soap:Envelope>
```

The protocol server then responds with the following:

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetPermissionCollectionResponse
xmlns="http://schemas.microsoft.com/sharepoint/soap/directory/">
      <GetPermissionCollectionResult>
        <GetPermissionCollection>
          <Permissions>
            <Permission MemberID="1" Mask="-1" MemberIsUser="True" MemberGlobal="False"
UserLogin="MYDOMAIN\user1" />
            <Permission MemberID="3" Mask="-1" MemberIsUser="False" MemberGlobal="True"
GroupName="Farm Administrators" />
            <Permission MemberID="5" Mask="138612833" MemberIsUser="False" MemberGlobal="True"
GroupName="HelpGroup" />
          </Permissions>
        </GetPermissionCollection>
      </GetPermissionCollectionResult>
    </GetPermissionCollectionResponse>
  </soap:Body>
</soap:Envelope>
```


5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

For ease of implementation, the full WSDL and schema are provided in this appendix.

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:tm="http://microsoft.com/wsdl/mime/textMatching/"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:mime="http://schemas.xmlsoap.org/wsdl/mime/"
xmlns:tns="http://schemas.microsoft.com/sharepoint/soap/directory/"
xmlns:s1="http://microsoft.com/wsdl/types/" xmlns:s="http://www.w3.org/2001/XMLSchema"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
targetNamespace="http://schemas.microsoft.com/sharepoint/soap/directory/"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <s:schema elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/sharepoint/soap/directory/">
      <s:import namespace="http://microsoft.com/wsdl/types/" />
      <s:element name="GetPermissionCollection">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="objectName" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="objectType" type="s:string" />
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:element name="GetPermissionCollectionResponse">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="GetPermissionCollectionResult">
              <s:complexType>
                <s:sequence>
                  <s:element name="GetPermissionCollection">
                    <s:complexType>
                      <s:sequence>
                        <s:element maxOccurs="unbounded" name="Permission">
                          <s:complexType>
                            <s:attribute name="MemberID" type="s:int" use="required" />
                            <s:attribute name="Mask" type="s:int" use="required" />
                            <s:attribute name="MemberIsUser" type="s:string" use="required" />
                            <s:attribute name="MemberGlobal" type="s:string" use="required" />
                            <s:attribute name="UserLogin" type="s:string" use="optional" />
                            <s:attribute name="GroupName" type="s:string" use="optional" />
                          </s:complexType>
                        </s:element>
                      </s:sequence>
                    </s:complexType>
                  </s:element>
                </s:sequence>
              </s:complexType>
            </s:element>
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:element name="AddPermission">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="objectName" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="objectType" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="permissionIdentifier" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="permissionType" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="permissionMask" type="s:int" />
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:element name="AddPermissionResponse">
```

```

    <s:complexType />
  </s:element>
  <s:element name="AddPermissionCollection">
    <s:complexType>
      <s:sequence>
        <s:element name="objectName" type="s:string" minOccurs="1"/>
        <s:element name="objectType" type="s:string" minOccurs="1"/>
        <s:element name="permissionsInfoXml" minOccurs="1">
          <s:complexType>
            <s:sequence>
              <s:element name="Permissions">
                <s:complexType>
                  <s:sequence>
                    <s:element name="Users" minOccurs="0" maxOccurs="1">
                      <s:complexType>
                        <s:sequence>
                          <s:element minOccurs="0" maxOccurs="100" name="User">
                            <s:complexType>
                              <s:attribute name="LoginName" type="s:string" use="required" />
                              <s:attribute name="Email" type="s:string" use="optional" />
                              <s:attribute name="Name" type="s:string" use="optional" />
                              <s:attribute name="Notes" type="s:string" use="optional" />
                              <s:attribute name="PermissionMask" type="s:int" use="required" />
                            </s:complexType>
                          </s:element>
                        </s:sequence>
                      </s:complexType>
                    </s:element>
                    <s:element name="Groups" minOccurs="0" maxOccurs="1">
                      <s:complexType>
                        <s:sequence>
                          <s:element minOccurs="0" maxOccurs="100" name="Group">
                            <s:complexType>
                              <s:attribute name="GroupName" type="s:string" use="required" />
                              <s:attribute name="PermissionMask" type="s:int" use="required" />
                            </s:complexType>
                          </s:element>
                        </s:sequence>
                      </s:complexType>
                    </s:element>
                    <s:element name="Roles" minOccurs="0" maxOccurs="1">
                      <s:complexType>
                        <s:sequence>
                          <s:element minOccurs="0" maxOccurs="100" name="Role">
                            <s:complexType>
                              <s:attribute name="RoleName" type="s:string" use="required" />
                              <s:attribute name="PermissionMask" type="s:int" use="required" />
                            </s:complexType>
                          </s:element>
                        </s:sequence>
                      </s:complexType>
                    </s:element>
                  </s:sequence>
                </s:complexType>
              </s:element>
            </s:sequence>
          </s:complexType>
        </s:element>
        <s:element name="AddPermissionCollectionResponse">
          <s:complexType />
        </s:element>
        <s:element name="UpdatePermission">
          <s:complexType>
            <s:sequence>
              <s:element minOccurs="1" maxOccurs="1" name="objectName" type="s:string" />
              <s:element minOccurs="1" maxOccurs="1" name="objectType" type="s:string" />
            </s:sequence>
          </s:complexType>
        </s:element>
      </s:sequence>
    </s:complexType>
  </s:element>

```

```

        <s:element minOccurs="1" maxOccurs="1" name="permissionIdentifier" type="s:string" />
        <s:element minOccurs="1" maxOccurs="1" name="permissionType" type="s:string" />
        <s:element minOccurs="1" maxOccurs="1" name="permissionMask" type="s:int" />
    </s:sequence>
</s:complexType>
</s:element>
<s:element name="UpdatePermissionResponse">
    <s:complexType />
</s:element>
<s:element name="RemovePermission">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="1" maxOccurs="1" name="objectName" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="objectType" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="permissionIdentifier" type="s:string" />
            <s:element minOccurs="1" maxOccurs="1" name="permissionType" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="RemovePermissionResponse">
    <s:complexType />
</s:element>
<s:element name="RemovePermissionCollection">
    <s:complexType>
        <s:sequence>
            <s:element name="objectName" type="s:string" minOccurs="1"/>
            <s:element name="objectType" type="s:string" minOccurs="1"/>
            <s:element name="memberIdsXml" minOccurs="1">
                <s:complexType>
                    <s:sequence>
                        <s:element name="Members">
                            <s:complexType>
                                <s:sequence>
                                    <s:element maxOccurs="unbounded" name="Member">
                                        <s:complexType>
                                            <s:attribute name="ID" type="s:int" use="required" />
                                        </s:complexType>
                                    </s:element>
                                </s:sequence>
                            </s:complexType>
                        </s:element>
                    </s:sequence>
                </s:complexType>
            </s:element>
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="RemovePermissionCollectionResponse">
    <s:complexType />
</s:element>
</s:schema>
<s:schema elementFormDefault="qualified"
targetNamespace="http://microsoft.com/wsdl/types/">
    <s:simpleType name="guid">
        <s:restriction base="s:string">
            <s:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-
F]{12}" />
        </s:restriction>
    </s:simpleType>
</s:schema>
</wsdl:types>
<wsdl:message name="GetPermissionCollectionSoapIn">
    <wsdl:part name="parameters" element="tns:GetPermissionCollection" />
</wsdl:message>
<wsdl:message name="GetPermissionCollectionSoapOut">
    <wsdl:part name="parameters" element="tns:GetPermissionCollectionResponse" />
</wsdl:message>
<wsdl:message name="AddPermissionSoapIn">
    <wsdl:part name="parameters" element="tns:AddPermission" />

```

```

</wsdl:message>
<wsdl:message name="AddPermissionSoapOut">
  <wsdl:part name="parameters" element="tns:AddPermissionResponse" />
</wsdl:message>
<wsdl:message name="AddPermissionCollectionSoapIn">
  <wsdl:part name="parameters" element="tns:AddPermissionCollection" />
</wsdl:message>
<wsdl:message name="AddPermissionCollectionSoapOut">
  <wsdl:part name="parameters" element="tns:AddPermissionCollectionResponse" />
</wsdl:message>
<wsdl:message name="UpdatePermissionSoapIn">
  <wsdl:part name="parameters" element="tns:UpdatePermission" />
</wsdl:message>
<wsdl:message name="UpdatePermissionSoapOut">
  <wsdl:part name="parameters" element="tns:UpdatePermissionResponse" />
</wsdl:message>
<wsdl:message name="RemovePermissionSoapIn">
  <wsdl:part name="parameters" element="tns:RemovePermission" />
</wsdl:message>
<wsdl:message name="RemovePermissionSoapOut">
  <wsdl:part name="parameters" element="tns:RemovePermissionResponse" />
</wsdl:message>
<wsdl:message name="RemovePermissionCollectionSoapIn">
  <wsdl:part name="parameters" element="tns:RemovePermissionCollection" />
</wsdl:message>
<wsdl:message name="RemovePermissionCollectionSoapOut">
  <wsdl:part name="parameters" element="tns:RemovePermissionCollectionResponse" />
</wsdl:message>
<wsdl:portType name="PermissionsSoap">
  <wsdl:operation name="GetPermissionCollection">
    <wsdl:input message="tns:GetPermissionCollectionSoapIn" />
    <wsdl:output message="tns:GetPermissionCollectionSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="AddPermission">
    <wsdl:input message="tns:AddPermissionSoapIn" />
    <wsdl:output message="tns:AddPermissionSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="AddPermissionCollection">
    <wsdl:input message="tns:AddPermissionCollectionSoapIn" />
    <wsdl:output message="tns:AddPermissionCollectionSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="UpdatePermission">
    <wsdl:input message="tns:UpdatePermissionSoapIn" />
    <wsdl:output message="tns:UpdatePermissionSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="RemovePermission">
    <wsdl:input message="tns:RemovePermissionSoapIn" />
    <wsdl:output message="tns:RemovePermissionSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="RemovePermissionCollection">
    <wsdl:input message="tns:RemovePermissionCollectionSoapIn" />
    <wsdl:output message="tns:RemovePermissionCollectionSoapOut" />
  </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="PermissionsSoap" type="tns:PermissionsSoap">
  <soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
  <wsdl:operation name="GetPermissionCollection">
    <soap:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/GetPermissionCollection"
style="document" />
    <wsdl:input>
      <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="AddPermission">

```

```

    <soap:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/AddPermission"
style="document" />
    <wsdl:input>
    <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="AddPermissionCollection">
    <soap:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/AddPermissionCollection"
style="document" />
    <wsdl:input>
    <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdatePermission">
    <soap:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/UpdatePermission"
style="document" />
    <wsdl:input>
    <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RemovePermission">
    <soap:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/RemovePermission"
style="document" />
    <wsdl:input>
    <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RemovePermissionCollection">
    <soap:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/RemovePermissionCollection"
style="document" />
    <wsdl:input>
    <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:binding name="PermissionsSoap12" type="tns:PermissionsSoap">
    <soap12:binding transport="http://schemas.xmlsoap.org/soap/http" />
    <wsdl:operation name="GetPermissionCollection">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/GetPermissionCollection"
style="document" />
    <wsdl:input>
    <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
    <wsdl:operation name="AddPermission">

```

```

    <soap12:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/AddPermission"
style="document" />
    <wsdl:input>
    <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
    <wsdl:operation name="AddPermissionCollection">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/AddPermissionCollection"
style="document" />
    <wsdl:input>
    <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
    <wsdl:operation name="UpdatePermission">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/UpdatePermission"
style="document" />
    <wsdl:input>
    <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
    <wsdl:operation name="RemovePermission">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/RemovePermission"
style="document" />
    <wsdl:input>
    <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
    <wsdl:operation name="RemovePermissionCollection">
    <soap12:operation
soapAction="http://schemas.microsoft.com/sharepoint/soap/directory/RemovePermissionCollection"
style="document" />
    <wsdl:input>
    <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
    <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding></wsdl:definitions>

```

7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs.

- The 2007 Microsoft Office system
- Microsoft Office 2010 suites
- Microsoft Office 2013
- Windows SharePoint Services 2.0
- Windows SharePoint Services 3.0
- Microsoft SharePoint Foundation 2010
- Microsoft SharePoint Foundation 2013
- Microsoft Office 2016
- Microsoft SharePoint Server 2016

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 3.1.4.1.2.1](#): This is the expected behavior but when "role" is given, Windows SharePoint Services 3.0 does not work as expected.

[<2> Section 3.1.4.4.2.1](#): This is the expected behavior but when "role" is given, Windows SharePoint Services 3.0 does not work as expected.

[<3> Section 3.1.4.6.2.1](#): This is the expected behavior but when "role" is given, Windows SharePoint Services 3.0 does not work as expected.

8 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

9 Index

A

Abstract data model
[server](#) 13
[AddPermission operation](#) 14
 attribute groups ([section 3.1.4.1.6](#) 16, [section 3.1.4.1.7](#) 16)
 [attributes](#) 16
 [complex types](#) 16
 [elements](#) 14
 [AddPermission](#) 15
 [AddPermissionResponse](#) 15
 [messages](#) 14
 [AddPermissionSoapIn](#) 14
 [AddPermissionSoapOut](#) 14
 [simple types](#) 16
[AddPermissionCollection operation](#) 16
 [attribute groups](#) 19
 [attributes](#) 19
 [complex types](#) 19
 [elements](#) 17
 [AddPermissionCollection](#) 17
 [AddPermissionCollectionResponse](#) 19
 [groups](#) 19
 [messages](#) 16
 [AddPermissionCollectionSoapIn](#) 17
 [AddPermissionCollectionSoapOut](#) 17
 [simple types](#) 19
[Applicability](#) 10
[Attribute groups](#) 12
[Attributes](#) 12

C

[Capability negotiation](#) 10
[Change tracking](#) 41
Client
 [overview](#) 13
[Complex types](#) 11

D

Data model - abstract
[server](#) 13

E

Elements
 server
 [AddPermission](#) 15
 [AddPermissionCollection](#) 17
 [AddPermissionCollectionResponse](#) 19
 [AddPermissionResponse](#) 15
 [GetPermissionCollection](#) 20
 [GetPermissionCollectionResponse](#) 21
 [RemovePermission](#) 23
 [RemovePermissionCollection](#) 26
 [RemovePermissionCollectionResponse](#) 26
 [RemovePermissionResponse](#) 24
 [UpdatePermission](#) 28
 [UpdatePermissionResponse](#) 29
Events

[local - server](#) 29
[timer - server](#) 29
[Examples](#) 30

F

[Fields - vendor-extensible](#) 10
[Full WSDL](#) 34

G

[GetPermissionCollection operation](#) 19
 [attribute groups](#) 22
 [attributes](#) 22
 [complex types](#) 22
 [elements](#) 20
 [GetPermissionCollection](#) 20
 [GetPermissionCollectionResponse](#) 21
 [groups](#) 22
 [messages](#) 20
 [GetPermissionCollectionSoapIn](#) 20
 [GetPermissionCollectionSoapOut](#) 20
 [simple types](#) 22
[Glossary](#) 7
[Groups](#) 12

I

[Implementer - security considerations](#) 33
[Index of security parameters](#) 33
[Informative references](#) 9
Initialization
 [server](#) 13
[Introduction](#) 7

L

Local events
[server](#) 29

M

Message processing
[server](#) 13
Messages
 [attribute groups](#) 12
 [attributes](#) 12
 [complex types](#) 11
 [elements](#) 11
 [enumerated](#) 11
 [groups](#) 12
 [namespaces](#) 11
 server
 [AddPermissionCollectionSoapIn](#) 17
 [AddPermissionCollectionSoapOut](#) 17
 [AddPermissionSoapIn](#) 14
 [AddPermissionSoapOut](#) 14
 [GetPermissionCollectionSoapIn](#) 20
 [GetPermissionCollectionSoapOut](#) 20
 [RemovePermissionCollectionSoapIn](#) 25
 [RemovePermissionCollectionSoapOut](#) 25
 [RemovePermissionSoapIn](#) 23

RemovePermissionSoapOut	23
UpdatePermissionSoapIn	27
UpdatePermissionSoapOut	28
simple types	12
syntax	11
transport	11
N	
Namespaces	11
Normative references	8
O	
Operations	
AddPermission	14
AddPermissionCollection	16
GetPermissionCollection	19
RemovePermission	22
RemovePermissionCollection	24
UpdatePermission	27
Overview (synopsis)	9
P	
Parameters - security index	33
Preconditions	10
Prerequisites	10
Product behavior	40
Protocol Details	
overview	13
R	
References	8
informative	9
normative	8
Relationship to other protocols	9
RemovePermission operation	22
attribute groups	24
attributes	24
complex types	24
elements	23
RemovePermission	23
RemovePermissionResponse	24
groups	24
messages	22
RemovePermissionSoapIn	23
RemovePermissionSoapOut	23
simple types	24
RemovePermissionCollection operation	24
attribute groups	27
attributes	27
complex types	26
elements	25
RemovePermissionCollection	26
RemovePermissionCollectionResponse	26
groups	27
messages	25
RemovePermissionCollectionSoapIn	25
RemovePermissionCollectionSoapOut	25
simple types	27
S	
Security	
implementer considerations	33
parameter index	33
Sequencing rules	
server	13
Server	
abstract data model	13
AddPermission operation	14
AddPermissionCollection operation	16
GetPermissionCollection operation	19
initialization	13
local events	29
message processing	13
overview	13
RemovePermission operation	22
RemovePermissionCollection operation	24
sequencing rules	13
timer events	29
timers	13
UpdatePermission operation	27
Simple types	12
Standards assignments	10
Syntax	
messages - overview	11
T	
Timer events	
server	29
Timers	
server	13
Tracking changes	41
Transport	11
Types	
complex	11
simple	12
U	
UpdatePermission operation	27
attribute groups	29
attributes	29
complex types	29
elements	28
UpdatePermission	28
UpdatePermissionResponse	29
groups	29
messages	27
UpdatePermissionSoapIn	27
UpdatePermissionSoapOut	28
simple types	29
V	
Vendor-extensible fields	10
Versioning	10
W	
WSDL	34