

[MS-PPSAS]: PerformancePoint Services Authoring Service Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
07/13/2009	0.1	Major	Initial Availability
08/28/2009	0.2	Editorial	Revised and edited the technical content
11/06/2009	0.3	Editorial	Revised and edited the technical content
02/19/2010	1.0	Major	Updated and revised the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Editorial	Revised and edited the technical content
06/07/2010	1.03	Editorial	Revised and edited the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.05	Minor	Clarified the meaning of the technical content.
09/27/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	2.0	Major	Significantly changed the technical content.
04/11/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
09/12/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	2.1	Minor	Clarified the meaning of the technical content.
02/11/2013	2.1	No change	No changes to the meaning, language, or formatting of the technical content.
07/30/2013	2.1	No change	No changes to the meaning, language, or formatting of the technical content.

Date	Revision History	Revision Class	Comments
11/18/2013	2.2	Minor	Clarified the meaning of the technical content.

Table of Contents

1 Introduction	29
1.1 Glossary	29
1.2 References	31
1.2.1 Normative References	31
1.2.2 Informative References	33
1.3 Overview	33
1.4 Relationship to Other Protocols	33
1.5 Prerequisites/Preconditions	34
1.6 Applicability Statement	34
1.7 Versioning and Capability Negotiation	35
1.8 Vendor-Extensible Fields	35
1.9 Standards Assignments	35
2 Messages	36
2.1 Transport	36
2.2 Common Message Syntax	36
2.2.1 Namespaces	36
2.2.2 Messages	37
2.2.2.1 Faults	37
2.2.2.1.1 SOAP Fault Detail Element	37
2.2.2.1.2 Full List of Possible Error Codes	37
2.2.2.1.3 Common List of Error Codes	41
2.2.3 Elements	43
2.2.4 Complex Types	43
2.2.4.1 AddAllMembersSetOp	57
2.2.4.2 AddCalcMemberSetOp	57
2.2.4.3 AddChildrenSetOp	57
2.2.4.4 AddDefaultMemberSetOp	58
2.2.4.5 AddDescendantsLeavesSetOp	58
2.2.4.6 AddDescendantsSetOp	58
2.2.4.7 AddDescendantsSubtreeSetOp	58
2.2.4.8 AddFilterSetOp	59
2.2.4.9 AddFilterTopBottomSetOp	59
2.2.4.10 AddMemberSetOp	59
2.2.4.11 AddNamedSetSetOp	60
2.2.4.12 AddParentSiblingsSetOp	60
2.2.4.13 AliasInfo	60
2.2.4.14 AnalyticBaseReportViewData	60
2.2.4.15 AnalyticChartLegend	68
2.2.4.16 AnalyticChartReportView	69
2.2.4.17 AnalyticGridReportView	70
2.2.4.18 Annotation	71
2.2.4.19 AnnotationComment	74
2.2.4.20 ArrayOfAliasInfo	74
2.2.4.21 ArrayOfAnnotationComment	75
2.2.4.22 ArrayOfAxis	75
2.2.4.23 ArrayOfBpmProperty	75
2.2.4.24 ArrayOfBpmPropertyListItem	75
2.2.4.25 ArrayOfChoice1	76
2.2.4.26 ArrayOfComment	77

2.2.4.27	ArrayOfConfiguredView	77
2.2.4.28	ArrayOfDashboardElement	77
2.2.4.29	ArrayOfDataColumnMapping	78
2.2.4.30	ArrayOfDecimal	78
2.2.4.31	ArrayOfDefaultDimensionSetting	78
2.2.4.32	ArrayOfDimension	78
2.2.4.33	ArrayOfEndPoint	79
2.2.4.34	ArrayOfFirstClassElement	79
2.2.4.35	ArrayOfGridCell	79
2.2.4.36	ArrayOfGridDisplayElement	80
2.2.4.37	ArrayOfGridHeaderItem	80
2.2.4.38	ArrayOfGridViewTransformReference	80
2.2.4.39	ArrayOfHierarchy	81
2.2.4.40	ArrayOfIndicatorBand	81
2.2.4.41	ArrayOfKpi	81
2.2.4.42	ArrayOfKpiMeasure	81
2.2.4.43	ArrayOfLevel	82
2.2.4.44	ArrayOfMeasure	82
2.2.4.45	ArrayOfMember	82
2.2.4.46	ArrayOfMemberTransform	83
2.2.4.47	ArrayOfNamedSet	83
2.2.4.48	ArrayOfNameInfo	83
2.2.4.49	ArrayOfParameter	84
2.2.4.50	ArrayOfParameterDefinition	84
2.2.4.51	ArrayOfParameterMapping	84
2.2.4.52	ArrayOfPropertyBag	85
2.2.4.53	ArrayOfSetOperation	85
2.2.4.54	ArrayOfString	85
2.2.4.55	ArrayOfTarget	85
2.2.4.56	ArrayOfTimeIntelligenceDataSource	86
2.2.4.57	ArrayOfTimeIntelligenceFormula	86
2.2.4.58	ArrayOfTimeIntelligenceLevelBinding	86
2.2.4.59	Axis	87
2.2.4.60	Banding	88
2.2.4.61	BpmException	88
2.2.4.62	BpmProperty	88
2.2.4.63	BpmPropertyBool	89
2.2.4.64	BpmPropertyDate	89
2.2.4.65	BpmPropertyDecimal	90
2.2.4.66	BpmPropertyHyperlink	90
2.2.4.67	BpmPropertyHyperlink2	90
2.2.4.68	BpmPropertyLinkBase	91
2.2.4.69	BpmPropertyList	91
2.2.4.70	BpmPropertyListItem	91
2.2.4.71	BpmPropertyLongText	92
2.2.4.72	BpmPropertyText	92
2.2.4.73	BpmPropertyUser	92
2.2.4.74	CalculatedFormulaInfo	93
2.2.4.75	CalculatedMember	93
2.2.4.76	Comment	94
2.2.4.77	ConfiguredView	94
2.2.4.78	Cube	96
2.2.4.79	Dashboard	97

2.2.4.80	DashboardElement	98
2.2.4.81	DashboardElementContainer	99
2.2.4.82	DashboardElementSize	99
2.2.4.83	DashboardItem	99
2.2.4.84	DataColumnMapping	100
2.2.4.85	DataSource	101
2.2.4.86	DataTableMapping	105
2.2.4.87	DefaultDimensionSetting	106
2.2.4.88	DictionaryWrapperOfStringGridCell	107
2.2.4.89	DictionaryWrapperOfStringPropertyBag	107
2.2.4.90	Dimension	108
2.2.4.91	Element	109
2.2.4.92	ElementVersion	109
2.2.4.93	EliminateDescendantsSetOp	109
2.2.4.94	EliminateMemberSetOp	110
2.2.4.95	EndPoint	110
2.2.4.96	ExcelDataSet	110
2.2.4.97	ExcelServicesData	111
2.2.4.98	Filter	112
2.2.4.99	FirstClassElement	113
2.2.4.100	GridCell	115
2.2.4.101	GridCellSet	122
2.2.4.102	GridColor	123
2.2.4.103	GridDisplayElement	124
2.2.4.104	GridDisplayElementActual	126
2.2.4.105	GridDisplayElementAggregation	126
2.2.4.106	GridDisplayElementHyperLink	126
2.2.4.107	GridDisplayElementIndicator	126
2.2.4.108	GridDisplayElementIndicatorText	127
2.2.4.109	GridDisplayElementNumber	127
2.2.4.110	GridDisplayElementScore	128
2.2.4.111	GridDisplayElementTarget	128
2.2.4.112	GridDisplayElementText	129
2.2.4.113	GridDisplayElementVariance	129
2.2.4.114	GridFontInfo	129
2.2.4.115	GridFormatInfo	130
2.2.4.116	GridHeaderItem	130
2.2.4.117	GridIndicatorSettings	134
2.2.4.118	GridScoreSettings	135
2.2.4.119	GridTargetSettings	135
2.2.4.120	GridVarianceSettings	136
2.2.4.121	GridViewData	137
2.2.4.122	GridViewDefinition	139
2.2.4.123	GridViewTransformReference	141
2.2.4.124	Hierarchy	141
2.2.4.125	Indicator	142
2.2.4.126	IndicatorBand	143
2.2.4.127	Item	144
2.2.4.128	Kpi	144
2.2.4.129	KpiMeasure	144
2.2.4.130	KpiNumberFormatProperties	146
2.2.4.131	Level	147
2.2.4.132	MDXParameterDefinition	147

2.2.4.133	Measure	148
2.2.4.134	Member	148
2.2.4.135	MemberList	149
2.2.4.136	MemberOperation	150
2.2.4.137	MemberOperationAllDescendants	150
2.2.4.138	MemberOperationChildren	150
2.2.4.139	MemberOperationDescendants	150
2.2.4.140	MemberOperationDrillUp	151
2.2.4.141	MemberOperationHide	151
2.2.4.142	MemberOperationLeafDescendants	151
2.2.4.143	MemberParameterDefinition	152
2.2.4.144	MemberSet	152
2.2.4.145	MemberSetFormula	152
2.2.4.146	MemberTransform	153
2.2.4.147	NamedSet	153
2.2.4.148	NamedSetParameterDefinition	154
2.2.4.149	NameInfo	154
2.2.4.150	NumericFormat	155
2.2.4.151	NumericFormatsHashtable	155
2.2.4.152	OLAPQueryData	156
2.2.4.153	OLAPReportView	156
2.2.4.154	Parameter	157
2.2.4.155	ParameterDefinition	158
2.2.4.156	ParameterMapping	159
2.2.4.157	PasReportViewData	160
2.2.4.158	PropertyBag	161
2.2.4.159	QueryState	161
2.2.4.160	ReportView	162
2.2.4.161	RepositoryLocation	165
2.2.4.162	Scorecard	166
2.2.4.163	SecondClassElement	167
2.2.4.164	SerializableDictionary	167
2.2.4.165	SetOperation	167
2.2.4.166	SqlReportViewData	169
2.2.4.167	StatusFilter	170
2.2.4.168	StrategyMapViewData	170
2.2.4.169	StringCollection	171
2.2.4.170	Target	171
2.2.4.171	TimeIntelligenceDataSource	172
2.2.4.172	TimeIntelligenceDefinition	172
2.2.4.173	TimeIntelligenceFormula	173
2.2.4.174	TimeIntelligenceLevelBinding	173
2.2.4.175	TimeIntelligenceMdxSettings	174
2.2.4.176	TimeIntelligencePostFormulaDefinition	174
2.2.4.177	TimeIntelligenceSettings	175
2.2.4.178	Title	175
2.2.4.179	ToolbarOptions	176
2.2.4.180	Tuple	177
2.2.4.181	XmlFont	177
2.2.5	Simple Types	178
2.2.5.1	AggregateTypeEnum	181
2.2.5.2	AlignmentType	181
2.2.5.3	AnalyticChartType	182

2.2.5.4	AnalyticLegendLocation	182
2.2.5.5	AnalyticMarkerStyle	183
2.2.5.6	AnnotationVersions	184
2.2.5.7	AxisType	184
2.2.5.8	BandType	185
2.2.5.9	BeginPointEmitterType	185
2.2.5.10	ConnectionContext	186
2.2.5.11	DataValuePosition	186
2.2.5.12	DateAggregationTypes	187
2.2.5.13	DimensionTypeEnum	188
2.2.5.14	EndPointCategory	189
2.2.5.15	ExcelServicesToolbarOptions	189
2.2.5.16	ExcelServicesToolbarType	190
2.2.5.17	ExcelServicesViewOptions	190
2.2.5.18	FactAggregations	191
2.2.5.19	FilterSelectionMode	192
2.2.5.20	FirstClassObjectType	193
2.2.5.21	FontStyle	193
2.2.5.22	FormatNegativeSymbol	194
2.2.5.23	FormatType	194
2.2.5.24	GraphicsUnit	195
2.2.5.25	GridCellElementStatus	196
2.2.5.26	HeaderAggregationTypes	196
2.2.5.27	HierarchyOrigin	197
2.2.5.28	HierarchyType	197
2.2.5.29	HorizontalAlignments	198
2.2.5.30	IndicatorPosition	198
2.2.5.31	IndicatorType	199
2.2.5.32	KpiPattern	199
2.2.5.33	LayoutOrientation	200
2.2.5.34	MappedColumnDataTypes	200
2.2.5.35	MappedColumnTypes	201
2.2.5.36	MemberRelationship	201
2.2.5.37	MemberTransformOperation	202
2.2.5.38	MemberTransformType	203
2.2.5.39	MemberType	203
2.2.5.40	ReportLayout	204
2.2.5.41	RollupTypes	204
2.2.5.42	ScorecardEmptyRowsFilterMode	205
2.2.5.43	ScorecardNamedSetType	205
2.2.5.44	ScorecardNodeTypes	206
2.2.5.45	ScoreTypes	207
2.2.5.46	SizeType	207
2.2.5.47	SortType	208
2.2.5.48	SqlReportViewDataServerMode	208
2.2.5.49	StrategyMapToolbarOptions	209
2.2.5.50	Trinary	209
2.2.5.51	ValueSources	210
2.2.5.52	VarianceDisplayType	210
2.2.5.53	VarianceType	211
2.2.5.54	VerticalAlignments	211
2.2.6	Attributes	212
2.2.7	Groups	212

2.2.8	Attribute Groups	212
2.2.9	Common Data Structures	212
3	Protocol Details	213
3.1	Server Details	213
3.1.1	Abstract Data Model	213
3.1.2	Timers	216
3.1.3	Initialization	216
3.1.4	Message Processing Events and Sequencing Rules	216
3.1.4.1	CreateAnnotation.....	222
3.1.4.1.1	Messages	223
3.1.4.1.1.1	CreateAnnotationSoapIn.....	223
3.1.4.1.1.2	CreateAnnotationSoapOut	223
3.1.4.1.2	Elements.....	223
3.1.4.1.2.1	CreateAnnotation	224
3.1.4.1.2.2	CreateAnnotationResponse	224
3.1.4.1.3	Complex Types	224
3.1.4.1.4	Simple Types.....	224
3.1.4.1.5	Attributes.....	224
3.1.4.1.6	Groups.....	224
3.1.4.1.7	Attribute Groups	224
3.1.4.2	CreateDashboard.....	225
3.1.4.2.1	Messages	226
3.1.4.2.1.1	CreateDashboardSoapIn.....	226
3.1.4.2.1.2	CreateDashboardSoapOut.....	226
3.1.4.2.2	Elements.....	226
3.1.4.2.2.1	CreateDashboard.....	226
3.1.4.2.2.2	CreateDashboardResponse	227
3.1.4.2.3	Complex Types	227
3.1.4.2.4	Simple Types.....	227
3.1.4.2.5	Attributes.....	227
3.1.4.2.6	Groups.....	227
3.1.4.2.7	Attribute Groups	227
3.1.4.3	CreateDataSource.....	228
3.1.4.3.1	Messages	229
3.1.4.3.1.1	CreateDataSourceSoapIn.....	229
3.1.4.3.1.2	CreateDataSourceSoapOut	229
3.1.4.3.2	Elements.....	229
3.1.4.3.2.1	CreateDataSource	229
3.1.4.3.2.2	CreateDataSourceResponse	230
3.1.4.3.3	Complex Types	230
3.1.4.3.4	Simple Types.....	230
3.1.4.3.5	Attributes.....	230
3.1.4.3.6	Groups.....	230
3.1.4.3.7	Attribute Groups	230
3.1.4.4	CreateFilter.....	231
3.1.4.4.1	Messages	232
3.1.4.4.1.1	CreateFilterSoapIn.....	232
3.1.4.4.1.2	CreateFilterSoapOut.....	232
3.1.4.4.2	Elements.....	232
3.1.4.4.2.1	CreateFilter.....	232
3.1.4.4.2.2	CreateFilterResponse	233
3.1.4.4.3	Complex Types	233

3.1.4.4.4	Simple Types	233
3.1.4.4.5	Attributes	233
3.1.4.4.6	Groups	233
3.1.4.4.7	Attribute Groups	233
3.1.4.5	CreateIndicator	233
3.1.4.5.1	Messages	234
3.1.4.5.1.1	CreateIndicatorSoapIn	235
3.1.4.5.1.2	CreateIndicatorSoapOut	235
3.1.4.5.2	Elements	235
3.1.4.5.2.1	CreateIndicator	235
3.1.4.5.2.2	CreateIndicatorResponse	236
3.1.4.5.3	Complex Types	236
3.1.4.5.4	Simple Types	236
3.1.4.5.5	Attributes	236
3.1.4.5.6	Groups	236
3.1.4.5.7	Attribute Groups	236
3.1.4.6	CreateKpi	236
3.1.4.6.1	Messages	237
3.1.4.6.1.1	CreateKpiSoapIn	238
3.1.4.6.1.2	CreateKpiSoapOut	238
3.1.4.6.2	Elements	238
3.1.4.6.2.1	CreateKpi	238
3.1.4.6.2.2	CreateKpiResponse	239
3.1.4.6.3	Complex Types	239
3.1.4.6.4	Simple Types	239
3.1.4.6.5	Attributes	239
3.1.4.6.6	Groups	239
3.1.4.6.7	Attribute Groups	239
3.1.4.7	CreateReportView	239
3.1.4.7.1	Messages	240
3.1.4.7.1.1	CreateReportViewSoapIn	241
3.1.4.7.1.2	CreateReportViewSoapOut	241
3.1.4.7.2	Elements	241
3.1.4.7.2.1	CreateReportView	241
3.1.4.7.2.2	CreateReportViewResponse	241
3.1.4.7.3	Complex Types	242
3.1.4.7.4	Simple Types	242
3.1.4.7.5	Attributes	242
3.1.4.7.6	Groups	242
3.1.4.7.7	Attribute Groups	242
3.1.4.8	CreateScorecard	242
3.1.4.8.1	Messages	243
3.1.4.8.1.1	CreateScorecardSoapIn	243
3.1.4.8.1.2	CreateScorecardSoapOut	244
3.1.4.8.2	Elements	244
3.1.4.8.2.1	CreateScorecard	244
3.1.4.8.2.2	CreateScorecardResponse	244
3.1.4.8.3	Complex Types	245
3.1.4.8.4	Simple Types	245
3.1.4.8.5	Attributes	245
3.1.4.8.6	Groups	245
3.1.4.8.7	Attribute Groups	245
3.1.4.9	DeleteAnnotation	245

3.1.4.9.1	Messages	246
3.1.4.9.1.1	DeleteAnnotationSoapIn	246
3.1.4.9.1.2	DeleteAnnotationSoapOut	246
3.1.4.9.2	Elements	246
3.1.4.9.2.1	DeleteAnnotation	246
3.1.4.9.2.2	DeleteAnnotationResponse	247
3.1.4.9.3	Complex Types	247
3.1.4.9.4	Simple Types	247
3.1.4.9.5	Attributes	247
3.1.4.9.6	Groups	247
3.1.4.9.7	Attribute Groups	247
3.1.4.10	DeleteDashboard	247
3.1.4.10.1	Messages	248
3.1.4.10.1.1	DeleteDashboardSoapIn	248
3.1.4.10.1.2	DeleteDashboardSoapOut	248
3.1.4.10.2	Elements	248
3.1.4.10.2.1	DeleteDashboard	249
3.1.4.10.2.2	DeleteDashboardResponse	249
3.1.4.10.3	Complex Types	249
3.1.4.10.4	Simple Types	249
3.1.4.10.5	Attributes	249
3.1.4.10.6	Groups	249
3.1.4.10.7	Attribute Groups	249
3.1.4.11	DeleteDataSource	250
3.1.4.11.1	Messages	250
3.1.4.11.1.1	DeleteDataSourceSoapIn	250
3.1.4.11.1.2	DeleteDataSourceSoapOut	251
3.1.4.11.2	Elements	251
3.1.4.11.2.1	DeleteDataSource	251
3.1.4.11.2.2	DeleteDataSourceResponse	251
3.1.4.11.3	Complex Types	251
3.1.4.11.4	Simple Types	251
3.1.4.11.5	Attributes	251
3.1.4.11.6	Groups	252
3.1.4.11.7	Attribute Groups	252
3.1.4.12	DeleteFilter	252
3.1.4.12.1	Messages	252
3.1.4.12.1.1	DeleteFilterSoapIn	252
3.1.4.12.1.2	DeleteFilterSoapOut	253
3.1.4.12.2	Elements	253
3.1.4.12.2.1	DeleteFilter	253
3.1.4.12.2.2	DeleteFilterResponse	253
3.1.4.12.3	Complex Types	253
3.1.4.12.4	Simple Types	253
3.1.4.12.5	Attributes	254
3.1.4.12.6	Groups	254
3.1.4.12.7	Attribute Groups	254
3.1.4.13	DeleteIndicator	254
3.1.4.13.1	Messages	254
3.1.4.13.1.1	DeleteIndicatorSoapIn	255
3.1.4.13.1.2	DeleteIndicatorSoapOut	255
3.1.4.13.2	Elements	255
3.1.4.13.2.1	DeleteIndicator	255

3.1.4.13.2.2	DeleteIndicatorResponse	255
3.1.4.13.3	Complex Types	256
3.1.4.13.4	Simple Types	256
3.1.4.13.5	Attributes	256
3.1.4.13.6	Groups.....	256
3.1.4.13.7	Attribute Groups.....	256
3.1.4.14	DeleteKpi.....	256
3.1.4.14.1	Messages	256
3.1.4.14.1.1	DeleteKpiSoapIn.....	257
3.1.4.14.1.2	DeleteKpiSoapOut.....	257
3.1.4.14.2	Elements	257
3.1.4.14.2.1	DeleteKpi.....	257
3.1.4.14.2.2	DeleteKpiResponse	257
3.1.4.14.3	Complex Types	258
3.1.4.14.4	Simple Types	258
3.1.4.14.5	Attributes	258
3.1.4.14.6	Groups.....	258
3.1.4.14.7	Attribute Groups.....	258
3.1.4.15	DeleteReportView	258
3.1.4.15.1	Messages	259
3.1.4.15.1.1	DeleteReportViewSoapIn	259
3.1.4.15.1.2	DeleteReportViewSoapOut	259
3.1.4.15.2	Elements	259
3.1.4.15.2.1	DeleteReportView	259
3.1.4.15.2.2	DeleteReportViewResponse	260
3.1.4.15.3	Complex Types	260
3.1.4.15.4	Simple Types	260
3.1.4.15.5	Attributes	260
3.1.4.15.6	Groups.....	260
3.1.4.15.7	Attribute Groups.....	260
3.1.4.16	DeleteScorecard	260
3.1.4.16.1	Messages	261
3.1.4.16.1.1	DeleteScorecardSoapIn	261
3.1.4.16.1.2	DeleteScorecardSoapOut	261
3.1.4.16.2	Elements	261
3.1.4.16.2.1	DeleteScorecard	262
3.1.4.16.2.2	DeleteScorecardResponse	262
3.1.4.16.3	Complex Types	262
3.1.4.16.4	Simple Types	262
3.1.4.16.5	Attributes	262
3.1.4.16.6	Groups.....	262
3.1.4.16.7	Attribute Groups.....	262
3.1.4.17	ExportDashboard	262
3.1.4.17.1	Messages	263
3.1.4.17.1.1	ExportDashboardSoapIn	263
3.1.4.17.1.2	ExportDashboardSoapOut	263
3.1.4.17.2	Elements	264
3.1.4.17.2.1	ExportDashboard	264
3.1.4.17.2.2	ExportDashboardResponse.....	264
3.1.4.17.3	Complex Types	264
3.1.4.17.4	Simple Types	264
3.1.4.17.5	Attributes	265
3.1.4.17.6	Groups.....	265

3.1.4.17.7	Attribute Groups.....	265
3.1.4.18	GenerateView.....	265
3.1.4.18.1	Messages.....	265
3.1.4.18.1.1	GenerateViewSoapIn.....	266
3.1.4.18.1.2	GenerateViewSoapOut.....	266
3.1.4.18.2	Elements.....	266
3.1.4.18.2.1	GenerateView.....	266
3.1.4.18.2.2	GenerateViewResponse.....	267
3.1.4.18.3	Complex Types.....	267
3.1.4.18.4	Simple Types.....	267
3.1.4.18.5	Attributes.....	267
3.1.4.18.6	Groups.....	267
3.1.4.18.7	Attribute Groups.....	267
3.1.4.19	GenerateViewDirect.....	267
3.1.4.19.1	Messages.....	268
3.1.4.19.1.1	GenerateViewDirectSoapIn.....	268
3.1.4.19.1.2	GenerateViewDirectSoapOut.....	268
3.1.4.19.2	Elements.....	268
3.1.4.19.2.1	GenerateViewDirect.....	269
3.1.4.19.2.2	GenerateViewDirectResponse.....	269
3.1.4.19.3	Complex Types.....	270
3.1.4.19.3.1	ArrayOfIndicator.....	270
3.1.4.19.3.2	ArrayOfDataSource.....	270
3.1.4.19.4	Simple Types.....	271
3.1.4.19.5	Attributes.....	271
3.1.4.19.6	Groups.....	271
3.1.4.19.7	Attribute Groups.....	271
3.1.4.20	GetAllAnnotationsByScorecardLocation.....	271
3.1.4.20.1	Messages.....	271
3.1.4.20.1.1	GetAllAnnotationsByScorecardLocationSoapIn.....	272
3.1.4.20.1.2	GetAllAnnotationsByScorecardLocationSoapOut.....	272
3.1.4.20.2	Elements.....	272
3.1.4.20.2.1	GetAllAnnotationsByScorecardLocation.....	272
3.1.4.20.2.2	GetAllAnnotationsByScorecardLocationResponse.....	273
3.1.4.20.3	Complex Types.....	273
3.1.4.20.3.1	ArrayOfAnnotation.....	273
3.1.4.20.4	Simple Types.....	273
3.1.4.20.5	Attributes.....	274
3.1.4.20.6	Groups.....	274
3.1.4.20.7	Attribute Groups.....	274
3.1.4.21	GetAnalyticReportView.....	274
3.1.4.21.1	Messages.....	275
3.1.4.21.1.1	GetAnalyticReportViewSoapIn.....	275
3.1.4.21.1.2	GetAnalyticReportViewSoapOut.....	275
3.1.4.21.2	Elements.....	275
3.1.4.21.2.1	GetAnalyticReportView.....	275
3.1.4.21.2.2	GetAnalyticReportViewResponse.....	276
3.1.4.21.3	Complex Types.....	276
3.1.4.21.4	Simple Types.....	276
3.1.4.21.5	Attributes.....	276
3.1.4.21.6	Groups.....	276
3.1.4.21.7	Attribute Groups.....	276
3.1.4.22	GetAnnotation.....	277

3.1.4.22.1	Messages	277
3.1.4.22.1.1	GetAnnotationSoapIn	277
3.1.4.22.1.2	GetAnnotationSoapOut	278
3.1.4.22.2	Elements	278
3.1.4.22.2.1	GetAnnotation	278
3.1.4.22.2.2	GetAnnotationResponse	278
3.1.4.22.3	Complex Types	279
3.1.4.22.3.1	ArrayOfTuple	279
3.1.4.22.3.2	Tuple	279
3.1.4.22.4	Simple Types	280
3.1.4.22.5	Attributes	280
3.1.4.22.6	Groups	280
3.1.4.22.7	Attribute Groups	280
3.1.4.23	GetAnnotationByID	280
3.1.4.23.1	Messages	280
3.1.4.23.1.1	GetAnnotationByIDSoapIn	281
3.1.4.23.1.2	GetAnnotationByIDSoapOut	281
3.1.4.23.2	Elements	281
3.1.4.23.2.1	GetAnnotationByID	281
3.1.4.23.2.2	GetAnnotationByIDResponse	281
3.1.4.23.3	Complex Types	282
3.1.4.23.4	Simple Types	282
3.1.4.23.5	Attributes	282
3.1.4.23.6	Groups	282
3.1.4.23.7	Attribute Groups	282
3.1.4.24	GetAnnotationSetting	282
3.1.4.24.1	Messages	282
3.1.4.24.1.1	GetAnnotationSettingSoapIn	283
3.1.4.24.1.2	GetAnnotationSettingSoapOut	283
3.1.4.24.2	Elements	283
3.1.4.24.2.1	GetAnnotationSetting	283
3.1.4.24.2.2	GetAnnotationSettingResponse	283
3.1.4.24.3	Complex Types	284
3.1.4.24.3.1	AnnotationSetting	284
3.1.4.24.4	Simple Types	284
3.1.4.24.5	Attributes	284
3.1.4.24.6	Groups	285
3.1.4.24.7	Attribute Groups	285
3.1.4.25	GetAskpis	285
3.1.4.25.1	Messages	285
3.1.4.25.1.1	GetAskpisSoapIn	285
3.1.4.25.1.2	GetAskpisSoapOut	286
3.1.4.25.2	Elements	286
3.1.4.25.2.1	GetAskpis	286
3.1.4.25.2.2	GetAskpisResponse	286
3.1.4.25.3	Complex Types	286
3.1.4.25.4	Simple Types	287
3.1.4.25.5	Attributes	287
3.1.4.25.6	Groups	287
3.1.4.25.7	Attribute Groups	287
3.1.4.26	GetCube	287
3.1.4.26.1	Messages	288
3.1.4.26.1.1	GetCubeSoapIn	288

3.1.4.26.1.2	GetCubeSoapOut	288
3.1.4.26.2	Elements	288
3.1.4.26.2.1	GetCube	288
3.1.4.26.2.2	GetCubeResponse	289
3.1.4.26.3	Complex Types	289
3.1.4.26.4	Simple Types	289
3.1.4.26.5	Attributes	289
3.1.4.26.6	Groups.....	289
3.1.4.26.7	Attribute Groups.....	289
3.1.4.27	GetCubeFromDataSource	289
3.1.4.27.1	Messages	290
3.1.4.27.1.1	GetCubeFromDataSourceSoapIn	290
3.1.4.27.1.2	GetCubeFromDataSourceSoapOut.....	290
3.1.4.27.2	Elements	290
3.1.4.27.2.1	GetCubeFromDataSource.....	291
3.1.4.27.2.2	GetCubeFromDataSourceResponse	291
3.1.4.27.3	Complex Types	291
3.1.4.27.4	Simple Types	291
3.1.4.27.5	Attributes	292
3.1.4.27.6	Groups.....	292
3.1.4.27.7	Attribute Groups.....	292
3.1.4.28	GetCubeMetaData	292
3.1.4.28.1	Messages	293
3.1.4.28.1.1	GetCubeMetaDataSoapIn	293
3.1.4.28.1.2	GetCubeMetaDataSoapOut.....	293
3.1.4.28.2	Elements	293
3.1.4.28.2.1	GetCubeMetaData	293
3.1.4.28.2.2	GetCubeMetaDataResponse	294
3.1.4.28.3	Complex Types	294
3.1.4.28.4	Simple Types	294
3.1.4.28.5	Attributes	294
3.1.4.28.6	Groups.....	294
3.1.4.28.7	Attribute Groups.....	294
3.1.4.29	GetCubeMetaDataForDataSource	294
3.1.4.29.1	Messages	295
3.1.4.29.1.1	GetCubeMetaDataForDataSourceSoapIn	295
3.1.4.29.1.2	GetCubeMetaDataForDataSourceSoapOut	296
3.1.4.29.2	Elements	296
3.1.4.29.2.1	GetCubeMetaDataForDataSource	296
3.1.4.29.2.2	GetCubeMetaDataForDataSourceResponse	296
3.1.4.29.3	Complex Types	297
3.1.4.29.4	Simple Types	297
3.1.4.29.5	Attributes	297
3.1.4.29.6	Groups.....	297
3.1.4.29.7	Attribute Groups.....	297
3.1.4.30	GetCubeNameInfos	297
3.1.4.30.1	Messages	298
3.1.4.30.1.1	GetCubeNameInfosSoapIn	298
3.1.4.30.1.2	GetCubeNameInfosSoapOut	298
3.1.4.30.2	Elements	298
3.1.4.30.2.1	GetCubeNameInfos	298
3.1.4.30.2.2	GetCubeNameInfosResponse.....	299
3.1.4.30.3	Complex Types	299

3.1.4.30.4	Simple Types	299
3.1.4.30.5	Attributes	299
3.1.4.30.6	Groups.....	299
3.1.4.30.7	Attribute Groups.....	299
3.1.4.31	GetCurrentCultureLcid	299
3.1.4.31.1	Messages	300
3.1.4.31.1.1	GetCurrentCultureLcidSoapIn	300
3.1.4.31.1.2	GetCurrentCultureLcidSoapOut	300
3.1.4.31.2	Elements	300
3.1.4.31.2.1	GetCurrentCultureLcid	300
3.1.4.31.2.2	GetCurrentCultureLcidResponse.....	301
3.1.4.31.3	Complex Types	301
3.1.4.31.4	Simple Types	301
3.1.4.31.5	Attributes	301
3.1.4.31.6	Groups.....	301
3.1.4.31.7	Attribute Groups.....	301
3.1.4.32	GetCurrentUserInfo.....	301
3.1.4.32.1	Messages	302
3.1.4.32.1.1	GetCurrentUserInfoSoapIn	302
3.1.4.32.1.2	GetCurrentUserInfoSoapOut.....	302
3.1.4.32.2	Elements	302
3.1.4.32.2.1	GetCurrentUserInfo	302
3.1.4.32.2.2	GetCurrentUserInfoResponse	303
3.1.4.32.3	Complex Types	303
3.1.4.32.4	Simple Types	303
3.1.4.32.5	Attributes	303
3.1.4.32.6	Groups.....	303
3.1.4.32.7	Attribute Groups.....	303
3.1.4.33	GetDashboard	303
3.1.4.33.1	Messages	304
3.1.4.33.1.1	GetDashboardSoapIn	304
3.1.4.33.1.2	GetDashboardSoapOut	304
3.1.4.33.2	Elements	304
3.1.4.33.2.1	GetDashboard	305
3.1.4.33.2.2	GetDashboardResponse.....	305
3.1.4.33.3	Complex Types	305
3.1.4.33.4	Simple Types	305
3.1.4.33.5	Attributes	305
3.1.4.33.6	Groups.....	305
3.1.4.33.7	Attribute Groups.....	306
3.1.4.34	GetDatabaseNamesFromDataSource	306
3.1.4.34.1	Messages	306
3.1.4.34.1.1	GetDatabaseNamesFromDataSourceSoapIn	307
3.1.4.34.1.2	GetDatabaseNamesFromDataSourceSoapOut	307
3.1.4.34.2	Elements	307
3.1.4.34.2.1	GetDatabaseNamesFromDataSource	307
3.1.4.34.2.2	GetDatabaseNamesFromDataSourceResponse	307
3.1.4.34.3	Complex Types	308
3.1.4.34.4	Simple Types	308
3.1.4.34.5	Attributes	308
3.1.4.34.6	Groups.....	308
3.1.4.34.7	Attribute Groups.....	308
3.1.4.35	GetDataSource	308

3.1.4.35.1	Messages	309
3.1.4.35.1.1	GetDataSourceSoapIn	309
3.1.4.35.1.2	GetDataSourceSoapOut	309
3.1.4.35.2	Elements	309
3.1.4.35.2.1	GetDataSource	309
3.1.4.35.2.2	GetDataSourceResponse	310
3.1.4.35.3	Complex Types	310
3.1.4.35.4	Simple Types	310
3.1.4.35.5	Attributes	310
3.1.4.35.6	Groups	310
3.1.4.35.7	Attribute Groups	310
3.1.4.36	GetDependentElements	310
3.1.4.36.1	Messages	311
3.1.4.36.1.1	GetDependentElementsSoapIn	311
3.1.4.36.1.2	GetDependentElementsSoapOut	312
3.1.4.36.2	Elements	312
3.1.4.36.2.1	GetDependentElements	312
3.1.4.36.2.2	GetDependentElementsResponse	312
3.1.4.36.3	Complex Types	313
3.1.4.36.3.1	ArrayOfRepositoryLocation	313
3.1.4.36.3.2	DependentElementInfo	313
3.1.4.36.3.3	ArrayOfRepositoryList	314
3.1.4.36.3.4	RepositoryList	314
3.1.4.36.3.5	ListLocation	314
3.1.4.36.4	Simple Types	315
3.1.4.36.4.1	FCOContentType	315
3.1.4.36.5	Attributes	316
3.1.4.36.6	Groups	316
3.1.4.36.7	Attribute Groups	316
3.1.4.37	GetDimensions	316
3.1.4.37.1	Messages	317
3.1.4.37.1.1	GetDimensionsSoapIn	317
3.1.4.37.1.2	GetDimensionsSoapOut	317
3.1.4.37.2	Elements	317
3.1.4.37.2.1	GetDimensions	317
3.1.4.37.2.2	GetDimensionsResponse	318
3.1.4.37.3	Complex Types	318
3.1.4.37.4	Simple Types	318
3.1.4.37.5	Attributes	318
3.1.4.37.6	Groups	318
3.1.4.37.7	Attribute Groups	318
3.1.4.38	GetDimensionsFromDataSource	318
3.1.4.38.1	Messages	319
3.1.4.38.1.1	GetDimensionsFromDataSourceSoapIn	319
3.1.4.38.1.2	GetDimensionsFromDataSourceSoapOut	320
3.1.4.38.2	Elements	320
3.1.4.38.2.1	GetDimensionsFromDataSource	320
3.1.4.38.2.2	GetDimensionsFromDataSourceResponse	320
3.1.4.38.3	Complex Types	321
3.1.4.38.4	Simple Types	321
3.1.4.38.5	Attributes	321
3.1.4.38.6	Groups	321
3.1.4.38.7	Attribute Groups	321

3.1.4.39	GetFilter	321
3.1.4.39.1	Messages	322
3.1.4.39.1.1	GetFilterSoapIn	322
3.1.4.39.1.2	GetFilterSoapOut	322
3.1.4.39.2	Elements	322
3.1.4.39.2.1	GetFilter	322
3.1.4.39.2.2	GetFilterResponse	323
3.1.4.39.3	Complex Types	323
3.1.4.39.4	Simple Types	323
3.1.4.39.5	Attributes	323
3.1.4.39.6	Groups	323
3.1.4.39.7	Attribute Groups	323
3.1.4.40	GetIndicator	323
3.1.4.40.1	Messages	324
3.1.4.40.1.1	GetIndicatorSoapIn	324
3.1.4.40.1.2	GetIndicatorSoapOut	324
3.1.4.40.2	Elements	324
3.1.4.40.2.1	GetIndicator	325
3.1.4.40.2.2	GetIndicatorResponse	325
3.1.4.40.3	Complex Types	325
3.1.4.40.4	Simple Types	325
3.1.4.40.5	Attributes	325
3.1.4.40.6	Groups	325
3.1.4.40.7	Attribute Groups	326
3.1.4.41	GetKpi	326
3.1.4.41.1	Messages	326
3.1.4.41.1.1	GetKpiSoapIn	326
3.1.4.41.1.2	GetKpiSoapOut	327
3.1.4.41.2	Elements	327
3.1.4.41.2.1	GetKpi	327
3.1.4.41.2.2	GetKpiResponse	327
3.1.4.41.3	Complex Types	327
3.1.4.41.4	Simple Types	328
3.1.4.41.5	Attributes	328
3.1.4.41.6	Groups	328
3.1.4.41.7	Attribute Groups	328
3.1.4.42	GetKpisFromScorecard	328
3.1.4.42.1	Messages	328
3.1.4.42.1.1	GetKpisFromScorecardSoapIn	329
3.1.4.42.1.2	GetKpisFromScorecardSoapOut	329
3.1.4.42.2	Elements	329
3.1.4.42.2.1	GetKpisFromScorecard	329
3.1.4.42.2.2	GetKpisFromScorecardResponse	330
3.1.4.42.3	Complex Types	330
3.1.4.42.4	Simple Types	330
3.1.4.42.5	Attributes	330
3.1.4.42.6	Groups	330
3.1.4.42.7	Attribute Groups	330
3.1.4.43	GetLatestAnalyticReportVersion	330
3.1.4.43.1	Messages	331
3.1.4.43.1.1	GetLatestAnalyticReportVersionSoapIn	331
3.1.4.43.1.2	GetLatestAnalyticReportVersionSoapOut	331
3.1.4.43.2	Elements	331

3.1.4.43.2.1	GetLatestAnalyticReportVersion	332
3.1.4.43.2.2	GetLatestAnalyticReportVersionResponse	332
3.1.4.43.3	Complex Types	332
3.1.4.43.4	Simple Types	332
3.1.4.43.5	Attributes	332
3.1.4.43.6	Groups	332
3.1.4.43.7	Attribute Groups	333
3.1.4.44	GetListItems	333
3.1.4.44.1	Messages	333
3.1.4.44.1.1	GetListItemsSoapIn	333
3.1.4.44.1.2	GetListItemsSoapOut	334
3.1.4.44.2	Elements	334
3.1.4.44.2.1	GetListItems	334
3.1.4.44.2.2	GetListItemsResponse	334
3.1.4.44.3	Complex Types	335
3.1.4.44.4	Simple Types	335
3.1.4.44.5	Attributes	335
3.1.4.44.6	Groups	335
3.1.4.44.7	Attribute Groups	335
3.1.4.45	GetMdx	335
3.1.4.45.1	Messages	336
3.1.4.45.1.1	GetMdxSoapIn	336
3.1.4.45.1.2	GetMdxSoapOut	336
3.1.4.45.2	Elements	336
3.1.4.45.2.1	GetMdx	336
3.1.4.45.2.2	GetMdxResponse	337
3.1.4.45.3	Complex Types	337
3.1.4.45.4	Simple Types	337
3.1.4.45.5	Attributes	337
3.1.4.45.6	Groups	337
3.1.4.45.7	Attribute Groups	338
3.1.4.46	GetParameterDisplayData	338
3.1.4.46.1	Messages	338
3.1.4.46.1.1	GetParameterDisplayDataSoapIn	339
3.1.4.46.1.2	GetParameterDisplayDataSoapOut	339
3.1.4.46.2	Elements	339
3.1.4.46.2.1	GetParameterDisplayData	339
3.1.4.46.2.2	GetParameterDisplayDataResponse	340
3.1.4.46.3	Complex Types	341
3.1.4.46.4	Simple Types	341
3.1.4.46.5	Attributes	341
3.1.4.46.6	Groups	341
3.1.4.46.7	Attribute Groups	341
3.1.4.47	GetPreviewDataSet	341
3.1.4.47.1	Messages	342
3.1.4.47.1.1	GetPreviewDataSetSoapIn	342
3.1.4.47.1.2	GetPreviewDataSetSoapOut	342
3.1.4.47.2	Elements	342
3.1.4.47.2.1	GetPreviewDataSet	342
3.1.4.47.2.2	GetPreviewDataSetResponse	343
3.1.4.47.3	Complex Types	343
3.1.4.47.4	Simple Types	343
3.1.4.47.5	Attributes	343

3.1.4.47.6	Groups.....	343
3.1.4.47.7	Attribute Groups.....	343
3.1.4.48	GetQueryResultMembers	344
3.1.4.48.1	Messages	344
3.1.4.48.1.1	GetQueryResultMembersSoapIn	344
3.1.4.48.1.2	GetQueryResultMembersSoapOut	345
3.1.4.48.2	Elements.....	345
3.1.4.48.2.1	GetQueryResultMembers	345
3.1.4.48.2.2	GetQueryResultMembersResponse	345
3.1.4.48.3	Complex Types	346
3.1.4.48.4	Simple Types	346
3.1.4.48.5	Attributes	346
3.1.4.48.6	Groups.....	346
3.1.4.48.7	Attribute Groups.....	346
3.1.4.49	GetRegisteredCustomFCOs.....	346
3.1.4.49.1	Messages	347
3.1.4.49.1.1	GetRegisteredCustomFCOsSoapIn.....	347
3.1.4.49.1.2	GetRegisteredCustomFCOsSoapOut	347
3.1.4.49.2	Elements.....	347
3.1.4.49.2.1	GetRegisteredCustomFCOs.....	347
3.1.4.49.2.2	GetRegisteredCustomFCOsResponse	348
3.1.4.49.3	Complex Types	348
3.1.4.49.3.1	ArrayOfCustomFCODefinition.....	348
3.1.4.49.3.2	CustomFCODefinition	349
3.1.4.49.4	Simple Types	349
3.1.4.49.4.1	CustomFCOType	350
3.1.4.49.5	Attributes	350
3.1.4.49.6	Groups.....	350
3.1.4.49.7	Attribute Groups.....	350
3.1.4.50	GetReportView	351
3.1.4.50.1	Messages	351
3.1.4.50.1.1	GetReportViewSoapIn	351
3.1.4.50.1.2	GetReportViewSoapOut	352
3.1.4.50.2	Elements.....	352
3.1.4.50.2.1	GetReportView	352
3.1.4.50.2.2	GetReportViewResponse	352
3.1.4.50.3	Complex Types	353
3.1.4.50.4	Simple Types	353
3.1.4.50.5	Attributes	353
3.1.4.50.6	Groups.....	353
3.1.4.50.7	Attribute Groups.....	353
3.1.4.51	GetScorecard	353
3.1.4.51.1	Messages	354
3.1.4.51.1.1	GetScorecardSoapIn	354
3.1.4.51.1.2	GetScorecardSoapOut	354
3.1.4.51.2	Elements.....	354
3.1.4.51.2.1	GetScorecard	354
3.1.4.51.2.2	GetScorecardResponse	355
3.1.4.51.3	Complex Types	355
3.1.4.51.4	Simple Types	355
3.1.4.51.5	Attributes	355
3.1.4.51.6	Groups.....	355
3.1.4.51.7	Attribute Groups.....	355

3.1.4.52	ImportDashboard.....	355
3.1.4.52.1	Messages	356
3.1.4.52.1.1	ImportDashboardSoapIn.....	356
3.1.4.52.1.2	ImportDashboardSoapOut	356
3.1.4.52.2	Elements	356
3.1.4.52.2.1	ImportDashboard	357
3.1.4.52.2.2	ImportDashboardResponse	358
3.1.4.52.3	Complex Types	358
3.1.4.52.4	Simple Types	358
3.1.4.52.5	Attributes	358
3.1.4.52.6	Groups.....	358
3.1.4.52.7	Attribute Groups.....	358
3.1.4.53	QueryChildMembers	358
3.1.4.53.1	Messages	359
3.1.4.53.1.1	QueryChildMembersSoapIn	359
3.1.4.53.1.2	QueryChildMembersSoapOut	359
3.1.4.53.2	Elements	360
3.1.4.53.2.1	QueryChildMembers	360
3.1.4.53.2.2	QueryChildMembersResponse.....	360
3.1.4.53.3	Complex Types	361
3.1.4.53.4	Simple Types	361
3.1.4.53.5	Attributes	361
3.1.4.53.6	Groups.....	361
3.1.4.53.7	Attribute Groups.....	361
3.1.4.54	QueryChildMembersByRangeFromDataSource	361
3.1.4.54.1	Messages	362
3.1.4.54.1.1	QueryChildMembersByRangeFromDataSourceSoapIn	362
3.1.4.54.1.2	QueryChildMembersByRangeFromDataSourceSoapOut	362
3.1.4.54.2	Elements	362
3.1.4.54.2.1	QueryChildMembersByRangeFromDataSource	362
3.1.4.54.2.2	QueryChildMembersByRangeFromDataSourceResponse	363
3.1.4.54.3	Complex Types	363
3.1.4.54.4	Simple Types	363
3.1.4.54.5	Attributes	363
3.1.4.54.6	Groups.....	364
3.1.4.54.7	Attribute Groups.....	364
3.1.4.55	QueryChildMembersFromDataSource.....	364
3.1.4.55.1	Messages	364
3.1.4.55.1.1	QueryChildMembersFromDataSourceSoapIn.....	365
3.1.4.55.1.2	QueryChildMembersFromDataSourceSoapOut.....	365
3.1.4.55.2	Elements	365
3.1.4.55.2.1	QueryChildMembersFromDataSource.....	365
3.1.4.55.2.2	QueryChildMembersFromDataSourceResponse	366
3.1.4.55.3	Complex Types	366
3.1.4.55.4	Simple Types	366
3.1.4.55.5	Attributes	366
3.1.4.55.6	Groups.....	366
3.1.4.55.7	Attribute Groups.....	366
3.1.4.56	QueryDimensionRootMembers	366
3.1.4.56.1	Messages	367
3.1.4.56.1.1	QueryDimensionRootMembersSoapIn	367
3.1.4.56.1.2	QueryDimensionRootMembersSoapOut.....	367
3.1.4.56.2	Elements	367

3.1.4.56.2.1	QueryDimensionRootMembers	368
3.1.4.56.2.2	QueryDimensionRootMembersResponse	368
3.1.4.56.3	Complex Types	369
3.1.4.56.4	Simple Types	369
3.1.4.56.5	Attributes	369
3.1.4.56.6	Groups	369
3.1.4.56.7	Attribute Groups	369
3.1.4.57	QueryDimensionRootMembersFromDataSource	369
3.1.4.57.1	Messages	370
3.1.4.57.1.1	QueryDimensionRootMembersFromDataSourceSoapIn	370
3.1.4.57.1.2	QueryDimensionRootMembersFromDataSourceSoapOut	370
3.1.4.57.2	Elements	370
3.1.4.57.2.1	QueryDimensionRootMembersFromDataSource	370
3.1.4.57.2.2	QueryDimensionRootMembersFromDataSourceResponse	371
3.1.4.57.3	Complex Types	371
3.1.4.57.4	Simple Types	371
3.1.4.57.5	Attributes	371
3.1.4.57.6	Groups	371
3.1.4.57.7	Attribute Groups	372
3.1.4.58	QueryNamedSets	372
3.1.4.58.1	Messages	372
3.1.4.58.1.1	QueryNamedSetsSoapIn	373
3.1.4.58.1.2	QueryNamedSetsSoapOut	373
3.1.4.58.2	Elements	373
3.1.4.58.2.1	QueryNamedSets	373
3.1.4.58.2.2	QueryNamedSetsResponse	373
3.1.4.58.3	Complex Types	374
3.1.4.58.4	Simple Types	374
3.1.4.58.5	Attributes	374
3.1.4.58.6	Groups	374
3.1.4.58.7	Attribute Groups	374
3.1.4.59	QueryNamedSetsFromDataSource	374
3.1.4.59.1	Messages	375
3.1.4.59.1.1	QueryNamedSetsFromDataSourceSoapIn	375
3.1.4.59.1.2	QueryNamedSetsFromDataSourceSoapOut	375
3.1.4.59.2	Elements	375
3.1.4.59.2.1	QueryNamedSetsFromDataSource	376
3.1.4.59.2.2	QueryNamedSetsFromDataSourceResponse	376
3.1.4.59.3	Complex Types	376
3.1.4.59.4	Simple Types	376
3.1.4.59.5	Attributes	376
3.1.4.59.6	Groups	377
3.1.4.59.7	Attribute Groups	377
3.1.4.60	QueryRelatedMember	377
3.1.4.60.1	Messages	377
3.1.4.60.1.1	QueryRelatedMemberSoapIn	378
3.1.4.60.1.2	QueryRelatedMemberSoapOut	378
3.1.4.60.2	Elements	378
3.1.4.60.2.1	QueryRelatedMember	378
3.1.4.60.2.2	QueryRelatedMemberResponse	379
3.1.4.60.3	Complex Types	379
3.1.4.60.4	Simple Types	379
3.1.4.60.5	Attributes	379

3.1.4.60.6	Groups.....	379
3.1.4.60.7	Attribute Groups.....	379
3.1.4.61	QueryRelatedMemberFromDataSource.....	379
3.1.4.61.1	Messages	380
3.1.4.61.1.1	QueryRelatedMemberFromDataSourceSoapIn.....	380
3.1.4.61.1.2	QueryRelatedMemberFromDataSourceSoapOut	381
3.1.4.61.2	Elements.....	381
3.1.4.61.2.1	QueryRelatedMemberFromDataSource	381
3.1.4.61.2.2	QueryRelatedMemberFromDataSourceResponse	382
3.1.4.61.3	Complex Types	382
3.1.4.61.4	Simple Types	382
3.1.4.61.5	Attributes	382
3.1.4.61.6	Groups.....	382
3.1.4.61.7	Attribute Groups.....	382
3.1.4.62	QueryTimeIntelligence.....	382
3.1.4.62.1	Messages	383
3.1.4.62.1.1	QueryTimeIntelligenceSoapIn.....	383
3.1.4.62.1.2	QueryTimeIntelligenceSoapOut.....	383
3.1.4.62.2	Elements.....	384
3.1.4.62.2.1	QueryTimeIntelligence.....	384
3.1.4.62.2.2	QueryTimeIntelligenceResponse	384
3.1.4.62.3	Complex Types	385
3.1.4.62.4	Simple Types	385
3.1.4.62.5	Attributes	385
3.1.4.62.6	Groups.....	385
3.1.4.62.7	Attribute Groups.....	385
3.1.4.63	QueryTimeIntelligenceDirect	385
3.1.4.63.1	Messages	386
3.1.4.63.1.1	QueryTimeIntelligenceDirectSoapIn	386
3.1.4.63.1.2	QueryTimeIntelligenceDirectSoapOut	386
3.1.4.63.2	Elements.....	386
3.1.4.63.2.1	QueryTimeIntelligenceDirect	387
3.1.4.63.2.2	QueryTimeIntelligenceDirectResponse	387
3.1.4.63.3	Complex Types	387
3.1.4.63.4	Simple Types	388
3.1.4.63.5	Attributes	388
3.1.4.63.6	Groups.....	388
3.1.4.63.7	Attribute Groups.....	388
3.1.4.64	QueryTransformMembers.....	388
3.1.4.64.1	Messages	388
3.1.4.64.1.1	QueryTransformMembersSoapIn.....	389
3.1.4.64.1.2	QueryTransformMembersSoapOut.....	389
3.1.4.64.2	Elements.....	389
3.1.4.64.2.1	QueryTransformMembers.....	389
3.1.4.64.2.2	QueryTransformMembersResponse	390
3.1.4.64.3	Complex Types	390
3.1.4.64.4	Simple Types	390
3.1.4.64.4.1	QueryTransformMembersType	390
3.1.4.64.5	Attributes	391
3.1.4.64.6	Groups.....	391
3.1.4.64.7	Attribute Groups.....	391
3.1.4.65	SaveTemporaryAnalyticReport.....	391
3.1.4.65.1	Messages	392

3.1.4.65.1.1	SaveTemporaryAnalyticReportSoapIn.....	392
3.1.4.65.1.2	SaveTemporaryAnalyticReportSoapOut.....	392
3.1.4.65.2	Elements.....	393
3.1.4.65.2.1	SaveTemporaryAnalyticReport.....	393
3.1.4.65.2.2	SaveTemporaryAnalyticReportResponse.....	393
3.1.4.65.3	Complex Types.....	393
3.1.4.65.4	Simple Types.....	394
3.1.4.65.5	Attributes.....	394
3.1.4.65.6	Groups.....	394
3.1.4.65.7	Attribute Groups.....	394
3.1.4.66	TestConnection.....	394
3.1.4.66.1	Messages.....	395
3.1.4.66.1.1	TestConnectionSoapIn.....	395
3.1.4.66.1.2	TestConnectionSoapOut.....	395
3.1.4.66.2	Elements.....	395
3.1.4.66.2.1	TestConnection.....	395
3.1.4.66.2.2	TestConnectionResponse.....	396
3.1.4.66.3	Complex Types.....	396
3.1.4.66.4	Simple Types.....	396
3.1.4.66.5	Attributes.....	396
3.1.4.66.6	Groups.....	396
3.1.4.66.7	Attribute Groups.....	396
3.1.4.67	TrimAnnotationByOwner.....	396
3.1.4.67.1	Messages.....	397
3.1.4.67.1.1	TrimAnnotationByOwnerSoapIn.....	397
3.1.4.67.1.2	TrimAnnotationByOwnerSoapOut.....	397
3.1.4.67.2	Elements.....	397
3.1.4.67.2.1	TrimAnnotationByOwner.....	398
3.1.4.67.2.2	TrimAnnotationByOwnerResponse.....	398
3.1.4.67.3	Complex Types.....	398
3.1.4.67.4	Simple Types.....	398
3.1.4.67.5	Attributes.....	398
3.1.4.67.6	Groups.....	398
3.1.4.67.7	Attribute Groups.....	398
3.1.4.68	TrimAnnotationByScorecardLocation.....	398
3.1.4.68.1	Messages.....	399
3.1.4.68.1.1	TrimAnnotationByScorecardLocationSoapIn.....	399
3.1.4.68.1.2	TrimAnnotationByScorecardLocationSoapOut.....	400
3.1.4.68.2	Elements.....	400
3.1.4.68.2.1	TrimAnnotationByScorecardLocation.....	400
3.1.4.68.2.2	TrimAnnotationByScorecardLocationResponse.....	400
3.1.4.68.3	Complex Types.....	400
3.1.4.68.4	Simple Types.....	401
3.1.4.68.5	Attributes.....	401
3.1.4.68.6	Groups.....	401
3.1.4.68.7	Attribute Groups.....	401
3.1.4.69	TrimAnnotationUntouchedSince.....	401
3.1.4.69.1	Messages.....	401
3.1.4.69.1.1	TrimAnnotationUntouchedSinceSoapIn.....	402
3.1.4.69.1.2	TrimAnnotationUntouchedSinceSoapOut.....	402
3.1.4.69.2	Elements.....	402
3.1.4.69.2.1	TrimAnnotationUntouchedSince.....	402
3.1.4.69.2.2	TrimAnnotationUntouchedSinceResponse.....	403

3.1.4.69.3	Complex Types	403
3.1.4.69.4	Simple Types	403
3.1.4.69.5	Attributes	403
3.1.4.69.6	Groups	403
3.1.4.69.7	Attribute Groups.....	403
3.1.4.70	UpdateAnnotation	403
3.1.4.70.1	Messages	404
3.1.4.70.1.1	UpdateAnnotationSoapIn	404
3.1.4.70.1.2	UpdateAnnotationSoapOut	405
3.1.4.70.2	Elements	405
3.1.4.70.2.1	UpdateAnnotation	405
3.1.4.70.2.2	UpdateAnnotationResponse	405
3.1.4.70.3	Complex Types	406
3.1.4.70.4	Simple Types	406
3.1.4.70.5	Attributes	406
3.1.4.70.6	Groups.....	406
3.1.4.70.7	Attribute Groups.....	406
3.1.4.71	UpdateDashboard	406
3.1.4.71.1	Messages	407
3.1.4.71.1.1	UpdateDashboardSoapIn	407
3.1.4.71.1.2	UpdateDashboardSoapOut	407
3.1.4.71.2	Elements	408
3.1.4.71.2.1	UpdateDashboard	408
3.1.4.71.2.2	UpdateDashboardResponse	408
3.1.4.71.3	Complex Types	408
3.1.4.71.4	Simple Types	408
3.1.4.71.5	Attributes	409
3.1.4.71.6	Groups.....	409
3.1.4.71.7	Attribute Groups.....	409
3.1.4.72	UpdateDataSource	409
3.1.4.72.1	Messages	410
3.1.4.72.1.1	UpdateDataSourceSoapIn	410
3.1.4.72.1.2	UpdateDataSourceSoapOut	410
3.1.4.72.2	Elements	411
3.1.4.72.2.1	UpdateDataSource	411
3.1.4.72.2.2	UpdateDataSourceResponse.....	411
3.1.4.72.3	Complex Types	411
3.1.4.72.4	Simple Types	411
3.1.4.72.5	Attributes	412
3.1.4.72.6	Groups.....	412
3.1.4.72.7	Attribute Groups.....	412
3.1.4.73	UpdateFilter	412
3.1.4.73.1	Messages	413
3.1.4.73.1.1	UpdateFilterSoapIn	413
3.1.4.73.1.2	UpdateFilterSoapOut	413
3.1.4.73.2	Elements	413
3.1.4.73.2.1	UpdateFilter	414
3.1.4.73.2.2	UpdateFilterResponse.....	414
3.1.4.73.3	Complex Types	414
3.1.4.73.4	Simple Types	414
3.1.4.73.5	Attributes	414
3.1.4.73.6	Groups.....	414
3.1.4.73.7	Attribute Groups.....	415

3.1.4.74	UpdateIndicator	415
3.1.4.74.1	Messages	416
3.1.4.74.1.1	UpdateIndicatorSoapIn	416
3.1.4.74.1.2	UpdateIndicatorSoapOut	416
3.1.4.74.2	Elements	417
3.1.4.74.2.1	UpdateIndicator	417
3.1.4.74.2.2	UpdateIndicatorResponse	417
3.1.4.74.3	Complex Types	417
3.1.4.74.4	Simple Types	417
3.1.4.74.5	Attributes	417
3.1.4.74.6	Groups	418
3.1.4.74.7	Attribute Groups	418
3.1.4.75	UpdateKpi	418
3.1.4.75.1	Messages	419
3.1.4.75.1.1	UpdateKpiSoapIn	419
3.1.4.75.1.2	UpdateKpiSoapOut	419
3.1.4.75.2	Elements	419
3.1.4.75.2.1	UpdateKpi	420
3.1.4.75.2.2	UpdateKpiResponse	420
3.1.4.75.3	Complex Types	420
3.1.4.75.4	Simple Types	420
3.1.4.75.5	Attributes	420
3.1.4.75.6	Groups	420
3.1.4.75.7	Attribute Groups	420
3.1.4.76	UpdateReportView	421
3.1.4.76.1	Messages	422
3.1.4.76.1.1	UpdateReportViewSoapIn	422
3.1.4.76.1.2	UpdateReportViewSoapOut	422
3.1.4.76.2	Elements	422
3.1.4.76.2.1	UpdateReportView	423
3.1.4.76.2.2	UpdateReportViewResponse	423
3.1.4.76.3	Complex Types	423
3.1.4.76.4	Simple Types	423
3.1.4.76.5	Attributes	423
3.1.4.76.6	Groups	423
3.1.4.76.7	Attribute Groups	423
3.1.4.77	UpdateScorecard	424
3.1.4.77.1	Messages	424
3.1.4.77.1.1	UpdateScorecardSoapIn	425
3.1.4.77.1.2	UpdateScorecardSoapOut	425
3.1.4.77.2	Elements	425
3.1.4.77.2.1	UpdateScorecard	425
3.1.4.77.2.2	UpdateScorecardResponse	425
3.1.4.77.3	Complex Types	426
3.1.4.77.4	Simple Types	426
3.1.4.77.5	Attributes	426
3.1.4.77.6	Groups	426
3.1.4.77.7	Attribute Groups	426
3.1.4.78	ValidateKpi	426
3.1.4.78.1	Messages	427
3.1.4.78.1.1	ValidateKpiSoapIn	427
3.1.4.78.1.2	ValidateKpiSoapOut	428
3.1.4.78.2	Elements	428

3.1.4.78.2.1	ValidateKpi	428
3.1.4.78.2.2	ValidateKpiResponse	428
3.1.4.78.3	Complex Types	428
3.1.4.78.4	Simple Types	428
3.1.4.78.5	Attributes	429
3.1.4.78.6	Groups.....	429
3.1.4.78.7	Attribute Groups.....	429
3.1.4.79	ValidateScorecard	429
3.1.4.79.1	Messages	429
3.1.4.79.1.1	ValidateScorecardSoapIn	430
3.1.4.79.1.2	ValidateScorecardSoapOut	430
3.1.4.79.2	Elements.....	430
3.1.4.79.2.1	ValidateScorecard	430
3.1.4.79.2.2	ValidateScorecardResponse.....	430
3.1.4.79.3	Complex Types	431
3.1.4.79.4	Simple Types	431
3.1.4.79.5	Attributes	431
3.1.4.79.6	Groups.....	431
3.1.4.79.7	Attribute Groups.....	431
3.1.4.80	ValidateSiteCollection	431
3.1.4.80.1	Messages	432
3.1.4.80.1.1	ValidateSiteCollectionSoapIn	432
3.1.4.80.1.2	ValidateSiteCollectionSoapOut.....	432
3.1.4.80.2	Elements.....	432
3.1.4.80.2.1	ValidateSiteCollection	433
3.1.4.80.2.2	ValidateSiteCollectionResponse.....	433
3.1.4.80.3	Complex Types	433
3.1.4.80.4	Simple Types	433
3.1.4.80.4.1	URLValidationResult	433
3.1.4.80.5	Attributes	434
3.1.4.80.6	Groups.....	435
3.1.4.80.7	Attribute Groups.....	435
3.1.5	Timer Events	435
3.1.6	Other Local Events	435
4	Protocol Examples.....	436
4.1	Scorecard Update	436
4.1.1	CreateKpi	436
4.1.2	GetScorecard.....	440
4.1.3	UpdateScorecard.....	446
4.1.4	GenerateView	459
4.1.5	DeleteScorecard.....	464
4.2	Create and Use a DataSource.....	465
4.2.1	CreateDataSource	465
4.2.2	TestDataSource	467
4.2.3	GetDimensions.....	468
4.2.4	QueryDimensionRootMembersFromDataSource	471
4.2.5	QueryChildMembersFromDataSource	471
5	Security.....	473
5.1	Security Considerations for Implementers.....	473
5.2	Index of Security Parameters	473

6	Appendix A: Full WSDL	474
7	Appendix B: Full XML Schema	581
7.1	http://performancepoint.microsoft.com/OLAPQueryData Schema	581
7.2	http://schemas.microsoft.com/performancepoint/2007/03/query Schema	581
7.3	http://www.microsoft.com/performancepoint/scorecards/Analytics Schema	581
8	Appendix C: Product Behavior	583
9	Change Tracking	586
10	Index	588

1 Introduction

The PerformancePoint Services Authoring Service Protocol specifies the PerformancePoint Authoring Services Protocol, which is a Web service protocol that is used to read from, write to, and perform basic operations on a visual interface displaying related views hosted on a server.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

- deserialize**
- GUID**
- Hypertext Transfer Protocol (HTTP)**
- Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**
- object**
- Secure Sockets Layer (SSL)**
- server**
- SOAP**
- SOAP action**
- SOAP body**
- SOAP fault**
- UTF-8**
- XML namespace**

The following terms are defined in [\[MS-OFCGLOS\]](#):

- Analysis Services**
- attribute hierarchy**
- AutoFilter**
- banding**
- base64 encoding**
- cell**
- child**
- context site**
- cube**
- current user**
- current version**
- dashboard**
- data point**
- data source**
- descendant**
- dimension**
- display folder**
- document library**
- drilldown**
- feature**
- filter**
- formula**
- hierarchy**
- hyperlink**

item
key performance indicator (KPI)
level
list
list item
login name
major version
master page
MDS
measure
measure group
member
multidimensional expression (MDX)
OLAP
OLAP calculated member
PivotChart
PivotTable
pixel
Portable Network Graphics (PNG)
published item
query
report
report view
rollup
score
scorecard
server-relative URL
site
site collection
slice
slicer
SOAP fault detail
subsite
target
target application
ToolTip
transform
trusted location
tuple
UI culture
Unified Modeling Language (UML)
Uniform Resource Locator (URL)
Web Part
Web Services Description Language (WSDL)
whitespace
workbook
WSDL message
WSDL operation
XML document
XML namespace prefix
XML schema

The following terms are specific to this document:

average weighted value: A type of rollup value. It indicates an average that factors the weighted value of all of the child values that are contained within it.

default member: The dimension member that is used in a query if a member is not specified for the dimension.

fact: A row in a table that contains numerical measures and keys, and associates specific facts with dimension tables, which are referred to as fact tables. A fact contains values that define a data event, such as a sales transaction.

named set: A grouping of dimension members or items from a data source that are named and treated as a single unit and can be referenced or reused multiple times.

normalized: In relational database design, the movement of data toward its optimized state, typically third normal form, to avoid redundancy and inconsistency and to promote efficient maintenance and storage of that data.

objective KPI: A type of key performance indicator (KPI) that derives its target value and score from a rollup of the child KPIs that are contained within it.

security zone: A setting that determines whether a resource, such as a website, can access data on other domains, or access files and settings on a user's computer. There are four security zones: Internet, Local intranet, Trusted sites, and Restricted sites. The zone to which a resource is assigned specifies the security settings that are used for that resource. See also form security level.

Simple Time Period Specification (STPS): A language and syntax that can be used to define time-based expressions, such as offsets from a specific date or the current date.

strategy map: A performance management tool that is used to visually present objectives and goals, groupings of objectives and goals, and mappings of objectives and goals to themes, initiatives, key performance indicators (KPIs), targets, business processes, and action plans.

time intelligence: A type of computation that is used to update data automatically, relative to the current time, in scorecards and reports.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-DSDIFFGRAM] Microsoft Corporation, "[SharePoint Web Services: DataSet DiffGram Structure Specification](#)".

- [MS-ESP] Microsoft Corporation, "[Excel Web Services Protocol](#)".
- [MS-NRBF] Microsoft Corporation, "[.NET Remoting: Binary Format Data Structure](#)".
- [MS-PRIMEPF] Microsoft Corporation, "[Deployment Package Format Specification](#)".
- [MS-SSAS] Microsoft Corporation, "[SQL Server Analysis Services Protocol Specification](#)".
- [MS-SSWPS] Microsoft Corporation, "[Secure Store Web Service Protocol](#)".
- [MS-VGSFF] Microsoft Corporation, "[Visio Graphics Service File Format \(.vdw\) Specification](#)".
- [MS-XLS] Microsoft Corporation, "[Excel Binary File Format \(.xls\) Structure](#)".
- [MS-XLSX] Microsoft Corporation, "[Excel Extensions to the Office Open XML SpreadsheetML File Format \(.xlsx\) Specification](#)".
- [RFC1738] Berners-Lee, T., Masinter, L., and McCahill, M., "Uniform Resource Locators (URL)", RFC 1738, December 1994, <http://www.ietf.org/rfc/rfc1738.txt>
- [RFC1808] Fielding, R., "Relative Uniform Resource Locators", RFC 1808, June 1995, <http://www.rfc-editor.org/rfc/rfc1808.txt>
- [RFC1952] Deutsch, P., "GZIP file format specification version 4.3", RFC 1952, May 1996, <http://www.rfc-editor.org/rfc/rfc1952.txt>
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>
- [RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>
- [SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>
- [SOAP1.2/1] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>
- [SOAP1.2/2] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 2: Adjuncts", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part2-20030624>
- [UNICODE] The Unicode Consortium, "Unicode Home Page", 2006, <http://www.unicode.org/>
- [WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>
- [XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>
- [XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., Eds., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>
- [XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[DataTable] Microsoft Corporation, "DataTable Class", <http://msdn.microsoft.com/en-us/library/system.data.datatable.aspx>

[MSDN-Axis] Microsoft Corporation, "Axis (MDX) Function", <http://msdn.microsoft.com/en-us/library/ms145531.aspx>

[MSFT-ConnectionFormula] Microsoft Corporation, "Use the Connection Formula dialog box to configure a filter connection", TechNet Library, [http://technet.microsoft.com/en-us/library/ff535788\(office.14\).aspx](http://technet.microsoft.com/en-us/library/ff535788(office.14).aspx)

[MSFT-TimeIntelligence] Microsoft Corporation, "About syntax for Time Intelligence expressions", Office Online, <http://office.microsoft.com/en-us/help/HA102411381033.aspx>

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

1.3 Overview

Dashboard platforms typically support workflow whereby a user creates and publishes content representing the various parts that make up **dashboards**, such as indicators, scorecards, reports in a variety of forms, and data source references. This content is composed of metadata (such as names of **dimensions (1)** or measures, or the names of data source references), calculation definitions, and formatting information (such as color or layout.)

This protocol enables a protocol client to:

- Create, read, update, validate and delete a variety of dashboard content in a content store. The types and sub-types of content were summarized previously, and described in detail by Common Message Syntax (section [2](#).)
- Create, read, update, and delete annotations in an annotation store.
- Retrieve metadata, such as the names of dimensions (1) or measures, via data source references.
- Retrieve data sets via data source references.
- Retrieve a listing of content sub-types and component information from a configuration store.

A typical scenario for using this protocol is an extensible editing application that enables users to create, publish and maintain some of the content used in a larger dashboard rendering system.

1.4 Relationship to Other Protocols

This protocol uses the **SOAP** message protocol for formatting request and response messages, as described in [\[SOAP1.1\]](#), [\[SOAP1.2/1\]](#) and [\[SOAP1.2/2\]](#). It transmits those messages by using **HTTP**, as described in [\[RFC2616\]](#), or **Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**, as described in [\[RFC2818\]](#).

The following diagram shows the underlying messaging and transport stack used by the protocol:




Figure 1: This protocol in relation to other protocols

1.5 Prerequisites/Preconditions

This protocol operates against a site that is identified by a **URL** that is known by protocol clients. The **server (2)** endpoint is formed by appending "_vti_bin/pps/ppsauthoringservice.asmx" to the URL or the site, as in `http://www.contoso.com/_vti_bin/pps/ppsauthoringservice.asmx`, for example.

This protocol assumes that authentication has been performed by the underlying protocols.

1.6 Applicability Statement

This protocol enables communication between a server (2) that stores dashboard logic definitions and a protocol client which presents a user interface to author them.

This protocol is typically used to build dashboard editing applications. Other typical usages are limited to:

- Publishing a scorecard and retrieving the [GridViewData](#) for a scorecard so that the data can be rendered in an alternative fashion, such as for a mobile device (see section [3.1.4.19](#)).
- Creating and testing data source definitions (including retrieving test data sets) to check that the data source is configured correctly for used in the separate construction of scorecards or dashboards.

This protocol is intended for use by protocol clients connected by high-bandwidth, low-latency network connections, because of the complexity of some of the types used in the protocol and the typically large amount of metadata associated with data sources used in dashboards.

This protocol is not intended as a pass-through to query and receive data sets from back end data sources, except in service of the typical uses described previously.

Although the protocol does not require data source metadata references be acquired using the protocol (for example, publish scorecard content containing member names that were not acquired using the protocol) the protocol does not provide for discrete validation of metadata, so appropriate and typical use is using only this protocol to acquire metadata references (for example, retrieve member names using this protocol to create scorecard content then publish that content using the protocol.)

Although the server (2) does return authentication information (for example authenticated user name), it is not intended as an authentication protocol.

Although this protocol does provide content type extensibility, to the extent that any content for any purpose could be published via the protocol, it is not intended for publishing content other than that which makes up a dashboard.

1.7 Versioning and Capability Negotiation

In addition to specifying versioning issues in the following areas, this protocol does not provide specific mechanisms to handle versioning and capability negotiation other than what's provided by the standard SOAP [\[SOAP1.1\]](#) protocol:

- **Supported Transports:** This protocol uses multiple transports with SOAP as described in section Transport (see section [2.1](#))
- **Security and Authentication Methods:** The security and authentication methods supported by this protocol are described in section Security (see section [5](#)).
- **Localization:** This protocol includes text strings in various messages. Localization considerations for such strings are described in sections Common Message Syntax (see section [2.2](#)) and Message Processing Events and Sequencing Rules (see section [3.1.4](#)).

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

Occasionally, instances occur where this web service's **Web Services Description Language (WSDL)** specifies optionality (for example, `minOccurs="0"` and `maxOccurs="1"`) that conflicts with the stated behavior in this document, or the document doesn't contain the stated behavior. In such cases where the document and the WSDL conflict, the document takes precedence. In cases where the document doesn't specify optionality, the argument has to be present, even if the WSDL specifies that the argument is optional (for example, `minOccurs="0"`).

In cases where an argument is optional and the WSDL specifies both `"minOccurs=0"` and `"Nillable=true"`, treat the argument as only `"minOccurs=0"`.

2.1 Transport

Servers (1) **MUST** support SOAP over HTTP. Servers (1) **SHOULD** also support SOAP over HTTPS to provide secure communication between protocol clients and servers (1).

Protocol messages **MUST** be formatted as specified either in [\[SOAP1.1\]](#), section 4 or in [\[SOAP1.2/1\]](#), section 5. Server faults **MUST** be returned either using HTTP Status Codes as specified in [\[RFC2616\]](#), section 10 or using **SOAP faults** as specified in [\[SOAP1.1\]](#), section 4.4. The version of the SOAP fault returned **MUST** correspond to the version of SOAP used for the request **WSDL message**.

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and WSDL, as specified in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific **XML namespace prefix** for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
http	http://schemas.xmlsoap.org/wsdl/http/	
qdata	http://performancepoint.microsoft.com/OLAPQueryData	
query	http://schemas.microsoft.com/performancepoint/2007/03/query	
s1	http://microsoft.com/wsdl/types/	
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
soap12	http://schemas.xmlsoap.org/wsdl/soap12/	[SOAP1.2/1] [SOAP1.2/2]
tns	http://www.microsoft.com/performancepoint/scorecards	
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]

Prefix	Namespace URI	Reference
		[XMLSCHEMA2]

2.2.2 Messages

The following table summarizes common WSDL messages defined by this specification.

Message	Description
SOAP fault	The operations defined in section 3.1.4 return a SOAP fault as specified in section 2.2.2.1 .

This specification does not define any common WSDL message definitions.

2.2.2.1 Faults

In the event of an application error, the server (2) returns a SOAP fault as a response to the operation as specified in [\[SOAP1.1\]](#) section 4.4.

2.2.2.1.1 SOAP Fault Detail Element

The protocol client MUST ignore all elements of the SOAP fault, except for the **SOAP fault detail** element.

The SOAP fault detail element MUST contain a **BpmException** ([2.2.4.61](#)).

2.2.2.1.2 Full List of Possible Error Codes

In the event of an application error, the server (2) MUST return one of these values in the **ErrorCode** element of the **BpmException** ([2.2.4.61](#)), as specified in section [2.2.2.1.1](#).

The protocol client MUST NOT perform any logical operation on the value of the **ErrorCode**, unless it appears in section [2.2.2.1.3](#) or is explicitly specified for a message in section [3.1.4](#).

Error code	Description
AnnotationDeleteNotEnabled	Deletion of scorecard annotations is not enabled.
AnnotationNotEnabled	Scorecard annotations are not enabled.
BIMonitoringApplicationProxyNotFound	The server (2) is not configured properly or is not functioning correctly.
BIMonitoringApplicationProxyThreadAborted	The request has timed out or has been aborted.
BIMonitoringApplicationUnavailable	The server (2) is not configured properly or is not functioning correctly.
CannotGetWindowsIdentity	The server (2) is not configured properly or is not functioning correctly.
CannotGetWindowsIdentityForNonWindowsClaim	The server (2) cannot locate credentials for the user.
CannotPublishReadOnlyElement	The publish event of a read only element was aborted.

Error code	Description
CreateReturnedNull	The server (2) is not configured properly or is not functioning correctly.
DatabaseConnectionFailed	The server (2) is not configured properly or is not functioning correctly.
DataSourceConnectionFailed	See section 2.2.2.1.3 .
DataSourceConnectionUnsupported	See section 2.2.2.1.3 .
DataSourceCubeNotFound	The user does not have access to the cube specified by a DataSource (section 2.2.4.85) or the cube does not exist
DataSourceDatabaseNotFound	See section 2.2.2.1.3 .
DataSourceHostNotFound	See section 2.2.2.1.3 .
DataSourceNotRegistered	The server (2) is not configured properly or is not functioning correctly.
DataSourceProviderMessage	An error occurred in a data source.
ErrorCode_InvalidNameInfo	An attribute of a NameInfo (section 2.2.4.149) is invalid.
ExtInvalidSetting	A value for setting on the server (2) is invalid.
FCOCreateFailed	See section 2.2.2.1.3 .
FCOCreateFailedListAccess	See section 2.2.2.1.3 .
FCOCreateFailedListType	See section 2.2.2.1.3 .
FCOCreateFailedNameCollision	See section 2.2.2.1.3 .
FCODeleteFailed	See section 2.2.2.1.3 .
FCODeleteFailedListAccess	See section 2.2.2.1.3 .
FCOReadFailed	See section 2.2.2.1.3 .
FCOReadFailedListAccess	See section 2.2.2.1.3 .
FCOUpdateFailed	See section 2.2.2.1.3 .
FCOUpdateFailedListAccess	See section 2.2.2.1.3 .
FCOUpdateFailedListType	See section 2.2.2.1.3 .
FCOUpdateFailedNameCollision	See section 2.2.2.1.3 .
ImpersonationLoginFailure	The shared account credentials are not available.
ImportAsKpisException	An error occurred while importing a KPI from Analysis Services .
IncompatibleSiteDomain	The server (2) is not configured properly or is

Error code	Description
	not functioning correctly.
InvalidAdomdDataSource	An attribute of an Analysis Services DataSource (section 2.2.4.85) is not valid.
InvalidAliasName	The AliasName attribute of a NameInfo (section 2.2.4.13) is invalid.
InvalidAnnotation	An attribute of an Annotation (section 2.2.4.18) is invalid.
InvalidBpmPropertyHyperlink	A FirstClassElement (section 2.2.4.99) contains an invalid hyperlink property
InvalidBpmPropertyList	An attribute of a BpmPropertyList (section 2.2.4.69) is invalid.
InvalidBpmPropertyText	An attribute of a BpmPropertyText (section 2.2.4.72) is invalid.
InvalidBuiltinIndicatorOperation	See section 2.2.2.1.3 .
InvalidCategoryName	See section 2.2.2.1.3 .
InvalidCharacters	The UniqueName of a BpmProperty (section 2.2.4.62) contains invalid characters.
InvalidComment	An attribute of an Comment (section 2.2.4.76) is invalid
InvalidConnectionString	Unable to connect to an Analysis Services data source.
InvalidDataSource	See section 2.2.2.1.3 .
InvalidDefaultMemberName	The DefaultMemberName attribute of a Dimension (section 2.2.4.90) is invalid.
InvalidElement	See section 2.2.2.1.3 .
InvalidElementField	See section 2.2.2.1.3 .
InvalidEndPoint	An attribute of an EndPoint (section 2.2.4.95) is invalid.
InvalidFirstClassElementField	See section 2.2.2.1.3 .
InvalidId	A KPI or scorecard is missing or not available to the current user .
InvalidIndicator	See section 2.2.2.1.3 .
InvalidIndicatorBand	See section 2.2.2.1.3 .
InvalidItemType	See section 2.2.2.1.3 .
InvalidKpi	See section 2.2.2.1.3 .
InvalidKpiMeasure	An attribute of a KPIMeasure (section 2.2.4.129) is invalid.

Error code	Description
InvalidMember	An attribute of a Member (section 2.2.4.134) is invalid.
InvalidNamedSet	An attribute of a NamedSet (section 2.2.4.147) is invalid.
InvalidNamedSetSetting	A named set expression is invalid.
InvalidObject	See section 2.2.2.1.3 .
InvalidOverrideFormatProperties	An attribute of a KpiNumberFormatProperties (section 2.2.4.130) is invalid.
InvalidPermission	See section 2.2.2.1.3 .
InvalidPermissionAdmin	See section 2.2.2.1.3 .
InvalidQueryChildMembers	The specified member (3) name is invalid.
InvalidQueryDimensionRootMembers	The specified dimension (1) name is invalid.
InvalidReportView	See section 2.2.2.1.3 .
InvalidReportViewCubeName	The cube name in an MDX query is not equal to the cube specified in the Analysis Services DataSource (section 2.2.4.85) used to run the query.
InvalidSetting	See section 2.2.2.1.3 .
InvalidStatusFilterBandIndex	The BandIndex attribute of a StatusFilter (section 2.2.4.167) is invalid.
InvalidTextLength	A string attribute is null, empty or exceeds its specified maximum length.
InvalidTimeIntelligenceConfiguration	The time intelligence configuration of a data source (1) is invalid.
InvalidTimeIntelligenceFormula	A time intelligence expression is invalid.
InvalidTimeIntelligenceSetting	An attribute of a TimeIntelligenceDataSource (2.2.4.171), TimeIntelligenceFormula (2.2.4.173), TimeIntelligenceLevelBinding (2.2.4.174), or TimeIntelligenceMdxSettings (2.2.4.175) is invalid.
InvalidUrl	The server (2) is not configured properly or is not functioning correctly.
InvalidVersion	An attribute of a ElementVersion (section 2.2.4.92) is invalid
MissingConnectionString	The server (2) is not configured properly or is not functioning correctly.
NewSetting	An attempt was made to update a non-existent setting.

Error code	Description
NotAParaterizableControl	The server (2) is not configured properly or is not functioning correctly.
NotTrustedLocation	See section 2.2.2.1.3
OperationContextNull	The server (2) is not configured properly or is not functioning correctly.
ParameterDataProviderNotRegistered	The parameter data provider is not registered.
QueryTimeout	A timeout occurred while querying a data source (1).
RepositoryLocationAbsoluteUrl	See section 2.2.2.1.3 .
RepositoryLocationEmpty	See section 2.2.2.1.3 .
RepositoryLocationUrlLength	See section 2.2.2.1.3 .
SharedAccountMisconfigured	The shared account credentials are not configured correctly.
TimeIntelligenceNotConfigured	A DataSource is not configured for time intelligence.
TimeIntelligenceNotSupported	A data source (1) does not support time intelligence.
UnableToLoadCustomDataSource	The server (2) is not configured properly or is not functioning correctly.
UnableToLoadCustomParameterDataProvider	The server (2) is not configured properly or is not functioning correctly.
UnableToLoadCustomViewTransform	The server (2) is not configured properly or is not functioning correctly.
UnableToLoadFCODao	The server (2) is not configured properly or is not functioning correctly.
Unknown	See section 2.2.2.1.3 .

2.2.2.1.3 Common List of Error Codes

In the event of an application error, these values are commonly returned by the server (2) in the **ErrorCode** element of the **BpmException** complex type ([2.2.4.61](#)), as specified in section [2.2.2.1.1](#). The protocol client MAY perform logical operations on these values of the **ErrorCode** element.

Error code	Description
DataSourceConnectionFailed	A connection to the data source (1) could not be established.
DatabaseConnectionNotOpen	The connection to the data source (1) has been lost.
DataSourceConnectionUnsupported	The host server (2) defined by the data source (1) is not a supported server (2), or the server (2) refused the connection.

Error code	Description
DataSourceDatabaseNotFound	A connection to the database defined by the data source (1) could not be established.
DataSourceHostNotFound	A connection to the host server (2) defined by the data source (1) could not be established. This indicates a network or security issue.
FCOCreateFailed	There are inadequate permissions to create this object.
FCOCreateFailedListAccess	The content store<1> containing this object no longer exists. The object cannot be created.
FCOCreateFailedListType	The object cannot be created<2>.
FCOCreateFailedNameCollision	A data source (1) with the requested name already exists. Choose a different name.
FCODeleteFailed	The content store<3> containing this object no longer exists, there are inadequate permissions to view the content store<4> or the object has already been deleted.
FCODeleteFailedListAccess	There are inadequate permissions to delete this object. The object cannot be deleted.
FCOReadFailed	There are inadequate permissions to read this object or it cannot be read.
FCOReadFailedListAccess	The content store<5> containing this object no longer exists or there are inadequate permissions to view it.
FCOUpdateFailed	An update of this object failed.
FCOUpdateFailedListAccess	The content store<6> containing this object no longer exists or there are inadequate permissions to view it. The object cannot be updated.
FCOUpdateFailedListType	The content store<7> containing this object does not support the type of object being updated. The object cannot be updated.
FCOUpdateFailedNameCollision	An update this object failed because of a name collision.
InvalidBuiltinIndicatorOperation	Current operation on the indicator cannot be finished because the indicator's URL is invalid.
InvalidCategoryName	Current operation on the object cannot be finished because the object's containing folder is invalid.
InvalidDataSource	Current operation on the data source (1) cannot be finished because the data source (1) has failed validation.
InvalidElement	Current operation on the Element cannot be finished because the Element has failed basic validation.
InvalidElementField	Current operation on the Element cannot be finished because the Element has an invalid identifier.
InvalidFirstClassElementField	Current operation on the object cannot be finished because some of the object's data fields are invalid.

Error code	Description
InvalidIndicator	Current operation on the indicator cannot be finished because the indicator has failed validation.
InvalidIndicatorBand	Current operation on the indicator cannot be finished because the indicator has failed validation.
InvalidItemType	Current operation on the object cannot be finished because the object's corresponding SharePoint item does not have the expected content type.
InvalidKpi	Current operation on the KPI cannot be finished because the KPI has failed validation.
InvalidObject	Current operation on the Element cannot be finished because the Element has failed validation.
InvalidPermission	The user does not have sufficient permissions to complete the request.
InvalidPermissionAdmin	The user does not have sufficient administrative permissions to complete the request.
InvalidReportView	Current operation on the report view cannot be finished because the report view has failed validation.
InvalidSetting	Current operation on the object cannot be finished because some of the object's UI appearance data fields are invalid.
NotTrustedLocation	The location of the data source (1) or object is not configured as trusted.
RepositoryLocationEmpty	The URL address supplied in the RepositoryLocation (section 2.2.4.161) contains the empty string.
RepositoryLocationUrlLength	The URL address supplied in the RepositoryLocation exceeds the maximum length of 2048 characters.
RepositoryLocationAbsoluteUrl	The URL address supplied in the RepositoryLocation is absolute, when it MUST be relative, as specified in [RFC1808] .
Unknown	An unexpected error occurred. An error number is included in the message text.

2.2.3 Elements

This specification does not define any common XML schema element definitions.

2.2.4 Complex Types

The following table summarizes the set of common XML schema complex type definitions defined by this specification. XML schema complex type definitions that are specific to a particular operation are described with the operation.

Complex type	Description
AddAllMembersSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add all members, at the level specified by

Complex type	Description
	Name (see section 2.2.4.165), to a MemberSet (see section 2.2.4.144).
AddCalcMemberSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add a calculated member (3), specified by Name (see section 2.2.4.165), to a MemberSet (see section 2.2.4.144).
AddChildrenSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add child members (3), of the member (3) specified by Name (see section 2.2.4.165), to a MemberSet (see section 2.2.4.144).
AddDefaultMemberSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add the default member to a MemberSet (see section 2.2.4.144).
AddDescendantsLeavesSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add leaf descendant members (3), of the member (3) specified by Name (see section 2.2.4.165), to a MemberSet (see section 2.2.4.144).
AddDescendantsSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add descendant members (3), at the level specified by LevelName to the member (3) specified by Name (see section 2.2.4.165), to a MemberSet (see section 2.2.4.144).
AddDescendantsSubtreeSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add descendant members (3), from all levels subordinate to the member specified by Name (see section 2.2.4.165), to a MemberSet (see section 2.2.4.144).
AddFilterSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add a value filter set operation to a MemberSet (see section 2.2.4.144).
AddFilterTopBottomSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add a top or bottom filter set operation to a MemberSet (see section 2.2.4.144).
AddMemberSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add a member (3), specified by Name (see section 2.2.4.165), to a MemberSet (see section 2.2.4.144).
AddNamedSetSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add a named set, specified by Name (see section 2.2.4.165), to a MemberSet (see section 2.2.4.144).
AddParentSiblingsSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to add the parent's siblings (members (3)), of the member (3) specified by Name (see section 2.2.4.165), to a MemberSet (see section 2.2.4.144).
AliasInfo	The AliasInfo complex type maps a KpiMeasure complex type (section 2.2.4.129) to a string. This mapping defines an alias used to simplify the display, and the definition of formulas used in calculated metrics. The format MUST be as follows:
AnalyticBaseReportViewData	The AnalyticBaseReportViewData is a complex type that contains the base report view details for analytic reports.

Complex type	Description
AnalyticChartLegend	The AnalyticChartLegend complex type specifies a chart legend.
AnalyticChartReportView	The AnalyticChartReportView is a complex type that contains the chart type report view details for analytic reports.
AnalyticGridReportView	The AnalyticGridReportView complex type defines how analytic grid reports are displayed to users.
Annotation	The Annotation complex type associates a collection of comments to a cell in a particular slice of a scorecard. An annotation is created using CreateAnnotation operation (section 3.1.4.1), and updated using the UpdateAnnotation operation (section 3.1.4.70).
AnnotationComment	This complex type specifies a comment for an Annotation (see section 2.2.4.18). This type extends Comment type (see section 2.2.4.76).
ArrayOfAliasInfo	This complex type specifies an array of AliasInfo complex types (see section 2.2.4.13).
ArrayOfAnnotationComment	The ArrayOfAnnotationComment complex type specifies an array of AnnotationComment elements (see section 2.2.4.19).
ArrayOfAxis	A collection of axes used in a QueryState object (see section 2.2.4.158).
ArrayOfBpmProperty	The ArrayOfBpmProperty complex type specifies an array of BpmProperty elements (see section 2.2.4.62).
ArrayOfBpmPropertyListItem	The ArrayOfBpmPropertyListItem complex type specifies an array of items in a list property.
ArrayOfChoice1	The ArrayOfChoice1 complex type specifies an array of property values. The type of the element in the array MUST be one of decimal , ArrayOfMember (section 2.2.4.45), ArrayOfMemberTransform (section 2.2.4.46), dateTime , string , double , guid , char , or int .
ArrayOfComment	The ArrayOfComment complex type specifies an array of comments.
ArrayOfConfiguredView	The ArrayOfConfiguredView complex type specifies an array of view definitions for a scorecard.
ArrayOfDashboardElement	The ArrayOfDashboardElement complex type specifies an array of DashboardElement (see section 2.2.4.80).
ArrayOfDataColumnMapping	The ArrayOfDataColumnMapping complex type specifies an array of DataColumnMapping (see section 2.2.4.84).
ArrayOfDecimal	The ArrayOfDecimal complex type specifies an array of Decimal .
ArrayOfDefaultDimensionSetting	The ArrayOfDefaultDimensionSetting complex type specifies an array of DefaultDimensionSetting (see section 2.2.4.87).
ArrayOfDimension	The ArrayOfDimension complex type specifies an array of dimension (1) elements.
ArrayOfEndPoint	The ArrayOfEndPoint complex type specifies an array of connection termination points for a consumer Web Part such as a report view or a scorecard.
ArrayOfFirstClassElement	The ArrayOfFirstClassElement complex type specifies an array of first-


Complex type	Description
	class objects.
ArrayOfGridCell	The ArrayOfGridCell complex type specifies an array of cells used by a grid view such as the scorecard view (section 2.2.4.121).
ArrayOfGridDisplayElement	An array of elements for a scorecard cell.
ArrayOfGridHeaderItem	The ArrayOfGridHeaderItem complex type specifies an array of headers for a scorecard.
ArrayOfGridViewTransformReference	The ArrayOfGridViewTransformReference complex type specifies an array of references to a grid view transform.
ArrayOfHierarchy	The ArrayOfHierarchy complex type specifies an array of hierarchy values for a dimension (1).
ArrayOfIndicatorBand	The ArrayOfIndicatorBand complex type specifies an array of indicator bands.
ArrayOfKpi	The ArrayOfKpi complex type specifies an array of Kpi complex types (section 2.2.4.128) for a scorecard.
ArrayOfKpiMeasure	The ArrayOfKpiMeasure complex type specifies an array of KpiMeasure complex types (section 2.2.4.129).
ArrayOfLevel	The ArrayOfLevel complex type defines an array of Level (section 2.2.4.131) complex type.
ArrayOfMeasure	The ArrayOfMeasure complex type defines an array of Measure (section 2.2.4.133) complex type.
ArrayOfMember	The ArrayOfMember complex type defines an array of Member (section 2.2.4.134) complex type.
ArrayOfMemberTransform	The ArrayOfMemberTransform complex type defines an array of MemberTransform (section 2.2.4.146) complex type.
ArrayOfNamedSet	The ArrayOfNamedSet complex type defines an array of NamedSet (section 2.2.4.147) complex type.
ArrayOfNameInfo	The ArrayOfNameInfo complex type <8> defines an array of NameInfo complex types (section 2.2.4.149).
ArrayOfParameter	A collection of parameters used in an analytic query .
ArrayOfParameterDefinition	The ArrayOfParameterDefinition complex type defines an array of ParameterDefinition (section 2.2.4.155) complex type.
ArrayOfParameterMapping	The ArrayOfParameterMapping complex type defines an array of ParameterMapping (section 2.2.4.156) complex type.
ArrayOfPropertyBag	The ArrayOfPropertyBag complex type defines an array of PropertyBag (section 2.2.4.158) elements.
ArrayOfSetOperation	The ArrayOfSetOperation complex type specifies an array of SetOperation elements (see section 2.2.4.165)
ArrayOfString	The ArrayOfString complex type specifies an array of string.

Complex type	Description
ArrayOfTarget	The ArrayOfTarget complex type specifies an array of Target (section 2.2.4.170) complex types.
ArrayOfTimeIntelligenceDataSource	A collection of time intelligence data source reference used in time intelligence parameter definitions.
ArrayOfTimeIntelligenceFormula	A collection of time intelligence parameter formulas.
ArrayOfTimeIntelligenceLevelBinding	The ArrayOfTimeIntelligenceLevelBinding complex type specifies an array of time intelligence binding elements.
Axis	The Axis complex type specifies information about an axis in a query result.
Banding	The Banding complex type represents the banding settings of the KPI target .
BpmException	The BpmException complex type contains the details of a server (2) alert.
BpmProperty	This BpmProperty complex type is the abstract base type for BpmPropertyDate , BpmPropertyDecimal , BpmPropertyHyperlink , BpmPropertyHyperlink2 , BpmPropertyLinkBase , BpmPropertyList , BpmPropertyListItem , BpmPropertyLongText , BpmPropertyText and BpmPropertyUser .
BpmPropertyBool	The BpmPropertyBool complex type defines a Boolean property. It extends the BpmProperty (section 2.2.4.62) type.
BpmPropertyDate	The BpmPropertyDate complex type defines a Date property. It extends the BpmProperty (section 2.2.4.62) type.
BpmPropertyDecimal	The BpmPropertyDecimal complex type defines a Decimal property. It extends the BpmProperty (section 2.2.4.62) type.
BpmPropertyHyperlink	This complex type defines a Hyperlink property. This type extends BpmPropertyLinkBase (section 2.2.4.68). This type is used to specify Hyperlinks as custom properties for types that extend FirstClassElement (section 2.2.4.99).
BpmPropertyHyperlink2	The BpmPropertyHyperlink2 complex type defines a Hyperlink property. This type extends BpmPropertyLinkBase (section 2.2.4.68). This type is used to specify Hyperlinks as part of annotations for types that extend FirstClassElement complex type (section 2.2.4.99).
BpmPropertyLinkBase	The BpmPropertyLinkBase complex type defines a Hyperlink property. It extends the BpmProperty (section 2.2.4.62) type.
BpmPropertyList	The BpmPropertyList complex type specifies zero, or one item of the ArrayOfBpmPropertyListItem complex type (section 2.2.4.24). It extends the BpmProperty complex type (section 2.2.4.62).
BpmPropertyListItem	The BpmPropertyListItem complex type specifies a name-value pair.
BpmPropertyLongText	This complex type defines a Long Text property. The type extends BpmProperty (section 2.2.4.62).


Complex type	Description
BpmPropertyText	This complex type defines a Text property. The type extends BpmProperty (section 2.2.4.62).
BpmPropertyUser	This complex type defines a User property. The type extends BpmProperty (section 2.2.4.62).
CalculatedFormulaInfo	This complex type specifies a calculated formula in a KpiMeasure (section 2.2.4.129). This type is used to specify calculations as part of a KPI's calculated metric.
CalculatedMember	Represents an OLAP calculated member in a Dimension complex type (section 2.2.4.90).<9>
Comment	This complex type represents a comment to be associated with a data entity. This class is the base class for AnnotationComment (section 2.2.4.19).
ConfiguredView	This complex type specifies the scorecard view and configuration settings of how the scorecard displays and what end user actions are allowed. The protocol client that renders the scorecard MUST use this configuration when displaying it.
Cube	The Cube complex type specifies the structure of a cube. It extends the complex type NameInfo complex type(section 2.2.4.149).
Dashboard	The Dashboard complex type defines a dashboard. It specifies the layout and content of the pages in the dashboard and, if the dashboard has been deployed, its deployment location. The Dashboard complex type extends the FirstClassElement type (section 2.2.4.99).
DashboardElement	The DashboardElement complex type specifies the parts of a Dashboard (section 2.2.4.79) that have width and height. The DashboardElement complex type extends the SecondClassElement type (section 2.2.4.163) and is the base type for DashboardElementContainer (section 2.2.4.81) and DashboardItem (section 2.2.4.83).
DashboardElementContainer	The DashboardElementContainer complex type specifies a group of DashboardElement complex types (section 2.2.4.80) that are displayed vertically or horizontally. Each dashboard page is specified by a DashboardElementContainer . Each zone on a dashboard page is specified by a DashboardElementContainer . The DashboardElementContainer complex type extends the DashboardElement .
DashboardElementSize	This complex type specifies the width or height of a DashboardElement (section 2.2.4.80).
DashboardItem	The DashboardItem complex type specifies a single report , scorecard, or filter on a dashboard page. DashboardItem extends the DashboardElement (section 2.2.4.80).
DataColumnMapping	The DataColumnMapping complex type specifies dimensional mapping information for a column of data.

Complex type	Description
DataSource	The DataSource complex type specifies a connection to an external data provider.
DataTableMapping	The DataTableMapping complex type specifies how data from tabular data sources is mapped to multidimensional data.
DefaultDimensionSetting	Specifies a default set of members in a dimension (1). It extends the Dimension (see section 2.2.4.90) type.
DictionaryWrapperOfStringGridCell	This complex type specifies a collection of ArrayOfGridCells (see section 2.2.4.35) with associated string keys.
DictionaryWrapperOfStringPropertyBag	This complex type specifies a collection of ArrayOfPropertyBags with associated string keys.
Dimension	The Dimension complex type specifies the structure of a dimension (1). It extends the complex type NameInfo (section 2.2.4.149).
Element	This abstract class specifies basic metadata about an item. This class is the base class for FirstClassElement and SecondClassElement .
ElementVersion	This complex type specifies the version information used to distinguish different instances of a FirstClassElement .
EliminateDescendantsSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to eliminate descendant members (3), of the member (3) specified by Name (see section 2.2.4.165), from a MemberSet (see section 2.2.4.144).
EliminateMemberSetOp	This complex type extends the SetOperation (section 2.2.4.165) type. It defines an operation to eliminate a member (3), specified by Name (see section 2.2.4.165), from a MemberSet (see section 2.2.4.144).
EndPoint	This complex type defines the receiving end of a connection between a Web Part that provides parameter values such as a filter or a scorecard, and a Web Part that consumes parameter values, such as a report view or a scorecard.
ExcelDataSet	Specifies the Excel workbook ([MS-XLS]) data for an ExcelWorkbook data source.
ExcelServicesData	Describes an Excel Services ([MS-ESPI]) data connection used by Excel Services data sources and Excel Services reports.
Filter	The Filter complex type specifies a filter.
FirstClassElement	The FirstClassElement complex type is an abstract class that represents an object that is versionable. This is the base class for the complex types Dashboard (section 2.2.4.79), DataSource (section 2.2.4.85), Scorecard (section 2.2.4.162), ReportView (section 2.2.4.160), Kpi (section 2.2.4.128) and Indicator (section 2.2.4.125).
GridCell	Specifies a single cell used by the scorecard grid view and the analytic grid view. The following Unified Modeling Language (UML) class diagram shows the GridCell and its relationship with other classes.

Complex type	Description
	<pre> classDiagram class GridCell { +FormatInfo : GridFormatInfo +DisplayElements +ActualValue : decimal +Value : decimal +Score : decimal +BestChildScore : decimal +WorstChildScore : decimal +Weight : decimal +InBand : int +ValueSource : ValueSources +Properties : PropertyBag +CellAnnotation : Annotation +IndicatorLocation : RepositoryLocation +IsValueInError : bool +IsValidScore : bool +IsRollupScore : bool +HasAnnotation : bool } class GridDisplayElement { +Text : string +Status : GridCellElementStatus +TooltipText : string } class GridFormatInfo { +FontInfo +ForeColor +BackColor +TextWrap +VerticalAlign +HorizontalAlign } class GridFontInfo { +FamilyName : string +SizeInPoints : float +Bold +Italic +Underline +Strikeout } GridCell o-- "*" GridDisplayElement : +DisplayElements GridCell ..> GridFormatInfo GridFormatInfo ..> GridFontInfo </pre> <p>Figure 2: GridCell in relation to other classes</p>
GridCellSet	This class specifies the cells used to represent a scorecard or analytic grid. The representation is based on a two dimensional array of GridCell elements indexed by objects of type GridHeaderItem .
GridColor	This class represents the grid color for the GridCell contents.
GridDisplayElement	Specifies an element in a scorecard cell. This is a base class for the following complex types: GridDisplayElementNumber , GridDisplayElementIndicator , GridDisplayElementText , GridDisplayElementHyperLink . Also see following diagram:

Complex type	Description
	 <p>Figure 3: GridDisplayElement</p>
GridDisplayElementActual	Specifies the GridDisplayElement of a KPI's actual value in a scorecard cell. Inherits from the GridDisplayElementNumber .
GridDisplayElementAggregation	Specifies the GridDisplayElement of an aggregated value in a scorecard cell. Inherits from the GridDisplayElementNumber .
GridDisplayElementHyperLink	Specifies the GridDisplayElement of a KPI's hyperlink property in a cell. Inherits from the GridDisplayElement .
GridDisplayElementIndicator	Specifies the image of an indicator for the GridDisplayElement in a scorecard cell. Inherits from the GridDisplayElement .
GridDisplayElementIndicator Text	Specifies the descriptive name of an indicator for the GridDisplayElement in a scorecard cell. Descriptive name of the IndicatorBand is the ToolTip property of the IndicatorBand , for example: "off target"

Complex type	Description
GridDisplayElementNumber	Specifies a numeric GridDisplayElement in a scorecard cell. This is a base class for the following complex types GridDisplayElementsActual , GridDisplayElementTarget , GridDisplayElementScore , GridDisplayElementVariance
GridDisplayElementScore	Specifies the GridDisplayElement of the KPI target's score in a scorecard cell. Inherits from the GridDisplayElementNumber.
GridDisplayElementTarget	Specifies the GridDisplayElement of a KPI's target value in a scorecard cell. Inherits from the GridDisplayElementNumber.
GridDisplayElementText	Specifies the GridDisplayElement of a text value in a scorecard cell. Inherits from the GridDisplayElement.
GridDisplayElementVariance	Specifies the GridDisplayElement of a KPI target's variance value in a scorecard cell. Inherits from the GridDisplayElementNumber.
GridFontInfo	This class represents the font display options for the GridCell contents.
GridFormatInfo	This class represents the display format settings for the GridCell contents.
GridHeaderItem	The GridHeaderItem complex type specifies the header that represents a row or a column node in a scorecard.
GridIndicatorSettings	Defines the settings for the Indicator in the Target field.
GridScoreSettings	Defines the settings for the score in the Target field.
GridTargetSettings	Defines the display settings for the Target column.
GridVarianceSettings	Defines the settings for the variance in the Target column.
GridViewData	<p>The GridViewData complex type specifies the data structure that represents the scorecard view. The following diagram illustrates the scorecard view representation:</p>

Complex type	Description																		
	<p>Figure 4: GridViewData</p> <p>The GridViewData is mainly composed of two tree data structures representing all the row and column headers and a two dimensional array representing every possible interception between elements of those two trees.</p> <p>The row and column header trees MUST be accessed by the properties RootRowHeader and RootColumnHeader respectively. The two dimensional array MUST be accessed by the Cells property.</p>																		
<p>GridViewDefinition</p>	<p>The GridViewDefinition complex type specifies the definition of a grid-based scorecard view. The following picture illustrates the role of a GridViewDefinition in a scorecard.</p>  <p>Figure 5: GridViewDefinition</p> <p>The GridViewDefinition contains the tree data structures representing all the row and column headers. The row and column header trees MUST be accessed by the properties RootRowHeader and RootColumnHeader respectively.</p> <table border="1" data-bbox="1128 871 1469 1029"> <thead> <tr> <th></th> <th colspan="2">CY 2003</th> </tr> <tr> <th></th> <th>Actual</th> <th>Target</th> </tr> </thead> <tbody> <tr> <td>InternetOrderQuantity</td> <td></td> <td></td> </tr> <tr> <td>Accessories</td> <td>15,025</td> <td>13,13</td> </tr> <tr> <td>Bikes</td> <td>5,710</td> <td>31,31</td> </tr> <tr> <td>Clothing</td> <td>3,708</td> <td>31,62</td> </tr> </tbody> </table>		CY 2003			Actual	Target	InternetOrderQuantity			Accessories	15,025	13,13	Bikes	5,710	31,31	Clothing	3,708	31,62
	CY 2003																		
	Actual	Target																	
InternetOrderQuantity																			
Accessories	15,025	13,13																	
Bikes	5,710	31,31																	
Clothing	3,708	31,62																	
<p>GridViewTransformReference</p>	<p>The GridViewTransformReference complex type specifies one transform operation to be applied to a GridViewData complex type (section 2.2.4.121) instance.</p>																		
<p>Hierarchy</p>	<p>The Hierarchy complex type specifies a hierarchy. It extends the complex type NameInfo (section 2.2.4.149).</p>																		
<p>Indicator</p>	<p>A set of visualizations that represent how the actual value of a KPI compares against its target value.</p>																		
<p>IndicatorBand</p>	<p>This is a visualization representing one state of an indicator.</p>																		
<p>Item</p>	<p>Represents a key-value pair in a SerializableDictionary (section</p>																		

Complex type	Description
	2.2.4.164).
Kpi	A key performance indicator (KPI) is contained in a scorecard.
KpiMeasure	The KpiMeasure complex type is contained in a KPI.
KpiNumberFormatProperties	Used for custom formatting of KPI measure values.
Level	This complex type specifies a level. It extends the complex type NameInfo (section 2.2.4.149).
MDXParameterDefinition	The MDXParameterDefinition is a complex type that specifies a custom MDX used to retrieve data.
Measure	The Measure complex type specifies a measure. It extends the complex type NameInfo (section 2.2.4.149).
Member	The Member complex type represents an OLAP member in a Dimension complex type (section 2.2.4.90).
MemberList	The MemberList complex type specifies the members (3) of an OLAP hierarchy. This type extends MemberSet complex type (section 2.2.4.144), and can be used with any axis type.
MemberOperation	Represents the basic member operations that can be performed on an OLAP dimension (1) member. MemberOperation abstract type is the base class for MemberOperationAllDescendants , MemberOperationChildren , MemberOperationDescendants , MemberOperationDrillUp , MemberOperationHide and MemberOperationLeafDescendants .
MemberOperationAllDescendants	A MemberOperation complex type (section 2.2.4.136) that represents all descendants of a referred member in the dimension hierarchy . This type extends MemberOperation .
MemberOperationChildren	A MemberOperation that represents all child members of a referred member in a dimension hierarchy. This type extends MemberOperation.
MemberOperationDescendants	A MemberOperation that represents all descendants of a referred member at a specified level in the hierarchy. This type extends MemberOperation.
MemberOperationDrillUp	A MemberOperation that represents the parent of a referred member. This type extends MemberOperation.
MemberOperationHide	A MemberOperation that hides a referred member. This type extends MemberOperation.
MemberOperationLeafDescendants	A MemberOperation that represents all descendants of a referred member that are also leaf members in the dimension hierarchy. This type extends MemberOperation.
MemberParameterDefinition	The MemberParameterDefinition is a complex type that represents a group of members (3) used to retrieve data.
MemberSet	Specifies the properties of a OLAP member hierarchy.
MemberSetFormula	Specifies a collection of operations on the members (3) of a OLAP hierarchy. This type extends MemberSet and can be used with any axis type.

Complex type	Description
MemberTransform	Represents a transform, such as drilldown , applied to a member, hierarchy group or KPI.
NamedSet	An OLAP named set.
NamedSetParameterDefinition	The NamedSetParameterDefinition is a complex type representing a set of members (3) used to retrieve data.
NameInfo	The NameInfo complex type specifies the names and the description of a cube, dimension (1), hierarchy, level, or measure. It is the base type for the complex types Cube (section 2.2.4.78), Dimension (section 2.2.4.90), Hierarchy (section 2.2.4.124), Level (section 2.2.4.131), and Measure (section 2.2.4.133).
NumericFormat	The NumericFormat is a complex type that represents the numeric format setting for an Analysis Services measure numeric value within an analytic grid report.
NumericFormatsHashtable	An array of NumericFormat objects.
OLAPQueryData	Represents an analytic query.
OLAPReportView	The OLAPReportView complex type contains all the state information for an analytic report.
Parameter	Specifies a logical element of an analytic query whose value can be changed independently of the analytic query.
ParameterDefinition	This class represents the non visual portion of the metadata to describe a parameter. This class carries the state necessary to generate a parameter list representing possible connections that can be originated from a first-class element.
ParameterMapping	Provides the mapping information between a ParameterDefinition (section 2.2.4.155) and a DashboardItem (section 2.2.4.83).
PasReportViewData	Contains all the state information for a ProClarity Analytics Server report.
PropertyBag	The PropertyBag complex type MUST contain a pairing of keys and values.
QueryState	An alternate representation of a MDX query that includes the member selections of each axis.
ReportView	The ReportView complex type controls the visual display of data in a dashboard and can be coordinated with other report views using filters. Report views include analytic grids and charts, PivotTable and PivotChart reports, Excel spreadsheets [MS-XLSX] , SQL Server Reporting Services reports, strategy maps , trend charts, web pages, and custom reports.
RepositoryLocation	The RepositoryLocation complex type specifies the location of a FirstClassElement (section 2.2.4.99) stored on the server (2).
Scorecard	This complex type represents a scorecard.
SecondClassElement	This abstract class is the base class for ConfiguredView (section 2.2.4.77), DashboardElement (section 2.2.4.80), and KpiMeasure (section 2.2.4.129).

Complex type	Description
SerializableDictionary	This complex type specifies an ordered collection of elements of complex type MemberSetFormula (section 2.2.4.145), MemberList (section 2.2.4.135), or Member (section 2.2.4.134), with their associated string keys.
SetOperation	This complex type specifies a set operation. It is the abstract base type for AddAllMembersSetOp , AddCalcMemberSetOp , AddChildrenSetOp , AddDefaultMemberSetOp , AddDescendantsLeavesSetOp , AddDescendantsSetOp , AddDescendantsSubtreeSetOp , AddFilterSetOp , AddFilterTopBottomSetOp , AddMemberSetOp , AddNamedSetSetOp , AddParentSiblingsSetOp , EliminateDescendantsSetOp and EliminateMemberSetOp .
SqlReportViewData	The SqlReportViewData complex type contains all the state information for a SQL Reporting Services report.
StatusFilter	This complex type specifies an indicator to be filtered.
StrategyMapViewData	The StrategyMapViewData complex type class specifies metadata information about a strategy map.
StringCollection	The StringCollection complex type specifies a collection of dimension (1) properties.
Target	The target of a KPI used to measure against actual data.
TimeIntelligenceDataSource	A time intelligence data source reference used in time intelligence parameter definitions.
TimeIntelligenceDefinition	The TimeIntelligenceDefinition complex type specifies time intelligence formulas and data sources. It is used in CustomDefinition of the ParameterDefinition complex type (section 2.2.4.155).
TimeIntelligenceFormula	This complex type specifies a time intelligence parameter formula.
TimeIntelligenceLevelBinding	Specifies the mapping of internal cube dimensions (1) to their time aggregation level.
TimeIntelligenceMdxSettings	Specifies how a dimension (1) in an Analysis Services data source maps to a time intelligence filter when running Simple Time Period Specification (STPS) formulas against the data source.
TimeIntelligencePostFormula Definition	This complex type specifies a time intelligence post formula filter definition.
TimeIntelligenceSettings	Specifies additional time intelligence settings for a data source.
Title	This complex type represents a title for an analytic chart.
ToolbarOptions	Contains the configuration settings of the toolbar of a ConfiguredView (section 2.2.4.77).
Tuple	The Tuple complex type <10> represents an ordered collection of one or more Member complex types (section 2.2.4.134) from different dimensions (1). It contains an instance of SerializableDictionary complex type (section 2.2.4.164).
XmlFont	Specifies a set of attributes that define a font.

2.2.4.1 AddAllMembersSetOp

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add all members, at the level specified by **Name** (see section [2.2.4.165](#)), to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddAllMembersSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.2 AddCalcMemberSetOp

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add a calculated member (3), specified by **Name** (see section [2.2.4.165](#)), to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddCalcMemberSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Aggregate" type="xs:boolean"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Caption" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Aggregate: Specifies whether the aggregate function will be used when the member set definition is generated. When the aggregate element is not present, the default value for the aggregate member is set to **TRUE** if the calculated member definition is not yet already aggregated. If the calculated member definition is aggregated, it is set to **FALSE** to avoid double aggregation.

Caption: The display name of the calculated member. This element **MUST** be present.

2.2.4.3 AddChildrenSetOp

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add child members (3), of the member (3) specified by **Name** (see section [2.2.4.165](#)), to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddChildrenSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.4 AddDefaultMemberSetOp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add the default member to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddDefaultMemberSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.5 AddDescendantsLeavesSetOp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add leaf descendant members (3), of the member (3) specified by **Name** (see section [2.2.4.165](#)), to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddDescendantsLeavesSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.6 AddDescendantsSetOp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add descendant members (3), at the level specified by **LevelName** to the member (3) specified by **Name** (see section [2.2.4.165](#)), to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddDescendantsSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="LevelName" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

LevelName: A level name from the hierarchy associated with the **MemberSet** (see section [2.2.4.144](#)). It MUST exist and MUST NOT be empty.

2.2.4.7 AddDescendantsSubtreeSetOp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add descendant members (3), from all levels subordinate to the member specified by **Name** (see section [2.2.4.165](#)), to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddDescendantsSubtreeSetOp"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.8 AddFilterSetOp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add a value filter set operation to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddFilterSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.9 AddFilterTopBottomSetOp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add a top or bottom filter set operation to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddFilterTopBottomSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.10 AddMemberSetOp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add a member (3), specified by **Name** (see section [2.2.4.165](#)), to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddMemberSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.11 AddNamedSetSetOp

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add a named set, specified by **Name** (see section [2.2.4.165](#)), to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddNamedSetSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.12 AddParentSiblingsSetOp

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to add the parent's siblings (members (3)), of the member (3) specified by **Name** (see section [2.2.4.165](#)), to a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="AddParentSiblingsSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.13 AliasInfo

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **AliasInfo** complex type maps a **KpiMeasure** complex type (section [2.2.4.129](#)) to a string. This mapping defines an alias used to simplify the display, and the definition of formulas used in calculated metrics. The format MUST be as follows:

```
<xs:complexType name="AliasInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="AliasCalculationInfo"
      type="tns:KpiMeasure"/>
  </xs:sequence>
  <xs:attribute name="AliasName" type="xs:string"/>
</xs:complexType>
```

AliasCalculationInfo: MUST specify the **KpiMeasure** used in the calculated metric. This element MUST NOT be null and MUST conform to the schema of the **KpiMeasure** complex type.

AliasName: Is the display name of the **AliasCalculationInfo** instance. This value MUST NOT be null and MUST NOT be empty. It MUST be less than or equal to 31 characters in length.

2.2.4.14 AnalyticBaseReportViewData

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **AnalyticBaseReportViewData** is a complex type that contains the base report view details for analytic reports.

```
<xs:complexType name="AnalyticBaseReportViewData"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="NumericFormats"
type="tns:NumericFormatsHashtable"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Font" type="tns:XmlFont"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FontColor" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="BackgroundColor" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

NumericFormats: Numeric format settings for row or column measures of the analytic report as specified in the **NumericFormatsHashtable** (see section [2.2.4.151](#)).

Font: Grid font used for rendering the analytic report and specified by XmlFont (see section [2.2.4.181](#)).

FontColor: The color of the grid font used for rendering the analytic report. The font color is specified by a string. This MUST be one of the following formats:

- "NamedColor:<name>" where:
 - "<name>" is the name of a predefined color, specified by a string. Values MUST be the same as the names of the elements in Color Table, which follows.
 - Example: "NamedColor:Black".
- "ARGBColor:<A>:<R>:<G>:" where:
 - "<A>" is the alpha component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - "<R>" is the red component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - "<G>" is the green component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - "" is the blue component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - Example: "ARGBColor:255:255:255:255".

Member name	Description
ActiveBorder	The system-defined color of the active window's border.
ActiveCaption	The system-defined color of the background of the active window's title bar.
ActiveCaptionText	The system-defined color of the text in the active window's title bar.
AppWorkspace	The system-defined color of the application workspace. The application workspace is the area in a multiple-document view that is

Member name	Description
	not being occupied by documents.
Control	The system-defined face color of a 3-D element.
ControlDark	The system-defined shadow color of a 3-D element. The shadow color is applied to parts of a 3-D element that face away from the light source.
ControlDarkDark	The system-defined color that is the dark shadow color of a 3-D element. The dark shadow color is applied to the parts of a 3-D element that are the darkest color.
ControlLight	The system-defined color that is the light color of a 3-D element. The light color is applied to parts of a 3-D element that face the light source.
ControlLightLight	The system-defined highlight color of a 3-D element. The highlight color is applied to the parts of a 3-D element that are the lightest color.
ControlText	The system-defined color of text in a 3-D element.
Desktop	The system-defined color of the desktop.
GrayText	The system-defined color of dimmed text. Items in a list (1) that are disabled are displayed in dimmed text.
Highlight	The system-defined color of the background of selected items. This includes selected menu items as well as selected text.
HighlightText	The system-defined color of the text of selected items.
HotTrack	The system-defined color used to designate a hot-tracked item. Single-clicking a hot-tracked item runs the item.
InactiveBorder	The system-defined color of an inactive window's border.
InactiveCaption	The system-defined color of the background of an inactive window's title bar.
InactiveCaptionText	The system-defined color of the text in an inactive window's title bar.
Info	The system-defined color of the background of a ToolTip .
InfoText	The system-defined color of the text of a ToolTip.
Menu	The system-defined color of a menu's background.
MenuText	The system-defined color of a menu's text.
ScrollBar	The system-defined color of the background of a scroll bar.
Window	The system-defined color of the background in the client area of a window.
WindowFrame	The system-defined color of a window frame.
WindowText	The system-defined color of the text in the client area of a window.
Transparent	A system-defined color.

Member name	Description
AliceBlue	A system-defined color.
AntiqueWhite	A system-defined color.
Aqua	A system-defined color.
Aquamarine	A system-defined color.
Azure	A system-defined color.
Beige	A system-defined color.
Bisque	A system-defined color.
Black	A system-defined color.
BlanchedAlmond	A system-defined color.
Blue	A system-defined color.
BlueViolet	A system-defined color.
Brown	A system-defined color.
BurlyWood	A system-defined color.
CadetBlue	A system-defined color.
Chartreuse	A system-defined color.
Chocolate	A system-defined color.
Coral	A system-defined color.
CornflowerBlue	A system-defined color.
Cornsilk	A system-defined color.
Crimson	A system-defined color.
Cyan	A system-defined color.
DarkBlue	A system-defined color.
DarkCyan	A system-defined color.
DarkGoldenrod	A system-defined color.
DarkGray	A system-defined color.
DarkGreen	A system-defined color.
DarkKhaki	A system-defined color.
DarkMagenta	A system-defined color.
DarkOliveGreen	A system-defined color.
DarkOrange	A system-defined color.

Member name	Description
DarkOrchid	A system-defined color.
DarkRed	A system-defined color.
DarkSalmon	A system-defined color.
DarkSeaGreen	A system-defined color.
DarkSlateBlue	A system-defined color.
DarkSlateGray	A system-defined color.
DarkTurquoise	A system-defined color.
DarkViolet	A system-defined color.
DeepPink	A system-defined color.
DeepSkyBlue	A system-defined color.
DimGray	A system-defined color.
DodgerBlue	A system-defined color.
Firebrick	A system-defined color.
FloralWhite	A system-defined color.
ForestGreen	A system-defined color.
Fuchsia	A system-defined color.
Gainsboro	A system-defined color.
GhostWhite	A system-defined color.
Gold	A system-defined color.
Goldenrod	A system-defined color.
Gray	A system-defined color.
Green	A system-defined color.
GreenYellow	A system-defined color.
Honeydew	A system-defined color.
HotPink	A system-defined color.
IndianRed	A system-defined color.
Indigo	A system-defined color.
Ivory	A system-defined color.
Khaki	A system-defined color.
Lavender	A system-defined color.

Member name	Description
LavenderBlush	A system-defined color.
LawnGreen	A system-defined color.
LemonChiffon	A system-defined color.
LightBlue	A system-defined color.
LightCoral	A system-defined color.
LightCyan	A system-defined color.
LightGoldenrodYellow	A system-defined color.
LightGray	A system-defined color.
LightGreen	A system-defined color.
LightPink	A system-defined color.
LightSalmon	A system-defined color.
LightSeaGreen	A system-defined color.
LightSkyBlue	A system-defined color.
LightSlateGray	A system-defined color.
LightSteelBlue	A system-defined color.
LightYellow	A system-defined color.
Lime	A system-defined color.
LimeGreen	A system-defined color.
Linen	A system-defined color.
Magenta	A system-defined color.
Maroon	A system-defined color.
MediumAquamarine	A system-defined color.
MediumBlue	A system-defined color.
MediumOrchid	A system-defined color.
MediumPurple	A system-defined color.
MediumSeaGreen	A system-defined color.
MediumSlateBlue	A system-defined color.
MediumSpringGreen	A system-defined color.
MediumTurquoise	A system-defined color.
MediumVioletRed	A system-defined color.

Member name	Description
MidnightBlue	A system-defined color.
MintCream	A system-defined color.
MistyRose	A system-defined color.
Moccasin	A system-defined color.
NavajoWhite	A system-defined color.
Navy	A system-defined color.
OldLace	A system-defined color.
Olive	A system-defined color.
OliveDrab	A system-defined color.
Orange	A system-defined color.
OrangeRed	A system-defined color.
Orchid	A system-defined color.
PaleGoldenrod	A system-defined color.
PaleGreen	A system-defined color.
PaleTurquoise	A system-defined color.
PaleVioletRed	A system-defined color.
PapayaWhip	A system-defined color.
PeachPuff	A system-defined color.
Peru	A system-defined color.
Pink	A system-defined color.
Plum	A system-defined color.
PowderBlue	A system-defined color.
Purple	A system-defined color.
Red	A system-defined color.
RosyBrown	A system-defined color.
RoyalBlue	A system-defined color.
SaddleBrown	A system-defined color.
Salmon	A system-defined color.
SandyBrown	A system-defined color.
SeaGreen	A system-defined color.

Member name	Description
SeaShell	A system-defined color.
Sienna	A system-defined color.
Silver	A system-defined color.
SkyBlue	A system-defined color.
SlateBlue	A system-defined color.
SlateGray	A system-defined color.
Snow	A system-defined color.
SpringGreen	A system-defined color.
SteelBlue	A system-defined color.
Tan	A system-defined color.
Teal	A system-defined color.
Thistle	A system-defined color.
Tomato	A system-defined color.
Turquoise	A system-defined color.
Violet	A system-defined color.
Wheat	A system-defined color.
White	A system-defined color.
WhiteSmoke	A system-defined color.
Yellow	A system-defined color.
YellowGreen	A system-defined color.
ButtonFace	The system-defined face color of a 3-D element.
ButtonHighlight	The system-defined color that is the highlight color of a 3-D element. This color is applied to parts of a 3-D element that face the light source.
ButtonShadow	The system-defined color that is the shadow color of a 3-D element. This color is applied to parts of a 3-D element that face away from the light source.
GradientActiveCaption	The system-defined color of the lightest color in the color gradient of an active window's title bar.
GradientInactiveCaption	The system-defined color of the lightest color in the color gradient of an inactive window's title bar.
MenuBar	The system-defined color of the background of a menu bar.
MenuHighlight	The system-defined color used to highlight menu items when the

Member name	Description
	menu appears as a flat menu.

BackgroundColor: The background color for the grid data values of the analytic report. The font color is specified by a string. This MUST be one of the following formats:

- "NamedColor:<name>" where:
 - "<name>" is the name of a predefined color, specified by a string. Values MUST be the same as the names of the elements in Color Table, which precedes this section.
- "ARGBColor:<A>:<R>:<G>:" where:
 - "<A>" is the alpha component, specified by a string. Values MUST NOT be less than zero and MUST NOT be greater than 255.
 - "<R>" is the red component, specified by a string. Values MUST NOT be less than zero and MUST NOT be greater than 255.
 - "<G>" is the green component, specified by a string. Values MUST NOT be less than zero and MUST NOT be greater than 255.
 - "" is the blue component, specified by a string. Values MUST NOT be less than zero and MUST NOT be greater than 255.

2.2.4.15 AnalyticChartLegend

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **AnalyticChartLegend** complex type specifies a chart legend.

```
<xs:complexType name="AnalyticChartLegend" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="BackColor" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Font" type="tns:XmlFont"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FontColor" type="xs:string"/>
  </xs:sequence>
  <xs:attribute default="true" name="Visible" type="xs:boolean"/>
  <xs:attribute default="false" name="BorderVisible" type="xs:boolean"/>
  <xs:attribute default="Right" name="Location" type="tns:AnalyticLegendLocation"/>
</xs:complexType>
```

BackColor: The background color of the legend, specified by a string. This MUST be present and MUST be one of the following formats:

- "NamedColor:<name>" where:
 - "<name>" is the name of a predefined color, specified by a string. Values MUST be the same as the names of the elements listed in the color table in section [2.2.4.14](#).
- "ARGBColor:<A>:<R>:<G>:" where:
 - "<A>" is the alpha component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.

- "<R>" is the red component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
- "<G>" is the green component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
- "" is the blue component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.

Font: The font of the chart legend as specified in XmlFont (see section [2.2.4.181](#)). This MUST be present.

FontColor: The font color of the chart legend, specified by a string. This MUST be present and MUST be one of the following formats:

- "NamedColor:<name>" where:
 - "<name>" is the name of a predefined color, specified by a string. Values MUST be the same as the names of the elements listed in the color table in section [2.2.4.14](#).
- "ARGBColor:<A>:<R>:<G>:" where:
 - "<A>" is the alpha component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - "<R>" is the red component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - "<G>" is the green component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - "" is the blue component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.

Visible: This attribute MUST be present and MUST be **true** if the chart legend is visible; otherwise, **false**.

BorderVisible: This attribute MUST be present MUST be **true** if the chart legend border is visible; otherwise, **false**.

Location: The location of the chart legend as specified in **AnalyticLegendLocation** (see section [2.2.5.4](#)). This MUST be present and has a default value of "Right".

2.2.4.16 AnalyticChartReportView

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **AnalyticChartReportView** is a complex type that contains the chart type report view details for analytic reports.

```
<xs:complexType name="AnalyticChartReportView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:AnalyticBaseReportViewData">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Title" type="tns:Title"/>
        <xs:element minOccurs="0" maxOccurs="1" name="PlotAreaBackColor" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Legend"
          type="tns:AnalyticChartLegend"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

```

</xs:sequence>
<xs:attribute default="Column" name="ChartType" type="tns:AnalyticChartType"/>
<xs:attribute default="None" name="LineMarkerStyle" type="tns:AnalyticMarkerStyle"/>
<xs:attribute default="true" name="ChartColorVisible" type="xs:boolean"/>
<xs:attribute default="false" name="ChartPointersVisible" type="xs:boolean"/>
<xs:attribute default="2" name="LineWidth" type="xs:int"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

Title: The title for the analytic chart as specified in **Title** complex type (section [2.2.4.178](#)).

PlotAreaBackColor: The plot area background color for the grid data values of the analytic report. The background color is specified by a string. This MUST be one of the following formats:

- "NamedColor:<name>" where:
 - "<name>" is the name of a predefined color, specified by a string. Values MUST be the same as the names of the elements listed in Color Table 1 (see section [2.2.4.14](#)).
- "ARGBColor:<A>:<R>:<G>:" where:
 - "<A>" is the alpha component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - "<R>" is the red component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - "<G>" is the green component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
 - "" is the blue component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.

Legend: The chart legend as specified in **AnalyticChartLegend** complex type (section [2.2.4.15](#)).

ChartType: The type of analytic chart, as specified in **AnalyticChartType** simple type (section [2.2.5.3](#)). This element MUST be present and the default value is of **Column** type.

LineMarkerStyle: The style for the line markers in the analytic chart as specified in **AnalyticMarkerStyle** (section [2.2.5.5](#)). This element MUST be present and the default value is "None".

ChartColorVisible: This attribute MUST be present and MUST be **TRUE** if the analytic chart color is visible; otherwise, the attribute is **FALSE**.

ChartPointersVisible: This attribute MUST be present and MUST be **TRUE** if the pointers of the analytic chart are visible; otherwise, the attribute is **FALSE**.

LineWidth: This element is a deprecated property, and MUST NOT be used.

2.2.4.17 AnalyticGridReportView

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **AnalyticGridReportView** complex type defines how analytic grid reports are displayed to users.

```
<xs:complexType name="AnalyticGridReportView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:AnalyticBaseReportViewData">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="ReportLayout" type="tns:ReportLayout"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ShortenRowLabels" type="xs:boolean"/>
        <xs:element minOccurs="1" maxOccurs="1" name="MaxRowLabelLength" type="xs:int"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ShortenColumnLabels"
type="xs:boolean"/>
        <xs:element minOccurs="1" maxOccurs="1" name="MaxColumnLabelLength" type="xs:int"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

ReportLayout: A **ReportLayout** simple type object (section [2.2.5.40](#)) that specifies the manner in which row and column headers are displayed.

ShortenRowLabels: Specifies whether long row labels are truncated to save space. A value of **TRUE** indicates that long labels will be truncated. A value of **FALSE** indicates that they will not.

MaxRowLabelLength: Specifies the maximum length for row labels. **ShortenRowLabels** MUST be set to **TRUE** for this property to be used.

ShortenColumnLabels: Specifies whether long column labels are truncated to save space. A value of **TRUE** indicates that long labels will be truncated. A value of **FALSE** indicates that they will not.

MaxColumnLabelLength: Specifies the maximum length for column labels. **ShortenColumnLabels** MUST be set to **TRUE** for this property to be used.

2.2.4.18 Annotation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **Annotation** complex type associates a collection of comments to a cell in a particular slice of a scorecard. An annotation is created using **CreateAnnotation** operation (section [3.1.4.1](#)), and updated using the **UpdateAnnotation** operation (section [3.1.4.70](#)).

```
<xs:complexType name="Annotation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Comments"
type="tns:ArrayOfAnnotationComment"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Properties" type="tns:ArrayOfBpmProperty"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Owner" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="LastUpdatedBy" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Slice" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="CreatedOn" type="xs:dateTime"/>
    <xs:element minOccurs="1" maxOccurs="1" name="LastUpdatedOn" type="xs:dateTime"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ScorecardLocation"
type="tns:RepositoryLocation"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ConfiguredViewID"
xmlns:s1="http://microsoft.com/wsd1/types/" type="s1:guid"/>
  </xs:sequence>
</xs:complexType>
```

```

    <xs:element minOccurs="1" maxOccurs="1" name="Guid"
xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CellpathCoordinates" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Version" type="tns:AnnotationVersions"/>
  </xs:sequence>
</xs:complexType>

```

Comments: Specifies the comment collection contained by the annotation. This element **MUST** conform to the schema of the **ArrayOfAnnotationComment** complex type (section [2.2.4.21](#)).

Properties: Specifies the properties of the annotation. This element **MUST** conform to the schema of the **ArrayOfBpmProperty** complex type (section [2.2.4.23](#)).

Owner: Specifies the identity of the person responsible for the creation of the annotation. This element **MUST** be present. The value **MUST NOT** be empty, and **MUST NOT** consist of only whitespace characters.

LastUpdatedBy: Specifies the last person to update the annotation. This element **MUST** be present.

Slice: Specifies an aggregation context of the **PageFilters** element as defined in the **GridViewData** complex type (section [2.2.4.121](#)) corresponding to the cell or cells in the scorecard for which this annotation is applicable. The value **MUST** be a sorted string of page filter member names, where each member name in the string is separated by a comma. The page filter member names are sorted using the current **UI culture**.

CreatedOn: Specifies the **dateTime** at which this annotation instance was created.

LastUpdatedOn: Specifies the **dateTime** at which this annotation was last updated.

ScorecardLocation: Specifies the location of the scorecard referenced by this annotation. This element **MUST** be present. This element **MUST** conform to the schema of the **RepositoryLocation** complex type (section [2.2.4.161](#)).

ConfiguredViewID: Specifies the identity of the **ConfiguredView** complex type (section [2.2.4.77](#)) for this annotation. This element **MUST** be formatted as a **GUID** and its value **MUST NOT** be {000000000000-00000000-000000-00000000}.

Guid: Specifies the identity for this annotation. This element **MUST** be formatted as a GUID and its value **MUST NOT** be {000000000000-00000000-000000-00000000}.

CellpathCoordinates: Specifies the coordinates of the scorecard cell that this annotation is associated with. The value **MUST** be the **MD5** hash of the dimension (1) values of all the headers of a cell, sorted by their dimension (1) names. This value **MUST NOT** be null or empty. The header cells **MUST** conform to the schema of **GridHeaderItem** complex type (section [2.2.4.116](#)). This value for the checked cell in the following example scorecard is calculated as follows:

	All Geographies					
			Oregon		Washington	
	Actual	Target	Actual	Target	Actual	Target
Internet Order Quantity						

	All Geographies					
Accessories	X					
Bikes						
Clothing						

- The column and row headers for the cell are extracted and are used to compute the **CellPathCoordinates** for the cell. The **CellPathCoordinates** is a collection of headers of the cell and is computed as follows:
 1. For each row and column header of the cell its parent path is computed and represented as a collection of headers.
 2. The corresponding path is then reversed and appended to the **CellPathCoordinates**.
 3. The **CellPathCoordinates** for the checked cell is shown in the following table. The **DimensionValue**, **DimensionName** and **DisplayText** values of the **GridHeaderItem** complex type (section [2.2.4.116](#)) for each header cell in the **CellPathCoordinates** are also listed in the table.

GridHeaderItem	DimensionValue	DimensionName	DisplayText
Row Header Parent	"/PerformancePoint/Lists/PerformancePoint Content/10_.000"	"Scorecard_"	"Internet Order Quantity"
Row Header	"[Product].[Category].&[4]"	"Product.Category"	"Accessories"
Column Header Parent's Parent	"[Geography].[State-Province].[All Geographies]"	"Geography.State-Province"	"All Geographies"
Column Header Parent	"[Geography].[State-Province].[All Geographies]"	"Geography.State-Province"	""
Column Header	"Actual"	"Scorecard_Measures_"	"Actual"

- A sorted dictionary containing one entry per element in the **CellPathCoordinates** is then created.
- The sorted dictionary key is the header.DimensionName concatenated with header.Guid. The corresponding value in the dictionary is the header.DimensionValue.
- The dictionary keys MUST be sorted alphabetically in ascending order.
- The string representation of the coordinates of the path is then created by concatenating each of the values in the dictionary. This value for the example is:
 - "[Geography].[State-Province].[All Geographies][Geography].[State-Province].[All Geographies][Product].[Category].&[4]/PerformancePoint/Lists/PerformancePoint Content/10_.000Actual"
- A MD5 hash value (128-bit number) represented as a 32-digit hexadecimal number. The final output is the string "2BB92D0CE8F91E3E5FA5FB402EEE0E5C".

Version: Specifies the product version used to create this annotation. This element MUST conform to the schema of the **AnnotationVersions** simple type (section [2.2.5.6](#)).

2.2.4.19 AnnotationComment

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type specifies a comment for an **Annotation** (see section [2.2.4.18](#)). This type extends **Comment** type (see section [2.2.4.76](#)).

```
<xs:complexType name="AnnotationComment" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:Comment">
      <xs:attribute name="Title" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Title: Specifies the title for the comment. This element MUST be present. The value MUST NOT be empty and MUST NOT consist of only white-space characters.

2.2.4.20 ArrayOfAliasInfo

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type specifies an array of **AliasInfo** complex types (see section [2.2.4.13](#)).

```
<xs:complexType name="ArrayOfAliasInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="AliasInfo" nillable="true"
      type="tns:AliasInfo"/>
  </xs:sequence>
</xs:complexType>
```

AliasInfo: This element MUST NOT be null and MUST conform to the schema of the **AliasInfo** (section [2.2.4.13](#)) complex type.

2.2.4.21 ArrayOfAnnotationComment

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **ArrayOfAnnotationComment** complex type specifies an array of **AnnotationComment** elements (see section [2.2.4.19](#)).

```
<xs:complexType name="ArrayOfAnnotationComment" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="AnnotationComment" nillable="true"
type="tns:AnnotationComment"/>
  </xs:sequence>
</xs:complexType>
```

AnnotationComment: This element MUST NOT be null and MUST conform to the schema of the **AnnotationComment** (section [2.2.4.19](#)) complex type.

2.2.4.22 ArrayOfAxis

Namespace: http://www.microsoft.com/performancepoint/scorecards

A collection of axes used in a **QueryState** object (see section [2.2.4.158](#)).

```
<xs:complexType name="ArrayOfAxis" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Axis" type="tns:Axis"/>
  </xs:sequence>
</xs:complexType>
```

Axis: An **Axis** object (see section [2.2.4.59](#)).

2.2.4.23 ArrayOfBpmProperty

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **ArrayOfBpmProperty** complex type specifies an array of **BpmProperty** elements (see section [2.2.4.62](#)).

```
<xs:complexType name="ArrayOfBpmProperty" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="BpmProperty" nillable="true"
type="tns:BpmProperty"/>
  </xs:sequence>
</xs:complexType>
```

BpmProperty: This element MUST NOT be null and MUST conform to the schema of the **BpmProperty** (section [2.2.4.62](#)) complex type.

2.2.4.24 ArrayOfBpmPropertyListItem

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **ArrayOfBpmPropertyListItem** complex type specifies an array of items in a list property.

```

<xs:complexType name="ArrayOfBpmPropertyListItem"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="BpmPropertyListItem"
nillable="true" type="tns:BpmPropertyListItem"/>
  </xs:sequence>
</xs:complexType>

```

BpmPropertyListItem: This element MUST NOT be null and MUST conform to the schema of the **BpmPropertyListItem** (section [2.2.4.70](#)) complex type.

2.2.4.25 ArrayOfChoice1

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfChoice1** complex type specifies an array of property values. The type of the element in the array MUST be one of **decimal**, **ArrayOfMember** (section [2.2.4.45](#)), **ArrayOfMemberTransform** (section [2.2.4.46](#)), **dateTime**, **string**, **double**, **guid**, **char**, or **int**.

```

<xs:complexType name="ArrayOfChoice1" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element minOccurs="1" maxOccurs="1" name="char"
xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:char"/>
    <xs:element minOccurs="1" maxOccurs="1" name="int" type="xs:int"/>
    <xs:element minOccurs="1" maxOccurs="1" name="double" type="xs:double"/>
    <xs:element minOccurs="1" maxOccurs="1" name="string" nillable="true" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="dateTime" type="xs:dateTime"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ArrayOfMemberTransform" nillable="true"
type="tns:ArrayOfMemberTransform"/>
    <xs:element minOccurs="1" maxOccurs="1" name="guid"
xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ArrayOfString" nillable="true"
type="tns:ArrayOfString"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ArrayOfMember" nillable="true"
type="tns:ArrayOfMember"/>
    <xs:element minOccurs="1" maxOccurs="1" name="decimal" type="xs:decimal"/>
  </xs:choice>
</xs:complexType>

```

char: A character value.

int: An **integer** value.

double: A **double** numeric value.

string: A **string** value and MUST NOT be null.

dateTime: A **dateTime** value.

ArrayOfMemberTransform: This element MUST NOT be null and MUST conform to the schema of the **ArrayOfMemberTransform** (section [2.2.4.46](#)) complex type.

guid: An identity value.

ArrayOfString: This element MUST NOT be null and MUST conform to the schema of the **ArrayOfString** (section [2.2.4.54](#)) complex type.

ArrayOfMember: This element MUST NOT be null and MUST conform to the schema of the ArrayOfMember (section [2.2.4.45](#)) complex type.

decimal: A decimal value.

2.2.4.26 ArrayOfComment

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfComment** complex type specifies an array of comments.

```
<xs:complexType name="ArrayOfComment" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Comment" nillable="true"
      type="tns:Comment"/>
  </xs:sequence>
</xs:complexType>
```

Comment: This element MUST NOT be null and MUST conform to the schema of the **Comment** (section [2.2.4.76](#)) complex type.

2.2.4.27 ArrayOfConfiguredView

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfConfiguredView** complex type specifies an array of view definitions for a scorecard.

```
<xs:complexType name="ArrayOfConfiguredView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="ConfiguredView" nillable="true"
      type="tns:ConfiguredView"/>
  </xs:sequence>
</xs:complexType>
```

ConfiguredView: This element MUST NOT be null and MUST conform to the schema of the **ConfiguredView** (section [2.2.4.77](#)) complex type.

2.2.4.28 ArrayOfDashboardElement

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfDashboardElement** complex type specifies an array of DashboardElement (see section [2.2.4.80](#)).

```
<xs:complexType name="ArrayOfDashboardElement" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DashboardElement" nillable="true"
      type="tns:DashboardElement"/>
  </xs:sequence>
</xs:complexType>
```

DashboardElement: This element MUST NOT be null and MUST conform to the schema of the **DashboardElement** (section [2.2.4.80](#)) complex type.

2.2.4.29 ArrayOfDataColumnMapping

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfDataColumnMapping** complex type specifies an array of **DataColumnMapping** (see section [2.2.4.84](#)).

```
<xs:complexType name="ArrayOfDataColumnMapping" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DataColumnMapping" nillable="true"
type="tns:DataColumnMapping"/>
  </xs:sequence>
</xs:complexType>
```

DataColumnMapping: This element MUST NOT be null and MUST conform to the schema of the **DataColumnMapping** (section [2.2.4.84](#)) complex type.

2.2.4.30 ArrayOfDecimal

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfDecimal** complex type specifies an array of **Decimal**.

```
<xs:complexType name="ArrayOfDecimal" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="decimal" type="xs:decimal"/>
  </xs:sequence>
</xs:complexType>
```

decimal: A valid **Decimal** value.

2.2.4.31 ArrayOfDefaultDimensionSetting

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfDefaultDimensionSetting** complex type specifies an array of **DefaultDimensionSetting** (see section [2.2.4.87](#)).

```
<xs:complexType name="ArrayOfDefaultDimensionSetting"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DefaultDimensionSetting"
nillable="true" type="tns:DefaultDimensionSetting"/>
  </xs:sequence>
</xs:complexType>
```

DefaultDimensionSetting: This element MUST NOT be null and MUST conform to the schema of the **DefaultDimensionSetting** (section [2.2.4.87](#)) complex type.

2.2.4.32 ArrayOfDimension

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfDimension** complex type specifies an array of dimension (1) elements.

```

<xs:complexType name="ArrayOfDimension" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Dimension" nillable="true"
type="tns:Dimension"/>
  </xs:sequence>
</xs:complexType>

```

Dimension: This element MUST NOT be null and MUST conform to the schema of the **Dimension** complex type (section [2.2.4.90](#)).

2.2.4.33 ArrayOfEndPoint

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfEndPoint** complex type specifies an array of connection termination points for a consumer Web Part such as a report view or a scorecard.

```

<xs:complexType name="ArrayOfEndPoint" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="EndPoint" nillable="true"
type="tns:EndPoint"/>
  </xs:sequence>
</xs:complexType>

```

EndPoint: This element MUST NOT be null and MUST conform to the schema of the **EndPoint** (section [2.2.4.95](#)) complex type.

2.2.4.34 ArrayOfFirstClassElement

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfFirstClassElement** complex type specifies an array of first-class objects.

```

<xs:complexType name="ArrayOfFirstClassElement" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="FirstClassElement" nillable="true"
type="tns:FirstClassElement"/>
  </xs:sequence>
</xs:complexType>

```

FirstClassElement: This element MUST NOT be null and MUST conform to the schema of the **FirstClassElement** (section [2.2.4.99](#)) complex type.

2.2.4.35 ArrayOfGridCell

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfGridCell** complex type specifies an array of cells used by a grid view such as the scorecard view (section [2.2.4.121](#)).

```

<xs:complexType name="ArrayOfGridCell" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="GridCell" nillable="true"
type="tns:GridCell"/>
  </xs:sequence>
</xs:complexType>

```

```
</xs:sequence>
</xs:complexType>
```

GridCell: This element MUST NOT be null and MUST conform to the schema of the **GridCell** (section [2.2.4.100](#)) complex type.

2.2.4.36 ArrayOfGridDisplayElement

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

An array of elements for a scorecard cell.

```
<xs:complexType name="ArrayOfGridDisplayElement" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="GridDisplayElement" nillable="true"
      type="tns:GridDisplayElement"/>
  </xs:sequence>
</xs:complexType>
```

GridDisplayElement: This element MUST NOT be null and MUST conform to the schema of the **GridDisplayElement** (section [2.2.4.103](#)) complex type.

2.2.4.37 ArrayOfGridHeaderItem

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfGridHeaderItem** complex type specifies an array of headers for a scorecard.

```
<xs:complexType name="ArrayOfGridHeaderItem" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="GridHeaderItem" nillable="true"
      type="tns:GridHeaderItem"/>
  </xs:sequence>
</xs:complexType>
```

GridHeaderItem: This element MUST NOT be null and MUST conform to the schema of the **GridHeaderItem** (section [2.2.4.116](#)) complex type.

2.2.4.38 ArrayOfGridViewTransformReference

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfGridViewTransformReference** complex type specifies an array of references to a grid view transform.

```
<xs:complexType name="ArrayOfGridViewTransformReference"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="GridViewTransformReference"
      nillable="true" type="tns:GridViewTransformReference"/>
  </xs:sequence>
</xs:complexType>
```


GridViewTransformReference: This element MUST NOT be null and MUST conform to the schema of the **GridViewTransformReference** (section [2.2.4.123](#)) complex type.

2.2.4.39 ArrayOfHierarchy

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfHierarchy** complex type specifies an array of hierarchy values for a dimension (1).

```
<xs:complexType name="ArrayOfHierarchy" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Hierarchy" nillable="true"
      type="tns:Hierarchy"/>
  </xs:sequence>
</xs:complexType>
```

Hierarchy: This element MUST NOT be null and MUST conform to the schema of the **Hierarchy** complex type (section [2.2.4.124](#)).

2.2.4.40 ArrayOfIndicatorBand

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfIndicatorBand** complex type specifies an array of indicator bands.

```
<xs:complexType name="ArrayOfIndicatorBand" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="IndicatorBand" nillable="true"
      type="tns:IndicatorBand"/>
  </xs:sequence>
</xs:complexType>
```

IndicatorBand: This element MUST NOT be null and MUST conform to the schema of the **IndicatorBand** (section [2.2.4.126](#)) complex type.

2.2.4.41 ArrayOfKpi

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfKpi** complex type specifies an array of **Kpi** complex types (section [2.2.4.128](#)) for a scorecard.

```
<xs:complexType name="ArrayOfKpi" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Kpi" nillable="true"
      type="tns:Kpi"/>
  </xs:sequence>
</xs:complexType>
```

Kpi: This element MUST NOT be null, and MUST conform to the schema of the **Kpi**.

2.2.4.42 ArrayOfKpiMeasure

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfKpiMeasure** complex type specifies an array of **KpiMeasure** complex types (section [2.2.4.129](#)).

```
<xs:complexType name="ArrayOfKpiMeasure" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="KpiMeasure" nillable="true"
      type="tns:KpiMeasure"/>
  </xs:sequence>
</xs:complexType>
```

KpiMeasure: This element MUST NOT be null and MUST conform to the schema of the **KpiMeasure**.

2.2.4.43 ArrayOfLevel

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfLevel** complex type defines an array of **Level** (section [2.2.4.131](#)) complex type.

```
<xs:complexType name="ArrayOfLevel" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Level" nillable="true"
      type="tns:Level"/>
  </xs:sequence>
</xs:complexType>
```

Level: This element MUST NOT be null and MUST conform to the schema of the **Level** (section [2.2.4.131](#)) complex type.

2.2.4.44 ArrayOfMeasure

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfMeasure** complex type defines an array of **Measure** (section [2.2.4.133](#)) complex type.

```
<xs:complexType name="ArrayOfMeasure" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Measure" nillable="true"
      type="tns:Measure"/>
  </xs:sequence>
</xs:complexType>
```

Measure: This element MUST NOT be null and MUST conform to the schema of the **Measure** (section [2.2.4.133](#)) complex type.

2.2.4.45 ArrayOfMember

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfMember** complex type defines an array of **Member** (section [2.2.4.134](#)) complex type.

```
<xs:complexType name="ArrayOfMember" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
```

```

    <xs:element minOccurs="0" maxOccurs="unbounded" name="Member" nillable="true"
type="tns:Member"/>
  </xs:sequence>
</xs:complexType>

```

Member: This element MUST NOT be null and MUST conform to the schema of the **Member** (section [2.2.4.134](#)) complex type.

2.2.4.46 ArrayOfMemberTransform

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfMemberTransform** complex type defines an array of **MemberTransform** (section [2.2.4.146](#)) complex type.

```

<xs:complexType name="ArrayOfMemberTransform" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="MemberTransform" nillable="true"
type="tns:MemberTransform"/>
  </xs:sequence>
</xs:complexType>

```

MemberTransform: This element MUST NOT be null and MUST conform to the schema of the **MemberTransform** (section [2.2.4.146](#)) complex type.

2.2.4.47 ArrayOfNamedSet

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfNamedSet** complex type defines an array of **NamedSet** (section [2.2.4.147](#)) complex type.

```

<xs:complexType name="ArrayOfNamedSet" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="NamedSet" nillable="true"
type="tns:NamedSet"/>
  </xs:sequence>
</xs:complexType>

```

NamedSet: This element MUST NOT be null and MUST conform to the schema of the **NamedSet** (section [2.2.4.147](#)) complex type.

2.2.4.48 ArrayOfNameInfo

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfNameInfo** complex type [<11>](#) defines an array of **NameInfo** complex types (section [2.2.4.149](#)).

```

<xs:complexType name="ArrayOfNameInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="NameInfo" nillable="true"
type="tns:NameInfo"/>
  </xs:sequence>

```

```
</xs:complexType>
```

NameInfo: This element MUST NOT be null and MUST conform to the schema of **NameInfo**.

2.2.4.49 ArrayOfParameter

Namespace: http://www.microsoft.com/performancepoint/scorecards

A collection of parameters used in an analytic query.

```
<xs:complexType name="ArrayOfParameter" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Parameter" nillable="true"
      type="tns:Parameter"/>
  </xs:sequence>
</xs:complexType>
```

Parameter: A **Parameter** object (see section [2.2.4.154](#)).

2.2.4.50 ArrayOfParameterDefinition

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **ArrayOfParameterDefinition** complex type defines an array of **ParameterDefinition** (section [2.2.4.155](#)) complex type.

```
<xs:complexType name="ArrayOfParameterDefinition"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="ParameterDefinition"
      nillable="true" type="tns:ParameterDefinition"/>
  </xs:sequence>
</xs:complexType>
```

ParameterDefinition: This element MUST NOT be null and MUST conform to the schema of the **ParameterDefinition** (section [2.2.4.155](#)) complex type.

2.2.4.51 ArrayOfParameterMapping

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **ArrayOfParameterMapping** complex type defines an array of **ParameterMapping** (section [2.2.4.156](#)) complex type.

```
<xs:complexType name="ArrayOfParameterMapping" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="ParameterMapping" nillable="true"
      type="tns:ParameterMapping"/>
  </xs:sequence>
</xs:complexType>
```

ParameterMapping: This element MUST NOT be null and MUST conform to the schema of the **ParameterMapping** (section [2.2.4.156](#)) complex type.

2.2.4.52 ArrayOfPropertyBag

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfPropertyBag** complex type defines an array of **PropertyBag** (section [2.2.4.158](#)) elements.

```
<xs:complexType name="ArrayOfPropertyBag" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="PropertyBag" nillable="true"
      type="tns:PropertyBag"/>
  </xs:sequence>
</xs:complexType>
```

PropertyBag: This element MUST NOT be null and MUST conform to the schema of the **PropertyBag** (section [2.2.4.158](#)) complex type.

2.2.4.53 ArrayOfSetOperation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfSetOperation** complex type specifies an array of **SetOperation** elements (see section [2.2.4.165](#))

```
<xs:complexType name="ArrayOfSetOperation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SetOperation" nillable="true"
      type="tns:SetOperation"/>
  </xs:sequence>
</xs:complexType>
```

SetOperation: This element MUST NOT be null and MUST conform to the schema of the **SetOperation** (section [2.2.4.165](#)) complex type.

2.2.4.54 ArrayOfString

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfString** complex type specifies an array of string.

```
<xs:complexType name="ArrayOfString" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
      type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

string: This element MUST NOT be null and MUST be an **xs:string** ([\[XMLSCHEMA2\]](#) section 3.2.1).

2.2.4.55 ArrayOfTarget

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfTarget** complex type specifies an array of **Target** (section [2.2.4.170](#)) complex types.

```
<xs:complexType name="ArrayOfTarget" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Target" nillable="true"
type="tns:Target"/>
  </xs:sequence>
</xs:complexType>
```

Target: This element MUST NOT be null and MUST conform to the schema of the **Target** (section [2.2.4.170](#)) complex type.

2.2.4.56 ArrayOfTimeIntelligenceDataSource

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A collection of time intelligence data source reference used in time intelligence parameter definitions.

```
<xs:complexType name="ArrayOfTimeIntelligenceDataSource"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="TimeIntelligenceDataSource"
nillable="true" type="tns:TimeIntelligenceDataSource"/>
  </xs:sequence>
</xs:complexType>
```

TimeIntelligenceDataSource: See **TimeIntelligenceDataSource** (section [2.2.4.171](#)).

2.2.4.57 ArrayOfTimeIntelligenceFormula

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A collection of time intelligence parameter formulas.

```
<xs:complexType name="ArrayOfTimeIntelligenceFormula"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="TimeIntelligenceFormula"
nillable="true" type="tns:TimeIntelligenceFormula"/>
  </xs:sequence>
</xs:complexType>
```

TimeIntelligenceFormula: See **TimeIntelligenceFormula** (section [2.2.4.173](#)).

2.2.4.58 ArrayOfTimeIntelligenceLevelBinding

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfTimeIntelligenceLevelBinding** complex type specifies an array of time intelligence binding elements.

```
<xs:complexType name="ArrayOfTimeIntelligenceLevelBinding"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
```

```

    <xs:element minOccurs="0" maxOccurs="unbounded" name="TimeIntelligenceLevelBinding"
nillable="true" type="tns:TimeIntelligenceLevelBinding"/>
  </xs:sequence>
</xs:complexType>

```

TimeIntelligenceLevelBinding: This element MUST NOT be null and MUST conform to the schema of the **TimeIntelligenceLevelBinding** complex type (section [2.2.4.174](#)).

2.2.4.59 Axis

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **Axis** complex type specifies information about an axis in a query result.

```

<xs:complexType name="Axis" mixed="true" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Type" type="tns:AxisType"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FilterEmpty" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="PropertyList" type="tns:StringCollection"/>
    <xs:element minOccurs="1" maxOccurs="1" name="MemberSets"
type="tns:SerializableDictionary"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SortMode" type="tns:SortType"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SortIndex" type="xs:int"/>
    <xs:element minOccurs="0" maxOccurs="1" name="SortTuple" type="tns:Tuple"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SortDescending" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SortPreservePeerGroups" type="xs:boolean"/>
  </xs:sequence>
</xs:complexType>

```

Type: Specifies an **AxisType** simple type (section [2.2.5.7](#)).

FilterEmpty: This value MUST be **TRUE** if the axis is not permitted to use empty values; otherwise, the value is **false**. The default is **false**.

PropertyList: Specifies a **StringCollection** complex type (section [2.2.4.169](#)) of dimension (1) properties. Each value in this **StringCollection** MUST be a valid intrinsic or custom multidimensional expression (MDX) dimension (1) properties.

MemberSets: Specifies a collection of **MemberSet** complex type objects (section [2.2.4.144](#)).

SortMode: Specifies a **SortType** simple type (section [2.2.5.47](#)).

SortIndex: Specifies a column index to sort by.

SortTuple: Specifies a **Tuple** complex type (section [2.2.4.182](#)) to sort by.

SortDescending: This value MUST be **TRUE** if the filter axis MUST be sorted in descending order; otherwise, the value is **FALSE**.

SortPreservePeerGroups: This value MUST be **TRUE** if peer groups MUST be preserved during sorting; otherwise, the value is **FALSE**. Preserving peer groups includes hierarchical relationships and sorting is constrained to a parent's child objects. Alternatively, breaking peer groups ignore hierarchical relationships.

2.2.4.60 Banding

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **Banding** complex type represents the banding settings of the KPI target.

```
<xs:complexType name="Banding" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="CustomBoundary" type="tns:ArrayOfDecimal"/>
  </xs:sequence>
  <xs:attribute name="Type" type="tns:BandType" use="required"/>
  <xs:attribute name="BandValue" type="xs:string"/>
  <xs:attribute name="ActualWorst" type="xs:decimal" use="required"/>
  <xs:attribute name="SpreadMinimum" type="xs:decimal" use="required"/>
  <xs:attribute name="SpreadMaximum" type="xs:decimal" use="required"/>
</xs:complexType>
```

CustomBoundary: The list (1) of boundaries for bands. It does not include the minimum and maximum boundaries.

Type: The type of banding. See **BandType** simple type (section [2.2.5.8](#)) for details.

BandValue: This attribute is reserved and MUST NOT be used.

ActualWorst: The worst value in the scale of actual values.

SpreadMinimum: The minimum boundary for values.

SpreadMaximum: The maximum boundary for values.

2.2.4.61 BpmException

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **BpmException** complex type contains the details of a server (2) alert.

```
<xs:complexType name="BpmException" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="ErrorCode" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="EventLogged" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Message" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

ErrorCode: Identifies the alert type. MUST be one of the values specified in section [2.2.2.1.2](#).

EventLogged: MUST be **true** if the alert was logged by the server (2), **false** otherwise.

Message: A text description of the alert. The text MUST be included. The text MUST NOT be empty. The text MUST be in the language of the UI culture of the session.

2.2.4.62 BpmProperty

Namespace: http://www.microsoft.com/performancepoint/scorecards

This **BpmProperty** complex type is the abstract base type for [BpmPropertyDate](#), [BpmPropertyDecimal](#), [BpmPropertyHyperlink](#), [BpmPropertyHyperlink2](#), [BpmPropertyLinkBase](#), [BpmPropertyList](#), [BpmPropertyListItem](#), [BpmPropertyLongText](#), [BpmPropertyText](#) and [BpmPropertyUser](#).

```
<xs:complexType name="BpmProperty" abstract="true"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="UniqueName" type="xs:string"/>
  <xs:attribute name="DisplayName" type="xs:string"/>
  <xs:attribute name="Description" type="xs:string"/>
  <xs:attribute name="Required" type="xs:boolean" use="required"/>
  <xs:attribute name="Visible" type="xs:boolean" use="required"/>
</xs:complexType>
```

UniqueName: The **UniqueName** attribute MUST be set to a string that is distinct from UniqueNames used for other instances of BpmProperty and derived types. It MUST NOT contain any of the following characters: [] . ` ~ # % & * { } | \ : " / ? < > and the string length MUST be less than 1000 characters.

DisplayName: The **DisplayName** attribute is the string that is provided to the user. It MUST be shorter than 1000 characters.

Description: The **Description** attribute describes the property. It MUST be shorter than 1000 characters.

Required: This attribute MUST be present and MUST be **true** if this property MUST be specified when an instance of the type is used; otherwise, **false**.

Visible: This attribute MUST be present and MUST be **true** if this attribute is presented to the user; otherwise, **false**.

2.2.4.63 BpmPropertyBool

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **BpmPropertyBool** complex type defines a Boolean property. It extends the **BpmProperty** (section [2.2.4.62](#)) type.

```
<xs:complexType name="BpmPropertyBool" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:attribute name="Value" type="xs:boolean" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Value: A Boolean value.

2.2.4.64 BpmPropertyDate

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **BpmPropertyDate** complex type defines a **Date** property. It extends the **BpmProperty** (section [2.2.4.62](#)) type.

```

<xs:complexType name="BpmPropertyDate" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:attribute name="Date" type="xs:dateTime" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Date: A required **dateTime** value. The property MUST be considered empty if set to 0001-01-01T00:00:00.

2.2.4.65 BpmPropertyDecimal

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **BpmPropertyDecimal** complex type defines a **Decimal** property. It extends the **BpmProperty** (section [2.2.4.62](#)) type.

```

<xs:complexType name="BpmPropertyDecimal" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:attribute name="Decimal" type="xs:decimal" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Decimal: A decimal value.

2.2.4.66 BpmPropertyHyperlink

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type defines a Hyperlink property. This type extends **BpmPropertyLinkBase** (section [2.2.4.68](#)).

This type is used to specify Hyperlinks as custom properties for types that extend **FirstClassElement** (section [2.2.4.99](#)).

```

<xs:complexType name="BpmPropertyHyperlink" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmPropertyLinkBase"/>
  </xs:complexContent>
</xs:complexType>

```

2.2.4.67 BpmPropertyHyperlink2

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **BpmPropertyHyperlink2** complex type defines a Hyperlink property. This type extends **BpmPropertyLinkBase** (section [2.2.4.68](#)).

This type is used to specify Hyperlinks as part of annotations for types that extend **FirstClassElement** complex type (section [2.2.4.99](#)).

```

<xs:complexType name="BpmPropertyHyperlink2" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmPropertyLinkBase"/>
  </xs:complexContent>
</xs:complexType>

```

2.2.4.68 BpmPropertyLinkBase

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **BpmPropertyLinkBase** complex type defines a **Hyperlink** property. It extends the **BpmProperty** (section [2.2.4.62](#)) type.

```

<xs:complexType name="BpmPropertyLinkBase" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:attribute name="Hyperlink" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Hyperlink: Hyperlink URL. The attribute MUST NOT be null and MUST be a valid [RFC1738](#) URL or a string constant: "about:blank".

2.2.4.69 BpmPropertyList

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **BmpPropertyList** complex type specifies zero, or one item of the **ArrayOfBpmPropertyListItem** complex type (section [2.2.4.24](#)). It extends the **BpmProperty** complex type (section [2.2.4.62](#)).

```

<xs:complexType name="BpmPropertyList" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="ListItems"
type="tns:ArrayOfBpmPropertyListItem"/>
      </xs:sequence>
      <xs:attribute name="SelectedIndex" type="xs:int" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

ListItems: This element MUST NOT be null and MUST conform to the schema of the **ArrayOfBpmPropertyListItem**.

SelectedIndex: An integer value that MUST fall between zero and the length of **ListItems**.

2.2.4.70 BpmPropertyListItem

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **BpmPropertyListItem** complex type specifies a name-value pair.

```
<xs:complexType name="BpmPropertyListItem" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="Name" type="xs:string"/>
  <xs:attribute name="Value" type="xs:string"/>
</xs:complexType>
```

Name: The string that MUST be present, MUST be shorter than 1000 characters, MUST NOT be empty after trimming leading and trailing **whitespaces**, and MUST NOT be null.

Value: The string that MUST be present, MUST be shorter than 1000 characters, MUST NOT be empty after trimming leading and trailing whitespaces, and MUST NOT be null.

2.2.4.71 BpmPropertyLongText

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type defines a Long Text property. The type extends **BpmProperty** (section [2.2.4.62](#)).

```
<xs:complexType name="BpmPropertyLongText" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:attribute name="Text" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Text: The long text value. If the **BpmProperty** (section [2.2.4.62](#)) Required field is set to **true**, the value MUST NOT be empty after trimming leading and trailing whitespaces and MUST NOT be **null**. The text MUST contain fewer than 4000 characters.

2.2.4.72 BpmPropertyText

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type defines a **Text** property. The type extends **BpmProperty** (section [2.2.4.62](#)).

```
<xs:complexType name="BpmPropertyText" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:attribute name="Text" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Text: The text value. If the **BpmProperty** (section [2.2.4.62](#)) Required field is set to **true**, the value MUST NOT be empty after trimming leading and trailing whitespaces and MUST NOT be null. The text MUST be less than 1000 characters.

2.2.4.73 BpmPropertyUser

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type defines a **User** property. The type extends **BpmProperty** (section [2.2.4.62](#)).

```

<xs:complexType name="BpmPropertyUser" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:attribute name="Login" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Login: The user **login name** in domain\user format. If the **BpmProperty** (section [2.2.4.62](#)) Required field is set to **true**, the value MUST NOT be empty after trimming leading and trailing white space and MUST NOT be null. It MUST contain less than 1000 characters.

2.2.4.74 CalculatedFormulaInfo

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type specifies a calculated formula in a KpiMeasure (section [2.2.4.129](#)). This type is used to specify calculations as part of a KPI's calculated metric.

```

<xs:complexType name="CalculatedFormulaInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="AliasInfoCollection"
      type="tns:ArrayOfAliasInfo"/>
  </xs:sequence>
  <xs:attribute name="Formula" type="xs:string"/>
</xs:complexType>

```

AliasInfoCollection: Specifies the array of AliasInfo elements used in the formula. This is of type **ArrayOfAliasInfo** (section [2.2.4.20](#)) and MUST contain 0 or more valid **AliasInfo** (section [2.2.4.13](#)) elements. If any of the **AliasInfo** objects fails validation, the **ErrorCode** MUST be one of the values specified in section [2.2.2.1.2](#).

A detailed specification of how exceptions are reported by the protocol server (2) is in section [2.2.2.1](#).

Formula: Specifies the formula for calculation using the aliases specified in **AliasInfoCollection**. Formula is of type string and MUST be no more than 1000 characters in length.

2.2.4.75 CalculatedMember

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Represents an OLAP calculated member in a **Dimension** complex type (section [2.2.4.90](#)).<12>

```

<xs:complexType name="CalculatedMember" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:Member">
      <xs:attribute name="Expression" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

Expression: A string containing the MDX statement for the OLAP calculated member.

2.2.4.76 Comment

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type represents a comment to be associated with a data entity. This class is the base class for **AnnotationComment** (section [2.2.4.19](#)).

```
<xs:complexType name="Comment" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="Guid" xmlns:s1="http://microsoft.com/wsd/types/" type="s1:guid"
  use="required"/>
  <xs:attribute name="CreatedBy" type="xs:string"/>
  <xs:attribute name="CreatedDate" type="xs:dateTime" use="required"/>
  <xs:attribute name="Message" type="xs:string"/>
</xs:complexType>
```

Guid: Specifies the identity for this comment. MUST be formatted as a GUID.

CreatedBy: The name of the user who created this comment. MUST be shorter than 1000 characters.

CreatedDate: The data and time when this comment was created.

Message: The message body of this comment. MUST be shorter than 4000.

2.2.4.77 ConfiguredView

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type specifies the scorecard view and configuration settings of how the scorecard displays and what end user actions are allowed. The protocol client that renders the scorecard MUST use this configuration when displaying it.

```
<xs:complexType name="ConfiguredView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SecondClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="StatusFilters"
        type="tns:StatusFilter"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ToolbarOptions"
        type="tns:ToolbarOptions"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
        type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="GridViewDefinition"
        type="tns:GridViewDefinition"/>
      </xs:sequence>
      <xs:attribute name="AllowStatusFilter" type="xs:boolean" use="required"/>
      <xs:attribute name="AllowFilter" type="xs:boolean" use="required"/>
      <xs:attribute name="AllowSort" type="xs:boolean" use="required"/>
      <xs:attribute name="AllowAnnotations" type="xs:boolean" use="required"/>
      <xs:attribute name="EmptyRowsFilterMode" type="tns:ScorecardEmptyRowsFilterMode"
      use="required"/>
      <xs:attribute name="AllowShowDetails" type="xs:boolean" use="required"/>
      <xs:attribute name="EnableTextwrap" type="xs:boolean" use="required"/>
      <xs:attribute name="AllowDynamicRowMemberExpansion" type="xs:boolean" use="required"/>
      <xs:attribute name="AllowDynamicColumnMemberExpansion" type="xs:boolean"
      use="required"/>
      <xs:attribute name="AllowRowDrill" type="xs:boolean" use="required"/>
      <xs:attribute name="AllowColumnDrill" type="xs:boolean" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

```

<xs:attribute name="AlwaysShowAnnotationCellFlags" type="xs:boolean" use="required"/>
<xs:attribute name="ExpandToFitWidth" type="xs:boolean" use="required"/>
<xs:attribute name="HideScorecard" type="xs:boolean" use="required"/>
<xs:attribute name="ShowStatusFiltersByDefault" type="xs:boolean" use="required"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

StatusFilters: Contains an array of 0 or more **StatusFilter** (section [2.2.4.167](#)) items. Specifies the list (1) of status filters that can be applied to the scorecard.

ToolbarOptions: This element is of type **ToolbarOptions** (section [2.2.4.179](#)) and specifies the configuration for the toolbar displayed in column headers of the scorecard.

DataSourceLocation: This element is of type **RepositoryLocation** (section [2.2.4.161](#)) and specifies the location of the data source (1) the scorecard connects to for retrieving and displaying data.

GridViewDefinition: This element is of type **GridViewDefinition** (section [2.2.4.122](#)) and specifies the definition of the grid based view displayed in the scorecard.

AllowStatusFilter: This attribute MUST be present and MUST be set to **true** if filtering by status is allowed in the scorecard; otherwise, **false**.

AllowFilter: This attribute MUST be present and MUST be set to **true** if filtering of rows is allowed in the scorecard; otherwise, **false**.

AllowSort: This attribute MUST be present and MUST be set to **true** if sorting of rows is allowed in the scorecard; otherwise, **false**.

AllowAnnotations: This attribute MUST be present and MUST be set to **true** if annotations are allowed to be entered in cells in the scorecard; otherwise, **false**.

EmptyRowsFilterMode: This attribute MUST be present. It is of type **ScorecardEmptyRowsFilterMode** (section [2.2.5.42](#)) and specifies how empty rows MUST be handled in the scorecard.

AllowShowDetails: This attribute MUST be present and MUST be set to **true** if the protocol client MUST display the **Show Details** menu option in the scorecard; otherwise, **false**.

EnableTextwrap: This attribute MUST be present and MUST be set to **true** if the protocol client MUST wrap the text in the scorecard cells; otherwise, **false**.

AllowDynamicRowMemberExpansion: This attribute MUST be present and MUST be set to **true** if row members in a scorecard are allowed to dynamically expand or collapse; otherwise, **false**.

AllowDynamicColumnMemberExpansion: This attribute MUST be present and MUST be set to **true** if column members in a scorecard are allowed to dynamically expand or collapse; otherwise, **false**.

AllowRowDrill: This attribute MUST be present and MUST be set to **true** if drilldown is allowed for members in rows; otherwise, **false**.

AllowColumnDrill: This attribute MUST be present and MUST be set to **true** if drilldown is allowed for members in columns; otherwise, **false**.

AlwaysShowAnnotationCellFlags: Reserved. MUST be set to **false** and MUST be ignored by the protocol client.

ExpandToFitWidth: This attribute MUST be present and MUST be set to **true** if the scorecard is expanded to fit the width of its container; otherwise, **false**.

HideScorecard: This attribute MUST be present and MUST be set to **true** if the scorecard MUST NOT be displayed; otherwise, **false**.

ShowStatusFiltersByDefault: This attribute MUST be present and MUST be set to **true** if filtering by status MUST be enabled by default; otherwise, **false**.

2.2.4.78 Cube

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **Cube** complex type specifies the structure of a cube. It extends the complex type **NameInfo** complex type (section [2.2.4.149](#)).

```
<xs:complexType name="Cube" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:NameInfo">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Dimensions"
type="tns:ArrayOfDimension"/>
        <xs:element minOccurs="0" maxOccurs="1" name="MeasureGroups"
type="tns:ArrayOfNameInfo"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Measures" type="tns:ArrayOfMeasure"/>
        <xs:element minOccurs="0" maxOccurs="1" name="NamedSets" type="tns:ArrayOfNamedSet"/>
      </xs:sequence>
      <xs:attribute name="Version" type="xs:int" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Dimensions: Specifies the dimensions (1) in the cube. This is an array of **Dimension** (see section [2.2.4.90](#)) items as defined in **ArrayOfDimension** (see section [2.2.4.19](#)). This element MUST be present.

MeasureGroups: Specifies the **measure groups** in the cube. This is an array of **NameInfo** (see section [2.2.4.149](#)) items as defined in **ArrayOfNameInfo** (see section [2.2.4.33](#)). This element MUST be present.

Measures: Specifies the measures in the cube. This is an array of **Measure** (see section [2.2.4.133](#)) items as defined in **ArrayOfMeasure** (see section [2.2.4.44](#)). This element MUST be present.

NamedSets: Specifies the named sets in the cube. This is an array of **NamedSet** (see section [2.2.4.147](#)) items as defined in **ArrayOfNamedSet** (see section [2.2.4.47](#)). This element MUST be present.

Version: Species the **major version** of the software on the server (2) that hosts the cube. MUST be a non-negative integer. This element MUST be 0 when the dimension (1) is part of a non-OLAP data source. This element MUST be present.

2.2.4.79 Dashboard

Namespace: <http://www.microsoft.com/performancepoint/scorecards>








The **Dashboard** complex type defines a dashboard. It specifies the layout and content of the pages in the dashboard and, if the dashboard has been deployed, its deployment location.


The **Dashboard** complex type extends the **FirstClassElement** type (section [2.2.4.99](#)).

```
<xs:complexType name="Dashboard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:FirstClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Pages"
type="tns:ArrayOfDashboardElement"/>
      </xs:sequence>
      <xs:attribute name="TemplateType" type="xs:string"/>
      <xs:attribute name="DeploymentPath" type="xs:string"/>
      <xs:attribute name="SitePath" type="xs:string"/>
      <xs:attribute name="MasterPagePath" type="xs:string"/>
      <xs:attribute name="MasterPageDisplayName" type="xs:string"/>
      <xs:attribute name="PageList" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Pages: Specifies the layout and content of pages in the dashboard. It is an array of **DashboardElement** items (section [2.2.4.80](#)). This **MUST** be present.

TemplateType: Specifies the initial layout of the first page of the dashboard. This **MUST** be present and **MUST** be one of the values from the following table.

Value	Example	Meaning
Blank		A blank dashboard page.
Header2Columns		A dashboard page with a header zone above two column zones.
1Zone		A dashboard page with one zone.
2Columns		A dashboard page with two column zones.
3Columns		A dashboard page with three column zones.
2Rows		A dashboard page with two row zones.
3Rows		A dashboard page with three row zones.

Value	Example	Meaning
ColumnSplitColumn		A dashboard page a column on the right and two rows zones on the left.

DeploymentPath: Specifies the URL where the dashboard is deployed. This MUST be a relative URL on the **site (2)** identified by the **SitePath** attribute.

SitePath: Specifies the URL of the site (2) where the dashboard will be deployed. This MUST be a relative URL on the protocol server (2) to which to deploy.

MasterPagePath: Specifies the URL of the **master page** used when the dashboard will be deployed. This MUST be a relative URL on the protocol server (2) to which to deploy.

MasterPageDisplayName: Specifies the display name of the master page used when the dashboard will be deployed.

PageList: Specifies whether or not each page in the deployed dashboard includes a page list.

Value	Meaning
True	A list (1) of pages will be displayed at the top of each deployed dashboard page, enabling users to switch between pages.
False	A list (1) of pages will not be displayed at the top of each deployed dashboard page.

2.2.4.80 DashboardElement

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **DashboardElement** complex type specifies the parts of a **Dashboard** (section [2.2.4.79](#)) that have width and height.

The **DashboardElement** complex type extends the **SecondClassElement** type (section [2.2.4.163](#)) and is the base type for **DashboardElementContainer** (section [2.2.4.81](#)) and **DashboardItem** (section [2.2.4.83](#)).

```
<xs:complexType name="DashboardElement" abstract="true"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SecondClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Height"
          type="tns:DashboardElementSize"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Width"
          type="tns:DashboardElementSize"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Height: Specifies the height of the **DashboardElement**. This MUST be present. This MUST be a **DashboardElementSize** (see section [2.2.4.82](#)).

Width: Specifies the width of the **DashboardElement**. This MUST be present. This MUST be a **DashboardElementSize**.

2.2.4.81 DashboardElementContainer

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **DashboardElementContainer** complex type specifies a group of **DashboardElement** complex types (section [2.2.4.80](#)) that are displayed vertically or horizontally.

Each dashboard page is specified by a **DashboardElementContainer**.

Each zone on a dashboard page is specified by a **DashboardElementContainer**.

The **DashboardElementContainer** complex type extends the **DashboardElement**.

```
<xs:complexType name="DashboardElementContainer" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DashboardElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="DashboardElements"
          type="tns:ArrayOfDashboardElement"/>
      </xs:sequence>
      <xs:attribute name="Orientation" type="tns:LayoutOrientation" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

DashboardElements: Specifies the **DashboardElements** in the **DashboardElementContainer**. This is an array of **DashboardElements** (section [2.2.4.14](#)).

Orientation: Specifies the orientation of the **DashboardElementContainer**. This is a **LayoutOrientation** complex type (section [2.2.5.33](#)). This MUST be present.

2.2.4.82 DashboardElementSize

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type specifies the width or height of a **DashboardElement** (section [2.2.4.80](#)).

```
<xs:complexType name="DashboardElementSize" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="Measurement" type="xs:int" use="required"/>
  <xs:attribute name="Units" type="tns:SizeType" use="required"/>
</xs:complexType>
```

Measurement: Specifies the number of size units. This number MUST be positive and MUST be less than or equal to 2,147,483,647. This MUST be present.

Units: Specifies the type of size units specified by the **Measurement** attribute. This MUST be a **SizeType** (section [2.2.5.46](#)). This MUST be present.

2.2.4.83 DashboardItem

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **DashboardItem** complex type specifies a single report, scorecard, or filter on a dashboard page. **DashboardItem** extends the **DashboardElement** (section [2.2.4.80](#)).

```
<xs:complexType name="DashboardItem" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DashboardElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="InboundParameters"
type="tns:ArrayOfParameterMapping"/>
        <xs:element minOccurs="0" maxOccurs="1" name="UnderlyingElementLocation"
type="tns:RepositoryLocation"/>
      </xs:sequence>
      <xs:attribute name="UnderlyingElementTypeName" type="xs:string"/>
      <xs:attribute name="AutoSizeWidth" type="xs:boolean" use="required"/>
      <xs:attribute name="AutoSizeHeight" type="xs:boolean" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

InboundParameters: Specifies an array of zero or more **ParameterMapping** (section [2.2.4.156](#)) items which indicate any parameters coming from other elements on the dashboard. This element **MUST** be present.

UnderlyingElementLocation: Specifies the **RepositoryLocation** (section [2.2.4.161](#)) for the contained element. This element **MUST** be present.

UnderlyingElementTypeName: Specifies the fully qualified name for the assembly class that provides the implementation of the element. This attribute **MUST** be present. [<13>](#)

AutoSizeWidth: Specifies whether the **DashboardItem** width is automatically set by the containing zone or uses a specific width. **true** indicates the **DashboardItem** width is controlled by the zone. **false** indicates the **DashboardItem** width is set by the **DashboardElement** (section [2.2.4.80](#)) base. This element **MUST** be present.

AutoSizeHeight: Specifies whether the **DashboardItem** height is automatically set by the containing zone or uses a specific height. **true** indicates the **DashboardItem** width is controlled by the zone. **false** indicates **DashboardItem** width is set by the **DashboardElement** (section [2.2.4.80](#)) base. This element **MUST** be present.

2.2.4.84 DataColumnMapping

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **DataColumnMapping** complex type specifies dimensional mapping information for a column of data.

```
<xs:complexType name="DataColumnMapping" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="UniqueName" type="xs:string"/>
  <xs:attribute name="KeyColumnName" type="xs:string"/>
  <xs:attribute name="SourceColumnName" type="xs:string"/>
  <xs:attribute name="FriendlyColumnName" type="xs:string"/>
  <xs:attribute name="ColumnType" type="tns:MappedColumnTypes" use="required"/>
  <xs:attribute name="FactAggregation" type="tns:FactAggregations" use="required"/>
  <xs:attribute name="ColumnDataType" type="tns:MappedColumnDataTypes" use="required"/>
</xs:complexType>
```

UniqueName: This attribute MUST be present. **UniqueName** specifies the unique name of the dimension (1) that a column represents. The value MUST NOT be empty.

ColumnType	Content
Ignore	The value MUST be an empty string.
Fact	The value MUST be an empty string.
Dimension	The value MUST be an empty string.
TimeDimension	The value MUST be an empty string.
Key	UniqueName specifies the unique name of the dimension (1) that a column represents. It is used when referenced by another column mapping via the KeyColumnName. The value MUST NOT be empty.

KeyColumnName: This attribute MUST be present. The content of **KeyColumnName** is determined by the **ColumnType** as designated in the following table:

ColumnType	Content
Ignore	The attribute MUST be ignored.
Fact	The attribute MUST be ignored.
Dimension	KeyColumnName specifies the name of the tabular column that contains the UniqueName for the dimension (1). If this attribute is not present, the UniqueName of this column is used as the UniqueName for the dimension (1).
TimeDimension	KeyColumnName specifies the name of the tabular column that contains the UniqueName for the dimension (1). If this attribute is not present, the UniqueName of this column is used as the UniqueName for the dimension (1).
Key	The attribute MUST be ignored.

SourceColumnName: Specifies the tabular data source column name of the source for this mapping. This attribute MUST be present and MUST be a string of 1 or more characters.

FriendlyColumnName: Specifies a descriptive string for the tabular column name of the source for this mapping. This attribute MUST be present. The value MUST be a string of 1 or more characters.

ColumnType: Specifies the mapped column type. This attribute MUST be present. The value MUST conform to the **MappedColumnTypes** (Section [2.2.5.35](#)) simple type.

FactAggregation: Specifies the aggregation method. This attribute MUST be present. If the **ColumnType** is not "Fact", the value is not used and MUST be "None". Otherwise, the value MUST conform to the **FactAggregations** (Section [2.2.5.18](#)) simple type.

ColumnDataType: Specifies the type of data contained within the mapped column. This attribute MUST be present. The value MUST conform to the **MappedColumnDataTypes** (Section [2.2.5.34](#)) simple type.

2.2.4.85 DataSource

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **DataSource** complex type specifies a connection to an external data provider.

```

<xs:complexType name="DataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:FirstClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="CustomData" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CustomTimeIntelligenceSettings"
type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DataTableMapping"
type="tns:DataTableMapping"/>
      </xs:sequence>
      <xs:attribute name="SourceName" type="xs:string"/>
      <xs:attribute name="ServerName" type="xs:string"/>
      <xs:attribute name="DatabaseName" type="xs:string"/>
      <xs:attribute name="CubeName" type="xs:string"/>
      <xs:attribute name="CubeDisplayName" type="xs:string"/>
      <xs:attribute name="FormattingDimensionName" type="xs:string"/>
      <xs:attribute name="FormattingDimensionDisplayName" type="xs:string"/>
      <xs:attribute name="FormattingDimensionType" type="tns:DimensionTypeEnum"
use="required"/>
      <xs:attribute name="ConnectionString" type="xs:string"/>
      <xs:attribute name="Roles" type="xs:string"/>
      <xs:attribute name="UseConnectionString" type="xs:boolean" use="required"/>
      <xs:attribute name="ConnectionContext" type="tns:ConnectionContext" use="required"/>
      <xs:attribute name="PassUserNameAsAdomdCustomData" type="xs:boolean" use="required"/>
      <xs:attribute name="ReadOnly" type="xs:boolean" use="required"/>
      <xs:attribute name="MinutesToCache" type="xs:int" use="required"/>
      <xs:attribute name="ServerMajorVersion" type="xs:int" use="required"/>
      <xs:attribute name="SubTypeId" type="xs:string"/>
      <xs:attribute name="TargetApplicationId" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

CustomData: String of custom data for the data source (1). This element MUST be present.

For **ExcelServicesWorkbook** data sources, **CustomData** MUST contain an **ExcelServicesData** complex type object (section [2.2.4.97](#)) serialized as an **XML document** and XML encoded.

For **ExcelWorkbook** data sources, **CustomData** MUST contain an **ExcelDataSet** complex type object (section [2.2.4.96](#)) serialized as an XML document and XML encoded.

For all other data source types, **CustomData** MUST be an empty string.

CustomTimeIntelligenceSettings: Contains a string of custom time intelligence data for the data source. This element MUST be present.

For **ADOMD.NET** data sources, **CustomTimeIntelligenceSettings** MUST be a **TimeIntelligenceMdxSettings** complex type object (section [2.2.4.175](#)) serialized as an XML document and XML encoded.

For all other data source types, this element MUST be an empty string.

DataTableMapping: Specifies how tabular data is mapped to multidimensional data for table-based data sources. This element MUST be present. This element is used for **ExcelServicesWorkbook**, **ExcelWorkbook**, **SqlTabularDataSource**, and **SpListDataSource** types. For other data source types, it MUST be set to **NULL** and MUST be ignored by the protocol server (2).

SourceName: Specifies the type of the data source. This attribute MUST be present and MUST be one of the values specified in the following table.

Value	Meaning
ADOMD.NET	An Analysis Services data source.
SqlTabularDataSource	A SQL Server table data source.
ExcelServicesWorkbook	An Excel Services workbook.
ExcelWorkbook	An embedded Excel workbook.
SplistDataSource	A list data source <14> .

ServerName: Specifies the name of the server (2) used by the data source. This attribute MUST be present. The content of **ServerName** is determined by the type of the data source as specified in the following table.

Type	Contents
ADOMD.NET	ServerName MUST be the host name of the server (2) running Analysis Services.
SqlTabularDataSource	ServerName MUST be the host name of the server (2) instance that hosts the tabular data source.
ExcelServicesWorkbook	ServerName MUST be the URL of the site (2) which hosts the data source.
ExcelWorkbook	ServerName MUST be an empty string.
SplistDataSource	ServerName MUST be the URL of the site (2) containing the list (1) used by the data source.

DatabaseName: Specifies the name of the database used by the data source. This attribute MUST be present. The content of **DatabaseName** is determined by the type of the data source as designated in the following table.

Type	Contents
ADOMD.NET	DatabaseName MUST be the name of the multidimensional database used by the data source.
SqlTabularDataSource	DatabaseName MUST be the name of the database used by the data source.
ExcelServicesWorkbook	DatabaseName MUST be the name of the document library containing the workbook.
ExcelWorkbook	DatabaseName MUST be an empty string.
SplistDataSource	DatabaseName MUST be the name of the site (2) list which contains the list (1) used by the data source.

CubeName: Specifies the name of the cube used by the data source. This attribute MUST be present. The content of **CubeName** is determined by the type of the data source as designated in the following table.

Type	Contents
ADOMD.NET	CubeName MUST be the name of the cube used by the data source.
SqlTabularDataSource	CubeName MUST be the name of the table in the database used by the data source. CubeName MUST be in the form <code>[schema].[table]</code> , where <i>schema</i> is the name of the table schema and <i>table</i> is the name of the table.
ExcelServicesWorkbook	CubeName MUST be the path and file name of the Excel Services workbook to be used.
ExcelWorkbook	CubeName MUST be an empty string.
SplistDataSource	CubeName MUST be the GUID of the list (1) used as the data source.

CubeDisplayName: Provides a display name for the **CubeName** used by the data source. This attribute **MUST** be present. The content of **CubeDisplayName** is determined by the type of the data source as designated in the following table.

Type	Contents
ADOMD.NET	CubeDisplayName is the name of the selected cube that is displayed to the user.
SqlTabularDataSource	CubeDisplayName is the name of the selected SQL table that is displayed to the user.
ExcelServicesWorkbook	CubeDisplayName is the name of the selected Excel Services workbook that is displayed to the user.
ExcelWorkbook	CubeDisplayName MUST be an empty string.
SplistDataSource	CubeDisplayName SHOULD be the name of the list (1).

FormattingDimensionName: Specifies the initial value for the dimension (1) in the cube which contains the numerical formats for analytic grids or charts using the data source. This element is only used for **ADOMD.NET** data sources. It **MUST** be present for all data source types.

For non-**ADOMD.NET** data sources, this attribute **MUST** be an empty string.

For **ADOMD.NET** data sources, this attribute **MAY** be an empty string.

FormattingDimensionDisplayName: Provides a display name for the **FormattingDimensionName** used for **ADOMD.NET** data sources. This attribute **MUST** be present for all data source types. For non-**ADOMD.NET** data sources, this element **MUST** be an empty string.

FormattingDimensionType: Specifies the **DimensionTypeEnum** simple type (section [2.2.5.13](#)) of the dimension (1) used in **FormattingDimensionName**. This attribute **MUST** be present for all data source types. For non-**ADOMD.NET** data sources, this element **MUST** be set to "Other".

ConnectionString: Specifies the user-defined connection string used to connect to the data source when **UseConnectionString** is set to **TRUE**. This attribute **MUST** be present and **MUST NOT** be an empty string. The content of **ConnectionString** is determined by the type of the data source as designated in the following table.

Type	Contents
ADOMD.NET	ConnectionString MUST be a valid connection string which connects to the OLAP data source. If the ReadOnly attribute is set to "true", ConnectionString MUST be an empty string.
SqlTabularDataSource	ConnectionString MUST be a valid SQL table connection string. If the ReadOnly attribute is set to "true", the ConnectionString MUST be empty.
ExcelServicesWorkbook	ConnectionString MUST be an empty string.
ExcelWorkbook	ConnectionString MUST be an empty string.
SpListDataSource	ConnectionString MUST be an empty string.

Roles: Specifies the database roles used when connecting to an **ADOMD.NET** data source. This attribute MUST be present for all data source types. For non-**ADOMD.NET** data sources, this attribute MUST be an empty string.

UseConnectionString: If **TRUE**, **ConnectionString** is used to connect to the data source. If **FALSE**, the contents of the **ConnectionString** property are ignored and the connection string is built internally. This attribute MUST be present, and is only used for **ADOMD.NET** and **SqlTabularDataSource** data source types.

ConnectionContext: Specifies the user **ConnectionContext** simple type (section [2.2.5.10](#)) to be used for authentication to the data source. This attribute MUST be present, and MUST be ignored for **ExcelWorkbook** data source types.

PassUserNameAsAdomdCustomData: Specifies whether to pass the user name to **ADOMD.NET** as part of the **CustomData** property of the connection string. **CustomData** is sometimes used as an alternative identity, distinct from the connection identity. This attribute MUST be present, is only used by **ADOMD.NET** data sources and MUST be ignored by all other data source types.

ReadOnly: This attribute MUST be present and MUST be set to **TRUE** if the data source object is read-only for the current user; otherwise, this attribute is **FALSE**. When calling the **CreateDataSource** operation (section [3.1.4.3](#)), if this attribute is set to **TRUE**, the server (2) responds with a SOAP fault containing the **ErrorCode** "CannotPublishReadOnlyElement"; otherwise, if this attribute is set to **FALSE**, the creation is successful.

MinutesToCache: Specifies the timeout in minutes for caching data source requests. This attribute MUST be present and the value MUST be a non-negative integer. If **MinutesToCache** is set to zero, the data source MUST NOT be cached.

ServerMajorVersion: Indicates the major version of the data source being used. This attribute MUST be present.

SubTypeId: Specifies the subtype of the data source. This attribute MUST be present and MUST be the same value as the **SourceName** element.

TargetApplicationId: Specifies the Secure Store ([\[MS-SSWPS\]](#)) **target application** identifier containing the credentials that MUST be used for authentication to the data source when **ConnectionContext** is set to **SecureStoreCredentials**. When **ConnectionContext** IS NOT set to **SecureStoreCredentials**, this attribute MUST be ignored. This attribute MUST be present.

2.2.4.86 DataTableMapping

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **DataTableMapping** complex type specifies how data from tabular data sources is mapped to multidimensional data.

```
<xs:complexType name="DataTableMapping" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="ColumnMappings"
type="tns:ArrayOfDataColumnMapping"/>
    <xs:element minOccurs="0" maxOccurs="1" name="MasterTimeColumn"
type="tns:DataColumnMapping"/>
  </xs:sequence>
  <xs:attribute name="DateAggregationType" type="tns:DateAggregationTypes" use="required"/>
  <xs:attribute name="CalendarStartMonth" type="xs:int" use="required"/>
</xs:complexType>
```

ColumnMappings: Specifies the **ArrayOfDataColumnMapping** (section [2.2.4.29](#)) items that provide the mapping information for each of the tabular columns. This element **MUST** be present.

If an item in **ColumnMappings** has a **Dimension** or **TimeDimension** MappedColumnType (see section [2.2.5.35](#)), the item's **KeyColumnName** (section [2.2.4.84](#)) **MUST** be either an empty string or **MUST** be equal to the **UniqueName** (section [2.2.4.84](#)) of one of the other columns in the array with a **MappedColumnType** equal to Key (section [2.2.5.35](#)).

MasterTimeColumn: Specifies the mapped **DateTime** column (section [2.2.5.34](#)) in the tabular data source that is used as the time dimension (1) for time intelligence calculations.

DateAggregationType: Specifies the list (1) of **DateAggregationTypes** (see section [2.2.5.12](#)) that specifies which time period levels are used for the mapped time dimensions (1). This attribute **MUST** be present and **MUST** contain at least one **DateAggregationType**.

CalendarStartMonth: Specifies the fiscal year start month used for the time dimensions (1). This element **MUST** be present and **MUST** be one of these values: 0 for January, 1 for February, 2 for March, 3 for April, 4 for May, 5 for June, 6 for July, 7 for August, 8 for September, 9 for October, 10 for November, or 11 for December.

2.2.4.87 DefaultDimensionSetting

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies a default set of members in a dimension (1). It extends the Dimension (see section [2.2.4.90](#)) type.

```
<xs:complexType name="DefaultDimensionSetting" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:Dimension">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="Members" type="tns:Member"/>
      </xs:sequence>
      <xs:attribute name="IsVisible" type="xs:boolean" use="required"/>
      <xs:attribute name="ShowAsSlider" type="xs:boolean" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Members: Specifies a default set of members (3) in a dimension (1). Contains an array of 0 or more **Member** (see section [2.2.4.134](#)) items. This element **MUST** be present.

IsVisible: This attribute is deprecated from the protocol and MUST NOT be used.

ShowAsSlider: This type is deprecated from the protocol and MUST NOT be used.

2.2.4.88 DictionaryWrapperOfStringGridCell

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type specifies a collection of `ArrayOfGridCells` (see section [2.2.4.35](#)) with associated string keys.

```
<xs:complexType name="DictionaryWrapperOfStringGridCell"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Keys" type="tns:ArrayOfString"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Values" type="tns:ArrayOfGridCell"/>
  </xs:sequence>
</xs:complexType>
```

Keys: An array of strings representing keys for addressing the contents of the **Values** array (see section [2.2.4.54](#)).

Values: An array of **GridCells** (see section [2.2.4.100](#)). This element MUST conform to the schema of the **ArrayOfGridCell** complex type (see section [2.2.4.35](#)).

The **Keys** and **Values** MUST conform to the following:

- The number of items in **Keys** and the number of items in **Values** MUST be the same.
- Each item in **Values** MUST NOT be null.
- Each item in **Keys** MUST be a unique, non-null string.
- Each value in **Values** MUST have a corresponding key in **Keys** (that is, for each `Values[i]`, the corresponding key is `Keys[i]`).

2.2.4.89 DictionaryWrapperOfStringPropertyBag

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type specifies a collection of **ArrayOfPropertyBags** with associated string keys.

```
<xs:complexType name="DictionaryWrapperOfStringPropertyBag"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Keys" type="tns:ArrayOfString"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Values" type="tns:ArrayOfPropertyBag"/>
  </xs:sequence>
</xs:complexType>
```

Keys: An array of strings serving as keys for addressing the contents of the **Values** array. See **ArrayOfString**, section [2.2.4.54](#).

Values: An array of **PropertyBags**. See **ArrayOfPropertyBag**, section [2.2.4.52](#).

The **Keys** and **Values** MUST conform to the following:

- The number of items in **Keys** and the number of items in **Values** MUST be the same.
- Each item in **Values** MUST NOT be null.
- Each item in **Keys** MUST be a unique, non-null string.
- Each value in **Values** MUST have a corresponding key in **Keys** (that is, for each `Values[i]`, the corresponding key is `Keys[i]`).

2.2.4.90 Dimension

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **Dimension** complex type specifies the structure of a dimension (1). It extends the complex type **NameInfo** (section [2.2.4.149](#)).

```
<xs:complexType name="Dimension" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:NameInfo">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="MeasureGroupNames"
type="tns:ArrayOfString"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Type" type="tns:DimensionTypeEnum"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Hierarchies"
type="tns:ArrayOfHierarchy"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Levels" type="tns:ArrayOfLevel"/>
      </xs:sequence>
      <xs:attribute name="IsMeasureDimension" type="xs:boolean" use="required"/>
      <xs:attribute name="DefaultMemberName" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

MeasureGroupNames: Specifies a list (1) of the names of groupings of the measures in the dimension (1). This element MUST be present.

Type: Specifies the type of the dimension (1) in the form of the simple type **DimensionTypeEnum** (section [2.2.5.13](#)). This element MUST be present.

Hierarchies: Specifies the hierarchies in the dimension (1). A list (1) of the **Hierarchy** elements as defined in the complex type **ArrayOfHierarchy** (section [2.2.4.39](#)). The **Hierarchy.Levels** collection will contain only the **Levels** that are used in that **Hierarchy**. This element MUST be present.

Levels: Specifies the levels in the dimension (1). A list (1) of the **Level** elements as defined in the complex type **ArrayOfLevel** (section [2.2.4.43](#)). The **Dimension.Levels** collection will contain all of the **Levels** that are used in all of the **Hierarchies** in a **Dimension**. This element MUST be present.

IsMeasureDimension: Specifies if the dimension (1) is a measure dimension (1). This value MUST be **TRUE** when the value of **Type** is "Measure"; otherwise, it is **FALSE**. This element MUST be present.

DefaultMemberName: Specifies the unique name of the default member for the dimension (1). The length of the value MUST NOT exceed 1000 characters. This element MUST be present.

2.2.4.91 Element

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This abstract class specifies basic metadata about an item. This class is the base class for [FirstClassElement](#) and [SecondClassElement](#).

```
<xs:complexType name="Element" abstract="true" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Properties" type="tns:ArrayOfBpmProperty"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Comments" type="tns:ArrayOfComment"/>
  </xs:sequence>
</xs:complexType>
```

Properties: Specifies properties associated with the Element. This element MUST be present. Contains an array of 0 or more [BpmProperty](#) items.

Comments: Specifies comments associated with the Element. This element MUST be present. Contains an array of 0 or more [Comment](#) items.

2.2.4.92 ElementVersion

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type specifies the version information used to distinguish different instances of a [FirstClassElement](#).

```
<xs:complexType name="ElementVersion" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="Major" type="xs:int" use="required"/>
  <xs:attribute name="Minor" type="xs:int" use="required"/>
</xs:complexType>
```

Major: The major version number of the **FirstClassElement**. This attribute MUST be present and MUST be 0 or greater and MUST be less than or equal to 2,147,483,647.

Minor: The minor version number of the **FirstClassElement**. This attribute MUST be present and MUST be 0 or greater and MUST be less than or equal to 2,147,483,647.

2.2.4.93 EliminateDescendantsSetOp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to eliminate descendant members (3), of the member (3) specified by **Name** (see section [2.2.4.165](#)), from a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="EliminateDescendantsSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.94 EliminateMemberSetOp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type extends the **SetOperation** (section [2.2.4.165](#)) type. It defines an operation to eliminate a member (3), specified by **Name** (see section [2.2.4.165](#)), from a **MemberSet** (see section [2.2.4.144](#)).

```
<xs:complexType name="EliminateMemberSetOp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.95 EndPoint

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type defines the receiving end of a connection between a Web Part that provides parameter values such as a filter or a scorecard, and a Web Part that consumes parameter values, such as a report view or a scorecard.

```
<xs:complexType name="EndPoint" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="Category" type="tns:EndPointCategory" use="required"/>
  <xs:attribute name="UniqueName" type="xs:string"/>
  <xs:attribute name="DisplayName" type="xs:string"/>
  <xs:attribute name="AcceptsMultipleFilterLinks" type="xs:boolean" use="required"/>
</xs:complexType>
```

Category: This attribute describes the category of the **EndPoint** as defined in [EndPointCategory](#). It MUST be present.

UniqueName: This attribute is a string that represents the unique name of the **EndPoint**. It MUST be present.

DisplayName: This attribute is a string that represents the display name of the **EndPoint**. It MUST be present.

AcceptsMultipleFilterLinks: This attribute MUST be present and MUST be **true** if the **EndPoint** can accept multiple connections from a filter or a scorecard; otherwise, **false**.

2.2.4.96 ExcelDataSet

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the Excel workbook ([\[MS-XLS\]](#)) data for an **ExcelWorkbook** data source.

```
<xs:complexType name="ExcelDataSet" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="CompressedDataTable" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ExcelFileBlob" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="TableMapping" type="tns:DataTableMapping"/>
  </xs:sequence>
  <xs:attribute name="UseFirstRowHeaders" type="xs:boolean" use="required"/>
</xs:complexType>
```

```
</xs:complexType>
```

CompressedDataTable: An ADO.NET **DataTable** object (as described in [\[DataTable\]](#)), which contains all of the rows and columns of data in the embedded workbook. The **DataTable** object MUST be serialized into binary format as specified in [\[MS-NRBF\]](#), then compressed using GZIP compression as specified in [\[RFC1952\]](#), and then encoded with **base64 encoding**.

ExcelFileBlob: Contains the embedded Excel workbook. This element MUST be present and MUST contain a valid workbook file containing the data for the data source. The file contents MUST be compressed using GZIP compression as specified in [\[RFC1952\]](#) and then MUST be encoded with base64 encoding.

TableMapping: This attribute is deprecated from the protocol and MUST NOT be used.

UseFirstRowHeaders: This attribute MUST be present and MUST be **true** if the first row in the embedded spreadsheet consists of headers; otherwise, **false**.

2.2.4.97 ExcelServicesData

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Describes an Excel Services ([\[MS-ESP\]](#)) data connection used by Excel Services data sources and Excel Services reports.

```
<xs:complexType name="ExcelServicesData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="WorkbookParameters"
type="tns:PropertyBag"/>
  </xs:sequence>
  <xs:attribute name="SharePointSite" type="xs:string"/>
  <xs:attribute name="DocumentLibrary" type="xs:string"/>
  <xs:attribute name="DocumentLibraryRootFolder" type="xs:string"/>
  <xs:attribute name="DocumentLibraryDisplay" type="xs:string"/>
  <xs:attribute name="FolderFileName" type="xs:string"/>
  <xs:attribute name="FileName" type="xs:string"/>
  <xs:attribute name="ItemName" type="xs:string"/>
  <xs:attribute name="ViewOptions" type="tns:ExcelServicesViewOptions" use="required"/>
  <xs:attribute name="ToolbarType" type="tns:ExcelServicesToolbarType" use="required"/>
  <xs:attribute name="ToolbarOptions" type="tns:ExcelServicesToolbarOptions" use="required"/>
</xs:complexType>
```

WorkbookParameters: Specifies the **PropertyBag** (section [2.2.4.158](#)) containing the parameters that are passed to the workbook when opening the data source. This element MUST be present.

SharePointSite: Specifies the URL of the site (2) containing an Excel Services data source. This attribute MUST be present. **SharePointSite** MUST only be used for Excel Services reports.

DocumentLibrary: Specifies the GUID of the document library that contains the data source. This attribute MUST be present.

DocumentLibraryRootFolder: Specifies the root folder of the document library. This attribute MUST be present.

DocumentLibraryDisplay: Specifies the display name of the document library. This attribute MUST be present.

FolderFileName: Specifies the path and file name of the Excel Services workbook. This attribute MUST be present. **FolderFileName** MUST only be used for Excel Services reports.

FileName: Specifies the file name of the Excel Services workbook. This attribute MUST be present. **FileName** MUST only be used for Excel Services reports.

ItemName: Specifies the name of the **published item** in the Excel Service workbook used as the data source. This attribute MUST be present.

ViewOptions: Specifies the combination of one or more **ExcelServicesViewOptions** (section [2.2.5.17](#)) that control how the user is allowed to interact with the Excel Services report. This attribute MUST be present.

ToolbarType: Specifies the **ExcelServicesToolbarType** (section [2.2.5.16](#)) that controls which toolbar is shown in the Excel Services report. This attribute MUST be present.

ToolbarOptions: Specifies the combination of one or more **ExcelServicesToolbarOptions** (section [2.2.5.15](#)) for the toolbar displayed on the report. This attribute MUST be present.

2.2.4.98 Filter

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **Filter** complex type specifies a filter.

```
<xs:complexType name="Filter" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:FirstClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="BeginPoints"
type="tns:ArrayOfParameterDefinition"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CustomData" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="EndPoints" type="tns:ArrayOfEndPoint"/>
      </xs:sequence>
      <xs:attribute name="SubTypeId" type="xs:string"/>
      <xs:attribute name="ReadOnly" type="xs:boolean" use="required"/>
      <xs:attribute name="SelectionMode" type="tns:FilterSelectionMode" use="required"/>
      <xs:attribute name="Visualization" type="xs:string"/>
      <xs:attribute name="RendererClassName" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

BeginPoints: Specifies the available connection sources to filter and set conditions for the display of other reports and scorecards. This element MUST be present, and the array MUST contain at least one **ParameterDefinition** complex type (section [2.2.4.155](#)). This element MUST conform to the schema of the **ArrayOfParameterDefinition** complex type (section [2.2.4.50](#)).

DataSourceLocation: Specifies the data source (1) for the selectable filter values. This element MUST be present. This element MUST conform to the schema of the **RepositoryLocation** complex type (section [2.2.4.161](#)). This element MUST contain the **RepositoryLocation** of a data source (1).

CustomData: Specifies custom data for the filter. This element MUST be present. If **SubTypeId** does not contain a custom value, **CustomData** MUST contain an empty string. If **SubTypeId** does

contain a custom value, **CustomData** MAY be used depending on the implementation of the third-party filter. The specific content will be defined by the implementer of the custom filter.

EndPoints: Specifies available connections destinations for filtering and controlling the conditional visibility of the filter. This element **MUST** be present, and the array **MUST** be empty if the **SubTypeId** is not a custom value. This element **MUST** conform to the schema of the **ArrayOfEndPoint** complex type (section [2.2.4.33](#)).

SubTypeId: Specifies the identifier for the type of the filter. This attribute **MUST** be present. The value **MUST NOT** be empty. It **MUST NOT** be longer than 60 characters. It **MUST NOT** contain the characters ', ", or \. Each **ParameterDefinition** in the **BeginPoints** of the filter **MUST** have a **CustomDefinition** that is valid for the specified **SubTypeId**. If the filter is a third-party filter, the value **MUST NOT** be one of the values in the following table. Otherwise, the value of **SubTypeId** **MUST** be one of the values specified in the following table.

Value	Content
FixedValues	Specifies a filter that contains selections provided from a tabular data source (1).
MDXQuery	Specifies a filter that contains selections provided by an MDX query.
MemberSelection	Specifies a filter that contains selections provided by selecting members from a data source (1).
NamedSets	Specifies a filter that contains selections provided from a named set definition.
TimeIntelligence	Specifies a filter that contains selections provided by a time intelligence mapped data source (1).
TimeIntelligencePostFormula	Specifies a filter that contains selections provided by a custom formula applied against a time intelligence mapped data source (1).

ReadOnly: This element is ignored if **SubTypeId** is "FixedValues", "MDXQuery", "MemberSelection", "NamedSets", "TimeIntelligence", or "TimeIntelligencePostFormula". It **MAY** be used by any other **SubTypeId**. This attribute **MUST** be present and **MUST** be **TRUE** if the filter is read-only; otherwise, this element is **FALSE**.

SelectionMode: Specifies the selection mode that the filter supports. The attribute **MUST** be present. The value **MUST** be one of the enumerated values specified in the **FilterSelectionMode** simple type (section [2.2.5.19](#)).

Visualization: Specifies the type of visualization for the filter. The attribute **MUST** be present. The value **MUST** be one of the following: "SingleSelectList", "SingleSelectTree", "MultiSelectTree", "TimeIntelligenceCalendar", or "Custom".

RendererClassName: Specifies the fully qualified name for the assembly class that provides the rendering for the filter. This attribute **MUST** be present. If **SubTypeId** is "FixedValues", "MDXQuery", "MemberSelection", "NamedSets", "TimeIntelligence", or "TimeIntelligencePostFormula" the value **MUST NOT** be empty; otherwise, this element **MUST** be the assembly-qualified name of the custom type.

2.2.4.99 FirstClassElement

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **FirstClassElement** complex type is an abstract class that represents an object that is versionable. This is the base class for the complex types **Dashboard** (section [2.2.4.79](#)), **DataSource** (section [2.2.4.85](#)), **Scorecard** (section [2.2.4.162](#)), **ReportView** (section [2.2.4.160](#)), **Kpi** (section [2.2.4.128](#)) and **Indicator** (section [2.2.4.125](#)).

```
<xs:complexType name="FirstClassElement" abstract="true"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:Element">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Version" type="tns:ElementVersion"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Location"
type="tns:RepositoryLocation"/>
      </xs:sequence>
      <xs:attribute name="Folder" type="xs:string"/>
      <xs:attribute name="CreatedBy" type="xs:string"/>
      <xs:attribute name="CreatedDate" type="xs:dateTime" use="required"/>
      <xs:attribute name="ContentType" type="tns:FCOContentType" use="required"/>
      <xs:attribute name="LastModified" type="xs:dateTime" use="required"/>
      <xs:attribute name="ModifiedBy" type="xs:string"/>
      <xs:attribute name="CheckedOutTo" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Version: The **ElementVersion** complex type (section [2.2.4.92](#)) information of the object. This value is optional, and has a default value of zero for the major and minor version. The major version will increase when the child classes **Dashboard**, **DataSource**, **Scorecard**, **ReportView**, **Kpi**, and **Indicator** are created and updated.

Location: The location information of the object, as specified by the **RepositoryLocation** complex type (section [2.2.4.161](#)).

Folder: The folder that the object belongs to, in the form of "folder1\subfolder2\subfolder3". This value is optional. and has a default value of empty string.

CreatedBy: The user who initially created the object. This value is optional, and if it is set to the value of null, the server (2) will set it to the value of the actual user creating it.

CreatedDate: The date the object was initially created. This value MUST be set by the server (2) upon **FirstClassElement** creation.

ContentType: The content type of the object in the form of **FCOContentType** simple type (section [3.1.4.36.4.1](#)). This value MUST be set by the server (2) upon **FirstClassElement** creation.

LastModified: The date this version of the object was last modified. This value MUST be set by the server (2) upon **FirstClassElement** creation.

ModifiedBy: The user who last modified the object. This value is optional, and if it is set to the value of null, the server (2) will set it the value of the actual user modifying it.

CheckedOutTo: The user who currently has the object checked out. This value is optional, and has a default value of empty string.

When creating dashboard content in a content store, the dashboard content SHOULD contain at least one **BpmProperty** complex type (section [2.2.4.62](#)). <15> The **BpmProperty's UniqueName** property is "8dd07d4d87794510afdb1f07664359bc_Element_Name" which maps to the SharePoint

list property "Title", required for a SharePoint list item. The Description property is "8dd07d4d87794510afdb1f07664359bc_Element_Description" and maps to the SharePoint list property "Description", which is optional. "8dd07d4d87794510afdb1f07664359bc_Element_Owner" maps to the SharePoint list property "Person Responsible", which is also optional.

2.2.4.100 GridCell

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies a single cell used by the scorecard grid view and the analytic grid view. The following Unified Modeling Language (UML) class diagram shows the **GridCell** and its relationship with other classes.




Figure 6: GridCell in relation to other classes

```

<xs:complexType name="GridCell1" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>

```

```

    <xs:element minOccurs="0" maxOccurs="1" name="FormatInfo" type="tns:GridFormatInfo"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Properties" type="tns:PropertyBag"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DisplayElements"
type="tns:ArrayOfGridDisplayElement"/>
    <xs:element minOccurs="0" maxOccurs="1" name="IndicatorLocation"
type="tns:RepositoryLocation"/>
    <xs:element minOccurs="1" maxOccurs="1" name="InBand" type="xs:int"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CellAnnotation" type="tns:Annotation"/>
  </xs:sequence>
  <xs:attribute name="Value" type="xs:decimal" use="required"/>
  <xs:attribute name="ActualValue" type="xs:decimal" use="required"/>
  <xs:attribute name="Score" type="xs:decimal" use="required"/>
  <xs:attribute name="Weight" type="xs:decimal" use="required"/>
  <xs:attribute name="BestChildScore" type="xs:decimal" use="required"/>
  <xs:attribute name="WorstChildScore" type="xs:decimal" use="required"/>
  <xs:attribute name="IsValueInError" type="xs:boolean" use="required"/>
  <xs:attribute name="HasAnnotation" type="xs:boolean" use="required"/>
  <xs:attribute name="IsRollupScore" type="xs:boolean" use="required"/>
  <xs:attribute name="ValueSource" type="tns:ValueSources" use="required"/>
  <xs:attribute name="IsValidScore" type="xs:boolean" use="required"/>
</xs:complexType>

```

FormatInfo: Specifies overriding styles applied to the **GridCell**, as defined in [GridFormatInfo](#). Any style changed on the GridFormatInfo overrides the default style.

Properties: This is a property bag as defined in [PropertyBag](#). This property allows third parties to specify custom properties for a single grid view cell.

DisplayElements: Specifies a collection of [GridDisplayElement](#) as defined in [ArrayOfGridDisplayElement](#). Each cell MUST contain zero or more visible elements such as **actual**, **target**, **variance**, **indicator**, and **score**. Each visible element is represented as a GridDisplayElement in this collection.

IndicatorLocation: If the **GridCell** contains an **indicator**, this property MUST point to the indicator location, as defined in [RepositoryLocation](#). For built-in indicators, define only the **RepositoryLocation's ItemUrl** attribute (section [2.2.4.161](#)) as `"/PPSBUILTININDICATORS/000_.00"`, replacing the **000** with the Indicator ID.

Indicator	ID
Stoplight	0
Stoplight (Centered)	1
2 light – Small	2
2 light - Small (Centered)	3
2 light - Medium	4
2 light - Medium (Centered)	5
2 light – Large	6
2 light - Large (Centered)	7
Stoplight – Smal	8

Indicator	ID
Stoplight - Small (Centered)	9
Stoplight - Medium	10
Stoplight - Medium (Centered)	11
Stoplight - Large	12
Stoplight - Large (Centered)	13
Stoplight E - Small	14
Stoplight E - Small (Centered)	15
Stoplight D - Small (Centered)	16
Stoplight D - Medium	17
Stoplight D - Medium (Centered)	18
Stoplight A - Small	19
Stoplight A - Small (Centered)	20
Stoplight A - Medium	21
Stoplight A - Medium (Centered)	22
Stoplight A - Medium (Centered)	23
Stoplight A - Large	24
Stoplight A - Large (Centered)	25
Stoplight B - Small	26
Stoplight B - Small (Centered)	27
Stoplight B - Medium	28
Stoplight B - Medium (Centered)	29
Stoplight B - Large	30
Stoplight B - Large (Centered)	31
Cylinder	32
Cylinder (Centered)	33
Gradient	34
Gradient (Centered)	35
Thermometer	36
Thermometer (Centered)	37
Half Gauge	38

Indicator	ID
Half Gauge (Centered)	39
Reverse Half Gauge	40
Reverse Half Gauge (Centered)	41
Progress 4 Bar	42
Progress 4 Bar (Centered)	43
Progress 5 Bar	44
Progress 5 Bar (Centered)	45
Progress 6 Bar	46
Progress 6 Bar (Centered)	47
Progress 7 Bar	48
Progress 7 Bar (Centered)	49
Progress 8 Bar	50
Progress 8 Bar (Centered)	51
Progress 9 Bar	52
Progress 9 Bar (Centered)	53
Progress 10 Bar	54
Progress 10 Bar (Centered)	55
Progress 4 Bar - Medium	56
Progress 4 Bar - Medium (Centered)	57
Progress 5 Bar - Medium	58
Progress 5 Bar - Medium (Centered)	59
Progress 6 Bar - Medium	60
Progress 6 Bar - Medium (Centered)	61
Progress 7 Bar - Medium	62
Progress 7 Bar - Medium (Centered)	63
Progress 8 Bar - Medium	64
Progress 8 Bar - Medium (Centered)	65
Progress 9 Bar - Medium	66
Progress 9 Bar - Medium (Centered)	67
Progress 10 Bar - Medium	68

Indicator	ID
Progress 10 Bar - Medium (Centered)	69
Progress 4 Bar - Large	70
Progress 4 Bar - Large (Centered)	71
Progress 5 Bar - Large	72
Progress 5 Bar - Large (Centered)	73
Progress 6 Bar - Large	74
Progress 6 Bar - Large (Centered)	75
Progress 7 Bar - Large	76
Progress 7 Bar - Large (Centered)	77
Progress 8 Bar - Large	78
Progress 8 Bar - Large (Centered)	79
Progress 9 Bar - Large	80
Progress 9 Bar - Large (Centered)	81
Progress 10 Bar - Large	82
Progress 10 Bar - Large (Centered)	83
Vertical Bar - Small	84
Vertical Bar - Small (Centered)	85
Vertical Bar -Medium	86
Vertical Bar -Medium (Centered)	87
Vertical Bar - Large	88
Vertical Bar - Large (Centered)	89
Smiley - Small	90
Smiley - Small (Centered)	91
Smiley - Medium	92
Smiley - Medium (Centered)	93
Smiley B - Small	94
Smiley B - Small (Centered)	95
Smiley B -Medium	96
Smiley B -Medium (Centered)	97
Smiley B - Large	98

Indicator	ID
Smiley B - Large (Centered)	99
Road Sign	100
Road Sign (Centered)	101
Weather	102
Weather (Centered)	103
Operators	104
Operators (Centered)	105
Flags - Small	106
Flags - Small (Centered)	107
Flags - Medium	108
Flags - Medium (Centered)	109
Flags - Large	110
Flags - Large (Centered)	111
Check - Small	112
Check - Small (Centered)	113
Check - Medium	114
Check - Medium (Centered)	115
Check - Large	116
Check - Large (Centered)	117
Check A - Small	118
Check A - Small (Centered)	119
Check - Medium	120
Check - Medium (Centered)	121
Check - Large	122
Check - Large (Centered)	123
Quarters - Small	124
Quarters - Small (Centered)	125
Quarters - Medium	126
Quarters - Medium (Centered)	127
Quarters - Large	128

Indicator	ID
Quarters - Large (Centered)	129
Red To Black - Small	130
Red To Black - Small (Centered)	131
Red To Black - Medium	132
Red To Black - Medium (Centered)	133
Red To Black - Large	134
Red To Black - Large (Centered)	135
Up Trend B - Small	136
Up Trend B - Small (Centered)	137
Down Trend B - Small	138
Down Trend B - Small (Centered)	139
Gray Trend B - Small	140
Gray Trend B - Small (Centered)	141
Up Trend - Small	142
Up Trend - Small (Centered)	143
Down Trend -Small	144
Down Trend -Small (Centered)	145
Gray Trend - Small	146
Gray Trend - Small (Centered)	147
Up Trend - Medium	148
Up Trend - Medium (Centered)	149
Down Trend - Medium	150
Down Trend - Medium (Centered)	151
Gray Trend - Medium	152
Gray Trend- Medium (Centered)	153
Up Trend - Large	154
Up Trend - Large (Centered)	155
Down Trend - Large	156
Down Trend - Large (Centered)	157
Gray Trend - Large	158

Indicator	ID
Gray Trend - Large (Centered)	159

InBand: If the GridCell contains an **indicator**, this property MUST contain the index to the indicator band (see [Indicator.IndicatorBands](#)) or -1 if the cell contains no data (see [Indicator.NoDataIndicatorBand](#)).

CellAnnotation: If the property HasAnnotation is set to **true**, **CellAnnotation** MUST NOT be null and it MUST contain a valid [Annotation](#) instance.

Value: Specifies the numeric value for the metric associated with the GridCell. The value represents the decimal value of the metric from a column or row that contains that cell. If the metric is a Target, Value contains the Target value for that cell. The same happens for other metric types, like **Actual** and **Aggregation**.

ActualValue: The cell can either be a **target** or an **actual** and corresponds to the value of the recorded fact. Otherwise, this value **MUST** be zero.

Score: Specifies the calculated score for a target cell.

Weight: Specifies the weight of the GridCell on weighted **rollup** calculations.

BestChildScore: This property keeps track of the best score on cells that are located below the current GridCell on the same column.

WorstChildScore: This property keeps track of the worst score on cells that are located below the GridCell on the same column.

IsValueInError: This attribute MUST be **true** if the value for the **GridCell** could not be retrieved from the data source (1) or could not be calculated; otherwise, **false**.

HasAnnotation: This attribute MUST be **true** if the **GridCell** contains annotations; otherwise, **false**. The annotations are stored on the **CellAnnotation** property.

IsRollupScore: This attribute MUST be **true** if the **GridCell** has a calculated rollup score; otherwise, **false**.

ValueSource: Represents the type of calculation used to compute the value of the **GridCell**, as defined in [ValueSources](#).

IsValidScore: This attribute MUST be **true** if the scoring engine was able to calculate the score for this cell; otherwise, **false**.

2.2.4.101 GridCellSet

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This class specifies the cells used to represent a scorecard or analytic grid. The representation is based on a two dimensional array of [GridCell](#) elements indexed by objects of type [GridHeaderItem](#).

```
<xs:complexType name="GridCellSet" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Table"
      type="tns:DictionaryWrapperOfStringGridCell"/>
  </xs:sequence>
```

</xs:complexType>

Table: Specifies a dictionary that maps strings to GridCell objects, as defined in [DictionaryWrapperOfStringGridCell](#).

The key string used on this dictionary is derived from the two GridHeaderItem instances used to index this two dimensional array, and MUST be created as follows:

1. Build an auxiliary dictionary
2. The dictionary MUST be created with one entry for each GridHeaderItem instance.
3. The keys MUST be the GridHeaderItem.DimensionValue values. If DimensionValue is null or empty, GridHeaderItem.DisplayText MUST be used.
4. The value MUST be the dictionary key concatenated with GridHeaderItem.Id.
5. The dictionary keys MUST be sorted alphabetically in descending order.
6. Build the **Table** key based on the previous described dictionary
7. The key to the **Table** dictionary MUST be generated by concatenating the following string pattern for each entry on the auxiliary dictionary:

[entry key] + ":" + [entry value] + "_"

Example:

Given two GridHeaderItems

- Header 1 (KPI named Internet Sales Amount):
 - Id = 1;
 - DimensionValue = "/PerformancePoint/Lists/Dashboard Content/1_.000";
 - DisplayName = "Internet Sales Amount"
- Header 2 (Target metric):
 - Id = 2;
 - DimensionValue = "Target";
 - DisplayName = "Target"

The generated Key is: "/PerformancePoint/Lists/Dashboard Content/1_.000:/PerformancePoint/Lists/Dashboard Content/1_.0001_Target:Target2_"

2.2.4.102 GridColor

Namespace: http://www.microsoft.com/performancepoint/scorecards

This class represents the grid color for the [GridCell](#) contents.

```
<xs:complexType name="GridColor" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:attribute name="A" type="xs:unsignedByte" use="required"/>  
</xs:complexType>
```

```
<xs:attribute name="R" type="xs:unsignedByte" use="required"/>
<xs:attribute name="G" type="xs:unsignedByte" use="required"/>
<xs:attribute name="B" type="xs:unsignedByte" use="required"/>
</xs:complexType>
```

A: The alpha color channel. The value MUST be between 0 and 255. A value of 0 means that the **pixel** does not have any coverage information (transparent). A value of 255 means that the pixel is completely overlapped (opaque).

R: The red color channel. The value MUST be between 0 and 255.

G: The green color channel. The value MUST be between 0 and 255.

B: The blue color channel. The value MUST be between 0 and 255.

2.2.4.103 GridDisplayElement

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies an element in a scorecard cell. This is a base class for the following complex types:

[GridDisplayElementNumber](#), [GridDisplayElementIndicator](#), [GridDisplayElementText](#), [GridDisplayElementHyperLink](#).

Also see following diagram:




Figure 7: GridDisplayElement

```

<xs:complexType name="GridDisplayElement" abstract="true"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Text" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="TooltipText" type="xs:string"/>
  </xs:sequence>
  <xs:attribute name="Status" type="tns:GridCellElementStatus" use="required"/>
</xs:complexType>

```

Text: Specifies the text of the element in the cell.

TooltipText: Specifies the text that will appear when users hover with the mouse over the element in the cell.

Status: Specifies the status of the element in a scorecard cell. MUST be one of the values defined in [GridCellElementStatus](#)

2.2.4.104 GridDisplayElementActual

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the [GridDisplayElement](#) of a KPI's actual value in a scorecard cell. Inherits from the [GridDisplayElementNumber](#).

```
<xs:complexType name="GridDisplayElementActual" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElementNumber"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.105 GridDisplayElementAggregation

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the [GridDisplayElement](#) of an aggregated value in a scorecard cell. Inherits from the [GridDisplayElementNumber](#).

```
<xs:complexType name="GridDisplayElementAggregation"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElementNumber"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.106 GridDisplayElementHyperLink

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the [GridDisplayElement](#) of a KPI's hyperlink property in a cell. Inherits from the [GridDisplayElement](#).

```
<xs:complexType name="GridDisplayElementHyperLink"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElement">
      <xs:attribute name="LinkUrl" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

LinkUrl: Hyperlink URL that will appear in the cell. The attribute MUST be a valid [\[RFC1738\]](#) URL.

2.2.4.107 GridDisplayElementIndicator

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the image of an **indicator** for the [GridDisplayElement](#) in a scorecard cell. Inherits from the [GridDisplayElement](#).

```
<xs:complexType name="GridDisplayElementIndicator"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<xs:complexContent mixed="false">
  <xs:extension base="tns:GridDisplayElement">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="IndicatorLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
    <xs:attribute name="IndicatorBand" type="xs:int" use="required"/>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

IndicatorLocation: Specifies the [RepositoryLocation](#) of the [Indicator](#) object for the scorecard cell. MUST NOT be null and MUST reference an Indicator stored in the server (2). See [RepositoryLocation](#).

IndicatorBand: Specifies the one based index of the **IndicatorBand** that is displayed in the scorecard cell. The image defined by the **Indicator** property **NoDataIndicatorBand** is used in the cell if the value is less than one, or if the value is greater than the total number of [IndicatorBands](#).

2.2.4.108 GridDisplayElementIndicatorText

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the descriptive name of an **indicator** for the [GridDisplayElement](#) in a scorecard cell. Descriptive name of the **IndicatorBand** is the **ToolTip** property of the [IndicatorBand](#), for example: "off target"

```

<xs:complexType name="GridDisplayElementIndicatorText"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElementText">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="IndicatorLocation"
type="tns:RepositoryLocation"/>
      </xs:sequence>
      <xs:attribute name="IndicatorBand" type="xs:int" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

IndicatorLocation: Specifies the [RepositoryLocation](#) of the [Indicator](#) object for the scorecard cell. MUST NOT be null and MUST reference an Indicator stored in the server (2). See [RepositoryLocation](#).

IndicatorBand: Specifies the one based index of the indicator band that its descriptive name is displayed in the scorecard cell. The descriptive name defined by the **Indicator** property **NoDataIndicatorBand** is used in the cell if the value is less than one, or if the value is greater than the total number of IndicatorBands.

2.2.4.109 GridDisplayElementNumber

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies a numeric [GridDisplayElement](#) in a scorecard cell. This is a base class for the following complex types [GridDisplayElementsActual](#), [GridDsisplayElementTarget](#), [GridDisplayElementScore](#), [GridDisplayElementVariance](#)

```
<xs:complexType name="GridDisplayElementNumber" abstract="true"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElement">
      <xs:attribute name="Value" type="xs:decimal" use="required"/>
      <xs:attribute name="OverrideValue" type="xs:decimal" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Value: Specifies the decimal value of the cell element.

OverrideValue: Specifies the decimal value equivalent to the formatted value of the cell.

Example is shown in following table:

Property	Value
Text	55%
Value	0.5498
OverrideValue	55

2.2.4.110 GridDisplayElementScore

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the [GridDisplayElement](#) of the KPI target's score in a scorecard cell. Inherits from the [GridDisplayElementNumber](#).

```
<xs:complexType name="GridDisplayElementScore" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElementNumber"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.111 GridDisplayElementTarget

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the [GridDisplayElement](#) of a KPI's target value in a scorecard cell. Inherits from the [GridDisplayElementNumber](#).

```
<xs:complexType name="GridDisplayElementTarget" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElementNumber"/>
  </xs:complexContent>
</xs:complexType>
```


2.2.4.112 GridDisplayElementText

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the [GridDisplayElement](#) of a text value in a scorecard cell. Inherits from the [GridDisplayElement](#).

```
<xs:complexType name="GridDisplayElementText" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElement"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.113 GridDisplayElementVariance

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the [GridDisplayElement](#) of a KPI target's variance value in a scorecard cell. Inherits from the [GridDisplayElementNumber](#).

```
<xs:complexType name="GridDisplayElementVariance"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElementNumber"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.114 GridFontInfo

Namespace: http://www.microsoft.com/performancepoint/scorecards

This class represents the font display options for the [GridCell](#) contents.

```
<xs:complexType name="GridFontInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="FamilyName" type="xs:string"/>
  <xs:attribute name="SizeInPoints" type="xs:float" use="required"/>
  <xs:attribute name="Bold" type="tns:Trinary" use="required"/>
  <xs:attribute name="Italic" type="tns:Trinary" use="required"/>
  <xs:attribute name="Underline" type="tns:Trinary" use="required"/>
  <xs:attribute name="Strikeout" type="tns:Trinary" use="required"/>
</xs:complexType>
```

FamilyName: The family name of the font. This value MUST be present.

SizeInPoints: The font size in points. This value MUST be present.

Bold: Specifies whether the font is bold. This value MUST be set in the form of [Trinary](#) and MUST be present.

Italic: Specifies whether the font is italicized. This value MUST be set in the form of [Trinary](#) and MUST be present.

Underline: Specifies whether the font is underlined. This value MUST be set in the form of [Trinary](#) and MUST be present.

Strikeout: Specifies whether the font has a strikethrough. This value MUST be set in the form of [Trinary](#) and MUST be present.

2.2.4.115 GridFormatInfo

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This class represents the display format settings for the [GridCell](#) contents.

```
<xs:complexType name="GridFormatInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="FontInfo" type="tns:GridFontInfo"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ForeColor" type="tns:GridColor"/>
    <xs:element minOccurs="0" maxOccurs="1" name="BackColor" type="tns:GridColor"/>
  </xs:sequence>
  <xs:attribute name="TextWrap" type="tns:Trinary" use="required"/>
  <xs:attribute name="VerticalAlignment" type="tns:VerticalAlignments" use="required"/>
  <xs:attribute name="HorizontalAlignment" type="tns:HorizontalAlignments" use="required"/>
</xs:complexType>
```

FontInfo: The font information of the GridCell contents, as defined in [GridFontInfo](#).

ForeColor: The font color of the GridCell contents, as defined in [GridColor](#).

BackColor: The background color of the GridCell contents, as defined in [GridColor](#).

TextWrap: Specifies whether the contents of a GridCell wraps. This value MUST be set in the form of [Trinary](#) and MUST be present.

VerticalAlignment: The vertical alignment of the GridCell contents. This value MUST be set in the form of [VerticalAlignments](#) and MUST be present.

HorizontalAlignment: The horizontal alignment of the GridCell contents. This value MUST be set in the form of [HorizontalAlignments](#) and MUST be present.

2.2.4.116 GridHeaderItem

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **GridHeaderItem** complex type specifies the header that represents a row or a column node in a scorecard.

```
<xs:complexType name="GridHeaderItem" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="HeaderFormatInfo"
      type="tns:GridFormatInfo"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CellFormatInfo" type="tns:GridFormatInfo"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Children"
      type="tns:ArrayOfGridHeaderItem"/>
    <xs:element minOccurs="0" maxOccurs="1" name="SerializeTag"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DimensionMember" type="tns:Member"/>
    <xs:element minOccurs="0" maxOccurs="1" name="OverrideIndicatorLocation"
      type="tns:RepositoryLocation"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Banding" type="tns:Banding"/>
    <xs:element minOccurs="0" maxOccurs="1" name="LinkedKpiLocation"
      type="tns:RepositoryLocation"/>
  </xs:sequence>
</xs:complexType>
```

```

    <xs:element minOccurs="0" maxOccurs="1" name="BpmProperties"
type="tns:ArrayOfBpmProperty"/>
    <xs:element minOccurs="0" maxOccurs="1" name="TargetSettings"
type="tns:GridTargetSettings"/>
    <xs:element minOccurs="0" maxOccurs="1" name="TrendIndicatorLocation"
type="tns:RepositoryLocation"/>
  </xs:sequence>
  <xs:attribute name="Id" type="xs:int" use="required"/>
  <xs:attribute name="Guid" xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"
use="required"/>
  <xs:attribute name="DefinitionGuid" xmlns:s1="http://microsoft.com/wsdl/types/"
type="s1:guid" use="required"/>
  <xs:attribute name="DisplayText" type="xs:string"/>
  <xs:attribute name="DimensionName" type="xs:string"/>
  <xs:attribute name="DimensionValue" type="xs:string"/>
  <xs:attribute name="HeaderType" type="tns:ScorecardNodeTypes" use="required"/>
  <xs:attribute name="GroupId" type="xs:int" use="required"/>
  <xs:attribute name="Depth" type="xs:int" use="required"/>
  <xs:attribute name="DescendantSpan" type="xs:int" use="required"/>
  <xs:attribute name="LeafSpan" type="xs:int" use="required"/>
  <xs:attribute name="IsCollapsed" type="xs:boolean" use="required"/>
  <xs:attribute name="IsDynamicCellExpansionEnabled" type="xs:boolean" use="required"/>
  <xs:attribute name="IsDrillEnabled" type="xs:boolean" use="required"/>
  <xs:attribute name="IsDrillDownDisabled" type="xs:boolean" use="required"/>
  <xs:attribute name="IsDrillUpDisabled" type="xs:boolean" use="required"/>
  <xs:attribute name="IsDynamicallyExpandedHeader" type="xs:boolean" use="required"/>
  <xs:attribute name="IsCellHidden" type="xs:boolean" use="required"/>
  <xs:attribute name="IsPathHidden" type="xs:boolean" use="required"/>
  <xs:attribute name="IsHiddenBasedOnFilterStatus" type="xs:boolean" use="required"/>
  <xs:attribute name="NamedSetExpression" type="xs:string"/>
  <xs:attribute name="CustomSetFormula" type="xs:string"/>
  <xs:attribute name="IsNamedSetInError" type="xs:boolean" use="required"/>
  <xs:attribute name="IsNamedSetEmpty" type="xs:boolean" use="required"/>
  <xs:attribute name="NamedSetType" type="tns:ScorecardNamedSetType" use="required"/>
  <xs:attribute name="UseLinkedElementDisplayText" type="xs:boolean" use="required"/>
  <xs:attribute name="Hyperlink" type="xs:string"/>
  <xs:attribute name="ShowHyperlinkInNewWindow" type="xs:boolean" use="required"/>
  <xs:attribute name="IsHierarchyHeader" type="xs:boolean" use="required"/>
  <xs:attribute name="IsColumnHeader" type="xs:boolean" use="required"/>
  <xs:attribute name="AppendFilterInfoToHyperlink" type="xs:boolean" use="required"/>
  <xs:attribute name="Weight" type="xs:decimal" use="required"/>
  <xs:attribute name="KpiTargetName" type="xs:string"/>
  <xs:attribute name="AggregationType" type="tns:HeaderAggregationTypes" use="required"/>
</xs:complexType>

```

HeaderFormatInfo: This property, as defined in the **GridFormatInfo** complex type (section [2.2.4.115](#)), overrides the format information set for **GridHeaderItem**, under either the **GridViewDefinition** (section [2.2.4.122](#)) or **GridViewData** (section [2.2.4.121](#)) complex types, for **GridHeaderItem**.

CellFormatInfo: This property, as defined in **GridFormatInfo**, overrides the format information set under **GridHeaderItem.HeaderFormatInfo** for **GridHeaderItem**.

Children: Specifies an array of **GridHeaderItem**, as defined in the **ArrayOfGridHeaderItem** complex type (section [2.2.4.37](#)).

SerializeTag: A general purpose tag for **GridHeaderItem** defined as a generic **object (1)**.

DimensionMember: **Dimension** member (section [2.2.4.90](#)) associated with this header, as defined in the **Member** complex type (section [2.2.4.134](#)).

OverrideIndicatorLocation: The location of the override **Indicator** complex type (section [2.2.4.125](#)) for rollups as defined in the **RepositoryLocation** complex type (section [2.2.4.161](#)). If null, the default rollup indicator location, as mentioned under **GridViewDefinition** or **GridViewData** will be used.

Banding: Banding settings, as defined in the **Banding** complex type (section [2.2.4.60](#)). When null, the **BandingType.Type** is **Normalized**.

LinkedKpiLocation: Location of the linked **Kpi** complex type (section [2.2.4.128](#)), as defined in **RepositoryLocation**.

BpmProperties: Collection of element properties, as defined in the **ArrayOfBpmProperty** complex type (section [2.2.4.23](#)).

TargetSettings: Target column settings, as defined in **GridTargetSettings** complex type (section [2.2.4.119](#)).

TrendIndicatorLocation: If the header type is aggregate and **TrendIndicatorLocation** points to a valid location as defined in **RepositoryLocation**, this header item represents a trend column. The **TrendIndicatorLocation** MUST point to the location of the indicator used to show the trend.

Id: Unique integer identifier for this header.

Guid: Global unique identifier for **GridHeaderItem**.

DefinitionGuid: Global unique identifier that links a data header back to the definition header.

DisplayText: Display text for **GridHeaderItem**.

DimensionName: **Dimension** name is set based on the header type. The following table specifies the allowable dimension (1) names for different scorecard header types.

Header type	Dimension name
Member	Member Dimension name.
Kpi	Scorecard__
KpiActual	Scorecard_Measures__
KpiTarget	Scorecard_Measures__
Aggregate	Scorecard_Aggregates__
ScorecardDetails	Scorecard_Details__
DocumentLinks	Scorecard_DocumentLinks__
NamedSet	null
None	null

DimensionValue: **Dimension** value is set based on the header type. The following table specifies the allowable dimension (1) values for different scorecard header types.

Header type	Dimension value
Member	Member unique name.
Kpi	RepositoryLocation of the Kpi .
KpiActual	This value equals the BpmPropertyText.Text value.
KpiTarget	This value equals the BpmPropertyText.Text value.
Aggregate	AggregateType as specified by the AggregateTypeEnum simple type (section 2.2.5.1).
ScorecardDetails	Only the values "Description", "Name", or "Person Responsible" are supported.
DocumentLinks	GUID.
NamedSet	null
None	null

HeaderType: The type of **GridHeaderItem** as defined in the **ScorecardNodeTypes** simple type (section [2.2.5.44](#)).

GroupId: An integer identifier to identify all members (3) in a set. The **GroupId** is positive if the header type is **Member** or **NamedSet** and has a negative value when no hierarchy (for example, a flat list (1) of members). Root headers are an exception to this rule because their **GroupId** value is zero.

Depth: Depth of the **GridHeaderItem** in the tree. It starts with value zero for the root level node and keeps incrementing moving towards the leaves.

DescendantSpan: Maximum number of header levels for all descendant leaves.

LeafSpan: Number of leaves under **GridHeaderItem**.

IsCollapsed: This attribute MUST be **TRUE** if the header node is collapsed; otherwise, this attribute is **FALSE**.

IsDynamicCellExpansionEnabled: This attribute MUST be **TRUE** if the dynamic expansion (named set expansion) setting is enabled for this header node; otherwise, this attribute is **FALSE**. This setting is valid only for **Dimension** members.

IsDrillEnabled: This attribute MUST be **TRUE** if the drill operations are enabled for **GridHeaderItem**; otherwise, this attribute is **FALSE**. This setting is valid only for **Dimension** members.

IsDrillDownDisabled: This attribute MUST be **TRUE** if the drilldown operation is disabled for **GridHeaderItem**; otherwise, this attribute is **FALSE**. This gets set if it is the leaf node in the **Hierarchy** complex type (section [2.2.4.124](#)).

IsDrillUpDisabled: This attribute MUST be **TRUE** if the drill up operation is disabled for this header; otherwise, the attribute is **FALSE**. This attribute gets set if it is the top most node in the **Hierarchy**.

IsDynamicallyExpandedHeader: This attribute MUST be **TRUE** if **GridHeaderItem** was created through dynamic expansion (named set expansion); otherwise, this attribute is **FALSE**. The header item can be dynamically expanded only if the **IsDynamicCellExpansionEnabled** attribute and the

corresponding **ConfiguredView** (section [2.2.4.77](#)) setting (**AllowDynamicRowMemberExpansion** for rows and **AllowDynamicColumnMemberExpansion** for columns) are set to **TRUE**.

IsCellHidden: This attribute MUST be **TRUE** if the header cell is hidden; otherwise, this attribute is **FALSE**.

IsPathHidden: This attribute MUST be **TRUE** if the header path is hidden; otherwise, this attribute is **FALSE**.

IsHiddenBasedOnFilterStatus: This attribute MUST be **TRUE** if this **GridHeaderItem** is hidden by **Filter** (section [2.2.4.98](#)) status; otherwise, this attribute is **FALSE**.

NamedSetExpression: When the **NamedSetType** is **NamedSet**, this MUST conform to a valid MDX set expression. When the type is **CustomFormula**, the **CustomSetFormula** and **NamedSetExpression** properties are equal. For the **TimeFormula** type, this MUST be an empty string.

CustomSetFormula: When the **NamedSetType** is **TimeFormula**, this MUST be a valid time intelligence formula. When the type is **CustomFormula**, the **NamedSetExpression** properties are equal.

IsNamedSetInError: This attribute MUST be **TRUE** if the named set expression is in an error state; otherwise, this attribute is **FALSE**.

IsNamedSetEmpty: This attribute MUST be **TRUE** if the named set expression returned an empty set; otherwise, this attribute is **FALSE**.

NamedSetType: It identifies whether it is a named set header, custom formula, time formula, or none, as defined in the **ScorecardNamedSetType** simple type (section [2.2.5.43](#)).

UseLinkedElementDisplayText: This attribute MUST be **TRUE** if the linked **Kpi** name should be used as the display text for **GridHeaderItem**; otherwise, this attribute is **FALSE**.

Hyperlink: Obsolete.

ShowHyperlinkInNewWindow: Obsolete.

IsHierarchyHeader: This attribute MUST be **TRUE** if the header is part of a **Hierarchy** collection, or **FALSE** if the header is part of a linear list (1).

IsColumnHeader: This attribute MUST be **TRUE** if this is a column header, or **FALSE** if this is a row header.

AppendFilterInfoToHyperlink: This attribute MUST be **TRUE** if the filter information MUST be appended to the hyperlink; otherwise, this attribute is **FALSE**.

Weight: Display value weight that gets used for **Kpi** headers.

KpiTargetName: **Kpi** actual or **Target** (section [2.2.4.170](#)) display name for **GridHeaderItem**.

AggregationType: Specifies the aggregation types, as defined in the **HeaderAggregationTypes** simple type (section [2.2.5.26](#)).

2.2.4.117 GridIndicatorSettings

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Defines the settings for the [Indicator](#) in the [Target](#) field.

```
<xs:complexType name="GridIndicatorSettings" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Position" type="tns:IndicatorPosition"/>
  </xs:sequence>
  <xs:attribute name="ShowImage" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowText" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowForeColor" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowBackColor" type="xs:boolean" use="required"/>
</xs:complexType>
```

Position: Represents the position of the Indicator as defined in [IndicatorPosition](#).

ShowImage: This attribute MUST be **true** if the Indicator's image (see [IndicatorBand.ImageData](#)) displays; otherwise, **false**.

ShowText: This attribute MUST be **true** if the Indicator's text (see [IndicatorBand.ToolTip](#)) displays; otherwise, **false**.

ShowForeColor: This attribute MUST be **true** if the Indicator's foreground color (see [IndicatorBand.Color](#)) is applied; otherwise, **false**.

ShowBackColor: This attribute MUST be **true** if the Indicator's background color (see [IndicatorBand.BackColor](#)) is applied; otherwise, **false**.

2.2.4.118 GridScoreSettings

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Defines the settings for the score in the [Target](#) field.

```
<xs:complexType name="GridScoreSettings" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="ShowValue" type="xs:boolean" use="required"/>
  <xs:attribute name="ScoreType" type="tns:ScoreTypes" use="required"/>
  <xs:attribute name="RollupType" type="tns:RollupTypes" use="required"/>
  <xs:attribute name="Position" type="tns:DataValuePosition" use="required"/>
</xs:complexType>
```

ShowValue: This attribute MUST be **true** if the score is shown for Target column; otherwise, **false**.

ScoreType: Represents the score type as defined in [ScoreTypes](#).

RollupType: Represents the score rollup type as defined in [RollupTypes](#).

Position: Represents the score position as defined in [DataValuePosition](#).

2.2.4.119 GridTargetSettings

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Defines the display settings for the [Target](#) column.

```
<xs:complexType name="GridTargetSettings" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
```

```

    <xs:element minOccurs="0" maxOccurs="1" name="VarianceSettings"
type="tns:GridVarianceSettings"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FilterEmptyRows" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Position" type="tns:DataValuePosition"/>
    <xs:element minOccurs="1" maxOccurs="1" name="PositionActual"
type="tns:DataValuePosition"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ScoreSettings"
type="tns:GridScoreSettings"/>
    <xs:element minOccurs="0" maxOccurs="1" name="IndicatorSettings"
type="tns:GridIndicatorSettings"/>
  </xs:sequence>
  <xs:attribute name="ShowValue" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowActualAsTarget" type="xs:boolean" use="required"/>
  <xs:attribute name="IgnoreScoreFilter" type="xs:boolean" use="required"/>
</xs:complexType>

```

VarianceSettings: Represents the **variance** settings as defined in [GridVarianceSettings](#).

FilterEmptyRows: This attribute MUST be **true** if the empty rows are filtered; otherwise, **false**.

Position: Represents the position of the Target value in the cell as defined in [DataValuePosition](#).

PositionActual: Represents the position of the associated actual value in the cell as defined in [DataValuePosition](#).

ScoreSettings: Represents the Target cell's score settings as defined in [GridScoreSettings](#).

IndicatorSettings: Represents the Target cell's [Indicator](#) settings as defined in [GridIndicatorSettings](#).

ShowValue: This attribute MUST be **true** if the Target value is shown; otherwise, **false**.

ShowActualAsTarget: This attribute MUST be **true** if the actual value is shown in place of the Target value; otherwise, **false**.

IgnoreScoreFilter: This attribute MUST be **true** if the Target is considered when filtering rows using the score filter; otherwise, **false**.

2.2.4.120 GridVarianceSettings

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Defines the settings for the **variance** in the [Target](#) column.

```

<xs:complexType name="GridVarianceSettings" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="NumDecimalPlaces" type="xs:int" use="required"/>
  <xs:attribute name="VarianceType" type="tns:VarianceType" use="required"/>
  <xs:attribute name="DisplayType" type="tns:VarianceDisplayType" use="required"/>
  <xs:attribute name="ShowValue" type="xs:boolean" use="required"/>
  <xs:attribute name="Position" type="tns:DataValuePosition" use="required"/>
</xs:complexType>

```

NumDecimalPlaces: Represents the number of decimal places to show after the decimal.

VarianceType: Represents the **variance** calculation type as defined in [VarianceType](#).

DisplayType: Represents the **variance** display type as defined in [VarianceDisplayType](#).

ShowValue: This attribute MUST be **true** if the **variance** is displayed in the Target column; otherwise **false**.

Position: Represents the position of the **variance** value as defined in [DataValuePosition](#).

2.2.4.121 GridViewData

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **GridViewData** complex type specifies the data structure that represents the scorecard view. The following diagram illustrates the scorecard view representation:




Figure 8: GridViewData

The **GridViewData** is mainly composed of two tree data structures representing all the row and column headers and a two dimensional array representing every possible interception between elements of those two trees.

The row and column header trees MUST be accessed by the properties **RootRowHeader** and **RootColumnHeader** respectively. The two dimensional array MUST be accessed by the **Cells** property.

```
<xs:complexType name="GridViewData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Cells" type="tns:GridCellSet"/>
    <xs:element minOccurs="0" maxOccurs="1" name="RootRowHeader" type="tns:GridHeaderItem"/>
    <xs:element minOccurs="0" maxOccurs="1" name="RootColumnHeader"
type="tns:GridHeaderItem"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ScorecardLocation"
type="tns:RepositoryLocation"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DefaultRollupIndicatorLocation"
type="tns:RepositoryLocation"/>
    <xs:element minOccurs="0" maxOccurs="1" name="PreQueryTransforms"
type="tns:ArrayOfGridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="1" name="PostQueryTransforms"
type="tns:ArrayOfGridViewTransformReference"/>
  </xs:sequence>
</xs:complexType>
```

```

    <xs:element minOccurs="0" maxOccurs="1" name="PreRenderTransforms"
type="tns:ArrayOfGridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="1" name="PerUserTransforms"
type="tns:ArrayOfGridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="1" name="PageFilters" type="tns:ArrayOfMember"/>
  </xs:sequence>
  <xs:attribute name="ScorecardViewId" xmlns:s1="http://microsoft.com/wsd1/types/"
type="s1:guid" use="required"/>
  <xs:attribute name="Cached" type="xs:boolean" use="required"/>
  <xs:attribute name="CacheExpiration" type="xs:dateTime" use="required"/>
  <xs:attribute name="DefaultRollupIndicatorId" xmlns:s1="http://microsoft.com/wsd1/types/"
type="s1:guid" use="required"/>
  <xs:attribute name="EmptyCell" type="xs:string"/>
  <xs:attribute name="InvalidCell" type="xs:string"/>
  <xs:attribute name="TIFormula" type="xs:string"/>
  <xs:attribute name="TICurrentDateTime" type="xs:string"/>
</xs:complexType>

```

Cells: This is a two dimensional array as defined in the complex type **GridCellSet** (section [2.2.4.101](#)). The array is indexed by two **GridHeaderItem** complex type objects (section [2.2.4.116](#)). One representing a row header and one representing a column header. This element **MUST** contain one **GridCell** complex type object (section [2.2.4.100](#)) for each possible intersection of a row header and a leaf column header.

RootRowHeader: Specifies the root element for the row header tree, as defined in **GridHeaderItem**.

RootColumnHeader: Specifies the root element for the column header tree, as defined in **GridHeaderItem**.

ScorecardLocation: Points to the scorecard object for which the **GridViewData** was created, as defined in the [RepositoryLocation](#) complex type (section [2.2.4.161](#)).

DefaultRollupIndicatorLocation: Points to the default **indicator** for rollup calculated cells, as defined in **RepositoryLocation**.

PreQueryTransforms: Specifies a set of transform operations that are applied to the **GridViewData** just before getting data from the data sources (1) (see **GridViewTransformReference** section [2.2.4.123](#)).

PostQueryTransforms: Specifies a set of transform operations that are applied to the **GridViewData** after getting data from the data sources(1) (see **GridViewTransformReference**).

PreRenderTransforms: Specifies a set of transform operations that are applied to the **GridViewData** prior to rendering the scorecard (see **GridviewTransformReference**). While all the other types of transform operations are applied once when the **GridViewData** is generated, the pre-render and per-user transforms are applied every time the scorecard is rendered, even if the **GridViewData** object is not new.

PerUserTransforms: This element is deprecated and **MUST NOT** be used.

PageFilters: Specifies a collection of members used to slice the scorecard values, as defined in **ArrayOfMember** (section [2.2.4.45](#)).

ScorecardViewId: GUID that identifies the **ConfiguredView** complex type (section [2.2.4.77](#)) instance associated with the scorecard pointed to by **ScorecardLocation**.

Cached: This attribute MUST be **FALSE** if the **GridViewData** is new, or **TRUE** if it was retrieved from a caching mechanism.

CacheExpiration: Specifies when the **GridViewData** object becomes invalid.

DefaultRollupIndicatorId: GUID used as the identifier for the **indicator** that is used by default for rollup calculated cells.

EmptyCell: Specifies the default text used as the display test for empty cells.

InvalidCell: Specifies the default text used as the display test for invalid cells.

TIFormula: Specifies the value passed from an external time intelligence filter connected to the scorecard TI Formula endpoint (see **Scorecard.EndPoints** section [2.2.4.162](#)). If set, it represents the Simple Time Period Specification formula that is used by the scorecard query engine to filter **KpiMeasure** complex types (section [2.2.4.129](#)) uniformly independent of data source. If it is null or empty, the default time intelligence filter of the KPI is applied, if one is defined.

TICurrentDateTime: Specifies the value passed from an external time intelligence filter connected to the scorecard Current Date Time endpoint (see **Scorecard.EndPoints**). If set, it represents the Simple Time Period Specification (STPS) **dateTime** that is used by the scorecard query engine to evaluate **KpiMeasures** that contain a time intelligence filter. If not set, the current date time of the server (2) is used by the scorecard query engine to evaluate **KpiMeasures** if a time intelligence filter is defined.

2.2.4.122 GridViewDefinition

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **GridViewDefinition** complex type specifies the definition of a grid-based scorecard view. The following picture illustrates the role of a **GridViewDefinition** in a scorecard.




Figure 9: GridViewDefinition

The **GridViewDefinition** contains the tree data structures representing all the row and column headers. The row and column header trees **MUST** be accessed by the properties **RootRowHeader** and **RootColumnHeader** respectively.

```
<xs:complexType name="GridViewDefinition" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="CornerCellFormatInfo"
type="tns:GridFormatInfo"/>
    <xs:element minOccurs="0" maxOccurs="1" name="RootRowHeader" type="tns:GridHeaderItem"/>
    <xs:element minOccurs="0" maxOccurs="1" name="RootColumnHeader"
type="tns:GridHeaderItem"/>
    <xs:element minOccurs="1" maxOccurs="1" name="DefaultRollupIndicatorId"
xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DefaultRollupIndicatorLocation"
type="tns:RepositoryLocation"/>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="PreQueryTransforms"
type="tns:GridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="PostQueryTransforms"
type="tns:GridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="PreRenderTransforms"
type="tns:GridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="PerUserTransforms"
type="tns:GridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CellBorderColor" type="tns:GridColor"/>
  </xs:sequence>
  <xs:attribute name="EmptyCell" type="xs:string"/>
  <xs:attribute name="InvalidCell" type="xs:string"/>
  <xs:attribute name="ShowGridLines" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowHiddenHeaders" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowMetricHeaders" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowPlusMinus" type="xs:boolean" use="required"/>
</xs:complexType>
```

CornerCellFormatInfo: Specifies the format applied to the top left cell of the scorecard as defined in the **GridFormatInfo** complex type (section [2.2.4.115](#)).

RootRowHeader: Specifies the root element of the row header tree, as defined in the **GridHeaderItem** complex type (section [2.2.4.116](#)).

RootColumnHeader: Specifies the root element of the column header tree, as defined in **GridHeaderItem**.

DefaultRollupIndicatorId: This attribute is deprecated from the protocol and **MUST NOT** be used.

DefaultRollupIndicatorLocation: Points to the default **indicator** for rollup calculated cells, as defined in the **RepositoryLocation** complex type (section [2.2.4.161](#)).

PreQueryTransforms: This attribute is deprecated from the protocol and **MUST NOT** be used.

PostQueryTransforms: This attribute is deprecated from the protocol and **MUST NOT** be used.

PreRenderTransforms: This attribute is deprecated from the protocol and **MUST NOT** be used.

PerUserTransforms: This attribute is deprecated from the protocol and **MUST NOT** be used.

CellBorderColor: Specifies the border color applied to scorecard cells, as defined in the **GridColor** complex type (section [2.2.4.102](#)).

EmptyCell: Specifies the string that needs to be displayed in empty scorecard cells. The cells are left empty when this property is **null** or empty.

InvalidCell: Specifies the string that needs to be displayed in invalid scorecard cells. The default value for this property is "Error".

ShowGridLines: This attribute MUST be **TRUE** if the scorecard grid lines are displayed; otherwise, this attribute is **FALSE**.

ShowHiddenHeaders: This attribute MUST be **TRUE** if the hidden headers (see **GridViewHeaderItem.IsHidden**) are displayed; otherwise, this attribute is **FALSE**.

ShowMetricHeaders: This attribute MUST be **TRUE** if the metric headers are displayed; otherwise, this attribute is **FALSE**.

ShowPlusMinus: This attribute MUST be **TRUE** if the expand/collapse signs are displayed; otherwise, this attribute is **FALSE**.

2.2.4.123 GridViewTransformReference

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **GridViewTransformReference** complex type specifies one transform operation to be applied to a **GridViewData** complex type (section [2.2.4.121](#)) instance.

```
<xs:complexType name="GridViewTransformReference"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Parameters" type="tns:PropertyBag"/>
  </xs:sequence>
  <xs:attribute name="Id" type="xs:string"/>
</xs:complexType>
```

Parameters: Represents a general property bag, as defined in the **PropertyBag** complex type (section [2.2.4.158](#)). The **Parameters** property MAY be null or empty. If the transformation associated with the **GridViewTransformReference** complex type (section [2.2.4.123](#)) requires any specific information, the **Parameters** property MUST contain that information.

Id: Specifies the transformation associated with the **GridViewTransformReference**. It MUST NOT be null or empty. It MUST be one of the transformations registered on the server (2). [<16>](#)

2.2.4.124 Hierarchy

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **Hierarchy** complex type specifies a hierarchy. It extends the complex type **NameInfo** (section [2.2.4.149](#)).

```
<xs:complexType name="Hierarchy" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:NameInfo">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Levels" type="tns:ArrayOfLevel"/>
      </xs:sequence>
      <xs:attribute name="DefaultMemberName" type="xs:string"/>
      <xs:attribute name="DimensionUniqueName" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

```

    <xs:attribute name="DisplayFolder" type="xs:string"/>
    <xs:attribute name="HierarchyOrigin" type="tns:HierarchyOrigin" use="required"/>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

Levels: An array of **Level** complex type objects (section [2.2.4.131](#)) in the hierarchy.

DefaultMemberName: The unique name of the hierarchy's default member.

DimensionUniqueName: The parent dimension (1) (see **Dimension** complex type section [2.2.4.90](#)) name of the hierarchy.

DisplayFolder: The **display folder** of the hierarchy.

HierarchyOrigin: The hierarchy structure, as defined by the **HierarchyOrigin** simple type (section [2.2.5.27](#)).

2.2.4.125 Indicator

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A set of visualizations that represent how the actual value of a KPI compares against its target value.

```

<xs:complexType name="Indicator" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:FirstClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="NoDataIndicatorBand"
type="tns:IndicatorBand"/>
        <xs:element minOccurs="0" maxOccurs="1" name="IndicatorBands"
type="tns:ArrayOfIndicatorBand"/>
      </xs:sequence>
      <xs:attribute name="IndicatorType" type="tns:IndicatorType" use="required"/>
      <xs:attribute name="IsBuiltIn" type="xs:boolean" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

NoDataIndicatorBand: The [IndicatorBand](#) element that is used when the KPI contains no data. It MUST exist.

IndicatorBands: An array of IndicatorBand elements that represent different ranges of values for a KPI.

- The array MUST exist.
- If **IndicatorType** is set to "Standard", there MUST be at least two and no more than ten indicator bands.
- If **IndicatorType** is set to "Centered", there MUST be an even number of indicator bands that counts at least four and no more than 20.

IndicatorType: The type of **indicator** as specified by [IndicatorType](#).

IsBuiltIn: A Boolean that specifies whether the **indicator** was shipped with the product or not. A value of **true** means the **indicator** was shipped with the product. A value of **false** means that it is a custom **indicator** created by a user.

2.2.4.126 IndicatorBand

Namespace: http://www.microsoft.com/performancepoint/scorecards

This is a visualization representing one state of an **indicator**.

```
<xs:complexType name="IndicatorBand" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="ImageData" type="xs:string"/>
  </xs:sequence>
  <xs:attribute name="Color" type="xs:string"/>
  <xs:attribute name="BackColor" type="xs:string"/>
  <xs:attribute name="ToolTip" type="xs:string"/>
</xs:complexType>
```

ImageData: A base-64 encoded string converted from a stream of the **Portable Network Graphics (PNG)** image file representing this indicator state.

- The PNG file stream that **ImageData** originates from MUST NOT exceed 512,000 bytes in length.
- Both the height and the width of the PNG image MUST NOT exceed 256 pixels.

Color: A string converted from a 24-bit color that represents this **indicator** state when it is shown as text. The string MUST be formatted as "#RRGGBB".

- **RR** – A two-digit hexadecimal value that indicates the amount of red light in the color. For example, #FF0000 defines the color red.
- **GG** – A two-digit hexadecimal value that indicates the amount of green light in the color. For example, #00FF00 defines the color green.
- **BB** – A two-digit hexadecimal value that indicates the amount of blue light in the color. For example, #0000FF defines the color blue.

BackColor: A string converted from a 24-bit color that represents this indicator state in visualizations where images or text cannot be displayed, such as in strategy maps. The string MUST be formatted as "#RRGGBB".

- **RR** – A two-digit hexadecimal value that indicates the amount of red light in the color. For example, #FF0000 defines the color red.
- **GG** – A two-digit hexadecimal value that indicates the amount of green light in the color. For example, #00FF00 defines the color green.
- **BB** – A two-digit hexadecimal value that indicates the amount of blue light in the color. For example, #0000FF defines the color blue.

ToolTip: A string containing the ToolTip for this **IndicatorBand**. The length MUST NOT exceed 1000 characters.

2.2.4.127 Item

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Represents a key-value pair in a **SerializableDictionary** (section [2.2.4.164](#)).

```
<xs:complexType name="Item" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Key" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Value" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Key: Specifies the string key used for addressing the **Value** element content.

Value: Specifies the element associated with the **Key**. It MUST be of complex type **MemberSetFormula** (section [2.2.4.145](#)), **MemberList** (section [2.2.4.135](#)), or **Member** (section [2.2.4.134](#)).

The **Key** and **Value** elements MUST conform to the following:

- For each **Key**, there MUST be an associated **Value**.
- Each **Key** MUST be unique and MUST NOT be **null**.

Each **Value** MUST NOT be **null**.

2.2.4.128 Kpi

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A key performance indicator (KPI) is contained in a scorecard.

```
<xs:complexType name="Kpi" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:FirstClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Actuals" type="tns:ArrayOfKpiMeasure"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Targets" type="tns:ArrayOfTarget"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Actuals: An array of **KpiMeasure** (see section [2.2.4.129](#)) elements. The array MUST exist and MUST contain at least one **KpiMeasure**.

Targets: An array of **Target** (see section [2.2.4.170](#)) elements.

2.2.4.129 KpiMeasure

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **KpiMeasure** complex type is contained in a KPI.


```

<xs:complexType name="KpiMeasure" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SecondClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="OwnerKpiLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DefaultDimensionSettings"
type="tns:ArrayOfDefaultDimensionSetting"/>
        <xs:element minOccurs="0" maxOccurs="1" name="OverrideFormatProperties"
type="tns:KpiNumberFormatProperties"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CalcFormulaInfo"
type="tns:CalculatedFormulaInfo"/>
      </xs:sequence>
      <xs:attribute name="AggregateBy" type="tns:AggregateTypeEnum" use="required"/>
      <xs:attribute name="DisableScorecardFilters" type="xs:boolean" use="required"/>
      <xs:attribute name="ModelCurrent" type="xs:decimal" use="required"/>
      <xs:attribute name="Pattern" type="tns:KpiPattern" use="required"/>
      <xs:attribute name="CurrentFormula" type="xs:string"/>
      <xs:attribute name="IsCustomCurrentFormula" type="xs:boolean" use="required"/>
      <xs:attribute name="OdbcQuery" type="xs:string"/>
      <xs:attribute name="OverrideHoverText" type="xs:string"/>
      <xs:attribute name="TimeFilterFormula" type="xs:string"/>
      <xs:attribute name="ValueSource" type="tns:ValueSources" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

OwnerKpiLocation: The location of the parent **Kpi** complex type (section [2.2.4.128](#)), as specified by the **RepositoryLocation** complex type (see section [2.2.4.161](#)). Upon successful **Kpi** creation, the server (2) MUST set this value to a **RepositoryLocation**, whose **ItemUrl** field matches the location of the parent **Kpi**.

DataSourceLocation: The location of the **DataSource** complex type (section [2.2.4.85](#)), as specified by **RepositoryLocation**. For **CalcFormulaInfo** to apply to the measure query, **DataSourceLocation.ItemUrl** MUST be empty.

DefaultDimensionSettings: An array of **DefaultDimensionSetting** complex types (section [2.2.4.87](#)) which represent the dimension (1) slices to apply to the measure query.

OverrideFormatProperties: This allows for custom formatting of measure values, as specified by **KpiNumberFormatProperties** (section [2.2.4.130](#)).

CalcFormulaInfo: A calculated formula to apply to the measure query, as specified by **CalculatedFormulaInfo** (section [2.2.4.74](#)). For this formula to apply, **DataSourceLocation.ItemUrl** MUST be empty.

AggregateBy: The aggregation method to apply to the measure query, as specified by **AggregateTypeEnum** (section [2.2.5.1](#)).

DisableScorecardFilters: A value of **TRUE** indicates that scorecard filters are disabled for the measure query; a value of **FALSE** indicates that scorecard filters are enabled for the measure query.

ModelCurrent: The fixed value of the **KpiMeasure**.

- **DataSourceLocation.ItemUrl** MUST equal `"/%%fixedvalues%%"` for **ModelCurrent** to be used.

Pattern: The pattern this **KpiMeasure** follows, as specified by the **KpiPattern** simple type (section [2.2.5.32](#)). Banding and scoring behave differently with different patterns.

CurrentFormula: The MDX formula or **tuple** used to retrieve the current value.

- If **IsCustomCurrentFormula** is set to **TRUE**, the value **MUST** have one or more non-whitespace characters.
- If **IsCustomCurrentFormula** is set to **FALSE**, the value is ignored.
- **MUST** be a valid MDX formula or tuple if **DataSource.SourceName** (see section [2.2.4.85](#)) equals "ADOMD.NET".
- The length **MUST NOT** exceed 4,000 characters.

IsCustomCurrentFormula: A value of **TRUE** indicates that **CurrentFormula** is used to compute the current value; a value of **FALSE** indicates that **CurrentFormula** is ignored.

- **DataSource.SourceName** **MUST** equal "ADOMD.NET" for **IsCustomCurrentFormula** to be used.

OdbcQuery: This attribute is deprecated from the protocol and **MUST NOT** be used.

OverrideHoverText: A descriptive string meant for the user. The length **MUST NOT** exceed 256 characters.

TimeFilterFormula: The time intelligence formula to apply to the measure query. The length **MUST NOT** exceed 4,000 characters.

ValueSource: The rollup method to apply to the source data, as specified by the **ValueSources** simple type (section [2.2.5.51](#)).

2.2.4.130 KpiNumberFormatProperties

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Used for custom formatting of KPI measure values.

```
<xs:complexType name="KpiNumberFormatProperties" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="Multiplier" type="xs:decimal" use="required"/>
  <xs:attribute name="FormatType" type="tns:FormatType" use="required"/>
  <xs:attribute name="CurrencySymbol" type="xs:string"/>
  <xs:attribute name="DecimalPlaces" type="xs:int" use="required"/>
  <xs:attribute name="NegativeSymbol" type="tns:FormatNegativeSymbol" use="required"/>
  <xs:attribute name="ShowZeroAs" type="xs:string"/>
  <xs:attribute name="UseThousandsSeparator" type="xs:boolean" use="required"/>
  <xs:attribute name="AdditionalTextLeft" type="xs:string"/>
  <xs:attribute name="AdditionalTextRight" type="xs:string"/>
</xs:complexType>
```

Multiplier: The multiplier value used to convert the original value to a different scale.

FormatType: The formatting pattern used for number formatting, as specified by **FormatType** (see section [2.2.5.23](#)).

CurrencySymbol: The currency symbol used for number formatting.

DecimalPlaces: The number of decimal places used for number formatting. The value MUST NOT be less than 0 and MUST NOT be greater than 28.

NegativeSymbol: The representation of negative values used for number formatting, as specified by `FormatNegativeSymbol` (see section [2.2.5.22](#)).

ShowZeroAs: The string used, if its length is greater than 0 characters, to express a value of 0; otherwise, 0 will be formatted as a number, as specified in **FormatType** (section [2.2.5.23](#)). The length MUST NOT exceed 8 characters.

UseThousandsSeparator: A value of **true** indicates that a thousands separator is enabled for number formatting; a value of **false** indicates it is disabled.

AdditionalTextLeft: The string added to the left of the formatted number. The length MUST NOT exceed 8 characters.

AdditionalTextRight: The string added to the right of the formatted number. The length MUST NOT exceed 8 characters.

2.2.4.131 Level

Namespace: `http://www.microsoft.com/performancepoint/scorecards`

This complex type specifies a level. It extends the complex type **NameInfo** (section [2.2.4.149](#)).

```
<xs:complexType name="Level" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:NameInfo">
      <xs:attribute name="DimensionUniqueName" type="xs:string"/>
      <xs:attribute name="HierarchyUniqueName" type="xs:string"/>
      <xs:attribute name="IsAllLevel" type="xs:boolean" use="required"/>
      <xs:attribute name="LevelNumber" type="xs:int" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

DimensionUniqueName: The unique name of the dimension (1) for the level.

HierarchyUniqueName: The unique name of the hierarchy for the level.

IsAllLevel: This attribute MUST be **true** if this Level is the level that unites all the members of the dimension (1) or hierarchy into one element at the top of the dimension (1) or hierarchy; otherwise, **false**.

LevelNumber: The numeric representation of the level depth in the dimension (1) or hierarchy that the level represents. The value MUST NOT be less than 0. Zero means this level is the root level in the dimension (1) or hierarchy. If set to 1, this member is at the first level of the dimension (1) or hierarchy, 2 indicates that the member is at the second level of the dimension (1) or hierarchy, and so on.

2.2.4.132 MDXParameterDefinition

Namespace: `http://www.microsoft.com/performancepoint/scorecards`

The **MDXParameterDefinition** is a complex type that specifies a custom MDX used to retrieve data.

```

<xs:complexType name="MDXParameterDefinition" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Expression" type="xs:string"/>
  </xs:sequence>
</xs:complexType>

```

Expression: A string representing an MDX.

2.2.4.133 Measure

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **Measure** complex type specifies a measure. It extends the complex type **NameInfo** (section [2.2.4.149](#)).

```

<xs:complexType name="Measure" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:NameInfo">
      <xs:attribute name="AggregatorValue" type="xs:int" use="required"/>
      <xs:attribute name="MeasureGroup" type="xs:string"/>
      <xs:attribute name="DisplayFolder" type="xs:string"/>
      <xs:attribute name="HierarchyName" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

AggregatorValue: The numeric value representing the aggregation type for this measure as defined in the MEASURE_AGGREGATOR column of the MDSHEMA_MEASURES rowset in [\[MS-SSAS\]](#) section 3.1.4.2.2.1.3.9.1.

MeasureGroup: The name of the measure group which contains this measure.

DisplayFolder: The name of the display folder for this measure.

HierarchyName: The unique name of the hierarchy of this measure.

2.2.4.134 Member

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **Member** complex type represents an OLAP member in a **Dimension** complex type (section [2.2.4.90](#)).

```

<xs:complexType name="Member" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="MemberOperation"
type="tns:MemberOperation"/>
  </xs:sequence>
  <xs:attribute name="Caption" type="xs:string"/>
  <xs:attribute name="UniqueName" type="xs:string"/>
  <xs:attribute name="HierarchyPath" type="xs:string"/>
  <xs:attribute name="LevelName" type="xs:string"/>
  <xs:attribute name="DimensionName" type="xs:string"/>
  <xs:attribute name="LevelDepth" type="xs:int" use="required"/>
  <xs:attribute name="ChildCount" type="xs:long" use="required"/>

```

```

<xs:attribute name="IsChildCountReal" type="xs:boolean" use="required"/>
<xs:attribute name="IsAllLevel" type="xs:boolean" use="required"/>
<xs:attribute name="DimensionUniqueName" type="xs:string"/>
<xs:attribute name="MemberType" type="tns:MemberType" use="required"/>
</xs:complexType>

```

MemberOperation: The **MemberOperation** complex type (section [2.2.4.136](#)) for this member (3).

Caption: The display name for this member (3).

UniqueName: The unique name for this member (3).

HierarchyPath: The hierarchy tree path of this member (3).

LevelName: The unique name of the level for this member (3).

DimensionName: The unique name of the dimension (1) that this member (3) belongs to.

LevelDepth: The numeric value of the level depth in the **Hierarchy** (section [2.2.4.124](#)) that this member belongs to. Zero indicates that this member is at the root level in the hierarchy. If set to 1, this member is at the first level of the hierarchy, 2 indicates that the member is at the second level of the hierarchy, and so on.

ChildCount: The number of child members (3) of this member (3).

IsChildCountReal: This attribute MUST be **FALSE** if the **ChildCount** property is an estimate, or **TRUE** if it is the actual number. This property is used to monitor whether the **ChildCount** property is up-to-date. This property is set by the client.

IsAllLevel: This attribute MUST be **TRUE** if the level that this member (3) belongs to is the level that unites all the members (3) of the hierarchy into one element at the top of the hierarchy; otherwise, this attribute is **FALSE**.

DimensionUniqueName: The unique name of the **Dimension** for this member (3).

MemberType: The **MemberType** simple type (section [2.2.5.39](#)) for this member (3).

2.2.4.135 MemberList

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **MemberList** complex type specifies the members (3) of an OLAP hierarchy. This type extends **MemberSet** complex type (section [2.2.4.144](#)), and can be used with any axis type.

```

<xs:complexType name="MemberList" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:MemberSet">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="memberList" type="tns:ArrayOfString"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

memberList: An array of strings representing the members of an OLAP hierarchy. This MUST conform to the schema of complex type **ArrayOfString** complex type (section [2.2.4.54](#)). Each string in the list represents the **UniqueName** string property of an OLAP **Member** complex type (section [2.2.4.134](#)).

2.2.4.136 MemberOperation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Represents the basic [member](#) operations that can be performed on an OLAP dimension (1) member. MemberOperation abstract type is the base class for [MemberOperationAllDescendants](#), [MemberOperationChildren](#), [MemberOperationDescendants](#), [MemberOperationDrillUp](#), [MemberOperationHide](#) and [MemberOperationLeafDescendants](#).

```
<xs:complexType name="MemberOperation" abstract="true"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

2.2.4.137 MemberOperationAllDescendants

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A **MemberOperation** complex type (section [2.2.4.136](#)) that represents all descendants of a referred [member](#) in the [dimension hierarchy](#). This type extends **MemberOperation**.

```
<xs:complexType name="MemberOperationAllDescendants"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:MemberOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.138 MemberOperationChildren

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A [MemberOperation](#) that represents all child members of a referred [member](#) in a [dimension hierarchy](#). This type extends MemberOperation.

```
<xs:complexType name="MemberOperationChildren" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:MemberOperation"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.139 MemberOperationDescendants

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A [MemberOperation](#) that represents all descendants of a referred [member](#) at a specified level in the [hierarchy](#). This type extends MemberOperation.

```
<xs:complexType name="MemberOperationDescendants"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<xs:complexContent mixed="false">
  <xs:extension base="tns:MemberOperation">
    <xs:attribute name="LevelUniqueName" type="xs:string"/>
    <xs:attribute name="LevelDisplayName" type="xs:string"/>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

LevelUniqueName: The unique name of a [level](#) in the [dimension](#) hierarchy.

LevelDisplayName: The display name of a level (see section [2.2.4.131](#)) in a dimension (see section [2.2.4.90](#)) hierarchy (see section [2.2.4.124](#)).

2.2.4.140 MemberOperationDrillUp

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A [MemberOperation](#) that represents the parent of a referred [member](#). This type extends MemberOperation.

```

<xs:complexType name="MemberOperationDrillUp" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:MemberOperation"/>
  </xs:complexContent>
</xs:complexType>

```

2.2.4.141 MemberOperationHide

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A [MemberOperation](#) that hides a referred [member](#). This type extends MemberOperation.

```

<xs:complexType name="MemberOperationHide" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:MemberOperation"/>
  </xs:complexContent>
</xs:complexType>

```

2.2.4.142 MemberOperationLeafDescendants

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A [MemberOperation](#) that represents all descendants of a referred [member](#) that are also leaf members in the [dimension hierarchy](#). This type extends MemberOperation.

```

<xs:complexType name="MemberOperationLeafDescendants"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:MemberOperation"/>
  </xs:complexContent>
</xs:complexType>

```

2.2.4.143 MemberParameterDefinition

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **MemberParameterDefinition** is a complex type that represents a group of members (3) used to retrieve data.

```
<xs:complexType name="MemberParameterDefinition" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Dimension" type="tns:Dimension"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Members" type="tns:ArrayOfMember"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DefaultMembers" type="tns:ArrayOfMember"/>
  </xs:sequence>
</xs:complexType>
```

Dimension: A **Dimension** (see section [2.2.4.90](#)) representing the dimension (1) for the group of associated (or related) members (3).

Members: The group of members (3) used to identify the data to be retrieved.

DefaultMembers: An **ArrayOfMember** (see section [2.2.4.45](#)) object representing the list (1) of default members (3) for a specified dimension (1).

2.2.4.144 MemberSet

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the properties of a OLAP member hierarchy.

```
<xs:complexType name="MemberSet" abstract="true" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="FilterEmpty" type="xs:boolean" use="required"/>
  <xs:attribute name="HierarchyType" type="tns:HierarchyType" use="required"/>
  <xs:attribute name="Hierarchize" type="xs:boolean" use="required"/>
  <xs:attribute name="Distinct" type="xs:boolean" use="required"/>
  <xs:attribute name="HierarchyName" type="xs:string"/>
</xs:complexType>
```

FilterEmpty: This attribute MUST be present and MUST be **true** if the FILTER function MUST be used in the MDX query; otherwise, **false**.

HierarchyType: This attribute MUST be present. It specifies the type of the hierarchy that the members belong to. It MUST conform to the schema of **HierarchyType** (section [2.2.5.28](#)) simple type.

Hierarchize: This attribute MUST be present and MUST be **true** if the HIERARCHIZE function MUST be used in the MDX query; otherwise, **false**.

Distinct: This attribute MUST be present and MUST be **true** if the DISTINCT function MUST be used in the MDX query; otherwise, **false**.

HierarchyName: This attribute MUST NOT be **null**. It specifies the unique name of the hierarchy.

2.2.4.145 MemberSetFormula

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies a collection of operations on the members (3) of a OLAP hierarchy. This type extends [MemberSet](#) and can be used with any axis type.

```
<xs:complexType name="MemberSetFormula" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:MemberSet">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Operations"
type="tns:ArrayOfSetOperation"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Operations: This element MUST NOT be **null**. It contains a collection of elements of complex type **SetOperation** (section [2.2.4.165](#)) that specify the operations on the members of the hierarchy.

2.2.4.146 MemberTransform

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Represents a transform, such as drilldown, applied to a [member](#), [hierarchy](#) group or [KPI](#).

```
<xs:complexType name="MemberTransform" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="GroupId" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CellPath" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Type" type="tns:MemberTransformType"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Operation"
type="tns:MemberTransformOperation"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CustomData" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

GroupId: The string representing a hierarchy group identifier.

CellPath: The location of the member inside the hierarchy group.

Type: The [MemberTransformType](#) of the **MemberTransform**.

Operation: The [MemberTransformOperation](#) of the **MemberTransform**.

CustomData: Specifies additional data related to the **MemberTransform**. This element MUST be present. This element MUST NOT be empty. The content of **CustomData** is dependent on the Operation of the **MemberTransform** as designated in the following table.

Operation	Content
Replace	CustomData MUST be an instance of ArrayOfMember .
DrillUp, DrillDown, or Expand	CustomData MUST be an instance of DataSource .

2.2.4.147 NamedSet

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

An OLAP named set.

```
<xs:complexType name="NamedSet" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Dimensions" type="tns:ArrayOfString"/>
  </xs:sequence>
  <xs:attribute name="Name" type="xs:string"/>
  <xs:attribute name="Expression" type="xs:string"/>
  <xs:attribute name="DisplayFolder" type="xs:string"/>
</xs:complexType>
```

Dimensions: The list (1) of dimensions (section [2.2.4.90](#)) used in the named set, using the `Dimension.UniqueName` property. It MUST conform to the schema of the **ArrayOfString** (section [2.2.4.54](#)) complex type.

Name: The display name for the named set.

Expression: The MDX for this named set.

DisplayFolder: Where the named set appears in a hierarchical view of named sets.

2.2.4.148 NamedSetParameterDefinition

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **NamedSetParameterDefinition** is a complex type representing a set of members (3) used to retrieve data.

```
<xs:complexType name="NamedSetParameterDefinition"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Expression" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Name: A display name for the named set.

Expression: The MDX representing a set of members (3) used to retrieve data.

2.2.4.149 NameInfo

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **NameInfo** complex type specifies the names and the description of a cube, dimension (1), hierarchy, level, or measure. It is the base type for the complex types **Cube** (section [2.2.4.78](#)), **Dimension** (section [2.2.4.90](#)), **Hierarchy** (section [2.2.4.124](#)), **Level** (section [2.2.4.131](#)), and **Measure** (section [2.2.4.133](#)).

```
<xs:complexType name="NameInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="DisplayName" type="xs:string"/>
  <xs:attribute name="UniqueName" type="xs:string"/>
  <xs:attribute name="Description" type="xs:string"/>
</xs:complexType>
```

DisplayName: The display name of the cube, dimension, hierarchy, level, or measure.

UniqueName: The unique name of the cube, dimension, hierarchy, level, or measure.

Description: The description of the cube, dimension, hierarchy, level, or measure.

2.2.4.150 NumericFormat

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **NumericFormat** is a complex type that represents the numeric format setting for an Analysis Services measure numeric value within an analytic grid report.

```
<xs:complexType name="NumericFormat" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="MemberName" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FormatType" type="tns:FormatType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CurrencySymbol" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="DecimalPlaces" type="xs:int"/>
    <xs:element minOccurs="1" maxOccurs="1" name="NegativeSymbol"
type="tns:FormatNegativeSymbol"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ShowZeroAs" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="UseThousandsSeparator" type="xs:boolean"/>
    <xs:element minOccurs="0" maxOccurs="1" name="AdditionalTextLeft" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="AdditionalTextRight" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

MemberName: The Analysis Services measure name to which this numeric formatting is being applied.

FormatType: The formatting pattern used for number formatting, as specified by **FormatType** (see section [2.2.5.23](#)).

CurrencySymbol: The currency symbol for number formatting.

DecimalPlaces: The number of trailing decimal places used for number formatting. The value MUST NOT be less than 0 and MUST NOT be greater than 30.

NegativeSymbol: The representation of negative values used for number formatting.

ShowZeroAs: The string used, if its length is greater than 0 characters, to express the value of 0; otherwise formatted as a number.

UseThousandsSeparator: A value of **true** indicates that a thousands separator is enabled for number formatting; a value of **false** indicates it is disabled.

AdditionalTextLeft: The text added to the left of the formatted number.

AdditionalTextRight: The text added to the right of the formatted number.

2.2.4.151 NumericFormatsHashtable

Namespace: http://www.microsoft.com/performancepoint/scorecards

An array of **NumericFormat** objects.

```
<xs:complexType name="NumericFormatsHashtable" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="NumericFormat"
type="tns:NumericFormat"/>
  </xs:sequence>
</xs:complexType>
```

NumericFormat: This element MUST NOT be null and MUST conform to the schema of the **NumericFormat** (see section [2.2.4.150](#)) complex type.

2.2.4.152 OLAPQueryData

Namespace: <http://performancepoint.microsoft.com/OLAPQueryData>

Represents an analytic query.

```
<xs:complexType name="OLAPQueryData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Parameters" type="tns:ArrayOfParameter"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
    <xs:element minOccurs="0" maxOccurs="1" name="MDX" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Parameters: An **ArrayOfParameters** collection (see section [2.2.4.49](#)) containing all the user-defined parameters for the current query as well as their default values. It MUST NOT be null. If there are no user-defined parameters, it MUST be empty.

DataSourceLocation: A **RepositoryLocation** object (see section [2.2.4.161](#)) that specifies the location on the server (2) of the data source object associated with this query. It MUST NOT be null.

MDX: The MDX query used to generate data for the analytic report. It MUST NOT be null or empty. Any parameters from the **Parameters** collection used in this query MUST be denoted using left and right angle brackets. For example, a parameter named *ParameterName* MUST be included as `<<ParameterName>>`.

2.2.4.153 OLAPReportView

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **OLAPReportView** complex type contains all the state information for an analytic report.

```
<xs:complexType name="OLAPReportView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="QueryData" type="qdata:OLAPQueryData"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ReportViewData" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ParentReportViewLocation"
type="tns:RepositoryLocation"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ShowInformationBar" type="xs:boolean"/>
    <xs:element minOccurs="0" maxOccurs="1" name="QueryState" type="query:QueryState"/>
  </xs:sequence>
  <xs:attribute name="MeasureGroupName" type="xs:string"/>
  <xs:attribute name="Caption" type="xs:string"/>
  <xs:attribute name="Description" type="xs:string"/>
</xs:complexType>
```

```
<xs:attribute name="FormatDimensionUniqueName" type="xs:string"/>
</xs:complexType>
```

QueryData: An **OLAPQueryData** complex type object (section [2.2.4.152](#)) that specifies data source information and user-defined parameters. It MUST NOT be null. Either this object or the **QueryState** complex type object (section [2.2.4.159](#)) MUST be populated to represent the query for the report.

ReportViewData: Specifies view data for the current report. It MUST be XML that can **deserialize** into an object that inherits from the **AnalyticBaseReportViewData** complex type (section [2.2.4.14](#)). It MUST NOT be null or empty. See also the complex types **AnalyticChartReportView** (section [2.2.4.16](#)) and **AnalyticGridReportView** (section [2.2.4.17](#)), which both inherit from **AnalyticBaseReportViewData**.

ParentReportViewLocation: A **RepositoryLocation** complex type object (section [2.2.4.161](#)) that specifies the location of the parent report on the server (2). It MUST NOT be null. It SHOULD be empty to indicate that there is no parent report. It MUST contain the location of a report on the server (2) if the method **SaveTemporaryAnalyticReport** is being called (section [3.1.4.65](#)).

ShowInformationBar: Specifies whether to display an information bar along the top of the report view.

QueryState: A **QueryState** object that specifies the current data query. It MUST NOT be null. Either this object or the **QueryData** object MUST be populated to represent the query for the report. If this object is used, the **IsEnabled** property MUST be set to **TRUE**. If both **QueryData** and **QueryState** are populated and **QueryState.IsEnabled** is **TRUE**, the **QueryState** object will be used to run the query. If **QueryState.IsEnabled** is **FALSE**, the **QueryData** object will be used to run the query.

MeasureGroupName: Specifies the measure group that was selected when the report was last modified.

Caption: Specifies the text that is displayed in the caption for the report.

Description: This attribute is deprecated from the protocol and MUST NOT be used.

FormatDimensionUniqueName: Specifies a text name that uniquely identifies the dimension (1) to use to obtain data formatting information for this report.

2.2.4.154 Parameter

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies a logical element of an analytic query whose value can be changed independently of the analytic query.

```
<xs:complexType name="Parameter" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="DefaultValue" type="xs:string"/>
  </xs:sequence>
  <xs:attribute name="Name" type="xs:string"/>
</xs:complexType>
```

DefaultValue: The string value that the parameter will use by default.

Name: A string that uniquely identifies the parameter within its parent, `ArrayOfParameter` (see section [2.2.4.49](#)). It MUST NOT contain a left-angle bracket (<) or a right-angle bracket (>).

2.2.4.155 ParameterDefinition

Namespace: `http://www.microsoft.com/performancepoint/scorecards`

This class represents the non visual portion of the metadata to describe a parameter. This class carries the state necessary to generate a parameter list representing possible connections that can be originated from a first-class element.

```
<xs:complexType name="ParameterDefinition" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="ParameterUniqueName" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DisplayValues">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded"
            namespace="http://www.w3.org/2001/XMLSchema" processContents="lax"/>
          <xs:any minOccurs="1" namespace="urn:schemas-microsoft-com:xml-diffgram-v1"
            processContents="lax"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element minOccurs="0" maxOccurs="1" name="CustomDefinition" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ParameterProviderId" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DisplayName" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="EmitterType"
      type="tns:BeginPointEmitterType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="KeyColumn" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ParentKeyColumn" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DisplayColumn" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="IsDefaultColumn" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DefaultPostFormula" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

ParameterUniqueName: The unique name of the parameter.

DisplayValues: The **DataTable** (as described in [\[DataTable\]](#)) containing **DataColumn** definitions that define the parameter outputs of a data source. A **DataColumn** that is a parameter output MUST contain a **ShowColumn** extended property and its value MUST be **true** using the format specified in [\[MS-DSDIFFGRAM\]](#), section [2.3.2](#). A column definition that is a parameter output not to be used for configuring conditional visibility MUST contain a **NotShowColumnForCondVisibility** extended property and its value MUST be **true** using the format specified in [\[MS-DSDIFFGRAM\]](#), section [2.3.2](#).

CustomDefinition: A serialized object or string value. If the value of **ParameterProviderId** is in the **ParameterProviderId** table, the value of **CustomDefinition** MUST be the corresponding chart value or serialized object. If the value for **ParameterProviderId** is not in the chart, **CustomDefinition** can be any string.

ParameterProviderId: The identifier of the data provider for the value or serialized object in **CustomDefinition**.

ParameterProviderId	CustomDefinition
MDXParameterDataProvider	A MdxParameterDefinition object.
MemberParameterDataProvider	A MemberParameterDefinition object.
NamedSetParameterDataProvider	A NamedSetParameterDefinition object.
ParameterScorecardCellProvider	"BeginPoint_ScorecardCell"
ParameterScorecardColumnMemberProvider	"BeginPoint_ScorecardColumnMember"
ParameterScorecardKpiProvider	"BeginPoint_Kpi"
ParameterScorecardRowMemberProvider	"BeginPoint_ScorecardRowMember"
TimeIntelligencePostFormulaProvider	A TimeIntelligencePostFormulaDefinition object.
TimeIntelligenceProvider	A TimeIntelligenceDefinition object.

DisplayName: The display name of the parameter.

EmitterType: A [BeginPointEmitterType](#) object that specifies the type of information the parameter emits.

KeyColumn: The column name containing the key identifier for the parameter values.

ParentKeyColumn: The column name containing the parent key column.

DisplayColumn: The column name containing the display name of the parameter values.

IsDefaultColumn: The column name containing the Boolean value that indicates the row is a default selection of the parameter values.

DefaultPostFormula: The default post formula for this parameter as defined in [\[MSFT-ConnectionFormula\]](#).

2.2.4.156 ParameterMapping

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Provides the mapping information between a **ParameterDefinition** (section [2.2.4.155](#)) and a **DashboardItem** (section [2.2.4.83](#)).

```
<xs:complexType name="ParameterMapping" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="ConditionalData">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded"
            namespace="http://www.w3.org/2001/XMLSchema" processContents="lax"/>
          <xs:any minOccurs="1" namespace="urn:schemas-microsoft-com:xml-diffgram-v1"
            processContents="lax"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="EndPointUniqueName" type="xs:string"/>
</xs:complexType>
```

```

    <xs:attribute name="Id" xmlns:s1="http://microsoft.com/wsd/types/" type="s1:guid"
    use="required"/>
    <xs:attribute name="SourceColumnName" type="xs:string"/>
    <xs:attribute name="DashboardItemId" xmlns:s1="http://microsoft.com/wsd/types/"
    type="s1:guid" use="required"/>
    <xs:attribute name="ParameterUniqueName" type="xs:string"/>
    <xs:attribute name="PostFormula" type="xs:string"/>
    <xs:attribute name="IsConditionalDataEnabled" type="xs:boolean" use="required"/>
    <xs:attribute name="IsDefaultVisibility" type="xs:boolean" use="required"/>
</xs:complexType>

```

ConditionalData: The **DataTable** (as described in [\[DataTable\]](#)) containing visibility values that indicate a connected Web Part is visible. The **DataTable** MUST contain a **DataColumn** with name equal to the **KeyColumn** defined in **ParameterDefinition** (section [2.2.4.155](#)) that contains key values. The **DataTable** MUST contain a **DataColumn** with name equal to the **DisplayColumn** defined in **ParameterDefinition** (section [2.2.4.155](#)) that contains display values; otherwise, the first column in the **DataTable** will be used for display values.

EndPointUniqueName: Specifies the unique name of the endpoint for the **DashboardItem** (section [2.2.4.83](#)).

Id: A GUID that marks the mapping relationship.

SourceColumnName: A column name that appears in the return of the query that pulls selected values for the parameter associated with the element identified by **DashboardItemId**.

DashboardItemId: Identifies the **DashboardItem** that is the source of the parameter.

ParameterUniqueName: This attribute MUST equal the **ParameterUniqueName** defined in **ParameterDefinition** (section [2.2.4.155](#)).

PostFormula: A **PostFormula** is a transformation expression that is applied to the selected values passed from a filter or scorecard to consuming report or scorecard as defined in [\[MSFT-ConnectionFormula\]](#).

IsConditionalDataEnabled: This attribute MUST be set to **true** if **ConditionalData** is not null; otherwise, **false**.

IsDefaultVisibility: This attribute MUST be set to **true** if the Web Part is shown as a default, when the provider does not enable any consumers via configured visible values; otherwise, **false**.

2.2.4.157 PasReportViewData

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Contains all the state information for a ProClarity Analytics Server report.

```

<xs:complexType name="PasReportViewData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="ServerUrl" type="xs:string"/>
  <xs:attribute xmlns:s1="http://microsoft.com/wsd/types/" name="PageId" type="s1:guid"
  use="required"/>
  <xs:attribute name="PagePath" type="xs:string"/>
  <xs:attribute name="ConfigOptions" type="xs:string"/>
</xs:complexType>

```

ServerUrl: The URL identifies the ProClarity Analytics Server of the report view.

PageId: The ProClarity Analytics Server report view GUID identifier.

PagePath: The ProClarity Analytics Server report URL path that is relative to the server (2) URL. The absolute URL is the combination of the **ServerUrl** and **PagePath** parts.

ConfigOptions: A list (1) of ProClarity Analytics Server report view configuration options that is included as the "uiConfig" URL parameter query string.

2.2.4.158 PropertyBag

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **PropertyBag** complex type MUST contain a pairing of keys and values.

```
<xs:complexType name="PropertyBag" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Keys" type="tns:ArrayOfString"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Values" type="tns:ArrayOfChoice1"/>
  </xs:sequence>
</xs:complexType>
```

Keys: Key names of type string.

Values: A property chosen from a list (1) of various data types; see [ArrayOfChoice1](#).

2.2.4.159 QueryState

Namespace: http://schemas.microsoft.com/performancepoint/2007/03/query

An alternate representation of a MDX query that includes the member selections of each axis.

```
<xs:complexType name="QueryState" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Axes" type="tns:ArrayOfAxis"/>
    <xs:element minOccurs="1" maxOccurs="1" name="IsEnabled" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="UnknownFilterParameter" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ShowDataSourceFormatting"
      type="xs:boolean"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
      type="tns:RepositoryLocation"/>
  </xs:sequence>
</xs:complexType>
```

Axes: An **ArrayOfAxis** (see section [2.2.4.22](#)) collection that contains the member selections for each axis. It MUST NOT be null.

IsEnabled: Specifies whether the **QueryState** object represents the query for the report. A value of **true** indicates that the **QueryState** object will be used. A value of **false** indicates that the **QueryState** object will not be used.

UnknownFilterParameter: Specifies whether or not an aggregation of multiple members are selected on one of the filter axes. A value of **true** indicates that multiple members are selected on a filter axis. A value of **false** indicates that they are not.

ShowDataSourceFormatting: Specifies whether or not formatting information from the data source is used to determine how to display data. A value of **true** indicates that formatting information from the data source is to be used. A value of **false** indicates that it is not.

DataSourceLocation: A **RepositoryLocation** object (see section [2.2.4.161](#)) that specifies the location on the server (2) of the data source object associated with this query state. It MUST NOT be null.

2.2.4.160 ReportView

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **ReportView** complex type controls the visual display of data in a dashboard and can be coordinated with other report views using filters. Report views include analytic grids and charts, PivotTable and PivotChart reports, Excel spreadsheets [\[MS-XLSX\]](#), SQL Server Reporting Services reports, strategy maps, trend charts, web pages, and custom reports.

```
<xs:complexType name="ReportView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:FirstClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="ScorecardLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CustomData" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="EndPoints" type="tns:ArrayOfEndPoint"/>
        <xs:element minOccurs="0" maxOccurs="1" name="BeginPoints"
type="tns:ArrayOfParameterDefinition"/>
      </xs:sequence>
      <xs:attribute name="TypeName" type="xs:string"/>
      <xs:attribute name="RenderClientSide" type="xs:boolean" use="required"/>
      <xs:attribute name="ConfiguredViewId" xmlns:s1="http://microsoft.com/wsd1/types/"
type="s1:guid" use="required"/>
      <xs:attribute name="SubTypeId" type="xs:string"/>
      <xs:attribute name="RendererClassName" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

ScorecardLocation: This property is only used for strategy map **ReportViews**. It stores the **RepositoryLocation** complex type (section [2.2.4.161](#)) of the Scorecard associated with the strategy map.

CustomData: Specifies custom data for the report view. This element MUST be present. The content of **CustomData** is determined by the **TypeName** of the report view as designated in the following table.

TypeName	Content
AnalyticChart	CustomData MUST contain an OlapReportView complex type object (section 2.2.4.153) serialized as an XML document and XML encoded. The value of the OlapReportView ReportViewData property MUST be an AnalyticChartReportView complex type (section 2.2.4.16) serialized as an XML document.
DecompositionTree	CustomData MUST be ignored.
ExcelService	CustomData MUST contain an ExcelServicesData complex type object

TypeName	Content
	(section 2.2.4.97) serialized as an XML document and XML encoded.
Implementation-specific custom string	CustomData MAY be used depending on the implementation of the third-party report view. The specific content required is defined by the implementer of the custom report view.
KpiDetails	CustomData MUST be ignored.
OLAPDrillThrough	CustomData MUST be ignored.
OLAPGrid	CustomData MUST contain an OlapReportView object serialized as an XML document and XML encoded. The value of the OlapReportView ReportViewData property MUST be an AnalyticGridReportView complex type (section 2.2.4.17) serialized as an XML document.
PasPage	CustomData MUST contain a PasReportViewData complex type (section 2.2.4.157) serialized as an XML document and XML encoded.
PivotChart	CustomData MUST be ignored.
PivotTable	CustomData MUST be ignored.
Spreadsheet	CustomData MUST be ignored.
StrategyMap	CustomData MUST contain a StrategyMapViewData complex type (section 2.2.4.168) serialized as an XML document and XML encoded.
SqlReport	CustomData MUST contain a SqlReportViewData complex type (section 2.2.4.166) serialized as an XML document and XML encoded.
TrendAnalysisChart	CustomData MUST be ignored.
Url	CustomData MUST NOT be null and MUST be a valid RFC1738 URL or a string constant: "about:blank".

EndPoint: Specifies the available connection destinations to filter and control the display of this report view. This element MUST be present. If the **SubTypeId** is not custom and there are no connection destinations, two **Endpoint** complex type (section [2.2.4.95](#)) items will be present for row and column with a category of None. This element MUST conform to the schema of the **ArrayOfEndPoint** complex type (section [2.2.4.33](#)).

BeginPoints: Specifies the available connection sources to filter and set conditions for the display of other reports and scorecards. This element MUST be present. This element MUST conform to the schema of the **ArrayOfParameterDefinition** complex type (section [2.2.4.50](#)).

TypeName: Specifies the name of the report view type. This attribute MUST be present. The content of **TypeName** is determined by the type of the report view as designated in the following table. If the report view is a custom report view, **TypeName** MUST NOT be empty. It MUST NOT be longer than 60 characters. It MUST NOT contain the characters ', ', or \. It MUST NOT be the same as one of the predefined report view types already listed in the following table.

Type	Content
URL	TypeName MUST be "Url".
SQL Report	TypeName MUST be "SqlReport".

Type	Content
Spreadsheet	TypeName MUST be "Spreadsheet".
PivotTable	TypeName MUST be "PivotTable".
PivotChart	TypeName MUST be "PivotChart".
Strategy Map	TypeName MUST be "StrategyMap".
Trend Analysis Chart	TypeName MUST be "TrendAnalysisChart".
Analytic Grid	TypeName MUST be "OLAPGrid".
Analytic Chart	TypeName MUST be "AnalyticChart".
Decomposition Tree Report	TypeName MUST be "DecompositionTree".
Analytic Drill Through report	TypeName MUST be "OLAPDrillThrough".
Excel Services Workbook	TypeName MUST be "ExcelServices".
PAS Page	TypeName MUST be "PasPage".
KPI Detail Page	TypeName MUST be "KpiDetails".

RenderClientSide: If **TRUE**, the report view is rendered on the client. If **FALSE**, the report view is rendered on the server (2).

ConfiguredViewId: Specifies the identity of the **ConfiguredView** complex type (section [2.2.4.77](#)) for this **ReportView**. This element **MUST** be present.

SubTypeId: Specifies the identifier for the type of the report view. This attribute **MUST** be present. The content of **SubTypeId** is determined by the type of the report view, as designated in the following table. If the report view is a custom report view, **SubTypeId** **MUST NOT** be empty. It **MUST NOT** be longer than 60 characters. It **MUST NOT** contain the characters ', ", or \. It **MUST NOT** be the same as one of the predefined report view type's **SubTypeId** already listed in the following table.

Type	Content
URL	SubTypeId MUST be "Url".
SQL Report	SubTypeId MUST be "SqlReport".
Spreadsheet	SubTypeId MUST be "Spreadsheet".
PivotTable	SubTypeId MUST be "PivotTable".
PivotChart	SubTypeId MUST be "PivotChart".
Strategy Map	SubTypeId MUST be "StrategyMap".
Trend Analysis Chart	SubTypeId MUST be "TrendAnalysisChart".
Analytic Grid	SubTypeId MUST be "OLAPGrid".
Analytic Chart	SubTypeId MUST be "AnalyticChart".

Type	Content
Decomposition Tree Report	SubTypeId MUST be "DecompositionTree".
Analytic Drill Through report	SubTypeId MUST be "OLAPDrillThrough".
Excel Services Workbook	SubTypeId MUST be "ExcelServices".
PAS Page	SubTypeId MUST be "PasPage".
KPI Detail Page	SubTypeId MUST be "KpiDetails".

RendererClassName: Specifies the fully qualified name for the assembly class that provides the rendering for the report view. This attribute **MUST** be present. If **SubTypeId** is not one of the predefined report view types listed in the table for **SubTypeId**, **RendererClassName** **MUST** be the assembly-qualified name of the custom type; otherwise, the value **MUST** be empty.

2.2.4.161 RepositoryLocation

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **RepositoryLocation** complex type specifies the location of a **FirstClassElement** (section [2.2.4.99](#)) stored on the server (2).

```
<xs:complexType name="RepositoryLocation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="ItemUrl" type="xs:string" use="required"/>
  <xs:attribute default="None" name="ItemType" type="tns:FirstClassObjectType"
  use="optional"/>
  <xs:attribute default="00000000-0000-0000-0000-000000000000" name="ItemGuid"
  use="optional">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
  <xs:attribute default="00000000-0000-0000-0000-000000000000" name="SpSiteCollectionGuid"
  use="optional">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
  <xs:attribute default="00000000-0000-0000-0000-000000000000" name="SpSiteGuid"
  use="optional">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
  <xs:attribute default="00000000-0000-0000-0000-000000000000" name="SpListGuid"
  use="optional">
    <xs:simpleType>
      <xs:restriction base="xs:string">
```

```

        <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}"/>
    </xs:restriction>
</xs:simpleType>
</xs:attribute>
</xs:complexType>

```

ItemUrl: A **server-relative URL** to a **FirstClassElement** (section [2.2.4.99](#)) stored by the server (2).

- If the **FirstClassElement** was created by **SaveTemporaryAnalyticReport** (section [3.1.4.65](#)), this value **MUST** be empty.
- When creating a new **FirstClassElement**, this value **MUST** be empty.
- In all other cases, this value **MUST** contain a valid URL.

ItemType: The type of **FirstClassElement** as specified by **FirstClassObjectType** (section [2.2.5.20](#)).

ItemGuid: The GUID assigned to the **FirstClassElement** by the server (2).

SpSiteCollectionGuid: The GUID of the **site collection** to which the **FirstClassElement** belongs. This value is assigned by the server (2).

SpSiteGuid: The GUID of the site (2) to which the **FirstClassElement** belongs. This value is assigned by the server (2).

SpListGuid: The GUID of the list (2) to which the **FirstClassElement** belongs. This value is assigned by the server (2).

2.2.4.162 Scorecard

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type represents a scorecard.

```

<xs:complexType name="Scorecard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:FirstClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="ConfiguredViews"
type="tns:ArrayOfConfiguredView"/>
        <xs:element minOccurs="0" maxOccurs="1" name="EndPoints" type="tns:ArrayOfEndPoint"/>
        <xs:element minOccurs="0" maxOccurs="1" name="BeginPoints"
type="tns:ArrayOfParameterDefinition"/>
      </xs:sequence>
      <xs:attribute name="RendererClassName" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

ConfiguredViews: Settings for display, behavior, and other purposes, as specified by **ArrayOfConfiguredView** (section [2.2.4.27](#)). **MUST** be present and **MUST** contain at least one **ConfiguredView** (section [2.2.4.77](#)).

EndPoint: Specifies the available connection destinations to filter and control the display of this scorecard. This element MUST be present. This element MUST conform to the schema of the **ArrayOfEndPoint** (section [2.2.4.33](#)) complex type.

BeginPoints: Specifies the available connection sources to filter and set conditions for the display of other reports and scorecards. This element MUST be present and MUST conform to the schema of the **ArrayOfParameterDefinition** (section [2.2.4.50](#)) complex type.

RendererClassName: Specifies the fully qualified name for the assembly class that provides the rendering for the scorecard. This attribute MUST be present. If the scorecard is a custom type, **RendererClassName** MUST be the assembly-qualified name of the custom type; otherwise, the value MUST be empty.

2.2.4.163 SecondClassElement

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This abstract class is the base class for **ConfiguredView** (section [2.2.4.77](#)), **DashboardElement** (section [2.2.4.80](#)), and **KpiMeasure** (section [2.2.4.129](#)).

```
<xs:complexType name="SecondClassElement" abstract="true"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:Element">
      <xs:attribute name="Guid" xmlns:s1="http://microsoft.com/wsd1/types/" type="s1:guid"
use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Guid: The element's unique identifier.

2.2.4.164 SerializableDictionary

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type specifies an ordered collection of elements of complex type **MemberSetFormula** (section [2.2.4.145](#)), **MemberList** (section [2.2.4.135](#)), or **Member** (section [2.2.4.134](#)), with their associated string keys.

```
<xs:complexType name="SerializableDictionary" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Item" type="tns:Item"/>
  </xs:sequence>
</xs:complexType>
```

Item: Represents a key-value pair (section [2.2.4.127](#)).

2.2.4.165 SetOperation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type specifies a set operation. It is the abstract base type for [AddAllMembersSetOp](#), [AddCalcMemberSetOp](#), [AddChildrenSetOp](#), [AddDefaultMemberSetOp](#), [AddDescendantsLeavesSetOp](#), [AddDescendantsSetOp](#), [AddDescendantsSubtreeSetOp](#), [AddFilterSetOp](#), [AddFilterTopBottomSetOp](#),

[AddMemberSetOp](#), [AddNamedSetSetOp](#), [AddParentSiblingsSetOp](#), [EliminateDescendantsSetOp](#) and [EliminateMemberSetOp](#).

```
<xs:complexType name="SetOperation" abstract="true"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FilterValue1" type="xs:double"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FilterValue2" type="xs:double"/>
    <xs:element minOccurs="0" maxOccurs="1" name="TupleSet" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="TupleCaption" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FilterHierarchy" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FilterMeasure" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DefaultMeasure" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Level" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="LevelDepth" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FilterType" type="xs:int"/>
    <xs:element minOccurs="0" maxOccurs="1" name="MemberDefinition" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Name: Specifies the name of a set operation.

FilterValue1: This contains the first filter value for those filter operations that need two filter values (for example, filtering a set such that the result is between a given minimum and maximum values). This is also used for filter operations that only require one filter value.

FilterValue2: For filter operations that need two filter values, this contains the second filter value. This is ignored for filter operations that only need one filter value.

TupleSet: This is the string representation of the tuple set used in filter operation to specify what to filter. The tuple set definition MUST be a valid MDX expression.

TupleCaption: This contains the tuple caption that will be displayed on the information bar.

FilterHierarchy: This contains the hierarchy unique name in a valid MDX that is used on the filter operation.

FilterMeasure: This contains the measure display name in that is used on the filter operation.

DefaultMeasure: This attribute is deprecated from the protocol and MUST NOT be used.

Level: This is used in filter set operation. This contains the level display name where the filter is being applied.

LevelDepth: This is used in filter set operation. This contains the level number where the filter is being applied.

FilterType: Specifies the type of filter. This MUST be one of the following values

Value	Meaning
0	No filter specified
1	Specifies top count.
2	Specifies top percent.

Value	Meaning
3	Specifies top sum.
4	Specifies bottom count.
5	Specifies bottom percent.
6	Specifies bottom sum.
7	Specifies equal.
8	Specifies not equals.
9	Specifies greater than.
10	Specifies greater than or equals.
11	Specifies less than.
12	Specifies less than or equals.
13	Specifies between.
14	Specifies not between.

MemberDefinition: This defines a calculated member in a valid MDX being added to a **MemberSet** (see section [2.2.4.144](#)).

2.2.4.166 SqlReportViewData

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **SqlReportViewData** complex type contains all the state information for a SQL Reporting Services report.

```
<xs:complexType name="SqlReportViewData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="ReportName" type="xs:string"/>
  <xs:attribute name="ServerAddress" type="xs:string"/>
  <xs:attribute name="ServerUrl" type="xs:string"/>
  <xs:attribute name="ReportPath" type="xs:string"/>
  <xs:attribute name="ReportUrl" type="xs:string"/>
  <xs:attribute name="ReportMode" type="tns:SqlReportViewDataServerMode" use="required"/>
  <xs:attribute name="ShowToolbar" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowParameters" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowDocMap" type="xs:boolean" use="required"/>
  <xs:attribute name="DocMapId" type="xs:string"/>
  <xs:attribute name="Zoom" type="xs:string"/>
  <xs:attribute name="Section" type="xs:string"/>
  <xs:attribute name="Format" type="xs:string"/>
</xs:complexType>
```

ReportName: The SQL Reporting Services report name.

ServerAddress: The SQL Reporting Services URL. The URL is the path to the Report Server of the SQL Server Reporting Service.

ServerUrl: The SQL Report URL, when in "SharePoint Integrated" mode. The URL is the path to the Report Server of the SQL Server Reporting Service.

ReportPath: The server-relative SQL Report URL, when in "Report Center" mode. The report path is the actual path in the SQL Server Reporting Service reports list to the report desired.

ReportUrl: In "SharePoint Integrated" mode, it defines the path of the SQL Report RDL including the RDL extension.

ReportMode: Indicates whether the report is in "SharePoint Integrated" or "Report Center" mode.

ShowToolbar: When **TRUE**, the SQL Report toolbar is shown.

ShowParameters: When **TRUE**, the SQL Report parameter toolbar is shown.

ShowDocMap: When **TRUE**, the SQL Report document map toolbar is shown.

DocMapId: The SQL Report document map identifier.

Zoom: The SQL Report zoom property.

Section: The SQL Report section property.

Format: The SQL Report format property.

2.2.4.167 StatusFilter

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type specifies an **indicator** to be filtered.

```
<xs:complexType name="StatusFilter" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="IndicatorLocationGuid" xmlns:s1="http://microsoft.com/wsd1/types/"
  type="s1:guid" use="required"/>
  <xs:attribute name="BandIndex" type="xs:int" use="required"/>
</xs:complexType>
```

IndicatorLocationGuid: The unique identifier for the filtered **indicator**.[<17>](#)

BandIndex: The index of the **indicator band** for the filtered **indicator**. MUST be a valid index for the indicator used in the **IndicatorLocationGuid**.

2.2.4.168 StrategyMapViewData

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **StrategyMapViewData** complex type class specifies metadata information about a strategy map.

```
<xs:complexType name="StrategyMapViewData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" default="None" name="ToolbarOptions"
    type="tns:StrategyMapToolbarOptions"/>
    <xs:element minOccurs="0" maxOccurs="1" name="VDX" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Version" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ParentLocation"
    type="tns:RepositoryLocation"/>
  </xs:sequence>
</xs:complexType>
```

```

    <xs:element minOccurs="0" maxOccurs="1" name="ParentType"
type="tns:FirstClassObjectType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Parameters" type="xs:string"/>
  </xs:sequence>
</xs:complexType>

```

ToolbarOptions: Specifies the toolbar configuration, as defined in the **StrategyMapToolbarOptions** simple type (section [2.2.5.49](#)).

VDX: Specifies a base64-bit representation of the compressed VDX [\[MS-VGSFF\]](#) file that represents the strategy map.

Version: Specifies the version of the protocol client where the strategy map was created. The version **MUST** be a number displayed as "major number.minor number.build number.private part number". A product version **MUST** represent a 64-bit number that holds the version number according to the following format:

- The first 16 bits are the product major part number.
- The next 16 bits are the product minor part number.
- The third set of 16 bits are the product build part number.
- The last 16 bits are the product private part number.

ParentLocation: Specifies the **FirstClassElement** complex type (section [2.2.4.99](#)) that represents the parent location of the strategy map. This element **MUST** be present. It **MUST** conform to the schema of the **RepositoryLocation** complex type (section [2.2.4.161](#)), and the **ItemUrl** attribute **MUST NOT** be **null**.

ParentType: The **ItemType** attribute for the parent **FirstClassElement**, as specified in **FirstClassObjectType** (section [2.2.5.20](#)).

Parameters: This value **MUST** be an empty string.

2.2.4.169 StringCollection

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The StringCollection complex type specifies a collection of dimension (1) properties.

```

<xs:complexType name="StringCollection" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string"/>
  </xs:sequence>
</xs:complexType>

```

string: Specifies the name of the dimension (1) property.

2.2.4.170 Target

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The target of a [KPI](#) used to measure against actual data.

```

<xs:complexType name="Target" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:KpiMeasure">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="IndicatorLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="StatedScore" type="tns:KpiMeasure"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Banding" type="tns:Banding"/>
        <xs:element minOccurs="1" maxOccurs="1" name="RelatedActualId"
xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
      </xs:sequence>
      <xs:attribute name="IsRollupScore" type="xs:boolean" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

IndicatorLocation: The [RepositoryLocation](#) of the [Indicator](#).

StatedScore: The **KpiMeasure** complex type (section [2.2.4.129](#)) that the Target uses when the type of the **Banding** complex type (section [2.2.4.60](#)) is "StatedScore". This value MUST NOT be null, if the type of **Banding** is "StatedScore".

Banding: The **Banding** data that correspond to the target.

RelatedActualId: The GUID of the corresponding **Actuals** property of the **Kpi** complex type (section [2.2.4.128](#)). This element MUST be present.

IsRollupScore: This attribute MUST be **true** if the score of this target is computed by rolling up the child scores, or MUST be **false** if the score is computed from the source data.

2.2.4.171 TimeIntelligenceDataSource

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

A time intelligence data source reference used in time intelligence parameter definitions.

```

<xs:complexType name="TimeIntelligenceDataSource"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DisplayName" type="xs:string"/>
  </xs:sequence>
</xs:complexType>

```

DataSourceLocation: The [RepositoryLocation](#) of the data source.

DisplayName: The display name of the data source.

2.2.4.172 TimeIntelligenceDefinition

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **TimeIntelligenceDefinition** complex type specifies time intelligence formulas and data sources. It is used in **CustomDefinition** of the **ParameterDefinition** complex type (section [2.2.4.155](#)).

```

<xs:complexType name="TimeIntelligenceDefinition"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Formulas"
type="tns:ArrayOfTimeIntelligenceFormula"/>
    <xs:element minOccurs="0" maxOccurs="1" name="MasterDataSource"
type="tns:TimeIntelligenceDataSource"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DataSources"
type="tns:ArrayOfTimeIntelligenceDataSource"/>
  </xs:sequence>
</xs:complexType>

```

Formulas: See complex type **ArrayOfTimeIntelligenceFormula** (section [2.2.4.57](#)).

MasterDataSource: The **TimeIntelligenceDataSource** (section [2.2.4.171](#)) that is queried to populate the parameter display values.

DataSources: The **ArrayOfTimeIntelligenceDataSource** complex type (section [2.2.4.56](#)) that are queried to populate the parameter message values.

2.2.4.173 TimeIntelligenceFormula

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type specifies a time intelligence parameter formula.

```

<xs:complexType name="TimeIntelligenceFormula" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="DisplayName" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Formula" type="xs:string"/>
  </xs:sequence>
</xs:complexType>

```

DisplayName: The display name of the formula.

Formula: The time intelligence formula. MUST NOT be **null**.

2.2.4.174 TimeIntelligenceLevelBinding

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the mapping of internal cube dimensions (1) to their time aggregation level.

```

<xs:complexType name="TimeIntelligenceLevelBinding"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Level" type="tns:DateAggregationTypes"/>
    <xs:element minOccurs="0" maxOccurs="1" name="UniqueName" type="xs:string"/>
  </xs:sequence>
</xs:complexType>

```

Level: The [DateAggregationType](#) that indicates the level of the binding.

UniqueName: The unique name of the dimension (1) in the cube that is mapped to the DateAggregationType indicated in Level. This element MUST be present.

2.2.4.175 TimeIntelligenceMdxSettings

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies how a dimension (1) in an Analysis Services data source maps to a time intelligence filter when running Simple Time Period Specification (STPS) formulas against the data source.

```
<xs:complexType name="TimeIntelligenceMdxSettings"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:TimeIntelligenceSettings">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="ReferenceDimension"
type="tns:Dimension"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ReferenceLevel"
type="tns:DateAggregationTypes"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ReferenceMember" type="tns:Member"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ReferenceDateTime" type="xs:dateTime"/>
        <xs:element minOccurs="0" maxOccurs="1" name="LevelBindings"
type="tns:ArrayOfTimeIntelligenceLevelBinding"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

ReferenceDimension: Specifies the time dimension (1) in the cube that is used when the STPS formula is run. See **Dimension** (section [2.2.4.90](#)). This element MUST be present.

ReferenceLevel: Specifies the lowest hierarchy level in the **ReferenceDimension** that will be available for STPS formulas run against the data source. See **DataAggregationTypes** (section [2.2.5.12](#)).

ReferenceMember: Specifies the date **Member** (see section [2.2.4.134](#)) in the dimension (1) specified in the **ReferenceDimension** element that corresponds to the date provided in the **ReferenceDateTime** element. This element MUST be present.

ReferenceDateTime: Specifies the actual date to which the value in the **ReferenceMember** element maps.

LevelBindings: Specifies the **ArrayOfTimeIntelligenceLevelBinding** (see section [2.2.4.58](#)) that maps the internal cube member levels to their corresponding STPS formula. If there is no mapping for one or more of the member levels, the member (3) level MUST NOT have a binding present in this array. This element MUST be present.

2.2.4.176 TimeIntelligencePostFormulaDefinition

Namespace: http://www.microsoft.com/performancepoint/scorecards

This complex type specifies a time intelligence post formula filter definition.

```
<xs:complexType name="TimeIntelligencePostFormulaDefinition"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="MasterDataSource" type="tns:DataSource"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DataSources" type="tns:ArrayOfDataSource"/>
  </xs:sequence>
```

```
</xs:complexType>
```

MasterDataSource: The DataSource (see section [2.2.4.85](#)) that is queried to populate the parameter display values (see section [2.2.4.155](#)).

DataSources: The data sources (see section [2.2.4.18](#)) that are queried to populate the parameter message values (See section [2.2.4.155](#)).

2.2.4.177 TimeIntelligenceSettings

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies additional time intelligence settings for a data source.

```
<xs:complexType name="TimeIntelligenceSettings" abstract="true"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Enabled" type="xs:boolean"/>
  </xs:sequence>
</xs:complexType>
```

Enabled: This value MUST be **true** if the time intelligence setting is enabled; otherwise, **false**.

2.2.4.178 Title

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This complex type represents a title for an analytic chart.

```
<xs:complexType name="Title" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Font" type="tns:XmlFont"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FontColor" type="xs:string"/>
  </xs:sequence>
  <xs:attribute default="" name="Text" type="xs:string"/>
  <xs:attribute default="Center" name="Alignment" type="tns:AlignmentType"/>
</xs:complexType>
```

Font: The font, specified by **XmlFont** (see section [2.2.4.181](#)). This MUST be present.

FontColor: The font color, specified by a string. This MUST be present and MUST be one of the following formats:

- "NamedColor:<name>" where:
 - "<name>" is the name of a predefined color, specified by a case-insensitive string. Values MUST be the same as the names of the elements in the Color Table (see section [2.2.4.14](#)).
 - Example: "NamedColor:Black".
- "ARGBColor:<A>:<R>:<G>:" where:
 - "<A>" is the alpha component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.

- "<R>" is the red component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
- "<G>" is the green component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
- "" is the blue component, specified by a string. Values MUST NOT be less than 0 and MUST NOT be greater than 255.
- Example: "ARGBColor:255:255:255:255".

Text: The title text, specified by a string.

Alignment: The alignment, specified by **AlignmentType** (see section [2.2.5.2](#)).

2.2.4.179 **ToolbarOptions**

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Contains the configuration settings of the toolbar of a **ConfiguredView** (section [2.2.4.77](#)).

```
<xs:complexType name="ToolbarOptions" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="ShowInlineText" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowToolbar" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowStatusFilter" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowToolTips" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowCollapse" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowMode" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowExpand" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowToolbarItemsLabel" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowDefaultRollup" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowWorstChildRollup" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowIndicatorCount" type="xs:boolean" use="required"/>
</xs:complexType>
```

ShowInlineText: This attribute MUST be **true** if the inline text button MUST be shown; **false** if not.

ShowToolbar: Specifies whether the toolbar is shown or not.

1. If set to **true**, toolbar MUST be shown following the toolbar configuration settings.
2. If set to **false**, toolbar MUST NOT be shown, and toolbar configuration settings MUST be ignored.

ShowStatusFilter: This attribute MUST be **true** if the status filtering options (see [StatusFilter](#), section [2.2.4.167](#)) MUST be shown; **false** if not. MUST be ignored if the **AllowStatusFilter** of the related **ConfiguredView** (section [2.2.4.77](#)) is set to **false**, in which case the filtering options MUST NOT be shown.

ShowToolTips: This attribute MUST be **true** if ToolTips MUST display in the toolbar buttons and options; **false** if not.

ShowCollapse: This attribute MUST be **true** if the collapse all button MUST be shown; **false** if not.

ShowMode: This attribute MUST be **true** if the button to switch between tree and flat mode MUST be shown; **false** if not.

ShowExpand: This attribute MUST be **true** if the expand all button MUST be shown; **false** if not.

ShowToolbarItemsLabel: Specifies whether the toolbar buttons are rendered with text label or not

1. If set to **true**, toolbar options and buttons MUST include both icon and text label.
2. If set to **false**, toolbar options and buttons MUST NOT include the text labels and MUST only include icon.

ShowDefaultRollup: This attribute MUST be **true** if the default rollup button MUST be shown; **false** if not.

ShowWorstChildRollup: This attribute MUST be **true** if the worst child rollup button MUST be shown; **false** if not.

ShowIndicatorCount: This attribute MUST be **true** if the indicator count rollup button MUST be shown; **false** if not.

2.2.4.180 Tuple

Namespace: <http://www.microsoft.com/performancepoint/scorecards/Analytics>

The **Tuple** complex type [<18>](#) represents an ordered collection of one or more **Member** complex types (section [2.2.4.134](#)) from different dimensions (1). It contains an instance of **SerializableDictionary** complex type (section [2.2.4.164](#)).

```
<xs:complexType name="Tuple" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="memberDictionary"
      type="tns:SerializableDictionary"/>
  </xs:sequence>
</xs:complexType>
```

memberDictionary: This element MUST NOT be null.

2.2.4.181 XmlFont

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies a set of attributes that define a font.

```
<xs:complexType name="XmlFont" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="FontFamily" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="GraphicsUnit" type="tns:GraphicsUnit"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Size" type="xs:float"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Style" type="tns:FontStyle"/>
  </xs:sequence>
</xs:complexType>
```

FontFamily: Specifies a group of typefaces having a similar basic design and style, such as "Arial" or "Courier". It SHOULD be set to a font family name that the server (2) can recognize. If the server (2) cannot recognize the font family name, it MUST instead use a font family name it does recognize.

GraphicsUnit: Specifies the unit of measure for the font as specified by **GraphicsUnit** (section [2.2.5.24](#)).

Size: Specifies the em-size of the font in the units specified by the **GraphicsUnit** attribute.

Style: Specifies style information applied to the font as specified by **FontStyle** (section [2.2.5.21](#)).

2.2.5 Simple Types

The following table summarizes the set of common XML schema simple type definitions defined by this specification. XML schema simple type definitions that are specific to a particular operation are described with the operation.

Simple type	Description
AggregateTypeEnum	The AggregateTypeEnum simple type specifies the method by which a KpiMeasure will be aggregated.
AlignmentType	Specifies the alignment of a text string relative to its layout rectangle.
AnalyticChartType	Type of chart to display.
AnalyticLegendLocation	The location of the analytic chart legend.
AnalyticMarkerStyle	The AnalyticMarkerStyle simple type specifies a Data Point marker shape for a line-type series of the report view.
AnnotationVersions	Specifies the product version that was used to create the annotation.
AxisType	The AxisType simple type specifies the type of an axis (as described in [MSDN-Axis]) in a query result.
BandType	Specifies the type of the banding for the Target (see section 2.2.4.170).
BeginPointEmitterType	The BeginPointEmitterType simple type specifies the type of information the parameter emits.
ConnectionContext	The ConnectionContext simple type specifies what identity is used to connect to the data source.
DataValuePosition	Specifies the display positioning for a data value.
DateAggregationTypes	This simple type represents a category of time intervals and MUST contain an item from the enumerated list.
DimensionTypeEnum	Specifies the type of information in a dimension (1).
EndPointCategory	The category specifying sort and filter EndPoints when connecting provider Web Parts to consumer Web Parts on the Dashboard.
ExcelServicesToolbarOptions	Specifies the toolbar options for an Excel Services ([MS-ESP]) report.
ExcelServicesToolbarType	Specifies which type of toolbar is shown on the Excel Services ([MS-ESP]) report.
ExcelServicesViewOptions	The ExcelServicesViewOptions simple type specifies how a user

Simple type	Description
	is allowed to interact with an Excel Services report ([MS-ESP]).
FactAggregations	This simple type specifies the type of aggregation to be performed on a numeric fact column in a tabular data set. The values are exclusive; that is, exactly one MUST be present in any field that uses this type.
FilterSelectionMode	Specifies the manner in which the items in a Filter (see section 2.2.4.98) can be selected.
FirstClassObjectType	Specifies the type of a first-class object.
FontStyle	Specifies style information applied to the font. It MUST equal Regular or any combination of the other values.
FormatNegativeSymbol	This simple type specifies the formatting pattern for negative numbers when custom formatting is used. Positive values are not affected. See KpiNumberFormatProperties (section 2.2.4.130).
FormatType	Defines the formatting pattern for numeric values. See KpiNumberFormatProperties (section 2.2.4.130).
GraphicsUnit	Specifies the unit of measure for the font.
GridCellElementStatus	The GridCellElementStatus simple type specifies the status of a display element of a scorecard cell. It MUST be zero, one or two.
HeaderAggregationTypes	This simple type specifies the type of aggregation used by the Scorecard.
HierarchyOrigin	This simple type specifies the overall structure of a hierarchy.
HierarchyType	This simple type specifies the type of an OLAP hierarchy.
HorizontalAlignments	This simple type specifies how an object or text in a control is horizontally aligned relative to the control element.
IndicatorPosition	The IndicatorPosition simple type specifies the position of the indicator within the target value cell.
IndicatorType	This simple type specifies whether the indicator bands indicate a better or worse status as values move lower or higher, or whether the indicator bands indicate a better or worse status as values move closer to the center.
KpiPattern	This simple type specifies how banding and scoring change in appearance according to the setting of the KPI pattern.
LayoutOrientation	This simple type defines the layout of items within a DashboardElementContainer (see section 2.2.4.81).
MappedColumnDataTypes	This simple type specifies the data type of the mapped columns in DataColumnMapping (see section 2.2.4.84).
MappedColumnTypes	This simple type specifies the classification of a mapped column in DataColumnMapping (see section 2.2.4.84).
MemberRelationship	This simple type specifies the relationship among dimension (1) members (see section 2.2.4.90). Member (see section 2.2.4.134)

Simple type	Description
	relationships are used in the context of a referred member.
MemberTransformOperation	This simple type specifies the transform action that the MemberTransform (section 2.2.4.146) will use.
MemberTransformType	This simple type specifies the classification of the MemberTransform (section 2.2.4.146).
MemberType	This simple type specifies the type represented by the member (section 2.2.4.134) object.
ReportLayout	Specifies the way that row and column headers are displayed in a grid report.
RollupTypes	This simple type enumeration specifies the types of rollup behavior that can be exhibited by a target column in a scorecard.
ScorecardEmptyRowsFilterMode	This simple type enumeration specifies whether to display scorecard rows with empty cells. A scorecard GridCell (section 2.2.4.100) is considered empty if DisplayElements does not contain any GridDisplayElements (section 2.2.4.103) with a Status of 0, as specified in GridCellElementStatus (section 2.2.5.25).
ScorecardNamedSetType	This simple type enumeration specifies how to define a set of dimension (1) members (3). It is used by GridHeaderItem (section 2.2.4.116) when the attribute HeaderType is set to "NamedSet", as specified in ScorecardNodeTypes (section 2.2.5.44).
ScorecardNodeTypes	This simple type enumeration specifies the type of scorecard node header. This is used in the GridHeaderItem (section 2.2.4.116).
ScoreTypes	This simple type enumeration specifies the type of score to be used when rolling up the target column in a scorecard.
SizeType	This simple type enumeration specifies the size unit in DashboardElementSize (section 2.2.4.82).
SortType	The SortType simple type specifies the manner in which the values in a query result are sorted.
SqlReportViewDataServerMode	The SqlReportViewDataServerMode simple type indicates when SQL Server Reporting Services integrated into a SharePoint server (1).
StrategyMapToolbarOptions	The StrategyMapToolbarOptions simple type specifies the view options for a strategy map report.
Trinary	This simple type specifies an enumeration type that has three possible values.
ValueSources	This simple type enumeration specifies how rollup values are computed. The enumeration determines how values for parent scorecard row items will be computed from the values of child scorecard row items within the same scorecard column.
VarianceDisplayType	This simple type enumeration specifies how a variance value is calculated and presented.
VarianceType	This simple type enumeration specifies how a variance calculation

Simple type	Description
	uses indicator status band and target values.
VerticalAlignments	This simple type enumeration specifies a vertical alignment of content within a grid cell or display element.

2.2.5.1 AggregateTypeEnum

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **AggregateTypeEnum** simple type specifies the method by which a KpiMeasure will be aggregated.

```
<xs:simpleType name="AggregateTypeEnum" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default"/>
    <xs:enumeration value="Sum"/>
    <xs:enumeration value="Minimum"/>
    <xs:enumeration value="Maximum"/>
    <xs:enumeration value="Count"/>
    <xs:enumeration value="Average"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **AggregateTypeEnum** simple type.

Value	Meaning
Default	Query using the default KpiMeasure aggregation.
Sum	Query the total value of the KpiMeasure.
Minimum	Query the minimum value of the KpiMeasure.
Maximum	Query the maximum value of the KpiMeasure.
Count	Query the count of values in the KpiMeasure.
Average	Query the average value of the KpiMeasure.

2.2.5.2 AlignmentType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the alignment of a text string relative to its layout rectangle.

```
<xs:simpleType name="AlignmentType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Left"/>
    <xs:enumeration value="Right"/>
    <xs:enumeration value="Center"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **AlignmentType** simple type.

Value	Meaning
Left	Specifies that the text be aligned left of the layout rectangle.
Right	Specifies that the text be aligned right of the layout rectangle.
Center	Specifies that the text be aligned center of the layout rectangle.

2.2.5.3 AnalyticChartType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Type of chart to display.

```
<xs:simpleType name="AnalyticChartType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Column"/>
    <xs:enumeration value="ColumnStacked"/>
    <xs:enumeration value="ColumnStacked100"/>
    <xs:enumeration value="Line"/>
    <xs:enumeration value="Pie"/>
    <xs:enumeration value="Bar"/>
    <xs:enumeration value="BarStacked"/>
    <xs:enumeration value="BarStacked100"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **AnalyticChartType** simple type.

Value	Meaning
None	The type of chart has not been set.
Column	Displays a vertical bar chart.
ColumnStacked	Displays a stacked vertical bar chart.
ColumnStacked100	Displays a stacked vertical bar chart with bars sized as a percentage of the total.
Line	Displays a line chart.
Pie	Displays a pie chart.
Bar	Displays a horizontal bar chart.
BarStacked	Displays a stacked horizontal bar chart.
BarStacked100	Displays a stacked horizontal bar chart with bars sized as a percentage of the total.

2.2.5.4 AnalyticLegendLocation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The location of the analytic chart legend.

```

<xs:simpleType name="AnalyticLegendLocation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Right"/>
    <xs:enumeration value="Top"/>
    <xs:enumeration value="Bottom"/>
    <xs:enumeration value="Left"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **AnalyticLegendLocation** simple type.

Value	Meaning
None	The legend is not displayed.
Right	The legend is displayed to the right of the analytic chart.
Top	The legend is displayed on top of the analytic chart.
Bottom	The legend is displayed on the bottom of the analytic chart.
Left	The legend is displayed to the left of the analytic chart.

2.2.5.5 AnalyticMarkerStyle

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **AnalyticMarkerStyle** simple type specifies a Data Point marker shape for a line-type series of the report view.

```

<xs:simpleType name="AnalyticMarkerStyle" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Square"/>
    <xs:enumeration value="Circle"/>
    <xs:enumeration value="Diamond"/>
    <xs:enumeration value="Triangle"/>
    <xs:enumeration value="Cross"/>
    <xs:enumeration value="Star4"/>
    <xs:enumeration value="Star5"/>
    <xs:enumeration value="Star6"/>
    <xs:enumeration value="Star10"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **AnalyticMarkerStyle** simple type.

Value	Meaning
None	No marker is displayed for the series/ data point (1) .
Square	A square marker is displayed.
Circle	A circular marker is displayed.

Value	Meaning
Diamond	A diamond-shaped marker is displayed.
Triangle	A triangular marker is displayed.
Cross	A cross-shaped marker is displayed.
Star4	A 4-point star-shaped marker is displayed.
Star5	A 5-point star-shaped marker is displayed.
Star6	A 6-point star-shaped marker is displayed.
Star10	A 10-point star-shaped marker is displayed.

2.2.5.6 AnnotationVersions

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the product version that was used to create the annotation.

```
<xs:simpleType name="AnnotationVersions" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Office14Beta2"/>
    <xs:enumeration value="Office14Beta1"/>
    <xs:enumeration value="Pps2007"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **AnnotationVersions** simple type.

Value	Meaning
Office14Beta2	Annotation was created with a Beta2 or RTM version <19> .
Office14Beta1	Annotation was created with a Beta1 version <20> .
Pps2007	Annotation was created with a prior production version. <21>

2.2.5.7 AxisType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **AxisType** simple type specifies the type of an axis (as described in [\[MSDN-Axis\]](#)) in a query result.

```
<xs:simpleType name="AxisType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Filter"/>
    <xs:enumeration value="Columns"/>
    <xs:enumeration value="Rows"/>
    <xs:enumeration value="Pages"/>
    <xs:enumeration value="Sections"/>
    <xs:enumeration value="Chapters"/>
  </xs:restriction>
</xs:simpleType>
```



```
</xs:simpleType>
```

The following table specifies the allowable values for the **AxisType** simple type.

Value	Meaning
Filter	Specifies a FILTER axis type or the slicer axis of the query.
Columns	Specifies a COLUMNS axis type that contains the column definition of the query.
Rows	Specifies a ROWS axis type that contains the row definition of the query.
Pages	Specifies a PAGES axis type that contains the page definition of the query. This axis type is unused.
Sections	Specifies a SECTIONS axis type that contains the section definition of the query. This axis type is unused.
Chapters	Specifies a CHAPTERS axis type that contains the chapter definition of the query. This axis type is unused.

2.2.5.8 BandType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the type of the banding for the **Target** (see section [2.2.4.170](#)).

```
<xs:simpleType name="BandType" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:restriction base="xs:string">  
    <xs:enumeration value="Normalized"/>  
    <xs:enumeration value="Actual"/>  
    <xs:enumeration value="StatedScore"/>  
  </xs:restriction>  
</xs:simpleType>
```

The following table specifies the allowable values for the **BandType** simple type.

Value	Meaning
Normalized	The value will be normalized .
Actual	The actual value will be used.
StatedScore	The selected Target value will be used. See Target.StatedScore (section 2.2.4.170).

2.2.5.9 BeginPointEmitterType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **BeginPointEmitterType** simple type specifies the type of information the parameter emits.

```
<xs:simpleType name="BeginPointEmitterType" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:restriction base="xs:string">  
    <xs:enumeration value="BothAConditionalVisibilityAndParameterEmitter"/>  
    <xs:enumeration value="ConditionalVisibilityEmitter"/>  
  </xs:restriction>  
</xs:simpleType>
```

```

    <xs:enumeration value="ParameterEmitter"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **BeginPointEmitterType** simple type.

Value	Meaning
BothAConditionalVisibilityAndParameterEmitter	Emits information that is used for setting conditional visibility values that indicate a connected Web Part is visible and parameter values.
ConditionalVisibilityEmitter	Emits information that is used for setting conditional visibility values that indicate a connected Web Part is visible.
ParameterEmitter	Emits information that is used for setting parameter values.

2.2.5.10 ConnectionContext

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **ConnectionContext** simple type specifies what identity is used to connect to the data source.

```

<xs:simpleType name="ConnectionContext" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="ConnectAsUser"/>
    <xs:enumeration value="ConnectAsSharedUser"/>
    <xs:enumeration value="SecureStoreCredentials"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **ConnectionContext** simple type.

Value	Meaning
ConnectAsUser	Connects to the data source using the user credentials.
ConnectAsSharedUser	Connects to the data source using the shared account credentials.
SecureStoreCredentials	Connects to the data source using credentials obtained from the Secure Store ([MS-SSWPS]).

2.2.5.11 DataValuePosition

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the display positioning for a data value.

```

<xs:simpleType name="DataValuePosition" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Left"/>
    <xs:enumeration value="Right"/>
    <xs:enumeration value="NotDisplayed"/>
  </xs:restriction>
</xs:simpleType>

```

```

    </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **DataValuePosition** simple type.

Value	Meaning
Left	Specifies that the data value will be displayed on the left.
Right	Specifies that the data value will be displayed on the right.
NotDisplayed	Specifies that the data value will not be displayed.

2.2.5.12 DateAggregationTypes

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type represents a category of time intervals and **MUST** contain an item from the enumerated list.

```

<xs:simpleType name="DateAggregationTypes" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="Second"/>
        <xs:enumeration value="Minute"/>
        <xs:enumeration value="Hour"/>
        <xs:enumeration value="Day"/>
        <xs:enumeration value="Week"/>
        <xs:enumeration value="Month"/>
        <xs:enumeration value="Quarter"/>
        <xs:enumeration value="Year"/>
        <xs:enumeration value="Semester"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>

```

The following table specifies the allowable values for the **DateAggregationTypes** simple type.

Value	Meaning
None	No time interval is defined.
Second	Intervals are seconds.
Minute	Intervals are minutes.
Hour	Intervals are hours.
Day	Intervals are days.
Week	Intervals are weeks.
Month	Intervals are months.

Value	Meaning
Quarter	Intervals are quarters.
Year	Intervals are years.
Semester	Intervals are half years or semesters.

2.2.5.13 DimensionTypeEnum

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the type of information in a dimension (1).

```
<xs:simpleType name="DimensionTypeEnum" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Accounts"/>
    <xs:enumeration value="BillOfMaterials"/>
    <xs:enumeration value="Channel"/>
    <xs:enumeration value="Currency"/>
    <xs:enumeration value="Customers"/>
    <xs:enumeration value="Geography"/>
    <xs:enumeration value="Measure"/>
    <xs:enumeration value="Organization"/>
    <xs:enumeration value="Other"/>
    <xs:enumeration value="Products"/>
    <xs:enumeration value="Promotion"/>
    <xs:enumeration value="Quantitative"/>
    <xs:enumeration value="Rates"/>
    <xs:enumeration value="Scenario"/>
    <xs:enumeration value="Time"/>
    <xs:enumeration value="Unknown"/>
    <xs:enumeration value="Utility"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **DimensionTypeEnum** simple type.

Value	Meaning
Accounts	The dimension (1) contains an accounts structure with parent-child relationships.
BillOfMaterials	The dimension (1) represents a material/component breakdown. The parent-child relationship implies a parent composed of its child elements.
Channel	The dimension (1) contains information about a distribution channel.
Currency	The dimension (1) contains currency information.
Customers	The dimension (1) contains customer information. The lowest level represents individual customers.
Geography	The dimension (1) contains a geographic hierarchy.
Measure	The dimension (1) contains measures.
Organization	The dimension (1) represents the reporting structure of an organization.

Value	Meaning
Other	The dimension (1) type is not Time, Measure or otherwise specified.
Products	The dimension (1) contains product information. The lowest level contains individual products.
Promotion	The dimension (1) contains information about marketing and advertising promotions.
Quantitative	The dimension (1) contains quantitative elements (for example, income level, or number of child elements).
Rates	The dimension (1) contains different types of rates (for example, buy, sell, or discounted).
Scenario	The dimension (1) contains different business scenarios.
Time	The dimension (1) refers to time (for example, year, month, week, day).
Unknown	The type of the dimension (1) is not specified.
Utility	The dimension (1) contains only calculated members.

2.2.5.14 EndPointCategory

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The category specifying sort and filter **EndPoints** when connecting provider Web Parts to consumer Web Parts on the Dashboard.

```
<xs:simpleType name="EndPointCategory" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Axis"/>
    <xs:enumeration value="ColumnHierarchy"/>
    <xs:enumeration value="RowHierarchy"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **EndPointCategory** simple type.

Value	Meaning
None	EndPoint has no category
Axis	EndPoint is a Scorecard Axis
ColumnHierarchy	EndPoint is a Scorecard Column Hierarchy
RowHierarchy	EndPoint is a Scorecard Row Hierarchy

2.2.5.15 ExcelServicesToolbarOptions

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the toolbar options for an Excel Services ([\[MS-ESP\]](#)) report.

```

<xs:simpleType name="ExcelServicesToolbarOptions"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="AllowInExcelOperations"/>
        <xs:enumeration value="AllowRefreshConnections"/>
        <xs:enumeration value="AllowRecalculation"/>
        <xs:enumeration value="ShowVisibleItemButton"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>

```

The following table specifies the allowable values for the **ExcelServicesToolbarOptions** simple type.

Value	Meaning
AllowInExcelOperations	Allows operations that open the Excel workbook ([MS-XLS]).
AllowRefreshConnections	Allows data connections in the Excel workbook to refresh.
AllowRecalculation	Allows users to recalculate the Excel workbook.
ShowVisibleItemButton	Shows the view menu to enable users to change the currently displayed published item.

2.2.5.16 ExcelServicesToolbarType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies which type of toolbar is shown on the Excel Services ([\[MS-ESP\]](#)) report.

```

<xs:simpleType name="ExcelServicesToolbarType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="FullToolbar"/>
    <xs:enumeration value="SummaryToolbar"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **ExcelServicesToolbarType** simple type.

Value	Meaning
None	No toolbar is displayed.
FullToolbar	The full toolbar is displayed.
SummaryToolbar	The summary toolbar is displayed.

2.2.5.17 ExcelServicesViewOptions

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ExcelServicesViewOptions** simple type specifies how a user is allowed to interact with an Excel Services report ([\[MS-ESP1\]](#)).

```
<xs:simpleType name="ExcelServicesViewOptions" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="AllowInteractivity"/>
        <xs:enumeration value="AllowParameterModification"/>
        <xs:enumeration value="ShowWorkbookParameters"/>
        <xs:enumeration value="AllowSorting"/>
        <xs:enumeration value="AllowFiltering"/>
        <xs:enumeration value="AllowHyperlinks"/>
        <xs:enumeration value="AllowPivotSpecificOperations"/>
        <xs:enumeration value="AllowPeriodicRefresh"/>
        <xs:enumeration value="CloseWorkbookSessions"/>
        <xs:enumeration value="AllowScratchPadMode"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
```

The following table specifies the allowable values for the **ExcelServicesViewOptions** simple type.

Value	Meaning
AllowInteractivity	Allows users to interact with the workbook.
AllowParameterModification	Allows users to change workbook parameters.
ShowWorkbookParameters	Allows users to view and edit workbook parameters.
AllowSorting	Allows users to sort when using AutoFilter , lists (1), and PivotTables.
AllowFiltering	Allows users to filter when using AutoFilter, lists (1), and PivotTables.
AllowHyperlinks	Allows users to use hyperlinks in the workbook.
AllowPivotSpecificOperations	Allows users to drilldown, find members (3), and take actions in PivotTables in the workbook.
AllowPeriodicRefresh	Allows Excel Services to perform periodic refreshes of external data sources if the data connection has a refresh interval defined.
CloseWorkbookSessions	Closes the current workbook before opening a new one.
AllowScratchPadMode	The value of this element MUST be ignored.

2.2.5.18 FactAggregations

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type specifies the type of aggregation to be performed on a numeric fact column in a tabular data set. The values are exclusive; that is, exactly one MUST be present in any field that uses this type.

```
<xs:simpleType name="FactAggregations" xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<xs:restriction base="xs:string">
  <xs:enumeration value="Average"/>
  <xs:enumeration value="Count"/>
  <xs:enumeration value="Max"/>
  <xs:enumeration value="Min"/>
  <xs:enumeration value="None"/>
  <xs:enumeration value="StDev"/>
  <xs:enumeration value="Sum"/>
  <xs:enumeration value="Variance"/>
  <xs:enumeration value="FirstOccurance"/>
</xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **FactAggregations** simple type.

Value	Meaning
Average	Calculate the average of numeric fact values.
Count	Calculate the total number of fact values.
Max	Determine the largest numeric fact value.
Min	Determine the smallest numeric fact value.
None	Perform no aggregation.
StDev	Calculate the variance of the numeric fact values.
Sum	Calculate the sum of the numeric fact values.
Variance	Calculate the statistical variance of the numeric fact values.
FirstOccurance	Determine the first fact value that occurs for each unique column member.

2.2.5.19 FilterSelectionMode

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the manner in which the items in a Filter (see section [2.2.4.98](#)) can be selected.

```

<xs:simpleType name="FilterSelectionMode" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="SingleSelect"/>
    <xs:enumeration value="MultiSelect"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **FilterSelectionMode** simple type.

Value	Meaning
SingleSelect	Single select parameter selection. Only one item can be selected for the filter at one time.
MultiSelect	Multi select parameter selection. Multiple items can be selected for the filter at one time.

2.2.5.20 FirstClassObjectType

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies the type of a first-class object.

```
<xs:simpleType name="FirstClassObjectType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Kpi"/>
    <xs:enumeration value="Scorecard"/>
    <xs:enumeration value="ReportView"/>
    <xs:enumeration value="Indicator"/>
    <xs:enumeration value="DataSource"/>
    <xs:enumeration value="Dashboard"/>
    <xs:enumeration value="TempReportView"/>
    <xs:enumeration value="Filter"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **FirstClassObjectType** simple type.

Value	Meaning
None	Indicates the object type is undefined
Kpi	Indicates the object is a Kpi (see section 2.2.4.128).
Scorecard	Indicates the object is a Scorecard (see section 2.2.4.162)
ReportView	Indicates the object is a ReportView (see section 2.2.4.160)
Indicator	Indicates the object is an Indicator (see section 2.2.4.125)
DataSource	Indicates the object is a DataSource (see section 2.2.4.85)
Dashboard	Indicates the object is a Dashboard (see section 2.2.4.79)
TempReportView	Indicates the object is a temporary ReportView (see section 2.2.4.160) as created by SaveTemporaryAnalyticReport
Filter	Indicates the object is a Filter (see section 2.2.4.98)

2.2.5.21 FontStyle

Namespace: http://www.microsoft.com/performancepoint/scorecards

Specifies style information applied to the font. It MUST equal **Regular** or any combination of the other values.

```
<xs:simpleType name="FontStyle" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="Regular"/>
        <xs:enumeration value="Bold"/>
        <xs:enumeration value="Italic"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
```

```

    <xs:enumeration value="Underline"/>
    <xs:enumeration value="Strikeout"/>
  </xs:restriction>
</xs:simpleType>
</xs:list>
</xs:simpleType>

```

The following table specifies the allowable values for the **FontStyle** simple type.

Value	Meaning
Regular	Normal text.
Bold	Bold text.
Italic	Italic text.
Underline	Underlined text.
Strikeout	Text with a line through the middle.

2.2.5.22 FormatNegativeSymbol

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type specifies the formatting pattern for negative numbers when custom formatting is used. Positive values are not affected. See [KpiNumberFormatProperties](#) (section [2.2.4.130](#)).

```

<xs:simpleType name="FormatNegativeSymbol" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NegativeSign"/>
    <xs:enumeration value="Parenthesis"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **FormatNegativeSymbol** simple type.

Value	Meaning
NegativeSign	Show minus sign preceding to the number. Example: -42.15
Parenthesis	Enclose the number in parenthesis. Example: (42.15)

2.2.5.23 FormatType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Defines the formatting pattern for numeric values. See [KpiNumberFormatProperties](#) (section [2.2.4.130](#)).

```

<xs:simpleType name="FormatType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">

```

```

    <xs:enumeration value="Default"/>
    <xs:enumeration value="Number"/>
    <xs:enumeration value="Currency"/>
    <xs:enumeration value="Percentage"/>
    <xs:enumeration value="Unknown"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **FormatType** simple type.

Value	Meaning
Default	No formatting. Formatting of the data source is used.
Number	General numeric formatting—for example, 12,222.003
Currency	Currency formatting—for example, \$25.00
Percentage	Percentage formatting—for example, 25%
Unknown	Null or undetermined formatting

2.2.5.24 GraphicsUnit

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the unit of measure for the font.

```

<xs:simpleType name="GraphicsUnit" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="World"/>
    <xs:enumeration value="Display"/>
    <xs:enumeration value="Pixel"/>
    <xs:enumeration value="Point"/>
    <xs:enumeration value="Inch"/>
    <xs:enumeration value="Document"/>
    <xs:enumeration value="Millimeter"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **GraphicsUnit** simple type.

Value	Meaning
World	Specifies the world coordinate system unit as the unit of measure.
Display	Specifies the unit of measure of the display device. Typically pixels for video displays, and 1/100 inch for printers.
Pixel	Specifies a device pixel as the unit of measure.
Point	Specifies a printer's point (1/72 inch) as the unit of measure.
Inch	Specifies the inch as the unit of measure.
Document	Specifies the document unit (1/300 inch) as the unit of measure.

Value	Meaning
Millimeter	Specifies the millimeter as the unit of measure.

2.2.5.25 GridCellElementStatus

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **GridCellElementStatus** simple type specifies the status of a display element of a scorecard cell. It MUST be zero, one or two.

```
<xs:simpleType name="GridCellElementStatus" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="0"/>
    <xs:enumeration value="1"/>
    <xs:enumeration value="2"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **GridCellElementStatus** simple type.

Value	Meaning
0	OK: Specifies that element is displayed correctly
1	Error: Specifies that element is in error: error state is displayed. See the InvalidCell property of the GridViewDefinition complex type (section 2.2.4.122)
2	Null: Specifies that element is empty: empty state is displayed. See the EmptyCell property of GridViewDefinition

2.2.5.26 HeaderAggregationTypes

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type specifies the type of aggregation used by the Scorecard.

```
<xs:simpleType name="HeaderAggregationTypes" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Sum"/>
    <xs:enumeration value="Average"/>
    <xs:enumeration value="Min"/>
    <xs:enumeration value="Max"/>
    <xs:enumeration value="Trend"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **HeaderAggregationTypes** simple type.

Value	Meaning
None	No aggregation

Value	Meaning
Sum	Aggregate the sum value
Average	Aggregate the average value
Min	Aggregate the minimum value
Max	Aggregate the maximum value
Trend	Aggregate the trend of the last two sibling values

2.2.5.27 HierarchyOrigin

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type specifies the overall structure of a hierarchy.

```
<xs:simpleType name="HierarchyOrigin" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="AttributeHierarchy"/>
    <xs:enumeration value="ParentChildHierarchy"/>
    <xs:enumeration value="UserHierarchy"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **HierarchyOrigin** simple type.

Value	Meaning
None	The hierarchy has no structure.
AttributeHierarchy	The hierarchy is an attribute hierarchy .
ParentChildHierarchy	The hierarchy is a parent-child hierarchy.
UserHierarchy	The hierarchy is a user-defined hierarchy.

2.2.5.28 HierarchyType

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type specifies the type of an OLAP hierarchy.

```
<xs:simpleType name="HierarchyType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Standard"/>
    <xs:enumeration value="Measure"/>
    <xs:enumeration value="Time"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **HierarchyType** simple type.

Value	Meaning
Standard	Indicates a Standard OLAP hierarchy.
Measure	Indicates a Measured OLAP hierarchy.
Time	Indicates a Time OLAP hierarchy.

2.2.5.29 HorizontalAlignments

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type specifies how an object or text in a control is horizontally aligned relative to the control element.

```
<xs:simpleType name="HorizontalAlignments" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Undefined"/>
    <xs:enumeration value="Left"/>
    <xs:enumeration value="Center"/>
    <xs:enumeration value="Right"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **HorizontalAlignments** simple type.

Value	Meaning
Undefined	No horizontal alignment is applied to the object or text.
Left	The object or text is aligned on the left of the control element.
Center	The object or text is aligned in the center of the control element.
Right	The object or text is aligned on the right of the control element.

2.2.5.30 IndicatorPosition

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **IndicatorPosition** simple type specifies the position of the indicator within the target value cell.

```
<xs:simpleType name="IndicatorPosition" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Left"/>
    <xs:enumeration value="Right"/>
    <xs:enumeration value="Center"/>
    <xs:enumeration value="NotDisplayed"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **IndicatorPosition** simple type.

Value	Meaning
Left	Display the indicator against the left edge of the cell.
Right	Display the indicator against the right edge of the cell.
Center	Display the indicator in the center of the cell between the two numeric values.
NotDisplayed	Do not display the indicator.

2.2.5.31 IndicatorType

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type specifies whether the **indicator bands** indicate a better or worse status as values move lower or higher, or whether the **indicator bands** indicate a better or worse status as values move closer to the center.

```
<xs:simpleType name="IndicatorType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Standard"/>
    <xs:enumeration value="Centered"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **IndicatorType** simple type.

Value	Meaning
Standard	Indicator bands go from best to worst as values increase (or decrease).
Centered	Indicator bands go from best to worst as values get further away from the center.

2.2.5.32 KpiPattern

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type specifies how banding and scoring change in appearance according to the setting of the KPI pattern.

```
<xs:simpleType name="KpiPattern" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="IncreasingIsBetter"/>
    <xs:enumeration value="DecreasingIsBetter"/>
    <xs:enumeration value="CloserToTargetIsBetter"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **KpiPattern** simple type.

Value	Meaning
IncreasingIsBetter	For banding and scoring, data that increases is better.

Value	Meaning
DecreasingIsBetter	For banding and scoring, data that decreases is better.
CloserToTargetIsBetter	For banding and scoring, data that is closer to the target is better.

2.2.5.33 LayoutOrientation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type defines the layout of items within a DashboardElementContainer (see section [2.2.4.81](#)).

```
<xs:simpleType name="LayoutOrientation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="HorizontalLeftJustified"/>
    <xs:enumeration value="HorizontalRightJustified"/>
    <xs:enumeration value="VerticalBottomJustified"/>
    <xs:enumeration value="VerticalTopJustified"/>
    <xs:enumeration value="Stacked"/>
    <xs:enumeration value="Hidden"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **LayoutOrientation** simple type.

Value	Meaning
HorizontalLeftJustified	Horizontal layout where adjacent items are left-justified.
HorizontalRightJustified	Horizontal layout where adjacent items are right-justified.
VerticalBottomJustified	Vertical layout where adjacent items are bottom-justified.
VerticalTopJustified	Vertical layout where adjacent items are top-justified.
Stacked	Items are stacked so that only one item is visible at a time.
Hidden	Items are not displayed.

2.2.5.34 MappedColumnDataTypes

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type specifies the data type of the mapped columns in DataColumnMapping (see section [2.2.4.84](#)).

```
<xs:simpleType name="MappedColumnDataTypes" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NotSupported"/>
    <xs:enumeration value="Number"/>
    <xs:enumeration value="String"/>
    <xs:enumeration value="DateTime"/>
  </xs:restriction>
</xs:simpleType>
```


The following table specifies the allowable values for the **MappedColumnDataTypes** simple type.

Value	Meaning
NotSupported	Used when MappedColumnTypes is set to Ignore in DataColumnMapping.
Number	The mapped column values are numeric. Valid numeric values are short, integer, long, decimal and float.
String	The mapped column values are UNICODE characters.
DateTime	The mapped column values are date-time values.

2.2.5.35 MappedColumnTypes

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type specifies the classification of a mapped column in **DataColumnMapping** (see section [2.2.4.84](#)).

```
<xs:simpleType name="MappedColumnTypes" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Ignore"/>
    <xs:enumeration value="Fact"/>
    <xs:enumeration value="Dimension"/>
    <xs:enumeration value="TimeDimension"/>
    <xs:enumeration value="Key"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **MappedColumnTypes** simple type.

Value	Meaning
Ignore	The ignore type indicates that the mapped column in DataColumnMapping MUST be ignored.
Fact	The mapped column contains fact data. A fact column type MUST have an associated FactAggregations (see section 2.2.5.18).
Dimension	The mapped column contains dimension (1) (see section 2.2.4.90) members.
TimeDimension	The mapped column contains time-based dimension (1) members.
Key	The mapped column is the key column for columns mapped as Dimension (see section 2.2.4.90).

2.2.5.36 MemberRelationship

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type specifies the relationship among dimension (1) members (see section [2.2.4.90](#)). Member (see section [2.2.4.134](#)) relationships are used in the context of a referred member.

```
<xs:simpleType name="MemberRelationship" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
```

```

    <xs:enumeration value="Parent"/>
    <xs:enumeration value="FirstSibling"/>
    <xs:enumeration value="PrevMember"/>
    <xs:enumeration value="NextMember"/>
    <xs:enumeration value="LastSibling"/>
    <xs:enumeration value="FirstChild"/>
    <xs:enumeration value="LastChild"/>
    <xs:enumeration value="CurrentMember"/>
    <xs:enumeration value="Children"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **MemberRelationship** simple type.

Value	Meaning
Parent	Parent of the referred dimension (1) (section 2.2.4.90) member (3) (section 2.2.4.134).
FirstSibling	First child of the parent of the referred (section 2.2.4.90) member (3) (section 2.2.4.134).
PrevMember	Previous member (3) at the same level that contains the referred dimension (1) (section 2.2.4.90) member (3) (section 2.2.4.134).
NextMember	Next member (3) at the same level that contains the referred dimension (1) (section 2.2.4.90) member (3) (section 2.2.4.134).
LastSibling	Last child of the parent of the referred dimension (1) (section 2.2.4.90) member (3) (section 2.2.4.134).
FirstChild	First child of the parent of the referred dimension (1) (section 2.2.4.90) member (3) (section 2.2.4.134).
LastChild	Last child of the referred dimension (1) (section 2.2.4.90) member (3) (section 2.2.4.134).
CurrentMember	Current member (3) (section 2.2.4.134) along a specified dimension (1) (section 2.2.4.90) or hierarchy (section 2.2.4.124) during iteration. When used in the context of a referred member (3) it implies the referred member (3) itself.
Children	Child members (3) of the referred dimension (1) (section 2.2.4.90) member (section 2.2.4.134).

2.2.5.37 MemberTransformOperation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type specifies the transform action that the **MemberTransform** (section [2.2.4.146](#)) will use.

```

<xs:simpleType name="MemberTransformOperation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Replace"/>
    <xs:enumeration value="DrillUp"/>
    <xs:enumeration value="DrillDown"/>
    <xs:enumeration value="Expand"/>
  </xs:restriction>
</xs:simpleType>

```

```
</xs:simpleType>
```

The following table specifies the allowable values for the **MemberTransformOperation** simple type.

Value	Meaning
Replace	Replaces a single hierarchy (section 2.2.4.124) group or all members (3) (section 2.2.4.134) from a KPI (section 2.2.4.128) with members (3) (section 2.2.4.134) provided by filters (section 2.2.4.98).
DrillUp	Drills up on a referred member (3) (section 2.2.4.134).
DrillDown	Drills down on a referred member (3) (section 2.2.4.134).
Expand	Dynamically expands the child members (3) of a referred member (3) (section 2.2.4.134).

2.2.5.38 MemberTransformType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type specifies the classification of the **MemberTransform** (section [2.2.4.146](#)).

```
<xs:simpleType name="MemberTransformType" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:restriction base="xs:string">  
    <xs:enumeration value="Row"/>  
    <xs:enumeration value="Column"/>  
  </xs:restriction>  
</xs:simpleType>
```

The following table specifies the allowable values for the **MemberTransformType** simple type.

Value	Meaning
Row	The MemberTransform (section 2.2.4.146) will be applied to rows.
Column	The MemberTransform (section 2.2.4.146) will be applied to columns.

2.2.5.39 MemberType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type specifies the type represented by the member (section [2.2.4.134](#)) object.

```
<xs:simpleType name="MemberType" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:restriction base="xs:string">  
    <xs:enumeration value="Regular"/>  
    <xs:enumeration value="Operation"/>  
    <xs:enumeration value="Default"/>  
    <xs:enumeration value="Formula"/>  
  </xs:restriction>  
</xs:simpleType>
```

The following table specifies the allowable values for the **MemberType** simple type.

Value	Meaning
Regular	A regular member (3) (section 2.2.4.134).
Operation	The member object represents a member operation (section 2.2.4.136).
Default	The member object represents the default member (section 2.2.4.134).
Formula	The member object represents a calculated member.

2.2.5.40 ReportLayout

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the way that row and column headers are displayed in a grid report.

```
<xs:simpleType name="ReportLayout" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="TabularForm"/>
    <xs:enumeration value="CompactForm"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **ReportLayout** simple type.

Value	Meaning
TabularForm	Row and column headers are flattened so that data is displayed in a space-efficient manner.
CompactForm	Row and column headers are displayed in an indented manner that reflects their hierarchical relationship.

2.2.5.41 RollupTypes

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type enumeration specifies the types of rollup behavior that can be exhibited by a target column in a scorecard.

```
<xs:simpleType name="RollupTypes" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="AverageWeighted"/>
    <xs:enumeration value="WorstChild"/>
    <xs:enumeration value="IndicatorCount"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **RollupTypes** simple type.

Value	Meaning
None	Do not perform rollups.

Value	Meaning
AverageWeighted	Rollup a weighted average of the scores of the direct child members.
WorstChild	Rollup the worst score among the descendants.
IndicatorCount	Rollup a count of each state of each indicator found within the descendants, excluding those belonging to objective KPIs .

2.2.5.42 ScorecardEmptyRowsFilterMode

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type enumeration specifies whether to display scorecard rows with empty cells. A scorecard **GridCell** (section [2.2.4.100](#)) is considered empty if **DisplayElements** does not contain any **GridDisplayElements** (section [2.2.4.103](#)) with a **Status** of 0, as specified in **GridCellElementStatus** (section [2.2.5.25](#)).

```
<xs:simpleType name="ScorecardEmptyRowsFilterMode"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="AllValuesAreEmpty"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **ScorecardEmptyRowsFilterMode** simple type.

Value	Meaning
None	Do not filter rows.
AllValuesAreEmpty	Filter out rows where all non-header cells are empty.

2.2.5.43 ScorecardNamedSetType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type enumeration specifies how to define a set of dimension (1) members (3). It is used by **GridHeaderItem** (section [2.2.4.116](#)) when the attribute **HeaderType** is set to "NamedSet", as specified in **ScorecardNodeTypes** (section [2.2.5.44](#)).

```
<xs:simpleType name="ScorecardNamedSetType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="NamedSet"/>
        <xs:enumeration value="CustomFormula"/>
        <xs:enumeration value="TimeFormula"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
```

```
</xs:simpleType>
```

The following table specifies the allowable values for the **ScorecardNamedSetType** simple type.

Value	Meaning
None	GridHeaderItem (section 2.2.4.116) does not contain any dimension (1) members (3) specified by a named set, a custom formula, or a time intelligence formula. A GridHeaderItem MUST NOT use this value if the HeaderType attribute is set to "NamedSet", as specified in ScorecardNodeTypes (section 2.2.5.44).
NamedSet	Dimension (1) members (3) are specified by a named set.
CustomFormula	Dimension (1) members (3) are specified by a custom formula.
TimeFormula	Dimension (1) members (3) are specified by a time intelligence formula.

2.2.5.44 ScorecardNodeTypes

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type enumeration specifies the type of scorecard node header. This is used in the **GridHeaderItem** (section [2.2.4.116](#)).

```
<xs:simpleType name="ScorecardNodeTypes" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="Member"/>
        <xs:enumeration value="Kpi"/>
        <xs:enumeration value="KpiActual"/>
        <xs:enumeration value="KpiTarget"/>
        <xs:enumeration value="ScorecardDetails"/>
        <xs:enumeration value="DocumentLinks"/>
        <xs:enumeration value="NamedSet"/>
        <xs:enumeration value="Aggregate"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
```

The following table specifies the allowable values for the **ScorecardNodeTypes** simple type.

Value	Meaning
None	An unknown node type. This value SHOULD NOT be used except for the row and column root nodes. The behavior for this node type is unspecified.
Member	A dimension (1) member node.
Kpi	A KPI node.
KpiActual	A KPI actual value node.
KpiTarget	A KPI target value node.

Value	Meaning
ScorecardDetails	Additional properties of scorecard elements node.
DocumentLinks	Document links of scorecard elements node.
NamedSet	A named set node.
Aggregate	An aggregation node.

2.2.5.45 ScoreTypes

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type enumeration specifies the type of score to be used when rolling up the target column in a scorecard.

```
<xs:simpleType name="ScoreTypes" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Normalized"/>
    <xs:enumeration value="Raw"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **ScoreTypes** simple type.

Value	Meaning
Normalized	Rollup scores are determined using child scores normalized to a common scale.
Raw	Rollup scores are determined using the child scores without any conversion or normalization.

2.2.5.46 SizeType

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type enumeration specifies the size unit in **DashboardElementSize** (section [2.2.4.82](#)).

```
<xs:simpleType name="SizeType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="AutoSize"/>
    <xs:enumeration value="Absolute"/>
    <xs:enumeration value="Percent"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **SizeType** simple type.

Value	Meaning
AutoSize	Auto sized based on internal content. Any related measurement value MUST be ignored if specified.
Absolute	Absolute value in pixels.

Value	Meaning
Percent	Percentage value relative to the container size. This value MUST NOT be less than 0 and MUST NOT be greater than 100.

2.2.5.47 SortType

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **SortType** simple type specifies the manner in which the values in a query result are sorted.

```
<xs:simpleType name="SortType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Off"/>
    <xs:enumeration value="ByIndex"/>
    <xs:enumeration value="ByTuple"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **SortType** simple type.

Value	Meaning
Off	No sort is applied.
ByIndex	Sort by column index.
ByTuple	Sort by value, which is specified by the measure in the tuple.

2.2.5.48 SqlReportViewDataServerMode

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **SqlReportViewDataServerMode** simple type indicates when SQL Server Reporting Services integrated into a SharePoint server (1).

```
<xs:simpleType name="SqlReportViewDataServerMode"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="SharepointIntegrated"/>
    <xs:enumeration value="ReportCenter"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **SqlReportViewDataServerMode** simple type.

Value	Meaning
SharepointIntegrated	The SQL Reporting Services server (1) is integrated into SharePoint, allowing reports to be stored and rendered using SharePoint server (1).
ReportCenter	SQL Reports are stored and rendered using a SQL Server Reporting Services server (1).

2.2.5.49 StrategyMapToolBarOptions

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **StrategyMapToolBarOptions** simple type specifies the view options for a strategy map report.

```
<xs:simpleType name="StrategyMapToolBarOptions" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="ShowToolBar"/>
        <xs:enumeration value="ShowPage"/>
        <xs:enumeration value="ShowScrollbars"/>
        <xs:enumeration value="ShowPageTabs"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
```

The following table specifies the allowable values for the **StrategyMapToolBarOptions** simple type.

Value	Meaning
None	No options are specified.
ShowToolBar	The toolbar is displayed.
ShowPage	The drawing page is displayed.
ShowScrollbars	The scrollbars are displayed.
ShowPageTabs	The page tabs are displayed.

2.2.5.50 Trinary

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type specifies an enumeration type that has three possible values.

```
<xs:simpleType name="Trinary" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Undefined"/>
    <xs:enumeration value="False"/>
    <xs:enumeration value="True"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **Trinary** simple type.

Value	Meaning
Undefined	Not Defined.

Value	Meaning
False	Specified as False.
True	Specified as True.

2.2.5.51 ValueSources

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type enumeration specifies how rollup values are computed. The enumeration determines how values for parent scorecard row items will be computed from the values of child scorecard row items within the same scorecard column.

```
<xs:simpleType name="ValueSources" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default"/>
    <xs:enumeration value="NoValue"/>
    <xs:enumeration value="SourceData"/>
    <xs:enumeration value="Text"/>
    <xs:enumeration value="AverageRollup"/>
    <xs:enumeration value="MinRollup"/>
    <xs:enumeration value="MaxRollup"/>
    <xs:enumeration value="TotalRollup"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **ValueSources** simple type.

Value	Meaning
Default	Use default settings: If there are child members (3), the average weighted value of child objects MUST be used; otherwise, when there are no child objects, SourceData value MUST be used.
NoValue	Don't compute or show values.
SourceData	No rollup, query source data.
Text	Text value of source data.
AverageRollup	Mathematical average value of child objects.
MinRollup	Minimum value of child objects.
MaxRollup	Maximum value of child objects.
TotalRollup	Total, summed, value of child objects.

2.2.5.52 VarianceDisplayType

Namespace: http://www.microsoft.com/performancepoint/scorecards

This simple type enumeration specifies how a **variance** value is calculated and presented.

```
<xs:simpleType name="VarianceDisplayType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<xs:restriction base="xs:string">
  <xs:enumeration value="ShowPercent"/>
  <xs:enumeration value="ShowValue"/>
  <xs:enumeration value="ShowInvertedPercent"/>
</xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **VarianceDisplayType** simple type.

Value	Meaning
ShowPercent	Show variance value as the percentage variance between a target (section 2.2.4.170) value and its associated actual value.
ShowValue	Show the variance value as the difference between a target (section 2.2.4.170) value and its associated actual value.
ShowInvertedPercent	Show the variance value as the inverted percentage variance between a target (section 2.2.4.170) value and its associated actual value.

2.2.5.53 VarianceType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type enumeration specifies how a **variance** calculation uses **indicator status band** and target values.

```

<xs:simpleType name="VarianceType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="VarianceToTarget"/>
    <xs:enumeration value="VarianceToBestTarget"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **VarianceType** simple type.

Value	Meaning
VarianceToTarget	Show the variance value as the inverted percentage variance between a target (section 2.2.4.170) value and its associated actual value.
VarianceToBestTarget	Calculate value as the variance between the actual value and a computed target (section 2.2.4.170) value. The computed target (section 2.2.4.170) value takes into account the nearest threshold of the best indicator status band . See the Banding complex type (section 2.2.4.60) for more information about bands.

2.2.5.54 VerticalAlignments

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

This simple type enumeration specifies a vertical alignment of content within a grid cell or display element.

```

<xs:simpleType name="VerticalAlignments" xmlns:xs="http://www.w3.org/2001/XMLSchema">

```

```

<xs:restriction base="xs:string">
  <xs:enumeration value="Undefined"/>
  <xs:enumeration value="Top"/>
  <xs:enumeration value="Middle"/>
  <xs:enumeration value="Bottom"/>
</xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **VerticalAlignments** simple type.

Value	Meaning
Undefined	Vertical alignment is undefined.
Top	Align at the top.
Middle	Align at the middle.
Bottom	Align at the bottom.

2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

2.2.9 Common Data Structures

This specification does not define any common XML schema data structures.

3 Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

Except where specified, protocol clients SHOULD interpret HTTP status codes returned by the server (2) as specified in [\[RFC2616\]](#) section 10, Status Code Definitions).

This protocol allows servers (2) to notify protocol clients of application-level faults using SOAP faults. Except where specified, these SOAP faults are not significant for interoperability, and protocol clients can interpret them in an implementation-specific manner.

This protocol allows servers (2) to perform implementation-specific authorization checks and notify protocol clients of authorization faults either using HTTP status codes or using SOAP faults as specified previously in this section.

Occasionally, instances occur where this web service's WSDL specifies optionality (for example, `minOccurs="0"` and `maxOccurs="1"`) that conflicts with the stated behavior in this document, or the document doesn't contain the stated behavior. In such cases, where the document and the WSDL conflict, the document takes precedence. In cases where the document doesn't specify optionality, the argument has to be present, even if the WSDL specifies that the argument is optional (for example, `minOccurs="0"`).

In cases where an argument is optional and the WSDL specifies both `"minOccurs=0"` and `"Nillable=true"`, treat the argument as only `"minOccurs=0"`.

3.1 Server Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

The server (2) maintains a collection of first-class elements indexed by unique repository locations. Each first-class element can be independently published to and read from the server (2). Each first-class element references its dependents by their unique repository locations. The following UML diagram describes how the first-class elements are related:




Figure 10: Overview of first-class elements

A first-class element’s dependents must be published prior to that first-class element being consumed on the server (2). For example, all the first-class elements that a dashboard is dependent on must be published prior to that dashboard being deployed or viewed.

The following classes are defined as first-class elements:

Dashboard: A customizable landing page for a business application or workspace that uses Web Parts to display selected information. It can provide a comprehensive look at the information inside the application or workspace by consolidating lists (1), libraries, text, images and other data into a dynamic, customizable information portal.

Each Web Part on a dashboard displays the information specified by a single first-class element.

The Filters, Reports, and Scorecards in a Dashboard can be connected together so that changes in the state of one first-class element will change the information displayed by other first-class

elements. For example, a Filter can be connected to Report Views or Scorecards so that changes to the selections made in the Filter are reflected in the information shown by those Report Views and Scorecards.

When Filters, Reports, and Scorecards are connected in a Dashboard, each connection has an explicit source and a destination. State information in a dashboard always flows from a connection source or begin point in one first-class element to a connection destination or endpoint in another first-class element. Filters, Reports, and Scorecards can each have multiple begin points and endpoints. A connection is fully defined by a source element, a begin point on that element, a destination element and an endpoint on that element. For example, the member name begin point on a Filter could be connected to the row endpoint on a Scorecard.

There are limitations on the way different first-class element can be connected in a Dashboard:

First-class element	Can be a source?	Can be a destination?
Filter	Yes	No
Report View	No	Yes
Scorecard	Yes	Yes

- The connection cannot create a circular reference; a user cannot connect a scorecard to a filter that is already linked to the scorecard.
- A begin point is available if:
 - It is not already connected to another begin point or it is connected but its `AcceptMultipleFilterLinks` property is set to true.
 - It is not already connected to the begin point. If the dashboard item is a scorecard it can accept multiple connections from the same begin point.
- Unless the target item is a scorecard a user cannot make multiple connections from a begin point to a target.
- Although a scorecard can accept multiple connections from the same begin point, those connections cannot be to the same end point on the scorecard. In other words, a user can connect a filter to a scorecard's Row end point and its Column end point, but a user cannot connect a begin point to a scorecard's Row end point twice.

Scorecard: A report type that depicts organizational performance by displaying a collection of key performance indicators (KPIs) together with performance targets for those KPIs. A scorecard can be organized hierarchically.

ReportView: A visual display of data in a dashboard that can be coordinated with other report views by using filters.

Filter: A feature that enables users to modify dashboard views by changing the subset of data that is displayed in reports or scorecards.

KPI (key performance indicator): A predefined measure that is used to track performance of a strategic goal, objective, plan, initiative, or business process. A KPI is evaluated against a target. An explicit and measurable value taken directly from a data source.

Indicator: A set of graphics, text, and colors for defining different levels of performance when comparing an actual value and a target value within a KPI.

DataSource: A reference to a disk, file, document, or other collection of information from which data is taken or moved.

The server (2) also maintains a collection of annotations.

Annotation: One of possibly several notations associated with a comment. Each comment is associated with a single cell in a scorecard and meant to provide related information about the value in that scorecard cell.

3.1.2 Timers

If a request exceeds a query timeout period, the server (2) MUST return a SOAP fault response, which MUST contain the **Query Timeout** <22> **ErrorCode** as specified in section [2.2.2.1](#).

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

This section specifies the server (2) operations.

The following table summarizes the list of operations as defined by this specification.

Operation	Description
CreateAnnotation	The CreateAnnotation operation is used to create an Annotation complex type (section 2.2.4.18) on the server (2).
CreateDashboard	The CreateDashboard operation is used to create a Dashboard complex type (section 2.2.4.79) on the server (2).
CreateDataSource	The CreateDataSource operation is used to create a DataSource complex type (section 2.2.4.85) on the server (2).
CreateFilter	The CreateFilter operation is used to create a Filter complex type (section 2.2.4.98) on the server (2).
CreateIndicator	The CreateIndicator operation is used to create an Indicator complex type (section 2.2.4.125) on the server (2).
CreateKpi	The CreateKpi operation is used to create a Kpi complex type (section 2.2.4.128) on the server (2).
CreateReportView	The CreateReportView operation creates a ReportView complex type (section 2.2.4.160) on the server (2).
CreateScorecard	The CreateScorecard operation creates a Scorecard complex type (section 2.2.4.162) on the server (2).
DeleteAnnotation	The DeleteAnnotation operation deletes an Annotation complex type (section 2.2.4.18) from

Operation	Description
	the server (2).
DeleteDashboard	The DeleteDashboard operation deletes a Dashboard complex type (section 2.2.4.79) from the server (2).
DeleteDataSource	The DeleteDataSource operation deletes a DataSource complex type (section 2.2.4.85) from the server (2).
DeleteFilter	The DeleteFilter operation deletes a Filter complex type (section 2.2.4.98) from the server (2).
DeleteIndicator	The DeleteIndicator operation deletes an Indicator complex type (section 2.2.4.125) from the server (2).
DeleteKpi	The DeleteKpi operation deletes a Kpi complex type (section 2.2.4.128) from the server (2).
DeleteReportView	The DeleteReportView operation deletes a ReportView complex type (section 2.2.4.160) from the server (2).
DeleteScorecard	The DeleteScorecard operation deletes a Scorecard complex type (section 2.2.4.162) from the server (2).
ExportDashboard	The ExportDashboard operation <23> is used to export dashboard pages and their associated content from the server (2) into a specified Deployment Package ([MS-PRIMEPF]).
GenerateView	The GenerateView operation generates the data structure that represents a scorecard grid view, the GridViewData complex type (section 2.2.4.121), based on information stored on the server (2).
GenerateViewDirect	The GenerateViewDirect operation generates the data structure that represents a scorecard grid view (see GridViewData complex type, section 2.2.4.121), using information sent from the client.
GetAllAnnotationsByScorecardLocation	The GetAllAnnotationsByScorecardLocation operation retrieves an array of Annotation complex type elements (section 2.2.4.18) associated with a scorecard.
GetAnalyticReportView	The GetAnalyticReportView operation retrieves a report view from the server (2) that has been created through the SaveTemporaryAnalyticReport (section 3.1.4.65) or CreateReportView (section 3.1.4.7) operation.
GetAnnotation	The GetAnnotation operation retrieves an Annotation complex type (section 2.2.4.18) associated with a scorecard cell from the server (2).
GetAnnotationByID	The GetAnnotationByID operation retrieves an Annotation complex type (section 2.2.4.18) from a

Operation	Description
	specified GUID from the server (2).
GetAnnotationSetting	The Attribute Groups operation retrieves an AnnotationSetting complex type object (section 3.1.4.24.3.1) that contains the annotation settings for the server (2).
GetAsKpis	The GetAsKpis operation takes in an Analysis Services data source along with a server-relative URL to a Kpi complex type (section 2.2.4.128) list (1), and returns a collection of Kpis as defined in the ArrayOfKpi complex type (see section 2.2.4.41).
GetCube	The GetCube operation takes in a RepositoryLocation complex type object (section 2.2.4.161), and returns the associated Cube complex type object (section 2.2.4.78).
GetCubeFromDataSource	The GetCubeFromDataSource operation takes in a data source object and returns the associated Cube complex type object section 2.2.4.78 ().
GetCubeMetaData	The GetCubeMetaData operation takes in an Analysis Services RepositoryLocation complex type object (section 2.2.4.161) and returns the associated Cube complex type object (section 2.2.4.78).
GetCubeMetaDataForDataSource	The GetCubeMetaDataForDataSource operation takes in an Analysis Services data source object and returns the associated Cube complex type object (section 2.2.4.78). This operation is valid for Analysis Services data sources only.
GetCubeNameInfos	The GetCubeNameInfos operation retrieves an ArrayOfNameInfo complex type (section 2.2.4.48) that describes the cubes of the data source (1).
GetCurrentCultureLcid	The GetCurrentCulturLcid operation retrieves the current culture locale identifier.
GetCurrentUserInfo	The GetCurrentUserInfo operation retrieves the user name and display name information of the current user.
GetDashboard	The GetDashboard operation retrieves a dashboard.
GetDatabaseNamesFromDataSource	The GetDatabaseNamesFromDataSource operation retrieves an array of database names associated with the data source (1).
GetDataSource	The GetDataSource operation retrieves a data source (1).
GetDependentElements	The GetDependentElements operation retrieves from the server (2) all FirstClassElement complex types (section 2.2.4.99) associated with a list (1) of repository locations. In addition, all FirstClassElements that are related by reference are also included in the response. For example, for a requested scorecard, all Kpis , Indicators , and

Operation	Description
	DataSources that the scorecard depends on will also be retrieved.
GetDimensions	The GetDimensions operation retrieves an array of dimension (1) objects.
GetDimensionsFromDataSource	The GetDimensionsFromDataSource operation retrieves an array of dimension (1) objects (see section 2.2.4.90).
GetFilter	The GetFilter operation retrieves a Filter complex type (section 2.2.4.98).
GetIndicator	The GetIndicator operation retrieves an Indicator complex type (section 2.2.4.125) from the server (2).
GetKpi	The GetKpi operation retrieves a Kpi complex type object (section 2.2.4.128).
GetKpisFromScorecard	The GetKpisFromScorecard operation retrieves an array of Kpi complex type objects (section 2.2.4.128) associated with a scorecard.
GetLatestAnalyticReportVersion	The GetLatestAnalyticReportVersion operation retrieves from the server (2) the version number for a report view that has been created through SaveTemporaryAnalyticReport operation (section 3.1.4.65).
GetListItems	The GetListItems operation retrieves all FirstClassElements complex types (section 2.2.4.99) associated with a given repository list (1) from the server (2).
GetMdx	The GetMdx operation retrieves an MDX that can be used to query data sources for the given analytic report. The Analytic Chart and Analytic Grid report view types contain custom data that is used to generate MDX queries. See the ReportView complex type (section 2.2.4.160) for more detail.
GetParameterDisplayData	The GetParameterDisplayData operation builds a template data table containing only the columns produced by a specific parameter type. The referred parameter represents a specific kind of connection between two Web Parts. The resulting DataTable (as described in [DataTable]) represents an empty sample of the information that gets passed on that connection.
GetPreviewDataSet	The GetPreviewDataSet method retrieves a data set from a data source, which is suitable for previewing results.
GetQueryResultMembers	The GetQueryResultMembers operation retrieves an array of members (3) associated with the specified report.

Operation	Description
GetRegisteredCustomFCOs	The GetRegisteredCustomFCOs operation retrieves custom object definitions registered on the server (2).
GetReportView	The GetReportView operation retrieves a ReportView complex type (section 2.2.4.160) from the server (2).
GetScorecard	The GetScorecard operation retrieves a Scorecard complex type (section 2.2.4.162).
ImportDashboard	The ImportDashboard operation <24> is used to import content from a specified Deployment Package ([MS-PRIMEPF]) to the server (2).
QueryChildMembers	The QueryChildMembers operation uses a data source for the specified member, and returns a collection of members.
QueryChildMembersByRangeFromDataSource	The QueryChildMembersByRangeFromDataSource operation queries the DataSource complex type (section 2.2.4.85), and returns a collection of child members.
QueryChildMembersFromDataSource	The QueryChildMembersFromDataSource operation uses the data source to retrieve a collection of child members for the specified member name.
QueryDimensionRootMembers	The QueryDimensionRootMembers operation uses a data source (1) from the repository location for the specified member, and returns a collection of root members.
QueryDimensionRootMembersFromDataSource	The QueryDimensionRootMembersFromDataSource method uses the data source to retrieve a collection of root members for the specified member name.
QueryNamedSets	The QueryNamedSets operation is used to retrieve the named sets that are defined by a data source (1) when given the RepositoryLocation complex type (section 2.2.4.161) of the data source (1).
QueryNamedSetsFromDataSource	The QueryNamedSetsFromDataSource operation is used to retrieve the named sets that are defined by the given data source (1).
QueryRelatedMember	The QueryRelatedmember operation is used to retrieve a member (3) having the specified relationship to the specified member from the data source (1) at the given RepositoryLocation complex type (section 2.2.4.161).
QueryRelatedMemberFromDataSource	The QueryRelatedMemberFromDataSource operation queries the given data source (1) for the member (3) having the specified relationship to the specified member.

Operation	Description
QueryTimeIntelligence	The QueryTimeIntelligence operation queries a data source (1) location for the members (3) that are specified by a time intelligence formula.
QueryTimeIntelligenceDirect	The QueryTimeIntelligenceDirect operation queries the provided data source (1) for the members (3) that are specified by a time intelligence formula.
QueryTransformMembers	The QueryTransformMembers method transforms any collection of Member complex types (section 2.2.4.134) into a new member collection based on the operation passed on the transformType parameter of the QueryTransformMembers element (section 3.1.4.64.2.1) as specified in section 3.1.4.64.4.1 .
SaveTemporaryAnalyticReport	The SaveTemporaryAnalyticReport operation stores a temporary copy of a ReportView complex type (section 2.2.4.160) to the server (2).
TestConnection	The TestConnection operation is used to determine whether a connection as specified by the dataSource element can be established.
TrimAnnotationByOwner	The TrimAnnotationByOwner operation removes all the Annotation complex types (section 2.2.4.18) that are owned by a specific user.
TrimAnnotationByScorecardLocation	The TrimAnnotationByScorecardLocation operation removes all the annotations that belong to a scorecard at a specific location.
TrimAnnotationUntouchedSince	The TrimAnnotationUntouchedSince operation removes all the Annotation complex types (section 2.2.4.18) that haven't been updated since the specified date.
UpdateAnnotation	The UpdateAnnotation operation updates an existing Annotation complex type (section 2.2.4.18).
UpdateDashboard	The UpdateDashboard operation updates an existing Dashboard complex type (section 2.2.4.79).
UpdateDataSource	The UpdateDataSource operation updates an existing DataSource complex type (section 2.2.4.85).
UpdateFilter	The UpdateFilter operation is used to update the existing filter as specified by the Filter complex type object (section 2.2.4.98) in the UpdateFilter input element (section 3.1.4.73.2.1).
UpdateIndicator	The UpdateIndicator operation is used to update the existing Indicator as specified by the Indicator complex type object (section 2.2.4.125) in the UpdateIndicator input element (section 2.2.4.125).

Operation	Description
	3.1.4.74.2.1).
UpdateKpi	The UpdateKpi operation is used to update the existing KPI as specified by the Kpi complex type object (section 2.2.4.128) in the UpdateKpi input element (section 3.1.4.75.2.1).
UpdateReportView	The UpdateReportView operation is used to update the existing report view as specified by the ReportView complex type object (section 2.2.4.160) in the UpdateReportView input element (section 3.1.4.76.2.1).
UpdateScorecard	The UpdateScorecard operation is used to update the existing scorecard as specified by the Scorecard complex type object (section 2.2.4.162) in the UpdateScorecard input element (section 3.1.4.77.2.1).
ValidateKpi	The ValidateKpi operation checks whether a KPI stored on the server (2) is valid.
ValidateScorecard	The ValidateScorecard operation checks if a scorecard stored on the server (2) is valid.
ValidateSiteCollection	The ValidateSiteCollection operation is used to check if the context site has the server (2) feature installed.

3.1.4.1 CreateAnnotation

The **CreateAnnotation** operation is used to create an **Annotation** complex type (section [2.2.4.18](#)) on the server (2).

The following is the WSDL port type specification of the **CreateAnnotation WSDL operation**.

```
<wsdl:operation name="CreateAnnotation" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CreateAnnotationSoapIn"/>
  <wsdl:output message="tns:CreateAnnotationSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CreateAnnotationSoapIn** request message (section [3.1.4.1.1.1](#)), and the server (2) responds with a **CreateAnnotationSoapOut** response message (section [3.1.4.1.1.2](#)) as follows:

- The protocol client MUST send the **Annotation** to be created.
- The server (2) MUST create the specified **Annotation** in the database.
- If creation is successful, the server (2) MUST return the created **Annotation** whose following fields are updated:
 - CreatedOn
 - Guid

- LastUpdatedOn

ErrorCode	Description
AnnotationNotEnabled	See Full List of Possible Error Codes (section 2.2.2.1.2).
InvalidAnnotation	See Full List of Possible Error Codes (section 2.2.2.1.2).
InvalidComment	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the **ErrorCode** MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.1.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CreateAnnotationSoapIn	The request WSDL message for the CreateAnnotation WSDL operation.
CreateAnnotationSoapOut	The response WSDL message for the CreateAnnotation WSDL operation.

3.1.4.1.1.1 CreateAnnotationSoapIn

The request WSDL message for the **CreateAnnotation** WSDL operation.

The **SOAP action** value is:

```
http://www.microsoft.com/performancepoint/scorecards/CreateAnnotation
```

The **SOAP body** contains the **CreateAnnotation** element.

3.1.4.1.1.2 CreateAnnotationSoapOut

The response WSDL message for the **CreateAnnotation** WSDL operation.

The SOAP body contains the **CreateAnnotationResponse** element.

3.1.4.1.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CreateAnnotation	The input data for the CreateAnnotation WSDL operation.
CreateAnnotationResponse	The result data for the CreateAnnotation WSDL operation.

3.1.4.1.2.1 CreateAnnotation

The **CreateAnnotation** element specifies the input data for the **CreateAnnotation** WSDL operation.

```
<xs:element name="CreateAnnotation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="annotation" type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

annotation: The **Annotation** complex type (section [2.2.4.18](#)) to be created on the server (2). This element **MUST** be present.

3.1.4.1.2.2 CreateAnnotationResponse

The **CreateAnnotationResponse** element specifies the result data for the **CreateAnnotation** WSDL operation.

```
<xs:element name="CreateAnnotationResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateAnnotationResult"
type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CreateAnnotationResult: The **Annotation** complex type (section [2.2.4.18](#)) created on the server (2). This element **MUST** be present. All of the fields **MUST** be set as designated in section [3.1.4.1](#).

3.1.4.1.3 Complex Types

None.

3.1.4.1.4 Simple Types

None.

3.1.4.1.5 Attributes

None.

3.1.4.1.6 Groups

None.

3.1.4.1.7 Attribute Groups

None.

3.1.4.2 CreateDashboard

The **CreateDashboard** operation is used to create a **Dashboard** complex type (section [2.2.4.79](#)) on the server (2).

The following is the WSDL port type specification of the **CreateDashboard** WSDL operation.

```
<wsdl:operation name="CreateDashboard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CreateDashboardSoapIn"/>
  <wsdl:output message="tns:CreateDashboardSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CreateDashboardSoapIn** request message (section [3.1.4.2.1.1](#)), and the server (2) responds with a **CreateDashboardSoapOut** response message (section [3.1.4.2.1.2](#)) as follows:

- The protocol client MUST send the **Dashboard** and its target location on the server (2).
- The server (2) MUST create the specified **Dashboard** at the specified server (2) location.
- If creation is successful, the server (2) MUST return the created **Dashboard** with the following fields set, as specified in the **FirstClassElement** complex type (section [2.2.4.99](#)):
 - Location
 - CreatedBy
 - ModifiedBy
 - CreatedDate
 - LastModified
 - Version

ErrorCode	Description
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common list of Error Codes (section 2.2.2.1.3).
FCOCreateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationUrlLength	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationAbsoluteUrl	See Common List of Error Codes (section 2.2.2.1.3).

ErrorCode	Description
Unknown	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the **ErrorCode** MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.2.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CreateDashboardSoapIn	The request WSDL message for the CreateDashboard WSDL operation.
CreateDashboardSoapOut	The response WSDL message for the CreateDashboard WSDL operation.

3.1.4.2.1.1 CreateDashboardSoapIn

The request WSDL message for the **CreateDashboard** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/CreateDashboard
```

The SOAP body contains the **CreateDashboard** element.

3.1.4.2.1.2 CreateDashboardSoapOut

The response WSDL message for the **CreateDashboard** WSDL operation.

The SOAP body contains the **CreateDashboardResponse** element.

3.1.4.2.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CreateDashboard	The input data for the CreateDashboard WSDL operation.
CreateDashboardResponse	The result data for the CreateDashboard WSDL operation.

3.1.4.2.2.1 CreateDashboard

The **CreateDashboard** element specifies the input data for the **CreateDashboard** WSDL operation.

```
<xs:element name="CreateDashboard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
```

```

<xs:sequence>
  <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
  <xs:element minOccurs="0" maxOccurs="1" name="dashboard" type="tns:Dashboard"/>
</xs:sequence>
</xs:complexType>
</xs:element>

```

listUrl: The location on the server (2) where the dashboard is created. This element MUST be present. It MUST be a valid URL as specified in [\[RFC1738\]](#) and MUST be a valid **subsite** on the server (2).

dashboard: The **Dashboard** complex type (section [2.2.4.79](#)) to be created on the server (2). This element MUST be present.

3.1.4.2.2 CreateDashboardResponse

The **CreateDashboardResponse** element specifies the result data for the **CreateDashboard** WSDL operation.

```

<xs:element name="CreateDashboardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateDashboardResult"
        type="tns:Dashboard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

CreateDashboardResult: The **Dashboard** complex type (section [2.2.4.79](#)) created on the server (2). This element MUST be present. All of the fields MUST be set as designated in section [3.1.4.2](#).

3.1.4.2.3 Complex Types

None.

3.1.4.2.4 Simple Types

None.

3.1.4.2.5 Attributes

None.

3.1.4.2.6 Groups

None.

3.1.4.2.7 Attribute Groups

None.

3.1.4.3 CreateDataSource

The **CreateDataSource** operation is used to create a **DataSource** complex type (section [2.2.4.85](#)) on the server (2).

The following is the WSDL port type specification of the **CreateDataSource** WSDL operation.

```
<wsdl:operation name="CreateDataSource" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CreateDataSourceSoapIn"/>
  <wsdl:output message="tns:CreateDataSourceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CreateDataSourceSoapIn** request message (section [3.1.4.3.1.1](#)), and the server (2) responds with a **CreateDataSourceSoapOut** response message (section [3.1.4.3.1.2](#)) as follows:

- The protocol client MUST send the **DataSource** and its target location on the server (2).
- The server (2) MUST create the specified **DataSource** at the specified server (2) location.
- If creation is successful, the server (2) MUST return the created **DataSource** with the following fields set as specified in the **FirstClassElement** complex type (section [2.2.4.99](#)):
 - Location
 - CreatedBy
 - ModifiedBy
 - CreatedDate
 - LastModified
 - Version

Error code	Description
InvalidDataSource	See Common List of Error Codes (section 2.2.2.1.3).
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common list of Error Codes (section 2.2.2.1.3).
FCOCreateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationUrlLength	See Common List of Error Codes (section 2.2.2.1.3).

Error code	Description
RepositoryLocationAbsoluteUrl	See Common List of Error Codes (section 2.2.2.1.3).
Unknown	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.3.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CreateDataSourceSoapIn	The request WSDL message for the CreateDataSource WSDL operation.
CreateDataSourceSoapOut	The response WSDL message for the CreateDataSource WSDL operation.

3.1.4.3.1.1 CreateDataSourceSoapIn

The request WSDL message for the **CreateDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/CreateDataSource
```

The SOAP body contains the **CreateDataSource** element.

3.1.4.3.1.2 CreateDataSourceSoapOut

The response WSDL message for the **CreateDataSource** WSDL operation.

The SOAP body contains the **CreateDataSourceResponse** element.

3.1.4.3.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CreateDataSource	The input data for the CreateDataSource WSDL operation.
CreateDataSourceResponse	The result data for the CreateDataSource WSDL operation.

3.1.4.3.2.1 CreateDataSource

The **CreateDataSource** element specifies the input data for the **CreateDataSource** WSDL operation.

```

<xs:element name="CreateDataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

listUrl: The location on the server (2) where the **DataSource** complex type (section [2.2.4.85](#)) is to be created. This element MUST be present. It MUST be a valid relative URL as specified in [\[RFC1808\]](#) and MUST be a site (2) on the server (2).

dataSource: The **DataSource** to be created on the server (2). This element MUST be present.

3.1.4.3.2 CreateDataSourceResponse

The **CreateDataSourceResponse** element specifies the result data for the **CreateDataSource** WSDL operation.

```

<xs:element name="CreateDataSourceResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateDataSourceResult"
type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

CreateDataSourceResult: The **DataSource** complex type (section [2.2.4.85](#)) created on the server (2). This element MUST be present. All of the fields MUST be set as designated in section [3.1.4.3](#).

3.1.4.3.3 Complex Types

None.

3.1.4.3.4 Simple Types

None.

3.1.4.3.5 Attributes

None.

3.1.4.3.6 Groups

None.

3.1.4.3.7 Attribute Groups

None.

3.1.4.4 CreateFilter

The **CreateFilter** operation is used to create a **Filter** complex type (section [2.2.4.98](#)) on the server (2).

The following is the WSDL port type specification of the **CreateFilter** WSDL operation.

```
<wsdl:operation name="CreateFilter" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CreateFilterSoapIn"/>
  <wsdl:output message="tns:CreateFilterSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CreateFilterSoapIn** request message (section [3.1.4.4.1.1](#)), and the server (2) responds with a **CreateFilterSoapOut** response message (section [3.1.4.4.1.2](#)) as follows:

- The protocol client MUST send the **Filter** and its target location on the server (2).
- The server (2) MUST create the specified **Filter** at the specified server (2) location.
- If creation is successful, the server (2) MUST return the created Filter with the following fields set as specified in the **FirstClassElement** complex type (section [2.2.4.99](#)):
 - CreatedBy
 - CreatedDate
 - LastModified
 - Location
 - ModifiedBy
 - Version

Error code	Description
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common list of Error Codes (section 2.2.2.1.3).
FCOCreateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationUrlLength	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationAbsoluteUrl	See Common List of Error Codes (section 2.2.2.1.3).
Unknown	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.4.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CreateFilterSoapIn	The request WSDL message for the CreateFilter WSDL operation.
CreateFilterSoapOut	The response WSDL message for the CreateFilter WSDL operation.

3.1.4.4.1.1 CreateFilterSoapIn

The request WSDL message for the **CreateFilter** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/CreateFilter
```

The SOAP body contains the **CreateFilter** element.

3.1.4.4.1.2 CreateFilterSoapOut

The response WSDL message for the **CreateFilter** WSDL operation.

The SOAP body contains the **CreateFilterResponse** element.

3.1.4.4.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CreateFilter	The input data for the CreateFilter WSDL operation.
CreateFilterResponse	The result data for the CreateFilter WSDL operation.

3.1.4.4.2.1 CreateFilter

The **CreateFilter** element specifies the input data for the **CreateFilter** WSDL operation.

```
<xs:element name="CreateFilter" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="filter" type="tns:Filter"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```


listUrl: The location on the server (2) where the **Filter** complex type (section [2.2.4.98](#)) is to be created. This element **MUST** be present. It **MUST** be a valid relative URL, as specified in [\[RFC1808\]](#) and **MUST** be a valid site (2) on the server (2).

filter: The Filter to be created on the server (2). This element **MUST** be present.

3.1.4.4.2 CreateFilterResponse

The **CreateFilterResponse** element specifies the result data for the **CreateFilter** WSDL operation.

```
<xs:element name="CreateFilterResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateFilterResult" type="tns:Filter"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CreateFilterResult: The **Filter** complex type (section [2.2.4.98](#)) created on the server (2). This element **MUST** be present. All of the fields **MUST** be set as designated in section [3.1.4.4](#).

3.1.4.4.3 Complex Types

None.

3.1.4.4.4 Simple Types

None.

3.1.4.4.5 Attributes

None.

3.1.4.4.6 Groups

None.

3.1.4.4.7 Attribute Groups

None.

3.1.4.5 CreateIndicator

The **CreateIndicator** operation is used to create an **Indicator** complex type (section [2.2.4.125](#)) on the server (2).

The following is the WSDL port type specification of the **CreateIndicator** WSDL operation.

```
<wsdl:operation name="CreateIndicator" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CreateIndicatorSoapIn"/>
  <wsdl:output message="tns:CreateIndicatorSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CreateIndicatorSoapIn** request message (section [3.1.4.5.1.1](#)), and the server (2) responds with a **CreateIndicatorSoapOut** response message (section [3.1.4.5.1.2](#)) as follows:

- The protocol client MUST send the **Indicator** and its target location on the server (2).
- The server (2) MUST create the specified **Indicator** at the specified server (2) location.
- If creation is successful, the server (2) MUST return the created **Indicator** with the following fields set as specified in the **FirstClassElement** complex type (section [2.2.4.99](#)):
 - Location
 - CreatedBy
 - ModifiedBy
 - CreatedDate
 - LastModified
 - Version

Error code	Description
InvalidIndicator	See Common List of Error Codes (section 2.2.2.1.3).
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common list of Error Codes (section 2.2.2.1.3).
FCOCreateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationUrlLength	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationAbsoluteUrl	See Common List of Error Codes (section 2.2.2.1.3).
Unknown	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.5.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CreateIndicatorSoapIn	The request WSDL message for the CreateIndicator WSDL operation.
CreateIndicatorSoapOut	The response WSDL message for the CreateIndicator WSDL operation.

3.1.4.5.1.1 CreateIndicatorSoapIn

The request WSDL message for the **CreateIndicator** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/CreateIndicator
```

The SOAP body contains the **CreateIndicator** element.

3.1.4.5.1.2 CreateIndicatorSoapOut

The response WSDL message for the **CreateIndicator** WSDL operation.

The SOAP body contains the **CreateIndicatorResponse** element.

3.1.4.5.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CreateIndicator	The input data for the CreateIndicator WSDL operation.
CreateIndicatorResponse	The result data for the CreateIndicator WSDL operation.

3.1.4.5.2.1 CreateIndicator

The **CreateIndicator** element specifies the input data for the **CreateIndicator** WSDL operation.

```
<xs:element name="CreateIndicator" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="indicator" type="tns:Indicator"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

listUrl: The location on the server (2) where the **Indicator** complex type (section [2.2.4.125](#)) is to be created. This element **MUST** be present. It **MUST** be a valid relative URL as specified in [\[RFC1808\]](#) and **MUST** be a valid site (2) on the server (2).

indicator: The **Indicator** to be created on the server (2). **MUST** be present.

3.1.4.5.2 CreateIndicatorResponse

The **CreateIndicatorResponse** element specifies the result data for the **CreateIndicator** WSDL operation.

```
<xs:element name="CreateIndicatorResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateIndicatorResult"
        type="tns:Indicator"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CreateIndicatorResult: The **Indicator** complex type (section [2.2.4.125](#)) created on the server (2). This element **MUST** be present. All of the fields **MUST** be set as designated in section [3.1.4.5](#).

3.1.4.5.3 Complex Types

None.

3.1.4.5.4 Simple Types

None.

3.1.4.5.5 Attributes

None.

3.1.4.5.6 Groups

None.

3.1.4.5.7 Attribute Groups

None.

3.1.4.6 CreateKpi

The **CreateKpi** operation is used to create a **Kpi** complex type (section [2.2.4.128](#)) on the server (2).

The following is the WSDL port type specification of the **CreateKpi** WSDL operation.

```
<wsdl:operation name="CreateKpi" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CreateKpiSoapIn"/>
  <wsdl:output message="tns:CreateKpiSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CreateKpiSoapIn** request message (section [3.1.4.6.1.1](#)), and the server (2) responds with a **CreateKpiSoapOut** response message (section [3.1.4.6.1.2](#)) as follows:

- The protocol client **MUST** send the **Kpi** and its target location on the server (2).

- The server (2) MUST create the specified **Kpi** at the specified server (2) location.
- If creation is successful, the server (2) MUST return the created **Kpi** with the following fields set as specified in the **FirstClassElement** (section [2.2.4.99](#)) and **KpiMeasure** (section [2.2.4.129](#)) complex types:
 - Location
 - CreatedBy
 - ModifiedBy
 - CreatedDate
 - LastModified
 - Version
 - Actuals.OwnerKpiLocation
 - Targets.OwnerKpiLocation

Error code	Description
InvalidKpi	See Common List of Error Codes (section 2.2.2.1.3).
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common list of Error Codes (section 2.2.2.1.3).
FCOCreateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationUrlLength	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationAbsoluteUrl	See Common List of Error Codes (section 2.2.2.1.3).
Unknown	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.6.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CreateKpiSoapIn	The request WSDL message for the CreateKpi WSDL operation.
CreateKpiSoapOut	The response WSDL message for the CreateKpi WSDL operation.

3.1.4.6.1.1 CreateKpiSoapIn

The request WSDL message for the **CreateKpi** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/CreateKpi
```

The SOAP body contains the **CreateKpi** element.

3.1.4.6.1.2 CreateKpiSoapOut

The response WSDL message for the **CreateKpi** WSDL operation.

The SOAP body contains the **CreateKpiResponse** element.

3.1.4.6.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CreateKpi	The input data for the CreateKpi WSDL operation.
CreateKpiResponse	The result data for the CreateKpi WSDL operation.

3.1.4.6.2.1 CreateKpi

The **CreateKpi** element specifies the input data for the **CreateKpi** WSDL operation.

```
<xs:element name="CreateKpi" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="kpi" type="tns:Kpi"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

listUrl: The location on the server (2) where the **Kpi** complex type (section [2.2.4.128](#)) is to be created. This element **MUST** be present. It **MUST** be a valid relative URL as specified in [\[RFC1808\]](#) and **MUST** be a valid site (2) on the server (2).

kpi: The KPI to be created on the server (2). This element **MUST** be present.

3.1.4.6.2.2 CreateKpiResponse

The **CreateKpiResponse** element specifies the result data for the **CreateKpi** WSDL operation.

```
<xs:element name="CreateKpiResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateKpiResult" type="tns:Kpi"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CreateKpiResult: The **Kpi** complex type (section [2.2.4.128](#)) created on the server (2). This element **MUST** be present. All of the fields **MUST** be set as designated in section [3.1.4.6](#).

3.1.4.6.3 Complex Types

None.

3.1.4.6.4 Simple Types

None.

3.1.4.6.5 Attributes

None.

3.1.4.6.6 Groups

None.

3.1.4.6.7 Attribute Groups

None.

3.1.4.7 CreateReportView

The **CreateReportView** operation creates a **ReportView** complex type (section [2.2.4.160](#)) on the server (2).

The following is the WSDL port type specification of the **CreateReportView** WSDL operation.

```
<wsdl:operation name="CreateReportView" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CreateReportViewSoapIn"/>
  <wsdl:output message="tns:CreateReportViewSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CreateReportViewSoapIn** request message (section [3.1.4.7.1.1](#)), and the server (2) responds with a **CreateReportViewSoapOut** response message (section [3.1.4.7.1.2](#)) as follows:

- The protocol client **MUST** send the **ReportView** and URL location.
- The server (2) **MUST** create the specified **ReportView** at the specified URL location.

- If creation is successful, the server (2) MUST return the created **ReportView** with the following fields set as specified in the **FirstClassElement** complex type (section [2.2.4.99](#)):
 - Location
 - CreatedBy
 - ModifiedBy
 - CreatedDate
 - LastModified
 - Version

Error code	Description
InvalidReportView	See Common List of Error Codes (section 2.2.2.1.3).
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common list of Error Codes (section 2.2.2.1.3).
FCOCreateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationUrlLength	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationAbsoluteUrl	See Common List of Error Codes (section 2.2.2.1.3).
Unknown	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.7.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CreateReportViewSoapIn	The request WSDL message for the CreateReportView WSDL operation.
CreateReportViewSoapOut	The response WSDL message for the CreateReportView WSDL operation.

3.1.4.7.1.1 CreateReportViewSoapIn

The request WSDL message for the **CreateReportView** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/CreateReportView
```

The SOAP body contains the **CreateReportView** element.

3.1.4.7.1.2 CreateReportViewSoapOut

The response WSDL message for the **CreateReportView** WSDL operation.

The SOAP body contains the **CreateReportViewResponse** element.

3.1.4.7.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CreateReportView	The input data for the CreateReportView WSDL operation.
CreateReportViewResponse	The result data for the CreateReportView WSDL operation.

3.1.4.7.2.1 CreateReportView

The **CreateReportView** element specifies the input data for the **CreateReportView** WSDL operation.

```
<xs:element name="CreateReportView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="reportView" type="tns:ReportView"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

listUrl: The location on the server (2) where the **ReportView** complex type (section [2.2.4.160](#)) is to be created. This element **MUST** be present. It **MUST** be a valid relative URL as specified in [\[RFC1808\]](#) and **MUST** be a valid site (2) on the server (2).

reportView: The **ReportView** to be created on the server (2). This element **MUST** be present.

3.1.4.7.2.2 CreateReportViewResponse

The **CreateReportViewResponse** element specifies the result data for the **CreateReportView** WSDL operation.

```
<xs:element name="CreateReportViewResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
```

```

    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateReportViewResult"
        type="tns:ReportView"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

CreateReportViewResult: The **ReportView** complex type (section [2.2.4.160](#)) created on the server (2). This element MUST be present. All of the fields MUST be set as designated in section [3.1.4.7](#).

3.1.4.7.3 Complex Types

None.

3.1.4.7.4 Simple Types

None.

3.1.4.7.5 Attributes

None.

3.1.4.7.6 Groups

None.

3.1.4.7.7 Attribute Groups

None.

3.1.4.8 CreateScorecard

The **CreateScorecard** operation creates a **Scorecard** complex type (section [2.2.4.162](#)) on the server (2).

The following is the WSDL port type specification of the **CreateScorecard** WSDL operation.

```

<wsdl:operation name="CreateScorecard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CreateScorecardSoapIn"/>
  <wsdl:output message="tns:CreateScorecardSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **CreateScorecardSoapIn** request message (section [3.1.4.8.1.1](#)), and the server (2) responds with a **CreateScorecardSoapOut** response message (section [3.1.4.8.1.2](#)) as follows:

- The protocol client MUST send the **Scorecard** and URL location.
- The server (2) MUST create the specified **Scorecard** at the specified URL location.
- If creation is successful, the server (2) MUST return the created **Scorecard** with the following fields set as specified in the **FirstClassElement** complex type (section [2.2.4.99](#)):

- Location
- CreatedBy
- ModifiedBy
- CreatedDate
- LastModified
- Version

Error code	Description
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common list of Error Codes (section 2.2.2.1.3).
FCOCreateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
FCOCreateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationUrlLength	See Common List of Error Codes (section 2.2.2.1.3).
RepositoryLocationAbsoluteUrl	See Common List of Error Codes (section 2.2.2.1.3).
Unknown	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.8.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CreateScorecardSoapIn	The request WSDL message for the CreateScorecard WSDL operation.
CreateScorecardSoapOut	The response WSDL message for the CreateScorecard WSDL operation.

3.1.4.8.1.1 CreateScorecardSoapIn

The request WSDL message for the **CreateScorecard** WSDL operation.

The SOAP action value is:

<http://www.microsoft.com/performancepoint/scorecards/CreateScorecard>

The SOAP body contains the **CreateScorecard** element.

3.1.4.8.1.2 CreateScorecardSoapOut

The response WSDL message for the **CreateScorecard** WSDL operation.

The SOAP body contains the **CreateScorecardResponse** element.

3.1.4.8.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CreateScorecard	The input data for the CreateScorecard WSDL operation.
CreateScorecardResponse	The result data for the CreateScorecard WSDL operation.

3.1.4.8.2.1 CreateScorecard

The **CreateScorecard** element specifies the input data for the **CreateScorecard** WSDL operation.

```
<xs:element name="CreateScorecard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecard" type="tns:Scorecard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

listUrl: The location on the server (2) where a Scorecard complex type (section [2.2.4.162](#)) is to be created. This element **MUST** present. It **MUST** be a valid relative URL as specified in [\[RFC1808\]](#) and **MUST** be a valid site (2) on the server (2).

scorecard: The Scorecard to be created on the server (2). This element **MUST** be present.

3.1.4.8.2.2 CreateScorecardResponse

The **CreateScorecardResponse** element specifies the result data for the **CreateScorecard** WSDL operation.

```
<xs:element name="CreateScorecardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateScorecardResult"
type="tns:Scorecard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CreateScorecardResult: A Scorecard complex type (section [2.2.4.162](#)) created on the server (2). This element **MUST** be present. All of the fields **MUST** be set as designated in section [3.1.4.8](#).

3.1.4.8.3 Complex Types

None.

3.1.4.8.4 Simple Types

None.

3.1.4.8.5 Attributes

None.

3.1.4.8.6 Groups

None.

3.1.4.8.7 Attribute Groups

None.

3.1.4.9 DeleteAnnotation

The **DeleteAnnotation** operation deletes an **Annotation** complex type (section [2.2.4.18](#)) from the server (2).

The following is the WSDL port type specification of the **DeleteAnnotation** WSDL operation.

```
<wsdl:operation name="DeleteAnnotation" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns>DeleteAnnotationSoapIn"/>
  <wsdl:output message="tns>DeleteAnnotationSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteAnnotationSoapIn** request message (section [3.1.4.9.1.1](#)), and the server (2) responds with a **DeleteAnnotationSoapOut** response message (section [3.1.4.9.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) of an **Annotation**.
- The server (2) **MUST** delete the **Annotation**.

Exceptions:

Error code	Description
AnnotationNotEnabled	Annotations are not enabled in the server (2).
AnnotationDeleteNotEnabled	If Annotation Delete is not enabled in the server (2), but this request, which would delete comments, is received, the comments will not be changed on the server (2) and the AnnotationDeleteNotEnabled error code will be returned.

Error code	Description
InvalidAnnotation	The annotation does not exist in the server (2).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.9.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteAnnotationSoapIn	The request WSDL message for the DeleteAnnotation WSDL operation.
DeleteAnnotationSoapOut	The response WSDL message for the DeleteAnnotation WSDL operation.

3.1.4.9.1.1 DeleteAnnotationSoapIn

The request WSDL message for the **DeleteAnnotation** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/DeleteAnnotation
```

The SOAP body contains the **DeleteAnnotation** element.

3.1.4.9.1.2 DeleteAnnotationSoapOut

The response WSDL message for the **DeleteAnnotation** WSDL operation.

The SOAP body contains the **DeleteAnnotationResponse** element.

3.1.4.9.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteAnnotation	The input data for the DeleteAnnotation WSDL operation.
DeleteAnnotationResponse	The result data for the DeleteAnnotation WSDL operation.

3.1.4.9.2.1 DeleteAnnotation

The **DeleteAnnotation** element specifies the input data for the **DeleteAnnotation** WSDL operation.

```
<xs:element name="DeleteAnnotation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
```

```
<xs:element minOccurs="1" maxOccurs="1" name="annotationID"
  xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
</xs:sequence>
</xs:complexType>
</xs:element>
```

annotationID: A GUID that specifies the **Annotation** complex type (section [2.2.4.18](#)) to be deleted. This element **MUST** be present.

3.1.4.9.2.2 DeleteAnnotationResponse

The **DeleteAnnotationResponse** element specifies the result data for the **DeleteAnnotation** WSDL operation.

```
<xs:element name="DeleteAnnotationResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.9.3 Complex Types

None.

3.1.4.9.4 Simple Types

None.

3.1.4.9.5 Attributes

None.

3.1.4.9.6 Groups

None.

3.1.4.9.7 Attribute Groups

None.

3.1.4.10 DeleteDashboard

The **DeleteDashboard** operation deletes a **Dashboard** complex type (section [2.2.4.79](#)) from the server (2).

The following is the WSDL port type specification of the **DeleteDashboard** WSDL operation.

```
<wsdl:operation name="DeleteDashboard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteDashboardSoapIn"/>
  <wsdl:output message="tns:DeleteDashboardSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteDashboardSoapIn** request message (section [3.1.4.10.1.1](#)), and the server (2) responds with a **DeleteDashboardSoapOut** response message (section [3.1.4.10.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) of a **Dashboard**.
- The server (2) MUST delete the **Dashboard**.

Exceptions:

Error code	Description
FCODeleteFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCODeleteFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the ErrorCode MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.10.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteDashboardSoapIn	The request WSDL message for the DeleteDashboard WSDL operation.
DeleteDashboardSoapOut	The response WSDL message for the DeleteDashboard WSDL operation.

3.1.4.10.1.1 DeleteDashboardSoapIn

The request WSDL message for the **DeleteDashboard** WSDL operation.

The SOAP action value is:

`http://www.microsoft.com/performancepoint/scorecards/DeleteDashboard`

The SOAP body contains the **DeleteDashboard** element.

3.1.4.10.1.2 DeleteDashboardSoapOut

The response WSDL message for the **DeleteDashboard** WSDL operation.

The SOAP body contains the **DeleteDashboardResponse** element.

3.1.4.10.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteDashboard	The input data for the DeleteDashboard WSDL operation.
DeleteDashboardResponse	The result data for the DeleteDashboard WSDL operation.

3.1.4.10.2.1 DeleteDashboard

The **DeleteDashboard** element specifies the input data for the **DeleteDashboard** WSDL operation.

```
<xs:element name="DeleteDashboard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present and MUST contain the location of a **Dashboard** complex type (section [2.2.4.79](#)).

3.1.4.10.2.2 DeleteDashboardResponse

The **DeleteDashboardResponse** element specifies the result data for the **DeleteDashboard** WSDL operation.

```
<xs:element name="DeleteDashboardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.10.3 Complex Types

None.

3.1.4.10.4 Simple Types

None.

3.1.4.10.5 Attributes

None.

3.1.4.10.6 Groups

None.

3.1.4.10.7 Attribute Groups

None.

3.1.4.11 DeleteDataSource

The **DeleteDataSource** operation deletes a **DataSource** complex type (section [2.2.4.85](#)) from the server (2).

The following is the WSDL port type specification of the **DeleteDataSource** WSDL operation.

```
<wsdl:operation name="DeleteDataSource" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteDataSourceSoapIn"/>
  <wsdl:output message="tns:DeleteDataSourceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteDataSourceSoapIn** request message (section [3.1.4.11.1.1](#)), and the server (2) responds with a **DeleteDataSourceSoapOut** response message (section [3.1.4.11.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) for a **DataSource**.
- The server (2) MUST delete the **DataSource**.

Exceptions:

Error code	Description
FCDeleteFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCDeleteFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.11.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteDataSourceSoapIn	The request WSDL message for the DeleteDataSource WSDL operation.
DeleteDataSourceSoapOut	The response WSDL message for the DeleteDataSource WSDL operation.

3.1.4.11.1.1 DeleteDataSourceSoapIn

The request WSDL message for the **DeleteDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/DeleteDataSource
```

The SOAP body contains the **DeleteDataSource** element.

3.1.4.11.1.2 DeleteDataSourceSoapOut

The response WSDL message for the **DeleteDataSource** WSDL operation.

The SOAP body contains the **DeleteDataSourceResponse** element.

3.1.4.11.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteDataSource	The input data for the DeleteDataSource WSDL operation.
DeleteDataSourceResponse	The result data for the DeleteDataSource WSDL operation.

3.1.4.11.2.1 DeleteDataSource

The **DeleteDataSource** element specifies the input data for the **DeleteDataSource** WSDL operation.

```
<xs:element name="DeleteDataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present. It MUST contain the location of a **DataSource**.

3.1.4.11.2.2 DeleteDataSourceResponse

The **DeleteDataSourceResponse** element specifies the result data for the **DeleteDataSource** WSDL operation.

```
<xs:element name="DeleteDataSourceResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.11.3 Complex Types

None.

3.1.4.11.4 Simple Types

None.

3.1.4.11.5 Attributes

None.

3.1.4.11.6 Groups

None.

3.1.4.11.7 Attribute Groups

None.

3.1.4.12 DeleteFilter

The **DeleteFilter** operation deletes a **Filter** complex type (section [2.2.4.98](#)) from the server (2).

The following is the WSDL port type specification of the **DeleteFilter** WSDL operation.

```
<wsdl:operation name="DeleteFilter" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteFilterSoapIn"/>
  <wsdl:output message="tns:DeleteFilterSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteFilterSoapIn** request message (section [3.1.4.12.1.1](#)), and the server (2) responds with a **DeleteFilterSoapOut** response message (section [3.1.4.12.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) of a **Filter**.
- The server (2) MUST delete the **Filter**.

Exceptions:

Error code	Description
FCODeleteFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCODeleteFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.12.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteFilterSoapIn	The request WSDL message for the DeleteFilter WSDL operation.
DeleteFilterSoapOut	The response WSDL message for the DeleteFilter WSDL operation.

3.1.4.12.1.1 DeleteFilterSoapIn

The request WSDL message for the **DeleteFilter** WSDL operation.

The SOAP action value is:

The SOAP body contains the **DeleteFilter** element.

3.1.4.12.1.2 DeleteFilterSoapOut

The response WSDL message for the **DeleteFilter** WSDL operation.

The SOAP body contains the **DeleteFilterResponse** element.

3.1.4.12.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteFilter	The input data for the DeleteFilter WSDL operation.
DeleteFilterResponse	The result data for the DeleteFilter WSDL operation.

3.1.4.12.2.1 DeleteFilter

The **DeleteFilter** element specifies the input data for the **DeleteFilter** WSDL operation.

```
<xs:element name="DeleteFilter" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present. It MUST contain the location of a **Filter**.

3.1.4.12.2.2 DeleteFilterResponse

The **DeleteFilterResponse** element specifies the result data for the **DeleteFilter** WSDL operation.

```
<xs:element name="DeleteFilterResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.12.3 Complex Types

None.

3.1.4.12.4 Simple Types

None.

3.1.4.12.5 Attributes

None.

3.1.4.12.6 Groups

None.

3.1.4.12.7 Attribute Groups

None.

3.1.4.13 DeleteIndicator

The **DeleteIndicator** operation deletes an **Indicator** complex type (section [2.2.4.125](#)) from the server (2).

The following is the WSDL port type specification of the **DeleteIndicator** WSDL operation.

```
<wsdl:operation name="DeleteIndicator" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteIndicatorSoapIn"/>
  <wsdl:output message="tns:DeleteIndicatorSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteIndicatorSoapIn** request message (section [3.1.4.13.1.1](#)), and the server (2) responds with a **DeleteIndicatorSoapOut** response message (section [3.1.4.13.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) of an **Indicator**.
- The server (2) MUST delete the **Indicator**.

Exceptions:

Error code	Description
FCDeleteFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCDeleteFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.13.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteIndicatorSoapIn	The request WSDL message for the DeleteIndicator WSDL operation.
DeleteIndicatorSoapOut	The response WSDL message for the DeleteIndicator WSDL operation.

3.1.4.13.1.1 DeleteIndicatorSoapIn

The request WSDL message for the **DeleteIndicator** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/DeleteIndicator
```

The SOAP body contains the **DeleteIndicator** element.

3.1.4.13.1.2 DeleteIndicatorSoapOut

The response WSDL message for the **DeleteIndicator** WSDL operation.

The SOAP body contains the **DeleteIndicatorResponse** element.

3.1.4.13.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteIndicator	The input data for the DeleteIndicator WSDL operation.
DeleteIndicatorResponse	The result data for the DeleteIndicator WSDL operation.

3.1.4.13.2.1 DeleteIndicator

The **DeleteIndicator** element specifies the input data for the **DeleteIndicator** WSDL operation.

```
<xs:element name="DeleteIndicator" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present. It MUST contain the location of an Indicator.

3.1.4.13.2.2 DeleteIndicatorResponse

The **DeleteIndicatorResponse** element specifies the result data for the **DeleteIndicator** WSDL operation.

```
<xs:element name="DeleteIndicatorResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.13.3 Complex Types

None.

3.1.4.13.4 Simple Types

None.

3.1.4.13.5 Attributes

None.

3.1.4.13.6 Groups

None.

3.1.4.13.7 Attribute Groups

None.

3.1.4.14 DeleteKpi

The **DeleteKpi** operation deletes a **Kpi** complex type (section [2.2.4.128](#)) from the server (2).

The following is the WSDL port type specification of the **DeleteKpi** WSDL operation.

```
<wsdl:operation name="DeleteKpi" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteKpiSoapIn"/>
  <wsdl:output message="tns:DeleteKpiSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteKpiSoapIn** request message (section [3.1.4.14.1.1](#)), and the server (2) responds with a **DeleteKpiSoapOut** response message (section [3.1.4.14.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) of a **Kpi**.
- The server (2) MUST delete the **Kpi**.

Exceptions:

Error code	Description
FCDeleteFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCDeleteFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.14.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteKpiSoapIn	The request WSDL message for the DeleteKpi WSDL operation.
DeleteKpiSoapOut	The response WSDL message for the DeleteKpi WSDL operation.

3.1.4.14.1.1 DeleteKpiSoapIn

The request WSDL message for the **DeleteKpi** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/DeleteKpi
```

The SOAP body contains the **DeleteKpi** element.

3.1.4.14.1.2 DeleteKpiSoapOut

The response WSDL message for the **DeleteKpi** WSDL operation.

The SOAP body contains the **DeleteKpiResponse** element.

3.1.4.14.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteKpi	The input data for the DeleteKpi WSDL operation.
DeleteKpiResponse	The result data for the DeleteKpi WSDL operation.

3.1.4.14.2.1 DeleteKpi

The **DeleteKpi** element specifies the input data for the **DeleteKpi** WSDL operation.

```
<xs:element name="DeleteKpi" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present. It MUST contain the location of a KPI.

3.1.4.14.2.2 DeleteKpiResponse

The **DeleteKpiResponse** element specifies the result data for the **DeleteKpi** WSDL operation.

```
<xs:element name="DeleteKpiResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```
<xs:complexType/>
</xs:element>
```

3.1.4.14.3 Complex Types

None.

3.1.4.14.4 Simple Types

None.

3.1.4.14.5 Attributes

None.

3.1.4.14.6 Groups

None.

3.1.4.14.7 Attribute Groups

None.

3.1.4.15 DeleteReportView

The **DeleteReportView** operation deletes a **ReportView** complex type (section [2.2.4.160](#)) from the server (2).

The following is the WSDL port type specification of the **DeleteReportView** WSDL operation.

```
<wsdl:operation name="DeleteReportView" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteReportViewSoapIn"/>
  <wsdl:output message="tns:DeleteReportViewSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteReportViewSoapIn** request message (section [3.1.4.15.1.1](#)), and the server (2) responds with a **DeleteReportViewSoapOut** response message (section [3.1.4.15.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) of a **ReportView**.
- The server (2) MUST delete the **ReportView**.

Exceptions:

Error code	Description
FCODeleteFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCODeleteFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.15.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteReportViewSoapIn	The request WSDL message for the DeleteReportView WSDL operation.
DeleteReportViewSoapOut	The response WSDL message for the DeleteReportView WSDL operation.

3.1.4.15.1.1 DeleteReportViewSoapIn

The request WSDL message for the **DeleteReportView** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/DeleteReportView
```

The SOAP body contains the **DeleteReportView** element.

3.1.4.15.1.2 DeleteReportViewSoapOut

The response WSDL message for the **DeleteReportView** WSDL operation.

The SOAP body contains the **DeleteReportViewResponse** element.

3.1.4.15.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteReportView	The input data for the DeleteReportView WSDL operation.
DeleteReportViewResponse	The result data for the DeleteReportView WSDL operation.

3.1.4.15.2.1 DeleteReportView

The **DeleteReportView** element specifies the input data for the **DeleteReportView** WSDL operation.

```
<xs:element name="DeleteReportView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
```

```
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present. It MUST contain the location of a **ReportView** complex type (section [2.2.4.160](#)).

3.1.4.15.2 DeleteReportViewResponse

The **DeleteReportViewResponse** element specifies the result data for the **DeleteReportView** WSDL operation.

```
<xs:element name="DeleteReportViewResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.15.3 Complex Types

None.

3.1.4.15.4 Simple Types

None.

3.1.4.15.5 Attributes

None.

3.1.4.15.6 Groups

None.

3.1.4.15.7 Attribute Groups

None.

3.1.4.16 DeleteScorecard

The **DeleteScorecard** operation deletes a **Scorecard** complex type (section [2.2.4.162](#)) from the server (2).

The following is the WSDL port type specification of the **DeleteScorecard** WSDL operation.

```
<wsdl:operation name="DeleteScorecard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteScorecardSoapIn"/>
  <wsdl:output message="tns:DeleteScorecardSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteScorecardSoapIn** request message (section [3.1.4.16.1.1](#)), and the server (2) responds with a **DeleteScorecardSoapOut** response message (section [3.1.4.16.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) of a **Scorecard**.

- The server (2) MUST delete the **Scorecard**.

Exceptions:

Error code	Description
InvalidPermission	The content store<25> containing this object no longer exists or the object has already been deleted.
FCODeleteFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.16.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteScorecardSoapIn	The request WSDL message for the DeleteScorecard WSDL operation.
DeleteScorecardSoapOut	The response WSDL message for the DeleteScorecard WSDL operation.

3.1.4.16.1.1 DeleteScorecardSoapIn

The request WSDL message for the **DeleteScorecard** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/DeleteScorecard
```

The SOAP body contains the **DeleteScorecard** element.

3.1.4.16.1.2 DeleteScorecardSoapOut

The response WSDL message for the **DeleteScorecard** WSDL operation.

The SOAP body contains the **DeleteScorecardResponse** element.

3.1.4.16.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteScorecard	The input data for the DeleteScorecard WSDL operation.
DeleteScorecardResponse	The result data for the DeleteScorecard WSDL operation.

3.1.4.16.2.1 DeleteScorecard

The **DeleteScorecard** element specifies the input data for the **DeleteScorecard** WSDL operation.

```
<xs:element name="DeleteScorecard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present. It MUST contain the location of a **Scorecard** complex type (section [2.2.4.162](#)).

3.1.4.16.2.2 DeleteScorecardResponse

The **DeleteScorecardResponse** element specifies the result data for the **DeleteScorecard** WSDL operation.

```
<xs:element name="DeleteScorecardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.16.3 Complex Types

None.

3.1.4.16.4 Simple Types

None.

3.1.4.16.5 Attributes

None.

3.1.4.16.6 Groups

None.

3.1.4.16.7 Attribute Groups

None.

3.1.4.17 ExportDashboard

The **ExportDashboard** operation [<26>](#) is used to export dashboard pages and their associated content from the server (2) into a specified Deployment Package ([\[MS-PRIMEPF\]](#)).

The following is the WSDL port type specification of the **ExportDashboard** WSDL operation.

```
<wsdl:operation name="ExportDashboard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:ExportDashboardSoapIn"/>
</wsdl:operation>
```

```
<wsdl:output message="tns:ExportDashboardSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **ExportDashboardSoapIn** request message (section [3.1.4.17.1.1](#)), and the server (2) responds with an **ExportDashboardSoapOut** response message (section [3.1.4.17.1.2](#)) as follows:

- The server (2) exports the items specified in **itemUrls** into the Deployment Package located at the filename.
- If there was an application error on the server (2) during the operation, the server (2) MUST return a SOAP fault response, which SHOULD include one of exceptions specified below, but MAY contain any other exceptions.

Exceptions:

Error code	Description
InvalidUrl	An invalid URL was specified
FCOUnauthorizedAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#)

3.1.4.17.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ExportDashboardSoapIn	The request WSDL message for the ExportDashboard WSDL operation.
ExportDashboardSoapOut	The response WSDL message for the ExportDashboard WSDL operation.

3.1.4.17.1.1 ExportDashboardSoapIn

The request WSDL message for the **ExportDashboard** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/ExportDashboard
```

The SOAP body contains the **ExportDashboard** element.

3.1.4.17.1.2 ExportDashboardSoapOut

The response WSDL message for the **ExportDashboard** WSDL operation.

The SOAP body contains the **ExportDashboardResponse** element.

3.1.4.17.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
ExportDashboard	The input data for the ExportDashboard WSDL operation.
ExportDashboardResponse	The result data for the ExportDashboard WSDL operation.

3.1.4.17.2.1 ExportDashboard

The **ExportDashboard** element specifies the input data for the **ExportDashboard** WSDL operation.

```
<xs:element name="ExportDashboard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="filename" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="siteCollectionUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="itemUrls" type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

filename: Contains the site collection relative path and file name of the Deployment Package ([\[MS-PRIMEPF\]](#)) to use for the export. The path specified MUST be the relative path of a document library in the site collection specified in **siteCollectionUrl**. This element MUST be present.

siteCollectionUrl: Contains the site collection URL to use for the export. This element MUST be present.

itemUrls: Contains an array of strings containing the site relative URLs of the items to include in the Deployment Package. This element MUST be present. It MUST contain at least one item URL.

3.1.4.17.2.2 ExportDashboardResponse

The **ExportDashboardResponse** element specifies the result data for the **ExportDashboard** WSDL operation.

```
<xs:element name="ExportDashboardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.17.3 Complex Types

None.

3.1.4.17.4 Simple Types

None.

3.1.4.17.5 Attributes

None.

3.1.4.17.6 Groups

None.

3.1.4.17.7 Attribute Groups

None.

3.1.4.18 GenerateView

The **GenerateView** operation generates the data structure that represents a scorecard grid view, the **GridViewData** complex type (section [2.2.4.121](#)), based on information stored on the server (2).

The following is the WSDL port type specification of the **GenerateView** WSDL operation.

```
<wsdl:operation name="GenerateView" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GenerateViewSoapIn"/>
  <wsdl:output message="tns:GenerateViewSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GenerateViewSoapIn** request message (section [3.1.4.18.1.1](#)), and the server (2) responds with a **GenerateViewSoapOut** response message (section [3.1.4.18.1.2](#)) as follows:

- The server (2) protocol uses the **scorecardLocation** to retrieve the scorecard for which the view will be generated.
- **pageFilters** MAY be used to slice the scorecard data.
- **propertyBags** MUST NOT be null, but MAY be empty or MAY contain information that will be consumed by the server (2) defined transforms for the scorecard. See the **GridViewTransformReference** complex type (section [2.2.4.123](#)) for details.
- If there was an application error on the server (2) during the operation, the server (2) MUST return a SOAP fault response, which SHOULD include one of the exceptions specified in the **GetScorecard** (section [3.1.4.51](#)) and **GetDataSource** (section [3.1.4.35](#)) operations, but MAY instead contain any other exceptions.

3.1.4.18.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GenerateViewSoapIn	The request WSDL message for the GenerateView WSDL operation.
GenerateViewSoapOut	The response WSDL message for the GenerateView WSDL operation.

3.1.4.18.1.1 GenerateViewSoapIn

The request WSDL message for the **GenerateView** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GenerateView
```

The SOAP body contains the **GenerateView** element.

3.1.4.18.1.2 GenerateViewSoapOut

The response WSDL message for the **GenerateView** WSDL operation.

The SOAP body contains the **GenerateViewResponse** element.

3.1.4.18.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GenerateView	The input data for the GenerateView WSDL operation.
GenerateViewResponse	The result data for the GenerateView WSDL operation.

3.1.4.18.2.1 GenerateView

The **GenerateView** element specifies the input data for the **GenerateView** WSDL operation.

```
<xs:element name="GenerateView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="pageFilters" type="tns:ArrayOfMember"/>
      <xs:element minOccurs="0" maxOccurs="1" name="propertyBags"
type="tns:DictionaryWrapperOfStringPropertyBag"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

scorecardLocation: Points to the scorecard for which the grid view will be generated, as defined in the **RepositoryLocation** complex type (section [2.2.4.161](#)). It MUST NOT be null or empty, and it MUST point to a valid scorecard location. If ANY of those conditions are not met, the returned view is null.

pageFilters: Represents a collection of members (3) used to slice the scorecard values, as defined in the **ArrayOfMember** complex type (section [2.2.4.45](#)).

propertyBags: Is a dictionary, as defined in the **DictionaryWrapperOfStringPropertyBag** complex type (section [2.2.4.89](#)), containing specific settings that will be consumed by each

individual transformation defined for the scorecard. See the **GridViewTransformReference** complex type in section [2.2.4.123](#) for details. This element MUST NOT be null, but MAY be empty.

3.1.4.18.2.2 GenerateViewResponse

The **GenerateViewResponse** element specifies the result data for the **GenerateView** WSDL operation.

```
<xs:element name="GenerateViewResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GenerateViewResult"
type="tns:GridViewData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GenerateViewResult: Represents a scorecard grid view data, as defined in the **GridViewData** complex type (section [2.2.4.121](#)). The returned result is **NULL**, if **scorecardLocation** is null, empty or invalid.

3.1.4.18.3 Complex Types

None.

3.1.4.18.4 Simple Types

None.

3.1.4.18.5 Attributes

None.

3.1.4.18.6 Groups

None.

3.1.4.18.7 Attribute Groups

None.

3.1.4.19 GenerateViewDirect

The **GenerateViewDirect** operation generates the data structure that represents a scorecard grid view (see **GridViewData** complex type, section [2.2.4.121](#)), using information sent from the client.

The following is the WSDL port type specification of the **GenerateViewDirect** WSDL operation.

```
<wsdl:operation name="GenerateViewDirect" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GenerateViewDirectSoapIn"/>
  <wsdl:output message="tns:GenerateViewDirectSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GenerateViewDirectSoapIn** request message (section [3.1.4.19.1.1](#)), and the server (2) responds with a **GenerateViewDirectSoapOut** response message (section [3.1.4.19.1.2](#)) as follows:

- The server (2) protocol uses the **scorecard**, **kpis**, **dataSources** and **indicators** to build the scorecard view. The provided information MAY be incomplete, in which case the missing information will be retrieved from the server (2).
- **pageFilters** MAY be used to slice the scorecard data.
- **propertyBags** MUST NOT be null but MAY be empty or MAY contain information that will be consumed by the server-defined transforms for the scorecard. See the **GridViewTransformReference** complex type (section [2.2.4.123](#)) for details.

3.1.4.19.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GenerateViewDirectSoapIn	The request WSDL message for the GenerateViewDirect WSDL operation.
GenerateViewDirectSoapOut	The response WSDL message for the GenerateViewDirect WSDL operation.

3.1.4.19.1.1 GenerateViewDirectSoapIn

The request WSDL message for the **GenerateViewDirect** WSDL operation.

The SOAP action value is:

`http://www.microsoft.com/performancepoint/scorecards/GenerateViewDirect`

The SOAP body contains the **GenerateViewDirect** element.

3.1.4.19.1.2 GenerateViewDirectSoapOut

The response WSDL message for the **GenerateViewDirect** WSDL operation.

The SOAP body contains the **GenerateViewDirectResponse** element.

3.1.4.19.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GenerateViewDirect	The input data for the GenerateViewDirect WSDL operation.
GenerateViewDirectResponse	The result data for the GenerateViewDirect WSDL operation.

3.1.4.19.2.1 GenerateViewDirect

The **GenerateViewDirect** element specifies the input data for the **GenerateViewDirect** WSDL operation.

```
<xs:element name="GenerateViewDirect" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecard" type="tns:Scorecard"/>
      <xs:element minOccurs="0" maxOccurs="1" name="kpis" type="tns:ArrayOfKpi"/>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSources"
type="tns:ArrayOfDataSource"/>
      <xs:element minOccurs="0" maxOccurs="1" name="indicators" type="tns:ArrayOfIndicator"/>
      <xs:element minOccurs="0" maxOccurs="1" name="pageFilters" type="tns:ArrayOfMember"/>
      <xs:element minOccurs="0" maxOccurs="1" name="propertyBags"
type="tns:DictionaryWrapperOfStringPropertyBag"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

scorecard: The scorecard for which the grid view will be generated. The element MUST NOT be null.

kpis: Represents a list (1) of **Kpi** complex types (section [2.2.4.128](#)) used by **scorecard**, as defined in the **ArrayOfKpi** complex type (section [2.2.4.41](#)). It MAY be null and it SHOULD contain all the **Kpis** referenced by **scorecard**. It MUST contain at least all the **Kpis** referenced by **scorecard** that are not yet stored on the server (2).

dataSources: Represents a list (1) of data sources (1) used by **scorecard**, as defined in the **ArrayOfDataSource** complex type (section [3.1.4.19.3.2](#)). It MAY be null and it SHOULD contain all the data sources referenced by **scorecard**. It MUST contain at least all the data sources (1) referenced by **scorecard** that are not yet stored on the server (2).

indicators: Represents a list (1) of **indicators** used by **scorecard**, as defined in the **ArrayOfIndicator** complex type (section [3.1.4.19.3.1](#)). It MAY be null and it SHOULD contain all the **indicators** referenced by **scorecard**. It MUST contain at least all the **indicators** referenced by **scorecard** that are not yet stored on the server (2).

pageFilters: Represents a collection of members (3) used to slice the scorecard values, as defined in the **ArrayOfMember** complex type (section [2.2.4.45](#)).

propertyBags: Is a dictionary, as defined in the **DictionaryWrapperOfStringPropertyBag** complex type (section [2.2.4.89](#)), containing specific settings that will be consumed by each individual transformation defined for the scorecard. See the **GridViewTransformReference** complex type (section [2.2.4.123](#)) for details. The element MUST NOT be null, but MAY be empty.

3.1.4.19.2.2 GenerateViewDirectResponse

The **GenerateViewDirectResponse** element specifies the result data for the **GenerateViewDirect** WSDL operation.

```
<xs:element name="GenerateViewDirectResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GenerateViewDirectResult"
type="tns:GridViewData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
</xs:complexType>
</xs:element>
```

GenerateViewDirectResult: Represents a scorecard grid view data, as specified by the **GridViewData** complex type (section [2.2.4.121](#)). The returned result is a **BpmException** complex type (section [2.2.4.61](#)), if **scorecard** is null or invalid or if **kpis**, **dataSources**, and **indicators** together with the server (2) store do not contain all necessary dependencies.

3.1.4.19.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfDataSource	Specifies an array of data sources.
ArrayOfIndicator	Specifies an array of indicators for a scorecard.

3.1.4.19.3.1 ArrayOfIndicator

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfIndicator** complex type specifies an array of indicators for a scorecard.

```
<xs:complexType name="ArrayOfIndicator" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Indicator" nillable="true"
      type="tns:Indicator"/>
  </xs:sequence>
</xs:complexType>
```

Indicator: This element MUST NOT be null. It MUST conform to the schema of the **Indicator** complex type (section [2.2.4.125](#)).

3.1.4.19.3.2 ArrayOfDataSource

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfDataSource** complex type specifies an array of data sources.

```
<xs:complexType name="ArrayOfDataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DataSource" nillable="true"
      type="tns:DataSource"/>
  </xs:sequence>
</xs:complexType>
```

DataSource: This element MUST NOT be null and MUST conform to the schema of the **DataSource** (section [2.2.4.85](#)) complex type.

3.1.4.19.4 Simple Types

None.

3.1.4.19.5 Attributes

None.

3.1.4.19.6 Groups

None.

3.1.4.19.7 Attribute Groups

None.

3.1.4.20 GetAllAnnotationsByScorecardLocation

The **GetAllAnnotationsByScorecardLocation** operation retrieves an array of **Annotation** complex type elements (section [2.2.4.18](#)) associated with a scorecard.

The following is the WSDL port type specification of the **GetAllAnnotationsByScorecardLocation** WSDL operation.

```
<wsdl:operation name="GetAllAnnotationsByScorecardLocation"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetAllAnnotationsByScorecardLocationSoapIn"/>
  <wsdl:output message="tns:GetAllAnnotationsByScorecardLocationSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetAllAnnotationsByScorecardLocationSoapIn** request message (section [3.1.4.20.1.1](#)), and the server (2) responds with a **GetAllAnnotationsByScorecardLocationSoapOut** response message (section [3.1.4.20.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) of a scorecard.
- The server (2) MUST retrieve an array of **Annotation** elements.

Exceptions:

Error code	Description
InvalidPermission	Caused by not having access to the scorecard. See section 2.2.2.1.3 for the Common list of Error Codes.

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.20.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAllAnnotationsByScorecardLocationSoapIn	The request WSDL message for the GetAllAnnotationsByScorecardLocation WSDL operation.
GetAllAnnotationsByScorecardLocationSoapOut	The response WSDL message for the GetAllAnnotationsByScorecardLocation WSDL operation.

3.1.4.20.1.1 GetAllAnnotationsByScorecardLocationSoapIn

The request WSDL message for the **GetAllAnnotationsByScorecardLocation** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetAllAnnotationsByScorecardLocation
```

The SOAP body contains the **GetAllAnnotationsByScorecardLocation** element.

3.1.4.20.1.2 GetAllAnnotationsByScorecardLocationSoapOut

The response WSDL message for the **GetAllAnnotationsByScorecardLocation** WSDL operation.

The SOAP body contains the **GetAllAnnotationsByScorecardLocationResponse** element.

3.1.4.20.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAllAnnotationsByScorecardLocation	The input data for the GetAllAnnotationsByScorecardLocation WSDL operation.
GetAllAnnotationsByScorecardLocationResponse	The result data for the GetAllAnnotationsByScorecardLocation WSDL operation.

3.1.4.20.2.1 GetAllAnnotationsByScorecardLocation

The **GetAllAnnotationsByScorecardLocation** element specifies the input data for the **GetAllAnnotationsByScorecardLocation** WSDL operation.

```
<xs:element name="GetAllAnnotationsByScorecardLocation"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
```



```
</xs:element>
```

scorecardLocation: The location of a scorecard, as specified by a **RepositoryLocation** complex type (section [2.2.4.161](#)). This element MUST be present.

3.1.4.20.2 GetAllAnnotationsByScorecardLocationResponse

The **GetAllAnnotationsByScorecardLocationResponse** element specifies the result data for the **GetAllAnnotationsByScorecardLocation** WSDL operation.

```
<xs:element name="GetAllAnnotationsByScorecardLocationResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1"
        name="GetAllAnnotationsByScorecardLocationResult" type="tns:ArrayOfAnnotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetAllAnnotationsByScorecardLocationResult: An array of **Annotation** complex type elements (section [2.2.4.18](#)) associated with the **scorecardLocation** that was requested from the server (2).

3.1.4.20.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfAnnotation	Specifies an array of Annotation elements.

3.1.4.20.3.1 ArrayOfAnnotation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfAnnotation** complex type specifies an array of **Annotation** elements.

```
<xs:complexType name="ArrayOfAnnotation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Annotation" nillable="true"
      type="tns:Annotation"/>
  </xs:sequence>
</xs:complexType>
```

Annotation: This element MUST NOT be null and MUST conform to the schema of the **Annotation** complex type (section [2.2.4.18](#)).

3.1.4.20.4 Simple Types

None.

3.1.4.20.5 Attributes

None.

3.1.4.20.6 Groups

None.

3.1.4.20.7 Attribute Groups

None.

3.1.4.21 GetAnalyticReportView

The **GetAnalyticReportView** operation retrieves a report view from the server (2) that has been created through the **SaveTemporaryAnalyticReport** (section [3.1.4.65](#)) or **CreateReportView** (section [3.1.4.7](#)) operation.

The following is the WSDL port type specification of the **GetAnalyticReportView** WSDL operation.

```
<wsdl:operation name="GetAnalyticReportView" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetAnalyticReportViewSoapIn"/>
  <wsdl:output message="tns:GetAnalyticReportViewSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetAnalyticReportViewSoapIn** request message (section [3.1.4.21.1.1](#)), and the server (2) responds with a **GetAnalyticReportViewSoapOut** response message (section [3.1.4.21.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the report view to be retrieved.
- The server (2) sends the corresponding report view.
- In the event that a report view cannot be retrieved, the server (2) SHOULD [<27>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
InvalidPermission	If the report view was created with SaveTemporaryAnalyticReport , the security permissions are inherited from the parent report view. The location of the parent report view can be determined from the RepositoryLocation object "ParentReportViewLocation" embedded within "CustomData" of the report view.
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.21.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAnalyticReportViewSoapIn	The request WSDL message for the GetAnalyticReportView WSDL operation.
GetAnalyticReportViewSoapOut	The response WSDL message for the GetAnalyticReportView WSDL operation.

3.1.4.21.1.1 GetAnalyticReportViewSoapIn

The request WSDL message for the **GetAnalyticReportView** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetAnalyticReportView
```

The SOAP body contains the **GetAnalyticReportView** element.

3.1.4.21.1.2 GetAnalyticReportViewSoapOut

The response WSDL message for the **GetAnalyticReportView** WSDL operation.

The SOAP body contains the **GetAnalyticReportViewResponse** element.

3.1.4.21.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAnalyticReportView	The input data for the GetAnalyticReportView WSDL operation.
GetAnalyticReportViewResponse	The result data for the GetAnalyticReportView WSDL operation.

3.1.4.21.2.1 GetAnalyticReportView

The **GetAnalyticReportView** element specifies the input data for the **GetAnalyticReportView** WSDL operation.

```
<xs:element name="GetAnalyticReportView" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="analyticReportViewLocation"  
        type="tns:RepositoryLocation"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

analyticReportViewLocation: A **RepositoryLocation** complex type object (section [2.2.4.161](#)) that specifies the location of the report view on the server (2).

- If the report view to be retrieved was created with the **SaveTemporaryAnalyticReport** operation (section [3.1.4.65](#)):
 - The **ItemGuid** property MUST equal the GUID that was returned from **SaveTemporaryAnalyticReport**.
 - The **ItemType** property MUST equal **TempReportView** as specified by the **FirstClassObjectType** simple type (section [2.2.5.20](#)).
 - The **ItemUrl** property MUST equal an empty string.
- If the report view to be retrieved was created with the **CreateReportView** (section [3.1.4.7](#)), the **ItemUrl** property MUST be set to the location of the report view.

3.1.4.21.2.2 GetAnalyticReportViewResponse

The **GetAnalyticReportViewResponse** element specifies the result data for the **GetAnalyticReportView** WSDL operation.

```
<xs:element name="GetAnalyticReportViewResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="GetAnalyticReportViewResult"  
type="tns:ReportView"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

GetAnalyticReportViewResult: The **ReportView** complex type object (section [2.2.4.160](#)) that was requested from the server (2).

3.1.4.21.3 Complex Types

None.

3.1.4.21.4 Simple Types

None.

3.1.4.21.5 Attributes

None.

3.1.4.21.6 Groups

None.

3.1.4.21.7 Attribute Groups

None.

3.1.4.22 GetAnnotation

The **GetAnnotation** operation retrieves an **Annotation** complex type (section [2.2.4.18](#)) associated with a scorecard cell from the server (2).

The following is the WSDL port type specification of the **GetAnnotation** WSDL operation.

```
<wsdl:operation name="GetAnnotation" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetAnnotationSoapIn"/>
  <wsdl:output message="tns:GetAnnotationSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetAnnotationSoapIn** request message (section [3.1.4.22.1.1](#)), and the server (2) responds with a **GetAnnotationSoapOut** response message (section [3.1.4.22.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the scorecard containing the **Annotation**. It also sends an array of **Tuple** complex type objects (section [3.1.4.22.3.2](#)) and a string that specifies the **Annotation** within the scorecard to be retrieved. All of these objects MUST be present.
- The server (2) sends the corresponding **Annotation**.

Exceptions:

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.22.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAnnotationSoapIn	The request WSDL message for the GetAnnotation WSDL operation.
GetAnnotationSoapOut	The response WSDL message for the GetAnnotation WSDL operation.

3.1.4.22.1.1 GetAnnotationSoapIn

The request WSDL message for the **GetAnnotation** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetAnnotation
```

The SOAP body contains the **GetAnnotation** element.

3.1.4.22.1.2 GetAnnotationSoapOut

The response WSDL message for the **GetAnnotation** WSDL operation.

The SOAP body contains the **GetAnnotationResponse** element.

3.1.4.22.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAnnotation	The input data for the GetAnnotation WSDL operation.
GetAnnotationResponse	The result data for the GetAnnotation WSDL operation.

3.1.4.22.2.1 GetAnnotation

The **GetAnnotation** element specifies the input data for the **GetAnnotation** WSDL operation.

```
<xs:element name="GetAnnotation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="tupleCollection"
type="tns:ArrayOfTuple"/>
      <xs:element minOccurs="0" maxOccurs="1" name="cellPath" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

scorecardLocation: A **RepositoryLocation** complex type object (section [2.2.4.161](#)) that specifies the location of the scorecard on the server (2) containing the **Annotation**.

- This element **MUST** be present.
- The **ItemUrl** property **MUST** be set to the location of the report view associated with the **Annotation**.

tupleCollection: An array of **Tuple** complex type objects (section [3.1.4.22.3.2](#)) that aggregates all the column, row, and page filter selections corresponding to the cell or cells in the scorecard for which this **Annotation** is applicable. This element **MUST** be present.

cellPath: **CellpathCoordinates** property, as specified in the **Annotation** complex type (section [2.2.4.18](#)). This element **MUST** be present.

3.1.4.22.2.2 GetAnnotationResponse

The **GetAnnotationResponse** element specifies the result data for the **GetAnnotation** WSDL operation.

```
<xs:element name="GetAnnotationResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
```

```

    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetAnnotationResult"
type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetAnnotationResult: The **Annotation** complex type object (see section [2.2.4.18](#)) that was requested from the server (2).

3.1.4.22.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfTuple	Specifies an array of Tuple.
Tuple	Specifies an ordered collection of one or more members from different dimensions.

3.1.4.22.3.1 ArrayOfTuple

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfTuple** complex type specifies an array of **Tuple** (section [3.1.4.22.3.2](#)).

```

<xs:complexType name="ArrayOfTuple" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Tuple" nillable="true"
type="tns:Tuple"/>
  </xs:sequence>
</xs:complexType>

```

Tuple: This element MUST NOT be null and MUST conform to the schema of the **Tuple** complex type (section [3.1.4.22.3.2](#)).

3.1.4.22.3.2 Tuple

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **Tuple** complex type represents an ordered collection of one or more members from different dimensions and it contains an instance of **ArrayOfMember** (see section [2.2.4.45](#)).

```

<xs:complexType name="Tuple" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="DimensionMembers"
type="tns:ArrayOfMember"/>
  </xs:sequence>
</xs:complexType>

```

DimensionMembers: This element MUST NOT be **null**.

3.1.4.22.4 Simple Types

None.

3.1.4.22.5 Attributes

None.

3.1.4.22.6 Groups

None.

3.1.4.22.7 Attribute Groups

None.

3.1.4.23 GetAnnotationByID

The **GetAnnotationByID** operation retrieves an **Annotation** complex type (section [2.2.4.18](#)) from a specified GUID from the server (2).

The following is the WSDL port type specification of the **GetAnnotationByID** WSDL operation.

```
<wsdl:operation name="GetAnnotationByID" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetAnnotationByIDSoapIn"/>
  <wsdl:output message="tns:GetAnnotationByIDSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetAnnotationByIDSoapIn** request message (section [3.1.4.23.1.1](#)), and the server (2) responds with a **GetAnnotationByIDSoapOut** response message (section [3.1.4.23.1.2](#)) as follows:

- The protocol client sends a GUID that specifies the **Annotation** to be retrieved.
- The server (2) sends the corresponding **Annotation**.

Exceptions:

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.23.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAnnotationByIDSoapIn	The request WSDL message for the GetAnnotationByID WSDL operation.

Message	Description
GetAnnotationByIDSoapOut	The response WSDL message for the GetAnnotationByID WSDL operation.

3.1.4.23.1.1 GetAnnotationByIDSoapIn

The request WSDL message for the **GetAnnotationByID** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetAnnotationByID
```

The SOAP body contains the **GetAnnotationByID** element.

3.1.4.23.1.2 GetAnnotationByIDSoapOut

The response WSDL message for the **GetAnnotationByID** WSDL operation.

The SOAP body contains the **GetAnnotationByIDResponse** element.

3.1.4.23.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAnnotationByID	The input data for the GetAnnotationByID WSDL operation.
GetAnnotationByIDResponse	The result data for the GetAnnotationByID WSDL operation.

3.1.4.23.2.1 GetAnnotationByID

The **GetAnnotationByID** element specifies the input data for the **GetAnnotationByID** WSDL operation.

```
<xs:element name="GetAnnotationByID" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="annotationID"
        xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

annotationID: A GUID that specifies the **Annotation** complex type (section [2.2.4.18](#)) to be retrieved. This element **MUST** be present.

3.1.4.23.2.2 GetAnnotationByIDResponse

The **GetAnnotationByIDResponse** element specifies the result data for the **GetAnnotationByID** WSDL operation.

```

<xs:element name="GetAnnotationByIDResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetAnnotationByIDResult"
type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetAnnotationByIDResult: The **Annotation** complex type object (section [2.2.4.18](#)) that was requested from the server (2).

3.1.4.23.3 Complex Types

None.

3.1.4.23.4 Simple Types

None.

3.1.4.23.5 Attributes

None.

3.1.4.23.6 Groups

None.

3.1.4.23.7 Attribute Groups

None.

3.1.4.24 GetAnnotationSetting

The **Attribute Groups** operation retrieves an **AnnotationSetting** complex type object (section [3.1.4.24.3.1](#)) that contains the annotation settings for the server (2).

The following is the WSDL port type specification of the **GetAnnotationSetting** WSDL operation.

```

<wsdl:operation name="GetAnnotationSetting" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetAnnotationSettingSoapIn"/>
  <wsdl:output message="tns:GetAnnotationSettingSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetAnnotationSettingSoapIn** request message (section [3.1.4.24.1.1](#)), and the server (2) responds with a **GetAnnotationSettingSoapOut** response message (section [3.1.4.24.1.2](#)) as follows:

- The server (2) MUST retrieve an **AnnotationSetting** object.

3.1.4.24.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAnnotationSettingSoapIn	The request WSDL message for the GetAnnotationSetting WSDL operation.
GetAnnotationSettingSoapOut	The response WSDL message for the GetAnnotationSetting WSDL operation.

3.1.4.24.1.1 GetAnnotationSettingSoapIn

The request WSDL message for the **GetAnnotationSetting** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetAnnotationSetting
```

The SOAP body contains the **GetAnnotationSetting** element.

3.1.4.24.1.2 GetAnnotationSettingSoapOut

The response WSDL message for the **GetAnnotationSetting** WSDL operation.

The SOAP body contains the **GetAnnotationSettingResponse** element.

3.1.4.24.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAnnotationSetting	The input data for the GetAnnotationSetting WSDL operation.
GetAnnotationSettingResponse	The result data for the GetAnnotationSetting WSDL operation.

3.1.4.24.2.1 GetAnnotationSetting

The **GetAnnotationSetting** element specifies the input data for the **GetAnnotationSetting** WSDL operation.

```
<xs:element name="GetAnnotationSetting" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.24.2.2 GetAnnotationSettingResponse

The **GetAnnotationSettingResponse** element specifies the result data for the **GetAnnotationSetting** WSDL operation.

```
<xs:element name="GetAnnotationSettingResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
```

```

        <xs:element minOccurs="0" maxOccurs="1" name="GetAnnotationSettingResult"
type="tns:AnnotationSetting"/>
    </xs:sequence>
</xs:complexType>
</xs:element>

```

GetAnnotationSettingResult: An **AnnotationSetting** complex type object (section [3.1.4.24.3.1](#)) that was requested from the server (2).

3.1.4.24.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
AnnotationSetting	Specifies annotation settings for this service application.

3.1.4.24.3.1 AnnotationSetting

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **AnnotationSetting** complex type specifies annotation settings for this service application.

```

<xs:complexType name="AnnotationSetting" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:attribute name="IsAnnotationEnabled" type="xs:boolean" use="required"/>
  <xs:attribute name="IsAnnotationEnabledDefault" type="xs:boolean" use="required"/>
  <xs:attribute name="IsDeletionByAuthorEnabled" type="xs:boolean" use="required"/>
  <xs:attribute name="IsDeletionByAuthorEnabledDefault" type="xs:boolean" use="required"/>
  <xs:attribute name="MaxAnnotationAllowed" type="xs:int" use="required"/>
</xs:complexType>

```

IsAnnotationEnabled: Specifies whether annotations are enabled for scorecards; if set to **true**, annotations are enabled; otherwise, annotations are not enabled.

IsAnnotationEnabledDefault: Specifies the default value of **IsAnnotationEnabled** used by the server (2). The default value is **true**.

IsDeletionByAuthorEnabled: Specifies whether annotations can be deleted by the user; if set to **true**, annotations can be deleted; otherwise, annotations cannot be deleted.

IsDeletionByAuthorEnabledDefault: Specifies the default value of **IsDeletionByAuthorEnabled** used by the server (2). The default is **true**.

MaxAnnotationAllowed: Specifies the maximum number of annotations that can be added for a scorecard. This value MUST be an integer greater than or equal to zero.

3.1.4.24.4 Simple Types

None.

3.1.4.24.5 Attributes

None.

3.1.4.24.6 Groups

None.

3.1.4.24.7 Attribute Groups

None.

3.1.4.25 GetAsKpis

The **GetAsKpis** operation takes in an Analysis Services data source along with a server-relative URL to a **Kpi** complex type (section [2.2.4.128](#)) list (1), and returns a collection of **Kpis** as defined in the **ArrayOfKpi** complex type (see section [2.2.4.41](#)).

The following is the WSDL port type specification of the **GetAsKpis** WSDL operation.

```
<wsdl:operation name="GetAsKpis" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetAsKpisSoapIn"/>
  <wsdl:output message="tns:GetAsKpisSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetAsKpisSoapIn** request message (section [3.1.4.25.1.1](#)), and the server (2) responds with a **GetAsKpisSoapOut** message (section [3.1.4.25.1.2](#)) as follows:

- The server (2) validates the data source as to whether it is a **trusted location (1)**, along with the user's access permissions. If it is from an un-trusted location, it is added to the list (1) of untrusted data sources.
- The server (2) retrieves the **Cube** complex type object (section [2.2.4.78](#)) represented by the data source.
- The server (2) returns the list (1) of Kpis from the **Cube**.

3.1.4.25.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAsKpisSoapIn	The request WSDL message for the GetAsKpis WSDL operation.
GetAsKpisSoapOut	The response WSDL message for the GetAsKpis WSDL operation.

3.1.4.25.1.1 GetAsKpisSoapIn

The request WSDL message for the **GetAsKpis** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetAsKpis
```

The SOAP body contains the **GetAsKpis** element.

3.1.4.25.1.2 GetAsKpisSoapOut

The response WSDL message for the **GetAsKpis** WSDL operation.

The SOAP body contains the **GetAsKpisResponse** element.

3.1.4.25.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAsKpis	The input data for the GetAsKpis WSDL operation.
GetAsKpisResponse	The result data for the GetAsKpis WSDL operation.

3.1.4.25.2.1 GetAsKpis

The **GetAsKpis** element specifies the input data for the **GetAsKpis** WSDL operation.

```
<xs:element name="GetAsKpis" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: This element MUST be an Analysis Services data source.

listUrl: This element MUST be a server-relative URL to the Analysis Services data source (see section [2.2.4.85](#)) list (1).

3.1.4.25.2.2 GetAsKpisResponse

The **GetAsKpisResponse** element specifies the result data for the **GetAsKpis** WSDL operation.

```
<xs:element name="GetAsKpisResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetAsKpisResult" type="tns:ArrayOfKpi"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetAsKpisResult: This element MUST return a collection of **Kpi** complex types (section [2.2.4.128](#)), as defined in the **ArrayOfKpi** complex type (section [2.2.4.41](#)).

3.1.4.25.3 Complex Types

None.

3.1.4.25.4 Simple Types

None.

3.1.4.25.5 Attributes

None.

3.1.4.25.6 Groups

None.

3.1.4.25.7 Attribute Groups

None.

3.1.4.26 GetCube

The **GetCube** operation takes in a **RepositoryLocation** complex type object (section [2.2.4.161](#)), and returns the associated **Cube** complex type object (section [2.2.4.78](#)).

The following is the WSDL port type specification of the **GetCube** WSDL operation.

```
<wsdl:operation name="GetCube" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCubeSoapIn"/>
  <wsdl:output message="tns:GetCubeSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetCubeSoapIn** request message (section [3.1.4.26.1.1](#)), and the server (2) responds with a **GetCubeSoapOut** message (section [3.1.4.26.1.2](#)) as follows:

- The server (2) retrieves the data source from the **RepositoryLocation**.
- The server (2) validates the data source as to whether it is a trusted location (1), along with the user's access permissions. If it is from an un-trusted location, it is added to the list (1) of untrusted data sources. Valid data source types include Analysis Services and Tabular sources.
- The server (2) returns a **Cube** complex type object (section [2.2.4.78](#)) represented by the data source.

Error code	Description
DataSourceHostNotFound	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceConnectionUnsupported	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceDatabaseNotFound	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceCubeNotFound	See Full List of Possible Error Codes (section 2.2.2.1.2).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.26.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCubeSoapIn	The request WSDL message for the GetCube WSDL operation.
GetCubeSoapOut	The response WSDL message for the GetCube WSDL operation.

3.1.4.26.1.1 GetCubeSoapIn

The request WSDL message for the **GetCube** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetCube
```

The SOAP body contains the **GetCube** element.

3.1.4.26.1.2 GetCubeSoapOut

The response WSDL message for the **GetCube** WSDL operation.

The SOAP body contains the **GetCubeResponse** element.

3.1.4.26.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCube	The input data for the GetCube WSDL operation.
GetCubeResponse	The result data for the GetCube WSDL operation.

3.1.4.26.2.1 GetCube

The **GetCube** element specifies the input data for the **GetCube** WSDL operation.

```
<xs:element name="GetCube" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"  
type="tns:RepositoryLocation"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

dataSourceLocation: This element MUST be a valid **RepositoryLocation** complex type (section [2.2.4.161](#)).

3.1.4.26.2.2 GetCubeResponse

The **GetCubeResponse** element specifies the result data for the **GetCube** WSDL operation.

```
<xs:element name="GetCubeResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCubeResult" type="tns:Cube"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetCubeResult: This element **MUST** return **NULL**, if input fails validation; otherwise, **MUST** return the **Cube** complex type (section [2.2.4.78](#)) represented by the **RepositoryLocation** complex type (section [2.2.4.161](#)).

3.1.4.26.3 Complex Types

None.

3.1.4.26.4 Simple Types

None.

3.1.4.26.5 Attributes

None.

3.1.4.26.6 Groups

None.

3.1.4.26.7 Attribute Groups

None.

3.1.4.27 GetCubeFromDataSource

The **GetCubeFromDataSource** operation takes in a data source object and returns the associated **Cube** complex type object section [2.2.4.78](#)().

The following is the WSDL port type specification of the **GetCubeFromDataSource** WSDL operation.

```
<wsdl:operation name="GetCubeFromDataSource" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCubeFromDataSourceSoapIn"/>
  <wsdl:output message="tns:GetCubeFromDataSourceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetCubeFromDataSourceSoapIn** request message (section [3.1.4.27.1.1](#)), and the server (2) responds with a **GetCubeFromDataSourceSoapOut** message (section [3.1.4.27.1.2](#)) as follows:

- The server (2) validates the data source as to whether it is in a trusted location (1), along with the user's access permissions. If it is from an un-trusted location, it is added to the list (1) of untrusted data sources. Valid data source types include Analysis Services and Tabular sources.
- The server (2) returns a **Cube** complex type object (section [2.2.4.78](#)) represented by the data source.

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceDatabaseNotFound	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceCubeNotFound	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.27.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCubeFromDataSourceSoapIn	The request WSDL message for the GetCubeFromDataSource WSDL operation.
GetCubeFromDataSourceSoapOut	The response WSDL message for the GetCubeFromDataSource WSDL operation.

3.1.4.27.1.1 GetCubeFromDataSourceSoapIn

The request WSDL message for the **GetCubeFromDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetCubeFromDataSource
```

The SOAP body contains the **GetCubeFromDataSource** element.

3.1.4.27.1.2 GetCubeFromDataSourceSoapOut

The response WSDL message for the **GetCubeFromDataSource** WSDL operation.

The SOAP body contains the **GetCubeFromDataSourceResponse** element.

3.1.4.27.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCubeFromDataSource	The input data for the GetCubeFromDataSource WSDL operation.
GetCubeFromDataSourceResponse	The result data for the GetCubeFromDataSource WSDL operation.

3.1.4.27.2.1 GetCubeFromDataSource

The **GetCubeFromDataSource** element specifies the input data for the **GetCubeFromDataSource** WSDL operation.

```
<xs:element name="GetCubeFromDataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: A **DataSource** complex type (section [2.2.4.85](#)) to be used for the request. This element MUST be present.

3.1.4.27.2.2 GetCubeFromDataSourceResponse

The **GetCubeFromDataSourceResponse** element specifies the result data for the **GetCubeFromDataSource** WSDL operation.

```
<xs:element name="GetCubeFromDataSourceResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCubeFromDataSourceResult"
type="tns:Cube"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetCubeFromDataSourceResult: This element MUST return 'Null' when the Input is read-only and does not match the **DataSource** complex type (section [2.2.4.85](#)) stored on the server (2), or when the Input is not read-only and the user does not have adequate permissions to open and edit the **DataSource**. Otherwise, it MUST return the **Cube** complex type (section [2.2.4.78](#)) represented by that **DataSource**.

3.1.4.27.3 Complex Types

None.

3.1.4.27.4 Simple Types

None.

3.1.4.27.5 Attributes

None.

3.1.4.27.6 Groups

None.

3.1.4.27.7 Attribute Groups

None.

3.1.4.28 GetCubeMetaData

The **GetCubeMetaData** operation takes in an Analysis Services **RepositoryLocation** complex type object (section [2.2.4.161](#)) and returns the associated **Cube** complex type object (section [2.2.4.78](#)).

The following is the WSDL port type specification of the **GetCubeMetaData** WSDL operation.

```
<wsdl:operation name="GetCubeMetaData" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCubeMetaDataSoapIn"/>
  <wsdl:output message="tns:GetCubeMetaDataSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetCubeMetaDataSoapIn** request message (section [3.1.4.28.1.1](#)), and the server (2) responds with a **GetCubeMetaDataSoapOut** message (section [3.1.4.28.1.2](#)) as follows:

- The server (2) retrieves the data source from the **RepositoryLocation**.
- The server (2) validates whether it is a trusted location (1), along with the user's access permissions. If it is from an un-trusted location, it is added to the list (1) of untrusted data sources.
- The server (2) retrieves the **Cube** definition represented by the data source, and generates a generic **Cube** object with dimensions (1) as defined in the **Dimension** complex type object (section [2.2.4.90](#)) with only hierarchies and levels from the specified **Analysis Services** cube definition.

Error code	Description
UnableToLoadFCODao	See Full List of Possible Error Codes (section 2.2.2.1.2).
DataSourceCubeNotFound	See Full List of Possible Error Codes (section 2.2.2.1.2).
DatabaseConnectionNotOpen	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceHostNotFound	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceConnectionUnsupported	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceDatabaseNotFound	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.28.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCubeMetaDataSoapIn	The request WSDL message for the GetCubeMetaData WSDL operation.
GetCubeMetaDataSoapOut	The response WSDL message for the GetCubeMetaData WSDL operation.

3.1.4.28.1.1 GetCubeMetaDataSoapIn

The request WSDL message for the **GetCubeMetaData** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetCubeMetaData
```

The SOAP body contains the **GetCubeMetaData** element.

3.1.4.28.1.2 GetCubeMetaDataSoapOut

The response WSDL message for the **GetCubeMetaData** WSDL operation.

The SOAP body contains the **GetCubeMetaDataResponse** element.

3.1.4.28.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCubeMetaData	The input data for the GetCubeMetaData WSDL operation.
GetCubeMetaDataResponse	The result data for the GetCubeMetaData WSDL operation.

3.1.4.28.2.1 GetCubeMetaData

The **GetCubeMetaData** element specifies the input data for the **GetCubeMetaData** WSDL operation.

```
<xs:element name="GetCubeMetaData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
```

```
</xs:element>
```

dataSourceLocation: This element MUST be an Analysis Services data source **RepositoryLocation** complex type (section [2.2.4.161](#)).

3.1.4.28.2 GetCubeMetaDataResponse

The **GetCubeMetaDataResponse** element specifies the result data for the **GetCubeMetaData** WSDL operation.

```
<xs:element name="GetCubeMetaDataResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCubeMetaDataResult" type="tns:Cube"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetCubeMetaDataResult: This element MUST return the **Cube** complex type object (section [2.2.4.78](#)) associated with the **RepositoryLocation** complex type (section [2.2.4.161](#)).

3.1.4.28.3 Complex Types

None.

3.1.4.28.4 Simple Types

None.

3.1.4.28.5 Attributes

None.

3.1.4.28.6 Groups

None.

3.1.4.28.7 Attribute Groups

None.

3.1.4.29 GetCubeMetaDataForDataSource

The **GetCubeMetaDataForDataSource** operation takes in an Analysis Services data source object and returns the associated **Cube** complex type object (section [2.2.4.78](#)). This operation is valid for Analysis Services data sources only.

The following is the WSDL port type specification of the **GetCubeMetaDataForDataSource** WSDL operation.

```
<wsdl:operation name="GetCubeMetaDataForDataSource"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCubeMetaDataForDataSourceSoapIn"/>
```

```
<wsdl:output message="tns:GetCubeMetaDataForDataSourceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetCubeMetaDataForDataSourceSoapIn** request message (section [3.1.4.29.1.1](#)), and the server (2) responds with a **GetCubeMetaDataForDataSourceSoapOut** message (section [3.1.4.29.1.2](#)) as follows:

- The server (2) validates whether it is a trusted data source, along with the user's access permissions. If it is from an un-trusted location, it is added to the list (1) of untrusted data sources.
- The server (2) retrieves the **Cube** definition represented by the data source, and generates a generic **Cube** complex type object (section [2.2.4.78](#)) with dimensions (1) as defined in the **Dimension** complex type object (section [2.2.4.90](#)) from the **Analysis Services** cube definition.

Error code	Description
UnableToLoadFCODao	See Full List of Possible Error Codes (section 2.2.2.1.2).
DataSourceCubeNotFound	See Full List of Possible Error Codes (section 2.2.2.1.2).
DatabaseConnectionNotOpen	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceHostNotFound	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceConnectionUnsupported	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceDatabaseNotFound	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.29.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCubeMetaDataForDataSourceSoapIn	The request WSDL message for the GetCubeMetaDataForDataSource WSDL operation.
GetCubeMetaDataForDataSourceSoapOut	The response WSDL message for the GetCubeMetaDataForDataSource WSDL operation.

3.1.4.29.1.1 GetCubeMetaDataForDataSourceSoapIn

The request WSDL message for the **GetCubeMetaDataForDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetCubeMetaDataForDataSource
```

The SOAP body contains the **GetCubeMetaDataForDataSource** element.

3.1.4.29.1.2 GetCubeMetaDataForDataSourceSoapOut

The response WSDL message for the **GetCubeMetaDataForDataSource** WSDL operation.

The SOAP body contains the **GetCubeMetaDataForDataSourceResponse** element.

3.1.4.29.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCubeMetaDataForDataSource	The input data for the GetCubeMetaDataForDataSource WSDL operation.
GetCubeMetaDataForDataSourceResponse	The result data for the GetCubeMetaDataForDataSource WSDL operation.

3.1.4.29.2.1 GetCubeMetaDataForDataSource

The **GetCubeMetaDataForDataSource** element specifies the input data for the **GetCubeMetaDataForDataSource** WSDL operation.

```
<xs:element name="GetCubeMetaDataForDataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: This element MUST be an Analysis Services data source, as specified in section [2.2.4.85](#).

3.1.4.29.2.2 GetCubeMetaDataForDataSourceResponse

The **GetCubeMetaDataForDataSourceResponse** element specifies the result data for the **GetCubeMetaDataForDataSource** WSDL operation.

```
<xs:element name="GetCubeMetaDataForDataSourceResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCubeMetaDataForDataSourceResult"
        type="tns:Cube"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetCubeMetaDataForDataSourceResult: This element MUST return the **Cube** complex type object (section [2.2.4.78](#)) associated with the specified data source.

3.1.4.29.3 Complex Types

None.

3.1.4.29.4 Simple Types

None.

3.1.4.29.5 Attributes

None.

3.1.4.29.6 Groups

None.

3.1.4.29.7 Attribute Groups

None.

3.1.4.30 GetCubeNameInfos

The **GetCubeNameInfos** operation retrieves an **ArrayOfNameInfo** complex type (section [2.2.4.48](#)) that describes the cubes of the data source (1).

The following is the WSDL port type specification of the **GetCubeNameInfos** WSDL operation.

```
<wsdl:operation name="GetCubeNameInfos" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCubeNameInfosSoapIn"/>
  <wsdl:output message="tns:GetCubeNameInfosSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetCubeNameInfoSoapIn** request message (section [3.1.4.30.1.1](#)), and the server (2) responds with a **GetCubeNameInfoSoapOut** response message (section [3.1.4.30.1.2](#)) as follows:

- The server (2) receives a data source (1).
- The server (2) sends the **NameInfo** complex type object (section [2.2.4.149](#)) for each of the corresponding cubes.

Exceptions:

Error code	Description
DataSourceDatabaseNotFound	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceConnectionFailed	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.30.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCubeNameInfosSoapIn	The request WSDL message for the GetCubeNameInfos WSDL operation.
GetCubeNameInfosSoapOut	The response WSDL message for the GetCubeNameInfos WSDL operation.

3.1.4.30.1.1 GetCubeNameInfosSoapIn

The request WSDL message for the **GetCubeNameInfos** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetCubeNameInfos
```

The SOAP body contains the **GetCubeNameInfos** element.

3.1.4.30.1.2 GetCubeNameInfosSoapOut

The response WSDL message for the **GetCubeNameInfos** WSDL operation.

The SOAP body contains the **GetCubeNameInfosResponse** element.

3.1.4.30.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCubeNameInfos	The input data for the GetCubeNameInfos WSDL operation.
GetCubeNameInfosResponse	The result data for the GetCubeNameInfos WSDL operation.

3.1.4.30.2.1 GetCubeNameInfos

The **GetCubeNameInfos** element specifies the input data for the **GetCubeNameInfos** WSDL operation.

```
<xs:element name="GetCubeNameInfos" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: The data source (1). This element MUST be present.

3.1.4.30.2.2 GetCubeNameInfosResponse

The **GetCubeNameInfosResponse** element specifies the result data for the **GetCubeNameInfos** WSDL operation.

```
<xs:element name="GetCubeNameInfosResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCubeNameInfosResult"
        type="tns:ArrayOfNameInfo"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetCubeNameInfosResult: An **ArrayOfNameInfo** complex type (section [2.2.4.48](#)). This element MUST be present.

3.1.4.30.3 Complex Types

None.

3.1.4.30.4 Simple Types

None.

3.1.4.30.5 Attributes

None.

3.1.4.30.6 Groups

None.

3.1.4.30.7 Attribute Groups

None.

3.1.4.31 GetCurrentCultureLcid

The **GetCurrentCultureLcid** operation retrieves the current culture locale identifier.

The following is the WSDL port type specification of the **GetCurrentCultureLcid** WSDL operation.

```
<wsdl:operation name="GetCurrentCultureLcid" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCurrentCultureLcidSoapIn"/>
  <wsdl:output message="tns:GetCurrentCultureLcidSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetCurrentCultureLcidSoapIn** request message (section [3.1.4.31.1.1](#)), and the server (2) responds with a **GetCurrentCultureLcidSoapOut** response message (section [3.1.4.31.1.2](#)) as follows:

- The server (2) MUST respond by retrieving the current culture locale identifier.

- If there was an application error on the server (2) during the operation, the server (2) MUST return a SOAP fault response. The error code MUST be one of the values specified in section [2.2.2.1.2](#).

3.1.4.31.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCurrentCultureLcidSoapIn	The request WSDL message for the GetCurrentCultureLcid WSDL operation.
GetCurrentCultureLcidSoapOut	The response WSDL message for the GetCurrentCultureLcid WSDL operation.

3.1.4.31.1.1 GetCurrentCultureLcidSoapIn

The request WSDL message for the **GetCurrentCultureLcid** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetCurrentCultureLcid
```

The SOAP body contains the **GetCurrentCultureLcid** element.

3.1.4.31.1.2 GetCurrentCultureLcidSoapOut

The response WSDL message for the **GetCurrentCultureLcid** WSDL operation.

The SOAP body contains the **GetCurrentCultureLcidResponse** element.

3.1.4.31.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCurrentCultureLcid	The input data for the GetCurrentCultureLcid WSDL operation.
GetCurrentCultureLcidResponse	The result data for the GetCurrentCultureLcid WSDL operation.

3.1.4.31.2.1 GetCurrentCultureLcid

The **GetCurrentCultureLcid** element specifies the input data for the **GetCurrentCultureLcid** WSDL operation.

```
<xs:element name="GetCurrentCultureLcid" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.31.2.2 GetCurrentCultureLcidResponse

The **GetCurrentCultureLcidResponse** element specifies the result data for the **GetCurrentCultureLcid** WSDL operation.

```
<xs:element name="GetCurrentCultureLcidResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="GetCurrentCultureLcidResult"
        type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetCurrentCultureLcidResult: An integer representing the current culture locale identifier, which determines how dates, times, numbers, currencies, calendar preferences, input methods, and sorting preferences are formatted.

3.1.4.31.3 Complex Types

None.

3.1.4.31.4 Simple Types

None.

3.1.4.31.5 Attributes

None.

3.1.4.31.6 Groups

None.

3.1.4.31.7 Attribute Groups

None.

3.1.4.32 GetCurrentUserInfo

The **GetCurrentUserInfo** operation retrieves the user name and display name information of the current user.

The following is the WSDL port type specification of the **GetCurrentUserInfo** WSDL operation.

```
<wsdl:operation name="GetCurrentUserInfo" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCurrentUserInfoSoapIn"/>
  <wsdl:output message="tns:GetCurrentUserInfoSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetCurrentUserInfoSoapIn** request message (section [3.1.4.32.1.1](#)), and the server (2) responds with a **GetCurrentUserInfoSoapOut** response message (section [3.1.4.32.1.2](#)) as follows:

- The protocol client MUST provide out parameters to hold the current user name and display name.
- The server (2) MUST set those parameters to the current user name and user display name.
- In the event of an application error, the server (2) MUST set the current user name to the string "i:Anonymous" and user display name to the string "Anonymous".

3.1.4.32.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCurrentUserInfoSoapIn	The request WSDL message for the GetCurrentUserInfo WSDL operation.
GetCurrentUserInfoSoapOut	The response WSDL message for the GetCurrentUserInfo WSDL operation.

3.1.4.32.1.1 GetCurrentUserInfoSoapIn

The request WSDL message for the **GetCurrentUserInfo** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetCurrentUserInfo
```

The SOAP body contains the **GetCurrentUserInfo** element.

3.1.4.32.1.2 GetCurrentUserInfoSoapOut

The response WSDL message for the **GetCurrentUserInfo** WSDL operation.

The SOAP body contains the **GetCurrentUserInfoResponse** element.

3.1.4.32.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCurrentUserInfo	The input data for the GetCurrentUserInfo WSDL operation.
GetCurrentUserInfoResponse	The result data for the GetCurrentUserInfo WSDL operation.

3.1.4.32.2.1 GetCurrentUserInfo

The **GetCurrentUserInfo** element specifies the input data for the **GetCurrentUserInfo** WSDL operation.

```
<xs:element name="GetCurrentUserInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```
<xs:complexType/>
</xs:element>
```

3.1.4.32.2.2 GetCurrentUserInfoResponse

The **GetCurrentUserInfoResponse** element specifies the result data for the **GetCurrentUserInfo** WSDL operation.

```
<xs:element name="GetCurrentUserInfoResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userName" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="userDisplayName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

userName: User name information of current user.

userDisplayName: Display name information of current user.

3.1.4.32.3 Complex Types

None.

3.1.4.32.4 Simple Types

None.

3.1.4.32.5 Attributes

None.

3.1.4.32.6 Groups

None.

3.1.4.32.7 Attribute Groups

None.

3.1.4.33 GetDashboard

The **GetDashboard** operation retrieves a dashboard.

The following is the WSDL port type specification of the **GetDashboard** WSDL operation.

```
<wsdl:operation name="GetDashboard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetDashboardSoapIn"/>
  <wsdl:output message="tns:GetDashboardSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetDashboardSoapIn** request message (section [3.1.4.33.1.1](#)), and the server (2) responds with a **GetDashboardSoapOut** response message (section [3.1.4.33.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the dashboard to be retrieved.
- The server (2) responds with the corresponding dashboard.
- In the event the dashboard cannot be retrieved, the server (2) SHOULD [<28>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.33.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetDashboardSoapIn	The request WSDL message for the GetDashboard WSDL operation.
GetDashboardSoapOut	The response WSDL message for the GetDashboard WSDL operation.

3.1.4.33.1.1 GetDashboardSoapIn

The request WSDL message for the **GetDashboard** WSDL operation.

The SOAP action value is:

`http://www.microsoft.com/performancepoint/scorecards/GetDashboard`

The SOAP body contains the **GetDashboard** element.

3.1.4.33.1.2 GetDashboardSoapOut

The response WSDL message for the **GetDashboard** WSDL operation.

The SOAP body contains the **GetDashboardResponse** element.

3.1.4.33.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetDashboard	The input data for the GetDashboard WSDL operation.
GetDashboardResponse	The result data for the GetDashboard WSDL operation.

3.1.4.33.2.1 GetDashboard

The **GetDashboard** element specifies the input data for the **GetDashboard** WSDL operation.

```
<xs:element name="GetDashboard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present. The **ItemUrl** property MUST contain a valid URL.

3.1.4.33.2.2 GetDashboardResponse

The **GetDashboardResponse** element specifies the result data for the **GetDashboard** WSDL operation.

```
<xs:element name="GetDashboardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetDashboardResult"
type="tns:Dashboard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetDashboardResult: A **Dashboard** complex type, as specified in section [2.2.4.79](#). This element SHOULD be present.

3.1.4.33.3 Complex Types

None.

3.1.4.33.4 Simple Types

None.

3.1.4.33.5 Attributes

None.

3.1.4.33.6 Groups

None.

3.1.4.33.7 Attribute Groups

None.

3.1.4.34 GetDatabaseNamesFromDataSource

The **GetDatabaseNamesFromDataSource** operation retrieves an array of database names associated with the data source (1).

The following is the WSDL port type specification of the **GetDatabaseNamesFromDataSource** WSDL operation.

```
<wsdl:operation name="GetDatabaseNamesFromDataSource"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetDatabaseNamesFromDataSourceSoapIn"/>
  <wsdl:output message="tns:GetDatabaseNamesFromDataSourceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetDatabaseNamesSoapIn** request message (section [3.1.4.34.1.1](#)), and the server (2) responds with a **GetDatabaseNamesSoapOut** response message (section [3.1.4.34.1.2](#)) as follows:

- The server (2) receives a **DataSource** complex type (section [2.2.4.79](#)).
- The server (2) returns the name for each database associated with the data source (3).

Exceptions:

Error code	Description
DataSourceDatabaseNotFound	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceConnectionFailed	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.34.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetDatabaseNamesFromDataSourceSoapIn	The request WSDL message for the GetDatabaseNamesFromDataSource WSDL operation.
GetDatabaseNamesFromDataSourceSoapOut	The response WSDL message for the GetDatabaseNamesFromDataSource WSDL operation.

3.1.4.34.1.1 GetDatabaseNamesFromDataSourceSoapIn

The request WSDL message for the **GetDatabaseNamesFromDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetDatabaseNamesFromDataSource
```

The SOAP body contains the **GetDatabaseNamesFromDataSource** element.

3.1.4.34.1.2 GetDatabaseNamesFromDataSourceSoapOut

The response WSDL message for the **GetDatabaseNamesFromDataSource** WSDL operation.

The SOAP body contains the **GetDatabaseNamesFromDataSourceResponse** element.

3.1.4.34.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetDatabaseNamesFromDataSource	The input data for the GetDatabaseNamesFromDataSource WSDL operation.
GetDatabaseNamesFromDataSourceResponse	The result data for the GetDatabaseNamesFromDataSource WSDL operation.

3.1.4.34.2.1 GetDatabaseNamesFromDataSource

The **GetDatabaseNamesFromDataSource** element specifies the input data for the **GetDatabaseNamesFromDataSource** WSDL operation.

```
<xs:element name="GetDatabaseNamesFromDataSource"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: The data source (1). This element **MUST** be present.

3.1.4.34.2.2 GetDatabaseNamesFromDataSourceResponse

The **GetDatabaseNamesFromDataSourceResponse** element specifies the result data for the **GetDatabaseNamesFromDataSource** WSDL operation.

```
<xs:element name="GetDatabaseNamesFromDataSourceResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<xs:complexType>
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="GetDatabaseNamesFromDataSourceResult"
type="tns:ArrayOfString"/>
  </xs:sequence>
</xs:complexType>
</xs:element>

```

GetDatabaseNamesFromDataSourceResult: An array of strings. This element **MUST** be present.

3.1.4.34.3 Complex Types

None.

3.1.4.34.4 Simple Types

None.

3.1.4.34.5 Attributes

None.

3.1.4.34.6 Groups

None.

3.1.4.34.7 Attribute Groups

None.

3.1.4.35 GetDataSource

The **GetDataSource** operation retrieves a data source (1).

The following is the WSDL port type specification of the **GetDataSource** WSDL operation.

```

<wsdl:operation name="GetDataSource" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetDataSourceSoapIn"/>
  <wsdl:output message="tns:GetDataSourceSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetDataSourceSoapIn** request message (section [3.1.4.35.1.1](#)), and the server (2) responds with a **GetDataSourceSoapOut** response message (section [3.1.4.35.1.2](#)) as follows:

- Receives a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the data source (1) to be retrieved.
- The server (2) sends the corresponding data source (1).
- In the event that a data source (1) cannot be retrieved, the server (2) **SHOULD** [<29>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.35.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetDataSourceSoapIn	The request WSDL message for the GetDataSource WSDL operation.
GetDataSourceSoapOut	The response WSDL message for the GetDataSource WSDL operation.

3.1.4.35.1.1 GetDataSourceSoapIn

The request WSDL message for the **GetDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetDataSource
```

The SOAP body contains the **GetDataSource** element.

3.1.4.35.1.2 GetDataSourceSoapOut

The response WSDL message for the **GetDataSource** WSDL operation.

The SOAP body contains the **GetDataSourceResponse** element.

3.1.4.35.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetDataSource	The input data for the GetDataSource WSDL operation.
GetDataSourceResponse	The result data for the GetDataSource WSDL operation.

3.1.4.35.2.1 GetDataSource

The **GetDataSource** element specifies the input data for the **GetDataSource** WSDL operation.

```
<xs:element name="GetDataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
```

```

    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

location: A **RepositoryLocation** complex type (section [2.2.4.161](#)) of a data source. This element **MUST** be present.

3.1.4.35.2.2 GetDataSourceResponse

The **GetDataSourceResponse** element specifies the result data for the **GetDataSource** WSDL operation.

```

<xs:element name="GetDataSourceResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetDataSourceResult"
type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetDataSourceResult: A data source (1), as specified in the **DataSource** complex type (section [2.2.4.85](#)). This element **MUST** be present.

3.1.4.35.3 Complex Types

None.

3.1.4.35.4 Simple Types

None.

3.1.4.35.5 Attributes

None.

3.1.4.35.6 Groups

None.

3.1.4.35.7 Attribute Groups

None.

3.1.4.36 GetDependentElements

The **GetDependentElements** operation retrieves from the server (2) all **FirstClassElement** complex types (section [2.2.4.99](#)) associated with a list (1) of repository locations. In addition, all **FirstClassElements** that are related by reference are also included in the response. For example, for a requested scorecard, all **Kpis**, **Indicators**, and **DataSources** that the scorecard depends on will also be retrieved.

The following is the WSDL port type specification of the **GetDependentElements** WSDL operation.

```
<wsdl:operation name="GetDependentElements" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetDependentElementsSoapIn"/>
  <wsdl:output message="tns:GetDependentElementsSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetDependentElementsSoapIn** request message (section [3.1.4.36.1.1](#)), and the server (2) responds with a **GetDependentElementsSoapOut** response message (section [3.1.4.36.1.2](#)) as follows:

- The protocol client sends a list (1) of **RepositoryLocation** complex types (section [2.2.4.161](#)).
- The server (2) responds with a **DependentElementInfo** complex type (section [3.1.4.36.3.2](#)) containing all **FirstClassElement** items specified by the list of **RepositoryLocations**, all associated sub-items, and all containing list URLs.
- In the event that all **FirstClassElement** items and sub-items referenced by the list cannot be retrieved, the server (2) SHOULD [<30>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.36.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetDependentElementsSoapIn	The request WSDL message for the GetDependentElements WSDL operation.
GetDependentElementsSoapOut	The response WSDL message for the GetDependentElements WSDL operation.

3.1.4.36.1.1 GetDependentElementsSoapIn

The request WSDL message for the **GetDependentElements** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetDependentElements
```

The SOAP body contains the **GetDependentElements** element.

3.1.4.36.1.2 GetDependentElementsSoapOut

The response WSDL message for the **GetDependentElements** WSDL operation.

The SOAP body contains the **GetDependentElementsResponse** element.

3.1.4.36.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetDependentElements	The input data for the GetDependentElements WSDL operation.
GetDependentElementsResponse	The result data for the GetDependentElements WSDL operation.

3.1.4.36.2.1 GetDependentElements

The **GetDependentElements** element specifies the input data for the **GetDependentElements** WSDL operation.

```
<xs:element name="GetDependentElements" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="missingItems"
type="tns:ArrayOfRepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

missingItems: An **ArrayOfRepositoryLocation** complex type, as specified in section [3.1.4.36.3.1](#). This element specifies which items to retrieve.

3.1.4.36.2.2 GetDependentElementsResponse

The **GetDependentElementsResponse** element specifies the result data for the **GetDependentElements** WSDL operation.

```
<xs:element name="GetDependentElementsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetDependentElementsResult"
type="tns:DependentElementInfo"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetDependentElementsResult: A **DependentElementInfo** complex type, as specified in section [3.1.4.36.3.2](#). This element **MUST** be present.

3.1.4.36.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfRepositoryList	Specifies an array of RepositoryList elements.
ArrayOfRepositoryLocation	Specifies an array of RepositoryLocation .
DependentElementInfo	Contains elements and associated list references.
ListLocation	Contains the necessary information to identify a list (1) on the server (2).
RepositoryList	Specifies a location where FirstClassElement (section 2.2.4.99) items are stored on the server.

3.1.4.36.3.1 ArrayOfRepositoryLocation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfRepositoryLocation** complex type specifies an array of **RepositoryLocation** complex types (section [2.2.4.161](#)).

```
<xs:complexType name="ArrayOfRepositoryLocation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="RepositoryLocation" nillable="true"
      type="tns:RepositoryLocation"/>
  </xs:sequence>
</xs:complexType>
```

RepositoryLocation: This element MUST NOT be null and MUST conform to the schema of the **RepositoryLocation**.

3.1.4.36.3.2 DependentElementInfo

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **DependentElementInfo** complex type contains elements and associated list references.

```
<xs:complexType name="DependentElementInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="DependentLists"
      type="tns:ArrayOfRepositoryList"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DependentElements"
      type="tns:ArrayOfFirstClassElement"/>
  </xs:sequence>
</xs:complexType>
```

DependentLists: An **ArrayOfRepositoryList** complex type (section [3.1.4.36.3.3](#)). A collection of lists (1) associated with the items in **DependentElements**.

DependentElements: An **ArrayOfFirstClassElement** complex type (section [2.2.4.34](#)). A collection of **FirstClassElement** complex type items (section [2.2.4.99](#)), and all items associated through **FirstClassElement** references.

3.1.4.36.3.3 ArrayOfRepositoryList

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfRepositoryList** complex type specifies an array of **RepositoryList** elements (section [3.1.4.36.3.4](#)).

```
<xs:complexType name="ArrayOfRepositoryList" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="RepositoryList" nillable="true"
      type="tns:RepositoryList"/>
  </xs:sequence>
</xs:complexType>
```

RepositoryList: This element MUST NOT be null and MUST conform to the schema of the **RepositoryList** complex type (section [3.1.4.36.3.4](#)).

3.1.4.36.3.4 RepositoryList

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **RepositoryList** complex type specifies a location where **FirstClassElement** complex type items (section [2.2.4.99](#)) are stored on the server (2).

```
<xs:complexType name="RepositoryList" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Location" type="tns:ListLocation"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SupportedTypes" type="tns:FCOContentType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Title" type="xs:string"/>
    <xs:element xmlns:s1="http://microsoft.com/wsdl/types/" minOccurs="1" maxOccurs="1"
      name="ListId" type="s1:guid"/>
  </xs:sequence>
</xs:complexType>
```

Location: Specifies the **ListLocation** complex type (section [3.1.4.36.3.5](#)). This element MUST be present.

SupportedTypes: The content types that are supported in the form of the **FCOContentType** simple type (section [3.1.4.36.4.1](#)).

Title: Specifies the title for the **RepositoryList**. This element MUST be present. The value MUST NOT be empty and MUST NOT consist of only whitespace characters.

ListId: Specifies the identity for this **RepositoryList**. This element MUST be formatted as a GUID.

3.1.4.36.3.5 ListLocation

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ListLocation** complex type contains the necessary information to identify a list (1) on the server (2).

```

<xs:complexType name="ListLocation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="SiteUrl" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ListUrl" type="xs:string"/>
  </xs:sequence>
</xs:complexType>

```

SiteUrl: The url for the server where the list (1) is located. The attribute MUST be a valid [\[RFC1738\]](#) URL.

ListUrl: The location on the server where the list (1) is located. MUST be present. MUST be a valid URL as specified in [\[RFC1738\]](#).

3.1.4.36.4 Simple Types

The following table summarizes the XML schema simple type definitions that are specific to this operation.

Simple type	Description
FCOContentType	

3.1.4.36.4.1 FCOContentType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **FCOContentType** simple type specifies the type of an **FCO**.

```

<xs:simpleType name="FCOContentType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="PpsDashboard"/>
        <xs:enumeration value="PpsScorecard"/>
        <xs:enumeration value="PpsKpi"/>
        <xs:enumeration value="PpsReportView"/>
        <xs:enumeration value="PpsIndicator"/>
        <xs:enumeration value="PpsDataSource"/>
        <xs:enumeration value="PpsFilter"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>

```

The following table specifies the allowable values for the **FCOContentType** simple type.

Value	Meaning
None	The type of object is unknown.
PpsDashboard	The object is a Dashboard .
PpsScorecard	The object is a Scorecard .

Value	Meaning
PpsKpi	The object is a Kpi .
PpsReportView	The object is a ReportView .
PpsIndicator	The object is an Indicator .
PpsDataSource	The object is a DataSource .
PpsFilter	The object is a Filter .

3.1.4.36.5 Attributes

None.

3.1.4.36.6 Groups

None.

3.1.4.36.7 Attribute Groups

None.

3.1.4.37 GetDimensions

The **GetDimensions** operation retrieves an array of dimension (1) objects.

The following is the WSDL port type specification of the **GetDimensions** WSDL operation.

```
<wsdl:operation name="GetDimensions" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetDimensionsSoapIn"/>
  <wsdl:output message="tns:GetDimensionsSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetDimensionsSoapIn** request message (section [3.1.4.37.1.1](#)), and the server (2) responds with a **GetDimensionsSoapOut** response message (section [3.1.4.37.1.2](#)) as follows:

- Receives a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the associated data source (1).
- The server (2) sends the corresponding **ArrayOfDimension** complex type (section [2.2.4.32](#)).

Exceptions:

Error code	Description
DataSourceConnectionFailed	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceHostNotFound	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceConnectionUnsupported	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceDatabaseNotFound	See Common List of Error Codes (section 2.2.2.1.3).

Error code	Description
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.37.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetDimensionsSoapIn	The request WSDL message for the GetDimensions WSDL operation.
GetDimensionsSoapOut	The response WSDL message for the GetDimensions WSDL operation.

3.1.4.37.1.1 GetDimensionsSoapIn

The request WSDL message for the **GetDimensions** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetDimensions
```

The SOAP body contains the **GetDimensions** element.

3.1.4.37.1.2 GetDimensionsSoapOut

The response WSDL message for the **GetDimensions** WSDL operation.

The SOAP body contains the **GetDimensionsResponse** element.

3.1.4.37.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetDimensions	The input data for the GetDimensions WSDL operation.
GetDimensionsResponse	The result data for the GetDimensions WSDL operation.

3.1.4.37.2.1 GetDimensions

The **GetDimensions** element specifies the input data for the **GetDimensions** WSDL operation.

```
<xs:element name="GetDimensions" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
```

```

        <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
</xs:complexType>
</xs:element>

```

dataSourceLocation: A **RepositoryLocation** complex type (section [2.2.4.161](#)). This element MUST be present.

3.1.4.37.2.2 GetDimensionsResponse

The **GetDimensionsResponse** element specifies the result data for the **GetDimensions** WSDL operation.

```

<xs:element name="GetDimensionsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetDimensionsResult"
type="tns:ArrayOfDimension"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetDimensionsResult: An **ArrayOfDimension** complex type (section [2.2.4.32](#)). This element MUST be present.

3.1.4.37.3 Complex Types

None.

3.1.4.37.4 Simple Types

None.

3.1.4.37.5 Attributes

None.

3.1.4.37.6 Groups

None.

3.1.4.37.7 Attribute Groups

None.

3.1.4.38 GetDimensionsFromDataSource

The **GetDimensionsFromDataSource** operation retrieves an array of dimension (1) objects (see section [2.2.4.90](#)).

The following is the WSDL port type specification of the **GetDimensionsFromDataSource** WSDL operation.

```

<wsdl:operation name="GetDimensionsFromDataSource"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetDimensionsFromDataSourceSoapIn"/>
  <wsdl:output message="tns:GetDimensionsFromDataSourceSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetDimensionsFromDataSourceSoapIn** request message (section [3.1.4.38.1.1](#)), and the server (2) responds with a **GetDimensionsFromDataSourceSoapOut** response message (section [3.1.4.38.1.2](#)) as follows:

- Receives a **DataSource** complex type (section [2.2.4.85](#)).
- The server (2) sends the corresponding **ArrayOfDimension** complex type (section [2.2.4.32](#)).

Exceptions:

Error code	Description
DataSourceConnectionFailed	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceHostNotFound	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceConnectionUnsupported	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceDatabaseNotFound	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.38.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetDimensionsFromDataSourceSoapIn	The request WSDL message for the GetDimensionsFromDataSource WSDL operation.
GetDimensionsFromDataSourceSoapOut	The response WSDL message for the GetDimensionsFromDataSource WSDL operation.

3.1.4.38.1.1 GetDimensionsFromDataSourceSoapIn

The request WSDL message for the **GetDimensionsFromDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetDimensionsFromDataSource
```

The SOAP body contains the **GetDimensionsFromDataSource** element.

3.1.4.38.1.2 GetDimensionsFromDataSourceSoapOut

The response WSDL message for the **GetDimensionsFromDataSource** WSDL operation.

The SOAP body contains the **GetDimensionsFromDataSourceResponse** element.

3.1.4.38.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetDimensionsFromDataSource	The input data for the GetDimensionsFromDataSource WSDL operation.
GetDimensionsFromDataSourceResponse	The result data for the GetDimensionsFromDataSource WSDL operation.

3.1.4.38.2.1 GetDimensionsFromDataSource

The **GetDimensionsFromDataSource** element specifies the input data for the **GetDimensionsFromDataSource** WSDL operation.

```
<xs:element name="GetDimensionsFromDataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: A data source (1), as specified in section [2.2.4.85](#). This element MUST be present.

3.1.4.38.2.2 GetDimensionsFromDataSourceResponse

The **GetDimensionsFromDataSourceResponse** element specifies the result data for the **GetDimensionsFromDataSource** WSDL operation.

```
<xs:element name="GetDimensionsFromDataSourceResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetDimensionsFromDataSourceResult"
        type="tns:ArrayOfDimension"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetDimensionsFromDataSourceResult: An **ArrayOfDimension** complex type (section [2.2.4.32](#)). This element MUST be present.

3.1.4.38.3 Complex Types

None.

3.1.4.38.4 Simple Types

None.

3.1.4.38.5 Attributes

None.

3.1.4.38.6 Groups

None.

3.1.4.38.7 Attribute Groups

None.

3.1.4.39 GetFilter

The **GetFilter** operation retrieves a **Filter** complex type (section [2.2.4.98](#)).

The following is the WSDL port type specification of the **GetFilter** WSDL operation.

```
<wsdl:operation name="GetFilter" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetFilterSoapIn"/>
  <wsdl:output message="tns:GetFilterSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetFilterSoapIn** request message (section [3.1.4.40.1.1](#)), and the server (2) responds with a **GetFilterSoapOut** response message (section [3.1.4.40.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the **Filter** to be retrieved.
- The server (2) responds with the corresponding **Filter**.
- In the event the **Filter** cannot be retrieved, the server (2) SHOULD [<31>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.39.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetFilterSoapIn	The request WSDL message for the GetFilter WSDL operation.
GetFilterSoapOut	The response WSDL message for the GetFilter WSDL operation.

3.1.4.39.1.1 GetFilterSoapIn

The request WSDL message for the **GetFilter** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetFilter
```

The SOAP body contains the **GetFilter** element.

3.1.4.39.1.2 GetFilterSoapOut

The response WSDL message for the **GetFilter** WSDL operation.

The SOAP body contains the **GetFilterResponse** element.

3.1.4.39.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetFilter	The input data for the GetFilter WSDL operation.
GetFilterResponse	The result data for the GetFilter WSDL operation.

3.1.4.39.2.1 GetFilter

The **GetFilter** element specifies the input data for the **GetFilter** WSDL operation.

```
<xs:element name="GetFilter" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present. The **ItemUrl** property MUST contain a valid URL.

3.1.4.39.2.2 GetFilterResponse

The **GetFilterResponse** element specifies the result data for the **GetFilter** WSDL operation.

```
<xs:element name="GetFilterResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetFilterResult" type="tns:Filter"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetFilterResult: A **Filter** complex type, as specified in section [2.2.4.98](#). This element SHOULD be present.

3.1.4.39.3 Complex Types

None.

3.1.4.39.4 Simple Types

None.

3.1.4.39.5 Attributes

None.

3.1.4.39.6 Groups

None.

3.1.4.39.7 Attribute Groups

None.

3.1.4.40 GetIndicator

The **GetIndicator** operation retrieves an **Indicator** complex type (section [2.2.4.125](#)) from the server (2).

The following is the WSDL port type specification of the **GetIndicator** WSDL operation.

```
<wsdl:operation name="GetIndicator" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetIndicatorSoapIn"/>
  <wsdl:output message="tns:GetIndicatorSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetIndicatorSoapIn** request message (section [3.1.4.40.1.1](#)), and the server (2) responds with a **GetIndicatorSoapOut** response message (section [3.1.4.40.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the **Indicator** to be retrieved.

- The server (2) sends the corresponding **Indicator**.
- In the event that an **indicator** cannot be retrieved, the server (2) SHOULD [<32>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.40.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetIndicatorSoapIn	The request WSDL message for the GetIndicator WSDL operation.
GetIndicatorSoapOut	The response WSDL message for the GetIndicator WSDL operation.

3.1.4.40.1.1 GetIndicatorSoapIn

The request WSDL message for the **GetIndicator** WSDL operation.

The SOAP action value is:

`http://www.microsoft.com/performancepoint/scorecards/GetIndicator`

The SOAP body contains the **GetIndicator** element.

3.1.4.40.1.2 GetIndicatorSoapOut

The response WSDL message for the **GetIndicator** WSDL operation.

The SOAP body contains the **GetIndicatorResponse** element.

3.1.4.40.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetIndicator	The input data for the GetIndicator WSDL operation.
GetIndicatorResponse	The result data for the GetIndicator WSDL operation.

3.1.4.40.2.1 GetIndicator

The **GetIndicator** element specifies the input data for the **GetIndicator** WSDL operation.

```
<xs:element name="GetIndicator" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: The **RepositoryLocation** complex type object (section [2.2.4.161](#)) that specifies the location of the indicator on the server (2).

- It MUST be present.
- The **ItemUrl** property MUST be set to the location of the **indicator**.

3.1.4.40.2.2 GetIndicatorResponse

The **GetIndicatorResponse** element specifies the result data for the **GetIndicator** WSDL operation.

```
<xs:element name="GetIndicatorResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetIndicatorResult"
        type="tns:Indicator"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetIndicatorResult: The **Indicator** complex type object (section [2.2.4.125](#)) that was requested from the server (2).

3.1.4.40.3 Complex Types

None.

3.1.4.40.4 Simple Types

None.

3.1.4.40.5 Attributes

None.

3.1.4.40.6 Groups

None.

3.1.4.40.7 Attribute Groups

None.

3.1.4.41 GetKpi

The **GetKpi** operation retrieves a **Kpi** complex type object (section [2.2.4.128](#)).

The following is the WSDL port type specification of the **GetKpi** WSDL operation.

```
<wsdl:operation name="GetKpi" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetKpiSoapIn"/>
  <wsdl:output message="tns:GetKpiSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetKpiSoapIn** request message (section [3.1.4.41.1.1](#)), and the server (2) responds with a **GetKpiSoapOut** response message (section [3.1.4.41.1.2](#)) as follows:

- The server (2) receives the **RepositoryLocation** complex type (section [2.2.4.161](#)) of a **Kpi**.
- The server (2) MUST retrieve the **Kpi**.
- In the event that a **Kpi** cannot be retrieved, the server (2) SHOULD [<33>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.41.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetKpiSoapIn	The request WSDL message for the GetKpi WSDL operation.
GetKpiSoapOut	The response WSDL message for the GetKpi WSDL operation.

3.1.4.41.1.1 GetKpiSoapIn

The request WSDL message for the **GetKpi** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetKpi
```

The SOAP body contains the **GetKpi** element.

3.1.4.41.1.2 GetKpiSoapOut

The response WSDL message for the **GetKpi** WSDL operation.

The SOAP body contains the **GetKpiResponse** element.

3.1.4.41.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetKpi	The input data for the GetKpi WSDL operation.
GetKpiResponse	The result data for the GetKpi WSDL operation.

3.1.4.41.2.1 GetKpi

The **GetKpi** element specifies the input data for the **GetKpi** WSDL operation.

```
<xs:element name="GetKpi" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: The location of the KPI to be retrieved, as specified by a **RepositoryLocation** complex type (section [2.2.4.161](#)). This element **MUST** be present.

3.1.4.41.2.2 GetKpiResponse

The **GetKpiResponse** element specifies the result data for the **GetKpi** WSDL operation.

```
<xs:element name="GetKpiResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetKpiResult" type="tns:Kpi"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetKpiResult: The **Kpi** complex type object (section [2.2.4.128](#)) that was requested from the server (2).

3.1.4.41.3 Complex Types

None.

3.1.4.41.4 Simple Types

None.

3.1.4.41.5 Attributes

None.

3.1.4.41.6 Groups

None.

3.1.4.41.7 Attribute Groups

None.

3.1.4.42 GetKpisFromScorecard

The **GetKpisFromScorecard** operation retrieves an array of **Kpi** complex type objects (section [2.2.4.128](#)) associated with a scorecard.

The following is the WSDL port type specification of the **GetKpisFromScorecard** WSDL operation.

```
<wsdl:operation name="GetKpisFromScorecard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetKpisFromScorecardSoapIn"/>
  <wsdl:output message="tns:GetKpisFromScorecardSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetKpisFromScorecardSoapIn** request message (section [3.1.4.43.1.1](#)), and the server (2) responds with a **GetKpisFromScorecardSoapOut** response message (section [3.1.4.43.1.2](#)) as follows:

- The server (2) receives a **RepositoryLocation** complex type (section [2.2.4.161](#)) of a scorecard.
- The server (2) MUST retrieve the array of **Kpi** elements.

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.42.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetKpisFromScorecardSoapIn	The request WSDL message for the GetKpisFromScorecard WSDL operation.
GetKpisFromScorecardSoapOut	The response WSDL message for the GetKpisFromScorecard WSDL operation.

3.1.4.42.1.1 GetKpisFromScorecardSoapIn

The request WSDL message for the **GetKpisFromScorecard** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetKpisFromScorecard
```

The SOAP body contains the **GetKpisFromScorecard** element.

3.1.4.42.1.2 GetKpisFromScorecardSoapOut

The response WSDL message for the **GetKpisFromScorecard** WSDL operation.

The SOAP body contains the **GetKpisFromScorecardResponse** element.

3.1.4.42.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetKpisFromScorecard	The input data for the GetKpisFromScorecard WSDL operation.
GetKpisFromScorecardResponse	The result data for the GetKpisFromScorecard WSDL operation.

3.1.4.42.2.1 GetKpisFromScorecard

The **GetKpisFromScorecard** element specifies the input data for the **GetKpisFromScorecard** WSDL operation.

```
<xs:element name="GetKpisFromScorecard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

scorecardLocation: The location of a scorecard, as specified by the **RepositoryLocation** complex type (section [2.2.4.161](#)). This element **MUST** be present.

3.1.4.42.2 GetKpisFromScorecardResponse

The **GetKpisFromScorecardResponse** element specifies the result data for the **GetKpisFromScorecard** WSDL operation.

```
<xs:element name="GetKpisFromScorecardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetKpisFromScorecardResult"
        type="tns:ArrayOfKpi"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetKpisFromScorecardResult: An array of **Kpi** complex type elements (section [2.2.4.128](#)) that was requested from the server (2).

3.1.4.42.3 Complex Types

None.

3.1.4.42.4 Simple Types

None.

3.1.4.42.5 Attributes

None.

3.1.4.42.6 Groups

None.

3.1.4.42.7 Attribute Groups

None.

3.1.4.43 GetLatestAnalyticReportVersion

The **GetLatestAnalyticReportVersion** operation retrieves from the server (2) the version number for a report view that has been created through **SaveTemporaryAnalyticReport** operation (section [3.1.4.65](#)).

The following is the WSDL port type specification of the **GetLatestAnalyticReportVersion** WSDL operation.

```
<wsdl:operation name="GetLatestAnalyticReportVersion"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetLatestAnalyticReportVersionSoapIn"/>
  <wsdl:output message="tns:GetLatestAnalyticReportVersionSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetReportViewSoapIn** request message (section [3.1.4.43.1.1](#)) and the server (2) responds with a **GetReportViewSoapOut** response message (section [3.1.4.43.1.2](#)) as follows:

- The protocol client sends a GUID that uniquely identifies a report view.
- The server (2) sends an integer representing the latest version number of the corresponding report view.

In case of failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is specified in section [2.2.2.1](#).

3.1.4.43.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetLatestAnalyticReportVersionSoapIn	The request WSDL message for the GetLatestAnalyticReportVersion WSDL operation.
GetLatestAnalyticReportVersionSoapOut	The response WSDL message for the GetLatestAnalyticReportVersion WSDL operation.

3.1.4.43.1.1 GetLatestAnalyticReportVersionSoapIn

The request WSDL message for the **GetLatestAnalyticReportVersion** WSDL operation.

The SOAP action value is:

`http://www.microsoft.com/performancepoint/scorecards/GetLatestAnalyticReportVersion`

The SOAP body contains the **GetLatestAnalyticReportVersion** element.

3.1.4.43.1.2 GetLatestAnalyticReportVersionSoapOut

The response WSDL message for the **GetLatestAnalyticReportVersion** WSDL operation.

The SOAP body contains the **GetLatestAnalyticReportVersionResponse** element.

3.1.4.43.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetLatestAnalyticReportVersion	The input data for the GetLatestAnalyticReportVersion WSDL operation.
GetLatestAnalyticReportVersionResponse	The result data for the GetLatestAnalyticReportVersion WSDL operation.

3.1.4.43.2.1 GetLatestAnalyticReportVersion

The **GetLatestAnalyticReportVersion** element specifies the input data for the **GetLatestAnalyticReportVersion** WSDL operation.

```
<xs:element name="GetLatestAnalyticReportVersion"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="analyticReportViewId"
        xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

analyticReportViewId: The **SaveTemporaryAnalyticReportResult** element (section [3.1.4.65.2.2](#)) returned when the report view was saved. This element MUST be present.

3.1.4.43.2.2 GetLatestAnalyticReportVersionResponse

The **GetLatestAnalyticReportVersionResponse** element specifies the result data for the **GetLatestAnalyticReportVersion** WSDL operation.

```
<xs:element name="GetLatestAnalyticReportVersionResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="GetLatestAnalyticReportVersionResult"
        type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetLatestAnalyticReportVersionResult: The version number of the report view. This element MUST be present.

3.1.4.43.3 Complex Types

None.

3.1.4.43.4 Simple Types

None.

3.1.4.43.5 Attributes

None.

3.1.4.43.6 Groups

None.

3.1.4.43.7 Attribute Groups

None.

3.1.4.44 GetListItems

The **GetListItems** operation retrieves all **FirstClassElements** complex types (section [2.2.4.99](#)) associated with a given repository list (1) from the server (2).

The following is the WSDL port type specification of the **GetListItems** WSDL operation.

```
<wsdl:operation name="GetListItems" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetListItemsSoapIn"/>
  <wsdl:output message="tns:GetListItemsSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetListItemsSoapIn** request message (section [3.1.4.44.1.1](#)), and the server (2) responds with a **GetListItemsSoapOut** response message (section [3.1.4.44.1.2](#)) as follows:

- The protocol client sends the URL of the list (1) from which to retrieve items.
- The server (2) responds with a collection of corresponding **FirstClassElement** items.
- In the event that all **FirstClassElement** items in the list (1) cannot be retrieved, the server (2) SHOULD [<34>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.44.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetListItemsSoapIn	The request WSDL message for the GetListItems WSDL operation.
GetListItemsSoapOut	The response WSDL message for the GetListItems WSDL operation.

3.1.4.44.1.1 GetListItemsSoapIn

The request WSDL message for the **GetListItems** WSDL operation.

The SOAP action value is:

The SOAP body contains the **GetListItems** element.

3.1.4.44.1.2 GetListItemsSoapOut

The response WSDL message for the **GetListItems** WSDL operation.

The SOAP body contains the **GetListItemsResponse** element.

3.1.4.44.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetListItems	The input data for the GetListItems WSDL operation.
GetListItemsResponse	The result data for the GetListItems WSDL operation.

3.1.4.44.2.1 GetListItems

The **GetListItems** element specifies the input data for the **GetListItems** WSDL operation.

```
<xs:element name="GetListItems" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

listUrl: A server-relative URL that references the list (1) on the server (2) from which to retrieve the items. This element **MUST** be present and **MUST** be a valid URL.

3.1.4.44.2.2 GetListItemsResponse

The **GetListItemsResponse** element specifies the result data for the **GetListItems** WSDL operation.

```
<xs:element name="GetListItemsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetListItemsResult"
type="tns:ArrayOfFirstClassElement"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetListItemsResult: An array of **FirstClassElement** complex type objects (section [2.2.4.99](#)), as specified in the **ArrayOfFirstClassElement** (section [2.2.4.34](#)). This element **MUST** be present. This

array MUST contain one element for each item in the requested list (1) and SHOULD NOT contain null elements.

3.1.4.44.3 Complex Types

None.

3.1.4.44.4 Simple Types

None.

3.1.4.44.5 Attributes

None.

3.1.4.44.6 Groups

None.

3.1.4.44.7 Attribute Groups

None.

3.1.4.45 GetMdx

The **GetMdx** operation retrieves an MDX that can be used to query data sources for the given analytic report. The Analytic Chart and Analytic Grid report view types contain custom data that is used to generate MDX queries. See the **ReportView** complex type (section [2.2.4.160](#)) for more detail.

The following is the WSDL port type specification of the **GetMdx** WSDL operation.

```
<wsdl:operation name="GetMdx" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetMdxSoapIn"/>
  <wsdl:output message="tns:GetMdxSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetMdxSoapIn** request message (section [3.1.4.45.1.1](#)), and the server (2) responds with a **GetMdxSoapOut** response message (section [3.1.4.45.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) referencing the analytic report from which to generate the MDX.
- The server (2) responds with an MDX expression.
- In the event the MDX cannot be retrieved, the server (2) SHOULD [<35>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.45.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetMdxSoapIn	The request WSDL message for the GetMdx WSDL operation.
GetMdxSoapOut	The response WSDL message for the GetMdx WSDL operation.

3.1.4.45.1.1 GetMdxSoapIn

The request WSDL message for the **GetMdx** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetMdx
```

The SOAP body contains the **GetMdx** element.

3.1.4.45.1.2 GetMdxSoapOut

The response WSDL message for the **GetMdx** WSDL operation.

The SOAP body contains the **GetMdxResponse** element.

3.1.4.45.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetMdx	The input data for the GetMdx WSDL operation.
GetMdxResponse	The result data for the GetMdx WSDL operation.

3.1.4.45.2.1 GetMdx

The **GetMdx** element specifies the input data for the **GetMdx** WSDL operation.

```
<xs:element name="GetMdx" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
```



```

        <xs:element minOccurs="0" maxOccurs="1" name="analyticReportViewLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
</xs:complexType>
</xs:element>

```

analyticReportViewLocation: A **RepositoryLocation** complex type (section [2.2.4.161](#)). This element **MUST** be present.

- If the report view was created with the **CreateReportView** operation (section [3.1.4.7](#)), the **ItemUrl** property **MUST** contain a valid URL. **ItemType** and **ItemGuid** are set by the server (2).
- If the report view was created with the **SaveTemporaryAnalyticReport** operation (section [3.1.4.65](#)):
 - The **ItemGuid** property **MUST** equal the GUID that was returned from **SaveTemporaryAnalyticReport**.
 - The **ItemType** property **MUST** equal **TempReportView**, as specified by **FirstClassObjectType** simple type (section [2.2.5.20](#)).
 - The **ItemUrl** property **MUST** equal an empty string.

3.1.4.45.2.2 GetMdxResponse

The **GetMdxResponse** element specifies the result data for the **GetMdx** WSDL operation.

```

<xs:element name="GetMdxResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetMdxResult" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetMdxResult: A string that represents an MDX. This string **SHOULD NOT** be empty.

3.1.4.45.3 Complex Types

None.

3.1.4.45.4 Simple Types

None.

3.1.4.45.5 Attributes

None.

3.1.4.45.6 Groups

None.

3.1.4.45.7 Attribute Groups

None.

3.1.4.46 GetParameterDisplayData

The **GetParameterDisplayData** operation builds a template data table containing only the columns produced by a specific parameter type. The referred parameter represents a specific kind of connection between two Web Parts. The resulting **DataTable** (as described in [\[DataTable\]](#)) represents an empty sample of the information that gets passed on that connection.

The following is the WSDL port type specification of the **GetParameterDisplayData** WSDL operation.

```
<wsdl:operation name="GetParameterDisplayData" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetParameterDisplayDataSoapIn"/>
  <wsdl:output message="tns:GetParameterDisplayDataSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetParameterDisplayDataSoapIn** request message (section [3.1.4.46.1.1](#)), and the server (2) responds with a **GetParameterDisplayDataSoapOut** response message (section [3.1.4.46.1.2](#)) as follows:

- The server (2) uses the **ParameterProviderId** property from the **ParameterDefinition** complex type (section [2.2.4.155](#)) to identify one of the parameter providers registered on the server (2).
- The server (2) creates the **DataTable** containing all columns used by that parameter type. The server (2) uses the data source (1) referenced by **parameterSourceLocation** and the **GridViewData** [<36>](#) complex type (section [2.2.4.121](#)) referenced by **gridViewData** element (see section [3.1.4.46.2.1](#)) to create the **DataTable**.

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.46.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetParameterDisplayDataSoapIn	The request WSDL message for the GetParameterDisplayData WSDL operation.
GetParameterDisplayDataSoapOut	The response WSDL message for the GetParameterDisplayData WSDL operation.

3.1.4.46.1.1 GetParameterDisplayDataSoapIn

The request WSDL message for the **GetParameterDisplayData** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetParameterDisplayData
```

The SOAP body contains the **GetParameterDisplayData** element.

3.1.4.46.1.2 GetParameterDisplayDataSoapOut

The response WSDL message for the **GetParameterDisplayData** WSDL operation.

The SOAP body contains the **GetParameterDisplayDataResponse** element.

3.1.4.46.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetParameterDisplayData	The input data for the GetParameterDisplayData WSDL operation.
GetParameterDisplayDataResponse	The result data for the GetParameterDisplayData WSDL operation.

3.1.4.46.2.1 GetParameterDisplayData

The **GetParameterDisplayData** element specifies the input data for the **GetParameterDisplayData** WSDL operation.

```
<xs:element name="GetParameterDisplayData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="parameterDefinition"
type="tns:ParameterDefinition"/>
      <xs:element minOccurs="0" maxOccurs="1" name="parameterSourceLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="gridViewData" type="tns:GridViewData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

parameterDefinition: Specifies the **ParameterDefinition** complex type (section [2.2.4.155](#)). This element MUST NOT be null and the **ParameterProviderId** property MUST refer to one of the parameter data providers registered on the server (2). This function supports only filter-type parameters shown in the following table.

ParameterProviderId	CustomDefinition
MDXParameterDataProvider	A MdxParameterDefinition object.

ParameterProviderId	CustomDefinition
MemberParameterDataProvider	A MemberParameterDefinition object.
NamedSetParameterDataProvider	A NamedSetParameterDefinition object.
TimeIntelligencePostFormulaProvider	A TimeIntelligencePostFormulaDefinition object.
TimeIntelligenceProvider	A TimeIntelligenceDefinition object.

parameterSourceLocation: Specifies a data source location as defined in a **RepositoryLocation** complex type (section [2.2.4.161](#)). This element MAY be null or empty, in which case if the parameter type requires a data source location, the resulting **DataTable** (as described in [\[DataTable\]](#)) is **NULL**.

The following parameter providers require an MDX capable OLAP data source (1).

ParameterProviderId	CustomDefinition
MDXParameterDataProvider	A MdxParameterDefinition object.
MemberParameterDataProvider	A MemberParameterDefinition object.
NamedSetParameterDataProvider	A NamedSetParameterDefinition object.

gridViewData: Unused. This element MUST be set to **NULL** and MUST be ignored by the protocol client.

3.1.4.46.2.2 GetParameterDisplayDataResponse

The **GetParameterDisplayDataResponse** element specifies the result data for the **GetParameterDisplayData** WSDL operation.

```
<xs:element name="GetParameterDisplayDataResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetParameterDisplayDataResult">
        <xs:complexType>
          <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded"
              namespace="http://www.w3.org/2001/XMLSchema" processContents="lax"/>
            <xs:any minOccurs="1" namespace="urn:schemas-microsoft-com:xml-diffgram-v1"
              processContents="lax"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetParameterDisplayDataResult: This defines the template data table that contains only the columns produced by a specific parameter type.

3.1.4.46.3 Complex Types

None.

3.1.4.46.4 Simple Types

None.

3.1.4.46.5 Attributes

None.

3.1.4.46.6 Groups

None.

3.1.4.46.7 Attribute Groups

None.

3.1.4.47 GetPreviewDataSet

The **GetPreviewDataSet** method retrieves a data set from a data source, which is suitable for previewing results.

The following is the WSDL port type specification of the **GetPreviewDataSet** WSDL operation.

```
<wsdl:operation name="GetPreviewDataSet" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetPreviewDataSetSoapIn"/>
  <wsdl:output message="tns:GetPreviewDataSetSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetPreviewDataSetSoapIn** request message (section [3.1.4.47.1.1](#)), and the server (2) responds with a **GetPreviewDataSetSoapOut** response message (section [3.1.4.47.1.2](#)) as follows:

- The protocol client sends a **DataSource** complex type (section [2.2.4.85](#)) that defines the data to be retrieved.
- The server (2) responds with a data set suitable for previewing the data.
- In the event a data set cannot be retrieved, the server (2) MUST return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceConnectionFailed	See Common List of Error Codes (section 2.2.2.1.3).
DataSourceConnectionUnsupported	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.47.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetPreviewDataSetSoapIn	The request WSDL message for the GetPreviewDataSet WSDL operation.
GetPreviewDataSetSoapOut	The response WSDL message for the GetPreviewDataSet WSDL operation.

3.1.4.47.1.1 GetPreviewDataSetSoapIn

The request WSDL message for the **GetPreviewDataSet** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetPreviewDataSet
```

The SOAP body contains the **GetPreviewDataSet** element.

3.1.4.47.1.2 GetPreviewDataSetSoapOut

The response WSDL message for the **GetPreviewDataSet** WSDL operation.

The SOAP body contains the **GetPreviewDataSetResponse** element.

3.1.4.47.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetPreviewDataSet	The input data for the GetPreviewDataSet WSDL operation.
GetPreviewDataSetResponse	The result data for the GetPreviewDataSet WSDL operation.

3.1.4.47.2.1 GetPreviewDataSet

The **GetPreviewDataSet** element specifies the input data for the **GetPreviewDataSet** WSDL operation.

```
<xs:element name="GetPreviewDataSet" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="maxRecords" type="xs:int"/>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
</xs:complexType>
</xs:element>
```

maxRecords: The maximum number of records to retrieve.

dataSource: The **DataSource** complex type (section [2.2.4.85](#)) to be used in the query. This element MUST NOT be null or empty. The **DataSource** MUST allow the query of preview data sets. [<37>](#)

3.1.4.47.2.2 GetPreviewDataSetResponse

The **GetPreviewDataSetResponse** element specifies the result data for the **GetPreviewDataSet** WSDL operation.

```
<xs:element name="GetPreviewDataSetResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetPreviewDataSetResult">
        <xs:complexType mixed="true">
          <xs:sequence>
            <xs:any/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetPreviewDataSetResult: The data set matching the specifications in the **DataSource** complex type (section [2.2.4.85](#)). The data set MUST include two elements: a schema element and a data element. The content of the data element MUST conform to the schema in the schema element. The data set SHOULD include one table, but MAY be empty if the **dataSource** is invalid. The data table MUST include the columns specified in **DataSource**.

3.1.4.47.3 Complex Types

None.

3.1.4.47.4 Simple Types

None.

3.1.4.47.5 Attributes

None.

3.1.4.47.6 Groups

None.

3.1.4.47.7 Attribute Groups

None.

3.1.4.48 GetQueryResultMembers

The **GetQueryResultMembers** operation retrieves an array of members (3) associated with the specified report.

The following is the WSDL port type specification of the **GetQueryResultMembers** WSDL operation.

```
<wsdl:operation name="GetQueryResultMembers" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetQueryResultMembersSoapIn"/>
  <wsdl:output message="tns:GetQueryResultMembersSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetQueryResultMembersSoapIn** request message (section [3.1.4.48.1.1](#)), and the server (2) responds with a **GetQueryResultMembersSoapOut** response message (section [3.1.4.48.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the report view. It also sends a unique dimension (1) name.
- The server (2) sends the corresponding **ArrayOfMember** complex type (section [2.2.4.45](#)).

Exceptions:

Error code	Description
InvalidDataSource	Current operation on the data source (1) cannot be finished because the data source (1) has failed basic validation.
InvalidReportView	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.48.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetQueryResultMembersSoapIn	The request WSDL message for the GetQueryResultMembers WSDL operation.
GetQueryResultMembersSoapOut	The response WSDL message for the GetQueryResultMembers WSDL operation.

3.1.4.48.1.1 GetQueryResultMembersSoapIn

The request WSDL message for the **GetQueryResultMembers** WSDL operation.

The SOAP action value is:

<http://www.microsoft.com/performancepoint/scorecards/GetQueryResultMembers>

The SOAP body contains the **GetQueryResultMembers** element.

3.1.4.48.1.2 GetQueryResultMembersSoapOut

The response WSDL message for the **GetQueryResultMembers** WSDL operation.

The SOAP body contains the **GetQueryResultMembersResponse** element.

3.1.4.48.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetQueryResultMembers	The input data for the GetQueryResultMembers WSDL operation.
GetQueryResultMembersResponse	The result data for the GetQueryResultMembers WSDL operation.

3.1.4.48.2.1 GetQueryResultMembers

The **GetQueryResultMembers** element specifies the input data for the **GetQueryResultMembers** WSDL operation.

```
<xs:element name="GetQueryResultMembers" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="analyticReportViewLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="formattingDimensionName"
type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

analyticReportViewLocation: A **RepositoryLocation** complex type (section [2.2.4.161](#)). This element **MUST** be present.

formattingDimensionName: The unique name of the formatting dimension (1). The element **MUST** be present.

3.1.4.48.2.2 GetQueryResultMembersResponse

The **GetQueryResultMembersResponse** element specifies the result data for the **GetQueryResultMembers** WSDL operation.

```
<xs:element name="GetQueryResultMembersResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
```

```

        <xs:element minOccurs="0" maxOccurs="1" name="GetQueryResultMembersResult"
type="tns:ArrayOfMember"/>
    </xs:sequence>
</xs:complexType>
</xs:element>

```

GetQueryResultMembersResult: This element MUST contain an **ArrayOfMember** complex type (section [2.2.4.45](#)).

3.1.4.48.3 Complex Types

None.

3.1.4.48.4 Simple Types

None.

3.1.4.48.5 Attributes

None.

3.1.4.48.6 Groups

None.

3.1.4.48.7 Attribute Groups

None.

3.1.4.49 GetRegisteredCustomFCOs

The **GetRegisteredCustomFCOs** operation retrieves custom object definitions registered on the server (2).

The following is the WSDL port type specification of the **GetRegisteredCustomFCOs** WSDL operation.

```

<wsdl:operation name="GetRegisteredCustomFCOs" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:input message="tns:GetRegisteredCustomFCOsSoapIn"/>
    <wsdl:output message="tns:GetRegisteredCustomFCOsSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetRegisteredCustomFCOsSoapIn** request message (section [3.1.4.49.1.1](#)), and the server (2) responds with a **GetRegisteredCustomFCOsSoapOut** response message (section [3.1.4.49.1.2](#)) as follows:

- The protocol client sends the type of custom objects to be returned by the server (2). The informed type MUST be one of the following: All, **DataSource**, **Filter**, and **ReportView**, as defined in the **CustomFCOType** simple type (section [3.1.4.49.4.1](#)).
- The server (2) reads all the custom object entries registered on the server (2) and returns only those matching the type provided by the client protocol.

- The result is a collection of **CustomFCODefinition** complex type objects (section [3.1.4.49.3.2](#)), as defined in the **ArrayOfCustomFCODefinition** complex type (section [3.1.4.49.3.1](#)).

3.1.4.49.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetRegisteredCustomFCOsSoapIn	The request WSDL message for the GetRegisteredCustomFCOs WSDL operation.
GetRegisteredCustomFCOsSoapOut	The response WSDL message for the GetRegisteredCustomFCOs WSDL operation.

3.1.4.49.1.1 GetRegisteredCustomFCOsSoapIn

The request WSDL message for the **GetRegisteredCustomFCOs** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetRegisteredCustomFCOs
```

The SOAP body contains the **GetRegisteredCustomFCOs** element.

3.1.4.49.1.2 GetRegisteredCustomFCOsSoapOut

The response WSDL message for the **GetRegisteredCustomFCOs** WSDL operation.

The SOAP body contains the **GetRegisteredCustomFCOsResponse** element.

3.1.4.49.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetRegisteredCustomFCOs	The input data for the GetRegisteredCustomFCOs WSDL operation.
GetRegisteredCustomFCOsResponse	The result data for the GetRegisteredCustomFCOs WSDL operation.

3.1.4.49.2.1 GetRegisteredCustomFCOs

The **GetRegisteredCustomFCOs** element specifies the input data for the **GetRegisteredCustomFCOs** WSDL operation.

```
<xs:element name="GetRegisteredCustomFCOs" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="type" type="tns:CustomFCOType"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

    </xs:sequence>
  </xs:complexType>
</xs:element>

```

type: Specifies the type of custom objects to be returned by the server (2). The informed type MUST be one of the following: All, **DataSource**, **Filter**, and **ReportView**, as defined in **CustomFCOType** simple type (section [3.1.4.49.4.1](#)).

3.1.4.49.2.2 GetRegisteredCustomFCOsResponse

The **GetRegisteredCustomFCOsResponse** element specifies the result data for the **GetRegisteredCustomFCOs** WSDL operation.

```

<xs:element name="GetRegisteredCustomFCOsResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetRegisteredCustomFCOsResult"
        type="tns:ArrayOfCustomFCODefinition"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetRegisteredCustomFCOsResult: Specifies a collection of **CustomFCODefinition** complex type objects (section [3.1.4.49.3.2](#)), as defined in the **ArrayOfCustomFCODefinition** complex type (section [3.1.4.49.3.1](#)). This collection MUST contain all the valid custom objects registered on the server (2) that equal the type sent from the protocol client.

3.1.4.49.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfCustomFCODefinition	Specifies an array of definitions for a custom object.
CustomFCODefinition	Specifies how instances of a custom object class are created, modified, and rendered in dashboards.

3.1.4.49.3.1 ArrayOfCustomFCODefinition

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **ArrayOfCustomFCODefinition** complex type specifies an array of definitions for a custom object.

```

<xs:complexType name="ArrayOfCustomFCODefinition"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="CustomFCODefinition"
      nillable="true" type="tns:CustomFCODefinition"/>
  </xs:sequence>

```

```
</xs:complexType>
```

CustomFCODefinition: This element MUST NOT be null and MUST conform to the schema of the **CustomFCODefinition** complex type (section [3.1.4.49.3.2](#)).

3.1.4.49.3.2 CustomFCODefinition

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **CustomFCODefinition** complex type specifies how instances of a custom object class are created, modified, and rendered in dashboards.

```
<xs:complexType name="CustomFCODefinition" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="TemplateIconSerialized" type="xs:string"/>
  </xs:sequence>
  <xs:attribute name="Type" type="tns:CustomFCOType" use="required"/>
  <xs:attribute name="SubType" type="xs:string"/>
  <xs:attribute name="Name" type="xs:string"/>
  <xs:attribute name="Description" type="xs:string"/>
  <xs:attribute name="RendererClass" type="xs:string"/>
  <xs:attribute name="EditorUri" type="xs:string"/>
</xs:complexType>
```

TemplateIconSerialized: Specifies an image that represents the custom object. The value MUST be either empty or a base64 encoding of a bitmap.

Type: The type of custom object class instance, as specified in the **CustomFCOType** simple type (section [3.1.4.49.4.1](#)). The value MUST be **DataSource**, **Filter**, or **ReportView**.

SubType: The sub-type instances of the custom object class.

- The value MUST NOT be empty.
- The value MUST NOT be longer than 60 characters.
- The value MUST NOT contain the following characters: apostrophe ('), quotation mark ("), or backslash (\).

Name: The name of the custom object class.

Description: The description of the custom object class.

RendererClass: The assembly-qualified name of a type that renders the custom object. When the **Type** attribute equals "DataSource", the value MUST be empty.

EditorUri: The URL of the associated application used to create and modify the custom object. The value MUST NOT be empty.

3.1.4.49.4 Simple Types

The following table summarizes the XML schema simple type definitions that are specific to this operation.

Simple type	Description
CustomFCOType	Specifies the type of a custom object.

3.1.4.49.4.1 CustomFCOType

Namespace: http://www.microsoft.com/performancepoint/scorecards

The **CustomFCOType** enumeration specifies the type of a custom object.

```
<xs:simpleType name="CustomFCOType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="DataSource"/>
        <xs:enumeration value="Filter"/>
        <xs:enumeration value="ReportView"/>
        <xs:enumeration value="All"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
```

The following table specifies the allowable values for the **CustomFCOType** simple type.

Value	Meaning
None	The object type is not specified.
DataSource	The object is a DataSource complex type (section 2.2.4.85).
Filter	The object is a Filter complex type (section 2.2.4.98).
ReportView	The object is a ReportView complex type (section 2.2.4.160).
All	This object is a DataSource , Filter or ReportView . This value MUST only be used when GetRegisteredCustomFCOs operation (section 3.1.4.49) is invoked.

3.1.4.49.5 Attributes

None.

3.1.4.49.6 Groups

None.

3.1.4.49.7 Attribute Groups

None.

3.1.4.50 GetReportView

The **GetReportView** operation retrieves a **ReportView** complex type (section [2.2.4.160](#)) from the server (2).

The following is the WSDL port type specification of the **GetReportView** WSDL operation.

```
<wsdl:operation name="GetReportView" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetReportViewSoapIn"/>
  <wsdl:output message="tns:GetReportViewSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetReportViewSoapIn** request message (section [3.1.4.50.1.1](#)), and the server (2) responds with a **GetReportViewSoapOut** response message (section [3.1.4.50.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the **ReportView** to be retrieved.
- The server (2) sends the corresponding **ReportView**.
- In the event that a **ReportView** cannot be retrieved, the server (2) SHOULD [<38>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.50.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetReportViewSoapIn	The request WSDL message for the GetReportView WSDL operation.
GetReportViewSoapOut	The response WSDL message for the GetReportView WSDL operation.

3.1.4.50.1.1 GetReportViewSoapIn

The request WSDL message for the **GetReportView** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetReportView
```

The SOAP body contains the **GetReportView** element.

3.1.4.50.1.2 GetReportViewSoapOut

The response WSDL message for the **GetReportView** WSDL operation.

The SOAP body contains the **GetReportViewResponse** element.

3.1.4.50.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetReportView	The input data for the GetReportView WSDL operation.
GetReportViewResponse	The result data for the GetReportView WSDL operation.

3.1.4.50.2.1 GetReportView

The **GetReportView** element specifies the input data for the **GetReportView** WSDL operation.

```
<xs:element name="GetReportView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: The **RepositoryLocation** complex type object (section [2.2.4.161](#)) that specifies the location of the **ReportView** complex type (section [2.2.4.160](#)) on the server (2).

- This element **MUST** be present.
- The **ItemUrl** property **MUST** be set to the location of the **ReportView**.

3.1.4.50.2.2 GetReportViewResponse

The **GetReportViewResponse** element specifies the result data for the **GetReportView** WSDL operation.

```
<xs:element name="GetReportViewResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetReportViewResult"
type="tns:ReportView"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetReportViewResult: The **ReportView** complex type object (section [2.2.4.160](#)) that was requested from the server (2).

3.1.4.50.3 Complex Types

None.

3.1.4.50.4 Simple Types

None.

3.1.4.50.5 Attributes

None.

3.1.4.50.6 Groups

None.

3.1.4.50.7 Attribute Groups

None.

3.1.4.51 GetScorecard

The **GetScorecard** operation retrieves a **Scorecard** complex type (section [2.2.4.162](#)).

The following is the WSDL port type specification of the **GetScorecard** WSDL operation.

```
<wsdl:operation name="GetScorecard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetScorecardSoapIn"/>
  <wsdl:output message="tns:GetScorecardSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetScorecardSoapIn** request message (section [3.1.4.51.1.1](#)), and the server (2) responds with a **GetScorecardSoapOut** response message (section [3.1.4.51.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the **Scorecard** to be retrieved.
- The server (2) responds with the corresponding **Scorecard**.
- In the event that the **Scorecard** cannot be retrieved, the server (2) SHOULD [<39>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.51.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetScorecardSoapIn	The request WSDL message for the GetScorecard WSDL operation.
GetScorecardSoapOut	The response WSDL message for the GetScorecard WSDL operation.

3.1.4.51.1.1 GetScorecardSoapIn

The request WSDL message for the **GetScorecard** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/GetScorecard
```

The SOAP body contains the **GetScorecard** element.

3.1.4.51.1.2 GetScorecardSoapOut

The response WSDL message for the **GetScorecard** WSDL operation.

The SOAP body contains the **GetScorecardResponse** element.

3.1.4.51.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetScorecard	The input data for the GetScorecard WSDL operation.
GetScorecardResponse	The result data for the GetScorecard WSDL operation.

3.1.4.51.2.1 GetScorecard

The **GetScorecard** element specifies the input data for the **GetScorecard** WSDL operation.

```
<xs:element name="GetScorecard" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

location: A **RepositoryLocation** complex type, as specified in section [2.2.4.161](#). This element MUST be present. The **ItemUrl** property MUST contain a valid URL.

3.1.4.51.2.2 GetScorecardResponse

The **GetScorecardResponse** element specifies the result data for the **GetScorecard** WSDL operation.

```
<xs:element name="GetScorecardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetScorecardResult"
        type="tns:Scorecard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetScorecardResult: A **Scorecard** complex type, as specified in section [2.2.4.162](#). This element SHOULD be present.

3.1.4.51.3 Complex Types

None.

3.1.4.51.4 Simple Types

None.

3.1.4.51.5 Attributes

None.

3.1.4.51.6 Groups

None.

3.1.4.51.7 Attribute Groups

None.

3.1.4.52 ImportDashboard

The **ImportDashboard** operation [<40>](#) is used to import content from a specified Deployment Package ([\[MS-PRIMEPF\]](#)) to the server (2).

The following is the WSDL port type specification of the **ImportDashboard** WSDL operation.

```
<wsdl:operation name="ImportDashboard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:ImportDashboardSoapIn"/>
  <wsdl:output message="tns:ImportDashboardSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **ImportDashboardSoapIn** request message (section [3.1.4.52.1.1](#)), and the server (2) responds with an **ImportDashboardSoapOut** response message (section [3.1.4.52.1.2](#)) as follows:

- The server (2) imports the items from the Deployment Package ([MS-PRIMEPF]) specified in the filename.
- If there was an application error on the server (2) during the operation, the server (2) MUST return a SOAP fault response, which SHOULD include one of exceptions specified below, but MAY contain any other exceptions.

Exceptions:

Error code	Description
InvalidUrl	An invalid URL was specified
FCOUnauthorizedAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.52.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ImportDashboardSoapIn	The request WSDL message for the ImportDashboard WSDL operation.
ImportDashboardSoapOut	The response WSDL message for the ImportDashboard WSDL operation.

3.1.4.52.1.1 ImportDashboardSoapIn

The request WSDL message for the **ImportDashboard** WSDL operation.

The SOAP action value is:

`http://www.microsoft.com/performancepoint/scorecards/ImportDashboard`

The SOAP body contains the **ImportDashboard** element.

3.1.4.52.1.2 ImportDashboardSoapOut

The response WSDL message for the **ImportDashboard** WSDL operation.

The SOAP body contains the **ImportDashboardResponse** element.

3.1.4.52.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
ImportDashboard	The input data for the ImportDashboard WSDL operation.
ImportDashboardResponse	The result data for the ImportDashboard WSDL operation.

3.1.4.52.2.1 ImportDashboard

The **ImportDashboard** element specifies the input data for the **ImportDashboard** WSDL operation.

```
<xs:element name="ImportDashboard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="siteUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="filename" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="locationMap">
        <xs:complexType mixed="true">
          <xs:sequence>
            <xs:any/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element minOccurs="0" maxOccurs="1" name="datasourceMap">
        <xs:complexType mixed="true">
          <xs:sequence>
            <xs:any/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element minOccurs="0" maxOccurs="1" name="masterPageUrl" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

siteUrl: Contains the site collection URL to use for the import. This element **MUST** be present.

filename: Contains the site collection relative path and file name of the Deployment Package ([\[MS-PRIMEPF\]](#)) to import. The path specified **MUST** be the relative path of a document library in the site collection specified in **siteUrl**. This element **MUST** be present.

locationMap: Contains a **SerializableDictionary** complex type (section [2.2.4.164](#)) containing keys of type string and values of type string where:

- **Key** contains the server-relative URL of the source list in the Deployment Package ([\[MS-PRIMEPF\]](#))
- **Value** contains the server-relative URL of the destination list

During the import, all **list items** in the Deployment Package in one of the list URLs specified in **Keys** **MUST** be imported to the corresponding new destination list URL specified in the corresponding **Value**. If the parent list URL of a list item in the Deployment Package does not have an entry specified in **Keys**, then the list item **MUST** be imported to the same destination list as specified in the Deployment Package.

This element **MUST** be present.

datasourceMap: Contains a **SerializableDictionary** containing keys of type string and values of type string where:

- **Key** contains the server-relative URL of a **DataSource** complex type (section [2.2.4.85](#)) in the Deployment Package ([MS-PRIMEPF]).
- **Value** contains the server-relative URL of an existing **DataSource** in the destination site.

During the import, all **FirstClassElement** complex types (section [2.2.4.99](#)) with references to the **DataSources** specified in **Keys** MUST be updated to use the new **DataSource** specified in the corresponding **Value**.

This element MUST be present.

masterPageUrl: Contains the site relative URL of the master page to be used by the dashboard pages in the Deployment Package ([MS-PRIMEPF]). If this element is specified, the server (2) MUST update the dashboard pages to use the given master page; otherwise, the server (2) MUST NOT change the master page during import.

3.1.4.52.2 ImportDashboardResponse

The **ImportDashboardResponse** element specifies the result data for the **ImportDashboard** WSDL operation.

```
<xs:element name="ImportDashboardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType/>  
</xs:element>
```

3.1.4.52.3 Complex Types

None.

3.1.4.52.4 Simple Types

None.

3.1.4.52.5 Attributes

None.

3.1.4.52.6 Groups

None.

3.1.4.52.7 Attribute Groups

None.

3.1.4.53 QueryChildMembers

The **QueryChildMembers** operation uses a data source for the specified member, and returns a collection of members.

The following is the WSDL port type specification of the **QueryChildMembers** WSDL operation.

```
<wsdl:operation name="QueryChildMembers" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryChildMembersSoapIn"/>
  <wsdl:output message="tns:QueryChildMembersSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryChildMembersSoapIn** request message (section [3.1.4.53.1.1](#)), and the server (2) responds with a **QueryChildMembersSoapOut** response message (section [3.1.4.53.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the data source to use for retrieving members.
- The server (2) sends the corresponding **ArrayOfMember** complex type (section [2.2.4.45](#)).

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.53.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryChildMembersSoapIn	The request WSDL message for the QueryChildMembers WSDL operation.
QueryChildMembersSoapOut	The response WSDL message for the QueryChildMembers WSDL operation.

3.1.4.53.1.1 QueryChildMembersSoapIn

The request WSDL message for the **QueryChildMembers** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryChildMembers
```

The SOAP body contains the **QueryChildMembers** element.

3.1.4.53.1.2 QueryChildMembersSoapOut

The response WSDL message for the **QueryChildMembers** WSDL operation.

The SOAP body contains the **QueryChildMembersResponse** element.

3.1.4.53.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryChildMembers	The input data for the QueryChildMembers WSDL operation.
QueryChildMembersResponse	The result data for the QueryChildMembers WSDL operation.

3.1.4.53.2.1 QueryChildMembers

The **QueryChildMembers** element specifies the input data for the **QueryChildMembers** WSDL operation.

```
<xs:element name="QueryChildMembers" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="memberUniqueName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSourceLocation: The **RepositoryLocation** complex type object (section [2.2.4.161](#)) that specifies the location of the data source for the members (3) on the server (2).

- The **RepositoryLocation** object MUST NOT be null or empty.
- The **RepositoryLocation** object MUST NOT be a fully specified URL.
- The **RepositoryLocation** object MUST be the location of the data source that allows the query of child members for a specified member name.

memberUniqueName: A value that uniquely identifies this element within the hierarchy. The value MUST be less than 255 characters and MUST NOT be null or empty.

3.1.4.53.2.2 QueryChildMembersResponse

The **QueryChildMembersResponse** element specifies the result data for the **QueryChildMembers** WSDL operation.

```
<xs:element name="QueryChildMembersResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryChildMembersResult"
type="tns:ArrayOfMember"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryChildMembersResult: This element MUST contain a collection of **Member** complex type objects (section [2.2.4.134](#)), as specified in the **ArrayOfMember** complex type (section [2.2.4.45](#)).

3.1.4.53.3 Complex Types

None.

3.1.4.53.4 Simple Types

None.

3.1.4.53.5 Attributes

None.

3.1.4.53.6 Groups

None.

3.1.4.53.7 Attribute Groups

None.

3.1.4.54 QueryChildMembersByRangeFromDataSource

The **QueryChildMembersByRangeFromDataSource** operation queries the **DataSource** complex type (section [2.2.4.85](#)), and returns a collection of child members.

The following is the WSDL port type specification of the **QueryChildMembersByRangeFromDataSource** WSDL operation.

```
<wsdl:operation name="QueryChildMembersByRangeFromDataSource"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryChildMembersByRangeFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryChildMembersByRangeFromDataSourceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryChildMembersByRangeFromDataSourceSoapIn** request message (section [3.1.4.54.1.1](#)), and the server (2) responds with a **QueryChildMembersByRangeFromDataSourceSoapOut** response message (section [3.1.4.54.1.2](#)) as follows:

- The protocol client sends a **DataSource** to use for retrieving members.
- The server (2) sends the corresponding **ArrayOfMember** complex type (section [2.2.4.45](#)).

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.54.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryChildMembersByRangeFromDataSourceSoapIn	The request WSDL message for the QueryChildMembersByRangeFromDataSource WSDL operation.
QueryChildMembersByRangeFromDataSourceSoapOut	The response WSDL message for the QueryChildMembersByRangeFromDataSource WSDL operation.

3.1.4.54.1.1 QueryChildMembersByRangeFromDataSourceSoapIn

The request WSDL message for the **QueryChildMembersByRangeFromDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryChildMembersByRangeFromDataSource
```

The SOAP body contains the **QueryChildMembersByRangeFromDataSource** element.

3.1.4.54.1.2 QueryChildMembersByRangeFromDataSourceSoapOut

The response WSDL message for the **QueryChildMembersByRangeFromDataSource** WSDL operation.

The SOAP body contains the **QueryChildMembersByRangeFromDataSourceResponse** element.

3.1.4.54.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryChildMembersByRangeFromDataSource	The input data for the QueryChildMembersByRangeFromDataSource WSDL operation.
QueryChildMembersByRangeFromDataSourceResponse	The result data for the QueryChildMembersByRangeFromDataSource WSDL operation.

3.1.4.54.2.1 QueryChildMembersByRangeFromDataSource

The **QueryChildMembersByRangeFromDataSource** element specifies the input data for the **QueryChildMembersByRangeFromDataSource** WSDL operation.

```
<xs:element name="QueryChildMembersByRangeFromDataSource"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<xs:complexType>
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    <xs:element minOccurs="0" maxOccurs="1" name="self" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="start" type="xs:long"/>
    <xs:element minOccurs="1" maxOccurs="1" name="count" type="xs:long"/>
  </xs:sequence>
</xs:complexType>
</xs:element>

```

dataSource: The **DataSource** complex type (section [2.2.4.85](#)) to be used in the query. This element MUST NOT be null or empty. The **DataSource** MUST allow the query of child members for a specified member.

self: A name identifying a member within a **DataSource**. This element MUST NOT be null or empty, or contain more than 255 characters.

start: The starting index of the records in the returned **ArrayOfMember** complex type (section [2.2.4.45](#)). The starting index MUST NOT be greater than the number of members in the requested range.

count: The number of records to be returned in the **ArrayOfMember**. The value MUST NOT be less than zero.

3.1.4.54.2.2 QueryChildMembersByRangeFromDataSourceResponse

The **QueryChildMembersByRangeFromDataSourceResponse** element specifies the result data for the **QueryChildMembersByRangeFromDataSource** WSDL operation.

```

<xs:element name="QueryChildMembersByRangeFromDataSourceResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1"
        name="QueryChildMembersByRangeFromDataSourceResult" type="tns:ArrayOfMember"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

QueryChildMembersByRangeFromDataSourceResult: This element MUST contain a collection of **Member** complex type objects (section [2.2.4.134](#)), as specified in the **ArrayOfMember** complex type (section [2.2.4.45](#)).

3.1.4.54.3 Complex Types

None.

3.1.4.54.4 Simple Types

None.

3.1.4.54.5 Attributes

None.

3.1.4.54.6 Groups

None.

3.1.4.54.7 Attribute Groups

None.

3.1.4.55 QueryChildMembersFromDataSource

The **QueryChildMembersFromDataSource** operation uses the data source to retrieve a collection of child members for the specified member name.

The following is the WSDL port type specification of the **QueryChildMembersFromDataSource** WSDL operation.

```
<wsdl:operation name="QueryChildMembersFromDataSource"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryChildMembersFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryChildMembersFromDataSourceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryChildMembersFromDataSourceSoapIn** request message (section [3.1.4.55.1.1](#)), and the server (2) responds with a **QueryChildMembersFromDataSourceSoapOut** response message (section [3.1.4.55.1.2](#)) as follows:

- The protocol client sends a **DataSource** complex type (section [2.2.4.85](#)) to use for retrieving members.
- The server (2) sends the corresponding **ArrayOfMember** complex type (section [2.2.4.45](#)).

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.55.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryChildMembersFromDataSourceSoapIn	The request WSDL message for the QueryChildMembersFromDataSource WSDL operation.
QueryChildMembersFromDataSourceSoapOut	The response WSDL message for the QueryChildMembersFromDataSource WSDL operation.

3.1.4.55.1.1 QueryChildMembersFromDataSourceSoapIn

The request WSDL message for the **QueryChildMembersFromDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryChildMembersFromDataSource
```

The SOAP body contains the **QueryChildMembersFromDataSource** element.

3.1.4.55.1.2 QueryChildMembersFromDataSourceSoapOut

The response WSDL message for the **QueryChildMembersFromDataSource** WSDL operation.

The SOAP body contains the **QueryChildMembersFromDataSourceResponse** element.

3.1.4.55.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryChildMembersFromDataSource	The input data for the QueryChildMembersFromDataSource WSDL operation.
QueryChildMembersFromDataSourceResponse	The result data for the QueryChildMembersFromDataSource WSDL operation.

3.1.4.55.2.1 QueryChildMembersFromDataSource

The **QueryChildMembersFromDataSource** element specifies the input data for the **QueryChildMembersFromDataSource** WSDL operation.

```
<xs:element name="QueryChildMembersFromDataSource"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
      <xs:element minOccurs="0" maxOccurs="1" name="memberUniqueName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: The **DataSource** complex type (section [2.2.4.85](#)) to be used in the query. This element MUST NOT be null or empty. The **DataSource** MUST support the query of child members for a specified member.

memberUniqueName: A value that uniquely identifies this element within the hierarchy. This value MUST NOT be null or empty, and MUST be less than 255 characters.

3.1.4.55.2.2 QueryChildMembersFromDataSourceResponse

The **QueryChildMembersFromDataSourceResponse** element specifies the result data for the **QueryChildMembersFromDataSource** WSDL operation.

```
<xs:element name="QueryChildMembersFromDataSourceResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryChildMembersFromDataSourceResult"
        type="tns:ArrayOfMember"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryChildMembersFromDataSourceResult: This element MUST contain a collection of **Member** complex type objects (section [2.2.4.134](#)), as specified in the **ArrayOfMember** complex type (section [2.2.4.45](#)).

3.1.4.55.3 Complex Types

None.

3.1.4.55.4 Simple Types

None.

3.1.4.55.5 Attributes

None.

3.1.4.55.6 Groups

None.

3.1.4.55.7 Attribute Groups

None.

3.1.4.56 QueryDimensionRootMembers

The **QueryDimensionRootMembers** operation uses a data source (1) from the repository location for the specified member, and returns a collection of root members.

The following is the WSDL port type specification of the **QueryDimensionRootMembers** WSDL operation.

```
<wsdl:operation name="QueryDimensionRootMembers"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryDimensionRootMembersSoapIn"/>
  <wsdl:output message="tns:QueryDimensionRootMembersSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryDimensionRootMembersSoapIn** request message (section [3.1.4.56.1.1](#)), and the server (2) responds with a **QueryDimensionRootMembersSoapOut** response message (section [3.1.4.56.1.2](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the data source to use for retrieving members.
- The server (2) sends the corresponding **ArrayOfMember** complex type (section [2.2.4.45](#)).

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.56.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryDimensionRootMembersSoapIn	The request WSDL message for the QueryDimensionRootMembers WSDL operation.
QueryDimensionRootMembersSoapOut	The response WSDL message for the QueryDimensionRootMembers WSDL operation.

3.1.4.56.1.1 QueryDimensionRootMembersSoapIn

The request WSDL message for the **QueryDimensionRootMembers** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryDimensionRootMembers
```

The SOAP body contains the **QueryDimensionRootMembers** element.

3.1.4.56.1.2 QueryDimensionRootMembersSoapOut

The response WSDL message for the **QueryDimensionRootMembers** WSDL operation.

The SOAP body contains the **QueryDimensionRootMembersResponse** element.

3.1.4.56.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryDimensionRootMembers	The input data for the QueryDimensionRootMembers WSDL operation.
QueryDimensionRootMembersResponse	The result data for the QueryDimensionRootMembers WSDL operation.

3.1.4.56.2.1 QueryDimensionRootMembers

The **QueryDimensionRootMembers** element specifies the input data for the **QueryDimensionRootMembers** WSDL operation.

```
<xs:element name="QueryDimensionRootMembers" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="dimensionName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSourceLocation: The **RepositoryLocation** complex type (section [2.2.4.161](#)) that specifies the location of the data source for the members (3) on the server (2).

- The **RepositoryLocation** object MUST NOT be null or empty.
- The **RepositoryLocation** object MUST NOT be a fully specified URL.
- The **RepositoryLocation** object MUST be the location of the data source that allows the query of root members for a specified member name.

dimensionName: A value that uniquely identifies this dimension (1). The value MUST be less than 255 characters and MUST NOT be null or empty.

3.1.4.56.2.2 QueryDimensionRootMembersResponse

The **QueryDimensionRootMembersResponse** element specifies the result data for the **QueryDimensionRootMembers** WSDL operation.

```
<xs:element name="QueryDimensionRootMembersResponse"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryDimensionRootMembersResult"
type="tns:ArrayOfMember"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryDimensionRootMembersResult: This element MUST contain a collection of **Member** complex type objects (section [2.2.4.134](#)), as specified in the **ArrayOfMember** complex type (section [2.2.4.45](#)).

3.1.4.56.3 Complex Types

None.

3.1.4.56.4 Simple Types

None.

3.1.4.56.5 Attributes

None.

3.1.4.56.6 Groups

None.

3.1.4.56.7 Attribute Groups

None.

3.1.4.57 QueryDimensionRootMembersFromDataSource

The **QueryDimensionRootMembersFromDataSource** method uses the data source to retrieve a collection of root members for the specified member name.

The following is the WSDL port type specification of the **QueryDimensionRootMembersFromDataSource** WSDL operation.

```
<wsdl:operation name="QueryDimensionRootMembersFromDataSource"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryDimensionRootMembersFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryDimensionRootMembersFromDataSourceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryDimensionRootMembersFromDataSourceSoapIn** request message (section [3.1.4.57.1.1](#)), and the server (2) responds with a **QueryDimensionRootMembersFromDataSourceSoapOut** response message (section [3.1.4.57.1.2](#)) as follows:

- The protocol client sends a **DataSource** complex type (section [2.2.4.85](#)) to use for retrieving members.
- The server (2) sends the corresponding **ArrayOfMember** complex type (section [2.2.4.45](#)).

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.57.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryDimensionRootMembersFromDataSourceSoapIn	The request WSDL message for the QueryDimensionRootMembersFromDataSource WSDL operation.
QueryDimensionRootMembersFromDataSourceSoapOut	The response WSDL message for the QueryDimensionRootMembersFromDataSource WSDL operation.

3.1.4.57.1.1 QueryDimensionRootMembersFromDataSourceSoapIn

The request WSDL message for the **QueryDimensionRootMembersFromDataSource** WSDL operation.

The SOAP action value is:

`http://www.microsoft.com/performancepoint/scorecards/QueryDimensionRootMembersFromDataSource`

The SOAP body contains the **QueryDimensionRootMembersFromDataSource** element.

3.1.4.57.1.2 QueryDimensionRootMembersFromDataSourceSoapOut

The response WSDL message for the **QueryDimensionRootMembersFromDataSource** WSDL operation.

The SOAP body contains the **QueryDimensionRootMembersFromDataSourceResponse** element.

3.1.4.57.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryDimensionRootMembersFromDataSource	The input data for the QueryDimensionRootMembersFromDataSource WSDL operation.
QueryDimensionRootMembersFromDataSourceResponse	The result data for the QueryDimensionRootMembersFromDataSource WSDL operation.

3.1.4.57.2.1 QueryDimensionRootMembersFromDataSource

The **QueryDimensionRootMembersFromDataSource** element specifies the input data for the **QueryDimensionRootMembersFromDataSource** WSDL operation.

```

<xs:element name="QueryDimensionRootMembersFromDataSource"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
      <xs:element minOccurs="0" maxOccurs="1" name="dimensionName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

dataSource: The **DataSource** complex type (section [2.2.4.85](#)) to be used in the query. This element MUST NOT be null or empty. The **DataSource** MUST support the query of root members for a specified dimension (1).

dimensionName: A value that uniquely identifies this dimension (1). This value MUST NOT be null or empty and MUST be less than 255 characters.

3.1.4.57.2.2 QueryDimensionRootMembersFromDataSourceResponse

The **QueryDimensionRootMembersFromDataSourceResponse** element specifies the result data for the **QueryDimensionRootMembersFromDataSource** WSDL operation.

```

<xs:element name="QueryDimensionRootMembersFromDataSourceResponse"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1"
name="QueryDimensionRootMembersFromDataSourceResult" type="tns:ArrayOfMember"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

QueryDimensionRootMembersFromDataSourceResult: This element MUST contain a collection of **Member** complex type objects (section [2.2.4.134](#)), as specified in the **ArrayOfMember** complex type (section [2.2.4.45](#)).

3.1.4.57.3 Complex Types

None.

3.1.4.57.4 Simple Types

None.

3.1.4.57.5 Attributes

None.

3.1.4.57.6 Groups

None.

3.1.4.57.7 Attribute Groups

None.

3.1.4.58 QueryNamedSets

The **QueryNamedSets** operation is used to retrieve the named sets that are defined by a data source (1) when given the **RepositoryLocation** complex type (section [2.2.4.161](#)) of the data source (1).

The following is the WSDL port type specification of the **QueryNamedSets** WSDL operation.

```
<wsdl:operation name="QueryNamedSets" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryNamedSetsSoapIn"/>
  <wsdl:output message="tns:QueryNamedSetsSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryNamedSetsSoapIn** request message (section [3.1.4.58.1.1](#)), and the server (2) responds with a **QueryNamedSetsSoapOut** response message (section [3.1.4.58.1.2](#)) as follows:

- Receives a **RepositoryLocation** for the data source (1) to be queried for named sets.
- The server (2) queries the corresponding data source (1).
- The server (2) responds with the result.
- In the event that a data source (1) cannot be retrieved for the query, the server (2) SHOULD [<41>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.58.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryNamedSetsSoapIn	The request WSDL message for the QueryNamedSets WSDL operation.
QueryNamedSetsSoapOut	The response WSDL message for the QueryNamedSets WSDL operation.

3.1.4.58.1.1 QueryNamedSetsSoapIn

The request WSDL message for the **QueryNamedSets** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryNamedSets
```

The SOAP body contains the **QueryNamedSets** element.

3.1.4.58.1.2 QueryNamedSetsSoapOut

The response WSDL message for the **QueryNamedSets** WSDL operation.

The SOAP body contains the **QueryNamedSetsResponse** element.

3.1.4.58.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryNamedSets	The input data for the QueryNamedSets WSDL operation.
QueryNamedSetsResponse	The result data for the QueryNamedSets WSDL operation.

3.1.4.58.2.1 QueryNamedSets

The **QueryNamedSets** element specifies the input data for the **QueryNamedSets** WSDL operation.

```
<xs:element name="QueryNamedSets" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSourceLocation: The location (as specified in the complex type **RepositoryLocation** section [2.2.4.161](#)) for the data source (1) being queried for named sets. This element **MUST** be present. It **MUST** be a **RepositoryLocation** to a data source (1).

3.1.4.58.2.2 QueryNamedSetsResponse

The **QueryNamedSetsResponse** element specifies the result data for the **QueryNamedSets** WSDL operation.

```
<xs:element name="QueryNamedSetsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
```

```

    <xs:element minOccurs="0" maxOccurs="1" name="QueryNamedSetsResult"
type="tns:ArrayOfNamedSet"/>
  </xs:sequence>
</xs:complexType>
</xs:element>

```

QueryNamedSetsResult: This element MUST be either a collection of **NamedSet** complex type objects (section [2.2.4.147](#)), specified in the **ArrayOfNamedSet** complex type (section [2.2.4.47](#)), or null, if there are no named sets defined for the data source (1).

3.1.4.58.3 Complex Types

None.

3.1.4.58.4 Simple Types

None.

3.1.4.58.5 Attributes

None.

3.1.4.58.6 Groups

None.

3.1.4.58.7 Attribute Groups

None.

3.1.4.59 QueryNamedSetsFromDataSource

The **QueryNamedSetsFromDataSource** operation is used to retrieve the named sets that are defined by the given data source (1).

The following is the WSDL port type specification of the **QueryNamedSetsFromDataSource** WSDL operation.

```

<wsdl:operation name="QueryNamedSetsFromDataSource"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryNamedSetsFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryNamedSetsFromDataSourceSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **QueryNamedSetsFromDataSourceSoapIn** request message (section [3.1.4.59.1.1](#)), and the server (2) responds with a **QueryNamedSetsFromDataSourceSoapOut** response message (section [3.1.4.59.1.2](#)) as follows:

- Receives a **DataSource** complex type (section [2.2.4.85](#)) to be queried for named sets.
- The server (2) queries the received data source (1).
- The server (2) responds with the result.

- In the event that a data source (1) cannot be retrieved for obtaining the named sets, the server (2) SHOULD [return a SOAP fault response](#), as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.59.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryNamedSetsFromDataSourceSoapIn	The request WSDL message for the QueryNamedSetsFromDataSource WSDL operation.
QueryNamedSetsFromDataSourceSoapOut	The response WSDL message for the QueryNamedSetsFromDataSource WSDL operation.

3.1.4.59.1.1 QueryNamedSetsFromDataSourceSoapIn

The request WSDL message for the **QueryNamedSetsFromDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryNamedSetsFromDataSource
```

The SOAP body contains the **QueryNamedSetsFromDataSource** element.

3.1.4.59.1.2 QueryNamedSetsFromDataSourceSoapOut

The response WSDL message for the **QueryNamedSetsFromDataSource** WSDL operation.

The SOAP body contains the **QueryNamedSetsFromDataSourceResponse** element.

3.1.4.59.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryNamedSetsFromDataSource	The input data for the QueryNamedSetsFromDataSource WSDL operation.
QueryNamedSetsFromDataSourceResponse	The result data for the QueryNamedSetsFromDataSource WSDL operation.

3.1.4.59.2.1 QueryNamedSetsFromDataSource

The **QueryNamedSetsFromDataSource** element specifies the input data for the **QueryNamedSetsFromDataSource** WSDL operation.

```
<xs:element name="QueryNamedSetsFromDataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: The data source (1) to be queried for named sets, as specified in the **DataSource** complex type (section [2.2.4.85](#)). This element MUST be present.

3.1.4.59.2.2 QueryNamedSetsFromDataSourceResponse

The **QueryNamedSetsFromDataSourceResponse** element specifies the result data for the **QueryNamedSetsFromDataSource** WSDL operation.

```
<xs:element name="QueryNamedSetsFromDataSourceResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryNamedSetsFromDataSourceResult"
        type="tns:ArrayOfNamedSet"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryNamedSetsFromDataSourceResult: This element MUST be either a collection of **NamedSet** complex type objects (section [2.2.4.147](#)), specified in the **ArrayOfNamedSet** complex type (section [2.2.4.47](#)), or null, if there are no named sets defined for the data source (1).

3.1.4.59.3 Complex Types

None.

3.1.4.59.4 Simple Types

None.

3.1.4.59.5 Attributes

None.

3.1.4.59.6 Groups

None.

3.1.4.59.7 Attribute Groups

None.

3.1.4.60 QueryRelatedMember

The **QueryRelatedMember** operation is used to retrieve a member (3) having the specified relationship to the specified member from the data source (1) at the given **RepositoryLocation** complex type (section [2.2.4.161](#)).

The following is the WSDL port type specification of the **QueryRelatedMember** WSDL operation.

```
<wsdl:operation name="QueryRelatedMember" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryRelatedMemberSoapIn"/>
  <wsdl:output message="tns:QueryRelatedMemberSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryRelatedMemberSoapIn** request message (section [3.1.4.60.1.1](#)), and the server (2) responds with a **QueryRelatedMemberSoapOut** response message (section [3.1.4.60.1.2](#)) as follows:

- Receives a **RepositoryLocation** for the data source (1) to be queried for a related member (3) along with the unique member (3) name and the **MemberRelationship** simple type (section [2.2.5.36](#)) being queried for.
- The server (2) queries the corresponding data source (1) for the related member (3).
- The server (2) responds with the result.
- In the event that a data source (1) cannot be retrieved from the **RepositoryLocation**, the server (2) SHOULD [<43>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.60.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryRelatedMemberSoapIn	The request WSDL message for the QueryRelatedMember WSDL operation.
QueryRelatedMemberSoapOut	The response WSDL message for the QueryRelatedMember WSDL operation.

3.1.4.60.1.1 QueryRelatedMemberSoapIn

The request WSDL message for the **QueryRelatedMember** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryRelatedMember
```

The SOAP body contains the **QueryRelatedMember** element.

3.1.4.60.1.2 QueryRelatedMemberSoapOut

The response WSDL message for the **QueryRelatedMember** WSDL operation.

The SOAP body contains the **QueryRelatedMemberResponse** element.

3.1.4.60.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryRelatedMember	The input data for the QueryRelatedMember WSDL operation.
QueryRelatedMemberResponse	The result data for the QueryRelatedMember WSDL operation.

3.1.4.60.2.1 QueryRelatedMember

The **QueryRelatedMember** element specifies the input data for the **QueryRelatedMember** WSDL operation.

```
<xs:element name="QueryRelatedMember" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="memberUniqueName" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="relationship"
type="tns:MemberRelationship"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSourceLocation: The location (as specified in the complex type **RepositoryLocation** complex type section [2.2.4.161](#)) for the data source (1) being queried for a related member (3). This element **MUST** be present. It **MUST** be a **RepositoryLocation** to a data source (1).

memberUniqueName: A value that uniquely identifies this element within the data source (1).

relationship: The relationship, as specified in the simple type **MemberRelationship** (section [2.2.5.36](#)), between **memberUniqueName** and the result.

3.1.4.60.2.2 QueryRelatedMemberResponse

The **QueryRelatedMemberResponse** element specifies the result data for the **QueryRelatedMember** WSDL operation.

```
<xs:element name="QueryRelatedMemberResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryRelatedMemberResult"
        type="tns:Member"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryRelatedMemberResult: This element **MUST** be either the related member (3) as specified in the **Member** complex type (section [2.2.4.134](#)), or null, if there are no related members (3), or if the **MemberRelationship** simple type (section [2.2.5.36](#)) is "Children".

3.1.4.60.3 Complex Types

None.

3.1.4.60.4 Simple Types

None.

3.1.4.60.5 Attributes

None.

3.1.4.60.6 Groups

None.

3.1.4.60.7 Attribute Groups

None.

3.1.4.61 QueryRelatedMemberFromDataSource

The **QueryRelatedMemberFromDataSource** operation queries the given data source (1) for the member (3) having the specified relationship to the specified member.

The following is the WSDL port type specification of the **QueryRelatedMemberFromDataSource** WSDL operation.

```

<wsdl:operation name="QueryRelatedMemberFromDataSource"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryRelatedMemberFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryRelatedMemberFromDataSourceSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **QueryRelatedMemberFromDataSourceSoapIn** request message (section [3.1.4.61.1.1](#)) and the server (2) responds with a **QueryRelatedMemberFromDataSourceSoapOut** response message (section [3.1.4.61.1.2](#)) as follows:

- Receives a **DataSource** complex type (section [2.2.4.85](#)) to be queried for the related member (3) along with the unique member (3) name and the **MemberRelationship** simple type (section [2.2.5.36](#)) being queried for.
- The server (2) queries the corresponding data source (1) for the related member (3).
- The server (2) responds with the result.
- In the event that a data source (1) cannot be retrieved for the query, the server (2) SHOULD [<44>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.61.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryRelatedMemberFromDataSourceSoapIn	The request WSDL message for the QueryRelatedMemberFromDataSource WSDL operation.
QueryRelatedMemberFromDataSourceSoapOut	The response WSDL message for the QueryRelatedMemberFromDataSource WSDL operation.

3.1.4.61.1.1 QueryRelatedMemberFromDataSourceSoapIn

The request WSDL message for the **QueryRelatedMemberFromDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryRelatedMemberFromDataSource
```

The SOAP body contains the **QueryRelatedMemberFromDataSource** element.

3.1.4.61.1.2 QueryRelatedMemberFromDataSourceSoapOut

The response WSDL message for the **QueryRelatedMemberFromDataSource** WSDL operation.

The SOAP body contains the **QueryRelatedMemberFromDataSourceResponse** element.

3.1.4.61.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryRelatedMemberFromDataSource	The input data for the QueryRelatedMemberFromDataSource WSDL operation.
QueryRelatedMemberFromDataSourceResponse	The result data for the QueryRelatedMemberFromDataSource WSDL operation.

3.1.4.61.2.1 QueryRelatedMemberFromDataSource

The **QueryRelatedMemberFromDataSource** element specifies the input data for the **QueryRelatedMemberFromDataSource** WSDL operation.

```
<xs:element name="QueryRelatedMemberFromDataSource"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
      <xs:element minOccurs="0" maxOccurs="1" name="memberUniqueName" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="relationship"
        type="tns:MemberRelationship"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: The data source (1) to be queried for a related member, as specified in the **DataSource** complex type (section [2.2.4.85](#)). This element **MUST** be present.

memberUniqueName: A value that uniquely identifies this element within the data source (1).

relationship: The relationship, as specified in the **MemberRelationship** simple type (section [2.2.5.36](#)), between **memberUniqueName** and the result.

3.1.4.61.2.2 QueryRelatedMemberFromDataSourceResponse

The **QueryRelatedMemberFromDataSourceResponse** element specifies the result data for the **QueryRelatedMemberFromDataSource** WSDL operation.

```
<xs:element name="QueryRelatedMemberFromDataSourceResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryRelatedMemberFromDataSourceResult"
        type="tns:Member"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryRelatedMemberFromDataSourceResult: This element MUST be either the related member (3) as specified in the **Member** complex type (section [2.2.4.134](#)), or null, if there are no related members (3).

3.1.4.61.3 Complex Types

None.

3.1.4.61.4 Simple Types

None.

3.1.4.61.5 Attributes

None.

3.1.4.61.6 Groups

None.

3.1.4.61.7 Attribute Groups

None.

3.1.4.62 QueryTimeIntelligence

The **QueryTimeIntelligence** operation queries a data source (1) location for the members (3) that are specified by a time intelligence formula.

The following is the WSDL port type specification of the **QueryTimeIntelligence** WSDL operation.

```
<wsdl:operation name="QueryTimeIntelligence" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryTimeIntelligenceSoapIn"/>
  <wsdl:output message="tns:QueryTimeIntelligenceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryTimeIntelligenceSoapIn** request message (section [3.1.4.62.1.1](#)), and the server (2) responds with a **QueryTimeIntelligenceSoapOut** response message (section [3.1.4.62.1.2](#)) as follows:

- Receives **RepositoryLocation** complex type (section [2.2.4.161](#)) for the data source (1) to be queried for time intelligence, along with the current time and date and a formula.
- The server (2) queries the corresponding data source (1) using the current time and date and formula for the related member (3).
- The server (2) responds with the result.
- In the event that a data source (1) cannot be retrieved from the **RepositoryLocation**, the server (2) SHOULD [<45>](#) return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
TimeIntelligenceNotConfigured	The data source (1) has an invalid time intelligence configuration or time intelligence is not configured.
InvalidTimeIntelligenceFormula	The time intelligence formula is invalid
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.62.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryTimeIntelligenceSoapIn	The request WSDL message for the QueryTimeIntelligence WSDL operation.
QueryTimeIntelligenceSoapOut	The response WSDL message for the QueryTimeIntelligence WSDL operation.

3.1.4.62.1.1 QueryTimeIntelligenceSoapIn

The request WSDL message for the **QueryTimeIntelligence** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryTimeIntelligence
```

The SOAP body contains the **QueryTimeIntelligence** element.

3.1.4.62.1.2 QueryTimeIntelligenceSoapOut

The response WSDL message for the **QueryTimeIntelligence** WSDL operation.

The SOAP body contains the **QueryTimeIntelligenceResponse** element.

3.1.4.62.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryTimeIntelligence	The input data for the QueryTimeIntelligence WSDL operation.
QueryTimeIntelligenceResponse	The result data for the QueryTimeIntelligence WSDL operation.

3.1.4.62.2.1 QueryTimeIntelligence

The **QueryTimeIntelligence** element specifies the input data for the **QueryTimeIntelligence** WSDL operation.

```
<xs:element name="QueryTimeIntelligence" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="1" maxOccurs="1" name="currentTime" type="xs:dateTime"/>
      <xs:element minOccurs="0" maxOccurs="1" name="formula" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSourceLocation: The location (for specification see the **RepositoryLocation** complex type section [2.2.4.161](#)) for the data source (1) being queried for time intelligence. This element **MUST** be present. It **MUST** be a **RepositoryLocation** to a data source.

currentTime: The current time and date. This element **MUST** be present, and its value **MUST** be a valid **dateTime**.

formula: The STPS formula, as described in [\[MSFT-TimeIntelligence\]](#). This element **MUST** be present, and its value **MUST** be a STPS formula for the data source.

3.1.4.62.2.2 QueryTimeIntelligenceResponse

The **QueryTimeIntelligenceResponse** element specifies the result data for the **QueryTimeIntelligence** WSDL operation.

```
<xs:element name="QueryTimeIntelligenceResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryTimeIntelligenceResult"
type="tns:ArrayOfMember"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```


QueryTimeIntelligenceResult: This element MUST contain a collection of **Member** complex type objects (section [2.2.4.134](#)), as specified in the **ArrayOfMember** complex type (section [2.2.4.45](#)). If there are no **Members** returned from the specified formula, **ArrayOfMember** MUST contain a single **Member** where the **Member's Expression** attribute MUST be set to "NULL".

3.1.4.62.3 Complex Types

None.

3.1.4.62.4 Simple Types

None.

3.1.4.62.5 Attributes

None.

3.1.4.62.6 Groups

None.

3.1.4.62.7 Attribute Groups

None.

3.1.4.63 QueryTimeIntelligenceDirect

The **QueryTimeIntelligenceDirect** operation queries the provided data source (1) for the members (3) that are specified by a time intelligence formula.

The following is the WSDL port type specification of the **QueryTimeIntelligenceDirect** WSDL operation.

```
<wsdl:operation name="QueryTimeIntelligenceDirect"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryTimeIntelligenceDirectSoapIn"/>
  <wsdl:output message="tns:QueryTimeIntelligenceDirectSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryTimeIntelligenceDirectSoapIn** request message (section [3.1.4.64.1.1](#)), and the server (2) responds with a **QueryTimeIntelligenceDirectSoapOut** response message (section [3.1.4.64.1.2](#)) as follows:

- Receives a **DataSource** complex type (section [2.2.4.85](#)) to be queried for the time intelligence, along with the current time and date and a formula.
- The server (2) queries the corresponding data source (1) using the current time and date and formula for the related member (3).
- The server (2) responds with the result.
- In the event that a data source (1) cannot be retrieved for the query, the server (2) SHOULD return a SOAP fault response, as detailed in section [2.2.2.1](#).

Exceptions:

Error code	Description
FCOReadFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOReadFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
TimeIntelligenceNotConfigured	The data source (1) has an invalid time intelligence configuration or time intelligence is not configured.
InvalidTimeIntelligenceFormula	The time intelligence formula is invalid.
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.63.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryTimeIntelligenceDirectSoapIn	The request WSDL message for the QueryTimeIntelligenceDirect WSDL operation.
QueryTimeIntelligenceDirectSoapOut	The response WSDL message for the QueryTimeIntelligenceDirect WSDL operation.

3.1.4.63.1.1 QueryTimeIntelligenceDirectSoapIn

The request WSDL message for the **QueryTimeIntelligenceDirect** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryTimeIntelligenceDirect
```

The SOAP body contains the **QueryTimeIntelligenceDirect** element.

3.1.4.63.1.2 QueryTimeIntelligenceDirectSoapOut

The response WSDL message for the **QueryTimeIntelligenceDirect** WSDL operation.

The SOAP body contains the **QueryTimeIntelligenceDirectResponse** element.

3.1.4.63.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryTimeIntelligenceDirect	The input data for the QueryTimeIntelligenceDirect WSDL

Element	Description
	operation.
QueryTimeIntelligenceDirectResponse	The result data for the QueryTimeIntelligenceDirect WSDL operation.

3.1.4.63.2.1 QueryTimeIntelligenceDirect

The **QueryTimeIntelligenceDirect** element specifies the input data for the **QueryTimeIntelligenceDirect** WSDL operation.

```
<xs:element name="QueryTimeIntelligenceDirect" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
      <xs:element minOccurs="1" maxOccurs="1" name="currentTime" type="xs:dateTime"/>
      <xs:element minOccurs="0" maxOccurs="1" name="formula" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: The data source (1) to be queried for time intelligence members. See the **DataSource** complex type (section [2.2.4.85](#)) for specification. This element **MUST** be present.

currentTime: The current time and date. This element **MUST** be present, and its value **MUST** be a valid **dateTime**.

formula: The STPS formula. This element **MUST** be present, and its value **MUST** be a STPS formula for the data source.

3.1.4.63.2.2 QueryTimeIntelligenceDirectResponse

The **QueryTimeIntelligenceDirectResponse** element specifies the result data for the **QueryTimeIntelligenceDirect** WSDL operation.

```
<xs:element name="QueryTimeIntelligenceDirectResponse"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryTimeIntelligenceDirectResult"
type="tns:ArrayOfMember"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryTimeIntelligenceDirectResult: This element **MUST** contain a collection of **Member** complex type objects (section [2.2.4.134](#)), as specified in the **ArrayOfMember** complex type (section [2.2.4.45](#)). If there are no **Members** returned from the specified formula, **ArrayOfMember** **MUST** contain a single **Member** where the **Member's Expression** attribute **MUST** be set to "NULL".

3.1.4.63.3 Complex Types

None.

3.1.4.63.4 Simple Types

None.

3.1.4.63.5 Attributes

None.

3.1.4.63.6 Groups

None.

3.1.4.63.7 Attribute Groups

None.

3.1.4.64 QueryTransformMembers

The **QueryTransformMembers** method transforms any collection of **Member** complex types (section [2.2.4.134](#)) into a new member collection based on the operation passed on the **transformType** parameter of the **QueryTransformMembers** element (section [3.1.4.64.2.1](#)) as specified in section [3.1.4.64.4.1](#).

The following is the WSDL port type specification of the **QueryTransformMembers** WSDL operation.

```
<wsdl:operation name="QueryTransformMembers" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:QueryTransformMembersSoapIn"/>
  <wsdl:output message="tns:QueryTransformMembersSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **QueryTransformMembersSoapIn** request message (section [3.1.4.64.1.1](#)), and the server (2) responds with a **QueryTransformMembersSoapOut** response message (section [3.1.4.64.1.1](#)) as follows:

- The protocol client sends a **RepositoryLocation** complex type (section [2.2.4.161](#)) for the data source to use for retrieving members.
- The server (2) sends a corresponding **ArrayOfMember** complex type (see section [2.2.4.45](#)).

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.64.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
QueryTransformMembersSoapIn	The request WSDL message for the QueryTransformMembers WSDL operation.
QueryTransformMembersSoapOut	The response WSDL message for the QueryTransformMembers WSDL operation.

3.1.4.64.1.1 QueryTransformMembersSoapIn

The request WSDL message for the **QueryTransformMembers** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/QueryTransformMembers
```

The SOAP body contains the **QueryTransformMembers** element.

3.1.4.64.1.2 QueryTransformMembersSoapOut

The response WSDL message for the **QueryTransformMembers** WSDL operation.

The SOAP body contains the **QueryTransformMembersResponse** element.

3.1.4.64.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
QueryTransformMembers	The input data for the QueryTransformMembers WSDL operation.
QueryTransformMembersResponse	The result data for the QueryTransformMembers WSDL operation.

3.1.4.64.2.1 QueryTransformMembers

The **QueryTransformMembers** element specifies the input data for the **QueryTransformMembers** WSDL operation.

```
<xs:element name="QueryTransformMembers" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="memberCollection"
type="tns:ArrayOfMember"/>
      <xs:element minOccurs="1" maxOccurs="1" name="transformType"
type="tns:QueryTransformMembersType"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSourceLocation: A **RepositoryLocation** complex type object (section [2.2.4.161](#)) that specifies the location of data source for the members (3) on the server (2).

- The **RepositoryLocation** object MUST NOT be null or empty.
- The **RepositoryLocation** object MUST NOT be a fully specified URL.
- The **RepositoryLocation** object MUST be the location of the data source that allows the query of child members for a specified member name.

memberCollection: A collection of **Member** complex types (section [2.2.4.134](#)) that will be transformed based on the type of transformation specified in the **transformType** parameter.

transformType: Type of operation specified in the **QueryTransformMembersType** simple type (section [3.1.4.64.4.1](#)) that will be applied to the member collection.

3.1.4.64.2.2 QueryTransformMembersResponse

The **QueryTransformMembersResponse** element specifies the result data for the **QueryTransformMembers** WSDL operation.

```
<xs:element name="QueryTransformMembersResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryTransformMembersResult"
type="tns:ArrayOfMember"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

QueryTransformMembersResult: This element MUST contain a collection of **Member** complex type objects (section [2.2.4.134](#)), as specified in the **ArrayOfMember** complex type (section [2.2.4.45](#)).

3.1.4.64.3 Complex Types

None.

3.1.4.64.4 Simple Types

The following table summarizes the XML schema simple type definitions that are specific to this operation.

Simple type	Description
QueryTransformMembersType	Specifies the transformation type that will be applied to the collection of member.

3.1.4.64.4.1 QueryTransformMembersType

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

Specifies the transformation type that will be applied to the collection of **Member** complex types (section [2.2.4.134](#)).

```

<xs:simpleType name="QueryTransformMembersType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Hierarchize"/>
    <xs:enumeration value="Parents"/>
    <xs:enumeration value="Ancestors"/>
    <xs:enumeration value="AscendantsIntersect"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **QueryTransformMembersType** simple type.

Value	Meaning
Hierarchize	Returns the hierarchized representation of the member set.
Parents	Returns the parent of each member on the set. This operation type is reserved and MUST NOT be called.
Ancestors	Returns the ancestor of each member on the set. This operation type is reserved and MUST NOT be called.
AscendantsIntersect	Returns the original set plus any direct ancestor contained in the set.

3.1.4.64.5 Attributes

None.

3.1.4.64.6 Groups

None.

3.1.4.64.7 Attribute Groups

None.

3.1.4.65 SaveTemporaryAnalyticReport

The **SaveTemporaryAnalyticReport** operation stores a temporary copy of a **ReportView** complex type (section [2.2.4.160](#)) to the server (2).

The following is the WSDL port type specification of the **SaveTemporaryAnalyticReport** WSDL operation.

```

<wsdl:operation name="SaveTemporaryAnalyticReport"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:SaveTemporaryAnalyticReportSoapIn"/>
  <wsdl:output message="tns:SaveTemporaryAnalyticReportSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **SaveTemporaryAnalyticReportSoapIn** request message (section [3.1.4.65.1.1](#)), and the server (2) responds with a **SaveTemporaryAnalyticReportSoapOut** response message (section [3.1.4.65.1.2](#)) as follows:

- The protocol client MUST send a **ReportView**.

- If the server (2) contains a **ReportView** where all attributes and elements except **Location** equal those of the passed in **ReportView**, the server (2) MUST return the GUID of the **ReportView** on the server (2). The GUID MUST be equal to the **RepositoryLocation** complex type's (section [2.2.4.161](#)) **ItemGuid** GUID. The stored **ReportView** MUST NOT be altered.
- If the server (2) does not contain a **ReportView** where all attributes and elements except **Location** equal those of the passed in **ReportView**, the server (2) MUST store a copy of the **ReportView** and MUST return a unique GUID for it. The server (2) MUST replace the **Location** element for the stored copy which MUST conform to the schema of the **RepositoryLocation**, such that the **ItemType** attribute equals **TempReportView**, as specified in the **FirstClassObjectType** simple type (section [2.2.5.20](#)), and the **ItemGuid** attribute equals the returned GUID.

Exceptions:

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.65.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
SaveTemporaryAnalyticReportSoapIn	The request WSDL message for the SaveTemporaryAnalyticReport WSDL operation.
SaveTemporaryAnalyticReportSoapOut	The response WSDL message for the SaveTemporaryAnalyticReport WSDL operation.

3.1.4.65.1.1 SaveTemporaryAnalyticReportSoapIn

The request WSDL message for the **SaveTemporaryAnalyticReport** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/SaveTemporaryAnalyticReport
```

The SOAP body contains the **SaveTemporaryAnalyticReport** element.

3.1.4.65.1.2 SaveTemporaryAnalyticReportSoapOut

The response WSDL message for the **SaveTemporaryAnalyticReport** WSDL operation.

The SOAP body contains the **SaveTemporaryAnalyticReportResponse** element.

3.1.4.65.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
SaveTemporaryAnalyticReport	The input data for the SaveTemporaryAnalyticReport WSDL operation.
SaveTemporaryAnalyticReportResponse	The result data for the SaveTemporaryAnalyticReport WSDL operation.

3.1.4.65.2.1 SaveTemporaryAnalyticReport

The **SaveTemporaryAnalyticReport** element specifies the input data for the **SaveTemporaryAnalyticReport** WSDL operation.

```
<xs:element name="SaveTemporaryAnalyticReport" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="reportView" type="tns:ReportView"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

reportView: The report view to store. This element **MUST** be present and **MUST** conform to the schema of the **ReportView** complex type (section [2.2.4.160](#)).

3.1.4.65.2.2 SaveTemporaryAnalyticReportResponse

The **SaveTemporaryAnalyticReportResponse** element specifies the result data for the **SaveTemporaryAnalyticReport** WSDL operation.

```
<xs:element name="SaveTemporaryAnalyticReportResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="SaveTemporaryAnalyticReportResult"
        xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

SaveTemporaryAnalyticReportResult: A GUID that uniquely identifies a **ReportView** complex type (section [2.2.4.160](#)) and the values of all attributes and elements except **Location**. This element **MUST** be present.

3.1.4.65.3 Complex Types

None.

3.1.4.65.4 Simple Types

None.

3.1.4.65.5 Attributes

None.

3.1.4.65.6 Groups

None.

3.1.4.65.7 Attribute Groups

None.

3.1.4.66 TestConnection

The **TestConnection** operation is used to determine whether a connection as specified by the **dataSource** element can be established.

The following is the WSDL port type specification of the **TestConnection** WSDL operation.

```
<wsdl:operation name="TestConnection" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:TestConnectionSoapIn"/>
  <wsdl:output message="tns:TestConnectionSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **TestConnectionSoapIn** request message (section [3.1.4.66.1.1](#)), and the server (2) responds with a **TestConnectionSoapOut** response message (section [3.1.4.66.1.2](#)) as follows:

- The protocol client MUST set the **dataSource** element to a non-empty value. If the **Location** attribute of the **dataSource** element refers to a location for which the user does not have read permissions, the server (2) MUST return a SOAP fault containing the error code **InvalidPermission**.
- The server (2) MUST return **TRUE** if a connection as specified by the data source (1) can be established, and if the **Location** attribute of the **dataSource** element refers to a trusted location (1). Otherwise, the server (2) MUST return **FALSE**.
- Any errors that occur while making a connection as specified by the data source (1) MUST NOT result in a SOAP fault, and MUST result in a return value of **FALSE**.

Error code	Description
NotTrustedLocation	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#)

3.1.4.66.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
TestConnectionSoapIn	The request WSDL message for the TestConnection WSDL operation.
TestConnectionSoapOut	The response WSDL message for the TestConnection WSDL operation.

3.1.4.66.1.1 TestConnectionSoapIn

The request WSDL message for the **TestConnection** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/TestConnection
```

The SOAP body contains the **TestConnection** element.

3.1.4.66.1.2 TestConnectionSoapOut

The response WSDL message for the **TestConnection** WSDL operation.

The SOAP body contains the **TestConnectionResponse** element.

3.1.4.66.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
TestConnection	The input data for the TestConnection WSDL operation.
TestConnectionResponse	The result data for the TestConnection WSDL operation.

3.1.4.66.2.1 TestConnection

The **TestConnection** element specifies the input data for the **TestConnection** WSDL operation.

```
<xs:element name="TestConnection" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

dataSource: The data source (1) to be tested. See the **DataSource** complex type (section [2.2.4.85](#)) for specification. This element MUST NOT be empty.

3.1.4.66.2 TestConnectionResponse

The **TestConnectionResponse** element specifies the result data for the **TestConnection** WSDL operation.

```
<xs:element name="TestConnectionResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="TestConnectionResult" type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

TestConnectionResult: Set to **TRUE** if the connection specified by the data source (1) can be made; otherwise, this element is **FALSE**.

3.1.4.66.3 Complex Types

None.

3.1.4.66.4 Simple Types

None.

3.1.4.66.5 Attributes

None.

3.1.4.66.6 Groups

None.

3.1.4.66.7 Attribute Groups

None.

3.1.4.67 TrimAnnotationByOwner

The **TrimAnnotationByOwner** operation removes all the **Annotation** complex types (section [2.2.4.18](#)) that are owned by a specific user.

The following is the WSDL port type specification of the **TrimAnnotationByOwner** WSDL operation.

```
<wsdl:operation name="TrimAnnotationByOwner" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:TrimAnnotationByOwnerSoapIn"/>
  <wsdl:output message="tns:TrimAnnotationByOwnerSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **TrimAnnotationByOwnerSoapIn** request message (section [3.1.4.67.1.1](#)), and the server (2) responds with a **TrimAnnotationByOwnerSoapOut** response message (section [3.1.4.67.1.2](#)) as follows:

- The protocol client MUST send the name of a user as the **Owner** property of the **TrimAnnotationByOwner** element (section [3.1.4.67.2.1](#)).
- The server (2) MUST delete all **Annotations** for which the **Owner** element equals the **Owner** element of the passed in **TrimAnnotationByOwner** element. The server (2) MUST ignore case when comparing the strings.

Error code	Description
InvalidPermissionAdmin	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.67.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
TrimAnnotationByOwnerSoapIn	The request WSDL message for the TrimAnnotationByOwner WSDL operation.
TrimAnnotationByOwnerSoapOut	The response WSDL message for the TrimAnnotationByOwner WSDL operation.

3.1.4.67.1.1 TrimAnnotationByOwnerSoapIn

The request WSDL message for the **TrimAnnotationByOwner** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/TrimAnnotationByOwner
```

The SOAP body contains the **TrimAnnotationByOwner** element.

3.1.4.67.1.2 TrimAnnotationByOwnerSoapOut

The response WSDL message for the **TrimAnnotationByOwner** WSDL operation.

The SOAP body contains the **TrimAnnotationByOwnerResponse** element.

3.1.4.67.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
TrimAnnotationByOwner	The input data for the TrimAnnotationByOwner WSDL operation.
TrimAnnotationByOwnerResponse	The result data for the TrimAnnotationByOwner WSDL operation.

Element	Description
	operation.

3.1.4.67.2.1 TrimAnnotationByOwner

The **TrimAnnotationByOwner** element specifies the input data for the **TrimAnnotationByOwner** WSDL operation.

```
<xs:element name="TrimAnnotationByOwner" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="Owner" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

Owner: Specifies the name of the user. This element **MUST** be present and **MUST** have a length greater than zero.

3.1.4.67.2.2 TrimAnnotationByOwnerResponse

The **TrimAnnotationByOwnerResponse** element specifies the result data for the **TrimAnnotationByOwner** WSDL operation.

```
<xs:element name="TrimAnnotationByOwnerResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.67.3 Complex Types

None.

3.1.4.67.4 Simple Types

None.

3.1.4.67.5 Attributes

None.

3.1.4.67.6 Groups

None.

3.1.4.67.7 Attribute Groups

None.

3.1.4.68 TrimAnnotationByScorecardLocation

The **TrimAnnotationByScorecardLocation** operation removes all the annotations that belong to a scorecard at a specific location.

The following is the WSDL port type specification of the **TrimAnnotationByScorecardLocation** WSDL operation.

```
<wsdl:operation name="TrimAnnotationByScorecardLocation"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:TrimAnnotationByScorecardLocationSoapIn"/>
  <wsdl:output message="tns:TrimAnnotationByScorecardLocationSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **TrimAnnotationByScorecardLocationSoapIn** request message (section [3.1.4.68.1.1](#)), and the server (2) responds with a **TrimAnnotationByScorecardLocationSoapOut** response message (section [3.1.4.68.1.2](#)) as follows:

- The protocol client MUST send the location of a scorecard as the **scorecardLocation** property of the **TrimAnnotationByScorecardLocation** element (section [3.1.4.68.2.1](#)).
- The server (2) MUST delete all **Annotation** complex types (section [2.2.4.18](#)) for which the **ScorecardLocation** element's **ItemUrl** attribute, as specified by **RepositoryLocation** complex type (section [2.2.4.161](#)), equals the **ItemUrl** attribute of the passed in **scorecardLocation** element.

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.68.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
TrimAnnotationByScorecardLocationSoapIn	The request WSDL message for the TrimAnnotationByScorecardLocation WSDL operation.
TrimAnnotationByScorecardLocationSoapOut	The response WSDL message for the TrimAnnotationByScorecardLocation WSDL operation.

3.1.4.68.1.1 TrimAnnotationByScorecardLocationSoapIn

The request WSDL message for the **TrimAnnotationByScorecardLocation** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/TrimAnnotationByScorecardLocation
```

The SOAP body contains the **TrimAnnotationByScorecardLocation** element.

3.1.4.68.1.2 TrimAnnotationByScorecardLocationSoapOut

The response WSDL message for the **TrimAnnotationByScorecardLocation** WSDL operation.

The SOAP body contains the **TrimAnnotationByScorecardLocationResponse** element.

3.1.4.68.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
TrimAnnotationByScorecardLocation	The input data for the TrimAnnotationByScorecardLocation WSDL operation.
TrimAnnotationByScorecardLocationResponse	The result data for the TrimAnnotationByScorecardLocation WSDL operation.

3.1.4.68.2.1 TrimAnnotationByScorecardLocation

The **TrimAnnotationByScorecardLocation** element specifies the input data for the **TrimAnnotationByScorecardLocation** WSDL operation.

```
<xs:element name="TrimAnnotationByScorecardLocation"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
        type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

scorecardLocation: Specifies the location of the scorecard for which all annotations will be deleted. This element **MUST** conform to the schema of the **RepositoryLocation** complex type (section [2.2.4.161](#)), **MUST** be present, and the **ItemType** attribute **MUST NOT** equal **TempReportView**, as specified in the **FirstClassObjectType** complex type (section [2.2.5.20](#)).

3.1.4.68.2.2 TrimAnnotationByScorecardLocationResponse

The **TrimAnnotationByScorecardLocationResponse** element specifies the result data for the **TrimAnnotationByScorecardLocation** WSDL operation.

```
<xs:element name="TrimAnnotationByScorecardLocationResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.68.3 Complex Types

None.

3.1.4.68.4 Simple Types

None.

3.1.4.68.5 Attributes

None.

3.1.4.68.6 Groups

None.

3.1.4.68.7 Attribute Groups

None.

3.1.4.69 TrimAnnotationUntouchedSince

The **TrimAnnotationUntouchedSince** operation removes all the **Annotation** complex types (section [2.2.4.18](#)) that haven't been updated since the specified date.

The following is the WSDL port type specification of the **TrimAnnotationUntouchedSince** WSDL operation.

```
<wsdl:operation name="TrimAnnotationUntouchedSince"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:TrimAnnotationUntouchedSinceSoapIn"/>
  <wsdl:output message="tns:TrimAnnotationUntouchedSinceSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **TrimAnnotationUntouchedSinceSoapIn** request message (section [3.1.4.69.1.1](#)), and the server (2) responds with a **TrimAnnotationUntouchedSinceSoapOut** response message (section [3.1.4.69.1.2](#)) as follows:

- The protocol client MUST send the last modified date as the **untouchedSince** property of the **TrimAnnotationUntouchedSince** element (section [3.1.4.69.2.1](#)).
- The server (2) MUST delete all the **Annotations** for which the date specified by **LastUpdatedOn** property is before or equal to the date specified by the client.

Error code	Description
InvalidPermissionAdmin	User does not have sufficient administration permissions to complete the request.

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.69.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
TrimAnnotationUntouchedSinceSoapIn	The request WSDL message for the TrimAnnotationUntouchedSince WSDL operation.
TrimAnnotationUntouchedSinceSoapOut	The response WSDL message for the TrimAnnotationUntouchedSince WSDL operation.

3.1.4.69.1.1 TrimAnnotationUntouchedSinceSoapIn

The request WSDL message for the **TrimAnnotationUntouchedSince** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/TrimAnnotationUntouchedSince
```

The SOAP body contains the **TrimAnnotationUntouchedSince** element.

3.1.4.69.1.2 TrimAnnotationUntouchedSinceSoapOut

The response WSDL message for the **TrimAnnotationUntouchedSince** WSDL operation.

The SOAP body contains the **TrimAnnotationUntouchedSinceResponse** element.

3.1.4.69.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
TrimAnnotationUntouchedSince	The input data for the TrimAnnotationUntouchedSince WSDL operation.
TrimAnnotationUntouchedSinceResponse	The result data for the TrimAnnotationUntouchedSince WSDL operation.

3.1.4.69.2.1 TrimAnnotationUntouchedSince

The **TrimAnnotationUntouchedSince** element specifies the input data for the **TrimAnnotationUntouchedSince** WSDL operation.

```
<xs:element name="TrimAnnotationUntouchedSince" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="untouchedSince" type="xs:dateTime"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

untouchedSince: Specifies the last modified date of the **Annotation** complex types (section [2.2.4.18](#)) which MUST be deleted. This element MUST be present and MUST be a valid dateTime.

3.1.4.69.2.2 TrimAnnotationUntouchedSinceResponse

The **TrimAnnotationUntouchedSinceResponse** element specifies the result data for the **TrimAnnotationUntouchedSince** WSDL operation.

```
<xs:element name="TrimAnnotationUntouchedSinceResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.69.3 Complex Types

None.

3.1.4.69.4 Simple Types

None.

3.1.4.69.5 Attributes

None.

3.1.4.69.6 Groups

None.

3.1.4.69.7 Attribute Groups

None.

3.1.4.70 UpdateAnnotation

The **UpdateAnnotation** operation updates an existing **Annotation** complex type (section [2.2.4.18](#)).

The following is the WSDL port type specification of the **UpdateAnnotation** WSDL operation.

```
<wsdl:operation name="UpdateAnnotation" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:UpdateAnnotationSoapIn"/>
  <wsdl:output message="tns:UpdateAnnotationSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **UpdateAnnotationSoapIn** request message (section [3.1.4.70.1.1](#)), and the server (2) responds with an **UpdateAnnotationSoapOut** response message (section [3.1.4.70.1.2](#)) as follows:

- The protocol client MUST send a valid **Annotation** object that specifies the new state of the annotation that is being updated.
- The server (2) MUST validate the **Annotation** object following the schema of the **Annotation**.
- The server (2) MUST verify that the **Annotation** object exists by using the **AnnotationId** property (see section [3.1.4.23.2.1](#)), and MUST verify that the **Annotation** object is unchanged since received by the client by comparing the **LastModifiedOn** value. If the **LastModifiedOn**

value is not the same, which means the **Annotation** object has been changed since it was received by the client, the update **MUST** be ignored and an application error raised using the **Unknown** error code.

- The server (2) **MUST** update the stored copy of the **Annotation** object and **SHOULD** generate a new **LastModifiedOn** date value with the server (2) current date. **MUST NOT** update the **CreatedOn** value and **MUST** ignore the value if changed by the protocol client.
- The server (2) **MUST** return the updated copy of the **Annotation** object, including the updated **LastModifiedOn** value.

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
InvalidAnnotation	The updated annotation did not validate to the conforming schema.
InvalidTextLength	A string attribute is null, empty or exceeds its specified maximum length.
InvalidCharacters	The updated annotation properties did not validate to the conforming schema.
InvalidComment	The updated annotation comments did not validate to the conforming schema.
AnnotationNotEnabled	Annotations are not enabled in the server (2).
AnnotationDeleteNotEnabled	If Annotation Delete is not enabled in the server (2), but this request, which would delete comments, is received, the comments will not be changed on the server (2) and the AnnotationDeleteNotEnabled error code will be returned.

In case of any other failure, the error code **MUST** be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.70.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdateAnnotationSoapIn	The request WSDL message for the UpdateAnnotation WSDL operation.
UpdateAnnotationSoapOut	The response WSDL message for the UpdateAnnotation WSDL operation.

3.1.4.70.1.1 UpdateAnnotationSoapIn

The request WSDL message for the **UpdateAnnotation** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/UpdateAnnotation
```

The SOAP body contains the **UpdateAnnotation** element.

3.1.4.70.1.2 UpdateAnnotationSoapOut

The response WSDL message for the **UpdateAnnotation** WSDL operation.

The SOAP body contains the **UpdateAnnotationResponse** element.

3.1.4.70.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdateAnnotation	The input data for the UpdateAnnotation WSDL operation.
UpdateAnnotationResponse	The result data for the UpdateAnnotation WSDL operation.

3.1.4.70.2.1 UpdateAnnotation

The **UpdateAnnotation** element specifies the input data for the **UpdateAnnotation** WSDL operation.

```
<xs:element name="UpdateAnnotation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="annotation" type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

annotation: The updated **Annotation** complex type (section [2.2.4.18](#)). This element MUST NOT be null and MUST conform to the schema of the **Annotation**. It MUST contain the original **AnnotationId** and **LastModifiedOn** values.

3.1.4.70.2.2 UpdateAnnotationResponse

The **UpdateAnnotationResponse** element specifies the result data for the **UpdateAnnotation** WSDL operation.

```
<xs:element name="UpdateAnnotationResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateAnnotationResult"
        type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

UpdateAnnotationResult: The updated **Annotation** complex type object (section [2.2.4.18](#)). This element MUST be a copy of the updated **Annotation** with the new **LastModifiedOn** value, as stored in the server (2).

3.1.4.70.3 Complex Types

None.

3.1.4.70.4 Simple Types

None.

3.1.4.70.5 Attributes

None.

3.1.4.70.6 Groups

None.

3.1.4.70.7 Attribute Groups

None.

3.1.4.71 UpdateDashboard

The **UpdateDashboard** operation updates an existing **Dashboard** complex type (section [2.2.4.79](#)).

The following is the WSDL port type specification of the **UpdateDashboard** WSDL operation.

```
<wsdl:operation name="UpdateDashboard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:UpdateDashboardSoapIn"/>
  <wsdl:output message="tns:UpdateDashboardSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **UpdateDashboardSoapIn** request message (section [3.1.4.71.1.1](#)), and the server (2) responds with an **UpdateDashboardSoapOut** response message (section [3.1.4.71.1.2](#)) as follows:

- The protocol client MUST send a valid **Dashboard** object that specifies the new state of the dashboard that is being updated.
- The server (2) MUST validate the **Dashboard** following the schema of the **Dashboard**.
- The server (2) MUST verify that the **Dashboard** exists by using the **Location** attribute as specified in the base class **FirstClassElement** complex type (section [2.2.4.99](#)).
- The server (2) MUST update the stored copy of the **Dashboard**.
 - **ModifiedBy** SHOULD be updated by the server (2) with the login name of the current user.
 - **LastModified** SHOULD be updated by the server (2) with the date and time of when the dashboard was updated on the server (2) storage. The new value of **LastModified** MUST be greater than or equal to the **LastModified** that was initially submitted to the server (2).
 - **Version** SHOULD be updated by the server (2) with the **current version** of the dashboard object. If **Version** is updated by the server (2), it MUST NOT be null and MUST be a valid **ElementVersion** complex type object (section [2.2.4.92](#)).

- The other properties of the dashboard SHOULD be equal to the **Dashboard** object submitted to the server (2).
- The server (2) MUST return a copy of the updated **Dashboard** object.

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidItemType	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedNameCollision	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.71.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdateDashboardSoapIn	The request WSDL message for the UpdateDashboard WSDL operation.
UpdateDashboardSoapOut	The response WSDL message for the UpdateDashboard WSDL operation.

3.1.4.71.1.1 UpdateDashboardSoapIn

The request WSDL message for the **UpdateDashboard** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/UpdateDashboard
```

The SOAP body contains the **UpdateDashboard** element.

3.1.4.71.1.2 UpdateDashboardSoapOut

The response WSDL message for the **UpdateDashboard** WSDL operation.

The SOAP body contains the **UpdateDashboardResponse** element.

3.1.4.71.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdateDashboard	The input data for the UpdateDashboard WSDL operation.
UpdateDashboardResponse	The result data for the UpdateDashboard WSDL operation.

3.1.4.71.2.1 UpdateDashboard

The **UpdateDashboard** element specifies the input data for the **UpdateDashboard** WSDL operation.

```
<xs:element name="UpdateDashboard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dashboard" type="tns:Dashboard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dashboard: The updated dashboard. This element **MUST NOT** be null and **MUST** conform to the schema of the **Dashboard** complex type (section [2.2.4.79](#)).

3.1.4.71.2.2 UpdateDashboardResponse

The **UpdateDashboardResponse** element specifies the result data for the **UpdateDashboard** WSDL operation.

```
<xs:element name="UpdateDashboardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateDashboardResult"
type="tns:Dashboard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

UpdateDashboardResult: The updated **Dashboard** complex type object (section [2.2.4.79](#)). This element **MUST** be a copy of the updated dashboard, as stored in the server (2).

3.1.4.71.3 Complex Types

None.

3.1.4.71.4 Simple Types

None.

3.1.4.71.5 Attributes

None.

3.1.4.71.6 Groups

None.

3.1.4.71.7 Attribute Groups

None.

3.1.4.72 UpdateDataSource

The **UpdateDataSource** operation updates an existing **DataSource** complex type (section [2.2.4.85](#)).

The following is the WSDL port type specification of the **UpdateDataSource** WSDL operation.

```
<wsdl:operation name="UpdateDataSource" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:UpdateDataSourceSoapIn"/>
  <wsdl:output message="tns:UpdateDataSourceSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **UpdateDataSourceSoapIn** request message (section [3.1.4.72.1.1](#)), and the server (2) responds with an **UpdateDataSourceSoapOut** response message (section [3.1.4.72.1.2](#)) as follows:

- The protocol client MUST send a valid **DataSource** object that specifies the new state of the data source (1) that is being updated.
- The server (2) MUST validate the **DataSource** following the schema of the **DataSource**.
- The server (2) MUST verify that the **DataSource** exists by using the **Location** attribute as specified in the base class **FirstClassElement** complex type (section [2.2.4.99](#)).
- The server (2) MUST update the stored copy of the **DataSource**. MUST NOT update the **SourceName** value and MUST ignore the value if changed by the protocol client.
 - **ModifiedBy** SHOULD be updated by the server (2) with the login name of the current user.
 - **LastModified** SHOULD be updated by the server (2) with the date and time of when the data source (1) was updated on the server (2) storage.
 - **Version** SHOULD be updated by the server (2) with the current version of the **DataSource** object. If **Version** is updated by the server (2), it MUST NOT be null and MUST be a valid **ElementVersion** complex type object (section [2.2.4.92](#)).
- The other properties of the data source (1) SHOULD be equal to the data source (1) submitted to the server (2).
- The server (2) MUST return a copy of the updated **DataSource** object.

Error code	Description
InvalidPermission	See Common List of Error Codes (section 2.2.2.1.3).
InvalidDataSource	The updated data source (1) did not validate to the conforming schema.
FCOUpdateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidItemType	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedNameCollision	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.72.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdateDataSourceSoapIn	The request WSDL message for the UpdateDataSource WSDL operation.
UpdateDataSourceSoapOut	The response WSDL message for the UpdateDataSource WSDL operation.

3.1.4.72.1.1 UpdateDataSourceSoapIn

The request WSDL message for the **UpdateDataSource** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/UpdateDataSource
```

The SOAP body contains the **UpdateDataSource** element.

3.1.4.72.1.2 UpdateDataSourceSoapOut

The response WSDL message for the **UpdateDataSource** WSDL operation.

The SOAP body contains the **UpdateDataSourceResponse** element.

3.1.4.72.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdateDataSource	The input data for the UpdateDataSource WSDL operation.
UpdateDataSourceResponse	The result data for the UpdateDataSource WSDL operation.

3.1.4.72.2.1 UpdateDataSource

The **UpdateDataSource** element specifies the input data for the **UpdateDataSource** WSDL operation.

```
<xs:element name="UpdateDataSource" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

dataSource: The updated **datasource**. This element **MUST NOT** be null and **MUST** conform to the schema of the **DataSource** complex type (section [2.2.4.85](#)).

3.1.4.72.2.2 UpdateDataSourceResponse

The **UpdateDataSourceResponse** element specifies the result data for the **UpdateDataSource** WSDL operation.

```
<xs:element name="UpdateDataSourceResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateDataSourceResult"
type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

UpdateDataSourceResult: The updated **DataSource** complex type (section [2.2.4.85](#)). This element **MUST** be a copy of the updated **datasource** as stored in the server (2).

3.1.4.72.3 Complex Types

None.

3.1.4.72.4 Simple Types

None.

3.1.4.72.5 Attributes

None.

3.1.4.72.6 Groups

None.

3.1.4.72.7 Attribute Groups

None.

3.1.4.73 UpdateFilter

The **UpdateFilter** operation is used to update the existing filter as specified by the **Filter** complex type object (section [2.2.4.98](#)) in the **UpdateFilter** input element (section [3.1.4.73.2.1](#)).

The following is the WSDL port type specification of the **UpdateFilter** WSDL operation.

```
<wsdl:operation name="UpdateFilter" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:UpdateFilterSoapIn"/>
  <wsdl:output message="tns:UpdateFilterSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **UpdateFilterSoapIn** request message (section [3.1.4.73.1.1](#)), and the server (2) responds with an **UpdateFilterSoapOut** response message (section [3.1.4.73.1.2](#)) as follows:

- The protocol client MUST send a valid **Filter** object instance that specifies the new state of the filter.
- The server (2) MUST validate the filter following the schema of the **Filter**.
- The server (2) MUST verify that the filter exists by using the **Location** attribute as specified in the base class **FirstClassElement** complex type (section [2.2.4.99](#)) and that the user has permissions to access and modify it.
- The server (2) MUST update the stored copy of the filter.
 - **ModifiedBy** SHOULD be updated by the server (2) with the login name of the current user.
 - **LastModified** SHOULD be updated by the server (2) with the date and time of when the filter was updated on the server (2) storage. The new value of **LastModified** MUST be greater than or equal to the **LastModified** that was initially submitted to the server (2).
 - **Version** SHOULD be updated by the server (2) with the current version of the filter object. If **Version** is updated by the server (2), it MUST NOT be null and MUST be a valid **ElementVersion** complex type object (section [2.2.4.92](#)).
 - The other properties of the filter SHOULD be equal to the **Filter** object submitted to the server (2).
- The server (2) MUST return a new **Filter** object instance that represents the updated filter.

Error code	Description
FCOUpdateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidItemType	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.73.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdateFilterSoapIn	The request WSDL message for the UpdateFilter WSDL operation.
UpdateFilterSoapOut	The response WSDL message for the UpdateFilter WSDL operation.

3.1.4.73.1.1 UpdateFilterSoapIn

The request WSDL message for the **UpdateFilter** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/UpdateFilter
```

The SOAP body contains the **UpdateFilter** element.

3.1.4.73.1.2 UpdateFilterSoapOut

The response WSDL message for the **UpdateFilter** WSDL operation.

The SOAP body contains the **UpdateFilterResponse** element.

3.1.4.73.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdateFilter	The input data for the UpdateFilter WSDL operation.
UpdateFilterResponse	The result data for the UpdateFilter WSDL operation.

3.1.4.73.2.1 UpdateFilter

The **UpdateFilter** element specifies the input data for the **UpdateFilter** WSDL operation.

```
<xs:element name="UpdateFilter" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="filter" type="tns:Filter"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

filter: A **Filter** complex type object (section [2.2.4.98](#)) instance that specifies the new state of the filter that is being updated.

3.1.4.73.2.2 UpdateFilterResponse

The **UpdateFilterResponse** element specifies the result data for the **UpdateFilter** WSDL operation.

```
<xs:element name="UpdateFilterResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateFilterResult" type="tns:Filter"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

UpdateFilterResult: A **Filter** complex type object (section [2.2.4.98](#)) instance that specifies the updated filter.

3.1.4.73.3 Complex Types

None.

3.1.4.73.4 Simple Types

None.

3.1.4.73.5 Attributes

None.

3.1.4.73.6 Groups

None.

3.1.4.73.7 Attribute Groups

None.

3.1.4.74 UpdateIndicator

The **UpdateIndicator** operation is used to update the existing **Indicator** as specified by the **Indicator** complex type object (section [2.2.4.125](#)) in the **UpdateIndicator** input element (section [3.1.4.74.2.1](#)).

The following is the WSDL port type specification of the **UpdateIndicator** WSDL operation.

```
<wsdl:operation name="UpdateIndicator" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:UpdateIndicatorSoapIn"/>
  <wsdl:output message="tns:UpdateIndicatorSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **UpdateIndicatorSoapIn** request message (section [3.1.4.74.1.1](#)), and the server (2) responds with an **UpdateIndicatorSoapOut** response message (section [3.1.4.74.1.2](#)) as follows:

- The protocol client MUST send a valid **Indicator** object instance that specifies the new state of the **indicator**.
- The server (2) MUST validate the **indicator** following the schema of the **Indicator**.
- The server (2) MUST verify that the **indicator** exists by using the **Location** attribute as specified in the base class **FirstClassElement** complex type (section [2.2.4.99](#)) and that the user has permissions to access and modify it.
- The server (2) MUST update the stored copy of the **indicator**.
 - **ModifiedBy** SHOULD be updated by the server (2) with the login name of the current user.
 - **LastModified** SHOULD be updated by the server (2) with the date and time of when the **indicator** was updated on the server (2) storage. The new value of **LastModified** MUST be greater than or equal to the **LastModified** that was initially submitted to the server (2). **Version** SHOULD be updated by the server (2) with the current version of the **indicator** object. If **Version** is updated by the server (2), it MUST NOT be null and MUST be a valid **ElementVersion** complex type object (section [2.2.4.92](#)).
 - **CreatedBy** SHOULD be updated by the server (2).
 - **CreatedDate** SHOULD be updated by the server (2).
 - The other properties of the **indicator** SHOULD be equal to the **Indicator** object submitted to the server (2).
- The server (2) MUST return a new **Indicator** object instance that represents the updated **indicator**.

Error code	Description
InvalidBuiltinIndicatorOperation	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailed	See Common List of Error Codes (section 2.2.2.1.3).

Error code	Description
FCOUpdateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidItemType	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
InvalidIndicator	See Common List of Error Codes (section 2.2.2.1.3).
InvalidIndicatorBand	See Common List of Error Codes (section 2.2.2.1.3).
InvalidSetting	See Common List of Error Codes (section 2.2.2.1.3).
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).
Unknown	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.74.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdateIndicatorSoapIn	The request WSDL message for the UpdateIndicator WSDL operation.
UpdateIndicatorSoapOut	The response WSDL message for the UpdateIndicator WSDL operation.

3.1.4.74.1.1 UpdateIndicatorSoapIn

The request WSDL message for the **UpdateIndicator** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/UpdateIndicator
```

The SOAP body contains the **UpdateIndicator** element.

3.1.4.74.1.2 UpdateIndicatorSoapOut

The response WSDL message for the **UpdateIndicator** WSDL operation.

The SOAP body contains the **UpdateIndicatorResponse** element.

3.1.4.74.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdateIndicator	The input data for the UpdateIndicator WSDL operation.
UpdateIndicatorResponse	The result data for the UpdateIndicator WSDL operation.

3.1.4.74.2.1 UpdateIndicator

The **UpdateIndicator** element specifies the input data for the **UpdateIndicator** WSDL operation.

```
<xs:element name="UpdateIndicator" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="indicator" type="tns:Indicator"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

indicator: An **Indicator** complex type object (section [2.2.4.125](#)) instance that specifies the new state of the indicator that is being updated.

3.1.4.74.2.2 UpdateIndicatorResponse

The **UpdateIndicatorResponse** element specifies the result data for the **UpdateIndicator** WSDL operation.

```
<xs:element name="UpdateIndicatorResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateIndicatorResult"
type="tns:Indicator"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

UpdateIndicatorResult: An **Indicator** complex type object (section [2.2.4.125](#)) instance that specifies the updated indicator.

3.1.4.74.3 Complex Types

None.

3.1.4.74.4 Simple Types

None.

3.1.4.74.5 Attributes

None.

3.1.4.74.6 Groups

None.

3.1.4.74.7 Attribute Groups

None.

3.1.4.75 UpdateKpi

The **UpdateKpi** operation is used to update the existing KPI as specified by the **Kpi** complex type object (section [2.2.4.128](#)) in the **UpdateKpi** input element (section [3.1.4.75.2.1](#)).

The following is the WSDL port type specification of the **UpdateKpi** WSDL operation.

```
<wsdl:operation name="UpdateKpi" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:UpdateKpiSoapIn"/>
  <wsdl:output message="tns:UpdateKpiSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **UpdateKpiSoapIn** request message (section [3.1.4.75.1.1](#)), and the server (2) responds with an **UpdateKpiSoapOut** response message (section [3.1.4.75.1.2](#)) as follows:

- The protocol client MUST send a valid **Kpi** object instance that specifies the new state of the KPI.
- The server (2) MUST validate the KPI following the schema of the **Kpi**.
- The server (2) MUST verify that the KPI exists by using the **Location** attribute as specified in the base class **FirstClassElement** complex type (section [2.2.4.99](#)) and that the user has permissions to access and modify it.
- The server (2) MUST update the stored copy of the KPI.
 - **ModifiedBy** SHOULD be updated by the server (2) with the login name of the current user.
 - **LastModified** SHOULD be updated by the server (2) with the date and time of when the KPI was updated on the server (2) storage. The new value of **LastModified** MUST be greater than or equal to the **LastModified** that was initially submitted to the server (2).
 - **Version** SHOULD be updated by the server (2) with the current version of the KPI object. If **Version** is updated by the server (2), it MUST NOT be null and MUST be a valid **ElementVersion** complex type object (section [2.2.4.92](#)).
 - The other properties of the KPI SHOULD be equal to the **Kpi** object submitted to the server (2).
- The server (2) MUST return a new **Kpi** object instance that represents the updated KPI.

Error code	Description
FCOUpdateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidItemType	See Common List of Error Codes (section 2.2.2.1.3).

Error code	Description
FCOUpdateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
InvalidKpi	See Common List of Error Codes (section 2.2.2.1.3).
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.75.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdateKpiSoapIn	The request WSDL message for the UpdateKpi WSDL operation.
UpdateKpiSoapOut	The response WSDL message for the UpdateKpi WSDL operation.

3.1.4.75.1.1 UpdateKpiSoapIn

The request WSDL message for the **UpdateKpi** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/UpdateKpi
```

The SOAP body contains the **UpdateKpi** element.

3.1.4.75.1.2 UpdateKpiSoapOut

The response WSDL message for the **UpdateKpi** WSDL operation.

The SOAP body contains the **UpdateKpiResponse** element.

3.1.4.75.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdateKpi	The input data for the UpdateKpi WSDL operation.

Element	Description
UpdateKpiResponse	The result data for the UpdateKpi WSDL operation.

3.1.4.75.2.1 UpdateKpi

The **UpdateKpi** element specifies the input data for the **UpdateKpi** WSDL operation.

```
<xs:element name="UpdateKpi" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="kpi" type="tns:Kpi"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

kpi: A **Kpi** complex type object (section [2.2.4.128](#)) instance that specifies the new state of the KPI that is being updated.

3.1.4.75.2.2 UpdateKpiResponse

The **UpdateKpiResponse** element specifies the result data for the **UpdateKpi** WSDL operation.

```
<xs:element name="UpdateKpiResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateKpiResult" type="tns:Kpi"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

UpdateKpiResult: A **Kpi** complex type object (section [2.2.4.128](#)) instance that specifies the updated KPI.

3.1.4.75.3 Complex Types

None.

3.1.4.75.4 Simple Types

None.

3.1.4.75.5 Attributes

None.

3.1.4.75.6 Groups

None.

3.1.4.75.7 Attribute Groups

None.

3.1.4.76 UpdateReportView

The **UpdateReportView** operation is used to update the existing report view as specified by the **ReportView** complex type object (section [2.2.4.160](#)) in the **UpdateReportView** input element (section [3.1.4.76.2.1](#)).

The following is the WSDL port type specification of the **UpdateReportView** WSDL operation.

```
<wsdl:operation name="UpdateReportView" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:UpdateReportViewSoapIn"/>
  <wsdl:output message="tns:UpdateReportViewSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **UpdateReportViewSoapIn** request message (section [3.1.4.76.1.1](#)), and the server (2) responds with an **UpdateReportViewSoapOut** response message (section [3.1.4.76.1.2](#)) as follows:

- The protocol client MUST send a valid **ReportView** object instance that specifies the new state of the report view.
- The server (2) MUST validate the report view following the schema of the **ReportView**.
- The server (2) MUST verify that the report view exists by using the **Location** attribute as specified in the base class **FirstClassElement** complex type (section [2.2.4.99](#)) and that the user has permissions to access and modify it.
- The server (2) MUST update the stored copy of the report view.
 - **ModifiedBy** SHOULD be updated by the server (2) with the login name of the current user.
 - **LastModified** SHOULD be updated by the server (2) with the date and time of when the report view was updated on the server (2) storage. The new value of **LastModified** MUST be greater than or equal to the **LastModified** that was initially submitted to the server (2).
 - **Version** SHOULD be updated by the server (2) with the current version of the report view object. If **Version** is updated by the server (2), it MUST NOT be null and MUST be a valid **ElementVersion** complex type object (section [2.2.4.92](#)).
 - The other properties of the report view SHOULD be equal to the **Indicator** complex type object (section [2.2.4.125](#)) submitted to the server (2).

The server (2) MUST return a new **ReportView** object instance that represents the updated report view.

Error code	Description
FCOUpdateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidItemType	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
InvalidReportView	See Common List of Error Codes (section 2.2.2.1.3).
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).

Error code	Description
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.76.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdateReportViewSoapIn	The request WSDL message for the UpdateReportView WSDL operation.
UpdateReportViewSoapOut	The response WSDL message for the UpdateReportView WSDL operation.

3.1.4.76.1.1 UpdateReportViewSoapIn

The request WSDL message for the **UpdateReportView** WSDL operation.

The SOAP action value is:

`http://www.microsoft.com/performancepoint/scorecards/UpdateReportView`

The SOAP body contains the **UpdateReportView** element.

3.1.4.76.1.2 UpdateReportViewSoapOut

The response WSDL message for the **UpdateReportView** WSDL operation.

The SOAP body contains the **UpdateReportViewResponse** element.

3.1.4.76.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdateReportView	The input data for the UpdateReportView WSDL operation.
UpdateReportViewResponse	The result data for the UpdateReportView WSDL operation.

3.1.4.76.2.1 UpdateReportView

The **UpdateReportView** element specifies the input data for the **UpdateReportView** WSDL operation.

```
<xs:element name="UpdateReportView" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="reportView" type="tns:ReportView"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

reportView: A **ReportView** complex type object (section [2.2.4.160](#)) instance that specifies the new state of the report view that is being updated.

3.1.4.76.2.2 UpdateReportViewResponse

The **UpdateReportViewResponse** element specifies the result data for the **UpdateReportView** WSDL operation.

```
<xs:element name="UpdateReportViewResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateReportViewResult"
type="tns:ReportView"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

UpdateReportViewResult: A **ReportView** complex type object (section [2.2.4.160](#)) instance that specifies the updated report view.

3.1.4.76.3 Complex Types

None.

3.1.4.76.4 Simple Types

None.

3.1.4.76.5 Attributes

None.

3.1.4.76.6 Groups

None.

3.1.4.76.7 Attribute Groups

None.

3.1.4.77 UpdateScorecard

The **UpdateScorecard** operation is used to update the existing scorecard as specified by the **Scorecard** complex type object (section [2.2.4.162](#)) in the **UpdateScorecard** input element (section [3.1.4.77.2.1](#)).

The following is the WSDL port type specification of the **UpdateScorecard** WSDL operation.

```
<wsdl:operation name="UpdateScorecard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:UpdateScorecardSoapIn"/>
  <wsdl:output message="tns:UpdateScorecardSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **UpdateScorecardSoapIn** request message (section [3.1.4.77.1.1](#)), and the server (2) responds with an **UpdateScorecardSoapOut** response message (section [3.1.4.77.1.2](#)) as follows:

- The scorecard to be updated MUST be a valid **Scorecard**.
- The **Location** of the scorecard (see [FirstClassElement](#) section 2.2.4.99) MUST exist.
- The current user MUST have read and write permissions to the **Location** (FirstClassElement) of the scorecard.
- The **Location** of the scorecard MUST support storing objects of type **Scorecard**.
- The stored copy on the server (2) MUST be updated with the scorecard provided by the protocol client in the **UpdateScorecardSoapIn** request message.

Error code	Description
FCOUpdateFailed	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListAccess	See Common List of Error Codes (section 2.2.2.1.3).
InvalidItemType	See Common List of Error Codes (section 2.2.2.1.3).
FCOUpdateFailedListType	See Common List of Error Codes (section 2.2.2.1.3).
InvalidObject	See Common List of Error Codes (section 2.2.2.1.3).
InvalidCategoryName	See Common List of Error Codes (section 2.2.2.1.3).
InvalidFirstClassElementField	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElement	See Common List of Error Codes (section 2.2.2.1.3).
InvalidElementField	See Common List of Error Codes (section 2.2.2.1.3).

In case of any other failure, the error code MUST be one of the values specified in section [2.2.2.1.2](#). A detailed specification of how exceptions are reported by the server (2) is in section [2.2.2.1](#).

3.1.4.77.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdateScorecardSoapIn	The request WSDL message for the UpdateScorecard WSDL operation.
UpdateScorecardSoapOut	The response WSDL message for the UpdateScorecard WSDL operation.

3.1.4.77.1.1 UpdateScorecardSoapIn

The request WSDL message for the **UpdateScorecard** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/UpdateScorecard
```

The SOAP body contains the **UpdateScorecard** element.

3.1.4.77.1.2 UpdateScorecardSoapOut

The response WSDL message for the **UpdateScorecard** WSDL operation.

The SOAP body contains the **UpdateScorecardResponse** element.

3.1.4.77.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdateScorecard	The input data for the UpdateScorecard WSDL operation.
UpdateScorecardResponse	The result data for the UpdateScorecard WSDL operation.

3.1.4.77.2.1 UpdateScorecard

The **UpdateScorecard** element specifies the input data for the **UpdateScorecard** WSDL operation.

```
<xs:element name="UpdateScorecard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecard" type="tns:Scorecard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

scorecard: The scorecard to be updated, which MUST be a valid **Scorecard** complex type (section [2.2.4.162](#)). The **UpdateScorecard** operation (section [3.1.4.77](#)) is used to update the existing scorecard as specified by **Scorecard**.

3.1.4.77.2.2 UpdateScorecardResponse

The **UpdateScorecardResponse** element specifies the result data for the **UpdateScorecard** WSDL operation.

```

<xs:element name="UpdateScorecardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateScorecardResult"
type="tns:Scorecard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

UpdateScorecardResult: The original scorecard object submitted to the server (2), modified as follows:

- **ModifiedBy** SHOULD be updated by the server (2) with the login name of the current user.
- **LastModified** SHOULD be updated by the server (2) with the date and time of when the scorecard was last updated on the server (2) storage. The new value of **LastModified** MUST be greater than or equal to the **LastModified** that was initially submitted to the server (2).
- **Version** SHOULD be updated by the server (2) with the current version of the scorecard object. If **Version** is updated by the server (2), it MUST NOT be null and MUST be a valid **ElementVersion** complex type object (section [2.2.4.92](#)).
- The other properties of the scorecard SHOULD be equal to the original scorecard submitted to the server (2).

3.1.4.77.3 Complex Types

None.

3.1.4.77.4 Simple Types

None.

3.1.4.77.5 Attributes

None.

3.1.4.77.6 Groups

None.

3.1.4.77.7 Attribute Groups

None.

3.1.4.78 ValidateKpi

The **ValidateKpi** operation checks whether a KPI stored on the server (2) is valid.

The following is the WSDL port type specification of the **ValidateKpi** WSDL operation.

```

<wsdl:operation name="ValidateKpi" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:ValidateKpiSoapIn"/>
  <wsdl:output message="tns:ValidateKpiSoapOut"/>

```

</wsdl:operation>

The protocol client sends a **ValidateKpiSoapIn** request message (section [3.1.4.78.1.1](#)), and the server (2) responds with a **ValidateKpiSoapOut** response message (section [3.1.4.78.1.2](#)), as follows:

- If the KPI contains any **Actuals** (see section [2.2.4.128](#)), each MUST be a valid **KpiMeasure** complex type (section [2.2.4.129](#)) as follows:
 - If the **DataSourceLocation** field of **KpiMeasure** is not empty, it MUST refer to an existing data source (1) element (see section [2.2.4.85](#)), and the connection to the data source MUST be successful.
 - If the data source at **DataSourceLocation** is of type ADOMD.NET (see section [2.2.4.85](#)), each **DefaultDimensionSetting** (section [2.2.4.87](#)) MUST be valid as follows:
 - If the **DefaultDimensionSetting** contains any **Members** elements, a **Member** complex type (section [2.2.4.134](#)) for each MUST exist in the data source.
- If the KPI contains any **Targets** elements, each MUST be a valid Target complex type (section [2.2.4.170](#)) as follows:
 - If the property **RelatedActualId** is not empty, it MUST refer to an existing **Actual**, which MUST be valid according to item 1.
 - The **Target** itself MUST be a valid **KpiMeasure** according to item 1.
 - If the property **IndicatorLocation** is not empty, it MUST refer to an existing **Indicator**.
 - If the property **StatedScore** is not empty, it MUST be a valid **KpiMeasure** according to item 1.

3.1.4.78.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ValidateKpiSoapIn	The request WSDL message for the ValidateKpi WSDL operation.
ValidateKpiSoapOut	The response WSDL message for the ValidateKpi WSDL operation.

3.1.4.78.1.1 ValidateKpiSoapIn

The request WSDL message for the **ValidateKpi** WSDL operation.

The SOAP action value is:

`http://www.microsoft.com/performancepoint/scorecards/ValidateKpi`

The SOAP body contains the **ValidateKpi** element.

3.1.4.78.1.2 ValidateKpiSoapOut

The response WSDL message for the **ValidateKpi** WSDL operation.

The SOAP body contains the **ValidateKpiResponse** element.

3.1.4.78.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
ValidateKpi	The input data for the ValidateKpi WSDL operation.
ValidateKpiResponse	The result data for the ValidateKpi WSDL operation.

3.1.4.78.2.1 ValidateKpi

The **ValidateKpi** element specifies the input data for the **ValidateKpi** WSDL operation.

```
<xs:element name="ValidateKpi" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: Location of the KPI to be validated (see [RepositoryLocation](#) section 2.2.4.161).

3.1.4.78.2.2 ValidateKpiResponse

The **ValidateKpiResponse** element specifies the result data for the **ValidateKpi** WSDL operation.

```
<xs:element name="ValidateKpiResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="ValidateKpiResult"
type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

ValidateKpiResult: An array of strings. If the KPI is valid, this array MUST be empty. Otherwise, this array SHOULD contain one localized error message per validation failure.

3.1.4.78.3 Complex Types

None.

3.1.4.78.4 Simple Types

None.

3.1.4.78.5 Attributes

None.

3.1.4.78.6 Groups

None.

3.1.4.78.7 Attribute Groups

None.

3.1.4.79 ValidateScorecard

The **ValidateScorecard** operation checks if a scorecard stored on the server (2) is valid.

The following is the WSDL port type specification of the **ValidateScorecard** WSDL operation.

```
<wsdl:operation name="ValidateScorecard" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:ValidateScorecardSoapIn"/>
  <wsdl:output message="tns:ValidateScorecardSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **ValidateScorecardSoapIn** request message (section [3.1.4.79.1.1](#)), and the server (2) responds with a **ValidateScorecardSoapOut** response message (section [3.1.4.79.1.2](#)) as follows:

- If the scorecard contains one or more KPIs, each KPI MUST be valid according to the specification in the [ValidateKPI](#) operation (section [3.1.4.78](#)).
- If the scorecard contains any **ConfiguredView** complex types (section [2.2.4.77](#)), each MUST be valid as follows:
 - If the **DataSourceLocation** field is not empty, it MUST refer to an existing data source element (section [2.2.4.85](#)) and the connection to the data source MUST be successful.
 - The column and row headers defined in the **GridViewDefinition** (section [2.2.4.122](#)) and [GridHeaderItem](#) (section [2.2.4.116](#)) complex types MUST be valid according to the following:
 - Each column or row header that is of complex type **Member** (section [2.2.4.134](#)) MUST refer to a valid member in the data source.
 - Each column or row header that is of complex type **NamedSet** (section [2.2.4.147](#)) MUST be a well-formed named set MDX.

3.1.4.79.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ValidateScorecardSoapIn	The request WSDL message for the ValidateScorecard WSDL operation.
ValidateScorecardSoapOut	The response WSDL message for the ValidateScorecard WSDL

Message	Description
	operation.

3.1.4.79.1.1 ValidateScorecardSoapIn

The request WSDL message for the **ValidateScorecard** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/ValidateScorecard
```

The SOAP body contains the **ValidateScorecard** element.

3.1.4.79.1.2 ValidateScorecardSoapOut

The response WSDL message for the **ValidateScorecard** WSDL operation.

The SOAP body contains the **ValidateScorecardResponse** element.

3.1.4.79.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
ValidateScorecard	The input data for the ValidateScorecard WSDL operation.
ValidateScorecardResponse	The result data for the ValidateScorecard WSDL operation.

3.1.4.79.2.1 ValidateScorecard

The **ValidateScorecard** element specifies the input data for the **ValidateScorecard** WSDL operation.

```
<xs:element name="ValidateScorecard" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location" type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

location: Location of the scorecard to be validated (see [RepositoryLocation](#) section 2.2.4.161).

3.1.4.79.2.2 ValidateScorecardResponse

The **ValidateScorecardResponse** element specifies the result data for the **ValidateScorecard** WSDL operation.

```
<xs:element name="ValidateScorecardResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
```

```

    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="ValidateScorecardResult"
        type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

ValidateScorecardResult: An array of strings. If the scorecard is valid, this array MUST be empty. Otherwise, this array SHOULD contain one localized error message per validation failure.

3.1.4.79.3 Complex Types

None.

3.1.4.79.4 Simple Types

None.

3.1.4.79.5 Attributes

None.

3.1.4.79.6 Groups

None.

3.1.4.79.7 Attribute Groups

None.

3.1.4.80 ValidateSiteCollection

The **ValidateSiteCollection** operation is used to check if the context site has the server (2) feature installed.

The following is the WSDL port type specification of the **ValidateSiteCollection** WSDL operation.

```

<wsdl:operation name="ValidateSiteCollection" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:ValidateSiteCollectionSoapIn"/>
  <wsdl:output message="tns:ValidateSiteCollectionSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **ValidateSiteCollectionSoapIn** request message (section [3.1.4.80.1.1](#)), and the server (2) responds with a **ValidateSiteCollectionSoapOut** response message (section [3.1.4.80.1.2](#)) as follows:

- If the user-defined context site is the top-level site (2) of a site collection that has the server (2) feature installed, the **ValidateSiteCollectionResult** attribute MUST be "SiteCollection".
- If the user-defined context site is a subsite of a site collection that has the server (2) feature installed, **ValidateSiteCollectionResult** MUST be "Site".
- If the user-defined context site is null, **ValidateSiteCollectionResult** MUST be "NonexistentSiteCollection".

- If the user-defined context site is not a valid site (2) or a site collection and the **siteCollectionUrl** attribute derived from the user-defined context site is not empty, **ValidateSiteCollectionResult** MUST be "Nonexistentsite".
- If the user-defined context site is not a valid site (2) or a site collection and **siteCollectionUrl** derived from the user-defined context site is empty, **ValidateSiteCollectionResult** MUST be "NonexistentSiteCollection".
- If the site collection of the user-defined context site does not have the server (2) feature installed, **ValidateSiteCollectionResult** MUST be "PPSNotActivatedOnSiteCollection".
- **ValidateSiteCollectionResult** MUST NOT have any other values from the **URLValidationResult** enumeration (section [3.1.4.80.4.1](#)) other than those enumerated in the preceding items.

3.1.4.80.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ValidateSiteCollectionSoapIn	The request WSDL message for the ValidateSiteCollection WSDL operation.
ValidateSiteCollectionSoapOut	The response WSDL message for the ValidateSiteCollection WSDL operation.

3.1.4.80.1.1 ValidateSiteCollectionSoapIn

The request WSDL message for the **ValidateSiteCollection** WSDL operation.

The SOAP action value is:

```
http://www.microsoft.com/performancepoint/scorecards/ValidateSiteCollection
```

The SOAP body contains the **ValidateSiteCollection** element.

3.1.4.80.1.2 ValidateSiteCollectionSoapOut

The response WSDL message for the **ValidateSiteCollection** WSDL operation.

The SOAP body contains the **ValidateSiteCollectionResponse** element.

3.1.4.80.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
ValidateSiteCollection	The input data for the ValidateSiteCollection WSDL operation.
ValidateSiteCollectionResponse	The result data for the ValidateSiteCollection WSDL operation.

3.1.4.80.2.1 ValidateSiteCollection

The **ValidateSiteCollection** element specifies the input data for the **ValidateSiteCollection** WSDL operation.

```
<xs:element name="ValidateSiteCollection" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.80.2.2 ValidateSiteCollectionResponse

The **ValidateSiteCollectionResponse** element specifies the result data for the **ValidateSiteCollection** WSDL operation.

```
<xs:element name="ValidateSiteCollectionResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="ValidateSiteCollectionResult"
        type="tns:URLValidationResult"/>
      <xs:element minOccurs="0" maxOccurs="1" name="siteCollectionUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="siteUrl" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

ValidateSiteCollectionResult: A value of type **URLValidationResult** indicating the result of the validation process. See the definition of the **URLValidationResult** simple type (section [3.1.4.80.4.1](#)) for more details.

siteCollectionUrl: The site collection URL of the context site.

siteUrl: The URL of the context site.

3.1.4.80.3 Complex Types

None.

3.1.4.80.4 Simple Types

The following table summarizes the XML schema simple type definitions that are specific to this operation.

Simple type	Description
URLValidationResult	Specifies the possible results of URL validation.

3.1.4.80.4.1 URLValidationResult

Namespace: <http://www.microsoft.com/performancepoint/scorecards>

The **URLValidationResult** is an enumeration used to specify the possible results of URL validation.

```
<xs:simpleType name="URLValidationResult" xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<xs:restriction base="xs:string">
  <xs:enumeration value="SiteCollectionOrSite"/>
  <xs:enumeration value="SiteCollection"/>
  <xs:enumeration value="Site"/>
  <xs:enumeration value="List"/>
  <xs:enumeration value="DocumentLibrary"/>
  <xs:enumeration value="InvalidURL"/>
  <xs:enumeration value="AlreadyExists"/>
  <xs:enumeration value="NonexistentSiteCollection"/>
  <xs:enumeration value="NonexistentSite"/>
  <xs:enumeration value="PPSNotActivatedOnSiteCollection"/>
  <xs:enumeration value="URLZoneNotAllowed"/>
  <xs:enumeration value="NoAccess"/>
  <xs:enumeration value="InvalidSiteVersion"/>
</xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **URLValidationResult** simple type.

Value	Meaning
SiteCollectionOrSite	The context site is a subsite of a site collection or the top-level site (2) of a site collection that has the server (2) feature installed.
SiteCollection	The context site is the top-level site (2) of a site collection and the site collection has the server (2) feature installed.
Site	The context site is a subsite of a site collection and the site collection has the protocol feature installed.
List	The context site is a list (1) of a site collection.
DocumentLibrary	The context site is a document library of a site collection.
InvalidURL	The URL is not valid.
AlreadyExists	The URL already exists.
NonexistentSiteCollection	The context site is not a valid site collection.
NonexistentSite	The context site is not a valid site (2).
PPSNotActivatedOnSiteCollection	The site collection of the context site does not have the server (2) feature activated.
URLZoneNotAllowed	The URL is not in the following security zones : Local, Intranet, or Trusted.
NoAccess	The user has insufficient rights to access the context site.
InvalidSiteVersion	The context site version is not compatible with the current server (2) feature.

3.1.4.80.5 Attributes

None.

3.1.4.80.6 Groups

None.

3.1.4.80.7 Attribute Groups

None.

3.1.5 Timer Events

No timer events are required on the server (2) beyond those required by the underlying RPC transport.

3.1.6 Other Local Events

None.

4 Protocol Examples

The following subsections contain examples of this protocol's usage.

4.1 Scorecard Update

In this example, a protocol client creates a new KPI, adds that KPI to an existing scorecard, gets the result data set for that scorecard, and deletes the scorecard.

The example assumes that the following objects are known to the server (2) with the following identifiers:

Type	Name	Path	ID
Scorecard	New Scorecard.	/PerformancePoint/Lists/Dashboard Content	8_.000
KPI	InternetSales.	/PerformancePoint/Lists/Dashboard Content	4_.000
DataSource	New DataSource.	/PerformancePoint/Data Sources	1_.000

4.1.1 CreateKpi

To create a new KPI, the protocol client calls **CreateKpi** operation (section [3.1.4.6](#)). This call will create a KPI with an Analysis Services actual value using the Internet Sales Amount measure. The target value is a fixed data source with a value of one. The KPI will use a built-in indicator and normalized banding type.

The protocol client creates and sends the following message (white space added for readability):

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CreateKpi xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <listUrl>/PerformancePoint/Lists/Dashboard Content</listUrl>
      <kpi Folder="" CreatedBy="Sample User" CreatedDate="2009-05-21T13:13:06"
Content Type="PpsKpi" LastModified="2009-05-21T13:13:47" ModifiedBy="Sample User"
CheckedOutTo="">
        <Properties>
          <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="InternetSales" />
          <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
          <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
        </Properties>
        <Comments />
        <Version Major="1" Minor="0" />
        <Location ItemUrl="/PerformancePoint/Lists/Dashboard Content" />
        <Actuals>
          <KpiMeasure Guid="6b25b5bc-ffed-4f36-823c-d919b9f4716f" AggregateBy="Default"
DisableScorecardFilters="false" CustomData="" MeasureType="Fixed" ModelCurrent="1"
Pattern="IncreasingIsBetter" CurrentFormula="" IsCustomCurrentFormula="false" OdbcQuery=""
OverrideHoverText="" TimeFilterFormula="" ValueSource="Default">

```

```

<Properties>
  <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="Actual" />
  <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
  <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
</Properties>
<Comments />
<OwnerKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content" />
<DataSourceLocation ItemUrl="/PerformancePoint/Data Sources/1_000"
ItemType="DataSource" ItemGuid="571b7526-4246-4926-b05c-7cla350ce3e2"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7ald-4602-
9a4c-69695440dca4" SpListGuid="d5f0d9e4-7473-4845-820a-920dedeb0593" />
<DefaultDimensionSettings>
  <DefaultDimensionSetting DisplayName="{[Measures].[Measures]}" UniqueName="[Measures]"
IsMeasureDimension="true" DefaultMemberName="" IsVisible="true" ShowAsSlider="false">
    <MeasureGroupNames />
    <Type>Unknown</Type>
    <Hierarchies />
    <Levels>
      <Level DisplayName="MeasureLevel" UniqueName="MeasureLevel"
DimensionUniqueName="[Measures]" IsAllLevel="false" LevelNumber="0" />
    </Levels>
    <Members Caption="Internet Sales Amount" UniqueName="[Measures].[Internet Sales
Amount]" LevelName="[Measures].[MeasuresLevel]" DimensionName="Measures.Measures"
LevelDepth="0" ChildCount="0" IsChildCountReal="false" IsAllLevel="false"
DimensionUniqueName="[Measures]" MemberType="Regular" />
  </DefaultDimensionSetting>
</DefaultDimensionSettings>
<OverrideFormatProperties Multiplier="1" FormatType="Default" DecimalPlaces="0"
NegativeSymbol="NegativeSign" UseThousandsSeparator="true" />
</KpiMeasure>
</Actuals>
<Targets>
  <Target Guid="fla4falf-2474-4746-99e6-660e8dafe1e8" AggregateBy="Default"
DisableScorecardFilters="false" CustomData="" MeasureType="Fixed" ModelCurrent="1"
Pattern="IncreasingIsBetter" IsCustomCurrentFormula="false" OverrideHoverText=""
ValueSource="Default" IsRollupScore="false">
    <Properties>
      <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="Target" />
      <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
      <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
    </Properties>
    <Comments />
    <OwnerKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content" />
    <DataSourceLocation ItemUrl="/%%fixedvalues%%" />
    <DefaultDimensionSettings />
    <OverrideFormatProperties Multiplier="1" FormatType="Default" DecimalPlaces="0"
NegativeSymbol="NegativeSign" UseThousandsSeparator="true" />
    <IndicatorLocation ItemUrl="/PPSBUILTININDICATOR/0_000" />
    <Banding Type="Normalized" ActualWorst="0" SpreadMinimum="0" SpreadMaximum="1.2">

```

```

    <CustomBoundary>
      <decimal>0.50</decimal>
      <decimal>1</decimal>
    </CustomBoundary>
  </Banding>
  <RelatedActualId>6b25b5bc-ffed-4f36-823c-d919b9f4716f</RelatedActualId>
</Target>
</Targets>
</kpi>
</CreateKpi>
</soap:Body>
</soap:Envelope>

```

The server (2) responds with the following (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CreateKpiResponse xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <CreateKpiResult Folder="" CreatedBy="Sample User" CreatedDate="2009-05-21T13:14:28"
ContentTypes="PpsKpi" LastModified="2009-05-21T13:14:28" ModifiedBy="Sample User"
CheckedOutTo="">
        <Properties>
          <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="InternetSales" />
          <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
          <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
        </Properties>
        <Comments />
        <Version Major="1" Minor="0" />
        <Location ItemUrl="/PerformancePoint/Lists/Dashboard Content/4_.000" ItemType="Kpi"
ItemGuid="d4a177e7-721b-4793-981b-94e6b44fb791" SpSiteCollectionGuid="7d7875a5-583b-419c-
ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-9a4c-69695440dca4" SpListGuid="c2f6f377-
a268-4cf1-a9fc-76d4b2ddabe0" />
        <Actuals>
          <KpiMeasure Guid="6b25b5bc-ffed-4f36-823c-d919b9f4716f" AggregateBy="Default"
DisableScorecardFilters="false" CustomData="" MeasureType="Fixed" ModelCurrent="1"
Pattern="IncreasingIsBetter" CurrentFormula="" IsCustomCurrentFormula="false" OdbcQuery=""
OverrideHoverText="" TimeFilterFormula="" ValueSource="Default">
            <Properties>
              <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="Actual" />
              <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
              <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
            </Properties>
            <Comments />
            <OwnerKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/4_.000"
ItemType="Kpi" ItemGuid="d4a177e7-721b-4793-981b-94e6b44fb791"

```

```

SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7ald-4602-
9a4c-69695440dca4" SpListGuid="c2f6f377-a268-4cf1-a9fc-76d4b2ddabe0" />
  <DataSourceLocation ItemUrl="/PerformancePoint/Data Sources/1_.000"
ItemType="DataSource" ItemGuid="571b7526-4246-4926-b05c-7c1a350ce3e2"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7ald-4602-
9a4c-69695440dca4" SpListGuid="d5f0d9e4-7473-4845-820a-920dedeb0593" />
  <DefaultDimensionSettings>
    <DefaultDimensionSetting DisplayName="{[Measures].[Measures]}" UniqueName="[Measures]"
IsMeasureDimension="true" DefaultMemberName="" IsVisible="true" ShowAsSlider="false">
      <MeasureGroupNames />
      <Type>Unknown</Type>
      <Hierarchies />
      <Levels>
        <Level DisplayName="MeasureLevel" UniqueName="MeasureLevel"
DimensionUniqueName="[Measures]" IsAllLevel="false" LevelNumber="0" />
      </Levels>
      <Members Caption="Internet Sales Amount" UniqueName="[Measures].[Internet Sales
Amount]" LevelName="[Measures].[MeasuresLevel]" DimensionName="Measures.Measures"
LevelDepth="0" ChildCount="0" IsChildCountReal="false" IsAllLevel="false"
DimensionUniqueName="[Measures]" MemberType="Regular" />
    </DefaultDimensionSetting>
  </DefaultDimensionSettings>
  <OverrideFormatProperties Multiplier="1" FormatType="Default" DecimalPlaces="0"
NegativeSymbol="NegativeSign" UseThousandsSeparator="true" />
</KpiMeasure>
</Actuals>
<Targets>
  <Target Guid="fla4falf-2474-4746-99e6-660e8dafe1e8" AggregateBy="Default"
DisableScorecardFilters="false" CustomData="" MeasureType="Fixed" ModelCurrent="1"
Pattern="IncreasingIsBetter" IsCustomCurrentFormula="false" OverrideHoverText=""
ValueSource="Default" IsRollupScore="false">
    <Properties>
      <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="Target" />
      <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
      <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
    </Properties>
    <Comments />
    <OwnerKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/4_.000"
ItemType="Kpi" ItemGuid="d4a177e7-721b-4793-981b-94e6b44fb791"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7ald-4602-
9a4c-69695440dca4" SpListGuid="c2f6f377-a268-4cf1-a9fc-76d4b2ddabe0" />
    <DataSourceLocation ItemUrl="/%%fixedvalues%%" />
    <DefaultDimensionSettings />
    <OverrideFormatProperties Multiplier="1" FormatType="Default" DecimalPlaces="0"
NegativeSymbol="NegativeSign" UseThousandsSeparator="true" />
    <IndicatorLocation ItemUrl="/PPSBUILTININDICATOR/0_.000" />
    <Banding Type="Normalized" ActualWorst="0" SpreadMinimum="0" SpreadMaximum="1.2">
      <CustomBoundary>
        <decimal>0.50</decimal>
        <decimal>1</decimal>
      </CustomBoundary>
    </Banding>
    <RelatedActualId>6b25b5bc-ffed-4f36-823c-d919b9f4716f</RelatedActualId>
  </Target>
</Targets>
</CreateKpiResult>

```

```

    </CreateKpiResponse>
  </soap:Body>
</soap:Envelope>

```

4.1.2 GetScorecard

The protocol client then retrieves the scorecard to be updated.

The protocol client creates and sends the following message (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetScorecard xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <location ItemUrl="/PerformancePoint/Lists/Dashboard Content/8_.000" />
    </GetScorecard>
  </soap:Body>
</soap:Envelope>

```

The server (2) responds with the following (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetScorecardResponse xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <GetScorecardResult Folder="" CreatedBy="REDMOND\sbishel" CreatedDate="2009-05-
21T16:42:00" ContentType="PpsScorecard" LastModified="2009-05-21T17:27:39"
ModifiedBy="REDMOND\sbishel" CheckedOutTo="" TemplateType="General"
RendererClassName="Microsoft.PerformancePoint.Scorecards.ServerRendering.ScorecardCtrl,
Microsoft.PerformancePoint.Scorecards.ServerRendering, Version=14.0.0.0, Culture=neutral,
PublicKeyToken=94de0004b6e3fcc5">
        <Properties>
          <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="New Scorecard" />
          <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
          <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
        </Properties>
        <Comments />
        <Version Major="2" Minor="0" />
        <Location ItemUrl="/PerformancePoint/Lists/Dashboard Content/8_.000" ItemType="Scorecard"
ItemGuid="cb692449-f20e-4809-9ee3-e012c78f026e" SpSiteCollectionGuid="7d7875a5-583b-419c-
ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-9a4c-69695440dca4" SpListGuid="c2f6f377-
a268-4cf1-a9fc-76d4b2ddabe0" />
        <ConfiguredViews>
          <ConfiguredView Guid="7675ef55-d456-469e-9381-8c1eddd94c1d" AllowStatusFilter="true"
AllowFilter="true" AllowSort="true" AllowAnnotations="true" EmptyRowsFilterMode="None"
AllowShowDetails="true" ShowInfoToolTips="false" EnableTextwrap="false"
MaintainMemberLevelDepth="true" AllowDynamicRowMemberExpansion="true"
AllowDynamicColumnMemberExpansion="true" AllowRowDrill="true" AllowColumnDrill="true"

```



```

AlwaysShowAnnotationCellFlags="false" ExpandToFitWidth="false" HideScorecard="false"
ShowStatusFiltersByDefault="false">
  <Properties>
    <BpmProperty xsi:type="BpmPropertyText"
    UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
    Description="Name Description" Required="false" Visible="true" Text="Default View" />
    <BpmProperty xsi:type="BpmPropertyLongText"
    UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
    Description="Description Description" Required="false" Visible="true" Text="" />
    <BpmProperty xsi:type="BpmPropertyUser"
    UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
    Description="Person Responsible Description" Required="false" Visible="true" Login="" />
  </Properties>
  <Comments />
  <ToolbarOptions ShowInlineText="true" ShowToolbar="false" ShowPageFilters="true"
  ShowRefresh="true" ShowStatusFilter="true" ShowToolTips="true" ShowCollapse="true"
  ShowMode="true" ShowPrint="true" ShowExpand="true" ShowCellSelection="false"
  AnnotationOnByDefault="true" ShowPageFiltersByDefault="false"
  ShowStatusFilterByDefault="false" ShowToolbarItemsLabel="false" ShowDefaultRollup="true"
  ShowWorstChildRollup="true" ShowIndicatorCount="true" />
  <DataSourceLocation ItemUrl="/%%fixedvalues%%" />
  <GridViewDefinition EmptyCell="" InvalidCell="Error" ShowGridLines="true"
  ShowHiddenHeaders="false" ShowMetricHeaders="true" ShowPlusMinus="true">
    <CornerCellFormatInfo TextWrap="Undefined" VerticalAlignment="Middle"
    HorizontalAlignment="Center">
      <BackColor A="0" R="235" G="243" B="255" />
    </CornerCellFormatInfo>
    <RootRowHeader Id="0" Guid="ffa9ff3b-ea47-4149-8a9e-d5f06d938f2f"
    DefinitionGuid="ffa9ff3b-ea47-4149-8a9e-d5f06d938f2f" DisplayText="" HeaderType="None"
    GroupId="0" Depth="0" LevelDepth="0" DescendantSpan="1" LeafSpan="1" IsCollapsed="false"
    IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
    IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
    MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
    IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
    NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
    IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
    Weight="1" AggregationType="None">
      <Children>
        <GridHeaderItem Id="1" Guid="af0bd13a-2ad5-4470-b81c-14ef2e7cafd3"
        DefinitionGuid="af0bd13a-2ad5-4470-b81c-14ef2e7cafd3" DisplayText="InternetSales"
        DimensionName="Scorecard_" DimensionValue="/PerformancePoint/Lists/Dashboard Content/4_.000"
        HeaderType="Kpi" GroupId="-4" Depth="1" LevelDepth="0" DescendantSpan="0" LeafSpan="1"
        IsCollapsed="false" IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false"
        IsDrillDownDisabled="false" IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
        MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
        IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
        NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
        IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
        Weight="1" AggregationType="None">
          <Children />
          <OverrideIndicatorLocation ItemUrl="" />
          <LinkedKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/4_.000"
          ItemType="Kpi" ItemGuid="d4a177e7-721b-4793-981b-94e6b44fb791"
          SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7ald-4602-
          9a4c-69695440dca4" SpListGuid="c2f6f377-a268-4cf1-a9fc-76d4b2ddabe0" />
          <BpmProperties />
          <TrendIndicatorLocation ItemUrl="" />
        </GridHeaderItem>
      </Children>
      <OverrideIndicatorLocation ItemUrl="" />
      <LinkedKpiLocation ItemUrl="" />
      <BpmProperties />
      <TrendIndicatorLocation ItemUrl="" />

```

```

</RootRowHeader>
<RootColumnHeader Id="0" Guid="ab5c8048-cae2-4054-88bb-917449fda92e"
DefinitionGuid="ab5c8048-cae2-4054-88bb-917449fda92e" DisplayText="" HeaderType="None"
GroupId="0" Depth="0" LevelDepth="-1" DescendantSpan="1" LeafSpan="2" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
  <Children>
    <GridHeaderItem Id="1" Guid="c3d60c40-8627-4a07-8e74-2e9bbc6776c5"
DefinitionGuid="c3d60c40-8627-4a07-8e74-2e9bbc6776c5" DisplayText="Actual"
DimensionName="Scorecard Measures__" DimensionValue="Actual" HeaderType="KpiActual"
GroupId="-2" Depth="1" LevelDepth="-1" DescendantSpan="0" LeafSpan="1" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" KpiTargetName="Actual" AggregationType="None">
      <Children />
      <OverrideIndicatorLocation ItemUrl="" />
      <LinkedKpiLocation ItemUrl="" />
      <BpmProperties />
      <TargetSettings ShowValue="true" ShowActualAsTarget="false"
IgnoreScoreFilter="false">
        <VarianceSettings NumDecimalPlaces="0" VarianceType="VarianceToTarget"
DisplayType="ShowPercent" ShowValue="false" Position="NotDisplayed" />
        <FilterEmptyRows>false</FilterEmptyRows>
        <Position>NotDisplayed</Position>
        <PositionActual>NotDisplayed</PositionActual>
        <ScoreSettings ShowValue="false" ScoreType="Normalized"
RollupType="AverageWeighted" Position="NotDisplayed" />
        <IndicatorSettings ShowImage="true" ShowText="false" ShowForeColor="false"
ShowBackColor="false">
          <Position>Center</Position>
        </IndicatorSettings>
      </TargetSettings>
      <TrendIndicatorLocation ItemUrl="" />
    </GridHeaderItem>
    <GridHeaderItem Id="2" Guid="a6d178eb-68d9-430a-a3ba-0b4cbef77511"
DefinitionGuid="a6d178eb-68d9-430a-a3ba-0b4cbef77511" DisplayText="Target"
DimensionName="Scorecard Measures__" DimensionValue="Target" HeaderType="KpiTarget"
GroupId="-3" Depth="1" LevelDepth="-1" DescendantSpan="0" LeafSpan="1" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" KpiTargetName="Target" AggregationType="None">
      <Children />
      <OverrideIndicatorLocation ItemUrl="" />
      <LinkedKpiLocation ItemUrl="" />
      <BpmProperties />
      <TargetSettings ShowValue="true" ShowActualAsTarget="false"
IgnoreScoreFilter="false">
        <VarianceSettings NumDecimalPlaces="0" VarianceType="VarianceToTarget"
DisplayType="ShowPercent" ShowValue="false" Position="Right" />

```

```

    <FilterEmptyRows>false</FilterEmptyRows>
    <Position>Left</Position>
    <PositionActual>NotDisplayed</PositionActual>
    <ScoreSettings ShowValue="false" ScoreType="Normalized"
RollupType="AverageWeighted" Position="NotDisplayed" />
    <IndicatorSettings ShowImage="true" ShowText="false" ShowForeColor="false"
ShowBackColor="false">
        <Position>Center</Position>
    </IndicatorSettings>
</TargetSettings>
    <TrendIndicatorLocation ItemUrl="" />
</GridHeaderItem>
</Children>
    <OverrideIndicatorLocation ItemUrl="" />
    <LinkedKpiLocation ItemUrl="" />
    <BpmProperties />
    <TrendIndicatorLocation ItemUrl="" />
</RootColumnHeader>
    <DefaultRollupIndicatorId>00000000-0000-0000-0000-
000000000000</DefaultRollupIndicatorId>
    <DefaultRollupIndicatorLocation ItemUrl="" />
    <CellBorderColor A="255" R="208" G="216" B="229" />
</GridViewDefinition>
</ConfiguredView>
</ConfiguredViews>
<EndPoints>
    <EndPoint Category="Axis" UniqueName="EndPoint_Page" DisplayName="Page"
AcceptsMultipleFilterLinks="true" />
    <EndPoint Category="Axis" UniqueName="EndPoint_Row" DisplayName="Row"
AcceptsMultipleFilterLinks="false" />
    <EndPoint Category="Axis" UniqueName="EndPoint_Column" DisplayName="Column"
AcceptsMultipleFilterLinks="false" />
    <EndPoint Category="Axis" UniqueName="EndPoint_TIFormula" DisplayName="TI formula"
AcceptsMultipleFilterLinks="true" />
    <EndPoint Category="Axis" UniqueName="EndPoint_CurrentDate-Time" DisplayName="Current
date-time" AcceptsMultipleFilterLinks="true" />
</EndPoints>
<BeginPoints>
    <ParameterDefinition>
        <ParameterUniqueName>2833def6-63f3-43d5-9bfd-ebd371113b27</ParameterUniqueName>
        <DisplayValues>
            <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">
                <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
                    <xs:complexType>
                        <xs:choice minOccurs="0" maxOccurs="unbounded">
                            <xs:element name="ParameterData" msdata:Locale="en-US">
                                <xs:complexType>
                                    <xs:sequence>
                                        <xs:element name="Key" type="xs:string" minOccurs="0" />
                                        <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                                        <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                                        <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
                                        <xs:element name="KpiId" msprop:ShowColumn="True"
msprop:NotShowColumnForCondVisibility="True" type="xs:string" minOccurs="0" />
                                        <xs:element name="Name" msprop:ShowColumn="True"
msprop:NotShowColumnForCondVisibility="True" type="xs:string" minOccurs="0" />

```

```

        <xs:element name="Description" msprop:ShowColumn="True"
msprop:NotShowColumnForCondVisibility="True" type="xs:string" minOccurs="0" />
        <xs:element name="Person_x0020_Responsible" msprop:ShowColumn="True"
msprop:NotShowColumnForCondVisibility="True" type="xs:string" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
</xs:element>
</xs:choice>
</xs:complexType>
</xs:element>
</xs:schema>
<diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
</DisplayValues>
<CustomDefinition>BeginPoint_Kpi</CustomDefinition>
<ParameterProviderId>ParameterScorecardKpiProvider</ParameterProviderId>
<DisplayName>KPI</DisplayName>
<EmitterType>BothAConditionalVisibilityAndParameterEmitter</EmitterType>
<KeyColumn>Key</KeyColumn>
<ParentKeyColumn>ParentKey</ParentKeyColumn>
<DisplayColumn>DisplayValue</DisplayColumn>
<IsDefaultColumn>IsDefault</IsDefaultColumn>
<DefaultPostFormula />
</ParameterDefinition>
<ParameterDefinition>
<ParameterUniqueName>dd5820fe-d454-4a30-8980-1e37a5bc2341</ParameterUniqueName>
<DisplayValues>
<xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">
    <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
        <xs:complexType>
            <xs:choice minOccurs="0" maxOccurs="unbounded">
                <xs:element name="ParameterData" msdata:Locale="en-US">
                    <xs:complexType>
                        <xs:sequence>
                            <xs:element name="Key" type="xs:string" minOccurs="0" />
                            <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                            <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                            <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
                            <xs:element name="CellDisplay" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                        </xs:sequence>
                    </xs:complexType>
                </xs:element>
            </xs:choice>
        </xs:complexType>
    </xs:element>
</xs:schema>
<diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
</DisplayValues>
<CustomDefinition>BeginPoint_ScorecardCell</CustomDefinition>
<ParameterProviderId>ParameterScorecardCellProvider</ParameterProviderId>
<DisplayName>Cell</DisplayName>
<EmitterType>ParameterEmitter</EmitterType>
<KeyColumn>Key</KeyColumn>
<ParentKeyColumn>ParentKey</ParentKeyColumn>

```

```

    <DisplayColumn>DisplayValue</DisplayColumn>
    <IsDefaultColumn>IsDefault</IsDefaultColumn>
    <DefaultPostFormula />
  </ParameterDefinition>
</ParameterDefinition>
  <ParameterUniqueName>c6441909-fc12-4f5f-1aa-8c5d6729e7de</ParameterUniqueName>
  <DisplayValues>
    <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-com:xml-msprop">
      <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
        <xs:complexType>
          <xs:choice minOccurs="0" maxOccurs="unbounded">
            <xs:element name="ParameterData" msdata:Locale="en-US">
              <xs:complexType>
                <xs:sequence>
                  <xs:element name="Key" type="xs:string" minOccurs="0" />
                  <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                  <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                  <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
                  <xs:element name="MemberUniqueName" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                </xs:sequence>
              </xs:complexType>
            </xs:element>
          </xs:choice>
        </xs:complexType>
      </xs:element>
    </xs:schema>
    <diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
  </DisplayValues>
  <CustomDefinition>BeginPoint_ScorecardRowMember</CustomDefinition>
  <ParameterProviderId>ParameterScorecardRowMemberProvider</ParameterProviderId>
  <DisplayName>Row Member</DisplayName>
  <EmitterType>ParameterEmitter</EmitterType>
  <KeyColumn>Key</KeyColumn>
  <ParentKeyColumn>ParentKey</ParentKeyColumn>
  <DisplayColumn>DisplayValue</DisplayColumn>
  <IsDefaultColumn>IsDefault</IsDefaultColumn>
  <DefaultPostFormula />
</ParameterDefinition>
</ParameterDefinition>
  <ParameterUniqueName>957d3ae6-c5db-4d06-a432-0f5df8d07ce7</ParameterUniqueName>
  <DisplayValues>
    <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-com:xml-msprop">
      <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
        <xs:complexType>
          <xs:choice minOccurs="0" maxOccurs="unbounded">
            <xs:element name="ParameterData" msdata:Locale="en-US">
              <xs:complexType>
                <xs:sequence>
                  <xs:element name="Key" type="xs:string" minOccurs="0" />
                  <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                </xs:sequence>
              </xs:complexType>
            </xs:element>
          </xs:choice>
        </xs:complexType>
      </xs:element>
    </xs:schema>
  </DisplayValues>

```

```

        <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
        <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
        <xs:element name="MemberUniqueName" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
    </xs:sequence>
</xs:complexType>
</xs:element>
</xs:choice>
</xs:complexType>
</xs:element>
</xs:schema>
<diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
</DisplayValues>
<CustomDefinition>BeginPoint_ScorecardColumnMember</CustomDefinition>
<ParameterProviderId>ParameterScorecardColumnMemberProvider</ParameterProviderId>
<DisplayName>Column Member</DisplayName>
<EmitterType>ParameterEmitter</EmitterType>
<KeyColumn>Key</KeyColumn>
<ParentKeyColumn>ParentKey</ParentKeyColumn>
<DisplayColumn>DisplayValue</DisplayColumn>
<IsDefaultColumn>IsDefault</IsDefaultColumn>
<DefaultPostFormula />
</ParameterDefinition>
</BeginPoints>
</GetScorecardResult>
</GetScorecardResponse>
</soap:Body>
</soap:Envelope>

```

4.1.3 UpdateScorecard

The protocol client then calls **UpdateScorecard**. The **GridHeaderItem** section with ID set to 2 has been added to the scorecard returned in the **GetScorecard** example.

The protocol client creates and sends the following message (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <UpdateScorecard xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <scorecard Folder="" CreatedBy="Sample User" CreatedDate="2009-05-21T13:10:54"
ContentTypes="PpsScorecard" LastModified="2009-05-21T13:12:24" ModifiedBy="Sample User"
CheckedOutTo="" TemplateType="General"
RendererClassName="Microsoft.PerformancePoint.Scorecards.ServerRendering.ScorecardCtrl,
Microsoft.PerformancePoint.Scorecards.ServerRendering, Version=14.0.0.0, Culture=neutral,
PublicKeyToken=94de0004b6e3fcc5">
        <Properties>
          <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="MyScorecard" />
          <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
        </Properties>
      </scorecard>
    </UpdateScorecard>
  </soap:Body>
</soap:Envelope>

```

```

    <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
  </Properties>
  <Comments />
  <Version Major="2" Minor="0" />
  <Location ItemUrl="/PerformancePoint/Lists/Dashboard Content/2_.000" ItemType="Scorecard"
ItemGuid="22dd6dc3-247c-43b1-b246-6ab222e9001e" SpSiteCollectionGuid="7d7875a5-583b-419c-
ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-9a4c-69695440dca4" SpListGuid="c2f6f377-
a268-4cf1-a9fc-76d4b2ddabe0" />
  <ConfiguredViews>
    <ConfiguredView Guid="9bb8d042-eff9-415c-baa4-3d0c5507e441" AllowStatusFilter="true"
AllowFilter="true" AllowSort="true" AllowAnnotations="true" EmptyRowsFilterMode="None"
AllowShowDetails="true" ShowInfoToolTips="false" EnableTextwrap="false"
MaintainMemberLevelDepth="true" AllowDynamicRowMemberExpansion="true"
AllowDynamicColumnMemberExpansion="true" AllowRowDrill="true" AllowColumnDrill="true"
AlwaysShowAnnotationCellFlags="false" ExpandToFitWidth="false" HideScorecard="false"
ShowStatusFiltersByDefault="false">
      <Properties>
        <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="Default View" />
        <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
        <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
      </Properties>
      <Comments />
      <ToolbarOptions ShowInlineText="true" ShowToolbar="false" ShowPageFilters="true"
ShowRefresh="true" ShowStatusFilter="true" ShowToolTips="true" ShowCollapse="true"
ShowMode="true" ShowPrint="true" ShowExpand="true" ShowCellSelection="false"
AnnotationOnByDefault="true" ShowPageFiltersByDefault="false"
ShowStatusFilterByDefault="false" ShowToolbarItemsLabel="false" ShowDefaultRollup="true"
ShowWorstChildRollup="true" ShowIndicatorCount="true" />
      <DataSourceLocation ItemUrl="/PerformancePoint/Data Sources/1_.000"
ItemType="DataSource" ItemGuid="571b7526-4246-4926-b05c-7c1a350ce3e2"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-
9a4c-69695440dca4" SpListGuid="d5f0d9e4-7473-4845-820a-920dedeb0593" />
      <GridViewDefinition EmptyCell="" InvalidCell="Error" ShowGridLines="true"
ShowHiddenHeaders="false" ShowMetricHeaders="true" ShowPlusMinus="true">
        <CornerCellFormatInfo TextWrap="Undefined" VerticalAlignment="Middle"
HorizontalAlignment="Center">
          <BackColor A="0" R="235" G="243" B="255" />
        </CornerCellFormatInfo>
        <RootRowHeader Id="0" Guid="fd56bee3-dba4-400b-99e2-f1e14f5956a3"
DefinitionGuid="fd56bee3-dba4-400b-99e2-f1e14f5956a3" DisplayText="" HeaderType="None"
GroupId="0" Depth="0" LevelDepth="0" DescendantSpan="1" LeafSpan="2" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
          <Children>
            <GridHeaderItem Id="1" Guid="b70a0ba9-ea56-4ffa-bc41-bd190f06cc1d"
DefinitionGuid="b70a0ba9-ea56-4ffa-bc41-bd190f06cc1d" DisplayText=""
DimensionName="Scorecard_" DimensionValue="/PerformancePoint/Lists/Dashboard Content/1_.000"
HeaderType="Kpi" GroupId="-1" Depth="1" LevelDepth="0" DescendantSpan="0" LeafSpan="1"
IsCollapsed="false" IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false"
IsDrillDownDisabled="false" IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"

```

```

MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
  <Children />
  <OverrideIndicatorLocation ItemUrl="" />
  <LinkedKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/1_.000"
ItemType="Kpi" ItemGuid="87b809c4-bda0-4670-9c5d-3fbcac4102ab"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7ald-4602-
9a4c-69695440dca4" SpListGuid="c2f6f377-a268-4cfl-a9fc-76d4b2ddabe0" />
  <BpmProperties />
  <TrendIndicatorLocation ItemUrl="" />
</GridHeaderItem>
<GridHeaderItem Id="2" Guid="db9f17e1-a0a3-41d6-a492-56240189204d"
DefinitionGuid="db9f17e1-a0a3-41d6-a492-56240189204d" DisplayText="InternetSales"
DimensionName="Scorecard__" DimensionValue="/PerformancePoint/Lists/Dashboard Content/4_.000"
HeaderType="Kpi" GroupId="-5" Depth="1" LevelDepth="0" DescendantSpan="0" LeafSpan="1"
IsCollapsed="false" IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false"
IsDrillDownDisabled="false" IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
  <Children />
  <OverrideIndicatorLocation ItemUrl="" />
  <LinkedKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/4_.000"
ItemType="Kpi" ItemGuid="d4a177e7-721b-4793-981b-94e6b44fb791"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7ald-4602-
9a4c-69695440dca4" SpListGuid="c2f6f377-a268-4cfl-a9fc-76d4b2ddabe0" />
  <BpmProperties />
  <TrendIndicatorLocation ItemUrl="" />
</GridHeaderItem>
</Children>
<OverrideIndicatorLocation ItemUrl="" />
<LinkedKpiLocation ItemUrl="" />
<BpmProperties />
<TrendIndicatorLocation ItemUrl="" />
</RootRowHeader>
<RootColumnHeader Id="0" Guid="09055f3f-77da-4fb0-9482-d434fa95f81c"
DefinitionGuid="09055f3f-77da-4fb0-9482-d434fa95f81c" DisplayText="" HeaderType="None"
GroupId="0" Depth="0" LevelDepth="-1" DescendantSpan="1" LeafSpan="2" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
  <Children>
    <GridHeaderItem Id="1" Guid="13c063f8-e3ba-459d-a7f9-526fdc3b29de"
DefinitionGuid="13c063f8-e3ba-459d-a7f9-526fdc3b29de" DisplayText="Actual"
DimensionName="Scorecard_Measures__" DimensionValue="Actual" HeaderType="KpiActual"
GroupId="-3" Depth="1" LevelDepth="-1" DescendantSpan="0" LeafSpan="1" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" KpiTargetName="Actual" AggregationType="None">
    <Children />

```



```

        <OverrideIndicatorLocation ItemUrl="" />
        <LinkedKpiLocation ItemUrl="" />
        <BpmProperties />
        <TargetSettings ShowValue="true" ShowActualAsTarget="false"
IgnoreScoreFilter="false">
            <VarianceSettings NumDecimalPlaces="0" VarianceType="VarianceToTarget"
DisplayType="ShowPercent" ShowValue="false" Position="NotDisplayed" />
            <FilterEmptyRows>false</FilterEmptyRows>
            <Position>NotDisplayed</Position>
            <PositionActual>NotDisplayed</PositionActual>
            <ScoreSettings ShowValue="false" ScoreType="Normalized"
RollupType="AverageWeighted" Position="NotDisplayed" />
            <IndicatorSettings ShowImage="true" ShowText="false" ShowForeColor="false"
ShowBackColor="false">
                <Position>Center</Position>
            </IndicatorSettings>
        </TargetSettings>
        <TrendIndicatorLocation ItemUrl="" />
    </GridHeaderItem>
    <GridHeaderItem Id="2" Guid="f6b2afe4-fe5b-47a1-974b-c7e59ab3f80f"
DefinitionGuid="f6b2afe4-fe5b-47a1-974b-c7e59ab3f80f" DisplayText="Target"
DimensionName="Scorecard_Measures__" DimensionValue="Target" HeaderType="KpiTarget"
GroupId="-4" Depth="1" LevelDepth="-1" DescendantSpan="0" LeafSpan="1" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" KpiTargetName="Target" AggregationType="None">
        <Children />
        <OverrideIndicatorLocation ItemUrl="" />
        <LinkedKpiLocation ItemUrl="" />
        <BpmProperties />
        <TargetSettings ShowValue="true" ShowActualAsTarget="false"
IgnoreScoreFilter="false">
            <VarianceSettings NumDecimalPlaces="0" VarianceType="VarianceToTarget"
DisplayType="ShowPercent" ShowValue="false" Position="Right" />
            <FilterEmptyRows>false</FilterEmptyRows>
            <Position>Left</Position>
            <PositionActual>NotDisplayed</PositionActual>
            <ScoreSettings ShowValue="false" ScoreType="Normalized"
RollupType="AverageWeighted" Position="NotDisplayed" />
            <IndicatorSettings ShowImage="true" ShowText="false" ShowForeColor="false"
ShowBackColor="false">
                <Position>Center</Position>
            </IndicatorSettings>
        </TargetSettings>
        <TrendIndicatorLocation ItemUrl="" />
    </GridHeaderItem>
</Children>
<OverrideIndicatorLocation ItemUrl="" />
<LinkedKpiLocation ItemUrl="" />
<BpmProperties />
<TrendIndicatorLocation ItemUrl="" />
</RootColumnHeader>
<DefaultRollupIndicatorId>00000000-0000-0000-0000-
000000000000</DefaultRollupIndicatorId>
    <DefaultRollupIndicatorLocation ItemUrl="" />
    <CellBorderColor A="255" R="208" G="216" B="229" />
</GridViewDefinition>

```

```

    </ConfiguredView>
  </ConfiguredViews>
  <EndPoints>
    <EndPoint Category="Axis" UniqueName="EndPoint_Page" DisplayName="Page"
AcceptsMultipleFilterLinks="true" />
    <EndPoint Category="Axis" UniqueName="EndPoint_Row" DisplayName="Row"
AcceptsMultipleFilterLinks="false" />
    <EndPoint Category="Axis" UniqueName="EndPoint_Column" DisplayName="Column"
AcceptsMultipleFilterLinks="false" />
    <EndPoint Category="Axis" UniqueName="EndPoint_TIFormula" DisplayName="TI formula"
AcceptsMultipleFilterLinks="true" />
    <EndPoint Category="Axis" UniqueName="EndPoint_CurrentDate-Time" DisplayName="Current
date-time" AcceptsMultipleFilterLinks="true" />
  </EndPoints>
  <BeginPoints>
    <ParameterDefinition>
      <ParameterUniqueName>0f6ca5f9-e8d9-4fd9-bf4e-d6aa03f2d745</ParameterUniqueName>
      <DisplayValues>
        <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">
          <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
            <xs:complexType>
              <xs:choice minOccurs="0" maxOccurs="unbounded">
                <xs:element name="ParameterData" msdata:Locale="en-US">
                  <xs:complexType>
                    <xs:sequence>
                      <xs:element name="Key" type="xs:string" minOccurs="0" />
                      <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                      <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                      <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
                      <xs:element name="KpiId" msprop:NotShowColumnForCondVisibility="True"
msprop:ShowColumn="True" type="xs:string" minOccurs="0" />
                      <xs:element name="Name" msprop:NotShowColumnForCondVisibility="True"
msprop:ShowColumn="True" type="xs:string" minOccurs="0" />
                      <xs:element name="Description" msprop:NotShowColumnForCondVisibility="True"
msprop:ShowColumn="True" type="xs:string" minOccurs="0" />
                      <xs:element name="Person_x0020_Responsible"
msprop:NotShowColumnForCondVisibility="True" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                    </xs:sequence>
                  </xs:complexType>
                </xs:element>
              </xs:choice>
            </xs:complexType>
          </xs:element>
        </xs:schema>
        <diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
      </DisplayValues>
      <CustomDefinition>BeginPoint_Kpi</CustomDefinition>
      <ParameterProviderId>ParameterScorecardKpiProvider</ParameterProviderId>
      <DisplayName>KPI</DisplayName>
      <EmitterType>BothAConditionalVisibilityAndParameterEmitter</EmitterType>
      <KeyColumn>Key</KeyColumn>
      <ParentKeyColumn>ParentKey</ParentKeyColumn>
      <DisplayColumn>DisplayValue</DisplayColumn>
      <IsDefaultColumn>IsDefault</IsDefaultColumn>
    </ParameterDefinition>
  </BeginPoints>

```

```

    <DefaultPostFormula />
  </ParameterDefinition>
  <ParameterDefinition>
    <ParameterUniqueName>c9b6e4c4-4f13-4d17-99b9-1b7f77fafd34</ParameterUniqueName>
    <DisplayValues>
      <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">
        <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
          <xs:complexType>
            <xs:choice minOccurs="0" maxOccurs="unbounded">
              <xs:element name="ParameterData" msdata:Locale="en-US">
                <xs:complexType>
                  <xs:sequence>
                    <xs:element name="Key" type="xs:string" minOccurs="0" />
                    <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                    <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                    <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
                    <xs:element name="CellDisplay" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                  </xs:sequence>
                </xs:complexType>
              </xs:element>
            </xs:choice>
          </xs:complexType>
        </xs:element>
      </xs:schema>
      <diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
    </DisplayValues>
    <CustomDefinition>BeginPoint_ScorecardCell</CustomDefinition>
    <ParameterProviderId>ParameterScorecardCellProvider</ParameterProviderId>
    <DisplayName>Cell</DisplayName>
    <EmitterType>ParameterEmitter</EmitterType>
    <KeyColumn>Key</KeyColumn>
    <ParentKeyColumn>ParentKey</ParentKeyColumn>
    <DisplayColumn>DisplayValue</DisplayColumn>
    <IsDefaultColumn>IsDefault</IsDefaultColumn>
    <DefaultPostFormula />
  </ParameterDefinition>
  <ParameterDefinition>
    <ParameterUniqueName>cb138e38-09b0-42e1-8219-b26d3ffba337</ParameterUniqueName>
    <DisplayValues>
      <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">
        <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
          <xs:complexType>
            <xs:choice minOccurs="0" maxOccurs="unbounded">
              <xs:element name="ParameterData" msdata:Locale="en-US">
                <xs:complexType>
                  <xs:sequence>
                    <xs:element name="Key" type="xs:string" minOccurs="0" />
                    <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                    <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                    <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
                  </xs:sequence>
                </xs:complexType>
              </xs:element>
            </xs:choice>
          </xs:complexType>
        </xs:element>
      </xs:schema>
    </DisplayValues>
  </ParameterDefinition>

```

```

        <xs:element name="MemberUniqueName" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:choice>
</xs:complexType>
</xs:element>
</xs:schema>
<diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
</DisplayValues>
<CustomDefinition>BeginPoint_ScorecardRowMember</CustomDefinition>
<ParameterProviderId>ParameterScorecardRowMemberProvider</ParameterProviderId>
<DisplayName>Row Member</DisplayName>
<EmitterType>ParameterEmitter</EmitterType>
<KeyColumn>Key</KeyColumn>
<ParentKeyColumn>ParentKey</ParentKeyColumn>
<DisplayColumn>DisplayValue</DisplayColumn>
<IsDefaultColumn>IsDefault</IsDefaultColumn>
<DefaultPostFormula />
</ParameterDefinition>
<ParameterDefinition>
  <ParameterUniqueName>fbf44bbb-d222-431b-930a-ac41c9a58127</ParameterUniqueName>
  <DisplayValues>
    <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">
      <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
        <xs:complexType>
          <xs:choice minOccurs="0" maxOccurs="unbounded">
            <xs:element name="ParameterData" msdata:Locale="en-US">
              <xs:complexType>
                <xs:sequence>
                  <xs:element name="Key" type="xs:string" minOccurs="0" />
                  <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                  <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                  <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
                  <xs:element name="MemberUniqueName" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                </xs:sequence>
              </xs:complexType>
            </xs:element>
          </xs:choice>
        </xs:complexType>
      </xs:schema>
<diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
</DisplayValues>
<CustomDefinition>BeginPoint_ScorecardColumnMember</CustomDefinition>
<ParameterProviderId>ParameterScorecardColumnMemberProvider</ParameterProviderId>
<DisplayName>Column Member</DisplayName>
<EmitterType>ParameterEmitter</EmitterType>
<KeyColumn>Key</KeyColumn>
<ParentKeyColumn>ParentKey</ParentKeyColumn>
<DisplayColumn>DisplayValue</DisplayColumn>
<IsDefaultColumn>IsDefault</IsDefaultColumn>

```

```

    <DefaultPostFormula />
  </ParameterDefinition>
</BeginPoints>
</scorecard>
</UpdateScorecard>
</soap:Body>
</soap:Envelope>

```

The server (2) responds with the following (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <UpdateScorecardResponse xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <UpdateScorecardResult Folder="" CreatedBy="Sample User" CreatedDate="2009-05-21T13:10:54"
ContentTypes="PpsScorecard" LastModified="2009-05-21T15:39:11" ModifiedBy="Sample User"
CheckedOutTo="" TemplateType="General"
RendererClassName="Microsoft.PerformancePoint.Scorecards.ServerRendering.ScorecardCtrl,
Microsoft.PerformancePoint.Scorecards.ServerRendering, Version=14.0.0.0, Culture=neutral,
PublicKeyToken=94de0004b6e3fcc5">
        <Properties>
          <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="MyScorecard" />
          <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
          <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
        </Properties>
        <Comments />
        <Version Major="3" Minor="0" />
        <Location ItemUrl="/PerformancePoint/Lists/Dashboard Content/2_000" ItemType="Scorecard"
ItemGuid="22dd6dc3-247c-43b1-b246-6ab222e9001e" SpSiteCollectionGuid="7d7875a5-583b-419c-
ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-9a4c-69695440dca4" SpListGuid="c2f6f377-
a268-4cf1-a9fc-76d4b2ddabe0" />
        <ConfiguredViews>
          <ConfiguredView Guid="9bb8d042-eff9-415c-baa4-3d0c5507e441" AllowStatusFilter="true"
AllowFilter="true" AllowSort="true" AllowAnnotations="true" EmptyRowsFilterMode="None"
AllowShowDetails="true" ShowInfoToolTips="false" EnableTextwrap="false"
MaintainMemberLevelDepth="true" AllowDynamicRowMemberExpansion="true"
AllowDynamicColumnMemberExpansion="true" AllowRowDrill="true" AllowColumnDrill="true"
AlwaysShowAnnotationCellFlags="false" ExpandToFitWidth="false" HideScorecard="false"
ShowStatusFiltersByDefault="false">
            <Properties>
              <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="Default View" />
              <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
              <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
            </Properties>
            <Comments />

```

```

<ToolBarOptions ShowInlineText="true" ShowToolBar="false" ShowPageFilters="true"
ShowRefresh="true" ShowStatusFilter="true" ShowToolTips="true" ShowCollapse="true"
ShowMode="true" ShowPrint="true" ShowExpand="true" ShowCellSelection="false"
AnnotationOnByDefault="true" ShowPageFiltersByDefault="false"
ShowStatusFilterByDefault="false" ShowToolBarItemsLabel="false" ShowDefaultRollup="true"
ShowWorstChildRollup="true" ShowIndicatorCount="true" />
<DataSourceLocation ItemUrl="/PerformancePoint/Data Sources/1_.000"
ItemType="DataSource" ItemGuid="571b7526-4246-4926-b05c-7c1a350ce3e2"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-
9a4c-69695440dca4" SpListGuid="d5f0d9e4-7473-4845-820a-920dedeb0593" />
<GridViewDefinition EmptyCell="" InvalidCell="Error" ShowGridLines="true"
ShowHiddenHeaders="false" ShowMetricHeaders="true" ShowPlusMinus="true">
<CornerCellFormatInfo TextWrap="Undefined" VerticalAlignment="Middle"
HorizontalAlignment="Center">
<BackColor A="0" R="235" G="243" B="255" />
</CornerCellFormatInfo>
<RootRowHeader Id="0" Guid="fd56bee3-dba4-400b-99e2-f1e14f5956a3"
DefinitionGuid="fd56bee3-dba4-400b-99e2-f1e14f5956a3" DisplayText="" HeaderType="None"
GroupId="0" Depth="0" LevelDepth="0" DescendantSpan="0" LeafSpan="0" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
<Children>
<GridHeaderItem Id="1" Guid="b70a0ba9-ea56-4ffa-bc41-bd190f06cc1d"
DefinitionGuid="b70a0ba9-ea56-4ffa-bc41-bd190f06cc1d" DisplayText=""
DimensionName="Scorecard__" DimensionValue="/PerformancePoint/Lists/Dashboard Content/1_.000"
HeaderType="Kpi" GroupId="-1" Depth="0" LevelDepth="0" DescendantSpan="0" LeafSpan="0"
IsCollapsed="false" IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false"
IsDrillDownDisabled="false" IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
<Children />
<OverrideIndicatorLocation ItemUrl="" />
<LinkedKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/1_.000"
ItemType="Kpi" ItemGuid="87b809c4-bda0-4670-9c5d-3fbcac4102ab"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-
9a4c-69695440dca4" SpListGuid="c2f6f377-a268-4cfl-a9fc-76d4b2ddabe0" />
<BpmProperties />
<TrendIndicatorLocation ItemUrl="" />
</GridHeaderItem>
<GridHeaderItem Id="2" Guid="db9f17e1-a0a3-41d6-a492-56240189204d"
DefinitionGuid="db9f17e1-a0a3-41d6-a492-56240189204d" DisplayText="InternetSales"
DimensionName="Scorecard__" DimensionValue="/PerformancePoint/Lists/Dashboard Content/4_.000"
HeaderType="Kpi" GroupId="-5" Depth="0" LevelDepth="0" DescendantSpan="0" LeafSpan="0"
IsCollapsed="false" IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false"
IsDrillDownDisabled="false" IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
<Children />
<OverrideIndicatorLocation ItemUrl="" />
<LinkedKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/4_.000"
ItemType="Kpi" ItemGuid="d4a177e7-721b-4793-981b-94e6b44fb791"

```

```

SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7ald-4602-
9a4c-69695440dca4" SpListGuid="c2f6f377-a268-4cf1-a9fc-76d4b2ddabe0" />
  <BpmProperties />
  <TrendIndicatorLocation ItemUrl="" />
</GridHeaderItem>
</Children>
<OverrideIndicatorLocation ItemUrl="" />
<LinkedKpiLocation ItemUrl="" />
<BpmProperties />
<TrendIndicatorLocation ItemUrl="" />
</RootRowHeader>
<RootColumnHeader Id="0" Guid="09055f3f-77da-4fb0-9482-d434fa95f81c"
DefinitionGuid="09055f3f-77da-4fb0-9482-d434fa95f81c" DisplayText="" HeaderType="None"
GroupId="0" Depth="0" LevelDepth="-1" DescendantSpan="0" LeafSpan="0" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
  <Children>
    <GridHeaderItem Id="1" Guid="13c063f8-e3ba-459d-a7f9-526fdc3b29de"
DefinitionGuid="13c063f8-e3ba-459d-a7f9-526fdc3b29de" DisplayText="Actual"
DimensionName="Scorecard_Measures__" DimensionValue="Actual" HeaderType="KpiActual"
GroupId="-3" Depth="0" LevelDepth="-1" DescendantSpan="0" LeafSpan="0" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" KpiTargetName="Actual" AggregationType="None">
      <Children />
      <OverrideIndicatorLocation ItemUrl="" />
      <LinkedKpiLocation ItemUrl="" />
      <BpmProperties />
      <TargetSettings ShowValue="true" ShowActualAsTarget="false"
IgnoreScoreFilter="false">
        <VarianceSettings NumDecimalPlaces="0" VarianceType="VarianceToTarget"
DisplayType="ShowPercent" ShowValue="false" Position="NotDisplayed" />
        <FilterEmptyRows>false</FilterEmptyRows>
        <Position>NotDisplayed</Position>
        <PositionActual>NotDisplayed</PositionActual>
        <ScoreSettings ShowValue="false" ScoreType="Normalized"
RollupType="AverageWeighted" Position="NotDisplayed" />
        <IndicatorSettings ShowImage="true" ShowText="false" ShowForeColor="false"
ShowBackColor="false">
          <Position>Center</Position>
        </IndicatorSettings>
      </TargetSettings>
      <TrendIndicatorLocation ItemUrl="" />
    </GridHeaderItem>
    <GridHeaderItem Id="2" Guid="f6b2afe4-fe5b-47a1-974b-c7e59ab3f80f"
DefinitionGuid="f6b2afe4-fe5b-47a1-974b-c7e59ab3f80f" DisplayText="Target"
DimensionName="Scorecard_Measures__" DimensionValue="Target" HeaderType="KpiTarget"
GroupId="-4" Depth="0" LevelDepth="-1" DescendantSpan="0" LeafSpan="0" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"

```

```

IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" KpiTargetName="Target" AggregationType="None">
  <Children />
  <OverrideIndicatorLocation ItemUrl="" />
  <LinkedKpiLocation ItemUrl="" />
  <BpmProperties />
  <TargetSettings ShowValue="true" ShowActualAsTarget="false"
IgnoreScoreFilter="false">
  <VarianceSettings NumDecimalPlaces="0" VarianceType="VarianceToTarget"
DisplayType="ShowPercent" ShowValue="false" Position="Right" />
  <FilterEmptyRows>>false</FilterEmptyRows>
  <Position>Left</Position>
  <PositionActual>NotDisplayed</PositionActual>
  <ScoreSettings ShowValue="false" ScoreType="Normalized"
RollupType="AverageWeighted" Position="NotDisplayed" />
  <IndicatorSettings ShowImage="true" ShowText="false" ShowForeColor="false"
ShowBackColor="false">
  <Position>Center</Position>
  </IndicatorSettings>
</TargetSettings>
  <TrendIndicatorLocation ItemUrl="" />
</GridHeaderItem>
</Children>
  <OverrideIndicatorLocation ItemUrl="" />
  <LinkedKpiLocation ItemUrl="" />
  <BpmProperties />
  <TrendIndicatorLocation ItemUrl="" />
</RootColumnHeader>
  <DefaultRollupIndicatorId>00000000-0000-0000-0000-
000000000000</DefaultRollupIndicatorId>
  <DefaultRollupIndicatorLocation ItemUrl="" />
  <CellBorderColor A="255" R="208" G="216" B="229" />
</GridViewDefinition>
</ConfiguredView>
</ConfiguredViews>
<EndPoints>
  <EndPoint Category="Axis" UniqueName="EndPoint_Page" DisplayName="Page"
AcceptsMultipleFilterLinks="true" />
  <EndPoint Category="Axis" UniqueName="EndPoint_Row" DisplayName="Row"
AcceptsMultipleFilterLinks="false" />
  <EndPoint Category="Axis" UniqueName="EndPoint_Column" DisplayName="Column"
AcceptsMultipleFilterLinks="false" />
  <EndPoint Category="Axis" UniqueName="EndPoint_TIFormula" DisplayName="TI formula"
AcceptsMultipleFilterLinks="true" />
  <EndPoint Category="Axis" UniqueName="EndPoint_CurrentDate-Time" DisplayName="Current
date-time" AcceptsMultipleFilterLinks="true" />
</EndPoints>
<BeginPoints>
<ParameterDefinition>
  <ParameterUniqueName>0f6ca5f9-e8d9-4fd9-bf4e-d6aa03f2d745</ParameterUniqueName>
<DisplayValues>
  <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">
    <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
      <xs:complexType>
        <xs:choice minOccurs="0" maxOccurs="unbounded">
          <xs:element name="ParameterData" msdata:Locale="en-US">
            <xs:complexType>
              <xs:sequence>

```



```

        <xs:element name="Key" type="xs:string" minOccurs="0" />
        <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
        <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
        <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
        <xs:element name="KpiId" msprop:ShowColumn="True"
msprop:NotShowColumnForCondVisibility="True" type="xs:string" minOccurs="0" />
        <xs:element name="Name" msprop:ShowColumn="True"
msprop:NotShowColumnForCondVisibility="True" type="xs:string" minOccurs="0" />
        <xs:element name="Description" msprop:ShowColumn="True"
msprop:NotShowColumnForCondVisibility="True" type="xs:string" minOccurs="0" />
        <xs:element name="Person_x0020_Responsible" msprop:ShowColumn="True"
msprop:NotShowColumnForCondVisibility="True" type="xs:string" minOccurs="0" />
    </xs:sequence>
</xs:complexType>
</xs:element>
</xs:choice>
</xs:complexType>
</xs:element>
</xs:schema>
<diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
</DisplayValues>
<CustomDefinition>BeginPoint_Kpi</CustomDefinition>
<ParameterProviderId>ParameterScorecardKpiProvider</ParameterProviderId>
<DisplayName>KPI</DisplayName>
<EmitterType>BothAConditionalVisibilityAndParameterEmitter</EmitterType>
<KeyColumn>Key</KeyColumn>
<ParentKeyColumn>ParentKey</ParentKeyColumn>
<DisplayColumn>DisplayValue</DisplayColumn>
<IsDefaultColumn>IsDefault</IsDefaultColumn>
<DefaultPostFormula />
</ParameterDefinition>
<ParameterDefinition>
<ParameterUniqueName>c9b6e4c4-4f13-4d17-99b9-1b7f77fafd34</ParameterUniqueName>
<DisplayValues>
    <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">
        <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
            <xs:complexType>
                <xs:choice minOccurs="0" maxOccurs="unbounded">
                    <xs:element name="ParameterData" msdata:Locale="en-US">
                        <xs:complexType>
                            <xs:sequence>
                                <xs:element name="Key" type="xs:string" minOccurs="0" />
                                <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                                <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                                <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
                                <xs:element name="CellDisplay" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                            </xs:sequence>
                        </xs:complexType>
                    </xs:element>
                </xs:choice>
            </xs:complexType>
        </xs:element>
    </xs:schema>

```

```

    <diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
  </DisplayValues>
  <CustomDefinition>BeginPoint_ScorecardCell</CustomDefinition>
  <ParameterProviderId>ParameterScorecardCellProvider</ParameterProviderId>
  <DisplayName>Cell</DisplayName>
  <EmitterType>ParameterEmitter</EmitterType>
  <KeyColumn>Key</KeyColumn>
  <ParentKeyColumn>ParentKey</ParentKeyColumn>
  <DisplayColumn>DisplayValue</DisplayColumn>
  <IsDefaultColumn>IsDefault</IsDefaultColumn>
  <DefaultPostFormula />
</ParameterDefinition>
<ParameterDefinition>
  <ParameterUniqueName>cb138e38-09b0-42e1-8219-b26d3ffba337</ParameterUniqueName>
  <DisplayValues>
    <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">
      <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
        <xs:complexType>
          <xs:choice minOccurs="0" maxOccurs="unbounded">
            <xs:element name="ParameterData" msdata:Locale="en-US">
              <xs:complexType>
                <xs:sequence>
                  <xs:element name="Key" type="xs:string" minOccurs="0" />
                  <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
                  <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                  <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
                  <xs:element name="MemberUniqueName" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
                </xs:sequence>
              </xs:complexType>
            </xs:element>
          </xs:choice>
        </xs:complexType>
      </xs:schema>
    <diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
  </DisplayValues>
  <CustomDefinition>BeginPoint_ScorecardRowMember</CustomDefinition>
  <ParameterProviderId>ParameterScorecardRowMemberProvider</ParameterProviderId>
  <DisplayName>Row Member</DisplayName>
  <EmitterType>ParameterEmitter</EmitterType>
  <KeyColumn>Key</KeyColumn>
  <ParentKeyColumn>ParentKey</ParentKeyColumn>
  <DisplayColumn>DisplayValue</DisplayColumn>
  <IsDefaultColumn>IsDefault</IsDefaultColumn>
  <DefaultPostFormula />
</ParameterDefinition>
<ParameterDefinition>
  <ParameterUniqueName>fbf44bbb-d222-431b-930a-ac41c9a58127</ParameterUniqueName>
  <DisplayValues>
    <xs:schema id="NewDataSet" xmlns="" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:msdata="urn:schemas-microsoft-com:xml-msdata" xmlns:msprop="urn:schemas-microsoft-
com:xml-msprop">

```

```

    <xs:element name="NewDataSet" msdata:IsDataSet="true"
msdata:MainDataTable="ParameterData" msdata:Locale="en-US">
    <xs:complexType>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element name="ParameterData" msdata:Locale="en-US">
    <xs:complexType>
    <xs:sequence>
    <xs:element name="Key" type="xs:string" minOccurs="0" />
    <xs:element name="ParentKey" type="xs:string" minOccurs="0" />
    <xs:element name="DisplayValue" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
    <xs:element name="IsDefault" type="xs:boolean" minOccurs="0" />
    <xs:element name="MemberUniqueName" msprop:ShowColumn="True" type="xs:string"
minOccurs="0" />
    </xs:sequence>
    </xs:complexType>
    </xs:element>
    </xs:choice>
    </xs:complexType>
    </xs:element>
    </xs:schema>
    <diffgr:diffgram xmlns:msdata="urn:schemas-microsoft-com:xml-msdata"
xmlns:diffgr="urn:schemas-microsoft-com:xml-diffgram-v1" />
    </DisplayValues>
    <CustomDefinition>BeginPoint_ScorecardColumnMember</CustomDefinition>
    <ParameterProviderId>ParameterScorecardColumnMemberProvider</ParameterProviderId>
    <DisplayName>Column Member</DisplayName>
    <EmitterType>ParameterEmitter</EmitterType>
    <KeyColumn>Key</KeyColumn>
    <ParentKeyColumn>ParentKey</ParentKeyColumn>
    <DisplayColumn>DisplayValue</DisplayColumn>
    <IsDefaultColumn>IsDefault</IsDefaultColumn>
    <DefaultPostFormula />
    </ParameterDefinition>
    </BeginPoints>
    </UpdateScorecardResult>
    </UpdateScorecardResponse>
    </soap:Body>
    </soap:Envelope>

```

4.1.4 GenerateView

The protocol client then calls **GenerateView** to get the scorecard result data set.

The protocol client creates and sends the following message (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GenerateView xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <scorecardLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/8_.000" />
      <propertyBags>
        <Keys />
        <Values />
      </propertyBags>
    </GenerateView>
  </soap:Body>
</soap:Envelope>

```

```
</soap:Body>
</soap:Envelope>
```

The server (2) responds with the following (white space added for readability):

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GenerateViewResponse xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <GenerateViewResult ScorecardViewId="7675ef55-d456-469e-9381-8c1eddd94c1d" Cached="false"
DefaultRollupIndicatorId="00000000-0000-0000-0000-000000000000" EmptyCell=""
InvalidCell="Error" TIFormula="" TICurrentDateTime="">
        <Cells>
          <Table>
            <Keys>
              <string>/PerformancePoint/Lists/Dashboard
Content/4_.000:/PerformancePoint/Lists/Dashboard Content/4_.0001_Actual:Actual1_</string>
              <string>/PerformancePoint/Lists/Dashboard
Content/4_.000:/PerformancePoint/Lists/Dashboard Content/4_.0001_Target:Target2_</string>
              <string>Actual:Actual1_</string>
              <string>Target:Target2_</string>
            </Keys>
            <Values>
              <GridCell Value="29358677.2207" ActualValue="29358677.2207" Score="0" Weight="1"
BestChildScore="0" WorstChildScore="0" IsValueInError="false" HasAnnotation="false"
IsRollupScore="false" ValueSource="SourceData" IsValidScore="true">
                <Properties>
                  <Keys />
                  <Values />
                </Properties>
                <DisplayElements>
                  <GridDisplayElement xsi:type="GridDisplayElementActual" Status="0"
Value="29358677.2207" OverrideValue="29358677.2207">
                    <Text>$29,358,677.22</Text>
                    <TooltipText />
                  </GridDisplayElement>
                </DisplayElements>
                <IndicatorLocation ItemUrl="" />
                <InBand>-1</InBand>
              </GridCell>
              <GridCell Value="1" ActualValue="29358677.2207" Score="100" Weight="1"
BestChildScore="100" WorstChildScore="100" IsValueInError="false" HasAnnotation="false"
IsRollupScore="false" ValueSource="SourceData" IsValidScore="true">
                <Properties>
                  <Keys />
                  <Values />
                </Properties>
                <DisplayElements>
                  <GridDisplayElement xsi:type="GridDisplayElementTarget" Status="0" Value="1"
OverrideValue="1">
                    <Text>1</Text>
                    <TooltipText />
                  </GridDisplayElement>
                  <GridDisplayElement xsi:type="GridDisplayElementIndicator" Status="0"
IndicatorBand="3">
                    <Text>On Target</Text>
                    <TooltipText>On Target</TooltipText>
                </DisplayElements>
              </GridCell>
            </Values>
          </Table>
        </Cells>
      </GenerateViewResult>
    </GenerateViewResponse>
  </soap:Body>
</soap:Envelope>
```

```

        <IndicatorLocation ItemUrl="/PPSBUILTININDICATOR/0_.000" />
    </GridDisplayElement>
    <GridDisplayElement xsi:type="GridDisplayElementVariance" Status="0"
Value="29358676.2207" OverrideValue="2935867622">
        <Text>2,935,867,622%</Text>
        <TooltipText />
    </GridDisplayElement>
</DisplayElements>
    <IndicatorLocation ItemUrl="/PPSBUILTININDICATOR/0_.000" />
    <InBand>3</InBand>
</GridCell>
    <GridCell Value="0" ActualValue="0" Score="0" Weight="1" BestChildScore="0"
WorstChildScore="0" IsValueInError="false" HasAnnotation="false" IsRollupScore="false"
ValueSource="Default" IsValidScore="true">
        <Properties>
            <Keys />
            <Values />
        </Properties>
        <DisplayElements />
        <IndicatorLocation ItemUrl="" />
    <InBand>-1</InBand>
</GridCell>
    <GridCell Value="0" ActualValue="0" Score="0" Weight="1" BestChildScore="0"
WorstChildScore="0" IsValueInError="false" HasAnnotation="false" IsRollupScore="false"
ValueSource="Default" IsValidScore="true">
        <Properties>
            <Keys />
            <Values />
        </Properties>
        <DisplayElements />
        <IndicatorLocation ItemUrl="" />
    <InBand>-1</InBand>
</GridCell>
</Values>
</Table>
</Cells>
    <RootRowHeader Id="0" Guid="ffa9ff3b-ea47-4149-8a9e-d5f06d938f2f"
DefinitionGuid="ffa9ff3b-ea47-4149-8a9e-d5f06d938f2f" DisplayText="" HeaderType="None"
GroupId="0" Depth="0" LevelDepth="0" DescendantSpan="1" LeafSpan="1" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
        <Children>
            <GridHeaderItem Id="1" Guid="af0bd13a-2ad5-4470-b81c-14ef2e7cafd3"
DefinitionGuid="af0bd13a-2ad5-4470-b81c-14ef2e7cafd3" DisplayText="InternetSales"
DimensionName="Scorecard__" DimensionValue="/PerformancePoint/Lists/Dashboard Content/4_.000"
HeaderType="Kpi" GroupId="-4" Depth="1" LevelDepth="0" DescendantSpan="0" LeafSpan="1"
IsCollapsed="false" IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false"
IsDrillDownDisabled="false" IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="false" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
                <Children />
            <OverrideIndicatorLocation ItemUrl="" />
        </Children>
    </RootRowHeader>

```

```

    <LinkedKpiLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/4_.000"
ItemType="Kpi" ItemGuid="d4a177e7-721b-4793-981b-94e6b44fb791"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7ald-4602-
9a4c-69695440dca4" SpListGuid="c2f6f377-a268-4cfl-a9fc-76d4b2ddabe0" />
    <BpmProperties />
    <TrendIndicatorLocation ItemUrl="" />
</GridHeaderItem>
</Children>
<OverrideIndicatorLocation ItemUrl="" />
<LinkedKpiLocation ItemUrl="" />
<BpmProperties />
<TrendIndicatorLocation ItemUrl="" />
</RootRowHeader>
<RootColumnHeader Id="0" Guid="ab5c8048-cae2-4054-88bb-917449fda92e"
DefinitionGuid="ab5c8048-cae2-4054-88bb-917449fda92e" DisplayText="" HeaderType="None"
GroupId="0" Depth="0" LevelDepth="-1" DescendantSpan="1" LeafSpan="2" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" AggregationType="None">
    <Children>
        <GridHeaderItem Id="1" Guid="c3d60c40-8627-4a07-8e74-2e9bbc6776c5"
DefinitionGuid="c3d60c40-8627-4a07-8e74-2e9bbc6776c5" DisplayText="Actual"
DimensionName="Scorecard_Measures__" DimensionValue="Actual" HeaderType="KpiActual"
GroupId="-2" Depth="1" LevelDepth="-1" DescendantSpan="0" LeafSpan="1" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"
NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" KpiTargetName="Actual" AggregationType="None">
            <Children />
            <OverrideIndicatorLocation ItemUrl="" />
            <LinkedKpiLocation ItemUrl="" />
            <BpmProperties />
            <TargetSettings ShowValue="true" ShowActualAsTarget="false" IgnoreScoreFilter="false">
                <VarianceSettings NumDecimalPlaces="0" VarianceType="VarianceToTarget"
DisplayType="ShowPercent" ShowValue="false" Position="NotDisplayed" />
                <FilterEmptyRows>false</FilterEmptyRows>
                <Position>NotDisplayed</Position>
                <PositionActual>NotDisplayed</PositionActual>
                <ScoreSettings ShowValue="false" ScoreType="Normalized" RollupType="AverageWeighted"
Position="NotDisplayed" />
                <IndicatorSettings ShowImage="true" ShowText="false" ShowForeColor="false"
ShowBackColor="false">
                    <Position>Center</Position>
                </IndicatorSettings>
            </TargetSettings>
            <TrendIndicatorLocation ItemUrl="" />
        </GridHeaderItem>
        <GridHeaderItem Id="2" Guid="a6d178eb-68d9-430a-a3ba-0b4cbef77511"
DefinitionGuid="a6d178eb-68d9-430a-a3ba-0b4cbef77511" DisplayText="Target"
DimensionName="Scorecard_Measures__" DimensionValue="Target" HeaderType="KpiTarget"
GroupId="-3" Depth="1" LevelDepth="-1" DescendantSpan="0" LeafSpan="1" IsCollapsed="false"
IsDynamicCellExpansionEnabled="false" IsDrillEnabled="false" IsDrillDownDisabled="false"
IsDrillUpDisabled="false" IsDynamicallyExpandedHeader="false"
MaintainMemberLevelDepth="false" IsCellHidden="false" IsPathHidden="false"
IsHiddenBasedOnFilterStatus="false" IsNamedSetInError="false" IsNamedSetEmpty="false"

```

```

NamedSetType="None" UseLinkedElementDisplayText="true" ShowHyperlinkInNewWindow="false"
IsHierarchyHeader="false" IsColumnHeader="true" AppendFilterInfoToHyperlink="false"
Weight="1" KpiTargetName="Target" AggregationType="None">
  <Children />
  <OverrideIndicatorLocation ItemUrl="" />
  <LinkedKpiLocation ItemUrl="" />
  <BpmProperties />
  <TargetSettings ShowValue="true" ShowActualAsTarget="false" IgnoreScoreFilter="false">
    <VarianceSettings NumDecimalPlaces="0" VarianceType="VarianceToTarget"
DisplayType="ShowPercent" ShowValue="false" Position="Right" />
    <FilterEmptyRows>false</FilterEmptyRows>
    <Position>Left</Position>
    <PositionActual>NotDisplayed</PositionActual>
    <ScoreSettings ShowValue="false" ScoreType="Normalized" RollupType="AverageWeighted"
Position="NotDisplayed" />
    <IndicatorSettings ShowImage="true" ShowText="false" ShowForeColor="false"
ShowBackColor="false">
      <Position>Center</Position>
    </IndicatorSettings>
  </TargetSettings>
  <TrendIndicatorLocation ItemUrl="" />
</GridHeaderItem>
</Children>
<OverrideIndicatorLocation ItemUrl="" />
<LinkedKpiLocation ItemUrl="" />
<BpmProperties />
<TrendIndicatorLocation ItemUrl="" />
</RootColumnHeader>
<ScorecardLocation ItemUrl="/PerformancePoint/Lists/Dashboard Content/8_.000"
ItemType="Scorecard" ItemGuid="cb692449-f20e-4809-9ee3-e012c78f026e"
SpSiteCollectionGuid="7d7875a5-583b-419c-ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-
9a4c-69695440dca4" SpListGuid="c2f6f377-a268-4cfl-a9fc-76d4b2ddabe0" />
  <DefaultRollupIndicatorLocation ItemUrl="" />
  <PreQueryTransforms>
    <GridViewTransformReference Id="ExpandNamedSets">
      <Parameters>
        <Keys />
        <Values />
      </Parameters>
    </GridViewTransformReference>
    <GridViewTransformReference Id="MemberTransforms">
      <Parameters>
        <Keys />
        <Values />
      </Parameters>
    </GridViewTransformReference>
    <GridViewTransformReference Id="UpdateDisplayText">
      <Parameters>
        <Keys />
        <Values />
      </Parameters>
    </GridViewTransformReference>
  </PreQueryTransforms>
  <PostQueryTransforms>
    <GridViewTransformReference Id="AnnotationTransform">
      <Parameters>
        <Keys />
        <Values />
      </Parameters>
    </GridViewTransformReference>
  </PostQueryTransforms>

```

```

</PostQueryTransforms>
<PreRenderTransforms>
  <GridViewTransformReference Id="ComputeAggregations">
    <Parameters>
      <Keys />
      <Values />
    </Parameters>
  </GridViewTransformReference>
  <GridViewTransformReference Id="ComputeRollups">
    <Parameters>
      <Keys />
      <Values />
    </Parameters>
  </GridViewTransformReference>
  <GridViewTransformReference Id="FilterEmptyRows">
    <Parameters>
      <Keys />
      <Values />
    </Parameters>
  </GridViewTransformReference>
</PreRenderTransforms>
<PerUserTransforms />
<PageFilters />
</GenerateViewResult>
</GenerateViewResponse>
</soap:Body>
</soap:Envelope>

```

4.1.5 DeleteScorecard

The protocol client then calls **DeleteScorecard** to delete the scorecard.

The protocol client creates and sends the following message (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <DeleteScorecard xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <location ItemUrl="/PerformancePoint/Lists/Dashboard Content/2_.000" ItemType="Scorecard"
        ItemGuid="22dd6dc3-247c-43b1-b246-6ab222e9001e" SpSiteCollectionGuid="7d7875a5-583b-419c-
        ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-9a4c-69695440dca4" SpListGuid="c2f6f377-
        a268-4cf1-a9fc-76d4b2ddabe0" />
    </DeleteScorecard>
  </soap:Body>
</soap:Envelope>

```

The server (2) responds with the following (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <DeleteScorecardResponse xmlns="http://www.microsoft.com/performancepoint/scorecards" />
  </soap:Body>

```



```
</soap:Envelope>
```

4.2 Create and Use a DataSource

This scenario involves the creation of a **DataSource** complex type (section [2.2.4.85](#)). The protocol client creates a **DataSource**, tests connectivity to that **DataSource**, and retrieves dimension (1) data from the **DataSource**.

It is assumed that an analysis server (2) (cubes3) exists with a database (Adventure Works DW) and a cube (Adventure Works).

4.2.1 CreateDataSource

The protocol client calls the **CreateDataSource** operation (section [3.1.4.3](#)) to create a new **DataSource** complex type (section [2.2.4.85](#)).

The protocol client creates and sends the following message (white space added for readability):

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CreateDataSource xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <listUrl>/PerformancePoint/Data Sources</listUrl>
      <dataSource Folder="" CreatedBy="" CreatedDate="2009-05-21T12:59:13"
Contentype="PpsDataSource" LastModified="0001-01-01T00:00:00" ModifiedBy="" CheckedOutTo=""
SourceName="ADOMD.NET" ServerName="cubes3" DatabaseName="Adventure Works DW"
CubeName="Adventure Works" CubeDisplayName="Adventure Works" FormattingDimensionName=""
FormattingDimensionDisplayName="" FormattingDimensionType="Other" ConnectionString=""
Roles="" UseConnectionString="false" ConnectionContext="ConnectAsSharedUser"
PassUserNameAsAdomdCustomData="false" ReadOnly="false" MinutesToCache="10"
ServerMajorVersion="0" SubTypeId="ADOMD.NET">
      <Properties>
        <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="New Data Source" />
        <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
        <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
      </Properties>
      <Comments />
      <Version Major="0" Minor="0" />
      <Location ItemUrl="/PerformancePoint/Data Sources" />
      <Variables />
      <CustomTimeIntelligenceSettings>&lt;?xml version="1.0" encoding="utf-16"?&gt;
&lt;TimeIntelligenceMdxSettings xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"&gt;
  &lt;Enabled&gt;true&lt;/Enabled&gt;
  &lt;ReferenceLevel&gt;None&lt;/ReferenceLevel&gt;
  &lt;ReferenceDateTime&gt;0001-01-01T00:00:00&lt;/ReferenceDateTime&gt;
  &lt;LevelBindings /&gt;
&lt;/TimeIntelligenceMdxSettings&gt;</CustomTimeIntelligenceSettings>
      <DataTableMapping DateAggregationType="Year" CalendarStartMonth="0">
        <ColumnMappings />
      </DataTableMapping>
    </CreateDataSource>
  </soap:Body>
</soap:Envelope>
```

```

    </DataTableMapping>
  </dataSource>
</CreateDataSource>
</soap:Body>
</soap:Envelope>

```

The server (2) responds with the following (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CreateDataSourceResponse xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <CreateDataSourceResult Folder="" CreatedBy="REDMOND\sbishel" CreatedDate="2009-05-
21T12:59:34" ContentType="PpsDataSource" LastModified="2009-05-21T12:59:42"
ModifiedBy="REDMOND\sbishel" CheckedOutTo="" SourceName="ADOMD.NET" ServerName=""
DatabaseName="" CubeName="" CubeDisplayName="" FormattingDimensionName=""
FormattingDimensionDisplayName="" FormattingDimensionType="Other" ConnectionString=""
Roles="" UseConnectionString="false" ConnectionContext="ConnectAsSharedUser"
PassUserNameAsAdomdCustomData="false" ReadOnly="false" MinutesToCache="10"
ServerMajorVersion="0" SubTypeId="ADOMD.NET">
        <Properties>
          <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="New Data Source" />
          <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
          <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
        </Properties>
        <Comments />
        <Version Major="1" Minor="0" />
        <Location ItemUrl="/PerformancePoint/Data Sources/1_000" ItemType="DataSource"
ItemGuid="37f08ea5-2f7c-4eda-9085-f1858f065447" SpSiteCollectionGuid="7d7875a5-583b-419c-
ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-9a4c-69695440dca4" SpListGuid="d5f0d9e4-
7473-4845-820a-920dedeb0593" />
        <Variables />
        <CustomTimeIntelligenceSettings>&lt;?xml version="1.0" encoding="utf-16"?&gt;
&lt;TimeIntelligenceMdxSettings xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"&gt;
          &lt;Enabled&gt;true&lt;/Enabled&gt;
          &lt;ReferenceLevel&gt;None&lt;/ReferenceLevel&gt;
          &lt;ReferenceDateTime&gt;0001-01-01T00:00:00&lt;/ReferenceDateTime&gt;
          &lt;LevelBindings /&gt;
        &lt;/TimeIntelligenceMdxSettings&gt;</CustomTimeIntelligenceSettings>
        <DataTableMapping DateAggregationType="Year" CalendarStartMonth="0">
          <ColumnMappings />
        </DataTableMapping>
      </CreateDataSourceResult>
    </CreateDataSourceResponse>
  </soap:Body>
</soap:Envelope>

```

4.2.2 TestDataSource

The protocol client calls **TestDataSource** to test connectivity to the data source.

The protocol client creates and sends the following message (white space added for readability):

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <TestConnection xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <dataSource Folder="" CreatedBy="REDMOND\sbishel" CreatedDate="2009-05-21T12:59:13"
Content Type="PpsDataSource" LastModified="2009-05-21T13:12:09" ModifiedBy="REDMOND\sbishel"
CheckedOutTo="" SourceName="ADOMD.NET" ServerName="cubes3" DatabaseName="Adventure Works DW"
CubeName="Adventure Works" CubeDisplayName="Adventure Works" FormattingDimensionName=""
FormattingDimensionDisplayName="" FormattingDimensionType="Other" ConnectionString=""
Roles="" UseConnectionString="false" ConnectionContext="ConnectAsSharedUser"
PassUserNameAsAdomdCustomData="false" ReadOnly="false" MinutesToCache="10"
ServerMajorVersion="9" SubTypeId="ADOMD.NET">
        <Properties>
          <BpmProperty xsi:type="BpmPropertyText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Name" DisplayName="Name"
Description="Name Description" Required="false" Visible="true" Text="AdventureWorks" />
          <BpmProperty xsi:type="BpmPropertyLongText"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Description" DisplayName="Description"
Description="Description Description" Required="false" Visible="true" Text="" />
          <BpmProperty xsi:type="BpmPropertyUser"
UniqueName="8dd07d4d87794510afdb1f07664359bc_Element_Owner" DisplayName="Person Responsible"
Description="Person Responsible Description" Required="false" Visible="true" Login="" />
        </Properties>
        <Comments />
        <Version Major="3" Minor="0" />
        <Location ItemUrl="/PerformancePoint/Data Sources/1_000" ItemType="DataSource"
ItemGuid="571b7526-4246-4926-b05c-7c1a350ce3e2" SpSiteCollectionGuid="7d7875a5-583b-419c-
ab90-ca79a98a2083" SpSiteGuid="94d89bc7-7a1d-4602-9a4c-69695440dca4" SpListGuid="d5f0d9e4-
7473-4845-820a-920dedeb0593" />
        <Variables />
        <CustomTimeIntelligenceSettings>&lt;?xml version="1.0" encoding="utf-16"?&gt;
&lt;TimeIntelligenceMdxSettings xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"&gt;
          &lt;Enabled&gt;true&lt;/Enabled&gt;
          &lt;ReferenceLevel&gt;None&lt;/ReferenceLevel&gt;
          &lt;ReferenceDateTime&gt;0001-01-01T00:00:00&lt;/ReferenceDateTime&gt;
          &lt;LevelBindings /&gt;
        &lt;/TimeIntelligenceMdxSettings&gt;</CustomTimeIntelligenceSettings>
        <DataTableMapping DateAggregationType="Year" CalendarStartMonth="0">
          <ColumnMappings />
        </DataTableMapping>
      </dataSource>
    </TestConnection>
  </soap:Body>
</soap:Envelope>
```

The server (2) responds with the following (white space added for readability):

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
```

```

<soap:Body>
  <TestConnectionResponse xmlns="http://www.microsoft.com/performancepoint/scorecards">
    <TestConnectionResult>true</TestConnectionResult>
  </TestConnectionResponse>
</soap:Body>
</soap:Envelope>

```

4.2.3 GetDimensions

The protocol client now calls **GetDimensions** to retrieve the available dimensions (1) from the data source.

The protocol client creates and sends the following message (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetDimensions xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <dataSourceLocation ItemUrl="/PerformancePoint/Data Sources/1_.000" />
    </GetDimensions>
  </soap:Body>
</soap:Envelope>

```

The server (2) responds with the following (white space added for readability):

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetDimensionsFromDataSourceResponse
xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <GetDimensionsFromDataSourceResult>
        <Dimension DisplayName="Account.Account" UniqueName="[Account].[Account]" Description=""
IsMeasureDimension="false" DefaultMemberName="[Account].[Account].[All Accounts]">
          <MeasureGroupNames />
          <Type>Unknown</Type>
          <Hierarchies />
          <Levels>
            <Level DisplayName="(All)" UniqueName="[Account].[Account].[(All)]" Description=""
DimensionUniqueName="[Account].[Account]" IsAllLevel="true" LevelNumber="0" />
            <Level DisplayName="Account" UniqueName="[Account].[Account].[Account]" Description=""
DimensionUniqueName="[Account].[Account]" IsAllLevel="false" LevelNumber="1" />
          </Levels>
        </Dimension>
        <Dimension DisplayName="Account.Account Number" UniqueName="[Account].[Account Number]"
Description="" IsMeasureDimension="false" DefaultMemberName="[Account].[Account Number].[All
Accounts]">
          <MeasureGroupNames />
          <Type>Unknown</Type>
          <Hierarchies />
          <Levels>
            <Level DisplayName="(All)" UniqueName="[Account].[Account Number].[(All)]"
Description="" DimensionUniqueName="[Account].[Account Number]" IsAllLevel="true"
LevelNumber="0" />

```

```

    <Level DisplayName="Account Number" UniqueName="[Account].[Account Number].[Account
Number]" Description="" DimensionUniqueName="[Account].[Account Number]" IsAllLevel="false"
LevelNumber="1" />
  </Levels>
</Dimension>
<Dimension DisplayName="Account.Account Type" UniqueName="[Account].[Account Type]"
Description="" IsMeasureDimension="false" DefaultMemberName="[Account].[Account Type].[All
Accounts]">
  <MeasureGroupNames />
  <Type>Unknown</Type>
  <Hierarchies />
  <Levels>
    <Level DisplayName="(All)" UniqueName="[Account].[Account Type].(All)" Description=""
DimensionUniqueName="[Account].[Account Type]" IsAllLevel="true" LevelNumber="0" />
    <Level DisplayName="Account Type" UniqueName="[Account].[Account Type].[Account Type]"
Description="" DimensionUniqueName="[Account].[Account Type]" IsAllLevel="false"
LevelNumber="1" />
  </Levels>
</Dimension>
<Dimension DisplayName="Account.Accounts" UniqueName="[Account].[Accounts]"
Description="" IsMeasureDimension="false" DefaultMemberName="[Account].[Accounts].&[47]">
  <MeasureGroupNames />
  <Type>Unknown</Type>
  <Hierarchies />
  <Levels>
    <Level DisplayName="Account Level 01" UniqueName="[Account].[Accounts].[Account Level
01]" Description="" DimensionUniqueName="[Account].[Accounts]" IsAllLevel="false"
LevelNumber="0" />
    <Level DisplayName="Account Level 02" UniqueName="[Account].[Accounts].[Account Level
02]" Description="" DimensionUniqueName="[Account].[Accounts]" IsAllLevel="false"
LevelNumber="1" />
    <Level DisplayName="Account Level 03" UniqueName="[Account].[Accounts].[Account Level
03]" Description="" DimensionUniqueName="[Account].[Accounts]" IsAllLevel="false"
LevelNumber="2" />
    <Level DisplayName="Account Level 04" UniqueName="[Account].[Accounts].[Account Level
04]" Description="" DimensionUniqueName="[Account].[Accounts]" IsAllLevel="false"
LevelNumber="3" />
    <Level DisplayName="Account Level 05" UniqueName="[Account].[Accounts].[Account Level
05]" Description="" DimensionUniqueName="[Account].[Accounts]" IsAllLevel="false"
LevelNumber="4" />
    <Level DisplayName="Account Level 06" UniqueName="[Account].[Accounts].[Account Level
06]" Description="" DimensionUniqueName="[Account].[Accounts]" IsAllLevel="false"
LevelNumber="5" />
  </Levels>
</Dimension>
<Dimension DisplayName="Geography.Country" UniqueName="[Geography].[Country]"
Description="" IsMeasureDimension="false" DefaultMemberName="[Geography].[Country].[All
Geographies]">
  <MeasureGroupNames />
  <Type>Unknown</Type>
  <Hierarchies />
  <Levels>
    <Level DisplayName="(All)" UniqueName="[Geography].[Country].(All)" Description=""
DimensionUniqueName="[Geography].[Country]" IsAllLevel="true" LevelNumber="0" />
    <Level DisplayName="Country" UniqueName="[Geography].[Country].[Country]"
Description="" DimensionUniqueName="[Geography].[Country]" IsAllLevel="false" LevelNumber="1"
/>
  </Levels>
</Dimension>

```

```

    <Dimension DisplayName="Geography.Geography" UniqueName="[Geography].[Geography]"
Description="" IsMeasureDimension="false" DefaultMemberName="[Geography].[Geography].[All
Geographies]">
    <MeasureGroupNames />
    <Type>Unknown</Type>
    <Hierarchies />
    <Levels>
    <Level DisplayName="(All)" UniqueName="[Geography].[Geography].(All)" Description=""
DimensionUniqueName="[Geography].[Geography]" IsAllLevel="true" LevelNumber="0" />
    <Level DisplayName="Country" UniqueName="[Geography].[Geography].Country"
Description="" DimensionUniqueName="[Geography].[Geography]" IsAllLevel="false"
LevelNumber="1" />
    <Level DisplayName="State-Province" UniqueName="[Geography].[Geography].State-
Province]" Description="" DimensionUniqueName="[Geography].[Geography]" IsAllLevel="false"
LevelNumber="2" />
    <Level DisplayName="City" UniqueName="[Geography].[Geography].City" Description=""
DimensionUniqueName="[Geography].[Geography]" IsAllLevel="false" LevelNumber="3" />
    <Level DisplayName="Postal Code" UniqueName="[Geography].[Geography].Postal Code"
Description="" DimensionUniqueName="[Geography].[Geography]" IsAllLevel="false"
LevelNumber="4" />
    </Levels>
    </Dimension>
    <Dimension DisplayName="Geography.Postal Code" UniqueName="[Geography].Postal Code"
Description="" IsMeasureDimension="false" DefaultMemberName="[Geography].Postal Code].[All
Geographies]">
    <MeasureGroupNames />
    <Type>Unknown</Type>
    <Hierarchies />
    <Levels>
    <Level DisplayName="(All)" UniqueName="[Geography].Postal Code.(All)"
Description="" DimensionUniqueName="[Geography].Postal Code" IsAllLevel="true"
LevelNumber="0" />
    <Level DisplayName="Postal Code" UniqueName="[Geography].Postal Code.Postal Code"
Description="" DimensionUniqueName="[Geography].Postal Code" IsAllLevel="false"
LevelNumber="1" />
    </Levels>
    </Dimension>
    <Dimension DisplayName="Geography.State-Province" UniqueName="[Geography].State-
Province]" Description="" IsMeasureDimension="false" DefaultMemberName="[Geography].State-
Province].[All Geographies]">
    <MeasureGroupNames />
    <Type>Unknown</Type>
    <Hierarchies />
    <Levels>
    <Level DisplayName="(All)" UniqueName="[Geography].State-Province.(All)"
Description="" DimensionUniqueName="[Geography].State-Province" IsAllLevel="true"
LevelNumber="0" />
    <Level DisplayName="State-Province" UniqueName="[Geography].State-Province.State-
Province]" Description="" DimensionUniqueName="[Geography].State-Province"
IsAllLevel="false" LevelNumber="1" />
    </Levels>
    </Dimension>
    </GetDimensionsFromDataSourceResult>
    </GetDimensionsFromDataSourceResponse>
</soap:Body>
</soap:Envelope>

```

4.2.4 QueryDimensionRootMembersFromDataSource

The protocol client calls **QueryDimensionRootMembers** to retrieve the root members from the "Country" level of the "Geography" dimension (1).

The protocol client creates and sends the following message (white space added for readability):

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <QueryDimensionRootMembers xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <dataSourceLocation ItemUrl="/PerformancePoint/Data Sources/1_.000" />
      <dimensionName>[Geography].[Country]</dimensionName>
    </QueryDimensionRootMembers>
  </soap:Body>
</soap:Envelope>
```

The server (2) responds with the following (white space added for readability):

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <QueryDimensionRootMembersFromDataSourceResponse
xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <QueryDimensionRootMembersFromDataSourceResult>
        <Member Caption="All Geographies" UniqueName="[Geography].[Country].[All Geographies]"
LevelName="[Geography].[Country].[All]" DimensionName="Geography.Country" LevelDepth="0"
ChildCount="6" IsChildCountReal="false" IsAllLevel="true"
DimensionUniqueName="[Geography].[Country]" MemberType="Regular" />
      </QueryDimensionRootMembersFromDataSourceResult>
    </QueryDimensionRootMembersFromDataSourceResponse>
  </soap:Body>
</soap:Envelope>
```

4.2.5 QueryChildMembersFromDataSource

The protocol client calls **QueryChildMembers** to retrieve the child members from the "All Geographies" member of the "Country" level of the "Geography" dimension (1).

The protocol client creates and sends the following message (white space added for readability):

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <QueryChildMembers xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <dataSourceLocation ItemUrl="/PerformancePoint/Data Sources/1_.000" />
      <memberUniqueName>[Geography].[Country].[All Geographies]</memberUniqueName>
    </QueryChildMembers>
  </soap:Body>
</soap:Envelope>
```

The server (2) responds with the following (white space added for readability):

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <QueryChildMembersFromDataSourceResponse
xmlns="http://www.microsoft.com/performancepoint/scorecards">
      <QueryChildMembersFromDataSourceResult>
        <Member Caption="Australia" UniqueName="[Geography].[Country].&[Australia]"
LevelName="[Geography].[Country].[Country]" DimensionName="Geography.Country" LevelDepth="1"
ChildCount="0" IsChildCountReal="false" IsAllLevel="false"
DimensionUniqueName="[Geography].[Country]" MemberType="Regular" />
        <Member Caption="Canada" UniqueName="[Geography].[Country].&[Canada]"
LevelName="[Geography].[Country].[Country]" DimensionName="Geography.Country" LevelDepth="1"
ChildCount="0" IsChildCountReal="false" IsAllLevel="false"
DimensionUniqueName="[Geography].[Country]" MemberType="Regular" />
        <Member Caption="France" UniqueName="[Geography].[Country].&[France]"
LevelName="[Geography].[Country].[Country]" DimensionName="Geography.Country" LevelDepth="1"
ChildCount="0" IsChildCountReal="false" IsAllLevel="false"
DimensionUniqueName="[Geography].[Country]" MemberType="Regular" />
        <Member Caption="Germany" UniqueName="[Geography].[Country].&[Germany]"
LevelName="[Geography].[Country].[Country]" DimensionName="Geography.Country" LevelDepth="1"
ChildCount="0" IsChildCountReal="false" IsAllLevel="false"
DimensionUniqueName="[Geography].[Country]" MemberType="Regular" />
        <Member Caption="United Kingdom" UniqueName="[Geography].[Country].&[United Kingdom]"
LevelName="[Geography].[Country].[Country]" DimensionName="Geography.Country" LevelDepth="1"
ChildCount="0" IsChildCountReal="false" IsAllLevel="false"
DimensionUniqueName="[Geography].[Country]" MemberType="Regular" />
        <Member Caption="United States" UniqueName="[Geography].[Country].&[United States]"
LevelName="[Geography].[Country].[Country]" DimensionName="Geography.Country" LevelDepth="1"
ChildCount="0" IsChildCountReal="false" IsAllLevel="false"
DimensionUniqueName="[Geography].[Country]" MemberType="Regular" />
      </QueryChildMembersFromDataSourceResult>
    </QueryChildMembersFromDataSourceResponse>
  </soap:Body>
</soap:Envelope>
```


5 Security

5.1 Security Considerations for Implementers

Secure Sockets Layer (SSL) is required to securely implement this protocol. The protocol exposes data sources (1) to potential tampering or data disclosure without SSL.

The security permissions for all [FirstClassElement](#) objects are based on the list (1) containing the object.

The security permissions for a [TempReportView](#) or [Annotation](#) are inherited from the parent FirstClassElement objects.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

For ease of implementation, the full WSDL is provided in this appendix.

```
<?xml version="1.0"?>
<wsdl:definitions xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
xmlns:s1="http://microsoft.com/wsdl/types/"
xmlns:tns="http://www.microsoft.com/performancepoint/scorecards"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://www.microsoft.com/performancepoint/scorecards"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <xs:schema xmlns:qdata="http://performancepoint.microsoft.com/OLAPQueryData"
xmlns:query="http://schemas.microsoft.com/performancepoint/2007/03/query"
attributeFormDefault="unqualified" elementFormDefault="qualified"
targetNamespace="http://www.microsoft.com/performancepoint/scorecards">
      <xs:element name="CreateDataSource">
        <xs:complexType>
          <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:complexType name="DataSource">
        <xs:complexContent mixed="false">
          <xs:extension base="tns:FirstClassElement">
            <xs:sequence>
              <xs:element minOccurs="0" maxOccurs="1" name="CustomData" type="xs:string"/>
              <xs:element minOccurs="0" maxOccurs="1" name="CustomTimeIntelligenceSettings"
type="xs:string"/>
              <xs:element minOccurs="0" maxOccurs="1" name="DataTableMapping"
type="tns:DataTableMapping"/>
            </xs:sequence>
            <xs:attribute name="SourceName" type="xs:string"/>
            <xs:attribute name="ServerName" type="xs:string"/>
            <xs:attribute name="DatabaseName" type="xs:string"/>
            <xs:attribute name="CubeName" type="xs:string"/>
            <xs:attribute name="CubeDisplayName" type="xs:string"/>
            <xs:attribute name="FormattingDimensionName" type="xs:string"/>
            <xs:attribute name="FormattingDimensionDisplayName" type="xs:string"/>
            <xs:attribute name="FormattingDimensionType" type="tns:DimensionTypeEnum"
use="required"/>
            <xs:attribute name="ConnectionString" type="xs:string"/>
            <xs:attribute name="Roles" type="xs:string"/>
            <xs:attribute name="UseConnectionString" type="xs:boolean" use="required"/>
            <xs:attribute name="ConnectionContext" type="tns:ConnectionContext"
use="required"/>
            <xs:attribute name="PassUserNameAsAdomdCustomData" type="xs:boolean"
use="required"/>
            <xs:attribute name="ReadOnly" type="xs:boolean" use="required"/>
            <xs:attribute name="MinutesToCache" type="xs:int" use="required"/>
            <xs:attribute name="ServerMajorVersion" type="xs:int" use="required"/>
            <xs:attribute name="SubTypeId" type="xs:string"/>
            <xs:attribute name="TargetApplicationId" type="xs:string"/>
          </xs:extension>
        </xs:complexContent>
      </xs:complexType>
    </xs:schema>
  </wsdl:types>
</wsdl:definitions>
```

```

<xs:complexType name="FirstClassElement" abstract="true">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:Element">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Version"
type="tns:ElementVersion"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Location"
type="tns:RepositoryLocation"/>
      </xs:sequence>
      <xs:attribute name="Folder" type="xs:string"/>
      <xs:attribute name="CreatedBy" type="xs:string"/>
      <xs:attribute name="CreatedDate" type="xs:dateTime" use="required"/>
      <xs:attribute name="ContentType" type="tns:FCOContentType" use="required"/>
      <xs:attribute name="LastModified" type="xs:dateTime" use="required"/>
      <xs:attribute name="ModifiedBy" type="xs:string"/>
      <xs:attribute name="CheckedOutTo" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="Element" abstract="true">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Properties"
type="tns:ArrayOfBpmProperty"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Comments" type="tns:ArrayOfComment"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfBpmProperty">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="BpmProperty" nillable="true"
type="tns:BpmProperty"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="BpmProperty" abstract="true">
  <xs:attribute name="UniqueName" type="xs:string"/>
  <xs:attribute name="DisplayName" type="xs:string"/>
  <xs:attribute name="Description" type="xs:string"/>
  <xs:attribute name="Required" type="xs:boolean" use="required"/>
  <xs:attribute name="Visible" type="xs:boolean" use="required"/>
</xs:complexType>
<xs:complexType name="BpmPropertyUser">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:attribute name="Login" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="BpmPropertyLinkBase">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmProperty">
      <xs:attribute name="Hyperlink" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="BpmPropertyHyperlink">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BpmPropertyLinkBase"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="BpmPropertyHyperlink2">

```

```

    <xs:complexContent mixed="false">
      <xs:extension base="tns:BpmPropertyLinkBase"/>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="BpmPropertyDate">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:BpmProperty">
        <xs:attribute name="Date" type="xs:dateTime" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="BpmPropertyLongText">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:BpmProperty">
        <xs:attribute name="Text" type="xs:string"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="BpmPropertyText">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:BpmProperty">
        <xs:attribute name="Text" type="xs:string"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="BpmPropertyDecimal">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:BpmProperty">
        <xs:attribute name="Decimal" type="xs:decimal" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="BpmPropertyList">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:BpmProperty">
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="ListItems"
type="tns:ArrayOfBpmPropertyListItem"/>
        </xs:sequence>
        <xs:attribute name="SelectedIndex" type="xs:int" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="ArrayOfBpmPropertyListItem">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="BpmPropertyListItem"
nillable="true" type="tns:BpmPropertyListItem"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="BpmPropertyListItem">
    <xs:attribute name="Name" type="xs:string"/>
    <xs:attribute name="Value" type="xs:string"/>
  </xs:complexType>
  <xs:complexType name="BpmPropertyBool">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:BpmProperty">
        <xs:attribute name="Value" type="xs:boolean" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

```

```

</xs:complexType>
<xs:complexType name="ArrayOfComment">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Comment" nillable="true"
type="tns:Comment"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Comment">
  <xs:attribute name="Guid" type="s1:guid" use="required"/>
  <xs:attribute name="CreatedBy" type="xs:string"/>
  <xs:attribute name="CreateDate" type="xs:dateTime" use="required"/>
  <xs:attribute name="Message" type="xs:string"/>
</xs:complexType>
<xs:complexType name="ElementVersion">
  <xs:attribute name="Major" type="xs:int" use="required"/>
  <xs:attribute name="Minor" type="xs:int" use="required"/>
</xs:complexType>
<xs:simpleType name="FCOContentType">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="PpsDashboard"/>
        <xs:enumeration value="PpsScorecard"/>
        <xs:enumeration value="PpsKpi"/>
        <xs:enumeration value="PpsReportView"/>
        <xs:enumeration value="PpsIndicator"/>
        <xs:enumeration value="PpsDataSource"/>
        <xs:enumeration value="PpsFilter"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
<xs:complexType name="DataTableMapping">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="ColumnMappings"
type="tns:ArrayOfDataColumnMapping"/>
    <xs:element minOccurs="0" maxOccurs="1" name="MasterTimeColumn"
type="tns:DataColumnMapping"/>
  </xs:sequence>
  <xs:attribute name="DateAggregationType" type="tns:DateAggregationTypes"
use="required"/>
  <xs:attribute name="CalendarStartMonth" type="xs:int" use="required"/>
</xs:complexType>
<xs:complexType name="ArrayOfDataColumnMapping">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DataColumnMapping"
nillable="true" type="tns:DataColumnMapping"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="DataColumnMapping">
  <xs:attribute name="UniqueName" type="xs:string"/>
  <xs:attribute name="KeyColumnName" type="xs:string"/>
  <xs:attribute name="SourceColumnName" type="xs:string"/>
  <xs:attribute name="FriendlyColumnName" type="xs:string"/>
  <xs:attribute name="ColumnType" type="tns:MappedColumnTypes" use="required"/>
  <xs:attribute name="FactAggregation" type="tns:FactAggregations" use="required"/>
  <xs:attribute name="ColumnDataType" type="tns:MappedColumnDataTypes" use="required"/>
</xs:complexType>

```

```

<xs:simpleType name="MappedColumnTypes">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Ignore"/>
    <xs:enumeration value="Fact"/>
    <xs:enumeration value="Dimension"/>
    <xs:enumeration value="TimeDimension"/>
    <xs:enumeration value="Key"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="FactAggregations">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Average"/>
    <xs:enumeration value="Count"/>
    <xs:enumeration value="Max"/>
    <xs:enumeration value="Min"/>
    <xs:enumeration value="None"/>
    <xs:enumeration value="StDev"/>
    <xs:enumeration value="Sum"/>
    <xs:enumeration value="Variance"/>
    <xs:enumeration value="FirstOccurance"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="MappedColumnDataTypes">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NotSupported"/>
    <xs:enumeration value="Number"/>
    <xs:enumeration value="String"/>
    <xs:enumeration value="DateTime"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DateAggregationTypes">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="Second"/>
        <xs:enumeration value="Minute"/>
        <xs:enumeration value="Hour"/>
        <xs:enumeration value="Day"/>
        <xs:enumeration value="Week"/>
        <xs:enumeration value="Month"/>
        <xs:enumeration value="Quarter"/>
        <xs:enumeration value="Year"/>
        <xs:enumeration value="Semester"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
<xs:simpleType name="DimensionTypeEnum">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Accounts"/>
    <xs:enumeration value="BillOfMaterials"/>
    <xs:enumeration value="Channel"/>
    <xs:enumeration value="Currency"/>
    <xs:enumeration value="Customers"/>
    <xs:enumeration value="Geography"/>
    <xs:enumeration value="Measure"/>
    <xs:enumeration value="Organization"/>
    <xs:enumeration value="Other"/>
  </xs:restriction>
</xs:simpleType>

```

```

        <xs:enumeration value="Products"/>
        <xs:enumeration value="Promotion"/>
        <xs:enumeration value="Quantitative"/>
        <xs:enumeration value="Rates"/>
        <xs:enumeration value="Scenario"/>
        <xs:enumeration value="Time"/>
        <xs:enumeration value="Unknown"/>
        <xs:enumeration value="Utility"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ConnectionContext">
    <xs:restriction base="xs:string">
        <xs:enumeration value="ConnectAsUser"/>
        <xs:enumeration value="ConnectAsSharedUser"/>
        <xs:enumeration value="SecureStoreCredentials"/>
    </xs:restriction>
</xs:simpleType>
<xs:element name="CreateDataSourceResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="CreateDataSourceResult"
type="tns:DataSource"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateDataSource">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateDataSourceResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="UpdateDataSourceResult"
type="tns:DataSource"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetDataSource">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetDataSourceResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetDataSourceResult"
type="tns:DataSource"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteDataSource">
    <xs:complexType>
        <xs:sequence>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="DeleteDataSourceResponse">
    <xs:complexType/>
</xs:element>
<xs:element name="CreateKpi">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="kpi" type="tns:Kpi"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="Kpi">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:FirstClassElement">
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="Actuals"
type="tns:ArrayOfKpiMeasure"/>
                <xs:element minOccurs="0" maxOccurs="1" name="Targets"
type="tns:ArrayOfTarget"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ArrayOfKpiMeasure">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="KpiMeasure" nillable="true"
type="tns:KpiMeasure"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="KpiMeasure">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:SecondClassElement">
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="OwnerKpiLocation"
type="tns:RepositoryLocation"/>
                <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
                <xs:element minOccurs="0" maxOccurs="1" name="DefaultDimensionSettings"
type="tns:ArrayOfDefaultDimensionSetting"/>
                <xs:element minOccurs="0" maxOccurs="1" name="OverrideFormatProperties"
type="tns:KpiNumberFormatProperties"/>
                <xs:element minOccurs="0" maxOccurs="1" name="CalcFormulaInfo"
type="tns:CalculatedFormulaInfo"/>
            </xs:sequence>
            <xs:attribute name="AggregateBy" type="tns:AggregateTypeEnum" use="required"/>
            <xs:attribute name="DisableScorecardFilters" type="xs:boolean" use="required"/>
            <xs:attribute name="ModelCurrent" type="xs:decimal" use="required"/>
            <xs:attribute name="Pattern" type="tns:KpiPattern" use="required"/>
            <xs:attribute name="CurrentFormula" type="xs:string"/>
            <xs:attribute name="IsCustomCurrentFormula" type="xs:boolean" use="required"/>
            <xs:attribute name="OdbcQuery" type="xs:string"/>
            <xs:attribute name="OverrideHoverText" type="xs:string"/>
            <xs:attribute name="TimeFilterFormula" type="xs:string"/>
            <xs:attribute name="ValueSource" type="tns:ValueSources" use="required"/>
        </xs:extension>
    </xs:complexContent>

```



```

    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="SecondClassElement" abstract="true">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:Element">
        <xs:attribute name="Guid" type="s1:guid" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="ArrayOfDefaultDimensionSetting">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="DefaultDimensionSetting"
nillable="true" type="tns:DefaultDimensionSetting"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="DefaultDimensionSetting">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:Dimension">
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="unbounded" name="Members"
type="tns:Member"/>
        </xs:sequence>
        <xs:attribute name="IsVisible" type="xs:boolean" use="required"/>
        <xs:attribute name="ShowAsSlider" type="xs:boolean" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="Dimension">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:NameInfo">
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="MeasureGroupNames"
type="tns:ArrayOfString"/>
          <xs:element minOccurs="1" maxOccurs="1" name="Type"
type="tns:DimensionTypeEnum"/>
          <xs:element minOccurs="0" maxOccurs="1" name="Hierarchies"
type="tns:ArrayOfHierarchy"/>
          <xs:element minOccurs="0" maxOccurs="1" name="Levels" type="tns:ArrayOfLevel"/>
        </xs:sequence>
        <xs:attribute name="IsMeasureDimension" type="xs:boolean" use="required"/>
        <xs:attribute name="DefaultMemberName" type="xs:string"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="NameInfo">
    <xs:attribute name="DisplayName" type="xs:string"/>
    <xs:attribute name="UniqueName" type="xs:string"/>
    <xs:attribute name="Description" type="xs:string"/>
  </xs:complexType>
  <xs:complexType name="Level">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:NameInfo">
        <xs:attribute name="DimensionUniqueName" type="xs:string"/>
        <xs:attribute name="HierarchyUniqueName" type="xs:string"/>
        <xs:attribute name="IsAllLevel" type="xs:boolean" use="required"/>
        <xs:attribute name="LevelNumber" type="xs:int" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

```

```

<xs:complexType name="Hierarchy">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:NameInfo">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Levels" type="tns:ArrayOfLevel"/>
      </xs:sequence>
      <xs:attribute name="DefaultMemberName" type="xs:string"/>
      <xs:attribute name="DimensionUniqueName" type="xs:string"/>
      <xs:attribute name="DisplayFolder" type="xs:string"/>
      <xs:attribute name="HierarchyOrigin" type="tns:HierarchyOrigin" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="ArrayOfLevel">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Level" nillable="true"
type="tns:Level"/>
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="HierarchyOrigin">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="AttributeHierarchy"/>
    <xs:enumeration value="ParentChildHierarchy"/>
    <xs:enumeration value="UserHierarchy"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="ArrayOfString">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfHierarchy">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Hierarchy" nillable="true"
type="tns:Hierarchy"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Member">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="MemberOperation"
type="tns:MemberOperation"/>
  </xs:sequence>
  <xs:attribute name="Caption" type="xs:string"/>
  <xs:attribute name="UniqueName" type="xs:string"/>
  <xs:attribute name="HierarchyPath" type="xs:string"/>
  <xs:attribute name="LevelName" type="xs:string"/>
  <xs:attribute name="DimensionName" type="xs:string"/>
  <xs:attribute name="LevelDepth" type="xs:int" use="required"/>
  <xs:attribute name="ChildCount" type="xs:long" use="required"/>
  <xs:attribute name="IsChildCountReal" type="xs:boolean" use="required"/>
  <xs:attribute name="IsAllLevel" type="xs:boolean" use="required"/>
  <xs:attribute name="DimensionUniqueName" type="xs:string"/>
  <xs:attribute name="MemberType" type="tns:MemberType" use="required"/>
</xs:complexType>
<xs:complexType name="MemberOperation" abstract="true"/>
<xs:complexType name="MemberOperationLeafDescendants">
  <xs:complexContent mixed="false">

```

```

        <xs:extension base="tns:MemberOperation"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="MemberOperationDescendants">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:MemberOperation">
            <xs:attribute name="LevelUniqueName" type="xs:string"/>
            <xs:attribute name="LevelDisplayName" type="xs:string"/>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="MemberOperationHide">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:MemberOperation"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="MemberOperationDrillUp">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:MemberOperation"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="MemberOperationChildren">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:MemberOperation"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="MemberOperationAllDescendants">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:MemberOperation"/>
    </xs:complexContent>
</xs:complexType>
<xs:simpleType name="MemberType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Regular"/>
        <xs:enumeration value="Operation"/>
        <xs:enumeration value="Default"/>
        <xs:enumeration value="Formula"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="KpiNumberFormatProperties">
    <xs:attribute name="Multiplier" type="xs:decimal" use="required"/>
    <xs:attribute name="FormatType" type="tns:FormatType" use="required"/>
    <xs:attribute name="CurrencySymbol" type="xs:string"/>
    <xs:attribute name="DecimalPlaces" type="xs:int" use="required"/>
    <xs:attribute name="NegativeSymbol" type="tns:FormatNegativeSymbol" use="required"/>
    <xs:attribute name="ShowZeroAs" type="xs:string"/>
    <xs:attribute name="UseThousandsSeparator" type="xs:boolean" use="required"/>
    <xs:attribute name="AdditionalTextLeft" type="xs:string"/>
    <xs:attribute name="AdditionalTextRight" type="xs:string"/>
</xs:complexType>
<xs:simpleType name="FormatType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Default"/>
        <xs:enumeration value="Number"/>
        <xs:enumeration value="Currency"/>
        <xs:enumeration value="Percentage"/>
        <xs:enumeration value="Unknown"/>
    </xs:restriction>
</xs:simpleType>

```

```

<xs:simpleType name="FormatNegativeSymbol">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NegativeSign"/>
    <xs:enumeration value="Parenthesis"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="CalculatedFormulaInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="AliasInfoCollection"
type="tns:ArrayOfAliasInfo"/>
  </xs:sequence>
  <xs:attribute name="Formula" type="xs:string"/>
</xs:complexType>
<xs:complexType name="ArrayOfAliasInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="AliasInfo" nillable="true"
type="tns:AliasInfo"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="AliasInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="AliasCalculationInfo"
type="tns:KpiMeasure"/>
  </xs:sequence>
  <xs:attribute name="AliasName" type="xs:string"/>
</xs:complexType>
<xs:simpleType name="AggregateTypeEnum">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default"/>
    <xs:enumeration value="Sum"/>
    <xs:enumeration value="Minimum"/>
    <xs:enumeration value="Maximum"/>
    <xs:enumeration value="Count"/>
    <xs:enumeration value="Average"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="KpiPattern">
  <xs:restriction base="xs:string">
    <xs:enumeration value="IncreasingIsBetter"/>
    <xs:enumeration value="DecreasingIsBetter"/>
    <xs:enumeration value="CloserToTargetIsBetter"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ValueSources">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Default"/>
    <xs:enumeration value="NoValue"/>
    <xs:enumeration value="SourceData"/>
    <xs:enumeration value="Text"/>
    <xs:enumeration value="AverageRollup"/>
    <xs:enumeration value="MinRollup"/>
    <xs:enumeration value="MaxRollup"/>
    <xs:enumeration value="TotalRollup"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="Target">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:KpiMeasure">
      <xs:sequence>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="IndicatorLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="StatedScore"
type="tns:KpiMeasure"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Banding" type="tns:Banding"/>
        <xs:element minOccurs="1" maxOccurs="1" name="RelatedActualId" type="s1:guid"/>
    </xs:sequence>
    <xs:attribute name="IsRollupScore" type="xs:boolean" use="required"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="Banding">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="CustomBoundary"
type="tns:ArrayOfDecimal"/>
    </xs:sequence>
    <xs:attribute name="Type" type="tns:BandType" use="required"/>
    <xs:attribute name="BandValue" type="xs:string"/>
    <xs:attribute name="ActualWorst" type="xs:decimal" use="required"/>
    <xs:attribute name="SpreadMinimum" type="xs:decimal" use="required"/>
    <xs:attribute name="SpreadMaximum" type="xs:decimal" use="required"/>
</xs:complexType>
<xs:complexType name="ArrayOfDecimal">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="decimal" type="xs:decimal"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="BandType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Normalized"/>
        <xs:enumeration value="Actual"/>
        <xs:enumeration value="StatedScore"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="ArrayOfTarget">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="Target" nillable="true"
type="tns:Target"/>
    </xs:sequence>
</xs:complexType>
<xs:element name="CreateKpiResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="CreateKpiResult" type="tns:Kpi"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateKpi">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="kpi" type="tns:Kpi"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateKpiResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="UpdateKpiResult" type="tns:Kpi"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

        </xs:complexType>
    </xs:element>
    <xs:element name="GetKpisFromScorecard">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
type="tns:RepositoryLocation"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="GetKpisFromScorecardResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="GetKpisFromScorecardResult"
type="tns:ArrayOfKpi"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:complexType name="ArrayOfKpi">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="Kpi" nillable="true"
type="tns:Kpi"/>
        </xs:sequence>
    </xs:complexType>
    <xs:element name="GetKpi">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="GetKpiResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="GetKpiResult" type="tns:Kpi"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="DeleteKpi">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="DeleteKpiResponse">
        <xs:complexType/>
    </xs:element>
    <xs:element name="CreateScorecard">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
                <xs:element minOccurs="0" maxOccurs="1" name="scorecard" type="tns:Scorecard"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:complexType name="Scorecard">

```

```

    <xs:complexContent mixed="false">
      <xs:extension base="tns:FirstClassElement">
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="ConfiguredViews"
type="tns:ArrayOfConfiguredView"/>
          <xs:element minOccurs="0" maxOccurs="1" name="EndPoints"
type="tns:ArrayOfEndPoint"/>
          <xs:element minOccurs="0" maxOccurs="1" name="BeginPoints"
type="tns:ArrayOfParameterDefinition"/>
        </xs:sequence>
        <xs:attribute name="RendererClassName" type="xs:string"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="ArrayOfConfiguredView">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="ConfiguredView"
nillable="true" type="tns:ConfiguredView"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ConfiguredView">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:SecondClassElement">
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="unbounded" name="StatusFilters"
type="tns:StatusFilter"/>
          <xs:element minOccurs="0" maxOccurs="1" name="ToolbarOptions"
type="tns:ToolbarOptions"/>
          <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
          <xs:element minOccurs="0" maxOccurs="1" name="GridViewDefinition"
type="tns:GridViewDefinition"/>
        </xs:sequence>
        <xs:attribute name="AllowStatusFilter" type="xs:boolean" use="required"/>
        <xs:attribute name="AllowFilter" type="xs:boolean" use="required"/>
        <xs:attribute name="AllowSort" type="xs:boolean" use="required"/>
        <xs:attribute name="AllowAnnotations" type="xs:boolean" use="required"/>
        <xs:attribute name="EmptyRowsFilterMode" type="tns:ScorecardEmptyRowsFilterMode"
use="required"/>
        <xs:attribute name="AllowShowDetails" type="xs:boolean" use="required"/>
        <xs:attribute name="EnableTextwrap" type="xs:boolean" use="required"/>
        <xs:attribute name="AllowDynamicRowMemberExpansion" type="xs:boolean"
use="required"/>
        <xs:attribute name="AllowDynamicColumnMemberExpansion" type="xs:boolean"
use="required"/>
        <xs:attribute name="AllowRowDrill" type="xs:boolean" use="required"/>
        <xs:attribute name="AllowColumnDrill" type="xs:boolean" use="required"/>
        <xs:attribute name="AlwaysShowAnnotationCellFlags" type="xs:boolean"
use="required"/>
        <xs:attribute name="ExpandToFitWidth" type="xs:boolean" use="required"/>
        <xs:attribute name="HideScorecard" type="xs:boolean" use="required"/>
        <xs:attribute name="ShowStatusFiltersByDefault" type="xs:boolean"
use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="StatusFilter">
    <xs:attribute name="IndicatorLocationGuid" type="s1:guid" use="required"/>
    <xs:attribute name="BandIndex" type="xs:int" use="required"/>
  </xs:complexType>

```

```

<xs:complexType name="ToolbarOptions">
  <xs:attribute name="ShowInlineText" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowToolbar" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowStatusFilter" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowToolTips" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowCollapse" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowMode" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowExpand" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowToolbarItemsLabel" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowDefaultRollup" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowWorstChildRollup" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowIndicatorCount" type="xs:boolean" use="required"/>
</xs:complexType>
<xs:complexType name="GridViewDefinition">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="CornerCellFormatInfo"
type="tns:GridFormatInfo"/>
    <xs:element minOccurs="0" maxOccurs="1" name="RootRowHeader"
type="tns:GridHeaderItem"/>
    <xs:element minOccurs="0" maxOccurs="1" name="RootColumnHeader"
type="tns:GridHeaderItem"/>
    <xs:element minOccurs="1" maxOccurs="1" name="DefaultRollupIndicatorId"
type="s1:guid"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DefaultRollupIndicatorLocation"
type="tns:RepositoryLocation"/>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="PreQueryTransforms"
type="tns:GridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="PostQueryTransforms"
type="tns:GridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="PreRenderTransforms"
type="tns:GridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="PerUserTransforms"
type="tns:GridViewTransformReference"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CellBorderColor"
type="tns:GridColor"/>
  </xs:sequence>
  <xs:attribute name="EmptyCell" type="xs:string"/>
  <xs:attribute name="InvalidCell" type="xs:string"/>
  <xs:attribute name="ShowGridLines" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowHiddenHeaders" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowMetricHeaders" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowPlusMinus" type="xs:boolean" use="required"/>
</xs:complexType>
<xs:complexType name="GridFormatInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="FontInfo" type="tns:GridFontInfo"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ForeColor" type="tns:GridColor"/>
    <xs:element minOccurs="0" maxOccurs="1" name="BackColor" type="tns:GridColor"/>
  </xs:sequence>
  <xs:attribute name="TextWrap" type="tns:Trinary" use="required"/>
  <xs:attribute name="VerticalAlignment" type="tns:VerticalAlignments" use="required"/>
  <xs:attribute name="HorizontalAlignment" type="tns:HorizontalAlignments"
use="required"/>
</xs:complexType>
<xs:complexType name="GridFontInfo">
  <xs:attribute name="FamilyName" type="xs:string"/>
  <xs:attribute name="SizeInPoints" type="xs:float" use="required"/>
  <xs:attribute name="Bold" type="tns:Trinary" use="required"/>
  <xs:attribute name="Italic" type="tns:Trinary" use="required"/>
  <xs:attribute name="Underline" type="tns:Trinary" use="required"/>

```



```

    <xs:attribute name="Strikeout" type="tns:Trinary" use="required"/>
  </xs:complexType>
  <xs:simpleType name="Trinary">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Undefined"/>
      <xs:enumeration value="False"/>
      <xs:enumeration value="True"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="GridColor">
    <xs:attribute name="A" type="xs:unsignedByte" use="required"/>
    <xs:attribute name="R" type="xs:unsignedByte" use="required"/>
    <xs:attribute name="G" type="xs:unsignedByte" use="required"/>
    <xs:attribute name="B" type="xs:unsignedByte" use="required"/>
  </xs:complexType>
  <xs:simpleType name="VerticalAlignments">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Undefined"/>
      <xs:enumeration value="Top"/>
      <xs:enumeration value="Middle"/>
      <xs:enumeration value="Bottom"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="HorizontalAlignments">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Undefined"/>
      <xs:enumeration value="Left"/>
      <xs:enumeration value="Center"/>
      <xs:enumeration value="Right"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="GridHeaderItem">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="HeaderFormatInfo"
type="tns:GridFormatInfo"/>
      <xs:element minOccurs="0" maxOccurs="1" name="CellFormatInfo"
type="tns:GridFormatInfo"/>
      <xs:element minOccurs="0" maxOccurs="1" name="Children"
type="tns:ArrayOfGridHeaderItem"/>
      <xs:element minOccurs="0" maxOccurs="1" name="SerializeTag"/>
      <xs:element minOccurs="0" maxOccurs="1" name="DimensionMember" type="tns:Member"/>
      <xs:element minOccurs="0" maxOccurs="1" name="OverrideIndicatorLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="Banding" type="tns:Banding"/>
      <xs:element minOccurs="0" maxOccurs="1" name="LinkedKpiLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="BpmProperties"
type="tns:ArrayOfBpmProperty"/>
      <xs:element minOccurs="0" maxOccurs="1" name="TargetSettings"
type="tns:GridTargetSettings"/>
      <xs:element minOccurs="0" maxOccurs="1" name="TrendIndicatorLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
    <xs:attribute name="Id" type="xs:int" use="required"/>
    <xs:attribute name="Guid" type="s1:guid" use="required"/>
    <xs:attribute name="DefinitionGuid" type="s1:guid" use="required"/>
    <xs:attribute name="DisplayText" type="xs:string"/>
    <xs:attribute name="DimensionName" type="xs:string"/>
    <xs:attribute name="DimensionValue" type="xs:string"/>
    <xs:attribute name="HeaderType" type="tns:ScorecardNodeTypes" use="required"/>
  </xs:complexType>

```

```

<xs:attribute name="GroupId" type="xs:int" use="required"/>
<xs:attribute name="Depth" type="xs:int" use="required"/>
<xs:attribute name="DescendantSpan" type="xs:int" use="required"/>
<xs:attribute name="LeafSpan" type="xs:int" use="required"/>
<xs:attribute name="IsCollapsed" type="xs:boolean" use="required"/>
<xs:attribute name="IsDynamicCellExpansionEnabled" type="xs:boolean" use="required"/>
<xs:attribute name="IsDrillEnabled" type="xs:boolean" use="required"/>
<xs:attribute name="IsDrillDownDisabled" type="xs:boolean" use="required"/>
<xs:attribute name="IsDrillUpDisabled" type="xs:boolean" use="required"/>
<xs:attribute name="IsDynamicallyExpandedHeader" type="xs:boolean" use="required"/>
<xs:attribute name="IsCellHidden" type="xs:boolean" use="required"/>
<xs:attribute name="IsPathHidden" type="xs:boolean" use="required"/>
<xs:attribute name="IsHiddenBasedOnFilterStatus" type="xs:boolean" use="required"/>
<xs:attribute name="NamedSetExpression" type="xs:string"/>
<xs:attribute name="CustomSetFormula" type="xs:string"/>
<xs:attribute name="IsNamedSetInError" type="xs:boolean" use="required"/>
<xs:attribute name="IsNamedSetEmpty" type="xs:boolean" use="required"/>
<xs:attribute name="NamedSetType" type="tns:ScorecardNamedSetType" use="required"/>
<xs:attribute name="UseLinkedElementDisplayText" type="xs:boolean" use="required"/>
<xs:attribute name="Hyperlink" type="xs:string"/>
<xs:attribute name="ShowHyperlinkInNewWindow" type="xs:boolean" use="required"/>
<xs:attribute name="IsHierarchyHeader" type="xs:boolean" use="required"/>
<xs:attribute name="IsColumnHeader" type="xs:boolean" use="required"/>
<xs:attribute name="AppendFilterInfoToHyperlink" type="xs:boolean" use="required"/>
<xs:attribute name="Weight" type="xs:decimal" use="required"/>
<xs:attribute name="KpiTargetName" type="xs:string"/>
<xs:attribute name="AggregationType" type="tns:HeaderAggregationTypes"
use="required"/>
</xs:complexType>
<xs:complexType name="ArrayOfGridHeaderItem">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="GridHeaderItem"
nillable="true" type="tns:GridHeaderItem"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="GridTargetSettings">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="VarianceSettings"
type="tns:GridVarianceSettings"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FilterEmptyRows" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Position"
type="tns:DataValuePosition"/>
    <xs:element minOccurs="1" maxOccurs="1" name="PositionActual"
type="tns:DataValuePosition"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ScoreSettings"
type="tns:GridScoreSettings"/>
    <xs:element minOccurs="0" maxOccurs="1" name="IndicatorSettings"
type="tns:GridIndicatorSettings"/>
  </xs:sequence>
  <xs:attribute name="ShowValue" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowActualAsTarget" type="xs:boolean" use="required"/>
  <xs:attribute name="IgnoreScoreFilter" type="xs:boolean" use="required"/>
</xs:complexType>
<xs:complexType name="GridVarianceSettings">
  <xs:attribute name="NumDecimalPlaces" type="xs:int" use="required"/>
  <xs:attribute name="VarianceType" type="tns:VarianceType" use="required"/>
  <xs:attribute name="DisplayType" type="tns:VarianceDisplayType" use="required"/>
  <xs:attribute name="ShowValue" type="xs:boolean" use="required"/>
  <xs:attribute name="Position" type="tns:DataValuePosition" use="required"/>

```

```

</xs:complexType>
<xs:simpleType name="VarianceType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="VarianceToTarget"/>
    <xs:enumeration value="VarianceToBestTarget"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="VarianceDisplayType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="ShowPercent"/>
    <xs:enumeration value="ShowValue"/>
    <xs:enumeration value="ShowInvertedPercent"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="DataValuePosition">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Left"/>
    <xs:enumeration value="Right"/>
    <xs:enumeration value="NotDisplayed"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="GridScoreSettings">
  <xs:attribute name="ShowValue" type="xs:boolean" use="required"/>
  <xs:attribute name="ScoreType" type="tns:ScoreTypes" use="required"/>
  <xs:attribute name="RollupType" type="tns:RollupTypes" use="required"/>
  <xs:attribute name="Position" type="tns:DataValuePosition" use="required"/>
</xs:complexType>
<xs:simpleType name="ScoreTypes">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Normalized"/>
    <xs:enumeration value="Raw"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="RollupTypes">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="AverageWeighted"/>
    <xs:enumeration value="WorstChild"/>
    <xs:enumeration value="IndicatorCount"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="GridIndicatorSettings">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Position"
type="tns:IndicatorPosition"/>
  </xs:sequence>
  <xs:attribute name="ShowImage" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowText" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowForeColor" type="xs:boolean" use="required"/>
  <xs:attribute name="ShowBackColor" type="xs:boolean" use="required"/>
</xs:complexType>
<xs:simpleType name="IndicatorPosition">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Left"/>
    <xs:enumeration value="Right"/>
    <xs:enumeration value="Center"/>
    <xs:enumeration value="NotDisplayed"/>
  </xs:restriction>
</xs:simpleType>

```

```

<xs:simpleType name="ScorecardNodeTypes">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="Member"/>
        <xs:enumeration value="Kpi"/>
        <xs:enumeration value="KpiActual"/>
        <xs:enumeration value="KpiTarget"/>
        <xs:enumeration value="ScorecardDetails"/>
        <xs:enumeration value="DocumentLinks"/>
        <xs:enumeration value="NamedSet"/>
        <xs:enumeration value="Aggregate"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
<xs:simpleType name="ScorecardNamedSetType">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="NamedSet"/>
        <xs:enumeration value="CustomFormula"/>
        <xs:enumeration value="TimeFormula"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
<xs:simpleType name="HeaderAggregationTypes">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Sum"/>
    <xs:enumeration value="Average"/>
    <xs:enumeration value="Min"/>
    <xs:enumeration value="Max"/>
    <xs:enumeration value="Trend"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="GridViewTransformReference">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Parameters" type="tns:PropertyBag"/>
  </xs:sequence>
  <xs:attribute name="Id" type="xs:string"/>
</xs:complexType>
<xs:complexType name="PropertyBag">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Keys" type="tns:ArrayOfString"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Values" type="tns:ArrayOfChoice1"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfChoice1">
  <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element minOccurs="1" maxOccurs="1" name="char" type="s1:char"/>
    <xs:element minOccurs="1" maxOccurs="1" name="int" type="xs:int"/>
    <xs:element minOccurs="1" maxOccurs="1" name="double" type="xs:double"/>
    <xs:element minOccurs="1" maxOccurs="1" name="string" nillable="true"
type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="dateTime" type="xs:dateTime"/>
  </xs:choice>
</xs:complexType>

```

```

        <xs:element minOccurs="1" maxOccurs="1" name="ArrayOfMemberTransform"
nillable="true" type="tns:ArrayOfMemberTransform"/>
        <xs:element minOccurs="1" maxOccurs="1" name="guid" type="s1:guid"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ArrayOfString" nillable="true"
type="tns:ArrayOfString"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ArrayOfMember" nillable="true"
type="tns:ArrayOfMember"/>
        <xs:element minOccurs="1" maxOccurs="1" name="decimal" type="xs:decimal"/>
    </xs:choice>
</xs:complexType>
<xs:complexType name="ArrayOfMemberTransform">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="MemberTransform"
nillable="true" type="tns:MemberTransform"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="MemberTransform">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="GroupId" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CellPath" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Type"
type="tns:MemberTransformType"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Operation"
type="tns:MemberTransformOperation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CustomData" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="MemberTransformType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Row"/>
        <xs:enumeration value="Column"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="MemberTransformOperation">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Replace"/>
        <xs:enumeration value="DrillUp"/>
        <xs:enumeration value="DrillDown"/>
        <xs:enumeration value="Expand"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="ArrayOfMember">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="Member" nillable="true"
type="tns:Member"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="ScorecardEmptyRowsFilterMode">
    <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="AllValuesAreEmpty"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="ArrayOfEndPoint">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="EndPoint" nillable="true"
type="tns:EndPoint"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="EndPoint">

```

```

    <xs:attribute name="Category" type="tns:EndPointCategory" use="required"/>
    <xs:attribute name="UniqueName" type="xs:string"/>
    <xs:attribute name="DisplayName" type="xs:string"/>
    <xs:attribute name="AcceptsMultipleFilterLinks" type="xs:boolean" use="required"/>
  </xs:complexType>
  <xs:simpleType name="EndPointCategory">
    <xs:restriction base="xs:string">
      <xs:enumeration value="None"/>
      <xs:enumeration value="Axis"/>
      <xs:enumeration value="ColumnHierarchy"/>
      <xs:enumeration value="RowHierarchy"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="ArrayOfParameterDefinition">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="ParameterDefinition"
nillable="true" type="tns:ParameterDefinition"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ParameterDefinition">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="ParameterUniqueName"
type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="DisplayValues">
        <xs:complexType>
          <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded"
namespace="http://www.w3.org/2001/XMLSchema" processContents="lax"/>
            <xs:any minOccurs="1" namespace="urn:schemas-microsoft-com:xml-diffgram-v1"
processContents="lax"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element minOccurs="0" maxOccurs="1" name="CustomDefinition" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="ParameterProviderId"
type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="DisplayName" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="EmitterType"
type="tns:BeginPointEmitterType"/>
      <xs:element minOccurs="0" maxOccurs="1" name="KeyColumn" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="ParentKeyColumn" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="DisplayColumn" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="IsDefaultColumn" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="DefaultPostFormula"
type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:simpleType name="BeginPointEmitterType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="BothAConditionalVisibilityAndParameterEmitter"/>
      <xs:enumeration value="ConditionalVisibilityEmitter"/>
      <xs:enumeration value="ParameterEmitter"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="CreateScorecardResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="CreateScorecardResult"
type="tns:Scorecard"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>

```

```

    </xs:complexType>
  </xs:element>
  <xs:element name="UpdateScorecard">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="scorecard" type="tns:Scorecard"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="UpdateScorecardResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="UpdateScorecardResult"
type="tns:Scorecard"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetScorecard">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetScorecardResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="GetScorecardResult"
type="tns:Scorecard"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="DeleteScorecard">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="DeleteScorecardResponse">
    <xs:complexType/>
  </xs:element>
  <xs:element name="CreateFilter">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="filter" type="tns:Filter"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="Filter">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:FirstClassElement">
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="BeginPoints"
type="tns:ArrayOfParameterDefinition"/>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CustomData" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="EndPoints"
type="tns:ArrayOfEndPoint"/>
    </xs:sequence>
    <xs:attribute name="SubTypeId" type="xs:string"/>
    <xs:attribute name="ReadOnly" type="xs:boolean" use="required"/>
    <xs:attribute name="SelectionMode" type="tns:FilterSelectionMode"
use="required"/>
    <xs:attribute name="Visualization" type="xs:string"/>
    <xs:attribute name="RendererClassName" type="xs:string"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:simpleType name="FilterSelectionMode">
    <xs:restriction base="xs:string">
        <xs:enumeration value="SingleSelect"/>
        <xs:enumeration value="MultiSelect"/>
    </xs:restriction>
</xs:simpleType>
<xs:element name="CreateFilterResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="CreateFilterResult"
type="tns:Filter"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateFilter">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="filter" type="tns:Filter"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateFilterResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="UpdateFilterResult"
type="tns:Filter"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetFilter">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetFilterResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetFilterResult"
type="tns:Filter"/>
        </xs:sequence>
    </xs:complexType>

```



```

</xs:element>
<xs:element name="DeleteFilter">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DeleteFilterResponse">
  <xs:complexType/>
</xs:element>
<xs:element name="CreateIndicator">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="indicator" type="tns:Indicator"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:complexType name="Indicator">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:FirstClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="NoDataIndicatorBand"
type="tns:IndicatorBand"/>
        <xs:element minOccurs="0" maxOccurs="1" name="IndicatorBands"
type="tns:ArrayOfIndicatorBand"/>
      </xs:sequence>
      <xs:attribute name="IndicatorType" type="tns:IndicatorType" use="required"/>
      <xs:attribute name="IsBuiltIn" type="xs:boolean" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="IndicatorBand">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="ImageData" type="xs:string"/>
  </xs:sequence>
  <xs:attribute name="Color" type="xs:string"/>
  <xs:attribute name="BackColor" type="xs:string"/>
  <xs:attribute name="ToolTip" type="xs:string"/>
</xs:complexType>
<xs:complexType name="ArrayOfIndicatorBand">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="IndicatorBand"
nillable="true" type="tns:IndicatorBand"/>
  </xs:sequence>
</xs:complexType>
<xs:simpleType name="IndicatorType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Standard"/>
    <xs:enumeration value="Centered"/>
  </xs:restriction>
</xs:simpleType>
<xs:element name="CreateIndicatorResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateIndicatorResult"
type="tns:Indicator"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateIndicator">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="indicator" type="tns:Indicator"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateIndicatorResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="UpdateIndicatorResult"
type="tns:Indicator"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetIndicator">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetIndicatorResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetIndicatorResult"
type="tns:Indicator"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteIndicator">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteIndicatorResponse">
    <xs:complexType/>
</xs:element>
<xs:element name="CreateReportView">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="reportView" type="tns:ReportView"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="ReportView">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:FirstClassElement">
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="ScorecardLocation"
type="tns:RepositoryLocation"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="CustomData" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="EndPoints"
type="tns:ArrayOfEndPoint"/>
        <xs:element minOccurs="0" maxOccurs="1" name="BeginPoints"
type="tns:ArrayOfParameterDefinition"/>
    </xs:sequence>
    <xs:attribute name="TypeName" type="xs:string"/>
    <xs:attribute name="RenderClientSide" type="xs:boolean" use="required"/>
    <xs:attribute name="ConfiguredViewId" type="s1:guid" use="required"/>
    <xs:attribute name="SubTypeId" type="xs:string"/>
    <xs:attribute name="RendererClassName" type="xs:string"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="CreateReportViewResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="CreateReportViewResult"
type="tns:ReportView"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateReportView">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="reportView" type="tns:ReportView"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateReportViewResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="UpdateReportViewResult"
type="tns:ReportView"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetReportView">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetReportViewResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetReportViewResult"
type="tns:ReportView"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteReportView">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

    </xs:complexType>
  </xs:element>
  <xs:element name="DeleteReportViewResponse">
    <xs:complexType/>
  </xs:element>
  <xs:element name="GetAnalyticReportView">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="analyticReportViewLocation"
type="tns:RepositoryLocation"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetAnalyticReportViewResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="GetAnalyticReportViewResult"
type="tns:ReportView"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetLatestAnalyticReportVersion">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="analyticReportViewId"
type="s1:guid"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetLatestAnalyticReportVersionResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1"
name="GetLatestAnalyticReportVersionResult" type="xs:int"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="SaveTemporaryAnalyticReport">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="reportView" type="tns:ReportView"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="SaveTemporaryAnalyticReportResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="SaveTemporaryAnalyticReportResult"
type="s1:guid"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetQueryResultMembers">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="analyticReportViewLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="formattingDimensionName"
type="xs:string"/>

```

```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetQueryResultMembersResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetQueryResultMembersResult"
type="tns:ArrayOfMember"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetAnnotation">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
type="tns:RepositoryLocation"/>
            <xs:element minOccurs="0" maxOccurs="1" name="tupleCollection"
type="tns:ArrayOfTuple"/>
            <xs:element minOccurs="0" maxOccurs="1" name="cellPath" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="ArrayOfTuple">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="Tuple" nillable="true"
type="tns:Tuple"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Tuple">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="DimensionMembers"
type="tns:ArrayOfMember"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Annotation">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Comments"
type="tns:ArrayOfAnnotationComment"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Properties"
type="tns:ArrayOfBpmProperty"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Owner" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="LastUpdatedBy" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Slice" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="CreatedOn" type="xs:dateTime"/>
        <xs:element minOccurs="1" maxOccurs="1" name="LastUpdatedOn" type="xs:dateTime"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ScorecardLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ConfiguredViewID" type="s1:guid"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Guid" type="s1:guid"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CellpathCoordinates"
type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Version"
type="tns:AnnotationVersions"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfAnnotationComment">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="AnnotationComment"
nillable="true" type="tns:AnnotationComment"/>
    </xs:sequence>

```

```

</xs:complexType>
<xs:complexType name="AnnotationComment">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:Comment">
      <xs:attribute name="Title" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="AnnotationVersions">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Office14Beta2"/>
    <xs:enumeration value="Office14Beta1"/>
    <xs:enumeration value="Pps2007"/>
  </xs:restriction>
</xs:simpleType>
<xs:element name="GetAnnotationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetAnnotationResult"
type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetAnnotationByID">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="annotationID" type="s1:guid"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetAnnotationByIDResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetAnnotationByIDResult"
type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetAllAnnotationsByScorecardLocation">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:complexType name="ArrayOfAnnotation">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Annotation" nillable="true"
type="tns:Annotation"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="GetAllAnnotationsByScorecardLocationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1"
name="GetAllAnnotationsByScorecardLocationResult" type="tns:ArrayOfAnnotation"/>
    </xs:sequence>
  </xs:complexType>

```

```

</xs:element>
<xs:element name="CreateAnnotation">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="annotation" type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CreateAnnotationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateAnnotationResult"
type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="UpdateAnnotation">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="annotation" type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="UpdateAnnotationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateAnnotationResult"
type="tns:Annotation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DeleteAnnotation">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="annotationID" type="s1:guid"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DeleteAnnotationResponse">
  <xs:complexType/>
</xs:element>
<xs:element name="TrimAnnotationByScorecardLocation">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="TrimAnnotationByScorecardLocationResponse">
  <xs:complexType/>
</xs:element>
<xs:element name="TrimAnnotationByOwner">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="Owner" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

<xs:element name="TrimAnnotationByOwnerResponse">
  <xs:complexType/>
</xs:element>
<xs:element name="TrimAnnotationUntouchedSince">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="untouchedSince"
type="xs:dateTime"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="TrimAnnotationUntouchedSinceResponse">
  <xs:complexType/>
</xs:element>
<xs:element name="GetDatabaseNamesFromDataSource">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetDatabaseNamesFromDataSourceResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1"
name="GetDatabaseNamesFromDataSourceResult" type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetMdx">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="analyticReportViewLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetMdxResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetMdxResult" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetCubeNameInfos">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:complexType name="ArrayOfNameInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="NameInfo" nillable="true"
type="tns:NameInfo"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="GetCubeNameInfosResponse">
  <xs:complexType>

```



```

        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="GetCubeNameInfosResult"
type="tns:ArrayOfNameInfo"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="GetPreviewDataSet">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="1" maxOccurs="1" name="maxRecords" type="xs:int"/>
          <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="GetPreviewDataSetResponse">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="GetPreviewDataSetResult">
            <xs:complexType mixed="true">
              <xs:sequence>
                <xs:any/>
              </xs:sequence>
            </xs:complexType>
          </xs:element>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="TestConnection">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="TestConnectionResponse">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="1" maxOccurs="1" name="TestConnectionResult"
type="xs:boolean"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="GetCubeMetaData">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:complexType name="NamedSet">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Dimensions"
type="tns:ArrayOfString"/>
      </xs:sequence>
      <xs:attribute name="Name" type="xs:string"/>
      <xs:attribute name="Expression" type="xs:string"/>
      <xs:attribute name="DisplayFolder" type="xs:string"/>
    </xs:complexType>

```

```

    <xs:complexType name="ArrayOfDimension">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="Dimension" nillable="true"
type="tns:Dimension"/>
      </xs:sequence>
    </xs:complexType>
    <xs:complexType name="ArrayOfMeasure">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="Measure" nillable="true"
type="tns:Measure"/>
      </xs:sequence>
    </xs:complexType>
    <xs:complexType name="Measure">
      <xs:complexContent mixed="false">
        <xs:extension base="tns:NameInfo">
          <xs:attribute name="AggregatorValue" type="xs:int" use="required"/>
          <xs:attribute name="MeasureGroup" type="xs:string"/>
          <xs:attribute name="DisplayFolder" type="xs:string"/>
          <xs:attribute name="HierarchyName" type="xs:string"/>
        </xs:extension>
      </xs:complexContent>
    </xs:complexType>
    <xs:complexType name="ArrayOfNamedSet">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="NamedSet" nillable="true"
type="tns:NamedSet"/>
      </xs:sequence>
    </xs:complexType>
    <xs:element name="GetCubeMetaDataResponse">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="GetCubeMetaDataResult"
type="tns:Cube"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:complexType name="Cube">
      <xs:complexContent mixed="false">
        <xs:extension base="tns:NameInfo">
          <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="Dimensions"
type="tns:ArrayOfDimension"/>
            <xs:element minOccurs="0" maxOccurs="1" name="MeasureGroups"
type="tns:ArrayOfNameInfo"/>
            <xs:element minOccurs="0" maxOccurs="1" name="Measures"
type="tns:ArrayOfMeasure"/>
            <xs:element minOccurs="0" maxOccurs="1" name="NamedSets"
type="tns:ArrayOfNamedSet"/>
          </xs:sequence>
          <xs:attribute name="Version" type="xs:int" use="required"/>
        </xs:extension>
      </xs:complexContent>
    </xs:complexType>
    <xs:element name="GetCubeMetaDataForDataSource">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>

```

```

<xs:element name="GetCubeMetaDataForDataSourceResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCubeMetaDataForDataSourceResult"
type="tns:Cube"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetDimensions">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetDimensionsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetDimensionsResult"
type="tns:ArrayOfDimension"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetDimensionsFromDataSource">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetDimensionsFromDataSourceResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetDimensionsFromDataSourceResult"
type="tns:ArrayOfDimension"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetCube">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetCubeResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCubeResult" type="tns:Cube"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetCubeFromDataSource">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

```

    </xs:complexType>
  </xs:element>
  <xs:element name="GetCubeFromDataSourceResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="GetCubeFromDataSourceResult"
type="tns:Cube"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="QueryDimensionRootMembers">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="dimensionName" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="QueryDimensionRootMembersResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="QueryDimensionRootMembersResult"
type="tns:ArrayOfMember"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="QueryDimensionRootMembersFromDataSource">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
        <xs:element minOccurs="0" maxOccurs="1" name="dimensionName" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="QueryDimensionRootMembersFromDataSourceResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1"
name="QueryDimensionRootMembersFromDataSourceResult" type="tns:ArrayOfMember"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="QueryTransformMembers">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="memberCollection"
type="tns:ArrayOfMember"/>
        <xs:element minOccurs="1" maxOccurs="1" name="transformType"
type="tns:QueryTransformMembersType"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:simpleType name="QueryTransformMembersType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Hierarchize"/>
      <xs:enumeration value="Parents"/>
    </xs:restriction>
  </xs:simpleType>

```

```

        <xs:enumeration value="Ancestors"/>
        <xs:enumeration value="AscendantsIntersect"/>
    </xs:restriction>
</xs:simpleType>
<xs:element name="QueryTransformMembersResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="QueryTransformMembersResult"
type="tns:ArrayOfMember"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryChildMembers">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
            <xs:element minOccurs="0" maxOccurs="1" name="memberUniqueName"
type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryChildMembersResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="QueryChildMembersResult"
type="tns:ArrayOfMember"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryChildMembersFromDataSource">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
            <xs:element minOccurs="0" maxOccurs="1" name="memberUniqueName"
type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryChildMembersFromDataSourceResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1"
name="QueryChildMembersFromDataSourceResult" type="tns:ArrayOfMember"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryChildMembersByRangeFromDataSource">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
            <xs:element minOccurs="0" maxOccurs="1" name="self" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="start" type="xs:long"/>
            <xs:element minOccurs="1" maxOccurs="1" name="count" type="xs:long"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryChildMembersByRangeFromDataSourceResponse">
    <xs:complexType>

```

```

        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1"
name="QueryChildMembersByRangeFromDataSourceResult" type="tns:ArrayOfMember"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="QueryRelatedMember">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
          <xs:element minOccurs="0" maxOccurs="1" name="memberUniqueName"
type="xs:string"/>
          <xs:element minOccurs="1" maxOccurs="1" name="relationship"
type="tns:MemberRelationship"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:simpleType name="MemberRelationship">
      <xs:restriction base="xs:string">
        <xs:enumeration value="Parent"/>
        <xs:enumeration value="FirstSibling"/>
        <xs:enumeration value="PrevMember"/>
        <xs:enumeration value="NextMember"/>
        <xs:enumeration value="LastSibling"/>
        <xs:enumeration value="FirstChild"/>
        <xs:enumeration value="LastChild"/>
        <xs:enumeration value="CurrentMember"/>
        <xs:enumeration value="Children"/>
      </xs:restriction>
    </xs:simpleType>
    <xs:element name="QueryRelatedMemberResponse">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="QueryRelatedMemberResult"
type="tns:Member"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="QueryRelatedMemberFromDataSource">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
          <xs:element minOccurs="0" maxOccurs="1" name="memberUniqueName"
type="xs:string"/>
          <xs:element minOccurs="1" maxOccurs="1" name="relationship"
type="tns:MemberRelationship"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="QueryRelatedMemberFromDataSourceResponse">
      <xs:complexType>
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1"
name="QueryRelatedMemberFromDataSourceResult" type="tns:Member"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="QueryNamedSets">
      <xs:complexType>

```

```

        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryNamedSetsResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="QueryNamedSetsResult"
type="tns:ArrayOfNamedSet"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryNamedSetsFromDataSource">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="QueryNamedSetsFromDataSourceResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="QueryNamedSetsFromDataSourceResult"
type="tns:ArrayOfNamedSet"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetAnnotationSetting">
    <xs:complexType/>
</xs:element>
<xs:complexType name="AnnotationSetting">
    <xs:attribute name="IsAnnotationEnabled" type="xs:boolean" use="required"/>
    <xs:attribute name="IsAnnotationEnabledDefault" type="xs:boolean" use="required"/>
    <xs:attribute name="IsDeletionByAuthorEnabled" type="xs:boolean" use="required"/>
    <xs:attribute name="IsDeletionByAuthorEnabledDefault" type="xs:boolean"
use="required"/>
    <xs:attribute name="MaxAnnotationAllowed" type="xs:int" use="required"/>
</xs:complexType>
<xs:element name="GetAnnotationSettingResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetAnnotationSettingResult"
type="tns:AnnotationSetting"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="ValidateKpi">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="ValidateKpiResponse">
    <xs:complexType>
        <xs:sequence>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="ValidateKpiResult"
type="tns:ArrayOfString"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="ValidateScorecard">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="ValidateScorecardResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="ValidateScorecardResult"
type="tns:ArrayOfString"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="ValidateSiteCollection">
    <xs:complexType/>
</xs:element>
<xs:element name="ValidateSiteCollectionResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="ValidateSiteCollectionResult"
type="tns:URLValidationResult"/>
            <xs:element minOccurs="0" maxOccurs="1" name="siteCollectionUrl"
type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="siteUrl" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:simpleType name="URLValidationResult">
    <xs:restriction base="xs:string">
        <xs:enumeration value="SiteCollectionOrSite"/>
        <xs:enumeration value="SiteCollection"/>
        <xs:enumeration value="Site"/>
        <xs:enumeration value="List"/>
        <xs:enumeration value="DocumentLibrary"/>
        <xs:enumeration value="InvalidURL"/>
        <xs:enumeration value="AlreadyExists"/>
        <xs:enumeration value="NonexistentSiteCollection"/>
        <xs:enumeration value="NonexistentSite"/>
        <xs:enumeration value="PPSNotActivatedOnSiteCollection"/>
        <xs:enumeration value="URLZoneNotAllowed"/>
        <xs:enumeration value="NoAccess"/>
        <xs:enumeration value="InvalidSiteVersion"/>
    </xs:restriction>
</xs:simpleType>
<xs:element name="GetCurrentCultureLcid">
    <xs:complexType/>
</xs:element>
<xs:element name="GetCurrentCultureLcidResponse">
    <xs:complexType>
        <xs:sequence>

```



```

        <xs:element minOccurs="1" maxOccurs="1" name="GetCurrentCultureLcidResult"
type="xs:int"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="GetCurrentUserInfo">
    <xs:complexType/>
</xs:element>
<xs:element name="GetCurrentUserInfoResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="userName" type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="userDisplayName" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GenerateView">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="scorecardLocation"
type="tns:RepositoryLocation"/>
            <xs:element minOccurs="0" maxOccurs="1" name="pageFilters"
type="tns:ArrayOfMember"/>
            <xs:element minOccurs="0" maxOccurs="1" name="propertyBags"
type="tns:DictionaryWrapperOfStringPropertyBag"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="DictionaryWrapperOfStringPropertyBag">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Keys" type="tns:ArrayOfString"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Values"
type="tns:ArrayOfPropertyBag"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfPropertyBag">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="PropertyBag" nillable="true"
type="tns:PropertyBag"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="GridViewData">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Cells" type="tns:GridCellSet"/>
        <xs:element minOccurs="0" maxOccurs="1" name="RootRowHeader"
type="tns:GridHeaderItem"/>
        <xs:element minOccurs="0" maxOccurs="1" name="RootColumnHeader"
type="tns:GridHeaderItem"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ScorecardLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DefaultRollupIndicatorLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="PreQueryTransforms"
type="tns:ArrayOfGridViewTransformReference"/>
        <xs:element minOccurs="0" maxOccurs="1" name="PostQueryTransforms"
type="tns:ArrayOfGridViewTransformReference"/>
        <xs:element minOccurs="0" maxOccurs="1" name="PreRenderTransforms"
type="tns:ArrayOfGridViewTransformReference"/>
        <xs:element minOccurs="0" maxOccurs="1" name="PerUserTransforms"
type="tns:ArrayOfGridViewTransformReference"/>
    </xs:sequence>
</xs:complexType>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="PageFilters"
type="tns:ArrayOfMember"/>
    </xs:sequence>
    <xs:attribute name="ScorecardViewId" type="s1:guid" use="required"/>
    <xs:attribute name="Cached" type="xs:boolean" use="required"/>
    <xs:attribute name="CacheExpiration" type="xs:dateTime" use="required"/>
    <xs:attribute name="DefaultRollupIndicatorId" type="s1:guid" use="required"/>
    <xs:attribute name="EmptyCell" type="xs:string"/>
    <xs:attribute name="InvalidCell" type="xs:string"/>
    <xs:attribute name="TIFormula" type="xs:string"/>
    <xs:attribute name="TICurrentDateTime" type="xs:string"/>
</xs:complexType>
<xs:complexType name="GridCellSet">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Table"
type="tns:DictionaryWrapperOfStringGridCell"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="DictionaryWrapperOfStringGridCell">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Keys" type="tns:ArrayOfString"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Values" type="tns:ArrayOfGridCell"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfGridCell">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="GridCell" nillable="true"
type="tns:GridCell"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="GridCell">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="FormatInfo"
type="tns:GridFormatInfo"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Properties" type="tns:PropertyBag"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DisplayElements"
type="tns:ArrayOfGridDisplayElement"/>
        <xs:element minOccurs="0" maxOccurs="1" name="IndicatorLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="1" maxOccurs="1" name="InBand" type="xs:int"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CellAnnotation"
type="tns:Annotation"/>
    </xs:sequence>
    <xs:attribute name="Value" type="xs:decimal" use="required"/>
    <xs:attribute name="ActualValue" type="xs:decimal" use="required"/>
    <xs:attribute name="Score" type="xs:decimal" use="required"/>
    <xs:attribute name="Weight" type="xs:decimal" use="required"/>
    <xs:attribute name="BestChildScore" type="xs:decimal" use="required"/>
    <xs:attribute name="WorstChildScore" type="xs:decimal" use="required"/>
    <xs:attribute name="IsValueInError" type="xs:boolean" use="required"/>
    <xs:attribute name="HasAnnotation" type="xs:boolean" use="required"/>
    <xs:attribute name="IsRollupScore" type="xs:boolean" use="required"/>
    <xs:attribute name="ValueSource" type="tns:ValueSources" use="required"/>
    <xs:attribute name="IsValidScore" type="xs:boolean" use="required"/>
</xs:complexType>
<xs:complexType name="ArrayOfGridDisplayElement">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="GridDisplayElement"
nillable="true" type="tns:GridDisplayElement"/>
    </xs:sequence>

```

```

</xs:complexType>
<xs:complexType name="GridDisplayElement" abstract="true">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Text" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="TooltipText" type="xs:string"/>
  </xs:sequence>
  <xs:attribute name="Status" type="tns:GridCellElementStatus" use="required"/>
</xs:complexType>
<xs:simpleType name="GridCellElementStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="0"/>
    <xs:enumeration value="1"/>
    <xs:enumeration value="2"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="GridDisplayElementHyperLink">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElement">
      <xs:attribute name="LinkUrl" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="GridDisplayElementIndicator">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="IndicatorLocation"
type="tns:RepositoryLocation"/>
      </xs:sequence>
      <xs:attribute name="IndicatorBand" type="xs:int" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="GridDisplayElementText">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElement"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="GridDisplayElementIndicatorText">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElementText">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="IndicatorLocation"
type="tns:RepositoryLocation"/>
      </xs:sequence>
      <xs:attribute name="IndicatorBand" type="xs:int" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="GridDisplayElementNumber" abstract="true">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:GridDisplayElement">
      <xs:attribute name="Value" type="xs:decimal" use="required"/>
      <xs:attribute name="OverrideValue" type="xs:decimal" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="GridDisplayElementActual">
  <xs:complexContent mixed="false">

```

```

        <xs:extension base="tns:GridDisplayElementNumber"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="GridDisplayElementTarget">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:GridDisplayElementNumber"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="GridDisplayElementVariance">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:GridDisplayElementNumber"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="GridDisplayElementScore">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:GridDisplayElementNumber"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="GridDisplayElementAggregation">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:GridDisplayElementNumber"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ArrayOfGridViewTransformReference">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="GridViewTransformReference"
nillable="true" type="tns:GridViewTransformReference"/>
    </xs:sequence>
</xs:complexType>
<xs:element name="GenerateViewResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GenerateViewResult"
type="tns:GridViewData"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GenerateViewDirect">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="scorecard" type="tns:Scorecard"/>
            <xs:element minOccurs="0" maxOccurs="1" name="kpis" type="tns:ArrayOfKpi"/>
            <xs:element minOccurs="0" maxOccurs="1" name="dataSources"
type="tns:ArrayOfDataSource"/>
            <xs:element minOccurs="0" maxOccurs="1" name="indicators"
type="tns:ArrayOfIndicator"/>
            <xs:element minOccurs="0" maxOccurs="1" name="pageFilters"
type="tns:ArrayOfMember"/>
            <xs:element minOccurs="0" maxOccurs="1" name="propertyBags"
type="tns:DictionaryWrapperOfStringPropertyBag"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="ArrayOfDataSource">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="DataSource" nillable="true"
type="tns:DataSource"/>
    </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="ArrayOfIndicator">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Indicator" nillable="true"
type="tns:Indicator"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="GenerateViewDirectResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GenerateViewDirectResult"
type="tns:GridViewData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetAsKpis">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetAsKpisResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetAsKpisResult"
type="tns:ArrayOfKpi"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="CreateDashboard">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="dashboard" type="tns:Dashboard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:complexType name="Dashboard">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:FirstClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Pages"
type="tns:ArrayOfDashboardElement"/>
      </xs:sequence>
      <xs:attribute name="TemplateType" type="xs:string"/>
      <xs:attribute name="DeploymentPath" type="xs:string"/>
      <xs:attribute name="SitePath" type="xs:string"/>
      <xs:attribute name="MasterPagePath" type="xs:string"/>
      <xs:attribute name="MasterPageDisplayName" type="xs:string"/>
      <xs:attribute name="PageList" type="xs:string"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="ArrayOfDashboardElement">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DashboardElement"
nillable="true" type="tns:DashboardElement"/>
  </xs:sequence>

```

```

</xs:complexType>
<xs:complexType name="DashboardElement" abstract="true">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SecondClassElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Height"
type="tns:DashboardElementSize"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Width"
type="tns:DashboardElementSize"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="DashboardElementSize">
  <xs:attribute name="Measurement" type="xs:int" use="required"/>
  <xs:attribute name="Units" type="tns:SizeType" use="required"/>
</xs:complexType>
<xs:simpleType name="SizeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="AutoSize"/>
    <xs:enumeration value="Absolute"/>
    <xs:enumeration value="Percent"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="DashboardItem">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DashboardElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="InboundParameters"
type="tns:ArrayOfParameterMapping"/>
        <xs:element minOccurs="0" maxOccurs="1" name="UnderlyingElementLocation"
type="tns:RepositoryLocation"/>
      </xs:sequence>
      <xs:attribute name="UnderlyingElementTypeName" type="xs:string"/>
      <xs:attribute name="AutoSizeWidth" type="xs:boolean" use="required"/>
      <xs:attribute name="AutoSizeHeight" type="xs:boolean" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="ArrayOfParameterMapping">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="ParameterMapping"
nillable="true" type="tns:ParameterMapping"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ParameterMapping">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="ConditionalData">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded"
namespace="http://www.w3.org/2001/XMLSchema" processContents="lax"/>
          <xs:any minOccurs="1" namespace="urn:schemas-microsoft-com:xml-diffgram-v1"
processContents="lax"/>
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="EndPointUniqueName" type="xs:string"/>

```

```

<xs:attribute name="Id" type="sl:guid" use="required"/>
<xs:attribute name="SourceColumnName" type="xs:string"/>
<xs:attribute name="DashboardItemId" type="sl:guid" use="required"/>
<xs:attribute name="ParameterUniqueName" type="xs:string"/>
<xs:attribute name="PostFormula" type="xs:string"/>
<xs:attribute name="IsConditionalDataEnabled" type="xs:boolean" use="required"/>
<xs:attribute name="IsDefaultVisibility" type="xs:boolean" use="required"/>
</xs:complexType>
<xs:complexType name="DashboardElementContainer">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DashboardElement">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="DashboardElements"
type="tns:ArrayOfDashboardElement"/>
      </xs:sequence>
      <xs:attribute name="Orientation" type="tns:LayoutOrientation" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="LayoutOrientation">
  <xs:restriction base="xs:string">
    <xs:enumeration value="HorizontalLeftJustified"/>
    <xs:enumeration value="HorizontalRightJustified"/>
    <xs:enumeration value="VerticalBottomJustified"/>
    <xs:enumeration value="VerticalTopJustified"/>
    <xs:enumeration value="Stacked"/>
    <xs:enumeration value="Hidden"/>
  </xs:restriction>
</xs:simpleType>
<xs:element name="CreateDashboardResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="CreateDashboardResult"
type="tns:Dashboard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="UpdateDashboard">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dashboard" type="tns:Dashboard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="UpdateDashboardResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="UpdateDashboardResult"
type="tns:Dashboard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetDashboard">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>

```

```

</xs:element>
<xs:element name="GetDashboardResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetDashboardResult"
type="tns:Dashboard"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DeleteDashboard">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="location"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="DeleteDashboardResponse">
  <xs:complexType/>
</xs:element>
<xs:element name="ImportDashboard">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="siteUrl" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="filename" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="locationMap">
        <xs:complexType mixed="true">
          <xs:sequence>
            <xs:any/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element minOccurs="0" maxOccurs="1" name="datasourceMap">
        <xs:complexType mixed="true">
          <xs:sequence>
            <xs:any/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element minOccurs="0" maxOccurs="1" name="masterPageUrl" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ImportDashboardResponse">
  <xs:complexType/>
</xs:element>
<xs:element name="ExportDashboard">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="filename" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="siteCollectionUrl"
type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="itemUrls"
type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ExportDashboardResponse">
  <xs:complexType/>

```



```

</xs:element>
<xs:element name="GetParameterDisplayData">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="parameterDefinition"
type="tns:ParameterDefinition"/>
      <xs:element minOccurs="0" maxOccurs="1" name="parameterSourceLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="gridViewData"
type="tns:GridViewData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetParameterDisplayDataResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetParameterDisplayDataResult">
        <xs:complexType>
          <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded"
namespace="http://www.w3.org/2001/XMLSchema" processContents="lax"/>
            <xs:any minOccurs="1" namespace="urn:schemas-microsoft-com:xml-diffgram-v1"
processContents="lax"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="QueryTimeIntelligence">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSourceLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="1" maxOccurs="1" name="currentTime" type="xs:dateTime"/>
      <xs:element minOccurs="0" maxOccurs="1" name="formula" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="QueryTimeIntelligenceResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="QueryTimeIntelligenceResult"
type="tns:ArrayOfMember"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="QueryTimeIntelligenceDirect">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="dataSource" type="tns:DataSource"/>
      <xs:element minOccurs="1" maxOccurs="1" name="currentTime" type="xs:dateTime"/>
      <xs:element minOccurs="0" maxOccurs="1" name="formula" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="QueryTimeIntelligenceDirectResponse">
  <xs:complexType>
    <xs:sequence>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="QueryTimeIntelligenceDirectResult"
type="tns:ArrayOfMember"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="GetRegisteredCustomFCOs">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="type" type="tns:CustomFCOType"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:simpleType name="CustomFCOType">
    <xs:list>
        <xs:simpleType>
            <xs:restriction base="xs:string">
                <xs:enumeration value="None"/>
                <xs:enumeration value="DataSource"/>
                <xs:enumeration value="Filter"/>
                <xs:enumeration value="ReportView"/>
                <xs:enumeration value="All"/>
            </xs:restriction>
        </xs:simpleType>
    </xs:list>
</xs:simpleType>
<xs:complexType name="CustomFCODefinition">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="TemplateIconSerialized"
type="xs:string"/>
    </xs:sequence>
    <xs:attribute name="Type" type="tns:CustomFCOType" use="required"/>
    <xs:attribute name="SubType" type="xs:string"/>
    <xs:attribute name="Name" type="xs:string"/>
    <xs:attribute name="Description" type="xs:string"/>
    <xs:attribute name="RendererClass" type="xs:string"/>
    <xs:attribute name="EditorUri" type="xs:string"/>
</xs:complexType>
<xs:complexType name="ArrayOfCustomFCODefinition">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="CustomFCODefinition"
nillable="true" type="tns:CustomFCODefinition"/>
    </xs:sequence>
</xs:complexType>
<xs:element name="GetRegisteredCustomFCOsResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetRegisteredCustomFCOsResult"
type="tns:ArrayOfCustomFCODefinition"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetListItems">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="listUrl" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="ArrayOfFirstClassElement">

```

```

    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="FirstClassElement"
nillable="true" type="tns:FirstClassElement"/>
    </xs:sequence>
  </xs:complexType>
</xs:element name="GetListItemsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetListItemsResult"
type="tns:ArrayOfFirstClassElement"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetDependentElements">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="missingItems"
type="tns:ArrayOfRepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:complexType name="ArrayOfRepositoryLocation">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="RepositoryLocation"
nillable="true" type="tns:RepositoryLocation"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="DependentElementInfo">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="DependentLists"
type="tns:ArrayOfRepositoryList"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DependentElements"
type="tns:ArrayOfFirstClassElement"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfRepositoryList">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="RepositoryList"
nillable="true" type="tns:RepositoryList"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="RepositoryList">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Location" type="tns:ListLocation"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SupportedTypes"
type="tns:FCOContentType"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Title" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ListId" type="s1:guid"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="GetDependentElementsResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetDependentElementsResult"
type="tns:DependentElementInfo"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="AnnotationSetting" nillable="true" type="tns:AnnotationSetting"/>
<xs:element name="int" type="xs:int"/>

```

```

    <xs:element name="ArrayOfCustomFCODefinition" nillable="true"
type="tns:ArrayOfCustomFCODefinition"/>
    <xs:element name="ArrayOfFirstClassElement" nillable="true"
type="tns:ArrayOfFirstClassElement"/>
    <xs:element name="FirstClassObjectType" type="tns:FirstClassObjectType"/>
    <xs:simpleType name="FirstClassObjectType">
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="Kpi"/>
        <xs:enumeration value="Scorecard"/>
        <xs:enumeration value="ReportView"/>
        <xs:enumeration value="Indicator"/>
        <xs:enumeration value="DataSource"/>
        <xs:enumeration value="Dashboard"/>
        <xs:enumeration value="TempReportView"/>
        <xs:enumeration value="Filter"/>
      </xs:restriction>
    </xs:simpleType>
    <xs:complexType name="RepositoryLocation">
      <xs:attribute name="ItemUrl" type="xs:string" use="required"/>
      <xs:attribute default="None" name="ItemType" type="tns:FirstClassObjectType"
use="optional"/>
      <xs:attribute default="00000000-0000-0000-0000-000000000000" name="ItemGuid"
use="optional">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:attribute>
      <xs:attribute default="00000000-0000-0000-0000-000000000000"
name="SpSiteCollectionGuid" use="optional">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:attribute>
      <xs:attribute default="00000000-0000-0000-0000-000000000000" name="SpSiteGuid"
use="optional">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:attribute>
      <xs:attribute default="00000000-0000-0000-0000-000000000000" name="SpListGuid"
use="optional">
        <xs:simpleType>
          <xs:restriction base="xs:string">
            <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}"/>
          </xs:restriction>
        </xs:simpleType>
      </xs:attribute>
    </xs:complexType>

```

```

    <xs:element name="AnalyticChartReportView" nillable="true"
type="tns:AnalyticChartReportView"/>
    <xs:complexType name="AnalyticChartReportView">
      <xs:complexContent mixed="false">
        <xs:extension base="tns:AnalyticBaseReportViewData">
          <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="Title" type="tns:Title"/>
            <xs:element minOccurs="0" maxOccurs="1" name="PlotAreaBackColor"
type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="Legend"
type="tns:AnalyticChartLegend"/>
          </xs:sequence>
          <xs:attribute default="Column" name="ChartType" type="tns:AnalyticChartType"/>
          <xs:attribute default="None" name="LineMarkerStyle"
type="tns:AnalyticMarkerStyle"/>
          <xs:attribute default="true" name="ChartColorVisible" type="xs:boolean"/>
          <xs:attribute default="false" name="ChartPointersVisible" type="xs:boolean"/>
          <xs:attribute default="2" name="LineWidth" type="xs:int"/>
        </xs:extension>
      </xs:complexContent>
    </xs:complexType>
    <xs:complexType name="AnalyticBaseReportViewData">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="NumericFormats"
type="tns:NumericFormatsHashtable"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Font" type="tns:XmlFont"/>
        <xs:element minOccurs="0" maxOccurs="1" name="FontColor" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="BackgroundColor" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
    <xs:complexType name="NumericFormatsHashtable">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="NumericFormat"
type="tns:NumericFormat"/>
      </xs:sequence>
    </xs:complexType>
    <xs:complexType name="NumericFormat">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="MemberName" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="FormatType" type="tns:FormatType"/>
        <xs:element minOccurs="0" maxOccurs="1" name="CurrencySymbol" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="DecimalPlaces" type="xs:int"/>
        <xs:element minOccurs="1" maxOccurs="1" name="NegativeSymbol"
type="tns:FormatNegativeSymbol"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ShowZeroAs" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="UseThousandsSeparator"
type="xs:boolean"/>
        <xs:element minOccurs="0" maxOccurs="1" name="AdditionalTextLeft"
type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="AdditionalTextRight"
type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
    <xs:complexType name="XmlFont">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="FontFamily" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="GraphicsUnit"
type="tns:GraphicsUnit"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Size" type="xs:float"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Style" type="tns:FontStyle"/>
      </xs:sequence>
    </xs:complexType>

```

```

</xs:sequence>
</xs:complexType>
<xs:complexType name="Title">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Font" type="tns:XmlFont"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FontColor" type="xs:string"/>
  </xs:sequence>
  <xs:attribute default="" name="Text" type="xs:string"/>
  <xs:attribute default="Center" name="Alignment" type="tns:AlignmentType"/>
</xs:complexType>
<xs:simpleType name="AlignmentType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Left"/>
    <xs:enumeration value="Right"/>
    <xs:enumeration value="Center"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="AnalyticChartLegend">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="BackColor" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Font" type="tns:XmlFont"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FontColor" type="xs:string"/>
  </xs:sequence>
  <xs:attribute default="true" name="Visible" type="xs:boolean"/>
  <xs:attribute default="false" name="BorderVisible" type="xs:boolean"/>
  <xs:attribute default="Right" name="Location" type="tns:AnalyticLegendLocation"/>
</xs:complexType>
<xs:simpleType name="AnalyticLegendLocation">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Right"/>
    <xs:enumeration value="Top"/>
    <xs:enumeration value="Bottom"/>
    <xs:enumeration value="Left"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="AnalyticChartType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Column"/>
    <xs:enumeration value="ColumnStacked"/>
    <xs:enumeration value="ColumnStacked100"/>
    <xs:enumeration value="Line"/>
    <xs:enumeration value="Pie"/>
    <xs:enumeration value="Bar"/>
    <xs:enumeration value="BarStacked"/>
    <xs:enumeration value="BarStacked100"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="AnalyticMarkerStyle">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Square"/>
    <xs:enumeration value="Circle"/>
    <xs:enumeration value="Diamond"/>
    <xs:enumeration value="Triangle"/>
    <xs:enumeration value="Cross"/>
    <xs:enumeration value="Star4"/>
    <xs:enumeration value="Star5"/>
  </xs:restriction>
</xs:simpleType>

```

```

        <xs:enumeration value="Star6"/>
        <xs:enumeration value="Star10"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="ArrayOfTimeIntelligenceDataSource">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="TimeIntelligenceDataSource"
nillable="true" type="tns:TimeIntelligenceDataSource"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfTimeIntelligenceFormula">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="TimeIntelligenceFormula"
nillable="true" type="tns:TimeIntelligenceFormula"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Axis" mixed="true">
    <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="Type" type="tns:AxisType"/>
        <xs:element minOccurs="1" maxOccurs="1" name="FilterEmpty" type="xs:boolean"/>
        <xs:element minOccurs="1" maxOccurs="1" name="PropertyList"
type="tns:StringCollection"/>
        <xs:element minOccurs="1" maxOccurs="1" name="MemberSets"
type="tns:SerializableDictionary"/>
        <xs:element minOccurs="1" maxOccurs="1" name="SortMode" type="tns:SortType"/>
        <xs:element minOccurs="1" maxOccurs="1" name="SortIndex" type="xs:int"/>
        <xs:element minOccurs="0" maxOccurs="1" name="SortTuple" type="tns:Tuple"/>
        <xs:element minOccurs="1" maxOccurs="1" name="SortDescending" type="xs:boolean"/>
        <xs:element minOccurs="1" maxOccurs="1" name="SortPreservePeerGroups"
type="xs:boolean"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="AxisType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Filter"/>
        <xs:enumeration value="Columns"/>
        <xs:enumeration value="Rows"/>
        <xs:enumeration value="Pages"/>
        <xs:enumeration value="Sections"/>
        <xs:enumeration value="Chapters"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="SortType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Off"/>
        <xs:enumeration value="ByIndex"/>
        <xs:enumeration value="ByTuple"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="StringCollection">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="CalculatedMember">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:Member">
            <xs:attribute name="Expression" type="xs:string"/>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

```

```

        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="BpmException">
    <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="ErrorCode" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="EventLogged" type="xs:boolean"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Message" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="OLAPReportView">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="QueryData"
type="qdata:OLAPQueryData"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ReportViewData" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ParentReportViewLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ShowInformationBar"
type="xs:boolean"/>
        <xs:element minOccurs="0" maxOccurs="1" name="QueryState" type="query:QueryState"/>
    </xs:sequence>
    <xs:attribute name="MeasureGroupName" type="xs:string"/>
    <xs:attribute name="Caption" type="xs:string"/>
    <xs:attribute name="Description" type="xs:string"/>
    <xs:attribute name="FormatDimensionUniqueName" type="xs:string"/>
</xs:complexType>
<xs:complexType name="OLAPQueryData">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Parameters"
type="tns:ArrayOfParameter"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="MDX" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfParameter">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="Parameter" nillable="true"
type="tns:Parameter"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Parameter">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="DefaultValue" type="xs:string"/>
    </xs:sequence>
    <xs:attribute name="Name" type="xs:string"/>
</xs:complexType>
<xs:complexType name="QueryState">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Axes" type="tns:ArrayOfAxis"/>
        <xs:element minOccurs="1" maxOccurs="1" name="IsEnabled" type="xs:boolean"/>
        <xs:element minOccurs="1" maxOccurs="1" name="UnknownFilterParameter"
type="xs:boolean"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ShowDataSourceFormatting"
type="xs:boolean"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfAxis">

```



```

    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="Axis" type="tns:Axis"/>
    </xs:sequence>
  </xs:complexType>
  <xs:element name="AnalyticGridReportView" nillable="true"
type="tns:AnalyticGridReportView"/>
  <xs:complexType name="AnalyticGridReportView">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:AnalyticBaseReportViewData">
        <xs:sequence>
          <xs:element minOccurs="1" maxOccurs="1" name="ReportLayout"
type="tns:ReportLayout"/>
          <xs:element minOccurs="1" maxOccurs="1" name="ShortenRowLabels"
type="xs:boolean"/>
          <xs:element minOccurs="1" maxOccurs="1" name="MaxRowLabelLength"
type="xs:int"/>
          <xs:element minOccurs="1" maxOccurs="1" name="ShortenColumnLabels"
type="xs:boolean"/>
          <xs:element minOccurs="1" maxOccurs="1" name="MaxColumnLabelLength"
type="xs:int"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:simpleType name="ReportLayout">
    <xs:restriction base="xs:string">
      <xs:enumeration value="TabularForm"/>
      <xs:enumeration value="CompactForm"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="PasReportViewData" nillable="true" type="tns:PasReportViewData"/>
  <xs:complexType name="PasReportViewData">
    <xs:attribute name="ServerUrl" type="xs:string"/>
    <xs:attribute name="PageId" type="s1:guid" use="required"/>
    <xs:attribute name="PagePath" type="xs:string"/>
    <xs:attribute name="ConfigOptions" type="xs:string"/>
  </xs:complexType>
  <xs:element name="SqlReportViewData" nillable="true" type="tns:SqlReportViewData"/>
  <xs:complexType name="SqlReportViewData">
    <xs:attribute name="ReportName" type="xs:string"/>
    <xs:attribute name="ServerAddress" type="xs:string"/>
    <xs:attribute name="ServerUrl" type="xs:string"/>
    <xs:attribute name="ReportPath" type="xs:string"/>
    <xs:attribute name="ReportUrl" type="xs:string"/>
    <xs:attribute name="ReportMode" type="tns:SqlReportViewDataServerMode"
use="required"/>
    <xs:attribute name="ShowToolbar" type="xs:boolean" use="required"/>
    <xs:attribute name="ShowParameters" type="xs:boolean" use="required"/>
    <xs:attribute name="ShowDocMap" type="xs:boolean" use="required"/>
    <xs:attribute name="DocMapId" type="xs:string"/>
    <xs:attribute name="Zoom" type="xs:string"/>
    <xs:attribute name="Section" type="xs:string"/>
    <xs:attribute name="Format" type="xs:string"/>
  </xs:complexType>
  <xs:simpleType name="SqlReportViewDataServerMode">
    <xs:restriction base="xs:string">
      <xs:enumeration value="SharepointIntegrated"/>
      <xs:enumeration value="ReportCenter"/>
    </xs:restriction>
  </xs:simpleType>

```

```

</xs:simpleType>
<xs:complexType name="ExcelDataSet">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="CompressedDataTable"
type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ExcelFileBlob" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="TableMapping"
type="tns:DataTableMapping"/>
  </xs:sequence>
  <xs:attribute name="UseFirstRowHeaders" type="xs:boolean" use="required"/>
</xs:complexType>
<xs:complexType name="ExcelServicesData">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="WorkbookParameters"
type="tns:PropertyBag"/>
  </xs:sequence>
  <xs:attribute name="SharePointSite" type="xs:string"/>
  <xs:attribute name="DocumentLibrary" type="xs:string"/>
  <xs:attribute name="DocumentLibraryRootFolder" type="xs:string"/>
  <xs:attribute name="DocumentLibraryDisplay" type="xs:string"/>
  <xs:attribute name="FolderFileName" type="xs:string"/>
  <xs:attribute name="FileName" type="xs:string"/>
  <xs:attribute name="ItemName" type="xs:string"/>
  <xs:attribute name="ViewOptions" type="tns:ExcelServicesViewOptions" use="required"/>
  <xs:attribute name="ToolbarType" type="tns:ExcelServicesToolbarType" use="required"/>
  <xs:attribute name="ToolbarOptions" type="tns:ExcelServicesToolbarOptions"
use="required"/>
</xs:complexType>
<xs:simpleType name="ExcelServicesViewOptions">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="AllowInteractivity"/>
        <xs:enumeration value="AllowParameterModification"/>
        <xs:enumeration value="ShowWorkbookParameters"/>
        <xs:enumeration value="AllowSorting"/>
        <xs:enumeration value="AllowFiltering"/>
        <xs:enumeration value="AllowHyperlinks"/>
        <xs:enumeration value="AllowPivotSpecificOperations"/>
        <xs:enumeration value="AllowPeriodicRefresh"/>
        <xs:enumeration value="CloseWorkbookSessions"/>
        <xs:enumeration value="AllowScratchPadMode"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
<xs:simpleType name="ExcelServicesToolbarType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="FullToolbar"/>
    <xs:enumeration value="SummaryToolbar"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ExcelServicesToolbarOptions">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="AllowInExcelOperations"/>
        <xs:enumeration value="AllowRefreshConnections"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>

```

```

        <xs:enumeration value="AllowRecalculation"/>
        <xs:enumeration value="ShowVisibleItemButton"/>
    </xs:restriction>
</xs:simpleType>
</xs:list>
</xs:simpleType>
<xs:element name="ListLocation" nillable="true" type="tns:ListLocation"/>
<xs:complexType name="ListLocation">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="SiteUrl" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ListUrl" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="MDXParameterDefinition">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Expression" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="MemberParameterDefinition">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Dimension" type="tns:Dimension"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Members" type="tns:ArrayOfMember"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DefaultMembers"
type="tns:ArrayOfMember"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="NamedSetParameterDefinition">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Expression" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:element name="SetOperation" nillable="true" type="tns:SetOperation"/>
<xs:complexType name="SetOperation" abstract="true">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="FilterValue1" type="xs:double"/>
        <xs:element minOccurs="1" maxOccurs="1" name="FilterValue2" type="xs:double"/>
        <xs:element minOccurs="0" maxOccurs="1" name="TupleSet" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="TupleCaption" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="FilterHierarchy" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="FilterMeasure" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DefaultMeasure" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Level" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="LevelDepth" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="FilterType" type="xs:int"/>
        <xs:element minOccurs="0" maxOccurs="1" name="MemberDefinition" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="EliminateMemberSetOp">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:SetOperation"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="EliminateDescendantsSetOp">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:SetOperation"/>
    </xs:complexContent>
</xs:complexType>

```

```

<xs:complexType name="AddAllMembersSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddParentSiblingsSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddNamedSetSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddCalcMemberSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Aggregate" type="xs:boolean"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Caption" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddDescendantsSubtreeSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddDescendantsSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="LevelName" type="xs:string"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddDescendantsLeavesSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddDefaultMemberSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddFilterSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddMemberSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>

```

```

<xs:complexType name="AddChildrenSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="AddFilterTopBottomSetOp">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SetOperation"/>
  </xs:complexContent>
</xs:complexType>
<xs:element name="MemberSet" nillable="true" type="tns:MemberSet"/>
<xs:complexType name="MemberSet" abstract="true">
  <xs:attribute name="FilterEmpty" type="xs:boolean" use="required"/>
  <xs:attribute name="HierarchyType" type="tns:HierarchyType" use="required"/>
  <xs:attribute name="Hierarchize" type="xs:boolean" use="required"/>
  <xs:attribute name="Distinct" type="xs:boolean" use="required"/>
  <xs:attribute name="HierarchyName" type="xs:string"/>
</xs:complexType>
<xs:simpleType name="HierarchyType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Standard"/>
    <xs:enumeration value="Measure"/>
    <xs:enumeration value="Time"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="ArrayOfSetOperation">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SetOperation" nillable="true"
type="tns:SetOperation"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="SerializableDictionary" nillable="true"
type="tns:SerializableDictionary"/>
<xs:complexType name="SerializableDictionary">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="Item" type="tns:Item"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Item">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Key" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Value" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="MemberList" nillable="true" type="tns:MemberList"/>
<xs:complexType name="MemberList">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:MemberSet">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="memberList"
type="tns:ArrayOfString"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="MemberSetFormula">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:MemberSet">
      <xs:sequence>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="Operations"
type="tns:ArrayOfSetOperation"/>
    </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="StrategyMapViewData" nillable="true" type="tns:StrategyMapViewData"/>
<xs:complexType name="StrategyMapViewData">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" default="None" name="ToolbarOptions"
type="tns:StrategyMapToolbarOptions"/>
        <xs:element minOccurs="0" maxOccurs="1" name="VDX" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Version" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ParentLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ParentType"
type="tns:FirstClassObjectType"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Parameters" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="StrategyMapToolbarOptions">
    <xs:list>
        <xs:simpleType>
            <xs:restriction base="xs:string">
                <xs:enumeration value="None"/>
                <xs:enumeration value="ShowToolbar"/>
                <xs:enumeration value="ShowPage"/>
                <xs:enumeration value="ShowScrollbars"/>
                <xs:enumeration value="ShowPageTabs"/>
            </xs:restriction>
        </xs:simpleType>
    </xs:list>
</xs:simpleType>
<xs:complexType name="TimeIntelligenceDataSource">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DisplayName" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TimeIntelligenceDefinition">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Formulas"
type="tns:ArrayOfTimeIntelligenceFormula"/>
        <xs:element minOccurs="0" maxOccurs="1" name="MasterDataSource"
type="tns:TimeIntelligenceDataSource"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DataSources"
type="tns:ArrayOfTimeIntelligenceDataSource"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TimeIntelligenceFormula">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="DisplayName" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Formula" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TimeIntelligenceMdxSettings">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:TimeIntelligenceSettings">
            <xs:sequence>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="ReferenceDimension"
type="tns:Dimension"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ReferenceLevel"
type="tns:DateAggregationTypes"/>
        <xs:element minOccurs="0" maxOccurs="1" name="ReferenceMember"
type="tns:Member"/>
        <xs:element minOccurs="1" maxOccurs="1" name="ReferenceDateTime"
type="xs:dateTime"/>
        <xs:element minOccurs="0" maxOccurs="1" name="LevelBindings"
type="tns:ArrayOfTimeIntelligenceLevelBinding"/>
    </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="TimeIntelligenceSettings" abstract="true">
    <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="Enabled" type="xs:boolean"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfTimeIntelligenceLevelBinding">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="TimeIntelligenceLevelBinding"
nillable="true" type="tns:TimeIntelligenceLevelBinding"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TimeIntelligenceLevelBinding">
    <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="Level"
type="tns:DateAggregationTypes"/>
        <xs:element minOccurs="0" maxOccurs="1" name="UniqueName" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TimeIntelligencePostFormulaDefinition">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="MasterDataSource"
type="tns:DataSource"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DataSources"
type="tns:ArrayOfDataSource"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="GraphicsUnit">
    <xs:restriction base="xs:string">
        <xs:enumeration value="World"/>
        <xs:enumeration value="Display"/>
        <xs:enumeration value="Pixel"/>
        <xs:enumeration value="Point"/>
        <xs:enumeration value="Inch"/>
        <xs:enumeration value="Document"/>
        <xs:enumeration value="Millimeter"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="FontStyle">
    <xs:list>
        <xs:simpleType>
            <xs:restriction base="xs:string">
                <xs:enumeration value="Regular"/>
                <xs:enumeration value="Bold"/>
                <xs:enumeration value="Italic"/>
                <xs:enumeration value="Underline"/>
                <xs:enumeration value="Strikeout"/>
            </xs:restriction>
        </xs:simpleType>
    </xs:list>
</xs:simpleType>

```

```

        </xs:restriction>
    </xs:simpleType>
</xs:list>
</xs:simpleType>
<xs:import namespace="http://microsoft.com/wsdl/types/" />
<xs:import namespace="http://www.w3.org/2001/XMLSchema" />
</xs:schema>
<xs:schema elementFormDefault="qualified"
targetNamespace="http://microsoft.com/wsdl/types/">
    <xs:simpleType name="guid">
        <xs:restriction base="xs:string">
            <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-
9a-fA-F]{12}" />
        </xs:restriction>
    </xs:simpleType>
    <xs:simpleType name="char">
        <xs:restriction base="xs:unsignedShort" />
    </xs:simpleType>
</xs:schema>
</wsdl:types>
<wsdl:portType name="PPSAuthoringServiceSoap">
    <wsdl:operation name="CreateDataSource">
        <wsdl:input message="tns:CreateDataSourceSoapIn" />
        <wsdl:output message="tns:CreateDataSourceSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="UpdateDataSource">
        <wsdl:input message="tns:UpdateDataSourceSoapIn" />
        <wsdl:output message="tns:UpdateDataSourceSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="GetDataSource">
        <wsdl:input message="tns:GetDataSourceSoapIn" />
        <wsdl:output message="tns:GetDataSourceSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="DeleteDataSource">
        <wsdl:input message="tns>DeleteDataSourceSoapIn" />
        <wsdl:output message="tns>DeleteDataSourceSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="CreateKpi">
        <wsdl:input message="tns:CreateKpiSoapIn" />
        <wsdl:output message="tns:CreateKpiSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="UpdateKpi">
        <wsdl:input message="tns:UpdateKpiSoapIn" />
        <wsdl:output message="tns:UpdateKpiSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="GetKpisFromScorecard">
        <wsdl:input message="tns:GetKpisFromScorecardSoapIn" />
        <wsdl:output message="tns:GetKpisFromScorecardSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="GetKpi">
        <wsdl:input message="tns:GetKpiSoapIn" />
        <wsdl:output message="tns:GetKpiSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="DeleteKpi">
        <wsdl:input message="tns>DeleteKpiSoapIn" />
        <wsdl:output message="tns>DeleteKpiSoapOut" />
    </wsdl:operation>
    <wsdl:operation name="CreateScorecard">
        <wsdl:input message="tns:CreateScorecardSoapIn" />

```



```

    <wsdl:output message="tns:CreateScorecardSoapOut"/>
</wsdl:operation>
<wsdl:operation name="UpdateScorecard">
    <wsdl:input message="tns:UpdateScorecardSoapIn"/>
    <wsdl:output message="tns:UpdateScorecardSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetScorecard">
    <wsdl:input message="tns:GetScorecardSoapIn"/>
    <wsdl:output message="tns:GetScorecardSoapOut"/>
</wsdl:operation>
<wsdl:operation name="DeleteScorecard">
    <wsdl:input message="tns:DeleteScorecardSoapIn"/>
    <wsdl:output message="tns:DeleteScorecardSoapOut"/>
</wsdl:operation>
<wsdl:operation name="CreateFilter">
    <wsdl:input message="tns:CreateFilterSoapIn"/>
    <wsdl:output message="tns:CreateFilterSoapOut"/>
</wsdl:operation>
<wsdl:operation name="UpdateFilter">
    <wsdl:input message="tns:UpdateFilterSoapIn"/>
    <wsdl:output message="tns:UpdateFilterSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetFilter">
    <wsdl:input message="tns:GetFilterSoapIn"/>
    <wsdl:output message="tns:GetFilterSoapOut"/>
</wsdl:operation>
<wsdl:operation name="DeleteFilter">
    <wsdl:input message="tns:DeleteFilterSoapIn"/>
    <wsdl:output message="tns:DeleteFilterSoapOut"/>
</wsdl:operation>
<wsdl:operation name="CreateIndicator">
    <wsdl:input message="tns:CreateIndicatorSoapIn"/>
    <wsdl:output message="tns:CreateIndicatorSoapOut"/>
</wsdl:operation>
<wsdl:operation name="UpdateIndicator">
    <wsdl:input message="tns:UpdateIndicatorSoapIn"/>
    <wsdl:output message="tns:UpdateIndicatorSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetIndicator">
    <wsdl:input message="tns:GetIndicatorSoapIn"/>
    <wsdl:output message="tns:GetIndicatorSoapOut"/>
</wsdl:operation>
<wsdl:operation name="DeleteIndicator">
    <wsdl:input message="tns:DeleteIndicatorSoapIn"/>
    <wsdl:output message="tns:DeleteIndicatorSoapOut"/>
</wsdl:operation>
<wsdl:operation name="CreateReportView">
    <wsdl:input message="tns:CreateReportViewSoapIn"/>
    <wsdl:output message="tns:CreateReportViewSoapOut"/>
</wsdl:operation>
<wsdl:operation name="UpdateReportView">
    <wsdl:input message="tns:UpdateReportViewSoapIn"/>
    <wsdl:output message="tns:UpdateReportViewSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetReportView">
    <wsdl:input message="tns:GetReportViewSoapIn"/>
    <wsdl:output message="tns:GetReportViewSoapOut"/>
</wsdl:operation>
<wsdl:operation name="DeleteReportView">

```

```

    <wsdl:input message="tns:DeleteReportViewSoapIn"/>
    <wsdl:output message="tns:DeleteReportViewSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetAnalyticReportView">
    <wsdl:input message="tns:GetAnalyticReportViewSoapIn"/>
    <wsdl:output message="tns:GetAnalyticReportViewSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetLatestAnalyticReportVersion">
    <wsdl:input message="tns:GetLatestAnalyticReportVersionSoapIn"/>
    <wsdl:output message="tns:GetLatestAnalyticReportVersionSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="SaveTemporaryAnalyticReport">
    <wsdl:input message="tns:SaveTemporaryAnalyticReportSoapIn"/>
    <wsdl:output message="tns:SaveTemporaryAnalyticReportSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetQueryResultMembers">
    <wsdl:input message="tns:GetQueryResultMembersSoapIn"/>
    <wsdl:output message="tns:GetQueryResultMembersSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetAnnotation">
    <wsdl:input message="tns:GetAnnotationSoapIn"/>
    <wsdl:output message="tns:GetAnnotationSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetAnnotationByID">
    <wsdl:input message="tns:GetAnnotationByIDS SoapIn"/>
    <wsdl:output message="tns:GetAnnotationByIDS SoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetAllAnnotationsByScorecardLocation">
    <wsdl:input message="tns:GetAllAnnotationsByScorecardLocationSoapIn"/>
    <wsdl:output message="tns:GetAllAnnotationsByScorecardLocationSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="CreateAnnotation">
    <wsdl:input message="tns:CreateAnnotationSoapIn"/>
    <wsdl:output message="tns:CreateAnnotationSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="UpdateAnnotation">
    <wsdl:input message="tns:UpdateAnnotationSoapIn"/>
    <wsdl:output message="tns:UpdateAnnotationSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="DeleteAnnotation">
    <wsdl:input message="tns>DeleteAnnotationSoapIn"/>
    <wsdl:output message="tns>DeleteAnnotationSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="TrimAnnotationByScorecardLocation">
    <wsdl:input message="tns:TrimAnnotationByScorecardLocationSoapIn"/>
    <wsdl:output message="tns:TrimAnnotationByScorecardLocationSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="TrimAnnotationByOwner">
    <wsdl:input message="tns:TrimAnnotationByOwnerSoapIn"/>
    <wsdl:output message="tns:TrimAnnotationByOwnerSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="TrimAnnotationUntouchedSince">
    <wsdl:input message="tns:TrimAnnotationUntouchedSinceSoapIn"/>
    <wsdl:output message="tns:TrimAnnotationUntouchedSinceSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetDatabaseNamesFromDataSource">
    <wsdl:input message="tns:GetDatabaseNamesFromDataSourceSoapIn"/>
    <wsdl:output message="tns:GetDatabaseNamesFromDataSourceSoapOut"/>
  </wsdl:operation>

```

```

<wsdl:operation name="GetMdx">
  <wsdl:input message="tns:GetMdxSoapIn"/>
  <wsdl:output message="tns:GetMdxSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetCubeNameInfos">
  <wsdl:input message="tns:GetCubeNameInfosSoapIn"/>
  <wsdl:output message="tns:GetCubeNameInfosSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetPreviewDataSet">
  <wsdl:input message="tns:GetPreviewDataSetSoapIn"/>
  <wsdl:output message="tns:GetPreviewDataSetSoapOut"/>
</wsdl:operation>
<wsdl:operation name="TestConnection">
  <wsdl:input message="tns:TestConnectionSoapIn"/>
  <wsdl:output message="tns:TestConnectionSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetCubeMetaData">
  <wsdl:input message="tns:GetCubeMetaDataSoapIn"/>
  <wsdl:output message="tns:GetCubeMetaDataSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetCubeMetaDataForDataSource">
  <wsdl:input message="tns:GetCubeMetaDataForDataSourceSoapIn"/>
  <wsdl:output message="tns:GetCubeMetaDataForDataSourceSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetDimensions">
  <wsdl:input message="tns:GetDimensionsSoapIn"/>
  <wsdl:output message="tns:GetDimensionsSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetDimensionsFromDataSource">
  <wsdl:input message="tns:GetDimensionsFromDataSourceSoapIn"/>
  <wsdl:output message="tns:GetDimensionsFromDataSourceSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetCube">
  <wsdl:input message="tns:GetCubeSoapIn"/>
  <wsdl:output message="tns:GetCubeSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetCubeFromDataSource">
  <wsdl:input message="tns:GetCubeFromDataSourceSoapIn"/>
  <wsdl:output message="tns:GetCubeFromDataSourceSoapOut"/>
</wsdl:operation>
<wsdl:operation name="QueryDimensionRootMembers">
  <wsdl:input message="tns:QueryDimensionRootMembersSoapIn"/>
  <wsdl:output message="tns:QueryDimensionRootMembersSoapOut"/>
</wsdl:operation>
<wsdl:operation name="QueryDimensionRootMembersFromDataSource">
  <wsdl:input message="tns:QueryDimensionRootMembersFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryDimensionRootMembersFromDataSourceSoapOut"/>
</wsdl:operation>
<wsdl:operation name="QueryTransformMembers">
  <wsdl:input message="tns:QueryTransformMembersSoapIn"/>
  <wsdl:output message="tns:QueryTransformMembersSoapOut"/>
</wsdl:operation>
<wsdl:operation name="QueryChildMembers">
  <wsdl:input message="tns:QueryChildMembersSoapIn"/>
  <wsdl:output message="tns:QueryChildMembersSoapOut"/>
</wsdl:operation>
<wsdl:operation name="QueryChildMembersFromDataSource">
  <wsdl:input message="tns:QueryChildMembersFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryChildMembersFromDataSourceSoapOut"/>

```

```

</wsdl:operation>
<wsdl:operation name="QueryChildMembersByRangeFromDataSource">
  <wsdl:input message="tns:QueryChildMembersByRangeFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryChildMembersByRangeFromDataSourceSoapOut"/>
</wsdl:operation>
<wsdl:operation name="QueryRelatedMember">
  <wsdl:input message="tns:QueryRelatedMemberSoapIn"/>
  <wsdl:output message="tns:QueryRelatedMemberSoapOut"/>
</wsdl:operation>
<wsdl:operation name="QueryRelatedMemberFromDataSource">
  <wsdl:input message="tns:QueryRelatedMemberFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryRelatedMemberFromDataSourceSoapOut"/>
</wsdl:operation>
<wsdl:operation name="QueryNamedSets">
  <wsdl:input message="tns:QueryNamedSetsSoapIn"/>
  <wsdl:output message="tns:QueryNamedSetsSoapOut"/>
</wsdl:operation>
<wsdl:operation name="QueryNamedSetsFromDataSource">
  <wsdl:input message="tns:QueryNamedSetsFromDataSourceSoapIn"/>
  <wsdl:output message="tns:QueryNamedSetsFromDataSourceSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetAnnotationSetting">
  <wsdl:input message="tns:GetAnnotationSettingSoapIn"/>
  <wsdl:output message="tns:GetAnnotationSettingSoapOut"/>
</wsdl:operation>
<wsdl:operation name="ValidateKpi">
  <wsdl:input message="tns:ValidateKpiSoapIn"/>
  <wsdl:output message="tns:ValidateKpiSoapOut"/>
</wsdl:operation>
<wsdl:operation name="ValidateScorecard">
  <wsdl:input message="tns:ValidateScorecardSoapIn"/>
  <wsdl:output message="tns:ValidateScorecardSoapOut"/>
</wsdl:operation>
<wsdl:operation name="ValidateSiteCollection">
  <wsdl:input message="tns:ValidateSiteCollectionSoapIn"/>
  <wsdl:output message="tns:ValidateSiteCollectionSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetCurrentCultureLcid">
  <wsdl:input message="tns:GetCurrentCultureLcidSoapIn"/>
  <wsdl:output message="tns:GetCurrentCultureLcidSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetCurrentUserInfo">
  <wsdl:input message="tns:GetCurrentUserInfoSoapIn"/>
  <wsdl:output message="tns:GetCurrentUserInfoSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GenerateView">
  <wsdl:input message="tns:GenerateViewSoapIn"/>
  <wsdl:output message="tns:GenerateViewSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GenerateViewDirect">
  <wsdl:input message="tns:GenerateViewDirectSoapIn"/>
  <wsdl:output message="tns:GenerateViewDirectSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetAsKpis">
  <wsdl:input message="tns:GetAsKpisSoapIn"/>
  <wsdl:output message="tns:GetAsKpisSoapOut"/>
</wsdl:operation>
<wsdl:operation name="CreateDashboard">
  <wsdl:input message="tns:CreateDashboardSoapIn"/>

```

```

        <wsdl:output message="tns:CreateDashboardSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="UpdateDashboard">
        <wsdl:input message="tns:UpdateDashboardSoapIn"/>
        <wsdl:output message="tns:UpdateDashboardSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="GetDashboard">
        <wsdl:input message="tns:GetDashboardSoapIn"/>
        <wsdl:output message="tns:GetDashboardSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="DeleteDashboard">
        <wsdl:input message="tns>DeleteDashboardSoapIn"/>
        <wsdl:output message="tns>DeleteDashboardSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="ImportDashboard">
        <wsdl:input message="tns:ImportDashboardSoapIn"/>
        <wsdl:output message="tns:ImportDashboardSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="ExportDashboard">
        <wsdl:input message="tns:ExportDashboardSoapIn"/>
        <wsdl:output message="tns:ExportDashboardSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="GetParameterDisplayData">
        <wsdl:input message="tns:GetParameterDisplayDataSoapIn"/>
        <wsdl:output message="tns:GetParameterDisplayDataSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="QueryTimeIntelligence">
        <wsdl:input message="tns:QueryTimeIntelligenceSoapIn"/>
        <wsdl:output message="tns:QueryTimeIntelligenceSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="QueryTimeIntelligenceDirect">
        <wsdl:input message="tns:QueryTimeIntelligenceDirectSoapIn"/>
        <wsdl:output message="tns:QueryTimeIntelligenceDirectSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="GetRegisteredCustomFCOs">
        <wsdl:input message="tns:GetRegisteredCustomFCOsSoapIn"/>
        <wsdl:output message="tns:GetRegisteredCustomFCOsSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="GetListItems">
        <wsdl:input message="tns:GetListItemsSoapIn"/>
        <wsdl:output message="tns:GetListItemsSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="GetDependentElements">
        <wsdl:input message="tns:GetDependentElementsSoapIn"/>
        <wsdl:output message="tns:GetDependentElementsSoapOut"/>
    </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="PPSAuthoringServiceSoap" type="tns:PPSAuthoringServiceSoap">
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="CreateDataSource">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateDataSource"
style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>

```

```

    </wsdl:operation>
    <wsdl:operation name="UpdateDataSource">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateDataSource"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetDataSource">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDataSource"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteDataSource">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteDataSource"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CreateKpi">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateKpi"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateKpi">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateKpi"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetKpisFromScorecard">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetKpisFromScorecard"
style="document"/>

```

```

    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetKpi">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetKpi" style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeleteKpi">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteKpi"
style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="CreateScorecard">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateScorecard"
style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateScorecard">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateScorecard"
style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetScorecard">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetScorecard"
style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>

```

```

    </wsdl:operation>
    <wsdl:operation name="DeleteScorecard">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteScorecard"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CreateFilter">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateFilter"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateFilter">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateFilter"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetFilter">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetFilter"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteFilter">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteFilter"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CreateIndicator">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateIndicator"
style="document"/>

```



```

    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateIndicator">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateIndicator"
style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetIndicator">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetIndicator"
style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeleteIndicator">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteIndicator"
style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="CreateReportView">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateReportView"
style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateReportView">
  <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateReportView"
style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>

```

```

    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetReportView">
    <soap:operation
      soapAction="http://www.microsoft.com/performancepoint/scorecards/GetReportView"
      style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="DeleteReportView">
    <soap:operation
      soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteReportView"
      style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetAnalyticReportView">
    <soap:operation
      soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAnalyticReportView"
      style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetLatestAnalyticReportVersion">
    <soap:operation
      soapAction="http://www.microsoft.com/performancepoint/scorecards/GetLatestAnalyticReportVersion"
      style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="SaveTemporaryAnalyticReport">
    <soap:operation
      soapAction="http://www.microsoft.com/performancepoint/scorecards/SaveTemporaryAnalyticReport"
      style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetQueryResultMembers">

```

```

    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetQueryResultMembers"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAnnotation">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAnnotation"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAnnotationByID">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAnnotationByID"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAllAnnotationsByScorecardLocation">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAllAnnotationsByScorecard
Location" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="CreateAnnotation">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateAnnotation"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateAnnotation">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateAnnotation"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>

```

```

        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteAnnotation">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteAnnotation"
style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="TrimAnnotationByScorecardLocation">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/TrimAnnotationByScorecardLoc
ation" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="TrimAnnotationByOwner">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/TrimAnnotationByOwner"
style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="TrimAnnotationUntouchedSince">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/TrimAnnotationUntouchedSince
" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetDatabaseNamesFromDataSource">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDatabaseNamesFromDataSour
ce" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>

```

```

    <wsdl:operation name="GetMdx">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetMdx" style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetCubeNameInfos">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCubeNameInfos"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetPreviewDataSet">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetPreviewDataSet"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="TestConnection">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/TestConnection"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetCubeMetaData">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCubeMetaData"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetCubeMetaDataForDataSource">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCubeMetaDataForDataSource"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>

```

```

    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetDimensions">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDimensions"
style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetDimensionsFromDataSource">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDimensionsFromDataSource"
style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetCube">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCube" style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetCubeFromDataSource">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCubeFromDataSource"
style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="QueryDimensionRootMembers">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryDimensionRootMembers"
style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="QueryDimensionRootMembersFromDataSource">

```

```

    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryDimensionRootMembersFromDataSource" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="QueryTransformMembers">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryTransformMembers"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="QueryChildMembers">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryChildMembers"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="QueryChildMembersFromDataSource">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryChildMembersFromDataSource" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="QueryChildMembersByRangeFromDataSource">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryChildMembersByRangeFromDataSource" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="QueryRelatedMember">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryRelatedMember"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>

```

```

        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryRelatedMemberFromDataSource">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryRelatedMemberFromDataSo
urce" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryNamedSets">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryNamedSets"
style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryNamedSetsFromDataSource">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryNamedSetsFromDataSoure
" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetAnnotationSetting">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAnnotationSetting"
style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="ValidateKpi">
        <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ValidateKpi"
style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>

```



```

    <wsdl:operation name="ValidateScorecard">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ValidateScorecard"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="ValidateSiteCollection">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ValidateSiteCollection"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetCurrentCultureLcid">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCurrentCultureLcid"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetCurrentUserInfo">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCurrentUserInfo"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GenerateView">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GenerateView"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GenerateViewDirect">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GenerateViewDirect"
style="document"/>
      <wsdl:input>

```

```

        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAsKpis">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAsKpis"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="CreateDashboard">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateDashboard"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateDashboard">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateDashboard"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDashboard">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDashboard"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeleteDashboard">
    <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteDashboard"
style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>

```

```

    </wsdl:operation>
    <wsdl:operation name="ImportDashboard">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ImportDashboard"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="ExportDashboard">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ExportDashboard"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetParameterDisplayData">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetParameterDisplayData"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryTimeIntelligence">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryTimeIntelligence"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryTimeIntelligenceDirect">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryTimeIntelligenceDirect"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetRegisteredCustomFCOs">
      <soap:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetRegisteredCustomFCOs"
style="document"/>

```

```

        <wsdl:input>
          <soap:body use="literal"/>
        </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetListItems">
      <soap:operation
        soapAction="http://www.microsoft.com/performancepoint/scorecards/GetListItems"
        style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetDependentElements">
      <soap:operation
        soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDependentElements"
        style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
  </wsdl:binding>
  <wsdl:binding name="PPSAuthoringServiceSoap12" type="tns:PPSAuthoringServiceSoap">
    <soap12:binding transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="CreateDataSource">
      <soap12:operation
        soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateDataSource"
        style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateDataSource">
      <soap12:operation
        soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateDataSource"
        style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetDataSource">
      <soap12:operation
        soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDataSource"
        style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>

```

```

        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteDataSource">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteDataSource"
style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CreateKpi">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateKpi"
style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateKpi">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateKpi"
style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetKpisFromScorecard">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetKpisFromScorecard"
style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetKpi">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetKpi" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteKpi">

```

```

    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteKpi"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="CreateScorecard">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateScorecard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateScorecard">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateScorecard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetScorecard">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetScorecard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeleteScorecard">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteScorecard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="CreateFilter">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateFilter"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>

```

```

    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="UpdateFilter">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateFilter"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetFilter">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetFilter"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="DeleteFilter">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteFilter"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="CreateIndicator">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateIndicator"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="UpdateIndicator">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateIndicator"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>

```

```

    <wsdl:operation name="GetIndicator">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetIndicator"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteIndicator">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteIndicator"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CreateReportView">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateReportView"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateReportView">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateReportView"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetReportView">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetReportView"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteReportView">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteReportView"
style="document"/>
      <wsdl:input>

```



```

        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAnalyticReportView">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAnalyticReportView"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetLatestAnalyticReportVersion">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetLatestAnalyticReportVersi
on" style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="SaveTemporaryAnalyticReport">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/SaveTemporaryAnalyticReport"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetQueryResultMembers">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetQueryResultMembers"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAnnotation">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAnnotation"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>

```

```

    </wsdl:operation>
    <wsdl:operation name="GetAnnotationByID">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAnnotationByID"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetAllAnnotationsByScorecardLocation">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAllAnnotationsByScorecard
Location" style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CreateAnnotation">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateAnnotation"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateAnnotation">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateAnnotation"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteAnnotation">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteAnnotation"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="TrimAnnotationByScorecardLocation">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/TrimAnnotationByScorecardLoc
ation" style="document"/>

```

```

    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="TrimAnnotationByOwner">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/TrimAnnotationByOwner"
style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="TrimAnnotationUntouchedSince">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/TrimAnnotationUntouchedSince"
style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDatabaseNamesFromDataSource">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDatabaseNamesFromDataSou
ce" style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetMdx">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetMdx" style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetCubeNameInfos">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCubeNameInfos"
style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>

```

```

    </wsdl:operation>
    <wsdl:operation name="GetPreviewDataSet">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetPreviewDataSet"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="TestConnection">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/TestConnection"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetCubeMetaData">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCubeMetaData"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetCubeMetaDataForDataSource">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCubeMetaDataForDataSource"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetDimensions">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDimensions"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetDimensionsFromDataSource">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDimensionsFromDataSource"
style="document"/>

```

```

    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetCube">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCube" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetCubeFromDataSource">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCubeFromDataSource"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="QueryDimensionRootMembers">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryDimensionRootMembers"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="QueryDimensionRootMembersFromDataSource">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryDimensionRootMembersFromDataSource" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="QueryTransformMembers">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryTransformMembers"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>

```

```

    </wsdl:operation>
    <wsdl:operation name="QueryChildMembers">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryChildMembers"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryChildMembersFromDataSource">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryChildMembersFromDataSou
rce" style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryChildMembersByRangeFromDataSource">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryChildMembersByRangeFrom
DataSource" style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryRelatedMember">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryRelatedMember"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryRelatedMemberFromDataSource">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryRelatedMemberFromDataSo
urce" style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryNamedSets">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryNamedSets"
style="document"/>

```

```

    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="QueryNamedSetsFromDataSource">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryNamedSetsFromDataSource"
style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAnnotationSetting">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAnnotationSetting"
style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ValidateKpi">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ValidateKpi"
style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ValidateScorecard">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ValidateScorecard"
style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ValidateSiteCollection">
  <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ValidateSiteCollection"
style="document"/>
  <wsdl:input>
    <soap12:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal"/>
  </wsdl:output>

```

```

    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetCurrentCultureLcid">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCurrentCultureLcid"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetCurrentUserInfo">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetCurrentUserInfo"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GenerateView">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GenerateView"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GenerateViewDirect">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GenerateViewDirect"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetAsKpis">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetAsKpis"
style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="CreateDashboard">

```



```

    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/CreateDashboard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateDashboard">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/UpdateDashboard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDashboard">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDashboard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeleteDashboard">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/DeleteDashboard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ImportDashboard">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ImportDashboard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ExportDashboard">
    <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/ExportDashboard"
style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>

```

```

        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetParameterDisplayData">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetParameterDisplayData"
style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryTimeIntelligence">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryTimeIntelligence"
style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="QueryTimeIntelligenceDirect">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/QueryTimeIntelligenceDirect"
style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetRegisteredCustomFCOs">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetRegisteredCustomFCOs"
style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetListItems">
        <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetListItems"
style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>

```

```

    <wsdl:operation name="GetDependentElements">
      <soap12:operation
soapAction="http://www.microsoft.com/performancepoint/scorecards/GetDependentElements"
style="document"/>
      <wsdl:input>
        <soap12:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap12:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
  </wsdl:binding>
  <wsdl:message name="CreateAnnotationSoapIn">
    <wsdl:part name="parameters" element="tns:CreateAnnotation"/>
  </wsdl:message>
  <wsdl:message name="CreateAnnotationSoapOut">
    <wsdl:part name="parameters" element="tns:CreateAnnotationResponse"/>
  </wsdl:message>
  <wsdl:message name="CreateDashboardSoapIn">
    <wsdl:part name="parameters" element="tns:CreateDashboard"/>
  </wsdl:message>
  <wsdl:message name="CreateDashboardSoapOut">
    <wsdl:part name="parameters" element="tns:CreateDashboardResponse"/>
  </wsdl:message>
  <wsdl:message name="CreateDataSourceSoapIn">
    <wsdl:part name="parameters" element="tns:CreateDataSource"/>
  </wsdl:message>
  <wsdl:message name="CreateDataSourceSoapOut">
    <wsdl:part name="parameters" element="tns:CreateDataSourceResponse"/>
  </wsdl:message>
  <wsdl:message name="CreateFilterSoapIn">
    <wsdl:part name="parameters" element="tns:CreateFilter"/>
  </wsdl:message>
  <wsdl:message name="CreateFilterSoapOut">
    <wsdl:part name="parameters" element="tns:CreateFilterResponse"/>
  </wsdl:message>
  <wsdl:message name="CreateIndicatorSoapIn">
    <wsdl:part name="parameters" element="tns:CreateIndicator"/>
  </wsdl:message>
  <wsdl:message name="CreateIndicatorSoapOut">
    <wsdl:part name="parameters" element="tns:CreateIndicatorResponse"/>
  </wsdl:message>
  <wsdl:message name="CreateKpiSoapIn">
    <wsdl:part name="parameters" element="tns:CreateKpi"/>
  </wsdl:message>
  <wsdl:message name="CreateKpiSoapOut">
    <wsdl:part name="parameters" element="tns:CreateKpiResponse"/>
  </wsdl:message>
  <wsdl:message name="CreateReportViewSoapIn">
    <wsdl:part name="parameters" element="tns:CreateReportView"/>
  </wsdl:message>
  <wsdl:message name="CreateReportViewSoapOut">
    <wsdl:part name="parameters" element="tns:CreateReportViewResponse"/>
  </wsdl:message>
  <wsdl:message name="CreateScorecardSoapIn">
    <wsdl:part name="parameters" element="tns:CreateScorecard"/>
  </wsdl:message>
  <wsdl:message name="CreateScorecardSoapOut">
    <wsdl:part name="parameters" element="tns:CreateScorecardResponse"/>
  </wsdl:message>

```

```

</wsdl:message>
<wsdl:message name="DeleteAnnotationSoapIn">
  <wsdl:part name="parameters" element="tns:DeleteAnnotation"/>
</wsdl:message>
<wsdl:message name="DeleteAnnotationSoapOut">
  <wsdl:part name="parameters" element="tns:DeleteAnnotationResponse"/>
</wsdl:message>
<wsdl:message name="DeleteDashboardSoapIn">
  <wsdl:part name="parameters" element="tns:DeleteDashboard"/>
</wsdl:message>
<wsdl:message name="DeleteDashboardSoapOut">
  <wsdl:part name="parameters" element="tns:DeleteDashboardResponse"/>
</wsdl:message>
<wsdl:message name="DeleteDataSourceSoapIn">
  <wsdl:part name="parameters" element="tns:DeleteDataSource"/>
</wsdl:message>
<wsdl:message name="DeleteDataSourceSoapOut">
  <wsdl:part name="parameters" element="tns:DeleteDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="DeleteFilterSoapIn">
  <wsdl:part name="parameters" element="tns:DeleteFilter"/>
</wsdl:message>
<wsdl:message name="DeleteFilterSoapOut">
  <wsdl:part name="parameters" element="tns:DeleteFilterResponse"/>
</wsdl:message>
<wsdl:message name="DeleteIndicatorSoapIn">
  <wsdl:part name="parameters" element="tns:DeleteIndicator"/>
</wsdl:message>
<wsdl:message name="DeleteIndicatorSoapOut">
  <wsdl:part name="parameters" element="tns:DeleteIndicatorResponse"/>
</wsdl:message>
<wsdl:message name="DeleteKpiSoapIn">
  <wsdl:part name="parameters" element="tns:DeleteKpi"/>
</wsdl:message>
<wsdl:message name="DeleteKpiSoapOut">
  <wsdl:part name="parameters" element="tns:DeleteKpiResponse"/>
</wsdl:message>
<wsdl:message name="DeleteReportViewSoapIn">
  <wsdl:part name="parameters" element="tns:DeleteReportView"/>
</wsdl:message>
<wsdl:message name="DeleteReportViewSoapOut">
  <wsdl:part name="parameters" element="tns:DeleteReportViewResponse"/>
</wsdl:message>
<wsdl:message name="DeleteScorecardSoapIn">
  <wsdl:part name="parameters" element="tns:DeleteScorecard"/>
</wsdl:message>
<wsdl:message name="DeleteScorecardSoapOut">
  <wsdl:part name="parameters" element="tns:DeleteScorecardResponse"/>
</wsdl:message>
<wsdl:message name="ExportDashboardSoapIn">
  <wsdl:part name="parameters" element="tns:ExportDashboard"/>
</wsdl:message>
<wsdl:message name="ExportDashboardSoapOut">
  <wsdl:part name="parameters" element="tns:ExportDashboardResponse"/>
</wsdl:message>
<wsdl:message name="GenerateViewDirectSoapIn">
  <wsdl:part name="parameters" element="tns:GenerateViewDirect"/>
</wsdl:message>
<wsdl:message name="GenerateViewDirectSoapOut">

```

```

    <wsdl:part name="parameters" element="tns:GenerateViewDirectResponse"/>
</wsdl:message>
<wsdl:message name="GenerateViewSoapIn">
    <wsdl:part name="parameters" element="tns:GenerateView"/>
</wsdl:message>
<wsdl:message name="GenerateViewSoapOut">
    <wsdl:part name="parameters" element="tns:GenerateViewResponse"/>
</wsdl:message>
<wsdl:message name="GetAllAnnotationsByScorecardLocationSoapIn">
    <wsdl:part name="parameters" element="tns:GetAllAnnotationsByScorecardLocation"/>
</wsdl:message>
<wsdl:message name="GetAllAnnotationsByScorecardLocationSoapOut">
    <wsdl:part name="parameters" element="tns:GetAllAnnotationsByScorecardLocationResponse"/>
</wsdl:message>
<wsdl:message name="GetAnalyticReportViewSoapIn">
    <wsdl:part name="parameters" element="tns:GetAnalyticReportView"/>
</wsdl:message>
<wsdl:message name="GetAnalyticReportViewSoapOut">
    <wsdl:part name="parameters" element="tns:GetAnalyticReportViewResponse"/>
</wsdl:message>
<wsdl:message name="GetAnnotationByIDSoapIn">
    <wsdl:part name="parameters" element="tns:GetAnnotationByID"/>
</wsdl:message>
<wsdl:message name="GetAnnotationByIDSoapOut">
    <wsdl:part name="parameters" element="tns:GetAnnotationByIDResponse"/>
</wsdl:message>
<wsdl:message name="GetAnnotationSettingHttpGetIn">
<wsdl:message name="GetAnnotationSettingHttpGetOut">
    <wsdl:part name="Body" element="tns:AnnotationSetting"/>
</wsdl:message>
<wsdl:message name="GetAnnotationSettingHttpPostIn">
<wsdl:message name="GetAnnotationSettingHttpPostOut">
    <wsdl:part name="Body" element="tns:AnnotationSetting"/>
</wsdl:message>
<wsdl:message name="GetAnnotationSettingSoapIn">
    <wsdl:part name="parameters" element="tns:GetAnnotationSetting"/>
</wsdl:message>
<wsdl:message name="GetAnnotationSettingSoapOut">
    <wsdl:part name="parameters" element="tns:GetAnnotationSettingResponse"/>
</wsdl:message>
<wsdl:message name="GetAnnotationSoapIn">
    <wsdl:part name="parameters" element="tns:GetAnnotation"/>
</wsdl:message>
<wsdl:message name="GetAnnotationSoapOut">
    <wsdl:part name="parameters" element="tns:GetAnnotationResponse"/>
</wsdl:message>
<wsdl:message name="GetAsKpisSoapIn">
    <wsdl:part name="parameters" element="tns:GetAsKpis"/>
</wsdl:message>
<wsdl:message name="GetAsKpisSoapOut">
    <wsdl:part name="parameters" element="tns:GetAsKpisResponse"/>
</wsdl:message>
<wsdl:message name="GetCubeFromDataSourceSoapIn">
    <wsdl:part name="parameters" element="tns:GetCubeFromDataSource"/>
</wsdl:message>
<wsdl:message name="GetCubeFromDataSourceSoapOut">
    <wsdl:part name="parameters" element="tns:GetCubeFromDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="GetCubeMetaDataForDataSourceSoapIn">

```

```

    <wsdl:part name="parameters" element="tns:GetCubeMetaDataForDataSource"/>
</wsdl:message>
<wsdl:message name="GetCubeMetaDataForDataSourceSoapOut">
    <wsdl:part name="parameters" element="tns:GetCubeMetaDataForDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="GetCubeMetaDataSoapIn">
    <wsdl:part name="parameters" element="tns:GetCubeMetaData"/>
</wsdl:message>
<wsdl:message name="GetCubeMetaDataSoapOut">
    <wsdl:part name="parameters" element="tns:GetCubeMetaDataResponse"/>
</wsdl:message>
<wsdl:message name="GetCubeNameInfosSoapIn">
    <wsdl:part name="parameters" element="tns:GetCubeNameInfos"/>
</wsdl:message>
<wsdl:message name="GetCubeNameInfosSoapOut">
    <wsdl:part name="parameters" element="tns:GetCubeNameInfosResponse"/>
</wsdl:message>
<wsdl:message name="GetCubeSoapIn">
    <wsdl:part name="parameters" element="tns:GetCube"/>
</wsdl:message>
<wsdl:message name="GetCubeSoapOut">
    <wsdl:part name="parameters" element="tns:GetCubeResponse"/>
</wsdl:message>
<wsdl:message name="GetCurrentCultureLcidHttpGetIn"/>
<wsdl:message name="GetCurrentCultureLcidHttpGetOut">
    <wsdl:part name="Body" element="tns:int"/>
</wsdl:message>
<wsdl:message name="GetCurrentCultureLcidHttpPostIn"/>
<wsdl:message name="GetCurrentCultureLcidHttpPostOut">
    <wsdl:part name="Body" element="tns:int"/>
</wsdl:message>
<wsdl:message name="GetCurrentCultureLcidSoapIn">
    <wsdl:part name="parameters" element="tns:GetCurrentCultureLcid"/>
</wsdl:message>
<wsdl:message name="GetCurrentCultureLcidSoapOut">
    <wsdl:part name="parameters" element="tns:GetCurrentCultureLcidResponse"/>
</wsdl:message>
<wsdl:message name="GetCurrentUserInfoSoapIn">
    <wsdl:part name="parameters" element="tns:GetCurrentUserInfo"/>
</wsdl:message>
<wsdl:message name="GetCurrentUserInfoSoapOut">
    <wsdl:part name="parameters" element="tns:GetCurrentUserInfoResponse"/>
</wsdl:message>
<wsdl:message name="GetDashboardSoapIn">
    <wsdl:part name="parameters" element="tns:GetDashboard"/>
</wsdl:message>
<wsdl:message name="GetDashboardSoapOut">
    <wsdl:part name="parameters" element="tns:GetDashboardResponse"/>
</wsdl:message>
<wsdl:message name="GetDatabaseNamesFromDataSourceSoapIn">
    <wsdl:part name="parameters" element="tns:GetDatabaseNamesFromDataSource"/>
</wsdl:message>
<wsdl:message name="GetDatabaseNamesFromDataSourceSoapOut">
    <wsdl:part name="parameters" element="tns:GetDatabaseNamesFromDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="GetDataSourceSoapIn">
    <wsdl:part name="parameters" element="tns:GetDataSource"/>
</wsdl:message>
<wsdl:message name="GetDataSourceSoapOut">

```

```

    <wsdl:part name="parameters" element="tns:GetDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="GetDependentElementsSoapIn">
  <wsdl:part name="parameters" element="tns:GetDependentElements"/>
</wsdl:message>
<wsdl:message name="GetDependentElementsSoapOut">
  <wsdl:part name="parameters" element="tns:GetDependentElementsResponse"/>
</wsdl:message>
<wsdl:message name="GetDimensionsFromDataSourceSoapIn">
  <wsdl:part name="parameters" element="tns:GetDimensionsFromDataSource"/>
</wsdl:message>
<wsdl:message name="GetDimensionsFromDataSourceSoapOut">
  <wsdl:part name="parameters" element="tns:GetDimensionsFromDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="GetDimensionsSoapIn">
  <wsdl:part name="parameters" element="tns:GetDimensions"/>
</wsdl:message>
<wsdl:message name="GetDimensionsSoapOut">
  <wsdl:part name="parameters" element="tns:GetDimensionsResponse"/>
</wsdl:message>
<wsdl:message name="GetFilterSoapIn">
  <wsdl:part name="parameters" element="tns:GetFilter"/>
</wsdl:message>
<wsdl:message name="GetFilterSoapOut">
  <wsdl:part name="parameters" element="tns:GetFilterResponse"/>
</wsdl:message>
<wsdl:message name="GetIndicatorSoapIn">
  <wsdl:part name="parameters" element="tns:GetIndicator"/>
</wsdl:message>
<wsdl:message name="GetIndicatorSoapOut">
  <wsdl:part name="parameters" element="tns:GetIndicatorResponse"/>
</wsdl:message>
<wsdl:message name="GetKpisFromScorecardSoapIn">
  <wsdl:part name="parameters" element="tns:GetKpisFromScorecard"/>
</wsdl:message>
<wsdl:message name="GetKpisFromScorecardSoapOut">
  <wsdl:part name="parameters" element="tns:GetKpisFromScorecardResponse"/>
</wsdl:message>
<wsdl:message name="GetKpiSoapIn">
  <wsdl:part name="parameters" element="tns:GetKpi"/>
</wsdl:message>
<wsdl:message name="GetKpiSoapOut">
  <wsdl:part name="parameters" element="tns:GetKpiResponse"/>
</wsdl:message>
<wsdl:message name="GetLatestAnalyticReportVersionSoapIn">
  <wsdl:part name="parameters" element="tns:GetLatestAnalyticReportVersion"/>
</wsdl:message>
<wsdl:message name="GetLatestAnalyticReportVersionSoapOut">
  <wsdl:part name="parameters" element="tns:GetLatestAnalyticReportVersionResponse"/>
</wsdl:message>
<wsdl:message name="GetListItemsHttpGetIn">
  <wsdl:part name="listUrl" type="xs:string"/>
</wsdl:message>
<wsdl:message name="GetListItemsHttpGetOut">
  <wsdl:part name="Body" element="tns:ArrayOfFirstClassElement"/>
</wsdl:message>
<wsdl:message name="GetListItemsHttpPostIn">
  <wsdl:part name="listUrl" type="xs:string"/>
</wsdl:message>

```

```

<wsdl:message name="GetListItemsHttpPostOut">
  <wsdl:part name="Body" element="tns:ArrayOfFirstClassElement"/>
</wsdl:message>
<wsdl:message name="GetListItemsSoapIn">
  <wsdl:part name="parameters" element="tns:GetListItems"/>
</wsdl:message>
<wsdl:message name="GetListItemsSoapOut">
  <wsdl:part name="parameters" element="tns:GetListItemsResponse"/>
</wsdl:message>
<wsdl:message name="GetMdxSoapIn">
  <wsdl:part name="parameters" element="tns:GetMdx"/>
</wsdl:message>
<wsdl:message name="GetMdxSoapOut">
  <wsdl:part name="parameters" element="tns:GetMdxResponse"/>
</wsdl:message>
<wsdl:message name="GetParameterDisplayDataSoapIn">
  <wsdl:part name="parameters" element="tns:GetParameterDisplayData"/>
</wsdl:message>
<wsdl:message name="GetParameterDisplayDataSoapOut">
  <wsdl:part name="parameters" element="tns:GetParameterDisplayDataResponse"/>
</wsdl:message>
<wsdl:message name="GetPreviewDataSetSoapIn">
  <wsdl:part name="parameters" element="tns:GetPreviewDataSet"/>
</wsdl:message>
<wsdl:message name="GetPreviewDataSetSoapOut">
  <wsdl:part name="parameters" element="tns:GetPreviewDataSetResponse"/>
</wsdl:message>
<wsdl:message name="GetQueryResultMembersSoapIn">
  <wsdl:part name="parameters" element="tns:GetQueryResultMembers"/>
</wsdl:message>
<wsdl:message name="GetQueryResultMembersSoapOut">
  <wsdl:part name="parameters" element="tns:GetQueryResultMembersResponse"/>
</wsdl:message>
<wsdl:message name="GetRegisteredCustomFCOsHttpGetIn">
  <wsdl:part name="type" type="xs:string"/>
</wsdl:message>
<wsdl:message name="GetRegisteredCustomFCOsHttpGetOut">
  <wsdl:part name="Body" element="tns:ArrayOfCustomFCODefinition"/>
</wsdl:message>
<wsdl:message name="GetRegisteredCustomFCOsHttpPostIn">
  <wsdl:part name="type" type="xs:string"/>
</wsdl:message>
<wsdl:message name="GetRegisteredCustomFCOsHttpPostOut">
  <wsdl:part name="Body" element="tns:ArrayOfCustomFCODefinition"/>
</wsdl:message>
<wsdl:message name="GetRegisteredCustomFCOsSoapIn">
  <wsdl:part name="parameters" element="tns:GetRegisteredCustomFCOs"/>
</wsdl:message>
<wsdl:message name="GetRegisteredCustomFCOsSoapOut">
  <wsdl:part name="parameters" element="tns:GetRegisteredCustomFCOsResponse"/>
</wsdl:message>
<wsdl:message name="GetReportViewSoapIn">
  <wsdl:part name="parameters" element="tns:GetReportView"/>
</wsdl:message>
<wsdl:message name="GetReportViewSoapOut">
  <wsdl:part name="parameters" element="tns:GetReportViewResponse"/>
</wsdl:message>
<wsdl:message name="GetScorecardSoapIn">
  <wsdl:part name="parameters" element="tns:GetScorecard"/>

```



```

</wsdl:message>
<wsdl:message name="GetScorecardSoapOut">
  <wsdl:part name="parameters" element="tns:GetScorecardResponse"/>
</wsdl:message>
<wsdl:message name="ImportDashboardSoapIn">
  <wsdl:part name="parameters" element="tns:ImportDashboard"/>
</wsdl:message>
<wsdl:message name="ImportDashboardSoapOut">
  <wsdl:part name="parameters" element="tns:ImportDashboardResponse"/>
</wsdl:message>
<wsdl:message name="QueryChildMembersByRangeFromDataSourceSoapIn">
  <wsdl:part name="parameters" element="tns:QueryChildMembersByRangeFromDataSource"/>
</wsdl:message>
<wsdl:message name="QueryChildMembersByRangeFromDataSourceSoapOut">
  <wsdl:part name="parameters"
element="tns:QueryChildMembersByRangeFromDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="QueryChildMembersFromDataSourceSoapIn">
  <wsdl:part name="parameters" element="tns:QueryChildMembersFromDataSource"/>
</wsdl:message>
<wsdl:message name="QueryChildMembersFromDataSourceSoapOut">
  <wsdl:part name="parameters" element="tns:QueryChildMembersFromDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="QueryChildMembersSoapIn">
  <wsdl:part name="parameters" element="tns:QueryChildMembers"/>
</wsdl:message>
<wsdl:message name="QueryChildMembersSoapOut">
  <wsdl:part name="parameters" element="tns:QueryChildMembersResponse"/>
</wsdl:message>
<wsdl:message name="QueryDimensionRootMembersFromDataSourceSoapIn">
  <wsdl:part name="parameters" element="tns:QueryDimensionRootMembersFromDataSource"/>
</wsdl:message>
<wsdl:message name="QueryDimensionRootMembersFromDataSourceSoapOut">
  <wsdl:part name="parameters"
element="tns:QueryDimensionRootMembersFromDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="QueryDimensionRootMembersSoapIn">
  <wsdl:part name="parameters" element="tns:QueryDimensionRootMembers"/>
</wsdl:message>
<wsdl:message name="QueryDimensionRootMembersSoapOut">
  <wsdl:part name="parameters" element="tns:QueryDimensionRootMembersResponse"/>
</wsdl:message>
<wsdl:message name="QueryNamedSetsFromDataSourceSoapIn">
  <wsdl:part name="parameters" element="tns:QueryNamedSetsFromDataSource"/>
</wsdl:message>
<wsdl:message name="QueryNamedSetsFromDataSourceSoapOut">
  <wsdl:part name="parameters" element="tns:QueryNamedSetsFromDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="QueryNamedSetsSoapIn">
  <wsdl:part name="parameters" element="tns:QueryNamedSets"/>
</wsdl:message>
<wsdl:message name="QueryNamedSetsSoapOut">
  <wsdl:part name="parameters" element="tns:QueryNamedSetsResponse"/>
</wsdl:message>
<wsdl:message name="QueryRelatedMemberFromDataSourceSoapIn">
  <wsdl:part name="parameters" element="tns:QueryRelatedMemberFromDataSource"/>
</wsdl:message>
<wsdl:message name="QueryRelatedMemberFromDataSourceSoapOut">
  <wsdl:part name="parameters" element="tns:QueryRelatedMemberFromDataSourceResponse"/>

```

```

</wsdl:message>
<wsdl:message name="QueryRelatedMemberSoapIn">
  <wsdl:part name="parameters" element="tns:QueryRelatedMember"/>
</wsdl:message>
<wsdl:message name="QueryRelatedMemberSoapOut">
  <wsdl:part name="parameters" element="tns:QueryRelatedMemberResponse"/>
</wsdl:message>
<wsdl:message name="QueryTimeIntelligenceDirectSoapIn">
  <wsdl:part name="parameters" element="tns:QueryTimeIntelligenceDirect"/>
</wsdl:message>
<wsdl:message name="QueryTimeIntelligenceDirectSoapOut">
  <wsdl:part name="parameters" element="tns:QueryTimeIntelligenceDirectResponse"/>
</wsdl:message>
<wsdl:message name="QueryTimeIntelligenceSoapIn">
  <wsdl:part name="parameters" element="tns:QueryTimeIntelligence"/>
</wsdl:message>
<wsdl:message name="QueryTimeIntelligenceSoapOut">
  <wsdl:part name="parameters" element="tns:QueryTimeIntelligenceResponse"/>
</wsdl:message>
<wsdl:message name="QueryTransformMembersSoapIn">
  <wsdl:part name="parameters" element="tns:QueryTransformMembers"/>
</wsdl:message>
<wsdl:message name="QueryTransformMembersSoapOut">
  <wsdl:part name="parameters" element="tns:QueryTransformMembersResponse"/>
</wsdl:message>
<wsdl:message name="SaveTemporaryAnalyticReportSoapIn">
  <wsdl:part name="parameters" element="tns:SaveTemporaryAnalyticReport"/>
</wsdl:message>
<wsdl:message name="SaveTemporaryAnalyticReportSoapOut">
  <wsdl:part name="parameters" element="tns:SaveTemporaryAnalyticReportResponse"/>
</wsdl:message>
<wsdl:message name="TestConnectionSoapIn">
  <wsdl:part name="parameters" element="tns:TestConnection"/>
</wsdl:message>
<wsdl:message name="TestConnectionSoapOut">
  <wsdl:part name="parameters" element="tns:TestConnectionResponse"/>
</wsdl:message>
<wsdl:message name="TrimAnnotationByOwnerHttpGetIn">
  <wsdl:part name="Owner" type="xs:string"/>
</wsdl:message>
<wsdl:message name="TrimAnnotationByOwnerHttpGetOut"/>
<wsdl:message name="TrimAnnotationByOwnerHttpPostIn">
  <wsdl:part name="Owner" type="xs:string"/>
</wsdl:message>
<wsdl:message name="TrimAnnotationByOwnerHttpPostOut"/>
<wsdl:message name="TrimAnnotationByOwnerSoapIn">
  <wsdl:part name="parameters" element="tns:TrimAnnotationByOwner"/>
</wsdl:message>
<wsdl:message name="TrimAnnotationByOwnerSoapOut">
  <wsdl:part name="parameters" element="tns:TrimAnnotationByOwnerResponse"/>
</wsdl:message>
<wsdl:message name="TrimAnnotationByScorecardLocationSoapIn">
  <wsdl:part name="parameters" element="tns:TrimAnnotationByScorecardLocation"/>
</wsdl:message>
<wsdl:message name="TrimAnnotationByScorecardLocationSoapOut">
  <wsdl:part name="parameters" element="tns:TrimAnnotationByScorecardLocationResponse"/>
</wsdl:message>
<wsdl:message name="TrimAnnotationUntouchedSinceHttpGetIn">
  <wsdl:part name="untouchedSince" type="xs:string"/>

```

```

</wsdl:message>
<wsdl:message name="TrimAnnotationUntouchedSinceHttpGetOut"/>
<wsdl:message name="TrimAnnotationUntouchedSinceHttpPostIn">
  <wsdl:part name="untouchedSince" type="xs:string"/>
</wsdl:message>
<wsdl:message name="TrimAnnotationUntouchedSinceHttpPostOut"/>
<wsdl:message name="TrimAnnotationUntouchedSinceSoapIn">
  <wsdl:part name="parameters" element="tns:TrimAnnotationUntouchedSince"/>
</wsdl:message>
<wsdl:message name="TrimAnnotationUntouchedSinceSoapOut">
  <wsdl:part name="parameters" element="tns:TrimAnnotationUntouchedSinceResponse"/>
</wsdl:message>
<wsdl:message name="UpdateAnnotationSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAnnotation"/>
</wsdl:message>
<wsdl:message name="UpdateAnnotationSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAnnotationResponse"/>
</wsdl:message>
<wsdl:message name="UpdateDashboardSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateDashboard"/>
</wsdl:message>
<wsdl:message name="UpdateDashboardSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateDashboardResponse"/>
</wsdl:message>
<wsdl:message name="UpdateDataSourceSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateDataSource"/>
</wsdl:message>
<wsdl:message name="UpdateDataSourceSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateDataSourceResponse"/>
</wsdl:message>
<wsdl:message name="UpdateFilterSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateFilter"/>
</wsdl:message>
<wsdl:message name="UpdateFilterSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateFilterResponse"/>
</wsdl:message>
<wsdl:message name="UpdateIndicatorSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateIndicator"/>
</wsdl:message>
<wsdl:message name="UpdateIndicatorSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateIndicatorResponse"/>
</wsdl:message>
<wsdl:message name="UpdateKpiSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateKpi"/>
</wsdl:message>
<wsdl:message name="UpdateKpiSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateKpiResponse"/>
</wsdl:message>
<wsdl:message name="UpdateReportViewSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateReportView"/>
</wsdl:message>
<wsdl:message name="UpdateReportViewSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateReportViewResponse"/>
</wsdl:message>
<wsdl:message name="UpdateScorecardSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateScorecard"/>
</wsdl:message>
<wsdl:message name="UpdateScorecardSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateScorecardResponse"/>

```

```
</wsdl:message>
<wsdl:message name="ValidateKpiSoapIn">
  <wsdl:part name="parameters" element="tns:ValidateKpi"/>
</wsdl:message>
<wsdl:message name="ValidateKpiSoapOut">
  <wsdl:part name="parameters" element="tns:ValidateKpiResponse"/>
</wsdl:message>
<wsdl:message name="ValidateScorecardSoapIn">
  <wsdl:part name="parameters" element="tns:ValidateScorecard"/>
</wsdl:message>
<wsdl:message name="ValidateScorecardSoapOut">
  <wsdl:part name="parameters" element="tns:ValidateScorecardResponse"/>
</wsdl:message>
<wsdl:message name="ValidateSiteCollectionSoapIn">
  <wsdl:part name="parameters" element="tns:ValidateSiteCollection"/>
</wsdl:message>
<wsdl:message name="ValidateSiteCollectionSoapOut">
  <wsdl:part name="parameters" element="tns:ValidateSiteCollectionResponse"/>
</wsdl:message>
</wsdl:definitions>
```

7 Appendix B: Full XML Schema

Schema name	Prefix	Section
http://performancepoint.microsoft.com/OLAPQueryData	qdata	7.1
http://schemas.microsoft.com/performancepoint/2007/03/query	query	7.2
http://www.microsoft.com/performancepoint/scorecards/Analytics	Unassigned	7.3

For ease of implementation, the following sections provide the full XML schema for this protocol.

7.1 http://performancepoint.microsoft.com/OLAPQueryData Schema

```
<?xml version="1.0"?>
<xs:schema xmlns:tns="http://www.microsoft.com/performancepoint/scorecards"
attributeFormDefault="unqualified" elementFormDefault="qualified"
targetNamespace="http://performancepoint.microsoft.com/OLAPQueryData"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://www.microsoft.com/performancepoint/scorecards"/>
  <xs:complexType name="OLAPQueryData">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="Parameters" type="tns:ArrayOfParameter"/>
      <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
      <xs:element minOccurs="0" maxOccurs="1" name="MDX" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

7.2 http://schemas.microsoft.com/performancepoint/2007/03/query Schema

```
<?xml version="1.0"?>
<xs:schema xmlns:tns="http://www.microsoft.com/performancepoint/scorecards"
attributeFormDefault="unqualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/performancepoint/2007/03/query"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://www.microsoft.com/performancepoint/scorecards"/>
  <xs:complexType name="QueryState">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="Axes" type="tns:ArrayOfAxis"/>
      <xs:element minOccurs="1" maxOccurs="1" name="IsEnabled" type="xs:boolean"/>
      <xs:element minOccurs="1" maxOccurs="1" name="UnknownFilterParameter"
type="xs:boolean"/>
      <xs:element minOccurs="1" maxOccurs="1" name="ShowDataSourceFormatting"
type="xs:boolean"/>
      <xs:element minOccurs="0" maxOccurs="1" name="DataSourceLocation"
type="tns:RepositoryLocation"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

7.3 http://www.microsoft.com/performancepoint/scorecards/Analytics Schema

```
<?xml version="1.0"?>
```

```
<xs:schema xmlns:tns="http://www.microsoft.com/performancepoint/scorecards"
attributeFormDefault="unqualified" elementFormDefault="qualified"
targetNamespace="http://www.microsoft.com/performancepoint/scorecards/Analytics"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://www.microsoft.com/performancepoint/scorecards"/>
  <xs:complexType name="Tuple">
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="memberDictionary"
type="tns:SerializableDictionary"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- PerformancePoint Services in Microsoft SharePoint Server 2010
- PerformancePoint Services in Microsoft SharePoint Server 2010
- Microsoft SharePoint Server 2010
- Microsoft SharePoint Server 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

<1> [Section 2.2.2.1.3](#): The content store refers to a SharePoint Server 2010 list.

<2> [Section 2.2.2.1.3](#): Data sources are stored in document libraries in SharePoint Server 2010.

<3> [Section 2.2.2.1.3](#): The content store refers to a SharePoint Server 2010 list.

<4> [Section 2.2.2.1.3](#): The content store refers to a SharePoint Server 2010 list.

<5> [Section 2.2.2.1.3](#): The content store refers to a SharePoint Server 2010 list.

<6> [Section 2.2.2.1.3](#): The content store refers to a SharePoint Server 2010 list.

<7> [Section 2.2.2.1.3](#): The content store refers to a SharePoint Server 2010 list.

<8> [Section 2.2.4](#): This type is available only in SharePoint Server 2013.

<9> [Section 2.2.4](#): This type is available only in SharePoint Server 2013.

<10> [Section 2.2.4](#): This type is available only in SharePoint Server 2013.

<11> [Section 2.2.4.48](#): This type is available only in SharePoint Server 2013.

<12> [Section 2.2.4.75](#): This type is available only in SharePoint Server 2013.

<13> [Section 2.2.4.83](#): The values for **UnderlyingElementTypeName** for the built-in element types in PerformancePoint Services 2010 are:

Type	Value
Scorecard	Microsoft.PerformancePoint.Scorecards.Scorecard, Microsoft.PerformancePoint.Scorecards.Client, Version=14.0.0.0, Culture=neutral, PublicKeyToken=71e9bce111e9429c
ReportView	Microsoft.PerformancePoint.Scorecards.ReportView,

Type	Value
	Microsoft.PerformancePoint.Scorecards.Client, Version=14.0.0.0, Culture=neutral, PublicKeyToken=71e9bce111e9429c
▪ Filter	Microsoft.PerformancePoint.Scorecards.Filter, Microsoft.PerformancePoint.Scorecards.Client, Version=14.0.0.0, Culture=neutral, PublicKeyToken=71e9bce111e9429c

<14> [Section 2.2.4.85](#): The list data source refers to a SharePoint Server 2010 list.

<15> [Section 2.2.4.99](#): For SharePoint Server 2010, the content store is a SharePoint list.

<16> [Section 2.2.4.123](#): The registered transforms can be found in the web.config file under the CustomViewTransforms section. The content for the PropertyBag of each transform is determined by what is chosen to be passed in through the parameter.

<17> [Section 2.2.4.167](#): In PerformancePoint Services 2010, the identifier is generated by obtaining the **UTF-8** formatted bytes of the indicator's relative URL, computing an MD5 hash of those bytes and formatting the 16 byte hash to a GUID value format.

<18> [Section 2.2.4.180](#): This type is available only in SharePoint Server 2013.

<19> [Section 2.2.5.6](#): Beta2 or RTM refers to PerformancePoint Services 2010 Beta2 or PerformancePoint Services 2010.

<20> [Section 2.2.5.6](#): Beta1 refers to PerformancePoint Services 2010 Beta1.

<21> [Section 2.2.5.6](#): Microsoft Office PerformancePoint Server 2007

<22> [Section 3.1.2](#): In PerformancePoint Services 2010, the default query timeout is 300 seconds.

<23> [Section 3.1.4](#): This operation is available only in SharePoint Server 2013.

<24> [Section 3.1.4](#): This operation is available only in SharePoint Server 2013.

<25> [Section 3.1.4.16](#): The content store refers to a SharePoint Server 2010 list.

<26> [Section 3.1.4.17](#): This operation is available only in SharePoint Server 2013.

<27> [Section 3.1.4.21](#): PerformancePoint Services 2010 returns a **GetAnalyticReportViewResponse** (see section [3.1.4.44.2.2](#)) containing a null value instead of a report view for failures unrelated to security restrictions.

<28> [Section 3.1.4.33](#): PerformancePoint Services 2010 returns an empty **GetDashboardResponse** (see section [3.1.4.33.2.2](#)) for failures unrelated to security restrictions.

<29> [Section 3.1.4.35](#): PerformancePoint Services 2010 returns a **GetDataSourceResponse** (section [3.1.4.35.2.2](#)) containing a null value instead of a data source (1) for failures unrelated to security restrictions.

<30> [Section 3.1.4.36](#): PerformancePoint Services 2010 returns a **GetDependentElementResponse** (see section [3.1.4.44.2.2](#)) containing an **DependentElementInfo** that contains a **FirstClassElementCollection** (see section [2.2.4.34](#)) with null elements for failures unrelated to security restrictions.

<31> [Section 3.1.4.39](#): PerformancePoint Services 2010 returns an empty **GetFilterResponse** element (section [3.1.4.39.2.2](#)) for failures unrelated to security restrictions.

<32> [Section 3.1.4.40](#): PerformancePoint Services 2010 returns a **GetIndicatorResponse** element (section [3.1.4.40.2.2](#)) containing a null value instead of an **Indicator** complex type (section [2.2.4.125](#)) for failures unrelated to security restrictions.

<33> [Section 3.1.4.41](#): PerformancePoint Services 2010 returns a **GetKpiResponse** (see section [3.1.4.44.2.2](#)) containing a null value instead of a **Kpi** for failures unrelated to security restrictions.

<34> [Section 3.1.4.44](#): PerformancePoint Services 2010 returns a **GetListItemsResponse** (see section [3.1.4.44.2.2](#)) containing an **ArrayOfFirstClassElements** (see section [2.2.4.34](#)) with null elements for failures unrelated to security restrictions.

<35> [Section 3.1.4.45](#): PerformancePoint Services 2010 returns a **GetMdxResponse** with an empty **GetMdxResult** for failures unrelated to security restrictions.

<36> [Section 3.1.4.46](#): In PerformancePoint Services 2010, **GetParameterDisplayData** receives the **GridViewData** (section [2.2.4.121](#)) as an untyped object referenced by the **customData** parameter on the **GetParameterDisplayDataIn** message (section [3.1.4.46.1.1](#)).

<37> [Section 3.1.4.47.2.1](#): PerformancePoint Services 2010 supports preview data sets for the following data source types: **ExcelWorkbook**, **ExcelServicesWorkbook**, **SqlTabularDataSource**, and **SPListDataSource**.

<38> [Section 3.1.4.50](#): PerformancePoint Services 2010 returns a **GetReportViewResponse** (see section [3.1.4.44.2.2](#)) containing a null value instead of a report view for failures unrelated to security restrictions.

<39> [Section 3.1.4.51](#): PerformancePoint Services 2010 returns an empty **GetScorecardResponse** (see section [3.1.4.51.2.2](#)) for failures unrelated to security restrictions.

<40> [Section 3.1.4.52](#): This operation is available only in SharePoint Server 2013.

<41> [Section 3.1.4.58](#): PerformancePoint Services 2010 returns a **QueryNamedSetsResponse** (section [3.1.4.58.2.2](#)) containing a **null** value instead of named sets for failures unrelated to security restrictions.

<42> [Section 3.1.4.59](#): PerformancePoint Services 2010 returns a **QueryNamedSetsFromDataSourceResponse** (see section [3.1.4.59.1.2](#)) containing an empty collection of named sets if null is passed in for the data source (1).

<43> [Section 3.1.4.60](#): PerformancePoint Services 2010 returns a **QueryRelatedMemberResponse** (see section [3.1.4.44.2.2](#)) containing null for failures unrelated to security restrictions.

<44> [Section 3.1.4.61](#): PerformancePoint Services 2010 returns a **QueryRelatedMemberFromDataSourceResponse** element (section [3.1.4.61.2.2](#)) containing null, if null is passed in for the data source (1).

<45> [Section 3.1.4.62](#): PerformancePoint Services 2010 returns a **QueryTimeIntelligenceResponse** (see section [3.1.4.44.2.2](#)) containing an Unknown error if an invalid **RepositoryLocation** (see section [2.2.4.161](#)) is passed in.

9 Change Tracking

This section identifies changes that were made to the [MS-PPSAS] protocol document between the July 2013 and November 2013 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.

- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
3.1.1 Abstract Data Model	Changed "...may each have multiple begin points and end points" to "...can each have multiple begin points and end points" for clarity.	N	Content updated.
3.1.4.43.2.1 GetLatestAnalyticReportVersion	Changed "SaveTemporaryAnalyticReportResult attribute" to "SaveTemporaryAnalyticReportResult element" in the description for the analyticReportViewId element.	N	Content updated.

10 Index

A

Abstract data model
 [server](#) 213
[AddAllMembersSetOpcomplex type](#) 57
[AddCalcMemberSetOpcomplex type](#) 57
[AddChildrenSetOpcomplex type](#) 57
[AddDefaultMemberSetOpcomplex type](#) 58
[AddDescendantsLeavesSetOpcomplex type](#) 58
[AddDescendantsSetOpcomplex type](#) 58
[AddDescendantsSubtreeSetOpcomplex type](#) 58
[AddFilterSetOpcomplex type](#) 59
[AddFilterTopBottomSetOpcomplex type](#) 59
[AddMemberSetOpcomplex type](#) 59
[AddNamedSetSetOpcomplex type](#) 60
[AddParentSiblingsSetOpcomplex type](#) 60
[AggregateTypeEnumsimple type](#) 181
[AliasInfocomplex type](#) 60
[AlignmentTypesimple type](#) 181
[AnalyticBaseReportViewDatacomplex type](#) 60
[AnalyticChartLegendcomplex type](#) 68
[AnalyticChartReportViewcomplex type](#) 69
[AnalyticChartTypesimple type](#) 182
[AnalyticGridReportViewcomplex type](#) 70
[AnalyticLegendLocationsimple type](#) 182
[AnalyticMarkerStylesimple type](#) 183
[AnnotationCommentcomplex type](#) 74
[Annotationcomplex type](#) 71
[AnnotationVersionssimple type](#) 184
[Applicability](#) 34
[ArrayOfAliasInfocomplex type](#) 74
[ArrayOfAnnotationCommentcomplex type](#) 75
[ArrayOfAxiscomplex type](#) 75
[ArrayOfBpmPropertycomplex type](#) 75
[ArrayOfBpmPropertyListItemcomplex type](#) 75
[ArrayOfChoice1complex type](#) 76
[ArrayOfCommentcomplex type](#) 77
[ArrayOfConfiguredViewcomplex type](#) 77
[ArrayOfDashboardElementcomplex type](#) 77
[ArrayOfDataColumnMappingcomplex type](#) 78
[ArrayOfDecimalcomplex type](#) 78
[ArrayOfDefaultDimensionSettingcomplex type](#) 78
[ArrayOfDimensioncomplex type](#) 78
[ArrayOfEndPointcomplex type](#) 79
[ArrayOfFirstClassElementcomplex type](#) 79
[ArrayOfGridCellcomplex type](#) 79
[ArrayOfGridDisplayElementcomplex type](#) 80
[ArrayOfGridHeaderItemcomplex type](#) 80
[ArrayOfGridViewTransformReferencecomplex type](#)
80
[ArrayOfHierarchycomplex type](#) 81
[ArrayOfIndicatorBandcomplex type](#) 81
[ArrayOfKpicomplex type](#) 81
[ArrayOfKpiMeasurecomplex type](#) 81
[ArrayOfLevelcomplex type](#) 82
[ArrayOfMeasurecomplex type](#) 82
[ArrayOfMembercomplex type](#) 82
[ArrayOfMemberTransformcomplex type](#) 83

[ArrayOfNamedSetcomplex type](#) 83
[ArrayOfNameInfocomplex type](#) 83
[ArrayOfParametercomplex type](#) 84
[ArrayOfParameterDefinitioncomplex type](#) 84
[ArrayOfParameterMappingcomplex type](#) 84
[ArrayOfPropertyBagcomplex type](#) 85
[ArrayOfSetOperationcomplex type](#) 85
[ArrayOfStringcomplex type](#) 85
[ArrayOfTargetcomplex type](#) 85
[ArrayOfTimeIntelligenceDataSourcecomplex type](#) 86
[ArrayOfTimeIntelligenceFormulacomplex type](#) 86
[ArrayOfTimeIntelligenceLevelBindingcomplex type](#)
86
[Attribute groups](#) 212
[Attributes](#) 212
[Axiscomplex type](#) 87
[AxisTypesimple type](#) 184

B

[Bandingcomplex type](#) 88
[BandTypesimple type](#) 185
[BeginPointEmitterTypesimple type](#) 185
[BpmExceptioncomplex type](#) 88
[BpmPropertyBoolcomplex type](#) 89
[BpmPropertycomplex type](#) 88
[BpmPropertyDatecomplex type](#) 89
[BpmPropertyDecimalcomplex type](#) 90
[BpmPropertyHyperlink2complex type](#) 90
[BpmPropertyHyperlinkcomplex type](#) 90
[BpmPropertyLinkBasecomplex type](#) 91
[BpmPropertyListcomplex type](#) 91
[BpmPropertyListItemcomplex type](#) 91
[BpmPropertyLongTextcomplex type](#) 92
[BpmPropertyTextcomplex type](#) 92
[BpmPropertyUsercomplex type](#) 92

C

[CalculatedFormulaInfocomplex type](#) 93
[CalculatedMembercomplex type](#) 93
[Capability negotiation](#) 35
[Change tracking](#) 586
Client
 [overview](#) 213
[Commentcomplex type](#) 94
Common data structures ([section 2.2.9](#) 212, [section 2.2.9](#) 212)
[Common list of error codes](#) 41
[Complex types](#) 43
 [AddAllMembersSetOp](#) 57
 [AddCalcMemberSetOp](#) 57
 [AddChildrenSetOp](#) 57
 [AddDefaultMemberSetOp](#) 58
 [AddDescendantsLeavesSetOp](#) 58
 [AddDescendantsSetOp](#) 58
 [AddDescendantsSubtreeSetOp](#) 58
 [AddFilterSetOp](#) 59

[AddFilterTopBottomSetOp](#) 59
[AddMemberSetOp](#) 59
[AddNamedSetSetOp](#) 60
[AddParentSiblingsSetOp](#) 60
[AliasInfo](#) 60
[AnalyticBaseReportViewData](#) 60
[AnalyticChartLegend](#) 68
[AnalyticChartReportView](#) 69
[AnalyticGridReportView](#) 70
[Annotation](#) 71
[AnnotationComment](#) 74
[ArrayOfAliasInfo](#) 74
[ArrayOfAnnotationComment](#) 75
[ArrayOfAxis](#) 75
[ArrayOfBpmProperty](#) 75
[ArrayOfBpmPropertyListItem](#) 75
[ArrayOfChoice1](#) 76
[ArrayOfComment](#) 77
[ArrayOfConfiguredView](#) 77
[ArrayOfDashboardElement](#) 77
[ArrayOfDataColumnMapping](#) 78
[ArrayOfDecimal](#) 78
[ArrayOfDefaultDimensionSetting](#) 78
[ArrayOfDimension](#) 78
[ArrayOfEndPoint](#) 79
[ArrayOfFirstClassElement](#) 79
[ArrayOfGridCell](#) 79
[ArrayOfGridDisplayElement](#) 80
[ArrayOfGridHeaderItem](#) 80
[ArrayOfGridViewTransformReference](#) 80
[ArrayOfHierarchy](#) 81
[ArrayOfIndicatorBand](#) 81
[ArrayOfKpi](#) 81
[ArrayOfKpiMeasure](#) 81
[ArrayOfLevel](#) 82
[ArrayOfMeasure](#) 82
[ArrayOfMember](#) 82
[ArrayOfMemberTransform](#) 83
[ArrayOfNamedSet](#) 83
[ArrayOfNameInfo](#) 83
[ArrayOfParameter](#) 84
[ArrayOfParameterDefinition](#) 84
[ArrayOfParameterMapping](#) 84
[ArrayOfPropertyBag](#) 85
[ArrayOfSetOperation](#) 85
[ArrayOfString](#) 85
[ArrayOfTarget](#) 85
[ArrayOfTimeIntelligenceDataSource](#) 86
[ArrayOfTimeIntelligenceFormula](#) 86
[ArrayOfTimeIntelligenceLevelBinding](#) 86
[Axis](#) 87
[Banding](#) 88
[BpmException](#) 88
[BpmProperty](#) 88
[BpmPropertyBool](#) 89
[BpmPropertyDate](#) 89
[BpmPropertyDecimal](#) 90
[BpmPropertyHyperlink](#) 90
[BpmPropertyHyperlink2](#) 90
[BpmPropertyLinkBase](#) 91
[BpmPropertyList](#) 91
[BpmPropertyListItem](#) 91
[BpmPropertyLongText](#) 92
[BpmPropertyText](#) 92
[BpmPropertyUser](#) 92
[CalculatedFormulaInfo](#) 93
[CalculatedMember](#) 93
[Comment](#) 94
[ConfiguredView](#) 94
[Cube](#) 96
[Dashboard](#) 97
[DashboardElement](#) 98
[DashboardElementContainer](#) 99
[DashboardElementSize](#) 99
[DashboardItem](#) 99
[DataColumnMapping](#) 100
[DataSource](#) 101
[DataTableMapping](#) 105
[DefaultDimensionSetting](#) 106
[DictionaryWrapperOfStringGridCell](#) 107
[DictionaryWrapperOfStringPropertyBag](#) 107
[Dimension](#) 108
[Element](#) 109
[ElementVersion](#) 109
[EliminateDescendantsSetOp](#) 109
[EliminateMemberSetOp](#) 110
[EndPoint](#) 110
[ExcelDataSet](#) 110
[ExcelServicesData](#) 111
[Filter](#) 112
[FirstClassElement](#) 113
[GridCell](#) 115
[GridCellSet](#) 122
[GridColor](#) 123
[GridDisplayElement](#) 124
[GridDisplayElementActual](#) 126
[GridDisplayElementAggregation](#) 126
[GridDisplayElementHyperLink](#) 126
[GridDisplayElementIndicator](#) 126
[GridDisplayElementIndicatorText](#) 127
[GridDisplayElementNumber](#) 127
[GridDisplayElementScore](#) 128
[GridDisplayElementTarget](#) 128
[GridDisplayElementText](#) 129
[GridDisplayElementVariance](#) 129
[GridFontInfo](#) 129
[GridFormatInfo](#) 130
[GridHeaderItem](#) 130
[GridIndicatorSettings](#) 134
[GridScoreSettings](#) 135
[GridTargetSettings](#) 135
[GridVarianceSettings](#) 136
[GridViewData](#) 137
[GridViewDefinition](#) 139
[GridViewTransformReference](#) 141
[Hierarchy](#) 141
[Indicator](#) 142
[IndicatorBand](#) 143
[Item](#) 144
[Kpi](#) 144
[KpiMeasure](#) 144
[KpiNumberFormatProperties](#) 146

[Level](#) 147
[MDXParameterDefinition](#) 147
[Measure](#) 148
[Member](#) 148
[MemberList](#) 149
[MemberOperation](#) 150
[MemberOperationAllDescendants](#) 150
[MemberOperationChildren](#) 150
[MemberOperationDescendants](#) 150
[MemberOperationDrillUp](#) 151
[MemberOperationHide](#) 151
[MemberOperationLeafDescendants](#) 151
[MemberParameterDefinition](#) 152
[MemberSet](#) 152
[MemberSetFormula](#) 152
[MemberTransform](#) 153
[NamedSet](#) 153
[NamedSetParameterDefinition](#) 154
[NameInfo](#) 154
[NumericFormat](#) 155
[NumericFormatsHashtable](#) 155
[OLAPQueryData](#) 156
[OLAPReportView](#) 156
[Parameter](#) 157
[ParameterDefinition](#) 158
[ParameterMapping](#) 159
[PasReportViewData](#) 160
[PropertyBag](#) 161
[QueryState](#) 161
[ReportView](#) 162
[RepositoryLocation](#) 165
[Scorecard](#) 166
[SecondClassElement](#) 167
[SerializableDictionary](#) 167
[SetOperation](#) 167
[SqlReportViewData](#) 169
[StatusFilter](#) 170
[StrategyMapViewData](#) 170
[StringCollection](#) 171
[Target](#) 171
[TimeIntelligenceDataSource](#) 172
[TimeIntelligenceDefinition](#) 172
[TimeIntelligenceFormula](#) 173
[TimeIntelligenceLevelBinding](#) 173
[TimeIntelligenceMdxSettings](#) 174
[TimeIntelligencePostFormulaDefinition](#) 174
[TimeIntelligenceSettings](#) 175
[Title](#) 175
[ToolBarOptions](#) 176
[Tuple](#) 177
[XmlFont](#) 177
[ConfiguredViewcomplex type](#) 94
[ConnectionContextsimple type](#) 186
[Create and use a datasource example](#) 465
[CreateDataSource example](#) 465
[CreateKPI example](#) 436
[Cubecomplex type](#) 96

D

[Dashboardcomplex type](#) 97
[DashboardElementcomplex type](#) 98

[DashboardElementContainercomplex type](#) 99
[DashboardElementSizecomplex type](#) 99
[DashboardItemcomplex type](#) 99
 Data model - abstract
 [server](#) 213
[DataColumnMappingcomplex type](#) 100
[DataSourcecomplex type](#) 101
[DataTableMappingcomplex type](#) 105
[DataValuePositionsimple type](#) 186
[DateAggregationTypesimple type](#) 187
[DefaultDimensionSettingcomplex type](#) 106
[DeleteScorecard scorecard](#) 464
[DictionaryWrapperOfStringGridCellcomplex type](#) 107
[DictionaryWrapperOfStringPropertyBagcomplex type](#) 107
[Dimensioncomplex type](#) 108
[DimensionTypeEnumsimple type](#) 188

E

[Elementcomplex type](#) 109
[ElementVersioncomplex type](#) 109
[EliminateDescendantsSetOpcomplex type](#) 109
[EliminateMemberSetOpcomplex type](#) 110
[EndPointCategorysimple type](#) 189
[EndPointcomplex type](#) 110
 Events
 [local - server](#) 435
 [timer - server](#) 435
 Examples
 [create and use a datasource](#) 465
 [CreateDataSource](#) 465
 [CreateKPI](#) 436
 [DeleteScorecard](#) 464
 [GenerateView](#) 459
 [GetDimensions](#) 468
 [GetScorecard](#) 440
 [overview](#) 436
 [QueryChildMembersFromDataSource](#) 471
 [QueryDimensionRootMembersFromDataSource](#) 471
 [scorecard update](#) 436
 [TestDataSource](#) 467
 [UpdateScorecard](#) 446
[ExcelDataSetcomplex type](#) 110
[ExcelServicesDatacomplex type](#) 111
[ExcelServicesToolBarOptionssimple type](#) 189
[ExcelServicesToolBarTypesimple type](#) 190
[ExcelServicesViewOptionssimple type](#) 190

F

[FactAggregationssimple type](#) 191
[Faults](#) 37
 [common list of error codes](#) 41
 [full list of possible error codes](#) 37
 [SOAP fault detail element](#) 37
[Fields - vendor-extensible](#) 35
[Filtercomplex type](#) 112
[FilterSelectionModesimple type](#) 192
[FirstClassElementcomplex type](#) 113

[FirstClassObjectTypesimple type](#) 193
[FontStylesimple type](#) 193
[FormatNegativeSymbolsimple type](#) 194
[FormatTypesimple type](#) 194
[Full list of possible error codes](#) 37
[Full WSDL](#) 474
[Full XML Schema](#) 581
<http://performancepoint.microsoft.com/OLAPQueryData Schema> 581
<http://schemas.microsoft.com/performancepoint/2007/03/query Schema> 581
<http://www.microsoft.com/performancepoint/scorecards/Analytics Schema> 581

G

[GenerateView example](#) 459
[GetDimensions example](#) 468
[GetScorecard example](#) 440
[Glossary](#) 29
[GraphicsUnitsimple type](#) 195
[GridCellcomplex type](#) 115
[GridCellElementStatussimple type](#) 196
[GridCellSetcomplex type](#) 122
[GridColorcomplex type](#) 123
[GridDisplayElementActualcomplex type](#) 126
[GridDisplayElementAggregationcomplex type](#) 126
[GridDisplayElementcomplex type](#) 124
[GridDisplayElementHyperLinkcomplex type](#) 126
[GridDisplayElementIndicatorcomplex type](#) 126
[GridDisplayElementIndicatorTextcomplex type](#) 127
[GridDisplayElementNumbercomplex type](#) 127
[GridDisplayElementScorecomplex type](#) 128
[GridDisplayElementTargetcomplex type](#) 128
[GridDisplayElementTextcomplex type](#) 129
[GridDisplayElementVariancecomplex type](#) 129
[GridFontInfocomplex type](#) 129
[GridFormatInfocomplex type](#) 130
[GridHeaderItemcomplex type](#) 130
[GridIndicatorSettingscomplex type](#) 134
[GridScoreSettingscomplex type](#) 135
[GridTargetSettingscomplex type](#) 135
[GridVarianceSettingscomplex type](#) 136
[GridViewDatacomplex type](#) 137
[GridViewDefinitioncomplex type](#) 139
[GridViewTransformReferencecomplex type](#) 141
[Groups](#) 212

H

[HeaderAggregationTypesimple type](#) 196
[Hierarchycomplex type](#) 141
[HierarchyOriginsimple type](#) 197
[HierarchyTypesimple type](#) 197
[HorizontalAlignmentssimple type](#) 198

I

[Implementer - security considerations](#) 473
[Index of security parameters](#) 473
[IndicatorBandcomplex type](#) 143
[Indicatorcomplex type](#) 142

[IndicatorPositionsimple type](#) 198
[IndicatorTypesimple type](#) 199
[Informative references](#) 33
Initialization
[server](#) 216
[Introduction](#) 29
[Itemcomplex type](#) 144

K

[Kpicomplex type](#) 144
[KpiMeasurecomplex type](#) 144
[KpiNumberFormatPropertiescomplex type](#) 146
[KpiPatternsimple type](#) 199

L

[LayoutOrientationsimple type](#) 200
[Levelcomplex type](#) 147
Local events
[server](#) 435

M

[MappedColumnDataTypesimple type](#) 200
[MappedColumnTypesimple type](#) 201
[MDXParameterDefinitioncomplex type](#) 147
[Measurecomplex type](#) 148
[Membercomplex type](#) 148
[MemberListcomplex type](#) 149
[MemberOperationAllDescendantscomplex type](#) 150
[MemberOperationChildrencomplex type](#) 150
[MemberOperationcomplex type](#) 150
[MemberOperationDescendantscomplex type](#) 150
[MemberOperationDrillUpcomplex type](#) 151
[MemberOperationHidecomplex type](#) 151
[MemberOperationLeafDescendantscomplex type](#) 151
[MemberParameterDefinitioncomplex type](#) 152
[MemberRelationshipsimple type](#) 201
[MemberSetcomplex type](#) 152
[MemberSetFormulacomplex type](#) 152
[MemberTransformcomplex type](#) 153
[MemberTransformOperationsimple type](#) 202
[MemberTransformTypesimple type](#) 203
[MemberTypesimple type](#) 203
Message processing
[server](#) 216
[Messages](#) 36
[AddAllMembersSetOpcomplex type](#) 57
[AddCalcMemberSetOpcomplex type](#) 57
[AddChildrenSetOpcomplex type](#) 57
[AddDefaultMemberSetOpcomplex type](#) 58
[AddDescendantsLeavesSetOpcomplex type](#) 58
[AddDescendantsSetOpcomplex type](#) 58
[AddDescendantsSubtreeSetOpcomplex type](#) 58
[AddFilterSetOpcomplex type](#) 59
[AddFilterTopBottomSetOpcomplex type](#) 59
[AddMemberSetOpcomplex type](#) 59
[AddNamedSetSetOpcomplex type](#) 60
[AddParentSiblingsSetOpcomplex type](#) 60
[AggregateTypeEnumssimple type](#) 181

[AliasInfocomplex type](#) 60
[AlignmentTypesimple type](#) 181
[AnalyticBaseReportViewDatacomplex type](#) 60
[AnalyticChartLegendcomplex type](#) 68
[AnalyticChartReportViewcomplex type](#) 69
[AnalyticChartTypesimple type](#) 182
[AnalyticGridReportViewcomplex type](#) 70
[AnalyticLegendLocationsimple type](#) 182
[AnalyticMarkerStylesimple type](#) 183
[AnnotationCommentcomplex type](#) 74
[Annotationcomplex type](#) 71
[AnnotationVersionssimple type](#) 184
[ArrayOfAliasInfocomplex type](#) 74
[ArrayOfAnnotationCommentcomplex type](#) 75
[ArrayOfAxiscomplex type](#) 75
[ArrayOfBpmPropertycomplex type](#) 75
[ArrayOfBpmPropertyListItemcomplex type](#) 75
[ArrayOfChoice1complex type](#) 76
[ArrayOfCommentcomplex type](#) 77
[ArrayOfConfiguredViewcomplex type](#) 77
[ArrayOfDashboardElementcomplex type](#) 77
[ArrayOfDataColumnMappingcomplex type](#) 78
[ArrayOfDecimalcomplex type](#) 78
[ArrayOfDefaultDimensionSettingcomplex type](#) 78
[ArrayOfDimensioncomplex type](#) 78
[ArrayOfEndPointcomplex type](#) 79
[ArrayOfFirstClassElementcomplex type](#) 79
[ArrayOfGridCellcomplex type](#) 79
[ArrayOfGridDisplayElementcomplex type](#) 80
[ArrayOfGridHeaderItemcomplex type](#) 80
[ArrayOfGridViewTransformReferencecomplex type](#) 80
[ArrayOfHierarchycomplex type](#) 81
[ArrayOfIndicatorBandcomplex type](#) 81
[ArrayOfKpicomplex type](#) 81
[ArrayOfKpiMeasurecomplex type](#) 81
[ArrayOfLevelcomplex type](#) 82
[ArrayOfMeasurecomplex type](#) 82
[ArrayOfMembercomplex type](#) 82
[ArrayOfMemberTransformcomplex type](#) 83
[ArrayOfNamedSetcomplex type](#) 83
[ArrayOfNameInfocomplex type](#) 83
[ArrayOfParametercomplex type](#) 84
[ArrayOfParameterDefinitioncomplex type](#) 84
[ArrayOfParameterMappingcomplex type](#) 84
[ArrayOfPropertyBagcomplex type](#) 85
[ArrayOfSetOperationcomplex type](#) 85
[ArrayOfStringcomplex type](#) 85
[ArrayOfTargetcomplex type](#) 85
[ArrayOfTimeIntelligenceDataSourcecomplex type](#) 86
[ArrayOfTimeIntelligenceFormulacomplex type](#) 86
[ArrayOfTimeIntelligenceLevelBindingcomplex type](#) 86
[attribute groups](#) 212
[attributes](#) 212
[Axiscomplex type](#) 87
[AxisTypesimple type](#) 184
[Bandingcomplex type](#) 88
[BandTypesimple type](#) 185
[BeginPointEmitterTypesimple type](#) 185
[BpmExceptioncomplex type](#) 88
[BpmPropertyBoolcomplex type](#) 89
[BpmPropertycomplex type](#) 88
[BpmPropertyDatecomplex type](#) 89
[BpmPropertyDecimalcomplex type](#) 90
[BpmPropertyHyperlink2complex type](#) 90
[BpmPropertyHyperlinkcomplex type](#) 90
[BpmPropertyLinkBasecomplex type](#) 91
[BpmPropertyListcomplex type](#) 91
[BpmPropertyListItemcomplex type](#) 91
[BpmPropertyLongTextcomplex type](#) 92
[BpmPropertyTextcomplex type](#) 92
[BpmPropertyUsercomplex type](#) 92
[CalculatedFormulaInfocomplex type](#) 93
[CalculatedMembercomplex type](#) 93
[Commentcomplex type](#) 94
[common data structures \(\[section 2.2.9\]\(#\) 212, \[section 2.2.9\]\(#\) 212\)](#)
[complex types](#) 43
[ConfiguredViewcomplex type](#) 94
[ConnectionContextssimple type](#) 186
[Cubecomplex type](#) 96
[Dashboardcomplex type](#) 97
[DashboardElementcomplex type](#) 98
[DashboardElementContainercomplex type](#) 99
[DashboardElementSizecomplex type](#) 99
[DashboardItemcomplex type](#) 99
[DataColumnMappingcomplex type](#) 100
[DataSourcecomplex type](#) 101
[DataTableMappingcomplex type](#) 105
[DataValuePositionssimple type](#) 186
[DateAggregationTypessimple type](#) 187
[DefaultDimensionSettingcomplex type](#) 106
[DictionaryWrapperOfStringGridCellcomplex type](#) 107
[DictionaryWrapperOfStringPropertyBagcomplex type](#) 107
[Dimensioncomplex type](#) 108
[DimensionTypeEnumssimple type](#) 188
[Elementcomplex type](#) 109
[elements](#) 43
[ElementVersioncomplex type](#) 109
[EliminateDescendantsSetOpcomplex type](#) 109
[EliminateMemberSetOpcomplex type](#) 110
[EndPointCategoryssimple type](#) 189
[EndPointcomplex type](#) 110
[enumerated](#) 37
[ExcelDataSetcomplex type](#) 110
[ExcelServicesDatacomplex type](#) 111
[ExcelServicesToolbarOptionssimple type](#) 189
[ExcelServicesToolbarTypesimple type](#) 190
[ExcelServicesViewOptionssimple type](#) 190
[FactAggregationssimple type](#) 191
[Faults](#) 37
[Faultsmessagge](#) 37
[Filtercomplex type](#) 112
[FilterSelectionModeSimple type](#) 192
[FirstClassElementcomplex type](#) 113
[FirstClassObjectTypesimple type](#) 193
[FontStylesimple type](#) 193
[FormatNegativeSymbolsimple type](#) 194

[FormatTypesimple type](#) 194
[GraphicsUnitsimple type](#) 195
[GridCellcomplex type](#) 115
[GridCellElementStatussimple type](#) 196
[GridCellSetcomplex type](#) 122
[GridColorcomplex type](#) 123
[GridDisplayElementActualcomplex type](#) 126
[GridDisplayElementAggregationcomplex type](#) 126
[GridDisplayElementcomplex type](#) 124
[GridDisplayElementHyperLinkcomplex type](#) 126
[GridDisplayElementIndicatorcomplex type](#) 126
[GridDisplayElementIndicatorTextcomplex type](#) 127
[GridDisplayElementNumbercomplex type](#) 127
[GridDisplayElementScorecomplex type](#) 128
[GridDisplayElementTargetcomplex type](#) 128
[GridDisplayElementTextcomplex type](#) 129
[GridDisplayElementVariancecomplex type](#) 129
[GridFontInfocomplex type](#) 129
[GridFormatInfocomplex type](#) 130
[GridHeaderItemcomplex type](#) 130
[GridIndicatorSettingscomplex type](#) 134
[GridScoreSettingscomplex type](#) 135
[GridTargetSettingscomplex type](#) 135
[GridVarianceSettingscomplex type](#) 136
[GridViewDatacomplex type](#) 137
[GridViewDefinitioncomplex type](#) 139
[GridViewTransformReferencecomplex type](#) 141
[groups](#) 212
[HeaderAggregationTypessimple type](#) 196
[Hierarchycomplex type](#) 141
[HierarchyOriginsimple type](#) 197
[HierarchyTypesimple type](#) 197
[HorizontalAlignmentssimple type](#) 198
[IndicatorBandcomplex type](#) 143
[Indicatorcomplex type](#) 142
[IndicatorPositionssimple type](#) 198
[IndicatorTypesimple type](#) 199
[Itemcomplex type](#) 144
[Kpicomplex type](#) 144
[KpiMeasurecomplex type](#) 144
[KpiNumberFormatPropertiescomplex type](#) 146
[KpiPatternssimple type](#) 199
[LayoutOrientationssimple type](#) 200
[Levelcomplex type](#) 147
[MappedColumnDataTypessimple type](#) 200
[MappedColumnTypessimple type](#) 201
[MDXParameterDefinitioncomplex type](#) 147
[Measurecomplex type](#) 148
[Membercomplex type](#) 148
[MemberListcomplex type](#) 149
[MemberOperationAllDescendantscomplex type](#) 150
[MemberOperationChildrencomplex type](#) 150
[MemberOperationcomplex type](#) 150
[MemberOperationDescendantscomplex type](#) 150
[MemberOperationDrillUpcomplex type](#) 151
[MemberOperationHidecomplex type](#) 151
[MemberOperationLeafDescendantscomplex type](#) 151
[MemberParameterDefinitioncomplex type](#) 152
[MemberRelationshipssimple type](#) 201
[MemberSetcomplex type](#) 152
[MemberSetFormulacomplex type](#) 152
[MemberTransformcomplex type](#) 153
[MemberTransformOperationsimple type](#) 202
[MemberTransformTypesimple type](#) 203
[MemberTypesimple type](#) 203
[NamedSetcomplex type](#) 153
[NamedSetParameterDefinitioncomplex type](#) 154
[NameInfocomplex type](#) 154
[namespaces](#) 36
[NumericFormatcomplex type](#) 155
[NumericFormatsHashtablecomplex type](#) 155
[OLAPQueryDatacomplex type](#) 156
[OLAPReportViewcomplex type](#) 156
[Parametercomplex type](#) 157
[ParameterDefinitioncomplex type](#) 158
[ParameterMappingcomplex type](#) 159
[PasReportViewDatacomplex type](#) 160
[PropertyBagcomplex type](#) 161
[QueryStatecomplex type](#) 161
[ReportLayoutssimple type](#) 204
[ReportViewcomplex type](#) 162
[RepositoryLocationcomplex type](#) 165
[RollupTypessimple type](#) 204
[Scorecardcomplex type](#) 166
[ScorecardEmptyRowsFilterModesimple type](#) 205
[ScorecardNamedSetTypesimple type](#) 205
[ScorecardNodeTypessimple type](#) 206
[ScoreTypessimple type](#) 207
[SecondClassElementcomplex type](#) 167
[SerializableDictionarycomplex type](#) 167
[SetOperationcomplex type](#) 167
[simple types](#) 178
[SizeTypesimple type](#) 207
[SortTypesimple type](#) 208
[SqlReportViewDatacomplex type](#) 169
[SqlReportViewDataServerModesimple type](#) 208
[StatusFiltercomplex type](#) 170
[StrategyMapToolbarOptionssimple type](#) 209
[StrategyMapViewDatacomplex type](#) 170
[StringCollectioncomplex type](#) 171
[syntax](#) 36
[Targetcomplex type](#) 171
[TimeIntelligenceDataSourcecomplex type](#) 172
[TimeIntelligenceDefinitioncomplex type](#) 172
[TimeIntelligenceFormulacomplex type](#) 173
[TimeIntelligenceLevelBindingcomplex type](#) 173
[TimeIntelligenceMdxSettingscomplex type](#) 174
[TimeIntelligencePostFormulaDefinitioncomplex type](#) 174
[TimeIntelligenceSettingscomplex type](#) 175
[Titlecomplex type](#) 175
[ToolbarOptionscomplex type](#) 176
[transport](#) 36
[Trinarysimple type](#) 209
[Tuplecomplex type](#) 177
[ValueSourcessimple type](#) 210
[VarianceDisplayTypesimple type](#) 210
[VarianceTypesimple type](#) 211
[VerticalAlignmentssimple type](#) 211

[XmlFontcomplex type](#) 177

N

[NamedSetcomplex type](#) 153
[NamedSetParameterDefinitioncomplex type](#) 154
[NameInfocomplex type](#) 154
[Namespaces](#) 36
[Normative references](#) 31
[NumericFormatcomplex type](#) 155
[NumericFormatsHashtablecomplex type](#) 155

O

[OLAPQueryDatacomplex type](#) 156
[OLAPReportViewcomplex type](#) 156
Operations
[CreateAnnotation](#) 222
[CreateDashboard](#) 225
[CreateDataSource](#) 228
[CreateFilter](#) 231
[CreateIndicator](#) 233
[CreateKpi](#) 236
[CreateReportView](#) 239
[CreateScorecard](#) 242
[DeleteAnnotation](#) 245
[DeleteDashboard](#) 247
[DeleteDataSource](#) 250
[DeleteFilter](#) 252
[DeleteIndicator](#) 254
[DeleteKpi](#) 256
[DeleteReportView](#) 258
[DeleteScorecard](#) 260
[ExportDashboard](#) 262
[GenerateView](#) 265
[GenerateViewDirect](#) 267
[GetAllAnnotationsByScorecardLocation](#) 271
[GetAnalyticReportView](#) 274
[GetAnnotation](#) 277
[GetAnnotationByID](#) 280
[GetAnnotationSetting](#) 282
[GetAsKpis](#) 285
[GetCube](#) 287
[GetCubeFromDataSource](#) 289
[GetCubeMetaData](#) 292
[GetCubeMetaDataForDataSource](#) 294
[GetCubeNameInfos](#) 297
[GetCurrentCultureLcid](#) 299
[GetCurrentUserInfo](#) 301
[GetDashboard](#) 303
[GetDatabaseNamesFromDataSource](#) 306
[GetDataSource](#) 308
[GetDependentElements](#) 310
[GetDimensions](#) 316
[GetDimensionsFromDataSource](#) 318
[GetFilter](#) 321
[GetIndicator](#) 323
[GetKpi](#) 326
[GetKpisFromScorecard](#) 328
[GetLatestAnalyticReportVersion](#) 330
[GetListItems](#) 333
[GetMdx](#) 335

[GetParameterDisplayData](#) 338
[GetPreviewDataSet](#) 341
[GetQueryResultMembers](#) 344
[GetRegisteredCustomFCOs](#) 346
[GetReportView](#) 351
[GetScorecard](#) 353
[ImportDashboard](#) 355
[QueryChildMembers](#) 358
[QueryChildMembersByRangeFromDataSource](#) 361
[QueryChildMembersFromDataSource](#) 364
[QueryDimensionRootMembers](#) 366
[QueryDimensionRootMembersFromDataSource](#) 369
[QueryNamedSets](#) 372
[QueryNamedSetsFromDataSource](#) 374
[QueryRelatedMember](#) 377
[QueryRelatedMemberFromDataSource](#) 379
[QueryTimeIntelligence](#) 382
[QueryTimeIntelligenceDirect](#) 385
[QueryTransformMembers](#) 388
[SaveTemporaryAnalyticReport](#) 391
[TestConnection](#) 394
[TrimAnnotationByOwner](#) 396
[TrimAnnotationByScorecardLocation](#) 398
[TrimAnnotationUntouchedSince](#) 401
[UpdateAnnotation](#) 403
[UpdateDashboard](#) 406
[UpdateDataSource](#) 409
[UpdateFilter](#) 412
[UpdateIndicator](#) 415
[UpdateKpi](#) 418
[UpdateReportView](#) 421
[UpdateScorecard](#) 424
[ValidateKpi](#) 426
[ValidateScorecard](#) 429
[ValidateSiteCollection](#) 431
[Overview \(synopsis\)](#) 33

P

[Parametercomplex type](#) 157
[ParameterDefinitioncomplex type](#) 158
[ParameterMappingcomplex type](#) 159
[Parameters - security index](#) 473
[PasReportViewDatacomplex type](#) 160
[Preconditions](#) 34
[Prerequisites](#) 34
[Product behavior](#) 583
[PropertyBagcomplex type](#) 161
Protocol Details
[overview](#) 213

Q

[QueryChildMembersFromDataSource example](#) 471
[QueryDimensionRootMembersFromDataSource example](#) 471
[QueryStatecomplex type](#) 161

R

[References](#) 31

[informative](#) 33
[normative](#) 31
[Relationship to other protocols](#) 33
[ReportLayoutsimple type](#) 204
[ReportViewcomplex type](#) 162
[RepositoryLocationcomplex type](#) 165
[RollupTypessimple type](#) 204

S

[Scorecard update example](#) 436
[Scorecardcomplex type](#) 166
[ScorecardEmptyRowsFilterModesimple type](#) 205
[ScorecardNamedSetTypesimple type](#) 205
[ScorecardNodeTypessimple type](#) 206
[ScoreTypessimple type](#) 207
[SecondClassElementcomplex type](#) 167
Security
 [implementer considerations](#) 473
 [parameter index](#) 473
Sequencing rules
 [server](#) 216
[SerializableDictionarycomplex type](#) 167
Server
 [abstract data model](#) 213
 [CreateAnnotation operation](#) 222
 [CreateDashboard operation](#) 225
 [CreateDataSource operation](#) 228
 [CreateFilter operation](#) 231
 [CreateIndicator operation](#) 233
 [CreateKpi operation](#) 236
 [CreateReportView operation](#) 239
 [CreateScorecard operation](#) 242
 [DeleteAnnotation operation](#) 245
 [DeleteDashboard operation](#) 247
 [DeleteDataSource operation](#) 250
 [DeleteFilter operation](#) 252
 [DeleteIndicator operation](#) 254
 [DeleteKpi operation](#) 256
 [DeleteReportView operation](#) 258
 [DeleteScorecard operation](#) 260
 [details](#) 213
 [ExportDashboard operation](#) 262
 [GenerateView operation](#) 265
 [GenerateViewDirect operation](#) 267
 [GetAllAnnotationsByScorecardLocation operation](#) 271
 [GetAnalyticReportView operation](#) 274
 [GetAnnotation operation](#) 277
 [GetAnnotationByID operation](#) 280
 [GetAnnotationSetting operation](#) 282
 [GetAsKpis operation](#) 285
 [GetCube operation](#) 287
 [GetCubeFromDataSource operation](#) 289
 [GetCubeMetaData operation](#) 292
 [GetCubeMetaDataForDataSource operation](#) 294
 [GetCubeNameInfos operation](#) 297
 [GetCurrentCultureLcid operation](#) 299
 [GetCurrentUserInfo operation](#) 301
 [GetDashboard operation](#) 303
 [GetDatabaseNamesFromDataSource operation](#) 306

[GetDataSource operation](#) 308
[GetDependentElements operation](#) 310
[GetDimensions operation](#) 316
[GetDimensionsFromDataSource operation](#) 318
[GetFilter operation](#) 321
[GetIndicator operation](#) 323
[GetKpi operation](#) 326
[GetKpisFromScorecard operation](#) 328
[GetLatestAnalyticReportVersion operation](#) 330
[GetListItems operation](#) 333
[GetMdx operation](#) 335
[GetParameterDisplayData operation](#) 338
[GetPreviewDataSet operation](#) 341
[GetQueryResultMembers operation](#) 344
[GetRegisteredCustomFCOs operation](#) 346
[GetReportView operation](#) 351
[GetScorecard operation](#) 353
[ImportDashboard operation](#) 355
[initialization](#) 216
[local events](#) 435
[message processing](#) 216
[overview](#) 213
[QueryChildMembers operation](#) 358
[QueryChildMembersByRangeFromDataSource operation](#) 361
[QueryChildMembersFromDataSource operation](#) 364
[QueryDimensionRootMembers operation](#) 366
[QueryDimensionRootMembersFromDataSource operation](#) 369
[QueryNamedSets operation](#) 372
[QueryNamedSetsFromDataSource operation](#) 374
[QueryRelatedMember operation](#) 377
[QueryRelatedMemberFromDataSource operation](#) 379
[QueryTimeIntelligence operation](#) 382
[QueryTimeIntelligenceDirect operation](#) 385
[QueryTransformMembers operation](#) 388
[SaveTemporaryAnalyticReport operation](#) 391
[sequencing rules](#) 216
[TestConnection operation](#) 394
[timer events](#) 435
[timers](#) 216
[TrimAnnotationByOwner operation](#) 396
[TrimAnnotationByScorecardLocation operation](#) 398
[TrimAnnotationUntouchedSince operation](#) 401
[UpdateAnnotation operation](#) 403
[UpdateDashboard operation](#) 406
[UpdateDataSource operation](#) 409
[UpdateFilter operation](#) 412
[UpdateIndicator operation](#) 415
[UpdateKpi operation](#) 418
[UpdateReportView operation](#) 421
[UpdateScorecard operation](#) 424
[ValidateKpi operation](#) 426
[ValidateScorecard operation](#) 429
[ValidateSiteCollection operation](#) 431
[SetOperationcomplex type](#) 167
[Simple types](#) 178
[AggregateTypeEnum](#) 181

[AlignmentType](#) 181
[AnalyticChartType](#) 182
[AnalyticLegendLocation](#) 182
[AnalyticMarkerStyle](#) 183
[AnnotationVersions](#) 184
[AxisType](#) 184
[BandType](#) 185
[BeginPointEmitterType](#) 185
[ConnectionContext](#) 186
[DataValuePosition](#) 186
[DateAggregationTypes](#) 187
[DimensionTypeEnum](#) 188
[EndPointCategory](#) 189
[ExcelServicesToolbarOptions](#) 189
[ExcelServicesToolbarType](#) 190
[ExcelServicesViewOptions](#) 190
[FactAggregations](#) 191
[FilterSelectionMode](#) 192
[FirstClassObjectType](#) 193
[FontStyle](#) 193
[FormatNegativeSymbol](#) 194
[FormatType](#) 194
[GraphicsUnit](#) 195
[GridCellElementStatus](#) 196
[HeaderAggregationTypes](#) 196
[HierarchyOrigin](#) 197
[HierarchyType](#) 197
[HorizontalAlignments](#) 198
[IndicatorPosition](#) 198
[IndicatorType](#) 199
[KpiPattern](#) 199
[LayoutOrientation](#) 200
[MappedColumnDataTypes](#) 200
[MappedColumnTypes](#) 201
[MemberRelationship](#) 201
[MemberTransformOperation](#) 202
[MemberTransformType](#) 203
[MemberType](#) 203
[ReportLayout](#) 204
[RollupTypes](#) 204
[ScorecardEmptyRowsFilterMode](#) 205
[ScorecardNamedSetType](#) 205
[ScorecardNodeTypes](#) 206
[ScoreTypes](#) 207
[SizeType](#) 207
[SortType](#) 208
[SqlReportViewDataServerMode](#) 208
[StrategyMapToolbarOptions](#) 209
[Trinary](#) 209
[ValueSources](#) 210
[VarianceDisplayType](#) 210
[VarianceType](#) 211
[VerticalAlignments](#) 211
[SizeTypesimple type](#) 207
[SOAP fault detail element](#) 37
[SortTypesimple type](#) 208
[SqlReportViewDatacomplex type](#) 169
[SqlReportViewDataServerModesimple type](#) 208
[Standards assignments](#) 35
[StatusFiltercomplex type](#) 170
[StrategyMapToolbarOptionssimple type](#) 209

[StrategyMapViewDatacomplex type](#) 170
[StringCollectioncomplex type](#) 171
 Syntax
 [messages - overview](#) 36

T

[Targetcomplex type](#) 171
[TestDataSource example](#) 467
[TimeIntelligenceDataSourcecomplex type](#) 172
[TimeIntelligenceDefinitioncomplex type](#) 172
[TimeIntelligenceFormulacomplex type](#) 173
[TimeIntelligenceLevelBindingcomplex type](#) 173
[TimeIntelligenceMdxSettingscomplex type](#) 174
[TimeIntelligencePostFormulaDefinitioncomplex type](#) 174
[TimeIntelligenceSettingscomplex type](#) 175
 Timer events
 [server](#) 435
 Timers
 [server](#) 216
[Titlecomplex type](#) 175
[ToolbarOptionscomplex type](#) 176
[Tracking changes](#) 586
[Transport](#) 36
[Trinarysimple type](#) 209
[Tuplecomplex type](#) 177
 Types
 [complex](#) 43
 [simple](#) 178

U

[UpdateScorecard example](#) 446

V

[ValueSourcesimple type](#) 210
[VarianceDisplayTypesimple type](#) 210
[VarianceTypesimple type](#) 211
[Vendor-extensible fields](#) 35
[Versioning](#) 35
[VerticalAlignmentsimple type](#) 211

W

[WSDL](#) 474

X

[XML Schema](#) 581
 <http://performancepoint.microsoft.com/OLAPQueryData Schema> 581
 <http://schemas.microsoft.com/performancepoint/2007/03/query Schema> 581
 <http://www.microsoft.com/performancepoint/scorecards/Analytics Schema> 581
[XmlFontcomplex type](#) 177