

# [MS-SOCCSOM]: SharePoint Social Client-Side Object Model Protocol Specification

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

**Preliminary Documentation.** This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

## Revision Summary

Date	Revision History	Revision Class	Comments
07/16/2012	0.1	New	Released new document.

# Table of Contents

<b>1 Introduction</b>	<b>16</b>
1.1 Glossary	16
1.2 References	16
1.2.1 Normative References	17
1.2.2 Informative References	17
1.3 Overview	17
1.4 Relationship to Other Protocols	17
1.5 Prerequisites/Preconditions	18
1.6 Applicability Statement	18
1.7 Versioning and Capability Negotiation	18
1.8 Vendor-Extensible Fields	18
1.9 Standards Assignments	18
<b>2 Messages</b>	<b>19</b>
2.1 Transport	19
2.2 Message Syntax	19
2.2.1 Namespaces	19
<b>3 Protocol Details</b>	<b>20</b>
3.1 Server Details	20
3.1.1 Abstract Data Model	20
3.1.2 Timers	20
3.1.3 Initialization	20
3.1.4 Higher-Layer Triggered Events	20
3.1.5 Message Processing Events and Sequencing Rules	20
3.1.5.1 Microsoft.SharePoint.Client.Social.SocialActor	20
3.1.5.1.1 Properties	20
3.1.5.1.1.1 Scalar Properties	20
3.1.5.1.1.1.1 AccountName	20
3.1.5.1.1.1.2 ActorType	21
3.1.5.1.1.1.3 EmailAddress	21
3.1.5.1.1.1.4 FollowedContentUri	21
3.1.5.1.1.1.5 Id	21
3.1.5.1.1.1.6 ImageUri	21
3.1.5.1.1.1.7 LibraryUri	21
3.1.5.1.1.1.8 Name	22
3.1.5.1.1.1.9 TagGuid	22
3.1.5.1.1.1.10 Title	22
3.1.5.1.1.1.11 Uri	22
3.1.5.1.1.1.12 ContentUri	22
3.1.5.1.1.1.13 IsFollowed	22
3.1.5.1.1.1.14 PersonalSiteUri	23
3.1.5.1.1.1.15 StatusText	23
3.1.5.1.1.2 ObjectPath Properties	23
3.1.5.2 Microsoft.SharePoint.Client.Social.SocialActorInfo	23
3.1.5.2.1 Properties	23
3.1.5.2.1.1 Scalar Properties	23
3.1.5.2.1.1.1 AccountName	23
3.1.5.2.1.1.2 ActorType	23
3.1.5.2.1.1.3 ContentUri	23

3.1.5.2.1.1.4	Id .....	24
3.1.5.2.1.1.5	TagGuid .....	24
3.1.5.2.1.2	ObjectPath Properties.....	24
3.1.5.3	Microsoft.SharePoint.Client.Social.SocialActorType.....	24
3.1.5.3.1	Field Values .....	24
3.1.5.3.1.1	User.....	24
3.1.5.3.1.2	Document.....	24
3.1.5.3.1.3	Site .....	24
3.1.5.3.1.4	Tag.....	25
3.1.5.4	Microsoft.SharePoint.Client.Social.SocialActorTypes .....	25
3.1.5.4.1	Field Values .....	25
3.1.5.4.1.1	None.....	25
3.1.5.4.1.2	Users .....	25
3.1.5.4.1.3	Documents .....	25
3.1.5.4.1.4	Sites .....	25
3.1.5.4.1.5	Tags .....	25
3.1.5.4.1.6	All .....	25
3.1.5.4.1.7	ExcludeContentWithoutFeeds .....	25
3.1.5.5	Microsoft.SharePoint.Client.Social.SocialAttachment.....	26
3.1.5.5.1	Properties .....	26
3.1.5.5.1.1	Scalar Properties .....	26
3.1.5.5.1.1.1	Description.....	26
3.1.5.5.1.1.2	Name .....	26
3.1.5.5.1.1.3	Uri .....	26
3.1.5.5.1.2	ObjectPath Properties.....	26
3.1.5.6	Microsoft.SharePoint.Client.Social.SocialDataItem .....	26
3.1.5.6.1	Properties .....	27
3.1.5.6.1.1	Scalar Properties .....	27
3.1.5.6.1.1.1	AccountName .....	27
3.1.5.6.1.1.2	ItemType .....	27
3.1.5.6.1.1.3	TagGuid .....	27
3.1.5.6.1.1.4	Text .....	27
3.1.5.6.1.1.5	Uri .....	27
3.1.5.6.1.2	ObjectPath Properties.....	27
3.1.5.7	Microsoft.SharePoint.Client.Social.SocialDataItemType.....	28
3.1.5.7.1	Field Values.....	28
3.1.5.7.1.1	User.....	28
3.1.5.7.1.2	Document.....	28
3.1.5.7.1.3	Site .....	28
3.1.5.7.1.4	Tag.....	28
3.1.5.7.1.5	Link .....	28
3.1.5.8	Microsoft.SharePoint.Client.Social.SocialDataOverlay .....	28
3.1.5.8.1	Properties .....	29
3.1.5.8.1.1	Scalar Properties .....	29
3.1.5.8.1.1.1	ActorIndexes .....	29
3.1.5.8.1.1.2	Index .....	29
3.1.5.8.1.1.3	Length .....	29
3.1.5.8.1.1.4	LinkUri.....	29
3.1.5.8.1.1.5	OverlayType .....	29
3.1.5.8.1.2	ObjectPath Properties.....	29
3.1.5.9	Microsoft.SharePoint.Client.Social.SocialDataOverlayType.....	30
3.1.5.9.1	Field Values .....	30
3.1.5.9.1.1	Link .....	30

3.1.5.9.1.2	Actors .....	30
3.1.5.10	Microsoft.SharePoint.Client.Social.SocialFeed .....	30
3.1.5.10.1	Properties.....	30
3.1.5.10.1.1	Scalar Properties .....	30
3.1.5.10.1.1.1	Attributes.....	30
3.1.5.10.1.1.2	FailedActorIds.....	30
3.1.5.10.1.1.3	NewestProcessed .....	31
3.1.5.10.1.1.4	OldestProcessed.....	31
3.1.5.10.1.1.5	Status.....	31
3.1.5.10.1.1.6	Threads .....	31
3.1.5.10.1.1.7	UnreadMentionCount .....	31
3.1.5.10.1.2	ObjectPath Properties.....	32
3.1.5.11	Microsoft.SharePoint.Client.Social.SocialFeedAttributes.....	32
3.1.5.11.1	Field Values .....	32
3.1.5.11.1.1	None.....	32
3.1.5.11.1.2	MoreThreadsAvailable .....	32
3.1.5.12	Microsoft.SharePoint.Client.Social.SocialFeedManager .....	32
3.1.5.12.1	Properties.....	32
3.1.5.12.1.1	Scalar Properties .....	32
3.1.5.12.1.1.1	Owner.....	32
3.1.5.12.1.2	ObjectPath Properties.....	32
3.1.5.12.2	Methods.....	33
3.1.5.12.2.1	Scalar Methods.....	33
3.1.5.12.2.1.1	CreatePost.....	33
3.1.5.12.2.1.2	DeletePost.....	33
3.1.5.12.2.1.3	GetAllLikers .....	33
3.1.5.12.2.1.4	GetFeed .....	34
3.1.5.12.2.1.5	GetFeedFor.....	34
3.1.5.12.2.1.6	GetFullThread .....	35
3.1.5.12.2.1.7	GetMentions .....	35
3.1.5.12.2.1.8	GetUnreadMentionCount .....	35
3.1.5.12.2.1.9	LikePost.....	35
3.1.5.12.2.1.10	LockThread .....	36
3.1.5.12.2.1.11	UnlikePost .....	36
3.1.5.12.2.1.12	UnlockThread.....	36
3.1.5.12.2.1.13	SuppressThreadNotifications .....	36
3.1.5.12.2.1.14	CreateImageAttachment.....	37
3.1.5.12.2.2	ObjectPath Methods .....	37
3.1.5.12.2.2.1	CSOM Constructor .....	37
3.1.5.13	Microsoft.SharePoint.Client.Social.SocialFeedOptions.....	37
3.1.5.13.1	Properties.....	37
3.1.5.13.1.1	Scalar Properties .....	37
3.1.5.13.1.1.1	MaxThreadCount .....	37
3.1.5.13.1.1.2	NewerThan .....	38
3.1.5.13.1.1.3	OlderThan .....	38
3.1.5.13.1.1.4	SortOrder.....	38
3.1.5.13.1.2	ObjectPath Properties.....	38
3.1.5.14	Microsoft.SharePoint.Client.Social.SocialFeedSortOrder.....	38
3.1.5.14.1	Field Values .....	38
3.1.5.14.1.1	ByModifiedTime .....	38
3.1.5.14.1.2	ByCreatedTime.....	38
3.1.5.15	Microsoft.SharePoint.Client.Social.SocialFeedStatus .....	39
3.1.5.15.1	Field Values .....	39

3.1.5.15.1.1	OK .....	39
3.1.5.16	Microsoft.SharePoint.Client.Social.SocialFeedType .....	39
3.1.5.16.1	Field Values .....	39
3.1.5.16.1.1	Personal .....	39
3.1.5.16.1.2	News .....	39
3.1.5.16.1.3	Timeline .....	39
3.1.5.16.1.4	Likes .....	39
3.1.5.16.1.5	Company .....	40
3.1.5.17	Microsoft.SharePoint.Client.Social.SocialFollowingManager .....	40
3.1.5.17.1	Properties .....	40
3.1.5.17.1.1	Scalar Properties .....	40
3.1.5.17.1.1.1	FollowedDocumentsUri .....	40
3.1.5.17.1.1.2	FollowedSitesUri .....	40
3.1.5.17.1.2	ObjectPath Properties .....	40
3.1.5.17.2	Methods .....	40
3.1.5.17.2.1	Scalar Methods .....	40
3.1.5.17.2.1.1	Follow .....	40
3.1.5.17.2.1.2	GetFollowed .....	41
3.1.5.17.2.1.3	GetFollowedCount .....	41
3.1.5.17.2.1.4	GetFollowers .....	41
3.1.5.17.2.1.5	GetSuggestions .....	41
3.1.5.17.2.1.6	IsFollowed .....	42
3.1.5.17.2.1.7	StopFollowing .....	42
3.1.5.17.2.2	ObjectPath Methods .....	42
3.1.5.17.2.2.1	CSOM Constructor .....	42
3.1.5.18	Microsoft.SharePoint.Client.Social.SocialFollowResult .....	42
3.1.5.18.1	Field Values .....	42
3.1.5.18.1.1	OK .....	42
3.1.5.18.1.2	AlreadyFollowing .....	43
3.1.5.18.1.3	LimitReached .....	43
3.1.5.18.1.4	InternalError .....	43
3.1.5.19	Microsoft.SharePoint.Client.Social.SocialLink .....	43
3.1.5.19.1	Properties .....	43
3.1.5.19.1.1	Scalar Properties .....	43
3.1.5.19.1.1.1	Text .....	43
3.1.5.19.1.1.2	Uri .....	43
3.1.5.19.1.2	ObjectPath Properties .....	43
3.1.5.20	Microsoft.SharePoint.Client.Social.SocialPost .....	44
3.1.5.20.1	Properties .....	44
3.1.5.20.1.1	Scalar Properties .....	44
3.1.5.20.1.1.1	Attachment .....	44
3.1.5.20.1.1.2	Attributes .....	44
3.1.5.20.1.1.3	AuthorIndex .....	44
3.1.5.20.1.1.4	CreatedTime .....	44
3.1.5.20.1.1.5	Id .....	44
3.1.5.20.1.1.6	LikerInfo .....	45
3.1.5.20.1.1.7	ModifiedTime .....	45
3.1.5.20.1.1.8	Overlays .....	45
3.1.5.20.1.1.9	PostType .....	45
3.1.5.20.1.1.10	PreferredImageUri .....	45
3.1.5.20.1.1.11	Source .....	45
3.1.5.20.1.1.12	Text .....	46
3.1.5.20.1.2	ObjectPath Properties .....	46

3.1.5.21	Microsoft.SharePoint.Client.Social.SocialPostActorInfo	46
3.1.5.21.1	Properties	46
3.1.5.21.1.1	Scalar Properties	46
3.1.5.21.1.1.1	Indexes	46
3.1.5.21.1.1.2	TotalCount	46
3.1.5.21.1.1.3	IncludesCurrentUser	46
3.1.5.21.1.2	ObjectPath Properties	47
3.1.5.22	Microsoft.SharePoint.Client.Social.SocialPostAttributes	47
3.1.5.22.1	Field Values	47
3.1.5.22.1.1	None	47
3.1.5.22.1.2	CanLike	47
3.1.5.22.1.3	CanDelete	47
3.1.5.22.1.4	UseAuthorImage	47
3.1.5.22.1.5	UseSmallImage	47
3.1.5.22.1.6	CanFollowUp	47
3.1.5.23	Microsoft.SharePoint.Client.Social.SocialPostCreationData	48
3.1.5.23.1	Properties	48
3.1.5.23.1.1	Scalar Properties	48
3.1.5.23.1.1.1	Attachment	48
3.1.5.23.1.1.2	ContentItems	48
3.1.5.23.1.1.3	ContentText	48
3.1.5.23.1.1.4	DefinitionData	48
3.1.5.23.1.1.5	Source	49
3.1.5.23.1.1.6	SecurityUri	49
3.1.5.23.1.1.7	UpdateStatusText	49
3.1.5.23.1.2	ObjectPath Properties	49
3.1.5.24	Microsoft.SharePoint.Client.Social.SocialPostDefinitionData	49
3.1.5.24.1	Properties	49
3.1.5.24.1.1	Scalar Properties	49
3.1.5.24.1.1.1	Items	49
3.1.5.24.1.1.2	Name	50
3.1.5.24.1.2	ObjectPath Properties	50
3.1.5.25	Microsoft.SharePoint.Client.Social.SocialPostDefinitionDataItem	50
3.1.5.25.1	Properties	50
3.1.5.25.1.1	Scalar Properties	50
3.1.5.25.1.1.1	AccountName	50
3.1.5.25.1.1.2	ItemType	50
3.1.5.25.1.1.3	PlaceholderName	50
3.1.5.25.1.1.4	TagGuid	51
3.1.5.25.1.1.5	Text	51
3.1.5.25.1.1.6	Uri	51
3.1.5.25.1.2	ObjectPath Properties	51
3.1.5.26	Microsoft.SharePoint.Client.Social.SocialPostDefinitionDataItemType	51
3.1.5.26.1	Field Values	51
3.1.5.26.1.1	Text	51
3.1.5.26.1.2	User	51
3.1.5.26.1.3	Document	52
3.1.5.26.1.4	Site	52
3.1.5.26.1.5	Tag	52
3.1.5.26.1.6	Link	52
3.1.5.27	Microsoft.SharePoint.Client.Social.SocialPostReference	52
3.1.5.27.1	Properties	52
3.1.5.27.1.1	Scalar Properties	52

3.1.5.27.1.1.1	Digest	52
3.1.5.27.1.1.2	Post	52
3.1.5.27.1.1.3	ThreadId	53
3.1.5.27.1.2	ObjectPath Properties	53
3.1.5.28	Microsoft.SharePoint.Client.Social.SocialPostType	53
3.1.5.28.1	Field Values	53
3.1.5.28.1.1	Root	53
3.1.5.28.1.2	Reply	53
3.1.5.29	Microsoft.SharePoint.Client.Social.SocialRestActor	53
3.1.5.29.1	Properties	53
3.1.5.29.1.1	Scalar Properties	53
3.1.5.29.1.1.1	FollowableItem	53
3.1.5.29.1.1.2	Me	54
3.1.5.29.1.2	ObjectPath Properties	54
3.1.5.29.2	Methods	54
3.1.5.29.2.1	Scalar Methods	54
3.1.5.29.2.1.1	UnreadMentionCount	54
3.1.5.29.2.2	ObjectPath Methods	54
3.1.5.29.2.2.1	CSOM Constructor	54
3.1.5.29.2.2.2	Feed	54
3.1.5.29.2.2.3	Likes	55
3.1.5.29.2.2.4	Mentionfeed	55
3.1.5.29.2.2.5	News	56
3.1.5.29.2.2.6	Timelinefeed	56
3.1.5.30	Microsoft.SharePoint.Client.Social.SocialRestFeed	56
3.1.5.30.1	Properties	57
3.1.5.30.1.1	Scalar Properties	57
3.1.5.30.1.1.1	Action	57
3.1.5.30.1.1.2	SocialFeed	57
3.1.5.30.1.2	ObjectPath Properties	57
3.1.5.30.2	Methods	57
3.1.5.30.2.1	Scalar Methods	57
3.1.5.30.2.2	ObjectPath Methods	57
3.1.5.30.2.2.1	CSOM Constructor	57
3.1.5.30.2.2.2	ClearUnReadMentionCount	57
3.1.5.30.2.2.3	Post	58
3.1.5.31	Microsoft.SharePoint.Client.Social.SocialRestFeedManager	58
3.1.5.31.1	Properties	59
3.1.5.31.1.1	Scalar Properties	59
3.1.5.31.1.2	ObjectPath Properties	59
3.1.5.31.2	Methods	59
3.1.5.31.2.1	Scalar Methods	59
3.1.5.31.2.2	ObjectPath Methods	59
3.1.5.31.2.2.1	CSOM Constructor	59
3.1.5.31.2.2.2	Actor	59
3.1.5.31.2.2.3	My	59
3.1.5.31.2.2.4	Post	60
3.1.5.32	Microsoft.SharePoint.Client.Social.SocialRestFollowingManager	60
3.1.5.32.1	Properties	60
3.1.5.32.1.1	Scalar Properties	60
3.1.5.32.1.1.1	FollowedDocumentsUri	60
3.1.5.32.1.1.2	FollowedSitesUri	61
3.1.5.32.1.1.3	MyFollowedDocumentsUri	61



3.1.5.32.1.1.4	MyFollowedSitesUri.....	61
3.1.5.32.1.1.5	SocialActor.....	61
3.1.5.32.1.2	ObjectPath Properties.....	61
3.1.5.32.2	Methods.....	62
3.1.5.32.2.1	Scalar Methods.....	62
3.1.5.32.2.1.1	Follow.....	62
3.1.5.32.2.1.2	Followed.....	62
3.1.5.32.2.1.3	FollowedCount.....	63
3.1.5.32.2.1.4	Followers.....	63
3.1.5.32.2.1.5	IsFollowed.....	63
3.1.5.32.2.1.6	StopFollowing.....	64
3.1.5.32.2.1.7	Suggestions.....	64
3.1.5.32.2.2	ObjectPath Methods.....	65
3.1.5.32.2.2.1	CSOM Constructor.....	65
3.1.5.32.2.2.2	my.....	65
3.1.5.33	Microsoft.SharePoint.Client.Social.SocialRestPostCreationData.....	65
3.1.5.33.1	Properties.....	66
3.1.5.33.1.1	Scalar Properties.....	66
3.1.5.33.1.1.1	creationData.....	66
3.1.5.33.1.1.2	ID.....	66
3.1.5.33.1.2	ObjectPath Properties.....	66
3.1.5.34	Microsoft.SharePoint.Client.Social.SocialRestThread.....	66
3.1.5.34.1	Properties.....	66
3.1.5.34.1.1	Scalar Properties.....	66
3.1.5.34.1.1.1	ID.....	66
3.1.5.34.1.1.2	SocialThread.....	66
3.1.5.34.1.2	ObjectPath Properties.....	67
3.1.5.34.2	Methods.....	67
3.1.5.34.2.1	Scalar Methods.....	67
3.1.5.34.2.1.1	Delete.....	67
3.1.5.34.2.1.2	Likers.....	67
3.1.5.34.2.2	ObjectPath Methods.....	68
3.1.5.34.2.2.1	CSOM Constructor.....	68
3.1.5.34.2.2.2	Like.....	68
3.1.5.34.2.2.3	Lock.....	68
3.1.5.34.2.2.4	Reply.....	69
3.1.5.34.2.2.5	Unlike.....	69
3.1.5.34.2.2.6	UnLock.....	70
3.1.5.35	Microsoft.SharePoint.Client.Social.SocialThread.....	70
3.1.5.35.1	Properties.....	71
3.1.5.35.1.1	Scalar Properties.....	71
3.1.5.35.1.1.1	Actors.....	71
3.1.5.35.1.1.2	Attributes.....	71
3.1.5.35.1.1.3	Id.....	71
3.1.5.35.1.1.4	OwnerIndex.....	71
3.1.5.35.1.1.5	Permalink.....	71
3.1.5.35.1.1.6	PostReference.....	71
3.1.5.35.1.1.7	Replies.....	72
3.1.5.35.1.1.8	RootPost.....	72
3.1.5.35.1.1.9	Status.....	72
3.1.5.35.1.1.10	ThreadType.....	72
3.1.5.35.1.1.11	TotalReplyCount.....	72
3.1.5.35.1.2	ObjectPath Properties.....	73

3.1.5.36	Microsoft.SharePoint.Client.Social.SocialThreadAttributes	73
3.1.5.36.1	Field Values	73
3.1.5.36.1.1	None	73
3.1.5.36.1.2	IsDigest	73
3.1.5.36.1.3	CanReply	73
3.1.5.36.1.4	CanLock	73
3.1.5.36.1.5	IsLocked	73
3.1.5.36.1.6	ReplyLimitReached	73
3.1.5.37	Microsoft.SharePoint.Client.Social.SocialThreadStatus	73
3.1.5.37.1	Field Values	74
3.1.5.37.1.1	OK	74
3.1.5.38	Microsoft.SharePoint.Client.Social.SocialThreadType	74
3.1.5.38.1	Field Values	74
3.1.5.38.1.1	Normal	74
3.1.5.38.1.2	LikeReference	74
3.1.5.38.1.3	ReplyReference	74
3.1.5.38.1.4	MentionReference	74
3.1.5.38.1.5	TagReference	74
3.1.5.39	Microsoft.SharePoint.Client.UserProfiles.ChangeTypes	75
3.1.5.39.1	Field Values	75
3.1.5.39.1.1	None	75
3.1.5.39.1.2	Add	75
3.1.5.39.1.3	Modify	75
3.1.5.39.1.4	Remove	75
3.1.5.39.1.5	Metadata	75
3.1.5.39.1.6	All	75
3.1.5.40	Microsoft.SharePoint.Client.UserProfiles.FollowedContent	75
3.1.5.40.1	Properties	76
3.1.5.40.1.1	Scalar Properties	76
3.1.5.40.1.1.1	FollowedDocumentsUrl	76
3.1.5.40.1.1.2	FollowedSitesUrl	76
3.1.5.40.1.2	ObjectPath Properties	76
3.1.5.40.2	Methods	76
3.1.5.40.2.1	Scalar Methods	76
3.1.5.40.2.1.1	FindAndUpdateFollowedItem	76
3.1.5.40.2.1.2	Follow	76
3.1.5.40.2.1.3	GetFollowedStatus	77
3.1.5.40.2.1.4	IsFollowed	77
3.1.5.40.2.1.5	StopFollowing	77
3.1.5.40.2.1.6	UpdateData	77
3.1.5.40.2.1.7	FollowItem	78
3.1.5.40.2.1.8	GetItem	78
3.1.5.40.2.1.9	GetItems	78
3.1.5.40.2.1.10	RefreshFollowedItem	79
3.1.5.40.2.2	ObjectPath Methods	79
3.1.5.40.2.2.1	CSOM Constructor	79
3.1.5.41	Microsoft.SharePoint.Client.UserProfiles.FollowedContentExceptionCode	79
3.1.5.41.1	Field Values	79
3.1.5.41.1.1	ItemAlreadyExists	79
3.1.5.41.1.2	ItemDoesNotExist	79
3.1.5.41.1.3	InvalidQueryString	80
3.1.5.41.1.4	InvalidSubtypeValue	80
3.1.5.41.1.5	UnsupportedItemType	80

3.1.5.41.1.6	FollowLimitReached	80
3.1.5.41.1.7	UntrustedSource	80
3.1.5.41.1.8	InternalError	80
3.1.5.41.1.9	UnsupportedSite	80
3.1.5.42	Microsoft.SharePoint.Client.UserProfiles.FollowedContentQueryOptions	80
3.1.5.42.1	Field Values	81
3.1.5.42.1.1	Unset	81
3.1.5.42.1.2	Sites	81
3.1.5.42.1.3	Documents	81
3.1.5.42.1.4	Hidden	81
3.1.5.42.1.5	NonFeed	81
3.1.5.42.1.6	DefaultOptions	81
3.1.5.42.1.7	All	81
3.1.5.43	Microsoft.SharePoint.Client.UserProfiles.FollowedItem	81
3.1.5.43.1	Properties	82
3.1.5.43.1.1	Scalar Properties	82
3.1.5.43.1.1.1	Data	82
3.1.5.43.1.1.2	Title	82
3.1.5.43.1.1.3	Url	82
3.1.5.43.1.1.4	FileType	82
3.1.5.43.1.1.5	Hidden	82
3.1.5.43.1.1.6	IconUrl	82
3.1.5.43.1.1.7	ItemId	83
3.1.5.43.1.1.8	ItemType	83
3.1.5.43.1.1.9	ListId	83
3.1.5.43.1.1.10	ParentUrl	83
3.1.5.43.1.1.11	SiteId	83
3.1.5.43.1.1.12	Subtype	83
3.1.5.43.1.1.13	UniqueId	83
3.1.5.43.1.1.14	WebId	84
3.1.5.43.1.1.15	Flags	84
3.1.5.43.1.1.16	HasFeed	84
3.1.5.43.1.1.17	FileTypeProgid	84
3.1.5.43.1.1.18	ServerUrlProgid	84
3.1.5.43.1.2	ObjectPath Properties	84
3.1.5.44	Microsoft.SharePoint.Client.UserProfiles.FollowedItemData	84
3.1.5.44.1	Properties	85
3.1.5.44.1.1	Scalar Properties	85
3.1.5.44.1.1.1	Properties	85
3.1.5.44.1.2	ObjectPath Properties	85
3.1.5.44.2	Methods	85
3.1.5.44.2.1	Scalar Methods	85
3.1.5.44.2.2	ObjectPath Methods	85
3.1.5.44.2.2.1	CSOM Constructor	85
3.1.5.45	Microsoft.SharePoint.Client.UserProfiles.FollowedItemType	85
3.1.5.45.1	Field Values	85
3.1.5.45.1.1	Unknown	85
3.1.5.45.1.2	Document	86
3.1.5.45.1.3	Site	86
3.1.5.45.1.4	All	86
3.1.5.46	Microsoft.SharePoint.Client.UserProfiles.FollowResult	86
3.1.5.46.1	Properties	86
3.1.5.46.1.1	Scalar Properties	86

3.1.5.46.1.1.1	Item .....	86
3.1.5.46.1.1.2	ResultType .....	86
3.1.5.46.1.2	ObjectPath Properties .....	86
3.1.5.47	Microsoft.SharePoint.Client.UserProfiles.FollowResultType .....	86
3.1.5.47.1	Field Values .....	87
3.1.5.47.1.1	Unknown .....	87
3.1.5.47.1.2	Followed .....	87
3.1.5.47.1.3	Refollowed .....	87
3.1.5.47.1.4	HitFollowLimit .....	87
3.1.5.47.1.5	Failed .....	87
3.1.5.48	Microsoft.SharePoint.Client.UserProfiles.FollowedStatus .....	87
3.1.5.48.1	Field Values .....	87
3.1.5.48.1.1	Followed .....	87
3.1.5.48.1.2	NotFollowed .....	87
3.1.5.48.1.3	NotFollowable .....	88
3.1.5.49	Microsoft.SharePoint.Client.UserProfiles.ObjectTypes .....	88
3.1.5.49.1	Field Values .....	88
3.1.5.49.1.1	None .....	88
3.1.5.49.1.2	SingleValueProperty .....	88
3.1.5.49.1.3	MultiValueProperty .....	88
3.1.5.49.1.4	Anniversary .....	88
3.1.5.49.1.5	DLMembership .....	88
3.1.5.49.1.6	SiteMembership .....	88
3.1.5.49.1.7	QuickLink .....	88
3.1.5.49.1.8	Colleague .....	89
3.1.5.49.1.9	PersonalizationSite .....	89
3.1.5.49.1.10	UserProfile .....	89
3.1.5.49.1.11	WebLog .....	89
3.1.5.49.1.12	Custom .....	89
3.1.5.49.1.13	OrganizationProfile .....	89
3.1.5.49.1.14	OrganizationMembership .....	89
3.1.5.49.1.15	All .....	89
3.1.5.50	Microsoft.SharePoint.Client.UserProfiles.PeopleManager .....	89
3.1.5.50.1	Properties .....	90
3.1.5.50.1.1	Scalar Properties .....	90
3.1.5.50.1.1.1	EditProfileLink .....	90
3.1.5.50.1.1.2	IsMyPeopleListPublic .....	90
3.1.5.50.1.2	ObjectPath Properties .....	90
3.1.5.50.2	Methods .....	90
3.1.5.50.2.1	Scalar Methods .....	90
3.1.5.50.2.1.1	AmIFollowedBy .....	90
3.1.5.50.2.1.2	AmIFollowing .....	90
3.1.5.50.2.1.3	Follow .....	91
3.1.5.50.2.1.4	HideSuggestion .....	91
3.1.5.50.2.1.5	IsFollowing .....	91
3.1.5.50.2.1.6	StopFollowing .....	91
3.1.5.50.2.1.7	GetUserProfilePropertiesFor .....	92
3.1.5.50.2.1.8	GetUserProfilePropertyFor .....	92
3.1.5.50.2.1.9	SetMyProfilePicture .....	92
3.1.5.50.2.1.10	FollowTag .....	92
3.1.5.50.2.1.11	StopFollowingTag .....	93
3.1.5.50.2.2	ObjectPath Methods .....	93
3.1.5.50.2.2.1	GetMyProperties .....	93

3.1.5.50.2.2.2	GetPropertiesFor .....	93
3.1.5.50.2.2.3	CSOM Constructor .....	93
3.1.5.50.2.2.4	GetFollowersFor .....	93
3.1.5.50.2.2.5	GetMyFollowers.....	94
3.1.5.50.2.2.6	GetMySuggestions.....	94
3.1.5.50.2.2.7	GetPeopleFollowedBy.....	94
3.1.5.50.2.2.8	GetPeopleFollowedByMe.....	94
3.1.5.51	Microsoft.SharePoint.Client.UserProfiles.PersonalSiteCapabilities.....	94
3.1.5.51.1	Field Values .....	95
3.1.5.51.1.1	Uninitialized .....	95
3.1.5.51.1.2	None .....	95
3.1.5.51.1.3	Profile .....	95
3.1.5.51.1.4	Social.....	95
3.1.5.51.1.5	Storage .....	95
3.1.5.51.1.6	MyTasksDashboard .....	95
3.1.5.52	Microsoft.SharePoint.Client.UserProfiles.PersonProperties .....	95
3.1.5.52.1	Properties.....	95
3.1.5.52.1.1	Scalar Properties .....	95
3.1.5.52.1.1.1	AccountName .....	95
3.1.5.52.1.1.2	DirectReports.....	96
3.1.5.52.1.1.3	DisplayName .....	96
3.1.5.52.1.1.4	Email .....	96
3.1.5.52.1.1.5	ExtendedManagers .....	96
3.1.5.52.1.1.6	ExtendedReports.....	96
3.1.5.52.1.1.7	IsFollowed.....	96
3.1.5.52.1.1.8	LatestPost .....	97
3.1.5.52.1.1.9	Peers .....	97
3.1.5.52.1.1.10	PersonalUrl .....	97
3.1.5.52.1.1.11	PictureUrl .....	97
3.1.5.52.1.1.12	Title.....	97
3.1.5.52.1.1.13	UserUrl.....	97
3.1.5.52.1.1.14	UserProfileProperties.....	97
3.1.5.52.1.2	ObjectPath Properties.....	98
3.1.5.52.2	Methods.....	98
3.1.5.52.2.1	Scalar Methods.....	98
3.1.5.52.2.2	ObjectPath Methods .....	98
3.1.5.53	Microsoft.SharePoint.Client.UserProfiles.ProfileLoader.....	98
3.1.5.53.1	Properties.....	98
3.1.5.53.1.1	Scalar Properties .....	98
3.1.5.53.1.2	ObjectPath Properties.....	98
3.1.5.53.2	Methods.....	98
3.1.5.53.2.1	Scalar Methods.....	98
3.1.5.53.2.2	ObjectPath Methods .....	98
3.1.5.53.2.2.1	GetProfileLoader.....	98
3.1.5.53.2.2.2	GetUserProfile.....	99
3.1.5.54	Microsoft.SharePoint.Client.UserProfiles.SocialDataStoreExceptionCode .....	99
3.1.5.54.1	Field Values .....	99
3.1.5.54.1.1	SocialListNotFound.....	99
3.1.5.54.1.2	PersonalSiteNotFound .....	99
3.1.5.54.1.3	CannotCreatePersonalSite.....	99
3.1.5.55	Microsoft.SharePoint.Client.UserProfiles.UserProfile .....	99
3.1.5.55.1	Properties.....	99
3.1.5.55.1.1	Scalar Properties .....	99

3.1.5.55.1.1.1	UrlToCreatePersonalSite .....	99
3.1.5.55.1.1.2	PersonalSiteCapabilities .....	100
3.1.5.55.1.1.3	PictureImportEnabled .....	100
3.1.5.55.1.2	ObjectPath Properties .....	100
3.1.5.55.1.2.1	FollowedContent .....	100
3.1.5.55.1.2.2	PersonalSite .....	100
3.1.5.55.2	Methods .....	100
3.1.5.55.2.1	Scalar Methods .....	100
3.1.5.55.2.1.1	CreatePersonalSite .....	100
3.1.5.55.2.1.2	ShareAllSocialData .....	101
3.1.5.55.2.2	ObjectPath Methods .....	101
3.1.5.56	Microsoft.SharePoint.Client.UserProfiles.UserProfilePropertiesForUser .....	101
3.1.5.56.1	Properties .....	101
3.1.5.56.1.1	Scalar Properties .....	101
3.1.5.56.1.1.1	AccountName .....	101
3.1.5.56.1.2	ObjectPath Properties .....	101
3.1.5.56.2	Methods .....	101
3.1.5.56.2.1	Scalar Methods .....	101
3.1.5.56.2.1.1	GetPropertyNames .....	101
3.1.5.56.2.2	ObjectPath Methods .....	102
3.1.5.56.2.2.1	CSOM Constructor .....	102
3.1.5.57	Microsoft.Office.Server.ReputationModel.Reputation .....	102
3.1.5.57.1	Properties .....	102
3.1.5.57.1.1	Scalar Properties .....	102
3.1.5.57.1.2	ObjectPath Properties .....	102
3.1.5.57.2	Methods .....	102
3.1.5.57.2.1	Scalar Methods .....	102
3.1.5.57.2.1.1	SetLike .....	102
3.1.5.57.2.1.2	SetRating .....	103
3.1.5.57.2.2	ObjectPath Methods .....	103
3.1.6	Timer Events .....	103
3.1.7	Other Local Events .....	103
<b>4</b>	<b>Protocol Examples .....</b>	<b>104</b>
4.1	Making a New Root Post .....	104
4.2	Response from Server for New Root Post .....	105
4.3	Posting a New Reply .....	106
4.4	Server Response for a New Reply .....	107
4.5	Requesting a Feed .....	110
4.6	Server Response for Requesting a Feed .....	111
4.7	Liking a Post .....	114
4.8	Server Response to Liking a Post .....	114
4.9	Making a New Root Post Using REST .....	116
4.10	Server Response to Making a New Root Post Using REST .....	117
4.11	Posting a New Reply Using REST .....	119
4.12	Server Response to Posting a New Reply Using REST .....	119
4.13	Getting a Thread Using REST .....	122
4.14	Server Response to Getting a Thread Using REST .....	122
<b>5</b>	<b>Security .....</b>	<b>126</b>
5.1	Security Considerations for Implementers .....	126
5.2	Index of Security Parameters .....	126

<b>6 Appendix A: Product Behavior .....</b>	<b>127</b>
<b>7 Change Tracking.....</b>	<b>128</b>
<b>8 Index .....</b>	<b>129</b>

Preliminary

# 1 Introduction

The SharePoint Social Client-Side Object Model Protocol provides types, methods, and properties to enable a protocol client to access social data for the current user. Social data includes:

- User profiles
- Microblogging
- Activity Feeds
- Following people and content
- Sharing documents

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

### GUID

The following terms are defined in [\[MS-OFCGLOS\]](#):

### Boolean

### CSOM Boolean

### CSOM DateTime

### CSOM dictionary

### CSOM Double

### CSOM GUID

### CSOM Int32

### CSOM String

### list

### list item

### Uniform Resource Locator (URL)

The following terms are specific to this document:

**default scalar property set:** A set of properties that are retrieved by default for an object. The properties map to fields in a storage schema.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.



### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-CSOM] Microsoft Corporation, "[SharePoint Client Query Protocol Specification](#)".

[MS-CSOMREST] Microsoft Corporation, "[SharePoint Client Query OData Protocol Specification](#)".

[MS-SITEDATS] Microsoft Corporation, "[Site Data Web Service Protocol Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

[RFC4627] Crockford, D., "The application/json Media Type for Javascript Object Notation (JSON)", RFC 4627, July 2006, <http://www.ietf.org/rfc/rfc4627.txt>

### 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".


[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

### 1.3 Overview

This protocol defines types, methods, and properties that protocol clients use to access feeds and social data on a protocol server. The set of types, properties, and methods provide the ability for remote clients to send and retrieve data from site social features. Social features include getting and writing to feeds, getting user profile data, specifying what documents, users, tags, and sites that the user running on the protocol client system likes or follows, and getting information about the current user's social contacts.

### 1.4 Relationship to Other Protocols

The SharePoint Social Client-Side Object Model Protocol is a set of types, properties, and methods that can be accessed by using the SharePoint Client Query protocol as described in [\[MS-CSOM\]](#). This protocol uses JSON as described in [\[RFC4627\]](#) to format data returned to a protocol client. This protocol also uses HTTP, as described in [\[RFC2616\]](#), and HTTPS, as described in [\[RFC2818\]](#). The dependencies for this protocol are shown in the following layering diagram.



### 1.5 Prerequisites/Preconditions

This protocol operates on a site that is identified by a **Uniform Resource Locator (URL)** that is known by protocol clients. This protocol assumes that authentication has been performed by underlying protocols.

### 1.6 Applicability Statement

None

### 1.7 Versioning and Capability Negotiation

None

### 1.8 Vendor-Extensible Fields

None

### 1.9 Standards Assignments

None

## 2 Messages

### 2.1 Transport

Messages are transported by using the SharePoint Client Query Protocol Specification, as specified in [\[MS-CSOM\]](#).

### 2.2 Message Syntax

None

#### 2.2.1 Namespaces

The SharePoint Social Client-Side Object Model uses the following namespaces:

- Microsoft.Office.Server.ReputationModel
- Microsoft.SharePoint.Client.UserProfiles
- Microsoft.SharePoint.Client.Social

## 3 Protocol Details

### 3.1 Server Details

#### 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

The server maintains a set of social information for each user. This social information includes the following:

- Messages posted by a user, which can be a response to another message, can contain social mentions of a user, and can contain social tags.
- Social likes and follows specified by the user, which identify other users, message posts, documents, tags, and web sites that the user has selected.

This protocol shares the abstract data model used by the SharePoint Client Query protocol as described in [\[MS-CSOM\]](#) section 3.1.1 to communicate with the protocol server.

#### 3.1.2 Timers

None

#### 3.1.3 Initialization

None

#### 3.1.4 Higher-Layer Triggered Events

None

#### 3.1.5 Message Processing Events and Sequencing Rules

##### 3.1.5.1 Microsoft.SharePoint.Client.Social.SocialActor

**TypeId:** {A9A8B6CF-B696-4DBC-BD62-B78D45149EB1}

**ShortName:** SP.Social.SocialActor

The **SocialActor** type contains information about an actor retrieved from server. An actor is a user, document, site, or tag.

##### 3.1.5.1.1 Properties

###### 3.1.5.1.1.1 Scalar Properties

###### 3.1.5.1.1.1.1 AccountName

**Type:** CSOM String

**Accessibility:** Read Only

The **AccountName** property returns the user account name. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **User**.

#### 3.1.5.1.1.1.2 ActorType

**Type:** Microsoft.SharePoint.Client.Social.SocialActorType

**Accessibility:** Read Only

The **ActorType** property identifies whether the actor is a user, document, site, or tag.

See section [3.1.5.3](#) for details on the **SocialActorType** type.

#### 3.1.5.1.1.1.3 EmailAddress

**Type:** CSOM String

**Accessibility:** Read Only

The **EmailAddress** property returns the email address of the user. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **User**.

#### 3.1.5.1.1.1.4 FollowedContentUri

**Type:** CSOM String

**Accessibility:** Read Only

The **FollowedContentUri** property returns the URI of the user's followed content folder. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **User**.

#### 3.1.5.1.1.1.5 Id

**Type:** CSOM String

**Accessibility:** Read Only

The **Id** property returns the actor's unique identifier.

#### 3.1.5.1.1.1.6 ImageUri

**Type:** CSOM String

**Accessibility:** Read Only

The **ImageUri** property returns the URI of the image representing the actor. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **User**, **Document**, or **Site**.

#### 3.1.5.1.1.1.7 LibraryUri

**Type:** CSOM String

**Accessibility:** Read Only

The **LibraryUri** property returns the URI of the library containing the document. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **Document**.

#### 3.1.5.1.1.1.8 Name

**Type:** CSOM String

**Accessibility:** Read Only

The **Name** property returns the actor's display name.

#### 3.1.5.1.1.1.9 TagGuid

**Type:** CSOM GUID

**Accessibility:** Read Only

The **TagGuid** property returns the GUID of the tag. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **Tag**.

#### 3.1.5.1.1.1.10 Title

**Type:** CSOM String

**Accessibility:** Read Only

The **Title** property returns the user's title. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **User**.

#### 3.1.5.1.1.1.11 Uri

**Type:** CSOM String

**Accessibility:** Read Only

The **Uri** property returns the URI of the actor.

#### 3.1.5.1.1.1.12 ContentUri

**Type:** CSOM String

**Accessibility:** Read Only

The **ContentUri** property returns the URI of the document or site content. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **Document** or **Site**.

#### 3.1.5.1.1.1.13 IsFollowed

**Type:** CSOM Boolean

**Accessibility:** Read Only

The **IsFollowed** property returns true if the current user is following the actor; otherwise, it returns false.

#### 3.1.5.1.1.1.14 PersonalSiteUri

**Type:** CSOM String

**Accessibility:** Read Only

The **PersonalSiteUri** property returns the URI of the user's personal site. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **User**.

#### 3.1.5.1.1.1.15 StatusText

**Type:** CSOM String

**Accessibility:** Read Only

The **StatusText** property returns the most recent post of the user. This property is only available if the **ActorType** property (see section [3.1.5.1.1.1.2](#)) has a value of **User**.

#### 3.1.5.1.1.2 ObjectPath Properties

None.

#### 3.1.5.2 Microsoft.SharePoint.Client.Social.SocialActorInfo

**TypeId:** {700A3260-5AFB-4CF9-B401-A8E1F2C89EFC}

**ShortName:** SP.Social.SocialActorInfo

The **SocialActorInfo** type identifies an actor to the server. An actor can be a user, document, site, or tag.

#### 3.1.5.2.1 Properties

##### 3.1.5.2.1.1 Scalar Properties

###### 3.1.5.2.1.1.1 AccountName

**Type:** CSOM String

**Accessibility:** Read/Write

The **AccountName** property specifies the user's account name.

###### 3.1.5.2.1.1.2 ActorType

**Type:** Microsoft.SharePoint.Client.Social.SocialActorType

**Accessibility:** Read/Write

The **ActorType** property identifies whether the actor is a user, document, site, or tag. If the **Id** property is not empty, the server ignores the **ActorType** property. See section [3.1.5.3](#) for details on the **SocialActorType** type.

###### 3.1.5.2.1.1.3 ContentUri

**Type:** CSOM String

**Accessibility:** Read/Write

The **ContentUri** property identifies the actor by its URI. Documents and sites can be identified by this property.

#### 3.1.5.2.1.1.4 Id

**Type:** CSOM String

**Accessibility:** Read/Write

The **Id** property identifies the actor by its unique identification. If the **Id** property is not empty, it is sufficient to identify the actor. Consequently, if the **Id** property is not empty, the server ignores all other properties. In some cases, the client may not have access to the actor's unique identification. In these cases, the client can use the other properties to identify the actor.

#### 3.1.5.2.1.1.5 TagGuid

**Type:** CSOM GUID

**Accessibility:** Read/Write

The **TagGuid** identifies the actor by its GUID. Tags can be identified by this property.

#### 3.1.5.2.1.2 ObjectPath Properties

None.

### 3.1.5.3 Microsoft.SharePoint.Client.Social.SocialActorType

**ShortName:** SP.Social.SocialActorType

**Flag:** false

The **SocialActorType** type identifies an actor as a user, document, site, or tag.

#### 3.1.5.3.1 Field Values

##### 3.1.5.3.1.1 User

**Value:** 0

The actor is a user.

##### 3.1.5.3.1.2 Document

**Value:** 1

The actor is a document.

##### 3.1.5.3.1.3 Site

**Value:** 2

The actor is a site.



#### **3.1.5.3.1.4 Tag**

**Value:** 3

The actor is a tag.

#### **3.1.5.4 Microsoft.SharePoint.Client.Social.SocialActorTypes**

**ShortName:** SP.Social.SocialActorTypes

**Flag:** true

The **SocialActorTypes** flag type specifies one or more actor types in a query to the server.

##### **3.1.5.4.1 Field Values**

###### **3.1.5.4.1.1 None**

**Value:** 0

This value specifies no actor type.

###### **3.1.5.4.1.2 Users**

**Value:** 1

This value specifies the actor type users.

###### **3.1.5.4.1.3 Documents**

**Value:** 2

This value specifies the actor type documents.

###### **3.1.5.4.1.4 Sites**

**Value:** 4

This value specifies the actor type sites.

###### **3.1.5.4.1.5 Tags**

**Value:** 8

This value specifies the actor type tags.

###### **3.1.5.4.1.6 All**

**Value:** 15

This value specifies the actor types users, documents, sites, and tags.

###### **3.1.5.4.1.7 ExcludeContentWithoutFeeds**

**Value:** 268435456

The set excludes documents and sites that do not have feeds.

### 3.1.5.5 Microsoft.SharePoint.Client.Social.SocialAttachment

**TypeId:** {74C3AAFE-F743-415A-A839-EE0AB0F340A1}

**ShortName:** SP.Social.SocialAttachment

The **SocialAttachment** class represents the metadata for image, video, and document preview.

#### 3.1.5.5.1 Properties

##### 3.1.5.5.1.1 Scalar Properties

###### 3.1.5.5.1.1.1 Description

**Type:** CSOM String

**Accessibility:** Read/Write

The **Description** property provides a text description of the attachment.

###### 3.1.5.5.1.1.2 Name

**Type:** CSOM String

**Accessibility:** Read/Write

The **Name** property provides the attachment name.

###### 3.1.5.5.1.1.3 Uri

**Type:** CSOM String

**Accessibility:** Read/Write

The **Uri** property provides the attachment URI.

##### 3.1.5.5.1.2 ObjectPath Properties

None.

### 3.1.5.6 Microsoft.SharePoint.Client.Social.SocialDataItem

**TypeId:** {F6AEF1D2-6189-4848-9F6C-C4CCCF4D548D}

**ShortName:** SP.Social.SocialDataItem

The **SocialDataItem** class defines a user, document, site, tag, or link to be inserted in a new post. The **SocialPostCreationData** class (see section [3.1.5.23](#)) defines the content text that contains substitution strings. Each substitution string is replaced by a **SocialDataItem** value.

### 3.1.5.6.1 Properties

#### 3.1.5.6.1.1 Scalar Properties

##### 3.1.5.6.1.1.1 AccountName

**Type:** CSOM String

**Accessibility:** Read/Write

The **AccountName** property specifies the user by account name. This property is only used if the **ItemType** (see section [3.1.5.6.1.1.2](#)) has a value of **User**.

##### 3.1.5.6.1.1.2 ItemType

**Type:** Microsoft.SharePoint.Client.Social.SocialDataItemType

**Accessibility:** Read/Write

The **ItemType** property specifies whether the item being inserted is a user, document, site, tag, or link. See section [3.1.5.7](#) for details on the **SocialDataItemType** type.

##### 3.1.5.6.1.1.3 TagGuid

**Type:** CSOM GUID

**Accessibility:** Read/Write

The **TagGuid** property specifies the tag by its GUID. This property is only used if the **ItemType** (see section [3.1.5.6.1.1.2](#)) has a value of **Tag**.

##### 3.1.5.6.1.1.4 Text

**Type:** CSOM String

**Accessibility:** Read/Write

The **Text** property specifies the plain text to be inserted in the created post. The server can use the specified text or can use text that identifies the item, for example the name specified in a user profile.

##### 3.1.5.6.1.1.5 Uri

**Type:** CSOM String

**Accessibility:** Read/Write

The **Uri** property identifies the site, document, or link. This property is only used if the **ItemType** (see section [3.1.5.6.1.1.2](#)) has a value of **Document**, **Site**, or **Link**.

#### 3.1.5.6.1.2 ObjectPath Properties

None.

### 3.1.5.7 Microsoft.SharePoint.Client.Social.SocialDataItemType

**ShortName:** SP.Social.SocialDataItemType

**Flag:** false

The **SocialDataItemType** type specifies whether the item being inserted is a user, document, site, tag, or link.

#### 3.1.5.7.1 Field Values

##### 3.1.5.7.1.1 User

**Value:** 0

The item is a user.

##### 3.1.5.7.1.2 Document

**Value:** 1

The item is a document.

##### 3.1.5.7.1.3 Site

**Value:** 2

The item is a site.

##### 3.1.5.7.1.4 Tag

**Value:** 3

The item is a tag.

##### 3.1.5.7.1.5 Link

**Value:** 4

The item is a link.

### 3.1.5.8 Microsoft.SharePoint.Client.Social.SocialDataOverlay

**TypeId:** {154BD33E-3BEA-40D6-B869-CAC54A473FE7}

**ShortName:** SP.Social.SocialDataOverlay

The **SocialDataOverlay** class provides information about an overlay. An overlay is a substring in a post that represents a user, document, site, tag, or link. The **SocialPost** class (see section [3.1.5.20](#)) contains an array of **SocialDataOverlay** objects. Each of the **SocialDataOverlay** objects specifies a link or one or more actors.

### 3.1.5.8.1 Properties

#### 3.1.5.8.1.1 Scalar Properties

##### 3.1.5.8.1.1.1 ActorIndexes

**Type:** CSOM Array

**Accessibility:** Read Only

The **ActorIndexes** property specifies one or more actors as an array of integers where each integer specifies an index into the **SocialThread Actors** array (see section [3.1.5.35.1.1.1](#)). Each actor can be a user, document, site, or tag. This property is only available if the **OverlayType** (see section [3.1.5.8.1.1.5](#)) has a value of **Actors**.

##### 3.1.5.8.1.1.2 Index

**Type:** CSOM Int32

**Accessibility:** Read Only

The **Index** property specifies the starting position of the overlay in the **SocialPost Text** string (see section [3.1.5.20.1.1.12](#)).

##### 3.1.5.8.1.1.3 Length

**Type:** CSOM Int32

**Accessibility:** Read Only

The **Length** property specifies the number of characters in the overlay.

##### 3.1.5.8.1.1.4 LinkUri

**Type:** CSOM String

**Accessibility:** Read Only

The **LinkUri** property specifies the URI of the link. This property is only available if the **OverlayType** (see section [3.1.5.8.1.1.5](#)) has a value of **Link**.

##### 3.1.5.8.1.1.5 OverlayType

**Type:** Microsoft.SharePoint.Client.Social.SocialDataOverlayType

**Accessibility:** Read Only

The **OverlayType** property specifies whether the overlay is a link or one or more actors. If the overlay specifies one or more actors, the array entry in the **SocialThread Actors** array (see section [3.1.5.35.1.1.1](#)) specifies whether the actor is a user, document, site, or tag. See section [3.1.5.9](#) for details on the **SocialDataOverlayType** type.

#### 3.1.5.8.1.2 ObjectPath Properties

None.

### 3.1.5.9 Microsoft.SharePoint.Client.Social.SocialDataOverlayType

**ShortName:** SP.Social.SocialDataOverlayType

**Flag:** false

The **SocialDataOverlayType** type specifies whether the overlay is a link or one or more actors.

#### 3.1.5.9.1 Field Values

##### 3.1.5.9.1.1 Link

**Value:** 0

The substring in the post represents a link.

##### 3.1.5.9.1.2 Actors

**Value:** 1

The substring in the post represents one or more actors.

### 3.1.5.10 Microsoft.SharePoint.Client.Social.SocialFeed

**TypeId:** {0EB7D3EA-3238-4CAA-9D34-7AD86514B18B}

**ShortName:** SP.Social.SocialFeed

The **SocialFeed** class specifies a feed, which contains an array of **SocialThreads**, each of which specifies a root **SocialPost** object and an array of response **SocialPost** objects.

#### 3.1.5.10.1 Properties

##### 3.1.5.10.1.1 Scalar Properties

###### 3.1.5.10.1.1.1 Attributes

**Type:** Microsoft.SharePoint.Client.Social.SocialFeedAttributes

**Accessibility:** Read Only

The **Attributes** property specifies attributes of the returned feed. The attributes specify if the requested feed has additional threads that were not included in the returned thread. See section [3.1.5.11](#) for details on the **SocialFeedAttributes** type.

###### 3.1.5.10.1.1.2 FailedActorIds

**Type:** CSOM Array

**Accessibility:** Read Only

The **FailedActorIds** property is an array of strings that identify actors whose threads could not be retrieved [<1>](#).

### 3.1.5.10.1.1.3 NewestProcessed

**Type:** CSOM DateTime

**Accessibility:** Read Only

The **NewestProcessed** property returns the date-time of the most recent post that was requested. The most recent post that was requested can be removed from the feed if the current user does not have access to it. Consequently, the feed does not always contain the post with the date specified in this property.

### 3.1.5.10.1.1.4 OldestProcessed

**Type:** CSOM DateTime

**Accessibility:** Read Only

The **OldestProcessed** property returns the date-time of the oldest post that was requested. The oldest post that was requested can be removed from the feed if the current user does not have access to it. Consequently, the feed does not always contain the post with the date specified in this property.

### 3.1.5.10.1.1.5 Status

**Type:** Microsoft.SharePoint.Client.Social.SocialFeedStatus

**Accessibility:** Read Only

The **Status** property returns information about whether there were recoverable errors when retrieving the feed. See section [3.1.5.11](#) for details on the **SocialFeedStatus** type.

### 3.1.5.10.1.1.6 Threads

**Type:** Microsoft.SharePoint.Client.Social.SocialThread[]

**Accessibility:** Read Only

The **Threads** property contains the social threads in the feed. See section [3.1.5.35](#) for details on the **SocialThread** class.

### 3.1.5.10.1.1.7 UnreadMentionCount

**Type:** CSOM Int32

**Accessibility:** Read Only

The **UnreadMentionCount** property returns the number of mentions of the current user that have been added to the feed on the server since the time that the unread mention count was cleared for the current user.

The **GetMentions** method (see section [3.1.5.12.2.1.7](#)) optionally clears the unread mention count for the current user.

The **UnreadMentionCount** property is available only for social feeds returned by the **GetFeed** method (see section [3.1.5.12.2.1.4](#)).

### 3.1.5.10.1.2 ObjectPath Properties

None.

### 3.1.5.11 Microsoft.SharePoint.Client.Social.SocialFeedAttributes

**ShortName:** SP.Social.SocialFeedAttributes

**Flag:** true

The **SocialFeedAttributes** type provides information about the feed. This type provides information about whether the feed on the server contains additional threads that were not returned.

#### 3.1.5.11.1 Field Values

##### 3.1.5.11.1.1 None

**Value:** 0

No attributes are specified for the feed.

##### 3.1.5.11.1.2 MoreThreadsAvailable

**Value:** 1

There are additional threads in the feed on the server that were not returned to the client.

### 3.1.5.12 Microsoft.SharePoint.Client.Social.SocialFeedManager

**TypeId:** {C32F5230-2ED0-48FA-AC80-E2FFA22E3D28}

**ShortName:** SP.Social.SocialFeedManager

The **SocialFeedManager** class provides access to social feeds. It provides methods to create posts, delete posts, read posts, and perform other operations on posts.

#### 3.1.5.12.1 Properties

##### 3.1.5.12.1.1 Scalar Properties

###### 3.1.5.12.1.1.1 Owner

**Type:** Microsoft.SharePoint.Client.Social.SocialActor

**Accessibility:** Read Only

The **Owner** property returns the current user. See section [3.1.5.1](#) for details on the **SocialActor** type.

##### 3.1.5.12.1.2 ObjectPath Properties

None.



## 3.1.5.12.2 Methods

### 3.1.5.12.2.1 Scalar Methods

#### 3.1.5.12.2.1.1 CreatePost

**Return Type:** Microsoft.SharePoint.Client.Social.SocialThread

The **CreatePost** method creates a post in the current user's newsfeed, in the specified user's feed, or in the specified thread. This method returns a new or a modified thread. See section [3.1.5.35](#) for details on the **SocialThread** class.

**Parameters:**

*targetId*: Optional, specifies the target of the post. If this parameter is null, the post is created as a root post in the current user's feed. If this parameter is set to a site URL or a site actor identification, the post is created as a root post in the specified site feed. If this parameter is set to a thread identification, the post is created as a reply post in the specified thread.

Type: CSOM String

If *targetId* is an empty string, the post is created as a new thread in the current user's newsfeed.

*creationData*: Specifies the text and details of the post.

Type: Microsoft.SharePoint.Client.Social.SocialPostCreationData

*CreationData* specifies the format and content of the post, see section [3.1.5.23](#) for details on the **SocialPostCreationData** class.

#### 3.1.5.12.2.1.2 DeletePost

**Return Type:** Microsoft.SharePoint.Client.Social.SocialThread

The **DeletePost** method deletes the specified post. This method returns a digest of the modified thread. If the entire thread is deleted, this method returns null. See section [3.1.5.35](#) for details on the **SocialThread** class.

**Parameters:**

*postId*: Specifies the post to be deleted. The post identifier is specified in the **SocialPost.Id** property (see section [3.1.5.20.1.1.5](#)).

Type: CSOM String

If the post being deleted is the root post of a thread, all reply posts are also deleted.

#### 3.1.5.12.2.1.3 GetAllLikers

**Return Type:** Microsoft.SharePoint.Client.Social.SocialActor[]

The **GetAllLikers** method returns the set of users who have liked the specified post. See section [3.1.5.1](#) for details on the **SocialActor** class.

**Parameters:**

*postId*: Specifies the post being queried for information about users that like the post. The post identifier is specified in the **SocialPost.Id** property (see section [3.1.5.20.1.1.5](#)).

Type: CSOM String

#### 3.1.5.12.2.1.4 GetFeed

**Return Type:** Microsoft.SharePoint.Client.Social.SocialFeed

The **GetFeed** method returns a feed for the current user. The feed consists of an array of message threads. Each thread consists of a root post and an array of reply posts. See section [3.1.5.10](#) for details on the **SocialFeed** type. The server selects a set of posts to return in the feed based on the *type* and *options* parameters, but this protocol does not require any specific algorithm to select the set of posts from all posts that meet the specified *type* and *options*.

**Parameters:**

*type*: Specifies the type of feed to be returned. Feeds can be viewed using a personal view, news view, timeline view, or likes view. If the type is not specified, **GetFeed** returns the news view.

Type: Microsoft.SharePoint.Client.Social.SocialFeedType

See section [3.1.5.16](#) for details on the **SocialFeedType** type.

*options*: Specifies the maximum number of threads to get in the feed, the sort order of the threads, and how the threads are to be selected based on the date and time that the threads were created.

Type: Microsoft.SharePoint.Client.Social.SocialFeedOptions

See section [3.1.5.13](#) for details on the **SocialFeedOptions** type.

#### 3.1.5.12.2.1.5 GetFeedFor

**Return Type:** Microsoft.SharePoint.Client.Social.SocialFeed

The **GetFeedFor** method returns the public feed for a user or for a site. The feed lists activity by the user and posts created by the server for that user. For example, the feed can include posts indicating the user's birthday or indicating that the user liked a post. See section [3.1.5.10](#) for details on the **SocialFeed** type. The server selects a set of posts to return in the feed based on the *options* parameter, but this protocol does not require any specific algorithm to select the returned set of posts from all posts on the server.

**Parameters:**

*actorId*: Specifies the user or site. The user is specified by an actor identification or an account name. The site is specified by an actor identification or a site URL.

Type: CSOM String

The actor identification is specified in the **Id** property of the **SocialActor** object. See section [3.1.5.1.1.1.5](#) for details. If the *actorId* specifies the current user, this method returns the public feed for the current user.

*options*: Specifies the maximum number of threads to get in the feed, the sort order of the threads, and how the threads are to be selected based on the date and time that the threads were created.

Type: Microsoft.SharePoint.Client.Social.SocialFeedOptions

See section [3.1.5.13](#) for details on **SocialFeedOptions**.

#### 3.1.5.12.2.1.6 GetFullThread

**Return Type:** Microsoft.SharePoint.Client.Social.SocialThread

The **GetFullThread** method returns the root post and all reply posts in the thread. See section [3.1.5.35](#) for details on the **SocialThread** class.

**Parameters:**

*threadId*: Specifies the identifier of the thread.

Type: CSOM String

The thread identifier is specified in the **Id** property of the **SocialThread** object. See section [3.1.5.35.1.1.3](#) for details.

#### 3.1.5.12.2.1.7 GetMentions

**Return Type:** Microsoft.SharePoint.Client.Social.SocialFeed

The **GetMentions** method returns a feed containing mention reference threads from the current user's personal feed. See section [3.1.5.10](#) for details on the **SocialFeed** object.

**Parameters:**

*clearUnreadMentions*: If true, clear the count of unread mentions.

Type: CSOM Boolean

*options*: Specifies the maximum number of threads, dates of the posts, and the sort order.

Type: Microsoft.SharePoint.Client.Social.SocialFeedOptions

See section [3.1.5.13](#) for details on the **SocialFeedOptions** type.

#### 3.1.5.12.2.1.8 GetUnreadMentionCount

**Return Type:** CSOM Int32

The **GetUnreadMentionCount** method returns the server's count of unread mentions of the current user. The server maintains a count of unread mentions in posts, but does not track which mentions have been read. When a new mention is stored on the server, it increments the unread mention for the user specified by the mention. When the unread mention count is cleared by the **GetMentions** method (see section [3.1.5.12.2.1.7](#)), it is set to zero.

**Parameters:** None

#### 3.1.5.12.2.1.9 LikePost

**Return Type:** Microsoft.SharePoint.Client.Social.SocialThread

The **LikePost** method specifies that the current user likes the specified post. Returns a digest thread containing the specified post. A digest thread contains the root post and a selection of reply posts [<2>](#). See section [3.1.5.35](#) for details on the **SocialThread** class.

**Parameters:**

*postId*: Specifies the post being liked. The post identifier is specified in the **SocialPost.Id** property (see section [3.1.5.20.1.1.5](#)).

Type: CSOM String

**3.1.5.12.2.1.10 LockThread**

**Return Type:** Microsoft.SharePoint.Client.Social.SocialThread

The **LockThread** method prevents any user from adding a new reply post to the specified thread. Once a thread is locked, no new reply posts can be added until after the thread has been unlocked with the **UnlockThread** method (see section [3.1.5.12.2.1.12](#)). This method returns a digest of the locked thread. See section [3.1.5.35](#) for details on the **SocialThread** class.

**Parameters:**

*threadId*: Specifies the thread to be locked. The thread identifier is specified in the **SocialThread.Id** property (see section [3.1.5.35.1.1.3](#)).

Type: CSOM String

**3.1.5.12.2.1.11 UnlikePost**

**Return Type:** Microsoft.SharePoint.Client.Social.SocialThread

The **UnlikePost** method specifies that the current user does not like the specified post. Returns a digest thread containing the specified post. A digest thread contains the root post and a selection of reply posts<3>. See section [3.1.5.35](#) for details on the **SocialThread** class.

**Parameters:**

*postId*: Specifies the post being unliked. The post identifier is specified in the **SocialPost.Id** property (see section [3.1.5.20.1.1.5](#)).

Type: CSOM String

**3.1.5.12.2.1.12 UnlockThread**

**Return Type:** Microsoft.SharePoint.Client.Social.SocialThread

The **UnlockThread** method allows users to add new reply posts to the specified thread. See section [3.1.5.12.2.1.12](#) for details on the **LockThread** method. The **UnlockThread** method returns a digest thread. See section [3.1.5.35](#) for details on the **SocialThread** class.

**Parameters:**

*threadId*: Specifies the thread to be unlocked. The thread identifier is specified in the **SocialThread.Id** property (see section [3.1.5.35.1.1.3](#)).

Type: CSOM String

**3.1.5.12.2.1.13 SuppressThreadNotifications**

**Return Type:** None

The **SuppressThreadNotifications** method suppresses activity notifications for the current user of updates to the specified thread.

**Parameters:**

*threadId*: Thread to suppress update notifications.

Type: CSOM String

### 3.1.5.12.2.1.14 CreateImageAttachment

**Return Type:** Microsoft.SharePoint.Client.Social.SocialAttachment

The **CreateImageAttachment** method creates an image attachment for a future post.

**Parameters:**

*name*: The name of the image.

Type: CSOM String

*description*: An optional description of the image.

Type: CSOM String

*imageData*: A stream containing the image data.

Type: CSOM Stream

### 3.1.5.12.2.2 ObjectPath Methods

#### 3.1.5.12.2.2.1 CSOM Constructor

The constructor method initializes a new instance of **SocialFeedManager** (see section [3.1.5.12](#)).

**Parameters:** None

### 3.1.5.13 Microsoft.SharePoint.Client.Social.SocialFeedOptions

**TypeId:** {86CFC806-C9BB-448A-AED2-C7FF9A5B7EE6}

**ShortName:** SP.Social.SocialFeedOptions

The **SocialFeedOptions** class specifies selection criteria and sort options when retrieving threads from a feed on a server. The selection criteria are the maximum number of threads to return and the date-time range of threads to return. The sort options control whether the threads are sorted by creation time or modification time.

#### 3.1.5.13.1 Properties

##### 3.1.5.13.1.1 Scalar Properties

###### 3.1.5.13.1.1.1 MaxThreadCount

**Type:** CSOM Int32

**Accessibility:** Read/Write

The **MaxThreadCount** property specifies the maximum number of threads that are to be returned in the feed.

#### 3.1.5.13.1.1.2 NewerThan

**Type:** CSOM DateTime

**Accessibility:** Read/Write

The **NewerThan** property specifies a date; any thread older than this date is not returned. To specify a range of dates to select, specify the oldest date in the **NewerThan** property and the most recent date in the **OlderThan** property (see section [3.1.5.13.1.1.3](#)).

#### 3.1.5.13.1.1.3 OlderThan

**Type:** CSOM DateTime

**Accessibility:** Read/Write

The **OlderThan** property specifies a date; any thread newer than this date is not returned. To specify a range of dates to select, specify the oldest date in the **NewerThan** property (see section [3.1.5.13.1.1.2](#)) and the most recent date in the **OlderThan** property.

#### 3.1.5.13.1.1.4 SortOrder

**Type:** Microsoft.SharePoint.Client.Social.SocialFeedSortOrder

**Accessibility:** Read/Write

The **SortOrder** property specifies whether the threads are to be sorted in creation time or in modification time order. See section [3.1.5.14](#) for details on the **SocialFeedSortOrder** type.

#### 3.1.5.13.1.2 ObjectPath Properties

None.

### 3.1.5.14 Microsoft.SharePoint.Client.Social.SocialFeedSortOrder

**ShortName:** SP.Social.SocialFeedSortOrder

**Flag:** false

The **SocialFeedSortOrder** type specifies whether the sort order is by creation time or modification time.

#### 3.1.5.14.1 Field Values

##### 3.1.5.14.1.1 ByModifiedTime

**Value:** 0

The sort order is by modification time.

##### 3.1.5.14.1.2 ByCreatedTime

**Value:** 1

The sort order is by creation time.

### 3.1.5.15 Microsoft.SharePoint.Client.Social.SocialFeedStatus

**ShortName:** SP.Social.SocialFeedStatus

**Flag:** false

The **SocialFeedStatus** type identifies if a recoverable problem was encountered while retrieving the feed. A recoverable problem is one in which the overall operation succeeds and a feed is returned but information about the problem encountered is returned.

#### 3.1.5.15.1 Field Values

##### 3.1.5.15.1.1 OK

**Value:** 0

There was no problem encountered in retrieving the feed.

### 3.1.5.16 Microsoft.SharePoint.Client.Social.SocialFeedType

**ShortName:** SP.Social.SocialFeedType

**Flag:** false

The **SocialFeedType** type identifies the kind of post to be retrieved.

#### 3.1.5.16.1 Field Values

##### 3.1.5.16.1.1 Personal

**Value:** 0

This value specifies a feed that contains posts that are activities by the current user, such as posts or likes by the current user.

##### 3.1.5.16.1.2 News

**Value:** 1

This is the default value and specifies posts that are activities by the current user or by users and other actors that the current user is following.

##### 3.1.5.16.1.3 Timeline

**Value:** 2

This value returns the same kinds of posts as the **News** value, but gives priority to selecting posts from more different actors. In contrast, **News** gives priority to selecting the most recent posts that meet the selection criteria.

##### 3.1.5.16.1.4 Likes

**Value:** 3

This value specifies a feed consisting of reference posts that identify the posts that the current user likes.

### 3.1.5.16.1.5 Company

**Value:** 4

This value specifies a feed that contains posts from all users.

### 3.1.5.17 Microsoft.SharePoint.Client.Social.SocialFollowingManager

**TypeId:** {651F2511-B4A4-4C3D-8C12-B049C7F79D69}

**ShortName:** SP.Social.SocialFollowingManager

The **SocialFollowingManager** class provides properties and methods for managing a user's list of followed actors. Actors can be users, documents, sites, and tags.

#### 3.1.5.17.1 Properties

##### 3.1.5.17.1.1 Scalar Properties

###### 3.1.5.17.1.1.1 FollowedDocumentsUri

**Type:** CSOM String

**Accessibility:** Read Only

The **FollowedDocumentsUri** property returns a URI to a site that lists the current user's followed documents.

###### 3.1.5.17.1.1.2 FollowedSitesUri

**Type:** CSOM String

**Accessibility:** Read Only

The **FollowedSitesUri** property returns a URI to a site that lists the current user's followed sites.

###### 3.1.5.17.1.2 ObjectPath Properties

None.

#### 3.1.5.17.2 Methods

##### 3.1.5.17.2.1 Scalar Methods

###### 3.1.5.17.2.1.1 Follow

**Return Type:** Microsoft.SharePoint.Client.Social.SocialFollowResult

The **Follow** method adds the specified actor to the current user's list of followed items. This method returns information on whether the actor was successfully added to the current user's list. See section [3.1.5.18](#) for details on the **SocialFollowResult** type.



**Parameters:**

*actor*: Specifies the user, document, site, or tag to follow.

Type: Microsoft.SharePoint.Client.Social.SocialActorInfo

See section [3.1.5.2](#) for details on the **SocialActorInfo** type.

### 3.1.5.17.2.1.2 GetFollowed

**Return Type:** Microsoft.SharePoint.Client.Social.SocialActor[]

The **GetFollowed** method retrieves a list of the specified kind of actors being followed by the current user. For details on the **SocialActor** type, see section [3.1.5.1](#).

**Parameters:**

*types*: Specifies the kind of actors to select.

Type: Microsoft.SharePoint.Client.Social.SocialActorTypes

For details on the **SocialActorTypes** type, see section [3.1.5.4](#).

### 3.1.5.17.2.1.3 GetFollowedCount

**Return Type:** CSOM Int32

The **GetFollowedCount** method returns the number of the specified kind of actors being followed by the current user.

**Parameters:**

*types*: Specifies the kind of actors to select.

Type: Microsoft.SharePoint.Client.Social.SocialActorTypes

For details on the **SocialActorTypes** type, see section [3.1.5.4](#).

### 3.1.5.17.2.1.4 GetFollowers

**Return Type:** Microsoft.SharePoint.Client.Social.SocialActor[]

The **GetFollowers** method returns the users who are followers of the current user.

**Parameters:** None

### 3.1.5.17.2.1.5 GetSuggestions

**Return Type:** Microsoft.SharePoint.Client.Social.SocialActor[]

The **GetSuggestions** method returns a list of actors that are suggestions for the current user to follow.

**Parameters:** None

### 3.1.5.17.2.1.6 IsFollowed

**Return Type:** CSOM Boolean

The **IsFollowed** method returns true if the current user is following the specified actor, and otherwise returns false.

**Parameters:**

*actor*: Specifies the actor, which is a document, user, site, or tag.

Type: Microsoft.SharePoint.Client.Social.SocialActorInfo

For details on the **SocialActorInfo** type, see section [3.1.5.3](#).

### 3.1.5.17.2.1.7 StopFollowing

**Return Type:** None

The **StopFollowing** method removes the specified actor from the list of actors that the current user is following.

**Parameters:**

*actor*: Specifies the actor, which is a document, user, site, or tag.

Type: Microsoft.SharePoint.Client.Social.SocialActorInfo

For details on the **SocialActorInfo** type, see section [3.1.5.3](#).

### 3.1.5.17.2.2 ObjectPath Methods

#### 3.1.5.17.2.2.1 CSOM Constructor

The constructor method initializes a new instance of **SocialFollowingManager** (see section [3.1.5.17](#)).

**Parameters:** None

### 3.1.5.18 Microsoft.SharePoint.Client.Social.SocialFollowResult

**ShortName:** SP.Social.SocialFollowResult

**Flag:** false

The **SocialFollowResult** type specifies the result status of a request to follow an actor.

#### 3.1.5.18.1 Field Values

##### 3.1.5.18.1.1 OK

**Value:** 0

This value specifies that the request to follow the actor succeeded and the current user now follows the specified actor.

### 3.1.5.18.1.2 AlreadyFollowing

**Value:** 1

This value specifies that the current user was already following the specified actor and no actions were performed to meet the request.

### 3.1.5.18.1.3 LimitReached

**Value:** 2

This value specifies that the request to follow the actor failed because an internal limit was reached. The current user is not following the specified actor.

### 3.1.5.18.1.4 InternalError

**Value:** 3

This value specifies that the request to follow the actor failed because an internal error was encountered. The current user is not following the specified actor.

## 3.1.5.19 Microsoft.SharePoint.Client.Social.SocialLink

**TypeId:** {31B25401-CEC9-496E-A758-B0B280C1711E}

**ShortName:** SP.Social.SocialLink

The **SocialLink** class defines a link that includes a URI and text representation. This class is used to represent the location of a web site.

### 3.1.5.19.1 Properties

#### 3.1.5.19.1.1 Scalar Properties

##### 3.1.5.19.1.1.1 Text

**Type:** CSOM String

**Accessibility:** Read/Write

The **Text** property specifies the text to display for the link.

##### 3.1.5.19.1.1.2 Uri

**Type:** CSOM String

**Accessibility:** Read/Write

The **Uri** property specifies the address of the post source.

#### 3.1.5.19.1.2 ObjectPath Properties

None.

### 3.1.5.20 Microsoft.SharePoint.Client.Social.SocialPost

**TypeId:** {11386A5F-9543-44B8-8A96-1AA33D964F87}

**ShortName:** SP.Social.SocialPost

The **SocialPost** specifies a post read from the server.

#### 3.1.5.20.1 Properties

##### 3.1.5.20.1.1 Scalar Properties

###### 3.1.5.20.1.1.1 Attachment

**Type:** Microsoft.SharePoint.Client.Social.SocialAttachment

**Accessibility:** Read Only

The **Attachment** property specifies an image. For details on the **SocialAttachment** type, see section [3.1.5.5](#).

###### 3.1.5.20.1.1.2 Attributes

**Type:** Microsoft.SharePoint.Client.Social.SocialPostAttributes

**Accessibility:** Read Only

The **Attributes** property describes attributes about the post, such as whether the current user can delete or like the post. For details on the **SocialPostAttributes** type, see section [3.1.5.22](#).

###### 3.1.5.20.1.1.3 AuthorIndex

**Type:** CSOM Int32

**Accessibility:** Read Only

Specifies the author of the post as an index to the social thread's **Actors** array (see section [3.1.5.35.1.1.1](#)).

###### 3.1.5.20.1.1.4 CreatedTime

**Type:** CSOM DateTime

**Accessibility:** Read Only

The **CreatedTime** property specifies the date and time that the post was created on the server.

###### 3.1.5.20.1.1.5 Id

**Type:** CSOM String

**Accessibility:** Read Only

The **Id** property specifies the unique identifier of the post.

### 3.1.5.20.1.1.6 LikerInfo

**Type:** Microsoft.SharePoint.Client.Social.SocialPostActorInfo

**Accessibility:** Read Only

The **LikerInfo** property specifies information about users who like the post. See section [3.1.5.21](#) for details on the **SocialPostActorInfo** type.

### 3.1.5.20.1.1.7 ModifiedTime

**Type:** CSOM DateTime

**Accessibility:** Read Only

The **ModifiedTime** property specifies the date and time that the post was last modified on the server. The **ModifiedTime** indicates the most recent time that the post was liked or unliked by a user.

### 3.1.5.20.1.1.8 Overlays

**Type:** Microsoft.SharePoint.Client.Social.SocialDataOverlay[]

**Accessibility:** Read Only

The **Overlays** property is an array of objects in a post, where each object represents a user, document, site, tag, or link. See section [3.1.5.8](#) for details on the **SocialDataOverlay** type.

### 3.1.5.20.1.1.9 PostType

**Type:** Microsoft.SharePoint.Client.Social.SocialPostType

**Accessibility:** Read Only

The **PostType** property specifies whether a post is the root post or a reply post in a thread. See section [3.1.5.28](#) for details on the **SocialPostType** type.

### 3.1.5.20.1.1.10 PreferredImageUri

**Type:** CSOM String

**Accessibility:** Read Only

The **PreferredImageUri** property specifies the URI of the author image to be displayed with the post. If this property is not present, there is no preferred image.

### 3.1.5.20.1.1.11 Source

**Type:** Microsoft.SharePoint.Client.Social.SocialLink

**Accessibility:** Read Only

The **Source** property specifies the link to a web site associated with the application that created the post. See section [3.1.5.19](#) for details on the **SocialLink** type.

### 3.1.5.20.1.1.12 Text

**Type:** CSOM String

**Accessibility:** Read Only

The Text property specifies the text of the post. The **Overlays** property (see section [3.1.5.20.1.1.8](#)) identifies substring in the text that represent users, documents, sites, tags, and links.

### 3.1.5.20.1.2 ObjectPath Properties

None.

### 3.1.5.21 Microsoft.SharePoint.Client.Social.SocialPostActorInfo

**TypeId:** {255E9B47-C24C-414E-9ECC-23E42CC7042B}

**ShortName:** SP.Social.SocialPostActorInfo

The **SocialPostActorInfo** class specifies a set of users, documents, sites, and tags by an index into the **SocialThread Actors** array (see section [3.1.5.35.1.1.1](#)). In the **SocialPost LikerInfo** property (see section [3.1.5.20.1.1.6](#)), this class represents a set of users that like the post.

### 3.1.5.21.1 Properties

#### 3.1.5.21.1.1 Scalar Properties

##### 3.1.5.21.1.1.1 Indexes

**Type:** CSOM Array

**Accessibility:** Read Only

The **Indexes** property specifies an array of indexes into the **SocialThread Actors** array (see section [3.1.5.35.1.1.1](#)). The server can choose to return a limited set of actors. For example, the server can choose to return a subset of the users that like a post.

##### 3.1.5.21.1.1.2 TotalCount

**Type:** CSOM Int32

**Accessibility:** Read Only

The **TotalCount** property returns the total number of actors. If the **Indexes** property returns a subset of actors, the **TotalCount** property returns to number of actors in the full set. For example, if the server returns a subset of the likers in the **Indexes** property, the **TotalCount** property specifies the number of users who like the post, and not the number of users returned in **Indexes**.

##### 3.1.5.21.1.1.3 IncludesCurrentUser

**Type:** CSOM Boolean

**Accessibility:** Read Only

The **IncludesCurrentUser** property has a true value if the current user is included in the actors specified. For example, if the current user likes the post, this property has a true value in the

**LikerInfo** property (see section [3.1.5.20.1.1.6](#)). The current user is omitted from the Indexes array.

### 3.1.5.21.1.2 ObjectPath Properties

None.

### 3.1.5.22 Microsoft.SharePoint.Client.Social.SocialPostAttributes

**ShortName:** SP.Social.SocialPostAttributes

**Flag:** true

The **SocialPostAttributes** flag type specifies attributes of the post, such as whether the current user can like or delete the post.

#### 3.1.5.22.1 Field Values

##### 3.1.5.22.1.1 None

**Value:** 0

There are no post attributes.

##### 3.1.5.22.1.2 CanLike

**Value:** 1

The current user can like the post.

##### 3.1.5.22.1.3 CanDelete

**Value:** 2

The current user can delete the post.

##### 3.1.5.22.1.4 UseAuthorImage

**Value:** 4

The post is to be displayed with the author image.

##### 3.1.5.22.1.5 UseSmallImage

**Value:** 8

The post is to be displayed with a small image.

##### 3.1.5.22.1.6 CanFollowUp

**Value:** 16

The current user can create a task from the post.

### 3.1.5.23 Microsoft.SharePoint.Client.Social.SocialPostCreationData

**TypeId:** {2830DD33-271E-4091-A211-E88988E16B03}

**ShortName:** SP.Social.SocialPostCreationData

The **SocialPostCreationData** object specifies the content of a post in the **SocialFeedManager.CreatePost** method (see section [3.1.5.12.2.1.1](#)). The post consists of a text message, which can optionally include social tags, mentions of users, and links.

#### 3.1.5.23.1 Properties

##### 3.1.5.23.1.1 Scalar Properties

###### 3.1.5.23.1.1.1 Attachment

**Type:** Microsoft.SharePoint.Client.Social.SocialAttachment

**Accessibility:** Read/Write

Specifies an image to be used in the post. See section [3.1.5.5](#).

###### 3.1.5.23.1.1.2 ContentItems

**Type:** Microsoft.SharePoint.Client.Social.SocialDataItem[]

**Accessibility:** Read/Write

Specifies an array consisting of social tags, user mentions, links to documents, links to sites, and generic links. Each element in the array is inserted into the **ContentText** string if there is a substitution reference to the array element in the string. See section [3.1.5.6](#) for details on the **SocialDataItem** type and section [3.1.5.23.1.1.3](#) for details on the **ContentText** string.

###### 3.1.5.23.1.1.3 ContentText

**Type:** CSOM String

**Accessibility:** Read/Write

The **ContentText** string contains the text body of the post. It can optionally contain one or more substitution references to elements in the zero-based **SocialDataItems** array. A substitution reference consists of a series of characters that consist of an open-brace character ( { ) followed by one or more digits in the range 0 to 9 and terminated by a close-brace character ( } ). The substitution reference is replaced by the text value of the element in the array at the offset specified by the value of the digits. For example, the text string "{0}" is replaced by the first element in the **SocialDataItems** array.

Although it is not required by this interchange protocol, substitution references to mentions can be preceded by an at sign ( @ ) in the **ContentText** and substitution references to social tags can be preceded by a hash mark ( # ) in the **ContentText**. The at sign and hash mark are not required by the protocol but are helpful if the post is displayed to a user by a client.

###### 3.1.5.23.1.1.4 DefinitionData

**Type:** Microsoft.SharePoint.Client.Social.SocialPostDefinitionData



**Accessibility:** Read/Write

The **DefinitionData** property specifies additional information when creating server-generated posts. This property can only be used in a server-to-server call. The client MUST set this property to the null value. This document does not define any behavior for the server if the client specifies a non-null value.

### 3.1.5.23.1.1.5 Source

**Type:** Microsoft.SharePoint.Client.Social.SocialLink

**Accessibility:** Read/Write

The **Source** property specifies the link to a web site associated with the application that created the post. See section [3.1.5.19](#) for details on the **SocialLink** type.

### 3.1.5.23.1.1.6 SecurityUris

**Type:** CSOM Array

**Accessibility:** Read/Write

The **SecurityUris** property specifies that access to the post SHOULD be restricted to users that have access to the objects identified by the array of URIs. [<4>](#)

### 3.1.5.23.1.1.7 UpdateStatusText

**Type:** CSOM Boolean

**Accessibility:** Read/Write

The **UpdateStatusText** property indicates whether the post is to be used as the current user's new status message.

### 3.1.5.23.1.2 ObjectPath Properties

None.

## 3.1.5.24 Microsoft.SharePoint.Client.Social.SocialPostDefinitionData

**TypeId:** {0DEA3DB3-D522-4691-AB98-9B5FFE6A613F}

**ShortName:** SP.Social.SocialPostDefinitionData

The **SocialPostDefinitionData** type provides additional information about server-generated posts. This type can only be specified in a server-to-server call.

### 3.1.5.24.1 Properties

#### 3.1.5.24.1.1 Scalar Properties

##### 3.1.5.24.1.1.1 Items

**Type:** Microsoft.SharePoint.Client.Social.SocialPostDefinitionDataItem[]

**Accessibility:** Read/Write

The **Items** property specifies an array of **SocialPostDefinitionDataItem** objects. See section [3.1.5.25](#) for details on the **SocialPostDefinitionDataItem** type.

#### 3.1.5.24.1.1.2 Name

**Type:** CSOM String

**Accessibility:** Read/Write

The **Name** property specifies the name of the post definition to be used for the post.

#### 3.1.5.24.1.2 ObjectPath Properties

None.

#### 3.1.5.25 Microsoft.SharePoint.Client.Social.SocialPostDefinitionDataItem

**TypeId:** {C818A4F0-DB17-4E56-B741-4F473C108647}

**ShortName:** SP.Social.SocialPostDefinitionDataItem

The **SocialPostDefinitionDataItem** class specifies an item to be inserted in a post by replacing a token in the post definition. This type can only be specified in a server-to-server call.

#### 3.1.5.25.1 Properties

##### 3.1.5.25.1.1 Scalar Properties

###### 3.1.5.25.1.1.1 AccountName

**Type:** CSOM String

**Accessibility:** Read/Write

The **AccountName** property specifies the name of the user. This property is only available if the **ItemType** property specifies that the item is a **User**.

###### 3.1.5.25.1.1.2 ItemType

**Type:** Microsoft.SharePoint.Client.Social.SocialPostDefinitionDataItemType

**Accessibility:** Read/Write

The **ItemType** property specifies whether the item being formatted is a text element, a user, a document, a site, a tag, or a link. For details on the **SocialPostDefinitionDataItemType** type, see section [3.1.5.26](#).

###### 3.1.5.25.1.1.3 PlaceholderName

**Type:** CSOM String

**Accessibility:** Read/Write

The **PlaceholderName** property specifies the post definition token to be replaced by the item.

#### 3.1.5.25.1.1.4 TagGuid

**Type:** CSOM GUID

**Accessibility:** Read/Write

The **TagGuid** property specifies the GUID that identifies the tag. This property is only used if the **ItemType** property specifies that the item is a **Tag**.

#### 3.1.5.25.1.1.5 Text

**Type:** CSOM String

**Accessibility:** Read/Write

The **Text** property specifies the text that is substituted for the placeholder.

#### 3.1.5.25.1.1.6 Uri

**Type:** CSOM String

**Accessibility:** Read/Write

The **Uri** property specifies the URI of the document, site, or link. This property is only available if the **ItemType** property specifies that the item is a **Document**, **Link**, or **Site**.

#### 3.1.5.25.1.2 ObjectPath Properties

None.

### 3.1.5.26 Microsoft.SharePoint.Client.Social.SocialPostDefinitionDataType

**ShortName:** SP.Social.SocialPostDefinitionDataType

**Flag:** false

The **SocialPostDefinitionDataType** type defines the type of item being specified in the **SocialPostDefinitionDataItem** (see section [3.1.5.25](#)). This type is only available in server-to-server calls.

#### 3.1.5.26.1 Field Values

##### 3.1.5.26.1.1 Text

**Value:** 0

The **SocialPostDefinitionDataItem** is a text element.

##### 3.1.5.26.1.2 User

**Value:** 1

The **SocialPostDefinitionDataItem** is a user.

### 3.1.5.26.1.3 Document

**Value:** 2

The **SocialPostDefinitionDataItem** is a document.

### 3.1.5.26.1.4 Site

**Value:** 3

The **SocialPostDefinitionDataItem** is a site.

### 3.1.5.26.1.5 Tag

**Value:** 4

The **SocialPostDefinitionDataItem** is a tag.

### 3.1.5.26.1.6 Link

**Value:** 5

The **SocialPostDefinitionDataItem** is a link.

## 3.1.5.27 Microsoft.SharePoint.Client.Social.SocialPostReference

**TypeId:** {5952A7BE-5EF5-4246-8760-48544F41EAB9}

**ShortName:** SP.Social.SocialPostReference

The **SocialPostReference** class specifies a reference to a post in another thread. The referenced post can be a post with a tag, a post that is liked, a post that mentions a user, or a post that is a reply. Threads that contain a **SocialPostReference** in the **PostReference** property (see section [3.1.5.35.1.1.6](#)) are threads with root posts that are generated on the server and not created by a client.

### 3.1.5.27.1 Properties

#### 3.1.5.27.1.1 Scalar Properties

##### 3.1.5.27.1.1.1 Digest

**Type:** Microsoft.SharePoint.Client.Social.SocialThread

**Accessibility:** Read Only

The **Digest** property provides a digest of the thread containing the referenced post. See section [3.1.5.35](#) for details on the **SocialThread** class.

##### 3.1.5.27.1.1.2 Post

**Type:** Microsoft.SharePoint.Client.Social.SocialPost

**Accessibility:** Read Only

The **Post** property provides access to the post being referenced. See section [3.1.5.20](#) for details on the **SocialPost** class.

### 3.1.5.27.1.1.3 ThreadId

**Type:** CSOM String

**Accessibility:** Read Only

The **ThreadId** property specifies the unique identifier of the thread containing the referenced post.

### 3.1.5.27.1.2 ObjectPath Properties

None.

### 3.1.5.28 Microsoft.SharePoint.Client.Social.SocialPostType

**ShortName:** SP.Social.SocialPostType

**Flag:** false

The **SocialPostType** type specifies whether a post is the root post or a reply post in a thread.

#### 3.1.5.28.1 Field Values

##### 3.1.5.28.1.1 Root

**Value:** 0

The post is the root post in the thread.

##### 3.1.5.28.1.2 Reply

**Value:** 1

The post is a reply post in the thread.

### 3.1.5.29 Microsoft.SharePoint.Client.Social.SocialRestActor

**TypeId:** {76F18988-E6D7-470C-9421-A221BE0B951C}

**ShortName:** SP.Social.SocialRestActor

The **SocialRestActor** type contains information about an actor retrieved from server. An actor is a user, document, site, or tag. The **SocialRestActor** type is available when the protocol client sends an **OData** request to a protocol server using [\[MS-CSOMREST\]](#). It is not available using [\[MS-CSOM\]](#).

#### 3.1.5.29.1 Properties

##### 3.1.5.29.1.1 Scalar Properties

###### 3.1.5.29.1.1.1 FollowableItem

**Type:** CSOM String

**Accessibility:** Read Only

The **FollowableItem** property provides access to the underlying **SocialActor** type (see section [3.1.5.1](#)). The string can be a URI for a document, site, or tag or can be a user identifier.

### 3.1.5.29.1.1.2 Me

**Type:** Microsoft.SharePoint.Client.Social.SocialActor

**Accessibility:** Read Only

The **Me** property provides access to the current user. See section [3.1.5.1](#) for details on the **SocialActor** type.

### 3.1.5.29.1.2 ObjectPath Properties

None.

### 3.1.5.29.2 Methods

#### 3.1.5.29.2.1 Scalar Methods

##### 3.1.5.29.2.1.1 UnreadMentionCount

**Return Type:** CSOM Int32

The **UnreadMentionCount** method is only available on the **SocialRestActor** object that represents the current user. **UnreadMentionCount** returns the number of mentions of the current user that have been added to the feed on the server since the time that the unread mention count was cleared for the current user.

**Parameters:** None

##### 3.1.5.29.2.2 ObjectPath Methods

###### 3.1.5.29.2.2.1 CSOM Constructor

The constructor method creates a new instance of **SocialRestActor** (see section [3.1.5.4](#)).

**Parameters:** None

###### 3.1.5.29.2.2.2 Feed

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestFeed

The **Feed** method gets a feed that lists activity by the current user. For details on the **SocialRestFeed** type, see section [3.1.5.30](#).

**Parameters:**

*feedOptions:* Specify the maximum number of threads, date-time values to use for selecting threads, and sort order.

Type: Microsoft.SharePoint.Client.Social.SocialFeedOptions

For details on the **SocialFeedOptions** type, see section [3.1.5.13](#)).

For example, the following REST HTTP\_GET message calls the **Feed** resource. The parameter is specified in the URL; consequently, the entity body is equal to the empty string ("").

```
http://my.contoso.com/_api/social.feed/my/Feed(MaxThreadCount=25,SortOrder=0,NewerThan=@v)?@v=dateTime'2012-04-16T08:11'
```

The @v construct used in this message allows a colon (:) to be included in the date-time value.

### 3.1.5.29.2.2.3 Likes

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestFeed

The **Likes** method gets a feed that lists threads containing posts that the current user likes. For details on the **SocialRestFeed** type, see section [3.1.5.30](#).

**Parameters:**

*feedOptions:* Specifies the maximum number of threads, date-time values to use for selecting threads, and sort order.

Type: Microsoft.SharePoint.Client.Social.SocialFeedOptions

For details on the **SocialFeedOptions** type, see section [3.1.5.13](#).

For example, the following REST HTTP\_GET message calls the **Likes** resource. The parameter is specified in the URL; consequently, the entity body is equal to the empty string ("").

```
http://my.contoso.com/_api/social.feed/my/Likes(MaxThreadCount=25,SortOrder=0,NewerThan=@v)?@v=dateTime'2012-04-16T08:11'
```

The @v construct used in this message allows a colon (:) to be included in the date-time value.

### 3.1.5.29.2.2.4 Mentionfeed

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestFeed

The **MentionFeed** method gets a feed consisting of threads that contain posts that mention the current user. For details on the **SocialRestFeed** type, see section [3.1.5.30](#).

**Parameters:**

*feedOptions:* Specifies the maximum number of threads, date-time values to use for selecting threads, and sort order.

Type: Microsoft.SharePoint.Client.Social.SocialFeedOptions

For details on the **SocialFeedOptions** type, see section [3.1.5.13](#).

For example, the following REST HTTP\_GET message calls the **MentionFeed** resource. The parameter is specified in the URL; consequently, the entity body is equal to the empty string ("").

```
http://my.contoso.com/_api/social.feed/my/Mentionfeed(MaxThreadCount=25,SortOrder=0,NewerThan=@v)?@v=dateTime'2012-04-16T08:11'
```

The @v construct used in this message allows a colon (:) to be included in the date-time value.

### 3.1.5.29.2.2.5 News

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestFeed

The **News** method gets a feed that contains posts by the current user and the users that are socially connected to the current user.

**Parameters:**

*feedOptions:* Specifies the maximum number of threads, date-time values to use for selecting threads, and sort order.

Type: Microsoft.SharePoint.Client.Social.SocialFeedOptions

For details on the **SocialFeedOptions** type, see section [3.1.5.13](#).

For example, the following REST HTTP\_GET message calls the **News** resource. The parameter is specified in the URL; consequently, the entity body is equal to the empty string ("").

```
http://my.contoso.com/_api/social.feed/my/news(MaxThreadCount=25,SortOrder=0,NewerThan=@v)?@v=dateTime'2012-04-16T08:11'
```

The @v construct used in this message allows a colon (:) to be included in the date-time value.

### 3.1.5.29.2.2.6 Timelinefeed

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestFeed

The **Timelinefeed** method returns same kind of information as the **News** method (see section [3.1.5.29.2.2.5](#)) but uses a different filter for selecting threads. The **News** method selects threads with the most recent reply post but the **Timelinefeed** method selects threads with the most recent root post.

**Parameters:**

*feedOptions:* Specifies the maximum number of threads, date-time values to use for selecting threads, and sort order.

Type: Microsoft.SharePoint.Client.Social.SocialFeedOptions

For details on the **SocialFeedOptions** type, see section [3.1.5.13](#).

For example, the following REST HTTP\_GET message calls the **Timelinefeed** resource. The parameter is specified in the URL; consequently, the entity body is equal to the empty string ("").

```
http://contoso.com/my/_api/social.feed/my/Timelinefeed(MaxThreadCount=25,SortOrder=0,NewerThan=@v)?@v=dateTime'2012-04-16T08:11'
```

The @v construct used in this message allows a colon (:) to be included in the date-time value.

### 3.1.5.30 Microsoft.SharePoint.Client.Social.SocialRestFeed

**TypeId:** {81C08601-C142-4364-B182-7A0B1052D341}

**ShortName:** SP.Social.SocialRestFeed



The **SocialRestFeed** class specifies a feed, which is an array of thread, each of which specifies a root post and an array of response posts. The **SocialRestFeed** type is available when the protocol client sends an **OData** request to a protocol server using [\[MS-CSOMREST\]](#). It is not available using [\[MS-CSOM\]](#).

### 3.1.5.30.1 Properties

#### 3.1.5.30.1.1 Scalar Properties

##### 3.1.5.30.1.1.1 Action

**Type:** CSOM String

**Accessibility:** Read Only

Not used. MUST be ignored.

##### 3.1.5.30.1.1.2 SocialFeed

**Type:** Microsoft.SharePoint.Client.Social.SocialFeed

**Accessibility:** Read Only

The **SocialFeed** property provides the object that contains the feed. For details on the **SocialFeed** type, see section [3.1.5.10](#).

#### 3.1.5.30.1.2 ObjectPath Properties

None.

### 3.1.5.30.2 Methods

#### 3.1.5.30.2.1 Scalar Methods

None.

#### 3.1.5.30.2.2 ObjectPath Methods

##### 3.1.5.30.2.2.1 CSOM Constructor

The constructor method creates a new instance of **SocialRestFeed** (see section [3.1.5.17](#)).

**Parameters:** None

##### 3.1.5.30.2.2.2 ClearUnReadMentionCount

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestFeed

The **ClearUnReadMentionCount** method clears the count of unread mentions of the current user on the server. For details on the **SocialRestFeed** type, see section [3.1.5.30](#).

**Parameters:**

*feedOptions:* This parameter MUST be null. It is not specified in the REST call.

Type: Microsoft.SharePoint.Client.Social.SocialFeedOptions

For details on the **SocialFeedOptions** type, see section [3.1.5.13](#).

For example, the following REST HTTP\_GET message calls the **ClearUnReadMentionCount** resource. This message has an entity body equal to the empty string ("").

```
http://my.contoso.com/_api/social.feed/my/mentionfeed/ClearUnReadMentionCount
```

The method returns a **SocialRestFeed** object with unabbreviated post and actor information.

### 3.1.5.30.2.2.3 Post

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestThread

The **Post** method creates a new post on the feed. The method returns the newly created thread with the new post. See section [3.1.5.34](#) for details on the **SocialRestThread** type.

**Parameters:**

*restCreationData*: Specifies the content of the post.

Type: Microsoft.SharePoint.Client.Social.SocialRestPostCreationData

See section [3.1.5.33](#) for details on the **SocialRestPostCreationData** type.

For example, the following REST HTTP\_POST message calls the **Post** resource.

```
http://my.contoso.com/_api/social.feed/my/Feed/Post
```

The following is an example of the entity body for this message:

```
{
  'restCreationData': {
    '__metadata': {
      'type': 'SP.Social.SocialRestPostCreationData'
    },
    'ID': null,
    'creationData': {
      '__metadata': {
        'type': 'SP.Social.SocialPostCreationData'
      },
      'ContentText': 'This is my first post',
      'UpdateStatusText': false
    }
  }
}
```

### 3.1.5.31 Microsoft.SharePoint.Client.Social.SocialRestFeedManager

**TypeId:** {0756D6A9-6830-4161-991D-E3CEC6C94E22}

**ShortName:** SP.Social.SocialRestFeedManager

The **SocialRestFeedManager** class provides REST methods for creating posts, modifying threads, and consuming feeds on behalf of the current user. The **SocialRestFeedManager** class is available when the protocol client sends an **OData** request to a protocol server using [\[MS-CSOMREST\]](#). It is not available using [\[MS-CSOM\]](#).

### 3.1.5.31.1 Properties

#### 3.1.5.31.1.1 Scalar Properties

None.

#### 3.1.5.31.1.2 ObjectPath Properties

None.

### 3.1.5.31.2 Methods

#### 3.1.5.31.2.1 Scalar Methods

None.

#### 3.1.5.31.2.2 ObjectPath Methods

##### 3.1.5.31.2.2.1 CSOM Constructor

The constructor method creates a new instance of **SocialRestFeedManager** (see section [3.1.5.31](#)).

**Parameters:** None

##### 3.1.5.31.2.2.2 Actor

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestActor

The **Actor** method accepts an identifier for an actor and returns a **SocialRestActor** entity representing the specified item. See section [3.1.5.29](#) for details on the **SocialRestActor** type.

**Parameters:**

*item*: URL identifying a document or site or a user name in the form *domain\user-name*.

Type: CSOM String

For example, the following REST HTTP\_GET message calls the **Actor** resource. The parameter is specified in the URL; consequently, the entity body is equal to the empty string ("").

```
http://my.contoso.com/_api/social.feed/actor(item='CONTOSO\mhedland')
```

##### 3.1.5.31.2.2.3 My

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestActor

The **My** method gets a **SocialRestActor** object that represents the current user. See section [3.1.5.29](#) for details on the **SocialRestActor** type.

For example, the following REST HTTP\_GET message calls the **My** resource. There is no parameter; consequently, the entity body is equal to the empty string ("")

```
http://my.contoso.com/_api/social.feed/my
```

**Parameters:** None

#### 3.1.5.31.2.2.4 Post

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestThread

The **Post** method retrieves the specified thread or reply post with unabbreviated post and actor information.

**Parameters:**

*ID*: The unique identifier that identifies a thread by the root post identifier or a reply post.

Type: CSOM String

For example, the following REST HTTP\_POST message calls the **Post** resource.

```
http://my.contoso.com/_api/social.feed/Post
```

The following is an example of the entity body for this message:

```
{
  'ID': '1.94fdcc5fc39b4a2c99ae4570caf02321.d0a03fb1761a404a9a8e7f9f5ec58e17.5a1067e8af65410b9e2
ba6a74a4b718a.0c37852b34d0418e91c62ac25af4be5b.9dbfb5598e2248d7b57eee57abf2e7c1.31.31.S-1-5-
21-124525095-708259637-1543119021-565461'
}
```

#### 3.1.5.32 Microsoft.SharePoint.Client.Social.SocialRestFollowingManager

**TypeId:** {2892E6D4-16DA-47BF-A33F-A3C8942503CF}

**ShortName:** SP.Social.SocialRestFollowingManager

The **SocialRestFollowingManager** class provides methods for managing a user's list of followed actors (users, documents, sites, and tags). The **SocialRestFollowingManager** type is available when the protocol client sends an **OData** request to a protocol server using [\[MS-CSOMREST\]](#). It is not available using [\[MS-CSOM\]](#).

The FollowedDocumentsUri and FollowedSitesUri properties are not included in the **default scalar property set** for this type.

##### 3.1.5.32.1 Properties

###### 3.1.5.32.1.1 Scalar Properties

###### 3.1.5.32.1.1.1 FollowedDocumentsUri

**Type:** CSOM String

**Accessibility:** Read Only

The **FollowedDocumentsUri** property specifies a URI to a site that lists the current user's followed documents.

For example, the following REST HTTP\_GET message calls the **FollowedDocumentsUri** resource. There is no parameter; consequently, the entity body is equal to the empty string ("").

```
http://my.contoso.com/_api/social.following/my/FollowedDocumentsUri
```

### 3.1.5.32.1.1.2 FollowedSitesUri

**Type:** CSOM String

**Accessibility:** Read Only

The **FollowedSitesUri** property specifies a URI to a site that lists the current user's followed sites.

For example, the following REST HTTP\_GET message calls the **FollowedSitesUri** resource. There is no parameter; consequently, the entity body is equal to the empty string ("").

```
http://my.contoso.com/_api/social.following/my/FollowedSitesUri
```

### 3.1.5.32.1.1.3 MyFollowedDocumentsUri

**Type:** CSOM String

**Accessibility:** Read Only

The **MyFollowedDocumentsUri** property provides the URI of the page that lists the current user's followed documents.

### 3.1.5.32.1.1.4 MyFollowedSitesUri

**Type:** CSOM String

**Accessibility:** Read Only

The **MyFollowedSitesUri** property provides the URI of the page that lists the current user's followed sites.

### 3.1.5.32.1.1.5 SocialActor

**Type:** Microsoft.SharePoint.Client.Social.SocialActor

**Accessibility:** Read Only

The **SocialActor** property contains the **SocialActor** class for the owner of the **SocialRestFollowingManager**. Typically, this is the current user.

### 3.1.5.32.1.2 ObjectPath Properties

None.

## 3.1.5.32.2 Methods

### 3.1.5.32.2.1 Scalar Methods

#### 3.1.5.32.2.1.1 Follow

**Return Type:** Microsoft.SharePoint.Client.Social.SocialFollowResult

The **Follow** method adds the specified actor to the current user's list of followed actors. For details on the **SocialFollowResult** type, see section [3.1.5.18](#).

**Parameters:**

*actor*: An object that specifies the actor to be added.

Type: Microsoft.SharePoint.Client.Social.SocialActorInfo

For details on the **SocialActorInfo** type, see section [3.1.5.2](#).

For example, the following REST HTTP\_POST message calls the **Follow** resource.

```
http://my.contoso.com/_api/social.following/Follow
```

The following is an example of the entity body for this message:

```
{
  'actor': {
    '__metadata': {
      'type': 'SP.Social.SocialActorInfo'
    },
    'AccountName': 'contoso.com\\evacorets',
    'ActorType': 0,
    'ContentUri': 'http://my.contoso.com/evacorets',
    'Id': null,
    'TagGuid': 'ff24780e-a35c-4d31-ae52-54afbb49ec6c'
  }
}
```

#### 3.1.5.32.2.1.2 Followed

**Return Type:** Microsoft.SharePoint.Client.Social.SocialActor[]

The **Followed** method retrieves a list of actors being followed by the current user.

**Parameters:**

*types*: The actor types to retrieve.

Type: Microsoft.SharePoint.Client.Social.SocialActorTypes

For details on the section **SocialActorTypes** type, see section [3.1.5.4](#).

For example, the following REST HTTP\_GET message calls the **Followed** resource. This message has an entity body equal to the empty string ("").

`http://my.contoso.com/_api/social.following/my/Followed(types=1)`

### 3.1.5.32.2.1.3 FollowedCount

**Return Type:** CSOM Int32

The **FollowedCount** method retrieves a count of actors being followed by the current user.

**Parameters:**

*types:* The types of actors to include in the count.

Type: Microsoft.SharePoint.Client.Social.SocialActorTypes

For details on the section **SocialActorTypes** type, see section [3.1.5.4](#).

For example, the following REST HTTP\_GET message calls the **FollowedCount** resource. This message has an entity body equal to the empty string ("").

`http://my.contoso.com/_api/social.following/my/FollowedCount(types=1)`

### 3.1.5.32.2.1.4 Followers

**Return Type:** Microsoft.SharePoint.Client.Social.SocialActor[]

The **Followers** method retrieves the current user's list of followers. For details on the **SocialActor** type, see section [3.1.5.1](#).

For example, the following REST HTTP\_GET message calls the **Followers** resource. This message has an entity body equal to the empty string ("").

`http://my.contoso.com/_api/social.following/my/Followers`

**Parameters:** None

### 3.1.5.32.2.1.5 IsFollowed

**Return Type:** CSOM Boolean

The **IsFollowed** method determines whether the current user is following the specified actor.

**Parameters:**

*actor:* An object that specifies the actor.

Type: Microsoft.SharePoint.Client.Social.SocialActorInfo

For details on the **SocialActorInfo** type, see section [3.1.5.2](#).

For example, the following REST HTTP\_POST message calls the **IsFollowed** resource.

`http://my.contoso.com/_api/social.following/IsFollowed`

The following is an example of the entity body for this message:

```
{
  'actor':{
    '_metadata':{
      'type':'SP.Social.SocialActorInfo'
    },
    'AccountName':contoso.com\\evacorets',
    'ActorType':0,
    'ContentUri':'http://my.contoso.com/',
    'Id':null,
    'TagGuid':'ff24780e-a35c-4d31-ae52-54afbb49ec6c'
  }
}
```

### 3.1.5.32.2.1.6 StopFollowing

**Return Type:** None

The **StopFollowing** method removes the specified actor from the current user's list of followed actors.

**Parameters:**

*actor*: An object that specifies the actor to be removed.

Type: Microsoft.SharePoint.Client.Social.SocialActorInfo

For details on the **SocialActorInfo** type, see section [3.1.5.2](#).

For example, the following REST HTTP\_POST message calls the **StopFollowing** resource.

```
http://my.contoso.com/_api/social.following/StopFollowing
```

The following is an example of the entity body for this message:

```
{
  'actor':{
    '_metadata':{
      'type':'SP.Social.SocialActorInfo'
    },
    'AccountName':'contoso.com\\evacorets',
    'ActorType':0,
    'ContentUri': 'http://my.contoso.com/',
    'Id':null,
    'TagGuid':'ff24780e-a35c-4d31-ae52-54afbb49ec6c'
  }
}
```

### 3.1.5.32.2.1.7 Suggestions

**Return Type:** Microsoft.SharePoint.Client.Social.SocialActor[]



The **Suggestions** method retrieves a list of suggested actors for the current user to follow. For details on the **SocialActor** type, see section [3.1.5.1](#).

For example, the following REST HTTP\_GET message calls the **Suggestions** resource. This message has an entity body equal to the empty string ("").

```
http://my.contoso.com/_api/social.following/my/Suggestions
```

**Parameters:** None

### 3.1.5.32.2.2 ObjectPath Methods

#### 3.1.5.32.2.2.1 CSOM Constructor

The constructor method creates a new instance of **SocialRestFollowingManager** (see section [3.1.5.32](#)).

For example, the following REST HTTP\_GET message calls the **SocialRestFollowingManager** resource. This message has an entity body equal to the empty string ("").

```
http://my.contoso.com/_api/social.feed
```

**Parameters:** None

#### 3.1.5.32.2.2.2 my

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestFollowingManager

The **my** property contains the **SocialActor** class for the current user.

For example, the following REST HTTP\_GET message calls the **my** resource. This message has an entity body equal to the empty string ("").

```
http://my.contoso.com/_api/social.following/my
```

**Parameters:** None

### 3.1.5.33 Microsoft.SharePoint.Client.Social.SocialRestPostCreationData

**TypeId:** {330A9A57-2B1E-499D-B5DB-93953C5C5001}

**ShortName:** SP.Social.SocialRestPostCreationData

The **SocialRestPostCreationData** class defines the content of a new post. The **SocialRestPostCreationData** type is available when the protocol client sends an **OData** request to a protocol server using [\[MS-CSOMREST\]](#). It is not available using [\[MS-CSOM\]](#).

### 3.1.5.33.1 Properties

#### 3.1.5.33.1.1 Scalar Properties

##### 3.1.5.33.1.1.1 creationData

**Type:** Microsoft.SharePoint.Client.Social.SocialPostCreationData

**Accessibility:** Read/Write

The **creationData** property specifies the content of the post. See section [3.1.5.23](#) for details on the **SocialPostCreationData** type.

##### 3.1.5.33.1.1.2 ID

**Type:** CSOM String

**Accessibility:** Read/Write

The **ID** property specifies the target thread for a response post or the target feed by the actor identification for a new root post. If the **ID** property is null, then the target is the current user's feed.

#### 3.1.5.33.1.2 ObjectPath Properties

None.

### 3.1.5.34 Microsoft.SharePoint.Client.Social.SocialRestThread

**TypeId:** {10237333-95CE-447D-80F0-2025548F7DA5}

**ShortName:** SP.Social.SocialRestThread

The **SocialRestThread** class specifies a thread that is stored on the server. The thread contains a root post and zero or more reply posts. The **SocialRestThread** type is available when the protocol client sends an **OData** request to a protocol server using [\[MS-CSOMREST\]](#). It is not available using [\[MS-CSOM\]](#).

### 3.1.5.34.1 Properties

#### 3.1.5.34.1.1 Scalar Properties

##### 3.1.5.34.1.1.1 ID

**Type:** CSOM String

**Accessibility:** Read Only

The **ID** property returns the thread identifier.

##### 3.1.5.34.1.1.2 SocialThread

**Type:** Microsoft.SharePoint.Client.Social.SocialThread

**Accessibility:** Read Only

The **SocialThread** property provides the object that contains the thread. For details on the **SocialThread** type, see section [3.1.5.35](#).

### 3.1.5.34.1.2 ObjectPath Properties

None.

### 3.1.5.34.2 Methods

#### 3.1.5.34.2.1 Scalar Methods

##### 3.1.5.34.2.1.1 Delete

**Return Type:** None

The **Delete** method deletes the specified post, either the root post or a reply post in the thread. If the root post is deleted, the entire thread is deleted.

**Parameters:**

*ID*: Specifies the post to delete.

Type: CSOM String

For example, the following REST HTTP\_POST message calls the **Delete** resource.

```
http://my.contoso.com/_api/social.feed/post/Delete
```

The following is an example of the entity body for this message:

```
{
  'ID': '1.94fdcc5fc39b4a2c99ae4570caf02321.d0a03fb1761a404a9a8e7f9f5ec58e17.5a1067e8af65410b9e2ba6a74a4b718a.0c37852b34d0418e91c62ac25af4be5b.9dbfb5598e2248d7b57eee57abf2e7c1.31.31.S-1-5-21-124525095-708259637-1543119021-565461'
}
```

##### 3.1.5.34.2.1.2 Likers

**Return Type:** Microsoft.SharePoint.Client.Social.SocialActor[]

The **Likers** method returns the complete set of users who like the specified post. Each **SocialActor** in the returned array identifies a user who likes the specified post. For details on the **SocialActor** type, see section [3.1.5.1](#).

**Parameters:**

*ID*: Specifies the post by its identifier.

Type: CSOM String

For example, the following REST HTTP\_POST message calls the **Likers** resource.

```
http://my.contoso.com/_api/social.feed/post/Likers
```

The following is an example of the entity body for this message:

```
{
  'ID': '1.94fdcc5fc39b4a2c99ae4570caf02321.d0a03fb1761a404a9a8e7f9f5ec58e17.5a1067e8af65410b9e2
ba6a74a4b718a.0c37852b34d0418e91c62ac25af4be5b.9dbfb5598e2248d7b57eee57abf2e7c1.31.31.S-1-5-
21-124525095-708259637-1543119021-565461'
}
```

### 3.1.5.34.2.2 ObjectPath Methods

#### 3.1.5.34.2.2.1 CSOM Constructor

The constructor method creates a new instance of **SocialRestThread** (see section [3.1.5.34](#)).

**Parameters:** None

#### 3.1.5.34.2.2.2 Like

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestThread

The **Like** method makes the current user a liker of the specified post. The method returns a thread digest of the thread containing the specified post. See section [3.1.5.34](#) for details on the **SocialRestThread** type.

**Parameters:**

*ID:* Specifies the post by its identifier.

Type: CSOM String

For example, the following REST HTTP\_POST message calls the **Like** resource.

```
http://my.contoso.com/_api/social.feed/post/Like
```

The following is an example of the entity body for this message:

```
{
  'ID': '1.94fdcc5fc39b4a2c99ae4570caf02321.d0a03fb1761a404a9a8e7f9f5ec58e17.5a1067e8af65410b9e2
ba6a74a4b718a.0c37852b34d0418e91c62ac25af4be5b.9dbfb5598e2248d7b57eee57abf2e7c1.31.31.S-1-5-
21-124525095-708259637-1543119021-565461'
}
```

#### 3.1.5.34.2.2.3 Lock

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestThread

The **Lock** method locks the specified thread. Once the thread is locked, no reply posts can be added to the thread until it is unlocked. The Lock method returns a digest of the locked thread. For details on the **SocialRestThread** type, see section [3.1.5.34](#).

**Parameters:**

*ID:* Specifies the thread by its identifier, which is the identifier of the root post.

Type: CSOM String

For example, the following REST HTTP\_POST message calls the **Lock** resource.

```
http://my.contoso.com/_api/social.feed/post/Lock
```

The following is an example of the entity body for this message:

```
{
  'ID': '1.94fdcc5fc39b4a2c99ae4570caf02321.d0a03fb1761a404a9a8e7f9f5ec58e17.5a1067e8af65410b9e2
ba6a74a4b718a.0c37852b34d0418e91c62ac25af4be5b.9dbfb5598e2248d7b57eee57abf2e7c1.31.31.S-1-5-
21-124525095-708259637-1543119021-565461'
}
```

#### 3.1.5.34.2.2.4 Reply

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestThread

The **Reply** method posts a reply to the specified root post. This method returns a digest thread. See section [3.1.5.34](#) for details on the **SocialRestThread** type.

**Parameters:**

*restCreationData*: Specifies the root post by identifier and specifies the content of the reply.

Type: Microsoft.SharePoint.Client.Social.SocialRestPostCreationData

See section [3.1.5.33](#) for details on the **SocialRestPostCreationData** type.

For example, the following REST HTTP\_POST message calls the **Reply** resource.

```
http://my.contoso.com/my/_api/social.feed/post/Reply
```

The following is an example of the entity body for this message:

```
{
  'restCreationData': { '__metadata': { 'type': 'SP.Social.SocialRestPostCreationData' },
  'ID': '1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814
c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-
5-21-124525095-708259637-1543119021-565461', 'creationData': { '__metadata': {
  'type': 'SP.Social.SocialPostCreationData' }, 'ContentText': 'This is my first
reply', 'UpdateStatusText': false } }
}
```

#### 3.1.5.34.2.2.5 Unlike

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestThread

The **Unlike** method removes the current user from the list of likers for the specified post. If the current is not a liker of the post, this method has no effect. This method returns a digest thread of the modified thread that includes the specified post. See section [3.1.5.34](#) for details on the **SocialRestThread** type.

**Parameters:**

*ID*: Specifies the post by identifier to unlike.

Type: CSOM String

For example, the following REST HTTP\_POST message calls the **Unlike** resource.

```
http://my.contoso.com/_api/social.feed/post/Unlike
```

The following is an example of the entity body for this message:

```
{
  'ID': '1.94fdcc5fc39b4a2c99ae4570caf02321.d0a03fb1761a404a9a8e7f9f5ec58e17.5a1067e8af65410b9e2
ba6a74a4b718a.0c37852b34d0418e91c62ac25af4be5b.9dbfb5598e2248d7b57eee57abf2e7c1.31.31.S-1-5-
21-124525095-708259637-1543119021-565461'
}
```

### 3.1.5.34.2.2.6 UnLock

**Return Type:** Microsoft.SharePoint.Client.Social.SocialRestThread

The **Unlock** method unlocks the specified thread. This method returns a digest of the locked thread. For details on the **SocialRestThread** type, see section [3.1.5.34](#).

**Parameters:**

*ID*: Specifies the thread by its identifier, which is the identifier of the root post.

Type: CSOM String

For example, the following REST HTTP\_POST message calls the **Unlock** resource.

```
http://my.contoso.com/_api/social.feed/post/Unlock
```

The following is an example of the entity body for this message:

```
{
  'ID': '1.94fdcc5fc39b4a2c99ae4570caf02321.d0a03fb1761a404a9a8e7f9f5ec58e17.5a1067e8af65410b9e2
ba6a74a4b718a.0c37852b34d0418e91c62ac25af4be5b.9dbfb5598e2248d7b57eee57abf2e7c1.31.31.S-1-5-
21-124525095-708259637-1543119021-565461'
}
```

### 3.1.5.35 Microsoft.SharePoint.Client.Social.SocialThread

**TypeId:** {2219E58B-DDDF-4D04-8F7B-171151704CC1}

**ShortName:** SP.Social.SocialThread

The **SocialThread** class specifies a thread that is stored on the server. The thread contains a root post and zero or more reply posts.

### 3.1.5.35.1 Properties

#### 3.1.5.35.1.1 Scalar Properties

##### 3.1.5.35.1.1.1 Actors

**Type:** Microsoft.SharePoint.Client.Social.SocialActor[]

**Accessibility:** Read Only

The **Actors** property is an array that specifies the users who have created a post in the returned thread and also contains any users, documents, sites, and tags that are referenced in any of the posts in the returned thread. For details on the **SocialActor** type, see section [3.1.5.1](#).

##### 3.1.5.35.1.1.2 Attributes

**Type:** Microsoft.SharePoint.Client.Social.SocialThreadAttributes

**Accessibility:** Read Only

The **Attributes** property specifies attributes of the thread, such as whether the current user can reply or lock the thread and whether the thread is a digest of a thread on the server, whether the number of replies has reached the maximum, and whether the thread is locked. See section [3.1.5.36](#) for details on the **SocialThreadAttributes** type.

##### 3.1.5.35.1.1.3 Id

**Type:** CSOM String

**Accessibility:** Read Only

The **Id** property specifies the unique identification of the thread.

##### 3.1.5.35.1.1.4 OwnerIndex

**Type:** CSOM Int32

**Accessibility:** Read Only

The **OwnerIndex** property specifies the thread owner as an index into the **Actors** array. Typically, the thread owner is the user who created the root post, but the thread owner can be any user included in the **Actors** array.

##### 3.1.5.35.1.1.5 Permalink

**Type:** CSOM String

**Accessibility:** Read Only

The **Permalink** property specifies a URI that is a permanent reference to the thread, if such a permanent reference is available.

##### 3.1.5.35.1.1.6 PostReference

**Type:** Microsoft.SharePoint.Client.Social.SocialPostReference

**Accessibility:** Read Only

The **PostReference** property specifies a reference to a post in another thread. The **PostReference** property is available only if the **ThreadType** (see section [3.1.5.35.1.1.10](#)) has a value of **ReplyReference**, **LikeReference**, **MentionReference**, or **TagReference**. See section [3.1.5.27](#) for details on the **SocialPostReference** type.

### 3.1.5.35.1.1.7 Replies

**Type:** Microsoft.SharePoint.Client.Social.SocialPost[]

**Accessibility:** Read Only

The **Replies** property returns an array of zero or more reply posts. The server can return a subset of the reply posts that are stored on the server. See section [3.1.5.20](#) for details on the **SocialPost** type.

### 3.1.5.35.1.1.8 RootPost

**Type:** Microsoft.SharePoint.Client.Social.SocialPost

**Accessibility:** Read Only

The **RootPost** property returns the root post. See section [3.1.5.20](#) for details on the **SocialPost** type.

### 3.1.5.35.1.1.9 Status

**Type:** Microsoft.SharePoint.Client.Social.SocialThreadStatus

**Accessibility:** Read Only

The **Status** property provides information about conditions that were encountered retrieving the thread that did not prevent the operation from completing. See section [3.1.5.37](#) for details on the **SocialThreadStatus** type.

### 3.1.5.35.1.1.10 ThreadType

**Type:** Microsoft.SharePoint.Client.Social.SocialThreadType

**Accessibility:** Read Only

The **ThreadType** property specifies if the thread is a normal thread created by one or more **CreatePost** calls (see section [3.1.5.12.2.1.1](#)) or a reference post generated by the server when a user replies to a post, likes a post, or creates a post with a tag or mention. The **PostReference** property (see section [3.1.5.35.1.1.6](#)) contains a reference to the post that generated the reference.

### 3.1.5.35.1.1.11 TotalReplyCount

**Type:** CSOM Int32

**Accessibility:** Read Only

The **TotalReplyCount** property specifies that number of reply posts in the thread as stored on the server. The **Replies** property (see section [3.1.5.35.1.1.7](#)) can contain a subset of the reply posts.



### 3.1.5.35.1.2 ObjectPath Properties

None.

### 3.1.5.36 Microsoft.SharePoint.Client.Social.SocialThreadAttributes

**ShortName:** SP.Social.SocialThreadAttributes

**Flag:** true

The **SocialThreadAttributes** flag type specifies properties of the thread.

#### 3.1.5.36.1 Field Values

##### 3.1.5.36.1.1 None

**Value:** 0

The **None** value specifies no properties.

##### 3.1.5.36.1.2 IsDigest

**Value:** 1

If this flag is set, the thread is a digest thread. It can contain a subset<5> of the replies.

##### 3.1.5.36.1.3 CanReply

**Value:** 2

If this flag is set, the current user can reply to the posts in the thread.

##### 3.1.5.36.1.4 CanLock

**Value:** 4

If this flag is set, the current user can lock or unlock the thread.

##### 3.1.5.36.1.5 IsLocked

**Value:** 8

If this flag is set, the thread is locked and no replies can be added to the thread until the thread is unlocked.

##### 3.1.5.36.1.6 ReplyLimitReached

**Value:** 16

If this flag is set, the thread contains the maximum number of replies.

### 3.1.5.37 Microsoft.SharePoint.Client.Social.SocialThreadStatus

**ShortName:** SP.Social.SocialThreadStatus

**Flag:** false

The **SocialThreadStatus** type identifies recoverable error conditions that were encountered when retrieving the thread. Although the server encountered these conditions, it was able to recover and successfully return a thread.

### 3.1.5.37.1 Field Values

#### 3.1.5.37.1.1 OK

**Value:** 0

No errors were encountered while retrieving the thread.

### 3.1.5.38 Microsoft.SharePoint.Client.Social.SocialThreadType

**ShortName:** SP.Social.SocialThreadType

**Flag:** false

The **SocialThreadType** type identifies the kind of thread that is returned by the server in a feed. The thread can be a normal thread that was created by one or more **CreatePost** calls (see section [3.1.5.12.2.1.1](#)) or it can be a reference thread that was created on the server. Reference threads are created to provide information when another user likes a post, replies to a post, mentions a user, or creates a post containing a tag.

### 3.1.5.38.1 Field Values

#### 3.1.5.38.1.1 Normal

**Value:** 0

The thread consists of a root post and zero or more reply posts.

#### 3.1.5.38.1.2 LikeReference

**Value:** 1

The thread indicates that a user liked a post. The thread contains a reference to the liked post.

#### 3.1.5.38.1.3 ReplyReference

**Value:** 2

The thread indicates that a user replied to a post. The thread contains a reference to the reply.

#### 3.1.5.38.1.4 MentionReference

**Value:** 3

The thread indicates that a user created a post that mentioned a user. The thread contains a reference to the post.

#### 3.1.5.38.1.5 TagReference

**Value:** 4

The thread indicates that a user created a post with a tag. The thread contains a reference to the post.

### 3.1.5.39 Microsoft.SharePoint.Client.UserProfiles.ChangeTypes

**ShortName:** SP.UserProfiles.ChangeTypes

**Flag:** true

The **ChangeTypes** class indicates the type of change made on the object.

#### 3.1.5.39.1 Field Values

##### 3.1.5.39.1.1 None

**Value:** 0

This value indicates that no change was made to an object in the user profile store.

##### 3.1.5.39.1.2 Add

**Value:** 1

This value indicates that an object was added to the user profile store.

##### 3.1.5.39.1.3 Modify

**Value:** 2

This value indicates that an object was modified in the user profile store.

##### 3.1.5.39.1.4 Remove

**Value:** 4

This value indicates that an object was deleted from the user profile store.

##### 3.1.5.39.1.5 Metadata

**Value:** 8

This value indicates that the metadata of an object was modified in the user profile store.

##### 3.1.5.39.1.6 All

**Value:** 15

This value indicates that multiple operations were performed on an object in the user profile store.

### 3.1.5.40 Microsoft.SharePoint.Client.UserProfiles.FollowedContent

**TypeId:** {D4B5E80E-3C1B-4153-A37F-BEF19B3BA1BB}

**ShortName:** SP.UserProfiles.FollowedContent

The **FollowedContent** class provides access to followed content items.

### 3.1.5.40.1 Properties

#### 3.1.5.40.1.1 Scalar Properties

##### 3.1.5.40.1.1.1 FollowedDocumentsUrl

**Type:** CSOM String

**Accessibility:** Read Only

The **FollowedDocumentsUrl** property gets the location of the followed documents view.

##### 3.1.5.40.1.1.2 FollowedSitesUrl

**Type:** CSOM String

**Accessibility:** Read Only

The **FollowedSitesUrl** property gets the location of the followed sites view.

#### 3.1.5.40.1.2 ObjectPath Properties

None.

### 3.1.5.40.2 Methods

#### 3.1.5.40.2.1 Scalar Methods

##### 3.1.5.40.2.1.1 FindAndUpdateFollowedItem

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.FollowedItem

The **FindAndUpdateFollowedItem** method finds the original item that is being pointed to in the Followed Content list and updates the **Title**, **Url**, and **IconUrl** fields if they have been changed.

**Parameters:**

*url*: The URL of the original item as stored in the Followed Content list.

Type: CSOM String

##### 3.1.5.40.2.1.2 Follow

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.FollowResult

The **Follow** method adds the specified document or site to the list of followed content. The *url* parameter can identify an existing document or site using the *url* property of the original item. The *url* parameter can also identify a document with the following format:

```
http://host/site?listId=listid&itemId=itemid
```

where *listid* is the parent list identifier and *itemid* is the item identifier.

See section [3.1.5.43](#) for details on **FollowedItem** type.

**Parameters:**

*url*: URL that identifies the item to follow.

Type: CSOM String

*data*: Optional parameter that holds application-defined data for the item.

Type: Microsoft.SharePoint.Client.UserProfiles.FollowedItemData

See section [3.1.5.44](#) for details on **FollowedItemData** type.

**3.1.5.40.2.1.3 GetFollowedStatus**

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.FollowedStatus

The **GetFollowedStatus** method retrieves the followed status of the specified document or site. See **Follow** method in section [3.1.5.40.2.1.2](#) for the description of the *url* parameter. An item can be followed if the *url* parameter identifies a document or site that the current user has access to. See section [3.1.5.48](#) for details on the **FollowedStatus** type.

**Parameters:**

*url*: URL that identifies the item.

Type: CSOM String

**3.1.5.40.2.1.4 IsFollowed**

**Return Type:** CSOM Boolean

The **IsFollowed** method determines if the specified document or site is being followed. See **Follow** method in section [3.1.5.40.2.1.2](#) for the description of the *url* parameter.

**Parameters:**

*url*: URL that identifies the item.

Type: CSOM String

**3.1.5.40.2.1.5 StopFollowing**

**Return Type:** None

The **StopFollowing** method removes the specified document or site from list of followed content. See **Follow** method in section [3.1.5.40.2.1.2](#) for the description of the *url* parameter.

**Parameters:**

*url*: URL that identifies the item to stop following.

Type: CSOM String

**3.1.5.40.2.1.6 UpdateData**

**Return Type:** None

The **UpdateData** method updates the properties for followed item with specified URL. See **Follow** method in section [3.1.5.40.2.1.2](#) for the description of the *url* parameter.

**Parameters:**

*url*: URL for the item to update.

Type: CSOM String

*data*: Application-defined data stored with the followed item.

Type: Microsoft.SharePoint.Client.UserProfiles.FollowedItemData

See section [3.1.5.44](#) for details on the **FollowedItemData** type.

### 3.1.5.40.2.1.7 FollowItem

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.FollowResult

The **FollowItem** method is reserved for server-to-server use only. The server sets the specified item to be followed by the current user. This method cannot be called from the client.

**Parameters:**

*item*: Identifies the item to follow.

Type: Microsoft.SharePoint.Client.UserProfiles.FollowedItem

See section [3.1.5.43](#) for details on **FollowedItem** type.

### 3.1.5.40.2.1.8 GetItem

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.FollowedItem

The **GetItem** method returns the followed item identified by a given URL or returns null if the item does not exist. See the **Follow** method in section [3.1.5.40.2.1.2](#) for the description of the *url* parameter.

**Parameters:**

*url*: URL that identifies the item to get.

Type: CSOM String

### 3.1.5.40.2.1.9 GetItems

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.FollowedItem[]

The **GetItems** method returns an array of zero or more followed items described by the *type* and *subtype* parameters. *subtype* is only valid for **FollowedItemType.Document** and should be -1 for other types. See section [3.1.5.43](#) for details on the **FollowedItem** type.

**Parameters:**

*options*: Describes the type of item to return.

Type: Microsoft.SharePoint.Client.UserProfiles.FollowedContentQueryOptions

See section [3.1.5.45](#) for details on the **FollowedItemType** type.

*subtype*: Integer that identifies the sites to return by the web template.

Type: CSOM Int32

### 3.1.5.40.2.1.10 RefreshFollowedItem

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.FollowedItem

The **RefreshFollowedItem** method returns the refreshed item that is being pointed to in the **Social** list. See section [3.1.5.43](#) for details on the **FollowedItem** type.

**Parameters:**

*item*: The original item as stored in the Followed Content list.

Type: Microsoft.SharePoint.Client.UserProfiles.FollowedItem

See section [3.1.5.43](#) for details on the **FollowedItem** type.

### 3.1.5.40.2.2 ObjectPath Methods

#### 3.1.5.40.2.2.1 CSOM Constructor

The constructor method initializes a new instance of a **FollowedContent** object (see section [3.1.5.40](#)).

**Parameters:** None

### 3.1.5.41 Microsoft.SharePoint.Client.UserProfiles.FollowedContentExceptionCode

**ShortName:** SP.UserProfiles.FollowedContentExceptionCode

**Flag:** false

The **FollowedContentExceptionCode** class represents an exception code that is used by the **FollowedContent** class (see section [3.1.5.40](#)) to specify a reason for the error.

#### 3.1.5.41.1 Field Values

##### 3.1.5.41.1.1 ItemAlreadyExists

**Value:** 3

The **ItemAlreadyExists** value specifies that the item is already followed and cannot be added to the followed list.

##### 3.1.5.41.1.2 ItemDoesNotExist

**Value:** 4

The **ItemDoesNotExist** value specifies that the item does not exist or is not currently followed.

### 3.1.5.41.1.3 InvalidQueryString

**Value:** 5

The **InvalidQueryString** value specifies that an invalid query string was provided.

### 3.1.5.41.1.4 InvalidSubtypeValue

**Value:** 6

The **InvalidSubtypeValue** value specifies that an invalid subtype value was provided.

### 3.1.5.41.1.5 UnsupportedItemType

**Value:** 7

The **UnsupportedItemType** value specifies that the item is not supported.

### 3.1.5.41.1.6 FollowLimitReached

**Value:** 8

The **FollowLimitReached** value specifies that the user has reached their maximum number of followed items for the item type.

### 3.1.5.41.1.7 UntrustedSource

**Value:** 9

The **UntrustedSource** value specifies that a protected server-to-server API was called from a non-server context (that is, a client application).

### 3.1.5.41.1.8 InternalError

**Value:** 11

The **InternalError** value specifies that an internal error occurred.

### 3.1.5.41.1.9 UnsupportedSite

**Value:** 10

The **UnsupportedSite** value specifies that the site cannot be followed. For example, personal sites cannot be followed.

## 3.1.5.42 Microsoft.SharePoint.Client.UserProfiles.FollowedContentQueryOptions

**ShortName:** SP.UserProfiles.FollowedContentQueryOptions

**Flag:** false

The flag **FollowedContentQueryOptions** type specifies the query options.



### 3.1.5.42.1 Field Values

#### 3.1.5.42.1.1 Unset

**Value:** 0

This value specifies that no query options are specified.

#### 3.1.5.42.1.2 Sites

**Value:** 1

This value specifies that the query should include sites.

#### 3.1.5.42.1.3 Documents

**Value:** 2

This value specifies that the query should include documents.

#### 3.1.5.42.1.4 Hidden

**Value:** 4

This value specifies that the query should include hidden items.

#### 3.1.5.42.1.5 NonFeed

**Value:** 8

This value specifies that the query should include items that do not have feeds.

#### 3.1.5.42.1.6 DefaultOptions

**Value:** 15

This value specifies the default option values.

#### 3.1.5.42.1.7 All

**Value:** 255

This value specifies all options.

### 3.1.5.43 Microsoft.SharePoint.Client.UserProfiles.FollowedItem

**TypeId:** {EE324D8C-2232-4163-BBA5-38138A571CA7}

**ShortName:** SP.UserProfiles.FollowedItem

The **FollowedItem** class represents a followed content resource.

### 3.1.5.43.1 Properties

#### 3.1.5.43.1.1 Scalar Properties

##### 3.1.5.43.1.1.1 Data

**Type:** CSOM dictionary

**Accessibility:** Read/Write

The **Data** property contains additional metadata associated with this item.

##### 3.1.5.43.1.1.2 Title

**Type:** CSOM String

**Accessibility:** Read/Write

The **Title** property contains the title of this item.

##### 3.1.5.43.1.1.3 Url

**Type:** CSOM String

**Accessibility:** Read/Write

The **Url** property contains the URL of this item.

##### 3.1.5.43.1.1.4 FileType

**Type:** CSOM String

**Accessibility:** Read/Write

The **FileType** property specifies the type of the file if this item is a file. Otherwise, this property is the empty string.

##### 3.1.5.43.1.1.5 Hidden

**Type:** CSOM Boolean

**Accessibility:** Read/Write

The **Hidden** property specifies if the item is hidden from the user. If true this item will not generate activity in the user's feed.

##### 3.1.5.43.1.1.6 IconUrl

**Type:** CSOM String

**Accessibility:** Read/Write

The **IconUrl** property specifies the URL of an icon to represent this item.

### 3.1.5.43.1.1.7 **ItemId**

**Type:** CSOM Int32

**Accessibility:** Read/Write

The **ItemId** property specifies the identification for this item in the Content database.

### 3.1.5.43.1.1.8 **ItemType**

**Type:** Microsoft.SharePoint.Client.UserProfiles.FollowedItemType

**Accessibility:** Read/Write

The **ItemType** property specifies the type of this item.

### 3.1.5.43.1.1.9 **ListId**

**Type:** CSOM GUID

**Accessibility:** Read/Write

The **ListId** property specifies the list identification for this item in the Content database if this item is a list or the list identification for its parent list. If the **ItemType** (see section [3.1.5.43.1.1.8](#)) is **Document**, this property is specified, but if the **ItemType** is **Site**, then this property is not specified.

### 3.1.5.43.1.1.10 **ParentUrl**

**Type:** CSOM String

**Accessibility:** Read/Write

The **ParentUrl** property specifies the URL of this item's parent list or web.

### 3.1.5.43.1.1.11 **SiteId**

**Type:** CSOM GUID

**Accessibility:** Read/Write

The **SiteId** property specifies the site identification in the Content database for this item if this item is a site, or for its parent site if this item is not a site.

### 3.1.5.43.1.1.12 **Subtype**

**Type:** CSOM Int32

**Accessibility:** Read/Write

The **Subtype** property specifies the subtype of this item. If the **ItemType** is **Site**, the **Subtype** specifies the web template identification. If the **ItemType** is **Document**, the **Subtype** has a value of 1.

### 3.1.5.43.1.1.13 **UniqueId**

**Type:** CSOM GUID

**Accessibility:** Read/Write

The **UniqueId** property specifies the GUID for this item in the Content database.

#### 3.1.5.43.1.1.14 **WebId**

**Type:** CSOM GUID

**Accessibility:** Read/Write

The **WebId** property specifies the site identification in the Content database for this item if it is a site, or the identification of its parent site if this item is a document.

#### 3.1.5.43.1.1.15 **Flags**

**Type:** CSOM String

**Accessibility:** Read/Write

The **Flags** property allows the client to specify additional information about the followed item. The server stores the data so that it can return it to the client.

#### 3.1.5.43.1.1.16 **HasFeed**

**Type:** CSOM Boolean

**Accessibility:** Read/Write

The **HasFeed** Boolean indicates whether the followed site has a feed.

#### 3.1.5.43.1.1.17 **FileTypeProgid**

**Type:** CSOM String

**Accessibility:** Read/Write

The **FileTypeProgid** property provides information about the application that opens a followed document.

#### 3.1.5.43.1.1.18 **ServerUrlProgid**

**Type:** CSOM String

**Accessibility:** Read/Write

The **ServerUrlProgid** property provides information about the followed document to the application that opens it.

#### 3.1.5.43.1.2 **ObjectPath Properties**

None.

#### 3.1.5.44 **Microsoft.SharePoint.Client.UserProfiles.FollowedItemData**

**TypeId:** {BFC2A2AC-07CD-4D35-AAE1-9BC7D41DA9CE}

**ShortName:** SP.UserProfiles.FollowedItemData

The **FollowedItemData** class contains additional data that can be attached to a **FollowedItem** (see section [3.1.5.43](#)).

### 3.1.5.44.1 Properties

#### 3.1.5.44.1.1 Scalar Properties

##### 3.1.5.44.1.1.1 Properties

**Type:** CSOM dictionary

**Accessibility:** Read Only

The **Properties** property is an unordered collection of key/value pairs for custom properties to be set on the item.

#### 3.1.5.44.1.2 ObjectPath Properties

None.

#### 3.1.5.44.2 Methods

##### 3.1.5.44.2.1 Scalar Methods

None.

##### 3.1.5.44.2.2 ObjectPath Methods

###### 3.1.5.44.2.2.1 CSOM Constructor

The constructor method initializes a new instance of **FollowedItemData** (see section [3.1.5.44](#)).

**Parameters:**

*props*: Specifies an unordered collection of key/value pairs for custom properties to be set on the item.

Type: CSOM dictionary

### 3.1.5.45 Microsoft.SharePoint.Client.UserProfiles.FollowedItemType

**ShortName:** SP.UserProfiles.FollowedItemType

**Flag:** false

The **FollowedItemType** type represents the type of a followable content resource.

#### 3.1.5.45.1 Field Values

##### 3.1.5.45.1.1 Unknown

**Value:** 0

This value is not used.

### 3.1.5.45.1.2 Document

**Value:** 1

The followed item is a document.

### 3.1.5.45.1.3 Site

**Value:** 2

The followed item is a site.

### 3.1.5.45.1.4 All

**Value:** 3

The followed item can be any type. This value is used only in queries.

## 3.1.5.46 Microsoft.SharePoint.Client.UserProfiles.FollowResult

**TypeId:** {39498102-06DB-49BC-9DF7-D8E91AD10ADF}

**ShortName:** SP.UserProfiles.FollowResult

The **FollowResult** class returns information about a request to follow an item.

### 3.1.5.46.1 Properties

#### 3.1.5.46.1.1 Scalar Properties

##### 3.1.5.46.1.1.1 Item

**Type:** Microsoft.SharePoint.Client.UserProfiles.FollowedItem

**Accessibility:** Read/Write

The **Item** property contains the item being followed.

##### 3.1.5.46.1.1.2 ResultType

**Type:** Microsoft.SharePoint.Client.UserProfiles.FollowResultType

**Accessibility:** Read/Write

The **ResultType** property provides information about the attempt to follow an item. For details on the **FollowResultType** type, see section [3.1.5.47](#).

##### 3.1.5.46.1.2 ObjectPath Properties

None.

## 3.1.5.47 Microsoft.SharePoint.Client.UserProfiles.FollowResultType

**ShortName:** SP.UserProfiles.FollowResultType

**Flag:** false

The **FollowResultType** type specifies the result of a request to follow an item.

### 3.1.5.47.1 Field Values

#### 3.1.5.47.1.1 Unknown

**Value:** 0

The result is unknown.

#### 3.1.5.47.1.2 Followed

**Value:** 1

The request succeeded and the item is being followed.

#### 3.1.5.47.1.3 Refollowed

**Value:** 2

The item was already being followed by the current user so there is no change in status.

#### 3.1.5.47.1.4 HitFollowLimit

**Value:** 3

The request encountered the maximum follow limit.

#### 3.1.5.47.1.5 Failed

**Value:** 4

The request failed.

### 3.1.5.48 Microsoft.SharePoint.Client.UserProfiles.FollowedStatus

**ShortName:** SP.UserProfiles.FollowedStatus

**Flag:** false

The **FollowedStatus** type represents the followed status of a content resource.

#### 3.1.5.48.1 Field Values

##### 3.1.5.48.1.1 Followed

**Value:** 0

The item is followed.

##### 3.1.5.48.1.2 NotFollowed

**Value:** 1

The item is not followed.

### **3.1.5.48.1.3 NotFollowable**

**Value:** 2

The item cannot be followed.

### **3.1.5.49 Microsoft.SharePoint.Client.UserProfiles.ObjectTypes**

**ShortName:** SP.UserProfiles.ObjectTypes

**Flag:** true

Specifies the type of object represented.

#### **3.1.5.49.1 Field Values**

##### **3.1.5.49.1.1 None**

**Value:** 0

No object type has been specified.

##### **3.1.5.49.1.2 SingleValueProperty**

**Value:** 1

The type of object is a single value property.

##### **3.1.5.49.1.3 MultiValueProperty**

**Value:** 2

The type of object is a multiple value property.

##### **3.1.5.49.1.4 Anniversary**

**Value:** 4

The type of object is an anniversary.

##### **3.1.5.49.1.5 DLMembership**

**Value:** 8

The type of object is a distribution list (DL) membership.

##### **3.1.5.49.1.6 SiteMembership**

**Value:** 16

The type of object is a site membership.

##### **3.1.5.49.1.7 QuickLink**

**Value:** 32



The type of object is a quick link.

#### **3.1.5.49.1.8 Colleague**

**Value:** 64

The type of object is a colleague.

#### **3.1.5.49.1.9 PersonalizationSite**

**Value:** 128

The type of object is a personalization site.

#### **3.1.5.49.1.10 UserProfile**

**Value:** 256

The type of object is a profile of a user.

#### **3.1.5.49.1.11 WebLog**

**Value:** 512

The type of object is a Web log.

#### **3.1.5.49.1.12 Custom**

**Value:** 1024

The type of object is custom.

#### **3.1.5.49.1.13 OrganizationProfile**

**Value:** 2048

The type of the object is a profile of an organization.

#### **3.1.5.49.1.14 OrganizationMembership**

**Value:** 4096

The type of the object is an organization membership.

#### **3.1.5.49.1.15 All**

**Value:** 8191

All types of objects.

### **3.1.5.50 Microsoft.SharePoint.Client.UserProfiles.PeopleManager**

**TypeId:** {CF560D69-0FDB-4489-A216-B6B47ADF8EF8}

**ShortName:** SP.UserProfiles.PeopleManager

The **PeopleManager** class is used for operations related to people.

### 3.1.5.50.1 Properties

#### 3.1.5.50.1.1 Scalar Properties

##### 3.1.5.50.1.1.1 EditProfileLink

**Type:** CSOM String

**Accessibility:** Read Only

The **EditProfileLink** property is the URL to the edit profile page.

##### 3.1.5.50.1.1.2 IsMyPeopleListPublic

**Type:** CSOM Boolean

**Accessibility:** Read Only

The **IsMyPeopleListPublic** property represents whether or not the people list is public.

#### 3.1.5.50.1.2 ObjectPath Properties

None.

### 3.1.5.50.2 Methods

#### 3.1.5.50.2.1 Scalar Methods

##### 3.1.5.50.2.1.1 AmIFollowedBy

**Return Type:** CSOM Boolean

The **AmIFollowedBy** method tests whether the given user is following the current user. This method can result in exceptions for conditions such as null arguments or if the specified user cannot be found.

**Parameters:**

*accountName*: Specifies the user by account name.

Type: CSOM String

##### 3.1.5.50.2.1.2 AmIFollowing

**Return Type:** CSOM Boolean

The **AmIFollowing** method tests whether the current user is following the given user. This method can result in exceptions for conditions such as null arguments or if the specified user cannot be found.

**Parameters:**

*accountName*: Specifies the user by account name. If the current user is following the specified user, the method returns true; otherwise, the method returns false.

Type: CSOM String

### 3.1.5.50.2.1.3 Follow

**Return Type:** None

The **Follow** method sets the current user to be following the specified user with default settings. This method can result in exceptions for conditions such as null arguments or if the specified user cannot be found.

**Parameters:**

*accountName*: Specifies the user by account name.

Type: CSOM String

### 3.1.5.50.2.1.4 HideSuggestion

**Return Type:** None

The **HideSuggestion** method adds the specified user to list of rejected suggestions.

**Parameters:**

*accountName*: Specifies the user by account name.

Type: CSOM String

### 3.1.5.50.2.1.5 IsFollowing

This method is a static CSOM method.

**Return Type:** CSOM Boolean

The **IsFollowing** method tests whether the first user is following the second user. This method can result in exceptions for conditions such as null arguments or if the specified user cannot be found.

**Parameters:**

*possibleFollowerAccountName*: Specifies the user by account name. This is the first user being tested if this user is following the second user.

Type: CSOM String

*possibleFolloweeAccountName*: Specifies the user by account name. This is the second user.

Type: CSOM String

### 3.1.5.50.2.1.6 StopFollowing

**Return Type:** None

The **StopFollowing** method sets the current user to no longer be following the specified user. This method can result in exceptions for conditions such as null arguments or if the specified user or specified privacy item cannot be found.

**Parameters:**

*accountName*: Specifies the user by account name.

Type: CSOM String

### 3.1.5.50.2.1.7 GetUserProfilePropertiesFor

**Return Type:** CSOM Array

The **GetUserProfilePropertiesFor** method returns the specified user profile properties for the specified user.

**Parameters:**

*propertiesForUser*: Specifies the user and the properties to get for that user. For details on the **UserProfilePropertiesForUser** type, see section [3.1.5.56](#).

Type: Microsoft.SharePoint.Client.UserProfiles.UserProfilePropertiesForUser

### 3.1.5.50.2.1.8 GetUserProfilePropertyFor

**Return Type:** CSOM String

The **GetUserProfilePropertyFor** method returns a string representation of a user profile property for the specified user.

**Parameters:**

*accountName*: Specifies the user by account name.

Type: CSOM String

*propertyName*: Specifies a property in the user profile.

Type: CSOM String

### 3.1.5.50.2.1.9 SetMyProfilePicture

**Return Type:** None

The **SetMyProfilePicture** method uploads and sets the user profile picture. Pictures in bmp, jpg and png formats and up to 5,000,000 bytes are supported. A user can upload a picture only to the user's own profile.

**Parameters:**

*picture*: Binary content of an image file

Type: CSOM Stream

### 3.1.5.50.2.1.10 FollowTag

**Return Type:** None

The **FollowTag** method sets the current user to be following the specified tag.

**Parameters:**

*value*: Specifies the tag by its GUID.

Type: CSOM GUID

### 3.1.5.50.2.1.11 StopFollowingTag

**Return Type:** None

The **StopFollowingTag** method sets the current user to no longer be following the specified tag.

**Parameters:**

*value:* Specifies the tag by its GUID.

Type: CSOM GUID

### 3.1.5.50.2.2 ObjectPath Methods

#### 3.1.5.50.2.2.1 GetMyProperties

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.PersonProperties

The **GetMyProperties** method gets the **PersonProperties** object corresponding to the current user. See section [3.1.5.52](#) for details on the **PersonProperties** type.

**Parameters:** None

#### 3.1.5.50.2.2.2 GetPropertiesFor

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.PersonProperties

The **GetPropertiesFor** method gets the **PersonProperties** object corresponding to the specified user. See section [3.1.5.52](#) for details on the **PersonProperties** type.

**Parameters:**

*accountName:* Specifies the user by account name.

Type: CSOM String

#### 3.1.5.50.2.2.3 CSOM Constructor

The constructor method initializes a new instance of **PeopleManager** (see section [3.1.5.50](#)).

**Parameters:** None

#### 3.1.5.50.2.2.4 GetFollowersFor

**Return Type:** CSOM Array

The **GetFollowersFor** method returns a list of **PersonProperties** objects for the people who are following the specified user. This method can result in exceptions for conditions such as null arguments or if the specified user cannot be found.

**Parameters:**

*accountName:* Specifies the user by account name.

Type: CSOM String

### 3.1.5.50.2.2.5 GetMyFollowers

**Return Type:** CSOM Array

This method returns a list of **PersonProperties** objects for the people who are following the current user.

**Parameters:** None

### 3.1.5.50.2.2.6 GetMySuggestions

**Return Type:** CSOM Array

The **GetMySuggestions** method returns a list of **PersonProperties** objects to suggest that the current user should follow. The objects to select for this set are not determined by this document. The server implementation can use any information accessible to the current user including the people that other users are following.

**Parameters:** None

### 3.1.5.50.2.2.7 GetPeopleFollowedBy

**Return Type:** CSOM Array

The **GetPeopleFollowedBy** method returns a list of **PersonProperties** objects for people who the specified user is following. This method can result in exceptions for conditions such as null arguments or if the specified user cannot be found.

**Parameters:**

*accountName*: Account name of the specified user.

Type: CSOM String

### 3.1.5.50.2.2.8 GetPeopleFollowedByMe

**Return Type:** CSOM Array

The **GetPeopleFollowedByMe** method returns a list of **PersonProperties** objects for people who the current user is following.

**Parameters:** None

### 3.1.5.51 Microsoft.SharePoint.Client.UserProfiles.PersonalSiteCapabilities

**ShortName:** SP.UserProfiles.PersonalSiteCapabilities

**Flag:** true

The **PersonalSiteCapabilities** enumeration specifies attributes that describe the state of a user's personal site.

### 3.1.5.51.1 Field Values

#### 3.1.5.51.1.1 Uninitialized

**Value:** -1

The site is uninitialized.

#### 3.1.5.51.1.2 None

**Value:** 0

This value does not define any attributes.

#### 3.1.5.51.1.3 Profile

**Value:** 1

The personal site specifies a user profile.

#### 3.1.5.51.1.4 Social

**Value:** 2

The personal site contains a feed with social posts.

#### 3.1.5.51.1.5 Storage

**Value:** 4

The personal site contains document storage.

#### 3.1.5.51.1.6 MyTasksDashboard

**Value:** 8

The personal site contains a task dashboard.

### 3.1.5.52 Microsoft.SharePoint.Client.UserProfiles.PersonProperties

**TypeId:** {9A467BF8-BBFB-4A76-9C41-0753ECF7218F}

**ShortName:** SP.UserProfiles.PersonProperties

The **PersonProperties** class contains the data about people and is returned by **PeopleManager** methods (see section [3.1.5.50](#)).

#### 3.1.5.52.1 Properties

##### 3.1.5.52.1.1 Scalar Properties

###### 3.1.5.52.1.1.1 AccountName

**Type:** CSOM String

**Accessibility:** Read Only

The **AccountName** property specifies the person's account name.

#### 3.1.5.52.1.1.2 DirectReports

**Type:** CSOM Array

**Accessibility:** Read Only

The **DirectReports** property specifies an array of strings containing the account names of a person's direct reports.

#### 3.1.5.52.1.1.3 DisplayName

**Type:** CSOM String

**Accessibility:** Read Only

The **DisplayName** property specifies the person's name.

#### 3.1.5.52.1.1.4 Email

**Type:** CSOM String

**Accessibility:** Read Only

The **Email** property specifies the person's email address.

#### 3.1.5.52.1.1.5 ExtendedManagers

**Type:** CSOM Array

**Accessibility:** Read Only

The **ExtendedManagers** property specifies an array of strings that specify the account names of a person's managers.

#### 3.1.5.52.1.1.6 ExtendedReports

**Type:** CSOM Array

**Accessibility:** Read Only

The **ExtendedReports** properties specifies an array of strings that specify the account names of person's extended reports.

#### 3.1.5.52.1.1.7 IsFollowed

**Type:** CSOM Boolean

**Accessibility:** Read Only

The **IsFollowed** property represents whether or not the current user is following this person. [<6>](#)



### 3.1.5.52.1.1.8 LatestPost

**Type:** CSOM String

**Accessibility:** Read Only

The **LatestPost** property specifies the person's latest microblog post.

### 3.1.5.52.1.1.9 Peers

**Type:** CSOM Array

**Accessibility:** Read Only

The **Peers** property specifies an array of strings that specify the account names of person's peers, that is, those who have the same manager.

### 3.1.5.52.1.1.10 PersonalUrl

**Type:** CSOM String

**Accessibility:** Read Only

The **PersonalUrl** property specifies the absolute URL of the person's personal page.

### 3.1.5.52.1.1.11 PictureUrl

**Type:** CSOM String

**Accessibility:** Read Only

The **PictureUrl** property specifies the URL for the person's profile picture.

### 3.1.5.52.1.1.12 Title

**Type:** CSOM String

**Accessibility:** Read Only

The **Title** property specifies the person's title.

### 3.1.5.52.1.1.13 UserUrl

**Type:** CSOM String

**Accessibility:** Read Only

The **UserUrl** property specifies the URL for the person's profile.

### 3.1.5.52.1.1.14 UserProfileProperties

**Type:** CSOM dictionary

**Accessibility:** Read Only

The **UserProfileProperties** property specifies the person's profile properties. The property returns a dictionary which is a set of keys and values, where both are provided as strings. The keys

represent property names and the values represent the property values. The privacy settings affect which properties can be retrieved. Multiple values are delimited by the vertical bar "|". Null values are specified as empty strings.

### 3.1.5.52.1.2 ObjectPath Properties

None.

### 3.1.5.52.2 Methods

#### 3.1.5.52.2.1 Scalar Methods

None.

#### 3.1.5.52.2.2 ObjectPath Methods

None.

### 3.1.5.53 Microsoft.SharePoint.Client.UserProfiles.ProfileLoader

**TypeId:** {9C42543A-91B3-4902-B2FE-14CCDEFB6E2B}

**ShortName:** SP.UserProfiles.ProfileLoader

The **ProfileLoader** class provides access to the current user's profile.

#### 3.1.5.53.1 Properties

##### 3.1.5.53.1.1 Scalar Properties

None.

##### 3.1.5.53.1.2 ObjectPath Properties

None.

#### 3.1.5.53.2 Methods

##### 3.1.5.53.2.1 Scalar Methods

None.

##### 3.1.5.53.2.2 ObjectPath Methods

###### 3.1.5.53.2.2.1 GetProfileLoader

This method is a static CSOM method.

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.ProfileLoader

The **GetProfileLoader** method returns a profile loader.

**Parameters:** None

### 3.1.5.53.2.2.2 GetUserProfile

**Return Type:** Microsoft.SharePoint.Client.UserProfiles.UserProfile

The **GetUserProfile** method returns the user profile for the current user.

**Parameters:** None

### 3.1.5.54 Microsoft.SharePoint.Client.UserProfiles.SocialDataStoreExceptionCode

**ShortName:** SP.UserProfiles.SocialDataStoreExceptionCode

**Flag:** false

The **SocialDataStoreExceptionCode** class represents an exception code for a user's Social data storage to specify a reason for an error.

#### 3.1.5.54.1 Field Values

##### 3.1.5.54.1.1 SocialListNotFound

**Value:** 0

The Social list storage on the user's My Site could not be accessed.

##### 3.1.5.54.1.2 PersonalSiteNotFound

**Value:** 1

The user does not have a personal site.

##### 3.1.5.54.1.3 CannotCreatePersonalSite

**Value:** 2

The user does not have a personal site, and does not have permission to create one.

### 3.1.5.55 Microsoft.SharePoint.Client.UserProfiles.UserProfile

**TypeId:** {A3B3B313-DF8C-4192-B623-57B8FA3872D9}

**ShortName:** SP.UserProfiles.UserProfile

The **UserProfile** class stores the profile of individual user, which includes properties such as the user's account name, preferred name, and email address.

#### 3.1.5.55.1 Properties

##### 3.1.5.55.1.1 Scalar Properties

###### 3.1.5.55.1.1.1 UrlToCreatePersonalSite

**Type:** CSOM String

**Accessibility:** Read Only

The **UrlToCreatePersonalSite** property specifies the URL to allow the current user to create a personal site.

### 3.1.5.55.1.1.2 PersonalSiteCapabilities

**Type:** Microsoft.SharePoint.Client.UserProfiles.PersonalSiteCapabilities

**Accessibility:** Read Only

The **PersonalSiteCapabilities** property specifies attributes of the user's personal site. See section [3.1.5.51](#) for details on the **PersonalSiteCapabilities** type.

### 3.1.5.55.1.1.3 PictureImportEnabled

**Type:** CSOM Boolean

**Accessibility:** Read Only

The **PictureImportEnabled** property specifies whether the user can import pictures.

### 3.1.5.55.1.2 ObjectPath Properties

#### 3.1.5.55.1.2.1 FollowedContent

**Type:** Microsoft.SharePoint.Client.UserProfiles.FollowedContent

**Accessibility:** Read Only

The **FollowedContent** property specifies the content that a user is following. See section [3.1.5.40](#) for details on the **FollowedContent** type.

#### 3.1.5.55.1.2.2 PersonalSite

**Type:** Microsoft.SharePoint.Client.Site

**Accessibility:** Read Only

The **PersonalSite** property specifies the user's personal site. For details on the **Site** type, see the description of **SPSite** in [\[MS-SITEDATS\]](#) section 3.1.4.3.2.8.

### 3.1.5.55.2 Methods

#### 3.1.5.55.2.1 Scalar Methods

##### 3.1.5.55.2.1.1 CreatePersonalSite

**Return Type:** None

The **CreatePersonalSite** method creates a personal site for this user, which can be used to share documents, web pages, and other files.

**Parameters:**

*lcid*: Specifies the locale identifier for the site.

Type: CSOM Int32

### 3.1.5.55.2.1.2 ShareAllSocialData

**Return Type:** None

The **ShareAllSocialData** method specifies whether the current user's social data is to be shared.

**Parameters:**

*shareAll*: If true, social data is shared; if false, social data is not shared.

Type: CSOM Boolean

### 3.1.5.55.2.2 ObjectPath Methods

None.

## 3.1.5.56 Microsoft.SharePoint.Client.UserProfiles.UserProfilePropertiesForUser

**TypeId:** {1ADD223C-FF83-471F-8E55-519FE8A0CA31}

**ShortName:** SP.UserProfiles.UserProfilePropertiesForUser

The **UserProfilePropertiesForUser** class represents a set of user profile properties for a user.

### 3.1.5.56.1 Properties

#### 3.1.5.56.1.1 Scalar Properties

##### 3.1.5.56.1.1.1 AccountName

**Type:** CSOM String

**Accessibility:** Read/Write

The **AccountName** property specifies the account name of the user.

#### 3.1.5.56.1.2 ObjectPath Properties

None.

### 3.1.5.56.2 Methods

#### 3.1.5.56.2.1 Scalar Methods

##### 3.1.5.56.2.1.1 GetPropertyNames

**Return Type:** CSOM Array

The **GetPropertyNames** method gets an array of strings that specify the user profile property names.

**Parameters:** None

### 3.1.5.56.2.2 ObjectPath Methods

#### 3.1.5.56.2.2.1 CSOM Constructor

The constructor method creates a new instance of **UserProfilePropertiesForUser** (see section [3.1.5.56](#)).

**Parameters:**

*accountName*: Specifies the user by account name.

Type: CSOM String

*propertyNames*: Specifies an array of strings that specify the properties to set.

Type: CSOM Array

### 3.1.5.57 Microsoft.Office.Server.ReputationModel.Reputation

**TypeId**: {D9C758A9-D32D-4C9C-AB60-46FD8B3C79B7}

**ShortName**: Microsoft.Office.Server.ReputationModel.Reputation

The **Reputation** static type includes methods to set the reputation properties on a **list item**.

#### 3.1.5.57.1 Properties

##### 3.1.5.57.1.1 Scalar Properties

None.

##### 3.1.5.57.1.2 ObjectPath Properties

None.

#### 3.1.5.57.2 Methods

##### 3.1.5.57.2.1 Scalar Methods

###### 3.1.5.57.2.1.1 SetLike

This method is a static CSOM method.

**Return Type**: CSOM Int32

The **SetLike** static method sets or unsets the like quality for the current user for an item within the specified **list (1)**. The return value is the total number of likes for the specified list item.

**Parameters:**

*listID*: A string-represented **GUID** value specifying the list (1) that the list item belongs to.

Type: CSOM String

*itemID*: An integer value that identifies a list item within the list (1) it belongs to.

Type: CSOM Int32

*like*: A **Boolean** value that indicates the operation being either like or unlike. A True value indicates like.

Type: CSOM Boolean

### 3.1.5.57.2.1.2 SetRating

This method is a static CSOM method.

**Return Type:** **CSOM Double**

The **SetRating** static method rates an item within the specified list. The return value is the average rating for the specified list item.

**Parameters:**

*listID*: A string-represented GUID value specifying the list (1) that the list item belongs to.

Type: CSOM String

*itemID*: An integer value that identifies a list item within the list (1) it belongs to.

Type: CSOM Int32

*rating*: An integer value for the rating to be submitted.

Type: CSOM Int32

The rating value SHOULD be between **1** and **5**; otherwise, the server SHOULD return an **SPEXception**.

### 3.1.5.57.2.2 ObjectPath Methods

None.

### 3.1.6 Timer Events

None

### 3.1.7 Other Local Events

None

## 4 Protocol Examples

### 4.1 Making a New Root Post

The following sample message from the client creates a new root post in the current user's feed.

```
POST http://my.contoso.com/_vti_bin/client.svc/ProcessQuery HTTP/1.1
Accept: */*
X-Requested-With: XMLHttpRequest
Content-Type: text/xml
X-RequestDigest:
0x8A23682F5FE3479666EEBB0546E1A5E22DDD21D8A587558D37CAC88897EA3BB0AC368E15BBBC9F5D48BC6FB9DCD
D611ADD264D9557C571F7BF03E336F90BD2AF,22 May 2012 12:38:53 -0000
Referer: http://my.contoso.com/default.aspx
Accept-Language: en-us
Accept-Encoding: gzip, deflate
User-Agent: Mozilla/4.0 (compatible; MSIE 7.0; Windows NT 6.1; WOW64; Trident/5.0; SLCC2;
.NET4.0C; .NET4.0E)
Host: social.contoso.com
Content-Length: 827
Connection: Keep-Alive
Pragma: no-cache
Cookie: WSS_FullScreenMode=false
Authorization: NTLM
TlRMTVNTUADAAAAAAAAAFgAAAAAAAAAWAAAAAAAAABYAAAAAAAAAFgAAAAAAAAWAAAAAAAAABYAAAAABcKIogYBsR0AA
AAPzICGUnyqRfwQC6pz9b3tlQ==

<Request
  xmlns="http://schemas.microsoft.com/sharepoint/clientquery/2009"
  SchemaVersion="15.0.0.0"
  LibraryVersion="15.0.0.0"
  ApplicationName="Javascript Library"
>
  <Actions>
    <Method Name="CreatePost" Id="11" ObjectPathId="0">
      <Parameters>
        <Parameter Type="String">
        </Parameter>
        <Parameter TypeId="{2830dd33-271e-4091-a211-e88988e16b03}">
          <Property Name="Attachment" Type="Null" />
          <Property Name="ContentItems" Type="Array" />
          <Property Name="ContentText" Type="String">Hello, world.</Property>
          <Property Name="DefinitionData" Type="Null" />
          <Property Name="SecurityUris" Type="Null" />
          <Property Name="Source" Type="Null" />
          <Property Name="UpdateStatusText" Type="Boolean">true</Property>
        </Parameter>
      </Parameters>
    </Method>
  </Actions>
  <ObjectPaths>
    <Constructor Id="0"
      TypeId="{c32f5230-2ed0-48fa-ac80-e2ffa22e3d28}"
    />
  </ObjectPaths>
</Request>
```



## 4.2 Response from Server for New Root Post

The following is the response from the server for a new root post after decompressing from the zip compressed message.

```
Content-Type: application/json; charset=utf-8
Vary: Accept-Encoding
Server: Microsoft-IIS/7.5
X-SharePointHealthScore: 0
X-AspNet-Version: 4.0.30319
X-RequestDigest:
0xAA80E9414B7363A72635FDA35C4494B7446C39756C1B95881BA26D7A09AB05D4DF3CC809AE34711004FB5A8BC45
7691ADBA5B8FC5702252A1FABA75055A6C222,22 May 2012 12:44:18 -0000
X-FRAME-OPTIONS: SAMEORIGIN
SPRequestGuid: 066ca89b-bcde-5026-2451-a625463ec85e
request-id: 066ca89b-bcde-5026-2451-a625463ec85e
Persistent-Auth: true
X-Powered-By: ASP.NET
MicrosoftSharePointTeamServices: 15.0.0.4118
X-Content-Type-Options: nosniff
X-MS-InvokeApp: 1; RequireReadOnly
Date: Tue, 22 May 2012 12:44:20 GMT
Content-Length: 2178
```

```
[
  {
    "SchemaVersion": "15.0.0.0",
    "LibraryVersion": "15.0.4118.3001",
    "ErrorInfo": null,
    "TraceCorrelationId": "066ca89b-bcde-5026-2451-a625463ec85e"
  },
  11,
  {
    "_ObjectType_": "SP.Social.SocialThread",
    "Actors": [
      {
        "_ObjectType_": "SP.Social.SocialActor",
        "AccountName": "contoso.com\\evacorets",
        "ActorType": 0,
        "ContentUri": null,
        "EmailAddress": "Eva.Corets@contoso.com",
        "FollowedContentUri": null,
        "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
47049989.0c37852b34d0418e91c62ac25af4be5b",
        "ImageUri": null,
        "IsFollowed": false,
        "LibraryUri": null,
        "Name": "Eva Corets",
        "PersonalSiteUri": "http://my.contoso.com/evacorets/personal/evacorets",
        "StatusText": "",
        "TagGuid": "/Guid(00000000-0000-0000-0000-000000000000)/",
        "Title": "SENIOR SDE",
        "Uri": "http://my.contoso.com/
evacorets:80/Person.aspx?accountname=contoso.com%5Cevacorets"
      }
    ],
    "Attributes": 6,
  }
]
```

```

      "Id":
      "1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
      47049989.0c37852b34d0418e91c62ac25af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-
      124525095-708259637-1543119021-565522",
      "OwnerIndex": 0,
      "Permalink":
      "http://my.contoso.com/evacorets:80/ThreadView.aspx?ThreadID=1.1b73bf8d80eb4dbeab329c3bd23262
      4c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c16747049989.0c37852b34d0418e91c62ac2
      5af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-124525095-708259637-1543119021-
      565522",
      "PostReference": null,
      "Replies": [],
      "RootPost": {
        "_ObjectType_": "SP.Social.SocialPost",
        "Attachment": null,
        "Attributes": 23,
        "AuthorIndex": 0,
        "CreatedTime": "/Date(1337690658345)/",
        "Id":
        "1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
        47049989.0c37852b34d0418e91c62ac25af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-
        124525095-708259637-1543119021-565522",
        "LikerInfo": {
          "_ObjectType_": "SP.Social.SocialPostActorInfo",
          "IncludesCurrentUser": false,
          "Indexes": [],
          "TotalCount": 0
        },
        "ModifiedTime": "/Date(1337690658345)/",
        "Overlays": [],
        "PostType": 0,
        "PreferredImageUri": null,
        "Source": {
          "_ObjectType_": "SP.Social.SocialLink",
          "Text": null,
          "Uri": null
        },
        "Text": "Hello, world."
      },
      "Status": 0,
      "ThreadType": 0,
      "TotalReplyCount": 0
    }
  ]

```

### 4.3 Posting a New Reply

The following sample message from the client creates a reply to an existing message. The headers are omitted from this and the following CSOM samples.

```

POST http://my.contoso.com/_vti_bin/client.svc/ProcessQuery HTTP/1.1
<Request
  xmlns="http://schemas.microsoft.com/sharepoint/clientquery/2009"
  SchemaVersion="15.0.0.0"
  LibraryVersion="15.0.0.0"
  ApplicationName="Javascript Library">
<Actions>
  <ObjectPath Id="1" ObjectPathId="0" />

```

```

<ObjectPath Id="3" ObjectPathId="2" />
<Method Name="CreatePost" Id="4" ObjectPathId="0">
  <Parameters>
    <Parameter Type="String">
      1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c1674
      7049989.0c37852b34d0418e91c62ac25af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-
      124525095-708259637-1543119021-565522
    </Parameter>
    <Parameter TypeId="{2830dd33-271e-4091-a211-e88988e16b03}">
      <Property Name="Attachment" Type="Null" />
      <Property Name="ContentItems" Type="Array" />
      <Property Name="ContentText" Type="String">Hello yourself!</Property>
      <Property Name="DefinitionData" Type="Null" />
      <Property Name="SecurityUri" Type="Null" />
      <Property Name="Source" Type="Null" />
      <Property Name="UpdateStatusText" Type="Boolean">false</Property>
    </Parameter>
  </Parameters>
</Method>
<ObjectPath Id="6" ObjectPathId="5" />
<Query Id="7" ObjectPathId="5">
  <Query SelectAllProperties="false"><Properties /></Query>
  <ChildItemQuery SelectAllProperties="false">
    <Properties>
      <Property Name="DisplayName" SelectAll="true" />
      <Property Name="AccountName" SelectAll="true" />
      <Property Name="UserUrl" SelectAll="true" />
      <Property Name="PictureUrl" SelectAll="true" />
      <Property Name="Email" SelectAll="true" />
      <Property Name="LatestPost" SelectAll="true" />
      <Property Name="IsFollowed" SelectAll="true" />
    </Properties>
  </ChildItemQuery>
</Query>
<Query Id="9" ObjectPathId="0">
  <Query SelectAllProperties="true">
    <Properties />
  </Query>
</Query>
</Actions>
<ObjectPaths>
  <Constructor Id="0"
    TypeId="{c32f5230-2ed0-48fa-ac80-e2ffa22e3d28}" />
  <Constructor Id="2"
    TypeId="{cf560d69-0fdb-4489-a216-b6b47adf8ef8}" />
  <Method Id="5" ParentId="2" Name="GetPeopleFollowedByMe" />
</ObjectPaths>
</Request>

```

#### 4.4 Server Response for a New Reply

The following is the response from the server for a new reply post, after decompressing from the zip compressed message.

[

```

{
  "SchemaVersion": "15.0.0.0",
  "LibraryVersion": "15.0.4118.3001",
  "ErrorInfo": null,
  "TraceCorrelationId": "766ca89b-9c75-5026-2451-a130aedb3fce"
},
1,
{
  "IsNull": false
},
3,
{
  "IsNull": false
},
4,
{
  "_ObjectType_": "SP.Social.SocialThread",
  "Actors": [
    {
      "_ObjectType_": "SP.Social.SocialActor",
      "AccountName": "contoso.com\\evacorets",
      "ActorType": 0,
      "ContentUri": null,
      "EmailAddress": "eva.corets@contoso.com",
      "FollowedContentUri": null,
      "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
47049989.0c37852b34d0418e91c62ac25af4be5b",
      "ImageUri": null,
      "IsFollowed": false,
      "LibraryUri": null,
      "Name": "Eva Corets",
      "PersonalSiteUri": "http://my.contoso.com/evacorets/personal/evacorets",
      "StatusText": "Hello, world.",
      "TagGuid": "/Guid(00000000-0000-0000-0000-000000000000)/",
      "Title": "SENIOR SDE",
      "Uri":
"http://my.contoso.com/evacorets:80/Person.aspx?accountname=contoso.com%5Cevacorets"
    }
  ],
  "Attributes": 6,
  "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
47049989.0c37852b34d0418e91c62ac25af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-
124525095-708259637-1543119021-565522",
  "OwnerIndex": 0,
  "Permalink":
"http://my.contoso.com/evacorets:80/ThreadView.aspx?ThreadID=1.1b73bf8d80eb4dbeab329c3bd23262
4c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c16747049989.0c37852b34d0418e91c62ac2
5af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-124525095-708259637-1543119021-
565522",
  "PostReference": null,
  "Replies": [
    {
      "_ObjectType_": "SP.Social.SocialPost",
      "Attachment": null,
      "Attributes": 23,
      "AuthorIndex": 0,
      "CreatedTime": "/Date(1337691115541)/",

```

```

      "Id":
      "1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
      47049989.0c37852b34d0418e91c62ac25af4be5b.6022554462e44325ac0b70dfc2636af7.3.4.S-1-5-21-
      124525095-708259637-1543119021-565522",
      "LikerInfo": {
        "_ObjectType_": "SP.Social.SocialPostActorInfo",
        "IncludesCurrentUser": false,
        "Indexes": [],
        "TotalCount": 0
      },
      "ModifiedTime": "/Date(1337691115541)/",
      "Overlays": [],
      "PostType": 1,
      "PreferredImageUri": null,
      "Source": {
        "_ObjectType_": "SP.Social.SocialLink",
        "Text": null,
        "Uri": null
      },
      "Text": "Hello yourself!"
    }
  ],
  "RootPost": {
    "_ObjectType_": "SP.Social.SocialPost",
    "Attachment": null,
    "Attributes": 23,
    "AuthorIndex": 0,
    "CreatedTime": "/Date(1337690658000)/",
    "Id":
    "1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
    47049989.0c37852b34d0418e91c62ac25af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-
    124525095-708259637-1543119021-565522",
    "LikerInfo": {
      "_ObjectType_": "SP.Social.SocialPostActorInfo",
      "IncludesCurrentUser": false,
      "Indexes": [],
      "TotalCount": 0
    },
    "ModifiedTime": "/Date(1337691115790)/",
    "Overlays": [],
    "PostType": 0,
    "PreferredImageUri": null,
    "Source": {
      "_ObjectType_": "SP.Social.SocialLink",
      "Text": null,
      "Uri": null
    },
    "Text": "Hello, world."
  },
  "Status": 0,
  "ThreadType": 0,
  "TotalReplyCount": 1
},
6,
{
  "IsNull": false
},
7,
{

```

```

    "_ObjectType_": "SP.ClientObjectList",
    "_Child_Items_": []
  },
  9,
  {
    "_ObjectType_": "SP.Social.SocialFeedManager",
    "Owner": {
      "_ObjectType_": "SP.Social.SocialActor",
      "AccountName": "contoso.com\\evacorets",
      "ActorType": 0,
      "ContentUri": null,
      "EmailAddress": "evacorets@contoso.com",
      "FollowedContentUri": null,
      "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
47049989.0c37852b34d0418e91c62ac25af4be5b",
      "ImageUri": null,
      "IsFollowed": false,
      "LibraryUri": null,
      "Name": "Eva Corets",
      "PersonalSiteUri": "http://my.contoso.com/evacorets/personal/evacorets",
      "StatusText": "Hello, world.",
      "TagGuid": "/Guid(00000000-0000-0000-0000-000000000000)/",
      "Title": "SENIOR SDE",
      "Uri":
"http://my.contoso.com/evacorets:80/Person.aspx?accountname=contoso.com%5Cevacorets"
    }
  }
]

```

## 4.5 Requesting a Feed

The following sample message from the client requests a feed.

```
POST http://my.contoso.com/_vti_bin/client.svc/ProcessQuery HTTP/1.1
```

```

<Request
  xmlns="http://schemas.microsoft.com/sharepoint/clientquery/2009"
  SchemaVersion="15.0.0.0"
  LibraryVersion="15.0.0.0"
  ApplicationName="Javascript Library"
>
  <Actions>
    <ObjectPath Id="1" ObjectPathId="0" />
    <ObjectPath Id="3" ObjectPathId="2" />
    <Method Name="GetFeed" Id="4" ObjectPathId="0">
      <Parameters>
        <Parameter Type="Number">1</Parameter>
        <Parameter TypeId="{86cfc806-c9bb-448a-aed2-c7ff9a5b7ee6}">
          <Property Name="MaxThreadCount" Type="Number">20</Property>
          <Property Name="NewerThan" Type="DateTime">
            2012-05-22T12:59:05.000Z
          </Property>
          <Property Name="OlderThan" Type="Null" />
          <Property Name="SortOrder" Type="Number">0</Property>
        </Parameter>
      </Parameters>
    </Method>
  </Actions>

```

```

</Method>
<ObjectPath Id="6" ObjectPathId="5" />
<Query Id="7" ObjectPathId="5">
  <Query SelectAllProperties="false">
    <Properties />
  </Query>
  <ChildItemQuery SelectAllProperties="false">
    <Properties>
      <Property Name="DisplayName" SelectAll="true" />
      <Property Name="AccountName" SelectAll="true" />
      <Property Name="UserUrl" SelectAll="true" />
      <Property Name="PictureUrl" SelectAll="true" />
      <Property Name="Email" SelectAll="true" />
      <Property Name="LatestPost" SelectAll="true" />
      <Property Name="IsFollowed" SelectAll="true" />
    </Properties>
  </ChildItemQuery>
</Query>
<Query Id="9" ObjectPathId="0">
  <Query SelectAllProperties="true">
    <Properties />
  </Query>
</Query>
</Actions>
<ObjectPaths>
  <Constructor Id="0"
    TypeId="{c32f5230-2ed0-48fa-ac80-e2ffa22e3d28}" />
  <Constructor Id="2"
    TypeId="{cf560d69-0fdb-4489-a216-b6b47adf8ef8}"
  />
  <Method Id="5"
    ParentId="2"
    Name="GetPeopleFollowedByMe"
  />
</ObjectPaths>
</Request>

```

#### 4.6 Server Response for Requesting a Feed

The following is the response from the server for a request for a feed, after decompressing from the zip compressed message.

```

[
  {
    "SchemaVersion": "15.0.0.0",
    "LibraryVersion": "15.0.4118.3001",
    "ErrorInfo": null,
    "TraceCorrelationId": "f06ca89b-fcb2-5026-2451-a351899b7132"
  },
  1,
  {
    "IsNull": false
  },
  3,
  {
    "IsNull": false
  },
]

```

```

4,
{
  "_ObjectType_": "SP.Social.SocialFeed",
  "Attributes": 0,
  "FailedActorIds": [],
  "NewestProcessed": "/Date(1,0,1,0,0,0,0)/",
  "OldestProcessed": "/Date(1,0,1,0,0,0,0)/",
  "Status": 0,
  "Threads": [
    {
      "_ObjectType_": "SP.Social.SocialThread",
      "Actors": [
        {
          "_ObjectType_": "SP.Social.SocialActor",
          "AccountName": "contoso.com\\evacorets",
          "ActorType": 0,
          "ContentUri": null,
          "EmailAddress": "evacorets@contoso.com",
          "FollowedContentUri":
"http://my.contoso.com/evacorets:80/_layouts/15/MySite.aspx?MySiteRedirect=FollowedDocuments"
,
          "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
47049989.0c37852b34d0418e91c62ac25af4be5b",
          "ImageUri": null,
          "IsFollowed": true,
          "LibraryUri": null,
          "Name": "Eva Corets",
          "PersonalSiteUri":
"http://my.contoso.com/evacorets/personal/evacorets",
          "StatusText": "Путин является лучшим премьер-министром.",
          "TagGuid": "/Guid(00000000-0000-0000-0000-000000000000)/",
          "Title": "SENIOR SDE",
          "Uri":
"http://my.contoso.com/evacorets:80/Person.aspx?accountname=contoso.com%5Cevacorets"
        }
      ],
      "Attributes": 6,
      "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
47049989.0c37852b34d0418e91c62ac25af4be5b.28b078c64e3f4a6c9defc9a18b738c7d.5.5.S-1-5-21-
124525095-708259637-1543119021-565522",
      "OwnerIndex": 0,
      "Permalink":
"http://my.contoso.com/evacorets:80/ThreadView.aspx?ThreadID=1.1b73bf8d80eb4dbeab329c3bd23262
4c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c16747049989.0c37852b34d0418e91c62ac2
5af4be5b.28b078c64e3f4a6c9defc9a18b738c7d.5.5.S-1-5-21-124525095-708259637-1543119021-
565522",
      "PostReference": null,
      "Replies": [],
      "RootPost": {
        "_ObjectType_": "SP.Social.SocialPost",
        "Attachment": null,
        "Attributes": 23,
        "AuthorIndex": 0,
        "CreatedTime": "/Date(1337691545000)/",
        "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
47049989.0c37852b34d0418e91c62ac25af4be5b.28b078c64e3f4a6c9defc9a18b738c7d.5.5.S-1-5-21-
124525095-708259637-1543119021-565522",

```



```

        "LikerInfo": {
            "_ObjectType_": "SP.Social.SocialPostActorInfo",
            "IncludesCurrentUser": true,
            "Indexes": [],
            "TotalCount": 1
        },
        "ModifiedTime": "/Date(1337691545000)/",
        "Overlays": [],
        "PostType": 0,
        "PreferredImageUri": null,
        "Source": {
            "_ObjectType_": "SP.Social.SocialLink",
            "Text": null,
            "Uri": null
        },
        "Text": "Путин является лучшим премьер-министром."
    },
    "Status": 0,
    "ThreadType": 0,
    "TotalReplyCount": 0
}
],
"UnreadMentionCount": 0
},
6,
{
    "IsNull": false
},
7,
{
    "_ObjectType_": "SP.ClientObjectList",
    "_Child_Items_": []
},
9,
{
    "_ObjectType_": "SP.Social.SocialFeedManager",
    "Owner": {
        "_ObjectType_": "SP.Social.SocialActor",
        "AccountName": "contoso.com\\evacorets",
        "ActorType": 0,
        "ContentUri": null,
        "EmailAddress": "evacorets@contoso.com",
        "FollowedContentUri": null,
        "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
47049989.0c37852b34d0418e91c62ac25af4be5b",
        "ImageUri": null,
        "IsFollowed": false,
        "LibraryUri": null,
        "Name": "Eva Corets",
        "PersonalSiteUri": "http://my.contoso.com/evacorets/personal/evacorets",
        "StatusText": "Путин является лучшим премьер-министром.",
        "TagGuid": "/Guid(00000000-0000-0000-0000-000000000000)/",
        "Title": "SENIOR SDE",
        "Uri":
"http://my.contoso.com/evacorets:80/Person.aspx?accountname=contoso.com%5Cevacorets"
    }
}
}

```

]

## 4.7 Liking a Post

The following sample message from the client specifies that the current user likes a post.

```
POST http://my.contoso.com/_vti_bin/client.svc/ProcessQuery HTTP/1.1
<Request xmlns="http://schemas.microsoft.com/sharepoint/clientquery/2009"
SchemaVersion="15.0.0.0" LibraryVersion="15.0.0.0" ApplicationName="Javascript Library">
  <Actions>
    <Method Name="LikePost" Id="12" ObjectPathId="0">
      <Parameters>
        <Parameter
Type="String">1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201
c4db0a296c16747049989.0c37852b34d0418e91c62ac25af4be5b.6022554462e44325ac0b70dfc2636af7.3.4.S
-1-5-21-124525095-708259637-1543119021-565522</Parameter>
      </Parameters>
    </Method>
  </Actions>
  <ObjectPaths>
    <Constructor Id="0" TypeId="{c32f5230-2ed0-48fa-ac80-e2ffa22e3d28}" />
  </ObjectPaths>
</Request>
```

## 4.8 Server Response to Liking a Post

The following is the response from the server for a message specifying that the current user likes a post, after decompressing from the zip compressed message.

```
[
  {
    "SchemaVersion": "15.0.0.0",
    "LibraryVersion": "15.0.4118.3001",
    "ErrorInfo": null,
    "TraceCorrelationId": "b76ca89b-1c49-5026-2451-aaelf6932f8e"
  },
  12,
  {
    "_ObjectType_": "SP.Social.SocialThread",
    "Actors": [
      {
        "_ObjectType_": "SP.Social.SocialActor",
        "AccountName": "contoso.com\\evacorets",
        "ActorType": 0,
        "ContentUri": null,
        "EmailAddress": "evacorets@contoso.com",
        "FollowedContentUri": null,
        "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c167
47049989.0c37852b34d0418e91c62ac25af4be5b",
        "ImageUri": null,
        "IsFollowed": false,
        "LibraryUri": null,
        "Name": "Eva Corets",
        "PersonalSiteUri": "http://my.contoso.com/evacorets/personal/evacorets",
        "StatusText": "Hello, world.",
      }
    ]
  }
]
```

```

        "TagGuid": "/Guid(00000000-0000-0000-0000-000000000000)/",
        "Title": "SENIOR SDE",
        "Uri":
"http://my.contoso.com/evacorets:80/Person.aspx?accountname=contoso.com%5Cevacorets"
    }
},
    "Attributes": 6,
    "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c16747049989.0c37852b34d0418e91c62ac25af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-124525095-708259637-1543119021-565522",
    "OwnerIndex": 0,
    "Permalink":
"http://evacorets:80/ThreadView.aspx?ThreadID=1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c16747049989.0c37852b34d0418e91c62ac25af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-124525095-708259637-1543119021-565522",
    "PostReference": null,
    "Replies": [
        {
            "_ObjectType_": "SP.Social.SocialPost",
            "Attachment": null,
            "Attributes": 23,
            "AuthorIndex": 0,
            "CreatedTime": "/Date(1337691116000)/",
            "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c16747049989.0c37852b34d0418e91c62ac25af4be5b.6022554462e44325ac0b70dfc2636af7.3.4.S-1-5-21-124525095-708259637-1543119021-565522",
            "LikerInfo": {
                "_ObjectType_": "SP.Social.SocialPostActorInfo",
                "IncludesCurrentUser": true,
                "Indexes": [],
                "TotalCount": 1
            },
            "ModifiedTime": "/Date(1337691116000)/",
            "Overlays": [],
            "PostType": 1,
            "PreferredImageUri": null,
            "Source": {
                "_ObjectType_": "SP.Social.SocialLink",
                "Text": null,
                "Uri": null
            },
            "Text": "Hello yourself!"
        }
    ],
    "RootPost": {
        "_ObjectType_": "SP.Social.SocialPost",
        "Attachment": null,
        "Attributes": 23,
        "AuthorIndex": 0,
        "CreatedTime": "/Date(1337690658000)/",
        "Id":
"1.1b73bf8d80eb4dbeab329c3bd232624c.a3088f9c195e4e819c247506f084bb6a.6aff918c201c4db0a296c16747049989.0c37852b34d0418e91c62ac25af4be5b.105b8d84258e4a519f6c642f8891db37.3.3.S-1-5-21-124525095-708259637-1543119021-565522",
        "LikerInfo": {
            "_ObjectType_": "SP.Social.SocialPostActorInfo",
            "IncludesCurrentUser": false,
            "Indexes": [],

```

```

        "TotalCount": 0
    },
    "ModifiedTime": "/Date(1337691115000)/",
    "Overlays": [],
    "PostType": 0,
    "PreferredImageUri": null,
    "Source": {
        "_ObjectType_": "SP.Social.SocialLink",
        "Text": null,
        "Uri": null
    },
    "Text": "Hello, world."
},
"Status": 0,
"ThreadType": 0,
"TotalReplyCount": 1
}
]

```

## 4.9 Making a New Root Post Using REST

The following sample REST message creates a new root post in the current user's feed.

```

POST http://my.contoso.com/my/_api/social.feed/my/feed/Post HTTP/1.1
Content-Type: application/json
Accept-Language: en-us
x-requestdigest:
0x75BB236E02F26DF34658EF675052A5689CE204801F874ED1C9932D2E86E0CCB1D820ACA4AB3178501B1711225BC
B55C753074D935D20F48AEE96D97494F64CBD,15 May 2012 13:29:54 -0000
Accept: */*, application/json;odata=verbose
Accept-Encoding: gzip, deflate
User-Agent: Mozilla/5.0 (compatible; MSIE 9.0; Windows NT 6.1; WOW64; Trident/5.0)
Host: evacorets-z400
Content-Length: 250
Connection: Keep-Alive
Pragma: no-cache
Cookie: WSS_FullScreenMode=false; WSS_KeepSessionAuthenticated={fd97fc8e-c3f8-4b4b-8e65-ad8b72dd354f}; MSOWebPartPage_AnonymousAccessCookie={fd97fc8e-c3f8-4b4b-8e65-ad8b72dd354f}
Authorization: NTLM
TlRMTVNTUAAADAAAAGAAAYAI4AAACsAawBpgAAABgAGABYAAAADAAMAHAAAAASABIAfAAAAAAAABSAGaAABYKIogYBsR0AA
AAP5lwRzp4YbtFFkSj3B26RWU4ATwBSAFQASABBAE0ARQBSAEkAQwBBAGIAbABvAG0AbQBlAEIATABPAE0ATQBFADkANg
AwAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAEtRmE5OK3rUV+kZbcuTIBAQAAAAAGXeFbqHMs0BAxy2QrDxvTUAAAA
AAgAYAE4ATwBSAFQASABBAE0ARQBSAEkAQwBBAAEFABMAE8ATQBNAEUALQBaADQAMAAwAAQAPgBuAG8AcgB0AGgAYQbt
AGUAcgBpAGMAYQAUAGMABwByAHAAALgBtAGkAYwByAG8AcwBvAGYAdAAuAGMABwBtAAMAVABsAG8AbQBtAGUALQB6ADQAM
AAwAC4AbgBvAHIAAdABOAGEAbQBlAHIAaQBjAGEALgBjAG8AcgBwAC4AbQBpAGMAGcBvAHMABwBmAHQALgBjAG8AbQAFAC
QAYwBvAHIAcAAuAG0AaQBjAHIAbWZAG8AZgB0AC4AYwBvAG0ABwAIAGXeFbqHMs0BBgAEAAIAAAAIADAAMAAAAAAAAAAA
BAAAAACAAAJHMLK5CIzkrKGVbq+IHWv6H2g7ud3XAYSKPeQoWJdsCgAQAAAAAAAIAAAAAAAAAAAAAAAAAAABJAB4ASABUAFQA
UAAvAGwAbwBtAG0AZQAtAHoANAAdAAAAAAAAAAAAAAAAAAAA
{
  'restCreationData': {
    '__metadata': {
      'type': 'SP.Social.SocialRestPostCreationData'
    },
    'ID': null,
    'creationData': {
      '__metadata': {

```

```

        'type': 'SP.Social.SocialPostCreationData'
    },
    'ContentText': 'ThisismyfirstMicrofeedpost',
    'UpdateStatusText': false
}
}
}}

```

#### 4.10 Server Response to Making a New Root Post Using REST

The following is the response from the server for a REST message creating a new root post, after decompressing from the zip compressed message.

```

HTTP/1.1 200 OK
Cache-Control: private, max-age=0
Content-Type: application/json; charset=utf-8
Expires: Mon, 30 Apr 2012 13:50:45 GMT
Last-Modified: Tue, 15 May 2012 13:50:45 GMT
Vary: Accept-Encoding
Server: Microsoft-IIS/7.5
Set-Cookie: WSS_KeepSessionAuthenticated={fd97fc8e-c3f8-4b4b-8e65-ad8b72dd354f}; path=/
Set-Cookie: MSOWebPartPage_AnonymousAccessCookie={fd97fc8e-c3f8-4b4b-8e65-ad8b72dd354f};
expires=Tue, 15-May-2012 14:20:45 GMT; path=/
X-SharePointHealthScore: 0
X-AspNet-Version: 4.0.30319
X-RequestDigest:
0x0F3D7A760CE51C6FEF28B5E2909C265C5470B214F356430B43F9048507934F239160E4FA964D094B0363E07AC91
911DBE2476433F565922375864ABFA8C481FB,15 May 2012 13:50:45 -0000
X-FRAME-OPTIONS: SAMEORIGIN
SPRequestGuid: 0c2fa69b-061b-608f-f24b-45aa5e6013d8
request-id: 0c2fa69b-061b-608f-f24b-45aa5e6013d8
Persistent-Auth: true
X-Powered-By: ASP.NET
MicrosoftSharePointTeamServices: 15.0.0.4107
X-Content-Type-Options: nosniff
X-MS-InvokeApp: 1; RequireReadOnly
Date: Tue, 15 May 2012 13:50:45 GMT
Content-Length: 2717

{
  "d": {
    "__metadata": {
      "id": "2b20d950-f36d-4743-bcd9-a884b6f14d46",
      "uri":
"http://my.contoso.com/my/_api/social.feed/post(ID=@ai)/?@ai='1.4975bef1e1bc42608c1dfae9f320c
751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-
565461'",
      "type": "SP.Social.SocialRestThread"
    },
    "ID":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c0002
67d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-
124525095-708259637-1543119021-565461",
    "SocialThread": {
      "__metadata": {
        "type": "SP.Social.SocialThread"
      },

```

```

"Actors": {
  "results": [
    {
      "__metadata": {
        "type": "SP.Social.SocialActor"
      },
      "AccountName": "CONTOSO.COM\\evacorets",
      "ActorType": 0,
      "ContentUri": null,
      "EmailAddress": "evacorets@contoso.com",
      "FollowedContentUri": null,
      "Id":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b",
      "ImageUri": null,
      "IsFollowed": false,
      "LibraryUri": null,
      "Name": "Eva Corets",
      "PersonalSiteUri": "http://my.contoso.com/my/personal/evacorets",
      "StatusText": "TestPost",
      "TagGuid": "00000000-0000-0000-0000-000000000000",
      "Title": "SENIOR SDE",
      "Uri":
"http://my.contoso.com:80/my/Person.aspx?accountname=CONTOSO.COM%evacorets"
    }
  ],
  "Attributes": 6,
  "Id":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461",
  "OwnerIndex": 0,
  "Permalink":
"http://my.contoso.com:80/my/ThreadView.aspx?ThreadID=1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461",
  "PostReference": null,
  "Replies": {
    "results": []
  },
  "RootPost": {
    "__metadata": {
      "type": "SP.Social.SocialPost"
    },
    "Attachment": null,
    "Attributes": 23,
    "AuthorIndex": 0,
    "CreatedTime": "2012-05-15T13:50:46.1071671Z",
    "Id":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461",
    "LikerInfo": {
      "__metadata": {
        "type": "SP.Social.SocialPostActorInfo"
      },
      "IncludesCurrentUser": false,
      "Indexes": {
        "results": []
      }
    }
  }
}

```

```

    },
    "TotalCount": 0
  },
  "ModifiedTime": "2012-05-15T13:50:46.1071671Z",
  "Overlays": {
    "results": []
  },
  "PostType": 0,
  "PreferredImageUri": null,
  "Source": {
    "__metadata": {
      "type": "SP.Social.SocialLink"
    },
    "Text": "web",
    "Uri": null
  },
  "Text": "This is my first Microfeed post"
},
"Status": 0,
"ThreadType": 0,
"TotalReplyCount": 0
}
}
}

```

#### 4.11 Posting a New Reply Using REST

The following sample REST message creates a new reply post.

```

POST http://my.contoso.com/my/_api/social.feed/post/Reply HTTP/1.1
{
  'restCreationData': {
    '__metadata': {
      'type': 'SP.Social.SocialRestPostCreationData'
    },
    'ID':
'1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c0002
67d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-
124525095-708259637-1543119021-565461',
    'creationData': {
      '__metadata': {
        'type': 'SP.Social.SocialPostCreationData'
      },
      'ContentText': 'Thisismyfirstreply',
      'UpdateStatusText': false
    }
  }
}

```

#### 4.12 Server Response to Posting a New Reply Using REST

The following is the response from the server for a REST message creating a new reply post, after decompressing from the zip compressed message.

```

{
  "d": {

```

```

    "__metadata": {
      "id": "0193d96b-8af1-484c-bdd3-4c6c5adde8e7",
      "uri":
"http://my.contoso.com/my/_api/social.feed/post(ID=@ai)/?@ai='1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461'",
      "type": "SP.Social.SocialRestThread"
    },
    "ID":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461",
    "SocialThread": {
      "__metadata": {
        "type": "SP.Social.SocialThread"
      },
      "Actors": {
        "results": [
          {
            "__metadata": {
              "type": "SP.Social.SocialActor"
            },
            "AccountName": "CONTOSO.COM\\evacorets",
            "ActorType": 0,
            "ContentUri": null,
            "EmailAddress": "evacorets@contoso.com",
            "FollowedContentUri": null,
            "Id":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b",
            "ImageUri": null,
            "IsFollowed": false,
            "LibraryUri": null,
            "Name": "Eva Corets",
            "PersonalSiteUri": "http://my.contoso.com/my/personal/evacorets",
            "StatusText": "TestPost",
            "TagGuid": "00000000-0000-0000-0000-000000000000",
            "Title": "SENIOR SDE",
            "Uri":
"http://my.contoso.com:80/my/Person.aspx?accountname=CONTOSO.COM%5Cevacorets"
          }
        ]
      },
      "Attributes": 6,
      "Id":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461",
      "OwnerIndex": 0,
      "Permalink":
"http://my.contoso.com:80/my/ThreadView.aspx?ThreadID=1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461",
      "PostReference": null,
      "Replies": {
        "results": [
          {
            "__metadata": {
              "type": "SP.Social.SocialPost"
            }
          }
        ]
      }
    }
  }
}

```



```

    },
    "Attachment": null,
    "Attributes": 23,
    "AuthorIndex": 0,
    "CreatedTime": "2012-05-15T13:54:54.9150454Z",
    "Id":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c0002
67d3e5e4.0c37852b34d0418e91c62ac25af4be5b.58651127efcd41d4b1c1dc137b2aada6.119.121.S-1-5-21-
124525095-708259637-1543119021-565461",
    "LikerInfo": {
      "__metadata": {
        "type": "SP.Social.SocialPostActorInfo"
      },
      "IncludesCurrentUser": false,
      "Indexes": {
        "results": []
      },
      "TotalCount": 0
    },
    "ModifiedTime": "2012-05-15T13:54:54.9150454Z",
    "Overlays": {
      "results": []
    },
    "PostType": 1,
    "PreferredImageUri": null,
    "Source": {
      "__metadata": {
        "type": "SP.Social.SocialLink"
      },
      "Text": "web",
      "Uri": null
    },
    "Text": "This is my first reply"
  }
]
},
"RootPost": {
  "__metadata": {
    "type": "SP.Social.SocialPost"
  },
  "Attachment": null,
  "Attributes": 23,
  "AuthorIndex": 0,
  "CreatedTime": "2012-05-15T13:50:46Z",
  "Id":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c0002
67d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-
124525095-708259637-1543119021-565461",
  "LikerInfo": {
    "__metadata": {
      "type": "SP.Social.SocialPostActorInfo"
    },
    "IncludesCurrentUser": false,
    "Indexes": {
      "results": []
    },
    "TotalCount": 0
  },
  "ModifiedTime": "2012-05-15T13:54:55.2180757Z",

```

```

    "Overlays": {
      "results": []
    },
    "PostType": 0,
    "PreferredImageUri": null,
    "Source": {
      "__metadata": {
        "type": "SP.Social.SocialLink"
      },
      "Text": "web",
      "Uri": null
    },
    "Text": "This is my first Microfeed post"
  },
  "Status": 0,
  "ThreadType": 0,
  "TotalReplyCount": 1
}
}
}

```

#### 4.13 Getting a Thread Using REST

The following sample REST post requests a thread.

```

POST http://my.contoso.com/my/_api/social.feed/post HTTP/1.1
{
  'ID': '1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461'
}

```

#### 4.14 Server Response to Getting a Thread Using REST

The following is the response from the server for a REST message requesting a thread, after decompressing from the zip compressed message.

```

{
  "d": {
    "__metadata": {
      "id": "84bcc697-7d9f-4b7e-95f5-fd51a8d53eca",
      "uri":
        "http://my.contoso.com/my/_api/social.feed/post(ID=@ai)/?@ai='1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461'",
      "type": "SP.Social.SocialRestThread"
    },
    "ID":
      "1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461",
    "SocialThread": {
      "__metadata": {
        "type": "SP.Social.SocialThread"
      }
    }
  }
}

```

```

    },
    "Actors": {
      "results": [
        {
          "__metadata": {
            "type": "SP.Social.SocialActor"
          },
          "AccountName": "CONTOSO.COM\\evacorets",
          "ActorType": 0,
          "ContentUri": null,
          "EmailAddress": "evacorets@contoso.com",
          "FollowedContentUri": null,
          "Id":
            "1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b",
          "ImageUri": null,
          "IsFollowed": false,
          "LibraryUri": null,
          "Name": "Eva Corets",
          "PersonalSiteUri": "http://my.contoso.com/my/personal/evacorets",
          "StatusText": "TestPost",
          "TagGuid": "00000000-0000-0000-0000-000000000000",
          "Title": "SENIOR SDE",
          "Uri":
            "http://my.contoso.com:80/my/Person.aspx?accountname=CONTOSO.COM%5Cevacorets"
        }
      ]
    },
    "Attributes": 6,
    "Id":
      "1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461",
    "OwnerIndex": 0,
    "Permalink":
      "http://my.contoso.com:80/my/ThreadView.aspx?ThreadID=1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-124525095-708259637-1543119021-565461",
    "PostReference": null,
    "Replies": {
      "results": [
        {
          "__metadata": {
            "type": "SP.Social.SocialPost"
          },
          "Attachment": null,
          "Attributes": 23,
          "AuthorIndex": 0,
          "CreatedTime": "2012-05-15T13:54:55Z",
          "Id":
            "1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c000267d3e5e4.0c37852b34d0418e91c62ac25af4be5b.58651127efcd41d4b1c1dc137b2aada6.119.121.S-1-5-21-124525095-708259637-1543119021-565461",
          "LikerInfo": {
            "__metadata": {
              "type": "SP.Social.SocialPostActorInfo"
            },
            "IncludesCurrentUser": false,
            "Indexes": {
              "results": []
            }
          }
        }
      ]
    }
  }
}

```

```

    },
    "TotalCount": 0
  },
  "ModifiedTime": "2012-05-15T13:54:55Z",
  "Overlays": {
    "results": []
  },
  },
  "PostType": 1,
  "PreferredImageUri": null,
  "Source": {
    "__metadata": {
      "type": "SP.Social.SocialLink"
    },
    "Text": "web",
    "Uri": null
  },
  },
  "Text": "This is my first reply"
}
]
},
"RootPost": {
  "__metadata": {
    "type": "SP.Social.SocialPost"
  },
  "Attachment": null,
  "Attributes": 23,
  "AuthorIndex": 0,
  "CreatedTime": "2012-05-15T13:50:46Z",
  "Id":
"1.4975bef1e1bc42608c1dfae9f320c751.35c9fd7b79904800aaa5f74684bf0f75.623664921f034e8d814c0002
67d3e5e4.0c37852b34d0418e91c62ac25af4be5b.230d3c5272fc499f88ac0b74b2f4512f.119.119.S-1-5-21-
124525095-708259637-1543119021-565461",
  "LikerInfo": {
    "__metadata": {
      "type": "SP.Social.SocialPostActorInfo"
    },
    "IncludesCurrentUser": false,
    "Indexes": {
      "results": []
    },
  },
  "TotalCount": 0
},
"ModifiedTime": "2012-05-15T13:54:56Z",
"Overlays": {
  "results": []
},
"PostType": 0,
"PreferredImageUri": null,
"Source": {
  "__metadata": {
    "type": "SP.Social.SocialLink"
  },
  "Text": "web",
  "Uri": null
},
"Text": "This is my first Microfeed post"
},
"Status": 0,
"ThreadType": 0,

```

```
    "TotalReplyCount": 1  
  }  
}
```

Preliminary

## **5 Security**

### **5.1 Security Considerations for Implementers**

None.

### **5.2 Index of Security Parameters**

None.

Preliminary

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® SharePoint® Server 2013 Preview

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 3.1.5.10.1.1.2:](#) SharePoint Server 2013 Preview does not set the **FailedActorIds** property.

[<2> Section 3.1.5.12.2.1.9:](#) SharePoint Server 2013 Preview returns the root post and at most two posts in the thread digest.

[<3> Section 3.1.5.12.2.1.11:](#) SharePoint Server 2013 Preview returns the root post and at most two posts in the thread digest.

[<4> Section 3.1.5.23.1.1.6:](#) SharePoint Server 2013 Preview allows you to create posts with a maximum of one element in the **SecurityUris** array.

[<5> Section 3.1.5.36.1.2:](#) SharePoint Server 2013 Preview includes the root post and at most two replies in a digest thread.

[<6> Section 3.1.5.52.1.1.7:](#) SharePoint Server 2013 Preview returns the value when this object was loaded. If the state has changed between the time the object was loaded and the time when the property value is accessed, the value represents the original state. The client can refresh the object to get a current value.

## 7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

Preliminary



## 8 Index

### A

Abstract data model  
[server](#) 20  
[Applicability](#) 18

### C

[Capability negotiation](#) 18  
[Change tracking](#) 128  
[ChangeTypes](#) 75

### D

Data model - abstract  
[server](#) 20

### E

#### Examples

[getting a thread using REST](#) 122  
[liking a post](#) 114  
[making a new root post](#) 104  
[making a new root post using REST](#) 116  
[posting a new reply](#) 106  
[posting a new reply using REST](#) 119  
[Requesting a feed](#) 110  
[response from server for new root post](#) 105  
[server response for a new reply](#) 107  
[server response for requesting a feed](#) 111  
[server response to getting a thread using REST](#)  
122  
[server response to liking a post](#) 114  
[server response to making a new root post using REST](#) 117  
[server response to posting a new reply using REST](#) 119

### F

[Fields - vendor-extensible](#) 18  
[FollowedContent](#) 75  
[FollowedContentExceptionCode](#) 79  
[FollowedContentQueryOptions](#) 80  
[FollowedItem](#) 81  
[FollowedItemData](#) 84  
[FollowedItemType](#) 85  
[FollowedStatus](#) 87  
[FollowResult](#) 86  
[FollowResultType](#) 86

### G

[Getting a thread using REST example](#) 122  
[Glossary](#) 16

### H

Higher-layer triggered events

[server](#) 20

### I

[Implementer - security considerations](#) 126  
[Index of security parameters](#) 126  
[Informative references](#) 17  
Initialization  
[server](#) 20  
[Introduction](#) 16

### L

[Liking a post example](#) 114

### M

[Making a new root post example](#) 104  
[Making a new root post using REST example](#) 116  
Messages  
[Namespaces](#) 19  
[transport](#) 19

### N

[Namespaces message](#) 19  
[Normative references](#) 17

### O

[ObjectTypes](#) 88  
Other local events  
[server](#) 103  
[Overview \(synopsis\)](#) 17

### P

[Parameters - security index](#) 126  
[PeopleManager](#) 89  
[PersonalSiteCapabilities](#) 94  
[PersonProperties](#) 95  
[Posting a new reply example](#) 106  
[Posting a new reply using REST example](#) 119  
[Preconditions](#) 18  
[Prerequisites](#) 18  
[Product behavior](#) 127  
[ProfileLoader](#) 98

### R

[References](#) 16  
[informative](#) 17  
[normative](#) 17  
[Relationship to other protocols](#) 17  
[Reputation](#) 102  
[Requesting a feed example](#) 110  
[Response from server for new root post example](#)  
105

## S

Security  
[implementer considerations](#) 126  
[parameter index](#) 126

Server  
[abstract data model](#) 20  
[higher-layer triggered events](#) 20  
[initialization](#) 20  
[other local events](#) 103  
[timer events](#) 103  
[timers](#) 20  
[Server response for a new reply example](#) 107  
[Server response for requesting a feed example](#) 111  
[Server response to getting a thread using REST example](#) 122  
[Server response to liking a post example](#) 114  
[Server response to making a new root post using REST example](#) 117  
[Server response to posting a new reply using REST example](#) 119  
[SocialActor](#) 20  
[SocialActorInfo](#) 23  
[SocialActorType](#) 24  
[SocialActorTypes](#) 25  
[SocialAttachment](#) 26  
[SocialDataItem](#) 26  
[SocialDataItemType](#) 28  
[SocialDataOverlay](#) 28  
[SocialDataOverlayType](#) 30  
[SocialDataStoreExceptionCode](#) 99  
[SocialFeed](#) 30  
[SocialFeedAttributes](#) 32  
[SocialFeedManager](#) 32  
[SocialFeedOptions](#) 37  
[SocialFeedSortOrder](#) 38  
[SocialFeedStatus](#) 39  
[SocialFeedType](#) 39  
[SocialFollowingManager](#) 40  
[SocialFollowResult](#) 42  
[SocialLink](#) 43  
[SocialPost](#) 44  
[SocialPostActorInfo](#) 46  
[SocialPostCreationData](#) 48  
[SocialPostDefinitionData](#) 49  
[SocialPostDefinitionDataItem](#) 50  
[SocialPostDefinitionDataItemType](#) 51  
[SocialPostReference](#) 52  
[SocialPostType](#) 53  
[SocialRestActor](#) 53  
[SocialRestFeed](#) 56  
[SocialRestFeedManager](#) 58  
[SocialRestFollowingManager](#) 60  
[SocialRestPostCreationData](#) 65  
[SocialRestThread](#) 66  
[SocialThread](#) 70  
[SocialThreadAttributes](#) 73  
[SocialThreadStatus](#) 73  
[SocialThreadType](#) 74  
[Standards assignments](#) 18

## T

Timer events  
[server](#) 103

Timers  
[server](#) 20  
[Tracking changes](#) 128  
[Transport](#) 19

Triggered events - higher-layer  
[server](#) 20

## U

[UserProfile](#) 99  
[UserProfilePropertiesForUser](#) 101

## V

[Vendor-extensible fields](#) 18  
[Versioning](#) 18