

# [MS-STANXIMAP]: Exchange Internet Message Access Protocol (IMAP) Standards Support

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

**Preliminary Documentation.** This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

## Revision Summary

Date	Revision History	Revision Class	Comments
07/15/2009	1.0.0	Major	Initial Availability.
10/01/2008	1.1.0	Minor	Updated IP notice.
04/10/2009	2.0.0	Major	Updated applicable product releases.
07/15/2009	3.0.0	Major	Revised and edited technical content.
11/04/2009	3.1.0	Minor	Updated the technical content.
02/10/2010	3.1.0	None	Version 3.1.0 release
08/04/2010	3.2	Minor	Clarified the meaning of the technical content.
11/03/2010	3.3	Minor	Clarified the meaning of the technical content.
03/18/2011	3.4	Minor	Clarified the meaning of the technical content.
08/05/2011	3.4	No change	No changes to the meaning, language, or formatting of the technical content.
10/07/2011	4.0	Major	Significantly changed the technical content.
01/20/2012	5.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1 Introduction</b> .....	<b>5</b>
1.1 Glossary .....	5
1.2 References.....	5
1.2.1 Normative References.....	5
1.2.2 Informative References .....	6
1.3 Microsoft Implementations.....	6
1.4 Standards Support Requirements .....	6
1.5 Notation .....	6
<b>2 Standards Support Statements</b> .....	<b>7</b>
2.1 Normative Variations.....	7
2.1.1 [RFC3501] Section 2.1, Port 143 .....	7
2.1.2 [RFC3501] Section 2.3.1.1, Unique Identifiers MUST NOT Change During Session ....	7
2.1.3 [RFC3501] Section 2.3.1.1, Combination of Mailbox Name, UIDVALIDITY, and UID MUST Refer to Single, Immutable message .....	7
2.1.4 [RFC3501] Section 7.2.1, Server MUST Support STARTTLS, LOGINDISABLED, and AUTH=PLAIN Capabilities .....	7
2.1.5 [RFC3501] Section 9, ABNF Rules in General .....	7
2.1.6 [RFC3501] Section 9, Rule Regarding Spaces .....	8
2.1.7 [RFC3501] Section 11.1, Server MUST Implement the TLS_RSA_WITH_RC4_128_MD5 Cipher Suite .....	8
2.2 Clarifications .....	8
2.2.1 [RFC3501] Section 2.2.1, Client Protocol Sender and Server Protocol Receiver.....	8
2.2.2 [RFC3501] Section 2.2.2, Server Protocol Sender and Client Protocol Receiver.....	8
2.2.3 [RFC3501] Section 2.3.1.1, Unique Identifier (UID) Message Attribute.....	9
2.2.4 [RFC3501] Section 2.3.2, Flags Message Attribute.....	9
2.2.5 [RFC3501] Section 2.3.4, [RFC2822] Size Message Attribute .....	9
2.2.6 [RFC3501] Section 4.3.1, 8-bit and Binary Strings .....	10
2.2.7 [RFC3501] Section 5.1, Mailbox Naming .....	10
2.2.8 [RFC3501] Section 5.2, Mailbox Size and Message Status Updates .....	11
2.2.9 [RFC3501] Section 5.3, Response When No Command in Progress .....	11
2.2.10 [RFC3501] Section 5.4, Autologout Timer.....	11
2.2.11 [RFC3501] Section 5.5, Multiple Commands in Progress .....	12
2.2.12 [RFC3501] Section 6.2, Client Commands — Not Authenticated State .....	12
2.2.13 [RFC3501] Section 6.2.1, STARTTLS Command.....	13
2.2.14 [RFC3501] Section 6.2.2, AUTHENTICATE Command .....	13
2.2.15 [RFC3501] Section 6.2.3, LOGIN Command .....	14
2.2.16 [RFC3501] Section 6.3.3, CREATE Command .....	14
2.2.17 [RFC3501] Section 6.3.4, DELETE Command .....	14
2.2.18 [RFC3501] Section 6.3.6, SUBSCRIBE Command.....	15
2.2.19 [RFC3501] Section 6.3.8, LIST Command.....	15
2.2.20 [RFC3501] Section 6.3.9, LSUB Command.....	15
2.2.21 [RFC3501] Section 6.3.11, APPEND Command .....	16
2.2.22 [RFC3501] Section 6.4.1, CHECK Command .....	16
2.2.23 [RFC3501] Section 6.4.4, SEARCH Command.....	16
2.2.24 [RFC3501] Section 6.4.5, FETCH Command .....	18
2.2.25 [RFC3501] Section 6.4.6, STORE Command.....	18
2.2.26 [RFC3501] Section 6.5, Client Commands — Experimental/Expansion .....	19
2.2.27 [RFC3501] Section 7.1, Server Responses — Status Responses.....	19
2.2.28 [RFC3501] Section 7.1.1, OK Response .....	19

2.2.29	[RFC3501] Section 7.1.4, PREAUTH Response .....	19
2.2.30	[RFC3501] Section 7.2.1, CAPABILITY Response .....	20
2.2.31	[RFC3501] Section 7.2.2, LIST Response.....	20
2.2.32	[RFC3501] Section 7.2.6, FLAGS Response .....	20
2.2.33	[RFC3501] Section 7.4.1, EXPUNGE Response.....	20
2.2.34	[RFC3501] Section 7.4.2, FETCH Response .....	20
2.2.35	[RFC3501] Section 7.5, Server Responses – Command Continuation Request .....	21
2.2.36	[RFC3501] Section 11.1, STARTTLS Security Considerations .....	21
2.2.37	[RFC3501] Section 11.2, Other Security Considerations .....	22
2.3	Error Handling .....	22
2.4	Security.....	22
<b>3</b>	<b>Change Tracking.....</b>	<b>23</b>
<b>4</b>	<b>Index .....</b>	<b>25</b>

# 1 Introduction

This document specifies the level to which Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, and Microsoft® Exchange Server 15 Technical Preview conform to the Internet Message Access Protocol (IMAP). A client that implements IMAP is able to access and manipulate electronic **mailboxes** on an IMAP server in a way that is functionally equivalent to local folders. The Microsoft® Exchange Server IMAP service component processes requests from an IMAP client.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**Augmented Backus-Naur Form (ABNF)**  
**NT LAN Manager (NTLM) Authentication Protocol**  
**SASL**  
**Transmission Control Protocol (TCP)**

The following terms are defined in [\[MS-OXGLOS\]](#):

**base64 encoding**  
**mailbox**

The following terms are specific to this document:

**Generic Security Services (GSS) API:** A programming interface that provides security services to a caller (typically, a communications protocol) in a generic fashion and that allows source-level portability of applications to different environments.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2246] Dierks, T., and Allen, C., "The TLS Protocol Version 1.0", RFC 2246, January 1999, <http://www.ietf.org/rfc/rfc2246.txt>

[RFC2822] Resnick, P., Ed., "Internet Message Format", STD 11, RFC 2822, April 2001, <http://www.ietf.org/rfc/rfc2822.txt>

## 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

## 1.3 Microsoft Implementations

Microsoft® Exchange Server 2007

Microsoft® Exchange Server 2010

Microsoft® Exchange Server 15 Technical Preview

## 1.4 Standards Support Requirements

The conformance requirements for [\[RFC3501\]](#) are as follows:

- All required portions of the specification are implemented according to the specification.
- Any recommended portions that are implemented are implemented according to the specification.
- Any optional portions that are implemented are implemented according to the specification.

The following table lists the sections of [\[RFC3501\]](#) that are considered normative and the sections that are considered informative.

Section(s)	Normative/Informative
1	Informative
2 - 7	Normative
8	Informative
9	Normative
10 - 12	Informative

## 1.5 Notation

The following notations are used to identify clarifications in section [2.2](#).

Notation	Explanation
C####	This notation identifies a clarification of ambiguity in the target specification. This includes imprecise statements, omitted information, discrepancies, and errata. This does not include data formatting clarifications.
V####	This notation identifies an intended point of variability in the target specification such as the use of MAY, SHOULD, or RECOMMENDED. This does not include extensibility points.
E####	Because the use of extensibility points, such as optional implementation-specific data, could impair interoperability, this notation identifies such points in the target specification.

## 2 Standards Support Statements

### 2.1 Normative Variations

The following subsections detail the normative variations from [\[RFC3501\]](#).

#### 2.1.1 [RFC3501] Section 2.1, Port 143

The specification states: "When **TCP** is used, an IMAP4rev1 server listens on port 143."

By default, Microsoft® Exchange Server uses port 143 for TCP connections and port 993 for SSL connections. However, Microsoft Exchange can be configured to use any port.

#### 2.1.2 [RFC3501] Section 2.3.1.1, Unique Identifiers MUST NOT Change During Session

The specification states that the unique identifier of a message MUST NOT change during the session.

Microsoft® Exchange Server assigns a new UID to a revised message. (A message can be changed by another protocol and, under certain conditions, the revised message replaces the existing message.)

#### 2.1.3 [RFC3501] Section 2.3.1.1, Combination of Mailbox Name, UIDVALIDITY, and UID MUST Refer to Single, Immutable message

The specification states: "The combination of mailbox name, UIDVALIDITY, and UID must refer to a single immutable message on that server forever. In particular, the internal date, [\[RFC2822\]](#) size, envelope, body structure, and message texts (RFC822, RFC822.HEADER, RFC822.TEXT, and all BODY[...] fetch data items) must never change."

Although Microsoft® Exchange Server adheres to this rule, other protocols have access to these messages, and some of these protocols modify message properties such as the message body.

#### 2.1.4 [RFC3501] Section 7.2.1, Server MUST Support STARTTLS, LOGINDISABLED, and AUTH=PLAIN Capabilities

The specification states that the server implementation MUST support the STARTTLS, the LOGINDISABLED, and the AUTH=PLAIN capabilities.

Microsoft® Exchange Server does not support the LOGINDISABLED capability by default, but it can be configured to do so.

#### 2.1.5 [RFC3501] Section 9, ABNF Rules in General

The specification states that **ABNF** rules MUST be strictly followed.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, and Microsoft® Exchange Server 2010 Service Pack 1 (SP1) do not strictly follow the rules when sending responses or when parsing commands from the client.

Microsoft® Exchange Server 2010 Service Pack 2 (SP2) and Microsoft® Exchange Server 15 Technical Preview strictly follow the rules when sending responses but do not strictly follow the rules when parsing commands from the client.

## 2.1.6 [RFC3501] Section 9, Rule Regarding Spaces

The specification states: "In all cases, SP refers to exactly one space. It is NOT permitted to substitute TAB, insert additional spaces, or otherwise treat SP as being equivalent to LWSP."

Microsoft® Exchange Server strictly follows the rules when sending responses. When parsing a command from the client, Microsoft Exchange accepts a TAB character as a delimiter of the command itself, but allows only one space in all other places.

## 2.1.7 [RFC3501] Section 11.1, Server MUST Implement the TLS\_RSA\_WITH\_RC4\_128\_MD5 Cipher Suite

The specification states that the server MUST implement the TLS\_RSA\_WITH\_RC4\_128\_MD5 cipher suite.

Microsoft® Exchange Server does not implement the TLS\_RSA\_WITH\_RC4\_128\_MD5 cipher suite and, instead, relies on the operating system to provide the implementation.

## 2.2 Clarifications

The following subsections identify clarifications relative to [\[RFC3501\]](#).

Unless otherwise stated, the specified products conform to all SHOULD and RECOMMENDED behavior as specified in [\[RFC3501\]](#). The term "can" is used throughout [\[RFC3501\]](#) and is interpreted to indicate optional behavior.

### 2.2.1 [RFC3501] Section 2.2.1, Client Protocol Sender and Server Protocol Receiver

C0001:

The specification states that each client command is prefixed with an identifier, called a tag, but does not make a specific requirement on format. Later in the specification (section 9), the syntax is explicitly stated.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not enforce any particular format.

V0001:

The specification states that a different tag is generated by the client for each command.

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange accepts repeated use of the same tag in subsequent commands.

### 2.2.2 [RFC3501] Section 2.2.2, Server Protocol Sender and Client Protocol Receiver

V0002:

The specification states: "Server data MAY be sent as a result of a client command, or MAY be sent unilaterally by the server."



Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server sends data to the client unilaterally.

V0003:

The specification states: "Servers SHOULD enforce the syntax outlined in this specification strictly. Any client command with a protocol syntax error, including (but not limited to) missing or extraneous spaces or arguments, SHOULD be rejected, and the client given a BAD server completion response."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange is liberal in parsing the spaces in commands. For more details, see section [2.1.6](#) in this document.

### **2.2.3 [RFC3501] Section 2.3.1.1, Unique Identifier (UID) Message Attribute**

V0004:

The specification states that the unique identifier of a message SHOULD NOT change between sessions.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server assigns a new UID to a revised message. (A message can be changed by another protocol and, under certain conditions, the revised message replaces the existing message.)

### **2.2.4 [RFC3501] Section 2.3.2, Flags Message Attribute**

E0001:

The specification states that the server can define keywords. (A keyword is a non-system flag.)

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server defines the \$MDNSent keyword, which is set on the message when the client sends a message delivery notification (MDN).

V0005:

The specification states: "Servers MAY permit the client to define new keywords in the mailbox."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange does not support client-defined keywords.

### **2.2.5 [RFC3501] Section 2.3.4, [RFC2822] Size Message Attribute**

V0006:

The specification defines the [\[RFC2822\]](#) size message attribute as the number of octets in the message.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

By default, Microsoft® Exchange Server calculates the [\[RFC2822\]](#) size based on the amount of storage space that the message actually occupies. However, Microsoft Exchange can be configured to base the calculation of the [\[RFC2822\]](#) size on the exact MIME size of the message.

## 2.2.6 [RFC3501] Section 4.3.1, 8-bit and Binary Strings

V0007:

The specification states that implementations MAY transmit 8-bit or multi-octet characters in literals, but SHOULD do so only when the IANA-registered character set is identified.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not transmit 8-bit or multi-octet characters.

## 2.2.7 [RFC3501] Section 5.1, Mailbox Naming

V0008:

The specification takes no position on case-sensitivity in non-INBOX mailbox names.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server is case-insensitive regarding non-INBOX mailbox names.

V0009:

The specification states: "Any character which is one of the atom-specials will require that the mailbox name be represented as a quoted string or literal."

Exchange 2007

Microsoft Exchange returns a literal for a mailbox name that includes the backslash character ("\"), but does not return a literal for a mailbox name that includes other atom-specials.

Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange returns a literal for a mailbox name that includes the backslash character ("\"), or the double-quote character ("\"), but does not return a literal for a mailbox name that includes other atom-specials.

V0010:

The specification states: "Although the list-wildcard characters ('%' and '\*') are valid in a mailbox name, it is difficult to use such mailbox names with the LIST and LSUB commands due to the conflict with wildcard interpretation."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange allows a mailbox name to contain a wildcard character and other special characters (such as atom-specials), provided that the characters are escaped.

V0011:

The specification states: "Usually, a character (determined by the server implementation) is reserved to delimit levels of hierarchy."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange uses the forward slash ("/") as the hierarchy delimiter.

V0012:

The specification states: "Two characters, '#' and '&', have meanings by convention, and should be avoided except when used in that convention."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange allows a mailbox name to contain "&", provided that the "&" is encoded as specified in section 5.1.3 of the specification. An unescaped "&" would be treated as a shift to the modified **base64 encoding**, as described in section 5.1.3 of the specification. Microsoft Exchange allows unescaped "#" in folder names.

### **2.2.8 [RFC3501] Section 5.2, Mailbox Size and Message Status Updates**

V0013:

The specification states that agents other than the server MAY add messages to the mailbox, change the flags of the messages in the mailbox, or even remove messages from the mailbox.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server allows non-IMAP protocols to add messages, change flags of messages, and remove messages.

### **2.2.9 [RFC3501] Section 5.3, Response When No Command in Progress**

V0014:

The specification states: "Server implementations are permitted to send an untagged response (except for EXPUNGE) while there is no command in progress. Server implementations that send such responses MUST deal with flow control considerations. Specifically, they MUST either (1) verify that the size of the data does not exceed the underlying transport's available window size, or (2) use non-blocking writes."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server can send an untagged response when there is no command in progress. Microsoft Exchange has mechanisms to manage flow control. Any untagged responses that Microsoft Exchange sends are brief and, therefore, fit into most MTA windows.

### **2.2.10 [RFC3501] Section 5.4, Autologout Timer**

V0015:

The specification states: "If a server has an inactivity autologout timer, the duration of that timer MUST be at least 30 minutes."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server has an inactivity autologout timer with a default duration of 30 minutes, but can be configured to use a duration of less than 30 minutes.

E0002:

The specification does not describe any other required or optional autologout timers.

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange implements an unauthenticated timer, which limits the duration of an unauthenticated session. The default duration of the unauthenticated timer is 60 seconds, but Microsoft Exchange can be configured to use a duration of less than 60 seconds. The receipt of any command from the client during that interval does not reset the unauthenticated timer.

### **2.2.11 [RFC3501] Section 5.5, Multiple Commands in Progress**

V0016:

The specification states that a server MAY begin processing another command before processing the current command to completion, subject to ambiguity rules.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not begin processing another command before processing the current command to completion. (Microsoft Exchange processes commands serially.)

V0017:

The specification states: "If the server detects a possible ambiguity, it MUST execute commands to completion in the order given by the client."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange processes commands serially and, therefore, does not need to deal with ambiguities.

### **2.2.12 [RFC3501] Section 6.2, Client Commands – Not Authenticated State**

V0018:

The specification states that server implementations MAY allow access to certain mailboxes without establishing authentication.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not allow access to mailboxes without authentication.

V0019:

The specification states that a client can access mailboxes without establishing authentication by using either the ANONYMOUS authenticator or the LOGIN command with a user name of "anonymous".

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange does not support either the ANONYMOUS authenticator or the LOGIN command with an anonymous user name.

### 2.2.13 [RFC3501] Section 6.2.1, STARTTLS Command

V0020:

The specification states: "The server MAY advertise different capabilities after STARTTLS."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server sends capabilities only in response to a CAPABILITY command from the client. Microsoft Exchange does not send capabilities automatically by using the CAPABILITY response code. For more details, see sections [2.2.14](#), [2.2.15](#), and [2.2.30](#) of this document.

### 2.2.14 [RFC3501] Section 6.2.2, AUTHENTICATE Command

V0021:

The specification states: "If the server supports the requested authentication mechanism, it performs an authentication protocol exchange to authenticate and identify the client. It MAY also negotiate an OPTIONAL security layer for subsequent protocol interactions."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not support negotiation of an OPTIONAL security layer.

E0003:

The specification states that the server is not required to implement any authentication mechanisms other than the PLAIN authentication mechanism.

Exchange 2007

In addition to the PLAIN authentication mechanism, Microsoft Exchange implements the following authentication mechanisms:

- **NTLM**
- **GSSAPI** (also called Kerberos)

Exchange 2010, Exchange 15 Technical Preview

In addition to the PLAIN authentication mechanism, Microsoft Exchange implements the GSSAPI authentication mechanism.

V0022:

The specification states that server sites SHOULD NOT use any configuration that permits a plaintext password mechanism without a protection mechanism against password snooping.

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

By default, Microsoft Exchange does not permit plaintext password authentication, but can be configured to allow plaintext password authentication without protection against password snooping.

E0004:

The specification states that servers SHOULD implement additional **SASL** mechanisms that do not use plaintext passwords.

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

For details, see E0005 in this section.

V0023:

The specification states: "A server MAY include a CAPABILITY response code in the tagged OK response of a successful AUTHENTICATE command in order to send capabilities automatically."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange does not include a CAPABILITY response code in its response to a successful AUTHENTICATE command. Microsoft Exchange sends capabilities only in response to a CAPABILITY command from the client. For more details, see sections [2.2.13](#), [2.2.15](#), and [2.2.30](#) of this document.

### **2.2.15 [RFC3501] Section 6.2.3, LOGIN Command**

V0024:

The specification states: "A server MAY include a CAPABILITY response code in the tagged OK response to a successful LOGIN command in order to send capabilities automatically."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not include a CAPABILITY response code in its response to a successful LOGIN command. Microsoft Exchange sends capabilities only in response to a CAPABILITY command from the client. For more details, see sections [2.2.13](#), [2.2.14](#), and [2.2.30](#) of this document.

### **2.2.16 [RFC3501] Section 6.3.3, CREATE Command**

V0025:

The specification states: "If the server's hierarchy separator character appears elsewhere in the name, the server SHOULD create any superior hierarchical names that are needed for the CREATE command to be successfully completed."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server creates all superior hierarchical names, wherever possible, to allow successful completion of the CREATE command.

### **2.2.17 [RFC3501] Section 6.3.4, DELETE Command**

V0026:

The specification states: "It is permitted to delete a name that has inferior hierarchical names and does not have the \Noselect mailbox name attribute."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not allow a mailbox to be deleted if it has inferior hierarchical names.

### **2.2.18 [RFC3501] Section 6.3.6, SUBSCRIBE Command**

V0027:

The specification states: "A server MAY validate the mailbox argument to SUBSCRIBE to verify that it exists."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not validate that the mailbox exists.

### **2.2.19 [RFC3501] Section 6.3.8, LIST Command**

V0028:

The specification prescribes rules that apply to mailbox names that are returned in the LIST response.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

If a mailbox name contains the backslash character ("\"), then Microsoft® Exchange Server returns the mailbox name as a literal preceded by a <length> field.

V0029:

The specification states: "If the reference argument is not a level of mailbox hierarchy (that is, it is a \NoInferiors name), and/or the reference argument does not end with the hierarchy delimiter, it is implementation-dependent how this is interpreted."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange simply returns "LIST completed" in this case.

V0030:

The specification states that server implementations are permitted to hide otherwise accessible mailboxes from the wildcard characters.

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange does not hide any mailboxes from wildcard characters.

### **2.2.20 [RFC3501] Section 6.3.9, LSUB Command**

V0031:

The specification prescribes rules that apply to mailbox names that are returned in the LSUB response.

Microsoft® Exchange Server 2007

If a mailbox name contains the backslash character ("\"), then Microsoft® Exchange Server returns the mailbox name as a literal preceded by a <length> field.

Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

If a mailbox name contains the backslash character ("\"), or the double-quote character ("\"), then Microsoft Exchange returns the mailbox name as a literal preceded by a <length> field.

V0032:

The specification states: "The returned untagged LSUB response MAY contain different mailbox flags from a LIST untagged response."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange supports an untagged LSUB response containing mailbox flags that are different from those in an untagged LIST response. The flags differ according to the mailbox's existing flags.

### **2.2.21 [RFC3501] Section 6.3.11, APPEND Command**

V0033:

The specification states: "If the mailbox is currently selected, the normal new message actions SHOULD occur. Specifically, the server SHOULD notify the client immediately via an untagged EXISTS response."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

If the mailbox is currently selected, then Microsoft® Exchange Server does not immediately send an untagged EXISTS response. Instead, Microsoft Exchange sends an untagged EXISTS response upon successful completion of APPEND within the currently selected mailbox.

### **2.2.22 [RFC3501] Section 6.4.1, CHECK Command**

V0034:

The specification defines the CHECK command.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server implements the CHECK command as identical to the NOOP command.

### **2.2.23 [RFC3501] Section 6.4.4, SEARCH Command**

V0035:

The specification states: "US-ASCII MUST be supported; other IANA character sets MAY be supported."



Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server supports only the US-ASCII character set.

V0036:

The specification states that the tagged NO response SHOULD contain the BADCHARSET response code, which MAY list the IANA character sets that are supported by the server.

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange includes the BADCHARSET response code followed by (US-ASCII).

V0037:

The specification defines the KEYWORD <flag> search key as: "Messages with the specified keyword flag set."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange supports only the \$MDNSent keyword flag for the KEYWORD search key. For more details, see section [2.2.4](#) of this document.

V0038:

The specification defines the LARGER <n> search key as: "Messages with an [\[RFC2822\]](#) size larger than the specified number of octets."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

If the [\[RFC2822\]](#) size of the message is known, then Microsoft Exchange compares the [\[RFC2822\]](#) size to the specified number of octets; otherwise, Microsoft Exchange compares the stored-message size (this is the amount of storage space that the message actually occupies) to the specified number of octets. Microsoft Exchange can be configured to evaluate the [\[RFC2822\]](#) size in all circumstances.

V0039:

The specification defines the SMALLER <n> search key as: "Messages with an [\[RFC2822\]](#) size smaller than the specified number of octets."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

If the [\[RFC2822\]](#) size of the message is known, then Microsoft Exchange compares the [\[RFC2822\]](#) size with the specified number of octets; otherwise, Microsoft Exchange compares the stored-message size (this is the amount of storage space that the message actually occupies) of the message to the specified number of octets. Microsoft Exchange can be configured to evaluate the [\[RFC2822\]](#) size in all circumstances.

V0040:

The specification defines the UNKEYWORD <flag> search key as: "Messages that do not have the specified keyword flag set."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange supports only the \$MDNSent keyword flag for the UNKEYWORD search key. For more details, see section [2.2.4](#) of this document.

V0041:

The specification states: "Searching criteria consist of one or more search keys."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange supports recursive grouping of criteria as follows:

- There can be as many as ten levels of recursion.
- Within each recursion, any number of search keys can be used to specify the criteria.
- Parentheses are used to delimit the levels of recursion. For example, four levels of recursion will have the following form: (criteria 1 (OR criteria 2 (OR criteria 3 (OR criteria 4))))

### **2.2.24 [RFC3501] Section 6.4.5, FETCH Command**

V0042:

The specification states that some data items, identified in the formal syntax under the msg-att-dynamic rule, MAY change, either as a result of a STORE command, or due to external events.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server allows such data items to change either as a result of a STORE command or due to external events.

V0043:

The specification describes the RFC822.SIZE data item as: "The [RFC2822](#) size of the message."

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

If the [RFC2822](#) size of the message is known, then Microsoft Exchange returns that value; otherwise, Microsoft Exchange returns the stored-message size (this is the amount of storage space that the message actually occupies). Microsoft Exchange can be configured to return the [RFC2822](#) size in all circumstances.

### **2.2.25 [RFC3501] Section 6.4.6, STORE Command**

V0044:

The specification states that, regardless of whether the .SILENT suffix was used in the data item name, the server SHOULD send an untagged FETCH response if a message's flags are changed by an external source.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server never sends an untagged FETCH response if a message's flags are changed by an external source.

## **2.2.26 [RFC3501] Section 6.5, Client Commands – Experimental/Expansion**

V0045:

The specification describes how to define an experimental command or any command that is not part of the specification.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not define any such commands.

## **2.2.27 [RFC3501] Section 7.1, Server Responses – Status Responses**

V0046:

The specification states that status responses (OK, NO, BAD, PREAUTH, and BYE) MAY include an OPTIONAL response code.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server includes optional response codes for certain status responses.

V0047:

The specification defines the ALERT response code and the PARSE response code.

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange does not implement the ALERT response code and the PARSE response code.

## **2.2.28 [RFC3501] Section 7.1.1, OK Response**

V0048:

The specification states: "The untagged form indicates an information-only message; the nature of the information MAY be indicated by a response code."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server sends an untagged OK response that includes human-readable text with no response code.

## **2.2.29 [RFC3501] Section 7.1.4, PREAUTH Response**

V0049:

The specification defines the PREAUTH response.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not implement the PREAUTH response.

### **2.2.30 [RFC3501] Section 7.2.1, CAPABILITY Response**

V0050:

The specification states: "A server MAY send capabilities automatically, by using the CAPABILITY response code in the initial PREAUTH or OK responses, and by sending an updated CAPABILITY response code in the tagged OK response as part of a successful authentication."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not use the CAPABILITY response code to automatically send capabilities to the client. Microsoft Exchange sends capabilities to the client only when the client requests capabilities by using the CAPABILITY command. For more details, see sections [2.2.13](#), [2.2.14](#), and [2.2.15](#) of this document.

### **2.2.31 [RFC3501] Section 7.2.2, LIST Response**

V0051:

The specification defines four name attributes for the LIST response.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server uses the \Marked and the \Noselect name attributes. Microsoft Exchange does not use the \Noinferiors and the \Unmarked name attributes.

### **2.2.32 [RFC3501] Section 7.2.6, FLAGS Response**

V0052:

The specification states that flags other than the system flags can also exist, depending on server implementation.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

For more details, see section [2.2.4](#) of this document.

### **2.2.33 [RFC3501] Section 7.4.1, EXPUNGE Response**

V0053:

The specification states that the server does not need to send an EXISTS response after an untagged EXPUNGE response decrements the number of messages in the mailbox.

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Upon successful completion of the EXPUNGE command, Microsoft® Exchange Server sends an EXISTS response with the updated size of the mailbox.

### **2.2.34 [RFC3501] Section 7.4.2, FETCH Response**

V0054:

The specification states: "Extension data is never returned with the BODY fetch, but can be returned with a BODYSTRUCTURE fetch."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server returns extension data as part of a BODYSTRUCTURE fetch.

V0055:

The specification states that a server can return a NIL envelope member in the case where the Date, Subject, In-Reply-To, or Message-ID header line are present but empty.

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

If the Date, Subject, In-Reply-To, or Message-ID header line are present but empty, Microsoft Exchange returns a NIL envelope member.

### **2.2.35 [RFC3501] Section 7.5, Server Responses – Command Continuation Request**

V0056:

The specification states that the command continuation request response "is also used if an argument to any command is a literal."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 2010 Service Pack 1 (SP1), Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not return the command continuation request response when a client issues a SEARCH command with a literal.

### **2.2.36 [RFC3501] Section 11.1, STARTTLS Security Considerations**

V0057:

The specification states that the server SHOULD implement the TLS\_DHE\_DSS\_WITH\_3DES\_EDE\_CBC\_SHA cipher suite, as specified in [\[RFC2246\]](#).

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server does not implement the TLS\_DHE\_DSS\_WITH\_3DES\_EDE\_CBC\_SHA cipher suite and, instead, relies on the operating system to provide the implementation.

V0058:

The specification states that all cipher suites other than TLS\_RSA\_WITH\_RC4\_128\_MD5 and TLS\_DHE\_DSS\_WITH\_3DES\_EDE\_CBC\_SHA are optional.

Exchange 2007, Exchange 2010, Exchange 15 Technical Preview

Microsoft Exchange does not implement any optional cipher suites and, instead, relies on the operating system to provide the implementation of any optional cipher suites.

## 2.2.37 [RFC3501] Section 11.2, Other Security Considerations

V0059:

The specification states: "A server SHOULD have mechanisms in place to limit or delay failed AUTHENTICATE/LOGIN attempts."

Microsoft® Exchange Server 2007, Microsoft® Exchange Server 2010, Microsoft® Exchange Server 15 Technical Preview

Microsoft® Exchange Server allows four failed attempts before it drops the session. However, Microsoft Exchange does not have any cross-session limits.

## 2.3 Error Handling

Unless otherwise specified in the previous sections, Microsoft® Exchange Server handles errors according to the following:

- Invalid property values and invalid parameter values are ignored.
- Invalid components are ignored.

## 2.4 Security

None.

### 3 Change Tracking

This section identifies changes that were made to the [MS-STANXIMAP] protocol document between the October 2011 and January 2012 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [protocol@microsoft.com](mailto:protocol@microsoft.com).

<b>Section</b>	<b>Tracking number (if applicable) and description</b>	<b>Major change (Y or N)</b>	<b>Change type</b>
<a href="#">1.3 Microsoft Implementations</a>	Added Exchange 15 Technical Preview to the list of Microsoft implementations.	Y	Content updated.



## 4 Index

[\[RFC2822\] Size Message Attribute](#) 9  
[8-bit and Binary Strings](#) 10

### A

[ABNF Rules in General](#) 7  
[APPEND Command](#) 16  
[AUTHENTICATE Command](#) 13  
[Autologout Timer](#) 11

### C

[CAPABILITY Response](#) 20  
[Change tracking](#) 23  
[CHECK Command](#) 16  
[Client Commands — Experimental/Expansion](#) 19  
[Client Commands — Not Authenticated State](#) 12  
[Client Protocol Sender and Server Protocol Receiver](#) 8  
[Combination of Mailbox Name - UIDVALIDITY - and UID MUST Refer to Single - Immutable message](#) 7  
[CREATE Command](#) 14

### D

[DELETE Command](#) 14

### E

[EXPUNGE Response](#) 20

### F

[FETCH Command](#) 18  
[FETCH Response](#) 20  
[Flags Message Attribute](#) 9  
[FLAGS Response](#) 20

### G

[Glossary](#) 5

### I

[Informative references](#) 6  
[Introduction](#) 5

### L

[LIST Command](#) 15  
[LIST Response](#) 20  
[LOGIN Command](#) 14  
[LSUB Command](#) 15

### M

[Mailbox Naming](#) 10

[Mailbox Size and Message Status Updates](#) 11  
[Multiple Commands in Progress](#) 12

### N

[Normative references](#) 5

### O

[OK Response](#) 19  
[Other Security Considerations](#) 22

### P

[Port 143](#) 7  
[PREAUTH Response](#) 19

### R

References  
[informative](#) 6  
[normative](#) 5  
[Response When No Command in Progress](#) 11  
[Rule Regarding Spaces](#) 8

### S

[SEARCH Command](#) 16  
[Server MUST Implement the TLS\\_RSA\\_WITH\\_RC4\\_128\\_MD5 Cipher Suite](#) 8  
[Server MUST Support STARTTLS - LOGINDISABLED - and AUTH=PLAIN Capabilities](#) 7  
[Server Protocol Sender and Client Protocol Receiver](#) 8  
[Server Responses – Command Continuation Request](#) 21  
[Server Responses – Status Responses](#) 19  
[STARTTLS Command](#) 13  
[STARTTLS Security Considerations](#) 21  
[STORE Command](#) 18  
[SUBSCRIBE Command](#) 15

### T

[Tracking changes](#) 23

### U

[Unique Identifier \(UID\) Message Attribute](#) 9  
[Unique Identifiers MUST NOT Change During Session](#) 7