

[MS-TMPLDISC]: Template Discovery Web Service Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
07/13/2009	0.1	Major	Initial Availability
08/28/2009	0.2	Editorial	Revised and edited the technical content
11/06/2009	0.3	Editorial	Revised and edited the technical content
02/19/2010	1.0	Minor	Updated the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Minor	Updated the technical content
06/07/2010	1.03	Editorial	Revised and edited the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	1.5	Minor	Clarified the meaning of the technical content.
04/11/2012	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
09/12/2012	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
02/11/2013	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
07/30/2013	1.5	No change	No changes to the meaning, language, or formatting of

Date	Revision History	Revision Class	Comments
			the technical content.
11/18/2013	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
02/10/2014	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
04/30/2014	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
07/31/2014	1.6	Minor	Clarified the meaning of the technical content.

Table of Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	6
1.2.1 Normative References	6
1.2.2 Informative References	7
1.3 Protocol Overview (Synopsis)	7
1.4 Relationship to Other Protocols	7
1.5 Prerequisites/Preconditions	8
1.6 Applicability Statement	8
1.7 Versioning and Capability Negotiation	8
1.8 Vendor-Extensible Fields	8
1.9 Standards Assignments	8
2 Messages	9
2.1 Transport	9
2.2 Common Message Syntax	9
2.2.1 Namespaces	9
2.2.2 Messages	9
2.2.3 Elements	9
2.2.4 Complex Types	9
2.2.4.1 ApplicationType	9
2.2.4.2 FeaturedContentType	10
2.2.4.3 FeaturedTemplatesType	10
2.2.4.4 FeaturedTemplateType	11
2.2.5 Simple Types	11
2.2.6 Attributes	11
2.2.7 Groups	11
2.2.8 Attribute Groups	11
3 Protocol Details	12
3.1 Server Details	12
3.1.1 Abstract Data Model	12
3.1.2 Timers	12
3.1.3 Initialization	12
3.1.4 Message Processing Events and Sequencing Rules	12
3.1.4.1 GetSpotlight.ashx	12
3.1.4.1.1 GetSpotlight	12
3.1.4.1.1.1 Return Values	13
3.1.5 Timer Events	13
3.1.6 Other Local Events	14
4 Protocol Examples	15
4.1 GetSpotlight.ashx	15
5 Security	16
5.1 Security Considerations for Implementers	16
5.2 Index of Security Parameters	16
6 Appendix A: Full WSDL	17
7 Appendix B: Product Behavior	18

8 Change Tracking.....	19
9 Index	21

1 Introduction

This document specifies the Template Discovery Web Service Protocol. It enables a protocol client to retrieve links to the **document templates** associated with a **document library** on a protocol server.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in [RFC2119]. Sections 1.5 and 1.9 are also normative but does not contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [MS-GLOS]:

Hypertext Transfer Protocol (HTTP)
Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)
language code identifier (LCID)
XML namespace

The following terms are defined in [MS-OFCGLOS]:

absolute URL
document library
document template
root folder
site-relative URL

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[RFC1123] Braden, R., "Requirements for Internet Hosts - Application and Support", STD 3, RFC 1123, October 1989, <http://www.ietf.org/rfc/rfc1123.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFGLS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

[MS-PLSP] Microsoft Corporation, "[Published Links Web Service Protocol](#)".

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

1.3 Protocol Overview (Synopsis)

This protocol enables a protocol client to retrieve links to the document templates associated with a document library on the protocol server. Once retrieved, these links can be used by the client to offer the document templates to the user as the basis for new documents suitable for storage in the document library.

1.4 Relationship to Other Protocols

This protocol uses **Hypertext Transfer Protocol (HTTP)**, as described in [\[RFC2616\]](#), or **Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**, as described in [\[RFC2818\]](#).

The following diagram shows the underlying messaging and transport stack used by the protocol:




Figure 1: This protocol in relation to other protocols

The Template Discovery Web Service can be used after the Published Links Web Service Protocol [\[MS-PLSP\]](#) has finished. A protocol client can use the Published Links Web Service Protocol to acquire URLs to document libraries that offer document templates. The client can then use the Template Discovery Web Service protocol to retrieve links to the templates from these document libraries.

1.5 Prerequisites/Preconditions

This protocol operates against a site that is identified by a URL that is known by the protocol client. The protocol server endpoint is formed by appending "/_layouts/GetSpotlight.ashx" to the URL of the site. For example, given the following site URL:

- <http://www.contoso.com/Repository>

The server endpoint would be:

- http://www.contoso.com/Repository/_layouts/GetSpotlight.ashx

In addition, to use this web service, the protocol client needs to have the name of a document library on the site. The Published Links Web Service Protocol [\[MS-PLSP\]](#) can be used to obtain this information.

1.6 Applicability Statement

This protocol is applicable for retrieving links to the document templates associated with a document library.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

This protocol uses HTTP version 1.1 (as specified in [\[RFC2616\]](#)) as transport for the GET methods. Protocol servers SHOULD additionally support HTTPS for securing communication with clients.

2.2 Common Message Syntax

This section contains common definitions used by this protocol. The syntax of the definitions uses **XML Schema** as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific prefix for each XML namespace that is used, the choice of any particular prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
o	urn:schemas-microsoft-com:office:office	
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1] [XMLSCHEMA2]

2.2.2 Messages

None.

2.2.3 Elements

This specification does not define any common XML Schema element definitions.

2.2.4 Complex Types

The following table summarizes the XML Schema complex types defined by this specification. XML Schema complex type definitions that are specific to a particular operation are described with the operation.

Complex Type	Description
ApplicationType	A set of templates of a particular class.
FeaturedContentType	A set of ApplicationType elements whose described templates are designed for a common LCID .
FeaturedTemplatesType	A set of FeaturedTemplateType elements.
FeaturedTemplateType	A specification of the properties and location of a single template.

2.2.4.1 ApplicationType

Specifies a set of templates of a particular class.

```

<xs:complexType name="ApplicationType">
  <xs:sequence>
    <xs:element name="featuredtemplates" type="o:FeaturedTemplatesType"/>
  </xs:sequence>
  <xs:attribute name="id" use="required">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="1"/>
        <xs:maxLength value="3"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
</xs:complexType>

```

featuredtemplates: A set of one or more templates belonging to the same class.

id: The class of the templates. [<1>](#)

2.2.4.2 FeaturedContentType

Specifies a set of **ApplicationType** elements whose described templates are designed for a common LCID.

```

<xs:complexType name="FeaturedContentType">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="application"
type="o:ApplicationType"/>
  </xs:sequence>
  <xs:attribute name="lcid" type="xs:int" use="required"/>
</xs:complexType>

```

application: A single **ApplicationType** element.

lcid: The LCID of the set.

2.2.4.3 FeaturedTemplatesType

Specifies a set of templates.

```

<xs:complexType name="FeaturedTemplatesType">
  <xs:sequence>
    <xs:element maxOccurs="unbounded" name="featuredtemplate" type="o:FeaturedTemplateType"/>
  </xs:sequence>
  <xs:attribute name="startdate" type="xs:date" use="required"/>
  <xs:attribute name="enddate" type="xs:date" use="required"/>
</xs:complexType>

```

featuredtemplate: A single template.

startdate: Date when this set of templates takes effect. Value MUST be set to the string "1901-01-01".

enddate: Date when this set of templates expires. Value MUST be set to the string "2201-01-01".

2.2.4.4 FeaturedTemplateType

Specifies the properties and location of a single template.

```
<xs:complexType name="FeaturedTemplateType">
  <xs:attribute name="source" type="xs:string" use="required"/>
  <xs:attribute name="lmod" type="xs:string" use="required"/>
  <xs:attribute name="savelocation" type="xs:string" use="required"/>
  <xs:attribute name="title" use="required">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="1"/>
        <xs:maxLength value="255"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
  <xs:attribute name="filename" use="required">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:minLength value="1"/>
        <xs:maxLength value="128"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
</xs:complexType>
```

source: The **absolute URL** of the template on the server.

lmod: Last modification date and time of the template (GMT), in the format defined by [RFC1123](#) section 5.2.14.

savelocation: The absolute URL of the document library on the server into which the server recommends that new documents created from this template be saved.

title: The title of the template.

filename: The file name of the template, including the file extension.

2.2.5 Simple Types

This specification does not define any common XML Schema simple type definitions.

2.2.6 Attributes

This specification does not define any common XML Schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML Schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML Schema attribute group definitions.

3 Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

3.1 Server Details

All operations consist of a basic HTTP request-response pair and the protocol server treats each request as an independent transaction, unrelated to any previous request.

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

The protocol server **MUST** maintain a mapping from document libraries to templates such that, for any document library, the server can retrieve the properties of all templates associated with the document library.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

This protocol includes a single operation:

Operation	Description
GetSpotlight.ashx	Gets an XML document describing document templates that can be used by client applications for creating new documents in the specified document library.

3.1.4.1 GetSpotlight.ashx

The methods in this section are supported by GetSpotlight.ashx.

3.1.4.1.1 GetSpotlight

This method gets an XML document describing document templates that can be used by client applications for creating new documents in the specified document library.

URL query parameters sent through the GET request:

Parameter	Value
ListName	Site-relative URL of the root folder of the document library.
app	The class of templates being requested. This parameter is optional. If specified, the protocol server MUST return information about all templates of the matching class and MUST NOT return information about templates belonging to other classes. When not specified, the protocol server SHOULD return information about all templates regardless of class. <2> If app is specified by an invalid class name that the server does not support, the server SHOULD return the status code 200 with an empty featuredContentType element in the XML document returned.
lidhelp	The LCID of the requested template language as a four-character hexadecimal string. The protocol server MUST return information only about templates designed for the specified LCID. When not specified the server SHOULD use the current culture LCID instead. If lidhelp is specified by an invalid LCID, the server SHOULD return status code 200 with an HTML web page reporting error, instead of the XML document.
liduser	The LCID of the client operating system as a four-character hexadecimal string. The protocol client MAY choose to specify this parameter but the protocol server MUST ignore it.
lidui	The LCID of the client application as a four-character hexadecimal string. The protocol client MAY choose to specify this parameter but the protocol server MUST ignore it.

3.1.4.1.1.1 Return Values

On success, an XML document described by the following schema is returned:

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:o="urn:schemas-microsoft-com:office:office"
  attributeFormDefault="unqualified"
  elementFormDefault="qualified"
  targetNamespace="urn:schemas-microsoft-com:office:office"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:element name="featuredcontent" type="o:FeaturedContentType">
  </xs:element>
</xs:schema>
```

featuredcontent: A **FeaturedContentType** element describing templates that are designed for the language specified by the **lidhelp** parameter in the request.

The returned HTTP status code **MUST** be one of the following:

Value	Description
200	Success.
400	Invalid or missing parameters.
401	Security not validated. The credentials supplied by the user are not valid.
500	Any other error.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

4.1 GetSpotlight.ashx

A protocol client could issue the following command to request a list of all templates from the "Routing Target" document library that were designed for LCID 0x0409 (en-US) and that were classed as "WD" templates:

```
http://site/dc/_layouts/GetSpotlight.ashx?lidhelp=0409&ListName=Routing%20Target&app=WD
```

The following example is sample XML that might be returned for this request. This XML specifies a single template located at "http://site/dc/Routing Target/Forms/template.dotx" whose preferred save location for new documents is "http://site/dc/Routing Target".

```
<?xml version="1.0" encoding="UTF-8"?>
<!--Office Server generated Spotlight XML-->
<o:featuredcontent lcid="1033" xmlns:o="urn:schemas-microsoft-com:office:office">
  <o:application id="WD">
    <o:featuredtemplates startdate="1901-01-01" enddate="2201-01-01">
      <o:featuredtemplate source="http://site/dc/Routing Target/Forms/template.dotx"
lmod="Mon, 27 Apr 2009 21:11:03 GMT" savelocation="http://site/dc/Routing Target"
title="Document" filename="template.dotx">
        </o:featuredtemplate>
      </o:featuredtemplates>
    </o:application>
  </o:featuredcontent>
```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Office 97
- Microsoft Office 2000
- Microsoft Office XP
- Microsoft Office 2003
- The 2007 Microsoft Office system
- Microsoft Office 2010 suites
- Microsoft Office 2013
- Microsoft SharePoint Server 2010
- Microsoft SharePoint Server 2013
- Microsoft Visio 2010
- Microsoft Visio 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2.4.1:](#) The SharePoint Server 2010 classifies all Word 97, Word 2000, Word 2002, Office Word 2003, Office Word 2007 and Word 2010 templates as "WD", all Excel 97, Excel 2000, Excel 2002, Office Excel 2003, Office Excel 2007 and Excel 2010 templates as "XL", all PowerPoint 97, PowerPoint 2000, PowerPoint 2002, Office PowerPoint 2003, Office PowerPoint 2007 and PowerPoint 2010 templates as "PP", and all Visio 2010 templates as "VO". It does not return any information about templates that do not belong to one of these four classes.

[<2> Section 3.1.4.1.1:](#) SharePoint Server 2010 and SharePoint Server 2013 only return information about templates classed as "WD", "XL", "PP", or "VO".

8 Change Tracking

This section identifies changes that were made to the [MS-TMPLDISC] protocol document between the April 2014 and July 2014 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.

- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
3.1.4.1.1 GetSpotlight	Added SharePoint Server 2013's behavior for returning information about all templates regardless of class.	N	Product behavior note updated.

9 Index

A

Abstract data model
[server](#) 12
[Applicability](#) 8
[ApplicationTypecomplex type](#) 9
[Attribute groups](#) 11
[Attributes](#) 11

C

[Capability negotiation](#) 8
[Change tracking](#) 19
Client
[overview](#) 12
[Complex types](#) 9
[ApplicationType](#) 9
[FeaturedContentType](#) 10
[FeaturedTemplatesType](#) 10
[FeaturedTemplateType](#) 11

D

Data model - abstract
[server](#) 12

E

Events
[local - server](#) 14
[timer - server](#) 13
Examples
[GetSpotlight.ashx](#) 15

F

[FeaturedContentTypecomplex type](#) 10
[FeaturedTemplatesTypecomplex type](#) 10
[FeaturedTemplateTypecomplex type](#) 11
[Fields - vendor-extensible](#) 8

G

[GetSpotlight.ashx example](#) 15
[Glossary](#) 6
[Groups](#) 11

I

[Implementer - security considerations](#) 16
[Index of security parameters](#) 16
[Informative references](#) 7
Initialization
[server](#) 12
[Introduction](#) 6

L

Local events
[server](#) 14

M

Message processing
[server](#) 12
Messages
[ApplicationTypecomplex type](#) 9
[attribute groups](#) 11
[attributes](#) 11
[complex types](#) 9
[elements](#) 9
[enumerated](#) 9
[FeaturedContentTypecomplex type](#) 10
[FeaturedTemplatesTypecomplex type](#) 10
[FeaturedTemplateTypecomplex type](#) 11
[groups](#) 11
[namespaces](#) 9
[simple types](#) 11
[syntax](#) 9
[transport](#) 9

N

[Namespaces](#) 9
[Normative references](#) 6

O

Operations
[GetSpotlight.ashx](#) 12
[Overview \(synopsis\)](#) 7

P

[Parameters - security index](#) 16
[Preconditions](#) 8
[Prerequisites](#) 8
[Product behavior](#) 18
Protocol Details
[overview](#) 12

R

[References](#) 6
[informative](#) 7
[normative](#) 6
[Relationship to other protocols](#) 7

S

Security
[implementer considerations](#) 16
[parameter index](#) 16
Sequencing rules
[server](#) 12
Server

- [abstract data model](#) 12
- [GetSpotlight.ashx operation](#) 12
- [initialization](#) 12
- [local events](#) 14
- [message processing](#) 12
- [overview](#) 12
- [sequencing rules](#) 12
- [timer events](#) 13
- [timers](#) 12
- [Server details](#) 12
- [Simple types](#) 11
- [Standards assignments](#) 8
- Syntax
 - [messages - overview](#) 9

T

- Timer events
 - [server](#) 13
- Timers
 - [server](#) 12
- [Tracking changes](#) 19
- [Transport](#) 9
- Types
 - [complex](#) 9
 - [simple](#) 11

V

- [Vendor-extensible fields](#) 8
- [Versioning](#) 8