

Preliminary

[MS-UPSDWS]: User Profile Social Data Web Service Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final

documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

Date	Revision History	Revision Class	Comments
07/13/2009	0.1	Major	Initial Availability
08/28/2009	0.2	Editorial	Revised and edited the technical content
11/06/2009	0.3	Editorial	Revised and edited the technical content
02/19/2010	1.0	Major	Updated and revised the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Editorial	Revised and edited the technical content
06/07/2010	1.03	Editorial	Revised and edited the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.05	Major	Significantly changed the technical content.
09/27/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	2.0	Major	Significantly changed the technical content.
04/11/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1.1	Glossary	15
1.2	References.....	16
1.2.1	Normative References.....	16
1.2.2	Informative References.....	16
1.3	Protocol Overview (Synopsis).....	17
1.4	Relationship to Other Protocols.....	17
1.5	Prerequisites/Preconditions	17
1.6	Applicability Statement.....	17
1.7	Versioning and Capability Negotiation.....	17
1.8	Vendor-Extensible Fields.....	18
1.9	Standards Assignments	18
2	Messages.....	19
2.1	Transport.....	19
2.2	Common Message Syntax	19
2.2.1	Namespaces	19
2.2.2	Messages	19
2.2.3	Elements.....	20
2.2.4	Complex Types	20
2.2.4.1	ArrayOfDeletedSocialCommentDetail.....	21
2.2.4.2	ArrayOfDeletedSocialRatingDetail	21
2.2.4.3	ArrayOfDeletedSocialTagDetail	22
2.2.4.4	ArrayOfSocialCommentDetail	22
2.2.4.5	ArrayOfSocialRatingDetail	22
2.2.4.6	ArrayOfSocialTagDetail.....	23
2.2.4.7	ArrayOfSocialTermDetail.....	23
2.2.4.8	ArrayOfSocialUrlDetail	23
2.2.4.9	ArrayOfString.....	24
2.2.4.10	DeletedSocialCommentDetail.....	24
2.2.4.11	DeletedSocialDataDetail.....	24
2.2.4.12	DeletedSocialRatingDetail	25
2.2.4.13	DeletedSocialTagDetail	25
2.2.4.14	SocialCommentDetail	25
2.2.4.15	SocialDataDetail	26
2.2.4.16	SocialRatingDetail	26
2.2.4.17	SocialReplicationData	26
2.2.4.18	SocialTagDetail.....	27
2.2.4.19	SocialTermDetail.....	28
2.2.4.20	SocialUrlDetail	28
2.2.4.21	TermDetail.....	28
2.2.5	Simple Types.....	29
2.2.5.1	guid.....	29
2.2.6	Attributes.....	29
2.2.7	Groups.....	29
2.2.8	Attribute Groups	29
2.2.9	Common Data Structures	29
3	Protocol Details.....	30
3.1	Server Details	30
3.1.1	Abstract Data Model	30
3.1.1.1	Social Tags	30
3.1.1.2	Notes (Social Comments)	30
3.1.1.3	Ratings.....	31

3.1.2	Timers	31
3.1.3	Initialization	31
3.1.4	Message Processing Events and Sequencing Rules	31
3.1.4.1	AddComment	34
3.1.4.1.1	Messages	34
3.1.4.1.1.1	AddCommentSoapIn	34
3.1.4.1.1.2	AddCommentSoapOut	34
3.1.4.1.2	Elements	34
3.1.4.1.2.1	AddComment	35
3.1.4.1.2.2	AddCommentResponse	35
3.1.4.1.3	Complex Types	35
3.1.4.1.4	Simple Types	36
3.1.4.1.5	Attributes	36
3.1.4.1.6	Groups	36
3.1.4.1.7	Attribute Groups	36
3.1.4.2	AddTag	36
3.1.4.2.1	Messages	36
3.1.4.2.1.1	AddTagSoapIn	36
3.1.4.2.1.2	AddTagSoapOut	37
3.1.4.2.2	Elements	37
3.1.4.2.2.1	AddTag	37
3.1.4.2.2.2	AddTagResponse	37
3.1.4.2.3	Complex Types	38
3.1.4.2.4	Simple Types	38
3.1.4.2.5	Attributes	38
3.1.4.2.6	Groups	38
3.1.4.2.7	Attribute Groups	38
3.1.4.3	AddTagByKeyword	38
3.1.4.3.1	Messages	39
3.1.4.3.1.1	AddTagByKeywordSoapIn	39
3.1.4.3.1.2	AddTagByKeywordSoapOut	39
3.1.4.3.2	Elements	39
3.1.4.3.2.1	AddTagByKeyword	39
3.1.4.3.2.2	AddTagByKeywordResponse	40
3.1.4.3.3	Complex Types	40
3.1.4.3.4	Simple Types	40
3.1.4.3.5	Attributes	40
3.1.4.3.6	Groups	40
3.1.4.3.7	Attribute Groups	40
3.1.4.4	CountCommentsOfUser	41
3.1.4.4.1	Messages	41
3.1.4.4.1.1	CountCommentsOfUserSoapIn	41
3.1.4.4.1.2	CountCommentsOfUserSoapOut	41
3.1.4.4.2	Elements	41
3.1.4.4.2.1	CountCommentsOfUser	42
3.1.4.4.2.2	CountCommentsOfUserResponse	42
3.1.4.4.3	Complex Types	42
3.1.4.4.4	Simple Types	42
3.1.4.4.5	Attributes	42
3.1.4.4.6	Groups	43
3.1.4.4.7	Attribute Groups	43
3.1.4.5	CountCommentsOfUserOnUrl	43
3.1.4.5.1	Messages	43

3.1.4.5.1.1	CountCommentsOfUserOnUrlSoapIn	43
3.1.4.5.1.2	CountCommentsOfUserOnUrlSoapOut	43
3.1.4.5.2	Elements.....	44
3.1.4.5.2.1	CountCommentsOfUserOnUrl	44
3.1.4.5.2.2	CountCommentsOfUserOnUrlResponse	44
3.1.4.5.3	Complex Types	45
3.1.4.5.4	Simple Types.....	45
3.1.4.5.5	Attributes.....	45
3.1.4.5.6	Groups.....	45
3.1.4.5.7	Attribute Groups	45
3.1.4.6	CountCommentsOnUrl.....	45
3.1.4.6.1	Messages	45
3.1.4.6.1.1	CountCommentsOnUrlSoapIn	45
3.1.4.6.1.2	CountCommentsOnUrlSoapOut.....	46
3.1.4.6.2	Elements.....	46
3.1.4.6.2.1	CountCommentsOnUrl.....	46
3.1.4.6.2.2	CountCommentsOnUrlResponse	46
3.1.4.6.3	Complex Types	47
3.1.4.6.4	Simple Types.....	47
3.1.4.6.5	Attributes.....	47
3.1.4.6.6	Groups.....	47
3.1.4.6.7	Attribute Groups	47
3.1.4.7	CountRatingsOnUrl	47
3.1.4.7.1	Messages	47
3.1.4.7.1.1	CountRatingsOnUrlSoapIn	47
3.1.4.7.1.2	CountRatingsOnUrlSoapOut	48
3.1.4.7.2	Elements.....	48
3.1.4.7.2.1	CountRatingsOnUrl	48
3.1.4.7.2.2	CountRatingsOnUrlResponse	48
3.1.4.7.3	Complex Types	49
3.1.4.7.4	Simple Types.....	49
3.1.4.7.5	Attributes.....	49
3.1.4.7.6	Groups.....	49
3.1.4.7.7	Attribute Groups	49
3.1.4.8	CountTagsOfUser.....	49
3.1.4.8.1	Messages	49
3.1.4.8.1.1	CountTagsOfUserSoapIn.....	50
3.1.4.8.1.2	CountTagsOfUserSoapOut.....	50
3.1.4.8.2	Elements.....	50
3.1.4.8.2.1	CountTagsOfUser.....	50
3.1.4.8.2.2	CountTagsOfUserResponse	50
3.1.4.8.3	Complex Types	51
3.1.4.8.4	Simple Types.....	51
3.1.4.8.5	Attributes.....	51
3.1.4.8.6	Groups.....	51
3.1.4.8.7	Attribute Groups	51
3.1.4.9	DeleteComment	51
3.1.4.9.1	Messages	51
3.1.4.9.1.1	DeleteCommentSoapIn	52
3.1.4.9.1.2	DeleteCommentSoapOut	52
3.1.4.9.2	Elements.....	52
3.1.4.9.2.1	DeleteComment	52
3.1.4.9.2.2	DeleteCommentResponse	53

3.1.4.9.3	Complex Types	53
3.1.4.9.4	Simple Types.....	53
3.1.4.9.5	Attributes.....	53
3.1.4.9.6	Groups.....	53
3.1.4.9.7	Attribute Groups	53
3.1.4.10	DeleteRating	53
3.1.4.10.1	Messages	53
3.1.4.10.1.1	DeleteRatingSoapIn	54
3.1.4.10.1.2	DeleteRatingSoapOut	54
3.1.4.10.2	Elements	54
3.1.4.10.2.1	DeleteRating	54
3.1.4.10.2.2	DeleteRatingResponse	54
3.1.4.10.3	Complex Types	55
3.1.4.10.4	Simple Types	55
3.1.4.10.5	Attributes	55
3.1.4.10.6	Groups.....	55
3.1.4.10.7	Attribute Groups.....	55
3.1.4.11	DeleteTag	55
3.1.4.11.1	Messages	55
3.1.4.11.1.1	DeleteTagSoapIn	56
3.1.4.11.1.2	DeleteTagSoapOut	56
3.1.4.11.2	Elements	56
3.1.4.11.2.1	DeleteTag	56
3.1.4.11.2.2	DeleteTagResponse	57
3.1.4.11.3	Complex Types	57
3.1.4.11.4	Simple Types	57
3.1.4.11.5	Attributes	57
3.1.4.11.6	Groups.....	57
3.1.4.11.7	Attribute Groups.....	57
3.1.4.12	DeleteTagByKeyword	57
3.1.4.12.1	Messages	57
3.1.4.12.1.1	DeleteTagByKeywordSoapIn	58
3.1.4.12.1.2	DeleteTagByKeywordSoapOut	58
3.1.4.12.2	Elements	58
3.1.4.12.2.1	DeleteTagByKeyword	58
3.1.4.12.2.2	DeleteTagByKeywordResponse	59
3.1.4.12.3	Complex Types	59
3.1.4.12.4	Simple Types	59
3.1.4.12.5	Attributes	59
3.1.4.12.6	Groups.....	59
3.1.4.12.7	Attribute Groups.....	59
3.1.4.13	DeleteTags.....	59
3.1.4.13.1	Messages	60
3.1.4.13.1.1	DeleteTagsSoapIn.....	60
3.1.4.13.1.2	DeleteTagsSoapOut.....	60
3.1.4.13.2	Elements	60
3.1.4.13.2.1	DeleteTags.....	60
3.1.4.13.2.2	DeleteTagsResponse	61
3.1.4.13.3	Complex Types	61
3.1.4.13.4	Simple Types	61
3.1.4.13.5	Attributes	61
3.1.4.13.6	Groups.....	61
3.1.4.13.7	Attribute Groups.....	61

3.1.4.14	GetAllTagTerms	61
3.1.4.14.1	Messages	61
3.1.4.14.1.1	GetAllTagTermsSoapIn	62
3.1.4.14.1.2	GetAllTagTermsSoapOut	62
3.1.4.14.2	Elements	62
3.1.4.14.2.1	GetAllTagTerms	62
3.1.4.14.2.2	GetAllTagTermsResponse	62
3.1.4.14.3	Complex Types	63
3.1.4.14.4	Simple Types	63
3.1.4.14.5	Attributes	63
3.1.4.14.6	Groups	63
3.1.4.14.7	Attribute Groups	63
3.1.4.15	GetAllTagTermsForUrlFolder	63
3.1.4.15.1	Messages	63
3.1.4.15.1.1	GetAllTagTermsForUrlFolderSoapIn	64
3.1.4.15.1.2	GetAllTagTermsForUrlFolderSoapOut	64
3.1.4.15.2	Elements	64
3.1.4.15.2.1	GetAllTagTermsForUrlFolder	64
3.1.4.15.2.2	GetAllTagTermsForUrlFolderResponse	65
3.1.4.15.3	Complex Types	65
3.1.4.15.4	Simple Types	65
3.1.4.15.5	Attributes	65
3.1.4.15.6	Groups	65
3.1.4.15.7	Attribute Groups	65
3.1.4.16	GetAllTagUrls	65
3.1.4.16.1	Messages	66
3.1.4.16.1.1	GetAllTagUrlsSoapIn	66
3.1.4.16.1.2	GetAllTagUrlsSoapOut	66
3.1.4.16.2	Elements	66
3.1.4.16.2.1	GetAllTagUrls	66
3.1.4.16.2.2	GetAllTagUrlsResponse	67
3.1.4.16.3	Complex Types	67
3.1.4.16.4	Simple Types	67
3.1.4.16.5	Attributes	67
3.1.4.16.6	Groups	67
3.1.4.16.7	Attribute Groups	67
3.1.4.17	GetAllTagUrlsByKeyword	67
3.1.4.17.1	Messages	68
3.1.4.17.1.1	GetAllTagUrlsByKeywordSoapIn	68
3.1.4.17.1.2	GetAllTagUrlsByKeywordSoapOut	68
3.1.4.17.2	Elements	68
3.1.4.17.2.1	GetAllTagUrlsByKeyword	68
3.1.4.17.2.2	GetAllTagUrlsByKeywordResponse	69
3.1.4.17.3	Complex Types	69
3.1.4.17.4	Simple Types	69
3.1.4.17.5	Attributes	69
3.1.4.17.6	Groups	69
3.1.4.17.7	Attribute Groups	69
3.1.4.18	GetCommentsOfUser	70
3.1.4.18.1	Messages	70
3.1.4.18.1.1	GetCommentsOfUserSoapIn	70
3.1.4.18.1.2	GetCommentsOfUserSoapOut	70
3.1.4.18.2	Elements	70

3.1.4.18.2.1	GetCommentsOfUser.....	71
3.1.4.18.2.2	GetCommentsOfUserResponse	71
3.1.4.18.3	Complex Types	72
3.1.4.18.4	Simple Types	72
3.1.4.18.5	Attributes	72
3.1.4.18.6	Groups.....	72
3.1.4.18.7	Attribute Groups.....	72
3.1.4.19	GetCommentsOfUserOnUrl	72
3.1.4.19.1	Messages	72
3.1.4.19.1.1	GetCommentsOfUserOnUrlSoapIn	72
3.1.4.19.1.2	GetCommentsOfUserOnUrlSoapOut.....	73
3.1.4.19.2	Elements.....	73
3.1.4.19.2.1	GetCommentsOfUserOnUrl.....	73
3.1.4.19.2.2	GetCommentsOfUserOnUrlResponse	73
3.1.4.19.3	Complex Types	74
3.1.4.19.4	Simple Types	74
3.1.4.19.5	Attributes.....	74
3.1.4.19.6	Groups.....	74
3.1.4.19.7	Attribute Groups.....	74
3.1.4.20	GetCommentsOnUrl	74
3.1.4.20.1	Messages	74
3.1.4.20.1.1	GetCommentsOnUrlSoapIn	75
3.1.4.20.1.2	GetCommentsOnUrlSoapOut	75
3.1.4.20.2	Elements.....	75
3.1.4.20.2.1	GetCommentsOnUrl	75
3.1.4.20.2.2	GetCommentsOnUrlResponse.....	76
3.1.4.20.3	Complex Types	76
3.1.4.20.4	Simple Types	76
3.1.4.20.5	Attributes.....	76
3.1.4.20.6	Groups.....	76
3.1.4.20.7	Attribute Groups.....	77
3.1.4.21	GetRatingAverageOnUrl.....	77
3.1.4.21.1	Messages	77
3.1.4.21.1.1	GetRatingAverageOnUrlSoapIn	77
3.1.4.21.1.2	GetRatingAverageOnUrlSoapOut.....	77
3.1.4.21.2	Elements.....	78
3.1.4.21.2.1	GetRatingAverageOnUrl.....	78
3.1.4.21.2.2	GetRatingAverageOnUrlResponse.....	78
3.1.4.21.3	Complex Types	79
3.1.4.21.3.1	SocialRatingAverageDetail	79
3.1.4.21.4	Simple Types	79
3.1.4.21.5	Attributes.....	79
3.1.4.21.6	Groups.....	80
3.1.4.21.7	Attribute Groups.....	80
3.1.4.22	GetRatingOfUserOnUrl	80
3.1.4.22.1	Messages	80
3.1.4.22.1.1	GetRatingOfUserOnUrlSoapIn	80
3.1.4.22.1.2	GetRatingOfUserOnUrlSoapOut.....	81
3.1.4.22.2	Elements.....	81
3.1.4.22.2.1	GetRatingOfUserOnUrl.....	81
3.1.4.22.2.2	GetRatingOfUserOnUrlResponse	81
3.1.4.22.3	Complex Types	82
3.1.4.22.4	Simple Types	82

3.1.4.22.5	Attributes	82
3.1.4.22.6	Groups.....	82
3.1.4.22.7	Attribute Groups.....	82
3.1.4.23	GetRatingOnUrl	82
3.1.4.23.1	Messages	82
3.1.4.23.1.1	GetRatingOnUrlSoapIn	83
3.1.4.23.1.2	GetRatingOnUrlSoapOut	83
3.1.4.23.2	Elements.....	83
3.1.4.23.2.1	GetRatingOnUrl	83
3.1.4.23.2.2	GetRatingOnUrlResponse	83
3.1.4.23.3	Complex Types	84
3.1.4.23.4	Simple Types	84
3.1.4.23.5	Attributes	84
3.1.4.23.6	Groups.....	84
3.1.4.23.7	Attribute Groups.....	84
3.1.4.24	GetRatingsOfUser	84
3.1.4.24.1	Messages	84
3.1.4.24.1.1	GetRatingsOfUserSoapIn	85
3.1.4.24.1.2	GetRatingsOfUserSoapOut	85
3.1.4.24.2	Elements.....	85
3.1.4.24.2.1	GetRatingsOfUser	85
3.1.4.24.2.2	GetRatingsOfUserResponse	85
3.1.4.24.3	Complex Types	86
3.1.4.24.4	Simple Types	86
3.1.4.24.5	Attributes	86
3.1.4.24.6	Groups.....	86
3.1.4.24.7	Attribute Groups.....	86
3.1.4.25	GetRatingsOnUrl	86
3.1.4.25.1	Messages	86
3.1.4.25.1.1	GetRatingsOnUrlSoapIn	87
3.1.4.25.1.2	GetRatingsOnUrlSoapOut	87
3.1.4.25.2	Elements.....	87
3.1.4.25.2.1	GetRatingsOnUrl	87
3.1.4.25.2.2	GetRatingsOnUrlResponse.....	87
3.1.4.25.3	Complex Types	88
3.1.4.25.4	Simple Types	88
3.1.4.25.5	Attributes	88
3.1.4.25.6	Groups.....	88
3.1.4.25.7	Attribute Groups.....	88
3.1.4.26	GetSocialDataForFullReplication	88
3.1.4.26.1	Messages	89
3.1.4.26.1.1	GetSocialDataForFullReplicationSoapIn	89
3.1.4.26.1.2	GetSocialDataForFullReplicationSoapOut.....	89
3.1.4.26.2	Elements.....	89
3.1.4.26.2.1	GetSocialDataForFullReplication	89
3.1.4.26.2.2	GetSocialDataForFullReplicationResponse	90
3.1.4.26.3	Complex Types	90
3.1.4.26.4	Simple Types	90
3.1.4.26.5	Attributes	90
3.1.4.26.6	Groups.....	90
3.1.4.26.7	Attribute Groups.....	90
3.1.4.27	GetSocialDataForIncrementalReplication	90
3.1.4.27.1	Messages	91

3.1.4.27.1.1	GetSocialDataForIncrementalReplicationSoapIn	91
3.1.4.27.1.2	GetSocialDataForIncrementalReplicationSoapOut	91
3.1.4.27.2	Elements	91
3.1.4.27.2.1	GetSocialDataForIncrementalReplication	92
3.1.4.27.2.2	GetSocialDataForIncrementalReplicationResponse	92
3.1.4.27.3	Complex Types	92
3.1.4.27.4	Simple Types	93
3.1.4.27.5	Attributes	93
3.1.4.27.6	Groups	93
3.1.4.27.7	Attribute Groups	93
3.1.4.28	GetTags	93
3.1.4.28.1	Messages	93
3.1.4.28.1.1	GetTagsSoapIn	93
3.1.4.28.1.2	GetTagsSoapOut	94
3.1.4.28.2	Elements	94
3.1.4.28.2.1	GetTags	94
3.1.4.28.2.2	GetTagsResponse	94
3.1.4.28.3	Complex Types	94
3.1.4.28.4	Simple Types	95
3.1.4.28.5	Attributes	95
3.1.4.28.6	Groups	95
3.1.4.28.7	Attribute Groups	95
3.1.4.29	GetTagsOfUser	95
3.1.4.29.1	Messages	95
3.1.4.29.1.1	GetTagsOfUserSoapIn	95
3.1.4.29.1.2	GetTagsOfUserSoapOut	96
3.1.4.29.2	Elements	96
3.1.4.29.2.1	GetTagsOfUser	96
3.1.4.29.2.2	GetTagsOfUserResponse	96
3.1.4.29.3	Complex Types	97
3.1.4.29.4	Simple Types	97
3.1.4.29.5	Attributes	97
3.1.4.29.6	Groups	97
3.1.4.29.7	Attribute Groups	97
3.1.4.30	GetTagTerms	97
3.1.4.30.1	Messages	97
3.1.4.30.1.1	GetTagTermsSoapIn	98
3.1.4.30.1.2	GetTagTermsSoapOut	98
3.1.4.30.2	Elements	98
3.1.4.30.2.1	GetTagTerms	98
3.1.4.30.2.2	GetTagTermsResponse	99
3.1.4.30.3	Complex Types	99
3.1.4.30.4	Simple Types	99
3.1.4.30.5	Attributes	99
3.1.4.30.6	Groups	99
3.1.4.30.7	Attribute Groups	99
3.1.4.31	GetTagTermsOfUser	99
3.1.4.31.1	Messages	100
3.1.4.31.1.1	GetTagTermsOfUserSoapIn	100
3.1.4.31.1.2	GetTagTermsOfUserSoapOut	100
3.1.4.31.2	Elements	100
3.1.4.31.2.1	GetTagTermsOfUser	100
3.1.4.31.2.2	GetTagTermsOfUserResponse	101

3.1.4.31.3	Complex Types	101
3.1.4.31.4	Simple Types	101
3.1.4.31.5	Attributes	101
3.1.4.31.6	Groups	101
3.1.4.31.7	Attribute Groups	102
3.1.4.32	GetTagTermsOnUrl	102
3.1.4.32.1	Messages	102
3.1.4.32.1.1	GetTagTermsOnUrlSoapIn	102
3.1.4.32.1.2	GetTagTermsOnUrlSoapOut	102
3.1.4.32.2	Elements	102
3.1.4.32.2.1	GetTagTermsOnUrl	103
3.1.4.32.2.2	GetTagTermsOnUrlResponse	103
3.1.4.32.3	Complex Types	103
3.1.4.32.4	Simple Types	103
3.1.4.32.5	Attributes	104
3.1.4.32.6	Groups	104
3.1.4.32.7	Attribute Groups	104
3.1.4.33	GetTagUrls	104
3.1.4.33.1	Messages	104
3.1.4.33.1.1	GetTagUrlsSoapIn	104
3.1.4.33.1.2	GetTagUrlsSoapOut	104
3.1.4.33.2	Elements	105
3.1.4.33.2.1	GetTagUrls	105
3.1.4.33.2.2	GetTagUrlsResponse	105
3.1.4.33.3	Complex Types	105
3.1.4.33.4	Simple Types	105
3.1.4.33.5	Attributes	106
3.1.4.33.6	Groups	106
3.1.4.33.7	Attribute Groups	106
3.1.4.34	GetTagUrlsByKeyword	106
3.1.4.34.1	Messages	106
3.1.4.34.1.1	GetTagUrlsByKeywordSoapIn	106
3.1.4.34.1.2	GetTagUrlsByKeywordSoapOut	106
3.1.4.34.2	Elements	107
3.1.4.34.2.1	GetTagUrlsByKeyword	107
3.1.4.34.2.2	GetTagUrlsByKeywordResponse	107
3.1.4.34.3	Complex Types	107
3.1.4.34.4	Simple Types	108
3.1.4.34.5	Attributes	108
3.1.4.34.6	Groups	108
3.1.4.34.7	Attribute Groups	108
3.1.4.35	GetTagUrlsOfUser	108
3.1.4.35.1	Messages	108
3.1.4.35.1.1	GetTagUrlsOfUserSoapIn	108
3.1.4.35.1.2	GetTagUrlsOfUserSoapOut	109
3.1.4.35.2	Elements	109
3.1.4.35.2.1	GetTagUrlsOfUser	109
3.1.4.35.2.2	GetTagUrlsOfUserResponse	109
3.1.4.35.3	Complex Types	110
3.1.4.35.4	Simple Types	110
3.1.4.35.5	Attributes	110
3.1.4.35.6	Groups	110
3.1.4.35.7	Attribute Groups	110

3.1.4.36	GetTagUrlsOfUserByKeyword.....	110
3.1.4.36.1	Messages	110
3.1.4.36.1.1	GetTagUrlsOfUserByKeywordSoapIn.....	111
3.1.4.36.1.2	GetTagUrlsOfUserByKeywordSoapOut	111
3.1.4.36.2	Elements	111
3.1.4.36.2.1	GetTagUrlsOfUserByKeyword	111
3.1.4.36.2.2	GetTagUrlsOfUserByKeywordResponse	112
3.1.4.36.3	Complex Types	112
3.1.4.36.4	Simple Types	112
3.1.4.36.5	Attributes	112
3.1.4.36.6	Groups.....	112
3.1.4.36.7	Attribute Groups.....	112
3.1.4.37	PropagateRating	112
3.1.4.37.1	Messages	113
3.1.4.37.1.1	PropagateRatingSoapIn	113
3.1.4.37.1.2	PropagateRatingSoapOut	113
3.1.4.37.2	Elements	113
3.1.4.37.2.1	PropagateRating	113
3.1.4.37.2.2	PropagateRatingResponse.....	114
3.1.4.37.3	Complex Types	114
3.1.4.37.4	Simple Types	114
3.1.4.37.5	Attributes	114
3.1.4.37.6	Groups.....	114
3.1.4.37.7	Attribute Groups.....	114
3.1.4.38	ReplicateFullSocialData.....	114
3.1.4.38.1	Messages	114
3.1.4.38.1.1	ReplicateFullSocialDataSoapIn.....	115
3.1.4.38.1.2	ReplicateFullSocialDataSoapOut.....	115
3.1.4.38.2	Elements	115
3.1.4.38.2.1	ReplicateFullSocialData.....	115
3.1.4.38.2.2	ReplicateFullSocialDataResponse	116
3.1.4.38.3	Complex Types	116
3.1.4.38.4	Simple Types	116
3.1.4.38.5	Attributes	116
3.1.4.38.6	Groups.....	116
3.1.4.38.7	Attribute Groups.....	116
3.1.4.39	ReplicateIncrementalSocialData.....	116
3.1.4.39.1	Messages	117
3.1.4.39.1.1	ReplicateIncrementalSocialDataSoapIn.....	117
3.1.4.39.1.2	ReplicateIncrementalSocialDataSoapOut.....	117
3.1.4.39.2	Elements	117
3.1.4.39.2.1	ReplicateIncrementalSocialData.....	118
3.1.4.39.2.2	ReplicateIncrementalSocialDataResponse	118
3.1.4.39.3	Complex Types	118
3.1.4.39.4	Simple Types	118
3.1.4.39.5	Attributes	118
3.1.4.39.6	Groups.....	118
3.1.4.39.7	Attribute Groups.....	119
3.1.4.40	SetRating.....	119
3.1.4.40.1	Messages	119
3.1.4.40.1.1	SetRatingSoapIn.....	119
3.1.4.40.1.2	SetRatingSoapOut	119
3.1.4.40.2	Elements.....	119

3.1.4.40.2.1	SetRating	120
3.1.4.40.2.2	SetRatingResponse	120
3.1.4.40.3	Complex Types	120
3.1.4.40.3.1	FeedbackData	121
3.1.4.40.4	Simple Types	122
3.1.4.40.5	Attributes	122
3.1.4.40.6	Groups.....	122
3.1.4.40.7	Attribute Groups.....	123
3.1.4.41	UpdateComment.....	123
3.1.4.41.1	Messages	123
3.1.4.41.1.1	UpdateCommentSoapIn.....	123
3.1.4.41.1.2	UpdateCommentSoapOut.....	123
3.1.4.41.2	Elements.....	123
3.1.4.41.2.1	UpdateComment.....	124
3.1.4.41.2.2	UpdateCommentResponse	124
3.1.4.41.3	Complex Types	124
3.1.4.41.4	Simple Types	125
3.1.4.41.5	Attributes	125
3.1.4.41.6	Groups.....	125
3.1.4.41.7	Attribute Groups.....	125
3.1.5	Timer Events	125
3.1.6	Other Local Events	125
4	Protocol Examples.....	126
4.1	Add Social Data to a URI	126
4.2	View Social Data Comments.....	127
4.3	Delete Social Data Comments	130
4.4	Find Social Data Tags.....	130
4.5	Delete Social Data Tags.....	132
4.6	Add Social Ratings to a URI.....	132
4.7	Find Information about Social Ratings	133
4.8	Delete Social Ratings.....	136
5	Security.....	137
5.1	Security Considerations for Implementers.....	137
5.2	Index of Security Parameters	137
6	Appendix A: Full WSDL	138
7	Appendix B: Product Behavior	177
8	Change Tracking.....	178
9	Index	179

1 Introduction

This document specifies the User Profile Social Data Web Service Protocol, which is used to add, remove, and retrieve user-provided data that facilitates social networking. These data are in the form of tags, notes, and ratings about documents, Web pages, and other types of items that are stored on a protocol server.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also

normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Hypertext Transfer Protocol (HTTP)
Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)

The following terms are defined in [\[MS-OFCGLOS\]](#):

back-end database server
content database
current user
document
field
Hypertext Markup Language (HTML)
list item
Simple Object Access Protocol (SOAP)
site
SOAP action
SOAP body
SOAP fault
social comment
social data
social rating
social tag
term
term store
timestamp
Uniform Resource Identifier (URI)
Uniform Resource Locator (URL)
user profile
Web Services Description Language (WSDL)
WSDL message
WSDL operation
XML namespace
XML namespace prefix
XML schema

The following terms are specific to this document:

social tag term: A user-defined keyword for a Web page or item on a SharePoint site or the Internet. Individual users create social tags and, by default, share them with other users.

social tag URL: The address of a Web page or item on a SharePoint site or the Internet for which a user created a social tag.

social tag user: The user who created a social tag.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP1.2/1] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>

[SOAP1.2/2] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 2: Adjuncts", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part2-20030624>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

1.3 Protocol Overview (Synopsis)

This protocol allows a protocol client to add, remove, and retrieve **social tags**, **social comments**, and **social ratings** for **documents**, Web pages, and other types of items that are stored on a protocol server. This protocol allows the protocol client to pass criteria to the protocol server and to receive a list of social tags, social comments, and social ratings.

A typical scenario for using this protocol is a social networking application. A social tag is a descriptive term that a user assigns to the content at a **URI**. A social comment is a textual note that a user adds to a document or Web page. A social rating is a user's assessment, from one to five stars, of the quality of a document or list item. An application can use this protocol to add, remove, and retrieve social tags, social comments, and social ratings.

1.4 Relationship to Other Protocols

This protocol uses the **SOAP** message protocol for formatting request and response messages, as described in [\[SOAP1.1\]](#), [\[SOAP1.2/1\]](#) and [\[SOAP1.2/2\]](#). It transmits those messages by using **HTTP**, as described in [\[RFC2616\]](#), or **HTTPS**, as described in [\[RFC2818\]](#).

The following diagram shows the underlying messaging and transport stack used by the protocol:




Figure 1: This protocol in relation to other protocols

1.5 Prerequisites/Preconditions

This protocol operates against a **site (2)** that is identified by a URL that is known by protocol clients. The protocol server endpoint is formed by appending "_vti_bin/socialdataservice.asmx" to the URL of the site, for example http://www.example.com/Repository/_vti_bin/socialdataservice.asmx.

This protocol assumes that authentication has been performed by the underlying protocols.

1.6 Applicability Statement

This protocol was designed to support a scale point of approximately 2 million user profiles and an average of 500 social tags, 300 social comments, and 300 social ratings across all of those user profiles.

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Supported Transports:** This protocol can be implemented by using transports that support sending Simple Object Access Protocol (SOAP) messages, as specified in section 2.1.
- **Protocol Versions:** This protocol is not versioned.
- **Capability Negotiation:** This protocol does not support version negotiation.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

Preliminary

2 Messages

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The **WSDL** in this specification matches the WSDL that shipped with the product and provides a base description of the schema. The text that introduces the WSDL might specify differences that reflect actual Microsoft product behavior. For example, the schema definition might allow for an element to be **empty**, **null**, or **not present** but the behavior of the protocol as specified restricts the same elements to being **non-empty**, **present**, and **not null**.

2.1 Transport

Protocol servers **MUST** support SOAP over HTTP. Protocol servers **SHOULD** additionally support SOAP over HTTPS to help secure communications with protocol clients.

Protocol messages **MUST** be formatted as specified in either [\[SOAP1.1\]](#) section 4 or [\[SOAP1.2/1\]](#) section 5. Server faults **MUST** be returned by using either HTTP status codes, as specified in [\[RFC2616\]](#) section 10, or **SOAP faults**, as specified in [\[SOAP1.1\]](#) section 4.4 or [\[SOAP1.2/1\]](#) section 5.4.

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and WSDL, as specified in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific **XML namespace prefix** for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
http	http://schemas.xmlsoap.org/wsdl/http/	
s1	http://microsoft.com/wsdl/types/	
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
soap12	http://schemas.xmlsoap.org/wsdl/soap12/	[SOAP1.2/1] [SOAP1.2/2]
tns	http://microsoft.com/webservices/SharePointPortalServer/SocialDataService	
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1] [XMLSCHEMA2]

2.2.2 Messages

This specification does not define any common WSDL message definitions.

2.2.3 Elements

This specification does not define any common XML schema element definitions.

2.2.4 Complex Types

The following table summarizes the set of common XML schema complex type definitions defined by this specification. XML schema complex type definitions that are specific to a particular operation are described with the operation.

Complex Type	Description
ArrayOfDeletedSocialCommentDetail	The ArrayOfDeletedSocialCommentDetail complex type contains zero or more DeletedSocialCommentDetail elements.
ArrayOfDeletedSocialRatingDetail	The ArrayOfDeletedSocialRatingDetail complex type contains zero or more DeletedSocialRatingDetail elements.
ArrayOfDeletedSocialTagDetail	The ArrayOfDeletedSocialTagDetail complex type contains zero or more DeletedSocialTagDetail elements.
ArrayOfSocialCommentDetail	The ArrayOfSocialCommentDetail complex type contains zero or more SocialCommentDetail elements.
ArrayOfSocialRatingDetail	The ArrayOfSocialRatingDetail complex type contains zero or more SocialRatingDetail elements.
ArrayOfSocialTagDetail	The ArrayOfSocialTagDetail complex type contains zero or more SocialTagDetail elements.
ArrayOfSocialTermDetail	The ArrayOfSocialTermDetail complex type contains zero or more SocialTermDetail elements.
ArrayOfSocialUrlDetail	The ArrayOfSocialUrlDetail complex type contains zero or more SocialUrlDetail elements.
ArrayOfString	The ArrayOfString complex type contains zero or more strings.
DeletedSocialCommentDetail	The DeletedSocialCommentDetail complex type contains the data within and about a deleted social comment.
DeletedSocialDataDetail	The DeletedSocialDataDetail complex type contains the data within and about deleted social data. This is the base type for DeletedSocialCommentDetail , DeletedSocialRatingDetail and DeletedSocialTagDetail complex types.
DeletedSocialRatingDetail	The DeletedSocialRatingDetail complex type contains the data within and about a deleted social rating.
DeletedSocialTagDetail	The DeletedSocialTagDetail complex type contains the data within and about a deleted social tag.
SocialCommentDetail	The SocialCommentDetail complex type contains the data within and about a social comment.
SocialDataDetail	The SocialDataDetail complex type contains the data within and about social data. This is the base type for SocialCommentDetail , SocialRatingDetail and SocialTagDetail complex types.

Complex Type	Description
SocialRatingDetail	The SocialRatingDetail complex type contains information about a social rating.
SocialReplicationData	The SocialReplicationData complex type contains information about current and deleted social tags, comments and ratings.
SocialTagDetail	The SocialTagDetail complex type contains information about a social tag.
SocialTermDetail	The SocialTermDetail complex type contains a term and count of a social tag term .
SocialUrlDetail	The SocialUrlDetail complex type contains a string in URI format and the count of social tags that are associated with that URI.
TermDetail	The TermDetail complex type contains information for a social tag term.

2.2.4.1 ArrayOfDeletedSocialCommentDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **ArrayOfDeletedSocialCommentDetail** complex type contains zero or more **DeletedSocialCommentDetail** elements.

```
<xs:complexType name="ArrayOfDeletedSocialCommentDetail"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DeletedSocialCommentDetail"
nillable="true" type="tns:DeletedSocialCommentDetail"/>
  </xs:sequence>
</xs:complexType>
```

DeletedSocialCommentDetail: A **DeletedSocialCommentDetail** complex type (section [2.2.4.10](#)) that contains the deleted comment information.

2.2.4.2 ArrayOfDeletedSocialRatingDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **ArrayOfDeletedSocialRatingDetail** complex type contains zero or more **DeletedSocialRatingDetail** elements.

```
<xs:complexType name="ArrayOfDeletedSocialRatingDetail"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DeletedSocialRatingDetail"
nillable="true" type="tns:DeletedSocialRatingDetail"/>
  </xs:sequence>
</xs:complexType>
```

DeletedSocialRatingDetail: A **DeletedSocialRatingDetail** complex type (section [2.2.4.12](#)) that contains the deleted rating information.

2.2.4.3 ArrayOfDeletedSocialTagDetail

Namespace: <http://microsoft.com/webservices/SharePointPortalServer/SocialDataService>

The **ArrayOfDeletedSocialTagDetail** complex type contains zero or more **DeletedSocialTagDetail** elements.

```
<xs:complexType name="ArrayOfDeletedSocialTagDetail"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="DeletedSocialTagDetail"
      nillable="true" type="tns:DeletedSocialTagDetail"/>
  </xs:sequence>
</xs:complexType>
```

DeletedSocialTagDetail: A **DeletedSocialTagDetail** complex type (section [2.2.4.13](#)) that contains the deleted tag information.

2.2.4.4 ArrayOfSocialCommentDetail

Namespace: <http://microsoft.com/webservices/SharePointPortalServer/SocialDataService>

The **ArrayOfSocialCommentDetail** complex type contains zero or more **SocialCommentDetail** elements.

```
<xs:complexType name="ArrayOfSocialCommentDetail"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialCommentDetail"
      nillable="true" type="tns:SocialCommentDetail"/>
  </xs:sequence>
</xs:complexType>
```

SocialCommentDetail: A **SocialCommentDetail** complex type (section [2.2.4.14](#)) that contains comment information.

2.2.4.5 ArrayOfSocialRatingDetail

Namespace: <http://microsoft.com/webservices/SharePointPortalServer/SocialDataService>

The **ArrayOfSocialRatingDetail** complex type contains zero or more **SocialRatingDetail** elements.

```
<xs:complexType name="ArrayOfSocialRatingDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialRatingDetail" nillable="true"
      type="tns:SocialRatingDetail"/>
  </xs:sequence>
</xs:complexType>
```

SocialRatingDetail: A **SocialRatingDetail** complex type (section [2.2.4.16](#)) that contains the rating information.

2.2.4.6 ArrayOfSocialTagDetail

Namespace: <http://microsoft.com/webservices/SharePointPortalServer/SocialDataService>

The **ArrayOfSocialTagDetail** complex type contains zero or more **SocialTagDetail** elements.

```
<xs:complexType name="ArrayOfSocialTagDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialTagDetail" nillable="true"
      type="tns:SocialTagDetail"/>
  </xs:sequence>
</xs:complexType>
```

SocialTagDetail: A **SocialTagDetail** (section [2.2.4.18](#)) that contains the tag information.

2.2.4.7 ArrayOfSocialTermDetail

Namespace: <http://microsoft.com/webservices/SharePointPortalServer/SocialDataService>

The **ArrayOfSocialTermDetail** complex type contains zero or more **SocialTermDetail** elements.

```
<xs:complexType name="ArrayOfSocialTermDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialTermDetail" nillable="true"
      type="tns:SocialTermDetail"/>
  </xs:sequence>
</xs:complexType>
```

SocialTermDetail: A **SocialTermDetail** complex type (section [2.2.4.19](#)) that contains the term information.

2.2.4.8 ArrayOfSocialUrlDetail

Namespace: <http://microsoft.com/webservices/SharePointPortalServer/SocialDataService>

The **ArrayOfSocialUrlDetail** complex type contains zero or more **SocialUrlDetail** elements.

```
<xs:complexType name="ArrayOfSocialUrlDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialUrlDetail" nillable="true"
      type="tns:SocialUrlDetail"/>
  </xs:sequence>
</xs:complexType>
```

SocialUrlDetail: A **SocialUrlDetail** complex type (section [2.2.4.20](#)) that contains the **social tag URL** information.

2.2.4.9 ArrayOfString

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **ArrayOfString** complex type contains zero or more strings.

```
<xs:complexType name="ArrayOfString" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

string: A string.

2.2.4.10 DeletedSocialCommentDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **DeletedSocialCommentDetail** complex type contains the data within and about a deleted social comment.

```
<xs:complexType name="DeletedSocialCommentDetail"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DeletedSocialDataDetail">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="LastModifiedTime" type="xs:dateTime"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

LastModifiedTime: A value containing the last modified time of the comment.

2.2.4.11 DeletedSocialDataDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **DeletedSocialDataDetail** complex type contains the data within and about deleted social data. This is the base type for **DeletedSocialCommentDetail**, **DeletedSocialRatingDetail** and **DeletedSocialTagDetail** complex types.

```
<xs:complexType name="DeletedSocialDataDetail" abstract="true"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Url" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Owner" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="DeletedTime" type="xs:dateTime"/>
  </xs:sequence>
</xs:complexType>
```

Url: A string type that specifies the URL that is associated with the social data.

Owner: A string type that specifies the owner account that is associated with the social data.

DeletedTime: A value containing the deleted time of the social data.

2.2.4.12 DeletedSocialRatingDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **DeletedSocialRatingDetail** complex type contains the data within and about a deleted social rating.

```
<xs:complexType name="DeletedSocialRatingDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DeletedSocialDataDetail"/>
  </xs:complexContent>
</xs:complexType>
```

2.2.4.13 DeletedSocialTagDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **DeletedSocialTagDetail** complex type contains the data within and about a deleted social tag.

```
<xs:complexType name="DeletedSocialTagDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:DeletedSocialDataDetail">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="TermID"
          xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

TermID: A unique identifier for the term that was deleted.

2.2.4.14 SocialCommentDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **SocialCommentDetail** complex type contains the data within and about a social comment.

```
<xs:complexType name="SocialCommentDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SocialDataDetail">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Comment" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="IsHighPriority" type="xs:boolean"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Comment: A string type that contains the body of the social comment.

IsHighPriority: A Boolean flag that specifies the priority level of the social comment. A value of **true** indicates that the social comment is high priority. A value of **false** indicates that the social comment is normal priority.

2.2.4.15 SocialDataDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **SocialDataDetail** complex type contains the data within and about social data. This is the base type for **SocialCommentDetail**, **SocialRatingDetail** and **SocialTagDetail** complex types.

```
<xs:complexType name="SocialDataDetail" abstract="true"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Url" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Owner" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="LastModifiedTime" type="xs:dateTime"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Title" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Url: A string type that specifies the URL that is associated with the social data.

Owner: A string type that specifies the owner account that is associated with the social data.

LastModifiedTime: A value containing the last modified time of the social data.

Title: A string type that contains the title of the social data.

2.2.4.16 SocialRatingDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **SocialRatingDetail** complex type contains information about a social rating.

```
<xs:complexType name="SocialRatingDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SocialDataDetail">
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="Rating" type="xs:int"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Rating: An integer type that specifies the rating value. The valid range for this value is 1 through 5. A value of 1 is a low rating, while a value of 5 is the highest rating possible.

2.2.4.17 SocialReplicationData

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **SocialReplicationData** complex type contains information about current and deleted social tags, comments and ratings.

```
<xs:complexType name="SocialReplicationData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Tags" type="tns:ArrayOfSocialTagDetail"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Comments"
type="tns:ArrayOfSocialCommentDetail"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Ratings"
type="tns:ArrayOfSocialRatingDetail"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DeletedTags"
type="tns:ArrayOfDeletedSocialTagDetail"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DeletedComments"
type="tns:ArrayOfDeletedSocialCommentDetail"/>
    <xs:element minOccurs="0" maxOccurs="1" name="DeletedRatings"
type="tns:ArrayOfDeletedSocialRatingDetail"/>
  </xs:sequence>
</xs:complexType>
```

Tags: An **ArrayOfSocialTagDetail** type element that contains the social tags.

Comments: An **ArrayOfSocialCommentDetail** type element that contains the social comments.

Ratings: An **ArrayOfSocialRatingDetail** type element that contains the social ratings.

DeletedTags: An **ArrayOfDeletedSocialTagDetail** type element that contains the deleted social tags.

DeletedComments: An **ArrayOfDeletedSocialCommentDetail** type element that contains the deleted social comments.

DeletedRatings: An **ArrayOfDeletedSocialRatingDetail** type element that contains the deleted social ratings.

2.2.4.18 SocialTagDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **SocialTagDetail** complex type contains information about a social tag.

```
<xs:complexType name="SocialTagDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SocialDataDetail">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Term" type="tns:TermDetail"/>
        <xs:element minOccurs="1" maxOccurs="1" name="IsPrivate" type="xs:boolean"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Term: A **TermDetail** complex type (section [2.2.4.18](#)) that contains term information for the social tag.

IsPrivate: A Boolean value that specifies whether the social tag is private. A value of **true** is used to specify that the social tag is private. A value of **false** is used to specify that the social tag is not private.

2.2.4.19 SocialTermDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **SocialTermDetail** complex type contains a term and count of a social tag term.

```
<xs:complexType name="SocialTermDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Term" type="tns:TermDetail"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Count" type="xs:long"/>
  </xs:sequence>
</xs:complexType>
```

Term: A **TermDetail** complex type (section [2.2.4.18](#)) that contains a social tag term.

Count: A **long** type that specifies the number of **social data** elements that contain the **Term** for the given results.

2.2.4.20 SocialUriDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **SocialUriDetail** complex type contains a string in URI format and the count of social tags that are associated with that URI.

```
<xs:complexType name="SocialUriDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Uri" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Count" type="xs:long"/>
  </xs:sequence>
</xs:complexType>
```

Uri: A string that specifies the URL that is associated with the **SocialUriDetail**.

Count: A **long** type that specifies the number of social data elements that contain the **Uri** for the given results.

2.2.4.21 TermDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **TermDetail** complex type contains information for a social tag term.

```
<xs:complexType name="TermDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Id"
      xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string"/>
  </xs:sequence>
```

</xs:complexType>

Id: A GUID type that specifies an identifier for the **term**.

Name: A string that contains the name of the social tag term.

2.2.5 Simple Types

The following table summarizes the set of common XML schema simple type definitions defined by this specification. XML schema simple type definitions that are specific to a particular operation are described with the operation.

Simple type	Description
guid	The guid simple type is a string that matches the following pattern. The guid simple type is from the namespace http://microsoft.com/wsd/types/ .

2.2.5.1 guid

Namespace: <http://microsoft.com/wsd/types/>

The **guid** simple type is a string that matches the following pattern. The **guid** simple type is from the namespace <http://microsoft.com/wsd/types/>.

```
<xs:simpleType name="guid" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

2.2.9 Common Data Structures

This specification does not define any common XML schema data structures.

3 Protocol Details

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The WSDL in this specification matches the WSDL that shipped with the product and provides a base description of the schema. The text that introduces the WSDL might specify differences that reflect actual Microsoft product behavior. For example, the schema definition might allow for an element to be **empty**, **null**, or **not present** but the behavior of the protocol as specified restricts the same elements to being **non-empty**, **present**, and **not null**.

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

Except where specified, protocol clients SHOULD interpret HTTP status codes that are returned by the protocol server as specified in [\[RFC2616\]](#) section 10.

This protocol allows protocol servers to notify protocol clients of application-level faults by using SOAP faults. Except where specified, these SOAP faults are not significant for interoperability and protocol clients can interpret them in an implementation-specific manner.

This protocol allows protocol servers to perform implementation-specific authorization checks and notify protocol clients of authorization faults by using either HTTP status codes or SOAP faults as specified in this section.

3.1 Server Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

3.1.1.1 Social Tags

This protocol enables users to add descriptive keywords to documents and Web pages that were published with a URI. The tags are stored on a **back-end database server** and are not part of the document or Web page with which they are associated. Each social tag has an identifier, which is retrieved from a **term store**, and is associated with a URL. Other information that is stored on a back-end database server includes the person who applied the social tag, a flag that specifies whether the tag is visible only to the person who applied the social tag, and the date when the social tag was last modified.

3.1.1.2 Notes (Social Comments)

This protocol enables users to add textual comments to documents and Web pages that were published with a URI. The comments are stored on a back-end database server and are not part of the document or Web page with which they are associated. Each comment has an identifier and is associated with a URI. Other information that is stored on a back-end database server includes the author of the comment and the date when the comment was last modified.

3.1.1.3 Ratings

This protocol enables users to rate documents and **list items** that are stored on a protocol server. The ratings scale is from one to five stars, inclusive. Ratings are stored on a back-end database server and are not part of the documents or list items with which they are associated. Ratings are aggregated on a per item basis. The number of people who rated an item and the average rating for that item is calculated periodically and stored in a **content database**. Each rating has an identifier and is associated with a URI. Other information that is stored on a back-end database server includes the author of the rating and the date when the rating was last modified.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

The following table summarizes the list of operations as defined by this specification:

Operation	Description
AddComment	The AddComment operation creates an association between a social comment and a specified URI for the current user .
AddTag	The AddTag operation creates an association between a social tag and a specified URI, for the current user.
AddTagByKeyword	The AddTagByKeyword operation creates an association between a social tag and a specified URI, for the current user.
CountCommentsOfUser	The CountCommentsOfUser operation retrieves the total number of social comments for a specified user profile .
CountCommentsOfUserOnUrl	The CountCommentsOfUserOnUrl operation retrieves the total number of social comments for a specified user profile and a specified URI.
CountCommentsOnUrl	The CountCommentsOnUrl operation retrieves the total number of social comments for a specified URI.
CountRatingsOnUrl	The CountRatingsOnUrl operation retrieves the total number of social ratings for a specified URI.
CountTagsOfUser	The CountTagsOfUser operation retrieves the total number of social tags for a specified user profile.
DeleteComment	The DeleteComment operation deletes a social comment that is associated with the current user, stored at a specified URI, and was last modified at a specified time.
DeleteRating	The DeleteRating operation deletes a social rating that is associated with the current user for a specified URI.

Operation	Description
DeleteTag	The DeleteTag operation deletes the social tag that is associated with the current user and for the specified URI and social tag term identifier.
DeleteTagByKeyword	The DeleteTagByKeyword operation deletes a social tag based on a keyword parameter, the current user, and a specified URI.
DeleteTags	The DeleteTags operation deletes all of the social tags that are associated with the current user for a specified URI.
GetAllTagTerms	The GetAllTagTerms operation retrieves all social tag terms.
GetAllTagTermsForUrlFolder	The GetAllTagTermsForUrlFolder operation retrieves all social tag terms for a given URI.
GetAllTagUrls	The GetAllTagUrls operation retrieves all of the social tag URLs that are associated with a specified social tag term.
GetAllTagUrlsByKeyword	The GetAllTagUrlsByKeyword operation retrieves all of the social tag URLs that are associated with a specified social tag term.
GetCommentsOfUser	The GetCommentsOfUser operation retrieves the social comments that are associated with a specified user profile.
GetCommentsOfUserOnUrl	The GetCommentsOfUserOnUrl operation retrieves the social comments that are associated with a specified user profile and for a specified URI.
GetCommentsOnUrl	The GetCommentsOnUrl operation retrieves all of the social comments for a specified URI and for a specified set of parameters.
GetRatingAverageOnUrl	The GetRatingAverageOnUrl operation retrieves the average social rating for the item at a specified URI.
GetRatingOfUserOnUrl	The GetRatingOfUserOnUrl operation retrieves a social rating that is associated with a specified user profile and for a specified URI.
GetRatingOnUrl	The GetRatingOnUrl operation retrieves a social rating that was added by the current user for a specified URI.
GetRatingsOfUser	The GetRatingsOfUser operation retrieves the social ratings that are associated with a specified user profile.
GetRatingsOnUrl	The GetRatingsOnUrl operation retrieves all of the social ratings for a specified URI.
GetSocialDataForFullReplication	The GetSocialDataForFullReplication operation retrieves the list of existing social comments, social tags and social ratings for a specified user profile for use when replicating the social data.
GetSocialDataForIncrementalReplication	The GetSocialDataForIncrementalReplication operation retrieves the list of existing and deleted social comments, social

Operation	Description
	tags and social ratings for a specified time period.
GetTags	The GetTags operation retrieves the social tags that were created by the current user for a specified URL.
GetTagsOfUser	The GetTagsOfUser operation retrieves the social tags that were added by a specified user.
GetTagTerms	The GetTagTerms operation retrieves only social tag terms that were authored by the current user.
GetTagTermsOfUser	The GetTagTermsOfUser operation retrieves the social tag terms that were authored by a specific social tag user . The result set can be limited to a maximum number of items.
GetTagTermsOnUrl	The GetTagTermsOnUrl operation retrieves the social tag terms for a specified social tag URL.
GetTagUrls	The GetTagUrls operation retrieves the social tag URLs that were tagged by the current user with a specified social tag term.
GetTagUrlsByKeyword	The GetTagUrlsByKeyword operation retrieves the social tag URLs, tagged with a specified keyword, which are associated to the current user.
GetTagUrlsOfUser	The GetTagUrlsOfUser operation retrieves the social tag URLs that are associated with a specified social tag term and were added by a specified social tag user.
GetTagUrlsOfUserByKeyword	The GetTagUrlsOfUserByKeyword operation retrieves the social tag URLs that are associated with a specified social tag term and were added by a specified social tag user.
PropagateRating	The PropagateRating operation triggers a recalculation of the current, average social rating for the specified URI that points to a protocol server list item and it stores that new value in the Rating field (2) .
ReplicateFullSocialData	The ReplicateFullSocialData operation replicates the specified social comments, social tags and social ratings for a specified user profile to the server.
ReplicateIncrementalSocialData	The ReplicateIncrementalSocialData operation replicates the specified existing and deleted social comments, social tags and social ratings to the server.
SetRating	The SetRating operation specifies a social rating by the current user for a specified URI.
UpdateComment	The UpdateComment operation updates an existing social comment at a specified URI that was created by the calling user with the specified last modified time.

3.1.4.1 AddComment

The **AddComment** operation creates an association between a social comment and a specified URI for the current user.

```
<wsdl:operation name="AddComment" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:AddCommentSoapIn"/>
  <wsdl:output message="tns:AddCommentSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **AddCommentSoapIn** request message and the protocol server responds with an **AddCommentSoapOut** response message.

The protocol server MUST associate the social comment with the user profile of the current user. The protocol server MUST ensure that the saved social comment body is escaped for **HTML** output.

3.1.4.1.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message	Description
AddCommentSoapIn	The request WSDL message for the AddComment WSDL operation .
AddCommentSoapOut	The response WSDL message for the AddComment WSDL operation.

3.1.4.1.1.1 AddCommentSoapIn

The request WSDL message for the **AddComment** WSDL operation.

The **SOAP action** value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/AddComment
```

The **SOAP body** contains the **AddComment** element.

3.1.4.1.1.2 AddCommentSoapOut

The response WSDL message for the **AddComment** WSDL operation.

The SOAP body contains the **AddCommentResponse** element.

3.1.4.1.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
AddComment	The input data for the AddComment WSDL operation.

Element	Description
AddCommentResponse	The result data for the AddComment WSDL operation.

3.1.4.1.2.1 AddComment

The input data for the **AddComment** WSDL operation.

```
<xs:element name="AddComment" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="comment" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="isHighPriority" nillable="true"
type="xs:boolean"/>
      <xs:element minOccurs="0" maxOccurs="1" name="title" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI of the item to associate with the social comment. This value MUST be fewer than 2085 characters and MUST be URI format.

comment: A string type that contains the body of the social comment. This value MUST contain more than zero characters and fewer than 4001 characters.

isHighPriority: A Boolean type that specifies the priority level of the social comment. A value of **true** indicates that the social comment is high priority. A value of **false** indicates that the social comment is normal priority.

title: A string type that specifies the title of the social comment, as it appears to users. This value MUST be fewer than 501 characters.

3.1.4.1.2.2 AddCommentResponse

The result data for the **AddComment** WSDL operation.

```
<xs:element name="AddCommentResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="AddCommentResult"
type="tns:SocialCommentDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

AddCommentResult: A **SocialCommentDetail** complex type (section [2.2.4.14](#)), that contains the new social comment.

3.1.4.1.3 Complex Types

None.

3.1.4.1.4 Simple Types

None.

3.1.4.1.5 Attributes

None.

3.1.4.1.6 Groups

None.

3.1.4.1.7 Attribute Groups

None.

3.1.4.2 AddTag

The **AddTag** operation creates an association between a social tag and a specified URI, for the current user.

```
<wsdl:operation name="AddTag" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:AddTagSoapIn"/>
  <wsdl:output message="tns:AddTagSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **AddTagSoapIn** request message and the protocol server responds with an **AddTagSoapOut** response message.

The protocol server MUST associate the social tag with the user profile of the current user.

If no social tag term exists for the specified **termID** (section [3.1.4.2.2.1](#)), then the protocol server MUST send a SOAP fault message.

3.1.4.2.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
AddTagSoapIn	The request WSDL message for the AddTag WSDL operation.
AddTagSoapOut	The response WSDL message for the AddTag WSDL operation.

3.1.4.2.1.1 AddTagSoapIn

The request WSDL message for the **AddTag** WSDL operation.

The SOAP action value is:

<http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/AddTag>

The SOAP body contains the **AddTag** element.

3.1.4.2.1.2 AddTagSoapOut

The response WSDL message for the **AddTag** WSDL operation.

The SOAP body contains the **AddTagResponse** element.

3.1.4.2.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
AddTag	The input data for the AddTag WSDL operation.
AddTagResponse	The result data for the AddTag WSDL operation.

3.1.4.2.2.1 AddTag

The input data for the **AddTag** WSDL operation.

```
<xs:element name="AddTag" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="termID"
        xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
      <xs:element minOccurs="0" maxOccurs="1" name="title" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="isPrivate" nillable="true"
        type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI to associate with the social tag. This value MUST be fewer than or equal to 2084 characters and MUST be URI format.

termID: A GUID type that identifies the social tag term to associate with the URI, as defined by the **Id** value of an existing **TermDetail** type (section [2.2.4.18](#)).

title: A string type that specifies the title of the social tag, as it appears to users. This value MUST be fewer than or equal to 500 characters.

isPrivate: A Boolean type that is used to determine the visibility of the social tag. For a value of **true**, the protocol server MUST ensure the tag is visible only to the current user. For a value of **false** or null, the protocol server MUST ensure the tag is publicly visible.

3.1.4.2.2.2 AddTagResponse

The result data for the **AddTag** WSDL operation.

```

<xs:element name="AddTagResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="AddTagResult"
type="tns:SocialTagDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

AddTagResult: A **SocialTagDetail** complex type (section [2.2.4.18](#)) that contains the new social tag.

3.1.4.2.3 Complex Types

None.

3.1.4.2.4 Simple Types

None.

3.1.4.2.5 Attributes

None.

3.1.4.2.6 Groups

None.

3.1.4.2.7 Attribute Groups

None.

3.1.4.3 AddTagByKeyword

The **AddTagByKeyword** operation creates an association between a social tag and a specified URI, for the current user.

```

<wsdl:operation name="AddTagByKeyword" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:AddTagByKeywordSoapIn"/>
  <wsdl:output message="tns:AddTagByKeywordSoapOut"/>
</wsdl:operation>

```

The protocol client sends an **AddTagByKeywordSoapIn** request message and the protocol server responds with an **AddTagByKeywordSoapOut** response message.

The protocol server MUST associate the social tag with the user profile of the current user.

If no social tag term exists for the specified keyword, then the protocol server MUST create it.

3.1.4.3.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
AddTagByKeywordSoapIn	The request WSDL message for the AddTagByKeyword WSDL operation.
AddTagByKeywordSoapOut	The response WSDL message for the AddTagByKeyword WSDL operation.

3.1.4.3.1.1 AddTagByKeywordSoapIn

The request WSDL message for the **AddTagByKeyword** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/AddTagByKeyword
```

The SOAP body contains the **AddTagByKeyword** element.

3.1.4.3.1.2 AddTagByKeywordSoapOut

The response WSDL message for the **AddTagByKeyword** WSDL operation.

The SOAP body contains the **AddTagByKeywordResponse** element.

3.1.4.3.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
AddTagByKeyword	The input data for the AddTagByKeyword WSDL operation.
AddTagByKeywordResponse	The result data for the AddTagByKeyword WSDL operation.

3.1.4.3.2.1 AddTagByKeyword

The input data for the **AddTagByKeyword** WSDL operation.

```
<xs:element name="AddTagByKeyword" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="title" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="isPrivate" nillable="true"
type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
```

```
</xs:element>
```

url: A string type that specifies the URI to associate the social tag with. This value MUST be fewer than or equal to 2084 characters and MUST be URI format.

keyword: A string type that specifies the value of the social tag term and matches the **Name** value of an existing **TermDetail** complex type (section [2.2.4.18](#)).

title: A string type that specifies the title of the social tag, as it appears to users. This value MUST be fewer than or equal to 500 characters.

isPrivate: A Boolean type that is used to determine the visibility of the social tag. For a value of **true**, the protocol server MUST ensure the tag is visible only to the current user. For a value of **false** or **null**, the protocol server MUST ensure the tag is publicly visible.

3.1.4.3.2 AddTagByKeywordResponse

The result data for the **AddTagByKeyword** WSDL operation.

```
<xs:element name="AddTagByKeywordResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="AddTagByKeywordResult"
        type="tns:SocialTagDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

AddTagByKeywordResult: A **SocialTagDetail** complex type (section [2.2.4.18](#)) that contains the new social tag.

3.1.4.3.3 Complex Types

None.

3.1.4.3.4 Simple Types

None.

3.1.4.3.5 Attributes

None.

3.1.4.3.6 Groups

None.

3.1.4.3.7 Attribute Groups

None.

3.1.4.4 CountCommentsOfUser

The **CountCommentsOfUser** operation retrieves the total number of social comments for a specified user profile.

```
<wsdl:operation name="CountCommentsOfUser" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CountCommentsOfUserSoapIn"/>
  <wsdl:output message="tns:CountCommentsOfUserSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CountCommentsOfUserSoapIn** request message and the protocol server responds with a **CountCommentsOfUserSoapOut** response message.

If the specified user profile does not exist, then the protocol server MUST send a SOAP fault message.

3.1.4.4.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CountCommentsOfUserSoapIn	The request WSDL message for the CountCommentsOfUser WSDL operation.
CountCommentsOfUserSoapOut	The response WSDL message for the CountCommentsOfUser WSDL operation.

3.1.4.4.1.1 CountCommentsOfUserSoapIn

The request WSDL message for the **CountCommentsOfUser** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountCommentsOfUser
```

The SOAP body contains the **CountCommentsOfUser** element.

3.1.4.4.1.2 CountCommentsOfUserSoapOut

The response WSDL message for the **CountCommentsOfUser** WSDL operation.

The SOAP body contains the **CountCommentsOfUserResponse** element.

3.1.4.4.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CountCommentsOfUser	The input data for the CountCommentsOfUser WSDL operation.
CountCommentsOfUserResponse	The result data for the CountCommentsOfUser WSDL operation.

3.1.4.4.2.1 CountCommentsOfUser

The input data for the **CountCommentsOfUser** WSDL operation.

```
<xs:element name="CountCommentsOfUser" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

userAccountName: A string type that specifies the user login name of the user profile to get the count of social comments for.

3.1.4.4.2.2 CountCommentsOfUserResponse

The result data for the **CountCommentsOfUser** WSDL operation.

```
<xs:element name="CountCommentsOfUserResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="CountCommentsOfUserResult"
type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CountCommentsOfUserResult: An integer type that indicates the total number of social comments that are associated with the specified user profile. If the comment count is zero, or if the protocol server fails to retrieve the count of social comments for the specific user, the protocol server MUST return zero.

3.1.4.4.3 Complex Types

None.

3.1.4.4.4 Simple Types

None.

3.1.4.4.5 Attributes

None.

3.1.4.4.6 Groups

None.

3.1.4.4.7 Attribute Groups

None.

3.1.4.5 CountCommentsOfUserOnUrl

The **CountCommentsOfUserOnUrl** operation retrieves the total number of social comments for a specified user profile and a specified URI.

```
<wsdl:operation name="CountCommentsOfUserOnUrl"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CountCommentsOfUserOnUrlSoapIn"/>
  <wsdl:output message="tns:CountCommentsOfUserOnUrlSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CountCommentsOfUserOnUrlSoapIn** request message and the protocol server responds with a **CountCommentsOfUserOnUrlSoapOut** response message.

If the specified user profile does not exist, then the protocol server MUST send a SOAP fault message.

3.1.4.5.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CountCommentsOfUserOnUrlSoapIn	The request WSDL message for the CountCommentsOfUserOnUrl WSDL operation.
CountCommentsOfUserOnUrlSoapOut	The response WSDL message for the CountCommentsOfUserOnUrl WSDL operation.

3.1.4.5.1.1 CountCommentsOfUserOnUrlSoapIn

The request WSDL message for the **CountCommentsOfUserOnUrl** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountCommentsOfUserOnUrl
```

The SOAP body contains the **CountCommentsOfUserOnUrl** element.

3.1.4.5.1.2 CountCommentsOfUserOnUrlSoapOut

The response WSDL message for the **CountCommentsOfUserOnUrl** WSDL operation.

The SOAP body contains the **CountCommentsOfUserOnUrlResponse** element.

3.1.4.5.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CountCommentsOfUserOnUrl	The input data for the CountCommentsOfUserOnUrl WSDL operation.
CountCommentsOfUserOnUrlResponse	The result data for the CountCommentsOfUserOnUrl WSDL operation.

3.1.4.5.2.1 CountCommentsOfUserOnUrl

The input data for the **CountCommentsOfUserOnUrl** WSDL operation.

```
<xs:element name="CountCommentsOfUserOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

userAccountName: A string type that specifies the user login name of the user profile to retrieve the count of social comments for.

url: A string type that specifies the URI to retrieve the count of social comments for. This value MUST be fewer than or equal to 2,084 characters and MUST be URI format.

3.1.4.5.2.2 CountCommentsOfUserOnUrlResponse

The result data for the **CountCommentsOfUserOnUrl** WSDL operation.

```
<xs:element name="CountCommentsOfUserOnUrlResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="CountCommentsOfUserOnUrlResult"
        type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CountCommentsOfUserOnUrlResult: An integer type that specifies the total number of social comments for the specified user profile and for the specified URI. If the protocol server cannot find the count of social comments, then the protocol server MUST return zero.

3.1.4.5.3 Complex Types

None.

3.1.4.5.4 Simple Types

None.

3.1.4.5.5 Attributes

None.

3.1.4.5.6 Groups

None.

3.1.4.5.7 Attribute Groups

None.

3.1.4.6 CountCommentsOnUrl

The **CountCommentsOnUrl** operation retrieves the total number of social comments for a specified URI.

```
<wsdl:operation name="CountCommentsOnUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CountCommentsOnUrlSoapIn"/>
  <wsdl:output message="tns:CountCommentsOnUrlSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CountCommentsOnUrlSoapIn** request message and the protocol server responds with a **CountCommentsOnUrlSoapOut** response message.

3.1.4.6.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CountCommentsOnUrlSoapIn	The request WSDL message for the CountCommentsOnUrl WSDL operation.
CountCommentsOnUrlSoapOut	The response WSDL message for the CountCommentsOnUrl WSDL operation.

3.1.4.6.1.1 CountCommentsOnUrlSoapIn

The request WSDL message for the **CountCommentsOnUrl** WSDL operation.

The SOAP action value is:

<http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountCommentsOnUrl>

The SOAP body contains the **CountCommentsOnUrl** element.

3.1.4.6.1.2 CountCommentsOnUrlSoapOut

The response WSDL message for the **CountCommentsOnUrl** WSDL operation.

The SOAP body contains the **CountCommentsOnUrlResponse** element.

3.1.4.6.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CountCommentsOnUrl	The input data for the CountCommentsOnUrl WSDL operation.
CountCommentsOnUrlResponse	The result data for the CountCommentsOnUrl WSDL operation.

3.1.4.6.2.1 CountCommentsOnUrl

The input data for the **CountCommentsOnUrl** WSDL operation.

```
<xs:element name="CountCommentsOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI to retrieve the count of social comments for. The value MUST be fewer than or equal to 2,084 characters and MUST be URI format.

3.1.4.6.2.2 CountCommentsOnUrlResponse

The result data for the **CountCommentsOnUrl** WSDL operation.

```
<xs:element name="CountCommentsOnUrlResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="CountCommentsOnUrlResult" type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CountCommentsOnUrlResult: An integer that represents the total number of social comments at the specified URI. If the protocol server cannot find the count of social comments, the protocol server MUST return zero.

3.1.4.6.3 Complex Types

None.

3.1.4.6.4 Simple Types

None.

3.1.4.6.5 Attributes

None.

3.1.4.6.6 Groups

None.

3.1.4.6.7 Attribute Groups

None.

3.1.4.7 CountRatingsOnUrl

The **CountRatingsOnUrl** operation retrieves the total number of social ratings for a specified URI.

```
<wsdl:operation name="CountRatingsOnUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CountRatingsOnUrlSoapIn"/>
  <wsdl:output message="tns:CountRatingsOnUrlSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CountRatingsOnUrlSoapIn** request message and the protocol server responds with a **CountRatingsOnUrlSoapOut** response message.

3.1.4.7.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CountRatingsOnUrlSoapIn	The request WSDL message for the CountRatingsOnUrl WSDL operation.
CountRatingsOnUrlSoapOut	The response WSDL message for the CountRatingsOnUrl WSDL operation.

3.1.4.7.1.1 CountRatingsOnUrlSoapIn

The request WSDL message for the **CountRatingsOnUrl** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountRatingsOnUrl
```

The SOAP body contains the **CountRatingsOnUrl** element.

3.1.4.7.1.2 CountRatingsOnUrlSoapOut

The response WSDL message for the **CountRatingsOnUrl** WSDL operation.

The SOAP body contains the **CountRatingsOnUrlResponse** element.

3.1.4.7.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CountRatingsOnUrl	The input data for the CountRatingsOnUrl WSDL operation.
CountRatingsOnUrlResponse	The result data for the CountRatingsOnUrl WSDL operation.

3.1.4.7.2.1 CountRatingsOnUrl

The input data for the **CountRatingsOnUrl** WSDL operation.

```
<xs:element name="CountRatingsOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI to retrieve the count of social ratings for. This value **MUST** be fewer than or equal to 2,084 characters and **MUST** be URI format.

3.1.4.7.2.2 CountRatingsOnUrlResponse

The result data for the **CountRatingsOnUrl** WSDL operation.

```
<xs:element name="CountRatingsOnUrlResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="CountRatingsOnUrlResult" type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

CountRatingsOnUrlResult: An integer type that represents the total number of social ratings for the specified URI. If the protocol server cannot find the count of social ratings, the protocol server **MUST** return zero.

3.1.4.7.3 Complex Types

None.

3.1.4.7.4 Simple Types

None.

3.1.4.7.5 Attributes

None.

3.1.4.7.6 Groups

None.

3.1.4.7.7 Attribute Groups

None.

3.1.4.8 CountTagsOfUser

The **CountTagsOfUser** operation retrieves the total number of social tags for a specified user profile.

```
<wsdl:operation name="CountTagsOfUser" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:CountTagsOfUserSoapIn"/>
  <wsdl:output message="tns:CountTagsOfUserSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **CountTagsOfUserSoapIn** request message and the protocol server responds with a **CountTagsOfUserSoapOut** response message.

If the name of the current user is equal to the value of the specified **userAccountName**, or the current user is an administrator, then the protocol server MUST return the count of both private social tags and public social tags which is determined by the **IsPrivate** field (1) of the tag (see section [2.2.4.18](#)). If the name of the current user is not equal to the value of the specified **userAccountName** and the current user is not an administrator, then the protocol server MUST return the count of public social tags only.

3.1.4.8.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
CountTagsOfUserSoapIn	The request WSDL message for the CountTagsOfUser WSDL operation.
CountTagsOfUserSoapOut	The response WSDL message for the CountTagsOfUser WSDL operation.

3.1.4.8.1.1 CountTagsOfUserSoapIn

The request WSDL message for the **CountTagsOfUser** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountTagsOfUser
```

The SOAP body contains the **CountTagsOfUser** element.

3.1.4.8.1.2 CountTagsOfUserSoapOut

The response WSDL message for the **CountTagsOfUser** WSDL operation.

The SOAP body contains the **CountTagsOfUserResponse** element.

3.1.4.8.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
CountTagsOfUser	The input data for the CountTagsOfUser WSDL operation.
CountTagsOfUserResponse	The result data for the CountTagsOfUser WSDL operation.

3.1.4.8.2.1 CountTagsOfUser

The input data for the **CountTagsOfUser** WSDL operation.

```
<xs:element name="CountTagsOfUser" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

userAccountName: A string type that specifies the user login name of the user profile to retrieve the count of social tags for.

3.1.4.8.2.2 CountTagsOfUserResponse

The result data for the **CountTagsOfUser** WSDL operation.

```
<xs:element name="CountTagsOfUserResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="1" maxOccurs="1" name="CountTagsOfUserResult" type="xs:int"/>  
    </xs:sequence>  
  </xs:complexType>
```

</xs:element>

CountTagsOfUserResult: An integer type that represents the total number of social tags for the specified user profile. If the protocol server cannot find the count of social tags for the specified user, the protocol server MUST return zero.

3.1.4.8.3 Complex Types

None.

3.1.4.8.4 Simple Types

None.

3.1.4.8.5 Attributes

None.

3.1.4.8.6 Groups

None.

3.1.4.8.7 Attribute Groups

None.

3.1.4.9 DeleteComment

The **DeleteComment** operation deletes a social comment that is associated with the current user, stored at a specified URI, and was last modified at a specified time.

```
<wsdl:operation name="DeleteComment" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteCommentSoapIn"/>
  <wsdl:output message="tns:DeleteCommentSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteCommentSoapIn** request message and the protocol server responds with a **DeleteCommentSoapOut** response message.

The protocol server MUST delete only the social comment that is associated with the current user, is associated with the specified URI, and was last modified at the specified time.

3.1.4.9.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteCommentSoapIn	The request WSDL message for the DeleteComment WSDL operation.

Message	Description
DeleteCommentSoapOut	The response WSDL message for the DeleteComment WSDL operation.

3.1.4.9.1.1 DeleteCommentSoapIn

The request WSDL message for the **DeleteComment** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteComment
```

The SOAP body contains the **DeleteComment** element.

3.1.4.9.1.2 DeleteCommentSoapOut

The response WSDL message for the **DeleteComment** WSDL operation.

The SOAP body contains the **DeleteCommentResponse** element.

3.1.4.9.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteComment	The input data for the DeleteComment WSDL operation.
DeleteCommentResponse	The result data for the DeleteComment WSDL operation.

3.1.4.9.2.1 DeleteComment

The input data for the **DeleteComment** WSDL operation.

```
<xs:element name="DeleteComment" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="lastModifiedTime" type="xs:dateTime"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI that is associated with the social comment to delete. This value MUST be fewer than or equal to 2,084 characters and MUST be URI format.

lastModifiedTime: A dateTime value that specifies when the social comment to delete was last modified.

3.1.4.9.2 DeleteCommentResponse

The result data for the **DeleteComment** WSDL operation.

```
<xs:element name="DeleteCommentResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.9.3 Complex Types

None.

3.1.4.9.4 Simple Types

None.

3.1.4.9.5 Attributes

None.

3.1.4.9.6 Groups

None.

3.1.4.9.7 Attribute Groups

None.

3.1.4.10 DeleteRating

The **DeleteRating** operation deletes a social rating that is associated with the current user for a specified URI.

```
<wsdl:operation name="DeleteRating" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteRatingSoapIn"/>
  <wsdl:output message="tns:DeleteRatingSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteRatingSoapIn** request message and the protocol server responds with a **DeleteRatingSoapOut** response message.

The protocol server MUST delete only the social rating that is associated with both the current user and the specified URI.

3.1.4.10.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteRatingSoapIn	The request WSDL message for the DeleteRating WSDL operation.
DeleteRatingSoapOut	The response WSDL message for the DeleteRating WSDL operation.

3.1.4.10.1.1 DeleteRatingSoapIn

The request WSDL message for the **DeleteRating** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteRating
```

The SOAP body contains the **DeleteRating** element.

3.1.4.10.1.2 DeleteRatingSoapOut

The response WSDL message for the **DeleteRating** WSDL operation.

The SOAP body contains the **DeleteRatingResponse** element.

3.1.4.10.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteRating	The input data for the DeleteRating WSDL operation.
DeleteRatingResponse	The result data for the DeleteRating WSDL operation.

3.1.4.10.2.1 DeleteRating

The input data for the **DeleteRating** WSDL operation.

```
<xs:element name="DeleteRating" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI that is associated with the social rating to delete. This value MUST be fewer than or equal to 2,084 characters and MUST be URI format.

3.1.4.10.2.2 DeleteRatingResponse

The result data for the **DeleteRating** WSDL operation.

```

<xs:element name="DeleteRatingResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>

```

3.1.4.10.3 Complex Types

None.

3.1.4.10.4 Simple Types

None.

3.1.4.10.5 Attributes

None.

3.1.4.10.6 Groups

None.

3.1.4.10.7 Attribute Groups

None.

3.1.4.11 DeleteTag

The **DeleteTag** operation deletes the social tag that is associated with the current user and for the specified URI and social tag term identifier.

```

<wsdl:operation name="DeleteTag" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteTagSoapIn"/>
  <wsdl:output message="tns:DeleteTagSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **DeleteTagSoapIn** request message and the protocol server responds with a **DeleteTagSoapOut** response message.

The protocol server MUST delete only the social tag that is associated with the current user and for the specified URI and social tag term identifier.

If no social tag term exists for the specified **termID** (section [3.1.4.11.2.1](#)), then the protocol server MUST send a SOAP fault message.

3.1.4.11.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteTagSoapIn	The request WSDL message for the DeleteTag WSDL operation.

Message	Description
DeleteTagSoapOut	The response WSDL message for the DeleteTag WSDL operation.

3.1.4.11.1.1 DeleteTagSoapIn

The request WSDL message for the **DeleteTag** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteTag
```

The SOAP body contains the **DeleteTag** element.

3.1.4.11.1.2 DeleteTagSoapOut

The response WSDL message for the **DeleteTag** WSDL operation.

The SOAP body contains the **DeleteTagResponse** element.

3.1.4.11.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteTag	The input data for the DeleteTag WSDL operation.
DeleteTagResponse	The result data for the DeleteTag WSDL operation.

3.1.4.11.2.1 DeleteTag

The input data for the **DeleteTag** WSDL operation.

```
<xs:element name="DeleteTag" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="termID"
        xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI that is associated with the social tag to delete. This value MUST be fewer than or equal to 2,084 characters and MUST be URI format.

termID: A GUID type that identifies the social tag term. This value is the same as the **Id** value of the **TermDetail** complex type (section [2.2.4.21](#)) for the term.

3.1.4.11.2 DeleteTagResponse

The result data for the **DeleteTag** WSDL operation.

```
<xs:element name="DeleteTagResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.11.3 Complex Types

None.

3.1.4.11.4 Simple Types

None.

3.1.4.11.5 Attributes

None.

3.1.4.11.6 Groups

None.

3.1.4.11.7 Attribute Groups

None.

3.1.4.12 DeleteTagByKeyword

The **DeleteTagByKeyword** operation deletes a social tag based on a keyword parameter, the current user, and a specified URI.

```
<wsdl:operation name="DeleteTagByKeyword" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteTagByKeywordSoapIn"/>
  <wsdl:output message="tns:DeleteTagByKeywordSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteTagByKeywordSoapIn** request message and the protocol server responds with a **DeleteTagByKeywordSoapOut** response message.

The protocol server MUST delete only that social tag which is identified by the specified keyword and is associated with the current user for the specified URI.

If a social tag term does not exist for the specified keyword, then the protocol server MUST send a SOAP fault message.

3.1.4.12.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteTagByKeywordSoapIn	The request WSDL message for the DeleteTagByKeyword WSDL operation.
DeleteTagByKeywordSoapOut	The response WSDL message for the DeleteTagByKeyword WSDL operation.

3.1.4.12.1.1 DeleteTagByKeywordSoapIn

The request WSDL message for the **DeleteTagByKeyword** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteTagByKeyword
```

The SOAP body contains the **DeleteTagByKeyword** element.

3.1.4.12.1.2 DeleteTagByKeywordSoapOut

The response WSDL message for the **DeleteTagByKeyword** WSDL operation.

The SOAP body contains the **DeleteTagByKeywordResponse** element.

3.1.4.12.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteTagByKeyword	The input data for the DeleteTagByKeyword WSDL operation.
DeleteTagByKeywordResponse	The result data for the DeleteTagByKeyword WSDL operation.

3.1.4.12.2.1 DeleteTagByKeyword

The input data for the **DeleteTagByKeyword** WSDL operation.

```
<xs:element name="DeleteTagByKeyword" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI that is associated with the social tag to delete. This value **MUST** be fewer than 2,085 characters and **MUST** be URI format.

keyword: A string type that contains the keyword that identifies the social tag term. The value of this element MUST be the same as the value of the **Name** element of an existing **TermDetail** complex type (section [2.2.4.21](#)).

3.1.4.12.2 DeleteTagByKeywordResponse

The result data for the **DeleteTagByKeyword** WSDL operation.

```
<xs:element name="DeleteTagByKeywordResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.12.3 Complex Types

None.

3.1.4.12.4 Simple Types

None.

3.1.4.12.5 Attributes

None.

3.1.4.12.6 Groups

None.

3.1.4.12.7 Attribute Groups

None.

3.1.4.13 DeleteTags

The **DeleteTags** operation deletes all of the social tags that are associated with the current user for a specified URI.

```
<wsdl:operation name="DeleteTags" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:DeleteTagsSoapIn"/>
  <wsdl:output message="tns:DeleteTagsSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **DeleteTagsSoapIn** request message and the protocol server responds with a **DeleteTagsSoapOut** response message.

The protocol server MUST delete only those social tags that are associated with both the current user and the specified URI.

3.1.4.13.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
DeleteTagsSoapIn	The request WSDL message for the DeleteTags WSDL operation.
DeleteTagsSoapOut	The response WSDL message for the DeleteTags WSDL operation.

3.1.4.13.1.1 DeleteTagsSoapIn

The request WSDL message for the **DeleteTags** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteTags
```

The SOAP body contains the **DeleteTags** element.

3.1.4.13.1.2 DeleteTagsSoapOut

The response WSDL message for the **DeleteTags** WSDL operation.

The SOAP body contains the **DeleteTagsResponse** element.

3.1.4.13.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
DeleteTags	The input data for the DeleteTags WSDL operation.
DeleteTagsResponse	The result data for the DeleteTags WSDL operation.

3.1.4.13.2.1 DeleteTags

The input data for the **DeleteTags** WSDL operation.

```
<xs:element name="DeleteTags" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI to delete the social tags from. This value MUST be fewer than or equal to 2,084 characters and MUST be URI format.

3.1.4.13.2 DeleteTagsResponse

The result data for the **DeleteTags** WSDL operation.

```
<xs:element name="DeleteTagsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.13.3 Complex Types

None.

3.1.4.13.4 Simple Types

None.

3.1.4.13.5 Attributes

None.

3.1.4.13.6 Groups

None.

3.1.4.13.7 Attribute Groups

None.

3.1.4.14 GetAllTagTerms

The **GetAllTagTerms** operation retrieves all social tag terms.

```
<wsdl:operation name="GetAllTagTerms" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetAllTagTermsSoapIn"/>
  <wsdl:output message="tns:GetAllTagTermsSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetAllTagTermsSoapIn** request message and the protocol server responds with a **GetAllTagTermsSoapOut** response message.

3.1.4.14.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAllTagTermsSoapIn	The request WSDL message for the GetAllTagTerms WSDL operation.
GetAllTagTermsSoapOut	The response WSDL message for the GetAllTagTerms WSDL operation.

3.1.4.14.1.1 GetAllTagTermsSoapIn

The request WSDL message for the **GetAllTagTerms** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllTagTerms
```

The SOAP body contains the **GetAllTagTerms** element.

3.1.4.14.1.2 GetAllTagTermsSoapOut

The response WSDL message for the **GetAllTagTerms** WSDL operation.

The SOAP body contains the **GetAllTagTermsResponse** element.

3.1.4.14.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAllTagTerms	The input data for the GetAllTagTerms WSDL operation.
GetAllTagTermsResponse	The result data for the GetAllTagTerms WSDL operation.

3.1.4.14.2.1 GetAllTagTerms

The input data for the **GetAllTagTerms** WSDL operation.

```
<xs:element name="GetAllTagTerms" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn" nillable="true"  
        type="xs:int"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

maximumItemsToReturn: An integer type that specifies the maximum number of items to return. This value **MUST** be greater than or equal to "0" (zero) or null. When "0" (zero) or null is passed, the protocol server **MUST** return a maximum of 1000 results.

3.1.4.14.2.2 GetAllTagTermsResponse

The result data for the **GetAllTagTerms** WSDL operation.

```
<xs:element name="GetAllTagTermsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>
```

```

        <xs:element minOccurs="0" maxOccurs="1" name="GetAllTagTermsResult"
type="tns:ArrayOfSocialTermDetail"/>
    </xs:sequence>
</xs:complexType>
</xs:element>

```

GetAllTagTermsResult: An **ArrayOfSocialTermDetail** complex type (section [2.2.4.7](#)) that contains the results in descending order on the **SocialTermDetail Count** value. This element MUST be returned when the operation succeeds. There MUST be one entry for each social tag term, up to any maximum number of entries, as defined by the value of the **maximumItemsToReturn** element. The protocol server MUST trim the results by removing all elements after the first N elements, where N is specified by the value of the **maximumItemsToReturn** element.

3.1.4.14.3 Complex Types

None.

3.1.4.14.4 Simple Types

None.

3.1.4.14.5 Attributes

None.

3.1.4.14.6 Groups

None.

3.1.4.14.7 Attribute Groups

None.

3.1.4.15 GetAllTagTermsForUrlFolder

The **GetAllTagTermsForUrlFolder** operation retrieves all social tag terms for a given Url.

```

<wsdl:operation name="GetAllTagTermsForUrlFolder"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
    <wsdl:input message="tns:GetAllTagTermsForUrlFolderSoapIn"/>
    <wsdl:output message="tns:GetAllTagTermsForUrlFolderSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetAllTagTermsForUrlFolderSoapIn** request message and the protocol server responds with a **GetAllTagTermsForUrlFolderSoapOut** response message.

3.1.4.15.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAllTagTermsForUrlFolderSoapIn	The request WSDL message for the GetAllTagTermsForUrlFolder WSDL operation.
GetAllTagTermsForUrlFolderSoapOut	The response WSDL message for the GetAllTagTermsForUrlFolder WSDL operation.

3.1.4.15.1.1 GetAllTagTermsForUrlFolderSoapIn

The request WSDL message for the **GetAllTagTermsForUrlFolder** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllTagTermsForUrlFolder
```

The SOAP body contains the **GetAllTagTermsForUrlFolder** element.

3.1.4.15.1.2 GetAllTagTermsForUrlFolderSoapOut

The response WSDL message for the **GetAllTagTermsForUrlFolder** WSDL operation.

The SOAP body contains the **GetAllTagTermsForUrlFolderResponse** element.

3.1.4.15.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAllTagTermsForUrlFolder	The input data for the GetAllTagTermsForUrlFolder WSDL operation.
GetAllTagTermsForUrlFolderResponse	The result data for the GetAllTagTermsForUrlFolder WSDL operation.

3.1.4.15.2.1 GetAllTagTermsForUrlFolder

The input data for the **GetAllTagTermsForUrlFolder** WSDL operation.

```
<xs:element name="GetAllTagTermsForUrlFolder" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="urlFolder" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn" type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

urlFolder: A string which specifies the Url which the social tags should be retrieved for.

maximumItemsToReturn: An integer type that specifies the maximum number of items to return. This value MUST be greater than or equal to "0" and less than 1001 or null. When "0" (zero) or null is passed, the protocol server MUST return a maximum of 1000 results.

3.1.4.15.2 GetAllTagTermsForUrlFolderResponse

The result data for the **GetAllTagTermsForUrlFolder** WSDL operation.

```
<xs:element name="GetAllTagTermsForUrlFolderResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetAllTagTermsForUrlFolderResult"
        type="tns:ArrayOfSocialTermDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetAllTagTermsForUrlFolderResult: An **ArrayOfSocialTermDetail** complex type (section [2.2.4.7](#)) that contains the results. This element MUST be returned when the operation succeeds. There MUST be one entry for each social tag term, up to any maximum number of entries, as defined by the value of the **maximumItemsToReturn** element.

3.1.4.15.3 Complex Types

None.

3.1.4.15.4 Simple Types

None.

3.1.4.15.5 Attributes

None.

3.1.4.15.6 Groups

None.

3.1.4.15.7 Attribute Groups

None.

3.1.4.16 GetAllTagUrls

The **GetAllTagUrls** operation retrieves all of the social tag URLs that are associated with a specified social tag term.

```
<wsdl:operation name="GetAllTagUrls" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetAllTagUrlsSoapIn"/>
  <wsdl:output message="tns:GetAllTagUrlsSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetAllTagUrlsSoapIn** request message and the protocol server responds with a **GetAllTagUrlsSoapOut** response message.

3.1.4.16.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAllTagUrlsSoapIn	The request WSDL message for the GetAllTagUrls WSDL operation.
GetAllTagUrlsSoapOut	The response WSDL message for the GetAllTagUrls WSDL operation.

3.1.4.16.1.1 GetAllTagUrlsSoapIn

The request WSDL message for the **GetAllTagUrls** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllTagUrls
```

The SOAP body contains the **GetAllTagUrls** element.

3.1.4.16.1.2 GetAllTagUrlsSoapOut

The response WSDL message for the **GetAllTagUrls** WSDL operation.

The SOAP body contains the **GetAllTagUrlsResponse** element.

3.1.4.16.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAllTagUrls	The input data for the GetAllTagUrls WSDL operation.
GetAllTagUrlsResponse	The result data for the GetAllTagUrls WSDL operation.

3.1.4.16.2.1 GetAllTagUrls

The input data for the **GetAllTagUrls** WSDL operation.

```
<xs:element name="GetAllTagUrls" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="1" maxOccurs="1" name="termID"  
        xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

```
</xs:element>
```

termID: A GUID type that identifies the social tag term to retrieve results for. The social tag term referenced by this **termID** MUST be available for tagging. If this value does not match the identifier for an existing social tag term, the protocol server MUST send a SOAP fault message.

3.1.4.16.2.2 GetAllTagUrlsResponse

The result data for the **GetAllTagUrls** WSDL operation.

```
<xs:element name="GetAllTagUrlsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetAllTagUrlsResult"
        type="tns:ArrayOfSocialUrlDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetAllTagUrlsResult: An **ArrayOfSocialUrlDetail** complex type (section [2.2.4.8](#)) that contains the results. This element MUST be returned when the operation succeeds. There MUST be one entry for each social tag URL for the specified social tag term.

3.1.4.16.3 Complex Types

None.

3.1.4.16.4 Simple Types

None.

3.1.4.16.5 Attributes

None.

3.1.4.16.6 Groups

None.

3.1.4.16.7 Attribute Groups

None.

3.1.4.17 GetAllTagUrlsByKeyword

The **GetAllTagUrlsByKeyword** operation retrieves all of the social tag URLs that are associated with a specified social tag term.

```
<wsdl:operation name="GetAllTagUrlsByKeyword" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetAllTagUrlsByKeywordSoapIn"/>
  <wsdl:output message="tns:GetAllTagUrlsByKeywordSoapOut"/>
</wsdl:operation>
```

</wsdl:operation>

The protocol client sends a **GetAllTagUrlsSoapIn** request message and the protocol server responds with a **GetAllTagUrlsSoapOut** response message.

3.1.4.17.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetAllTagUrlsByKeywordSoapIn	The request WSDL message for the GetAllTagUrlsByKeyword WSDL operation.
GetAllTagUrlsByKeywordSoapOut	The response WSDL message for the GetAllTagUrlsByKeyword WSDL operation.

3.1.4.17.1.1 GetAllTagUrlsByKeywordSoapIn

The request WSDL message for the **GetAllTagUrlsByKeyword** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllTagUrlsByKeyword
```

The SOAP body contains the **GetAllTagUrlsByKeyword** element.

3.1.4.17.1.2 GetAllTagUrlsByKeywordSoapOut

The response WSDL message for the **GetAllTagUrlsByKeyword** WSDL operation.

The SOAP body contains the **GetAllTagUrlsByKeywordResponse** element.

3.1.4.17.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetAllTagUrlsByKeyword	The input data for the GetAllTagUrlsByKeyword WSDL operation.
GetAllTagUrlsByKeywordResponse	The result data for the GetAllTagUrlsByKeyword WSDL operation.

3.1.4.17.2.1 GetAllTagUrlsByKeyword

The input data for the **GetAllTagUrlsByKeyword** WSDL operation.

```
<xs:element name="GetAllTagUrlsByKeyword" xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<xs:complexType>
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
</xs:element>

```

keyword: A string type that specifies the social tag term to return social tag URLs for. This value matches the **Name** value of an existing **TermDetail** complex type (section [2.2.4.21](#)). The social tag term referenced by this value MUST be available for tagging. If the specified value is not an existing social tag term, the protocol server MUST send a SOAP fault message.

3.1.4.17.2.2 GetAllTagUrlsByKeywordResponse

The result data for the **GetAllTagUrlsByKeyword** WSDL operation.

```

<xs:element name="GetAllTagUrlsByKeywordResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetAllTagUrlsByKeywordResult"
        type="tns:ArrayOfSocialUrlDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetAllTagUrlsByKeywordResult: An **ArrayOfSocialUrlDetail** complex type (section [2.2.4.8](#)) that contains the results. This element MUST be returned when the operation succeeds. There MUST be one entry for each social tag URL for the specified social tag term.

3.1.4.17.3 Complex Types

None.

3.1.4.17.4 Simple Types

None.

3.1.4.17.5 Attributes

None.

3.1.4.17.6 Groups

None.

3.1.4.17.7 Attribute Groups

None.

3.1.4.18 GetCommentsOfUser

The **GetCommentsOfUser** operation retrieves the social comments that are associated with a specified user profile.

```
<wsdl:operation name="GetCommentsOfUser" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCommentsOfUserSoapIn"/>
  <wsdl:output message="tns:GetCommentsOfUserSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetCommentsOfUserSoapIn** request message and the protocol server responds with a **GetCommentsOfUserSoapOut** response message.

If the specified user profile does not exist, then the protocol server MUST send a SOAP fault message.

3.1.4.18.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCommentsOfUserSoapIn	The request WSDL message for the GetCommentsOfUser WSDL operation.
GetCommentsOfUserSoapOut	The response WSDL message for the GetCommentsOfUser WSDL operation.

3.1.4.18.1.1 GetCommentsOfUserSoapIn

The request WSDL message for the **GetCommentsOfUser** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetCommentsOfUser
```

The SOAP body contains the **GetCommentsOfUser** element.

3.1.4.18.1.2 GetCommentsOfUserSoapOut

The response WSDL message for the **GetCommentsOfUser** WSDL operation.

The SOAP body contains the **GetCommentsOfUserResponse** element.

3.1.4.18.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCommentsOfUser	The input data for the GetCommentsOfUser WSDL operation.
GetCommentsOfUserResponse	The result data for the GetCommentsOfUser WSDL operation.

3.1.4.18.2.1 GetCommentsOfUser

The input data for the **GetCommentsOfUser** WSDL operation.

```
<xs:element name="GetCommentsOfUser" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn" nillable="true"
type="xs:int"/>
      <xs:element minOccurs="1" maxOccurs="1" name="startIndex" nillable="true"
type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

userAccountName: A string type that specifies the user login name of the user profile for which to retrieve social comments.

maximumItemsToReturn: An integer type that indicates the maximum number of social comments to return. This value **MUST** be greater than or equal to zero, or **null**. This value **MUST** be less than 1001. If this value is zero or null, then the protocol server **MUST** limit the number of social comments that are returned to 100.

startIndex: An integer type that specifies the zero-based index into the total set of comments retrievable by this operation for which the returned set starts. The protocol server **MUST NOT** include any comments with indices that are less than the specified value. This value **MUST** be greater than or equal to zero, or **null**. If this value is zero or **null**, then the protocol server **MUST** use the first social comment in the total set of comments retrievable by this operation as the starting value when returning the social comments.

3.1.4.18.2.2 GetCommentsOfUserResponse

The result data for the **GetCommentsOfUser** WSDL operation.

```
<xs:element name="GetCommentsOfUserResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCommentsOfUserResult"
type="tns:ArrayOfSocialCommentDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetCommentsOfUserResult: An **ArrayOfSocialCommentDetail** complex type (section [2.2.4.4](#)) that contains the requested social comments. This element **MUST** be returned when the operation succeeds.

3.1.4.18.3 Complex Types

None.

3.1.4.18.4 Simple Types

None.

3.1.4.18.5 Attributes

None.

3.1.4.18.6 Groups

None.

3.1.4.18.7 Attribute Groups

None.

3.1.4.19 GetCommentsOfUserOnUrl

The **GetCommentsOfUserOnUrl** operation retrieves the social comments that are associated with a specified user profile and for a specified URI.

```
<wsdl:operation name="GetCommentsOfUserOnUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCommentsOfUserOnUrlSoapIn"/>
  <wsdl:output message="tns:GetCommentsOfUserOnUrlSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetCommentsOfUserOnUrlSoapIn** request message and the protocol server responds with a **GetCommentsOfUserOnUrlSoapOut** response message.

If the specified user profile does not exist, then the protocol server MUST send a SOAP fault message.

3.1.4.19.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCommentsOfUserOnUrlSoapIn	The request WSDL message for the GetCommentsOfUserOnUrl WSDL operation.
GetCommentsOfUserOnUrlSoapOut	The response WSDL message for the GetCommentsOfUserOnUrl WSDL operation.

3.1.4.19.1.1 GetCommentsOfUserOnUrlSoapIn

The request WSDL message for the **GetCommentsOfUserOnUrl** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetCommentsOfUserOnUrl
```

The SOAP body contains the **GetCommentsOfUserOnUrl** element.

3.1.4.19.1.2 GetCommentsOfUserOnUrlSoapOut

The response WSDL message for the **GetCommentsOfUserOnUrl** WSDL operation.

The SOAP body contains the **GetCommentsOfUserOnUrlResponse** element.

3.1.4.19.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCommentsOfUserOnUrl	The input data for the GetCommentsOfUserOnUrl WSDL operation.
GetCommentsOfUserOnUrlResponse	The result data for the GetCommentsOfUserOnUrl WSDL operation.

3.1.4.19.2.1 GetCommentsOfUserOnUrl

The input data for the **GetCommentsOfUserOnUrl** WSDL operation.

```
<xs:element name="GetCommentsOfUserOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>  
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

userAccountName: A string type that specifies the user login name of the user profile to retrieve social comments for.

url: A string type that specifies the URI to retrieve social comments for. This value **MUST** be fewer than or equal to 2,084 characters and **MUST** be URI format.

3.1.4.19.2.2 GetCommentsOfUserOnUrlResponse

The result data for the **GetCommentsOfUserOnUrl** WSDL operation.

```
<xs:element name="GetCommentsOfUserOnUrlResponse"  
  xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>
```

```

    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCommentsOfUserOnUrlResult"
        type="tns:ArrayOfSocialCommentDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetCommentsOfUserOnUrlResult: An **ArrayOfSocialCommentDetail** complex type (section [2.2.4.4](#)) that contains the requested social comments. This element MUST be returned when the operation succeeds. The protocol server MUST limit the results to 1000.

3.1.4.19.3 Complex Types

None.

3.1.4.19.4 Simple Types

None.

3.1.4.19.5 Attributes

None.

3.1.4.19.6 Groups

None.

3.1.4.19.7 Attribute Groups

None.

3.1.4.20 GetCommentsOnUrl

The **GetCommentsOnUrl** operation retrieves all of the social comments for a specified URI and for a specified set of parameters.

```

<wsdl:operation name="GetCommentsOnUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetCommentsOnUrlSoapIn"/>
  <wsdl:output message="tns:GetCommentsOnUrlSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetCommentsOnUrlSoapIn** request message and the protocol server responds with a **GetCommentsOnUrlSoapOut** response message.

3.1.4.20.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetCommentsOnUrlSoapIn	The request WSDL message for the GetCommentsOnUrl WSDL operation.
GetCommentsOnUrlSoapOut	The response WSDL message for the GetCommentsOnUrl WSDL operation.

3.1.4.20.1.1 GetCommentsOnUrlSoapIn

The request WSDL message for the **GetCommentsOnUrl** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetCommentsOnUrl
```

The SOAP body contains the **GetCommentsOnUrl** element.

3.1.4.20.1.2 GetCommentsOnUrlSoapOut

The response WSDL message for the **GetCommentsOnUrl** WSDL operation.

The SOAP body contains the **GetCommentsOnUrlResponse** element.

3.1.4.20.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetCommentsOnUrl	The input data for the GetCommentsOnUrl WSDL operation.
GetCommentsOnUrlResponse	The result data for the GetCommentsOnUrl WSDL operation.

3.1.4.20.2.1 GetCommentsOnUrl

The input data for the **GetCommentsOnUrl** WSDL operation.

```
<xs:element name="GetCommentsOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn" nillable="true"
type="xs:int"/>
      <xs:element minOccurs="1" maxOccurs="1" name="startIndex" nillable="true"
type="xs:int"/>
      <xs:element minOccurs="1" maxOccurs="1" name="excludeItemsTime" nillable="true"
type="xs:dateTime"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI to get social comments for. This value MUST be fewer than or equal to 2084 characters and MUST be URI format.

maximumItemsToReturn: An integer type that specifies the maximum number of social comments to return. This value MUST be greater than or equal to zero or **null**. If this value is zero or **null**, then the protocol server MUST limit the number of social comments that are returned to 1000.

startIndex: An integer type that specifies the zero-based index into the total set of comments retrievable by this operation for which the returned set starts. The protocol server MUST NOT include any comments with indices that are less than the specified value. This value MUST be greater than or equal to zero, or **null**. If this value is zero or **null**, then the protocol server MUST use the first social comment in the total set of comments retrievable by this operation as the starting value when returning the social comments.

excludeItemsTime: A dateTime value that specifies a cut-off point for returning the social comments. The protocol server MUST limit the results by returning only those social comments that were modified after the time that is specified by this value. If this value is **null**, then the protocol server MUST NOT limit the results based on the date when a social comment was last modified.

3.1.4.20.2.2 GetCommentsOnUrlResponse

The result data for the **GetCommentsOnUrl** WSDL operation.

```
<xs:element name="GetCommentsOnUrlResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCommentsOnUrlResult"
type="tns:ArrayOfSocialCommentDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetCommentsOnUrlResult: An **ArrayOfSocialCommentDetail** complex type (section [2.2.4.2](#)) that contains the requested social comments. This element MUST be returned when the operation succeeds.

3.1.4.20.3 Complex Types

None.

3.1.4.20.4 Simple Types

None.

3.1.4.20.5 Attributes

None.

3.1.4.20.6 Groups

None.

3.1.4.20.7 Attribute Groups

None.

3.1.4.21 GetRatingAverageOnUrl

The **GetRatingAverageOnUrl** operation retrieves the average social rating for the item at a specified URI.

```
<wsdl:operation name="GetRatingAverageOnUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetRatingAverageOnUrlSoapIn"/>
  <wsdl:output message="tns:GetRatingAverageOnUrlSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetRatingAverageOnUrlSoapIn** request message and the protocol server responds with a **GetRatingAverageOnUrlSoapOut** response message.

If the current user does not have permissions to view the social ratings on the specified **url**, the protocol server **MUST** send a SOAP fault message.

3.1.4.21.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetRatingAverageOnUrlSoapIn	The request WSDL message for the GetRatingAverageOnUrl WSDL operation.
GetRatingAverageOnUrlSoapOut	The response WSDL message for the GetRatingAverageOnUrl WSDL operation.

3.1.4.21.1.1 GetRatingAverageOnUrlSoapIn

The request WSDL message for the **GetRatingAverageOnUrl** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRatingAverageOnU
rl
```

The SOAP body contains the **GetRatingAverageOnUrl** element.

3.1.4.21.1.2 GetRatingAverageOnUrlSoapOut

The response WSDL message for the **GetRatingAverageOnUrl** WSDL operation.

The SOAP body contains the **GetRatingAverageOnUrlResponse** element.

3.1.4.21.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetRatingAverageOnUrl	The input data for the GetRatingAverageOnUrl WSDL operation.
GetRatingAverageOnUrlResponse	The result data for the GetRatingAverageOnUrl WSDL operation.

3.1.4.21.2.1 GetRatingAverageOnUrl

The input data for the **GetRatingAverageOnUrl** WSDL operation.

```
<xs:element name="GetRatingAverageOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI of the item to get the average social rating for. This value MUST be fewer than 2,085 characters and MUST be URI format.

3.1.4.21.2.2 GetRatingAverageOnUrlResponse

The result data for the **GetRatingAverageOnUrl** WSDL operation.

```
<xs:element name="GetRatingAverageOnUrlResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetRatingAverageOnUrlResult"
type="tns:SocialRatingAverageDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetRatingAverageOnUrlResult: A **SocialRatingAverageDetail** complex type (section [3.1.4.21.3.1](#)) that contains the average social rating that is being requested.

If no social ratings are associated with the current user, then the protocol server MUST set the value of the **CurrentUserRating** element of the **SocialRatingAverageDetail** complex type to zero.

If no social ratings are associated with the specified URI, then the protocol server MUST set the value of the **LastModifiedTime** element of the **SocialRatingAverageDetail** complex type to the minimum dateTime value.

If no social ratings are associated with the specified URI, then the protocol server MUST set the value of the **Average** element of the **SocialRatingAverageDetail** complex type to negative infinity.

If no social ratings are associated with the specified URI, then the protocol server **MUST** set the **Count** element of the **SocialRatingAverageDetail** complex type to the minimum long value.

3.1.4.21.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
SocialRatingAverageDetail	

3.1.4.21.3.1 SocialRatingAverageDetail

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **SocialRatingAverageDetail** complex type contains information about the social ratings that are associated with a URI.

```
<xs:complexType name="SocialRatingAverageDetail" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Url" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Average" type="xs:float"/>
    <xs:element minOccurs="1" maxOccurs="1" name="LastModifiedTime" type="xs:dateTime"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Count" type="xs:long"/>
    <xs:element minOccurs="1" maxOccurs="1" name="CurrentUserRating" type="xs:int"/>
  </xs:sequence>
</xs:complexType>
```

Url: A string type that specifies the URI of the item that the average social rating is associated with.

Average: A floating-point number that indicates the average of the social ratings that are associated with any user profile for the specified URI.

LastModifiedTime: A **dateTime** value that indicates when the social rating data was last modified for the specified URI.

Count: A long type that specifies the total number of social ratings that are associated with any user profile for the specified URI.

CurrentUserRating: An integer type that specifies the social rating that the current user provided for the specified URI.

3.1.4.21.4 Simple Types

None.

3.1.4.21.5 Attributes

None.

3.1.4.21.6 Groups

None.

3.1.4.21.7 Attribute Groups

None.

3.1.4.22 GetRatingOfUserOnUrl

The **GetRatingOfUserOnUrl** operation retrieves a social rating that is associated with a specified user profile and for a specified URI.

```
<wsdl:operation name="GetRatingOfUserOnUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetRatingOfUserOnUrlSoapIn"/>
  <wsdl:output message="tns:GetRatingOfUserOnUrlSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetRatingOfUserOnUrlSoapIn** request message and the protocol server responds with a **GetRatingOfUserOnUrlSoapOut** response message.

If the current user does not have permission to view the specified user profile, then the protocol server MUST send a SOAP fault message. If the current user does not have permission to view the social rating for the specified **userAccountName** on the specified **url**, the protocol server MUST send a SOAP fault message. If the specified user profile does not exist, then the protocol server MUST send a SOAP fault message.

3.1.4.22.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetRatingOfUserOnUrlSoapIn	The request WSDL message for the GetRatingOfUserOnUrl WSDL operation.
GetRatingOfUserOnUrlSoapOut	The response WSDL message for the GetRatingOfUserOnUrl WSDL operation.

3.1.4.22.1.1 GetRatingOfUserOnUrlSoapIn

The request WSDL message for the **GetRatingOfUserOnUrl** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRatingOfUserOnUr  
1
```

The SOAP body contains the **GetRatingOfUserOnUrl** element.

3.1.4.22.1.2 GetRatingOfUserOnUrlSoapOut

The response WSDL message for the **GetRatingOfUserOnUrl** WSDL operation.

The SOAP body contains the **GetRatingOfUserOnUrlResponse** element.

3.1.4.22.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetRatingOfUserOnUrl	The input data for the GetRatingOfUserOnUrl WSDL operation.
GetRatingOfUserOnUrlResponse	The result data for the GetRatingOfUserOnUrl WSDL operation.

3.1.4.22.2.1 GetRatingOfUserOnUrl

The input data for the **GetRatingOfUserOnUrl** WSDL operation.

```
<xs:element name="GetRatingOfUserOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

userAccountName: A string type that specifies the user login name of the user profile to retrieve the social rating for.

url: A string type that specifies the URI to retrieve the social rating for. This value **MUST** be fewer than or equal to 2,084 characters and **MUST** be URI format.

3.1.4.22.2.2 GetRatingOfUserOnUrlResponse

The result data for the **GetRatingOfUserOnUrl** WSDL operation.

```
<xs:element name="GetRatingOfUserOnUrlResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetRatingOfUserOnUrlResult"
type="tns:SocialRatingDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetRatingOfUserOnUrlResult: A **SocialRatingDetail** complex type (section [2.2.4.16](#)) that contains the requested social rating. If no social rating is associated with the specified **userAccountName**, then the protocol server **MUST** set the **Rating** value of the

SocialRatingDetail type to zero and the **LastModifiedTime** value of the **SocialRatingDetail** type to the minimum value.

3.1.4.22.3 Complex Types

None.

3.1.4.22.4 Simple Types

None.

3.1.4.22.5 Attributes

None.

3.1.4.22.6 Groups

None.

3.1.4.22.7 Attribute Groups

None.

3.1.4.23 GetRatingOnUrl

The **GetRatingOnUrl** operation retrieves a social rating that was added by the current user for a specified URI.

```
<wsdl:operation name="GetRatingOnUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetRatingOnUrlSoapIn"/>
  <wsdl:output message="tns:GetRatingOnUrlSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetRatingOnUrlSoapIn** request message and the protocol server responds with a **GetRatingOnUrlSoapOut** response message.

The protocol server MUST return only the social rating that is associated with both the current user and a specified URI. If the current user does not have permission to view the social rating on the specified **url**, the protocol server MUST send a SOAP fault message.

3.1.4.23.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetRatingOnUrlSoapIn	The request WSDL message for the GetRatingOnUrl WSDL operation.
GetRatingOnUrlSoapOut	The response WSDL message for the GetRatingOnUrl WSDL operation.

3.1.4.23.1.1 GetRatingOnUrlSoapIn

The request WSDL message for the **GetRatingOnUrl** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRatingOnUrl
```

The SOAP body contains the **GetRatingOnUrl** element.

3.1.4.23.1.2 GetRatingOnUrlSoapOut

The response WSDL message for the **GetRatingOnUrl** WSDL operation.

The SOAP body contains the **GetRatingOnUrlResponse** element.

3.1.4.23.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetRatingOnUrl	The input data for the GetRatingOnUrl WSDL operation.
GetRatingOnUrlResponse	The result data for the GetRatingOnUrl WSDL operation.

3.1.4.23.2.1 GetRatingOnUrl

The input data for the **GetRatingOnUrl** WSDL operation.

```
<xs:element name="GetRatingOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

url: A string type that specifies the URI that is associated with the social rating to retrieve. This value MUST be fewer than or equal to 2,084 characters and MUST be URI format.

3.1.4.23.2.2 GetRatingOnUrlResponse

The result data for the **GetRatingOnUrl** WSDL operation.

```
<xs:element name="GetRatingOnUrlResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" maxOccurs="1" name="GetRatingOnUrlResult"  
        type="tns:SocialRatingDetail"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

```
</xs:complexType>
</xs:element>
```

GetRatingOnUrlResult: A **SocialRatingDetail** complex type (section [2.2.4.16](#)) that contains the requested social rating. If no social rating is associated with the current user for the specific URI, then the protocol server **MUST** set the **Rating** value of the **SocialRatingDetail** type to zero and the **LastModifiedTime** value of the **SocialRatingDetail** type to the minimum value.

3.1.4.23.3 Complex Types

None.

3.1.4.23.4 Simple Types

None.

3.1.4.23.5 Attributes

None.

3.1.4.23.6 Groups

None.

3.1.4.23.7 Attribute Groups

None.

3.1.4.24 GetRatingsOfUser

The **GetRatingsOfUser** operation retrieves the social ratings that are associated with a specified user profile.

```
<wsdl:operation name="GetRatingsOfUser" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetRatingsOfUserSoapIn"/>
  <wsdl:output message="tns:GetRatingsOfUserSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetRatingsOfUserSoapIn** request message and the protocol server responds with a **GetRatingsOfUserSoapOut** response message.

If the specified user profile does not exist, then the protocol server **MUST** send a SOAP fault message.

3.1.4.24.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetRatingsOfUserSoapIn	The request WSDL message for the GetRatingsOfUser WSDL operation.
GetRatingsOfUserSoapOut	The response WSDL message for the GetRatingsOfUser WSDL operation.

3.1.4.24.1.1 GetRatingsOfUserSoapIn

The request WSDL message for the **GetRatingsOfUser** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRatingsOfUser
```

The SOAP body contains the **GetRatingsOfUser** element.

3.1.4.24.1.2 GetRatingsOfUserSoapOut

The response WSDL message for the **GetRatingsOfUser** WSDL operation.

The SOAP body contains the **GetRatingsOfUserResponse** element.

3.1.4.24.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetRatingsOfUser	The input data for the GetRatingsOfUser WSDL operation.
GetRatingsOfUserResponse	The result data for the GetRatingsOfUser WSDL operation.

3.1.4.24.2.1 GetRatingsOfUser

The input data for the **GetRatingsOfUser** WSDL operation.

```
<xs:element name="GetRatingsOfUser" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

userAccountName: A string type that specifies the user login name of the user profile to retrieve social ratings for.

3.1.4.24.2.2 GetRatingsOfUserResponse

The result data for the **GetRatingsOfUser** WSDL operation.

```

<xs:element name="GetRatingsOfUserResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetRatingsOfUserResult"
type="tns:ArrayOfSocialRatingDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetRatingsOfUserResult: An **ArrayOfSocialRatingDetail** complex type (section [2.2.4.5](#)) that contains the requested social ratings. This element **MUST** be returned when the operation succeeds. The protocol server **MUST** limit the results to 1000.

3.1.4.24.3 Complex Types

None.

3.1.4.24.4 Simple Types

None.

3.1.4.24.5 Attributes

None.

3.1.4.24.6 Groups

None.

3.1.4.24.7 Attribute Groups

None.

3.1.4.25 GetRatingsOnUrl

The **GetRatingsOnUrl** operation retrieves all of the social ratings for a specified URI.

```

<wsdl:operation name="GetRatingsOnUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetRatingsOnUrlSoapIn"/>
  <wsdl:output message="tns:GetRatingsOnUrlSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetRatingsOnUrlSoapIn** request message and the protocol server responds with a **GetRatingsOnUrlSoapOut** response message.

3.1.4.25.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetRatingsOnUrlSoapIn	The request WSDL message for the GetRatingsOnUrl WSDL operation.
GetRatingsOnUrlSoapOut	The response WSDL message for the GetRatingsOnUrl WSDL operation.

3.1.4.25.1.1 GetRatingsOnUrlSoapIn

The request WSDL message for the **GetRatingsOnUrl** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRatingsOnUrl
```

The SOAP body contains the **GetRatingsOnUrl** element.

3.1.4.25.1.2 GetRatingsOnUrlSoapOut

The response WSDL message for the **GetRatingsOnUrl** WSDL operation.

The SOAP body contains the **GetRatingsOnUrlResponse** element.

3.1.4.25.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetRatingsOnUrl	The input data for the GetRatingsOnUrl WSDL operation.
GetRatingsOnUrlResponse	The result data for the GetRatingsOnUrl WSDL operation.

3.1.4.25.2.1 GetRatingsOnUrl

The input data for the **GetRatingsOnUrl** WSDL operation.

```
<xs:element name="GetRatingsOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI to retrieve social ratings for. This value MUST be fewer than or equal to 2,084 characters and MUST be URI format.

3.1.4.25.2.2 GetRatingsOnUrlResponse

The result data for the **GetRatingsOnUrl** WSDL operation.

```

<xs:element name="GetRatingsOnUrlResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetRatingsOnUrlResult"
type="tns:ArrayOfSocialRatingDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetRatingsOnUrlResult: An **ArrayOfSocialRatingDetail** complex type (section [2.2.4.5](#)) that contains the social ratings for the specified URI. This element **MUST** be returned when the operation succeeds.

3.1.4.25.3 Complex Types

None.

3.1.4.25.4 Simple Types

None.

3.1.4.25.5 Attributes

None.

3.1.4.25.6 Groups

None.

3.1.4.25.7 Attribute Groups

None.

3.1.4.26 GetSocialDataForFullReplication

The **GetSocialDataForFullReplication** operation retrieves the list of existing social comments, social tags and social ratings for a specified user profile for use when replicating the social data.

```

<wsdl:operation name="GetSocialDataForFullReplication"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetSocialDataForFullReplicationSoapIn"/>
  <wsdl:output message="tns:GetSocialDataForFullReplicationSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetSocialDataForFullReplicationSoapIn** request message and the protocol server responds with a **GetSocialDataForFullReplicationSoapOut** response message.

The protocol server **MUST** return the social data elements that are associated to the specified user profile.

3.1.4.26.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetSocialDataForFullReplicationSoapIn	The request WSDL message for the GetSocialDataForFullReplication WSDL operation.
GetSocialDataForFullReplicationSoapOut	The response WSDL message for the GetSocialDataForFullReplication WSDL operation.

3.1.4.26.1.1 GetSocialDataForFullReplicationSoapIn

The request WSDL message for the **GetSocialDataForFullReplication** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetSocialDataForFullReplication
```

The SOAP body contains the **GetSocialDataForFullReplication** element.

3.1.4.26.1.2 GetSocialDataForFullReplicationSoapOut

The response WSDL message for the **GetSocialDataForFullReplication** WSDL operation.

The SOAP body contains the **GetSocialDataForFullReplicationResponse** element.

3.1.4.26.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetSocialDataForFullReplication	The input data for the GetSocialDataForFullReplication WSDL operation.
GetSocialDataForFullReplicationResponse	The result data for the GetSocialDataForFullReplication WSDL operation.

3.1.4.26.2.1 GetSocialDataForFullReplication

The input data for the **GetSocialDataForFullReplication** WSDL operation.

```
<xs:element name="GetSocialDataForFullReplication"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```
</xs:complexType>
</xs:element>
```

userAccountName: A string type that specifies the user login name of the user profile to retrieve the existing social data elements for. If the user profile for the specified user name does not exist, the protocol server MUST send a SOAP fault message.

3.1.4.26.2.2 GetSocialDataForFullReplicationResponse

The result data for the **GetSocialDataForFullReplication** WSDL operation.

```
<xs:element name="GetSocialDataForFullReplicationResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetSocialDataForFullReplicationResult"
        type="tns:SocialReplicationData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetSocialDataForFullReplicationResult: A **SocialReplicationData** (section [2.2.4.17](#)) containing the existing social comments, social tags and social ratings for the specified user profile. The protocol server MUST return null for the **DeletedTags**, **DeletedComments** and **DeletedRatings** fields (1) of the **SocialReplicationData** object.

3.1.4.26.3 Complex Types

None.

3.1.4.26.4 Simple Types

None.

3.1.4.26.5 Attributes

None.

3.1.4.26.6 Groups

None.

3.1.4.26.7 Attribute Groups

None.

3.1.4.27 GetSocialDataForIncrementalReplication

The **GetSocialDataForIncrementalReplication** operation retrieves the list of existing and deleted social comments, social tags and social ratings for a specified time period.

```

<wsdl:operation name="GetSocialDataForIncrementalReplication"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetSocialDataForIncrementalReplicationSoapIn"/>
  <wsdl:output message="tns:GetSocialDataForIncrementalReplicationSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetSocialDataForIncrementalReplicationSoapIn** request message and the protocol server responds with a **GetSocialDataForIncrementalReplicationSoapOut** response message.

The protocol server MUST return the social data elements that are associated to the specified time period.

3.1.4.27.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetSocialDataForIncrementalReplicationSoapIn	The request WSDL message for the GetSocialDataForIncrementalReplication WSDL operation.
GetSocialDataForIncrementalReplicationSoapOut	The response WSDL message for the GetSocialDataForIncrementalReplication WSDL operation.

3.1.4.27.1.1 GetSocialDataForIncrementalReplicationSoapIn

The request WSDL message for the **GetSocialDataForIncrementalReplication** WSDL operation.

The SOAP action value is:

```

http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetSocialDataForIncrementalReplication

```

The SOAP body contains the **GetSocialDataForIncrementalReplication** element.

3.1.4.27.1.2 GetSocialDataForIncrementalReplicationSoapOut

The response WSDL message for the **GetSocialDataForIncrementalReplication** WSDL operation.

The SOAP body contains the **GetSocialDataForIncrementalReplicationResponse** element.

3.1.4.27.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetSocialDataForIncrementalReplication	The input data for the GetSocialDataForIncrementalReplication WSDL operation.
GetSocialDataForIncrementalReplicationResponse	The result data for the GetSocialDataForIncrementalReplication WSDL operation.

3.1.4.27.2.1 GetSocialDataForIncrementalReplication

The input data for the **GetSocialDataForIncrementalReplication** WSDL operation.

```
<xs:element name="GetSocialDataForIncrementalReplication"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="startTime" type="xs:dateTime"/>
      <xs:element minOccurs="1" maxOccurs="1" name="endTime" type="xs:dateTime"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

startTime: A dateTime value used to limit the results. The protocol server MUST NOT return the existing and deleted social comments, social tags and social ratings which were last modified or deleted before this time.

endTime: A dateTime value used to limit the results. The protocol server MUST NOT return the existing and deleted social comments, social tags and social ratings which were last modified or deleted after or equal to this time.

3.1.4.27.2.2 GetSocialDataForIncrementalReplicationResponse

The result data for the **GetSocialDataForIncrementalReplication** WSDL operation.

```
<xs:element name="GetSocialDataForIncrementalReplicationResponse"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1"
name="GetSocialDataForIncrementalReplicationResult" type="tns:SocialReplicationData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetSocialDataForIncrementalReplicationResult: A **SocialReplicationData** (section [2.2.4.17](#)) containing the existing and deleted social comments, social tags and social ratings limited by the specified **startTime** and **endTime**.

3.1.4.27.3 Complex Types

None.

3.1.4.27.4 Simple Types

None.

3.1.4.27.5 Attributes

None.

3.1.4.27.6 Groups

None.

3.1.4.27.7 Attribute Groups

None.

3.1.4.28 GetTags

The **GetTags** operation retrieves the social tags that were created by the current user for a specified URL.

```
<wsdl:operation name="GetTags" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetTagsSoapIn"/>
  <wsdl:output message="tns:GetTagsSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetTagsSoapIn** request message and the protocol server responds with a **GetTagsSoapOut** response message.

3.1.4.28.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetTagsSoapIn	The request WSDL message for the GetTags WSDL operation.
GetTagsSoapOut	The response WSDL message for the GetTags WSDL operation.

3.1.4.28.1.1 GetTagsSoapIn

The request WSDL message for the **GetTags** WSDL operation.

The SOAP action value is:

<http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTags>

The SOAP body contains the **GetTags** element.

3.1.4.28.1.2 GetTagsSoapOut

The response WSDL message for the **GetTags** WSDL operation.

The SOAP body contains the **GetTagsResponse** element.

3.1.4.28.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetTags	The input data for the GetTags WSDL operation.
GetTagsResponse	The result data for the GetTags WSDL operation.

3.1.4.28.2.1 GetTags

The input data for the **GetTags** WSDL operation.

```
<xs:element name="GetTags" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URL to retrieve social tags for.

3.1.4.28.2.2 GetTagsResponse

The result data for the **GetTags** WSDL operation.

```
<xs:element name="GetTagsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagsResult"
        type="tns:ArrayOfSocialTagDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetTagsResult: An **ArrayOfSocialTagDetail** complex type (section [2.2.4.6](#)) that contains the results. This element **MUST** be returned when the operation succeeds. There **MUST** be one entry for each social tag that was created by the current user and is associated with the specified URL. The protocol server **MUST** limit the results to 1000.

3.1.4.28.3 Complex Types

None.

3.1.4.28.4 Simple Types

None.

3.1.4.28.5 Attributes

None.

3.1.4.28.6 Groups

None.

3.1.4.28.7 Attribute Groups

None.

3.1.4.29 GetTagsOfUser

The **GetTagsOfUser** operation retrieves the social tags that were added by a specified user.

```
<wsdl:operation name="GetTagsOfUser" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetTagsOfUserSoapIn"/>
  <wsdl:output message="tns:GetTagsOfUserSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetTagsOfUserSoapIn** request message and the protocol server responds with a **GetTagsOfUserSoapOut** response message.

If the specified user profile does not exist, then the protocol server MUST send a SOAP fault message

3.1.4.29.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetTagsOfUserSoapIn	The request WSDL message for the GetTagsOfUser WSDL operation.
GetTagsOfUserSoapOut	The response WSDL message for the GetTagsOfUser WSDL operation.

3.1.4.29.1.1 GetTagsOfUserSoapIn

The request WSDL message for the **GetTagsOfUser** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagsOfUser
```

The SOAP body contains the **GetTagsOfUser** element.

3.1.4.29.1.2 GetTagsOfUserSoapOut

The response WSDL message for the **GetTagsOfUser** WSDL operation.

The SOAP body contains the **GetTagsOfUserResponse** element.

3.1.4.29.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetTagsOfUser	The input data for the GetTagsOfUser WSDL operation.
GetTagsOfUserResponse	The result data for the GetTagsOfUser WSDL operation.

3.1.4.29.2.1 GetTagsOfUser

The input data for the **GetTagsOfUser** WSDL operation.

```
<xs:element name="GetTagsOfUser" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn" nillable="true"
type="xs:int"/>
      <xs:element minOccurs="1" maxOccurs="1" name="startIndex" nillable="true"
type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

userAccountName: A string type that specifies the user login name of the social tag user to retrieve results for. If the specified account does not reference an existing social tag user, the protocol server MUST send a SOAP fault message.

maximumItemsToReturn: An integer type that specifies the maximum number of social tags to return. This value MUST be greater than or equal to zero or **null**. When zero or **null** is passed, the protocol server MUST return a maximum of 1000 results.

startIndex: An integer type that specifies the zero-based index into the total set of social tags retrievable by this operation for which the returned set starts. The protocol server MUST NOT include any social tags with indices that are less than the specified value. This value MUST NOT be negative. If the value is zero or **null**, the protocol server MUST NOT limit the results based on this value.

3.1.4.29.2.2 GetTagsOfUserResponse

The result data for the **GetTagsOfUser** WSDL operation.

```
<xs:element name="GetTagsOfUserResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
```



```

    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagsOfUserResult"
        type="tns:ArrayOfSocialTagDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetTagsOfUserResult: An **ArrayOfSocialTagDetail** complex type (section [2.2.4.6](#)) that contains the results. This element MUST be returned when the operation succeeds. Unless trimmed from the results, there MUST be one entry for each social tag that was added by the user who is specified by the **userAccountName** element. The results MUST be trimmed such that the values of the **maximumItemsToReturn** and **startIndex** elements are respected.

3.1.4.29.3 Complex Types

None.

3.1.4.29.4 Simple Types

None.

3.1.4.29.5 Attributes

None.

3.1.4.29.6 Groups

None.

3.1.4.29.7 Attribute Groups

None.

3.1.4.30 GetTagTerms

The **GetTagTerms** operation retrieves only social tag terms that were authored by the current user.

```

<wsdl:operation name="GetTagTerms" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetTagTermsSoapIn"/>
  <wsdl:output message="tns:GetTagTermsSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **GetTagTermsSoapIn** request message and the protocol server responds with a **GetTagTermsSoapOut** response message.

3.1.4.30.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetTagTermsSoapIn	The request WSDL message for the GetTagTerms WSDL operation.
GetTagTermsSoapOut	The response WSDL message for the GetTagTerms WSDL operation.

3.1.4.30.1.1 GetTagTermsSoapIn

The request WSDL message for the **GetTagTerms** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagTerms
```

The SOAP body contains the **GetTagTerms** element.

3.1.4.30.1.2 GetTagTermsSoapOut

The response WSDL message for the **GetTagTerms** WSDL operation.

The SOAP body contains the **GetTagTermsResponse** element.

3.1.4.30.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetTagTerms	The input data for the GetTagTerms WSDL operation.
GetTagTermsResponse	The result data for the GetTagTerms WSDL operation.

3.1.4.30.2.1 GetTagTerms

The input data for the **GetTagTerms** WSDL operation.

```
<xs:element name="GetTagTerms" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn" nillable="true"
type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

maximumItemsToReturn: An integer type that specifies the maximum number of social tag terms to return. This value **MUST** be greater than or equal to zero and less than 3001 or null. When zero or **null** is passed, the protocol server **MUST** return a maximum of 1000 results.

3.1.4.30.2 GetTagTermsResponse

The result data for the **GetTagTerms** WSDL operation.

```
<xs:element name="GetTagTermsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagTermsResult"
type="tns:ArrayOfSocialTermDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetTagTermsResult: An **ArrayOfSocialTermDetails** complex type (section [2.2.4.7](#)) that contains the results in descending order on the **SocialTermDetail Count** value. This element **MUST** be returned when the operation succeeds. There **MUST** be one entry for each social tag term for the current user, up to any maximum number of entries, as defined by the value of the **maximumItemsToReturn** element. The protocol server **MUST** trim the results by removing all elements after the first N elements, where N is specified by the value of the **maximumItemsToReturn** element.

3.1.4.30.3 Complex Types

None.

3.1.4.30.4 Simple Types

None.

3.1.4.30.5 Attributes

None.

3.1.4.30.6 Groups

None.

3.1.4.30.7 Attribute Groups

None.

3.1.4.31 GetTagTermsOfUser

The **GetTagTermsOfUser** operation retrieves the social tag terms that were authored by a specific social tag user. The result set can be limited to a maximum number of items.

```
<wsdl:operation name="GetTagTermsOfUser" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetTagTermsOfUserSoapIn"/>
  <wsdl:output message="tns:GetTagTermsOfUserSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetTagTermsOfUserSoapIn** request message and the protocol server responds with a **GetTagTermsOfUserSoapOut** response message.

3.1.4.31.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetTagTermsOfUserSoapIn	The request WSDL message for the GetTagTermsOfUser WSDL operation.
GetTagTermsOfUserSoapOut	The response WSDL message for the GetTagTermsOfUser WSDL operation.

3.1.4.31.1.1 GetTagTermsOfUserSoapIn

The request WSDL message for the **GetTagTermsOfUser** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagTermsOfUser
```

The SOAP body contains the **GetTagTermsOfUser** element.

3.1.4.31.1.2 GetTagTermsOfUserSoapOut

The response WSDL message for the **GetTagTermsOfUser** WSDL operation.

The SOAP body contains the **GetTagTermsOfUserResponse** element.

3.1.4.31.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetTagTermsOfUser	The input data for the GetTagTermsOfUser WSDL operation.
GetTagTermsOfUserResponse	The result data for the GetTagTermsOfUser WSDL operation.

3.1.4.31.2.1 GetTagTermsOfUser

The input data for the **GetTagTermsOfUser** WSDL operation.

```
<xs:element name="GetTagTermsOfUser" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

        <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn" nillable="true"
type="xs:int"/>
    </xs:sequence>
</xs:complexType>
</xs:element>

```

userAccountName: A string type that contains the user login name that is associated with the social tag terms to query for. This argument **MUST NOT** be **NULL**. If the specified user login name does not reference an existing social tag user, the protocol server **MUST** return a SOAP fault message.

maximumItemsToReturn: An integer type that specifies the maximum number of items to return. This value **MUST** be greater than or equal to zero and less than 3001 or **null**. When zero or **null** is passed, the protocol server **MUST** return a maximum of 1000 results.

3.1.4.31.2.2 GetTagTermsOfUserResponse

The result data for the **GetTagTermsOfUser** WSDL operation.

```

<xs:element name="GetTagTermsOfUserResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagTermsOfUserResult"
type="tns:ArrayOfSocialTermDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetTagTermsOfUserResult: An **ArrayOfSocialTermDetail** complex type (section [2.2.4.7](#)) that contains the results. This element **MUST** be returned when the operation succeeds. There **MUST** be one entry for each term that was created by the specified social tag user, and no more than the maximum number of results specified by the value of the **maximumItemsToReturn** element. The protocol server **MUST** trim the results by removing all elements after the first N elements, where N is specified by the value of the **maximumItemsToReturn** element.

3.1.4.31.3 Complex Types

None.

3.1.4.31.4 Simple Types

None.

3.1.4.31.5 Attributes

None.

3.1.4.31.6 Groups

None.

3.1.4.31.7 Attribute Groups

None.

3.1.4.32 GetTagTermsOnUrl

The **GetTagTermsOnUrl** operation retrieves the social tag terms for a specified social tag URL.

```
<wsdl:operation name="GetTagTermsOnUrl" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetTagTermsOnUrlSoapIn"/>
  <wsdl:output message="tns:GetTagTermsOnUrlSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetTagTermsOnUrlSoapIn** request message and the protocol server responds with a **GetTagTermsOnUrlSoapOut** response message.

3.1.4.32.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetTagTermsOnUrlSoapIn	The request WSDL message for the GetTagTermsOnUrl WSDL operation.
GetTagTermsOnUrlSoapOut	The response WSDL message for the GetTagTermsOnUrl WSDL operation.

3.1.4.32.1.1 GetTagTermsOnUrlSoapIn

The request WSDL message for the **GetTagTermsOnUrl** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagTermsOnUrl
```

The SOAP body contains the **GetTagTermsOnUrl** element.

3.1.4.32.1.2 GetTagTermsOnUrlSoapOut

The response WSDL message for the **GetTagTermsOnUrl** WSDL operation.

The SOAP body contains the **GetTagTermsOnUrlResponse** element.

3.1.4.32.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetTagTermsOnUrl	The input data for the GetTagTermsOnUrl WSDL operation.

Element	Description
GetTagTermsOnUrlResponse	The result data for the GetTagTermsOnUrl WSDL operation.

3.1.4.32.2.1 GetTagTermsOnUrl

The input data for the **GetTagTermsOnUrl** WSDL operation.

```
<xs:element name="GetTagTermsOnUrl" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn" nillable="true"
type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the social tag URL to retrieve results for. This value **MUST** be fewer than or equal to 2,084 characters and **MUST** be URI format.

maximumItemsToReturn: An integer type that specifies the maximum number of items to return. This value **MUST** be greater than or equal to "0" (zero) and less than 1001 or null. When "0" (zero) or null is passed, the protocol server **MUST** return a maximum of 100 results.

3.1.4.32.2.2 GetTagTermsOnUrlResponse

The result data for the **GetTagTermsOnUrl** WSDL operation.

```
<xs:element name="GetTagTermsOnUrlResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagTermsOnUrlResult"
type="tns:ArrayOfSocialTermDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetTagTermsOnUrlResult: An **ArrayOfSocialTermDetail** complex type (section [2.2.4.7](#)) that contains the results in descending order on the **SocialTermDetail Count** value. This element **MUST** be returned when the operation succeeds. There **MUST** be one entry for each term, up to any maximum number of entries, as defined by the value of the **maximumItemsToReturn** element. The protocol server **MUST** trim the results by removing all elements after the first N elements, where N is specified by the value of the **maximumItemsToReturn** element.

3.1.4.32.3 Complex Types

None.

3.1.4.32.4 Simple Types

None.

3.1.4.32.5 Attributes

None.

3.1.4.32.6 Groups

None.

3.1.4.32.7 Attribute Groups

None.

3.1.4.33 GetTagUrls

The **GetTagUrls** operation retrieves the social tag URLs that were tagged by the current user with a specified social tag term.

```
<wsdl:operation name="GetTagUrls" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetTagUrlsSoapIn"/>
  <wsdl:output message="tns:GetTagUrlsSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetTagUrlsSoapIn** request message and the protocol server responds with a **GetTagUrlsSoapOut** response message.

3.1.4.33.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetTagUrlsSoapIn	The request WSDL message for the GetTagUrls WSDL operation.
GetTagUrlsSoapOut	The response WSDL message for the GetTagUrls WSDL operation.

3.1.4.33.1.1 GetTagUrlsSoapIn

The request WSDL message for the **GetTagUrls** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagUrls
```

The SOAP body contains the **GetTagUrls** element.

3.1.4.33.1.2 GetTagUrlsSoapOut

The response WSDL message for the **GetTagUrls** WSDL operation.

The SOAP body contains the **GetTagUrlsResponse** element.

3.1.4.33.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetTagUrls	The input data for the GetTagUrls WSDL operation.
GetTagUrlsResponse	The result data for the GetTagUrls WSDL operation.

3.1.4.33.2.1 GetTagUrls

The input data for the **GetTagUrls** WSDL operation.

```
<xs:element name="GetTagUrls" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="termID"
        xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

termID: A GUID type that identifies the social tag term to retrieve results for. If the specified value does not reference an existing social tag term, the protocol server MUST send a SOAP fault message.

3.1.4.33.2.2 GetTagUrlsResponse

The result data for the **GetTagUrls** WSDL operation.

```
<xs:element name="GetTagUrlsResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagUrlsResult"
        type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetTagUrlsResult: An **ArrayOfString** complex type (section [2.2.4.9](#)) that contains the results. This element MUST be returned when the operation succeeds. There MUST be one entry for each social tag URL for the specified social tag term. The protocol server MUST limit the results to 400.

3.1.4.33.3 Complex Types

None.

3.1.4.33.4 Simple Types

None.

3.1.4.33.5 Attributes

None.

3.1.4.33.6 Groups

None.

3.1.4.33.7 Attribute Groups

None.

3.1.4.34 GetTagUrlsByKeyword

The **GetTagUrlsByKeyword** operation retrieves the social tag URLs, tagged with a specified keyword, which are associated to the current user.

```
<wsdl:operation name="GetTagUrlsByKeyword" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetTagUrlsByKeywordSoapIn"/>
  <wsdl:output message="tns:GetTagUrlsByKeywordSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetTagUrlsByKeywordSoapIn** request message and the protocol server responds with a **GetTagUrlsByKeywordSoapOut** response message.

3.1.4.34.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetTagUrlsByKeywordSoapIn	The request WSDL message for the GetTagUrlsByKeyword WSDL operation.
GetTagUrlsByKeywordSoapOut	The response WSDL message for the GetTagUrlsByKeyword WSDL operation.

3.1.4.34.1.1 GetTagUrlsByKeywordSoapIn

The request WSDL message for the **GetTagUrlsByKeyword** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagUrlsByKeyword
```

The SOAP body contains the **GetTagUrlsByKeyword** element.

3.1.4.34.1.2 GetTagUrlsByKeywordSoapOut

The response WSDL message for the **GetTagUrlsByKeyword** WSDL operation.

The SOAP body contains the **GetTagUrlsByKeywordResponse** element.

3.1.4.34.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetTagUrlsByKeyword	The input data for the GetTagUrlsByKeyword WSDL operation.
GetTagUrlsByKeywordResponse	The result data for the GetTagUrlsByKeyword WSDL operation.

3.1.4.34.2.1 GetTagUrlsByKeyword

The input data for the **GetTagUrlsByKeyword** WSDL operation.

```
<xs:element name="GetTagUrlsByKeyword" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

keyword: A string type that specifies the social tag term to query for. This value matches the **Name** value of an existing **TermDetail** complex type (section [2.2.4.21](#)). If the specified value is not an existing social tag term, the protocol server **MUST** send a SOAP fault message.

3.1.4.34.2.2 GetTagUrlsByKeywordResponse

The result data for the **GetTagUrlsByKeyword** WSDL operation.

```
<xs:element name="GetTagUrlsByKeywordResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagUrlsByKeywordResult"
type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetTagUrlsByKeywordResult: An **ArrayOfString** complex type (section [2.2.4.9](#)) that contains the results of the query. This element **MUST** be returned when the operation succeeds. There **MUST** be exactly one entry for each social tag URL that is associated with the specified social tag term. The protocol server **MUST** limit the results to 400.

3.1.4.34.3 Complex Types

None.

3.1.4.34.4 Simple Types

None.

3.1.4.34.5 Attributes

None.

3.1.4.34.6 Groups

None.

3.1.4.34.7 Attribute Groups

None.

3.1.4.35 GetTagUrlsOfUser

The **GetTagUrlsOfUser** operation retrieves the social tag URLs that are associated with a specified social tag term and were added by a specified social tag user.

```
<wsdl:operation name="GetTagUrlsOfUser" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetTagUrlsOfUserSoapIn"/>
  <wsdl:output message="tns:GetTagUrlsOfUserSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetTagUrlsOfUserSoapIn** request message and the protocol server responds with a **GetTagUrlsOfUserSoapOut** response message.

3.1.4.35.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetTagUrlsOfUserSoapIn	The request WSDL message for the GetTagUrlsOfUser WSDL operation.
GetTagUrlsOfUserSoapOut	The response WSDL message for the GetTagUrlsOfUser WSDL operation.

3.1.4.35.1.1 GetTagUrlsOfUserSoapIn

The request WSDL message for the **GetTagUrlsOfUser** WSDL operation.

The SOAP action value is:

<http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagUrlsOfUser>

The SOAP body contains the **GetTagUrlsOfUser** element.

3.1.4.35.1.2 GetTagUrlsOfUserSoapOut

The response WSDL message for the **GetTagUrlsOfUser** WSDL operation.

The SOAP body contains the **GetTagUrlsOfUserResponse** element.

3.1.4.35.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetTagUrlsOfUser	The input data for the GetTagUrlsOfUser WSDL operation.
GetTagUrlsOfUserResponse	The result data for the GetTagUrlsOfUser WSDL operation.

3.1.4.35.2.1 GetTagUrlsOfUser

The input data for the **GetTagUrlsOfUser** WSDL operation.

```
<xs:element name="GetTagUrlsOfUser" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="termID"
        xmlns:s1="http://microsoft.com/wsdl/types/" type="s1:guid"/>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

termID: A GUID type that specifies the identifier of the social tag term to query for. If the specified value does not reference an existing social tag term, the protocol server MUST send a SOAP fault message.

userAccountName: A string type that specifies the user login name of the user who added a social tag with the specified social tag term. The protocol server MUST return only those social tags that were added by the specified social tag user. If the specified social tag user does not exist, the protocol server MUST send a SOAP fault message.

3.1.4.35.2.2 GetTagUrlsOfUserResponse

The result data for the **GetTagUrlsOfUser** WSDL operation.

```
<xs:element name="GetTagUrlsOfUserResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagUrlsOfUserResult"
        type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetTagUrlsOfUserResult: An **ArrayOfString** complex type (section [2.2.4.9](#)) that contains the results. This element **MUST** be returned when the operation succeeds. There **MUST** be exactly one entry for each social tag URL that was tagged with the specified social tag term by the specified user. The protocol server **MUST** limit the results to 400.

3.1.4.35.3 Complex Types

None.

3.1.4.35.4 Simple Types

None.

3.1.4.35.5 Attributes

None.

3.1.4.35.6 Groups

None.

3.1.4.35.7 Attribute Groups

None.

3.1.4.36 GetTagUrlsOfUserByKeyword

The **GetTagUrlsOfUserByKeyword** operation retrieves the social tag URLs that are associated with a specified social tag term and were added by a specified social tag user.

```
<wsdl:operation name="GetTagUrlsOfUserByKeyword"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetTagUrlsOfUserByKeywordSoapIn"/>
  <wsdl:output message="tns:GetTagUrlsOfUserByKeywordSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **GetTagUrlsOfUserByKeywordSoapIn** request message and the protocol server responds with a **GetTagUrlsOfUserByKeywordSoapOut** response message.

3.1.4.36.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
GetTagUrlsOfUserByKeywordSoapIn	The request WSDL message for the GetTagUrlsOfUserByKeyword WSDL operation.
GetTagUrlsOfUserByKeywordSoapOut	The response WSDL message for the GetTagUrlsOfUserByKeyword WSDL operation.

3.1.4.36.1.1 GetTagUrlsOfUserByKeywordSoapIn

The request WSDL message for the **GetTagUrlsOfUserByKeyword** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagUrlsOfUserByKeyword
```

The SOAP body contains the **GetTagUrlsOfUserByKeyword** element.

3.1.4.36.1.2 GetTagUrlsOfUserByKeywordSoapOut

The response WSDL message for the **GetTagUrlsOfUserByKeyword** WSDL operation.

The SOAP body contains the **GetTagUrlsOfUserByKeywordResponse** element.

3.1.4.36.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetTagUrlsOfUserByKeyword	The input data for the GetTagUrlsOfUserByKeyword WSDL operation.
GetTagUrlsOfUserByKeywordResponse	The result data for the GetTagUrlsOfUserByKeyword WSDL operation.

3.1.4.36.2.1 GetTagUrlsOfUserByKeyword

The input data for the **GetTagUrlsOfUserByKeyword** WSDL operation.

```
<xs:element name="GetTagUrlsOfUserByKeyword" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

keyword: A string type that specifies the social tag term to query for. This value matches the **Name** value of an existing **TermDetail** complex type (section [2.2.4.21](#)). If the specified value is not an existing social tag term, the protocol server MUST send a SOAP fault message.

userAccountName: A string type that specifies the user login name of the social tag user to query for. If the specified social tag user does not exist, the protocol server MUST send a SOAP fault message.

3.1.4.36.2 GetTagUrlsOfUserByKeywordResponse

The result data for the **GetTagUrlsOfUserByKeyword** WSDL operation.

```
<xs:element name="GetTagUrlsOfUserByKeywordResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagUrlsOfUserByKeywordResult"
        type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetTagUrlsOfUserByKeywordResult: An **ArrayOfString** complex type (section [2.2.4.9](#)) that contains the results. This element **MUST** be returned when the operation succeeds. There **MUST** be exactly one entry for each social tag URL that is associated with the specified social tag term and was authored by the specified social tag user. The protocol server **MUST** limit the results to 400.

3.1.4.36.3 Complex Types

None.

3.1.4.36.4 Simple Types

None.

3.1.4.36.5 Attributes

None.

3.1.4.36.6 Groups

None.

3.1.4.36.7 Attribute Groups

None.

3.1.4.37 PropagateRating

The **PropagateRating** operation triggers a recalculation of the current, average social rating for the specified URI that points to a protocol server list item and it stores that new value in the **Rating** field (2).

```
<wsdl:operation name="PropagateRating" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:PropagateRatingSoapIn"/>
  <wsdl:output message="tns:PropagateRatingSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **PropagateRatingSoapIn** request message and the protocol server responds with a **PropagateRatingSoapOut** response message.

3.1.4.37.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
PropagateRatingSoapIn	The request WSDL message for the PropagateRating WSDL operation.
PropagateRatingSoapOut	The response WSDL message for the PropagateRating WSDL operation.

3.1.4.37.1.1 PropagateRatingSoapIn

The request WSDL message for the **PropagateRating** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/PropagateRating
```

The SOAP body contains the **PropagateRating** element.

3.1.4.37.1.2 PropagateRatingSoapOut

The response WSDL message for the **PropagateRating** WSDL operation.

The SOAP body contains the **PropagateRatingResponse** element.

3.1.4.37.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
PropagateRating	The input data for the PropagateRating WSDL operation.
PropagateRatingResponse	The result data for the PropagateRating WSDL operation.

3.1.4.37.2.1 PropagateRating

The input data for the **PropagateRating** WSDL operation.

```
<xs:element name="PropagateRating" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the URI of a protocol server list item whose metadata to update with the current, average social rating.

3.1.4.37.2 PropagateRatingResponse

The result data for the **PropagateRating** WSDL operation.

```
<xs:element name="PropagateRatingResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType/>
</xs:element>
```

3.1.4.37.3 Complex Types

None.

3.1.4.37.4 Simple Types

None.

3.1.4.37.5 Attributes

None.

3.1.4.37.6 Groups

None.

3.1.4.37.7 Attribute Groups

None.

3.1.4.38 ReplicateFullSocialData

The **ReplicateFullSocialData** operation replicates the specified social comments, social tags and social ratings for a specified user profile to the server.

```
<wsdl:operation name="ReplicateFullSocialData" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:ReplicateFullSocialDataSoapIn"/>
  <wsdl:output message="tns:ReplicateFullSocialDataSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **ReplicateFullSocialDataSoapIn** request message and the protocol server responds with a **ReplicateFullSocialDataSoapOut** response message.

3.1.4.38.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ReplicateFullSocialDataSoapIn	The request WSDL message for the ReplicateFullSocialData WSDL operation.

Message	Description
ReplicateFullSocialDataSoapOut	The response WSDL message for the ReplicateFullSocialData WSDL operation.

3.1.4.38.1.1 ReplicateFullSocialDataSoapIn

The request WSDL message for the **ReplicateFullSocialData** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/ReplicateFullSocialData
```

The SOAP body contains the **ReplicateFullSocialData** element.

3.1.4.38.1.2 ReplicateFullSocialDataSoapOut

The response WSDL message for the **ReplicateFullSocialData** WSDL operation.

The SOAP body contains the **ReplicateFullSocialDataResponse** element.

3.1.4.38.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
ReplicateFullSocialData	The input data for the ReplicateFullSocialData WSDL operation.
ReplicateFullSocialDataResponse	The result data for the ReplicateFullSocialData WSDL operation.

3.1.4.38.2.1 ReplicateFullSocialData

The input data for the **ReplicateFullSocialData** WSDL operation.

```
<xs:element name="ReplicateFullSocialData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="changes"
type="tns:SocialReplicationData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

userAccountName: A string type that specifies the user login name of the user profile that the specified social data comments, social tags and social ratings should be replicated for. This value MUST NOT be **null** or empty.

changes: A **SocialReplicationData** complex type (section [2.2.4.17](#)) that contains the existing social comments, social tags and social ratings to replicate. The **DeletedComments**, **DeletedTags** and **DeletedRatings** fields (1) on this value MUST be **null**. This value MUST NOT be **null**.

3.1.4.38.2 ReplicateFullSocialDataResponse

The result data for the **ReplicateFullSocialData** WSDL operation.

```
<xs:element name="ReplicateFullSocialDataResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="ReplicateFullSocialDataResult"
        type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

ReplicateFullSocialDataResult: A Boolean value that contains the status of the operation. A value of **true** indicates success. A value of **false** indicates failure.

The protocol server MUST return a value of **false** if the specified user profile could not be found. The protocol server MUST return a value of **false** if **DeletedComments**, **DeletedTags** or **DeletedRatings** field (1) on **changes** is not **null**. The protocol server MUST return a value of **false** if the **Comments**, **Tags** or **Ratings** field (1) contain elements whose **Owner** field (1) is not equal to the specified user profile user name. The protocol server MUST return a value of **false** if there is a failure when replicating any data to the server.

3.1.4.38.3 Complex Types

None.

3.1.4.38.4 Simple Types

None.

3.1.4.38.5 Attributes

None.

3.1.4.38.6 Groups

None.

3.1.4.38.7 Attribute Groups

None.

3.1.4.39 ReplicateIncrementalSocialData

The **ReplicateIncrementalSocialData** operation replicates the specified existing and deleted social comments, social tags and social ratings to the server.

```

<wsdl:operation name="ReplicateIncrementalSocialData"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:ReplicateIncrementalSocialDataSoapIn"/>
  <wsdl:output message="tns:ReplicateIncrementalSocialDataSoapOut"/>
</wsdl:operation>

```

The protocol client sends a **ReplicateIncrementalSocialDataSoapIn** request message and the protocol server responds with a **ReplicateIncrementalSocialDataSoapOut** response message.

3.1.4.39.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
ReplicateIncrementalSocialDataSoapIn	The request WSDL message for the ReplicateIncrementalSocialData WSDL operation.
ReplicateIncrementalSocialDataSoapOut	The response WSDL message for the ReplicateIncrementalSocialData WSDL operation.

3.1.4.39.1.1 ReplicateIncrementalSocialDataSoapIn

The request WSDL message for the **ReplicateIncrementalSocialData** WSDL operation.

The SOAP action value is:

```

http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/ReplicateIncrementalSocialData

```

The SOAP body contains the **ReplicateIncrementalSocialData** element.

3.1.4.39.1.2 ReplicateIncrementalSocialDataSoapOut

The response WSDL message for the **ReplicateIncrementalSocialData** WSDL operation.

The SOAP body contains the **ReplicateIncrementalSocialDataResponse** element.

3.1.4.39.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
ReplicateIncrementalSocialData	The input data for the ReplicateIncrementalSocialData WSDL operation.
ReplicateIncrementalSocialDataResponse	The result data for the ReplicateIncrementalSocialData WSDL operation.

3.1.4.39.2.1 ReplicateIncrementalSocialData

The input data for the **ReplicateIncrementalSocialData** WSDL operation.

```
<xs:element name="ReplicateIncrementalSocialData"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="changes"
        type="tns:SocialReplicationData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

changes: A **SocialReplicationData** complex type (section [2.2.4.17](#)) that contains the existing and deleted social comments, social tags and social ratings to replicate. This value **MUST NOT** be null.

3.1.4.39.2.2 ReplicateIncrementalSocialDataResponse

The result data for the **ReplicateIncrementalSocialData** WSDL operation.

```
<xs:element name="ReplicateIncrementalSocialDataResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="ReplicateIncrementalSocialDataResult"
        type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

ReplicateIncrementalSocialDataResult: A Boolean value that contains the status of the operation. A value of **true** indicates success. A value of **false** indicates failure.

The protocol server **MUST** return a value of **false** if there is a failure when replicating any data to the server.

3.1.4.39.3 Complex Types

None.

3.1.4.39.4 Simple Types

None.

3.1.4.39.5 Attributes

None.

3.1.4.39.6 Groups

None.

3.1.4.39.7 Attribute Groups

None.

3.1.4.40 SetRating

The **SetRating** operation specifies a social rating by the current user for a specified URI.

```
<wsdl:operation name="SetRating" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:SetRatingSoapIn"/>
  <wsdl:output message="tns:SetRatingSoapOut"/>
</wsdl:operation>
```

The protocol client sends a **SetRatingSoapIn** request message and the protocol server responds with a **SetRatingSoapOut** response message. The protocol server MUST store the rating information, along with the time at which the rating was stored.

3.1.4.40.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
SetRatingSoapIn	The request WSDL message for the SetRating WSDL operation.
SetRatingSoapOut	The response WSDL message for the SetRating WSDL operation.

3.1.4.40.1.1 SetRatingSoapIn

The request WSDL message for the **SetRating** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/SetRating
```

The SOAP body contains the **SetRating** element.

3.1.4.40.1.2 SetRatingSoapOut

The response WSDL message for the **SetRating** WSDL operation.

The SOAP body contains the **SetRatingResponse** element.

3.1.4.40.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
SetRating	The input data for the SetRating WSDL operation.
SetRatingResponse	The result data for the SetRating WSDL operation.

3.1.4.40.2.1 SetRating

The input data for the **SetRating** WSDL operation.

```
<xs:element name="SetRating" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="rating" type="xs:int"/>
      <xs:element minOccurs="0" maxOccurs="1" name="title" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="analysisDataEntry"
type="tns:FeedbackData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string type that specifies the **URL** of the item to apply the social rating to.

rating: An integer type that specifies the rating value for the item. This value **MUST** be an integer between 1 and 5 inclusive, where 1 is the lowest rating and 5 is the highest rating possible.

title: A string type that specifies the title of the social rating, as it appears to users. This value **MUST** be fewer than or equal to 500 characters.

analysisDataEntry: A **FeedbackData** complex type (section [3.1.4.40.3.1](#)) that contains data about the social rating that is used to generate usage logging.

3.1.4.40.2.2 SetRatingResponse

The result data for the **SetRating** WSDL operation.

```
<xs:element name="SetRatingResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="SetRatingResult" type="xs:dateTime"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

SetRatingResult: A **dateTime** value that contains a **timestamp** indicating when the social rating was stored.

3.1.4.40.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
FeedbackData	

3.1.4.40.3.1 FeedbackData

Namespace: http://microsoft.com/webservices/SharePointPortalServer/SocialDataService

The **FeedbackData** type contains data about a social rating that is used to generate usage logging.

```
<xs:complexType name="FeedbackData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="BrowserSessionId" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="CustomData"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FeedbackAnswerId"
      xmlns:s1="http://microsoft.com/wsd/types/" type="s1:guid"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FeedbackAnswerNumericEquivalent"
      type="xs:int"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FeedbackAnswerText" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FeedbackControlCulture" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FeedbackIdentifier"
      xmlns:s1="http://microsoft.com/wsd/types/" type="s1:guid"/>
    <xs:element minOccurs="1" maxOccurs="1" name="FeedbackQuestionId"
      xmlns:s1="http://microsoft.com/wsd/types/" type="s1:guid"/>
    <xs:element minOccurs="0" maxOccurs="1" name="FeedbackQuestionText" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="IsUserSatisfactionAnswer"
      type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="QueryId"
      xmlns:s1="http://microsoft.com/wsd/types/" type="s1:guid"/>
    <xs:element minOccurs="0" maxOccurs="1" name="RatedAssetId" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="RatedAssetTitle" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SampleRate" type="xs:unsignedByte"/>
    <xs:element minOccurs="1" maxOccurs="1" name="RatedAssetWebId"
      xmlns:s1="http://microsoft.com/wsd/types/" type="s1:guid"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SiteId"
      xmlns:s1="http://microsoft.com/wsd/types/" type="s1:guid"/>
    <xs:element minOccurs="0" maxOccurs="1" name="UserId" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="UserDepartment" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="UserTitle" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="UserVerbatim" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

BrowserSessionId: A string type that contains the identifier that was assigned to the instance of the Web browser session's **SessionId** field that was active when the operation was called.

CustomData: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

FeedbackAnswerId: A GUID value that MUST be "a970c91c-28cb-4656-9b28-1fc1c9f87725".

FeedbackAnswerNumericEquivalent: An integer type that specifies the rating number to store. The value MUST be in the range of 0-100 inclusive.

FeedbackAnswerText: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

FeedbackControlCulture: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

FeedbackIdentifier: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

FeedbackQuestionId: A GUID value that MUST be "b471a6c6-c2c6-412e-aa07-96b0ed29eb30".

FeedbackQuestionText: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

IsUserSatisfactionAnswer: A Boolean value that MUST be **true**.

QueryId: A GUID value that MUST be "00000000-0000-0000-0000-000000000000".

RatedAssetId: A string type that specifies the URL to which the feedback data applies. This value MUST be the same as the value of the **url** element of the **SetRating** request that specified this **FeedbackData** complex type.

RatedAssetTitle: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

SampleRate: An unsigned byte value that MUST be 100.

RatedAssetWebId: A GUID type that identifies the site containing the item to which to apply the rating.

SiteId: A GUID type that identifies the site collection containing the item to which to apply the rating.

UserId: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

UserDepartment: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

UserName: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

UserVerbatim: Ignored. This element MUST NOT be set by client. The protocol server MUST ignore this value.

3.1.4.40.4 Simple Types

None.

3.1.4.40.5 Attributes

None.

3.1.4.40.6 Groups

None.

3.1.4.40.7 Attribute Groups

None.

3.1.4.41 UpdateComment

The **UpdateComment** operation updates an existing social comment at a specified URI that was created by the calling user with the specified last modified time.

```
<wsdl:operation name="UpdateComment" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:UpdateCommentSoapIn"/>
  <wsdl:output message="tns:UpdateCommentSoapOut"/>
</wsdl:operation>
```

The protocol client sends an **UpdateCommentSoapIn** request message and the protocol server responds with an **UpdateCommentSoapOut** response message.

If the comment is not found at the specified URI created by the calling user with the specified time of last modification, the protocol server **MUST** return the current UTC time. The **Title** of a social comment cannot be updated using this operation.

3.1.4.41.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
UpdateCommentSoapIn	The request WSDL message for the UpdateComment WSDL operation.
UpdateCommentSoapOut	The response WSDL message for the UpdateComment WSDL operation.

3.1.4.41.1.1 UpdateCommentSoapIn

The request WSDL message for the **UpdateComment** WSDL operation.

The SOAP action value is:

```
http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/UpdateComment
```

The SOAP body contains the **UpdateComment** element.

3.1.4.41.1.2 UpdateCommentSoapOut

The response WSDL message for the **UpdateComment** WSDL operation.

The SOAP body contains the **UpdateCommentResponse** element.

3.1.4.41.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
UpdateComment	The input data for the UpdateComment WSDL operation.
UpdateCommentResponse	The result data for the UpdateComment WSDL operation.

3.1.4.41.2.1 UpdateComment

The input data for the **UpdateComment** WSDL operation.

```
<xs:element name="UpdateComment" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="lastModifiedTime" type="xs:dateTime"/>
      <xs:element minOccurs="0" maxOccurs="1" name="comment" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="isHighPriority" type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

url: A string that specifies the URI that is associated with the social comment to update. This value MUST be fewer than 2085 characters and MUST be URI format.

lastModifiedTime: A **dateTime** value that indicates when the social comment to update was last modified.

comment: A string that contains the body of the social comment. This value MUST contain at least one character and fewer than ,001 characters.

isHighPriority: A Boolean that indicates the priority level of the social comment. A value of **true** indicates that the social comment is high priority. A value of **false** indicates that the social comment is normal priority.

3.1.4.41.2.2 UpdateCommentResponse

The result data for the **UpdateComment** WSDL operation.

```
<xs:element name="UpdateCommentResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="UpdateCommentResult" type="xs:dateTime"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

UpdateCommentResult: A **dateTime** value that indicates the UTC time when this operation was called.

3.1.4.41.3 Complex Types

None.

3.1.4.41.4 Simple Types

None.

3.1.4.41.5 Attributes

None.

3.1.4.41.6 Groups

None.

3.1.4.41.7 Attribute Groups

None.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

4.1 Add Social Data to a URI

In this scenario, the current user wants to add a social comment and a social tag to a Web page. The protocol client uses the **AddComment** and **AddTagByKeyword** operations to add the data.

The protocol client starts by sending the following **AddComment** request:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <AddComment
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <url>http://server.example.com/page</url>
      <comment>I enjoyed reading this page and will return to it later for
reference.</comment>
      <isHighPriority>>false</isHighPriority>
      <title>Reference Page</title>
    </AddComment>
  </soap:Body>
</soap:Envelope>
```

The protocol server stores this information and sends the following response:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <AddCommentResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <AddCommentResult>
        <Url>http://server.example.com/page</Url>
        <Owner>USERNAME</Owner>
        <LastModifiedTime>2009-05-08T19:32:27.847</LastModifiedTime>
        <Comment>I enjoyed reading this page and will return to it later for
reference.</Comment>
        <IsHighPriority>>false</IsHighPriority>
        <Title>Reference Page</Title>
      </AddCommentResult>
    </AddCommentResponse>
  </soap:Body>
</soap:Envelope>
```

The user also wants to add a social tag. Therefore, the protocol client then sends the following [AddTagByKeyword](#) request:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
```

```

    <soap:Body>
      <AddTagByKeyword
        xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
        <url>http://server.example.com/page</url>
        <keyword>for future reference</keyword>
        <title>Reference Page</title>
        <isPrivate>>false</isPrivate>
      </AddTagByKeyword>
    </soap:Body>
  </soap:Envelope>

```

The protocol server stores this information and sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <AddTagByKeywordResponse
      xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <AddTagByKeywordResult>
        <Url>http://server.example.com/page</Url>
        <Owner>USERNAME</Owner>
        <LastModifiedTime>2009-05-08T19:46:06.513</LastModifiedTime>
        <Term>
          <Id>e62b6078-456f-4b4d-8497-c4037f54f9e8</Id>
          <Name>for future reference</Name>
        </Term>
        <Title>Reference Page</Title>
        <IsPrivate>>false</IsPrivate>
      </AddTagByKeywordResult>
    </AddTagByKeywordResponse>
  </soap:Body>
</soap:Envelope>

```

4.2 View Social Data Comments

In this scenario, the current user wants to see the number of social comments that they have added and the social comments that they have added to a specific page.

The protocol client starts by sending the following **CountCommentsOfUser** request:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CountCommentsOfUser
      xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <userAccountName>USERNAME</userAccountName>
    </CountCommentsOfUser>
  </soap:Body>
</soap:Envelope>

```

The protocol server sends the following response:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CountCommentsOfUserResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <CountCommentsOfUserResult>3</CountCommentsOfUserResult>
    </CountCommentsOfUserResponse>
  </soap:Body>
</soap:Envelope>
```

The protocol client then sends the following **CountCommentsOnUrl** request:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CountCommentsOnUrl
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <url>http://server.example.com/page</url>
    </CountCommentsOnUrl>
  </soap:Body>
</soap:Envelope>
```

The protocol server sends the following response:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CountCommentsOnUrlResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <CountCommentsOnUrlResult>1</CountCommentsOnUrlResult>
    </CountCommentsOnUrlResponse>
  </soap:Body>
</soap:Envelope>
```

To verify that this social comment was added by the current user, the protocol client then sends the following **CountCommentsOfUserOnUrl** request:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CountCommentsOfUserOnUrl
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <userAccountName>USERNAME</userAccountName>
      <url>http://server.example.com/page</url>
    </CountCommentsOfUserOnUrl>
  </soap:Body>
</soap:Envelope>
```



```

    </CountCommentsOfUserOnUrl>
  </soap:Body>
</soap:Envelope>

```

The protocol server sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CountCommentsOfUserOnUrlResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <CountCommentsOfUserOnUrlResult>1</CountCommentsOfUserOnUrlResult>
    </CountCommentsOfUserOnUrlResponse>
  </soap:Body>
</soap:Envelope>

```

Finally, the protocol client requests the complete social comment for this URI by sending the following **GetCommentsOnUrl** request:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetCommentsOnUrl
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <url>http://server.example.com/page</url>
      <maximumItemsToReturn>5</maximumItemsToReturn>
      <startIndex>0</startIndex>
      <excludeItemsTime>2009-05-07T00:00:00</excludeItemsTime>
    </GetCommentsOnUrl>
  </soap:Body>
</soap:Envelope>

```

The protocol server sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetCommentsOnUrlResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <GetCommentsOnUrlResult>
        <SocialCommentDetail>
          <Url>http://server.example.com/page</Url>
          <Owner>USERNAME</Owner>
          <LastModifiedTime>2009-05-08T19:32:27.847</LastModifiedTime>
          <Comment>I enjoyed reading this page and will return to it later for
reference.</Comment>
          <IsHighPriority>>false</IsHighPriority>
          <Title>Reference Page</Title>
        </SocialCommentDetail>
      </GetCommentsOnUrlResult>
    </GetCommentsOnUrlResponse>
  </soap:Body>
</soap:Envelope>

```

```

        </SocialCommentDetail>
    </GetCommentsOnUrlResult>
</GetCommentsOnUrlResponse>
</soap:Body>
</soap:Envelope>

```

4.3 Delete Social Data Comments

In this scenario, the current user wants to delete a social comment that they added. This example assumes that the protocol client knows the value of the **LastModifiedTime** element of the social comment to delete. The protocol client starts by sending the following **DeleteComment** request to the protocol server:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
        <DeleteComment
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
            <url>http://server.example.com/page</url>
            <lastModifiedTime>2009-05-08T19:32:27.847</lastModifiedTime>
        </DeleteComment>
    </soap:Body>
</soap:Envelope>

```

The protocol server deletes the social comment and sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
        <DeleteCommentResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService" />
    </soap:Body>
</soap:Envelope>

```

4.4 Find Social Data Tags

In this scenario, the current user wants to see a list of their social tags and other URIs that have the same social tags.

The protocol client starts by sending the following **GetTagsOfUser** request:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
        <GetTagsOfUser
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
            <userAccountName>USERNAME</userAccountName>
        </GetTagsOfUser>
    </soap:Body>
</soap:Envelope>

```

```

        <maximumItemsToReturn>100</maximumItemsToReturn>
        <startIndex>0</startIndex>
    </GetTagsOfUser>
</soap:Body>
</soap:Envelope>

```

The protocol server sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetTagsOfUserResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <GetTagsOfUserResult>
        <SocialTagDetail>
          <Url>http://server.example.com/page</Url>
          <Owner>USERNAME</Owner>
          <LastModifiedTime>2009-05-08T19:46:06.513</LastModifiedTime>
          <Term>
            <Id>e62b6078-456f-4b4d-8497-c4037f54f9e8</Id>
            <Name>for future reference</Name>
          </Term>
          <Title>Reference Page</Title>
          <IsPrivate>>false</IsPrivate>
        </SocialTagDetail>
      </GetTagsOfUserResult>
    </GetTagsOfUserResponse>
  </soap:Body>
</soap:Envelope>

```

The current user is interested in other URIs that have the same social tag. To retrieve these URIs, the protocol client sends the following **GetTagUrls** request:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetTagUrls
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <termID>e62b6078-456f-4b4d-8497-c4037f54f9e8</termID>
    </GetTagUrls>
  </soap:Body>
</soap:Envelope>

```

The protocol server sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>

```

```

    <GetTagUrlsResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
    <GetTagUrlsResult>
        <string>http://server.example.com/page</string>
        <string>http://server.example.com/page2</string>
    </GetTagUrlsResult>
    </GetTagUrlsResponse>
</soap:Body>
</soap:Envelope>

```

4.5 Delete Social Data Tags

In this scenario, the current user wants to delete a social tag that they created, as described in the preceding examples. This example assumes that the protocol client has saved the value of the **termID** element for the social tag.

The protocol client sends the following **DeleteTag** request:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
        <DeleteTag
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
            <url>http://server.example.com/page</url>
            <termID>e62b6078-456f-4b4d-8497-c4037f54f9e8</termID>
        </DeleteTag>
    </soap:Body>
</soap:Envelope>

```

The protocol server deletes the specified social tag and sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
        <DeleteTagResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService" />
    </soap:Body>
</soap:Envelope>

```

4.6 Add Social Ratings to a URI

In this example, the current user wants to add a social rating to a document. The protocol client does this by sending the following **SetRating** request:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>

```

```

    <SetRating
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
  <url>http://server.example.com/document</url>
  <rating>5</rating>
  <title>Title</title>
  <analysisDataEntry>
    <BrowserSessionId></BrowserSessionId>
    <FeedbackAnswerId>a970c91c-28cb-4656-9b28-1fc1c9f87725</FeedbackAnswerId>
    <FeedbackAnswerNumericEquivalent>5</FeedbackAnswerNumericEquivalent>
    <FeedbackQuestionId>b471a6c6-c2c6-412e-aa07-96b0ed29eb30</FeedbackQuestionId>
    <IsUserSatisfactionAnswer>1</IsUserSatisfactionAnswer>
    <RatedAssetId>http://server.example.com/document</RatedAssetId>
    <SampleRate>100</SampleRate>
    <RatedAssetWebId>2a01a954-1db0-45c9-942a-38f0288c8591</RatedAssetWebId>
    <SiteId>58cdfd10-f3a7-4528-97e2-6f6e8a077aba</SiteId>
  </analysisDataEntry>
</SetRating>
</soap:Body>
</soap:Envelope>

```

The protocol server stores this information and sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <SetRatingResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <SetRatingResult>2009-05-08T23:59:06.17</SetRatingResult>
    </SetRatingResponse>
  </soap:Body>
</soap:Envelope>

```

4.7 Find Information about Social Ratings

In this scenario, the current user wants to see the average rating for a document, and then progressively get more information about the social ratings for that document and their social ratings for other documents.

The protocol client starts by sending the following **GetRatingAverageOnUrl** request:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetRatingAverageOnUrl
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <url>http://server.example.com/document</url>
    </GetRatingAverageOnUrl>
  </soap:Body>
</soap:Envelope>

```

The protocol server sends the following response:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetRatingAverageOnUrlResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <GetRatingAverageOnUrlResult>
        <Url>http://server.example.com/document</Url>
        <Average>2.75</Average>
        <LastModifiedTime>2009-05-11T17:14:44.26</LastModifiedTime>
        <Count>4</Count>
        <CurrentUserRating>5</CurrentUserRating>
      </GetRatingAverageOnUrlResult>
    </GetRatingAverageOnUrlResponse>
  </soap:Body>
</soap:Envelope>
```

The current user now wants to see details for all four social ratings for the document. The protocol client sends the following **GetRatingsOnUrl** request:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetRatingsOnUrl
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <url>http://server.example.com/document</url>
    </GetRatingsOnUrl>
  </soap:Body>
</soap:Envelope>
```

The protocol server sends the following response:

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetRatingsOnUrlResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <GetRatingsOnUrlResult>
        <SocialRatingDetail>
          <Url>http://server.example.com/document</Url>
          <Owner>USERNAME</Owner>
          <LastModifiedTime>2009-05-08T23:59:06.17</LastModifiedTime>
          <Title>Title</Title>
          <Rating>5</Rating>
        </SocialRatingDetail>
        <SocialRatingDetail>
          <Url>http://server.example.com/document</Url>
          <Owner>USERNAME1</Owner>
```

```

        <LastModifiedTime>2009-05-11T17:14:43.683</LastModifiedTime>
        <Title>Title2</Title>
        <Rating>1</Rating>
    </SocialRatingDetail>
    <SocialRatingDetail>
        <Url>http://server.example.com/document</Url>
        <Owner>USERNAME2</Owner>
        <LastModifiedTime>2009-05-11T17:14:44.043</LastModifiedTime>
        <Title>Title3</Title>
        <Rating>2</Rating>
    </SocialRatingDetail>
    <SocialRatingDetail>
        <Url>http://server.example.com/document</Url>
        <Owner>USERNAME3</Owner>
        <LastModifiedTime>2009-05-11T17:14:44.26</LastModifiedTime>
        <Title>Title4</Title>
        <Rating>3</Rating>
    </SocialRatingDetail>
</GetRatingsOnUrlResult>
</GetRatingsOnUrlResponse>
</soap:Body>
</soap:Envelope>

```

The current user now wants to know about all the social ratings that were added by a specific user. The protocol client sends the following **GetRatingsOfUser** request:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
        <GetRatingsOfUser
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
            <userAccountName>USERNAME</userAccountName>
        </GetRatingsOfUser>
    </soap:Body>
</soap:Envelope>

```

The protocol server sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
        <GetRatingsOfUserResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
            <GetRatingsOfUserResult>
                <SocialRatingDetail>
                    <Url>http://server.example.com/document</Url>
                    <Owner>USERNAME</Owner>
                    <LastModifiedTime>2009-05-08T23:59:06.17</LastModifiedTime>
                    <Title>Title</Title>
                    <Rating>5</Rating>
                </SocialRatingDetail>
            </GetRatingsOfUserResult>
        </GetRatingsOfUserResponse>
    </soap:Body>
</soap:Envelope>

```

```

        <SocialRatingDetail>
            <Url>http://server.example.com/document2</Url>
            <Owner>USERNAME</Owner>
            <LastModifiedTime>2009-05-08T23:56:07.21</LastModifiedTime>
            <Title>Title2</Title>
            <Rating>4</Rating>
        </SocialRatingDetail>
    </GetRatingsOfUserResult>
</GetRatingsOfUserResponse>
</soap:Body>
</soap:Envelope>

```

4.8 Delete Social Ratings

In this example, the current user wants to delete one of their social ratings.

The protocol client sends the following **DeleteRating** request:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
        <DeleteRating
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
            <url>http://server.example.com/document</url>
        </DeleteRating>
    </soap:Body>
</soap:Envelope>

```

The protocol server deletes the rating and sends the following response:

```

<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
        <DeleteRatingResponse
xmlns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService" />
    </soap:Body>
</soap:Envelope>

```


5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

Preliminary

6 Appendix A: Full WSDL

For ease of implementation, the full WSDL is provided in this appendix.

```
<?xml version="1.0"?>
<wsdl:definitions
xmlns:tns="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:s1="http://microsoft.com/wsdl/types/"
xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:documentation>Social Data Service</wsdl:documentation>
  <wsdl:types>
    <xs:schema elementFormDefault="qualified"
targetNamespace="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService">
      <xs:import namespace="http://microsoft.com/wsdl/types/" />
      <xs:element name="CountCommentsOfUser">
        <xs:complexType>
          <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="CountCommentsOfUserResponse">
        <xs:complexType>
          <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="CountCommentsOfUserResult"
type="xs:int"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="CountCommentsOnUrl">
        <xs:complexType>
          <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="CountCommentsOnUrlResponse">
        <xs:complexType>
          <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="CountCommentsOnUrlResult"
type="xs:int"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="CountCommentsOfUserOnUrl">
        <xs:complexType>
          <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:schema>
  </wsdl:types>

```

```

<xs:element name="CountCommentsOfUserOnUrlResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="CountCommentsOfUserOnUrlResult"
type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetCommentsOfUser">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn"
nillable="true" type="xs:int"/>
      <xs:element minOccurs="1" maxOccurs="1" name="startIndex" nillable="true"
type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetCommentsOfUserResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetCommentsOfUserResult"
type="tns:ArrayOfSocialCommentDetail"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:complexType name="ArrayOfSocialCommentDetail">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialCommentDetail"
nillable="true" type="tns:SocialCommentDetail"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="SocialCommentDetail">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:SocialDataDetail">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Comment" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="IsHighPriority"
type="xs:boolean"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="SocialDataDetail" abstract="true">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Url" type="xs:string"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Owner" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="LastModifiedTime"
type="xs:dateTime"/>
    <xs:element minOccurs="0" maxOccurs="1" name="Title" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:element name="GetCommentsOnUrl">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>

```

```

        <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn"
nillable="true" type="xs:int"/>
        <xs:element minOccurs="1" maxOccurs="1" name="startIndex" nillable="true"
type="xs:int"/>
        <xs:element minOccurs="1" maxOccurs="1" name="excludeItemsTime" nillable="true"
type="xs:dateTime"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="GetCommentsOnUrlResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetCommentsOnUrlResult"
type="tns:ArrayOfSocialCommentDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetCommentsOfUserOnUrl">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetCommentsOfUserOnUrlResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetCommentsOfUserOnUrlResult"
type="tns:ArrayOfSocialCommentDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="AddComment">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="comment" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="isHighPriority" nillable="true"
type="xs:boolean"/>
            <xs:element minOccurs="0" maxOccurs="1" name="title" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="AddCommentResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="AddCommentResult"
type="tns:SocialCommentDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="UpdateComment">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="lastModifiedTime"
type="xs:dateTime"/>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="comment" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="isHighPriority" type="xs:boolean"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="UpdateCommentResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="UpdateCommentResult"
type="xs:dateTime"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteComment">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="lastModifiedTime"
type="xs:dateTime"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteCommentResponse">
    <xs:complexType/>
</xs:element>
<xs:element name="CountRatingsOnUrl">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="CountRatingsOnUrlResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="CountRatingsOnUrlResult"
type="xs:int"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetRatingsOfUser">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetRatingsOfUserResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetRatingsOfUserResult"
type="tns:ArrayOfSocialRatingDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="ArrayOfSocialRatingDetail">
    <xs:sequence>

```

```

        <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialRatingDetail"
nillable="true" type="tns:SocialRatingDetail"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="SocialRatingDetail">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:SocialDataDetail">
            <xs:sequence>
                <xs:element minOccurs="1" maxOccurs="1" name="Rating" type="xs:int"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:element name="GetRatingsOnUrl">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetRatingsOnUrlResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetRatingsOnUrlResult"
type="tns:ArrayOfSocialRatingDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetRatingOnUrl">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetRatingOnUrlResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetRatingOnUrlResult"
type="tns:SocialRatingDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetRatingOfUserOnUrl">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetRatingOfUserOnUrlResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetRatingOfUserOnUrlResult"
type="tns:SocialRatingDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>

```

```

    </xs:complexType>
  </xs:element>
  <xs:element name="SetRating">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="rating" type="xs:int"/>
        <xs:element minOccurs="0" maxOccurs="1" name="title" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="analysisDataEntry"
type="tns:FeedbackData"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="FeedbackData">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="BrowserSessionId" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="CustomData"/>
      <xs:element minOccurs="1" maxOccurs="1" name="FeedbackAnswerId" type="s1:guid"/>
      <xs:element minOccurs="1" maxOccurs="1" name="FeedbackAnswerNumericEquivalent"
type="xs:int"/>
      <xs:element minOccurs="0" maxOccurs="1" name="FeedbackAnswerText"
type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="FeedbackControlCulture"
type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="FeedbackIdentifier" type="s1:guid"/>
      <xs:element minOccurs="1" maxOccurs="1" name="FeedbackQuestionId" type="s1:guid"/>
      <xs:element minOccurs="0" maxOccurs="1" name="FeedbackQuestionText"
type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="IsUserSatisfactionAnswer"
type="xs:boolean"/>
      <xs:element minOccurs="1" maxOccurs="1" name="QueryId" type="s1:guid"/>
      <xs:element minOccurs="0" maxOccurs="1" name="RatedAssetId" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="RatedAssetTitle" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="SampleRate" type="xs:unsignedByte"/>
      <xs:element minOccurs="1" maxOccurs="1" name="RatedAssetWebId" type="s1:guid"/>
      <xs:element minOccurs="1" maxOccurs="1" name="SiteId" type="s1:guid"/>
      <xs:element minOccurs="0" maxOccurs="1" name="UserId" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="UserDepartment" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="UserTitle" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="UserVerbatim" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
  <xs:element name="SetRatingResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="SetRatingResult"
type="xs:dateTime"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="DeleteRating">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="DeleteRatingResponse">

```

```

    <xs:complexType/>
  </xs:element>
  <xs:element name="GetRatingAverageOnUrl">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:complexType name="SocialRatingAverageDetail">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="Url" type="xs:string"/>
      <xs:element minOccurs="1" maxOccurs="1" name="Average" type="xs:float"/>
      <xs:element minOccurs="1" maxOccurs="1" name="LastModifiedTime"
type="xs:dateTime"/>
      <xs:element minOccurs="1" maxOccurs="1" name="Count" type="xs:long"/>
      <xs:element minOccurs="1" maxOccurs="1" name="CurrentUserRating" type="xs:int"/>
    </xs:sequence>
  </xs:complexType>
  <xs:element name="GetRatingAverageOnUrlResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="GetRatingAverageOnUrlResult"
type="tns:SocialRatingAverageDetail"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="PropagateRating">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="PropagateRatingResponse">
    <xs:complexType/>
  </xs:element>
  <xs:element name="CountTagsOfUser">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="CountTagsOfUserResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="CountTagsOfUserResult"
type="xs:int"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetTagTerms">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn"
nillable="true" type="xs:int"/>

```



```

        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="SocialTermDetail">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Term" type="tns:TermDetail"/>
        <xs:element minOccurs="1" maxOccurs="1" name="Count" type="xs:long"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TermDetail">
    <xs:sequence>
        <xs:element minOccurs="1" maxOccurs="1" name="Id" type="s1:guid"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Name" type="xs:string"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfSocialTermDetail">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialTermDetail"
nillable="true" type="tns:SocialTermDetail"/>
    </xs:sequence>
</xs:complexType>
<xs:element name="GetTagTermsResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetTagTermsResult"
type="tns:ArrayOfSocialTermDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetTagTermsOfUser">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn"
nillable="true" type="xs:int"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetTagTermsOfUserResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetTagTermsOfUserResult"
type="tns:ArrayOfSocialTermDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetTagTermsOnUrl">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn"
nillable="true" type="xs:int"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetTagTermsOnUrlResponse">
    <xs:complexType>
        <xs:sequence>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="GetTagTermsOnUrlResult"
type="tns:ArrayOfSocialTermDetail"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="GetAllTagTerms">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn"
nillable="true" type="xs:int"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetAllTagTermsResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetAllTagTermsResult"
type="tns:ArrayOfSocialTermDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetAllTagTermsForUrlFolder">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="urlFolder" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn"
type="xs:int"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetAllTagTermsForUrlFolderResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="GetAllTagTermsForUrlFolderResult"
type="tns:ArrayOfSocialTermDetail"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="GetTags">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="ArrayOfSocialTagDetail">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialTagDetail"
nillable="true" type="tns:SocialTagDetail"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="SocialTagDetail">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:SocialDataDetail">
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="Term" type="tns:TermDetail"/>
                <xs:element minOccurs="1" maxOccurs="1" name="IsPrivate" type="xs:boolean"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

```

```

        </xs:extension>
        </xs:complexContent>
    </xs:complexType>
    <xs:element name="GetTagsResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="GetTagsResult"
type="tns:ArrayOfSocialTagDetail"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="GetTagsOfUser">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
                <xs:element minOccurs="1" maxOccurs="1" name="maximumItemsToReturn"
nillable="true" type="xs:int"/>
                <xs:element minOccurs="1" maxOccurs="1" name="startIndex" nillable="true"
type="xs:int"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="GetTagsOfUserResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="GetTagsOfUserResult"
type="tns:ArrayOfSocialTagDetail"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="GetTagUrls">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="1" maxOccurs="1" name="termID" type="s1:guid"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:complexType name="ArrayOfString">
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
    <xs:element name="GetTagUrlsResponse">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="GetTagUrlsResult"
type="tns:ArrayOfString"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>
    <xs:element name="GetTagUrlsByKeyword">
        <xs:complexType>
            <xs:sequence>
                <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
            </xs:sequence>
        </xs:complexType>
    </xs:element>

```

```

<xs:element name="GetTagUrlsByKeywordResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagUrlsByKeywordResult"
type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetTagUrlsOfUser">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="termID" type="sl:guid"/>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetTagUrlsOfUserResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagUrlsOfUserResult"
type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetTagUrlsOfUserByKeyword">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetTagUrlsOfUserByKeywordResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="GetTagUrlsOfUserByKeywordResult"
type="tns:ArrayOfString"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetAllTagUrls">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="termID" type="sl:guid"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:complexType name="SocialUrlDetail">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="1" name="Url" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="Count" type="xs:long"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfSocialUrlDetail">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="SocialUrlDetail"
nillable="true" type="tns:SocialUrlDetail"/>
  </xs:sequence>
</xs:complexType>

```

```

    </xs:sequence>
  </xs:complexType>
  <xs:element name="GetAllTagUrlsResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="GetAllTagUrlsResult"
type="tns:ArrayOfSocialUrlDetail"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetAllTagUrlsByKeyword">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetAllTagUrlsByKeywordResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="GetAllTagUrlsByKeywordResult"
type="tns:ArrayOfSocialUrlDetail"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="AddTag">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="termID" type="s1:guid"/>
        <xs:element minOccurs="0" maxOccurs="1" name="title" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="isPrivate" nillable="true"
type="xs:boolean"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="AddTagResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="AddTagResult"
type="tns:SocialTagDetail"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="AddTagByKeyword">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="title" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="isPrivate" nillable="true"
type="xs:boolean"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="AddTagByKeywordResponse">
    <xs:complexType>
      <xs:sequence>

```

```

        <xs:element minOccurs="0" maxOccurs="1" name="AddTagByKeywordResult"
type="tns:SocialTagDetail"/>
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="DeleteTag">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
            <xs:element minOccurs="1" maxOccurs="1" name="termID" type="sl:guid"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteTagResponse">
    <xs:complexType/>
</xs:element>
<xs:element name="DeleteTagByKeyword">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
            <xs:element minOccurs="0" maxOccurs="1" name="keyword" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteTagByKeywordResponse">
    <xs:complexType/>
</xs:element>
<xs:element name="DeleteTags">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1" name="url" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="DeleteTagsResponse">
    <xs:complexType/>
</xs:element>
<xs:element name="GetSocialDataForIncrementalReplication">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="1" maxOccurs="1" name="startTime" type="xs:dateTime"/>
            <xs:element minOccurs="1" maxOccurs="1" name="endTime" type="xs:dateTime"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="SocialReplicationData">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Tags"
type="tns:ArrayOfSocialTagDetail"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Comments"
type="tns:ArrayOfSocialCommentDetail"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Ratings"
type="tns:ArrayOfSocialRatingDetail"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DeletedTags"
type="tns:ArrayOfDeletedSocialTagDetail"/>
        <xs:element minOccurs="0" maxOccurs="1" name="DeletedComments"
type="tns:ArrayOfDeletedSocialCommentDetail"/>
    
```

```

        <xs:element minOccurs="0" maxOccurs="1" name="DeletedRatings"
type="tns:ArrayOfDeletedSocialRatingDetail"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfDeletedSocialTagDetail">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="DeletedSocialTagDetail"
nillable="true" type="tns:DeletedSocialTagDetail"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="DeletedSocialTagDetail">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:DeletedSocialDataDetail">
            <xs:sequence>
                <xs:element minOccurs="1" maxOccurs="1" name="TermID" type="s1:guid"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="DeletedSocialDataDetail" abstract="true">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="Url" type="xs:string"/>
        <xs:element minOccurs="0" maxOccurs="1" name="Owner" type="xs:string"/>
        <xs:element minOccurs="1" maxOccurs="1" name="DeletedTime" type="xs:dateTime"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="DeletedSocialRatingDetail">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:DeletedSocialDataDetail"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="DeletedSocialCommentDetail">
    <xs:complexContent mixed="false">
        <xs:extension base="tns:DeletedSocialDataDetail">
            <xs:sequence>
                <xs:element minOccurs="1" maxOccurs="1" name="LastModifiedTime"
type="xs:dateTime"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ArrayOfDeletedSocialCommentDetail">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="DeletedSocialCommentDetail"
nillable="true" type="tns:DeletedSocialCommentDetail"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ArrayOfDeletedSocialRatingDetail">
    <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="unbounded" name="DeletedSocialRatingDetail"
nillable="true" type="tns:DeletedSocialRatingDetail"/>
    </xs:sequence>
</xs:complexType>
<xs:element name="GetSocialDataForIncrementalReplicationResponse">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" maxOccurs="1"
name="GetSocialDataForIncrementalReplicationResult" type="tns:SocialReplicationData"/>

```

```

    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetSocialDataForFullReplication">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="GetSocialDataForFullReplicationResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1"
name="GetSocialDataForFullReplicationResult" type="tns:SocialReplicationData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ReplicateIncrementalSocialData">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="changes"
type="tns:SocialReplicationData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ReplicateIncrementalSocialDataResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1"
name="ReplicateIncrementalSocialDataResult" type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ReplicateFullSocialData">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="1" name="userAccountName" type="xs:string"/>
      <xs:element minOccurs="0" maxOccurs="1" name="changes"
type="tns:SocialReplicationData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="ReplicateFullSocialDataResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="1" maxOccurs="1" name="ReplicateFullSocialDataResult"
type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
</xs:schema>
<xs:schema elementFormDefault="qualified"
targetNamespace="http://microsoft.com/wsdl/types/">
  <xs:simpleType name="guid">
    <xs:restriction base="xs:string">
      <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-
9a-fA-F]{12}"/>
    </xs:restriction>
  </xs:simpleType>

```



```

        </xs:restriction>
    </xs:simpleType>
</xs:schema>
</wsdl:types>
<wsdl:message name="CountCommentsOfUserSoapIn">
    <wsdl:part name="parameters" element="tns:CountCommentsOfUser"/>
</wsdl:message>
<wsdl:message name="CountCommentsOfUserSoapOut">
    <wsdl:part name="parameters" element="tns:CountCommentsOfUserResponse"/>
</wsdl:message>
<wsdl:message name="CountCommentsOnUrlSoapIn">
    <wsdl:part name="parameters" element="tns:CountCommentsOnUrl"/>
</wsdl:message>
<wsdl:message name="CountCommentsOnUrlSoapOut">
    <wsdl:part name="parameters" element="tns:CountCommentsOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="CountCommentsOfUserOnUrlSoapIn">
    <wsdl:part name="parameters" element="tns:CountCommentsOfUserOnUrl"/>
</wsdl:message>
<wsdl:message name="CountCommentsOfUserOnUrlSoapOut">
    <wsdl:part name="parameters" element="tns:CountCommentsOfUserOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="GetCommentsOfUserSoapIn">
    <wsdl:part name="parameters" element="tns:GetCommentsOfUser"/>
</wsdl:message>
<wsdl:message name="GetCommentsOfUserSoapOut">
    <wsdl:part name="parameters" element="tns:GetCommentsOfUserResponse"/>
</wsdl:message>
<wsdl:message name="GetCommentsOnUrlSoapIn">
    <wsdl:part name="parameters" element="tns:GetCommentsOnUrl"/>
</wsdl:message>
<wsdl:message name="GetCommentsOnUrlSoapOut">
    <wsdl:part name="parameters" element="tns:GetCommentsOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="GetCommentsOfUserOnUrlSoapIn">
    <wsdl:part name="parameters" element="tns:GetCommentsOfUserOnUrl"/>
</wsdl:message>
<wsdl:message name="GetCommentsOfUserOnUrlSoapOut">
    <wsdl:part name="parameters" element="tns:GetCommentsOfUserOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="AddCommentSoapIn">
    <wsdl:part name="parameters" element="tns:AddComment"/>
</wsdl:message>
<wsdl:message name="AddCommentSoapOut">
    <wsdl:part name="parameters" element="tns:AddCommentResponse"/>
</wsdl:message>
<wsdl:message name="UpdateCommentSoapIn">
    <wsdl:part name="parameters" element="tns:UpdateComment"/>
</wsdl:message>
<wsdl:message name="UpdateCommentSoapOut">
    <wsdl:part name="parameters" element="tns:UpdateCommentResponse"/>
</wsdl:message>
<wsdl:message name="DeleteCommentSoapIn">
    <wsdl:part name="parameters" element="tns>DeleteComment"/>
</wsdl:message>
<wsdl:message name="DeleteCommentSoapOut">
    <wsdl:part name="parameters" element="tns>DeleteCommentResponse"/>

```

```

</wsdl:message>
<wsdl:message name="CountRatingsOnUrlSoapIn">
  <wsdl:part name="parameters" element="tns:CountRatingsOnUrl"/>
</wsdl:message>
<wsdl:message name="CountRatingsOnUrlSoapOut">
  <wsdl:part name="parameters" element="tns:CountRatingsOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="GetRatingsOfUserSoapIn">
  <wsdl:part name="parameters" element="tns:GetRatingsOfUser"/>
</wsdl:message>
<wsdl:message name="GetRatingsOfUserSoapOut">
  <wsdl:part name="parameters" element="tns:GetRatingsOfUserResponse"/>
</wsdl:message>
<wsdl:message name="GetRatingsOnUrlSoapIn">
  <wsdl:part name="parameters" element="tns:GetRatingsOnUrl"/>
</wsdl:message>
<wsdl:message name="GetRatingsOnUrlSoapOut">
  <wsdl:part name="parameters" element="tns:GetRatingsOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="GetRatingOnUrlSoapIn">
  <wsdl:part name="parameters" element="tns:GetRatingOnUrl"/>
</wsdl:message>
<wsdl:message name="GetRatingOnUrlSoapOut">
  <wsdl:part name="parameters" element="tns:GetRatingOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="GetRatingOfUserOnUrlSoapIn">
  <wsdl:part name="parameters" element="tns:GetRatingOfUserOnUrl"/>
</wsdl:message>
<wsdl:message name="GetRatingOfUserOnUrlSoapOut">
  <wsdl:part name="parameters" element="tns:GetRatingOfUserOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="SetRatingSoapIn">
  <wsdl:part name="parameters" element="tns:SetRating"/>
</wsdl:message>
<wsdl:message name="SetRatingSoapOut">
  <wsdl:part name="parameters" element="tns:SetRatingResponse"/>
</wsdl:message>
<wsdl:message name="DeleteRatingSoapIn">
  <wsdl:part name="parameters" element="tns>DeleteRating"/>
</wsdl:message>
<wsdl:message name="DeleteRatingSoapOut">
  <wsdl:part name="parameters" element="tns>DeleteRatingResponse"/>
</wsdl:message>
<wsdl:message name="GetRatingAverageOnUrlSoapIn">
  <wsdl:part name="parameters" element="tns:GetRatingAverageOnUrl"/>
</wsdl:message>
<wsdl:message name="GetRatingAverageOnUrlSoapOut">
  <wsdl:part name="parameters" element="tns:GetRatingAverageOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="PropagateRatingSoapIn">
  <wsdl:part name="parameters" element="tns:PropagateRating"/>
</wsdl:message>
<wsdl:message name="PropagateRatingSoapOut">
  <wsdl:part name="parameters" element="tns:PropagateRatingResponse"/>
</wsdl:message>
<wsdl:message name="CountTagsOfUserSoapIn">
  <wsdl:part name="parameters" element="tns:CountTagsOfUser"/>

```

```

</wsdl:message>
<wsdl:message name="CountTagsOfUserSoapOut">
  <wsdl:part name="parameters" element="tns:CountTagsOfUserResponse"/>
</wsdl:message>
<wsdl:message name="GetTagTermsSoapIn">
  <wsdl:part name="parameters" element="tns:GetTagTerms"/>
</wsdl:message>
<wsdl:message name="GetTagTermsSoapOut">
  <wsdl:part name="parameters" element="tns:GetTagTermsResponse"/>
</wsdl:message>
<wsdl:message name="GetTagTermsOfUserSoapIn">
  <wsdl:part name="parameters" element="tns:GetTagTermsOfUser"/>
</wsdl:message>
<wsdl:message name="GetTagTermsOfUserSoapOut">
  <wsdl:part name="parameters" element="tns:GetTagTermsOfUserResponse"/>
</wsdl:message>
<wsdl:message name="GetTagTermsOnUrlSoapIn">
  <wsdl:part name="parameters" element="tns:GetTagTermsOnUrl"/>
</wsdl:message>
<wsdl:message name="GetTagTermsOnUrlSoapOut">
  <wsdl:part name="parameters" element="tns:GetTagTermsOnUrlResponse"/>
</wsdl:message>
<wsdl:message name="GetAllTagTermsSoapIn">
  <wsdl:part name="parameters" element="tns:GetAllTagTerms"/>
</wsdl:message>
<wsdl:message name="GetAllTagTermsSoapOut">
  <wsdl:part name="parameters" element="tns:GetAllTagTermsResponse"/>
</wsdl:message>
<wsdl:message name="GetAllTagTermsForUrlFolderSoapIn">
  <wsdl:part name="parameters" element="tns:GetAllTagTermsForUrlFolder"/>
</wsdl:message>
<wsdl:message name="GetAllTagTermsForUrlFolderSoapOut">
  <wsdl:part name="parameters" element="tns:GetAllTagTermsForUrlFolderResponse"/>
</wsdl:message>
<wsdl:message name="GetTagsSoapIn">
  <wsdl:part name="parameters" element="tns:GetTags"/>
</wsdl:message>
<wsdl:message name="GetTagsSoapOut">
  <wsdl:part name="parameters" element="tns:GetTagsResponse"/>
</wsdl:message>
<wsdl:message name="GetTagsOfUserSoapIn">
  <wsdl:part name="parameters" element="tns:GetTagsOfUser"/>
</wsdl:message>
<wsdl:message name="GetTagsOfUserSoapOut">
  <wsdl:part name="parameters" element="tns:GetTagsOfUserResponse"/>
</wsdl:message>
<wsdl:message name="GetTagUrlsSoapIn">
  <wsdl:part name="parameters" element="tns:GetTagUrls"/>
</wsdl:message>
<wsdl:message name="GetTagUrlsSoapOut">
  <wsdl:part name="parameters" element="tns:GetTagUrlsResponse"/>
</wsdl:message>
<wsdl:message name="GetTagUrlsByKeywordSoapIn">
  <wsdl:part name="parameters" element="tns:GetTagUrlsByKeyword"/>
</wsdl:message>
<wsdl:message name="GetTagUrlsByKeywordSoapOut">
  <wsdl:part name="parameters" element="tns:GetTagUrlsByKeywordResponse"/>

```

```

</wsdl:message>
<wsdl:message name="GetTagUrlsOfUserSoapIn">
  <wsdl:part name="parameters" element="tns:GetTagUrlsOfUser"/>
</wsdl:message>
<wsdl:message name="GetTagUrlsOfUserSoapOut">
  <wsdl:part name="parameters" element="tns:GetTagUrlsOfUserResponse"/>
</wsdl:message>
<wsdl:message name="GetTagUrlsOfUserByKeywordSoapIn">
  <wsdl:part name="parameters" element="tns:GetTagUrlsOfUserByKeyword"/>
</wsdl:message>
<wsdl:message name="GetTagUrlsOfUserByKeywordSoapOut">
  <wsdl:part name="parameters" element="tns:GetTagUrlsOfUserByKeywordResponse"/>
</wsdl:message>
<wsdl:message name="GetAllTagUrlsSoapIn">
  <wsdl:part name="parameters" element="tns:GetAllTagUrls"/>
</wsdl:message>
<wsdl:message name="GetAllTagUrlsSoapOut">
  <wsdl:part name="parameters" element="tns:GetAllTagUrlsResponse"/>
</wsdl:message>
<wsdl:message name="GetAllTagUrlsByKeywordSoapIn">
  <wsdl:part name="parameters" element="tns:GetAllTagUrlsByKeyword"/>
</wsdl:message>
<wsdl:message name="GetAllTagUrlsByKeywordSoapOut">
  <wsdl:part name="parameters" element="tns:GetAllTagUrlsByKeywordResponse"/>
</wsdl:message>
<wsdl:message name="AddTagSoapIn">
  <wsdl:part name="parameters" element="tns:AddTag"/>
</wsdl:message>
<wsdl:message name="AddTagSoapOut">
  <wsdl:part name="parameters" element="tns:AddTagResponse"/>
</wsdl:message>
<wsdl:message name="AddTagByKeywordSoapIn">
  <wsdl:part name="parameters" element="tns:AddTagByKeyword"/>
</wsdl:message>
<wsdl:message name="AddTagByKeywordSoapOut">
  <wsdl:part name="parameters" element="tns:AddTagByKeywordResponse"/>
</wsdl:message>
<wsdl:message name="DeleteTagSoapIn">
  <wsdl:part name="parameters" element="tns>DeleteTag"/>
</wsdl:message>
<wsdl:message name="DeleteTagSoapOut">
  <wsdl:part name="parameters" element="tns>DeleteTagResponse"/>
</wsdl:message>
<wsdl:message name="DeleteTagByKeywordSoapIn">
  <wsdl:part name="parameters" element="tns>DeleteTagByKeyword"/>
</wsdl:message>
<wsdl:message name="DeleteTagByKeywordSoapOut">
  <wsdl:part name="parameters" element="tns>DeleteTagByKeywordResponse"/>
</wsdl:message>
<wsdl:message name="DeleteTagsSoapIn">
  <wsdl:part name="parameters" element="tns>DeleteTags"/>
</wsdl:message>
<wsdl:message name="DeleteTagsSoapOut">
  <wsdl:part name="parameters" element="tns>DeleteTagsResponse"/>
</wsdl:message>
<wsdl:message name="GetSocialDataForIncrementalReplicationSoapIn">
  <wsdl:part name="parameters" element="tns:GetSocialDataForIncrementalReplication"/>

```

```

</wsdl:message>
<wsdl:message name="GetSocialDataForIncrementalReplicationSoapOut">
  <wsdl:part name="parameters"
element="tns:GetSocialDataForIncrementalReplicationResponse"/>
</wsdl:message>
<wsdl:message name="GetSocialDataForFullReplicationSoapIn">
  <wsdl:part name="parameters" element="tns:GetSocialDataForFullReplication"/>
</wsdl:message>
<wsdl:message name="GetSocialDataForFullReplicationSoapOut">
  <wsdl:part name="parameters" element="tns:GetSocialDataForFullReplicationResponse"/>
</wsdl:message>
<wsdl:message name="ReplicateIncrementalSocialDataSoapIn">
  <wsdl:part name="parameters" element="tns:ReplicateIncrementalSocialData"/>
</wsdl:message>
<wsdl:message name="ReplicateIncrementalSocialDataSoapOut">
  <wsdl:part name="parameters" element="tns:ReplicateIncrementalSocialDataResponse"/>
</wsdl:message>
<wsdl:message name="ReplicateFullSocialDataSoapIn">
  <wsdl:part name="parameters" element="tns:ReplicateFullSocialData"/>
</wsdl:message>
<wsdl:message name="ReplicateFullSocialDataSoapOut">
  <wsdl:part name="parameters" element="tns:ReplicateFullSocialDataResponse"/>
</wsdl:message>
<wsdl:portType name="SocialDataServiceSoap">
  <wsdl:operation name="CountCommentsOfUser">
    <wsdl:input message="tns:CountCommentsOfUserSoapIn"/>
    <wsdl:output message="tns:CountCommentsOfUserSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="CountCommentsOnUrl">
    <wsdl:input message="tns:CountCommentsOnUrlSoapIn"/>
    <wsdl:output message="tns:CountCommentsOnUrlSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="CountCommentsOfUserOnUrl">
    <wsdl:input message="tns:CountCommentsOfUserOnUrlSoapIn"/>
    <wsdl:output message="tns:CountCommentsOfUserOnUrlSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetCommentsOfUser">
    <wsdl:input message="tns:GetCommentsOfUserSoapIn"/>
    <wsdl:output message="tns:GetCommentsOfUserSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetCommentsOnUrl">
    <wsdl:input message="tns:GetCommentsOnUrlSoapIn"/>
    <wsdl:output message="tns:GetCommentsOnUrlSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetCommentsOfUserOnUrl">
    <wsdl:input message="tns:GetCommentsOfUserOnUrlSoapIn"/>
    <wsdl:output message="tns:GetCommentsOfUserOnUrlSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="AddComment">
    <wsdl:input message="tns:AddCommentSoapIn"/>
    <wsdl:output message="tns:AddCommentSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="UpdateComment">
    <wsdl:input message="tns:UpdateCommentSoapIn"/>
    <wsdl:output message="tns:UpdateCommentSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="DeleteComment">

```

```

    <wsdl:input message="tns:DeleteCommentSoapIn"/>
    <wsdl:output message="tns:DeleteCommentSoapOut"/>
</wsdl:operation>
<wsdl:operation name="CountRatingsOnUrl">
    <wsdl:input message="tns:CountRatingsOnUrlSoapIn"/>
    <wsdl:output message="tns:CountRatingsOnUrlSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetRatingsOfUser">
    <wsdl:input message="tns:GetRatingsOfUserSoapIn"/>
    <wsdl:output message="tns:GetRatingsOfUserSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetRatingsOnUrl">
    <wsdl:input message="tns:GetRatingsOnUrlSoapIn"/>
    <wsdl:output message="tns:GetRatingsOnUrlSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetRatingOnUrl">
    <wsdl:input message="tns:GetRatingOnUrlSoapIn"/>
    <wsdl:output message="tns:GetRatingOnUrlSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetRatingOfUserOnUrl">
    <wsdl:input message="tns:GetRatingOfUserOnUrlSoapIn"/>
    <wsdl:output message="tns:GetRatingOfUserOnUrlSoapOut"/>
</wsdl:operation>
<wsdl:operation name="SetRating">
    <wsdl:input message="tns:SetRatingSoapIn"/>
    <wsdl:output message="tns:SetRatingSoapOut"/>
</wsdl:operation>
<wsdl:operation name="DeleteRating">
    <wsdl:input message="tns>DeleteRatingSoapIn"/>
    <wsdl:output message="tns>DeleteRatingSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetRatingAverageOnUrl">
    <wsdl:input message="tns:GetRatingAverageOnUrlSoapIn"/>
    <wsdl:output message="tns:GetRatingAverageOnUrlSoapOut"/>
</wsdl:operation>
<wsdl:operation name="PropagateRating">
    <wsdl:input message="tns:PropagateRatingSoapIn"/>
    <wsdl:output message="tns:PropagateRatingSoapOut"/>
</wsdl:operation>
<wsdl:operation name="CountTagsOfUser">
    <wsdl:input message="tns:CountTagsOfUserSoapIn"/>
    <wsdl:output message="tns:CountTagsOfUserSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetTagTerms">
    <wsdl:input message="tns:GetTagTermsSoapIn"/>
    <wsdl:output message="tns:GetTagTermsSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetTagTermsOfUser">
    <wsdl:input message="tns:GetTagTermsOfUserSoapIn"/>
    <wsdl:output message="tns:GetTagTermsOfUserSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetTagTermsOnUrl">
    <wsdl:input message="tns:GetTagTermsOnUrlSoapIn"/>
    <wsdl:output message="tns:GetTagTermsOnUrlSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetAllTagTerms">
    <wsdl:input message="tns:GetAllTagTermsSoapIn"/>

```

```

    <wsdl:output message="tns:GetAllTagTermsSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetAllTagTermsForUrlFolder">
    <wsdl:input message="tns:GetAllTagTermsForUrlFolderSoapIn"/>
    <wsdl:output message="tns:GetAllTagTermsForUrlFolderSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetTags">
    <wsdl:input message="tns:GetTagsSoapIn"/>
    <wsdl:output message="tns:GetTagsSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetTagsOfUser">
    <wsdl:input message="tns:GetTagsOfUserSoapIn"/>
    <wsdl:output message="tns:GetTagsOfUserSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetTagUrls">
    <wsdl:input message="tns:GetTagUrlsSoapIn"/>
    <wsdl:output message="tns:GetTagUrlsSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetTagUrlsByKeyword">
    <wsdl:input message="tns:GetTagUrlsByKeywordSoapIn"/>
    <wsdl:output message="tns:GetTagUrlsByKeywordSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetTagUrlsOfUser">
    <wsdl:input message="tns:GetTagUrlsOfUserSoapIn"/>
    <wsdl:output message="tns:GetTagUrlsOfUserSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetTagUrlsOfUserByKeyword">
    <wsdl:input message="tns:GetTagUrlsOfUserByKeywordSoapIn"/>
    <wsdl:output message="tns:GetTagUrlsOfUserByKeywordSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetAllTagUrls">
    <wsdl:input message="tns:GetAllTagUrlsSoapIn"/>
    <wsdl:output message="tns:GetAllTagUrlsSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="GetAllTagUrlsByKeyword">
    <wsdl:input message="tns:GetAllTagUrlsByKeywordSoapIn"/>
    <wsdl:output message="tns:GetAllTagUrlsByKeywordSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="AddTag">
    <wsdl:input message="tns:AddTagSoapIn"/>
    <wsdl:output message="tns:AddTagSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="AddTagByKeyword">
    <wsdl:input message="tns:AddTagByKeywordSoapIn"/>
    <wsdl:output message="tns:AddTagByKeywordSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="DeleteTag">
    <wsdl:input message="tns>DeleteTagSoapIn"/>
    <wsdl:output message="tns>DeleteTagSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="DeleteTagByKeyword">
    <wsdl:input message="tns>DeleteTagByKeywordSoapIn"/>
    <wsdl:output message="tns>DeleteTagByKeywordSoapOut"/>
  </wsdl:operation>
  <wsdl:operation name="DeleteTags">
    <wsdl:input message="tns>DeleteTagsSoapIn"/>
    <wsdl:output message="tns>DeleteTagsSoapOut"/>
  </wsdl:operation>

```

```

</wsdl:operation>
<wsdl:operation name="GetSocialDataForIncrementalReplication">
  <wsdl:input message="tns:GetSocialDataForIncrementalReplicationSoapIn"/>
  <wsdl:output message="tns:GetSocialDataForIncrementalReplicationSoapOut"/>
</wsdl:operation>
<wsdl:operation name="GetSocialDataForFullReplication">
  <wsdl:input message="tns:GetSocialDataForFullReplicationSoapIn"/>
  <wsdl:output message="tns:GetSocialDataForFullReplicationSoapOut"/>
</wsdl:operation>
<wsdl:operation name="ReplicateIncrementalSocialData">
  <wsdl:input message="tns:ReplicateIncrementalSocialDataSoapIn"/>
  <wsdl:output message="tns:ReplicateIncrementalSocialDataSoapOut"/>
</wsdl:operation>
<wsdl:operation name="ReplicateFullSocialData">
  <wsdl:input message="tns:ReplicateFullSocialDataSoapIn"/>
  <wsdl:output message="tns:ReplicateFullSocialDataSoapOut"/>
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="SocialDataServiceSoap" type="tns:SocialDataServiceSoap">
  <soap:binding transport="http://schemas.xmlsoap.org/soap/http"/>
  <wsdl:operation name="CountCommentsOfUser">
    <soap:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountCommentsOfUser" style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="CountCommentsOnUrl">
    <soap:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountCommentsOnUrl" style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="CountCommentsOfUserOnUrl">
    <soap:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountCommentsOfUserOnUrl" style="document"/>
    <wsdl:input>
      <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetCommentsOfUser">
    <soap:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetCommentsOfUser" style="document"/>
    <wsdl:input>

```



```

        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetCommentsOnUrl">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetComm
entsOnUrl" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetCommentsOfUserOnUrl">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetComm
entsOfUserOnUrl" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="AddComment">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/AddComm
ent" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateComment">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/UpdateC
omment" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeleteComment">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteC
omment" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>

```

```

        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="CountRatingsOnUrl">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountRa
tingsOnUrl" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetRatingsOfUser">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRati
ngsOfUser" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetRatingsOnUrl">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRati
ngsOnUrl" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetRatingOnUrl">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRati
ngOnUrl" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetRatingOfUserOnUrl">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRati
ngOfUserOnUrl" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>

```

```

    <wsdl:operation name="SetRating">
      <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/SetRating" style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteRating">
      <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteRating" style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetRatingAverageOnUrl">
      <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRatingAverageOnUrl" style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="PropagateRating">
      <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/PropagateRating" style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CountTagsOfUser">
      <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountTagsOfUser" style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagTerms">

```

```

    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagT
erms" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetTagTermsOfUser">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagT
ermsOfUser" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetTagTermsOnUrl">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagT
ermsOnUrl" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAllTagTerms">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllT
agTerms" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetAllTagTermsForUrlFolder">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllT
agTermsForUrlFolder" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetTags">
    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTags
" style="document"/>

```

```

        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagsOfUser">
        <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTags
OfUser" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagUrls">
        <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagU
rls" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagUrlsByKeyword">
        <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagU
rlsByKeyword" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagUrlsOfUser">
        <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagU
rlsOfUser" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagUrlsOfUserByKeyword">
        <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagU
rlsOfUserByKeyword" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
    </wsdl:input>

```

```

        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetAllTagUrls">
        <soap:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllTagUrls"
            style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetAllTagUrlsByKeyword">
        <soap:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllTagUrlsByKeyword"
            style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="AddTag">
        <soap:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/AddTag"
            style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="AddTagByKeyword">
        <soap:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/AddTagByKeyword"
            style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteTag">
        <soap:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteTag"
            style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:output>

```

```

</wsdl:operation>
<wsdl:operation name="DeleteTagByKeyword">
  <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteT
agByKeyword" style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeleteTags">
  <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteT
ags" style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetSocialDataForIncrementalReplication">
  <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetSoci
alDataForIncrementalReplication" style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetSocialDataForFullReplication">
  <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetSoci
alDataForFullReplication" style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReplicateIncrementalSocialData">
  <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/Replica
teIncrementalSocialData" style="document"/>
  <wsdl:input>
    <soap:body use="literal"/>
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReplicateFullSocialData">

```

```

    <soap:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/Replica
teFullSocialData" style="document"/>
    <wsdl:input>
        <soap:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:binding name="SocialDataServiceSoap12" type="tns:SocialDataServiceSoap">
    <soap12:binding transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="CountCommentsOfUser">
        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountCo
mmentsOfUser" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CountCommentsOnUrl">
        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountCo
mmentsOnUrl" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CountCommentsOfUserOnUrl">
        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountCo
mmentsOfUserOnUrl" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetCommentsOfUser">
        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetComm
entsOfUser" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetCommentsOnUrl">

```



```

    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetComm
entsOnUrl" style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetCommentsOfUserOnUrl">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetComm
entsOfUserOnUrl" style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="AddComment">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/AddComm
ent" style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateComment">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/UpdateC
omment" style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="DeleteComment">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteC
omment" style="document"/>
    <wsdl:input>
        <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal"/>
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="CountRatingsOnUrl">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountRa
tingsOnUrl" style="document"/>

```

```

    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetRatingsOfUser">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRati
      ngsOfUser" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetRatingsOnUrl">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRati
      ngsOnUrl" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetRatingOnUrl">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRati
      ngOnUrl" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetRatingOfUserOnUrl">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRati
      ngOfUserOnUrl" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="SetRating">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/SetRati
      ng" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
  </wsdl:operation>

```

```

        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteRating">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteRating" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetRatingAverageOnUrl">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetRatingAverageOnUrl" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="PropagateRating">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/PropagateRating" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="CountTagsOfUser">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/CountTagsOfUser" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagTerms">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagTerms" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:output>

```

```

</wsdl:operation>
  <wsdl:operation name="GetTagTermsOfUser">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagT
ermsOfUser" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetTagTermsOnUrl">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagT
ermsOnUrl" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetAllTagTerms">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllT
agTerms" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetAllTagTermsForUrlFolder">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllT
agTermsForUrlFolder" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetTags">
    <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTags
" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetTagsOfUser">

```

```

        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTags
OfUser" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagUrls">
        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagU
rls" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagUrlsByKeyword">
        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagU
rlsByKeyword" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagUrlsOfUser">
        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagU
rlsOfUser" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetTagUrlsOfUserByKeyword">
        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetTagU
rlsOfUserByKeyword" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetAllTagUrls">
        <soap12:operation
soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllT
agUrls" style="document"/>

```

```

    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="GetAllTagUrlsByKeyword">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetAllTagUrlsByKeyword" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="AddTag">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/AddTag" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="AddTagByKeyword">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/AddTagByKeyword" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="DeleteTag">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteTag" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
    <wsdl:output>
      <soap12:body use="literal"/>
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="DeleteTagByKeyword">
    <soap12:operation
      soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteTagByKeyword" style="document"/>
    <wsdl:input>
      <soap12:body use="literal"/>
    </wsdl:input>
  </wsdl:input>

```

```

        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="DeleteTags">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/DeleteTags" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetSocialDataForIncrementalReplication">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetSocialDataForIncrementalReplication" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetSocialDataForFullReplication">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/GetSocialDataForFullReplication" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="ReplicateIncrementalSocialData">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/ReplicateIncrementalSocialData" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="ReplicateFullSocialData">
        <soap12:operation
            soapAction="http://microsoft.com/webservices/SharePointPortalServer/SocialDataService/ReplicateFullSocialData" style="document"/>
        <wsdl:input>
            <soap12:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>

```

```
</wsdl:operation>  
</wsdl:binding>  
</wsdl:definitions>
```

Preliminary

7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Lync™ 2010
- Microsoft® Office 2010 suites
- Microsoft® SharePoint® Designer 2010
- Microsoft® SharePoint® Server 2010
- Microsoft® SharePoint® Workspace 2010
- Microsoft® Visio® 2010
- Microsoft® Lync 15 Technical Preview
- Microsoft® Office 15 Technical Preview
- Microsoft® SharePoint® Designer 15 Technical Preview
- Microsoft® Visio® 15 Technical Preview

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

8 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

Preliminary

9 Index

A

Abstract data model
 [server](#) 30
[Add social data to a URI example](#) 126
[Add social ratings to a URI example](#) 132
[Applicability](#) 17
[ArrayOfDeletedSocialCommentDetail complex type](#)
 21
[ArrayOfDeletedSocialRatingDetail complex type](#) 21
[ArrayOfDeletedSocialTagDetail complex type](#) 22
[ArrayOfSocialCommentDetail complex type](#) 22
[ArrayOfSocialRatingDetail complex type](#) 22
[ArrayOfSocialTagDetail complex type](#) 23
[ArrayOfSocialTermDetail complex type](#) 23
[ArrayOfSocialUriDetail complex type](#) 23
[ArrayOfString complex type](#) 24
[Attribute groups](#) 29
[Attributes](#) 29

C

[Capability negotiation](#) 17
[Change tracking](#) 178
Client
 [overview](#) 30
Common data structures ([section 2.2.9](#) 29, [section 2.2.9](#) 29)
[Complex types](#) 20
 [ArrayOfDeletedSocialCommentDetail](#) 21
 [ArrayOfDeletedSocialRatingDetail](#) 21
 [ArrayOfDeletedSocialTagDetail](#) 22
 [ArrayOfSocialCommentDetail](#) 22
 [ArrayOfSocialRatingDetail](#) 22
 [ArrayOfSocialTagDetail](#) 23
 [ArrayOfSocialTermDetail](#) 23
 [ArrayOfSocialUriDetail](#) 23
 [ArrayOfString](#) 24
 [DeletedSocialCommentDetail](#) 24
 [DeletedSocialDataDetail](#) 24
 [DeletedSocialRatingDetail](#) 25
 [DeletedSocialTagDetail](#) 25
 [SocialCommentDetail](#) 25
 [SocialDataDetail](#) 26
 [SocialRatingDetail](#) 26
 [SocialReplicationData](#) 26
 [SocialTagDetail](#) 27
 [SocialTermDetail](#) 28
 [SocialUriDetail](#) 28
 [TermDetail](#) 28

D

Data model - abstract
 [server](#) 30
[Delete social data comments example](#) 130
[Delete social data tags example](#) 132

[Delete social ratings example](#) 136
[DeletedSocialCommentDetail complex type](#) 24
[DeletedSocialDataDetail complex type](#) 24
[DeletedSocialRatingDetail complex type](#) 25
[DeletedSocialTagDetail complex type](#) 25

E

Events
 [local - server](#) 125
 [timer - server](#) 125
Examples
 [add social data to a URI](#) 126
 [add social ratings to a URI](#) 132
 [delete social data comments](#) 130
 [delete social data tags](#) 132
 [delete social ratings](#) 136
 [find information about social ratings](#) 133
 [find social data tags](#) 130
 [view social data comments](#) 127

F

[Fields - vendor-extensible](#) 18
[Find information about social ratings example](#) 133
[Find social data tags example](#) 130
[Full WSDL](#) 138

G

[Glossary](#) 15
[Groups](#) 29
[guid simple type](#) 29

I

[Implementer - security considerations](#) 137
[Index of security parameters](#) 137
[Informative references](#) 16
Initialization
 [server](#) 31
[Introduction](#) 14

L

Local events
 [server](#) 125

M

Message processing
 [server](#) 31
[Messages](#) 19
 [ArrayOfDeletedSocialCommentDetail complex type](#) 21
 [ArrayOfDeletedSocialRatingDetail complex type](#) 21

- [ArrayOfDeletedSocialTagDetail_complex_type](#) 22
- [ArrayOfSocialCommentDetail_complex_type](#) 22
- [ArrayOfSocialRatingDetail_complex_type](#) 22
- [ArrayOfSocialTagDetail_complex_type](#) 23
- [ArrayOfSocialTermDetail_complex_type](#) 23
- [ArrayOfSocialUriDetail_complex_type](#) 23
- [ArrayOfString_complex_type](#) 24
- [attribute groups](#) 29
- [attributes](#) 29
- common data structures ([section 2.2.9](#) 29, [section 2.2.9](#) 29)
- [complex types](#) 20
- [DeletedSocialCommentDetail_complex_type](#) 24
- [DeletedSocialDataDetail_complex_type](#) 24
- [DeletedSocialRatingDetail_complex_type](#) 25
- [DeletedSocialTagDetail_complex_type](#) 25
- [elements](#) 20
- [enumerated](#) 19
- [groups](#) 29
- [guid simple type](#) 29
- [namespaces](#) 19
- [simple types](#) 29
- [SocialCommentDetail_complex_type](#) 25
- [SocialDataDetail_complex_type](#) 26
- [SocialRatingDetail_complex_type](#) 26
- [SocialReplicationData_complex_type](#) 26
- [SocialTagDetail_complex_type](#) 27
- [SocialTermDetail_complex_type](#) 28
- [SocialUriDetail_complex_type](#) 28
- [syntax](#) 19
- [TermDetail_complex_type](#) 28
- [transport](#) 19

N

- [Namespaces](#) 19
- [Normative references](#) 16
- Notes (social comments)
 - [server](#) 30

O

Operations

- [AddComment](#) 34
- [AddTag](#) 36
- [AddTagByKeyword](#) 38
- [CountCommentsOfUser](#) 41
- [CountCommentsOfUserOnUrl](#) 43
- [CountCommentsOnUrl](#) 45
- [CountRatingsOnUrl](#) 47
- [CountTagsOfUser](#) 49
- [DeleteComment](#) 51
- [DeleteRating](#) 53
- [DeleteTag](#) 55
- [DeleteTagByKeyword](#) 57
- [DeleteTags](#) 59
- [GetAllTagTerms](#) 61
- [GetAllTagTermsForUrlFolder](#) 63
- [GetAllTagUrls](#) 65
- [GetAllTagUrlsByKeyword](#) 67
- [GetCommentsOfUser](#) 70
- [GetCommentsOfUserOnUrl](#) 72

- [GetCommentsOnUrl](#) 74
- [GetRatingAverageOnUrl](#) 77
- [GetRatingOfUserOnUrl](#) 80
- [GetRatingOnUrl](#) 82
- [GetRatingsOfUser](#) 84
- [GetRatingsOnUrl](#) 86
- [GetSocialDataForFullReplication](#) 88
- [GetSocialDataForIncrementalReplication](#) 90
- [GetTags](#) 93
- [GetTagsOfUser](#) 95
- [GetTagTerms](#) 97
- [GetTagTermsOfUser](#) 99
- [GetTagTermsOnUrl](#) 102
- [GetTagUrls](#) 104
- [GetTagUrlsByKeyword](#) 106
- [GetTagUrlsOfUser](#) 108
- [GetTagUrlsOfUserByKeyword](#) 110
- [PropagateRating](#) 112
- [ReplicateFullSocialData](#) 114
- [ReplicateIncrementalSocialData](#) 116
- [SetRating](#) 119
- [UpdateComment](#) 123
- [Overview \(synopsis\)](#) 17

P

- [Parameters - security index](#) 137
- [Preconditions](#) 17
- [Prerequisites](#) 17
- [Product behavior](#) 177

R

Ratings

- [server](#) 31

[References](#) 16

- [informative](#) 16
- [normative](#) 16

[Relationship to other protocols](#) 17

S

Security

- [implementer considerations](#) 137
- [parameter index](#) 137

Sequencing rules

- [server](#) 31

Server

- [abstract data model](#) 30
- [AddComment operation](#) 34
- [AddTag operation](#) 36
- [AddTagByKeyword operation](#) 38
- [CountCommentsOfUser operation](#) 41
- [CountCommentsOfUserOnUrl operation](#) 43
- [CountCommentsOnUrl operation](#) 45
- [CountRatingsOnUrl operation](#) 47
- [CountTagsOfUser operation](#) 49
- [DeleteComment operation](#) 51
- [DeleteRating operation](#) 53
- [DeleteTag operation](#) 55
- [DeleteTagByKeyword operation](#) 57
- [DeleteTags operation](#) 59

[GetAllTagTerms operation](#) 61
[GetAllTagTermsForUrlFolder operation](#) 63
[GetAllTagUrls operation](#) 65
[GetAllTagUrlsByKeyword operation](#) 67
[GetCommentsOfUser operation](#) 70
[GetCommentsOfUserOnUrl operation](#) 72
[GetCommentsOnUrl operation](#) 74
[GetRatingAverageOnUrl operation](#) 77
[GetRatingOfUserOnUrl operation](#) 80
[GetRatingOnUrl operation](#) 82
[GetRatingsOfUser operation](#) 84
[GetRatingsOnUrl operation](#) 86
[GetSocialDataForFullReplication operation](#) 88
[GetSocialDataForIncrementalReplication operation](#) 90
[GetTags operation](#) 93
[GetTagsOfUser operation](#) 95
[GetTagTerms operation](#) 97
[GetTagTermsOfUser operation](#) 99
[GetTagTermsOnUrl operation](#) 102
[GetTagUrls operation](#) 104
[GetTagUrlsByKeyword operation](#) 106
[GetTagUrlsOfUser operation](#) 108
[GetTagUrlsOfUserByKeyword operation](#) 110
[initialization](#) 31
[local events](#) 125
[message processing](#) 31
[overview](#) 30
[PropagateRating operation](#) 112
[ReplicateFullSocialData operation](#) 114
[ReplicateIncrementalSocialData operation](#) 116
[sequencing rules](#) 31
[SetRating operation](#) 119
[timer events](#) 125
[timers](#) 31
[UpdateComment operation](#) 123

Server abstract data model
[notes \(social comments\)](#) 30
[Ratings](#) 31
[social tags](#) 30
[Simple types](#) 29
[guid](#) 29

Social tags
[server](#) 30

[SocialCommentDetail complex type](#) 25
[SocialDataDetail complex type](#) 26
[SocialRatingDetail complex type](#) 26
[SocialReplicationData complex type](#) 26
[SocialTagDetail complex type](#) 27
[SocialTermDetail complex type](#) 28
[SocialUrlDetail complex type](#) 28
[Standards assignments](#) 18

Syntax
[messages - overview](#) 19

T

[TermDetail complex type](#) 28

Timer events
[server](#) 125

Timers
[server](#) 31

[Tracking changes](#) 178
[Transport](#) 19

Types
[complex](#) 20
[simple](#) 29

V

[Vendor-extensible fields](#) 18
[Versioning](#) 17
[View social data comments example](#) 127

W

[WSDL](#) 138