

[MS-UPWCFWS]: User Profile Property Service Application Web Service Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
07/13/2009	0.1	Major	Initial Availability
08/28/2009	0.2	Editorial	Revised and edited the technical content
11/06/2009	0.3	Editorial	Revised and edited the technical content
02/19/2010	1.0	Major	Updated and revised the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Editorial	Revised and edited the technical content
06/07/2010	1.03	Editorial	Revised and edited the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.05	Minor	Clarified the meaning of the technical content.
09/27/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	2.0	Major	Significantly changed the technical content.
04/11/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
09/12/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	2.1	Minor	Clarified the meaning of the technical content.
02/11/2013	2.1	No change	No changes to the meaning, language, or formatting of the technical content.
07/30/2013	2.2	Minor	Clarified the meaning of the technical content.
11/18/2013	2.2	No change	No changes to the meaning, language, or formatting of

Date	Revision History	Revision Class	Comments
			the technical content.
02/10/2014	2.2	No change	No changes to the meaning, language, or formatting of the technical content.
04/30/2014	2.2	No change	No changes to the meaning, language, or formatting of the technical content.
07/31/2014	2.2	No change	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	7
1.2.1 Normative References	7
1.2.2 Informative References	8
1.3 Overview	8
1.4 Relationship to Other Protocols	8
1.5 Prerequisites/Preconditions	9
1.6 Applicability Statement	9
1.7 Versioning and Capability Negotiation	9
1.8 Vendor-Extensible Fields	9
1.9 Standards Assignments	9
2 Messages	10
2.1 Transport	10
2.2 Common Message Syntax	10
2.2.1 Namespaces	10
2.2.2 Messages	11
2.2.3 Elements	11
2.2.4 Complex Types	11
2.2.5 Simple Types	11
2.2.5.1 char	11
2.2.5.2 duration	11
2.2.6 Attributes	12
2.2.7 Groups	12
2.2.8 Attribute Groups	12
2.2.9 Common Data Structures	12
3 Protocol Details	13
3.1 Server Details	13
3.1.1 Abstract Data Model	14
3.1.2 Timers	14
3.1.3 Initialization	14
3.1.4 Message Processing Events and Sequencing Rules	14
3.1.4.1 GetProfileProperties	14
3.1.4.1.1 Messages	14
3.1.4.1.1.1 IProfilePropertyService_GetProfileProperties_InputMessage	15
3.1.4.1.1.2 IProfilePropertyService_GetProfileProperties_OutputMessage	15
3.1.4.1.2 Elements	15
3.1.4.1.2.1 GetProfileProperties	15
3.1.4.1.2.2 GetProfilePropertiesResponse	15
3.1.4.1.3 Complex Types	16
3.1.4.1.3.1 ProfilePropertyData	16
3.1.4.1.3.2 ArrayOfguid	21
3.1.4.1.4 Simple Types	22
3.1.4.1.4.1 guid	22
3.1.4.1.4.2 SPObjectStatus	22
3.1.4.1.4.3 SPPartitionOptions	23
3.1.4.1.4.4 UserProfileApplication.PersonalSitePagesRemoteStatus	23
3.1.4.1.5 Attributes	24

3.1.4.1.6	Groups.....	24
3.1.4.1.7	Attribute Groups	24
3.1.5	Timer Events	24
3.1.6	Other Local Events	24
4	Protocol Examples.....	25
4.1	Retrieving User Profile Service Configuration State.....	25
5	Security.....	27
5.1	Security Considerations for Implementers.....	27
5.2	Index of Security Parameters	27
6	Appendix A: Full WSDL.....	28
7	Appendix B: Full XML Schema	29
7.1	http://tempuri.org/ Schema.....	29
7.2	http://schemas.microsoft.com/2003/10/Serialization/ Schema	29
7.3	http://Microsoft/Office/Server/UserProfiles Schema	30
7.4	http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration Schema	32
7.5	http://schemas.microsoft.com/2003/10/Serialization/Arrays Schema	32
7.6	http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities Schema.....	32
7.7	http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration Schema	33
8	Appendix C: Product Behavior	34
9	Change Tracking.....	35
10	Index	36

1 Introduction

The User Profile Property Service Application Web Service Protocol is built upon the Windows Communication Foundation and enables a protocol client to retrieve user profile application configuration information that is located in a user profile store on a site.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in [\[RFC2119\]](#). Sections 1.5 and 1.9 are also normative but does not contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

- access control entry (ACE)**
- access control list (ACL)**
- Augmented Backus-Naur Form (ABNF)**
- base64**
- domain controller (DC)**
- Domain Name System (DNS)**
- GUID**
- Hypertext Transfer Protocol (HTTP)**
- Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**
- language code identifier (LCID)**
- security identifier (SID)**
- service**
- SOAP**
- SOAP action**
- SOAP body**
- SOAP fault**
- Transmission Control Protocol (TCP)**
- Unicode**
- user object**
- XML**
- XML namespace**

The following terms are defined in [\[MS-OFCGLOS\]](#):

- application server**
- Business Data Connectivity (BDC)**
- collation**
- data connection**
- endpoint**
- group**
- partition**
- provisioned**
- schema version**
- security principal**
- social data**
- subscriber**
- Uniform Resource Identifier (URI)**
- Uniform Resource Locator (URL)**
- user profile**
- User Profile Service**

user profile store
Web Services Description Language (WSDL)
WSDL message
WSDL operation
XML namespace prefix
XML schema

The following terms are specific to this document:

Identity Lifecycle Management Service: A set of identity management services that enables protocol clients to manage digital identities from creation through retirement. Services include identity synchronization, certificate and password management, and user provisioning.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[MS-DTYP] Microsoft Corporation, "[Windows Data Types](#)".

[MS-SPSTWS] Microsoft Corporation, "[SharePoint Security Token Service Web Service Protocol](#)".

[MS-WSSFO3] Microsoft Corporation, "[Windows SharePoint Services \(WSS\): File Operations Database Communications Version 3 Protocol](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP1.2/1] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XML] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Fourth Edition)", W3C Recommendation, August 2006, <http://www.w3.org/TR/2006/REC-xml-20060816/>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

[MS-SPTWS] Microsoft Corporation, "[Service Platform Topology Web Service Protocol](#)".

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

[RFC2822] Resnick, P., Ed., "Internet Message Format", STD 11, RFC 2822, April 2001, <http://www.ietf.org/rfc/rfc2822.txt>

[SOAP1.2/2] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 2: Adjuncts", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part2-20030624>

1.3 Overview

This protocol enables protocol clients to interact with the **User Profile Service** running on the middle-tier **application server**. The protocol client obtains information required to establish a connection, retrieves information about the permissions associated with the protocol client, and retrieves **URLs** to the sites that offer the User Profile Service. The protocol does not require that the protocol client had previous interaction with this **service**, nor does it require state information from the protocol client. The protocol requires that the protocol client obtain the URL of the service **endpoint (4)** of this protocol server and authenticate to use this service.

1.4 Relationship to Other Protocols

This protocol uses the **SOAP** message protocol for formatting request and response messages, as described in [\[SOAP1.1\]](#), [\[SOAP1.2/1\]](#) and [\[SOAP1.2/2\]](#). It transmits those messages by using **HTTP**, as described in [\[RFC2616\]](#), or **Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)**, as described in [\[RFC2818\]](#).

The following diagram shows the underlying messaging and transport stack used by the protocol:




Figure 1: This protocol in relation to other protocols

1.5 Prerequisites/Preconditions

This protocol operates against a protocol server that exposes one or more endpoint (4) **URIs** that are known by protocol clients. The endpoint (4) URI of the protocol server and the transport that is used by the protocol server are either known by the protocol client or obtained by using the discovery mechanism that is described in [\[MS-SPTWS\]](#).

The protocol client obtains the requisite ApplicationClassId and ApplicationVersion values and the endpoint (4) URI of the protocol server that provides the discovery mechanism, as described in [\[MS-SPTWS\]](#), by means that are independent of either protocol.

This protocol requires the protocol client to have appropriate permission to call the methods on the protocol server.

The protocol client implements the token-based security mechanisms that are required by the protocol server and related security protocols, as described in [\[MS-SPSTWS\]](#).

1.6 Applicability Statement

This protocol retrieves basic connectivity and configuration information for the user profile middle-tier service. It is the first interaction between a protocol client and this site service, and is required before the protocol client retrieves any **user profile** information.

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Supported Transports:** This protocol can be implemented by using transports that support sending Simple Object Access Protocol (SOAP) messages, as described in section 2.1.
- **Protocol Versions:** This protocol is not versioned.

Capability Negotiation: This protocol does not support version negotiation.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

Protocol servers MUST support Simple Object Access Protocol (SOAP) over Hypertext Transfer Protocol (HTTP), Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS), or **TCP**.

All protocol messages MUST be transported by using HTTP or TCP bindings at the transport level.

Protocol messages MUST be formatted as specified in either [\[SOAP1.1\]](#) section 4 or [\[SOAP1.2/1\]](#) section 5. Protocol server faults MUST be returned by using HTTP status codes, as specified in [\[RFC2616\]](#) section 10, or **SOAP faults**, as specified in [\[SOAP1.1\]](#) section 4.4 or [\[SOAP1.2/1\]](#) section 5.4.

If the HTTPS transport is used, a server certificate MUST be deployed.

This protocol MAY transmit an additional SOAP header, the **ServiceContext** header, as specified in [\[MS-SPSTWS\]](#).

This protocol does not define any means for activating a protocol server or protocol client. The protocol server MUST be configured and begin listening in an implementation-specific way. In addition, the protocol client MUST know the format and transport that is used by the server, for example, the SOAP format over an HTTP transport.

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and **WSDL**, as specified in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific **XML namespace prefix** for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
q1	http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration	
q2	http://schemas.microsoft.com/2003/10/Serialization/Arrays	
q3	http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities	
ser	http://schemas.microsoft.com/2003/10/Serialization/	
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
tns	http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration	
tns1	http://Microsoft/Office/Server/UserProfiles	
tns2	http://tempuri.org/	
tns3	http://tempuri.org/Imports	

Prefix	Namespace URI	Reference
wsaw	http://www.w3.org/2006/05/addressing/wsdl	
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1] [XMLSCHEMA2]

2.2.2 Messages

This specification does not define any common **WSDL message** definitions.

2.2.3 Elements

This specification does not define any common XML schema element definitions.

2.2.4 Complex Types

This specification does not define any common XML schema complex type definitions.

2.2.5 Simple Types

The following table summarizes the set of common XML schema simple type definitions defined by this specification. XML schema simple type definitions that are specific to a particular operation are described with the operation.

Simple type	Description
char	The char simple type is a Unicode character that is stored in a 4-byte integer. This type MUST NOT be used by this protocol.
duration	The duration simple type is the length of time, as specified in [XMLSCHEMA1] and [XMLSCHEMA2] . This type MUST NOT be used by this protocol.

2.2.5.1 char

Namespace: http://schemas.microsoft.com/2003/10/Serialization/

The **char** simple type is a Unicode character that is stored in a 4-byte integer. This type **MUST NOT** be used by this protocol.

```
<xs:simpleType name="char" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:int"/>
</xs:simpleType>
```

2.2.5.2 duration

Namespace: http://schemas.microsoft.com/2003/10/Serialization/

The **duration** simple type is the length of time, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#). This type **MUST NOT** be used by this protocol.

```
<xs:simpleType name="duration" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:duration">
    <xs:pattern value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?"/>
    <xs:minInclusive value="-P10675199DT2H48M5.4775808S"/>
    <xs:maxInclusive value="P10675199DT2H48M5.4775807S"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

2.2.9 Common Data Structures

This specification does not define any common XML schema data structures.

3 Protocol Details

This is a server-side protocol. The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

3.1 Server Details

This protocol is based on stateless interaction between the protocol client and protocol server. The protocol simply exposes the current configuration state of the User Profile Service to all authenticated **user objects**. There are no dependencies between the information sent in one client-server request/response pair and the next pair; all dependencies are based on the current state of the application service. They are specified in the following figure.




Figure 2: State Dependencies of the application service

The User Profile Service uses authentication mechanisms that are standard for Web Services and SOAP.

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

This protocol enables protocol clients to query the latest configuration state information for the User Profile Service.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

This protocol supports only the **GetProfileProperties** operation. This **WSDL operation** is stateless.

The following table summarizes the list of operations as defined by this specification.

Operation	Description
GetProfileProperties	This WSDL operation retrieves the configuration state of the User Profile Service.

3.1.4.1 GetProfileProperties

This WSDL operation retrieves the configuration state of the User Profile Service.

The following is the WSDL port type specification of the **GetProfileProperties** WSDL operation.

```
<wsdl:operation name="GetProfileProperties" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input wsaw:Action="http://Microsoft.Office.Server.UserProfiles/GetProfileProperties"
    message="tns2:IProfilePropertyService_GetProfileProperties_InputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
  <wsdl:output
    wsaw:Action="http://tempuri.org/IProfilePropertyService/GetProfilePropertiesResponse"
    message="tns2:IProfilePropertyService_GetProfileProperties_OutputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>
```

The protocol client sends an **IProfilePropertyService_GetProfileProperties_InputMessage** request message and the protocol server responds with an **IProfilePropertyService_GetProfileProperties_OutputMessage** response message containing the configuration state information associated with the application service.

3.1.4.1.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IProfilePropertyService_GetProfileProperties_InputMessage	The request WSDL message for the GetProfileProperties WSDL operation.
IProfilePropertyService_GetProfileProperties_OutputMessage	The response WSDL message for the GetProfileProperties WSDL operation.

3.1.4.1.1.1 IProfilePropertyService_GetProfileProperties_InputMessage

The request WSDL message for the **GetProfileProperties** WSDL operation.

The **SOAP action** value is:

```
http://Microsoft.Office.Server.UserProfiles/GetProfileProperties
```

The **SOAP body** contains the **GetProfileProperties** element.

3.1.4.1.1.2 IProfilePropertyService_GetProfileProperties_OutputMessage

The response WSDL message for the **GetProfileProperties** WSDL operation.

The SOAP body contains the **GetProfilePropertiesResponse** element.

3.1.4.1.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetProfileProperties	The input data for the GetProfileProperties WSDL operation.
GetProfilePropertiesResponse	The result data for the GetProfileProperties WSDL operation.

3.1.4.1.2.1 GetProfileProperties

The **GetProfileProperties** element specifies the input data for the **GetProfileProperties** WSDL operation.

```
<xs:element name="GetProfileProperties" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence/>
  </xs:complexType>
</xs:element>
```

3.1.4.1.2.2 GetProfilePropertiesResponse

The **GetProfilePropertiesResponse** element specifies the result data for the **GetProfileProperties** WSDL operation.

```

<xs:element name="GetProfilePropertiesResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element xmlns:tns1="http://Microsoft/Office/Server/UserProfiles" minOccurs="0"
name="GetProfilePropertiesResult" nillable="true" type="tns1:ProfilePropertyData"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

GetProfilePropertiesResult: A **ProfilePropertyData** element that contains the configuration state information. However, if connection failures, authentication failures, or other transport errors occurred before the request reached the corresponding SOAP service endpoint (4), then the element will not contain the **ProfilePropertyData** element.

3.1.4.1.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfguid	A list of GUIDs .
ProfilePropertyData	The information required for a SOAP protocol client to connect to a User Profile Service that is currently running.

3.1.4.1.3.1 ProfilePropertyData

Namespace: http://Microsoft/Office/Server/UserProfiles

This complex type is the main payload that the **GetProfileProperties** operation sends to the protocol client. It exposes the information required for a SOAP protocol client to connect to a User Profile Service that is currently running.

Because the User Profile Service configuration state contains optional elements, the protocol client **MUST** plan for the possibility that elements are not present.

```

<xs:complexType name="ProfilePropertyData" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" name="AppID" type="ser:guid"/>
    <xs:element
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration"
minOccurs="0" name="AppStatus" type="q1:SPObjectStatus"/>
    <xs:element minOccurs="0" name="ChangeJobSchedule" nillable="true" type="xs:string"/>
    <xs:element minOccurs="0" name="DaysWorthOfEventsToKeep" type="xs:int"/>
    <xs:element minOccurs="0" name="DisableAddCommentWebService" type="xs:boolean"/>
    <xs:element minOccurs="0" name="DisableProfileCreationWebServicesForTenants"
type="xs:boolean"/>
    <xs:element minOccurs="0" name="DocumentsFollowingLimit" type="xs:int"/>
    <xs:element minOccurs="0" name="FeedCacheLMTTTLDeltaHours" type="xs:int"/>
    <xs:element minOccurs="0" name="FeedCacheTTLHours" type="xs:int"/>
    <xs:element minOccurs="0" name="ILMMachineName" nillable="true" type="xs:string"/>
    <xs:element minOccurs="0" name="IgnoreIsActiveFlag" type="xs:boolean"/>
    <xs:element minOccurs="0" name="IsClaimProvider" nillable="true" type="xs:boolean"/>
    <xs:element minOccurs="0" name="IsCrossForestADImport" type="xs:boolean"/>
    <xs:element minOccurs="0" name="IsIlmFullyConfigured" type="xs:boolean"/>

```



```

<xs:element minOccurs="0" name="IsInitialDataPopulated" type="xs:boolean"/>
<xs:element minOccurs="0" name="IsSynchronizationRunning" type="xs:boolean"/>
<xs:element minOccurs="0" name="IsUpscaleILMUsed" type="xs:boolean"/>
<xs:element minOccurs="0" name="IsUsersOnlyILMImport" type="xs:boolean"/>
<xs:element minOccurs="0" name="NetBIOSDomainNamesEnabled" type="xs:boolean"/>
<xs:element minOccurs="0" name="NoILMUsed" type="xs:boolean"/>
<xs:element minOccurs="0" name="Office365NotificationEnabled" type="xs:boolean"/>
<xs:element xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="PartitionIDs" nillable="true" type="q2:ArrayOfguid"/>
<xs:element
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities"
minOccurs="0" name="PartitionOptions" type="q3:SPPartitionOptions"/>
<xs:element minOccurs="0" name="PeopleFollowingLimit" type="xs:int"/>
<xs:element minOccurs="0" name="PerfmonInstanceHandle" type="xs:int"/>
<xs:element minOccurs="0" name="ProfileDatabaseBackwardsCompatibleSchemaVersion"
nillable="true" type="xs:string"/>
<xs:element minOccurs="0" name="ProfileDatabaseConnectionString" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="ProfileDatabaseSchemaVersion" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="ProfileStoreCollationId" type="xs:int"/>
<xs:element minOccurs="0" name="ProfileStoreLanguage" type="xs:int"/>
<xs:element
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration"
minOccurs="0" name="RemotePersonalSitePages"
type="tns:UserProfileApplication.PersonalSitePagesRemoteStatus"/>
<xs:element minOccurs="0" name="SecTrimCacheEnabled" type="xs:boolean"/>
<xs:element minOccurs="0" name="SecTrimCacheMaxNumberOfDataItems" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimCacheMaxRetryCount" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimCacheMaxTTLMinutes" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimCacheNonAuthoritativeAccessTTLMinutes"
type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimCacheThrottledTTLMinutes" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimMaxNumberOfSocialUrls" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimOptimizationsEnabled" type="xs:boolean"/>
<xs:element minOccurs="0" name="Secret" type="ser:guid"/>
<xs:element minOccurs="0" name="SerializedAdministratorAcl" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="SitesFollowingLimit" type="xs:int"/>
<xs:element minOccurs="0" name="SkipBDCImport" type="xs:boolean"/>
<xs:element minOccurs="0" name="SocialDatabaseBackwardsCompatibleSchemaVersion"
nillable="true" type="xs:string"/>
<xs:element minOccurs="0" name="SocialDatabaseConnectionString" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="SocialDatabaseSchemaVersion" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="SyncServiceInstanceId" type="ser:guid"/>
<xs:element minOccurs="0" name="UseOnlyPreferredDomainControllers" type="xs:boolean"/>
<xs:element minOccurs="0" name="YammerEnabled" type="xs:boolean"/>
</xs:sequence>
</xs:complexType>

```

AppID: The unique identifier of the User Profile Service that is currently running.

AppStatus: An **SPObjctStatus** (section [3.1.4.1.4.2](#)) enumeration that specifies the current state of the User Profile Service specified by the **AppID** element.

ChangeJobSchedule: A string that specifies the schedule for the automated processing of tasks for the User Profile Service associated with the specified **AppID** element. The string MUST be formatted as specified by the following **ABNF** ([RFC5234]) grammar.

```
ChangeJobSchedule = SecondRecurrence / MinuteRecurrence / HourlyRecurrence / DailyRecurrence /
WeeklyRecurrence / MonthlyRecurrence / YearlyRecurrence
SecondRecurrence = "every " NONZEROSECONDORMINUTE " seconds"
MinuteRecurrence = "every " NONZEROSECONDORMINUTE " minutes " [SecondOrMinuteInstance]
HourlyRecurrence = "hourly " SecondOrMinuteInstance
DailyRecurrence = "daily " TimeInstance
WeeklyRecurrence = "weekly " DayInstance
MonthlyRecurrence = "monthly " (DateInstance / OrdinalDayInstance)
YearlyRecurrence = "yearly " MonthInstance
MonthInstance = ("at " MONTH " " DATE " " HourInstance) / ("between " MONTH " " DATE " "
HourInstance " and " MONTH " " DATE " " HourInstance)
DateInstance = ("at " DATE " " HourInstance) / ("between " DATE " " HourInstance " and " DATE
" " HourInstance)
DayInstance = ("at " DAY " " HourInstance) / ("between " DAY " " HourInstance " and " DAY " "
HourInstance)
OrdinalDayInstance = "at " ORDINAL " " DAY " " HourInstance
TimeInstance = ("at " HourInstance) / ("between " HourInstance " and " HourInstance)
SecondOrMinuteInstance = ("at " SECONDDORMINUTE) / ("between " SECONDDORMINUTE " and "
SECONDDORMINUTE)
HourInstance = HOUR ":" SECONDDORMINUTE [ ":" SECONDDORMINUTE ]
MONTH = "jan" / "feb" / "mar" / "apr" / "may" / "jun" / "jul" / "aug" / "sep" / "oct" / "nov"
/ "dec"
DATE = ( [ "1" / "2" ] NONZERODIGIT ) / "10" / "20" / "30" / "31" ; 1-31
DAY = "sun" / "mon" / "tue" / "wed" / "thu" / "fri" / "sat" / "su" / "mo" / "tu" / "we" /
"th" / "fr" / "sa"
ORDINAL = "first" / "second" / "third" / "fourth" / "last"
HOUR = ( [ "1" ] DIGIT ) / "20" / "21" / "22" / "23" ; 0-23
SECONDDORMINUTE = "0" / NONZEROSECONDDORMINUTE ; 0-59
NONZEROSECONDDORMINUTE = NONZERODIGIT / ( ( "1" / "2" / "3" / "4" / "5" ) DIGIT ) ; 1-59
NONZERODIGIT = "1" / "2" / "3" / "4" / "5" / "6" / "7" / "8" / "9" ; 1-9
DIGIT = "0" / NONZERODIGIT ; 0-9
```

DaysWorthOfEventsToKeep: The number of days that logs for tracking changes in the **user profile store** are stored before they are removed.

DisableAddCommentWebService: If set to true, it disables the AddComment Web Service, and if set to false, it enables the service.

DisableProfileCreationWebServicesForTenants: If set to true, it disables Web Services to create Profiles for all Tenants of the User Profile Service, and if set to false, it enables these services.

DocumentsFollowingLimit: Limit for the number of documents a user can follow. The maximum value allowed for this is 500.

FeedCacheLMTTTLDeltaHours: The time to live for the last modified time of any feed cache entry.

FeedCacheTTLHours: The time to live for any feed cache entry.

ILMMachineName: The name of the computer in standard **DNS** format that runs the **Identity Lifecycle Management Service** associated with this User Profile Service.

IgnoreIsActiveFlag: Specifies whether the current authenticated user object that invoked this request for the **GetProfileProperties** operation is active in this User Profile Service.

IsClaimProvider: The value MAY be TRUE, FALSE, or NULL. The protocol client MUST ignore this value.

IsCrossForestADImport: This is not supported and setting this has no effect on existing functionality. This MUST always be false.

IsIlmFullyConfigured: Specifies whether the computer, specified by the **ILMMachineName** element, is completely configured to synchronize user profile information with this User Profile Service.

IsInitialDataPopulated: Specifies whether user profile information was imported successfully at least once, which initially populates user profile information in the user profile store.

IsSynchronizationRunning: Indicates whether synchronization is running for this User Profile Service at the present time.

IsUpscaleILMUsed: Specifies whether the Identity Lifecycle Management Service is managed externally to the site. If this value is TRUE, the elements **ILMMachineName**, **IsIlmFullyConfigured**, **IsUsersOnlyILMImport**, **SkipBDCImport**, and **SyncServiceInstanceId** are not applicable and MUST be ignored.

IsUsersOnlyILMImport: Specifies whether the user profile synchronization process imports only user objects for the Identity Lifecycle Management Service, or whether it also imports **groups (2)**.

NetBIOSDomainNamesEnabled: Indicates whether NetBIOS domain names are being used during synchronization of this User Profile Service with a directory using Identity Lifecycle Management Service.

NoILMUsed: Indicates whether the Identity Lifecycle Management Service-based synchronization is enabled for this User Profile Service.

Office365NotificationEnabled: Specifies whether the notification about Office365 features such as OneDrive and Yammer is displayed in the Central Admin status bar.

PartitionIDs: The list of **partitions (1)** that were **provisioned** for this User Profile Service.

PartitionOptions: Specifies whether partitioning is supported, as specified by the **SPPartitionOptions** (section [3.1.4.1.4.3](#)) enumeration.

PeopleFollowingLimit: Limit for the number of people a user can follow. The maximum value allowed for this is 1000.

PerfmonInstanceHandle: MUST be set to -1.

ProfileDatabaseBackwardsCompatibleSchemaVersion: The earliest **schema version** with which the schema version of the user profile store is backward-compatible. The current schema is not considered to be compatible with any database schema with a version number lower than this version number. This version number appears in the version number format specified in the description of **ProfileDatabaseSchemaVersion**.

ProfileDatabaseConnectionString: The **data connection (2)** string that is associated with the user profile store.

ProfileDatabaseSchemaVersion: The current schema version number of the user profile store. The version number appears in the format major.minor[.build[.revision]], where major, minor, build, and revision are non-negative integers. 4.0 and 12.0.47.0 are examples of valid version

numbers. When the database schema is updated, this version number is increased. For the purpose of comparing version numbers, the integer fields appear in decreasing order of significance.

ProfileStoreCollationId: The **collation** identifier of the user profile store.

ProfileStoreLanguage: **LCID** of the language of the user profile store.

RemotePersonalSitePages: An enumeration that specifies whether or not various personal site pages are hosted remotely or on premise.

SecTrimCacheEnabled: Specifies if the security trimmer access cache is enabled. Default value equals true.

SecTrimCacheMaxNumberOfDataItems: Specifies the maximum number of data items in security trim cache per user. Default is 50 items in cache per-user.

SecTrimCacheMaxRetryCount: Specifies the maximum number of attempts that can be made when the search provider gets queried before persisting the cache entry state. Default number of retries equals 5.

SecTrimCacheMaxTTLMinutes: Indicates how long the security trim cache exists in minutes before being purged. Default TTL is 1440 minutes (1 day).

SecTrimCacheNonAuthoritativeAccessTTLMinutes: Indicates how long a cached non-authoritative entry exists in minutes in security trim cache before being purged. Default TTL is 15 minutes.

SecTrimCacheThrottledTTLMinutes: Indicates how long a throttled entry can be cached in minutes before being purged. Default TTL is 5 minutes.

SecTrimMaxNumberOfSocialUrls: Specifies the maximum number of URLs that the Search Service will be queried for to satisfy a social data request. This value should be defined in increments of 8, as a single security trim request may be broken down into multiple search service requests each with a non-configurable limit to 8 URLs per-request. The default value equals 24 URLs.

SecTrimOptimizationsEnabled: Specifies if security trim optimizations are enabled. Default value equals true.

Secret: A shared secret between the protocol client and protocol server.

SerializedAdministratorAcl: A string that specifies the **access control list (ACL)** that specifies the user objects that have administrative permissions associated with this user profile application. The protocol client uses this information to enable or disable specific administrator-only interactions with the User Profile Service. This field is optional because verification of authentication occurs at the service endpoint (4). This string MUST be well-formed **XML**, as specified by [\[XML\]](#) section 2. The root node of the XML MUST be an "acl" element. The "acl" element MUST specify a **version** attribute whose value MUST be the string ([\[XMLSCHEMA2\]](#) section 3.2.1) "1.0". The "acl" element MUST contain one "ace" child element for each **access control entry (ACE)** appearing in the **ACL**. Each "ace" element MUST specify the following attributes:

- **identityName:** A string ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the login name of the **security principal (2)**.
- **displayName:** A string ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the display name of the principal.

- **sid**: A string ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the **security identifier (SID)** of the principal. This is the contents of the **SID** byte array specified in [\[MS-DTYP\]](#) section 2.4.2, represented as a string via **base64** encoding.
- **allowRights**: A string ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies a Rights Mask ([\[MS-WSSFO3\]](#) section 2.2.2.15) that specifies the permissions granted to the principal. This string MUST consist of the integer representation of the Rights Mask ([\[MS-WSSFO3\]](#)).
- **denyRights**: A string ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies a Rights Mask ([\[MS-WSSFO3\]](#) section 2.2.2.15) that specifies the permissions denied to the principal. This string MUST consist of the integer representation of the Rights Mask ([\[MS-WSSFO3\]](#)).

SitesFollowingLimit: Limit for the number of sites a user can follow. The maximum value allowed for this is 500.

SkipBDCImport: Specifies whether the **Business Data Connectivity (BDC)** synchronization steps will be skipped during the process that synchronizes the user profile store with external sources.

SocialDatabaseBackwardsCompatibleSchemaVersion: The earliest schema version with which the schema version of the **social data** within the user profile store is backward-compatible. The current schema is not considered to be compatible with any database schema with a version number lower than this version number. This version number appears in the version number format specified in the description of **ProfileDatabaseSchemaVersion**.

SocialDatabaseConnectionString: The data connection (2) string associated with the social data within the user profile store.

SocialDatabaseSchemaVersion: The schema version of the social data within the user profile store. When the schema is updated, this version number is increased. This version number appears in the version number format specified in the description of **ProfileDatabaseSchemaVersion**.

SyncServiceInstanceId: The identifier of the user profile store's profile synchronization service instance.

UseOnlyPreferredDomainControllers: Specifies whether communication will only take place with a specified **domain controller (DC)**, or whether communication MAY also take place with other domain controllers.

YammerEnabled: Specifies whether Yammer is used as the social platform. True if Yammer is used as the social platform. False if SharePoint social (legacy) is used.

3.1.4.1.3.2 ArrayOfguid

Namespace: <http://schemas.microsoft.com/2003/10/Serialization/Arrays>

The **ArrayOfguid** element specifies a list of GUIDs.

```
<xs:complexType name="ArrayOfguid" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="guid" type="ser:guid"/>
  </xs:sequence>
</xs:complexType>
```

guid: A **GUID** as specified in section [3.1.4.1.4.1](#).

3.1.4.1.4 Simple Types

The following table summarizes the XML schema simple type definitions that are specific to this operation.

Simple type	Description
guid	A GUID that is 16 bytes long.
SPObjctStatus	The processing status of the object or service.
SPPartitionOptions	An enumeration that specifies whether the User Profile Service was partitioned.
UserProfileApplication.PersonalSitePagesRemoteStatus	An enumeration that specifies whether or not various personal site pages are hosted remotely or on premise.

3.1.4.1.4.1 guid

Namespace: <http://schemas.microsoft.com/2003/10/Serialization/>

A GUID that is 16 bytes long.

```
<xs:simpleType name="guid" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:restriction base="xs:string">  
    <xs:pattern value="\{8\}-\{4\}-\{4\}-\{4\}-\{4\}-\{12\}"/>  
  </xs:restriction>  
</xs:simpleType>
```

3.1.4.1.4.2 SPObjctStatus

Namespace: <http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration>

This element specifies the processing status of the object or service.

```
<xs:simpleType name="SPObjctStatus" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:restriction base="xs:string">  
    <xs:enumeration value="Online"/>  
    <xs:enumeration value="Disabled"/>  
    <xs:enumeration value="Offline"/>  
    <xs:enumeration value="Unprovisioning"/>  
    <xs:enumeration value="Provisioning"/>  
    <xs:enumeration value="Upgrading"/>  
  </xs:restriction>  
</xs:simpleType>
```

The following table specifies the allowable values for the **SPObjctStatus** simple type.

Value	Meaning
Online	The object or service is online and ready.

Value	Meaning
Disabled	The object or service is disabled and is not accessible.
Offline	The object or service is temporarily offline.
Unprovisioning	The object or service is being un-provisioned and will be disabled shortly.
Provisioning	The object or service is being provisioned and is temporarily unavailable.
Upgrading	The object or service is being upgraded and is temporarily offline.

3.1.4.1.4.3 SPPartitionOptions

Namespace: http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities

This element is an enumeration that specifies whether the User Profile Service was partitioned.

```
<xs:simpleType name="SPPartitionOptions" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="UnPartitioned"/>
    <xs:enumeration value="UniquePartitionPerSubscription"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **SPPartitionOptions** simple type.

Value	Meaning
UnPartitioned	Not Partitioned
UniquePartitionPerSubscription	Partitioned so that a unique partition (1) exists for each subscriber , and each subscriber is isolated from the information or changes for another subscriber.

3.1.4.1.4.4 UserProfileApplication.PersonalSitePagesRemoteStatus

Namespace: http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration

An enumeration that specifies whether or not various personal site pages are hosted remotely or on premise.

```
<xs:simpleType name="UserProfileApplication.PersonalSitePagesRemoteStatus"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:list>
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="None"/>
        <xs:enumeration value="CloudStorage"/>
        <xs:enumeration value="SitesPage"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:list>
</xs:simpleType>
```

The following table specifies the allowable values for the **UserProfileApplication.PersonalSitePagesRemoteStatus** simple type.

Value	Meaning
None	No personal site pages are hosted remotely.
CloudStorage	The cloud storage personal site page is hosted remotely.
SitesPage	The Sites personal site page is hosted remotely.

3.1.4.1.5 Attributes

None.

3.1.4.1.6 Groups

None.

3.1.4.1.7 Attribute Groups

None.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

This section describes example scenarios for retrieving the current configuration state of the User Profile Service.

4.1 Retrieving User Profile Service Configuration State

The protocol client constructs the following WSDL message to retrieve the current configuration state of the User Profile Service.

```
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope"
xmlns:a="http://www.w3.org/2005/08/addressing" xmlns:u="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <s:Header>
    <a:Action
s:mustUnderstand="1">http://Microsoft.Office.Server.UserProfiles/GetProfileProperties</a:Acti
on>
    <a:MessageID>urn:uuid:3eb21222-2b62-4735-a9ac-e673a6ee31df</a:MessageID>
    <a:ReplyTo>
      <a:Address>http://www.w3.org/2005/08/addressing/anonymous</a:Address>
    </a:ReplyTo>
    <a:To
s:mustUnderstand="1">net.tcp://mossperf64d2325:32845/59de0abe24804e18aeccdc292a7581f1/Profile
PropertyService.svc</a:To>
    <o:Security s:mustUnderstand="1" xmlns:o="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd">
      ...
    </o:Security>
  </s:Header>
  <s:Body>
    <GetProfileProperties xmlns="http://tempuri.org/"></GetProfileProperties>
  </s:Body>
</s:Envelope>
```

The protocol server sends the following response.

```
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope"
xmlns:a="http://www.w3.org/2005/08/addressing" xmlns:u="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <s:Header>
    <a:Action
s:mustUnderstand="1">http://tempuri.org/IProfilePropertyService/GetProfilePropertiesResponse<
/a:Action>
    <a:RelatesTo>urn:uuid:3eb21222-2b62-4735-a9ac-e673a6ee31df</a:RelatesTo>
    <a:To s:mustUnderstand="1">http://www.w3.org/2005/08/addressing/anonymous</a:To>
    <o:Security s:mustUnderstand="1" xmlns:o="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd">
      ...
    </o:Security>
  </s:Header>
  <s:Body>
    <GetProfilePropertiesResponse xmlns="http://tempuri.org/">
      <GetProfilePropertiesResult xmlns:b="http://Microsoft/Office/Server/UserProfiles"
xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
        <d4p1:AppID>9f5c3c8f-beec-44ea-bc04-6ffe2fb0e7bc</d4p1:AppID>
        <d4p1:AppStatus>Online</d4p1:AppStatus>
        <d4p1:ChangeJobSchedule>hourly between 0 and 0</d4p1:ChangeJobSchedule>
        <d4p1:ILMMachineName i:nil="true"></d4p1:ILMMachineName>
      </GetProfilePropertiesResult>
    </s:Body>
</s:Envelope>
```

```

<d4p1:IgnoreIsActiveFlag>>false</d4p1:IgnoreIsActiveFlag>
<d4p1:IsClaimProvider i:nil="true"></d4p1:IsClaimProvider>
<d4p1:IsIilmFullyConfigured>>false</d4p1:IsIilmFullyConfigured>
<d4p1:IsInitialDataPopulated>>false</d4p1:IsInitialDataPopulated>
<d4p1:IsUpscaleILMUsed>>false</d4p1:IsUpscaleILMUsed>
<d4p1:IsUsersOnlyILMImport>>false</d4p1:IsUsersOnlyILMImport>
<d4p1:PartitionIDs xmlns:d5p1="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
  <d5p1:guid>0c37852b-34d0-418e-91c6-2ac25af4be5b</d5p1:guid>
</d4p1:PartitionIDs>
<d4p1:PartitionOptions>UnPartitioned</d4p1:PartitionOptions>
<d4p1:PerfmonInstanceHandle>-1</d4p1:PerfmonInstanceHandle>

<d4p1:ProfileDatabaseBackwardsCompatibleSchemaVersion>14.0.82.0</d4p1:ProfileDatabaseBackward
sCompatibleSchemaVersion>
  <d4p1:ProfileDatabaseConnectionString>Data Source=TestMachine;Initial
Catalog="User Profile Service
Application_ProfileDB_715524f91eac4f7caeee38a2f53375c9";Integrated
Security=True;Enlist=False;Connect Timeout=15</d4p1:ProfileDatabaseConnectionString>
  <d4p1:ProfileDatabaseSchemaVersion>14.0.82.0</d4p1:ProfileDatabaseSchemaVersion>
<d4p1:ProfileStoreCollationId>25</d4p1:ProfileStoreCollationId>
<d4p1:ProfileStoreLanguage>1033</d4p1:ProfileStoreLanguage>
<d4p1:SerializedAdministratorAcl>
  <acl version="1.0">
    <ace identityName="domain\user1" displayName="User 1"
sid="AQUAAAAAAAAUVAAAAoGXPfnhLm1/nfIdwKgQBAA==" allowRights="8" denyRights="0" />
  </acl>
</d4p1:SerializedAdministratorAcl>
<d4p1:SkipBDCImport>>false</d4p1:SkipBDCImport>

<d4p1:SocialDatabaseBackwardsCompatibleSchemaVersion>14.0.21.0</d4p1:SocialDatabaseBackwardsC
ompatibleSchemaVersion>
  <d4p1:SocialDatabaseConnectionString>Data Source=TestMachine;Initial Catalog="User
Profile Service Application_SocialDB_bba7ac6987904e2b93f3aded1af2e65d";Integrated
Security=True;Enlist=False;Connect Timeout=15</d4p1:SocialDatabaseConnectionString>
  <d4p1:SocialDatabaseSchemaVersion>14.0.21.0</d4p1:SocialDatabaseSchemaVersion>
<d4p1:SyncServiceInstanceId>00000000-0000-0000-0000-
000000000000</d4p1:SyncServiceInstanceId>

<d4p1:UseOnlyPreferredDomainControllers>>false</d4p1:UseOnlyPreferredDomainControllers>
  </GetProfilePropertiesResult>
</GetProfilePropertiesResponse>
</s:Body>
</s:Envelope>

```

5 Security

5.1 Security Considerations for Implementers

There are no security considerations that are specific to this protocol. General security considerations pertaining to [RFC2822](#) apply.

This protocol does not introduce any additional security considerations beyond those that apply to its underlying protocols.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

For ease of implementation, the full WSDL is provided in this appendix.

```
<?xml version="1.0"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:tns2="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl" targetNamespace="http://tempuri.org/"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <xs:schema xmlns:tns3="http://tempuri.org/Imports"
targetNamespace="http://tempuri.org/Imports">
      <xs:import namespace="http://Microsoft/Office/Server/UserProfiles"/>
      <xs:import
namespace="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration"/>
      <xs:import
namespace="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities"/>
      <xs:import
namespace="http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration"/>
      <xs:import namespace="http://schemas.microsoft.com/2003/10/Serialization"/>
      <xs:import namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"/>
      <xs:import namespace="http://tempuri.org/">
    </xs:schema>
  </wsdl:types>
  <wsdl:portType name="IProfilePropertyService">
    <wsdl:operation name="GetProfileProperties">
      <wsdl:input
wsaw:Action="http://Microsoft.Office.Server.UserProfiles/GetProfileProperties"
message="tns2:IProfilePropertyService_GetProfileProperties_InputMessage"/>
      <wsdl:output
wsaw:Action="http://tempuri.org/IProfilePropertyService/GetProfilePropertiesResponse"
message="tns2:IProfilePropertyService_GetProfileProperties_OutputMessage"/>
    </wsdl:operation>
  </wsdl:portType>
  <wsdl:binding name="DefaultBinding_IProfilePropertyService"
type="tns2:IProfilePropertyService">
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="GetProfileProperties">
      <soap:operation
soapAction="http://Microsoft.Office.Server.UserProfiles/GetProfileProperties"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
  </wsdl:binding>
  <wsdl:message name="IProfilePropertyService_GetProfileProperties_InputMessage">
    <wsdl:part name="parameters" element="tns2:GetProfileProperties"/>
  </wsdl:message>
  <wsdl:message name="IProfilePropertyService_GetProfileProperties_OutputMessage">
    <wsdl:part name="parameters" element="tns2:GetProfilePropertiesResponse"/>
  </wsdl:message>
</wsdl:definitions>
```

7 Appendix B: Full XML Schema

Schema name	Prefix	Section
http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration	tns	7.7
http://Microsoft/Office/Server/UserProfiles	tns1	7.3
http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities	q3	7.6
http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration	q1	7.4
http://schemas.microsoft.com/2003/10/Serialization/Arrays	q2	7.5
http://schemas.microsoft.com/2003/10/Serialization/	ser	7.2
http://tempuri.org/	tns2	7.1

For ease of implementation, the following sections provide the full XML schema for this protocol.

7.1 <http://tempuri.org/> Schema

```
<?xml version="1.0"?>
<xs:schema elementFormDefault="qualified" targetNamespace="http://tempuri.org/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://Microsoft/Office/Server/UserProfiles"/>
  <xs:element name="GetProfileProperties">
    <xs:complexType>
      <xs:sequence/>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetProfilePropertiesResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element xmlns:tns1="http://Microsoft/Office/Server/UserProfiles" minOccurs="0"
name="GetProfilePropertiesResult" nillable="true" type="tns1:ProfilePropertyData"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
</xs:schema>
```

7.2 <http://schemas.microsoft.com/2003/10/Serialization/> Schema

```
<?xml version="1.0"?>
<xs:schema xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
attributeFormDefault="qualified" elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:element name="anyType" nillable="true" type="xs:anyType"/>
  <xs:element name="anyURI" nillable="true" type="xs:anyURI"/>
  <xs:element name="base64Binary" nillable="true" type="xs:base64Binary"/>
  <xs:element name="boolean" nillable="true" type="xs:boolean"/>
  <xs:element name="byte" nillable="true" type="xs:byte"/>
  <xs:element name="dateTime" nillable="true" type="xs:dateTime"/>
  <xs:element name="decimal" nillable="true" type="xs:decimal"/>
```

```

<xs:element name="double" nillable="true" type="xs:double"/>
<xs:element name="float" nillable="true" type="xs:float"/>
<xs:element name="int" nillable="true" type="xs:int"/>
<xs:element name="long" nillable="true" type="xs:long"/>
<xs:element name="QName" nillable="true" type="xs:QName"/>
<xs:element name="short" nillable="true" type="xs:short"/>
<xs:element name="string" nillable="true" type="xs:string"/>
<xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte"/>
<xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt"/>
<xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong"/>
<xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort"/>
<xs:element name="char" nillable="true" type="ser:char"/>
<xs:simpleType name="char">
  <xs:restriction base="xs:int"/>
</xs:simpleType>
<xs:element name="duration" nillable="true" type="ser:duration"/>
<xs:simpleType name="duration">
  <xs:restriction base="xs:duration">
    <xs:pattern value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
    <xs:minInclusive value="-P10675199DT2H48M5.4775808S"/>
    <xs:maxInclusive value="P10675199DT2H48M5.4775807S"/>
  </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="ser:guid"/>
<xs:simpleType name="guid">
  <xs:restriction base="xs:string">
    <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}"/>
  </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName"/>
<xs:attribute name="Id" type="xs:ID"/>
<xs:attribute name="Ref" type="xs:IDREF"/>
</xs:schema>

```

7.3 http://Microsoft/Office/Server/UserProfiles Schema

```

<?xml version="1.0"?>
<xs:schema xmlns:tns1="http://Microsoft/Office/Server/UserProfiles"
  xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
  elementFormDefault="qualified" targetNamespace="http://Microsoft/Office/Server/UserProfiles"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType name="ProfilePropertyData">
    <xs:sequence>
      <xs:element minOccurs="0" name="AppID" type="ser:guid"/>
      <xs:element
        xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration"
        minOccurs="0" name="AppStatus" type="q1:SPObjectStatus"/>
      <xs:element minOccurs="0" name="ChangeJobSchedule" nillable="true" type="xs:string"/>
      <xs:element minOccurs="0" name="DaysWorthOfEventsToKeep" type="xs:int"/>
      <xs:element minOccurs="0" name="DisableAddCommentWebService" type="xs:boolean"/>
      <xs:element minOccurs="0" name="DisableProfileCreationWebServicesForTenants"
        type="xs:boolean"/>
      <xs:element minOccurs="0" name="DocumentsFollowingLimit" type="xs:int"/>
      <xs:element minOccurs="0" name="FeedCacheLMTTLDeltaHours" type="xs:int"/>
      <xs:element minOccurs="0" name="FeedCacheTTLHours" type="xs:int"/>
      <xs:element minOccurs="0" name="ILMMachineName" nillable="true" type="xs:string"/>
      <xs:element minOccurs="0" name="IgnoreIsActiveFlag" type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>

```

```

<xs:element minOccurs="0" name="IsClaimProvider" nillable="true" type="xs:boolean"/>
<xs:element minOccurs="0" name="IsCrossForestADImport" type="xs:boolean"/>
<xs:element minOccurs="0" name="IsIilmFullyConfigured" type="xs:boolean"/>
<xs:element minOccurs="0" name="IsInitialDataPopulated" type="xs:boolean"/>
<xs:element minOccurs="0" name="IsSynchronizationRunning" type="xs:boolean"/>
<xs:element minOccurs="0" name="IsUpscaleILMUsed" type="xs:boolean"/>
<xs:element minOccurs="0" name="IsUsersOnlyILMImport" type="xs:boolean"/>
<xs:element minOccurs="0" name="NetBIOSDomainNamesEnabled" type="xs:boolean"/>
<xs:element minOccurs="0" name="NoILMUsed" type="xs:boolean"/>
<xs:element minOccurs="0" name="Office365NotificationEnabled" type="xs:boolean"/>
<xs:element xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="PartitionIDs" nillable="true" type="q2:ArrayOfguid"/>
<xs:element
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities"
minOccurs="0" name="PartitionOptions" type="q3:SPPartitionOptions"/>
<xs:element minOccurs="0" name="PeopleFollowingLimit" type="xs:int"/>
<xs:element minOccurs="0" name="PerfmonInstanceHandle" type="xs:int"/>
<xs:element minOccurs="0" name="ProfileDatabaseBackwardsCompatibleSchemaVersion"
nillable="true" type="xs:string"/>
<xs:element minOccurs="0" name="ProfileDatabaseConnectionString" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="ProfileDatabaseSchemaVersion" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="ProfileStoreCollationId" type="xs:int"/>
<xs:element minOccurs="0" name="ProfileStoreLanguage" type="xs:int"/>
<xs:element
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration"
minOccurs="0" name="RemotePersonalSitePages"
type="tns:UserProfileApplication.PersonalSitePagesRemoteStatus"/>
<xs:element minOccurs="0" name="SecTrimCacheEnabled" type="xs:boolean"/>
<xs:element minOccurs="0" name="SecTrimCacheMaxNumberOfDataItems" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimCacheMaxRetryCount" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimCacheMaxTTLMinutes" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimCacheNonAuthoritativeAccessTTLMinutes"
type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimCacheThrottledTTLMinutes" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimMaxNumberOfSocialUrls" type="xs:int"/>
<xs:element minOccurs="0" name="SecTrimOptimizationsEnabled" type="xs:boolean"/>
<xs:element minOccurs="0" name="Secret" type="ser:guid"/>
<xs:element minOccurs="0" name="SerializedAdministratorAcl" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="SitesFollowingLimit" type="xs:int"/>
<xs:element minOccurs="0" name="SkipBDCImport" type="xs:boolean"/>
<xs:element minOccurs="0" name="SocialDatabaseBackwardsCompatibleSchemaVersion"
nillable="true" type="xs:string"/>
<xs:element minOccurs="0" name="SocialDatabaseConnectionString" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="SocialDatabaseSchemaVersion" nillable="true"
type="xs:string"/>
<xs:element minOccurs="0" name="SyncServiceInstanceId" type="ser:guid"/>
<xs:element minOccurs="0" name="UseOnlyPreferredDomainControllers" type="xs:boolean"/>
<xs:element minOccurs="0" name="YammerEnabled" type="xs:boolean"/>
</xs:sequence>
</xs:complexType>
<xs:element name="ProfilePropertyData" nillable="true" type="tns1:ProfilePropertyData"/>
<xs:import
namespace="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration"/>
<xs:import
namespace="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities"/>

```

```

<xs:import
namespace="http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration"/>
  <xs:import namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
  <xs:import namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
</xs:schema>

```

7.4

http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration Schema

```

<?xml version="1.0"?>
<xs:schema
xmlns:q1="http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:simpleType name="SPObjectStatus">
    <xs:restriction base="xs:string">
      <xs:enumeration value="Online"/>
      <xs:enumeration value="Disabled"/>
      <xs:enumeration value="Offline"/>
      <xs:enumeration value="Unprovisioning"/>
      <xs:enumeration value="Provisioning"/>
      <xs:enumeration value="Upgrading"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="SPObjectStatus" nillable="true" type="q1:SPObjectStatus"/>
</xs:schema>

```

7.5 http://schemas.microsoft.com/2003/10/Serialization/Arrays Schema

```

<?xml version="1.0"?>
<xs:schema xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:ser="http://schemas.microsoft.com/2003/10/Serialization/"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
  <xs:complexType name="ArrayOfguid">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="guid" type="ser:guid"/>
    </xs:sequence>
  </xs:complexType>
  <xs:element name="ArrayOfguid" nillable="true" type="q2:ArrayOfguid"/>
</xs:schema>

```

7.6 http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities Schema

```

<?xml version="1.0"?>
<xs:schema
xmlns:q3="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities"
xmlns:xs="http://www.w3.org/2001/XMLSchema">

```



```

<xs:simpleType name="SPPartitionOptions">
  <xs:restriction base="xs:string">
    <xs:enumeration value="UnPartitioned"/>
    <xs:enumeration value="UniquePartitionPerSubscription"/>
  </xs:restriction>
</xs:simpleType>
<xs:element name="SPPartitionOptions" nillable="true" type="q3:SPPartitionOptions"/>
</xs:schema>

```

7.7

http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administratio n Schema

```

<?xml version="1.0"?>
<xs:schema
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration"
elementFormDefault="qualified"
targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administrati
on" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://schemas.microsoft.com/2003/10/Serialization/" />
  <xs:simpleType name="UserProfileApplication.PersonalSitePagesRemoteStatus">
    <xs:list>
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:enumeration value="None"/>
          <xs:enumeration value="CloudStorage"/>
          <xs:enumeration value="SitesPage"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:list>
  </xs:simpleType>
  <xs:element name="UserProfileApplication.PersonalSitePagesRemoteStatus" nillable="true"
type="tns:UserProfileApplication.PersonalSitePagesRemoteStatus"/>
</xs:schema>

```

8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft SharePoint Server 2010
- Microsoft SharePoint Server 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

9 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

10 Index

A

Abstract data model
 [server](#) 14
[Applicability](#) 9
[Attribute groups](#) 12
[Attributes](#) 12

C

[Capability negotiation](#) 9
[Change tracking](#) 35
[charsimple type](#) 11
Client
 [overview](#) 13
Common data structures ([section 2.2.9](#) 12, [section 2.2.9](#) 12)
[Complex types](#) 11

D

Data model - abstract
 [server](#) 14
[durationsimple type](#) 11

E

Events
 [local - server](#) 24
 [timer - server](#) 24
Examples
 [overview](#) 25
 [retrieving user profile service configuration state](#) 25

F

[Fields - vendor-extensible](#) 9
[Full WSDL](#) 28
Full XML Schema ([section 7](#) 29, [section 7](#) 29)
 <http://Microsoft/Office/Server/UserProfiles/Schema> 30
 <http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration.Schema> 33
 <http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities.Schema> 32
 <http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration.Schema> 32
 <http://schemas.microsoft.com/2003/10/Serialization/Schema> 29
 <http://schemas.microsoft.com/2003/10/Serialization/Arrays.Schema> 32
 <http://tempuri.org/Schema> 29

G

[Glossary](#) 6
[Groups](#) 12

I

[Implementer - security considerations](#) 27
[Index of security parameters](#) 27
[Informative references](#) 8
Initialization
 [server](#) 14
[Introduction](#) 6

L

Local events
 [server](#) 24

M

Message processing
 [server](#) 14
Messages
 [attribute groups](#) 12
 [attributes](#) 12
 [charsimple type](#) 11
 common data structures ([section 2.2.9](#) 12, [section 2.2.9](#) 12)
 [complex types](#) 11
 [durationsimple type](#) 11
 [elements](#) 11
 [enumerated](#) 11
 [groups](#) 12
 [namespaces](#) 10
 [simple types](#) 11
 [syntax](#) 10
 [transport](#) 10

N

[Namespaces](#) 10
[Normative references](#) 7

O

Operations
 [GetProfileProperties](#) 14
[Overview \(synopsis\)](#) 8

P

[Parameters - security index](#) 27
[Preconditions](#) 9
[Prerequisites](#) 9
[Product behavior](#) 34
Protocol Details
 [overview](#) 13

R

[References](#) 7
 [informative](#) 8

[normative](#) 7
[Relationship to other protocols](#) 8
[Retrieving user profile service configuration state example](#) 25

<http://schemas.microsoft.com/2003/10/Serialization/Schema> 29
<http://schemas.microsoft.com/2003/10/Serialization/Arrays Schema> 32
<http://tempuri.org/Schema> 29

S

Security
[implementer considerations](#) 27
[parameter index](#) 27
Sequencing rules
[server](#) 14
Server
[abstract data model](#) 14
[GetProfileProperties operation](#) 14
[initialization](#) 14
[local events](#) 24
[message processing](#) 14
[overview](#) 13
[sequencing rules](#) 14
[timer events](#) 24
[timers](#) 14
[Server details](#) 13
[Simple types](#) 11
[char](#) 11
[duration](#) 11
[Standards assignments](#) 9
Syntax
[messages - overview](#) 10

T

Timer events
[server](#) 24
Timers
[server](#) 14
[Tracking changes](#) 35
[Transport](#) 10
Types
[complex](#) 11
[simple](#) 11

V

[Vendor-extensible fields](#) 9
[Versioning](#) 9

W

[WSDL](#) 28

X

XML Schema ([section 7](#) 29, [section 7](#) 29)
<http://Microsoft/Office/Server/UserProfiles Schema> 30
<http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Administration Schema> 33
<http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.Utilities Schema> 32
<http://schemas.datacontract.org/2004/07/Microsoft.SharePoint.Administration Schema> 32