

[MS-WMS]: Work Management Service Web Service Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
01/20/2012	0.1	New	Released new document.
04/11/2012	0.1	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	0.1	No change	No changes to the meaning, language, or formatting of the technical content.
09/12/2012	0.1	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	1.0	Major	Significantly changed the technical content.
02/11/2013	2.0	Major	Significantly changed the technical content.
07/30/2013	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
11/18/2013	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
02/10/2014	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
04/30/2014	2.0	No change	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1 Introduction	7
1.1 Glossary	7
1.2 References	7
1.2.1 Normative References	7
1.2.2 Informative References	8
1.3 Overview	8
1.4 Relationship to Other Protocols	8
1.5 Prerequisites/Preconditions	9
1.6 Applicability Statement	9
1.7 Versioning and Capability Negotiation	9
1.8 Vendor-Extensible Fields	9
1.9 Standards Assignments	9
2 Messages	10
2.1 Transport	10
2.2 Common Message Syntax	10
2.2.1 Namespaces	10
2.2.2 Messages	11
2.2.3 Elements	11
2.2.4 Complex Types	11
2.2.5 Simple Types	11
2.2.5.1 char	11
2.2.5.2 duration	11
2.2.5.3 guid	12
2.2.6 Attributes	12
2.2.7 Groups	12
2.2.8 Attribute Groups	12
2.2.9 Common Data Structures	12
3 Protocol Details	13
3.1 Server Details	13
3.1.1 Abstract Data Model	13
3.1.2 Timers	13
3.1.3 Initialization	13
3.1.4 Message Processing Events and Sequencing Rules	13
3.1.4.1 BeginCacheRefresh	14
3.1.4.1.1 Messages	14
3.1.4.1.1.1	
IWorkManagementServiceApplication_BeginCacheRefresh_InputMessage	15
3.1.4.1.1.2	
IWorkManagementServiceApplication_BeginCacheRefresh_OutputMessage	15
3.1.4.1.2 Elements	15
3.1.4.1.2.1 BeginCacheRefresh	15
3.1.4.1.2.2 BeginCacheRefreshResponse	15
3.1.4.1.3 Complex Types	16
3.1.4.1.3.1 CreateRefreshJobResult	16
3.1.4.1.4 Simple Types	16
3.1.4.1.5 Attributes	16

3.1.4.1.6	Groups.....	17
3.1.4.1.7	Attribute Groups	17
3.1.4.2	BeginExchangeSync	17
3.1.4.2.1	Messages	17
3.1.4.2.1.1	IWorkManagementServiceApplication_BeginExchangeSync_InputMessage	17
3.1.4.2.1.2	IWorkManagementServiceApplication_BeginExchangeSync_OutputMessage	18
3.1.4.2.2	Elements.....	18
3.1.4.2.2.1	BeginExchangeSync.....	18
3.1.4.2.2.2	BeginExchangeSyncResponse.....	18
3.1.4.2.3	Complex Types	18
3.1.4.2.4	Simple Types.....	18
3.1.4.2.5	Attributes.....	19
3.1.4.2.6	Groups.....	19
3.1.4.2.7	Attribute Groups	19
3.1.4.3	BeginCreateTaskPropagation	19
3.1.4.3.1	Messages	19
3.1.4.3.1.1	IWorkManagementServiceApplication_BeginCreateTaskPropagation_InputMessage.....	19
3.1.4.3.1.2	IWorkManagementServiceApplication_BeginCreateTaskPropagation_OutputMessage	20
3.1.4.3.2	Elements.....	20
3.1.4.3.2.1	BeginCreateTaskPropagation	20
3.1.4.3.2.2	BeginCreateTaskPropagationResponse	20
3.1.4.3.3	Complex Types	21
3.1.4.3.4	Simple Types.....	21
3.1.4.3.5	Attributes.....	21
3.1.4.3.6	Groups.....	21
3.1.4.3.7	Attribute Groups	21
3.1.4.4	BeginDeleteTaskPropagation	21
3.1.4.4.1	Messages	21
3.1.4.4.1.1	IWorkManagementServiceApplication_BeginDeleteTaskPropagation_InputMessage.....	22
3.1.4.4.1.2	IWorkManagementServiceApplication_BeginDeleteTaskPropagation_OutputMessage	22
3.1.4.4.2	Elements.....	22
3.1.4.4.2.1	BeginDeleteTaskPropagation	22
3.1.4.4.2.2	BeginDeleteTaskPropagationResponse.....	23
3.1.4.4.3	Complex Types	23
3.1.4.4.4	Simple Types.....	23
3.1.4.4.5	Attributes.....	23
3.1.4.4.6	Groups.....	23
3.1.4.4.7	Attribute Groups	23
3.1.4.5	BeginUpdateTaskPropagation	23
3.1.4.5.1	Messages	24

3.1.4.5.1.1	IWorkManagementServiceApplication_BeginUpdateTaskPropagation_	
	InputMessage	24
3.1.4.5.1.2	IWorkManagementServiceApplication_BeginUpdateTaskPropagation_	
	OutputMessage	24
3.1.4.5.2	Elements.....	24
3.1.4.5.2.1	BeginUpdateTaskPropagation	25
3.1.4.5.2.2	BeginUpdateTaskPropagationResponse.....	25
3.1.4.5.3	Complex Types	25
3.1.4.5.4	Simple Types.....	25
3.1.4.5.5	Attributes.....	25
3.1.4.5.6	Groups.....	25
3.1.4.5.7	Attribute Groups	25
3.1.4.6	GetExchangeSyncInfo	25
3.1.4.6.1	Messages	26
3.1.4.6.1.1	IWorkManagementServiceApplication_GetExchangeSyncInfo_InputM	
	essage	26
3.1.4.6.1.2	IWorkManagementServiceApplication_GetExchangeSyncInfo_Output	
	Message	26
3.1.4.6.2	Elements.....	26
3.1.4.6.2.1	GetExchangeSyncInfo	27
3.1.4.6.2.2	GetExchangeSyncInfoResponse	27
3.1.4.6.3	Complex Types	27
3.1.4.6.3.1	ExchangeUserSyncState	27
3.1.4.6.4	Simple Types.....	28
3.1.4.6.4.1	ExchangeSyncResult	28
3.1.4.6.5	Attributes.....	29
3.1.4.6.6	Groups.....	29
3.1.4.6.7	Attribute Groups	29
3.1.4.7	OptIntoExchangeSync	29
3.1.4.7.1	Messages	29
3.1.4.7.1.1	IWorkManagementServiceApplication_OptIntoExchangeSync_InputM	
	essage	30
3.1.4.7.1.2	IWorkManagementServiceApplication_OptIntoExchangeSync_Output	
	Message	30
3.1.4.7.2	Elements.....	30
3.1.4.7.2.1	OptIntoExchangeSync	30
3.1.4.7.2.2	OptIntoExchangeSyncResponse.....	30
3.1.4.7.3	Complex Types	31
3.1.4.7.4	Simple Types.....	31
3.1.4.7.4.1	ExchangeOptInResult	31
3.1.4.7.5	Attributes.....	32
3.1.4.7.6	Groups.....	32
3.1.4.7.7	Attribute Groups	32
3.1.4.8	OptOutOfExchangeSync.....	32
3.1.4.8.1	Messages	33

3.1.4.8.1.1	IWorkManagementServiceApplication_OptOutOfExchangeSync_Input Message	33
3.1.4.8.1.2	IWorkManagementServiceApplication_OptOutOfExchangeSync_Outp utMessage	33
3.1.4.8.2	Elements	33
3.1.4.8.2.1	OptOutOfExchangeSync	34
3.1.4.8.2.2	OptOutOfExchangeSyncResponse	34
3.1.4.8.3	Complex Types	34
3.1.4.8.4	Simple Types	34
3.1.4.8.5	Attributes	34
3.1.4.8.6	Groups	34
3.1.4.8.7	Attribute Groups	34
3.1.4.9	BeginRelocateTaskPropagation	34
3.1.4.9.1	Messages	35
3.1.4.9.1.1	IWorkManagementServiceApplication_BeginRelocateTaskPropagation _InputMessage	35
3.1.4.9.1.2	IWorkManagementServiceApplication_BeginRelocateTaskPropagation _OutputMessage	35
3.1.4.9.2	Elements	36
3.1.4.9.2.1	BeginRelocateTaskPropagation	36
3.1.4.9.2.2	BeginRelocateTaskPropagationResponse	36
3.1.4.9.3	Complex Types	36
3.1.4.9.4	Simple Types	36
3.1.4.9.5	Attributes	37
3.1.4.9.6	Groups	37
3.1.4.9.7	Attribute Groups	37
3.1.5	Timer Events	37
3.1.6	Other Local Events	37
4	Protocol Examples	38
5	Security	50
5.1	Security Considerations for Implementers	50
5.2	Index of Security Parameters	50
6	Appendix A: Full WSDL	51
7	Appendix B: Full XML Schema	56
7.1	http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement Schema	56
7.2	http://schemas.microsoft.com/2003/10/Serialization/ Schema	57
7.3	http://tempuri.org/ Schema	58
8	Appendix C: Product Behavior	61
9	Change Tracking	62
10	Index	63

1 Introduction

The Work Management Service Web Service Protocol provides a way for a protocol client to trigger task aggregation and synchronization operations for a user.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

SOAP action
SOAP body
SOAP fault
Unicode
XML namespace

The following terms are defined in [\[MS-OFCGLOS\]](#):

application server
back-end database server
personal site
task
Uniform Resource Locator (URL)
user profile
User Profile Service
Web Services Description Language (WSDL)
WSDL message
WSDL operation
XML namespace prefix
XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[MS-SPSTWS] Microsoft Corporation, "[SharePoint Security Token Service Web Service Protocol](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", May 2000, <http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP1.2/1] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>

[WSA1.0] World Wide Web Consortium, "Web Services Addressing 1.0 - WSDL Binding", W3C Candidate Recommendation, May 2006, <http://www.w3.org/TR/2006/CR-ws-addr-wsdl-20060529/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

[MS-USPSWS] Microsoft Corporation, "[User Profile Service Web Service Protocol](#)".

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <http://www.ietf.org/rfc/rfc2818.txt>

[SOAP1.2/2] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 2: Adjuncts", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part2-20030624>

1.3 Overview

This protocol allows protocol clients to refresh a user's **task (3)** information through a middle-tier **application server**. The protocol client sends a request for a user to the protocol server, and the server responds with an acknowledgement of the request and refreshes the task (3) information asynchronously.

1.4 Relationship to Other Protocols

This protocol uses the **SOAP** message protocol for formatting request and response messages, as described in [\[SOAP1.1\]](#), [\[SOAP1.2/1\]](#) and [\[SOAP1.2/2\]](#). It transmits those messages by using **HTTP**, as described in [\[RFC2616\]](#), or **HTTPS**, as described in [\[RFC2818\]](#).

The following diagram shows the underlying messaging and transport stack used by the protocol:




Figure 1: This protocol in relation to other protocols

This protocol also calls APIs that use the User Profile Service Web Service protocol described in [\[MS-USPSWS\]](#) to get the location of a **personal site** associated with a **user profile**.

1.5 Prerequisites/Preconditions

This protocol operates against a personal site that is identified by a **URL** that is known by a user profile service implementing the User Profile Service Web Service protocol, as defined by [\[MS-USPSWS\]](#). The protocol client needs sufficient privileges to access the site and its data stored on the **back-end database server** corresponding to the site.

This protocol assumes that authentication has been performed by the underlying protocols.

1.6 Applicability Statement

This protocol is designed to run operations on behalf of a single user per invocation and store results for that user in a storage location associated with that user's user profile.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

Protocol servers MUST support SOAP over HTTP, HTTPS, or TCP.

All protocol messages MUST be transported by using HTTP or TCP bindings at the transport level.

Protocol messages MUST be formatted as specified in either [\[SOAP1.1\]](#) section 4 or [\[SOAP1.2/1\]](#) section 5. Protocol server faults MUST be returned by using HTTP status codes, as specified in [\[RFC2616\]](#) section 10, or **SOAP faults**, as specified in [\[SOAP1.1\]](#) section 4.4 or [\[SOAP1.2/1\]](#) section 5.4.

If the HTTPS transport is used, a server certificate MUST be deployed.

This protocol SHOULD transmit an additional SOAP header, the **ServiceContext** header, as specified in [\[MS-SPSTWS\]](#).

This protocol does not define any means for activating a protocol server or protocol client. The protocol server MUST be configured and begin listening in an implementation-specific way. In addition, the protocol client MUST be capable of handling the format and transport that is used by the server, for example, the SOAP format over an HTTP transport.

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses the **XML schema** syntax in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and Web Services Description Language, as defined in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific **XML namespace prefix** for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
tns	http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement	
tns1	http://schemas.microsoft.com/2003/10/Serialization/	
tns2	http://tempuri.org/	
tns3	http://tempuri.org/Imports	
wsaw	http://www.w3.org/2006/05/addressing/wsdl	Web Service Addressing [WSA1.0]
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]

Prefix	Namespace URI	Reference
		1 [XMLSCHEMA2 1

2.2.2 Messages

This specification does not define any common **WSDL message** definitions.

2.2.3 Elements

This specification does not define any common XML schema element definitions.

2.2.4 Complex Types

This specification does not define any common XML schema complex type definitions.

2.2.5 Simple Types

The following table summarizes the set of common XML schema simple type definitions defined by this specification. XML schema simple type definitions that are specific to a particular operation are described with the operation.

Simple type	Description
char	A char simple type that represents a Unicode character. This type is not used by this protocol.
duration	A time interval with its period in days, hours, minutes, and seconds. This type is not used by this protocol.
guid	A unique identifier. This type is not used by this protocol.

2.2.5.1 char

Namespace: <http://schemas.microsoft.com/2003/10/Serialization/>

A **char** simple type that represents a Unicode character. This type is not used by this protocol.

```
<xs:simpleType name="char" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:int"/>
</xs:simpleType>
```

2.2.5.2 duration

Namespace: <http://schemas.microsoft.com/2003/10/Serialization/>

A time interval with its period in days, hours, minutes, and seconds. This type is not used by this protocol.

```
<xs:simpleType name="duration" xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```
<xs:restriction base="xs:duration">
  <xs:pattern value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?"/>
  <xs:minInclusive value="-P10675199DT2H48M5.4775808S"/>
  <xs:maxInclusive value="P10675199DT2H48M5.4775807S"/>
</xs:restriction>
</xs:simpleType>
```

2.2.5.3 guid

Namespace: <http://schemas.microsoft.com/2003/10/Serialization/>

A unique identifier. This type is not used by this protocol.

```
<xs:simpleType name="guid" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.6 Attributes

This specification does not define any common XML schema attribute definitions.

2.2.7 Groups

This specification does not define any common XML schema group definitions.

2.2.8 Attribute Groups

This specification does not define any common XML schema attribute group definitions.

2.2.9 Common Data Structures

None.

3 Protocol Details

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The WSDL in this specification matches the WSDL that shipped with the product and provides a base description of the schema. The text that introduces the WSDL might specify differences that reflect actual Microsoft product behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the protocol as specified restricts the same elements to being non-empty, present, and not null.

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

3.1 Server Details

This protocol is based on stateless interaction between the protocol client and protocol server. The protocol client **MUST** be authenticated with the credentials of the user that the service will aggregate and refresh tasks (3) for.

3.1.1 Abstract Data Model

This protocol allows a protocol client to call the application server tier to trigger a refresh of a user's task (3) cache. When called, the protocol server will aggregate tasks (3) from systems defined in its configuration and write them into a storage location, such as a list in the content back-end database server. The protocol server returns a result indicating whether a new aggregation job was created along with an id for the job if one exists.

This protocol also allows a protocol client to call the application server tier to trigger a synchronization of tasks (3) between an external location such as a mailbox and the back-end database server.

3.1.2 Timers

None.

3.1.3 Initialization

A User Profile Service Application implementing the User Profile Service Web Service protocol, as defined by [\[MS-USPSWS\]](#) **MUST** be available before this protocol can be used.

3.1.4 Message Processing Events and Sequencing Rules

The following table summarizes the list of operations as defined by this specification.

Operation	Description
BeginCacheRefresh	Triggers the server to create a job to aggregate tasks (3) on behalf of the calling user and writes results to a storage location.
BeginCreateTaskPropagation	Triggers the server to create a task (3) in the external synchronization server.
BeginDeleteTaskPropagation	Triggers the server to delete a task (3) in an external task (3) server.

Operation	Description
BeginExchangeSync	Starts a server synchronization for the current user.
BeginRelocateTaskPropagation	Triggers the server to move a task (3) in an external task (3) server to a target location on that server.
BeginUpdateTaskPropagation	Triggers the server to update a task (3) in an external task (3) server.
GetExchangeSyncInfo	Returns information about an external server synchronization for a user.
OptIntoExchangeSync	Triggers the server to turn on synchronization with a task (3) server for a user.
OptOutOfExchangeSync	Turns off task (3) synchronization with a task (3) server for a user.

3.1.4.1 BeginCacheRefresh

Triggers the server to create a job to aggregate tasks (3) on behalf of the calling user and writes results to a storage location.

The following is the **WSDL** port type specification of the **BeginCacheRefresh WSDL operation**.

```
<wsdl:operation name="BeginCacheRefresh" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginCacheRefresh"
    message="tns2:IWorkManagementServiceApplication_BeginCacheRefresh_InputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
  <wsdl:output
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginCacheRefreshResponse"
    message="tns2:IWorkManagementServiceApplication_BeginCacheRefresh_OutputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>
```

The method returns confirmation of whether an aggregation job was created.

3.1.4.1.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IWorkManagementServiceApplication_BeginCacheRefresh_InputMessage	The request WSDL message for the BeginCacheRefresh WSDL operation.
IWorkManagementServiceApplication_BeginCacheRefresh_OutputMessage	The response WSDL message for the BeginCacheRefresh WSDL operation.

3.1.4.1.1.1

IWorkManagementServiceApplication_BeginCacheRefresh_InputMessage

The request WSDL message for the **BeginCacheRefresh** WSDL operation.

The **SOAP action** value is:

```
http://tempuri.org/IWorkManagementServiceApplication/BeginCacheRefresh
```

The **SOAP body** contains the **BeginCacheRefresh** element.

3.1.4.1.1.2

IWorkManagementServiceApplication_BeginCacheRefresh_OutputMessage

The response WSDL message for the **BeginCacheRefresh** WSDL operation.

The SOAP body contains the **BeginCacheRefreshResponse** element.

3.1.4.1.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
BeginCacheRefresh	The input data for the BeginCacheRefresh WSDL operation.
BeginCacheRefreshResponse	The result data for the BeginCacheRefresh WSDL operation.

3.1.4.1.2.1 BeginCacheRefresh

The **BeginCacheRefresh** element specifies the input data for the **BeginCacheRefresh** WSDL operation.

```
<xs:element name="BeginCacheRefresh" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence/>  
  </xs:complexType>  
</xs:element>
```

3.1.4.1.2.2 BeginCacheRefreshResponse

The **BeginCacheRefreshResponse** element specifies the result data for the **BeginCacheRefresh** WSDL operation.

```
<xs:element name="BeginCacheRefreshResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element  
        xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"  
        minOccurs="0" name="BeginCacheRefreshResult" nillable="true"  
        type="tns:CreateRefreshJobResult"/>  
    </xs:sequence>  
  </xs:complexType>
```

</xs:element>

BeginCacheRefreshResult: Returns the CreateRefreshJobResult that indicates the result of the aggregation refresh request.

3.1.4.1.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
CreateRefreshJobResult	Information about the task (3) aggregation job that was created as a result of the refresh request.

3.1.4.1.3.1 CreateRefreshJobResult

Namespace: http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement

Information resulting from a request to create an aggregation refresh job.

```
<xs:complexType name="CreateRefreshJobResult" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" name="CreatedJob" type="xs:boolean"/>
    <xs:element minOccurs="0" name="CurrentJobId" nillable="true" type="xs:int"/>
    <xs:element minOccurs="0" name="CurrentJobIdClient" type="xs:int"/>
    <xs:element minOccurs="0" name="EncounteredError" type="xs:boolean"/>
  </xs:sequence>
</xs:complexType>
```

CreatedJob: The result of creating a new refresh job, which MUST return true if the job was successfully created and false if the job was not. A job will not be created if there is already a job running for that user or an error occurs while creating the job.

CurrentJobId: The integer identifier of the job that is currently running on behalf of the user. This MAY be the job created as a result of the request, or a job that is still in progress. MUST return NULL if creation of the job failed.

CurrentJobIdClient: Same as **CurrentJobId**, except that it MUST return **WmaClientConstants.NoValue** if the creation of the job failed instead of NULL.

EncounteredError: MUST return true if there was an error while creating the job and false otherwise.

3.1.4.1.4 Simple Types

None.

3.1.4.1.5 Attributes

None.

3.1.4.1.6 Groups

None.

3.1.4.1.7 Attribute Groups

None.

3.1.4.2 BeginExchangeSync

Starts a server synchronization for the current user.

The following is the WSDL port type specification of the **BeginExchangeSync** WSDL operation.

```
<wsdl:operation name="BeginExchangeSync" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginExchangeSync"
    message="tns2:IWorkManagementServiceApplication_BeginExchangeSync_InputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
  <wsdl:output
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginExchangeSyncResponse"
    message="tns2:IWorkManagementServiceApplication_BeginExchangeSync_OutputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>
```

This operation returns whether the synchronization process successfully started.

3.1.4.2.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IWorkManagementServiceApplication_BeginExchangeSync_InputMessage	The request WSDL message for the BeginExchangeSync WSDL operation.
IWorkManagementServiceApplication_BeginExchangeSync_OutputMessage	The response WSDL message for the BeginExchangeSync WSDL operation.

3.1.4.2.1.1

IWorkManagementServiceApplication_BeginExchangeSync_InputMessage

The request WSDL message for the **BeginExchangeSync** WSDL operation.

The SOAP action value is:

```
http://tempuri.org/IWorkManagementServiceApplication/BeginExchangeSync
```

The SOAP body contains the **BeginExchangeSync** element.

3.1.4.2.1.2

IWorkManagementServiceApplication_BeginExchangeSync_OutputMessage

The response WSDL message for the **BeginExchangeSync** WSDL operation.

The SOAP body contains the **BeginExchangeSyncResponse** element.

3.1.4.2.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
BeginExchangeSync	The input data for the BeginExchangeSync WSDL operation.
BeginExchangeSyncResponse	The result data for the BeginExchangeSync WSDL operation.

3.1.4.2.2.1 BeginExchangeSync

The **BeginExchangeSync** element specifies the input data for the **BeginExchangeSync** WSDL operation.

```
<xs:element name="BeginExchangeSync" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence/>
  </xs:complexType>
</xs:element>
```

3.1.4.2.2.2 BeginExchangeSyncResponse

The **BeginExchangeSyncResponse** element specifies the result data for the **BeginExchangeSync** WSDL operation.

```
<xs:element name="BeginExchangeSyncResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="BeginExchangeSyncResult" type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

BeginExchangeSyncResult: MUST return true if the synchronization job successfully started and false if not.

3.1.4.2.3 Complex Types

None.

3.1.4.2.4 Simple Types

None.

3.1.4.2.5 Attributes

None.

3.1.4.2.6 Groups

None.

3.1.4.2.7 Attribute Groups

None.

3.1.4.3 BeginCreateTaskPropagation

Triggers the server to create a task (3) in the external synchronization server.

The following is the WSDL port type specification of the **BeginCreateTaskPropagation** WSDL operation.

```
<wsdl:operation name="BeginCreateTaskPropagation"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginCreateTaskPropagation"
    message="tns2:IWorkManagementServiceApplication_BeginCreateTaskPropagation_InputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
  <wsdl:output
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginCreateTaskPropagationResponse"
    message="tns2:IWorkManagementServiceApplication_BeginCreateTaskPropagation_OutputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>
```

The method returns acknowledgement that the request was received and will be processed.

3.1.4.3.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IWorkManagementServiceApplication_BeginCreateTaskPropagation_InputMessage	The request WSDL message for the BeginCreateTaskPropagation WSDL operation.
IWorkManagementServiceApplication_BeginCreateTaskPropagation_OutputMessage	The response WSDL message for the BeginCreateTaskPropagation WSDL operation.

3.1.4.3.1.1

IWorkManagementServiceApplication_BeginCreateTaskPropagation_InputMessage

The request WSDL message for the **BeginCreateTaskPropagation** WSDL operation.

The SOAP action value is:

```
http://tempuri.org/IWorkManagementServiceApplication/BeginCreateTaskPropagation
```

The SOAP body contains the **BeginCreateTaskPropagation** element.

3.1.4.3.1.2

IWorkManagementServiceApplication_BeginCreateTaskPropagation_OutputMessage

The response WSDL message for the **BeginCreateTaskPropagation** WSDL operation.

The SOAP body contains the **BeginCreateTaskPropagationResponse** element.

3.1.4.3.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
BeginCreateTaskPropagation	The input data for the BeginCreateTaskPropagation WSDL operation.
BeginCreateTaskPropagationResponse	The result data for the BeginCreateTaskPropagation WSDL operation.

3.1.4.3.2.1 BeginCreateTaskPropagation

The **BeginCreateTaskPropagation** element specifies the input data for the **BeginCreateTaskPropagation** WSDL operation.

```
<xs:element name="BeginCreateTaskPropagation" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element minOccurs="0" name="taskId" type="xs:int"/>  
    </xs:sequence>  
  </xs:complexType>  
</xs:element>
```

taskId: The integer identifier of the task (3) to be created.

3.1.4.3.2.2 BeginCreateTaskPropagationResponse

The **BeginCreateTaskPropagationResponse** element specifies the result data for the **BeginCreateTaskPropagation** WSDL operation.

```
<xs:element name="BeginCreateTaskPropagationResponse"  
  xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence/>  
  </xs:complexType>  
</xs:element>
```

3.1.4.3.3 Complex Types

None.

3.1.4.3.4 Simple Types

None.

3.1.4.3.5 Attributes

None.

3.1.4.3.6 Groups

None.

3.1.4.3.7 Attribute Groups

None.

3.1.4.4 BeginDeleteTaskPropagation

Triggers the server to delete a task (3) in an external task (3) server.

The following is the WSDL port type specification of the **BeginDeleteTaskPropagation** WSDL operation.

```
<wsdl:operation name="BeginDeleteTaskPropagation"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginDeleteTaskPropagation"
message="tns2:IWorkManagementServiceApplication_BeginDeleteTaskPropagation_InputMessage"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
  <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginDeleteTaskPropagationR
esponse"
message="tns2:IWorkManagementServiceApplication_BeginDeleteTaskPropagation_OutputMessage"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>
```

The method returns acknowledgement that the request was received and will be processed.

3.1.4.4.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IWorkManagementServiceApplication_BeginDeleteTaskPropagation_InputMessage	The request WSDL message for the BeginDeleteTaskPropagation WSDL operation.
IWorkManagementServiceApplication_BeginDeleteTaskPropagation_OutputMessage	The response WSDL message for the

Message	Description
	BeginDeleteTaskPropagation WSDL operation.

3.1.4.4.1.1

IWorkManagementServiceApplication_BeginDeleteTaskPropagation_InputMessage

The request WSDL message for the **BeginDeleteTaskPropagation** WSDL operation.

The SOAP action value is:

```
http://tempuri.org/IWorkManagementServiceApplication/BeginDeleteTaskPropagation
```

The SOAP body contains the **BeginDeleteTaskPropagation** element.

3.1.4.4.1.2

IWorkManagementServiceApplication_BeginDeleteTaskPropagation_OutputMessage

The response WSDL message for the **BeginDeleteTaskPropagation** WSDL operation.

The SOAP body contains the **BeginDeleteTaskPropagationResponse** element.

3.1.4.4.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
BeginDeleteTaskPropagation	The input data for the BeginDeleteTaskPropagation WSDL operation.
BeginDeleteTaskPropagationResponse	The result data for the BeginDeleteTaskPropagation WSDL operation.

3.1.4.4.2.1 BeginDeleteTaskPropagation

The **BeginDeleteTaskPropagation** element specifies the input data for the **BeginDeleteTaskPropagation** WSDL operation.

```
<xs:element name="BeginDeleteTaskPropagation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="taskId" type="xs:int"/>
      <xs:element minOccurs="0" name="mappedKey" nillable="true" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

taskId: The integer identifier of the task (3) to be deleted.

mappedKey: The unique identifier of the target location in the external server to delete the task (3) from.

3.1.4.4.2 BeginDeleteTaskPropagationResponse

The **BeginDeleteTaskPropagationResponse** element specifies the result data for the **BeginDeleteTaskPropagation** WSDL operation.

```
<xs:element name="BeginDeleteTaskPropagationResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence/>
  </xs:complexType>
</xs:element>
```

3.1.4.4.3 Complex Types

None.

3.1.4.4.4 Simple Types

None.

3.1.4.4.5 Attributes

None.

3.1.4.4.6 Groups

None.

3.1.4.4.7 Attribute Groups

None.

3.1.4.5 BeginUpdateTaskPropagation

Triggers the server to update a task (3) in an external task (3) server.

The following is the WSDL port type specification of the **BeginUpdateTaskPropagation** WSDL operation.

```
<wsdl:operation name="BeginUpdateTaskPropagation"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginUpdateTaskPropagation"
    message="tns2:IWorkManagementServiceApplication_BeginUpdateTaskPropagation_InputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
  <wsdl:output
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginUpdateTaskPropagationR
    esponse"
    message="tns2:IWorkManagementServiceApplication_BeginUpdateTaskPropagation_OutputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>
```

The method returns acknowledgement that the request was received and will be processed.

3.1.4.5.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IWorkManagementServiceApplication_BeginUpdateTaskPropagation_InputMessage	The request WSDL message for the BeginUpdateTaskPropagation WSDL operation.
IWorkManagementServiceApplication_BeginUpdateTaskPropagation_OutputMessage	The response WSDL message for the BeginUpdateTaskPropagation WSDL operation.

3.1.4.5.1.1

IWorkManagementServiceApplication_BeginUpdateTaskPropagation_InputMessage

The request WSDL message for the **BeginUpdateTaskPropagation** WSDL operation.

The SOAP action value is:

`http://tempuri.org/IWorkManagementServiceApplication/BeginUpdateTaskPropagation`

The SOAP body contains the **BeginUpdateTaskPropagation** element.

3.1.4.5.1.2

IWorkManagementServiceApplication_BeginUpdateTaskPropagation_OutputMessage

The response WSDL message for the **BeginUpdateTaskPropagation** WSDL operation.

The SOAP body contains the **BeginUpdateTaskPropagationResponse** element.

3.1.4.5.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
BeginUpdateTaskPropagation	The input data for the BeginUpdateTaskPropagation WSDL operation.
BeginUpdateTaskPropagationResponse	The result data for the BeginUpdateTaskPropagation WSDL operation.

3.1.4.5.2.1 BeginUpdateTaskPropagation

The **BeginUpdateTaskPropagation** element specifies the input data for the **BeginUpdateTaskPropagation** WSDL operation.

```
<xs:element name="BeginUpdateTaskPropagation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="taskId" type="xs:int"/>
      <xs:element minOccurs="0" name="lastModified" type="xs:dateTime"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

taskId: The integer identifier of the task (3) that needs to be updated.

lastModified: The datetime when the task (3) that needs to be updated was last updated.

3.1.4.5.2.2 BeginUpdateTaskPropagationResponse

The **BeginUpdateTaskPropagationResponse** element specifies the result data for the **BeginUpdateTaskPropagation** WSDL operation.

```
<xs:element name="BeginUpdateTaskPropagationResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence/>
  </xs:complexType>
</xs:element>
```

3.1.4.5.3 Complex Types

None.

3.1.4.5.4 Simple Types

None.

3.1.4.5.5 Attributes

None.

3.1.4.5.6 Groups

None.

3.1.4.5.7 Attribute Groups

None.

3.1.4.6 GetExchangeSyncInfo

Returns information about an external server synchronization for a user.

The following is the WSDL port type specification of the **GetExchangeSyncInfo** WSDL operation.

```
<wsdl:operation name="GetExchangeSyncInfo" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/GetExchangeSyncInfo"
    message="tns2:IWorkManagementServiceApplication_GetExchangeSyncInfo_InputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
  <wsdl:output
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/GetExchangeSyncInfoResponse"
    message="tns2:IWorkManagementServiceApplication_GetExchangeSyncInfo_OutputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>
```

Returns the ExchangeSyncInfoResult that indicates the user's external server synchronization status.

3.1.4.6.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IWorkManagementServiceApplication_GetExchangeSyncInfo_InputMessage	The request WSDL message for the GetExchangeSyncInfo WSDL operation.
IWorkManagementServiceApplication_GetExchangeSyncInfo_OutputMessage	The response WSDL message for the GetExchangeSyncInfo WSDL operation.

3.1.4.6.1.1

IWorkManagementServiceApplication_GetExchangeSyncInfo_InputMessage

The request WSDL message for the **GetExchangeSyncInfo** WSDL operation.

The SOAP action value is:

```
http://tempuri.org/IWorkManagementServiceApplication/GetExchangeSyncInfo
```

The SOAP body contains the **GetExchangeSyncInfo** element.

3.1.4.6.1.2

IWorkManagementServiceApplication_GetExchangeSyncInfo_OutputMessage

The response WSDL message for the **GetExchangeSyncInfo** WSDL operation.

The SOAP body contains the **GetExchangeSyncInfoResponse** element.

3.1.4.6.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
GetExchangeSyncInfo	The input data for the GetExchangeSyncInfo WSDL operation.
GetExchangeSyncInfoResponse	The result data for the GetExchangeSyncInfo WSDL operation.

3.1.4.6.2.1 GetExchangeSyncInfo

The **GetExchangeSyncInfo** element specifies the input data for the **GetExchangeSyncInfo** WSDL operation.

```
<xs:element name="GetExchangeSyncInfo" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence/>
  </xs:complexType>
</xs:element>
```

3.1.4.6.2.2 GetExchangeSyncInfoResponse

The **GetExchangeSyncInfoResponse** element specifies the result data for the **GetExchangeSyncInfo** WSDL operation.

```
<xs:element name="GetExchangeSyncInfoResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element
        xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"
        minOccurs="0" name="GetExchangeSyncInfoResult" nillable="true"
        type="tns:ExchangeUserSyncState"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

GetExchangeSyncInfoResult: The ExchangeSyncInfoResult that indicates the user's external server synchronization status.

3.1.4.6.3 Complex Types

The following table summarizes the XML schema complex type definitions that are specific to this operation.

Complex type	Description
ExchangeUserSyncState	Information about the external server synchronization status for a user.

3.1.4.6.3.1 ExchangeUserSyncState

Namespace: <http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement>

Represents status for external task (3) server synchronization operations for a user, including whether or not the user is set up to synchronize with the server, the time that the last synchronization completed, and results of the last synchronization.

```

<xs:complexType name="ExchangeUserSyncState" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" name="IsOptedIn" type="xs:boolean"/>
    <xs:element minOccurs="0" name="LastEndTime" nillable="true" type="xs:dateTime"/>
    <xs:element minOccurs="0" name="LastSyncResult" type="tns:ExchangeSyncResult"/>
  </xs:sequence>
</xs:complexType>

```

IsOptedIn: Specifies whether synchronization is enabled for a user or not. MUST be true if tasks (3) for the user will be synchronized and false otherwise.

LastEndTime: When the last synchronization operation completed

LastSyncResult: The outcome of the last synchronization operation for the user

3.1.4.6.4 Simple Types

The following table summarizes the XML schema simple type definitions that are specific to this operation.

Simple type	Description
ExchangeSyncResult	Information about a task (3) server synchronization operation.

3.1.4.6.4.1 ExchangeSyncResult

Namespace: http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement

Results about a task (3) server synchronization operation.

```

<xs:simpleType name="ExchangeSyncResult" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NoValue"/>
    <xs:enumeration value="Success"/>
    <xs:enumeration value="UnknownError"/>
    <xs:enumeration value="CouldNotConnectToExchange"/>
    <xs:enumeration value="CouldNotGetUserCredentials"/>
    <xs:enumeration value="CouldNotKickoffJob"/>
    <xs:enumeration value="SyncWithErrors"/>
  </xs:restriction>
</xs:simpleType>

```

The following table specifies the allowable values for the **ExchangeSyncResult** simple type.

Value	Meaning
NoValue	No value.
Success	The operation succeeded.
UnknownError	There was an unknown error during the synchronization.
CouldNotConnectToExchange	The operation could not connect with the external task (3) server.
CouldNotGetUserCredentials	The operation could not get credentials for the user it was trying to

Value	Meaning
	synchronize.
CouldNotKickoffJob	The synchronization operation could not be started.
SyncWithErrors	The synchronization finished but with errors.

3.1.4.6.5 Attributes

None.

3.1.4.6.6 Groups

None.

3.1.4.6.7 Attribute Groups

None.

3.1.4.7 OptIntoExchangeSync

Triggers the server to turn on synchronization with a task (3) server for a user.

The following is the WSDL port type specification of the **OptIntoExchangeSync** WSDL operation.

```
<wsdl:operation name="OptIntoExchangeSync" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/OptIntoExchangeSync"
    message="tns2:IWorkManagementServiceApplication_OptIntoExchangeSync_InputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
  <wsdl:output
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/OptIntoExchangeSyncResponse"
    message="tns2:IWorkManagementServiceApplication_OptIntoExchangeSync_OutputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>
```

Returns the **OptIntoExchangeSyncResult** that indicates the result of the operation to turn on synchronization.

3.1.4.7.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IWorkManagementServiceApplication_OptIntoExchangeSync_InputMessage	The request WSDL message for the OptIntoExchangeSync WSDL operation.
IWorkManagementServiceApplication_OptIntoExchangeSync_OutputMessage	The response WSDL message for the OptIntoExchangeSync WSDL operation.

3.1.4.7.1.1

IWorkManagementServiceApplication_OptIntoExchangeSync_InputMessage

The request WSDL message for the **OptIntoExchangeSync** WSDL operation.

The SOAP action value is:

```
http://tempuri.org/IWorkManagementServiceApplication/OptIntoExchangeSync
```

The SOAP body contains the **OptIntoExchangeSync** element.

3.1.4.7.1.2

IWorkManagementServiceApplication_OptIntoExchangeSync_OutputMessage

The response WSDL message for the **OptIntoExchangeSync** WSDL operation.

The SOAP body contains the **OptIntoExchangeSyncResponse** element.

3.1.4.7.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
OptIntoExchangeSync	The input data for the OptIntoExchangeSync WSDL operation.
OptIntoExchangeSyncResponse	The result data for the OptIntoExchangeSync WSDL operation.

3.1.4.7.2.1 OptIntoExchangeSync

The **OptIntoExchangeSync** element specifies the input data for the **OptIntoExchangeSync** WSDL operation.

```
<xs:element name="OptIntoExchangeSync" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence/>  
  </xs:complexType>  
</xs:element>
```

3.1.4.7.2.2 OptIntoExchangeSyncResponse

The **OptIntoExchangeSyncResponse** element specifies the result data for the **OptIntoExchangeSync** WSDL operation.

```
<xs:element name="OptIntoExchangeSyncResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">  
  <xs:complexType>  
    <xs:sequence>  
      <xs:element  
        xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"  
        minOccurs="0" name="OptIntoExchangeSyncResult" type="tns:ExchangeOptInResult"/>  
    </xs:sequence>  
  </xs:complexType>
```

</xs:element>

OptIntoExchangeSyncResult: The ExchangeOptInResult that indicates the result of the operation to turn on synchronization.

3.1.4.7.3 Complex Types

None.

3.1.4.7.4 Simple Types

The following table summarizes the XML schema simple type definitions that are specific to this operation.

Simple type	Description
ExchangeOptInResult	Information about whether or not the user was successfully set up to synchronize tasks (3).

3.1.4.7.4.1 ExchangeOptInResult

Namespace: http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement

Information about whether or not the user was successfully set up to synchronize tasks (3).

```
<xs:simpleType name="ExchangeOptInResult" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NoValue"/>
    <xs:enumeration value="Success"/>
    <xs:enumeration value="UnknownError"/>
    <xs:enumeration value="CouldNotConnectToExchange"/>
    <xs:enumeration value="CouldNotFindOrCreateMySite"/>
    <xs:enumeration value="UserAlreadyOptedIn"/>
    <xs:enumeration value="UserExchangeOperationPending"/>
    <xs:enumeration value="UnsupportedExchangeVersion"/>
    <xs:enumeration value="MissingEmailAddress"/>
    <xs:enumeration value="ExchangeWebServiceClientMissing"/>
    <xs:enumeration value="UnsupportedSharePointConfiguration"/>
    <xs:enumeration value="InvalidOrUnauthorizedUser"/>
    <xs:enumeration value="CouldNotActivateExchangeSyncFeatureOnSiteSubscription"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **ExchangeOptInResult** simple type.

Value	Meaning
NoValue	No value.
Success	The operation succeeded.
UnknownError	There was an unknown error when enabling synchronization.

Value	Meaning
CouldNotConnectToExchange	The operation could not connect with the external task (3) server.
CouldNotFindOrCreateMySite	The synchronization operation could not find or create the user's personal site (2) in which to store synchronization data.
UserAlreadyOptedIn	The user was already set up to synchronize tasks (3).
UserExchangeOperationPending	The operation to enable synchronization is already in process.
UnsupportedExchangeVersion	The task (3) server is not compatible with the synchronization operation.
MissingEmailAddress	The user's email address could not be found in the User Profile Service .
ExchangeWebServiceClientMissing	The component required to connect to the external task (3) server is not available.
UnsupportedSharePointConfiguration	The local server is not configured correctly for synchronization with an external task (3) server.
InvalidOrUnauthorizedUser	The user specified is not valid or unauthorized on the external task (3) server.
CouldNotActivateExchangeSyncFeatureOnSiteSubscription	The synchronization operation could not be activated on the local server.

3.1.4.7.5 Attributes

None.

3.1.4.7.6 Groups

None.

3.1.4.7.7 Attribute Groups

None.

3.1.4.8 OptOutOfExchangeSync

Turns off task (3) synchronization with a task (3) server for a user.

The following is the WSDL port type specification of the **OptOutOfExchangeSync** WSDL operation.

```
<wsdl:operation name="OptOutOfExchangeSync" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input
    wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/OptOutOfExchangeSync"
    message="tns2:IWorkManagementServiceApplication_OptOutOfExchangeSync_InputMessage"
    xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
```

```

<wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/OptOutOfExchangeSyncResponse"
message="tns2:IWorkManagementServiceApplication_OptOutOfExchangeSync_OutputMessage"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>

```

Returns true if the operation to turn off synchronization was successful and false otherwise.

3.1.4.8.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IWorkManagementServiceApplication_OptOutOfExchangeSync_InputMessage	The request WSDL message for the OptOutOfExchangeSync WSDL operation.
IWorkManagementServiceApplication_OptOutOfExchangeSync_OutputMessage	The response WSDL message for the OptOutOfExchangeSync WSDL operation.

3.1.4.8.1.1

IWorkManagementServiceApplication_OptOutOfExchangeSync_InputMessage

The request WSDL message for the **OptOutOfExchangeSync** WSDL operation.

The SOAP action value is:

```
http://tempuri.org/IWorkManagementServiceApplication/OptOutOfExchangeSync
```

The SOAP body contains the **OptOutOfExchangeSync** element.

3.1.4.8.1.2

IWorkManagementServiceApplication_OptOutOfExchangeSync_OutputMessage

The response WSDL message for the **OptOutOfExchangeSync** WSDL operation.

The SOAP body contains the **OptOutOfExchangeSyncResponse** element.

3.1.4.8.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
OptOutOfExchangeSync	The input data for the OptOutOfExchangeSync WSDL operation.
OptOutOfExchangeSyncResponse	The result data for the OptOutOfExchangeSync WSDL operation.

3.1.4.8.2.1 OptOutOfExchangeSync

The **OptOutOfExchangeSync** element specifies the input data for the **OptOutOfExchangeSync** WSDL operation.

```
<xs:element name="OptOutOfExchangeSync" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence/>
  </xs:complexType>
</xs:element>
```

3.1.4.8.2.2 OptOutOfExchangeSyncResponse

The **OptOutOfExchangeSyncResponse** element specifies the result data for the **OptOutOfExchangeSync** WSDL operation.

```
<xs:element name="OptOutOfExchangeSyncResponse" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="OptOutOfExchangeSyncResult" type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

OptOutOfExchangeSyncResult: The result of the operation to turn off synchronization.. MUST return true if successful and false otherwise.

3.1.4.8.3 Complex Types

None.

3.1.4.8.4 Simple Types

None.

3.1.4.8.5 Attributes

None.

3.1.4.8.6 Groups

None.

3.1.4.8.7 Attribute Groups

None.

3.1.4.9 BeginRelocateTaskPropagation

Triggers the server to move a task (3) in an external task (3) server to a target location on that server.

The following is the WSDL port type specification of the **BeginRelocateTaskPropagation** WSDL operation.

```

<wsdl:operation name="BeginRelocateTaskPropagation"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginRelocateTaskPropagation"
message="tns2:IWorkManagementServiceApplication_BeginRelocateTaskPropagation_InputMessage"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
  <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginRelocateTaskPropagationResponse"
message="tns2:IWorkManagementServiceApplication_BeginRelocateTaskPropagation_OutputMessage"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"/>
</wsdl:operation>

```

The method returns confirmation that the request was received and will be processed.

3.1.4.9.1 Messages

The following table summarizes the set of WSDL message definitions that are specific to this operation.

Message	Description
IWorkManagementServiceApplication_BeginRelocateTaskPropagation_InputMessage	The request WSDL message for the BeginRelocateTaskPropagation WSDL operation.
IWorkManagementServiceApplication_BeginRelocateTaskPropagation_OutputMessage	The response WSDL message for the BeginRelocateTaskPropagation WSDL operation.

3.1.4.9.1.1

IWorkManagementServiceApplication_BeginRelocateTaskPropagation_InputMessage

The request WSDL message for the **BeginRelocateTaskPropagation** WSDL operation.

The SOAP action value is:

```
http://tempuri.org/IWorkManagementServiceApplication/BeginRelocateTaskPropagation
```

The SOAP body contains the **BeginRelocateTaskPropagation** element.

3.1.4.9.1.2

IWorkManagementServiceApplication_BeginRelocateTaskPropagation_OutputMessage

The response WSDL message for the **BeginRelocateTaskPropagation** WSDL operation.

The SOAP body contains the **BeginRelocateTaskPropagationResponse** element.

3.1.4.9.2 Elements

The following table summarizes the XML schema element definitions that are specific to this operation.

Element	Description
BeginRelocateTaskPropagation	The input data for the BeginRelocateTaskPropagation WSDL operation.
BeginRelocateTaskPropagationResponse	The result data for the BeginRelocateTaskPropagation WSDL operation.

3.1.4.9.2.1 BeginRelocateTaskPropagation

The **BeginRelocateTaskPropagation** element specifies the input data for the **BeginRelocateTaskPropagation** WSDL operation.

```
<xs:element name="BeginRelocateTaskPropagation" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence>
      <xs:element minOccurs="0" name="taskId" type="xs:int"/>
      <xs:element minOccurs="0" name="mappedKey" nillable="true" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

taskId: The integer identifier of the task (3) to be moved.

mappedKey: The unique identifier of the target location in the external server to move the task (3) to.

3.1.4.9.2.2 BeginRelocateTaskPropagationResponse

The **BeginRelocateTaskPropagationResponse** element specifies the result data for the **BeginRelocateTaskPropagation** WSDL operation.

```
<xs:element name="BeginRelocateTaskPropagationResponse"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType>
    <xs:sequence/>
  </xs:complexType>
</xs:element>
```

3.1.4.9.3 Complex Types

None.

3.1.4.9.4 Simple Types

None.

3.1.4.9.5 Attributes

None.

3.1.4.9.6 Groups

None.

3.1.4.9.7 Attribute Groups

None.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None

4 Protocol Examples

In this scenario, the protocol client calls **BeginCacheRefresh** to request a task (3) aggregation job on behalf of a user:

```
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope"
xmlns:a="http://www.w3.org/2005/08/addressing" xmlns:u="Security">
  <s:Header>
    <a:Action
s:mustUnderstand="1">http://tempuri.org/IWorkManagementServiceApplication/BeginCacheRefresh</
a:Action>
    <a:MessageID>urn:uuid:d9b6e13c-d6e6-46e1-a4e8-8e88006d273e</a:MessageID>
    <a:SequenceAcknowledgement>
      <a:ReplyTo>http://www.w3.org/2005/08/addressing/anonymous</a:ReplyTo>
    </a:SequenceAcknowledgement>
    <ServiceContext xmlns="http://schemas.microsoft.com/sharepoint/servicecontext"
xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
      <correlationId>666b6e9b-7569-3030-1abf-a25007b984f2</correlationId>
      <devdashboardIsEnabled>>false</devdashboardIsEnabled>
      <language>en-US</language>
      <region>en-US</region>
      <scopeId>99445843689490</scopeId>
      <siteSubscriptionId>00000000-0000-0000-0000-000000000000</siteSubscriptionId>
      <ulstraceOverrideLevel>10</ulstraceOverrideLevel>
    </ServiceContext>
    <a:To s:mustUnderstand="1"
u:Id="_1">http://serverurl:32843/44058d0990524belb0f66a890da50007/WorkManagementService.svc</
a:To>
    <o:Timestamp s:mustUnderstand="1" xmlns:o="http://www.w3.org/2001/04/xmlenc#">
      <u:Created u:Id="_0">
        <u:Expires>2011-11-24T07:45:46.175Z</u:Expires>
        <u:Length>2011-11-24T07:50:46.175Z</u:Length>
      </u:Created>
      <saml:Assertion MajorVersion="1" MinorVersion="1" AssertionID="_9b6296d4-3f78-4887-8a99-
73355d77ed4b" Issuer="SharePoint" IssueInstant="2011-11-24T07:21:27.120Z"
xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion">
        <saml:Conditions NotBefore="2011-11-24T07:21:27.089Z" NotOnOrAfter="2011-11-
24T17:21:27.089Z">
          <saml:AudienceRestrictionCondition>
            <saml:Audience>urn:schemas-microsoft-com:sharepoint:service</saml:Audience>
          </saml:AudienceRestrictionCondition>
        </saml:Conditions>
        <saml:AttributeStatement>
          <saml:Subject>
            <saml:NameIdentifier>username</saml:NameIdentifier>
            <saml:SubjectConfirmation>
              <saml:ConfirmationMethod>urn:oasis:names:tc:SAML:1.0:cm:holder-of-
key</saml:ConfirmationMethod>
              <KeyInfo xmlns="http://www.w3.org/2000/09/xmldsig#">
                <KeyValue>
                  <RSAKeyValue>
                    <Modulus>xTLtoGopRTYng4kkTo+AGsU9AYYqsoJ3TsiUdALBVW9C7hNQBgx0loCVV2H23ckHi1970VEyOmYAIIVxtMFL
jQb9TtDckncZDrN8CuL/Pc5LIKhh9zuFIjdbJiLqnYQBAYxHyLphEcW6MSRaTX62EoGk/pxPzZAhUocVOzvk7aU=</Mod
ulus>
                  <Exponent>AQAB</Exponent>
                </RSAKeyValue>
              </KeyValue>
            </KeyInfo>
          </saml:Subject>
        </saml:AttributeStatement>
      </saml:Assertion>
    </o:Timestamp>
  </s:Header>
  <s:Body>
  </s:Body>
</s:Envelope>
```

```

    </saml:SubjectConfirmation>
  </saml:Subject>
  <saml:Attribute AttributeName="primarysid"
AttributeNamespace="http://schemas.microsoft.com/ws/2008/06/identity/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>S-1-5-21-2127521184-1604012920-1887927527-
526964</saml:AttributeValue>
</saml:Attribute>
  <saml:Attribute AttributeName="primarygroupsid"
AttributeNamespace="http://schemas.microsoft.com/ws/2008/06/identity/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>S-1-5-21-2127521184-1604012920-1887927527-
513</saml:AttributeValue>
</saml:Attribute>
  <saml:Attribute AttributeName="upn"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>username@contoso.com</saml:AttributeValue>
</saml:Attribute>
  <saml:Attribute AttributeName="userlogonname"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>Username</saml:AttributeValue>
</saml:Attribute>
  <saml:Attribute AttributeName="userid"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="SecurityTokenService"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>0#.w|username</saml:AttributeValue>
</saml:Attribute>
  <saml:Attribute AttributeName="name"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims"
a:OriginalIssuer="SecurityTokenService"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>0#.w|username</saml:AttributeValue>
</saml:Attribute>
  <saml:Attribute AttributeName="identityprovider"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="SecurityTokenService"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>windows</saml:AttributeValue>
</saml:Attribute>
  <saml:Attribute AttributeName="isauthenticated"
AttributeNamespace="http://sharepoint.microsoft.com/claims/2009/08"
a:OriginalIssuer="SecurityTokenService"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>True</saml:AttributeValue>
</saml:Attribute>
  <saml:Attribute AttributeName="farmid"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="ClaimProvider:System"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>95cc4a80-a978-4077-ae9-1103092e5303</saml:AttributeValue>
</saml:Attribute>
  <saml:Attribute AttributeName="tokenreference"
AttributeNamespace="http://sharepoint.microsoft.com/claims/2009/08">
  <saml:AttributeValue>0).w|s-1-5-21-2127521184-1604012920-1887927527-
526964,0#.w|username,129666288871048579,True,mosiwjgtmyOf4EPy284D/Jwtb4Zff6qhlMZhV+dsneECHLdv
9sWwc8pWIqM/lx£ZPgcR6udlpRKezroqo017Nf+MzTSypfUe5ZwL6qhIuDmFE+LcjpVavwnVbE6ubBWPn9hM+Rv66vfCn
FNh/vM2tNQhV7hTqE29C3J6rNVBKlM4QFyCyZuH+GdED49S/55XDA5wmTSCgAz/t8swIM80vmHyMBtA4v0pKs2faXeN1F
N1npDaQvwNNnt0qYJv7Y0Nj3Ri8btJQ58BKX+HCztHZKqtQpBjoTH7XLbl1Wsap1c6JdCo1Sghz8BQEK8U9QLx9vWVavMK
MfNywsyWtnSg3uw==,urn:schemas-microsoft-com:sharepoint:service</saml:AttributeValue>

```

```

</saml:Attribute>
<saml:Attribute AttributeName="SidCompressed"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>S-1-5-21-2127521184-1604012920-
1887927527;513;3235764;5631067;6527764;1495408;2041268;5958388;5001327;6527739;2898815;634623
;6527783;492976;6527730;5951129;6527781;6525568;3535576;7360148;5377546;6621241;3168605;30615
41;3794426;4600588;7781173;4466716;4933277;3168614;1421044;7681958;7347463;5782818;7781172;31
68604;8091924;8133536;1910859;326949;7781246;3535807;7864574;7149326;5005350;3533463;6088077;
7338907;8084865;2115484;1921745;6598066;7485662;2738467;7513462;6835656;7957251;3240403;31213
04;7492442;1821296;7693631;6094633;3535581;8139922;1924384;7311515;3244172;3244301;7781169;77
81163;4552137;3168601;3168602;6129242;6071320;8227456;5518445;6835659;7781164;5124256;5869759
;1929380;8004468;7856854;2927357;6634566;2889412;650728;7856812;7877130;175772;2361615;650727
;6527731;771043;7547205;7856860;7877049;6527765;4814166;6639913;1700934;6984515;2547081;77640
26;6527784;4666181;2361614;4662838;6527782;7205074;4662826;2015132;7856806;6634544;1230889;26
71629;6260547;2289587;6634723;7856956;7672696;6253091;6916102;4923067;6639947;7842436;7547198
;4968904;6634530;7672705;3457292;6639831;1378086;4662824;5135771;4662842;7755302;6634516;1908
118;1908119;7856977;1230890;1378084;1472082;2400103;2542707;1908120;6001903;158181;4571792;20
62437;6015065;556526;771112;7672780;2289588;2529053;5107804;1390170;7877064;6984513;2361613;7
25547;6639879;1378088;6639888;7672699;5107803;6634527;754149;2671628;1472096;6634538;7856830;
1908117;1908121;2984327;7856938;6680169;6639833;571;6634536;3132840;6634505;6634528;7844666;7
764017;7316492;6634535;6527740;6869767;6634518;6634503;2361612;1378091;6634531|S-1-1;0|S-1-5-
21-1049126966-2357333717-3104358719;1012|S-1-5;11|S-1-5-21-2146773085-903363285-
719344707;1309616;1146011;1253526;1260212;1252077|S-1-5-21-1721254763-462695806-
1538882281;3217681;3207910|S-1-5-21-124525095-708259637-
1543119021;1115857;1115914;1115908;1165956;1115917;926551;926563;1115903|S-1-5-
64;10|</saml:AttributeValue>
</saml:Attribute>
<saml:Attribute AttributeName="actor"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>&lt;Actor&gt;&lt;/saml:Attribute AttributeName="nameidentifier"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims"
a:OriginalIssuer="SharePoint" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
;username&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="userlogonname"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="Windows" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
;Username&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="userid"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="SecurityTokenService" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
;0#.w|username&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="identityprovider"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="SecurityTokenService" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
;windows&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="isauthenticated"
AttributeNamespace="http://sharepoint.microsoft.com/claims/2009/08"
a:OriginalIssuer="SecurityTokenService" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
;True&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="name"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims"
a:OriginalIssuer="SecurityTokenService" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
;0#.w|username&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="farmid"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="ClaimProvider:System" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
;95cc4a80-a978-4077-ae9-

```

```

1103092e5303<lt;/saml:AttributeValue>&lt;/saml:Attribute>&lt;/saml:Attribute></saml:Attribute
Value>
  </saml:Attribute>
</saml:AttributeStatement>
<saml:AuthenticationStatement
AuthenticationMethod="urn:federation:authentication:windows" AuthenticationInstant="2011-11-
24T07:21:26.995Z">
  <saml:Subject>
    <saml:NameIdentifier>username</saml:NameIdentifier>
    <saml:SubjectConfirmation>
      <saml:ConfirmationMethod>urn:oasis:names:tc:SAML:1.0:cm:holder-of-
key</saml:ConfirmationMethod>
      <KeyInfo xmlns="http://www.w3.org/2000/09/xmldsig#">
        <KeyValue>
          <RSAKeyValue>
            <Modulus>xTLtoGopRTYng4kkTo+AGsU9AYYqsoJ3TsiUdALBVW9C7hNQBgx0loCVV2H23ckHi1970VEyOmYAIIVxtMFL
jQb9TtDckncZDrN8CuL/Pc5LlKhH9zuFIjdbJiLqnYQBAYxHyLphEcW6MSRaTX62EoGk/pxPzZAhUocVOzv7aU=</Mod
ulus>
              <Exponent>AQAB</Exponent>
            </RSAKeyValue>
          </KeyValue>
        </KeyInfo>
      </saml:SubjectConfirmation>
    </saml:Subject>
  </saml:AuthenticationStatement>
  <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
      </ds:CanonicalizationMethod>
      <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-sha256">
      </ds:SignatureMethod>
      <ds:Reference URI="#_9b6296d4-3f78-4887-8a99-73355d77ed4b">
        <ds:Transforms>
          <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature">
          </ds:Transform>
          <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
          </ds:Transform>
        </ds:Transforms>
        <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmllenc#sha256">
        </ds:DigestMethod>
        <ds:DigestValue>p+PdaqS/EfOyTid+2Tr5yH8xywIik1KktiaoN9FzIPA=</ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>g9VAK+5/ZGLOzk8rd5RUG99Q/g9Qnh+JTeHi3Dt9REyn6aLH7DJ2P2qRenrrMPMyQIqUIF/Nfx
pXfo8UqLX1+02HQZ188ZoCqXzQUj6lLeEWI2OVXlyFehdvtFG+3UstKWdR3wVJ7CWh62u/SOXvPiM8GyXitGnG5AE6bja
82fnV+QNxrlYKbMMeMgBmIs9B87x4Ivq7ksetFstbiXO3mIZcz1YsTTCLkeX2StxlhF+yb0EsdLJ6NcCxUJk0y6KzATt
f6TEfzmsSoqq2J82DaablbtY0z8HBTmr27rQ9mVU1SvYra9PoBsw1S5Q8fD/GFgxtfVZ60UYXpBQ+ArQow==</ds:Sign
atureValue>
      <KeyInfo xmlns="http://www.w3.org/2000/09/xmldsig#">
        <X509Data>
          <X509Certificate>MIIERjCCAi6gAwIBAgIQM5u5YNJ2qZRK7/rf8N2SezANBqkqhkiG9w0BAQUFADBaMQswCQYDVQQG
EwJVUzESMBAGAlUEChMjTlwljcm9zb2Z0MRMwEQYDVQQLEWpTaGFyZVBvaW50MSIwIAYDVQQDEx1TaGFyZVBvaW50IFJvb
3QgQXV0aG9yaXR5MCAXDTEyMTEyMzAwMzQ1MjYzZDk1OThkMTAxMDAwMDAwWjBiMQswCQYDVQQGEwJVUzESMBAGAlUECh
MjTlwljcm9zb2Z0MRMwEQYDVQQLEWpTaGFyZVBvaW50MSowKAYDVQQDEyFTaGFyZVBvaW50IFNlY3VyaXR5IFRva2VuIFN
lcnZpY2UwgqEiMA0GCSqGSIb3DQEBAQUAA4IBDwAwggEKAoIBAQCzHm/BcOXm6TYMGMQYc+XPR/9YTG0RXYi43SGOC9wR
qzipS6r/AU+hidfFpUOS3bjER5wCcLiG39cokOlBmk5uYkNgQpEcEshgklbeyfsQfs4M5jbc0z5z+FmK4CqN1LebHDJgN
6vcONnxBKmvR0H4szZ45p2fbpLTueJvIeM4/89lTaIvByI7a6HU6pIwL3jYTa9MdtVSgQj3ExiLw7k4hlec+0+CiqrYnL
imQe30Urdl0CS71uwQsTJcrY0u5zwnFJL9A+PLUwg8HS2bsAue50dvc1MIMS4ifaOkMDkdpQYqutjeZLyMJ0ty0dh1HUU
Yl0lLUDtvR2YaykogoekPAGMBAEwDQYJKoZIhvcNAQEFBQADggIBAJgAElPG314GeVA8mIfE2mAc1SWjDM4xaA+azelZ

```

FGzIT8h3Kbr201Mqw8TvuSpTQiFAlaP0ldU3PoRQYwck60Q5Z3plYZ7bL4K0kxvcPgbSsRoQ/R0odkdokNw3yE5yQUo21
Y1X289hwsYoWrXGYxIBz8B82bZe3Ty1H5edU3SJU9P2nCoC/8xDkhjQp0lrrwTOHcwcqaBeqdmYCZT0QafnAQlm7NpSuF
6UEyMGd343N1ZtC6CgxisqT1K19Dcw54ryG0R9CrP5RsJGyk+tMeWLYG/i08V26o3Y9Hq/iC8JoYM9m1TmAMaekKawxY4
3SxObEmqiVP6mX6N1StWxIwU7HhGjz6sgOhQGU3Ljlr4cMe6yBhzWZ/reOjGI/viDNuFkbrLtzRDAFe+oG1T9VWcUtV4p
1s17lXx+dbY2+sBSKfO5340sCyuERX4i3HcdUaHAIwoY26Yy3mkkU3AJL7eKex/09Sr2GfTxxBS818dCXagagFQ+qJv8
CVn8WyyHhkb20u8gzIBwNjbdosJcmJh1B7q7rJd06gLi0jp7HqtsYYcsw/Y6XBSp8S09uENVhrgiZdNzBIhUu39igm5su
gK1VJGtljp6gDsMM/xgAh/H+OVYQ0t5HbCdZ7vPeKxubGoEFYit6MpahdjWqZU6s5m2dnQ9tMJ57e2jhIhztSE</X509C
ertificate>

```
</X509Data>
</KeyInfo>
</ds:Signature>
</saml:Assertion>
<SignedInfo xmlns="http://www.w3.org/2000/09/xmldsig#enveloped-signature">
  <CanonicalizationMethod>
    <SignatureMethod Algorithm="PrefixList">
    </SignatureMethod>
    <SignatureValue Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-sha256">
    </SignatureValue>
    <Reference URI="#_0">
      <Transforms>
        <Transform Algorithm="PrefixList">
        </Transform>
      </Transforms>
      <DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256">
      </DigestMethod>
      <Address>U+ftZ2ktf2g6IYzZHI3l4WH7I40=</Address>
    </Reference>
    <Reference URI="#_1">
      <Transforms>
        <Transform Algorithm="PrefixList">
        </Transform>
      </Transforms>
      <DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256">
      </DigestMethod>
      <Address>E0mgpYR9TOWs6SpBQXM/j4UjD2w=</Address>
    </Reference>
  </CanonicalizationMethod>

  <DataReference>sAMgAVtnJAl+VsmvyoEgobVTSTOSchwI6TYOtquAlBb3cxN9QFCw+WNLmuAg3VQ24ZuZUe2nfxGMSJ
  Jqv5+Gn6oVD5UNEKvNAI8c8Bp/pNe5+ZGMxN8xe6qNk8uMqujRlsETwDFaSOweqXL8hZ6vlnN9S4vfo1OsF7Wojlufaac
  =</DataReference>
  <http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd>
    <o:Sequence k:http://docs.oasis-open.org/wss/oasis-wss-soap-message-security-
    1.1#ThumbprintSHA1="http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.1#SAMLV1.1"
    xmlns:k="RequestSecurityTokenResponseCollection">
      <o:http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-
      1.0#Base64Binary Type="http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-
      1.0#SAMLAssertionID">_9b6296d4-3f78-4887-8a99-73355d77ed4b</o:http://docs.oasis-
      open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0#Base64Binary>
    </o:Sequence>
  </http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd>
</SignedInfo>
</o:Timestamp>
</s:Header>
<s:Body>
  <BeginCacheRefresh xmlns="http://tempuri.org/">
  </BeginCacheRefresh>
</s:Body>
</s:Envelope>
```

The protocol server might respond with a message such as this one:

```
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope"
xmlns:a="http://www.w3.org/2005/08/addressing" xmlns:u="Security">
  <s:Header>
    <a:Action
s:mustUnderstand="1">http://tempuri.org/IWorkManagementServiceApplication/BeginCacheRefreshRe
sponse</a:Action>
    <ActivityId CorrelationId="668cb0dd-3d8c-4f55-af96-22cfb06c13d3"
xmlns="http://schemas.microsoft.com/2004/09/ServiceModel/Diagnostics">58cad185-6509-43cd-
8e89-58a3338b0cdd</ActivityId>
    <a:RelatesTo>urn:uuid:d9b6e13c-d6e6-46e1-a4e8-8e88006d273e</a:RelatesTo>
    <ServiceResourceConsumption xmlns="http://schemas.microsoft.com/sharepoint/servicecontext"
xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
      <CPUMCycles>2288</CPUMCycles>
      <ManagedMemoryBytes i:nil="true">
      </ManagedMemoryBytes>
      <ManagedMemoryBytesLOH i:nil="true">
      </ManagedMemoryBytesLOH>
      <TotalSqlQueryCount>19</TotalSqlQueryCount>
      <TotalSqlQueryDuration>74</TotalSqlQueryDuration>
    </ServiceResourceConsumption>
    <o:Timestamp s:mustUnderstand="1" xmlns:o="http://www.w3.org/2001/04/xmlenc#">
      <u:Created u:Id="_0">
      <u:Expires>2011-11-24T07:45:47.028Z</u:Expires>
      <u:Length>2011-11-24T07:50:47.028Z</u:Length>
      </u:Created>
    </o:Timestamp>
  </s:Header>
  <s:Body>
    <BeginCacheRefreshResponse xmlns="http://tempuri.org/">
      <BeginCacheRefreshResult
xmlns:b="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"
xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
        <b:CreatedJob>true</b:CreatedJob>
        <b:CurrentJobId>2</b:CurrentJobId>
        <b:CurrentJobIdClient>2</b:CurrentJobIdClient>
      </BeginCacheRefreshResult>
    </BeginCacheRefreshResponse>
  </s:Body>
</s:Envelope>
```

In this scenario, the protocol client calls **BeginExchangeSync** to request a task (3) synchronization job on behalf of a user:

```
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope"
xmlns:a="http://www.w3.org/2005/08/addressing" xmlns:u="Security">
  <s:Header>
    <a:Action
s:mustUnderstand="1">http://tempuri.org/IWorkManagementServiceApplication/BeginExchangeSync</
a:Action>
    <a:MessageID>urn:uuid:1246723e-3b80-448d-9b1e-bfe889babd78</a:MessageID>
    <a:SequenceAcknowledgement>
    <a:ReplyTo>http://www.w3.org/2005/08/addressing/anonymous</a:ReplyTo>
    </a:SequenceAcknowledgement>
    <ServiceContext xmlns="http://schemas.microsoft.com/sharepoint/servicecontext"
xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
      <correlationId>93ef6f9b-65fb-3030-1abf-a71cdec960af</correlationId>
```

```

    <devdashboardIsEnabled>>false</devdashboardIsEnabled>
    <language>en-US</language>
    <region>en-US</region>
    <scopeId>4286270333255698</scopeId>
    <siteSubscriptionId>00000000-0000-0000-0000-000000000000</siteSubscriptionId>
    <ulstraceOverrideLevel>0</ulstraceOverrideLevel>
  </ServiceContext>
  <a:To s:mustUnderstand="1"
u:Id="_1">http://servername:port/44058d0990524belb0f66a890da50007/WorkManagementService.svc</
a:To>
    <o:Timestamp s:mustUnderstand="1" xmlns:o="http://www.w3.org/2001/04/xmlenc#">
      <u:Created u:Id="_0">
        <u:Expires>2011-11-29T00:49:38.851Z</u:Expires>
        <u:Length>2011-11-29T00:54:38.851Z</u:Length>
      </u:Created>
      <saml:Assertion MajorVersion="1" MinorVersion="1" AssertionID="_a760cacb-9550-4af5-8ad0-
e3b902ael891" Issuer="SharePoint" IssueInstant="2011-11-28T17:29:46.432Z"
xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion">
        <saml:Conditions NotBefore="2011-11-28T17:29:46.416Z" NotOnOrAfter="2011-11-
29T03:29:46.416Z">
          <saml:AudienceRestrictionCondition>
            <saml:Audience>urn:schemas-microsoft-com:sharepoint:service</saml:Audience>
          </saml:AudienceRestrictionCondition>
        </saml:Conditions>
        <saml:AttributeStatement>
          <saml:Subject>
            <saml:NameIdentifier>username</saml:NameIdentifier>
            <saml:SubjectConfirmation>
              <saml:ConfirmationMethod>urn:oasis:names:tc:SAML:1.0:cm:holder-of-
key</saml:ConfirmationMethod>
              <KeyInfo xmlns="http://www.w3.org/2000/09/xmldsig#">
                <KeyValue>
                  <RSAKeyValue>
                    <Modulus>33Z32MKwwMpKEQf16k+Z2C7lsFrEtj0AvliOKUE33xhSHB91111jvDorzNIANA2BUbEQFZGmfGbVzbKdG0o9
un978aRNAzZyit53GYaeZo5qPMvJkrTTbUjcJ77Rf/4osXxiEcCo0IVrf4m6qOy0laOKAM3KZadAZD+v/psQA9E=</Mod
ulus>
                    <Exponent>AQAB</Exponent>
                  </RSAKeyValue>
                </KeyValue>
              </KeyInfo>
            </saml:SubjectConfirmation>
          </saml:Subject>
          <saml:Attribute AttributeName="primarysid"
AttributeNamespace="http://schemas.microsoft.com/ws/2008/06/identity/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
            <saml:AttributeValue>S-1-5-21-2127521184-1604012920-1887927527-
526964</saml:AttributeValue>
          </saml:Attribute>
          <saml:Attribute AttributeName="primarygroupid"
AttributeNamespace="http://schemas.microsoft.com/ws/2008/06/identity/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
            <saml:AttributeValue>S-1-5-21-2127521184-1604012920-1887927527-
513</saml:AttributeValue>
          </saml:Attribute>
          <saml:Attribute AttributeName="upn"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
            <saml:AttributeValue>username@contoso.com</saml:AttributeValue>
          </saml:Attribute>

```

```
<saml:Attribute AttributeName="userlogonname"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>Username</saml:AttributeValue>
</saml:Attribute>
<saml:Attribute AttributeName="userid"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="SecurityTokenService"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>0#.w|username</saml:AttributeValue>
</saml:Attribute>
<saml:Attribute AttributeName="name"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims"
a:OriginalIssuer="SecurityTokenService"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>0#.w|username</saml:AttributeValue>
</saml:Attribute>
<saml:Attribute AttributeName="identityprovider"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="SecurityTokenService"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>windows</saml:AttributeValue>
</saml:Attribute>
<saml:Attribute AttributeName="isauthenticated"
AttributeNamespace="http://sharepoint.microsoft.com/claims/2009/08"
a:OriginalIssuer="SecurityTokenService"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>True</saml:AttributeValue>
</saml:Attribute>
<saml:Attribute AttributeName="farmid"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="ClaimProvider:System"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>95cc4a80-a978-4077-ae9-1103092e5303</saml:AttributeValue>
</saml:Attribute>
<saml:Attribute AttributeName="tokenreference"
AttributeNamespace="http://sharepoint.microsoft.com/claims/2009/08">
  <saml:AttributeValue>0).w|s-1-5-21-2127521184-1604012920-1887927527-
526964,0#.w|username,129670109864168945,True,BwACO6nxCcbSMU1RgxAgTUmvdqvyo70g8KKPdguhZCtNTEtD
rEbGA98YUsfJcT+JN5qk22/S1HAsjd21+b5hh8JW2oRJJ2bpiJQeC3rdkIv9pj8p5NjeEHF3noP3eYP2CvWxRVUr6NZ/j
mc7Q7B7/cJsmRsJhMrmNNaqCCLIWrs5XpuNnHomSrEeCdqBnZGpwYE9HhscTicQsf3wKCR+0iBEFgftjOKJ4irJWD9p5YW
RHsVXUSmMnfP5zqE9hbBjt7JhCX+EZuDd/fWjzkXzrrf3rB3JMKRrXZOCyH70BFmIBRNvYnnYdiWNUHHCmOlggnAwoFjGB
Fiy+iH+T00LK6eg==,urn:schemas-microsoft-com:sharepoint:service</saml:AttributeValue>
</saml:Attribute>
<saml:Attribute AttributeName="SidCompressed"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="Windows" xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
  <saml:AttributeValue>S-1-5-21-2127521184-1604012920-
1887927527;513;3235764;5631067;6527764;1495408;2041268;5958388;5001327;6527739;2898815;634623
;6527783;492976;6527730;5951129;6527781;6525568;3535576;7360148;5377546;6621241;3168605;30615
41;3794426;4600588;7781173;4466716;4933277;3168614;1421044;7681958;7347463;5782818;7781172;31
68604;8091924;8133536;1910859;326949;7781246;3535807;7864574;7149326;5005350;3533463;6088077;
7338907;8084865;2115484;1921745;6598066;7485662;2738467;7513462;6835656;7957251;3240403;31213
04;7492442;1821296;7693631;6094633;3535581;8139922;1924384;7311515;3244172;3244301;7781169;77
81163;4552137;3168601;3168602;6129242;6071320;8227456;5518445;6835659;7781164;5124256;5869759
;129380;8004468;7856854;2927357;6634566;2889412;650728;7856812;7877130;175772;2361615;650727
;6527731;771043;7547205;7856860;7877049;6527765;4814166;6639913;1700934;6984515;2547081;77640
26;6527784;4666181;2361614;4662838;6527782;7205074;4662826;2015132;7856806;6634544;1230889;26
71629;6260547;2289587;6634723;7856956;7672696;6253091;6916102;4923067;6639947;7842436;7547198
;4968904;6634530;7672705;3457292;6639831;1378086;4662824;5135771;4662842;7755302;6634516;1908
118;1908119;7856977;1230890;1378084;1472082;2400103;2542707;1908120;6001903;158181;4571792;20
62437;6015065;556526;771112;7672780;2289588;2529053;5107804;1390170;7877064;6984513;2361613;7
25547;6639879;1378088;6639888;7672699;5107803;6634527;754149;2671628;1472096;6634538;7856830;
```

```

1908117;1908121;2984327;7856938;6680169;6639833;571;6634536;3132840;6634505;6634528;7844666;7
764017;7316492;6634535;6527740;6869767;6634518;6634503;2361612;1378091;6634531|S-1-1;0|S-1-
5;11|S-1-5-21-2146773085-903363285-719344707;1309616;1146011;1253526;1260212;1252077|S-1-5-
21-1721254763-462695806-1538882281;3217681;3207910|S-1-5-21-124525095-708259637-
1543119021;1115857;1115914;1115908;1165956;1115917;926551;926563;1115903|</saml:AttributeValu
e>
</saml:Attribute>
<saml:Attribute AttributeName="actor"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2009/09/identity/claims">
<saml:AttributeValue>&lt;Actor&gt;&lt;saml:Attribute AttributeName="nameidentifier"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims"
a:OriginalIssuer="SharePoint" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
user&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="userlogonname"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="Windows" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
Username&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="userid"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="SecurityTokenService" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
0#.w|username&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="identityprovider"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="SecurityTokenService" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
windows&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="isauthenticated"
AttributeNamespace="http://sharepoint.microsoft.com/claims/2009/08"
a:OriginalIssuer="SecurityTokenService" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
True&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="name"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims"
a:OriginalIssuer="SecurityTokenService" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
0#.w|username&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;saml:Attribute
AttributeName="farmid"
AttributeNamespace="http://schemas.microsoft.com/sharepoint/2009/08/claims"
a:OriginalIssuer="ClaimProvider:System" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:a="http://schemas.xmlsoap.org/ws/2009/09/identity/claims"&gt;&lt;saml:AttributeValue&gt;
95cc4a80-a978-4077-ae9-
1103092e5303&lt;/saml:AttributeValue&gt;&lt;/saml:Attribute&gt;&lt;/Actor&gt;</saml:Attribute
Value>
</saml:Attribute>
</saml:AttributeStatement>
<saml:AuthenticationStatement
AuthenticationMethod="urn:federation:authentication:windows" AuthenticationInstant="2011-11-
28T17:29:46.401Z">
<saml:Subject>
<saml:NameIdentifier>username</saml:NameIdentifier>
<saml:SubjectConfirmation>
<saml:ConfirmationMethod>urn:oasis:names:tc:SAML:1.0:cm:holder-of-
key</saml:ConfirmationMethod>
<KeyInfo xmlns="http://www.w3.org/2000/09/xmldsig#">
<KeyValue>
<RSAKeyValue>
<Modulus>33Z32MKwwMpKEQf16k+Z2C7lsFrEtj0AvliOKUE33xhSHB91111jvDorzNIANA2BUBEQFZGmfGbVzbKdG0o9
un978aRNAzZyit53GYaeZo5qPMvJkrTTbUjcJ77Rf/4osXxiEcCo0IVrf4m6qOy0laOKAM3KZadAZD+v/psQA9E=</Mod
ulus>
<Exponent>AQAB</Exponent>

```



```

<Transforms>
  <Transform Algorithm="PrefixList">
    </Transform>
  </Transforms>
<DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256">
  </DigestMethod>
<Address>sybFh758WbKHAB6sqM0Za+X5UQg=</Address>
</Reference>
<Reference URI="#_1">
  <Transforms>
    <Transform Algorithm="PrefixList">
      </Transform>
    </Transforms>
    <DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256">
      </DigestMethod>
    <Address>E0mgpYR9TOws6SpBQXM/j4UjD2w=</Address>
  </Reference>
</CanonicalizationMethod>

<DataReference>kEwSrGK8PJvww92WEEbVp/kfqhhG9VBH6U2lrxadcfiu5vQj1gt1GVKhhijYhbJMgcZKoKf/BGDRyLS
3ZCmAQWDBfg+TTX4E/BLiz/XPRC0Ixnad6Mws1e+FEtOnPHG9swQjavgn03lAgVERKMfREY1ADS72L960v7gEJ0bd76dc
=</DataReference>
  <http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd>
    <o:Sequence k:http://docs.oasis-open.org/wss/oasis-wss-soap-message-security-
1.1#ThumbprintSHA1="http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.1#SAMLV1.1"
xmlns:k="RequestSecurityTokenResponseCollection">
      <o:http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-
1.0#Base64Binary Type="http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-
1.0#SAMLAssertionID">_a760cacb-9550-4af5-8ad0-e3b902ae1891</o:http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0#Base64Binary>
    </o:Sequence>
  </http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd>
</SignedInfo>
</o:Timestamp>
</s:Header>
<s:Body>
  <BeginExchangeSync xmlns="http://tempuri.org/">
    </BeginExchangeSync>
  </s:Body>
</s:Envelope>

```

The protocol server might respond with a message such as this one:

```

<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope"
xmlns:a="http://www.w3.org/2005/08/addressing" xmlns:u="Security">
  <s:Header>
    <a:Action
s:mustUnderstand="1">http://tempuri.org/IWorkManagementServiceApplication/BeginExchangeSyncRe
sponse</a:Action>
    <ActivityId CorrelationId="be8fbd1c-5b27-4527-a8bf-d65b51a20d89"
xmlns="http://schemas.microsoft.com/2004/09/ServiceModel/Diagnostics">701b8f86-20fa-4451-
960a-d3767f47b2c1</ActivityId>
    <a:RelatesTo>urn:uuid:1246723e-3b80-448d-9b1e-bfe889babd78</a:RelatesTo>
    <ServiceResourceConsumption xmlns="http://schemas.microsoft.com/sharepoint/servicecontext"
xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
      <CPUMCycles>1257</CPUMCycles>
      <ManagedMemoryBytes i:nil="true">
    </ManagedMemoryBytes>

```

```
<ManagedMemoryBytesLOH i:nil="true">
</ManagedMemoryBytesLOH>
<TotalSqlQueryCount>8</TotalSqlQueryCount>
<TotalSqlQueryDuration>25</TotalSqlQueryDuration>
</ServiceResourceConsumption>
<o:Timestamp s:mustUnderstand="1" xmlns:o="http://www.w3.org/2001/04/xmlenc#">
  <u:Created u:Id="_0">
    <u:Expires>2011-11-29T00:49:39.324Z</u:Expires>
    <u:Length>2011-11-29T00:54:39.324Z</u:Length>
  </u:Created>
</o:Timestamp>
</s:Header>
<s:Body>
  <BeginExchangeSyncResponse xmlns="http://tempuri.org/">
    <BeginExchangeSyncResult>true</BeginExchangeSyncResult>
  </BeginExchangeSyncResponse>
</s:Body>
</s:Envelope>
```

5 Security

5.1 Security Considerations for Implementers

Aggregation and synchronization will occur on behalf of the user whose identity is tied to the request. Implementers need to make sure that the identity is established for the correct user prior to making calls to this protocol.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

For ease of implementation, the full WSDL is provided in this appendix.

```
<?xml version="1.0"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:tns2="http://tempuri.org/" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl" targetNamespace="http://tempuri.org/"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <xs:schema xmlns:tns3="http://tempuri.org/Imports"
targetNamespace="http://tempuri.org/Imports">
      <xs:import
namespace="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"/>
      <xs:import namespace="http://schemas.microsoft.com/2003/10/Serialization"/>
      <xs:import namespace="http://tempuri.org"/>
    </xs:schema>
  </wsdl:types>
  <wsdl:portType name="IWorkManagementServiceApplication">
    <wsdl:operation name="BeginCacheRefresh">
      <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginCacheRefresh"
message="tns2:IWorkManagementServiceApplication_BeginCacheRefresh_InputMessage"/>
      <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginCacheRefreshResponse"
message="tns2:IWorkManagementServiceApplication_BeginCacheRefresh_OutputMessage"/>
    </wsdl:operation>
    <wsdl:operation name="BeginExchangeSync">
      <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginExchangeSync"
message="tns2:IWorkManagementServiceApplication_BeginExchangeSync_InputMessage"/>
      <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginExchangeSyncResponse"
message="tns2:IWorkManagementServiceApplication_BeginExchangeSync_OutputMessage"/>
    </wsdl:operation>
    <wsdl:operation name="OptIntoExchangeSync">
      <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/OptIntoExchangeSync"
message="tns2:IWorkManagementServiceApplication_OptIntoExchangeSync_InputMessage"/>
      <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/OptIntoExchangeSyncResponse"
message="tns2:IWorkManagementServiceApplication_OptIntoExchangeSync_OutputMessage"/>
    </wsdl:operation>
    <wsdl:operation name="OptOutOfExchangeSync">
      <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/OptOutOfExchangeSync"
message="tns2:IWorkManagementServiceApplication_OptOutOfExchangeSync_InputMessage"/>
      <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/OptOutOfExchangeSyncResponse"
message="tns2:IWorkManagementServiceApplication_OptOutOfExchangeSync_OutputMessage"/>
    </wsdl:operation>
    <wsdl:operation name="GetExchangeSyncInfo">
      <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/GetExchangeSyncInfo"
message="tns2:IWorkManagementServiceApplication_GetExchangeSyncInfo_InputMessage"/>
      <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/GetExchangeSyncInfoResponse"
message="tns2:IWorkManagementServiceApplication_GetExchangeSyncInfo_OutputMessage"/>
    </wsdl:operation>
    <wsdl:operation name="BeginCreateTaskPropagation">
```

```

        <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginCreateTaskPropagation"
message="tns2:IWorkManagementServiceApplication_BeginCreateTaskPropagation_InputMessage"/>
        <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginCreateTaskPropagationR
esponse"
message="tns2:IWorkManagementServiceApplication_BeginCreateTaskPropagation_OutputMessage"/>
        </wsdl:operation>
        <wsdl:operation name="BeginUpdateTaskPropagation">
        <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginUpdateTaskPropagation"
message="tns2:IWorkManagementServiceApplication_BeginUpdateTaskPropagation_InputMessage"/>
        <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginUpdateTaskPropagationR
esponse"
message="tns2:IWorkManagementServiceApplication_BeginUpdateTaskPropagation_OutputMessage"/>
        </wsdl:operation>
        <wsdl:operation name="BeginDeleteTaskPropagation">
        <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginDeleteTaskPropagation"
message="tns2:IWorkManagementServiceApplication_BeginDeleteTaskPropagation_InputMessage"/>
        <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginDeleteTaskPropagationR
esponse"
message="tns2:IWorkManagementServiceApplication_BeginDeleteTaskPropagation_OutputMessage"/>
        </wsdl:operation>
        <wsdl:operation name="BeginRelocateTaskPropagation">
        <wsdl:input
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginRelocateTaskPropagatio
n"
message="tns2:IWorkManagementServiceApplication_BeginRelocateTaskPropagation_InputMessage"/>
        <wsdl:output
wsaw:Action="http://tempuri.org/IWorkManagementServiceApplication/BeginRelocateTaskPropagatio
nResponse"
message="tns2:IWorkManagementServiceApplication_BeginRelocateTaskPropagation_OutputMessage"/>
        </wsdl:operation>
    </wsdl:portType>
    <wsdl:binding name="DefaultBinding_IWorkManagementServiceApplication"
type="tns2:IWorkManagementServiceApplication">
        <soap:binding transport="http://schemas.xmlsoap.org/soap/http"/>
        <wsdl:operation name="BeginCacheRefresh">
        <soap:operation
soapAction="http://tempuri.org/IWorkManagementServiceApplication/BeginCacheRefresh"
style="document"/>
        <wsdl:input>
        <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
        <soap:body use="literal"/>
        </wsdl:output>
        </wsdl:operation>
        <wsdl:operation name="BeginExchangeSync">
        <soap:operation
soapAction="http://tempuri.org/IWorkManagementServiceApplication/BeginExchangeSync"
style="document"/>
        <wsdl:input>
        <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
        <soap:body use="literal"/>
        </wsdl:output>

```

```

    </wsdl:operation>
    <wsdl:operation name="OptIntoExchangeSync">
      <soap:operation
soapAction="http://tempuri.org/IWorkManagementServiceApplication/OptIntoExchangeSync"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="OptOutOfExchangeSync">
      <soap:operation
soapAction="http://tempuri.org/IWorkManagementServiceApplication/OptOutOfExchangeSync"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetExchangeSyncInfo">
      <soap:operation
soapAction="http://tempuri.org/IWorkManagementServiceApplication/GetExchangeSyncInfo"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="BeginCreateTaskPropagation">
      <soap:operation
soapAction="http://tempuri.org/IWorkManagementServiceApplication/BeginCreateTaskPropagation"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="BeginUpdateTaskPropagation">
      <soap:operation
soapAction="http://tempuri.org/IWorkManagementServiceApplication/BeginUpdateTaskPropagation"
style="document"/>
      <wsdl:input>
        <soap:body use="literal"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="BeginDeleteTaskPropagation">
      <soap:operation
soapAction="http://tempuri.org/IWorkManagementServiceApplication/BeginDeleteTaskPropagation"
style="document"/>

```

```

        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="BeginRelocateTaskPropagation">
        <soap:operation
soapAction="http://tempuri.org/IWorkManagementServiceApplication/BeginRelocateTaskPropagation
" style="document"/>
        <wsdl:input>
            <soap:body use="literal"/>
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
</wsdl:binding>
<wsdl:message name="IWorkManagementServiceApplication_BeginCacheRefresh_InputMessage">
    <wsdl:part name="parameters" element="tns2:BeginCacheRefresh"/>
</wsdl:message>
<wsdl:message name="IWorkManagementServiceApplication_BeginCacheRefresh_OutputMessage">
    <wsdl:part name="parameters" element="tns2:BeginCacheRefreshResponse"/>
</wsdl:message>
<wsdl:message
name="IWorkManagementServiceApplication_BeginCreateTaskPropagation_InputMessage">
    <wsdl:part name="parameters" element="tns2:BeginCreateTaskPropagation"/>
</wsdl:message>
<wsdl:message
name="IWorkManagementServiceApplication_BeginCreateTaskPropagation_OutputMessage">
    <wsdl:part name="parameters" element="tns2:BeginCreateTaskPropagationResponse"/>
</wsdl:message>
<wsdl:message
name="IWorkManagementServiceApplication_BeginDeleteTaskPropagation_InputMessage">
    <wsdl:part name="parameters" element="tns2:BeginDeleteTaskPropagation"/>
</wsdl:message>
<wsdl:message
name="IWorkManagementServiceApplication_BeginDeleteTaskPropagation_OutputMessage">
    <wsdl:part name="parameters" element="tns2:BeginDeleteTaskPropagationResponse"/>
</wsdl:message>
<wsdl:message name="IWorkManagementServiceApplication_BeginExchangeSync_InputMessage">
    <wsdl:part name="parameters" element="tns2:BeginExchangeSync"/>
</wsdl:message>
<wsdl:message name="IWorkManagementServiceApplication_BeginExchangeSync_OutputMessage">
    <wsdl:part name="parameters" element="tns2:BeginExchangeSyncResponse"/>
</wsdl:message>
<wsdl:message
name="IWorkManagementServiceApplication_BeginRelocateTaskPropagation_InputMessage">
    <wsdl:part name="parameters" element="tns2:BeginRelocateTaskPropagation"/>
</wsdl:message>
<wsdl:message
name="IWorkManagementServiceApplication_BeginRelocateTaskPropagation_OutputMessage">
    <wsdl:part name="parameters" element="tns2:BeginRelocateTaskPropagationResponse"/>
</wsdl:message>
<wsdl:message
name="IWorkManagementServiceApplication_BeginUpdateTaskPropagation_InputMessage">
    <wsdl:part name="parameters" element="tns2:BeginUpdateTaskPropagation"/>
</wsdl:message>

```

```
<wsdl:message
name="IWorkManagementServiceApplication_BeginUpdateTaskPropagation_OutputMessage">
  <wsdl:part name="parameters" element="tns2:BeginUpdateTaskPropagationResponse"/>
</wsdl:message>
<wsdl:message name="IWorkManagementServiceApplication_GetExchangeSyncInfo_InputMessage">
  <wsdl:part name="parameters" element="tns2:GetExchangeSyncInfo"/>
</wsdl:message>
<wsdl:message name="IWorkManagementServiceApplication_GetExchangeSyncInfo_OutputMessage">
  <wsdl:part name="parameters" element="tns2:GetExchangeSyncInfoResponse"/>
</wsdl:message>
<wsdl:message name="IWorkManagementServiceApplication_OptIntoExchangeSync_InputMessage">
  <wsdl:part name="parameters" element="tns2:OptIntoExchangeSync"/>
</wsdl:message>
<wsdl:message name="IWorkManagementServiceApplication_OptIntoExchangeSync_OutputMessage">
  <wsdl:part name="parameters" element="tns2:OptIntoExchangeSyncResponse"/>
</wsdl:message>
<wsdl:message name="IWorkManagementServiceApplication_OptOutOfExchangeSync_InputMessage">
  <wsdl:part name="parameters" element="tns2:OptOutOfExchangeSync"/>
</wsdl:message>
<wsdl:message name="IWorkManagementServiceApplication_OptOutOfExchangeSync_OutputMessage">
  <wsdl:part name="parameters" element="tns2:OptOutOfExchangeSyncResponse"/>
</wsdl:message>
</wsdl:definitions>
```

7 Appendix B: Full XML Schema

Schema name	Prefix	Section
http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement	tns	7.1
http://schemas.microsoft.com/2003/10/Serialization/	tns1	7.2
http://tempuri.org/	tns2	7.3

For ease of implementation, the following sections provide the full XML schema for this protocol.

7.1

<http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement> Schema

```
<?xml version="1.0"?>
<xs:schema
  xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"
  elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType name="CreateRefreshJobResult">
    <xs:sequence>
      <xs:element minOccurs="0" name="CreatedJob" type="xs:boolean"/>
      <xs:element minOccurs="0" name="CurrentJobId" nillable="true" type="xs:int"/>
      <xs:element minOccurs="0" name="CurrentJobIdClient" type="xs:int"/>
      <xs:element minOccurs="0" name="EncounteredError" type="xs:boolean"/>
    </xs:sequence>
  </xs:complexType>
  <xs:element name="CreateRefreshJobResult" nillable="true"
    type="tns:CreateRefreshJobResult"/>
  <xs:simpleType name="ExchangeOptInResult">
    <xs:restriction base="xs:string">
      <xs:enumeration value="NoValue"/>
      <xs:enumeration value="Success"/>
      <xs:enumeration value="UnknownError"/>
      <xs:enumeration value="CouldNotConnectToExchange"/>
      <xs:enumeration value="CouldNotFindOrCreateMySite"/>
      <xs:enumeration value="UserAlreadyOptedIn"/>
      <xs:enumeration value="UserExchangeOperationPending"/>
      <xs:enumeration value="UnsupportedExchangeVersion"/>
      <xs:enumeration value="MissingEmailAddress"/>
      <xs:enumeration value="ExchangeWebServiceClientMissing"/>
      <xs:enumeration value="UnsupportedSharePointConfiguration"/>
      <xs:enumeration value="InvalidOrUnauthorizedUser"/>
      <xs:enumeration value="CouldNotActivateExchangeSyncFeatureOnSiteSubscription"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="ExchangeOptInResult" nillable="true" type="tns:ExchangeOptInResult"/>
  <xs:complexType name="ExchangeUserSyncState">
    <xs:sequence>
      <xs:element minOccurs="0" name="IsOptedIn" type="xs:boolean"/>
      <xs:element minOccurs="0" name="LastEndTime" nillable="true" type="xs:dateTime"/>
      <xs:element minOccurs="0" name="LastSyncResult" type="tns:ExchangeSyncResult"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

```

</xs:complexType>
<xs:element name="ExchangeUserSyncState" nillable="true" type="tns:ExchangeUserSyncState"/>
<xs:simpleType name="ExchangeSyncResult">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NoValue"/>
    <xs:enumeration value="Success"/>
    <xs:enumeration value="UnknownError"/>
    <xs:enumeration value="CouldNotConnectToExchange"/>
    <xs:enumeration value="CouldNotGetUserCredentials"/>
    <xs:enumeration value="CouldNotKickoffJob"/>
    <xs:enumeration value="SyncWithErrors"/>
  </xs:restriction>
</xs:simpleType>
<xs:element name="ExchangeSyncResult" nillable="true" type="tns:ExchangeSyncResult"/>
</xs:schema>

```

7.2 <http://schemas.microsoft.com/2003/10/Serialization/> Schema

```

<?xml version="1.0"?>
<xs:schema xmlns:tns1="http://schemas.microsoft.com/2003/10/Serialization/"
  attributeFormDefault="qualified" elementFormDefault="qualified"
  targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:element name="anyType" nillable="true" type="xs:anyType"/>
  <xs:element name="anyURI" nillable="true" type="xs:anyURI"/>
  <xs:element name="base64Binary" nillable="true" type="xs:base64Binary"/>
  <xs:element name="boolean" nillable="true" type="xs:boolean"/>
  <xs:element name="byte" nillable="true" type="xs:byte"/>
  <xs:element name="dateTime" nillable="true" type="xs:dateTime"/>
  <xs:element name="decimal" nillable="true" type="xs:decimal"/>
  <xs:element name="double" nillable="true" type="xs:double"/>
  <xs:element name="float" nillable="true" type="xs:float"/>
  <xs:element name="int" nillable="true" type="xs:int"/>
  <xs:element name="long" nillable="true" type="xs:long"/>
  <xs:element name="QName" nillable="true" type="xs:QName"/>
  <xs:element name="short" nillable="true" type="xs:short"/>
  <xs:element name="string" nillable="true" type="xs:string"/>
  <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte"/>
  <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt"/>
  <xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong"/>
  <xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort"/>
  <xs:element name="char" nillable="true" type="tns1:char"/>
  <xs:simpleType name="char">
    <xs:restriction base="xs:int"/>
  </xs:simpleType>
  <xs:element name="duration" nillable="true" type="tns1:duration"/>
  <xs:simpleType name="duration">
    <xs:restriction base="xs:duration">
      <xs:pattern value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?"/>
      <xs:minInclusive value="-P10675199DT2H48M5.4775808S"/>
      <xs:maxInclusive value="P10675199DT2H48M5.4775807S"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:element name="guid" nillable="true" type="tns1:guid"/>
  <xs:simpleType name="guid">
    <xs:restriction base="xs:string">
      <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}"/>
    </xs:restriction>
  </xs:simpleType>

```

```

    </xs:restriction>
  </xs:simpleType>
  <xs:attribute name="FactoryType" type="xs:QName"/>
  <xs:attribute name="Id" type="xs:ID"/>
  <xs:attribute name="Ref" type="xs:IDREF"/>
</xs:schema>

```

7.3 http://tempuri.org/ Schema

```

<?xml version="1.0"?>
<xs:schema elementFormDefault="qualified" targetNamespace="http://tempuri.org/"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import
namespace="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"/>
  <xs:element name="BeginCacheRefresh">
    <xs:complexType>
      <xs:sequence/>
    </xs:complexType>
  </xs:element>
  <xs:element name="BeginCacheRefreshResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"
minOccurs="0" name="BeginCacheRefreshResult" nillable="true"
type="tns:CreateRefreshJobResult"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="BeginExchangeSync">
    <xs:complexType>
      <xs:sequence/>
    </xs:complexType>
  </xs:element>
  <xs:element name="BeginExchangeSyncResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" name="BeginExchangeSyncResult" type="xs:boolean"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="OptIntoExchangeSync">
    <xs:complexType>
      <xs:sequence/>
    </xs:complexType>
  </xs:element>
  <xs:element name="OptIntoExchangeSyncResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"
minOccurs="0" name="OptIntoExchangeSyncResult" type="tns:ExchangeOptInResult"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="OptOutOfExchangeSync">
    <xs:complexType>
      <xs:sequence/>
    </xs:complexType>
  </xs:element>

```

```

    </xs:complexType>
  </xs:element>
  <xs:element name="OptOutOfExchangeSyncResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" name="OptOutOfExchangeSyncResult" type="xs:boolean"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetExchangeSyncInfo">
    <xs:complexType>
      <xs:sequence/>
    </xs:complexType>
  </xs:element>
  <xs:element name="GetExchangeSyncInfoResponse">
    <xs:complexType>
      <xs:sequence>
        <xs:element
xmlns:tns="http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement"
minOccurs="0" name="GetExchangeSyncInfoResult" nillable="true"
type="tns:ExchangeUserSyncState"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="BeginCreateTaskPropagation">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" name="taskId" type="xs:int"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="BeginCreateTaskPropagationResponse">
    <xs:complexType>
      <xs:sequence/>
    </xs:complexType>
  </xs:element>
  <xs:element name="BeginUpdateTaskPropagation">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" name="taskId" type="xs:int"/>
        <xs:element minOccurs="0" name="lastModified" type="xs:dateTime"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="BeginUpdateTaskPropagationResponse">
    <xs:complexType>
      <xs:sequence/>
    </xs:complexType>
  </xs:element>
  <xs:element name="BeginDeleteTaskPropagation">
    <xs:complexType>
      <xs:sequence>
        <xs:element minOccurs="0" name="taskId" type="xs:int"/>
        <xs:element minOccurs="0" name="mappedKey" nillable="true" type="xs:string"/>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="BeginDeleteTaskPropagationResponse">
    <xs:complexType>

```

```
        <xs:sequence/>
    </xs:complexType>
</xs:element>
<xs:element name="BeginRelocateTaskPropagation">
    <xs:complexType>
        <xs:sequence>
            <xs:element minOccurs="0" name="taskId" type="xs:int"/>
            <xs:element minOccurs="0" name="mappedKey" nillable="true" type="xs:string"/>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="BeginRelocateTaskPropagationResponse">
    <xs:complexType>
        <xs:sequence/>
    </xs:complexType>
</xs:element>
</xs:schema>
```

8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft SharePoint Server 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

9 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

10 Index

A

Abstract data model
[server](#) 13
[Applicability](#) 9
[Attribute groups](#) 12
[Attributes](#) 12

C

[Capability negotiation](#) 9
[Change tracking](#) 62
[charsimple type](#) 11
Client
[overview](#) 13
[Common data structures](#) 12
[Complex types](#) 11

D

Data model - abstract
[server](#) 13
[durationsimple type](#) 11

E

Events
[local - server](#) 37
[timer - server](#) 37
Examples
[overview](#) 38

F

[Fields - vendor-extensible](#) 9
[Full WSDL](#) 51
[Full XML Schema](#) 56
<http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement.Schema> 56
<http://schemas.microsoft.com/2003/10/Serialization/Schema> 57
<http://tempuri.org/Schema> 58

G

[Glossary](#) 7
[Groups](#) 12
[guidsimple type](#) 12

I

[Implementer - security considerations](#) 50
[Index of security parameters](#) 50
[Informative references](#) 8
Initialization
[server](#) 13
[Introduction](#) 7

L

Local events
[server](#) 37

M

Message processing
[server](#) 13
Messages
[attribute groups](#) 12
[attributes](#) 12
[charsimple type](#) 11
[common data structures](#) 12
[complex types](#) 11
[durationsimple type](#) 11
[elements](#) 11
[enumerated](#) 11
[groups](#) 12
[guidsimple type](#) 12
[namespaces](#) 10
[simple types](#) 11
[syntax](#) 10
[transport](#) 10

N

[Namespaces](#) 10
[Normative references](#) 7

O

Operations
[BeginCacheRefresh](#) 14
[BeginCreateTaskPropagation](#) 19
[BeginDeleteTaskPropagation](#) 21
[BeginExchangeSync](#) 17
[BeginRelocateTaskPropagation](#) 34
[BeginUpdateTaskPropagation](#) 23
[GetExchangeSyncInfo](#) 25
[OptIntoExchangeSync](#) 29
[OptOutOfExchangeSync](#) 32
[Overview \(synopsis\)](#) 8

P

[Parameters - security index](#) 50
[Preconditions](#) 9
[Prerequisites](#) 9
[Product behavior](#) 61
Protocol Details
[overview](#) 13

R

[References](#) 7
[informative](#) 8
[normative](#) 7
[Relationship to other protocols](#) 8

S

- Security
 - [implementer considerations](#) 50
 - [parameter index](#) 50
- Sequencing rules
 - [server](#) 13
- Server
 - [abstract data model](#) 13
 - [BeginCacheRefresh operation](#) 14
 - [BeginCreateTaskPropagation operation](#) 19
 - [BeginDeleteTaskPropagation operation](#) 21
 - [BeginExchangeSync operation](#) 17
 - [BeginRelocateTaskPropagation operation](#) 34
 - [BeginUpdateTaskPropagation operation](#) 23
 - [details](#) 13
 - [GetExchangeSyncInfo operation](#) 25
 - [initialization](#) 13
 - [local events](#) 37
 - [message processing](#) 13
 - [OptIntoExchangeSync operation](#) 29
 - [OptOutOfExchangeSync operation](#) 32
 - [overview](#) 13
 - [sequencing rules](#) 13
 - [timer events](#) 37
 - [timers](#) 13
- [Simple types](#) 11
 - [char](#) 11
 - [duration](#) 11
 - [guid](#) 12
- [Standards assignments](#) 9
- Syntax
 - [messages - overview](#) 10

T

- Timer events
 - [server](#) 37
- Timers
 - [server](#) 13
- [Tracking changes](#) 62
- [Transport](#) 10
- Types
 - [complex](#) 11
 - [simple](#) 11

V

- [Vendor-extensible fields](#) 9
- [Versioning](#) 9

W

- [WSDL](#) 51

X

- [XML Schema](#) 56
 - <http://schemas.datacontract.org/2004/07/Microsoft.Office.Server.WorkManagement.Schema> 56
 - <http://schemas.microsoft.com/2003/10/Serialization/Schema> 57
 - <http://tempuri.org/Schema> 58