

# [MS-WSSCAML]: Collaborative Application Markup Language (CAML) Structure

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability
06/27/2008	1.0	Major	Revised and edited the technical content
12/12/2008	1.01	Editorial	Revised and edited the technical content
07/13/2009	1.02	Major	Revised and edited the technical content
08/28/2009	1.03	Editorial	Revised and edited the technical content
11/06/2009	1.04	Editorial	Revised and edited the technical content
02/19/2010	2.0	Major	Updated and revised the technical content
03/31/2010	2.01	Editorial	Revised and edited the technical content
04/30/2010	2.02	Editorial	Revised and edited the technical content
06/07/2010	2.03	Editorial	Revised and edited the technical content
06/29/2010	2.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	3.0	Major	Significantly changed the technical content.
04/11/2012	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
09/12/2012	3.0	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	3.1	Minor	Clarified the meaning of the technical content.

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
02/11/2013	4.0	Major	Significantly changed the technical content.
07/30/2013	4.1	Minor	Clarified the meaning of the technical content.
11/18/2013	4.1	No change	No changes to the meaning, language, or formatting of the technical content.
02/10/2014	4.1	No change	No changes to the meaning, language, or formatting of the technical content.
04/30/2014	4.2	Minor	Clarified the meaning of the technical content.
07/31/2014	4.3	Minor	Clarified the meaning of the technical content.

# Table of Contents

<b>1 Introduction</b>	<b>12</b>
1.1 Glossary	12
1.2 References	14
1.2.1 Normative References	14
1.2.2 Informative References	15
1.3 Overview	15
1.4 Relationship to Protocols and Other Structures	15
1.5 Applicability Statement	15
1.6 Versioning and Localization	15
1.7 Vendor-Extensible Fields	15
1.7.1 XmlDocument Documents on ContentTypeDefinition Type	15
1.7.2 PolicyItem	15
<b>2 Structures</b>	<b>17</b>
2.1 Common Simple Types	17
2.1.1 AssemblyClass	17
2.1.2 AssemblyStrongName	17
2.1.3 FALSE_Case_Insensitive_ElseAnything	17
2.1.4 IntNonNegative	17
2.1.5 RelativeFilePath	17
2.1.6 RelativeUrl	18
2.1.7 String255Chars	18
2.1.8 TRUE_Case_Insensitive_ElseAnything	18
2.1.9 TRUE_Case_Sensitive_ElseAnything	18
2.1.10 TRUE_If_Present	18
2.1.11 TRUE_NegOne_ElseAnything	18
2.1.12 TRUEFALSE	19
2.1.13 truefalse_Only_Lowercase	19
2.1.14 UniqueIdentifierWithoutBracesOrEmpty	19
2.1.15 UniqueIdentifierWithoutBraces	19
2.1.16 UniqueIdentifierWithBraces	19
2.1.17 UniqueIdentifierWithBracesOrEmpty	19
2.1.18 UniqueIdentifierWithOrWithoutBraces	20
2.1.19 UniqueIdentifierWithOrWithoutBracesWithOrWithoutDashes	20
2.2 Query Types	20
2.2.1 Simple Types	20
2.2.1.1 ListJoinJoin Type	20
2.2.2 Complex Types	20
2.2.2.1 CamlQueryRoot Type	21
2.2.2.1.1 Schema	21
2.2.2.1.2 Attributes	21
2.2.2.1.3 Child Elements	21
2.2.2.2 LogicalJoinDefinition Type	21
2.2.2.2.1 Schema	21
2.2.2.2.2 Attributes	22
2.2.2.2.3 Child Elements	22
2.2.2.3 OrderByDefinition Type	24
2.2.2.3.1 Schema	24
2.2.2.3.2 Attributes	24
2.2.2.3.3 Child Elements	24

2.2.2.4	FieldRefDefinitionOrderBy Type	24
2.2.2.4.1	Schema	24
2.2.2.4.2	Attributes	24
2.2.2.4.3	Child Elements	25
2.2.2.5	GroupByDefinition Type	25
2.2.2.5.1	Schema	25
2.2.2.5.2	Attributes	25
2.2.2.5.3	Child Elements	25
2.2.2.6	FieldRefDefinitionGroupBy Type	25
2.2.2.6.1	Schema	25
2.2.2.6.2	Attributes	26
2.2.2.6.3	Child Elements	26
2.2.2.7	ExtendedLogicalJoinDefinition Type	26
2.2.2.7.1	Schema	26
2.2.2.7.2	Attributes	26
2.2.2.7.3	Child Elements	26
2.2.2.8	LogicalTestDefinition Type	27
2.2.2.8.1	Schema	27
2.2.2.8.2	Attributes	27
2.2.2.8.3	Child Elements	27
2.2.2.9	ValueDefinition Type	27
2.2.2.9.1	Schema	27
2.2.2.9.2	Attributes	27
2.2.2.9.3	Child Elements	27
2.2.2.10	FieldRefDefinitionQueryTest Type	27
2.2.2.10.1	Schema	28
2.2.2.10.2	Attributes	28
2.2.2.10.3	Child Elements	28
2.2.2.11	LogicalTestDefinitionDateRange Type	28
2.2.2.11.1	Schema	28
2.2.2.11.2	Attributes	28
2.2.2.11.3	Child Elements	28
2.2.2.12	ValueDefinitionDateRange Type	29
2.2.2.12.1	Schema	29
2.2.2.12.2	Attributes	29
2.2.2.12.3	Child Elements	29
2.2.2.13	FieldRefDefinitionQueryDate Type	30
2.2.2.13.1	Schema	30
2.2.2.13.2	Attributes	30
2.2.2.13.3	Child Elements	30
2.2.2.14	LogicalNullDefinition Type	30
2.2.2.14.1	Schema	30
2.2.2.14.2	Attributes	30
2.2.2.14.3	Child Elements	30
2.2.2.15	FieldRefDefinitionQueryNull Type	31
2.2.2.15.1	Schema	31
2.2.2.15.2	Attributes	31
2.2.2.15.3	Child Elements	31
2.2.2.16	MembershipDefinition Type	31
2.2.2.16.1	Schema	31
2.2.2.16.2	Attributes	31
2.2.2.16.3	Child Elements	31
2.2.2.17	LogicalTestInValuesDefinition Type	31

2.2.2.17.1	Schema.....	31
2.2.2.17.2	Attributes.....	32
2.2.2.17.3	Child Elements.....	32
2.2.2.18	ValueDefinitionCollection Type.....	32
2.2.2.18.1	Schema.....	32
2.2.2.18.2	Attributes.....	32
2.2.2.18.3	Child Elements.....	32
2.2.2.19	ProjectedFieldsDefinitionType.....	32
2.2.2.19.1	Schema.....	32
2.2.2.19.2	Attributes.....	33
2.2.2.19.3	Child Elements.....	33
2.2.2.20	ProjectedFieldDefinitionType.....	33
2.2.2.20.1	Schema.....	33
2.2.2.20.2	Attributes.....	33
2.2.2.21	ListJoinsDefinitionType.....	33
2.2.2.21.1	Schema.....	33
2.2.2.21.2	Attributes.....	34
2.2.2.21.3	Child Elements.....	34
2.2.2.22	ListJoinDefinitionType.....	34
2.2.2.22.1	Schema.....	34
2.2.2.22.2	Attributes.....	34
2.2.2.22.3	Child Elements.....	34
2.2.2.23	ListJoinConditionDefinitionType.....	34
2.2.2.23.1	Schema.....	34
2.2.2.23.2	Attributes.....	34
2.2.2.23.3	Child Elements.....	35
2.2.2.24	ListJoinConditionSourceFieldDefinition Type.....	35
2.2.2.24.1	Schema.....	35
2.2.2.24.2	Attributes.....	35
2.2.2.25	ListJoinConditionTargetFieldDefinition Type.....	35
2.2.2.25.1	Schema.....	35
2.2.2.25.2	Attributes.....	35
2.2.2.26	LogicalWithIndexDefinition Type.....	35
2.2.2.26.1	Schema.....	36
2.2.2.26.2	Attributes.....	36
2.2.2.26.3	Child Elements.....	36
2.2.2.27	ExtendedLogicalJoinDefinitionWithIndex Type.....	36
2.2.2.27.1	Schema.....	36
2.2.2.27.2	Attributes.....	37
2.2.2.27.3	Child Elements.....	37
2.3	List Schema Definitions.....	37
2.3.1	Simple Types.....	37
2.3.1.1	ListTemplateBaseType.....	37
2.3.1.2	AggregationsType.....	38
2.3.1.3	AggregationsValue Type.....	38
2.3.1.4	ContentTypeId Type.....	39
2.3.1.5	FormType.....	39
2.3.1.6	ListTemplateCategoryType.....	39
2.3.1.7	ToolbarPosition.....	40
2.3.1.8	ToolbarType.....	40
2.3.1.9	ViewModerationType.....	41
2.3.1.10	ViewPageLevel.....	41
2.3.1.11	ViewScope.....	41

2.3.1.12	ViewType .....	42
2.3.2	Complex Types .....	43
2.3.2.1	AggregationsDefinition Type .....	43
2.3.2.1.1	Schema .....	43
2.3.2.1.2	Attributes.....	43
2.3.2.1.3	Child Elements.....	43
2.3.2.2	FieldRefDefinitionAggregation Type .....	43
2.3.2.2.1	Schema .....	43
2.3.2.2.2	Attributes.....	43
2.3.2.2.3	Child Elements.....	44
2.3.2.3	CalendarViewStylesDefinition Type .....	44
2.3.2.3.1	Schema .....	44
2.3.2.3.2	Attributes.....	44
2.3.2.3.3	Child Elements.....	44
2.3.2.4	CalendarViewStyleDefinition Type .....	44
2.3.2.4.1	Schema .....	44
2.3.2.4.2	Child Elements.....	44
2.3.2.4.3	Attributes.....	45
2.3.2.5	FormDefinition Type.....	45
2.3.2.5.1	Schema .....	45
2.3.2.5.2	Attributes.....	46
2.3.2.5.3	Child Elements.....	46
2.3.2.6	ListDefinition Type .....	47
2.3.2.6.1	Schema .....	47
2.3.2.6.2	Attributes.....	48
2.3.2.6.3	Child Elements.....	52
2.3.2.7	ListFormSet Type.....	52
2.3.2.7.1	Schema .....	52
2.3.2.7.2	Attributes.....	52
2.3.2.7.3	Child Elements.....	52
2.3.2.8	ListMetaDataDefinition Type.....	52
2.3.2.8.1	Schema .....	52
2.3.2.8.2	Attributes.....	53
2.3.2.8.3	Child Elements.....	53
2.3.2.9	FieldDefinitions Type .....	53
2.3.2.9.1	Schema .....	53
2.3.2.9.2	Attribute .....	53
2.3.2.9.3	Child Elements.....	53
2.3.2.10	ListMetaDataDefault Type .....	53
2.3.2.10.1	Schema.....	53
2.3.2.10.2	Attributes .....	54
2.3.2.10.3	Child Elements .....	54
2.3.2.11	ListSecurity Type .....	54
2.3.2.11.1	Schema.....	54
2.3.2.11.2	Attributes .....	54
2.3.2.11.3	Child Elements .....	54
2.3.2.12	ListTemplateDefinitions Type.....	55
2.3.2.12.1	Schema.....	55
2.3.2.13	ListTemplateDefinition Type .....	55
2.3.2.13.1	Schema.....	55
2.3.2.13.2	Attributes .....	56
2.3.2.13.3	Child Elements .....	60
2.3.2.14	RowLimitDefinition Type .....	60

2.3.2.14.1	Schema.....	60
2.3.2.14.2	Attributes.....	60
2.3.2.14.3	Child Elements.....	60
2.3.2.15	ToolbarDefinition Type.....	60
2.3.2.15.1	Schema.....	60
2.3.2.15.2	Child Elements.....	60
2.3.2.15.3	Attributes.....	60
2.3.2.16	ViewDefinitions Type.....	61
2.3.2.16.1	Schema.....	61
2.3.2.16.2	Attributes.....	61
2.3.2.16.3	Child Elements.....	61
2.3.2.17	ViewDefinition Type.....	61
2.3.2.17.1	Schema.....	61
2.3.2.17.2	Attributes.....	65
2.3.2.17.3	Child Elements.....	68
2.3.2.18	FieldRefDefinitionViewData Type.....	69
2.3.2.18.1	Schema.....	69
2.3.2.18.2	Attributes.....	69
2.3.2.18.3	Child Elements.....	70
2.3.2.19	FieldRefDefinitionView Type.....	70
2.3.2.19.1	Schema.....	70
2.3.2.19.2	Attributes.....	70
2.3.2.19.3	Child Elements.....	70
2.3.2.20	ViewStyleReference Type.....	70
2.3.2.20.1	Schema.....	71
2.3.2.20.2	Attributes.....	71
2.3.2.20.3	Child Elements.....	71
2.3.2.21	ViewFormatDefinitions Type.....	71
2.3.2.21.1	Schema.....	71
2.3.2.21.2	Attributes.....	71
2.3.2.21.3	Child Elements.....	71
2.3.2.22	FormatDefDefinition Type.....	71
2.3.2.22.1	Schema.....	71
2.3.2.22.2	Attributes.....	72
2.3.2.22.3	Child Elements.....	72
2.3.2.23	FormatDefinition Type.....	72
2.3.2.23.1	Schema.....	72
2.3.2.23.2	Attributes.....	72
2.3.2.23.3	Child Elements.....	72
2.3.2.24	MobileViewDefinition Type.....	72
2.3.2.24.1	Schema.....	72
2.3.2.24.2	Attributes.....	72
2.3.2.24.3	Child Elements.....	73
2.4	Content Type Schema Definitions.....	73
2.4.1	ContentTypeDefinition Type.....	73
2.4.1.1	Schema.....	73
2.4.1.2	Attributes.....	73
2.4.1.3	Child Elements.....	74
2.4.2	FieldRefDefinitionCTs Type.....	74
2.4.2.1	Schema.....	74
2.4.2.2	Attributes.....	75
2.4.2.3	Child Elements.....	75
2.4.3	FieldRefDefinitionCT Type.....	75

2.4.3.1	Schema	75
2.4.3.2	Attributes	76
2.4.3.3	Child Elements	76
2.4.4	ContentTypeDocumentTemplateDefinition Type	76
2.4.4.1	Schema	76
2.4.4.2	Attribute	76
2.4.4.3	Child Elements	76
2.4.5	ContentTypeReference Type	76
2.4.5.1	Schema	76
2.4.5.2	Attributes	77
2.4.5.3	Child Elements	77
2.4.6	ContentTypeReferences Type	77
2.4.6.1	Schema	77
2.4.6.2	Attributes	77
2.4.6.3	Child Elements	77
2.4.7	FolderReference Type	77
2.4.7.1	Schema	77
2.4.7.2	Attributes	78
2.4.7.3	Child Elements	78
2.4.8	ContentTypeDatabase Type	78
2.4.8.1	Schema	78
2.4.8.2	Attributes	78
2.4.8.3	Child Elements	78
2.4.9	ContentTypeDefinitionTP Type	78
2.4.9.1	Schema	78
2.4.9.2	Attributes	79
2.4.9.3	Child Elements	79
2.4.10	FieldDefinitionCTRemove Type	79
2.4.10.1	Schema	79
2.4.10.2	Attributes	79
2.4.10.3	Child Elements	80
2.4.11	XmlDocumentDefinition Type	80
2.4.11.1	Schema	80
2.4.11.2	Attributes	80
2.4.11.3	Child Elements	80
2.4.12	XmlDocumentDefinitionCollection Type	81
2.4.12.1	Schema	81
2.4.12.2	Attributes	81
2.4.12.3	Child Elements	81
2.5	Extensible Types	81
2.5.1	Content Type Custom Simple Types	81
2.5.1.1	customXsn Type	81
2.5.1.1.1	Schema	81
2.5.1.1.2	Attributes	82
2.5.1.1.3	Child Elements	82
2.5.1.2	FormDefinitions Type	82
2.5.1.2.1	Schema	82
2.5.1.2.2	Attributes	82
2.5.1.2.3	Child Elements	82
2.5.1.3	FormTemplateDefinitions Type	82
2.5.1.3.1	Schema	82
2.5.1.3.2	Attributes	83
2.5.1.3.3	Child Elements	83

2.5.1.4	FormUrlDefinitions Type	83
2.5.1.4.1	Schema	83
2.5.1.4.2	Attributes	83
2.5.1.4.3	Child Elements	83
2.5.1.5	NamespaceDefinition Type	83
2.5.1.5.1	Schema	84
2.5.1.5.2	Attributes	84
2.5.1.5.3	Child Elements	84
2.5.1.6	NamespaceDefinitions Type	84
2.5.1.6.1	Schema	84
2.5.1.6.2	Attributes	84
2.5.1.6.3	Child Elements	84
2.5.1.7	PolicyDirtyBag Type	84
2.5.1.7.1	Schema	84
2.5.1.7.2	Attributes	85
2.5.1.7.3	Child Elements	85
2.5.1.8	PolicyFeatureOperation Type	85
2.5.1.8.1	Schema	85
2.5.1.8.2	Attributes	85
2.5.1.8.3	Child Elements	85
2.5.1.9	Policy Type	85
2.5.1.9.1	Schema	86
2.5.1.9.2	Attributes	86
2.5.1.9.3	Child Elements	86
2.5.1.10	PolicyItem Type	86
2.5.1.10.1	Schema	86
2.5.1.10.2	Attributes	87
2.5.1.10.3	Child Elements	87
2.5.1.11	Barcode Type	88
2.5.1.11.1	Schema	88
2.5.1.11.2	Attributes	88
2.5.1.11.3	Child Elements	88
2.5.1.12	PolicyEventDefinition Type	88
2.5.1.12.1	Schema	88
2.5.1.12.2	Attributes	88
2.5.1.12.3	Child Elements	89
2.5.1.13	Label Type	89
2.5.1.13.1	Schema	89
2.5.1.13.2	Attributes	89
2.5.1.13.3	Child Elements	89
2.5.1.14	PolicySegmentDefinition Type	90
2.5.1.14.1	Schema	90
2.5.1.14.2	Attributes	90
2.5.1.14.3	Child Elements	90
2.5.1.15	Audit Type	90
2.5.1.15.1	Schema	91
2.5.1.15.2	Attributes	91
2.5.1.15.3	Child Elements	91
2.5.1.16	Schedules Type	91
2.5.1.16.1	Schema	91
2.5.1.16.2	Attributes	91
2.5.1.16.3	Child Elements	92
2.5.1.17	PolicyScheduleDefinition Type	92

2.5.1.17.1	Schema.....	92
2.5.1.17.2	Attributes.....	92
2.5.1.17.3	Child Elements.....	93
2.5.1.18	PolicyDataDefinition Type.....	93
2.5.1.18.1	Schema.....	93
2.5.1.18.2	Attributes.....	93
2.5.1.18.3	Child Elements.....	94
2.5.1.19	PolicyFormulaDefinition Type.....	94
2.5.1.19.1	Schema.....	94
2.5.1.19.2	Attributes.....	94
2.5.1.19.3	Child Elements.....	94
2.5.1.20	PolicyActionDefinition Type.....	95
2.5.1.20.1	Schema.....	95
2.5.1.20.2	Attributes.....	95
2.5.1.20.3	Child Elements.....	97
2.5.1.21	ReceiverDefinitions Type.....	97
2.5.1.21.1	Schema.....	97
2.5.1.21.2	Attributes.....	97
2.5.1.21.3	Child Elements.....	98
2.5.1.22	ReceiverDefinition Type.....	98
2.5.1.22.1	Schema.....	98
2.5.1.22.2	Attributes.....	98
2.5.1.22.3	Child Elements.....	98
<b>3</b>	<b>Structure Examples.....</b>	<b>100</b>
<b>4</b>	<b>Security.....</b>	<b>112</b>
4.1	Security Considerations for Implementers.....	112
4.2	Index of Security Fields.....	112
<b>5</b>	<b>Appendix A: Full XML Schema.....</b>	<b>113</b>
<b>6</b>	<b>Appendix B: Product Behavior.....</b>	<b>145</b>
<b>7</b>	<b>Change Tracking.....</b>	<b>147</b>
<b>8</b>	<b>Index.....</b>	<b>149</b>

# 1 Introduction

The Collaborative Application Markup Language (CAML) structure consists of XML-based formats for queries, lists, and content types in Windows SharePoint Services, as used by other protocols.

Sections 1.7 and 2 of this specification are normative and contain RFC 2119 language. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

### **GUID**

The following terms are defined in [\[MS-OFCGLOS\]](#):

**after event**  
**assembly**  
**audit log**  
**base view**  
**before event**  
**Boolean**  
**cascading style sheet (CSS)**  
**class name**  
**composite field index**  
**computed field**  
**content type**  
**content type group**  
**current user**  
**discussion board**  
**document**  
**Document Information Panel**  
**document library**  
**document template**  
**event handler**  
**event receiver**  
**feature**  
**field**  
**field definition**  
**field internal name**  
**file extension**  
**FilterDescriptor**  
**Finder**  
**font**  
**form**  
**form template**  
**friendly name**  
**front-end web server**  
**fully qualified class name**  
**group**  
**item**  
**item identifier**  
**list**  
**list form**  
**list item**

**list template**  
**lookup field**  
**major version**  
**mobile device**  
**moderated list**  
**paged view**  
**policy**  
**publishing level**  
**query**  
**record**  
**recurrence exception**  
**resource folder**  
**RSS item**  
**security scope**  
**server-relative URL**  
**site**  
**site collection**  
**strong name**  
**survey list**  
**toolbar**  
**top-level site**  
**Uniform Resource Locator (URL)**  
**Uniform Resource Name (URN)**  
**view**  
**Web Part**  
**Web Part zone**  
**workflow**  
**XML namespace prefix**

The following terms are specific to this document:

**control template:** A fragment of HTML and ASP.NET markup that customizes and extends the functionality of an ASP.NET control.

**document property:** A name/value pair that serves as metadata for a document.

**policy feature:** A type of rule that can be used within a policy to govern interactions with an object such as a document or item.

**retention action:** An action that occurs on an object, such as a document or site, in response to an event defined by a retention formula in a larger retention policy. Examples of retention actions are delete, move to a different location, and delete previous versions.

**retention formula:** A logical equation or function that is used to calculate when a retention action occurs on an object, such as a document or content type, as defined by a larger retention policy that applies to that object.

**retention schedule:** A sequence of stages that defines the retention lifecycle of an object such as a document, list item, list, content type, or site. Each stage consists of an event/action pair that specifies what action to perform on an object before or after that stage.

**retention stage:** One of a sequence of phases in a retention policy that defines the retention lifecycle of an object such as a document, list item, list, content type, or site. Each stage consists of an event/action pair that specifies what action to perform on an object before or after that stage.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[MS-WSSCAP] Microsoft Corporation, "[Windows SharePoint Services Collaborative Application Protocol](#)".

[MS-WSSFO2] Microsoft Corporation, "[Windows SharePoint Services \(WSS\): File Operations Database Communications Version 2 Protocol](#)".

[MS-WSSFO3] Microsoft Corporation, "[Windows SharePoint Services \(WSS\): File Operations Database Communications Version 3 Protocol](#)".

[MS-WSSTS] Microsoft Corporation, "[Windows SharePoint Services](#)".

[RFC1808] Fielding, R., "Relative Uniform Resource Locators", RFC 1808, June 1995, <http://www.rfc-editor.org/rfc/rfc1808.txt>

[RFC2068] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2068, January 1997, <http://www.ietf.org/rfc/rfc2068.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2234] Crocker, D., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 2234, November 1997, <http://www.ietf.org/rfc/rfc2234.txt>

[RFC3339] Klyne, G., and Newman, C., "Date and Time on the Internet: Timestamps", RFC 3339, July 2002, <http://www.ietf.org/rfc/rfc3339.txt>

[RSS2.0] Winer, D., "RSS 2.0 Specification", Fall 2002, version 2.0.1: July 2003, <http://cyber.law.harvard.edu/rss/rss.html>

[XML] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Fourth Edition)", W3C Recommendation, August 2006, <http://www.w3.org/TR/2006/REC-xml-20060816/>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

## 1.2.2 Informative References

[MSDN-SHPTSDK] Microsoft Corporation, "Windows SharePoint Services 3.0 SDK", <http://msdn.microsoft.com/en-us/library/ms441339.aspx>

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

## 1.3 Overview

This document specifies canonical XML definitions of components that are frequently used in communications between protocol clients and protocol servers. Such components include **lists**, **content types**, **queries**, and so on.

## 1.4 Relationship to Protocols and Other Structures

This structure specifies XML schemas, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), for data structures that are based on structures further described in [\[MS-WSSTS\]](#).

## 1.5 Applicability Statement

None.

## 1.6 Versioning and Localization

None.

## 1.7 Vendor-Extensible Fields

For complex types defined in this document, an implementation of protocol servers can optionally support reading, writing, and persisting additional arbitrary elements or attributes. Unless otherwise specified in the underlying schema definition, this capability is not to be used by vendors or by protocol server implementations to provide extensions to the schema specified in this document.

Several elements of the XML, as specified in [\[XML\]](#), formats that are specified in this document are designed for additional customization and extensibility.

### 1.7.1 XmlDocument on ContentTypeDefinition Type

The **ContentTypeDefinition** complex type, which is specified in **ContentTypeDefinition** (section [2.4.1](#)), can contain child **XmlDocumentDefinition** elements. Each **XmlDocument** element is identified by a unique namespace URI. Vendors can define additional **XmlDocument** elements with unique namespace URIs, and readers and writers persist these **XmlDocument** elements.

### 1.7.2 PolicyItem

The **PolicyItem** element, as specified in **PolicyItem Type** (section [2.5.1.10](#)), contains the settings for a **policy feature**. These settings include information that is required for all policy features, such as the identifier and name. This element is vendor-extensible through its **CustomData** child element.

In addition to vendor-extensible schemas, there are well known schema types specified in **PolicyItem Type Child Elements** (section [2.5.1.10.3](#)). One of these well known schemas is for the retention policy feature also has vendor-extensible fields for controlling the **retention formula** or

**retention action**, as specified in **PolicyDataDefinition** Type (section [2.5.1.18](#)) and **Schedules Type** (section [2.5.1.16](#)).

## 2 Structures

### 2.1 Common Simple Types

#### 2.1.1 AssemblyClass

This type specifies a **fully qualified class name** of a code-based implementation. This type is defined as follows:

```
<xs:simpleType name="AssemblyClass">
  <xs:restriction base="xs:string">
    <xs:maxLength value="255" />
  </xs:restriction>
</xs:simpleType>
```

#### 2.1.2 AssemblyStrongName

This type specifies a **strong name** of a code-based implementation. This type is defined as follows:

```
<xs:simpleType name="AssemblyStrongName">
  <xs:restriction base="xs:string">
    <xs:maxLength value="255" />
  </xs:restriction>
</xs:simpleType>
```

#### 2.1.3 FALSE\_Case\_Insensitive\_Else\_Anything

This type specifies a **Boolean** value. For more details, see [\[MS-WSSFO2\]](#) section 2.2.8.2.1.

#### 2.1.4 IntNonNegative

This type specifies a non-negative integer. This type is defined as follows:

```
<xs:simpleType name="IntNonNegative">
  <xs:restriction base="xs:int">
    <xs:minInclusive value="0" />
  </xs:restriction>
</xs:simpleType>
```

#### 2.1.5 RelativeFilePath

This type specifies the location of a template file stored on the physical disk of the **front-end Web server**. This type is defined as follows:

```
<xs:simpleType name="RelativeFilePath">
  <xs:restriction base="xs:string" >
    <xs:minLength value="0" />
  </xs:restriction>
</xs:simpleType>
```

### 2.1.6 RelativeUrl

This type specifies a relative [URL \[RFC1808\]](#) relative to a [site \(2\)](#). This type is defined as follows:

```
<xs:simpleType name="RelativeUrl">
  <xs:restriction base="xs:string" >
    <xs:maxLength value="255" />
    <xs:minLength value="0" />
  </xs:restriction>
</xs:simpleType>
```

### 2.1.7 String255Chars

This type specifies a string with a length in the range from zero through 255 characters. This type is defined as follows:

```
<xs:simpleType name="String255Chars">
  <xs:restriction base="xs:string">
    <xs:maxLength value="255" />
    <xs:minLength value="0" />
  </xs:restriction>
</xs:simpleType>
```

### 2.1.8 TRUE\_Case\_Insensitive\_Else\_Anything

This type specifies a Boolean value. This type is defined as follows:

```
<xs:simpleType name="TRUE_Case_Insensitive_Else_Anything">
  <xs:restriction base="xs:string">
    <xs:pattern value="([Tt][Rr][Uu][Ee])|.*" />
  </xs:restriction>
</xs:simpleType>
```

### 2.1.9 TRUE\_Case\_Sensitive\_Else\_Anything

This type specifies a Boolean value. For more details, see [\[MS-WSSFO2\]](#), section [2.2.8.2.12](#).

### 2.1.10 TRUE\_If\_Present

This type specifies a Boolean value. For more details, see [\[MS-WSSFO2\]](#) section 2.2.8.2.10.

### 2.1.11 TRUE\_NegOne\_Else\_Anything

This type specifies a Boolean value. This type is defined as follows:

```
<xs:simpleType name="TRUE_NegOne_Else_Anything">
  <xs:restriction base="xs:string">
    <xs:pattern value="(TRUE)|(\-1)|.*" />
  </xs:restriction>
</xs:simpleType>
```

### 2.1.12 TRUEFALSE

This type specifies a Boolean value. For more details, see [\[MS-WSSFO2\]](#) section 2.2.8.2.11.

### 2.1.13 truefalse\_Only\_Lowercase

This type specifies a Boolean value. This type is defined as follows:

```
<xs:simpleType name="truefalse_Only_Lowercase">
  <xs:restriction base="xs:boolean">
    <xs:pattern value="true|false"/>
  </xs:restriction>
</xs:simpleType>
```

### 2.1.14 UniqueIdentifierWithoutBracesOrEmpty

This type specifies a **GUID**. This type is defined as follows:

```
<xs:simpleType name="UniqueIdentifierWithoutBracesOrEmpty">
  <xs:restriction base="xs:string">
    <xs:pattern value="[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}|"/>
    <xs:minLength value="0"/>
  </xs:restriction>
</xs:simpleType>
```

### 2.1.15 UniqueIdentifierWithoutBraces

This type specifies a GUID. This type is defined as follows:

```
<xs:simpleType name="UniqueIdentifierWithoutBraces">
  <xs:restriction base="UniqueIdentifierWithoutBracesOrEmpty">
    <xs:minLength value="1"/>
  </xs:restriction>
</xs:simpleType>
```

### 2.1.16 UniqueIdentifierWithBraces

This type specifies a GUID. This type is defined as follows:

```
<xs:simpleType name="UniqueIdentifierWithBraces">
  <xs:restriction base="xs:string">
    <xs:pattern value="\{[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\}"/>
  </xs:restriction>
</xs:simpleType>
```

### 2.1.17 UniqueIdentifierWithBracesOrEmpty

This type [<1>](#) specifies a GUID. This type is defined as follows:

```
<xs:simpleType name="UniqueIdentifierWithBracesOrEmpty">
```

```

    <xs:restriction base="xs:string">
      <xs:pattern value="\{[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\}" />
    </xs:restriction>
  </xs:simpleType>

```

### 2.1.18 UniqueIdentifierWithOrWithoutBraces

This type specifies a GUID. For more details, see [\[MS-WSSFO2\]](#) section 2.2.8.2.14.

### 2.1.19 UniqueIdentifierWithOrWithoutBracesWithOrWithoutDashes

This type specifies a GUID. This type is defined as follows:

```

<xs:simpleType name="UniqueIdentifierWithOrWithoutBracesWithOrWithoutDashes">
  <xs:restriction base="xs:string">
    <xs:pattern value="\{?[0-9a-fA-F]{8}\-?[0-9a-fA-F]{4}\-?[0-9a-fA-F]{4}\-?[0-9a-fA-F]{4}\-?[0-9a-fA-F]{12}\}?" />
  </xs:restriction>
</xs:simpleType>

```

## 2.2 Query Types

A query specifies a set of restrictions and preferences for returning a set of **list items** from a larger collection of list items. For these types, a server processes a query and applies the specified criteria to return list items from a larger set of list items.

### 2.2.1 Simple Types

#### 2.2.1.1 ListJoinJoin Type

The **ListJoinJoinType** type specifies the type of the join.

```

<xs:simpleType name="ListJoinJoinType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="LEFT" />
    <xs:enumeration value="INNER" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes possible values.

Value	Description
LEFT	A left outer join
INNER	An inner join

### 2.2.2 Complex Types

The following XML Schema complex type definitions are specific to query operations.

### 2.2.2.1 CamlQueryRoot Type

The **CamlQueryRoot** type specifies conditions and preferences for returning list items from a larger set of list items.

#### 2.2.2.1.1 Schema

```
<xs:complexType name="CamlQueryRoot">
  <xs:all>
    <xs:element name="Where" type="LogicalJoinDefinition" minOccurs="0" maxOccurs="1" />
    <xs:element name="OrderBy" type="OrderByDefinition" minOccurs="0" maxOccurs="1" />
    <xs:element name="GroupBy" type="GroupByDefinition" minOccurs="0" maxOccurs="1" />
    <xs:element name="WithIndex" type="LogicalWithIndexDefinition" minOccurs="0"
maxOccurs="1" />
  </xs:all>
</xs:complexType>
```

#### 2.2.2.1.2 Attributes

None.

#### 2.2.2.1.3 Child Elements

**Where:** Specifies a set of conditions to filter a list of **items** retrieved from a set of items.

**WithIndex:** Specifies a set of conditions and a **composite field index** to filter a list of items retrieved from a set of items.

**OrderBy:** Specifies a set of **fields (1)** to sort results obtained from a query.

**GroupBy:** Specifies a set of fields (1) to group results obtained from a query.

### 2.2.2.2 LogicalJoinDefinition Type

The **LogicalJoinDefinition** type specifies a restriction on the items returned by the query. When this element is present and has child elements, the server **MUST** return only list items that satisfy the conditions specified by those child elements. When there are no child elements, no additional conditions apply to the query.

#### 2.2.2.2.1 Schema

```
<xs:complexType name="LogicalJoinDefinition">
  <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element name="And" type="ExtendedLogicalJoinDefinition" />
    <xs:element name="BeginsWith" type="LogicalTestDefinition" />
    <xs:element name="Contains" type="LogicalTestDefinition" />
    <xs:element name="DateRangesOverlap" type="LogicalTestDefinitionDateRange" />
    <xs:element name="Eq" type="LogicalTestDefinition" />
    <xs:element name="Geq" type="LogicalTestDefinition" />
    <xs:element name="Gt" type="LogicalTestDefinition" />
    <xs:element name="In" type="LogicalTestInValuesDefinition" />
    <xs:element name="Includes" type="LogicalTestDefinition" />
    <xs:element name="IsNull" type="LogicalNullDefinition" />
    <xs:element name="IsNotNull" type="LogicalNullDefinition" />
    <xs:element name="Leq" type="LogicalTestDefinition" />
    <xs:element name="Lt" type="LogicalTestDefinition" />
  </xs:choice>
</xs:complexType>
```

```

<xs:element name="Membership" type="MembershipDefinition" />
<xs:element name="Neq" type="LogicalTestDefinition" />
<xs:element name="NotIncludes" type="LogicalTestDefinition" />
<xs:element name="Or" type="ExtendedLogicalJoinDefinition" />
</xs:choice>
</xs:complexType>

```

#### 2.2.2.2.2 Attributes

None.

#### 2.2.2.2.3 Child Elements

**Eq:** Specifies whether the value of a list item for the field (1) specified by the **FieldRef** element is equal to the **Value** element.

**Neq:** Specifies whether the value of a list item for the field (1) specified by the **FieldRef** element is not equal to the **Value** element.

**Gt:** Specifies whether the value of a list item for the field (1) specified by the **FieldRef** element is greater than the **Value** element.

**Geq:** Specifies whether the value of a list item for the field (1) specified by the **FieldRef** element is greater than or equal to the **Value** element.

**Lt:** Specifies whether the value of a list item for the field (1) specified by the **FieldRef** element is less than the **Value** element.

**Leq:** Specifies whether the value of a list item for the field (1) specified by the **FieldRef** element is less than or equal to the **Value** element.

**BeginsWith:** Specifies whether the value of a list item for the field (1) specified by the **FieldRef** element begins with the **Value** element.

**Contains:** Specifies whether the **Value** element appears in a list item field referred to by the **FieldRef** element.

**Includes:** If the specified field (1) is a **lookup field** that allows multiple values, this element specifies whether the **Value** element is in the list item for the field (1) specified by the **FieldRef** element.

**NotIncludes:** If the specified field (1) is a **lookup field** that allows multiple values, this element specifies whether the **Value** element is not in the list item for the field (1) specified by the **FieldRef** element.

**DateRangesOverlap:** Specifies whether a date range defined by the specified list item fields (1) overlaps with a date range defined by a specified value.

The first date range is defined by at least two, and at most three, **FieldRef** elements. Each **FieldRef** element MUST refer to one of the following field types, or the protocol server MUST return an error:

- **DateTime** field (1)
- **Lookup** field with a target **DateTime** field

- **Calculated** field (1) with a formula that returns a **DateTime** value

The first **FieldRef** element represents the beginning of a time period. The second **FieldRef** element represents the end of a time period. The third **FieldRef** element, when present, represents the start date and time of a **recurrence exception**.

The second date range is defined by the **Value** element.

When the **Value** element has the child **Month**, the comparison **MUST** apply the following interpretation to the date range:

- If the site (2) uses the Gregorian calendar, the date range begins six days before the first day of the current month and ends six days after the last day of the current month.
- For other calendars, the date range begins 30 days before the first day of the current month and ends 30 days after the last day of the current month.

See **ValueDefinitionDateRange Type** (section [2.2.2.12](#)) for more information.

**IsNull**: Specifies that a list item field (1) specified by the **FieldRef** element is NULL.

**IsNotNull**: Specifies that a list item field (1) specified by the **FieldRef** element is not NULL.

**Membership**: Specifies a condition on the value of a list item for the field (1) specified by the **FieldRef** element.

**FieldRef** **MUST** refer to a **lookup** field, **Counter** field, or **integer** field (1).

The **Type** attribute of this element identifies the membership test to perform. The following table describes possible values.

Value	Description
<b>SPWeb.AllUsers</b>	Specifies whether the value of a list item for the field (1) specified by the <b>FieldRef</b> element is the identifier of a user who is either a member of the site (2) or who has browsed to the site (2) as an authenticated member of a domain group in the site (2).
<b>SPGroup</b>	Specifies whether the value of a list item for the field (1) specified by the <b>FieldRef</b> element is the identifier of a <b>group (2)</b> of which the <b>current user</b> is a member. The <b>ID</b> attribute of the <b>Membership</b> element <b>MUST</b> be present and non-empty. The <b>ID</b> attribute identifies a group. The current user <b>MUST</b> have permission to view the membership of the group that has the specified identifier.
<b>SPWeb.Groups</b>	Specifies whether a list item field (1) specified by the <b>FieldRef</b> element is the identifier of a group in the site (2).
<b>CurrentUserGroups</b>	Specifies whether a list item field (1) specified by the <b>FieldRef</b> element is the identifier of a group of which the current user is a member.
<b>SPWeb.Users</b>	Specifies whether a list item field (1) specified by the <b>FieldRef</b> element is the identifier of a user that has been explicitly granted permission to the site (2).

**And**: Specifies whether both of the conditions described by the child elements are satisfied.

**Or**: Specifies whether at least one of the conditions described by its child elements is satisfied.

**In:** Specifies whether the value of a list item for the field (1) specified by the **FieldRef** element is equal to one of the **Values** element.

### 2.2.2.3 OrderByDefinition Type

The **OrderByDefinition** type specifies conditions for the final sort order for the result set from a query.

#### 2.2.2.3.1 Schema

```
<xs:complexType name="OrderByDefinition">
  <xs:sequence>
    <xs:element name="FieldRef" type="FieldRefDefinitionOrderBy" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Override" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE"/>
</xs:complexType>
```

#### 2.2.2.3.2 Attributes

**Override:** If **Override** is **true**, the server MUST NOT give additional sort order conditions not specified under the **CamlQueryRoot** higher priority than the conditions specified under the **CamlQueryRoot**.

#### 2.2.2.3.3 Child Elements

**FieldRef:** Specifies the name of a field (1) to use for ordering.

#### 2.2.2.4 FieldRefDefinitionOrderBy Type

The **FieldRefDefinitionOrderBy** type specifies a field (1) to use in an **OrderByDefinition**.

#### 2.2.2.4.1 Schema

```
<xs:complexType name="FieldRefDefinitionOrderBy">
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="Name" type="xs:string" use="optional" />
  <xs:attribute name="Ascending" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE" />
</xs:complexType>
```

#### 2.2.2.4.2 Attributes

**ID:** Identifier of the field (1) to use for ordering.

**Name:** **Field internal name** of the field (1) or name of the projected field (1) specified in the **ProjectedFields** element to use for ordering.

When both **ID** and **Name** are present, the server MUST use **ID** to match the field (1).

**Ascending:** Specifies whether this field (1) is sorted in increasing order, based on sorting rules for the field type.

### 2.2.2.4.3 Child Elements

None.

### 2.2.2.5 GroupByDefinition Type

The **GroupByDefinition** type specifies the groups into which list items are to be placed to create the final result set. The groups are created by combining into a single group all the items that have identical values for a particular field (1) or combination of fields (1) as specified by the **FieldRef** element.

#### 2.2.2.5.1 Schema

```
<xs:complexType name="GroupByDefinition">
  <xs:sequence>
    <xs:element name="FieldRef" type="FieldRefDefinitionGroupBy" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Collapse" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE"/>
  <xs:attribute name="GroupLimit" type="IntNonNegative" use="optional" default="100"/>
</xs:complexType>
```

#### 2.2.2.5.2 Attributes

**Collapse:** If **true** and there are **computed fields** in the **ViewFields** element, the number of rows present in the result set MUST NOT be affected by the **GroupBy** element. If there are no computed fields in the **ViewFields** section, the number of rows present in the result set MAY be restricted to the number of unique tuples, where a tuple is a set of field values. Otherwise, the number of rows in the result set MUST NOT be affected by the **GroupBy** element.

**GroupLimit:** Specifies the number of groups for a **paged view**. If the **Collapse** attribute is set to **true** and there are no computed fields in the **ViewFields** section, the number of groups for a paged view can be restricted to the specified value.

#### 2.2.2.5.3 Child Elements

**FieldRef:** Specifies the name of a field (1) to use for grouping.

### 2.2.2.6 FieldRefDefinitionGroupBy Type

The **FieldRefDefinitionGroupBy** type specifies a field (1) whose value can be used to perform a grouping through **GroupByDefinition**.

#### 2.2.2.6.1 Schema

```
<xs:complexType name="FieldRefDefinitionGroupBy">
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="Name" type="xs:string" />
  <xs:attribute name="Ascending" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE" />
</xs:complexType>
```

### 2.2.2.6.2 Attributes

**ID:** Identifier of the field (1) to use for grouping.

**Name:** Field internal name of the field (1) to use for grouping.

**Ascending:** Specifies whether this field (1) is sorted in increasing order, based on sorting rules for the field type.

When both **ID** and **Name** are present, the attributes MUST identify the same field (1).

### 2.2.2.6.3 Child Elements

None.

### 2.2.2.7 ExtendedLogicalJoinDefinition Type

The **ExtendedLogicalJoinDefinition** type specifies a restriction on the list items returned by the query. When this element is present and contains child elements, the server MUST return only list items that satisfy the conditions specified by those child elements.

#### 2.2.2.7.1 Schema

```
<xs:complexType name="ExtendedLogicalJoinDefinition">
  <xs:sequence>
    <xs:choice minOccurs="2" maxOccurs="2">
      <xs:element name="And" type="ExtendedLogicalJoinDefinition" />
      <xs:element name="BeginsWith" type="LogicalTestDefinition" />
      <xs:element name="Contains" type="LogicalTestDefinition" />
      <xs:element name="DateRangesOverlap" type="LogicalTestDefinitionDateRange" />
      <xs:element name="Eq" type="LogicalTestDefinition" />
      <xs:element name="Geq" type="LogicalTestDefinition" />
      <xs:element name="Gt" type="LogicalTestDefinition" />
      <xs:element name="In" type="LogicalTestInValuesDefinition" />
      <xs:element name="Includes" type="LogicalTestDefinition" />
      <xs:element name="IsNull" type="LogicalNullDefinition" />
      <xs:element name="IsNotNull" type="LogicalNullDefinition" />
      <xs:element name="Leq" type="LogicalTestDefinition" />
      <xs:element name="Lt" type="LogicalTestDefinition" />
      <xs:element name="Membership" type="MembershipDefinition" />
      <xs:element name="Neq" type="LogicalTestDefinition" />
      <xs:element name="NotIncludes" type="LogicalTestDefinition" />
      <xs:element name="Or" type="ExtendedLogicalJoinDefinition" />
    </xs:choice>
  </xs:sequence>
</xs:complexType>
```

#### 2.2.2.7.2 Attributes

None.

#### 2.2.2.7.3 Child Elements

See child elements of **LogicalJoinDefinition Type** (section [2.2.2.2](#)).

### 2.2.2.8 LogicalTestDefinition Type

The **LogicalTestDefinition** type compares a list item field value and another specified value.

#### 2.2.2.8.1 Schema

```
<xs:complexType name="LogicalTestDefinition">
  <xs:all>
    <xs:element name="FieldRef" type="FieldRefDefinitionQueryTest" minOccurs="1"
maxOccurs="1" />
    <xs:element name="Value" type="ValueDefinition" minOccurs="1" maxOccurs="1" />
  </xs:all>
</xs:complexType>
```

#### 2.2.2.8.2 Attributes

None.

#### 2.2.2.8.3 Child Elements

**FieldRef**: List item field (1) or projected field (1) specified in the **ProjectedFields** element that contains the value to be compared.

**Value**: Value to be compared to the list item for the field (1) specified by the **FieldRef** attribute.

### 2.2.2.9 ValueDefinition Type

The **ValueDefinition** type specifies a value that is included in a comparison.

#### 2.2.2.9.1 Schema

```
<xs:complexType name="ValueDefinition" mixed="true">
  <xs:sequence>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:any namespace="##any" processContents="skip" />
    </xs:choice>
  </xs:sequence>
  <xs:attribute name="Type" type="xs:string" use="optional" />
</xs:complexType>
```

#### 2.2.2.9.2 Attributes

**Type**: Data type of the value.

#### 2.2.2.9.3 Child Elements

None.

### 2.2.2.10 FieldRefDefinitionQueryTest Type

The **FieldRefDefinitionQueryTest** type specifies a field (1) to use in a query comparison.

### 2.2.2.10.1 Schema

```
<xs:complexType name="FieldRefDefinitionQueryTest">
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="Name" type="xs:string" use="optional" />
  <xs:attribute name="LookupId" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE" />
</xs:complexType>
```

### 2.2.2.10.2 Attributes

**ID:** Identifier of the field (1) to be used in the query.

**Name:** Field internal name of the field or the name of the projected field specified in the **ProjectedFields** element to be used in the query.

When both **ID** and **Name** are present, the server MUST use **ID** to match the field (1).

**LookupId:** If **true** and the specified field (1) is a **lookup** field, the query MUST include the **item identifier** of the lookup target. When the specified field (1) is not a **lookup** field, the server MUST ignore this attribute.

### 2.2.2.10.3 Child Elements

None.

### 2.2.2.11 LogicalTestDefinitionDateRange Type

The **LogicalTestDefinitionDateRange** type defines a comparison of two or three fields (1) that specify a first time period with a value that specifies a second time period.

#### 2.2.2.11.1 Schema

```
<xs:complexType name="LogicalTestDefinitionDateRange">
  <xs:sequence>
    <xs:element name="FieldRef" type="FieldRefDefinitionQueryDate" minOccurs="2"
maxOccurs="3" />
    <xs:element name="Value" type="ValueDefinitionDateRange" minOccurs="1" maxOccurs="1" />
  </xs:sequence>
</xs:complexType>
```

#### 2.2.2.11.2 Attributes

None.

#### 2.2.2.11.3 Child Elements

**FieldRef:** List item that specifies the beginning of the time period.

**FieldRef:** List item that specifies the end of the time period.

**FieldRef:** When present, the list item field that identifies a recurrence exception.

**Value:** Time period to be compared.

### 2.2.2.12 ValueDefinitionDateRange Type

The **ValueDefinitionDateRange** type specifies a value that is included in a date range comparison.

#### 2.2.2.12.1 Schema

```
<xs:complexType name="ValueDefinitionDateRange" mixed="true">
  <xs:sequence>
    <xs:choice minOccurs="0" maxOccurs="1">
      <xs:element name="Month">
        <xs:complexType />
      </xs:element>
      <xs:element name="Now">
        <xs:complexType />
      </xs:element>
      <xs:element name="Today">
        <xs:complexType />
      </xs:element>
      <xs:element name="Week">
        <xs:complexType />
      </xs:element>
    </xs:choice>
  </xs:sequence>
  <xs:attribute name="Type" type="xs:string" use="optional" />
  <xs:attribute name="IncludeTimeValue" type="TRUEFALSE" use="optional" />
  <xs:attribute name="StorageTZ" type="TRUEFALSE" use="optional" />
</xs:complexType>
```

#### 2.2.2.12.2 Attributes

**Type:** Data type of the value.

**IncludeTimeValue:** Specifies whether the value is interpreted as a date and time value or compared as a date-only value.

**StorageTZ:** Specifies whether the **DateTime** value is interpreted in Coordinated Universal Time (UTC).

#### 2.2.2.12.3 Child Elements

An element of this type **MUST** contain one of the following:

- A string value in the following format, specified using the syntax description notation specified in [\[RFC2234\]](#) and [\[RFC3339\]](#). If the string is missing or cannot be parsed in this format, the server **MUST** use the current day, in site local time.

date-fullyear date-month date-mday time-hour time-minute time-second "Z"

- A child element that defines the date range, as described in the following table.

Element	Description
<b>Today</b>	Date range is the current day, in site local time.
<b>Week</b>	Date range is the current week, in site local time.

Element	Description
<b>Month</b>	Date range is the current month, in site local time.
<b>Now</b>	Date range begins with the current day and ends two years after the current day, in site local time.

### 2.2.2.13 FieldRefDefinitionQueryDate Type

The **FieldRefDefinitionQueryDate** type specifies a field (1) to use in a query date comparison.

#### 2.2.2.13.1 Schema

```
<xs:complexType name="FieldRefDefinitionQueryDate">
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="Name" type="xs:string" use="optional" />
</xs:complexType>
```

#### 2.2.2.13.2 Attributes

**ID:** Identifier of the field (1) to be used in the query.

**Name:** Field internal name of the field (1) or the name of the projected field (1) specified in the **ProjectedFields** element to be used in the query.

When both **ID** and **Name** are present, the reader **MUST** use **ID** to match the field (1).

#### 2.2.2.13.3 Child Elements

None.

### 2.2.2.14 LogicalNullDefinition Type

The **LogicalNullDefinition** type describes a comparison of a field (1) to NULL.

#### 2.2.2.14.1 Schema

```
<xs:complexType name="LogicalNullDefinition">
  <xs:all>
    <xs:element name="FieldRef" type="FieldRefDefinitionQueryNull" minOccurs="1"
maxOccurs="1" />
  </xs:all>
</xs:complexType>
```

#### 2.2.2.14.2 Attributes

None.

#### 2.2.2.14.3 Child Elements

**FieldRef:** A reference to a field (1) whose value is to be used for the comparison.

### 2.2.2.15 FieldRefDefinitionQueryNull Type

The **FieldRefDefinitionQueryNull** type specifies a field (1) to use in a null comparison.

#### 2.2.2.15.1 Schema

```
<xs:complexType name="FieldRefDefinitionQueryNull">
  <xs:attribute name="Name" type="xs:string" use="required" />
</xs:complexType>
```

#### 2.2.2.15.2 Attributes

**Name:** Field internal name of the field (1) or name of the projected field (1) specified in the **ProjectedFields** element to be included.

#### 2.2.2.15.3 Child Elements

None.

### 2.2.2.16 MembershipDefinition Type

The **MembershipDefinition** type defines a comparison of membership in a group.

#### 2.2.2.16.1 Schema

```
<xs:complexType name="MembershipDefinition">
  <xs:complexContent>
    <xs:extension base="LogicalNullDefinition">
      <xs:attribute name="Type" type="xs:string" use="optional" />
      <xs:attribute name="ID" type="xs:integer" use="optional" />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

#### 2.2.2.16.2 Attributes

**ID:** Integer that specifies the field (1) to be included.

**Type:** Specifies the type of membership. See **LogicalJoinDefinition Type** (section [2.2.2.2](#)) for more information.

#### 2.2.2.16.3 Child Elements

None.

### 2.2.2.17 LogicalTestInValuesDefinition Type

The **LogicalTestInValuesDefinition** type describes a comparison between the value of a list item field and a collection of specified values.

#### 2.2.2.17.1 Schema

```
<xs:complexType name="LogicalTestInValuesDefinition">
```

```

    <xs:all>
      <xs:element name="FieldRef" type="FieldRefDefinitionQueryTest" minOccurs="1"
maxOccurs="1" />
      <xs:element name="Values" type="ValueDefinitionCollection" minOccurs="1" maxOccurs="1"
/>
    </xs:all>
  </xs:complexType>

```

### 2.2.2.17.2 Attributes

None.

### 2.2.2.17.3 Child Elements

**FieldRef:** A reference to a field (1) whose value is to be used for the comparison.

**Values:** A collection of values to be compared to the value of the list item for the field (1) specified by the **FieldRef** attribute.

### 2.2.2.18 ValueDefinitionCollection Type

The **ValueDefinitionCollection** type specifies a collection of values that are included in a comparison.

#### 2.2.2.18.1 Schema

```

<xs:complexType name="ValueDefinitionCollection">
  <xs:sequence>
    <xs:element name="Value" type="ValueDefinition" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

```

#### 2.2.2.18.2 Attributes

None.

#### 2.2.2.18.3 Child Elements

**Value:** Specifies a value in the collection.

### 2.2.2.19 ProjectedFieldsDefinitionType

The **ProjectedFieldsDefinitionType** type specifies the fields (1) to project from the joined lists as specified by the **Joins** element of the view.

#### 2.2.2.19.1 Schema

```

<xs:complexType name="ProjectedFieldsDefinitionType">
  <xs:sequence>
    <xs:element name="Field" type="ProjectedFieldDefinitionType" minOccurs="1"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

```

### 2.2.2.19.2 Attributes

None.

### 2.2.2.19.3 Child Elements

**Field:** Specifies a **field definition**.

### 2.2.2.20 ProjectedFieldDefinitionType

The **ProjectedFieldDefinitionType** specifies a field (1) to project from the joined lists as specified by the **Joins** or the **FieldRef** element of the view.

#### 2.2.2.20.1 Schema

```
<xs:complexType name="ProjectedFieldDefinitionType">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="ShowField" type="xs:string" use="required" />
  <xs:attribute name="Type" type="xs:string" use="required" fixed="Lookup" />
  <xs:attribute name="List" type="xs:string" />
  <xs:attribute name="FieldRef" type="xs:string" />
</xs:complexType>
```

#### 2.2.2.20.2 Attributes

**Name:** String that identifies the field (1) in its list (2).

**ShowField:** Field internal name of the field (1) to project from the list (2) specified by either the **List** or the **FieldRef** attribute.

**Type:** The type of field (1).

**List:** Specifies the list (2) from which field (1) specified by **ShowField** MUST be projected. The value of the attribute MUST be equal to the **ListAlias** attribute of one of the joined lists specified by the **Joins** element of the view.

**FieldRef:** Field internal name of the **lookup** field of the list for which the query is specified. Target list of this **lookup** field specifies a list that MUST be used to project **ShowField**. When the **FieldRef** attribute is specified, the **Joins** element of the view MUST NOT be used for projection of **ShowField**.

Either the **List** or the **FieldRef** attributes can be present, and at least one of them MUST be specified.

### 2.2.2.21 ListJoinsDefinitionType

The **ListJoinsDefinitionType** type specifies the list of joins between lists.

#### 2.2.2.21.1 Schema

```
<xs:complexType name="ListJoinsDefinitionType">
  <xs:sequence>
    <xs:element name="Join" type="ListJoinDefinitionType" minOccurs="1"
      maxOccurs="unbounded" />
  </xs:sequence>
```

```
</xs:complexType>
```

#### 2.2.2.21.2 Attributes

None.

#### 2.2.2.21.3 Child Elements

**Join:** Specifies a join between two lists.

#### 2.2.2.22 ListJoinDefinitionType

The **ListJoinDefinitionType** type specifies a join between two lists.

##### 2.2.2.22.1 Schema

```
<xs:complexType name="ListJoinDefinitionType">
  <xs:choice>
    <xs:element name="Eq" type="ListJoinConditionDefinitionType" />
  </xs:choice>
  <xs:attribute name="Type" type="ListJoinJoinType" default="LEFT" />
  <xs:attribute name="ListAlias" type="xs:string" />
</xs:complexType>
```

##### 2.2.2.22.2 Attributes

**Type:** Specifies the type of join.

**ListAlias:** Specifies a temporary name to use for the right list of the join when running a query. The value **MUST** be unique across all **Join** elements in the query.

##### 2.2.2.22.3 Child Elements

**Eq:** Specifies the join condition that values of the fields specified by the two **FieldRef** elements are equal.

#### 2.2.2.23 ListJoinConditionDefinitionType

The **ListJoinConditionDefinitionType** type specifies the condition of the list join.

##### 2.2.2.23.1 Schema

```
<xs:complexType name="ListJoinConditionDefinitionType">
  <xs:sequence>
    <xs:element name="FieldRef" minOccurs="2" maxOccurs="2" />
  </xs:sequence>
</xs:complexType>
```

##### 2.2.2.23.2 Attributes

None.

### 2.2.2.23.3 Child Elements

**FieldRef:** There are two **FieldRef** elements, one type is **ListJoinConditionSourceFieldDefinitionType** and the other is **ListJoinConditionTargetFieldDefinitionType**. Each element specifies one of the fields (1) to be used in the join condition.

### 2.2.2.24 ListJoinConditionSourceFieldDefinition Type

The **ListJoinConditionSourceFieldDefinitionType** type specifies the field (1) of the left list that is involved in the join condition.

#### 2.2.2.24.1 Schema

```
<xs:complexType name="ListJoinConditionSourceFieldDefinitionType">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="RefType" type="xs:string" use="required" fixed="Id" />
  <xs:attribute name="List" type="xs:string" />
</xs:complexType>
```

#### 2.2.2.24.2 Attributes

**Name:** Field internal name of the field (1), which MUST be a **lookup** field of the left list of the join.

**RefType:** Specifies whether the value to be used is the value of **Id** field (1) of the list item or the value of the field (1).

**List:** Specifies the left list of the join. The value of the attribute MUST be equal to the **ListAlias** attribute of one of the joined lists specified by the **Joins** element of the view.

### 2.2.2.25 ListJoinConditionTargetFieldDefinition Type

The **ListJoinConditionTargetFieldDefinitionType** type specifies a field (1) of the right list that is involved in the join condition.

#### 2.2.2.25.1 Schema

```
<xs:complexType name="ListJoinConditionTargetFieldDefinitionType">
  <xs:attribute name="Name" type="xs:string" use="required" fixed="Id" />
  <xs:attribute name="List" type="xs:string" use="required" />
</xs:complexType>
```

#### 2.2.2.25.2 Attributes

**Name:** Specifies the field internal name of the field (1) used in the join condition.

**List:** Specifies the right list of the join. The value of this attribute MUST be the same as the value of the **ListAlias** attribute of the containing **Join** element.

### 2.2.2.26 LogicalWithIndexDefinition Type

The **LogicalWithIndexDefinition** type specifies a restriction on the items returned by the query. When this element is present and contains child elements, the server MUST return only list items

that satisfy the conditions specified by those child elements. When there are no child elements, no additional conditions apply to the query.

### 2.2.2.26.1 Schema

```
<xs:complexType name="LogicalWithIndexDefinition">
  <xs:choice minOccurs="1" maxOccurs="1">
    <xs:element name="And" type="ExtendedLogicalJoinDefinitionWithIndex" />
    <xs:element name="Eq" type="LogicalTestDefinition" />
  </xs:choice>
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="required" />
</xs:complexType>
```

### 2.2.2.26.2 Attributes

**ID**: Identifier of the composite field index to use when evaluating the conditions specified by the child elements of the **LogicalWithIndexDefinition**. The **ID** MUST refer to a composite field index that is defined for the list.

### 2.2.2.26.3 Child Elements

**And**: Specifies whether both of the conditions described by its child elements are satisfied.

**Eq**: Specifies whether a list item field (1) specified by the **FieldRef** element is equal to the **Value** element.

### 2.2.2.27 ExtendedLogicalJoinDefinitionWithIndex Type

The **ExtendedLogicalJoinDefinitionWithIndex** type specifies a restriction on the list items returned by the query, using the composite field index identified by the **ID** attribute of the parent **LogicalWithIndexDefinition**. When this element is present and has child elements, the server MUST return only list items that satisfy the conditions specified by those child elements. Any **FieldRef** element in the conditions specified by the child elements MUST refer to a field (1) that is included in the composite field index.

### 2.2.2.27.1 Schema

```
<xs:complexType name="ExtendedLogicalJoinDefinitionWithIndex">
  <xs:choice>
    <xs:sequence>
      <xs:element name="Eq" type="LogicalTestDefinition" />
      <xs:choice minOccurs="1" maxOccurs="1">
        <xs:element name="Geq" type="LogicalTestDefinition" />
        <xs:element name="Gt" type="LogicalTestDefinition" />
        <xs:element name="Eq" type="LogicalTestDefinition" />
        <xs:element name="In" type="LogicalTestInValuesDefinition" />
        <xs:element name="Leq" type="LogicalTestDefinition" />
        <xs:element name="Lt" type="LogicalTestDefinition" />
      </xs:choice>
    </xs:sequence>
    <xs:sequence>
      <xs:choice minOccurs="1" maxOccurs="1">
        <xs:element name="Geq" type="LogicalTestDefinition" />
        <xs:element name="Gt" type="LogicalTestDefinition" />
        <xs:element name="In" type="LogicalTestInValuesDefinition" />
      </xs:choice>
    </xs:sequence>
  </xs:choice>
```

```

        <xs:element name="Leq" type="LogicalTestDefinition" />
        <xs:element name="Lt" type="LogicalTestDefinition" />
    </xs:choice>
    <xs:element name="Eq" type="LogicalTestDefinition" />
</xs:sequence>
</xs:choice>
</xs:complexType>

```

### 2.2.2.27.2 Attributes

None.

### 2.2.2.27.3 Child Elements

**Eq:** Specifies whether a list item field (1) specified by the **FieldRef** element is equal to the **Value** element.

**Geq:** Specifies whether a list item field (1) specified by the **FieldRef** element is greater than or equal to the **Value** element.

**Gt:** Specifies whether a list item field (1) specified by the **FieldRef** element is greater than the **Value** element.

**In:** Specifies whether a list item field (1) specified by the **FieldRef** element is equal to one of the values specified by the **Values** element.

**Leq:** Specifies whether a list item field (1) specified by the **FieldRef** element is less than or equal to the **Value** element.

**Lt:** Specifies whether a list item field (1) specified by the **FieldRef** element is less than the **Value** element.

## 2.3 List Schema Definitions

Types in this section can be used to define a list, as well as the components of a list, such as a **list form** or a list **view**.

### 2.3.1 Simple Types

#### 2.3.1.1 ListTemplateBaseType

The **ListTemplateBaseType** type specifies the base type of a **list template**.

```

<xs:simpleType name="ListTemplateBaseType">
  <xs:restriction base="xs:int">
    <xs:enumeration value="0" />
    <xs:enumeration value="1" />
    <xs:enumeration value="3" />
    <xs:enumeration value="4" />
    <xs:enumeration value="5" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes possible values.

Value	Description
0	The list template is based on a list.
1	The list template is based on a <b>document library</b> .
3	The list template is based on a <b>discussion board</b> .
4	The list template is based on a <b>survey list</b> .
5	The list template is based on an issues list.

### 2.3.1.2 AggregationsType

The **AggregationsType** type specifies a type for an aggregation operation on a query. This type is defined as follows:

```
<xs:simpleType name="AggregationsType">
  <xs:restriction base="xs:string">
    <xs:pattern
      value="([Aa][Vv][Gg])|([Cc][Oo][Uu][Nn][Tt])|([Mm][Aa][Xx])|([Mm][Ii][Nn])|([Ss][Tt][Dd][Ee][
      Vv])|([Ss][Uu][Mm])|([Vv][Aa][Rr])" />
    </xs:restriction>
  </xs:simpleType>
```

The following table describes possible values.

Value	Description
<b>Avg</b>	Returns the average of all non-null values from the specified expression.
<b>Count</b>	Returns a count of the values from the specified expression.
<b>Max</b>	Returns the maximum value from all non-null values of the specified expression.
<b>Min</b>	Returns the minimum value from all non-null values of the specified expression.
<b>StDev</b>	Returns the standard deviation of all non-null values of the specified expression.
<b>Sum</b>	Returns a sum of the values of the specified expression.
<b>Var</b>	Returns the variance of all non-null values of the specified expression.

### 2.3.1.3 AggregationsValue Type

The **AggregationsValue** type specifies whether an aggregation is enabled for a query. This type is defined as follows:

```
<xs:simpleType name="AggregationsValue">
  <xs:restriction base="xs:string">
    <xs:pattern value="On|.*" />
  </xs:restriction>
</xs:simpleType>
```

### 2.3.1.4 ContentTypeId Type

The **ContentTypeId** type is the identifier for the specified content type. See [\[MS-WSSTS\]](#) section 2.1.2.8.1 for more information about the structure of a content type identifier.

```
<xs:simpleType name="ContentTypeId">
  <xs:restriction base="xs:string">
    <xs:pattern value="0x([0-9A-Fa-f] [1-9A-Fa-f] | [1-9A-Fa-f] [0-9A-Fa-f] | 00[0-9A-Fa-
f]{32})*" />
    <xs:minLength value="2"/>
    <xs:maxLength value="1026"/>
  </xs:restriction>
</xs:simpleType>
```

### 2.3.1.5 FormType

The **FormType** type specifies the type of the role of a particular **form (1)**.

```
<xs:simpleType name="FormType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="DisplayForm" />
    <xs:enumeration value="EditForm" />
    <xs:enumeration value="NewForm" />
    <xs:enumeration value="NewFormDialog" />
    <xs:enumeration value="SolutionForm" />
  </xs:restriction>
</xs:simpleType>
```

The following table describes possible values.

Value	Description
<b>DisplayForm</b>	A form that displays an individual list item.
<b>EditForm</b>	A form that edits an individual list item.
<b>NewForm</b>	A form that creates an individual list item.
<b>NewFormDialog</b>	A form that creates an individual list item within a client application.
<b>SolutionForm</b>	A form that creates a solution.

### 2.3.1.6 ListTemplateCategoryType

The **ListTemplateCategoryType** type specifies a category for a list template. This type is defined as follows:

```
<xs:simpleType name="ListTemplateCategoryType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Libraries" />
    <xs:enumeration value="Communications" />
    <xs:enumeration value="Tracking" />
    <xs:enumeration value="Custom Lists" />
  </xs:restriction>
```

```
</xs:simpleType>
```

The following table describes possible values.

Value	Description
<b>Libraries</b>	Specifies that the template is categorized with other library-style templates.
<b>Communications</b>	Specifies that the template is categorized with templates that are used for communicating.
<b>Tracking</b>	Specifies that the template is categorized with other tracking templates.
<b>Custom Lists</b>	Specifies that the template is categorized with other miscellaneous custom list templates.

### 2.3.1.7 ToolbarPosition

The **ToolbarPosition** type specifies where the **toolbar** is rendered on a page, relative to the main view content.

```
<xs:simpleType name="ToolbarPosition">  
  <xs:restriction base="xs:string">  
    <xs:enumeration value="After" />  
  </xs:restriction>  
</xs:simpleType>
```

**After** specifies that the toolbar is positioned after the main view content.

### 2.3.1.8 ToolbarType

The **ToolbarType** type specifies the type of toolbar to be rendered in the user interface for a list.

```
<xs:simpleType name="ToolbarType">  
  <xs:restriction base="xs:string">  
    <xs:enumeration value="Standard" />  
    <xs:enumeration value="FreeForm" />  
    <xs:enumeration value="RelatedTasks" />  
    <xs:enumeration value="None" />  
  </xs:restriction>  
</xs:simpleType>
```

The following table describes possible values.

Value	Description
<b>Standard</b>	A standard toolbar in a view.
<b>FreeForm</b>	A toolbar used in a summary view on a home page.
<b>RelatedTasks</b>	A toolbar with actions related to an item.
<b>None</b>	This view has no toolbar.

### 2.3.1.9 ViewModerationType

The **ViewModerationType** type specifies a style of moderation for a list.

```
<xs:simpleType name="ViewModerationType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Moderator" />
    <xs:enumeration value="Contributor" />
    <xs:enumeration value="HideUnapproved" />
    <xs:enumeration value="" />
  </xs:restriction>
</xs:simpleType>
```

This type **MUST** be one of the values in the following table, or it **MUST** be empty.

Value	Description
<b>Moderator</b>	System-created moderator's view of a <b>moderated list</b> , which displays list items that are pending approval. See also VIEWFLAG_MODTYPEMODERATOR (0x00008000) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
<b>Contributor</b>	System-created view of a user's items awaiting moderation in a moderated list. See also VIEWFLAG_MODTYPECONTRIBUTOR (0x00004000) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
<b>HideUnapproved</b>	View does not display items that have not been approved. Implementations <b>MUST NOT</b> show this view to anonymous users. See also VIEWFLAG_MODTYPEHIDEUNAPPROVED (0x20000000) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
<b>(empty string)</b>	Unused flag value, which <b>MUST</b> be ignored by client applications.

### 2.3.1.10 ViewPageLevel

The **ViewPageLevel** type specifies the **publishing level** of a page that contains the view. See [\[MS-WSSFO2\]](#) section 2.2.2.6.

```
<xs:simpleType name="ViewPageLevel">
  <xs:restriction base="xs:int">
    <xs:enumeration value="1" />
    <xs:enumeration value="2" />
    <xs:enumeration value="255" />
  </xs:restriction>
</xs:simpleType>
```

### 2.3.1.11 ViewScope

The **ViewScope** type specifies whether and how files and subfolders are included in a view.

```
<xs:simpleType name="ViewScope">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Recursive" />
    <xs:enumeration value="RecursiveAll" />
    <xs:enumeration value="FilesOnly" />
    <xs:enumeration value="" />
  </xs:restriction>
</xs:simpleType>
```

```

</xs:restriction>
</xs:simpleType>

```

The following table describes possible values.

Value	Description
<b>FilesOnly</b>	Shows only the files in the specified folder. See also VIEWFLAG_FILESONLY &~VIEWFLAG_RECURSIVE (0x00200000&~ 0x00001000) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
<b>Recursive</b>	Shows all files in the specified folder or any folder descending from it. See also (VIEWFLAG_FILESONLY  VIEWFLAG_RECURSIVE (0x00200000 0x00001000) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
<b>RecursiveAll</b>	Shows all files and folders in the specified folder or any folder descending from it. See also VIEWFLAG_RECURSIVE &~ VIEWFLAG_FILESONLY (0x00001000&~0x20000000) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
(empty string)	Shows only the files and subfolders of the specified folder.

### 2.3.1.12 ViewType

The **ViewType** type specifies the type of view rendering.

```

<xs:simpleType name="ViewType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="HTML" />
    <xs:enumeration value="GRID" />
    <xs:enumeration value="CALENDAR" />
    <xs:enumeration value="RECURRENCE" />
    <xs:enumeration value="CHART" />
    <xs:enumeration value="GANTT" />
    <xs:enumeration value="TABLE" />
  </xs:restriction>
</xs:simpleType>

```

The following table describes possible values.

Value	Description
HTML	Normal HTML-based view. See also VIEWFLAG_HTML (0x00000001) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
GRID	View presents a datasheet view of a rich client application. See also VIEWFLAG_GRID (0x00000800) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
CALENDAR	Displays data on a calendar based on date and time properties of the list items. See also VIEWFLAG_CALENDAR (0x00080000) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
RECURRENCE	Requires that the data of the view be expanded, based on a calendar recurrence—for example, having a view of list item data for the first Thursday of every month. See also VIEWFLAG_RECURRENCE_RS (0x00002000) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.12.
CHART	Displays HTML-based graphical charts of list item data. See also VIEWFLAG_CHART

Value	Description
	(0x00020000) in [MS-WSSFO2] section 2.2.2.12.
GANTT	Displays list item data in a Gantt chart. See also VIEWFLAG_GANTT (0x04000000) in [MS-WSSFO2] section 2.2.2.12.
TABLE	The implementation MUST write this value if the <b>ViewType</b> is not <b>HTML</b> , <b>GRID</b> , <b>CALENDAR</b> , <b>RECURRENCE</b> , <b>CHART</b> , or <b>GANTT</b> .

## 2.3.2 Complex Types

### 2.3.2.1 AggregationsDefinition Type

The **AggregationsDefinition** type specifies how the view is aggregated.

#### 2.3.2.1.1 Schema

```
<xs:complexType name="AggregationsDefinition">
  <xs:sequence>
    <xs:element name="FieldRef" type="FieldRefDefinitionAggregation" minOccurs="0"
      maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Value" type="AggregationsValue" use="optional"/>
</xs:complexType>
```

#### 2.3.2.1.2 Attributes

**Value:** If set to "On", the reader MUST interpret this to mean that aggregation of the field (1) specified in the preceding **FieldRef** is calculated. Otherwise, the reader MUST ignore the element.

#### 2.3.2.1.3 Child Elements

**FieldRef:** Specifies the field (1) on which aggregation occurs.

### 2.3.2.2 FieldRefDefinitionAggregation Type

The **FieldRefDefinitionAggregation** type specifies the field (1) to be aggregated.

#### 2.3.2.2.1 Schema

```
<xs:complexType name="FieldRefDefinitionAggregation">
  <xs:attribute name="Name" type="xs:string" use="required"/>
  <xs:attribute name="Type" type="AggregationsType" use="required"/>
</xs:complexType>
```

#### 2.3.2.2.2 Attributes

**Name:** Name of the field (1) to aggregate.

**Type:** Type of aggregation to be performed.

### 2.3.2.2.3 Child Elements

None.

### 2.3.2.3 CalendarViewStylesDefinition Type

The **CalendarViewStylesDefinition** type specifies zero or more calendar view styles.

#### 2.3.2.3.1 Schema

```
<xs:complexType name="CalendarViewStylesDefinition" mixed="true">
  <xs:sequence>
    <xs:element name="CalendarViewStyle" type="CalendarViewStyleDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

#### 2.3.2.3.2 Attributes

None.

#### 2.3.2.3.3 Child Elements

**CalendarViewStyle**: An instance of a calendar view style definition.

### 2.3.2.4 CalendarViewStyleDefinition Type

The **CalendarViewStyleDefinition** type expresses a single calendar view style for a view.

#### 2.3.2.4.1 Schema

```
<xs:complexType name="CalendarViewStyleDefinition" mixed="true">
  <xs:all>
    <xs:element name="AccessKey" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="ImageName" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="ImageWidth" type="xs:int" minOccurs="0" maxOccurs="1" />
    <xs:element name="ImageHeight" type="xs:int" minOccurs="0" maxOccurs="1" />
  </xs:all>
  <xs:attribute name="Title" type="xs:string" />
  <xs:attribute name="Type" type="xs:string" />
  <xs:attribute name="Template" type="xs:string" />
  <xs:attribute name="Sequence" type="xs:int" />
  <xs:attribute name="Default" type="TRUEFALSE" default="FALSE"/>
</xs:complexType>
```

#### 2.3.2.4.2 Child Elements

**AccessKey**: Specifies the keyboard shortcut to activate or focus on the calendar view style.

**ImageName**: File name of the image icon for the calendar view style.

**ImageWidth**: Width of the image icon for the calendar view style.

**ImageHeight**: Height of the image icon for the calendar view style.

### 2.3.2.4.3 Attributes

**Title:** Title of the calendar view style.

**Type:** Type of the calendar view style.

**Template:** Predefined **control template** for the calendar view style.

**Sequence:** Sequence order for the calendar view style.

**Default:** Specifies whether this is the default calendar view style.

### 2.3.2.5 FormDefinition Type

The **FormDefinition** type specifies a definition of list forms used to create, modify, or display individual list items.

#### 2.3.2.5.1 Schema

```
<xs:complexType name="FormDefinition">
  <xs:all>
    <xs:element name="ListFormOpening" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ListFormButtons" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ListFormBody" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ListFormClosing" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
  </xs:all>
  <xs:attribute name="Path" type="RelativeFilePath" />
</xs:complexType>
```

```

<xs:attribute name="SetupPath" type="RelativeFilePath" />
<xs:attribute name="Url" type="RelativeUrl" />
<xs:attribute name="Type" type="FormType" />
<xs:attribute name="UseLegacyForm" type="TRUEFALSE" default="FALSE"/>
<xs:attribute name="Template" type="xs:string" />
<xs:attribute name="WebPartZoneID" type="xs:string" />
<xs:attribute name="FormID" type="xs:int" default="0" />
<xs:attribute name="Name" type="UniqueIdentifierWithBraces" />
<xs:attribute name="ToolbarTemplate" type="xs:string" />
<xs:attribute name="Default" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="MobileUrl" type="RelativeUrl" />
</xs:complexType>

```

### 2.3.2.5.2 Attributes

**Type:** Type of the list form.

**Name:** Internal identifier for the **Web Part**.

**SetupPath:** Source file path to the ghosted document on the front-end Web server. This path **MUST** be relative to the application root path.

**Path:** Source path to the ghosted document. If the **SetupPath** attribute is specified, the reader **MUST** ignore this attribute and use the value of **SetupPath**.

**FormID:** Identifier of the list form.

**WebPartZoneID:** Identifier of the **Web Part zone** in which the list form Web Part exists.

**UseLegacyForm:** Specifies whether to use the obsolete XML-based form rendering infrastructure.

**Template:** Name of the list form control template. The list of available control templates depends on the server implementation.

**ToolbarTemplate:** Control template of the tool bar used in this list form.

**Url:** Specifies the URL of the page hosting the list form.

**Default:** Specifies whether this is the default list form for the type specified by the **Type** attribute for the list (1).

**MobileUrl:** Specifies the URL of the page hosting the list form that is suitable for **mobile devices**.

### 2.3.2.5.3 Child Elements

**ListFormOpening:** Specifies the rendering for the beginning of a list form. The reader **MUST** ignore the **ListFormOpening** element if **UseLegacyForm** is set to **false**.

**ListFormButtons:** Specifies the rendering for a button area of a list form. The reader **MUST** ignore the **ListFormButtons** element if **UseLegacyForm** is set to **false**.

**ListFormBody:** Specifies the rendering for the body of a list form. The reader **MUST** ignore the **ListFormBody** element if **UseLegacyForm** is set to **false**.

**ListFormClosing:** Specifies the rendering for the footer of a list form. The reader **MUST** ignore the **ListFormClosing** element if **UseLegacyForm** is set to **false**.

### 2.3.2.6 ListDefinition Type

The **ListDefinition** type specifies the structure of a list (1) and its components, such as forms, views, and fields (1).

#### 2.3.2.6.1 Schema

```
<xs:complexType name="ListDefinition">
  <xs:all>
    <xs:element name="MetaData" type="ListMetaDataDefinition" minOccurs="1" maxOccurs="1"
form="qualified" />
  </xs:all>
  <xs:attribute name="AllowDeletion" type="TRUEFALSE" default="TRUE" />
  <xs:attribute name="AllowEveryoneViewItem" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="AllowMultiVote" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="AlwaysIncludeContent" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="BaseType" type="xs:int" use="required" />
  <xs:attribute name="CacheSchema" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Catalog" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DefaultItemOpen" type="xs:int" default="0" />
  <xs:attribute name="Description" type="xs:string" use="required" />
  <xs:attribute name="Direction" type="xs:int" use="required" />
  <xs:attribute name="DisableAttachments" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DisableDeployingList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DisableDeployWithDependentList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DisallowContentTypes" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DontSaveInTemplate" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DraftVersionVisibility" type="xs:int" default="0" />
  <xs:attribute name="EmailAssignTo" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableContentTypes" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableMinorVersions" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnablePeopleSelector" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableResourceSelector" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableThumbnails" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EventSinkAssembly" type="AssemblyStrongName" />
  <xs:attribute name="EventSinkClass" type="AssemblyClass" />
  <xs:attribute name="EventSinkData" type="String255Chars" />
  <xs:attribute name="FeatureId" type="UniqueIdentifierWithBraces" />
  <xs:attribute name="FolderCreation" type="TRUEFALSE" default="TRUE" />
  <xs:attribute name="ForceCheckout" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="HiddenList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="IsApplicationList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="MajorVersionLimit" type="IntNonNegative" />
  <xs:attribute name="MajorWithMinorVersionsLimit" type="IntNonNegative" />
  <xs:attribute name="ModerationType" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="MultipleMtgDataList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="MustSaveRootFiles" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Name" type="xs:string" />
  <xs:attribute name="OrderedList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="PrivateList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="PublicList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="RestrictedTemplate" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="RootWebOnly" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="ServerTemplate" type="xs:int" />
  <xs:attribute name="SuppressNameDisplay" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="ThumbnailSize" type="xs:int" default="0" />
  <xs:attribute name="Title" type="xs:string" use="required" />
  <xs:attribute name="Url" type="RelativeUrl" />
  <xs:attribute name="Version" type="xs:int" />

```

```
<xs:attribute name="VersioningEnabled" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="WebImageHeight" type="xs:int" default="0" />
<xs:attribute name="WebImageWidth" type="xs:int" default="0" />
</xs:complexType>
```

### 2.3.2.6.2 Attributes

**AllowDeletion:** Specifies whether this list can be deleted—for example, whether the list is crucial to the functioning of the containing site (2) or **site collection**. See also flag LP\_UNDELETABLELIST (0x0000000000000004) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**AllowEveryoneViewItems:** Specifies whether list items in this list are visible to anyone who has access to the list itself. This setting is useful for shared resources, such as the master page gallery, where one page can be used throughout a site collection in **security scopes** with varying permissions. See also flag LP\_ALLOWEVERYONEVIEWITEMS (0x000000002000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**AllowMultiVote:** If this list is a survey, specifies whether to grant multiple responses to a user, rather than restricting the user to a single response. The reader MUST ignore this attribute unless the **ServerTemplate** attribute is set to 102. See also flag LP\_ALLOWMULTIVOTE (0x0000000000000800) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**AlwaysIncludeContent:** Specifies whether data from this list MUST always be included when it is saved as a list server template, even if not otherwise requested. See also flag LP\_ALWAYSINCLUDECONTENT (0x0000001000000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**BaseType:** Base type of the list as specified in section [2.3.1.1](#).

**CacheSchema:** Specifies whether this list can have its schema cached in memory when possible, rather than retrieving the schema every time that the list is accessed. See also flag LP\_CACHESHEMA (0x0000000200000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**Catalog:** Specifies whether this list is a catalog—for example, a Web Part gallery, master page gallery, and so on. See also flag LP\_CATALOGLIST (0x0000000000000010) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**DefaultItemOpen:** Specifies whether applications that generate server transformations of list items in this list can open the list item in a browser, rather than in a separate client-side application. This attribute SHOULD be set to zero or 1. The reader MUST accept any integer, but MUST treat all values except 1 as zero. A value of 1 indicates that the flag 0x0000000010000000 is set. See also flag LP\_DEFAULTITEMOPEN (0x0000000010000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**Description:** Textual description of the list.

**Direction:** Direction for displaying text. A writer SHOULD set this to zero to inherit the direction from a parent site (2), 1 to set the direction as left-to-right, or 2 to set the direction as right-to-left. The reader MUST interpret other values as zero.

**DisableAttachments:** Specifies whether attachments on list items are disabled. See also flag LP\_DISABLEATTACHMENTS (0x0000000000000008) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**DisableDeployingList:** Specifies whether this list is exported as part of a migration package. See also flag LP\_DISABLEDEPLOYINGLIST (0x0000000100000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**DisableDeployWithDependentList:** Specifies whether this list is automatically exported when exporting a list that references it. See also flag LP\_DISABLEDDEPLOYWITHDEPENDENTLIST (0x0000000008000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**DisallowContentTypes:** Specifies whether content type manipulation is disabled on this list. See also flag LP\_DISALLOWCONTENTTYPES (0x0000002000000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**DontSaveInTemplate:** Specifies whether this list is serialized when saving this site (2) as a site template. See also flag LP\_DONTSAVEINTEMPLATE (0x0000000000002000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**DraftVersionVisibility:** Specifies the rights required to see drafts. The following table describes possible values.

Value	Description
1	Requires edit right to see drafts. See LP_MINORAUTHOR (0x000000000100000) <a href="#">[MS-WSSFO2]</a> section 2.2.2.5.
2	Requires approval right to see drafts. See LP_MINORAPPROVER (0x000000000200000) in <a href="#">[MS-WSSFO2]</a> section 2.2.2.5.
Other values	Requires read right to see drafts.

**EmailAssignTo:** Specifies whether this list sends alerts when a list item is assigned to a user. See also flag LP\_ENABLEASSIGNTOEMAIL (0x0000000000000040) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**EnableContentTypes:** Specifies whether a user interface (UI) for manipulating multiple content types—for example, a list that contains both announcements and tasks is available. See also flag LP\_ENABLECONTENTTYPES (0x000000000400000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**EnableMinorVersions:** Specifies whether this list supports creation of minor versions on item revisions. See also flag LP\_MINORVERSIONENABLED (0x000000000080000) in [\[MS-WSSFO2\]](#) section 2.2.2.5. The reader **MUST** ignore this setting when **VersioningEnabled** is set to **false**.

**EnableThumbnails:** Specifies whether document parsers in this list generate thumbnail files that correspond to documents that are saved to this list. This attribute **MUST** be ignored for lists that are not document libraries. See also flag LP\_ENABLETHUMBNAILS (0x000000001000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**EnablePeopleSelector:** Specifies whether a UI for adding users is available in lists (1) whose **ServerTemplate** attribute is set to 106. See also flag LP\_ENABLEPEOPLESELECTOR (0x0000080000000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5

**EnableResourceSelector:** Specifies whether a UI for adding resources is available in lists (1) whose **ServerTemplate** attribute is set to 106. See also flag LP\_ENABLERESOURCESELECTOR (0x0000200000000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5

**EventSinkAssembly:** Specifies a .NET **assembly** strong name that contains an implementation of additional event behavior for a list. See [\[MSDN-SHPTSDK\]](#) for information about implementation-specific details of event-sink implementation.

**EventSinkClass:** Specifies a .NET fully qualified class name that contains an implementation of additional event behavior for a list. See [\[MSDN-SHPTSDK\]](#) for information about implementation-specific details of event-sink implementation.

**EventSinkData:** Optional additional properties or data for an **event handler** for the list.

**FeatureId:** Identifier of a feature associated with the underlying list definition.

**FolderCreation:** Specifies whether creation of folders is blocked in this list. See also flag LP\_DISABLEFOLDERS (0x0000000020000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**ForceCheckout:** Specifies whether this document library requires the user to check out documents before modifying them. See also flag LP\_FORCECHECKOUT (0x000000000040000) in [\[MS-WSSFO2\]](#) section 2.2.2.5. The reader MUST ignore this attribute unless the **ServerTemplate** attribute is set to 101.

**HiddenList:** Specifies whether this list is hidden from enumeration functions. This is intended for lists that implement the infrastructure for an application. See also flag LP\_HIDDENLIST (0x000000000000100) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**IsApplicationList:** Specifies whether the list implements the infrastructure for an application. See also flag LP\_ISAPPLICATIONLIST (0x0010000000000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**MajorVersionLimit:** Specifies the number of **major versions** to keep per item. The reader MUST ignore this setting when **VersioningEnabled** is set to **false**.

**MajorWithMinorVersionsLimit:** Specifies the number of minor versions to keep per major version of an item. The reader MUST ignore this setting when **VersioningEnabled** is set to **false**. The reader MUST also ignore this setting when **EnableMinorVersions** is set to **false** and **ModerationType** is set to **false**.

**ModerationType:** Specifies whether this list has moderation enabled, requiring an approval process when content is created or modified. See also flag LP\_MODERATEDLIST (0x000000000000400) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**MultipleMtgDataList:** Specifies whether this list is associated with a site (2) that uses the site template of the Meeting Workspace site (2) and contains data scoped to each instance of a recurring meeting. See also flag LP\_MULTIPLEMTGDATALIST (0x000000000000020) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**MustSaveRootFiles:** When a list server template is created for this list, specifies whether documents in the root of the list can also be serialized. See also flag LP\_MUSTSAVEROOTFILES (0x0000000000008000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**Name:** Name for the list. This value is the same as the list identifier.

**OrderedList:** Specifies whether this list is an ordered list—for example, a Links list, and supports ordering and reordering of its items. See also flag LP\_ORDEREDLIST (0x0000000000000001) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**PrivateList:** Specifies whether this is a private list. When a list template based on this list is created, the new list can be given an access control list so that only its owner and administrators can access the list. See also flag LP\_PRIVATELIST (0x000000000020000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**PublicList:** Specifies whether this list is a public list. See also flag LP\_PUBLICLIST (0x0000000000000002) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**RestrictedTemplate:** Specifies whether this list restricts view functionality, such as the datasheet view and views involving Web Part to Web Part connections. See also flag LP\_RESTRICTEDTEMPLATelist (0x0000000040000000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**RootWebOnly:** Specifies whether the list server template for this list can be instantiated only in the root site (2) of the site collection. See also flag LP\_ROOTWEBONLY (0x0000000000004000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**ServerTemplate:** The value corresponding to the template that the list is based on. See [\[MS-WSSFO3\]](#) section 2.2.1.2.12 for a list of reserved values. Reader MUST infer the value from the **BaseType** attribute if not present. The following table describes the ServerTemplate values inferred from the values of BaseType.

BaseType	Inferred ServerTemplate value
0 (BASETYPE_GENERIC_LIST)	100 (LISTTEMPLATE_GENERIC_LIST)
1 (BASETYPE_DOCUMENT_LIBRARY)	101 (LISTTEMPLATE_DOCUMENT_LIBRARY)
3 (BASETYPE_DISCUSSION)	108 (LISTTEMPLATE_DISCUSSION)
4 (BASETYPE_SURVEY)	102 (LISTTEMPLATE_SURVEY)
5 (BASETYPE_ISSUE)	1100 (LISTTEMPLATE_ISSUE_TRACKING)

The writer MUST include this attribute for any **BaseType** not mentioned and SHOULD include it even if it would be inferred.

**SuppressNameDisplay:** Specifies whether this list uses the value of each field's **ForcedDisplay** attribute when presenting data from that field (1). This is commonly used in anonymous surveys to display common placeholder text wherever the respondent's name would normally appear. See also flag LP\_USEFORCEDDISPLAY (0x0000000000001000) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**ThumbnailSize:** Specifies the size, in pixels, of a bounding rectangle for server-generated thumbnails. The writer SHOULD omit this attribute unless the **ServerTemplate** is set to 109, which specifies an image library list. If the **ServerTemplate** attribute is set to 109, the writer MUST specify a nonzero value. The reader MUST ignore this unless the **ServerTemplate** attribute is set to 109.

**Title:** A user-recognizable title for the list.

**Url:** URL of the list. The writer SHOULD include it [\[2\]](#).

**Version:** Current version of the list. The writer MUST increment the value by 1 each time the list definition is changed. The reader MUST ignore this attribute.

**VersioningEnabled:** See flag LP\_VERSIONINGENABLED (0x0000000000000080) in [\[MS-WSSFO2\]](#) section 2.2.2.5.

**WebImageHeight:** Specifies the height of a display image in an image library list. Like **ThumbnailSize**, the reader SHOULD ignore this, and the writer SHOULD omit this unless the **ServerTemplate** attribute is set to 109. The writer MUST specify a nonzero value if the **ServerTemplate** is set to 109.

**WebImageWidth:** Specifies the width of a display image in an image library list. Like **ThumbnailSize**, the reader SHOULD ignore this, and the writer SHOULD omit this unless the **ServerTemplate** attribute is set to 109. The writer MUST specify a nonzero value if the **ServerTemplate** is set to 109.

### 2.3.2.6.3 Child Elements

**MetaData:** Contains definitions of views, fields (1), forms, and other components for this list.

### 2.3.2.7 ListFormSet Type

The **ListFormSet** type is the overall container for list forms that are being used in the current list.

#### 2.3.2.7.1 Schema

```
<xs:complexType name="ListFormSet">
  <xs:sequence>
    <xs:element name="Form" type="FormDefinition" minOccurs="0" maxOccurs="4" />
  </xs:sequence>
</xs:complexType>
```

#### 2.3.2.7.2 Attributes

None.

#### 2.3.2.7.3 Child Elements

**Form:** Definition of a form for this list.

### 2.3.2.8 ListMetaDataDefinition Type

The **ListMetaDataDefinition** type contains elements used to define the structure of a list.

#### 2.3.2.8.1 Schema

```
<xs:complexType name="ListMetaDataDefinition">
  <xs:all>
    <xs:element name="ContentTypes" type="ContentTypeReferences" minOccurs="0"
maxOccurs="1" />
    <xs:element name="Default" type="ListMetaDataDefault" minOccurs="0" maxOccurs="1" />
    <xs:element name="DefaultDescription" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="DocumentLibraryTemplate" type="xs:string" minOccurs="0" maxOccurs="1"
/>
    <xs:element name="Fields" type="FieldDefinitions" minOccurs="0" maxOccurs="1" />
    <xs:element name="Forms" type="ListFormSet" minOccurs="0" maxOccurs="1" />
    <xs:element name="Security" type="ListSecurity" minOccurs="0" maxOccurs="1" />
    <xs:element name="Toolbar" type="ToolbarDefinition" minOccurs="0" maxOccurs="1" />
    <xs:element name="Validation" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="Views" type="ViewDefinitions" minOccurs="0" maxOccurs="1" />
  </xs:all>
</xs:complexType>
```

### 2.3.2.8.2 Attributes

None.

### 2.3.2.8.3 Child Elements

**ContentTypes:** Specifies a set of content types associated with the list.

**Default:** Specifies default forms for a list.

**DefaultDescription:** Sets the default description used to summarize this list.

**DocumentLibraryTemplate:** Specifies the URL of a document to use as a template when new documents are created in the document library. The reader **MUST** ignore this attribute unless the **ServerTemplate** attribute is set to 101.

**Fields:** Specifies a collection of fields (1) that comprise the schema of the list.

**Forms:** Specifies the forms that are associated with the list.

**Security:** Specifies special security constraints on the list.

**Toolbar:** Specifies a rendering for a toolbar for the list.

**Validation:** The implementation-specific XML that specifies the validation criteria to be used for items in this list (1).

**Views:** Specifies a set of views associated with this list.

### 2.3.2.9 FieldDefinitions Type

The **FieldDefinitions** type contains a collection of zero or more fields (1).

#### 2.3.2.9.1 Schema

```
<xs:complexType name="FieldDefinitions">
  <xs:sequence>
    <xs:element name="Field" type="FieldDefinition" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

#### 2.3.2.9.2 Attribute

None.

#### 2.3.2.9.3 Child Elements

**Field:** Contains a definition of a field (1), as described in [\[MS-WSSFO3\]](#) section 2.2.7.3.3 and in [\[MS-WSSFO2\]](#) section 2.2.8.3.3.

### 2.3.2.10 ListMetaDataDefault Type

#### 2.3.2.10.1 Schema

```
<xs:complexType name="ListMetaDataDefault">
```

```

<xs:sequence>
  <xs:element name="Forms" type="ListFormSet" />
</xs:sequence>
</xs:complexType>

```

### 2.3.2.10.2 Attributes

None.

### 2.3.2.10.3 Child Elements

**Forms:** Specifies default forms for a list.

### 2.3.2.11 ListSecurity Type

The **ListSecurity** type specifies the security information of a list definition.

#### 2.3.2.11.1 Schema

```

<xs:complexType name="ListSecurity">
  <xs:all>
    <xs:element name="ReadSecurity" type="xs:int" minOccurs="0" maxOccurs="1" />
    <xs:element name="WriteSecurity" type="xs:int" minOccurs="0" maxOccurs="1" />
    <xs:element name="SchemaSecurity" type="xs:int" minOccurs="0" maxOccurs="1" />
  </xs:all>
</xs:complexType>

```

#### 2.3.2.11.2 Attributes

None.

#### 2.3.2.11.3 Child Elements

**ReadSecurity:** Specifies an additional security restriction to read items in the list. The following table describes possible values.

Value	Description
1	No additional restriction.
2	Each item in the list is visible only to the item's author and list administrators.

**WriteSecurity:** Specifies an additional security restriction to update items in the list. The following table describes possible values.

Value	Description
1	No additional restriction.
2	Each item in the list can be changed only by the item's author and list administrators.
4	Each item in the list can be changed only by the list administrators.

**SchemaSecurity:** The server MUST set this element to zero. The reader MUST ignore it.

### 2.3.2.12 ListTemplateDefinitions Type

The **ListTemplateDefinitions** type is the container for a set of list templates for the site (2).

#### 2.3.2.12.1 Schema

```
<xs:complexType name="ListTemplateDefinitions" mixed="true">
  <xs:sequence>
    <xs:element name="ListTemplate" type="ListTemplateDefinition" minOccurs="0"
      maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

### 2.3.2.13 ListTemplateDefinition Type

The **ListTemplateDefinition** type specifies a template definition to create new lists of a specified type.

#### 2.3.2.13.1 Schema

```
<xs:complexType name="ListTemplateDefinition">
  <xs:attribute name="AllowDeletion" type="TRUEFALSE" default="TRUE" />
  <xs:attribute name="AllowEveryoneViewItem" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="AlwaysIncludeContent" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="BaseType" type="ListTemplateBaseType" use="required" />
  <xs:attribute name="CacheSchema" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Catalog" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Category" type="ListTemplateCategoryType" />
  <xs:attribute name="Description" type="xs:string" />
  <xs:attribute name="DisableAttachments" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DisallowContentTypes" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DisplayName" type="xs:string" />
  <xs:attribute name="DocumentAsEnclosure" type="TRUEFALSE" default="FALSE"/>
  <xs:attribute name="DocumentTemplate" type="xs:int" />
  <xs:attribute name="DontSaveInTemplate" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DraftVersionVisibility" type="xs:int" default="0" />
  <xs:attribute name="EditPage" type="xs:string" />
  <xs:attribute name="EmailAssignTo" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableContentTypes" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableMinorVersions" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnablePeopleSelector" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableResourceSelector" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableThumbnails" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="FeatureId"
type="UniqueIdentifierWithOrWithoutBracesWithOrWithoutDashes" />
  <xs:attribute name="FolderCreation" type="TRUEFALSE" default="TRUE" />
  <xs:attribute name="ForceCheckout" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Hidden" type="TRUEFALSE" default="FALSE"/>
  <xs:attribute name="HiddenList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Image" type="RelativeUrl" />
  <xs:attribute name="MajorVersionLimit" type="IntNonNegative" use="optional" />
  <xs:attribute name="MajorWithMinorVersionsLimit" type="IntNonNegative" use="optional" />
  <xs:attribute name="ModeratedList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="MultipleMtgDataList" type="TRUEFALSE" default="TRUE" />
  <xs:attribute name="MustSaveRootFiles" type="TRUEFALSE" default="FALSE" />
```

```

<xs:attribute name="Name" type="xs:string" />
<xs:attribute name="NewPage" type="xs:string" />
<xs:attribute name="NoCrawl" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="OnQuickLaunch" type="TRUEFALSE" />
<xs:attribute name="OrderedList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Path" type="xs:string" />
<xs:attribute name="PrivateList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="PublicList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="RootWebOnly" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="SecurityBits" type="xs:string" />
<xs:attribute name="SetupPath" type="RelativeFilePath" />
<xs:attribute name="Sequence" type="xs:int" />
<xs:attribute name="SyncType" type="xs:string" />
<xs:attribute name="ThumbnailSize" type="IntNonNegative" default="0" />
<xs:attribute name="Type" type="xs:int" use="required"/>
<xs:attribute name="Unique" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="UseRootFolderForNavigation" type="TRUEFALSE" />
<xs:attribute name="VersioningEnabled" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="WebImageHeight" type="IntNonNegative" default="0" />
<xs:attribute name="WebImageWidth" type="IntNonNegative" default="0" />
</xs:complexType>

```

### 2.3.2.13.2 Attributes

**AllowDeletion:** Specifies the value of the **AllowDeletion** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**AllowEveryoneViewItems:** Specifies the value of the **AllowEveryoneViewItems** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**AlwaysIncludeContent:** Specifies the value of the **AlwaysIncludeContent** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**BaseType:** Base type of the list as specified in section [2.3.1.1](#).

**CacheSchema:** Specifies the value of the **CacheSchema** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**Catalog:** Specifies the value of the **Catalog** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**Category:** Category with which to associate lists (1) created through the list definition. Possible values MUST be one of the values specified in **ListTemplateCategory Type** (section [2.3.1.6](#)). A reader MUST treat an unknown value as **Custom Lists**.

**Description:** Text description of the template.

**DisableAttachments:** Specifies the value of the **DisableAttachments** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**DisallowContentTypes:** Specifies the value of the **DisallowContentTypes** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**DisplayName:** **Friendly name** of the template.

**DocumentAsEnclosure:** If **true**, the **RSS items** for the list include the enclosure sub-element as specified in [\[RSS2.0\]](#)

**DocumentTemplate:** **Document template** for a document library. A reader SHOULD ignore this value if **BaseType** is not set to 1. A writer SHOULD NOT write this attribute<3>.

**DontSaveInTemplate:** Value of the **DontSaveInTemplate** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**DraftVersionVisibility:** Specifies the value of the **DraftVersionVisibility** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**EditPage:** Name of a custom form (1) to use as the page for editing the properties of the list created from this template.

**EmailAssignTo:** Specifies the value of the **EmailAssignTo** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**EnableContentTypes:** Specifies the value of the **EnableContentTypes** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**EnableMinorVersions:** Specifies the value of the **EnableMinorVersions** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)). A reader MUST ignore this value if the **BaseType** is not 1.

**EnablePeopleSelector:** Specifies the value of the **EnablePeopleSelector** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**EnableResourceSelector:** Specifies the value of the **EnableResourceSelector** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**EnableThumbnails:** Specifies the value of the **EnableThumbnails** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**FeatureId:** Identifies the **feature** with which the list template is associated.

**FolderCreation:** Specifies the value of the **FolderCreation** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**ForceCheckout:** Specifies the value of the **ForceCheckout** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)). A reader SHOULD ignore this value unless the **BaseType** is set to 1.

**Hidden:** If **true**, the list template is hidden in UIs that let users create new lists.

**HiddenList:** Specifies the value of the **HiddenList** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**Image:** URL that identifies the icon used to represent the list.

**MajorVersionLimit:** Specifies the value of the **MajorVersionLimit** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)). A reader MUST ignore this value when **VersioningEnabled** is set to **false**.

**MajorWithMinorVersionsLimit:** Specifies the value of the **DisableAttachments** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)). A reader MUST ignore this value when **VersioningEnabled** is set to **false**.

**ModeratedList:** Specifies whether the list template is a moderated list.

**MultipleMtgDataList:** Specifies the value of the **MultipleMtgDataList** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**MustSaveRootFiles:** Specifies the value of the **MustSaveRootFiles** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**Name:** Field internal name of the template.

**NewPage:** Name of a custom form (1) to use as the page for creating a new list of this template.

**NoCrawl:** TRUE to specify that the list is not visible in search results; otherwise, FALSE.

**OnQuickLaunch:** If **true**, lists created from this template **MUST** be placed in the left navigational area.

**OrderedList:** Specifies the value of the **OrderedList** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**PrivateList:** Specifies the value of the **PrivateList** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**PublicList:** Specifies the value of the **PublicList** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**RootWebOnly:** Specifies the value of the **RootWebOnly** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**SecurityBits:** Specifies the item-level permissions in the list for users with sufficient permission to read or edit list items. The value **MUST** be a two-digit string. The first digit in the string controls the read access as defined by the **ReadSecurity** element in the **ListSecurity Type** (section [2.3.2.11](#)), whereas the second digit in the string controls the edit access as defined by the **WriteSecurity** element in **ListSecurity Type** (section [2.3.2.11](#)).

**SetupPath:** Source file path to the ghosted document on the front-end Web server that specifies this list template. This path **MUST** be relative to the application root path.

**Sequence:** Specifies the ordering of this list template when present in a list.

**SyncType:** Specifies a short-name of the **Type** of this list template.

**ThumbnailSize:** Specifies the value of the **ThumbnailSize** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)). A reader **MUST** ignore this unless the **Type** attribute is set to 109.

**Type:** Unique identifier for the list definition. It **MUST** be of type **integer**. The value **MUST** be greater than zero. It **MUST** be unique in a feature. The following table describes possible values.

Value	Description
100	Generic list
101	Document library
102	Survey list
103	Links list
104	Announcements list
105	Contacts list

Value	Description
106	Events list
107	Tasks list
108	Discussion board
109	Picture library
110	Data sources
111	Site template gallery
113	Web Part gallery
114	List template gallery
115	XML form library
120	Custom grid for a list
200	Meeting series list
201	Meeting agenda list
202	Meeting attendees list
204	Meeting decisions list
207	Meeting objectives list
210	Meeting text box
211	Meeting things to bring list
212	Meeting workspace pages list
1100	Issue tracking

**Unique:** If **true**, this attribute specifies that there can be only one list of this template created in the site (2).

**UseRootFolderForNavigation:** If **true**, this attribute specifies that the link for the list in the left navigational area points to the root folder of the list, instead of the default view page of the list.

**VersioningEnabled:** Specifies the value of the **VersioningEnabled** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)).

**WebImageHeight:** Specifies the value of the **WebImageHeight** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)). Like **ThumbnailSize**, a reader MUST ignore this unless the **Type** attribute is set to 109.

**WebImageWidth:** Specifies the value of the **WebImageWidth** attribute for the list. See **ListDefinition Type** (section [2.3.2.6](#)). Like **ThumbnailSize**, a reader MUST ignore this unless the **Type** attribute is set to 109.

### 2.3.2.13.3 Child Elements

None.

### 2.3.2.14 RowLimitDefinition Type

The **RowLimitDefinition** type specifies a limit to the number of items that are returned with a view.

#### 2.3.2.14.1 Schema

```
<xs:complexType name="RowLimitDefinition">
  <xs:simpleContent>
    <xs:extension base="xs:int">
      <xs:attribute name="Paged" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```

#### 2.3.2.14.2 Attributes

**Paged:** Specifies whether the view supports displaying more items, page by page.

#### 2.3.2.14.3 Child Elements

**Content:** Specifies the number of items returned by this view. If not specified, the list schema consumer **MUST** return all items that meet the filter condition.

### 2.3.2.15 ToolbarDefinition Type

The **ToolbarDefinition** type specifies the rendering of the toolbar of a view.

#### 2.3.2.15.1 Schema

```
<xs:complexType name="ToolbarDefinition">
  <xs:sequence>
    <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any" processContents="skip" />
  </xs:sequence>
  <xs:attribute name="Position" type="ToolbarPosition" />
  <xs:attribute name="Type" type="ToolbarType" />
  <xs:anyAttribute processContents="skip" />
</xs:complexType>
```

#### 2.3.2.15.2 Child Elements

**ToolbarDefinition** contains HTML and markup used to render a view.

#### 2.3.2.15.3 Attributes

**Position:** If specified, **MUST** be the set to "After" so that the toolbar appears following the view body. If not specified, the toolbar appears preceding the view body.

**Type:** Type of toolbar that is defined by this element. For possible values, see **ToolBarType**, section 2.3.1.8. The protocol server MUST ignore this attribute if the **ToolBarDefinition** element has content. If the **ToolBarDefinition** element has no content and **Type** is set to "None", this view has no toolbar. If **Type** is set to "FreeForm", the toolbar of the view whose **BaseViewID** is set to zero is used. Otherwise, the toolbar of the list's default view is used.

### 2.3.2.16 ViewDefinitions Type

The **ViewDefinitions** type specifies a collection of views that are defined for a list.

#### 2.3.2.16.1 Schema

```
<xs:complexType name="ViewDefinitions">
  <xs:sequence>
    <xs:element name="View" type="ViewDefinition" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

#### 2.3.2.16.2 Attributes

None.

#### 2.3.2.16.3 Child Elements

**View:** A definition of a view for the list.

### 2.3.2.17 ViewDefinition Type

The **ViewDefinition** type provides a definition of a view of a list.

#### 2.3.2.17.1 Schema

```
<xs:complexType name="ViewDefinition">
  <xs:group ref="ViewDefinitionChildElementGroup"/>
  <xs:attribute name="AggregateView" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="BaseViewID" type="xs:int" />
  <xs:attribute name="CssStyleSheet" type="xs:string" />
  <xs:attribute name="DefaultView" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DisplayName" type="xs:string" />
  <xs:attribute name="FailIfEmpty" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="FileDialog" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="FPModified" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Hidden" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="List" type="UniqueIdentifierWithoutBraces" />
  <xs:attribute name="Name" type="UniqueIdentifierWithBraces" />
  <xs:attribute name="ContentTypeID" type="ContentTypeId" />
  <xs:attribute name="OrderedView" type="TRUEFALSE" />
  <xs:attribute name="DefaultViewForContentType" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="IncludeRootFolder" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="PageType" type="xs:string" />
  <xs:attribute name="Path" type="RelativeFilePath" />
  <xs:attribute name="Personal" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="ReadOnly" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="RecurrenceRowset" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="RequiresClientIntegration" type="TRUEFALSE" default="FALSE"/>
```

```

<xs:attribute name="RowLimit" type="xs:int" />
<xs:attribute name="ShowHeaderUI" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Type" type="ViewType" default="HTML"/>
<xs:attribute name="Url" type="RelativeUrl" />
<xs:attribute name="UseSchemaXmlToolbar" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="WebPartOrder" type="xs:int" />
<xs:attribute name="WebPartZoneID" type="xs:string" />
<xs:attribute name="FreeForm" type="TRUEFALSE" />
<xs:attribute name="ImageUrl" type="xs:string" />
<xs:attribute name="SetupPath" type="RelativeFilePath" />
<xs:attribute name="ToolbarTemplate" type="xs:string" />
<xs:attribute name="MobileView" type="TRUEFALSE" default="FALSE"/>
<xs:attribute name="MobileDefaultView" type="TRUEFALSE" />
<xs:attribute name="MobileUrl" type="RelativeUrl" />
<xs:attribute name="Level" type="ViewPageLevel" default="1" />
<xs:attribute name="FrameState" type="xs:string" default="Normal" />
<xs:attribute name="IsIncluded" type="TRUEFALSE" default="TRUE" />
<xs:attribute name="IncludeVersions" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="HackLockWeb" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ModerationType" type="ViewModerationType" default="" />
<xs:attribute name="Scope" type="ViewScope" default="" />
<xs:attribute name="Threaded" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="TabularView" type="FALSE_Case_Insensitive_Else_Anything"
default="TRUE" />
</xs:complexType>

<xs:group name="ViewDefinitionChildElementGroup">
  <xs:all>
    <xs:element name="PagedRowset" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Toolbar" type="ToolbarDefinition" minOccurs="0" maxOccurs="1" />
    <xs:element name="Query" type="CamlQueryRoot" minOccurs="0" maxOccurs="1" />
    <xs:element name="ViewFields" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="FieldRef" type="FieldRefDefinitionView" minOccurs="0"
maxOccurs="unbounded" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="GroupByHeader" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="GroupByFooter" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>

```

```

        <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
</xs:complexType>
</xs:element>
<xs:element name="ViewHeader" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
<xs:element name="ViewBody" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
<xs:element name="ViewFooter" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
<xs:element name="RowLimitExceeded" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
<xs:element name="ViewEmpty" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
<xs:element name="PagedRecurrenceRowset" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>

```

```

</xs:element>
<xs:element name="PagedClientCallbackRowset" minOccurs="0" maxOccurs="1">
  <xs:complexType>
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
  </xs:complexType>
</xs:element>
<xs:element name="Aggregations" type="AggregationsDefinition" minOccurs="0"
maxOccurs="1" />
<xs:element name="OpenApplicationExtension" type="xs:string" minOccurs="0"
maxOccurs="1" />
<xs:element name="RowLimit" type="RowLimitDefinition" minOccurs="0" maxOccurs="1"
default="2147483647" />
<xs:element name="Mobile" type="MobileViewDefinition" minOccurs="0" maxOccurs="1" />
<xs:element name="ViewStyle" type="ViewStyleReference" minOccurs="0" maxOccurs="1" />
<xs:element name="CalendarSettings" minOccurs="0" maxOccurs="1">
  <xs:complexType>
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
  </xs:complexType>
</xs:element>
<xs:element name="CalendarViewStyles" type="CalendarViewStylesDefinition" minOccurs="0"
maxOccurs="1" />
<xs:element name="ViewBidiHeader" minOccurs="0" maxOccurs="1">
  <xs:complexType>
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
  </xs:complexType>
</xs:element>
<xs:element name="Script" minOccurs="0" maxOccurs="1" mixed="true">
  <xs:complexType>
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
  </xs:complexType>
</xs:element>
<xs:element name="ViewData" minOccurs="0" maxOccurs="1">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="FieldRef" type="FieldRefDefinitionViewData" minOccurs="3"
maxOccurs="5" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
<xs:element name="Formats" type="ViewFormatDefinitions" minOccurs="0" maxOccurs="1" />
<xs:element name="InlineEdit" type="TRUE_If_Present" minOccurs="0" maxOccurs="1" />
<xs:element name="ProjectedFields" type="ProjectedFieldsDefinitionType" minOccurs="0"
maxOccurs="1" />
<xs:element name="Joins" type="ListJoinsDefinitionType" minOccurs="0" maxOccurs="1" />

```

```

<xs:element name="Method" type="ViewMethodDefinition" minOccurs="0" maxOccurs="1" />
<xs:element name="ParameterBindings" minOccurs="0" maxOccurs="1">
  <xs:complexType>
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
  </xs:complexType>
</xs:element>
<xs:element name="Xsl" minOccurs="0" maxOccurs="1">
  <xs:complexType>
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
  </xs:complexType>
</xs:element>
<xs:element name="XslLink" minOccurs="0" maxOccurs="1" mixed="true">
  <xs:complexType>
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
  </xs:complexType>
</xs:element>
<xs:element name="JS" minOccurs="0" maxOccurs="1" mixed="true">
  <xs:complexType>
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
  </xs:complexType>
</xs:element>
<xs:element name="JSLink" minOccurs="0" maxOccurs="1" mixed="true">
  <xs:complexType>
    <xs:sequence>
      <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
    </xs:sequence>
    <xs:anyAttribute processContents="skip" />
  </xs:complexType>
</xs:element>
</xs:all>
</xs:group>

```

### 2.3.2.17.2 Attributes

**Name:** Internal identifier of the list view Web Part.

**Level:** Publishing level of the page that hosts the view.

**DisplayName:** Display name of the view.

**Type:** Type of the view.

**BaseViewID:** Identifier of the **base view** for the view.

**SetupPath:** Path to the ghosted document on the front-end Web server.

**Path:** Source path to the ghosted document. If the **SetupPath** attribute is specified, the reader MUST ignore this attribute and use the value of **SetupPath**.

**List:** Identifier of the list for the view.

**WebPartOrder:** Render order of the list view Web Part in the Web Part zone.

**WebPartZoneID:** Identifier of the Web Part zone that contains the list view Web Part.

**IsIncluded:** If **true**, the list view Web Part is visible in the current page.

**FrameState:** MUST be set to "Normal" or "Minimized". If not specified as "Minimized", the list schema consumer MUST treat **FrameState** as set to "Normal".

**ImageUrl:** URL of an image that serves as an icon of the view.

**ModerationType:** Moderation type of the view. The list schema consumer MUST ignore this value if content approval is not enabled for the list. **ModerationType** MUST be either an empty string or one of the values specified in the **ViewModerationType** simple type, as specified in section [2.3.1.9](#).

**Scope:** Recursive scope of the view.

**Hidden:** If **true**, the view MUST NOT be displayed in enumerations of views of this list—for example, in a view selector UI element. See also flag 0x00000008 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**ReadOnly:** If **true**, the view is read-only, and implementations MUST NOT grant any modifications to its properties. See also flag 0x00000020 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**RecurrenceRowset:** If **true**, the view expands recurring events. See also flag 0x00002000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**RequiresClientIntegration:** If **true**, the view MUST NOT be displayed to any user who does not possess the **UseClientIntegration** right. See also flag 0x40000000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**ShowHeaderUI:** The reader MUST ignore this attribute.

**FPModified:** If **true**, the view has been modified by a client application so that it might not be compatible with the Web interface for view modification. Implementations MUST restrict modifying any properties they do not parse and persist. See also flag 0x00000002 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**Threaded:** If **true**, the view is a threaded view for legacy discussion boards, such as lists with base type 3. Implementations MUST display results in a threaded fashion, and paging of results MUST be done in terms of threads, instead of by individual list items. See also flag VIEWFLAG\_THREADED 0x00010000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**IncludeRootFolder:** If **true**, the view retrieves the list item for the root folder of the view, in addition to the standard behavior of retrieving all list items contained within it. See flag 0x08000000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**DefaultView:** Default form of the specified type for the corresponding list. See also flag 0x00100000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**MobileView:** If **true**, the view is intended for display on mobile devices. See also flag 0x00800000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**MobileDefaultView:** If **true**, the view is displayed as the default view of this list when a mobile view is requested. See also flag 0x01000000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**MobileUrl:** Specifies the URL of the page hosting the list view that is suitable for mobile devices.

**CssStyleSheet:** Specifies a **cascading style sheet (CSS)** file to register when rendering the view.

**DefaultViewForContentType:** If **true**, the view is the default view presented when a view is requested for a particular content type. See also flag 0x10000000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**Personal:** If **true**, the view is a personal view, which **MUST** only be displayed to the user who created the view. See flag 0x00040000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**OrderedView:** If **true**, the view displays list items based on the item order of the list. See also flag 0x00400000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**IncludeVersions:** If **true**, the view displays historical versions of list items. See also flag 0x02000000 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**FailIfEmpty:** If the query for this view returns no rows and this attribute is **true**, implementations of the front-end Web server **MUST** return an HTTP 410 error when displaying this view as part of an HTTP request, instead of displaying a normal empty view body. See [\[RFC2068\]](#) section 10.4.11 for the specification of HTTP 410. See also flag 0x00000040 in [\[MS-WSSFO2\]](#) section 2.2.2.12

**HackLockWeb:** This value is unused and **MUST** be ignored.

**FreeForm:** If **true**, the view presents data in a non-tabular fashion. Implementations can format results in a manner compatible with free-form presentation. See also flag 0x00000080 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**FileDialog:** If **true**, the view is suitable for being displayed in an HTML-based file navigation dialog box to client applications. See also flag 0x00000100 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**AggregateView:** If **true**, the view has functionality for aggregating data across multiple XML documents in an XML form library. See also flag 0x00000400 in [\[MS-WSSFO2\]](#) section 2.2.2.12.

**ToolbarTemplate:** Name of a pre-defined control template for the view toolbar.

**ContentTypeID:** Content type identifier of the view. This string specifies the identifier of the content type with which the view is associated so that the view is available only on folders of this content type.

**PageType:** The reader **MUST** ignore this attribute.

**RowLimit:** The reader **MUST** ignore this attribute.

**TabularView:** If **true**, the view presents data in a tabular fashion, including check boxes for manipulating list items in the view.

**UseSchemaXmlToolbar:** If **true**, the server **MUST** use the toolbar from the list definition file on the front-end Web server. Otherwise, the pre-defined toolbar template **MUST** be used.

**Url:** URL of the view.

### 2.3.2.17.3 Child Elements

**PagedRowset:** Specifies the rendering of navigation between pages. A reader MUST ignore this value if **PagedClientCallbackRowset** and **PagedRecurrenceRowset** are provided.

**Query:** Query of the view. See **Query Types** (section [2.2](#)).

**Toolbar:** Specifies the rendering of a toolbar.

**ViewFields:** List of fields (1) included in this view. See **FieldRefDefinitionView Type** (section [2.3.2.19](#)).

**GroupByHeader:** Specifies rendering of the header element for **GroupBy** sections.

**GroupByFooter:** Specifies the rendering of the footer element for **GroupBy** sections.

**ViewHeader:** Specifies the rendering of the header of the view.

**ViewBidiHeader:** Specifies the bidirectional locale header of the view. A server MUST ignore this attribute.

**ViewBody:** Specifies the rendering of the body of the view.

**ViewFooter:** Specifies the rendering the footer of the view.

**ViewEmpty:** Specifies the rendering of the view when the view returns no items.

**PagedClientCallbackRowset:** Specifies rendering of the page viewer and navigation between pages—for example, **Next** button and **Previous** button.

**PagedRecurrenceRowset:** Specifies rendering of the page viewer and navigation between pages—for example, **Next** button and **Previous** button.

**RowLimit:** Specifies the row limit for the view. See **RowLimitDefinition Type** (section [2.3.2.14](#)). If the body of **RowLimit** is set to a number that is less than 1 or to a value that is not a number, renditions of the view MUST return all items that meet the filter condition.

**Mobile:** Specifies properties related to the mobile view. See **MobileViewDefinition Type** (section [2.3.2.24](#)).

**RowLimitExceeded:** If this view is a paged view, specifies the rendering when the items returned exceeds the **RowLimit**.

**Formats:** This element and its child elements specify the format of the view.

**InlineEdit:** If **true**, the view has functionality for editing list items in place on the current page.

**Aggregations:** Contains a list of fields (1) by which the view is aggregated.

**ViewStyle:** Contains an identifier attribute that specifies the style of this view. The identifier MUST be an integer that uniquely identifies the view style.

**OpenApplicationExtension:** Specifies a hint for the kind of application to be used to edit the view. It MUST be in the form of a file extension, such as .doc. The reader can look up the preferred application for that extension and use that application to edit this view. If not specified, the server MUST present a default UI to edit the view.

**ViewData:** Specifies a reference to the field (1) that is used to render the calendar view or Gantt view. If the view is a calendar view or Gantt view, this MUST be specified. For other view types, it MUST be ignored.

**CalendarSettings:** Specifies implementation-specific settings for rendering list items in a calendar view.

**CalendarViewStyles:** This element and its child elements specify a calendar-specific view style for a view of type **Calendar**. If the view is a calendar view, this section MUST be specified. For other view types, it MUST be ignored.

**ProjectedFields:** This element and its child elements specify the list of fields to be projected from the joined lists, as specified by the **Joins** element. See **ProjectedFieldsDefinition Type** (section [2.2.2.19](#)).

**Joins:** This element and its child elements specify the list of joins to be made part of the query. See **ListJoinsDefinition Type** (section [2.2.2.21](#)).

**Method:** Specifies a **Finder** and the **FilterDescriptor** values to use when rendering a view of an external list. If the list is not an external list, **Method** MUST be ignored. See [\[MS-WSSCAP\]](#) section [2.2.5.2](#).

**ParameterBindings:** Specifies implementation-specific parameter bindings for rendering list items in the view.

**Xsl:** Specifies implementation-specific XSL for rendering list items in the view.

**XslLink:** Specifies a file with implementation-specific XSL for rendering list items in the view.

**JS:** Specifies the inline JavaScript used for the view. [<4>](#)

**JSLink:** Specifies the JavaScript files used for the view. [<5>](#)

### 2.3.2.18 FieldRefDefinitionViewData Type

The **FieldRefDefinitionViewData** type specifies extra fields (1) that are used to render a calendar view or a Gantt view.

#### 2.3.2.18.1 Schema

```
<xs:complexType name="FieldRefDefinitionViewData">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="Type" type="xs:string" use="required" />
</xs:complexType>
```

#### 2.3.2.18.2 Attributes

**Name:** Name of the field (1) for which the calendar view or Gantt view is used for the purpose specified by the **Type**.

**Type:** For a calendar view, the following table describes possible values.

Value	Description
<b>CalendarMonthTitle</b>	Title of a monthly calendar item.

Value	Description
<b>CalendarWeekTitle</b>	Title of a weekly calendar item.
<b>CalendarDayTitle</b>	Title of a daily calendar item.
<b>CalendarWeekLocation</b>	Location of a weekly calendar item.
<b>CalendarDayLocation</b>	Location of a daily calendar item.

For a Gantt view, the following table describes possible values.

Value	Description
<b>GanttTitle</b>	Title of the Gantt view item.
<b>GanttStartDate</b>	Start date of the Gantt view item.
<b>GanttEndDate</b>	End date of the Gantt view item.
<b>GanttPercentComplete</b>	Optional field (1) used as the completeness percentage of a weekly Gantt view item.

### 2.3.2.18.3 Child Elements

None.

### 2.3.2.19 FieldRefDefinitionView Type

The **FieldRefDefinitionView** type specifies the fields (1) to be returned for the view.

#### 2.3.2.19.1 Schema

```
<xs:complexType name="FieldRefDefinitionView">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="Explicit" type="TRUE_If_Present" use="optional" default="FALSE"/>
</xs:complexType>
```

#### 2.3.2.19.2 Attributes

**Name:** Name of the field (1) that is included in the view.

**Explicit:** The writer **MUST** specify whether the field (1) is explicitly declared in the view definition. The reader **MUST** ignore this attribute.

#### 2.3.2.19.3 Child Elements

None.

### 2.3.2.20 ViewStyleReference Type

The **ViewStyleReference** type specifies the style of a view.

### 2.3.2.20.1 Schema

```
<xs:complexType name="VisualStyleReference">
  <xs:attribute name="ID" type="xs:int" use="optional" />
</xs:complexType>
```

### 2.3.2.20.2 Attributes

**ID:** MUST correspond to an integer identifier of a view style definition, which is defined on the front-end Web server.

### 2.3.2.20.3 Child Elements

None.

### 2.3.2.21 ViewFormatDefinitions Type

The **ViewFormatDefinitions** type specifies the format information of the view.

#### 2.3.2.21.1 Schema

```
<xs:complexType name="ViewFormatDefinitions">
  <xs:sequence>
    <xs:element name="FormatDef" type="FormatDefDefinition" minOccurs="0"
maxOccurs="unbounded" />
    <xs:element name="Format" type="FormatDefinition" minOccurs="0" maxOccurs="unbounded"
/>
  </xs:sequence>
</xs:complexType>
```

#### 2.3.2.21.2 Attributes

None.

#### 2.3.2.21.3 Child Elements

**FormatDef:** Specifies a format.

**Format:** This element and its child elements specify the format for a field (1) in the view. A client uses this to render the field (1).

### 2.3.2.22 FormatDefDefinition Type

The **FormatDefDefinition** type specifies a format definition.

#### 2.3.2.22.1 Schema

```
<xs:complexType name="FormatDefDefinition">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="Type" type="xs:string" use="required" />
      <xs:attribute name="Value" type="xs:string" use="required" />
    </xs:extension>
  </xs:simpleContent>
```

```
</xs:complexType>
```

### 2.3.2.22.2 Attributes

**Type:** Name of the **Format** property, such as "ColWidth" or "RowHeight".

**Value:** The value for the specified format type.

### 2.3.2.22.3 Child Elements

None.

## 2.3.2.23 FormatDefinition Type

The **FormatDefinition** type specifies format information for the field (1).

### 2.3.2.23.1 Schema

```
<xs:complexType name="FormatDefinition">
  <xs:sequence>
    <xs:element name="FormatDef" type="FormatDefDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Name" type="xs:string" use="required" />
</xs:complexType>
```

### 2.3.2.23.2 Attributes

**Name:** Name of a specific field (1) to which to apply the format.

### 2.3.2.23.3 Child Elements

**FormatDef:** Specifies a format.

## 2.3.2.24 MobileViewDefinition Type

The **MobileViewDefinition** type specifies information for the mobile view.

### 2.3.2.24.1 Schema

```
<xs:complexType name="MobileViewDefinition">
  <xs:attribute name="MobileSimpleViewField" type="xs:string" use="required" />
  <xs:attribute name="MobileItemLimit" type="xs:string" use="required" />
</xs:complexType>
```

### 2.3.2.24.2 Attributes

**MobileSimpleViewField:** Specifies the name of the field to display in the simple mobile view.

**MobileItemLimit:** Specifies the number of items returned by the mobile view. If not specified, the view is not paged.

### 2.3.2.24.3 Child Elements

None.

## 2.4 Content Type Schema Definitions

Types in this section describe a content type in various contexts, along with its components in each context.

### 2.4.1 ContentTypeDefinition Type

The **ContentTypeDefinition** type specifies a content type and its associated components.

#### 2.4.1.1 Schema

```
<xs:complexType name="ContentTypeDefinition">
  <xs:all>
    <xs:element name="Fields" type="FieldRefDefinitionCTs" minOccurs="0" maxOccurs="1" />
    <xs:element name="FieldRefs" type="FieldRefDefinitionCTs" minOccurs="0" maxOccurs="1" />
  />
  <xs:element name="XmlDocuments" type="XmlDocumentDefinitionCollection" minOccurs="0"
maxOccurs="1" />
  <xs:element name="Folder" type="FolderReference" minOccurs="0" maxOccurs="1" />
  <xs:element name="DocumentTemplate" type="ContentTypeDocumentTemplateDefinition"
minOccurs="0" maxOccurs="1" />
</xs:all>
  <xs:attribute name="ID" type="ContentTypeId" use="required" />
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="Group" type="xs:string" use="optional" />
  <xs:attribute name="ReadOnly" type="TRUE_NegOne_Else_Anything" use="optional"
default="FALSE"/>
  <xs:attribute name="Hidden" type="TRUE_NegOne_Else_Anything" use="optional"
default="FALSE"/>
  <xs:attribute name="Description" type="xs:string" use="optional" />
  <xs:attribute name="Sealed" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
  <xs:attribute name="V2ListTemplateName" type="xs:string" use="optional"/>
  <xs:attribute name="Version" type="IntNonNegative" use="optional" default="0" />
  <xs:attribute name="FeatureId" type="UniqueIdentifierWithBraces" use="optional" />
  <xs:attribute name="Edited" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
  <xs:attribute name="ProgId" type="xs:string" use="optional" />
  <xs:attribute name="NewDocumentControl" type="xs:string" use="optional" />
  <xs:attribute name="PushDownChangedResourceFilesOnly"
type="TRUE_Case_Sensitive_Else_Anything" use="optional" default="FALSE" />
  <xs:attribute name="RequireClientRenderingOnNew" type="TRUE_Case_Sensitive_Else_Anything"
use="optional" default="TRUE" />
</xs:complexType>
```

#### 2.4.1.2 Attributes

**ID:** Identifier for this content type.

**Name:** Name of the content type.

**Group:** Name of the **content type group** of this content type.

**ReadOnly:** Specifies whether the content type can be edited.

**Hidden:** Specifies whether the content type appears in the UI.

**Description:** Description of the content type.

**Sealed:** Specifies whether another content type can inherit from the current content type.

**V2ListTemplateName:** Specifies an additional component for field names to ensure their uniqueness.

**Version:** Current version of the content type. The writer MUST increment the value by 1 each time the content type definition is changed. The reader MUST ignore this attribute.

**FeatureId:** Specifies the feature with which this content type is associated.

**Edited:** The reader MUST ignore this attribute.

**ProgId:** Specifies a preferred application to open a **document** of this content type. This element distinguishes between applications that save files with a specified **file extension**, for example, editors for .html or .xml files.

**NewDocumentControl:** Specifies a preferred application to open a document of this content type.

**PushDownChangedResourceFilesOnly:** Specifies whether to copy only changed resource files to derived content types during a push-down operation.

**RequireClientRenderingOnNew:** Specifies whether new list items of this content type open in a separate client-side application.

### 2.4.1.3 Child Elements

**Fields:** Contains references to fields associated with this content type. The protocol server MUST write either **Fields** or **FieldRefs**, but not both.

**FieldRefs:** Contains references to fields (1) associated with this content type. The protocol server MUST write either **Fields** or **FieldRefs**, but not both.

**XmlDocuments:** Collection of XML documents associated with this content type, which can include forms and **event receiver** manifests.

**Folder:** Specifies the **resource folder** to be used by this content type.

**DocumentTemplate:** Specifies the document template of the content type.

### 2.4.2 FieldRefDefinitionCTs Type

The **FieldRefDefinitionCTs** type describes the ways in which a content type can reference fields (1) in its encompassing list.

#### 2.4.2.1 Schema

```
<xs:complexType name="FieldRefDefinitionCTs" mixed="true" >
  <xs:sequence>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="FieldRef" type="FieldRefDefinitionCT" />
      <xs:element name="Field" type="FieldDefinitionCTRemove" />
    </xs:choice>
  </xs:sequence>
```

</xs:complexType>

### 2.4.2.2 Attributes

None.

### 2.4.2.3 Child Elements

**FieldRef**: Reference to a field (1) that belongs to this content type.

**Field**: Reference to a field (1) that was removed from this content type.

### 2.4.3 FieldRefDefinitionCT Type

The **FieldRefDefinitionCT** type specifies a reference to a field (1) in a content type.

#### 2.4.3.1 Schema

```
<xs:complexType name="FieldRefDefinitionCT">
  <xs:all>
    <xs:element name="Default" type="xs:string" minOccurs="0" maxOccurs="1" />
  </xs:all>
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="Required" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
  default="FALSE" />
  <xs:attribute name="Hidden" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
  default="FALSE" />
  <xs:attribute name="Customization" type="xs:string" use="optional" />
  <xs:attribute name="ShowInNewForm" type="FALSE_Case_Insensitive_Else_Anything"
  use="optional" default="TRUE" />
  <xs:attribute name="ShowInEditForm" type="FALSE_Case_Insensitive_Else_Anything"
  use="optional" default="TRUE" />
  <xs:attribute name="DisplayName" type="xs:string" use="optional" />
  <xs:attribute name="ReadOnly" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
  default="FALSE" />
  <xs:attribute name="PITarget" type="xs:string" use="optional" />
  <xs:attribute name="PrimaryPITarget" type="xs:string" use="optional" />
  <xs:attribute name="PIAttribute" type="xs:string" use="optional" />
  <xs:attribute name="PrimaryPIAttribute" type="xs:string" use="optional" />
  <xs:attribute name="Aggregation" type="xs:string" use="optional" />
  <xs:attribute name="Node" type="xs:string" use="optional" />
  <xs:attribute name="Format" type="xs:string" use="optional" />
  <xs:attribute name="NumLines" type="xs:string" default="6" />
  <xs:attribute name="Sealed" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
  default="FALSE" />
  <xs:attribute name="Sortable" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
  default="TRUE" />
  <xs:attribute name="FromBaseType" type="TRUE_Case_Insensitive_Else_Anything"
  use="optional" default="FALSE" />
  <xs:attribute name="Filterable" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
  default="TRUE" />
  <xs:attribute name="FilterableNoRecurrence" type="TRUE_Case_Sensitive_Else_Anything"
  use="optional" default="FALSE" />
  <xs:attribute name="ShowInDisplayForm" use="optional" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="ShowInFileDialog" type="FALSE_Case_Insensitive_Else_Anything"
  use="optional" default="TRUE" />
</xs:complexType>
```

```

    <xs:attribute name="ShowInListSettings" use="optional" type="TRUEFALSE" default="FALSE"
  />
  <xs:attribute name="Description" type="xs:string" use="optional" />
</xs:complexType>

```

### 2.4.3.2 Attributes

See attributes of **FieldRefDefinitionField** in [\[MS-WSSFO2\]](#) section 2.2.8.3.9, and **FieldDefinition** in [\[MS-WSSFO2\]](#) section 2.2.8.3.3. The reader MUST override the **Required**, **Hidden**, **Customization**, **ShowInNewForm**, **ShowInEditForm**, **DisplayName**, **ReadOnly**, **PITarget**, **PrimaryPITarget**, **PIAttribute**, **PrimaryPIAttribute**, **Aggregation**, **Node**, and **Format** attributes that are defined in the field definition.

### 2.4.3.3 Child Elements

**Default:** See child elements of **FieldRefDefinitionField** in [\[MS-WSSFO2\]](#) section 2.2.8.3.9, and **FieldDefinition** in [\[MS-WSSFO2\]](#) section 2.2.8.3.3.

## 2.4.4 ContentTypeDocumentTemplateDefinition Type

The **ContentTypeDocumentTemplateDefinition** type is a container for the document template of a content type.

### 2.4.4.1 Schema

```

<xs:complexType name="ContentTypeDocumentTemplateDefinition">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="TargetName" type="RelativeUrl" use="required"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

```

### 2.4.4.2 Attribute

**TargetName:** URL of the document template file associated with this content type.

### 2.4.4.3 Child Elements

None.

## 2.4.5 ContentTypeReference Type

The **ContentTypeReference** type is a container for a reference to a content type.

### 2.4.5.1 Schema

```

<xs:complexType name="ContentTypeReference">
  <xs:all>
    <xs:element name="Folder" type="FolderReference" minOccurs="0" maxOccurs="1" />
    <xs:element name="DocumentTemplate" type="ContentTypeDocumentTemplateDefinition"
  minOccurs="0" maxOccurs="1" />
  </xs:all>

```

```

    <xs:attribute name="ID" type="ContentTypeId" use="required" />
    <xs:attribute name="Edited" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
  </xs:complexType>

```

### 2.4.5.2 Attributes

**ID:** Identifier for the content type being referenced.

**Edited:** The reader MUST ignore this attribute.

### 2.4.5.3 Child Elements

**Folder:** Specifies a reference to the new resource folder for this content type. If it is not specified, the reader MUST read the resource folder specified in the original content type definition.

**DocumentTemplate:** Specifies a reference to an override document template to use for this content type. If it is not included, the reader MUST use the document template specified in the original content type schema.

## 2.4.6 ContentTypeReferences Type

### 2.4.6.1 Schema

```

<xs:complexType name="ContentTypeReferences">
  <xs:sequence>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="ContentTypeRef" type="ContentTypeReference" />
      <xs:element name="ContentType" type="ContentTypeDefinition" />
    </xs:choice>
  </xs:sequence>
</xs:complexType>

```

### 2.4.6.2 Attributes

None.

### 2.4.6.3 Child Elements

**ContentTypeRef:** Specifies a reference to an existing content type.

**ContentType:** Specifies a definition of a new content type for the list.

## 2.4.7 FolderReference Type

The **FolderReference** type specifies a resource folder for a content type.

### 2.4.7.1 Schema

```

<xs:complexType name="FolderReference">
  <xs:sequence />
  <xs:attribute name="TargetName" type="RelativeUrl" use="required" />
</xs:complexType>

```

### 2.4.7.2 Attributes

**TargetName:** URL of the resource folder associated with this content type. This value MUST be relative to the content type gallery URL of the site (2) and MUST be less than three levels deep.

### 2.4.7.3 Child Elements

None.

## 2.4.8 ContentypeDatabase Type

The **ContentypeDatabase** type provides an overall container for content types in the **tp\_ContentTypes** column as returned in the **ListMetadata** result set. See [\[MS-WSSFO2\]](#) section 2.2.5.12.

### 2.4.8.1 Schema

```
<xs:complexType name="ContentypeDatabase">
  <xs:sequence>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="ContentypeRef" type="ContentypeReference" />
      <xs:element name="Contentype" type="ContentypeDefinitionTP" />
    </xs:choice>
  </xs:sequence>
</xs:complexType>
```

### 2.4.8.2 Attributes

None.

### 2.4.8.3 Child Elements

**ContentypeRef:** A reference to an existing content type schema for this list.

**Contentype:** A content type schema for this list. If only the **ID** attribute is specified, this element specifies a reference to an existing content type that is defined as a template on the front-end Web server. If additional attributes are specified, the element is a definition of a new content type for the list.

## 2.4.9 ContentypeDefinitionTP Type

The **ContentypeDefinitionTP** type specifies a content type and its associated components.

**ContentypeDefinitionTP** has the same structure as **ContentypeDefinition**. However, if only the **ID** attribute of **ContentypeDefinitionTP** is specified, the content type specifies a content type schema that has been deleted.

### 2.4.9.1 Schema

```
<xs:complexType name="ContentypeDefinitionTP">
  <xs:all>
    <xs:element name="Fields" type="FieldRefDefinitionCTs" minOccurs="0" maxOccurs="1" />
  <xs:element name="FieldRefs" type="FieldRefDefinitionCTs" minOccurs="0" maxOccurs="1" />
</xs:complexType>
```

```

    <xs:element name="XmlDocuments" type="XmlDocumentDefinitionCollection" minOccurs="0"
maxOccurs="1" />
    <xs:element name="Folder" type="FolderReference" minOccurs="0" maxOccurs="1" />
    <xs:element name="DocumentTemplate" type="ContentTypeDocumentTemplateDefinition"
minOccurs="0" maxOccurs="1" />
  </xs:all>
  <xs:attribute name="ID" type="ContentTypeId" use="required" />
  <xs:attribute name="Name" type="xs:string" use="optional" />
  <xs:attribute name="Group" type="xs:string" use="optional" />
  <xs:attribute name="ReadOnly" type="TRUE_NegOne_Else_Anything" use="optional"
default="FALSE"/>
  <xs:attribute name="Hidden" type="TRUE_NegOne_Else_Anything" use="optional"
default="FALSE"/>
  <xs:attribute name="Description" type="xs:string" use="optional" />
  <xs:attribute name="Sealed" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
  <xs:attribute name="V2ListTemplateName" type="xs:string" use="optional"/>
  <xs:attribute name="Version" type="IntNonNegative" use="optional" default="0" />
  <xs:attribute name="FeatureId" type="UniqueIdentifierWithBraces" use="optional" />
  <xs:attribute name="Edited" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
  <xs:attribute name="ProgId" type="xs:string" use="optional" />
  <xs:attribute name="NewDocumentControl" type="xs:string" use="optional" />
  <xs:attribute name="PushDownChangedResourceFilesOnly"
type="TRUE_Case_Sensitive_Else_Anything" use="optional" default="FALSE" />
  <xs:attribute name="RequireClientRenderingOnNew" type="TRUE_Case_Sensitive_Else_Anything"
use="optional" default="TRUE" />
</xs:complexType>

```

#### 2.4.9.2 Attributes

See **ContentTypeDefinition Type** (section [2.4.1](#)).

#### 2.4.9.3 Child Elements

See **ContentTypeDefinition Type** (section [2.4.1](#)).

#### 2.4.10 FieldDefinitionCTRemove Type

The **FieldDefinitionCTRemove** type specifies a field definition that was removed from a content type schema.

##### 2.4.10.1 Schema

```

<xs:complexType name="FieldDefinitionCTRemove">
  <xs:complexContent>
    <xs:extension base="FieldDefinition"/>
  </xs:complexContent>
</xs:complexType>

```

##### 2.4.10.2 Attributes

**ID**: Identifier of the field definition to remove from this content type.

See **FieldDefinition** in [\[MS-WSSFO2\]](#) section 2.2.8.3.3.

### 2.4.10.3 Child Elements

See **FieldDefinition** in [\[MS-WSSFO2\]](#) section 2.2.8.3.3.

### 2.4.11 XmlDocumentDefinition Type

The **XmlDocumentDefinition** type is a container that describes a custom-extensible type associated with a content type definition.

#### 2.4.11.1 Schema

```
<xs:complexType name="XmlDocumentDefinition" mixed="true">
  <xs:complexContent>
    <xs:restriction base="xs:anyType">
      <xs:sequence>
        <xs:any namespace="##other" minOccurs="0" maxOccurs="unbounded"
processContents="skip" />
      </xs:sequence>
      <xs:attribute name="NamespaceURI" type="xs:string" use="required" />
    </xs:restriction>
  </xs:complexContent>
</xs:complexType>
```

#### 2.4.11.2 Attributes

**NamespaceURI:** Namespace that corresponds to the specified document.

#### 2.4.11.3 Child Elements

The child elements of this container are vendor extensible. Well-known elements are specified in the following section.

```
<FormTemplates type="FormTemplateDefinitions"
xmlns="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms" />
<FormUrls type="FormUrlDefinitions"
xmlns="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms/url" />
<Receivers type="ReceiverDefinitionCollection"
xmlns="http://schemas.microsoft.com/sharepoint/events" />
<Namespaces type="NamespacesDefinitions" xmlns="http://schemas.microsoft.com/sharepoint" />
<PolicyDirtyBag type="PolicyDirtyBag" xmlns="microsoft.office.server.policy.changes" />
<Policy type="Policy" xmlns="office.server.policy" />
```

The following elements can be included with a content type schema and are used to specify additional functionality for a content type.

**FormTemplates:** **Form templates** associated with the specified content type. See **FormTemplateDefinitions Type** (section [2.5.1.3](#)).

**FormUrls:** Form (1) URLs associated with the specified content type. See **FormUrlDefinitions Type** (section [2.5.1.4](#)).

**Receivers:** Event receiver manifests associated with the specified content type. See **ReceiverDefinitions Type** (section [2.5.1.21](#)).

**Namespaces:** XML namespace, as specified in [\[XMLNS\]](#), registrations associated with the specified content type. See **NamespaceDefinitions Type** (section [2.5.1.6](#)).

**PolicyDirtyBag:** Contains a list of changes made to a policy. See **PolicyDirtyBag Type** (section [2.5.1.7](#)).

**Policy:** Contains information management policy. See **Policy Type** (section [2.5.1.9](#)).

**Content:** Any of the preceding elements or vendor-extensible elements can have additional body text for this definition.

## 2.4.12 XmlDocumentDefinitionCollection Type

The **XmlDocumentDefinitionCollection** type is a container that describes additional custom documents that are associated with a content type.

### 2.4.12.1 Schema

```
<xs:complexType name="XmlDocumentDefinitionCollection">
  <xs:sequence>
    <xs:element name="XmlDocument" type="XmlDocumentDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

### 2.4.12.2 Attributes

None.

### 2.4.12.3 Child Elements

**XmlDocument:** An extensible type associated with this content type.

## 2.5 Extensible Types

### 2.5.1 Content Type Custom Simple Types

#### 2.5.1.1 customXsn Type

The **customXsn** type is an extended XML element that defines a custom **Document Information Panel** template.

##### 2.5.1.1.1 Schema

```
<xs:element name="customXsn">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="xsnLocation" type="xs:string" />
      <xs:element name="cached" type="xs:boolean" />
      <xs:element name="openByDefault" type="xs:boolean" />
      <xs:element name="xsnScope" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

### 2.5.1.1.2 Attributes

None.

### 2.5.1.1.3 Child Elements

**xsnLocation:** URL or **Uniform Resource Name (URN)** location of the XSN file for the custom Document Information Panel. This element **MUST** be empty if a content type does not have a custom Document Information Panel.

**cached:** **MUST** be set to **true** if the custom Document Information Panel generates its own layout to display the data.

**openByDefault:** **MUST** be set to **true** to always show the custom Document Information Panel solution when the document is opened and first saved for this content type.

**xsnScope:** Scope to which the custom Document Information Panel template applies.

## 2.5.1.2 FormDefinitions Type

The **FormDefinitions** type specifies a collection of form definitions associated with this content type.

### 2.5.1.2.1 Schema

```
<xs:complexType name="FormDefinitions">
  <xs:sequence>
    <xs:element name="Form" type="FormDefinition" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

### 2.5.1.2.2 Attributes

None.

### 2.5.1.2.3 Child Elements

**Form** A form definition.

## 2.5.1.3 FormTemplateDefinitions Type

The **FormTemplateDefinitions** type specifies the names of control templates for forms in a list.

### 2.5.1.3.1 Schema

```
<xs:complexType name="FormTemplateDefinitions" mixed="true">
  <xs:sequence>
    <xs:element name="Display" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="Edit" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="New" type="xs:string" minOccurs="0" maxOccurs="1" />
  </xs:sequence>
</xs:complexType>
```

### 2.5.1.3.2 Attributes

None.

### 2.5.1.3.3 Child Elements

**Display:** Specifies a control template for the display form of an item.

**Edit:** Specifies a control template for the edit form of an item.

**New:** Specifies a control template for the new form of an item.

### 2.5.1.4 FormUrlDefinitions Type

The **FormUrlDefinitions** type specifies a URL for various forms in a list.

#### 2.5.1.4.1 Schema

```
<xs:complexType name="FormUrlDefinitions">
  <xs:sequence>
    <xs:element name="Display" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="Edit" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="New" type="xs:string" minOccurs="0" maxOccurs="1" />
  </xs:sequence>
</xs:complexType>
```

#### 2.5.1.4.2 Attributes

None.

#### 2.5.1.4.3 Child Elements

**Display:** Form tokenized URL for the display form of an item.

**Edit:** Form tokenized URL for the edit form of an item.

**New:** Form tokenized URL for the new form of an item.

A form tokenized URL MUST be processed in one of the following manners:

- If the URL starts with a slash (/), the URL MUST be treated as a **server-relative URL**.
- If the URL starts with "~sitecollection/", the server MUST prefix the form URL with the server-relative URL of the parent site collection.
- If the URL starts with "~site/", the server MUST prefix the form URL with the server-relative URL of the parent site (2).
- If the URL starts with "~list/", the server MUST prefix the form URL with the server-relative URL of the parent list.
- Otherwise, the server MUST prefix the form URL with the server-relative URL of the site (2).

#### 2.5.1.5 NamespaceDefinition Type

The **NamespaceDefinition** type contains a registration of a namespace.

### 2.5.1.5.1 Schema

```
<xs:complexType name="NamespaceDefinition" mixed="true">
  <xs:attribute name="prefix" type="xs:string" use="required" />
  <xs:attribute name="value" type="xs:string" use="required" />
</xs:complexType>
```

### 2.5.1.5.2 Attributes

**prefix:** XML namespace prefix for the namespace registration.

**value:** Value of the XML namespace being registered.

### 2.5.1.5.3 Child Elements

None.

## 2.5.1.6 NamespaceDefinitions Type

The **NamespaceDefinitions** type is a container for a set of XML namespace registrations.

### 2.5.1.6.1 Schema

```
<xs:complexType name="NamespaceDefinitions" mixed="true">
  <xs:sequence>
    <xs:element name="Namespace" type="NamespaceDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

### 2.5.1.6.2 Attributes

None.

### 2.5.1.6.3 Child Elements

**Namespace:** A registration of an XML namespace and its associated XML namespace prefix.

## 2.5.1.7 PolicyDirtyBag Type

The **PolicyDirtyBag** type contains a list of changes made to a policy. For example, it tracks when a policy feature has been added or removed.

### 2.5.1.7.1 Schema

```
<xs:complexType name="PolicyDirtyBag">
  <xs:sequence minOccurs="0" maxOccurs="1">
    <xs:any namespace="##other" minOccurs="0" maxOccurs="unbounded" processContents="skip" />
  </xs:sequence>
</xs:complexType>
```

### 2.5.1.7.2 Attributes

None.

### 2.5.1.7.3 Child Elements

The **PolicyDirtyBag** element contains a list of changes made to a policy. Each child element is a change to one of the policy features for the policy with **featureId** corresponding to the element name. The child elements of this container are vendor extensible. Well-known elements are specified in the following schema.

```
<s:element name="Microsoft.Office.RecordsManagement.PolicyFeatures.PolicyLabel"
type="PolicyFeatureOperation" />
<s:element name="Microsoft.Office.RecordsManagement.PolicyFeatures.PolicyAudit"
type="PolicyFeatureOperation" />
<s:element name="Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration"
type="PolicyFeatureOperation" />
<s:element name="Microsoft.Office.RecordsManagement.PolicyFeatures.Barcode"
type="PolicyFeatureOperation" />
```

Each element MUST conform to the schema of the **PolicyFeatureOperation Type** (section [2.5.1.8](#)).

### 2.5.1.8 PolicyFeatureOperation Type

The **PolicyFeatureOperation** type specifies a change to a policy item.

#### 2.5.1.8.1 Schema

```
<xs:complexType name="PolicyFeatureOperation">
  <xs:attribute name="op" type="xs:string" use="required" />
</xs:complexType>
```

#### 2.5.1.8.2 Attributes:

**op**: The type of change to a policy feature. The following table describes possible values.

Value	Description
<b>Add</b>	A policy feature is added.
<b>Delete</b>	A policy feature is removed.
<b>Change</b>	A policy feature has been changed.

#### 2.5.1.8.3 Child Elements

None.

### 2.5.1.9 Policy Type

The **Policy** type represents a **policy**.

### 2.5.1.9.1 Schema

```
<xs:complexType name="policy">
  <xs:sequence>
    <xs:element name="Name" type="xs:string" />
    <xs:element name="Description" type="xs:string" minOccurs="0" />
    <xs:element name="Statement" type="xs:string" minOccurs="0" />
    <xs:element name="PolicyItems" minOccurs="0" >
      <xs:complexType>
        <xs:sequence>
          <xs:element name="PolicyItem" type="policyItem" minOccurs="0" maxOccurs="unbounded"
        />
      </xs:sequence>
    </xs:complexType>
  </xs:sequence>
  <xs:attribute name="id" type="UniqueIdentifierWithoutBracesOrEmpty" use="required" />
  <xs:attribute name="local" type="xs:boolean" use="required" />
</xs:complexType>
```

### 2.5.1.9.2 Attributes

**id:** Policy identifier, which MUST be empty if **local** is set to **true**. Otherwise, MUST be a GUID.

**local:** Specifies whether the policy is locally defined, that is, it applies only to a specific scope, in contrast to a reference to a policy defined at an implementation-specific [6](#) scope.

### 2.5.1.9.3 Child Elements

**Description:** Administrative description of the policy.

**Name:** Name of the policy.

**PolicyItems:** List of policy items applicable to the policy.

**Statement:** Textual description of applicable policies to give helpful information to users.

### 2.5.1.10 PolicyItem Type

The **PolicyItem** type specifies settings for a policy feature.

#### 2.5.1.10.1 Schema

```
<xs:complexType name="policyItem">
  <xs:sequence>
    <xs:element name="Name" type="xs:string" />
    <xs:element name="Statement" type="xs:string" minOccurs="0" />
    <xs:element name="Description" type="xs:string" minOccurs="0" />
    <xs:element name="CustomData" type="customData" minOccurs="0" />
  </xs:sequence>
  <xs:attribute name="featureId" type="xs:string" use="required" />
  <xs:attribute name="BlockPreview" type="xs:boolean" />
  <xs:attribute name="UniqueId" type="xs:string" />
</xs:complexType>
```

### 2.5.1.10.2 Attributes

**featureId:** Identifier of a policy feature. This identifier is vendor extensible for implementation-specific policy features. The following table describes well-known values.

featureId	Policy feature description
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Barcode</b>	Generates an implementation-specific barcode image for documents.
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.PolicyLabel</b>	Generates implementation-specific label images for documents based on their <b>document properties</b> .
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.PolicyAudit</b>	Logs a record of user actions to an <b>audit log</b> .
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration</b>	Manages the implementation-specific retention lifecycle of content. For example, this can be used to archive and delete content according to a schedule.

**BlockPreview:** Reserved. MUST be set to **false** and MUST be ignored.

**UniqueId:** Identifier of a policy item. MUST be a GUID.

### 2.5.1.10.3 Child Elements

**Name:** Name of the policy item.

**Description:** Description of the policy item.

**Statement:** Reserved and MUST NOT be present.

**CustomData:** Container for additional information about the policy item.

```
<xs:complexType name="customData">
  <xs:sequence>
    <xs:any processContents="lax" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

The child element(s) of **CustomData** are vendor extensible. The following table specifies the complex type for well-known policy features.

featureId	Complex type
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Barcode</b>	Barcode
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.PolicyLabel</b>	Label
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.PolicyAudit</b>	Audit

featureId	Complex type
Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration	SHOULD<7> be a <b>Schedules</b> element as specified in <b>Schedules Type</b> (section <a href="#">2.5.1.16</a> ), but MAY contain a <b>Data</b> element as specified in <b>PolicyDataDefinition Type</b> (section <a href="#">2.5.1.18</a> ).

### 2.5.1.11 Barcode Type

The **Barcode** type specifies settings for a policy feature for generating implementation-specific barcode images for documents.

#### 2.5.1.11.1 Schema

```
<xs:complexType name="barcode">
  <xs:sequence>
    <xs:element name="event" type="PolicyEventDefinition" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

#### 2.5.1.11.2 Attributes

None.

#### 2.5.1.11.3 Child Elements

**event:** Operation that starts implementation-specific<8> generation of the barcode image.

### 2.5.1.12 PolicyEventDefinition Type

The **PolicyEventDefinition** type specifies the type of operation that starts generation of implementation-specific barcode or label images for a document.

#### 2.5.1.12.1 Schema

```
<xs:complexType name="PolicyEventDefinition" >
  <xs:attribute name="type" type="xs:string" use="required" />
</xs:complexType>
```

#### 2.5.1.12.2 Attributes

**type:** Operation type. The following table describes possible values.

Value	Description
Save	The operation of saving a document.
Print	The operation of printing a document.

### 2.5.1.12.3 Child Elements

None.

### 2.5.1.13 Label Type

The **Label** type specifies settings for a policy feature for generating implementation-specific label images for documents based on their document properties.

#### 2.5.1.13.1 Schema

```
<xs:complexType name="label">
  <xs:sequence>
    <xs:element name="properties" minOccurs="0">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="width" type="xs:decimal" minOccurs="0" />
          <xs:element name="height" type="xs:decimal" minOccurs="0" />
          <xs:element name="justification" type="xs:string" minOccurs="0" />
          <xs:element name="fontstyle" type="xs:string" minOccurs="0" />
          <xs:element name="font" type="xs:string" minOccurs="0" />
          <xs:element name="fontsize" type="xs:int" minOccurs="0" />
          <xs:element name="lock" type="xs:boolean" minOccurs="0" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="event" type="PolicyEventDefinition" minOccurs="0"
maxOccurs="unbounded" />
    <xs:element name="segment" type="PolicySegmentDefinition" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>
```

#### 2.5.1.13.2 Attributes

None.

#### 2.5.1.13.3 Child Elements

**properties:** A list of document properties for generating the label image.

**properties.width:** Physical width, in inches, of the label image. This value MUST be between 0.25 and 20 inches.

**properties.height:** Physical height, in inches, of the label image. This value MUST be between 0.25 and 20 inches.

**properties.justification:** Specifies the alignment of content in the label image. The following table describes possible values.

Value	Description
<b>Center</b>	The content aligns to the center of the label image.
<b>Right</b>	The content aligns to the right of the label image.
<b>Left</b>	The content aligns to the left of the label image.

**properties.fontstyle:** **Font** style of the content in the label image. The following table describes possible values.

Value	Description
<b>Regular</b>	The font style of the content is neither bold nor italicized.
<b>Bold</b>	The font style of the content is bold.
<b>Italic</b>	The font style of the content is italicized.

**properties.font:** Font family name of the content in the label image.

**properties.fontsize:** Font size of the content in the label image.

**properties.lock:** Specifies whether the label image can be changed after being generated. If **true**, the label image MUST NOT be changed after it is generated. Otherwise, the label MUST be re-generated when the values of any the document properties from the **properties** list is updated.

**event:** Operation that starts implementation-specific<9> generation of the label image.

**segment:** A list of content segments from which the label image is generated.

### 2.5.1.14 PolicySegmentDefinition Type

The **PolicySegmentDefinition** type specifies either fixed text or a reference to a document property to include as content in a label image.

#### 2.5.1.14.1 Schema

```
<xs:complexType name="PolicySegmentDefinition">
  <xs:attribute name="type" type="xs:string" use="required" />
</xs:complexType>
```

#### 2.5.1.14.2 Attributes

**type:** Type of policy label segment. The following table describes possible values.

Value	Description
literal	The segment contains fixed text to be included in the label.
metadata	The segment contains the name of a document property to be included in the label.

#### 2.5.1.14.3 Child Elements

None.

### 2.5.1.15 Audit Type

The **Audit** type specifies settings for a policy feature for logging a record of user actions to an audit log.

### 2.5.1.15.1 Schema

```
<xs:complexType name="audit">
  <xs:all>
    <xs:element name="Update" minOccurs="0" />
    <xs:element name="View" minOccurs="0" />
    <xs:element name="CheckInOut" minOccurs="0" />
    <xs:element name="MoveCopy" minOccurs="0" />
    <xs:element name="DeleteRestore" minOccurs="0" />
  </xs:all>
</xs:complexType>
```

### 2.5.1.15.2 Attributes

None.

### 2.5.1.15.3 Child Elements

**CheckInOut:** Can be any type. If present, audits check-in and check-out operations for items.

**DeleteRestore:** Can be any type. If present, audits deletion or restoration of items.

**MoveCopy:** Can be any type. If present, audits moving and copying of items.

**Update:** Can be any type. If present, audits updates made to items.

**View:** Can be any type. If present, audits any operation for opening or downloading items, viewing items in lists, or viewing item properties.

### 2.5.1.16 Schedules Type

The **Schedules** type specifies the retention lifecycle of content by specifying one or two **retention schedules**, each of which has one or more **retention stages**.

#### 2.5.1.16.1 Schema

```
<xs:complexType name="Schedules">
  <xs:sequence>
    <xs:element name="Schedule" type="PolicyScheduleDefinition" minOccurs="1" />
  </xs:sequence>
  <xs:attribute name="default" type="xs:boolean" use="optional" />
  <xs:attribute name="nextStageId" type="xs:int" use="required" />
</xs:complexType>
```

#### 2.5.1.16.2 Attributes

**default:** The identifier of whether to use the retention schedule with type set to "Default" for all items. The default value of this attribute is **true**. Set it to **false**, and **records** items will follow the retention schedule with type set to "Record".

**nextStageId:** The identifier of the next retention stage. It MUST be a positive integer that MUST NOT have been used in the **stageId** attribute of any child **Schedule.stages.data** element.

### 2.5.1.16.3 Child Elements

**Schedule:** Retention schedule. There MUST be a single **Schedule** element or two **Schedule** elements, one with **Schedule.type** set to "Default" and the other with **Schedule.type** set to "Record".

The following conditions determine the applicability of the retention schedule:

1. If there is a single **Schedule** element with **Schedule.type** set to "Default", that retention schedule is applicable to all items.
2. If there is a single **Schedule** element with **Schedule.type** set to "Record" and the **Schedules.default** attribute is set to **false**, that retention schedule is applicable to items that are records.
3. If there are two **Schedule** elements and the **Schedules.default** attribute is set to **false**, the **Schedule** element with **Schedule.type** set to "Default" applies to items that are not records, and the **Schedule** element with **Schedule.type** set to "Record" applies to items that are records.
4. If there are two **Schedule** elements and the **Schedules.default** attribute is set to **true** or not present, the **Schedule** element with type set to "Default" applies to all items.
5. All other combinations of **Schedules.default** and **Schedule.type** and number of **Schedule** elements MUST NOT be used.

### 2.5.1.17 PolicyScheduleDefinition Type

The **PolicyScheduleDefinition** type specifies a retention schedule. A retention schedule contains one or more retention stages. Each retention stage specifies a retention formula and a retention action. The protocol server performs the retention action on an implementation-specific schedule determined using the retention formula.

#### 2.5.1.17.1 Schema

```
<xs:complexType name="PolicyScheduleDefinition">
  <xs:sequence>
    <xs:element name="stages">
      <xs:complexType>
        <xs:sequence>
          <xs:element maxOccurs="unbounded" name="data" type="PolicyDataDefinition" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="type" type="xs:string" use="required" />
</xs:complexType>
```

#### 2.5.1.17.2 Attributes

**type:** Type of retention schedule. The following table describes possible values.

Value	Description
Default	The retention schedule applies to all items if the <b>Schedules</b> type does not also have a child

Value	Description
	<b>Schedule</b> element with <b>type</b> set to "Record". Otherwise, it applies to items that are not records.
Record	The retention schedule applies to record items.

### 2.5.1.17.3 Child Elements

**data:** A retention stage.

### 2.5.1.18 PolicyDataDefinition Type

The **PolicyDataDefinition** type specifies a retention stage.

#### 2.5.1.18.1 Schema

```
<xs:complexType name="PolicyDataDefinition">
  <xs:sequence>
    <xs:element name="formula" type="PolicyFormulaDefinition" />
    <xs:element name="action" type="PolicyActionDefinition" />
  </xs:sequence>
  <xs:attribute name="stageId" type="xs:int" use="required" />
  <xs:attribute name="recur" type="xs:boolean" use="optional" />
  <xs:attribute name="offset" type="xs:int" use="optional" />
  <xs:attribute name="unit" type="xs:string" use="optional" />
  <xs:attribute name="stageDeleted" type="xs:boolean" use="optional" />
</xs:complexType>
```

#### 2.5.1.18.2 Attributes

**stageId:** Identifier of the retention stage. It **MUST** be a positive integer.

**recur:** Specifies whether the retention stage recurs, that is, whether the retention action is performed periodically based on the **offset** and **unit** until the next retention stage is run.

**offset:** Number of time period units until the retention action recurs. **MUST** be ignored unless **recur** is set to **true**.

**unit:** Time period units for recurrence, which **MUST** be one of the enumerated values that are specified in the following table. **MUST** be ignored unless **recur** is set to **true**.

Value	Description
<b>days</b>	The recurrence unit is a day. The <b>offset</b> <b>MUST</b> be less than or equal to 182500 and greater than or equal to zero.
<b>months</b>	The recurrence unit is a month. The <b>offset</b> <b>MUST</b> be less than or equal to 6000 and greater than or equal to zero.
<b>years</b>	The recurrence unit is a year. The <b>offset</b> <b>MUST</b> be less than or equal to 500 and greater than or equal to zero.

**stageDeleted:** Specifies whether the retention stage has been deleted. This **MUST** be set to **true** or not present.

### 2.5.1.18.3 Child Elements

**formula:** Retention formula of the retention stage.

**action:** Retention action of the retention stage.

### 2.5.1.19 PolicyFormulaDefinition Type

The **PolicyFormulaDefinition** type specifies a retention formula.

#### 2.5.1.19.1 Schema

```
<xs:complexType name="PolicyFormulaDefinition">
  <xs:sequence>
    <xs:element name="number" type="xs:int" />
    <xs:element name="property" type="xs:string" />
    <xs:element name="propertyId" type="xs:string" />
    <xs:element name="period" type="xs:string" />
  </xs:sequence>
  <xs:attribute name="id" type="xs:string" />
</xs:complexType>
```

#### 2.5.1.19.2 Attributes

**id:** The identifier of the retention formula, which MUST be the one of the well-known values that are specified in the following table or an implementation-specific **class name**.

Value	Description
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.For formula.BuiltIn</b>	The expiration date is calculated based on the value of the document property specified by <b>PolicyFormulaDefinition.pro perty</b> , plus the time period calculated by <b>PolicyFormulaDefinition.nu mber</b> times the <b>PolicyFormulaDefinition.peri od</b> .
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.For formula.None</b>	The expiration date is not automatically calculated. This value is obsolete and SHOULD NOT <a href="#">&lt;10&gt;</a> be used.

#### 2.5.1.19.3 Child Elements

**number:** Number of time period units to offset from the value of the document property specified by the **property**. MUST be ignored unless the **formula.id** is

**Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Formula.BuiltIn.**

**property:** Document property that is to be used in the formula to determine when to perform the **retention action**. The type of the document property MUST be a date and time and MUST be ignored unless the **formula.id** is

**Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Formula.BuiltIn.**

**propertyId:** The identifier of the document property that is to be used in the formula to determine when to perform the retention action, which MUST be a GUID.

**period:** Time period units to offset from the value of the document property specified by the **property**. MUST be ignored unless the **formula.id** is **Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Formula.BuiltIn**. The following table describes possible values.

Value	Description
<b>days</b>	The offset unit is a day. The <b>number</b> MUST be less than or equal to 182500 and greater than or equal to zero.
<b>months</b>	The offset unit is a month. The <b>number</b> MUST be less than or equal to 6000 and greater than or equal to zero.
<b>years</b>	The offset unit is a year. The <b>number</b> MUST be less than or equal to 500 and greater than or equal to zero.

### 2.5.1.20 PolicyActionDefinition Type

The **PolicyActionDefinition** type specifies an action to perform when the formula comes due. For example, a common retention action is to delete the item.

#### 2.5.1.20.1 Schema

```
<xs:complexType name="PolicyActionDefinition">
  <xs:attribute name="type" type="xs:string" />
  <xs:attribute name="id" type="xs:string" use="required"/>
  <xs:attribute name="destnExplanation" type="xs:string" />
  <xs:attribute name="destnName" type="xs:string" />
  <xs:attribute name="destnUrl" type="xs:string" />
  <xs:attribute name="destnId" type="xs:string" />
</xs:complexType>
```

#### 2.5.1.20.2 Attributes

**type:** Type of action. The following table describes possible values.

action.type	Description
<b>action</b>	The action to perform is specified by the <b>id</b> .
<b>workflow</b>	The action is to start a <b>workflow (1)</b> .

**id:** If **type** is set to "workflow", this is the implementation-specific identifier of the workflow (1) to start. Otherwise, this SHOULD be one of the enumerated values that are specified in the following table, but it can be a vendor-extensible class name.

action.id	Description
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.MoveToRecycle Bin</b>	The action is to move the item to

action.id	Description
	the Recycle Bin.
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.Delete</b>	The action is to delete the item.
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.Skip</b>	The action is to skip to the next retention stage.
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.Record</b>	The action is to make the item a record.
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileCopy</b>	The action is to copy the item to a new location.
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileMove</b>	The action is to move the item to a new location.
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileLink</b>	The action is to copy the item to a new location and leave a link to the item in its new location.
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.DeletePreviousDrafts</b>	The action is to delete previous drafts of the item.
<b>Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.DeletePreviousVersions</b>	The action is to delete previous versions of item.

**destnExplanation:** User-provided reason for transferring (copying, moving, and so on) a file to a new location. MUST NOT be present unless **id** is set to **Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileCopy**,

**Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileMove**, or **Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileLink**.

The following attributes are implementation-specific<sup><11></sup>:

**destnName:** Name of the location to which to transfer the file. MUST NOT be present unless **id** is set to

**Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileCopy**, **Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileMove**, or **Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileLink**.

**destnUrl:** URL of the location to which to transfer the file, which MUST be of valid URL format. MUST NOT be present unless **id** is set to

**Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileCopy**, **Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileMove**, or **Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileLink**.

**destnId:** Identifier of the location to which to transfer the file, which MUST be a GUID. MUST NOT be present unless **id** is set to

**Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileCopy**, **Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileMove**, or **Microsoft.Office.RecordsManagement.PolicyFeatures.Expiration.Action.SubmitFileLink**.

### 2.5.1.20.3 Child Elements

None.

### 2.5.1.21 ReceiverDefinitions Type

The **ReceiverDefinitions** type specifies a collection of event receivers of the **EventReceiver** type.

#### 2.5.1.21.1 Schema

```
<xs:complexType name="ReceiverDefinitions">
  <xs:sequence>
    <xs:element name="Receiver" type="ReceiverDefinition" minOccurs="0" maxOccurs="unbounded"
  />
  </xs:sequence>
  <xs:attribute name="ListTemplateId" type="xs:int" />
  <xs:attribute name="ListUrl" type="xs:string" />
  <xs:attribute name="ListTemplateOwner" type="xs:string" />
  <xs:attribute name="Scope" type="xs:string" /></xs:complexType>
```

#### 2.5.1.21.2 Attributes

**ListTemplateId:** The identifier of the list template to which to apply the event receivers.

**ListUrl:** The Web-relative URL of the list (1) to which to apply the event receivers.

**ListTemplateOwner:** This value MUST be ignored.

**Scope:** An optional value indicates where to apply the event receivers. When present, the value MUST be one of values in the following table. The value "Web" is assumed if a value is expected but not present.

Scope	Description
Site	Apply the event receivers to the site collection.
Web	Apply the event receivers to the <b>top-level site</b> .

### 2.5.1.21.3 Child Elements

**Receiver:** An event receiver defined by the **ReceiverDefinition** type.

### 2.5.1.22 ReceiverDefinition Type

The **ReceiverDefinition** type specifies information about one event receiver.

#### 2.5.1.22.1 Schema

```
<xs:complexType name="ReceiverDefinition">
  <xs:all>
    <xs:element name="Name" type="String255Chars" minOccurs="1" maxOccurs="1" />
    <xs:element name="Synchronization" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="Type" type="xs:integer" minOccurs="1" maxOccurs="1" />
    <xs:element name="SequenceNumber" type="xs:integer" minOccurs="1" maxOccurs="1" />
    <xs:element name="Assembly" type="AssemblyStrongName" minOccurs="1" maxOccurs="1" />
    <xs:element name="Class" type="AssemblyClass" minOccurs="1" maxOccurs="1" />
    <xs:element name="Data" type="String255Chars" minOccurs="0" maxOccurs="1" />
  </xs:all>
</xs:complexType>
```

#### 2.5.1.22.2 Attributes

None.

#### 2.5.1.22.3 Child Elements

**Name:** The name of the event receiver.

**Type:** Type of the event to which the event receiver responds. The reader MUST ignore values not specified in [\[MS-WSSFO2\]](#) section 2.2.3.6 Event Receiver Type.

**Sequence:** Determines the order in which event receivers are run. Event receivers with a lower sequence number are run before event receivers with a higher sequence number.

**Assembly:** .NET assembly strong name that contains the event receiver implementation.

**Class:** .NET class name that contains the event receiver implementation.

**Data:** MAY contain additional data for the event receiver implementation.

**Synchronization:** An optional value that specifies whether the event receiver is run synchronously or asynchronously. When present, this value MUST be set to "Default", "Synchronous", or "Asynchronous" as described in the following table. When omitted, the default MUST be assumed.

Synchronization	Description
Default	Run receiver of <b>before event</b> synchronously, and run receiver of <b>after event</b>

<b>Synchronization</b>	<b>Description</b>
	asynchronously.
<b>Synchronous</b>	Run event receiver synchronously.
<b>Asynchronous</b>	Run event receiver asynchronously.

### 3 Structure Examples

The following example shows a view returned through the **ExportList** method. See [\[MS-WSSCAP\]](#) section 3.1.4.9, for a specification of **ExportList**. The view contains a query that filters for items whose title equals "MyTitle" that display three fields (1)—**Attachments**, **LinkTitle**, and **Modified**.

```
<View Name="{9C252FCA-B070-46DC-B89F-22FC1A01D40F}" Type="HTML" DisplayName="MyListView"
Url="Lists/Announcements/MyListView.aspx" Level="1" BaseViewID="1" ContentTypeID="0x"
ImageUrl="/_layouts/images/announce.png"
xmlns="http://schemas.microsoft.com/sharepoint/soap/">
  <Query>
    <Where>
      <Eq>
        <FieldRef Name="Title" />
        <Value Type="Text">MyTitle</Value>
      </Eq>
    </Where>
  </Query>
  <ViewFields>
    <FieldRef Name="Attachments" />
    <FieldRef Name="LinkTitle" />
    <FieldRef Name="Modified" />
  </ViewFields>
  <RowLimit Paged="TRUE">100</RowLimit>
  <Aggregations Value="Off" />
</View>
```

The following example shows a list schema returned through the **ExportList** method. See [\[MS-WSSCAP\]](#) section 3.1.4.9 for a specification of **ExportList**. Some components that specify the rendering of views and fields (1), which are not specified in this document, have been removed for brevity and are marked as "[removed for brevity]".

```
<List Name="{16DC665B-DC24-476A-A7FD-EB6C3B02527C}" Title="Some New Title" Description=""
Direction="2" BaseType="0" FeatureId="{00BFEA71-DE22-43B2-A848-C05709900100}"
ServerTemplate="100" Url="Lists/Some Custom List via RPC" OrderedList="TRUE"
PublicList="TRUE" VersioningEnabled="TRUE" MajorVersionLimit="9"
MajorWithMinorVersionsLimit="10" DraftVersionVisibility="2" DefaultItemOpen="1"
HiddenList="TRUE" DisableAttachments="TRUE" FolderCreation="FALSE" EmailAssignTo="TRUE"
ModerationType="TRUE" DisableDeployWithDependentList="TRUE" DisableDeployingList="TRUE"
AllowDeletion="FALSE" EnableContentTypes="TRUE" AllowEveryoneViewItems="TRUE"
CacheSchema="TRUE" Version="67">
  <MetaData>
    <Views>
      <View Name="{D24FB901-5836-4CC9-8F86-4CA4B53B5B51}" DefaultView="TRUE" Type="HTML"
DisplayName="All Items" Url="Lists/Some Custom List via RPC/AllItems.aspx" Level="1"
BaseViewID="1" ContentTypeID="0x" ImageUrl="/_layouts/images/generic.png">
        <ViewFields>
          <FieldRef Name="DocIcon" />
          <FieldRef Name="LinkTitle" />
          <FieldRef Name="_ModerationStatus" />
        </ViewFields>
        <GroupByHeader>
          [removed for brevity]
        </GroupByHeader>
      </View>
    </Views>
  </MetaData>
  <GroupByFooter>
```

```

    [removed for brevity]
  </GroupByFooter>

  <ViewHeader>
    [removed for brevity]
  </ViewHeader>

  <ViewBidiHeader>
    [removed for brevity]
  </ViewBidiHeader>

  <ViewBody>
    [removed for brevity]
  </ViewBody>

  <ViewFooter>
    [removed for brevity]
  </ViewFooter>

  <RowLimitExceeded>
    [removed for brevity]
  </RowLimitExceeded>

  <PagedRowset>
    [removed for brevity]
  </PagedRowset>

  <PagedClientCallbackRowset>
    [removed for brevity]
  </PagedClientCallbackRowset>

  <PagedRecurrenceRowset>
    [removed for brevity]
  </PagedRecurrenceRowset>

  <RowLimit Paged="TRUE">100</RowLimit>

  <ViewEmpty>
    [removed for brevity]
  </ViewEmpty>

  <Toolbar Type="Standard" />

  <Script>
    [removed for brevity]
  </Script>

  <Query>
    <OrderBy>
      <FieldRef Name="ID" />
    </OrderBy>
  </Query>
</View>
</Views>
<Fields>
  <Field ID="{03e45e84-1992-4d42-9116-26f756012634}" RowOrdinal="0" Type="ContentTypeId"
  Sealed="TRUE" ReadOnly="TRUE" Hidden="TRUE" DisplayName="Content Type ID"
  Name="ContentTypeId" DisplaceOnUpgrade="TRUE"

```

```

SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="ContentTypeId"
ColName="tp_ContentTypeId" FromBaseType="TRUE" />
  <Field ID="{fa564e0f-0c70-4ab9-b863-0177e6ddd247}" Type="Text" Name="Title"
DisplayName="Title" Required="TRUE" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="Title" FromBaseType="TRUE" ColName="nvarchar1" />
  <Field ID="{34ad21eb-75bd-4544-8c73-0e08330291fe}" ReadOnly="TRUE" Type="Note"
Name="_ModerationComments" DisplayName="Approver Comments" Hidden="FALSE"
CanToggleHidden="TRUE" Filterable="FALSE" Sortable="FALSE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="_ModerationComments"
FromBaseType="TRUE" ColName="ntext1" />
  <Field ID="{39360f11-34cf-4356-9945-25c44e68dade}" ReadOnly="TRUE" Hidden="TRUE"
Type="Text" Name="File_x0020_Type" DisplaceOnUpgrade="TRUE" DisplayName="File Type"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="File_x0020_Type"
FromBaseType="TRUE" ColName="nvarchar2" />
  <Field ID="{fdc3b2ed-5bf2-4835-a4bc-b885f3396a61}" ColName="tp_ModerationStatus"
RowOrdinal="0" ReadOnly="TRUE" Type="ModStat" Name="_ModerationStatus" DisplayName="Approval
Status" Hidden="FALSE" CanToggleHidden="TRUE" Required="TRUE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="_ModerationStatus"
FromBaseType="TRUE">
  <CHOICES>
    <CHOICE>0;#Approved</CHOICE>
    <CHOICE>1;#Rejected</CHOICE>
    <CHOICE>2;#Pending</CHOICE>
    <CHOICE>3;#Draft</CHOICE>
    <CHOICE>4;#Scheduled</CHOICE>
  </CHOICES>
  <Default>0</Default>
</Field>
  <Field ID="{1d22ea11-1e32-424e-89ab-9fedbadb6cel}" ColName="tp_ID" RowOrdinal="0"
ReadOnly="TRUE" Type="Counter" Name="ID" PrimaryKey="TRUE" DisplayName="ID"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="ID" FromBaseType="TRUE" />
  <Field ID="{c042a256-787d-4a6f-8a8a-cf6ab767f12d}" RowOrdinal="0" Type="Text"
DisplayName="Content Type" ReadOnly="TRUE" Name="ContentType" DisplaceOnUpgrade="TRUE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="ContentType"
ColName="tp_ContentType" Group="_Hidden" PITarget="MicrosoftWindowsSharePointServices"
PIAttribute="ContentTypeID" FromBaseType="TRUE" />
  <Field ID="{28cf69c5-fa48-462a-b5cd-27b6f9d2bd5f}" ColName="tp_Modified" RowOrdinal="0"
ReadOnly="TRUE" Type="DateTime" Name="Modified" DisplayName="Modified" StorageTZ="TRUE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="Modified"
FromBaseType="TRUE" />
  <Field ID="{8c06beca-0777-48f7-91c7-6da68bc07b69}" ColName="tp_Created" RowOrdinal="0"
ReadOnly="TRUE" Type="DateTime" Name="Created" DisplayName="Created" StorageTZ="TRUE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="Created"
FromBaseType="TRUE" />
  <Field ID="{1df5e554-ec7e-46a6-901d-d85a3881cb18}" ColName="tp_Author" RowOrdinal="0"
ReadOnly="TRUE" Type="User" List="UserInfo" Name="Author" DisplayName="Created By"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="Author" FromBaseType="TRUE"
/>
  <Field ID="{d31655d1-1d5b-4511-95a1-7a09e9b75bf2}" ColName="tp_Editor" RowOrdinal="0"
ReadOnly="TRUE" Type="User" List="UserInfo" Name="Editor" DisplayName="Modified By"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="Editor" FromBaseType="TRUE"
/>
  <Field ID="{26d0756c-986a-48a7-af35-bf18ab85ff4a}" ColName="tp_HasCopyDestinations"
RowOrdinal="0" Sealed="TRUE" Hidden="TRUE" ReadOnly="TRUE" Type="Boolean"
Name="_HasCopyDestinations" DisplaceOnUpgrade="TRUE" DisplayName="Has Copy Destinations"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="_HasCopyDestinations"
FromBaseType="TRUE" />
  <Field ID="{6b4e226d-3d88-4a36-808d-a129bf52bccf}" ColName="tp_CopySource"
RowOrdinal="0" Sealed="TRUE" Hidden="TRUE" ReadOnly="TRUE" Type="Text" Name="_CopySource"
DisplaceOnUpgrade="TRUE" DisplayName="Copy Source"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="_CopySource"
FromBaseType="TRUE" />
  <Field ID="{d4e44a66-ee3a-4d02-88c9-4ec5ff3f4cd5}" ColName="tp_Version" RowOrdinal="0"
Hidden="TRUE" ReadOnly="TRUE" Type="Integer" SetAs="owshiddenversion" Name="owshiddenversion"

```

```

DisplayName="owshiddenversion" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="owshiddenversion" FromBaseType="TRUE" />
  <Field ID="{f1e020bc-ba26-443f-bf2f-b68715017bbc}" ColName="tp_WorkflowVersion"
RowOrdinal="0" Hidden="TRUE" ReadOnly="TRUE" Type="Integer" Name="WorkflowVersion"
DisplaceOnUpgrade="TRUE" DisplayName="Workflow Version"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="WorkflowVersion"
FromBaseType="TRUE" />
  <Field ID="{7841bf41-43d0-4434-9f50-a673baef7631}" ColName="tp_UIVersion"
RowOrdinal="0" ReadOnly="TRUE" Type="Integer" Name="_UIVersion" DisplaceOnUpgrade="TRUE"
DisplayName="UI Version" Hidden="TRUE" CanToggleHidden="TRUE" Required="FALSE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="_UIVersion"
FromBaseType="TRUE" />
  <Field ID="{dce8262a-3ae9-45aa-aab4-83bd75fb738a}" ColName="tp_UIVersionString"
RowOrdinal="0" ReadOnly="TRUE" Type="Text" Name="_UIVersionString" DisplaceOnUpgrade="TRUE"
DisplayName="Version" CanToggleHidden="TRUE" Required="FALSE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="_UIVersionString"
FromBaseType="TRUE" />
  <Field ID="{67df98f4-9dec-48ff-a553-29bece9c5bf4}" ColName="tp_HasAttachment"
RowOrdinal="0" Type="Attachments" Name="Attachments" DisplayName="Attachments"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="Attachments"
FromBaseType="TRUE" />
  <Field ID="{503f1caa-358e-4918-9094-4a2cdc4bc034}" ReadOnly="TRUE" Type="Computed"
Name="Edit" Sortable="FALSE" Filterable="FALSE" DisplayName="Edit" ClassInfo="Icon"
AuthoringInfo="(link to edit item)" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="Edit" FromBaseType="TRUE">
    <DisplayPattern>
      <IfHasRights>
        <RightsChoices>
          <RightsGroup PermEditListItems="required" />
        </RightsChoices>
        <Then>
          <HTML><![CDATA[<a href="]]></HTML>
          <URL Cmd="Edit" />
          <HTML><![CDATA[" onclick="GoToLink(this);return false;"
target="_self">]]></HTML>
          <HTML><![CDATA[<img border="0" alt="]]></HTML>
          <HTML>Edit</HTML>
          <HTML><![CDATA[" src="/_layouts/images/edititem.gif">]]></HTML>
          <HTML><![CDATA[</a>]]></HTML>
        </Then>
        <Else>
          <HTML><![CDATA[&nbsp;]]></HTML>
        </Else>
      </IfHasRights>
    </DisplayPattern>
  </Field>
  <Field ID="{bc91a437-52e7-49e1-8c4e-4698904b2b6d}" ReadOnly="TRUE" Type="Computed"
Name="LinkTitleNoMenu" DisplayName="Title" Dir="" DisplayNameSrcField="Title"
AuthoringInfo="(linked to item)" EnableLookup="TRUE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="LinkTitleNoMenu"
FromBaseType="TRUE">
    <FieldRefs>
      <FieldRef Name="Title" />
      <FieldRef Name="LinkFilenameNoMenu" />
    </FieldRefs>
    <DisplayPattern>
      <IfEqual>
        <Expr1>
          <LookupColumn Name="FSObjType" />
        </Expr1>
        <Expr2>1</Expr2>
      </IfEqual>
    </DisplayPattern>
  </Field>

```

```

    <Field Name="LinkFilenameNoMenu" />
  </Then>
  <Else>
    <HTML><![CDATA[<a onfocus="OnLink(this)" href="]]></HTML>
    <URL />
    <HTML><![CDATA[" ONCLICK="GoToLink(this);return false;"
target="_self">]]></HTML>
    <Column HTMLEncode="TRUE" Name="Title" Default="(no title)" />
    <IfEqual>
      <Expr1>
        <GetVar Name="ShowAccessibleIcon" />
      </Expr1>
      <Expr2>1</Expr2>
      <Then>
        <HTML><![CDATA[</HTML>
        <HTML>Use SHIFT+ENTER to open the menu (new window).</HTML>
        <HTML><![CDATA[">]]></HTML>
      </Then>
    </IfEqual>
    <HTML><![CDATA[</a>]]></HTML>
    <IfNew>
      <HTML><![CDATA[<IMG SRC="/_layouts/1033/images/new.gif" alt="]]></HTML>
      <HTML>New</HTML>
      <HTML><![CDATA[">]]></HTML>
    </IfNew>
  </Else>
</IfEqual>
</DisplayPattern>
</Field>
  <Field ID="{82642ec8-ef9b-478f-acf9-31f7d45fbc31}" ReadOnly="TRUE" Type="Computed"
Name="LinkTitle" DisplayName="Title" DisplayNameSrcField="Title" ClassInfo="Menu"
AuthoringInfo="(linked to item with edit menu)"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="LinkTitle"
From BaseType="TRUE">
  <FieldRefs>
    <FieldRef Name="Title" />
    <FieldRef Name="LinkTitleNoMenu" />
    <FieldRef Name="_EditMenuTableStart" />
    <FieldRef Name="_EditMenuTableEnd" />
  </FieldRefs>
  <DisplayPattern>
    <FieldSwitch>
      <Expr>
        <GetVar Name="FreeForm" />
      </Expr>
      <Case Value="TRUE">
        <Field Name="LinkTitleNoMenu" />
      </Case>
      <Default>
        <Field Name="_EditMenuTableStart" />
        <SetVar Name="ShowAccessibleIcon" Value="1" />
        <Field Name="LinkTitleNoMenu" />
        <SetVar Name="ShowAccessibleIcon" Value="0" />
        <Field Name="_EditMenuTableEnd" />
      </Default>
    </FieldSwitch>
  </DisplayPattern>
</Field>

```

```

    <Field ID="{b1f7969b-ea65-42e1-8b54-b588292635f2}" ReadOnly="TRUE" Type="Computed"
Sortable="FALSE" Filterable="FALSE" Name="SelectTitle" Hidden="TRUE" CanToggleHidden="TRUE"
DisplayName="Select" Dir="" AuthoringInfo="(web part connection)" HeaderImage="blank.gif"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="SelectTitle"
FromBaseType="TRUE">
    <FieldRefs>
    <FieldRef Name="ID" />
    </FieldRefs>
    <DisplayPattern>
    <IfEqual>
    <Expr1>
    <GetVar Name="SelectedID" />
    </Expr1>
    <Expr2>
    <Column Name="ID" />
    </Expr2>
    <Then>
    <HTML><![CDATA[</HTML>
    <HTML>Selected</HTML>
    <HTML><![CDATA[""]></HTML>
    </Then>
    <Else>
    <HTML><![CDATA[<a href="javascript:SelectField(')></HTML>
    <GetVar Name="View" />
    <HTML><![CDATA[', '])></HTML>
    <ScriptQuote NotAddingQuote="TRUE">
    <Column Name="ID" />
    </ScriptQuote>
    <HTML><![CDATA[');return false;" onclick="javascript:SelectField(')></HTML>
    <GetVar Name="View" />
    <HTML><![CDATA[', '])></HTML>
    <ScriptQuote NotAddingQuote="TRUE">
    <Column Name="ID" />
    </ScriptQuote>
    <HTML><![CDATA[');return false;" target="_self"]></HTML>
    <HTML><![CDATA[</HTML>
    <HTML>Normal</HTML>
    <HTML><![CDATA[""]></HTML>
    <HTML><![CDATA[</a>]]></HTML>
    </Else>
    </IfEqual>
    </DisplayPattern>
    </Field>
    <Field ID="{50a54da4-1528-4e67-954a-e2d24f1e9efb}" Name="InstanceID"
DisplayName="Instance ID" ColName="tp_InstanceID" RowOrdinal="0" ReadOnly="TRUE"
Hidden="TRUE" Type="Integer" Min="0" Max="99991231" Filterable="TRUE" Sortable="TRUE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="InstanceID"
FromBaseType="TRUE" />
    <Field ID="{ca4addac-796f-4b23-b093-d2a3f65c0774}" ColName="tp_ItemOrder"
RowOrdinal="0" Name="Order" DisplayName="Order" Type="Number" Hidden="TRUE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="Order" FromBaseType="TRUE"
/>
    <Field ID="{ae069f25-3ac2-4256-b9c3-15dbc15da0e0}" ColName="tp_GUID" RowOrdinal="0"
ReadOnly="TRUE" Hidden="TRUE" Type="Guid" Name="GUID" DisplayName="GUID"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="GUID" FromBaseType="TRUE"
/>
    <Field ID="{de8beacf-5505-47cd-80a6-aa44e7ffe2f4}" ColName="tp_WorkflowInstanceID"
RowOrdinal="0" ReadOnly="TRUE" Hidden="TRUE" Type="Guid" Name="WorkflowInstanceID"
DisplaceOnUpgrade="TRUE" DisplayName="Workflow Instance ID"

```

```

SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="WorkflowInstanceID"
FromBaseType="TRUE" />
  <Field ID="{94f89715-e097-4e8b-ba79-ea02aa8b7adb}" Name="FileRef"
DisplaceOnUpgrade="TRUE" ReadOnly="TRUE" Hidden="TRUE" Type="Lookup" DisplayName="URL Path"
List="Docs" FieldRef="ID" ShowField="FullUrl" JoinColName="DoclibRowId" JoinRowOrdinal="0"
JoinType="INNER" SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="FileRef"
FromBaseType="TRUE" />
  <Field ID="{56605df6-8fa1-47e4-a04c-5b384d59609f}" Name="FileDirRef"
DisplaceOnUpgrade="TRUE" ReadOnly="TRUE" Hidden="TRUE" Type="Lookup" DisplayName="Path"
List="Docs" FieldRef="ID" ShowField="DirName" JoinColName="DoclibRowId" JoinRowOrdinal="0"
JoinType="INNER" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="FileDirRef" FromBaseType="TRUE" />
  <Field ID="{173f76c8-aebd-446a-9bc9-769a2bd2c18f}" Name="Last_x0020_Modified"
DisplaceOnUpgrade="TRUE" ReadOnly="TRUE" Hidden="TRUE" DisplayName="Modified" Type="Lookup"
List="Docs" FieldRef="ID" ShowField="TimeLastModified" Format="TRUE"
JoinColName="DoclibRowId" JoinRowOrdinal="0" JoinType="INNER"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="Last_x0020_Modified"
FromBaseType="TRUE" />
  <Field ID="{998b5cff-4a35-47a7-92f3-3914aa6aa4a2}" Name="Created_x0020_Date"
DisplaceOnUpgrade="TRUE" ReadOnly="TRUE" Hidden="TRUE" DisplayName="Created" Type="Lookup"
List="Docs" FieldRef="ID" ShowField="TimeCreated" Format="TRUE" JoinColName="DoclibRowId"
JoinRowOrdinal="0" JoinType="INNER" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="Created_x0020_Date" FromBaseType="TRUE" />
  <Field ID="{30bb605f-5bae-48fe-b4e3-1f81d9772af9}" Name="FSObjType"
DisplaceOnUpgrade="TRUE" ReadOnly="TRUE" Hidden="TRUE" ShowInFileDlg="FALSE" Type="Lookup"
DisplayName="Item Type" List="Docs" FieldRef="ID" ShowField="FSType"
JoinColName="DoclibRowId" JoinRowOrdinal="0" JoinType="INNER"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="FSObjType"
FromBaseType="TRUE" />
  <Field ID="{ba3c27ee-4791-4867-8821-ff99000bac98}" Name="PermMask"
DisplaceOnUpgrade="TRUE" ReadOnly="TRUE" Hidden="TRUE" RenderXMLUsingPattern="TRUE"
ShowInFileDlg="FALSE" Type="Computed" DisplayName="Effective Permissions Mask"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="PermMask"
FromBaseType="TRUE">
  <FieldRefs>
    <FieldRef Name="ID" />
  </FieldRefs>
  <DisplayPattern>
    <CurrentRights />
  </DisplayPattern>
</Field>
  <Field ID="{8553196d-ec8d-4564-9861-3dbe931050c8}" Hidden="TRUE" ShowInFileDlg="FALSE"
ShowInVersionHistory="FALSE" Type="File" Name="FileLeafRef" DisplaceOnUpgrade="TRUE"
DisplayName="Name" AuthoringInfo="(for use in forms)" List="Docs" FieldRef="ID"
ShowField="LeafName" JoinColName="DoclibRowId" JoinRowOrdinal="0" JoinType="INNER"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="FileLeafRef"
FromBaseType="TRUE" />
  <Field ID="{4b7403de-8d94-43e8-9f0f-137a3e298126}" Name="UniqueId"
DisplaceOnUpgrade="TRUE" ReadOnly="TRUE" Hidden="TRUE" ShowInFileDlg="FALSE" Type="Lookup"
DisplayName="Unique Id" List="Docs" FieldRef="ID" ShowField="UniqueId"
JoinColName="DoclibRowId" JoinRowOrdinal="0" JoinType="INNER"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="UniqueId"
FromBaseType="TRUE" />
  <Field ID="{c5c4b81c-f1d9-4b43-a6a2-090df32ebb68}" Name="ProgId"
DisplaceOnUpgrade="TRUE" ReadOnly="TRUE" Hidden="TRUE" ShowInFileDlg="FALSE" Type="Lookup"
DisplayName="ProgId" List="Docs" FieldRef="ID" ShowField="ProgId" JoinColName="DoclibRowId"
JoinRowOrdinal="0" JoinType="INNER" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="ProgId" FromBaseType="TRUE" />
  <Field ID="{dddd2420-b270-4735-93b5-92b713d0944d}" Name="ScopeId"
DisplaceOnUpgrade="TRUE" ReadOnly="TRUE" Hidden="TRUE" ShowInFileDlg="FALSE" Type="Lookup"
DisplayName="ScopeId" List="Docs" FieldRef="ID" ShowField="ScopeId" JoinColName="DoclibRowId"
JoinRowOrdinal="0" JoinType="INNER" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="ScopeId" FromBaseType="TRUE" />

```

```

    <Field ReadOnly="TRUE" ID="{4ef1b78f-fdba-48dc-b8ab-3fa06a0c9804}" Hidden="TRUE"
Type="Computed" Name="HTML_x0020_File_x0020_Type" DisplaceOnUpgrade="TRUE" DisplayName="HTML
File Type" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="HTML_x0020_File_x0020_Type" FromBaseType="TRUE">
    <FieldRefs>
    <FieldRef Name="File_x0020_Type" />
    </FieldRefs>
    <DisplayPattern />
</Field>
<Field ID="{3c6303be-e21f-4366-80d7-d6d0a3b22c7a}" Hidden="TRUE" ReadOnly="TRUE"
Type="Computed" Name="_EditMenuTableStart" DisplaceOnUpgrade="TRUE" DisplayName="Edit Menu
Table Start" ClassInfo="Menu" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="_EditMenuTableStart" FromBaseType="TRUE">
    <FieldRefs>
    <FieldRef Name="FileLeafRef" />
    <FieldRef Name="FileDirRef" />
    <FieldRef Name="FSObjType" />
    <FieldRef Name="ID" />
    <FieldRef Name="ServerUrl" />
    <FieldRef Name="HTML_x0020_File_x0020_Type" />
    <FieldRef Name="File_x0020_Type" />
    <FieldRef Name="PermMask" />
    <FieldRef Name="_HasCopyDestinations" />
    <FieldRef Name="_CopySource" />
    <FieldRef Name="ContentType" />
    <FieldRef Name="ContentTypeId" />
    <FieldRef Name="_ModerationStatus" />
    <FieldRef Name="_UIVersion" />
    </FieldRefs>
    <DisplayPattern>
    [removed for brevity]
    </DisplayPattern>
</Field>
<Field ID="{2ea78cef-1bf9-4019-960a-02c41636cb47}" Hidden="TRUE" ReadOnly="TRUE"
Type="Computed" Name="_EditMenuTableEnd" DisplaceOnUpgrade="TRUE" DisplayName="Edit Menu
Table End" ClassInfo="Menu" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="_EditMenuTableEnd" FromBaseType="TRUE">
    <FieldRefs>
    <FieldRef Name="ID" />
    </FieldRefs>
    <DisplayPattern>
    <HTML><![CDATA[</td><td></td></tr></table>]]></HTML>
    </DisplayPattern>
</Field>
<Field ID="{9d30f126-ba48-446b-b8f9-83745f322ebe}" ReadOnly="TRUE" Type="Computed"
Name="LinkFilenameNoMenu" DisplaceOnUpgrade="TRUE" DisplayName="Name" Hidden="TRUE"
DisplayNameSrcField="FileLeafRef" Filterable="FALSE" AuthoringInfo="(linked to document)"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="LinkFilenameNoMenu"
FromBaseType="TRUE">
    <FieldRefs>
    <FieldRef Name="FileLeafRef" />
    <FieldRef Name="FSObjType" />
    <FieldRef Name="Created_x0020_Date" />
    <FieldRef Name="FileRef" />
    <FieldRef Name="File_x0020_Type" />
    <FieldRef Name="ContentTypeId" />
    <FieldRef Name="PermMask" />
    </FieldRefs>
    <DisplayPattern>

```

```

    [removed for brevity]
  </DisplayPattern>
</Field>
<Field ID="{5cc6dc79-3710-4374-b433-61cb4a686c12}" ReadOnly="TRUE" Type="Computed"
Name="LinkFilename" DisplaceOnUpgrade="TRUE" Hidden="TRUE" DisplayName="Name"
DisplayNameSrcField="FileLeafRef" Filterable="FALSE" ClassInfo="Menu" AuthoringInfo="(linked
to document with edit menu)" SourceID="http://schemas.microsoft.com/sharepoint/v3"
StaticName="LinkFilename" FromBaseType="TRUE">
  <FieldRefs>
    <FieldRef Name="LinkFilenameNoMenu" />
    <FieldRef Name="_EditMenuTableStart" />
    <FieldRef Name="_EditMenuTableEnd" />
  </FieldRefs>
  <DisplayPattern>
    <FieldSwitch>
      <Expr>
        <GetVar Name="FreeForm" />
      </Expr>
      <Case Value="TRUE">
        <Field Name="LinkFilenameNoMenu" />
      </Case>
      <Default>
        <Field Name="_EditMenuTableStart" />
        <SetVar Name="ShowAccessibleIcon" Value="1" />
        <Field Name="LinkFilenameNoMenu" />
        <SetVar Name="ShowAccessibleIcon" Value="0" />
        <Field Name="_EditMenuTableEnd" />
      </Default>
    </FieldSwitch>
  </DisplayPattern>
</Field>
<Field ID="{081c6e4c-5c14-4f20-b23e-1a71ceb6a67c}" Type="Computed" ReadOnly="TRUE"
Name="DocIcon" DisplaceOnUpgrade="TRUE" DisplayName="Type" TextOnly="TRUE" ClassInfo="Icon"
AuthoringInfo="(icon linked to document)"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="DocIcon"
FromBaseType="TRUE">
  <FieldRefs>
    <FieldRef Name="File_x0020_Type" />
    <FieldRef Name="FSObjType" />
    <FieldRef Name="FileRef" />
    <FieldRef Name="FileLeafRef" />
    <FieldRef Name="HTML_x0020_File_x0020_Type" />
    <FieldRef Name="PermMask" />
  </FieldRefs>
  <DisplayPattern>
    [removed for brevity]
  </DisplayPattern>
</Field>
<Field ID="{105f76ce-724a-4bba-aece-f81f2fce58f5}" ReadOnly="TRUE" Hidden="TRUE"
Type="Computed" Name="ServerUrl" DisplaceOnUpgrade="TRUE" DisplayName="Server Relative URL"
Filterable="FALSE" RenderXMLUsingPattern="TRUE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="ServerUrl"
FromBaseType="TRUE">
  <FieldRefs>
    <FieldRef Name="FileRef" />
  </FieldRefs>
  <DisplayPattern>
    <HTML></HTML>
    <LookupColumn Name="FileRef" />
  </DisplayPattern>

```

```

    </Field>
    <Field ID="{7177cfc7-f399-4d4d-905d-37dd51bc90bf}" ReadOnly="TRUE" Hidden="TRUE"
    Type="Computed" Name="EncodedAbsUrl" DisplaceOnUpgrade="TRUE" DisplayName="Encoded Absolute
    URL" Filterable="FALSE" RenderXMLUsingPattern="TRUE"
    SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="EncodedAbsUrl"
    FromBaseType="TRUE">
      <FieldRefs>
        <FieldRef Name="FileRef" />
      </FieldRefs>
      <DisplayPattern>
        <HttpHost URLEncodeAsURL="TRUE" />
        <HTML></HTML>
        <LookupColumn Name="FileRef" URLEncodeAsURL="TRUE" />
      </DisplayPattern>
    </Field>
    <Field ID="{7615464b-559e-4302-b8e2-8f440b913101}" ReadOnly="TRUE" Hidden="TRUE"
    Type="Computed" Name="BaseName" DisplaceOnUpgrade="TRUE" DisplayName="File Name"
    Filterable="FALSE" RenderXMLUsingPattern="TRUE"
    SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="BaseName"
    FromBaseType="TRUE">
      <FieldRefs>
        <FieldRef Name="FileLeafRef" />
        <FieldRef Name="FSObjType" />
      </FieldRefs>
      <DisplayPattern>
        <IfEqual>
          <Expr1>
            <LookupColumn Name="FSObjType" />
          </Expr1>
          <Expr2>1</Expr2>
          <Then>
            <LookupColumn Name="FileLeafRef" HTMLEncode="TRUE" />
          </Then>
          <Else>
            <UrlBaseName HTMLEncode="TRUE">
              <LookupColumn Name="FileLeafRef" />
            </UrlBaseName>
          </Else>
        </IfEqual>
      </DisplayPattern>
    </Field>
    <Field ID="{687c7f94-686a-42d3-9b67-2782eac4b4f8}" Name="MetaInfo"
    DisplaceOnUpgrade="TRUE" Hidden="TRUE" ShowInFileDlg="FALSE" Type="Lookup"
    DisplayName="Property Bag" List="Docs" FieldRef="ID" ShowField="MetaInfo"
    JoinColName="DoclibRowId" JoinType="INNER"
    SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="MetaInfo"
    FromBaseType="TRUE" />
    <Field ID="{43bdd51b-3c5b-4e78-90a8-fb2087f71e70}" ColName="tp_Level" RowOrdinal="0"
    ReadOnly="TRUE" Type="Integer" Name="_Level" DisplaceOnUpgrade="TRUE" DisplayName="Level"
    Hidden="TRUE" Required="FALSE" SourceID="http://schemas.microsoft.com/sharepoint/v3"
    StaticName="_Level" FromBaseType="TRUE" />
    <Field ID="{c101c3e7-122d-4d4d-bc34-58e94a38c816}" ColName="tp_IsCurrentVersion"
    DisplaceOnUpgrade="TRUE" RowOrdinal="0" ReadOnly="TRUE" Type="Boolean"
    Name="_IsCurrentVersion" DisplayName="Is Current Version" Hidden="TRUE" Required="FALSE"
    SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="_IsCurrentVersion"
    FromBaseType="TRUE" />
  </Fields>
  <ContentTypes>
    <ContentType ID="0x01003056A1FBD7AB3B43BA55FA8F5AC76D6A" Name="Item" Group="List
    Content Types" Description="Create a new list item." Version="0" FeatureId="{695b6570-a48b-
    4a8e-8ea5-26ea7fc1d162}">

```

```

    <FieldRefs>
      <FieldRef ID="{c042a256-787d-4a6f-8a8a-cf6ab767f12d}" Name="ContentType" />
      <FieldRef ID="{fa564e0f-0c70-4ab9-b863-0177e6ddd247}" Name="Title" Required="TRUE"
ShowInNewForm="TRUE" ShowInEditForm="TRUE" />
    </FieldRefs>
    <XmlDocuments>
      <XmlDocument
NamespaceURI="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms">
        <FormTemplates
xmlns="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms">
          <Display>ListForm</Display>
          <Edit>ListForm</Edit>
          <New>ListForm</New>
        </FormTemplates>
      </XmlDocument>
    </XmlDocuments>
    <Folder TargetName="Item" />
  </ContentType>
  <ContentType ID="0x01200009BBE0546A19524F9D32D2C92AE60FDF" Name="Folder" Group="Folder
Content Types" Description="Create a new folder." Sealed="TRUE" Version="0"
FeatureId="{695b6570-a48b-4a8e-8ea5-26ea7fcl1d162}">
    <FieldRefs>
      <FieldRef ID="{c042a256-787d-4a6f-8a8a-cf6ab767f12d}" Name="ContentType" />
      <FieldRef ID="{fa564e0f-0c70-4ab9-b863-0177e6ddd247}" Name="Title" Required="FALSE"
Hidden="TRUE" />
      <FieldRef ID="{8553196d-ec8d-4564-9861-3dbe931050c8}" Name="FileLeafRef"
Hidden="FALSE" Required="TRUE" />
    </FieldRefs>
    <XmlDocuments>
      <XmlDocument
NamespaceURI="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms">
        <FormTemplates
xmlns="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms">
          <Display>ListForm</Display>
          <Edit>ListForm</Edit>
          <New>ListForm</New>
        </FormTemplates>
      </XmlDocument>
    </XmlDocuments>
  </ContentType>
</ContentTypes>
<Forms>
  <Form Type="DisplayForm" Name="{3247C226-DA6D-40D2-AC6E-635A33F2DBFF}" Url="Lists/Some
Custom List via RPC/DispForm.aspx" Default="TRUE" />
  <Form Type="EditForm" Name="{A8C98402-6DF3-4A9F-9853-54216A85140A}" Url="Lists/Some
Custom List via RPC/EditForm.aspx" Default="TRUE" />
  <Form Type="NewForm" Name="{C81F208E-F5BD-421D-B8C4-BBD73A0221C8}" Url="Lists/Some
Custom List via RPC/NewForm.aspx" Default="TRUE" />
</Forms>
<Security>
  <ReadSecurity>1</ReadSecurity>
  <WriteSecurity>2</WriteSecurity>
  <SchemaSecurity>0</SchemaSecurity>
</Security>
</MetaData>
</List>

```

The following example shows a content type schema.

```

<ContentTypes>
  <ContentType ID="0x010100151D6E9AAB0A8E43B94916DB521E696C" Name="Document" Group="Document
Content Types" Description="Create a new document." V2ListTemplateName="doclib" Version="0"
FeatureId="{695b6570-a48b-4a8e-8ea5-26ea7fc1d162}">
    <FieldRefs>
      <FieldRef ID="{c042a256-787d-4a6f-8a8a-cf6ab767f12d}" Name="ContentType"/>
      <FieldRef ID="{5f47e085-2150-41dc-b661-442f3027f552}" Name="SelectFilename"/>
      <FieldRef ID="{8553196d-ec8d-4564-9861-3dbe931050c8}" Name="FileLeafRef"
Required="TRUE"/>
      <FieldRef ID="{8c06beca-0777-48f7-91c7-6da68bc07b69}" Name="Created" Hidden="TRUE"/>
      <FieldRef ID="{fa564e0f-0c70-4ab9-b863-0177e6ddd247}" Name="Title" Required="FALSE"
ShowInNewForm="FALSE" ShowInEditForm="TRUE"/>
      <FieldRef ID="{28cf69c5-fa48-462a-b5cd-27b6f9d2bd5f}" Name="Modified" Hidden="TRUE"/>
      <FieldRef ID="{822c78e3-1ea9-4943-b449-57863ad33ca9}" Name="Modified_x0020_By"
Hidden="FALSE"/>
      <FieldRef ID="{4dd7e525-8d6b-4cb4-9d3e-44ee25f973eb}" Name="Created_x0020_By"
Hidden="FALSE"/>
    </FieldRefs>
    <XmlDocuments>
      <XmlDocument
NamespaceURI="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms">
        <FormTemplates xmlns="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms">
          <Display>DocumentLibraryForm</Display>
          <Edit>DocumentLibraryForm</Edit>
          <New>DocumentLibraryForm</New>
        </FormTemplates>
      </XmlDocument>
    </XmlDocuments>
    <Folder TargetName="Forms/Document"/>
  </ContentType>
  <ContentType ID="0x0120007DAE54352CCF27408D0C1505674612EC" Name="Folder" Group="Folder
Content Types" Description="Create a new folder." Sealed="TRUE" Version="0"
FeatureId="{695b6570-a48b-4a8e-8ea5-26ea7fc1d162}">
    <FieldRefs>
      <FieldRef ID="{c042a256-787d-4a6f-8a8a-cf6ab767f12d}" Name="ContentType"/>
      <FieldRef ID="{fa564e0f-0c70-4ab9-b863-0177e6ddd247}" Name="Title" Required="FALSE"
Hidden="TRUE"/>
      <FieldRef ID="{8553196d-ec8d-4564-9861-3dbe931050c8}" Name="FileLeafRef" Hidden="FALSE"
Required="TRUE"/>
    </FieldRefs>
    <XmlDocuments>
      <XmlDocument
NamespaceURI="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms">
        <FormTemplates xmlns="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms">
          <Display>ListForm</Display>
          <Edit>ListForm</Edit>
          <New>ListForm</New>
        </FormTemplates>
      </XmlDocument>
    </XmlDocuments>
  </ContentType>
</ContentTypes>

```

## 4 Security

### 4.1 Security Considerations for Implementers

The **Path** and **SetupPath** attributes of the **FormDefinition** and **ListDefinition** types contain a location to template files stored on the front-end Web server. When reading these complex types, validation is performed to ensure that access to files not intended for use as templates is prevented.

The server exposes a certain amount of internal implementation detail to the client by way of the **ColName**, **ColName2**, **RowOrdinal**, and **RowOrdinal2** attributes of the **FieldDefinition** type. The values for these attributes is set by the server, and the server does not permit the client to influence these settings.

### 4.2 Index of Security Fields

None.

## 5 Appendix A: Full XML Schema

For ease of implementation, the following CAML schema is provided.

**Note** In the following schema, in some cases a line is broken into multiple lines for readability.

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema id="WSS" targetNamespace="http://schemas.microsoft.com/sharepoint/soap/"
xmlns="http://schemas.microsoft.com/sharepoint/soap/"
xmlns:mstns="http://schemas.microsoft.com/sharepoint/soap/" elementFormDefault="qualified"
xmlns:xs="http://www.w3.org/2001/XMLSchema" version="1.0" attributeFormDefault="unqualified">

  <xs:simpleType name="AggregationsType">
    <xs:restriction base="xs:string">
      <xs:pattern
value="[Aa][Vv][Gg][Cc][Oo][Uu][Nn][Tt][Mm][Aa][Xx][Mm][Ii][Nn][Ss][Tt][Dd][Ee][Vv][Ss][
Uu][Mm][Vv][Aa][Rr]" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="AggregationsValue">
    <xs:restriction base="xs:string">
      <xs:pattern value="On|.*" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="AssemblyClass">
    <xs:restriction base="xs:string">
      <xs:maxLength value="255" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="AssemblyStrongName">
    <xs:restriction base="xs:string">
      <xs:maxLength value="255" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="ContentTypeId">
    <xs:restriction base="xs:string">
      <xs:pattern value="0x([0-9A-Fa-f][1-9A-Fa-f]|[1-9A-Fa-f][0-9A-Fa-f]|00[0-9A-Fa-
f]{32})*" />
      <xs:minLength value="2"/>
      <xs:maxLength value="1026"/>
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="FALSE_Case_Insensitive_Else_Anything">
    <xs:restriction base="xs:string">
      <xs:pattern value="[Ff][Aa][Ll][Ss][Ee]|.*" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="FieldAggregationAttribute">
    <xs:restriction base="xs:string">
      <xs:enumeration value="average" />
      <xs:enumeration value="count" />
      <xs:enumeration value="first" />
      <xs:enumeration value="last" />
    </xs:restriction>
  </xs:simpleType>
```

```

    <xs:enumeration value="max" />
    <xs:enumeration value="merge" />
    <xs:enumeration value="min" />
    <xs:enumeration value="plaintext" />
    <xs:enumeration value="signature" />
    <xs:enumeration value="sum" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="FieldInternalType">
  <xs:restriction base="xs:string">
    <xs:pattern
value="[iI][nN][tT][eE][gG][eE][rR][tT][eE][xX][tT][nN][oO][tT][eE][dD][aA][tT][eE][tT][iI]
][mM][eE][cC][oO][uU][nN][tT][eE][rR][cC][hH][oO][iI][cC][eE][lL][oO][oO][kK][uU][pP][bB]
][oO][oO][lL][eE][aA][nN][nN][uU][mM][bB][eE][rR][cC][uU][rR][rR][eE][nN][cC][yY][uU][rR][lL]
][cC][oO][mM][pP][uU][tT][eE][dD][tT][hH][rR][eE][aA][dD][iI][nN][gG][gG][uU][iI][dD][mM]
][uU][lL][tT][iI][cC][hH][oO][iI][cC][eE][gG][rR][iI][dD][cC][hH][oO][iI][cC][eE][cC][aA][lL]
][cC][uU][lL][aA][tT][eE][dD][fF][iI][lL][eE][aA][tT][tT][aA][cC][hH][mM][eE][nN][tT][sS][uU]
][sS][eE][rR][rR][eE][cC][uU][rR][rR][eE][nN][cC][eE][cC][rR][oO][sS][sS][pP][rR][oO][jJ]
][eE][cC][tT][lL][iI][nN][kK][mM][oO][dD][sS][tT][aA][tT][eE][rR][rR][oO][rR][cC][oO][nN][tT]
][eE][nN][tT][tT][yY][pP][eE][iI][dD][pP][aA][gG][eE][sS][eE][pP][aA][rR][aA][tT][oO][rR][tT]
][hH][rR][eE][aA][dD][iI][nN][dD][eE][xX][wW][oO][rR][kK][fF][lL][oO][wW][sS][tT][aA][tT]
][uU][sS][aA][lL][lL][dD][aA][yY][eE][vV][eE][nN][tT][wW][oO][rR][kK][fF][lL][oO][wW][eE][vV]
][eE][nN][tT][tT][yY][pP][eE]" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="FieldRefType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Recurrence" />
    <xs:enumeration value="EventType" />
    <xs:enumeration value="UID" />
    <xs:enumeration value="RecurrenceId" />
    <xs:enumeration value="EventCancel" />
    <xs:enumeration value="StartDate" />
    <xs:enumeration value="EndDate" />
    <xs:enumeration value="RecurData" />
    <xs:enumeration value="Duration" />
    <xs:enumeration value="TimeZone" />
    <xs:enumeration value="XMLTZzone" />
    <xs:enumeration value="CPLink" />
    <xs:enumeration value="LinkURL" />
    <xs:enumeration value="MasterSeriesItemID" />
    <xs:enumeration value="AllDayEvent" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="FieldRichTextMode">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Compatible"/>
    <xs:enumeration value="FullHtml"/>
    <xs:enumeration value="HtmlAsXml"/>
    <xs:enumeration value="ThemeHtml"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="FormType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="DisplayForm" />
    <xs:enumeration value="EditForm" />
  </xs:restriction>
</xs:simpleType>

```

```

    <xs:enumeration value="NewForm" />
    <xs:enumeration value="NewFormDialog" />
    <xs:enumeration value="SolutionForm" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="IMEMode">
  <xs:restriction base="xs:string">
    <xs:enumeration value="inactive" />
    <xs:enumeration value="auto" />
    <xs:enumeration value="active" />
    <xs:enumeration value="disabled" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="IntNonNegative">
  <xs:restriction base="xs:int">
    <xs:minInclusive value="0" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="IntPositive">
  <xs:restriction base="xs:int">
    <xs:minInclusive value="1" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="JoinType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="INNER" />
    <xs:enumeration value="LEFT OUTER" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ListTemplateBaseType">
  <xs:restriction base="xs:int ">
    <xs:enumeration value="0" />
    <xs:enumeration value="1" />
    <xs:enumeration value="3" />
    <xs:enumeration value="4" />
    <xs:enumeration value="5" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ListTemplateCategoryType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Libraries" />
    <xs:enumeration value="Communications" />
    <xs:enumeration value="Tracking" />
    <xs:enumeration value="Custom Lists" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="RelationshipDeleteBehaviorAttribute">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Cascade" />
    <xs:enumeration value="Restrict" />
    <xs:enumeration value="None" />
  </xs:restriction>

```

```

</xs:simpleType>

<xs:simpleType name="RelativeFilePath">
  <xs:restriction base="xs:string" >
    <xs:minLength value="0" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="RelativeUrl">
  <xs:restriction base="xs:string" >
    <xs:maxLength value="255" />
    <xs:minLength value="0" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="String255Chars">
  <xs:restriction base="xs:string">
    <xs:maxLength value="255" />
    <xs:minLength value="0" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="TextDirection">
  <xs:restriction base="xs:string">
    <xs:enumeration value="ltr" />
    <xs:enumeration value="rtl" />
    <xs:enumeration value="none" />
    <xs:enumeration value="None" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ToolbarPosition">
  <xs:restriction base="xs:string">
    <xs:enumeration value="After" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ToolbarType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Standard" />
    <xs:enumeration value="FreeForm" />
    <xs:enumeration value="RelatedTasks" />
    <xs:enumeration value="None" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="truefalse_Only_Lowercase">
  <xs:restriction base="xs:boolean">
    <xs:pattern value="true|false"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="TRUE_Case_Insensitive_Else_Anything">
  <xs:restriction base="xs:string">
    <xs:pattern value="[Tt][Rr][Uu][Ee]|.*" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="TRUE_Case_Sensitive_Else_Anything">

```

```

    <xs:restriction base="xs:string">
      <xs:pattern value="TRUE|.*" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="TRUE_NegOne_Else_Anything">
    <xs:restriction base="xs:string">
      <xs:pattern value="(TRUE)|(\-1)|.*" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="TRUE_If_Present">
    <xs:restriction base="xs:string"/>
  </xs:simpleType>

  <xs:simpleType name="TRUEFALSE">
    <xs:restriction base="xs:string">
      <xs:pattern value="[Tt][Rr][Uu][Ee]|[Ff][Aa][Ll][Ss][Ee]" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="UniqueIdentifierWithBraces">
    <xs:restriction base="xs:string">
      <xs:pattern value="\{[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\}" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="UniqueIdentifierWithBracesOrEmpty">
    <xs:restriction base="xs:string">
      <xs:pattern value="\{[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\}|" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="UniqueIdentifierWithOrWithoutBraces">
    <xs:restriction base="xs:string">
      <xs:pattern value="\{?[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}\}?" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="UniqueIdentifierWithOrWithoutBracesWithOrWithoutDashes">
    <xs:restriction base="xs:string">
      <xs:pattern value="\{?[0-9a-fA-F]{8}\-?[0-9a-fA-F]{4}\-?[0-9a-fA-F]{4}\-?[0-9a-fA-F]{4}\-?[0-9a-fA-F]{12}\}" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="UniqueIdentifierWithoutBraces">
    <xs:restriction base="UniqueIdentifierWithoutBracesOrEmpty">
      <xs:minLength value="1" />
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name="UniqueIdentifierWithoutBracesOrEmpty">
    <xs:restriction base="xs:string">
      <xs:pattern value="[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}|" />
    </xs:restriction>
  </xs:simpleType>

```

```

    <xs:minLength value="0"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ViewModerationType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Moderator" />
    <xs:enumeration value="Contributor" />
    <xs:enumeration value="HideUnapproved" />
    <xs:enumeration value="" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ViewPageLevel">
  <xs:restriction base="xs:int">
    <xs:enumeration value="1" />
    <xs:enumeration value="2" />
    <xs:enumeration value="255" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ViewScope">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Recursive" />
    <xs:enumeration value="RecursiveAll" />
    <xs:enumeration value="FilesOnly" />
    <xs:enumeration value="" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="ViewType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="HTML" />
    <xs:enumeration value="GRID" />
    <xs:enumeration value="CALENDAR" />
    <xs:enumeration value="RECURRENCE" />
    <xs:enumeration value="CHART" />
    <xs:enumeration value="GANTT" />
    <xs:enumeration value="TABLE" />
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="AggregationsDefinition">
  <xs:sequence>
    <xs:element name="FieldRef" type="FieldRefDefinitionAggregation" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Value" type="AggregationsValue" use="optional"/>
</xs:complexType>

<xs:complexType name="CalendarViewStyleDefinition" mixed="true">
  <xs:all>
    <xs:element name="AccessKey" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="ImageName" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="ImageWidth" type="xs:int" minOccurs="0" maxOccurs="1" />
    <xs:element name="ImageHeight" type="xs:int" minOccurs="0" maxOccurs="1" />
  </xs:all>
  <xs:attribute name="Title" type="xs:string" />

```

```

    <xs:attribute name="Type" type="xs:string" />
    <xs:attribute name="Template" type="xs:string" />
    <xs:attribute name="Sequence" type="xs:int" />
    <xs:attribute name="Default" type="TRUEFALSE" default="FALSE"/>
</xs:complexType>

<xs:complexType name="CalendarViewStylesDefinition" mixed="true">
  <xs:sequence>
    <xs:element name="CalendarViewStyle" type="CalendarViewStyleDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="CamlQueryRoot">
  <xs:all>
    <xs:element name="Where" type="LogicalJoinDefinition" minOccurs="0" maxOccurs="1" />
    <xs:element name="OrderBy" type="OrderByDefinition" minOccurs="0" maxOccurs="1" />
    <xs:element name="GroupBy" type="GroupByDefinition" minOccurs="0" maxOccurs="1" />
    <xs:element name="WithIndex" type="LogicalWithIndexDefinition" minOccurs="0"
maxOccurs="1" />
  </xs:all>
</xs:complexType>

<xs:complexType name="CHOICEDEFINITION" mixed="true">
  <xs:attribute name="JumpTo" type="xs:string" />
</xs:complexType>

<xs:complexType name="CHOICEDEFINITIONS">
  <xs:sequence>
    <xs:element name="CHOICE" type="CHOICEDEFINITION" minOccurs="0" maxOccurs="unbounded"
/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="ContentTypeDatabase">
  <xs:sequence>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="ContentTypeRef" type="ContentTypeReference" />
      <xs:element name="ContentType" type="ContentTypeDefinitionTP" />
    </xs:choice>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="ContentTypeDefinition">
  <xs:all>
    <xs:element name="Fields" type="FieldRefDefinitionCTs" minOccurs="0" maxOccurs="1" />
    <xs:element name="FieldRefs" type="FieldRefDefinitionCTs" minOccurs="0" maxOccurs="1"
/>
    <xs:element name="XmlDocuments" type="XmlDocumentDefinitionCollection" minOccurs="0"
maxOccurs="1" />
    <xs:element name="Folder" type="FolderReference" minOccurs="0" maxOccurs="1" />
    <xs:element name="DocumentTemplate" type="ContentTypeDocumentTemplateDefinition"
minOccurs="0" maxOccurs="1" />
  </xs:all>
  <xs:attribute name="ID" type="ContentTypeId" use="required" />
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="Group" type="xs:string" use="optional" />
  <xs:attribute name="ReadOnly" type="TRUE_NegOne_Else_Anything" use="optional"
default="FALSE"/>

```

```

    <xs:attribute name="Hidden" type="TRUE_NegOne_Else_Anything" use="optional"
default="FALSE"/>
    <xs:attribute name="Description" type="xs:string" use="optional" />
    <xs:attribute name="Sealed" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
    <xs:attribute name="V2ListTemplateName" type="xs:string" use="optional"/>
    <xs:attribute name="Version" type="IntNonNegative" use="optional" default="0" />
    <xs:attribute name="FeatureId" type="UniqueIdentifierWithBraces" use="optional" />
    <xs:attribute name="Edited" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
    <xs:attribute name="ProgId" type="xs:string" use="optional" />
    <xs:attribute name="RequireClientRenderingOnNew" type="TRUE_Case_Sensitive_Else_Anything"
use="optional" default="TRUE" />
</xs:complexType>

<xs:complexType name="ContentTypeDefinitionTP">
  <xs:all>
    <xs:element name="Fields" type="FieldRefDefinitionCTs" minOccurs="0" maxOccurs="1" />
  <xs:element name="FieldRefs" type="FieldRefDefinitionCTs" minOccurs="0" maxOccurs="1" />
    <xs:element name="XmlDocuments" type="XmlDocumentDefinitionCollection" minOccurs="0"
maxOccurs="1" />
    <xs:element name="Folder" type="FolderReference" minOccurs="0" maxOccurs="1" />
    <xs:element name="DocumentTemplate" type="ContentTypeDocumentTemplateDefinition"
minOccurs="0" maxOccurs="1" />
  </xs:all>
  <xs:attribute name="ID" type="ContentTypeId" use="required" />
  <xs:attribute name="Name" type="xs:string" use="optional" />
  <xs:attribute name="Group" type="xs:string" use="optional" />
  <xs:attribute name="ReadOnly" type="TRUE_NegOne_Else_Anything" use="optional"
default="FALSE"/>
  <xs:attribute name="Hidden" type="TRUE_NegOne_Else_Anything" use="optional"
default="FALSE"/>
  <xs:attribute name="Description" type="xs:string" use="optional" />
  <xs:attribute name="Sealed" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
  <xs:attribute name="V2ListTemplateName" type="xs:string" use="optional"/>
  <xs:attribute name="Version" type="IntNonNegative" use="optional" default="0" />
  <xs:attribute name="FeatureId" type="UniqueIdentifierWithBraces" use="optional" />
  <xs:attribute name="Edited" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
  <xs:attribute name="ProgId" type="xs:string" use="optional" />
  <xs:attribute name="NewDocumentControl" type="xs:string" use="optional" />
  <xs:attribute name="PushDownChangedResourceFilesOnly"
type="TRUE_Case_Sensitive_Else_Anything" use="optional" default="FALSE" />
  <xs:attribute name="RequireClientRenderingOnNew" type="TRUE_Case_Sensitive_Else_Anything"
use="optional" default="TRUE" />
</xs:complexType>

<xs:complexType name="ContentTypeReference">
  <xs:all>
    <xs:element name="Folder" type="FolderReference" minOccurs="0" maxOccurs="1" />
    <xs:element name="DocumentTemplate" type="ContentTypeDocumentTemplateDefinition"
minOccurs="0" maxOccurs="1" />
  </xs:all>
  <xs:attribute name="ID" type="ContentTypeId" use="required" />
  <xs:attribute name="Edited" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="FALSE" />
</xs:complexType>

<xs:complexType name="ContentTypeReferences">

```

```

<xs:sequence>
  <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element name="ContentTypeRef" type="ContentTypeReference" />
    <xs:element name="ContentType" type="ContentTypeDefinition" />
  </xs:choice>
</xs:sequence>
</xs:complexType>

<xs:complexType name="ContentTypeDocumentTemplateDefinition">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="TargetName" type="RelativeUrl" use="required"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

<xs:complexType name="ExtendedLogicalJoinDefinition">
  <xs:sequence>
    <xs:choice minOccurs="2" maxOccurs="2">
      <xs:element name="And" type="ExtendedLogicalJoinDefinition" />
      <xs:element name="BeginsWith" type="LogicalTestDefinition" />
      <xs:element name="Contains" type="LogicalTestDefinition" />
      <xs:element name="DateRangesOverlap" type="LogicalTestDefinitionDateRange" />
      <xs:element name="Eq" type="LogicalTestDefinition" />
      <xs:element name="Geq" type="LogicalTestDefinition" />
      <xs:element name="Gt" type="LogicalTestDefinition" />
      <xs:element name="In" type="LogicalTestInValuesDefinition" />
      <xs:element name="Includes" type="LogicalTestDefinition" />
      <xs:element name="IsNull" type="LogicalNullDefinition" />
      <xs:element name="IsNotNull" type="LogicalNullDefinition" />
      <xs:element name="Leq" type="LogicalTestDefinition" />
      <xs:element name="Lt" type="LogicalTestDefinition" />
      <xs:element name="Membership" type="MembershipDefinition" />
      <xs:element name="Neq" type="LogicalTestDefinition" />
      <xs:element name="NotIncludes" type="LogicalTestDefinition" />
      <xs:element name="Or" type="ExtendedLogicalJoinDefinition" />
    </xs:choice>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="FieldDefinitionCTRemove">
  <xs:complexContent>
    <xs:extension base="FieldDefinition"/>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="FieldDefinitions">
  <xs:sequence>
    <xs:element name="Field" type="FieldDefinition" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="FieldParserRef">
  <xs:attribute name="Name" type="xs:string" />
  <xs:attribute name="ProgId" type="xs:string" />
</xs:complexType>

<xs:complexType name="FieldParserRefs">
  <xs:sequence>

```

```

    <xs:element name="ParserRef" type="FieldParserRef" minOccurs="0" maxOccurs="unbounded"
  />
</xs:sequence>
</xs:complexType>

<xs:complexType name="FieldDefinition" mixed="true">
  <xs:all>
    <xs:element name="CHOICES" type="CHOICEDEFINITIONS" minOccurs="0" maxOccurs="1" />
    <xs:element name="Customization" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="1" maxOccurs="1" namespace="##any" processContents="skip" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Default" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="DefaultFormula" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="DisplayBidiPattern" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="DisplayPattern" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="FieldRefs" minOccurs="0" maxOccurs="1">
      <xs:complexType mixed="true">
        <xs:sequence>
          <xs:element name="FieldRef" type="FieldRefDefinitionField" minOccurs="0"
maxOccurs="unbounded" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="Formula" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="FormulaDisplayNames" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="MAPPINGS" type="MAPPINGDEFINITIONS" minOccurs="0" maxOccurs="1" />
    <xs:element name="ParserRefs" type="FieldParserRefs" minOccurs="0" maxOccurs="1" />
    <xs:element name="Validation" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
  </xs:all>
  <xs:attribute name="Aggregation" type="FieldAggregationAttribute" default="first"/>
  <xs:attribute name="aggregation" type="xs:string" />

```

```

<xs:attribute name="AllowDeletion" type="TRUEFALSE" default="TRUE" />
<xs:attribute name="AllowHyperlink" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="AllowMultiVote" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="AppendOnly" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="AuthoringInfo" type="xs:string" default=""/>
<xs:attribute name="BaseRenderingType" type="FieldInternalType" />
<xs:attribute name="BaseType" type="FieldInternalType" default="Text" />
<xs:attribute name="Calculated" type="xs:string" />
<xs:attribute name="CalType" type="xs:int" />
<xs:attribute name="CalendarType" type="xs:int" />
<xs:attribute name="CAMLRendering" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="CanToggleHidden" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="CountRelated" type="TRUE_If_Present" default="FALSE" />
<xs:attribute name="ClassInfo" type="xs:string" default=""/>
<xs:attribute name="ColName" type="xs:string" />
<xs:attribute name="ColName2" type="xs:string" />
<xs:attribute name="Commas" type="TRUEFALSE" />
<xs:attribute name="Customization" type="xs:string" />
<xs:attribute name="Decimals" type="xs:int" default="-1"/>
<xs:attribute name="DefaultListField" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="DefaultURLDesc" type="xs:string" />
<xs:attribute name="Description" type="xs:string" />
<xs:attribute name="Direction" type="TextDirection" default="none" />
<xs:attribute name="Dir" type="xs:string" />
<xs:attribute name="DisplaceOnUpgrade" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="DisplayImage" type="xs:string" />
<xs:attribute name="DisplayName" type="xs:string" />
<xs:attribute name="DisplayNameSrcField" type="xs:string" />
<xs:attribute name="DisplaySize" type="xs:int" />
<xs:attribute name="Div" type="xs:string" default="1.0" />
<xs:attribute name="EnableLookup" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="EnforceUniqueValues" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ExceptionImage" type="xs:string" />
<xs:attribute name="FieldRef" type="xs:string" />
<xs:attribute name="FillInChoice" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Filterable" type="TRUEFALSE" default="TRUE" />
<xs:attribute name="FilterableNoRecurrence" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ForcedDisplay" type="xs:string" />
<xs:attribute name="ForcePromoteDemote" type="TRUE_If_Present" />
<xs:attribute name="Format" type="xs:string" />
<xs:attribute name="FromBaseType" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="GridEndNum" type="xs:int" />
<xs:attribute name="GridNATxt" type="xs:string" default=""/>
<xs:attribute name="GridStartNum" type="IntPositive" />
<xs:attribute name="GridTxtRng1" type="xs:string" default=""/>
<xs:attribute name="GridTxtRng2" type="xs:string" default=""/>
<xs:attribute name="GridTxtRng3" type="xs:string" default=""/>
<xs:attribute name="Group" type="xs:string" />
<xs:attribute name="HeaderImage" type="xs:string" />
<xs:attribute name="Height" type="xs:int" />
<xs:attribute name="Hidden" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" />
<xs:attribute name="Id" type="xs:string" />
<xs:attribute name="IMEMode" type="IMEMode" />
<xs:attribute name="Indexed" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ImnHeader" type="xs:string" />
<xs:attribute name="IsolateStyles" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="IsRelationship" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="JoinColName" type="xs:string" default="tp_ID" />

```

```

<xs:attribute name="JoinRowOrdinal" type="xs:int" fixed="0" />
<xs:attribute name="JoinType" type="JoinType" default="LEFT OUTER" />
<xs:attribute name="JumpTo" type="xs:string" />
<xs:attribute name="JumpToFillinChoice" type="xs:string" />
<xs:attribute name="JumpToNo" type="xs:string" />
<xs:attribute name="JumpToYes" type="xs:string" />
<xs:attribute name="LCID" type="xs:int" />
<xs:attribute name="LinkToItem" type="TRUE_Case_Sensitive_Else_Anything" />
<xs:attribute name="LinkToItemAllowed" type="xs:string" />
<xs:attribute name="List" type="xs:string" />
<xs:attribute name="ListItemMenu" type="TRUE_Case_Sensitive_Else_Anything" />
<xs:attribute name="ListItemMenuAllowed" type="xs:string" />
<xs:attribute name="Max" type="xs:float" />
<xs:attribute name="MaxLength" type="xs:int" />
<xs:attribute name="maxLength" type="xs:string" />
<xs:attribute name="Min" type="xs:string" />
<xs:attribute name="Mult" type="xs:string" />
<xs:attribute name="Name" type="xs:string" use="required" />
<xs:attribute name="NegativeFormat" type="xs:string" />
<xs:attribute name="node" type="xs:string" />
<xs:attribute name="Node" type="xs:string" />
<xs:attribute name="NoEditFormBreak" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="NumLines" type="xs:string" default="6" />
<xs:attribute name="Percentage" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="PIAttribute" type="xs:string" />
<xs:attribute name="PITarget" type="xs:string" />
<xs:attribute name="PrependId" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Presence" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="PreviousName" type="xs:string" />
<xs:attribute name="PrimaryKey" type="TRUEFALSE" />
<xs:attribute name="PrimaryPIAttribute" type="xs:string" />
<xs:attribute name="PrimaryPITarget" type="xs:string" />
<xs:attribute name="ReadOnly" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ReadOnlyEnforced" type="TRUEFALSE" default="FALSE" />
type="RelationshipDeleteBehaviorAttribute" default="None" />
<xs:attribute name="RenderXMLUsingPattern" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Required" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="RestrictedMode" type="TRUEFALSE" default="TRUE" />
<xs:attribute name="ResultType" type="FieldInternalType" />
<xs:attribute name="ResyncOnChange" type="TRUEFALSE" default="FALSE"/>
<xs:attribute name="RichText" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="RichTextMode" type="FieldRichTextMode" default="Compatible" />
<xs:attribute name="RowOrdinal" type="xs:int" default="0" />
<xs:attribute name="RowOrdinal2" type="xs:int" default="0" />
<xs:attribute name="Sealed" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="SeparateLine" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="SetAs" type="xs:string" />
<xs:attribute name="ShowAddressBookButton" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ShowField" type="xs:string" />
<xs:attribute name="ShowInDisplayForm" type="TRUEFALSE" />
<xs:attribute name="ShowInEditForm" type="TRUEFALSE" default="TRUE" />
<xs:attribute name="ShowInFileDialog" type="TRUEFALSE" />
<xs:attribute name="ShowInFileDialog" type="TRUEFALSE" />
<xs:attribute name="ShowInListSettings" type="TRUEFALSE" />
<xs:attribute name="ShowInNewForm" type="TRUEFALSE" default="TRUE" />
<xs:attribute name="ShowInVersionHistory" type="TRUEFALSE" />
<xs:attribute name="ShowInViewForms" type="TRUEFALSE" />
<xs:attribute name="Sortable" type="TRUEFALSE" />

```

```

<xs:attribute name="SourceID" type="xs:string" />
<xs:attribute name="StaticName" type="xs:string" />
<xs:attribute name="StorageTZ" type="xs:string" />
<xs:attribute name="StripWS" type="xs:string" />
<xs:attribute name="SuppressNameDisplay" type="TRUEFALSE" />
<xs:attribute name="TextOnly" type="TRUEFALSE" />
<xs:attribute name="Title" type="xs:string" />
<xs:attribute name="TitleField" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Type" type="xs:string" use="required" />
<xs:attribute name="UniqueId" type="xs:string" />
<xs:attribute name="UnlimitedLengthInDocumentLibrary" type="TRUEFALSE" />
<xs:attribute name="URLEncode" type="TRUEFALSE" />
<xs:attribute name="URLEncodeAsURL" type="TRUEFALSE" />
<xs:attribute name="UserSelectionMode" type="xs:string" />
<xs:attribute name="UserSelectionScope" type="xs:int" />
<xs:attribute name="Version" type="xs:int" default="0" />
<xs:attribute name="Viewable" type="FALSE_Case_Insensitive_Else_Anything" />
<xs:attribute name="WebId" type="UniqueIdentifierWithoutBraces" />
<xs:attribute name="Width" type="xs:int" />
<xs:attribute name="WikiLinking" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="WorkflowStatusURL" type="xs:string" use="optional" />
<xs:attribute name="XName" type="xs:string" />
<xs:anyAttribute namespace="##other" processContents="lax" />
</xs:complexType>

<xs:complexType name="FieldRefDefinitionAggregation">
  <xs:attribute name="Name" type="xs:string" use="required"/>
  <xs:attribute name="Type" type="AggregationsType" use="required"/>
</xs:complexType>

<xs:complexType name="FieldRefDefinitionCT">
  <xs:all>
    <xs:element name="Default" type="xs:string" minOccurs="0" maxOccurs="1" />
  </xs:all>
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="Required" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
  default="FALSE" />
  <xs:attribute name="Hidden" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
  default="FALSE" />
  <xs:attribute name="Customization" type="xs:string" use="optional" />
  <xs:attribute name="ShowInNewForm" type="FALSE_Case_Insensitive_Else_Anything"
  use="optional" default="TRUE" />
  <xs:attribute name="ShowInEditForm" type="FALSE_Case_Insensitive_Else_Anything"
  use="optional" default="TRUE" />
  <xs:attribute name="DisplayName" type="xs:string" use="optional" />
  <xs:attribute name="ReadOnly" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
  default="FALSE" />
  <xs:attribute name="PITarget" type="xs:string" use="optional" />
  <xs:attribute name="PrimaryPITarget" type="xs:string" use="optional" />
  <xs:attribute name="PIAttribute" type="xs:string" use="optional" />
  <xs:attribute name="PrimaryPIAttribute" type="xs:string" use="optional" />
  <xs:attribute name="Aggregation" type="xs:string" use="optional" />
  <xs:attribute name="Node" type="xs:string" use="optional" />
  <xs:attribute name="Format" type="xs:string" use="optional" />
  <xs:attribute name="NumLines" type="xs:string" default="6" />
  <xs:attribute name="Sealed" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
  default="FALSE" />

```

```

    <xs:attribute name="Sortable" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="TRUE" />
    <xs:attribute name="FromBaseType" type="TRUE_Case_Insensitive_Else_Anything"
use="optional" default="FALSE" />
    <xs:attribute name="Filterable" type="TRUE_Case_Sensitive_Else_Anything" use="optional"
default="TRUE" />
    <xs:attribute name="FilterableNoRecurrence" type="TRUE_Case_Sensitive_Else_Anything"
use="optional" default="FALSE" />
    <xs:attribute name="ShowInDisplayForm" use="optional" type="TRUEFALSE" default="FALSE" />
    <xs:attribute name="ShowInFileDialog" type="FALSE_Case_Insensitive_Else_Anything"
use="optional" default="TRUE" />
    <xs:attribute name="ShowInListSettings" use="optional" type="TRUEFALSE" default="FALSE"
/>
    <xs:attribute name="Description" type="xs:string" use="optional" />
</xs:complexType>

<xs:complexType name="FieldRefDefinitionCTs" mixed="true" >
  <xs:sequence>
    <xs:choice minOccurs="0" maxOccurs="unbounded">
      <xs:element name="FieldRef" type="FieldRefDefinitionCT" />
      <xs:element name="Field" type="FieldDefinitionCTRemove" />
    </xs:choice>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="FieldRefDefinitionField" mixed="true" >
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="ShowField" type="xs:string" use="optional" />
  <xs:attribute name="RefType" type="FieldRefType" use="optional" />
  <xs:attribute name="CreateURL" type="xs:string" use="optional" />
  <xs:attribute name="Key" type="xs:string" use="optional" />
  <xs:attribute name="DisplayName" type="xs:string" use="optional" />
</xs:complexType>

<xs:complexType name="FieldRefDefinitionGroupBy">
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="Name" type="xs:string" />
  <xs:attribute name="Ascending" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE" />
</xs:complexType>

<xs:complexType name="FieldRefDefinitionOrderBy">
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="Name" type="xs:string" use="optional" />
  <xs:attribute name="Ascending" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE" />
</xs:complexType>

<xs:complexType name="FieldRefDefinitionQueryDate">
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />
  <xs:attribute name="Name" type="xs:string" use="optional" />
</xs:complexType>

<xs:complexType name="FieldRefDefinitionQueryNull">
  <xs:attribute name="Name" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="FieldRefDefinitionQueryTest">
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="optional" />

```

```

    <xs:attribute name="Name" type="xs:string" use="optional" />
    <xs:attribute name="LookupId" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE" />
</xs:complexType>

<xs:complexType name="FieldRefDefinitionView">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="Explicit" type="TRUE_If_Present" use="optional" default="FALSE"/>
</xs:complexType>

<xs:complexType name="FieldRefDefinitionViewData">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="Type" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="FolderReference">
  <xs:sequence />
  <xs:attribute name="TargetName" type="RelativeUrl" use="required" />
</xs:complexType>

<xs:complexType name="FormatDefDefinition">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="Type" type="xs:string" use="required" />
      <xs:attribute name="Value" type="xs:string" use="required" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

<xs:complexType name="FormatDefinition">
  <xs:sequence>
    <xs:element name="FormatDef" type="FormatDefDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Name" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="FormDefinition">
  <xs:all>
    <xs:element name="ListFormOpening" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ListFormButtons" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ListFormBody" minOccurs="0" maxOccurs="1">
      <xs:complexType>

```

```

        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ListFormClosing" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
  </xs:all>
  <xs:attribute name="Path" type="RelativeFilePath" />
  <xs:attribute name="SetupPath" type="RelativeFilePath" />
  <xs:attribute name="Url" type="RelativeUrl" />
  <xs:attribute name="Type" type="FormType" />
  <xs:attribute name="UseLegacyForm" type="TRUEFALSE" default="FALSE"/>
  <xs:attribute name="Template" type="xs:string" />
  <xs:attribute name="WebPartZoneID" type="xs:string" />
  <xs:attribute name="FormID" type="xs:int" default="0" />
  <xs:attribute name="Name" type="UniqueIdentifierWithBraces" />
  <xs:attribute name="ToolbarTemplate" type="xs:string" />
  <xs:attribute name="Default" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="MobileUrl" type="RelativeUrl" />
</xs:complexType>

<xs:complexType name="FormDefinitions">
  <xs:sequence>
    <xs:element name="Form" type="FormDefinition" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="GroupByDefinition">
  <xs:sequence>
    <xs:element name="FieldRef" type="FieldRefDefinitionGroupBy" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Collapse" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE"/>
  <xs:attribute name="GroupLimit" type="IntNonNegative" use="optional" default="100"/>
</xs:complexType>

<xs:complexType name="ListDefinition">
  <xs:all>
    <xs:element name="MetaData" type="ListMetaDataDefinition" minOccurs="1" maxOccurs="1"
form="qualified" />
  </xs:all>
  <xs:attribute name="AllowDeletion" type="TRUEFALSE" default="TRUE" />
  <xs:attribute name="AllowEveryoneViewItems" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="AllowMultiVote" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="AlwaysIncludeContent" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="BaseType" type="xs:int" use="required" />
  <xs:attribute name="CacheSchema" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Catalog" type="TRUEFALSE" default="FALSE" />

```

```

<xs:attribute name="DefaultItemOpen" type="xs:int" default="0" />
<xs:attribute name="Description" type="xs:string" use="required" />
<xs:attribute name="Direction" type="xs:int" use="required" />
<xs:attribute name="DisableAttachments" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="DisableDeployingList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="DisableDeployWithDependentList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="DisallowContentTypes" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="DontSaveInTemplate" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="DraftVersionVisibility" type="xs:int" default="0" />
<xs:attribute name="EmailAssignTo" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="EnableContentTypes" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="EnableMinorVersions" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="EnableThumbnails" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="EventSinkAssembly" type="AssemblyStrongName" />
<xs:attribute name="EventSinkClass" type="AssemblyClass" />
<xs:attribute name="EventSinkData" type="String255Chars" />
<xs:attribute name="FeatureId" type="UniqueIdentifierWithBraces" />
<xs:attribute name="FolderCreation" type="TRUEFALSE" default="TRUE" />
<xs:attribute name="ForceCheckout" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="HiddenList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="MajorVersionLimit" type="IntNonNegative" />
<xs:attribute name="MajorWithMinorVersionsLimit" type="IntNonNegative" />
<xs:attribute name="ModerationType" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="MultipleMtgDataList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="MustSaveRootFiles" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Name" type="xs:string" />
<xs:attribute name="OrderedList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="PrivateList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="PublicList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="RestrictedTemplate" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="RootWebOnly" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ServerTemplate" type="xs:int" />
<xs:attribute name="SuppressNameDisplay" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ThumbnailSize" type="xs:int" default="0" />
<xs:attribute name="Title" type="xs:string" use="required" />
<xs:attribute name="Url" type="RelativeUrl" />
<xs:attribute name="Version" type="xs:int" />
<xs:attribute name="VersioningEnabled" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="WebImageHeight" type="xs:int" default="0" />
<xs:attribute name="WebImageWidth" type="xs:int" default="0" />
</xs:complexType>

<xs:complexType name="ListFormSet">
  <xs:sequence>
    <xs:element name="Form" type="FormDefinition" minOccurs="0" maxOccurs="4" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="ListMetaDataDefault">
  <xs:sequence>
    <xs:element name="Forms" type="ListFormSet" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="ListMetaDataDefinition">
  <xs:all>
    <xs:element name="ContentTypes" type="ContentTypeReferences" minOccurs="0"
maxOccurs="1" />
    <xs:element name="Default" type="ListMetaDataDefault" minOccurs="0" maxOccurs="1" />
  </xs:all>
</xs:complexType>

```

```

    <xs:element name="DefaultDescription" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="DocumentLibraryTemplate" type="xs:string" minOccurs="0" maxOccurs="1" />
  />
  <xs:element name="Fields" type="FieldDefinitions" minOccurs="0" maxOccurs="1" />
  <xs:element name="Forms" type="ListFormSet" minOccurs="0" maxOccurs="1" />
  <xs:element name="Security" type="ListSecurity" minOccurs="0" maxOccurs="1" />
  <xs:element name="Toolbar" type="ToolbarDefinition" minOccurs="0" maxOccurs="1" />
  <xs:element name="Validation" minOccurs="0" maxOccurs="1">
    <xs:complexType>
      <xs:sequence>
        <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
      </xs:sequence>
      <xs:anyAttribute processContents="skip" />
    </xs:complexType>
  </xs:element>
  <xs:element name="Views" type="ViewDefinitions" minOccurs="0" maxOccurs="1" />
</xs:all>
</xs:complexType>

<xs:complexType name="ListSecurity">
  <xs:all>
    <xs:element name="ReadSecurity" type="xs:int" minOccurs="0" maxOccurs="1" />
    <xs:element name="WriteSecurity" type="xs:int" minOccurs="0" maxOccurs="1" />
    <xs:element name="SchemaSecurity" type="xs:int" minOccurs="0" maxOccurs="1" />
  </xs:all>
</xs:complexType>

<xs:complexType name="ListTemplateDefinition">
  <xs:attribute name="AllowDeletion" type="TRUEFALSE" default="TRUE" />
  <xs:attribute name="AllowEveryoneViewItem" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="AlwaysIncludeContent" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="BaseType" type="ListTemplateBaseType" use="required" />
  <xs:attribute name="CacheSchema" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Catalog" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Category" type="ListTemplateCategoryType" />
  <xs:attribute name="Description" type="xs:string" />
  <xs:attribute name="DisableAttachments" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DisallowContentTypes" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DisplayName" type="xs:string" />
  <xs:attribute name="DocumentAsEnclosure" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DocumentTemplate" type="xs:int" />
  <xs:attribute name="DontSaveInTemplate" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="DraftVersionVisibility" type="xs:int" default="0" />
  <xs:attribute name="EditPage" type="xs:string" />
  <xs:attribute name="EmailAssignTo" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableContentTypes" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableMinorVersions" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="EnableThumbnails" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="FeatureId"
type="UniqueIdentifierWithOrWithoutBracesWithOrWithoutDashes" />
  <xs:attribute name="FolderCreation" type="TRUEFALSE" default="TRUE" />
  <xs:attribute name="ForceCheckout" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Hidden" type="TRUEFALSE" default="FALSE"/>
  <xs:attribute name="HiddenList" type="TRUEFALSE" default="FALSE" />
  <xs:attribute name="Image" type="RelativeUrl" />
  <xs:attribute name="MajorVersionLimit" type="IntNonNegative" use="optional" />
  <xs:attribute name="MajorWithMinorVersionsLimit" type="IntNonNegative" use="optional" />
  <xs:attribute name="ModeratedList" type="TRUEFALSE" default="FALSE" />

```

```

<xs:attribute name="MultipleMtgDataList" type="TRUEFALSE" default="TRUE" />
<xs:attribute name="MustSaveRootFiles" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Name" type="xs:string" />
<xs:attribute name="NewPage" type="xs:string" />
<xs:attribute name="NoCrawl" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="OnQuickLaunch" type="TRUEFALSE" />
<xs:attribute name="OrderedList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Path" type="xs:string" />
<xs:attribute name="PrivateList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="PublicList" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="RootWebOnly" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="SecurityBits" type="xs:string" />
<xs:attribute name="SetupPath" type="RelativeFilePath" />
<xs:attribute name="Sequence" type="xs:int" />
<xs:attribute name="SyncType" type="xs:string" />
<xs:attribute name="ThumbnailSize" type="IntNonNegative" default="0" />
<xs:attribute name="Type" type="xs:int" use="required"/>
<xs:attribute name="Unique" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="UseRootFolderForNavigation" type="TRUEFALSE" />
<xs:attribute name="VersioningEnabled" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="WebImageHeight" type="IntNonNegative" default="0" />
<xs:attribute name="WebImageWidth" type="IntNonNegative" default="0" />
</xs:complexType>

<xs:complexType name="ListTemplateDefinitions" mixed="true">
  <xs:sequence>
    <xs:element name="ListTemplate" type="ListTemplateDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="LogicalJoinDefinition">
  <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element name="And" type="ExtendedLogicalJoinDefinition" />
    <xs:element name="BeginsWith" type="LogicalTestDefinition" />
    <xs:element name="Contains" type="LogicalTestDefinition" />
    <xs:element name="DateRangesOverlap" type="LogicalTestDefinitionDateRange" />
    <xs:element name="Eq" type="LogicalTestDefinition" />
    <xs:element name="Geq" type="LogicalTestDefinition" />
    <xs:element name="Gt" type="LogicalTestDefinition" />
    <xs:element name="In" type="LogicalTestInValuesDefinition" />
    <xs:element name="Includes" type="LogicalTestDefinition" />
    <xs:element name="IsNull" type="LogicalNullDefinition" />
    <xs:element name="IsNotNull" type="LogicalNullDefinition" />
    <xs:element name="Leq" type="LogicalTestDefinition" />
    <xs:element name="Lt" type="LogicalTestDefinition" />
    <xs:element name="Membership" type="MembershipDefinition" />
    <xs:element name="Neq" type="LogicalTestDefinition" />
    <xs:element name="NotIncludes" type="LogicalTestDefinition" />
    <xs:element name="Or" type="ExtendedLogicalJoinDefinition" />
  </xs:choice>
</xs:complexType>

<xs:complexType name="LogicalNullDefinition">
  <xs:all>
    <xs:element name="FieldRef" type="FieldRefDefinitionQueryNull" minOccurs="1"
maxOccurs="1" />
  </xs:all>
</xs:complexType>

```

```

<xs:complexType name="LogicalTestDefinition">
  <xs:all>
    <xs:element name="FieldRef" type="FieldRefDefinitionQueryTest" minOccurs="1"
maxOccurs="1" />
    <xs:element name="Value" type="ValueDefinition" minOccurs="1" maxOccurs="1" />
  </xs:all>
</xs:complexType>

<xs:complexType name="LogicalTestDefinitionDateRange">
  <xs:sequence>
    <xs:element name="FieldRef" type="FieldRefDefinitionQueryDate" minOccurs="2"
maxOccurs="3" />
    <xs:element name="Value" type="ValueDefinitionDateRange" minOccurs="1" maxOccurs="1" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="MAPPINGDEFINITION">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="Value" type="xs:string" />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

<xs:complexType name="MAPPINGDEFINITIONS">
  <xs:sequence>
    <xs:element name="MAPPING" type="MAPPINGDEFINITION" minOccurs="0" maxOccurs="unbounded"
/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="MembershipDefinition">
  <xs:complexContent>
    <xs:extension base="LogicalNullDefinition">
      <xs:attribute name="Type" type="xs:string" use="optional" />
      <xs:attribute name="ID" type="xs:integer" use="optional" />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="MobileViewDefinition">
  <xs:attribute name="MobileSimpleViewField" type="xs:string" use="required" />
  <xs:attribute name="MobileItemLimit" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="OrderByDefinition">
  <xs:sequence>
    <xs:element name="FieldRef" type="FieldRefDefinitionOrderBy" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Override" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE"/>
</xs:complexType>

<xs:complexType name="RowLimitDefinition">
  <xs:simpleContent>
    <xs:extension base="xs:int">

```

```

        <xs:attribute name="Paged" type="TRUE_Case_Insensitive_Else_Anything" use="optional"
default="FALSE"/>
    </xs:extension>
</xs:simpleContent>
</xs:complexType>

<xs:complexType name="ToolbarDefinition">
    <xs:sequence>
        <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any" processContents="skip" />
    </xs:sequence>
    <xs:attribute name="Position" type="ToolbarPosition" />
    <xs:attribute name="Type" type="ToolbarType" />
    <xs:anyAttribute processContents="skip" />
</xs:complexType>

<xs:complexType name="ValueDefinition" mixed="true">
    <xs:sequence>
        <xs:choice minOccurs="0" maxOccurs="unbounded">
            <xs:any namespace="##any" processContents="skip" />
        </xs:choice>
    </xs:sequence>
    <xs:attribute name="Type" type="xs:string" use="optional" />
</xs:complexType>

<xs:complexType name="ValueDefinitionDateRange" mixed="true">
    <xs:sequence>
        <xs:choice minOccurs="0" maxOccurs="1">
            <xs:element name="Month">
                <xs:complexType />
            </xs:element>
            <xs:element name="Now">
                <xs:complexType />
            </xs:element>
            <xs:element name="Today">
                <xs:complexType />
            </xs:element>
            <xs:element name="Week">
                <xs:complexType />
            </xs:element>
        </xs:choice>
    </xs:sequence>
    <xs:attribute name="Type" type="xs:string" use="optional" />
    <xs:attribute name="IncludeTimeValue" type="TRUEFALSE" use="optional" />
    <xs:attribute name="StorageTZ" type="TRUEFALSE" use="optional" />
</xs:complexType>

<xs:complexType name="ViewDefinition">
    <xs:group ref="ViewDefinitionChildElementGroup"/>
    <xs:attribute name="AggregateView" type="TRUEFALSE" default="FALSE"/>
    <xs:attribute name="BaseViewID" type="xs:int" />
    <xs:attribute name="CssStyleSheet" type="xs:string" />
    <xs:attribute name="DefaultView" type="TRUEFALSE" default="FALSE" />
    <xs:attribute name="DisplayName" type="xs:string" />
    <xs:attribute name="FailIfEmpty" type="TRUEFALSE" default="FALSE" />
    <xs:attribute name="FileDialog" type="TRUEFALSE" default="FALSE" />
    <xs:attribute name="FPModified" type="TRUEFALSE" default="FALSE" />
    <xs:attribute name="Hidden" type="TRUEFALSE" default="FALSE" />
    <xs:attribute name="List" type="UniqueIdentifierWithoutBraces" />
    <xs:attribute name="Name" type="UniqueIdentifierWithBraces" />

```

```

<xs:attribute name="ContentTypeID" type="ContentTypeId" />
<xs:attribute name="OrderedView" type="TRUEFALSE" />
<xs:attribute name="DefaultViewForContentType" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="IncludeRootFolder" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="PageType" type="xs:string" />
<xs:attribute name="Path" type="RelativeFilePath" />
<xs:attribute name="Personal" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ReadOnly" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="RecurrenceRowset" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="RequiresClientIntegration" type="TRUEFALSE" default="FALSE"/>
<xs:attribute name="RowLimit" type="xs:int" />
<xs:attribute name="ShowHeaderUI" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="Type" type="ViewType" default="HTML"/>
<xs:attribute name="Url" type="RelativeUrl" />
<xs:attribute name="UseSchemaXmlToolbar" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="WebPartOrder" type="xs:int" />
<xs:attribute name="WebPartZoneID" type="xs:string" />
<xs:attribute name="FreeForm" type="TRUEFALSE" />
<xs:attribute name="ImageUrl" type="xs:string" />
<xs:attribute name="SetupPath" type="RelativeFilePath" />
<xs:attribute name="ToolbarTemplate" type="xs:string" />
<xs:attribute name="MobileView" type="TRUEFALSE" default="FALSE"/>
<xs:attribute name="MobileDefaultView" type="TRUEFALSE" />
<xs:attribute name="MobileUrl" type="RelativeUrl" />
<xs:attribute name="Level" type="ViewPageLevel" default="1" />
<xs:attribute name="FrameState" type="xs:string" default="Normal" />
<xs:attribute name="IsIncluded" type="TRUEFALSE" default="TRUE" />
<xs:attribute name="IncludeVersions" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="HackLockWeb" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="ModerationType" type="ViewModerationType" default="" />
<xs:attribute name="Scope" type="ViewScope" default="" />
<xs:attribute name="Threaded" type="TRUEFALSE" default="FALSE" />
<xs:attribute name="TabularView" type="FALSE_Case_Insensitive_Else_Anything"
default="TRUE" />
</xs:complexType>

<xs:group name="ViewDefinitionChildElementGroup">
  <xs:all>
    <xs:element name="PagedRowset" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="Toolbar" type="ToolbarDefinition" minOccurs="0" maxOccurs="1" />
    <xs:element name="Query" type="CamlQueryRoot" minOccurs="0" maxOccurs="1" />
    <xs:element name="ViewFields" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:element name="FieldRef" type="FieldRefDefinitionView" minOccurs="0"
maxOccurs="unbounded" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
    <xs:element name="GroupByHeader" minOccurs="0" maxOccurs="1">
      <xs:complexType>

```

```

        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="GroupByFooter" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ViewHeader" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ViewBody" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ViewFooter" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="RowLimitExceeded" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>
    <xs:element name="ViewEmpty" minOccurs="0" maxOccurs="1">
      <xs:complexType>
        <xs:sequence>
          <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
      </xs:complexType>
    </xs:element>

```

```

    </xs:complexType>
  </xs:element>
  <xs:element name="PagedRecurrenceRowset" minOccurs="0" maxOccurs="1">
    <xs:complexType>
      <xs:sequence>
        <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
      </xs:sequence>
      <xs:anyAttribute processContents="skip" />
    </xs:complexType>
  </xs:element>
  <xs:element name="PagedClientCallbackRowset" minOccurs="0" maxOccurs="1">
    <xs:complexType>
      <xs:sequence>
        <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
      </xs:sequence>
      <xs:anyAttribute processContents="skip" />
    </xs:complexType>
  </xs:element>
  <xs:element name="Aggregations" type="AggregationsDefinition" minOccurs="0"
maxOccurs="1" />
  <xs:element name="OpenApplicationExtension" type="xs:string" minOccurs="0"
maxOccurs="1" />
  <xs:element name="RowLimit" type="RowLimitDefinition" minOccurs="0" maxOccurs="1"
default="2147483647" />
  <xs:element name="Mobile" type="MobileViewDefinition" minOccurs="0" maxOccurs="1" />
  <xs:element name="ViewStyle" type="ViewStyleReference" minOccurs="0" maxOccurs="1" />
  <xs:element name="CalendarSettings" minOccurs="0" maxOccurs="1">
    <xs:complexType>
      <xs:sequence>
        <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
      </xs:sequence>
      <xs:anyAttribute processContents="skip" />
    </xs:complexType>
  </xs:element>
  <xs:element name="CalendarViewStyles" type="CalendarViewStylesDefinition" minOccurs="0"
maxOccurs="1" />
  <xs:element name="ViewBidiHeader" minOccurs="0" maxOccurs="1">
    <xs:complexType>
      <xs:sequence>
        <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
      </xs:sequence>
      <xs:anyAttribute processContents="skip" />
    </xs:complexType>
  </xs:element>
  <xs:element name="Script" minOccurs="0" maxOccurs="1" mixed="true">
    <xs:complexType>
      <xs:sequence>
        <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
      </xs:sequence>
      <xs:anyAttribute processContents="skip" />
    </xs:complexType>
  </xs:element>
  <xs:element name="ViewData" minOccurs="0" maxOccurs="1">
    <xs:complexType>
      <xs:sequence>

```

```

        <xs:element name="FieldRef" type="FieldRefDefinitionViewData" minOccurs="3"
maxOccurs="5" />
    </xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Formats" type="ViewFormatDefinitions" minOccurs="0" maxOccurs="1" />
<xs:element name="InlineEdit" type="TRUE_If_Present" minOccurs="0" maxOccurs="1" />
<xs:element name="ProjectedFields" type="ProjectedFieldsDefinitionType" minOccurs="0"
maxOccurs="1" />
<xs:element name="Joins" type="ListJoinsDefinitionType" minOccurs="0" maxOccurs="1" />
<xs:element name="Method" type="ViewMethodDefinition" minOccurs="0" maxOccurs="1" />
<xs:element name="ParameterBindings" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
<xs:element name="Xsl" minOccurs="0" maxOccurs="1">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
<xs:element name="XslLink" minOccurs="0" maxOccurs="1" mixed="true">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
<xs:element name="JS" minOccurs="0" maxOccurs="1" mixed="true">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
<xs:element name="JSLink" minOccurs="0" maxOccurs="1" mixed="true">
    <xs:complexType>
        <xs:sequence>
            <xs:any minOccurs="0" maxOccurs="unbounded" namespace="##any"
processContents="skip" />
        </xs:sequence>
        <xs:anyAttribute processContents="skip" />
    </xs:complexType>
</xs:element>
</xs:all>
</xs:group>

```

```

<xs:complexType name="ViewDefinitions">
  <xs:sequence>
    <xs:element name="View" type="ViewDefinition" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="ViewFormatDefinitions">
  <xs:sequence>
    <xs:element name="FormatDef" type="FormatDefDefinition" minOccurs="0"
maxOccurs="unbounded" />
    <xs:element name="Format" type="FormatDefinition" minOccurs="0" maxOccurs="unbounded"
/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="ViewStyleReference">
  <xs:attribute name="ID" type="xs:int" use="optional" />
</xs:complexType>

<xs:complexType name="XmlDocumentDefinition" mixed="true">
  <xs:complexContent>
    <xs:restriction base="xs:anyType">
      <xs:sequence>
        <xs:any namespace="##other" minOccurs="0" maxOccurs="unbounded"
processContents="skip" />
      </xs:sequence>
      <xs:attribute name="NamespaceURI" type="xs:string" use="required" />
    </xs:restriction>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="XmlDocumentDefinitionCollection">
  <xs:sequence>
    <xs:element name="XmlDocument" type="XmlDocumentDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:element name="customXsn">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="xsnLocation" type="xs:string" />
      <xs:element name="cached" type="xs:boolean" />
      <xs:element name="openByDefault" type="xs:boolean" />
      <xs:element name="xsnScope" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
</xs:element>

<xs:complexType name="policy">
  <xs:sequence>
    <xs:element name="Name" type="xs:string" />
    <xs:element name="Description" type="xs:string" minOccurs="0" />
    <xs:element name="Statement" type="xs:string" minOccurs="0" />
    <xs:element name="PolicyItems" minOccurs="0" >
      <xs:complexType>
        <xs:sequence>

```

```

        <xs:element name="PolicyItem" type="policyItem" minOccurs="0" maxOccurs="unbounded"
/>
    </xs:sequence>
</xs:complexType>
</xs:element>
</xs:sequence>
<xs:attribute name="id" type="UniqueIdentifierWithoutBracesOrEmpty" use="required" />
<xs:attribute name="local" type="xs:boolean" use="required" />
</xs:complexType>

<xs:complexType name="PolicyDirtyBag">
    <xs:sequence minOccurs="0" maxOccurs="1">
        <xs:any namespace="##other" minOccurs="0" maxOccurs="unbounded" processContents="skip" />
    </xs:sequence>
</xs:complexType>

<xs:complexType name="PolicyFeatureOperation">
    <xs:attribute name="op" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="policyItem">
    <xs:sequence>
        <xs:element name="Name" type="xs:string" />
        <xs:element name="Statement" type="xs:string" minOccurs="0" />
        <xs:element name="Description" type="xs:string" minOccurs="0" />
        <xs:element name="CustomData" type="customData" minOccurs="0" />
    </xs:sequence>
    <xs:attribute name="featureId" type="xs:string" use="required" />
    <xs:attribute name="BlockPreview" type="xs:boolean" />
    <xs:attribute name="UniqueId" type="xs:string" />
</xs:complexType>

<xs:complexType name="customData">
    <xs:sequence>
        <xs:any processContents="lax" minOccurs="0" maxOccurs="unbounded" />
    </xs:sequence>
</xs:complexType>

<xs:complexType name="barcode">
    <xs:sequence>
        <xs:element name="event" type="PolicyEventDefinition" minOccurs="0" maxOccurs="unbounded"
/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="label">
    <xs:sequence>
        <xs:element name="properties" minOccurs="0">
            <xs:complexType>
                <xs:sequence>
                    <xs:element name="width" type="xs:decimal" minOccurs="0" />
                    <xs:element name="height" type="xs:decimal" minOccurs="0" />
                    <xs:element name="justification" type="xs:string" minOccurs="0" />
                    <xs:element name="fontstyle" type="xs:string" minOccurs="0" />
                    <xs:element name="font" type="xs:string" minOccurs="0" />
                    <xs:element name="fontsize" type="xs:int" minOccurs="0" />
                    <xs:element name="lock" type="xs:boolean" minOccurs="0" />
                </xs:sequence>
            </xs:complexType>
        </xs:element>
    </xs:sequence>
</xs:complexType>

```

```

        </xs:element>
        <xs:element name="event" type="PolicyEventDefinition" minOccurs="0"
maxOccurs="unbounded" />
        <xs:element name="segment" type="PolicySegmentDefinition" maxOccurs="unbounded" />
    </xs:sequence>
</xs:complexType>

<xs:complexType name="audit">
    <xs:all>
        <xs:element name="Update" minOccurs="0" />
        <xs:element name="View" minOccurs="0" />
        <xs:element name="CheckInOut" minOccurs="0" />
        <xs:element name="MoveCopy" minOccurs="0" />
        <xs:element name="DeleteRestore" minOccurs="0" />
    </xs:all>
</xs:complexType>

<xs:complexType name="PolicyEventDefinition">
    <xs:attribute name="type" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="PolicySegmentDefinition">
    <xs:attribute name="type" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="PolicyFormulaDefinition">
    <xs:sequence>
        <xs:element name="number" type="xs:int" />
        <xs:element name="property" type="xs:string" />
        <xs:element name="propertyId" type="xs:string" />
        <xs:element name="period" type="xs:string" />
    </xs:sequence>
    <xs:attribute name="id" type="xs:string" />
</xs:complexType>

<xs:complexType name="PolicyActionDefinition">
    <xs:attribute name="type" type="xs:string" />
    <xs:attribute name="id" type="xs:string" use="required"/>
    <xs:attribute name="destnExplanation" type="xs:string" />
    <xs:attribute name="destnName" type="xs:string" />
    <xs:attribute name="destnUrl" type="xs:string" />
    <xs:attribute name="destnId" type="xs:string" />
</xs:complexType>

<xs:complexType name="ReceiverDefinitions">
    <xs:sequence>
        <xs:element name="Receiver" type="ReceiverDefinition" minOccurs="0" maxOccurs="unbounded"
/>
    </xs:sequence>
    <xs:attribute name="ListTemplateId" type="xs:int" />
    <xs:attribute name="ListUrl" type="xs:string" />
    <xs:attribute name="ListTemplateOwner" type="xs:string" />
    <xs:attribute name="Scope" type="xs:string" />
</xs:complexType>

<xs:complexType name="ReceiverDefinition">
    <xs:all>
        <xs:element name="Name" type="String255Chars" minOccurs="1" maxOccurs="1" />
        <xs:element name="Synchronization" type="xs:string" minOccurs="0" maxOccurs="1" />
    </xs:all>
</xs:complexType>

```

```

    <xs:element name="Type" type="xs:integer" minOccurs="1" maxOccurs="1" />
    <xs:element name="SequenceNumber" type="xs:integer" minOccurs="1" maxOccurs="1" />
    <xs:element name="Assembly" type="AssemblyStrongName" minOccurs="1" maxOccurs="1" />
    <xs:element name="Class" type="AssemblyClass" minOccurs="1" maxOccurs="1" />
    <xs:element name="Data" type="String255Chars" minOccurs="0" maxOccurs="1" />
  </xs:all>
</xs:complexType>

<xs:complexType name="ValueDefinitionCollection">
  <xs:sequence>
    <xs:element name="Value" type="ValueDefinition" minOccurs="0" maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="LogicalTestInValuesDefinition">
  <xs:all>
    <xs:element name="FieldRef" type="FieldRefDefinitionQueryTest" minOccurs="1"
maxOccurs="1" />
    <xs:element name="Values" type="ValueDefinitionCollection" minOccurs="1" maxOccurs="1"
/>
  </xs:all>
</xs:complexType>

<xs:complexType name="ProjectedFieldsDefinitionType">
  <xs:sequence>
    <xs:element name="Field" type="ProjectedFieldDefinitionType" minOccurs="1"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="ProjectedFieldDefinitionType">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="ShowField" type="xs:string" use="required" />
  <xs:attribute name="Type" type="xs:string" use="required" fixed="Lookup" />
  <xs:attribute name="List" type="xs:string" />
  <xs:attribute name="FieldRef" type="xs:string" />
</xs:complexType>

<xs:complexType name="ListJoinsDefinitionType">
  <xs:sequence>
    <xs:element name="Join" type="ListJoinDefinitionType" minOccurs="1"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="ListJoinDefinitionType">
  <xs:choice>
    <xs:element name="Eq" type="ListJoinConditionDefinitionType" />
  </xs:choice>
  <xs:attribute name="Type" type="ListJoinJoinType" default="LEFT" />
  <xs:attribute name="ListAlias" type="xs:string" />
</xs:complexType>

<xs:complexType name="ListJoinConditionDefinitionType">
  <xs:sequence>
    <xs:element name="FieldRef" minOccurs="2" maxOccurs="2" />
  </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="ListJoinConditionSourceFieldDefinitionType">
  <xs:attribute name="Name" type="xs:string" use="required" />
  <xs:attribute name="RefType" type="xs:string" use="required" fixed="Id" />
  <xs:attribute name="List" type="xs:string" />
</xs:complexType>

<xs:complexType name="ListJoinConditionTargetFieldDefinitionType">
  <xs:attribute name="Name" type="xs:string" use="required" fixed="Id" />
  <xs:attribute name="List" type="xs:string" use="required" />
</xs:complexType>

<xs:simpleType name="ListJoinJoinType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="LEFT" />
    <xs:enumeration value="INNER" />
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="LogicalWithIndexDefinition">
  <xs:choice minOccurs="1" maxOccurs="1">
    <xs:element name="And" type="ExtendedLogicalJoinDefinitionWithIndex" />
    <xs:element name="Eq" type="LogicalTestDefinition" />
  </xs:choice>
  <xs:attribute name="ID" type="UniqueIdentifierWithOrWithoutBraces" use="required" />
</xs:complexType>

<xs:complexType name="ExtendedLogicalJoinDefinitionWithIndex">
  <xs:choice>
    <xs:sequence>
      <xs:element name="Eq" type="LogicalTestDefinition" />
      <xs:choice minOccurs="1" maxOccurs="1">
        <xs:element name="Geq" type="LogicalTestDefinition" />
        <xs:element name="Gt" type="LogicalTestDefinition" />
        <xs:element name="Eq" type="LogicalTestDefinition" />
        <xs:element name="In" type="LogicalTestInValuesDefinition" />
        <xs:element name="Leq" type="LogicalTestDefinition" />
        <xs:element name="Lt" type="LogicalTestDefinition" />
      </xs:choice>
    </xs:sequence>
    <xs:sequence>
      <xs:choice minOccurs="1" maxOccurs="1">
        <xs:element name="Geq" type="LogicalTestDefinition" />
        <xs:element name="Gt" type="LogicalTestDefinition" />
        <xs:element name="In" type="LogicalTestInValuesDefinition" />
        <xs:element name="Leq" type="LogicalTestDefinition" />
        <xs:element name="Lt" type="LogicalTestDefinition" />
      </xs:choice>
      <xs:element name="Eq" type="LogicalTestDefinition" />
    </xs:sequence>
  </xs:choice>
</xs:complexType>

<xs:complexType name="FormTemplateDefinitions" mixed="true">
  <xs:sequence>
    <xs:element name="Display" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="Edit" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="New" type="xs:string" minOccurs="0" maxOccurs="1" />
  </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="FormUrlDefinitions">
  <xs:sequence>
    <xs:element name="Display" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="Edit" type="xs:string" minOccurs="0" maxOccurs="1" />
    <xs:element name="New" type="xs:string" minOccurs="0" maxOccurs="1" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="NamespaceDefinition" mixed="true">
  <xs:attribute name="prefix" type="xs:string" use="required" />
  <xs:attribute name="value" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="NamespaceDefinitions" mixed="true">
  <xs:sequence>
    <xs:element name="Namespace" type="NamespaceDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="Schedules">
  <xs:sequence>
    <xs:element name="Schedule" type="PolicyScheduleDefinition" minOccurs="1" />
  </xs:sequence>
  <xs:attribute name="nextStageId" type="xs:int" use="required" />
</xs:complexType>

<xs:complexType name="PolicyScheduleDefinition">
  <xs:sequence>
    <xs:element name="stages">
      <xs:complexType>
        <xs:sequence>
          <xs:element maxOccurs="unbounded" name="data" type="PolicyDataDefinition" />
        </xs:sequence>
      </xs:complexType>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="type" type="xs:string" use="required" />
</xs:complexType>

<xs:complexType name="PolicyDataDefinition">
  <xs:sequence>
    <xs:element name="formula" type="PolicyFormulaDefinition" />
    <xs:element name="action" type="PolicyActionDefinition" />
  </xs:sequence>
  <xs:attribute name="stageId" type="xs:int" use="required" />
  <xs:attribute name="recur" type="xs:boolean" use="optional" />
  <xs:attribute name="offset" type="xs:int" use="optional" />
  <xs:attribute name="unit" type="xs:string" use="optional" />
  <xs:attribute name="stageDeleted" type="xs:boolean" use="optional" />
</xs:complexType>

<xs:complexType name="ViewMethodDefinition">
  <xs:sequence>
    <xs:element name="Filter" type="ViewFilterDefinition" minOccurs="0"
maxOccurs="unbounded" />
  </xs:sequence>
  <xs:attribute name="Name" type="xs:string" use="required"/>

```

```
</xs:complexType>
<xs:complexType name="ViewFilterDefinition">
  <xs:attribute name="Name" type="xs:string" />
  <xs:attribute name="Value" type="xs:string" />
</xs:complexType>

</xs:schema>
```

## 6 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- The 2007 Microsoft Office system
- Microsoft Office 2010 suites
- Microsoft Office 2013
- Microsoft SharePoint Foundation 2010
- Windows SharePoint Services 3.0
- Microsoft SharePoint Foundation 2013
- Windows 8.1 Update

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.17:](#) This type is available only in SharePoint Foundation 2013.

[<2> Section 2.3.2.6.2:](#) Windows SharePoint Services 3.0 does not include the URL attribute if the list is being exported from an external site.

[<3> Section 2.3.2.13.2:](#) This attribute has been deprecated in Windows SharePoint Services 3.0. For future compatibility, it is recommended that **DocumentTemplate** be written as an empty value.

[<4> Section 2.3.2.17.3:](#) This element is available only in SharePoint Foundation 2013.

[<5> Section 2.3.2.17.3:](#) This element is available only in SharePoint Foundation 2013.

[<6> Section 2.5.1.9.2:](#) The 2007 Office system, Office 2010, SharePoint Foundation 2010, Windows SharePoint Services 3.0, and SharePoint Foundation 2013 all enable policies to be defined for a site collection.

[<7> Section 2.5.1.10.3:](#) Office SharePoint Server 2007 uses the **data** element. SharePoint Server 2010 uses either the **data** element or the **Schedules** child elements.

[<8> Section 2.5.1.11.3:](#) The implementations in Office SharePoint Server 2007 and SharePoint Server 2010 prompt the user to insert a barcode into the document when the specified event occurs.

[<9> Section 2.5.1.13.3:](#) The 2007 Office system, Office 2010, SharePoint Foundation 2010, Windows SharePoint Services 3.0, and SharePoint Foundation 2013 all prompt the user to insert a label into the document when the specified event occurs.

[<10> Section 2.5.1.19.2:](#) This value is obsolete for SharePoint Server 2010, but was valid for Office SharePoint Server 2007.

[<11> Section 2.5.1.20.2:](#) Office SharePoint Server 2007, SharePoint Server 2010 and SharePoint Server 2013 maintain a list of locations to transfer the file. Each location has a GUID identifier, a name, and a URL.

## 7 Change Tracking

This section identifies changes that were made to the [MS-WSSCAML] protocol document between the April 2014 and July 2014 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.

- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">2.3.1.9 ViewModerationType</a>	Added the empty value's description in the table for ViewModerationType type.	N	Content updated.
<a href="#">2.3.2.17.1 Schema</a>	Added the JS and JSLink elements into the schema.	N	Content updated.
<a href="#">2.3.2.17.1 Schema</a>	Added the "mixed" value for Script and XslLink elements.	N	Content updated.
<a href="#">2.3.2.17.3 Child Elements</a>	Added description and note for the JS and JSLink elements.	N	Content updated.
<a href="#">2.4.9.1 Schema</a>	Updated the schema for the ContentTypeDefinitionTP complexType.	N	Content updated.
<a href="#">2.5.1.7.3 Child Elements</a>	Updated the schema of the PolicyDirtyBag element.	N	Content updated.
<a href="#">5 Appendix A: Full XML Schema</a>	Added the JS and JSLink elements into the schema.	N	Content updated.
<a href="#">5 Appendix A: Full XML Schema</a>	Added the "mixed" value for Script and XslLink elements.	N	Content updated.
<a href="#">5 Appendix A: Full XML Schema</a>	Updated the schema for the ContentTypeDefinitionTP complexType.	N	Content updated.

## 8 Index

### A

[AggregationsDefinition complex type](#) 43  
[AggregationsType simple type](#) 38  
[AggregationsValue simple type](#) 38  
[Applicability](#) 15

### C

[CalendarViewStyleDefinition complex type](#) 44  
[CalendarViewStylesDefinition complex type](#) 44  
[CamlQueryRoot complex type](#) 21  
[Change tracking](#) 147  
Common types  
  [AssemblyClass](#) 17  
  [AssemblyStrongName](#) 17  
  [FALSE Case Insensitive Else Anything](#) 17  
  [IntNonNegative](#) 17  
  [RelativeFilePath](#) 17  
  [RelativeUrl](#) 18  
  [String255Chars](#) 18  
  [TRUE Case Insensitive Else Anything](#) 18  
  [TRUE Case Sensitive Else Anything](#) 18  
  [TRUE If Present](#) 18  
  [TRUE NegOne Else Anything](#) 18  
  [TRUEFALSE](#) 19  
  [truefalse Only Lowercase](#) 19  
  [UniqueIdentifierWithBraces](#) 19  
  [UniqueIdentifierWithBracesOrEmpty](#) 19  
  [UniqueIdentifierWithOrWithoutBraces](#) 20  
  [UniqueIdentifierWithOrWithoutBracesWithOrWith  
  outDashes](#) 20  
  [UniqueIdentifierWithoutBraces](#) 19  
  [UniqueIdentifierWithoutBracesOrEmpty](#) 19  
Complex types  
  [query types](#) 20  
[Content type schema definitions](#) 73  
[ContentTypeId simple type](#) 39

### E

[Example](#) 100  
[Examples](#) 100  
[ExtendedLogicalJoinDefinition complex type](#) 26  
[ExtendedLogicalJoinDefinitionWithIndex complex  
type](#) 36

### F

[FieldDefinitions complex type](#) 53  
[FieldRefDefinitionAggregation complex type](#) 43  
[FieldRefDefinitionGroupBy complex type](#) 25  
[FieldRefDefinitionOrderBy complex type](#) 24  
[FieldRefDefinitionQueryDate complex type](#) 30  
[FieldRefDefinitionQueryNull complex type](#) 31  
[FieldRefDefinitionQueryTest complex type](#) 27  
[FieldRefDefinitionView complex type](#) 70  
[FieldRefDefinitionViewData complex type](#) 69

[Fields - security index](#) 112  
[Fields - vendor-extensible](#) 15  
  [PolicyItem element](#) 15  
  [XmlDocument element](#) 15  
[FormatDefDefinition complex type](#) 71  
[FormatDefinition complex type](#) 72  
[FormDefinition complex type](#) 45  
[FormType simple type](#) 39  
[Full XML schema](#) 113

### G

[Glossary](#) 12  
[GroupByDefinition complex type](#) 25

### I

[Implementer - security considerations](#) 112  
[Index of security fields](#) 112  
[Informative references](#) 15  
[Introduction](#) 12

### L

List schema - complex types  
  [AggregationsDefinition](#) 43  
  [CalendarViewStyleDefinition](#) 44  
  [CalendarViewStylesDefinition](#) 44  
  [FieldDefinitions](#) 53  
  [FieldRefDefinitionAggregation](#) 43  
  [FieldRefDefinitionView](#) 70  
  [FieldRefDefinitionViewData](#) 69  
  [FormatDefDefinition](#) 71  
  [FormatDefinition](#) 72  
  [FormDefinition](#) 45  
  [ListDefinition](#) 47  
  [ListFormSet](#) 52  
  [ListMetaDataDefinition](#) 52  
  [ListSecurity](#) 54  
  [ListTemplateDefinition](#) 55  
  [ListTemplateDefinitions](#) 55  
  [RowLimitDefinition](#) 60  
  [ToolbarDefinition](#) 60  
  [ViewDefinition](#) 61  
  [ViewDefinitions](#) 61  
  [ViewFormatDefinitions](#) 71  
  [ViewStyleReference](#) 70  
List schema - simple types  
  [AggregationsType](#) 38  
  [AggregationsValue](#) 38  
  [ContentTypeId](#) 39  
  [FormType](#) 39  
  [ListTemplateBaseType](#) 37  
  [ListTemplateCategoryType](#) 39  
  [ToolbarPosition](#) 40  
  [ToolbarType](#) 40  
  [ViewModerationType](#) 41  
  [ViewPageLevel](#) 41

[ViewScope](#) 41  
[ViewType](#) 42  
[List schema definitions](#) 37  
[ListDefinition complex type](#) 47  
[ListFormSet complex type](#) 52  
[ListJoinConditionDefinitionType complex type](#) 34  
[ListJoinConditionSourceFieldDefinitionType complex type](#) 35  
[ListJoinConditionTargetFieldDefinitionType complex type](#) 35  
[ListJoinDefinitionType complex type](#) 34  
[ListJoinsDefinitionType complex type](#) 33  
[ListMetaDataDefinition complex type](#) 52  
[ListSecurity complex type](#) 54  
[ListTemplateBaseType simple type](#) 37  
[ListTemplateCategoryType simple type](#) 39  
[ListTemplateDefinition complex type](#) 55  
[ListTemplateDefinitions complex type](#) 55  
[Localization](#) 15  
[LogicalJoinDefinition complex type](#) 21  
[LogicalNullDefinition complex type](#) 30  
[LogicalTestDefinition complex type](#) 27  
[LogicalTestDefinitionDateRange complex type](#) 28  
[LogicalTestInValuesDefinition complex type](#) 31  
[LogicalWithIndexDefinition complex type](#) 35

## M

[MembershipDefinition complex type](#) 31

## N

[Normative references](#) 14

## O

[OrderByDefinition complex type](#) 24  
[Overview \(synopsis\)](#) 15

## P

[PolicyItem element](#) 15  
[Product behavior](#) 145  
[ProjectedFieldDefinitionType complex type](#) 33  
[ProjectedFieldsDefinitionType complex type](#) 32

## Q

[Query types](#) 20  
  [complex types](#) 20  
  [simple types](#) 20

## R

[References](#) 14  
  [informative](#) 15  
  [normative](#) 14  
[Relationship to protocols and other structures](#) 15  
[RowLimitDefinition complex type](#) 60

## S

Security  
  [field index](#) 112  
  [implementer considerations](#) 112  
Simple types  
  [query types](#) 20  
Structures  
  [content type schema definitions](#) 73  
  [list schema definitions](#) 37  
  [query types](#) 20

## T

[ToolbarDefinition complex type](#) 60  
[ToolbarPosition simple type](#) 40  
[ToolbarType simple type](#) 40  
[Tracking changes](#) 147  
Types - simple  
  [AssemblyClass](#) 17  
  [AssemblyStrongName](#) 17  
  [FALSE Case Insensitive Else Anything](#) 17  
  [IntNonNegative](#) 17  
  [RelativeFilePath](#) 17  
  [RelativeUrl](#) 18  
  [String255Chars](#) 18  
  [TRUE Case Insensitive Else Anything](#) 18  
  [TRUE Case Sensitive Else Anything](#) 18  
  [TRUE If Present](#) 18  
  [TRUE NegOne Else Anything](#) 18  
  [TRUEFALSE](#) 19  
  [truefalse Only Lowercase](#) 19  
  [UniqueIdentifierWithBraces](#) 19  
  [UniqueIdentifierWithBracesOrEmpty](#) 19  
  [UniqueIdentifierWithOrWithoutBraces](#) 20  
  [UniqueIdentifierWithOrWithoutBracesWithOrWithoutDashes](#) 20  
  [UniqueIdentifierWithoutBraces](#) 19  
  [UniqueIdentifierWithoutBracesOrEmpty](#) 19

## V

[ValueDefinition complex type](#) 27  
[ValueDefinitionCollection complex type](#) 32  
[ValueDefinitionDateRange complex type](#) 29  
[Vendor-extensible fields](#) 15  
[Versioning](#) 15  
[ViewDefinition complex type](#) 61  
[ViewDefinitions complex type](#) 61  
[ViewFormatDefinitions complex type](#) 71  
[ViewModerationType simple type](#) 41  
[ViewPageLevel simple type](#) 41  
[ViewScope simple type](#) 41  
[ViewStyleReference complex type](#) 70  
[ViewType simple type](#) 42

## X

[XML schema](#) 113  
[XmlDocument element](#) 15