

[MS-XJRNL]: Journal Record Message File Format

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.msp>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Revised and edited technical content.
09/03/2008	1.02		Revised and edited technical content.
12/03/2008	1.03		Updated IP notice.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	3.1.0	Minor	Updated the technical content.
02/10/2010	3.2.0	Minor	Updated the technical content.
05/05/2010	3.2.1	Editorial	Revised and edited the technical content.

Table of Contents

1 Introduction	4
1.1 Glossary	4
1.2 References	5
1.2.1 Normative References	5
1.2.2 Informative References	5
1.3 Overview	6
1.3.1 Body Text of the Journal-Report Message	6
1.3.2 original-message	6
1.4 Relationship to Protocols and Other Structures	6
1.5 Applicability Statement	7
1.6 Versioning and Localization	7
1.7 Vendor-Extensible Fields	7
2 Structures	8
2.1 Envelope-Part	8
2.1.1 Sender	8
2.1.2 Subject	8
2.1.3 Message-ID	8
2.1.4 recipient-specification	8
2.1.4.1 recipient-p2-type	8
2.1.4.2 forward-path	9
2.1.4.3 redirection-type	9
2.1.4.3.1 Expanded	9
2.1.4.3.2 Forwarded	9
2.1.4.4 original-forward-path	9
2.1.5 label	10
2.2 Original-Message-Part	10
3 Structure Examples	11
4 Security Considerations	12
5 Appendix A: Product Behavior	13
6 Change Tracking	14
7 Index	16

1 Introduction

Journal record **messages** are e-mail messages that are generated by the server to capture and report information about messages sent to and from users of the e-mail system. For background information about how journaling works, see [\[MSFT-WPXTJ\]](#).

This **document** specifies an extension to [\[RFC2045\]](#) and [\[RFC2046\]](#) to accommodate journal record messages.

1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

ASCII
Attachment
Augmented Backus-Naur Form (ABNF)
Bcc recipient
binary large object (BLOB)
body part
Cc recipient
character set
distribution list
journal
Journal-Report
message
message ID (MID)
MIME
MIME content-type
MIME message
original-message
recipient(1)
Simple Mail Transfer Protocol (SMTP)
To recipient

The following terms are specific to this document:

body: The contents of a **body part** or an entire **message** (containing several **body parts**), as specified in [\[RFC2045\]](#) section 2.6.

Content-Transfer-Encoding: A header field that defines a way of encoding non-**ASCII** character data as **ASCII** data. This is specified in [\[RFC2045\]](#) section 6.

encoding: The process of specifying a Content-Transfer-Encoding to transform character data from one form to another.

Envelope-Part: The portion of a **Journal-Report** containing metadata about the journaled **message** in machine-readable form.

message/rfc822: The **MIME content-type** of an e-mail message that is embedded within another e-mail message. The type is expressed via the well known **MIME content-type** header field. The message/rfc822 type is specified in [\[RFC2046\]](#) section 5.2.

MIME attachment: A body part within a **MIME message**, for example, an e-mail **message** or file that is attached to an e-mail **message**.

Original-Message-Part: The portion of a **Journal-Report** that captures the contents of the **original-message** that was journaled. The Original-Message-Part contains the entire data of the **original-message**. The Original-Message-Part is an opaque **binary large object (BLOB)**.

recipient forwarding: A feature provided by many e-mail delivery systems, where a **message** sent to one **recipient** e-mail address is instead redirected to a different e-mail address, called the "forwarded address". E-mail software typically provides methods to configure which specific e-mail addresses are enabled for recipient forwarding. Some e-mail systems allow configuring whether the **message** is entirely redirected to the forwarded address with no copy going to the original e-mail address, or whether the original e-mail address receives a copy of the **message** in addition to the forwarded address.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", April 2008.

[MS-OXMSG] Microsoft Corporation, "[.MSG File Format](#)", April 2008.

[RFC2045] Freed, N., and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", RFC 2045, November 1996, <http://www.ietf.org/rfc/rfc2045.txt>

[RFC2046] Freed, N., and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", RFC 2046, November 1996, <http://www.ietf.org/rfc/rfc2046.txt>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", RFC 2119, BCP 14, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

[RFC2821] Klensin, J., Ed., "Simple Mail Transfer Protocol", RFC 2821, April 2001, <http://www.ietf.org/rfc/rfc2821.txt>

[RFC2822] Resnick, P., Ed., "Internet Message Format", RFC 2822, April 2001, <http://www.ietf.org/rfc/rfc2822.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 5234, STD 68, January 2008, <http://www.ietf.org/rfc/rfc5234.txt>

1.2.2 Informative References

[MSFT-WPXTJ] Chand, N., "White Paper: Exchange 2007 Transport Journaling", September 2007, <http://go.microsoft.com/fwlink/?LinkId=111316>

1.3 Overview

Journal-Reports are **MIME messages** produced by the server that capture information about other ordinary (non-Journal-Report) messages sent through the server. These other messages are referred to here as **original-messages**.

1.3.1 Body Text of the Journal-Report Message

The **body** text of the Journal-Report message lists the e-mail addresses of the sender and **recipients** of the message, the subject, the Internet **message ID (MID)**, and certain other metadata about the original-message. The body text is referred to as the **Envelope-Part** of the Journal-Report. This document formally specifies the structure of the Envelope-Part.

1.3.2 original-message

The original-message is attached as a **MIME attachment** to the Envelope-Part. This is referred to as the **Original-Message-Part** of the Journal-Report. How the Original-Message-Part is attached to the Envelope-Part is fully specified in [\[RFC2045\]](#) and [\[RFC2046\]](#).

1.4 Relationship to Protocols and Other Structures

The Envelope-Part that is documented here is a substructure within the larger structure of the Journal-Report MIME message. The Journal-Report structure is a MIME message and conforms to [\[RFC2045\]](#) and [\[RFC2046\]](#).

[\[RFC2045\]](#) specifies how messages with a **MIME content-type** of **Message/rfc822** might be nested recursively as **attachments**. The outermost Message/rfc822 **body part** of the Journal-Report contains the Envelope-Part as the body.

The Envelope-Part is encoded using the mechanisms prescribed in [\[RFC2045\]](#), such as the **Content-Transfer-Encoding** mechanism, which specifies details such as the **character set** and encoding used for the data in the Envelope-Part. This document specifies the syntax of the Envelope-Part prior to any **MIME encoding** being applied.

To illustrate the concept of encoding: The Envelope-Part could contain textual data outside the **ASCII** character set range if the original-message had any non-English text. The MIME message is in many circumstances constrained to contain only data in the ASCII character range, so the MIME standards define methods of encoding non-ASCII data using mechanisms such as "base64" and "quote-printable encoding." Thus, if an encoding mechanism was specified for the Envelope-Part using standardized MIME conventions, decoding would be done before processing the Envelope-Part structure.

The terms **Content-Transfer-Encoding**, character set, and encoding are specified in [\[RFC2045\]](#). The mechanism for decoding the Envelope-Part is specified in [\[RFC2045\]](#) section 6.

Figure 1 shows how the Envelope-Part substructure is placed in relation to the various other substructures in the Journal-Report MIME message.




Figure 1: MIME structure of a Journal-Report message

1.5 Applicability Statement

Applications can use this protocol to create and consume journal record messages.

1.6 Versioning and Localization

None.

1.7 Vendor-Extensible Fields

None.

2 Structures

Journal-Reports extend the structures defined in [\[RFC2045\]](#) and [\[RFC2046\]](#) by defining a substructure called the Envelope-Part, which is embedded within the MIME message.

2.1 Envelope-Part

The **Augmented Backus-Naur Form (ABNF)** notation [\[RFC5234\]](#) is used to specify the format of the Envelope-Part. The format is a series of field/value pairs on CRLF terminated lines.

```
<Envelope-Part> =  
"Sender:" SP <reverse-path> CRLF  
"Subject:" SP <subject-string> CRLF  
"Message-ID:" SP <msg-id> CRLF  
1*<recipient-specification>  
0*1<label>
```

2.1.1 Sender

The **reverse-path** field is a **Simple Mail Transfer Protocol (SMTP)** e-mail address as specified in [\[RFC2821\]](#). This field MUST be set to the sender of the original-message.

2.1.2 Subject

The **subject-string** field MUST contain the data from the "Subject" header of the original-message. This header is specified in [\[RFC2822\]](#).

The **subject-string** can consist of characters outside the ASCII character set range as specified in [\[RFC2045\]](#) and [\[RFC2046\]](#). The MIME content-type header of the respective body part in which Envelope-Part is embedded MUST specify the character set to use to interpret the **subject-string** in accordance with the MIME specifications [\[RFC2045\]](#) and [\[RFC2046\]](#).

2.1.3 Message-ID

The **msg-id** field MUST contain the value of the SMTP "Message-ID" header of the original-message. This header is specified in [\[RFC2822\]](#) section 3.6.4.

2.1.4 recipient-specification

One or more occurrences of **recipient-specification** give information about the recipients of the original-message that was journaled.

The following provides details about **recipient-specification**:

```
<recipient-specification> =  
<recipient-p2-type> ":" SP <forward-path>  
[<redirection-type> ":" SP <original-forward-path>] CRLF  
<recipient-p2-type> = "Bcc" / "To" / "Cc" / "Recipient"  
<redirection-type> = "Expanded" / "Forwarded"
```

2.1.4.1 recipient-p2-type

This field MUST be set according to the following table:

Value	Meaning
"Bcc"	The recipient listed in forward-path was addressed as a Bcc recipient .
"To"	The recipient listed in forward-path was addressed as a To recipient .
"Cc"	The recipient listed in forward-path was addressed as a Cc recipient .
"Recipient"	The server was unable to determine how the recipient was addressed.

2.1.4.2 forward-path

This field is an SMTP e-mail address as specified in [\[RFC2821\]](#). This field MUST be set to a recipient of the original-message.

2.1.4.3 redirection-type

This field MUST be set to either "Expanded" or "Forwarded."

2.1.4.3.1 Expanded

A message sent to a **distribution list** is redirected instead to the users and distribution groups contained within the distribution list. This process is known as "expansion" and the distribution group is said to have been "expanded." The expansion is repeated for the nested distribution groups until all distribution groups have been expanded to ordinary users. The **redirection-type** element, when set to "Expanded", denotes that the sender of the message sent it originally to **original-forward-path**, which was a distribution group. The server then expanded **original-forward-path** to one or more recipients (perhaps expanding nested recipients repeatedly until all recipients were non-distribution group, ordinary recipients). Each of these expanded recipients is listed in the **forward-path** field of a recipient-specification.

2.1.4.3.2 Forwarded

A **redirection-type** of "Forwarded" indicates that the recipient indicated by **original-forward-path** was configured for **recipient forwarding**. The message was forwarded to the recipient indicated by **forward-path**.

2.1.4.4 original-forward-path

This field is an SMTP e-mail address as specified in [\[RFC2821\]](#). The **original-forward-path** field is the SMTP address of the recipient that was redirected to **forward-path** by the server. Although syntactically identical to **forward-path**, it has different semantics. The appearance of **redirection-type** and **original-forward-path** in a recipient-specification indicates that originally the message that was journaled was sent to the recipient with address **original-forward-path** and the server did one of the following:

1. Changed the recipient address to **forward-path**.
2. Added a new recipient with the address **forward-path** due to the **original-forward-path** recipient being present.

If the server does not have information about what type of forwarding or expansion was done on the recipient, the **redirection-type** and **original-forward-path** elements are omitted.

2.1.5 label

If present, this optional field MUST contain a text value, the contents of which are implementation-specific.

The following provides detail about **label**:

```
<label> = "Label:" SP 1*255CHAR CRLF
```

2.2 Original-Message-Part

This data MUST be one of the following:

- A MIME attachment of type Message/rfc822.
- A .MSG file as specified in [\[MS-OXMSG\]](#).

Neither format is preferred over the other. The choice of format is left to the implementation.

3 Structure Examples

The following is an example of the Envelope-Part of Journal-Report, followed by an explanation of the various syntax elements (note that the line numbers are not present in the actual Envelope-Part, but are shown here so the structure can be discussed line by line):

```
Sender: sender@contoso.com
Subject: Sample Message
Message-ID: <12345@contoso.com>
To: dl-to-member1@contoso.com, Expanded: dl-to@contoso.com
To: dl-to-member2@contoso.com, Expanded: dl-to@contoso.com
Cc: fwd@contoso.com, Forwarded: user@contoso.com
Bcc: dl-bcc-member@contoso.com, Expanded: dl-bcc@contoso.com
Bcc: fwd@contoso.com, Forwarded: user@contoso.com
Recipient: user-unk@contoso.com
```

1. The sender of the original-message was "sender@contoso.com."
2. The subject of the original-message was "Sample Message."
3. The message ID of the original-message was "12345@contoso.com."
4. The original-message was sent by the mail client as To: to dl-to@contoso.com, which is a distribution list that was expanded to dl-to-member1@contoso.com and dl-to-member2@contoso.com (captured in Line 5) by the server.
5. See (4).
6. The original-message was sent to user@contoso.com as Cc:, which was changed by the e-mail server to fwd@contoso.com because recipient forwarding was configured. User@contoso.com did not receive a copy of the message because there is no **recipient-specification** where user@contoso.com was listed in the **forward-path**.
7. The original-message was sent by the mail client as Bcc: to dl-bcc@contoso.com, which is a distribution list that was expanded to dl-bcc-member@contoso.com.
8. The original-message was sent to user@contoso.com as Bcc:, which was rewritten by the e-mail server to fwd@contoso.com because recipient forwarding was configured. User@contoso.com did not receive a copy of the message because there is no **recipient-specification** where user@contoso.com was listed in the **forward-path**.
9. Finally, there is no information about whether user-unk@contoso.com was sent the original-message as a To, Cc, or Bcc recipient. It is also not known whether this recipient got the message due to distribution list expansion, recipient forwarding, or was directly addressed by the sender. The "recipient:" element indicates that the server was only able to capture that user-unk@contoso.com was a recipient of the message and no further recipient metadata was available.

4 Security Considerations

This format does not implement or concern itself with security, but relies on the underlying e-mail transport software and e-mail storage software to provide security as applicable.

5 Appendix A: Product Behavior

The information in this specification is applicable to the following product versions. References to product versions include released service packs.

- Microsoft® Office Outlook® 2007
- Microsoft® Exchange Server 2007
- Microsoft® Outlook® 2010
- Microsoft® Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

6 Change Tracking

This section identifies changes made to [MS-XJRN] protocol documentation between February 2010 and May 2010 releases. Changes are classed as major, minor, or editorial.

Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- A protocol is deprecated.
- The removal of a document from the documentation set.
- Changes made for template compliance.

Minor changes do not affect protocol interoperability or implementation. Examples are updates to fix technical accuracy or ambiguity at the sentence, paragraph, or table level.

Editorial changes apply to grammatical, formatting, and style issues.

No changes means that the document is identical to its last release.

Major and minor changes can be described further using the following revision types:

- New content added.
- Content update.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.

- Content removed for template compliance.
- Obsolete document removed.

Editorial changes always have the revision type "Editorially updated."

Some important terms used in revision type descriptions are defined as follows:

Protocol syntax refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.

Protocol revision refers to changes made to a protocol that affect the bits that are sent over the wire.

Changes are listed in the following table. If you need further information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
1.3 Overview	Updated the section title.	N	Content updated for template compliance.

7 Index

C

[Tracking changes](#) 14

[Change tracking](#) 14

[Common data types and fields](#) 8

D

[Data types and fields - common](#) 8

Details

[common data types and fields](#) 8

[Envelope-Part structure](#) 8

[Original-Message-Part structure](#) 10

E

[Envelope-Part structure](#) 8

[Example](#) 11

G

[Glossary](#) 4

I

[Implementer - security considerations](#) 12

[Informative references](#) 5

[Introduction](#) 4

N

[Normative references](#) 5

O

[Original-Message-Part structure](#) 10

[Overview](#) 6

P

[Product behavior](#) 13

R

References

[informative](#) 5

[normative](#) 5

Relationship to protocols and other structures

([section 1.4](#) 6, [section 1.5](#) 7)

S

[Security - implementer considerations](#) 12

Structures

[Envelope-Part](#) 8

[Original-Message-Part](#) 10

[overview](#) 8

T