

[MS-XLSX]: Excel (.xlsx) Extensions to the Office Open XML SpreadsheetML File Format

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
07/13/2009	0.1	Major	Initial Availability
08/28/2009	0.2	Editorial	Revised and edited the technical content
11/06/2009	0.3	Editorial	Revised and edited the technical content
02/19/2010	1.0	Major	Updated and revised the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Editorial	Revised and edited the technical content
06/07/2010	1.03	Editorial	Revised and edited the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	1.5	Minor	Clarified the meaning of the technical content.
06/10/2011	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	2.0	Major	Significantly changed the technical content.
04/11/2012	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	3.0	Major	Significantly changed the technical content.
10/08/2012	4.0	Major	Significantly changed the technical content.
02/11/2013	4.1	Minor	Clarified the meaning of the technical content.
07/30/2013	4.1	No change	No changes to the meaning, language, or formatting of the technical content.
11/18/2013	4.2	Minor	Clarified the meaning of the technical content.
02/10/2014	4.2	No change	No changes to the meaning, language, or formatting of the technical content.

Date	Revision History	Revision Class	Comments
04/30/2014	4.3	Minor	Clarified the meaning of the technical content.
07/31/2014	5.0	Major	Significantly changed the technical content.

Table of Contents

1	Introduction	11
1.1	Glossary	11
1.2	References	13
1.2.1	Normative References	13
1.2.2	Informative References	14
1.3	Structure Overview (Synopsis)	14
1.4	Relationship to Protocols and Other Structures	15
1.5	Applicability Statement	15
1.6	Versioning and Localization	15
1.7	Vendor-Extensible Fields	16
2	Structures	17
2.1	Part Enumerations	17
2.1.1	Control Properties	17
2.1.2	Custom Data	17
2.1.3	Custom Data Properties	18
2.1.4	Slicer Cache	18
2.1.5	Slicers	18
2.1.6	Data Model	19
2.1.6.1	Command Annotations	19
2.1.6.2	DimensionAttribute Annotations	20
2.1.7	Timeline Cache	20
2.1.8	Timelines	21
2.1.9	Survey	21
2.2	Extensions	21
2.2.1	SpreadsheetML Extensibility Elements	22
2.2.2	Formulas	22
2.2.2.1	Cell Formulas	50
2.2.2.2	Conditional Formatting Formulas	50
2.2.2.3	Data Validation Formulas	50
2.2.2.4	External Name Formulas	51
2.2.2.5	Name Formulas	51
2.2.2.6	Pivot Field Formulas	51
2.2.2.7	Pivot Item Formulas	52
2.2.3	Functions	52
2.2.4	Extensions by Part	56
2.2.4.1	Connections	56
2.2.4.2	Drawing	57
2.2.4.3	External Workbook References	58
2.2.4.4	Pivot Table	58
2.2.4.5	Pivot Table Cache Definition	60
2.2.4.6	Query Table	62
2.2.4.7	Styles	62
2.2.4.8	SlicerCache	63
2.2.4.9	Table Definition	63
2.2.4.10	Workbook	65
2.2.4.11	Worksheet	65
2.3	Conceptual Overview	68
2.3.1	PivotTable What-if Analysis	68
2.3.2	Slicers	68

2.3.2.1	Slicer Cache	69
2.3.2.1.1	Slicer Source Data	69
2.3.2.1.2	Slicer Cache Relationship to PivotCache	69
2.3.2.1.3	Slicer Cache Relationship to Table	70
2.3.2.1.4	Slicer Cache Relationship to PivotTable View	70
2.3.2.1.5	Slicer Cache Relationship to Table column	71
2.3.2.1.6	Slicer Items	71
2.3.2.1.6.1	Non-OLAP Slicer Items	71
2.3.2.1.6.2	OLAP Slicer Items	72
2.3.2.1.7	Slicer Cross Filtering	72
2.3.2.2	Slicer View	72
2.3.2.2.1	Slicer View Relationship to Slicer Cache	73
2.3.2.3	Slicers and Cube Functions	73
2.3.2.4	Slicer Styles	73
2.3.3	Non-Worksheet PivotTable	74
2.3.4	PivotValues	74
2.3.4.1	PivotValueCell	74
2.3.4.1.1	Value	74
2.3.4.1.2	Server Formatting	74
2.3.5	Timelines	74
2.3.5.1	Timeline Cache	75
2.3.5.1.1	Timeline Source Data	75
2.3.5.1.2	Timeline Cache Relationship to PivotCache	75
2.3.5.1.3	Timeline Cache Relationship to PivotTable View	75
2.3.5.1.4	Timeline State	76
2.3.5.2	Timeline View	76
2.3.5.2.1	Timeline View Relationship to Timeline Cache	76
2.3.5.3	Timelines and Cube Functions	76
2.3.5.4	Timeline Styles	76
2.4	Global Elements	77
2.4.1	pivotTableReference	77
2.4.2	pivotTableServerFormats	77
2.4.3	f	77
2.4.4	ref	78
2.4.5	sqref	78
2.4.6	conditionalFormattings	78
2.4.7	dataValidations	79
2.4.8	sparklineGroups	79
2.4.9	slicerList	79
2.4.10	protectedRanges	80
2.4.11	ignoredErrors	80
2.4.12	pivotCaches	80
2.4.13	slicerCaches	80
2.4.14	workbookPr	81
2.4.15	calculatedMember	81
2.4.16	cacheHierarchy	81
2.4.17	dataField	82
2.4.18	pivotField	82
2.4.19	pivotTableDefinition	82
2.4.20	pivotCacheDefinition	83
2.4.21	connection	83
2.4.22	table	83
2.4.23	slicerStyles	83

2.4.24	dxfs	84
2.4.25	oleItem	84
2.4.26	pivotHierarchy	84
2.4.27	cacheField	85
2.4.28	id	85
2.4.29	iconFilter	85
2.4.30	filter	86
2.4.31	customFilters	86
2.4.32	sortCondition	86
2.4.33	sourceConnection	86
2.4.34	formControlPr	87
2.4.35	datastoreItem	87
2.4.36	slicers	87
2.4.37	slicer	88
2.4.38	slicerCacheDefinition	88
2.4.39	pivotCaches	88
2.4.40	pivotTableReferences	89
2.4.41	queryTable	89
2.4.42	webExtensions	89
2.4.43	connection	90
2.4.44	calculatedMember	90
2.4.45	pivotTableUISettings	90
2.4.46	pivotFilter	90
2.4.47	slicerCaches	91
2.4.48	tableSlicerCache	91
2.4.49	timelineCacheRefs	91
2.4.50	timelineRefs	92
2.4.51	timelineCachePivotCaches	92
2.4.52	cacheHierarchy	92
2.4.53	slicerCacheHideItemsWithNoData	92
2.4.54	timelineStyles	93
2.4.55	dxfs	93
2.4.56	timelinePivotCacheDefinition	93
2.4.57	timelines	94
2.4.58	timelineCacheDefinition	94
2.4.59	workbookPr	94
2.4.60	slicerCachePivotTables	94
2.4.61	cachedUniqueNames	95
2.4.62	dataModel	95
2.4.63	pivotTableData	95
2.4.64	pivotCacheDecoupled	96
2.4.65	pivotCacheIdVersion	96
2.4.66	timeslicer	96
2.4.67	list	97
2.4.68	absPath	97
2.4.69	dataField	97
2.4.70	survey	98
2.4.71	contentPart	98
2.5	Global Attributes	98
2.5.1	dyDescent	98
2.5.2	knownFonts	98
2.6	Complex Types	99
2.6.1	CT_ConditionalFormattings	99

2.6.2	CT_ConditionalFormatting	99
2.6.3	CT_DataValidations	100
2.6.4	CT_DataValidationFormula	101
2.6.5	CT_DataValidation	102
2.6.6	CT_SparklineGroups	104
2.6.7	CT_SparklineGroup	104
2.6.8	CT_Sparklines	108
2.6.9	CT_Sparkline	109
2.6.10	CT_WorkbookPr	109
2.6.11	CT_SlicerRefs	110
2.6.12	CT_SlicerRef	110
2.6.13	CT_SlicerCaches	111
2.6.14	CT_SlicerCache	111
2.6.15	CT_CalculatedMember	112
2.6.16	CT_TupleSet	113
2.6.17	CT_TupleSetHeaders	114
2.6.18	CT_TupleSetHeader	114
2.6.19	CT_TupleSetRows	115
2.6.20	CT_TupleSetRow	115
2.6.21	CT_TupleSetRowItem	116
2.6.22	CT_SetLevels	116
2.6.23	CT_SetLevel	117
2.6.24	CT_CacheHierarchy	117
2.6.25	CT_DataField	120
2.6.26	CT_Cfvo	122
2.6.27	CT_CfRule	123
2.6.28	CT_IconSet	127
2.6.29	CT_ColorScale	128
2.6.30	CT_DataBar	129
2.6.31	CT_PivotField	132
2.6.32	CT_PivotTableDefinition	133
2.6.33	CT_PivotCacheDefinition	135
2.6.34	CT_Connection	136
2.6.35	CT_Table	137
2.6.36	CT_CfIcon	138
2.6.37	CT_PivotEdits	138
2.6.38	CT_PivotEdit	139
2.6.39	CT_PivotChanges	139
2.6.40	CT_PivotChange	140
2.6.41	CT_PivotUserEdit	141
2.6.42	CT_PivotEditValue	141
2.6.43	CT_TupleItems	142
2.6.44	CT_SlicerStyle	142
2.6.45	CT_SlicerStyleElement	143
2.6.46	CT_OleItem	144
2.6.47	CT_PivotHierarchy	145
2.6.48	CT_CacheField	146
2.6.49	CT_ConditionalFormats	147
2.6.50	CT_ConditionalFormat	148
2.6.51	CT_SlicerStyles	149
2.6.52	CT_SlicerStyleElements	149
2.6.53	CT_IgnoredErrors	150
2.6.54	CT_IgnoredError	150

2.6.55	CT_ProtectedRanges	153
2.6.56	CT_ProtectedRange	153
2.6.57	CT_IconFilter	155
2.6.58	CT_Filter	155
2.6.59	CT_CustomFilters	156
2.6.60	CT_CustomFilter	157
2.6.61	CT_SortCondition	157
2.6.62	CT_SourceConnection	158
2.6.63	CT_ListItem	159
2.6.64	CT_ListItems	159
2.6.65	CT_FormControlPr	160
2.6.66	CT_DatastoreItem	164
2.6.67	CT_Slicers	165
2.6.68	CT_Slicer	165
2.6.69	CT_Slicer	167
2.6.70	CT_SlicerCacheDefinition	168
2.6.71	CT_SlicerCacheData	169
2.6.72	CT_SlicerCachePivotTables	169
2.6.73	CT_SlicerCachePivotTable	170
2.6.74	CT_OlapSlicerCacheItem	171
2.6.75	CT_OlapSlicerCacheItemParent	171
2.6.76	CT_OlapSlicerCacheRange	172
2.6.77	CT_OlapSlicerCacheRanges	172
2.6.78	CT_OlapSlicerCacheLevelData	173
2.6.79	CT_OlapSlicerCacheLevelsData	174
2.6.80	CT_OlapSlicerCache	174
2.6.81	CT_OlapSlicerCacheSelections	175
2.6.82	CT_OlapSlicerCacheSelection	176
2.6.83	CT_TabularSlicerCache	176
2.6.84	CT_TabularSlicerCacheItems	178
2.6.85	CT_TabularSlicerCacheItem	178
2.6.86	CT_PivotTableReferences	179
2.6.87	CT_PivotTableReference	180
2.6.88	CT_QueryTable	180
2.6.89	CT_WebExtensions	181
2.6.90	CT_WebExtension	181
2.6.91	CT_Connection	182
2.6.92	CT_CalculatedMemberExt	184
2.6.93	CT_CalculatedMember	184
2.6.94	CT_FieldListActiveTabTopLevelEntity	185
2.6.95	CT_PivotFilter	186
2.6.96	CT_PivotTableUISettings	188
2.6.97	CT_TableSlicerCache	188
2.6.98	CT_TimelineCacheRefs	189
2.6.99	CT_TimelineCacheRef	190
2.6.100	CT_TimelineRefs	190
2.6.101	CT_TimelineRef	191
2.6.102	CT_CacheHierarchy	191
2.6.103	CT_SlicerCacheHideNoData	192
2.6.104	CT_SlicerCacheOlapLevelName	192
2.6.105	CT_TimelineStyles	193
2.6.106	CT_TimelineStyleElements	193
2.6.107	CT_TimelineStyle	194

2.6.108	CT_TimelineStyleElement	194
2.6.109	CT_TimelinePivotCacheDefinition	195
2.6.110	CT_Timelines	195
2.6.111	CT_Timeline	196
2.6.112	CT_TimelineCacheDefinition	198
2.6.113	CT_TimelineCachePivotTables.....	200
2.6.114	CT_TimelineCachePivotTable	200
2.6.115	CT_TimelineRange	201
2.6.116	CT_TimelineState	201
2.6.117	CT_WorkbookPr	202
2.6.118	CT_TimelinePivotFilter	203
2.6.119	CT_ModelTextPr.....	204
2.6.120	CT_RangePr	205
2.6.121	CT_DbTable	205
2.6.122	CT_DbTables.....	205
2.6.123	CT_DbCommand.....	206
2.6.124	CT_OleDbPr.....	206
2.6.125	CT_DataFeedPr.....	207
2.6.126	CT_CachedUniqueNames	207
2.6.127	CT_CachedUniqueName.....	208
2.6.128	CT_ModelTable	209
2.6.129	CT_ModelTables.....	209
2.6.130	CT_ModelRelationship	210
2.6.131	CT_ModelRelationships	210
2.6.132	CT_DataModel	211
2.6.133	CT_PivotTableData.....	211
2.6.134	CT_PivotRow	212
2.6.135	CT_PivotValueCell	213
2.6.136	CT_PivotValueCellExtra.....	214
2.6.137	CT_PivotTableServerFormats.....	215
2.6.138	CT_PivotCacheDecoupled.....	215
2.6.139	CT_PivotCacheIdVersion	216
2.6.140	CT_Timeline	216
2.6.141	CT_AbsolutePath	217
2.6.142	CT_DataField.....	217
2.6.143	CT_Survey	218
2.6.144	CT_SurveyQuestions	219
2.6.145	CT_SurveyQuestion.....	219
2.6.146	CT_SurveyElementPr.....	221
2.6.147	CT_Ref	222
2.6.148	CT_Sqref	223
2.6.149	CT_ApplicationNonVisualDrawingProps	223
2.6.150	CT_CacheSourceExt	224
2.6.151	CT_ContentPart	224
2.6.152	CT_ContentPartNonVisual	225
2.7	Simple Types	225
2.7.1	ST_Ref.....	225
2.7.2	ST_Sqref.....	226
2.7.3	ST_DisbBlanksAs.....	226
2.7.4	ST_SparklineAxisMinMax	227
2.7.5	ST_SparklineType	228
2.7.6	ST_PivotShowAs	228
2.7.7	ST_DataBarDirection	229

2.7.8	ST_DataBarAxisPosition	229
2.7.9	ST_CfvoType	230
2.7.10	ST_IconSetType	231
2.7.11	ST_PivotEditValueType	233
2.7.12	ST_AllocationMethod	233
2.7.13	ST_SlicerStyleType	234
2.7.14	ST_ObjectType	235
2.7.15	ST_Checked	236
2.7.16	ST_DropStyle	236
2.7.17	ST_SelType	237
2.7.18	ST_EditValidation	237
2.7.19	ST_OlapSlicerCacheSortOrder	238
2.7.20	ST_TabularSlicerCacheSortOrder	239
2.7.21	ST_SlicerCacheCrossFilter	239
2.7.22	ST_TextHAlign	240
2.7.23	ST_TextVAlign	240
2.7.24	ST_TimelineStyleType	241
2.7.25	ST_CalcMemNumberFormat	242
2.7.26	ST_SXVCellType	243
2.7.27	ST_QuestionType	243
2.7.28	ST_QuestionFormat	244
2.7.29	ST_SurveyPosition	245
3	Structure Examples	247
3.1	Slicer	247
3.1.1	Slicer Cache Part	248
3.1.2	Slicer Part	249
4	Security Considerations	251
4.1	Security Considerations for Implementers	251
4.2	Index of Security Fields	251
5	Appendix A: Full XML Schema	252
5.1	http://schemas.microsoft.com/office/excel/2006/main Schema	252
5.2	http://schemas.microsoft.com/office/drawing/2010/slicer Schema	253
5.3	http://schemas.microsoft.com/office/spreadsheetml/2010/11/main Schema	253
5.4	http://schemas.microsoft.com/office/spreadsheetml/2009/9/main Schema	262
5.5	http://schemas.microsoft.com/office/spreadsheetml/2009/9/ac Schema	278
5.6	http://schemas.microsoft.com/office/spreadsheetml/2011/1/ac Schema	278
5.7	http://schemas.microsoft.com/office/drawing/2012/timeslicer Schema	278
5.8	http://schemas.microsoft.com/office/excel/2010/spreadsheetDrawing Schema	279
5.9	http://schemas.microsoft.com/office/spreadsheetml/2010/11/ac Schema	279
5.10	http://schemas.openxmlformats.org/spreadsheetml/2006/main Schema	280
6	Appendix B: Product Behavior	281
7	Change Tracking	290
8	Index	292

1 Introduction

The Excel (.xlsx) Extensions to the Office Open XML SpreadsheetML File Format specifies extensions to the Office Open XML file formats described in [\[ISO/IEC29500-1:2011\]](#). The extensions are specified using conventions provided by the Office Open XML file formats described in [\[ISO/IEC29500-3:2011\]](#). The extensions are a collection of structures and parts in a container that specify appropriate content, which can include unstructured or semi-structured tables of numbers, text, or both numbers and text, equations or functions, external **data connections (2)**, charts, and images. Content in such a container is typically organized in a grid-based layout, and often includes numeric data, structured data, and formulas.

Sections 1.7 and 2 of this specification are normative and contain RFC 2119 language. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

- attribute**
- Augmented Backus-Naur Form (ABNF)**
- credential**
- GUID**
- salt**
- Unicode**
- unique identifier (UID)**
- XML**
- XML namespace**

The following terms are defined in [\[MS-OFCGLOS\]](#):

- add-in**
- Boolean**
- calculate**
- cell**
- cell reference**
- cell value**
- character set**
- color scale**
- column**
- condition**
- conditional formatting**
- control**
- cube function**
- custom filter**
- custom list**
- data bar**
- data connection**
- data marker**
- data point**
- data provider**
- data source**
- data table**
- data validation**
- defined name**
- descendant**

dimension
display folder
drillthrough
English Metric Unit (EMU)
field
filter
formula
hash
hidden
hierarchy
icon
icon set
Input Method Editor (IME)
left-to-right
locale
locked
MDX unique name
measure
multidimensional expression (MDX)
Object Linking and Embedding (OLE)
OLAP
OLAP All level
OLAP All member
OLAP allocation
OLAP hierarchy
OLAP level
OLAP measure
OLAP member
OLAP named set
OLAP subselect
OLAP tuple
OLAP weight expression
OLE DB
PivotTable
PivotTable field list
pixel
plot area
point
protection
query table
range
right-to-left
root element
row
security descriptor
selected
shape
sheet
sort
sort condition
sort order
source data
sparkline
spreadsheet data model
table

workbook
worksheet
XML schema definition (XSD)
XOR obfuscation
zoom level

The following terms are specific to this document:

future function: A function that can be written to but is not implemented in a file.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[CSS-Level2-2009] Bos, B., Celik, T., Hickson, I., and Wium Lie, H., Eds., "Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification", W3C Candidate Recommendation 08 September 2009, <http://www.w3.org/TR/2009/CR-CSS2-20090908/>

[ISO/IEC29500:2011] ISO/IEC, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Parts 1-4", ISO/IEC 29500-1:2011, 2011, http://www.iso.org/iso/catalogue/catalogue_tc/catalogue_detail.htm?csnumber=59575

[ISO/IEC29500-1:2011] ISO/IEC, "Information Technology -- Document description and processing languages -- Office Open XML File Formats -- Part 1: Fundamentals and Markup Language Reference", ISO/IEC 29500-1:2011, 2011, http://www.iso.org/iso/catalogue/catalogue_tc/catalogue_detail.htm?csnumber=59575

[ISO/IEC-29500-1] International Organization for Standardization, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 1: Fundamentals and Markup Language Reference", ISO/IEC 29500-1:2008, http://www.iso.org/iso/catalogue/catalogue_tc/catalogue_detail.htm?csnumber=51463

[ISO/IEC29500-3:2011] ISO/IEC, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 3: Markup Compatibility and Extensibility", ISO/IEC 29500-3:2011, 2011, http://www.iso.org/iso/catalogue/catalogue_tc/catalogue_detail.htm?csnumber=59577

[ISO/IEC29500-4:2011] ISO/IEC, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 4: Transitional Migration Features", ISO/IEC 29500-4:2011, 2011, http://www.iso.org/iso/home/store/catalogue_ics/catalogue_detail_ics.htm?csnumber=59578

[MS-ODRAWXML] Microsoft Corporation, "[Office Drawing Extensions to Office Open XML Structure Specification](#)".

- [MS-OFFCRYPTO] Microsoft Corporation, "[Office Document Cryptography Structure](#)".
- [MS-OWEXML] Microsoft Corporation, "[Office Web Extensibility Extensions to Office Open XML Structure Specification](#)".
- [MS-XLDM] Microsoft Corporation, "[Spreadsheet Data Model File Format](#)".
- [MS-XLSB] Microsoft Corporation, "[Excel Binary File Format \(.xlsb\) Structure Specification](#)".
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>
- [RFC3066] Alvestrand, H., "Tags for the Identification of Language", RFC 3066, January 2001, <http://www.ietf.org/rfc/rfc3066.txt>
- [RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>
- [UNICODE5.1] The Unicode Consortium, "The Unicode Standard, Version 5.1.0, defined by: The Unicode Standard, Version 5.0 (Boston, MA, Addison-Wesley, 2007. ISBN 0-321-48091-0), as amended by Unicode 5.1.0", <http://www.unicode.org/versions/Unicode5.1.0/>
- [W3C-XML] Bray, T., Paoli, J., Sperberg-McQueen, C.M., Maler, E., Yergeau, F., Eds., "Extensible Markup Language (XML) 1.1 (Second Edition)", W3C Recommendation, August 2006, <http://www.w3.org/TR/2006/REC-xml11-20060816/>
- [XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>
- [XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>
- [XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

- [ISO/IEC29500-2:2011] ISO/IEC, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 2: Open Packaging Conventions", ISO/IEC 29500-2:2011, 2011, http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=59576
- [MS-AZOD] Microsoft Corporation, "[Authorization Protocols Overview](#)".
- [MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".
- [MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

1.3 Structure Overview (Synopsis)

This document specifies spreadsheet-related extensions to Office Open XML file formats as described in [\[ISO/IEC29500-1:2011\]](#). **Workbook** data is contained in a ZIP package conforming to the Open Packaging Conventions as described in [\[ISO/IEC29500-2:2011\]](#). Individual files stored in the ZIP package, called parts [\[ISO/IEC29500-1:2011\]](#), contain information about the content and structure of a workbook, including workbook data, such as **worksheet** definitions. Some parts [\[ISO/IEC29500-1:2011\]](#) store information by using **XML** and other parts [\[ISO/IEC29500-1:2011\]](#)

store information by using binary data. The extensions specified in this document use the conventions specified by [\[ISO/IEC29500-3:2011\]](#), and they are both structures within parts specified by [\[ISO/IEC29500-1:2011\]](#) and extension parts within the package described by [\[ISO/IEC29500-2:2011\]](#).

1.4 Relationship to Protocols and Other Structures

This file format is a specified set of extensions to Office Open XML SpreadsheetML, specified in [\[ISO/IEC29500-1:2011\]](#). This specification is dependent on the structures and concepts defined in the following references:

- [\[ISO/IEC29500-1:2011\]](#) for baseline SpreadsheetML persistence format.
- [\[ISO/IEC29500-2:2011\]](#) for open packaging conventions.
- [\[ISO/IEC29500-3:2011\]](#) for markup compatibility and extensibility.
- [\[ISO/IEC29500-4:2011\]](#) for backward compatibility considerations.
- [\[MS-OFFCRYPTO\]](#) for the persistence format for document signing, information rights management, document encryption, and obfuscation.
- [\[MS-ODRAWXML\]](#) for the persistence format for **shapes**.

1.5 Applicability Statement

This document specifies a persistence format for extensions to Office Open XML file formats as described in [\[ISO/IEC29500-1:2011\]](#) SpreadsheetML documents. The extensions specified in this document allow for expressing additional content and properties, and are not applicable as a stand-alone file format. Each structure specified in this document is integrated with SpreadsheetML documents as described in [\[ISO/IEC29500-1:2011\]](#) in a particular way, as specified in the section for that structure. All structures are integrated into SpreadsheetML documents in such a way that maintains compatibility with implementations of the Office Open XML file formats as described in [\[ISO/IEC29500-1:2011\]](#).

The extensions specified in this document do not require any other extensions to be used, and do not prohibit any other extensions from being used in the same document.

This persistence format provides interoperability with applications that create or read documents conforming to this structure.

1.6 Versioning and Localization

This document covers versioning issues in the following areas:

- **Structure Versions:** There is only one version of Excel Extensions to the Office Open XML SpreadsheetML File Format.
- **Localization:** The [CT_ProtectedRange](#) structure contains **fields (1)** that specify locale-dependent meaning.

The [Security Considerations](#) section also specifies processes and data that are locale-dependent. See each structure and section description for more information.

1.7 Vendor-Extensible Fields

Specified in this document are extensions, using conventions described in [\[ISO/IEC29500-3:2011\]](#), both as structures within parts described in [\[ISO/IEC29500-1:2011\]](#) and as extension parts within the package described in [\[ISO/IEC29500-2:2011\]](#). Implementations are not required to preserve or remove additional parts when modifying an existing document. See [\[ISO/IEC29500-3:2011\]](#) for more information.

2 Structures

In the following sections, the schema definition might be less restrictive than the processing rules imposed by the application. The XSD in this specification provides a base description of the file format. The text that introduces the XSD specifies additional restrictions that reflect actual Microsoft product behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the application as specified restricts the same elements to being non-empty, not null, and present.

2.1 Part Enumerations

This section specifies parts in this file format that extend Office Open XML file formats as specified in [\[ISO/IEC29500-1:2011\]](#).

2.1.1 Control Properties

Content type: application/vnd.ms-excel.controlproperties+xml

Source relationship:

<http://schemas.openxmlformats.org/officeDocument/2006/relationships/ctrlProp>

An instance of this part type specifies the properties of a form **control** embedded object in the package. A package can contain one or more control properties parts, and each part **MUST** be the target of an explicit relationship from a SpreadsheetML control, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.3.1.19.

If this relationship is present, the control **MUST NOT** have a relationship with an embedded control persistence part, as specified in [\[ISO/IEC29500-1:2011\]](#) section 15.2.9.

The syntax of the structures contained in this part uses **XML schema definition (XSD)**, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

This specification defines and references various **XML namespaces** by using the mechanisms specified in [\[XMLNS\]](#).

The content of this part is XML, and the **root element** for the part is the **formControlPr** element, as specified in section [2.4.34](#).

2.1.2 Custom Data

Content type: application/binary

Source relationship:

<http://schemas.openxmlformats.org/officeDocument/2006/relationships/customData>

An instance of this part type specifies user-defined binary data.

A package **MUST** contain at most one custom data part per custom data properties part, as specified in section [2.1.3](#), and that part **MUST** be the target of an implicit relationship from a custom data properties part.

A custom data part **MUST NOT** have any implicit or explicit relationships to any other part specified by this protocol.

The content of this part consists of user-defined binary data that is stored on behalf of **add-ins**. The content is not specified in this protocol.

2.1.3 Custom Data Properties

Content type: application/vnd.openxmlformats-officedocument.customDataProperties+xml

Source relationship:

<http://schemas.openxmlformats.org/officeDocument/2006/relationships/customDataProps>

An instance of this part type specifies a single custom data properties part. This part specifies properties for the associated custom data part, as specified in section [2.1.2](#), specifically a **unique identifier (UID)** for the data storage.

A custom data properties part **MUST** be the target of an implicit relationship from the workbook part, as specified in [\[ISO/IEC29500-1:2011\]](#) section 12.3.23.

A custom data properties part is permitted to contain implicit relationships to the custom data part specified in section [2.1.2](#).

The syntax of the structures contained in this part uses XSD, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

This specification defines and references various XML namespaces by using the mechanisms specified in [\[XMLNS\]](#).

The content of this part is XML, and the root element for the part is the **datastoreItem** element, as specified in section [2.4.35](#).

2.1.4 Slicer Cache

Content type: application/vnd.ms-excel.slicerCache+xml

Source relationship: <http://schemas.microsoft.com/office/2007/relationships/slicerCache>

An instance of this part type specifies a single slicer cache part, as specified in section [3.1.1](#), in the workbook.

A package **MUST** contain one slicer cache part per **CT_SlicerCache** element, as specified in section [2.6.14](#), in the workbook part, as specified in [\[ISO/IEC29500-1:2011\]](#) section 12.3.23, and that part **MUST** be the target of an explicit relationship from the workbook part.

A slicer cache part **MUST NOT** have implicit or explicit relationships to any part specified by this protocol.

The syntax of the structures contained in this part uses XSD, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

This specification defines and references various XML namespaces by using the mechanisms specified in [\[XMLNS\]](#).

The content of this part is XML, and the root element for the part is the **slicerCacheDefinition** element, as specified in section [2.4.38](#).

2.1.5 Slicers

Content type: application/vnd.ms-excel.slicer+xml

Source relationship: <http://schemas.microsoft.com/office/2007/relationships/slicer>

An instance of this part type specifies the slicer views, as specified in section [2.3.2.2](#), for a single worksheet.

The presence of a slicers part indicates that there is at least one slicer view on the associated worksheet, and that this part **MUST** be the target of an explicit relationship from the worksheet part, as specified in [\[ISO/IEC29500-1:2011\]](#) section 12.3.24.

A slicers part **MUST NOT** have implicit or explicit relationships to any part specified by this protocol.

The syntax of the structures contained in this part uses XSD, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

This specification defines and references various XML namespaces by using the mechanisms specified in [\[XMLNS\]](#).

The content of this part is XML, and the root element for the part is the **slicers** element, as specified in section [2.4.36](#).

2.1.6 Data Model

Content type: application/vnd.openxmlformats-officedocument.model+data

The presence of a model part indicates that there is a **spreadsheet data model** present in the workbook.

The content of this part is specified in [\[MS-XLDM\]](#). In addition, this specification is extended by the **Annotations** property on different objects. Unless otherwise specified, all extensions in an **Annotations** object are written as XML.

2.1.6.1 Command Annotations

The **Annotations** property of a command object describing a **measure** ([\[MS-XLDM\]](#) section 2.6.9) can be extended with the following optional properties:

Type: **MUST** be either "Implicit" or "Explicit". "Implicit" specifies that the measure was created in the field (1) list. "Explicit" specifies that the measure was created by the user specifying the definition of the measure.

Name: Specifies the name of the measure. **MUST** exist if **Type** is equal to "Implicit".

Table: Specifies the name of the source table for this measure. **MUST** exist if **Type** is equal to "Implicit".

Column: Specifies the name of the source field (1) for this measure. **MUST** exist if **Type** is equal to "Implicit".

Aggregation: Specifies the aggregation type of an implicit measure. If this attribute is present, **Type** **MUST** be equal to "Implicit". This value **MUST** have the following form:

AGGREGATION (TABLENAME . COLUMNNAME)

Where TABLENAME **MUST** be equal to **Table**, COLUMNNAME **MUST** be equal to **Column**, and the aggregation **MUST** be equal to one of the following:

Value	Meaning
SUM	The measure is the sum of the values in the source field (1) specified by Column .

Value	Meaning
MAX	This measure is the maximum value in the source field (1) specified by Column .
COUNTA	This measure is the count of values in the source field (1) specified by Column .
AVERAGE	This measure is the average of the values in the source field (1) specified by Column .
STDEV.S	This measure is the standard deviation of the values in the source field (1) specified by Column .
STDEV.P	This measure is the standard deviation of the values in the source field (1) specified by Column .
VAR.S	This measure is the variance in the values of the source field (1) specified by Column .
DISTINCTCOUNT	This measure is the count of unique values in the source field (1) specified by Column .

Application: Specifies the name of the application that created this measure. MUST exist if **Type** is equal to "Implicit"

2.1.6.2 DimensionAttribute Annotations

The **Annotations** property of a **DimensionAttribute** object describing a **column (2)** in a **DimensionTabularModel** ([\[MS-XLDM\]](#) section 2.6.6) can be extended with the following optional properties:

ShortColumnId: Specifies the identifier used to represent this column (2) in the command text when data is pushed to the model.

2.1.7 Timeline Cache

Content type: application/vnd.ms-excel.TimelineCache+xml

Source relationship: <http://schemas.microsoft.com/office/2010/relationships/TimelineCache>

An instance of this part type specifies a single **Timeline Cache** (section [2.3.5.1](#)) in the workbook.

A package MUST contain one **Timeline cache** part per **CT_TimelineCacheRef** element, as specified in section [2.6.99](#), in the workbook part, as specified in [\[ISO/IEC29500-1:2011\]](#) section 12.3.23, and that part MUST be the target of an explicit relationship from the workbook part.

A **Timeline cache** part MUST NOT have implicit or explicit relationships to any part specified by this protocol.

The syntax of the structures contained in this part uses XSD, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

This specification defines and references various XML namespaces by using the mechanisms specified in [\[XMLNS\]](#).

The content of this part is XML, and the root element for the part is the **timelineCacheDefinition** element, as specified in section [2.4.58](#).

2.1.8 Timelines

Content type: application/vnd.ms-excel.Timeline+xml

Source relationship: <http://schemas.microsoft.com/office/2010/relationships/Timeline>

An instance of this part type specifies the [Timeline views](#) for a single worksheet.

The presence of a Timelines part indicates that there is at least one Timeline view on the associated worksheet, and that this part MUST be the target of an explicit relationship from the worksheet part, as specified in [\[ISO/IEC29500-1:2011\]](#) section 12.3.24.

A Timelines part MUST NOT have implicit or explicit relationships to any part specified by this protocol.

The syntax of the structures contained in this part uses XSD, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

This specification defines and references various XML namespaces by using the mechanisms specified in [\[XMLNS\]](#).

The content of this part is XML, and the root element for the part is the **timelines** element, as specified in section [2.4.57](#).

2.1.9 Survey

Content type: application/vnd.ms-excel.Survey+xml

Source relationship: <http://schemas.microsoft.com/office/2010/relationships/Survey>

The syntax of the structures contained in this part uses XSD, as specified in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

This specification defines and references various XML namespaces by using the mechanisms specified in [\[XMLNS\]](#).

The content of this part is XML, and the root element for the part is the **survey** element, as specified in section [2.4.70](#).

2.2 Extensions

Extensions are specified by using the conventions provided by Office Open XML file formats as specified in [\[ISO/IEC29500-3:2011\]](#). The following namespaces are utilized by the extensions specified in this document:

- "http://schemas.microsoft.com/office/drawingml/2010/slicer" [<1>](#)
- "http://schemas.microsoft.com/office/spreadsheetml/2009/9/main" [<2>](#)
- "http://schemas.microsoft.com/office/spreadsheetml/2009/9/ac" [<3>](#)
- "http://schemas.microsoft.com/office/excel/2006/main"
- "http://schemas.microsoft.com/office/spreadsheetml/2010/11/main" [<4>](#)
- "http://schemas.microsoft.com/office/drawing/2012/timeslicer" [<5>](#)

2.2.1 SpreadsheetML Extensibility Elements

When the global elements [f](#), [ref](#), or [sqref](#) are contained within an **ext** ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) element and contain **cell references**, an application can adjust these cell references when the worksheet layout changes, even when the containing **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) is not recognized by the application. See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more details about how extension lists are used.

2.2.2 Formulas

The following ABNF grammar is used by formulas in other parts of this document.

```
formula = expression

expression= ref-expression / *whitespace nospace-expression *whitespace
ref-expression= *whitespace ref-nospace-expression *whitespace
nospace-expression = "(" expression ")" / constant / prefix-operator expression /
expression infix-operator expression / expression postfix-operator / function-call
ref-nospace-expression = "(" ref-expression ")" / ref-constant / ref-expression ref-infix-
operator ref-expression / cell-reference / ref-function-call / name-reference / structure-
reference
constant = error-constant / logical-constant / numerical-constant / string-constant / array-
constant
ref-constant = "#REF!"
error-constant = ref-constant / "#DIV/0!" / "#N/A" / "#NAME?" / "#NULL!" / "#NUM!" /
"#VALUE!" / "#GETTING_DATA"
logical-constant = "FALSE" / "TRUE"
numerical-constant = [neg-sign] significand-part [exponent-part]
significand-part = whole-number-part [fractional-part] / fractional-part
whole-number-part = digit-sequence
fractional-part = full-stop digit-sequence
exponent-part = exponent-character [ sign ] digit-sequence
full-stop = "."
sign = "+" / neg-sign
neg-sign = "-"
exponent-character = "E"
digit-sequence = 1*decimal-digit
decimal-digit= %x30-39
nonzero-decimal-digit = %x31-39
string-constant = double-quote [string-chars] double-quote
string-chars = string-char *string-char
string-char = escaped-double-quote / character ; MUST NOT be a double-quote
escaped-double-quote = 2double-quote
double-quote = %x22
;character = as defined by the production Char in the [W3C-XML] section 2.2
array-constant = "{" constant-list-rows "}"
constant-list-rows = constant-list-row *(semicolon constant-list-row)
semicolon = ";"
constant-list-row = constant *(comma constant)
;An array-constant MUST NOT contain an array-constant or columns of unequal length or rows of
unequal length.
operator = ":" / comma / space / "^" / "*" / "/" / "+" / "-" / "&" / "=" / "<>" / "<" / "<="
/ ">" / ">=" / "%"
infix-operator = ref-infix-operator / value-infix-operator
value-infix-operator = "^" / "*" / "/" / "+" / "-" / "&" / "=" / "<>" / "<" / "<=" / ">" /
">="
ref-infix-operator = range-operator / union-operator / intersection-operator
union-operator = comma
intersection-operator = space
```

```

range-operator = ":"
postfix-operator = "%"
prefix-operator = "+" / "-"
cell-reference = external-cell-reference / local-cell-reference
local-cell-reference = A1-reference
external-cell-reference = bang-reference / sheet-range-reference / single-sheet-reference
book-prefix = workbook-index "!"
bang-reference = "!" (A1-reference / "#REF!")
sheet-range-reference = sheet-range "!" A1-reference
single-sheet-prefix = single-sheet "!"
single-sheet-reference = single-sheet-prefix (A1-reference / "#REF!")
single-sheet-area = single-sheet-prefix A1-area
single-sheet = [workbook-index] sheet-name / apostrophe [workbook-index] sheet-name-special
apostrophe = "'"
sheet-range = [workbook-index] sheet-name ":" sheet-name / apostrophe [workbook-index] sheet-
name-special ":" sheet-name-special apostrophe
workbook-index = "[" whole-number-part "]"
sheet-name = sheet-name-characters
sheet-name-characters = 1*sheet-name-character
sheet-name-character = character ; MUST NOT be an operator, ', [, ], \, or ?
apostrophe = "'"
space = " "
whitespace = space / %x0D %x0A
sheet-name-special = sheet-name-base-character [*sheet-name-character-special sheet-name-
base-character]
sheet-name-character-special = 2apostrophe / sheet-name-base-character
sheet-name-base-character = character ; MUST NOT be ', *, [, ], \, :, /, ?, or Unicode
character 'END OF TEXT'
A1-reference = (A1-column ":" A1-column) / (A1-row ":" A1-row) / A1-cell / A1-area
A1-cell = A1-column A1-row
A1-area = A1-cell ":" A1-cell
A1-column = A1-relative-column / A1-absolute-column
A1-relative-column = 1*2letter / A-to-W 2letter / "X" A-to-E letter / "XF" A-to-D
A-to-D = %x41-44 / %x61-64
A-to-E = A-to-D / "E"
A-to-W = %x41-57 / %x61-77
letter = %x41-5A / %x61-7A
A1-absolute-column = "$" A1-relative-column
A1-row = A1-relative-row / A1-absolute-row
A1-relative-row = row-digit-sequence
row-digit-sequence = nonzero-decimal-digit *5decimal-digit / "10" %x30-33 4decimal-digit /
"104" %x30-37 3decimal-digit / "1048" %x30-34 2decimal-digit / "10485" %x30-36 decimal-digit
/ "104857" %x30-36
A1-absolute-row = "$" A1-relative-row
cell-function-call = A1-cell "(" argument-list ")"
user-defined-function-call = user-defined-function-name "(" argument-list ")"
user-defined-function-name = name-reference
argument-list = argument *253(comma argument)
comma = ","
argument = *whitespace [argument-expression]
argument-expression = ref-argument-expression / *whitespace nospace-argument-expression
*whitespace
ref-argument-expression = *whitespace ref-argument-nospace-expression *whitespace
nospace-argument-expression = "(" expression ")" / constant / prefix-operator argument-
expression / argument-expression argument-infix-operator argument-expression / argument-
expression postfix-operator / function-call
ref-argument-nospace-expression = "(" ref-expression ")" / ref-constant / ref-argument-
expression ref-argument-infix-operator ref-argument-expression / cell-reference / ref-
function-call / name-reference / structure-reference
argument-infix-operator = ref-argument-infix-operator / value-infix-operator

```

```

ref-argument-infix-operator = range-operator / intersection-operator
unicode-digit = (any code points which are digits as defined by the Unicode character
properties, [UNICODE5.1] chapter 4)
R1C1-cell-reference = R1C1-row / R1C1-column / R1C1-row R1C1-column / R1C1-column R1C1-row
R1C1-row = "R" row-number

R1C1-column = "C" column-number
column-number = 1-16384
; A string composed of unicode-digits that represents an unsigned integer that is greater
than or equal to 1 and less than or equal to 16384

row-number = 1-1048576
; A string composed of unicode-digits that represents an unsigned integer that is greater
than or equal to 1 and less than or equal to 1048576.

name-reference = name / external-name
external-name = bang-name / (single-sheet-prefix / book-prefix ) name
bang-name = "!" name
name = name-start-character [ name-characters ]
name-start-character = underscore / backslash / letter / name-base-character
underscore = "_"
backslash = "\"
name-base-character = (any code points which are characters as defined by the Unicode
character properties, [UNICODE5.1] chapter 4 ; MUST NOT be 0x0-0x7F)
name-characters= 1*name-character
name-character = name-start-character / decimal-digit / full-stop / questionmark
questionmark = "?"
;A name MUST NOT have any of the following forms:
;TRUE or FALSE
;cell-reference
;function-list
;command-list
;future-function-list
;R1C1-cell-reference

structure-reference = [table-identifier] intra-table-reference
table-identifier = [book-prefix] table-name
table-name = name
;table-name is the name of the table the structure reference refers to. If it is missing, the
formula containing the structure reference MUST be entered into a cell which belongs to a
table and that table's name is used as the table-name. table-name MUST be the value of the
displayName attribute of some table element ([ISO/IEC29500-1:2011] section 18.5.1.2). It MUST
NOT be any other user-defined name.
intra-table-reference = spaced-lbracket inner-reference spaced-rbracket / keyword / ("["
[ simple-column-name ] "]" )
inner-reference = keyword-list / ([keyword-list spaced-comma] column-range)
keyword = "[#All]" / "[#Data]" / "[#Headers]" / "[#Totals]" / "[#This Row]"
keyword-list = keyword / ("[#Headers]" spaced-comma "[#Data]") / ("[#Data]" spaced-comma
"[#Totals]")
column-range = column [":" column]
column = simple-column-name / ("[" *space simple-column-name *space "]" )
simple-column-name = [any-nospace-column-character *any-column-character] any-nospace-column-
character
escape-column-character = tick / "[" / "]" / "#"
tick = %x27
unescaped-column-character = character ; MUST NOT match escape-column-character or space
any-column-character = any-nospace-column-character / space
any-nospace-column-character = unescaped-column-character / (tick escape-column-character)
spaced-comma = [space] comma [space]

```



```

spaced-lbracket = "[" [space]
spaced-rbracket = [space] "]"
function-list = "ABS" / "ABSREF" / "ACCRINT" / "ACCRINTM" / "ACOS" / "ACOSH" / "ACTIVE.CELL"
/ "ADD.BAR" / "ADD.COMMAND" / "ADD.MENU" / "ADD.TOOLBAR" / "ADDRESS" / "AMORDEGRC" /
"AMORLINC" / "AND" / "APP.TITLE" / "AREAS" / "ARGUMENT" / "ASC" / "ASIN" / "ASINH" / "ATAN" /
"ATAN2" / "ATANH" / "AVEDEV" / "AVERAGE" / "AVERAGEA" / "AVERAGEIF" / "AVERAGEIFS" /
"BAHTTEXT" / "BESSELI" / "BESSELJ" / "BESSELK" / "BESSELY" / "BETADIST" / "BETAINV" /
"BIN2DEC" / "BIN2HEX" / "BIN2OCT" / "BINOMDIST" / "BREAK" / "CALL" / "CALLER" / "CANCEL.KEY"
/ "CEILING" / "CELL" / "CHAR" / "CHECK.COMMAND" / "CHIDIST" / "CHIINV" / "CHITEST" / "CHOOSE"
/ "CLEAN" / "CODE" / "COLUMN" / "COLUMNS" / "COMBIN" / "COMPLEX" / "CONCATENATE" /
"CONFIDENCE" / "CONVERT" / "CORREL" / "COS" / "COSH" / "COUNT" / "COUNTA" / "COUNTBLANK" /
"COUNTIF" / "COUNTIFS" / "COUPDAYBS" / "COUPDAYS" / "COUPDAYSNC" / "COUPNCD" / "COUPNUM" /
"COUPPCD" / "COVAR" / "CREATE.OBJECT" / "CRITBINOM" / "CUBEKPIMEMBER" / "CUBEMEMBER" /
"CUBEMEMBERPROPERTY" / "CUBERANKEDMEMBER" / "CUBESET" / "CUBESETCOUNT" / "CUBEVALUE" /
"CUMIPMT" / "CUMPRINC" / "CUSTOM.REPEAT" / "CUSTOM.UNDO" / "DATE" / "DATEDIF" / "DATESTRING"
/ "DATEVALUE" / "DAVERAGE" / "DAY" / "DAYS360" / "DB" / "DBCS" / "DCOUNT" / "DCOUNTA" / "DDB"
/ "DEC2BIN" / "DEC2HEX" / "DEC2OCT" / "DEGREES" / "DELETE.BAR" / "DELETE.COMMAND" /
"DELETE.MENU" / "DELETE.TOOLBAR" / "DELTA" / "DEREF" / "DEVSQ" / "DGET" / "DIALOG.BOX" /
"DIRECTORY" / "DISC" / "DMAX" / "DMIN" / "DOCUMENTS" / "DOLLAR" / "DOLLARDE" / "DOLLARFR" /
"DPRODUCT" / "DSTDEV" / "DSTDEVP" / "DSUM" / "DURATION" / "DVAR" / "DVARP" / "ECHO" / "EDATE"
/ "EFFECT" / "ELSE" / "ELSE.IF" / "ENABLE.COMMAND" / "ENABLE.TOOL" / "END.IF" / "EOMONTH" /
"ERF" / "ERFC" / "ERROR" / "ERROR.TYPE" / "EVALUATE" / "EVEN" / "EXACT" / "EXEC" / "EXECUTE"
/ "EXP" / "EXPONDIST" / "FACT" / "FACTDOUBLE" / "FALSE" / "FCLOSE" / "FDIST" / "FILES" /
"FIND" / "FINDB" / "FINV" / "FISHER" / "FISHERINV" / "FIXED" / "FLOOR" / "FOPEN" / "FOR" /
"FOR.CELL" / "FORECAST" / "FORMULA.CONVERT" / "FPOS" / "FREAD" / "FREADLN" / "FREQUENCY" /
"FSIZE" / "FTEST" / "FV" / "FVSCHEDULE" / "FWRITE" / "FWRITELN" / "GAMMADIST" / "GAMMAINV" /
"GAMMALN" / "GCD" / "GEOMEAN" / "GESTEP" / "GET.BAR" / "GET.CELL" / "GET.CHART.ITEM" /
"GET.DEF" / "GET.DOCUMENT" / "GET.FIELD" / "GET.FORMULA" / "GET.ITEM" / "GET.LINK.INFO" /
"GET.MOVIE" / "GET.NAME" / "GET.NOTE" / "GET.OBJECT" / "GET.TOOL" / "GET.TOOLBAR" /
"GET.VIEW" / "GET.WINDOW" / "GET.WORKBOOK" / "GET.WORKSPACE" / "GETPIVOTDATA" / "GOTO" /
"GROUP" / "GROWTH" / "HALT" / "HARMEAN" / "HELP" / "HEX2BIN" / "HEX2DEC" / "HEX2OCT" /
"HLOOKUP" / "HOUR" / "HYPERLINK" / "HYPGEOMDIST" / "IF" / "IFERROR" / "IMABS" / "IMAGINARY" /
"IMARGUMENT" / "IMCONJUGATE" / "IMCOS" / "IMDIV" / "IMEXP" / "IMLN" / "IMLOG10" / "IMLOG2" /
"IMPOWER" / "IMPRODUCT" / "IMREAL" / "IMSIN" / "IMSQRT" / "IMSUB" / "IMSUM" / "INDEX" /
"INDIRECT" / "INFO" / "INITIATE" / "INPUT" / "INT" / "INTERCEPT" / "INTRATE" / "IPMT" / "IRR"
/ "ISBLANK" / "ISERR" / "ISERROR" / "ISEVEN" / "ISLOGICAL" / "ISNA" / "ISNONTEXT" /
"ISNUMBER" / "ISODD" / "ISPMT" / "ISREF" / "ISTEXT" / "ISTHAIDIGIT" / "KURT" / "LARGE" /
"LAST.ERROR" / "LCM" / "LEFT" / "LEFTB" / "LEN" / "LENB" / "LINEST" / "LINKS" / "LN" / "LOG"
/ "LOG10" / "LOGEST" / "LOGINV" / "LOGNORMDIST" / "LOOKUP" / "LOWER" / "MATCH" / "MAX" /
"MAXA" / "MDTERM" / "MDURATION" / "MEDIAN" / "MID" / "MIDB" / "MIN" / "MINA" / "MINUTE" /
"MINVERSE" / "MIRR" / "MMULT" / "MOD" / "MODE" / "MONTH" / "MOVIE.COMMAND" / "MROUND" /
"MULTINOMIAL" / "N" / "NA" / "NAMES" / "NEGBINOMDIST" / "NETWORKDAYS" / "NEXT" / "NOMINAL" /
"NORMDIST" / "NORMINV" / "NORMSDIST" / "NORMSINV" / "NOT" / "NOTE" / "NOW" / "NPER" / "NPV" /
"NUMBERSTRING" / "OCT2BIN" / "OCT2DEC" / "OCT2HEX" / "ODD" / "ODDFPRICE" / "ODDFYIELD" /
"ODDLPRICE" / "ODDLYIELD" / "OFFSET" / "OPEN.DIALOG" / "OPTIONS.LISTS.GET" / "OR" / "PAUSE" /
"PEARSON" / "PERCENTILE" / "PERCENTRANK" / "PERMUT" / "PHONETIC" / "PI" / "PMT" / "POISSON" /
"POKE" / "POWER" / "PPMT" / "PRESS.TOOL" / "PRICE" / "PRICEDISC" / "PRICEMAT" / "PROB" /
"PRODUCT" / "PROPER" / "PV" / "QUARTILE" / "QUOTIENT" / "RADIANS" / "RAND" / "RANDBETWEEN" /
"RANK" / "RATE" / "RECEIVED" / "REFTEXT" / "REGISTER" / "REGISTER.ID" / "RELRIF" /
"RENAME.COMMAND" / "REPLACE" / "REPLACEB" / "REPT" / "REQUEST" / "RESET.TOOLBAR" / "RESTART"
/ "RESULT" / "RESUME" / "RETURN" / "RIGHT" / "RIGHTB" / "ROMAN" / "ROUND" / "ROUNDBAHTDOWN" /
"ROUNDBAHTUP" / "ROUNDDOWN" / "ROUNDUP" / "ROW" / "ROWS" / "RSQ" / "RTD" / "SAVE.DIALOG" /
"SAVE.TOOLBAR" / "SCENARIO.GET" / "SEARCH" / "SEARCHB" / "SECOND" / "SELECTION" / "SERIES" /
"SERIESSUM" / "SET.NAME" / "SET.VALUE" / "SHOW.BAR" / "SIGN" / "SIN" / "SINH" / "SKEW" /
"SLN" / "SLOPE" / "SMALL" / "SPELLING.CHECK" / "SPREADBASE.DATA.FIELD" / "SQRT" / "SQRTPI" /
"STANDARDIZE" / "STDEV" / "STDEVA" / "STDEVP" / "STDEVPA" / "STEP" / "STEYX" / "SUBSTITUTE" /
"SUBTOTAL" / "SUM" / "SUMIF" / "SUMIFS" / "SUMPRODUCT" / "SUMSQ" / "SUMX2MY2" / "SUMX2PY2" /
"SUMXMY2" / "SYD" / "T" / "TAN" / "TANH" / "TBILLEQ" / "TBILLPRICE" / "TBILLYIELD" / "TDIST"
/ "TERMINATE" / "TEXT" / "TEXT.BOX" / "TEXTREF" / "THAIDAYOFWEEK" / "THAIDIGIT" /
"THAIMONTHOFYEAR" / "THAINUMSOUND" / "THAINUMSTRING" / "THAISTRINGLENGTH" / "THAIYEAR" /
"TIME" / "TIMEVALUE" / "TINV" / "TODAY" / "TRANPOSE" / "TREND" / "TRIM" / "TRIMMEAN" /
"TRUE" / "TRUNC" / "TTEST" / "TYPE" / "UNREGISTER" / "UPPER" / "USDOLLAR" / "VALUE" / "VAR" /
"VARA" / "VARP" / "VARPA" / "VDB" / "VIEW.GET" / "VLOOKUP" / "VOLATILE" / "WEEKDAY" /
"WEEKNUM" / "WEIBULL" / "WHILE" / "WINDOW.TITLE" / "WINDOWS" / "WORKDAY" / "XIRR" / "XNPV" /
"YEAR" / "YEARFRAC" / "YIELD" / "YIELDDISC" / "YIELDMAT" / "ZTEST"

```

command-list = ("A1.R1C1" / "ACTIVATE" / "ACTIVATE.NEXT" / "ACTIVATE.NOTES" / "ACTIVATE.PREV"
/ "ACTIVE.CELL.FONT" / "ADD.ARROW" / "ADD.CHART.AUTOFORMAT" / "ADD.LIST.ITEM" / "ADD.OVERLAY"
/ "ADD.PRINT.AREA" / "ADD.TOOL" / "ADDIN.MANAGER" / "ALERT" / "ALIGNMENT" / "APP.ACTIVATE" /
"APP.ACTIVATE.MICROSOFT" / "APP.MAXIMIZE" / "APP.MINIMIZE" / "APP.MOVE" / "APP.RESTORE" /
"APP.SIZE" / "APPLY.NAMES" / "APPLY.STYLE" / "ARRANGE.ALL" / "ASSIGN.TO.OBJECT" /
"ASSIGN.TO.TOOL" / "ATTACH.TEXT" / "ATTACH.TOOLBARS" / "ATTRIBUTES" / "AUTO.OUTLINE" /
"AUTOCORRECT" / "AXES" / "BEEP" / "BORDER" / "BRING.TO.FRONT" / "CALCULATE.DOCUMENT" /
"CALCULATE.NOW" / "CALCULATION" / "CANCEL.COPY" / "CELL.PROTECTION" / "CHANGE.LINK" /
"CHART.ADD.DATA" / "CHART.TREND" / "CHART.WIZARD" / "CHECKBOX.PROPERTIES" / "CLEAR" /
"CLEAR.OUTLINE" / "CLEAR.PRINT.AREA" / "CLEAR.ROUTING.SLIP" / "CLOSE" / "CLOSE.ALL" /
"COLOR.PALETTE" / "COLUMN.WIDTH" / "COMBINATION" / "CONSOLIDATE" / "CONSTRAIN.NUMERIC" /
"COPY" / "COPY.CHART" / "COPY.PICTURE" / "COPY.TOOL" / "COPY" / "CREATE.NAMES" / "CREATE.PUBLISHER" /
"CUSTOMIZE.TOOLBAR" / "CUT" / "DATA.DELETE" / "DATA.FIND" / "DATA.FIND.NEXT" /
"DATA.FIND.PREV" / "DATA.FORM" / "DATA.LABEL" / "DATA.SERIES" / "DEFINE.NAME" /
"DEFINE.STYLE" / "DELETE.ARROW" / "DELETE.CHART.AUTOFORMAT" / "DELETE.FORMAT" / "DELETE.NAME"
/ "DELETE.NOTE" / "DELETE.OVERLAY" / "DELETE.STYLE" / "DELETE.TOOL" / "DEMOTE" /
"DISABLE.INPUT" / "DISPLAY" / "DUPLICATE" / "EDIT.COLOR" / "EDIT.DELETE" / "EDIT.OBJECT" /
"EDIT.REPEAT" / "EDIT.SERIES" / "EDIT.TOOL" / "EDITBOX.PROPERTIES" / "EDITION.OPTIONS" /
"ENABLE.OBJECT" / "ENABLE.TIPWIZARD" / "ENTER.DATA" / "ERRORBAR.X" / "ERRORBAR.Y" /
"EXTEND.POLYGON" / "EXTRACT" / "FILE.CLOSE" / "FILE.DELETE" / "FILL.AUTO" / "FILL.DOWN" /
"FILL.GROUP" / "FILL.LEFT" / "FILL.RIGHT" / "FILL.UP" / "FILTER" / "FILTER.ADVANCED" /
"FILTER.SHOW.ALL" / "FIND.FILE" / "FONT" / "FONT.PROPERTIES" / "FORMAT.AUTO" / "FORMAT.CHART"
/ "FORMAT.CHARTTYPE" / "FORMAT.FONT" / "FORMAT.LEGEND" / "FORMAT.MAIN" / "FORMAT.MOVE" /
"FORMAT.NUMBER" / "FORMAT.OVERLAY" / "FORMAT.SHAPE" / "FORMAT.SIZE" / "FORMAT.TEXT" /
"FORMULA" / "FORMULA.ARRAY" / "FORMULA.FILL" / "FORMULA.FIND" / "FORMULA.FIND.NEXT" /
"FORMULA.FIND.PREV" / "FORMULA.GOTO" / "FORMULA.REPLACE" / "FREEZE.PANES" / "FULL" /
"FULL.SCREEN" / "FUNCTION.WIZARD" / "GALLERY.3D.AREA" / "GALLERY.3D.BAR" /
"GALLERY.3D.COLUMN" / "GALLERY.3D.LINE" / "GALLERY.3D.PIE" / "GALLERY.3D.SURFACE" /
"GALLERY.AREA" / "GALLERY.BAR" / "GALLERY.COLUMN" / "GALLERY.CUSTOM" / "GALLERY.DOUGHNUT" /
"GALLERY.LINE" / "GALLERY.PIE" / "GALLERY.RADAR" / "GALLERY.SCATTER" / "GOAL.SEEK" /
"GRIDLINES" / "HIDE" / "HIDE.DIALOG" / "HIDE.OBJECT" / "HIDEALL.INKANNOTS" / "HIDEALL.NOTES"
/ "HIDECURR.NOTE" / "HLINE" / "HPAGE" / "HSCROLL" / "INSERT" / "INSERT.MAP.OBJECT" /
"INSERT.OBJECT" / "INSERT.PICTURE" / "INSERT.TITLE" / "INSERTDATATABLE" / "JUSTIFY" /
"LABEL.PROPERTIES" / "LAYOUT" / "LEGEND" / "LINE.PRINT" / "LINK.COMBO" / "LINK.FORMAT" /
"LIST.NAMES" / "LISTBOX.PROPERTIES" / "MACRO.OPTIONS" / "MAIL.ADD.MAILER" /
"MAIL.DELETE.MAILER" / "MAIL.EDIT.MAILER" / "MAIL.FORWARD" / "MAIL.LOGOFF" / "MAIL.LOGON" /
"MAIL.NEXT.LETTER" / "MAIL.REPLY" / "MAIL.REPLY.ALL" / "MAIL.SEND.MAILER" / "MAIN.CHART" /
"MAIN.CHART.TYPE" / "MENU.EDITOR" / "MERGE.STYLES" / "MESSAGE" / "MOVE.BRK" / "MOVE.TOOL" /
"MSCOCHECKS" / "NEW" / "NEW.WINDOW" / "NEWWEBQUERY" / "NORMAL" / "OBJECT.PROPERTIES" /
"OBJECT.PROTECTION" / "ON.DATA" / "ON.DOUBLECLICK" / "ON.ENTRY" / "ON.KEY" / "ON.RECALC" /
"ON.SHEET" / "ON.TIME" / "ON.WINDOW" / "OPEN" / "OPEN.LINKS" / "OPEN.MAIL" / "OPEN.TEXT" /
"OPTIONS.CALCULATION" / "OPTIONS.CHART" / "OPTIONS.EDIT" / "OPTIONS.GENERAL" /
"OPTIONS.LISTS.ADD" / "OPTIONS.LISTS.DELETE" / "OPTIONS.ME" / "OPTIONS.MENONO" /
"OPTIONS.SAVE" / "OPTIONS.SPELL" / "OPTIONS.TRANSITION" / "OPTIONS.VIEW" / "OUTLINE" /
"OVERLAY" / "OVERLAY.CHART.TYPE" / "PAGE.SETUP" / "PARSE" / "PASTE" / "PASTE.LINK" /
"PASTE.PICTURE" / "PASTE.PICTURE.LINK" / "PASTE.SPECIAL" / "PASTE.TOOL" / "PATTERNS" /
"PICKLIST" / "PIVOT.ADD.FIELDS" / "PIVOT.FIELD" / "PIVOT.FIELD.GROUP" /
"PIVOT.FIELD.PROPERTIES" / "PIVOT.FIELD.UNGROUP" / "PIVOT.ITEM" / "PIVOT.ITEM.PROPERTIES" /
"PIVOT.REFRESH" / "PIVOT.SHOW.PAGES" / "PIVOT.TABLE.CHART" / "PIVOT.TABLE.WIZARD" /
"POST.DOCUMENT" / "PRECISION" / "PREFERRED" / "PRINT" / "PRINT.PREVIEW" / "PRINTER.SETUP" /
"PROMOTE" / "PROTECT.DOCUMENT" / "PROTECT.REVISIONS" / "PUSHBUTTON.PROPERTIES" / "QUIT" /
"REMOVE.LIST.ITEM" / "REMOVE.PAGE.BREAK" / "RENAME.OBJECT" / "REPLACE.FONT" / "RESET.TOOL" /
"RM.PRINT.AREA" / "ROUTE.DOCUMENT" / "ROUTING.SLIP" / "ROW.HEIGHT" / "RUN" / "SAVE" /
"SAVE.AS" / "SAVE.COPY.AS" / "SAVE.NEW.OBJECT" / "SAVE.WORKBOOK" / "SAVE.WORKSPACE" / "SCALE"
/ "SCENARIO.ADD" / "SCENARIO.CELLS" / "SCENARIO.DELETE" / "SCENARIO.EDIT" / "SCENARIO.MERGE"
/ "SCENARIO.SHOW" / "SCENARIO.SHOW.NEXT" / "SCENARIO.SUMMARY" / "SCROLLBAR.PROPERTIES" /
"SELECT" / "SELECT.ALL" / "SELECT.CHART" / "SELECT.END" / "SELECT.LAST.CELL" /
"SELECT.LIST.ITEM" / "SELECT.PLOT.AREA" / "SELECT.SPECIAL" / "SEND.KEYS" / "SEND.MAIL" /
"SEND.TO.BACK" / "SERIES.AXES" / "SERIES.ORDER" / "SERIES.X" / "SERIES.Y" /
"SET.CONTROL.VALUE" / "SET.CRITERIA" / "SET.DATABASE" / "SET.DIALOG.DEFAULT" /
"SET.DIALOG.FOCUS" / "SET.EXTRACT" / "SET.LIST.ITEM" / "SET.PAGE.BREAK" / "SET.PREFERRED" /
"SET.PRINT.AREA" / "SET.PRINT.TITLES" / "SET.UPDATE.STATUS" / "SHARE" / "SHARE.NAME" /
"SHEET.BACKGROUND" / "SHORT.MENUS" / "SHOW.ACTIVE.CELL" / "SHOW.CLIPBOARD" / "SHOW.DETAIL" /
"SHOW.DIALOG" / "SHOW.INFO" / "SHOW.LEVELS" / "SHOW.TOOLBAR" / "SORT" / "SORT.SPECIAL" /
"SOUND.NOTE" / "SOUND.PLAY" / "SPELLING" / "SPLIT" / "STANDARD.FONT" / "STANDARD.WIDTH" /

"STYLE" / "SUBSCRIBE.TO" / "SUBTOTAL.CREATE" / "SUBTOTAL.REMOVE" / "SUMMARY.INFO" /
"TAB.ORDER" / "TABLE" / "TEXT.TO.COLUMN" / "TRACER.CLEAR" / "TRACER.DISPLAY" /
"TRACER.ERROR" / "TRACER.NAVIGATE" / "TRAVERSE.NOTES" / "UNDO" / "UNGROUP" / "UNGROUP.SHEETS"
/ "UNHIDE" / "UNLOCKED.NEXT" / "UNLOCKED.PREV" / "UNPROTECT.REVISIONS" / "UPDATE.LINK" /
"VBA.INSERT.FILE" / "VBA.MAKE.ADDIN" / "VBA.PROCEDURE.DEFINITION" / "VBAActivate" / "VIEW.3D"
/ "VIEW.DEFINE" / "VIEW.DELETE" / "VIEW.SHOW" / "VLIN" / "VPAGE" / "VSCROLL" / "WAIT" /
"WEB.PUBLISH" / "WINDOW.MAXIMIZE" / "WINDOW.MINIMIZE" / "WINDOW.MOVE" / "WINDOW.RESTORE" /
"WINDOW.SIZE" / "WORKBOOK.ACTIVATE" / "WORKBOOK.ADD" / "WORKBOOK.COPY" / "WORKBOOK.DELETE" /
"WORKBOOK.HIDE" / "WORKBOOK.INSERT" / "WORKBOOK.MOVE" / "WORKBOOK.NAME" / "WORKBOOK.NEW" /
"WORKBOOK.NEXT" / "WORKBOOK.OPTIONS" / "WORKBOOK.PREV" / "WORKBOOK.PROTECT" /
"WORKBOOK.SCROLL" / "WORKBOOK.SELECT" / "WORKBOOK.TAB.SPLIT" / "WORKBOOK.UNHIDE" /
"WORKGROUP" / "WORKGROUP.OPTIONS" / "WORKSPACE" / "ZOOM") ["?"]
future-function-list = ("_xlfn." ("AGGREGATE" / "ACOT" / "ACOTH" / "ARABIC" / "BASE" /
"BETA.DIST" / "BETA.INV" / "BINOM.DIST" / "BINOM.DIST.RANGE" / "BINOM.INV" / "BITAND" /
"BITLSHIFT" / "BITOR" / "BITRSHIFT" / "BITXOR" / "CEILING.MATH" / "CEILING.PRECISE" /
"CHISQ.DIST" / "CHISQ.DIST.RT" / "CHISQ.INV" / "CHISQ.INV.RT" / "CHISQ.TEST" / "COMBINA" /
"CONFIDENCE.NORM" / "CONFIDENCE.T" / "COT" / "COTH" / "COVARIANCE.P" / "COVARIANCE.S" / "CSC"
/ "CSCH" / "DAYS" / "DECIMAL" / "ERF.PRECISE" / "ERFC.PRECISE" / "EXPON.DIST" / "F.DIST" /
"F.DIST.RT" / "F.INV" / "F.INV.RT" / "F.TEST" / "FILTERXML" / "FLOOR.MATH" / "FLOOR.PRECISE"
/ "FORMULATEXT" / "GAMMA" / "GAMMA.DIST" / "GAMMA.INV" / "GAMMALN.PRECISE" / "GAUSS" /
"HYPGEOM.DIST" / "IFNA" / "IMCOSH" / "IMCOT" / "IMCSC" / "IMCSCH" / "IMSEC" / "IMSECH" /
"IMSINH" / "IMTAN" / "ISFORMULA" / "ISOWEENUM" / "LOGNORM.DIST" / "LOGNORM.INV" /
"MODE.MULT" / "MODE.SNGL" / "MUNIT" / "NEGBINOM.DIST" / "NORM.DIST" / "NORM.INV" /
"NORM.S.DIST" / "NORM.S.INV" / "NUMBERVALUE" / "PDURATION" / "PERCENTILE.EXC" /
"PERCENTILE.INC" / "PERCENTRANK.EXC" / "PERCENTRANK.INC" / "PERMUTATIONA" / "PHI" /
"POISSON.DIST" / "QUARTILE.EXC" / "QUARTILE.INC" / "QUERYSTRING" / "RANK.AVG" / "RANK.EQ" /
"RRI" / "SEC" / "SECH" / "SHEET" / "SHEETS" / "SKEW.P" / "STDEV.P" / "STDEV.S" / "T.DIST" /
"T.DIST.2T" / "T.DIST.RT" / "T.INV" / "T.INV.2T" / "T.TEST" / "UNICHAR" / "UNICODE" / "VAR.P"
/ "VAR.S" / "WEBSERVICE" / "WEIBULL.DIST" / "XOR" / "Z.TEST")) / "ECMA.CEILING" /
"ISO.CEILING" / "NETWORKDAYS.INTL" / "WORKDAY.INTL"
ref-function-call = "CHOOSE" choose-params / "IF" if-params / "INDEX" index-params /
"INDIRECT" indirect-params / "OFFSET" offset-params
future-function-call = ("_xlfn." (("ACOT" acot-params) / ("ACOTH" acoth-params) /
("AGGREGATE" aggregate-params) / ("ARABIC" arabic-params) / ("BASE" base-params) /
("BETA.DIST" beta-dist-params) / ("BETA.INV" beta-inv-params) / ("BINOM.DIST" binom-dist-
params) / ("BINOM.DIST.RANGE" binom-dist-range-params) / ("BINOM.INV" binom-inv-params) /
("BITAND" bitand-params) / ("BITLSHIFT" bitlshift-params) / ("BITOR" bitor-params) /
("BITRSHIFT" bitrshift-params) / ("BITXOR" bitxor-params) / ("CEILING.MATH" ceiling-math-
params) / ("CEILING.PRECISE" ceiling-precise-params) / ("CHISQ.DIST" chisq-dist-params) /
("CHISQ.DIST.RT" chisq-dist-rt-params) / ("CHISQ.INV" chisq-inv-params) / ("CHISQ.INV.RT"
chisq-inv-rt-params) / ("CHISQ.TEST" chisq-test-params) / ("COMBINA" combina-params) /
("CONFIDENCE.NORM" confidence-norm-params) / ("CONFIDENCE.T" confidence-t-params) / ("COT"
cot-params) / ("COTH" coth-params) / ("COVARIANCE.P" covariance-p-params) / ("COVARIANCE.S"
covariance-s-params) / ("CSC" csc-params) / ("CSCH" csch-params) / ("DAYS" days-params) /
("DECIMAL" decimal-params) / ("ERF.PRECISE" erf-precise-params) / ("ERFC.PRECISE" erfc-
precise-params) / ("EXPON.DIST" expon-dist-params) / ("F.DIST" f-dist-params) / ("F.DIST.RT"
f-dist-rt-params) / ("F.INV" f-inv-params) / ("F.INV.RT" f-inv-rt-params) / ("F.TEST" f-test-
params) / ("FILTERXML" filterxml-params) / ("FLOOR.MATH" floor-math-params) /
("FLOOR.PRECISE" floor-precise-params) / ("FORMULATEXT" formulatext-params) / ("GAMMA" gamma-
params) / ("GAMMA.DIST" gamma-dist-params) / ("GAMMA.INV" gamma-inv-params) /
("GAMMALN.PRECISE" gammaln-precise-params) / ("GAUSS" gauss-params) / ("HYPGEOM.DIST"
hypgeom-dist-params) / ("IFNA" ifna-params) / ("IMCOSH" imcosh-params) / ("IMCOT" imcot-
params) / ("IMCSC" imcsc-params) / ("IMCSCH" imcsch-params) / ("IMSEC" imsec-params) /
("IMSECH" imsech-params) / ("IMSINH" imsinh-params) / ("IMTAN" imtan-params) / ("ISFORMULA"
isformula-params) / ("ISOWEENUM" isoweeknum-params) / ("LOGNORM.DIST" lognorm-dist-params) /
("LOGNORM.INV" lognorm-inv-params) / ("MODE.MULT" mode-mult-params) / ("MODE.SNGL" mode-sngl-
params) / ("MUNIT" munit-params) / ("NEGBINOM.DIST" negbinom-dist-params) / ("NORM.DIST"
norm-dist-params) / ("NORM.INV" norm-inv-params) / ("NORM.S.DIST" norm-s-dist-params) /
("NORM.S.INV" norm-s-inv-params) / ("NUMBERVALUE" numbervalue-params) / ("PDURATION"
pduration-params) / ("PERCENTILE.EXC" percentile-exc-params) / ("PERCENTILE.INC" percentile-
inc-params) / ("PERCENTRANK.EXC" percentrank-exc-params) / ("PERCENTRANK.INC" percentrank-
inc-params) / ("PERMUTATIONA" permutatona-params) / ("PHI" phi-params) / ("POISSON.DIST"
poisson-dist-params) / ("QUARTILE.EXC" quartile-exc-params) / ("QUARTILE.INC" quartile-inc-
params) / ("QUERYSTRING" querystring-params) / ("RANK.AVG" rank-avg-params) / ("RANK.EQ"
rank-eg-params) / ("RRI" rri-params) / ("SEC" sec-params) / ("SECH" sech-params) / ("SHEET"
sheet-params) / ("SHEETS" sheets-params) / ("SKEW.P" skew-p-params) / ("STDEV.P" stdev-p-

params) / ("STDEV.S" stdev-s-params) / ("T.DIST" t-dist-params) / ("T.DIST.2T" t-dist-2t-params) / ("T.DIST.RT" t-dist-rt-params) / ("T.INV" t-inv-params) / ("T.INV.2T" t-inv-2t-params) / ("T.TEST" t-test-params) / ("UNICHAR" unichar-params) / ("UNICODE" unicode-params) / ("VAR.P" var-p-params) / ("VAR.S" var-s-params) / ("WEBSERVICE" webservice-params) / ("WEIBULL.DIST" weibull-dist-params) / ("XOR" xor-params) / ("Z.TEST" z-test-params))) / ("ECMA.CEILING" ecma-ceiling-params) / ("ISO.CEILING" iso-ceiling-params) / ("NETWORKDAYS.INTL" networkdays-intl-params) / ("WORKDAY.INTL" workday-intl-params) function-call = ref-function-call / future-function-call / cell-function-call / user-defined-function-call / "ABS" abs-params / "ACCRINT" accrint-params / "ACCRINTM" accrintm-params / "ACOS" acos-params / "ACOSH" acosh-params / "ADDRESS" address-params / "AMORDEGRC" amordegrc-params / "AMORLINC" amorlinc-params / "AND" and-params / "AREAS" areas-params / "ASC" asc-params / "ASIN" asin-params / "ASINH" asinh-params / "ATAN" atan-params / "ATAN2" atan2-params / "ATANH" atanh-params / "AVEDEV" aveDEV-params / "AVERAGE" average-params / "AVERAGEA" averagea-params / "AVERAGEIF" averageif-params / "AVERAGEIFS" averageifs-params / "BAHTTEXT" bahttext-params / "BESSELI" besseli-params / "BESSELJ" besselj-params / "BESSELK" besselk-params / "BESSELY" bessely-params / "BETADIST" betadist-params / "BETAINV" betainv-params / "BIN2DEC" bin2dec-params / "BIN2HEX" bin2hex-params / "BIN2OCT" bin2oct-params / "BINOMDIST" binomdist-params / "CEILING" ceiling-params / "CELL" cell-params / "CHAR" char-params / "CHIDIST" chidist-params / "CHIINV" chiinv-params / "CHITEST" chitest-params / "CLEAN" clean-params / "CODE" code-params / "COLUMN" column-params / "COLUMNS" columns-params / "COMBIN" combin-params / "COMPLEX" complex-params / "CONCATENATE" concatenate-params / "CONFIDENCE" confidence-params / "CONVERT" convert-params / "CORREL" correl-params / "COS" cos-params / "COSH" cosh-params / "COUNT" count-params / "COUNTA" counta-params / "COUNTBLANK" countblank-params / "COUNTIF" countif-params / "COUNTIFS" countifs-params / "COUPDAYBS" coupdaybs-params / "COUPDAYS" coupdays-params / "COUPDAYSNC" coupdaysnc-params / "COUPNCD" coupncd-params / "COUPNUM" coupnum-params / "COUPPCD" couppcd-params / "COVAR" covar-params / "CRITBINOM" critbinom-params / "CUBEKPIMEMBER" cubekpimember-params / "CUBEMEMBER" cubemember-params / "CUBEMEMBERPROPERTY" cubememberproperty-params / "CUBERANKEDMEMBER" cuberankedmember-params / "CUBESET" cubeset-params / "CUBESETCOUNT" cubesetcount-params / "CUBEVALUE" cubevalue-params / "CUMIPMT" cumipmt-params / "CUMPRINC" cumprinc-params / "DATE" date-params / "DATEDIF" datedif-params / "DATESTRING" datestring-params / "DATEVALUE" datevalue-params / "DAVERAGE" daverage-params / "DAY" day-params / "DAYS360" days360-params / "DB" db-params / "DBCS" dbcs-params / "DCOUNT" dcount-params / "DCOUNTA" dcounta-params / "DDB" ddb-params / "DEC2BIN" dec2bin-params / "DEC2HEX" dec2hex-params / "DEC2OCT" dec2oct-params / "DEGREES" degrees-params / "DELTA" delta-params / "DEVSQ" devsq-params / "DGET" dget-params / "DISC" disc-params / "DMAX" dmax-params / "DMIN" dmin-params / "DOLLAR" dollar-params / "DOLLARDE" dollarde-params / "DOLLARFR" dollarfr-params / "DPRODUCT" dproduct-params / "DSTDEV" dstdev-params / "DSTDEVP" dstdevp-params / "DSUM" dsum-params / "DURATION" duration-params / "DVAR" dvar-params / "DVARP" dvarp-params / "EDATE" edate-params / "EFFECT" effect-params / "EOMONTH" eomonth-params / "ERF" erf-params / "ERFC" erfc-params / "ERROR.TYPE" error-type-params / "EVEN" even-params / "EXACT" exact-params / "EXP" exp-params / "EXPONDIST" expondist-params / "FACT" fact-params / "FACTDOUBLE" factdouble-params / "FALSE" false-params / "FDIST" fdist-params / "FIND" find-params / "FINDB" findb-params / "FINV" finv-params / "FISHER" fisher-params / "FISHERINV" fisherinv-params / "FIXED" fixed-params / "FLOOR" floor-params / "FORECAST" forecast-params / "FREQUENCY" frequency-params / "FTTEST" fttest-params / "FV" fv-params / "FVSCHEDULE" fvschedule-params / "GAMMADIST" gammadist-params / "GAMMAINV" gammainv-params / "GAMMALN" gammaln-params / "GCD" gcd-params / "GEOMEAN" geomean-params / "GESTEP" gestep-params / "GETPIVOTDATA" getpivotdata-params / "GROWTH" growth-params / "HARMEAN" harmean-params / "HEX2BIN" hex2bin-params / "HEX2DEC" hex2dec-params / "HEX2OCT" hex2oct-params / "HLOOKUP" hlookup-params / "HOUR" hour-params / "HYPERLINK" hyperlink-params / "HYPGEOMDIST" hypgeomdist-params / "IFERROR" iferror-params / "IMABS" imabs-params / "IMAGINARY" imaginary-params / "IMARGUMENT" imargument-params / "IMCONJUGATE" imconjugate-params / "IMCOS" imcos-params / "IMDIV" imdiv-params / "IMEXP" imexp-params / "IMLN" imln-params / "IMLOG10" imlog10-params / "IMLOG2" imlog2-params / "IMPOWER" impower-params / "IMPRODUCT" improduct-params / "IMREAL" imreal-params / "IMSIN" imsin-params / "IMSQRT" imsqrt-params / "IMSUB" imsub-params / "IMSUM" imsum-params / "INFO" info-params / "INT" int-params / "INTERCEPT" intercept-params / "INTRATE" intrate-params / "IPMT" ipmt-params / "IRR" irr-params / "ISBLANK" isblank-params / "ISERR" iserr-params / "ISERROR" iserror-params / "ISEVEN" iseven-params / "ISLOGICAL" islogical-params / "ISNA" isna-params / "ISNONTEXT" isnontext-params / "ISNUMBER" isnumber-params / "ISODD" isodd-params / "ISPMT" ispmt-params / "ISREF" isref-params / "ISTEXT" istext-params / "ISTHAIDIGIT" isthaidigit-params / "KURT" kurt-params / "LARGE" large-params / "LCM" lcm-params / "LEFT" left-params / "LEFTB" leftb-params / "LEN" len-params / "LENB" lenb-params / "LINEST" linest-params / "LN" ln-params / "LOG" log-params / "LOG10" log10-params / "LOGEST" logest-params / "LOGINV" loginv-params / "LOGNORMDIST" lognormdist-params / "LOOKUP" lookup-params / "LOWER" lower-params / "MATCH" match-params /

"MAX" max-params / "MAXA" maxa-params / "MDETERM" mdeterm-params / "MDURATION" mduration-params / "MEDIAN" median-params / "MID" mid-params / "MIDB" midb-params / "MIN" min-params / "MINA" mina-params / "MINUTE" minute-params / "MINVERSE" minverse-params / "MIRR" mirr-params / "MMULT" mmult-params / "MOD" mod-params / "MODE" mode-params / "MONTH" month-params / "MROUND" mround-params / "MULTINOMIAL" multinomial-params / "N" n-params / "NA" na-params / "NEGBINOMDIST" negbinomdist-params / "NETWORKDAYS" networkdays-params / "NOMINAL" nominal-params / "NORMDIST" normdist-params / "NORMINV" norminv-params / "NORMSDIST" normsdist-params / "NORMSINV" normsinv-params / "NOT" not-params / "NOW" now-params / "NPER" nper-params / "NPV" npv-params / "NUMBERSTRING" numberstring-params / "OCT2BIN" oct2bin-params / "OCT2DEC" oct2dec-params / "OCT2HEX" oct2hex-params / "ODD" odd-params / "ODDFPRICE" oddfprice-params / "ODDFYIELD" oddfyield-params / "ODDLPRICE" oddlprice-params / "ODDLYIELD" oddlyield-params / "OR" or-params / "PEARSON" pearson-params / "PERCENTILE" percentile-params / "PERCENTRANK" percentrank-params / "PERMUT" permut-params / "PHONETIC" phonetic-params / "PI" pi-params / "PMT" pmt-params / "POISSON" poisson-params / "POWER" power-params / "PPMT" ppmt-params / "PRICE" price-params / "PRICEDISC" pricedisc-params / "PRICEMAT" pricemat-params / "PROB" prob-params / "PRODUCT" product-params / "PROPER" proper-params / "PV" pv-params / "QUARTILE" quartile-params / "QUOTIENT" quotient-params / "RADIANS" radians-params / "RAND" rand-params / "RANDBETWEEN" randbetween-params / "RANK" rank-params / "RATE" rate-params / "RECEIVED" received-params / "REPLACE" replace-params / "REPLACEB" replaceb-params / "REPT" rept-params / "RIGHT" right-params / "RIGHTB" rightb-params / "ROMAN" roman-params / "ROUND" round-params / "ROUNDBAHTDOWN" roundbahtdown-params / "ROUNDBAHTUP" roundbahtup-params / "ROUNDDOWN" rounddown-params / "ROUNDUP" roundup-params / "ROW" row-params / "ROWS" rows-params / "RSQ" rsq-params / "RTD" rtd-params / "SEARCH" search-params / "SEARCHB" searchb-params / "SECOND" second-params / "SERIES" series-params / "SERIESSUM" seriessum-params / "SIGN" sign-params / "SIN" sin-params / "SINH" sinh-params / "SKEW" skew-params / "SLN" sln-params / "SLOPE" slope-params / "SMALL" small-params / "SQRT" sqrt-params / "SQRTPI" sqrtpi-params / "STANDARDIZE" standardize-params / "STDEV" stdev-params / "STDEVA" stdeva-params / "STDEVP" stdevp-params / "STDEVPA" stdevpa-params / "STEYX" steyx-params / "SUBSTITUTE" substitute-params / "SUBTOTAL" subtotal-params / "SUM" sum-params / "SUMIF" sumif-params / "SUMIFS" sumifs-params / "SUMPRODUCT" sumproduct-params / "SUMSQ" sumsq-params / "SUMX2MY2" sumx2my2-params / "SUMX2PY2" sumx2py2-params / "SUMXY2" sumxmy2-params / "SYD" syd-params / "T" t-params / "TAN" tan-params / "TANH" tanh-params / "TBILLEQ" tbilleq-params / "TBILLPRICE" tbillprice-params / "TBILLYIELD" tbillyield-params / "TDIST" tdist-params / "TEXT" text-params / "THAIDAYOFWEEK" thaidayofweek-params / "THAIDIGIT" thaidigit-params / "THAIMONTHOFYEAR" thaimonthofyear-params / "THAINUMSOUND" thainumsound-params / "THAINUMSTRING" thainumstring-params / "THAISTRINGLENGTH" thaistringlength-params / "THAIYEAR" thaiyear-params / "TIME" time-params / "TIMEVALUE" timevalue-params / "TINV" tinv-params / "TODAY" today-params / "TRANSPOSE" transpose-params / "TREND" trend-params / "TRIM" trim-params / "TRIMMEAN" trimmean-params / "TRUE" true-params / "TRUNC" trunc-params / "TTEST" ttest-params / "TYPE" type-params / "UPPER" upper-params / "USDOLLAR" usdollar-params / "VALUE" value-params / "VAR" var-params / "VARA" vara-params / "VARP" varp-params / "VARPA" varpa-params / "VDB" vdb-params / "VLOOKUP" vlookup-params / "WEEKDAY" weekday-params / "WEEKNUM" weeknum-params / "WEIBULL" weibull-params / "WORKDAY" workday-params / "XIRR" xirr-params / "XNPV" xnpv-params / "YEAR" year-params / "YEARFRAC" yearfrac-params / "YIELD" yield-params / "YIELDDISC" yielddisc-params / "YIELDMAT" yieldmat-params / "ZTEST" ztest-params

emptyparams = "(" * whitespace ")"

abs-params = "(" argument-expression ")"

accrintm-params = "(" argument "," argument "," argument "," argument [" "," argument"] ")"

accrint-params = "(" argument "," argument "," argument "," argument "," argument "," argument [" "," argument [" "," argument"]] ")"

acosh-params = "(" argument-expression ")"

acos-params = "(" argument-expression ")"

acoth-params = "(" argument-expression ")"

acot-params = "(" argument-expression ")"

address-params = "(" argument "," argument [" "," argument [" "," argument [" "," argument"]]] ")"

aggregate-params = "(" argument "," argument "," argument [" "," argument [" "," ref-argument-expression *249("," ref-argument-expression)]] ")"

amordegrc-params = "(" argument "," argument "," argument "," argument "," argument "," argument [" "," argument"] ")"

amorlinc-params = "(" argument "," argument "," argument "," argument "," argument "," argument [" "," argument"] ")"

and-params = "(" (argument-expression / (argument 1*254("," argument))) ")"

arabic-params = "(" argument-expression ")"

```

areas-params = "(" ref-argument-expression ")"
asc-params = "(" argument-expression ")"
asinh-params = "(" argument-expression ")"
asin-params = "(" argument-expression ")"
atan2-params = "(" argument "," argument ")"
atanh-params = "(" argument-expression ")"
atan-params = "(" argument-expression ")"
avedev-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
averagea-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
averageif-params = "(" ref-argument-expression "," argument ["," ref-argument-expression ]
)"
averageifs-params = "(" ref-argument-expression "," ref-argument-expression "," argument
*126("," ref-argument-expression "," argument) ")"
average-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
bahttext-params = "(" argument-expression ")"
base-params = "(" argument "," argument ["," argument] ")"
besseli-params = "(" argument "," argument ")"
besselj-params = "(" argument "," argument ")"
besselk-params = "(" argument "," argument ")"
bessely-params = "(" argument "," argument ")"
beta-dist-params = "(" argument "," argument "," argument "," argument ["," argument [","
argument]] ")"
betadist-params = "(" argument "," argument "," argument ["," argument ["," argument]] ")"
betainv-params = "(" argument "," argument "," argument ["," argument ["," argument]] ")"
beta-inv-params = "(" argument "," argument "," argument ["," argument ["," argument]] ")"
bin2dec-params = "(" argument-expression ")"
bin2hex-params = "(" (argument-expression / (argument "," argument)) ")"
bin2oct-params = "(" (argument-expression / (argument "," argument)) ")"
binom-dist-range-params = "(" argument "," argument "," argument ["," argument] ")"
binomdist-params = "(" argument "," argument "," argument "," argument ")"
binom-dist-params = "(" argument "," argument "," argument "," argument ")"
binom-inv-params = "(" argument "," argument "," argument ")"
bitand-params = "(" argument "," argument ")"
bitlshift-params = "(" argument "," argument ")"
bitor-params = "(" argument "," argument ")"
bitrshift-params = "(" argument "," argument ")"
bitxor-params = "(" argument "," argument ")"
ceiling-math-params = "(" (argument-expression / (argument "," argument ["," argument])) ")"
ceiling-params = "(" argument "," argument ")"
ceiling-precise-params = "(" argument "," argument ")"
cell-params = "(" (argument-expression / (argument "," ref-argument-expression )) ")"
char-params = "(" argument-expression ")"
chidist-params = "(" argument "," argument ")"
chiinv-params = "(" argument "," argument ")"
chisq-dist-params = "(" argument "," argument "," argument ")"
chisq-dist-rt-params = "(" argument "," argument ")"
chisq-inv-params = "(" argument "," argument ")"
chisq-inv-rt-params = "(" argument "," argument ")"
chisq-test-params = "(" argument "," argument ")"
chitest-params = "(" argument "," argument ")"
choose-params = "(" argument "," argument *253("," argument) ")"
clean-params = "(" argument-expression ")"
code-params = "(" argument-expression ")"
column-params = "(" [ref-argument-expression ] ")"
columns-params = "(" argument-expression ")"
combina-params = "(" argument "," argument ")"
combin-params = "(" argument "," argument ")"
complex-params = "(" argument "," argument ["," argument] ")"
concatenate-params = "(" (argument-expression / (argument 1*254("," argument))) ")"

```

confidence-norm-params = "(" argument "," argument "," argument ")"
 confidence-params = "(" argument "," argument "," argument ")"
 confidence-t-params = "(" argument "," argument "," argument ")"
 convert-params = "(" argument "," argument "," argument ")"
 correl-params = "(" argument "," argument ")"
 cosh-params = "(" argument-expression ")"
 cos-params = "(" argument-expression ")"
 coth-params = "(" argument-expression ")"
 cot-params = "(" argument-expression ")"
 counta-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
 countblank-params = "(" ref-argument-expression ")"
 countif-params = "(" ref-argument-expression "," argument ")"
 countifs-params = "(" ref-argument-expression "," argument *126("," ref-argument-expression "," argument) ")"
 count-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
 coupdaybs-params = "(" argument "," argument "," argument ["," argument] ")"
 coupdaysnc-params = "(" argument "," argument ["," argument] ")"
 coupdays-params = "(" argument "," argument "," argument ["," argument] ")"
 coupncd-params = "(" argument "," argument "," argument ["," argument] ")"
 coupnum-params = "(" argument "," argument "," argument ["," argument] ")"
 coupncd-params = "(" argument "," argument "," argument ["," argument] ")"
 covariance-p-params = "(" argument "," argument ")"
 covariance-s-params = "(" argument "," argument ")"
 covar-params = "(" argument "," argument ")"
 critbinom-params = "(" argument "," argument "," argument ")"
 csch-params = "(" argument-expression ")"
 csc-params = "(" argument-expression ")"
 cubekpimember-params = "(" argument "," argument ["," argument] ")"
 cubemember-params = "(" argument "," argument ["," argument] ")"
 cubememberproperty-params = "(" argument "," argument "," argument ")"
 cuberankedmember-params = "(" argument "," argument "," argument ["," argument] ")"
 cubesetcount-params = "(" argument-expression ")"
 cubeset-params = "(" argument "," argument ["," argument ["," argument ["," argument]]] ")"
 cubevalue-params = "(" (argument-expression / (argument "," argument *253("," argument))) ")"
 cumipmt-params = "(" argument "," argument "," argument "," argument "," argument "," argument ")"
 cumprinc-params = "(" argument "," argument "," argument "," argument "," argument "," argument "," argument ")"
 datedif-params = "(" argument "," argument "," argument ")"
 date-params = "(" argument "," argument "," argument ")"
 datestring-params = "(" argument-expression ")"
 datevalue-params = "(" argument-expression ")"
 daverage-params = "(" ref-argument-expression "," argument "," argument ")"
 day-params = "(" argument-expression ")"
 days360-params = "(" argument "," argument ["," argument] ")"
 days-params = "(" argument "," argument ")"
 dbcs-params = "(" argument-expression ")"
 db-params = "(" argument "," argument "," argument "," argument ["," argument] ")"
 dcounta-params = "(" ref-argument-expression "," argument "," argument ")"
 dcount-params = "(" ref-argument-expression "," argument "," argument ")"
 ddb-params = "(" argument "," argument "," argument "," argument ["," argument] ")"
 dec2bin-params = "(" (argument-expression / (argument "," argument)) ")"
 dec2hex-params = "(" (argument-expression / (argument "," argument)) ")"
 dec2oct-params = "(" (argument-expression / (argument "," argument)) ")"
 decimal-params = "(" argument "," argument ")"
 degrees-params = "(" argument-expression ")"
 delta-params = "(" (argument-expression / (argument "," argument)) ")"
 devsq-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
 dget-params = "(" ref-argument-expression "," argument "," argument ")"

```

disc-params = "(" argument "," argument "," argument "," argument ["," argument] ")"
dmax-params = "(" ref-argument-expression "," argument "," argument ")"
dmin-params = "(" ref-argument-expression "," argument "," argument ")"
dollarde-params = "(" argument "," argument ")"
dollarfr-params = "(" argument "," argument ")"
dollar-params = "(" (argument-expression / (argument "," argument)) ")"
dproduct-params = "(" ref-argument-expression "," argument "," argument ")"
dstdev-params = "(" ref-argument-expression "," argument "," argument ")"
dstdevp-params = "(" ref-argument-expression "," argument "," argument ")"
dsum-params = "(" ref-argument-expression "," argument "," argument ")"
duration-params = "(" argument "," argument "," argument "," argument "," argument ["," argument] ")"
dvar-params = "(" ref-argument-expression "," argument "," argument ")"
dvarp-params = "(" ref-argument-expression "," argument "," argument ")"
ecma-ceiling-params = "(" argument "," argument ")"
edate-params = "(" argument "," argument ")"
effect-params = "(" argument "," argument ")"
eomonth-params = "(" argument "," argument ")"
erfc-params = "(" argument-expression ")"
erfc-precise-params = "(" argument-expression ")"
erf-params = "(" (argument-expression / (argument "," argument)) ")"
erf-precise-params = "(" argument-expression ")"
error-type-params = "(" argument-expression ")"
even-params = "(" argument-expression ")"
exact-params = "(" argument "," argument ")"
expondist-params = "(" argument "," argument "," argument ")"
expon-dist-params = "(" argument "," argument "," argument ")"
exp-params = "(" argument-expression ")"
factdouble-params = "(" argument-expression ")"
fact-params = "(" argument-expression ")"
false-params = emptyparams
fdist-params = "(" argument "," argument "," argument ")"
f-dist-params = "(" argument "," argument "," argument "," argument ")"
f-dist-rt-params = "(" argument "," argument "," argument ")"
filterxml-params = "(" argument "," argument ")"
findb-params = "(" argument "," argument ["," argument] ")"
find-params = "(" argument "," argument ["," argument] ")"
finv-params = "(" argument "," argument "," argument ")"
f-inv-params = "(" argument "," argument "," argument ")"
f-inv-rt-params = "(" argument "," argument "," argument ")"
fisherinv-params = "(" argument-expression ")"
fisher-params = "(" argument-expression ")"
fixed-params = "(" (argument-expression / (argument "," argument ["," argument])) ")"
floor-math-params = "(" (argument-expression / (argument "," argument ["," argument])) ")"
floor-params = "(" argument "," argument ")"
floor-precise-params = "(" argument "," argument ")"
forecast-params = "(" argument "," argument "," argument ")"
formulatext-params = "(" ref-argument-expression ")"
frequency-params = "(" argument "," argument ")"
ftest-params = "(" argument "," argument ")"
f-test-params = "(" argument "," argument ")"
fv-params = "(" argument "," argument "," argument ["," argument ["," argument]] ")"
fvschedule-params = "(" argument "," argument ")"
gammadist-params = "(" argument "," argument "," argument "," argument ")"
gamma-dist-params = "(" argument "," argument "," argument "," argument ")"
gammainv-params = "(" argument "," argument "," argument ")"
gamma-inv-params = "(" argument "," argument "," argument ")"
gammaln-params = "(" argument-expression ")"
gammaln-precise-params = "(" argument-expression ")"

```



```

gamma-params = "(" argument-expression ")"
gauss-params = "(" argument-expression ")"
gcd-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
geomean-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
gestep-params = "(" (argument-expression / (argument "," argument)) ")"
getpivotdata-params = "(" argument "," argument ["," argument ["," argument *125("," argument
"," argument)]]"
growth-params = "(" (argument-expression / (argument "," argument ["," argument [","
argument]])) ")"
harmean-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
hex2bin-params = "(" (argument-expression / (argument "," argument)) ")"
hex2dec-params = "(" argument-expression ")"
hex2oct-params = "(" (argument-expression / (argument "," argument)) ")"
hlookup-params = "(" argument "," argument "," argument ["," argument] ")"
hour-params = "(" argument-expression ")"
hyperlink-params = "(" (argument-expression / (argument "," argument)) ")"
hypgeomdist-params = "(" argument "," argument "," argument "," argument ")"
hypgeom-dist-params = "(" argument "," argument "," argument "," argument "," argument ")"
iferror-params = "(" argument "," argument ")"
ifna-params = "(" argument "," argument ")"
if-params = "(" (argument-expression / (argument "," argument ["," argument])) ")"
imabs-params = "(" argument-expression ")"
imaginary-params = "(" argument-expression ")"
imargument-params = "(" argument-expression ")"
imconjugate-params = "(" argument-expression ")"
imcosh-params = "(" argument-expression ")"
imcos-params = "(" argument-expression ")"
imcot-params = "(" argument-expression ")"
imcsch-params = "(" argument-expression ")"
imcsc-params = "(" argument-expression ")"
imdiv-params = "(" argument "," argument ")"
imexp-params = "(" argument-expression ")"
imln-params = "(" argument-expression ")"
imlog10-params = "(" argument-expression ")"
imlog2-params = "(" argument-expression ")"
impower-params = "(" argument "," argument ")"
improduct-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
imreal-params = "(" argument-expression ")"
imsech-params = "(" argument-expression ")"
imsec-params = "(" argument-expression ")"
imsinh-params = "(" argument-expression ")"
imsin-params = "(" argument-expression ")"
imsqrt-params = "(" argument-expression ")"
imsub-params = "(" argument "," argument ")"
imsum-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
imtan-params = "(" argument-expression ")"
index-params = "(" argument "," argument ["," argument ["," argument]] ")"
indirect-params = "(" (argument-expression / (argument "," argument)) ")"
info-params = "(" argument-expression ")"
intercept-params = "(" argument "," argument ")"
int-params = "(" argument-expression ")"
intrate-params = "(" argument "," argument "," argument "," argument ["," argument] ")"
ipmt-params = "(" argument "," argument "," argument "," argument ["," argument [","
argument]] ")"
irr-params = "(" (argument-expression / (argument "," argument)) ")"
isblank-params = "(" argument-expression ")"
iserror-params = "(" argument-expression ")"
iserr-params = "(" argument-expression ")"
iseven-params = "(" argument-expression ")"

```

```

isformula-params = "(" ref-argument-expression ")"
islogical-params = "(" argument-expression ")"
isna-params = "(" argument-expression ")"
isnontext-params = "(" argument-expression ")"
isnumber-params = "(" argument-expression ")"
iso-ceiling-params = "(" (argument-expression / (argument "," argument)) ")"
isodd-params = "(" argument-expression ")"
isoweeknum-params = "(" argument-expression ")"
ispmt-params = "(" argument "," argument "," argument "," argument ")"
isref-params = "(" argument-expression ")"
istext-params = "(" argument-expression ")"
isthaidigit-params = "(" argument-expression ")"
kurt-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
large-params = "(" argument "," argument ")"
lcm-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
leftb-params = "(" (argument-expression / (argument "," argument)) ")"
left-params = "(" (argument-expression / (argument "," argument)) ")"
lenb-params = "(" argument-expression ")"
len-params = "(" argument-expression ")"
linest-params = "(" (argument-expression / (argument "," argument [" argument [" argument [" argument ] ] ])) ")"
ln-params = "(" argument-expression ")"
log10-params = "(" argument-expression ")"
logest-params = "(" (argument-expression / (argument "," argument [" argument [" argument [" argument ] ] ])) ")"
loginv-params = "(" argument "," argument "," argument ")"
lognormdist-params = "(" argument "," argument "," argument ")"
lognorm-dist-params = "(" argument "," argument "," argument "," argument ")"
lognorm-inv-params = "(" argument "," argument "," argument ")"
log-params = "(" (argument-expression / (argument "," argument)) ")"
lookup-params = "(" argument "," argument [" argument ] ")"
lower-params = "(" argument-expression ")"
match-params = "(" argument "," argument [" argument ] ")"
maxa-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
max-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
mdeterm-params = "(" argument-expression ")"
mduration-params = "(" argument "," argument "," argument "," argument "," argument "," argument [" argument ] ")"
median-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
midb-params = "(" argument "," argument "," argument ")"
mid-params = "(" argument "," argument "," argument ")"
mina-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
min-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
minute-params = "(" argument-expression ")"
minverse-params = "(" argument-expression ")"
mirr-params = "(" argument "," argument "," argument ")"
mmult-params = "(" argument "," argument ")"
mode-mult-params = "(" (argument-expression / (argument 1*253("," argument))) ")"
mode-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
mode-sngl-params = "(" (argument-expression / (argument 1*253("," argument))) ")"
mod-params = "(" argument "," argument ")"
month-params = "(" argument-expression ")"
mround-params = "(" argument "," argument ")"
multinomial-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
munit-params = "(" argument-expression ")"
na-params = emptyparams
negbinomdist-params = "(" argument "," argument "," argument ")"
negbinom-dist-params = "(" argument "," argument "," argument "," argument ")"
networkdays-intl-params = "(" argument "," argument [" argument [" argument ] ] ")"

```

```

networkdays-params = "(" argument "," argument ["," argument] ")"
nominal-params = "(" argument "," argument ")"
normdist-params = "(" argument "," argument "," argument "," argument ")"
norm-dist-params = "(" argument "," argument "," argument "," argument ")"
norminv-params = "(" argument "," argument "," argument ")"
norm-inv-params = "(" argument "," argument "," argument ")"
norm-s-dist-params = "(" argument "," argument ")"
normsdist-params = "(" argument-expression ")"
normsinv-params = "(" argument-expression ")"
norm-s-inv-params = "(" argument-expression ")"
not-params = "(" argument-expression ")"
now-params = emptyparams
n-params = "(" argument-expression ")"
nper-params = "(" argument "," argument "," argument ["," argument ["," argument]] ")"
npv-params = "(" argument "," argument *253("," argument) ")"
numberstring-params = "(" argument "," argument ")"
numbervalue-params = "(" (argument-expression / (argument "," argument ["," argument])) ")"
oct2bin-params = "(" (argument-expression / (argument "," argument)) ")"
oct2dec-params = "(" argument-expression ")"
oct2hex-params = "(" (argument-expression / (argument "," argument)) ")"
oddprice-params = "(" argument "," argument "," argument "," argument "," argument "," argument ["," argument] ")"
oddfyield-params = "(" argument "," argument "," argument "," argument "," argument "," argument ["," argument] ")"
oddlprice-params = "(" argument "," argument "," argument "," argument "," argument "," argument ["," argument] ")"
oddiyld-params = "(" argument "," argument "," argument "," argument "," argument "," argument ["," argument] ")"
odd-params = "(" argument-expression ")"
offset-params = "(" ref-argument-expression "," argument "," argument ["," argument ["," argument]] ")"
or-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
pduration-params = "(" argument "," argument "," argument ")"
pearson-params = "(" argument "," argument ")"
percentile-exc-params = "(" argument "," argument ")"
percentile-inc-params = "(" argument "," argument ")"
percentile-params = "(" argument "," argument ")"
percentrank-exc-params = "(" argument "," argument ["," argument] ")"
percentrank-inc-params = "(" argument "," argument ["," argument] ")"
percentrank-params = "(" argument "," argument ["," argument] ")"
permutationa-params = "(" argument "," argument ")"
permut-params = "(" argument "," argument ")"
phi-params = "(" argument-expression ")"
phonetic-params = "(" ref-argument-expression ")"
pi-params = emptyparams
pmt-params = "(" argument "," argument "," argument ["," argument ["," argument]] ")"
poisson-dist-params = "(" argument "," argument "," argument ")"
poisson-params = "(" argument "," argument "," argument ")"
power-params = "(" argument "," argument ")"
ppmt-params = "(" argument "," argument "," argument "," argument ["," argument ["," argument]] ")"
pricedisc-params = "(" argument "," argument "," argument "," argument ["," argument] ")"
pricemat-params = "(" argument "," argument "," argument "," argument "," argument ["," argument] ")"
price-params = "(" argument "," argument "," argument "," argument "," argument "," argument ["," argument] ")"
prob-params = "(" argument "," argument "," argument ["," argument] ")"
product-params = "(" (argument-expression / (argument 1*254("," argument))) ")"
proper-params = "(" argument-expression ")"
pv-params = "(" argument "," argument "," argument ["," argument ["," argument]] ")"

```

```

quartile-exc-params = "(" argument "," argument ")"
quartile-inc-params = "(" argument "," argument ")"
quartile-params = "(" argument "," argument ")"
querystring-params = "(" argument "," argument *126( "," argument "," argument) ")"
quotient-params = "(" argument "," argument ")"
radians-params = "(" argument-expression ")"
randbetween-params = "(" argument "," argument ")"
rand-params = emptyparams
rank-avg-params = "(" argument "," ref-argument-expression ["," argument] ")"
rank-eq-params = "(" argument "," ref-argument-expression ["," argument] ")"
rank-params = "(" argument "," ref-argument-expression ["," argument] ")"
rate-params = "(" argument "," argument "," argument ["," argument ["," argument ["," argument]] ")"
received-params = "(" argument "," argument "," argument "," argument ["," argument] ")"
replaceb-params = "(" argument "," argument "," argument "," argument ")"
replace-params = "(" argument "," argument "," argument "," argument ")"
rept-params = "(" argument "," argument ")"
rightb-params = "(" (argument-expression / (argument "," argument)) ")"
right-params = "(" (argument-expression / (argument "," argument)) ")"
roman-params = "(" (argument-expression / (argument "," argument)) ")"
roundbahtdown-params = "(" argument-expression ")"
roundbahtup-params = "(" argument-expression ")"
rounddown-params = "(" argument "," argument ")"
round-params = "(" argument "," argument ")"
roundup-params = "(" argument "," argument ")"
row-params = "(" [ref-argument-expression] ")"
rows-params = "(" argument-expression ")"
rri-params = "(" argument "," argument "," argument ")"
rsq-params = "(" argument "," argument ")"
rtd-params = "(" argument "," argument "," argument *252( "," argument) ")"
searchb-params = "(" argument "," argument ["," argument] ")"
search-params = "(" argument "," argument ["," argument] ")"
sech-params = "(" argument-expression ")"
second-params = "(" argument-expression ")"
sec-params = "(" argument-expression ")"
series-params = "(" argument "," argument "," argument "," argument ["," argument] ")"
seriessum-params = "(" argument "," argument "," argument "," argument ")"
sheet-params = "(" argument ")"
sheets-params = "(" argument ")"
sign-params = "(" argument-expression ")"
sinh-params = "(" argument-expression ")"
sin-params = "(" argument-expression ")"
skew-params = "(" (argument-expression / (argument 1*254( "," argument))) ")"
skew-p-params = "(" (argument-expression / (argument 1*253( "," argument))) ")"
sln-params = "(" argument "," argument "," argument ")"
slope-params = "(" argument "," argument ")"
small-params = "(" argument "," argument ")"
sqrt-params = "(" argument-expression ")"
sqrtpi-params = "(" argument-expression ")"
standardize-params = "(" argument "," argument "," argument ")"
stdeva-params = "(" (argument-expression / (argument 1*254( "," argument))) ")"
stdevpa-params = "(" (argument-expression / (argument 1*254( "," argument))) ")"
stdev-params = "(" (argument-expression / (argument 1*254( "," argument))) ")"
stdev-p-params = "(" (argument-expression / (argument 1*253( "," argument))) ")"
stdevp-params = "(" (argument-expression / (argument 1*254( "," argument))) ")"
stdev-s-params = "(" (argument-expression / (argument 1*253( "," argument))) ")"
steyx-params = "(" argument "," argument ")"
substitute-params = "(" argument "," argument "," argument ["," argument] ")"

```

```

subtotal-params = "(" argument "," ref-argument-expression *253("," ref-argument-expression )
)"
sumif-params = "(" ref-argument-expression "," argument ["," ref-argument-expression ] )"
sumifs-params = "(" ref-argument-expression "," ref-argument-expression "," argument *126(","
ref-argument-expression "," argument )"
sum-params = "(" (argument-expression / (argument 1*254("," argument))) )"
sumproduct-params = "(" (argument-expression / (argument 1*254("," argument))) )"
sumsq-params = "(" (argument-expression / (argument 1*254("," argument))) )"
sumx2my2-params = "(" argument "," argument )"
sumx2py2-params = "(" argument "," argument )"
sumxmy2-params = "(" argument "," argument )"
syd-params = "(" argument "," argument "," argument "," argument )"
tanh-params = "(" argument-expression )"
tan-params = "(" argument-expression )"
tbilleq-params = "(" argument "," argument "," argument )"
tbillprice-params = "(" argument "," argument "," argument )"
tbillyield-params = "(" argument "," argument "," argument )"
t-dist-2t-params = "(" argument "," argument )"
tdist-params = "(" argument "," argument "," argument )"
t-dist-params = "(" argument "," argument "," argument )"
t-dist-rt-params = "(" argument "," argument )"
text-params = "(" argument "," argument )"
thaidayofweek-params = "(" argument-expression )"
thaidigit-params = "(" argument-expression )"
thaimonthofyear-params = "(" argument-expression )"
thainumsound-params = "(" argument-expression )"
thainumstring-params = "(" argument-expression )"
thainstringlength-params = "(" argument-expression )"
thaiyear-params = "(" argument-expression )"
time-params = "(" argument "," argument "," argument )"
timevalue-params = "(" argument-expression )"
t-inv-2t-params = "(" argument "," argument )"
tinv-params = "(" argument "," argument )"
t-inv-params = "(" argument "," argument )"
today-params = emptyparams
t-params = "(" argument-expression )"
transpose-params = "(" argument-expression )"
trend-params = "(" (argument-expression / (argument "," argument ["," argument [","
argument]])) )"
trimmean-params = "(" argument "," argument )"
trim-params = "(" argument-expression )"
true-params = emptyparams
trunc-params = "(" (argument-expression / (argument "," argument)) )"
ttest-params = "(" argument "," argument "," argument "," argument )"
t-test-params = "(" argument "," argument "," argument "," argument )"
type-params = "(" argument-expression )"
unicchar-params = "(" argument-expression )"
unicode-params = "(" argument-expression )"
upper-params = "(" argument-expression )"
usdollar-params = "(" (argument-expression / (argument "," argument)) )"
value-params = "(" argument-expression )"
vara-params = "(" (argument-expression / (argument 1*254("," argument))) )"
varpa-params = "(" (argument-expression / (argument 1*254("," argument))) )"
var-params = "(" (argument-expression / (argument 1*254("," argument))) )"
var-p-params = "(" (argument-expression / (argument 1*253("," argument))) )"
varp-params = "(" (argument-expression / (argument 1*254("," argument))) )"
var-s-params = "(" (argument-expression / (argument 1*253("," argument))) )"
vdb-params = "(" argument "," argument "," argument "," argument "," argument ["," argument
["," argument]] )"

```

```

vlookup-params = "(" argument "," argument "," argument ["," argument] ")"
webservice-params = "(" (argument-expression / (argument "," argument)) ")"
weekday-params = "(" (argument-expression / (argument "," argument)) ")"
weeknum-params = "(" (argument-expression / (argument "," argument)) ")"
weibull-dist-params = "(" argument "," argument "," argument "," argument ")"
weibull-params = "(" argument "," argument "," argument "," argument ")"
workday-intl-params = "(" argument "," argument ["," argument ["," argument]] ")"
workday-params = "(" argument "," argument ["," argument] ")"
xirr-params = "(" argument "," argument ["," argument] ")"
xnpv-params = "(" argument "," argument "," argument ")"
xor-params = "(" (argument-expression / (argument 1*253("," argument))) ")"
yearfrac-params = "(" argument "," argument ["," argument] ")"
year-params = "(" argument-expression ")"
yielddisc-params = "(" argument "," argument "," argument "," argument ["," argument] ")"
yieldmat-params = "(" argument "," argument "," argument "," argument "," argument ["," argument] ")"
yield-params = "(" argument "," argument "," argument "," argument "," argument "," argument ["," argument] ")"
ztest-params = "(" argument "," argument ["," argument] ")"
z-test-params = "(" argument "," argument ["," argument] ")"

ref-macro-function-call = "ABSREF" absref-params / "ACTIVE.CELL" active-cell-params / "CALL" call-params / "CALLER" caller-params / "EVALUATE" evaluate-params / "GET.DOCUMENT" get-document-params / "INPUT" input-params / "LAST.ERROR" last-error-params / "SCENARIO.GET" scenario-get-params / "SELECTION" selection-params / "TEXTREF" textref-params / "VIEW.GET" view-get-params
macro-function-call = ref-macro-function-call / "ADD.BAR" add-bar-params / "ADD.COMMAND" add-command-params / "ADD.MENU" add-menu-params / "ADD.TOOLBAR" add-toolbar-params / "APP.TITLE" app-title-params / "ARGUMENT" argument-params / "BREAK" break-params / "CANCEL.KEY" cancel-key-params / "CHECK.COMMAND" check-command-params / "CREATE.OBJECT" create-object-params / "CUSTOM.REPEAT" custom-repeat-params / "CUSTOM.UNDO" custom-undo-params / "DELETE.BAR" delete-bar-params / "DELETE.COMMAND" delete-command-params / "DELETE.MENU" delete-menu-params / "DELETE.TOOLBAR" delete-toolbar-params / "DEREF" deref-params / "DIALOG.BOX" dialog-box-params / "DIRECTORY" directory-params / "DOCUMENTS" documents-params / "ECHO" echo-params / "ELSE" else-params / "ELSE.IF" else-if-params / "ENABLE.COMMAND" enable-command-params / "ENABLE.TOOL" enable-tool-params / "END.IF" end-if-params / "ERROR" error-params / "EXEC" exec-params / "EXECUTE" execute-params / "FCLOSE" fclose-params / "FILES" files-params / "FOPEN" fopen-params / "FOR" for-params / "FOR.CELL" for-cell-params / "FORMULA.CONVERT" formula-convert-params / "FPOS" fpos-params / "FREAD" fread-params / "FREADLN" freadln-params / "FSIZE" fsize-params / "FWRITE" fwrite-params / "FWRITELN" fwriteln-params / "GET.BAR" get-bar-params / "GET.CELL" get-cell-params / "GET.CHART.ITEM" get-chart-item-params / "GET.DEF" get-def-params / "GET.FORMULA" get-formula-params / "GET.LINK.INFO" get-link-info-params / "GET.MOVIE" get-movie-params / "GET.NAME" get-name-params / "GET.NOTE" get-note-params / "GET.OBJECT" get-object-params / "GET.TOOL" get-tool-params / "GET.TOOLBAR" get-toolbar-params / "GET.WINDOW" get-window-params / "GET.WORKBOOK" get-workbook-params / "GET.WORKSPACE" get-workspace-params / "GOTO" goto-params / "GROUP" group-params / "HALT" halt-params / "HELP" help-params / "INITIATE" initiate-params / "LINKS" links-params / "MOVIE.COMMAND" movie-command-params / "NAMES" names-params / "NEXT" next-params / "NOTE" note-params / "OPEN.DIALOG" open-dialog-params / "OPTIONS.LISTS.GET" options-lists-get-params / "PAUSE" pause-params / "POKE" poke-params / "PRESS.TOOL" press-tool-params / "REFTEXT" ref-text-params / "REGISTER" register-params / "REGISTER.ID" register-id-params / "RELREF" relref-params / "RENAME.COMMAND" rename-command-params / "REQUEST" request-params / "RESET.TOOLBAR" reset-toolbar-params / "RESTART" restart-params / "RESULT" result-params / "RESUME" resume-params / "RETURN" return-params / "SAVE.DIALOG" save-dialog-params / "SAVE.TOOLBAR" save-toolbar-params / "SET.NAME" set-name-params / "SET.VALUE" set-value-params / "SHOW.BAR" show-bar-params / "SPELLING.CHECK" spelling-check-params / "STEP" step-params / "TERMINATE" terminate-params / "TEXT.BOX" text-box-params / "UNREGISTER" unregister-params / "VOLATILE" volatile-params / "WHILE" while-params / "WINDOW.TITLE" window-title-params / "WINDOWS" windows-params

absref-params = "(" argument "," ref-argument-expression ")"
active-cell-params = "(" *space ")"
add-bar-params = "(" argument ")"

```


get-object-params = "(" (argument-expression / (argument "," argument ["," argument ["," argument ["," argument ["," argument]]])) ") "
get-tool-params = "(" (argument-expression / (argument "," argument ["," argument])) ") "
get-toolbar-params = "(" (argument-expression / (argument "," argument)) ") "
get-window-params = "(" (argument-expression / (argument "," argument)) ") "
get-workbook-params = "(" (argument-expression / (argument "," argument)) ") "
get-workspace-params = "(" argument-expression ") "
goto-params = "(" ref-argument-expression ") "
group-params = "(" *space ") "
halt-params = "(" argument ") "
help-params = "(" argument ") "
initiate-params = "(" argument "," argument ") "
input-params = "(" (argument-expression / (argument "," argument ["," argument ["," argument ["," argument ["," argument ["," argument]]])))) ") "
last-error-params = "(" *space ") "
links-params = "(" argument ["," argument] ") "
movie-command-params = "(" argument "," argument "," argument ["," argument] ") "
names-params = "(" argument ["," argument ["," argument]] ") "
next-params = "(" *space ") "
note-params = "(" argument ["," argument ["," argument ["," argument]] ") "
open-dialog-params = "(" argument ["," argument ["," argument ["," argument]] ") "
options-lists-get-params = "(" argument-expression ") "
pause-params = "(" argument ") "
poke-params = "(" argument "," argument "," argument ") "
press-tool-params = "(" argument "," argument "," argument ") "
reftext-params = "(" ref-argument-expression "," argument ") "
register-params = "(" (argument-expression / (argument "," argument ["," argument ["," argument ["," argument ["," argument ["," argument]]])))) ") "
register-id-params = "(" argument "," argument ["," argument] ") "
relref-params = "(" ref-argument-expression "," ref-argument-expression ") "
rename-command-params = "(" argument "," argument "," argument "," argument ["," argument] ") "
request-params = "(" argument "," argument ") "
reset-toolbar-params = "(" argument-expression ") "
restart-params = "(" argument ") "
result-params = "(" argument ") "
resume-params = "(" argument ") "
return-params = "(" argument ") "
save-dialog-params = "(" argument ["," argument ["," argument ["," argument ["," argument]]]) ") "
save-toolbar-params = "(" argument ["," argument] ") "
scenario-get-params = "(" (argument-expression / (argument "," argument)) ") "
selection-params = "(" *space ") "
set-name-params = "(" (argument-expression / (argument "," argument)) ") "
set-value-params = "(" ref-argument-expression "," argument ") "
show-bar-params = "(" argument ") "
spelling-check-params = "(" (argument-expression / (argument "," argument ["," argument])) ") "
step-params = "(" *space ") "
terminate-params = "(" argument-expression ") "
text-box-params = "(" (argument-expression / (argument "," argument ["," argument ["," argument ["," argument]])) ") "
textref-params = "(" (argument-expression / (argument "," argument)) ") "
unregister-params = "(" argument-expression ") "
view-get-params = "(" (argument-expression / (argument "," argument)) ") "
volatile-params = "(" argument ") "
while-params = "(" argument-expression ") "
window-title-params = "(" argument ") "
windows-params = "(" argument ["," argument] ") "

command-function-call = "A1.R1C1" a1-rlc1-params / "ACTIVATE" ["?"] activate-params / "ACTIVATE.NEXT" activate-next-params / "ACTIVATE.NOTES" activate-notes-params / "ACTIVATE.PREV" activate-prev-params / "ACTIVE.CELL.FONT" ["?"] active-cell-font-params / "ADD.ARROW" add-arrow-params / "ADD.CHART.AUTOFORMAT" ["?"] add-chart-autoformat-params / "ADD.LIST.ITEM" add-list-item-params / "ADD.OVERLAY" add-overlay-params / "ADD.PRINT.AREA" add-print-area-params / "ADD.TOOL" add-tool-params / "ADDIN.MANAGER" ["?"] addin-manager-params / "ALERT" alert-params / "ALIGNMENT" ["?"] alignment-params / "APP.ACTIVATE" app-activate-params / "APP.ACTIVATE.MICROSOFT" app-activate-microsoft-params / "APP.MAXIMIZE" app-maximize-params / "APP.MINIMIZE" app-minimize-params / "APP.MOVE" ["?"] app-move-params / "APP.RESTORE" app-restore-params / "APP.SIZE" ["?"] app-size-params / "APPLY.NAMES" ["?"] apply-names-params / "APPLY.STYLE" ["?"] apply-style-params / "ARRANGE.ALL" ["?"] arrange-all-params / "ASSIGN.TO.OBJECT" ["?"] assign-to-object-params / "ASSIGN.TO.TOOL" ["?"] assign-to-tool-params / "ATTACH.TEXT" ["?"] attach-text-params / "ATTACH.TOOLBARS" ["?"] attach-toolbars-params / "ATTRIBUTES" ["?"] attributes-params / "AUTO.OUTLINE" auto-outline-params / "AUTOCORRECT" ["?"] autocorrect-params / "AXES" ["?"] axes-params / "BEEP" beep-params / "BORDER" ["?"] border-params / "BRING.TO.FRONT" bring-to-front-params / "CALCULATE.DOCUMENT" calculate-document-params / "CALCULATE.NOW" calculate-now-params / "CALCULATION" ["?"] calculation-params / "CANCEL.COPY" cancel-copy-params / "CELL.PROTECTION" ["?"] cell-protection-params / "CHANGE.LINK" ["?"] change-link-params / "CHART.ADD.DATA" ["?"] chart-add-data-params / "CHART.TREND" ["?"] chart-trend-params / "CHART.WIZARD" ["?"] chart-wizard-params / "CHECKBOX.PROPERTIES" ["?"] checkbox-properties-params / "CLEAR" ["?"] clear-params / "CLEAR.OUTLINE" clear-outline-params / "CLEAR.PRINT.AREA" clear-print-area-params / "CLEAR.ROUTING.SLIP" clear-routing-slip-params / "CLOSE" close-params / "CLOSE.ALL" close-all-params / "COLOR.PALETTE" ["?"] color-palette-params / "COLUMN.WIDTH" ["?"] column-width-params / "COMBINATION" ["?"] combination-params / "CONSOLIDATE" ["?"] consolidate-params / "CONSTRAIN.NUMERIC" constrain-numeric-params / "COPY" copy-params / "COPY.CHART" ["?"] copy-chart-params / "COPY.PICTURE" ["?"] copy-picture-params / "COPY.TOOL" copy-tool-params / "CREATE.NAMES" ["?"] create-names-params / "CREATE.PUBLISHER" ["?"] create-publisher-params / "CUSTOMIZE.TOOLBAR" ["?"] customize-toolbar-params / "CUT" cut-params / "DATA.DELETE" ["?"] data-delete-params / "DATA.FIND" data-find-params / "DATA.FIND.NEXT" data-find-next-params / "DATA.FIND.PREV" data-find-prev-params / "DATA.FORM" data-form-params / "DATA.LABEL" ["?"] data-label-params / "DATA.SERIES" ["?"] data-series-params / "DEFINE.NAME" ["?"] define-name-params / "DEFINE.STYLE" ["?"] define-style-params / "DELETE.ARROW" delete-arrow-params / "DELETE.CHART.AUTOFORMAT" delete-chart-autoformat-params / "DELETE.FORMAT" ["?"] delete-format-params / "DELETE.NAME" ["?"] delete-name-params / "DELETE.NOTE" delete-note-params / "DELETE.OVERLAY" delete-overlay-params / "DELETE.STYLE" delete-style-params / "DELETE.TOOL" delete-tool-params / "DEMOTE" ["?"] demote-params / "DISABLE.INPUT" disable-input-params / "DISPLAY" ["?"] display-params / "DUPLICATE" duplicate-params / "EDIT.COLOR" ["?"] edit-color-params / "EDIT.DELETE" ["?"] edit-delete-params / "EDIT.OBJECT" edit-object-params / "EDIT.REPEAT" edit-repeat-params / "EDIT.SERIES" ["?"] edit-series-params / "EDIT.TOOL" edit-tool-params / "EDITBOX.PROPERTIES" ["?"] editbox-properties-params / "EDITION.OPTIONS" ["?"] edition-options-params / "ENABLE.OBJECT" enable-object-params / "ENABLE.TIPWIZARD" enable-tipwizard-params / "ENTER.DATA" enter-data-params / "ERRORBAR.X" ["?"] errorbar-x-params / "ERRORBAR.Y" ["?"] errorbar-y-params / "EXTEND.POLYGON" extend-polygon-params / "EXTRACT" ["?"] extract-params / "FILE.CLOSE" file-close-params / "FILE.DELETE" ["?"] file-delete-params / "FILL.AUTO" fill-auto-params / "FILL.DOWN" fill-down-params / "FILL.GROUP" ["?"] fill-group-params / "FILL.LEFT" fill-left-params / "FILL.RIGHT" fill-right-params / "FILL.UP" fill-up-params / "FILTER" ["?"] filter-params / "FILTER.ADVANCED" ["?"] filter-advanced-params / "FILTER.SHOW.ALL" filter-show-all-params / "FIND.FILE" ["?"] find-file-params / "FONT" ["?"] font-params / "FONT.PROPERTIES" ["?"] font-properties-params / "FORMAT.AUTO" ["?"] format-auto-params / "FORMAT.CHART" ["?"] format-chart-params / "FORMAT.CHARTTYPE" ["?"] format-charttype-params / "FORMAT.FONT" ["?"] format-font-params / "FORMAT.LEGEND" ["?"] format-legend-params / "FORMAT.MAIN" ["?"] format-main-params / "FORMAT.MOVE" format-move-params / "FORMAT.NUMBER" ["?"] format-number-params / "FORMAT.OVERLAY" ["?"] format-overlay-params / "FORMAT.SHAPE" format-shape-params / "FORMAT.SIZE" format-size-params / "FORMAT.TEXT" ["?"] format-text-params / "FORMULA" formula-params / "FORMULA.ARRAY" formula-array-params / "FORMULA.FILL" formula-fill-params / "FORMULA.FIND" ["?"] formula-find-params / "FORMULA.FIND.NEXT" formula-find-next-params / "FORMULA.FIND.PREV" formula-find-prev-params / "FORMULA.GOTO" ["?"] formula-goto-params / "FORMULA.REPLACE" ["?"] formula-replace-params / "FREEZE.PANES" freeze-panes-params / "FULL" full-params / "FULL.SCREEN" full-screen-params / "FUNCTION.WIZARD" ["?"] function-wizard-params / "GALLERY.3D.AREA" ["?"] gallery-3d-area-params / "GALLERY.3D.BAR" ["?"] gallery-3d-bar-params / "GALLERY.3D.COLUMN" ["?"] gallery-3d-column-params / "GALLERY.3D.LINE" ["?"] gallery-3d-line-params / "GALLERY.3D.PIE" ["?"] gallery-3d-pie-params / "GALLERY.3D.SURFACE" ["?"] gallery-3d-surface-params / "GALLERY.AREA" ["?"] gallery-area-params / "GALLERY.BAR"

["?"] gallery-bar-params / "GALLERY.COLUMN" ["?"] gallery-column-params / "GALLERY.CUSTOM" ["?"] gallery-custom-params / "GALLERY.DOUGHNUT" ["?"] gallery-doughnut-params / "GALLERY.LINE" ["?"] gallery-line-params / "GALLERY.PIE" ["?"] gallery-pie-params / "GALLERY.RADAR" ["?"] gallery-radar-params / "GALLERY.SCATTER" ["?"] gallery-scatter-params / "GOAL.SEEK" ["?"] goal-seek-params / "GRIDLINES" ["?"] gridlines-params / "HIDE" hide-params / "HIDE.DIALOG" hide-dialog-params / "HIDE.OBJECT" hide-object-params / "HIDEALL.INKANNTOTS" hideall-inkannots-params / "HIDEALL.NOTES" hideall-notes-params / "HIDECURR.NOTE" hidecurr-note-params / "HLINE" hline-params / "HPAGE" hpage-params / "HSCROLL" hscroll-params / "INSERT" ["?"] insert-params / "INSERT.MAP.OBJECT" ["?"] insert-map-object-params / "INSERT.OBJECT" ["?"] insert-object-params / "INSERT.PICTURE" ["?"] insert-picture-params / "INSERT.TITLE" ["?"] insert-title-params / "INSERTDATATABLE" ["?"] insertdatatable-params / "JUSTIFY" justify-params / "LABEL.PROPERTIES" ["?"] label-properties-params / "LAYOUT" layout-params / "LEGEND" legend-params / "LINE.PRINT" line-print-params / "LINK.COMBO" link-combo-params / "LINK.FORMAT" link-format-params / "LIST.NAMES" list-names-params / "LISTBOX.PROPERTIES" ["?"] listbox-properties-params / "MACRO.OPTIONS" ["?"] macro-options-params / "MAIL.ADD.MAILER" mail-add-mailer-params / "MAIL.DELETE.MAILER" mail-delete-mailer-params / "MAIL.EDIT.MAILER" ["?"] mail-edit-mailer-params / "MAIL.FORWARD" mail-forward-params / "MAIL.LOGOFF" mail-logoff-params / "MAIL.LOGON" ["?"] mail-logon-params / "MAIL.NEXT.LETTER" mail-next-letter-params / "MAIL.REPLY" mail-reply-params / "MAIL.REPLY.ALL" mail-reply-all-params / "MAIL.SEND.MAILER" ["?"] mail-send-mailer-params / "MAIN.CHART" ["?"] main-chart-params / "MAIN.CHART.TYPE" ["?"] main-chart-type-params / "MENU.EDITOR" ["?"] menu-editor-params / "MERGE.STYLES" merge-styles-params / "MESSAGE" message-params / "MOVE.BRK" move-brk-params / "MOVE.TOOL" move-tool-params / "NEW" ["?"] new-params / "NEW.WINDOW" new-window-params / "NEWWEBQUERY" newwebquery-params / "NORMAL" normal-params / "OBJECT.PROPERTIES" ["?"] object-properties-params / "OBJECT.PROTECTION" ["?"] object-protection-params / "ON.DATA" on-data-params / "ON.DOUBLECLICK" on-doubleclick-params / "ON.ENTRY" on-entry-params / "ON.KEY" on-key-params / "ON.RECALC" on-recalc-params / "ON.SHEET" on-sheet-params / "ON.TIME" on-time-params / "ON.WINDOW" on-window-params / "OPEN" ["?"] open-params / "OPEN.LINKS" ["?"] open-links-params / "OPEN.MAIL" ["?"] open-mail-params / "OPEN.TEXT" open-text-params / "OPTIONS.CALCULATION" ["?"] options-calculation-params / "OPTIONS.CHART" ["?"] options-chart-params / "OPTIONS.EDIT" ["?"] options-edit-params / "OPTIONS.GENERAL" ["?"] options-general-params / "OPTIONS.LISTS.ADD" ["?"] options-lists-add-params / "OPTIONS.LISTS.DELETE" options-lists-delete-params / "OPTIONS.ME" ["?"] options-me-params / "OPTIONS.MENONO" ["?"] options-menono-params / "OPTIONS.SAVE" ["?"] options-save-params / "OPTIONS.SPELL" ["?"] options-spell-params / "OPTIONS.TRANSITION" ["?"] options-transition-params / "OPTIONS.VIEW" ["?"] options-view-params / "OUTLINE" ["?"] outline-params / "OVERLAY" ["?"] overlay-params / "OVERLAY.CHART.TYPE" ["?"] overlay-chart-type-params / "PAGE.SETUP" ["?"] page-setup-params / "PARSE" ["?"] parse-params / "PASTE" paste-params / "PASTE.LINK" paste-link-params / "PASTE.PICTURE" paste-picture-params / "PASTE.PICTURE.LINK" paste-picture-link-params / "PASTE.SPECIAL" ["?"] paste-special-params / "PASTE.TOOL" paste-tool-params / "PATTERNS" ["?"] patterns-params / "PICKLIST" ["?"] picklist-params / "PIVOT.ADD.FIELDS" pivot-add-fields-params / "PIVOT.FIELD" pivot-field-params / "PIVOT.FIELD.GROUP" ["?"] pivot-field-group-params / "PIVOT.FIELD.PROPERTIES" ["?"] pivot-field-properties-params / "PIVOT.FIELD.UNGROUP" ["?"] pivot-field-ungroup-params / "PIVOT.ITEM" pivot-item-params / "PIVOT.ITEM.PROPERTIES" pivot-item-properties-params / "PIVOT.REFRESH" pivot-refresh-params / "PIVOT.SHOW.PAGES" ["?"] pivot-show-pages-params / "PIVOT.TABLE.CHART" ["?"] pivot-table-chart-params / "PIVOT.TABLE.WIZARD" ["?"] pivot-table-wizard-params / "POST.DOCUMENT" ["?"] post-document-params / "PRECISION" precision-params / "PREFERRED" preferred-params / "PRINT" ["?"] print-params / "PRINT.PREVIEW" ["?"] print-preview-params / "PRINTER.SETUP" ["?"] printer-setup-params / "PROMOTE" ["?"] promote-params / "PROTECT.DOCUMENT" ["?"] protect-document-params / "PROTECT.REVISIONS" ["?"] protect-revisions-params / "PUSHBUTTON.PROPERTIES" ["?"] pushbutton-properties-params / "QUIT" quit-params / "REMOVE.LIST.ITEM" remove-list-item-params / "REMOVE.PAGE.BREAK" remove-page-break-params / "RENAME.OBJECT" rename-object-params / "REPLACE.FONT" ["?"] replace-font-params / "RESET.TOOL" reset-tool-params / "RM.PRINT.AREA" rm-print-area-params / "ROUTE.DOCUMENT" route-document-params / "ROUTING.SLIP" ["?"] routing-slip-params / "ROW.HEIGHT" ["?"] row-height-params / "RUN" ["?"] run-params / "SAVE" save-params / "SAVE.AS" ["?"] save-as-params / "SAVE.COPY.AS" save-copy-as-params / "SAVE.NEW.OBJECT" ["?"] save-new-object-params / "SAVE.WORKBOOK" ["?"] save-workbook-params / "SAVE.WORKSPACE" ["?"] save-workspace-params / "SCALE" ["?"] scale-params / "SCENARIO.ADD" ["?"] scenario-add-params / "SCENARIO.CELLS" ["?"] scenario-cells-params / "SCENARIO.DELETE" scenario-delete-params / "SCENARIO.EDIT" ["?"] scenario-edit-params / "SCENARIO.MERGE" ["?"] scenario-merge-params / "SCENARIO.SHOW" scenario-show-params / "SCENARIO.SHOW.NEXT" scenario-show-next-params / "SCENARIO.SUMMARY" ["?"] scenario-summary-params / "SCROLLBAR.PROPERTIES" ["?"] scrollbar-properties-params / "SELECT" select-params / "SELECT.ALL" select-all-params / "SELECT.CHART" select-chart-params / "SELECT.END" select-end-params / "SELECT.LAST.CELL" select-last-cell-params /

"SELECT.LIST.ITEM" select-list-item-params / "SELECT.PLOT.AREA" select-plot-area-params / "SELECT.SPECIAL" ["?"] select-special-params / "SEND.KEYS" send-keys-params / "SEND.MAIL" ["?"] send-mail-params / "SEND.TO.BACK" send-to-back-params / "SERIES.AXES" ["?"] series-axes-params / "SERIES.ORDER" ["?"] series-order-params / "SERIES.X" ["?"] series-x-params / "SERIES.Y" ["?"] series-y-params / "SET.CONTROL.VALUE" set-control-value-params / "SET.CRITERIA" set-criteria-params / "SET.DATABASE" set-database-params / "SET.DIALOG.DEFAULT" set-dialog-default-params / "SET.DIALOG.FOCUS" set-dialog-focus-params / "SET.EXTRACT" set-extract-params / "SET.LIST.ITEM" set-list-item-params / "SET.PAGE.BREAK" set-page-break-params / "SET.PREFERRED" set-preferred-params / "SET.PRINT.AREA" set-print-area-params / "SET.PRINT.TITLES" ["?"] set-print-titles-params / "SET.UPDATE.STATUS" ["?"] set-update-status-params / "SHARE" share-params / "SHARE.NAME" ["?"] share-name-params / "SHEET.BACKGROUND" ["?"] sheet-background-params / "SHORT.MENUS" short-menus-params / "SHOW.ACTIVE.CELL" show-active-cell-params / "SHOW.CLIPBOARD" show-clipboard-params / "SHOW.DETAIL" ["?"] show-detail-params / "SHOW.DIALOG" show-dialog-params / "SHOW.INFO" show-info-params / "SHOW.LEVELS" show-levels-params / "SHOW.TOOLBAR" ["?"] show-toolbar-params / "SORT" ["?"] sort-params / "SORT.SPECIAL" ["?"] sort-special-params / "SOUND.NOTE" sound-note-params / "SOUND.PLAY" sound-play-params / "SPELLING" spelling-params / "SPLIT" ["?"] split-params / "STANDARD.FONT" ["?"] standard-font-params / "STANDARD.WIDTH" ["?"] standard-width-params / "STYLE" ["?"] style-params / "SUBSCRIBE.TO" ["?"] subscribe-to-params / "SUBTOTAL.CREATE" ["?"] subtotal-create-params / "SUBTOTAL.REMOVE" subtotal-remove-params / "SUMMARY.INFO" ["?"] summary-info-params / "TAB.ORDER" ["?"] tab-order-params / "TABLE" ["?"] table-params / "TEXT.TO.COLUMNS" ["?"] text-to-columns-params / "TRACER.CLEAR" tracer-clear-params / "TRACER.DISPLAY" tracer-display-params / "TRACER.ERROR" tracer-error-params / "TRACER.NAVIGATE" tracer-navigate-params / "TRAVERSE.NOTES" traverse-notes-params / "UNDO" undo-params / "UNGROUP" ungroup-params / "UNGROUP.SHEETS" ungroup-sheets-params / "UNHIDE" ["?"] unhide-params / "UNLOCKED.NEXT" unlocked-next-params / "UNLOCKED.PREV" unlocked-prev-params / "UNPROTECT.REVISIONS" unprotect-revisions-params / "UPDATE.LINK" ["?"] update-link-params / "VBA.INSERT.FILE" ["?"] vba-insert-file-params / "VBA.MAKE.ADDIN" ["?"] vba-make-addin-params / "VBA.PROCEDURE.DEFINITION" ["?"] vba-procedure-definition-params / "VBA.ACTIVATE" vbaactivate-params / "VIEW.3D" ["?"] view-3d-params / "VIEW.DEFINE" ["?"] view-define-params / "VIEW.DELETE" view-delete-params / "VIEW.SHOW" ["?"] view-show-params / "VLINE" vline-params / "VPAGE" vpage-params / "VSCROLL" vscroll-params / "WAIT" wait-params / "WEB.PUBLISH" web-publish-params / "WINDOW.MAXIMIZE" window-maximize-params / "WINDOW.MINIMIZE" window-minimize-params / "WINDOW.MOVE" ["?"] window-move-params / "WINDOW.RESTORE" window-restore-params / "WINDOW.SIZE" ["?"] window-size-params / "WORKBOOK.ACTIVATE" workbook-activate-params / "WORKBOOK.ADD" ["?"] workbook-add-params / "WORKBOOK.COPY" ["?"] workbook-copy-params / "WORKBOOK.DELETE" workbook-delete-params / "WORKBOOK.HIDE" workbook-hide-params / "WORKBOOK.INSERT" ["?"] workbook-insert-params / "WORKBOOK.MOVE" ["?"] workbook-move-params / "WORKBOOK.NAME" ["?"] workbook-name-params / "WORKBOOK.NEW" ["?"] workbook-new-params / "WORKBOOK.NEXT" workbook-next-params / "WORKBOOK.OPTIONS" ["?"] workbook-options-params / "WORKBOOK.PREV" workbook-prev-params / "WORKBOOK.PROTECT" ["?"] workbook-protect-params / "WORKBOOK.SCROLL" workbook-scroll-params / "WORKBOOK.SELECT" workbook-select-params / "WORKBOOK.TAB.SPLIT" ["?"] workbook-tab-split-params / "WORKBOOK.UNHIDE" ["?"] workbook-unhide-params / "WORKGROUP" ["?"] workgroup-params / "WORKGROUP.OPTIONS" ["?"] workgroup-options-params / "WORKSPACE" ["?"] workspace-params / "ZOOM" ["?"] zoom-params

al-r1c1-params = "(" argument ")"

activate-params = "(" argument ["," argument] ")"

activate-next-params = "(" argument ")"

activate-notes-params = "(" argument ["," argument] ")"

activate-prev-params = "(" argument ")"

active-cell-font-params = "(" argument *13("," argument) ")"

add-arrow-params = "(" *space ")"

add-chart-autoformat-params = "(" argument ["," argument] ")"

add-list-item-params = "(" argument ["," argument] ")"

add-overlay-params = "(" *space ")"

add-print-area-params = "(" *space ")"

add-tool-params = "(" argument *2("," argument) ")"

addin-manager-params = "(" argument *2("," argument) ")"

alert-params = "(" argument *2("," argument) ")"

alignment-params = "(" argument *9("," argument) ")"

app-activate-params = "(" argument ["," argument] ")"

app-activate-microsoft-params = "(" argument ")"

app-maximize-params = "(" *space ")"

```

app-minimize-params = "(" *space ")"
app-move-params = "(" argument ["," argument] ")"
app-restore-params = "(" *space ")"
app-size-params = "(" argument ["," argument] ")"
apply-names-params = "(" argument *6("," argument) ")"
apply-style-params = "(" argument ")"
arrange-all-params = "(" argument *3("," argument) ")"
assign-to-object-params = "(" argument ")"
assign-to-tool-params = "(" argument *2("," argument) ")"
attach-text-params = "(" argument *2("," argument) ")"
attach-toolbars-params = "(" *space ")"
attributes-params = "(" argument ["," argument] ")"
auto-outline-params = "(" *space ")"
autocorrect-params = "(" argument ["," argument] ")"
axes-params = "(" argument *5("," argument) ")"
beep-params = "(" argument ")"
border-params = "(" argument *26("," argument) ")"
bring-to-front-params = "(" *space ")"
calculate-document-params = "(" *space ")"
calculate-now-params = "(" *space ")"
calculation-params = "(" argument *10("," argument) ")"
cancel-copy-params = "(" argument ")"
cell-protection-params = "(" argument ["," argument] ")"
change-link-params = "(" argument *2("," argument) ")"
chart-add-data-params = "(" argument *5("," argument) ")"
chart-trend-params = "(" argument *7("," argument) ")"
chart-wizard-params = "(" argument *13("," argument) ")"
checkbox-properties-params = "(" argument *4("," argument) ")"
clear-params = "(" argument ")"
clear-outline-params = "(" *space ")"
clear-print-area-params = "(" *space ")"
clear-routing-slip-params = "(" argument ")"
close-params = "(" argument ["," argument] ")"
close-all-params = "(" *space ")"
color-palette-params = "(" argument ")"
column-width-params = "(" argument *4("," argument) ")"
combination-params = "(" argument ")"
consolidate-params = "(" argument *4("," argument) ")"
constrain-numeric-params = "(" argument ")"
copy-params = "(" argument ["," argument] ")"
copy-chart-params = "(" argument ")"
copy-picture-params = "(" argument *2("," argument) ")"
copy-tool-params = "(" argument ["," argument] ")"
create-names-params = "(" argument *3("," argument) ")"
create-publisher-params = "(" argument *3("," argument) ")"
customize-toolbar-params = "(" argument ")"
cut-params = "(" argument ["," argument] ")"
data-delete-params = "(" *space ")"
data-find-params = "(" argument ")"
data-find-next-params = "(" *space ")"
data-find-prev-params = "(" *space ")"
data-form-params = "(" *space ")"
data-label-params = "(" argument *9("," argument) ")"
data-series-params = "(" argument *5("," argument) ")"
define-name-params = "(" argument *6("," argument) ")"
define-style-params = "(" argument *13("," argument) ")"
delete-arrow-params = "(" *space ")"
delete-chart-autoformat-params = "(" argument ")"
delete-format-params = "(" argument ")"

```

```

delete-name-params = "(" argument ")"
delete-note-params = "(" argument ")"
delete-overlay-params = "(" *space ")"
delete-style-params = "(" argument ")"
delete-tool-params = "(" argument ["," argument] ")"
demote-params = "(" argument ")"
disable-input-params = "(" argument ")"
display-params = "(" argument *8("," argument) ")"
duplicate-params = "(" *space ")"
edit-color-params = "(" argument *3("," argument) ")"
edit-delete-params = "(" argument ")"
edit-object-params = "(" argument ")"
edit-repeat-params = "(" *space ")"
edit-series-params = "(" argument *6("," argument) ")"
edit-tool-params = "(" argument ["," argument] ")"
editbox-properties-params = "(" argument *3("," argument) ")"
edition-options-params = "(" argument *6("," argument) ")"
enable-object-params = "(" argument ["," argument] ")"
enable-tipwizard-params = "(" argument ")"
enter-data-params = "(" argument ")"
errorbar-x-params = "(" argument *3("," argument) ")"
errorbar-y-params = "(" argument *3("," argument) ")"
extend-polygon-params = "(" argument ")"
extract-params = "(" argument ")"
file-close-params = "(" argument ["," argument] ")"
file-delete-params = "(" argument ")"
fill-auto-params = "(" argument ["," argument] ")"
fill-down-params = "(" *space ")"
fill-group-params = "(" argument ")"
fill-left-params = "(" *space ")"
fill-right-params = "(" *space ")"
fill-up-params = "(" *space ")"
filter-params = "(" argument *5("," argument) ")"
filter-advanced-params = "(" argument *4("," argument) ")"
filter-show-all-params = "(" *space ")"
find-file-params = "(" *space ")"
font-params = "(" argument ["," argument] ")"
font-properties-params = "(" argument *13("," argument) ")"
format-auto-params = "(" argument *6("," argument) ")"
format-chart-params = "(" argument *17("," argument) ")"
format-charttype-params = "(" argument *3("," argument) ")"
format-font-params = "(" argument *14("," argument) ")"
format-legend-params = "(" argument ")"
format-main-params = "(" argument *13("," argument) ")"
format-move-params = "(" argument *2("," argument) ")"
format-number-params = "(" argument ")"
format-overlay-params = "(" argument *13("," argument) ")"
format-shape-params = "(" argument *4("," argument) ")"
format-size-params = "(" argument *2("," argument) ")"
format-text-params = "(" argument *10("," argument) ")"
formula-params = "(" argument ["," argument] ")"
formula-array-params = "(" argument ["," argument] ")"
formula-fill-params = "(" argument ["," argument] ")"
formula-find-params = "(" argument *11("," argument) ")"
formula-find-next-params = "(" *space ")"
formula-find-prev-params = "(" *space ")"
formula-goto-params = "(" argument ["," argument] ")"
formula-replace-params = "(" argument *10("," argument) ")"
freeze-panes-params = "(" argument *2("," argument) ")"

```

```

full-params = "(" argument ")"
full-screen-params = "(" argument ")"
function-wizard-params = "(" argument ")"
gallery-3d-area-params = "(" argument ")"
gallery-3d-bar-params = "(" argument ")"
gallery-3d-column-params = "(" argument ")"
gallery-3d-line-params = "(" argument ")"
gallery-3d-pie-params = "(" argument ")"
gallery-3d-surface-params = "(" argument ")"
gallery-area-params = "(" argument ["," argument] ")"
gallery-bar-params = "(" argument ["," argument] ")"
gallery-column-params = "(" argument ["," argument] ")"
gallery-custom-params = "(" argument ")"
gallery-doughnut-params = "(" argument ["," argument] ")"
gallery-line-params = "(" argument ["," argument] ")"
gallery-pie-params = "(" argument ["," argument] ")"
gallery-radar-params = "(" argument ["," argument] ")"
gallery-scatter-params = "(" argument ["," argument] ")"
goal-seek-params = "(" argument *2("," argument) ")"
gridlines-params = "(" argument *6("," argument) ")"
hide-params = "(" *space ")"
hide-dialog-params = "(" argument ")"
hide-object-params = "(" argument ["," argument] ")"
hideall-inkannots-params = "(" argument ")"
hideall-notes-params = "(" argument ")"
hidecurr-note-params = "(" argument ["," argument] ")"
hline-params = "(" argument ")"
hpage-params = "(" argument ")"
hscroll-params = "(" argument ["," argument] ")"
insert-params = "(" argument ["," argument] ")"
insert-map-object-params = "(" *space ")"
insert-object-params = "(" argument *12("," argument) ")"
insert-picture-params = "(" argument ["," argument] ")"
insert-title-params = "(" argument *4("," argument) ")"
insertdatatable-params = "(" argument ")"
justify-params = "(" *space ")"
label-properties-params = "(" argument *2("," argument) ")"
layout-params = "(" *space ")"
legend-params = "(" argument ")"
line-print-params = "(" argument *10("," argument) ")"
link-combo-params = "(" argument ")"
link-format-params = "(" *space ")"
list-names-params = "(" *space ")"
listbox-properties-params = "(" argument *4("," argument) ")"
macro-options-params = "(" argument *9("," argument) ")"
mail-add-mailer-params = "(" *space ")"
mail-delete-mailer-params = "(" *space ")"
mail-edit-mailer-params = "(" argument *5("," argument) ")"
mail-forward-params = "(" *space ")"
mail-logoff-params = "(" *space ")"
mail-logon-params = "(" argument *2("," argument) ")"
mail-next-letter-params = "(" *space ")"
mail-reply-params = "(" *space ")"
mail-reply-all-params = "(" *space ")"
mail-send-mailer-params = "(" argument ["," argument] ")"
main-chart-params = "(" argument *9("," argument) ")"
main-chart-type-params = "(" argument ")"
menu-editor-params = "(" *space ")"
merge-styles-params = "(" argument ")"

```

```

message-params = "(" argument ["," argument] ")"
move-brk-params = "(" argument *3("," argument) ")"
move-tool-params = "(" argument *5("," argument) ")"
new-params = "(" argument *2("," argument) ")"
new-window-params = "(" *space ")"
newwebquery-params = "(" argument ")"
normal-params = "(" *space ")"
object-properties-params = "(" argument ["," argument] ")"
object-protection-params = "(" argument ["," argument] ")"
on-data-params = "(" argument ["," argument] ")"
on-doubleclick-params = "(" argument ["," argument] ")"
on-entry-params = "(" argument ["," argument] ")"
on-key-params = "(" argument ["," argument] ")"
on-recalc-params = "(" argument ["," argument] ")"
on-sheet-params = "(" argument *2("," argument) ")"
on-time-params = "(" argument *3("," argument) ")"
on-window-params = "(" argument ["," argument] ")"
open-params = "(" argument *16("," argument) ")"
open-links-params = "(" argument *14("," argument) ")"
open-mail-params = "(" argument ["," argument] ")"
open-text-params = "(" argument *16("," argument) ")"
options-calculation-params = "(" argument *9("," argument) ")"
options-chart-params = "(" argument *2("," argument) ")"
options-edit-params = "(" argument *10("," argument) ")"
options-general-params = "(" argument *13("," argument) ")"
options-lists-add-params = "(" argument ["," argument] ")"
options-lists-delete-params = "(" argument ")"
options-me-params = "(" argument *8("," argument) ")"
options-menono-params = "(" argument *4("," argument) ")"
options-save-params = "(" argument *3("," argument) ")"
options-spell-params = "(" argument *11("," argument) ")"
options-transition-params = "(" argument *4("," argument) ")"
options-view-params = "(" argument *17("," argument) ")"
outline-params = "(" argument *3("," argument) ")"
overlay-params = "(" argument *11("," argument) ")"
overlay-chart-type-params = "(" argument ")"
page-setup-params = "(" argument *29("," argument) ")"
parse-params = "(" argument ["," argument] ")"
paste-params = "(" argument ")"
paste-link-params = "(" *space ")"
paste-picture-params = "(" *space ")"
paste-picture-link-params = "(" *space ")"
paste-special-params = "(" argument *6("," argument) ")"
paste-tool-params = "(" argument ["," argument] ")"
patterns-params = "(" argument *12("," argument) ")"
picklist-params = "(" *space ")"
pivot-add-fields-params = "(" argument *4("," argument) ")"
pivot-field-params = "(" argument *3("," argument) ")"
pivot-field-group-params = "(" argument *3("," argument) ")"
pivot-field-properties-params = "(" argument *6("," argument) ")"
pivot-field-ungroup-params = "(" *space ")"
pivot-item-params = "(" argument *3("," argument) ")"
pivot-item-properties-params = "(" argument *6("," argument) ")"
pivot-refresh-params = "(" argument ")"
pivot-show-pages-params = "(" argument ["," argument] ")"
pivot-table-chart-params = "(" argument *15("," argument) ")"
pivot-table-wizard-params = "(" argument *15("," argument) ")"
post-document-params = "(" argument ")"
precision-params = "(" argument ")"

```

```

preferred-params = "(" *space ")"
print-params = "(" argument *16(" argument) )"
print-preview-params = "(" argument ")"
printer-setup-params = "(" argument ")"
promote-params = "(" argument ")"
protect-document-params = "(" argument *6(" argument) )"
protect-revisions-params = "(" *space ")"
pushbutton-properties-params = "(" argument *5(" argument) )"
quit-params = "(" *space ")"
remove-list-item-params = "(" argument [," argument] )"
remove-page-break-params = "(" argument [," argument] )"
rename-object-params = "(" argument ")"
replace-font-params = "(" argument *9(" argument) )"
reset-tool-params = "(" argument [," argument] )"
rm-print-area-params = "(" argument ")"
route-document-params = "(" *space ")"
routing-slip-params = "(" argument *5(" argument) )"
row-height-params = "(" argument *3(" argument) )"
run-params = "(" argument [," argument] )"
save-params = "(" *space ")"
save-as-params = "(" argument *6(" argument) )"
save-copy-as-params = "(" argument ")"
save-new-object-params = "(" argument ")"
save-workbook-params = "(" argument *5(" argument) )"
save-workspace-params = "(" argument ")"
scale-params = "(" argument *9(" argument) )"
scenario-add-params = "(" argument *5(" argument) )"
scenario-cells-params = "(" argument ")"
scenario-delete-params = "(" argument ")"
scenario-edit-params = "(" argument *6(" argument) )"
scenario-merge-params = "(" argument ")"
scenario-show-params = "(" argument ")"
scenario-show-next-params = "(" *space ")"
scenario-summary-params = "(" argument [," argument] )"
scrollbar-properties-params = "(" argument *6(" argument) )"
select-params = "(" argument [," argument] )"
select-all-params = "(" *space ")"
select-chart-params = "(" *space ")"
select-end-params = "(" argument ")"
select-last-cell-params = "(" *space ")"
select-list-item-params = "(" argument [," argument] )"
select-plot-area-params = "(" *space ")"
select-special-params = "(" argument *2(" argument) )"
send-keys-params = "(" argument [," argument] )"
send-mail-params = "(" argument *2(" argument) )"
send-to-back-params = "(" *space ")"
series-axes-params = "(" argument ")"
series-order-params = "(" argument *2(" argument) )"
series-x-params = "(" argument ")"
series-y-params = "(" argument [," argument] )"
set-control-value-params = "(" argument ")"
set-criteria-params = "(" *space ")"
set-database-params = "(" *space ")"
set-dialog-default-params = "(" argument ")"
set-dialog-focus-params = "(" argument ")"
set-extract-params = "(" *space ")"
set-list-item-params = "(" argument [," argument] )"
set-page-break-params = "(" *space ")"
set-preferred-params = "(" argument ")"

```



```

set-print-area-params = "(" argument ")"
set-print-titles-params = "(" argument ["," argument] ")"
set-update-status-params = "(" argument *2("," argument) ")"
share-params = "(" *space ")"
share-name-params = "(" argument ")"
sheet-background-params = "(" argument ["," argument] ")"
short-menus-params = "(" argument ")"
show-active-cell-params = "(" *space ")"
show-clipboard-params = "(" *space ")"
show-detail-params = "(" argument *3("," argument) ")"
show-dialog-params = "(" argument ")"
show-info-params = "(" argument ")"
show-levels-params = "(" argument ["," argument] ")"
show-toolbar-params = "(" argument *9("," argument) ")"
sort-params = "(" argument *16("," argument) ")"
sort-special-params = "(" argument *13("," argument) ")"
sound-note-params = "(" argument *2("," argument) ")"
sound-play-params = "(" argument *2("," argument) ")"
spelling-params = "(" argument *5("," argument) ")"
split-params = "(" argument ["," argument] ")"
standard-font-params = "(" argument *8("," argument) ")"
standard-width-params = "(" argument ")"
style-params = "(" argument ["," argument] ")"
subscribe-to-params = "(" argument ["," argument] ")"
subtotal-create-params = "(" argument *5("," argument) ")"
subtotal-remove-params = "(" *space ")"
summary-info-params = "(" argument *4("," argument) ")"
tab-order-params = "(" *space ")"
table-params = "(" argument ["," argument] ")"
text-to-columns-params = "(" argument *13("," argument) ")"
tracer-clear-params = "(" *space ")"
tracer-display-params = "(" argument ["," argument] ")"
tracer-error-params = "(" *space ")"
tracer-navigate-params = "(" argument *2("," argument) ")"
traverse-notes-params = "(" argument ["," argument] ")"
undo-params = "(" *space ")"
ungroup-params = "(" *space ")"
ungroup-sheets-params = "(" *space ")"
unhide-params = "(" argument ")"
unlocked-next-params = "(" *space ")"
unlocked-prev-params = "(" *space ")"
unprotect-revisions-params = "(" *space ")"
update-link-params = "(" argument ["," argument] ")"
vba-insert-file-params = "(" argument ")"
vba-make-addin-params = "(" argument ")"
vba-procedure-definition-params = "(" *space ")"
vbaactivate-params = "(" argument ["," argument] ")"
view-3d-params = "(" argument *5("," argument) ")"
view-define-params = "(" argument *2("," argument) ")"
view-delete-params = "(" argument ")"
view-show-params = "(" argument ")"
vline-params = "(" argument ")"
vpage-params = "(" argument ")"
vscroll-params = "(" argument ["," argument] ")"
wait-params = "(" argument ")"
web-publish-params = "(" argument *8("," argument) ")"
window-maximize-params = "(" argument ")"
window-minimize-params = "(" argument ")"
window-move-params = "(" argument *2("," argument) ")"

```

```

window-restore-params = "(" argument ")"
window-size-params = "(" argument *2("," argument) ")"
workbook-activate-params = "(" argument ["," argument] ")"
workbook-add-params = "(" argument *2("," argument) ")"
workbook-copy-params = "(" argument *2("," argument) ")"
workbook-delete-params = "(" argument ")"
workbook-hide-params = "(" argument ["," argument] ")"
workbook-insert-params = "(" argument ")"
workbook-move-params = "(" argument *2("," argument) ")"
workbook-name-params = "(" argument ["," argument] ")"
workbook-new-params = "(" argument *2("," argument) ")"
workbook-next-params = "(" *space ")"
workbook-options-params = "(" argument *2("," argument) ")"
workbook-prev-params = "(" *space ")"
workbook-protect-params = "(" argument *2("," argument) ")"
workbook-scroll-params = "(" argument ["," argument] ")"
workbook-select-params = "(" argument *2("," argument) ")"
workbook-tab-split-params = "(" argument ")"
workbook-unhide-params = "(" argument ")"
workgroup-params = "(" argument ")"
workgroup-options-params = "(" *space ")"
workspace-params = "(" argument *15("," argument) ")"
zoom-params = "(" argument ")"

```

2.2.2.1 Cell Formulas

A **cell** formula is a **formula** that adheres to the grammar specified in section [2.2.2](#), with the following restrictions:

- The formula MUST NOT use the bang-reference or bang-name production rules.

All **f** elements of **CT_Cell** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, and all **calculatedColumnFormula** and **totalsRowFormula** elements of **CT_TableColumn** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, are cell formulas.

2.2.2.2 Conditional Formatting Formulas

A **conditional formatting** formula is a formula that adheres to the grammar specified in section [2.2.2](#), with the following restrictions:

- The formula MUST NOT use the union-operator, intersection-operator, range-operator, bang-reference, bang-name, array-constant, external-cell-reference, or structure-reference production rules.

All **val attributes (1)** of **CT_Cfvo** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, and all **formula** elements of **CT_CfRule** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, are conditional formatting formulas.

2.2.2.3 Data Validation Formulas

A **data validation** formula is a formula that adheres to the grammar specified in section [2.2.2](#), with the following restrictions:

- The formula MUST NOT use the union-operator, intersection-operator, range-operator, bang-reference, bang-name, array-constant, sheet-range-reference, or structure-reference production rules.

All **formula1** and **formula2** elements of **CT_DataValidation** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, are data validation formulas.

2.2.2.4 External Name Formulas

An external name formula is a formula that adheres to the following grammar:

```
external-name-formula = ref-constant / sheet-range-reference / single-sheet-reference
```

When matching the single-sheet or sheet-range rules for an external name formula, the optional workbook-index in those rules MUST NOT be omitted.

All **refersTo** attributes of **CT_ExternalDefinedName** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, are external name formulas.

2.2.2.5 Name Formulas

A name formula is a formula that adheres to the grammar specified in section [2.2.2](#), with the following differences.

For name formulas, the function-call rule is expanded as follows:

```
function-call =/ (macro-function-call / command-function-call)
```

The formula MUST NOT use the local-cell-reference production rule.

All **formula** and **oldFormula** elements of **CT_RevisionDefinedName** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, and all **definedName** elements of **CT_DefinedNames** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, are name formulas.

2.2.2.6 Pivot Field Formulas

A pivot field (1) formula is a formula that adheres to the grammar specified in section [2.2.2](#), with the following differences.

For pivot field (1) formulas, the nospace-expression rule is expanded as follows:

```
nospace-expression =/ pivot-field-name  
pivot-field-name = name / apostrophe 1*pivot-field-string-character apostrophe  
pivot-field-string-character = apostrophe apostrophe / pivot-field-character  
pivot-field-character = character ; MUST NOT be apostrophe
```

The formula MUST NOT use the ref-infix-operator, array-constant, getpivotdata-params, dcount-params, dcounta-params, dsum-params, daverage-params, dmin-params, dmax-params, dproduct-params, dstdev-params, dstdevp-params, dvar-params, dvarp-params, index-params, rand-params, now-params, areas-params, rows-params, columns-params, offset-params, cell-params, index-params, today-params, info-params, or randbetween-params production rules.

A name used in a pivot field (1) formula MUST NOT have any of the following forms:

- All
- Blank

All **formula** attributes of **CT_CacheField** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, are pivot field (1) formulas.

2.2.2.7 Pivot Item Formulas

A pivot item formula is a formula that adheres to the grammar specified in section [2.2.2](#), with the following differences.

For pivot item formulas, the nospace-expression rule is expanded as follows:

```
nospace-expression =/ pivot-items
pivot-items = pivot-item space *(*whitespace pivot-item)
pivot-item = pivot-field-name / pivot-field-name "[" pivot-item-value "]"
pivot-item-value = pivot-field-name / [sign] whole-number-part
```

The formula MUST NOT use the ref-infix-operator, array-constant, getpivotdata-params, dcount-params, dcounta-params, dsum-params, daverage-params, dmin-params, dmax-params, dproduct-params, dstdev-params, dstdevp-params, dvar-params, dvarp-params, index-params, rand-params, now-params, areas-params, rows-params, columns-params, offset-params, cell-params, index-params, today-params, info-params, or randbetween-params production rules.

A name used in a pivot item formula MUST NOT have any of the following forms:

- All
- Blank

All **formula** attributes of **CT_CalculatedItem** elements, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, are pivot item formulas.

2.2.3 Functions

The predefined functions ([\[ISO/IEC29500-1:2011\]](#) section 18.17.7) are extended by the following **future functions**.

Future function
_xlfn.ACOT
_xlfn.ACOTH
_xlfn.AGGREGATE
_xlfn.ARABIC
_xlfn.BASE
_xlfn.BETA.DIST
_xlfn.BETA.INV
_xlfn.BINOM.DIST
_xlfn.BINOM.DIST.RANGE
_xlfn.BINOM.INV

Future function
_xln.BITAND
_xln.BITLSHIFT
_xln.BITOR
_xln.BITRSHIFT
_xln.BITXOR
_xln.CEILING.MATH
_xln.CEILING.PRECISE
_xln.CHISQ.DIST
_xln.CHISQ.DIST.RT
_xln.CHISQ.INV
_xln.CHISQ.INV.RT
_xln.CHISQ.TEST
_xln.COMBINA
_xln.CONFIDENCE.NORM
_xln.CONFIDENCE.T
_xln.COT
_xln.COTH
_xln.COVARANCE.P
_xln.COVARANCE.S
_xln.CSC
_xln.CSCH
_xln.DAYS
_xln.DECIMAL
ECMA.CEILING
_xln.ERF.PRECISE
_xln.ERFC.PRECISE
_xln.EXPON.DIST
_xln.F.DIST
_xln.F.DIST.RT
_xln.F.INV

Future function
_xlfn.F.INV.RT
_xlfn.F.TEST
_xlfn.FILTERXML
_xlfn.FLOOR.MATH
_xlfn.FLOOR.PRECISE
_xlfn.FORMULATEXT
_xlfn.GAMMA
_xlfn.GAMMA.DIST
_xlfn.GAMMA.INV
_xlfn.GAMMALN.PRECISE
_xlfn.GAUSS
_xlfn.HYPGEOM.DIST
_xlfn.IFNA
_xlfn.IMCOSH
_xlfn.IMCOT
_xlfn.IMCSC
_xlfn.IMCSCH
_xlfn.IMSEC
_xlfn.IMSECH
_xlfn.IMSINH
_xlfn.IMTAN
_xlfn.ISFORMULA
ISO.CEILING
_xlfn.ISOWEEKNUM
_xlfn.LOGNORM.DIST
_xlfn.LOGNORM.INV
_xlfn.MODE.MULT
_xlfn.MODE.SNGL
_xlfn.MUNIT
_xlfn.NEGBINOM.DIST

Future function
NETWORKDAYS.INTL
_xlnf.NORM.DIST
_xlnf.NORM.INV
_xlnf.NORM.S.DIST
_xlnf.NORM.S.INV
_xlnf.NUMBERVALUE
_xlnf.PDURATION
_xlnf.PERCENTILE.EXC
_xlnf.PERCENTILE.INC
_xlnf.PERCENTRANK.EXC
_xlnf.PERCENTRANK.INC
_xlnf.PERMUTATIONA
_xlnf.PHI
_xlnf.POISSON.DIST
_xlnf.QUARTILE.EXC
_xlnf.QUARTILE.INC
_xlnf.QUERYSTRING
_xlnf.RANK.AVG
_xlnf.RANK.EQ
_xlnf.RRI
_xlnf.SEC
_xlnf.SECH
_xlnf.SHEET
_xlnf.SHEETS
_xlnf.SKEW.P
_xlnf.STDEV.P
_xlnf.STDEV.S
_xlnf.T.DIST
_xlnf.T.DIST.2T
_xlnf.T.DIST.RT

Future function
_xlfn.T.INV
_xlfn.T.INV.2T
_xlfn.T.TEST
_xlfn.UNICHAR
_xlfn.UNICODE
_xlfn.VAR.P
_xlfn.VAR.S
_xlfn.WEBSERVICE
_xlfn.WEIBULL.DIST
WORKDAY.INTL
_xlfn.XOR
_xlfn.Z.TEST

The function syntax ([\[ISO/IEC29500-1:2011\]](#) section 18.17.2.4) is extended by changing the function-name rule to:

```
function-name =
    prefixed-function-name |
    predefined-function-name |
    user-defined-function-name |
    future-function-list;
```

The [future-function-list](#) rule is found in the Formulas grammar.

2.2.4 Extensions by Part

This section specifies the elements from Office Open XML file formats as specified in [\[ISO/IEC29500-1:2011\]](#) that are extended by this format. Either the **Ignorable** attribute ([\[ISO/IEC29500-3:2011\]](#) section 10.1.1), **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1), or the **extLst** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) MUST be used to maintain compatibility with Office Open XML file formats implementations as specified in [\[ISO/IEC29500:2011\]](#).

2.2.4.1 Connections

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **connection** element ([\[ISO/IEC29500-1:2011\]](#) section 18.13.1) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{D79990A0-CA42-45E3-83F4-45C500A0EAA5}	connection
{DE250136-89BD-433C-8126-D09CA5730AF9}	connection

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more details about how extension lists are used.

2.2.4.2 Drawing

The **oneCellAnchor** element ([\[ISO/IEC29500-1:2011\]](#) section 20.5.2.24) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/drawingml/2010/slicer	slicer
Fallback	sp ([ISO/IEC29500-1:2011] section 20.5.2.29)

The **twoCellAnchor** element ([\[ISO/IEC29500-1:2011\]](#) section 20.5.2.33) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/drawingml/2010/slicer	slicer
Fallback	sp ([ISO/IEC29500-1:2011] section 20.5.2.29)

The **grpSp** element ([\[ISO/IEC29500-1:2011\]](#) section 20.5.2.17) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/drawingml/2010/slicer	slicer
Fallback	sp ([ISO/IEC29500-1:2011] section 20.5.2.29)

The **absoluteAnchor** element ([\[ISO/IEC29500-1:2011\]](#) section 20.5.2.1) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/drawingml/2010/slicer	slicer
Fallback	sp

AlternateContent components	Child element
	[ISO/IEC29500-1:2011] section 20.5.2.29

2.2.4.3 External Workbook References

The **oleItems** element ([\[ISO/IEC29500-1:2011\]](#) section 18.14.10) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	oleItem
Fallback	oleItem ([ISO/IEC29500-1:2011] section 18.14.9)

2.2.4.4 Pivot Table

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **pivotTableDefinition** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.73) is extended by the addition of new child **ext** elements ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{962EF5D1-5CA2-4C93-8EF4-DBF5C05439D2}	pivotTableDefinition
{44433962-1CF7-4059-B4EE-95C3D5FFCF73}	pivotTableData
{C510F80B-63DE-4267-81D5-13C33094786E}	pivotTableServerFormats
{E67621CE-5B39-4880-91FE-76760E9C1902}	pivotTableUISettings

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **pivotField** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.69) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{2946ED86-A175-432A-8AC1-64E0C546D7DE}	pivotField

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **dataField** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.22) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{E15A36E0-9728-4E99-A89B-3F7291B0FE68}	dataField

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **pivotHierarchy** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.72) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{F1805F06-0CD304483-9156-8803C3D141DF}	pivotHierarchy

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **filterColumn** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.7) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	iconFilter
Fallback	customFilters ([ISO/IEC29500-1:2011] section 18.3.2.3)

The **filterColumn** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.7) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	customFilters
Fallback	Either customFilters ([ISO/IEC29500-1:2011] section 18.3.2.3) or none

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **filterColumn** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.7) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	filter
Fallback	customFilters ([ISO/IEC29500-1:2011] section 18.3.2.3)

The **filters** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.8) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	filter
Fallback	Either filter ([ISO/IEC29500-1:2011] section 18.3.2.6) or none

The **sortState** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.92) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	sortCondition
Fallback	sortCondition ([ISO/IEC29500-1:2011] section 18.3.1.91)

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **filter** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.33) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{0605FD5F-26C8-4aeb-8148-2DB25E43C511}	pivotFilter

2.2.4.5 Pivot Table Cache Definition

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **pivotCacheDefinition** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.67) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{725AE2AE-9491-48BE-B2B4-4EB974FC3084}	pivotCacheDefinition
{79D8C58B-0C89-4175-8D82-1AF69EB9B54B}	pivotCacheDecoupled
{5DA0FC9A-693D-419c-AD59-312A39285967}	timelinePivotCacheDefinition
{ABF5C744-AB39-4b91-8756-CFA1BBC848D5}	pivotCacheIdVersion

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **cacheField** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.3) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{63CAB8AC-B538-458D-9797-405883B0398D}	cacheField
{4F2E5C28-24EA-4EB8-9CBF-B6C8F9C3D259}	cachedUniqueNames

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **cacheHierarchy** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.6) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{8CF416AD-EC4C-4ABA-99F5-12A058AE0983}	cacheHierarchy
{B97F6D7D-B522-45F9-BDA1-12C45D357490}	cacheHierarchy

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **calculatedMember** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.10) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{0C70D0D5-359C-4A49-802D-23BBF952B5CE}	calculatedMember
{57DEB092-E4DC-418E-9C9A-C0C97F8552CB}	calculatedMember

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **cacheSource** element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.7) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{F057638F-6D5F-4E77-A914-E7F072B9BCA8}	sourceConnection

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

2.2.4.6 Query Table

The **sortState** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.92) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	sortCondition
Fallback	sortCondition ([ISO/IEC29500-1:2011] section 18.3.1.91)

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **queryTable** element ([\[ISO/IEC29500-1:2011\]](#) section 18.12.2) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{883FBD77-0823-4A55-B5E3-86C4891E6966}	queryTable

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

2.2.4.7 Styles

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **styleSheet** element ([\[ISO/IEC29500-1:2011\]](#) section 18.8.39) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{EB79DEF2-80B8-43E5-95BD-54CBDDF9020C}	slicerStyles
{46F421CA-312F-682F-3DD2-61675219B42D}	dxfs

Ext URI	Child element
{9260A510-F301-46a8-8635-F512D64BE5F5}	timelineStyles
{A0A4C193-F2C1-4fcb-8827-314CF55A85BB}	dxfs

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **font** element ([\[ISO/IEC29500-1:2011\]](#) section 18.8.22) is extended by the addition of a [knownFonts](#) attribute. To maintain compatibility with implementations of Office Open XML file formats as specified in [\[ISO/IEC29500:2011\]](#), the namespace prefix of the attribute MUST be specified as an **Ignorable** attribute ([\[ISO/IEC29500-3:2011\]](#) section 10.1.1).

2.2.4.8 SlicerCache

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **slicerCacheDefinition** element (section [2.4.38](#)) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{03082B11-2C62-411c-B77F-237D8FCFBE4C}	slicerCachePivotTables
{2F2917AC-EB37-4324-AD4E-5DD8C200BD13}	tableSlicerCache
{470722E0-AACD-4C17-9CDC-17EF765DBC7E}	slicerCacheHideItemsWithNoData

2.2.4.9 Table Definition

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **table** element ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{504A1906-F514-4F6F-8877-14C23A59335A}	table

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **filterColumn** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.7) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	iconFilter
Fallback	customFilters

AlternateContent components	Child element
	([ISO/IEC29500-1:2011] section 18.3.2.3)

The **filterColumn** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.7) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	customFilters
Fallback	Either customFilters ([ISO/IEC29500-1:2011] section 18.3.2.3) or none

The **filterColumn** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.7) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	filters ([ISO/IEC29500-1:2011] section 18.3.2.8) such that instead of any child filter ([ISO/IEC29500-1:2011] section 18.3.2.6) elements, there are filter elements
Fallback	customFilters ([ISO/IEC29500-1:2011] section 18.3.2.3)

The **filters** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.8) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	filter
Fallback	Either filter ([ISO/IEC29500-1:2011] section 18.3.2.6) or none

The **sortState** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.92) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	sortCondition
Fallback	sortCondition ([ISO/IEC29500-1:2011] section 18.3.1.91)

2.2.4.10 Workbook

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **workbook** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.27) is extended by the addition of new child **ext** elements ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{876F7934-8845-4945-9796-88D515C7AA90}	pivotCaches
{BBE1A952-AA13-448E-AADC-164F8A28A991}	slicerCaches
{79F54976-1DA5-4618-B147-ACDE4B953A38}	workbookPr
{841E416B-1EF1-43b6-AB56-02D37102CBD5}	pivotCaches
{983426D0-5260-488c-9760-48F4B6AC55F4}	pivotTableReferences
{A2CB5862-8E78-49c6-8D9D-AF26E26ADB89}	timelineCachePivotCaches
{D0CA8CA8-9F24-4464-BF8E-62219DCF47F9}	timelineCacheRefs
{140A7094-0E35-4892-8432-C4D2E57EDEB5}	workbookPr
{FCE2AD5D-F65C-4FA6-A056-5C36A1767C68}	dataModel

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

2.2.4.11 Worksheet

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **worksheet** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.99) is extended by the addition of new child **ext** elements ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{78C0D931-6437-407D-A8EE-F0AAD7539E65}	conditionalFormattings
{CCE6A557-97BC-4B89-ADB6-D9C93CAAB3DF}	dataValidations
{05C60535-1F16-4FD2-B633-F4F36F0B64E0}	sparklineGroups
{A8765BA9-456A-4DAB-B4F3-ACF838C121DE}	slicerList
{FC87AEE6-9EDD-4A0A-B7FB-166176984837}	protectedRanges

Ext URI	Child element
{01252117-D84E-4E92-8308-4BE1C098FCBB}	ignoredErrors
{F7C9EE02-42E1-4005-9D12-6889AFFD525C}	webExtensions
{3A4CF648-6AED-40f4-86FF-DC5316D8AED3}	slicerList
{7E03D99C-DC04-49d9-9315-930204A7B6E9}	timelineRefs

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **extLst** child element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.10) of the **cfRule** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.10) is extended by the addition of a new child **ext** element ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) whose structure is specified in the following table.

Ext URI	Child element
{B025F937-C7B1-47D3-B67F-A62EFF666E3E}	id

See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The **sheetFormatPr** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.81) is extended by the addition of a [dyDescent](#) attribute. To maintain compatibility with Office Open XML file formats implementations as specified in [\[ISO/IEC29500:2011\]](#), the namespace prefix of the attribute MUST be specified as an **Ignorable** attribute ([\[ISO/IEC29500-3:2011\]](#) section 10.1.1).

The **row** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.73) is extended by the addition of a [dyDescent](#) attribute. To maintain compatibility with Office Open XML file formats implementations as specified in [\[ISO/IEC29500:2011\]](#), the namespace prefix of the attribute MUST be specified as an **Ignorable** attribute ([\[ISO/IEC29500-3:2011\]](#) section 10.1.1).

The **sortState** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.92) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	sortCondition
Fallback	sortCondition ([ISO/IEC29500-1:2011] section 18.3.1.91)

The **filterColumn** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.7) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	iconFilter
Fallback	customFilters ([ISO/IEC29500-1:2011] section 18.3.2.3)

The **filterColumn** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.7) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	customFilters
Fallback	Either customFilters ([ISO/IEC29500-1:2011] section 18.3.2.3) or none

The **filterColumn** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.7) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	filters ([ISO/IEC29500-1:2011] section 18.3.2.8) such that instead of child filter ([ISO/IEC29500-1:2011] section 18.3.2.6) elements, there are filter elements
Fallback	customFilters ([ISO/IEC29500-1:2011] section 18.3.2.3)

The **filters** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.8) is extended by the addition of a child **AlternateContent** element ([\[ISO/IEC29500-3:2011\]](#) section 10.2.1) whose structure is specified in the following table.

AlternateContent components	Child element
Choice: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main	filter
Fallback	Either filter ([ISO/IEC29500-1:2011] section 18.3.2.6) or none

2.3 Conceptual Overview

This section specifies how higher-level features of the file format are represented by combinations of low-level structures.

2.3.1 PivotTable What-if Analysis

PivotTable what-if analysis enables the editing of summarized values in an **OLAP** PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view, for example, editing summarized values in the PivotTable data area of the PivotTable view.

A **CT_PivotEdits** element, as specified in section [2.6.37](#), and its child **CT_PivotEdit** elements, as specified in section [2.6.38](#), specify the values in the OLAP PivotTable view that have been modified and the corresponding values in the OLAP PivotTable **source data**. The **CT_PivotUserEdit** child element, as specified in section [2.6.41](#), of the **CT_PivotEdit** element specifies a value or a formula. The location of the modified value in the OLAP PivotTable view is specified by a PivotTable rule specified by the **CT_PivotArea** element ([\[ISO/IEC29500-4:2011\]](#) section A.2) in this **CT_PivotEdit** element. The **OLAP tuple** that identifies the corresponding value in the OLAP PivotTable source data is specified by the **CT_TupleItems** element, as specified in section [2.6.43](#), in this **CT_PivotEdit** element.

A **CT_PivotChanges** element, as specified in section [2.6.39](#), and its child **CT_PivotChange** elements, as specified in section [2.6.40](#), specify the values in the OLAP PivotTable view that have been designated for **OLAP allocation** and the corresponding values in the OLAP PivotTable source data. The order of the **CT_PivotChange** elements determines the order in which they are designated for OLAP allocation. The **CT_PivotChange** element specifies a single edited value designated for OLAP allocation. An OLAP allocation value is specified by the **CT_PivotEditValue** child element, as specified in section [2.6.42](#), of the **CT_PivotChange** element. The **allocationMethod** attribute of the **CT_PivotChange** element specifies the OLAP allocation method. The OLAP tuple that identifies the location of the edited value in the OLAP PivotTable view and the corresponding value in the OLAP PivotTable source data is specified by the **CT_TupleItems** child element of the **CT_PivotChange** element.

For example, when an OLAP PivotTable is refreshed, the values designated for OLAP allocation, specified by the **CT_PivotChanges** element and its child **CT_PivotChange** elements, are sent to the OLAP **data provider** along with the OLAP allocation method indicating how to allocate the updated values. The OLAP data provider updates the values, and those new values are then refreshed and summarized in the data area of the PivotTable view, instead of summarizing the original values from the OLAP PivotTable source data.

If the **enableEdit** attribute of the **CT_PivotTableDefinition** element, as specified in section [2.6.32](#), is "false", **CT_PivotEdits** and **CT_PivotChanges** elements MUST NOT exist in this part. PivotTable what-if analysis is enabled if, and only if, the **enableEdit** attribute of the **CT_PivotTableDefinition** element is "true" and the PivotTable source data is OLAP.

2.3.2 Slicers

A slicer is a mechanism for filtering data in PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views, **cube functions**, **tables** ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2) and Charts ([\[ISO/IEC29500-1:2011\]](#) section 21.2) based on [Non-Worksheet PivotTables](#). A slicer is based on a field (1) in the [slicer source data](#), and the slicer filters on distinct values in that column (2). In the case of using OLAP slicer source data, a slicer is based on an **OLAP hierarchy**.

A slicer has two major parts, a [slicer cache](#) and a [slicer view](#). There can be more than one slicer view based on a single slicer cache. When filtering multi-level OLAP hierarchies using slicers, separate slicer views are used for each **OLAP level**.

2.3.2.1 Slicer Cache

A slicer cache specifies the subset of [slicer source data](#) that is cached for display in [slicer views](#), as well as properties related to [slicer](#) filtering. A slicer cache is specified by the [CT_SlicerCacheDefinition](#) element.

A slicer cache has an associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache as specified in section [2.3.2.1.2](#), or **Table** ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2).

If the slicer source data is an OLAP **data source (1)**, the **sourceName** attribute of the **CT_SlicerCacheDefinition** element specifies the **MDX unique name** of the associated OLAP hierarchy.

If the slicer source data is a non-OLAP data source (1), the **sourceName** attribute of the **CT_SlicerCacheDefinition** element specifies the associated PivotTable cache field (1) of the associated PivotTable **PivotCache**.

If the slicer source data is a table data source (1), the **sourceName** attribute of the **CT_SlicerCacheDefinition** element specifies the associated table field (1).

If the slicer is used to **filter** PivotTable views, the slicer cache specifies the PivotTable views being filtered as specified in section [2.3.2.1.4](#).

2.3.2.1.1 Slicer Source Data

The source data for a [slicer](#) is specified by the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache as specified in [Slicer Cache Relationship to PivotCache](#), or **Table** ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2) as specified in [Slicer Cache Relationship to Table](#).

2.3.2.1.2 Slicer Cache Relationship to PivotCache

A [slicer cache](#) can be associated with a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache. The association is specified by the following rules:

- If the [CT_SlicerCacheDefinition](#) element has a child [CT_SlicerCacheData](#) element with a child [CT_OlapSlicerCache](#) element, then the type of [slicer source data](#) is OLAP and the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache of the slicer cache is specified by the **pivotCacheId** attribute of the [CT_OlapSlicerCache](#) element. The associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache MUST be based on an OLAP connection ([\[ISO/IEC29500-1:2011\]](#) section 18.13.5). The **slicerData** attribute of the [CT_PivotCacheDefinition](#) element MUST be "true".
- If the [CT_SlicerCacheDefinition](#) element has a child [CT_SlicerCacheData](#) element with a child [CT_TabularSlicerCache](#) element, the type of slicer source data is non-OLAP and the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache of the slicer cache is specified by the **pivotCacheId** attribute of the [CT_TabularSlicerCache](#) element. The associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache MUST be based on a non-OLAP connection ([\[ISO/IEC29500-1:2011\]](#) section 18.13). The **slicerData** attribute of the [CT_PivotCacheDefinition](#) element MUST be "false".

Multiple slicer caches can be associated with one PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache.

If a slicer cache is associated, as specified by [Slicer Cache Relationship to PivotTable View](#), with one or more PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views, and the slicer source data type is non-OLAP, the slicer cache and each associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view MUST be associated with the same PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache and the **slicerData** attribute of the CT_PivotCacheDefinition element MUST be "false".

If a slicer cache is associated, as specified by Slicer Cache Relationship to PivotTable View, with one or more PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views, and the slicer source data type is OLAP, the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache that is associated with the slicer cache and all PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCaches that are associated with the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views MUST be based on the same OLAP connection ([\[ISO/IEC29500-1:2011\]](#) section 18.13.5) and the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCaches associated with the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views MUST NOT be associated with any slicer cache. The **slicerData** attribute of the CT_PivotCacheDefinition element for each PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache associated with the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views MUST be "false".

2.3.2.1.3 Slicer Cache Relationship to Table

A [slicer cache](#) can be associated with a **Table** ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2). The association is specified by the following rule:

- If the [CT_SlicerCacheDefinition](#) element has a child **extLst** element with a child [CT_TableSlicerCache](#) element, the type of [slicer source data](#) is table and the associated **Table** ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2) of the slicer cache is specified by the **tableId** attribute of the CT_TableSlicerCache element.

Multiple slicer caches can be associated with one **Table** ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2).

2.3.2.1.4 Slicer Cache Relationship to PivotTable View

A slicer cache, as specified in section [2.3.2.1](#), can be associated with PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, views and Charts ([\[ISO/IEC29500-1:2011\]](#) section 21.2) based on [Non-Worksheet PivotTables](#), by the **pivotTables** group element of the **CT_SlicerCacheDefinition** element, as specified in section [2.6.70](#).

If the associated PivotTable **PivotCache** of a slicer cache, as specified by the [Slicer Cache Relationship to PivotCache](#), is an OLAP PivotTable **PivotCache**, the slicer items, as specified in section [2.3.2.1.6](#), in the slicer cache are used to apply PivotTable OLAP manual filters to the PivotTable **hierarchy** specified by the **sourceName** attribute of the **CT_SlicerCacheDefinition** element in all associated PivotTable views and Charts based on Non-Worksheet PivotTables, of the slicer cache. The **selected** slicer items in the slicer cache are converted into selected PivotTable items in the PivotTable OLAP manual filters by the application to apply the filter state of the slicer cache to the associated PivotTable views.

If the associated PivotTable **PivotCache** of a slicer cache, as specified by Slicer Cache Relationship to PivotCache, is a non-OLAP PivotTable **PivotCache**, the PivotTable **PivotCache** of the PivotTable views and the PivotTable **PivotCache** of the slicer cache MUST be the same.

When an OLAP PivotTable view is associated with an OLAP slicer cache, there MUST NOT be more than one slicer cache for each OLAP hierarchy. If the slicer cache is associated with at least one Chart based on Non-Worksheet PivotTable then the slicer cache MUST be OLAP sourced.

If the associated PivotTable **PivotCache** of a slicer cache, as specified by Slicer Cache Relationship to PivotCache, is a non-OLAP PivotTable **PivotCache**, the slicer items in the slicer cache are used to

apply PivotTable non-OLAP manual filters to the **PivotTable** field (1) specified by the **sourceName** attribute of the **CT_SlicerCacheDefinition** element in all associated PivotTable views of the slicer cache. The selected slicer items in the slicer cache are converted into selected PivotTable items in the PivotTable non-OLAP manual filters by the application to apply the filter state of the slicer cache to the associated PivotTable views. See the PivotTable items in [\[ISO/IEC29500-1:2011\]](#) section 18.10 for more details.

2.3.2.1.5 Slicer Cache Relationship to Table column

A slicer cache, as specified in section [2.3.2.1](#), can be associated with column (2) in a **Table**, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2. Associated column (2) is specified by the **column** attribute of the [CT_TableSlicerCache](#) element.

2.3.2.1.6 Slicer Items

Slicer items in a [slicer cache](#) represent distinct values in a column (2) of the [slicer source data](#). In the case of [slicers](#) based on OLAP slicer source data, the slicer cache is based on an OLAP hierarchy and slicer items represent **OLAP members** within levels of that OLAP hierarchy.

For slicers associated with PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views, each slicer item specifies whether slicer source data exists for that slicer item. For more information, see [Slicer Cross Filtering](#).

Each slicer item also specifies the item selection state, used for filtering, and can specify additional properties. For more information see [Non-OLAP Slicer Items](#) and [OLAP Slicer Items](#).

2.3.2.1.6.1 Non-OLAP Slicer Items

The slicer items of a non-OLAP slicer are specified by an ordered sequence of [CT_TabularSlicerCacheItem](#) elements. Each slicer item is associated with a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache item of the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache field (1) in the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache. For more information, see [Slicer Cache Relationship to PivotCache](#).

The associated cache field (1) is specified by the **sourceName** attribute of the [CT_SlicerCacheDefinition](#) element and MUST be equal to the **name** attribute of a **CT_CacheField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element in the collection of PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache fields (1) ([\[ISO/IEC29500-4:2011\]](#) section A.2) of the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache. The associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache item is specified by the **x** attribute of the [CT_TabularSlicerCacheItem](#) element, which contains a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache item index of the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache item in the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache field (1). Two non-OLAP slicer items MUST NOT be associated with the same PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache item.

The order of non-OLAP slicer items in the [slicer cache](#) is specified by the **sortOrder**, **crossFilter**, and **customListSort** attributes of the [CT_TabularSlicerCache](#) element.

The [CT_TabularSlicerCacheItem](#) element also specifies whether the non-OLAP slicer item is selected for filtering and whether data exists in the [slicer source data](#) for it. For more information, see [Slicer Cross Filtering](#).

2.3.2.1.6.2 OLAP Slicer Items

A [CT_OlapSlicerCache](#) element specifies properties of an OLAP [slicer cache](#), and its **descendant** elements specify OLAP slicer items.

A [CT_OlapSlicerCacheRanges](#) element specifies the cache for an OLAP level in an OLAP slicer cache.

The cache is organized into **ranges** of cached OLAP slicer items for each OLAP level in the slicer cache. Each range is specified in a [CT_OlapSlicerCacheRange](#) element. The **startItem** attribute of the [CT_OlapSlicerCacheRange](#) element specifies the zero-based index of the first OLAP slicer item in this cached range in the ordered collection of all OLAP members that exist in the [slicer source data](#) for the associated OLAP level. The collection in the slicer source data is ordered as specified by the **sortOrder** and **crossFilter** attributes of the earlier [CT_OlapSlicerCacheLevelData](#) element.

Each cached OLAP slicer item in a range is specified by a [CT_OlapSlicerCacheItem](#) element.

The OLAP slicer items that are selected for filtering are specified by the [CT_OlapSlicerCacheSelections](#) element.

Each individual OLAP slicer item selected for filtering is specified by a [CT_OlapSlicerCacheSelection](#) element.

2.3.2.1.7 Slicer Cross Filtering

Cross filtering is an application behavior that allows one slicer to reflect the results of filtering by another. This behavior exposes whether data exists in the [slicer source data](#) for each [slicer item](#) when the slicer source data is filtered by the selected slicer items of all associated [slicer caches](#) of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view, as specified by [Slicer Cache Relationship to PivotTable View](#), and all PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) manual filters in the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view.

If the type of slicer source data is OLAP, the existence of data, after filtering, for a slicer item is specified by the **nd** attribute of the [CT_OlapSlicerCacheItem](#) element. If the type of slicer source data is non-OLAP, the existence of data for a slicer item is specified by the **nd** attribute of the [CT_TabularSlicerCacheItem](#) element.

If the type of slicer source data is non-OLAP, the **crossFilter** attribute of the [CT_TabularSlicerCache](#) element specifies how the [non-OLAP slicer items](#) that have no data appear.

If the type of slicer source data is OLAP, the **crossFilter** attribute of the [CT_OlapSlicerCacheLevelData](#) element specifies how the [OLAP slicer items](#) that have no data are displayed for the OLAP level specified by the **uniqueName** attribute of the [CT_OlapSlicerCacheLevelData](#) element.

2.3.2.2 Slicer View

A slicer view specifies the display of a [slicer](#) on a worksheet. A slicer view is displayed as a list of [slicer items](#). The slicer view is specified by a [CT_Slicer](#) element.

Each slicer view is associated with a [slicer cache](#) as specified in [Slicer View Relationship to Slicer Cache](#). The filtering state of slicer items displayed in the slicer view is specified by the associated slicer cache.

Each slicer view is associated with a drawing ([\[ISO/IEC29500-1:2011\]](#) section 20.5), contained in the Drawings part ([\[ISO/IEC29500-1:2011\]](#) section 12.3.8). The associated drawing

([\[ISO/IEC29500-1:2011\]](#) section 20.5) contains a [CT_Slicer](#) element that has a **name** attribute that matches the **name** attribute of the CT_Slicer element that specifies the slicer view.

2.3.2.2.1 Slicer View Relationship to Slicer Cache

Each [slicer view](#) is associated with a [slicer cache](#). The slicer view is associated with a slicer cache through the **name** attribute of the [CT_SlicerCacheDefinition](#) element in the slicer cache that matches the **cache** attribute of the [CT_Slicer](#) element that specifies this slicer view.

If a slicer view is associated with an OLAP slicer cache, the slicer view also has an associated OLAP level, specified by the **level** attribute of the CT_Slicer element. In this case, the slicer view displays [OLAP Slicer Items](#) of that OLAP level.

There can be multiple slicer views associated with a single slicer cache. There are two main reasons for this:

- For a user-defined OLAP hierarchy with several OLAP levels—for example, a Geography OLAP hierarchy with Country, State, and City OLAP levels—each slicer view is associated with a single OLAP level, providing a mechanism for filtering different OLAP levels of the OLAP hierarchy.
- Multiple slicer views associated with either the same slicer cache (for a non-OLAP slicer cache) or the same OLAP level (for an OLAP slicer cache) provide a mechanism for displaying the filter state in more than one location in the workbook.

2.3.2.3 Slicers and Cube Functions

Each [slicer cache](#) has a **defined name** associated with it as specified by the **name** attribute of the [CT_SlicerCacheDefinition](#) element.

The value of the **CT_DefinedName** ([\[ISO/IEC29500-1:2011\]](#) section 18.2.5) element specifying a defined name associated with a slicer cache MUST be #N/A.

If the [slicer source data](#) type of a slicer cache is OLAP, cube functions can use the defined name of the slicer cache as a parameter to refer to the selection state of the slicer cache.

2.3.2.4 Slicer Styles

Slicer styles specify the formatting to apply to visual components of [slicer views](#). The **style** attribute of the [CT_Slicer](#) element specifies the slicer style to be applied. A slicer style can be either built-in or user-defined. Built-in slicer styles are specified in the CT_Slicer element. User-defined slicer styles are specified in the [CT_SlicerStyles](#) element.

A slicer style is an extension of a table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) with additional table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) elements specific to the formatting of slicer views. A user-defined slicer style is specified by a [CT_SlicerStyle](#) element and the table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) it references.

A user-defined slicer style consists of the table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) elements from the referenced table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) and table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) elements specified by a group of [CT_SlicerStyleElement](#) elements.

The **slicerStyleElements** element of a CT_SlicerStyle element specifies the slicer-style-specific table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) elements of the slicer style. The **name** attribute of the CT_SlicerStyle element references the user-defined table style ([\[ISO/IEC29500-1:2011\]](#)

section 18.8) that specifies the non-slicer-style-specific table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) elements of the slicer style.

2.3.3 Non-Worksheet PivotTable

A PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) with a relationship to a PivotCache Definition that has a **pivotCacheDecoupled** element (section [2.4.64](#)) specified, is specified to be a Non-Worksheet PivotTable.

Non-Worksheet PivotTables provide a way for Charts ([\[ISO/IEC29500-1:2011\]](#) section 21.2) to be based on PivotTable data without having to show the data in a worksheet. For more information see [\[MS-ODRAWXML\]](#).

A Non-Worksheet PivotTable MUST only be referenced from workbook.

2.3.4 PivotValues

PivotValues specifies the collection of values that are in the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area. The PivotValues contain a collection of PivotValueCells organized as a two dimensional array corresponding to the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area.

For a [Non-Worksheet PivotTable](#) the PivotValues are specified by the **pivotTableData** element (section [2.4.63](#)).

For PivotTables on a worksheet the PivotValues are specified by the cells of the worksheet ([\[ISO/IEC29500-1:2011\]](#) section 18.3) cell table in the locations specified by the location element ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.49) of the PivotTable.

2.3.4.1 PivotValueCell

A PivotValueCell is a point in individual data unit in the data area of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area. PivotValueCells contain summarized values for associated PivotTable data items. Every PivotValueCell can have two kinds of information associated with it, the [value](#) and the [server formatting](#) information.

2.3.4.1.1 Value

The value of a [PivotValueCell](#) is specified to be the number, string, error, date associated with the PivotValueCell.

2.3.4.1.2 Server Formatting

The server formatting of a [PivotValueCell](#) specifies formatting to be applied to the PivotValueCell.

2.3.5 Timelines

A Timeline is a mechanism for filtering data in PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views, cube functions and Charts ([\[ISO/IEC29500-1:2011\]](#) section 21.2) based on [Non-Worksheet PivotTables](#). In the case of using OLAP [Timeline source data](#), a Timeline is based on a key attribute (1) of an OLAP hierarchy. In the case of using native Timeline source data, a Timeline is based on a **data table (1)** column (2).

A Timeline has two major parts: a [Timeline cache](#), and a [Timeline view](#). There can be more than one Timeline view based on a single Timeline cache.

2.3.5.1 Timeline Cache

A **Timeline cache** specifies the subset of **Timeline source data** (section [2.3.5.1.1](#)) that is cached for display in **Timeline views** (section [2.3.5.2](#)), as well as properties related to **Timeline** filtering (section [2.3.5](#)). A **Timeline cache** is specified by the **CT_TimelineCacheDefinition** element (section [2.6.112](#)).

A **Timeline cache** has an associated **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) **PivotCache** as specified in section [2.3.5.1.2](#).

If the **Timeline source data** is an OLAP data source (1), the **sourceName** attribute (1) of the **CT_TimelineCacheDefinition** element specifies the key attribute name of the associated OLAP hierarchy. If the **Timeline source data** is a native data source (1), the **sourceName** attribute of the **CT_TimelineCacheDefinition** element specifies the name of the associated data table (1) column (2).

If the timeline is used to filter **PivotTable** views, the **Timeline cache** specifies the **PivotTable** views being filtered as specified in **Timeline Cache Relationship to PivotTable View** (section [2.3.5.1.3](#)).

2.3.5.1.1 Timeline Source Data

The source data for a **Timeline** is specified by the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache as specified in [Timeline Cache Relationship to PivotCache](#).

2.3.5.1.2 Timeline Cache Relationship to PivotCache

A **Timeline cache** is associated with a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache through the **pivotCacheId** attribute of the [CT_TimelineState](#) element. If the Timeline cache has an associated PivotTable PivotCache, the **timelineData** attribute of the [CT_TimelinePivotCacheDefinition](#) element MUST be "true".

Multiple Timeline caches can be associated with one PivotTable PivotCache.

If a Timeline cache is associated, as specified by [Timeline Cache Relationship to PivotTable View](#), with one or more PivotTable views, the PivotTable PivotCache that is associated with the Timeline cache and all PivotTable PivotCaches that are associated with the PivotTable views MUST be based on the same source – an OLAP connection ([\[ISO/IEC29500-1:2011\]](#) section 18.13.5) if the [Timeline source data](#) is OLAP and a data table (1) if the Timeline source data is native, and the PivotTable PivotCaches associated with the PivotTable views MUST NOT be associated with any Timeline cache. The **timelineData** attribute of the [CT_TimelinePivotCacheDefinition](#) element for each PivotTable PivotCache associated with the PivotTable views MUST be "false".

2.3.5.1.3 Timeline Cache Relationship to PivotTable View

A **Timeline cache** can be associated with PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views and Charts ([\[ISO/IEC29500-1:2011\]](#) section 21.2) based on [Non-Worksheet PivotTables](#), as specified by the **pivotTables** group element of the [CT_TimelineCacheDefinition](#) element.

The [Timeline State](#) of the Timeline cache is used to apply the PivotTable date filter to the PivotTable hierarchy which belongs to the same **dimension (1)** as the hierarchy associated with the **sourceName** attribute of the [CT_TimelineState](#) element, in all associated PivotTable views and Charts based on Non-Worksheet PivotTables of the Timeline cache. The selected date range in the Timeline cache is converted into selected PivotTable items in the PivotTable date filters by the application to apply the filter state of the Timeline cache to the associated PivotTable views and Charts based on Non-Worksheet PivotTables.

When an OLAP PivotTable view is associated with an OLAP Timeline cache, there MUST NOT be more than one Timeline cache for each OLAP hierarchy. If the Timeline cache has at least one Chart based on Non-Worksheet PivotTable, then the Timeline cache MUST be OLAP sourced. When a native PivotTable view is associated with a native Timeline cache, there MUST NOT be more than one Timeline cache for each data table (1) column (2).

2.3.5.1.4 Timeline State

Timeline state specifies the information used for display in [Timeline view](#). The **Timeline state** contains two elements, selection and bounds, of type [CT_TimelineRange](#). The selection element specifies the start and end dates of the selection in the Timeline and is used for filtering data in PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views and cube functions. The bounds element specifies the minimum and maximum dates that can be displayed by the Timeline view.

2.3.5.2 Timeline View

A Timeline view specifies the display of a [Timeline](#) (section [2.1.8](#)) on a worksheet. The Timeline view is specified by a [CT_Timeline](#) element.

Each Timeline view is associated with a [Timeline cache](#) as specified in [Timeline View Relationship to Timeline Cache](#). The filtering state of Timeline displayed in the Timeline view is specified by the associated Timeline cache.

Each Timeline view is associated with a drawing ([\[ISO/IEC29500-1:2011\]](#) section 20.5), contained in the Drawings part ([\[ISO/IEC29500-1:2011\]](#) section 12.3.8).

2.3.5.2.1 Timeline View Relationship to Timeline Cache

Each [Timeline view](#) is associated with a [Timeline cache](#). The Timeline view is associated with Timeline cache through the **name** attribute of the [CT_TimelineCacheDefinition](#) element in the Timeline cache that matches the **cache** attribute of the [CT_Timeline](#) element that specifies this Timeline view.

There can be multiple Timeline views associated with a single Timeline cache. The main reason for this is that multiple Timeline views associated with the same Timeline cache provide a mechanism for displaying the filter state in more than one location in the workbook.

2.3.5.3 Timelines and Cube Functions

Each [Timeline cache](#) has a defined name associated with it as specified by the **name** attribute of the [CT_TimelineCacheDefinition](#) element.

The value of the **CT_DefinedName** ([\[ISO/IEC29500-1:2011\]](#) section 18.2.5) element specifying a defined name associated with a Timeline Cache MUST be #N/A.

If the [Timeline source data](#) type of a Timeline cache is OLAP, cube functions can use the defined name of the Timeline cache as a parameter to refer to the selection state of the Timeline cache.

2.3.5.4 Timeline Styles

Timeline styles specify the formatting to apply to visual components of [Timeline views](#). The **style** attribute of the [CT_Timeline](#) element specifies the Timeline style to be applied. A Timeline style can be either built-in or user-defined. Built-in Timeline styles are specified in the [CT_Timeline](#) element. User-defined Timeline styles are specified in the [CT_TimelineStyles](#) element.

A Timeline style is an extension of a table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) with additional table style elements specific to the formatting of Timeline views. A user-defined Timeline style is specified by a [CT_TimelineStyle](#) element and the table style it references.

A user-defined Timeline style consists of the table style elements from the referenced table style and table style elements specified by a group of [CT_TimelineStyleElement](#) elements.

The **TimelineStyleElements** element of a [CT_TimelineStyle](#) element specifies the Timeline-style-specific table style elements of the Timeline style. The **name** attribute of the [CT_TimelineStyle](#) element references the user-defined table style that specifies the Timeline-style-specific table style elements of the Timeline style.

2.4 Global Elements

2.4.1 pivotTableReference

A **pivotTableReference** element is a [CT_PivotTableReference](#) type element, as specified in section [2.6.87](#), that specifies a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) part identifier for the workbook. The PivotTable specified by this element MUST be a [Non-Worksheet PivotTable](#). See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

2.4.2 pivotTableServerFormats

A **pivotTableServerFormats** is a [CT_PivotTableServerFormats](#) element that specifies collection of numeric formats specified by elements of complex type **CT_ServerFormat** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.86), for a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) that is specified by a [pivotTableReference](#) element in the extension of a workbook. See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#). If the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) is not a [Non-Worksheet PivotTable](#), MUST NOT be specified.

2.4.3 f

Target namespace: <http://schemas.microsoft.com/office/excel/2006/main>

Referenced by: [CT_WebExtension](#), [CT_CfRule](#), [CT_Cfvo](#), [CT_DataValidationFormula](#), [CT_SparklineGroup](#), [CT_Sparkline](#), [CT_PivotUserEdit](#)

The **f** element is an **ST_Formula** element, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.18.35, that specifies a generic formula that adheres to section [2.2.2](#).

An application can adjust the cell references within this formula when the worksheet layout changes, even when the containing **ext** element, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.2.7, is not recognized by the application. See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="f" type="x:ST_Formula"/>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.4 ref

Target namespace: <http://schemas.microsoft.com/office/excel/2006/main>

The **ref** element is a **CT_Ref** type element, as specified in section [2.6.147](#), that specifies a cell reference.

An application can adjust this cell reference when the worksheet layout changes, even when the containing **ext** element, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.2.7, is not recognized by the application. See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="ref" type="CT_Ref"/>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.5 sqref

Target namespace: <http://schemas.microsoft.com/office/excel/2006/main>

Referenced by: [CT_ConditionalFormatting](#), [CT_DataValidation](#), [CT_Sparkline](#), [CT_IgnoredError](#), [CT_ProtectedRange](#)

A **sqref** element is a **CT_Sqref** type element, as specified in section [2.6.148](#), that specifies a list of cell references.

An application can adjust these cell references when the worksheet layout changes, even when the containing **ext** element, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.2.7, is not recognized by the application. See [\[ISO/IEC29500-3:2011\]](#) section 10.1.2 for more information about how extension lists are used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="sqref" type="CT_Sqref"/>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.6 conditionalFormattings

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **conditionalFormattings** element is a **CT_ConditionalFormattings** type element, as specified in section [2.6.1](#), that specifies conditional formatting information for the worksheet. See section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="conditionalFormattings" type="CT_ConditionalFormattings"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.7 dataValidations

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

The **dataValidations** element is a **CT_DataValidations** type element, as specified in section [2.6.3](#), that specifies a group of data validation items on the **sheet (1)**. This element also specifies data validation properties of a sheet (1) that are used by the application user interface. See section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="dataValidations" type="CT_DataValidations"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.8 sparklineGroups

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **sparklineGroups** element is a **CT_SparklineGroups** type element, as specified in section [2.6.6](#), that specifies the groups of **sparklines** on the sheet (1). See section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="sparklineGroups" type="CT_SparklineGroups"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.9 slicerList

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **slicerList** element is a **CT_SlicerRefs** type element, as specified in section [2.6.11](#), that specifies a list of slicer, as specified in section [2.3.2](#), part identifiers for the worksheet. See section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="slicerList" type="CT_SlicerRefs"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.10 protectedRanges

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **protectedRanges** element is a **CT_ProtectedRanges** type element, as specified in section [2.6.55](#), that specifies a group of protected ranges on the sheet (1). See section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="protectedRanges" type="CT_ProtectedRanges"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.11 ignoredErrors

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

An **ignoredErrors** element is a **CT_IgnoredErrors** type element, as specified in section [2.6.53](#), that specifies a list of cell ranges and the types of cell errors that are to be ignored for each of those specific cell ranges. See section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="ignoredErrors" type="CT_IgnoredErrors"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.12 pivotCaches

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **pivotCaches** element is a **CT_PivotCaches** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies a list of **PivotTable**, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, **PivotCache** identifier elements. The list of elements specifies the PivotTable **PivotCaches** used by slicer caches, as specified in section [2.1.4](#), with OLAP slicer source data, as specified in section [2.3.2.1.1](#). See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotCaches" type="x:CT_PivotCaches"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.13 slicerCaches

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **slicerCaches** element is a **CT_SlicerCaches** type element, as specified in section [2.6.13](#), that specifies a group of slicer cache, as specified in section [2.1.4](#), identifiers for the workbook. See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="slicerCaches" type="CT_SlicerCaches"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.14 workbookPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **workbookPr** element is a **CT_WorkbookPr** element, as specified in section [2.6.10](#), that specifies additional properties for a workbook. See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="workbookPr" type="CT_WorkbookPr"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.15 calculatedMember

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **calculatedMember** element is a **CT_CalculatedMember** type element, as specified in section [2.6.15](#), that specifies extended properties of a PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, OLAP **calculated** member. See section [2.2.4.5](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="calculatedMember" type="CT_CalculatedMember"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.16 cacheHierarchy

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **cacheHierarchy** element is a **CT_CacheHierarchy** type element, as specified in section [2.6.24](#), that specifies the extended properties of a PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, named set. See section [2.2.4.5](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="cacheHierarchy" type="CT_CacheHierarchy"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.17 dataField

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **dataField** element is a **CT_DataField** type element, as specified in section [2.6.25](#), that specifies extended information about a PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, data field (1) item. See section [2.2.4.4](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="dataField" type="CT_DataField"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.18 pivotField

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **pivotField** element is a **CT_PivotField** element, as specified in section [2.6.31](#), that specifies properties of a PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, field (1). See section [2.2.4.4](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotField" type="CT_PivotField"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.19 pivotTableDefinition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **pivotTableDefinition** element is a **CT_PivotTableDefinition** type element, as specified in section [2.6.32](#), that specifies additional properties of the PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, view. See section [2.2.4.4](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotTableDefinition" type="CT_PivotTableDefinition"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.20 pivotCacheDefinition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **pivotCacheDefinition** element is a **CT_PivotCacheDefinition** type element, as specified in section [2.6.33](#), that specifies the extended properties of a PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, **PivotCache** definition. See section [2.2.4.5](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotCacheDefinition" type="CT_PivotCacheDefinition"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.21 connection

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **connection** element is a **CT_Connection** type element, as specified in section [2.6.34](#), that specifies the extended properties of an external connection, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.13. If this element exists, the **type** attribute of the ancestor **CT_Connection** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, **MUST** be equal to "5". See section [2.2.4.1](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="connection" type="CT_Connection"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.22 table

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **table** element is a **CT_Table** type element, as specified in section [2.6.35](#), that specifies alternate text properties for the table. See section [2.2.4.9](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="table" type="CT_Table"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.23 slicerStyles

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **slicerStyles** element is a **CT_SlicerStyles** type element, as specified in section [2.6.51](#), that specifies a group of slicer styles, as specified in section [2.3.2.4](#). See section [2.2.4.7](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="slicerStyles" type="CT_SlicerStyles"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.24 dxfs

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **dxfs** element is a **CT_Dxfs** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies the list of style differential formats (DXFs), as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.8. See section [2.2.4.7](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="dxfs" type="x:CT_Dxfs"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.25 oleItem

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

An **oleItem** element is a **CT_OleItem** type element, as specified in section [2.6.46](#), that specifies an **Object Linking and Embedding (OLE)** data item, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.14, with associated cached values. See section [2.2.4.3](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="oleItem" type="CT_OleItem"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.26 pivotHierarchy

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **pivotHierarchy** element is a **CT_PivotHierarchy** type element, as specified in section [2.6.47](#), that specifies multiple data items based on the same **OLAP measure** that exists in a PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, view. See section [2.2.4.4](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotHierarchy" type="CT_PivotHierarchy"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.27 cacheField

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

The **cacheField** element is a **CT_CacheField** type element, as specified in section [2.6.48](#), that specifies that duplicate OLAP measures exist in a PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, **PivotCache** definition. See section [2.2.4.5](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="cacheField" type="CT_CacheField"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.28 id

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

An **id** element is an **ST_Guid** element, as specified in [\[ISO/IEC29500-1:2011\]](#) section 22.9.2.4, that specifies an identifier for a conditional formatting rule. See section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="id" type="x:ST_Guid"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.29 iconFilter

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

An **iconFilter** element is a **CT_IconFilter** type element, as specified in section [2.6.57](#), that specifies the properties of an **icon** filter. See section [2.2.4.4](#), section [2.2.4.9](#), and section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="iconFilter" type="CT_IconFilter"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.30 filter

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **filter** element is a **CT_Filter** type element, as specified in section [2.6.58](#), that specifies the properties of a filter. See section [2.2.4.4](#), section [2.2.4.9](#), and section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="filter" type="CT_Filter"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.31 customFilters

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **customFilters** element is a **CT_CustomFilters** type element, as specified in section [2.6.59](#), that specifies the properties of **custom filters**. See section [2.2.4.4](#), section [2.2.4.9](#), and section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="customFilters" type="CT_CustomFilters"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.32 sortCondition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **sortCondition** element is a **CT_SortCondition** type element, as specified in section [2.6.61](#), that specifies a **sort condition** to apply to a range. See section [2.2.4.4](#), section [2.2.4.6](#), section [2.2.4.9](#), and section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="sortCondition" type="CT_SortCondition"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.33 sourceConnection

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_CacheSourceExt](#)

A **sourceConnection** element is a **CT_SourceConnection** type element, as specified in section [2.6.62](#), that specifies the name of a connection of the cache source element on a pivot cache. See section [2.2.4.5](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="sourceConnection" type="CT_SourceConnection"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.34 formControlPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **formControlPr** element is a **CT_FormControlPr** type element, as specified in section [2.6.65](#), that specifies properties of form control objects. This element is the root element of the control properties part, as specified in section [2.1.1](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="formControlPr" type="CT_FormControlPr"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.35 datastoreItem

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **datastoreItem** element is a **CT_DatastoreItem** type element, as specified in section [2.6.66](#), that specifies properties for an embedded custom data part, as specified in section [2.1.2](#). This element is the root element of the custom data properties part, as specified in section [2.1.3](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="datastoreItem" type="CT_DatastoreItem"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.36 slicers

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **slicers** element is a **CT_Slicers** type element, as specified in section [2.6.67](#), that specifies all the slicer views, as specified in section [2.3.2.2](#), on the sheet (1). This element is the root element of the slicers part, as specified in section [2.3.2](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="slicers" type="CT_Slicers"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.37 slicer

Target namespace: <http://schemas.microsoft.com/office/drawing/2010/slicer>

A **slicer** element is a **CT_Slicer** type element, as specified in section [2.6.69](#), that specifies which slicer view, as specified in section [2.3.2.2](#), is associated with this drawing element. See section [2.2.4.2](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="slicer" type="CT_Slicer"/>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.38 slicerCacheDefinition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

A **slicerCacheDefinition** element is a **CT_SlicerCacheDefinition** type element, as specified in section [2.6.70](#), that specifies a slicer cache, as specified in section [2.3.2.1](#). This element is the root element of the slicer cache part.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="slicerCacheDefinition" type="CT_SlicerCacheDefinition"/>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.39 pivotCaches

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **pivotCaches** element is a **CT_PivotCaches** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2 that specifies a list of **PivotTable**, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, **PivotCache** identifier elements. The list of elements specifies the PivotTable **PivotCaches**. See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#). The **pivotCacheDefinition** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.67) element identified by the [relationship](#) identifier in the **CT_PivotCache** ([\[ISO/IEC29500-4:2011\]](#) section A.2) child element of this element, MUST satisfy the following criteria.

- There MUST be a [CT_PivotCacheIdVersion](#) element in the extension of the element **pivotCacheDefinition**.

- The **type** attribute of the **CT_CacheSource** ([\[ISO/IEC29500-4:2011\]](#) section A.2) child element of the element **pivotCacheDefinition**, MUST have the value **external** specified by **ST_SourceType** ([\[ISO/IEC29500-1:2011\]](#) 18.18.75).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotCaches" type="x:CT_PivotCaches"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.40 pivotTableReferences

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **pivotTableReferences** element is a [CT_PivotTableReferences](#) element, as specified in section [2.6.86](#), that specifies a list of PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) part identifiers for the workbook. See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotTableReferences" type="CT_PivotTableReferences"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.41 queryTable

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **CT_QueryTable** element (section [2.6.88](#)) that specifies extended properties of a **query table** ([\[ISO/IEC29500-1:2011\]](#) section 18.12).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="queryTable" type="CT_QueryTable"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.42 webExtensions

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A [CT_WebExtensions](#) element that specifies a group of [CT_WebExtension](#) elements that specify Bindings on the Web Extensions, as specified by [\[MS-OWEXML\]](#) section 1.3, on the worksheet.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="webExtensions" type="CT_WebExtensions"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.43 connection

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A [CT_Connection](#) element that specifies the extended properties of an external connection.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="connection" type="CT_Connection"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.44 calculatedMember

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_CalculatedMemberExt](#)

A [CT_CalculatedMember](#) (section [2.6.93](#)) element that specifies a definition for a custom member or measure that is applied to a pivot table.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="calculatedMember" type="CT_CalculatedMember"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.45 pivotTableUISettings

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A [CT_PivotTableUISettings](#) element that specifies state of the **PivotTable field list** for this PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotTableUISettings" type="CT_PivotTableUISettings"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.46 pivotFilter

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A [CT_PivotFilter](#) element that specifies the extended properties of a **filter (PivotTable Advanced Filter)**, as specified in ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.33). See section [2.2.4.4](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotFilter" type="CT_PivotFilter"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.47 slicerCaches

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A [CT_SlicerCaches](#) element that specifies a group of slicer cache, as specified in section [2.1.4](#), identifiers for the workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="slicerCaches" type="x14:CT_SlicerCaches"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.48 tableSlicerCache

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A [CT_TableSlicerCache](#) element that specifies a table data source (1) for the [slicer cache](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="tableSlicerCache" type="CT_TableSlicerCache"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.49 timelineCacheRefs

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **timelineCacheRefs** element is a **CT_TimelineCacheRefs** type element, as specified in section [2.6.98](#), that specifies a group of **Timeline Cache** (section [2.3.5.1](#)) identifiers for the workbook. See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="timelineCacheRefs" type="CT_TimelineCacheRefs"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.50 timelineRefs

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **timelineRefs** element is a **CT_TimelineRefs** type element, as specified in section [2.6.100](#), that specifies a list of Timeline (section [2.3.5](#)) part identifiers for the worksheet. See section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="timelineRefs" type="CT_TimelineRefs"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.51 timelineCachePivotCaches

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **timelineCachePivotCaches** element is a **CT_PivotCaches** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2 that specifies a list of **PivotTable**, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, **PivotCache** identifier elements. The list of elements specifies the PivotTable **PivotCaches**. This element MUST be associated with a Timeline (section [2.3.5](#)). See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="timelineCachePivotCaches" type="x:CT_PivotCaches"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.52 cacheHierarchy

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **CacheHierarchy** element that specifies the extended properties of an OLAP measure.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="cacheHierarchy" type="CT_CacheHierarchy"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.53 slicerCacheHideItemsWithNoData

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **SlicerCacheHideNoData** element that specifies the extended properties of a **slicer cache**, as specified in section [2.3.2.1](#). If this element exists, the **non-OLAP slicer items** that have no data in its

ancestor slicer cache are not displayed and the [OLAP slicer items](#) that have no data are not displayed for the OLAP levels specified by the **uniqueName** attribute of the [CT_SlicerCacheOlapLevelName](#) element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="slicerCacheHideItemsWithNoData" type="CT_SlicerCacheHideNoData"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.54 **timelineStyles**

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **timelineStyles** element is a **CT_TimelineStyles** type element, as specified in section [2.6.105](#), that specifies a group of timeline styles, as specified in section [2.3.5.4](#). See section [2.2.4.7](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="timelineStyles" type="CT_TimelineStyles"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.55 **dxfs**

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **dxfs** element is a **CT_Dxfs** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies the list of style differential formats (DXFs), as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.8. See section [Styles](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="dxfs" type="x:CT_Dxfs"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.56 **timelinePivotCacheDefinition**

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **timelinePivotCacheDefinition** element is a [CT_TimelinePivotCacheDefinition](#) element that specifies the extended properties of a PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, **PivotCache** definition. See section [2.2.4.5](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="timelinePivotCacheDefinition" type="CT_TimelinePivotCacheDefinition"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.57 timelines

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **timelines** element is a **CT_Timelines** type element, as specified in section [2.6.110](#), that specifies all the Timeline views (section [2.3.5.2](#)), on the sheet (1). This element is the root element of the Timelines part (section [2.3.5](#)).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="timelines" type="CT_Timelines"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.58 timelineCacheDefinition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **timelineCacheDefinition** element is a **CT_TimelineCacheDefinition** type element, as specified in section [2.6.112](#), that specifies a Timeline cache (section [2.3.5.1](#)). This element is the root element of the Timeline cache part.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="timelineCacheDefinition" type="CT_TimelineCacheDefinition"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.59 workbookPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **workbookPr** element is a **CT_WorkbookPr** (section [2.6.117](#)) element that specifies additional properties for a workbook. See section [2.2.4.10](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="workbookPr" type="CT_WorkbookPr"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.60 slicerCachePivotTables

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **CT_SlicerCachePivotTables** element (section [2.6.72](#)) that specifies a group of **CT_SlicerCachePivotTable** elements (section [2.6.73](#)) that specify the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views that are filtered by the slicer cache (section [2.1.4](#)). The PivotTables specified by the **CT_SlicerCachePivotTable** (section [2.6.73](#)) child elements of this element MUST be Non-Worksheet PivotTables (section [2.3.3](#)).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="slicerCachePivotTables" type="x14:CT_SlicerCachePivotTables"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.61 cachedUniqueNames

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **CT_CachedUniqueNames** element that specifies the MDX unique names for PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache items in this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache field (1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="cachedUniqueNames" type="CT_CachedUniqueNames"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.62 dataModel

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **CT_DataModel** element that specifies properties of spreadsheet data model.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="dataModel" type="CT_DataModel"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.63 pivotTableData

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **pivotTableData** element is a **CT_PivotTableData** element that specifies the **PivotValues** of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10), specified by the **pivotTableReference** element in the extension of a workbook. See section [2.2.4.4](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#). If the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) is not a **Non-Worksheet PivotTable**, MUST NOT be specified.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotTableData" type="CT_PivotTableData"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.64 pivotCacheDecoupled

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A [CT_PivotCacheDecoupled](#) element that specifies the extended properties of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) **PivotCache Definition**. The **cacheID** attribute of the parent **CT_PivotCache** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element of this element MUST be equal to the **cacheId** attribute of the element **pivotTableDefinition** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.73) in the PivotTable part that has a relationship identifier specified by a [pivotTableReference](#) element in the extension of the workbook. See section [2.2.4.5](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotCacheDecoupled" type="CT_PivotCacheDecoupled"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.65 pivotCacheIdVersion

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A [CT_PivotCacheIdVersion](#) element that specifies the extended properties of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) **PivotCache Definition**. If this element exists, there MUST be a preceding [CT_PivotCacheDefinition](#) element and the **pivotCacheId** attribute of the preceding [CT_PivotCacheDefinition](#) element MUST be equal to one of the following:-

- The **cacheId** attribute of the [CT_PivotTableData](#) element in the PivotTable part that specifies a [Non-Worksheet PivotTable](#).
- The **pivotCacheId** attribute of the **CT_TimelineState** (section [2.6.116](#)) child element of a **CT_TimelineCacheDefinition** (section [2.6.112](#)) element that specifies a [Timeline cache](#).

See section [2.2.4.5](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="pivotCacheIdVersion" type="CT_PivotCacheIdVersion"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.66 timeslicer

Target namespace: <http://schemas.microsoft.com/office/drawing/2012/timeslicer>

A [CT_Timeline](#) element that specifies which [timeline view](#) is associated with this drawing element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="timeslicer" type="CT_Timeline"/>
```

See section [5.7](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.67 list

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2011/1/ac>

An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) element that specifies the first formula in the DataValidation dropdown used for custom or list type data validation. Only used when items need to be quoted.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="list" type="x:ST_Xstring"/>
```

See section [5.6](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.68 absPath

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/ac>

A **CT_AbsolutePath** element that specifies the absolute path to the workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="absPath" type="CT_AbsolutePath"/>
```

See section [5.9](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.69 dataField

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **dataField** element is a **CT_DataField** type element, as specified in section [2.6.25](#), that specifies extended information about a PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, data field (1) item. See section [2.2.4.4](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="dataField" type="CT_DataField"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.70 survey

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A **survey** element is a **CT_Survey** type element, as specified in section [2.6.143](#), that specifies the properties of a survey associated with a Table ([\[ISO/IEC29500-1:2011\]](#) section 18.5). This element is the root element of the Survey part (section [2.1.9](#))

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="survey" type="CT_Survey"/>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.4.71 contentPart

Target namespace: <http://schemas.microsoft.com/office/excel/2010/spreadsheetDrawing>

A [CT_ContentPart](#) element that specifies

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="contentPart" type="CT_ContentPart"/>
```

See section [5.8](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.5 Global Attributes

2.5.1 dyDescent

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/ac>

The **dyDescent** attribute is a **double** attribute, as specified in [\[XMLSCHEMA2\]](#) section 3.2.5, that specifies the vertical distance in **pixels** from the bottom of the cells in the current **row (2)** to the typographical baseline of the cell content if, hypothetically, the **zoom level** for the sheet (1) containing this row (2) is 100 percent and the cell has bottom-alignment formatting. See section [2.2.4.11](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#). The **dyDescent** attribute has a side effect; it sets the **customHeight** attribute to true even if the **customHeight** attribute is explicitly set to false.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this attribute.

```
<xsd:attribute name="dyDescent" type="xsd:double"/>
```

See section [5.5](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.5.2 knownFonts

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/ac>

The **knownFonts** attribute is a **Boolean** attribute, as specified in ([XMLSCHEMA2] section 3.2.2, that specifies the typographical descent information that is stored in the workbook. See section 2.2.4.7 for how this element integrates with the Office Open XML file formats specified in [ISO/IEC29500-1:2011].

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this attribute.

```
<xsd:attribute name="knownFonts" type="xsd:boolean"/>
```

See section 5.5 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6 Complex Types

2.6.1 CT_ConditionalFormattings

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [conditionalFormattings](#)

The **CT_ConditionalFormattings** complex type specifies conditional formatting information for the worksheet.

Child Elements:

conditionalFormatting: A **CT_ConditionalFormatting** element (section 2.6.2) that specifies the conditional formatting properties for a range.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ConditionalFormattings">
  <xsd:sequence>
    <xsd:element name="conditionalFormatting" type="CT_ConditionalFormatting" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.2 CT_ConditionalFormatting

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_ConditionalFormattings](#)

The **CT_ConditionalFormatting** complex type specifies conditional formatting properties for a range.

Child Elements:

cfRule: A **CT_CfRule** element (section 2.6.27) that specifies a conditional formatting rule for this range.

xm:sqref: A **sqref** element (section [2.4.5](#)) that specifies the range this conditional formatting applies to.

extLst: A **CT_ExtensionList** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

pivot: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this conditional formatting is applied only to a PivotTable. MUST be a value from the following table.

Value	Meaning
"true"	The area specified by sqref only includes cells that are part of a PivotTable data area.
"false"	The area specified by sqref includes cells that are not part of a PivotTable data area.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ConditionalFormatting">
  <xsd:sequence>
    <xsd:element name="cfRule" type="CT_CfRule" minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element ref="xm:sqref" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" minOccurs="0" type="x:CT_ExtensionList"/>
  </xsd:sequence>
  <xsd:attribute name="pivot" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.3 CT_DataValidations

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [dataValidations](#)

CT_DataValidations is a complex type that specifies a group of data validation items on the sheet (1). MUST contain less than or equal to 65,534 elements. This complex type also specifies data validation properties of a sheet (1) that are used by the application UI.

Child Elements:

dataValidation: A **CT_DataValidation** element (section [2.6.5](#)) that specifies the properties for a single data validation item defined on a range of the sheet (1).

Attributes:

disablePrompts: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether all data validation input prompts are disabled for this sheet (1).

Value	Meaning
"true"	All data validation input prompts are disabled for this sheet (1).
"false"	The data validation input prompts are enabled for this sheet (1).

xWindow: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the x-coordinate, relative to the application window, of the upper-left corner of the data validation input prompt, measured in pixels. This value MUST be less than or equal to 65,535. [<6>](#)

yWindow: An **unsignedInt** attribute that specifies the y-coordinate, relative to the application window, of the upper-left corner of the data validation input prompt, measured in pixels. This value MUST be less than or equal to 65,535. [<7>](#)

count: An **unsignedInt** attribute that specifies the number of **dataValidation** child elements of this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DataValidations">
  <xsd:sequence>
    <xsd:element name="dataValidation" type="CT_DataValidation" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="disablePrompts" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="xWindow" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="yWindow" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.4 CT_DataValidationFormula

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_DataValidation](#)

CT_DataValidationFormula is a complex type that specifies a formula used in data validation.

Child Elements:

xm:f: An **f** element (section [2.4.3](#)) that specifies a formula for the data validation. The formula MUST adhere to the grammar provided in section [2.2.2](#), with the following restrictions:

- MUST NOT use the ref-infix-operator, local-cell-reference, bang-reference, bang-name, array-constant, sheet-range-reference, or structure-reference production rules.
- MUST be an external-cell-reference if used by the **formula1** element of the ancestor **CT_DataValidation** element (section [2.6.5](#)), and the **formula1** element of the ancestor **CT_DataValidation** element uses the external-cell-reference production rule, and the **type** attribute of the ancestor **CT_DataValidation** element is "list".
- MUST NOT be an external-cell-reference that references more than one cell if used by the **formula1** element of the ancestor **CT_DataValidation** element and the **type** attribute of the ancestor **CT_DataValidation** element is not "list".
- MUST NOT be an external-cell-reference that references more than one cell if used by the **formula2** element of the ancestor **CT_DataValidation** element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DataValidationFormula">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.5 CT_DataValidation

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_DataValidations](#)

CT_DataValidation is a complex type that specifies data validation for a range on this sheet (1).

Child Elements:

formula1: A **CT_DataValidationFormula** element (section [2.6.4](#)) that specifies the first formula for the data validation.

- If **operator** is "between" or "notBetween" and **type** is not "custom", "list", or "none", this formula is used as the lesser of two bounding values and MUST exist.
- If **operator** is not "between" or "notBetween", or **type** is "custom", this formula is the only formula and MUST exist.
- If **operator** is not "between" or "notBetween", or **type** is "custom" or "list", either formula is the only formula and MUST exist or **CT_DataValidation** MUST have a **list** (section [2.4.67](#)) child element.
- If the **type** is "none", this formula MUST NOT exist.

formula2: A **CT_DataValidationFormula** element that specifies the second formula for the data validation.

- If **operator** is "between" or "notBetween" and **type** is not "custom", "list", or "none", this formula is used as the greater of two bounding values and MUST exist.
- If **operator** is not "between" or "notBetween", or **type** is "custom", "list", or "none", this formula MUST NOT exist.

xm:sqref: A **sqref** element (section [2.4.5](#)) that specifies ranges to which data validation is applied.

Attributes:

type: An **ST_DataValidationType** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.21) attribute that specifies the type of data validation.

errorStyle: An **ST_DataValidationErrorStyle** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.18) attribute that specifies the style of error alert used for this data validation.

imeMode: An **ST_DataValidationImeMode** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.19) attribute that specifies the **Input Method Editor (IME)** mode enforced by this data validation.

operator: An **ST_DataValidationOperator** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.20) attribute that specifies the relational operator used with this data validation. If **type** is "custom", "list", or "none", the value of the **operator** attribute is undefined and MUST be ignored.

allowBlank: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the data validation treats empty or blank entries as valid.

Value	Meaning
"true"	The data validation treats empty or blank entries as valid.
"false"	The data validation treats empty or blank entries as invalid.

showDropDown: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to display the drop-down combo box for a list type data validation.

Value of showDropDown	Value of type	Meaning
"true"	list	Displays the drop-down combo box.
"false"	list	Suppresses the drop-down combo box.

showInputMessage: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to display the input prompt message.

Value	Meaning
"true"	Display the input prompt message.
"false"	Suppress the input prompt message.

showErrorMessage: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to display the error alert message.

Value	Meaning
"true"	Display the error alert message.
"false"	Suppress the error alert message.

errorTitle: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the text of the title bar of the error alert. The length of this string MUST be less than or equal to 32 characters.

error: An **ST_Xstring** attribute that specifies the message text of the error alert. The length of this string MUST be less than or equal to 225 characters.

promptTitle: An **ST_Xstring** attribute that specifies the text of the title bar of the input prompt. The length of this string MUST be less than or equal to 32 characters.

prompt: An **ST_Xstring** attribute that specifies the message text of the input prompt. This string MUST be less than or equal to 255 characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_DataValidation">
  <xsd:sequence>
    <xsd:element name="formula1" type="CT_DataValidationFormula" minOccurs="0"
maxOccurs="1"/>
    <xsd:element name="formula2" type="CT_DataValidationFormula" minOccurs="0"
maxOccurs="1"/>
    <xsd:element ref="xm:sqref" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="type" type="x:ST_DataValidationType" use="optional" default="none"/>
  <xsd:attribute name="errorStyle" type="x:ST_DataValidationErrorStyle" use="optional"
default="stop"/>
  <xsd:attribute name="imeMode" type="x:ST_DataValidationImeMode" use="optional"
default="noControl"/>
  <xsd:attribute name="operator" type="x:ST_DataValidationOperator" use="optional"
default="between"/>
  <xsd:attribute name="allowBlank" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="showDropDown" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="showInputMessage" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="showErrorMessage" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="errorTitle" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="error" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="promptTitle" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="prompt" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.6 CT_SparklineGroups

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [sparklineGroups](#)

CT_SparklineGroups is a complex type that specifies the groups of sparklines on the sheet (1). MUST contain fewer than 2³¹ elements.

Child Elements:

sparklineGroup: A **CT_SparklineGroup** element (section [2.6.7](#)) that specifies properties for a single sparkline group.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_SparklineGroups">
  <xsd:sequence>
    <xsd:element name="sparklineGroup" type="CT_SparklineGroup" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.7 CT_SparklineGroup

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SparklineGroups](#)

CT_SparklineGroup is a complex type that specifies properties for a sparkline group.

Child Elements:

colorSeries: A **CT_Color** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies the color for each sparkline in this sparkline group. The **auto** attribute of the **CT_Color** element MUST NOT exist.

colorNegative: A **CT_Color** element that specifies the color of the negative **data points (2)** for each sparkline in this sparkline group. The **auto** attribute of the **CT_Color** element MUST NOT exist.

colorAxis: A **CT_Color** element that specifies the color of the horizontal axis for each sparkline in this sparkline group. The **auto** attribute of the **CT_Color** element MUST NOT exist.

colorMarkers: A **CT_Color** element that specifies the color of the **data markers** for each sparkline in this sparkline group. The **auto** attribute of the **CT_Color** element MUST NOT exist.

colorFirst: A **CT_Color** element that specifies the color of the first data point (2) for each sparkline in this sparkline group. The **auto** attribute of the **CT_Color** element MUST NOT exist.

colorLast: A **CT_Color** element that specifies the color of the last data point (2) for each sparkline in this sparkline group. The **auto** attribute of the **CT_Color** element MUST NOT exist.

colorHigh: A **CT_Color** element that specifies the color of the highest data point (2) for each sparkline in this sparkline group. The **auto** attribute of the **CT_Color** element MUST NOT exist.

colorLow: A **CT_Color** element that specifies the color of the lowest data point (2) for each sparkline in this sparkline group. The **auto** attribute of the **CT_Color** element MUST NOT exist.

xm:f: An **f** element (section [2.4.3](#)) that specifies the date range for the sparkline group. The syntax, as specified in section [2.2.2](#), for this **f** element is the following:

```
sparklinegroup-formula = single-sheet-area / [single-sheet-prefix / book-prefix] name
```

Additionally, if a single-sheet-area is specified, that single-sheet-area MUST contain cells from either a single row (2) or a single column (2).

sparklines: A **CT_Sparklines** element (section [2.6.8](#)) that specifies properties for individual sparklines.

Attributes:

manualMax: A **double** ([\[XMLSCHEMA2\]](#) section 3.2.5) attribute that specifies the maximum for the vertical axis that is shared across all sparklines in this sparkline group. This attribute MUST NOT exist if **maxAxisType** does not equal "custom".

manualMin: A **double** attribute that specifies the minimum for the vertical axis that is shared across all sparklines in this sparkline group. This attribute MUST NOT exist if **minAxisType** does not equal "custom".

lineWeight: A **double** attribute that specifies the line weight for each sparkline in the sparkline group, where the line weight is measured in **points**. MUST be greater than or equal to zero, and MUST be less than or equal to 1584.

type: An **ST_SparklineType** attribute (section [2.7.5](#)) that specifies the type of the sparkline group.

dateAxis: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this sparkline group uses a date axis.

Value of dateAxis	Meaning
"false"	No date axis is specified for this sparkline group.
"true"	A date axis is specified for this sparkline group.

displayEmptyCellsAs: An **ST_DispBlanksAs** attribute (section [2.7.3](#)) that specifies how empty cells are plotted.

markers: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether data markers are displayed for each sparkline in this sparkline group.

Value	Meaning
"true"	Data markers are displayed for each sparkline in this sparkline group.
"false"	No data marker is displayed for sparkline in this sparkline group.

high: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the data points (2) with the highest value are formatted differently for each sparkline in this sparkline group.

Value	Meaning
"true"	Data points (2) with the highest value are formatted differently for each sparkline in this sparkline group.
"false"	No data point (2) with the highest value is formatted for sparkline in this sparkline group.

low: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the data points (2) with the lowest value are formatted differently for each sparkline in this sparkline group.

Value	Meaning
"true"	Data points (2) with the lowest value are formatted differently for each sparkline in this sparkline group.
"false"	No data point (2) with the lowest value is formatted for sparkline in this sparkline group.

first: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the first data point (2) is formatted differently for each sparkline in this sparkline group.

Value	Meaning
"true"	The first data point (2) is formatted differently for each sparkline in this sparkline group.
"false"	The first data point (2) is not formatted for sparkline in this sparkline group.

last: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the last data point (2) is formatted differently for each sparkline in this sparkline group.

Value	Meaning
"true"	The last data point (2) is formatted differently for each sparkline in this sparkline group.
"false"	The last data point (2) is not formatted for sparkline in this sparkline group.

negative: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the negative data points (2) are formatted differently for each sparkline in this sparkline group.

Value	Meaning
"true"	The negative data point (2) is formatted differently for each sparkline in this sparkline group.
"false"	The negative data point (2) is not formatted for sparkline in this sparkline group.

displayXAxis: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the horizontal axis is displayed for each sparkline in this sparkline group.

Value	Meaning
"true"	The horizontal axis is displayed for each sparkline in this sparkline group.
"false"	No horizontal axis is displayed for sparkline in this sparkline group.

displayHidden: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether data in **hidden** cells are plotted for the sparklines in this sparkline group.

Value	Meaning
"true"	Data in hidden cells are plotted for the sparklines in this sparkline group.
"false"	Data in hidden cells are not plotted for the sparklines in this sparkline group.

minAxisType: An **ST_SparklineAxisMinMax** attribute (section [2.7.4](#)) that specifies how the vertical axis minimums for the sparklines in this sparkline group are calculated.

maxAxisType: An **ST_SparklineAxisMinMax** attribute that specifies how the vertical axis maximums for the sparklines in this sparkline group are calculated.

rightToLeft: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether each sparkline in the sparkline group is displayed in a **right-to-left** manner.

Value	Meaning
"true"	Each sparkline in the sparkline group is displayed in a right-to-left manner.
"false"	Not all sparklines in the sparkline group is displayed in a right-to-left manner.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SparklineGroup">
  <xsd:sequence>
    <xsd:element name="colorSeries" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
    <xsd:element name="colorNegative" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
  </xsd:sequence>
</xsd:complexType>
```

```

<xsd:element name="colorAxis" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
<xsd:element name="colorMarkers" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
<xsd:element name="colorFirst" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
<xsd:element name="colorLast" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
<xsd:element name="colorHigh" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
<xsd:element name="colorLow" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
<xsd:element ref="xm:f" minOccurs="0" maxOccurs="1"/>
<xsd:element name="sparklines" type="CT_Sparklines" minOccurs="1" maxOccurs="1"/>
</xsd:sequence>
<xsd:attribute name="manualMax" type="xsd:double" use="optional"/>
<xsd:attribute name="manualMin" type="xsd:double" use="optional"/>
<xsd:attribute name="lineWeight" type="xsd:double" use="optional" default="0.75"/>
<xsd:attribute name="type" type="ST_SparklineType" use="optional" default="line"/>
<xsd:attribute name="dateAxis" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="displayEmptyCellsAs" type="ST_DisbBlanksAs" use="optional"
default="zero"/>
<xsd:attribute name="markers" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="high" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="low" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="first" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="last" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="negative" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="displayXAxis" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="displayHidden" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="minAxisType" type="ST_SparklineAxisMinMax" use="optional"
default="individual"/>
<xsd:attribute name="maxAxisType" type="ST_SparklineAxisMinMax" use="optional"
default="individual"/>
<xsd:attribute name="rightToLeft" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.8 CT_Sparklines

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SparklineGroup](#)

CT_Sparklines is a complex type that specifies a list of individual sparklines in a sparkline group. MUST contain fewer than 2³¹ elements.

Child Elements:

sparkline: A **CT_Sparkline** element (section [2.6.9](#)) that specifies properties for an individual sparkline.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_Sparklines">
  <xsd:sequence>
    <xsd:element name="sparkline" type="CT_Sparkline" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.9 CT_Sparkline

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_Sparklines](#)

CT_Sparkline is a complex type that specifies information for a single sparkline.

Child Elements:

xm:f: An **f** element (section [2.4.3](#)) that specifies the data range for this sparkline. The syntax, specified in section [2.2.2](#), for this element is the following:

```
sparkline-formula = single-sheet-area / [single-sheet-prefix / book-prefix] name
```

Additionally, if a single-sheet-area is specified, that single-sheet-area MUST contain cells from either a single row (2) or a single column (2).

xm:sqref: A **sqref** element (section [2.4.5](#)) that specifies the cell in which the sparkline is located. This **sqref** element MUST contain exactly one **ref** element (section [2.4.4](#)) that MUST specify exactly one cell.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Sparkline">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="0" maxOccurs="1"/>
    <xsd:element ref="xm:sqref" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.10 CT_WorkbookPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [workbookPr](#)

CT_WorkbookPr is a complex type that specifies additional properties for a workbook.

Attributes:

defaultImageDpi: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the resolution in which images in the workbook is saved, in DPI ([\[ISO/IEC29500-1:2011\]](#) section 18.2.24), when the **autoCompressPictures** attribute of the **WorkbookPr** ([\[ISO/IEC29500-1:2011\]](#) section 18.2.28) element is "true" and the **CT_UseLocalDpi** ([\[MS-ODRAWXML\]](#) section [2.3.4](#)) element of the drawings part ([\[ISO/IEC29500-1:2011\]](#) section 12.3.8) corresponding to the image being saved is "false". MUST be equal to "96", "150", or "220".

discardImageEditData: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies whether all **CT_Photo** ([MS-ODRAWXML] section 2.3.3) elements and cropped out areas of images in the workbook are not saved.

Value	Meaning
"true"	All CT_Photo elements and cropped out areas of images in the workbook are not saved.
"false"	All CT_Photo elements and cropped out areas of images in the workbook are saved.

accuracyVersion: An **unsignedInt** attribute that specifies how functions are calculated in the workbook. SHOULD be equal to zero ("0").<8>

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_WorkbookPr">
  <xsd:attribute name="defaultImageDpi" type="xsd:unsignedInt" default="220"/>
  <xsd:attribute name="discardImageEditData" type="xsd:boolean" default="false"/>
  <xsd:attribute name="accuracyVersion" type="xsd:unsignedInt" default="0"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.11 CT_SlicerRefs

Target namespace: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main

Referenced by: [slicerList](#)

CT_SlicerRefs is a complex type that specifies a list of slicer (section 2.3.2) part identifiers for the worksheet. MUST contain exactly one slicer part identifier.

Child Elements:

slicer: A **CT_SlicerRef** element (section 2.6.12) that specifies the slicer part identifier for the worksheet.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerRefs">
  <xsd:sequence>
    <xsd:element name="slicer" type="CT_SlicerRef" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.12 CT_SlicerRef

Target namespace: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main

Referenced by: [CT_SlicerRefs](#)

A complex type that specifies a [relationship](#) identifier of the part that contains the [slicers](#) in this worksheet.

Attributes:

r:id: An **ST_RelationshipId** ([\[ISO/IEC29500-1:2011\]](#) section 22.8.2.1) attribute that specifies a relationship identifier of the part that contains the slicers in this worksheet.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerRef">
  <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.13 CT_SlicerCaches

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [slicerCaches](#), [slicerCaches](#)

A complex type that specifies a list of [slicer cache](#) part identifiers for the workbook. MUST contain fewer than 2³¹ elements.

Child Elements:

slicerCache: A [CT_SlicerCache](#) element that specifies a slicer cache part identifier in this workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerCaches">
  <xsd:sequence>
    <xsd:element name="slicerCache" type="CT_SlicerCache" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.14 CT_SlicerCache

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SlicerCaches](#)

A complex type that specifies a [relationship](#) identifier to a [slicer cache](#) part in this workbook.

Attributes:

r:id: An **ST_RelationshipId** ([\[ISO/IEC29500-1:2011\]](#) section 22.8.2.1) attribute that specifies a relationship identifier to a slicer cache part in this workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerCache">
  <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.15 CT_CalculatedMember

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [calculatedMember](#)

A complex type that specifies extended properties of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) OLAP calculated member.

Child Elements:

tupleSet: A **CT_TupleSet** element (section [2.6.16](#)) that specifies OLAP tuples within this **OLAP named set**.

Attributes:

displayFolder: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the display folder of this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set. The length of this value **MUST** be less than 65,536 characters. This attribute **MUST NOT** exist if the **set** attribute in the ancestor **CT_CalculatedMember** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element is zero ("0").

flattenHierarchies: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to display members from different OLAP levels of the same PivotTable cache hierarchy of this **PivotTable** named set in the same **PivotTable** field (1). This attribute **MUST NOT** exist if the **set** attribute in the ancestor **CT_CalculatedMember** element is zero ("0").

Value	Meaning
"0"	Each member from a different level of the same PivotTable cache hierarchy of this PivotTable named set is displayed in a separate PivotTable field (1).
"1"	All members from different levels of the same PivotTable cache hierarchy of this PivotTable named set are displayed in the same PivotTable field (1).

dynamicSet: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this **PivotTable** named set is a dynamic OLAP named set. This attribute **MUST NOT** exist if the **set** attribute in the ancestor **CT_CalculatedMember** element is zero ("0").

Value	Meaning
"0"	This PivotTable named set is a static OLAP named set.
"1"	This PivotTable named set is a dynamic OLAP named set.

hierarchizeDistinct: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to automatically order and remove duplicates from this **PivotTable** named set. This attribute **MUST NOT** exist if the **set** attribute in the ancestor **CT_CalculatedMember** element is zero ("0").

Value	Meaning
"0"	Do not automatically order and remove duplicates from this PivotTable named set.
"1"	Automatically order and remove duplicates from this PivotTable named set.

mdxLong: An **ST_Xstring** attribute that specifies **multidimensional expression (MDX)** of the PivotTable OLAP calculated member. The length of this attribute **MUST** be zero or it **MUST** be greater than 32,767 characters and less than 1,073,741,823 characters. If this value is greater than 32,767 characters, the length of the **mdx** attribute in the ancestor **CT_CalculatedMember** element **MUST** be "1" and the first character of the **mdx** attribute **MUST** be equal to " ", the space character (0x0020).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CalculatedMember">
  <xsd:sequence>
    <xsd:element name="tupleSet" minOccurs="0" maxOccurs="1" type="CT_TupleSet"/>
  </xsd:sequence>
  <xsd:attribute name="displayFolder" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="flattenHierarchies" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="dynamicSet" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="hierarchizeDistinct" type="xsd:boolean" use="optional"
  default="true"/>
  <xsd:attribute name="mdxLong" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.16 CT_TupleSet

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_CalculatedMember](#)

A complex type that specifies an OLAP named set.

Child Elements:

headers: A [CT_TupleSetHeaders](#) element that specifies the MDX unique names of the OLAP hierarchies and the MDX unique names of the OLAP levels specified by this OLAP named set.

rows: A [CT_TupleSetRows](#) element that specifies the OLAP tuples specified by this OLAP named set.

Attributes:

rowCount: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of OLAP tuples specified by this OLAP named set. **MUST** equal the number of [CT_TupleSetRow](#) elements within the **rows** element. **rowCount** * **columnCount** **MUST** be less than or equal to 3,000.

columnCount: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of MDX unique names of the OLAP hierarchies and the MDX unique names of the OLAP levels specified by this OLAP named set. MUST equal the number of [CT_TupleSetHeader](#) elements within the **headers** element. **rowCount** * **columnCount** MUST be less than or equal to 3,000.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TupleSet">
  <xsd:sequence>
    <xsd:element name="headers" type="CT_TupleSetHeaders" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="rows" type="CT_TupleSetRows" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="rowCount" type="xsd:unsignedInt" use="optional" default="1"/>
  <xsd:attribute name="columnCount" type="xsd:unsignedInt" use="optional" default="1"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.17 CT_TupleSetHeaders

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_TupleSet](#)

A complex type that specifies the MDX unique names of the OLAP hierarchies and the MDX unique names of the OLAP levels of the OLAP named set.

Child Elements:

header: [CT_TupleSetHeader](#) elements that specify the MDX unique names of the OLAP hierarchies and the MDX unique names of the OLAP levels of the OLAP named set. The number of these elements MUST be equal to the value of the **columnCount** attribute in the CT_TupleSet element that is the ancestor of this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TupleSetHeaders">
  <xsd:sequence>
    <xsd:element name="header" type="CT_TupleSetHeader" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.18 CT_TupleSetHeader

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_TupleSetHeaders](#)

A complex type that specifies the MDX unique name of the OLAP hierarchy and the MDX unique name of the OLAP level of the OLAP named set that is specified by the [CT_TupleSet](#) element that is an ancestor of this element.

Attributes:

uniqueName: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the MDX unique name of the OLAP level. MUST be less than or equal to 65,535 characters in length.

hierarchyName: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the MDX unique name of the OLAP hierarchy. MUST be less than or equal to 65,535 characters in length.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TupleSetHeader">
  <xsd:attribute name="uniqueName" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="hierarchyName" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.19 CT_TupleSetRows

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_TupleSet](#)

A complex type that specifies the OLAP tuples for this OLAP named set.

Child Elements:

row: [CT_TupleSetRow](#) elements that specify the OLAP tuples for this OLAP named set. The number of these elements MUST be equal to the value of the **rowCount** attribute in the parent CT_TupleSet element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TupleSetRows">
  <xsd:sequence>
    <xsd:element name="row" type="CT_TupleSetRow" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.20 CT_TupleSetRow

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_TupleSetRows](#)

A complex type that specifies an OLAP tuple for this OLAP named set.

Child Elements:

rowItem: [CT_TupleSetRowItem](#) elements that specify the OLAP members that are part of the OLAP tuple that is specified by this CT_TupleSetRow element. The number of these elements MUST be

equal to value of the **columnCount** attribute in the [CT_TupleSet](#) element that is an ancestor of this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TupleSetRow">
  <xsd:sequence>
    <xsd:element name="rowItem" type="CT_TupleSetRowItem" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.21 CT_TupleSetRowItem

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_TupleSetRow](#)

A complex type that specifies an OLAP member that is part of an OLAP tuple.

Attributes:

u: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the MDX unique name of this OLAP member. MUST be less than or equal to 65,535 characters in length.

d: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies a display name for this OLAP member. MUST be less than or equal to 65,535 characters in length.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TupleSetRowItem">
  <xsd:attribute name="u" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="d" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.22 CT_SetLevels

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_CacheHierarchy](#)

A complex type that specifies a list of [CT_SetLevel](#) elements that specify the OLAP levels of the **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set.

Child Elements:

setLevel: A [CT_SetLevel](#) element that specifies an OLAP level of the **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache hierarchy of the **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set.

Attributes:

count: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the number of child **setLevel** elements of this element.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SetLevels">
  <xsd:sequence>
    <xsd:element name="setLevel" minOccurs="1" maxOccurs="unbounded" type="CT_SetLevel"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.23 CT_SetLevel

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SetLevels](#)

A complex type that specifies an OLAP level of the **PivotTable** ([ISO/IEC29500-1:2011] section 18.10) cache hierarchy of a **PivotTable** named set.

Attributes:

hierarchy: An **int** ([XMLSCHEMA2] section 3.3.17) attribute that specifies a reference to the PivotTable cache hierarchy. MUST be a value from the following table.

Value	Meaning
"-2"	The PivotTable measure cache hierarchy is used.
"-1"	No PivotTable cache hierarchy is used.
Greater than or equal to zero	A zero-based PivotTable cache hierarchy index. The referenced CT_CacheHierarchy ([ISO/IEC29500-4:2011] section A.2) element specifies the PivotTable cache hierarchy that is used. MUST be less than the number of CT_CacheHierarchy elements within the CT_CacheHierarchies ([ISO/IEC29500-1:2011] section 18.10) element.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SetLevel">
  <xsd:attribute name="hierarchy" use="required" type="xsd:int"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.24 CT_CacheHierarchy

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [cacheHierarchy](#)

This complex type specifies the extended properties of a **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set. When an element of this type is present, the **set** attribute of the ancestor **cacheHierarchy** element of type **CT_CacheHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) MUST be "true".

Child Elements:

setLevels: A [CT_SetLevels](#) element that specifies the OLAP levels of the hierarchy that is used by this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set.

Attributes:

flattenHierarchies: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to display members from different levels of the same PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache hierarchy of this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set in the same **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) field (1). MUST be "false" if **ignore** is "true". If a [CT_CalculatedMember](#) element that corresponds to the **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set exists, this attribute MUST be equal to the **flattenHierarchies** attribute of the [CT_CalculatedMember](#) element.

ignore	flattenHierarchies	Meaning
"true"	"false"	The ancestor cacheHierarchy element of type CT_CacheHierarchy ([ISO/IEC29500-4:2011] section A.2) of this PivotTable ([ISO/IEC29500-1:2011] section 18.10) named set is discarded.
"false"	"false"	Each member from a different level of the same PivotTable ([ISO/IEC29500-1:2011] section 18.10) cache hierarchy of this PivotTable ([ISO/IEC29500-1:2011] section 18.10) named set is displayed in a separate PivotTable ([ISO/IEC29500-1:2011] section 18.10) field (1).
"false"	"true"	All members from different levels of the same PivotTable ([ISO/IEC29500-1:2011] section 18.10) cache hierarchy of this PivotTable ([ISO/IEC29500-1:2011] section 18.10) named set are displayed in the same PivotTable ([ISO/IEC29500-1:2011] section 18.10) field (1).

measuresSet: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set contains one or more PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) measure cache hierarchies. MUST be "false" if **ignore** is "true".

ignore	measureSet	Meaning
"true"	"false"	The ancestor cacheHierarchy element of type CT_CacheHierarchy ([ISO/IEC29500-4:2011] section A.2) of this PivotTable ([ISO/IEC29500-1:2011] section 18.10) named set is discarded.
"false"	"false"	The PivotTable ([ISO/IEC29500-1:2011] section 18.10) named set does not contain PivotTable ([ISO/IEC29500-1:2011] section 18.10) measure cache hierarchies.
"false"	"true"	The PivotTable ([ISO/IEC29500-1:2011] section 18.10) named set contains PivotTable ([ISO/IEC29500-1:2011] section 18.10) measure cache hierarchies.

hierarchizeDistinct: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to automatically order and remove duplicates from this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set. MUST be "false" if **ignore** is "true". If a CT_CalculatedMember element that corresponds to the **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named set exists, this attribute MUST be equal to **hierarchizeDistinct** attribute of the CT_CalculatedMember element.

ignore	hierarchizeDistinct	Meaning
"true"	"false"	The ancestor cacheHierarchy element of type CT_CacheHierarchy ([ISO/IEC29500-4:2011] section A.2) of this PivotTable ([ISO/IEC29500-1:2011] section 18.10) named set is discarded.
"false"	"false"	Do not automatically order and remove duplicates from this PivotTable ([ISO/IEC29500-1:2011] section 18.10) named set.
"false"	"true"	Automatically order and remove duplicates from this PivotTable ([ISO/IEC29500-1:2011] section 18.10) named set.

ignore: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the ancestor **cacheHierarchy** element of type **CT_CacheHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) SHOULD <9> be discarded. If **ignore** is "true", the ancestor **cacheHierarchy** element of type **CT_CacheHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) MUST have the following attribute values:

Field	Value
measure	"true"
set	"false"
attribute	"false"
measures	"false"
oneField	"false"
time	"false"
keyAttribute	"false"
memberValueDatatype	MUST NOT be specified.
unbalanced	MUST NOT be specified.
unbalancedGroup	MUST NOT be specified.
hidden	"false"
count	"0"
parentSet	MUST NOT be specified.
dimensionUniqueName	MUST NOT be specified.
defaultMemberUniqueName	MUST NOT be specified.
allUniqueName	MUST NOT be specified.
allCaption	MUST NOT be specified.

Field	Value
displayFolder	MUST NOT be specified.
measureGroup	MUST NOT be specified.
uniqueName	"DummyN", where N is the text string representing in decimal form the zero-based index of the ancestor CT_CacheHierarchy ([ISO/IEC29500-4:2011] section A.2) element within the group of CT_CacheHierarchy ([ISO/IEC29500-4:2011] section A.2) elements that have a descendent CT_CacheHierarchy element with the ignore attribute equal to "true".

Within the **CT_CacheHierarchies** ([ISO/IEC29500-4:2011] section A.2) element, all **CT_CacheHierarchy** ([ISO/IEC29500-4:2011] section A.2) elements that have a descendant CT_CacheHierarchy element with the **ignore** attribute equal to "true" MUST follow all other **CT_CacheHierarchy** ([ISO/IEC29500-4:2011] section A.2) elements without a descendant CT_CacheHierarchy element or with a descendant CT_CacheHierarchy element with the **ignore** attribute equal to "false".

If this attribute is "true", there MUST exist a **CT_DataField** ([ISO/IEC29500-4:2011] section A.2) element with an **fld** attribute equal to the zero-based index of a **CT_CacheField** ([ISO/IEC29500-4:2011] section A.2) element in the list of **CT_CacheField** ([ISO/IEC29500-4:2011] section A.2) elements specified by **CT_CacheFields** ([ISO/IEC29500-4:2011] section A.2) with a **hierarchy** attribute that specifies the ancestor **CT_CacheHierarchy** ([ISO/IEC29500-4:2011] section A.2). Additionally, that **CT_DataField** ([ISO/IEC29500-4:2011] section A.2) element MUST have a descendant **CT_DataField** element with a **sourceField** attribute specified.

For more details, see CT_DataField.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CacheHierarchy">
  <xsd:sequence>
    <xsd:element name="setLevels" minOccurs="0" maxOccurs="1" type="CT_SetLevels"/>
  </xsd:sequence>
  <xsd:attribute name="flattenHierarchies" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="measuresSet" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="hierarchizeDistinct" type="xsd:boolean" use="optional"
  default="true"/>
  <xsd:attribute name="ignore" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.25 CT_DataField

Target namespace: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main

Referenced by: [dataField](#)

This complex type specifies extended information about a **PivotTable** ([ISO/IEC29500-1:2011] section 18.10) data field (1) item ([ISO/IEC29500-1:2011] section 18.10.1.22).

Attributes:

pivotShowAs: An [ST_PivotShowAs](#) attribute that specifies the data display format for this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data field (1) item. If this attribute is specified, the **showDataAs** attribute of the ancestor **CT_DataField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element MUST NOT be specified. If this attribute is equal to "percentOfParent", "percentOfRunningTotal", "rankAscending", or "rankDescending", the **baseField** attribute of the ancestor **CT_DataField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element MUST be greater than or equal to 0.

sourceField: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the zero-based index of the **CT_PivotField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element in the list of **CT_PivotField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) elements specified by the **CT_PivotFields** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that this data item summarizes.

If an OLAP measure is summarized in a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) as a data field (1) item ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.22) more than one time, data field (1) items ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.22) that specify that OLAP measure after the first data field (1) item ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.22) that specifies that OLAP measure MUST have a descendant **CT_DataField** element with a **sourceField** specified.

If this attribute is specified, the **CT_PivotField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element specified by the **fld** attribute of the ancestor **CT_DataField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element MUST have a descendant **CT_PivotField** element with an **ignore** attribute equal to "true".

If this attribute is specified, the **CT_CacheField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element with a zero-based index in the list of **CT_CacheField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) elements specified by the **CT_CacheFields** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element equal to the **fld** attribute of the ancestor **CT_DataField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that exists in the Pivot Table Cache Definition part ([\[ISO/IEC29500-1:2011\]](#) section 12.3.12) specified by the **cacheId** attribute of the **CT_PivotTableDefinition** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that is the ancestor of this element MUST have a descendant **CT_CacheField** element. The **CT_CacheHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element specified by the **hierarchy** attribute of that **CT_CacheField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element MUST have a descendant **CT_CacheHierarchy** element with an **ignore** attribute equal to "true". The **CT_PivotHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element with a zero-based index in the list of **CT_PivotHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) elements specified by the **CT_PivotHierarchies** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element in this part that is equal to the zero-based index of that **CT_CacheHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element in the list of **CT_CacheHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) elements specified by the **CT_CacheHierarchies** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element MUST have a descendant **CT_PivotHierarchy** element.

If this attribute is specified, the **fld** attribute of the ancestor **CT_DataField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element SHOULD<10> be ignored.

This attribute MUST NOT be specified for non-OLAP PivotTables ([\[ISO/IEC29500-1:2011\]](#) section 18.10).

uniqueName: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the unique name for duplicated OLAP measures. MUST be unique within this part. MUST be less than or equal to 65,535 characters in length.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DataField">
  <xsd:attribute name="pivotShowAs" type="ST_PivotShowAs" use="optional"/>
</xsd:complexType>
```

```
<xsd:attribute name="sourceField" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="uniqueName" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.26 CT_Cfvo

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_ColorScale](#), [CT_DataBar](#), [CT_IconSet](#)

This complex type specifies a Conditional Formatting Value Object (CFVO) that specifies how to calculate a value from the range of cells to which a conditional formatting rule applies.

Child Elements:

xf: An [f](#) element that specifies the formula that is evaluated and compared to the **cell value** by the comparison method specified by **gte**. The formula MUST adhere to the grammar provided in [Formulas](#), with the following restrictions:

- MUST NOT use the ref-infix-operator, book-prefix, local-cell-reference, bang-reference, bang-name, array-constant, sheet-range-reference or structure-reference production rules.
- MUST NOT use the A1-relative-column production rule except from the A1-absolute-column production rule, and it MUST NOT use the A1-relative-row production rule except from the A1-absolute-row production rule.
- MUST NOT match the single-sheet-area production rule.

extLst: A [CT_ExtensionList](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

type: An [ST_CfvoType](#) attribute that specifies how the CFVO value is determined:

- If this CT_Cfvo element is a child of a CT_ColorScale and specifies the beginning of the **color scale**, this attribute MUST NOT be max.
- If this CT_Cfvo element is a child of a CT_ColorScale and specifies the end of the color scale, this attribute MUST NOT be min.
- If this CT_Cfvo element is a child of a CT_ColorScale and specifies the midpoint of the color scale, this attribute MUST NOT be max and MUST NOT be min.
- If this CT_Cfvo element is a child of a CT_DataBar and specifies the cell value for the min length of the **data bar**, this attribute MUST NOT be max or autoMax.
- If this CT_Cfvo element is a child of a CT_DataBar and specifies the cell value for the max length of the data bar, this attribute MUST NOT be min or autoMin.
- If this CT_Cfvo element is not a child of a CT_DataBar, this attribute MUST NOT be autoMin and MUST NOT be autoMax.
- If this CT_Cfvo element is a child of a CT_IconSet record, this value MUST NOT be max or min.

- If the value is max, min, autoMax, or autoMin, **f** MUST NOT be present.

gte: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the CT_Cfvo will use greater-than or greater-than-or-equal-to when applying conditional formatting rules. If this CT_Cfvo element is a child of something other than a CT_IconSet element, this attribute MUST NOT be present. The value of this attribute is interpreted as follows:

Value	Meaning
"false"	Greater-than is used when applying conditional formatting rules.
"true"	Greater-than-or-equal-to is used when applying conditional formatting rules.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Cfvo">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="type" type="ST_CfvoType" use="required"/>
  <xsd:attribute name="gte" type="xsd:boolean" use="optional" default="true"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.27 CT_CfRule

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_ConditionalFormatting](#)

This complex type specifies a conditional formatting rule for a range.

Child Elements:

xm:f: **f** elements that specify the formulas in the conditional formatting rule. The formulas MUST adhere to the grammar specified in [Formulas](#), with the following restrictions:

- The formula MUST NOT conform to the ref-infix-operator, book-prefix, local-cell-reference, array-constant, bang-reference, bang-name, sheet-range-reference, or structure-reference production rules.
- The formula MUST NOT match the single-sheet-area production rule.

The following table explains how to interpret the formulas.

Value of type	Interpretation of the formulas in f
cellIs	f elements that specify the formulas, numeric values, or cell references that specify the operands for the ST_ConditionalFormattingOperator ([ISO/IEC29500-1:2011] section 18.18.15) specified by operator . If operator is "between" or "notBetween", f MUST contain two formulas; otherwise, f MUST contain one formula.

Value of type	Interpretation of the formulas in f
expression	An f element that specifies a formula. When the formula returns zero, conditional formatting is not displayed. When the formula returns a nonzero value, conditional formatting is displayed.
colorScale, dataBar, iconSet	An f element that specifies a formula. When the formula returns zero, conditional formatting is not displayed. When the formula returns a nonzero value, or is not present, conditional formatting is displayed.
containsText, notContainsText, beginsWith, endsWith, containsBlanks, notContainsBlanks, containsErrors, notContainsErrors	An f element that specifies a formula that implements the operation specified by type . When the formula returns zero, conditional formatting is not displayed. When the formula returns a nonzero value, conditional formatting is displayed.

colorScale: A [CT_ColorScale](#) element that specifies a color scale.

dataBar: A [CT_DataBar](#) element that specifies a data bar.

iconSet: A [CT_IconSet](#) element that specifies an **icon set**.

dx: A [CT_Dxf](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies the differential formatting ([\[ISO/IEC29500-1:2011\]](#) section M.2.7.3.8) applied to the range. If **type** is "colorScale", "dataBar", or "iconSet", or the **priority** attribute does not exist, this element MUST NOT exist.

extLst: A [CT_ExtensionList](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

type: An [ST_CfType](#) ([\[ISO/IEC29500-1:2011\]](#) section 18.18.12) attribute that specifies the way conditional formatting is displayed in the range.

If and only if **type** is "colorScale", a **colorScale** child element MUST exist in this element.

If and only if **type** is "dataBar", a **dataBar** child element MUST exist in this element.

If and only if **type** is "iconSet", an **iconSet** child element MUST exist in this element.

priority: An [int](#) ([\[XMLSCHEMA2\]](#) section 3.3.17) attribute that specifies the relative priority of this rule compared to the other rules in this sheet (1), or whether this [CT_CfRule](#) specifies extension information for a conditional formatting data bar rule as specified by the associated [CT_CfRule](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element. MUST be greater than 0.

If **priority** exists, rules are applied in order from the smallest **priority** to the largest **priority** and it MUST NOT duplicate a **priority** value in any other [CT_CfRule](#) or [CT_CfRule](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that exists in the same worksheet part.

If **priority** does not exist, this [CT_CfRule](#) specifies extension information for a conditional formatting data bar rule, and the **dataBar** child element MUST exist and describe this additional information. The **id** attribute is used to identify the associated [CT_CfRule](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2), and the **priority** attribute of this [CT_CfRule](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) specifies the relative priority of this rule. If neither the **priority** attribute nor the **id** attribute exists in this

element, or if **id** exists but there exists no **CT_CfRule** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element containing a matching **GUID**, this record and the succeeding **dataBar** child element MUST be ignored. If the **priority** attribute exists in this element, **id** MUST be ignored.

stopIfTrue: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether evaluation of additional conditional formatting rules is skipped for a cell if this rule evaluates to "true" for that cell.

Value	Meaning
"true"	Evaluation of additional conditional formatting rules is skipped for a cell if this rule evaluates to "true" for that cell.
"false"	Evaluation of additional conditional formatting rules is not skipped for a cell if this rule evaluates to "true" for that cell.

aboveAverage: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the conditional formatting rule is applied to cells with values above or below the average value of other cells in the range as specified by the following table. This attribute MUST NOT exist if **type** is not equal to "aboveAverage".

Value	Meaning
"true"	The conditional formatting rule is applied to cells with values above the average value of all cells in the range.
"false"	The conditional formatting rule is applied to cells with values below the average value of all cells in the range.

percent: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the conditional formatting rule is applied to a percentage of cells as specified by the following table. This attribute MUST NOT exist if **type** is not equal to "top10".

Value	Meaning
"true"	rank specifies the percentage of cells in the range to which conditional formatting is applied.
"false"	The conditional formatting rule is applied to the number of cells specified by rank .

bottom: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies how the conditional formatting rule is applied as specified by the following table. This attribute MUST NOT exist if **type** is not equal to "top10".

Value	Meaning
"true"	Conditional formatting is applied to cells whose value is in the bottom end of the range specified by percent and rank .
"false"	Conditional formatting is applied to cells whose value is in the top end of the range specified by percent and rank .

operator: An **ST_ConditionalFormattingOperator** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.15) attribute that specifies the type of value comparison used for this conditional formatting rule. This attribute MUST NOT exist if **type** is not equal to "cellIs".

text: A **string** ([\[XMLSCHEMA2\]](#) section 3.2.1) attribute that specifies a text value used for this conditional formatting rule. This attribute MUST NOT exist if type is not equal to "beginsWith", "containsText", "endsWith", or "notContainsText".

timePeriod: An **ST_TimePeriod** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.82) attribute that specifies the time period used for this conditional formatting rule. This attribute MUST NOT exist if **type** is not equal to "timePeriod".

rank: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies how many cells are formatted by this conditional formatting rule. The value of **percent** specifies whether **rank** is a percentage or a quantity of cells. When **percent** is "true", **rank** MUST be greater than or equal to zero and less than or equal to 100. Otherwise, **rank** MUST be greater than or equal to 1 and less than or equal to 1,000. This attribute MUST NOT exist if **type** is not equal to "top10".

stdDev: An **int** ([\[XMLSCHEMA2\]](#) section 3.3.17) attribute that specifies the number of standard deviations above or below the average to format in the conditional formatting rule. This attribute MUST NOT exist if **type** is not equal to "aboveAverage" or if **equalAverage** is "true".

equalAverage: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies, together with **aboveAverage**, how the conditional formatting rule is applied as specified by the following table. This attribute MUST NOT exist if **type** is not equal to "aboveAverage".

Value of equalAverage	Value of aboveAverage	Meaning
"true"	"true"	Conditional formatting is applied to cells whose value is equal to or above the average value of cells in the range.
"true"	"false"	Conditional formatting is applied to cells whose value is equal to or below the average value of cells in the range.
"false"	"true"	Conditional formatting is applied to cells whose value is above the average value of all cells in the range plus stdDev and multiplied by the standard deviation of all cells in the range.
"false"	"false"	Conditional formatting is applied to cells whose value is below the average value of all cells in the range minus stdDev and multiplied by the standard deviation of all cells in the range.

activePresent: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that MUST be "true" if, and only if, a formula is present in **f** and **type** is "colorScale", "dataBar", or "iconSet".

id: An **ST_Guid** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.4) attribute that identifies this conditional formatting rule. If the **priority** attribute does not exist, and this attribute exists, this attribute is used to match this CT_CfRule element to the corresponding **CT_CfRule** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element. If neither the **priority** attribute nor this attribute exists, this CT_CfRule and its child CT_DataBar element MUST be ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CfRule">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="0" maxOccurs="3"/>
    <xsd:element name="colorScale" type="CT_ColorScale" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="dataBar" type="CT_DataBar" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="iconSet" type="CT_IconSet" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

```

    <xsd:element name="dxf" type="x:CT_Dxf" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="type" type="x:ST_CfType" use="optional"/>
  <xsd:attribute name="priority" type="xsd:int" use="optional"/>
  <xsd:attribute name="stopIfTrue" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="aboveAverage" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="percent" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="bottom" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="operator" type="x:ST_ConditionalFormattingOperator" use="optional"/>
  <xsd:attribute name="text" type="xsd:string" use="optional"/>
  <xsd:attribute name="timePeriod" type="x:ST_TimePeriod" use="optional"/>
  <xsd:attribute name="rank" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="stdDev" type="xsd:int" use="optional"/>
  <xsd:attribute name="equalAverage" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="activePresent" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="id" type="x:ST_Guid" use="optional"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.28 CT_IconSet

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_CfRule](#)

A complex type that specifies the properties of a conditional formatting rule that uses an icon set. The first **cfvo** element following this element MUST be ignored. There MUST be greater than or equal to three **cfvo** elements and MUST be less than or equal to five **cfvo** elements following this complex type.

Child Elements:

cfvo: A [CT_Cfvo](#) element that specifies a threshold value between each icon in the icon set.

cfIcon: A [CT_CfIcon](#) element that specifies a particular icon to use within an icon set. This element MUST be present if and only if **custom** equals "true".

Attributes:

iconSet: An [ST_IconSetType](#) attribute that specifies the icon set used.

showValue: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the cells in the applied range display the icon and cell value, or the icon only.

Value	Meaning
"true"	The icon and cell value are shown in the cell.
"false"	Only the icon is shown in the cell.

percent: Undefined and MUST be ignored.

reverse: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the icons in the icon set specified in **iconSet** are shown in reverse order. If **custom** equals "true" this value MUST be ignored.

Value	Meaning
"true"	The icons specified in iconSet are shown in reverse order.
"false"	The icons specified in iconSet are shown in the order defined by the icon set.

custom: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether a custom set of icons is used. If this value is "true", there MUST be the same number of **cfIcon** elements as **cfvo** elements and the icons specified by the **cfIcon** elements are used rather than those specified by **iconSet**. If this value is "false", there MUST be 0 **cfIcon** elements.

Value	Meaning
"false"	No custom set of icons is used.
"true"	A custom set of icons is used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_IconSet">
  <xsd:sequence>
    <xsd:element name="cfvo" type="CT_Cfvo" minOccurs="2" maxOccurs="unbounded"/>
    <xsd:element name="cfIcon" type="CT_CfIcon" minOccurs="0" maxOccurs="5"/>
  </xsd:sequence>
  <xsd:attribute name="iconSet" type="ST_IconSetType" use="optional"
default="3TrafficLights1"/>
  <xsd:attribute name="showValue" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="percent" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="reverse" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="custom" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.29 CT_ColorScale

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_CfRule](#)

A complex type that specifies a color scale used in conditional formatting.

Child Elements:

cfvo: A [CT_Cfvo](#) element that specifies the cell values corresponding to the interpolation colors of the color scale. The **CT_ColorScale** MUST have either two or three child [CT_Cfvo](#) elements.

If there are two child [CT_Cfvo](#) elements present, the first child [CT_Cfvo](#) element specifies the cell value corresponding to the beginning color of the color scale. The second child [CT_Cfvo](#) element specifies the cell value corresponding to the end color of the color scale.

If there are three child [CT_Cfvo](#) elements present, the first child [CT_Cfvo](#) element specifies the cell value corresponding to the beginning color of the color scale. The second child [CT_Cfvo](#) element specifies the cell value corresponding to the midpoint color of the color scale. The third child [CT_Cfvo](#) element specifies the cell value corresponding to the end color of the color scale.

color: A **CT_Color** ([ISO/IEC29500-4:2011] section A.2) element that specifies the interpolation colors of the color scale for the **cfvo** element at the same corresponding position. The **CT_ColorScale** MUST have either two or three child **CT_Color** ([ISO/IEC29500-4:2011] section A.2) elements, and the number of child elements MUST equal the number of **CT_Cfvo** child elements.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ColorScale">
  <xsd:sequence>
    <xsd:element name="cfvo" type="CT_Cfvo" minOccurs="2" maxOccurs="unbounded"/>
    <xsd:element name="color" type="x:CT_Color" minOccurs="2" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.30 CT_DataBar

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_CfRule](#)

A complex type that specifies a data bar used in conditional formatting.

Child Elements:

cfvo: A **CT_Cfvo** element (section 2.6.26) that specifies the cell values corresponding to the min/max length of the data bar. If there exist **CT_Cfvo** ([ISO/IEC29500-4:2011] section A.2) elements in this sheet (1) that are child elements of a **CT_DataBar** ([ISO/IEC29500-4:2011] section A.2) element that is a child of a **CT_CfRule** ([ISO/IEC29500-4:2011] section A.2) element that is a parent of a **CT_ExtensionList** ([ISO/IEC29500-4:2011] section A.2) element with a child **CT_Extension** ([ISO/IEC29500-4:2011] section A.2) element that has a child **ST_Guid** ([ISO/IEC29500-4:2011] section A.2) element equal to the **id** attribute of this complex type's parent **CT_CfRule** element (section 2.6.27), those **CT_Cfvo** elements SHOULD<11> be ignored. The first child **CT_Cfvo** element specifies the **condition** corresponding to the min length of the data bar. The second child **CT_Cfvo** element specifies the condition corresponding to the max length of the data bar.

fillColor: A **CT_Color** ([ISO/IEC29500-4:2011] section A.2) element that specifies the fill color of the data bar. This element MUST exist if and only if the **priority** attribute of the **CT_CfRule** that is a parent of this complex type exists.

borderColor: A **CT_Color** element that specifies the border color of the data bar. This element MUST exist if and only if **border** equals "true".

negativeFillColor: A **CT_Color** element that specifies the negative fill color of the data bar. This element MUST exist if and only if **negativeBarColorSameAsPositive** equals "false".

negativeBorderColor: A **CT_Color** element that specifies the negative border color of the data bar. This element MUST exist if and only if **negativeBarBorderColorSameAsPositive** equals "false" and **border** equals "true".

axisColor: A **CT_Color** element that specifies the axis color of the data bar. This element MUST exist if and only if **axisPosition** does not equal "none".

Attributes:

minLength: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the length of the shortest data bar in this conditional formatting range, expressed as a percentage of the width of the cell containing the data bar. MUST be greater than or equal to zero and less than or equal to **maxLength**. If, in this same worksheet part, there exists a **CT_ExtensionList** element that is a descendent of a **CT_CfRule** with a child **CT_Extension** element with the child **ST_Guid** element equal to the **id** attribute of the **CT_CfRule** element that is a parent of this element, and the **minLength** attribute of this element is zero ("0") and the **maxLength** attribute of this element is "100", the **minLength** attribute of the **CT_DataBar** element that is a descendent of the **CT_CfRule** element that is a parent of the **CT_ExtensionList** element that is a parent of the **CT_Extension** element with the child **ST_Guid** element equal to the **id** attribute of the **CT_CfRule** element that is a parent of this element MUST be "10". If in this same worksheet part there exists an **CT_ExtensionList** element that is a descendent of a **CT_CfRule** with a child **CT_Extension** element with the child **ST_Guid** element equal to the **id** attribute of the **CT_CfRule** element that is a parent of this element, and the **minLength** attribute of this element is not zero ("0") or the **maxLength** attribute of this element is not "100", the **minLength** attribute of the **CT_DataBar** element that is a descendent of the **CT_CfRule** element that is a parent of the **CT_ExtensionList** element that is a parent of the **CT_Extension** element with the child **ST_Guid** element that is equal to the **id** attribute of the **CT_CfRule** element that is a parent of this element MUST be equal to this complex type's **minLength**.

maxLength: An **unsignedInt** attribute that specifies the length of the longest data bar in this conditional formatting range, expressed as a percentage of the width of the cell being formatted. MUST be greater than or equal to **minLength** and less than or equal to 100. If in this same worksheet part there exists a **CT_ExtensionList** element that is a descendent of a **CT_CfRule** with a child **CT_Extension** element with the child **ST_Guid** element equal to the **id** attribute of the **CT_CfRule** element that is a parent of this element, and the **minLength** attribute of this element is zero ("0") and the **maxLength** attribute of this element is "100", the **maxLength** attribute of the **CT_DataBar** element that is a descendent of the **CT_CfRule** element that is a parent of the **CT_ExtensionList** element that is a parent of the **CT_Extension** element with the child **ST_Guid** element that is equal to the **id** attribute of the **CT_CfRule** element that is a parent of this element MUST be "90". If, in this same worksheet part, there exists a **CT_ExtensionList** element that is a descendent of a **CT_CfRule** with a child **CT_Extension** element with the child **ST_Guid** element equal to the **id** attribute of the **CT_CfRule** element that is a parent of this element, and the **minLength** attribute of this element is not zero ("0") or the **maxLength** attribute of this element is not "100", the **maxLength** attribute of the **CT_DataBar** element that is a descendent of the **CT_CfRule** element that is a parent of the **CT_ExtensionList** element that is a parent of the **CT_Extension** element with the child **ST_Guid** element that is equal to the **id** attribute of the **CT_CfRule** element that is a parent of this element MUST be equal to this record's **maxLength**.

showValue: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the cells in the conditional formatting range display both the data bar and the numeric value or only the data bar. The following table describes its possible values.

Value	Meaning
"false"	Only the data bar is displayed in the cell.
"true"	Both the data bar and the numeric value are displayed in the cell.

border: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the data bar has a border.

Value	Meaning
"true"	The data bar has a border.
"false"	The data bar has no border.

gradient: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the data bar has a gradient fill. The following table describes its possible values.

Value	Meaning
"false"	The data bar fill is a solid color.
"true"	The data bar fill is a gradient.

direction: An **ST_DataBarDirection** attribute (section [2.7.7](#)) that specifies the direction of the data bar.

negativeBarColorSameAsPositive: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the data bar has a negative bar color that is different from the positive bar color.

negativeBarBorderColorSameAsPositive: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the data bar has a negative border color that is different from the positive border color.

axisPosition: An **ST_DataBarAxisPosition** attribute (section [2.7.8](#)) that specifies the axis position for the data bar.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DataBar">
  <xsd:sequence>
    <xsd:element name="cfvo" type="CT_Cfvo" minOccurs="2" maxOccurs="2"/>
    <xsd:element name="fillColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="borderColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="negativeFillColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="negativeBorderColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="axisColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="minLength" type="xsd:unsignedInt" use="optional" default="10"/>
  <xsd:attribute name="maxLength" type="xsd:unsignedInt" use="optional" default="90"/>
  <xsd:attribute name="showValue" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="border" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="gradient" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="direction" type="ST_DataBarDirection" use="optional"
  default="context"/>
  <xsd:attribute name="negativeBarColorSameAsPositive" type="xsd:boolean" use="optional"
  default="false"/>
  <xsd:attribute name="negativeBarBorderColorSameAsPositive" type="xsd:boolean"
  use="optional" default="true"/>
  <xsd:attribute name="axisPosition" type="ST_DataBarAxisPosition" use="optional"
  default="automatic"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.31 CT_PivotField

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [pivotField](#)

This complex type specifies additional properties of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) field (1).

Attributes:

fillDownLabels: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) item labels are repeated for this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) field (1). This attribute is ignored when the **compact** attribute and the **outline** attribute of the **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) field (1) are "true". This attribute is ignored if the **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) field (1) is not on the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) row (2) axis or the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) column (2) axis. This value **MUST** be one of the following:

Value	Meaning
"false"	The item labels are not repeated.
"true"	The item labels are repeated for each nested item.

ignore: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) field (1) **SHOULD** [<12>](#) be ignored.

If this attribute is "true", the ancestor **CT_PivotField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) **MUST** have only the following attributes specified, and these attributes **MUST** have the following values.

Name	Value
compact	"false"
dataField	"true"
defaultSubtotal	"false"
dragOff	"false"
dragToCol	"false"
dragToData	"false"
dragToPage	"false"
dragToRow	"false"
includeNewItemInFilter	"true"
itemPageCount	"false"
outline	"false"
showAll	"false"

Name	Value
subtotalTop	"false"
topAutoShow	"false"

If this attribute is equal to "true", there MUST exist a **CT_DataField** ([ISO/IEC29500-4:2011] section A.2) element with an **fld** attribute that specifies this PivotTable ([ISO/IEC29500-1:2011] section 18.10) field (1). Additionally, that **CT_DataField** ([ISO/IEC29500-4:2011] section A.2) element MUST have a descendant **CT_DataField** element with a **sourceField** attribute specified.

For more details, see CT_DataField.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotField">
  <xsd:attribute name="fillDownLabels" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="ignore" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.32 CT_PivotTableDefinition

Target namespace: http://schemas.microsoft.com/office/spreadsheetml/2009/9/main

Referenced by: [pivotTableDefinition](#)

This element specifies additional properties of a PivotTable ([ISO/IEC29500-1:2011] section 18.10) view.

Child Elements:

pivotEdits: A [CT_PivotEdits](#) element that specifies a collection of [PivotTable What-if Analysis](#) edits.

pivotChanges: A [CT_PivotChanges](#) element that specifies a collection of PivotTable What-if Analysis changes.

conditionalFormats: A [CT_ConditionalFormats](#) element that specifies a collection of conditional formats applied to the PivotTable ([ISO/IEC29500-1:2011] section 18.10) view.

Attributes:

fillDownLabelsDefault: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies the behavior of **PivotTable** ([ISO/IEC29500-1:2011] section 18.10) fields (1) that are not a part of the PivotTable ([ISO/IEC29500-1:2011] section 18.10) view if they are later added to a PivotTable ([ISO/IEC29500-1:2011] section 18.10) view. MUST be a value from the following table.

Value	Meaning
"false"	Specifies that PivotTable ([ISO/IEC29500-1:2011] section 18.10) fields (1) added to the PivotTable ([ISO/IEC29500-1:2011] section 18.10) view behave as if the fillDownLabels attribute of the CT_PivotField elements associated with those PivotTable ([ISO/IEC29500-1:2011] section 18.10) fields (1) are set to "false".

Value	Meaning
"true"	Specifies that PivotTable ([ISO/IEC29500-1:2011] section 18.10) fields (1) added to the PivotTable ([ISO/IEC29500-1:2011] section 18.10) view behave as if the fillDownLabels attribute of the CT_PivotField elements associated with those PivotTable ([ISO/IEC29500-1:2011] section 18.10) fields (1) are set to "true".

visualTotalsForSets: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether hidden PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) items will be included when calculating totals for **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) named sets. MUST be a value from the following table.

Value	Meaning
"false"	Include hidden PivotTable ([ISO/IEC29500-1:2011] section 18.10) items in the set totals.
"true"	Do not include hidden PivotTable ([ISO/IEC29500-1:2011] section 18.10) items in the set totals.

calculatedMembersInFilters: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) OLAP-calculated members participate in PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) manual filters and PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) advanced filters.

Value	Meaning
"false"	PivotTable ([ISO/IEC29500-1:2011] section 18.10) OLAP-calculated members do not participate in PivotTable ([ISO/IEC29500-1:2011] section 18.10) manual filters and PivotTable ([ISO/IEC29500-1:2011] section 18.10) advanced filters.
"true"	PivotTable ([ISO/IEC29500-1:2011] section 18.10) OLAP-calculated members participate in PivotTable ([ISO/IEC29500-1:2011] section 18.10) manual filters and PivotTable ([ISO/IEC29500-1:2011] section 18.10) advanced filters as do other PivotTable ([ISO/IEC29500-1:2011] section 18.10) items.

altText: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the alternate text for the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view. The string MUST be less than or equal to 2,000 characters in length.

altTextSummary: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the alternate text summary for the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view. This string MUST be less than or equal to 2,000 characters in length.

enableEdit: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether PivotTable what-if analysis is enabled for the current PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view.

autoApply: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether PivotTable what-if analysis values are automatically allocated.

allocationMethod: An **ST_AllocationMethod** attribute that specifies the allocation method to use for PivotTable what-if analysis.

weightExpression: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the multidimensional expression (MDX) of the weight expression for weighted allocations of PivotTable what-if analysis values. This string MUST be less than or equal to 65,535 characters in length.

hideValuesRow: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies whether the values row (2) in the PivotTable ([ISO/IEC29500-1:2011] section 18.10) report is visible.

Value	Meaning
"false"	The values row (2) in the PivotTable ([ISO/IEC29500-1:2011] section 18.10) report is visible.
"true"	The values row (2) in the PivotTable ([ISO/IEC29500-1:2011] section 18.10) report is not visible.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotTableDefinition">
  <xsd:sequence>
    <xsd:element name="pivotEdits" type="CT_PivotEdits" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="pivotChanges" type="CT_PivotChanges" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="conditionalFormats" type="CT_ConditionalFormats" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="fillDownLabelsDefault" type="xsd:boolean" use="optional"
  default="false"/>
  <xsd:attribute name="visualTotalsForSets" type="xsd:boolean" use="optional"
  default="false"/>
  <xsd:attribute name="calculatedMembersInFilters" type="xsd:boolean" use="optional"
  default="false"/>
  <xsd:attribute name="altText" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="altTextSummary" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="enableEdit" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="autoApply" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="allocationMethod" type="ST_AllocationMethod" use="optional"
  default="equalAllocation"/>
  <xsd:attribute name="weightExpression" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="hideValuesRow" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.33 CT_PivotCacheDefinition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [pivotCacheDefinition](#)

A complex type that specifies the extended properties of a PivotTable ([ISO/IEC29500-1:2011] section 18.10) **PivotCache** definition.

Attributes:

slicerData: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies whether the [Slicer Cache Relationship to PivotCache](#). MUST be "true" if the OLAP PivotTable ([ISO/IEC29500-1:2011] section 18.10) **PivotCache** definition is being referenced by a [slicer cache](#).

pivotCacheId: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute which uniquely identifies this PivotTable ([ISO/IEC29500-1:2011] section 18.10) PivotCache. The value MUST be greater than or equal to zero. The value MUST NOT be zero if there is a slicer cache that uses this PivotTable ([ISO/IEC29500-1:2011] section 18.10) PivotCache as a data source (1), or if there is a [CT_PivotCacheIdVersion](#) element that is preceded by this element.

supportSubqueryNonVisual: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies whether the OLAP source data of this PivotTable ([ISO/IEC29500-1:2011] section 18.10) supports hidden PivotTable items.

supportSubqueryCalcMem: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies whether the OLAP source data of this PivotTable supports PivotTable calculated members in an **OLAP subselect** for filtering.

Value	Meaning
"true"	The OLAP source data of this PivotTable supports PivotTable calculated members in an OLAP subselect for filtering.
"false"	The OLAP source data of this PivotTable does not support PivotTable calculated members in an OLAP subselect for filtering.

supportAddCalcMems: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies whether PivotTable ([ISO/IEC29500-1:2011] section 18.10) calculated members are shown for filtering.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotCacheDefinition">
  <xsd:attribute name="slicerData" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="pivotCacheId" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="supportSubqueryNonVisual" type="xsd:boolean" use="optional"
  default="false"/>
  <xsd:attribute name="supportSubqueryCalcMem" type="xsd:boolean" use="optional"
  default="false"/>
  <xsd:attribute name="supportAddCalcMems" type="xsd:boolean" use="optional"
  default="false"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.34 CT_Connection

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [connection](#)

A complex type that specifies the extended properties of an external connection ([ISO/IEC29500-1:2011] section 18.13).

Child Elements:

calculatedMembers: A **CT_CalculatedMembers** ([ISO/IEC29500-4:2011] section A.2) element that specifies a list of PivotTable ([ISO/IEC29500-1:2011] section 18.10) OLAP-calculated members associated with this external connection ([ISO/IEC29500-1:2011] section 18.13). If this external connection ([ISO/IEC29500-1:2011] section 18.13) is associated with a PivotTable ([ISO/IEC29500-1:2011] section 18.10) PivotCache, the list MUST NOT exist. If this element exists, the ancestor **CT_connection** ([ISO/IEC29500-4:2011] section A.2) element of this element MUST have a child **CT_OlapPr** ([ISO/IEC29500-1:2011] section 18.13.5) element.

Attributes:

culture: An **ST_Xstring** ([ISO/IEC29500-1:2011] section 22.9.2.19) attribute that specifies the language associated with this external connection ([ISO/IEC29500-1:2011] section 18.13). The length of this string MUST be less than 85 characters. If the length of this string is greater than 0, the contents of this string MUST **<13>** be a language tag as specified by [RFC3066]. If this attribute is not present, the data connection (2) is using the server language.

embeddedDataId: An **ST_Xstring** ([ISO/IEC29500-1:2011] section 22.9.2.19) attribute that specifies an embedded **Custom Data** part. The length of this value MUST be less than 65,536 characters. If the length of this string is greater than 0, the contents of this string MUST be equal to the **id** attribute of a **CT_DatastoreItem** element, in a **Custom Data Properties** part in this package ([ISO/IEC29500-1:2011] section 9).

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Connection">
  <xsd:sequence>
    <xsd:element name="calculatedMembers" type="x:CT_CalculatedMembers" minOccurs="0"
maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="culture" use="optional" type="x:ST_Xstring"/>
  <xsd:attribute name="embeddedDataId" use="optional" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.35 CT_Table

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [table](#)

A complex type that specifies alternate text properties for the table.

Attributes:

altText: An **ST_Xstring** ([ISO/IEC29500-1:2011] section 22.9.2.19) attribute that specifies the alternate text for the table. The string MUST be less than or equal to 25,000 characters in length.

altTextSummary: An **ST_Xstring** ([ISO/IEC29500-1:2011] section 22.9.2.19) attribute that specifies the alternate text summary for the table. The string MUST be less than or equal to 50,000 characters in length.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Table">
  <xsd:attribute name="altText" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="altTextSummary" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.36 CT_CfIcon

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_IconSet](#)

A complex type that specifies a single icon of an icon set.

Attributes:

iconSet: An [ST_IconSetType](#) attribute that specifies the icon set.

iconId: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the icon to be used. If the icon set specified by **iconSet** has three icons, this value **MUST** be less than or equal to 2. If the icon set specified by **iconSet** has four icons, this value **MUST** be less than or equal to 3. If the icon set specified by **iconSet** has five icons, this value **MUST** be less than or equal to 4. If **iconSet** equals "NoIcons", this value **MUST** be 0.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CfIcon">
  <xsd:attribute name="iconSet" type="ST_IconSetType" use="required"/>
  <xsd:attribute name="iconId" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.37 CT_PivotEdits

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotTableDefinition](#)

A complex type that specifies user inputs related to [PivotTable what-if analysis](#) in single cells of the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area. It also specifies the collections of MDX unique names that identify the values in the OLAP data source (1), and specifies the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) rules that can be used to identify the cells in the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area.

Child Elements:

pivotEdit: A [CT_PivotEdit](#) element that specifies user input, related to PivotTable what-if analysis, in a single cell of the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area, and specifies the collection of MDX unique names that identifies the value in the OLAP data source (1), and specifies a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) rule that can be used to identify the cell in the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotEdits">
  <xsd:sequence>
    <xsd:element name="pivotEdit" minOccurs="1" maxOccurs="unbounded" type="CT_PivotEdit"/>
  </xsd:sequence>
```

```
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.38 CT_PivotEdit

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotEdits](#)

A complex type that specifies user input, related to [PivotTable what-if analysis](#), in a single cell of the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area.

Child Elements:

userEdit: A [CT_PivotUserEdit](#) element that specifies the user input value or formula that replaces the original cell value, in a single cell of the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area.

tupleItems: A [CT_TupleItems](#) element that specifies the MDX unique names that identify the value in the OLAP data source (1) that was changed using PivotTable what-if analysis.

pivotArea: A [CT_PivotArea](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) rule that can be used to identify the cell in the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area.

extLst: A [CT_ExtensionList](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) that specifies future extensibility for this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotEdit">
  <xsd:sequence>
    <xsd:element name="userEdit" type="CT_PivotUserEdit" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="tupleItems" type="CT_TupleItems" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="pivotArea" type="x:CT_PivotArea" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.39 CT_PivotChanges

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotTableDefinition](#)

A complex type that specifies the values used for [PivotTable what-if analysis](#) calculations and specifies the allocation methods for how to apply the values. It also specifies the collections of MDX unique names that identify the original values in the OLAP data source (1) that were changed.

Child Elements:

pivotChange: A [CT_PivotChange](#) element that specifies the value used for PivotTable what-if analysis calculation and specifies the allocation method for how to apply the value. It also specifies a collection of MDX unique names that identifies the original value in the OLAP data source (1) that was changed.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotChanges">
  <xsd:sequence>
    <xsd:element name="pivotChange" minOccurs="1" maxOccurs="unbounded"
type="CT_PivotChange"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.40 CT_PivotChange

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotChanges](#)

A complex type that specifies the value used for [PivotTable what-if analysis](#) calculation and specifies the allocation method for how to apply the value. It also specifies a collection of MDX unique names that identifies the original value in the OLAP data source (1) that was changed.

Child Elements:

editValue: A [CT_PivotEditValue](#) element that specifies the value that replaces the original value in the OLAP data source (1) for the PivotTable what-if analysis.

tupleItems: A [CT_TupleItems](#) element that specifies the MDX unique names that identify the value in the OLAP data source (1) that was changed using PivotTable what-if analysis.

extLst: A [CT_ExtensionList](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) that specifies future extensibility for this element.

Attributes:

allocationMethod: An [ST_AllocationMethod](#) attribute that specifies the allocation method, used by PivotTable what-if analysis, to change the value in the OLAP data source (1).

weightExpression: An [ST_Xstring](#) ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the **OLAP weight expression** for PivotTable what-if analysis. The **weightExpression** MUST NOT exist if **allocationMethod** equals `equalAllocation` or `equalIncrement`. The **weightExpression** MUST be greater than or equal to 0 and less than or equal to 65,535 characters in length.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotChange">
  <xsd:sequence>
    <xsd:element name="editValue" type="CT_PivotEditValue" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="tupleItems" type="CT_TupleItems" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

```

    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="allocationMethod" type="ST_AllocationMethod"
    default="equalAllocation"/>
  <xsd:attribute name="weightExpression" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.41 CT_PivotUserEdit

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotEdit](#)

A complex type that specifies user input, related to [PivotTable what-if analysis](#), in a single cell of the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area.

Child Elements:

xm:f: An [f](#) element that specifies a formula. The formula MUST adhere to the grammar provided in [Formulas](#), with the following restriction: The **formula** MUST NOT use the bang-reference or bang-name production rules.

editValue: A [CT_PivotEditValue](#) element that specifies the user input value that replaces the original cell value, in a single cell of the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_PivotUserEdit">
  <xsd:choice minOccurs="1" maxOccurs="1">
    <xsd:element ref="xm:f" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="editValue" type="CT_PivotEditValue" minOccurs="1" maxOccurs="1"/>
  </xsd:choice>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.42 CT_PivotEditValue

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotUserEdit](#), [CT_PivotChange](#)

A complex type that specifies the value type of the user input in the single cell of the PivotTable, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10, data area, or value type of the value that replaces the original value in the OLAP data source (1) for PivotTable what-if analysis, as specified in section [2.3.1](#).

Attributes:

valueType: An **ST_PivotEditValueType** attribute, as specified in section [2.7.11](#), that specifies the type of the value of the user input or the type of the value that replaces the original value in the OLAP data source (1).

The length of the string **MUST** be greater than zero and **MUST** be less than 32,768 characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotEditValue">
  <xsd:simpleContent>
    <xsd:extension base="x:ST_Xstring">
      <xsd:attribute name="valueType" use="required" type="ST_PivotEditValueType"/>
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.43 CT_TupleItems

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotEdit](#), [CT_PivotChange](#)

A complex type that specifies the MDX unique names that identify the value in the OLAP data source (1) using PivotTable what-if analysis, as specified in section [2.3.1](#).

Child Elements:

tupleItem: An **ST_Xstring** element, as specified in [\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19, that specifies an MDX unique name. The number of these elements **MUST** be greater than zero and **MUST** be less than 2^{31} . The length of each **ST_Xstring** **MUST** be greater than zero and **MUST** be less than or equal to 65,535 characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TupleItems">
  <xsd:sequence>
    <xsd:element name="tupleItem" type="x:ST_Xstring" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.44 CT_SlicerStyle

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SlicerStyles](#)

CT_SlicerStyle specifies table style elements, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.8, of the slicer style, as specified in section [2.3.2.4](#), that are specific to slicers, as specified in section [2.3.2](#).

Child Elements:

slicerStyleElements : A **CT_SlicerStyleElements**, as specified in section [2.6.52](#), that specifies table style elements of the slicer style that are specific to slicers. There MUST NOT be more than one **CT_SlicerStyleElements** in this element.

Attributes:

name: A **string** attribute, as specified in [\[XMLSCHEMA2\]](#) section 3.2.1, that specifies the name of the user-defined table style that this slicer style is based upon. The length of the **string** MUST be greater than or equal to 1 character and less than or equal to 255 characters. This **string** MUST be unique within the **CT_SlicerStyle** elements in the **Styles** part, as specified in [\[ISO/IEC29500-1:2011\]](#) section 12.3.20. This **string** MUST match the **name** attribute of a **CT_TableStyle** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, in the **Styles** part. In the **CT_TableStyle** element with a **name** attribute that matches this **string**, the **pivot** attribute MUST equal "false" and the **table** attribute MUST equal "false".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerStyle">
  <xsd:sequence>
    <xsd:element name="slicerStyleElements" type="CT_SlicerStyleElements" minOccurs="0"
maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="xsd:string" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.45 CT_SlicerStyleElement

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SlicerStyleElements](#)

A complex type that specifies a table style element, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.8, of a slicer style, as specified in section [2.3.2.4](#).

Attributes:

type: An **ST_SlicerStyleType** attribute, as specified in section [2.7.13](#), that specifies the type of the table style element. This attribute MUST be unique within the parent **CT_SlicerStyleElements** complex type.

dxfid: An **ST_DxfId** attribute, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.18.25, that specifies a zero-based index for the list of elements specified by the **dxfs** global element, as specified in section [2.4.24](#). The specified **CT_Dxf** complex type, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, specifies the formatting to use with this table style element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerStyleElement">
  <xsd:attribute name="type" type="ST_SlicerStyleType" use="required"/>
  <xsd:attribute name="dxfid" type="x:ST_DxfId" use="optional"/>
</xsd:complexType>
```

</xsd:complexType>

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.46 CT_OleItem

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [oleItem](#)

OleItem is a complex type that specifies an OLE data item, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.14, with associated cached values.

Child Elements:

values: A **CT_DdeValues** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies the cached values.

Attributes:

name: An **ST_Xstring** attribute, as specified in [\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19, that specifies the name of the OLE data item.

icon: A **Boolean** attribute, as specified in [\[XMLSCHEMA2\]](#) section 3.2.2, that specifies whether the OLE data item is represented as an icon.

Value	Meaning
"false"	The OLE data item is not represented as an icon.
"true"	The OLE data item is represented as an icon.

advise: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the application requests that the OLE data source (1), as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.14, provides notifications when the source data changes.

Value	Meaning
"false"	The application does not request to be notified when the source data changes.
"true"	The application requests to be notified when the source data changes.

preferPic: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the OLE data item is an image.

Value	Meaning
"false"	The OLE data item is not an image.
"true"	The OLE data item is an image.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_OleItem">
```



```

<xsd:sequence>
  <xsd:element name="values" type="x:CT_DdeValues" minOccurs="0" maxOccurs="1"/>
</xsd:sequence>
<xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
<xsd:attribute name="icon" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="advise" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="preferPic" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.47 CT_PivotHierarchy

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [pivotHierarchy](#)

A complex type that specifies whether the ancestor **CT_PivotHierarchy** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, SHOULD [<14>](#) be ignored.

The ancestor **CT_PivotHierarchy** element has the following restrictions on attributes.

Name	Value
caption	MUST NOT be specified.
dragOff	MUST equal "false".
dragToCol	MUST equal "false".
dragToData	MUST equal "true".
dragToPage	MUST equal "false".
dragToRow	MUST equal "false".
includeNewItemInFilter	MUST equal "true".
multipleItemSelectionAllowed	MUST NOT be specified.
outline	MUST NOT be specified.
showInFieldList	MUST NOT be specified.
subtotalTop	MUST NOT be specified.

The ancestor **CT_PivotHierarchy** element has the following restrictions on child elements.

Child element	Restriction
CT_PivotHierarchy (this element)	Exactly 1 MUST exist.
CT_Members ([ISO/IEC29500-4:2011] section A.2)	MUST NOT exist.
CT_MemberProperties ([ISO/IEC29500-4:2011] section A.2)	MUST NOT exist.

If this element exists, there MUST exist a **CT_DataField** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, with an **fld** attribute equal to the zero-based index of a **CT_CacheField** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, in the list of **CT_CacheField** elements specified by **CT_CacheFields**, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, with a **hierarchy** attribute that specifies a **CT_CacheHierarchy**, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, with a zero-based index in the list of **CT_CacheHierarchy** elements specified by the **CT_CacheHierarchies** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, equal to the zero-based index of the ancestor **CT_PivotHierarchy** element in the list of **CT_PivotHierarchy** elements specified by **CT_PivotHierarchies**, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2. Additionally, that **CT_DataField** element MUST have a descendant **CT_DataField** element, as specified in section [2.6.25](#), with a **sourceField** attribute specified.

For more details, see section [2.6.25](#).

Attributes:

ignore: A **Boolean** attribute, as specified in [\[XMLSCHEMA2\]](#) section 3.2.2, that MUST be "true" and MUST be ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotHierarchy">
  <xsd:attribute name="ignore" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.48 CT_CacheField

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [cacheField](#)

This complex type specifies the ancestor **CT_CacheField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that SHOULD [<15>](#) be ignored.

The following table lists the restrictions on attributes of the ancestor **CT_CacheField** element.

Name	Value
caption	MUST NOT be specified.
databaseField	MUST NOT be specified.
formula	MUST NOT be specified.
level	MUST equal "32767".
mappingCount	MUST NOT be specified.
memberPropertyField	MUST NOT be specified.
numFmtId	MUST equal zero ("0").
propertyName	MUST NOT be specified.

Name	Value
serverField	MUST NOT be specified.
sqlType	MUST NOT be specified.
uniqueList	MUST NOT be specified.

The following table lists the restrictions on child elements of the ancestor **CT_CacheField** element.

Child element	Restriction
CT_CacheField (this element)	Exactly 1 MUST exist.
CT_FieldGroup ([ISO/IEC29500-4:2011] section A.2)	MUST NOT exist.
CT_X ([ISO/IEC29500-4:2011] section A.2)	MUST NOT exist.
CT_SharedItems ([ISO/IEC29500-4:2011] section A.2)	MUST NOT exist.

If this element exists, there MUST exist a **CT_DataField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element with an **fld** attribute equal to the zero-based index of the ancestor **CT_CacheField** element in the list of **CT_CacheField** elements specified by **CT_CacheFields** ([\[ISO/IEC29500-4:2011\]](#) section A.2). Additionally, that **CT_DataField** element MUST have a descendant **CT_DataField** element (section [2.6.25](#)) with a **sourceField** attribute specified.

For more details, see [CT_DataField](#)

Attributes:

ignore: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that MUST be "true" and MUST be ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CacheField">
  <xsd:attribute name="ignore" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.49 CT_ConditionalFormats

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotTableDefinition](#)

This complex type specifies a collection of conditional formats applied to the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view.

Child Elements:

conditionalFormat: A [CT_ConditionalFormat](#) element that specifies the conditional formatting applied to the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view.

Attributes:

count: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the number of **conditionalFormat** child elements of this element.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ConditionalFormats">
  <xsd:sequence>
    <xsd:element name="conditionalFormat" minOccurs="1" maxOccurs="unbounded"
type="CT_ConditionalFormat"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.50 CT_ConditionalFormat

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_ConditionalFormats](#)

This complex type specifies the scope, type, and priority of conditional formatting applied to this PivotTable ([ISO/IEC29500-1:2011] section 18.10) view.

Child Elements:

pivotAreas: A **CT_PivotAreas** ([ISO/IEC29500-4:2011] section A.2) element that specifies a set of PivotTable areas this conditional formatting applies to.

extLst: A **CT_ExtensionList** ([ISO/IEC29500-4:2011] section A.2) element that specifies future extensibility for this element.

Attributes:

scope: An **ST_Scope** ([ISO/IEC29500-1:2011] section 18.18.67) attribute that specifies the scope of this conditional formatting.

type: An **ST_Type** ([ISO/IEC29500-1:2011] section 18.18.84) attribute that MUST NOT be present or MUST be equal to "none".

priority: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the priority of the PivotTable conditional formatting. This value MUST be greater than or equal to 1. If this attribute is present, there MUST exist a **CT_CfRule** with a **priority** attribute equal to the value of this field (1) and it MUST be the same CT_CfRule element that is specified by **id**. The CT_CfRule specified by this value MUST have an ancestor **CT_ConditionalFormatting** element with a **pivot** attribute equal to "true".

id: An **ST_Guid** ([ISO/IEC29500-1:2011] section 22.9.2.4) attribute that specifies a particular CT_CfRule. There MUST exist a CT_CfRule with an **id** attribute equal to this value and it MUST be the same CT_CfRule element that is specified by **priority**.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_ConditionalFormat">
  <xsd:sequence>
    <xsd:element name="pivotAreas" type="x:CT_PivotAreas" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" minOccurs="0" maxOccurs="1" type="x:CT_ExtensionList"/>
  </xsd:sequence>
  <xsd:attribute name="scope" type="x:ST_Scope" default="selection" use="optional"/>
  <xsd:attribute name="type" type="x:ST_Type" default="none" use="optional"/>
  <xsd:attribute name="priority" use="optional" type="xsd:unsignedInt"/>
  <xsd:attribute name="id" type="x:ST_Guid" use="required"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.51 CT_SlicerStyles

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [slicerStyles](#)

A complex type that specifies a group of [slicer styles](#) and the default slicer style to apply to [slicers](#).

Child Elements:

slicerStyle: A [CT_SlicerStyle](#) element that specifies a slicer style.

Attributes:

defaultSlicerStyle: A **string** ([\[XMLSCHEMA2\]](#) section 3.2.1) attribute that specifies the name of the default slicer style to apply to slicers. The length of the string **MUST** be greater than or equal to 1 character and less than or equal to 255 characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_SlicerStyles">
  <xsd:sequence>
    <xsd:element name="slicerStyle" type="CT_SlicerStyle" minOccurs="0"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="defaultSlicerStyle" type="xsd:string" use="required"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.52 CT_SlicerStyleElements

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SlicerStyle](#)

A complex type that specifies the list of table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) elements of a [slicer style](#) that are specific to [slicers](#).

Child Elements:

slicerStyleElement: A [CT_SlicerStyleElement](#) element that specifies a table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) element of a slicer style that is specific to slicers.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerStyleElements">
  <xsd:sequence>
    <xsd:element name="slicerStyleElement" type="CT_SlicerStyleElement" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.53 CT_IgnoredErrors

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [ignoredErrors](#)

A complex type that specifies a list of cell ranges and the types of cell errors that are to be ignored for each of those specific cell ranges.

Child Elements:

ignoredError: A [CT_IgnoredError](#) element that specifies the types of cell errors that are to be ignored for a specific cell range.

extLst: A [CT_ExtensionList](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_IgnoredErrors">
  <xsd:sequence>
    <xsd:element name="ignoredError" type="CT_IgnoredError" minOccurs="0"
      maxOccurs="unbounded"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.54 CT_IgnoredError

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_IgnoredErrors](#)

A complex type that specifies the types of cell errors that are to be ignored for a specific cell range. This complex type is equivalent to **CT_IgnoredError** ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.50), but allows the **sqref** child element to have greater than or equal to 8,192 [ref](#) child elements.

Child Elements:

xm:sqref: A [sqref](#) element that specifies the range where cell errors have been ignored. This sqref MUST have greater than or equal to 8,192 ref child elements.

Attributes:

evalError: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to ignore calculation errors.

Value	Meaning
"true"	Ignore calculation errors.
"false"	Do not ignore calculation errors.

twoDigitTextYear: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to ignore errors arising from the formatting of date/time values.

Value	Meaning
"true"	Ignore errors arising from the formatting of data/time values.
"false"	Do not ignore errors arising from the formatting of date/time values.

numberStoredAsText: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to ignore errors arising from the formatting of numeric values.

Value	Meaning
"true"	Ignore errors arising from the formatting of numeric values.
"false"	Do not ignore errors arising from the formatting of numeric values.

formula: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to ignore errors arising from formulas that are inconsistent with formulas ([\[ISO/IEC29500-1:2011\]](#) section 18.17) in neighboring cells.

Value	Meaning
"true"	Ignore errors arising from formulas that are inconsistent with formulas ([ISO/IEC-29500-1] section 18.17) in neighboring cells.
"false"	Do not ignore errors arising from formulas that are inconsistent with formulas ([ISO/IEC-29500-1] section 18.17) in neighboring cells.

formulaRange: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to ignore errors arising from formulas ([\[ISO/IEC29500-1:2011\]](#) section 18.17) that contain references to less than the entirety of a range containing contiguous data.

Value	Meaning
"true"	Ignore errors arising from formulas ([ISO/IEC-29500-1] section 18.17) that contain references to less than the entirety of a range containing contiguous data.
"false"	Do not ignore errors arising from formulas ([ISO/IEC-29500-1] section 18.17) that contain references to less than the entirety of a range containing contiguous data.

unlockedFormula: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to ignore errors arising from unprotected formulas ([\[ISO/IEC29500-1:2011\]](#) section 18.17).

Value	Meaning
"true"	Ignore errors arising from unprotected formulas ([ISO/IEC-29500-1] section 18.17).
"false"	Do not ignore errors arising from unprotected formulas ([ISO/IEC-29500-1] section 18.17).

emptyCellReference: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to ignore errors arising from references to empty cells.

Value	Meaning
"true"	Ignore errors arising from references to empty cells.
"false"	Do not ignore errors arising from references to empty cells.

listDataValidation: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to ignore errors arising from data validation.

Value	Meaning
"true"	Ignore errors arising from data validation.
"false"	Do not ignore errors arising from data validation.

calculatedColumn: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether to ignore errors arising from calculated column (2) formulas ([\[ISO/IEC29500-1:2011\]](#) section 18.17).

Value	Meaning
"true"	Ignore errors arising from calculated column (2) formulas ([ISO/IEC-29500-1] section 18.17).
"false"	Do not ignore errors arising from calculated column (2) formulas ([ISO/IEC-29500-1] section 18.17).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_IgnoredError">
  <xsd:sequence>
    <xsd:element ref="xm:sqref" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="evalError" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="twoDigitTextYear" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="numberStoredAsText" type="xsd:boolean" use="optional"
  default="false"/>
  <xsd:attribute name="formula" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="formulaRange" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="unlockedFormula" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="emptyCellReference" type="xsd:boolean" use="optional"
  default="false"/>
  <xsd:attribute name="listDataValidation" type="xsd:boolean" use="optional"
  default="false"/>
  <xsd:attribute name="calculatedColumn" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```



```
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.55 CT_ProtectedRanges

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [protectedRanges](#)

A complex type that specifies a group of protected ranges on the sheet (1). MUST contain fewer than 2³¹ elements.

Child Elements:

protectedRange: A [CT_ProtectedRange](#) element that specifies the properties for a single protected range.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ProtectedRanges">
  <xsd:sequence>
    <xsd:element name="protectedRange" type="CT_ProtectedRange" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.56 CT_ProtectedRange

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_ProtectedRanges](#)

A complex type that specifies a cell range to be unprotected. The cell range is editable with a password or proper **credentials** when sheet (1) **protection** is on and the cell is **locked**.

Child Elements:

xm:sqref: A [sqref](#) element that specifies the cell range to be unprotected.

Attributes:

password: An **ST_UnsignedShortHex** ([\[ISO/IEC29500-4:2011\]](#) section 15.7.2) attribute that specifies the verifier value of the password required for editing the cell range. If the value is 0x0000, then there is no password.

The verifier value is calculated in two stages. First, the provided **Unicode** password string is converted to a new character string in the ANSI code page of the current system by using the algorithm specified in the **revisionsPassword** attribute in [\[ISO/IEC29500-1:2011\]](#) section 18.2.29. Second, this string is input into the **XOR obfuscation** algorithm specified in [\[MS-OFFCRYPTO\]](#) section [2.3.7.1](#) to produce a 16-bit password verifier value.

This attribute MUST NOT be present if **algorithmName** is present.

algorithmName: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the **hash** algorithm used to calculate **hashValue**. If this attribute is present, **hashValue**, **saltValue**, and **spinCount** MUST also be present. This attribute MUST NOT be present if **password** is present.

hashValue: A **base64Binary** ([\[XMLSCHEMA2\]](#) section 3.2.16) attribute that specifies the hash value for the password required to edit this range. This value will be compared with the resulting hash value after hashing the user-supplied password by using the algorithm specified by **algorithmName**, and if the two values match, the protection will no longer be enforced.

Password hashes are computed by the algorithm specified in [MS-OFFCRYPTO] section [2.4.2.4](#). Under some circumstances, the password is first converted to a 16-bit verifier value and reinterpreted as a single Unicode character, which is then passed to the algorithm specified in [MS-OFFCRYPTO] section [2.4.2.4](#). There is no way to determine which method was used to generate a hash without knowledge of the password; it is necessary to compute both hashes to verify the password.

This attribute MUST be present if and only if **algorithmName** is present.

saltValue: A **base64Binary** ([\[XMLSCHEMA2\]](#) section 3.2.16) attribute that specifies the **salt** used to calculate **hashValue**. This attribute MUST be present if and only if **algorithmName** is present.

spinCount: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of times that the hash function was iterated over the password to generate the **hashValue**. It MUST NOT be greater than 10,000,000. This attribute MUST be present if and only if **algorithmName** is present.

name: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the title of the cell range. The value MUST be unique for the sheet (1). The number of characters in the string MUST be greater than or equal to 1, and less than or equal to 255. The string MUST conform to the following **Augmented Backus-Naur Form (ABNF)** ([\[RFC5234\]](#)) grammar:

```
string = name-start-character *name-character
name-start-character = "_" / "\" / Unicode-character
name-character = name-start-character / Unicode-space / Unicode-digit / "?" / "."
```

The following points summarize this grammar:

- Unicode-character is any code point that is a character as defined by the Unicode character properties, [\[UNICODE5.1\]](#) chapter 4.
- Unicode-digit is any code point that is a digit as defined by the Unicode character properties, [\[UNICODE5.1\]](#) chapter 4.
- Unicode-space is any code point that is a space as defined by the Unicode character properties, [\[UNICODE5.1\]](#) chapter 4.

securityDescriptor: A **string** ([\[XMLSCHEMA2\]](#) section 3.2.1) attribute that describes a **security descriptor** ([\[MS-AZOD\]](#) section 1.1.1.3) that lists users who can edit the cell range without providing the password.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ProtectedRange">
  <xsd:sequence maxOccurs="1">
    <xsd:element ref="xm:sqref" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="password" type="x:ST_UnsignedShortHex" use="optional"/>
  <xsd:attribute name="algorithmName" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="hashValue" type="xsd:base64Binary" use="optional"/>
  <xsd:attribute name="saltValue" type="xsd:base64Binary" use="optional"/>
  <xsd:attribute name="spinCount" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="securityDescriptor" type="xsd:string" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.57 CT_IconFilter

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [iconFilter](#)

This complex type specifies the icon set and particular icon within that set to filter by. Rows (2) with a cell icon that do not match these criteria will be hidden when the filter is applied.

Attributes:

iconSet: An [ST_IconSetType](#) attribute that specifies the icon set used as the filter criteria.

iconId: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the index of the icon to be used as filter criteria. If **iconSet** is "NoIcons", this value MUST be 0 and this record does not specify a filter and MUST be ignored. If **iconSet** is not "NoIcons", this value MUST be greater than or equal to 0. If the icon set specified by **iconSet** has three icons, this value MUST be less than or equal to 2. If the icon set specified by **iconSet** has four icons, this value MUST be less than or equal to 3. If the icon set specified by **iconSet** has five icons, this value MUST be less than or equal to 4.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_IconFilter">
  <xsd:attribute name="iconSet" type="ST_IconSetType" use="required"/>
  <xsd:attribute name="iconId" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.58 CT_Filter

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [filter](#)

This complex type specifies a filter criterion. Rows (2) that contain a cell within the filter range that have value **val** will not be hidden by this **filter** criteria. Rows (2) that do not contain such a cell inside a **filters** element ([\[ISO/IEC29500-1:2011\]](#) section 18.3.2.8) will be hidden.

Attributes:

val: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the value to be used as a filter criterion. The length of this value **MUST** be less than 65536 characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Filter">
  <xsd:attribute name="val" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.59 CT_CustomFilters

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [customFilters](#)

This complex type specifies custom filter criteria. Rows (2) that contain a cell within the filter range such that the value does not meet the custom filter criteria will be hidden.

Child Elements:

customFilter: A **CT_CustomFilter** element that specifies a custom filter criterion.

Attributes:

and: A Boolean ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies the relationship between custom filter criterion. This attribute only applies when there are two criteria.

Value	Meaning
"false"	The two criteria are related by an OR relationship. That is, for a cell value to meet the custom filter criteria, at least one criterion specified by the customFilter child elements MUST be met.
"true"	The two criteria are related by an AND relationship. That is, for a cell value to meet the custom filter criteria, both criteria specified by the customFilter child elements MUST be met.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CustomFilters">
  <xsd:sequence>
    <xsd:element name="customFilter" type="CT_CustomFilter" minOccurs="1" maxOccurs="2"/>
  </xsd:sequence>
  <xsd:attribute name="and" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.60 CT_CustomFilter

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_CustomFilters](#)

This complex type specifies a custom filter criterion.

Attributes:

operator: An **ST_FilterOperator** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.31) attribute that specifies the operator of the custom filter criterion.

val: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the value to be used as a custom filter criterion. The length of this value **MUST** be less than 65536 characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CustomFilter">
  <xsd:attribute name="operator" type="x:ST_FilterOperator" default="equal" use="optional"/>
  <xsd:attribute name="val" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.61 CT_SortCondition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [sortCondition](#)

A complex type that specifies a sort condition to apply to a range.

Attributes:

descending: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies the direction of the **sort**.

Value	Meaning
"false"	If sortBy is "value", sort in ascending order. If sortBy is "cellColor" or "fontColor", cells in which the cell color or cell font color specified by dxfid occurs are ordered at the top of the range. If sortBy is "icon", cells in which the icon specified by iconSet and iconId occurs are ordered at the top of the range.
"true"	If sortBy is "value", sort in descending order. If sortBy is "cellColor" or "fontColor", cells in which the cell color or cell font color specified by dxfid occurs are ordered at the bottom of the range. If sortBy is "icon", cells in which the icon specified by iconSet and iconId occurs are ordered at the bottom of the range.

sortBy: An **ST_SortBy** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.72) attribute that specifies how the cells in a range are sorted.

ref: An **ST_Ref** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.62) attribute that specifies the row (2) or column (2) to which this sort condition applies. This value **MUST** be contained within the **ref** in the **sortState** ([\[ISO/IEC29500-1:2011\]](#) section 18.3.1.92) element that precedes this element. If the

sortState.columnSort attribute that precedes this element is "false", this value specifies the column (2) to which this sort condition applies and there MUST be only a single column (2) specified by **ref**. If the **sortState.columnSort** attribute that precedes this element is "true", this value specifies the row (2) to which this sort condition applies and there MUST be only a single row (2) specified by **ref**.

customList: An **ST_Xstring** ([ISO/IEC29500-1:2011] section 22.9.2.19) attribute that specifies a comma-delimited list of strings that specifies a custom **sort order (2)**. The order of strings in the list specifies the sort order (2). When a cell value matches a string in the list, it is sorted ahead of the cell values that match a later string in the list, and so on for each cell in the range. MUST be ignored if **sortBy** is not equal to "value".

dxfid: An **ST_DxfId** ([ISO/IEC29500-1:2011] section 18.18.25) attribute that specifies the format identifier when **sortBy** equals "cellColor" or **sortBy** equals "fontColor". MUST NOT be present if **sortBy** equals "icon" or "value".

iconSet: An **ST_IconSetType** attribute that specifies the icon set when **sortBy** equals "icon". The absence of this attribute means no icon. MUST NOT be present if **sortBy** is not equal to "icon".

iconId: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the zero-based index of an icon in an icon set. If the icon set specified by **iconSet** has three icons, this value MUST be less than or equal to 2. If the icon set specified by **iconSet** has four icons, this value MUST be less than or equal to 3. If the icon set specified by **iconSet** has five icons, this value MUST be less than or equal to 4. The absence of this attribute means no icon. MUST NOT be present if **sortBy** is not equal to "icon".

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SortCondition">
  <xsd:attribute name="descending" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="sortBy" type="x:ST_SortBy" use="optional" default="value"/>
  <xsd:attribute name="ref" type="x:ST_Ref" use="required"/>
  <xsd:attribute name="customList" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="dxfid" type="x:ST_DxfId" use="optional"/>
  <xsd:attribute name="iconSet" type="ST_IconSetType" use="optional" default="3Arrows"/>
  <xsd:attribute name="iconId" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.62 CT_SourceConnection

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_CacheSourceExt](#), [sourceConnection](#)

A complex type that stores the connection, which is specified by the **CT_Connection** element as specified in [ISO/IEC29500-4:2011] section A.2, that is associated with this pivot cache. The pivot cache MUST be associated with either an OLAP [slicer cache](#) or a [Non-Worksheet PivotTable](#).

Attributes:

name: An **ST_Xstring** ([ISO/IEC29500-1:2011] section 22.9.2.19) attribute that specifies the name of the connection, which is specified by the **name** attribute of **CT_Connection**

([\[ISO/IEC29500-4:2011\]](#) section A.2) for the connection that is associated with this pivot cache. The length, in characters, of this value MUST be less than 65,536.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SourceConnection">
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.63 CT_ListItem

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_ListItems](#)

A complex type that stores a single item for a list box or a drop-down form control [<16>](#).

Attributes:

val: A **string** attribute, as specified in [\[XMLSCHEMA2\]](#) section 3.2.1, that specifies the data for a single item.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ListItem">
  <xsd:attribute name="val" type="xsd:string" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.64 CT_ListItems

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_FormControlPr](#)

A complex type that contains a list of items of type **CT_ListItem**, as specified in section [2.6.63](#), to populate a list box or a drop-down form control. When present, the **FmlaRange** attribute of **CT_FormControlPr**, as specified in section [2.6.65](#), takes precedence over this element. This element is valid only for list box and drop-down form control.

Child Elements:

item: A **CT_ListItem** element that contains a single data item for a list box or drop-down form control.

extLst: A **CT_ExtensionList** element, as specified in ([\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies future extensibility for this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_ListItems">
  <xsd:sequence>
    <xsd:element name="item" type="CT_ListItem" minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.65 CT_FormControlPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [formControlPr](#)

A complex type that stores a form control's properties.

Child Elements:

itemLst: A **CT_ListItems** element, as specified in section [2.6.64](#), that specifies a list of items to populate a list box or drop-down form control.

extLst: A **CT_ExtensionList** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies future extensibility for this element.

Attributes:

objectType: An [ST_ObjectType](#) attribute that specifies the form control object type.

checked: An [ST_Checked](#) attribute that specifies whether a check box is selected or a radio button is selected. This attribute only applies to check box and radio button form controls.

colored: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether a drop-down object has a color applied to it. This attribute only applies to drop-down form controls.

Value	Meaning
"true"	A drop-down object has a color applied to it.
"false"	A drop-down object has no color applied to it.

dropLines: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of lines in the drop-down before scroll bars are added. This attribute only applies to drop-down form controls. This value **MUST** be at least 0 and at most 30000.

dropStyle: An [ST_DropStyle](#) attribute that specifies the style of the drop-down. This attribute only applies to drop-down form controls.

dx: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the width of the scroll bar in pixels. This attribute only applies to list boxes, scroll bars, spin boxes and drop-downs [<17>](#).

firstButton: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the object is the first button in a set of radio buttons. This attribute only applies to radio button form controls.

Value	Meaning
"true"	The object is the first button in a set of radio buttons.
"false"	The object is not the first button in a set of radio buttons.

fmlaGroup: An **ST_Formula** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.35) attribute that specifies the cell an object in a group box is linked to. This attribute overrides the attribute **fmlaLink** for any radio buttons within a group box. This attribute only applies to group box form controls. The application can chose to remove and not save this element and use the attribute **fmlaLink** of the first radio button in the group. This attribute **MUST** be a cell reference (see [\[ISO/IEC29500-1:2011\]](#) section 18.17.2.3).

fmlaLink: An **ST_Formula** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.35) attribute that specifies the cell the object is linked to. This attribute only applies to check boxes, radio buttons, scroll bars, spin boxes, drop-downs and list boxes. The value in the linked cell and the index of the selected item in the object are linked together. This link is ignored if the form control allows multiple selections. This attribute **MUST** be a cell reference (see [\[ISO/IEC29500-1:2011\]](#) section 18.17.2.3).

fmlaRange: An **ST_Formula** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.35) attribute that specifies the range of source data cells. This is used to populate a list box or a drop-down form control [<18>](#). This attribute only applies to list box and drop-down form controls. This attribute **MUST** be a cell reference (see [\[ISO/IEC29500-1:2011\]](#) section 18.17.2.3).

fmlaTxbx: An **ST_Formula** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.35) attribute that specifies the source data cell that the form control object's data is linked to. Any cell range **MAY** be specified but only the first cell in the range is considered. This attribute applies only to label and edit box form controls. This attribute **MUST** be a cell reference (see [\[ISO/IEC29500-1:2011\]](#) section 18.17.2.3).

horiz: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the scroll bar is horizontal. This attribute only applies to scroll bar form controls.

inc: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the change in the current value of a scroll bar or a spin box form control as a result of on an increment click. If present, it **MUST** be at least 0 and at most 30000. This attribute applies only to scroll bar or spin box form controls.

justLastX: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the last line in text is justified when in an East Asian alignment [<19>](#).

Value	Meaning
"true"	The last line in text is justified when in an East Asian alignment.
"false"	the last line in text is not justified when in an East Asian alignment.

lockText: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the object's text is locked. This attribute applies only to button, radio button, check box and label form controls.

Value	Meaning
"true"	The object's text is locked.
"false"	The object's text is not locked.

max: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the maximum value generated by the scroll bar (when scrolled all the way down) or by the spin box. It MUST be at least 0 and at most 30000. This attribute only applies to scroll bars and spin boxes.

min: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the minimum value generated by the scroll bar (when scrolled all the way up) or by the spin box. It MUST be at least 0 and at most 30000. This attribute only applies to scroll bars and spin box.

multiSel: A **string** ([\[XMLSCHEMA2\]](#) section 3.2.1) attribute that specifies the indices of selected items as a comma-delimited list. The list indices are one-based. This attribute is valid only if the attribute **selType** has the value "multi". This attribute applies only to list box form controls.

noThreeD: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether 3-D effects are disabled. This attribute only applies to check box, radio button, group box, scroll bar, drop-down, list box, and spin box form controls.

Value	Meaning
"true"	The 3-D effects are disabled.
"false"	The 3-D effects are enabled.

noThreeD2: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether 3-D effects are disabled. This element is used for drop-downs and list boxes [<20>](#).

Value	Meaning
"true"	The 3-D effects are disabled.
"false"	The 3-D effects are enabled.

page: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of items to move the scroll bar or spin box on a page click. It MUST be at least 0 and at most 30000 [<21>](#).

sel: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the index of the selected item. The list indices are one-based. If set to a value of 0, no items are selected. This attribute applies only to list box and drop-down form controls.

seltype: An [ST_SelType](#) attribute that specifies the selection type for the list box. This attribute applies only to list box form controls.

textHAlign: An [ST_TextHAlign](#) attribute that specifies the horizontal text alignment for the object [<22>](#).

textVAlign: An [ST_TextVAlign](#) attribute that specifies the vertical text alignment for the object [<23>](#).

val: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of top rows (2) currently hidden in the scroll bar. If omitted, the value is assumed to be 0. Those rows (2) are hidden but still accessible by clicking the scroll bar buttons. The number of top hidden rows (2) can change as the user interacts with the scroll bar. This attribute only applies to scroll bar, spin box, list box, and drop-down form controls.

widthMin: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the smallest width allowed for the drop-down box window in screen pixels. This attribute only applies for drop-down form controls.

editVal: An [ST_EditValidation](#) attribute that specifies how the edit box content is validated if the application chooses to validate it. This attribute only applies to edit box form controls.

multiLine: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the form control is multiline. This attribute only applies to edit box form controls. This attribute only works when the form control is run in a dialog box.

Value	Meaning
"true"	The form control is multiline.
"false"	The form control is singleline.

verticalBar: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the control has a vertical scroll bar. This attribute only applies to edit box form controls. This attribute only works when the form control is run in a dialog box.

Value	Meaning
"true"	The control has a vertical scroll bar.
"false"	The control has no vertical scroll bar.

passwordEdit: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the edit box control stores a password. In this case the control will display * for every character on it. This attribute only applies to edit box form controls. This attribute only works when the control is run in a dialog box.

Value	Meaning
"true"	The edit box control stores a password.
"false"	The edit box control does not store password.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_FormControlPr">
  <xsd:sequence>
    <xsd:element name="itemLst" type="CT_ListItems" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="objectType" type="ST_ObjectType" use="optional"/>
  <xsd:attribute name="checked" type="ST_Checked" use="optional"/>
  <xsd:attribute name="colored" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="dropLines" type="xsd:unsignedInt" use="optional" default="8"/>
  <xsd:attribute name="dropStyle" type="ST_DropStyle" use="optional"/>
  <xsd:attribute name="dx" type="xsd:unsignedInt" use="optional" default="80"/>
  <xsd:attribute name="firstButton" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="fmlaGroup" type="x:ST_Formula" use="optional"/>
  <xsd:attribute name="fmlaLink" type="x:ST_Formula" use="optional"/>
  <xsd:attribute name="fmlaRange" type="x:ST_Formula" use="optional"/>
</xsd:complexType>
```

```

<xsd:attribute name="fmlaTxbx" type="x:ST_Formula" use="optional"/>
<xsd:attribute name="horiz" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="inc" type="xsd:unsignedInt" use="optional" default="1"/>
<xsd:attribute name="justLastX" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="lockText" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="max" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="min" type="xsd:unsignedInt" use="optional" default="0"/>
<xsd:attribute name="multiSel" type="xsd:string" use="optional"/>
<xsd:attribute name="noThreeD" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="noThreeD2" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="page" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="sel" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="seltype" type="ST_SelType" use="optional" default="single"/>
<xsd:attribute name="textHAlign" type="ST_TextHAlign" use="optional" default="left"/>
<xsd:attribute name="textVAlign" type="ST_TextVAlign" use="optional" default="top"/>
<xsd:attribute name="val" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="widthMin" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="editVal" type="ST_EditValidation" use="optional"/>
<xsd:attribute name="multiLine" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="verticalBar" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="passwordEdit" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.66 CT_DatastoreItem

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [datastoreItem](#)

A complex type that specifies properties for an embedded custom data part.

Child Elements:

extLst: A **CT_ExtensionList** element, as specified in ([\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies future extensibility for this element.

Attributes:

id: An **ST_Xstring** attribute, as specified in ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19, that specifies the identifier for the associated [Custom Data](#) storage. The value of the string is used to identify the associated Custom Data storage, and the value of the string **MUST** be unique for each Custom Data storage in the workbook. The length of this value **MUST** be less than 65536 characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_DatastoreItem">
  <xsd:sequence>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="id" type="x:ST_Xstring" use="required"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.67 CT_Slicers

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [slicers](#)

A complex type that specifies a list of **CT_Slicer** elements, as specified in section [2.6.69](#). The list of **CT_Slicer** elements specifies all [slicer views](#) on the worksheet.

Child Elements:

slicer: A **CT_Slicer** element that specifies a slicer view on the worksheet.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Slicers">
  <xsd:sequence>
    <xsd:element name="slicer" type="CT_Slicer" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.68 CT_Slicer

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_Slicers](#)

A complex type that specifies a slicer view, as specified in section [2.3.2.2](#), in this worksheet.

Child Elements:

extLst: A **CT_ExtensionList** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies future extensibility for this element.

Attributes:

name: An **ST_Xstring** attribute, as specified in [\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19, that specifies the name of the slicer view. MUST be a unique case-insensitive name within the scope of this workbook. The length of this attribute MUST be greater than or equal to 1 character and MUST be less than or equal to 32767 characters.

cache: An **ST_Xstring** attribute that specifies the name of the slicer cache, as specified in section [2.3.2.1](#), that this slicer view is associated with. There MUST be a **CT_SlicerCacheDefinition** element, as specified in section [2.6.70](#), within this workbook with the **name** attribute equal to the value of this attribute.

caption: An **ST_Xstring** attribute that specifies the caption of the slicer view. If this string exists, the length MUST be greater than or equal to 1 character.

startItem: An **unsignedInt** attribute, as specified in [\[XMLSCHEMA2\]](#) section 3.3.22, that specifies the zero-based index of the first slicer item, as specified in section [2.3.2.1.6](#), displayed by the slicer view.

columnCount: An **unsignedInt** attribute that specifies the number of columns (2) in the slicer view. MUST be greater than or equal to 1 and MUST be less than or equal to 20000.

showCaption: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the caption is displayed.

Value	Meaning
"true"	The caption is displayed.
"false"	The caption is suppressed.

level: An **unsignedInt** attribute that specifies the OLAP level of the OLAP hierarchy of the [slicer source data](#) used by this slicer view.

If the slicer source data is OLAP, the value MUST be greater than or equal to 0 and MUST be less than **count** of the [CT_OlapSlicerCacheLevelsData](#) element specified by the CT_SlicerCacheDefinition element specified by **cache**. If the OLAP hierarchy has an **OLAP All level**, the value MUST NOT be 0.

If the slicer source data is non-OLAP, this attribute MUST NOT exist.

style: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the [slicer style](#) of the slicer view. If this field (1) exists, this string MUST match the **name** attribute of a [CT_SlicerStyle](#) element within this workbook or MUST be equal to one of the built-in slicer style names:

Built-in slicer style names
SlicerStyleLight1
SlicerStyleLight2
SlicerStyleLight3
SlicerStyleLight4
SlicerStyleLight5
SlicerStyleLight6
SlicerStyleOther1
SlicerStyleOther2
SlicerStyleDark1
SlicerStyleDark2
SlicerStyleDark3
SlicerStyleDark4
SlicerStyleDark5
SlicerStyleDark6

lockedPosition: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies whether the slicer view is locked.

Value	Meaning
"true"	The slicer view is locked.
"false"	The slicer view is not locked.

rowHeight: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the row (2) height of the slicer view in **English Metric Units (EMUs)**.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Slicer">
  <xsd:sequence>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="cache" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="caption" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="startItem" type="xsd:unsignedInt" use="optional" default="0"/>
  <xsd:attribute name="columnCount" type="xsd:unsignedInt" use="optional" default="1"/>
  <xsd:attribute name="showCaption" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="level" type="xsd:unsignedInt" use="optional" default="0"/>
  <xsd:attribute name="style" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="lockedPosition" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="rowHeight" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
```

See section 5.4 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.69 CT_Slicer

Target namespace: <http://schemas.microsoft.com/office/drawing/2010/slicer>

Referenced by: [slicer](#)

This complex type specifies which [slicer view](#) is associated with this drawing element.

Child Elements:

extLst: A **CT_OfficeArtExtensionList** ([ISO/IEC29500-4:2011] section A.4.1) element that specifies future extensibility for this element.

Attributes:

name: A **string** ([XMLSCHEMA2] section 3.2.1) attribute that specifies the name of the slicer view that is associated with this drawing element. The value of this attribute MUST match the value of the **name** attribute of a **slicer** element within the [CT_Slicers](#) element for the current worksheet.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Slicer">
```

```

<xsd:sequence>
  <xsd:element name="extLst" type="a:CT_OfficeArtExtensionList" minOccurs="0"
maxOccurs="1"/>
</xsd:sequence>
<xsd:attribute name="name" type="xsd:string" use="required"/>
</xsd:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.70 CT_SlicerCacheDefinition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [slicerCacheDefinition](#)

A complex type that specifies a [slicer cache](#).

Child Elements:

pivotTables: A **CT_SlicerCachePivotTables** element (section [2.6.72](#)) that specifies a group of **CT_SlicerCachePivotTable** elements (section [2.6.73](#)) that specify the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views that are filtered by the slicer cache (section [2.1.4](#)).

data: A **CT_SlicerCacheData** element (section [2.6.71](#)) that specifies a data source (1) for the slicer cache.

extLst: A **CT_ExtensionList** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies future extensibility for this element.

Attributes:

name: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the slicer cache. MUST adhere to the name production rule provided in section [2.2.2](#). MUST be a unique case-insensitive name within the scope of defined names.

sourceName: An **ST_Xstring** attribute that specifies the MDX unique name or **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache field (1) of the associated PivotTable **PivotCache** used by the slicer cache.

- If the slicer source data (section [2.3.2.1.1](#)) is a non-OLAP data source (1), the value of this attribute MUST be equal to the **name** attribute of a **CT_CacheField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element in the list of cache fields, as specified in section [2.3.2.1.2](#), and specify a **PivotTable** cache field (1). The specified **CT_CacheField** MUST have a **serverField** attribute equal to "false". The **includeNewItemsInFilter** attributes of the **CT_PivotField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) elements of all included **CT_CacheField** elements MUST be equal.
- If the slicer source data is an OLAP data source (1), the value MUST be equal to the value of the **uniqueName** attribute in one of the **CT_CacheHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) elements within the associated OLAP pivot cache, as specified in section [2.3.2.1.4](#), and specify a MDX unique name. The following attributes of the **CT_CacheHierarchy** element MUST be "false": **measure**, **set**, and **measures**. The **CT_PivotHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element with a zero-based index in the list of **CT_PivotHierarchy** elements specified by the **CT_PivotHierarchies** ([\[ISO/IEC29500-4:2011\]](#) section A.2) equal to the zero-based index of the **CT_CacheHierarchy** element in the list of **CT_CacheHierarchy** elements

specified by **CT_CacheHierarchies** ([\[ISO/IEC29500-4:2011\]](#) section A.2) MUST have an **includeNewItemInFilter** attribute equal to "false".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerCacheDefinition">
  <xsd:sequence>
    <xsd:element name="pivotTables" type="CT_SlicerCachePivotTables" minOccurs="0"
maxOccurs="1"/>
    <xsd:element name="data" type="CT_SlicerCacheData" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="sourceName" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.71 CT_SlicerCacheData

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SlicerCacheDefinition](#)

A complex type that specifies a data source (1) for the [slicer cache](#).

Child Elements:

olap: A [CT_OlapSlicerCache](#) element that specifies an OLAP data source (1).

tabular: A [CT_TabularSlicerCache](#) element that specifies a non-OLAP data source (1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerCacheData">
  <xsd:choice minOccurs="1" maxOccurs="1">
    <xsd:element name="olap" type="CT_OlapSlicerCache" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="tabular" type="CT_TabularSlicerCache" minOccurs="1" maxOccurs="1"/>
  </xsd:choice>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.72 CT_SlicerCachePivotTables

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [slicerCachePivotTables](#), [CT_SlicerCacheDefinition](#)

A complex type that specifies a group of [CT_SlicerCachePivotTable](#) elements that specify the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views that are filtered by the [slicer cache](#).

Child Elements:

pivotTable: A CT_SlicerCachePivotTable element that specifies the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view that is filtered. The list of **pivotTable** child elements MUST NOT contain duplicates. The **showCalcMbrs** attribute of all **CT_PivotTableDefinition** ([\[ISO/IEC29500-4:2011\]](#) section A.2) elements associated with PivotTables ([\[ISO/IEC29500-1:2011\]](#) section 18.10) that are specified by **pivotTable** child elements MUST have the same value.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerCachePivotTables">
  <xsd:sequence>
    <xsd:element name="pivotTable" type="CT_SlicerCachePivotTable" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.73 CT_SlicerCachePivotTable

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SlicerCachePivotTables](#)

A complex type that specifies a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view filtered by a [slicer cache](#).

Attributes:

tabId: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the unique identifier (UID) of the worksheet that contains the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view specified by the **name** attribute. MUST match the **sheetId** of an existing sheet (1) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element within the workbook. MUST be ignored if the PivotTable specified by the name attribute is a [Non-Worksheet PivotTable](#).

name: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view on the worksheet specified by **tabId** or a Non-Worksheet PivotTable. MUST match the **name** attribute of an existing [pivotTableDefinition](#) element in the worksheet. The **createdVersion** attribute of the **CT_PivotTableDefinition** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that defines the specified PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) MUST be greater than or equal to 3. Field (1) **showCalcMbrs** of all PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) MUST have the same value. Field (1) **calculatedMembersInFilters** of [CT_PivotTableDefinition](#) of all PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) MUST have the same value.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerCachePivotTable">
  <xsd:attribute name="tabId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.74 CT_OlapSlicerCacheItem

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_OlapSlicerCacheRange](#)

This element specifies an [OLAP slicer item](#) of the OLAP level in the OLAP hierarchy specified by the ancestor [CT_OlapSlicerCacheLevelData](#) element. This element contains a list of all ancestor OLAP members of this OLAP slicer item in the OLAP hierarchy.

Child Elements:

p: A [CT_OlapSlicerCacheItemParent](#) element that specifies the OLAP members that are ascendants of the OLAP slicer item specified by this element. The first element in this list specifies the OLAP member that is the parent of the OLAP slicer item specified by this element. Each subsequent element in this list specifies an ascendant OLAP member in the next level up the OLAP hierarchy.

Attributes:

n: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the MDX unique name of the OLAP member associated with the OLAP slicer item specified by this element.

c: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the caption of the OLAP slicer item specified by this element.

nd: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the OLAP slicer item specified by this element has no data associated with it. This attribute MUST NOT exist if the **crossFilter** attribute of the ancestor element [CT_OlapSlicerCacheLevelData](#) is "none". For more information, see [Slicer Cross Filtering](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_OlapSlicerCacheItem">
  <xsd:sequence>
    <xsd:element name="p" type="CT_OlapSlicerCacheItemParent" minOccurs="0"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="n" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="c" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="nd" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.75 CT_OlapSlicerCacheItemParent

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_OlapSlicerCacheItem](#), [CT_OlapSlicerCacheSelection](#)

This element specifies an ancestor OLAP member of the OLAP member specified by [CT_OlapSlicerCacheItem](#) or [CT_OlapSlicerCacheSelection](#) element that contains this element.

Attributes:

n: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the MDX unique name of the OLAP member specified by this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_OlapSlicerCacheItemParent">
  <xsd:attribute name="n" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.76 CT_OlapSlicerCacheRange

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_OlapSlicerCacheRanges](#)

A complex type that specifies a collection of cached [OLAP slicer items](#) in the OLAP level specified by the ancestor [CT_OlapSlicerCacheLevelData](#) element.

Child Elements:

i: A [CT_OlapSlicerCacheItem](#) element that specifies an OLAP slicer item in the OLAP level specified by the [CT_OlapSlicerCacheLevelData](#) element that is part of this range. The number of [CT_OlapSlicerCacheItem](#) child elements MUST be greater than 0 and equal to or less than 1,000.

Attributes:

startItem: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the zero-based index of the OLAP member on this OLAP level for the first item in this range. The order of the OLAP slicer item is determined by the current sort order (2) and current [slicer cross filtering](#) setting applied to all OLAP slicer items on this OLAP level. The value of the starting position MUST be 0 or MUST be a multiple of 1,000. See [Slicer Items](#) for more information.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_OlapSlicerCacheRange">
  <xsd:sequence>
    <xsd:element name="i" type="CT_OlapSlicerCacheItem" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="startItem" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.77 CT_OlapSlicerCacheRanges

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_OlapSlicerCacheLevelData](#)

A complex type that specifies the cached [OLAP slicer items](#) for the OLAP level specified by the [CT_OlapSlicerCacheLevelData](#) element.

Child Elements:

range: A [CT_OlapSlicerCacheRange](#) element that specifies a range of OLAP slicer items for this OLAP level within the OLAP hierarchy specified by this [slicer cache](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_OlapSlicerCacheRanges">
  <xsd:sequence>
    <xsd:element name="range" type="CT_OlapSlicerCacheRange" minOccurs="0"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.78 CT_OlapSlicerCacheLevelData

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_OlapSlicerCacheLevelsData](#)

A complex type that specifies the properties of an OLAP level in the OLAP hierarchy specified by this [slicer cache](#) and specifies the OLAP members that are cached for this OLAP level within the OLAP hierarchy specified by this slicer cache.

Child Elements:

ranges: A [CT_OlapSlicerCacheRanges](#) element that specifies cached [OLAP slicer items](#) for the OLAP level specified by this element.

Attributes:

uniqueName: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the MDX unique name of the OLAP level specified by this element within the OLAP hierarchy specified with this slicer cache. The length of this string **MUST** be at least 1 character and **MUST NOT** exceed 32,767 characters.

sourceCaption: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the caption of the OLAP level specified by this element within the OLAP hierarchy specified with this cache. The length of this string **MUST NOT** exceed 65,535 characters.

count: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the total number of OLAP members in the OLAP data source (1) in this OLAP level within the OLAP hierarchy specified by this slicer cache. The default value is zero.

sortOrder: An [ST_OlapSlicerCacheSortOrder](#) attribute that specifies how the OLAP slicer items for the OLAP level specified by this element are sorted in the [slicer view](#).

crossFilter: An [ST_SlicerCacheCrossFilter](#) attribute that specifies how the OLAP slicer items that are used in [slicer cross filtering](#) are displayed.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_OlapSlicerCacheLevelData">
  <xsd:sequence>
    <xsd:element name="ranges" type="CT_OlapSlicerCacheRanges" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="uniqueName" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="sourceCaption" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="sortOrder" type="ST_OlapSlicerCacheSortOrder" use="optional"
    default="natural"/>
  <xsd:attribute name="crossFilter" type="ST_SlicerCacheCrossFilter" use="optional"
    default="showItemsWithDataAtTop"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.79 CT_OlapSlicerCacheLevelsData

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_OlapSlicerCache](#)

A complex type that specifies a list of OLAP levels of the OLAP hierarchy specified by this [slicer cache](#).

Child Elements:

level: A [CT_OlapSlicerCacheLevelData](#) element that specifies properties of an OLAP level in the OLAP hierarchy specified by this slicer cache.

Attributes:

count: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of **level** child elements of this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_OlapSlicerCacheLevelsData">
  <xsd:sequence>
    <xsd:element name="level" type="CT_OlapSlicerCacheLevelData" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.80 CT_OlapSlicerCache

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SlicerCacheData](#)

A complex type that specifies the associated OLAP PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache, and specifies [OLAP Slicer Items](#). See [Slicer Cache Relationship to PivotCache](#) for more details.

Child Elements:

levels: A [CT_OlapSlicerCacheLevelsData](#) element that specifies a list of OLAP levels of the OLAP hierarchy specified by this [slicer cache](#).

selections: A [CT_OlapSlicerCacheSelections](#) element that specifies a list of OLAP Slicer Items that are selected.

extLst: A **CT_ExtensionList** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

pivotCacheId: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the associated OLAP PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache. MUST be equal to the **pivotCacheId** attribute of an existing [CT_PivotCacheDefinition](#) element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_OlapSlicerCache">
  <xsd:sequence>
    <xsd:element name="levels" type="CT_OlapSlicerCacheLevelsData" minOccurs="1"
maxOccurs="1"/>
    <xsd:element name="selections" type="CT_OlapSlicerCacheSelections" minOccurs="1"
maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="pivotCacheId" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.81 CT_OlapSlicerCacheSelections

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_OlapSlicerCache](#)

A complex type that specifies the [OLAP slicer items](#) that are selected in the [slicer cache](#).

Child Elements:

selection: A [CT_OlapSlicerCacheSelection](#) element that specifies an OLAP slicer item that is selected in the slicer cache.

Attributes:

count: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of **selection** child elements of this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_OlapSlicerCacheSelections">
  <xsd:sequence>
```

```

    <xsd:element name="selection" type="CT_OlapSlicerCacheSelection" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.82 CT_OlapSlicerCacheSelection

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_OlapSlicerCacheSelections](#)

A complex type that specifies an individual [OLAP slicer item](#) that is selected for filtering. This complex type also specifies the ancestor OLAP members of the OLAP member associated with the OLAP slicer item in the OLAP hierarchy.

Child Elements:

p: A [CT_OlapSlicerCacheItemParent](#) element that specifies OLAP members that are the ancestors of the OLAP member associated with the OLAP slicer item specified by this element. The first element in this list specifies the OLAP member that is the parent of the OLAP member associated with the OLAP slicer item specified by this element. Each subsequent element in this list specifies an ancestor OLAP member in the next level up the OLAP hierarchy, excluding the **OLAP All member**.

Attributes:

n: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the MDX unique name of the OLAP member associated with the OLAP slicer item specified by this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_OlapSlicerCacheSelection">
  <xsd:sequence>
    <xsd:element name="p" type="CT_OlapSlicerCacheItemParent" minOccurs="0"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="n" type="x:ST_Xstring" use="required"/>
</xsd:complexType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.83 CT_TabularSlicerCache

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SlicerCacheData](#)

A complex type that specifies [non-OLAP slicer items](#) that are cached within this [slicer cache](#) and properties of the slicer cache specific to non-OLAP slicer items.

Child Elements:

items: A [CT_TabularSlicerCacheItems](#) element that specifies non-OLAP slicer items that are cached within this slicer cache.

extLst: A [CT_ExtensionList](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

pivotCacheId: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the associated non-OLAP PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache. MUST match the **pivotCacheId** attribute of an existing [CT_PivotCacheDefinition](#) element.

sortOrder: An [ST_TabularSlicerCacheSortOrder](#) attribute that specifies how the non-OLAP slicer items are sorted in the [slicer view](#).

customListSort: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether **custom lists** are used when sorting the non-OLAP slicer items.

Value	Meaning
"false"	Custom lists are not used when sorting the non-OLAP slicer items.
"true"	Custom lists are used when sorting the non-OLAP slicer items.

showMissing: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether non-OLAP slicer items that correspond to unused PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache items that existed previously, but are no longer present in the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) source data, are displayed.

Value	Meaning
"false"	The unused non-OLAP slicer items are not displayed.
"true"	The unused non-OLAP slicer items are displayed.

crossFilter: An [ST_SlicerCacheCrossFilter](#) attribute that specifies how the non-OLAP slicer items that are used in [slicer cross filtering](#) are displayed.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TabularSlicerCache">
  <xsd:sequence>
    <xsd:element name="items" type="CT_TabularSlicerCacheItems" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="pivotCacheId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="sortOrder" type="ST_TabularSlicerCacheSortOrder" use="optional"
  default="ascending"/>
  <xsd:attribute name="customListSort" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="showMissing" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="crossFilter" type="ST_SlicerCacheCrossFilter" use="optional"
  default="showItemsWithDataAtTop"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.84 CT_TabularSlicerCacheItems

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_TabularSlicerCache](#)

A complex type that specifies [non-OLAP slicer items](#) that are cached within this [slicer cache](#).

Child Elements:

i: A [CT_TabularSlicerCacheItem](#) element that specifies a non-OLAP slicer item that is cached within this slicer cache. All CT_TabularSlicerCacheItem elements within this slicer cache MUST have unique **x** attributes. At least one CT_TabularSlicerCacheItem element MUST have **s** attribute be "true".

Attributes:

count: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of **i** child elements of this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TabularSlicerCacheItems">
  <xsd:sequence>
    <xsd:element name="i" type="CT_TabularSlicerCacheItem" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.85 CT_TabularSlicerCacheItem

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_TabularSlicerCacheItems](#)

A complex type that specifies a [non-OLAP slicer item](#) that is cached within this [slicer cache](#).

Attributes:

x: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies an index of the associated PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache item in the associated **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache field (1). MUST be within the range of items as specified by the **count** attribute of the **CT_PivotCacheRecords** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element of the associated non-OLAP PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache specified by the **pivotCacheId** attribute of the [CT_TabularSlicerCache](#) element that is an ancestor of this element.

s: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether a non-OLAP slicer item is selected.

Value	Meaning
"true"	A non-OLAP slicer item is selected.

Value	Meaning
"false"	A non-OLAP slicer item is not selected.

nd: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether a non-OLAP slicer item does not have data associated with it. This attribute MUST NOT exist if the **crossFilter** attribute of the CT_TabularSlicerCache element is equal to "none". For more information, see [Slicer Cross Filtering](#).

Value	Meaning
"true"	A non-OLAP slicer item does not have data associated with it.
"false"	A non-OLAP slicer item has data associated with it.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TabularSlicerCacheItem">
  <xsd:attribute name="x" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="s" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="nd" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.86 CT_PivotTableReferences

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [pivotTableReferences](#)

A complex type that specifies a list of PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) part identifiers for [Non-Worksheet PivotTables](#). MUST contain fewer than 2³¹ elements.

Child Elements:

pivotTableReference: A [CT_PivotTableReference](#) element that specifies a PivotTable part identifier of a Non-Worksheet PivotTable.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotTableReferences">
  <xsd:sequence>
    <xsd:element name="pivotTableReference" type="CT_PivotTableReference" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.87 CT_PivotTableReference

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_PivotTableReferences](#)

A complex type that specifies a [relationship](#) identifier to a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) part in this workbook. The PivotTable specified by the element **pivotTableDefinition** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.73) identified by this type MUST be a [Non-Worksheet PivotTable](#) and MUST satisfy the following criteria.

- The **ref** attribute of the child element **location** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.49) MUST begin with "A1".
- The **enableEdit** attribute of the **CT_PivotTableDefinition** element, as specified in section [2.6.32](#), MUST NOT exist or MUST be "false" if exists; **CT_PivotEdits** and **CT_PivotChanges** elements MUST NOT exist in this part.
- The PivotTable name specified by the **name** attribute of the element **pivotTableDefinition** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.73), MUST be unique among all the PivotTables in the workbook.
- There MUST be a child **CT_PivotCache** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element within the **pivotCaches** element, specified by section [2.4.39](#), with the attribute **cacheID** having the same value as the **cacheId** attribute of the element **pivotTableDefinition** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.73).
- The PivotTable MUST NOT have **CT_ConditionalFormats** element as specified by section [2.6.49](#).

Attributes:

r:id: An **ST_RelationshipId** ([\[ISO/IEC29500-1:2011\]](#) section 22.8.2.1) attribute that specifies a relationship identifier to a PivotTable part in this workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotTableReference">
  <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.88 CT_QueryTable

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [queryTable](#)

A complex type that specifies extended properties of a query table ([\[ISO/IEC29500-1:2011\]](#) section 18.12).

Attributes:

clipped: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether a query table ([\[ISO/IEC29500-1:2011\]](#) section 18.12) did not fit to worksheet and was clipped.

Value	Meaning
"true"	A query table ([ISO/IEC-29500-1] section 18.12) did not fit to the worksheet and was clipped.
"false"	A query table ([ISO/IEC-29500-1] section 18.12) did not fit to the worksheet and was not clipped.

sourceDataName: A **string** attribute that specifies the name of the primary data connection (2) for the query table. For more details, see **connection** ([\[ISO/IEC29500-1:2011\]](#) section 18.13.1)

drillThrough: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether a query table ([\[ISO/IEC29500-1:2011\]](#) is a result of **drillthrough** operation on OLAP data source (1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_QueryTable">
  <xsd:attribute name="clipped" use="optional" default="false" type="xsd:boolean"/>
  <xsd:attribute name="sourceDataName" type="xsd:string" use="optional"/>
  <xsd:attribute name="drillThrough" use="optional" default="false" type="xsd:boolean"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.89 CT_WebExtensions

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [webExtensions](#)

A complex type that specifies a list of [CT_WebExtension](#) elements. The list of CT_WebExtension elements specifies all the bindings for web extensions, as specified by [\[MS-OWEXML\]](#) section 1.3, on the worksheet.

Child Elements:

webExtension: A CT_WebExtension element that specifies a binding for a web extension, as specified by [\[MS-OWEXML\]](#) section 1.3, on the worksheet.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_WebExtensions">
  <xsd:sequence>
    <xsd:element name="webExtension" type="CT_WebExtension" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.90 CT_WebExtension

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_WebExtensions](#)

A complex type that specifies a binding for a web extension, as specified by [\[MS-OWEXML\]](#) section 1.3, on the worksheet.

Child Elements:

xm:f: An [f](#) element that specifies the data range for the Binding. The formula MUST adhere to the grammar specified in Section [Formulas](#), with the following restrictions:

- MUST follow the ref-nospace-expression rule.
- MUST NOT use the bang-reference, bang-name, sheet-range-reference, or local-cell-reference production rules.

Attributes:

appRef: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies a unique identifier for a binding for a web extension. This value MUST be equal to the **appref** field (1) of a **CT_OsfWebExtensionBinding** element as specified by [\[MS-OWEXML\]](#) section 2.2.3.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_WebExtension">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="appRef" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.91 CT_Connection

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [connection](#)

A complex type that specifies the extended properties of an external connection ([\[ISO/IEC29500-1:2011\]](#) section 18.13). See section [2.2.4.1](#) for how this element integrates with the Office Open XML file formats specified in [\[ISO/IEC29500-1:2011\]](#).

Child Elements:

textPr: A **CT_TextPr** ([\[ISO/IEC29500-4:2011\]](#) section 18.13.12) element that specifies properties for data model data source text importation.

If this element is present, then the **type** attribute of the ancestor **CT_Connection** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, MUST be equal to "103".

modelTextPr: A **CT_ModelTextPr** element that specifies a data model data source text importation ([\[MS-XLSB\]](#) section 2.2.8.9.4) properties in addition to those specified in **textPr** element.

If this element is present, then:

- the **type** attribute of the ancestor **CT_Connection** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, MUST be equal to "103".
- Ancestor **CT_Connection** element MUST contain **textPr** element.

rangePr: A [CT_RangePr](#) element that specifies data model data source Worksheet Data connection ([\[MS-XLSB\]](#) section 2.2.8.9.3) properties.

If this element is present, then the **type** attribute of the ancestor **CT_Connection** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, MUST be equal to "102".

oledbPr: A [CT_OledbPr](#) element that specifies data model data source OLE DB connection ([\[MS-XLSB\]](#) section 2.2.8.9.1) properties.

If this element is present, then the **type** attribute of the ancestor **CT_Connection** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, MUST be equal to "100".

dataFeedPr: A [CT_DataFeedPr](#) element that specifies data model data source Data Feed connection ([\[MS-XLSB\]](#) section 2.2.8.9.2) properties.

If this element is present, then the **type** attribute of the ancestor **CT_Connection** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, MUST be equal to "101".

Attributes:

id: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the identifier of the Data Model data source. The string MUST be less than or equal to 65535 characters in length. The string length MUST be equal to zero characters if the **model** attribute equals "true".

model: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this connection is a connection to the spreadsheet data model. If this element equals "true", the **type** attribute of the ancestor **CT_Connection** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, MUST be equal to "5".

excludeFromRefreshAll: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this connection is not to be refreshed on Refresh All.

Value	Meaning
"true"	This connection is not to be refreshed on Refresh All.
"false"	This connection is to be refreshed on Refresh All.

autoDelete: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this connection will be automatically deleted when all data features which use it are deleted.

Value	Meaning
"true"	This connection will be automatically deleted when all data features that use it are deleted.
"false"	This connection will not be automatically deleted when all data features that use it are deleted.

usedByAddin: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this connection is used by an addin component and will not be deleted with any data feature that uses it.

Value	Meaning
"true"	This connection is used by an addin component.
"false"	This connection is not used by an addin component.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Connection">
  <xsd:sequence>
    <xsd:element name="textPr" minOccurs="0" maxOccurs="1" type="x:CT_TextPr"/>
    <xsd:element name="modelTextPr" minOccurs="0" maxOccurs="1" type="CT_ModelTextPr"/>
    <xsd:element name="rangePr" minOccurs="0" maxOccurs="1" type="CT_RangePr"/>
    <xsd:element name="oledbPr" minOccurs="0" maxOccurs="1" type="CT_OledbPr"/>
    <xsd:element name="dataFeedPr" minOccurs="0" maxOccurs="1" type="CT_DataFeedPr"/>
  </xsd:sequence>
  <xsd:attribute name="id" use="required" type="x:ST_Xstring"/>
  <xsd:attribute name="model" type="xsd:boolean" default="false" use="optional"/>
  <xsd:attribute name="excludeFromRefreshAll" type="xsd:boolean" default="false"
  use="optional"/>
  <xsd:attribute name="autoDelete" type="xsd:boolean" default="false" use="optional"/>
  <xsd:attribute name="usedByAddin" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.92 CT_CalculatedMemberExt

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

This element adds an element for supporting new properties for calculated members.

Child Elements:

calculatedMember: A **CT_CalculatedMember** (section [2.6.93](#)) element that specifies a definition for a custom member or measure that is applied to a pivot table.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CalculatedMemberExt">
  <xsd:sequence>
    <xsd:element ref="calculatedMember" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.93 CT_CalculatedMember

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_CalculatedMemberExt](#), [calculatedMember](#)

This element adds new properties for supporting calculated members.

Attributes:

measureGroup: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the measure group that this calculated member is associated with if **measure** is TRUE.

numberFormat: An **ST_CalcMemNumberFormat** (see section [2.7.25](#)) attribute that specifies the formatting type of the calculated member.

measure: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this calculated member is also a calculated measure.

Value	Meaning
"true"	This calculated member is also a calculated measure.
"false"	This calculated member is not a calculated measure.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CalculatedMember">
  <xsd:attribute name="measureGroup" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="numberFormat" type="ST_CalcMemNumberFormat" use="optional"
  default="default"/>
  <xsd:attribute name="measure" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.94 CT_FieldListActiveTabTopLevelEntity

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_PivotTableUISettings](#)

A complex type which specifies a top level object in the hierarchy of objects displayed in the PivotTable field list.

Attributes:

name: A **string** attribute that specifies name of the object in the PivotTable field list.

type: An **unsignedInt** attribute that specifies the type of this top level object. MUST be specified. MUST be one of the values in the following table:

Value	Object Type
0	OLAP Dimension. The name attribute of this element MUST be the MDX unique name of the dimension (1).
1	Workbook Table. The name attribute of this element MUST be the name of the workbook table.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_FieldListActiveTabTopLevelEntity">
  <xsd:attribute name="name" use="required" type="xsd:string"/>
  <xsd:attribute name="type" use="optional" default="0" type="xsd:unsignedInt"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.95 CT_PivotFilter

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [pivotFilter](#)

A complex type that specifies the extended properties of a **CT_PivotFilter** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element.

Attributes:

useWholeDay: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the **filter** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.33) element extended by this type uses whole days in its filtering criteria. MUST be false for **filters** for which the value of the attribute **type** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.33) is not one of the values mentioned in the table below. MUST be true if the value of the **name** attribute of the containing **CT_PivotTableDefinition** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element is equal to the value of the **name** (section [2.6.114](#)) attribute of at least one **CT_TimelineCachePivotTable** (section [2.6.114](#)) element in the **Timeline cache** (section [2.1.7](#)) and the value of the attribute **type** of the containing **filter** element is one of the following.

Enumeration Value
dateBetween (Date Between)
dateEqual (Date Equals)
dateNewerThan (Date Newer Than)
dateNewerThanOrEqual (Date Newer Than or Equal To)
dateNotBetween (Date Not Between)
dateNotEqual (Date Does Not Equal)
dateOlderThan (Date Older Than)
dateOlderThanOrEqual (Date Older Than Or Equal)
lastMonth (Last Month)
lastQuarter (Last Quarter)
lastWeek (Last Week)
lastYear (Last Year)

Enumeration Value
M1 (Dates in January)
M10 (Dates in October)
M11 (Dates in November)
M12 (Dates in December)
M2 (Dates in February)
M3 (Dates in March)
M4 (Dates in April)
M5 (Dates in May)
M6 (Dates in June)
M7 (Dates in July)
M8 (Dates in August)
M9 (Dates in September)
nextMonth (Next Month)
nextQuarter (Next Quarter)
nextWeek (Next Week)
nextYear (Next Year)
percent (Percent)
Q1 (First Quarter)
Q2 (Second Quarter)
Q3 (Third Quarter)
Q4 (Fourth Quarter)
sum (Sum)
thisMonth (This Month)
thisQuarter (This Quarter)
thisWeek (This Week)
thisYear (This Year)
today (Today)
tomorrow (Tomorrow)

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotFilter">
  <xsd:attribute name="useWholeDay" type="xsd:boolean" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.96 CT_PivotTableUISettings

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [pivotTableUISettings](#)

Specifies state for user interface used to construct and manipulate a PivotTable.

Child Elements:

activeTabTopLevelEntity: A [CT_FieldListActiveTabTopLevelEntity](#) element that specifies a field (1) that appears in the user's working set of fields in the PivotTable field list.

extLst: A [CT_ExtensionList](#) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

sourceDataName: An [ST_Xstring](#) ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the primary data connection (2) for the PivotTable. See **connection** ([\[ISO/IEC29500-1:2011\]](#) section 18.13.1)

relNeededHidden: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the user closed the relationship warning for this PivotTable.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotTableUISettings">
  <xsd:sequence>
    <xsd:element name="activeTabTopLevelEntity" type="CT_FieldListActiveTabTopLevelEntity"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="sourceDataName" type="xsd:string" use="optional"/>
  <xsd:attribute name="relNeededHidden" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.97 CT_TableSlicerCache

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [tableSlicerCache](#)

A complex type that specifies properties of the [slicer cache](#) specific to table slicer items.

Child Elements:

extLst: A **CT_ExtensionList** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

tableId: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the associated **Table** ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2). MUST match **id** attribute of an existing **Table** ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.2) element.

column: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies associated **Table Column** ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.3). MUST match **id** attribute of an existing **tableColumn** element representing a column (2) in **Table** specified by the **tableId** attribute.

sortOrder: An **ST_TabularSlicerCacheSortOrder** attribute that specifies how the table slicer items are sorted in the [slicer view](#).

customListSort: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether custom lists are used when sorting the table slicer items.

Value	Meaning
"false"	Custom lists are not used when sorting the table slicer items.
"true"	Custom lists are used when sorting the table slicer items.

crossFilter: An **ST_SlicerCacheCrossFilter** attribute that specifies how the table slicer items that are used in [slicer cross filtering](#) are displayed.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TableSlicerCache">
  <xsd:sequence>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="tableId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="column" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="sortOrder" type="x14:ST_TabularSlicerCacheSortOrder" use="optional"
  default="ascending"/>
  <xsd:attribute name="customListSort" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="crossFilter" type="x14:ST_SlicerCacheCrossFilter" use="optional"
  default="showItemsWithDataAtTop"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.98 CT_TimelineCacheRefs

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [timelineCacheRefs](#)

A complex type that specifies a list of [Timeline cache](#) part identifiers for the workbook. MUST contain fewer than 2³¹ elements.

Child Elements:

timelineCacheRef: A [CT_TimelineCacheRef](#) element that specifies a Timeline cache part identifier in this workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineCacheRefs">
  <xsd:sequence>
    <xsd:element name="timelineCacheRef" type="CT_TimelineCacheRef" minOccurs="1"
      maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.99 CT_TimelineCacheRef

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineCacheRefs](#)

A complex type that specifies a **Relationship** (section [1.4](#)) identifier to a **Timeline Cache** (section [2.3.5.1](#)) part in this workbook.

Attributes:

r:id: An **ST_RelationshipId** ([\[ISO/IEC29500-1:2011\]](#) section 22.8.2.1) attribute that specifies a **Relationship** (section [1.4](#)) identifier to a **Timeline Cache** (section [2.3.5.1](#)) part in this workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineCacheRef">
  <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.100 CT_TimelineRefs

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [timelineRefs](#)

CT_TimelineRefs is a complex type that specifies a list of Timeline (section [2.3.5](#)) part identifiers for the worksheet. MUST contain exactly one Timeline part identifier.

Child Elements:

timelineRef: A **CT_TimelineRef** element (section [2.6.101](#)) that specifies the Timeline (section [2.3.5](#)) part identifier for the worksheet.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_TimelineRefs">
  <xsd:sequence>
    <xsd:element name="timelineRef" type="CT_TimelineRef" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>

```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.101 CT_TimelineRef

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineRefs](#)

A complex type that specifies a [relationship](#) identifier of the part that contains the [Timelines](#) in this worksheet.

Attributes:

r:id: An **ST_RelationshipId** ([\[ISO/IEC29500-1:2011\]](#) section 22.8.2.1) attribute that specifies a relationship identifier of the part that contains the Timelines in this worksheet.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_TimelineRef">
  <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>

```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.102 CT_CacheHierarchy

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [cacheHierarchy](#)

CT_CacheHierarchy is a complex type which specifies additional properties for an OLAP measure.

Attributes:

aggregatedColumn: An **int** attribute that specifies the zero-based index of PivotTable cache hierarchy which corresponds to this OLAP measure. The referenced **CT_CacheHierarchy** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element specifies the PivotTable cache hierarchy that this OLAP measure aggregates. MUST only be specified if the **measure** attribute of this cache hierarchy is "true". The value MUST match the index of an existing cache hierarchy in **CT_CacheHierarchies** ([\[ISO/IEC29500-4:2011\]](#)) collection or be equal -1 if this OLAP measure is not an implicit measure which aggregates a cache hierarchy.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_CacheHierarchy">
  <xsd:attribute name="aggregatedColumn" use="required" type="xsd:int"/>

```

</xsd:complexType>

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.103 CT_SlicerCacheHideNoData

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [slicerCacheHideItemsWithNoData](#)

A complex type that specifies the extended properties of a [slicer cache](#), as specified in section [2.3.2.1](#).

Child Elements:

slicerCacheOlapLevelName: A [CT_SlicerCacheOlapLevelName](#) element that specifies the properties of an OLAP level in the OLAP hierarchy specified by the ancestor slicer cache. [slicer items](#) with no data in this **OLAP level** are not displayed.

Attributes:

count: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of **slicerCacheOlapLevelName** child elements of this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerCacheHideNoData">
  <xsd:sequence>
    <xsd:element name="slicerCacheOlapLevelName" type="CT_SlicerCacheOlapLevelName"
      minOccurs="0" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional" default="0"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.104 CT_SlicerCacheOlapLevelName

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_SlicerCacheHideNoData](#)

A complex type that specifies the properties of an OLAP level in the OLAP hierarchy specified by the ancestor [slicer cache](#). [slicer items](#) with no data in this **OLAP level** are not displayed.

Attributes:

uniqueName: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the MDX unique name of the OLAP level specified by this element within the OLAP hierarchy specified with this slicer cache. The length of this string **MUST** be at least 1 character and **MUST NOT** exceed 32,767 characters.

count: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the total number of hidden slicer items in this OLAP level within the OLAP hierarchy specified by this slicer cache.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SlicerCacheOlapLevelName">
  <xsd:attribute name="uniqueName" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.105 CT_TimelineStyles

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [timelineStyles](#)

A complex type that specifies a group of [Timeline Styles](#) and the default Timeline Style to apply to [Timelines](#).

Child Elements:

timelineStyle: A [CT_TimelineStyle](#) element that specifies a Timeline Style.

Attributes:

defaultTimelineStyle: A **string** ([\[XMLSCHEMA2\]](#) section 3.2.1) attribute that specifies the name of the default Timeline Style to apply to Timelines. The length of the string **MUST** be greater than or equal to 1 character and less than or equal to 255 characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineStyles">
  <xsd:sequence>
    <xsd:element name="timelineStyle" type="CT_TimelineStyle" minOccurs="0"
      maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="defaultTimelineStyle" type="xsd:string" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.106 CT_TimelineStyleElements

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineStyle](#)

A complex type that specifies the list of table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) elements of a [Timeline Style](#) that are specific to [Timelines](#).

Child Elements:

timelineStyleElement: A [CT_TimelineStyleElement](#) element that specifies a table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) element of a timeline style that is specific to timelines.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineStyleElements">
  <xsd:sequence>
    <xsd:element name="timelineStyleElement" type="CT_TimelineStyleElement" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.107 CT_TimelineStyle

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineStyles](#)

CT_TimelineStyle specifies table style elements, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.8, of the timeline style, as specified in section [Timeline Styles](#), that are specific to timelines, as specified in section [Timelines](#).

Child Elements:

timelineStyleElements: A [CT_TimelineStyleElements](#), as specified in section [Timeline Style Elements](#), that specifies table style elements of the timeline style that are specific to timelines. There MUST NOT be more than one **CT_TimelineStyleElements** in this element.

Attributes:

name: A **string** attribute, as specified in [\[XMLSCHEMA2\]](#) section 3.2.1, that specifies the name of the user-defined table style that this timeline style is based upon. The length of the **string** MUST be greater than or equal to 1 character and less than or equal to 255 characters. This **string** MUST be unique within the **CT_TimelineStyle** elements in the **Styles** part, as specified in [\[ISO/IEC29500-1:2011\]](#) section 12.3.20. This **string** MUST match the **name** attribute of a **CT_TableStyle** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, in the **Styles** part. In the **CT_TableStyle** element with a **name** attribute that matches this **string**, the **pivot** attribute MUST equal "false" and the **table** attribute MUST equal "false".

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineStyle">
  <xsd:sequence>
    <xsd:element name="timelineStyleElements" type="CT_TimelineStyleElements" minOccurs="0"
maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="xsd:string" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.108 CT_TimelineStyleElement

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineStyleElements](#)

A complex type that specifies a table style element, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.8, of a timeline style, as specified in section [Timeline Styles](#).

Attributes:

type: An [ST_TimelineStyleType](#) attribute that specifies the type of the table style element. This attribute MUST be unique within the parent **CT_TimelineStyleElements** complex type.

dxfid: An **ST_DxfId** attribute, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.18.25, that specifies a zero-based index for the list of elements specified by the **dxfs** global element, as specified in section [2.4.55](#). The specified **CT_Dxf** complex type, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, specifies the formatting to use with this table style element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineStyleElement">
  <xsd:attribute name="type" type="ST_TimelineStyleType" use="required"/>
  <xsd:attribute name="dxfid" type="x:ST_DxfId" use="optional"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.109 CT_TimelinePivotCacheDefinition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [timelinePivotCacheDefinition](#)

A complex type that specifies the extended properties of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) **PivotCache** definition.

Attributes:

timelineData: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the [Timeline Cache Relationship to PivotCache](#). MUST be "true" if the OLAP PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) **PivotCache** definition is being referenced by a [timeline cache](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelinePivotCacheDefinition">
  <xsd:attribute name="timelineData" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.110 CT_Timelines

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [timelines](#)

A complex type that specifies a list of **CT_Timeline** elements, as specified in section [2.6.111](#). The list of **CT_Timeline** elements specifies all [Timeline views](#) on the worksheet.

Child Elements:

timeline: A **CT_Timeline** element that specifies a Timeline view on the worksheet.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Timelines">
  <xsd:sequence>
    <xsd:element name="timeline" type="CT_Timeline" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.111 CT_Timeline

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_Timelines](#)

The **CT_Timeline** complex type specifies a **Timeline view** (section [2.3.5.2](#)) in this worksheet.

Child Elements:

extLst: A **CT_ExtensionList** element, as specified in [\[ISO/IEC29500-4:2011\]](#) section A.2, that specifies future extensibility for this element.

Attributes:

name: An **ST_Xstring** attribute, as specified in [\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19, that specifies the name of the **Timeline view**. This element **MUST** be a unique case-insensitive name within the scope of this workbook. The length of this attribute **MUST** be greater than or equal to one character and **MUST** be less than or equal to 32767 characters.

cache: An **ST_Xstring** attribute that specifies the name of the **Timeline cache** (section [2.3.5.1](#)) that this **Timeline view** is associated with. There **MUST** be a **CT_TimelineCacheDefinition** element (section [2.6.112](#)) within this workbook with the **name** attribute equal to the value of this attribute.

caption: An **ST_Xstring** attribute that specifies the caption of the **Timeline view**. If this string exists, the length **MUST** be greater than or equal to one character.

showHeader: A **Boolean** attribute, as specified in [\[XMLSCHEMA2\]](#) section 3.2.2, that specifies whether the header is displayed.

Value	Meaning
"true"	The header is displayed.
"false"	The header is suppressed.

showSelectionLabel: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the selection label is displayed.

Value	Meaning
"true"	The selection label is displayed.
"false"	The selection label is suppressed.

showTimeLevel: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the time level is displayed.

Value	Meaning
"true"	The time level is displayed.
"false"	The time level is suppressed.

showHorizontalScrollbar: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the horizontal scrollbar is displayed.

Value	Meaning
"true"	The horizontal scrollbar is displayed.
"false"	The horizontal scrollbar is suppressed.

level: An **unsignedInt** attribute, as specified in [\[XMLSCHEMA2\]](#) section 3.3.22, that specifies the current time level of the **Timeline** (section [2.3.5](#)). This element **MUST** be a value from the following table:

Value	Meaning
0	Year
1	Quarter
2	Month
3	Day

selectionLevel: An **unsignedInt** attribute that specifies the time level at which the current selection was made for the **Timeline**. This element **MUST** be a value from the following table:

Value	Meaning
0	Year
1	Quarter
2	Month
3	Day

scrollPosition: A **dateTime** attribute ([\[XMLSCHEMA2\]](#) section 3.2.7) that specifies the start date of the timespan scrolling position of the **Timeline**.

style: An **ST_Xstring** attribute ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) that specifies the **Timeline style** (section [2.3.5.4](#)) of the **Timeline view**. If this field (1) exists, this string **MUST** match the **name** attribute of a **CT_TimelineStyle** element (section [2.6.107](#)) within this workbook or **MUST** be equal to one of the built-in **Timeline style** names:

Built-in Timeline style names
TimelineStyleLight1
TimelineStyleLight2
TimelineStyleLight3
TimelineStyleLight4
TimelineStyleLight5
TimelineStyleLight6
TimelineStyleDark1
TimelineStyleDark2
TimelineStyleDark3
TimelineStyleDark4
TimelineStyleDark5
TimelineStyleDark6

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Timeline">
  <xsd:sequence>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="cache" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="caption" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="showHeader" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="showSelectionLabel" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="showTimeLevel" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="showHorizontalScrollbar" type="xsd:boolean" use="optional"
  default="true"/>
  <xsd:attribute name="level" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="selectionLevel" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="scrollPosition" type="xsd:dateTime" use="optional"/>
  <xsd:attribute name="style" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.112 CT_TimelineCacheDefinition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [timelineCacheDefinition](#)

A complex type that specifies a [Timeline cache](#).

Child Elements:

pivotTables: A **CT_TimelineCachePivotTables** element (section [2.6.113](#)) that specifies a group of **CT_TimelineCachePivotTable** elements (section [2.6.114](#)) that specify the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views and [Non-Worksheet PivotTables](#) that are filtered by the **Timeline cache** (section [2.1.7](#)).

state: A **CT_TimelineState** element (section [2.6.116](#)) that specifies the information used for display in the **Timeline view** (section [2.3.5.2](#)).

timelinePivotFilter: A **CT_TimelinePivotFilter** element (section [2.6.118](#)) that specifies the filter used by the Timeline Cache (section [2.1.7](#)) to filter PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views and Non-Worksheet PivotTables. This element MUST exist only if the **filterType** attribute of the **CT_TimelineState** (section [2.6.116](#)) element of the Timeline Cache has a value that is not one of the following:

Enumeration Value	Description
dateBetween (Date Between)	Indicates the "between" filter for date values.
dateEqual (Date Equals)	Indicates the "equals" filter for date values.
unknown	Indicates the absence of a filter for date values.

extLst: A **CT_ExtensionList** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

name: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the **Timeline cache** (section [2.3.5.1](#)). MUST adhere to the name production rule provided in section [2.2.2](#). MUST be a unique case-insensitive name within the scope of defined names.

sourceName: An **ST_Xstring** attribute that specifies the MDX unique name of the key attribute (1) of the associated OLAP hierarchy if the **Timeline source data** (section [2.3.5.1.1](#)) is an OLAP data source (1).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineCacheDefinition">
  <xsd:sequence>
    <xsd:element name="pivotTables" type="CT_TimelineCachePivotTables" minOccurs="0"
maxOccurs="1"/>
    <xsd:element name="state" type="CT_TimelineState" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="timelinePivotFilter" minOccurs="0" maxOccurs="1"
type="CT_TimelinePivotFilter"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="sourceName" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.113 CT_TimelineCachePivotTables

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineCacheDefinition](#)

A complex type that specifies a group of [CT_TimelineCachePivotTable](#) elements that specify the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) views and Charts ([\[ISO/IEC29500-1:2011\]](#) section 21.2) based on [Non-Worksheet PivotTables](#) that are filtered by the [Timeline cache](#).

Child Elements:

pivotTable: A [CT_TimelineCachePivotTable](#) element that specifies the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view or a Non-Worksheet PivotTable that is filtered. The list of **pivotTable** child elements MUST NOT contain duplicates.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineCachePivotTables">
  <xsd:sequence>
    <xsd:element name="pivotTable" type="CT_TimelineCachePivotTable" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.114 CT_TimelineCachePivotTable

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineCachePivotTables](#)

A complex type that specifies a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view filtered by a [Timeline cache](#).

Attributes:

tabId: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the unique identifier (UID) of the worksheet that contains the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view specified by the **name** attribute. MUST match the **sheetId** of an existing sheet (1) ([\[ISO/IEC29500-4:2011\]](#) section A.2) element within the workbook. MUST be equal to the decimal equivalent of 0xFFFFFFFF if the PivotTable specified by the name attribute is a [Non-Worksheet PivotTable](#).

name: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) view on the worksheet specified by **tabId**. MUST match the **name** attribute of an existing [pivotTableDefinition](#) element in the worksheet. The **createdVersion** attribute of the **CT_PivotTableDefinition** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that defines the specified PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) MUST be greater than or equal to 3.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineCachePivotTable">
  <xsd:attribute name="tabId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.115 CT_TimelineRange

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineState](#)

A complex type that specifies the date range for a CT_TimelineState element that is the parent of this element.

Attributes:

startDate: A **dateTime** ([\[XMLSCHEMA2\]](#) section 3.2.7) attribute that specifies the start value of the date range.

endDate: A **dateTime** attribute that specifies the end value of the date range.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineRange">
  <xsd:attribute name="startDate" type="xsd:dateTime" use="required"/>
  <xsd:attribute name="endDate" type="xsd:dateTime" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.116 CT_TimelineState

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineCacheDefinition](#)

The **CT_TimelineState** complex type specifies the **Timeline state** (section [2.3.5.1.4](#)) of the **Timeline cache** (section [2.3.5.1](#)).

Child Elements:

selection: A **CT_TimelineRange** element (section [2.6.115](#)) that specifies the start and end dates that are selected in the **Timeline view** (section [2.3.5.2](#)). The start and end dates in the selection element MUST be interpreted as **dateTime** values ([\[XMLSCHEMA2\]](#) section 3.2.7).

bounds: A **CT_TimelineRange** element that specifies the minimum and maximum dates available for display in the **Timeline view**. The minimum and maximum dates in the bounds element MUST be interpreted as **dateTime** values ([\[XMLSCHEMA2\]](#) section 3.2.7).

extLst: A **CT_ExtensionList** element ([\[ISO/IEC29500-4:2011\]](#) section A.2) that specifies future extensibility for this element.

Attributes:

singleRangeFilterState: A **Boolean** attribute ([\[XMLSCHEMA2\]](#) section 3.2.2) that specifies whether the filtering state of the **Timeline** (section [2.3.5](#)) is a contiguous date range.

Value	Meaning
"true"	The filtering state of the Timeline is a contiguous date range.
"false"	The filtering state of the Timeline is not a contiguous date range.

minimalRefreshVersion: An **unsignedInt** attribute ([\[XMLSCHEMA2\]](#) section 3.3.22) that specifies the minimum application version required to refresh the **Timeline cache**.

lastRefreshVersion: An **unsignedInt** attribute that specifies the application version that last refreshed the **Timeline cache**.

pivotCacheId: An **unsignedInt** attribute that specifies the associated OLAP PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache. This element **MUST** be equal to the **pivotCacheId** attribute of an existing **CT_PivotCacheDefiniton** element (section [2.6.33](#)).

filterType: An **ST_PivotFilterType** attribute ([\[ISO/IEC29500-1:2011\]](#) section 18.18.59) that specifies type of the **filter** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.33) used in the **Timeline**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelineState">
  <xsd:sequence>
    <xsd:element name="selection" type="CT_TimelineRange" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="bounds" type="CT_TimelineRange" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="singleRangeFilterState" type="xsd:boolean" use="optional"
  default="true"/>
  <xsd:attribute name="minimalRefreshVersion" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="lastRefreshVersion" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="pivotCacheId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="filterType" use="required" type="x:ST_PivotFilterType"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.117 CT_WorkbookPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [workbookPr](#)

CT_WorkbookPr is a complex type that specifies additional properties for a workbook.

Attributes:

chartTrackingRefBase: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies how data point (2) properties and datalabels in all charts ([ISO/IEC29500-1:2011] section 21.2) in this workbook behave.

Value	Meaning
True	Datapoint properties and datalabels ([MS-ODRAWXML] section 2.2.1.2) in all charts ([ISO/IEC29500-1:2011] section 21.2) in this workbook follow their reference.
False	Datapoint properties and datalabels ([MS-ODRAWXML] section 2.2.1.2) in all charts ([ISO/IEC29500-1:2011] section 21.2) in this workbook follow their position in the chart.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_WorkbookPr">
  <xsd:attribute name="chartTrackingRefBase" type="xsd:boolean" default="false"/>
</xsd:complexType>
```

See section 5.3 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.118 CT_TimelinePivotFilter

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineCacheDefinition](#)

A complex type that specifies the filter used by the Timeline Cache (section 2.1.7) to filter PivotTable ([ISO/IEC29500-1:2011] section 18.10) views and [Non-Worksheet PivotTables](#).

Child Elements:

autoFilter: A **CT_AutoFilter** ([ISO/IEC29500-1:2011] section 18.3.1.2) element that specifies the embedded auto filter of the filter.

Attributes:

useWholeDay: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies whether the **pivot filter** ([ISO/IEC29500-1:2011] section 18.10.1.33) associated with either the PivotTable ([ISO/IEC29500-1:2011] section 18.10) or Non-Worksheet PivotTable (section 2.3.3) filtered by the Timeline Cache (section 2.1.7) uses whole days in its filtering criteria.

Value	Meaning
"true"	The pivot filter ([ISO/IEC-29500-1] section 18.10.1.33) associated with either the PivotTable ([ISO/IEC-29500-1] section 18.10) or Non-Worksheet PivotTable (section 2.3.3) filtered by the Timeline Cache (section 2.1.7) uses whole days in its filtering criteria.
"false"	The pivot filter ([ISO/IEC-29500-1] section 18.10.1.33) associated with either the PivotTable ([ISO/IEC-29500-1] section 18.10) or Non-Worksheet PivotTable (section 2.3.3) filtered by the Timeline Cache (section 2.1.7) does not use whole days in its filtering criteria.

fld: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the index of the field (1) to which the **pivot filter** associated with this filter belongs to.

id: An **unsignedInt** attribute that specifies the unique identifier of the **pivot filter** associated with this filter as assigned by the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) or Non-Worksheet PivotTable (section [2.3.3](#)) filtered by the Timeline Cache (section [2.1.7](#)).

name: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the filter. This string **MUST** be less than or equal to 65,535 characters in length.

description: An **ST_Xstring** attribute that specifies the description of the filter. This string **MUST** be less than or equal to 65,535 characters in length.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_TimelinePivotFilter">
  <xsd:sequence>
    <xsd:element name="autoFilter" minOccurs="0" maxOccurs="1" type="x:CT_AutoFilter"/>
  </xsd:sequence>
  <xsd:attribute name="useWholeDay" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="fld" use="required" type="xsd:unsignedInt"/>
  <xsd:attribute name="id" use="required" type="xsd:unsignedInt"/>
  <xsd:attribute name="name" use="optional" type="x:ST_Xstring"/>
  <xsd:attribute name="description" use="optional" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.119 CT_ModelTextPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_Connection](#)

Specifies Model Data Source text importation ([\[MS-XLSB\]](#) section 2.2.8.9.4) properties in addition to those specified in **CT_TextPr** ([\[ISO/IEC29500-1:2011\]](#) section A.2) element.

Attributes:

headers: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether data imported by this connection has column (2) headers.

Value	Meaning
"true"	Data imported by this connection has column (2) headers.
"false"	Data imported by this connection does not have column (2) headers.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ModelTextPr">
  <xsd:attribute name="headers" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.120 CT_RangePr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_Connection](#)

The **CT_RangePr** complex type specifies properties of a Model Data Source Worksheet Data connection ([\[MS-XLSB\]](#) section 2.2.8.9.3).

Attributes:

sourceName: An attribute of type **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) that specifies the string identifier of the source cell range for this connection. The string length MUST be less than or equal to 65,535 characters.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_RangePr">
  <xsd:attribute name="sourceName" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.121 CT_DbTable

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_DbTables](#)

The **CT_DbTable** complex type specifies a single database table that is used by a Model Data Source **OLE DB** connection ([\[MS-XLSB\]](#) section 2.2.8.9.1) or Model Data Source Data Feed connection ([\[MS-XLSB\]](#) section 2.2.8.9.2).

Attributes:

name: An attribute of type **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) that specifies the database table name.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DbTable">
  <xsd:attribute name="name" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.122 CT_DbTables

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_OledbPr](#), [CT_DataFeedPr](#)

The **CT_DbTables** complex type specifies the list of database tables that are used by a Model Data Source OLE DB connection ([\[MS-XLSB\]](#) section 2.2.8.9.1) or Model Data Source Data Feed connection ([\[MS-XLSB\]](#) section 2.2.8.9.2).

Child Elements:

dbTable: An element of type **CT_DbTable** (section [2.6.121](#)) specifying a single database table that is used by this connection.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DbTables">
  <xsd:sequence>
    <xsd:element name="dbTable" minOccurs="1" maxOccurs="unbounded" type="CT_DbTable"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.123 CT_DbCommand

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_OledbPr](#)

The **CT_DbCommand** complex type specifies OLE DB command text that is used by a Model Data Source OLE DB connection ([\[MS-XLSB\]](#) section 2.2.8.9.1).

Attributes:

text: An attribute of type **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) that specifies OLE DB command text.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DbCommand">
  <xsd:attribute name="text" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.124 CT_OledbPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_Connection](#)

The **CT_OledbPr** complex type specifies properties of a Model Data Source OLE DB connection ([\[MS-XLSB\]](#) section 2.2.8.9.1).

Child Elements:

dbTables: An element of type **CT_DbTables** (section [2.6.122](#)) specifying the list of database tables that are used by this connection.

dbCommand: An element of type **CT_DbCommand** (section [2.6.123](#)) specifying OLE DB command text that is used by this connection.

Attributes:

connection: An attribute of type **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) that specifies the OLE DB connection string.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_OledbPr">
  <xsd:choice minOccurs="1" maxOccurs="1">
    <xsd:element name="dbTables" type="CT_DbTables"/>
    <xsd:element name="dbCommand" type="CT_DbCommand"/>
  </xsd:choice>
  <xsd:attribute name="connection" use="optional" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.125 CT_DataFeedPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_Connection](#)

Specifies properties of a Model Data Source Data Feed connection ([\[MS-XLSB\]](#) section 2.2.8.9.2).

Child Elements:

dbTables: A [CT_DbTables](#) element that specifies the list of database tables used by this connection.

Attributes:

connection: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies connection string.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DataFeedPr">
  <xsd:sequence>
    <xsd:element name="dbTables" type="CT_DbTables" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="connection" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.126 CT_CachedUniqueNames

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [cachedUniqueNames](#)

A complex type that specifies the MDX unique names for PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache items in this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache field (1). MUST NOT exist if the **model** attribute of [CT_Connection](#) element of connection ([\[ISO/IEC29500-1:2011\]](#) section 2.6.91) associated with this PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) pivot cache is not equal to "true".

Child Elements:

cachedUniqueName: A [CT_CachedUniqueName](#) element that specifies the MDX unique name for a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache item.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CachedUniqueNames">
  <xsd:sequence>
    <xsd:element name="cachedUniqueName" minOccurs="1" maxOccurs="unbounded"
type="CT_CachedUniqueName"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.127 CT_CachedUniqueName

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_CachedUniqueNames](#)

A complex type that specifies the MDX unique name for a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache item.

Attributes:

index: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies an index of the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache item in this **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) cache field (1). MUST be less than **count** attributes of the **CT_Items** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element specified by the ancestor **CT_CacheField** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element. MUST be unique within parent [CT_CachedUniqueNames](#) (section [2.6.126](#)) collection.

name: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the MDX unique name. MUST be less than or equal to 65,535 characters in length.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CachedUniqueName">
  <xsd:attribute name="index" use="required" type="xsd:unsignedInt"/>
  <xsd:attribute name="name" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.128 CT_ModelTable

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_ModelTables](#)

Specifies properties of a single table in spreadsheet data model.

Attributes:

id: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies unique id of the spreadsheet data model table.

name: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies name of the spreadsheet data model table.

connection: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies name of the workbook connection associated with this spreadsheet data model table.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ModelTable">
  <xsd:attribute name="id" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="connection" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.129 CT_ModelTables

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_DataModel](#)

Specifies tables in the spreadsheet data model.

Child Elements:

modelTable: A [CT_ModelTable](#) element that specifies properties of a single table in spreadsheet data model.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ModelTables">
  <xsd:sequence>
    <xsd:element name="modelTable" minOccurs="1" maxOccurs="unbounded" type="CT_ModelTable"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.130 CT_ModelRelationship

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_ModelRelationships](#)

Specifies a single relationship in the spreadsheet data model.

Attributes:

fromTable: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the foreign key table for this relationship.

fromColumn: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the foreign key table column (2) for this relationship.

toTable: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the primary key table for this relationship.

toColumn: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the name of the primary key table column (2) for this relationship.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ModelRelationship">
  <xsd:attribute name="fromTable" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="fromColumn" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="toTable" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="toColumn" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.131 CT_ModelRelationships

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_DataModel](#)

Specifies active relationships in the spreadsheet data model.

Child Elements:

modelRelationship: A [CT_ModelRelationship](#) element that specifies a single relationship in the spreadsheet data model.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ModelRelationships">
  <xsd:sequence>
    <xsd:element name="modelRelationship" minOccurs="1" maxOccurs="unbounded"
type="CT_ModelRelationship"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.132 CT_DataModel

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [dataModel](#)

Specifies properties of a spreadsheet data model.

Child Elements:

modelTables: A **CT_ModelTables** (section [2.6.129](#)) element that specifies tables in the spreadsheet data model.

modelRelationships: A **CT_ModelRelationships** (section [2.6.131](#)) element that specifies active relationships in the spreadsheet data model.

extLst: A **CT_ExtensionList** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

minVersionLoad: An **unsignedByte** attribute that specifies the minimum application version required to load the spreadsheet data model in this workbook. This MUST be greater than or equal to 5.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DataModel">
  <xsd:sequence>
    <xsd:element name="modelTables" minOccurs="0" maxOccurs="1" type="CT_ModelTables"/>
    <xsd:element name="modelRelationships" minOccurs="0" maxOccurs="1"
type="CT_ModelRelationships"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="minVersionLoad" type="xsd:unsignedByte" use="optional" default="5"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.133 CT_PivotTableData

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [pivotTableData](#)

The **CT_PivotTableData** complex type specifies the **PivotValues** (section [2.3.4](#)) of the **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) that is specified by the **pivotTableReference** (section [2.4.1](#)) element in the extension of a workbook (section [2.2.4.10](#)).

Child Elements:

pivotRow: A **CT_PivotRow** (section [2.6.134](#)) element that specifies a single row (2) of **PivotValueCells** (section [2.3.4.1](#)) in an element of this type in the **PivotTable** ([\[ISO/IEC29500-](#)

[1:2011](#) section 18.10) that is specified by the **pivotTableReference** (section [2.4.1](#)) element in the extension of a workbook (section [2.2.4.10](#)).

Attributes:

rowCount: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of **pivotRow** child elements in an element of this type. This value MUST be equal to the value of the **count** attribute of the **rowItems** element, as specified in [\[ISO/IEC29500-1:2011\]](#) section 18.10.1.84.

columnCount: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute specifying the number of **PivotValueCells** (section [2.3.4.1](#)) that are specified by the **CT_PivotValueCell** (section [2.6.135](#)) complex type in each of the **pivotRow** child elements of this type. This value MUST be equal to the value of the **count** attribute in the **pivotRow** element, as specified by the **CT_PivotRow** (section [2.6.134](#)) complex type. This value MUST be equal to the value of the **count** attribute of the **colItems**, ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.17) element.

cacheId: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the associated OLAP PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) PivotCache.

The OLAP PivotTable PivotCache that is specified by this attribute MUST be extended by an **ext** ([\[ISO/IEC29500-1:2011\]](#) section 18.2.7) element that has a structure specified by a **CT_PivotCacheDefinition** (section [2.6.33](#)) element. The **pivotCacheId** attribute of such a **CT_PivotCacheDefinition** element MUST be equal to this attribute.

The OLAP PivotTable PivotCache that is specified by this attribute MUST also be extended by an **ext** element that has structure specified by a **CT_PivotCacheIdVersion** (section [2.6.139](#)) element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotTableData">
  <xsd:sequence>
    <xsd:element name="pivotRow" type="CT_PivotRow" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="rowCount" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="columnCount" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="cacheId" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.134 CT_PivotRow

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_PivotTableData](#)

A complex type that specifies a single row (2) of [PivotValueCells](#) in the **pivotTableData** element of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) specified by the [pivotTableReference](#) element in the extension of a workbook as specified by section [2.2.4.10](#).

Child Elements:

c: A [CT_PivotValueCell](#) element that specifies a PivotValueCell.

Attributes:

r: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the row (2) index of this element. MUST be within the range of items as specified by the **rowCount** attribute of the complex type **CT_PivotTableData**.

count: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the number of child elements of type **CT_PivotValueCell** in the current **pivotRow** element. MUST be less than or equal to the value specified by the **columnCount** attribute of complex type **CT_PivotTableData**.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotRow">
  <xsd:sequence>
    <xsd:element name="c" type="CT_PivotValueCell" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="r" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
```

See section 5.3 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.135 CT_PivotValueCell

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_PivotRow](#)

A complex type that specifies a [PivotValueCell](#).

Child Elements:

v: An **ST_Xstring** ([ISO/IEC29500-1:2011] section 22.9.2.19) element that specifies the string representation of the **Value** of a **PivotValueCell**. The attribute **t** of the parent **CT_PivotValueCell** element specifies how application interprets this element.

x: A [CT_PivotValueCellExtra](#) element that specifies the [server formatting](#) on the current **CT_PivotValueCell** element.

Attributes:

i: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the column (2) index of the current **CT_PivotValueCell** element. MUST be within the range of items as specified by the **columnCount** attribute of complex type [CT_PivotTableData](#).

t: An [ST_SXVCellType](#) attribute that specifies the type of the **PivotValueCell** represented by the parent element of this attribute.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotValueCell">
  <xsd:sequence>
    <xsd:element name="v" type="x:ST_Xstring" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="x" type="CT_PivotValueCellExtra" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

```

</xsd:sequence>
<xsd:attribute name="i" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="t" type="ST_SXVCellType" use="optional" default="n"/>
</xsd:complexType>

```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.136 CT_PivotValueCellExtra

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_PivotValueCell](#)

A complex type that specifies the **server formatting** (section [2.3.4.1.2](#)) for a **CT_PivotValueCell** element (section [2.6.135](#)) that is the parent of this element.

Attributes:

in: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies an index to the list of the numeric formats, specified by the **pivotTableServerFormats** element (section [2.4.2](#)) specified in the extension of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) specified by the **pivotTableReference** element (section [2.4.1](#)) in the extension of a workbook as specified in section [2.2.4.10](#). The value MUST be between zero and the **count** attribute of the **CT_PivotTableServerFormats** element (section [2.6.137](#)).

bc: An **ST_UnsignedIntHex** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.86) attribute that specifies the background color for the **CT_PivotValueCell** element (section [2.6.135](#)) that is a parent of this element. The color is specified as a hexadecimal value in RGB space.

fc: An **ST_UnsignedIntHex** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.86) attribute that specifies the foreground color for the **CT_PivotValueCell** element that is a parent of this element. The color is specified as a hexadecimal value in RGB space.

i: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the **PivotValueCell** (section [2.3.4.1](#)) specified by **CT_PivotValueCell**, that is a parent of this element, contains italic formatting. A value of one or true indicates this value contains italic formatting on the server.

un: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the **PivotValueCell** specified by **CT_PivotValueCell** that is a parent of this element contains underline formatting. A value of 1 or true indicates this value contains underline formatting on the server.

st: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the **PivotValueCell** specified by **CT_PivotValueCell** that is a parent of this element contains strikethrough formatting. A value of 1 or true indicates this value contains strikethrough formatting on the server.

b: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether the **PivotValueCell** specified by **CT_PivotValueCell** that is a parent of this element contains bold formatting. A value of 1 or true indicates this value contains bold formatting on the server.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_PivotValueCellExtra">
  <xsd:attribute name="in" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="bc" type="x:ST_UnsignedIntHex" use="optional"/>
  <xsd:attribute name="fc" type="x:ST_UnsignedIntHex" use="optional"/>

```

```

<xsd:attribute name="i" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="un" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="st" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="b" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>

```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.137 CT_PivotTableServerFormats

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

A complex type that specifies a list of **CT_ServerFormat** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.86) elements in a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) that is specified by a [pivotTableReference](#) element in the extension of a workbook. MUST contain fewer than 2³¹ elements.

Child Elements:

serverFormat: A **CT_ServerFormat** ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.86) element that specifies the numeric format for one or more [PivotValueCells](#).

Attributes:

count: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of **serverFormat** child elements in the collection.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_PivotTableServerFormats">
  <xsd:sequence>
    <xsd:element name="serverFormat" type="x:CT_ServerFormat" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" use="required" type="xsd:unsignedInt"/>
</xsd:complexType>

```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.138 CT_PivotCacheDecoupled

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [pivotCacheDecoupled](#)

A complex type that specifies the extended properties of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) **PivotCache** definition.

Attributes:

decoupled: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether this **PivotCache** definition is associated with a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) that is specified by a [pivotTableReference](#) element in the extension of a workbook.

Value	Meaning
"true"	This PivotCache Definition is associated with a PivotTable ([ISO/IEC-29500-1] section 18.10) that is specified by a pivotTableReference element in the extension of a workbook.
"false"	This PivotCache Definition has no relationship with a PivotTable ([ISO/IEC-29500-1] section 18.10) that is specified by a pivotTableReference element in the extension of a workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotCacheDecoupled">
  <xsd:attribute name="decoupled" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.139 CT_PivotCacheIdVersion

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [pivotCacheIdVersion](#)

A complex type that specifies the extended properties of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) **PivotCache** definition.

Attributes:

cacheIdSupportedVersion: An **unsignedByte** ([\[XMLSCHEMA2\]](#) section 3.3.24) attribute that specifies minimum version of the application where this **pivotCacheId** attribute of an existing [CT_PivotCacheDefinition](#) element is guaranteed to be unique.

cacheIdCreatedVersion: An **unsignedByte** ([\[XMLSCHEMA2\]](#) section 3.3.24) attribute that specifies the minimum version of the application where this **pivotCacheId** attribute of an existing CT_PivotCacheDefinition element can be changed upon saving the workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_PivotCacheIdVersion">
  <xsd:attribute name="cacheIdSupportedVersion" type="xsd:unsignedByte" use="required"/>
  <xsd:attribute name="cacheIdCreatedVersion" type="xsd:unsignedByte" use="required"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.140 CT_Timeline

Target namespace: <http://schemas.microsoft.com/office/drawing/2012/timeslicer>

Referenced by: [timeslicer](#)

This complex type specifies which [timeline view](#) is associated with this drawing element.

Child Elements:

extLst: A **CT_OfficeArtExtensionList** ([\[ISO/IEC29500-4:2011\]](#) section A.4.1) element that specifies future extensibility for this element.

Attributes:

name: A **string** ([\[XMLSCHEMA2\]](#) section 3.2.1) attribute that specifies the name of the timeline view (section [2.3.5.2](#)) that is associated with this drawing element. The value of this attribute MUST match the value of the **name** attribute of a **timeline** element within the CT_Timelines element (section [2.6.110](#)) for the current worksheet.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Timeline">
  <xsd:sequence>
    <xsd:element name="extLst" type="a:CT_OfficeArtExtensionList" minOccurs="0"
maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="xsd:string" use="required"/>
</xsd:complexType>
```

See section [5.7](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.141 CT_AbsolutePath

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/ac>

Referenced by: [absPath](#)

CT_AbsolutePath is a complex type that specifies the absolute path to a workbook.

Attributes:

url: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the URL string of the absolute path to the workbook.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_AbsolutePath">
  <xsd:attribute name="url" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
```

See section [5.9](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.142 CT_DataField

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [dataField](#)

This complex type specifies extended information about a **PivotTable** ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data field (1) item ([\[ISO/IEC29500-1:2011\]](#) section 18.10.1.22).

Attributes:

isCountDistinct: A **Boolean** ([XMLSCHEMA2] section 3.2.2) attribute that specifies that the aggregation function which applies to this data field (1) item ([ISO/IEC29500-1:2011] section 18.10.1.22) is the count of unique values. If this value is true, the subtotal attribute is ignored.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_DataField">
  <xsd:attribute name="isCountDistinct" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section 5.3 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.6.143 CT_Survey

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [survey](#)

CT_Survey is a complex type that specifies the properties for a survey.

Child Elements:

surveyPr: A [CT_SurveyElementPr](#) element that specifies additional properties of the survey.

titlePr: A [CT_SurveyElementPr](#) element that specifies additional properties associated with the title of the survey.

descriptionPr: A [CT_SurveyElementPr](#) element that specifies additional properties associated with the description of the survey.

questions: A [CT_SurveyQuestions](#) element that specifies the set of survey question elements associated with this survey.

extLst: A [CT_ExtensionList](#) ([ISO/IEC29500-4:2011] section A.2) element that specifies future extensibility for this element.

Attributes:

id: An **unsignedInt** ([XMLSCHEMA2] section 3.3.22) attribute that specifies the unique identifier (UID) of the survey. This id **MUST** be unique within the workbook.

guid: An **ST_Guid** ([ISO/IEC29500-1:2011] section 22.9.2.4) attribute that identifies this survey.

title: An **ST_Xstring** ([ISO/IEC29500-1:2011] section 22.9.2.19) attribute that specifies the title of the survey.

description: An **ST_Xstring** ([ISO/IEC29500-1:2011] section 22.9.2.19) attribute that specifies the description of the survey.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Survey">
  <xsd:sequence>
    <xsd:element name="surveyPr" type="CT_SurveyElementPr" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

```

<xsd:element name="titlePr" type="CT_SurveyElementPr" minOccurs="0" maxOccurs="1"/>
<xsd:element name="descriptionPr" type="CT_SurveyElementPr" minOccurs="0" maxOccurs="1"/>
<xsd:element name="questions" type="CT_SurveyQuestions" minOccurs="1" maxOccurs="1"/>
<xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
</xsd:sequence>
<xsd:attribute name="id" type="xsd:unsignedInt" use="required"/>
<xsd:attribute name="guid" type="x:ST_Guid" use="required"/>
<xsd:attribute name="title" type="x:ST_Xstring" use="optional"/>
<xsd:attribute name="description" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>

```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.144 CT_SurveyQuestions

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_Survey](#)

CT_SurveyQuestions is a complex type that specifies a list of survey question elements present in a survey.

Child Elements:

questionsPr: A [CT_SurveyElementPr](#) element that specifies additional properties associated with the list of survey question elements.

question: A [CT_SurveyQuestion](#) element that specifies one survey question in the list.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xsd:complexType name="CT_SurveyQuestions">
  <xsd:sequence>
    <xsd:element name="questionsPr" type="CT_SurveyElementPr" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="question" type="CT_SurveyQuestion" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>

```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.145 CT_SurveyQuestion

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_SurveyQuestions](#)

CT_SurveyQuestion is a complex type that specifies the properties of a survey question.

Child Elements:

questionPr: A [CT_SurveyElementPr](#) element that specifies additional properties associated with the survey question.

extLst: A **CT_ExtensionList** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

binding: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the unique identifier (UID) of the Table Column ([\[ISO/IEC29500-1:2011\]](#) section 18.5.1.3) to which the survey question is bound. MUST match the **id** of an existing Table Column ([\[ISO/IEC29500-1:2011\]](#) section 18.5) element within the Table ([\[ISO/IEC29500-1:2011\]](#) section 18.5) with which the survey is associated.

text: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the main text of the survey question.

type: An **ST_QuestionType** attribute that specifies the type of the survey question.

format: An **ST_QuestionFormat** attribute that specifies the format of answers to the survey question.

helpText: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies additional descriptive text associated with the survey question.

required: A **Boolean** ([\[XMLSCHEMA2\]](#) section 3.2.2) attribute that specifies whether an answer for the survey question is required when filling in the corresponding survey.

Value	Meaning
"false"	The answer to the survey question is not required when filling in the survey.
"true"	The answer to the survey question is required when filling in the survey.

defaultValue: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the default answer for the survey question.

decimalPlaces: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the number of digits after the decimal to use in a numerical answer to a survey question. MUST be less than or equal to 15.

rowSource: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies the set of available answers for the survey question. The set of available answers is a semicolon delimited list of values. The string MUST conform to the following Augmented Backus-Naur Form (ABNF) ([\[RFC5234\]](#)) grammar:

```
rowSource = [value] / *terminated-value value
terminated-value = value ";"
value = *value-char-with-quote / quoted-value
quoted-value = %x22 value-char-with-semicolon %x22
value-char-with-semicolon = value-char / ";"
value-char-with-quote = value-char / %x22
;value-char = as defined by the production Char in the [W3C-XML] section 2.2, but MUST NOT be
;" or %x22
```

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SurveyQuestion">
```

```

<xsd:sequence>
  <xsd:element name="questionPr" type="CT_SurveyElementPr" minOccurs="0" maxOccurs="1"/>
  <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
</xsd:sequence>
<xsd:attribute name="binding" type="xsd:unsignedInt" use="required"/>
<xsd:attribute name="text" type="x:ST_Xstring" use="optional"/>
<xsd:attribute name="type" type="ST_QuestionType" use="optional"/>
<xsd:attribute name="format" type="ST_QuestionFormat" use="optional"/>
<xsd:attribute name="helpText" type="x:ST_Xstring" use="optional"/>
<xsd:attribute name="required" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="defaultValue" type="x:ST_Xstring" use="optional"/>
<xsd:attribute name="decimalPlaces" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="rowSource" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>

```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.146 CT_SurveyElementPr

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_Survey](#), [CT_SurveyQuestions](#), [CT_SurveyQuestion](#)

CT_SurveyElementPr is a complex type that specifies additional properties of a survey element.

Child Elements:

extLst: A **CT_ExtensionList** ([\[ISO/IEC29500-4:2011\]](#) section A.2) element that specifies future extensibility for this element.

Attributes:

cssClass: An **ST_Xstring** ([\[ISO/IEC29500-1:2011\]](#) section 22.9.2.19) attribute that specifies a Cascading Style Sheet (CSS, [\[CSS-Level2-2009\]](#)) class name to apply to the survey element.

bottom: An **int** ([\[XMLSCHEMA2\]](#) section 3.3.17) attribute that specifies the bottom boundary of this survey element in pixels.

top: An **int** ([\[XMLSCHEMA2\]](#) section 3.3.17) attribute that specifies the top boundary of the survey element in pixels.

left: An **int** ([\[XMLSCHEMA2\]](#) section 3.3.17) attribute that specifies the left boundary of the survey element in pixels.

right: An **int** ([\[XMLSCHEMA2\]](#) section 3.3.17) attribute that specifies the right boundary of the survey element in pixels.

width: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the width of the survey element in pixels.

height: An **unsignedInt** ([\[XMLSCHEMA2\]](#) section 3.3.22) attribute that specifies the height of the survey element in pixels.

position: An **ST_SurveyPosition** attribute that specifies the type of positioning to be used on the survey element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_SurveyElementPr">
  <xsd:sequence>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="cssClass" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="bottom" type="xsd:int" use="optional"/>
  <xsd:attribute name="top" type="xsd:int" use="optional"/>
  <xsd:attribute name="left" type="xsd:int" use="optional"/>
  <xsd:attribute name="right" type="xsd:int" use="optional"/>
  <xsd:attribute name="width" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="height" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="position" type="ST_SurveyPosition" use="optional"/>
</xsd:complexType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.147 CT_Ref

Target namespace: <http://schemas.microsoft.com/office/excel/2006/main>

Referenced by: [ref](#)

CT_Ref is a complex type that extends **ST_Ref** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.62) specifies a rectangular range.

Attributes:

edited: A boolean attribute that specifies that at least one cell in this range has been edited by an application version that is unable to read one or more ancestor records.

adjusted: A boolean attribute that specifies whether this range has been adjusted by an application version that is unable to read one or more ancestor records.

adjust: A boolean attribute that specifies whether application versions that are unable to read one or more ancestor records should adjust this range if the contents of the cells that this range refers to are changed. MUST be TRUE if **adjusted** is TRUE.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Ref">
  <xsd:simpleContent>
    <xsd:extension base="ST_Ref">
      <xsd:attribute name="edited" type="xsd:boolean" use="optional"/>
      <xsd:attribute name="adjusted" type="xsd:boolean" use="optional"/>
      <xsd:attribute name="adjust" type="xsd:boolean" use="optional"/>
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.148 CT_Sqref

Target namespace: <http://schemas.microsoft.com/office/excel/2006/main>

Referenced by: [sqref](#), [CT_ConditionalFormatting](#), [CT_DataValidation](#), [CT_Sparkline](#), [CT_IgnoredError](#), [CT_ProtectedRange](#)

CT_Sqref is a complex type that extends **ST_Sqref** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.76) specifies a range.

Attributes:

edited: A boolean attribute that specifies that at least one cell in this range has been edited by an application version that is unable to read one or more ancestor records.

split: A boolean attribute that specifies that this range has been split.

adjusted: A boolean attribute that specifies whether this range has been adjusted by an application version that is unable to read one or more ancestor records.

adjust: A boolean attribute that specifies whether application versions that are unable to read one or more ancestor records should adjust this range if the contents of the cells that this range refers to are changed. MUST be TRUE if **adjusted** is TRUE.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Sqref">
  <xsd:simpleContent>
    <xsd:extension base="ST_Sqref">
      <xsd:attribute name="edited" type="xsd:boolean" use="optional"/>
      <xsd:attribute name="split" type="xsd:boolean" use="optional"/>
      <xsd:attribute name="adjusted" type="xsd:boolean" use="optional"/>
      <xsd:attribute name="adjust" type="xsd:boolean" use="optional"/>
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.149 CT_ApplicationNonVisualDrawingProps

Target namespace: <http://schemas.microsoft.com/office/excel/2010/spreadsheetDrawing>

Referenced by: [CT_ContentPart](#)

Non-visual ContentPart properties.

Attributes:

macro: A string attribute that specifies

This contains XL macro string.

fPublished: A Boolean attribute that specifies

Flag to determine whether the shape will be published on XL server.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ApplicationNonVisualDrawingProps">
  <xsd:attribute name="macro" type="xsd:string" use="optional"/>
  <xsd:attribute name="fPublished" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
```

See section [5.8](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.150 CT_CacheSourceExt

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Extended description of the data source whose data is stored in the pivot cache

Child Elements:

sourceConnection: A [CT_SourceConnection](#) element that specifies the source connection of the pivot cache

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_CacheSourceExt">
  <xsd:sequence>
    <xsd:element ref="sourceConnection" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.151 CT_ContentPart

Target namespace: <http://schemas.microsoft.com/office/excel/2010/spreadsheetDrawing>

Referenced by: [contentPart](#)

A single ContentPart.

Child Elements:

nvContentPartPr: A [CT_ContentPartNonVisual](#) element that specifies

nvPr: A [CT_ApplicationNonVisualDrawingProps](#) element that specifies

xfrm: A CT_Transform2D element that specifies

extLst: A CT_OfficeArtExtensionList element that specifies

Attributes:

r:id: An ST_RelationshipId attribute that specifies

bwMode: An ST_BlackWhiteMode attribute that specifies

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ContentPart">
  <xsd:sequence>
    <xsd:element name="nvContentPartPr" type="CT_ContentPartNonVisual" minOccurs="0"
maxOccurs="1"/>
    <xsd:element name="nvPr" type="CT_ApplicationNonVisualDrawingProps" minOccurs="0"
maxOccurs="1"/>
    <xsd:element name="xfirm" type="a:CT_Transform2D" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" type="a:CT_OfficeArtExtensionList" minOccurs="0"
maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute ref="r:id" use="required"/>
  <xsd:attribute name="bwMode" type="a:ST_BlackWhiteMode" use="optional" default="auto"/>
</xsd:complexType>
```

See section [5.8](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.6.152 CT_ContentPartNonVisual

Target namespace: <http://schemas.microsoft.com/office/excel/2010/spreadsheetDrawing>

Referenced by: [CT_ContentPart](#)

Non-visual ContentPart properties.

Child Elements:

cNvPr: A CT_NonVisualDrawingProps element that specifies

cNvContentPartPr: A CT_NonVisualInkContentPartProperties element that specifies

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_ContentPartNonVisual">
  <xsd:sequence>
    <xsd:element name="cNvPr" type="a:CT_NonVisualDrawingProps" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="cNvContentPartPr" type="a14:CT_NonVisualInkContentPartProperties"
minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

See section [5.8](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7 Simple Types

2.7.1 ST_Ref

Target namespace: <http://schemas.microsoft.com/office/excel/2006/main>

Referenced by: [CT_Ref](#), [ST_Sqref](#)

This simple type specifies a reference to a range of cells.

This simple type is identical to the **ST_Ref** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.62) simple type with the following exception: This simple type MUST have the following grammar.

(A1-cell [":" A1-cell]) / ref-constant

The ABNF ([\[RFC5234\]](#)) definitions for A1-cell and ref-constant are specified in [Formulas](#).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_Ref">
  <xsd:restriction base="xsd:string"/>
</xsd:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.2 ST_Sqref

Target namespace: <http://schemas.microsoft.com/office/excel/2006/main>

Referenced by: [CT_Sqref](#)

This simple type specifies a list of cell ranges.

This simple type is identical to the **ST_Sqref** ([\[ISO/IEC29500-1:2011\]](#) section 18.18.76) simple type with the following exceptions:

- MUST contain zero or more values of type [ST_Ref](#).
- If the value contains an ST_Ref of value "#REF!", then it MUST be the only value in the list.
- The number of cell references in this simple type MUST be less than 2,147,483,647.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_Sqref">
  <xsd:list itemType="ST_Ref"/>
</xsd:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.3 ST_DisplanksAs

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SparklineGroup](#)

This simple type specifies how empty cells are plotted for all sparklines in the sparkline group.

Value	Meaning
span	Empty cells are plotted as interpolated.
gap	Empty cells are not plotted.

Value	Meaning
zero	Empty cells are plotted as zero.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_DisbBlanksAs">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="span"/>
    <xsd:enumeration value="gap"/>
    <xsd:enumeration value="zero"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.4 ST_SparklineAxisMinMax

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SparklineGroup](#)

This simple type specifies information about how the vertical axis minimum or maximum is computed for this sparkline group.

Value	Meaning
individual	Specifies that the vertical axis minimum or maximum for each sparkline in this sparkline group is calculated automatically such that the data point (2) with the minimum or maximum value can be displayed in the plot area .
group	Specifies that the vertical axis minimum or maximum is shared across all sparklines in this sparkline group and is calculated automatically such that the data point (2) with the minimum or maximum value can be displayed in the plot area.
custom	Specifies that the vertical axis minimum or maximum for each sparkline in this sparkline group is specified by the manualMin attribute or the manualMax attribute of CT_SparklineGroup .

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_SparklineAxisMinMax">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="individual"/>
    <xsd:enumeration value="group"/>
    <xsd:enumeration value="custom"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.5 ST_SparklineType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SparklineGroup](#)

This simple type specifies the type of the sparkline group.

Value	Meaning
line	Line sparklines.
column	Column (2) sparklines.
stacked	100% stacked column (2) sparklines.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_SparklineType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="line"/>
    <xsd:enumeration value="column"/>
    <xsd:enumeration value="stacked"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.6 ST_PivotShowAs

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_DataField](#)

This simple type specifies the display format values for a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) field (1).

Value	Meaning
percentOfParent	Percentage of parent total.
percentOfParentRow	Percentage of parent row (2) total.
percentOfParentCol	Percentage of parent column (2) total.
percentOfRunningTotal	Percentage of running total.
rankAscending	Rank ascending.
rankDescending	Rank descending.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_PivotShowAs">
```

```

<xsd:restriction base="xsd:string">
  <xsd:enumeration value="percentOfParent"/>
  <xsd:enumeration value="percentOfParentRow"/>
  <xsd:enumeration value="percentOfParentCol"/>
  <xsd:enumeration value="percentOfRunningTotal"/>
  <xsd:enumeration value="rankAscending"/>
  <xsd:enumeration value="rankDescending"/>
</xsd:restriction>
</xsd:simpleType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.7 ST_DataBarDirection

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_DataBar](#)

A simple type that specifies the direction of the data bar.

Value	Meaning
context	The direction of the data bar is determined by context.
leftToRight	The data bar is displayed in a left-to-right manner.
rightToLeft	The data bar is displayed in a right-to-left manner.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xsd:simpleType name="ST_DataBarDirection">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="context"/>
    <xsd:enumeration value="leftToRight"/>
    <xsd:enumeration value="rightToLeft"/>
  </xsd:restriction>
</xsd:simpleType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.8 ST_DataBarAxisPosition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_DataBar](#)

A simple type that specifies the axis position for the data bar.

Value	Meaning
automatic	The axis position for the data bar is calculated automatically.
middle	The axis position for the data bar is the midpoint of the cell.

Value	Meaning
none	There is no axis for the data bar.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_DataBarAxisPosition">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="automatic"/>
    <xsd:enumeration value="middle"/>
    <xsd:enumeration value="none"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.9 ST_CfvoType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_Cfvo](#)

This simple type specifies how the Conditional Formatting Value Object (CFVO) value is determined. In the following table, X represents a parameter value. The value of X is determined by the value of the **f** element in the parent CT_Cfvo element. If the **f** element in the parent CT_Cfvo element is absent, then the value of X is 0. MUST be a value from the following table.

Value	Meaning
num	X
percent	The minimum value in the range of cells that the conditional formatting rule applies to plus X percent of the difference between the maximum and minimum values in the range of cells that the conditional formatting rule applies to. For example, if the min and max values in the range are 1 and 10 respectively, and X is 10, then the CFVO value is 1.9.
max	The maximum value from the range of cells that the conditional formatting rule applies to.
min	The minimum value from the range of cells that the conditional formatting rule applies to.
formula	X, or if the f element is formed by the numerical-constant rule alone in the grammar provided in Formulas , the formula is ignored and X is 0.
percentile	The minimum value of the cell that is in the X percentile of the range of cells that the conditional formatting rule applies to.
autoMin	The smaller of zero or the minimum value from the range of cells that the conditional formatting rule applies to.
autoMax	The larger of zero or the maximum value from the range of cells that the conditional formatting rule applies to.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xsd:simpleType name="ST_CfvoType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="num"/>
    <xsd:enumeration value="percent"/>
    <xsd:enumeration value="max"/>
    <xsd:enumeration value="min"/>
    <xsd:enumeration value="formula"/>
    <xsd:enumeration value="percentile"/>
    <xsd:enumeration value="autoMin"/>
    <xsd:enumeration value="autoMax"/>
  </xsd:restriction>
</xsd:simpleType>

```











See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).











2.7.10 ST_IconSetType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_IconFilter](#), [CT_SortCondition](#), [CT_IconSet](#), [CT_CfIcon](#)

A simple type that specifies an icon set.

Value	Meaning
3Arrows	
3ArrowsGray	
3Flags	
3TrafficLights1	
3TrafficLights2	
3Signs	
3Symbols	
3Symbols2	
4Arrows	
4ArrowsGray	

Value	Meaning
4RedToBlack	
4Rating	
4TrafficLights	
5Arrows	
5ArrowsGray	
5Rating	
5Quarters	
3Stars	
3Triangles	
5Boxes	
NoIcons	No icon set

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xsd:simpleType name="ST_IconSetType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="3Arrows"/>
    <xsd:enumeration value="3ArrowsGray"/>
    <xsd:enumeration value="3Flags"/>
    <xsd:enumeration value="3TrafficLights1"/>
    <xsd:enumeration value="3TrafficLights2"/>
    <xsd:enumeration value="3Signs"/>
    <xsd:enumeration value="3Symbols"/>
    <xsd:enumeration value="3Symbols2"/>
    <xsd:enumeration value="4Arrows"/>
    <xsd:enumeration value="4ArrowsGray"/>
    <xsd:enumeration value="4RedToBlack"/>
    <xsd:enumeration value="4Rating"/>
    <xsd:enumeration value="4TrafficLights"/>
    <xsd:enumeration value="5Arrows"/>
    <xsd:enumeration value="5ArrowsGray"/>
  </xsd:restriction>
</xsd:simpleType>

```



```

    <xsd:enumeration value="5Rating"/>
    <xsd:enumeration value="5Quarters"/>
    <xsd:enumeration value="3Stars"/>
    <xsd:enumeration value="3Triangles"/>
    <xsd:enumeration value="5Boxes"/>
    <xsd:enumeration value="NoIcons"/>
  </xsd:restriction>
</xsd:simpleType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.11 ST_PivotEditValueType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotEditValue](#)

A simple type that specifies the type of the modified value in the PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) data area using [PivotTable what-if analysis](#).

Value	Meaning
number	Numerical value
dateTime	Date and time value
string	String value
boolean	Boolean value
error	Error value

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xsd:simpleType name="ST_PivotEditValueType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="number"/>
    <xsd:enumeration value="dateTime"/>
    <xsd:enumeration value="string"/>
    <xsd:enumeration value="boolean"/>
    <xsd:enumeration value="error"/>
  </xsd:restriction>
</xsd:simpleType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.12 ST_AllocationMethod

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_PivotTableDefinition](#), [CT_PivotChange](#)

A simple type that specifies the method of allocation for [PivotTable what-if analysis](#).

Value	Meaning
equalAllocation	Equal allocation
equalIncrement	Equal increment
weightedAllocation	Weighted allocation
weightedIncrement	Weighted increment

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_AllocationMethod">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="equalAllocation"/>
    <xsd:enumeration value="equalIncrement"/>
    <xsd:enumeration value="weightedAllocation"/>
    <xsd:enumeration value="weightedIncrement"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.13 ST_SlicerStyleType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_SlicerStyleElement](#)

A simple type that specifies the types of table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) elements that are specific to [slicers](#). The possible values are listed in the following table.

Value	Meaning
unselectedItemWithData	A slicer item with data that is not selected. Used for slicers only.
selectedItemWithData	A selected slicer item with data. Used for slicers only.
unselectedItemWithNoData	A slicer item with no data that is not selected. Used for slicers only.
selectedItemWithNoData	A selected slicer item with no data. Used for slicers only.
hoveredUnselectedItemWithData	A slicer item with data that is not selected and over which the mouse is paused on. Used for slicers only.
hoveredSelectedItemWithData	A selected slicer item with data and over which the mouse is paused on. Used for slicers only.
hoveredUnselectedItemWithNoData	A slicer item with no data that is not selected and over which the mouse is paused on. Used for slicers only.
hoveredSelectedItemWithNoData	A selected slicer item with no data and over which the mouse is paused on. Used for slicers only.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xsd:simpleType name="ST_SlicerStyleType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="unselectedItemWithData"/>
    <xsd:enumeration value="selectedItemWithData"/>
    <xsd:enumeration value="unselectedItemWithNoData"/>
    <xsd:enumeration value="selectedItemWithNoData"/>
    <xsd:enumeration value="hoveredUnselectedItemWithData"/>
    <xsd:enumeration value="hoveredSelectedItemWithData"/>
    <xsd:enumeration value="hoveredUnselectedItemWithNoData"/>
    <xsd:enumeration value="hoveredSelectedItemWithNoData"/>
  </xsd:restriction>
</xsd:simpleType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.14 ST_ObjectType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_FormControlPr](#)

A simple type that specifies the types of form control objects. The possible values are included in the following table.

Value	Meaning
Button	Button control
CheckBox	Check-box control
Drop	Drop-down (combo box) control
GBox	Group box control; this control is used for grouping radio button form controls
Label	Label control
List	List box control
Radio	Radio button control
Scroll	Scroll bar control
Spin	Spin box control
EditBox	Edit box control
Dialog	Dialog control

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xsd:simpleType name="ST_ObjectType">
  <xsd:restriction base="xsd:token">
    <xsd:enumeration value="Button"/>
    <xsd:enumeration value="CheckBox"/>
    <xsd:enumeration value="Drop"/>
    <xsd:enumeration value="GBox"/>
  </xsd:restriction>
</xsd:simpleType>

```

```

    <xsd:enumeration value="Label"/>
    <xsd:enumeration value="List"/>
    <xsd:enumeration value="Radio"/>
    <xsd:enumeration value="Scroll"/>
    <xsd:enumeration value="Spin"/>
    <xsd:enumeration value="EditBox"/>
    <xsd:enumeration value="Dialog"/>
  </xsd:restriction>
</xsd:simpleType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.15 ST_Checked

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_FormControlPr](#)

A simple type that specifies if a check box is selected or if the radio button is selected.

Value	Meaning
Unchecked	Object is unchecked or unselected.
Checked	Object is checked or selected.
Mixed	Mixed selection. Applies only to check boxes. The application can determine whether to consider this option as a check box that is not initialized and it is neither selected nor cleared.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xsd:simpleType name="ST_Checked">
  <xsd:restriction base="xsd:token">
    <xsd:enumeration value="Unchecked"/>
    <xsd:enumeration value="Checked"/>
    <xsd:enumeration value="Mixed"/>
  </xsd:restriction>
</xsd:simpleType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.16 ST_DropStyle

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_FormControlPr](#)

This simple type specifies the style of a drop-down form control. The allowed values are included in the following table.

Value	Meaning
combo	Standard combo box.

Value	Meaning
comboedit	Editable combo box<24>.
simple	Standard combo box with only the drop-down button visible when the box is not expanded.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_DropStyle">
  <xsd:restriction base="xsd:token">
    <xsd:enumeration value="combo"/>
    <xsd:enumeration value="comboedit"/>
    <xsd:enumeration value="simple"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.17 ST_SelType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_FormControlPr](#)

A simple type that specifies the selection type for the list box form control object. The allowed values are included in the following table.

Value	Meaning
single	Only single selection is allowed.
multi	Multiple selection is allowed. Clicking any item on the list will add it to the selection or, if already selected, will remove it from the selection.
extended	Multiple selection is allowed while the CTRL key is pressed.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_SelType">
  <xsd:restriction base="xsd:token">
    <xsd:enumeration value="single"/>
    <xsd:enumeration value="multi"/>
    <xsd:enumeration value="extended"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.18 ST_EditValidation

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_FormControlPr](#)

This simple type specifies the type of validation used for data input to the control. If omitted, the value is assumed to be text. If present, the application can proceed to validate the data accordingly. The valid values are included in the following table.

Value	Meaning
text	Edit box contains text.
integer	Edit box contains an integer.
number	Edit box contains a number.
reference	Edit box contains a cell reference ([ISO/IEC29500-1:2011] section 18.17.2.3).
formula	Edit box contains a spreadsheet formula ([ISO/IEC29500-1:2011] section 18.17).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_EditValidation">
  <xsd:restriction base="xsd:token">
    <xsd:enumeration value="text"/>
    <xsd:enumeration value="integer"/>
    <xsd:enumeration value="number"/>
    <xsd:enumeration value="reference"/>
    <xsd:enumeration value="formula"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.19 ST_OlapSlicerCacheSortOrder

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_OlapSlicerCacheLevelData](#)

A simple type that specifies how the [OLAP slicer items](#) are sorted in the [slicer view](#).

Value	Meaning
natural	The OLAP slicer items are sorted in original order as determined by the OLAP slicer source data .
ascending	The OLAP slicer items are sorted in ascending alphabetical order.
descending	The OLAP slicer items are sorted in descending alphabetical order.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_OlapSlicerCacheSortOrder">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="natural"/>
    <xsd:enumeration value="ascending"/>
    <xsd:enumeration value="descending"/>
  </xsd:restriction>
</xsd:simpleType>
```

```

</xsd:restriction>
</xsd:simpleType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.20 ST_TabularSlicerCacheSortOrder

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_TableSlicerCache](#), [CT_TabularSlicerCache](#)

A simple type that specifies how the [non-OLAP slicer items](#) are sorted in the [slicer view](#).

Value	Meaning
ascending	The non-OLAP slicer items are sorted in ascending alphabetical order.
descending	The non-OLAP slicer items are sorted in descending alphabetical order.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xsd:simpleType name="ST_TabularSlicerCacheSortOrder">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="ascending"/>
    <xsd:enumeration value="descending"/>
  </xsd:restriction>
</xsd:simpleType>

```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.21 ST_SlicerCacheCrossFilter

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_TableSlicerCache](#), [CT_OlapSlicerCacheLevelData](#), [CT_TabularSlicerCache](#)

A simple type that specifies how the [slicer items](#) that are used in [slicer cross filtering](#) are displayed.

Value	Meaning
none	The table style ([ISO/IEC29500-1:2011] section 18.8) element of the slicer style for slicer items with no data is not applied to slicer items with no data, and slicer items with no data are not sorted separately in the list of slicer items in the slicer view .
showItemsWithDataAtTop	The table style ([ISO/IEC29500-1:2011] section 18.8) element of the slicer style for slicer items with no data is applied to slicer items with no data, and slicer items with no data are sorted at the bottom in the list of slicer items in the slicer view.
showItemsWithNoData	The table style ([ISO/IEC29500-1:2011] section 18.8) element of the slicer style for slicer items with no data is applied to slicer items with no data, and slicer items with no data are not sorted separately in the list of slicer items in the slicer view.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_SlicerCacheCrossFilter">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="none"/>
    <xsd:enumeration value="showItemsWithDataAtTop"/>
    <xsd:enumeration value="showItemsWithNoData"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.22 ST_TextHAlign

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_FormControlPr](#)

A simple type that specifies the vertical text alignment for the object. The valid values are included in the following table.

Value	Meaning
left	Left alignment
center	Center alignment
right	Right alignment
justify	Justify alignment
distributed	Distributed alignment

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_TextHAlign">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="left"/>
    <xsd:enumeration value="center"/>
    <xsd:enumeration value="right"/>
    <xsd:enumeration value="justify"/>
    <xsd:enumeration value="distributed"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.23 ST_TextVAlign

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main>

Referenced by: [CT_FormControlPr](#)

A simple type that specifies the vertical text alignment for the object. The valid values are included in the following table.

Value	Meaning
top	Top alignment
center	Center alignment
bottom	Bottom alignment
justify	Justify alignment
distributed	Distributed alignment

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_TextVAlign">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="top"/>
    <xsd:enumeration value="center"/>
    <xsd:enumeration value="bottom"/>
    <xsd:enumeration value="justify"/>
    <xsd:enumeration value="distributed"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.4](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.24 ST_TimelineStyleType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_TimelineStyleElement](#)

A simple type that specifies the types of table style ([\[ISO/IEC29500-1:2011\]](#) section 18.8) elements that are specific to [Timelines](#). The possible values are listed in the following table.

Value	Meaning
selectionLabel	Timeline style element that applies to the selection label which is the label that indicates the period that has been selected on the Timeline. Used for Timelines only.
timeLevel	Timeline style element that applies to the time level which is the label that indicates the time granularity of the Timeline. Used for Timelines only.
periodLabel1	Timeline style element that applies to the upper row (2) of the time block labels. Used for Timelines only.
periodLabel2	Timeline style element that applies to the lower row (2) of the time block labels. Used for Timelines only.
selectedTimeBlock	Timeline style element that applies to the selected time blocks which are the segments on the Timeline that have been selected by the user. Used for Timelines only.

Value	Meaning
unselectedTimeBlock	Timeline style element that applies to the unselected time blocks which are the segments on the Timeline that have not been selected by the user. Used for Timelines only.
selectedTimeBlockSpace	Timeline style element that applies to the area between any two selected time blocks. Used for Timelines only.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_TimelineStyleType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="selectionLabel"/>
    <xsd:enumeration value="timeLevel"/>
    <xsd:enumeration value="periodLabel1"/>
    <xsd:enumeration value="periodLabel2"/>
    <xsd:enumeration value="selectedTimeBlock"/>
    <xsd:enumeration value="unselectedTimeBlock"/>
    <xsd:enumeration value="selectedTimeBlockSpace"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.25 ST_CalcMemNumberFormat

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_CalculatedMember](#)

An enumeration that specifies the display format for a CT_CalculatedMember.

Value	Meaning
default	Specifies that the number will be displayed using its current format.
number	Specifies that the number will be displayed using a comma as a thousands separator.
percent	Specifies that the number will be displayed as a percentage with two decimal places.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_CalcMemNumberFormat">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="default"/>
    <xsd:enumeration value="number"/>
    <xsd:enumeration value="percent"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.26 ST_SXVCellType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_PivotValueCell](#)

A simple type that specifies the type of a [PivotValueCell](#) element of a PivotTable ([\[ISO/IEC29500-1:2011\]](#) section 18.10) that is specified by a [pivotTableReference](#) element in the extension of a workbook.

Value	Meaning
b	The child element v of the CT_PivotValueCell. MUST be interpreted as a Boolean value. MUST be true or false.
n	The child element v of the CT_PivotValueCell. MUST be interpreted as a numeric value.
e	The child element v of the CT_PivotValueCell. MUST be interpreted as an error value. MUST be one of the following: <ul style="list-style-type: none">▪ #DIV/0!▪ #VALUE!▪ #NUM!▪ #N/A▪ #GETTING_DATA
str	The child element v of the CT_PivotValueCell. MUST be interpreted as a string value. The string MUST be less than or equal to 65,535 characters in length.
d	The child element v of the CT_PivotValueCell. MUST be interpreted as a dateTime ([XMLSCHEMA2] section 3.2.7) value.
bl	A blank cell. The child element v of the CT_PivotValueCell. MUST NOT have any value.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_SXVCellType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="b"/>
    <xsd:enumeration value="n"/>
    <xsd:enumeration value="e"/>
    <xsd:enumeration value="str"/>
    <xsd:enumeration value="d"/>
    <xsd:enumeration value="bl"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.27 ST_QuestionType

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_SurveyQuestion](#)

The **ST_QuestionType** simple type specifies the type of input for the answer to a survey question as specified by the **type** attribute of a **CT_SurveyQuestion** (section [2.6.145](#)).

Value	Meaning
checkBox	Answer is indicated via checkbox.
choice	Answer is selected from a list of choices.
date	Answer in the form of a date.
time	Answer in the form of a time.
multipleLinesOfText	Answer in the form of multiple lines of text.
number	Answer is numerical.
singleLineOfText	Answer in the form of a single line of text.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_QuestionType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="checkBox"/>
    <xsd:enumeration value="choice"/>
    <xsd:enumeration value="date"/>
    <xsd:enumeration value="time"/>
    <xsd:enumeration value="multipleLinesOfText"/>
    <xsd:enumeration value="number"/>
    <xsd:enumeration value="singleLineOfText"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.28 ST_QuestionFormat

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_SurveyQuestion](#)

The **ST_QuestionFormat** simple type specifies the text formatting of the input for the answer to a survey question as specified by the **format** attribute of a **CT_SurveyQuestion** (section [2.6.145](#)).

Value	Meaning
generalDate	Format answer as a date.
longDate	Format answer as a long form date.
shortDate	Format answer as a short form date.
longTime	Format answer as a long form time.

Value	Meaning
shortTime	Format answer as a short form time.
generalNumber	Format answer as a number.
standard	Format answer as a number with thousands separators.
fixed	Format answer as a number with a fixed number of digits after the decimal.
percent	Format answer as a percentage.
currency	Format answer as a currency.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_QuestionFormat">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="generalDate"/>
    <xsd:enumeration value="longDate"/>
    <xsd:enumeration value="shortDate"/>
    <xsd:enumeration value="longTime"/>
    <xsd:enumeration value="shortTime"/>
    <xsd:enumeration value="generalNumber"/>
    <xsd:enumeration value="standard"/>
    <xsd:enumeration value="fixed"/>
    <xsd:enumeration value="percent"/>
    <xsd:enumeration value="currency"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.7.29 ST_SurveyPosition

Target namespace: <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main>

Referenced by: [CT_SurveyElementPr](#)

The **ST_SurveyPosition** simple type specifies the type of positioning of an element in a survey, as specified by the **position** attribute of a **CT_SurveyElementPr** (section [2.6.146](#)). The types correspond to the allowed values for the position property of Cascading Style Sheets 2.1, as defined in [\[CSS-Level2-2009\]](#).

Value	Meaning
absolute	Use absolute positioning.
fixed	Use fixed positioning.
relative	Use relative positioning.
static	Use static positioning.
inherit	Use inherit positioning.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_SurveyPosition">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="absolute"/>
    <xsd:enumeration value="fixed"/>
    <xsd:enumeration value="relative"/>
    <xsd:enumeration value="static"/>
    <xsd:enumeration value="inherit"/>
  </xsd:restriction>
</xsd:simpleType>
```

See section [5.3](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

3 Structure Examples

This section contains examples of some of the most commonly used data structures in Excel Binary File Format files. The examples are meant to be a starting point for an implementer learning the file format. They are not meant to cover all records in the file format.

In the following sections, the schema definition might differ from the processing rules imposed by the application. The XSD in this specification provides a base description of the file format. The text that introduces the XSD specifies additional restrictions that reflect actual Microsoft product behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the application as specified restricts the same elements to being non-empty, not null, and present.

3.1 Slicer

This example shows a [slicer](#) attached to a native PivotTable and its associated [slicer cache](#). The PivotTable has the "State" and "City" fields (1) added to the row (2) area and the "Population" field (1) added to the data area. The slicer is based on the "State" field (1), and is currently filtering on "Washington".

The following figure shows a possible implementation of the slicer discussed in this example.




Figure 1: PivotTable and slicer

The following figure shows that the source data for the PivotTable that the slicer discussed in this example is filtering, as depicted on a possible implementation of a worksheet.

	A	B	C
1	State	City	Population
2	Washington	Seattle	594210
3	Washington	Spokane	200975
4	Washington	Bellevue	121347
5	Oregon	Portland	550396
6	Oregon	Springfield	56666

Figure 2: Source data for the PivotTable

This example includes the entire slicer cache and [slicer](#) parts that are used in the specification of a non-OLAP slicer.

The `<i>` elements inside the `<items>` element specify the cached [non-OLAP slicer items](#). "Washington" and "Oregon" are the cached non-OLAP slicer items in this example.

3.1.1 Slicer Cache Part

The following is an example slicer cache part, as specified in section [2.1.4](#).

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<slicerCacheDefinition xmlns="http://schemas.microsoft.com/office/spreadsheetml/2009/9/main"
xmlns:mc="http://schemas.openxmlformats.org/markup-compatibility/2006" mc:Ignorable="x"
xmlns:x="http://schemas.openxmlformats.org/spreadsheetml/2006/main" name="Slicer_State"
sourceName="State">
  <pivotTables>
    <pivotTable tabId="1" name="PivotTable1"/>
  </pivotTables>
  <data>
    <tabular pivotCacheId="5">
      <items count="2">
        <i x="1"/>
        <i x="0" s="1"/>
      </items>
    </tabular>
  </data>
</slicerCacheDefinition>
```

The following table describes the **slicerCacheDefinition** element used in this example.

Attribute name	Value	Notes
name	Slicer_State	This is the name of the slicer cache.
sourceName	State	This is the name of the associated slicer, as specified in section 2.1.5 .

The following table describes the **pivotTable** element used in this example.

Attribute name	Value	Notes
tabId	1	This indicates that the associated PivotTable, as specified in ISO/IEC29500-1:2011 section 18.10, is located on the first sheet (1).

Attribute name	Value	Notes
name	PivotTable1	This is the name of the associated PivotTable.

The following table describes the **tabular** element used in this example.

Attribute name	Value	Notes
pivotCacheId	5	This indicates that the identifier of the associated PivotTable PivotCache is "5".

The following table describes the **items** element used in this example.

Attribute name	Value	Notes
count	2	This indicates that there are two items in the slicer cache.

The following table describes the first i (item) element used in this example.

Attribute name	Value	Notes
x	1	This indicates that the first item in the slicer cache is the second item in the PivotTable PivotCache .

The following table describes the second i (item) element used in this example.

Attribute name	Value	Notes
x	0	This indicates that the second item in the slicer cache is the first item in the PivotTable PivotCache .
s	1	This indicates that this item is selected in the slicer.

3.1.2 Slicer Part

The following is an example slicer part, as specified in section [2.1.5](#).

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<slicers xmlns="http://schemas.microsoft.com/office/spreadsheetml/2009/9/main"
xmlns:mc="http://schemas.openxmlformats.org/markup-compatibility/2006" mc:Ignorable="x"
xmlns:x="http://schemas.openxmlformats.org/spreadsheetml/2006/main">
  <slicer name="State" cache="Slicer_State" caption="State" rowHeight="228600"/>
</slicers>
```

The following table describes the slicer element used in this example.

Attribute name	Value	Notes
name	State	This is the name of the slicer.

Attribute name	Value	Notes
cache	Slicer_State	This is the name of the slicer cache, as specified in section 2.1.4 .
caption	State	This is the caption displayed at the top of the slicer.
rowHeight	228600	This is the height of a row (2) in EMUs, equal to one-fourth of an inch.

4 Security Considerations

4.1 Security Considerations for Implementers

The password verifier features available in the file format are used to prevent accidental modification, rather than being used as security features. It is possible to remove the passwords by removing the records containing the verifier values.

The translation of passwords from a double-byte Unicode string to a new character string in the ANSI code page of the current system converts any Unicode character that cannot be mapped to the ANSI code page of the current system to the 0x3F character in that code page, as described in [\[ISO/IEC29500-1:2011\]](#) section 18.2.29. Replacing these characters with "0x3F" when the hash is verified will generate positive hash value matches. In certain **locales**, this can be a significant portion of the everyday **character set (1)**.

Further security considerations regarding the file encryption algorithms are described in [\[MS-OFFCRYPTO\]](#) section [4.3](#).

4.2 Index of Security Fields

None.

5 Appendix A: Full XML Schema

For ease of implementation, this section provides the full W3C XML schemas for the new elements, attributes, complex types, and simple types specified in the earlier sections. Any schema references to namespaces included in Office Open XML file formats as described in [\[ISO/IEC29500:2011\]](#) refer specifically to the transitional schemas as described in [\[ISO/IEC29500-4:2011\]](#).

For ease of implementation, the following sections provide the full XML schema for this protocol.

Schema name	Prefix	Section
schemas.microsoft.com/office/excel/2006/main		section 5.1
schemas.microsoft.com/office/drawing/2010/slicer		section 5.2
schemas.microsoft.com/office/spreadsheetml/2010/11/main		section 5.3
schemas.microsoft.com/office/spreadsheetml/2009/9/main		section 5.4
schemas.microsoft.com/office/spreadsheetml/2009/9/ac		section 5.5
xl12AcSchemaUri		section 5.6
schemas.microsoft.com/office/drawing/2012/timeslicer		section 5.7

5.1 <http://schemas.microsoft.com/office/excel/2006/main> Schema

```
<xsd:schema xmlns="http://schemas.microsoft.com/office/excel/2006/main"
  elementFormDefault="qualified"
  targetNamespace="http://schemas.microsoft.com/office/excel/2006/main"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:x="http://schemas.openxmlformats.org/spreadsheetml/2006/main">
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
    schemaLocation="xlbasictypes.xsd"/>
  <xsd:simpleType name="ST_Ref">
    <xsd:restriction base="xsd:string"/>
  </xsd:simpleType>
  <xsd:complexType name="CT_Ref">
    <xsd:simpleContent>
      <xsd:extension base="ST_Ref">
        <xsd:attribute name="edited" type="xsd:boolean" use="optional"/>
        <xsd:attribute name="adjusted" type="xsd:boolean" use="optional"/>
        <xsd:attribute name="adjust" type="xsd:boolean" use="optional"/>
      </xsd:extension>
    </xsd:simpleContent>
  </xsd:complexType>
  <xsd:simpleType name="ST_Sqref">
    <xsd:list itemType="ST_Ref"/>
  </xsd:simpleType>
  <xsd:complexType name="CT_Sqref">
    <xsd:simpleContent>
      <xsd:extension base="ST_Sqref">
        <xsd:attribute name="edited" type="xsd:boolean" use="optional"/>
        <xsd:attribute name="split" type="xsd:boolean" use="optional"/>
        <xsd:attribute name="adjusted" type="xsd:boolean" use="optional"/>
        <xsd:attribute name="adjust" type="xsd:boolean" use="optional"/>
      </xsd:extension>
    </xsd:simpleContent>
  </xsd:complexType>
</xsd:schema>
```

```

</xsd:complexType>
<xsd:element name="f" type="x:ST_Formula"/>
<xsd:element name="ref" type="CT_Ref"/>
<xsd:element name="sqref" type="CT_Sqref"/>
</xsd:schema>

```

5.2 <http://schemas.microsoft.com/office/drawing/2010/slicer> Schema

```

<xsd:schema elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/office/drawing/2010/slicer"
xmlns="http://schemas.microsoft.com/office/drawing/2010/slicer"
xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/main"
xmlns:a14="http://schemas.microsoft.com/office/drawing/2010/main"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <xsd:complexType name="CT_Slicer">
    <xsd:sequence>
      <xsd:element name="extLst" type="a:CT_OfficeArtExtensionList" minOccurs="0"
maxOccurs="1"/>
    </xsd:sequence>
    <xsd:attribute name="name" type="xsd:string" use="required"/>
  </xsd:complexType>
  <xsd:element name="slicer" type="CT_Slicer"/>
  <xsd:import namespace="http://schemas.microsoft.com/office/drawing/2010/main"
schemaLocation="oart14docprop.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/drawingml/2006/main"
schemaLocation="oartdocprop.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
schemaLocation="orel.xsd"/>
</xsd:schema>

```

5.3 <http://schemas.microsoft.com/office/spreadsheetml/2010/11/main> Schema

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:x14="http://schemas.microsoft.com/office/spreadsheetml/2009/9/main"
xmlns:x="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
xmlns="http://schemas.microsoft.com/office/spreadsheetml/2010/11/main"
targetNamespace="http://schemas.microsoft.com/office/spreadsheetml/2010/11/main"
elementFormDefault="qualified"
xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
xmlns:xm="http://schemas.microsoft.com/office/excel/2006/main">
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
schemaLocation="xlbasictypes.xsd"/>
  <xsd:import namespace="http://schemas.microsoft.com/office/spreadsheetml/2009/9/main"
schemaLocation="xlslicercache.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
schemaLocation="xlworkbook.xsd"/>
  <xsd:import namespace="http://schemas.microsoft.com/office/excel/2006/main"
schemaLocation="xlmbasictypes.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
schemaLocation="xlsheet.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
schemaLocation="orel.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
schemaLocation="xlpivot.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
schemaLocation="xlextconns.xsd"/>
  <xsd:element name="slicerCaches" type="x14:CT_SlicerCaches"/>
  <xsd:element name="tableSlicerCache" type="CT_TableSlicerCache"/>

```

```

<xsd:complexType name="CT_TableSlicerCache">
  <xsd:sequence>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="tableId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="column" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="sortOrder" type="x14:ST_TabularSlicerCacheSortOrder" use="optional"
default="ascending"/>
  <xsd:attribute name="customListSort" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="crossFilter" type="x14:ST_SlicerCacheCrossFilter" use="optional"
default="showItemsWithDataAtTop"/>
</xsd:complexType>
<xsd:element name="slicerCacheHideItemsWithNoData" type="CT_SlicerCacheHideNoData"/>
<xsd:complexType name="CT_SlicerCacheHideNoData">
  <xsd:sequence>
    <xsd:element name="slicerCacheOlapLevelName" type="CT_SlicerCacheOlapLevelName"
minOccurs="0" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional" default="0"/>
</xsd:complexType>
<xsd:complexType name="CT_SlicerCacheOlapLevelName">
  <xsd:attribute name="uniqueName" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
<xsd:element name="slicerCachePivotTables" type="x14:CT_SlicerCachePivotTables"/>
<xsd:element name="pivotCaches" type="x:CT_PivotCaches"/>
<xsd:element name="pivotTableReferences" type="CT_PivotTableReferences"/>
<xsd:complexType name="CT_PivotTableReferences">
  <xsd:sequence>
    <xsd:element name="pivotTableReference" type="CT_PivotTableReference" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_PivotTableReference">
  <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>
<xsd:element name="queryTable" type="CT_QueryTable"/>
<xsd:complexType name="CT_QueryTable">
  <xsd:attribute name="clipped" use="optional" default="false" type="xsd:boolean"/>
  <xsd:attribute name="sourceDataName" type="xsd:string" use="optional"/>
  <xsd:attribute name="drillThrough" use="optional" default="false" type="xsd:boolean"/>
</xsd:complexType>
<xsd:element name="webExtensions" type="CT_WebExtensions"/>
<xsd:complexType name="CT_WebExtensions">
  <xsd:sequence>
    <xsd:element name="webExtension" type="CT_WebExtension" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_WebExtension">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="appRef" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:element name="timelineCacheRefs" type="CT_TimelineCacheRefs"/>
<xsd:complexType name="CT_TimelineCacheRefs">
  <xsd:sequence>

```

```

        <xsd:element name="timelineCacheRef" type="CT_TimelineCacheRef" minOccurs="1"
maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_TimelineCacheRef">
    <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>
<xsd:element name="timelineRefs" type="CT_TimelineRefs"/>
<xsd:complexType name="CT_TimelineRefs">
    <xsd:sequence>
        <xsd:element name="timelineRef" type="CT_TimelineRef" minOccurs="1"
maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_TimelineRef">
    <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>
<xsd:element name="timelineCachePivotCaches" type="x:CT_PivotCaches"/>
<xsd:complexType name="CT_WorkbookPr">
    <xsd:attribute name="chartTrackingRefBase" type="xsd:boolean" default="false"/>
</xsd:complexType>
<xsd:element name="workbookPr" type="CT_WorkbookPr"/>
<xsd:element name="timelineStyles" type="CT_TimelineStyles"/>
<xsd:complexType name="CT_TimelineStyles">
    <xsd:sequence>
        <xsd:element name="timelineStyle" type="CT_TimelineStyle" minOccurs="0"
maxOccurs="unbounded"/>
    </xsd:sequence>
    <xsd:attribute name="defaultTimelineStyle" type="xsd:string" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_TimelineStyleElements">
    <xsd:sequence>
        <xsd:element name="timelineStyleElement" type="CT_TimelineStyleElement" minOccurs="1"
maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_TimelineStyle">
    <xsd:sequence>
        <xsd:element name="timelineStyleElements" type="CT_TimelineStyleElements" minOccurs="0"
maxOccurs="1"/>
    </xsd:sequence>
    <xsd:attribute name="name" type="xsd:string" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_TimelineStyleElement">
    <xsd:attribute name="type" type="ST_TimelineStyleType" use="required"/>
    <xsd:attribute name="dxfsId" type="x:ST_DxfsId" use="optional"/>
</xsd:complexType>
<xsd:simpleType name="ST_TimelineStyleType">
    <xsd:restriction base="xsd:string">
        <xsd:enumeration value="selectionLabel"/>
        <xsd:enumeration value="timeLevel"/>
        <xsd:enumeration value="periodLabel1"/>
        <xsd:enumeration value="periodLabel2"/>
        <xsd:enumeration value="selectedTimeBlock"/>
        <xsd:enumeration value="unselectedTimeBlock"/>
        <xsd:enumeration value="selectedTimeBlockSpace"/>
    </xsd:restriction>
</xsd:simpleType>
<xsd:element name="dxfs" type="x:CT_Dxfs"/>

```

```

<xsd:element name="connection" type="CT_Connection"/>
<xsd:complexType name="CT_ModelTextPr">
  <xsd:attribute name="headers" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_RangePr">
  <xsd:attribute name="sourceName" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
<xsd:complexType name="CT_DbTable">
  <xsd:attribute name="name" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
<xsd:complexType name="CT_DbTables">
  <xsd:sequence>
    <xsd:element name="dbTable" minOccurs="1" maxOccurs="unbounded" type="CT_DbTable"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_DbCommand">
  <xsd:attribute name="text" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
<xsd:complexType name="CT_OleDbPr">
  <xsd:choice minOccurs="1" maxOccurs="1">
    <xsd:element name="dbTables" type="CT_DbTables"/>
    <xsd:element name="dbCommand" type="CT_DbCommand"/>
  </xsd:choice>
  <xsd:attribute name="connection" use="optional" type="x:ST_Xstring"/>
</xsd:complexType>
<xsd:complexType name="CT_DataFeedPr">
  <xsd:sequence>
    <xsd:element name="dbTables" type="CT_DbTables" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="connection" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
<xsd:complexType name="CT_Connection">
  <xsd:sequence>
    <xsd:element name="textPr" minOccurs="0" maxOccurs="1" type="x:CT_TextPr"/>
    <xsd:element name="modelTextPr" minOccurs="0" maxOccurs="1" type="CT_ModelTextPr"/>
    <xsd:element name="rangePr" minOccurs="0" maxOccurs="1" type="CT_RangePr"/>
    <xsd:element name="oledbPr" minOccurs="0" maxOccurs="1" type="CT_OleDbPr"/>
    <xsd:element name="dataFeedPr" minOccurs="0" maxOccurs="1" type="CT_DataFeedPr"/>
  </xsd:sequence>
  <xsd:attribute name="id" use="required" type="x:ST_Xstring"/>
  <xsd:attribute name="model" type="xsd:boolean" default="false" use="optional"/>
  <xsd:attribute name="excludeFromRefreshAll" type="xsd:boolean" default="false"
use="optional"/>
  <xsd:attribute name="autoDelete" type="xsd:boolean" default="false" use="optional"/>
  <xsd:attribute name="usedByAddin" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
<xsd:simpleType name="ST_CalcMemNumberFormat">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="default"/>
    <xsd:enumeration value="number"/>
    <xsd:enumeration value="percent"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_CalculatedMemberExt">
  <xsd:sequence>
    <xsd:element ref="calculatedMember" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:element name="calculatedMember" type="CT_CalculatedMember"/>

```



```

<xsd:complexType name="CT_CalculatedMember">
  <xsd:attribute name="measureGroup" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="numberFormat" type="ST_CalcMemNumberFormat" use="optional"
default="default"/>
  <xsd:attribute name="measure" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:element name="pivotTableUISettings" type="CT_PivotTableUISettings"/>
<xsd:complexType name="CT_PivotTableUISettings">
  <xsd:sequence>
    <xsd:element name="activeTabTopLevelEntity" type="CT_FieldListActiveTabTopLevelEntity"
minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="sourceDataName" type="xsd:string" use="optional"/>
  <xsd:attribute name="relNeededHidden" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:complexType name="CT_FieldListActiveTabTopLevelEntity">
  <xsd:attribute name="name" use="required" type="xsd:string"/>
  <xsd:attribute name="type" use="optional" default="0" type="xsd:unsignedInt"/>
</xsd:complexType>
<xsd:element name="pivotFilter" type="CT_PivotFilter"/>
<xsd:complexType name="CT_PivotFilter">
  <xsd:attribute name="useWholeDay" type="xsd:boolean" use="required"/>
</xsd:complexType>
<xsd:element name="cachedUniqueNames" type="CT_CachedUniqueNames"/>
<xsd:complexType name="CT_CachedUniqueNames">
  <xsd:sequence>
    <xsd:element name="cachedUniqueName" minOccurs="1" maxOccurs="unbounded"
type="CT_CachedUniqueName"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_CachedUniqueName">
  <xsd:attribute name="index" use="required" type="xsd:unsignedInt"/>
  <xsd:attribute name="name" use="required" type="x:ST_Xstring"/>
</xsd:complexType>
<xsd:complexType name="CT_CacheHierarchy">
  <xsd:attribute name="aggregatedColumn" use="required" type="xsd:int"/>
</xsd:complexType>
<xsd:element name="cacheHierarchy" type="CT_CacheHierarchy"/>
<xsd:element name="timelinePivotCacheDefinition" type="CT_TimelinePivotCacheDefinition"/>
<xsd:complexType name="CT_TimelinePivotCacheDefinition">
  <xsd:attribute name="timelineData" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:element name="pivotCacheIdVersion" type="CT_PivotCacheIdVersion"/>
<xsd:complexType name="CT_PivotCacheIdVersion">
  <xsd:attribute name="cacheIdSupportedVersion" type="xsd:unsignedByte" use="required"/>
  <xsd:attribute name="cacheIdCreatedVersion" type="xsd:unsignedByte" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_ModelTable">
  <xsd:attribute name="id" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="connection" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_ModelTables">
  <xsd:sequence>
    <xsd:element name="modelTable" minOccurs="1" maxOccurs="unbounded"
type="CT_ModelTable"/>
  </xsd:sequence>
</xsd:complexType>

```

```

<xsd:complexType name="CT_ModelRelationship">
  <xsd:attribute name="fromTable" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="fromColumn" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="toTable" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="toColumn" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_ModelRelationships">
  <xsd:sequence>
    <xsd:element name="modelRelationship" minOccurs="1" maxOccurs="unbounded"
type="CT_ModelRelationship"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_DataModel">
  <xsd:sequence>
    <xsd:element name="modelTables" minOccurs="0" maxOccurs="1" type="CT_ModelTables"/>
    <xsd:element name="modelRelationships" minOccurs="0" maxOccurs="1"
type="CT_ModelRelationships"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="minVersionLoad" type="xsd:unsignedByte" use="optional" default="5"/>
</xsd:complexType>
<xsd:element name="dataModel" type="CT_DataModel"/>
<xsd:element name="pivotTableData" type="CT_PivotTableData"/>
<xsd:complexType name="CT_PivotTableData">
  <xsd:sequence>
    <xsd:element name="pivotRow" type="CT_PivotRow" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="rowCount" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="columnCount" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="cacheId" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_PivotRow">
  <xsd:sequence>
    <xsd:element name="c" type="CT_PivotValueCell" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="r" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_PivotValueCell">
  <xsd:sequence>
    <xsd:element name="v" type="x:ST_Xstring" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="x" type="CT_PivotValueCellExtra" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="i" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="t" type="ST_SXVCellType" use="optional" default="n"/>
</xsd:complexType>
<xsd:complexType name="CT_PivotValueCellExtra">
  <xsd:attribute name="in" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="bc" type="x:ST_UnsignedIntHex" use="optional"/>
  <xsd:attribute name="fc" type="x:ST_UnsignedIntHex" use="optional"/>
  <xsd:attribute name="i" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="un" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="st" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="b" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:simpleType name="ST_SXVCellType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="b"/>
    <xsd:enumeration value="n"/>
  </xsd:restriction>
</xsd:simpleType>

```

```

    <xsd:enumeration value="e"/>
    <xsd:enumeration value="str"/>
    <xsd:enumeration value="d"/>
    <xsd:enumeration value="bl"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_PivotTableServerFormats">
  <xsd:sequence>
    <xsd:element name="serverFormat" type="x:CT_ServerFormat" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" use="required" type="xsd:unsignedInt"/>
</xsd:complexType>
<xsd:element name="pivotCacheDecoupled" type="CT_PivotCacheDecoupled"/>
<xsd:complexType name="CT_PivotCacheDecoupled">
  <xsd:attribute name="decoupled" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:element name="dataField" type="CT_DataField"/>
<xsd:complexType name="CT_DataField">
  <xsd:attribute name="isCountDistinct" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:element name="survey" type="CT_Survey"/>
<xsd:complexType name="CT_Survey">
  <xsd:sequence>
    <xsd:element name="surveyPr" type="CT_SurveyElementPr" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="titlePr" type="CT_SurveyElementPr" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="descriptionPr" type="CT_SurveyElementPr" minOccurs="0"
maxOccurs="1"/>
    <xsd:element name="questions" type="CT_SurveyQuestions" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="id" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="guid" type="x:ST_Guid" use="required"/>
  <xsd:attribute name="title" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="description" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_SurveyQuestions">
  <xsd:sequence>
    <xsd:element name="questionsPr" type="CT_SurveyElementPr" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="question" type="CT_SurveyQuestion" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_SurveyQuestion">
  <xsd:sequence>
    <xsd:element name="questionPr" type="CT_SurveyElementPr" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="binding" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="text" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="type" type="ST_QuestionType" use="optional"/>
  <xsd:attribute name="format" type="ST_QuestionFormat" use="optional"/>
  <xsd:attribute name="helpText" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="required" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="defaultValue" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="decimalPlaces" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="rowSource" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_SurveyElementPr">

```

```

<xsd:sequence>
  <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
</xsd:sequence>
<xsd:attribute name="cssClass" type="x:ST_Xstring" use="optional"/>
<xsd:attribute name="bottom" type="xsd:int" use="optional"/>
<xsd:attribute name="top" type="xsd:int" use="optional"/>
<xsd:attribute name="left" type="xsd:int" use="optional"/>
<xsd:attribute name="right" type="xsd:int" use="optional"/>
<xsd:attribute name="width" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="height" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="position" type="ST_SurveyPosition" use="optional"/>
</xsd:complexType>
<xsd:simpleType name="ST_QuestionType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="checkBox"/>
    <xsd:enumeration value="choice"/>
    <xsd:enumeration value="date"/>
    <xsd:enumeration value="time"/>
    <xsd:enumeration value="multipleLinesOfText"/>
    <xsd:enumeration value="number"/>
    <xsd:enumeration value="singleLineOfText"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_QuestionFormat">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="generalDate"/>
    <xsd:enumeration value="longDate"/>
    <xsd:enumeration value="shortDate"/>
    <xsd:enumeration value="longTime"/>
    <xsd:enumeration value="shortTime"/>
    <xsd:enumeration value="generalNumber"/>
    <xsd:enumeration value="standard"/>
    <xsd:enumeration value="fixed"/>
    <xsd:enumeration value="percent"/>
    <xsd:enumeration value="currency"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_SurveyPosition">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="absolute"/>
    <xsd:enumeration value="fixed"/>
    <xsd:enumeration value="relative"/>
    <xsd:enumeration value="static"/>
    <xsd:enumeration value="inherit"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:element name="timelines" type="CT_Timelines"/>
<xsd:complexType name="CT_Timelines">
  <xsd:sequence>
    <xsd:element name="timeline" type="CT_Timeline" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_Timeline">
  <xsd:sequence>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="cache" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="caption" type="x:ST_Xstring" use="optional"/>

```

```

    <xsd:attribute name="showHeader" type="xsd:boolean" use="optional" default="true"/>
    <xsd:attribute name="showSelectionLabel" type="xsd:boolean" use="optional"
default="true"/>
    <xsd:attribute name="showTimeLevel" type="xsd:boolean" use="optional" default="true"/>
    <xsd:attribute name="showHorizontalScrollbar" type="xsd:boolean" use="optional"
default="true"/>
    <xsd:attribute name="level" type="xsd:unsignedInt" use="required"/>
    <xsd:attribute name="selectionLevel" type="xsd:unsignedInt" use="required"/>
    <xsd:attribute name="scrollPosition" type="xsd:dateTime" use="optional"/>
    <xsd:attribute name="style" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:element name="timelineCacheDefinition" type="CT_TimelineCacheDefinition"/>
<xsd:complexType name="CT_TimelineCacheDefinition">
  <xsd:sequence>
    <xsd:element name="pivotTables" type="CT_TimelineCachePivotTables" minOccurs="0"
maxOccurs="1"/>
    <xsd:element name="state" type="CT_TimelineState" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="timelinePivotFilter" minOccurs="0" maxOccurs="1"
type="CT_TimelinePivotFilter"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="sourceName" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_TimelineCachePivotTables">
  <xsd:sequence>
    <xsd:element name="pivotTable" type="CT_TimelineCachePivotTable" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_TimelineCachePivotTable">
  <xsd:attribute name="tabId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_TimelineRange">
  <xsd:attribute name="startDate" type="xsd:dateTime" use="required"/>
  <xsd:attribute name="endDate" type="xsd:dateTime" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_TimelineState">
  <xsd:sequence>
    <xsd:element name="selection" type="CT_TimelineRange" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="bounds" type="CT_TimelineRange" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="singleRangeFilterState" type="xsd:boolean" use="optional"
default="true"/>
  <xsd:attribute name="minimalRefreshVersion" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="lastRefreshVersion" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="pivotCacheId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="filterType" use="required" type="x:ST_PivotFilterType"/>
</xsd:complexType>
<xsd:complexType name="CT_TimelinePivotFilter">
  <xsd:sequence>
    <xsd:element name="autoFilter" minOccurs="0" maxOccurs="1" type="x:CT_AutoFilter"/>
  </xsd:sequence>
  <xsd:attribute name="useWholeDay" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="fld" use="required" type="xsd:unsignedInt"/>
  <xsd:attribute name="id" use="required" type="xsd:unsignedInt"/>
  <xsd:attribute name="name" use="optional" type="x:ST_Xstring"/>

```

```

    <xsd:attribute name="description" use="optional" type="x:ST_Xstring"/>
  </xsd:complexType>
</xsd:schema>

```

5.4 <http://schemas.microsoft.com/office/spreadsheetml/2009/9/main> Schema

```

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
  xmlns="http://schemas.microsoft.com/office/spreadsheetml/2009/9/main"
  xmlns:x="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
  targetNamespace="http://schemas.microsoft.com/office/spreadsheetml/2009/9/main"
  elementFormDefault="qualified"
  xmlns:xm="http://schemas.microsoft.com/office/excel/2006/main">
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
    schemaLocation="xlbasictypes.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
    schemaLocation="xlsheet.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
    schemaLocation="orel.xsd"/>
  <xsd:import namespace="http://schemas.microsoft.com/office/spreadsheetml/2010/11/main"
    schemaLocation="xl15.xsd"/>
  <xsd:import namespace="http://schemas.microsoft.com/office/spreadsheetml/2010/11/main"
    schemaLocation="xlslicercache15.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
    schemaLocation="xlpivot.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
    schemaLocation="xlworkbook.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
    schemaLocation="xlsupbook.xsd"/>
  <xsd:import namespace="http://schemas.microsoft.com/office/excel/2006/main"
    schemaLocation="xlmbasictypes.xsd"/>
  <xsd:import schemaLocation="xlsst.xsd"
    namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"/>
  <xsd:element name="slicerCacheDefinition" type="CT_SlicerCacheDefinition"/>
  <xsd:complexType name="CT_SlicerCacheDefinition">
    <xsd:sequence>
      <xsd:element name="pivotTables" type="CT_SlicerCachePivotTables" minOccurs="0"
        maxOccurs="1"/>
      <xsd:element name="data" type="CT_SlicerCacheData" minOccurs="0" maxOccurs="1"/>
      <xsd:element name="extLst" minOccurs="0" maxOccurs="1"/>
    </xsd:sequence>
    <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
    <xsd:attribute name="sourceName" type="x:ST_Xstring" use="required"/>
  </xsd:complexType>
  <xsd:simpleType name="ST_OlapSlicerCacheSortOrder">
    <xsd:restriction base="xsd:string">
      <xsd:enumeration value="natural"/>
      <xsd:enumeration value="ascending"/>
      <xsd:enumeration value="descending"/>
    </xsd:restriction>
  </xsd:simpleType>
  <xsd:simpleType name="ST_TabularSlicerCacheSortOrder">
    <xsd:restriction base="xsd:string">
      <xsd:enumeration value="ascending"/>
      <xsd:enumeration value="descending"/>
    </xsd:restriction>
  </xsd:simpleType>
  <xsd:simpleType name="ST_SlicerCacheCrossFilter">
    <xsd:restriction base="xsd:string">

```

```

    <xsd:enumeration value="none"/>
    <xsd:enumeration value="showItemsWithDataAtTop"/>
    <xsd:enumeration value="showItemsWithNoData"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_SlicerCacheData">
  <xsd:choice minOccurs="1" maxOccurs="1">
    <xsd:element name="olap" type="CT_OlapSlicerCache" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="tabular" type="CT_TabularSlicerCache" minOccurs="1" maxOccurs="1"/>
  </xsd:choice>
</xsd:complexType>
<xsd:complexType name="CT_SlicerCachePivotTables">
  <xsd:sequence>
    <xsd:element name="pivotTable" type="CT_SlicerCachePivotTable" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_SlicerCachePivotTable">
  <xsd:attribute name="tabId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_OlapSlicerCacheItem">
  <xsd:sequence>
    <xsd:element name="p" type="CT_OlapSlicerCacheItemParent" minOccurs="0"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="n" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="c" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="nd" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:complexType name="CT_OlapSlicerCacheItemParent">
  <xsd:attribute name="n" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_OlapSlicerCacheRange">
  <xsd:sequence>
    <xsd:element name="i" type="CT_OlapSlicerCacheItem" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="startItem" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_OlapSlicerCacheRanges">
  <xsd:sequence>
    <xsd:element name="range" type="CT_OlapSlicerCacheRange" minOccurs="0"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_OlapSlicerCacheLevelData">
  <xsd:sequence>
    <xsd:element name="ranges" type="CT_OlapSlicerCacheRanges" minOccurs="0"
maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="uniqueName" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="sourceCaption" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="sortOrder" type="ST_OlapSlicerCacheSortOrder" use="optional"
default="natural"/>
  <xsd:attribute name="crossFilter" type="ST_SlicerCacheCrossFilter" use="optional"
default="showItemsWithDataAtTop"/>
</xsd:complexType>

```

```

<xsd:complexType name="CT_OlapSlicerCacheLevelsData">
  <xsd:sequence>
    <xsd:element name="level" type="CT_OlapSlicerCacheLevelData" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_OlapSlicerCache">
  <xsd:sequence>
    <xsd:element name="levels" type="CT_OlapSlicerCacheLevelsData" minOccurs="1"
maxOccurs="1"/>
    <xsd:element name="selections" type="CT_OlapSlicerCacheSelections" minOccurs="1"
maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="pivotCacheId" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_OlapSlicerCacheSelections">
  <xsd:sequence>
    <xsd:element name="selection" type="CT_OlapSlicerCacheSelection" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_OlapSlicerCacheSelection">
  <xsd:sequence>
    <xsd:element name="p" type="CT_OlapSlicerCacheItemParent" minOccurs="0"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="n" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_TabularSlicerCache">
  <xsd:sequence>
    <xsd:element name="items" type="CT_TabularSlicerCacheItems" minOccurs="1"
maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="pivotCacheId" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="sortOrder" type="ST_TabularSlicerCacheSortOrder" use="optional"
default="ascending"/>
  <xsd:attribute name="customListSort" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="showMissing" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="crossFilter" type="ST_SlicerCacheCrossFilter" use="optional"
default="showItemsWithDataAtTop"/>
</xsd:complexType>
<xsd:complexType name="CT_TabularSlicerCacheItems">
  <xsd:sequence>
    <xsd:element name="i" type="CT_TabularSlicerCacheItem" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_TabularSlicerCacheItem">
  <xsd:attribute name="x" type="xsd:unsignedInt" use="required"/>
  <xsd:attribute name="s" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="nd" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
  <xsd:element name="conditionalFormattings" type="CT_ConditionalFormattings"/>
  <xsd:element name="dataValidations" type="CT_DataValidations"/>
  <xsd:element name="sparklineGroups" type="CT_SparklineGroups"/>

```



```

<xsd:element name="slicerList" type="CT_SlicerRefs"/>
<xsd:element name="protectedRanges" type="CT_ProtectedRanges"/>
<xsd:element name="ignoredErrors" type="CT_IgnoredErrors"/>
<xsd:complexType name="CT_ConditionalFormattings">
  <xsd:sequence>
    <xsd:element name="conditionalFormatting" type="CT_ConditionalFormatting" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_ConditionalFormatting">
  <xsd:sequence>
    <xsd:element name="cfRule" type="CT_CfRule" minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element ref="xm:sqref" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" minOccurs="0" type="x:CT_ExtensionList"/>
  </xsd:sequence>
  <xsd:attribute name="pivot" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_DataValidations">
  <xsd:sequence>
    <xsd:element name="dataValidation" type="CT_DataValidation" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="disablePrompts" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="xWindow" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="yWindow" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_DataValidationFormula">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_DataValidation">
  <xsd:sequence>
    <xsd:element name="formula1" type="CT_DataValidationFormula" minOccurs="0"
maxOccurs="1"/>
    <xsd:element name="formula2" type="CT_DataValidationFormula" minOccurs="0"
maxOccurs="1"/>
    <xsd:element ref="xm:sqref" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="type" type="x:ST_DataValidationType" use="optional" default="none"/>
  <xsd:attribute name="errorStyle" type="x:ST_DataValidationErrorStyle" use="optional"
default="stop"/>
  <xsd:attribute name="imeMode" type="x:ST_DataValidationImeMode" use="optional"
default="noControl"/>
  <xsd:attribute name="operator" type="x:ST_DataValidationOperator" use="optional"
default="between"/>
  <xsd:attribute name="allowBlank" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="showDropDown" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="showInputMessage" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="showErrorMessage" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="errorTitle" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="error" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="promptTitle" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="prompt" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:simpleType name="ST_DispatchBlanksAs">
  <xsd:restriction base="xsd:string">

```

```

    <xsd:enumeration value="span"/>
    <xsd:enumeration value="gap"/>
    <xsd:enumeration value="zero"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_SparklineAxisMinMax">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="individual"/>
    <xsd:enumeration value="group"/>
    <xsd:enumeration value="custom"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_SparklineGroups">
  <xsd:sequence>
    <xsd:element name="sparklineGroup" type="CT_SparklineGroup" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_SparklineGroup">
  <xsd:sequence>
    <xsd:element name="colorSeries" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
    <xsd:element name="colorNegative" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
    <xsd:element name="colorAxis" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
    <xsd:element name="colorMarkers" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
    <xsd:element name="colorFirst" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
    <xsd:element name="colorLast" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
    <xsd:element name="colorHigh" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
    <xsd:element name="colorLow" minOccurs="0" maxOccurs="1" type="x:CT_Color"/>
    <xsd:element ref="xm:f" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="sparklines" type="CT_Sparklines" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="manualMax" type="xsd:double" use="optional"/>
  <xsd:attribute name="manualMin" type="xsd:double" use="optional"/>
  <xsd:attribute name="lineWeight" type="xsd:double" use="optional" default="0.75"/>
  <xsd:attribute name="type" type="ST_SparklineType" use="optional" default="line"/>
  <xsd:attribute name="dateAxis" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="displayEmptyCellsAs" type="ST_DispatchBlanksAs" use="optional"
default="zero"/>
  <xsd:attribute name="markers" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="high" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="low" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="first" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="last" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="negative" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="displayXAxis" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="displayHidden" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="minAxisType" type="ST_SparklineAxisMinMax" use="optional"
default="individual"/>
  <xsd:attribute name="maxAxisType" type="ST_SparklineAxisMinMax" use="optional"
default="individual"/>
  <xsd:attribute name="rightToLeft" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:simpleType name="ST_SparklineType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="line"/>
    <xsd:enumeration value="column"/>
    <xsd:enumeration value="stacked"/>
  </xsd:restriction>
</xsd:simpleType>

```

```

<xsd:complexType name="CT_Sparklines">
  <xsd:sequence>
    <xsd:element name="sparkline" type="CT_Sparkline" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_Sparkline">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="0" maxOccurs="1"/>
    <xsd:element ref="xm:sqref" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:element name="pivotCaches" type="x:CT_PivotCaches"/>
<xsd:element name=" slicerCaches" type="CT_SlicerCaches"/>
<xsd:element name="workbookPr" type="CT_WorkbookPr"/>
<xsd:complexType name="CT_WorkbookPr">
  <xsd:attribute name="defaultImageDpi" type="xsd:unsignedInt" default="220"/>
  <xsd:attribute name="discardImageEditData" type="xsd:boolean" default="false"/>
  <xsd:attribute name="accuracyVersion" type="xsd:unsignedInt" default="0"/>
</xsd:complexType>
<xsd:complexType name="CT_SlicerRefs">
  <xsd:sequence>
    <xsd:element name="slicer" type="CT_SlicerRef" minOccurs="1" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_SlicerRef">
  <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_SlicerCaches">
  <xsd:sequence>
    <xsd:element name="slicerCache" type="CT_SlicerCache" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_SlicerCache">
  <xsd:attribute ref="r:id" use="required"/>
</xsd:complexType>
<xsd:element name="calculatedMember" type="CT_CalculatedMember"/>
<xsd:complexType name="CT_CalculatedMember">
  <xsd:sequence>
    <xsd:element name="tupleSet" minOccurs="0" maxOccurs="1" type="CT_TupleSet"/>
  </xsd:sequence>
  <xsd:attribute name="displayFolder" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="flattenHierarchies" type="xsd:boolean" use="optional"
default="true"/>
  <xsd:attribute name="dynamicSet" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="hierarchizeDistinct" type="xsd:boolean" use="optional"
default="true"/>
  <xsd:attribute name="mdxLong" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_TupleSet">
  <xsd:sequence>
    <xsd:element name="headers" type="CT_TupleSetHeaders" minOccurs="1" maxOccurs="1"/>
    <xsd:element name="rows" type="CT_TupleSetRows" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="rowCount" type="xsd:unsignedInt" use="optional" default="1"/>
  <xsd:attribute name="columnCount" type="xsd:unsignedInt" use="optional" default="1"/>
</xsd:complexType>
<xsd:complexType name="CT_TupleSetHeaders">
  <xsd:sequence>

```

```

        <xsd:element name="header" type="CT_TupleSetHeader" minOccurs="1"
maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_TupleSetHeader">
    <xsd:attribute name="uniqueName" type="x:ST_Xstring" use="optional"/>
    <xsd:attribute name="hierarchyName" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_TupleSetRows">
    <xsd:sequence>
        <xsd:element name="row" type="CT_TupleSetRow" minOccurs="1" maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_TupleSetRow">
    <xsd:sequence>
        <xsd:element name="rowItem" type="CT_TupleSetRowItem" minOccurs="1"
maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_TupleSetRowItem">
    <xsd:attribute name="u" type="x:ST_Xstring" use="optional"/>
    <xsd:attribute name="d" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:element name="cacheHierarchy" type="CT_CacheHierarchy"/>
<xsd:complexType name="CT_SetLevels">
    <xsd:sequence>
        <xsd:element name="setLevel" minOccurs="1" maxOccurs="unbounded" type="CT_SetLevel"/>
    </xsd:sequence>
    <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_SetLevel">
    <xsd:attribute name="hierarchy" use="required" type="xsd:int"/>
</xsd:complexType>
<xsd:complexType name="CT_CacheHierarchy">
    <xsd:sequence>
        <xsd:element name="setLevels" minOccurs="0" maxOccurs="1" type="CT_SetLevels"/>
    </xsd:sequence>
    <xsd:attribute name="flattenHierarchies" type="xsd:boolean" use="optional"
default="true"/>
    <xsd:attribute name="measuresSet" type="xsd:boolean" use="optional" default="false"/>
    <xsd:attribute name="hierarchizeDistinct" type="xsd:boolean" use="optional"
default="true"/>
    <xsd:attribute name="ignore" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
<xsd:element name="dataField" type="CT_DataField"/>
<xsd:complexType name="CT_DataField">
    <xsd:attribute name="pivotShowAs" type="ST_PivotShowAs" use="optional"/>
    <xsd:attribute name="sourceField" type="xsd:unsignedInt" use="optional"/>
    <xsd:attribute name="uniqueName" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:simpleType name="ST_PivotShowAs">
    <xsd:restriction base="xsd:string">
        <xsd:enumeration value="percentOfParent"/>
        <xsd:enumeration value="percentOfParentRow"/>
        <xsd:enumeration value="percentOfParentCol"/>
        <xsd:enumeration value="percentOfRunningTotal"/>
        <xsd:enumeration value="rankAscending"/>
        <xsd:enumeration value="rankDescending"/>
    </xsd:restriction>

```

```

</xsd:simpleType>
<xsd:simpleType name="ST_DataBarDirection">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="context"/>
    <xsd:enumeration value="leftToRight"/>
    <xsd:enumeration value="rightToLeft"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_DataBarAxisPosition">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="automatic"/>
    <xsd:enumeration value="middle"/>
    <xsd:enumeration value="none"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_CfvoType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="num"/>
    <xsd:enumeration value="percent"/>
    <xsd:enumeration value="max"/>
    <xsd:enumeration value="min"/>
    <xsd:enumeration value="formula"/>
    <xsd:enumeration value="percentile"/>
    <xsd:enumeration value="autoMin"/>
    <xsd:enumeration value="autoMax"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_Cfvo">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="type" type="ST_CfvoType" use="required"/>
  <xsd:attribute name="gte" type="xsd:boolean" use="optional" default="true"/>
</xsd:complexType>
<xsd:complexType name="CT_CfRule">
  <xsd:sequence>
    <xsd:element ref="xm:f" minOccurs="0" maxOccurs="3"/>
    <xsd:element name="colorScale" type="CT_ColorScale" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="dataBar" type="CT_DataBar" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="iconSet" type="CT_IconSet" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="dxmf" type="x:CT_Dxmf" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="type" type="x:ST_CfType" use="optional"/>
  <xsd:attribute name="priority" type="xsd:int" use="optional"/>
  <xsd:attribute name="stopIfTrue" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="aboveAverage" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="percent" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="bottom" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="operator" type="x:ST_ConditionalFormattingOperator" use="optional"/>
  <xsd:attribute name="text" type="xsd:string" use="optional"/>
  <xsd:attribute name="timePeriod" type="x:ST_TimePeriod" use="optional"/>
  <xsd:attribute name="rank" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="stdDev" type="xsd:int" use="optional"/>
  <xsd:attribute name="equalAverage" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="activePresent" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="id" type="x:ST_Guid" use="optional"/>
</xsd:complexType>

```

```

<xsd:complexType name="CT_IconSet">
  <xsd:sequence>
    <xsd:element name="cfvo" type="CT_Cfvo" minOccurs="2" maxOccurs="unbounded"/>
    <xsd:element name="cfIcon" type="CT_CfIcon" minOccurs="0" maxOccurs="5"/>
  </xsd:sequence>
  <xsd:attribute name="iconSet" type="ST_IconSetType" use="optional"
default="3TrafficLights1"/>
  <xsd:attribute name="showValue" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="percent" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="reverse" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="custom" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:complexType name="CT_ColorScale">
  <xsd:sequence>
    <xsd:element name="cfvo" type="CT_Cfvo" minOccurs="2" maxOccurs="unbounded"/>
    <xsd:element name="color" type="x:CT_Color" minOccurs="2" maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_DataBar">
  <xsd:sequence>
    <xsd:element name="cfvo" type="CT_Cfvo" minOccurs="2" maxOccurs="2"/>
    <xsd:element name="fillColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="borderColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="negativeFillColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="negativeBorderColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="axisColor" type="x:CT_Color" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="minLength" type="xsd:unsignedInt" use="optional" default="10"/>
  <xsd:attribute name="maxLength" type="xsd:unsignedInt" use="optional" default="90"/>
  <xsd:attribute name="showValue" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="border" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="gradient" type="xsd:boolean" use="optional" default="true"/>
  <xsd:attribute name="direction" type="ST_DataBarDirection" use="optional"
default="context"/>
  <xsd:attribute name="negativeBarColorSameAsPositive" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="negativeBarBorderColorSameAsPositive" type="xsd:boolean"
use="optional" default="true"/>
  <xsd:attribute name="axisPosition" type="ST_DataBarAxisPosition" use="optional"
default="automatic"/>
</xsd:complexType>
<xsd:element name="pivotField" type="CT_PivotField"/>
<xsd:complexType name="CT_PivotField">
  <xsd:attribute name="fillDownLabels" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="ignore" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
<xsd:element name="pivotTableDefinition" type="CT_PivotTableDefinition"/>
<xsd:complexType name="CT_PivotTableDefinition">
  <xsd:sequence>
    <xsd:element name="pivotEdits" type="CT_PivotEdits" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="pivotChanges" type="CT_PivotChanges" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="conditionalFormats" type="CT_ConditionalFormats" minOccurs="0"/>
  </xsd:sequence>
  <xsd:attribute name="fillDownLabelsDefault" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="visualTotalsForSets" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="calculatedMembersInFilters" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="altText" type="x:ST_Xstring" use="optional"/>

```

```

<xsd:attribute name="altTextSummary" type="x:ST_Xstring" use="optional"/>
<xsd:attribute name="enableEdit" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="autoApply" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="allocationMethod" type="ST_AllocationMethod" use="optional"
default="equalAllocation"/>
<xsd:attribute name="weightExpression" type="x:ST_Xstring" use="optional"/>
<xsd:attribute name="hideValuesRow" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:element name="pivotCacheDefinition" type="CT_PivotCacheDefinition"/>
<xsd:complexType name="CT_PivotCacheDefinition">
<xsd:attribute name="slicerData" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="pivotCacheId" type="xsd:unsignedInt" use="optional"/>
<xsd:attribute name="supportSubqueryNonVisual" type="xsd:boolean" use="optional"
default="false"/>
<xsd:attribute name="supportSubqueryCalcMem" type="xsd:boolean" use="optional"
default="false"/>
<xsd:attribute name="supportAddCalcMems" type="xsd:boolean" use="optional"
default="false"/>
</xsd:complexType>
<xsd:element name="connection" type="CT_Connection"/>
<xsd:complexType name="CT_Connection">
<xsd:sequence>
<xsd:element name="calculatedMembers" type="x:CT_CalculatedMembers" minOccurs="0"
maxOccurs="1"/>
</xsd:sequence>
<xsd:attribute name="culture" use="optional" type="x:ST_Xstring"/>
<xsd:attribute name="embeddedDataId" use="optional" type="x:ST_Xstring"/>
</xsd:complexType>
<xsd:element name="table" type="CT_Table"/>
<xsd:complexType name="CT_Table">
<xsd:attribute name="altText" type="x:ST_Xstring" use="optional"/>
<xsd:attribute name="altTextSummary" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_CfIcon">
<xsd:attribute name="iconSet" type="ST_IconSetType" use="required"/>
<xsd:attribute name="iconId" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
<xsd:simpleType name="ST_IconSetType">
<xsd:restriction base="xsd:string">
<xsd:enumeration value="3Arrows"/>
<xsd:enumeration value="3ArrowsGray"/>
<xsd:enumeration value="3Flags"/>
<xsd:enumeration value="3TrafficLights1"/>
<xsd:enumeration value="3TrafficLights2"/>
<xsd:enumeration value="3Signs"/>
<xsd:enumeration value="3Symbols"/>
<xsd:enumeration value="3Symbols2"/>
<xsd:enumeration value="4Arrows"/>
<xsd:enumeration value="4ArrowsGray"/>
<xsd:enumeration value="4RedToBlack"/>
<xsd:enumeration value="4Rating"/>
<xsd:enumeration value="4TrafficLights"/>
<xsd:enumeration value="5Arrows"/>
<xsd:enumeration value="5ArrowsGray"/>
<xsd:enumeration value="5Rating"/>
<xsd:enumeration value="5Quarters"/>
<xsd:enumeration value="3Stars"/>
<xsd:enumeration value="3Triangles"/>
<xsd:enumeration value="5Boxes"/>

```

```

        <xsd:enumeration value="NoIcons"/>
    </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_PivotEdits">
    <xsd:sequence>
        <xsd:element name="pivotEdit" minOccurs="1" maxOccurs="unbounded" type="CT_PivotEdit"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_PivotEdit">
    <xsd:sequence>
        <xsd:element name="userEdit" type="CT_PivotUserEdit" minOccurs="1" maxOccurs="1"/>
        <xsd:element name="tupleItems" type="CT_TupleItems" minOccurs="1" maxOccurs="1"/>
        <xsd:element name="pivotArea" type="x:CT_PivotArea" minOccurs="1" maxOccurs="1"/>
        <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_PivotChanges">
    <xsd:sequence>
        <xsd:element name="pivotChange" minOccurs="1" maxOccurs="unbounded"
type="CT_PivotChange"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_PivotChange">
    <xsd:sequence>
        <xsd:element name="editValue" type="CT_PivotEditValue" minOccurs="1" maxOccurs="1"/>
        <xsd:element name="tupleItems" type="CT_TupleItems" minOccurs="1" maxOccurs="1"/>
        <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
    </xsd:sequence>
    <xsd:attribute name="allocationMethod" type="ST_AllocationMethod"
default="equalAllocation"/>
    <xsd:attribute name="weightExpression" type="x:ST_Xstring" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_PivotUserEdit">
    <xsd:choice minOccurs="1" maxOccurs="1">
        <xsd:element ref="xm:f" minOccurs="1" maxOccurs="1"/>
        <xsd:element name="editValue" type="CT_PivotEditValue" minOccurs="1" maxOccurs="1"/>
    </xsd:choice>
</xsd:complexType>
<xsd:complexType name="CT_PivotEditValue">
    <xsd:simpleContent>
        <xsd:extension base="x:ST_Xstring">
            <xsd:attribute name="valueType" use="required" type="ST_PivotEditValueType"/>
        </xsd:extension>
    </xsd:simpleContent>
</xsd:complexType>
<xsd:simpleType name="ST_PivotEditValueType">
    <xsd:restriction base="xsd:string">
        <xsd:enumeration value="number"/>
        <xsd:enumeration value="dateTime"/>
        <xsd:enumeration value="string"/>
        <xsd:enumeration value="boolean"/>
        <xsd:enumeration value="error"/>
    </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_TupleItems">
    <xsd:sequence>
        <xsd:element name="tupleItem" type="x:ST_Xstring" minOccurs="1" maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>

```



```

<xsd:simpleType name="ST_AllocationMethod">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="equalAllocation"/>
    <xsd:enumeration value="equalIncrement"/>
    <xsd:enumeration value="weightedAllocation"/>
    <xsd:enumeration value="weightedIncrement"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_SlicerStyle">
  <xsd:sequence>
    <xsd:element name="slicerStyleElements" type="CT_SlicerStyleElements" minOccurs="0"
maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="xsd:string" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_SlicerStyleElement">
  <xsd:attribute name="type" type="ST_SlicerStyleType" use="required"/>
  <xsd:attribute name="dxfid" type="x:ST_DxfId" use="optional"/>
</xsd:complexType>
<xsd:simpleType name="ST_SlicerStyleType">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="unselectedItemWithData"/>
    <xsd:enumeration value="selectedItemWithData"/>
    <xsd:enumeration value="unselectedItemWithNoData"/>
    <xsd:enumeration value="selectedItemWithNoData"/>
    <xsd:enumeration value="hoveredUnselectedItemWithData"/>
    <xsd:enumeration value="hoveredSelectedItemWithData"/>
    <xsd:enumeration value="hoveredUnselectedItemWithNoData"/>
    <xsd:enumeration value="hoveredSelectedItemWithNoData"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:element name="slicerStyles" type="CT_SlicerStyles"/>
<xsd:element name="dxfs" type="x:CT_Dxfs"/>
<xsd:complexType name="CT_OleItem">
  <xsd:sequence>
    <xsd:element name="values" type="x:CT_DdeValues" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
  <xsd:attribute name="icon" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="advise" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="preferPic" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:element name="oleItem" type="CT_OleItem"/>
<xsd:element name="pivotHierarchy" type="CT_PivotHierarchy"/>
<xsd:complexType name="CT_PivotHierarchy">
  <xsd:attribute name="ignore" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
<xsd:element name="cacheField" type="CT_CacheField"/>
<xsd:complexType name="CT_CacheField">
  <xsd:attribute name="ignore" type="xsd:boolean" default="false" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_ConditionalFormats">
  <xsd:sequence>
    <xsd:element name="conditionalFormat" minOccurs="1" maxOccurs="unbounded"
type="CT_ConditionalFormat"/>
  </xsd:sequence>
  <xsd:attribute name="count" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
<xsd:complexType name="CT_ConditionalFormat">

```

```

<xsd:sequence>
  <xsd:element name="pivotAreas" type="x:CT_PivotAreas" minOccurs="0" maxOccurs="1"/>
  <xsd:element name="extLst" minOccurs="0" maxOccurs="1" type="x:CT_ExtensionList"/>
</xsd:sequence>
<xsd:attribute name="scope" type="x:ST_Scope" default="selection" use="optional"/>
<xsd:attribute name="type" type="x:ST_Type" default="none" use="optional"/>
<xsd:attribute name="priority" use="optional" type="xsd:unsignedInt"/>
<xsd:attribute name="id" type="x:ST_Guid" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_SlicerStyles">
  <xsd:sequence>
    <xsd:element name="slicerStyle" type="CT_SlicerStyle" minOccurs="0"
maxOccurs="unbounded"/>
  </xsd:sequence>
  <xsd:attribute name="defaultSlicerStyle" type="xsd:string" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_SlicerStyleElements">
  <xsd:sequence>
    <xsd:element name="slicerStyleElement" type="CT_SlicerStyleElement" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:element name="id" type="x:ST_Guid"/>
<xsd:complexType name="CT_IgnoredErrors">
  <xsd:sequence>
    <xsd:element name="ignoredError" type="CT_IgnoredError" minOccurs="0"
maxOccurs="unbounded"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_IgnoredError">
  <xsd:sequence>
    <xsd:element ref="xm:sqref" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="evalError" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="twoDigitTextYear" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="numberStoredAsText" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="formula" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="formulaRange" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="unlockedFormula" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="emptyCellReference" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="listDataValidation" type="xsd:boolean" use="optional"
default="false"/>
  <xsd:attribute name="calculatedColumn" type="xsd:boolean" use="optional"
default="false"/>
</xsd:complexType>
<xsd:complexType name="CT_ProtectedRanges">
  <xsd:sequence>
    <xsd:element name="protectedRange" type="CT_ProtectedRange" minOccurs="1"
maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_ProtectedRange">
  <xsd:sequence maxOccurs="1">
    <xsd:element ref="xm:sqref" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="password" type="x:ST_UnsignedShortHex" use="optional"/>

```

```

    <xsd:attribute name="algorithmName" type="x:ST_Xstring" use="optional"/>
    <xsd:attribute name="hashValue" type="xsd:base64Binary" use="optional"/>
    <xsd:attribute name="saltValue" type="xsd:base64Binary" use="optional"/>
    <xsd:attribute name="spinCount" type="xsd:unsignedInt" use="optional"/>
    <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
    <xsd:attribute name="securityDescriptor" type="xsd:string" use="optional"/>
</xsd:complexType>
<xsd:element name="iconFilter" type="CT_IconFilter"/>
<xsd:complexType name="CT_IconFilter">
  <xsd:attribute name="iconSet" type="ST_IconSetType" use="required"/>
  <xsd:attribute name="iconId" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
<xsd:element name="filter" type="CT_Filter"/>
<xsd:complexType name="CT_Filter">
  <xsd:attribute name="val" type="x:ST_Xstring"/>
</xsd:complexType>
<xsd:element name="customFilters" type="CT_CustomFilters"/>
<xsd:complexType name="CT_CustomFilters">
  <xsd:sequence>
    <xsd:element name="customFilter" type="CT_CustomFilter" minOccurs="1" maxOccurs="2"/>
  </xsd:sequence>
  <xsd:attribute name="and" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:complexType name="CT_CustomFilter">
  <xsd:attribute name="operator" type="x:ST_FilterOperator" default="equal"
use="optional"/>
  <xsd:attribute name="val" type="x:ST_Xstring"/>
</xsd:complexType>
<xsd:complexType name="CT_SortCondition">
  <xsd:attribute name="descending" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="sortBy" type="x:ST_SortBy" use="optional" default="value"/>
  <xsd:attribute name="ref" type="x:ST_Ref" use="required"/>
  <xsd:attribute name="customList" type="x:ST_Xstring" use="optional"/>
  <xsd:attribute name="dxfId" type="x:ST_DxfId" use="optional"/>
  <xsd:attribute name="iconSet" type="ST_IconSetType" use="optional" default="3Arrows"/>
  <xsd:attribute name="iconId" type="xsd:unsignedInt" use="optional"/>
</xsd:complexType>
<xsd:element name="sortCondition" type="CT_SortCondition"/>
<xsd:complexType name="CT_CacheSourceExt">
  <xsd:sequence>
    <xsd:element ref="sourceConnection" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
<xsd:element name="sourceConnection" type="CT_SourceConnection"/>
<xsd:complexType name="CT_SourceConnection">
  <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:element name="datastoreItem" type="CT_DatastoreItem"/>
<xsd:complexType name="CT_DatastoreItem">
  <xsd:sequence>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="id" type="x:ST_Xstring" use="required"/>
</xsd:complexType>
<xsd:element name="formControlPr" type="CT_FormControlPr"/>
<xsd:complexType name="CT_ListItem">
  <xsd:attribute name="val" type="xsd:string" use="required"/>
</xsd:complexType>
<xsd:complexType name="CT_ListItems">

```

```

<xsd:sequence>
  <xsd:element name="item" type="CT_ListItem" minOccurs="0" maxOccurs="unbounded"/>
  <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
</xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_FormControlPr">
  <xsd:sequence>
    <xsd:element name="itemLst" type="CT_ListItems" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="objectType" type="ST_ObjectType" use="optional"/>
  <xsd:attribute name="checked" type="ST_Checked" use="optional"/>
  <xsd:attribute name="colored" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="dropLines" type="xsd:unsignedInt" use="optional" default="8"/>
  <xsd:attribute name="dropStyle" type="ST_DropStyle" use="optional"/>
  <xsd:attribute name="dx" type="xsd:unsignedInt" use="optional" default="80"/>
  <xsd:attribute name="firstButton" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="fmlaGroup" type="x:ST_Formula" use="optional"/>
  <xsd:attribute name="fmlaLink" type="x:ST_Formula" use="optional"/>
  <xsd:attribute name="fmlaRange" type="x:ST_Formula" use="optional"/>
  <xsd:attribute name="fmlaTxbx" type="x:ST_Formula" use="optional"/>
  <xsd:attribute name="horiz" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="inc" type="xsd:unsignedInt" use="optional" default="1"/>
  <xsd:attribute name="justLastX" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="lockText" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="max" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="min" type="xsd:unsignedInt" use="optional" default="0"/>
  <xsd:attribute name="multiSel" type="xsd:string" use="optional"/>
  <xsd:attribute name="noThreeD" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="noThreeD2" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="page" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="sel" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="seltype" type="ST_SelType" use="optional" default="single"/>
  <xsd:attribute name="textHAlign" type="ST_TextHAlign" use="optional" default="left"/>
  <xsd:attribute name="textVAlign" type="ST_TextVAlign" use="optional" default="top"/>
  <xsd:attribute name="val" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="widthMin" type="xsd:unsignedInt" use="optional"/>
  <xsd:attribute name="editVal" type="ST_EditValidation" use="optional"/>
  <xsd:attribute name="multiLine" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="verticalBar" type="xsd:boolean" use="optional" default="false"/>
  <xsd:attribute name="passwordEdit" type="xsd:boolean" use="optional" default="false"/>
</xsd:complexType>
<xsd:simpleType name="ST_ObjectType">
  <xsd:restriction base="xsd:token">
    <xsd:enumeration value="Button"/>
    <xsd:enumeration value="CheckBox"/>
    <xsd:enumeration value="Drop"/>
    <xsd:enumeration value="GBox"/>
    <xsd:enumeration value="Label"/>
    <xsd:enumeration value="List"/>
    <xsd:enumeration value="Radio"/>
    <xsd:enumeration value="Scroll"/>
    <xsd:enumeration value="Spin"/>
    <xsd:enumeration value="EditBox"/>
    <xsd:enumeration value="Dialog"/>
  </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_Checked">
  <xsd:restriction base="xsd:token">

```

```

        <xsd:enumeration value="Unchecked"/>
        <xsd:enumeration value="Checked"/>
        <xsd:enumeration value="Mixed"/>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_DropStyle">
    <xsd:restriction base="xsd:token">
        <xsd:enumeration value="combo"/>
        <xsd:enumeration value="comboedit"/>
        <xsd:enumeration value="simple"/>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_SelType">
    <xsd:restriction base="xsd:token">
        <xsd:enumeration value="single"/>
        <xsd:enumeration value="multi"/>
        <xsd:enumeration value="extended"/>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_TextHAlign">
    <xsd:restriction base="xsd:string">
        <xsd:enumeration value="left"/>
        <xsd:enumeration value="center"/>
        <xsd:enumeration value="right"/>
        <xsd:enumeration value="justify"/>
        <xsd:enumeration value="distributed"/>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_TextVAlign">
    <xsd:restriction base="xsd:string">
        <xsd:enumeration value="top"/>
        <xsd:enumeration value="center"/>
        <xsd:enumeration value="bottom"/>
        <xsd:enumeration value="justify"/>
        <xsd:enumeration value="distributed"/>
    </xsd:restriction>
</xsd:simpleType>
<xsd:simpleType name="ST_EditValidation">
    <xsd:restriction base="xsd:token">
        <xsd:enumeration value="text"/>
        <xsd:enumeration value="integer"/>
        <xsd:enumeration value="number"/>
        <xsd:enumeration value="reference"/>
        <xsd:enumeration value="formula"/>
    </xsd:restriction>
</xsd:simpleType>
<xsd:element name="slicers" type="CT_Slicers"/>
<xsd:complexType name="CT_Slicers">
    <xsd:sequence>
        <xsd:element name="slicer" type="CT_Slicer" minOccurs="1" maxOccurs="unbounded"/>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_Slicer">
    <xsd:sequence>
        <xsd:element name="extLst" type="x:CT_ExtensionList" minOccurs="0" maxOccurs="1"/>
    </xsd:sequence>
    <xsd:attribute name="name" type="x:ST_Xstring" use="required"/>
    <xsd:attribute name="cache" type="x:ST_Xstring" use="required"/>
    <xsd:attribute name="caption" type="x:ST_Xstring" use="optional"/>

```

```

<xsd:attribute name="startItem" type="xsd:unsignedInt" use="optional" default="0"/>
<xsd:attribute name="columnCount" type="xsd:unsignedInt" use="optional" default="1"/>
<xsd:attribute name="showCaption" type="xsd:boolean" use="optional" default="true"/>
<xsd:attribute name="level" type="xsd:unsignedInt" use="optional" default="0"/>
<xsd:attribute name="style" type="x:ST_Xstring" use="optional"/>
<xsd:attribute name="lockedPosition" type="xsd:boolean" use="optional" default="false"/>
<xsd:attribute name="rowHeight" type="xsd:unsignedInt" use="required"/>
</xsd:complexType>
</xsd:schema>

```

5.5 <http://schemas.microsoft.com/office/spreadsheetml/2009/9/ac> Schema

```

<xsd:schema targetNamespace="http://schemas.microsoft.com/office/spreadsheetml/2009/9/ac"
elementFormDefault="qualified" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
xmlns="http://schemas.microsoft.com/office/spreadsheetml/2009/9/ac">
  <xsd:attribute name="dyDescent" type="xsd:double"/>
  <xsd:attribute name="knownFonts" type="xsd:boolean"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
schemaLocation="orel.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
schemaLocation="xlbasictypes.xsd"/>
</xsd:schema>

```

5.6 <http://schemas.microsoft.com/office/spreadsheetml/2011/1/ac> Schema

```

<xsd:schema targetNamespace="http://schemas.microsoft.com/office/spreadsheetml/2011/1/ac"
elementFormDefault="qualified" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:x="http://schemas.openxmlformats.org/spreadsheetml/2006/main" xmlns="xl12AcSchemaUri">
  <xsd:element name="list" type="x:ST_Xstring"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
schemaLocation="orel.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
schemaLocation="xlbasictypes.xsd"/>
</xsd:schema>

```

5.7 <http://schemas.microsoft.com/office/drawing/2012/timeslicer> Schema

```

<xsd:schema elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/office/drawing/2012/timeslicer"
xmlns="http://schemas.microsoft.com/office/drawing/2012/timeslicer"
xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/main"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <xsd:complexType name="CT_Timeline">
    <xsd:sequence>
      <xsd:element name="extLst" type="a:CT_OfficeArtExtensionList" minOccurs="0"
maxOccurs="1"/>
    </xsd:sequence>
    <xsd:attribute name="name" type="xsd:string" use="required"/>
  </xsd:complexType>
  <xsd:element name="timeslicer" type="CT_Timeline"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/drawingml/2006/main"
schemaLocation="oartdocprop.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
schemaLocation="orel.xsd"/>

```

```
</xsd:schema>
```

5.8 <http://schemas.microsoft.com/office/excel/2010/spreadsheetDrawing> Schema

```
<xsd:schema elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/office/excel/2010/spreadsheetDrawing"
xmlns="http://schemas.microsoft.com/office/excel/2010/spreadsheetDrawing"
xmlns:xdr="http://schemas.openxmlformats.org/drawingml/2006/spreadsheetDrawing"
xmlns:xdr14="http://xldr14SchemaUri"
xmlns:a="http://schemas.openxmlformats.org/drawingml/2006/main"
xmlns:a14="http://schemas.microsoft.com/office/drawing/2010/main"
xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <xsd:complexType name="CT_ApplicationNonVisualDrawingProps">
    <xsd:attribute name="macro" type="xsd:string" use="optional"/>
    <xsd:attribute name="fPublished" type="xsd:boolean" use="optional" default="false"/>
  </xsd:complexType>
  <xsd:complexType name="CT_ContentPartNonVisual">
    <xsd:sequence>
      <xsd:element name="cNvPr" type="a:CT_NonVisualDrawingProps" minOccurs="1"
maxOccurs="1"/>
      <xsd:element name="cNvContentPartPr" type="a14:CT_NonVisualInkContentPartProperties"
minOccurs="0" maxOccurs="1"/>
    </xsd:sequence>
  </xsd:complexType>
  <xsd:complexType name="CT_ContentPart">
    <xsd:sequence>
      <xsd:element name="nvContentPartPr" type="CT_ContentPartNonVisual" minOccurs="0"
maxOccurs="1"/>
      <xsd:element name="nvPr" type="CT_ApplicationNonVisualDrawingProps" minOccurs="0"
maxOccurs="1"/>
      <xsd:element name="xfrm" type="a:CT_Transform2D" minOccurs="0" maxOccurs="1"/>
      <xsd:element name="extLst" type="a:CT_OfficeArtExtensionList" minOccurs="0"
maxOccurs="1"/>
    </xsd:sequence>
    <xsd:attribute ref="r:id" use="required"/>
    <xsd:attribute name="bwMode" type="a:ST_BlackWhiteMode" use="optional" default="auto"/>
  </xsd:complexType>
  <xsd:element name="contentPart" type="CT_ContentPart"/>
  <xsd:import namespace="http://schemas.microsoft.com/office/drawing/2010/main"
schemaLocation="oart14docprop.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/drawingml/2006/main"
schemaLocation="oartdocprop.xsd"/>
  <xsd:import namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
schemaLocation="orel.xsd"/>
</xsd:schema>
```

5.9 <http://schemas.microsoft.com/office/spreadsheetml/2010/11/ac> Schema

```
<xsd:schema targetNamespace="http://schemas.microsoft.com/office/spreadsheetml/2010/11/ac"
elementFormDefault="qualified" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:x="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
xmlns="http://schemas.microsoft.com/office/spreadsheetml/2010/11/ac">
  <xsd:complexType name="CT_AbsolutePath">
    <xsd:attribute name="url" use="required" type="x:ST_Xstring"/>
  </xsd:complexType>
```

```
<xsd:element name="absPath" type="CT_AbsolutePath"/>
<xsd:import namespace="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
schemaLocation="orel.xsd"/>
<xsd:import namespace="http://schemas.openxmlformats.org/spreadsheetml/2006/main"
schemaLocation="xlbasictypes.xsd"/>
</xsd:schema>
```

5.10 <http://schemas.openxmlformats.org/spreadsheetml/2006/main> Schema

6 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Office Excel 2007
- Microsoft Excel 2010
- Microsoft Excel 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2:](#) This namespace was introduced in Excel 2013.

[<2> Section 2.2:](#) This namespace was introduced in Excel 2010.

[<3> Section 2.2:](#) This namespace was introduced in Excel 2010.

[<4> Section 2.2:](#) This namespace was introduced in Excel 2013.

[<5> Section 2.2:](#) This namespace was introduced in Excel 2013.

[<6> Section 2.6.3:](#) Office Excel 2007, Excel 2010, and Excel 2013 do not always write the correct value into this field (1). Although the value of this field (1) is validated on load, it is not used at run time.

[<7> Section 2.6.3:](#) Office Excel 2007, Excel 2010, and Excel 2013 do not always write the correct value into this field (1). Although the value of this field (1) is validated on load, it is not used at run time.

[<8> Section 2.6.10:](#) The following table shows the different versions of function accuracy that Excel 2010 and Excel 2013 supports.

Value	Meaning
0	Functions are calculated using the current application's algorithms.
1	Functions are calculated using algorithms implemented in Office Excel 2007.
2	Functions are calculated using algorithms implemented in Excel 2010.

[<9> Section 2.6.24:](#) Office Excel 2007 does not support multiple uses of the same OLAP measure in one cache hierarchy, and does not discard the associated cache hierarchy when **ignore** is TRUE.

[<10> Section 2.6.25:](#) Office Excel 2007 will not ignore the **fld** attribute of the ancestor **CT_DataField** ([\[ISO/IEC29500-4:2011\]](#) section A.2).

[<11> Section 2.6.30:](#) Office Excel 2007 does not ignore these complex types.

<12> [Section 2.6.31](#): Office Excel 2007 does not support multiple uses of the same OLAP measure in one PivotTable view, and does not ignore this pivot field (1) when **ignore** is TRUE.

<13> [Section 2.6.34](#): The 2007 Office system does not load a file in which this field (1) contains a value that it does not recognize, or is not recognized by the underlying operating system. The 2007 Office system recognizes the following language tags.

Language	Locale	Language tag
Afrikaans	South Africa	af-ZA
Albanian	Albania	sq-AL
Alsatian	France	gsw-FR
Amharic	Ethiopia	am-ET
Arabic	Algeria	ar-DZ
Arabic	Kingdom of Bahrain	ar-BH
Arabic	Egypt	ar-EG
Arabic	Iraq	ar-IQ
Arabic	Jordan	ar-JO
Arabic	Kuwait	ar-KW
Arabic	Lebanon	ar-LB
Arabic	Libya	ar-LY
Arabic	Morocco	ar-MA
Arabic	Oman	ar-OM
Arabic	Qatar	ar-QA
Arabic	Saudi Arabia	ar-SA
Arabic	Syria	ar-SY
Arabic	Tunisia	ar-TN
Arabic	U.A.E.	ar-AE
Arabic	Yemen	ar-YE
Armenian	Armenia	hy-AM
Assamese	India	as-IN
Azeri (Cyrillic)	Azerbaijan	az-AZ-Cyrl
Azeri (Latin)	Azerbaijan	az-AZ-Latn
Bashkir	Russia	ba-RU
Basque	Basque (Basque)	eu-ES

Language	Locale	Language tag
Belarusian	Belarus	be-BY
Bengali	Bangladesh	bn-BD
Bengali (Bengali Script)	India	bn-IN
Bosnian (Cyrillic)	Bosnia and Herzegovina	bs-BA-Cyrl
Bosnian (Latin)	Bosnia and Herzegovina	bs-BA-Latn
Breton	France	br-FR
Bulgarian	Bulgaria	bg-BG
Catalan	Catalan	ca-ES
Chinese	Hong Kong SAR	zh-HK
Chinese	Macao SAR	zh-MO
Chinese	PRC	zh-CN
Chinese	Singapore	zh-SG
Chinese	Taiwan	zh-TW
Corsican	France	co-FR
Croatian	Croatia	hr-HR
Croatian (Latin)	Bosnia and Herzegovina	hr-BA-Latn
Czech	Czech Republic	cs-CZ
Danish	Denmark	da-DK
Dari	Afghanistan	prs-AF
Divehi	Maldives	div-MV
Dutch	Belgium	nl-BE
Dutch	Netherlands	nl-NL
English	Australia	en-AU
English	Belize	en-BZ
English	Canada	en-CA
English	Caribbean	en-CB
English	India	en-IN
English	Ireland	en-IE
English	Jamaica	en-JM
English	Malaysia	en-MY

Language	Locale	Language tag
English	New Zealand	en-NZ
English	Philippines	en-PH
English	South Africa	en-ZA
English	Trinidad	en-TT
English	United Kingdom	en-GB
English	United States	en-US
English	Zimbabwe	en-ZW
Estonian	Estonia	et-EE
Faroese	Faroe Islands	fo-FO
Filipino	Philippines	fil-PH
Finnish	Finland	fi-FI
French	Belgium	fr-BE
French	Canada	fr-CA
French	France	fr-FR
French	Luxembourg	fr-LU
French	Monaco	fr-MC
French	Switzerland	fr-CH
Frisian	Netherlands	fy-NL
Galician	Galicia	gl-ES
Georgian	Georgia	ka-GE
German	Austria	de-AT
German	Germany	de-DE
German	Liechtenstein	de-LI
German	Luxembourg	de-LU
German	Switzerland	de-CH
Greek	Greece	el-GR
Greenlandic	Greenland	kl-GL
Gujarati (Gujarati Script)	India	gu-IN
Hausa (Latin)	Nigeria	ha-NG-Latn
Hebrew	Israel	he-IL

Language	Locale	Language tag
Hindi	India	hi-IN
Hungarian	Hungary	hu-HU
Icelandic	Iceland	is-IS
Igbo	Nigeria	ig-NG
Inari Sami	Finland	smn-FI
Indonesian	Indonesia	id-ID
Inuktitut (Latin)	Canada	iu-CA-Latn
Inuktitut (Syllabics)	Canada	iu-CA-Cans
Irish	Ireland	ga-IE
isiXhosa / Xhosa	South Africa	xh-ZA
isiZulu / Zulu	South Africa	zu-ZA
Italian	Italy	it-IT
Italian	Switzerland	it-CH
Japanese	Japan	ja-JP
Kannada (Kannada Script)	India	kn-IN
Kazakh	Kazakhstan	kk-KZ
Khmer	Cambodia	kh-KH
K'iche	Guatemala	qut-GT
Kinyarwanda	Rwanda	rw-RW
Konkani	India	kok-IN
Korean	Korea	ko-KR
Kyrgyz	Kyrgyzstan	ky-KG
Lao	Lao PDR	lo-LA
Latvian	Latvia	lv-LV
Lithuanian	Lithuania	lt-LT
Lower Sorbian	Germany	wee-DE
Lule Sami	Norway	smj-NO
Lule Sami	Sweden	smj-SE
Luxembourgish	Luxembourg	lb-LU
Macedonian (F.Y.R.O. Macedonia)	Former Yugoslav Republic of Macedonia	mk-MK

Language	Locale	Language tag
Malay	Brunei	ms-BN
Malay	Malaysia	ms-MY
Malayalam (Malayalam Script)	India	ml-IN
Maltese	Malta	mt-MT
Maori	New Zealand	mi-NZ
Mapudungun	Chile	arn-CL
Marathi	India	mr-IN
Mohawk	Mohawk	moh-CA
Mongolian (Cyrillic)	Mongolia	mn-MN
Mongolian (Mongolian)	PRC	mn-CN-Mong
Nepali	Federal Democratic Republic of Nepal	ne-NP
Northern Sami	Finland	se-FI
Northern Sami	Norway	se-NO
Northern Sami	Sweden	se-SE
Norwegian (Bokmål)	Norway	nb-NO
Norwegian (Nynorsk)	Norway	nn-NO
Occitan	France	oc-FR
Oriya (Oriya Script)	India	or-IN
Pashto	Afghanistan	ps-AF
Persian	Iran	fa-IR
Polish	Poland	pl-PL
Portuguese	Brazil	pt-BR
Portuguese	Portugal	pt-PT
Punjabi (Gurmukhi Script)	India	pa-IN
Quechua	Bolivia	quz-BO
Quechua	Ecuador	quz-EC
Quechua	Peru	quz-PE
Romanian	Romania	ro-RO
Romansh	Switzerland	rm-CH
Russian	Russia	ru-RU

Language	Locale	Language tag
Sanskrit	India	sa-IN
Serbian (Cyrillic)	Bosnia and Herzegovina	sr-BA-Cyrl
Serbian (Cyrillic)	Serbia	sr-SP-Cyrl
Serbian (Latin)	Bosnia and Herzegovina	sr-BA-Latn
Serbian (Latin)	Serbia	sr-SP-Latn
Sesotho sa Leboa / Northern Sotho	South Africa	ns-ZA
Setswana / Tswana	South Africa	tn-ZA
Sinhala	Sri Lanka	si-LK
Skolt Sami	Finland	sms-FI
Slovak	Slovakia	sk-SK
Slovenian	Slovenia	sl-SI
Southern Sami	Norway	sma-NO
Southern Sami	Sweden	sma-SE
Spanish	Argentina	es-AR
Spanish	Bolivia	es-BO
Spanish	Chile	es-CL
Spanish	Columbia	es-CO
Spanish	Costa Rica	es-CR
Spanish	Dominican Republic	es-DO
Spanish	Ecuador	es-EC
Spanish	El Salvador	es-SV
Spanish	Guatemala	es-GT
Spanish	Honduras	es-HN
Spanish	Mexico	es-MX
Spanish	Nicaragua	es-NI
Spanish	Panama	es-PA
Spanish	Paraguay	es-PY
Spanish	Peru	es-PE
Spanish	Commonwealth of Puerto Rico	es-PR
Spanish	Spain	es-ES

Language	Locale	Language tag
Spanish	United States	es-US
Spanish	Uruguay	es-UY
Spanish	Venezuela	es-VE
Swahili	Kenya	sw-KE
Swedish	Finland	sv-FI
Swedish	Sweden	sv-SE
Syriac	Syria	syr-SY
Tajik (Cyrillic)	Tajikistan	tg-TJ-Cyrl
Tamazight (Latin)	Algeria	tmz-DZ-Latn
Tamil	India	ta-IN
Tatar	Russia	tt-RU
Telugu (Telugu Script)	India	te-IN
Thai	Thailand	th-TH
Bhutanese	Bhutan	bo-BT
Tibetan	PRC	bo-CN
Turkish	Turkey	tr-TR
Turkmen	Turkmenistan	tk-TM
Uighur	PRC	ug-CN
Ukrainian	Ukraine	uk-UA
Upper Sorbian	Germany	wen-DE
Urdu	Pakistan	ur-PK
Uzbek (Cyrillic)	Uzbekistan	uz-UZ-Cyrl
Uzbek (Latin)	Uzbekistan	uz-UZ-Latn
Vietnamese	Viet Nam	vi-VN
Welsh	United Kingdom	cy-GB
Wolof	Senegal	wo-SN
Sakha	Russia	sah-RU
Yi	PRC	ii-CN
Yoruba	Nigeria	yo-NG

<14> [Section 2.6.47:](#) Office Excel 2007 does not ignore the ancestor **CT_PivotHierarchy** element.

<15> [Section 2.6.48](#): Office Excel 2007 does not ignore the ancestor **CT_CacheField** element.

<16> [Section 2.6.63](#): Excel 2010 and Excel 2013 requires that the corresponding **ListItem** ([\[ISO/IEC29500-4:2011\]](#) section 14.4.2.36) be present.

<17> [Section 2.6.65](#): Excel 2010 loads and roundtrips this value for scroll bars and spin boxes, but it does not support its functionality.

<18> [Section 2.6.65](#): Excel 2010 requires that the corresponding **FmlaRange** ([\[ISO/IEC29500-4:2011\]](#) section 14.4.2.29) be present.

<19> [Section 2.6.65](#): Excel 2010 and Excel 2013 ignore this attribute. This attribute is being deprecated.

<20> [Section 2.6.65](#): This attribute is being deprecated in Excel 2010. Its functionality will be replaced with attribute **noThreeD**.

<21> [Section 2.6.65](#): Excel 2010 loads and roundtrips this value, but it only supports its functionality for scroll bar form controls when run in a dialog box .

<22> [Section 2.6.65](#): Excel 2010 does not support this attribute.

<23> [Section 2.6.65](#): Excel 2010 does not support this attribute.

<24> [Section 2.7.16](#): Excel 2010 uses this value only when the drop-down control is run in a dialog box, in all other cases the drop-down control behaves as a standard combo box.

7 Change Tracking

This section identifies changes that were made to the [MS-XLSX] protocol document between the April 2014 and July 2014 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.

- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.5.1 dyDescent	Clarified that the dyDescent attribute overrides the value of the customHeight attribute by setting the customHeight value to true.	Y	New content added.
2.6.150 CT CacheSourceExt	Clarified meaning of this type	N	Content updated.
2.6.150 CT CacheSourceExt	Clarified content of this type	N	Content updated.

8 Index

“External workbook references
[extensions by part](#) 58

A

[Applicability](#) 15

B

[BrBeginECTxtWiz](#) 182

C

[cachedUniqueNames element](#) 95

[cacheField element](#) 85

[cacheHierarchy element](#) ([section 2.4.16](#) 81, [section 2.4.52](#) 92)

[calculatedMember element](#) ([section 2.4.15](#) 81, [section 2.4.44](#) 90)

[Change tracking](#) 290

Common data types and fields ([section 2](#) 17, [section 2](#) 17)

Complex types

[CT_CachedUniqueName](#) 208

[CT_CachedUniqueNames](#) 207

[CT_CacheField](#) 146

[CT_CacheHierarchy](#) ([section 2.6.24](#) 117, [section 2.6.102](#) 191)

[CT_CalculatedMember](#) ([section 2.6.15](#) 112, [section 2.6.93](#) 184)

[CT_CalculatedMemberExt](#) 184

[CT_CfIcon](#) 138

[CT_CfRule](#) 123

[CT_Cfvo](#) 122

[CT_ColorScale](#) 128

[CT_ConditionalFormat](#) 148

[CT_ConditionalFormats](#) 147

[CT_ConditionalFormatting](#) 99

[CT_ConditionalFormattings](#) 99

[CT_Connection](#) ([section 2.6.34](#) 136, [section 2.6.91](#) 182)

[CT_CustomFilter](#) 157

[CT_CustomFilters](#) 156

[CT_DataBar](#) 129

[CT_DataFeedPr](#) 207

[CT_DataField](#) ([section 2.6.25](#) 120, [section 2.6.142](#) 217)

[CT_DataModel](#) 211

[CT_DatastoreItem](#) 164

[CT_DataValidation](#) 102

[CT_DataValidationFormula](#) 101

[CT_DataValidations](#) 100

[CT_DbCommand](#) 206

[CT_DbTable](#) 205

[CT_DbTables](#) 205

[CT_FieldListActiveTabTopLevelEntity](#) 185

[CT_Filter](#) 155

[CT_FormControlPr](#) 160

[CT_IconFilter](#) 155

[CT_IconSet](#) 127

[CT_IgnoredError](#) 150

[CT_IgnoredErrors](#) 150

[CT_ListItem](#) 159

[CT_ListItems](#) 159

[CT_ModelRelationship](#) 210

[CT_ModelRelationships](#) 210

[CT_ModelTable](#) 209

[CT_ModelTables](#) 209

[CT_ModelTextPr](#) 204

[CT_OlapSlicerCache](#) 174

[CT_OlapSlicerCacheItem](#) 171

[CT_OlapSlicerCacheItemParent](#) 171

[CT_OlapSlicerCacheLevelData](#) 173

[CT_OlapSlicerCacheLevelsData](#) 174

[CT_OlapSlicerCacheRange](#) 172

[CT_OlapSlicerCacheRanges](#) 172

[CT_OlapSlicerCacheSelection](#) 176

[CT_OlapSlicerCacheSelections](#) 175

[CT_OledbPr](#) 206

[CT_OleItem](#) 144

[CT_PivotCacheDecoupled](#) 215

[CT_PivotCacheDefinition](#) 135

[CT_PivotCacheIdVersion](#) 216

[CT_PivotChange](#) 140

[CT_PivotChanges](#) 139

[CT_PivotEdit](#) 139

[CT_PivotEdits](#) 138

[CT_PivotEditValue](#) 141

[CT_PivotField](#) 132

[CT_PivotFilter](#) 186

[CT_PivotHierarchy](#) 145

[CT_PivotRow](#) 212

[CT_PivotTableData](#) 211

[CT_PivotTableDefinition](#) 133

[CT_PivotTableReference](#) 180

[CT_PivotTableReferences](#) 179

[CT_PivotTableServerFormats](#) 215

[CT_PivotTableUISettings](#) 188

[CT_PivotUserEdit](#) 141

[CT_PivotValueCell](#) 213

[CT_PivotValueCellExtra](#) 214

[CT_ProtectedRange](#) 153

[CT_ProtectedRanges](#) 153

[CT_QueryTable](#) 180

[CT_RangePr](#) 205

[CT_SetLevel](#) 117

[CT_SetLevels](#) 116

[CT_Slicer](#) ([section 2.6.68](#) 165, [section 2.6.69](#) 167)

[CT_SlicerCache](#) 111

[CT_SlicerCacheData](#) 169

[CT_SlicerCacheDefinition](#) 168

[CT_SlicerCacheHideNoData](#) 192

[CT_SlicerCacheOlapLevelName](#) 192

[CT_SlicerCachePivotTable](#) 170

[CT_SlicerCachePivotTables](#) 169

[CT_SlicerCaches](#) 111
[CT_SlicerRef](#) 110
[CT_SlicerRefs](#) 110
[CT_Slicers](#) 165
[CT_SlicerStyle](#) 142
[CT_SlicerStyleElement](#) 143
[CT_SlicerStyleElements](#) 149
[CT_SlicerStyles](#) 149
[CT_SortCondition](#) 157
[CT_SourceConnection](#) 158
[CT_Sparkline](#) 109
[CT_SparklineGroup](#) 104
[CT_SparklineGroups](#) 104
[CT_Sparklines](#) 108
[CT_Table](#) 137
[CT_TableSlicerCache](#) 188
[CT_TabularSlicerCache](#) 176
[CT_TabularSlicerCacheItem](#) 178
[CT_TabularSlicerCacheItems](#) 178
[CT_Timeline](#) 196
[CT_TimelineCacheDefinition](#) 198
[CT_TimelineCachePivotTable](#) 200
[CT_TimelineCachePivotTables](#) 200
[CT_TimelineCacheRef](#) 190
[CT_TimelineCacheRefs](#) 189
[CT_TimelinePivotCacheDefinition](#) 195
[CT_TimelinePivotFilter](#) 203
[CT_TimelineRange](#) 201
[CT_TimelineRef](#) 191
[CT_TimelineRefs](#) 190
[CT_Timelines](#) 195
[CT_TimelineState](#) 201
[CT_TimelineStyle](#) 194
[CT_TimelineStyleElement](#) 194
[CT_TimelineStyleElements](#) 193
[CT_TimelineStyles](#) 193
[CT_TupleSet](#) 113
[CT_TupleSetHeader](#) 114
[CT_TupleSetHeaders](#) 114
[CT_TupleSetRow](#) 115
[CT_TupleSetRowItem](#) 116
[CT_TupleSetRows](#) 115
[CT_TypeItems](#) 142
[CT_WebExtension](#) 181
[CT_WebExtensions](#) 181
[CT_WorkbookPr](#) ([section 2.6.10](#) 109, [section 2.6.117](#) 202)
 Conceptual overview
 [structures](#) 68
 [conditionalFormattings element](#) 78
 connection element ([section 2.4.21](#) 83, [section 2.4.43](#) 90)
 Connections
 [extensions by part](#) 56
 Control properties
 [part enumerations](#) 17
[CT_CachedUniqueName complex type](#) 208
[CT_CachedUniqueNames complex type](#) 207
[CT_CacheField complex type](#) 146
[CT_CacheHierarchy complex type](#) ([section 2.6.24](#) 117, [section 2.6.102](#) 191)
[CT_CalculatedMember complex type](#) ([section 2.6.15](#) 112, [section 2.6.93](#) 184)
[CT_CalculatedMemberExt complex type](#) 184
[CT_CfIcon complex type](#) 138
[CT_CfRule complex type](#) 123
[CT_Cfvo complex type](#) 122
[CT_ColorScale complex type](#) 128
[CT_ConditionalFormat complex type](#) 148
[CT_ConditionalFormats complex type](#) 147
[CT_ConditionalFormatting complex type](#) 99
[CT_ConditionalFormattings complex type](#) 99
[CT_Connection complex type](#) ([section 2.6.34](#) 136, [section 2.6.91](#) 182)
[CT_CustomFilter complex type](#) 157
[CT_CustomFilters complex type](#) 156
[CT_DataBar complex type](#) 129
[CT_DataFeedPr complex type](#) 207
[CT_DataField complex type](#) ([section 2.6.25](#) 120, [section 2.6.142](#) 217)
[CT_DataModel complex type](#) 211
[CT_DatastoreItem complex type](#) 164
[CT_DataValidation complex type](#) 102
[CT_DataValidationFormula complex type](#) 101
[CT_DataValidations complex type](#) 100
[CT_DbCommand complex type](#) 206
[CT_DbTable complex type](#) 205
[CT_DbTables complex type](#) 205
[CT_FieldListActiveTabTopLevelEntity complex type](#) 185
[CT_Filter complex type](#) 155
[CT_FormControlPr complex type](#) 160
[CT_IconFilter complex type](#) 155
[CT_IconSet complex type](#) 127
[CT_IgnoredError complex type](#) 150
[CT_IgnoredErrors complex type](#) 150
[CT_ListItem complex type](#) 159
[CT_ListItems complex type](#) 159
[CT_ModelRelationship complex type](#) 210
[CT_ModelRelationships complex type](#) 210
[CT_ModelTable complex type](#) 209
[CT_ModelTables complex type](#) 209
[CT_ModelTextPr complex type](#) 204
[CT_OlapSlicerCache complex type](#) 174
[CT_OlapSlicerCacheItem complex type](#) 171
[CT_OlapSlicerCacheItemParent complex type](#) 171
[CT_OlapSlicerCacheLevelData complex type](#) 173
[CT_OlapSlicerCacheLevelsData complex type](#) 174
[CT_OlapSlicerCacheRange complex type](#) 172
[CT_OlapSlicerCacheRanges complex type](#) 172
[CT_OlapSlicerCacheSelection complex type](#) 176
[CT_OlapSlicerCacheSelections complex type](#) 175
[CT_OledbPr complex type](#) 206
[CT_OleItem complex type](#) 144
[CT_PivotCacheDecoupled complex type](#) 215
[CT_PivotCacheDefinition complex type](#) 135
[CT_PivotCacheIdVersion complex type](#) 216
[CT_PivotChange complex type](#) 140
[CT_PivotChanges complex type](#) 139
[CT_PivotEdit complex type](#) 139
[CT_PivotEdits complex type](#) 138
[CT_PivotEditValue complex type](#) 141

[CT_PivotField complex type](#) 132
[CT_PivotFilter complex type](#) 186
[CT_PivotHierarchy complex type](#) 145
[CT_PivotRow complex type](#) 212
[CT_PivotTableData complex type](#) 211
[CT_PivotTableDefinition complex type](#) 133
[CT_PivotTableReference complex type](#) 180
[CT_PivotTableReferences complex type](#) 179
[CT_PivotTableServerFormats complex type](#) 215
[CT_PivotTableUISettings complex type](#) 188
[CT_PivotUserEdit complex type](#) 141
[CT_PivotValueCell complex type](#) 213
[CT_PivotValueCellExtra complex type](#) 214
[CT_ProtectedRange complex type](#) 153
[CT_ProtectedRanges complex type](#) 153
[CT_QueryTable complex type](#) 180
[CT_RangePr complex type](#) 205
[CT_SetLevel complex type](#) 117
[CT_SetLevels complex type](#) 116
[CT_Slicer complex type](#) ([section 2.6.68](#) 165, [section 2.6.69](#) 167)
[CT_SlicerCache complex type](#) 111
[CT_SlicerCacheData complex type](#) 169
[CT_SlicerCacheDefinition complex type](#) 168
[CT_SlicerCacheHideNoData complex type](#) 192
[CT_SlicerCacheOlapLevelName complex type](#) 192
[CT_SlicerCachePivotTable complex type](#) 170
[CT_SlicerCachePivotTables complex type](#) 169
[CT_SlicerCaches complex type](#) 111
[CT_SlicerRef complex type](#) 110
[CT_SlicerRefs complex type](#) 110
[CT_Slicers complex type](#) 165
[CT_SlicerStyle complex type](#) 142
[CT_SlicerStyleElement complex type](#) 143
[CT_SlicerStyleElements complex type](#) 149
[CT_SlicerStyles complex type](#) 149
[CT_SortCondition complex type](#) 157
[CT_SourceConnection complex type](#) 158
[CT_Sparkline complex type](#) 109
[CT_SparklineGroup complex type](#) 104
[CT_SparklineGroups complex type](#) 104
[CT_Sparklines complex type](#) 108
[CT_Table complex type](#) 137
[CT_TableSlicerCache complex type](#) 188
[CT_TabularSlicerCache complex type](#) 176
[CT_TabularSlicerCacheItem complex type](#) 178
[CT_TabularSlicerCacheItems complex type](#) 178
[CT_Timeline complex type](#) 196
[CT_TimelineCacheDefinition complex type](#) 198
[CT_TimelineCachePivotTable complex type](#) 200
[CT_TimelineCachePivotTables complex type](#) 200
[CT_TimelineCacheRef complex type](#) 190
[CT_TimelineCacheRefs complex type](#) 189
[CT_TimelinePivotCacheDefinition complex type](#) 195
[CT_TimelinePivotFilter complex type](#) 203
[CT_TimelineRange complex type](#) 201
[CT_TimelineRef complex type](#) 191
[CT_TimelineRefs complex type](#) 190
[CT_Timelines complex type](#) 195
[CT_TimelineState complex type](#) 201
[CT_TimelineStyle complex type](#) 194

[CT_TimelineStyleElement complex type](#) 194
[CT_TimelineStyleElements complex type](#) 193
[CT_TimelineStyles complex type](#) 193
[CT_TupleItems complex type](#) 142
[CT_TupleSet complex type](#) 113
[CT_TupleSetHeader complex type](#) 114
[CT_TupleSetHeaders complex type](#) 114
[CT_TupleSetRow complex type](#) 115
[CT_TupleSetRowItem complex type](#) 116
[CT_TupleSetRows complex type](#) 115
[CT_WebExtension complex type](#) 181
[CT_WebExtensions complex type](#) 181
[CT_WorkbookPr complex type](#) ([section 2.6.10](#) 109, [section 2.6.117](#) 202)
 Custom data
 [part enumerations](#) 17
 Custom data properties
 [part enumerations](#) 18
[customFilters element](#) 86

D

Data model
 [part enumerations](#) 19
 Data types and fields - common ([section 2](#) 17, [section 2](#) 17)
 dataField element ([section 2.4.17](#) 82, [section 2.4.69](#) 97)
[dataModel element](#) 95
[datastoreItem element](#) 87
[dataValidations element](#) 79
 Details
 [BrtBeginECTxtWiz record](#) 182
 common data types and fields ([section 2](#) 17, [section 2](#) 17)
 Drawing
 [extensions by part](#) 57
 dxfs element ([section 2.4.24](#) 84, [section 2.4.55](#) 93)
[dyDescent attribute](#) 98

E

Examples ([section 3](#) 247, [section 3](#) 247)
 [Slicer](#) 247
 [slicer cache part](#) 248
 [slicer part](#) 249
 Extensions
 [formulas](#) 22
 [cell formulas](#) 50
 [conditional formatting formulas](#) 50
 [data validation formulas](#) 50
 [external name formulas](#) 51
 [name formulas](#) 51
 [pivot field formulas](#) 51
 [pivot item formulas](#) 52
 [functions](#) 52
 [SpreadsheetML extensibility elements](#) 22
 [structures](#) 21
 Extensions by part
 [connections](#) 56
 [drawing](#) 57
 [external workbook references](#) 58

[part enumerations](#) 56
[pivot table](#) 58
pivot table cache definition ([section 2.2.4.5](#) 60,
[section 2.2.4.6](#) 62)
[query table](#) 62
 [slicer cache](#) 63
[styles](#) 62
[table definition](#) 63
[workbook](#) 65
[worksheet](#) 65

F

[f element](#) 77
[Fields - vendor-extensible](#) 16
[filter element](#) 86
[formControlPr element](#) 87
Formulas
[extensions](#) 22
[cell formulas](#) 50
[conditional formatting formulas](#) 50
[data validation formulas](#) 50
[external name formulas](#) 51
[name formulas](#) 51
[pivot field formulas](#) 51
[pivot item formulas](#) 52
[Full XML schema](#) 252
Functions
[extensions](#) 52

G

Global attributes
[dyDescent](#) 98
[knownFonts](#) 98
Global elements
[cachedUniqueNames](#) 95
[cacheField](#) 85
cacheHierarchy ([section 2.4.16](#) 81, [section 2.4.52](#)
92)
calculatedMember ([section 2.4.15](#) 81, [section](#)
[2.4.44](#) 90)
[conditionalFormattings](#) 78
connection ([section 2.4.21](#) 83, [section 2.4.43](#) 90)
[customFilters](#) 86
dataField ([section 2.4.17](#) 82, [section 2.4.69](#) 97)
[dataModel](#) 95
[datastoreItem](#) 87
[dataValidations](#) 79
dxfs ([section 2.4.24](#) 84, [section 2.4.55](#) 93)
[f](#) 77
[filter](#) 86
[formControlPr](#) 87
[iconFilter](#) 85
[id](#) 85
[ignoredErrors](#) 80
[oleItem](#) 84
[pivotCacheDecoupled](#) 96
[pivotCacheDefinition](#) 83
[pivotCacheIdVersion](#) 96
pivotCaches ([section 2.4.12](#) 80, [section 2.4.39](#)
88)

[pivotField](#) 82
[pivotFilter](#) 90
[pivotHierarchy](#) 84
[pivotTableData](#) 95
[pivotTableDefinition](#) 82
pivotTableReferences ([section 2.4.1](#) 77, [section](#)
[2.4.40](#) 89)
[pivotTableServerFormats](#) 77
[pivotTableUISettings](#) 90
[protectedRanges](#) 80
[queryTable](#) 89
[ref](#) 78
slicer ([section 2.4.37](#) 88, [section 2.4.66](#) 96)
[slicerCacheDefinition](#) 88
[slicerCacheHideItemsWithNoData](#) 92
[slicerCachePivotTables](#) 94
slicerCaches ([section 2.4.13](#) 80, [section 2.4.47](#)
91)
[slicerList](#) 79
[slicers](#) 87
[slicerStyles](#) 83
[sortCondition](#) 86
[sortConnection](#) 86
[sparklineGroups](#) 79
[sqrref](#) 78
[table](#) 83
[tableSlicerCache](#) 91
[timelineCacheDefinition](#) 94
[timelineCachePivotCaches](#) 92
[timelineCacheRefs](#) 91
[timelinePivotCacheDefinition](#) 93
[timelineRefs](#) 92
[timelines](#) 94
[timelineStyles](#) 93
[webExtensions](#) 89
workbookPr ([section 2.4.14](#) 81, [section 2.4.59](#)
94)

[Glossary](#) 11

I

[iconFilter element](#) 85
[id element](#) 85
[ignoredErrors element](#) 80
[Implementer - security considerations](#) 251
[Informative references](#) 14
[Introduction](#) 11

K

[knownFonts attribute](#) 98

L

[Localization](#) 15

N

Non-worksheet pivot table
[overview](#) 74
[Normative references](#) 13

O

[oleItem element](#) 84
[Overview \(synopsis\)](#) 14

P

Part enumerations

[control properties](#) 17
[custom data](#) 17
[custom data properties](#) 18
[data model](#) 19
[extensions by part](#) 56
 [slicer cache](#) 18
 [slicers](#) 18
[structures](#) 17
[timeline cache](#) 20
timelines ([section 2.1.8](#) 21, [section 2.1.9](#) 21)

Pivot table

[extensions by part](#) 58

Pivot table cache definition

[extensions by part](#) ([section 2.2.4.5](#) 60, [section 2.2.4.6](#) 62)

[pivotCacheDecoupled element](#) 96
[pivotCacheDefinition element](#) 83
[pivotCacheIdVersion element](#) 96
pivotCaches element ([section 2.4.12](#) 80, [section 2.4.39](#) 88)
[pivotField element](#) 82
[pivotFilter element](#) 90
[pivotHierarchy element](#) 84
PivotTable what-if analysis
[overview](#) 68
[pivotTableData element](#) 95
[pivotTableDefinition element](#) 82
pivotTableReferences element ([section 2.4.1](#) 77, [section 2.4.40](#) 89)
[pivotTableServerFormats element](#) 77
[pivotTableUISettings element](#) 90
PivotValues
[overview](#) 74
[Product behavior](#) 281
[protectedRanges element](#) 80

Q

Query table

[extensions by part](#) 62
[queryTable element](#) 89

R

Records

[BrtBeginECTxtWiz](#) 182
[ref element](#) 78
[References](#) 13
[informative](#) 14
[normative](#) 13
[Relationship to protocols and other structures](#) 15

S

Security

[implementer considerations](#) 251
[index of security fields](#) 251

Simple types

[ST_AllocationMethod](#) 233
[ST_CalcMemNumberFormat](#) 242
[ST_CfvoType](#) 230
[ST_Checked](#) 236
[ST_DataBarAxisPosition](#) 229
[ST_DataBarDirection](#) 229
[ST_DisbBlanksAs](#) 226
[ST_DropStyle](#) 236
[ST_EditValidation](#) 237
[ST_IconSetType](#) 231
[ST_ObjectType](#) 235
[ST_OlapSlicerCacheSortOrder](#) 238
[ST_PivotEditValueType](#) 233
[ST_PivotShowAs](#) 228
[ST_Ref](#) 225
[ST_SelType](#) 237
[ST_SlicerCacheCrossFilter](#) 239
[ST_SlicerStyleType](#) 234
[ST_SparklineAxisMinMax](#) 227
[ST_SparklineType](#) 228
[ST_Sqref](#) 226
[ST_SXVCellType](#) 243
[ST_TabularSlicerCacheSortOrder](#) 239
[ST_TextHAlign](#) 240
[ST_TextVAlign](#) 240
[ST_TimelineStyleType](#) 241

Slicer cache

[extensions by part](#) 63
[overview](#) 69
[part enumerations](#) 18
[Slicer cache part example](#) 248
 slicer element ([section 2.4.37](#) 88, [section 2.4.66](#) 96)

[Slicer example](#) 247

[slicer cache part](#) 248
 [slicer part](#) 249

[Slicer part example](#) 249

Slicer styles

[overview](#) 73

Slicer view

[overview](#) 72
 [slicerCacheDefinition element](#) 88
 [slicerCacheHideItemsWithNoData element](#) 92
 [slicerCachePivotTables element](#) 94
 slicerCaches element ([section 2.4.13](#) 80, [section 2.4.47](#) 91)
 [slicerList element](#) 79

Slicers

[overview](#) 68
[part enumerations](#) 18
 [slicer cache](#) 69
 [slicer styles](#) 73
 [slicer view](#) 72
 [slicers and cube functions](#) 73

Slicers and cube functions

[overview](#) 73
 [slicers element](#) 87

[slicerStyles element](#) 83
[sortCondition element](#) 86
[sortConnection element](#) 86
[sparklineGroups element](#) 79
 SpreadsheetML extensibility elements
 [extensions](#) 22
[sqref element](#) 78
[ST_AllocationMethod simple type](#) 233
[ST_CalcMemNumberFormat simple type](#) 242
[ST_CfvoType simple type](#) 230
[ST_Checked simple type](#) 236
[ST_DataBarAxisPosition simple type](#) 229
[ST_DataBarDirection simple type](#) 229
[ST_DisbBlanksAs simple type](#) 226
[ST_DropStyle simple type](#) 236
[ST_EditValidation simple type](#) 237
[ST_IconSetType simple type](#) 231
[ST_ObjectType simple type](#) 235
[ST_OlapSlicerCacheSortOrder simple type](#) 238
[ST_PivotEditValueType simple type](#) 233
[ST_PivotShowAs simple type](#) 228
[ST_Ref simple type](#) 225
[ST_SelType simple type](#) 237
[ST_SlicerCacheCrossFilter simple type](#) 239
[ST_SlicerStyleType simple type](#) 234
[ST_SparklineAxisMinMax simple type](#) 227
[ST_SparklineType simple type](#) 228
[ST_Sqref simple type](#) 226
[ST_SXVCellType simple type](#) 243
[ST_TabularSlicerCacheSortOrder simple type](#) 239
[ST_TextHAlign simple type](#) 240
[ST_TextVAlign simple type](#) 240
[ST_TimelineStyleType simple type](#) 241
 Structures
 complex types
 [CT_CachedUniqueName](#) 208
 [CT_CachedUniqueNames](#) 207
 [CT_CacheField](#) 146
 [CT_CacheHierarchy](#) ([section 2.6.24](#) 117, [section 2.6.102](#) 191)
 [CT_CalculatedMember](#) ([section 2.6.15](#) 112, [section 2.6.93](#) 184)
 [CT_CalculatedMemberExt](#) 184
 [CT_Cficon](#) 138
 [CT_CfRule](#) 123
 [CT_Cfvo](#) 122
 [CT_ColorScale](#) 128
 [CT_ConditionalFormat](#) 148
 [CT_ConditionalFormats](#) 147
 [CT_ConditionalFormatting](#) 99
 [CT_ConditionalFormattings](#) 99
 [CT_Connection](#) ([section 2.6.34](#) 136, [section 2.6.91](#) 182)
 [CT_CustomFilter](#) 157
 [CT_CustomFilters](#) 156
 [CT_DataBar](#) 129
 [CT_DataFeedPr](#) 207
 [CT_DataField](#) ([section 2.6.25](#) 120, [section 2.6.142](#) 217)
 [CT_DataModel](#) 211
 [CT_DatastoreItem](#) 164
 [CT_DataValidation](#) 102
 [CT_DataValidationFormula](#) 101
 [CT_DataValidations](#) 100
 [CT_DbCommand](#) 206
 [CT_DbTable](#) 205
 [CT_DbTables](#) 205
 [CT_FieldListActiveTabTopLevelEntity](#) 185
 [CT_Filter](#) 155
 [CT_FormControlPr](#) 160
 [CT_IconFilter](#) 155
 [CT_IconSet](#) 127
 [CT_IgnoredError](#) 150
 [CT_IgnoredErrors](#) 150
 [CT_ListItem](#) 159
 [CT_ListItems](#) 159
 [CT_ModelRelationship](#) 210
 [CT_ModelRelationships](#) 210
 [CT_ModelTable](#) 209
 [CT_ModelTables](#) 209
 [CT_ModelTextPr](#) 204
 [CT_OlapSlicerCache](#) 174
 [CT_OlapSlicerCacheItem](#) 171
 [CT_OlapSlicerCacheItemParent](#) 171
 [CT_OlapslicerCacheLevelData](#) 173
 [CT_OlapSlicerCacheLevelsData](#) 174
 [CT_OlapSlicerCacheRange](#) 172
 [CT_OlapSlicerCacheRanges](#) 172
 [CT_OlapSlicerCacheSelection](#) 176
 [CT_OlapSlicerCacheSelections](#) 175
 [CT_OledbPr](#) 206
 [CT_OleItem](#) 144
 [CT_PivotCacheDecoupled](#) 215
 [CT_PivotCacheDefinition](#) 135
 [CT_PivotCacheIdVersion](#) 216
 [CT_PivotChange](#) 140
 [CT_PivotChanges](#) 139
 [CT_PivotEdit](#) 139
 [CT_PivotEdits](#) 138
 [CT_PivotEditValue](#) 141
 [CT_PivotField](#) 132
 [CT_PivotFilter](#) 186
 [CT_PivotHierarchy](#) 145
 [CT_PivotRow](#) 212
 [CT_PivotTableData](#) 211
 [CT_PivotTableDefinition](#) 133
 [CT_PivotTableReference](#) 180
 [CT_PivotTableReferences](#) 179
 [CT_PivotTableServerFormats](#) 215
 [CT_PivotTableUISettings](#) 188
 [CT_PivotUserEdit](#) 141
 [CT_PivotValueCell](#) 213
 [CT_PivotValueCellExtra](#) 214
 [CT_ProtectedRange](#) 153
 [CT_ProtectedRanges](#) 153
 [CT_QueryTable](#) 180
 [CT_RangePr](#) 205
 [CT_SetLevel](#) 117
 [CT_SetLevels](#) 116
 [CT_Slicer](#) ([section 2.6.68](#) 165, [section 2.6.69](#) 167)
 [CT_SlicerCache](#) 111

- [CT_SlicerCacheData](#) 169
- [CT_SlicerCacheDefinition](#) 168
- [CT_SlicerCacheHideNoData](#) 192
- [CT_SlicerCacheOlapLevelName](#) 192
- [CT_SlicerCachePivotTable](#) 170
- [CT_SlicerCachePivotTables](#) 169
- [CT_SlicerCaches](#) 111
- [CT_SlicerRef](#) 110
- [CT_SlicerRefs](#) 110
- [CT_Slicers](#) 165
- [CT_SlicerStyle](#) 142
- [CT_SlicerStyleElement](#) 143
- [CT_SlicerStyleElements](#) 149
- [CT_SlicerStyles](#) 149
- [CT_SortCondition](#) 157
- [CT_SourceConnection](#) 158
- [CT_Sparkline](#) 109
- [CT_SparklineGroup](#) 104
- [CT_SparklineGroups](#) 104
- [CT_Sparklines](#) 108
- [CT_Table](#) 137
- [CT_TableSlicerCache](#) 188
- [CT_TabularSlicerCache](#) 176
- [CT_TabularSlicerCacheItem](#) 178
- [CT_TabularSlicerCacheItems](#) 178
- [CT_Timeline](#) 196
- [CT_TimelineCacheDefinition](#) 198
- [CT_TimelineCachePivotTable](#) 200
- [CT_TimelineCachePivotTables](#) 200
- [CT_TimelineCacheRef](#) 190
- [CT_TimelineCacheRefs](#) 189
- [CT_TimelinePivotCacheDefinition](#) 195
- [CT_TimelinePivotFilter](#) 203
- [CT_TimelineRange](#) 201
- [CT_TimelineRef](#) 191
- [CT_TimelineRefs](#) 190
- [CT_Timelines](#) 195
- [CT_TimelineState](#) 201
- [CT_TimelineStyle](#) 194
- [CT_TimelineStyleElement](#) 194
- [CT_TimelineStyleElements](#) 193
- [CT_TimelineStyles](#) 193
- [CT_TupleItems](#) 142
- [CT_TupleSet](#) 113
- [CT_TupleSetHeader](#) 114
- [CT_TupleSetHeaders](#) 114
- [CT_TupleSetRow](#) 115
- [CT_TupleSetRowItem](#) 116
- [CT_TupleSetRows](#) 115
- [CT_WebExtension](#) 181
- [CT_WebExtensions](#) 181
- [CT_WorkbookPr](#) ([section 2.6.10](#) 109, [section 2.6.117](#) 202)
- [conceptual overview](#) 68
 - [non-worksheet pivot table](#) 74
 - [PivotTable what-if analysis](#) 68
 - [PivotValues](#) 74
 - [slicers](#) 68
 - [slicer cache](#) 69
 - [slicer styles](#) 73
 - [slicer view](#) 72
 - [slicers and cube functions](#) 73
 - [timeline cache](#) 75
- timeline
 - [timeline styles](#) 76
 - [timeline view](#) 76
- [timelines](#) 74
 - [timelines and cube functions](#) 76
- [extensions](#) 21
- global attributes
 - [dyDescent](#) 98
 - [knownFonts](#) 98
- global elements
 - [cachedUniqueNames](#) 95
 - [cacheField](#) 85
 - cacheHierarchy ([section 2.4.16](#) 81, [section 2.4.52](#) 92)
 - calculatedMember ([section 2.4.15](#) 81, [section 2.4.44](#) 90)
 - [conditionalFormattings](#) 78
 - connection ([section 2.4.21](#) 83, [section 2.4.43](#) 90)
 - [customFilters](#) 86
 - dataField ([section 2.4.17](#) 82, [section 2.4.69](#) 97)
 - [dataModel](#) 95
 - [datastoreItem](#) 87
 - [dataValidations](#) 79
 - dxfs ([section 2.4.24](#) 84, [section 2.4.55](#) 93)
 - [f](#) 77
 - [filter](#) 86
 - [formControlPr](#) 87
 - [iconFilter](#) 85
 - [id](#) 85
 - [ignoreerrors](#) 80
 - [oleItem](#) 84
 - [pivotCacheDecoupled](#) 96
 - [pivotCacheDefinition](#) 83
 - [pivotCacheIdVersion](#) 96
 - pivotCaches ([section 2.4.12](#) 80, [section 2.4.39](#) 88)
 - [pivotField](#) 82
 - [pivotFilter](#) 90
 - [pivotHierarchy](#) 84
 - [pivotTableData](#) 95
 - [pivotTableDefinition](#) 82
 - [pivotTableReference](#) 77
 - [pivotTableReferences](#) 89
 - [pivotTableServerFormats](#) 77
 - [pivotTableUISettings](#) 90
 - [protectedRanges](#) 80
 - [queryTable](#) 89
 - [ref](#) 78
 - slicer ([section 2.4.37](#) 88, [section 2.4.66](#) 96)
 - [slicerCacheDefinition](#) 88
 - [slicerCacheHideItemsWithNoData](#) 92
 - [slicerCachePivotTables](#) 94
 - slicerCaches ([section 2.4.13](#) 80, [section 2.4.47](#) 91)
 - [slicerList](#) 79
 - [slicers](#) 87
 - [slicerStyles](#) 83
 - [sortCondition](#) 86

- [sortConnection](#) 86
- [sparklineGroups](#) 79
- [sqref](#) 78
- [table](#) 83
- [tableSlicerCache](#) 91
- [timelineCacheDefinition](#) 94
- [timelineCachePivotCaches](#) 92
- [timelineCacheRefs](#) 91
- [timelinePivotCacheDefinition](#) 93
- [timelineRefs](#) 92
- [timelines](#) 94
- [timelineStyles](#) 93
- [webExtensions](#) 89
- workbookPr ([section 2.4.14](#) 81, [section 2.4.59](#) 94)
- overview ([section 2](#) 17, [section 2](#) 17)
- [part enumerations](#) 17
- simple types
 - [ST_AllocationMethod](#) 233
 - [ST_CfvoType](#) 230
 - [ST_Checked](#) 236
 - [ST_DataBarAxisPosition](#) 229
 - [ST_DataBarDirection](#) 229
 - [ST_DispBlanksAs](#) 226
 - [ST_DropStyle](#) 236
 - [ST_EditValidation](#) 237
 - [ST_IconSetType](#) 231
 - [ST_ObjectType](#) 235
 - [ST_OlapSlicerCacheSortOrder](#) 238
 - [ST_PivotEditValueType](#) 233
 - [ST_PivotShowAs](#) 228
 - [ST_Ref](#) 225
 - [ST_SelType](#) 237
 - [ST_SlicerCacheCrossFilter](#) 239
 - [ST_SlicerStyleType](#) 234
 - [ST_SparklineAxisMinMax](#) 227
 - [ST_SparklineType](#) 228
 - [ST_Sqref](#) 226
 - [ST_SXVCellType](#) 243
 - [ST_TabularSlicerCacheSortOrder](#) 239
- Structures – simple types
 - [ST_CalcMemNumberFormat](#) 242
 - [ST_TextHAlign](#) 240
 - [ST_TextVAlign](#) 240
 - [ST_TimelineStyleType](#) 241
- Structures/
 - /complex types /
 - /CT_AbsolutePath
 - Complex types/
 - [/CT_AbsolutePath](#) 217
 - /complex types/
 - /CT_ApplicationNonVisualDrawingProps
 - Complex types/
 - [/CT_ApplicationNonVisualDrawingProps](#) 223
 - /CT_ContentPart
 - Complex types/
 - [/CT_ContentPart](#) 224
 - /CT_ContentPartNonVisual
 - Complex types/
 - [/CT_ContentPartNonVisual](#) 225

- /CT_Ref
 - Complex types/
 - [/CT_Ref](#) 222
- /CT_Sqref
 - Complex types/
 - [/CT_Sqref](#) 223
- /CT_Survey
 - Complex types/
 - [/CT_Survey](#) 218
- /CT_SurveyElementPr
 - Complex types/
 - [/CT_SurveyElementPr](#) 221
- /CT_SurveyQuestion
 - Complex types/
 - [/CT_SurveyQuestion](#) 219
- /CT_SurveyQuestions
 - Complex types/
 - [/CT_SurveyQuestions](#) 219
- /CT_Timeline
 - Complex types/
 - [/CT_Timeline](#) 216
- /global elements/
 - /absPath
 - Global elements/
 - [/absPath](#) 97
 - /contentPart
 - Global elements/
 - [/contentPart](#) 98
 - /list
 - Global elements/
 - [/list](#) 97
 - /survey
 - Global elements/
 - [/survey](#) 98
- /simple types/
 - /ST_QuestionFormat
 - Simple types/
 - [/ST_QuestionFormat](#) 244
 - /ST_QuestionType
 - Simple types/
 - [/ST_QuestionType](#) 243
 - /ST_SurveyPosition
 - Simple types/
 - [/ST_SurveyPosition](#) 245
- Styles
 - [extensions by part](#) 62

T

- Table definition
 - [extensions by part](#) 63
 - [table element](#) 83
 - [tableSlicerCache element](#) 91
- Timeline cache
 - [overview](#) 75
 - [part enumerations](#) 20
- Timeline styles
 - [overview](#) 76
- Timeline view
 - [overview](#) 76
 - [timelineCacheDefinition element](#) 94
 - [timelineCachePivotCaches element](#) 92

[timelineCacheRefs element](#) 91
[timelinePivotCacheDefinition element](#) 93
[timelineRefs element](#) 92
Timelines
 [overview](#) 74
 part enumerations ([section 2.1.8](#) 21, [section 2.1.9](#) 21)
 [timeline cache](#) 75
 [timeline styles](#) 76
 [timeline view](#) 76
 [timelines and cube functions](#) 76
Timelines and cube functions
 [overview](#) 76
[timelines element](#) 94
[timelineStyles element](#) 93
[Tracking changes](#) 290

V

[Vendor-extensible fields](#) 16
[Versioning](#) 15

W

[webExtensions element](#) 89
Workbook
 [extensions by part](#) 65
workbookPr element ([section 2.4.14](#) 81, [section 2.4.59](#) 94)
Worksheet
 [extensions by part](#) 65

X

[XML schema](#) 252