

[MS-XWDVSEC]: Web Distributed Authoring and Versioning (WebDAV) Protocol Security Descriptor Extensions Specification

Intellectual Property Rights Notice for Protocol Documentation

- **Copyrights.** This protocol documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the protocols, and may distribute portions of it in your implementations of the protocols or your documentation as necessary to properly document the implementation. This permission also applies to any documents that are referenced in the protocol documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the protocols. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, the protocols may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>). If you would prefer a written license, or if the protocols are not covered by the OSP, patent licenses are available by contacting protocol@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. This protocol documentation is intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it. A protocol specification does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them.

Revision Summary			
Author	Date	Version	Comments
Microsoft Corporation	April 4, 2008	0.1	Initial Availability.
Microsoft Corporation	April 25, 2008	0.2	Revised and updated property names and other technical content.
Microsoft Corporation	June 27, 2008	1.0	Initial Release.
Microsoft Corporation	August 6, 2008	1.01	Updated references to reflect date of initial release.

Table of Contents

1	Introduction	4
1.1	Glossary	4
1.2	References	5
1.2.1	Normative References	5
1.2.2	Informative References	5
1.3	Protocol Overview	5
1.4	Relationship to Other Protocols	6
1.5	Prerequisites/Preconditions	6
1.6	Applicability Statement	6
1.7	Versioning and Capability Negotiation	6
1.8	Vendor-Extensible Fields	6
1.9	Standards Assignments	6
2	Messages	6
2.1	Transport	6
2.2	Message Syntax	6
2.2.1	descriptor Property	11
2.2.2	security_descriptor Element	11
2.2.2.1	from_mapi_tlh Attribute	11
2.2.3	microsoft.security_descriptor Type	11
2.2.4	revision Element	12
2.2.5	owner Element	12
2.2.5.1	defaulted Attribute	12
2.2.6	primary_group Element	12
2.2.6.1	defaulted Attribute	12
2.2.7	dacl Element	13
2.2.7.1	defaulted Attribute	13
2.2.7.2	protected Attribute	13
2.2.7.3	autoinherited Attribute	13
2.2.8	sacl Element	13
2.2.8.1	revision Element	14
2.2.8.2	audit_always Element	14
2.2.8.3	audit_on_failure Element	14
2.2.8.4	audit_on_success Element	14
2.2.8.5	defaulted Attribute	14
2.2.8.6	protected Attribute	15
2.2.8.7	autoinherited Attribute	15
2.2.9	acl Type	15
2.2.9.1	revision Element	15
2.2.9.2	effective_aces Element	15
2.2.9.3	subcontainer_inheritable_aces Element	15
2.2.9.4	subitem_inheritable_aces Element	16
2.2.10	aces Type	16

2.2.10.1	access_allowed_ace Element.....	16
2.2.10.2	access_denied_ace Element.....	16
2.2.10.3	system_audit_ace Element.....	17
2.2.11	inheritable_aces Type.....	17
2.2.11.1	access_allowed_ace Element.....	17
2.2.11.2	access_denied_ace Element.....	17
2.2.11.3	system_audit_ace Element.....	17
2.2.12	ace_T Type.....	18
2.2.12.1	access_mask Element.....	18
2.2.12.2	sid Element.....	18
2.2.12.3	inherited Attribute.....	18
2.2.13	inheritable_ace_T Type.....	18
2.2.13.1	no_propagate_inherit Attribute.....	19
2.2.14	access_mask Element.....	19
2.2.15	sid Type.....	19
2.2.16	NT_Sid Type.....	20
2.2.16.1	string_sid Element.....	20
2.2.16.2	nt4_compatible_name Element.....	21
2.2.16.3	type Element.....	21
2.2.16.4	ad_object_guid Element.....	21
2.2.16.5	display_name Element.....	21
2.2.17	type_string Type.....	22
2.2.18	guid Type.....	22
2.2.19	bool Type.....	22
3	Protocol Details.....	22
3.1	Client/Server Details.....	22
3.1.1	Abstract Data Model.....	23
3.1.2	Timers.....	23
3.1.3	Initialization.....	23
3.1.4	Higher-Layer Triggered Events.....	23
3.1.5	Message Processing Events and Sequencing Rules.....	23
3.1.6	Timer Events.....	23
3.1.7	Other Local Events.....	23
4	Protocol Examples.....	23
4.1	Retrieving the Property.....	23
5	Security.....	26
5.1	Security Considerations for Implementers.....	26
5.2	Index of Security Parameters.....	26
6	Appendix A: Office/Exchange Behavior.....	26
	Index.....	28

1 Introduction

This document specifies an extension to the WebDAV protocol, as specified in [RFC2518], by using a standard HTTP mechanism specified in [RFC2068]. This extension specifies how to request and set the Exchange Security Descriptor via WebDAV methods PROPFIND and PROPPATCH.

1.1 Glossary

The following terms are defined in [MS-OXGLOS]:

access control entry (ACE)
access control list (ACL)
security identifier (SID)
property
XML

The following terms are specific to this document:

discretionary access control list (DACL): An **access control list (ACL)** that is controlled by the owner of an object and that specifies the access particular users or groups can have to that object.

entity: A resource that can be identified by a URL. Use of this term is consistent with that specified in [RFC2616] section 2.3.

NT Security Descriptor: The **SECURITY_DESCRIPTOR** structure that defines an entity's security. It specifies the security principal that owns the entity, the security principal(s) that can access the entity and what they can do with it, what level of audit logging has to be applied to the entity, and what type of restrictions apply to the use of the security descriptor. For more information, see [MS-DTYP] section 2.4.6.

property: A named value associated with an entity, as specified in [RFC2518] section 13.

Web Distributed Authoring and Versioning Protocol (WebDAV): The protocol specified in [RFC2518].

WebDAV client: A computer that uses the WebDAV protocol, as specified in [RFC2518], to retrieve data from the **WebDAV server**.

WebDAV server: A computer that supports the **WebDAV protocol**, as specified in [RFC2518], to and from which **WebDAV clients** can connect and retrieve data.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

- [MS-ADA1] Microsoft Corporation, "Active Directory Schema Attributes A-L", July 2006, <http://go.microsoft.com/fwlink/?LinkId=112308>.
- [MS-ADA3] Microsoft Corporation, "Active Directory Schema Attributes N-Z", July 2006, <http://go.microsoft.com/fwlink/?LinkId=112148>.
- [MS-ADTS] Microsoft Corporation, "Active Directory Technical Specification", July 2006, <http://go.microsoft.com/fwlink/?LinkId=112149>.
- [MS-DTYP] Microsoft Corporation, "Windows Data Types", March 2007, <http://go.microsoft.com/fwlink/?LinkId=111558>.
- [MS-NSPI] Microsoft Corporation, "Name Service Provider Interface (NSPI) Protocol Specification", June 2008.
- [MS-OXGLOS] Microsoft Corporation, "Office Exchange Protocols Master Glossary", June 2008.
- [MS-SAMR] Microsoft Corporation, "Security Account Manager (SAM) Remote Protocol Specification (Client-to-Server)", <http://go.microsoft.com/fwlink/?LinkId=112150>.
- [MS-SECO] Microsoft Corporation, "Windows Security Overview", December 2006, <http://go.microsoft.com/fwlink/?LinkId=112307>.
- [RFC2068] Fielding, R., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2068, January 1997, <http://www.ietf.org/rfc/rfc2068.txt>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.
- [RFC2518] Goland Y., et al., "HTTP Extensions for Distributed Authoring – WEBDAV", RFC 2518, February 1999, <http://www.ietf.org/rfc/rfc2518.txt>.
- [RFC2616] Fielding, R., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <http://www.ietf.org/rfc/rfc2616.txt>.
- [W3C-XSD1] World Wide Web Consortium, "XML Schema Part 1: Structures Second Edition", October 2004, <http://www.w3.org/TR/xmlschema-1/>.
- [W3C-XSD2] World Wide Web Consortium, "XML Schema Part 2: Datatypes Second Edition", October 2004, <http://www.w3.org/TR/xmlschema-2/>.

1.2.2 Informative References

None.

1.3 Protocol Overview

In **WebDAV** [RFC2518], **properties** are able to be retrieved and set. A particular property that the server can implement is one that represents a Security Descriptor, as specified in [MS-DTYP], in **XML**. This property and its type are documented here.

1.4 Relationship to Other Protocols

The descriptor (<http://schemas.microsoft.com/exchange/security/descriptor>) is a property based on **WebDAV**, as specified in [RFC2518] section 13. Its value is that of a security descriptor that controls access to an entity.

1.5 Prerequisites/Preconditions

For this **property** to be exposed, a **WebDAV** method to retrieve or set it **MUST** be operated against an entity in which this property exists.

1.6 Applicability Statement

This **property** is only useful when a client issuing a **WebDAV** command requires knowledge of or adjustment to access to an entity. For example, a client with sufficient permission could gate access to a particular entity to various security principals.

1.7 Versioning and Capability Negotiation

This **Security Descriptor property** exposes no new versioning capabilities beyond the base protocol of **WebDAV** and the Security Descriptor revision field, as specified in [MS-DTYP] section 2.4.6.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

There is no standards assignment for this **property** other than the ones assigned for the base **WebDAV** protocol [RFC2518].

2 Messages

This **property** adds to the set of properties, as specified in [RFC2518] section 13.

2.1 Transport

Messages are transported using HTTP, as specified in [RFC2518] and [RFC2068].

2.2 Message Syntax

This **property** is an **XML** representation of a **Security Descriptor**. The type of this property is specified by using XSD grammar, as specified in the W3C [W3C-XSD1].

```
<?xml version="1.0" encoding="utf-8" ?>
<xs:schema xmlns:S="http://schemas.microsoft.com/security/"
  xmlns:D="urn:uuid:c2f41010-65b3-11d1-a29f-00aa00c14882/"
  attributeFormDefault="qualified"
  elementFormDefault="qualified"
  targetNamespace="http://schemas.microsoft.com/security/"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```

<!-- Bool is defined to be either 1 or 0 -->
<xs:simpleType name="bool">
  <xs:restriction base="xs:boolean">
    <xs:pattern value="0|1" />
  </xs:restriction>
</xs:simpleType>

<!-- Globally Unique Identifier [MS-DTYP]
      These MUST be enclosed by curly braces, e.g.
      '{41a1a32a-4d0f-41ab-ad0c-fb344ef368fd}' -->
<xs:simpleType name="guid">
  <xs:restriction base="xs:string">
    <xs:pattern value="\{[0-9A-Fa-f]{8}-[0-9A-Fa-f]{4}-[0-9A-Fa-f]{4}-[0-
9A-Fa-f]{4}-[0-9A-Fa-f]{12}\}" />
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="type_string">
  <xs:restriction base="xs:string">
    <xs:enumeration value="user" />
    <xs:enumeration value="group" />
    <xs:enumeration value="domain" />
    <xs:enumeration value="alias" />
    <xs:enumeration value="well_known_group" />
    <xs:enumeration value="deleted_account" />
    <xs:enumeration value="invalid" />
    <xs:enumeration value="unknown" />
    <xs:enumeration value="computer" />
  </xs:restriction>
</xs:simpleType>

<xs:element name="display_name" type="xs:string" />
<xs:element name="ad_object_guid" type="S:guid" />
<xs:element name="type" type="S:type_string" />
<xs:element name="nt4_compatible_name" type="xs:string" />
<xs:element name="string_sid" type="xs:string" />

<xs:complexType name="NT_Sid">
  <xs:sequence>
    <xs:element minOccurs="0" ref="S:string_sid" />
    <xs:element minOccurs="0" ref="S:nt4_compatible_name" />
    <xs:element minOccurs="0" ref="S:type" />
    <xs:element minOccurs="0" ref="S:ad_object_guid" />
    <xs:element minOccurs="0" ref="S:display_name" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="sid">
  <xs:sequence>
    <xs:element name="sid" type="S:NT_Sid" />
  </xs:sequence>
</xs:complexType>

```

```

<xs:element name="access_mask">
  <xs:simpleType>
    <xs:restriction base="xs:hexBinary">
      <xs:minLength value="1" />
      <xs:maxLength value="8" />
    </xs:restriction>
  </xs:simpleType>
</xs:element>

<xs:complexType name="ace_T">
  <xs:sequence>
    <xs:element ref="S:access_mask" />
    <xs:element name="sid" type="S:NT_Sid" />
  </xs:sequence>
  <xs:attribute name="inherited" type="S:bool" />
</xs:complexType>

<xs:complexType name="inheritable_ace_T">
  <xs:complexContent mixed="false">
    <xs:extension base="S:ace_T">
      <xs:attribute name="no_propagate_inherit" type="S:bool" />
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

<xs:complexType name="aces">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded"
name="access_allowed_ace" type="S:ace_T" />
    <xs:element minOccurs="0" maxOccurs="unbounded"
name="access_denied_ace" type="S:ace_T" />
    <xs:element minOccurs="0" maxOccurs="unbounded"
name="system_audit_ace" type="S:ace_T" />
  </xs:sequence>
</xs:complexType>

<xs:complexType name="inheritable_aces">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded"
name="access_allowed_ace" type="S:inheritable_ace_T" />
    <xs:element minOccurs="0" maxOccurs="unbounded"
name="access_denied_ace" type="S:inheritable_ace_T" />
    <xs:element minOccurs="0" maxOccurs="unbounded"
name="system_audit_ace" type="S:inheritable_ace_T" />
  </xs:sequence>
</xs:complexType>

<xs:element name="revision" type="xs:unsignedInt" />

<xs:complexType name="acl">
  <xs:all minOccurs="0">
    <xs:element ref="S:revision" />
    <xs:element name="effective_aces" type="S:aces" />
  </xs:all>
</xs:complexType>

```



```

        <xs:element name="subcontainer_inheritable_aces"
type="S:inheritable_aces" />
        <xs:element name="subitem_inheritable_aces" type="S:inheritable_aces"
/>
    </xs:all>
</xs:complexType>

<xs:element name="audit_always" type="S:acl" />
<xs:element name="audit_on_failure" type="S:acl" />
<xs:element name="audit_on_success" type="S:acl" />

<xs:element name="sacl">
    <xs:complexType>
        <xs:sequence>
            <xs:element ref="S:revision" />
            <xs:element ref="S:audit_always" />
            <xs:element ref="S:audit_on_failure" />
            <xs:element ref="S:audit_on_success" />
        </xs:sequence>
        <xs:attribute name="defaulted" type="S:bool" />
        <xs:attribute name="protected" type="S:bool" />
        <xs:attribute name="autoinherited" type="S:bool" />
    </xs:complexType>
</xs:element>

<xs:element name="dacl">
    <xs:complexType>
        <xs:complexContent mixed="false">
            <xs:extension base="S:acl">
                <xs:attribute name="defaulted" type="S:bool" />
                <xs:attribute name="protected" type="S:bool" />
                <xs:attribute name="autoinherited" type="S:bool" />
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
</xs:element>

<xs:element name="primary_group">
    <xs:complexType>
        <xs:complexContent mixed="false">
            <xs:extension base="S:sid">
                <xs:attribute name="defaulted" type="S:bool" />
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
</xs:element>

<xs:element name="owner">
    <xs:complexType>
        <xs:complexContent mixed="false">
            <xs:extension base="S:sid">
                <xs:attribute name="defaulted" type="S:bool" />
            </xs:extension>
        </xs:complexContent>
    </xs:complexType>
</xs:element>

```

```

    </xs:complexType>
</xs:element>

<xs:element name="security_descriptor">
  <xs:complexType>
    <xs:complexContent mixed="false">
      <xs:extension base="D:microsoft.security_descriptor">
        <xs:attribute name="from_mapi_tlh" type="S:bool" />
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
</xs:element>
</xs:schema>

<!-- The base microsoft security descriptor -->
<xs:schema xmlns:S="http://schemas.microsoft.com/security/"
  xmlns:D="urn:uuid:c2f41010-65b3-11d1-a29f-00aa00c14882/"
  attributeFormDefault="qualified"
  elementFormDefault="qualified"
  targetNamespace="urn:uuid:c2f41010-65b3-11d1-a29f-00aa00c14882/"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">

  <xs:complexType name="microsoft.security_descriptor">
    <xs:all minOccurs="0">
      <xs:element ref="S:revision" />
      <xs:element ref="S:owner" />
      <xs:element ref="S:primary_group" />
      <xs:element ref="S:dacl" />
      <xs:element ref="S:sacl" />
    </xs:all>
  </xs:complexType>
</xs:schema>

<!-- The schema of the actual descriptor property
      This is the property that can be asked for via WebDAV -
->

<xs:schema xmlns:S="http://schemas.microsoft.com/security/"
  xmlns:D="urn:uuid:c2f41010-65b3-11d1-a29f-00aa00c14882/"
  attributeFormDefault="qualified"
  elementFormDefault="qualified"
  targetNamespace=
    "http://schemas.microsoft.com/exchange/security/"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">

  <xs:element name="descriptor">
    <xs:complexType>
      <xs:sequence>
        <xs:element ref="S:security_descriptor" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>

```

</xs:schema>

2.2.1 descriptor Property

Name: **descriptor**
Namespace: <http://schemas.microsoft.com/exchange/security/>
Type: **security_descriptor** (section 2.2.2)
Purpose: Contains the **security_descriptor** for entities on the server.
Description: This **property** exposes in **XML** the entity's security attributes. These attributes specify who owns the entity, who can access it and what they can do with it, what level of audit logging SHOULD be applied to the object, and what kind of restrictions apply to the use of the security descriptor. This property is a limited XML version of SECURITY_DESCRIPTOR, as specified in [MS-DTYP] section 2.4.6.

One aspect of note in the handling of this property is that the XML security descriptor format does not have a way of transmitting the SECURITY_INFORMATION field needed to set the security descriptor. Instead, the SECURITY_INFORMATION field is derived from the presence/absence of fields in the XML description. So, to set only the DACL on an object, this property is set with only a DACL in it.

Also, it is NOT possible to get this descriptor on an entity and set it back on the entity unless the caller also created the object. When the caller resets the security descriptor, the XML representation includes the owner, and the store (and NT) will not allow a normal user to set the owner of an object to anyone other than that user.

2.2.2 security_descriptor Element

Name: **security_descriptor**
Namespace: <http://schemas.microsoft.com/security/>
Type: **microsoft.security_descriptor** (section 2.2.3)
Purpose: This is the type of descriptor specified in section 2.2.1.
Description: This type extends the **microsoft.security_descriptor** (section 2.2.3), adding a bool attribute of from_mapi_tlh.

2.2.2.1 from_mapi_tlh Attribute

Name: **from_mapi_tlh**
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.19)
Purpose: Indicates that the entity for which this **Security Descriptor** applies is from a store that is accessible via MAPI-enabled clients.
Description: This value MAY be present. If present, it MUST be "1". Absence of this value implies that its value is "1".

2.2.3 microsoft.security_descriptor Type

Name: **microsoft.security_descriptor**

Namespace: urn:uuid:c2f41010-65b3-11d1-a29f-00aa00c14882/
Purpose: This is the base **Security Descriptor** on which the server security descriptor is based. It was designed to be analogous to the SECURITY_DESCRIPTOR ([MS-DTYP] section 2.4.6) and shares nearly all of the same field names.

2.2.4 revision Element

Name: **revision**
Namespace: <http://schemas.microsoft.com/security/>
Type: **unsignedInt**, as specified in [W3C-XSD2] section 3.3.22
Purpose: The revision of the **microsoft.security_descriptor** type (section 2.2.3).
Description: This field MAY be present. If present, its value MUST be set to "1". The absence of this element implies that its value is "1".

2.2.5 owner Element

Name: **owner**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: Contains the **SID** (section 2.2.15) that specifies the owner of the entity to which the **Security Descriptor** is associated.
Description: This element MAY be present. This is the same semantics as specified for Owner in [MS-DTYP] section 2.4.6.

2.2.5.1 defaulted Attribute

Name: **defaulted**
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.19)
Purpose: Set when the owner (section 2.2.5) was established by default means.
Description: This attribute MUST be present for the **owner** element (section 2.2.5). This is the same semantic that is found in [MS-DTYP] section 2.4.6, relating to the Control bit flag OD.

2.2.6 primary_group Element

Name: **primary_group**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: Contains the **SID** (section 2.2.15) that specifies the group of the entity to which the **Security Descriptor** is associated.
Description: This element MUST be present for the **owner** element (section 2.2.5). This is the same semantics as specified for Group in [MS-DTYP] section 2.4.6.

2.2.6.1 defaulted Attribute

Name: **defaulted**
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.17)
Purpose: Set when the **primary_group** (section 2.2.6) was established by default means.

Description: This attribute **MUST** be present for the **primary_group** element (section 2.2.6). This is the same semantic that is found in [MS-DTYP] section 2.4.6, relating to the Control bit flag GD.

2.2.7 dacl Element

Name: **dacl**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: The discretionary **ACL** (section 2.2.9) contains **ACEs** (section 2.2.10) that grant or deny access to principals or groups.
Description: This is the same semantics as specified for DACL in [MS-DTYP] section 2.4.5.

2.2.7.1 defaulted Attribute

Name: **defaulted**
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.17)
Purpose: Set when the DACL (section 2.2.7) was established by default means.
Description: This attribute **MUST** be present for the **dacl** element (section 2.2.7). This is the same semantic as specified in [MS-DTYP] section 2.4.6, relating to the Control bit flag DD.

2.2.7.2 protected Attribute

Name: **protected**
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.17)
Purpose: Set when the DACL (section 2.2.7) should be protected from inherit operations.
Description: This attribute **MUST** be present for the **dacl** element (section 2.2.7). This is the same semantic as specified in [MS-DTYP] section 2.4.6, relating to the Control bit flag PD.

2.2.7.3 autoinherited Attribute

Name: **autoinherited**
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.17)
Purpose: Set when the **ACL** (section 2.2.7) was created through inheritance.
Description: This attribute **MUST** be present for the **dacl** element (section 2.2.7). This is the same semantic as specified in [MS-DTYP] section 2.4.6, relating to the Control bit flag DI.

2.2.8 sacl Element

Name: **sacl**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: The system **ACL** (section 2.2.9) contains auditing **ACEs** (section 2.2.10).

Description: This is the same semantics as specified for system ACL in [MS-DTYP] section 2.4.5.

2.2.8.1 revision Element

Name: **revision**
Namespace: <http://schemas.microsoft.com/security/>
Type: **unsignedInt** as specified in [W3C-XSD2] section 3.3.22
Purpose: This attribute MAY be present for the **sacl** element (section 2.2.8). Serves the same purpose as the **AclRevision** element found in [MS-DTYP] section 2.4.5 and shares the same appropriate values.

2.2.8.2 audit_always Element

Name: **audit_always**
Namespace: <http://schemas.microsoft.com/security/>
Type: **acl** (section 2.2.9)
Purpose: The set of **ACEs** to generate audit messages for access attempts.
Description: This is the same semantic as specified in [MS-DTYP] section 2.4.4.1: AceFlags FAILED_ACCESS_ACE_FLAG and SUCCESSFUL_ACCESS_ACE_FLAG.

2.2.8.3 audit_on_failure Element

Name: **audit_on_failure**
Namespace: <http://schemas.microsoft.com/security/>
Type: **acl** (section 2.2.9)
Purpose: The set of **ACEs** to generate audit messages for failed access attempts.
Description: This is used in place of [MS-DTYP] section 2.4.4.1 AceFlag FAILED_ACCESS_ACE_FLAG and has the same semantic meaning.

2.2.8.4 audit_on_success Element

Name: **audit_on_success**
Namespace: <http://schemas.microsoft.com/security/>
Type: **acl** (section 2.2.9)
Purpose: The set of **ACEs** to generate audit messages for successful access attempts.
Description: This is used in place of [MS-DTYP] section 2.4.4.1 AceFlag SUCCESSFUL_ACCESS_ACE_FLAG and has the same semantic meaning.

2.2.8.5 defaulted Attribute

Name: **defaulted**
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.17)
Purpose: Set when the system **ACL** (section 2.2.8) was established by default means.
Description: This attribute MUST be present for the **sacl** element (section 2.2.8). This is the same semantic that is specified in [MS-DTYP] section 2.4.6, relating to the Control bit flag SD.

2.2.8.6 protected Attribute

Name: protected
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.17)
Purpose: Set when the system **ACL** (section 2.2.8) should be protected from inherit operations.
Description: This attribute **MUST** be present for the **sacl** element (section 2.2.8). This is the same semantic that is specified in [MS-DTYP] section 2.4.6, relating to the Control bit flag PS.

2.2.8.7 autoinherited Attribute

Name: autoinherited
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.17)
Purpose: Set when the system **ACL** (section 2.2.8) was created by inheritance.
Description: This attribute **MUST** be present for the **sacl** element (section 2.2.8). This is the same semantic that is specified in [MS-DTYP] section 2.4.6, relating to the Control bit flag SI.

2.2.9 acl Type

Name: **acl**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: **Access Control List**
Description: Contains a list of **ACEs**. This is analogous to **ACL**, as specified in [MS-DTYP] section 2.4.5.

2.2.9.1 revision Element

Name: **revision**
Namespace: <http://schemas.microsoft.com/security/>
Type: **unsignedInt**, as specified in [W3C-XSD] section 3.3.22
Purpose: Indicates the version of the **ACL** Type (section 2.2.9).
Description: This element **MAY** exist. Serves the same purpose as the **AclRevision** element found in [MS-DTYP] section 2.4.5 and shares the same appropriate values.

2.2.9.2 effective_aces Element

Name: **effective_aces**
Namespace: <http://schemas.microsoft.com/security/>
Type: **aces** (section 2.2.10)
Purpose: This element **MAY** exist. Contains a list of **ACEs** that affect the entity of which **descriptor** (section 2.2.1) is a property.

2.2.9.3 subcontainer_inheritable_aces Element

Name: **subcontainer_inheritable_aces**

Namespace: <http://schemas.microsoft.com/security/>
Type: **inheritable_aces** (section 2.2.11)
Purpose: Contains a list of **ACEs** such that child objects that are containers, such as folders, inherit these ACEs as effective ACEs (section 2.2.9.2).
Description: This element **MAY** exist. Semantically the same as having each ACE within here having the **CONTAINER_INHERIT_ACE** flag set on the **AceFlags** as defined in [MS-DTYP] section 2.4.4.1.

2.2.9.4 subitem_inheritable_aces Element

Name: **subitem_inheritable_aces**
Namespace: <http://schemas.microsoft.com/security/>
Type: **inheritable_aces** (section 2.2.11)
Purpose: Contains a list of **ACEs** such that non-container child objects, such as attachments, inherit these ACEs as effective ACEs (section 2.2.9.2).
Description: This element **MAY** exist. Semantically the same as having each ace within here having the **OBJECT_INHERIT_ACE** flag set on them as specified in [MS-DTYP] section 2.4.4.1.

2.2.10 aces Type

Name: **aces**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: Contains a list of non-inheritable **ACES** (section 2.2.10.1 through 2.2.10.6)
Description: All the ACEs in this type are semantically the same as having the flag **ACE_INHERITED_OBJECT_TYPE** not set as specified in [MS-DTYP] section 2.4.4.2.

2.2.10.1 access_allowed_ace Element

Name: **access_allowed_ace**
Namespace: <http://schemas.microsoft.com/security/>
Type: **ace_T** (section 2.2.12)
Purpose: Allows access to an entity for a specific trustee identified by a SID (section 2.2.17).
Description: This **ACE** is only allowed on DACLs (section 2.2.7). This element **MAY** exist. This ACE follows the same semantics as **ACCESS_ALLOWED_ACE** as specified in [MS-DTYP] section 2.4.4.2.

2.2.10.2 access_denied_ace Element

Name: **access_denied_ace**
Namespace: <http://schemas.microsoft.com/security/>
Type: **ace_T** (section 2.2.12)
Purpose: Denies access to an entity for a specific trustee identified by a SID (section 2.2.17).

Description: This ACE is allowed only on DACLs (section 2.2.7). This element MAY exist. This ACE follows the same semantics as ACCESS_DENIED_ACE, as specified in [MS-DTYP] section 2.4.4.4.

2.2.10.3 system_audit_ace Element

Name: **system_audit_ace**
Namespace: <http://schemas.microsoft.com/security/>
Type: **ace_T** (section 2.2.12)
Purpose: System-audit ace.
Description: This ACE is only allowed on system ACLs (section 2.2.8). This element MAY exist. This ACE follows the same semantics as SYSTEM_AUDIT_ACE, as specified in [MS-DTYP] section 2.4.4.9.

2.2.11 inheritable_aces Type

Name: **inheritable_aces**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: Contains a list of inheritable aces.
Description: How these ACEs are inherited is declared by the usage of this type in either subitem_inheritable_aces (section 2.2.9.4) or subcontainer_inheritable_aces (section 2.2.9.3).

2.2.11.1 access_allowed_ace Element

Name: **access_allowed_ace**
Namespace: <http://schemas.microsoft.com/security/>
Type: **inheritable_ace_T** (section 2.2.15)
Purpose: Allows access to an entity for a specific trustee identified by a SID (section 2.2.17).
Description: This element MAY exist. This ACE is only allowed on DACLs (section 2.2.7). This ace follows the same semantics as ACCESS_ALLOWED_ACE, as specified in [MS-DTYP] section 2.4.4.2.

2.2.11.2 access_denied_ace Element

Name: **access_denied_ace**
Namespace: <http://schemas.microsoft.com/security/>
Type: **inheritable_ace_T** (section 2.2.13)
Purpose: Denies access to an entity for a specific trustee identified by a SID (section 2.2.17).
Description: This element MAY exist. This ACE is only allowed on DACLs (section 2.2.7). This ace follows the same semantics as ACCESS_DENIED_ACE, as specified in [MS-DTYP] section 2.4.4.4.

2.2.11.3 system_audit_ace Element

Name: **system_audit_ace**
Namespace: <http://schemas.microsoft.com/security/>

Type: **inheritable_ace_T** (section 2.2.15)
Purpose: System-audit ace.
Description: This element MAY exist. This **ACE** is only allowed on system ACLs (section 2.2.8). This ACE follows the same semantics as **SYSTEM_AUDIT_ACE**, as specified in [MS-DTYP] section 2.4.4.9.

2.2.12 ace_T Type

Name: **ace_T**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: The base type for **ACEs**.
Description: The type for access control entries found in ACEs (section 2.2.10).

2.2.12.1 access_mask Element

Name: **access_mask**
Namespace: <http://schemas.microsoft.com/security/>
Type: **access_mask** (section 2.2.14)
Purpose: Encodes the rights to an entity for a security principal.
Description: This element **MUST** exist on all **ACEs**. The actual flags for encoding these rights are in section 2.2.14.

2.2.12.2 sid Element

Name: **sid**
Namespace: <http://schemas.microsoft.com/security/>
Type: **sid** (section 2.2.15)
Purpose: Identifies a security principal.
Description: This element **MUST** exist on all **ACES**. Semantically the same as **SID** as specified in section 2.4.4 [MS-DTYP].

2.2.12.3 inherited Attribute

Name: **inherited**
Namespace: <http://schemas.microsoft.com/security/>
Type: **bool** (section 2.2.19)
Purpose: Indicates that the **ACE** was inherited.
Description: This attribute **MUST** exist. Semantically the same as the AceFlags **INHERITED_ACE** as specified in [MS-DTYP] section 2.4.4.1.

2.2.13 inheritable_ace_T Type

Name: **inheritable_ace_T**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: The base type for all inheritable **ACEs** (section 2.2.11)
Description: ACEs of this type are the equivalent of having the specific AceFlags **CONTAINER_INHERIT_ACE** or **OBJECT_INHERIT_ACE** set as specified in [MS-DTYP] section 2.4.4.1.

2.2.13.1 no_propagate_inherit Attribute

Name: no_propagate_inherit
 Namespace: <http://schemas.microsoft.com/security/>
 Type: **bool** (section 2.2.17)
 Purpose: Declares that an inherited ACE is not inheritable.
 Description: This attribute MUST exist. This is semantically the same as NO_PROPAGATE_INHERIT_ACE as found in section 2.4.4.1 [MS-DTYP] for the AceFlags CONTAINER_INHERIT_ACE and OBJECT_INHERIT_ACE.

2.2.14 access_mask Element

Name: **access_mask**
 Namespace: <http://schemas.microsoft.com/security/>
 Type: **hexBinary** [W3C-XSD2] section 3.2.15, but limited to between 1 and 8 digits.
 Purpose: 32-bit set of flags that are used to encode the user rights to an object. An access mask is used both to encode the rights to an object assigned to a principal and to encode the requested access when opening an object.
 Description: This element MUST exist for all ACEs. Exchange uses the same definition of the top 16 bits that Windows does in [MS-DTYP] section 2.4.3. The lower 16 bits are as follows:

MSB																LSB
15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	
				V	DOI	WOP	WA	RA		E	WP	RP	AM	WB	RB	

Value	Description
RB	Read Body
WB	Write Body
AM	Append Message
RP	Read Property
WP	Write Property
E	Execute
RA	Read Attributes
WA	Write Attributes
WOP	Write Own Property
DOI	Delete Own Item
V	View Item

2.2.15 sid Type

Name: **sid**
 Namespace: <http://schemas.microsoft.com/security/>
 Purpose: Contains the security identifier that uniquely identifies a security principal.

Description: This specific type simply wraps an **NT_Sid** (section 2.2.18) with a “<sid>” element.

2.2.16 NT_Sid Type

Name: **NT_Sid**

Namespace: <http://schemas.microsoft.com/security/>

Purpose: Contains a security identifier.

Description: It is important to understand more about the XML representation of NT security identities (SIDs). Note that it can be seen that a number of different pieces of information about the security identity are available.

If you retrieve from the **WebDAV server** the XML representation, all of the following elements will appear in the representation of the **NT_Sid** (so long as they are available):

<string_sid>	(see section 2.2.18.1)
<nt4_compatible_name>	(see section 2.2.18.2)
<type>	(see section 2.2.18.3)
<ad_object_guid>	(see section 2.2.18.4)
<display_name>	(see section 2.2.18.5)

In some cases, less information is returned. For example, if the **SID** cannot be looked up, you would see only the string SID. For some built-in NT accounts, you will only get the **string_sid**, **nt4_compatible_name**, and **type**.

If the WebDAV client sets the XML representation, it does not have to give all the elements providing that one of the following elements is sufficient:

<string_sid>	(see section 2.2.18.1)
<nt4_compatible_name>	(see section 2.2.18.2)
<ad_object_guid>	(see section 2.2.18.4)
<display_name>	(see section 2.2.18.5)

The WebDAV server will only use one of the elements the WebDAV client gives it to determine the SID. It SHOULD pick the cheapest element to work from. The notion of cost of determining which SID the client means is according to the order of the above list – so use **string_sid** if it is known, else **nt4_compatible_name**, and so on. As a last resort the client MAY use **display_name**, but because of the ambiguity problems it would probably not be a good choice.

2.2.16.1 string_sid Element

Name: **string_sid**

Namespace: <http://schemas.microsoft.com/security/>

Type: **string** [W3C-XSD2] section 3.2.1.

Purpose: Identifies a security principal.

Description: This element MAY exist for any **SID** (section 2.2.15). This is the string representation of the SID as specified in section 2.4.2 [MS-DTYP].

2.2.16.2 **nt4_compatible_name** Element

Name: **nt4_compatible_name**
Namespace: <http://schemas.microsoft.com/security/>
Type: **string** [W3C-XSD2] section 3.2.1
Purpose: Identifies a security principal.
Description: This element MAY exist for any **SID** (section 2.2.15). Contains a security principal as either a fully qualified account name (domain_name/user_name) or a user principal name (user_name@domain_name) as specified in section 2.2[MS-SECO].

2.2.16.3 **type** Element

Name: **type**
Namespace: <http://schemas.microsoft.com/security/>
Type: **type_string** (section 2.2.17)
Purpose: Value that specifies the type of **SID**.
Description: This element MAY exist for any **SID** (section 2.2.15). The enumeration of values is found in section 2.2.19.

2.2.16.4 **ad_object_guid** Element

Name: **ad_object_guid**
Namespace: <http://schemas.microsoft.com/security/>
Type: **guid** (section 2.2.18)
Purpose: Identifies a security principal.
Description: This element MAY exist for any **SID** (section 2.2.15). This element's value is a string representation of the **objectGuid** property found in [MS-ADA3] section 2.43. This property is included so clients that allow users to pick an entry from the directory service [MS-OLABK] can specify the entry by giving the **objectGuid** property.

2.2.16.5 **display_name** Element

Name: **display_name**
Namespace: <http://schemas.microsoft.com/security/>
Type: **string** [W3C-XSD2] section 3.2.1
Purpose: Identifies a security principal.
Description: This element MAY exist for any **SID** (section 2.2.15). This element's value is a display name that clients can display in the UI. It comes from the **PidTagDisplayName**, as found in [MS-NSPI]. It can also be read from the directory service as **displayName** section 2.175 [MS-ADA1]. The downside of identifying a security principal using this element is that it MAY not be unique.

2.2.17 type_string Type

Name: **type_string**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: Specifies the possible type of **NT_SID** (section 2.2.18).
Description: Can be one of the following values:

Value	Meaning
user	A user SID.
group	A group SID.
domain	A domain SID.
alias	An alias SID.
well_known_group	A SID for a well-known group.
deleted_account	A SID for a deleted account.
invalid	A SID that is not valid.
unknown	A SID of unknown type.
computer	A SID for a computer.

These values are semantically the same as found in the enumeration **SID_NAME_USE**, as defined in [MS-SAMR] section 2.2.2.6.

2.2.18 guid Type

Name: **guid**
Namespace: <http://schemas.microsoft.com/security/>
Purpose: globally unique identifier.
Description: Used to identify various things. Semantically the same as [MS-DTYP] section 2.3.2.1.

2.2.19 bool Type

Name : **bool**
Namespace : <http://schemas.microsoft.com/security/>
Type : **boolean** [W3C-XSD2]
Purpose : To indicate a **Boolean** state.
Description: This has the same meaning as specified in section 3.2.2 [W3C-XSD2], but is constrained to just the values of 0 and 1 .

3 Protocol Details

3.1 Client/Server Details

No additional detailed interaction between client and server is beyond that as specified in the **WebDAV** [RFC2518] protocol.

It is important to note that the descriptor property (section 2.2.1) does define access control access to the targeted entity. It is possible for the client to set this property in such a way as to deny or grant access to the targeted entity, so care has to be taken to ensure that the access set is what is desired.

Also, it bears reiterating that the descriptor property that is retrieved from the server MAY be more complete than what is required of the client to set it. In section 2.2.1 it is mentioned that the client does not need to set the entire security descriptor in order to just modify the **DAACL** (section 2.2.7). Another way that the property might differ is in the **SID** (section 2.2.16) values. The server attempts to generate all versions of the security principals identifiers, but the client MAY only generate one of them. It is encouraged that the client generate the most precise one as discussed in the SID section (2.2.16) in order to be as accurate as possible.

3.1.1 Abstract Data Model

No additional data is required beyond that as specified in **WebDAV** [RFC2518].

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

No additional higher-layer triggered events exist beyond those in **WebDAV**, and the behavior of any existing higher-layer triggered events is unchanged by this extension.

3.1.5 Message Processing Events and Sequencing Rules

The client sends a **WebDAV** command that retrieves or sets the value of this property. The sequence rules are those that are found for any property as specified in **WebDAV** [RFC2518] section 13.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

4 Protocol Examples

This section gives examples of how to retrieve and set this property.

4.1 Retrieving the Property

This security descriptor MAY be retrieved via a standard WebDAV PROPFIND request by asking for the property:

<http://schemas.microsoft.com/exchange/security/descriptor>

For example, the property *descriptor* MAY look like:

```

    <d:descriptor xmlns:d="http://schemas.microsoft.com/exchange/security/">
      <S:security_descriptor
xmlns:S="http://schemas.microsoft.com/security/"
xmlns:D="urn:uuid:c2f41010-65b3-11d1-a29f-00aa00c14882/"
D:dt="microsoft.security_descriptor" S:from_mapi_tlh="1">
        <S:revision>1</S:revision>
        <S:owner S:defaulted="0">
          <S:sid>
            <S:string_sid>S-1-5-21-2082262111-2968666075-236047801-
1111</S:string_sid>
            <S:type>user</S:type>
            <S:nt4_compatible_name>ELZCHU-
DOM\bob</S:nt4_compatible_name>
            <S:ad_object_guid>{138bfc4d-48e0-4d29-9de6-
643ecb7314f1}</S:ad_object_guid>
            <S:display_name>bob</S:display_name>
          </S:sid>
        </S:owner>
        <S:primary_group S:defaulted="0">
          <S:sid>
            <S:string_sid>S-1-5-21-2082262111-2968666075-236047801-
513</S:string_sid>
            <S:type>group</S:type>
            <S:nt4_compatible_name>ELZCHU-DOM\Domain
Users</S:nt4_compatible_name>
            <S:ad_object_guid>{f2a02601-c596-4fd2-9543-
d770ba31d9e5}</S:ad_object_guid>
          </S:sid>
        </S:primary_group>
        <S:dacl S:defaulted="1" S:protected="0" S:autoinherited="1">
          <S:revision>2</S:revision>
          <S:effective_aces>
            <S:access_allowed_ace S:inherited="1">
              <S:access_mask>1f0fbf</S:access_mask>
              <S:sid>
                <S:string_sid>S-1-5-21-2082262111-2968666075-236047801-
500</S:string_sid>
                <S:type>user</S:type>
                <S:nt4_compatible_name>ELZCHU-
DOM\Administrator</S:nt4_compatible_name>
                <S:ad_object_guid>{41a1a32a-4d0f-41ab-ad0c-
fb344ef368fd}</S:ad_object_guid>
                <S:display_name>Administrator</S:display_name>
              </S:sid>
            </S:access_allowed_ace>
            <S:access_allowed_ace S:inherited="1">
              <S:access_mask>1f0fbf</S:access_mask>
              <S:sid>
                <S:string_sid>S-1-5-7</S:string_sid>
                <S:type>well_known_group</S:type>
                <S:nt4_compatible_name>NT AUTHORITY\ANONYMOUS
LOGON</S:nt4_compatible_name>
                <S:ad_object_guid>{ff158509-ee41-4c44-98c1-
affd7edf6a83}</S:ad_object_guid>

```



```

        </S:sid>
        </S:access_allowed_ace>
        <S:access_allowed_ace S:inherited="1">
          <S:access_mask>1f0fbf</S:access_mask>
          <S:sid>
            <S:string_sid>S-1-1-0</S:string_sid>
            <S:type>well_known_group</S:type>
        </S:access_allowed_ace>
<S:nt4_compatible_name>\Everyone</S:nt4_compatible_name>
        <S:ad_object_guid>{aa5d6b3e-3546-4f9e-8530-59ad567c6dd8}</S:ad_object_guid>
        </S:sid>
        </S:access_allowed_ace>
        </S:effective_aces>
        </S:dacl>
        </S:security_descriptor>
</d:descriptor>

```

To set a security descriptor using the **WebDAV PROPPATCH**, the property **MAY** look like this:

```

<?xml version='1.0'?>
<d:descriptor xmlns:d='http://schemas.microsoft.com/exchange/security/'>
  <S:security_descriptor xmlns:data='urn:uuid:c2f41010-65b3-11d1-a29f-00aa00c14882/' data:dt='microsoft.security_descriptor'>
    <S:dacl xmlns:S="http://schemas.microsoft.com/security/"
S:defaulted="0" S:protected="0" S:autoinherited="0">
      <S:effective_aces>
        <S:access_allowed_ace>
          <S:access_mask>1f0fbf</S:access_mask>
          <S:sid>
            <S:string_sid>S-1-5-21-2082262111-2968666075-236047801-500</S:string_sid>
          </S:sid>
        </S:access_allowed_ace>
        <S:access_allowed_ace>
          <S:access_mask>1f0fbf</S:access_mask>
          <S:sid>
            <S:string_sid>S-1-5-7</S:string_sid>
          </S:sid>
        </S:access_allowed_ace>
        <S:access_allowed_ace>
          <S:access_mask>1208a9</S:access_mask>
          <S:sid>
            <S:ad_object_guid>{9F4AC28A-2FD0-475E-9736-A9AF92E6612F}</S:ad_object_guid>
          </S:sid>
        </S:access_allowed_ace>
        <S:access_allowed_ace>
          <S:access_mask>1200a9</S:access_mask>
          <S:sid>
            <S:string_sid>S-1-1-0</S:string_sid>
          </S:sid>
        </S:access_allowed_ace>

```

```

    <S:access_denied_ace>
      <S:access_mask>d0f16</S:access_mask>
      <S:sid>
        <S:string_sid>S-1-1-0</S:string_sid>
      </S:sid>
    </S:access_denied_ace>
  </S:effective_aces>
  <S:subcontainer_inheritable_aces>
    <S:access_allowed_ace>
      <S:access_mask>1208a9</S:access_mask>
      <S:sid>
        <S:ad_object_guid>{9F4AC28A-2FD0-475E-9736-
A9AF92E6612F}</S:ad_object_guid>
      </S:sid>
    </S:access_allowed_ace>
  </S:subcontainer_inheritable_aces>
  <S:subitem_inheritable_aces>
    <S:access_allowed_ace>
      <S:access_mask>1208a9</S:access_mask>
      <S:sid>
        <S:ad_object_guid>{9F4AC28A-2FD0-475E-9736-
A9AF92E6612F}</S:ad_object_guid>
      </S:sid>
    </S:access_allowed_ace>
  </S:subitem_inheritable_aces>
</S:dacl>
</S:security_descriptor>
</d:descriptor>

```

5 Security

5.1 Security Considerations for Implementers

This property has no security considerations beyond any as specified in **WebDAV** [RFC2518] section 17, HTTP [RFC2616] section 15, and [MS-DTYP] section 4.

5.2 Index of Security Parameters

None.

6 Appendix A: Office/Exchange Behavior

The information in this specification is applicable to the following versions of Office/Exchange:

- Office 2003 with Service Pack 3 applied
- Exchange 2003 with Service Pack 2 applied
- Office 2007 with Service Pack 1 applied
- Exchange 2007 with Service Pack 1 applied

Exceptions, if any, are noted below. Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies Office/Exchange behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies Office/Exchange does not follow the prescription.

Index

- Applicability statement, 6
- Client/server details, 22
- Fields, vendor-extensible, 6
- Glossary, 4
- Index of security parameters, 26
- Informative references, 5
- Introduction, 4
- Message syntax, 6
- Messages, 6
- Normative references, 5
- Office/Exchange behavior, 26
- Overview, 5
- Preconditions, 6
- Prerequisites, 6
- Protocol details, 22
 - Client/server details, 22
- Protocol Examples, 23
- References, 5
 - Informative references, 5
 - Normative references, 5
- Relationship to other protocols, 6
- Retrieving the property, 23
- Security, 26
 - Considerations for implementers, 26
 - Index of security parameters, 26
- Security considerations for implementers, 26
- Standards assignments, 6
- Transport, 6
 - Message syntax, 6
- Vendor-extensible fields, 6
- Versioning and capability negotiation, 6