

[MS-HTML401E]:

Internet Explorer Extensions to HTML 4.01 and DOM Level 2 HTML Specifications

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
3/26/2010	1.0	New	Released new document.
4/16/2010	1.1	Major	Significantly changed the technical content.
5/26/2010	1.2	Major	Significantly changed the technical content.
6/29/2010	1.21	Editorial	Changed language and formatting in the technical content.
9/8/2010	1.3	Major	Significantly changed the technical content.
10/13/2010	1.4	Minor	Clarified the meaning of the technical content.
2/10/2011	2.0	None	Introduced no new technical or language changes.
2/22/2012	3.0	Major	Significantly changed the technical content.
7/25/2012	3.1	Minor	Clarified the meaning of the technical content.
6/26/2013	4.0	Major	Significantly changed the technical content.
3/31/2014	4.0	None	No changes to the meaning, language, or formatting of the technical content.
1/22/2015	5.0	Major	Updated for new product version.
7/7/2015	5.1	Minor	Clarified the meaning of the technical content.
11/2/2015	5.2	Minor	Clarified the meaning of the technical content.
3/22/2016	5.3	Minor	Clarified the meaning of the technical content.
11/2/2016	5.3	None	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1	Introduction	8
1.1	Glossary	8
1.2	References	8
1.2.1	Normative References	8
1.2.2	Informative References	8
1.3	Extension Overview (Synopsis)	9
1.3.1	Element Behaviors and HTML Components.....	16
1.3.2	Organization of This Documentation.....	17
1.4	Relationship to Standards and Other Extensions	18
1.5	Applicability Statement	18
2	Extensions.....	20
2.1	Elements.....	20
2.1.1	?IMPORT?	20
2.1.2	COMMENT.....	21
2.1.3	MARQUEE	21
2.1.4	NOBR.....	22
2.1.5	PUBLIC:ATTACH	22
2.1.6	PUBLIC:COMPONENT	22
2.1.7	PUBLIC:DEFAULTS	23
2.1.8	PUBLIC:EVENT	23
2.1.9	PUBLIC:METHOD	23
2.1.10	PUBLIC:PROPERTY	24
2.2	Interfaces	24
2.2.1	Internet Explorer-Only Interfaces	25
2.2.1.1	HTCComponentElement	26
2.2.1.2	HTCElementBehaviorDefaults	26
2.2.1.3	HTCPropertyElement	26
2.2.1.4	HTMLBlockElement.....	26
2.2.1.5	HTMLCommentElement.....	26
2.2.1.6	HTMLDDElement	27
2.2.1.7	HTMLDTElement	27
2.2.1.8	HTMLMarqueeElement	28
2.2.2	DOM Interfaces	29
2.2.2.1	HTMLAnchorElement	29
2.2.2.2	HTMLAreaElement.....	30
2.2.2.3	HTMLAreasCollection	30
2.2.2.4	HTMLBodyElement	31
2.2.2.5	HTMLButtonElement.....	31
2.2.2.6	HTMLCollection	32
2.2.2.7	HTMLDivElement.....	32
2.2.2.8	HTMLDocument	32
2.2.2.9	HTMLElement	33
2.2.2.10	HTMLFieldSetElement	34
2.2.2.11	HTMLFormElement	35
2.2.2.12	HTMLFrameElement	35
2.2.2.13	HTMLFrameSetElement.....	36
2.2.2.14	HTMLHeadingElement.....	36
2.2.2.15	HTMLHRElement	37
2.2.2.16	HTMLIFrameElement	37
2.2.2.17	HTMLImageElement	38
2.2.2.18	HTMLInputElement.....	38
2.2.2.19	HTMLIsIndexElement.....	39
2.2.2.20	HTMLLabelElement.....	40
2.2.2.21	HTMLLegendElement	40

2.2.2.22	HTMLLinkElement	40
2.2.2.23	HTMLMetaElement	41
2.2.2.24	HTMLObjectElement	41
2.2.2.25	HTMLOptionElement	42
2.2.2.26	HTMLParagraphElement	42
2.2.2.27	HTMLSelectElement	42
2.2.2.28	HTMLSpanElement	43
2.2.2.29	HTMLStyleElement	43
2.2.2.30	HTMLTableCaptionElement	43
2.2.2.31	HTMLTableCellElement	44
2.2.2.32	HTMLTableElement	44
2.2.2.33	HTMLTableRowElement	45
2.2.2.34	HTMLTableSectionElement	45
2.2.2.35	HTMLTextAreaElement	46
2.3	Attributes	46
2.3.1	DOM and Content Attributes	51
2.3.1.1	action	51
2.3.1.2	align	52
2.3.1.3	allowTransparency	52
2.3.1.4	alt	53
2.3.1.5	background	53
2.3.1.6	BaseHref	53
2.3.1.7	behavior	53
2.3.1.8	bgColor	54
2.3.1.9	bgProperties	54
2.3.1.10	border	54
2.3.1.11	borderColor	54
2.3.1.12	borderColorDark	55
2.3.1.13	borderColorLight	55
2.3.1.14	bottomMargin	56
2.3.1.15	canHaveHTML	56
2.3.1.16	charset	56
2.3.1.17	classid	56
2.3.1.18	clear	56
2.3.1.19	color	57
2.3.1.20	cols	57
2.3.1.21	dataFld	57
2.3.1.22	dataFormatAs	58
2.3.1.23	dataPageSize	59
2.3.1.24	dataSrc	59
2.3.1.25	direction	60
2.3.1.26	dynsrc	60
2.3.1.27	frameBorder	60
2.3.1.28	frameSpacing	61
2.3.1.29	height	61
2.3.1.30	href	62
2.3.1.31	hspace	62
2.3.1.32	leftMargin	62
2.3.1.33	loop	63
2.3.1.34	lowsrc	63
2.3.1.35	Methods	64
2.3.1.36	name	64
2.3.1.37	noResize	64
2.3.1.38	noWrap	64
2.3.1.39	rightMargin	65
2.3.1.40	scroll	65
2.3.1.41	scrollAmount	65
2.3.1.42	scrollDelay	66

2.3.1.43	start.....	66
2.3.1.44	tabStop	66
2.3.1.45	topMargin	66
2.3.1.46	trueSpeed	67
2.3.1.47	urn.....	67
2.3.1.48	vAlign.....	67
2.3.1.49	value.....	68
2.3.1.50	viewInheritStyle.....	68
2.3.1.51	viewMasterTab	68
2.3.1.52	vspace.....	68
2.3.1.53	width.....	69
2.3.1.54	wrap	69
2.3.2	DOM Attributes Only	69
2.3.2.1	alinkColor	69
2.3.2.2	altHtml	70
2.3.2.3	contentWindow	70
2.3.2.4	dir.....	70
2.3.2.5	encoding.....	71
2.3.2.6	fgColor	71
2.3.2.7	fileCreatedDate.....	71
2.3.2.8	fileModifiedDate	71
2.3.2.9	fileSize	71
2.3.2.10	fileUpdatedDate	72
2.3.2.11	hash.....	72
2.3.2.12	host	72
2.3.2.13	hostname.....	72
2.3.2.14	indeterminate.....	73
2.3.2.15	isDisabled	73
2.3.2.16	isMultiLine.....	73
2.3.2.17	linkColor	73
2.3.2.18	contentType.....	74
2.3.2.19	nameProp	74
2.3.2.20	object.....	75
2.3.2.21	parentDocument	75
2.3.2.22	pathname	75
2.3.2.23	port.....	75
2.3.2.24	protocol	75
2.3.2.25	protocolLong	76
2.3.2.26	search	76
2.3.2.27	status.....	76
2.3.2.28	styleSheet.....	77
2.3.2.29	uniqueID.....	77
2.3.2.30	uniqueNumber.....	78
2.3.2.31	url.....	79
2.3.2.32	viewLink	79
2.3.2.33	vlinkColor	80
2.3.3	Content Attributes Only	80
2.3.3.1	application	80
2.3.3.2	atomicselection.....	80
2.3.3.3	event	80
2.3.3.4	for	81
2.3.3.5	get.....	81
2.3.3.6	implementation.....	81
2.3.3.7	internalName.....	82
2.3.3.8	lightWeight	82
2.3.3.9	literalContent	82
2.3.3.10	namespace.....	83
2.3.3.11	onevent	83

2.3.3.12	persist	83
2.3.3.13	put	84
2.3.3.14	supportsEditMode	84
2.3.3.15	tagName	84
2.3.3.16	unselectable	84
2.3.3.17	viewLinkContent	84
2.3.3.18	xmlns	85
2.3.4	Event Attributes	85
2.3.4.1	onactivate	85
2.3.4.2	onafterupdate	86
2.3.4.3	onbeforeactivate	86
2.3.4.4	onbeforecopy	86
2.3.4.5	onbeforecut	87
2.3.4.6	onbeforedeactivate	87
2.3.4.7	onbeforeeditfocus	87
2.3.4.8	onbeforepaste	88
2.3.4.9	onbeforeunload	88
2.3.4.10	onbeforeupdate	88
2.3.4.11	onbounce	89
2.3.4.12	oncellchange	89
2.3.4.13	oncontentready	89
2.3.4.14	oncontentsave	90
2.3.4.15	oncontrolselect	90
2.3.4.16	oncopy	90
2.3.4.17	oncut	91
2.3.4.18	ondataavailable	91
2.3.4.19	ondatasetchanged	91
2.3.4.20	ondatasetcomplete	92
2.3.4.21	ondeactivate	92
2.3.4.22	ondetach	92
2.3.4.23	ondocumentready	92
2.3.4.24	onerrorupdate	93
2.3.4.25	onfilterchange	93
2.3.4.26	onfinish	93
2.3.4.27	onfocusin	93
2.3.4.28	onfocusout	94
2.3.4.29	onhelp	94
2.3.4.30	onlosecapture	94
2.3.4.31	onmouseenter	95
2.3.4.32	onmouseleave	95
2.3.4.33	onmove	95
2.3.4.34	onmoveend	96
2.3.4.35	onmovestart	96
2.3.4.36	onpaste	96
2.3.4.37	onpropertychange	97
2.3.4.38	onresizeend	97
2.3.4.39	onresizestart	97
2.3.4.40	onrowenter	98
2.3.4.41	onrowexit	98
2.3.4.42	onrowsdelete	98
2.3.4.43	onrowsinserted	99
2.3.4.44	onselect	99
2.3.4.45	onselectstart	99
2.3.4.46	onstart	100
2.4	Methods	100
2.4.1	add	100
2.4.2	item	101
2.4.3	moveRow	101

2.4.4	namedItem	102
2.4.5	remove	102
2.4.6	setActive	102
2.4.7	tags	103
2.4.8	urns	103
2.5	Collections	104
2.5.1	all	104
2.5.2	cells	104
2.5.3	frames	104
3	Security Considerations	105
4	Appendix A: Product Behavior	106
5	Change Tracking	107
6	Index	108

1 Introduction

This document describes extensions provided by Microsoft web browsers for the *HTML Specification [HTML]*, W3C Recommendation 24 December 1999, and *Document Object Model (DOM) Level 2 HTML Specification Version 1.0 [DOM Level 2 - HTML]*, W3C Recommendation 09 January, 2003.

Section 2 of this specification is normative. All other sections and examples in this specification are informative.

1.1 Glossary

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[CSS-Level2-2009] Bos, B., Celik, T., Hickson, I., and Wium Lie, H., Eds., "Cascading Style Sheets Level 2 Revision 1 (CSS 2.1) Specification", W3C Candidate Recommendation 08 September 2009, <http://www.w3.org/TR/2009/CR-CSS2-20090908/>

[DOM Level 2 - Core] W3C, "Document Object Model (DOM) Level 2 Core Specification Version 1.0", W3C Recommendation 13 November, 2000, <http://www.w3.org/TR/DOM-Level-2-Core/>

[DOM Level 2 - HTML] W3C, "Document Object Model (DOM) Level 2 HTML Specification Version 1.0", W3C Recommendation, January 2003, <http://www.w3.org/TR/2003/REC-DOM-Level-2-HTML-20030109/>

[HTML] World Wide Web Consortium, "HTML 4.01 Specification", December 1999, <http://www.w3.org/TR/html4/>

[MS-DOM2CE] Microsoft Corporation, "[Internet Explorer Extensions to the Document Object Model \(DOM\) Level 2 Core Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

1.2.2 Informative References

[DOM Level 2 - Style] W3C, "Document Object Model (DOM) Level 2 Style Specification Version 1.0", W3C Recommendation, November 2000, <http://www.w3.org/TR/2000/REC-DOM-Level-2-Style-20001113/>

[ECMA-262-1999] ECMA International, "Standard ECMA-262 ECMAScript Language Specification", 3rd edition (December 1999), <http://www.ecma-international.org/publications/files/ECMA-ST-ARCH/ECMA-262,%203rd%20edition,%20December%201999.pdf>

[ECMA-262/5] ECMA International, "Standard ECMA-262 ECMAScript Language Specification", 5th Edition (December 2009), <http://www.ecma-international.org/publications/files/ECMA-ST-ARCH/ECMA-262%205th%20edition%20December%202009.pdf>

[HTML5] Berjon, R., Faulkner, S., Leithead, T., Navara, E., et al., Eds., "HTML5 -- A vocabulary and associated APIs for HTML and XHTML", <http://www.w3.org/TR/html5/>

[MS-CSS21E] Microsoft Corporation, "[Internet Explorer Extensions to Cascading Style Sheets \(CSS\) 2.1 and DOM Level 2 Style Specifications](#)".

[MS-DOM2CEX] Microsoft Corporation, "[Microsoft XML Extensions to the Document Object Model \(DOM\) Level 2 Core Specification](#)".

[MS-DOM2EE] Microsoft Corporation, "[Internet Explorer Extensions to the Document Object Model \(DOM\) Level 2 Events Specification](#)".

[MS-DOM2E] Microsoft Corporation, "[Internet Explorer Document Object Model \(DOM\) Level 2 Events Standards Support Document](#)".

[MS-ES3EX] Microsoft Corporation, "[Microsoft JScript Extensions to the ECMAScript Language Specification Third Edition](#)".

[MS-ES5EX] Microsoft Corporation, "[Internet Explorer Extensions to the ECMA-262 ECMAScript Language Specification \(Fifth Edition\)](#)".

[MS-HTML5E] Microsoft Corporation, "[Microsoft Edge / Internet Explorer Extensions to the HTML5 Specification](#)".

[MSDN-DHTMLBehaviors] Microsoft Corporation, "Introduction to DHTML Behaviors", [http://msdn.microsoft.com/en-us/library/ms531079\(v=VS.85\).aspx](http://msdn.microsoft.com/en-us/library/ms531079(v=VS.85).aspx)

1.3 Extension Overview (Synopsis)

The extensions described in this document were selected for their applicability to [\[HTML\]](#) and [\[DOM Level 2 - HTML\]](#).

The extensions to [\[HTML\]](#) and [\[DOM Level 2 - HTML\]](#) are organized as follows:

Elements

- [?IMPORT?](#)
- [COMMENT](#)
- [MARQUEE](#)
- [NOBR](#)
- [PUBLIC:ATTACH](#)
- [PUBLIC:COMPONENT](#)
- [PUBLIC:DEFAULTS](#)
- [PUBLIC:EVENT](#)
- [PUBLIC:METHOD](#)
- [PUBLIC:PROPERTY](#)

Interfaces

- [HTCComponentElement](#)
- [HTCElementBehaviorDefaults](#)
- [HTCPropertyElement](#)
- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)
- [HTMLAreasCollection](#)
- [HTMLBlockElement](#)
- [HTMLBodyElement](#)
- [HTMLButtonElement](#)
- [HTMLCollection](#)
- [HTMLDDElement](#)
- [HTMLDivElement](#)
- [HTMLDocument](#)
- [HTMLDTElement](#)
- [HTMLElement](#)
- [HTMLFieldSetElement](#)
- [HTMLFormElement](#)
- [HTMLFrameElement](#)
- [HTMLFrameSetElement](#)
- [HTMLHeadingElement](#)
- [HTMLHRElement](#)
- [HTMLIFrameElement](#)
- [HTMLImageElement](#)
- [HTMLInputElement](#)
- [HTMLIsIndexElement](#)
- [HTMLLabelElement](#)
- [HTMLLegendElement](#)
- [HTMLMarqueeElement](#)
- [HTMLMetaElement](#)
- [HTMLObjectElement](#)
- [HTMLOptionElement](#)

- [HTMLParagraphElement](#)
- [HTMLSelectElement](#)
- [HTMLSpanElement](#)
- [HTMLStyleElement](#)
- [HTMLTableCaptionElement](#)
- [HTMLTableCellElement](#)
- [HTMLTableElement](#)
- [HTMLTableRowElement](#)
- [HTMLTableSectionElement](#)
- [HTMLTextAreaElement](#)

The following attributes are listed alphabetically, but indicate their type: (DOM) for DOM attribute only, and (markup) for content attribute only.

Attributes

- [action](#)
- [align](#)
- [alinkColor](#) (DOM)
- [allowTransparency](#)
- [alt](#)
- [altHtml](#) (DOM)
- [application](#) (markup)
- [atomicselection](#) (markup)
- [background](#)
- [BaseHref](#)
- [behavior](#)
- [bgColor](#)
- [bgProperties](#)
- [border](#)
- [borderColor](#)
- [borderColorDark](#)
- [borderColorLight](#)
- [bottomMargin](#)
- [canHaveHTML](#)

- [charset](#)
- [classid](#)
- [clear](#)
- [color](#)
- [cols](#)
- [contentWindow](#) (DOM)
- [dataFld](#)
- [dataFormatAs](#)
- [dataPageSize](#)
- [dataSrc](#)
- [dir](#) (DOM)
- [direction](#)
- [dynsrc](#)
- [encoding](#)
- [event](#) (markup)
- [fgColor](#) (DOM)
- [fileCreatedDate](#) (DOM)
- [fileModifiedDate](#) (DOM)
- [fileSize](#) (DOM)
- [fileUpdatedDate](#) (DOM)
- [for](#) (markup)
- [frameBorder](#)
- [frameSpacing](#)
- [get](#) (markup)
- [hash](#) (DOM)
- [height](#)
- [host](#) (DOM)
- [hostname](#) (DOM)
- [href](#)
- [hspace](#)
- [implementation](#) (markup)
- [indeterminate](#) (DOM)

- [internalName](#) (markup)
- [isDisabled](#) (DOM)
- [isMultiLine](#) (DOM)
- [leftMargin](#)
- [lightWeight](#) (markup)
- [linkColor](#) (DOM)
- [literalContent](#) (markup)
- [loop](#)
- [lowsrc](#)
- [methods](#)
- [mimeType](#) (DOM)
- [name](#)
- [nameProp](#) (DOM)
- [namespace](#) (markup)
- [noResize](#)
- [noWrap](#)
- [object](#) (DOM)
- [onactivate](#)
- [onafterupdate](#)
- [onbeforeactivate](#)
- [onbeforecopy](#)
- [onbeforecut](#)
- [onbeforedeactivate](#)
- [onbeforeeditfocus](#)
- [onbeforepaste](#)
- [onbeforeunload](#)
- [onbeforeupdate](#)
- [onbounce](#)
- [oncellchange](#)
- [oncontrolselect](#)
- [oncopy](#)
- [oncut](#)

- [ondataavailable](#)
- [ondatasetchanged](#)
- [ondatasetcomplete](#)
- [ondeactivate](#)
- [onerrorupdate](#)
- [onevent](#) (markup)
- [onfilterchange](#)
- [onfinish](#)
- [onfocusin](#)
- [onfocusout](#)
- [onhelp](#)
- [onlosecapture](#)
- [onmouseenter](#)
- [onmouseleave](#)
- [onmove](#)
- [onmoveend](#)
- [onmovestart](#)
- [onpaste](#)
- [onpropertychange](#)
- [onresizeend](#)
- [onresizestart](#)
- [onrowenter](#)
- [onrowexit](#)
- [onrowsdelete](#)
- [onrowsinserted](#)
- [onselect](#)
- [onselectstart](#)
- [onstart](#)
- [parentDocument](#) (DOM)
- [pathname](#) (DOM)
- [persist](#) (markup)
- [port](#) (DOM)

- [protocol](#) (DOM)
- [protocolLong](#) (DOM)
- [put](#) (markup)
- [rightMargin](#)
- [scroll](#)
- [scrollAmount](#)
- [scrollDelay](#)
- [search](#) (DOM)
- [start](#)
- [status](#) (DOM)
- [styleSheet](#) (DOM)
- [supportsEditMode](#) (markup)
- [tabStop](#)
- [tagName](#) (markup)
- [topMargin](#)
- [trueSpeed](#)
- [uniqueID](#) (DOM)
- [uniqueNumber](#) (DOM)
- [unselectable](#) (markup)
- [url](#) (DOM)
- [urn](#)
- [vAlign](#)
- [value](#)
- [viewInheritStyle](#)
- [viewLink](#)
- [viewLinkContent](#) (markup)
- [viewMasterTab](#)
- [vlinkColor](#) (DOM)
- [vspace](#)
- [width](#)
- [wrap](#)
- [xmlns](#) (markup)

Methods

- [add\(\)](#)
- [item\(\)](#)
- [moveRow\(\)](#)
- [namedItem\(\)](#)
- [remove\(\)](#)
- [setActive\(\)](#)
- [tags\(\)](#)
- [urns\(\)](#)

Collections

- [all](#)
- [cells](#)
- [frames](#)

1.3.1 Element Behaviors and HTML Components

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

Element behaviors allow a developer to define custom elements that can be used in the same way as normal HTML elements in a webpage. Because element behaviors are encapsulated components, they can add functionality to a webpage while improving the reusability and organization of content, script, and style elements.

Element behaviors are synchronously attached to elements through special style sheet rules, or an IMPORT processing instruction such as the following:

```
<HTML xmlns:games>
<HEAD>
<?IMPORT namespace="games" implementation="checkers.htc" ?>
</HEAD>
<BODY>
<games:checkers />
</BODY>
</HTML>
```

Element behaviors, which are used to define custom elements, are also called HTML Components (HTC). The implementation of the HTC is encapsulated in an .htc file.

The following elements and attributes are used to define the public interface and event model of an HTC:

- [PUBLIC:ATTACH](#)
 - [event](#)
 - [for](#)
 - [onevent](#)

- [PUBLIC:COMPONENT](#)
 - [lightWeight](#)
 - [literalContent](#)
 - [supportsEditMode](#)
 - [tagName](#)
 - [urn](#)
- [PUBLIC:DEFAULTS](#)
 - [canHaveHTML](#)
 - [tabStop](#)
 - [viewInheritStyle](#)
 - [viewLinkContent](#)
 - [viewMasterTab](#)
- [PUBLIC:EVENT](#)
- [PUBLIC:METHOD](#)
 - [internalName](#)
- [PUBLIC:PROPERTY](#)
 - [get](#)
 - [internalName](#)
 - [persist](#)
 - [put](#)
 - [value](#)

For more information about Element Behaviors and HTC, see *Introduction to DHTML Behaviors* [[MSDN-DHTMLBehaviors](#)].

1.3.2 Organization of This Documentation

This document is organized as follows:

- **Elements:** New HTML elements are described.
- **Interfaces:** The extensions are listed according to interface at the highest level.

Interface members are described at the next levels.

- **Attributes:** Includes all markup and DOM properties.
 - **DOM and Content Attribute:** Attributes that are supported by both DOM and markup.
 - **DOM Attributes Only:** Attributes only available through the object model.
 - **Content Attributes Only:** Attributes declared only in markup.

- **Event Attributes:** Attributes that support events and event handlers.
- **Methods:** Extends DOM functionality.
- **Collections:** Objects that support array-type behavior.

1.4 Relationship to Standards and Other Extensions

Some of the extensions described here are standard functionality in HTML5 [\[HTML5\]](#). This document does not indicate for which extensions this is true. See [\[MS-HTML5E\]](#) for information about extensions relative to [\[HTML5\]](#)

The following documents provide additional extensions.

- [\[MS-CSS21E\]](#): Extensions to the [\[CSS-Level2-2009\]](#) and [\[DOM Level 2 - Style\]](#) specifications.
- [\[MS-DOM2CE\]](#) and [\[MS-DOM2CEX\]](#): Extensions to the [\[DOM Level 2 - Core\]](#) specification.
- [\[MS-DOM2EE\]](#): Extensions to the [\[MS-DOM2E\]](#) specification.
- [\[MS-ES3EX\]](#): Extensions to the ECMAScript [\[ECMA-262-1999\]](#) specification.
- [\[MS-ES5EX\]](#): Extensions to the ECMAScript [\[ECMA-262/5\]](#) specification.
- [\[MS-HTML5E\]](#): Extensions to the [\[HTML5\]](#) specification.

1.5 Applicability Statement

This document specifies a set of extensions to the [\[HTML\]](#) and [\[DOM Level 2 - HTML\]](#) specifications that are implemented in Microsoft web browsers.

Each browser version may implement multiple document rendering modes. The modes vary from one to another in support of the standard. The following table lists the document modes supported by each browser version.

Browser Version	Document Modes Supported
Windows Internet Explorer 7	Quirks Mode Standards Mode
Windows Internet Explorer 8	Quirks mode IE7 Mode IE8 Mode
Windows Internet Explorer 9	Quirks Mode IE7 Mode IE8 Mode IE9 Mode
Windows Internet Explorer 10	Quirks Mode IE7 Mode IE8 Mode IE9 Mode IE10 Mode
Internet Explorer 11	Quirks Mode IE7 Mode

Browser Version	Document Modes Supported
	IE8 Mode IE9 Mode IE10 Mode IE11 Mode
Microsoft Edge	EdgeHTML Mode

Many of the extensions listed in this documented are accompanied by a statement that indicates what modes and versions have the extension. The statement has a list of document modes followed by a list of browser versions in parentheses. For any listed version the extension is in all listed modes that the version provides. Here is an example of an availability statement:

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

This means that the extension is in Quirks mode in all browser versions that are shown in the table above to have Quirks Mode, and so on for IE7 Mode, IE8 Mode, and IE9 Mode.

If an extension does not have an availability statement, all modes of all versions shown in the table above have the extension.

Note: "Standards mode" in Internet Explorer 7 and "IE7 mode" in Internet Explorer 8 refer to the same document mode. "IE7 mode" is the preferred way of referring to this document mode across all versions of the browser.

2 Extensions

This section specifies additional elements, interfaces, attributes, methods and collections to [\[HTML\]](#) and [\[DOM Level 2 - HTML\]](#) that are available in Windows Internet Explorer and Microsoft Edge.

The extensions to [HTML] and [DOM Level 2 - HTML] are as follows:

- Extensions to the [Elements](#)
- Extensions to the [Interfaces](#)
- Extensions to the [Attributes](#)
- Extensions to the [Methods](#)
- Extensions to the [Collections](#)

2.1 Elements

The following elements are extensions to [\[HTML\]](#):

- [?IMPORT?](#)
- [comment](#) ([HTMLCommentElement](#))
- [marquee](#) ([HTMLMarqueeElement](#))
- [noBR](#)
- [PUBLIC:ATTACH](#)
- [PUBLIC:COMPONENT](#)
- [PUBLIC:DEFAULTS](#)
- [PUBLIC:EVENT](#)
- [PUBLIC:METHOD](#)
- [PUBLIC:PROPERTY](#)

2.1.1 ?IMPORT?

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

A processing instruction that imports a tag definition from an element behavior. Two attributes are required:

- [namespace](#)
- [implementation](#)

The value of an XMLNS attribute that has been defined in the HTML tag must correspond to the value of the **namespace** attribute defined in the **IMPORT** processing instruction (PI). Otherwise, the imported tag definition cannot be used.

An imported tag will not render if the value of the implementation attribute is not valid. When using an HTC file, the file must comply with the same security rules as all behaviors. For more information, see *Introduction to DHTML Behaviors* [\[MSDN-DHTMLBehaviors\]](#).

The **IMPORT** PI must be placed before the first instance of a custom element that uses the imported tag definition. If the **IMPORT** PI is placed after the custom element, the behavior does not attach to the custom element. This also means that the **document.write** method should not be used to add the **IMPORT** PI to a document.

The **IMPORT** PI is only processed during the initial parsing of the document. Therefore, a document that uses an element behavior must include the **IMPORT** PI in the HTML file. Provided that the **IMPORT** PI is specified in the primary document, the **document.write** method can be used to add the custom element and attach to the behavior.

2.1.2 COMMENT

Quirks Mode, IE7 Mode, and IE8 Mode (All Versions)

*Start tag: **required**, End tag: **required***

Indicates an HTML comment. Neither the **comment** element nor text and markup contained within it are rendered. An HTML comment declared with a **comment** element is not considered to be atomic.

Additional details about the **comment** element are found at [HTMLCommentElement](#).

2.1.3 MARQUEE

*Start tag: **required**, End tag: **required***

Defines a scrolling text marquee.

The following attributes are associated with the **marquee** element:

- [behavior](#)
- [bgColor](#)
- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)
- [direction](#)
- [height](#)
- [hspace](#)
- [loop](#)
- [scrollAmount](#)
- [scrollDelay](#)
- [trueSpeed](#)
- [vspace](#)
- [width](#)

Additional details on the **marquee** element is found at [HTMLMarqueeElement](#).

2.1.4 NOBR

Start tag: **required**, End tag: **required**

The **noBR** element renders text without line breaks.

This element is not rendered. This element derives from the **HTML** interface (as defined in [\[HTML\]](#)).

2.1.5 PUBLIC:ATTACH

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Start tag: **required**, End tag: **forbidden**

The PUBLIC:ATTACH element binds a function or script to an event in an HTC.

The element defines the following attributes:

- [event](#)
- [for](#)
- id (as defined by [\[HTML\]](#))
- [onevent](#)

2.1.6 PUBLIC:COMPONENT

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Start tag: **required**, End tag: **required**

The PUBLIC:COMPONENT element identifies the content of the file as an HTC.

The element defines the following attributes:

- id (as defined by [\[HTML\]](#))
- [lightWeight](#)
- [literalContent](#)
- name (as defined by [\[HTML\]](#))
- [supportsEditMode](#)
- [tagName](#)
- [urn](#)

The following child element can occur at most once:

- [PUBLIC:DEFAULTS](#)

The following child elements can occur one or more times:

- [PUBLIC:ATTACH](#)
- [PUBLIC:EVENT](#)

- [PUBLIC:METHOD](#)
- [PUBLIC:PROPERTY](#)

Additional details on the PUBLIC:COMPONENT element is found at [HTCComponentElement](#).

2.1.7 PUBLIC:DEFAULTS

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

*Start tag: **required**, End tag: **forbidden***

The PUBLIC:DEFAULTS element sets default properties for an HTC.

The element defines the following attributes:

- [canHaveHTML](#)
- style (as defined by [\[HTML\]](#))
- [tabStop](#)
- [viewInheritStyle](#)
- [viewLinkContent](#)
- [viewMasterTab](#)

Additional details on the PUBLIC:DEFAULTS element is found at [HTCElementBehaviorDefaults](#).

2.1.8 PUBLIC:EVENT

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

*Start tag: **required**, End tag: **forbidden***

The PUBLIC:EVENT element defines an event that is exposed by the HTC to the primary document.

The element defines the following attributes:

- id (as defined by [\[HTML\]](#))
- name (as defined by [\[HTML\]](#))

2.1.9 PUBLIC:METHOD

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

*Start tag: **required**, End tag: **forbidden***

The PUBLIC:METHOD element defines a method that is exposed by an HTC to the primary document.

The element defines the following attributes:

- id (as defined by [\[HTML\]](#))
- [internalName](#)
- name (as defined by [\[HTML\]](#))

2.1.10 PUBLIC:PROPERTY

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Start tag: **required**, End tag: **forbidden**

The PUBLIC:PROPERTY element defines a property that is exposed by the HTC to the primary document.

The element defines the following attributes:

- [get](#)
- id (as defined by [\[HTML\]](#))
- [internalName](#)
- name (as defined by [\[HTML\]](#))
- [persist](#)
- [put](#)
- [value](#)

Additional details on the PUBLIC:PROPERTY element is found at [HTCPropertyElement](#).

2.2 Interfaces

Internet Explorer-only Interfaces

The following interfaces are extensions of HTML:

- [HTCComponentElement](#)
- [HTCElementBehaviorDefaults](#)
- [HTCPropertyElement](#)
- [HTMLBlockElement](#)
- [HTMLCommentElement](#)
- [HTMLDDElement](#)
- [HTMLDTElement](#)
- [HTMLMarqueeElement](#)

DOM Interfaces

The following interfaces are defined in [\[DOM Level 2 - HTML\]](#) and extended by Internet Explorer:

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)
- [HTMLAreaCollection](#)
- [HTMLBodyElement](#)
- [HTMLButtonElement](#)

- [HTMLCollection](#)
- [HTMLDivElement](#)
- [HTMLDocument](#)
- [HTMLElement](#)
- [HTMLFieldSetElement](#)
- [HTMLFormElement](#)
- [HTMLFrameElement](#)
- [HTMLFrameSetElement](#)
- [HTMLHeadingElement](#)
- [HTMLHRElement](#)
- [HTMLIFrameElement](#)
- [HTMLImageElement](#)
- [HTMLInputElement](#)
- [HTMLIsIndexElement](#)
- [HTMLLabelElement](#)
- [HTMLLegendElement](#)
- [HTMLMetaElement](#)
- [HTMLObjectElement](#)
- [HTMLOptionElement](#)
- [HTMLParagraphElement](#)
- [HTMLSelectElement](#)
- [HTMLSpanElement](#)
- [HTMLStyleElement](#)
- [HTMLTableCaptionElement](#)
- [HTMLTableCellElement](#)
- [HTMLTableElement](#)
- [HTMLTableRowElement](#)
- [HTMLTableSectionElement](#)
- [HTMLTextAreaElement](#)

2.2.1 Internet Explorer-Only Interfaces

The following interfaces are extensions of HTML.

2.2.1.1 HTCComponentElement

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

The **HTCComponentElement** (IHTCDescBehavior) interface provides access to the following attribute:

- [urn](#)

2.2.1.2 HTCElementBehaviorDefaults

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

The **HTCElementBehaviorDefaults** (IHTMLElementDefaults) provides access to the following attributes:

- [canHaveHTML](#)
- [tabStop](#)
- [viewInheritStyle](#)
- [viewMasterTab](#)

2.2.1.3 HTCPropertyElement

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

The **HTCPropertyElement** (IHTCPropertyBehavior) provides access to the following attribute:

- [value](#)

2.2.1.4 HTMLBlockElement

The **HTMLBlockElement** interface provides access to properties and elements available to most block elements.

The **HTMLBlockElement** interface has been added, with the following attribute:

- [clear](#)

This interface provides access to the **blockquote** element.

```
//Introduced in Internet Explorer.  
interface HTMLBlockElement : HTMLElement {  
    attribute DOMString      clear;  
};
```

2.2.1.5 HTMLCommentElement

Quirks Mode, IE7 Mode, and IE8 Mode (All Versions)

The **HTMLCommentElement** interface indicates a comment that will not be displayed.

The **HTMLCommentElement** interface has been added with the following attributes:

- data – Defined in [\[DOM Level 2 - Core\]](#)
- length - Defined in [\[DOM Level 2 - Core\]](#)

- text – see [\[MS-DOM2CE\]](#)

The **HTMLCommentElement** interface has been added with the following methods:

- `appendData()` – Defined in [DOM Level 2 - Core]
- `atomic` – See [MS-DOM2CE]
- `deleteData()` – Defined in [DOM Level 2 - Core]
- `insertData()` – Defined in [DOM Level 2 - Core]
- `replaceData()` – Defined in [DOM Level 2 - Core]
- `substringData()` – Defined in [DOM Level 2 - Core]

For more information about the **HTMLCommentElement** interface, see [comment](#).

```
//Introduced in Internet Explorer.
interface HTMLCommentElement : HTMLElement {
    attribute DOMstring    datatext
    Node                    appendData(in DOMstring data);
    Node                    atomic();
    Node                    deleteData(in DOMstring data);
    Node                    insertData(in DOMstring data);
    Node                    replaceData(in DOMstring data);
    Node                    substringData(in DOMstring data);
};
```

2.2.1.6 HTMLDDElement

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **HTMLDDElement** interface provides access to the **dd** object.

The **HTMLDDElement** interface has been added, with the following attribute:

- [noWrap](#)

```
//Introduced in Internet Explorer.
interface HTMLDDElement : HTMLElement {
    attribute boolean      noWrap;
};
```

2.2.1.7 HTMLDTElement

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **HTMLDTElement** interface provides access for controlling the text-wrapping characteristics of the **HTMLDTElement** object.

The **HTMLDTElement** interface has been added, with the following attribute:

- [noWrap](#)

```
//Introduced in Internet Explorer.
interface HTMLDTElement : HTMLElement {
    attribute boolean      noWrap;
};
```

2.2.1.8 HTMLMarqueeElement

The **HTMLMarqueeElement** interface is used to specify a marquee element. For more information about the **HTMLMarqueeElement** interface, see [marquee](#).

The **HTMLMarqueeElement** interface has been added, with the following attributes:

- [behavior](#)
- [bgColor](#)
- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)
- [direction](#)
- [height](#)
- [hspace](#)
- [loop](#)
- [onbounce](#)
- [onfinish](#)
- [onstart](#)
- [scrollAmount](#)
- [scrollDelay](#)
- [trueSpeed](#)
- [vspace](#)
- [width](#)

```
//Introduced in Internet Explorer.
interface HTMLMarqueeElement : HTMLElement {
    attribute DOMString      behavior;
    attribute DOMString      bgColor;
    attribute DOMString      dataFld;
    attribute DOMString      dataFormatAs;
    attribute DOMString      dataSrc;
    attribute DOMString      direction;
    attribute DOMString      height;
    attribute long           hspace;
    attribute long           loop;
    attribute Function       onbounce;
    attribute Function       onfinish;
    attribute Function       onstart;
    attribute long           scrollAmount;
    attribute long           scrollDelay;
    attribute boolean        trueSpeed;
    attribute long           vspace;
    attribute DOMString      width;
};
```

2.2.2 DOM Interfaces

The following interfaces are defined in [\[DOM Level 2 - HTML\]](#) and extended by Microsoft web browsers.

2.2.2.1 HTMLAnchorElement

The **HTMLAnchorElement** interface designates the destination of a hypertext link.

The **HTMLAnchorElement** interface has been extended with the following attributes:

- [dataFld](#)
- [dataFormatAs](#) (not supported by the element)
- [dataSrc](#)
- [hash](#)
- [host](#)
- [hostname](#)
- [Methods](#)
- [mimeType](#)
- [nameProp](#)
- [pathname](#)
- [port](#)
- [protocol](#)
- [protocolLong](#)
- [search](#)
- [urn](#)

When an anchor contains an image, the image has a border by default. The color of the border reflects the visited or unvisited status of the link.

```
//Introduced in Internet Explorer.
interface HTMLAnchorElement : HTMLElement {
    attribute DOMString      dataFld;
    attribute DOMString      dataFormatAs;
    attribute DOMString      dataSrc;
    attribute DOMString      hash;
    attribute DOMString      host;
    attribute DOMString      hostname;
    attribute DOMString      Methods;
    attribute DOMString      mimeType;
    attribute DOMString      nameProp;
    attribute DOMString      pathname;
    attribute DOMString      port;
    attribute DOMString      protocol;
    attribute DOMString      protocolLong;
    attribute DOMString      search;
    attribute DOMString      urn;
};
```

2.2.2.2 HTMLAreaElement

The **HTMLAreaElement** interface specifies the shape of a hot spot in a client-side image map.

The **HTMLAreaElement** interface has been extended with the following attributes:

- [hash](#)
- [host](#)
- [hostname](#)
- [pathname](#)
- [port](#)
- [protocol](#)
- [search](#)

```
//Introduced in Internet Explorer.
interface HTMLAreaElement : HTMLElement {
    attribute DOMString    hash;
    attribute DOMString    host;
    attribute DOMString    hostname;
    attribute DOMString    pathname;
    attribute DOMString    port;
    attribute DOMString    protocol;
    attribute DOMString    search;
};
```

2.2.2.3 HTMLAreasCollection

The **HTMLAreasCollection** interface specifies the collection of areas that make up the image map.

The **HTMLAreasCollection** interface has been extended with the following methods:

- [add\(\)](#)
- [remove\(\)](#)
- [tags\(\)](#)
- [urns\(\)](#)

Areas can be added or removed from the collection. If duplicate names are found, a collection of those named items is returned. Subsequently, collections of duplicate names must be referenced by ordinal position.

```
//Introduced in Internet Explorer.
interface HTMLAreasCollection : HTMLCollection {
    void    add(in HTMLElement oElement,
               in long oBefore);
    void    remove(in long iIndex);
    Node    tags(in DOMString sTag);
    Node    urns(in DOMString sUrn);
};
```

2.2.2.4 HTMLBodyElement

The **HTMLBodyElement** interface provides access to the **body** element, and specifies the beginning and end of the document body.

The **HTMLBodyElement** interface has been extended with the following attributes:

- [bgProperties](#)
- [bottomMargin](#)
- [leftMargin](#)
- [noWrap](#)
- [onbeforeunload](#)
- [onselect](#)
- [rightMargin](#)
- [scroll](#)
- [topMargin](#)

The **body** element is a block element.

```
//Introduced in Internet Explorer.
interface HTMLBodyElement : HTMLElement {

    attribute DOMString      bgProperties;
    attribute DOMString      bottomMargin;
    attribute DOMString      leftMargin;
    attribute boolean        noWrap;
    attribute Function       onbeforeunload;
    attribute Function       onselect;
    attribute DOMString      rightMargin;
    attribute DOMString      scroll;
    attribute DOMString      topMargin;
};
```

2.2.2.5 HTMLButtonElement

The **HTMLButtonElement** interface renders content as an HTML button.

The **HTMLButtonElement** interface has been extended with the following attributes:

- [status](#)
- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)

The **button** element is a block element.

```
//Introduced in Internet Explorer.
interface HTMLButtonElement : HTMLElement {
    attribute boolean        status;
```

```

        attribute DOMString      dataFld;
        attribute DOMString      dataFormatAs;
        attribute DOMString      dataSrc;
};

```

2.2.2.6 HTMLCollection

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **HTMLCollection** interface provides access to collections of objects.

The **HTMLCollection** interface has been extended with the following methods:

- [tags\(\)](#)
- [urns\(\)](#)

```

//Introduced in Internet Explorer.
interface HTMLCollection {
    Node          tags(in DOMString sTag);
    Node          urns(in DOMString sUrn);
};

```

2.2.2.7 HTMLDivElement

The **HTMLDivElement** interface provides access to the **div** object.

The **HTMLDivElement** interface has been extended with the following attributes:

- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)
- [noWrap](#)

The **div** element is a block element.

```

//Introduced in Internet Explorer.
interface HTMLDivElement : HTMLElement {
    attribute DOMString      dataFld;
    attribute DOMString      dataFormatAs;
    attribute DOMString      dataSrc;
    attribute boolean        noWrap;
};

```

2.2.2.8 HTMLDocument

The **HTMLDocument** interface retrieves information about the document, and examines and modifies the HTML elements and text in the document.

The **HTMLDocument** interface has been extended with the following attributes:

- [alinkColor](#)
- [bgColor](#)

- [dir](#)
- [fgColor](#)
- [linkColor](#)
- [parentDocument](#)
- [uniqueID](#)
- [vlinkColor](#)
- [all](#)
- [frames](#)

```
//Introduced in Internet Explorer.
interface HTMLDocument : Document {
    attribute DOMString      alinkColor;
    attribute DOMString      bgColor;
    attribute DOMString      dir;
    attribute DOMString      fgColor;
    attribute DOMString      linkColor;
    attribute DOMString      parentDocument;
    attribute DOMString      uniqueID;
    attribute DOMString      vlinkColor;
    attribute HTMLCollection all;
    attribute HTMLCollection frames;
};
```

2.2.2.9 HTMLInputElement

The **HTMLInputElement** interface provides the ability to programmatically access the properties and methods that are common to all elements.

The **HTMLInputElement** interface has been added, with the following attributes:

- [isDisabled](#)
- [isMultiLine](#)
- [onactivate](#)
- [onafterupdate](#)
- [onbeforeactivate](#)
- [onbeforecopy](#)
- [onbeforecut](#)
- [onbeforedeactivate](#)
- [onbeforeeditfocus](#)
- [onbeforepaste](#)
- [onbeforeupdate](#)
- [oncellchange](#)
- [oncontrolselect](#)

- [oncopy](#)
- [oncut](#)
- [ondataavailable](#)
- [ondatachanged](#)
- [ondatasetcomplete](#)
- [ondeactivate](#)
- [onerrorupdate](#)
- [onfilterchange](#)
- [onfocusin](#)
- [onfocusout](#)
- [onhelp](#)
- [onlosecapture](#)
- [onmouseenter](#)
- [onmouseleave](#)
- [onmove](#)
- [onmoveend](#)
- [onmovestart](#)
- [onpaste](#)
- [onpropertychange](#)
- [onresizeend](#)
- [onresizestart](#)
- [onrowenter](#)
- [onrowexit](#)
- [onrowsdelete](#)
- [onrowsinserted](#)
- [onselectstart](#)
- [uniqueID](#)
- [uniqueNumber](#)

The **HTMLElement** interface has been added, with the following method:

- [setActive](#)

2.2.2.10 HTMLFieldSetElement

The **HTMLFieldSetElement** interface draws a box around the text and other elements it contains.

The **HTMLFieldSetElement** interface has been extended with the following attribute:

- [align](#)

This element is useful for grouping elements in a form and for distinctively marking text in a document.

```
//Introduced in Internet Explorer.
interface HTMLFieldSetElement : HTMLElement {
    attribute DOMString    align;
};
```

2.2.2.11 HTMLFormElement

The **HTMLFormElement** interface specifies that the contained controls take part in a form.

The **HTMLFormElement** interface has been extended with the following attribute:

- [encoding](#)

The **HTMLFormElement** interface has been extended with the following methods:

- [item\(\)](#)
- [namedItem\(\)](#)
- [tags\(\)](#)
- [urns\(\)](#)

```
//Introduced in Internet Explorer.
interface HTMLFormElement : HTMLElement {
    attribute DOMString    encoding;
    Node                    item(in unsigned long index);
    Node                    namedItem(in DOMString name);
    Node                    tags(in DOMString sTag);
    Node                    urns(in DOMString sUrn);
};
```

2.2.2.12 HTMLFrameElement

The **HTMLFrameElement** interface specifies an individual frame within a frameset.

The **HTMLFrameElement** interface has been extended with the following attributes:

- [contentWindow](#)
- [allowTransparency](#)
- [border](#)
- [borderColor](#)
- [dataFld](#)
- [dataFormatAs](#) (not supported by this element)

- [dataSrc](#)
- [frameBorder](#)
- [frameSpacing](#)
- [height](#)
- [width](#)

```
//Introduced in Internet Explorer.
interface HTMLFrameElement : HTMLElement {
    attribute Window          contentWindow;
    attribute boolean         allowTransparency;
    attribute DOMString       border;
    attribute DOMString       borderColor;
    attribute DOMString       dataFld;
    attribute DOMString       dataFormatAs;
    attribute DOMString       dataSrc;
    attribute DOMString       frameSpacing;
    attribute DOMString       frameBorder;
    attribute DOMString       height;
    attribute DOMString       width;
};
```

2.2.2.13 HTMLFrameSetElement

The **HTMLFrameSetElement** interface specifies a frameset.

The **HTMLFrameSetElement** interface has been extended with the following attributes:

- [onbeforeunload](#)
- [border](#)
- [borderColor](#)
- [frameBorder](#)
- [frameSpacing](#)
- [name](#)

Use framesets to organize multiple frames and nested framesets. A frameset organizes multiple frames on the screen. The only tags valid within a frameset are frame, nested frameSet, and noFrames.

```
//Introduced in Internet Explorer.
interface HTMLFrameSetElement : HTMLElement {
    attribute Function        onbeforeunload;
    attribute DOMString       border;
    attribute DOMString       borderColor;
    attribute DOMString       frameBorder;
    attribute DOMString       frameSpacing;
    attribute DOMString       name;
};
```

2.2.2.14 HTMLHeadingElement

The **HTMLHeadingElement** interface renders text as a heading style.

The **HTMLHeadingElement** interface has been extended with the following attribute:

- [clear](#)

```
//Introduced in Internet Explorer.
interface HTMLHeadingElement : HTMLElement {
    attribute DOMString    clear;
};
```

2.2.2.15 HTMLHRElement

The **HTMLHRElement** interface draws a horizontal rule.

The **HTMLHRElement** interface has been extended with the following attribute:

- [color](#)

```
//Introduced in Internet Explorer.
interface HTMLHRElement : HTMLElement {
    attribute DOMString    color;
};
```

2.2.2.16 HTMLIFrameElement

The **HTMLIFrameElement** interface creates inline floating frames.

The **HTMLIFrameElement** interface has been extended with the following attributes:

- [contentWindow](#)
- [allowTransparency](#)
- [border](#)
- [dataFld](#)
- [dataFormatAs](#) (Not supported by this element.)
- [dataSrc](#)
- [frameSpacing](#)
- [hspace](#)
- [noResize](#)
- [vspace](#)

```
//Introduced in Internet Explorer.
interface HTMLIFrameElement : HTMLElement {
    attribute Window    contentWindow;
    attribute boolean   allowTransparency;
    attribute DOMString border;
    attribute DOMString dataFld;
    attribute DOMString dataFormatAs;
    attribute DOMString dataSrc;
    attribute DOMString frameSpacing;
    attribute long     hspace;
    attribute boolean   noResize;
    attribute long     vspace;
};
```

```
};
```

2.2.2.17 HTMLImageElement

The **HTMLImageElement** interface provides access to properties and methods supported by the **img** element and the **input** element of the **image** type.

The **HTMLImageElement** interface has been extended with the following attributes:

- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)
- [dynsrc](#)
- [fileCreatedDate](#)
- [fileModifiedDate](#)
- [fileSize](#)
- [fileUpdatedDate](#)
- [href](#)
- [loop](#)
- [lowsrc](#)
- [mimeType](#)
- [nameProp](#)
- [protocol](#)
- [start](#)

```
//Introduced in Internet Explorer.
interface HTMLImageElement : HTMLElement {
    attribute DOMString      dataFld;
    attribute DOMString      dataFormatAs;
    attribute DOMString      dataSrc;
    attribute DOMString      dynsrc;
    attribute DOMString      fileCreatedDate;
    attribute DOMString      fileModifiedDate;
    attribute DOMString      fileSize;
    attribute DOMString      fileUpdatedDate;
    attribute DOMString      href;
    attribute long           loop;
    attribute DOMString      lowsrc;
    attribute DOMString      mimeType;
    attribute DOMString      nameProp;
    attribute DOMString      protocol;
    attribute DOMString      start;
};
```

2.2.2.18 HTMLInputElement

The **HTMLInputElement** interface specifies any type of input control.

The **HTMLInputElement** interface has been extended with the following attributes:

- [border](#)
- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)
- [dynsrc](#)
- [height](#)
- [hspace](#)
- [lowsrc](#)
- [indeterminate](#)
- [loop](#)
- [start](#)
- [status](#)
- [vspace](#)
- [width](#)

```
//Introduced in Internet Explorer.
interface HTMLInputElement : HTMLElement {
    attribute boolean          status;
    attribute DOMString        border;
    readonly attribute boolean complete;
    attribute DOMString        dataFld;
    attribute DOMString        dataFormatAs;
    attribute DOMString        dataSrc;
    attribute DOMString        dynsrc;
    attribute DOMString        height;
    attribute long             hspace;
    attribute DOMString        lowsrc;
    attribute boolean          indeterminate;
    attribute long             loop;
    attribute DOMString        start;
    attribute long             vspace;
    attribute DOMString        width;
};
```

2.2.2.19 HTMLIsIndexElement

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **HTMLIsIndexElement** interface indicates that the document contains a searchable index.

The **HTMLIsIndexElement** interface has been extended with the following attribute:

- [action](#)

To use the `isIndex` tag, the server must provide a search engine that supports this tag. The script to be executed on the server can be specified by the **`HTMLIsIndexElement::action`** property on this tag.

The **`isIndex`** element can be used only within the head tag.

```
//Introduced in Internet Explorer.
interface HTMLIsIndexElement : HTMLElement {
    attribute DOMString    action;
};
```

2.2.2.20 HTMLLabelElement

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **`HTMLLabelElement`** interface specifies a label for a control-like element.

The **`HTMLLabelElement`** interface has been extended with the following attributes:

- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)

```
//Introduced in Internet Explorer.
interface HTMLLabelElement : HTMLElement {
    attribute DOMString    dataFld;
    attribute DOMString    dataFormatAs;
    attribute DOMString    dataSrc;
};
```

2.2.2.21 HTMLLegendElement

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **`HTMLLegendElement`** interface inserts a caption into the box drawn by the `fieldset` element.

The **`HTMLLegendElement`** interface has been extended with the following attributes:

- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)

If provided, this element must be the first element in **`fieldset`**.

```
//Introduced in Internet Explorer.
interface HTMLLegendElement : HTMLElement {
    attribute DOMString    dataFld;
    attribute DOMString    dataFormatAs;
    attribute DOMString    dataSrc;
};
```

2.2.2.22 HTMLLinkElement

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **HTMLLinkElement** interface provides methods to access a link element that is used to specify a link to an external document.

The **HTMLLinkElement** interface has been extended with the following attribute:

- [styleSheet](#)

```
//Introduced in Internet Explorer.  
interface HTMLLinkElement : HTMLInputElement {  
    attribute CSSStyleSheet    styleSheet;  
  
};
```

2.2.2.23 HTMLMetaElement

The **HTMLMetaElement** interface represents the **meta** element.

The **HTMLMetaElement** interface has been extended with the following attributes:

- [url](#)
- [charset](#)

```
//Introduced in Internet Explorer.  
interface HTMLMetaElement : HTMLInputElement {  
    attribute DOMString    url;  
    attribute DOMString    charset;  
  
};
```

You can use the **meta** element to include hidden information about the document and to insert document-related information used by some search engines.

The meta element can be used only within the **head** element.

2.2.2.24 HTMLObjectElement

The **HTMLObjectElement** interface inserts an object into the HTML page.

The **HTMLObjectElement** interface has been extended with the following attributes:

- [alt](#)
- [altHtml](#)
- [BaseHref](#)
- [classid](#)
- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)
- [object](#)

```
//Introduced in Internet Explorer.
interface HTMLObjectElement : HTMLElement {
    attribute DOMString      alt;
    attribute DOMString      altHtml;
    attribute DOMString      BaseHref;
    attribute DOMString      classid;
    attribute DOMString      dataFld;
    attribute DOMString      dataFormatAs;
    attribute DOMString      dataSrc;
    readonly attribute any    object;
};
```

2.2.2.25 HTMLOptionElement

The **HTMLOptionElement** interface denotes one choice in a **select** block.

The **HTMLOptionElement** interface has been extended with the following attributes:

- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)

The **option** element is a block element.

```
//Introduced in Internet Explorer.
interface HTMLOptionElement : HTMLElement {
    attribute DOMString      dataFld;
    attribute DOMString      dataFormatAs;
    attribute DOMString      dataSrc;
};
```

2.2.2.26 HTMLParagraphElement

The **HTMLParagraphElement** interface denotes a paragraph.

The **HTMLParagraphElement** interface has been extended with the following attribute:

- [clear](#)

```
//Introduced in Internet Explorer.
interface HTMLParagraphElement : HTMLElement {
    attribute DOMString      clear;
};
```

2.2.2.27 HTMLSelectElement

The **HTMLSelectElement** interface provides access to the properties and methods of the **select** element.

The **HTMLSelectElement** interface has been extended with the following attributes:

- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)

The **HTMLSelectElement** interface has been extended with the following methods:

- [item\(\)](#)
- [namedItem\(\)](#)
- [tags\(\)](#)
- [urns\(\)](#)

```
//Introduced in Internet Explorer.
interface HTMLSelectElement : HTMLElement {
    attribute DOMString      dataFld;
    attribute DOMString      dataFormatAs;
    attribute DOMString      dataSrc;
    Node                      item(in unsigned long index);
    Node                      namedItem(in DOMString name);
    Node                      tags(in DOMString sTag);
    Node                      urns(in DOMString sUrn);
};
```

2.2.2.28 HTMLSpanElement

The **HTMLSpanElement** interface provides access to the properties of the **span** element.

The **HTMLSpanElement** interface has been extended with the following attributes:

- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)

```
//Introduced in Internet Explorer.
interface HTMLSpanElement : HTMLElement {
    attribute DOMString      dataFld;
    attribute DOMString      dataFormatAs;
    attribute DOMString      dataSrc;
};
```

2.2.2.29 HTMLStyleElement

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **HTMLStyleElement** interface specifies the style sheet for the page.

The **HTMLStyleElement** interface has been extended with the following attribute:

- [styleSheet](#)

The **style** element can be used only within either the **head** or the **body** element.

```
//Introduced in Internet Explorer.
interface HTMLStyleElement : HTMLElement {
    attribute CSSStyleSheet  styleSheet;
};
```

2.2.2.30 HTMLTableCaptionElement

The **HTMLTableCaptionElement** interface specifies a caption for a table **element**.

The **HTMLTableCaptionElement** interface has been extended with the following attribute:

- [vAlign](#)

The **caption** element is a block element.

```
//Introduced in Internet Explorer.
interface HTMLTableCaptionElement : HTMLElement {
    attribute DOMString    vAlign;
};
```

2.2.2.31 HTMLTableCellElement

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **HTMLTableCellElement** interface specifies a cell in a table.

The **HTMLTableCellElement** interface has been extended with the following attributes:

- [background](#)
- [borderColor](#)
- [borderColorDark](#)
- [borderColorLight](#)

The **td** element is a block element.

```
//Introduced in Internet Explorer.
interface HTMLTableCellElement : HTMLElement {
    attribute DOMString    background;
    attribute DOMString    borderColor;
    attribute DOMString    borderColorDark;
    attribute DOMString    borderColorLight;
};
```

2.2.2.32 HTMLTableElement

The **HTMLTableElement** interface specifies that the contained content is organized into a table with rows and columns.

The **HTMLTableElement** interface has been extended with the following attributes:

- [background](#)
- [borderColor](#)
- [borderColorDark](#)
- [borderColorLight](#)
- [cells](#)
- [cols](#)

- [dataFld](#)
- [dataFormatAs](#)
- [dataPageSize](#)
- [dataSrc](#)
- [height](#)

The **HTMLTableElement** interface has been extended with the following method:

- [moveRow\(\)](#)

Valid tags within a table include **caption**, **col**, **colGroup**, **tBody**, **tHead**, and **tr**.

The **table** element is a block element.

```
//Introduced in Internet Explorer.
interface HTMLTableElement : HTMLElement {
    attribute DOMString      background;
    attribute DOMString      borderColor;
    attribute DOMString      borderColorDark;
    attribute DOMString      borderColorLight;
    attribute DOMString      cells;
    attribute long           cols;
    attribute DOMString      dataFld;
    attribute DOMString      dataFormatAs;
    attribute DOMString      dataSrc;
    attribute DOMString      height;
    Node                      moveRow(in long iSource, in long iTarget);
};
```

2.2.2.33 HTMLTableRowElement

The **HTMLTableRowElement** interface specifies a row in a table.

The **HTMLTableRowElement** interface has been extended with the following attributes:

- [borderColor](#)
- [height](#)
- [borderColorDark](#)
- [borderColorLight](#)

Within a row, the **td** and **th** tags are valid.

The **tr** element is a block element.

```
//Introduced in Internet Explorer.
interface HTMLTableRowElement : HTMLElement {
    attribute DOMString      borderColor;
    attribute DOMString      height;
    attribute DOMString      borderColorDark;
    attribute DOMString      borderColorLight;
};
```

2.2.2.34 HTMLTableSectionElement

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

The **HTMLTableSectionElement** interface designates rows as the body of the table.

The **HTMLTableSectionElement** interface has been extended with the following attribute:

- [bgColor](#)

The **HTMLTableSectionElement** interface has been extended with the following method:

- [moveRow\(\)](#)

The **HTMLTableSectionElement** is exposed for all tables, even if the table does not explicitly define a **tBody** element.

The **tBody** element is a block element.

```
//Introduced in Internet Explorer.
interface HTMLTableSectionElement : HTMLElement {
    attribute DOMString    bgColor;
    Node                    moveRow(in long iSource, in long iTarget);
};
```

2.2.2.35 HTMLTextAreaElement

The **HTMLTextAreaElement** interface specifies a multiline text input control.

The **HTMLTextAreaElement** interface has been extended with the following attributes:

- [status](#)
- [dataFld](#)
- [dataFormatAs](#)
- [dataSrc](#)
- [wrap](#)

```
//Introduced in Internet Explorer.
interface HTMLTextAreaElement : HTMLElement {
    attribute boolean        status;
    attribute DOMString     dataFld;
    attribute DOMString     dataFormatAs;
    attribute DOMString     dataSrc;
    attribute DOMString     wrap;
};
```

2.3 Attributes

DOM and Content Attributes

The following attributes are supported by both DOM and markup:

- [action](#)
- [align](#)

- [allowTransparency](#)
- [alt](#)
- [background](#)
- [BaseHref](#)
- [behavior](#)
- [bgColor](#)
- [bgProperties](#)
- [border](#)
- [borderColor](#)
- [borderColorDark](#)
- [borderColorLight](#)
- [bottomMargin](#)
- [canHaveHTML](#)
- [charset](#)
- [classid](#)
- [clear](#)
- [color](#)
- [cols](#)
- [dataFld](#)
- [dataFormatAs](#)
- [dataPageSize](#)
- [dataSrc](#)
- [direction](#)
- [dynsrc](#)
- [encoding](#)
- [frameBorder](#)
- [frameSpacing](#)
- [height](#)
- [href](#)
- [hspace](#)
- [leftMargin](#)
- [loop](#)

- [lowsrc](#)
- [methods](#)
- [name](#)
- [noResize](#)
- [noWrap](#)
- [rightMargin](#)
- [scroll](#)
- [scrollAmount](#)
- [scrollDelay](#)
- [start](#)
- [tabStop](#)
- [topMargin](#)
- [trueSpeed](#)
- [urn](#)
- [vAlign](#)
- [value](#)
- [viewInheritStyle](#)
- [viewMasterTab](#)
- [vspace](#)
- [width](#)
- [wrap](#)

DOM Attributes Only

The following attributes are only available through the object model:

- [alinkColor](#)
- [altHtml](#)
- [contentWindow](#)
- [dir](#)
- [fgColor](#)
- [fileCreatedDate](#)
- [fileModifiedDate](#)
- [fileSize](#)
- [fileUpdatedDate](#)

- [hash](#)
- [host](#)
- [hostname](#)
- [indeterminate](#)
- [isDisabled](#)
- [isMultiLine](#)
- [linkColor](#)
- [mimeType](#)
- [nameProp](#)
- [object](#)
- [parentDocument](#)
- [pathname](#)
- [port](#)
- [protocol](#)
- [protocolLong](#)
- [search](#)
- [status](#)
- [styleSheet](#)
- [uniqueID](#)
- [uniqueNumber](#)
- [url](#)
- [viewLink](#)
- [vlinkColor](#)

Content Attributes Only

The following attributes are declared only in markup:

- [application](#)
- [atomicselection](#)
- [event](#)
- [for](#)
- [get](#)
- [implementation](#)
- [internalName](#)

- [lightWeight](#)
- [literalContent](#)
- [namespace](#)
- [onevent](#)
- [persist](#)
- [put](#)
- [supportsEditMode](#)
- [tagName](#)
- [unselectable](#)
- [viewLinkContent](#)
- [xmlns](#)

Event Attributes

The following attributes support events and event handlers:

- [onactivate](#)
- [onafterupdate](#)
- [onbeforeactivate](#)
- [onbeforecopy](#)
- [onbeforecut](#)
- [onbeforedeactivate](#)
- [onbeforeeditfocus](#)
- [onbeforepaste](#)
- [onbeforeunload](#)
- [onbeforeupdate](#)
- [onbounce](#)
- [oncellchange](#)
- [oncontentready](#)
- [oncontentsave](#)
- [oncontrolselect](#)
- [oncopy](#)
- [oncut](#)
- [ondataavailable](#)
- [ondatasetchanged](#)

- [ondatasetcomplete](#)
- [ondeactivate](#)
- [ondetach](#)
- [ondocumentready](#)
- [onerrorupdate](#)
- [onfilterchange](#)
- [onfinish](#)
- [onfocusin](#)
- [onfocusout](#)
- [onhelp](#)
- [onlosecapture](#)
- [onmouseenter](#)
- [onmouseleave](#)
- [onmove](#)
- [onmoveend](#)
- [onmovestart](#)
- [onpaste](#)
- [onpropertychange](#)
- [onresizeend](#)
- [onresizestart](#)
- [onrowenter](#)
- [onrowexit](#)
- [onrowsdelete](#)
- [onrowsinserted](#)
- [onselect](#)
- [onselectstart](#)
- [onstart](#)

2.3.1 DOM and Content Attributes

This section contains a list of attributes that are supported in markup and can be accessed programmatically from the DOM.

2.3.1.1 action

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

action of type `DOMString`

Sets or retrieves the URL to which the form content is sent for processing.

The attribute's value is a string that specifies or receives the URL to use. If a relative path is specified, the base URL of the document is assumed.

For Windows Internet Explorer 8 or later, when the browser is in Internet Explorer 8 mode, the value of the **action** attribute depends on the context of the reference to the attribute. When read as a Document Object Model (DOM) attribute, **action** returns an absolute URL. The value specified by the page author is returned when **action** is read as a content attribute, when the page is displayed in an earlier document compatibility mode, or when the page is viewed with an earlier version of the browser.

The **action** attribute extends the [HTMLIsIndexElement](#) interface.

2.3.1.2 align

align of type `DOMString`

Sets or retrieves how the object is aligned with adjacent text.

Possible values are:

- `absbottom` (as defined in [HTML])
- `baseline`
- `bottom`
- `left` – Default.
- `middle`
- `right`
- `texttop`
- `top`

The **align** attribute extends the [HTMLFieldSetElement](#) interface.

2.3.1.3 allowTransparency

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

allowTransparency of type `boolean`

Sets or retrieves whether the object can be transparent.

Returns `true` if the object can be transparent. If `false`, the object is opaque. The default value is `false`.

When the property is set to:

- `false`, the `backgroundColor` property of the object can only be that of the window.
- `true`, the `backgroundColor` property of the object can be set to any value, including the default value of transparent.

The **allowTransparency** attribute extends the following interfaces:

- [HTMLFrameElement](#)
- [HTMLIFrameElement](#)

2.3.1.4 alt

alt of type `DOMString`

Alternate text for user agents not rendering the normal content of this element.

Note This attribute is standard on **img**, **area**, **applet**, and **input** tags.

The alt text is displayed in the object only if the object fails to load and there is no fallback markup. The alt text is not displayed as a tooltip when the mouse pointer hovers over the object.

The **alt** attribute extends the [HTMLObjectElement](#) interface.

2.3.1.5 background

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

background of type `DOMString`

Sets or retrieves the URL of the file that is used as a background picture tiled behind text and graphics in the object.

For Internet Explorer 8 or later, when the browser is in Internet Explorer 8 mode, the value of the **background** attribute depends on the context of the reference to the attribute. When read as a Document Object Model (DOM) attribute, **background** returns an absolute URL. The value specified by the page author is returned when **background** is read as a content attribute, when the page is displayed in an earlier document compatibility mode, or when the page is viewed with an earlier version of the browser.

This attribute extends the following interfaces:

- [HTMLTableCellElement](#)
- [HTMLTableElement](#)

2.3.1.6 BaseHref

BaseHref of type `DOMString`

Read-only attribute that retrieves a string of the URL where the object tag can be found. This is often the href of the document that the object is in, or the value set by a base element.

This attribute extends the [HTMLObjectElement](#) interface.

2.3.1.7 behavior

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

behavior of type `DOMString`

Sets or retrieves how the text scrolls in the marquee.

Possible values are:

- `scroll` – Default. Marquee scrolls in the direction specified by the `direction` property. The text scrolls off the end and starts over each time.
- `alternate` – Marquee scroll direction reverses when its content reaches the edge of the container.
- `slide` – Marquee scrolls in the direction specified by the `direction` property. Text scrolls to the end and stops.

This attribute extends the [HTMLMarqueeElement](#) interface.

2.3.1.8 `bgColor`

`bgColor` of type `DOMString`

Deprecated. Sets or retrieves the background color behind the object.

This attribute extends the following interfaces:

- [HTMLDocument](#)
- [HTMLMarqueeElement](#)
- [HTMLTableSectionElement](#)

2.3.1.9 `bgProperties`

`bgProperties` of type `DOMString`

Sets or retrieves the properties of the background picture.

Possible values are:

- `empty string` – Default. The background can scroll.
- `fixed` – The background cannot scroll.

This attribute extends the [HTMLBodyElement](#) interface.

2.3.1.10 `border`

`border` of type `DOMString`

Sets or retrieves the space between the frames, including the 3-D border.

Setting a `border` to zero or omitting the attribute causes no border to be displayed. Supplying the `border` attribute without a value defaults to a single border.

This attribute extends the following interfaces:

- [HTMLFrameElement](#)
- [HTMLFrameSetElement](#)
- [HTMLIFrameElement](#)
- [HTMLInputElement](#)

2.3.1.11 **borderColor**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

borderColor of type `DOMString`

Sets or retrieves the border color of the object.

Possible values are the color name or RGB value. For more information, see [\[CSS-Level2-2009\]](#) section 4.3.6 Colors.

Returns a six-digit hex value.

To render the color specified, the **border** attribute must be set to an integer greater than zero.

This attribute extends the following interfaces:

- [HTMLFrameElement](#)
- [HTMLFrameSetElement](#)
- [HTMLTableCellElement](#)
- [HTMLTableElement](#)
- [HTMLTableRowElement](#)

2.3.1.12 **borderColorDark**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

borderColorDark of type `DOMString`

Sets or retrieves the color for one of the two colors used to draw the 3-D border of the object.

Possible values are the color name or RGB value. For more information, see [\[CSS-Level2-2009\]](#) section 4.3.6 Colors.

Returns a six-digit hex value.

This property is the opposite of [borderColorLight](#) and must be used with the border property that corresponds to the **border** attribute. This property does not affect the Cascading Style Sheets (CSS) border composite properties.

This attribute extends the following interfaces:

- [HTMLTableCellElement](#)
- [HTMLTableElement](#)
- [HTMLTableRowElement](#)

2.3.1.13 **borderColorLight**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

borderColorLight of type `DOMString`

Sets or retrieves the color for one of the two colors used to draw the 3-D border of the object.

Possible values are the color name or RGB value. For more information, see [\[CSS-Level2-2009\]](#) section 4.3.6 Colors.

Returns a six-digit hex value.

This property is the opposite of [borderColorDark](#) and must be used with the border property that corresponds to the **border** attribute. This property does not affect the Cascading Style Sheets (CSS) border composite properties.

This attribute extends the following interfaces:

- [HTMLTableCellElement](#)
- [HTMLTableElement](#)
- [HTMLTableRowElement](#)

2.3.1.14 **bottomMargin**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

bottomMargin of type `DOMString`

Sets or retrieves the bottom margin of the entire body of the page.

The default value is 15 pixels. If the value is an empty string, the bottom margin is set on the bottom edge of the window or frame.

The specified value overrides the default margin. By default, when the value of this property is set, the opposite margin is set to the same value.

This attribute extends the [HTMLBodyElement](#) interface.

2.3.1.15 **canHaveHTML**

canHaveHTML of type `boolean`

Returns `true` if the element can contain HTML markup, or `false` otherwise.

This attribute is read-only for all objects except the **defaults** object. It is read/write for the **defaults** object.

This attribute extends the [HTMLElement](#) and [HTCElementBehaviorDefaults](#) interface.

2.3.1.16 **charset**

charset of type `DOMString`

Sets or retrieves the character set used to encode the object.

This attribute extends the [HTMLMetaElement](#) interface.

2.3.1.17 **classid**

classid of type `DOMString`

Sets or retrieves the class identifier for the object.

This attribute extends the [HTMLObjectElement](#) interface.

2.3.1.18 clear

clear of type `DOMString`

Sets or retrieves the side on which floating objects are not to be positioned when any block-level element is inserted into the document.

Possible values are:

- `all` – Object is moved below any floating object.
- `left` – Object is moved below any floating object on the left side.
- `right` – Object is moved below any floating object on the right side.
- `none` – Floating objects are allowed on all sides.

This attribute extends the following interfaces:

- [HTMLBlockElement](#)
- [HTMLHeadingElement](#)
- [HTMLParagraphElement](#)

2.3.1.19 color

color of type `DOMString`

Sets or retrieves the color to be used by the object.

Possible values are the color name or RGB value. For more information, see [\[CSS-Level2-2009\]](#) section 4.3.6 Colors.

Returns a six-digit hex value.

This attribute extends the [HTMLHRElement](#) interface.

2.3.1.20 cols

cols of type `long`

Sets or retrieves the number of columns in the table.

This attribute extends the [HTMLTableElement](#) interface.

2.3.1.21 dataFld

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

dataFld of type `DOMString`

Sets or retrieves a field of a given data source, as specified by the **dataSrc** property, to bind to the specified object.

This attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLButtonElement](#)

- [HTMLDivElement](#)
- [HTMLFrameElement](#)
- [HTMLIFrameElement](#)
- [HTMLImageElement](#)
- [HTMLInputElement](#)
- [HTMLLabelElement](#)
- [HTMLLegendElement](#)
- [HTMLMarqueeElement](#)
- [HTMLObjectElement](#)
- [HTMLOptionElement](#)
- [HTMLSelectElement](#)
- [HTMLSpanElement](#)
- [HTMLTableElement](#)
- [HTMLTextAreaElement](#)

2.3.1.22 dataFormatAs

dataFormatAs of type `DOMString`

Sets or retrieves the rendering format for the data supplied to the object.

Possible values are:

- `text` – Default. Data is rendered as text.
- `html` – Data is rendered as HTML.
- `localized-text` – Data is rendered using the locale settings of the client machine.

This attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLButtonElement](#)
- [HTMLDivElement](#)
- [HTMLFrameElement](#)
- [HTMLIFrameElement](#)
- [HTMLImageElement](#)
- [HTMLInputElement](#)
- [HTMLLabelElement](#)
- [HTMLLegendElement](#)

- [HTMLMarqueeElement](#)
- [HTMLObjectElement](#)
- [HTMLOptionElement](#)
- [HTMLSelectElement](#)
- [HTMLSpanElement](#)
- [HTMLTableElement](#)
- [HTMLTextAreaElement](#)

2.3.1.23 dataPageSize

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

dataPageSize of type `long`

Sets or retrieves the number of records displayed in a table bound to a data source.

Use the **firstPage** and **lastPage** methods to navigate directly to the first and last pages of a data-bound table, respectively. Use the **nextPage** and **previousPage** methods to navigate sequentially through the pages of a data-bound table.

This attribute extends the [HTMLTableElement](#) interface.

The **dataPageSize**, **firstPage**, **lastPage**, **nextPage**, and **previousPage** properties are not supported in IE11 Mode, and EdgeHTML Mode.

2.3.1.24 dataSrc

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

dataSrc of type `DOMString`

Sets or retrieves the source of the data for data binding.

Tabular and single-valued data consumers use the **dataSrc** property to specify a binding. The property takes a string that corresponds to the unique identifier of a data source object (DSO) on the page. The string must be prefixed by a number sign (#).

When the **dataSrc** property is applied to a tabular data consumer, the entire data set is repeated by the consuming elements.

When the **dataSrc** property is applied to a table, any contained single-valued consumer objects that specify a **dataFld** property are repeated for each record in the supplied data set. To complete the binding, the binding agent interrogates the enclosing table for its data source. A tabular data consumer contained within another tabular data consumer (table) must specify an explicit **dataSrc**.

This attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLButtonElement](#)
- [HTMLDivElement](#)
- [HTMLFrameElement](#)

- [HTMLIFrameElement](#)
- [HTMLImageElement](#)
- [HTMLInputElement](#)
- [HTMLLabelElement](#)
- [HTMLLegendElement](#)
- [HTMLMarqueeElement](#)
- [HTMLObjectElement](#)
- [HTMLOptionElement](#)
- [HTMLSelectElement](#)
- [HTMLSpanElement](#)
- [HTMLTableElement](#)
- [HTMLTextAreaElement](#)

2.3.1.25 direction

direction of type `DOMString`

Sets or retrieves the direction in which the text should scroll.

Possible values are:

- `left` – Default. Marquee scrolls left.
- `right` – Marquee scrolls right.
- `down` – Marquee scrolls down.
- `up` – Marquee scrolls up.

This attribute extends the [HTMLMarqueeElement](#) interface.

2.3.1.26 dynsrc

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

dynsrc of type `DOMString`

Sets or retrieves the address of a video clip or VRML world to display in the window.

This attribute extends the following interfaces:

- [HTMLImageElement](#)
- [HTMLInputElement](#)

2.3.1.27 frameBorder

frameBorder of type `DOMString`

Sets or retrieves whether to display a border for the frame.

This attribute extends the [HTMLFrameSetElement](#) interface.

2.3.1.28 **frameSpacing**

frameSpacing of type `DOMString`

Sets or retrieves the amount of additional space, in pixels, between the frames.

Possible values are:

- `1` – Default. Inset border is drawn.
- `0` – No border is drawn.
- `no` – No border is drawn.
- `yes` – Inset border is drawn.

Invalid settings default to displaying borders.

The amount of space defined for **frameSpacing** does not include the width of the frame border. Frame spacing can be set on one or more **frameSet** objects and applies to all contained **frameSet** objects, unless the contained object defines a different frame spacing.

This attribute extends the following interfaces:

- [HTMLFrameElement](#)
- [HTMLFrameSetElement](#)
- [HTMLIFrameElement](#)

2.3.1.29 **height**

height of type `DOMString`

Sets or retrieves the height of the object.

Possible values are:

- `height` - Integer that specifies the height of the object, in pixels.
- `percentage` - Integer, followed by a percent sign (%). The value is a percentage of the height of the parent object.

Percentage values are based on the height of the parent object.

When scripting the height property, use either the **pixelHeight** or **posHeight** property to numerically manipulate the height value.

If dynamic changes are intended for the height and width, the original values should be set through style (for example, "`style=height:200px; width:200px`") rather than through the height and width attributes.

This property specifies the calculated height of the object, in pixels. For table rows and table cells, this property has a range of 0 to 32750 pixels.

This attribute extends the following interfaces:

- [HTMLFrameElement](#)
- [HTMLImageElement](#)
- [HTMLMarqueeElement](#)
- [HTMLTableElement](#)
- [HTMLTableRowElement](#)

2.3.1.30 href

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

href of type `DOMString`

Sets or retrieves a destination URL or an anchor point.

For Internet Explorer 8 or later, when the browser is in Internet Explorer 8 mode, the value of the **href** depends on the context of the reference to the attribute. When read as a Document Object Model (DOM) attribute, **href** returns a URL relative to the domain hosting the webpage. When the page is displayed in an earlier document compatibility mode, or the page is viewed with an earlier version of the browser, **href** is read as a content attribute and returns the value specified by the page author.

For Internet Explorer 8 or later, when Protected Mode is enabled and a webpage contains an anchor link that has a named target, Internet Explorer opens the target of the link in a new window when the target has a different integrity level than the webpage that contains the link.

The **img** element does not support the **href** content attribute. In addition, the **href** property is read-only for the **img** DOM object.

If **href** is specified as a blank value (`href=""` or `href=`), executing the link might display the directory that contains the current page, or it might generate an error, depending on other elements on the webpage and the server environment.

This attribute extends the [HTMLImageElement](#) interface.

2.3.1.31 hspace

hspace of type `long`

Sets or retrieves the horizontal margin for the object.

The **hspace** attribute is similar to the [border](#) attribute, except the margins do not have color when the element is a link.

When the **hspace** attribute is set dynamically for an **img** or **iframe** object, the property value will be updated but the display will show no visible change.

This attribute extends the following interfaces:

- [HTMLIFrameElement](#)
- [HTMLInputElement](#)
- [HTMLMarqueeElement](#)

2.3.1.32 leftMargin

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

leftMargin of type `DOMString`

Sets or retrieves the left margin for the entire body of the page.

The default value is 10 pixels. If the value is an empty string, the left margin is the left edge.

The value set on the property overrides the default margin.

By default, when the value of this property is set, the opposite margin is set to the same value.

The **leftMargin** attribute extends the [HTMLBodyElement](#) interface.

2.3.1.33 **loop**

loop of type `long`

Note: EdgeHTML Mode does not provide the loop attribute for the [HTMLImageElement](#) or [HTMLInputElement](#) interfaces.

Sets or retrieves the number of times a marquee, sound, or video clip will loop.

When defining the **marquee** element, possible values are:

- 0, -1 - Loops infinitely. The default value is -1.
- count - Number of times to loop

In each of the following boundary cases, the marquee loops infinitely:

- `<MARQUEE SCROLLAMOUNT=30 LOOP>`This is some scrolling text.`</MARQUEE>`
- `<MARQUEE SCROLLAMOUNT=30 LOOP=0>`This is some scrolling text.`</MARQUEE>`
- `<MARQUEE SCROLLAMOUNT=30 LOOP=>`This is some scrolling text.`</MARQUEE>`

If you set the **loop** property to `null` or 0 in script, a scripting error occurs.

When defining the **image** or **input** elements, possible values are:

- 0, -1 - Loops infinitely. The default value is 1.
- count - Number of times to loop

To restart a sound or video clip after changing its **loop** property, set the **src** property or **dynsrc** property to itself.

This attribute extends the following interfaces:

All Document Modes (All Versions)

- [HTMLMarqueeElement](#)

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

- [HTMLImageElement](#)
- [HTMLInputElement](#)

2.3.1.34 **lowsrc**

lowsrc of type `DOMString`

Sets or retrieves a lower resolution image to display.

If the **src** property is set in code, the new URL starts loading into the image area and aborts the transfer of any image data that is already loading into the same area. If you want to alter the **lowsrc** property, you must do so before setting the **src** property. If the URL in the **src** property references an image that is not the same size as the image cell it is loaded into, the source image is scaled to fit.

The **lowsrc** attribute extends the following interfaces:

- [HTMLImageElement](#)
- [HTMLInputElement](#)

2.3.1.35 Methods

Methods of type `DOMString`

Sets or retrieves the comma-separated list of HTTP methods that are supported by the object for public use.

The **Methods** attribute extends the [HTMLAnchorElement](#) interface.

2.3.1.36 name

name of type `DOMString`

Sets or retrieves the name of the object. In the case of **HTMLFrameSetElement**, the **name** property identifies which frame displays the content of a linked document.

The **name** attribute extends the [HTMLFrameSetElement](#) interface.

2.3.1.37 noResize

noResize of type `boolean`

Sets or retrieves whether the user can resize the frame.

Returns `false` if the user can resize the frame, or `true` otherwise. The default value is `false`.

The **noResizes** attribute extends the [HTMLIFrameElement](#) interface.

2.3.1.38 noWrap

Note: EdgeHTML Mode does not provide the **noWrap** attribute for the [HTMLBodyElement](#), [HTMLDDElement](#), or [HTMLDTElement](#) interfaces.

noWrap of type `boolean`

Sets or retrieves whether the browser automatically performs word wrap.

Returns `false` if the browser automatically wraps the text, or `true` otherwise. The default value is `false`.

Be aware of the following when using the **noWrap** property in conjunction with the **width** attribute of **table** or **td** elements:

- **Wordwrap** still occurs in a **td** element that has its **width** attribute set to a value smaller than the unwrapped content of the cell, even if the **noWrap** property is set to `true`. Therefore, the **width** attribute takes precedence over the **noWrap** property in this scenario.
- If a **td** element has its **noWrap** set to `true` and the **width** attribute of its **table** element is set to a smaller dimension than the rendered content of the **td** element, **wordwrap** does not occur. In this case, the **noWrap** setting takes precedence over the **width** attribute.

The **noWrap** attribute extends the following interfaces:

All Document Modes (All Versions)

- [HTMLDivElement](#)

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

- HTMLBodyElement
- HTMLDDElement
- HTMLDTElement

2.3.1.39 **rightMargin**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

rightMargin of type `DOMString`

Sets or retrieves the right margin for the entire body of the page.

If the value is an empty string, the right margin is on the right edge.

The value set on the property overrides the default margin.

By default, when you set the value of this property, the opposite margin is set to the same value. The property has a default value of 10.

This attribute extends the [HTMLBodyElement](#) interface.

2.3.1.40 **scroll**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

scroll of type `DOMString`

Sets or retrieves a value that indicates whether the scroll bars are turned on or off.

Possible values are:

- `yes` – Default. Scroll bars are turned on.
- `no` – Scroll bars are turned off.
- `auto` – Scroll bars are displayed when the page content exceeds the client area.

When you use the `!DOCTYPE` declaration to specify standards-compliant mode, this attribute applies to the **html** element. When standards-compliant mode is not specified, as with earlier versions of Internet Explorer, this attribute applies to the **body** element, not the **html** element.

This attribute extends the [HTMLBodyElement](#) interface.

2.3.1.41 scrollAmount

scrollAmount of type `long`

Sets or retrieves the number of pixels that the text scrolls between each subsequent rendering of the marquee. The default value is 6 pixels.

This attribute extends the [HTMLMarqueeElement](#) interface.

2.3.1.42 scrollDelay

scrollDelay of type `long`

Sets or retrieves the speed of the text scroll in a marquee. The default value is 85 milliseconds.

This attribute extends the [HTMLMarqueeElement](#) interface.

2.3.1.43 start

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

start of type `DOMString`

Sets or retrieves the time that a video clip file should begin playing.

Possible values are:

- `fileopen` – Default. Video begins as soon as it starts loading.
- `mouseover` – Video begins when the user moves the mouse over the animation.

The start property applies only to **img** elements with the [dynsrc](#) property specified.

This attribute extends the following interfaces:

- [HTMLImageElement](#)
- [HTMLInputElement](#)

2.3.1.44 tabStop

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

tabStop of type `boolean`

Set to `true` to enable an element behavior to receive focus and participate in tabbing sequence; or `false` otherwise. The default value is `false`.

This attribute is defined by the [HTCElementBehaviorDefaults](#) interface.

2.3.1.45 topMargin

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

topMargin of type `DOMString`

Sets or retrieves the margin for the top of the page.

The default value is 15 pixels. If the value is an empty string or is set to 0, the top margin is set on the top edge of the window or frame.

The specified value overrides the default margin.

By default, when the value of this property is set, the opposite margin is set to the same value.

This attribute extends the [HTMLBodyElement](#) interface.

2.3.1.46 trueSpeed

trueSpeed of type `boolean`

Sets or retrieves whether the position of the marquee is calculated using the `scrollDelay` and `scrollAmount` properties and the actual time elapsed from the last clock tick.

Possible values are:

- `false` – Default. Marquee computes movement based on 60-millisecond ticks of the clock. This means every **scrollDelay** value under 60 is ignored, and the marquee advances the amount of **scrollAmount** each 60 milliseconds. For example, if **scrollDelay** is 6 and **scrollAmount** is 10, the marquee advances 10 pixels every 60 milliseconds.
- `true` - Marquee advances the pixel value of **scrollAmount** by the number of milliseconds set for **scrollDelay**. For example, the marquee would advance 10 pixels for every 6 milliseconds if **scrollDelay** is 6, **scrollAmount** is 10, and the value of **trueSpeed** is true.

The **trueSpeed** attribute indicates that the exact **scrollDelay** value specified is used to move the marquee text. If **trueSpeed** is `false`, all **scrollDelay** values of 59 or less are rounded up to 60 milliseconds.

This attribute extends the [HTMLMarqueeElement](#) interface.

2.3.1.47 urn

urn of type `DOMString`

Sets or retrieves a Uniform Resource Name (URN) for a target document.

URNs are an adjunct to URLs. A URL, which is the address used on the World Wide Web, specifies a particular file on a particular machine. A URN specifies the identity of a resource instead of its location.

This attribute extends the [HTMLAnchorElement](#) interface.

urn of type `DOMString`

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

The URN that uniquely identifies an HTC. This value enables events to be uniquely identified when multiple behaviors may fire events of the same name. When an event is fired, the event object's **srcUrn** property is set to the URN of the behavior that fired the event.

This attribute is used by the [PUBLIC:COMPONENT](#) element and can be accessed with the [HTCComponentElement](#) interface.

2.3.1.48 vAlign

vAlign of type `DOMString`

Sets or retrieves whether the caption appears at the top or bottom of the table.

Possible values are:

- `top` – Default. Places the caption at the top of the table.
- `bottom` – Places the caption at the bottom of the table.

When this property is set dynamically, the value of the property will be updated, but there will be no visible change in the display.

This attribute extends the [HTMLTableCaptionElement](#) interface.

2.3.1.49 value

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

value of type `any`

Sets or retrieves a value associated with the [PUBLIC:PROPERTY](#) element.

This attribute is defined by the [HTCPropertyElement](#) interface.

2.3.1.50 viewInheritStyle

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

viewInheritStyle of type `boolean`

Returns `true` if a viewlink should inherit styles from the primary document; or `false` otherwise. The default value is `true`.

This attribute is defined by the [HTCElementBehaviorDefaults](#) interface.

2.3.1.51 viewMasterTab

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

viewMasterTab of type `boolean`

Returns `true` if the master element of a viewlink is included in the tab sequence of the primary document; or `false` otherwise. The default value is `true`.

This attribute is defined by the [HTCElementBehaviorDefaults](#) interface.

2.3.1.52 vspace

vspace of type `long`

Sets or retrieves the vertical margin, in pixels, for the object.

This property is similar to the **border** property, except the margins do not have color when the object is a link.

When this property is set dynamically for an **img** or **iframe** element, the property value will be updated but the display will show no visible change.

This attribute extends the following interfaces:

- [HTMLIFrameElement](#)
- [HTMLInputElement](#)
- [HTMLMarqueeElement](#)

2.3.1.53 width

width of type `DOMString`

Retrieves the width of the object, in pixels.

Possible values are:

- `width` – Integer that specifies the width of the object, in pixels, or as a percentage.
- `percentage` – String that specifies an integer value followed by a %. The value is a percentage of the width of the parent object.

If you specify the **width** property of an **img** element, but not the **height** property, the resulting height of the image is sized proportionally to the specified **width** property and the actual height, in pixels, of the source image file.

If you specify the **width** property of an **img**, and the height and width of the image in the source file are identical, the height of the image matches the width.

If dynamic changes are intended for the height and width, the original values should be set through style (for example, `style='height:200px; width:200px'`) rather than through the **height** and **width** attributes.

The **width** attribute extends the following interfaces:

- [HTMLFrameElement](#)
- [HTMLInputElement](#)
- [HTMLMarqueeElement](#)

2.3.1.54 wrap

wrap of type `DOMString`

Sets or retrieves how to handle word wrapping in the object.

Possible values are:

- `soft` – Default. Text is displayed wrapped and submitted without CR/LF characters.
- `hard` – Text is displayed wrapped and submitted with CR/LF characters.
- `off` – Word wrapping is disabled. The lines appear exactly as the user types them.

This attribute extends the [HTMLTextAreaElement](#) interface.

2.3.2 DOM Attributes Only

This section contains a list of attributes that are accessible only through the object model.

2.3.2.1 `alinkColor`

alinkColor of type `DOMString`

Sets or gets the color of all active links in the document.

Possible values are the color name or RGB value. For more information, see [\[CSS-Level2-2009\]](#) section 4.3.6 Colors. Returns a six-digit hex value. The default value is `#0000FF`.

This is a DOM attribute only.

The **alinkColor** attribute extends the [HTMLDocument](#) interface.

2.3.2.2 `altHtml`

altHtml of type `DOMString`

Returns the alternative HTML markup that would be rendered if the object failed to load.

During fallback, the object fires the **onerror** event to determine if the event handler can process the alternative HTML. The default action is to replace the failed object with the alternative HTML.

This DOM attribute is write-only.

This attribute extends the [HTMLObjectElement](#) interface.

2.3.2.3 `contentWindow`

contentWindow of type `Window`

Retrieves the window object of the specified **frame** or **iframe**.

This DOM attribute is read-only.

This attribute extends the [HTMLFrameElement](#) and [HTMLIFrameElement](#) interface.

2.3.2.4 `dir`

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

dir of type `DOMString`

Sets or retrieves a value that indicates the reading order of the object.

Possible values are:

- `ltr` – Default. Content flows from left to right.
- `rtl` – Content flows from right to left.

Unless explicitly set, the **dir** property has no return value when accessed in script.

The **dir** property does not affect alphanumeric characters in Latin documents. These characters always render `ltr`. However, the property does affect punctuation characters in Latin documents. For example, punctuation marks such as periods and question marks will render to the left of a sentence when the **dir** property is set to `rtl`.

The value of **dir** property has no effect on the orientation of coordinates for an object's positioning properties. For example, the **left** property and the **right** property perform the same placement in both

cases. However, when both the **left** and **right** properties are specified, the **left** property takes precedence when the **dir** property is set to `ltr`. Likewise, the **right** property takes precedence when the **dir** property is set to `rtl`.

This is a DOM attribute only.

This attribute extends the [HTMLDocument](#) interface.

2.3.2.5 encoding

encoding of type `DOMString`

Sets or retrieves the MIME encoding for the form.

As defined in [\[HTML\]](#), this is a DOM attribute only and reflects the value of the **enctype** attribute in the markup.

This attribute has a default value of `application/x-www-form-urlencoded`.

This attribute extends the [HTMLFormElement](#) interface.

2.3.2.6 fgColor

fgColor of type `DOMString`

Sets or retrieves the foreground (text) color of the document.

Possible values are the color name or RGB value. For more information, see [\[CSS-Level2-2009\]](#) section 4.3.6 Colors. Returns a six-digit hex value. The default value is `#000000`.

This is a DOM attribute only.

This attribute extends the [HTMLDocument](#) interface.

2.3.2.7 fileCreatedDate

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

fileCreatedDate of type `DOMString`

Retrieves the date the file was created.

This DOM attribute is read-only.

This attribute extends the [HTMLImageElement](#) interface.

2.3.2.8 fileModifiedDate

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

fileModifiedDate of type `DOMString`

Retrieves the date the file was last modified.

This DOM attribute is read-only.

This attribute extends the [HTMLImageElement](#) interface.

2.3.2.9 **fileSize**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

fileSize of type `DOMString`

Retrieves the file size.

This DOM attribute is read-only.

This attribute extends the [HTMLImageElement](#) interface.

2.3.2.10 **fileUpdatedDate**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

fileUpdatedDate of type `DOMString`

Retrieves the date the file was last updated.

This DOM attribute is read-only.

This attribute extends the [HTMLImageElement](#) interface.

2.3.2.11 **hash**

hash of type `DOMString`

Sets or retrieves the subsection of the [href](#) property that follows the number sign (#). If there is no number sign, this property returns an empty string.

This DOM attribute is read-only.

This attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)

2.3.2.12 **host**

host of type `DOMString`

Sets or retrieves the [hostname](#) and [port](#) number of the location or URL.

The **host** property is the concatenation of the **hostname** and **port** properties, separated by a colon (hostname:port). When the **port** property is `null`, the **host** property is the same as the **hostname** property.

The **host** property may be set at any time, although it is safer to set the **href** property to change a location. If the specified host cannot be found, an error is returned.

This DOM attribute is read-only.

This attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)

2.3.2.13 **hostname**

hostname of type `DOMString`

Sets or retrieves the host name part of the location or URL. If no host name is available, this property returns an empty string.

This is a DOM attribute only.

This attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)

2.3.2.14 **indeterminate**

indeterminate of type `boolean`

Set to `true` to indicate that a checkbox is neither checked nor cleared (unchecked); or `false` otherwise. The default value is `false`.

The **indeterminate** attribute can be used to indicate whether the user has acted on a control. For example, setting **indeterminate** to `true` causes the check box to appear dimmed, indicating neither a checked nor cleared state.

The value of the **indeterminate** attribute acts independently of the values of the **checked** and [status](#) attributes. Creating an indeterminate state is different from disabling the control. A check box in the indeterminate state can still receive the focus. When the user clicks an indeterminate control, the indeterminate state turns off and the check box toggles between cleared and checked as usual.

This is a DOM attribute only. There is no equivalent way of specifying **indeterminate** in the markup.

This attribute extends the [HTMLInputElement](#) interface.

2.3.2.15 **isDisabled**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

isDisabled of type `boolean`

Set to `true` to indicate that the user cannot interact with the object; or `false` otherwise.

This DOM attribute is read-only.

The **isDisabled** attribute extends the [HTMLElement](#) interface.

2.3.2.16 **isMultiLine**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

isMultiLine of type `boolean`

Set to `true` to indicate that the content contains more than one line; or `false` if the content contains exactly one line.

This DOM attribute is read-only.

The **isMultiLine** attribute extends the [HTMLElement](#) interface.

2.3.2.17 linkColor

linkColor of type `DOMString`

Sets or retrieves the color of the document links.

Possible values are the color name or RGB value. For more information, see [\[CSS-Level2-2009\]](#) section 4.3.6 Colors. Returns a six-digit hex value. The default value is `#0000ff`.

The **linkColor** property can be set by using the **body** object's **onload** event. However, you cannot use the **onload** event to set the **link** property.

This is a DOM attribute only.

The **linkColor** attribute extends the [HTMLDocument](#) interface.

2.3.2.18 mimeType

Note: EdgeHTML Mode does not provide the **mimeType** attribute for the [HTMLImageElement](#) interface.

mimeType of type `DOMString`

Retrieves the MIME type for the file.

Returns the registered file type of the image or anchor's target. If the object hasn't loaded yet, the empty string is returned. The file type string returned need not be a standard MIME type.

This is a DOM attribute only.

The **mimeType** attribute extends the following interfaces:

All Document Modes (All Versions)

- [HTMLAnchorElement](#)

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

- `HTMLImageElement`

2.3.2.19 nameProp

Note: EdgeHTML Mode does not provide the **nameProp** attribute for the [HTMLImageElement](#) interface.

nameProp of type `DOMString`

Retrieves the file name specified in the `href` or `src` property of the object.

This DOM attribute is read-only.

The **nameProp** attribute extends the following interfaces:

All Document Modes (All Versions)

- [HTMLAnchorElement](#)

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

- `HTMLImageElement`

2.3.2.20 **object**

object of type `any`

Retrieves the contained object. The **object** attribute may return an object reference of any type and is not limited to DOM objects.

This DOM attribute is read-only.

The **object** attribute extends the [HTMLObjectElement](#) interface.

2.3.2.21 **parentDocument**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

parentDocument of type `DOMString`

Returns the document interface of the parent object, or null if the current object is the top-most document.

This is a DOM attribute only.

The **parentDocument** attribute extends the [HTMLDocument](#) interface.

2.3.2.22 **pathname**

pathname of type `DOMString`

Sets or retrieves the file name or path specified by the object.

This is a DOM attribute only.

The **pathname** attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)

2.3.2.23 **port**

port of type `DOMString`

Sets or retrieves the port number associated with a URL.

The port will resolve based on the default port for the protocol set in the **href** attribute: 21 for FTP, 80 for HTTP, and so forth. Proprietary protocols that do not require a port may return 0 or an empty string.

This is a DOM attribute only.

The **port** attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)

2.3.2.24 **protocol**

Note: EdgeHTML Mode does not provide the **protocol** attribute for the [HTMLImageElement](#) interface.

protocol of type `DOMString`

Sets or retrieves the protocol portion of a URL.

The **protocol** property specifies how to transfer information from the host to the client.

The **document**, **img**, and **location** objects expose the **protocol** property as read-only. The **location.protocol** property returns the initial substring of a URL, including the first colon (for example, `http:`). However, the **document.protocol** property returns the expanded text of the protocol acronym. For example, it returns the `http` protocol as Hypertext Transfer Protocol.

This is a DOM attribute only.

The **protocol** attribute extends the following interfaces:

All Document Modes (All Versions)

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

- `HTMLImageElement`

2.3.2.25 **protocolLong**

protocolLong of type `DOMString`

Gets the registered long name of the protocol, such as Hypertext Transfer Protocol, used in the URL associated with the anchor.

This is a DOM attribute only.

The **protocolLong** attribute extends the section [HTMLAnchorElement](#) interface.

2.3.2.26 **search**

search of type `DOMString`

Sets or retrieves the substring of the **href** property that follows the question mark.

The substring that follows the question mark is the query string or form data.

This is a DOM attribute only.

The **search** attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)

2.3.2.27 **status**

status of type `any`

Sets or retrieves `true` to indicate that the control is selected; or `false` otherwise. The **status** property of a **textArea** object has a default value of `null`.

Setting the **status** updates the value of the property and causes the [onpropertychange](#) event to fire. However, this change has no visual effect on the object.

This is a DOM attribute only.

The **status** attribute extends the following interfaces:

- [HTMLButtonElement](#)
- [HTMLInputElement](#)
- [HTMLTextAreaElement](#)

2.3.2.28 styleSheet

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

styleSheet of type `CSSStyleSheet`

Retrieves an interface pointer that provides access to the style sheet object's properties and methods. A `null` value for **p** indicates that there is no style sheet for the object.

This DOM attribute is read-only.

The **styleSheet** attribute extends the [HTMLStyleElement](#) and [HTMLLinkElement](#) interfaces.

2.3.2.29 uniqueID

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

uniqueID of type `DOMString`

Retrieves an automatically generated, unique identifier for the object.

When you apply this property to the **document** object, the browser automatically generates a new ID that you can assign to an element's **id** property.

A new ID is generated and assigned to the element the first time the property is retrieved. Every subsequent access to the property on the same element returns the same ID.

Note: The unique ID generated is not guaranteed to be the same every time the page is loaded.

This is a DOM attribute only.

The **uniqueID** attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)
- [HTMLAreasCollection](#)
- [HTMLBlockElement](#)
- [HTMLButtonElement](#)
- [HTMLDDElement](#)
- [HTMLDivElement](#)
- [HTMLDocument](#)

- [HTMLDTElement](#)
- [HTMLFieldSetElement](#)
- [HTMLFormElement](#)
- [HTMLFrameElement](#)
- [HTMLHRElement](#)
- [HTMLInputElement](#)
- [HTMLIsIndexElement](#)
- [HTMLLabelElement](#)
- [HTMLLegendElement](#)
- [HTMLMarqueeElement](#)
- [HTMLMetaElement](#)
- [HTMLObjectElement](#)
- [HTMLOptionElement](#)
- [HTMLSelectElement](#)
- [HTMLSpanElement](#)
- [HTMLTextAreaElement](#)

2.3.2.30 **uniqueNumber**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

uniqueNumber of type `DOMString`

Retrieves the element's unique number.

The number is obtained by removing the string prefix from the element's [uniqueID](#).

This is a DOM attribute only.

The **uniqueNumber** attribute extends the following interfaces:

- [HTMLAnchorElement](#)
- [HTMLAreaElement](#)
- [HTMLAreasCollection](#)
- [HTMLBlockElement](#)
- [HTMLButtonElement](#)
- [HTMLDDElement](#)
- [HTMLDivElement](#)
- [HTMLDocument](#)

- [HTMLDTElement](#)
- [HTMLFieldSetElement](#)
- [HTMLFormElement](#)
- [HTMLFrameElement](#)
- [HTMLHRElement](#)
- [HTMLInputElement](#)
- [HTMLIsIndexElement](#)
- [HTMLLabelElement](#)
- [HTMLLegendElement](#)
- [HTMLMarqueeElement](#)
- [HTMLMetaElement](#)
- [HTMLObjectElement](#)
- [HTMLOptionElement](#)
- [HTMLSelectElement](#)
- [HTMLSpanElement](#)
- [HTMLTextAreaElement](#)

2.3.2.31 **url**

url of type `DOMString`

Sets or retrieves a URL string.

In Internet Explorer 8, relative URL strings are converted to absolute URLs when retrieved.

This is a DOM attribute only.

The **url** attribute extends the [HTMLMetaElement](#) interface.

2.3.2.32 **viewLink**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

viewLink of type `document`

Sets or retrieves the document object that supplies content to the master element.

A viewlink displays its document fragment in the primary document at the location of the master HTML Components (HTC) element. Components declared as a viewlink are encapsulated from the primary document and do not participate in the CSS style cascade or tab order unless allowed to do so by the component author.

This DOM attribute is read-only.

The **viewLink** attribute is defined by the [HTCElementBehaviorDefaults](#) interface.

See also [viewLinkContent](#).

2.3.2.33 vlinkColor

vlinkColor of type `DOMString`

Sets or retrieves the color of the links that the user has visited.

Possible values are the color name or RGB value. For more information, see [\[CSS-Level2-2009\]](#) section 4.3.6 Colors. Returns a six-digit hex value. The default value is #800080.

This is a DOM attribute only.

The **vlinkColor** attribute extends the [HTMLDocument](#) interface.

2.3.3 Content Attributes Only

This section contains a list of attributes that are declared in markup only. None of them are implemented in EdgeHTML Mode.

2.3.3.1 application

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

Determines whether the content of the frame is an HTML Application (HTA), which is exempt from the browser security model.

Can be one of the following values:

- `yes` – All content of the frame or iframe is trusted.
- `no` – Default. Browser security rules for unsafe content are applied.

This attribute is available in markup only for **frame** and **iframe** elements.

2.3.3.2 atomicselection

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

Specifies whether the element and its contents must be selected as a whole, indivisible unit.

Can be one of the following values:

- `false` – Default. The element content can be selected individually.
- `true` – The element and its content can be selected only as a single unit.

If the document is not in atomic selection mode, the **atomicselection** attribute is ignored. To turn on the atomic selection mode, run the `IDM_ATOMICELECTION` command with the value of `true`.

The **atomicselection** attribute is available only in markup for all elements.

See also [unselectable](#).

2.3.3.3 event

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Attribute of the [PUBLIC:ATTACH](#) element that specifies the name of any standard event (prefixed with "on") or one of the following HTML Component events:

- [oncontentready](#) – fires when the master element has been parsed completely
- [oncontentsave](#) – fires before content that is attached to an element is saved or copied
- [ondetach](#) – fires before a behavior is detached from a master element
- [ondocumentready](#) – fires when the primary document has been parsed completely

The following example attaches the `fnInit()` function to the `oncontentready` event:

```
<PUBLIC:COMPONENT tagName=TOOLBAR_BUTTON>
  <PUBLIC:ATTACH event="oncontentready" onevent="fnInit()" />
</PUBLIC:COMPONENT>
```

The **event** attribute is declared in markup only.

2.3.3.4 for

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Attribute of the [PUBLIC:ATTACH](#) element that identifies the source of the event. The value of **for** may be one of the following:

- `document` – an event of the **document** object
- `element` – Default. An event of the master element to which the behavior is attached.
- `window` – an event of the **window** object.

The following example attaches the **onclick** event to the `ExpandCollapse()` event handler:

```
<PUBLIC:ATTACH EVENT="onclick" ONEVENT="ExpandCollapse()" />
```

The **for** attribute is declared in markup only.

See also [event](#) and [onevent](#).

2.3.3.5 get

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

String that specifies the function to be called whenever the value of the property is retrieved. Any [PUBLIC:PROPERTY](#) element that specifies a **get** attribute without specifying a [put](#) attribute is a read-only property.

The **get** attribute is declared in markup only.

2.3.3.6 implementation

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

String that specifies the HTML Component (HTC) file that contains the tag definition.

This attribute is required when using the **IMPORT** processing instruction, and must include one of the following values:

- `#default` – an element behavior built into Microsoft Internet Explorer 5.5 or later
- `#objectID` – string that specifies the id attribute of an object tag
- `sImplementation`

The **implementation** attribute is declared in markup only.

2.3.3.7 **internalName**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

The name by which the property or method is called within the component. This internal name must be declared globally before it can be referenced; otherwise, a scripting error occurs, indicating that the name is undefined. If no internal name is specified, the [name](#) attribute is used instead.

The **internalName** attribute is declared in markup only.

This attribute is used by [PUBLIC:METHOD](#) and [PUBLIC:PROPERTY](#).

2.3.3.8 **lightWeight**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Set to `true` to indicate that the HTC file does not contain markup that would need to be parsed and rendered for each custom tag that is parsed in the primary document; or `false` otherwise.

The **lightWeight** attribute is declared in markup only.

This attribute is used by [PUBLIC:COMPONENT](#).

2.3.3.9 **literalContent**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

String that specifies whether the content contained within the custom element it is to be treated as a data island. Although the HTC may still treat any content as a data island, literal content is not automatically parsed and rendered in the primary document. This attribute is only valid when the HTC defines an element behavior, which requires the use of the [tagName](#) attribute.

The **literalContent** attribute can contain one of the following values:

- `false` – Text and markup within the custom element is parsed and rendered normally.
- `true` – Content within the first opening and first closing tags of the element defined by **tagName** is treated as a data island.
- `nested` – Content between the first opening and last closing tags of the element defined by **tagName** is treated as a data island. This mode allows custom tags to be nested in the primary document but requires the HTC to import the custom element namespace.

The following example demonstrates how to read nested literal content in an HTC. First, the HTC imports the *myns:mytag* custom element into a viewlink, then it sets the body of the component from literal content of the master element.

```
<HTML xmlns:myns>
```

```

<HEAD>
  <?import namespace="myns" implementation="mytag"/>
</HEAD>
<PUBLIC:COMPONENT TAGNAME="mytag" LITERALCONTENT="nested">
  <PUBLIC:DEFAULTS VIEWLINKCONTENT />
  <PUBLIC:ATTACH EVENT="oncontentready" ONEVENT="main()"/>
</PUBLIC:COMPONENT>
<SCRIPT>
  function main()
  {
    document.body.innerHTML = element.innerHTML;
    .
    .
    .
  }
</SCRIPT>
</HTML>

```

The **literalContent** attribute is declared in markup only.

This attribute is used by the [PUBLIC:COMPONENT](#) element.

2.3.3.10 namespace

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

Any string that specifies the namespace used as a prefix to custom tags, or specifies a Uniform Resource Name (URN) that uniquely identifies the namespace.

The **namespace** attribute is required when using the [?IMPORT?](#) processing instruction.

This attribute is declared in markup only.

2.3.3.11 onevent

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Attribute of the [PUBLIC:ATTACH](#) element that specifies the event handler script or function name.

The following example attaches the `fnInit()` function to the `oncontentready` event:

```

<PUBLIC:COMPONENT tagName=TOOLBAR BUTTON>
  <PUBLIC:ATTACH event="oncontentready" onevent="fnInit()"/>
</PUBLIC:COMPONENT>

```

The **onevent** attribute is declared in markup only.

2.3.3.12 persist

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Set to `true` to persist the property as part of the page; or `false` otherwise.

The **persist** attribute is declared in markup only.

This attribute is used by the [PUBLIC:PROPERTY](#) element.

2.3.3.13 **put**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

String that specifies the function to be called when the value of the property is set. A `PUBLIC:PROPERTY` element that specifies both a [get](#) and **put** attribute is a read/write property.

The **put** attribute is declared in markup only.

This attribute is used by the [PUBLIC:PROPERTY](#) element.

2.3.3.14 **supportsEditMode**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Set to `true` to specify whether the content within the HTC is editable; or `false` otherwise.

The **supportsEditMode** attribute is declared in markup only.

This attribute is used by the [PUBLIC:COMPONENT](#) element.

2.3.3.15 **tagName**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

String that specifies the name of the custom tag, which is defined in the HTC and imported into the primary document. This attribute is only valid for an HTC file that defines an element behavior.

The **tagName** attribute is declared in markup only.

This attribute is used by the [PUBLIC:COMPONENT](#) element.

2.3.3.16 **unselectable**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

Specifies that an element cannot be selected.

Note: Setting the **unselectable** attribute to `off` does not ensure that an element is selectable. One example is an HTML Application (HTA) with the **selection** attribute set to `no`. Elements in the body of the HTA cannot be selected, even if the **unselectable** attribute for an element is set to `off`.

When you click an element with the **unselectable** attribute set to `on`, any existing current selection is not destroyed.

An element with the **unselectable** attribute set to `on` can be included in a selection that starts somewhere outside the element.

The **unselectable** attribute is implemented as an `84xpan`d. Setting the **84xpan**d property of the **document** object to `false` precludes the functionality of all `expand`os.

The **unselectable** attribute is declared in markup only for all elements.

See also [atomicselection](#).

2.3.3.17 **viewLinkContent**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Set to `true` to use the markup in the `.htc` file is used as the `viewlink`; or `false` otherwise.

Here is a simple `.htc` file that uses a declaration to set the `viewlink` in the `PUBLIC:DEFAULTS` element.

```
<!-- "Toolbar_Button.htc" -->
<PUBLIC:COMPONENT tagName="TOOLBAR BUTTON">
  <PUBLIC:DEFAULTS viewLinkContent="true"/>
</PUBLIC:COMPONENT>

<BODY>
  Someday this will be a toolbar button.
</BODY>
```

Setting this attribute in the `PUBLIC:DEFAULTS` element causes the current HTC markup to be saved as a document fragment in the **HTCElementBehaviorDefaults::viewLink** property.

The **viewLinkContent** attribute is declared in markup only by the [PUBLIC:DEFAULTS](#) element.

See also [viewInheritStyle](#) and [viewMasterTab](#).

2.3.3.18 xmlns

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

Declares a namespace for custom tags in an HTML document.

The **xmlns** attribute is declared in markup only.

See also [namespace](#).

2.3.4 Event Attributes

This section contains a list of attributes that bind events to event handlers.

2.3.4.1 onactivate

onactivate of type `Function`

Occurs when the object is set as the active element, which is the element that has focus when the parent document has focus. The active element retains focus in the parent document even when focus is shifted from the parent to another application.

To invoke, click an element (other than the active element), use the keyboard to move focus, or invoke the **focus()** method.

- Bubbles: Yes
- Cancelable: No
- Context Info: `fromElement`, `srcElement`

This attribute is an extension to [HTMLInputElement](#).

See also [onbeforeactivate](#), [onbeforedeactivate](#).

2.3.4.2 onafterupdate

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

onafterupdate of type `Function`

Occurs on a databound object after successfully updating the associated data in the data source object.

To invoke, change the data that the object contains.

- Bubbles: Yes
- Cancelable: No
- Context Info: None

This attribute is an extension to [HTMLInputElement](#).

See also [onbeforeupdate](#).

2.3.4.3 onbeforeactivate

onbeforeactivate of type `Function`

Occurs immediately before the object is set as the active element.

To invoke, click an element (other than the active element), use the keyboard to move focus, or invoke the **focus()** method.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: `fromElement`, `srcElement`

This attribute is an extension to [HTMLInputElement](#).

See also [onactivate](#), [onbeforedeactivate](#).

2.3.4.4 onbeforecopy

onbeforecopy of type `Function`

Fires on the source object before the selection is copied to the system clipboard.

Return `true` from the event handler to disable the **Copy** shortcut.

To invoke, select text and right-click or press Ctrl+C.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: `dataTransfer`

This attribute is an extension to [HTMLInputElement](#).

See also [onbeforecut](#), [onbeforepaste](#).

2.3.4.5 onbeforecut

onbeforecut of type `Function`

Occurs on the source object before the selection is deleted from the document.

Return `true` from the event handler to disable the **Cut** shortcut.

To invoke, select text and right-click or press Ctrl+X.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: `dataTransfer`

This attribute is an extension to [HTMLInputElement](#).

See also [onbeforecopy](#), [onbeforepaste](#).

2.3.4.6 onbeforedeactivate

onbeforedeactivate of type `Function`

Occurs immediately before the active element is changed from the current element to another element in the parent document.

To invoke, click an element (other than the active element), use the keyboard to move focus, or invoke the **focus()** method.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: `fromElement`, `srcElement`

This attribute is an extension to [HTMLInputElement](#).

See also [onactivate](#), [onbeforeactivate](#).

2.3.4.7 onbeforeeditfocus

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onbeforeeditfocus of type `Function`

Occurs before an object contained in an editable element enters a UI-activated state or when an editable container object is control selected.

To invoke, press the Enter key, click an object when it has focus, or double-click an object.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: `fromElement`, `srcElement`

This attribute is an extension to [HTMLInputElement](#).

2.3.4.8 onbeforepaste

onbeforepaste of type `Function`

Occurs on the target before the selection is pasted from the clipboard into the document.

Return `true` from the event handler to disable the **Paste** shortcut.

To invoke, select text and right-click or press Ctrl+V.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: `dataTransfer`

This attribute is an extension to [HTMLInputElement](#).

See also [onbeforecopy](#), [onbeforecut](#).

2.3.4.9 onbeforeunload

onbeforeunload of type `Function`

Occurs prior to a page being unloaded.

To invoke, close the browser window; navigate to another page by entering a new address, selecting a Favorite, or clicking an anchor that refers to another webpage; click the Back, Forward, Refresh, or Home button; invoke `anchor.click()`, `document.write()`, `document.open()`, `document.close()`, `location.replace()`, `location.reload()`, `window.close()`, `window.navigate()`, or set a new value of `location.href` property; submit a form, or invoke `form.submit()`.

Return a string from the event handler to prompt the user with the option of staying on the current page. The statement that appears in the dialog box ("Are you sure you want to navigate away from this page? . . . Press OK to continue, or Cancel to stay on the current page") cannot be removed or altered.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: None

The **onbeforeunload** attribute extends the following interfaces:

- [HTMLBodyElement](#)
- [HTMLFrameSetElement](#)

2.3.4.10 onbeforeupdate

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

onbeforeupdate of type `Function`

Occurs on a databound object before updating the associated data in the data source object.

To invoke, change the data that the object contains.

- Bubbles: Yes

- Cancelable: Yes
- Context Info: None

This attribute is an extension to [HTMLElement](#).

See also [onafterupdate](#).

2.3.4.11 **onbounce**

onbounce of type `Function`

Occurs when the contents of a marquee element begin to scroll in the opposite direction.

To invoke, set the **behavior** attribute of the marquee to `alternate`.

- Bubbles: No
- Cancelable: Yes
- Context Info: None

The **onbounce** attribute extends the [HTMLMarqueeElement](#) interface.

2.3.4.12 **oncellchange**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

oncellchange of type `Function`

Occurs when the data changes in the data provider.

To invoke, cause the data in the data source to change.

- Bubbles: Yes
- Cancelable: No
- Context Info: dataFld, qualifier, recordset

This attribute is an extension of [HTMLElement](#).

See also [onafterupdate](#), [onbeforeupdate](#).

2.3.4.13 **oncontentready**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

oncontentready of type `Function`

Occurs when the content of the master element, to which a behavior is attached, has been parsed.

If the [literalContent](#) attribute of the [PUBLIC:COMPONENT](#) element is `true`, the literal content of the element behavior is stored in the **innerHTML** property.

The following example demonstrates how to attach and respond to the **oncontentready** event.

```
<PUBLIC:ATTACH EVENT="oncontentready" ONEVENT="show innerHTML()" />
<SCRIPT LANGUAGE="JScript">
```

```
function show_innerHTML()
{
    window.alert ('innerHTML = ' + element.innerHTML);
}
</SCRIPT>
```

This event is specific to HTC and element behaviors.

2.3.4.14 oncontentsave

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

oncontentsave of type `Function`

Occurs just before the content of a master element is saved or copied.

This event is specific to HTC and element behaviors

2.3.4.15 oncontrolselect

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

oncontrolselect of type `Function`

Occurs when the user is about to make a control selection in an editable region.

To invoke, select the control.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: altKey, shiftKey

This attribute is an extension of [HTMLElement](#).

See also [onselect](#), [onselectstart](#).

2.3.4.16 oncopy

oncopy of type `Function`

Occurs on the source element when the user copies the object or selection, adding it to the system clipboard.

To invoke, right-click and select **Copy** from the shortcut menu, or press Ctrl+C.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: dataTransfer

This attribute is an extension of [HTMLElement](#).

See also [onbeforecopy](#), [oncut](#), [onpaste](#).

2.3.4.17 **oncut**

oncut of type `Function`

Occurs on the source element when the object or selection is removed from the document and added to the system clipboard.

To invoke, right-click and select **Cut** from the shortcut menu, or press Ctrl+X.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: `dataTransfer`

This attribute is an extension of [HTMLInputElement](#).

See also [onbeforecut](#), [oncopy](#), [onpaste](#).

2.3.4.18 **ondataavailable**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

ondataavailable of type `Function`

Occurs periodically as data arrives from data source objects that asynchronously transmit data.

To invoke, request new data from the data source.

- Bubbles: Yes
- Cancelable: No
- Context Info: `recordset`

This attribute is an extension to [HTMLInputElement](#).

See also [ondataavailable](#), [ondataavailable](#).

2.3.4.19 **ondataavailable**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

ondataavailable of type `Function`

Occurs when the data set exposed by a data source object changes.

To invoke, make initial data available from a data source object, expose a different data set, or perform a filter operation.

- Bubbles: Yes
- Cancelable: No
- Context Info: `qualifier`, `reason`, `recordset`

This attribute is an extension to [HTMLInputElement](#).

See also [ondataavailable](#), [ondataavailable](#).

2.3.4.20 **ondatasetcomplete**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

ondatasetcomplete of type `Function`

Occurs when all data is available from the data source object.

To invoke, allow data set change to complete.

- Bubbles: Yes
- Cancelable: No
- Context Info: qualifier, reason, recordset

This attribute is an extension of [HTMLInputElement](#).

See also [ondataavailable](#), [ondatasetchanged](#).

2.3.4.21 **ondeactivate**

ondeactivate of type `Function`

Occurs when the active element is changed from the current object.

To invoke, click an element (other than the active element), use the keyboard to move focus, or invoke the `focus()` method.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: `fromElement`, `srcElement`

This attribute is an extension to [HTMLInputElement](#).

See also [onactivate](#), [onbeforedeactivate](#).

2.3.4.22 **ondetach**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

ondetach of type `Function`

Occurs before a behavior is detached from an element.

This event provides an opportunity for a dynamically attached behavior to stop receiving notifications from the page. Any behavior that attaches with [PUBLIC:ATTACH](#) will automatically stop receiving notifications when the behavior is detached.

This event is specific to HTC and element behaviors.

2.3.4.23 **ondocumentready**

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

ondocumentready of type `Function`

Occurs when the primary document that contains the behavior has been parsed completely.

This event is specific to HTC and element behaviors.

2.3.4.24 onerrorupdate

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

onerrorupdate of type `Function`

Occurs when an error occurs while updating the associated data in the data source object.

To invoke, cancel the data transfer, or return `false` from `onbeforeupdate` event handler.

- Bubbles: Yes
- Cancelable: No
- Context Info: None

This attribute is an extension to [HTMLElement](#).

See also [onbeforeupdate](#), [onafterupdate](#).

2.3.4.25 onfilterchange

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onfilterchange of type `Function`

Occurs when a visual filter changes state or completes a transition.

To invoke, change the filter state.

- Bubbles: No
- Cancelable: No
- Context Info: `srcFilter`

This attribute is an extension to [HTMLElement](#).

2.3.4.26 onfinish

onfinish of type `Function`

Occurs when marquee looping is complete.

To invoke, specify a value for the **loop** attribute of the marquee.

- Bubbles: No
- Cancelable: Yes
- Context Info: None

The **onfinish** attribute extends the [HTMLMarqueeElement](#) interface.

2.3.4.27 onfocusin

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

onfocusin of type `Function`

Occurs just prior to setting focus on an element.

To invoke, click an element or document when the element or document does not have focus; use the keyboard to move focus; invoke the **focus** method.

- Bubbles: Yes
- Cancelable: No
- Context Info: `fromElement`

This attribute is an extension to [HTMLElement](#).

See also [onfocusout](#).

2.3.4.28 onfocusout

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

onfocusout of type `Function`

Occurs immediately after moving focus to another element.

To invoke, click an element or document when the element or document does not have focus; use the keyboard to move focus; invoke the **focus** method.

- Bubbles: Yes
- Cancelable: No
- Context Info: `toElement`

This attribute is an extension to [HTMLElement](#).

See also [onfocusin](#).

2.3.4.29 onhelp

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onhelp of type `Function`

Occurs when the user presses the F1 key while the browser is the active window.

To invoke, press the F1 key.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: `srcElement`

This attribute is an extension to [HTMLElement](#).

2.3.4.30 onlosecapture

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onlosecapture of type `Function`

Occurs when an object loses the mouse capture.

To invoke, set mouse capture to a different object, change the active window, or invoke the **releaseCapture** method on the document or object.

- Bubbles: No
- Cancelable: No
- Context Info: None

This attribute is an extension to [HTMLElement](#).

2.3.4.31 onmouseenter

onmouseenter of type `Function`

Occurs when the user moves the mouse pointer into the object.

To invoke, move the mouse pointer inside the boundaries of an object.

- Bubbles: No
- Cancelable: No
- Context Info: fromElement, toElement

This attribute is an extension to [HTMLElement](#).

See also [onmouseleave](#).

2.3.4.32 onmouseleave

onmouseleave of type `Function`

Occurs when the user moves the mouse pointer outside the object.

To invoke, move the mouse pointer outside the boundaries of an object.

- Bubbles: No
- Cancelable: No
- Context Info: fromElement, toElement

This attribute is an extension to [HTMLElement](#).

See also [onmouseenter](#).

2.3.4.33 onmove

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onmove of type `Function`

Occurs when the object is moved.

To invoke, change the absolute position of an object.

- Bubbles: Yes
- Cancelable: No
- Context Info: None

This attribute is an extension to [HTMLElement](#).

2.3.4.34 onmoveend

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onmoveend of type `Function`

Occurs when an editable object stops moving.

To invoke, stop moving the editable object.

- Bubbles: Yes
- Cancelable: No
- Context Info: None

This attribute is an extension to [HTMLElement](#).

See also [onmovestart](#).

2.3.4.35 onmovestart

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onmovestart of type `Function`

Occurs when an editable object starts to move.

To invoke, start moving the editable object.

- Bubbles: Yes
- Cancelable: No
- Context Info: None

This attribute is an extension to [HTMLElement](#).

See also [onmoveend](#).

2.3.4.36 onpaste

onpaste of type `Function`

Occurs when the user pastes data, transferring the data from the system clipboard to the document.

To invoke after copying or cutting text, right-click and select **Paste** from the shortcut menu, or press Ctrl+V.

- Bubbles: Yes
- Cancelable: Yes

- Context Info: dataTransfer

This attribute is an extension to [HTMLElement](#).

See also [onbeforecopy](#), [onbeforecut](#), [onbeforepaste](#), [oncopy](#), [oncut](#).

2.3.4.37 onpropertychange

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onpropertychange of type `Function`

Occurs when a property changes on the object.

To invoke, cause a property to change value.

- Bubbles: No
- Cancelable: No
- Context Info: propertyName

This attribute is an extension to [HTMLElement](#).

2.3.4.38 onresizeend

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onresizeend of type `Function`

Occurs when the user finishes changing the dimensions of the object in a control selection.

To invoke, release the sizing handle of the selected control. By default, the object's display area conforms to the coordinates of the sizing handles when the operation is complete.

- Bubbles: Yes
- Cancelable: No
- Context Info: None

This attribute is an extension to [HTMLElement](#).

2.3.4.39 onresizestart

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

onresizestart of type `Function`

Occurs when the user begins to change the dimensions of the object in a control selection.

To invoke, drag one of the sizing handles of an object in a control selection.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: None

This attribute is an extension to [HTMLElement](#).

2.3.4.40 **onrowenter**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

onrowenter of type `Function`

Occurs when the current row has changed in the data source and new data values are available on the object in the current row.

To invoke, change data values in the current row.

- Bubbles: Yes
- Cancelable: No
- Context Info: qualifier, recordset

This attribute is an extension to [HTMLInputElement](#).

See also [onrowexit](#).

2.3.4.41 **onrowexit**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

onrowexit of type `Function`

Occurs just before the data source control changes the current row in the object. By default, signals that the row in the databound object is about to be changed.

To invoke, change rows in the data source.

- Bubbles: No
- Cancelable: Yes
- Context Info: qualifier, recordset

This attribute is an extension to [HTMLInputElement](#).

See also [onrowenter](#).

2.3.4.42 **onrowsdelete**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

onrowsdelete of type `Function`

Occurs when rows are about to be deleted from the recordset, signaling that the rows are about to be deleted.

Invoked when the **delete** method is called on the recordset.

- Bubbles: Yes
- Cancelable: No
- Context Info: qualifier, recordset

This attribute is an extension to [HTMLInputElement](#).

2.3.4.43 **onrowsinserted**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, and IE10 Mode (All Versions)

onrowsinserted of type `Function`

Occurs just after new rows are inserted in the current recordset, signaling that a new row has been inserted.

Invoked when the **AddNew** method (ADO) is called on the current recordset.

- Bubbles: Yes
- Cancelable: No
- Context Info: reason, recordset

This attribute is an extension to [HTMLInputElement](#).

2.3.4.44 **onselect**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

onselect of type `Function`

Occurs when the current selection changes. By default, moves the selection to a given character and highlights that selection.

To invoke, move the mouse from character to character during a drag selection, or press the SHIFT key while moving the cursor over text.

- Bubbles: No
- Cancelable: Yes
- Context Info: None

The **onselect** attribute extends the [HTMLBodyElement](#) interface

See also [onselectstart](#).

2.3.4.45 **onselectstart**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

onselectstart of type `Function`

Occurs as the object is being selected.

To invoke, begin selecting one or more objects.

- Bubbles: Yes
- Cancelable: Yes
- Context Info: offsetX, offsetY

This attribute is an extension to [HTMLInputElement](#).

See also [onselect](#).

2.3.4.46 **onstart**

onstart of type `Function`

Occurs at the beginning of every loop of the marquee.

To invoke, either set the **loop** attribute to 1 or higher for a set number of loops, or omit the **loop** attribute so that the marquee loops indefinitely.

- Bubbles: No
- Cancelable: No
- Context info: None

The **onstart** attribute extends the [HTMLMarqueeElement](#) interface.

2.4 Methods

The following methods are extensions to [\[HTML\]](#):

- [add\(\)](#)
- [item\(\)](#)
- [moveRow\(\)](#)
- [namedItem\(\)](#)
- [remove\(\)](#)
- [setActive\(\)](#)
- [tags\(\)](#)
- [urns\(\)](#)

2.4.1 **add**

Adds an element to the areas, controlRange, or options collection.

The **add** method extends the [HTMLAreasCollection](#) interface.

Parameters

oElement of type `HTMLElement`

Required. **Element** that specifies the element to add to the collection.

oBefore of type `any`

Optional. **Object** that specifies an element before which to insert, or an **Integer** that specifies the index position in the collection where the element is placed. If no value is given, the object is appended to the end of the collection.

In IE7 Mode, `oBefore` only accepts an **Integer**.

No Return Value

No JScript Error

2.4.2 item

Note: EdgeHTML Mode does not provide the **item** method for the [HTMLSelectElement](#) interface.

Retrieves an object from various collections, including the **all** collection.

The **item** method extends the following interfaces:

All Document Modes (All Versions)

- [HTMLFormElement](#)

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

- HTMLSelectElement

All Document Modes (Internet Explorer 8) The `iSubindex` parameter is not used.

The **item** method cannot retrieve `input type=image` elements from a form. To access all elements contained in a form, use the **children** collection.

Parameters

index of type `DOMString`

Specifies the object or collection to retrieve. If this parameter is a number, it is the zero-based index of the object. If this parameter is a string, all objects with matching **name** or **id** properties are retrieved, and a collection is returned if more than one match is made.

iSubindex of type `long`

Optional. Specifies the zero-based index of the object to retrieve when a collection is returned.

Return Value

Returns an object or a collection of objects if successful, or null otherwise.

No JScript Error

2.4.3 moveRow

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

Moves a table row to a new position. Rows between the `iSource` and `iTarget` positions in the **rows** collection are shifted based on the direction the row moves.

The **moveRow** method extends the following interfaces:

- [HTMLTableElement](#)
- [HTMLTableSectionElement](#)

Parameters

iSource of type `long`

Specifies the index in the **rows** collection of the table row that is moved. The default value is -1.

iTarget of type `long`

Specifies where the row is moved within the **rows** collection. The default value is -1.

Return Value

Object. Returns a reference to the table row that is moved.

No JScript Error

2.4.4 **namedItem**

Retrieves an object or a collection from a specified collection. The **namedItem** method first searches for an object with a matching `id` attribute. If a match is not found, the method searches for an object with a matching `name` attribute, but only on those elements that are allowed a `name` attribute.

The **namedItem** method extends the following interfaces:

- [HTMLFormElement](#)
- [HTMLSelectElement](#)

All Document Modes (Internet Explorer 8) The **namedItem** method does not return collections if more than one named item is found; instead, it returns the first case-insensitive matched element.

Parameters

sName of type `DOMString`

Specifies the **name** or **id** property of the object to retrieve. A collection is returned if more than one match is made.

Return Value

Returns an object or a collection of objects if successful, or null otherwise.

No JScript Error

2.4.5 **remove**

Removes an element from the collection.

The **remove** method extends the [HTMLAreasCollection](#) interface.

Parameters

iIndex of type `long`

Specifies the zero-based index of the element to remove from the collection.

No Return Value

No JScript Error

2.4.6 **setActive**

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

Sets the object as active without setting focus to the object.

The **setActive** method extends the [HTMLElement](#) interface.

See also [onactivate](#), [onbeforeactivate](#), [onbeforedeactivate](#), [ondeactivate](#).

2.4.7 tags

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

Retrieves a collection of objects that have the specified HTML tag name.

The **tags** method extends the following interfaces:

- [HTMLAreasCollection](#)
- [HTMLCollection](#)
- [HTMLFormElement](#)
- [HTMLSelectElement](#)

Parameters

sTag of type `DOMString`

Specifies an HTML tag. It can be any one of the **elements** exposed by the DHTML Object Model.

Return Value

Returns a collection of element objects if successful, or null otherwise.

Successful execution includes the case where no elements having the given name are found. In this case, a collection containing zero elements is returned.

The **length** property of the collection contains the number of elements in the collection.

Null may be returned in cases where the collection cannot be constructed, such as inability to allocate memory for even a zero-length collection.

No JScript Error

2.4.8 urns

Quirks Mode, IE7 Mode, IE8 Mode, and IE9 Mode (All Versions)

Retrieves a collection of all objects to which a specified behavior is attached.

The **urns** method extends the [HTMLSelectElement](#) interface.

Parameters

sUrn of type `DOMString`

Specifies the behavior's Uniform Resource Name (URN).

Return Value

Returns a collection of objects if successful, or null otherwise.

The **urns** method returns an empty collection if no element has the specified behavior attached to it.

Use the **length** property on the collection to determine the number of elements it contains, and the [item](#) method to obtain a particular item in the collection.

No JScript Error

2.5 Collections

The following collections are extensions to [\[HTML\]](#):

- [all](#)
- [cells](#)
- [frames](#)

2.5.1 all

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, IE11 Mode, and EdgeHTML Mode (All Versions)

all of type **HTMLCollection** (IHTMLElementCollection)

Returns a reference to the collection of elements contained by the specified object.

2.5.2 cells

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

cells of type **HTMLCollection** (IHTMLElementCollection)

Retrieves a collection of all cells in the table row or in the entire table.

2.5.3 frames

Quirks Mode, IE7 Mode, IE8 Mode, IE9 Mode, IE10 Mode, and IE11 Mode (All Versions)

frames of type **HTMLCollection** (IHTMLFramesCollection2)

Retrieves a collection of all window objects defined by the given document or defined by the document associated with the given window.

3 Security Considerations

There are no additional security considerations.

4 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs.

- Windows Internet Explorer 7
- Windows Internet Explorer 8
- Windows Internet Explorer 9
- Windows Internet Explorer 10
- Internet Explorer 11
- Microsoft Edge

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

5 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

6 Index

A

[Applicability](#) 18

Attributes

Content Only

[application](#) 80
[atomicselection](#) 80
[event](#) 80
[for](#) 81
[get](#) 81
[implementation](#) 81
[internalName](#) 82
[lightWeight](#) 82
[literalContent](#) 82
[namespace](#) 83
[onevent](#) 83
[persist](#) 83
[put](#) 84
[supportsEditMode](#) 84
[tagName](#) 84
[unselectable](#) 84
[viewLinkContent](#) 84
[xmlns](#) 85

DOM and Content

[action](#) 51
[align](#) 52
[allowTransparency](#) 52
[alt](#) 53
[background](#) 53
[BaseHref](#) 53
[behavior](#) 53
[bgColor](#) 54
[bgProperties](#) 54
[border](#) 54
[borderColor](#) 54
[borderColorDark](#) 55
[borderColorLight](#) 55
[bottomMargin](#) 56
[canHaveHTML](#) 56
[charset](#) 56
[classid](#) 56
[clear](#) 56
[color](#) 57
[cols](#) 57
[dataFld](#) 57
[dataFormatAs](#) 58
[dataPageSize](#) 59
[dataSrc](#) 59
[direction](#) 60
[dynsrc](#) 60
[frameBorder](#) 60
[frameSpacing](#) 61
[height](#) 61
[href](#) 62
[hspace](#) 62
[leftMargin](#) 62
[loop](#) 63
[lowsrc](#) 63
[Methods](#) 64
[name](#) 64
[noResize](#) 64
[noWrap](#) 64

[rightMargin](#) ([section 2.3.1.38](#) 64, [section 2.3.1.39](#) 65)

[scroll](#) 65
[scrollAmount](#) 65
[scrollDelay](#) 66
[start](#) 66
[tabStop](#) 66
[topMargin](#) 66
[trueSpeed](#) 67
[urn](#) 67
[vAlign](#) 67
[value](#) 68
[viewInheritStyle](#) 68
[viewMasterTab](#) 68
[vspace](#) 68
[width](#) 69
[wrap](#) 69

DOM Only

[alinkColor](#) 69
[altHtml](#) 70
[contentWindow](#) 70
[dir](#) 70
[encoding](#) 71
[fgColor](#) 71
[fileCreateDate](#) 71
[fileModifiedDate](#) 71
[fileSize](#) 71
[fileUpdatedDate](#) 72
[hash](#) 72
[host](#) 72
[hostname](#) 72
[indeterminate](#) 73
[isDisabled](#) 73
[isMultiLine](#) 73
[linkColor](#) 73
[mimeType](#) 74
[nameProp](#) 74
[object](#) 75
[parentDocument](#) 75
[pathname](#) 75
[port](#) 75
[protocol](#) ([section 2.3.1.38](#) 64, [section 2.3.2.24](#) 75)
[protocolLong](#) 76
[search](#) 76
[status](#) 76
[styleSheet](#) 77
[uniqueID](#) 77
[uniqueNumber](#) 78
[url](#) 79
[viewLink](#) 79
[vlinkColor](#) 80

Event

[onactivate](#) 85
[onafterupdate](#) ([section 2.3.4.2](#) 86, [section 2.3.4.10](#) 88, [section 2.3.4.12](#) 89, [section 2.3.4.18](#) 91, [section 2.3.4.19](#) 91, [section 2.3.4.20](#) 92, [section 2.3.4.24](#) 93)
[onbeforeactivate](#) 86
[onbeforecopy](#) 86
[onbeforecut](#) 87
[onbeforedeactivate](#) 87
[onbeforeeditfocus](#) 87

[onbeforepaste](#) 88
[onbeforeunload](#) 88
[onbeforeupdate](#) ([section 2.3.4.10](#) 88, [section 2.3.4.12](#) 89, [section 2.3.4.18](#) 91, [section 2.3.4.19](#) 91, [section 2.3.4.20](#) 92, [section 2.3.4.24](#) 93)
[onbounce](#) 89
[oncellchange](#) ([section 2.3.4.12](#) 89, [section 2.3.4.18](#) 91, [section 2.3.4.19](#) 91, [section 2.3.4.20](#) 92, [section 2.3.4.24](#) 93)
[oncontentready](#) 89
[oncontentsave](#) 90
[oncontrolselect](#) 90
[oncopy](#) 90
[oncut](#) 91
[ondataavailable](#) ([section 2.3.4.18](#) 91, [section 2.3.4.19](#) 91, [section 2.3.4.20](#) 92, [section 2.3.4.24](#) 93)
[ondatasetchanged](#) 91
[ondatasetcomplete](#) ([section 2.3.4.19](#) 91, [section 2.3.4.20](#) 92, [section 2.3.4.24](#) 93)
[ondeactivate](#) 92
[ondetach](#) 92
[ondocumentready](#) 92
[onerrorupdate](#) 93
[onfilterchange](#) 93
[onfinish](#) 93
[onfocusin](#) 93
[onfocusout](#) 94
[onhelp](#) 94
[onlosecapture](#) 94
[onmouseenter](#) 95
[onmouseleave](#) 95
[onmove](#) 95
[onmoveend](#) 96
[onmovestart](#) 96
[onpaste](#) 96
[onpropertychange](#) 97
[onresizeend](#) 97
[onresizestart](#) 97
[onrowenter](#) ([section 2.3.1.7](#) 53, [section 2.3.4.40](#) 98, [section 2.3.4.42](#) 98, [section 2.3.4.43](#) 99)
[onrowexit](#) 98
[onrowsdelete](#) ([section 2.3.1.7](#) 53, [section 2.3.4.42](#) 98, [section 2.3.4.43](#) 99)
[onrowsinserted](#) ([section 2.3.1.7](#) 53, [section 2.3.4.43](#) 99)
[onselect](#) 99
[onselectstart](#) 99
[onstart](#) 100

C

[Change tracking](#) 107
Collections
 [all](#) 104
 [cells](#) 104
 [frames](#) 104

E

Elements
 ?import? ([section 1.5](#) 18, [section 2.1.1](#) 20)
 [comment](#) 21
 [marquee](#) 21

[noBR](#) 22
[PUBLIC:ATTACH](#) 22
[PUBLIC:COMPONENT](#) 22
[PUBLIC:DEFAULTS](#) 23
[PUBLIC:EVENT](#) 23
[PUBLIC:METHOD](#) 23
[PUBLIC:PROPERTY](#) 24

G

[Glossary](#) 8

I

[Implementer - security considerations](#) 105
[Informative references](#) 8

Interfaces

HTCComponentElement ([section 1.3.1](#) 16, [section 2.2.1.1](#) 26, [section 2.2.1.6](#) 27, [section 2.2.1.7](#) 27, [section 2.2.2.6](#) 32, [section 2.2.2.19](#) 39, [section 2.2.2.20](#) 40, [section 2.2.2.22](#) 40, [section 2.2.2.29](#) 43, [section 2.2.2.31](#) 44, [section 2.2.2.34](#) 45, [section 2.3.1.1](#) 51, [section 2.3.1.3](#) 52, [section 2.3.1.5](#) 53, [section 2.3.1.11](#) 54, [section 2.3.1.12](#) 55, [section 2.3.1.13](#) 55, [section 2.3.1.14](#) 56, [section 2.3.1.21](#) 57, [section 2.3.1.22](#) 58, [section 2.3.1.23](#) 59, [section 2.3.1.24](#) 59, [section 2.3.1.26](#) 60, [section 2.3.1.30](#) 62, [section 2.3.1.32](#) 62, [section 2.3.1.33](#) 63, [section 2.3.1.38](#) 64, [section 2.3.1.39](#) 65, [section 2.3.1.40](#) 65, [section 2.3.1.43](#) 66, [section 2.3.1.45](#) 66, [section 2.3.1.47](#) 67, [section 2.3.2.4](#) 70, [section 2.3.2.7](#) 71, [section 2.3.2.8](#) 71, [section 2.3.2.9](#) 71, [section 2.3.2.10](#) 72, [section 2.3.2.15](#) 73, [section 2.3.2.16](#) 73, [section 2.3.2.18](#) 74, [section 2.3.2.19](#) 74, [section 2.3.2.21](#) 75, [section 2.3.2.24](#) 75, [section 2.3.2.28](#) 77, [section 2.3.2.29](#) 77, [section 2.3.2.30](#) 78, [section 2.3.2.33](#) 80, [section 2.3.3](#) 80, [section 2.3.3.1](#) 80, [section 2.3.3.2](#) 80, [section 2.3.3.5](#) 81, [section 2.3.3.7](#) 82, [section 2.3.3.10](#) 83, [section 2.3.3.11](#) 83, [section 2.3.3.12](#) 83, [section 2.3.3.13](#) 84, [section 2.3.3.16](#) 84, [section 2.3.4.2](#) 86, [section 2.3.4.7](#) 87, [section 2.3.4.9](#) 88, [section 2.3.4.10](#) 88, [section 2.3.4.12](#) 89, [section 2.3.4.15](#) 90, [section 2.3.4.18](#) 91, [section 2.3.4.19](#) 91, [section 2.3.4.20](#) 92, [section 2.3.4.24](#) 93, [section 2.3.4.25](#) 93, [section 2.3.4.27](#) 93, [section 2.3.4.28](#) 94, [section 2.3.4.29](#) 94, [section 2.3.4.30](#) 94, [section 2.3.4.33](#) 95, [section 2.3.4.34](#) 96, [section 2.3.4.35](#) 96, [section 2.3.4.37](#) 97, [section 2.3.4.38](#) 97, [section 2.3.4.39](#) 97, [section 2.3.4.40](#) 98, [section 2.3.4.41](#) 98, [section 2.3.4.42](#) 98, [section 2.3.4.43](#) 99, [section 2.3.4.44](#) 99, [section 2.3.4.45](#) 99, [section 2.4.2](#) 101, [section 2.4.3](#) 101, [section 2.4.6](#) 102, [section 2.5.1](#) 104, [section 2.5.2](#) 104, [section 2.5.3](#) 104)

[HTCElementBehaviorDefaults](#) 26
[HTCPropertyElement](#) 26
[HTMLAnchorElement](#) 29
[HTMLAreaElement](#) 30
[HTMLAreasCollection](#) 30

[HTMLBlockElement](#) 26
[HTMLBodyElement](#) 31
[HTMLButtonElement](#) 31
[HTMLCollection](#) 32
[HTMLCommentElement](#) 26
[HTMLDDElement](#) 27
[HTMLDivElement](#) 32
[HTMLDocument](#) 32
[HTMLDTEElement](#) 27
[HTMLElement](#) 33
[HTMLFieldSetElement](#) 34
[HTMLFormElement](#) 35
[HTMLFrameElement](#) 35
[HTMLFrameSetElement](#) 36
[HTMLHeadingElement](#) 36
[HTMLHRElement](#) 37
[HTMLIFrameElement](#) 37
[HTMLImageElement](#) 38
[HTMLInputElement](#) 38
[HTMLIsIndexElement](#) 39
[HTMLLabelElement](#) 40
[HTMLLegendElement](#) 40
[HTMLLinkElement](#) 40
[HTMLMarqueeElement](#) 28
[HTMLMetaElement](#) 41
[HTMLObjectElement](#) 41
[HTMLOptionElement](#) 42
[HTMLParagraphElement](#) 42
[HTMLSelectElement](#) 42
[HTMLSpanElement](#) 43
[HTMLStyleElement](#) 43
[HTMLTableCaptionElement](#) 43
[HTMLTableCellElement](#) 44
[HTMLTableElement](#) 44
[HTMLTableRowElement](#) 45
[HTMLTableSectionElement](#) 45
[HTMLTextAreaElement](#) 46
[Introduction](#) 8

M

Methods

[add](#) 100
[item](#) 101
[moveRow](#) ([section 2.4.2](#) 101, [section 2.4.3](#) 101)
[namedItem](#) 102
[remove](#) 102
[setActive](#) 102
[tags](#) 103
[urns](#) 103

N

[Normative references](#) 8

O

[Overview \(synopsis\)](#) 9

P

[Product behavior](#) 106

R

[References](#) 8
[informative](#) 8
[normative](#) 8

S

[Security - implementer considerations](#) 105

T

[Tracking changes](#) 107